

Imports

```
import java.sql.SQLException;
import sqlj.runtime.ExecutionContext;
import sqlj.runtime.ConnectionContext;
import sqlj.runtime.ResultSetIterator;
import sqlj.runtime.ref.DefaultContext;
import oracle.sql.runtime.Oracle;
```

Fundamental SQLJ Syntax

Statements

```
#sql { ...SQL code...}; // Use static default connection
#sql [ctx] {...SQL code...}; // Use context instance ctx
```

Bind Variables, Bind Expressions

```
#sql { ... :inVar ... :OUT outVar ... :INOUT inoutVar ...};
#sql { ... :(inExp) ... :OUT (outExp) ... :INOUT (ioExp) ...};
```

Declarations

```
#sql modifiers context ContextName;
#sql modifiers iterator IteratorName(...);
Must be placed where classes may legally be declared. Use
public static modifiers for inner class declarations.
```

Connections

Static Default Connection

```
Oracle.connect(Oracle_URL, user, password);
...
Oracle.close();
```

This is equivalent to the following.

```
java.sql.DriverManager.registerDriver
    (new oracle.jdbc.driver.OracleDriver());
java.sql.Connection conn =
    java.sql.DriverManager.getConnection
        (Oracle_URL, user, password);
conn.setAutoCommit(false);
DefaultContext.setDefaultContext
    (new DefaultContext(conn));
...
DefaultContext.getDefaultContext().close();
```

Other Connect Signatures

```
(Oracle_URL_with_user_and_password),
(JDBC_Connection), (SQLJ_context),
(Class_denoting_package, 'properties_file_name'), ...
```

Some Oracle URLs

```
"jdbc:oracle:thin:@hostname:port:database_SID"
    - thin JDBC driver
"jdbc:oracle:oci8:@tns_alias_name"
    - JDBC-OCI driver
"jdbc:oracle:kprb:" - server-side JDBC driver
```

Connection Context Instance ctx

Use DefaultContext or declare a context class
#sql context MyCtx; // **public static** for an inner class

Create a context instance

```
MyCtx ctx = // last argument specifies autocommit
    new MyCtx(Oracle_URL, user, password, false);
...
ctx.close(); // close(false) to keep JDBC connection
```

Use a DataSource

```
// autocommit is inherited from the data source
#sql context DSCtx
    with (dataSource="JNDI_name_of_data_source");
DSCtx ctx = new DSCtx(user, password);
...
ctx.close(); // close(false) to keep JDBC connection
```

JDBC Interoperability

```
java.sql.Connection conn = DefaultContext
    .getObjectContext().getConnection();
// or
conn = ctx.getConnection();
// and (note that autocommit is inherited from conn)
MyCtx ctx = new MyCtx(conn);
```

Queries

Single-Row Select

```
#sql { SELECT FROM tab
    INTO :x1, :x2, ... WHERE ...};
```

Named Iterators

```
#sql iterator NamedIter (String col1, int col2, ...);
...
// use public static for inner class
NamedIter ni;
#sql ni = { SELECT col1, col2, ...
    FROM tab WHERE ...};
while (ni.next()) {
    ...process... ni.col1() ... ni.col2() ...
}
ni.close();
```

Positional Iterators

```
#sql iterator PosIter (String, int, ...);
...
// use public static for inner class
PosIter pi; String x1=null; int x2=0;
#sql pi = { SELECT col1, col2, ...
    FROM tab WHERE ...};
while (true) {
    #sql { FETCH FROM :pi INTO :x1, :x2, ...};
    if (pi.endFetch()) break;
    ...process...x1...x2...
}
pi.close();
```

ResultSet Iterators

```
ResultSetIterator rsi; String x1; int x2; ...
#sql rsi = { SELECT col1, col2, ...
    FROM tab WHERE ...};
while (rsi.next()) {
    #sql { FETCH CURRENT FROM :rsi
    INTO :x1, :x2, ...};
    ...process...x1...x2...
}
rsi.close();
```

Scrollable Iterators

```
#sql iterator Iter
    implements sqlj.runtime.Scrollable (...);
// or use
sqlj.runtime.ScrollableResultIterator sri;
```

Predicates

```
isFirst(), isLast(), isBeforeFirst(), isAfterLast().
```

Movement Methods

```
previous(), first(), last(), beforeFirst(), afterLast(),
absolute(int), relative(int).
```

Positional Movement and Fetch Syntax

```
FETCH [ NEXT | PRIOR | CURRENT | FIRST
    | LAST | ABSOLUTE :x | RELATIVE :x ]
    FROM :pi INTO :x1, :x2 ...
```

JDBC Interoperability

```
java.sql.ResultSet rs = ...; Iter iter = ...;
// SQLJ iterator from result set
#sql iter = { CAST :rs }; ...process iter...; iter.close();
// result set from SQLJ iterator
rs = iter.getResultSet(); ...process rs...; iter.close();
```

Statements

Stored Procedures and Functions

```
#sql { CALL Stored_Procedure(...); };
#sql assignable_expr =
    { VALUES( Stored_Function(...) ) };
```

SQL Expressions and PL/SQL

```
#sql { SET :outputVar = ...SQL expression... };
#sql { BEGIN ... END; };
#sql { DECLARE ... BEGIN ... END; }
```

Transaction Control

```
#sql { SET TRANSACTION ISOLATION
    READ COMMITTED }; // default setting!
#sql { SET TRANSACTION ISOLATION
    SERIALIZABLE };
#sql { ROLLBACK }; // Use these instead of the
#sql { COMMIT }; // JDBC methods!
```

Dynamic SQL

```
#sql { ... :{runtime_expr} ... };
#sql { ... :{runtime_expr} :: translate_time_SQL ... };
Example: String table="emp2"; String col="comm";
#sql { select :{col}::sal INTO :x FROM :{table}::emp };
```

Execution Contexts

Create new or obtain it from a context
ExecutionContext ec = new ExecutionContext(); // or
ec = ctx.getExecutionContext(); // or
ec = DefaultContext.getDefaultContext()
 .getExecutionContext();

APIs to set up execution properties
get/setMaxFieldSize() -max. size in bytes

```
get/setMaxRows() - max. rows returned in result set
get/setQueryTimeout() - timeout in seconds, default 0
get/setFetchSize() - result set prefetch size, default 10
get/setFetchDirection() - default FETCH_FORWARD
is/setBatching() - default is false (batching off)
get/setBatchLimit() - default 0 (=UNLIMITED_BATCH)
```

Execute with explicit context ec

```
#sql [ec] { ... };
```

APIs to control execution

```
executeBatch() - execute pending batch (if any) and
    return the batch update counts
cancel() - cancel execution, cancel pending batch
```

APIs to retrieve execution results

```
getUpdateCount() - return number of rows updated or:
    - QUERY_COUNT (-1) - query execution
    - EXCEPTION_COUNT (-2) - exception occurred
    - NEW_BATCH_COUNT (-3) - new batch created
    - ADD_BATCH_COUNT (-4) - stmt. added to batch
    - EXEC_BATCH_COUNT (-5) - batch was executed
getBatchUpdateCounts() - after executing n batches
    statements: int[] with n elements containing -2 each
```

Type Support

Streams

For LONG columns use Ascii/UnicodeStream
sqlj.runtime.AsciiStream as =
 new sqlj.runtime.AsciiStream
 (input_stream, input_stream_length);
// For LONG RAW columns use BinaryStream

Retrieving streams

```
#sql { SELECT col INTO :as FROM stream_tab };
int len=as.getLength(); int c;
while((c= as.read()) != -1) System.out.println((char)c);
as.close();
```

Stream Limitations

- positional iterators/ResultSetIterators:
 only one long column, which must also be the last
 - named iterators:
 column processing must obey the select-list order

LOBs

Reading LOBs

```
oracle.sql.BLOB blob; oracle.sql.CLOB blob;
oracle.sql.BFILE bfile;
```

```
...
// Note: the index starts from 1 (not from 0)
byte[] b = blob.getBytes(begin_index, length);
String s = blob.getString(begin_index, length);
b = bfile.getBytes(begin_index, length);
```

```
java.io.InputStream is = blob.getBinaryStream();
is = blob.getAsciiStream();
is = bfile.getBinaryStream();
```

Write data into LOB

Create and select empty_lob(), except for JDBC-OCI.

```
byte[ ] b = ... ; String s = ...;
int amount_written = blob.putBytes(begin_index, b);
amount_written = clob.putString(begin_index,s);
```

Replace the LOB content from a stream
 Writer w = clob.getCharacterOutputStream();
 OutputStream os = clob.getAsciiOutputStream();
 os = blob.getBinaryOutputStream();

SQL-Java Type Compatibility

SQL Types	Java Types
NUMBER and all numeric types	boolean, Boolean, byte, Byte, short, Short, int, Integer, long, Long, float, Float, double, Double, String, java.math.BigDecimal, oracle.sql.NUMBER,
CHAR, VARCHAR2, LONG	String, oracle.sql.CHAR, sqj.runtime.Stream, sqj.runtime.UnicodeStream
RAW, LONG RAW	byte[], oracle.sql.RAW, sqj.runtime.BinaryStream
DATE	java.sql.Date, java.sql.Time, java.sql.Timestamp, oracle.sql.DATE
BLOB	java.sql.Blob*, oracle.sql.BLOB, sqj.runtime.BinaryStream**
CLOB	java.sql.Clob*, oracle.sql.CLOB, sqj.runtime.Stream**, sqj.runtime.UnicodeStream**
BFILE	oracle.sql.BFILE
ROWID	oracle.sql.ROWID
REF CURSOR	java.sql.ResultSet, SQLJ iterator instance
user-defined object	java.sql.Struct*, oracle.sql.STRUCT***, java.sql.SQLData* implementation, oracle.sql.ORADATA impl.
user-defined reference	java.sql.Ref, oracle.sql.REF***, oracle.sql.ORADATA implementation
user-defined collection	java.sql.Array, oracle.sql.ARRAY***, oracle.sql.ORADATA implementation

* Type requires JDBC 2.0 or later (JDK 1.2 and above).

** Streaming to database only supported in JDBC-OCI.

*** Not supported as OUT, INOUT, or return parameter.

Object Type Support

Introduction to Object support

Use implementations of oracle.sql.ORADATA in Java to read and write instances of SQL Object Types.
 Define SQL Object Types (schema SCOTT)
 CREATE TYPE ADDRESS AS OBJECT
 (street VARCHAR2(40));
 CREATE TYPE PERSON AS OBJECT
 (name VARCHAR2(20), paddr ADDRESS);
 CREATE TABLE PTAB AS TABLE OF PERSON;
 CREATE TABLE ATAB
 (addr ADDRESS, zip VARCHAR2(9));
 Generate Java Wrappers with JPublisher
 jpub -user=scott/tiger \
 -sql=ADDRESS:JAddress,PERSON:JPerson
 javac JAddress.* JPPerson.* # use sqlj for .sqlj files

Use Java Wrappers in Test.sqlj

```
public class Test {  

  public static void main(String[] args)  

    throws SQLException  

{ Oracle.connect("jdbc:oracle:oci8:@","scott","tiger");  

  JAddress a; JPson p = new JPson();  

  p.setName("John");  

#sql { INSERT INTO PTABLE VALUES(:p) };  

#sql { SELECT addr INTO :a FROM ATAB  

      WHERE zip='12345' };  

... } } // To compile and run: sqlj Test.sqlj; java Test
```

SQLJ ISO Object Support

Using java.sql.SQLData from JDBC 2.0.
 Create Java Wrappers With JPublisher
 jpub -usertypes=jdbc -user=scott/tiger \
 -sql=ADDRESS:IsoAddress,PERSON:IsoPerson
 javac IsoAddress.* IsoPerson.*
 Create Type Map isoMap.properties
 class.IsoAddress=STRUCT SCOTT.ADDRESS
 class.IsoPerson=STRUCT SCOTT.PERSON

Use SQLData Wrappers in Iso.sqlj

```
public class Iso {  

#sql public static IsoCtx with (typeMap="isoMap");  

public static void main(String[] args)  

  throws SQLException  

{ new oracle.jdbc.driver.OracleDriver();  

  IsoCtx ctx = new IsoCtx  

  ("jdbc:oracle:oci8:@","scott","tiger",false);  

  IsoAddress a; IsoPerson p = new IsoPerson();  

  p.setName("John");  

#sql [ctx] { INSERT INTO PTAB VALUES(:p) };  

#sql [ctx] { SELECT addr INTO :a FROM ATAB  

      WHERE zip='12345' };  

... } } // To compile and run: sqlj Iso.sqlj; java Iso
```

SQLJ Translator

CLASSPATH with Oracle 9i JDBC

JDK 1.1: translator.zip, runtime11.zip, classes111.zip.
 JDK 1.2 or 1.3: translator.zip, runtime12.zip,
 classes12.zip.

sqlj [options] *.java *.sqlj

- user user/password -url url
 - connect to database at translate time as user
- d directory
 - place .class and .ser files under directory
- codegen=oracle
 - generate Oracle 9i JDBC code (no .ser files)
- version-long, -help, -help-long
 - show version and environment, give help
- explain, -status
 - additional translation help and status messages
- linemap
 - map generated .class files to ..sqlj source files

sqlj [options] *.jar *.ser

- P-debug
 - add debugging auditor
- P-Cstmtcache=n
 - set SQLJ statement cache size n

Tools Reference

jpub [options]

- user=user/password -url=url
 - connect to database as user
- sql=sql_name:java_name
 - generate Java wrapper java_name for sql_name
- package=package
 - use package for generated classes
- usertypes=[oracle|jdbc]
 - generate ORADATA (SQLData) implementation
- methods=[always|false|true]
 - generate .sqlj files/.java files/.sqlj files iff methods
- input=file
 - read input for JPublisher translation from file

loadjava [options] *.jar

- *.sqlj *.java *.ser *.properties
- user user/password[@host:port:sid] [-thin]
 - connect to database as user. Default: JDBC-OCI.
- resolve
 - force immediate class resolution
- verbose
 - print out what loadjava is doing
- dropjava -user ...
 - verbose *.jar *.xxxx
 - drop classes and files
- Tips for SQLJ translation prior to using loadjava
 - use -d directory to collect all .class and .ser files
 - optionally use -ser2class to avoid re-customization
 - optionally use jar to package application
 - remember to copy .properties files, if used!

SQLJ Resources

Oracle Technology Network: <http://technet.oracle.com>
 - Download (Download -> Utility -> SQLJ Translator)
 - Frequently Asked Questions at:
technet.oracle.com/tech/java/sqlj_jdbc/htdocs/faq.html
 - Manuals (<http://technet.oracle.com/docs/content.html>)
 - Demos (download and then look under sqlj/demo)
 - Discussion Forum (Technologies, SQLJ/JDBC)
 Support: <http://www.oracle.com/support/>
 Feedback: helpsqlj_us@oracle.com

