

# **Oracle® Fusion Middleware**

Error Messages Reference

11g Release 1 (11.1.1)

**E10113-05**

January 2011

Oracle Fusion Middleware Error Messages Reference, 11g Release 1 (11.1.1)

E10113-05

Copyright © 2007, 2011, Oracle and/or its affiliates. All rights reserved.

Primary Author: Peter Jacobsen

Contributing Author: Promila Chitkara, Savita Thakur, Janet Blowney, Deb Owens, and Susan Shepard

Contributor: Buddhika Kottahachchi, Vivek Kumar

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications which may create a risk of personal injury. If you use this software in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure the safe use of this software. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software in dangerous applications.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

This software and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.



---

---

# Contents

**Preface** ..... ix

    Audience..... ix

    Documentation Accessibility ..... ix

    Conventions ..... x

- 1 ADF\_FACES-00001 to ADF\_FACES-60098
- 2 ADF-MNC-10000 to ADF-MNC-50073
- 3 ADF\_TRINID-00001 to ADF\_TRINID-30336
- 4 ADFC-00001 to ADFC-14008
- 5 ADFDI-00100 to ADFDI-55516
- 6 ADFF\_BIND-00001 to ADFF\_BIND-00045
- 7 APM-10000 to APM-10015
- 8 ASCRS-00001 to ASCRS-00143
- 9 B2B-50006 to B2B-52331
- 10 BAM-00001 to BAM-07041
- 11 BDSS-00000 to BDSS-65105
- 12 BI-DCBEANS-00001 to BI-DCBEANS-00017
- 13 BI-DCWBSVC-05001 to BI-DCWBSVC-05079
- 14 BI-EUL-00001 to BI-EUL-00002
- 15 BI-PDFRDR-02001 to BI-PDFRDR-02047
- 16 BI-PLUS-00001 to BI-PLUS-00050
- 17 BI-POPVD-00001 to BI-POPVD-00053
- 18 BI-SVR-00300 to BI-SVR-03964
- 19 BI-VIEWER-00001 to BI-VIEWER-01245
- 20 BPM-09708 to BPM-40011
- 21 BRW-15000 to BRW-16976
- 22 CFGFWK-60001 to CFGFWK-72080

- 23 CLONE-27010 to CLONE-28400**
- 24 CONF-30000 to CONF-35141**
- 25 DFW-40004 to DFW-40204**
- 26 DIP-00003 to DIP-87002**
- 27 DISCMAN-00100 to DISCMAN-80213**
- 28 DMS-50700 to DMS-58045**
- 29 DVT-02012 to DVT-26021**
- 30 ECSF-10001 to ECSF-11405**
- 31 EM-00251 to EM-02674**
- 32 ENS-00000 to ENS-00213**
- 33 EPMBPMUI-00101 to EPMBPMUI-01804**
- 34 EPMFR-00001 to EPMFR-00343**
- 35 EPMWKSP-00101 to EPMWKSP-02508**
- 36 ESS-00001 to ESS-09405**
- 37 FED-10102 to FED-20102**
- 38 FRC-60000 to FRC-60107**
- 39 FRM-41838 to FRM-99999**
- 40 FTS-40001 to FTS-40006**
- 41 HELP-00001 to HELP-30008**
- 42 IAU-01023 to IAU-62023**
- 43 INST-01000 to INST-08013**
- 44 IRM-00001 to IRM-03012**

45 J2EE HTTPC-00004 to J2EE HTTPC-12011

46 J2EE JMX-46000 to J2EE JMX-47006

47 J2EE JOC-00001 to J2EE JOC-00859

48 J2EE JSP-00002 to J2EE JSP-00302

49 JBO-24000 to JBO-80008

50 JPS-00001 to JPS-90641

51 JRF-10001 to JRF-20030

52 MAPVIEWER-00001 to MAPVIEWER-03107

53 MDS-00001 to MDS-91019

54 MODPLSQL-00001 to MODPLSQL-00868

55 OAAM-00000 to OAAM-70026

56 OAM-00001 to OAM-24001

57 OAMAP-60501 to OAMAP-60521

58 OAMCFG-60001 to OAMCFG-60080

59 OAMSSA-00001 to OAMSSA-16006

60 OBI\_OFFICE-00001 to OBI\_OFFICE-00072

61 ODI-01100 to ODI-30094

62 ODL-52001 to ODL-52501

63 ODSM-00001 to ODSM-01007

64 ODV-00011 to ODV-00168

65 OHS-03501 to OHS-03813

66 OID-03053 to OID-23737

- 67 OPM-00500 to OPM-00745
- 68 ORABPEL-00006 to ORABPEL-20511
- 69 ORAMED-01001 to ORAMED-09001
- 70 OSSOIAP-90001 to OSSOIAP-90005
- 71 OVD-01000 to OVD-80015
- 72 OWS-00016 to OWS-65005
- 73 PKI-01001 to PKI-07007
- 74 PROV-40000 to PROV-40000
- 75 RCS-00001 to RCS-23000
- 76 RCU-06000 to RCU-06138
- 77 REP-00001 to REP-80012
- 78 RUL-00000 to RUL-09043
- 79 SDF-10001 to SDF-10601
- 80 SDP-10111 to SDP-30017
- 81 SOA-00000 to SOA-00043
- 82 SSL-28750 to SSL-29249
- 83 SSLCFG-00131 to SSLCFG-00202
- 84 TCM-00006 to TCM-99009
- 85 TOP-00001 to TOP-72023
- 86 TPC-00001 to TPC-90022
- 87 TRS-10000 to TRS-20017
- 88 UCM-CS-000001 to UCM-CS-050023

- 89    **UIX-00001 to UIX-00025**
- 90    **UPGAST-00001 to UPGAST-02007**
- 91    **UPGCMP-00019 to UPGCMP-05203**
- 92    **WCS-03051 to WCS-51006**
- 93    **WOR-70021 to WOR-70229**
- 94    **WSM-00004 to WSM-09024**
- 95    **WWC-00000 to WWC-59083**
- 96    **WWS-18000 to WWS-33951**
- 97    **WWU-52262 to WWU-83028**
- 98    **WWV-00100 to WWV-61294**
- 99    **WXE-00010 to WXE-21271**
- 100    **XDF-10001 to XDF-10564**

---

# Preface

This manual provides information about the error messages you may encounter when installing and using Oracle Fusion Middleware components. It augments the message texts by providing additional cause and action information. For more information on error messages in Oracle Application Server, browse the documentation on the Oracle Technology Network (OTN) at <http://www.oracle.com/technology/products/ias/index.html>.

## Audience

This manual is intended for anyone who uses Oracle Fusion Middleware and requires more information about an error message encountered in the product.

## Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible to all users, including users that are disabled. To that end, our documentation includes features that make information available to users of assistive technology. This documentation is available in HTML format, and contains markup to facilitate access by the disabled community. Accessibility standards will continue to evolve over time, and Oracle is actively engaged with other market-leading technology vendors to address technical obstacles so that our documentation can be accessible to all of our customers. For more information, visit the Oracle Accessibility Program Web site at <http://www.oracle.com/accessibility/>.

### Accessibility of Code Examples in Documentation

Screen readers may not always correctly read the code examples in this document. The conventions for writing code require that closing braces should appear on an otherwise empty line; however, some screen readers may not always read a line of text that consists solely of a bracket or brace.

### Accessibility of Links to External Web Sites in Documentation

This documentation may contain links to Web sites of other companies or organizations that Oracle does not own or control. Oracle neither evaluates nor makes any representations regarding the accessibility of these Web sites.

### Access to Oracle Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/support/contact.html> or visit <http://www.oracle.com/accessibility/support.html> if you are hearing impaired.

# Conventions

The following text conventions are used in this document:

Convention	Meaning
<b>boldface</b>	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
<code>monospace</code>	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.



---

## ADF\_FACES-00001 to ADF\_FACES-60098

**ADF\_FACES-00001: unable to create Persistent ChangeManager: {0} {1}**

**Cause:** Could not load Persistent ChangeManager class specified in adf-config.xml

**Action:** Ensure that Java class specified in adf-config.xml exists in the Java ClassLoader of the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-00002: no listeners for custom event: {0}**

**Cause:** Application attempted to fire event when it never registered any listeners.

**Action:** Use the development tools to open the page and fix the event.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-00003: Unable to mark future region component client IDs that might be added to the RegionModel as needing a redraw because it is not supported in this implementation of the RegionModel.**

**Cause:** The RegionModel was incorrectly subclassed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-00004: Key: {0} is not of type String.**

**Cause:** Marshalling from client to server was invalid.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-00005: >attempt to synchronize secure key: {0}**

---

**Cause:** The client attempted to write to a component property that is only writable by the server.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-00006: Could not coerce key: {0} from value: {1} to type: {2}.**

**Cause:** Renderer's client-side peer marshalled a property that the Renderer doesn't know about.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-00007: Attempt to synchronized unknown key: {0}.**

**Cause:** Renderer's client-side peer marshalled a property that the Renderer doesn't know how to unmarshall.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-00008: A null QueryModel object was found.**

**Cause:** The QueryCriteria had a null or invalid QueryModel or no QueryDescriptors were specified for the model.

**Action:** Verify that the QueryModel is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-00009: Error processing viewId: {0} URI: {1} actual-URI: {2}.**

**Cause:** An exception was thrown when processing the children of the region.

**Action:** Use action related to thrown exception.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-00017: eventContext is set to launcher, but no launch ID is available.**

**To use eventContext launcher the popup must be launched on the client with the hint AdfDhtmlPopupWindow.HINT\_LAUNCH\_SOURCE\_ID set. See the popup doc for more information.**

**Cause:** the eventContext was set to launcher, but no launch ID is available.

**Action:** To use eventContext launcher the popup must be launched on the client with the hint AdfDhtmlPopupWindow.HINT\_LAUNCH\_SOURCE\_ID set. See the popup doc for more information.

---

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-00018: The launcherVar attribute is set, but the eventContext attribute is not set to launcher. LauncherVar is only made available when eventContext is set to launcher.**

**Cause:** The launcherVar attribute was set, but the eventContext attribute was not set to launcher.

**Action:** Remove launcherVar attribute or set eventContext attribute to launcher.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-00019: Error setting: {0} to from value: {1} for event: {2}.**

**Cause:** The setPropertyListener encountered an error when trying to set.

**Action:** Check that the EL expression is correct.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-00020: invokeOnComponent() is being called on the region with id {0} from inside of its RegionModel's processBeginRegion()**

**Cause:** This happens when the RegionModel implementation calls invokeOnComponent() before returning from its RegionModel's processBeginRegion(), typically because the application has used the expression language to bind a task flow parameter to a function that call invokeOnComponent().

**Action:** Instead of dynamically retrieving the component state with invokeOnComponent(), stash the value in application state, where it can be retrieved directly.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**ADF\_FACES-00021: The value {0} passed as identifier name to MoveChildComponentChange is not valid. Defaulting to 'id'.**

**Cause:** This happens when a MoveChildComponentChange is constructed with a value other than 'id' for identifier.

**Action:** Pass 'id' as the value.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-00022: No help topic found for helpTopicId={0}.**

**Cause:** A help topic was not found for the specified helpTopicId.

**Action:** Ensure a help topic is correctly configured.

---

**Level:** 2

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-00023: The MethodExpression wrapper of an include component was not able to locate the component after being deserialized. The expression will not be functional. Client ID not found was {0}**

**Cause:** Method expression was not deserialized when the include for its component was in the current component tree.

**Action:** The method expressions of properties of include components may only be deserialized when their component trees are the current ones.

**Level:** 2

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-00024: Unable to load the display names for TimeZone: {0} in Locale: {1}.**

**Cause:** No TimeZone information exists for this Locale.

**Action:** Ensure that the resource information exists for this Locale.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-10001: No representationClass provided.**

**Cause:** An illegal argument was passed to framework.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-10002: wrappedEvent**

**Cause:** An illegal argument was passed to framework.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-10003: Basename is null.**

**Cause:** Application never called setBaseName().

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-10004: No null numbers allowed in NumberRange.**

---

**Cause:** An illegal argument was passed to framework.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-10005: unregistered key: {0}**

**Cause:** An illegal argument was passed to framework.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-10006: Renderer {0} is not a rich renderer.**

**Cause:** Attempt was made to delegate rendering of a RichRenderer to a non-RichRenderer.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-10007: Null value for: {0} is not allowed.**

**Cause:** Tried to log the user activity information with null value for a non null field.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-10008: Parent cannot be null.**

**Cause:** Attempt was made to search for a child component inside a parent which is null.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-10011: attempt to add a duplicate ID**

**Cause:** Attempt was made to add a duplicate component under the destination.

**Action:** Ensure that destination does not already have a child with the ID of source component.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

---

**ADF\_FACES-10012: Allowed actions must be specified.**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-10013: Attempt to unsecure an always secured attribute**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-10014: Illegal access of the include attribute map outside of the include context**

**Cause:** An illegal attempt to access the attribute map of an include from outside of its context was made.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-10015: Illegal call to setup the context of an include that is already in context**

**Cause:** An illegal attempt to setup the context of an include component while the include was in context was made.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-10016: Illegal call to tear down the context of an include that is not in context**

**Cause:** An illegal attempt to tear down the context of an include component while the context was not set up.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-10017: Setup of page template context failed due to an unhandled exception.**

**Cause:** An unhandled exception in page template context setup.

**Action:** Contact Oracle Support Services.

---

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-10018: Tear down of page template context failed due to an unhandled exception.**

**Cause:** An unhandled exception in page template context tear down.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-10019: Setup of include component context failed due to an unhandled exception.**

**Cause:** An unhandled exception in include component context setup.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-10020: Tear down of include component context failed due to an unhandled exception.**

**Cause:** An unhandled exception in include component context tear down.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-10021: During the processing of the include component, the context change found did not match the current component.**

**Cause:** DDuring the processing of the include component, the context change found did not match the current component.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-10022: Attempt to resume an include component that was not suspended.**

**Cause:** An attempt was made to resume an include component that was not suspended.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

---

**ADF\_FACES-10023: readObject not supported for deserialization, SerializationProxy Required.**

**Cause:** An attempt was made to call readObject on a class that uses a SerializationProxy, therefore readObject should never be called.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-10024: The implementation of AdfFacesContext was not found. If this is a rich client application, it will not function. This is expected for Trinidad applications.**

**Cause:** AdfFacesContextImpl was not found on the class path.

**Action:** Contact Oracle Support Services if this is a rich client application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30001: invalid value for configuration parameter Estimated Number of Pages Per Channel: {0}**

**Cause:** Configuration of estimated number of pages per channel in adf-config.xml has exceeded 2,147,483,647.

**Action:** Fix configuration of pages-per-channel to a reasonable value.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30002: invalid value: {0} specified in configuration for parameter: {1}**

**Cause:** The active data configuration parameter from adf-config.xml was not a positive number.

**Action:** Fix the configuration to be a reasonable value.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30006: unexpected exception when starting active data on: {0}**

**Cause:** An error occurred in the ActiveModel implementation.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-30007: data changed notification on an unknown ActiveDataModel: {0}**

**Cause:** An error occurred in the ActiveModel implementation.

**Action:** Contact Oracle Support Services.



---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-30008: unexpected runtime exception stopping ActiveDataModel: {0}**

**Cause:** An error occurred in the ActiveModel implementation.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-30011: could not parse changeCount: {0} for clientId: {1}**

**Cause:** Change count delivered by client was not a number.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-30013: cannot register active data when window has no name**

**Cause:** WindowIdProvider returned a null window name. The Auto-PPR (partial page refresh) and ADS (active data service) features will not work.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-30014: no drag source for drop target: {0}**

**Cause:** A drop occurred, but no drag source can be found.

**Action:** Ensure that a drag source is defined for the drop target.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30016: no drop target for drag source: {0}**

**Cause:** Component was targeted for a drop but has no drop target.

**Action:** Ensure that a drop target is defined for the drag source.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30017: no listeners for custom event: {0}**

**Cause:** Client fired a custom client event for which there are no listeners.

**Action:** Define a listener for the custom client event.

**Level:** 1

---

**Type:** WARNING  
**Impact:** Logging  
**ADF\_FACES-30018: unable to parse Active Data Service start change count: {0}**  
**Cause:** Initial change count for active data was not a number.  
**Action:** Contact Oracle Support Services.  
**Level:** 1  
**Type:** INCIDENT\_ERROR  
**Impact:** Logging  
**ADF\_FACES-30022: error calling drop listener: {0}**  
**Cause:** Drop listener threw an exception.  
**Action:** Contact Oracle Support Services.  
**Level:** 1  
**Type:** INCIDENT\_ERROR  
**Impact:** Logging  
**ADF\_FACES-30023: error calling drop listener: {0} on: {1}**  
**Cause:** Drop listener threw an exception.  
**Action:** Contact Oracle Support Services.  
**Level:** 1  
**Type:** INCIDENT\_ERROR  
**Impact:** Logging  
**ADF\_FACES-30025: Client events for component: {0} were not in a valid form: {1}.**  
**Cause:** A parameter of a client event was marshalled as something other than a Map.  
**Action:** Contact Oracle Support Services.  
**Level:** 1  
**Type:** INCIDENT\_ERROR  
**Impact:** Logging  
**ADF\_FACES-30026: The collectionDragSource: {0} can only be attached to a collection component.**  
**Cause:** CollectionDragSource was not attached to UICollections.  
**Action:** Application should use a type of DragSource appropriate for this component.  
**Level:** 1  
**Type:** WARNING  
**Impact:** Logging  
**ADF\_FACES-30027: invalid align value: {0}**  
**Cause:** The popup alignment attribute was not one of the supported values.  
**Action:** Application should use a supported popup alignment attribute.  
**Level:** 1

---

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30028: could not find render kit: {0}**

**Cause:** The render kit with this ID was not registered with the application.

**Action:** Register this render kit or use the ID of a registered render kit.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30031: error decoding color string: {0} - returning null**

**Cause:** The value was not a supported String representation of a color.

**Action:** Ensure that the color string is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30032: column: {0} used outside of a table**

**Cause:** A column was used outside of a table.

**Action:** Move the column inside of the appropriate table.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30036: no skin icon exists with key: {0}**

**Cause:** The icon with this name did not exist in the skin.

**Action:** Ensure that the icon name is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30037: expected script element: {0}**

**Cause:** Application requested <script> output but wrote a non-script tag.

**Action:** Ensure the script element is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30038: illegal component hierarchy detected**

**Cause:** Expected UIXCommand but found another type of component instead.

**Action:** Ensure that the proper UIXCommand is used.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

---

**ADF\_FACES-30039: Collection decorator must contain a tree, table or treeTable as its first child.**

**Cause:** A non-tree or table component was used where tree or table was required.

**Action:** Ensure that the proper component is used.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30040: facet: {0} must be menu component**

**Cause:** A non-menu component was used where menu was required.

**Action:** Ensure that a menu component is used.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30041: toolbar facet: {0} must be RichToolbar component**

**Cause:** A non-toolbar component was used where toolbar was required.

**Action:** Ensure that a toolbar component is used.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30042: Loading popup: {0} during a full-page request is not supported.**

**Cause:** An attempt was made to load a popup during a full-page request.

**Action:** Ensure that the popup is not loaded during a full-page request.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30043: no PPR-capable ID found for elements of: {0}**

**Cause:** Application attempted to PPR an ID that does not exist.

**Action:** Ensure that a valid ID exists.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30044: Invalid model provided to progressIndicator (should be a BoundedRangeModel); progressIndicator ID: {0}.**

**Cause:** The value of the progressIndicator was not a BoundedRangeModel.

**Action:** Use the development tools to open the page and fix the progressIndicator.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

---

**ADF\_FACES-30045: Mode is null. It does not return correctly from current QueryDescriptor.**

**Cause:** No mode was set on QueryDescscriptor.

**Action:** Ensure a valid mode is set.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30046: A null QueryDescriptor object was found.**

**Cause:** Either a QueryDescriptor was not set on query component or the object provided was null or invalid.

**Action:** Ensure a valid QueryDescriptor is set on the query component.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30047: Component of ID: {0} cannot receive a client component because it is used as a repeating separator (or a similar usage).**

**Cause:** A ClientComponent is required where none is supported.

**Action:** Ensure the usage of the client component is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30048: Could not launch window, as render kit does not support the ExtendedRenderKitService.**

**Cause:** Launching a window required the ExtendedRenderKitService, but the current render kit does not support this service.

**Action:** Switch the RenderKitId to point to a render kit that supports the ExtendedRenderKitService.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30049: overwriting preexisting page flow scope parameters**

**Cause:** One of the dialog parameters conflicted with a page flow scope parameter.

**Action:** Ensure the parameters are valid.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30050: The original view root was not set.**

**Cause:** No viewRoot was set.

**Action:** Check servlet filter order.

**Level:** 1

---

Type: ERROR

Impact: Logging

**ADF\_FACES-30052: The group attribute on the selectBooleanRadio component is null. It must be set to a non-null value for the selectBooleanRadio component to function properly.**

**Cause:** No group attribute was set on selectBooleanRadio.

**Action:** Set the group value on the selectBooleanRadio component.

Level: 1

Type: WARNING

Impact: Logging

**ADF\_FACES-30053: Skinning property key: {0} cannot be parsed as int.**

**Cause:** The property was not an integer.

**Action:** Change skin property to be an integer.

Level: 1

Type: WARNING

Impact: Logging

**ADF\_FACES-30055: The number of items selected for shuttle: {0} exceeds the total number of items in the shuttle. No selected items will be returned.**

**Cause:** State of the shuttle was corrupted.

**Action:** Contact Oracle Support Services.

Level: 1

Type: INCIDENT\_ERROR

Impact: Logging

**ADF\_FACES-30056: Table with ID: {0} has no visible columns.**

**Cause:** Table contains no visible columns.

**Action:** Add at least one visible column to the table component.

Level: 1

Type: WARNING

Impact: Logging

**ADF\_FACES-30057: Table inlineStyle will be ignored because width:auto is not supported.**

**Cause:** The inline CSS property width:auto was ignored because it is not supported on table component to control its size.

**Action:** Remove the inlineStyle property on the table component.

Level: 1

Type: WARNING

Impact: Logging

**ADF\_FACES-30058: Table width attribute will be ignored because auto is not supported.**

---

**Cause:** The attribute width=auto was ignored because it is not supported on table component to control its size.

**Action:** Remove the table width attribute.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30059: unknown table fetch type**

**Cause:** The client table peer sent a fetch requests with an unknown fetch type.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-30060: Either a MenuModel object was not provided or an invalid object was provided.**

**Cause:** The train component required a value of type MenuModel.

**Action:** Correct the train definition.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30061: The model provided for the train has no stops.**

**Cause:** No train stops were supplied for the train component model.

**Action:** Check to see if the model is set up correctly.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30062: The parent stop label was null for the stop: {0}**

**Cause:** The parent stop label was null.

**Action:** Add a stop label.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30063: The nodeStamp facet on treeTable: {0} is missing or not of type UIXColumn.**

**Cause:** No nodeStamp facet was specified on treeTable.

**Action:** Specify a nodeStamp facet on the treeTable.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

---

**ADF\_FACES-30064: illegal value: {0} for: {1}**

**Cause:** The table banding interval must be  $\geq 0$ .

**Action:** Ensure the banding interval is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30065: The nodeStamp facet on treeTable: {0} is missing or not of type UIXColumn.**

**Cause:** The nodeStamp facet of a treeTable was invalid. It only supports components of type UIXColumn.

**Action:** Ensure a correct nodeStamp facet is defined.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30066: no registered FacesBean.Type for family: {0} type: {1}**

**Cause:** No FacesBean was registered for this componentFamily and rendererType.

**Action:** Use a render kit that supports this componentFamily and rendererType.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30067: Multithreaded execution was interrupted.**

**Cause:** Execution of the multithreaded streaming request was interrupted.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-30068: multithreaded execution exception**

**Cause:** The model threw an exception during multithreaded rendering.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-30071: The collection component with ID: {0} cannot be found inside the component.**

**Cause:** No component with the specified ID was found inside the popup.

**Action:** Specify a valid component ID.

**Level:** 1

**Type:** ERROR

**Impact:** Logging



---

**ADF\_FACES-30072: The component with ID: {0} is not a collection component.**

**Cause:** The collection popup content was not a collection component.

**Action:** Ensure the popup content is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30073: The collection return listener {0} must be inside of a UIComponent tag.**

**Cause:** The collection return listener was not inside of a UIComponent tag.

**Action:** Ensure that the collection return listener is inside of a UIComponent tag.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30074: The returnActionListener must be inside of an input popup component.**

**Cause:** The returnActionListener tag was not inside of a tag that created an input popup component.

**Action:** Correct the returnActionListener .

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30075: Could not find parent include tag for definition: {0}.**

**Cause:** Could not find the tag that included the definition tag.

**Action:** Ensure that the include tag is defined properly.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30076: Component: {0} must be included as a child of an include tag.**

**Cause:** The parent component of a pageTemplateDef or componentDef tag must be extend UIXInclude.

**Action:** Ensure that the pageTemplateDef or componentDef is the child of an include tag.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30077: Time-stamp checking enabled for faces component metadata.**

**Do not use in a production environment.**

**property:oracle.application.environment=development**

**Cause:** Application configured to run in development mode.

**Action:** No action needed.

---

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**ADF\_FACES-30078: Attribute: {0} is missing on component with ID: {1} in file: {2}.**

**Cause:** A required component attribute is not specified.

**Action:** Ensure all attributes are defined.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30079: error parsing component tag in file: {0}**

**Cause:** The metadata for the page template or include component contained an error.

**Action:** Use the development tools to open the include and fix the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30080: unknown element:{0} at: {1}**

**Cause:** The metadata for the include contained an unknown XML element.

**Action:** Use the development tools to open the include and fix the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30081: Attribute: {0} is missing at: {1}.**

**Cause:** The include metadata attribute name was not specified.

**Action:** Use the development tools to open the include and fix the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30082: exception at: {0}**

**Cause:** An exception occurred when parsing the include metadata.

**Action:** Use the development tools to open the include and fix the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30083: Component: {0} with ID: {1} cannot have children.**

**Cause:** Attempt was made to add a componentRef tag under a component that cannot have children.

**Action:** Use the development tools to open the include and fix the problem.

---

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30084: Could not get RequestDispatcher for viewId: {0} and uri: {1}.**

**Cause:** The JSP to include could not be found.

**Action:** Verify that the JSP exists at the specified location.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30085: The facetRef must be inside af:pageTemplateDef or af:componentDef.**

**Cause:** The facetRef tag was used outside of a f:pageTemplateDef or af:componentDef tag.

**Action:** Use the development tools to open the include and fix the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30086: Cannot find parent include component.**

**Cause:** Cannot find parent include component.

**Action:** Use the development tools to open the include and fix the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30087: Encountered null from the viewId expression: {0}.**

**Cause:** The URI of the include was null.

**Action:** Use the development tools to open the include and fix the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30088: Cannot find closing ">" in: {0}.**

**Cause:** XmlContentTag is missing an end tag.

**Action:** Use the development tools to open the include and fix the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30089: Cannot parse root element in: {0}.**

**Cause:** No root element was started on XmlContentTag.

**Action:** Use the development tools to open the include and fix the problem.

---

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30090: Could not find root element in: {0}.**

**Cause:** XmlContentTag had no root element.

**Action:** Use the development tools to open the include and fix the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30091: Could not compute the namespace for element: {0} with prefix: {1} in: {2}.**

**Cause:** No XML namespace found for prefix.

**Action:** Ensure the namespace is properly defined.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30093: error while loading library: {0}**

**Cause:** IE Exception occurred when attempting to load the deferred library.

**Action:** Ensure that the library is at the specified location.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30094: unable to get resource: {0}**

**Cause:** Specified resource was not found in classpath.

**Action:** Ensure that the resource is present in the classpath.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30095: Marshalling of StateHolders not yet supported; skipping: {0}.**

**Cause:** Marshalling of StateHolders not supported and was skipped.

**Action:** Use the development tools and fix the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30096: Unmarshaling of StateHolders not yet supported.**

**Cause:** Unmarshaling of StateHolders not supported.

**Action:** Use the development tools and fix the problem.

**Level:** 1

---

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30097: rich text parse error at position: {0}, unterminated element: {1}**

**Cause:** A rich text value was encountered with an unexpected unterminated element.

**Action:** Ensure that the tags for this element get terminated.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30098: rich text parse error at position: {0}, unclosed element: {1}**

**Cause:** A rich text value was encountered with an element that requires a closing tag but no closing tag was provided.

**Action:** Ensure that this element gets a closing tag.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30099: rich text parse error at position: {0}, unsupported element: {1}**

**Cause:** A rich text value was encountered with an element that is not supported.

**Action:** Do not use this element.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30100: rich text parse error at position: {0}, unterminated attribute name**

**Cause:** A rich text value was encountered with an attribute name that was not terminated.

**Action:** Ensure that this attribute name gets terminated.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30101: rich text parse error at position: {0}, unterminated value for attribute: {1}**

**Cause:** A rich text value was encountered with an attribute value that was not terminated.

**Action:** Ensure that this attribute value gets terminated.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30102: The rich text editor is not supported in the specified agent: {0}.**

---

**Cause:** An attempt was made to use the rich text editor component in an unsupported web browser.

**Action:** Ensure that the browser used is supported by this rich text editor component.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30107: The view state of the page has expired. Reload the page.**

**Cause:** The UI state of the view has expired, either because the back button has been used too many times, too many page submissions have occurred on the pages, or because of an underlying bug in the view code.

**Action:** The application using ADF should install an ADFc error handler for JSF ViewExpiredExceptions, or configure the org.apache.myfaces.trinidad.CLIENT\_STATE\_MAX\_TOKENS web.xml parameter to a larger value.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30108: The view state of the page has expired because of inactivity. Reload the page.**

**Cause:** The UI state of the view has expired because the session has expired.

**Action:** The application using ADF should install an ADFc error handler for JSF ViewExpiredExceptions.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30109: Conversion failed while trying to synchronize value from client. Attempted to convert: {0}, Component ID: {1}.**

**Cause:** An attempt was made to set a value on the client that could not be converted on the server.

**Action:** Make sure application setting legal value on client.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30110: export requires HTTP Servlet**

**Cause:** Export operation failed; it is supported only with an HTTP Servlet.

**Action:** For exporting content, ensure that HTTP Servlet is available.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30111: Collection with the ID: {0} is not supported by exportCollectionActionListener.**

---

**Cause:** exportCollectionActionListener used with invalid collection.  
**Action:** Ensure that the exported component is table, tree or treeTable.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30112: Export type: {0} is not supported by exportCollectionActionListener.**

**Cause:** Unsupported export type was specified.

**Action:** Use one of the supported export types as specified in exportCollectionActionListener tag documentation.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30113: Exported collection with the ID of: {0} was not found.**

**Cause:** Exported collection with the specified ID was not found.

**Action:** Ensure that the correct ID is specified.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30114: The converter supplied for inputDate with ID: {0} is not an instance of javax.DateConverter: {1}. This input field will only support showing dates. To get time and/or timezone support, subclass the converter from javax.DateConverter.DateConverter or obtain the converter using Application.createConverter (preferred).**

**Cause:** The supplied converter was not a subclass of javax.DateConverter.

**Action:** Use the converter supplied by javax.faces.application.Application.createConverter, or make the custom converter subclass javax.DateConverter.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30115: The converter supplied for InputDate with ID: {0} does not implement the ClientConverter interface: {1}. The input field will not support client conversion or validation, and only the input field will be displayed (no date-picker popup). To get client conversion and validation support, implement the org.apache.myfaces.trinidad.convert.ClientConverter interface or obtain the converter using javax.faces.application.Application.createConverter (preferred). If you just want to set the converter pattern programmatically, obtain it using createConverter and call setPattern() on it.**

**Cause:** The supplied converter does not implement the ClientConverter interface.

**Action:** Use the converter supplied by Application.createConverter, or make the custom converter implement org.apache.myfaces.trinidad.convert.ClientConverter.

---

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30116: User activity information for the {0} request is not available.**

**Cause:** User activity Information was null when logging this information to monitoring service.

**Action:** Ensure that user activity information is not null when monitoring service is enabled.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30117: Component cannot be located by the ID: {0}.**

**Cause:** Component was not found when trying to callback for component using client ID of component.

**Action:** Ensure that it has been invoked with correct client ID.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30118: No help provider found for helpTopicId={0}.**

**Cause:** A help provider was not found for the specified helpTopicId.

**Action:** Ensure a help provider is correctly configured.

**Level:** 2

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30120: More than one af:skipLinkTarget found: {0}. Only one af:skipLinkTarget is allowed per page.**

**Cause:** Multiple af:skipLinkTargets were found.

**Action:** Remove af:skipLinkTarget so that only one is specified per page.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30121: No af:document ancestor for af:skipLinkTarget in component: {0}. af:skipLinkTarget must be used in conjunction with af:document.**

**Cause:** Missing af:document ancestor for af:skipLinkTarget.

**Action:** Remove af:skipLinkTarget, or move inside of an af:document.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30122: Invalid parent for af:skipLinkTarget in component: {0}. af:skipLinkTarget must placed inside of a component that generates content.**



---

**Cause:** af:skipLinkTarget must be placed inside of a component that generates content.

**Action:** Remove the af:skipLinkTarget, or move it inside of a parent which generates content.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30123: Invalid facet size for af:panelStretchLayout: {0}. {1} is not a valid CSS length.**

**Cause:** An invalid value was specified for a panelStretchLayout size (topHeight, bottomHeight, startWidth, endWidth) attribute.

**Action:** Specify valid CSS lengths for the panelStretchLayout size (topHeight, bottomHeight, startWidth, endWidth) attributes.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30124: Multiple forms detected on viewId: {0}. Rich client currently has some limitations in dealing with multiple forms.**

**Cause:** An ADFFaces page was detected with multiple forms on the same page. Currently there are a number of issues associated with multiple forms on the same page and this should be done with caution.

**Action:** Reorganize page so that it contains only one form.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30125: Exported rows type: {0} is not supported by exportCollectionActionListener.**

**Cause:** Unsupported exported rows type was specified.

**Action:** Use one of the supported exported rows types as specified in exportCollectionActionListener tag documentation.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30126: File name: {0}, Message: {1}**

**Cause:** An error was detected while parsing a feature/partition configuration file.

**Action:** Verify that the feature/partition configuration file is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30127: Line: {0}, Column: {1}, Error: {2}**

**Cause:** An error was detected while parsing a feature/partition configuration file.

---

**Action:** Verify that the feature/partition configuration file is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30128: File name: {0}, Line number: {1}, Column number: {2}, Error: {3}**

**Cause:** An error was detected while parsing a feature/partition configuration file.

**Action:** Verify that the feature/partition configuration file is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30129: Ignoring feature element because missing feature-name.**

**Cause:** A feature element was missing a required feature-name child.

**Action:** Verify that the feature configuration file is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30130: Ignoring feature-dependency on feature "{0}". No such feature exists.**

**Cause:** A feature-dependency specified a dependency on a feature which does not exist.

**Action:** Verify that the feature configuration file is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30131: Ignoring partition element because missing partition-name.**

**Cause:** A partition element was missing a required partition-name child.

**Action:** Verify that the partition configuration file is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30132: Ignoring feature element "{0}". No such feature exists.**

**Cause:** A partition element contained an unknown feature.

**Action:** Verify that the partition configuration file is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30133: A circular dependency between partitions has been detected: {0}  
Library partitioning will be disabled.**

**Cause:** A circular dependency exists between partitions.

---

**Action:** Verify that the partition configuration file is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30134: Partition "{0}" ({1}) depends on partition "{2}" ({3}).**

**Cause:** A circular dependency exists between partitions.

**Action:** Verify that the partition configuration file is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30135: request for unknown partition: {0}**

**Cause:** A request was made for an unknown partition.

**Action:** Verify that the partition configuration is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30136: Feature "{0}" is not contained in any partition.**

**Cause:** A request was made for an unknown feature.

**Action:** Verify that the feature/partition configuration is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30137: Unable to service request for resource: {0}. FacesContext not available.**

**Cause:** The partition resource loader was unable to obtain a FacesContext.

**Action:** Check the logs for other exceptions/errors.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30138: Ignoring AdfBootstrap feature in partition {0}. The AdfBootstrapFeature must reside in its own partition.**

**Cause:** A partition was defined which contains both the AdfBootstrap feature as well as other features.

**Action:** The AdfBootstrap feature should be moved to its own partition.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

---

**ADF\_FACES-30139: Could not find the component with relative ID {0} from {1}. This method will try to locate the component for the given ID by calling findComponent on its parent NamingContainer as a final attempt.**

**Cause:** The identifier provided did not account for NamingContainers properly.

**Action:** Ensure that the relative ID specified is correct and the component with that ID exists.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30140: The slider component with label {0} has too many ticks that are rendered. This will have a huge performance impact.**

**Cause:** The provided minimum is too small or the provided maximum is too large.

**Action:** Provide a better range for the slider by modifying the maximum and/or minimum attributes.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30141: Unable to remove the criterion with rowKey {0} because a criterion with the specified rowKey could not be located.**

**Cause:** This could happen if an attempt is made to remove an already removed criterion and likely in slow performing applications

**Action:** Ensure that criterion fields are removed only once.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30142: Component {0} has attribute {1} with type {2}. The attribute should be of type {3}.**

**Cause:** The value supplied for the attribute is returning a wrong type.

**Action:** Check the method that returns the value for the attribute and correct its type.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30143: A circular dependency between features has been detected: {0} Library partitioning will be disabled.**

**Cause:** A circular dependency exists between features.

**Action:** Verify that the feature configuration files are valid.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

---

**ADF\_FACES-30144: Feature "{0}" depends on feature "{1}".**

**Cause:** A circular dependency exists between features.

**Action:** Verify that the feature configuration files are valid.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30145: A duplicate definition for the feature "{0}" has been found at {1}, line {2}. A feature with the same name was originally defined at {3}, line {4}. This may indicate that multiple copies of the same jar file are present on the class path. Ignoring the new feature definition.**

**Cause:** This occurs when there are multiple copies of a jar file containing the same adf-js-features.xml on the class path. Or, alternatively, this may come up if different adf-js-features.xml use the same feature name.

**Action:** Check for multiple copies of the jar containing the feature definition on the class path. Or, check to see whether feature names are unique.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30146: The calendarDropTarget: {0} can only be attached to a calendar component.**

**Cause:** CalendarDropTarget was not attached to UICalendar.

**Action:** Application should use a type of DragSource appropriate for this component.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30147: The converter supplied for InputColor with ID: {0} does not implement the ClientConverter interface: {1}. The input field will not support client conversion or validation, and only the input field will be displayed (no color-picker popup). To get client conversion and validation support, implement the org.apache.myfaces.trinidad.convert.ClientConverter interface or obtain the converter using javax.faces.application.Application.createConverter (preferred). If you just want to set the converter pattern programmatically, obtain it using createConverter and call setPattern() on it.**

**Cause:** The supplied converter does not implement the ClientConverter interface.

**Action:** Use the converter supplied by Application.createConverter, or make the custom converter implement org.apache.myfaces.trinidad.convert.ClientConverter.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30148: The supplied converter {1} with ID {0} does not implement the ClientConverter interface. The input field will not support client conversion or validation. Only normal string to number conversion will be supported, such as**

---

"5" to 5, but not "five" to 5. To get client conversion and validation support, implement the `org.apache.myfaces.trinidad.convert.ClientConverter` interface or obtain the converter using `javax.faces.application.Application.createConverter` (preferred). If you just want to set the converter pattern programmatically, obtain it using `createConverter` and call `setPattern()` on it.

**Cause:** The supplied converter does not implement the `ClientConverter` interface.

**Action:** Use the converter supplied by `Application.createConverter`, or make the custom converter implement `org.apache.myfaces.trinidad.convert.ClientConverter`.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-30149: No PartitionManager found, possibly due to passivation or failover. Re-creating the PartitionManager.**

**Cause:** The `PartitionManager` object is null, either due to passivation or failover.

**Action:** No action required. The `PartitionManager` will be re-created.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**ADF\_FACES-30150: Unable to parse Date: {0}.**

**Cause:** There was an error parsing the date string sent from the client.

**Action:** The date string must be set in the proper format.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30151: The {0} facet is not returning a popup.**

**Cause:** The facet is not returning a popup. Only popups are accepted for the Calendar facets.

**Action:** Check the facet to make sure it contains a popup.

**Level:** 1

**Type:** SEVERE

**Impact:** Logging

**ADF\_FACES-30152: The Calendar Toolbox Layout contains 'all' as well as built-in value {0}. 'all' will be used.**

**Cause:** If the `toolboxLayout` contains 'all', the other built-in values should not be used.

**Action:** Correct the `toolboxLayout` attribute to specify 'all' or the built-in value desired.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

---

**ADF\_FACES-30153: Unable to find facet corresponding to Calendar custom toolboxLayout value {0}.**

**Cause:** A custom value was encountered for the toolboxLayout but no corresponding facet was found.

**Action:** Check that the facet has been added and that its name matches the value specified in toolboxLayout.

**Level:** 1

**Type:** SEVERE

**Impact:** Logging

**ADF\_FACES-30154: No providerId was supplied for activity {0}. Provider Id is required.**

**Cause:** A null value was supplied for the activity's providerId.

**Action:** Check the activity source and ensure the providerId is not null.

**Level:** 1

**Type:** SEVERE

**Impact:** Logging

**ADF\_FACES-30155: No activityId was supplied for activity {0}. Activity Id is required.**

**Cause:** A null value was supplied for the activity's activityId.

**Action:** Check the activity source and ensure the activityId is not null.

**Level:** 1

**Type:** SEVERE

**Impact:** Logging

**ADF\_FACES-30156: The ALLDAY activity {0} has an invalid start and end date and it may not render correctly. See the CalendarActivity Javadoc for information about valid values for startDate and endDate for an ALLDAY activity.**

**Cause:** A null value was supplied for the activity's activityId.

**Action:** Check the activity source and ensure the activityId is not null.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30157: The ChooseColor component with client id {0} has width {1} which is too large. This will have a huge performance impact. In Design mode, the component will render with maximum width {2}**

**Cause:** The provided width is too large.

**Action:** Reduce the width attribute of the component.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30158: No af:document ancestor for af:resource for the component: {0}. af:resource must be used in conjunction with af:document.**

---

**Cause:** Missing af:document ancestor for af:resource.

**Action:** Remove af:resource, or move inside of an af:document.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30159: Invalid value {0} specified for the oracle.adf.view.rich.SUPPRESS\_IDS context parameter.**

**Cause:** Invalid value specified for the oracle.adf.view.rich.SUPPRESS\_IDS context parameter.

**Action:** Check web.xml file to verify that a valid SUPPRESS\_IDS value is specified.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30160: Invalid value {0} specified for calendar attribute 'availableViews'.**

**Cause:** The value specified for calendar attribute 'availableViews' was not recognized.

**Action:** Correct the 'availableViews' attribute to one of the following: all, day, week, month, list

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30161: The availableViews attribute contains 'all' as well as built-in value {0}. 'all' will be used.**

**Cause:** If availableViews contains 'all', the other built-in values should not be used.

**Action:** Correct the availableViews attribute to specify 'all' or the built-in value desired.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30162: The 'view' attribute {0} does not correspond to one of the built-in availableViews. The calendar will display {1}.**

**Cause:** The 'view' attribute should correspond to one of the views specified in 'availableViews'. If 'availableViews' is unspecified or set to 'all', the 'view' attribute should be one of the built-in views: day, week, month, list.

**Action:** Correct the 'view' attribute to be one of the views displayed in 'availableViews'.

**Level:** 1

**Type:** WARNING

**Impact:** Logging



---

**ADF\_FACES-30163: The application is running with the new window detect flag off. It is highly recommended that this flag be turned on to ensure proper functioning of your application when new browser windows are launched. In web.xml set the context parameter oracle.adf.view.rich.newWindowDetect.OPTIONS to 'on'.**

**Cause:** When new window detection is turned off, browser window dialog may not work as expected.

**Action:** Turn on new window detection by adding context parameter oracle.adf.view.rich.newWindowDetect.OPTIONS to web.xml with a value of on.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30164: {0} should be defined for varyElement in caching rule.**

**Cause:** one of the parameter undefined for varyElement.

**Action:** define all the parameters for varyElement.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30165: No expression defined for cache-key-pattern.**

**Cause:** No expression defined for cache-key-pattern.

**Action:** Define expression for cache-key-pattern.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30166: No cache-key-pattern defined for caching-rule.**

**Cause:** no cache-key-pattern defined for caching-rule.

**Action:** Define cache-key-pattern for caching-rule.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30167: No rule defined for caching.**

**Cause:** No rule defined for caching.

**Action:** Define rule for caching.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30168: No keys defined for Search-Key.**

**Cause:** No keys defined for Search-Key.

**Action:** Define keys for Search-Key.

**Level:** 1

---

Type: WARNING

Impact: Logging

**ADF\_FACES-30169: No vary-element defined for VaryBy element.**

Cause: No vary-element defined for VaryBy element.

Action: Define vary-element for VaryBy element.

Level: 1

Type: WARNING

Impact: Logging

**ADF\_FACES-30170: Suppressing Cache header overwriting-- {0}: {1}.**

Cause: Suppressing Cache header.

Action: Do not override cache header.

Level: 1

Type: NOTIFICATION

Impact: Logging

**ADF\_FACES-30171: WEB CACHE is installed ahead of Application Server.**

Cause: WEB CACHE is installed ahead of Application Server.

Action: None.

Level: 1

Type: NOTIFICATION

Impact: Logging

**ADF\_FACES-30172: Unable to include contents for region {0}. FaceletContext unavailable.**

Cause: This is an unexpected condition which may be due to an ADF Faces bug.

Action: Contact Oracle Support Services.

Level: 1

Type: SEVERE

Impact: Logging

**ADF\_FACES-30173: deprecated configuration element: parameter: use-polling is replaced by parameter: transport**

Cause: The active data configuration parameter from adf-config.xml is deprecated.

Action: Fix the configuration to be a reasonable value.

Level: 1

Type: WARNING

Impact: Logging

**ADF\_FACES-30174: An invalid or null contextId was provided when logging userActivity information for the previous request.**

Cause: This may occur if the previous response sent to the client included a null contextId or an error occurred in the client when retrieving the userActivity info.

Action: None.

---

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30175: A null contextId was returned by the service provider implementation for the ExecutionContextProvider.**

**Cause:** A null contextId was returned by the ExecutionContextProvider implementation.

**Action:** Ensure that a proper service provider has been registered in META-INF/services.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-30180: Circular dependency detected in the geometry management configuration of component id {0}.**

**Cause:** The component has an attribute assignment that resulted in a circular dependency.

**Action:** See the geometry management section of that component's tag documentation for more information.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-60001: ActiveDataModel is null.**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60002: attempt to register component for STATIC ActiveDataPolicy**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60003: Component with ID: {0} not registered for Active Data.**

**Cause:** Component was not registered properly.

**Action:** Register the component for Active Data.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60004: ActiveDataModel is not registered.**

---

**Cause:** The activeDataModel was not registered.

**Action:** Register the activeDataModel.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60005: <help-provider-class> is required and must come first.**

**Cause:** Online help was configured without first configuring the help-provider-class.

**Action:** Provide the help-provider-class in adf-config.xml.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60006: Request has not begun.**

**Cause:** An IllegalStateException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60007: Phase {0} has already passed; at least at phase {1}.**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60008: Attribute name required.**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60009: dropHandler required**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60010: allowed actions required**

**Cause:** An IllegalArgumentException occurred.

---

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60011: Allowed actions must be specified.**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60012: Single quotes and single quote escaping is not permitted in keys.**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60013: End of pattern not found.**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60014: NamedMessageFormat: empty argument {} found.**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60015: Must have a drop component.**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60016: Must have parameters.**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

---

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60017: Cannot retrieve drop action until DropTarget has been called.**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60018: clientActions out of range**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60019: illegal character**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60020: DnDAction.NONE not allowed in Set<DnDAction>.**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60021: No DnDActions specified.**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60022: Cannot add null DataFlavor to allowed flavors.**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

---

**Impact:** Logging

**ADF\_FACES-60023: Component: {0} does not support client listeners.**

**Cause:** An invalid client listener was encountered.

**Action:** Use the development tools to open the page and fix the client listener.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60024: Component: {0} does not support client attributes.**

**Cause:** Only UIXComponents support client attributes.

**Action:** Use the development tools to open the page and fix the component.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60025: Error trying to change index from: {0} to: {1} rowCount: {2}.**

**Cause:** An IllegalStateException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60026: Path contains a null rowKey.**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60027: unexpected navigationPane hint: {0}**

**Cause:** An invalid navigationPane hint was encountered.

**Action:** Use the development tools to open the page and fix the navigationPane component.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60028: targetComponent must be specified.**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

---

**ADF\_FACES-60029: Fetch constraint:{0} must be serializable if specified.**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60030: Fetch ClientEvent must not specify component.**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60031: No returnId is available for returning from the dialog.**

**Cause:** An IllegalStateException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60032: Could not find ExtendedRenderKitService.**

**Cause:** Render kit does not support the ExtendedRenderKitService.

**Action:** Use a render kit that does support the ExtendedRenderKitService.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60033: The index {0} of the submitted value for selectOne is out of bounds. It should be between 0 and {1}.**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60034: SelectOne could not convert index {0} of submitted value into int {1}.**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging



---

**ADF\_FACES-60035: Component {0} does not support a collection indexed by rowKeys.**

**Cause:** A component was found with an invalid index.

**Action:** Use the development tools to open the page and fix the component.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60036: bad PhaseId: {0}**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60037: ClientId must be specified.**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60038: Component ID parameter is null.**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60039: AsyncFetch model parameter is null.**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60040: AsyncFetcher is null.**

**Cause:** An IllegalArgumentException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60041: Phase {0} has already started or passed; at least at phase {1}.**

---

**Cause:** An `IllegalArgumentException` occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60042: Cannot recursively nest {0} elements.**

**Cause:** These elements were recursively nested.

**Action:** Use the application development tools to correct this issue.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60043: {0} is null.**

**Cause:** An `IllegalArgumentException` occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60044: not nested in FacesTag: {0}**

**Cause:** Parent tag was not a `FacesTag`.

**Action:** Use the development tools to ensure the tags are correct.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60045: Parent UIComponent instance is null.**

**Cause:** Parent `FacesTag` had no `UIComponent`.

**Action:** Use the development tools to ensure the tags are correct.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60046: unknown render kit ID: {0}**

**Cause:** No render kit with this ID was found.

**Action:** Register a render kit with a correct ID.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60047: Iterator cannot be null.**

**Cause:** Iterator was found to be null.

**Action:** Use the development tools to ensure the iterator is properly defined.

---

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60048: JavaScript does not support null keys.**

**Cause:** A null key was found in the JavaScript.

**Action:** Use the development tools to correct the JavaScript.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60049: rowKeys cannot be null.**

**Cause:** A null row key was found.

**Action:** Use the development tools to correct the problem.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60050: ActionListener: {0} must be inside of a UIComponent tag for a command component.**

**Cause:** An error was found in the JSP page metadata.

**Action:** Use the development tools to correct the ActionListener.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60051: Invalid width: {1} specified on column: {0}.**

**Cause:** A column was found with an invalid width.

**Action:** Use the development tools to open the page and fix the column.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60052: Invalid minimumWidth: {1} specified on column: {0}.**

**Cause:** A column with an invalid minimum width was encountered.

**Action:** Use the development tools to open the page and fix the column.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60053: rich text parse error at position: {0}**

**Cause:** A rich text value was encountered with a broken comment.

**Action:** Ensure that the comments in this value are well-formed.

**Level:** 2

---

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60054: rich text parse error at position: {0}**

**Cause:** A rich text value was encountered with a non-terminated comment.

**Action:** Ensure that the comments in this value are terminated.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60055: No setPattern method present on converter: {0}.**

**Cause:** A converter was encountered with a missing method.

**Action:** Use the development tools to open the page and fix the converter.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60056: Error executing setPattern method on converter: {0}.**

**Cause:** A converter was encountered with an invalid method.

**Action:** Use the development tools to open the page and fix the converter.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60057: Unable to access setPattern method present on converter: {0}.**

**Cause:** A converter was encountered with an invalid method.

**Action:** Use the development tools to open the page and fix the converter.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60058: Attempt to re-register component with different model.**

**Cause:** An IllegalStateException occurred.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60059: A null QueryModel object was found.**

**Cause:** Either a QueryModel was not set on the query component, or the expression for the model property resolved to a null or invalid object.

**Action:** Use the development tools to open the page and fix the query.

**Level:** 1

**Type:** WARNING

---

**Impact:** Logging

**ADF\_FACES-60060: A null ListOfValuesModel object was encountered.**

**Cause:** Either a ListOfValuesModel object was not set on the lov component, or the expression for the model property resolved to a null or invalid object.

**Action:** Use the development tools to open the page and fix the list of values component.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-60061: Current criterion is not valid or null.**

**Cause:** QueryDescriptor.getCurrentCriterion() method was not implemented correctly or returned null.

**Action:** Use the development tools to open the page and fix the query.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-60062: Popup component with the ID: {0} not found.**

**Cause:** The popup with the ID specified for createPopupId on LOV Component is not found.

**Action:** Use the development tools to open the page and fix the popup.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-60063: Invalid facet size for af:decorativeBox: {0}. {1} is not a valid CSS length.**

**Cause:** An invalid value was specified for a decorativeBox size (e.g. topHeight) attribute.

**Action:** Specify valid CSS lengths for the decorativeBox size (e.g. topHeight) attributes.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-60064: unsupported element: {0}**

**Cause:** An unsupported element was encountered while parsing a feature/partition configuration file.

**Action:** Verify that the feature/partition configuration is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-60065: unsupported namespace: {0}**

---

**Cause:** An unsupported namespace was encountered while parsing a feature/partition configuration file.

**Action:** Verify that the feature/partition configuration is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-60066: Failed to load ADF Faces JavaScript features.**

**Cause:** ADF Faces was unable to load its feature configuration metadata.

**Action:** Check the logs for other exceptions/errors.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60067: Failed to load ADF Faces JavaScript partitions.**

**Cause:** ADF Faces was unable to load its partition configuration metadata.

**Action:** Check the logs for other exceptions/errors.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60068: attempting to add setPropertyListener with type set to valueChange to component that is not editableValueHolder**

**Cause:** Attempted to add setPropertyListener with type set to valueChange to component that is not editableValueHolder.

**Action:** Move the setPropertyListener tag or change the type event it is listening for.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60069: No methodData information available for type: {0}.**

**Cause:** No methodData information was available for the type given.

**Action:** Check that the type is supported type. If it is a supported type log a bug.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60070: Attempting to add requested listener to component of type: {0} has failed. For the type: {1}, the setPropertyListener tag requires that the component have a method: {2}.**

**Cause:** For the type given, there was no appropriately named add method for the setPropertyListener to call in order to add itself as a listener.

**Action:** Change the type attribute to an event type that is supported on the component, or remove the setPropertyListener tag.

---

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60071: The type: {0} is not a legal type. The legal values for type are: {1}.**

**Cause:** An invalid type was passed to the setPropertyListener tag.

**Action:** Change the type property on the setPropertyListener tag to a supported type.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60072: The setPropertyListener tag must be a child of UIComponent.**

**Cause:** The setPropertyListener tag was not a child of UIComponent.

**Action:** Move setPropertyListener tag so that it is a child of a UIComponent.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60073: The setPropertyListener "to" attribute must be an EL expression.**

**Cause:** The setPropertyListener "to" attribute was not an EL expression.

**Action:** Fix the "to" attribute so that it is an EL expression.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60074: attempting to add setPropertyListener with type set to action to component that is not actionSource**

**Cause:** Attempted to add setPropertyListener with type set to action to component that is not actionSource.

**Action:** Move the setPropertyListener tag or change the type event it is listening for.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60075: Drop handler cannot return null.**

**Cause:** Drop handler cannot return null.

**Action:** Contact Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADF\_FACES-60076: Active Data Service is already initialized**

---

**Cause:** AdsInitializerListener is registered in web.xml.

**Action:** Remove the AdsInitializerListener class from your web.xml

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-60077: The CalendarModel is null.**

**Cause:** The calendar is not bound to a valid CalendarModel.

**Action:** Check the value attribute of the Calendar and ensure it is set to a valid oracle.adf.view.rich.model.CalendarModel.

**Level:** 1

**Type:** SEVERE

**Impact:** Logging

**ADF\_FACES-60078: Forcing the client to reload the page, because component with ID: {0} was not registered for Active Data.**

**Cause:** Component was not registered properly.

**Action:** Register the component for Active Data.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60079: The 'availableViews' attribute of the calendar contains 'month' but not 'day'. If 'month' is present, 'day' is required as well.**

**Cause:** The calendar 'availableViews' is configured to show month view but not day view.

**Action:** Correct the availableViews attribute to include 'day'.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60080: The 'availableViews' attribute of the calendar does not contain any valid values.**

**Cause:** The calendar 'availableViews' attribute is specified but does not contain any recognized values.

**Action:** Correct the availableViews attribute to use a valid combination of values (all, day, month, week, list) or leave unspecified to show the default views (all) .

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60081: OutputStream already retrieved.**

**Cause:** OutputStream already retrieved.

**Action:** OutputStream should be null.

**Level:** 2



---

**Type:** ERROR  
**Impact:** Logging  
**ADF\_FACES-60082: Writer already retrieved.**  
**Cause:** Writer already retrieved.  
**Action:** Writer should be null.  
**Level:** 2  
**Type:** ERROR  
**Impact:** Logging  
**ADF\_FACES-60083: Response has already been committed.**  
**Cause:** Response has already been committed.  
**Action:** Do not change response once committed.  
**Level:** 2  
**Type:** ERROR  
**Impact:** Logging  
**ADF\_FACES-60084: Component does not support a default DragSource or the provided DragSource was invalid.**  
**Cause:** An IllegalArgumentException occurred.  
**Action:** Contact Oracle Support Services.  
**Level:** 2  
**Type:** INCIDENT\_ERROR  
**Impact:** Logging  
**ADF\_FACES-60085: Parent not an instance of EditableValueHolder: {0}**  
**Cause:** Validator tag requires an EditableValueHolder parent  
**Action:** Add validator to an EditableValueHolder parent  
**Level:** 2  
**Type:** INCIDENT\_ERROR  
**Impact:** Logging  
**ADF\_FACES-60086: Failed to create Validator for validatorId: {0}, binding: {1}**  
**Cause:** A valid validatorId or binding has to be specified  
**Action:** Check validator's validatorId and binding  
**Level:** 2  
**Type:** INCIDENT\_ERROR  
**Impact:** Logging  
**ADF\_FACES-60089: An attempt to store a file larger than the configured value ({0}) for oracle.adf.view.rich.portal.FILE\_DOWNLOAD\_MAX\_DISK\_SPACE was encountered.**  
**Cause:** A call to a method on a FileDownloadActionListener resulted in a file being stored on the file system. The oracle.adf.view.rich.portal.FILE\_DOWNLOAD\_MAX\_DISK\_SPACE parameter in web.xml was either not

---

configured so the default limit of 2MB was exceeded, or the file was larger than the configured value.

**Action:** Either add or update the oracle.adf.view.rich.portal.FILE\_DOWNLOAD\_MAX\_DISK\_SPACE context-param in web.xml to allow for the desired max file size.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60094: Unrecognized feature in PanelCollection featuresOff attribute: {0}.**

**Cause:** An invalid feature name used in PanelCollection featuresOff attribute.

**Action:** Use a valid feature name. Feature names are case-sensitive. Refer to the PanelCollection tag docs.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_FACES-60096: Server Exception during PPR, #{0}**

**Cause:** An exception was thrown durring a PPR request.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60097: For more information, please see the server's error log for an entry beginning with: {0}**

**Cause:** An exception was thrown durring a PPR request.

**Action:** Please look in the servers error log for more details on this error.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_FACES-60098: Faces lifecycle receives unhandled exceptions in phase {0}**

**Cause:** An exception was not handled by any error handler.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

---

## ADF-MNC-10000 to ADF-MNC-50073

**ADF-MNC-10000: Cannot find schema resource at {0}.**

**Cause:** Schema file is missing.

**Action:** Place Schema file in the required location.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADF-MNC-10001: Problem registering schema {0}, exception = {1}.**

**Cause:** Schema file is invalid.

**Action:** Fix Schema file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADF-MNC-10002: Cannot instantiate rendering class {0} for platform {1}, exception = {2}.**

**Cause:** Exception occurred during creation of rendering kit.

**Action:** Check ADF Mobile Client configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADF-MNC-10003: {0} attribute is missing for one of the platforms in {1}.**

**Cause:** Required attribute missing in configuration file.

**Action:** Check ADF Mobile Client configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADF-MNC-10004: Duplicate platform with id = {0}, display value = {1} found in {2}.**

**Cause:** Duplicate Platform Id specified in configuration file.

**Action:** Check ADF Mobile Client configuration file.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**ADF-MNC-10005: {0} element is missing in {1}.**

**Cause:** Required element missing in configuration file.

**Action:** Check ADF Mobile Client configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADF-MNC-10006: Missing or invalid width/height attribute found for one of the form factors in {0}, exception = {1}.**

**Cause:** Width/Height attribute is missing or invalid in the configuration file.

**Action:** Check ADF Mobile Client configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADF-MNC-10007: Form factor element has negative width/height attribute defined in {0}, width = {1}, height = {2}.**

**Cause:** Width/Height attribute has negative value in configuration file.

**Action:** Check ADF Mobile Client configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADF-MNC-10008: Missing or invalid idref attribute found for {0} in {1}, idref = {2}.**

**Cause:** idref missing or invalid in configuration file.

**Action:** Check ADF Mobile Client configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADF-MNC-10009: Rendering kit factory class is not specified for id = {0} in {1}.**

**Cause:** Missing rendering kit factory class in configuration file.

**Action:** Check ADF Mobile Client configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADF-MNC-10010: Platform {0} does not have a rendering kit mapping defined in {1}.**

**Cause:** Rendering kit mapping missing in configuration file.

**Action:** Check ADF Mobile Client configuration file.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**ADF-MNC-10011: Problem opening configuration file {0}, exception = {1}.**

**Cause:** Exception opening configuration file.

**Action:** Check ADF Mobile Client configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADF-MNC-10012: Image repository is not specified for {0}.**

**Cause:** Missing image repository in configuration file.

**Action:** Check ADF Mobile Client configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADF-MNC-10013: Invalid configuration file for control {0}. The control will be loaded using default configuration.**

**Cause:** Exception loading control configuration file.

**Action:** Check control configuration file in image repository.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADF-MNC-10014: Invalid {0} attribute found for control id = {1}.**

**Cause:** Invalid attribute in mcx file.

**Action:** Check mcx file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADF-MNC-10015: Unable to resolve EL = {0}.**

**Cause:** Exception occurred while resolving EL expression.

**Action:** Check EL expression in mcx file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADF-MNC-10016: Missing or invalid group/index/weight attribute found for one of the default menu items in {0}, exception = {1}.**

**Cause:** Group/Index/Weight attribute is missing or invalid in the configuration file.

**Action:** Check ADF Mobile Client configuration file.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**ADF-MNC-10017: Invalid group/index attribute found for one of the default menu items in {0}, group = {1}, index={2}.**

**Cause:** Group/Index attribute is not in the valid range of 0 to 65535.

**Action:** Check ADF Mobile Client configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADF-MNC-10018: Invalid weight attribute found for one of the default menu items in {0}, weight = {1}.**

**Cause:** Weight attribute has negative value in configuration file.

**Action:** Check ADF Mobile Client configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADF-MNC-10019: An error occurred when attempting to read or write a record in table REPLAY\_TYPE with TYPE\_NAME value "{0}"**

**Cause:** A database error occurred.

**Action:** Ensure that the required database is accessible and is configured properly for Transaction Replay Service. If necessary, run the TRS configuration wizard to reconfigure TRS for the mobile application.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADF-MNC-10020: Failed to find record in table REPLAY\_TYPE with TYPE\_NAME value "{0}" when it is expected to exist. Run the TRS configuration wizard to reconfigure TRS for your mobile application.**

**Cause:** The specified database record does not exist in table REPLAY\_TYPE when it is expected to exist.

**Action:** Run the TRS configuration wizard to reconfigure TRS for your mobile application.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADF-MNC-10021: Failed to update a record in database table REPLAY\_TYPE. The database record has Type Name "{0}"**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**ADF-MNC-10022:** Type Name "{0}" conflicts with an existing record in database table REPLAY\_TYPE. Each type name must be unique. Specify a different type name.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADF-MNC-10023:** A database access error occurred.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADF-MNC-10024:** The chosen database connection "{0}" is not valid. Run the Transaction Replay Service configuration wizard to choose a valid database connection that identifies where the ADFmc Transaction Replay Schema is deployed.

**Cause:** Cannot find or validate the selected database connection indicated in the message.

**Action:** Run the Transaction Replay Service configuration wizard for the mobile application to choose a valid database connection.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADF-MNC-10025:** The chosen database connection is not valid. Connection Name: "{0}", Connection Store Name: "{1}"

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADF-MNC-10026:** The chosen database connection is corrupt. Connection Name: "{0}", Connection Store Name: "{1}". Run the TRS Configuration Wizard.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**ADF-MNC-10027: Cannot update file adf-config.xml to configure Transaction Replay Service for mobile application.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADF-MNC-10027: TRS configuration has been corrupted. To fix it, run the Transaction Replay Service configuration wizard to configure your mobile application to use Transaction Replay Service.**

**Cause:** Corrupt internal metadata has been detected in the project .JPR file for the Transaction Replay Service configuration wizard.

**Action:** Run the Transaction Replay Service configuration wizard to configure Transaction Replay Service for your mobile application. This will fix the problem by overwriting the corrupt metadata.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADF-MNC-50000: Could not open {0}.**

**Cause:** File is missing.

**Action:** Check that location and file both exist.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**ADF-MNC-50001: Corrupt COD: {0}.**

**Cause:** The COD file is corrupt.

**Action:** Delete the COD file and attempt to regenerate it.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**ADF-MNC-50002: Error: The specified module was rejected by the device and cannot be loaded.**

**Cause:** The file is corrupt.

**Action:** Delete the file and attempt to regenerate it.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**ADF-MNC-50003: Unknown Error: Examine logging information for additional details**

**Cause:** An unknown error occurred.

**Action:** Examine logging information for additional details.



---

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50004: BlackBerry JDE directory not specified. Set this in JDeveloper Preferences on the Mobile Client panel.**

**Cause:** BlackBerry JDE directory not specified.

**Action:** Set the BlackBerry JDE directory in JDeveloper Preferences on the Mobile Client panel.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50005: Could not create destination directory {0}**

**Cause:** Location may have disk problem.

**Action:** Examine disk for problems or permission issues.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**ADF-MNC-50006: Could not create directory {0}**

**Cause:** Location may have disk problem.

**Action:** Examine disk for problems or permission issues.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**ADF-MNC-50007: Illegal install directory (must be absolute): {0}**

**Cause:** Illegal install directory specified. This cannot be relative.

**Action:** Change to legal installation directory.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50008: Illegal source path (must be absolute): {0}**

**Cause:** Illegal source path specified. This cannot be relative.

**Action:** Change to legal source path.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50009: File not found: {0}**

**Cause:** File being added to CAB cannot be found.

**Action:** Check packaging directory for file.

---

**Level: 1**  
**Type: ERROR**  
**Impact: Deployment**  
**ADF-MNC-50010: Invalid argument (CPU): {0}**  
**Cause:** Specified CPU is not supported.  
**Action:** Select a supported CPU value.

**Level: 1**  
**Type: ERROR**  
**Impact: Deployment**  
**ADF-MNC-50011: Mobile server connection not specified.**  
**Cause:** No mobile server connection has been specified.  
**Action:** Select a mobile server connection.

**Level: 1**  
**Type: ERROR**  
**Impact: Deployment**  
**ADF-MNC-50012: Cannot find connection {0} in {1}.**  
**Cause:** Specified connection cannot be found.  
**Action:** Select a different connection.

**Level: 1**  
**Type: ERROR**  
**Impact: Deployment**  
**ADF-MNC-50013: Mobile Client application failed to deploy to BlackBerry device.**  
**Cause:** Device or device connection may not be working.  
**Action:** Examine device and device connection. Consider restarting device.

**Level: 1**  
**Type: ERROR**  
**Impact: Deployment**  
**ADF-MNC-50014: General failure deploying package to device.**  
**Cause:** Device or device connection may not be working.  
**Action:** Examine device and device connection. Consider restarting device.

**Level: 1**  
**Type: ERROR**  
**Impact: Deployment**  
**ADF-MNC-50015: Connection timeout attempting to deploy package to device.**  
**Cause:** Device or device connection may not be working.  
**Action:** Examine device and device connection. Consider restarting device.

**Level: 1**  
**Type: ERROR**

---

**Impact:** Deployment

**ADF-MNC-50016: Error attempting to deploy package to device: {0} not found.**

**Cause:** Application CAB not found after packaging.

**Action:** Check packaging directory for file.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50017: Error attempting to deploy package to device: {0} found on device, but overwrite flag not set.**

**Cause:** Application CAB already exists on device.

**Action:** Delete CAB from device.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50018: Error attempting to deploy package to device: Could not write {0} to device.**

**Cause:** Device storage might be full.

**Action:** Check device storage for available space and permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50019: Error attempting to deploy package to device: Could not execute {0} on device.**

**Cause:** User might not have permissions.

**Action:** Check user permissions on device.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50020: Error attempting to deploy package to device: Could not create directory {0} on device.**

**Cause:** User might not have permissions.

**Action:** Check user permissions on device.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50021: Error attempting to deploy package to device: Unknown error code ({0}).**

**Cause:** An unknown error occurred.

**Action:** Examine logging information for additional details.

---

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50022: Mobile Client Runtime failed to deploy to BlackBerry device.**

**Cause:** There was a problem deploying the ADF Mobile Client Runtime library to the BlackBerry device.

**Action:** Examine logging information for additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50023: Failed to deploy application debug files to BlackBerry simulator directory.**

**Cause:** JDeveloper could not deploy application debug files to BlackBerry simulator directory.

**Action:** Make sure you have write privileges for BlackBerry simulator directory.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50024: Exception caught: {0}**

**Cause:** Exception caught while updating root-task-flow in adf-config.xml.

**Action:** Check adf-config.xml for write permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50025: File exists: {0}**

**Cause:** File exists in destination location preventing copy operation.

**Action:** Delete file.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50026: BlackBerry JDE directory specified refers to a location that does not exist. Set this in JDeveloper Preferences on the Mobile Client panel.**

**Cause:** BlackBerry JDE directory does not exist.

**Action:** Set the BlackBerry JDE directory in JDeveloper Preferences on the Mobile Client panel.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50027: Mobile Client application failed to deploy to BlackBerry simulator.**

---

**Cause:** Device simulator or simulator connection may not be working.

**Action:** Examine device simulator and simulator connection. Consider restarting device simulator.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50028: BlackBerry simulator directory not specified. Set this in JDeveloper Preferences on the Mobile Client panel.**

**Cause:** BlackBerry simulator directory not specified.

**Action:** Set the BlackBerry simulator directory in JDeveloper Preferences on the Mobile Client panel.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50029: BlackBerry simulator directory specified refers to a location that does not exist. Set this in JDeveloper Preferences on the Mobile Client panel.**

**Cause:** BlackBerry simulator directory specified refers to a location that does not exist.

**Action:** Set the BlackBerry simulator directory in JDeveloper Preferences on the Mobile Client panel.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50030: Error attempting to deploy package to device: There is not enough free space on device.**

**Cause:** There is not enough free space on device.

**Action:** Attempt to free up space on device by removing unnecessary applications or files.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50031: Mobile Client Runtime failed to deploy to BlackBerry simulator.**

**Cause:** There was a problem deploying the ADF Mobile Client Runtime library to the BlackBerry simulator.

**Action:** Examine logging information for additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50032: Mobile Client Runtime failed to deploy to BlackBerry device as the device is not connected.**

**Cause:** BlackBerry device was not detected

---

**Action:** Connect the BlackBerry device and try the operation again.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50033: Failed to delete all old files in the Deployment Folder at {0}**

**Cause:** Some or all old files were not deleted from the deployment folder

**Action:** Verify user file privileges and try the operation again.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50034: Failed to create Deployment folder: {0}**

**Cause:** Unable to create deployment folder

**Action:** Verify user privileges and try the operation again.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50035: The Client Database Name must be alpha-numeric and 1 to 28 characters long.**

**Cause:** The client database name contains invalid characters or is not the correct length.

**Action:** Rename the client database to contain alpha-numerical characters only and ensure its length is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50036: The path of the standalone database must be between 1 and 255 characters long.**

**Cause:** The path to the location of the standalone database is not specified or has an invalid length.

**Action:** Specify a valid path to the location of the database and ensure its length is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50037: The path of the standalone database script must between 1 and 255 characters long.**

**Cause:** The path to the location of the standalone database initialization script has an invalid length.

**Action:** Specify a valid path to the location of the script contained in the application JAR file and ensure the path has a valid length.

---

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50038: Failed to obtain the workspace.**

**Cause:** Context information did not contain a valid value for the workspace property.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50039: Failed to locate a project containing adf-config.xml.**

**Cause:** The workspace either does not have a project containing the 'ADF Mobile Client UI' technology or has an invalid or missing adf-config.xml configuration file.

**Action:** Ensure the workspace has a 'Mobile Client View Controller Project' containing the 'ADF Mobile Client UI' technology. Also, verify that the project has a valid adf-config.xml configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50040: Failed to get the client database. Exception message: {0}**

**Cause:** An exception occurred when attempting to obtain the client database configuration value.

**Action:** Check the log file for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50041: Failed to save the client database. Exception message: {0}**

**Cause:** Failed to update adf-config.xml or failed to determine if a publication already exists for the application.

**Action:** Check adf-config.xml for write permissions. Verify the data publication configuration is correct and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50042: Deployment failed as Preverify returned an error code.**

**Cause:** Preverify utility failed to preverify the application jar file.

**Action:** Check the log file for more details.

**Level:** 1

**Type:** ERROR

---

**Impact:** Deployment

**ADF-MNC-50043: Deployment failed as RAPC returned an error code.**

**Cause:** RAPC utility failed.

**Action:** Check the log file for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50044: Application Name cannot be empty**

**Cause:** Application name field in BlackBerry Deployment Options panel was empty.

**Action:** Valid application name is required to deploy the application on BlackBerry device.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50045: Application Name cannot contain any of the following characters:**

/ ? : \ \* " < > | -

**Cause:** BlackBerry application name contained one of the un-supported characters.

**Action:** Remove un-supported characters from the BlackBerry application name.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50046: Application Name cannot begin with '.'**

**Cause:** BlackBerry application name contained period in the beginning of the name.

**Action:** Remove the period from the beginning of the BlackBerry application name.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50047: Application Name cannot be empty**

**Cause:** Application name field in Windows Mobile Deployment Options panel was empty.

**Action:** Valid application name is required to deploy the application on Windows Mobile device.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50048: Application Name cannot contain any of the following characters:**

/ ? : & \ \* " < > | # %



---

**Cause:** Windows Mobile application name contained one of the un-supported characters.

**Action:** Remove un-supported characters from the Windows Mobile application name.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50049: Application Name cannot begin or end with '.'**

**Cause:** Windows Mobile application name contained period in the beginning or ending of the name.

**Action:** Remove the period from the beginning and ending of the Windows Mobile application name.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50050: Application Name cannot be Windows system reserved names, including CON, AUX, PRN, COM1 or LPT2**

**Cause:** Windows Mobile application name used one of the Windows system reserved names.

**Action:** Modify Windows Mobile application name not to use any Windows system reserved names as specified.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50051: Unable to locate {0}. Make sure to enter valid path.**

**Cause:** Invalid Icon file path was entered.

**Action:** Verify the path entered.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50052: Selected icon file is not within the project directory. Please select the icon from within the following project directory: {0}**

**Cause:** The icon file was selected from outside the project directory.

**Action:** Select the icon file from within the project directory. Copy the icon in the project if it is not there.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50053: File type is not a supported icon type. Please provide supported icon type ({0}).**

**Cause:** Invalid Icon file type selected

---

**Action:** Select one of the supported file types only.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50054: Invalid parameter detected in method {0}. Parameter {1} is null or empty.**

**Cause:** Internal programming error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50055: Invalid parameter detected in method {0}. The value {1} is not allowed for a ADF setting of {2}.**

**Cause:** Internal programming error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50056: Failed to obtain a database provider for connection named {0}.**

**Cause:** Unable to obtain connection information for the Oracle Mobile Server Repository.

**Action:** Verify the database connection definition for the Oracle Mobile Server Repository is correct and ensure the database is available.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50057: Connection with ActiveSync could not be established. Ensure that PC-to-device/emulator connectivity is working correctly. Restarting JDeveloper may restore communications. See ADF Mobile Client documentation on Troubleshooting if the problem persists.**

**Cause:** JDeveloper could not connect to ActiveSync and initialize communication channel.

**Action:** Restart Windows Mobile Emulator, Windows Mobile Emulator Manager and ActiveSync. Ensure that PC-to-device/emulator connectivity is working correctly. Restarting JDeveloper may restore communications. See ADF Mobile Client documentation on Troubleshooting if the problem persists.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50058: Method {0} detected a invalid null parameter {1}.**

**Cause:** Internal programming error.

---

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50059: MDK is not installed or the path is not set. Publication is not created.**

**Cause:** The location to your Oracle Database Lite installation is not configured.

**Action:** Specify the location to your Oracle Database Lite installation available as an ADF Mobile Client preference option.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50060: The TRS database is either not configured correctly or does not have the TRS schema installed. TRS Publication is not created.**

**Cause:** The database may not be available or does not have the TRS schema installed.

**Action:** Verify the database is available and has the TRS schema installed.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50061: Detected an invalid profile type.**

**Cause:** Internal programming error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50062: There are no entity objects defined in the application. The Synchronization Publication deployment profile cannot be edited unless there are entity objects to be synchronized in the application.**

**Cause:** The application does not have entity objects imported from an ADF library.

**Action:** Import entity objects from an ADF library using the 'Business Components from ADF Library' wizard.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50063: Could not find dummy class file: {0}**

**Cause:** ADFMC\_Dummy.class file is required but was not found in the source location

**Action:** Check with the administrator.

---

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50064: You have specified an application schema outside of the database where the mobile server repository schema is installed. You must run the "apprepwizard" to install the remote application repository and then specify the password in the "Remote Application Repository Credential" section.**

**Cause:** The application schema and Oracle Mobile Server Repository schema are in different databases.

**Action:** Run the "apprepwizard" and specify the credential needed to access the application schema.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50065: Failed to determine if the connection {0} has the TRS Schema installed. Exception: {1}.**

**Cause:** A database error occurred.

**Action:** Verify the database containing the TRS Schema is available and examine logging information for additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50066: Connection {0} does not have the TRS Schema installed. Please select a different connection or install the TRS Schema and try again.**

**Cause:** The schema does not have the TRS tables installed.

**Action:** Install the TRS schema.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50067: The connection, {0}, is not valid and has been reset.**

**Cause:** The TRS connection definition was not valid.

**Action:** Verify the database containing the TRS schema is available.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50068: Failed to get the TRS configuration from the profile.**

**Cause:** The project did not contain TRS configuration options.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Deployment

**ADF-MNC-50069: Failed to establish a connection to {0}. Exception: {1}.**

**Cause:** A connection exception occurred when connecting to the database.

**Action:** Verify the connection configuration is correct and the database is online and available.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50070: Failed to initialize the TRS Publication panel. Exception: {0}.**

**Cause:** The panel failed to initialize.

**Action:** Check the log file for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50071: Mobile server repository connection information must be entered first.**

**Cause:** There is no connection configuration for the Oracle Mobile Server Repository schema or the connection is not valid.

**Action:** Verify there is a valid connection definition for the Oracle Mobile Server Repository schema.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50072: Windows Mobile deployment tool file not found: {0}**

**Cause:** The PPCDeployer DLL file is missing. Windows Mobile deployment requires this file.

**Action:** Check the location of the PPCDeployer.dll. Reinstall the ADF Mobile Client extension to restore this file

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADF-MNC-50073: Windows Mobile deployment tool file is corrupt, or not supported on this operating system: {0}**

**Cause:** The PPCDeployer DLL file is present, but it cannot be loaded correctly. It is either corrupt, or being invoked on an unsupported operating system.

**Action:** Reinstall the ADF Mobile Client extension to restore this file. Perform this operation in a Windows operating system environment.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment



---

## ADF\_TRINID-00001 to ADF\_TRINID-30336

**ADF\_TRINID-00001: Could not find FacesBean class {0}**

**Cause:** FacesBean class name could not be found.

**Action:** Log a bug against the application. Check that the jsf jars are all installed correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00002: Could not create instance of FacesBean {0}**

**Cause:** IllegalArgumentException

**Action:** Log a bug against the application. Check that the jsf jars are all installed correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00003: No faces-bean.properties files located**

**Cause:** Could not find the faces-bean.properties file in any jar

**Action:** Log a bug against the application. Check that the jsf jars are all installed correctly.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**ADF\_TRINID-00004: Could not load {0}**

**Cause:** Cannot find the url

**Action:** Log a bug against the application. Check that the jsf jars are all installed correctly. Check that the url is written correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00005: Error on trying to create new component instance for {0}**

**Cause:** Error in ChangeManager

---

**Action:** Log a bug against the application. Check that the Trinidad and jsf jars are all installed correctly.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-00006: Conversion class: {0} not of type {1}**

**Cause:** Error in ChangeManager

**Action:** Change the type so that it can be converted or log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-00007: Unable to instantiate converterClass: {0}**

**Cause:** Error in ChangeManager

**Action:** Make sure the converter class can be instantiated or log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-00008: Saved child count does not match current count (was {0}, now {1})**

**Cause:** Error in TreeState implementation

**Action:** Fix the TreeState implementation or log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-00009: State for some facets of {0} is missing, and will not be restored.**

**Cause:** Error in TreeState implementation

**Action:** Fix the TreeState facet state implementation or log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-00010: Saved facet state includes state for facet "{0}" which is not present in restored tree; discarding this state.**

**Cause:** Error in TreeState implementation

**Action:** Fix the TreeState facet state implementation or log a bug against the application.

**Level:** 1

**Type:** WARNING



---

**Impact:** Logging

**ADF\_TRINID-00011: Saved state includes state for a transient component: {0}**

**Cause:** Error in TreeState implementation

**Action:** Fix the TreeState state implementation or log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-00012: Could not find rowKey for clientRowKey:{0}**

**Cause:** Error in UIXCollection implementation when setting/getting clientRowKey

**Action:** Fix UIXCollection implementation or log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00013: There was no initial stamp state for currencyKey:{0} and currencyKeyForInitialStampState:{1} and stampId:{2}**

**Cause:** Error in UIXCollection

**Action:** Fix UIXCollection implementation or log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00014: Could not find renderer for {0} rendererType = {1}**

**Cause:** Error in renderer registration on render kit

**Action:** Log a bug against the application and make sure the Trinidad jars are installed and check the faces-config.xml files.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-00015: Could not load type properties**

**Cause:** Error getting faces-bean-type.properties from any jar

**Action:** Log a bug against the application and make sure the Trinidad and jsf jars are installed.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00016: Could not get resource key {0} from skin {1}**

**Cause:** ResourceBundle key does not exist in any resource bundle in framework or skin.

---

**Action:** Log a bug against the application or make sure the resource key exists in skin by checking the skin resource files (see trinidad-skins.xml).

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00017: Trying to attach RenderingContext to a thread that already had one.**

**Cause:** Thread already had a RenderingContext attached to it.

**Action:** Log a bug against the application. Call release()

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-00018: Cannot find RequestContext; two-digit-year-start will be defaulted**

**Cause:** RequestContext was not set up yet.

**Action:** Log a bug against the application. Make sure all jars are installed and filters are specified correctly in web.xml

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-00019: Cannot find RequestContext; TimeZone will default.**

**Cause:** RequestContext was not set up yet.

**Action:** Log a bug against the application. Make sure all jars are installed and filters are specified correctly in web.xml

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-00020: Failed to get hold of DecimalFormat for type: {0} decimal separator, number grouping separator, currency code will be defaulted based on locale {1}**

**Cause:** DecimalFormat not set up

**Action:** Log a bug against the application. Make sure all jars are installed and filters are specified correctly in web.xml

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-00021: RequestContext is null: decimal separator, number grouping separator, currency code will be defaulted based on locale**

**Cause:** RequestContext was not set up yet.

**Action:** Log a bug against the application. Make sure all jars are installed and filters are specified correctly in web.xml

---

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-00022: RequestContext is null, unable to get currency code**

**Cause:** RequestContext was not set up yet.

**Action:** Log a bug against the application. Make sure all jars are installed and filters are specified correctly in web.xml

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-00023: Number format was not instance of DecimalFormat: ignoring currency information while formatting.**

**Cause:** Number format was not set up correctly.

**Action:** Set up the Number format correctly or log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-00024: CollectionModel was set to null**

**Cause:** setCollectionModel was passed a null parameter

**Action:** Check the code that calls setCollectionModel or log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-00025: Invalid rowkey:{0} type:{1}**

**Cause:** ClassCastException rowkey should be an Integer

**Action:** Fix the rowkey to be an Integer or log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-00026: The viewId property in ViewIdPropertyMenuModel is null. The viewId property is needed to find the focus rowKey.**

**Cause:** viewIdProperty that is used to retrieve the viewId from a node in the tree is null.

**Action:** Set the viewIdProperty to be non-null or log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-00027: EL Expression {0} is invalid or returned a bad value**

---

**Cause:** ELExpression evaluation caused an exception  
**Action:** Fix the ELExpression to be valid or log a bug against the application.  
**Level:** 1  
**Type:** WARNING  
**Impact:** Logging

**ADF\_TRINID-00028: Exception opening URI {0}**  
**Cause:** Exception in openStream  
**Action:** Check the URI. Log a bug against the application.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Logging

**ADF\_TRINID-00029: Exception creating menu model {0}**  
**Cause:** Exception while creating menu model  
**Action:** Fix the menu model code or log a bug against the application.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Logging

**ADF\_TRINID-00030: Resource "{0}" at path "{1}" not found**  
**Cause:** Error calling getResource  
**Action:** Make sure the resource can be found or log a bug against the application.  
**Level:** 1  
**Type:** WARNING  
**Impact:** Logging

**ADF\_TRINID-00031: Unable to retrieve image data for icon of type {0}. Try using ContextImageIcon.**  
**Cause:** Icon openStream method called, and it is not supported.  
**Action:** Try using a ContextImageIcon in your code instead or log a bug against the application.  
**Level:** 1  
**Type:** WARNING  
**Impact:** Logging

**ADF\_TRINID-00032: Error parsing:{0}**  
**Cause:** Error parsing a service from a file in /META-INF/services  
**Action:** Check the services to make sure the urls are valid or log a bug against the application.  
**Level:** 1  
**Type:** WARNING  
**Impact:** Logging

---

**ADF\_TRINID-00033: error loading resource:{0}**

**Cause:** IOException while loading services

**Action:** Check your server or log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00034: Resource name "{0}" begins with a slash, which is not portable.**

**Cause:** resource name begins with a slash and it shouldn't.

**Action:** Fix the resource name to not begin with a slash or log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-00035: unable to load bundle {0}**

**Cause:** MissingResourceException; bundle could not be loaded.

**Action:** Fix the resource bundle so that it can be loaded or log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00036: Unable to load faces bundle {0}**

**Cause:** MissingResourceException

**Action:** Make sure the jsf jars are installed correctly. Make sure you can find the faces bundle. Log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00037: Unable to find ResourceLoader for ResourceServlet at servlet path:{0} Cause: Could not find resource:{1}**

**Cause:** Resource missing

**Action:** Make sure the resource can be found. Make sure the jars are installed correctly. Log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-00038: Trinidad ResourceServlet is running in debug mode. Do not use in a production environment. See the {0} parameter in /WEB-INF/web.xml**

**Cause:** Application is running in debug mode.

**Action:** Change the parameter in web.xml so that it is not running in debug mode.

**Level:** 1

---

**Type:** NOTIFICATION

**Impact:** Logging

**ADF\_TRINID-00039: Could not find context class loader.**

**Cause:** Thread.getContextClassLoader returned null.

**Action:** Fix the code so the ContextClassLoader can be loaded. Check the web server.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00040: Could not convert:{0} into int[]**

**Cause:** value is not a list of integers

**Action:** Change the value so that it can be converted to an array of integers. Log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00041: Could not parse value {0} into a Date using pattern "yyyy-MM-dd"; ignoring.**

**Cause:** date property's value is not in the correct format

**Action:** Nothing if the pattern it uses is ok. Otherwise log a bug against the application.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**ADF\_TRINID-00042: no parent <tr:componentRef> found!**

**Cause:** No parent componentRef component exists

**Action:** Log a bug against the application. Add a componentRef component on the page.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00043: Event {0} was delivered to a showDetail already in that disclosure state.**

**Cause:** Renderer delivered an unnecessary event or it set disclosed on its own instead of waiting for the disclosure event.

**Action:** Check the showDetail renderer code or log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-00044: Name "{0}" had already been registered.**

---

**Cause:** FacesBean addKey with name already added.

**Action:** Make sure you do not have duplicate names. Log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00045: Index "{0}" had already been registered.**

**Cause:** FacesBean addkey with index already added

**Action:** Make sure you do not have duplicate indexes. Log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00046: Type is already locked**

**Cause:** The FacesBean type object is locked, preventing further changes. .  
IllegalStateException, name already in keymap

**Action:** Fix code that has locked the FacesBean.Type. Log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00047: Property "{0}" cannot be bound.**

**Cause:** IllegalArgumentException, trying to set valuebinding on a key that does not support binding

**Action:** Do not valuebind the property or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00048: Key {0} cannot be used for lists**

**Cause:** IllegalArgumentException, PropertyKey is not a list and it should be to call this method.

**Action:** Fix the code so that the PropertyKey can be used for lists or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00049: Key {0} is a list key**

**Cause:** IllegalArgumentException, propertykey passed is a list and it shouldn't be.

**Action:** Fix code so that the propertyKey is not a list key or log a bug against the application.

---

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00050: Default value {0} is not assignable to type {1}**

**Cause:** IllegalStateException; PropertyKey constructor error

**Action:** Fix the PropertyKey constructor to pass in a non-null defaultValue parameter or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00051: Capability mask {0} not understood**

**Cause:** IllegalStateException; PropertyKey constructor error

**Action:** Check the PropertyKey API and use a valid Capability mask or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00052: Invalid index**

**Cause:** IllegalStateException; PropertyKey constructor error

**Action:** Check the PropertyKey API and provide a valid index to the PropertyKey constructor or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00053: Attempt to add a duplicate ID {0}**

**Cause:** ChangeManager, already a child with ID

**Action:** Remove duplicate ids or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00054: No node specified**

**Cause:** ChangeManager, componentNode passed to the method is null.

**Action:** Specify a node or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00055: component required**

**Cause:** ChangeManager, constructor error



---

**Action:** Check the ChangeManager API and code or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00056: DocumentFragment required**

**Cause:** ChangeManager, IllegalArgumentException

**Action:** Check the ChangeManager API and code or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00057: Cannot construct an AttributeChange with null attribute name.**

**Cause:** ChangeManager, IllegalArgumentException, constructor error

**Action:** Check the ChangeManager API and code or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00058: Cannot add a Change with either of facesContext, uiComponent or Change being null.**

**Cause:** ChangeManager, IllegalArgumentException, constructor error

**Action:** Check the ChangeManager API and code or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00059: Cannot construct an ChangeComponentProxy with null uiComponent.**

**Cause:** ChangeManager, IllegalArgumentException, constructor error

**Action:** Use a non null UIComponent parameter in the ChangeComponentProxy. Check the API. Log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00060: target class name must be provided**

**Cause:** ChangeManager, IllegalArgumentException

**Action:** Fix call to ChangeManager.registerDocumentFactory to provide a targetClassName or log a bug against the application.

---

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00061: converter class name must be provided**

**Cause:** ChangeManager, IllegalArgumentException

**Action:** Fix call to ChangeManager.registerDocumentFactory to provide a converterClassName or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00062: Parent cannot be null**

**Cause:** ChangeManager, null parameter

**Action:** Set the parent to be non-null or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00063: Cannot construct a RemoveChildChange with null childId.**

**Cause:** ChangeManager, IllegalArgumentException, constructor error

**Action:** Fix the constructor to provide a non-null childId or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00064: Cannot construct a RemoveFacetChange with null facetName.**

**Cause:** ChangeManager, IllegalArgumentException, constructor error

**Action:** Fix the constructor to use a non-null facetName or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00065: Cannot construct a ReorderChange with null childIds.**

**Cause:** ChangeManager, IllegalArgumentException, constructor error

**Action:** Fix the constructor to use a non-null childId or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00066: Cannot construct an AddFacetChange with either of facetName or facetComponent being null.**

---

**Cause:** ChangeManager, IllegalArgumentException, constructor error

**Action:** Fix the constructor to use a non-null facetName or facetComponent or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00067: Facet name must be specified**

**Cause:** ChangeManager, IllegalArgumentException, constructor error

**Action:** Fix the constructor to use a non-null facetName or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00068: index:{0} size:{1}**

**Cause:** ChildArrayList was not built properly

**Action:** Fix the code that builds the ChildArrayList or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00069: Bad PhaseId:{0}**

**Cause:** The phaseId passed to the method is invalid

**Action:** Make sure the phaseId is valid when calling this method or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00070: Illegal id: {0}**

**Cause:** The component has a bad id. First character might be a separator character or empty

**Action:** Fix the illegal component id in your page or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00071: wrappedEvent**

**Cause:** Illegal use of the WrapperEvent constructor. The wrappedEvent parameter was null.

**Action:** Fix the code that creates a WrappedEvent object or log a bug against the application.

---

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00072: RenderingContext was already released or had never been attached.**

**Cause:** An attempt was made to release an unattached RenderingContext

**Action:** Fix the code that tried to release the RenderingContext or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00073: Trying to release a different RenderingContext than the current context.**

**Cause:** An attempt was made to release a RenderingContext that is not the current RenderingContext.

**Action:** Fix the code that tried to release the RenderingContext or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00074: This is not an error. This trace is for debugging.**

**Cause:** This is not an error. This trace is for debugging the RequestContext class.

**Action:** No action needed since this is a debugging log message only. You can set the LOG to greater than FINEST to turn off the message.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00075: Trying to release a different RequestContext than the current context.**

**Cause:** An attempt was made to release a RequestContext that is not the current RequestContext.

**Action:** Make sure the release method was called by the same code that created the RequestContext or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00076: Factory already available for this class loader.**

**Cause:** IllegalStateException, an attempt was made to set in a map a RequestContextFactory that already exists for this classloader

**Action:** Do not call setFactory(RequestContextFactory factory) with a RequestContextFactory that already exists for the class loader or log a bug against the application.

---

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00077: Supplied FacesContext or UIComponent is null**

**Cause:** NullPointerException, the FacesContext or UIComponent passed to the method was null.

**Action:** Fix the code that caused this NullPointerException or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00078: FacesContext or UIComponent is null**

**Cause:** NullPointerException, the FacesContext or UIComponent passed to the method was null.

**Action:** Fix the code that caused this NullPointerException or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00079: Patterns should contain atleast one value and cannot be null**

**Cause:** IllegalArgumentException in ColorConverter; pattern is null or empty

**Action:** Fix the pattern in the ColorConverter or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00080: Cannot format given Object as a Color**

**Cause:** Object passed to method was not an instance of Color or Number

**Action:** Fix the Object that you pass into the method or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00081: Invalid attribute name {0}**

**Cause:** IllegalArgumentException, attribute name not found in FacesBean.Type

**Action:** Check your value bindings to make sure the attribute name exists or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00082: value:"{0}" is not of type java.util.Date, it is {1}**

---

**Cause:** ClassCastException, value is not a String or Date.

**Action:** Fix the value binding to point to a String or a Date or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00083: Invalid date style "{0}"**

**Cause:** IllegalStateException, the date style was not default, short, medium, long, full, or shortish.

**Action:** Fix the DateTimeConverter's dateStyle attribute or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00084: Invalid time style "{0}"**

**Cause:** IllegalStateException, the time style was not default, short, medium long or full.

**Action:** Fix the DateTimeConverter's timeStyle attribute or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00085: Invalid type "{0}"**

**Cause:** IllegalStateException, the type was not "date", "time", or "both"

**Action:** Fix the DateTimeConverter's type attribute or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00086: Illegal message id unexpected value {0}**

**Cause:** IllegalArgumentException in DateTimeConverter.

**Action:** Fix the message pattern or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00087: Illegal value for attribute "type" unexpected value {0}**

**Cause:** IllegalArgumentException

**Action:** Fix the DateTimeConverter's type attribute or log a bug against the application.

**Level:** 2

---

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00088: FacesContext or Component is null**

**Cause:** NullPointerException, the FacesContext or UIComponent passed to the method was null.

**Action:** Fix the code that caused the NullPointerException or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00089: Either "pattern" or "type" must be specified**

**Cause:** IllegalArgumentException, pattern and type parameters were both null.

**Action:** Set the NumberConverter's type or pattern attribute or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00090: "value" is not of type java.lang.Number**

**Cause:** IllegalArgumentException in NumberConverter

**Action:** Fix NumberConverter's value to be a Number or String or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00091: {0} is not a valid type**

**Cause:** IllegalArgumentException in NumberConverter. type should be number, currency or percent

**Action:** Fix NumberConverter's type attribute or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00092: Illegal pattern character "{0}"**

**Cause:** IllegalArgumentException in RGBColorFormat when checking the rgb pattern character

**Action:** Fix the rgb pattern in RGBColorFormat or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00093: Logger required**

---

**Cause:** TrinidadLogger constructor error

**Action:** Fix the code that creates the TrinidadLogger or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00094: Logger Name required**

**Cause:** Attempt was made to create a TrinidadLogger without a name which is a required parameter to this method.

**Action:** Check the call to TrinidadLogger.createTrinidadLogger or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00095: Class required**

**Cause:** Attempt was made to create a TrinidadLogger without a Class which is a required parameter to this method.

**Action:** Fix the call to TrinidadLogger.createTrinidadLogger or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00096: Package required**

**Cause:** Attempt was made to create a TrinidadLogger without a package which is a required parameter to this method.

**Action:** Fix the call to TrinidadLogger.createTrinidadLogger or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00097: rowData is null**

**Cause:** IllegalStateException in TreeModel or MenuModel. rowData is null.

**Action:** Fix rowData or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00098: Cannot exit the root container**

**Cause:** IllegalStateException in TreeModel or MenuModel.

**Action:** Fix code in the TreeModel or MenuModel regarding the path size or log a bug against the application.



---

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00099: Illegal value being set - value should be between -1 and maximum**

**Cause:** The constructor was called with the wrong value

**Action:** Fix the code that creates a DefaultBoundedRangeModel or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00100: Could not convert:{0} into a MenuModel**

**Cause:** IllegalArgumentException, the value could not be converted to a MenuModel.

**Action:** Fix the MenuModel's value so it can be converted to a MenuModel or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00101: rowKey**

**Cause:** IllegalStateException, PathHelper's rowKey has not been set and is null.

**Action:** Set PathHelper's rowKey or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00102: No Path element to pop**

**Cause:** IllegalStateException in PathHelper

**Action:** Fix the path or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00103: Could not clone**

**Cause:** CloneNotSupportedException, an attempt was made to call clone() on an object that is not clonable.

**Action:** Make sure the object is clonable before calling the method or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00104: No element to remove**

---

**Cause:** IllegalStateException, an attempt was made to remove a null element.

**Action:** Fix the rowKeySet code or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00105: todo**

**Cause:** This is only a todo. No cause.

**Action:** This is only a todo. No action.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00106: property is null**

**Cause:** SortCriterion constructor error, NullPointerException

**Action:** Fix the NullPointerException or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00107: No MenuContentHandler was registered.**

**Cause:** IllegalStateException, no MenuContentHandler was registered on services.

**Action:** Fix the code to register a MenuContentHandler or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00108: No RenderingContext**

**Cause:** IllegalStateException, RenderingContext is null and it shouldn't be.

**Action:** Log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00109: Resource path regular expression "{0}" does not have leading slash**

**Cause:** IllegalArgumentException, there was no leading slash and there should be.

**Action:** Fix the resource path by adding a leading slash or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

---

**ADF\_TRINID-00110: Factory already available for this class loader.**

**Cause:** IllegalStateException, SkinFactory already available for the class loader.

**Action:** Fix call to SkinFactory.setFactory or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00111: byte[] cannot be null**

**Cause:** NullPointerException, argument is null

**Action:** Fix the NullPointerException by setting byte[] to a non-null value or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00112: Actual Length:{0} offset:"{1} length:{2}**

**Cause:** IndexOutOfBoundsException, byte[], offset, length arguments passed to the method are incorrect.

**Action:** Fix the IndexOutOfBoundsException or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00113: FastMessageFormat only supports numeric arguments**

**Cause:** IllegalArgumentException, in FastMessageFormat while formatting.

**Action:** Fix the arguments passed into the method to be numeric or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00114: End of pattern not found**

**Cause:** IllegalArgumentException, in FastMessageFormat while formatting.

**Action:** Fix the FastMessageFormat pattern or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00115: FastMessageFormat: empty argument - {} - found**

**Cause:** IllegalArgumentException, in FastMessageFormat while formatting.

**Action:** Fix the call to the method to have a non-empty argument or log a bug against the application.

**Level:** 2

**Type:** ERROR

---

**Impact:** Logging

**ADF\_TRINID-00116: bundle not found**

**Cause:** No bundle was found.

**Action:** Fix the resource bundle (for example, the ApplicationFacesMessageBundle) so that it can be found by the code or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00117: resourceId is null**

**Cause:** NullPointerException. A null value was passed to a method.

**Action:** Fix the NullPointerException by passing in a non-null resourceid or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00118: The default FacesMessage.FACES\_MESSAGES cannot be found**

**Cause:** NullPointerException. FacesMessage.FACES\_MESSAGES from the jsf spec could not be found.

**Action:** Log a bug against the application. Check that the jsf jars are all installed correctly.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00119: FacesContext is null**

**Cause:** NullPointerException, FacesContext is null when it is passed to a method and it should not be null.

**Action:** Log a bug against the application. Check that the jsf jars are all installed correctly.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00120: custom message should be of type ValueBinding or String**

**Cause:** IllegalArgumentException, custom message in method was not of the correct type.

**Action:** Fix the customMessagePattern to be a ValueBinding or a String Object or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

---

**ADF\_TRINID-00121: Provider {0} did not return an object implementing {1}**

**Cause:** This error is no longer in the code.

**Action:** Log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00122: FacesContext.getRenderKit() returned null while trying to get the {0} service; please check your configuration.**

**Cause:** IllegalStateException, while getting a service in the Service utility code.

**Action:** Log a bug against the application. Check your configuration and check that the jsf jars are all installed correctly.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00123: FacesContext or Component is null**

**Cause:** NullPointerException, the FacesContext or UIComponent passed to the method was null.

**Action:** Log a bug against the application. Check your configuration and check that the jsf jars are all installed correctly.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00124: Encoding: {0} is unsupported by JVM**

**Cause:** IllegalCharsetNameException while trying to encode in the ByteLength Validator using an encoding that is not supported by the JVM.

**Action:** Check the encoding and check the JVM. Otherwise log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00125: "value" is not of type java.util.Date**

**Cause:** Value is not the type it should be.

**Action:** Change the value to be of type java.util.Date or log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-00126: Pattern null**

**Cause:** The regular expression's pattern is null and it shouldn't be.

**Action:** Fix the regular expression to be a non-null value or log a bug against the application.

---

**Level: 2**  
**Type: ERROR**  
**Impact: Logging**  
**ADF\_TRINID-00127: Invalid attribute name {0}**  
**Cause:** This error is no longer in the code.  
**Action:** Log a bug against the application.

**Level: 2**  
**Type: ERROR**  
**Impact: Logging**  
**ADF\_TRINID-00128: <f:view> was not present on this page; tag {0} encountered without an <f:view> being processed.**  
**Cause:** view tag was not present on the page.  
**Action:** Log a bug against the application. Add a view tag on your jsp page.

**Level: 2**  
**Type: ERROR**  
**Impact: Logging**  
**ADF\_TRINID-30001: The User-Agent "{0}" is unknown; creating an agent with null agent attributes.**  
**Cause:** The user-agent of the user's agent is unknown.  
**Action:** Use a known agent, like IE7 or Firefox.

**Level: 1**  
**Type: WARNING**  
**Impact: Logging**  
**ADF\_TRINID-30002: The agent type is unknown; creating an agent with null agent attributes.**  
**Cause:** The agent type of the user's agent is unknown.  
**Action:** Use a known agent, like IE7 or Firefox.

**Level: 1**  
**Type: WARNING**  
**Impact: Logging**  
**ADF\_TRINID-30003: could not get capabilities from capabilities document**  
**Cause:** RuntimeException when trying to get user agent's capabilities map  
**Action:** Use a known agent, like IE7 or Firefox. Log a bug against the Apache Trinidad framework.

**Level: 1**  
**Type: ERROR**  
**Impact: Logging**  
**ADF\_TRINID-30004: Could not locate Capabilities document**  
**Cause:** Could not find Capabilities document META-INF/agent/capabilities.xml

---

**Action:** Make sure the Apache Trinidad framework jars are installed. Log a bug against the Apache Trinidad framework.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30005: "Cannot resolve capabilities file"**

**Cause:** Exception while attempting to load the Capabilities document META-INF/agent/capabilities.xml

**Action:** Make sure the Apache Trinidad framework jars are installed. Log a bug against the Apache Trinidad framework.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30006: Invalid dependency found in include by reference**

**Cause:** Invalid dependency found while resolving the capabilities for a give capabilitiesNode

**Action:** Use a known agent, like IE7 or Firefox. Log a bug against the Apache Trinidad framework.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30007: Reference to id: {0} not found**

**Cause:** An attempt to get capabilities of node using a node refid, and refid was not found.

**Action:** Log a bug against the Apache Trinidad framework. Make sure the capabilities document is valid xml.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30008: Failed to parse capabilities document**

**Cause:** An IOException while parsing the XML-based capabilities document.

**Action:** Log a bug against the Apache Trinidad framework. Make sure the capabilities document is valid xml.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30009: Unable to parse agent string**

**Cause:** ParseException while parsing the agent string.

**Action:** Use a known agent, like IE7 or Firefox.

**Level:** 1

---

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30010: Element {0} has missing (or empty) attributes**

**Cause:** While attempting to parse a document, the element should have attributes but doesn't.

**Action:** Make sure the document that is being parsed has the correct syntax and attributes. Log a bug against the Apache Trinidad framework or the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30011: Failed to parse capabilities data document**

**Cause:** The capabilities data document was being parsed and failed.

**Action:** Log a bug against the Apache Trinidad framework. Make sure the capabilities document is valid xml.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30012: Unable to parse model string**

**Cause:** Error occurred while parsing the device nodes in the capabilities file

**Action:** Check the capabilities document. Make sure the capabilities document is valid xml. Log a bug against the Apache Trinidad framework.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30013: Capability data url {0} is invalid**

**Cause:** MalformedURLException while creating the URL.

**Action:** Check the capabilities document and make sure url is correctly formed.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30014: Could not find saved view state for token {0}**

**Cause:** Could not find the saved view state in the StateManager.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30015: No structure available and no root available**

**Cause:** While attempting to restore the state in the StateManager, no view root was available.



---

**Action:** Log a bug against the Apache Trinidad framework or against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30016: No structure available**

**Cause:** While attempting to restore the state in the StateManager, no structure was available.

**Action:** Log a bug against the Apache Trinidad framework or against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30017: Ignoring servlet init parameter:{0} unable to parse:{1}**

**Cause:** Attempting to parse servlet init parameter gave error.

**Action:** Check servlet init parameters. Check your web server.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30018: Could not load ViewHandler {0}**

**Cause:** Attempting to load viewhandler threw exception.

**Action:** Log a bug against the Apache Trinidad framework or against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30019: Apache Trinidad is running with time-stamp checking enabled. This should not be used in a production environment. See the {0} property in WEB-INF/web.xml**

**Cause:** time-stamp checking is enabled in web.xml.

**Action:** Turn off time-stamp checking in a production environment.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**ADF\_TRINID-30020: Could not load {0}**

**Cause:** Attempting to load an url and an exception occurred.

**Action:** Make sure the url can be found on the server. Log a bug against the Apache Trinidad framework or the application.

**Level:** 1

**Type:** ERROR

---

**Impact:** Logging

**ADF\_TRINID-30021: Could not instantiate UploadedFileProcessor**

**Cause:** Attempting to instantiate UploadedFileProcessor failed.

**Action:** Make sure the Trinidad jars are installed correctly. Log a bug against the Apache Trinidad framework.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30022: Trinidad is running in debug mode. Do not use in a production environment. See:{0}**

**Cause:** debug mode is turned on.

**Action:** Set debug to false in web.xml.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**ADF\_TRINID-30023: Element {0} is not understood**

**Cause:** Attempting to parse WEB-INF/trinidad-config.xml, an invalid element was found.

**Action:** Check the trinidad-config.xml file to make sure the element is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30024: Element {0} does not support EL expressions.**

**Cause:** Attempting to parse WEB-INF/trinidad-config.xml, and found an element that does not support EL binding EL bound.

**Action:** Check the trinidad-config.xml file and don't EL bind the element.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30025: "Element {0} only accepts integer values**

**Cause:** Found problem in WEB-INF/trinidad-config.xml.

**Action:** Check the trinidad-config.xml file.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30026: Could not find context class loader.**

**Cause:** Attempting to call Thread.currentThread().getContextClassLoader()

**Action:** Check the web server. Log a bug against the Apache Trinidad framework or the application.

---

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30027: Configurator services already initialized.**

**Cause:** While initializing the global configurator and the configurator services, discovered they are already initialized.

**Action:** Do not initial configurator services more than once.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30028: RequestContext had not been properly released on earlier request.**

**Cause:** RequestContext was checked to see if it was released and it wasn't.

**Action:** No action needed, since the code will clean this up. Check the code to make sure it is properly releasing the RequestContext.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30029: Unable to set request character encoding to {0}, because request parameters have already been read.**

**Cause:** Attempting to set the character encoding after parameters have been retrieved.

**Action:** Log a bug against the Apache Trinidad framework because the code is calling setCharacterEncoding at the wrong time.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30030: No 'DialogUsedRK' key available for returnFromDialog to do the right thing!**

**Cause:** Return from a dialog caused this error.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30031: Could not queue return event: no launch source**

**Cause:** Attempting to queue return event.

**Action:** Check your dialog code to make sure the launch source exists. Log a bug against the Apache Trinidad framework or the application.

**Level:** 1

**Type:** WARNING

---

**Impact:** Logging

**ADF\_TRINID-30032: RenderKit {0} does not support DialogRenderKitService, and cannot be used to launch dialogs; using a single window instead.**

**Cause:** Attempting to launch dialog.

**Action:** Use a renderkit that supports DialogRenderKitService or don't use DialogRenderKitService.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**ADF\_TRINID-30033: Apache Trinidad is using HttpSession for change persistence**

**Cause:** Notification to tell application developer that Trinidad is using HttpSession

**Action:** No action needed.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**ADF\_TRINID-30034: Unable to create ChangeManager:{0}**

**Cause:** Exception attempting to create the ChangeManager.

**Action:** Check your ChangeManager configuration. Log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30035: Could not find partial trigger {0} from {1}**

**Cause:** Attempting to find partial trigger.

**Action:** Make sure the partialTriggers are set to an existing component's id. View the jsp page in JDeveloper and JDeveloper will flag the errors for you. Log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30036: Failed to set character encoding {0}**

**Cause:** Attempting to set character encoding failed.

**Action:** Log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30037: Detecting request character encoding is disable.**

**Cause:** Exception getting character encoding from ServletRequest.

**Action:** Enable ServletRequest's character encoding if needed.

---

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30038: Failed to obtain ServletRequest#setCharacterEncoding()  
method: {0}**

**Cause:** Exception getting character encoding from ServletRequest

**Action:** Enable ServletRequest's character encoding if needed.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30039: The component is null, but it is needed for the client id, so no  
script written**

**Cause:** The UIComponent passed to the method is null.

**Action:** Make sure you pass an non-null UIComponent into the method. Log a  
bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30040: Client id is null, no script rendered**

**Cause:** The UIComponent passed to the method is null.

**Action:** Make sure you pass an non-null UIComponent into the method. Log a  
bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30041: Tried to create converter for type {0}, but could not, likely  
because no converter is registered.**

**Cause:** Attempting to create a converter failed.

**Action:** Log a bug against the application. Register a converter.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30042: Client id is null, no script rendered**

**Cause:** Attempting to create a converter failed.

**Action:** Log a bug against the application. Register a converter.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30043: Instantiation of Property {0} failed.**

---

**Cause:** Attempting to instantiate a Property caused an Exception.

**Action:** Log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30044: Couldn't get unique name!**

**Cause:** Attempting to get a unique name from the image cache failed.

**Action:** Log a bug against the Apache Trinidad framework. This exception should never happen.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30045: Elapsed time:{0} secs to encode gif**

**Cause:** Encoding gifs.

**Action:** No action needed.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**ADF\_TRINID-30046: laf "{0}" not found.**

**Cause:** Attempting to find the look and feel failed.

**Action:** Log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30047: Illegal character (space) in "name" attribute**

**Cause:** Attempting to parse the name attribute.

**Action:** Log a bug against the application. Check the name attribute and remove space

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30048: "name" attribute incorrectly set to "name"**

**Cause:** Attempting to parse the name attribute.

**Action:** Log a bug against the application. Check the name attribute and remove space

**Level:** 1

**Type:** WARNING

**Impact:** Logging

---

**ADF\_TRINID-30049: "name" attribute set to "target", which will cause Javascript errors.**

**Cause:** Attempting to parse the name attribute.

**Action:** Log a bug against the application. Check the name attribute and remove space

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30050: The value of the "{0}" attribute starts with "javascript:"; this is unnecessary, and in fact can lead to Javascript errors.**

**Cause:** Attempting to write the html to the page.

**Action:** Fix the attribute in the jsp page. Log a bug against the application or if it is in the renderer, against the Apache Trinidad framework

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**ADF\_TRINID-30051: Elements not closed:**

**Cause:** Attempting to write the html to the page.

**Action:** Fix the element in the jsp page. Log a bug against the application or if it is in the renderer, against the Apache Trinidad framework

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30052: Comments cannot include "--"**

**Cause:** Attempting to write the html to the page.

**Action:** Fix this in the jsp page. Log a bug against the application or if it is in the renderer, against the Apache Trinidad framework

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30053: Ending {0} when {1} expected. Passes:{2}**

**Cause:** Attempting to write the html to the page.

**Action:** Fix this in the jsp page. Log a bug against the application or if it is in the renderer, against the Apache Trinidad framework

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30054: Writing attribute outside of element**

**Cause:** Attempting to write the html to the page.

**Action:** Fix this in the jsp page. Log a bug against the application or if it is in the renderer, against the Apache Trinidad framework

---

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30055: Attribute "{0}" output twice; writing attribute as "duplicate\_{1}" instead.**

**Cause:** Attempting to write the html to the page.

**Action:** Fix this in the jsp page. Log a bug against the application or if it is in the renderer, against the Apache Trinidad framework

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30056: Element End name:{0} does not match start name:{1}**

**Cause:** Attempting to write the html to the page.

**Action:** Fix this in the jsp page. Log a bug against the application or if it is in the renderer, against the Apache Trinidad framework

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30057: GroupNode {0} refers to no valid node.**

**Cause:** Attempting to process the group node.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30058: Exception creating model {0}**

**Cause:** Attempting to create a menu model.

**Action:** Fix the menuModel. Log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30059: EL Expression {0} is invalid or returned a bad value.**

**Cause:** Attempting to create a menu model, and invalid EL expression was found.

**Action:** Fix the invalid EL expression. Log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30060: Resource bundle {0} could not be found.**

**Cause:** Attempting to load a bundle in the menu model.



---

**Action:** Make sure the resource bundle can be found. Log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30061: error closing file:{0}**

**Cause:** Attempting to process the region metatdata file.

**Action:** Fix the region metadata file to be a valid xml. Log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30062: Error getting region-metadata files:{0}**

**Cause:** Attempting to process the region metatdata file.

**Action:** Fix the region metadata file to be a valid xml and make sure it can be found on the filesystem. Log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30063: Error reading region-metadata file:{0}**

**Cause:** Attempting to process the region metatdata file.

**Action:** Fix the region metadata file to be a valid xml. Log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30064: Replaced jsUri {0} with {1} for componentType:{2}**

**Cause:** Attempting to process the region metatdata file.

**Action:** Fix the region metadata file to be a valid xml. Log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30065: Unknown element:{0} at {1}**

**Cause:** Attempting to process the region metatdata file.

**Action:** Fix the region metadata file to be a valid xml. Log a bug against the application.

**Level:** 1

**Type:** WARNING

---

**Impact:** Logging

**ADF\_TRINID-30066: <{0}> is missing at {1}**

**Cause:** Attempting to process the region metatdata file.

**Action:** Fix the region metadata file to be a valid xml. Log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30067: Exception at {0}**

**Cause:** Attempting to process the region metatdata file.

**Action:** Fix the region metadata file to be a valid xml. Log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30068: Instantiation of Renderer {0} failed**

**Cause:** Attempting to instantiate a Renderer failed.

**Action:** Check that your renderer is registered correctly in faces-config.xml. Log a bug against the application or Apache Trinidad framework.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30069: Renderer '{0}' not found for component family '{1}'**

**Cause:** Attempting to instantiate a Renderer failed.

**Action:** Check that your renderer is registered correctly in faces-config.xml. Log a bug against the application or Apache Trinidad framework.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30070: There is no SkinFactory**

**Cause:** Trying to find the SkinFactory failed. The SkinFactory was not registered.

**Action:** Log a bug against the application. Make sure the TrinidadFilter is installed since this registers the SkinFactory.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30071: The skin {0} specified on the requestMap will not be used because the styleSheetDocument id on the requestMap does not match the local skin's styleSheetDocument's id.**

**Cause:** A skin was specified on the requestMap but it can't be used.

---

**Action:** Log a bug against the application. Check to make sure the jars on the portal server match the jars on the portlet server to make the skin's styleSheetDocument ids match.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30072: The skin {0} specified on the requestMap will not be used because its styleSheetDocument id was not in the requestMap and it is needed to compare with the local skin's styleSheetDocument's id to make sure the skins are the same.**

**Cause:** A skin was specified on the requestMap but it can't be used.

**Action:** Log a bug against the application. Check to make sure the jars on the portal server match the jars on the portlet server to make the skin's styleSheetDocument ids match. Also, send the styleSheetDocument id to the server as well as the skin id.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30073: The skin {0} specified on the requestMap will not be used because it does not exist.**

**Cause:** A skin was specified on the requestMap but it can't be used because it does not exist on the server.

**Action:** Log a bug against the application. Check to make sure the jars on the portal server match the jars on the portlet server to make the skin's styleSheetDocument ids match.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30074: Could not get skin {0} from the SkinFactory**

**Cause:** Attempted to get a skin failed.

**Action:** Log a bug against the application. The skin requested was not registered with the SkinFactory on startup. Make sure the TrinidadFilter is installed.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30075: The java.io.File handle ("javax.servlet.context.tempdir") is not set in the ServletContext**

**Cause:** Attempting to get the file handle from the ServletContext.

**Action:** Log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

---

**ADF\_TRINID-30076: No AdfRenderingContext available**

**Cause:** Attempting to get the RenderingContext failed.

**Action:** Check that your Trinidad jars are installed properly. Log a bug against the Apache Trinidad framework.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30077: Basic HTMLRenderKit could not be located**

**Cause:** Attempting to locate the HTMLRenderKit failed.

**Action:** Check that your Trinidad jars are installed properly.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30078: Could not find basic HTML renderer for {0}, type={1}**

**Cause:** Could not find basic HTML renderer.

**Action:** Check that your Trinidad jars are installed properly.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30079: Could not get stylesheet cache**

**Cause:** Attempting to get the stylesheet cache failed.

**Action:** Make sure your stylesheet directory is writable.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30080: Model not specified for the chart component.**

**Cause:** Attempting to get the model on the chart component failed.

**Action:** Specify the model for the chart component. Log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30081: Trains must be used inside of a form**

**Cause:** The train component is not inside a form component.

**Action:** Log a bug against the application. Put the train inside a form

**Level:** 1

**Type:** WARNING

**Impact:** Logging

---

**ADF\_TRINID-30082: Train expect a nodeStamp facet, no such facet was found for train {0}**

**Cause:** Problem found while rendering the train.

**Action:** Log a bug against the application. Set a nodeStamp facet on the train

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30083: Visible stop count must be > 0, found {0}**

**Cause:** Problem found while rendering the train.

**Action:** Log a bug against the application. Set the train visible count to > 0.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30084: Visible stop count must be an integer, found {0}**

**Cause:** Problem found while rendering the train.

**Action:** Log a bug against the application. Set the train visible count to > 0.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30085: 'nodeStamp' facet missing!**

**Cause:** Problem found while rendering the train.

**Action:** Log a bug against the application. Set a nodeStamp facet on the train

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30086: Frames must appear inside FrameBorderLayouts**

**Cause:** Problem found while rendering frames.

**Action:** Log a bug against the application. Set frame inside of frameborderlayout

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30087: No PPR-capable 'id' found for elements of {0}. This component has not written-out an 'id' attribute.**

**Cause:** Trying to PPR update components failed.

**Action:** Log a bug against the application. Add ids to your components.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

---

**ADF\_TRINID-30088: Invalid string attribute for chooseDate: {0}**

**Cause:** Attempting to convert value to a Date.

**Action:** Log a bug against the application. See the chooseDate documentation.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30089: Unable to encode URL '{0}' using encoding '{1}'**

**Cause:** Attempting to encode an url failed.

**Action:** Recheck your url to make sure it is valid. Log a bug against the Apache Trinidad framework.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30090: Sorting disabled; table is not in a form**

**Cause:** Attempting to render a table that is not in a form.

**Action:** Log a bug against the application. Add a form as a parent to the table.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30091: {0}: Column used outside of a Table**

**Cause:** Attempting to render a table that has a column outside of the table.

**Action:** Log a bug against the application. Put all column components inside a table component.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30092: Cannot add client side converter and validators as the node name is null**

**Cause:** Attempting to add client-side converters and validators to the page.

**Action:** Log a bug against the applicaton. Set the node name.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30093: Null validators iterator for {0}**

**Cause:** Attempting to process validators found null validator iterators.

**Action:** Log a bug against the application. Check the validators.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

---

**ADF\_TRINID-30094: There is already a converter on "{0}". There should only be one converter per component.**

**Cause:** More than one converter found on a component.

**Action:** Log a bug against the application. Ensure you have only one converter per component in your page.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30095: frame:{0} is missing attribute:{1}**

**Cause:** Missing attribute in frameborderlayout.

**Action:** Log a bug against the application. Add the missing attribute.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30096: Warning: illegal component hierarchy detected, expected UIXCommand but found another type of component instead.**

**Cause:** Did not find the expected command component in the hierarchy.

**Action:** Log a bug against the application. Check your component hierarchy in your page.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30097: Warning: NavigationLevelRenderer was looking for child property "{0}" but none was found, it is likely that an unexpected child component was found (expected CommandNavigationItem).**

**Cause:** Rendering navigationLevel component and did not find expected child.

**Action:** Log a bug against the application. Make sure CommandNavigationItem is a child of the navigationLevel component

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30098: PanelAccordion must be used inside of a form**

**Cause:** Rendering panelAccordion that was not in a form.

**Action:** Log a bug against the application. Make sure panelAccordion is inside a form.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30099: Error during partial-page rendering**

**Cause:** Rendering a partial-page pass failed.

---

**Action:** Log a bug against the application. Check your page to make sure you are using PPR correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30100: The poll component must be inside of a form; disabling poll {0}**

**Cause:** Rendering poll component that wasn't in a form component.

**Action:** Log a bug against the application. Make sure poll is inside a form

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30101: The number of items selected for shuttle '{0}' exceeds the total number of items in the shuttle. No selected items will be returned.**

**Cause:** Rendering the shuttle component and the selected items.

**Action:** Log a bug against the application. Check the shuttle component and its children.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30102: showDetail is not in a form, and will not function correctly**

**Cause:** Rendering showDetail component that wasn't in a form component.

**Action:** Log a bug against the application. Make sure showDetail is inside a form

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30103: Some entries in value of {0} not found in SelectItems: {1}**

**Cause:** Rendering a selectMany component found inconsistency in selectItem values.

**Action:** Log a bug against the application. Check your selectMany components and the selectItems.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30104: Could not find selected item matching value "{0}" in {1}**

**Cause:** Rendering a select component and found problem with the select items.

**Action:** Log a bug against the application. Check your select components and the value and selectItems

**Level:** 1

**Type:** WARNING



---

**Impact:** Logging

**ADF\_TRINID-30105: Table with id: {0} has no visible columns!**

**Cause:** Rendering a table found no visible columns.

**Action:** Log a bug against the application. Make sure your table has at least one visible column.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30106: The tree component must be used inside of a form.**

**Cause:** Rendering tree component that wasn't in a form component.

**Action:** Log a bug against the application. Make sure tree is inside a form

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30107: Couldn't find scriptlet: {0}**

**Cause:** Rendering a component and a scriptlet could not be found.

**Action:** Check the code that registers the scriptlet if this is in our component. Log a bug against the application or the Apache Trinidad framework.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30108: Unable to get resource {0}**

**Cause:** Rendering a scriptlet.

**Action:** Log a bug against the Apache Trinidad framework. Possibly a problem in the build system.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30109: Apache Trinidad is running with debug javascript. Do not use in a production environment. See the "+\_DEBUG\_JAVASCRIPT+" parameter in /WEB-INF/web.xml**

**Cause:** debug javascript is enabled in web.xml.

**Action:** Turn off debug javascript checking in a production environment in web.xml.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**ADF\_TRINID-30110: Illegal value:{0} for {1}**

**Cause:** Rendering the table component and found illegal banding interval.

---

**Action:** Log a bug against the application. See the table and column component documentation regarding column and row banding intervals.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30111: Unknown value for align:{0}**

**Cause:** Rendering the table component and found illegal value for the align attribute.

**Action:** Log a bug against the application. See the column component documentation for valid align attribute values.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30112: tableSelect components may only be used inside table and treeTable**

**Cause:** While rendering tableSelect component the valid parent component was not found.

**Action:** Log a bug against the application. Make sure tableSelect components are inside table or treeTable.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30113: nodeStamp facet on treeTable:{0} is missing or not of type UIXColumn**

**Cause:** While rendering a treeTable component, a problem with the nodeStamp facet was found.

**Action:** Log a bug against the application. See the treeTable documentation and check your jsp page.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30114: Unexpected tree state: focus rowKey is empty on an expand/collapse all request.**

**Cause:** While rendering a tree component an unexpected tree state was found.

**Action:** Log a bug against the application. See the treeTable or tree documentation and check your jsp page.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30115: Page contains no form, it will not work properly**

**Cause:** Rendering the page without a form component.

---

**Action:** Log a bug against the application. Make sure there is a form in the page

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30116: Only tr:showDetailItem is allowed as child of tr:panelTabbed.**

**Cause:** While rendering a panelTabbed component an illegal child was found.

**Action:** Log a bug against the application. Use showDetailItem as the child of panelTabbed.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30117: Value for component with id '{0}' is not a valid BoundedRangeModel instance**

**Cause:** Rendering component and found an invalid BoundedRangeModel.

**Action:** Log a bug against the application. See the BoundedRangeModel documentation.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30118: Resource "{0}" at path "{1}" not found**

**Cause:** While rendering the resource was not found.

**Action:** Make sure the resource exists. Log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30119: Could not find bundle {0}**

**Cause:** While rendering, a translation bundle could not be found.

**Action:** Log a bug against the Apache Trinidad framework. Make sure the jars are installed correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30120: Required attribute "{0}" not found.**

**Cause:** While rendering, a required attribute was not found.

**Action:** Set the required attribute on the component in the jsp file. Log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

---

**ADF\_TRINID-30121: {0} is not an understood child element**

**Cause:** While parsing a document, an unknown element was found.

**Action:** Log a bug against the application. Check your jsp page in JDeveloper so it can flag the errors.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30122: "{0}" is not an understood attribute**

**Cause:** While parsing the document, an unknown attribute was found.

**Action:** Log a bug against the application. Check your jsp page in JDeveloper so it can flag the errors.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30123: Only one child element is allowed here.**

**Cause:** While parsing the document, an error was found.

**Action:** Log a bug against the application. Check your jsp page in JDeveloper so it can flag the errors.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30124: Could not parse value of attribute: {0}**

**Cause:** While parsing the document, an error was found.

**Action:** Log a bug against the application. Check your jsp page in JDeveloper so it can flag the errors.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30125: Could not parse value of attribute: {0}, namespace={1}**

**Cause:** While parsing the document, an error was found.

**Action:** Log a bug against the application. Check your jsp page in JDeveloper so it can flag the errors.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30126: Unknown attribute: {0}**

**Cause:** While parsing the document, an error was found.

**Action:** Log a bug against the application. Check your jsp page in JDeveloper so it can flag the errors.

**Level:** 1

---

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30127: Unknown attribute: {0}, namespace={1}**

**Cause:** While parsing the document, an error was found.

**Action:** Log a bug against the application. Check your jsp page in JDeveloper so it can flag the errors.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30128: Error when parsing the skin css file. The property's name cannot be null or the empty string. The parser will ignore it. name is '{0}' and value is '{1}'**

**Cause:** While parsing the skin css file, an error was found.

**Action:** Log a bug against the application. Check your skin css file.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30129: Ignoring properties {0} because there is no corresponding selector.**

**Cause:** While parsing the skin css file, an error was found.

**Action:** Log a bug against the application. Check your skin css file.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30130: Error reading from the skin css file**

**Cause:** While parsing the skin css file, an error was found.

**Action:** Log a bug against the application. Check your skin css file.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30131: Can't add Skin with null skinId or null skin**

**Cause:** While registering skins, an error was found.

**Action:** Log a bug against the application. Check your trinidad-skins.xml file to make sure the skin is defined correctly.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30132: Can't get Skin with null skinId**

**Cause:** While retrieving a skin, an error was found.

---

**Action:** Log a bug against the application. Check your trinidad-skins.xml file to make sure the skin is defined correctly.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30133: Can't find a skin that matches family {0} and renderkit {1}, so we will use the simple skin**

**Cause:** While retrieving a skin, an error was found.

**Action:** Log a bug against the application. Check your trinidad-skins.xml file to make sure the skin is defined correctly. Check trinidad-config and the skin-family element. Make sure the skin's renderkitid matches the current renderkit id

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30134: Could not get the stylesheet document's timestamp because we couldn't open the connection.**

**Cause:** Trying to get the skin's stylesheet document's timestamp failed.

**Action:** Log a bug against the application. Check the stylesheet document file and directory to make sure it can be opened.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30135: The following skins extend each other in a circular fashion or the skin they extend does not exist:{0}**

**Cause:** While registering the skins from the trinidad-skins.xml files, an error was found.

**Action:** Log a bug against the application. Check all the trinidad-skins.xml files (even the ones in jars on the classpath) to fix any skins that extend others in a circular fashion.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30136: Unable to locate base skin "{0}" for use in defining skin of id "{1}", family "{2}", renderkit ID "{3}". Using the default base skin "{4}".**

**Cause:** While registering the skins from the trinidad-skins.xml files, an error was found.

**Action:** Log a bug against the application. Check all the trinidad-skins.xml files (even the ones in jars on the classpath) to make sure the base skin exists and do not extend a skin that doesn't exist.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

---

**ADF\_TRINID-30137: Error parsing:{0}**

**Cause:** While parsing the trinidad-skins.xml file, an error was found.

**Action:** Log a bug against the application. Check the trinidad-skins.xml files (even ones in jars) for format problems.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30138: error loading file:{0}**

**Cause:** While attempting to load the trinidad-skins.xml file, an error was found.

**Action:** Log a bug against the application. Check the trinidad-skins.xml files (even ones in jars) for format problems.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30139: Could not load style sheet: {0}**

**Cause:** Could not load the skin's css file.

**Action:** Log a bug against the application. Check the skin's css file to make sure it exists and the style-sheet-name url in trinidad-skins.xml is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30140: IOException during parse of {0}**

**Cause:** IOException while creating a skin's stylesheet document.

**Action:** Log a bug against the application. Check the stylesheet document.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30141: No styles found context - {0}**

**Cause:** While creating the skin's stylesheet document, no styles were found that matched the StyleContext.

**Action:** Log a bug against the application. There should always be base skin definitions for all contexts.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30142: IOException while creating file: {0}**

**Cause:** IOException while creating the skin's stylesheet document.

**Action:** Log a bug against the application.

**Level:** 1

---

Type: WARNING

Impact: Logging

**ADF\_TRINID-30143: Unable to generate the style sheet {0} in cache directory {1}. Please make sure that the cache directory exists and is writable.**

**Cause:** Error while generating skin's stylesheet.

**Action:** Log a bug against the application. Make sure that the cache directory exists and is writable.

Level: 1

Type: WARNING

Impact: Logging

**ADF\_TRINID-30144: IOException while opening file for writing: {0}**

**Cause:** Error while generating skin's stylesheet.

**Action:** Log a bug against the application. Check the cache directory to make sure it is writable.

Level: 1

Type: WARNING

Impact: Logging

**ADF\_TRINID-30145: The css file has hit IE's limit of 4095 CSS selectors. It has {0} selectors. The selectors after that will be ignored.**

**Cause:** Error while generating the skin's stylesheet.

**Action:** Log a bug against the application. You will need to simplify your skinning file if possible. Otherwise log a bug against Apache Trinidad.

Level: 1

Type: WARNING

Impact: Logging

**ADF\_TRINID-30146: Consecutive sub-element (::) syntax used in selector {0}. This is not supported.**

**Cause:** Problem found in skin's stylesheet css file.

**Action:** Log a bug against the application. The skin's css file has two pseudo-elements in one selector and that is illegal in CSS.

Level: 1

Type: WARNING

Impact: Logging

**ADF\_TRINID-30147: An url value delimited by url() is expected for the property '{0}' in style sheet '{1}'. Found: '{2}'.**

**Cause:** Problem found in skin's stylesheet css file.

**Action:** Log a bug against the application. Check the skin's css file.

Level: 1

Type: WARNING

Impact: Logging



---

**ADF\_TRINID-30148: Invalid image uri '{0}' in style sheet '{1}'**

**Cause:** Problem found in skin's stylesheet css file.

**Action:** Log a bug against the application. Check the skin's css file.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30149: An empty URL was found in style sheet '{0}'**

**Cause:** Problem found in skin's stylesheet css file.

**Action:** Log a bug against the application. Check the skin's css file.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30150: "<style> elements must have either a name or a selector attribute**

**Cause:** Problem found in skin's XSS stylesheet.

**Action:** Log a bug against the application. Check the skin's XSS file.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30151: Could not parse import: {0}**

**Cause:** Problem found in skin's stylesheet.

**Action:** Log a bug against the application. Check the skin's stylesheet files.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30152: Import missing required href attribute**

**Cause:** Problem found in skin's stylesheet.

**Action:** Log a bug against the application. Check the skin's stylesheet files.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30153: 'componentType' attribute is required**

**Cause:** Problem found processing page.

**Action:** Log a bug against the application. Check your jsp page in JDeveloper so it can flag the errors.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

---

**ADF\_TRINID-30154: Could not find metadata for componentType:{0} in region-metadata**

**Cause:** Problem found processing page.

**Action:** Log a bug against the application. Check your jsp page in JDeveloper so it can flag the errors.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30155: There was no jspxUri for componentType:{0}**

**Cause:** Problem found processing page.

**Action:** Log a bug against the application. Check your jsp page in JDeveloper so it can flag the errors.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30156: attribute:{0} is missing on componentType:{1}**

**Cause:** Problem found processing page.

**Action:** Log a bug against the application. Check your jsp page in JDeveloper so it can flag the errors.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30157: facetRef must be inside of a UIComponent tag.**

**Cause:** Problem found processing page.

**Action:** Log a bug against the application. Check your jsp page in JDeveloper so it can flag the errors.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30158: Cannot find parent <tr:componentRef>>**

**Cause:** Problem found processing page.

**Action:** Log a bug against the application. Check your jsp page in JDeveloper so it can flag the errors.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30159: facetName is required on facetRef**

**Cause:** Problem found processing page.

**Action:** Log a bug against the application. Check your jsp page in JDeveloper so it can flag the errors.

---

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30160: validator tag is not inside a UIComponent.**

**Cause:** Problem found processing page.

**Action:** Log a bug against the application. Check your jsp page in JDeveloper so it can flag the errors.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30161: could not create validator for validatorId:{0} and binding:{1}**

**Cause:** Problem found creating the validator.

**Action:** Log a bug against the application. Check your jsp page in JDeveloper so it can flag the errors.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30162: attribute 'validatorId' is missing**

**Cause:** Problem found creating the validator.

**Action:** Log a bug against the application. Check your jsp page in JDeveloper so it can flag the errors.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30163: Could not parse value {0} into a Date using pattern "yyyy-MM-dd"; ignoring.**

**Cause:** Problem found parsing the date value.

**Action:** Log a bug against the application. Check the jsp page. Use the yyyy-MM-dd format.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**ADF\_TRINID-30164: No RendererFactory registered for components in namespace {0}**

**Cause:** RendererFactory not registered.

**Action:** Log a bug against the Apache Trinidad framework. Make sure the Trinidad and jsf jars are installed correctly.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

---

**ADF\_TRINID-30165: No Renderer registered for {0}**

**Cause:** Renderer was not registered.

**Action:** Log a bug against the Apache Trinidad framework or the application.  
Check the faces-config.xml file.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30166: Could not get image cache**

**Cause:** Could not find the image cache.

**Action:** Log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30167: Cannot convert {0} of class:{1} into DataObjectList**

**Cause:** Creating a DataObjectList adapter class around an object fails

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**ADF\_TRINID-30168: Could not convert {0} into a {1}**

**Cause:** Error converting a value into another value.

**Action:** Log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30169: Unsupported UINode:{0}, path = {1}**

**Cause:** Unsupported UINode found while rendering.

**Action:** Log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30170: Invalid value. Defaulting component with id '{0}' to indeterminate mode**

**Cause:** Invalid value rendering processing component.

**Action:** Log a bug against the application. Check your jsp page in JDeveloper so it can flag the errors.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

---

**ADF\_TRINID-30171: No form found for {0}**

**Cause:** Rendering a component that wasn't in a form component.

**Action:** Log a bug against the application. Make sure your form components are inside a form. Check your jsp page in JDeveloper so it can flag the errors.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30172: Could not get image provider for icon: {0}**

**Cause:** Error while attempting to get image provider.

**Action:** Log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30173: Could not get colorized icon for: {0}**

**Cause:** Error while attempting to get colorized image.

**Action:** Log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30174: Could not find icon with key given**

**Cause:** Error while attempting to get colorized image.

**Action:** Log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30175: Could not find renderer for alias {0}**

**Cause:** Error finding renderer.

**Action:** Check the faces-config.xml file to make sure the renderer is registered.  
Log a bug against the Apache Trinidad framework.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30176: Unable to flip icon '{0}' because it is not under the current request context, which is '{1}'**

**Cause:** Error trying to flip laf icon.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

---

**ADF\_TRINID-30177: Could not locate parent form for formValue {0}**

**Cause:** Rendering the page and couldn't find a form as a parent..

**Action:** Log a bug against the application. Make sure the formValue has a form parent.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30178: The component is null for node with local name {0}**

**Cause:** Error while finding component.

**Action:** Check the faces-config.xml file to make sure the component/renderers are registered. Log a bug against the Apache Trinidad framework.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30179: Could not get flipped icon for: {0}**

**Cause:** Error while trying to find a flipped icon.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30180: The node name is null and therefore no client side required validator added for node with local name {0}**

**Cause:** Error finding validator.

**Action:** Log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30181: Could not find class {0}**

**Cause:** Error finding class in Coercions.

**Action:** Make sure the jars are installed correctly. Log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30182: Could not load class {0}:{1}**

**Cause:** Error finding class in Coercions.

**Action:** Make sure the jars are installed correctly. Log a bug against the application.

**Level:** 1

---

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30183: Method {0} does not return an Icon**

**Cause:** Error attempting to retrieve an Icon.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30184: Could not find method {0} in {1}**

**Cause:** Error trying to find method.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30185: Could not find access {0} in {1}**

**Cause:** This error is no longer in the code.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30186: Required element 'skin-id' not found.**

**Cause:** Error in trinidad-skins.xml file.

**Action:** Log a bug against the application. Check the trinidad-skins.xml file and make sure your skin has a skin-id

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30187: Required element 'style-sheet-name' not found.**

**Cause:** Error in trinidad-skins.xml file.

**Action:** Log a bug against the application. Check the trinidad-skins.xml file and make sure your skin has a style-sheet-name

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30188: Required element 'id' not found.**

**Cause:** Error in trinidad-skins.xml file.

**Action:** Log a bug against the application. Check the trinidad-skins.xml file and make sure your skin has a unique id.

**Level:** 1

---

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30189: Required element 'family' not found.**

**Cause:** Error in trinidad-skins.xml file.

**Action:** Log a bug against the application. Check the trinidad-skins.xml file and make sure your skin has the skin-family set.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30190: Malformed property entry: {0}={1}**

**Cause:** Error in renderertype-localname.properties.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30191: Could not load renderer type to local name mapping.**

**Cause:** Error in renderertype-localname.properties.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30192: Encoding {0} is not supported at the client side. This will skip client side validation.**

**Cause:** Attempting to use an encoding the client doesn't support.

**Action:** Contact the system administrator to see if the encoding is supposed to be supported.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30193: The TrinidadFilter has not been installed. Apache Trinidad requires this filter for proper execution.**

**Cause:** Detected that the TrinidadFilter was not installed.

**Action:** Log a bug against the application. Install the TrinidadFilter; see web.xml

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ADF\_TRINID-30194: mergeCapabilities() may only be used with Agents created by this class.**

**Cause:** Attempting to merge capabilities with unsupported agent.



---

**Action:** Use a supported agent/browser. Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30195: Invalid Namespace: {0}**

**Cause:** Invalid namespace parsing capabilities document.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30196: Invalid Root Element: {0} {1}**

**Cause:** Invalid root element parsing capabilities document.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30197: Unexpected "\\".**

**Cause:** Error parsing agent's name and version.

**Action:** Log a bug against the Apache Trinidad framework. Try a different browser.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30198: Unexpected character. Expecting "." or "\"**

**Cause:** Error parsing agent's name and version.

**Action:** Log a bug against the Apache Trinidad framework. Try a different browser.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30199: Unexpected character. Expecting "\*"**

**Cause:** Error parsing agent's name and version.

**Action:** Log a bug against the Apache Trinidad framework. Try a different browser.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30200: Expecting char**

---

**Cause:** Error parsing agent's name and version.

**Action:** Log a bug against the Apache Trinidad framework. Try a different browser.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30201: Unterminated quote.**

**Cause:** Error parsing agent's name and version.

**Action:** Log a bug against the Apache Trinidad framework. Try a different browser.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30202: Unexpected char.**

**Cause:** Error parsing agent's name and version.

**Action:** Log a bug against the Apache Trinidad framework. Try a different browser.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30203: Invalid saved state object**

**Cause:** Saved state wasn't an instance of PageState.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30204: Don't support transient here**

**Cause:** transient isn't supported.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30205: Per-request disk space limits exceeded.**

**Cause:** per-request disk space limits exceeded.

**Action:** See the System Administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

---

**ADF\_TRINID-30206: popView(): No view has been pushed.**

**Cause:** IllegalStateException in DialogService.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30207: popView(): No view has been pushed.**

**Cause:** IllegalStateException in DialogService.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30208: You must call next() at least once**

**Cause:** This is no longer an error in the code.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30209: {0} UnsupportedOperationException**

**Cause:** This is no longer an error in the code.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30210: Only HttpServletRequest supported**

**Cause:** Attempting to get a paramter from ServletExternalContext without a HttpServletRequest.

**Action:** Log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30211: {0} can not be null.**

**Cause:** Attempting to get a paramter from ServletExternalContext without a HttpServletRequest.

**Action:** Log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

---

**ADF\_TRINID-30212: Request is null on this context.**

**Cause:** Calling ServletExternalContext's dispatch without a servletRequest.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30213: Response is null on this context.**

**Cause:** Calling ServletExternalContext's dispatch without a servletResponse.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30214: Unsupported conversion from:{0} to:{1}**

**Cause:** IllegalArgumentException while converting values in the BaseConverter.

**Action:** Check the converter code. Log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30215: Cannot convert to:{0}"**

**Cause:** This is no longer an error in the code.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30216: Null name**

**Cause:** The name attribute is null.

**Action:** Log a bug against the application. Set the name to a non-null value.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30217: Null value**

**Cause:** The value attribute is null.

**Action:** Log a bug against the application. Set the value to a non-null value.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30218: putAll operation not supported for WrappingMap**

---

**Cause:** UnsupportedOperationException, the WrappingMap which implements Map does not support the putAll operation and it was called.

**Action:** Log a bug against the Apache Trinidad framework. Fix code to not call putAll.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30219: clear operation not supported for WrappingMap**

**Cause:** UnsupportedOperationException, the WrappingMap which implements Map does not support the clear operation and it was called.

**Action:** Log a bug against the Apache Trinidad framework. Fix code to not call clear.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30220: Problem loading...**

**Cause:** While generating images, there was a problem.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30221: While grabbing pixels:**

**Cause:** While generating images, there was a problem.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30222: Error while fetching image. grabbed {0} pixel values of the {1} x {2} image.**

**Cause:** While generating images, there was a problem.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30223: Exceeded gif color limit.**

**Cause:** While generating images, there was a problem.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

---

**Impact:** Logging

**ADF\_TRINID-30224: No space left for transparency**

**Cause:** While generating images, there was a problem.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30225: Different lengths - sourceColors and targetColors**

**Cause:** While generating images, there was a problem.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30226: Cannot yet nest:{0} elements**

**Cause:** Region metadata was nested and it shouldn't be.

**Action:** Log a bug against the application. Do not nest region metadata in your page. Use JDeveloper to check the syntax of your page.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30227: Duplicate renderer type "{0}" for family "{1}"**

**Cause:** Attempting to add a duplicate renderer for a family to the render kit.

**Action:** Log a bug against the Apache Trinidad framework. Check the renderer registration in the faces-config.xml file.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30228: No returnId is available for returning from the dialog; this usually means that you aren't in a dialog in the first place.**

**Cause:** Returning from a dialog and found no returnId.

**Action:** Log a bug against the application. To return from a dialog, you need to be in a dialog, or make the pageFlowScope available

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30229: TrainRenderer can only renders instances of {0}, found {1}**

**Cause:** While rendering the train the wrong instance was found.

**Action:** Log a bug against the application. Check your jsp page.

**Level:** 2

---

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30230: SelectOne submittedValue's index {0} is out of bounds. It should be between 0 and {1}**

**Cause:** Rendering the selectOne component, the submittedValue was out of bounds from what it should be.

**Action:** Log a bug against the application. Possibly the model changed when it shouldn't have, so check the model.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30231: SelectOne could not convert submittedValue's index {0} into int {1}**

**Cause:** While rendering the selectOne component, the submittedValue couldn't be converted to an int.

**Action:** Log a bug against the application. Check the selectOne component's model.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30232: Don't call this for column headers**

**Cause:** While rendering the table, the method getHeaderFormatClass was called for a column header.

**Action:** Log a bug against the Apache Trinidad framework. Fix code to not call the method for a column header.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30233: contextURI is null**

**Cause:** Attempting to get a configuration context url where the directory is unavailable.

**Action:** Log a bug against the Apache Trinidad framework. Check the directory.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30234: context URI for {0} ends with a slash**

**Cause:** The configuration context URI ends with a slash and it shouldn't.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

---

**ADF\_TRINID-30235: contextPath is null {0}**

**Cause:** The configuration context path is null.

**Action:** Log a bug against the Apache Trinidad framework

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30236: Registered null URI**

**Cause:** Registering a configuration url and found it is null.

**Action:** Log a bug against the Apache Trinidad framework

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30237: A null path was registered for {0}**

**Cause:** Registering a configuration found a null path being registered.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30238: No base path registered**

**Cause:** Registering a configuration found no base path was registered.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30239: # of keys and values must match**

**Cause:** While processing ServletRequestParameters an error was found.

**Action:** Log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30240: {0} is not a character**

**Cause:** Trying to coerce a type to a character and found that it wasn't a character.

**Action:** Log a bug against the application. Check the valuebindings.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30241: Could not find class {0}**

**Cause:** Error finding class in Coercions.



---

**Action:** Log a bug against the application. Check the valuebindings.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30242: {0} cannot be parsed into a {1}**

**Cause:** Attempting to coerce a value.

**Action:** Log a bug against the application. Check the valuebindings.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30243: type is null**

**Cause:** Attempting to coerce a value.

**Action:** Log a bug against the application. Check the valuebindings.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30244: Could not coerce value of type {0} into type {1}**

**Cause:** Attempting to coerce a value.

**Action:** Log a bug against the application. Check the valuebindings.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30245: {0} cannot be coerced into a java.awt.Color**

**Cause:** Attempting to coerce a value.

**Action:** Log a bug against the application. Check the valuebindings.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30246: Could not find {1}**

**Cause:** Attempting to find file failed.

**Action:** Log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30247: DecimalFormatContext is not cloneable!**

**Cause:** IllegalStateException while attempting to clone the DecimalFormatContext.

**Action:** Log a bug against the Apache Trinidad framework.

---

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30248: User-defined subclasses not supported.**

**Cause:** IllegalStateException because you cannot subclass the LocaleContextImpl.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30249: Unknown reading direction: {0}**

**Cause:** Attempting to set the reading direction to an unknown value.

**Action:** Log a bug against the application. Try a different browser.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30250: Format.parseObject(String) failed**

**Cause:** Attempting to parse a ColorFormat failed.

**Action:** Ensure the ColorFormat is correct. Log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30251: Cannot format given Object as a Color**

**Cause:** Attempting to parse a ColorFormat failed.

**Action:** Ensure the ColorFormat is correct. Log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30252: Illegal pattern character "{0}"**

**Cause:** Attempting to parse a ColorFormat failed.

**Action:** Ensure the ColorFormat is correct. Log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30253: Illegal pattern character "{0}"**

**Cause:** Attempting to parse a ColorFormat failed.

**Action:** Ensure the ColorFormat is correct. Log a bug against the application.

**Level:** 2

**Type:** ERROR

---

**Impact:** Logging

**ADF\_TRINID-30254: FastMessageFormat only supports numeric arguments**

**Cause:** IllegalArgumentException, in FastMessageFormat while formatting.

**Action:** Use only numeric arguments in FastMessageFormat. Log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30255: End of pattern not found**

**Cause:** IllegalArgumentException, in FastMessageFormat while formatting.

**Action:** Fix the pattern in FastMessageFormat. Log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30256: FastMessageFormat: empty argument - {} - found**

**Cause:** IllegalArgumentException, in FastMessageFormat while formatting.

**Action:** Fix the FastMessageFormat. Log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30257: Content is not multipart form data**

**Cause:** IllegalStateException while attempting to create a MultipartFormHandler for the given InputStream and content

**Action:** Log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30258: Item is not a file**

**Cause:** IOException while attempting to create a MultipartFormHandler for the given InputStream and content

**Action:** Log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30259: Item has already been read past.**

**Cause:** IOException while attempting to create a MultipartFormHandler for the given InputStream and content

**Action:** Log a bug against the application.

**Level:** 2

---

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30260: Input stream has already been requested.**

**Cause:** IOException while attempting to create a MultipartFormHandler for the given InputStream and content

**Action:** Log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30261: Uploaded file of length {0} bytes exceeded maximum allowed length ({1} bytes)**

**Cause:** EOFException while attempting to create a MultipartFormHandler for the given InputStream and content

**Action:** Use smaller files. Log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30262: Item has already been read past.**

**Cause:** IOException while attempting to create a MultipartFormHandler for the given InputStream and content

**Action:** Log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30263: End Of File**

**Cause:** IOException while attempting to create a MultipartFormHandler for the given InputStream and content

**Action:** Log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30264: Undeclared prefix: {0}**

**Cause:** Exception while attempting to parse the namespace from a value.

**Action:** Log a bug against the application. Check the format of the namespace in the file that is being parsed. JDeveloper will flag errors.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30265: parser is null**

**Cause:** While setting up the ParserManager, a null parser was passed in.

---

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30266: Both rootClass and rootParser are null**

**Cause:** While parsing an xml document the root parser and root class were null.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30267: Circular include of {0} detected!**

**Cause:** SAXParseException while parsing an xml file because a circular include was detected.

**Action:** Log a bug against the application. Check the file that is being parsed and remove the circular include.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30268: Null id**

**Cause:** While creating a SkinExtension the skin id was null.

**Action:** Log a bug against the application. Check that the skin-extensions (defined in trinidad-skins.xml) have an id specified.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30269: Null IContext**

**Cause:** While getting a translated value from the Skin, the locale context was null.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30270: Null iconName**

**Cause:** A null icon was being registered with the Skin.

**Action:** Log a bug against the Apache Trinidad framework. Check the skin-extensions to make sure the icons are defined correctly.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30271: "Null styleSheetName"**

---

**Cause:** A null stylesheet was being registered with the Skin.

**Action:** Log a bug against the Apache Trinidad framework. Check the skin-extensions to make sure the stylesheet name is defined correctly.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30272: No Skin specified.**

**Cause:** Creating a SkinStyleProvider with no skin object.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30273: Null inputStream**

**Cause:** NullPointerException, no inputStream while parsing trinidad-skins.xml file.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30274: Null parserManager**

**Cause:** NullPointerException, no parserManager while parsing trinidad-skins.xml file.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30275: Required XSS file {0} does not exist.**

**Cause:** While registering a skin, the required XSS file does not exist.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30276: Null sourceName**

**Cause:** No source name found while parsing the skin's xss stylesheet.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

---

**ADF\_TRINID-30277: Null argument**

**Cause:** Error registering a look and feel extension, null baselookandfeel, id or family.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30278: Null propertyName**

**Cause:** While trying to parse an include from an xss file a null property name was found.

**Action:** Log a bug against the application. Check the xss file being parsed for a null property name.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30279: PropertyNode's name cannot be null or the empty string.name is "{0}" and value is "{1}"**

**Cause:** While trying to parse an include from an xss file a null property name was found.

**Action:** Log a bug against the application. Check the xss file being parsed for a null property name.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30280: child not instance of PropertyNode**

**Cause:** While trying to parse an include from an xss file an invalid child node was found.

**Action:** Log a bug against the application. Check the xss file being parsed.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30281: child not an instance of IncludePropertyNode**

**Cause:** While trying to parse an include from an xss file an invalid child node was found.

**Action:** Log a bug against the application. Check the xss file being parsed.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30282: Not nested in a UIComponentTag**

**Cause:** JSPException while processing an attribute tag.

**Action:** Log a bug against the application. Check the jsp page and fix error.

---

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30283: No component associated with UIComponentTag**

**Cause:** JSPException while processing an attribute tag.

**Action:** Log a bug against the application. Check the jsp page and fix error.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30284: Name attribute cannot be EL bound**

**Cause:** JSPException while processing an attribute tag.

**Action:** Log a bug against the application. Check the jsp page and fix error.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30285: "componentDef cannot be run as a stand-alone. It must be included inside a JSF component tree.**

**Cause:** JSPException while processing an componentDef tag.

**Action:** Log a bug against the application. Check the jsp page and fix error.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30286: componentDef must be included as a child of an <tr:componentRef>.**

**Cause:** JSPException while processing an componentDef tag.

**Action:** Log a bug against the application. Check the jsp page and fix error.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30287: tr:componentDef does not support EL on "var"**

**Cause:** JSPException while processing an componentDef tag.

**Action:** Log a bug against the application. Check the jsp page and fix error.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30288: "items" must be a simple JSF EL expression**

**Cause:** IllegalArgumentException while processing a forEach/items tags.

**Action:** Log a bug against the application. Check the jsp page and fix error with 'items'.



---

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30289: "var" cannot be an expression**

**Cause:** IllegalArgumentException while processing a forEach tag.

**Action:** Log a bug against the application. Check the jsp page and fix error with 'var'.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30290: "varStatus" cannot be an expression**

**Cause:** IllegalArgumentException while processing a forEach tag.

**Action:** Log a bug against the application. Check the jsp page and fix error with 'varStatus'.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30291: "items" must point to a List or array**

**Cause:** IllegalArgumentException while processing a forEach/items tags.

**Action:** Log a bug against the application. Check the jsp page and fix error with 'items'.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30292: "begin" and "end" should be specified if "items" is not specified**

**Cause:** IllegalArgumentException while processing a forEach tag.

**Action:** Log a bug against the application. Check the jsp page and fix error.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30293: "var" and "varStatus" must not have same value**

**Cause:** IllegalArgumentException while processing a forEach tag.

**Action:** Log a bug against the application. Check the jsp page and fix error.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30294: "begin" < 0**

**Cause:** IllegalArgumentException while processing a forEach tag.

---

**Action:** Log a bug against the application. Check the jsp page and fix error.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30295: "step" < 1**

**Cause:** IllegalArgumentException while processing a forEach tag.

**Action:** Log a bug against the application. Check the jsp page and fix error.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30296: ResetActionListener must be inside of a UIComponent tag.**

**Cause:** JSPException while processing an resetActionListener tag.

**Action:** Log a bug against the application. Check the jsp page and fix error.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30297: returnActionListener must be inside of a UIComponent tag.**

**Cause:** JSPException while processing an returnActionListener tag.

**Action:** Log a bug against the application. Check the jsp page and fix error.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30298: setActionListener must be inside of a UIComponent tag.**

**Cause:** JSPException while processing an setActionListener tag.

**Action:** Log a bug against the application. Check the jsp page and fix error.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30299: setActionListener's "to" attribute must be an EL expression.**

**Cause:** JSPException while processing an setActionListener tag.

**Action:** Log a bug against the application. Check the jsp page and fix error.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30300: Color code {0} in "{1}" does not start with a "#"**

**Cause:** ParseException processing the chooseColor's colordata.

**Action:** Log a bug against the application. Start the color code with a '#'.

---

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30301: This method changed to getRenderer(RenderingContext, UINode)**

**Cause:** IllegalStateException, calling an unsupported method.

**Action:** Log a bug against the Apache Trinidad framework. Call the correct method

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30302: Replaced in 2.0 by getIndexedNodeList()**

**Cause:** IllegalStateException, calling an unsupported method.

**Action:** Log a bug against the Apache Trinidad framework. Call the correct method

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30303: Instantiation of UIX Components Renderer failed, class {0} not found.**

**Cause:** Attempting to register a uix component rendered failed.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30304: Reusing role index**

**Cause:** IllegalArgumentException creating NodeRoles.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30305: Attempt to register a null renderer for {0}**

**Cause:** Attempting to register a null renderer.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30306: Only ContextBasedConfiguration is supported**

**Cause:** Attempting to set an invalid configuration type on the RenderingContext.

---

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30307: The facet may not be set after the RendererManager has been assigned.**

**Cause:** IllegalStateException trying to set the facet after the RendererManager has been assigned.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30308: It is illegal to set children on a {0}**

**Cause:** UnsupportedOperationException trying to replace a child.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30309: It is illegal to add children to a {0}**

**Cause:** UnsupportedOperationException trying to add a child.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30310: It is illegal to remove children from a {0}**

**Cause:** UnsupportedOperationException trying to remove a child.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30311: It is illegal to set children on an UnmodifiableCompoundNodeList**

**Cause:** UnsupportedOperationException trying to modify a child.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30312: It is illegal to add children to an UnmodifiableCompoundNodeList**

---

**Cause:** UnsupportedOperationException trying to add a child.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30313: It is illegal to remove children from an UnmodifiableCompoundNodeList**

**Cause:** UnsupportedOperationException trying to remove a child.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30314: Adapter class doesn't implement BeanDOAdapter**

**Cause:** IllegalArgumentException registered ia BeanAdapter class.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30315: {0} is not an instance of {1}**

**Cause:** IllegalArgumentException trying to attach an instance of the bean class to the adapter.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30316: leftSideValue is null**

**Cause:** Attempting to create a ComparisonBoundValue caused IllegalArgumentException.

**Action:** Log a bug against the appication.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30317: rightSideValue is null**

**Cause:** Attempting to create a ComparisonBoundValue caused IllegalArgumentException.

**Action:** Log a bug against the appication.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

---

**ADF\_TRINID-30318: Unknown comparison**

**Cause:** Attempting to create a ComparisonBoundValue caused IllegalArgumentException.

**Action:** Log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30319: test BoundValue required**

**Cause:** Attempting to create a IfBoundValue with IllegalArgumentException.

**Action:** Log a bug against the application.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30320: Null list argument**

**Cause:** NullPointerException in deprecated code.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30321: Null data object argument**

**Cause:** NullPointerException in deprecated code.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30322: No factory registered for {0}**

**Cause:** No renderer factory found in LookAndFeelExtension.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30323: Null baseScorer**

**Cause:** NullPointerException in skinning's NameOnly scorer.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30324: Null baseScore**

---

**Cause:** NullPointerException in skinning's NameOnly scorer.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30325: Facet {0} is not supported on {1}**

**Cause:** IllegalArgumentException returning Skins RendererFactory.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30326: # of keys and values much match**

**Cause:** Error encoding the Javascript event object because the number of keys and values did not match.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30327: child is not null and not an instance of IconNode**

**Cause:** This error is no longer in the code.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30328: "Null renderers or no renderers passed"**

**Cause:** This error is no longer in the code.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30329: Null child or child not an instance of RendererNode**

**Cause:** This error is no longer in the code.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30330: Null family**

**Cause:** While parsing skin nodes a null skin-family was found.

---

**Action:** Log a bug against the application. Check all trinidad-skins.xml on classpath and WEB-INF and make sure that the skin-family is set for each skin

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30331: Non Null child and child not an instance of SkinPropertyNode**

**Cause:** This error is no longer in the code.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30332: RenderingContext has already been created!**

**Cause:** Attempting to create a RenderingContext when it already exists.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30333: {0} not superclass of {1}**

**Cause:** IntrospectionException

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30334: Unexpected reflection exception: {0}**

**Cause:** This error is no longer in the code.

**Action:** Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30335: Javascript does not support null keys**

**Cause:** IllegalArgumentException while encoding a Map in JavaScript Object Notation.

**Action:** Do not use null keys. Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging

**ADF\_TRINID-30336: Encoding: {0} is unsupported by JVM**



---

**Cause:** IllegalCharsetNamesException while enabling byte length validation at the client side.

**Action:** Use a supported JVM. Log a bug against the Apache Trinidad framework.

**Level:** 2

**Type:** ERROR

**Impact:** Logging



---

## ADFC-00001 to ADFC-14008

**ADFC-00001: An exception is encountered.**

**Cause:** An unknown problem caused an exception.

**Action:** Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-00002: The ADF Controller cannot run without {0}. Ensure that "{1}" is present in the classpath.**

**Cause:** The ADF Controller was unable to locate the required class on the classpath.

**Action:** Modify the classpath to include the required class.

**Level:** 2

**Type:** ERROR

**Impact:** Installation

**ADFC-00003: AdfFacesContext is not found. The ADF Controller cannot run.**

**Cause:** The ADF Controller was unable to locate the required class on the classpath.

**Action:** Modify the classpath to include the required class.

**Level:** 2

**Type:** ERROR

**Impact:** Installation

**ADFC-00004: RequestContext is not found. The ADF Controller cannot run.**

**Cause:** The ADF Controller was unable to locate the required class on the classpath.

**Action:** Modify the classpath to include the required class.

**Level:** 2

**Type:** ERROR

**Impact:** Installation

**ADFC-00005: The ADF Controller cannot execute task flow template "{0}".**

---

**Cause:** An attempt was made to execute a task flow template. Task flow templates cannot be executed.

**Action:** Correct the associated task flow call activity to refer to a task flow definition.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-00006: Existing transaction is required when calling task flow "{0}".**

**Cause:** The ADF Controller attempted to enter a task flow that requires an existing transaction, but no transaction was open.

**Action:** Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-00007: Transaction type is unknown.**

**Cause:** The ADF Controller encountered an unknown transaction type.

**Action:** Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-00008: The ADF Controller is unable to find DataControlFrame for a task flow.**

**Cause:** The ADF Controller was unable to find the model layer DataControlFrame for a task flow.

**Action:** Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-00010: A DataControlFrame savepoint handle does not exist.**

**Cause:** Restore of a DataControlFrame savepoint was attempted when a savepoint handle did not exist. Savepoint handle can become null after an ADFc save for later savepoint was restored.

**Action:** Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-00011: The ADF Controller is unable to create an MDSSession. See exception for details.**

**Cause:** The ADF Controller requires an MDSSession to locate metadata. An attempt to create an MDSSession failed. This could be caused by a number of problems.

---

**Action:** See the accompanying exception.

**Level:** 2

**Type:** ERROR

**Impact:** Configuration

**ADFC-00012: The ADF Controller is unable to parse configuration file adf-config.xml.**

**Cause:** An unspecified error occurred while parsing configuration file adf-config.xml.

**Action:** See the accompanying exception.

**Level:** 2

**Type:** ERROR

**Impact:** Configuration

**ADFC-00013: Configuration file adf-config.xml has too many "{0}" elements.**

**Cause:** Configuration file adf-config.xml contained more instances of the specified element than are allowed.

**Action:** Correct the contents of the file.

**Level:** 2

**Type:** ERROR

**Impact:** Configuration

**ADFC-00014: Configuration file adf-config.xml contains duplicate phase-listener "{0}" registrations.**

**Cause:** One or more phase-listeners had the same listener-id value.

**Action:** Correct the contents of the file.

**Level:** 2

**Type:** ERROR

**Impact:** Configuration

**ADFC-00015: Configuration file adf-config.xml contains duplicate phase-listener "{0}" in either 'before-id-set' or 'after-id-set'.**

**Cause:** A phase-listener was specified twice in the same set.

**Action:** Correct the contents of the file.

**Level:** 2

**Type:** ERROR

**Impact:** Configuration

**ADFC-00016: Configuration file adf-config.xml contains an invalid value: [element, value] = [{"0}", "{1}"].**

**Cause:** Configuration file adf-config.xml contained invalid XML.

**Action:** Correct the contents of the file.

**Level:** 2

**Type:** ERROR

---

**Impact:** Configuration

**ADFC-00017: Configuration file adf-config.xml does not contain mandatory element "{0}".**

**Cause:** Configuration file adf-config.xml contained invalid XML.

**Action:** Correct the contents of the file.

**Level:** 2

**Type:** ERROR

**Impact:** Configuration

**ADFC-00018: EL expression for UrlParameterConverter is null.**

**Cause:** An attempt was made to convert a URL parameter, but the converter EL expression was null.

**Action:** Correct the metadata for the converter.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-00019: An incorrect object is specified by EL expression "{0}" for a URL parameter converter.**

**Cause:** An object was specified by the EL expression that did not implement the oracle.adf.controller.UrlParameterConverter interface.

**Action:** Specify an object that implements the oracle.adf.controller.UrlParameterConverter interface.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-00020: Task flow "{0}" requires a new transaction, but a transaction is already open on the frame.**

**Cause:** A new transaction could not be started on the frame because a transaction was already open.

**Action:** Correct the application's flow or the task flow's metadata.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-00021: Task flow "{0}" requires a shared DataControlFrame but parent frame is null.**

**Cause:** The task flow is configured to share its DataControl scope with its parent. The parent DataControlFrame is null.

**Action:** Correct the application's flow or the task flow's metadata.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-00022: Unable to create logger "{0}".**

---

**Cause:** An attempt was made to create a logger with a null name.

**Action:** Contact your Oracle Support Services.

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ADFC-00617: Absolute action URLs are not supported in a portal environment.**

**Cause:** An attempt was made to construct an absolute action URL while running in a portal environment.

**Action:** Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-00618: View ID "{0}" is invalid.**

**Cause:** The value provided was not a valid view ID in the context in which it was being used.

**Action:** Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-00619: Authorization check failed: "{0}" "{1}".**

**Cause:** An attempt was made to access a task flow without appropriate privilege.

**Action:** Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Security

**ADFC-00620: Parameter value is invalid.**

**Cause:** The value provided for one of the parameters failed validation.

**Action:** Check the parameter value.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-02000: The ADF Controller is not able to initialize the metadata service.**

**Cause:** The ADF Controller was unable to initialize the metadata service.

**Action:** Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Configuration

**ADFC-02001: The ADF Controller cannot find "{0}".**

---

**Cause:** An attempt was made to load metadata that cannot be found.

**Action:** Verify that all required files are available.

**Level:** 2

**Type:** ERROR

**Impact:** Files

**ADFC-02002: The ADF Controller cannot parse the task flow metadata.**

**Cause:** The metadata did not represent a valid task flow.

**Action:** See the associated exceptions. Validate the metadata.

**Level:** 2

**Type:** ERROR

**Impact:** Compliance

**ADFC-02003: Default activity must be specified in task flow definition "{0}".**

**Cause:** The ADF Controller was unable to find task flow default activity in the task flow definition.

**Action:** Add a default activity to the task flow definition.

**Level:** 2

**Type:** ERROR

**Impact:** Compliance

**ADFC-02004: Default activity ID "{0}" is invalid.**

**Cause:** The ADF Controller was unable to construct the default activity ID.

**Action:** Correct the default activity ID.

**Level:** 2

**Type:** ERROR

**Impact:** Compliance

**ADFC-02005: Task flow definition is not found: "{0}".**

**Cause:** An attempt was made to read the specified task flow. The task flow cannot be found.

**Action:** Verify that the required file is available.

**Level:** 2

**Type:** ERROR

**Impact:** Compliance

**ADFC-02006: A task flow ID is not found in the URL.**

**Cause:** The specified task flow ID was requested and could not be found.

**Action:** Verify that the task flow reference is correct. Verify that all required files can be found.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic



---

**ADFC-02007: A task flow document is not found in the URL.**

**Cause:** An attempt was made to access a task flow using URL parameters. The specified document could not be found.

**Action:** Correct the value for the document parameter.

**Level:** 2

**Type:** ERROR

**Impact:** Browser

**ADFC-02008: The value for 'documentName' cannot be null or empty.**

**Cause:** An attempt was made to reference a task flow using a null value for 'documentName'.

**Action:** Correct the value.

**Level:** 2

**Type:** ERROR

**Impact:** Compliance

**ADFC-02009: The value for 'localTaskFlowId' cannot be null or empty.**

**Cause:** An attempt was made to reference a task flow using a null value for 'localTaskFlowId'.

**Action:** Correct the value.

**Level:** 2

**Type:** ERROR

**Impact:** Compliance

**ADFC-02010: The value for 'localTaskFlowId' cannot be '#'.**

**Cause:** An attempt was made to reference a task flow using an invalid value for 'localTaskFlowId'.

**Action:** Correct the value.

**Level:** 2

**Type:** ERROR

**Impact:** Compliance

**ADFC-02011: The value for 'localActivityId' cannot be null or empty.**

**Cause:** An attempt was made to construct an oracle.adf.controller.internal.metadata.ActivityId using an invalid value for 'localActivityId'.

**Action:** Correct the value.

**Level:** 2

**Type:** ERROR

**Impact:** Compliance

**ADFC-02012: The activity ID string cannot be null or empty.**

**Cause:** An attempt was made construct an oracle.adf.controller.internal.metadata.ActivityId using an invalid value.

**Action:** Correct the value.

---

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-02013: The ADF Controller cannot find metadata for activity "{0}".**

**Cause:** An attempt was made to access an activity that has no metadata defined.

**Action:** Validate the task flow document.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-02014: No activity implementation is available for activity type "{0}".**

**Cause:** An attempt was made to access an activity that is not a known activity type.

**Action:** Validate the task flow document.

**Level:** 2

**Type:** ERROR

**Impact:** Compliance

**ADFC-02015: Task flow ID "{0}" in document "{1}" is invalid.**

**Cause:** The ADF Controller was unable to construct the task flow ID.

**Action:** Correct the task flow ID.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-02016: A possible cyclic reference to template "{0}" is detected when parsing "{1}".**

**Cause:** The task flow metadata references a template that is already referenced by this task flow.

**Action:** Verify that the task flow templates do not reference each other in a cyclic manner.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-02017: The value for 'url' cannot be null or empty.**

**Cause:** An attempt was made to reference a URL view activity using a null value for 'url'.

**Action:** Correct the value.

**Level:** 2

**Type:** ERROR

**Impact:** Browser

**ADFC-02018: Root tag "{0}" in "{1}" does not match <adfc-config>.**

---

**Cause:** A document with an invalid root tag was referenced.

**Action:** Correct the root tag.

**Level:** 2

**Type:** ERROR

**Impact:** Compliance

**ADFC-02019: No activities are specified in task flow definition "{0}".**

**Cause:** The task flow definition did not contain any activities.

**Action:** Add activities to the task flow definition.

**Level:** 2

**Type:** ERROR

**Impact:** Compliance

**ADFC-02020: Cannot find default activity "{0}" in task flow definition "{1}".**

**Cause:** The ADF Controller was unable to find a default activity in the task flow definition.

**Action:** Add a default activity.

**Level:** 2

**Type:** ERROR

**Impact:** Compliance

**ADFC-02021: Customization of the documents that appear multiple times on the classpath is not supported. Document name: "{0}".**

**Cause:** A document appears multiple times on the classpath.

**Action:** Remove multiple documents.

**Level:** 2

**Type:** ERROR

**Impact:** Compliance

**ADFC-02022: Either 'parent-outcome' or 'root-outcome' has to be specified.**

**Cause:** An attempt was made to parse a parent action activity with neither 'parent-outcome' and nor 'root-outcome' specified.

**Action:** Correct the value.

**Level:** 2

**Type:** ERROR

**Impact:** Browser

**ADFC-04000: The value of PagePhaseListener cannot be null.**

**Cause:** An attempt was made to use a PagePhaseListener with a null value.

**Action:** Correct the value.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

---

**ADFC-04001: The value of a listener ID string cannot be null or empty.**

**Cause:** An attempt was made to identify a PagePhaseListener using a null listener ID.

**Action:** Use a nonempty string for the listener ID.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-04002: A PagePhaseListener with the listener ID of "{0}" already exists.**

**Cause:** Each PagePhaseListener should be registered with a unique listener ID.

**Action:** Use a listener ID that does not already exist.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-04003: The PagePhaseListener of type "{0}" with listener ID of "{1}" cannot be registered because it is part of the internal API.**

**Cause:** The ADF Controller was unable to register an internal PagePhaseListener using the public API.

**Action:** Use a PagePhaseListener that is not internal.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-04004: The value 'any\_public\_listener' is not allowed.**

**Cause:** The value 'any\_public\_listener' was part of the afterSet or beforeSet parameter.

**Action:** Do not use 'any\_public\_listener' as the listener ID for beforeSet or afterSet.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-04005: The PagePhaseListener with ID "{0}" is internal and cannot be removed.**

**Cause:** A failed attempt was made to remove an internal PagePhaseListener. This operation is not supported.

**Action:** Ensure that a PagePhaseListener is public, not internal, before attempting to remove it.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-04006: The value of LifecycleContext cannot be null.**

**Cause:** An attempt was made to create a PagePhaseEvent with a null LifecycleContext.

**Action:** Correct the value.

---

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-04007: The FacesPageLifecycleContext does not exist yet.**

**Cause:** An attempt was made to retrieve the FacesPageLifecycleContext before it was created.

**Action:** Wait until the RestoreView phase of the JavaServer Faces lifecycle to retrieve the FacesPageLifecycleContext.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-06000: The ADF Controller caught exception '{0}' while performing control flow routing. See the stack trace for details.**

**Cause:** An unhandled exception occurred while the ADF Controller was executing the application's control flow.

**Action:** See the associated exception. Verify that the navigation rules are correctly specified. Verify that the correct outcome was generated to trigger routing.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-06001: TaskFlowId "{0}" is invalid.**

**Cause:** An attempt was made to construct a TaskFlowId using an invalid string.

**Action:** Correct the value.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-06002: unhandled exception**

**Cause:** The ADF Controller encountered an exception. Either no exception handler activity was defined or the ADF Controller and task flow were not configured to catch this exception.

**Action:** See the associated exception. Verify that the exception handler activity is correctly defined. Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-06003: TaskFlowId for a child view port must be specified.**

**Cause:** An attempt was made to create a child view port using a null value for TaskFlowId.

**Action:** Correct the value.

**Level:** 2

**Type:** ERROR

---

**Impact:** Programmatic

**ADFC-06004: Invalid transport "{0}" used. Task flows require "{1}".**

**Cause:** An attempt was made to access a task flow without using the required transport.

**Action:** Use the appropriate transport. Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Security

**ADFC-06005: The ADF Controller is unable to invoke URL parameter validator.**

**Cause:** A view activity defines one or more parameter validators. Invoking the parameter validator failed.

**Action:** See the associated exception. Verify that the metadata refers to the correct class and method.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-06006: The ADF Controller is unable to invoke application method.**

**Cause:** A view activity defines a bookmark method. Invoking the specified method failed.

**Action:** See the associated exception. Verify that the metadata refers to the correct class and method.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-06007: The ADF Controller is unable to copy task flow input parameters. Objects must be serializable.**

**Cause:** The task flow call activity specifies one or more input parameters. The ADF Controller was unable to copy the specified values.

**Action:** See the associated exception. Verify that the metadata refers to the correct class and method. Verify that the specified objects are serializable.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-06008: Router case expression "{0}" does not evaluate to a boolean.**

**Cause:** A router activity case contained an EL expression that did not evaluate to a boolean.

**Action:** Correct the expression.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-06009: The ADF Controller is unable to encode a URL.**

---

**Cause:** The ADF Controller was unable to encode a URL.

**Action:** See the associated exception. Correct the metadata.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-06010: The ADF Controller is unable to encode remote task flow URL: "{0}".**

**Cause:** The ADF Controller was unable to invoke a task flow using a URL.

**Action:** See the associated exception. Correct the metadata.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-06011: The ADF Controller is unable to encode remote process return URL: "{0}".**

**Cause:** The task flow metadata specified an invalid return URL.

**Action:** See the associated exception. Correct the metadata.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-06012: Return task flow ID "{0}" is invalid.**

**Cause:** The task flow ID being returned from did not match the ID of the task flow that was called.

**Action:** Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-06013: The ADF Controller is unable to encode bookmark parameter "{0}".**

**Cause:** The ADF Controller was unable to encode a bookmark parameter.

**Action:** See the associated exception.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-06014: An exception occurred when invoking a task flow finalizer.**

**Cause:** Execution of the task flow finalizer raised an exception.

**Action:** See the associated exception. Verify that the metadata references the correct class and method.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

---

**ADFC-06015: An exception occurred when invoking a task flow initializer.**

**Cause:** Execution of the task flow initializer raised an exception.

**Action:** See the associated exception. Verify that the metadata references the correct class and method.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-06016: Task flow reentry is not allowed: "{0}".**

**Cause:** A failed attempt was made to reenter a task flow where reentry is prohibited.

**Action:** Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-08000: The ADF Controller is unable to obtain the view state for the savepoint operation.**

**Cause:** An attempt to save or restore the UIViewRoot failed.

**Action:** Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-08001: The ADF Controller is unable to commit the savepoint database transaction.**

**Cause:** The ADF Controller was unable to commit a savepoint to the database.

**Action:** See the associated exception. Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-08002: The ADF Controller is unable to log in to the database or obtain a database connection.**

**Cause:** The ADF Controller was unable to log in to the database.

**Action:** See the associated exception. Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-08003: The ADF Controller is unable to delete all savepoint records for user "{0}" from the database.**

**Cause:** The ADF Controller was unable to delete all specified savepoints.

**Action:** See the associated exception. Contact the system administrator.

**Level:** 2



---

**Type:** ERROR

**Impact:** Programmatic

**ADFC-08004: The ADF Controller is unable to delete savepoint record "{0}" from the database.**

**Cause:** The ADF Controller was made to delete the specified savepoint.

**Action:** See the associated exception. Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-08005: Exception occurred when evaluating an expression used for savepoint ID.**

**Cause:** The task flow contains at least one save point restore activity. An attempt to evaluate the value for savepoint ID failed.

**Action:** See the associated exception. Check the task flow metadata.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-08006: The ADF Controller was unable to get the savepoint with ID = "{0}".**

**Cause:** The ADF Controller was unable to retrieve the specified savepoint.

**Action:** Verify that the correct ID was specified. Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-08007: The savepoint ID is empty.**

**Cause:** An attempt was made to create or get a savepoint with a null ID.

**Action:** Specify a valid savepoint ID.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-08008: The ADF Controller is unable to insert a savepoint record for ID "{0}".**

**Cause:** The ADF Controller was unable to insert a savepoint into the database.

**Action:** See the associated exception. Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-08009: The ADF Controller was unable to registering JDBC driver "{0}".**

**Cause:** The ADF Controller was unable to establish a JDBC connection.

**Action:** See the associated exception. Contact the system administrator.

**Level:** 2

---

**Type:** ERROR

**Impact:** Programmatic

**ADFC-08010: The ADF Controller was unable to find the JOC-based state manager implementation.**

**Cause:** The ADF Controller was unable to use the Java Object Cache to store savepoints.

**Action:** Make sure that the JOC is available. Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-08011: The JNDI connection name is not specified in configuration file adf-config.xml.**

**Cause:** An attempt was made to establish a JDBC connection.

**Action:** See the associated exception. Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-08012: The specified data source JNDI name, "{0}", could not be found.**

**Cause:** An attempt was made to establish a database connection.

**Action:** Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-08013: The ADF Controller is unable to query the database for the current user's savepoint IDs.**

**Cause:** The ADF Controller was unable to query the database for the set of savepoints.

**Action:** See the associated exception. Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-08014: The ADF Controller is unable to execute the save point restore activity.**

**Cause:** The task flow contains a savepoint restore activity. An attempt to execute that activity failed.

**Action:** See the associated exception. Verify that the metadata is correct. Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-08015: Cannot restore the savepoint. The savepoint ID is null.**

---

**Cause:** An attempt was made to restore a null savepoint.

**Action:** Verify that the task flow metadata is correct. Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-08016: The ADF Controller is unable to retrieve savepoint "{0}" from the database.**

**Cause:** The ADF Controller was unable to retrieve the specified savepoint from the database.

**Action:** Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-08017: The ADF Controller is unable to save the savepoint.**

**Cause:** The ADF Controller was unable to save the savepoint to the persistence manager.

**Action:** See the associated exception. Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-08018: The ADF Controller is unable to create or execute a SQL statement: "{0}".**

**Cause:** The ADF Controller generated SQL that is was unable to create or execute.

**Action:** See the associated exception. Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-08019: The ADF Controller is unable to find the transaction manager.**

**Cause:** The ADF Controller attempted to suspend or resume a transaction.

**Action:** See the associated exception. Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-08020: The ADF Controller is unable to resume a transaction.**

**Cause:** The ADF Controller was unable to resume the transaction.

**Action:** See the associated exception. Contact the system administrator.

**Level:** 2

**Type:** ERROR

---

**Impact:** Programmatic

**ADFC-08021: The ADF Controller is unable to suspend a transaction.**

**Cause:** The ADF Controller was unable to suspend the transaction.

**Action:** See the associated exception. Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-08022: The ADF Controller is unable to update the savepoint record for ID "{0}".**

**Cause:** The ADF Controller was unable to update a savepoint.

**Action:** Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-08023: The ADF Controller is encountering an error while invoking a savepoint restore finalizer.**

**Cause:** The task flow specifies a savepoint restore finalizer. Execution of the finalizer raised an exception.

**Action:** See the associated exception. Verify that the metadata references the correct class and method.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-08024: The savepoint ID "{0}" is not valid.**

**Cause:** An attempt was made to create or use a savepoint with an invalid ID.

**Action:** Specify a valid savepoint ID conforming to the UUID format.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-08025: The ADF Controller is unable to serialize the savepoint.**

**Cause:** The ADF Controller was unable to serialize the savepoint.

**Action:** See the associated exception. Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-08026: The ADF Controller is unable to deserialize the savepoint.**

**Cause:** The ADF Controller was unable to deserialize the savepoint.

**Action:** See the associated exception. Contact the system administrator.

**Level:** 2

---

**Type:** ERROR

**Impact:** Programmatic

**ADFC-08027: The ADF Controller is unable to close the database connection.**

**Cause:** The ADF Controller was unable to close the database connection.

**Action:** Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-08028: The ADF Controller is unable to restore the savepoint with ID = "{0}".**

**Cause:** The ADF Controller is unable to restore a non existing savepoint.

**Action:** Verify that the savepoint ID is correct. Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-08029: The ADF Controller is unable to find in memory savepoint created before dialog window was shown.**

**Cause:** An attempt to create save point failed.

**Action:** Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-10000: cannot find class "{0}" for a method parameter**

**Cause:** A method call activity attempted to call the specified class and could not find it.

**Action:** Correct the classpath. Verify that the metadata refers to the correct class.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-10001: cannot instantiate class "{0}"**

**Cause:** The task flow specifies a managed bean. Instantiation of this managed bean failed.

**Action:** Verify that the metadata for the managed bean is correct. Verify that the class has a default constructor.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-10002: cannot get a value from value binding expression "{0}"**

**Cause:** Task flow metadata references a managed bean. Bean instantiation failed.

**Action:** See the associated exception. Contact the system administrator.

---

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-10003: cannot set a null value into array of "{0}"**

**Cause:** The task flow specifies a managed bean of type 'LIST'. An attempt was made to set a null value.

**Action:** Change the bean type or modify the code that is attempting to set the bean value.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-10004: cannot set managed bean property "{0}"**

**Cause:** An attempt was made to set the property in a managed bean.

**Action:** See the associated exception. Validate the task flow metadata.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-10005: cannot find MethodExpression for "{0}"**

**Cause:** Task flow metadata references a method binding. Invoking the specified method failed.

**Action:** See the associated exception. Verify that the metadata is correct. Correct the specified method.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-10006: An exception occurred when evaluating an expression "{0}" specified for "{1}".**

**Cause:** Task flow metadata refers to an EL expression. Evaluation of this expression failed.

**Action:** See the associated exception. Correct the expression.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-10007: A possible cyclic reference to managed bean "{0}" is detected.**

**Cause:** The task flow metadata referenced a managed bean that was already referenced by this task flow.

**Action:** Verify that the managed bean is not already specified in a referenced template.

**Level:** 2

**Type:** ERROR

---

**Impact:** Programmatic

**ADFC-10008: Outcome to-string metadata cannot be specified for a method call activity that points to a void Java method. Activity ID: "{0}".**

**Cause:** The method call activity outcome metadata specified to-string.

**Action:** Change the method outcome metadata to use fixed-outcome, or change the Java to return a java.lang.String value.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-10009: An exception occurred during invocation of "{0}" method.**

**Cause:** Annotated managed bean method cannot be invoked.

**Action:** Check method implementation.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-12000: State ID in request is invalid for the current session.**

**Cause:** The request contained a state instance ID, but it did not exist in the session, nor was this a request for a bookmarked resource. This might be due to a session timeout.

**Action:** Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Session

**ADFC-12001: The ADF Controller is attempting to pop last entry from page flow scope stack.**

**Cause:** The ADF Controller attempted to pop the top task flow off the task flow stack.

**Action:** Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Session

**ADFC-12002: The ADF Controller is unable to pop the top-level ADF unbounded task flow from the page flow stack.**

**Cause:** The ADF Controller attempted to pop the unbounded task flow off the page flow stack.

**Action:** Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Session

**ADFC-12003: The page flow scope stack is empty.**

---

**Cause:** The ADF Controller attempted to get the current task flow

**Action:** Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Session

**ADFC-12004: Page flow stack ID "{0}" is invalid.**

**Cause:** The ADF Controller attempted to calculate the delta between two page flow stacks. The specified stack ID is invalid.

**Action:** Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Session

**ADFC-12005: The ADF Controller cannot find a common page flow stack element.**

**Cause:** The ADF Controller attempted to calculate the delta between two page flow stacks. The two stacks have no elements in common.

**Action:** Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Session

**ADFC-12006: The scope of the referenced object "{0}" is shorter than the referring object "{1}".**

**Cause:** An attempt was made to access a managed bean outside its scope.

**Action:** See the associated exception. Verify that the managed bean is correctly defined and that the reference is valid.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-12007: Page flow scope instance ID "{0}" is invalid.**

**Cause:** The ADF Controller attempted to get the unbounded task flow for this instance ID.

**Action:** Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-12008: The ADF Controller request state is missing or invalid.**

**Cause:** A missing or invalid ADF Controller request state was detected.

**Action:** Contact the system administrator.

**Level:** 2

**Type:** ERROR



---

**Impact:** Session

**ADFC-12009: An application is accessing the page flow scope prematurely.**

**Cause:** An application attempted to access the page flow scope early in the request lifecycle, before the page flow scope was available.

**Action:** Modify the application to access the page flow scope later in the request lifecycle.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-12010: A null window ID is detected.**

**Cause:** A null window ID value was detected.

**Action:** Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-12011: Window ID "{0}" is invalid.**

**Cause:** A window ID was submitted that was not a valid window ID generated during the current HTTP session.

**Action:** Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-12012: The request has an invalid state ID, and the session timed out.**

**Cause:** The request contained a state instance ID, but the session was created during the current request.

**Action:** Return to the start page of the application.

**Level:** 2

**Type:** ERROR

**Impact:** Session

**ADFC-14000: View port ID "{0}" is invalid.**

**Cause:** A reference was made to an invalid view port ID.

**Action:** Correct the value.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-14001: The ADF Controller cannot create a child view port.**

**Cause:** No root view port was created.

**Action:** Contact the system administrator.

**Level:** 2

---

**Type:** ERROR

**Impact:** Programmatic

**ADFC-14002: The ADF Controller is unable to set a view port hierarchy that has no root view port.**

**Cause:** The ADF Controller was unable to set the hierarchy of view ports with no root view port.

**Action:** Contact the system administrator.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-14003: Region does not have or cannot reach a view activity.**

**Cause:** The region specified a task flow where no view activities could be reached.

**Action:** Verify that the correct task flow is specified. Verify that the task flow has at least one navigable view.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-14004: The ADF Controller cannot execute task flow "{0}" that uses page fragments in the root view port.**

**Cause:** The task flow definition declares this task flow as using page fragments. The root viewport can only run task flows that use pages, not page fragments.

**Action:** Remove the use-page-fragments flag from the task flow definition "{0}".

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFC-14008: Task flow call activity cannot invoke remote task flow inside a region.**

**Cause:** An attempt was made to invoke a remote task flow from inside a region.

**Action:** Fix the application.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

---

## ADFDI-00100 to ADFDI-55516

**ADFDI-00100: Unable to send a request for BindingContext: a DIRemoteServlet call is already in progress.**

**Cause:** A request to DIRemoteServlet was attempted while another one is already in progress.

**Action:** This is an unexpected error condition. The system administrator can check the server logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-00101: unexpected value found in attribute metadata: {0}**

**Cause:** The XML response returned from the DIRemoteServlet is invalid.

**Action:** This is an unexpected error condition. The system administrator can check the server logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-00103: Unable to locate start element: BindingContainer in response stream.**

**Cause:** The XML response returned from the DIRemoteServlet is invalid.

**Action:** This is an unexpected error condition. The system administrator can check the server logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-00105: invalid child element <{0}> encountered within <{1}> element**

**Cause:** The XML response returned from the DIRemoteServlet is invalid.

**Action:** This is an unexpected error condition. The system administrator can check the server logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Session

---

**ADFDI-00106: missing end element: </{0}>**

**Cause:** The XML response returned from the DIRemoteServlet is invalid.

**Action:** This is an unexpected error condition. The system administrator can check the server logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-00107: row limit exceeded**

**Cause:** Too many rows exist in result set.

**Action:** Refine your query in order to reduce the number of matching rows.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-00108: user session required**

**Cause:** A valid user session is required to communicate with server.

**Action:** Log in to server and retry request.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-00109: invalid GetResourceBundle response**

**Cause:** The XML response returned from the DIRemoteServlet is invalid.

**Action:** This is an unexpected error condition. The system administrator can check the server logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-00110: unable to locate element {0} or parse its contents**

**Cause:** The XML response returned from the DIRemoteServlet is invalid.

**Action:** This is an unexpected error condition. The system administrator can check the server logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-00111: unable to create request object**

**Cause:** Unable to establish a connection to the DIRemoteServlet.

**Action:** Verify that the DIRemoteServlet URL is specified properly and retry request. The system administrator can check the server logs for more information.

**Level:** 1

**Type:** ERROR

---

**Impact:** Session

**ADFDI-00112: unable to create XmlTextWriter**

**Cause:** An unexpected error occurred while sending a request to the DIRemoteServlet.

**Action:** Retry your request. The system administrator can check the server logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-00113: unable to get request stream**

**Cause:** An unexpected error occurred while sending a request to the DIRemoteServlet.

**Action:** Retry your request. The system administrator can check the server logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-00114: The DIRemoteServlet returned an unrecognized value for element {0}, attribute {1}: {2}.**

**Cause:** The XML response returned from the DIRemoteServlet is invalid.

**Action:** This is an unexpected error condition. The system administrator can check the server logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-00115: The DIRemoteServlet returned an unexpected element type in the response XML: {0}**

**Cause:** The XML response returned from the DIRemoteServlet is invalid.

**Action:** This is an unexpected error condition. The system administrator can check the server logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-00116: The DIRemoteServlet returned invalid XML: unexpected end of response.**

**Cause:** An unexpected error occurred while reading the DIRemoteServlet response.

**Action:** Retry your request. The system administrator can check the server logs for more information.

**Level:** 1

**Type:** ERROR

---

**Impact:** Session

**ADFDI-00117: An unexpected error occurred reading the DIRemoteServlet response.**

**Cause:** An unexpected error occurred while reading the DIRemoteServlet response.

**Action:** Retry your request. The system administrator can check the server logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-00118: The DIRemoteServlet returned an error. A subsequent error occurred reading the error details from the response.**

**Cause:** An unexpected error occurred while reading the DIRemoteServlet response.

**Action:** Retry your request. The system administrator can check the server logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-00119: The DIRemoteServlet returned an error. A subsequent error occurred reading the error details from the response: unexpected element type: {0}.**

**Cause:** The XML response returned from the DIRemoteServlet is invalid.

**Action:** This is an unexpected error condition. The system administrator can check the server logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-00120: The DIRemoteServlet returned an error. A subsequent error occurred reading the error details from the response: unexpected element name: {0}.**

**Cause:** The XML response returned from the DIRemoteServlet is invalid.

**Action:** This is an unexpected error condition. The system administrator can check the server logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-00121: The expected XML element {0} was not found. Instead, the element {1} of type {2} was found.**

**Cause:** The XML response returned from the DIRemoteServlet is invalid.

**Action:** This is an unexpected error condition. The system administrator can check the server logs for more information.

**Level:** 1

**Type:** ERROR

---

**Impact:** Session

**ADFDI-00122: An unexpected XML element name was encountered (expected: {0}, found {1}).**

**Cause:** The XML response returned from the DIRemoteServlet is invalid.

**Action:** This is an unexpected error condition. The system administrator can check the server logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-00123: The expected XML end element {0} was not found. Instead, the element {1} of type {2} was found.**

**Cause:** The XML response returned from the DIRemoteServlet is invalid.

**Action:** This is an unexpected error condition. The system administrator can check the server logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-00124: The expected XML end element {0} was not found. Instead, the element {1} was found.**

**Cause:** The XML response returned from the DIRemoteServlet is invalid.

**Action:** This is an unexpected error condition. The system administrator can check the server logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-00125: The expected XML attribute {0} for element {1} was not found.**

**Cause:** The XML response returned from the DIRemoteServlet is invalid.

**Action:** This is an unexpected error condition. The system administrator can check the server logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-00126: An attempt was made to set the row position for control binding {0} to {1}. Iterator has {2} rows.**

**Cause:** Row index out of bounds.

**Action:** This is an unexpected error condition. The system administrator can check the server logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Session

---

**ADFDI-00127: A version mismatch was detected for {0}. Version {1} was found, version {2} was expected.**

**Cause:** The servlet version did not match the required level for the client.

**Action:** Upgrade the client and/or server so that compatible versions are in use.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-00128: unable to locate the column metadata for column with ID: {0}**

**Cause:** The binding container metadata did not match the data returned from the server.

**Action:** This is an unexpected error condition. The system administrator can check the server logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-00129: invalid Encode URL response**

**Cause:** The response received from the server for this request could not be processed. It may be caused by an exception in the server component.

**Action:** Retry your request. The system administrator can check the server logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-00130: The size of requested resource bundle ({1}) exceeds the maximum allowable limit: {0} bytes.**

**Cause:** The size of the resource bundle exceeded the supported size.

**Action:** Reduce the size of the resource bundle.

**Level:** 1

**Type:** WARNING

**Impact:** Files

**ADFDI-00131: The connection attempt has been canceled.**

**Cause:** The attempt to connect to the server was canceled.

**Action:** Retry the current action.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-00132: unable to execute Wininet method {0}; error code: {1}**

**Cause:** The Wininet library was unable to provide the requested service.

**Action:** Retry the current action, confirm connectivity, and/or consult the client logs for more information.



---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-00133: The user session has changed.**

**Cause:** The user session timed out or was otherwise invalid.

**Action:** Retry the current action, re-login, or re-establish a valid user session.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-00134: An attempt to connect to the web application has failed.**

**Cause:** The web application may not have been running or may not have been configured to allow client connections.

**Action:** Confirm that the web application is accepting connections from a web browser.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-00500: unable to execute Wininet method {0}; error code: {1}**

**Cause:** The Wininet library was unable to provide the requested service.

**Action:** Retry the current action, confirm connectivity, and/or consult the client logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-00501: An unexpected status: {0} ({1}) was returned from the server while requesting the URL: {2}**

**Cause:** The client was unable to complete its request to the server for the given URL. The server returned an unexpected status code.

**Action:** Retry the current action, confirm connectivity, and/or consult the client logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-00502: The client was unable to establish an unauthenticated session with the web application.**

**Cause:** An unexpected problem prevented the client from establishing a valid, unauthenticated session with the web application.

**Action:** Retry the current action, confirm the authentication configuration and connectivity, and/or consult the client logs and exception details for more information.

**Level:** 1

---

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-00503: A validation error occurred for metadata property {0}.**

**Cause:** An invalid property value was specified in the configuration metadata.

**Action:** Consult the client logs and exception details for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADFDI-00504: A validation warning occurred for metadata property {0}.**

**Cause:** An invalid property value was specified in the configuration metadata.

**Action:** Consult the client logs and exception details for more information.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**ADFDI-05000: Unexpected components exist at origin, {0}.**

**Cause:** More than one component was found at the specified origin.

**Action:** Delete the unwanted components.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ADFDI-05001: An unsupported binding type {0} exists in the page definition {1}.**

**Cause:** An unsupported binding type was encountered in the page definition file.

**Action:** Remove the unsupported binding from the page definition file.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ADFDI-05002: unable to locate page definition element in {0}**

**Cause:** The root element was missing from the page definition file.

**Action:** Ensure that the page definition file is well formed.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ADFDI-05003: unable to locate matching component palette item**

**Cause:** The metadata for this worksheet contained a reference to an unsupported component.

**Action:** Remove the unsupported component reference from the metadata.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**ADFDI-05006: A component already exists at origin {0}.**

**Cause:** An attempt was made to insert or move a component to a cell that is already in use as the origin of another component.

**Action:** Choose a different destination cell for the insertion or move operation.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**ADFDI-05007: This binding type is not supported: {0}.**

**Cause:** An attempt was made to insert a control binding with an unsupported type.

**Action:** Choose a different control binding to insert.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**ADFDI-05010: unable to move the component to new position; cannot parse position {0}**

**Cause:** The position specified for the new location of the component did not evaluate to a valid cell reference.

**Action:** Specify a valid cell reference. For example, use \$B\$3 for the cell in the second column and third row.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**ADFDI-05011: unable to move the component to new position; a component already exists at that position: {0}**

**Cause:** An attempt was made to move a component to a cell that is already in use as the origin of another component.

**Action:** Choose a different destination cell for the move operation.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**ADFDI-05012: unable to locate or open the page definition: {0}; no control bindings will be available; file: {1}**

**Cause:** An attempt was made to load the file specified. Either some portion of the file path was invalid, the file did not exist, or the user had insufficient permissions to open the file.

**Action:** Ensure that the relevant properties are configured correctly.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

---

**ADFDI-05013: There is no page definition file selected. So, no control bindings are available.**

**Cause:** User canceled the operation of selecting a page definition file.

**Action:** Select a valid page definition file to associate to the current worksheet.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**ADFDI-05015: An error occurred while updating the client registry**

**Cause:** The attempt to update the client registry was unsuccessful.

**Action:** Check client log file for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-05016: The workbook, {0}, is missing one or more required settings: ApplicationHomeFolder, WebPagesFolder.**

**Cause:** The specified workbook was missing one or more settings required for publishing.

**Action:** Provide valid values for all settings required for publishing.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADFDI-05500: error restoring server data context**

**Cause:** A failed attempt was made to reestablish the server state for a new user session.

**Action:** Check the configuration of the workbook to ensure that the attributes and actions used to reestablish the server state are defined correctly. Check the server to determine whether data has been deleted.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ADFDI-05501: value does not match for attribute {0}**

**Cause:** The value in the cache was not equal to the attribute value.

**Action:** Check the configuration of the workbook and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ADFDI-05502: unable to locate control binding {0} in binding container {1}**

**Cause:** A failed attempt was made to locate the binding information of a UI component.

**Action:** Check the configuration of the workbook and retry the operation.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ADFDI-05503: An incorrect binding type, {0}, exists for the control binding {1} in the binding container {2}.**

**Cause:** The binding type of the component differed from the binding type defined in the binding container.

**Action:** Check the configuration of the workbook and retry the operation. Ensure that the control binding type is defined correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ADFDI-05504: unable to find attribute: {0}**

**Cause:** A failed attempt was made to find an attribute in the data context cache.

**Action:** Check the configuration of the workbook and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ADFDI-05505: unable to find action: {0}**

**Cause:** A failed attempt was made to find a restore data context action in the data context cache.

**Action:** Check the configuration of the workbook and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ADFDI-05506: unable to find list control binding: {0}**

**Cause:** A failed attempt was made to locate the list control binding.

**Action:** Check the configuration of the workbook and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ADFDI-05507: invalid list control binding: {0}**

**Cause:** The binding type of the list control was not valid.

**Action:** Check the configuration of the workbook and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ADFDI-05508: An invalid list item is selected: {0}.**

---

**Cause:** An invalid list item was found while transferring data from a worksheet to the model.

**Action:** Check the configuration of the workbook and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ADFDI-05509: unable to find component: {0}**

**Cause:** A failed attempt was made to find the binding of the component.

**Action:** Check the configuration of the workbook and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ADFDI-05510: unable to insert column; column out-of-bounds**

**Cause:** A failed attempt was made to insert a dynamic column into the Table because the column was not within the named range.

**Action:** Check the configuration of the workbook and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ADFDI-05511: unable to remove column; column out-of-bounds**

**Cause:** A failed attempt was made to delete a dynamic column into the Table because the column was not within the named range.

**Action:** Check the configuration of the workbook and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ADFDI-05513: cannot find record**

**Cause:** A failed attempt was made to locate the record flagged for deletion.

**Action:** Check the configuration of the workbook and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ADFDI-05517: unable to find control {0}**

**Cause:** A failed attempt was made to locate the control in the binding container.

**Action:** Check the configuration of the workbook and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**ADFDI-05518: unable to set expression value for read-only expression**

**Cause:** A failed attempt was made to set the value for a read-only expression.

**Action:** Check the configuration of the workbook and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ADFDI-05519: unable to find component method, {0}, to invoke.**

**Cause:** A failed attempt was made to invoke the specified component method.

**Action:** Check the configuration of the workbook and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ADFDI-05524: unable to position on current table row**

**Cause:** A failed attempt was made to update the row position in a table for the purpose of invoking an action set on the row.

**Action:** Check the configuration of the workbook and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ADFDI-05529: unable to load binding container metadata**

**Cause:** A failed attempt was made to load the metadata that defines the binding container.

**Action:** Check the configuration of the workbook and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ADFDI-05530: unable to initialize worksheet: {0}**

**Cause:** A failed attempt was made to initialize a worksheet.

**Action:** Check the configuration of the workbook and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-05531: one or more rows could not be uploaded**

**Cause:** A failed attempt was made to upload data to the web application.

**Action:** Check the configuration of the workbook and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Session

---

**ADFDI-05535: one or more flagged rows could not be deleted**

**Cause:** A failed attempt was made to delete flagged rows.

**Action:** Check the configuration of the workbook and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-05537: The integrity of the workbook integration could not be determined. This workbook cannot be used safely. The integration will now terminate.**

**Cause:** The server was unable to read the client registry.

**Action:** Verify/correct the client registry in the web application.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-05538: The workbook integration has been altered after publishing. It can no longer be used safely. The integration will now terminate.**

**Cause:** The tampering check has determined that the workbook has been altered.

**Action:** Obtain a fresh, unaltered copy of the published workbook.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-05553: An invalid character was found in the server XML response. Verify the data from the data source and avoid any invalid character or binary data such as image be sent in the response.**

**Cause:** An attempt was made to read an invalid character in the XML data sent by the server.

**Action:** Verify the data from the data source and remove the invalid character from the data.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-05554: An incorrect version of the UI metadata schema is used in the workbook. Convert the UI metadata to the current version.**

**Cause:** The workbook contains UI metadata from an obsolete schema version.

**Action:** Convert the UI metadata to the current version.

**Level:** 1

**Type:** WARNING

**Impact:** Session

**ADFDI-05555: Required property {0} missing for component {1}.**

**Cause:** Required component property not defined.

**Action:** Check the configuration of the workbook and retry the operation.



---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ADFDI-05557: inserted row data must first be refreshed from server**

**Cause:** The row was successfully inserted to the database, but the row data has not been updated in the worksheet.

**Action:** First perform a Download or DownloadFlaggedRows operation, then retry the DeleteFlaggedRows operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ADFDI-05558: CacheDataContext must specify an action and at least one attribute.**

**Cause:** The metadata for this worksheet contains one or more invalid CacheDataContext definitions.

**Action:** Review and resolve CacheDataContext configuration issues and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ADFDI-05559: Row cache data is invalid.**

**Cause:** The row data cached for an ADF Table component is not valid.

**Action:** Re-download ADF Table data.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ADFDI-05560: Download action ignored for insert-only table, {0}.**

**Cause:** Download action has been included in an action-set, but is not applicable for an insert-only table.

**Action:** The developer should remove the action, or alter the table so it is no longer insert-only.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**ADFDI-05561: Failed to read multi-sync response as expected.**

**Cause:** The number of multi-sync responses did not match the number of multi-sync requests.

**Action:** Check your configuration and try the operation again.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**ADFDI-05562: Dependent list component has been misconfigured.**

---

**Cause:** The developer has incorrectly configured a list component that depends on another list component.

**Action:** Enable verbose logging on the client and review log for additional details on the specific configuration issue.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**ADFDI-05563: Restore Server Data Context Cache is corrupted**

**Cause:** The hidden cache of data was not in the expected format

**Action:** Obtain a new version of the workbook or Clear All Data

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**ADFDI-05564: The list binding "{0}" has {1} values. Only the first {2} items are stored in the cache.**

**Cause:** The number of items in the list exceeded the allowable limit.

**Action:** Reduce the number of items in the list. Or, configure the workbook to use a web page dialog for selecting an item from a large list of values.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**ADFDI-05565: unable to retrieve values for the list binding "{0}"**

**Cause:** A failed attempt was made to retrieve list values from the server.

**Action:** Check the configuration of the workbook and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ADFDI-05566: unable to retrieve values for the list binding "{0}", or for one or more of its dependent lists**

**Cause:** A failed attempt was made to retrieve list values from the server.

**Action:** Check the configuration of the workbook and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ADFDI-05567: Unable to restore server state. This condition is an unrecoverable. You will be automatically logged out of your current session.**

**Cause:** The attempt to restore server state failed.

**Action:** Log in to the application and retry the operation. Examine the server logs for additional information.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**ADFDI-05568: Failed to initialize cache for List binding: {0} in component/column: {1}, owned by type: {2} (in table: {3}).**

**Cause:** A failed attempt was made to retrieve and cache list values from the server.

**Action:** Check the configuration of the workbook and retry the operation.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**ADFDI-05569: Unable to report table status: status column is not visible.**

**Cause:** The table was configured so that the Status column is not visible.

**Action:** Configure the table so that the Status column is visible.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**ADFDI-05570: The Automation API encountered an unexpected condition. Details: {0}**

**Cause:** The Automation API encountered an unexpected condition.

**Action:** Check the configuration of the workbook and/or the automation scripts.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADFDI-05571: Failed to find resource. Alias: {0} Key: {1}**

**Cause:** The specified alias-key combination could not be located.

**Action:** Check the configuration of the workbook and/or resource files.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**ADFDI-05572: Failed to find resource bundle. Alias: {0}**

**Cause:** The specified resource bundle could not be located.

**Action:** Check the configuration of the workbook and/or resource files.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**ADFDI-06000: Workbook {0} is not enabled for {1}.**

**Cause:** The specified workbook was not the expected type.

**Action:** Specify only workbooks enabled for use with this product.

**Level:** 1

---

**Type:** ERROR

**Impact:** Files

**ADFDI-06001: An unexpected exception has occurred. The workbook {0} cannot be published.**

**Cause:** An unexpected exception occurred while attempting to publish the workbook.

**Action:** Verify settings, installation, and configuration. Then, retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ADFDI-06002: Error parsing the command line arguments.**

**Cause:** The command line arguments were not specified in the correct format.

**Action:** Check the usage of the tool and correct the input format.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADFDI-06003: Unexpected arguments specified: {0}**

**Cause:** The number of command line arguments exceeded the expected number.

**Action:** Specify only the expected arguments.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADFDI-07000: unable to open Excel file**

**Cause:** A failed attempt was made to open a workbook file.

**Action:** Ensure that the necessary file permissions have been applied, that the file exists, is not in use, and that it is a valid workbook file.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**ADFDI-07001: unable to find Excel file**

**Cause:** A failed attempt was made to find a workbook file.

**Action:** Ensure that the necessary file permissions have been applied, and that the file exists.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**ADFDI-07006: unable to update web.xml for ADF Desktop Integration**

**Cause:** An attempt to update the web application deployment descriptor failed.

**Action:** Apply the necessary changes using the deployment descriptor Properties dialog.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADFDI-07007: unable to update adf-config.xml for ADF Desktop Integration**

**Cause:** An attempt to update the application configuration failed.

**Action:** Apply the necessary changes by opening adf-config.xml in the source editor.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADFDI-07008: Unable to find ADF Desktop Integration installer**

**Cause:** The installer application was not found in the expected location.

**Action:** Ensure that the necessary file permissions have been applied, and that the file exists.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**ADFDI-07009: unable to start ADF Desktop Integration installer**

**Cause:** A failed attempt was made to execute the installer.

**Action:** Ensure that the necessary file permissions have been applied, that the file exists, and is not in use.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**ADFDI-07010: unable to copy template workbook**

**Cause:** A failed attempt was made to copy the template workbook.

**Action:** Ensure that the necessary file permissions have been applied, that the file exists, and is not in use.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**ADFDI-07500: unable to find version converters to perform the metadata conversion.**

**Cause:** Metadata converters for converting the workbook metadata to the current version cannot be found.

**Action:** Ensure there are converters supporting this conversion.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**ADFDI-07501: unable to perform an XSL transformation to migrate metadata.**

---

**Cause:** A failed attempt was made to perform an XSL transformation for migrating the metadata.

**Action:** Ensure both the XSLT stylesheet and the input XML document are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ADFDI-07503: cannot open workbook file {0}**

**Cause:** A failed attempt was made to open the workbook file during the Publish operation.

**Action:** Ensure that sufficient disk space is present and that user has the necessary privileges to open the workbook file.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**ADFDI-07504: cannot rename workbook file {0} to {1}**

**Cause:** A failed attempt was made to rename a workbook file during the Publish operation.

**Action:** Ensure that the user has sufficient privileges to delete the temporary file and to rename the workbook file.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**ADFDI-07506: cannot save workbook file {0}**

**Cause:** A failed attempt was made to save a copy of the workbook file.

**Action:** Ensure that sufficient disk space is present and that user has the necessary privileges to save a copy of the workbook file.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**ADFDI-07507: given buffer size is incorrect; given: {0}**

**Cause:** An incorrect value was supplied for the Workbook Parameters buffer size.

**Action:** Ensure that compatible versions of the client and server framework are in use. Check the workbook configuration and retry the operation with a different workbook.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ADFDI-07508: did not find expected start tag; found: {0}**

**Cause:** The workbook's internal format may be corrupted.

---

**Action:** Ensure that compatible versions of the client and server framework are in use. Check the workbook configuration and retry the operation with a different workbook.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ADFDI-07509: did not find expected end tag; found: {0}**

**Cause:** The workbook's internal format may be corrupted.

**Action:** Ensure that matching versions of the client and server framework are in use. Check the workbook configuration and retry the operation with a different workbook.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ADFDI-07510: mode length is incorrect; found: {0}**

**Cause:** The workbook's internal format may be corrupted.

**Action:** Ensure that compatible versions of the client and server framework are in use. Check the workbook configuration and retry the operation with a different workbook.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ADFDI-07511: AppRoot length is incorrect; found: {0}**

**Cause:** The workbook's internal format may be corrupted.

**Action:** Ensure that compatible versions of the client and server framework are in use. Check the workbook configuration and retry the operation with a different workbook.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ADFDI-07512: Workbook initialization parameters length is incorrect; found: {0}**

**Cause:** The workbook's internal format may be corrupted.

**Action:** Ensure that compatible versions of the client and server framework are in use. Check the workbook configuration and retry the operation with a different workbook.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-07513: Destination length {0} is less than found length {0}.**

**Cause:** Internal buffer size mismatch detected.

---

**Action:** Ensure that compatible versions of the client and server framework are in use. Check the workbook configuration and retry the operation with a different workbook.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ADFDI-07514: unable to create HttpRequest**

**Cause:** A failed attempt was made to create an http web resource.

**Action:** Check the configuration of the workbook to ensure that the web resource begins with http or https.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-07515: invalid response status code: {0}**

**Cause:** A failed attempt was made to access an http web resource.

**Action:** Check the configuration of the workbook and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-07516: A worksheet version mismatch was detected in worksheet {0}.**

**Version {1} was found, version {2} was expected.**

**Cause:** The workbook's internal format may be corrupted, or incompatible versions of the framework are in use.

**Action:** Ensure that compatible versions of the framework are in use; upgrade the workbook and framework.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ADFDI-07517: There are no more rows available in the metadata worksheet {0}.**

**Cause:** The maximum capacity for storing metadata has been reached, or the workbook's internal format may be corrupted.

**Action:** Remove some components from the workbook in order to free up space.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ADFDI-07518: The workbook has no metadata.**

**Cause:** The workbook may be corrupted or the metadata has been erased manually.

**Action:** Publish the workbook and try again or contact administrator.

**Level:** 1



---

**Type:** ERROR

**Impact:** Data

**ADFDI-07520: Unable to evaluate the expression '{0}' in '{1}'. Detail: {2}**

**Cause:** A failed attempt was made to evaluate an invalid expression.

**Action:** Verify and correct the expression.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**ADFDI-07521: Unable to evaluate the Excel formula '{0}' in '{1}'. Detail: {2}**

**Cause:** A failed attempt was made to evaluate an invalid Excel formula.

**Action:** Verify and correct the Excel formula.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**ADFDI-07522: Unable to execute the command: '{0}' while a cell is in editing mode.**

**Accept or cancel the changes to the current cell and then retry the command.**

**Cause:** An attempt was made to invoke a menu or toolbar command while a cell is open in editing mode.

**Action:** Accept or cancel the changes to the current cell and then retry the command.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**ADFDI-07523: Failed to delete worksheet**

**Cause:** The document may be corrupted.

**Action:** Obtain a fresh copy of the document.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**ADFDI-07524: The number of resource bundles ({1}) exceeds the supported limit of {0}.**

**Cause:** The number of resource bundles exceeded the supported limit.

**Action:** Reduce the number of resource bundles in this workbook.

**Level:** 1

**Type:** WARNING

**Impact:** Files

**ADFDI-07525: failed to suppress application alerts**

**Cause:** An attempt was made to suppress the display of alerts.

**Action:** Review the log files for additional details.

---

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**ADFDI-07526: unsupported version of Internet Explorer: {0}**

**Cause:** An unsupported version of Internet Explorer was found.

**Action:** Consult the documentation and install a supported version of Internet Explorer.

**Level:** 1

**Type:** WARNING

**Impact:** Session

**ADFDI-07527: An unexpected exception has occurred. The Workbook Designer cannot initialize. The design-time session will now abort.**

**Cause:** A failed attempt was made to initialize the workbook for Design Time mode.

**Action:** Check the configuration of the workbook and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-07528: An unexpected exception has occurred. The UI Controller cannot initialize. The runtime session will now abort.**

**Cause:** A failed attempt was made to initialize the workbook for Run Time mode.

**Action:** Check the configuration of the workbook and retry the operation. Ensure that the web application is running and accepting requests.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-07529: An unexpected exception has occurred. The workbook cannot initialize and will now abort.**

**Cause:** A failed attempt was made to initialize the workbook for an unknown mode.

**Action:** Check the configuration of the workbook and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-07530: An unexpected exception has occurred. The workbook cannot switch to test mode.**

**Cause:** A failed attempt was made to switch from Design Time mode to Test mode.

**Action:** Check the configuration of the workbook and retry the operation. Ensure that the web application is running and accepting requests.

**Level:** 1

---

**Type:** ERROR

**Impact:** Session

**ADFDI-07532: The workbook {0} cannot be used with this edition of {1}.**

**Cause:** An attempt was made to open a design-time or test mode workbook using the runtime edition.

**Action:** Use only published workbooks with the runtime edition. Install the design edition for other workbook types.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**ADFDI-07533: Unable to load add-in {0} because multiple editions are installed.**

**Cause:** Multiple editions of the add-in were installed.

**Action:** Remove one of the editions.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADFDI-07534: Unable to verify Trust Center setting. The Trust Center setting 'Trust access to the VBA project object model' is required for {0}.**

**Cause:** There was an unexpected problem while attempting to verify the Excel setting 'Trust access to the VBA project object model'.

**Action:** Activate the setting 'Trust access to the VBA project object model' by visiting the Excel Trust Center.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**ADFDI-07535: Unable to activate the Trust Center setting 'Trust access to the VBA project object model'. This setting is required for {0}.**

**Cause:** There was an unexpected problem while attempting to activate the Excel setting 'Trust access to the VBA project object model'.

**Action:** Activate the setting 'Trust access to the VBA project object model' by visiting the Excel Trust Center.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADFDI-08200: A valid {0} property must be chosen before editing this property.**

**Cause:** An attempt was made to edit the Web Pages Folder or Page Definition Folders properties before specifying a valid Web Application Home folder.

**Action:** Specify a valid Web Application Home folder property and retry the operation.

**Level:** 1

**Type:** WARNING

---

**Impact:** Configuration

**ADFDI-08201: A valid 'Web Pages' folder must be chosen. Do you want to do that now?**

**Cause:** An attempt was made to choose a web page for an ActionSet's Dialog.Page property before a valid Web Pages Folder property was specified.

**Action:** Specify a valid Web Pages Folder property and retry the operation.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**ADFDI-08202: A valid path that is relative to the 'ApplicationHomeFolder' property must be chosen.**

**Cause:** An attempt was made to choose a folder that is not a valid subfolder of the parent folder property.

**Action:** If necessary, change the 'ApplicationHomeFolder' property to a different value, and then choose a valid subfolder for this property.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**ADFDI-08203: A valid, absolute path name must be entered for this property.**

**Cause:** An attempt was made to choose a folder for the Application Home Folder property that is not a valid, absolute folder.

**Action:** Navigate to the folder in which your web application resides.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**ADFDI-50001: Resource bundle not found. bundle: {0}**

**Cause:** Unable to load the desired resource bundle class.

**Action:** Review the server logs for additional detail on the underlying cause.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADFDI-50002: Resource key not found. bundle**

**Cause:** Unable to find the desired key in the bundle.

**Action:** Review the server logs for additional detail on the underlying cause.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADFDI-55000: unknown desktop integration error**

**Cause:** An unexpected condition arose while handling the desktop integration request.

---

**Action:** Review the server logs for additional detail on the underlying cause.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-55001: XML element {0} missing required attribute {1}**

**Cause:** Invalid request XML was received.

**Action:** Review the server logs to ensure that only supported clients are accessing the ADFdi Remote Servlet.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-55002: The object, {0}, is not available.**

**Cause:** An expected object was not found or was unavailable.

**Action:** Ensure that both the client and server metadata are configured correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADFDI-55003: The object, {0}, is not available. Name: {1}**

**Cause:** An expected object was not found or was unavailable.

**Action:** Ensure that both the client and server metadata has been configured correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADFDI-55004: invalid GetResourceBundle request XML**

**Cause:** An invalid request was received.

**Action:** Review the server logs to ensure that only supported clients are accessing this servlet.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-55005: invalid SyncModel request XML**

**Cause:** An invalid request was received.

**Action:** Review the server logs to ensure that only supported clients are accessing this servlet.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-55006: unexpected value specified for XML element {0}**

---

**Cause:** An invalid request was received.

**Action:** Review the server logs to ensure that only supported clients are accessing this servlet.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-55007: invalid request XML**

**Cause:** An invalid request was received.

**Action:** Review the server logs to ensure that only supported clients are accessing this servlet.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-55008: invalid request method: {0}**

**Cause:** An invalid request was received.

**Action:** Review the server logs to ensure that only supported clients are accessing this servlet.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-55009: user session unavailable**

**Cause:** The user was not authenticated.

**Action:** No action is required.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-55010: expected XML element {0}; current element is {1}**

**Cause:** An invalid request was received.

**Action:** Review the server logs to ensure that only supported clients are accessing this servlet.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-55011: unexpected end-of-file in XML input stream**

**Cause:** An invalid request was received.

**Action:** Review the server logs to ensure that only supported clients are accessing this servlet.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**ADFDI-55012: invalid XML element: {0}**

**Cause:** An invalid request was received.

**Action:** Review the server logs to ensure that only supported clients are accessing this servlet.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-55013: expected XML reader state {0}; current state is {1}**

**Cause:** An invalid request was received.

**Action:** Review the server logs to ensure that only supported clients are accessing this servlet.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-55014: invalid child XML element {1} within XML element {0}**

**Cause:** The XML request sent by the client was invalid.

**Action:** Review the server logs to ensure that only supported clients are accessing this servlet.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-55017: The current row count exceeds the configured limit.**

**Cause:** The maximum number of rows requested by the client was exceeded.

**Action:** Submit a new request that conforms to the limit.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ADFDI-55018: exception occurred while reading an XML request**

**Cause:** A malformed request was received.

**Action:** Review the server logs to ensure that only supported clients are accessing this servlet.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-55019: exception occurred while writing the XML response**

**Cause:** Details about the underlying cause of the error are contained in the server logs.

**Action:** Review the server logs for details about additional steps to take.

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-55021: A version mismatch was detected for {0}. Version {1} was found, version {2} was expected.**

**Cause:** The client version does not match the required level for the DIRemoteServlet.

**Action:** Upgrade the client and/or server so that compatible versions are in use.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-55022: invalid SessionStatus request XML**

**Cause:** An invalid request was received.

**Action:** Review the server logs to ensure that only supported clients are accessing this servlet.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-55023: invalid MultiSyncModel request XML**

**Cause:** An invalid request was received.

**Action:** Review the server logs to ensure that only supported clients are accessing this servlet.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-55025: The control binding definition for item {0} is incorrect or incompatible. {1}**

**Cause:** The control binding definition has been misconfigured, or an incompatible control binding has been encountered.

**Action:** Check the control binding definition and ensure that only supported control bindings are used.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-55026: invalid TamperCheck request XML**

**Cause:** An invalid request was received.

**Action:** Review the server logs to ensure that only supported clients are accessing this servlet.

**Level:** 1

**Type:** ERROR



---

**Impact:** Requests/Responses

**ADFDI-55027: invalid EncodeURL request XML**

**Cause:** An invalid request was received.

**Action:** Review the server logs to ensure that only supported clients are accessing this servlet.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-55028: unexpected value specified for XML element {0}: {1}**

**Cause:** An invalid request was received.

**Action:** Review the server logs to ensure that only supported clients are accessing this servlet.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-55030: Cannot find the client registry file: {0}**

**Cause:** System could not find the client registry file in the web-inf location.

**Action:** Contact administrator

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-55031: An error occurred while trying to read client registry file**

**Cause:** While trying to read the client registry file, an I/O error occurred.

**Action:** Check logs for details of I/O error and address root cause to enable file access.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-55032: Unable to set attribute {0} (row object unavailable: {1})**

**Cause:** Client attempted to set an attribute value when no server row is available.

**Action:** Refresh the client data and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-55033: {0}: cannot convert the input value ({1}) to the expected data type ({2}).**

**Cause:** Input values are not consistent with expected data type.

**Action:** Correct input values according to data type.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**ADFDI-55034: Tamper check is disabled.**

**Cause:** The servlet was configured to disable the tamper check feature.

**Action:** Adjust servlet initialization parameters as desired.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**ADFDI-55035: Tamper check did not succeed. Result: {0}**

**Cause:** Tamper check was unable to match the hashcode of the client to the expected value.

**Action:** Adjust the configuration of tamper check or obtain a new copy of the workbook.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**ADFDI-55036: Received a request with unexpected content type: {0}**

**Cause:** A request with an unexpected content type was received.

**Action:** Use only supported content types.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**ADFDI-55037: Tamper check is configured to allow missing entries.**

**Cause:** The tamper check feature was configured to allow missing entries.

**Action:** Adjust servlet initialization parameters as desired.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**ADFDI-55038: The region binding includes an unsupported control type: {0}**

**Cause:** The page definition was configured to use an unsupported control type.

**Action:** Remove the unsupported type.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**ADFDI-55039: Unexpected servlet failure**

**Cause:** The servlet has failed due to an unexpected condition.

**Action:** Review the server logs for more information.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**ADFDI-55040: Unable to read requested resource bundle: {0}**

**Cause:** An attempt was made to load a resource bundle that was not available.

**Action:** Review the configuration to ensure that the resource bundle is available.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ADFDI-55041: Aborting the commit action for a transaction.**

**Cause:** The commit action was aborted for the transaction due to error in the binding container.

**Action:** Clear the error conditions and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ADFDI-55042: Unable to set position for {0} with value {1}**

**Cause:** A failed attempt was made to position a control binding by attribute value.

**Action:** Refresh the client data and retry the operation or review the server logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ADFDI-55043: Unable to locate parameter {0} for binding container {1}**

**Cause:** A failed attempt was made to set a parameter.

**Action:** Review the configuration to ensure that the parameter is available.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**ADFDI-55044: user session has changed**

**Cause:** The client user session timed out or was otherwise invalid.

**Action:** Establish a valid user session.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-55502: The length of the source data, {0}, is greater than the size of the destination buffer, {1}.**

**Cause:** Internal buffer size mismatch was detected.

**Action:** Ensure that compatible versions of the client and server framework are in use. Check the workbook configuration and retry the operation with a different workbook.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ADFDI-55510: unable to find expected workbook parameters start tag; found: {0}**

**Cause:** The internal format of the workbook might be corrupted.

**Action:** Run the workbook admin tool on this workbook. Ensure that compatible versions of the client and server framework are in use.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ADFDI-55511: unable to find expected workbook parameters end tag; found: {0}**

**Cause:** The internal format of the workbook might be corrupted.

**Action:** Run the workbook admin tool on this workbook. Ensure that compatible versions of the client and server framework are in use.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ADFDI-55512: The workbook parameters buffer size is incorrect: {0}.**

**Cause:** The internal format of the workbook might be corrupted.

**Action:** Run the workbook admin tool on this workbook. Ensure that compatible versions of the client and server framework are in use.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ADFDI-55513: The workbook parameters mode length is incorrect: {0}.**

**Cause:** The internal format of the workbook might be corrupted.

**Action:** Run the workbook admin tool on this workbook. Ensure that compatible versions of the client and server framework are in use.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ADFDI-55514: The workbook parameters application root length is incorrect: {0}.**

**Cause:** The internal format of the workbook might be corrupted.

**Action:** Run the workbook admin tool on this workbook. Ensure that compatible versions of the client and server framework are in use.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ADFDI-55515: The workbook parameters collection length is incorrect: {0}.**

---

**Cause:** The internal format of the workbook might be corrupted.

**Action:** Run the workbook admin tool on this workbook. Ensure that compatible versions of the client and server framework are in use.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**ADFDI-55516: Unexpected filter failure**

**Cause:** The filter has failed due to an unexpected condition.

**Action:** Review the server logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses



---

## ADFF\_BIND-00001 to ADFF\_BIND-00045

**ADFF\_BIND-00001: ADFv: Trouble getting the mutable document from MDS. {0}.**

**Cause:** MDS repository may be configured incorrectly, or may have been corrupted.

**Action:** Check MDS repository configuration and clear repository.

**Level:** 2

**Type:** WARNING

**Impact:** Programmatic

**ADFF\_BIND-00002: ADFv: ADF JSF databinding support installed.**

**Cause:** n/a.

**Action:** n/a.

**Level:** 2

**Type:** NOTIFICATION

**Impact:** Configuration

**ADFF\_BIND-00003: ADFv: ADF JSF databinding support for BC4J installed.**

**Cause:** n/a.

**Action:** n/a.

**Level:** 2

**Type:** NOTIFICATION

**Impact:** Configuration

**ADFF\_BIND-00004: ADFv: Cannot convert "{0}" into Array. Updating of arrays not supported.**

**Cause:** Error in application.

**Action:** Contact your application support person.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFF\_BIND-00005: ADFv: closing } not found in expression: {0}.**

**Cause:** Error in binding expression in application.

**Action:** Contact your application support person to correct binding expression.

---

**Level:** 2  
**Type:** ERROR  
**Impact:** Programmatic  
**ADFF\_BIND-00006: ADFv: rowIterator is null.**  
**Cause:** Internal error.  
**Action:** Contact your application support person.

**Level:** 2  
**Type:** WARNING  
**Impact:** Data  
**ADFF\_BIND-00007: ADFv: Rowkey does not have any primary key attributes.**  
**Rowkey:** {0}, **table:** {1}.  
**Cause:** Application or data error.  
**Action:** Contact your application support person to check for data corruption.

**Level:** 2  
**Type:** ERROR  
**Impact:** Programmatic  
**ADFF\_BIND-00008: ADFv: No row found for rowKey: {0}.**  
**Cause:** Application or data error.  
**Action:** Contact your application support person to check for data corruption.

**Level:** 2  
**Type:** WARNING  
**Impact:** Data  
**ADFF\_BIND-00009: ADFv: Could not find selected item matching value {0} of type: {1} in the list-of-values.**  
**Cause:** Application or data error.  
**Action:** Contact your application support person to ensure list data has not been corrupted.

**Level:** 2  
**Type:** WARNING  
**Impact:** Programmatic  
**ADFF\_BIND-00010: ADFv: AttributeDef not found for property: {0}.**  
**Cause:** Application or binding metadata error.  
**Action:** Contact your application support person to ensure binding metadata is correct.

**Level:** 2  
**Type:** WARNING  
**Impact:** Programmatic  
**ADFF\_BIND-00011: ADFv: Property '{0}' not supported on AttributeHints.**  
**Cause:** Application or binding metadata error.



---

**Action:** Contact your application support person to ensure binding metadata is correct.

**Level:** 2

**Type:** WARNING

**Impact:** Programmatic

**ADFF\_BIND-00012: ADFv: Row is null for rowKey: {0}.**

**Cause:** Application or data error.

**Action:** Contact your application support person to ensure data is correct.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFF\_BIND-00013: ADFv: Row is null at absoluteIndex: {0} rangeStart: {1} rangeSize: {2} estimatedRowCount: {3}.**

**Cause:** Application or data error.

**Action:** Contact your application support person to ensure data is correct.

**Level:** 2

**Type:** WARNING

**Impact:** Programmatic

**ADFF\_BIND-00014: ADFv: Unable to create the temporary file while saving the layout of the resultant component for the query.**

**Cause:** Error in MDS configuration.

**Action:** Ensure MDS configuration is correct and resources are accessible.

**Level:** 2

**Type:** WARNING

**Impact:** Programmatic

**ADFF\_BIND-00015: ADFv: Something bad has happened. The file should have been there.**

**Cause:** Error in MDS file.

**Action:** Ensure MDS configuration is correct and all resources are accessible.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFF\_BIND-00016: ADFv: The resultant component with the Id {0} does not exist.**

**Cause:** Error in MDS repository metadata.

**Action:** Contact your application support person to ensure that MDS repository isn't corrupted.

**Level:** 2

**Type:** WARNING

**Impact:** Programmatic

---

**ADFF\_BIND-00017: ADFv: Result component with the Id {0} not found in the parent.**

**Cause:** Error in MDS repository metadata.

**Action:** Contact your application support person to ensure that MDS repository isn't corrupted.

**Level:** 2

**Type:** WARNING

**Impact:** Programmatic

**ADFF\_BIND-00019: ADFv: Unable to read the contents of the streamedObject.**

**Cause:** Error in MDS repository metadata.

**Action:** Contact your application support person to ensure that MDS repository isn't corrupted.

**Level:** 2

**Type:** WARNING

**Impact:** Programmatic

**ADFF\_BIND-00020: ADFv: Error filtering based on date strings is not supported(filter field): {0}.**

**Cause:** Error in MDS repository metadata.

**Action:** Contact your application support person to ensure that MDS repository isn't corrupted.

**Level:** 2

**Type:** WARNING

**Impact:** Programmatic

**ADFF\_BIND-00021: ADFv: Null PagePhaseListener.**

**Cause:** Trying to add a null phase listener to a page.

**Action:** Contact your application support person to check the page configuration.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFF\_BIND-00022: ADFv: Unknown DataChangeType: {0}.**

**Cause:** Cause unknown.

**Action:** Contact your application support person.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFF\_BIND-00023: ADFv: Invalid attribute name: {0}.**

**Cause:** Check source page for attribute and correct.

**Action:** Contact your application support person.

**Level:** 2

---

**Type:** ERROR

**Impact:** Programmatic

**ADFF\_BIND-00024: ADFv: Illegal DataExceptionEvent severity type: {0}.**

**Cause:** Cause unknown.

**Action:** Contact your application support person.

**Level:** 2

**Type:** ERROR

**Impact:** Data

**ADFF\_BIND-00025: ADFv: Could not convert instance: {0} of type: {1} into type {2} {3}.**

**Cause:** Cause unknown.

**Action:** Contact your application support person.

**Level:** 2

**Type:** ERROR

**Impact:** Data

**ADFF\_BIND-00026: ADFv: Property: {0} not found on Row: {1}.**

**Cause:** Cause unknown.

**Action:** Contact your application support person.

**Level:** 2

**Type:** ERROR

**Impact:** Data

**ADFF\_BIND-00027: ADFv: Unsupported operation exception.**

**Cause:** Application performed an unsupported operation.

**Action:** Contact your application support person to correct application error.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFF\_BIND-00028: ADFv: Abort processing exception.**

**Cause:** Cause unknown.

**Action:** Contact your application support person.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFF\_BIND-00029: ADFv: No container available.**

**Cause:** Binding metadata is incorrect or corrupted.

**Action:** Contact your application support person to ensure binding metadata is correct.

**Level:** 2

---

**Type:** ERROR

**Impact:** Programmatic

**ADFF\_BIND-00030: ADFv: Not inside a container.**

**Cause:** Binding metadata is incorrect or corrupted.

**Action:** Contact your application support person to ensure binding metadata is correct.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFF\_BIND-00031: ADFv: Unknown DataChangeEventPolicy {0}.**

**Cause:** Binding metadata is incorrect or corrupted.

**Action:** Contact your application support person to ensure binding metadata is correct.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFF\_BIND-00032: ADFv: Illegal state exception.**

**Cause:** Cause unknown.

**Action:** Contact your application support person.

**Level:** 2

**Type:** ERROR

**Impact:** Data

**ADFF\_BIND-00033: ADFv: Attempt to start active for same DataUpdateListener.**

**Cause:** Cause unknown.

**Action:** Contact your application support person.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFF\_BIND-00034: ADFv: stopActiveData called for the unregistered listener.**

**Cause:** Cause unknown.

**Action:** Contact your application support person.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFF\_BIND-00035: ADFv: Illegal state, parent can't be null.**

**Cause:** Cause unknown.

**Action:** Contact your application support person.

**Level:** 2

---

**Type:** ERROR

**Impact:** Data

**ADFF\_BIND-00036: ADFv: rowIndex: {0} cannot be less than -1.**

**Cause:** Cause unknown.

**Action:** Contact your application support person.

**Level:** 2

**Type:** ERROR

**Impact:** Data

**ADFF\_BIND-00037: ADFv: Could not find row: {0} with key: {1} inside parent: {2} with key: {3}.**

**Cause:** Cause unknown.

**Action:** Contact your application support person.

**Level:** 2

**Type:** ERROR

**Impact:** Data

**ADFF\_BIND-00038: ADFv: Error getting the application factory.**

**Cause:** Error configuring databinding library.

**Action:** Ensure that the databinding library is included in the application.

**Level:** 2

**Type:** WARNING

**Impact:** Data

**ADFF\_BIND-00039: ADFv: Error getting the application object from factory.**

**Cause:** Error configuring databinding library.

**Action:** Ensure that the databinding library is included in the application.

**Level:** 2

**Type:** WARNING

**Impact:** Data

**ADFF\_BIND-00040: Invalid Data Provided for search operation.**

**Cause:** Invalid data.

**Action:** Clear Search Data and enter valid data.

**Level:** 2

**Type:** WARNING

**Impact:** Data

**ADFF\_BIND-00041: ADFv: Null Calendar Activity Definition. Please check the page definition page.**

**Cause:** Application error.

**Action:** Contact your application support person.

**Level:** 2

---

**Type:** ERROR

**Impact:** Data

**ADFF\_BIND-00042: ADFv: Calendar Activity Id and Provider Id cannot be null.**

**Cause:** Application data error.

**Action:** Contact your application support person.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFF\_BIND-00043: ADFv: Illegal state, trying to associate client id {0} with databinding which is already associated with a different client id {1}.**

**Cause:** Application data error.

**Action:** Contact your application support person.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

**ADFF\_BIND-00044: ADFv: Unable to resolve URL through MDS for the facelet resource. Customizations if any will not be applied. {0}.**

**Cause:** Failed to attach MDS stream handler to the URL for facelet resource.

**Action:** Contact your application support person.

**Level:** 2

**Type:** WARNING

**Impact:** Programmatic

**ADFF\_BIND-00045: Invalid value: {0}.**

**Cause:** Invalid value entered in the input field of listofvalues component.

**Action:** Enter a valid value or pick a value from the list of values.

**Level:** 2

**Type:** ERROR

**Impact:** Programmatic

---

## APM-10000 to APM-10015

**APM-10000: Template cannot be saved because a template with same name already exists.**

**Cause:** You are trying to save a role-template name that already exists in the system.

**Action:** Change the name of the template being saved to a different name that doesn't already exist in the system.

**Level:** 1

**Type:** ERROR

**Impact:** Authorization Policy Manager/Role-Template

**APM-10001: Duplicate dimension alias name detected.**

**Cause:** You have specified a name of dimension column-alias that has been defined for another column.

**Action:** Change the name of the column-alias to one that has not been used for a different column.

**Level:** 1

**Type:** ERROR

**Impact:** Authorization Policy Manager/Role-Template

**APM-10002: Template naming convention definition requires at least two rows.**

**Cause:** TODO

**Action:** TODO

**Level:** 1

**Type:** ERROR

**Impact:** Authorization Policy Manager/Role-Template

**APM-10003: Template naming convention definition requires at least one dimension base object.**

**Cause:** You are trying to save a role-template document without defining any dimension values.

**Action:** Specify a valid SQL statement that returns at least a single row.

**Level:** 1

**Type:** ERROR

**Impact:** Authorization Policy Manager/Role-Template

---

**APM-10004: Template naming convention definition requires at least one role base object.**

**Cause:** You are trying to save a role-template document without specifying a base-role.

**Action:** Specify a valid base-role in the base-role tab.

**Level:** 1

**Type:** ERROR

**Impact:** Authorization Policy Manager/Role-Template

**APM-10005: Template name contains invalid character.**

**Cause:** The name of the template contains one or more invalid characters.

**Action:** Remove the invalid character and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Authorization Policy Manager/Role-Template

**APM-10006: Template display name cannot be blank.**

**Cause:** You are trying to save a role-template document without specifying its display name.

**Action:** Specify valid display-name, and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Authorization Policy Manager/Role-Template

**APM-10007: Template name is too long (Max length is 30 characters)**

**Cause:** The number of characters you have entered for the template-name exceeds the max-number allowed.

**Action:** Reduce the number of characters for the template-name, and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Authorization Policy Manager/Role-Template

**APM-10008: Template name cannot contains white space.**

**Cause:** The template-name cannot contain any spaces.

**Action:** Remove any spaces in the template-name, and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Authorization Policy Manager/Role-Template

**APM-10009: Template operation did not complete due to system error. Please contact administrator for detail.**

**Cause:** Unexpected error occurred during Role-Template operation.

**Action:** Contact your system administrator.

**Level:** 1



---

**Type:** ERROR

**Impact:** Authorization Policy Manager/Role-Template

**APM-10010: Dimension column alias cannot contain blank value.**

**Cause:** One or more column-aliases contain null values.

**Action:** Provide values for all the column-aliases.

**Level:** 1

**Type:** ERROR

**Impact:** Authorization Policy Manager/Role-Template

**APM-10011: Template dimension sql has not been defined yet.**

**Cause:** You must define a SQL statement before the document can be saved.

**Action:** Provide a valid SQL statement.

**Level:** 1

**Type:** ERROR

**Impact:** Authorization Policy Manager/Role-Template

**APM-10012: Template naming convention definition requires at least two rows.**

**Cause:** You have not provided enough values to enforce name-uniqueness during data-role generation. There has to be at least two naming-rule defined for attributes from each entity: one or more attributes from base-role and one or more attributes from dimension.

**Action:** Select an attribute from base-role attributes and one from dimension-value attributes.

**Level:** 1

**Type:** ERROR

**Impact:** Authorization Policy Manager/Role-Template

**APM-10013: Template dimension alias value cannot contains white space.**

**Cause:** One of the column-aliases contain invalid characters.

**Action:** Remove the invalid character from the column-alias and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Authorization Policy Manager/Role-Template

**APM-10014: No data return from sql. Please check the syntax of the SQL you provided.**

**Cause:** The SQL you have entered is either invalid and/or not returning any data.

**Action:** Correct the SQL statement and/or ensure the SQL returns data.

**Level:** 1

**Type:** ERROR

**Impact:** Authorization Policy Manager/Role-Template

**APM-10015: Error occurs and template operation did not complete. Please contact administrator for detail.**

---

**Cause:** Role-Template execution did not complete successfully due to unknown reason.

**Action:** Contact your system-administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Authorization Policy Manager/Role-Template

---

## ASCRS-00001 to ASCRS-00143

**ASCRS-00001: {0} of {1} completed successfully.**

**Cause:** Operation is completed successfully.

**Action:** Informational, no further action is needed.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00002: {0} of {1} canceled.**

**Cause:** Operation is canceled.

**Action:** Informational, no further action is needed.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00003: {0} of {1} failed.**

**Cause:** Operation failed.

**Action:** Inspect the log files for the detailed cause.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00004: UP state of CRS with CRS HOME {0} could not be verified.**

**Cause:** CRS could be down.

**Action:** Try to restart CRS. Refer to CRS documentation if it persists.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00006: Please run the following as root to complete this operation. {0}**

**Cause:** Root privilege is needed for some resource task.

**Action:** Do as instructed.

**Level:** 1

---

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00007: Cluster nodes specified {1} is different from cluster nodes - {2} - for dependent resource {0}**

**Cause:** Not matching cluster nodes between this resource and its dependents.

**Action:** Please ensure the same set of cluster nodes for this resource and its dependents.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00008: Resource {0} cannot be deleted since dependent resources exist.**

**Cause:** Named resource cannot be deleted since other resources depend on it.

**Action:** Delete all the dependent resources first.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00009: Resource {0} already manages same object as {1} wants to manage: {2}.**

**Cause:** One physical resource shouldn't be managed twice by CRS.

**Action:** Delete and re-create the existing resource or update it.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00012: Invalid cluster node: {0}.**

**Cause:** The named node is not in the cluster.

**Action:** Specify the correct node name. Refer to CRS command olsnodes for listing node names.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00013: Invalid policy type: {0}.**

**Cause:** Invalid policy type specification.

**Action:** Refer to ASCRS online help for this operation and read about policy values.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00016: Malformed IP address or invalid host name : {0}.**

**Cause:** Malformed IP address or invalid host name

**Action:** Supply a valid IP or host name.

---

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00017: Invalid file or directory: {0}.**

**Cause:** The named file or directory doesn't exist.

**Action:** Specify a valid file or directory for this argument.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00019: Resource not found: {0}.**

**Cause:** Named resource doesn't exist.

**Action:** Please provide correct resource name.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00020: CRS error while calling {0}. Return code {1}.**

**Cause:** Failure of CRS command as indicated.

**Action:** Refer to CRS troubleshooting documentation.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00021: Resource of type {0} and name {1} already exists.**

**Cause:** Named resource was already created.

**Action:** Create a different resource or delete this one and try again.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00022: File {0} cannot be read.**

**Cause:** Unreadable file.

**Action:** Change the file permission to make it readable for the ASCRS user.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00026: Error trying to retrieve require resources for {0}.**

**Cause:** CRS cs\_stat has failed to return complete information for named resource.

**Action:** Ensure CRS is running, diagnose CRS cs\_stat. Refer to CRS troubleshooting documentation.

**Level:** 1

---

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00028: Error writing or creating file {0}.**

**Cause:** The file cannot be opened or created for writing.

**Action:** Ensure the file directory exists and the user has write permission on the named file.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00030: VIP {0} provided is up but not on this node.**

**Cause:** The named VIP is already in use on this network.

**Action:** Forfeit the use of this VIP on the other host, or select a different VIP.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00031: Resource {0} is already down.**

**Cause:** The named resource is already down.

**Action:** None.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00032: Resource {0} is already up on the node {1}.**

**Cause:** The named resource is already up on the node when trying to start it.

**Action:** None.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00033: Resource {0} is not in state to switch.**

**Cause:** Resource is not in good state for switch operation.

**Action:** Please refer to the CRS documentation for resource switchover.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00034: Specified node {1} is not in hosting members for {0}.**

**Cause:** Invalid node member name for the names resource.

**Action:** Specify the correct node name.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

---

**Impact:** High Availability

**ASCRS-00035: Permissions and/or ownership on resource {0} are not correct for this operation.**

**Cause:** The user is not qualified to perform this operation.

**Action:** Delegate this task to the owner of this resource.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00036: No parameters to update.**

**Cause:** No updatable information is specified for update operation.

**Action:** Specify updatable parameter/value. Refer to the online help.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00037: Network Interface {0} is invalid.**

**Cause:** Network Interface is invalid.

**Action:** Specify a valid network interface that is in working state.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00038: VIP {0} is up on this node but not on the provided interface.**

**Cause:** The named vip is in use by another interface on this node.

**Action:** Please make sure the vip is used for one interface.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00039: Update operation not allowed if either the target or resource state is not in offline state.**

**Cause:** Resource is not in good state for update operation.

**Action:** Stop and take the resource offline.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00040: Are you sure you want to delete {0} (y/n) ?**

**Cause:** Need user confirmation for resource deletion.

**Action:** Answer "y" for yes or "n" for no.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

---

**Impact:** High Availability

**ASCRS-00041: Are you sure you want to stop {0} (y/n) ?**  
**Cause:** Need user confirmation for resource stop.  
**Action:** Answer "y" for yes or "n" for no.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00042: Are you sure you want to switch over {0} (y/n) ?**  
**Cause:** Need user confirmation for resource switchover.  
**Action:** Answer "y" for yes or "n" for no.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00043: Unrecognized ASCRS resource name {0}.**  
**Cause:** Without type information, this name cannot be resolved to a canonical ASCRS resource name.  
**Action:** Use a canonical name, or specify resource type.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00044: ASCRS resource name {0} is not of type {1}.**  
**Cause:** The resource name and type are not consistent.  
**Action:** When the name is canonical, ensure its type is consistent if it is specified.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00045: Malformed CRS parameter specification: {0}.**  
**Cause:** Syntax error in CRS resource "-o" parameter.  
**Action:** Refer to CRS documentation or ASCRS online help for this operation.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00046: Invalid parameter name "{0}" for this resource.**  
**Cause:** This is not an ASCRS parameter or it is not applicable to this resource.  
**Action:** Avoid using this parameter for this resource.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability



---

**ASCRS-00047: Parameter "{0}" can only assume integer values.**

**Cause:** This argument doesn't accept non-integer values.

**Action:** Supply a valid integer value for this argument.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00048: Value is out of range for parameter: {0}.**

**Cause:** Integer value is out of valid range.

**Action:** Follow ASCRS online help for this command for correct value.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00049: "{0}" is not a valid value for parameter "{1}".**

**Cause:** The value for the command-line switch is not valid.

**Action:** Follow ASCRS online help for this command for the correct value.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00050: No disk is mounted at "{0}".**

**Cause:** No shared disk is mounted on the named mount point.

**Action:** Mount the shared disk.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00051: No signature found on shared disk at "{0}".**

**Cause:** Signature file is missing on the root of the shared disk.

**Action:** Create the .ascrssf file on the root of the shared disk.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00052: Value must be an absolute path name for argument: "{0}".**

**Cause:** The path name is not an absolute path.

**Action:** Use a valid absolute path name.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00053: Path does not exist: "{0}".**

**Cause:** The named path doesn't exist as a disk mount point.

---

**Action:** Create the path name if it is intended, or use a different valid path.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00054: Unrecognized AS component name: "{0}".**

**Cause:** User has supplied an invalid AS component name.

**Action:** Supply the correct WebLogic server name if this is WebLogic resource, or the OPMN component id if it is OPMN resource.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00055: Not a valid AS config file: "{0}".**

**Cause:** The AS config file in the component home is damaged, or this is not an AS component home.

**Action:** Correct the configuration file and make sure this is a valid AS component home.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00056: Not recognized as an AS component home: "{0}".**

**Cause:** User has supplied an invalid AS component home.

**Action:** Follow the ASCRS online help to identify the component home correctly.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00057: Node manager is not reachable at "{0}:{1}".**

**Cause:** AS node manager is down.

**Action:** Make sure node manager is running on the specified host and port.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00058: Managed server "{0}" is not reachable.**

**Cause:** The named AS server is down or invalid as user input.

**Action:** Make sure the server name is correct and running.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00059: Please run ascrsctl prepare command.**

**Cause:** AS environment is not ready for CRS management.

---

**Action:** Run ascrsctl prepare command to set it up.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00060: Please run ascrsctl check command for details.**

**Cause:** AS environment preparation failed.

**Action:** Run ascrsctl check command for details.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00061: Cannot write on the shared disk mounted at {0}.**

**Cause:** The user doesn't have write permission on the name disk.

**Action:** Make sure this is the right user for this operation, or grant this user write permission on this disk.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00062: Cannot connect to the node manager with the existing saved credential.**

**Cause:** Cannot log in to AS node manager due to invalid login credential file.

**Action:** Follow the Oracle Fusion Middleware High Availability Guide to re-create the node manager login credential files.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00063: Cannot connect to server {0} with the existing saved credential.**

**Cause:** Cannot log in to the named AS server due to invalid login credential file.

**Action:** Follow the Oracle Fusion Middleware High Availability Guide to re-create the WebLogic server login credential files.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00064: CRS command {0} execution encountered I/O errors.**

**Cause:** This command could be missing, corrupted, or other I/O issue.

**Action:** Ensure this CRS command can be executed manually. Check CRS logs.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00065: Stop of this resource will also stop these dependent resources:**

---

**Cause:** Other resources are or will be running and it depends on this resource.

**Action:** Confirm or cancel when this message is prompted.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00066: Start of resource {0} on node {1} completed successfully.**

**Cause:** Another resource is running and it depends on this resource.

**Action:** Either stop avoid this operation or use -f option.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00067: The current user is not the CRS home owner.**

**Cause:** The current user is not the CRS home owner.

**Action:** Run this command as CRS home owner.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00068: Circular ASCRS resource dependency is detected.**

**Cause:** The specified dependency resources depends on the updated resource.

**Action:** Choose different required resources.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00069: Switch of this resource will also switch these related resources:**

**Cause:** Other resources are running that depend on or are required by this resource.

**Action:** Confirm or cancel when this message is prompted.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00070: Command {0} finished with errors. Refer to ASCRS log files for details.**

**Cause:** The named ASCRS command has failed for some unknown reason.

**Action:** Refer to ASCRS ascrctl.log or the ASCRS agent log for this resource.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00071: The number of cluster nodes should be more than one.**

---

**Cause:** Too few cluster nodes are specified for hosting the resource.

**Action:** Use default or specify at least two cluster nodes

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00072: Type {0} dependencies cannot be empty for this resource.**

**Cause:** The specified type of dependencies are not allowed to be all removed.

**Action:** Update the dependencies with other resource names of the desired type

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00073: Not a valid XML file: "{0}".**

**Cause:** The XML file is damaged.

**Action:** Correct the file and try again.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00074: Value is not a number or out of bound for {0} in configuration for policy {1} and resource type {2}.**

**Cause:** The specified value for the named CRS property is either a non-number or out of range.

**Action:** Choose a number in range. Consult ASCRS configuration for property ranges.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00075: Invalid monitor name: "{0}".**

**Cause:** The monitor name is not found in ASCRS monitor configuration.

**Action:** Select a valid monitor name.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00102: ASCRS command is missing or invalid.**

**Cause:** ASCRS command is missing or invalid.

**Action:** Supply correct ASCRS command, or run "ascrsctl help" for details.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

---

**ASCRS-00103: Value is missing or empty for argument -{0}.**

**Cause:** The named argument cannot have an empty value.

**Action:** Supply the correct value for the argument. Run "ascrsctl help" for details

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00104: No value is needed for argument -{0}.**

**Cause:** The named argument cannot have a value.

**Action:** Remove the value for the argument. Run "ascrsctl help" for details.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00105: Invalid ASCRS command-line syntax: {0}.**

**Cause:** Invalid ASCRS command-line syntax.

**Action:** Run "ascrsctl help" for details.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00106: Required argument is missing: -{0}.**

**Cause:** The named argument is mandatory for this operation.

**Action:** Refer to ascrsctl online help for details about this operation.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00107: Multiple occurrence of the same argument or its aliases not allowed: {0}.**

**Cause:** This argument cannot be followed with multiple values.

**Action:** Supply a single value or refer to the ascrsctl online help for details.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00108: Invalid database component id: {0}.**

**Cause:** Invalid database component id is specified.

**Action:** If componentID is specified, it should be dbinstance, dbconsole, jobscheduler (Windows only) or vsswriter (Windows only).

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

---

**ASCRS-00140: Online help does not exist for this request.**

**Cause:** Invalid ascrsctl help specification.

**Action:** Run "ascrsctl help" for details.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00141: Invalid ASCRS resource type {0}.**

**Cause:** Invalid ASCRS resource type.

**Action:** Run "ascrsctl help" for details.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00142: Invalid ASCRS command-line keyword {0}.**

**Cause:** Invalid ASCRS argument name for ASCRS online help.

**Action:** Run "ascrsctl help" for details.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability

**ASCRS-00143: Invalid ASCRS resource name: "{0}".**

**Cause:** An ASCRS resource name must start with an English alphabet or number and it can only contain English alphabets, numbers and the dot character. It cannot be called "nil".

**Action:** Check for invalid special characters in the name.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** High Availability





---

## B2B-50006 to B2B-52331

### **B2B-50006: Exception Received**

**Cause:** B2B received an exception message from the trading partner.

**Action:** Review the UI report for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

### **B2B-50007: Notification of failure received**

**Cause:** B2B received a notification of failure - out of band exception from trading partner

**Action:** Review the UI report for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

### **B2B-50009: Failed to Send**

**Cause:** B2B cannot send message to the trading partner

**Action:** Review the UI report for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

### **B2B-50010: Trading partner agreement identification error**

**Cause:** B2B cannot identify an agreement using the current details

**Action:** Review the UI report for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason

---

that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-50011: Message Correlation Error**

**Cause:** B2B cannot correlate the message

**Action:** Review the UI report for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-50012: Pack/Unpack Error**

**Cause:** Error in packaging

**Action:** Review the UI report for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-50013: Security Error**

**Cause:** Error in security validation

**Action:** Review the UI report for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-50014: General Error**

**Cause:** Internal error in engine

**Action:** Review the UI report for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-50015: In-band notification error**

---

**Cause:** Internal engine error

**Action:** Review the UI report for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-50025: Repository error**

**Cause:** Error accessing metadata repository

**Action:** Review the UI report for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-50027: Failed to write data into output stream.**

**Cause:** Failed to write data into output stream.

**Action:** Review the diagnostic log for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-50028: Failed to read data from input stream.**

**Cause:** Failed to read data from input stream.

**Action:** Review the diagnostic log for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-50029: B2B runtime error**

**Cause:** A runtime error has occurred.

**Action:** Review the UI report for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

---

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-50031: B2B general error**

**Cause:** A general error has occurred

**Action:** Review the UI report for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-50032: B2B exchange protocol negative acknowledge received**

**Cause:** Received a negative exchange acknowledge message.

**Action:** Review the negative exchange acknowledge message to determine the cause, or check with the trading partner.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-50033: B2B functional acknowledgment processing error**

**Cause:** An error occurred during functional acknowledgment processing.

**Action:** Review the diagnostic log for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-50034: B2B negative functional acknowledgment**

**Cause:** A negative functional acknowledgment is received.

**Action:** Review the negative functional acknowledge message to determine the cause or check with the trading partner.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-50035: B2B exception message processing error**

**Cause:** An error occurred during exception message processing.

**Action:** Review the diagnostic log for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

---

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-50036: B2B trading partner agreement identification error**

**Cause:** An error had occurred during identify trading partner agreement.

**Action:** Review the diagnostic log for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-50037: B2B inbound message processing error**

**Cause:** An error occurred during incoming message processing.

**Action:** Review the diagnostic log for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-50041: TopLink server session initialization error**

**Cause:** An error occurred during TopLink server session initialization.

**Action:** Review the diagnostic log for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-50042: B2B trace context initialization error**

**Cause:** An error occurred during trace context initialization.

**Action:** Review the diagnostic log for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-50050: Engine initialization error.**

**Cause:** An error occurred during engine initialization.

**Action:** Review the diagnostic log for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason

---

that this exception has been generated. If the problem persists, contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-50051: Failed to shut down the B2B engine.**

**Cause:** An error occurred during engine shut down.

**Action:** Review the diagnostic log for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. If the problem persists, contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-50052: Engine already initialized.**

**Cause:** Attempt made to initialize B2B engine which has been initialized already.

**Action:** Ensure that the engine is stopped before attempting to initialize

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Process

**B2B-50059: Error in starting B2B Server.**

**Cause:** An error has occurred while starting the server.

**Action:** Review the diagnostic log for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Process

**B2B-50060: Error in stopping B2B Server**

**Cause:** An error has occurred while stopping the server.

**Action:** Review the diagnostic log for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-50075: Error loading document or exchange plug-in.**

**Cause:** Error loading document or exchange plug-in.

---

**Action:** Review the diagnostic log for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-50076: Error loading packaging plug-in.**

**Cause:** Error loading packaging plug-in.

**Action:** Review the diagnostic log for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-50077: Cannot Initialize Transport.**

**Cause:** Cannot Initialize Transport.

**Action:** Review the diagnostic log for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-50078: Cannot shut down transport.**

**Cause:** Cannot shut down transport.

**Action:** Review the diagnostic log for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-50079: Transport error**

**Cause:** An error has occurred in transport layer

**Action:** Review the diagnostic log for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Process

**B2B-50080: Exchange protocol identification error.**

**Cause:** Failed to identify the exchange protocol of the message.

**Action:** Review the diagnostic log for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-50081: Duplicate exchange protocol message error**

**Cause:** Duplicate exchange protocol message generated by the trading partner.

**Action:** Report this error to the trading partner.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-50082: Duplicated Control Number error**

**Cause:** Message received with duplicate control number {0}.

**Action:** Report this error to the trading partner.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-50083: Document protocol identification error.**

**Cause:** Failed to identify the document protocol for the message.

**Action:** Review the diagnostic log for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-50084: No service found**

**Cause:** Requested service was not registered in system

**Action:** Check requested web service URL

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-50545: An agreement {0} has expired or is not in force as yet. The effective From/To dates are {1} - {2}.**

**Cause:** An agreement effective From/To dates are invalid.



---

**Action:** Change the agreement effective From/To dates.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-50546: Information given to identify an agreement is insufficient: FromTP {0}, ToTP {1}, document type {2}.**

**Cause:** Failed to identify the agreement

**Action:** Make sure From/To TP and document information is not Null.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-50547: Agreement not found for trading partners: FromTP {0}, ToTP {1} with document type {2}.**

**Cause:** Failed to identify the trading partner agreement from the given input values.

**Action:** Make sure there is an agreement configured for the From/To trading partner and document information that presents in the message.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-50548: Agreement {0} not in active state.**

**Cause:** Agreement was not in active state.

**Action:** Make sure the agreement is deployed and it is in Active state.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-50549: Cannot uniquely identify the trading partner. The trading partners {0} have the same set of identifications.**

**Cause:** The trading partners {0} have the same set of identifications

**Action:** Make sure the trading partners have unique identifications

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-50550: Cannot find the trading partner for the given identification type {0} and value {1}**

**Cause:** The trading partner was not exist for the given identification type and value.

**Action:** Create or update the trading partner with the given identification type and value.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**B2B-50701: The agreement {0} cannot be activated because a similar agreement {1} found in active state**

**Cause:** Similar agreement found in active state. There cannot be two agreements with the same trading partners, document type, version, and direction.

**Action:** Make inactive existing active agreement which has the same trading partners, document type, version, and direction.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-50801: No input value is specified. At least one input value is needed: From/To trading partner or Document or Action**

**Cause:** Missing input values

**Action:** Specify input values such as From/To trading partner or Document or Action

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-50901: Failed to find a business message with B2BMessageId {0}.**

**Cause:** Failed to find a business message with B2BMessageId.

**Action:** Review the UI report to verify that a message exists with B2BMessageId.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-50902: Failed to find a wire message with B2BMessageId {0}.**

**Cause:** Failed to find a wire message with B2BMessageId.

**Action:** Review the UI report to verify that a message exists with B2BMessageId.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-50903: Message {0} retry count is zero.**

**Cause:** The maximum number of message retries has been reached.

**Action:** Increase the maximum number of retries in delivery channel.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Process

**B2B-50904: ReferTo message not found.**

**Cause:** The message ID specified in the header RefToMessageID not found.

---

**Action:** It is possible that the original message was purged. Try resubmitting the original message.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-50906: Failed to retrieve value for the given XPATH.**

**Cause:** Error occurred while extracting XPATH value.

**Action:** Make sure XPATH in document definition is correct and applicable for the payload

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51000: General packaging Error**

**Cause:** Packaging details were incorrect.

**Action:** Correct the packaging details in delivery channel.

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Process

**B2B-51001: Packaging fail**

**Cause:** Packaging information were insufficient.

**Action:** Correct the packaging details in delivery channel.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51002: Unpacking fail**

**Cause:** Packaging headers were incorrect.

**Action:** Correct the packaging details in delivery channel.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51003: Encoding failed**

**Cause:** Encoding type was incorrect.

**Action:** Review the UI report for the exact error, which begins with the string 'ERROR:' This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

---

**B2B-51004: Decoding failed**

**Cause:** Decoding type was incorrect.

**Action:** Review the UI report for the exact error, which begins with the string 'ERROR:' This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-51005: Validating packaging metadata failed.**

**Cause:** Packaging metadata was insufficient.

**Action:** Verify packaging metadata to pack the message.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51006: Invalid input parameter**

**Cause:** Packaging input parameters were invalid.

**Action:** Verify the packaging parameters and packaging metadata.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51007: Missing packaging metadata information.**

**Cause:** Missing few packaging metadata.

**Action:** Verify the packaging metadata.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51008: Circular dependency in packaging metadata.**

**Cause:** Circular dependency found in packaging metadata.

**Action:** Review the UI report for the exact error, which begins with the string 'ERROR:' This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-51009: Missing one or more packaging elements in packaging metadata.**

**Cause:** Missing one or more packaging elements in packaging metadata.

**Action:** Verify packaging metadata has packaging elements.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**B2B-51010: Missing composite packaging element in packaging metadata.**

**Cause:** None of the composite packaging elements exist in the Multipart message.

**Action:** Make sure Multipart message has at least one composite packaging element.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51011: Invalid packaging metadata.**

**Cause:** Message has more than one simple part. Hence, failed to package the message.

**Action:** Verify MIME message has only one simple part.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51012: Missing list of message components.**

**Cause:** Missing list of message component in the message.

**Action:** Verify the message has list of component.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51013: Missing one or more message components in the list of message components.**

**Cause:** Protocol components did not have all the required components while packaging information.

**Action:** Verify the protocol components and set all the required components for packaging the information.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51014: Missing data for message component.**

**Cause:** Invalid data for message component.

**Action:** Verify message has component data.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51015: Missing security information.**

**Cause:** Invalid security information.

**Action:** Verify security information is exist in packaging.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51016: Missing signature information.**

**Cause:** Invalid digital signature information.

**Action:** Review the UI report for the exact error, which begins with the string 'ERROR:' This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-51017: Missing encryption information.**

**Cause:** Required envelope information did not exist.

**Action:** Verify the required envelope information available in packaging.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51018: Message is not digitally signed.**

**Cause:** Message was not digitally signed.

**Action:** Review the UI report for the exact error, which begins with the string 'ERROR:' This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-51019: Message is not encrypted.**

**Cause:** Message was not encrypted.

**Action:** Verify the message which has to be encrypted.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51020: Signature protocol is not supported.**

**Cause:** Signature protocol was not Secure Multipurpose Internet Mail Extensions (S/MIME).

**Action:** Use Secure Multipurpose Internet Mail Extensions (S/MIME) as a signature protocol.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**B2B-51021: Encryption protocol is not supported.**

**Cause:** Encryption protocol was not a Secure Multipurpose Internet Mail Extensions (S/MIME).

**Action:** Use Secure Multipurpose Internet Mail Extensions (S/MIME) as a encryption protocol.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51022: Digest algorithm does not match.**

**Cause:** Invalid digest algorithm.

**Action:** Verify digest algorithm.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51023: Required signature information are already set for message.**

**Cause:** Attempt made to set the signature information when it already has been set.

**Action:** Remove the existing signature information before attempting to set this new signature information.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51024: Required envelope information is already set for message.**

**Cause:** Attempt made to set envelope information when it has already been set.

**Action:** Remove the existing envelope information before attempting to set this new envelope information.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51025: Keystore resource location incorrect**

**Cause:** Incorrect keystore location specified.

**Action:** Specify correct keystore location.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51026: Encoding type is not supported**

**Cause:** Encoding type was not supported.

**Action:** Verify supported encoding type as any one of base64, quoted-printable, 7bit, 8bit, or binary.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51050: MIME Content-Types do not match.**

**Cause:** Mismatched MIME body part and MIME type.

**Action:** Verify the Content-Types in MIME body part.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51051: MIME Content-Type parameter lists do not match.**

**Cause:** While creating MIME body part, MIME Content-Type parameter lists mismatch.

**Action:** Verify the MIME Content-Type parameters list.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51052: Invalid MIME Content-Type header or information.**

**Cause:** Missing MIME Content-Type and value.

**Action:** Review the UI report for the exact error, which begins with the string 'ERROR:' This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-51053: Invalid MIME content disposition header or information.**

**Cause:** Missing MIME content disposition header value.

**Action:** Verify MIME header content disposition.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51054: Missing MIME Content-Type header information.**

**Cause:** MIME Content-Type information was not exist.

**Action:** Verify MIME Content-Type header exist.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51055: Missing information for message component.**

**Cause:** Information were not exist for message component.



---

**Action:** Verify the message component information.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51056: Missing or unable to read data from message.**

**Cause:** Failed to read data from message.

**Action:** Verify the message data.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51057: Invalid or corrupted message.**

**Cause:** Invalid message format.

**Action:** Verify the message format.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51075: Missing signer certificate.**

**Cause:** Signer certificate not found.

**Action:** Provide the certificate to sign the message.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51076: Missing encryption certificate.**

**Cause:** Encryption certificate not found.

**Action:** Provide the certificate to encrypt the message.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51077: Missing certificate chain.**

**Cause:** Invalid certificate chain was exist.

**Action:** Provide the proper certificate with certificate chain.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51078: Message has invalid digest information.**

**Cause:** Failed to digest message or message corrupted.

**Action:** Provide appropriate digest for message.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51079: S/MIME version is not supported.**

**Cause:** Unsupported S/MIME version.

**Action:** Verify the S/MIME version should be either 2.0 or 3.0.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51080: Signature algorithm {0} is not supported.**

**Cause:** Unsupported signature algorithm specified.

**Action:** Review the UI report for the exact error, which begins with the string 'ERROR:' This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-51081: Digest algorithm {0} is not supported.**

**Cause:** Unsupported digest algorithm specified.

**Action:** Review the UI report for the exact error, which begins with the string 'ERROR:' This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51082: Encryption algorithm {0} is not supported.**

**Cause:** Unsupported encryption algorithm specified.

**Action:** Review the UI report for the exact error, which begins with the string 'ERROR:' This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-51083: General failure creating S/MIME digital signature.**

**Cause:** A failure has occurred when creating the S/MIME digital signature.

**Action:** Verify that the keystore has the correct private key and certificate.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**B2B-51084: General failure verifying S/MIME digital signature.**

**Cause:** A general failure has occurred when attempting to verify the S/MIME digital signature.

**Action:** 1. Use correct certificate to verify the signature. 2. Message might have been corrupted. Check with the trading partner.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51085: General failure encrypting S/MIME message.**

**Cause:** A general failure has occurred when attempting to encrypt the S/MIME digital signature.

**Action:** Use valid trading partner certificate.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51086: General failure while decrypting S/MIME message.**

**Cause:** General failure while decrypting S/MIME message.

**Action:** 1. Use correct Key Pair to decrypt the message. 2. Message might have been corrupted. Check with the trading partner.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51087: Could not create digest data for S/MIME digital signature {0}.**

**Cause:** Creating digest data for S/MIME digital signature failed {0}.

**Action:** Use the supported algorithm as per the S/MIME standard or as per the exchange protocol.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51088: Creating S/MIME digital signature failed {0}.**

**Cause:** Failed to create S/MIME digital signature.

**Action:** Check the signing credentials.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51089: Unable to verify S/MIME digital signature.**

**Cause:** Verifying S/MIME digital signature failed {0}.

**Action:** Use correct certificate to verify the message.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51090: Unable to create S/MIME message recipient.**

**Cause:** Creating S/MIME message recipient list failed {0}.

**Action:** Check the recipient certificate.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51091: Unable to add a recipient to S/MIME message recipient list {0}.**

**Cause:** Adding recipient to S/MIME message recipient list failed {0}.

**Action:** Check the recipient certificate.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51092: Encrypting S/MIME message failed {0}.**

**Cause:** Failed to encrypt S/MIME message.

**Action:** Check the certificate used to encrypt the message.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51093: Decrypting S/MIME message failed {0}.**

**Cause:** Message encrypted using a wrong certificate.

**Action:** Check the key-pair used to decrypt the message or verify with the trading partner that the certificate used to encrypt the message is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51094: Processing signature information for S/MIME message failed.**

**Cause:** Failed to process signature information for S/MIME message.

**Action:** Request a re-send from the trading partner.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51095: Processing envelope information for S/MIME message failed.**

**Cause:** Failed to process envelope information for S/MIME message.

**Action:** Request a re-send from the trading partner.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**B2B-51096: Cannot include more than one signer in the S/MIME digital signature.**

**Cause:** More than one signer in the S/MIME digital signature was not supported.

**Action:** Ask the trading partner to send the message with the single signer.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51097: Found empty packaging IDs list during packaging plug-in initialization.**

**Cause:** An empty packaging IDs list is passed for packaging plug-in initialization.

**Action:** Make sure correct packaging is mentioned.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51098: Invalid Content-Type {0} in packaging metadata.**

**Cause:** Packaging metadata contains invalid Content-Type.

**Action:** Make sure correct packaging details are mentioned.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51099: An incorrect RosettaNet version has been found in the message.**

**Cause:** Not a RosettaNet 1.1 message.

**Action:** Verify the packaging version.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51105: Unsupported algorithm**

**Cause:** Algorithm used was not supported by the S/MIME or exchange protocol.

**Action:** Use correct algorithm as specified by the exchange protocol or S/MIME standard.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51107: Digest mismatch**

**Cause:** Document might have been corrupted during transport.

**Action:** Request a re-send from the trading partner.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**B2B-51108: Failed to digest the message.**

**Cause:** Failed to create the digest for the message.

**Action:** Check the payload or digest algorithm.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51112: An invalid CRL has been found in the incoming message.**

**Cause:** Invalid CRL.

**Action:** Check with the trading partner that CRL is correct and request a re-send from the trading partner.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51114: CRL missing issuer**

**Cause:** Issuer not found in CRL.

**Action:** Check with the trading partner that CRL issuer is correct and request a re-send from the trading partner.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51120: Invalid Content-Type**

**Cause:** Content-Type of the signed/encrypted message was not correct.

**Action:** Request a re-send from the partner or resend the message with correct Content-Type.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51121: Empty recipient list**

**Cause:** No recipient list was exist in the encrypted message.

**Action:** Check with the trading partner and request a re-send with recipient list.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51122: Certificate decode error**

**Cause:** Certificate was not correct.

**Action:** Check if the certificate is in correct format.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**B2B-51124: Failed to create certificate chain**

**Cause:** Unable to create certificate chain while generating the message.

**Action:** Check if the certificate used is a trusted certificate.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51125: No certificate to sign**

**Cause:** Certificate used to sign the message was not available in the keystore.

**Action:** Check if the certificate is available in the keystore.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51128: Certificate missing issuer**

**Cause:** The certificate that is being used was missing issuer information.

**Action:** Use a trusted certificate.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51143: Certificate expired**

**Cause:** The certificate has expired.

**Action:** 1. Make sure host and trading partner has selected the local time zone, 2. If the time zone is correct request the trading partner to generate a new certificate.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51145: Certificate is not valid yet.**

**Cause:** Certificate was not valid. Because the certificate creation date was later than current system date.

**Action:** 1. Make sure Host and trading partner has selected the local time zone 2. System current date is later than certificate creation date.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51147: Missing recipient information**

**Cause:** Missed recipient information.

**Action:** Ask the trading partner to check the recipient certificate added during encryption and request for a re-send.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**B2B-51150: Failed to verify certificate chain.**

**Cause:** Unable to verify the certificate chain while processing the message.

**Action:** Verify the certificates used and request a re-send.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51152: CRL verification failed**

**Cause:** CRL verification failed.

**Action:** CRL received not matching with the certificates in the keystore. Request the trading partner to send the correct CRL.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51153: Certificate revoked**

**Cause:** Certificate revoked.

**Action:** Request a re-send with the valid certificate from the trading partner.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51154: Certificate signature verification failed.**

**Cause:** Failed to verify the certificate signature.

**Action:** Request for the valid certificate from the trading partner.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51165: Digest algorithm missing.**

**Cause:** Message received with incorrect digest algorithm.

**Action:** Request a re-send from the trading partner.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51193: Failed to open keystore.**

**Cause:** Keystore file was not in correct format, incorrect location or incorrect password.

**Action:** Make sure the keystore is generated properly or the location or password is correct.

**Level:** 1



---

**Type:** ERROR

**Impact:** Process

**B2B-51195: Failed to get key pair from keystore**

**Cause:** Unable to retrieve key pair from the keystore.

**Action:** Verify that the keystore has valid key pair.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51197: LDAP error**

**Cause:** LDAP error

**Action:** Check the LDAP details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51198: LDAP connect failed.**

**Cause:** LDAP connect failed.

**Action:** Check the LDAP details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51199: LDAP bind failed.**

**Cause:** LDAP bind failed.

**Action:** Check the LDAP details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51200: LDAP search failed.**

**Cause:** LDAP search failed.

**Action:** Check the LDAP details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51201: LDAP entry missing attribute.**

**Cause:** LDAP entry missing attribute.

**Action:** Check the LDAP details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**B2B-51202: No certificate in the directory for this user**

**Cause:** Unable to retrieve the certificate for this user from the directory.

**Action:** Make sure that the certificate is available in the directory.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51203: Error compressing data.**

**Cause:** An error has occurred while compressing data.

**Action:** Check the payload.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51204: Error decompressing data.**

**Cause:** An error has occurred while compressing data.

**Action:** Check the payload received or request for re-send from the trading partner.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51500: Document exchange success.**

**Cause:**

**Action:**

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Process

**B2B-51501: Document exchange initialization failure.**

**Cause:** Failed to initialize the document specific guidelines.

**Action:** Verify the document specific initialization parameters.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51503: General create message error.**

**Cause:** Failed to create message components.

**Action:** Verify values for message creation components.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51504: General decode error.**

---

**Cause:** Failed to decode the message.  
**Action:** Verify the incoming message contents.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51505: General validation error.**

**Cause:** An unexpected error occurred during validation.  
**Action:** Verify the validity of the document against the document definition.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51506: Message digest validation error.**

**Cause:** Message digest obtained from the incoming message payload, did not match with the original message digest.  
**Action:** Verify the digest algorithm.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51507: Payload validation error.**

**Cause:** An error occurred during message payload processing in document plug-in.  
**Action:** Verify the message payload validity against the document definition.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51508: EDI group header validation error.**

**Cause:** An error occurred in EDI document group header processing.  
**Action:** Verify the EDI group header parameters of the message validity against the document definition.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51509: Create message error: component- {0}.**

**Cause:** Failed to create message components.  
**Action:** Verify all components of the message.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**B2B-51510: EDI batch message processing error.**

**Cause:** An error occurred during EDI document batch message processing.

**Action:** Verify the batch message payload validity against the document definition.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51511: EDI interchange header validation error.**

**Cause:** An error occurred in interchange header of EDI document during message payload processing.

**Action:** Verify the EDI Interchange header parameters of the message validity against the document definition

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51512: Message payload parameter validation error.**

**Cause:** Document parameters validation failed.

**Action:** Verify the parameters of the message against the document protocol parameters.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51550: Invalid usage code.**

**Cause:** Specified usage code was neither production nor test.

**Action:** Verify that the usage code is either production or test.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51551: Invalid timestamp.**

**Cause:** Timestamp was not in the correct format.

**Action:** Correct timestamp format is CCYYMMDDThhmmss.sssZ.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51552: Mismatch in the PIP binding ID.**

**Cause:** PIP binding ID in the initiating message did not match the PIP binding ID in the response message.

**Action:** Ensure that the PIP binding ID in the initiating message matches the PIP binding ID in the response message.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**B2B-51553: Mismatch in PIP code.**

**Cause:** PIP code in the initiating message did not match the PIP code in the response message.

**Action:** Ensure that PIP Code in the initiating message matches the PIP code in the response message.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51554: Mismatch PIP in instance ID.**

**Cause:** PIP instance ID in the initiating message did not match the PIP instance ID in the response message.

**Action:** Ensure that the PIP instance ID in the initiating message matches the PIP instance ID in the responding message.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51555: Mismatch in PIP version.**

**Cause:** PIP version in the initiating message did not match the PIP version in the response message.

**Action:** Ensure that PIP version in the initiating message matches the PIP version in the response message.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51556: Invalid response message.**

**Cause:** Message ID in the initiating message did not match the message ID in the RefTo field of the response message.

**Action:** Ensure that message ID in the initiating message matches the message ID in the RefTo field of the response message.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51557: PIP binding ID exceeds 255 characters.**

**Cause:** PIP binding ID cannot exceed 255 characters.

**Action:** Limit the total characters of PIP binding ID to 255.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**B2B-51558: Invalid value for secure transport required attribute.**

**Cause:** Secure transport was neither Yes nor No.

**Action:** Ensure that the secure transport has values Yes or No.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51559: Mismatch in manifest content-type.**

**Cause:** Content-type in the manifest did not match the content-type associated with the attachment.

**Action:** Ensure that the content-type in the manifest and attachment are the same.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51560: Mismatch in manifest content-ID.**

**Cause:** Content-ID in the manifest did not match the content-ID associated with the attachment.

**Action:** Ensure that the content-ID in the manifest matches the content-ID associated with the attachment.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51561: Mismatch in the service of the host and the trading partner.**

**Cause:** FromService field in the initiating message did not match the ToService field in the response message.

**Action:** Verify the FromService field of the host matches with ToService field of the trading partner.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51562: Mismatch in the service of the host and the trading partner.**

**Cause:** ToService field in the initiating message did not match the FromService field in the response message.

**Action:** Verify the ToService field of the host matches with FromService of the trading partner.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51563: Mismatch in the role of the host and the trading partner.**

**Cause:** FromRole field in the initiating message did not match the ToRole field in the response message.

---

**Action:** Verify the FromRole field of the host matches with ToRole field of the trading partner.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51564: Mismatch in the role of the host and the trading partner.**

**Cause:** ToRole field in the initiating message did not match the FromRole field in the response message.

**Action:** Verify the ToRole field of the host matches with FromRole field of the trading partner.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51565: An unexpected error occurred while initializing the XML parser.**

**Cause:** Failed to initialize XML parser.

**Action:** Ensure that the XML parser initialized properly.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51566: Parse stream error**

**Cause:** An unexpected error occurred while parsing the input stream.

**Action:** Verify the message components of incoming message.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51567: Invalid Content-Type**

**Cause:** Sub-type of the Content-Type in the HTTP header was neither Multipart/related nor Multipart/signed.

**Action:** Check for the Content-Type in the HTTP header.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51568: encoding error**

**Cause:** An unexpected error occurred while encoding data.

**Action:** Verify encoded type is base64.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51569: decoding error**

---

**Cause:** An unexpected error occurred while decoding data.

**Action:** Verify the decode type is base64.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51570: Attachment error**

**Cause:** An unexpected error occurred while creating an attachment as component data.

**Action:** Verify the well-form of the XML content for attachment.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51571: Attachment error**

**Cause:** An unexpected error occurred while forming an attachment as XML data.

**Action:** Verify that the XML format of the data for the attachment is well-formed XML. Also verify the encoding and type attributes of attachment.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51572: Error reading input stream.**

**Cause:** An unexpected error occurred while reading the input stream.

**Action:** Ensure the input value is nonempty.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51573: Unexpected payload file naming, default format is <FromPartyName>\_<MessageID>.<Extension> e.g. Sun\_1234235.dat**

**Cause:** Payload file name was not as per expected naming convention.

**Action:** Expect default format is <FromPartyName>\_<MessageID>.<Extension> e.g. Sun\_1234235.dat.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51574: Error loading XEngine libraries. XEngine is most likely not installed.**

**Cause:** XEngine was not installed.

**Action:** Make sure XEngine is installed.

**Level:** 1

**Type:** ERROR

**Impact:** Process



---

**B2B-51575: Incorrect document exchange version.**

**Cause:** Document exchange version mismatch.

**Action:** Verify the document exchange header value.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51576: Incorrect document exchange.**

**Cause:** Document exchange mismatch.

**Action:** Verify the document exchange name.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51577: Document exchange validation error**

**Cause:** Document exchange validation failed.

**Action:** Verify the document exchange header values

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51703: Failed to unpack the message.**

**Cause:** An unexpected error occurred during the unpackaging of the RosettaNet business message.

**Action:** Verify the message headers.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51705: Unable to read the preamble.**

**Cause:** Failed to read preamble.

**Action:** Ensure the correctness of preamble content.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51707: Unable to read the delivery header.**

**Cause:** Failed to read delivery header.

**Action:** Ensure the correctness of the delivery header content.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51709: Unable to read the service header.**

---

**Cause:** Failed to read the service header.

**Action:** Ensure the correctness of the service header.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51715: Failed to unpack the message - reading the service content.**

**Cause:** Failed to read the service content.

**Action:** Ensure the correctness of the service content.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51915: No type is specified in party ID.**

**Cause:** No type was specified in party ID.

**Action:** Specify a party ID type.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51916: Reference ID in the manifest does not match payload ID.**

**Cause:** Reference ID in the manifest did not match payload ID.

**Action:** Make sure that reference ID in the manifest matches the payload ID.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51917: Content-Type set for ebMS message is incorrect.**

**Cause:** Content-Type set for ebMS message was incorrect.

**Action:** Set a valid Content-Type for the ebMS message.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51918: This version of ebMS is not supported. Only version 2.0 is supported.**

**Cause:** This version of ebMS was not supported. Only version 2.0 is supported.

**Action:** Make sure to exchange messages for the supported version.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51919: Hub mode not supported.**

**Cause:** As Hub mode was not supported, the actor value is incorrect.

**Action:** Specify the actor as urn:oasis:names:tc:ebXML-msg:actor:toPartyMSH

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51921: SOAP message has defective packaging.**

**Cause:** Defect identified in packaging of the SOAP message.

**Action:** Make sure that the message is a valid SOAP message.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51922: If the service type is not specified then the service must be a URI.**

**Cause:** If the service type was not specified then the service must be a URI.

**Action:** Specify a service URI if the service type is not specified.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51923: Value {0} for the element {1} is not recognized.**

**Cause:** Failed to recognise value for the element.

**Action:** Specify a correct value for the element.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51924: Message failed the security check.**

**Cause:** Message failed the security check.

**Action:** Verify that the message has been encrypted and signed with the correct credentials.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51925: Feature {0} is not supported.**

**Cause:** Selected feature is not supported.

**Action:** Make sure the feature is currently supported.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51926: SyncReply element must exist in the message.**

**Cause:** SyncReply element must be present in the message.

**Action:** Add a SyncReply element in the message.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**B2B-51927: Time to live has expired for the message.**

**Cause:** Time to live has expired for the message.

**Action:** Make sure to send a message with a valid time to live value.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51928: Message header validation failed. The received {0} does not match with the configured {1}.**

**Cause:** Message header did not have the element.

**Action:** Make sure to add element to the message header.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51929: No payload is found for the reference ID {0}.**

**Cause:** No payload attached for the reference ID.

**Action:** Make sure to have a payload for the reference ID, or remove this reference ID from the message.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51930: Message with ID {0} is a duplicate message.**

**Cause:** Duplicate message identified with same ID.

**Action:** Make sure to send a message with a unique message ID, a message which is not duplicated.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51931: Error found in decrypting or verifying the message.**

**Cause:** Error in decryption or on message verification.

**Action:** Make sure that the message is being decrypted and verified with the correct credentials.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51932: Multiple parts with same Content-ID or Content-Location header.**

**Cause:** Multiple parts with same Content-ID or Content-Location header.

**Action:** Use different Content-ID or Content-Location header values for different MIME parts of the message.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51933: Referenced Content-ID or Content-Location header not found.**

**Cause:** Referenced Content-ID or Content-Location header not found.

**Action:** Make sure that the referenced Content-ID or Content-Location header values are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51934: Unhandled attachment object {0} found.**

**Cause:** Unhandled attachment object found.

**Action:** Make use of correct attachment type for attaching objects.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51935: Error in resolving the content ID reference.**

**Cause:** Failed to resolve the content ID reference.

**Action:** Make sure that the content ID reference is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-51936: Signed acknowledgement requested, but not configured in delivery channel.**

**Cause:** Signed acknowledgement requested, but not configured in delivery channel.

**Action:** Make sure that the sign acknowledgement is configured in delivery channel.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52250: Error decoding incoming message at MLLP exchange.**

**Cause:** Message received consists of more than one part or component.

**Action:** Check the payload to make sure it has only one part/component.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52251: Error identifying remote trading partner at MLLP exchange with MLLP ID {0}.**

---

**Cause:** MLLP ID received from in the message header did not exist.

**Action:** Make sure that the MLLP ID of the remote trading partner is configured as in the trading partner identification section or the anonymous trading partner is configured.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52252: Only one trading partner in the system can have hosted=true.**

**Cause:** More than one trading partner has hosted=true.

**Action:** Make sure only one trading partner in the system has hosted=true.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52253: Trading partner {0} must have trading partner name as one of the identification.**

**Cause:** Trading partner must have trading partner name as one of the identification.

**Action:** Make sure trading partner has an identification with value as name of trading partner.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52254: Delivery channel {0} must have exchange protocol, if listening=false.**

**Cause:** Delivery channel did not have exchange protocol.

**Action:** Make sure delivery channel has exchange protocol.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52255: Certificate alias not specified in the secure delivery channel {0}.**

**Cause:** Security was enabled in delivery channel, but no certificate alias specified.

**Action:** Make sure certificate alias specified in the delivery channel.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52256: In delivery channel {0}, Transport protocol {1} is not supported by exchange protocol {2}.**

**Cause:** Specified transport protocol was not supported by exchange protocol.

**Action:** Choose transport protocol which is supported by exchange protocol.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**B2B-52257: In delivery channel {0}, algorithm {1} is not supported for exchange protocol {2}.**

**Cause:** Specified algorithm was not supported by exchange protocol.

**Action:** Choose algorithm which is supported by exchange protocol.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52258: In delivery channel {0}, exchange protocol parameter {1} is not supported for exchange protocol {2}.**

**Cause:** Selected exchangeProtocolParameter was not part of the specified exchange protocol.

**Action:** Select specified exchangeProtocol and re-save again in UI.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52259: In delivery channel {1}, exchange protocol {0} has to have acknowledge mode as ASYNC or NONE.**

**Cause:** RNIF exchange protocol did not support SYNC acknowledge mode.

**Action:** Verify RNIF exchange protocol has acknowledge mode as ASYNC or NONE.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52260: effectiveToDate {0} in agreement {1} must be a date in the future.**

**Cause:** Date specified in effectiveToDate was not a future date.

**Action:** Ensure that the effectiveToDate in the agreement is a date in the future.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52261: The effectiveFromDate {0} should be less than effectiveToDate {1} in agreement {2}.**

**Cause:** The effectiveFromDate should be less than effectiveToDate.

**Action:** Make sure the effectiveFromDate is less than effectiveToDate.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52262: Agreement {0} does not have a host and trading partner.**

**Cause:** Agreement did not have a host and trading partner.

---

**Action:** Make sure agreement has a host and trading partner.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52263: One of the participants must be a host in an agreement {0}.**

**Cause:** None of the participants was host in agreement.

**Action:** Make sure a participant in agreement is host.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52264: Document type name {0} and document protocol version {1} used in agreement {2} are not in sync with the corresponding definition in trading partner {3}.**

**Cause:** Document type name and document protocol version used in agreement were not in sync with the corresponding definition in trading partner.

**Action:** Make sure agreement has document type name and document type version as given in trading partner.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52265: DUNS identification value {0} must be 9 digit.**

**Cause:** DUNS identification was not have value in 9 digit.

**Action:** Verify DUNS identification has value in 9 digit.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52266: Identification type {0} and value {1} must be unique in the trading partner.**

**Cause:** Identification type and value occurred more than once in the trading partner.

**Action:** Make sure type and value of identification unique in the trading partner.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52267: Only one exchange protocol can have default=true.**

**Cause:** More than one exchange protocol has default=true.

**Action:** Make sure only one exchange protocol has default=true.

**Level:** 1

**Type:** ERROR



---

**Impact:** Process

**B2B-52268: Only one document protocol can have default=true.**

**Cause:** More than one document protocol has default=true.

**Action:** Make sure only one document protocol has default=true.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52269: Participant {0} cannot have more than one identification of the same type {1}.**

**Cause:** Participant has more than one identification of the same type.

**Action:** Make sure participant is not referring to more than one identification of same type.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52270: Participant {0} identification reference {1} is not part of same trading partner identification.**

**Cause:** Participant refer to some other trading partner identification.

**Action:** Make sure identification referred in participant is part of same trading partner.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52271: Participant {0} delivery channel reference {1} is not part of same trading partner.**

**Cause:** Participant delivery channel reference was not part of either same trading partner or host.

**Action:** Make sure delivery channel referred in participant is part of trading partner.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52272: Participant {0} document definition {1} is not part of same trading partner.**

**Cause:** Participant document definition was not part of same trading partner.

**Action:** Make sure trading partner has specified document definition.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52273: Participant {0} identification type {1} and value {2} are not synchronous with trading partner identification.**

---

**Cause:** Participant identification type and value were not sync with trading partner identification.

**Action:** Make sure the value and type given in identification reference in participant is synchronous with trading partner identification.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52274: Participant {0} can have only one exchange identifier.**

**Cause:** Participant has more than one exchange identification.

**Action:** Make sure only one exchange identification found in participant.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52275: Type of the parameter {0} must match with the default value {1}.**

**Cause:** Parameter type and default value type mismatched.

**Action:** Check the type and value of parameter are same type.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52276: Type of the parameter {0} must match with the value.**

**Cause:** Parameter type and given value mismatched.

**Action:** Check the type and value of parameter are same type.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52277: Only Custom document protocol can set custom attribute equal to true.**

**Cause:** Other than custom document protocol has custom attribute set to true.

**Action:** Make sure only custom document protocol has this attribute set to true.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52278: Document protocol {0} must have ID {1} starts with doc\_**

**Cause:** Document protocol has ID which did not start with doc\_

**Action:** Make sure document protocol has ID starts with doc\_

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52279: Document protocol {0} reference must be doc\_id.xml**

---

**Cause:** Document protocol reference was not in the form of doc\_id.xml  
**Action:** Make sure document protocol reference is in the form of doc\_id.xml

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52280: Trading partner {0} must have at least one exchange identification.**

**Cause:** None of the exchange identification found in trading partner.

**Action:** Add at least one exchange identification in trading partner.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52281: Trading partner {0} must have ID {1} starts with tp\_**

**Cause:** Trading partner has ID which did not start with tp\_

**Action:** Make sure trading partner has ID which starts with tp\_

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52282: Trading partner {0} reference must be tp\_id.xml**

**Cause:** Trading partner reference was not in the form of tp\_id.xml

**Action:** Make sure trading partner has reference in the form of tp\_id.xml

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52283: In delivery channel {0}, certificate alias {1} not found in the keystore.**

**Cause:** Given certificate alias did not exist in the keystore.

**Action:** Verify certificate alias is present in the keystore.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52284: Delivery channel {0} which has transport protocol {1} cannot be a listening channel.**

**Cause:** Selected transport protocol was not capable of listening

**Action:** Select listening transport to create listening delivery channel

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52285: Internal delivery channel {0} must use generic exchange.**

**Cause:** Internal delivery channel has other than generic exchange protocol.

---

**Action:** Make sure internal delivery channel uses generic exchange.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52286: HTTP transport protocol must have a URL.**

**Cause:** HTTP transport protocol did not have a URL.

**Action:** Make sure HTTP transport protocol has a URL.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52287: Agreement {0} must have ID {1} starts with tpa\_**

**Cause:** Agreement has ID which did not start with tpa\_

**Action:** Make sure agreement has ID which starts with tpa\_

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52288: Agreement {0} reference must be tpa\_id.xml**

**Cause:** Agreement reference was not in the form of tpa\_id.xml

**Action:** Make sure agreement has reference which is in the form of tpa\_id.xml

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52289: Agreement {0} has document definition with mismatching initiator flag.**

**Cause:** Agreement has document definition with mismatching initiator flag in trading partner.

**Action:** Make sure document definition is supported to send or receive by trading partner.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52290: Agreement {0} must have exactly one supported document type.**

**Cause:** Agreement has not exactly one supported document type.

**Action:** Make sure agreement has only one supported document type.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52291: Duplicate agreement {0} found with same combination of trading partners {1}, {2}, and document type {3} and document protocol version {4}.**

---

**Cause:** More than one agreement has same combination of trading partners, document type and version.

**Action:** Make sure only one agreement has same combination of trading partners, document type and version.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52292: In agreement {0}, trading partner {1} must have a delivery channel.**

**Cause:** The trading partner did not have delivery channel to send out bound message.

**Action:** Make sure in a agreement, the trading partner has a delivery channel to send out bound message.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52293: In agreement {0}, the host {1} can refer to only the internal delivery channel.**

**Cause:** Host refers to other than internal delivery channel.

**Action:** Make sure host is not referring to other than internal delivery channel.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52294: In agreement {0}, participant {1} cannot have more than one delivery channel.**

**Cause:** Participant has more than one delivery channel.

**Action:** Make sure only one delivery channel exist for participant.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52295: At least one name identification type present in system.**

**Cause:** Name identification type did not present in system.

**Action:** Check at least one name identification type present in system.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52296: Exchange identification {0} must have a value.**

**Cause:** Exchange identification did not have a value.

**Action:** Make sure all exchange identification has a value.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**B2B-52297: Packaging protocol reference {0} must point to packaging protocol element.**

**Cause:** Packaging protocol reference refer to other than packaging protocol element.

**Action:** Verify packaging protocol reference refers to packaging protocol element.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52298: Transport URL {0} already used in system.**

**Cause:** More than once same endpoint used in system.

**Action:** Make sure same endpoint not attached with different delivery channel in system.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52299: Participant {0} must have at least one exchange identification.**

**Cause:** None of the exchange identification referred in participant.

**Action:** Make sure participant has at least one exchange identification.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52300: Duplicate ID {0} found in node {1} and node {2}.**

**Cause:** Duplicate unique ID found in two different nodes.

**Action:** Target system has element with the same , change ID of importing node.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52301: MDSReference {0} is not referring to the trading partner.**

**Cause:** MDSReference did not refer to the trading partner.

**Action:** Make sure given reference is pointing to the trading partner.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52302: MDSReference {0} is not referring to an agreement.**

**Cause:** MDSReference did not refer to an agreement.

**Action:** Make sure given reference is pointing to an agreement.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**B2B-52303: Compressed file expected to import.**

**Cause:** Given file was not compressed using ZIP format.

**Action:** Verify given file is in compressed in ZIP format.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52304: Agreement {0} cannot have listening channels.**

**Cause:** Listening channels referred in agreement.

**Action:** Verify agreement is not referring to any listening channels.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52305: In agreement {0}, trading partner {1} cannot have internal delivery channel.**

**Cause:** Trading partner has internal delivery channel(s).

**Action:** Make sure none of the trading partners has internal delivery channel.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52306: Internal delivery channel {0} must not use HTTP transport.**

**Cause:** Internal delivery channel has HTTP as transport.

**Action:** Make sure internal delivery channel is not using HTTP transport.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52307: Listening delivery channel {0} must have a polling interval value.**

**Cause:** Listening channel did not have value for polling interval.

**Action:** Make sure listening channel has polling interval value.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52308: Listening delivery channel {0} with transport {1} does not have user name and password.**

**Cause:** Listening delivery channel did not have user name and password in transport.

**Action:** Make sure listening delivery channel has user name and password in transport.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52309: Validation error: see the diagnostic log for more details.**

**Cause:** Unknown exception found in validation engine.

**Action:** Review the diagnostic log for the exact error, which begins with the string 'ERROR:'. This error line, along with the preceding lines, will indicate the reason that this exception has been generated. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-52310: The XML {0} is not well-formed.**

**Cause:** Given XML content was not well-formed.

**Action:** Check XML content is well-formed and valid based on XSD/DTD constraints.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52311: New document protocol {0} found in source reference {1}.**

**Cause:** New document protocol name found in import source.

**Action:** Check name of the document protocol is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52312: Document protocol {0} must have ID {1} starts with doc\_**

**Cause:** Document protocol has ID which did not start with doc\_

**Action:** Make sure document protocol has ID which starts with doc\_

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52313: Document protocol {0} reference must be doc\_id.xml**

**Cause:** Document protocol reference was not in the form of doc\_id.xml

**Action:** Make sure document protocol has reference in the form of doc\_id.xml

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52314: Repository host name {0} and source Host name {1} are different.**

**Cause:** Different host name found in repository and source.



---

**Action:** Make host name as unique in source and target system, while doing import.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52315: Duplicate identification type {1} and value {2} found in source trading partner {0}.**

**Cause:** More than one identification type found in source trading partner(s) for a same value and type.

**Action:** Make sure combination of identification type and value unique in the trading partner.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52316: Pre-import transfer operation failed.**

**Cause:** Pre-import validation(s) failed while importing.

**Action:** Check validation error messages found below this message and correct source files accordingly.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52317: Duplicate identification type {1} and value {2} found in source agreement {0}.**

**Cause:** More than one identification type found in source agreement(s) for a same value and type.

**Action:** Make sure combination of identification type and value unique in agreement.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52318: MDSReference {0} does not exist in Repository.**

**Cause:** Specified reference was not available in repository.

**Action:** Make sure specified reference is available in repository.

**Level:** 1

**Type:** WARNING

**Impact:** Process

**B2B-52319: Transfer error: see log for more details.**

**Cause:** Unknown exception identified in transfer.

**Action:** Check the diagnostic log. Contact Oracle Support Services if the problem persists.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-52320: In agreement {0}, functional acknowledge can be enabled only when translate=true.**

**Cause:** Agreement has functional acknowledge with translate flag set to inactive.

**Action:** Functional acknowledge can be active only when translate is active.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52321: No metadata found to import.**

**Cause:** No metadata identified in recommended package.

**Action:** Check given import file has metadata in correct package.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52322: Mandatory field {0} is missing in {1}.**

**Cause:** Metadata might be imported without all mandatory fields.

**Action:** Import metadata with all mandatory fields or save again the business object which has error, using UI.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52323: Out-bound agreement {0} has to have only one exchange identifier type - {1}, in both participants**

**Cause:** Out-bound agreement has more than one exchange identifier, or has different type of exchange identifier which is not suitable to exchange protocol.

**Action:** Make sure given exchange identifier is supported by chosen exchange protocol in delivery channel.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52324: Listening Delivery channel {0} has duplicate endpoint {1}**

**Cause:** Already a delivery channel has same endpoint, hence new delivery channel cannot be activated with same endpoint.

**Action:** Make sure all listening channel endpoints are unique.

**Level:** 1

**Type:** ERROR

**Impact:** Backup and Recovery

**B2B-52325: Error in the SOA Composite {0}**

---

**Cause:** See the base error message in the SOA Composite.

**Action:** Correct the error in the Fabric Composite.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52326: Transport protocol with HTTPs URL has to have valid keystore location and password in host**

**Cause:** Valid keystore location and password was not specified in host.

**Action:** Check with administrator, whether valid keystore location specified in host.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52327: Channel {0} with transport {1} should have Queue name along with either datasource or the combination of SID, port number, user name, host name and password.**

**Cause:** AQ channel does not have required parameter values to connect to AQ queue.

**Action:** Provide AQ Queue name along with either datasource or the combination of SID, port number, user name, host name and password.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52328: Channel {0} with transport {1} should have either password or the combination of private key file and pass phrase.**

**Cause:** SFTP channel does not have required parameter values to connect to SFTP server.

**Action:** Provide either password or the combination of private key file and pass phrase.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**B2B-52329: Web Service outbound flow invocation error.**

**Cause:** An abnormal condition occurred during outbound flow invocation.

**Action:** Review the SOAP Fault for the exact error and correct the same. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-52330: Error invoking translation Web Service.**

---

**Cause:** An abnormal condition occurred during translation Web Service invocation.

**Action:** Review the SOAP Fault for the exact error and correct the same. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**B2B-52331: Translated content is not available**

**Cause:** B2B metadata or XEngine configuration was invalid.

**Action:** Review the SOAP Fault for the exact error and correct the same. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

---

## BAM-00001 to BAM-07041

**BAM-00001: Specified DataTable or DataColumn is missing.**

**Cause:** The column mapping was missing, and the missing schema action was Error.

**Action:** Change the missing schema action, or add column mapping.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-00002: Cannot add object to data table mapping collection: invalid type.**

**Cause:** The object being added to the data table mapping collection was of the incorrect type.

**Action:** Verify schema.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-00003: invalid xsd:datetime: {0}**

**Cause:** The date is invalid for the XML Schema datetime type.

**Action:** Provide a valid date.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-00004: Column value overflow: {0} value {1} is not between {2} and {3}**

**Cause:** The specified value is beyond the range of the column data type.

**Action:** Provide a valid value or change the column data type.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-00005: invalid connection string provided**

**Cause:** One or more parameters in connection string are invalid.

**Action:** Ensure parameters in connection string are valid.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-00006: IO exception: The network adapter could not establish the connection.**

**Cause:** In the connection string an improper host name has been given.

**Action:** Ensure that the parameters in the connection string are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-00007: invalid Oracle URL**

**Cause:** In connection string, improper parameter has been given.

**Action:** Ensure parameters in connection string are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-00008: invalid Oracle driver name**

**Cause:** In the driver definition an invalid driver name has been provided.

**Action:** Ensure that the driver name is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-00200: A custom parameter with the ID {0} does not exist.**

**Cause:** A custom parameter with the specified ID was not found while importing or processing a report.

**Action:** If the custom parameter no longer exists, then ignore this error; otherwise, verify that the ID is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-00201: Cannot create calculated field {0} from modifier.**

**Cause:** Failed to retrieve the calculated field because it has not been added to the modifier.

**Action:** Check the reason why the calculated field was not added to the modifier.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-00202: Cannot create decimal field {0} with scale {1}. Maximum scale is {2}.**

**Cause:** The specified scale for a Decimal column exceeded the maximum scale supported by the Oracle BAM Server.

---

**Action:** Limit the scale to 38 or less on Oracle.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-00203: Data object {0} contains no column named {1}.**

**Cause:** The specified column name was not found in the specified data object.

**Action:** Verify the column name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-00204: There is no data object named {0}.**

**Cause:** The specified data object was not found in the Oracle BAM Server.

**Action:** Verify the data object name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-00205: Cannot create folder {0}. A data object with that name already exists.**

**Cause:** A data object with the name specified for the folder already existed.

**Action:** Use a different folder name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-00206: GetUIXml call failed for external data source type.**

**Cause:** Failed to retrieve UI XML for an external data source type.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**BAM-00208: No external data source type exists with ID {0}.**

**Cause:** Failed to find the external data source type with the specified ID.

**Action:** Verify the external data source type ID.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-00210: Internal Error: Middleware.Persistence.ExternalDataSourceType: No current external data source type has been loaded.**

**Cause:** Load by ID failed, and there was no current external data source type.

**Action:** Check why load by ID failed.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-00211: invalid security filter ID**

**Cause:** Failed to load the security filter with the specified ID.

**Action:** Verify the security filter ID.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-00212: unknown user: {0}**

**Cause:** Failed to retrieve a user by the specified name.

**Action:** Verify the user name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-00213: unknown user**

**Cause:** There was no current user loaded in User object.

**Action:** Find out why the system failed to load the user.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-00214: The aggregates {0} and {1} are of different lengths.**

**Cause:** The two aggregates had different lengths.

**Action:** Make sure the two aggregates have the same length.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-00215: invalid sort in modifier: {0}**

**Cause:** The sort is invalid for the named modifier. The user chose a combination of fields and conditions to which a sort cannot be applied.

**Action:** Provide a valid sort.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-00216: invalid group in modifier: {0}**

**Cause:** The group is invalid for the named modifier.

**Action:** Provide a valid group.

**Level:** 1



---

**Type:** ERROR

**Impact:** Data

**BAM-00217: invalid XML modifier: {0}**

**Cause:** The XML modifier is invalid.

**Action:** Provide a valid XML modifier.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-00218: invalid RecordField in modifier: {0}**

**Cause:** The record field for the named modifier is invalid.

**Action:** Provide a valid record field.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-00219: No data set has been specified in the modifier**

**Cause:** No data set has been specified in the modifier.

**Action:** Specify a data set for the modifier.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-00220: The modifier does not have a valid fieldRef element: {0}**

**Cause:** The modifier does not have a valid fieldRef element.

**Action:** Specify a valid fieldRef element for the modifier.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-00221: unknown operator in modifier**

**Cause:** An unknown operator was encountered in the modifier.

**Action:** Verify the operators and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-00223: Service {0} is unavailable.**

**Cause:** The specified Oracle BAM Service is currently unavailable.

**Action:** Ensure that the specified Oracle BAM Service is started.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**BAM-00300: Conflicting conversion methods encountered for version {0,number,#}. Methods {1} and {2}.**

**Cause:** Two conflicting conversion methods were found for the version.

**Action:** Fix the methods.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**BAM-00301: The conversion from version {0} to version {1} failed.**

**Cause:** Failed to convert from the source version to the target version.

**Action:** Check the log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**BAM-00302: Invocation of conversion method {0} failed.**

**Cause:** Failed to invoke the specified conversion method.

**Action:** Check the log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**BAM-00303: The user already exists.**

**Cause:** This administrative user already exists.

**Action:** Rename this user and rerun the upgrade process.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**BAM-00304: Conversion Warnings:**

**Cause:** Warnings encountered during execution of upgrade.

**Action:** Review the warnings in the upgrade log file.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**BAM-00400: Authentication failed.**

**Cause:** The user cannot be authenticated.

**Action:** Provide the correct credential for the given user, or add the user to the Oracle BAM Server account.

**Level:** 1

**Type:** ERROR

**Impact:** Security

---

**BAM-00401: Unable to authenticate request. Request scheme {0} is not supported.**

**Cause:** Non-HTTP requests were received by Oracle BAM Web Application.

**Action:** Only HTTP and HTTPS requests are supported.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**BAM-00402: Unable to authenticate request. No request or invalid request specified.**

**Cause:** The servlet request was null.

**Action:** Provide a valid servlet request.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**BAM-00403: Unauthenticated request received.**

**Cause:** No user credentials were found.

**Action:** Provide valid user credentials.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**BAM-00404: Authentication failed. User is marked inactive.**

**Cause:** This user was no longer defined in the configured identity store and has been marked inactive.

**Action:** Use the Oracle BAM Administrator application to permanently delete any inactive users so that these user names can be reused.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**BAM-00501: Unrecoverable exception for destination {0}.**

**Cause:** Unrecoverable exception occurred.

**Action:** Examine other error messages that may have led to this message, and take appropriate action or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-00510: Resource acquisition for destination {0} timed out after {1} milliseconds.**

**Cause:** Resources, such as a connection, for the specified destination could not be acquired during open (initialization) or recovery in a timely manner.

**Action:** Ensure that the specified destination is available.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**BAM-00511: Resource acquisition for destination {0} was interrupted.**

**Cause:** Resources, such as a connection, for the specified destination could not be acquired during open (initialization) or recovery due to an interrupt, likely caused by server shutdown, application stop, undeployment, or redeployment.

**Action:** Examine other error messages that may have led to this message, and take appropriate action or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-00513: Resource acquisition for destination {0} failed.**

**Cause:** Resources, such as a connection, for the specified destination could not be acquired during open (initialization) or recovery.

**Action:** Examine other error messages that may have led to this message, and take appropriate action or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-00520: Resource recovery for destination {0} timed out after {1} milliseconds.**

**Cause:** Resources, such as a connection, for the specified destination were lost and could not be reacquired after repeated attempts in a timely manner.

**Action:** Ensure that the specified destination is available.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-00521: Resource recovery for destination {0} was interrupted.**

**Cause:** Resources, such as a connection, for the specified destination were lost and could not be reacquired after repeated attempts due to an interrupt, likely caused by server shutdown, application stop, undeployment, or redeployment.

**Action:** Examine other error messages that may have led to this message, and take appropriate action or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-00523: Resource recovery for destination {0} failed.**

**Cause:** Resources, such as a connection, for the specified destination were lost and could not be recovered.

**Action:** Examine other error messages that may have led to this message, and take appropriate action or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**BAM-00530: Resource open for destination {0} timed out after {1} milliseconds.**

**Cause:** Resources, such as a connection, for the specified destination could not be opened (initialized) in a timely manner.

**Action:** Ensure that the specified destination is available.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-00531: Resource open for destination {0} was interrupted.**

**Cause:** Resources, such as a connection, for the specified destination could not be opened (initialized) due to an interrupt, likely caused by server shutdown, application stop, undeployment, or redeployment.

**Action:** Examine other error messages that may have led to this message, and take appropriate action or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-00533: Resource open for destination {0} failed.**

**Cause:** Resources, such as a connection, for the specified destination could not be opened (initialized).

**Action:** Examine other error messages that may have led to this message, and take appropriate action or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-00543: Resources for destination {0} were not closed.**

**Cause:** Resources, such as a connection, for the specified destination could not be closed.

**Action:** Examine other error messages that may have led to this message, and take appropriate action or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-00550: Resource start operation for destination {0} timed out after {1} milliseconds.**

**Cause:** Resources, such as a connection, for the specified destination could not be started in a timely manner.

**Action:** Ensure that the specified destination is available.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**BAM-00551: Resource start operation for destination {0} was interrupted.**

**Cause:** Resources, such as a connection, for the specified destination could not be started due to an interrupt, likely caused by server shutdown, application stop, undeployment, or redeployment.

**Action:** Examine other error messages that may have led to this message, and take appropriate action or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-00553: Resources start operation for destination {0} failed.**

**Cause:** Resources, such as a connection, for the specified destination could not be started.

**Action:** Examine other error messages that may have led to this message, and take appropriate action or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-00560: JMS destination {0} not found.**

**Cause:** The specified JMS destination was not found.

**Action:** Ensure that the specified JMS destination is defined.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-00561: Only Topics are allowed to have durable subscriptions.**

**Cause:** The specified JMS Destination was not found be Topic.

**Action:** Ensure that the specified JMS Destination is a Topic.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-00562: Authentication Failure**

**Cause:** There was authentication failure against the JMS server.

**Action:** Ensure that you have specified the right credentials.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-01000: The Oracle BAM Active Data Cache Server failed to start. {0}.**

**Cause:** The Oracle BAM Active Data Cache Server failed to start.

**Action:** Check the log for more details.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**BAM-01001: The Oracle BAM Active Data Cache Server stopped, but with a failure: {0}.**

**Cause:** An exception was thrown when the Oracle BAM Active Data Cache Server stopped.

**Action:** Check the log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-01200: The Administrator role is required by the system and cannot be deleted.**

**Cause:** An attempt was made to delete the Administrator role.

**Action:** The Administrator role cannot be deleted.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**BAM-01201: The root folder cannot be deleted.**

**Cause:** An attempt was made to delete the root folder.

**Action:** Do not attempt to delete the root folder.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**BAM-01202: User cannot be deleted.**

**Cause:** An attempt was made by the user to delete his own account.

**Action:** A user cannot delete his own account.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**BAM-01203: insufficient permission to get the ACL for this object**

**Cause:** An attempt was made to retrieve the access control list for this object.

**Action:** Only the object owner or Administrator can retrieve the access control list for this object.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**BAM-01204: The account used to run the Oracle BAM Active Data Cache does not have permission to retrieve the list of groups for this user.**

**Cause:** The account used to run the Oracle BAM Active Data Cache did not have permission to retrieve the list of groups for the specified user.

---

**Action:** Contact the network administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**BAM-01205: Only an administrator can impersonate another user.**

**Cause:** An attempt was made to impersonate another user.

**Action:** Log in as an administrator to impersonate another user.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**BAM-01206: Permission to set the ACL for this object is not available.**

**Cause:** An attempt was made to set the access control list for this object.

**Action:** Only the object owner or administrator can set the access control list for this object.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**BAM-01207: The value of a timestamp column cannot be set explicitly.**

**Cause:** An attempt was made to set the value of a read-only timestamp column.

**Action:** The value of a read-only timestamp column cannot be set.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01208: GetChangeList() called on non-active viewset.**

**Cause:** An attempt was made to get a change list on a non-active viewset.

**Action:** Provide an active viewset.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-01209: The column {0} is read-only.**

**Cause:** An attempt was made to set the value of a read-only column.

**Action:** The value of a read-only column cannot be set.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01210: The column {0} cannot be null.**

**Cause:** The value of column is null.

**Action:** Set the value of column to be not null.



---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01211: The error, {0}, has occurred involving dataset {1} in the Active Data Cache internal data access system.**

**Cause:** An internal exception has occurred in the Active Data Cache.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**BAM-01212: The Active Data Cache data files are read-only. Startup cannot continue.**

**Cause:** The Active Data Cache data files are read-only.

**Action:** Change the access rights of Active Data Cache data files.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-01213: The Active Data Cache data files path {0} is invalid.**

**Cause:** The Active Data Cache data files path is invalid.

**Action:** Verify that the directory exists. If the directory is on a network, make sure that the network is available.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**BAM-01214: Active Data Cache data object already exists.**

**Cause:** The data object already exists in the Active Data Cache.

**Action:** Choose another data object name or delete the old data object.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01215: Active Data Cache data object could not be created.**

**Cause:** Create Table SQL statement failed.

**Action:** Check the log file for more details and report the error.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01216: The data object could not be deleted from the Active Data Cache.**

**Cause:** Drop Table SQL statement failed.

**Action:** Check the log file for more details and report the error.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01217: Active Data Cache data object could not be loaded.**

**Cause:** getDataSetSchema() failed.

**Action:** Check the log file for more details and report the error.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01218: The data object {0} does not exist.**

**Cause:** The data object does not exist.

**Action:** Create the data object first or take appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01219: Active Data Cache data object row could not be deleted.**

**Cause:** Delete row command failed.

**Action:** Check the log file for more details and report the error.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01220: Active Data Cache data object row could not be inserted.**

**Cause:** There was a failure trying to insert a row.

**Action:** Check the log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01221: The row in the data object could not be updated.**

**Cause:** There was a failure trying to update a row.

**Action:** Check the log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01222: Active Data Cache data objects list could not be loaded.**

**Cause:** There was a failure to load a list of Active Data Cache data objects.

**Action:** Check the log for more details.

**Level:** 1

**Type:** ERROR

---

**Impact:** Data

**BAM-01223: Only one column of type autoincrement is permitted in a single data object.**

**Cause:** The data object already contains an autoincrement column. The limit is one autoincrement column per data object.

**Action:** Change the column type to integer, or remove the existing autoincrement column.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01224: The data object cannot be deleted or edited when it is in use by an open view or alert.**

**Cause:** Failed to grab the lock for updating.

**Action:** Stop the attempted operation, or try the operation after freeing the view or alert.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01225: A timeout trying to obtain a lock on the data object {0} expired.**

**Cause:** Have timed out while waiting to obtain a lock on the data object.

**Action:** Try the attempted operation later or after the interfering tasks are finished.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01226: The decimal value does not fit in this column.**

**Cause:** This decimal value does not fit in this column.

**Action:** Check the accuracy of provided number.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01227: A data object with a Lookup into the current data object is in use.**

**Cause:** A data object depending on the current data object is in use.

**Action:** Stop the attempted operation (for example, destroy).

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01228: The folder already contains an object named {0}.**

**Cause:** Another object with the same name exists in the folder.

**Action:** Assign a unique name to the object.

---

**Level: 1**

**Type: ERROR**

**Impact: Data**

**BAM-01229: A group can be added to a role only once.**

**Cause:** A group cannot be added to a role more than once.

**Action:** Stop the operation.

**Level: 1**

**Type: ERROR**

**Impact: Data**

**BAM-01230: duplicate identifier**

**Cause:** The given identifier is already in use.

**Action:** Change the identifier.

**Level: 1**

**Type: ERROR**

**Impact: Data**

**BAM-01231: A user can be added to a role only once.**

**Cause:** A user cannot be added to a role more than once.

**Action:** Stop the operation.

**Level: 1**

**Type: ERROR**

**Impact: Data**

**BAM-01232: Exception was previously caught during transaction processing for this viewset.**

**Cause:** An exception occurred during the processing of active data.

**Action:** Check the log for more details.

**Level: 1**

**Type: ERROR**

**Impact: Process**

**BAM-01233: The folder {0} is already defined.**

**Cause:** The caller is attempting to create a folder with an existing name.

**Action:** Stop the operation.

**Level: 1**

**Type: ERROR**

**Impact: Data**

**BAM-01234: Folder {0} cannot be deleted.**

**Cause:** The folder cannot be deleted because it is not empty.

**Action:** Delete the items in the folder before attempting to delete the folder.

**Level: 1**

---

**Type:** ERROR

**Impact:** Data

**BAM-01235: Folder {0} not found.**

**Cause:** The folder was not found by its name.

**Action:** Check the spelling of folder name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01236: The Active Data Cache Satellite does not support this function.**

**Cause:** A clause to the monitor list was added; however, its function was not recognized.

**Action:** Provide the correct name for the viewset change.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01237: The Active Data Cache cannot group on column {0}.**

**Cause:** The Active Data Cache cannot group on a column containing null values.

**Action:** Provide non-null column values.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01238: invalid arguments**

**Cause:** The supplied parameters are invalid.

**Action:** Provide valid parameters.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-01239: The Active Data Cache has been secured using a security key.**

**Cause:** The Active Data Cache has been secured using a security key.

**Action:** The user must provide the correct security key in order to access it. To provide a security key, add a value for BAMSecureServerKey to the application configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**BAM-01240: Active Data Cache invalid data type**

**Cause:** The data is not the correct type for this column.

**Action:** Make sure that the data being inserted or updated is of the correct type for this column.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01241: invalid expression**

**Cause:** An invalid aggregate operation has been specified for the aggregate expression.

**Action:** Choose one of the following operations: COUNT, COUNTDISTINCT, AVG, SUM, MAX, MIN, FirstInGroup, or LastInGroup.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-01242: Invalid calculated column: {0}**

**Cause:** The expression specified for the calculated column is invalid.

**Action:** Correct the expression.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01243: The viewset count cannot be obtained if it was opened using the bRetrieveSchemaOnly option.**

**Cause:** The viewset was opened with the bRetrieveSchemaOnly option.

**Action:** Open the viewset and set the bRetrieveSchemaOnly option to false.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01244: invalid identifier**

**Cause:** The identifier contains an invalid character.

**Action:** The identifier must start with an alphanumeric character or underscore (\_), and it must contain only underscore and alphanumeric characters.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01245: Active Data Cache invalid max length**

**Cause:** Column type is decimal and its maximum size specification exceeds an accepted maximum system value.

**Action:** Change the column value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-01246: The scale must be greater than or equal to zero.**

---

**Cause:** The column is of type decimal and its scale is smaller than zero.

**Action:** Change the scale value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-01247: An invalid transaction type sequence exists in the transaction map.**

**Cause:** An invalid transaction type sequence was encountered in the transaction map, such as Insert or Update followed by Insert, or Delete followed by Insert or Update.

**Action:** Resequence the transactions.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01248: A group-level calculation exists in an operation that is invalid, such as sorting, filtering, or grouping.**

**Cause:** An aggregate expression is specified in a group-level calculation.

**Action:** Remove the aggregate expression.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01249: The maximum number of users automatically added to the Active Data Cache has been reached.**

**Cause:** The maximum number of users automatically added to the Active Data Cache has been reached.

**Action:** Add new users with the Oracle BAM Administrator application.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01250: The column {0} must have a default value or allow null values.**

**Cause:** The datetime column does not have a default or is not nullable.

**Action:** Provide a default for the datetime column or make it nullable.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01251: When using OpenViewsets, all of the modifiers must be on the same data object.**

**Cause:** Some modifiers are not applied on the same data object.

**Action:** Change the modifiers in the opened viewset.

**Level:** 1

---

**Type:** ERROR

**Impact:** Data

**BAM-01252: Multiple parent aggregate rows found.**

**Cause:** Multiple matching rows were found in Group Table.

**Action:** Trace the history to find out why multiple aggregate rows have been inserted.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01253: object name not found: {0}**

**Cause:** The object name was not found.

**Action:** Check the spelling of the name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01254: No record fields specified in the modifier on {0}.**

**Cause:** No record fields specified in the modifier.

**Action:** Provide record fields in the modifier.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01255: Path name {0} does not start with a slash (/).**

**Cause:** The path name started without a slash.

**Action:** The path name should start with a slash (/).

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01256: Operation not allowed.**

**Cause:** An invalid operation was performed.

**Action:** Avoid performing the invalid operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01257: Insufficient permission to perform the requested action.**

**Cause:** The user performed an action without permission.

**Action:** Grant the permission to the user or group.

**Level:** 1

**Type:** ERROR



---

**Impact:** Security

**BAM-01258: The user does not have the required privileges to perform the requested action.**

**Cause:** Privilege was required to rename a role in Oracle BAM server.

**Action:** Log in as an Administrator user.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**BAM-01259: Only objects of type {0} can be added to this folder.**

**Cause:** The object inserted to a folder is not a folder and it does not match the parent folder's type restriction.

**Action:** Either remove the type restriction or choose the right type name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01260: The Active Data Cache schema version {1,number,#} does not match the expected version {0,number,#}.**

**Cause:** At startup, the Data Store Server version did not match the ADC schema version.

**Action:** Check the versions of the Active Data Cache schema and Oracle BAM Server used, and make sure that they are compatible.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**BAM-01261: Cannot connect to the Oracle BAM Server.**

**Cause:** The system was unable to connect to the Oracle BAM Server.

**Action:** Contact the system administrator if the error persists.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-01262: Active Data Cache server exception in {0}.**

**Cause:** Failed to connect to Active Data Cache server locally.

**Action:** Check system configurations and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-01263: The Oracle BAM Server has restarted.**

**Cause:** The Oracle BAM Server was restarted.

**Action:** None

---

**Level:** 1

**Type:** WARNING

**Impact:** Process

**BAM-01264: Sorting required on TopN with ties.**

**Cause:** The viewset does not have the required sorting on the query.

**Action:** Specify sorting on the query.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01265: An error ({0}) has occurred in the Active Data Cache storage system.**

**Cause:** An error occurred in the Active Data Cache storage system.

**Action:** Check the log to see more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-01266: System object not found.**

**Cause:** No system object could be found with the given ID.

**Action:** Check the provided ID.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01267: Active Data Cache system type not found ({0}).**

**Cause:** No system type could be found with the given ID.

**Action:** Check the provided ID.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01268: A transaction is already in progress.**

**Cause:** An attempt was made to begin a transaction a second time without a commit or roll back.

**Action:** Commit or roll back the previous transaction first.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01269: invalid Active Data Cache transaction ID: {0}**

**Cause:** The transaction with the specified ID does not exist.

**Action:** Check the provided transaction ID.

**Level:** 1

---

**Type:** ERROR

**Impact:** Data

**BAM-01270: The Active Data Cache transaction with ID {0} is in use and cannot be committed or rolled back.**

**Cause:** The specified transaction is in use. There are open DataReaders in the transaction.

**Action:** All DataReaders created in this transaction must be closed prior to a commit or rollback operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01271: No transaction is in progress.**

**Cause:** An attempt was made to call commit or rollback without a call to begin transaction.

**Action:** Begin a transaction first.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01272: The user in the current thread is not authenticated.**

**Cause:** The user in the current thread was not authenticated.

**Action:** The user should be authenticated first.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**BAM-01273: Active Data Cache unique constraint violation**

**Cause:** A row cannot be inserted because a similar row has already been inserted.

**Action:** Delete the previous row or discard the new row.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01274: The field ID {0} is not recognized.**

**Cause:** No column could be found in the given data set with the given ID.

**Action:** Check the field ID.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01275: The field {0} is not recognized.**

**Cause:** An operand in an aggregate expression is an instance of Field ID, but it is not a recognized column ID.

**Action:** Check the field ID.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01276: Active Data Cache unknown internal event**

**Cause:** An unrecognized change occurred in a viewset.

**Action:** The change should be one of the following: Insert, Update, or Delete.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-01277: Active Data Cache unknown type data column**

**Cause:** Unknown Java class found.

**Action:** A valid native type should be one of the following: String, Integer, BigDecimal, DateTime, Byte, Boolean, Short, Double, Long, or DBNull.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01278: unsupported data type in result schema: {0}**

**Cause:** Incompatible data types of two operands are involved in a math operation.

**Action:** Check the data types and provide the appropriate data.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01279: unsupported expression: {0}**

**Cause:** An invalid aggregate operation was found.

**Action:** Provide a valid aggregate operation: COUNT, SUM, AVG, MIN, MAX, FirstInGroup, LastInGroup, STDDEV, RANGE, QUOTA, NOOP, PERCENTOFTOTAL, or COUNTDISTINCT.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01280: User not found.**

**Cause:** The given user name was not found in the Oracle BAM Server account.

**Action:** Provide a valid user in the Oracle BAM Server account.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**BAM-01281: Values {0} not found in table {1}.**

**Cause:** The specified key values in the group table were not found.

---

**Action:** Check if specified key values are missing from the group table.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01282: This viewset not found: {0}.**

**Cause:** The viewset was closed.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01283: The calculated column {0} contains a circular reference.**

**Cause:** A circular reference was found in the calculated column definition.

**Action:** When defining a calculated column there can be no circular references.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01284: Key column IDs cannot be changed within a transaction.**

**Cause:** Key column IDs were changed within a transaction.

**Action:** Avoid changing key column IDs within a transaction.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01285: Upsert value column IDs cannot be changed within a transaction.**

**Cause:** A list of columns to be updated was changed within a transaction.

**Action:** Avoid changing the list of columns to be updated during a single transaction.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01286: The super user cannot be deleted.**

**Cause:** The deleted user was the super user.

**Action:** The super user cannot be deleted.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**BAM-01287: The data object with ID {0} is external, and its contents cannot be edited.**

**Cause:** An attempt was made to update a data object derived from an external data source.

---

**Action:** Data objects created using external data sources cannot be updated.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01288: The data object {0} is external and cannot have lookup columns.**

**Cause:** An external data object definition contained lookup columns.

**Action:** Do not include lookup columns in external data object definitions.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01289: The external data source for this data object has been deleted.**

**Cause:** The external data source for this data object was not found.

**Action:** Provide the correct connection information.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01290: The external data source type {0} does not exist.**

**Cause:** The specified external data source type was not found.

**Action:** Provide a valid external data source type.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01291: The index {0} already exists.**

**Cause:** This index was found in the data object.

**Action:** Do not use an index twice within a data object.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01292: The column {0} cannot be removed because it is indexed.**

**Cause:** The column {0} was not removed because it is indexed.

**Action:** Remove the index before attempting to remove the column.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01293: The layout of the column {0} cannot be changed because it is indexed.**

**Cause:** The layout of the column {0} was not changed because it is indexed.

**Action:** Remove the index before attempting to change the layout of the column.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01294: The column {0} cannot be indexed because it is a calculated column.**

**Cause:** The column used in the index is a calculated column.

**Action:** Do not use a calculated column in an index.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01295: The column {0} cannot be indexed because it is a lookup.**

**Cause:** The column used in the index is a lookup column.

**Action:** Do not use a lookup column in an index.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01296: The specified set of columns is already indexed.**

**Cause:** The specified column list was already indexed.

**Action:** Do not attempt to index a set of indexed columns.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01297: The index {0} does not exist.**

**Cause:** The specified index was not found in the edit or remove operations.

**Action:** Verify that the provided index ID is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01298: An invalid ConnectionString is specified in Active Data Cache configuration. Parameter {0} is invalid.**

**Cause:** An invalid ConnectionString was specified in Active Data Cache configuration.

**Action:** Correct the ConnectionString specification.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BAM-01299: One of the String columns being used as a filter, group by, or sort in this view is too large.**

**Cause:** This column is too long to use in a sort, filter, or group operation.

**Action:** Do not use this column in a sort, filter, or group operation.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01300: The column {0} is a calculation and cannot be used as a lookup key.**

**Cause:** A calculated column was used as a lookup key.

**Action:** Do not use a calculated column as a lookup key.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01301: A lookup on the data object {0} cannot be created because it contains lookups.**

**Cause:** A lookup was created to a data object that contains lookups.

**Action:** A lookup cannot be created on a data object that contains lookups.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01302: The primary key list and the foreign key list are of different lengths, or one of the data types does not match.**

**Cause:** One of the data types on the matching key lists did not match.

**Action:** Match the data types of the matching keys.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01303: The data object {0} cannot have lookups because it is already being used as a dimension.**

**Cause:** The data object was already used as a dimension, and creating lookups in it was not permitted.

**Action:** Do not create lookups in data objects being used as dimensions.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01304: The foreign key column {0} does not exist.**

**Cause:** The foreign key column specified did not exist.

**Action:** Verify the column name or create the missing column.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01305: The primary key column {0} does not exist.**

**Cause:** The primary key column specified did not exist.



---

**Action:** Verify the column name or create the missing column.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01306: The column {0} is a lookup and cannot be used as a lookup key.**

**Cause:** A lookup column was used as a lookup key.

**Action:** Do not use lookup columns as lookup keys.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01307: The user must specify at least one column for the foreign and primary keys.**

**Cause:** No columns were specified for the foreign and primary keys.

**Action:** Specify at least one column for the foreign and primary keys.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01308: Lookups on calculated columns are not supported.**

**Cause:** Columns to be looked up were calculated columns.

**Action:** Do not attempt lookups on calculated columns.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01309: A negative or zero grouped time bucket cannot be created.**

**Cause:** A negative or zero grouped time bucket size was specified.

**Action:** Specify a positive grouped time bucket size.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01310: Time buckets with a non-time-based function cannot be created.**

**Cause:** A non-time-based function was specified for a time bucket.

**Action:** Specify one of the time-based functions: YEAR, HOUR, MINUTE, SECOND, WEEK, or MONTH.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01311: {0} is not divisible by {1}.**

**Cause:** The time bucket dimension was not divisible by bucket size.

---

**Action:** Change either the time bucket dimension or bucket size.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-01313: Unable to obtain URL for resource "{0}."**

**Cause:** Could not find the resource with the given name.

**Action:** Verify the resource name, or make sure that the resource exists at the given path name.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**BAM-01314: Unable to obtain path for resource "{0}."**

**Cause:** Could not determine the appropriate classpath entry for the given class name using the specified class loader.

**Action:** Verify the resource name, or make sure that the resource exists at given path name.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**BAM-01315: Evaluator has not been initialized.**

**Cause:** Evaluator was not successfully initialized.

**Action:** Find out why the static block of Evaluator failed to perform static initialization.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-01316: Evaluator initialization failed.**

**Cause:** Evaluator was not successfully initialized.

**Action:** Find out why the static block of Evaluator failed to perform static initialization.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-01317: Compilation for class {0} failed with error {1}.**

**Cause:** The compilation for a Java file failed.

**Action:** Check the syntax of the provided Java file or the version of the compiler used.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**BAM-01318: Expression evaluation failed.**

**Cause:** Failed to evaluate the specified method of the class represented by this Evaluator with the given arguments.

**Action:** Check the log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-01319: Unable to obtain class loader.**

**Cause:** Failed to get Evaluator's class loader.

**Action:** Check whether or not this class was loaded by the bootstrap class loader.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**BAM-01320: Cannot add an auto-incrementing field to a data object that contains data.**

**Cause:** The data object contains data, so a mandatory non-null column cannot be added.

**Action:** Clear the data from the data object before adding the auto-incrementing field.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01321: Cannot add a timestamp field to a data object that contains data.**

**Cause:** The data object contains data, so a mandatory non-null column cannot be added.

**Action:** Clear the data from the data object before adding the timestamp field.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01322: Calculated field does not have a name.**

**Cause:** Calculated field does not have a name.

**Action:** Provide a name for the calculated field.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-01323: This functionality is not supported.**

**Cause:** This functionality is not supported.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-01324: Unable to establish Oracle BAM administrator account.**

**Cause:** The Oracle BAM Active Data Cache failed to establish the Oracle BAM administrator account.

**Action:** Confirm that the Oracle BAM administrator account is properly defined in the configured identity store.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-01325: Cannot delete a data object that is a lookup source for another data object.**

**Cause:** Data object is lookup source for another data object.

**Action:** Delete dependent data objects before deleting lookup source data object.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01326: Aggregates are not allowed in this Filter condition.**

**Cause:** Aggregates are not allowed in this Filter condition.

**Action:** Change the Filter condition specified for the report/alert to remove aggregates.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-01328: The field being added already exists in Data Object "{0}".**

**Cause:** The field being added already exists in the Data Object.

**Action:** Check the Data Object schema, and if necessary, drop the existing field and then add it again.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01329: The storage engine factory failed to start.**

**Cause:** The Oracle BAM storage engine factory failed to start. The storage engine factory is needed to establish communication with the database.

**Action:** Check the log for more details on the cause of the failure.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01330: The default storage engine has not been instantiated.**

---

**Cause:** An attempt was made to use the default Oracle BAM storage engine, however, it has not been successfully instantiated.

**Action:** Check the log for more details on the cause of the failure to instantiate the default storage engine.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01331: Unable to obtain database metadata for configured data source.**

**Cause:** Oracle BAM failed to obtain database metadata for the configured data source. The database metadata is needed to establish communication with the configured database.

**Action:** Check the log for more details on the cause of the failure.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01332: The configured data source specifies an unsupported database: {0}.**

**Cause:** The data source configuration for Oracle BAM specifies a database that is not currently supported.

**Action:** Check the Oracle BAM documentation for details on supported databases.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01333: Unable to instantiate a storage engine for the configured data source.**

**Cause:** Oracle BAM was unable to instantiate a storage engine for the configured data source. The storage engine is needed to establish communication with the database.

**Action:** Check the log for more details on the cause of the failure.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01334: Failed to find data source: {0}.**

**Cause:** Oracle BAM failed to find the specified data source.

**Action:** Check that the data source is properly configured in the application server and that the correct data source name is being used.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01500: No value specified for key column {0}.**

**Cause:** A row was updated/upserted without key column values.

**Action:** Provide key column values in the update/upsert operation.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01501: No key columns specified for update request.**

**Cause:** A row was updated/upserted, but none of the columns were specified as keys.

**Action:** Specify some columns as keys in the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01502: No columns to be updated were specified for upsert request.**

**Cause:** The list of columns to be changed were null in an upsert operation.

**Action:** Specify a list of columns that should be changed if the upsert evaluates to an update instead of an insert.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01503: No value specified for update column {0}.**

**Cause:** A row was upserted with a missing update column value.

**Action:** Provide key column values for all update columns specified in an upsert operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01600: An aggregate expression is not allowed.**

**Cause:** An aggregate expression was specified in a calculated column definition.

**Action:** Avoid specifying an aggregate expression in a calculated column.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01601: Argument {1} in function {0} must be a Boolean value.**

**Cause:** A non-Boolean operand was found in an IF function expression.

**Action:** Change the operand type to Boolean.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-01602: Argument {1} in function {0} must be a datetime type value.**

**Cause:** Non-datetime operands were specified for a datetime-related function expression.

---

**Action:** Provide the datetime type of operands in this expression.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-01603: Argument {1} in function {0} must be an integer.**

**Cause:** Integer type operands were expected in the function expression, but other types of operands were found.

**Action:** Provide integer type operands in the function expression.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-01604: Argument {1} in function {0} must be numeric.**

**Cause:** Numeric type operands were expected in the function expression, but other types of operands were found.

**Action:** Provide numeric type operands in the function expression.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-01605: Argument {1} in function {0} must be a string.**

**Cause:** String type operands were expected in the function expression, but other types of operands were found.

**Action:** Provide string type operands in the function expression.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-01606: Cannot divide by zero.**

**Cause:** Dividing by zero was attempted.

**Action:** Avoid dividing by zero.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01607: The MOD operator can only be used with integers.**

**Cause:** Non-integer operands were used in a MOD operation.

**Action:** Provide operands of type integer for the MOD operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01608: invalid aggregate operand**

**Cause:** Non-numeric operands were found in AVG or SUM aggregates.

---

**Action:** Avoid using non-numeric operands in these aggregates.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01609: The function {0} requires {1} arguments.**

**Cause:** An invalid number of arguments were found in the aggregate definition.

**Action:** Provide the correct number of arguments in the aggregate definition.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-01610: invalid filter expression**

**Cause:** Invalid operands were found in the filter expression.

**Action:** Provide the correct operands.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01611: Math expression contains a non-numeric operand.**

**Cause:** Non-numeric operands were found in math expressions (for example, ADD, SUB, and so on).

**Action:** Provide numeric operands in math expressions.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01612: Return values differ in type.**

**Cause:** The return values differed in type.

**Action:** Provide values of the same type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-01613: unknown expression type**

**Cause:** An unknown expression type was found.

**Action:** Specify one of the valid expression types: MathExpression, FunctionExpression, CaseExpression, and so on.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-01614: The function {0} requires argument values of same data type.**

**Cause:** The argument values differed in data type.



---

**Action:** Provide argument values of the same data type

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-01700: Active Data Cache exception: {0}**

**Cause:** The Active Data Cache Servlet failed in doGet().

**Action:** Check the log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-01701: Value {0} specified for parameter {1} is unknown.**

**Cause:** An invalid parameter, call, was found for doGet() in the ADC Servlet.

**Action:** The value must be one of the following: ping or config.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-01702: Invalid request specified. Parameter {0} is missing.**

**Cause:** No call parameter was found for doGet() in the ADC Servlet.

**Action:** Provide a call parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-01800: ping failure**

**Cause:** Ping failed.

**Action:** See the console output for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-01801: Parameter {0} is not recognized.**

**Cause:** An invalid parameter was found.

**Action:** Check the parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01802: Type {0} is not recognized.**

**Cause:** An invalid type parameter was found.

**Action:** The type must be one of the following: network, storage, transaction, activeviewset, or staticviewset.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-01803: Parameter Dataobject requires an argument.**

**Cause:** An invalid value was found for the Dataobject parameter.

**Action:** Provide a valid parameter value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-01804: Parameter domain requires an argument.**

**Cause:** An invalid value was found for the domain parameter.

**Action:** Provide a valid parameter value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-01805: Parameter timeout requires an argument.**

**Cause:** An invalid value was found for the timeout parameter.

**Action:** Provide a valid parameter value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-01806: Parameter type requires an argument.**

**Cause:** An invalid value was found for the type parameter.

**Action:** Provide a valid parameter value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-01807: Timeout exceeded.**

**Cause:** The Active Data Cache server failed to respond within a specified time interval.

**Action:** Check the status of the Active Data Cache server.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-02000: The report contains prompts or parameters.**

**Cause:** PARAMETER was found in the filter value when the filter expression was built.

**Action:** Avoid using a parameter in the filter value.

---

**Level: 1**

**Type: ERROR**

**Impact: Data**

**BAM-02001: invalid expression**

**Cause:** An invalid expression was found.

**Action:** Check the syntax of the XML payload.

**Level: 1**

**Type: ERROR**

**Impact: Data**

**BAM-02002: unrecognized constant expression: {0}**

**Cause:** Failed to get constant expression from the given string.

**Action:** Correct the syntax of the constant expression.

**Level: 1**

**Type: ERROR**

**Impact: Data**

**BAM-02200: Version to convert to is earlier than the version to convert from.**

**Cause:** Version to convert to was earlier than the version to convert from.

**Action:** Verify the version numbers.

**Level: 1**

**Type: ERROR**

**Impact: Upgrade**

**BAM-02201: Target version specified for conversion is unsupported.**

**Cause:** Version to convert to was invalid.

**Action:** Verify the version number.

**Level: 1**

**Type: ERROR**

**Impact: Upgrade**

**BAM-02202: Source version specified for conversion is unsupported.**

**Cause:** Version to convert from was invalid.

**Action:** Verify the version number.

**Level: 1**

**Type: ERROR**

**Impact: Upgrade**

**BAM-02300: Event engine cannot find matching external action entry.**

**Cause:** A null pointer exception has been thrown.

**Action:** Verify that an external action entry was correctly configured.

**Level: 1**

**Type: ERROR**

---

**Impact:** Data

**BAM-02301: At least one recipient is required, but none were found.**

**Cause:** There were no recipients specified on either send-to list or Cc: list.

**Action:** Provide at least one recipient.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02302: invalid rule: malformed action**

**Cause:** Failed to append the action clauses.

**Action:** Check the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02303: invalid rule: malformed condition**

**Cause:** Failed to retrieve the content of the expected XML element.

**Action:** Check the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02304: invalid rule: malformed action constraint**

**Cause:** Failed to load the constraint clause.

**Action:** Check the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02305: invalid rule: malformed escalation clause**

**Cause:** Failed to parse or process the escalation clause.

**Action:** Check the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02306: invalid rule: malformed event**

**Cause:** Failed to parse the event clause.

**Action:** Check the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02307: invalid rule: malformed using clause**

---

**Cause:** Failed to parse the import clause.

**Action:** Check the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02308: Event Engine must run with an account that has the Oracle BAM Administrator role.**

**Cause:** An attempt was made to run the Event Engine with an account that did not have the Oracle BAM Administrator role.

**Action:** Grant the user sufficient privileges before retrying this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**BAM-02309: Unable to load rule {0}. Verify that the rule is based on the event when this rule is launched.**

**Cause:** The rule manager failed to retrieve the rule with the specified ID.

**Action:** Verify the alert name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02310: Event Engine failure. Rule failed to fire.**

**Cause:** A rule failed to fire by either its ID or name.

**Action:** Check the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-02311: Event Engine failure. Cannot deliver e-mail.**

**Cause:** The Event Engine failed to send e-mail.

**Action:** Check the Event Engine log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-02312: Event rule identifier duplicated.**

**Cause:** The specified event rule identifier already existed in the Event Engine.

**Action:** Change the event rule identifier.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**BAM-02313: Event rule not found.**

**Cause:** Failed to retrieve a clause function using the specified event rule ID.

**Action:** Verify the correct event rule ID.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02314: The specified rule is not based on the event when this rule is launched.**

**Cause:** The specified rule cannot be fired because it is not based on the event when this rule is launched.

**Action:** Build the rule to be a manual type.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02315: Event satellite could not load clause.**

**Cause:** Failed to add a clause to a monitor list.

**Action:** Check the log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02316: Event satellite does not support this function.**

**Cause:** An unknown function type to Time satellite was found.

**Action:** The function must be one of the following: At, In, or AtEvery.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02317: Event satellite not found.**

**Cause:** An unknown event satellite was found.

**Action:** The event satellite must be one of the following: time, date, viewset, or manual.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02318: Event satellite indicated an unexpected action.**

**Cause:** An invalid action was found.

**Action:** The action must be one of the following: Add, Delete, or Modify.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**BAM-02319: Unable to connect to the Oracle BAM Event Engine.**

**Cause:** Failed to fire rule.

**Action:** Contact the system administrator if the error persists.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-02400: The All value and a match cannot be specified at the same time.**

**Cause:** Both All and a match were specified.

**Action:** Specify only one of them.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-02401: The All value and a name cannot be specified at the same time.**

**Cause:** Both All and a name were specified.

**Action:** Specify only one of them.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-02402: The All value and a regular expression cannot be specified at the same time.**

**Cause:** Both All and a regular expression were specified.

**Action:** Specify only one of them.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-02403: premature end of command file**

**Cause:** The end of command file was found prematurely.

**Action:** Check the syntax of the command file.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02404: Specified file is not a valid ICommand command file.**

**Cause:** A file with invalid contents was found.

**Action:** Check the syntax of the command file.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**BAM-02405: Extra arguments present with CmdFile.**

---

**Cause:** Extra arguments were present with CmdFile.

**Action:** Remove the extra arguments.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02406: Either Cmd or CmdFile argument must be present.**

**Cause:** Neither Cmd nor CmdFile was present.

**Action:** Provide one of them.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-02407: The Cmd and CmdFile arguments cannot be present in the same command.**

**Cause:** Both Cmd and CmdFile were found in the command.

**Action:** Provide only one of them.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-02408: ICommand authentication failure. Unable to connect as user {0}.**

**Cause:** Failed to create a Context object using the specified credentials.

**Action:** Verify the credentials.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**BAM-02409: There is no data object named {0}.**

**Cause:** The specified data object was not found.

**Action:** Verify the data object name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02410: There is no distribution list named {0}.**

**Cause:** The specified distribution list was not found.

**Action:** Verify the correct distribution list name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02411: Too many {0} parameters.**

**Cause:** A parameter was specified more than once.



---

**Action:** Remove the duplicate parameters.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-02412: There is no external data source named {0}.**

**Cause:** The specified external data source was not found.

**Action:** Verify the correct external data source name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02413: There is no external data source type named {0}.**

**Cause:** The specified external data source type was not found.

**Action:** Verify the correct external data source type name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02414: There is no enterprise message source named {0}.**

**Cause:** The specified enterprise message source was not found.

**Action:** Verify the correct enterprise message source name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02415: There is no enterprise message source type named {0}.**

**Cause:** The specified enterprise message source type was not found.

**Action:** Verify the correct enterprise message source type name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02416: There is no folder named {0}.**

**Cause:** The specified folder was not found.

**Action:** Verify the correct folder name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02417: The Inline parameter cannot be set to 1 if the File parameter is also specified.**

**Cause:** The Inline parameter was set to 1, and the File parameter was also specified in the command arguments.

---

**Action:** Provide only one of them.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-02418: The Inline parameter can only be set to 1 from within a command file.**

**Cause:** The Inline parameter was used from the command-line.

**Action:** Specify the Inline parameter from a command file only.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-02419: The Inline parameter can only be set to 1 if a log file is also specified.**

**Cause:** The Inline parameter was set to 1 when there was no log file specified.

**Action:** Specify a log file when using the Inline parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-02420: invalid command: {0}**

**Cause:** An unrecognized command name was found.

**Action:** Use one of the following commands: export, import, delete, rename, or clear.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-02421: unrecognized parameter: {0}**

**Cause:** An invalid command-line parameter was found. Only a user name or password was found.

**Action:** Provide both the user name and the password in the command arguments.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-02422: invalid object type: {0}**

**Cause:** An invalid Type parameter for the Rename command was found.

**Action:** Provide one of the following parameters: dataobject, report, ems, emstype, folder, role, user, distributionlist, plan, rule, eds, or edstype.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02423: The Dependencies parameter is invalid for Type {0}.**

---

**Cause:** The Dependencies parameter was provided with an invalid Type parameter.

**Action:** Provide one of the following types: dataobject, report, or all.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-02424: invalid log mode: {0}**

**Cause:** An invalid Logmode parameter was found.

**Action:** Provide one of the following parameters: overwrite or append.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02425: A match and a regular expression cannot be specified at the same time.**

**Cause:** Both a match and a regular expression were specified in the command line.

**Action:** Provide only one of them.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-02426: missing file name**

**Cause:** A File parameter was missing when it was not in Inline mode.

**Action:** Add a File parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-02427: The Name parameter must be specified.**

**Cause:** The Name parameter was not found.

**Action:** Provide a Name parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-02428: A name and a match cannot be specified together.**

**Cause:** Both a name and a match were specified.

**Action:** Provide only one of them.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-02429: A name and a regular expression cannot be specified together.**

---

**Cause:** Both a name and a regular expression were specified.

**Action:** Provide only one of them.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-02430: invalid new name for data object**

**Cause:** A path was specified as the new name of a data object.

**Action:** Provide a valid name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02431: New name must be specified.**

**Cause:** The Newname parameter was missing in the Rename command.

**Action:** Provide the Newname parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-02432: invalid new name for report**

**Cause:** The new name specified was a path.

**Action:** Provide a new name without path.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02433: invalid object type: {0}**

**Cause:** An invalid Type parameter was found.

**Action:** Provide one of the following parameters: dataobject, folder, role, or distributionlist.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02434: Current user does not have security credentials to perform this operation.**

**Cause:** A user who performed the operation did not have sufficient privileges.

**Action:** Grant the user sufficient privileges before retrying this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**BAM-02435: There is no role named {0}.**

---

**Cause:** The specified role was not found.

**Action:** Verify the correct role name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02436: There is no report named {0}.**

**Cause:** The specified report was not found.

**Action:** Verify the correct report name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02437: There is no rule named {0}.**

**Cause:** The specified rule was not found.

**Action:** Verify the correct rule name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02438: There is no user named {0}.**

**Cause:** The specified user was not found.

**Action:** Verify the correct user name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02439: ICommand is unable to connect to the Oracle BAM server. Check the configured host name and port number.**

**Cause:** The specified host name or port number is incorrect.

**Action:** Verify the correct host name or port number.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02440: ICommand is unable to connect to the Oracle BAM server because user credentials (username/password) have not been specified.**

**Cause:** The user credentials (username/password) required to connect to the Oracle BAM server were not specified.

**Action:** Provide user credentials using the -username command-line parameter. ICommand will prompt for the password. If running ICommand from a script then provide the user credentials in ICommand configuration file.

**Level:** 1

**Type:** ERROR

---

**Impact:** Data

**BAM-02441: Parameter: {0} must be preceded by a hyphen (-).**

**Cause:** Command parameter was found without hyphen (-).

**Action:** Provide parameter with hyphen (-).

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-02442: There is no data object matching the given regular expression "{0}."**

**Cause:** There is no data object matching the regular expression.

**Action:** Verify the regular expression given.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02443: There is no security filter matching the given regular expression "{0}."**

**Cause:** There is no security filter matching the regular expression.

**Action:** Verify the regular expression given.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02444: There is no enterprise message source matching the given regular expression "{0}."**

**Cause:** There is no enterprise message source matching the regular expression.

**Action:** Verify the regular expression given.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02445: There is no report matching the given regular expression "{0}."**

**Cause:** There is no report matching the regular expression.

**Action:** Verify the regular expression given.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02446: There is no rule matching the given regular expression "{0}."**

**Cause:** There is no rule matching the regular expression.

**Action:** Verify the regular expression given.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**BAM-02447: There is no folder matching the given regular expression "{0}."**

**Cause:** There is no folder matching the regular expression.

**Action:** Verify the regular expression given.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02448: There is no distribution list matching the given regular expression "{0}."**

**Cause:** There is no distribution list matching the regular expression.

**Action:** Verify the regular expression given.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02449: There is no external data source matching the given regular expression "{0}."**

**Cause:** There is no external data source matching the regular expression.

**Action:** Verify the regular expression given.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02450: There is syntax error in the given regular expression "{0}" at or near index {1}.**

**Cause:** There is syntax error in the given regular expression.

**Action:** Verify the regular expression given.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02500: External Data Source is not available.**

**Cause:** The specified External Data Source does not exist.

**Action:** Verify the External Data Source ID.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02501: There is no data object named {0}.**

**Cause:** The specified data object was not found.

**Action:** Verify the name of the data object in the Oracle BAM Server.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**BAM-02502: There is no distribution list named {0}.**

**Cause:** The Specified distribution list was not found.

**Action:** Verify the name of the distribution list in the Oracle BAM Server.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02503: There is no external data source named {0}.**

**Cause:** Failed to create an external data source with the specified name.

**Action:** Verify the name of the external data source in the Oracle BAM Server.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02504: There is no external data source type named {0}.**

**Cause:** The specified external data source type was not found.

**Action:** Verify external data source type name defined in the Oracle BAM Server.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02505: There is no enterprise message source named {0}.**

**Cause:** The specified enterprise message source was not found.

**Action:** Verify the enterprise message source name defined in the Oracle BAM Server.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02506: There is no enterprise message source type named {0}.**

**Cause:** The specified enterprise message source type was not found.

**Action:** Verify the enterprise message source type name defined in the Oracle BAM Server.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02507: There is no folder named {0}.**

**Cause:** The specified folder was not found.

**Action:** Verify the folder name defined in the Oracle BAM Server.

**Level:** 1

**Type:** ERROR

**Impact:** Data



---

**BAM-02508: unsupported or unrecognized item type**

**Cause:** An exported item type was not recognized.

**Action:** Provide one of the following types: DataObject, Dataset, EntMsgSource, EMS, Report, SecurityFilters, Rule, Folder, DistributionList, ExternalDataSource, or EDS.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02509: Contents and Layout cannot be disabled at the same time.**

**Cause:** A role cannot be exported without both Contents and Layout.

**Action:** Export either Contents or Layout.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-02510: data object ID {0} not found**

**Cause:** The specified data object was not found.

**Action:** Verify either the data object name or data object definitions in the Oracle BAM Server.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02511: There is no report named {0}.**

**Cause:** Failed to load the specified report.

**Action:** Verify either the report name or report definitions in the Oracle BAM Server.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02512: There is no role named {0}.**

**Cause:** Failed to load the specified role.

**Action:** Verify either the role name or role definitions in the Oracle BAM Server.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02513: The data object {0}, referenced by this rule, does not exist.**

**Cause:** The data object referenced by the rule was not found.

**Action:** Verify the data object name in the Oracle BAM Server.

**Level:** 1

**Type:** ERROR

---

**Impact:** Data

**BAM-02514: There is no rule named {0}.**

**Cause:** Failed to load the specified rule.

**Action:** Verify the rule name in the Oracle BAM Server.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02515: There is no user named {0}.**

**Cause:** Failed to create the specified user.

**Action:** Verify the user name or the user list in the Oracle BAM Server.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02516: The report assigned to this user's home page is missing or invalid.**

**Cause:** Failed to load the report assigned to the user's home page.

**Action:** Check the report list in the Oracle BAM Server.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-02517: invalid mode: {0}**

**Cause:** An invalid user import mode was found.

**Action:** Provide one of the following modes: overwrite, rename, or error.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02518: unrecognized parameter: {0}**

**Cause:** Invalid user import parameter was found.

**Action:** Provide the following parameter: mode.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02519: invalid column type**

**Cause:** An invalid column type was found.

**Action:** A column type must be one of the following types: string, integer, auto-incr-integer, float, decimal, datetime, timestamp, Boolean, iterid, lookup, or calculated.

**Level:** 1

**Type:** ERROR

---

**Impact:** Data

**BAM-02520: Contents end tag is missing or extra elements are present.**

**Cause:** A Contents end tag was missing or extra elements were present.

**Action:** Check the syntax of the XML payload.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02521: Error while creating data object.**

**Cause:** Failed to create the data object in the importer.

**Action:** Check the log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-02522: The data object was created successfully, but an error occurred while creating the indexes.**

**Cause:** Failed to create the indexes.

**Action:** Check the log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-02523: DataObject end tag missing or extra elements present**

**Cause:** A DataObject end tag was missing or extra elements were present.

**Action:** Check the syntax of the XML payload.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02524: Error while editing data object layout.**

**Cause:** An exception was thrown while editing a data object layout.

**Action:** Check the log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-02525: The data object layout was edited successfully, but an error occurred while editing the indexes.**

**Cause:** Failed to edit the indexes.

**Action:** Check the log for more details.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**BAM-02526: Error while creating folder.**

**Cause:** Failed to create the folder.

**Action:** Check the log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-02527: A data object already exists with ID {0}.**

**Cause:** A data object with same ID was already created.

**Action:** Choose a unique ID.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02528: Column ID {0} in the Contents section of the import XML does not match any Column ID in the data object.**

**Cause:** An invalid column ID was found.

**Action:** Verify the correct column ID.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02529: The external data source {0} does not exist.**

**Cause:** The specified external data source was not found.

**Action:** Verify the correct external data source name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02530: invalid data object name: {0}**

**Cause:** The column ID was either null or empty.

**Action:** Enter a valid column ID.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02531: invalid row ID in import file: {0}**

**Cause:** The row ID was not a valid long-typed data.

**Action:** Provide a valid row ID.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**BAM-02532: improper XML in Layout element**

**Cause:** A syntax error was found in the Layout tag.

**Action:** Provide valid XML payload.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02533: The data object {0} is marked as external, but the ExternalDataSource attribute is missing.**

**Cause:** The ExternalDataSource attribute was missing.

**Action:** Provide the ExternalDataSource attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-02534: The data object {0} is marked as external, but the ExternalName attribute is missing.**

**Cause:** The ExternalName attribute was missing.

**Action:** Provide the ExternalName attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-02535: The data object {0} does not exist, or its layout is being edited, and Layout tag is missing or out of order.**

**Cause:** An update of a data object definition is executed, but the data object does not exist.

**Action:** Do a create operation instead.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02536: The data object name is missing or invalid.**

**Cause:** A data object name was missing or invalid.

**Action:** Provide a valid data object name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02537: Current user does not have security credential to perform this operation.**

**Cause:** Failed to create the data object.

**Action:** Grant this user sufficient privileges to create data objects.

**Level:** 1

---

**Type:** ERROR

**Impact:** Security

**BAM-02538: Unable to set column with ID {0} to value {1}.**

**Cause:** Failed to set the value in the specified column.

**Action:** Check the log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02539: parameter {0}: column {1}: Lookup and calculated columns cannot be set.**

**Cause:** The values of the lookup and calculated columns were overridden.

**Action:** Avoid overriding the lookup and calculated column values.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-02540: improper format for parameter {0}: {1}**

**Cause:** An invalid parameter value for Setcol was found.

**Action:** Provide a valid value with lhs and rhs separated by a slash (/).

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-02541: import internal error: unknown override type {0}**

**Cause:** An internal error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**BAM-02542: parameter {0}: There is no column named {1} in data object {2}.**

**Cause:** The specified column was not found in the Setcol parameter.

**Action:** Verify the correct column name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02543: parameter {0}: Column {1} is not nullable; null cannot be used.**

**Cause:** A non-nullable column was set to null.

**Action:** Provide a valid value for the column.

**Level:** 1

**Type:** ERROR

---

**Impact:** Compliance

**BAM-02544: Parameter {0}: column {1} is not of type datetime, timestamp or string; the Now function cannot be used.**

**Cause:** A column was set to Now.

**Action:** Verify that the column is one of the following types: datetime, timestamp, or string.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02545: Invalid value type {0} for parameter {1}. The type must be null, now, or value:.**

**Cause:** The right-hand side was set to a value not belonging to one of the following types: null, now, or value:.

**Action:** Provide the null, now, or value: type on the right-hand side.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02547: The Delay value must be an integer greater than zero.**

**Cause:** An integer less than or equal to zero was found.

**Action:** Provide a valid Delay value.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02548: The distribution list {0} already exists.**

**Cause:** The specified distribution list was already created and the import mode is Error.

**Action:** Either change the import mode or change the distribution list name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02549: Distribution list name is missing or invalid.**

**Cause:** The distribution list name was missing or invalid.

**Action:** Provide a valid distribution list name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02550: There is no user named {0}.**

**Cause:** The specified user was not found.

**Action:** Verify the correct user name.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02551: An external data source {0} already exists.**

**Cause:** The specified external data source was already created and the import mode was Error.

**Action:** Either change the import mode or change the external data source name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02552: unsupported external data source version**

**Cause:** An invalid external data source version was found.

**Action:** The acceptable version is 1.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-02553: An external data source type {0} already exists.**

**Cause:** The specified external data source type was already created and the import mode was Error.

**Action:** Either change the import mode or change the external data source type name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02554: The enterprise message source already exists.**

**Cause:** The specified enterprise message source was already created and the import mode was Error.

**Action:** Either change the import mode or change the enterprise message source name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02556: premature EOF in import file**

**Cause:** More XML payload was expected, but the end of file was found.

**Action:** Check the syntax of the XML payload.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02557: Import failed at or near line {0}.**



---

**Cause:** The import operation failed.  
**Action:** Check the log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02558: Import failed at or near line {0} of file {1}.**

**Cause:** The import operation failed.  
**Action:** Check the log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**BAM-02559: The folder {0} already exists.**

**Cause:** The specified folder was already created and the import mode was Error.  
**Action:** Either change the import mode or change the folder name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02560: The folder owner is missing or invalid.**

**Cause:** The folder had no Owner and the user specified the Preserveowner option in the import command.  
**Action:** Do not use the Preserveowner option on a folder with no owner.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02561: Unrecognized item type in import file {0}.**

**Cause:** An unrecognized item type was found.  
**Action:** Provide one of the following item types: DataObject, EDS, EDType, Report, EMS, EMSType, SecurityFilters, Rule, Folder, or DistributionList.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02562: The data object {0} was not found.**

**Cause:** Could not retrieve the data object ID with the specified name.  
**Action:** Verify the correct data object name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02563: The report {0} already exists.**

---

**Cause:** A report with this name was already created and the import mode was Error.

**Action:** Either check the name or change the import mode.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02564: improper report content in XML**

**Cause:** No Contents section was available to import from the XML payload.

**Action:** Add a Contents section to the XML payload.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02565: The report name is missing or invalid.**

**Cause:** The report name was invalid.

**Action:** Verify the correct report name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02566: The report owner is missing or invalid.**

**Cause:** There was no Owner attribute specified, and the Preserveowner parameter was set.

**Action:** Either add the Owner attribute or remove the Preserveowner parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02567: Role {0} already exists.**

**Cause:** The specified role was already created, and the import mode was Error.

**Action:** Either change the import mode or change the name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02568: This rule contains a reference to a data object that is missing or invalid.**

**Cause:** The data object referenced from the rule was not found.

**Action:** Verify the correct data object name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**BAM-02569: This rule contains a reference to a distribution list that is missing or invalid.**

**Cause:** The distribution list referenced by the rule was not found.

**Action:** Verify the correct distribution list name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02570: There is already a rule named {0}.**

**Cause:** The specified rule was already created.

**Action:** Verify the correct rule name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02571: Rule content is missing or invalid.**

**Cause:** No Contents section was specified in the rule.

**Action:** Provide a Contents section in the XML payload.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-02572: The rule ID is missing or invalid.**

**Cause:** The specified ID attribute was an empty string.

**Action:** Provide a valid ID attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02573: The rule name is missing or invalid.**

**Cause:** The specified ID attribute was an empty string.

**Action:** Provide a valid Name attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02574: The rule owner is missing or invalid.**

**Cause:** There was no Owner attribute specified and the Preserveowner parameter was set.

**Action:** Either add an Owner attribute or remove the Preserveowner parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**BAM-02575: Package ID is missing or invalid.**

**Cause:** There was no PackageID attribute specified, and the Preserveowner parameter was set.

**Action:** Either add a PackageID attribute or remove the Preserveowner parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02576: The report {0}, required by this alert, does not exist.**

**Cause:** The specified report was not found.

**Action:** Verify the correct report name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02577: The rule contains a reference to a rule that is missing or invalid.**

**Cause:** The rule referenced was not found.

**Action:** Verify the correct rule name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02578: The rule contains a reference to a user that is missing or invalid.**

**Cause:** The user referenced was not found.

**Action:** Verify the correct user name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02579: A security filter named {0} already exists.**

**Cause:** The specified security filter was already created, and the mode was not Overwrite.

**Action:** Either change the security filter name or change the mode.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02580: There is no data object named {0}.**

**Cause:** The DataObjectName attribute specified was an empty string.

**Action:** Provide a valid DataObjectName attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**BAM-02581: Security filter XML has no data object name.**

**Cause:** Security filter XML has no data object name.

**Action:** Verify the Security filter XML for proper data object name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02582: There is no data object named {0} in path {1}.**

**Cause:** The DataObjectName attribute specified was an empty string.

**Action:** Provide a valid DataObjectName attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02583: improper security filter XML**

**Cause:** The SecurityFilters element end-tag was expected, but it was not found.

**Action:** Check the syntax of the XML payload.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02584: improper import file**

**Cause:** The specified root element was invalid.

**Action:** The root element must be one of the following: OracleBAMExport, PeopleSoftRTSEExport, IstanteExport, or IterationExport.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**BAM-02585: User {0} already exists.**

**Cause:** The specified user was already created, and the import mode was Error.

**Action:** Either change the mode or change the name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02586: missing or invalid user name**

**Cause:** The Name attribute specified was an empty string.

**Action:** Provide a valid Name attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02587: unsupported import file version**

---

**Cause:** Version number in MajorVersion.MinorVersion format was expected.

**Action:** Provide a valid Version attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**BAM-02588: The report ID is missing or invalid.**

**Cause:** No ID attribute was found.

**Action:** Provide ID attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02589: The report with ID {0} already exists.**

**Cause:** A report with this ID was already created and the import mode was Preserveid.

**Action:** Either check the ID or change the import mode.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02590: A report already exists with ID {0}.**

**Cause:** A report with same ID was already created.

**Action:** Choose a unique ID.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02591: premature EOF at or near line {0}**

**Cause:** Unexpected end of file was found.

**Action:** Check the syntax of the XML file.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02592: premature EOF in import file {0} at or near line {1}**

**Cause:** Unexpected end of file was found.

**Action:** Check the syntax of the XML file.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02700: invalid Changelist**

---

**Cause:** The Changelist was overwritten, but one viewset was lagging behind and requested an older one.

**Action:** No action is necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-02701: Report Cache server error**

**Cause:** Report Cache failed with the specified operation (for example, start active data, open viewset, and so on).

**Action:** Check the log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-02702: The viewset expired.**

**Cause:** The viewset with specified ID has expired.

**Action:** Open a new viewset.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**BAM-02703: RecordSet size cannot be zero (0).**

**Cause:** For all other cases, the viewset could not be opened because a request was made that the Oracle BAM Server send back zero records for that viewset.

**Action:** Check the log file for more details and report the error.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-02704: Invalid RecordSet start row index {0} for the viewset with RecordSetSize {1} and RecordCount {2}.**

**Cause:** The RecordSet with the specified start row index could not be returned.

**Action:** Ensure that the start row index is a multiple of RecordSetSize, and that it has a value from 0 to a maximum of RecordCount minus RecordSetSize.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-04000: syntax error in calculated field {0}**

**Cause:** There was a syntax error in a calculated column definition.

**Action:** Correct the calculated column definition.

**Level:** 1

**Type:** ERROR

---

**Impact:** Data

**BAM-04001: Unable to set value {0} in column {2} (type {1}).**

**Cause:** Failed to set the specified value in a column.

**Action:** Check the given data value.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-04002: Specified data object was not found.**

**Cause:** The given data object was not found.

**Action:** The data object may have been deleted by another process.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-04003: Data objects cannot be edited while they are in use.**

**Cause:** There were open viewsets on this data object.

**Action:** Close any viewsets on this data object before proceeding to edit it.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**BAM-04004: Data objects cannot be deleted while they are in use.**

**Cause:** There were open viewsets on this data object.

**Action:** Close any viewsets on this data object before proceeding to delete it.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**BAM-04005: Cannot edit a data object that is a lookup source for a data object that is currently in use.**

**Cause:** There were open viewsets on data objects with a lookup into this data object.

**Action:** Close any viewsets on dependent data objects before proceeding to edit lookup source data objects.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**BAM-04006: Cannot delete a data object that is a lookup source for a data object that is currently in use.**

**Cause:** There were open viewsets on data objects with a lookup into this data object.

**Action:** Close any viewsets on dependent data objects before proceeding to delete lookup source data objects.



---

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**BAM-04007: Dimension name {0} is not unique.**

**Cause:** The specified dimension name was not unique.

**Action:** Specify a unique dimension name.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-04008: Hierarchy name {0} is not unique.**

**Cause:** The specified hierarchy name was not unique.

**Action:** Specify a unique hierarchy name.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-04009: Cannot change column {0} from a non-calculated column to a calculated column.**

**Cause:** An attempt was made to convert a non-calculated column to a calculated column.

**Action:** Do not attempt to convert a non-calculated column to a calculated column.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-04010: Cannot change column {0} to a datetime/timestamp column.**

**Cause:** An attempt was made to convert a column from a non-datetime type to a datetime type.

**Action:** Do not attempt to convert a non-datetime column to a datetime column.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-04011: Folder or data object {0} already exists.**

**Cause:** An attempt was made to create a folder that already exists.

**Action:** A unique name must be specified when creating folders.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-04012: Folder does not exist.**

**Cause:** The folder was deleted by another process.

---

**Action:** Create the folder before proceeding with the current operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-04013: The source lookup data object {0} for column {1} cannot be found.**

**Cause:** The source lookup data object was deleted.

**Action:** Create the source lookup data object before proceeding with the current operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-04014: Cannot move {0}. The destination folder is a subfolder of the source folder.**

**Cause:** The folder specified was a subfolder of the source folder.

**Action:** Do not attempt to move folders to their own subfolders.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-04015: Cannot move {0}.**

**Cause:** A FolderException was thrown when a folder was moved.

**Action:** Check the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Operating System

**BAM-04016: Cannot move {0}. The destination folder is the same as the source folder.**

**Cause:** The destination folder was the same as the source folder.

**Action:** Do not attempt to move an object to a folder that is the same as its source folder.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-04017: The external data sources cannot be created when there are no external data source types defined.**

**Cause:** There were no external data source types defined.

**Action:** Define external data source types in the Oracle BAM Administrator application.

**Level:** 1

**Type:** ERROR

---

**Impact:** Compliance

**BAM-04018: The data object does not contain a column named {0} that is used as a matching field in the lookup column {1}.**

**Cause:** The foreign key column was missing from this data object.

**Action:** Verify the name of the foreign key column.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-04019: An index cannot be created because this data object does not contain a column named {0}.**

**Cause:** The column referenced in the index was missing in this data object.

**Action:** Verify the column name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-04020: Folder named {0} not found.**

**Cause:** The specified folder did not exist.

**Action:** Create the folder before proceeding with the current operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-04021: At least one column must be defined in the index.**

**Cause:** No column has been specified in the index.

**Action:** Define at least one column in the index.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-04022: The date value must have the following format: {0}.**

**Cause:** Failed to set the specified date value in a column.

**Action:** Input date value in suggested format.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-04200: Action {0} ({1}) failed.**

**Cause:** The action order with the given action type failed.

**Action:** Check the log for more details.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BAM-04201: An error occurred while deleting the data.**

**Cause:** A delete operation initiated by a Delete action button failed with a reason other than missing permissions.

**Action:** Check the log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-04202: Enter a new value.**

**Cause:** An incorrect data type was found.

**Action:** Enter a new value.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Data

**BAM-04203: The value {0} is not a valid {1}.**

**Cause:** A column was updated with data of an invalid type.

**Action:** Provide data of the correct type for the update operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-04204: An error occurred while submitting the data.**

**Cause:** An insert operation failed due to reasons other than missing permissions or non-null requirements.

**Action:** See the log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-04205: insufficient permission to modify the data object**

**Cause:** An attempt was made to modify the data object without sufficient permission.

**Action:** Request that the administrator assign sufficient permission to the user account before attempting this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**BAM-04206: Cannot insert or update null value in column {0}.**

**Cause:** A null value was encountered.

**Action:** Specify a non-null value.

**Level:** 1

---

**Type:** ERROR

**Impact:** Data

**BAM-04207: An error occurred while updating the data.**

**Cause:** An update operation failed due to reasons other than missing permissions or non-null requirements.

**Action:** Check the log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-04208: Report not found.**

**Cause:** The report with the ID specified was not found.

**Action:** Check the log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-06000: Authentication failed.**

**Cause:** Credentials were not provided.

**Action:** Provide credentials in the service request.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**BAM-06002: Web services object {0} is null.**

**Cause:** A null pointer exception occurred in Web services. A Web services object was found null.

**Action:** Check the log message for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-06003: Data object {0} does not exist.**

**Cause:** The specified data object does not exist in the Oracle BAM Server.

**Action:** Provide the correct data object name including the full path to its location.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-06004: The rule name does not include a period (.) separator between the user name and the alert name.**

**Cause:** There was no period (.) found in the rule name.

**Action:** A period must be used as the separator between the user name and the alert name.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-06005: The rule name includes a user name that does not match the user making the actual call to the Web service.**

**Cause:** The user name embedded in the rule name did not match the user making the actual call to the Web service.

**Action:** Invoke Web services using the specified user name.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-06006: Exception occurred when firing the rule.**

**Cause:** An exception was thrown when firing the rule.

**Action:** Check the log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-06007: The XML payload is invalid; {0} is expected.**

**Cause:** The XML payload is invalid.

**Action:** Check the Web services schema and provide the correct payload.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-06008: The XML payload is invalid; extra contents were found.**

**Cause:** Extra contents were found in the XML payload.

**Action:** Check the Web services schema and provide the correct payload.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-06009: invalid column name: {0}**

**Cause:** An invalid column name was found in the payload.

**Action:** Check the Web services schema and provide the correct payload.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-06010: invalid XML payload; {0} found**

**Cause:** Premature end of XML payload reached.

**Action:** Check the Web services schema and provide the correct payload.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-06011: invalid key specification; {0} found**

**Cause:** An invalid key was specified.

**Action:** Provide keys in a comma separated format (for example, Salesperson,SalesNumber).

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-06012: invalid credentials**

**Cause:** The credentials were invalid or not supplied by the user.

**Action:** Supply valid credentials for the secured web service.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**BAM-06100: Data object definition creation failed.**

**Cause:** Invalid message content was present in the XML payload.

**Action:** Correct the message content in the XML payload.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-06101: Cannot delete the {0} data object definition.**

**Cause:** Invalid message content was present in the XML payload

**Action:** Correct the message content in the XML payload.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-06102: Cannot update data object definition.**

**Cause:** Invalid message content was present in the XML payload

**Action:** Correct the message content in the XML payload.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-06103: invalid XML payload for DataObjectDefinition Web service**

**Cause:** The XML payload was invalid.

**Action:** Provide a valid XML payload for the associated operation.

**Level:** 1

---

**Type:** ERROR

**Impact:** Data

**BAM-06104: Error serializing the definition of data object {0}.**

**Cause:** Web services failed to serialize the object to XML.

**Action:** Verify that the Oracle BAM Server is running. Check the log message if it is available.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-06140: Failure on data object {0} batch operation.**

**Cause:** Invalid message content was present in the XML payload

**Action:** Correct the message content in the XML payload

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-06141: Failure on data object {0}, {1} operation.**

**Cause:** Invalid message content was present in the XML payload.

**Action:** Correct the message content in the XML payload.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-06142: Cannot delete the rows of data object {0}.**

**Cause:** Invalid message content was present in the XML payload.

**Action:** Correct the message content in the XML payload

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-06143: Cannot look up the rows of data object {0}.**

**Cause:** Invalid message content was present in the XML payload.

**Action:** Correct the message content in the XML payload.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-06144: Cannot insert rows into data object {0}.**

**Cause:** Invalid message content was present in the XML payload.

**Action:** Correct the message content in the XML payload.

**Level:** 1

**Type:** ERROR



---

**Impact:** Process

**BAM-06145: Cannot update rows in data object {0}.**

**Cause:** Invalid message content was present in the XML payload.

**Action:** Correct the message content in the XML payload.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-06146: Cannot upsert rows in data object {0}.**

**Cause:** Invalid message content was present in the XML payload.

**Action:** Correct the message content in the XML payload.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-06147: invalid XML payload for DataObjectOperations Web service**

**Cause:** Invalid message content was present in the XML payload.

**Action:** Correct the message content in the XML payload.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-06180: Decoding {0} failed.**

**Cause:** Failed to decode the request's URL.

**Action:** Check the log message for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-06181: Encoding {0} failed.**

**Cause:** The WSIL Browser failed to encode the URL in the response.

**Action:** Check the log message for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-06182: Folder {0} does not exist.**

**Cause:** The folder specified in the URL does not exist.

**Action:** Correct the path in the URL.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-06183: MetadataBrowser initialization failed.**

---

**Cause:** Failed to initialize the MetadataBrowser object.

**Action:** Check the log message for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-06184: MetadataBrowser.browseDataObjects(): exception={0}**

**Cause:** Failed to browse and generate the response.

**Action:** Check the log message for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-06185: invalid URL: {0}**

**Cause:** Invalid URL was found.

**Action:** Correct the URL.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-06220: Exception while processing {0}.**

**Cause:** WSIL browser failed to process the request.

**Action:** Check the log message for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-06221: WSIL document creation failure**

**Cause:** Instantiating WSILCreator object failed.

**Action:** Check the log message for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-06260: Query string DataObjectID=\_Xxxx not found in the URL.**

**Cause:** The query string that specifies the data object ID was not found in the URL.

**Action:** Provide a URL similar to:

[http://999.99.999.99:9001/OracleBAM/WebServices/GetDataObjectDefinition?DataObjectID=\\_Employees](http://999.99.999.99:9001/OracleBAM/WebServices/GetDataObjectDefinition?DataObjectID=_Employees)

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**BAM-07000: Invalid field maximum size in enterprise message source definition.**

**Cause:** The field maximum size value in enterprise message source definition is an invalid number.

**Action:** Provide a valid numeric value for the field maximum size.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-07001: invalid XSL transformation for field {0}: {1}**

**Cause:** The XSL transformation for the field is invalid.

**Action:** Look at the error message for details and correct the errors.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-07002: Unrecognized field type in enterprise message source definition.**

**Cause:** A field type other than the following was specified: String, Integer, Float, DateTime, Decimal, or Boolean.

**Action:** Check the spelling of field type or choose one from the above list.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-07003: The enterprise message source definition could not be loaded.**

**Cause:** The enterprise message source definition could not be loaded using the given ID.

**Action:** Check the spelling of the ID.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BAM-07020: The required keys to perform the requested operation were not supplied.**

**Cause:** Keys were missing for the requested operation.

**Action:** Provide the required keys for the requested operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-07021: The data object {0} must have a surrogate key column named {1}.**

**Cause:** The surrogate key column does not exist in the data object.

**Action:** Check the spelling of the column name and correct it.

**Level:** 1

**Type:** ERROR

---

**Impact:** Data

**BAM-07022: The surrogate key column {0} must be an autoincrementing integer type.**

**Cause:** The surrogate key column was not of type autoincrementing integer.

**Action:** Change the type of surrogate key column to autoincrementing integer.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-07023: The data object {0} must have a natural key column named {1}.**

**Cause:** The natural key column does not exist in the data object.

**Action:** Check the spelling of the column name and correct it.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-07024: The data object {0} must have an error column named {1}.**

**Cause:** The required error column does not exist in the data object.

**Action:** Check the spelling of the column name and correct it.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-07025: Unsupported column name {0} in the result set.**

**Cause:** The column name provided is not supported in the result set.

**Action:** Check the spelling of the column name and correct it.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-07026: unsupported method**

**Cause:** The method name provided is not supported in the ResultSet.

**Action:** Use other methods.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-07027: no more rows**

**Cause:** There are no more rows in the ResultSet.

**Action:** Check the return value of the next method before invoking this method.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**BAM-07028: The key condition {0} is invalid.**

**Cause:** The key condition is invalid.

**Action:** Valid key conditions are: \*, =, !-, <, <=, >, and >=.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-07029: invalid XML payload**

**Cause:** None of the input fields match any data object field.

**Action:** Check the source field names and provide the correct payload.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-07030: Invalid XML payload for enterprise message source definition.**

**Error={0}**

**Cause:** An exception was thrown while loading up fields of this enterprise message source type with the information read from the System Object.

**Action:** Check the log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-07031: invalid message type: {0}**

**Cause:** An invalid message type was found.

**Action:** Provide either XML or MAP message type.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-07032: Oracle BAM enterprise message source is already started.**

**Cause:** The Oracle BAM enterprise message source was already started.

**Action:** No action is necessary.

**Level:** 1

**Type:** WARNING

**Impact:** Process

**BAM-07033: The enterprise message source failed with error: {0}.**

**Cause:** The Oracle BAM enterprise message source failed.

**Action:** Check the log file for more details and report the error.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**BAM-07034: Oracle BAM enterprise message source is not running.**

**Cause:** The Oracle BAM enterprise message source is not running, and an application tried to stop it.

**Action:** Check the log file for more details and report the error.

**Level:** 1

**Type:** WARNING

**Impact:** Process

**BAM-07035: Invalid request specified; parameter {0} is missing.**

**Cause:** The enterprise message source failed because the parameter was not provided.

**Action:** Check the log file for more details and report the error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BAM-07036: The value {0} specified for parameter {1} is unknown.**

**Cause:** The enterprise message source failed because wrong the parameter value was provided.

**Action:** Check the log file for more details and report the error.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-07037: Multiple matching rows were found in dimension table.**

**Cause:** Multiple matching rows were found in dimension table.

**Action:** Trace the history to find out why multiple rows with the same key have been inserted.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-07038: Non-key columns do not match.**

**Cause:** A matching is found in dimension table. But, non-key columns do not match.

**Action:** Provide the correct source column values in the looksert operation.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**BAM-07039: Row update failed with no matching rows.**

**Cause:** There was a failure trying to update a row because there is no matching rows in target table.

**Action:** Provide the correct source key values in the update operation.

**Level:** 1

---

**Type:** ERROR

**Impact:** Data

**BAM-07040: Data object {0} not found.**

**Cause:** There was a failure trying to access the Data object.

**Action:** Make sure the Data object exists.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BAM-07041: Invalid Message Selector format**

**Cause:** The attempt to parse the Message Selector data failed.

**Action:** Verify that the format meets the guidelines specified in the documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Data





---

## BDSS-00000 to BDSS-65105

**BDSS-00000: DispatcherSettings - error loading settings. {0}**

**Cause:** Cannot load the preferences node for BDSS.

**Action:** Verify that the preferences back-end store exists and that user this application is running under has correct access rights.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-00005: Exception thrown by backing store when setting ChunkSize: {0}**

**Cause:** Cannot store data to the preferences node for BDSS.

**Action:** Verify that the preferences back-end store exists and that user this application is running under has correct access rights.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-00006: Exception thrown by backing store when setting EngineEndpointUrl: {0}**

**Cause:** Cannot store data to the preferences node for BDSS.

**Action:** Verify that the preferences back-end store exists and that user this application is running under has correct access rights.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-00010: Cannot retrieve the backing store to load preferences.**

**Cause:** Cannot retrieve the preferences node for BDSS.

**Action:** Verify that the preferences back-end store exists and that user this application is running under has correct access rights.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**BDSS-00011: Cannot initialize SyncDispatcherBean.**

---

**Cause:** There is either improper configuration or BDSS components are not installed correctly.

**Action:** Verify your configuration and reinstall the BDSS components if necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-00012: User chunk size is not available from configuration. Using the default.**

**Cause:** Cannot retrieve the data from the preferences node for BDSS.

**Action:** Verify that the preferences back-end store exists and that user this application is running under has correct access rights.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**BDSS-00014: ArrayOutOfBoundsException exception occurred!**

**Cause:** The code referenced an array index that does not exist.

**Action:** Restart the application.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-00015: Cannot get users to dispatch from configuration!**

**Cause:** The list of users to synchronize was not returned by the BDSS configuration.

**Action:** Verify that there are users that are configured properly using the User Settings MBean.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-00017: Calling SynchronizeUsers failed: {0}**

**Cause:** The call to the operation SynchronizeUsers failed.

**Action:** Verify that the BDSS hub components are installed on your applications server and are accessible.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-00019: A member of the input users array was an empty string or was null. Continuing to process other users.**

**Cause:** A hub user login was stored as an empty string.

**Action:** Verify that all hub users have a non-empty string for their login.

**Level:** 1

---

**Type:** NOTIFICATION

**Impact:** Data

**BDSS-10001: Failed to allocate an object of type {0}.**

**Cause:** Failed to allocate an object of the type specified.

**Action:** Ensure that the system is not running low on memory. Check the log for other errors that may have led to this problem. Try restarting the appropriate component or machine.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BDSS-10002: Null object detected. Context: {0}**

**Cause:** A null object has been detected. The object name or type is logged with this message.

**Action:** Examine the log to determine the cause of this problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BDSS-10004: Original Error already logged.**

**Cause:** This indicates that an exception has been detected, although details of the primary error are not logged with this message to avoid duplicate logging of an error. The primary error which caused this exception should already be logged.

**Action:** Examine the log for an earlier log entry that indicates the primary error which caused this exception.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BDSS-10005: Object {0} is invalid.**

**Cause:** A component in the BDSS product has detected an invalid object that is expected to be valid. For example, the object may be null, or it may be an empty string, etc. The invalid object may be a function parameter or an object retrieved by other means.

**Action:** Try checking configuration. Try restarting components or the machine. Try reinstalling the appropriate BDSS component. Examine the log for other messages that may indicate the cause of this problem.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-10006: Failed to access EJB due to problem with object {0}.**

**Cause:** Indicates that an error occurred when attempting to access an Enterprise Java Bean.

---

**Action:** Examine the log to determine the cause for this error as an exception cause may have been logged with this message. Ensure that the product is properly installed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BDSS-10007: Version Id**

**Cause:** This message string is a label that identifies a PIM record version ID. This string is never logged by itself but is only ever appended to another primary logged message string. The primary message may be an error or may simply be a debug message.

**Action:** See the log for the primary logged message to determine whether any action is needed for the primary log message. No action is needed based on this message alone.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BDSS-20001: An unrecoverable error occurred while pushing record change(s) to the target PIM. Aborted pushing additional events to the PIM.**

**Cause:** The cause is unknown but has been caught by a Java Exception. The exception occurred while the Sync-Engine was in the process of pushing record change events to a connector.

**Action:** Search the BDSS log for the exception text that should give a clue to the cause.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20004: Failed to create a new record. The Sync-Engine will continue to push any additional create-record actions to the target PIM. Source-PIM record data: {0}**

**Cause:** A failure code was returned from the target connector when the Sync-Engine invoked its createRecord method.

**Action:** Ensure that the target PIM and PIM connector is installed and working correctly. Look in the target connector log for clues to the failure.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20005: Failed to update a PIM record. The Sync-Engine will continue to push any additional update-record actions to the target PIM.**

**Cause:** The Sync-Engine detected an error while attempting to update a PIM record.

**Action:** Ensure that the target PIM and PIM connector are installed and working correctly. Look in the Sync-Engine log and the target connector log for clues to identify the failure.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20006: Failed to update a PIM record.**

**Cause:** The Sync-Engine has detected an exception while in the process of updating a PIM record. The failure may be due to a problem in the hub, rather than a connector issue.

**Action:** Examine the Sync-Engine log for the exception text that should give a clue as to why the failure occurred.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20007: Source PIM record data:**

**Cause:** This message is simply used as a label to identify the source PIM record data that is logged immediately following this label text. This message is appended to a primary error message and is never logged by itself.

**Action:** No action is required specifically for this error message. Instead, see the action defined for the primary error message to which this error message is appended.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BDSS-20009: The target PIM connector failed to delete a PIM record. The Sync-Engine will attempt to push any additional delete-record actions to target PIM.**

**Cause:** The Sync-Engine has detected an error while attempting to delete a PIM record.

**Action:** Examine the Sync-Engine log for information about the error cause.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20010: Failed to write an error status message to a PIM metadata record for Connector {0}, Hub Domain {1}, PIM User {2} PIM record ID {3}.**

**Cause:** The Sync-Engine detected an error while preparing to write an error message to the database for a particular PIM Map Record.

**Action:** Examine the Sync-Engine log to find the underlying exception message.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20012: Failed to delete a PIM record.**

---

**Cause:** The Sync-Engine has detected an exception while in the process of deleting a PIM record. The failure may be due to a problem in the hub, rather than a connector issue.

**Action:** Examine the Sync-Engine log for the exception text that should give a clue as to why the failure occurred.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20013: Failed to update metadata to the BDSS hub-record. \tSource Connector user = {0} \tSource PIM Connector Name = {1} \tSource PIM Record Identifier = {2}.**

**Cause:** This error occurs when the Sync-Engine is unable to persist updated metadata to the BDSS database for a particular BDSS hub-record. In particular, this error occurs when the Sync-Engine catches an exception when invoking method `SyncConfig::getHubRecordForPimRecord`. This error could indicate corrupt metadata for a particular BDSS hub-record, or perhaps a network or database failure, or a problem with the SyncConfig component.

**Action:** Check that the database is accessible. Perhaps try restarting the BDSS hub. If corrupt metadata is suspected, then try removing all metadata for a user and perform initial synchronization for a user.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20015: Failed to find an BDSS PIM metadata record for BDSS master hub record ID = {0}**

**Cause:** This error message is logged when a PIM metadata record could not be found for the specified hub user ID, hub record ID and Connector. In particular, the Sync-Engine logs this message when it detects an exception from method `SyncConfig::getPimRecordForHubRecord`. This problem could be due to corrupt metadata (e.g. the PIM metadata record is actually missing) or some other cause.

**Action:** Examine the log for the exception text that should give a better clue as to the underlying cause of the error. Ensure that all infrastructure, such as the database and network, are working correctly. Ensure that all configuration is correct. Ensure that hub metadata is not corrupt for the logged hub record ID. If the problem is due to hub metadata corruption for a given user then try clearing that user hub metadata and perform first-time synchronization for the user.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20017: (Target Connector user)**

**Cause:** This message string is a label for a Connector user identifier that is a destination target for record events that are being pushed to a PIM connector. This string is never logged by itself but is only ever appended to another primary logged message string. The primary message may be an error or may simply be a debug message.

---

**Action:** See the log for the primary logged message to determine whether any action is needed. No action is needed based on this message alone.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**BDSS-20018: (Target PIM Connector Name)**

**Cause:** This message string is a label for the name of a PIM connector that is a destination target for record events that are being pushed to a PIM. This string is never logged by itself but is only ever appended to another primary logged message string. The primary message may be an error or may simply be a debug message.

**Action:** See the log for the primary logged message to determine whether any action is needed. No action is needed based on this message alone.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**BDSS-20019: BDSS queue message receiver timeout expired. Queue message not received.**

**Cause:** This error indicates that the Sync-Engine ExtractResponseTimeout occurred it received an ExtractResponse for which it was waiting. In particular, this error represents a failure to receive an ExtractResponse via a queue message in a timely fashion. The Sync-Engine uses the ExtractResponseTimeout as a time-trigger to determine when a connector has become unresponsive. In such a case, the Sync-Engine has determined that it will not receive an ExtractResponse in a timely fashion and thus takes recovery action to abort the synchronization. This problem could be caused when a connector does not correctly send an ExtractResponse to the Sync-Engine. Alternatively, the ExtractResponse was sufficiently large, or network latency slow enough, that the timeout occurred before the ExtractResponse could be properly transferred to the Sync-Engine from a connector.

**Action:** Ensure that all connectors are properly working and can successfully send ExtractResponse objects to the Sync-Engine. Ensure that the Sync-Engine machine is not overloaded and can handle receiving ExtractResponse objects efficiently. Ensure that the amount of data transferred via an ExtractResponse is not too large, or the network latency too slow, to trigger the ExtractResponseTimeout. If necessary, increase the ExtractResponseTimeout timeout value. Determine whether an http webservice timeout is occurring when a connector sends an ExtractResponse to the Sync-Engine.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20020: Received queue message that is an unexpected message class type. Expecting class type ObjectMessage. {}.**

**Cause:** This error indicates that the Sync-Engine has received a queue message with an unexpected Java class type. This error suggests a communication protocol failure within the Sync-Engine.

---

**Action:** Ensure the BDSS product is installed and configured correctly and ensure that a rogue producer is not sending messages to the BDSS message queue.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20021: Invalid Hashtable element key.**

**Cause:** This error indicates that the Sync-Engine has detected an invalid hash table element key.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20022: Invalid Hashtable element value for key = {0}.**

**Cause:** This error indicates that the Sync-Engine has detected an invalid hash table element value for the specified element key.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20023: null Hub User ID detected in an element of UsersArray.**

**Cause:** The Sync-Engine has detected an invalid hub-user in the UsersArray. The Sync-Engine cannot synchronize an invalid hub user. In particular, a string array element is null, instead of specifying a valid hub user.

**Action:** Ensure that the array of users sent to the Sync-Engine has a valid hub user for each element in the array.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20024: Invalid Hub User ID detected in an element of UsersArray.**

**Cause:** The Sync-Engine has detected an invalid hub-user in the UsersArray. The Sync-Engine cannot synchronize an invalid hub user. In particular, a valid string array element has been detected, but the string is empty and does not specify a hub user.

**Action:** Ensure that the array of users sent to the Sync-Engine has a valid hub user for each element in the array.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20026: Must configure a user hub-domain synchronization between two connector URLs. Currently detecting {0} URLs.**



---

**Cause:** Specifies that an invalid number of connector URLs have been identified for synchronization of a hub domain for a user. Synchronization can only occur between two connector URLs for a given user and hub domain.

**Action:** Validate that BDSS configuration is correct for synchronizing between two connectors.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-20028: Invalid ExtractResponse detected. The ExtractResponse sent by a connector indicates that it contains delete events but the delete events do not exist.**

**Cause:** This error occurs when the Sync-Engine detects that an ExtractResponse specifies a true value for member ExtractResponse.ExtractResponseData.hasDeletes and yet specifies a null value for member ExtractResponse.ExtractResponseData.deleteRecordIdArray. Thus, the ExtractResponse object is corrupt and cannot be processed.

**Action:** Fix the connector that is providing the invalid ExtractResponse.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20029: Invalid ExtractResponse detected. The ExtractResponse sent by a connector contains a null delete record ID.**

**Cause:** This error is logged when the Sync-Engine detects a null array element in member ExtractResponse.ExtractResponseData.deleteRecordIdArray when a valid delete record ID is expected.

**Action:** Fix the connector that is providing the invalid ExtractResponse.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20030: An ExtractResponse indicates that upserts exist but they do not.**

**Cause:** This error occurs when the Sync-Engine determines that an ExtractResponse should contain upsert records when it does not. In particular, member ExtractResponse.ExtractResponseData.hasUpserts is true but upsertRecordArray is ExtractResponse.ExtractResponseData.upsertRecordArray is invalid.

**Action:** Fix the connector that is providing the invalid ExtractResponse.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20035: Cannot find a PIM connector endpoint for the current user and Connector {0}**

**Cause:** The Sync-Engine queried all connector URLs for a particular Connector using connector interface method getPimServerEndPoint. However, none of the

---

connector instances provided a connector endpoint for a particular Connector user.

**Action:** See the log entry to identify the Connector and the corresponding hub user ID for this error. Ensure that the Connector user is configured in the PIM, that BDSS configuration is correct, that all connector instance URLs are properly configured, and that the connector instance can successfully return the endpoint for the Connector and user for which this problem occurs.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20040: An error occurred while pushing create, update or delete changes to Connector {0} for hub domain {1}.**

**Cause:** This is a generic high-level error message indicating that an error occurred while pushing create, update, or delete events to the specified Connector and hub domain.

**Action:** Examine this message in the log to find the pertinent Connector and hub domain. Examine the log for the underlying error that is expected to have been logged prior to this error message. Take appropriate action once the underlying error has been identified.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20041: The BDSS Engine will continue to push record changes to the next PIM if any are available.**

**Cause:** The text of this informational message is a supplement to the text of message SYNCENG\_PUSH\_TO\_PIM\_ERROR. This message text is logged only when the Sync-Engine has changes to additional PIMs that can be propagated for the same hub domain.

**Action:** No action is necessary that is specific to this message. Instead, see the action text for error message SYNCENG\_PUSH\_TO\_PIM\_ERROR.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20043: Unexpected or failure result code detected in an ExtractResponse. ExtractResponse Result Code = {0}. ExtractResponse Error Description = {1}**

**Cause:** An ExtractResultCode value of either PARTIAL\_EXTRACT\_COMPLETED\_OK or PARTIAL\_EXTRACT\_COMPLETED\_NOTOK has been detected in an ExtractResponse received from a connector. An ExtractResponse, with either of these ExtractResultCode values, is considered nonviable for synchronization by the Sync-Engine. Thus, the Sync-Engine cannot perform synchronization with the corresponding ExtractResponse.

**Action:** Examine the connector, PIM server and configuration corresponding to the failed ExtractResponse. Fix the problem with this connector-related error.

**Level:** 1

**Type:** ERROR

---

**Impact:** Data

**BDSS-20044: Unknown failure code detected in an ExtractResponse.**

**ExtractResponse Result Code** = {0}. **ExtractResponse Error Description** = {1}

**Cause:** The Sync-Engine detects an unknown ExtractResultCode value in an ExtractResponse received from a connector.

**Action:** Examine the connector, PIM server and configuration corresponding to the failed ExtractResponse. Fix the problem with this connector-related error.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20045: Unknown Connector detected when retrieving an extract response.**

**Cause:** The Sync-Engine recognizes only two Connectors - one for Exchange and the other for Webcenter. The Connector, received in an ExtractResponse from a connector, is not recognized by the Sync-Engine.

**Action:** Examine the log entry for this message to obtain the Connector retrieved from the problematic ExtractResponse. Examine the connector, PIM server and configuration corresponding to the problematic ExtractResponse. Ensure that the connector provides the correct PIM server type in the ExtractResponse objects it sends to the Sync-Engine.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20046: Error getting ExtractResponse objects.**

**Cause:** This message indicates that the Sync-Engine detected an error while receiving ExtractResponse objects during a synchronization session. The underlying problem should already have been logged.

**Action:** Examine earlier log messages, just prior to this log message, to identify the underlying problem.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20047: Null name-key object detected in PIM record description array.**

**Cause:** This error occurs when the Sync-Engine is comparing records using their key fields and detects that the name of a field is invalid, in other words empty or null, for an UpsertRecord provided by a connector ExtractResponse.

**Action:** Ensure that key-field configuration is correct. Examine recent ExtractRequests in the log to help determine which connector is providing an invalid key-field. Ensure that all connectors are providing valid ExtractRequest responses to the Sync-Engine.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20048: An Exception error occurred during synchronization.**

---

**Cause:** An exception has been detected in the Sync-Engine during synchronization.

**Action:** Examine the log file for information about this exception.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20049: Unable to access FtsLogger class object while processing an Exception error. Exception: {0}.**

**Cause:** An exception has been detected in the Sync-Engine during synchronization. However, the Sync-Engine is unable to log the session ID and hub user ID with this message.

**Action:** Examine the log file for information about this exception.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20050: Invalid Engine Endpoint URL received from configuration. URL is null or empty string.**

**Cause:** An invalid Sync-Engine endpoint URL has been returned from method SyncConfig::getEngineEndPointURL, without the method having thrown an exception.

**Action:** Confirm that a valid engine endpoint URL is configured.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-20052: Hub domain synchronization failed.**

**Cause:** This message indicates that an error was detected while synchronizing a particular hub domain. The hub user, synchronization session identifier and hub domain are logged with this message.

**Action:** Examine this message in the log to determine which hub domain failed. Examine the log to find the underlying cause of the failure.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20053: Failed to send extract request.**

**Cause:** An error was detected while attempting to send an extract request to a connector.

**Action:** Examine the log to determine the underlying problem which caused the error.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**BDSS-20054: Failed to initialize connector user synchronization session. BDSS presumes the connector instance URL is invalid and will clear the connector endpoint for hub user: {0}, Connector: {1}. Synchronization will be attempted in a subsequent sync cycle.**

**Cause:** An error was detected while invoking connector method initializeUserSyncSession.

**Action:** Examine the log to determine the underlying problem which caused the error. Expect to find the hub user ID, Connector and a description of the underlying exception in the log.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20057: Failed connector initialization.**

**Cause:** An error was detected while attempting to initialize the connectors involved in synchronization for a hub-user.

**Action:** Examine the log to determine the underlying problem which caused the error.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20058: Unable to get a connector instance URL for the configured connector endpoint for hub user: {0}, Connector: {1}. The failed connector endpoint will be cleared for this user so a new connector endpoint can be configured during the next synchronization cycle.**

**Cause:** The Sync-Engine was not able to get a connector endpoint for the hub user and Connector specified in this message.

**Action:** Examine the log entry for information about the underlying exception, and to identify the hub user and Connector for which the problem occurred.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-20059: Unable to get valid connector instance URL for hub user: {0}, Connector: {1}.**

**Cause:** The Sync-Engine has determined that a connector instance URL is invalid, either empty or null, even though an exception did not occur while attempting to retrieve the connector instance URL.

**Action:** Examine the log message to determine the hub user and Connector for which this error occurred. Ensure that all connector instance URL and endpoint configuration is correct. Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20060: Failure detected when attempting to invoke connector method {0}.**

---

**Cause:** An exception has been detected while invoking the connector method specified by this message.

**Action:** Examine the log to determine the hub user ID and Connector corresponding to this failure. Also, examine the log to determine which connector method failed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BDSS-20061: Unable to configure connector endpoint for current hub user and Connector.**

**Cause:** The Sync-Engine detected an exception thrown from method `m_SyncConfig.setConnectorEndPoint`.

**Action:** Ensure that configuration and installation are correct. Examine this message in the log to determine the corresponding hub user ID and Connector.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-20062: "Connector method {0} returned error code {1}."**

**Cause:** The Sync-Engine has detected an error code returned from a connector method.

**Action:** Examine the log to determine which connector method failed and the error code it returned.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BDSS-20063: Detected an invalid message type. Expecting type `javax.jms.MapMessage`. {0}**

**Cause:** The SyncUserMDB Message Driven Bean has erroneously received a queue message that is not of type `javax.jms.MapMessage`. SyncUserMDB retrieves messages from a Weblogic Server in-memory queue. It retrieves queue messages having message property `RECIPIENT = BDSS SyncUser MDB Recipient`.

**Action:** Ensure that no other software products are sending messages to the configured WLS in-memory queue with queue message having property `RECIPIENT = BDSS SyncUser MDB Recipient`. For reference, content of the erroneous queue message is appended to this log entry. Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20084: PIM Record Description:**

**Cause:** This message string is a label whose purpose is to indicate that PimRecordDescription metadata is being logged for a PIM record. This string is never logged by itself but is only ever appended to another primary logged

---

message string. The primary message may be an error or may simply be a debug message.

**Action:** See the log for the primary logged message to determine whether any action is needed. No action is needed based on this message alone.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20085: Field Name**

**Cause:** This message string is a label that identifies a single PimRecordDescription field name for a PIM record. This string is never logged by itself but is only ever appended to another primary logged message string. The primary message may be an error or may simply be a debug message.

**Action:** See the log for the primary logged message to determine whether any action is needed. No action is needed based on this message alone.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20086: Field Value is null**

**Cause:** This message string indicates that a PimRecordDescription.descriptionArray object contains a KeyValuePair object with a null field value. This string is never logged by itself but is only ever appended to another primary logged message string. The primary message may be an error or may simply be a debug message.

**Action:** See the log for the primary logged message to determine whether any action is needed for the primary log message. Also, fix the cause of this null field value within the PimRecordDescription metadata of a PIM record.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20087: Field Value**

**Cause:** This message string is a label that identifies a single PimRecordDescription field value for a PIM record. This string is never logged by itself but is only ever appended to another primary logged message string. The primary message may be an error or may simply be a debug message.

**Action:** See the log for the primary logged message to determine whether any action is needed for the primary log message. No action is needed based on this message alone.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20088: The description array is empty**

**Cause:** This string is never logged by itself but is only ever appended, to another primary logged message string, to provide ancillary information. The primary message may be an error or may simply be a debug message. This message

---

indicates that a PimRecordDescription information is not available. In this case, the PimRecordDescription object is valid, and contains a valid KeyValuePair array object, but the KeyValuePair array has no elements.

**Action:** See the log for the primary logged message to determine whether any action is needed.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20089: The description array is null**

**Cause:** This string is never logged by itself but is only ever appended, to another primary logged message string, to provide ancillary information. The primary message may be an error or may simply be a debug message. This message indicates that PimRecordDescription information is not available for a PIM record. In this case, the PimRecordDescription object is valid but contains a null KeyValuePair array.

**Action:** See the log for the primary logged message to determine whether any action is needed.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20092: No PimRecordDescription data is provided in this record**

**Cause:** This string is never logged by itself but is only ever appended, to another primary logged message string, to provide ancillary information. The primary message may be an error or may simply be a debug message. This message indicates that PimRecordDescription information is not available, for a PIM record, because the PimRecordDescription object is null.

**Action:** See the log for the primary logged message to determine whether any action is needed.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20093: A null field name is detected for a PimRecordDescription field name.**

**Cause:** This message string indicates that a field name is null within the PimRecordDescription metadata of a PIM record. This string is never logged by itself but is only ever appended to another primary logged message string. The primary message may be an error or may simply be a debug message.

**Action:** See the log for the primary logged message to determine whether any action is needed for the primary log message. Also, fix the cause that is producing this null field name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20094: ErrorCode**



---

**Cause:** This message string is a label that identifies an error code. This string is never logged by itself but is only ever appended to another primary logged message string. The primary message may be an error or may simply be a debug message.

**Action:** See the log for the primary logged message to determine whether any action is needed for the primary log message.

**Level:** 1

**Type:** ERROR

**Impact:** Other

#### **BDSS-20095: Hub Domain**

**Cause:** This message string is a label that identifies a hub domain identifier. This string is never logged by itself but is only ever appended to another primary logged message string. The primary message may be an error or may simply be a debug message.

**Action:** See the log for the primary logged message to determine whether any action is needed for the primary log message. No action is needed based on this message alone.

**Level:** 1

**Type:** ERROR

**Impact:** Other

#### **BDSS-20096: Hub User**

**Cause:** This message string is a label that identifies a hub user ID. This string is never logged by itself but is only ever appended to another primary logged message string. The primary message may be an error or may simply be a debug message.

**Action:** See the log for the primary logged message to determine whether any action is needed for the primary log message. No action is needed based on this message alone.

**Level:** 1

**Type:** ERROR

**Impact:** Other

#### **BDSS-20097: SessionID**

**Cause:** This message string is a label that identifies a user synchronization session ID. This string is never logged by itself but is only ever appended to another primary logged message string. The primary message may be an error or may simply be a debug message.

**Action:** See the log for the primary logged message to determine whether any action is needed for the primary log message. No action is needed based on this message alone.

**Level:** 1

**Type:** ERROR

**Impact:** Other

#### **BDSS-20098: Connector user**

---

**Cause:** This message string is a label that identifies a Connector user ID. This string is never logged by itself but is only ever appended to another primary logged message string. The primary message may be an error or may simply be a debug message.

**Action:** See the log for the primary logged message to determine whether any action is needed. No action is needed based on this message alone.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BDSS-20099: Connector Name**

**Cause:** This message string is a label that identifies a PIM connector name. This string is never logged by itself but is only ever appended to another primary logged message string. The primary message may be an error or may simply be a debug message.

**Action:** See the log for the primary logged message to determine whether any action is needed. No action is needed based on this message alone.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**BDSS-20100: PIM Record Id**

**Cause:** This message string is a label that identifies a PIM record ID. This string is never logged by itself but is only ever appended to another primary logged message string. The primary message may be an error or may simply be a debug message.

**Action:** See the log for the primary logged message to determine whether any action is needed for the primary log message. No action is needed based on this message alone.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BDSS-20102: Error detected when attempting to delete BDSS master hub metadata record {0}.**

**Cause:** This message indicates that an exception occurred when attempting to delete a hub metadata record from the BDSS database. In particular, method `SyncConfig::deleteHubMapRecord` threw an exception. The cause of the exception is logged with this message.

**Action:** See the log to find the exception cause that is logged with this message.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20103: Failed to delete an BDSS Pim-Map metadata record corresponding to specified PIM record.**

**Cause:** This message indicates that an exception occurred when attempting to delete a PIM map record from the BDSS database. In particular, method

---

SyncConfig::deletePimMapRecord threw an exception. The cause of the exception is logged with this message.

**Action:** See the log to find the exception cause that is logged with this message.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-20104: Hub domain synchronization succeeded.**

**Cause:** This is an informational message that indicates that synchronization has succeeded. The hub-user, sync-session ID, Connector and hub-domain are logged with this message.

**Action:** No action needed.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**BDSS-20106: Started synchronization for user**

**Cause:** This is an informational message that indicates when a synchronization session has started for a hub user. The hub user is specified in the log message header.

**Action:** No action needed.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**BDSS-20107: A user synchronization session has ended. User sync status is {0}.**

**Cause:** This is an informational message that indicates when a hub user synchronization session has ended. In particular, the call to method SyncConfig::setUserSyncSessionToEnded has succeeded. This notification does not imply whether domain synchronization succeeded or not for this same synchronization session. The hub user is specified in the log message header.

**Action:** No action needed.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**BDSS-20108: Failed to end a user synchronization session.**

**Cause:** This error message indicates that a hub user synchronization session did not end successfully. In particular, the call to method SyncConfig::setUserSyncSessionToEnded threw an exception. This error does not imply whether domain synchronization succeeded or not for this same synchronization session. The hub user is specified in the log message header.

**Action:** No specific action recommended. However, check configuration - perhaps for the hub user in particular. Also suggest restarting the BDSS application server, or reinstalling BDSS.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**BDSS-20109: Hub-domain {0} will not be synchronized for Connector {1} because no other Connector is configured to synchronize it for the current hub-user.**

**Cause:** Hub-user configuration, for the specified hub-domain, is set to synchronize the hub-domain using only a single Connector. It is invalid to synchronize a hub-domain by only a single Connector. The Sync-Engine has modified its only local copy of configuration, for the current hub-user sync-session, so that it will not synchronize the specified hub-domain for the current hub-user sync-session.

**Action:** Fix configuration for the specified hub-user so that the specified hub-domain is configured to synchronize by more than one Connector. Alternatively, remove the specified hub-domain from configuration for the specified hub-user.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**BDSS-20110: Connector {0} will not be synchronized, for the current hub-user sync-session, because it is not configured to synchronize any hub-domains.**

**Cause:** The Sync-Engine has determined that hub-user configuration, for the specified Connector, is not valid because it is not configured to synchronize any hub-domains. The specified Connector will not be allowed to synchronize for the current hub-user sync-session.

**Action:** Ensure that configuration, for the specified hub-user and Connector, is correct for synchronizing at least one hub-domain with another Connector.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**BDSS-30001: The engine setting for {0} is invalid.**

**Cause:** The Engine Settings for this parameter are invalid.

**Action:** Use the EngineSettings MBean to enter a valid value for this parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-30003: Error during construction of SyncConfig. {0}**

**Cause:** There was an out of memory error or SyncConfig cannot get EngineSettings MBean.

**Action:** Verify that the EngineSettings MBean was deployed or verify that there was sufficient memory.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BDSS-30006: Cannot find section {0} in profile {1}.**

---

**Cause:** The configuration data for that profile and section cannot be retrieved from the data store.

**Action:** Verify that the profile and section exist in the data store and that the data store can be reached.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BDSS-30007: EngineSettings - error loading settings. {0}**

**Cause:** Cannot find the engine settings in the preferences store or cannot load the preferences store.

**Action:** Verify that the preferences store exist on the server and that it is accessible.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-30011: A {0} was detected when attempting to set the {1} configuration option. {2}**

**Cause:** Cannot find the engine settings in the preferences store, cannot load the preferences store or cannot write to the preferences store.

**Action:** Verify that the preferences store exist on the server and that it is accessible.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-30012: A {0} was detected when attempting to invoke the MBean operation. {1}**

**Cause:** The BDSS MBeans are not accessible or were not successfully installed.

**Action:** Using the Application Server administration UI, verify that the BDSS MBeans were installed correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-30013: A {0} was detected when converting profile data: Profile = {1}, Section = {2}, Parameter = {3}, Value = {4}.**

**Cause:** There was an error converting the Profile settings returned from the database to a format that will display properly.

**Action:** Try the operation again. If the error persists, check the data in the database or reinstall the Profile Settings MBean.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-30014: Failed to build open mbeaninfo.**

---

**Cause:** There was an error loading the MBeans.

**Action:** Try restarting the MBean console or reinstalling the MBeans.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-30015: Operation name cannot be null.**

**Cause:** There was an error loading the MBeans because an operation name was null.

**Action:** Try reinstalling the MBeans.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-30016: Cannot call invoke with null operation name.**

**Cause:** There was an error loading the MBeans because an operation name was null.

**Action:** Try reinstalling the MBeans.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-30017: An error occurred when invoking MBean operation {0}. Exception Class Name = {1}. Caught [{2}].**

**Cause:** There was an error running the operation.

**Action:** Try the operation again. If the error persists, check the data in the database or reinstall the MBeans.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-30018: Cannot find MBean operation {0}.**

**Cause:** There was an error finding the MBean operation.

**Action:** Try the operation again. If the error persists, using the Application Server administration UI, verify that the BDSS MBeans were installed correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-30019: Cannot invoke operation {0} because an invalid parameter was provided to the MBean.**

**Cause:** An invalid parameter was given to the MBean.

**Action:** Try the action again with valid parameters. If the error continues, contact Oracle Support Services..

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**BDSS-30020: Error converting the server map. {0}**

**Cause:** There was an error converting the server map returned from the database to a format that will display properly.

**Action:** Try the operation again. If the error persists, check the data in the database or reinstall the Server and Connectors MBean.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-30021: Error converting the connector map. {0}**

**Cause:** There was an error converting the connector map returned from the database to a format that will display properly.

**Action:** Try the operation again. If the error persists, check the data in the database or reinstall the Server and Connectors MBean.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-30022: Error getting hub users. {0}**

**Cause:** This may be an error in the configuration of the Hub User or the Hub User does not exist.

**Action:** Ensure that the hub user exists in configuration and is configured correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-30023: Error getting Connector users. {0}**

**Cause:** This may be an error in the configuration of the Connector user or the Connector user does not exist.

**Action:** Ensure that the Connector user exists in configuration and is configured correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-30024: Error getting domains. {0}**

**Cause:** This may be an error in the configuration of the domain.

**Action:** Ensure that the domain exists in configuration and is configured correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**BDSS-30025: Error getting records. {0}**

**Cause:** This may be an error in the database for the record.

**Action:** Ensure that the record exists in the database.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35001: Cannot create a Connector user with the login {0} and cannot map the user to the hub user {1}.**

**Cause:** The data store was not accessible or the record does not exist in configuration.

**Action:** Ensure your data store is running and you can log in to it from a client and that the record exists in configuration

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35002: The configuration parameter {0} in the section {1} of the profile {2} cannot be deleted.**

**Cause:** The configuration was not accessible.

**Action:** Ensure your database is running and you can log in to it from a client.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35003: Cannot delete the record with an id of {0}.**

**Cause:** The data store was not accessible or the user does not exist in configuration.

**Action:** Ensure your data store is running and you can log in to it from a client and that the user exists in configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35004: Cannot find the hub record with an id of {0} for user {1}.**

**Cause:** The data store was not accessible or the user or record does not exist in configuration.

**Action:** Ensure your data store is running and you can log in to it from a client and that the user and record exist in configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35005: Cannot find the hub record for the PIM record with an id of {0} for user {1}.**



---

**Cause:** The data store was not accessible or the record does not exist in configuration.

**Action:** Ensure your data store is running and you can log in to it from a client and that the record exists in configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35006: Cannot find the hub user {0}.**

**Cause:** The data store was not accessible or the user does not exist in configuration.

**Action:** Ensure your data store is running and you can log in to it from a client and that the hub user exists in configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35007: Cannot find the {0} LOV with a value of {1}.**

**Cause:** The data store was not accessible or the record does not exist in configuration.

**Action:** Ensure your data store is running and you can log in to it from a client and that the record exists in configuration

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35008: Cannot find the {0} object with an id of {1}.**

**Cause:** The data store was not accessible or the record does not exist in configuration.

**Action:** Ensure your data store is running and you can log in to it from a client and that the record exists in configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35009: Cannot find the PIM record with an id of {0}.**

**Cause:** The data store was not accessible or the user or record does not exist in configuration.

**Action:** Ensure your data store is running and you can log in to it from a client and that the user and record exist in configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35010: Cannot find the PIM record with an id of {0} for user {1}.**

---

**Cause:** The data store was not accessible or the user or record does not exist in configuration.

**Action:** Ensure your data store is running and you can log in to it from a client and that the user and record exist in configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35011: Cannot find the PIM record for the hub record with an id of {0} for user {1}.**

**Cause:** The data store was not accessible or the record does not exist in configuration.

**Action:** Ensure your data store is running and you can log in to it from a client and that the record exists in configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35012: Cannot find the Connector user with the ID of {0} for the Connector named {1}.**

**Cause:** The data store was not accessible or the record does not exist in configuration.

**Action:** Ensure your data store is running and you can log in to it from a client and that the record exists in configuration

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35013: Cannot find the record associated data for the record {0}.**

**Cause:** The data store was not accessible or the user or record data does not exist in configuration.

**Action:** Ensure your data store is running and you can log in to it from a client and that the user and record exist in configuration.

**Level:** 32

**Type:** TRACE

**Impact:** Configuration

**BDSS-35014: Cannot return users from the data source.**

**Cause:** The data store was not accessible or the record does not exist in configuration.

**Action:** Ensure your data store is running and you can log in to it from a client and that the record exists in configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**BDSS-35015: Cannot retrieve {0} records for user {1}.**

**Cause:** The data store was not accessible or the user does not exist in configuration.

**Action:** Ensure your data store is running and you can log in to it from a client and that the user exists in configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35016: Cannot remove the {0} object with an id of {1}.**

**Cause:** The data store was not accessible or the record does not exist in configuration.

**Action:** Ensure your data store is running and you can log in to it from a client and that the record exists in configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35017: Cannot update the sync level for the domain {0} for the Connector named {1}.**

**Cause:** The data store was not accessible or the record does not exist in configuration.

**Action:** Ensure your data store is running and you can log in to it from a client and that the record exists in configuration

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35018: Cannot update the hub record with an id of {0} for user {1}.**

**Cause:** The data store was not accessible or the record does not exist in configuration.

**Action:** Ensure your data store is running and you can log in to it from a client and that the record exists in configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35019: Cannot update or create the {0} object with an id of {1}.**

**Cause:** The data store was not accessible or the record does not exist in configuration.

**Action:** Ensure your data store is running and you can log in to it from a client and that the record exists in configuration

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**BDSS-35020: Cannot update the PIM record with an id of {0} for user {1}.**

**Cause:** The data store was not accessible or the record does not exist in configuration.

**Action:** Ensure your data store is running and you can log in to it from a client and that the record exists in configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35021: Cannot update the session for hub user {0}.**

**Cause:** The user cannot be found in configuration or the data store is not allowing the update.

**Action:** Ensure your data store is running and you can log in to it from a client and that the hub user exists in configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35022: The configuration parameter {0} in the section {1} of the profile {2} cannot be written to the data store.**

**Cause:** The configuration was not accessible or cannot be written to.

**Action:** Ensure your database is running and you can log in to it from a client.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35023: Cannot store record associated data for the record with an id of {0}.**

**Cause:** The data store was not accessible or the user does not exist in configuration.

**Action:** Ensure your data store is running and you can log in to it from a client and that the user exists in configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35024: Cannot store record description data for the record with an id of {0}.**

**Cause:** The data store was not accessible or the user or record does not exist in configuration.

**Action:** Ensure your data store is running and you can log in to it from a client and that the user and record exist in configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35025: Cannot write user associated data for user {0}.**

**Cause:** The data store was not accessible or cannot be written to.

---

**Action:** Ensure your data store is running and you can log in to it from a client.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35026: Cannot write the {0} domain sync status for user {1} on the Connector named {2}.**

**Cause:** The data store was not accessible or cannot be written to or configuration for this user is corrupted.

**Action:** Ensure your data store is running and you can log in to it from a client. Also ensure the configuration for this user is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35027: The configuration for the Connector {0} has an error.**

**Cause:** There is an error in the configuration of this Connector.

**Action:** Review the configuration for this Connector and resolve the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35028: The configuration for the domain {0} has an error.**

**Cause:** There is an error in the configuration of this domain.

**Action:** Review the configuration for this domain and resolve the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35029: One of the Connector user mappings is invalid for hub user {0}.**

**Cause:** The configuration for one of the hub user to Connector user mappings is corrupted or not present.

**Action:** Ensure that the mapping exists in configuration and is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35030: The configuration for the Connector instance {0} is not correct. Review the configuration for {1}.**

**Cause:** There was missing configuration for this Connector instance.

**Action:** Review the configuration for this Connector instance and correct any configuration problems.

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**BDSS-35031: The configuration for the PIM domain {0} is not correct. Review the configuration for {1}.**

**Cause:** There was missing configuration for this domain.

**Action:** Review the configuration for this domain and correct any configuration problems.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35032: The configuration for the user {0} is not correct. Review the configuration for the user on Connector {1}.**

**Cause:** There was missing configuration for this user.

**Action:** Review the configuration for this user and correct any configuration problems.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35033: The Connector user for Connector {0} does not exist for hub user {1}, or there is more than one Connector user with this name configured for this Connector.**

**Cause:** This hub user had no Connector user associated to it for the Connector.

**Action:** Review the configuration for this user and correct any configuration problems.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35034: The configuration for the Connector {0} is not correct. Review the configuration for {1}.**

**Cause:** There was missing configuration for this Connector.

**Action:** Review the configuration for this Connector and correct any configuration problems.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35035: The configuration for the profile {0} is does not exist. Review the configuration for the profile.**

**Cause:** There was missing configuration for this profile.

**Action:** Review the configuration for this profile and correct any configuration problems if needed.

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**BDSS-35036: The configuration parameter {0} in the section {1} of the profile {2} does not exist.**

**Cause:** There was missing configuration for this profile.

**Action:** Review the configuration for this profile and correct any configuration problems if needed.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35037: There is no {0} for the user {1}.**

**Cause:** There was missing configuration for this user.

**Action:** Review the configuration for this user and correct any configuration problems.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35038: The configuration for the PIM server {0} has an error.**

**Cause:** There is an error in the configuration of this PIM server.

**Action:** Review the configuration for this PIM server and resolve the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35039: A Connector user with a login of {0} already exists for the Connector {1}.**

**Cause:** The configuration for at least one of the Connector users already exists. Verify this user is not already in configuration and that this is the correct ID for the Connector.

**Action:** Ensure that the mapping exists in configuration and is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35040: The user is not in the same session whose ID is {0}.**

**Cause:** The session ID for the user is not the same as the stored session ID. This may be due to 2 separate BDSS engines processing the same user.

**Action:** Ensure only one BDSS dispatcher is running at a time and that the user is not stuck in a sync session.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35041: Cannot store associated data for the user {0}.**

---

**Cause:** The data store was not accessible or the user does not exist in configuration.

**Action:** Ensure your data store is running and you can log in to it from a client and that the user exists in configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35042: Cannot store metadata for the user {0}.**

**Cause:** There was an error while storing the configuration of this user.

**Action:** Verify the database can be accessed and that the BDSS configuration is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35043: Cannot store a record for the user {0}.**

**Cause:** The data store was not accessible or the user does not exist in configuration.

**Action:** Ensure your data store is running and you can log in to it from a client and that the user exists in configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35044: There were too many {0} records found for {1}.**

**Cause:** There were too many records found that matched the query.

**Action:** Ensure your configuration is correct and that the user's data is not corrupted

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35045: The configuration for the user {0} has an error.**

**Cause:** There is an error in the configuration of this user.

**Action:** Review the configuration for this user and resolve the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35046: Cannot find the associated data for user {0}.**

**Cause:** The associated data for the user is not in the database.

**Action:** This may not be an error if this is the first time sync for the user. If not, verify the user is in the database and the database is accessible.

**Level:** 1



---

**Type:** ERROR

**Impact:** Configuration

**BDSS-35051: Cannot store the cached sync state for the user {0}.**

**Cause:** There was an error while storing the cached sync state of this user.

**Action:** Verify the database can be accessed, that the BDSS configuration is correct and the cached sync state exists.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-35052: Cannot store the permanent sync state for the user {0}.**

**Cause:** There was an error while storing the permanent sync state of this user.

**Action:** Verify the database can be accessed, that the BDSS configuration is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-35053: Could not obtain the Pim Record Versions for Connector User {0}, HubDomain {1}, Connector {2}. Exception detected: {3}.**

**Cause:** There was an error while attempting to obtain the Pim Record Version identifiers from the BDSS database for this user.

**Action:** Verify the database can be accessed and that the BDSS configuration is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-35054: An invalid Connector domain synchronization level has been detected.**

**Cause:** An invalid Connector domain synchronization level has been detected in configuration.

**Action:** Review Connector domain synchronization level configuration and correct it.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35055: An invalid Connector user synchronization level has been detected.**

**Cause:** An invalid Connector user synchronization level has been detected in configuration.

**Action:** Review Connector user synchronization level configuration and correct it.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**BDSS-35057: There is more than one record with the Hub user login of {0}.**

**Cause:** There is more than one hub user with this login. This is a configuration error.

**Action:** Review the configuration for this user and correct any configuration problems.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35063: Cannot find the domain {0} for Connector user Id {1}.**

**Cause:** The supplied domain does not exist for the Connector user. This could be a configuration error.

**Action:** Review the configuration for this user and correct any configuration problems.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35070: Cannot find the PIM server instance {0} for Connector {1}.**

**Cause:** Cannot update the PIM server instance. This could be a configuration error.

**Action:** Review the configuration for this PIM server instance and correct any configuration problems.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**BDSS-35071: Cannot find the domain {0} for the Connector named {1}.**

**Cause:** Cannot update the domain. This could be a configuration error.

**Action:** Review the configuration for this domain and correct any configuration problems.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**BDSS-35072: Cannot update the filter {0} for the domain {1} for the Connector named {2}.**

**Cause:** Cannot update the domain filter. This could be a configuration error.

**Action:** Review the configuration for this domain and correct any configuration problems.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35073: Cannot find the LOV for the PIM server type {0}.**

---

**Cause:** Cannot find the LOV for the PIM server type. This could be a configuration error.

**Action:** Review the LOVs, ensure you are using the correct LOV and correct any configuration problems.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35074: Cannot create or update the connector {0}.**

**Cause:** Cannot create or update the connector. This could be a configuration error or a database access error.

**Action:** Review the configuration and database connect information. Then correct any configuration problems.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35075: Cannot delete the connector {0}.**

**Cause:** Cannot delete the connector. This could be a configuration error or a database access error.

**Action:** Review the configuration and database connect information. Then correct any configuration problems.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35077: Cannot delete the filter {0} for the domain {1} for the Connector named {2}.**

**Cause:** Cannot delete the domain filter. This could be a configuration error.

**Action:** Review the configuration for this domain and correct any configuration problems.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35078: Cannot get connector details.**

**Cause:** Cannot get the details for the connectors. This could be a configuration error or a database access error.

**Action:** Review the configuration and database connect information. Then correct any configuration problems.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35079: Error converting the connector instance map. {0}**

---

**Cause:** There was an error converting the connector instance map returned from the database to a format that will display properly.

**Action:** Try the operation again. If the error persists, check the data in the database or reinstall the Servers and Connectors MBean.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35080: Error converting the domain map. {0}**

**Cause:** There was an error converting the domain map returned from the database to a format that will display properly.

**Action:** Try the operation again. If the error persists, check the data in the database or reinstall the Servers and Connectors MBean.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35081: Error converting the domain filter map. {0}**

**Cause:** There was an error converting the domain filter map returned from the database to a format that will display properly.

**Action:** Try the operation again. If the error persists, check the data in the database or reinstall the Servers and Connectors MBean.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35083: Missing configuration for PROFILE\_NAME = {0}, SECTION\_NAME = {1}, PARAMETER name = {2}.**

**Cause:** A required configuration record does not exist in database table PROFILES for the criteria specified in the log message.

**Action:** Review the configuration for this profile and correct any configuration problems. In particular, ensure that a record exists for the specified criteria.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-35084: Invalid configuration value for an existing record in database PROFILES table for PROFILE\_NAME = {0}, SECTION\_NAME = {1}, PARAMETER name = {2}.**

**Cause:** The content of the VALUE column is invalid for a record in the database PROFILES table that matches the specified profile name, section name and parameter name.

**Action:** Review the configuration for matching profile record and correct any configuration problems. In particular, ensure the database VALUE column is populated correctly for matching record.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**BDSS-35085: Cannot remove temporary sync state for Connector user = {0}, Connector Name = {1}, Hub Domain = {2}.**

**Cause:** The Sync-Engine cannot remove old state data for the specified Connector user, Connector and Hub Domain. This problem is unexpected and should not occur under normal operating conditions. This error message signifies a database access error which could be caused by a database deadlock or inability to contact the database.

**Action:** Examine the log for evidence of exception text that will give more specific information as to the cause of the problem. Ensure that all infrastructure, such as the database and network, are working correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-35086: Cannot create a UserContextState for Connector user = {0}, Connector Name = {1}, Hub Domain = {2}.**

**Cause:** The Sync-Engine cannot create a record in the database to save the sync state for the specified Connector user, Connector and Hub Domain. This problem is unexpected and should not occur under normal operating conditions. This error message signifies a database access error which could be caused by a database deadlock or inability to contact the database.

**Action:** Examine the log for evidence of exception text that will give more specific information as to the cause of the problem. Ensure that all infrastructure, such as the database and network, are working correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-35087: Cannot read history data.**

**Cause:** The Sync-Engine cannot read the history table. This problem is unexpected and should not occur under normal operating conditions. This error message signifies a database access error which could be caused by a database deadlock or inability to contact the database.

**Action:** Examine the log for evidence of exception text that will give more specific information as to the cause of the problem. Ensure that all infrastructure, such as the database and network, is working correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-60001: Unable to get the connector instance web service URL.**

**Cause:** Unknown. See recommended action.

**Action:** Examine the log and, if available, especially the stack trace and exception cause chain for the cause.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**BDSS-60002: An error occurred in connector interface method {0}.**

**Cause:** Unknown. See recommended action.

**Action:** Examine the log, especially the stack trace and exception cause chain for the cause.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BDSS-60003: Parameter {0} is null.**

**Cause:** The specified Java method argument is null.

**Action:** Examine the exception stack trace to determine which method failed.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BDSS-60004: Parameter {0} is an empty String object.**

**Cause:** The specified Java method argument is an empty String object.

**Action:** Examine the exception stack trace to determine which method failed.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BDSS-60005: Parameter {0} is an empty List object.**

**Cause:** The specified Java method argument is an empty List object.

**Action:** Examine the exception stack trace to determine which method failed.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BDSS-60006: Method failed with result {0}.**

**Cause:** May be caused by a failure in RuntimeLibraryWrapper methods setUserAssociatedData or setRecordAssociatedData.

**Action:** The caller of the RuntimeLibraryWrapper method must examine the returned Map to determine the particular failure details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BDSS-60007: Failed to build a record description field list. The value for hub field {0} is not available.**

**Cause:** The specified hub field value could not be found when creating a record field description list.

**Action:** Review configuration for record description fields.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-60008: PIM Transport provided too many PimExtractResponse objects.**

**Cause:** More than one PimExtractResponse objects have been received by the generic connector component.

**Action:** Ensure the PimTransport only provides a single PimExtractResponse to the generic connector component.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BDSS-60009: Failed to load PIM transport class {0}**

**Cause:** The generic connector component failed to load the specified PIM transport adapter class.

**Action:** Ensure that the PIM transport adapter class is configuration and deployed correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-60010: Failed to find PIM transport class name for the following configuration parameters. ConnectorName = {0}, Section = {1}, Parameter = {2}**

**Cause:** The generic connector component failed to find the specified PIM transport adapter class in configuration.

**Action:** Ensure that configuration specifies the correct PIM transport adapter class name.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-60011: Cannot get PimDomainInfo using arguments syncSessionId {0} and pimUserId = {1}**

**Cause:** Internal corruption in the generic connector.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BDSS-60012: Cannot find PimDomainInfo using arguments syncSessionId {0}, pimUserId = {1} and hubDomainName = {2}**

**Cause:** Internal corruption in the generic connector.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BDSS-60013: Failed to extract. Sending an error ExtractResponse to the hub.**

**Cause:** Internal corruption in the generic connector.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BDSS-60014: Failed an attempt to exceed the allowable ExtractResponse batch size.**

**Cause:** A PIM Transport has attempted to exceed the maximum ExtractResponse batch size allowed for a PimExtractResponse object.

**Action:** Examine the exception stack trace, in the log, to determine whether failure occurred when adding a delete-record event or an upsert-record event to the PimExtractResponse cache. Fix the PIM Transport so it doesn't exceed the allowable maximum batch size.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BDSS-60016: Configuration value not found for the following configuration parameters. Profile = {0}, Section = {1}, Parameter = {2}**

**Cause:** The generic connector component cannot find a configuration value in the BDSS database for the specified profile name, section name and parameter name.

**Action:** Ensure that configuration exists in the BDSS database for the specified profile name, section name and parameter name..

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-60018: Error Code**

**Cause:** This message string is a label that identifies an error code. This string is never logged by itself but is only ever appended to another primary logged message string. The primary message may be an error or may simply be a debug message.

**Action:** See the log for the primary logged message to determine whether any action is needed for the primary log message.

**Level:** 32

**Type:** TRACE

**Impact:** Logging

**BDSS-60019: Hub Domain**

**Cause:** This message string is a label that identifies a hub domain identifier. This string is never logged by itself but is only ever appended to another primary logged message string. The primary message may be an error or may simply be a debug message.



---

**Action:** See the log for the primary logged message to determine whether any action is needed for the primary log message. No action is needed based on this message alone.

**Level:** 32

**Type:** TRACE

**Impact:** Logging

**BDSS-60020: Hub User**

**Cause:** This message string is a label that identifies a hub user ID. This string is never logged by itself but is only ever appended to another primary logged message string. The primary message may be an error or may simply be a debug message.

**Action:** See the log for the primary logged message to determine whether any action is needed for the primary log message. No action is needed based on this message alone.

**Level:** 32

**Type:** TRACE

**Impact:** Logging

**BDSS-60021: SessionID**

**Cause:** This message string is a label that identifies a user synchronization session ID. This string is never logged by itself but is only ever appended to another primary logged message string. The primary message may be an error or may simply be a debug message.

**Action:** See the log for the primary logged message to determine whether any action is needed for the primary log message. No action is needed based on this message alone.

**Level:** 32

**Type:** TRACE

**Impact:** Logging

**BDSS-60022: Connector user**

**Cause:** This message string is a label that identifies a Connector user ID. This string is never logged by itself but is only ever appended to another primary logged message string. The primary message may be an error or may simply be a debug message.

**Action:** See the log for the primary logged message to determine whether any action is needed. No action is needed based on this message alone.

**Level:** 32

**Type:** TRACE

**Impact:** Logging

**BDSS-60023: Connector Name**

**Cause:** This message string is a label that identifies a PIM connector name. This string is never logged by itself but is only ever appended to another primary logged message string. The primary message may be an error or may simply be a debug message.

---

**Action:** See the log for the primary logged message to determine whether any action is needed. No action is needed based on this message alone.

**Level:** 32

**Type:** TRACE

**Impact:** Logging

**BDSS-60024: PIM Record Identifier**

**Cause:** This message string is a label that identifies a PIM record ID. This string is never logged by itself but is only ever appended to another primary logged message string. The primary message may be an error or may simply be a debug message.

**Action:** See the log for the primary logged message to determine whether any action is needed for the primary log message. No action is needed based on this message alone.

**Level:** 32

**Type:** TRACE

**Impact:** Logging

**BDSS-60025: Version Identifier**

**Cause:** This message string is a label that identifies a PIM record version identifier. This string is never logged by itself but is only ever appended to another primary logged message string. The primary message may be an error or may simply be a debug message.

**Action:** See the log for the primary logged message to determine whether any action is needed for the primary log message. No action is needed based on this message alone.

**Level:** 32

**Type:** TRACE

**Impact:** Logging

**BDSS-65001: Could not find Exchange account information for the user.**

**Cause:** Secure Socket Layer (SSL) handshaking failed.

**Action:** Ensure the Certificate Authority (CA) that issued the server certificate is installed as a trusted CA in the Web Logic Server Key Store.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-65003: The following configuration is invalid. Profile = {0}. Section = {1}. Parameter {2}. Using default value {3}.**

**Cause:** The configuration exists in the BDSS data store, but contains an invalid value.

**Action:** Modify the value and restart BDSS to use a value other than the default.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**BDSS-65004: Failed to read configuration profile. {0}.**

**Cause:** The profile does not exist in the BDSS data store or is misspelled.

**Action:** Ensure the profile name is spelled correctly. Verify the case of the profile name is correct and that space characters exist where they are expected. Restart BDSS.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-65005: Failed to read configuration section. Profile = {0}, Section = {1}.**

**Cause:** The section does not exist in the specified profile in the BDSS data store or is misspelled.

**Action:** Ensure the section and profile names are spelled correctly. Verify the case of the profile and section name are correct and that space characters exist where they are expected. Restart BDSS.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-65006: Failed to read configuration parameter. Profile = {0}, Section = {1}, Parameter = {2}.**

**Cause:** The parameter does not exist in the specified section and profile in the BDSS data store or is misspelled.

**Action:** Ensure the parameter, section, and profile names are spelled correctly. Verify the case of the parameter, section and profile are correct and that space characters exist where they are expected. Restart BDSS.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-65007: The domain XSD file has an invalid attribute value. XSD file {0}. Attribute Name = {1}. Attribute Value = {2}. Using default value of {3}.**

**Cause:** The XSD for the domain has a XML attribute that contains an invalid value.

**Action:** Modify the specified XSD attribute and restart the connector.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-65009: Failed to get a multi-valued group (MVG) field from the domain XSD. XSD file {0}. MVG Field Name = {1}.**

**Cause:** The XSD for the domain has an invalid definition for a multi-valued group field name causing the connector to fail when parsing the XSD.

**Action:** Update the specified MVG field definition in the specified XSD file.

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**BDSS-65010: Failed to add domain target for the user during session. Domain Target = {0}**

**Cause:** The user does not have an Exchange account.

**Action:** Verify the user has a valid Exchange account and that the user can be discovered by the Microsoft Auto Discovery service.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-65011: "The XML schema, {0}, is invalid.**

**Cause:** The XSD does not define any valid field definitions.

**Action:** Add at least one field definition to the XSD and restart BDSS.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-65012: Failed to get a field value from the Exchange record. Field Name = {0}.**

**Cause:** The field contains a value that cannot be converted to a value acceptable to BDSS.

**Action:** Modify the field value in Exchange and synchronize the user again.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-65013: Failed to set a Exchange record field value. Field Name = {0}. Field Value(s) = {1}.**

**Cause:** The field contains a value that cannot be converted to a value acceptable to Exchange Web Service.

**Action:** Modify the value in the source Pim and attempt to synchronize the user again.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-65014: Failed to convert a PimUpsertRecord to an Exchange {0}.**

**Cause:** The connector could not convert a field value it received from the BDSS Engine to an equivalent Exchange Web Service form.

**Action:** This error occurs when the connector converts a record it receives from BDSS. Examine the log for the underlying error that is expected to have been logged prior to this error message. Take appropriate action once the underlying error has been identified.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**BDSS-65015: Failed to initialize a synchronization session for the Pim User.**

**Cause:** If domain targets are correctly configured for each domain for the user, then this error indicates the folder manager could not begin a folder session for the synchronization session.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-65016: Failed to extract the domain.**

**Cause:** This error occurs when the connector fails to extract a domain.

**Action:** Examine the log for the underlying error that is expected to have been logged prior to this error message. Take appropriate action once the underlying error has been identified.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-65017: Failed to get all the records for the domain and user.**

**Cause:** This error occurs when the connector fails to obtain the record identifiers of all the records in Exchange for the user and domain.

**Action:** Examine the log for the underlying error that is expected to have been logged prior to this error message. Take appropriate action once the underlying error has been identified.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-65018: Failed to create an Exchange record.**

**Cause:** This error occurs when the connector fails to create an Exchange record for the user and domain.

**Action:** Examine the log for the underlying error that is expected to have been logged prior to this error message. Take appropriate action once the underlying error has been identified.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-65019: Failed to update an Exchange record.**

**Cause:** This error occurs when the connector fails to update an Exchange record for the user and domain.

**Action:** Examine the log for the underlying error that is expected to have been logged prior to this error message. Take appropriate action once the underlying error has been identified.

**Level:** 1

**Type:** ERROR

---

**Impact:** Data

**BDSS-65020: Failed to delete an Exchange record.**

**Cause:** This error occurs when the connector fails to delete an Exchange record for the user and domain.

**Action:** Examine the log for the underlying error that is expected to have been logged prior to this error message. Take appropriate action once the underlying error has been identified.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-65021: Failed to end the synchronization session for the user.**

**Cause:** This error occurs when the connector fails to end a synchronization session for the user.

**Action:** Examine the log for the underlying error that is expected to have been logged prior to this error message. Take appropriate action once the underlying error has been identified.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-65022: Failed to create an Exchange context.**

**Cause:** This error occurs when the connector fails to construct an internal Exchange context for the user.

**Action:** Examine the log for the underlying error that is expected to have been logged prior to this error message. Take appropriate action once the underlying error has been identified.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-65023: Failed to initialize the Exchange 2007 Pim Transport.**

**Cause:** The Pim Transport component could not be initialized.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-65024: Could not obtain the folder id for Pim User {0}.**

**Cause:** The connector could not find the folder id for the user.

**Action:** Verify the user has a valid domain target configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**BDSS-65025: Received a error from an Exchange Web Service call. Response Code = {0}. Response message: {1}. {2}**

**Cause:** The Exchange Web Service returned an error.

**Action:** Examine the response code and response message and consult Microsoft documentation regarding the error. Take appropriate action to resolve the error and synchronize the user.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-65026: Failed to get the users Exchange server.**

**Cause:** This error occurs when the connector cannot obtain the name of the Exchange 2007 server hosting the user's Exchange account.

**Action:** Verify the user has an Exchange account and that the account is discoverable by the Exchange Auto Discovery service. Consult Microsoft documentation regarding the Auto Discovery service.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-65027: Failed to get the user's Exchange folder identifier for the domain.**

**Cause:** The administrative user accessing the syncing users account does not have sufficient privileges.

**Action:** Ensure the administrative user has full mailbox rights to the syncing users mailbox.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-65028: The domain is not supported.**

**Cause:** The domain class is not supported by the Exchange 2007 connector.

**Action:** Specify the domain class in the XSD as one of 'TaskType', 'ContactItemType' or 'ItemType' and verify all field definitions are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-65029: Failed to get the distinguished folder identifier for the domain.**

**Cause:** The connector could not determine the distinguished folder id for the domain.

**Action:** Ensure the hub domain is either 'Task', 'Contact', or 'Calendar'.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-65030: Failed to get the item id for a record from the BDSS data store.**

---

**Cause:** Accessing the Connector Runtime Library failed or the BDSS data store is not accessible.

**Action:** Verify the BDSS data store and the Connector Runtime Library services are both online and available and resynchronize the user.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-65031: Failed to create or find the Exchange folder to synchronize for domain target {0}.**

**Cause:** Invalid domain target configuration.

**Action:** Fix the domain target configuration for the user.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-65032: Failed to create the Exchange folder {0}.**

**Cause:** The Exchange Web Service method 'createFolder' returned an error when the connector attempted to create a subfolder.

**Action:** Examine the Exchange error and consult Microsoft Exchange Web Service documentation to resolve the error.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-65033: Failed to get the Exchange Web Service URL for the user.**

**Cause:** The user's Exchange Web Server URL could not be obtained.

**Action:** Verify the user has an Exchange account and that the account is discoverable by the Exchange Auto Discovery service. Consult Microsoft documentation regarding the Auto Discovery service.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-65044: Configuration value is invalid and will be ignored. Profile = {0}, Section = {1}, Parameter = {2}, Value = {3}.**

**Cause:** This warning occurs when the connector profile has invalid Active Directory 'ServerN' or Auto Discovery 'SCPN' configuration where N represents an ordinal greater than or equal to 0.

**Action:** Reconfigure the section(s) and restart BDSS.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**BDSS-65045: Failed to generate ordered list.**



---

**Cause:** This error occurs when the connector fails to generate an ordered list of values in a configuration section.

**Action:** Verify the configuration section is configured correctly and restart BDSS.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**BDSS-65046: Invalid format for e-mail address. The domain is not specified.**

**Cause:** The users Pim User Id is not recognized as a valid SMTP email address.

**Action:** Specify the Pim User Id as a SMTP email address. For example, user1@sample.com

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-65047: There are no auto-discovery attributes available for the user.**

**Cause:** Internal programming error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-65048: Failed to generate Service Connection Point Url. Exception = {0}**

**Cause:** Internal programming error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**BDSS-65050: Failed to get Service Connection Point URLs from Active Directory using path {0}.**

**Cause:** Active Directory does have a 'configurationNamingContext' container object, but it does not contain the appropriate 'serviceBindingInformation' or 'keywords' objects. Note that if multiple Active Directory servers are configured, this error can be ignored if other Active Directory servers are configured correctly.

**Action:** Consult with the Active Directory administrator to resolve the issue.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**BDSS-65054: Failed to create a directory context. Context Factory = {0}, Provider Url = {1}, Referral = {2}, Connect Timeout = {3}, Read Timeout = {4}, Security Principal = {5}, Secure Ldap = {6}, Client Certificate = {7}.**

**Cause:** This error occurs if the connector cannot create an initial directory context.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-65060: Failed to construct a {0} Pim XML record.**

**Cause:** This error occurs when the connector fails to construct a Pim XML record from an Exchange record.

**Action:** Examine the log for the underlying error that is expected to have been logged prior to this error message. Take appropriate action once the underlying error has been identified.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-65061: Failed to convert a Exchange {0} item to a PimUpsertRecord.**

**Cause:** This error occurs when the connector fails to construct a PimUpsertRecord from an Exchange record.

**Action:** Examine the log for the underlying error that is expected to have been logged prior to this error message. Take appropriate action once the underlying error has been identified.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-65062: Failed to create a domain class. Domain = {0}.**

**Cause:** The connector failed to instantiate a domain class for a record.

**Action:** This error occurs when the domain XSD contains an invalid domain class.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-65063: Failed to get the domain target for the user during session.**

**Cause:** The connector could not obtain the user's domain target from a cache. Internal programming error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-65064: The extended field is incorrectly defined or is not allowed by the Exchange Web Service API. DistinguishedPropertySetId = {0}. PropertyId = {1}. PropertyName = {2}. PropertySetId = {3}. PropertyTag = {4}. PropertyType = {5}.**

**Cause:** An extended field is defined incorrectly in the XSD.

**Action:** Consult Microsoft Exchange Web Service documentation for extended field definitions and fix the field definition in the XSD file and then restart BDSS.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**BDSS-65065: The indexed field is incorrectly defined or is not allowed by the Exchange Web Service API. FieldIndex = {0}. Dictionary URI = {1}.**

**Cause:** An indexed field is defined incorrectly in the XSD.

**Action:** Consult Microsoft Exchange Web Service documentation for indexed field definitions and fix the field definition in the XSD file and then restart BDSS.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-65066: The unindexed field is incorrectly defined or is not allowed by the Exchange Web Service API. FieldURI = {0}.**

**Cause:** An unindexed field is defined incorrectly in the XSD.

**Action:** Consult Microsoft Exchange Web Service documentation for unindexed field definitions and fix the field definition in the XSD file and then restart BDSS.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-65067: The Extract Response Batch Size configured value is too small.**

**Cause:** A user has more records in their sync folder than what is allowed by the Extract Response Batch Size.

**Action:** Reconfigure the Extract Response Batch Size to be a large number such that no user has that many records in their folder.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-65068: Failed to get the record metadata from EWS response message.**

**Cause:** The Exchange record does not have a PR\_LAST\_MODIFICATION\_TIME or PR\_SOURCE\_KEY value.

**Action:** Update or re-create the Exchange record and resynchronize the user.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-65069: The domain XSD has an invalid or missing attribute. Attribute name = {0}. Attribute value = {1}.**

**Cause:** The domain XSD contains an error.

**Action:** Examine the XSD file to locate the attribute name and value that is logged. Fix the XSD and restart BDSS.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**BDSS-65070: The XSD field definition could not be resolved to an Exchange field definition.**

**Cause:** A extended field definition in the XSD is configured incorrectly.

**Action:** Consult Microsoft documentation on the PathToExtendedFieldType and Oracle documentation on field definitions for the Exchange 2007 connector and configure the field correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-65071: An index field name is required for indexed fields.**

**Cause:** This error occurs when attempting to obtain a indexed field without specifying an index field name.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-65072: The field definition for field {0} is invalid. It is not defined as a indexed, unindexed or extended field.**

**Cause:** A field definition is incorrect.

**Action:** Fix the field definition and restart BDSS.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-65073: The credential store does not contain the credential key {0}.**

**Cause:** The specified credential key is not obtainable.

**Action:** Configure the credential key and resynchronize the user.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**BDSS-65074: Failed to get the credentials from the credential store. Credential key = {0}.**

**Cause:** The specified credential key is not obtainable.

**Action:** Configure the credential key and resynchronize the user.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**BDSS-65075: Failed to start a folder session for the user.**

**Cause:** At the beginning of a synchronization session, the connector creates a corresponding folder session to cache folder information for the user during the synchronization session. The connector could not start the folder session for the user.

---

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BDSS-65076: Failed to add a folder id to the folder session.**

**Cause:** During a synchronization session, the connector uses a folder session to cache folder information for the user during the synchronization session. The connector could not add a folder id to the folder session for the user.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BDSS-65077: Failed to get a folder id from the folder session.**

**Cause:** During a synchronization session, the connector uses a folder session to cache folder information for the user during the synchronization session. The connector could not get a folder id from the folder session for the user.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BDSS-65078: Failed getting folder information from the folder session.**

**Cause:** During a synchronization session, the connector uses a folder session to cache folder information for the user during the synchronization session. The connector could not get a folder information from the folder session for the user.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BDSS-65079: Failed to get the field value. Field URI = {0}.**

**Cause:** This error occurs when the connector parses a Pim Xml record it receives from the BDSS hub.

**Action:** Verify the configuration for the field in the XSD is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BDSS-65080: Failed to get the calculated fields of the extracted records.**

**Cause:** The connector could not obtain the calculated fields for each extracted record.

**Action:** Verify the configuration of the calculated field is correct and resynchronize the user.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BDSS-65084: Failed to extract the domain because the BDSS-provided synchronization state is invalid. Retrying extraction using an empty synchronization state.**

**Cause:** The synchronization state is corrupted in the BDSS store or does not apply to the domain target for the user.

**Action:** No action is required as the connector will reattempt synchronization using an empty synchronization state.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Data

**BDSS-65086: Ended an existing folder session from a previous synchronization session.**

**Cause:** A call to end a folder session at the end of a previous synchronization session unexpectedly failed.

**Action:** No action is required as the connector will end the existing session and create a new one.

**Level:** 16

**Type:** NOTIFICATION

**Impact:** Data

**BDSS-65087: Failed to remove the domain information from the Url. Url = {0}**

**Cause:** The Url may be malformed.

**Action:** Verify the URL is correct in Active Directory and retry synchronizing the user.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-65088: Failed to close a output stream.**

**Cause:** A stream object could not be closed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-65089: Failed to obtain an Exchange record.**

**Cause:** The Exchange server may have not be available.

**Action:** Resynchronize the user.

**Level:** 1

**Type:** ERROR

---

**Impact:** Data

**BDSS-65090: The Hub Domain is not supported.**

**Cause:** The Hub domain is not supported by the Exchange connector.

**Action:** Ensure the Hub domain is either 'Task', 'Contact' or 'Calendar' and restart BDSS.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**BDSS-65091: Attendee {0} was not resolvable in Active Directory or the syncing users Contact folder and subfolders.**

**Cause:** There is no Active Directory or Contact record for the specified attendee.

**Action:** Optionally add the attendee to Active Directory or as a Contact in the synchronizing users folder.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Data

**BDSS-65092: Attendees defined in public folders are not supported.**

**Cause:** The specified attendee identifier is a public distribution member.

**Action:** Optionally remove the attendee from the calendar record.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-65093: Failed to obtain record associated data from the BDSS Hub. Detected an exception from connector runtime library method getRecordAssociatedData. Exception message: {0}**

**Cause:** A network error occurred.

**Action:** Attempt to synchronize the user again.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-65094: Failed to obtain record associated data from the BDSS Hub for the following Pim record identifiers: {0}**

**Cause:** The Hub failed to obtain the record associated data for the specified Pim record identifiers.

**Action:** Examine the Hub log file to determine the root cause of each error.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-65096: Cannot delete the Exchange record because the record associated data for the specified Pim Record Id could not be obtained from the BDSS Hub.**

---

**Cause:** Failed to obtain the record associated data for the given Pim Record Id. The BDSS store should have contained the record associated data.

**Action:** Perform an initial synchronization for the user or manually delete the record from the synchronizing users mailbox and perform another user synchronization.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-65097: Failed to obtain the record associated data for a record that has been deleted from Exchange. Pim Record Id = {0}.**

**Cause:** Failed to obtain the record associated data for the given Pim Record Id. The BDSS store should have contained the record associated data.

**Action:** Perform an initial synchronization for the user.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-65099: Failed to establish a subscription for the specified user and domain.**

**Cause:** BUGBUG

**Action:** BUGBUG

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-65100: Failed to obtain the specified users event associated data.**

**Cause:** BUGBUG

**Action:** BUGBUG

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BDSS-65105: Failed to end a subscription for the specified user and domain.**

**Cause:** BUGBUG

**Action:** BUGBUG

**Level:** 1

**Type:** ERROR

**Impact:** Data



---

## BI-DCBEANS-00001 to BI-DCBEANS-00017

**BI-DCBEANS-00001: The Discoverer service is stopped.**

**Cause:** The Discoverer service was stopped.

**Action:** Start the Discoverer service.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCBEANS-00002: The Discoverer Viewer service is disabled.**

**Cause:** The Discoverer Viewer service was stopped.

**Action:** Start the Discoverer Viewer service.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCBEANS-00003: The Discoverer Plus service is disabled.**

**Cause:** The Discoverer Plus service was stopped.

**Action:** Start the Discoverer Plus service.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCBEANS-00004: The request is not supported. The argument {0} must be single-valued.**

**Cause:** The user provided an argument that was not single-valued.

**Action:** Provide a single-valued argument.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCBEANS-00005: The request is not supported. Version {0} must be an integer.**

**Cause:** The argument provided by the user was not an integer.

**Action:** Provide an integer argument.

**Level:** 1

---

Type: ERROR

Impact: Process

**BI-DCBEANS-00006: The request is not supported. Compatible version number {0} must be an integer.**

**Cause:** The version number provided by the user was not an integer.

**Action:** Provide an integer version number.

Level: 1

Type: ERROR

Impact: Process

**BI-DCBEANS-00007: The request requires API version {0}. This installation can accept only version {1}.**

**Cause:** The API version requested was incompatible with the installation.

**Action:** Provide a compatible version number.

Level: 1

Type: ERROR

Impact: Process

**BI-DCBEANS-00008: Refresh argument must be an integer number.**

**Cause:** The user provided a refresh argument was not an integer.

**Action:** Provide an integer refresh argument.

Level: 1

Type: ERROR

Impact: Process

**BI-DCBEANS-00009: cannot specify non-XML formats without a page number**

**Cause:** The user did not provide the page number required for a non-XML format.

**Action:** Specify a valid page number.

Level: 1

Type: ERROR

Impact: Process

**BI-DCBEANS-00010: cannot specify worksheet without workbook**

**Cause:** The workbook could not be found.

**Action:** Refer log file for details.

Level: 1

Type: ERROR

Impact: Process

**BI-DCBEANS-00011: cannot specify workbook without connection parameters**

**Cause:** The user did not provide the necessary connection parameters, or the supplied connection parameters were invalid.

**Action:** Specify valid connection parameters.

Level: 1

---

**Type:** ERROR

**Impact:** Process

**BI-DCBEANS-00012: missing connection user**

**Cause:** The specified connection user was not found.

**Action:** Specify a valid connection user.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCBEANS-00013: Parameter {0} must be an ordered parameter.**

**Cause:** The specified parameter was not an ordered parameter.

**Action:** Specify an ordered parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCBEANS-00014: The requested URL contains expired bookmarked edits to the worksheet.**

**Cause:** The bookmarked edits for the worksheet have expired.

**Action:** Use a recent URL for the worksheet.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCBEANS-00015: Discoverer Plus cannot be accessed via the Discoverer Viewer URL.**

**Cause:** Discoverer Plus could not be accessed.

**Action:** Refer log file for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCBEANS-00016: Discoverer Plus is not supported. RMI server initialization failed.**

**Cause:** Discoverer Plus was disabled because the RMI server initialization failed.

**Action:** Check the RMI server status in the Discoverer configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCBEANS-00017: Discoverer Plus is not supported. The RMI server is disabled in the Discoverer configuration.**

**Cause:** Discoverer Plus was disabled because the RMI server was disabled.

**Action:** Enable the RMI server in the Discoverer configuration.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

## BI-DCWBSVC-05001 to BI-DCWBSVC-05079

**BI-DCWBSVC-05001: Error in connection list retrieval.**

**Cause:** An error occurred during connection list retrieval.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05002: The connection does not exist in the connection store. Invalid connectionkey :{0}.**

**Cause:** The connection list did not exist in connection store or invalid connection key :{0}.

**Action:** See the logs for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05003: The OLAP connection has an invalid dbname string. Use format host:port:sid.**

**Cause:** The OLAP connection has an invalid dbname string.

**Action:** Use format is host:port:sid.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05004: Error retriving connection details.**

**Cause:** An error occurred during connection details retrieval.

**Action:** Check whether the connection key is valid

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05005: Maximum sessions are in use. Unable to create new sessions.**

**Cause:** Reached maximum sessions. Unable to create new sessions.

**Action:** Contact your Administrator.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05006: The OracleAS Single Sign-On user name is not set.**

**Cause:** The OracleAS Single Sign-On user name was not set.

**Action:** Set the OracleAS Single Sign-On user name

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05007: The connection key is not set.**

**Cause:** No connection key was not set.

**Action:** Set the connection key.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05008: The workbook is not set.**

**Cause:** No workbook was set.

**Action:** Set the workbook.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05009: The worksheet is not set.**

**Cause:** No worksheet was set.

**Action:** Set the worksheet.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05010: Error in setting the connection Key.**

**Cause:** An error occurred while setting the Connection Key.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05011: Error resetting the connection Key.**

**Cause:** An error occurred while resetting the Connection Key.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**BI-DCWBSVC-05012: attempting to perform operation with invalid data. The globally unique identifier (GUID) is null.**

**Cause:** An attempt was made to perform an operation with invalid data. The globally unique identifier (GUID) is null.

**Action:** See whether you are an Oracle AS Single Sign-On user name.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05013: Error creating the Discoverer session.**

**Cause:** An error occurred while creating the Discoverer session.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05014: error creating session for connectionKey :{0}**

**Cause:** An errored while creating session for connection Key :{0}.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05015: authentication error in making a connection with connection key :{0}.**

**Cause:** an authentication error occurred while making a connection with connection key :{0}.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05016: The password is missing.**

**Cause:** No password was provided.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05017: An error occurs while creating the BISession.**

**Cause:** An error occurred while creating the BISession.

**Action:** See the log for details.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05018: An error in establishing the connection.**

**Cause:** An error occurred while establishing the connection. This could be due to invalid connection details, EUL db is down.

**Action:** Check whether the connection details are correct and the EUL Database is up.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05019: Folder type is unsupported.**

**Cause:** Unsupported folder type was used.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05020: Configuration file is not found :{0}.**

**Cause:** Configuration file was not found :{0}.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05021: Configuration directory is not found :{0}.**

**Cause:** Configuration directory was not found :{0}.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05022: XSD file {0} is not found.**

**Cause:** XSD file {0} was not found.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05023: An error occurred while reading the XMLPublisher XSD file.**

**Cause:** An error occurred while reading the BI Publisher XSD file.

**Action:** See the log for details.

**Level:** 1



---

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05024: Error reading maxsession value from the configuration file.**

**Cause:** An error occurred while reading the maxsession value file.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05025: Error reading WebServices status from the configuration file.**

**Cause:** An error occurred while reading WebServices Status from the configuration file.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05026: Parameter type used is not supported.**

**Cause:** Unsupported parameter type was used.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05027: Error getting the requested worksheet.**

**Cause:** An error occurred while getting the requested worksheet.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05028: Error retrieving parameters of worksheet :{0}.**

**Cause:** An error occurred while retrieving parameters of worksheet :{0}.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05029: Error retrieving parameter values for the worksheet :{0}.**

**Cause:** An error occurred while retrieving parameter values for the worksheet :{0}.

**Action:** See the log for details.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05030: The worksheet does not exist :{0}.**

**Cause:** Worksheet did not exist :{0}.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05031: Error opening the worksheet.**

**Cause:** An error occurred while opening the worksheet.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05032: Parameter values are not set.**

**Cause:** An I/O error occurred while exporting a data cell.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05033: The selected list contains null parameter.**

**Cause:** Parameter values were not set.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05034: Error in OracleAS Single Sign-On Username or globally unique identifier(GUID) lookup.**

**Cause:** An error occurred during OracleAS Single Sign-On User name/globally unique identifier (GUID) lookup.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05035: Invalid credentials.**

**Cause:** Invalid credentials were provided.

**Action:** See the log for details.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05036: Access is denied for the user.**

**Cause:** Access was denied for the user.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05037: Account is inactive for the user.**

**Cause:** Account was inactive for the user.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05038: Account is disabled for the user.**

**Cause:** Account was disabled for the user.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05039: Account is locked for the user.**

**Cause:** Account was locked for the user.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05040: Authentication fails for the user.**

**Cause:** Authentication failed for the user.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05041: Subscriber is not found for the user.**

**Cause:** No subscriber was found for the user.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**BI-DCWBSVC-05042: unsupported result type :{0}.**

**Cause:** Unsupported result Type :{0} was provided.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05043: invalid worksheet state**

**Cause:** Invalid worksheet state

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05044: An error in rowset XML generation.**

**Cause:** An error occurred during Rowset XML generation.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05045: No data is available for export.**

**Cause:** No data was available for export.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05046: The export operation fails.**

**Cause:** The export operation failed.

**Action:** See the application log or other errors on the screen for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05047: An error occurred during generation.**

**Cause:** An error occurred during generation.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05048: No data is available for export.**

**Cause:** This could be due to an issue within Oracle BI Discoverer.

---

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05049: error during controller creation**

**Cause:** An error had occurred during controller creation.

**Action:** See the log for details

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05050: error creating WSMModel object**

**Cause:** An error occurred while creating WSMModel object.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05051: unable to lookup workbook :{0}**

**Cause:** Lookup for workbook :{0} failed

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05052: unable to lookup worksheet :{0}**

**Cause:** Worksheet :{0} lookup failed

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05053: Unable to look up parameters.**

**Cause:** No parameters found.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05054: Connection to BI Discoverer Server is lost.**

**Cause:** Connection to BI Discoverer Server was lost.

**Action:** See the log for details.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05055: BI Discoverer server session is closed.**

**Cause:** BI Discoverer server session was closed.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05056: Error performing folder lookup for the folderpath :{0}.**

**Cause:** An error occurred while performing folder lookup for the folderpath :{0}

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05057: Error clearing workbook cache.**

**Cause:** An error occurred while clearing workbook cache.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05058: invalid session key :{0}.**

**Cause:** Invalid session key :{0} was provided.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05059: Invalid query Key :{0}.**

**Cause:** Query Key :{0} is not valid.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05060: Query identified by query key {0} is not complete.**

**Cause:** Incomplete query was identified by query key {0}.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**BI-DCWBSVC-05061: The exported file is not found.**

**Cause:** The exported file was not found.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05062: Nothing to print. Crosstab, table, or graph must be selected to print.**

**Cause:** Nothing was selected to print.

**Action:** Either the crosstab, table, or graph must be selected in order to print.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05063: unable to generate PDF using the current settings.**

**Cause:** PDF generation failed using the current settings.

**Action:** Change the settings by choosing the \"Printable page\" link in the actions section of the open worksheet.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05064: The visible option is not set to ALL or DISPLAYED.**

**Cause:** The visible option was not set to ALL or DISPLAYED.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05065: WebServices cannot generate the PDF output as requested.**

**Cause:** WebService was unable to generate the PDF output as requested.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05066: Oracle BI Discoverer is unable to determine if the worksheet contains page items.**

**Cause:** Oracle BI Discoverer was unable to determine if the worksheet contains page items.

**Action:** See the other error messages for details.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05067: The measurement unit for printing is invalid.**

**Cause:** The measurement unit for printing was invalid.

**Action:** Change the value and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05068: Specified locale string is invalid.**

**Cause:** An invalid locale string was specified.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05069: Oracle BI Discoverer Viewer is unable to scroll the graph to its proper position.**

**Cause:** Oracle BI Discoverer Viewer was unable to scroll the graph to its proper position.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05070: Margin value is illegal.**

**Cause:** An illegal margin value was supplied.

**Action:** Correct the value and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05071: Selected orientation is illegal.**

**Cause:** An illegal page orientation was selected.

**Action:** Try a different value.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05072: The selected paper size is illegal.**

**Cause:** An illegal paper size was selected.

**Action:** Contact your OracleAS administrator.

**Level:** 1



---

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05073: Oracle BI Discoverer is unable to generate PDF documents.**

**Cause:** The PDF printing pool was no longer valid.

**Action:** Restart the application and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05074: An illegal value is supplied for the selection of when to print the title, footnote, or page items.**

**Cause:** An illegal value was supplied for the selection of when to print the title, footnote, or page items.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05075: An illegal scaling value.**

**Cause:** An illegal scaling value was supplied.

**Action:** Try a different value.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05076: The PDF generator unable to calculate the column widths.**

**Cause:** The PDF generator was unable to calculate the column widths.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05077: Invalid width specified for column at position {0}.**

**Cause:** An invalid width was specified for the column at position {0}.

**Action:** See the logs for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05078: The specified worksheet layout is invalid.**

**Cause:** An invalid worksheet layout was specified.

**Action:** See the log for details.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**BI-DCWBSVC-05079: Webservice is disabled.**

**Cause:** Webservice wasdisabled.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

---

## BI-EUL-00001 to BI-EUL-00002

**BI-EUL-00001: Error creating EUL**

**Cause:** The user lacked sufficient privileges for EUL creation.

**Action:** Grant the privileges required to create an End User Layer.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-EUL-00002: Error deleting EUL**

**Cause:** The user lacked sufficient privileges for End User Layer deletion.

**Action:** Grant the privileges required to delete an End User Layer.

**Level:** 1

**Type:** ERROR

**Impact:** Process



---

## BI-PDFRDR-02001 to BI-PDFRDR-02047

**BI-PDFRDR-02001: I/O error during data cell export**

**Cause:** An I/O error occurred while exporting a data cell.

**Action:** See the Discoverer log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02002: I/O error during crosstab export**

**Cause:** An I/O error occurred while exporting a crosstab.

**Action:** See the Discoverer log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02003: An edge is out of range during crosstab export.**

**Cause:** An edge was out of range while exporting a crosstab.

**Action:** Provide an edge value within the range specified.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02004: A layer is out of range during crosstab export.**

**Cause:** A layer was out of range while exporting a crosstab.

**Action:** Provide a layer value within the range specified.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02005: A slice is out of range during crosstab export.**

**Cause:** A slice was out of range while exporting a crosstab.

**Action:** Provide a slice value within the range.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02006: A column is out of range during crosstab export.**

**Cause:** A column was out of range while exporting a crosstab.

**Action:** Provide a column value within the range.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02007: A row is out of range during crosstab export.**

**Cause:** A row was out of range while exporting a crosstab.

**Action:** Provide a row value within the range.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02008: An I/O error occurred during table export.**

**Cause:** An I/O error occurred while exporting a table.

**Action:** See the Discoverer log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02009: An edge was out of range during table export.**

**Cause:** An edge was out of range while exporting a table.

**Action:** Provide an edge value within the range specified.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02010: A layer was out of range during table export.**

**Cause:** A layer was out of range while exporting a table.

**Action:** Provide a layer value within the range specified.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02011: A slice was out of range during table export.**

**Cause:** A slice was out of range while exporting a table.

**Action:** Provide a slice value within the range.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**BI-PDFRDR-02012: A column was out of range during table export.**

**Cause:** A column was out of range while exporting a table.

**Action:** Provide a column value within the range.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02013: A row was out of range during table export.**

**Cause:** A row was out of range while exporting a table.

**Action:** Provide a row value within the range.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02014: An I/O error occurred during graph export.**

**Cause:** An I/O error occurred while exporting a graph.

**Action:** See the Discoverer log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02015: I/O error while streaming to the XDO PDF processor**

**Cause:** An I/O error occurred while streaming to the XDO PDF processor.

**Action:** See the Discoverer log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02016: The encoding supplied to XDO is not supported.**

**Cause:** The encoding supplied to XDO was not supported.

**Action:** See the Discoverer log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02017: The PDF generator is already running.**

**Cause:** The PDF generator was already running.

**Action:** See the Discoverer log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02018: A locale must be provided to print a PDF.**

**Cause:** No local was provided.

---

**Action:** Provide a locale.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02019: A PDFGraphLayout must be provided in the PDFWorksheet.**

**Cause:** The required PDFGraphLayout was not provided in the PDFWorksheet.

**Action:** Provide a PDFGraphLayout.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02020: As the graph layout is set to NONE, a grid view must be present in the PDFWorksheet.**

**Cause:** The graph layout was set to NONE, so there must be a graph view present in the PDFWorksheet.

**Action:** See the Discoverer log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02021: As the graph layout is set to ONLY, a graph view must be present in the PDFWorksheet.**

**Cause:** The graph layout was set to ONLY, so there must be a graph view present in the PDFWorksheet.

**Action:** Provide a worksheet which has a graph.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02022: As the graph layout is set to a position, a graph view must be present in the PDFWorksheet.**

**Cause:** The Graph Layout was set to a position, so there must be a graph view present in the PDFWorksheet.

**Action:** Provide a worksheet which has a graph.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02023: As the graph layout is set to a position, a grid view must be present in the PDFWorksheet.**

**Cause:** The graph layout was set to a position, so there must be a grid view present in the PDFWorksheet.

**Action:** Provide a worksheet with a grid view present.

**Level:** 1



---

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02024: No data is available.**

**Cause:** Either the query was not run or no data was available in the worksheet.

**Action:** Rerun the query and see the Discoverer log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02025: The left and right margins are too big or the page width is too small.**

**Cause:** Incompatible values were provided for side margins or page width.

**Action:** Change the margin size or page width.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02026: The top and bottom margins are too big or the page height is too small.**

**Cause:** Incompatible values were provided for the top and bottom margins and page width.

**Action:** Change the margin size or page width.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02027: A single column width is not greater than (pixels): {0}**

**Cause:** A single column width was not greater than the specified width, as required.

**Action:** "Increase the column width.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02028: The total width of the row headers when added is not smaller than the page width minus the right and left margins.**

**Cause:** The supplied row headers were too wide for the page size.

**Action:** Change the width of the row headers.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02029: A single column plus the total width of the row headers when added is not smaller than the page width minus the left and right margins.**

**Cause:** >The supplied row headers were too wide for the page size.

---

**Action:** Change the width of row headers.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02030: The graph height is not smaller than the page height minus the top and bottom margins, as required.**

**Cause:** The supplied graph height was too large for the page.

**Action:** Reset the height and width values.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02031: The graph width is not smaller than the page width minus the left and right margins, as required.**

**Cause:** The graph width must be smaller than the page width minus the left and right margins.

**Action:** Reset the height and width values.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02032: The graph height is not greater than one pixel, as required.**

**Cause:** A graph height was provided that was not greater than one pixel.

**Action:** Change the graph height and make it bigger than one pixel.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02033: The graph width is not greater than one pixel, as required.**

**Cause:** A graph width was provided that was less than or equal to one pixel.

**Action:** Change the graph width and make it bigger than one pixel.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02034: unable to validate page, margin, or column sizes**

**Cause:** Invalid values for page, margin or column sizes.

**Action:** Provide a valid page, margin or column sizes

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02035: The PDF generator is unable to generate a section start or end.**

**Cause:** The PDF generator was unable to generate a section start or end.

---

**Action:** See the Discoverer log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02036: The PDF generator is unable to generate the header or footer.**

**Cause:** The PDF generator was unable to generate the header or footer.

**Action:** See the Discoverer log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02037: The PDF generator is unable to generate the title or text area.**

**Cause:** The PDF generator was unable to generate the title or text area.

**Action:** See the Discoverer log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02038: The PDF generator is unable to generate the page items area.**

**Cause:** The PDF generator was unable to generate the page items area.

**Action:** See the Discoverer log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02039: The PDF generator is unable to generate all combinations of page items.**

**Cause:** The PDF generator was unable to generate all combinations of page items.

**Action:** See the Discoverer log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02040: unable to determine if the grid contains page items**

**Cause:** The PDF generator was unable to determine if the grid contains page items.

**Action:** See the Discoverer log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02041: unable to determine if the graph contains page items**

**Cause:** The PDF generator was unable to determine if the graph contains page items.

---

**Action:** Check if the graph contains page items.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02042: The grid type is not one of the following: a ThinTable, a Table, a ThinCrosstab, or a Crosstab, as required.**

**Cause:** The grid type must be one of the following: a ThinTable, a Table, a ThinCrosstab, or a Crosstab.

**Action:** Check the grid type.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02043: The units type is not inches, centimeters, or points, as required.**

**Cause:** An invalid type was provide for the units value.

**Action:** Change the units type to INCHES, CENTIMETER, or POINTS.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02044: The visible only option is only supported for thin crosstabs and tables.**

**Cause:** The visible only option was specified for an unsupported use.

**Action:** Change the visible option data.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02045: unable to complete the query to fetch data related to a page item combination**

**Cause:** The query to fetch data related to a page item combination did not complete successfully.

**Action:** See the Discoverer log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PDFRDR-02046: The page width and height are not greater than 0.**

**Cause:** The page width and height must be greater than 0.

**Action:** Change the page width value and the page height value.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**BI-PDFRDR-02047: The PDF generator cannot support the specified data access instance.**

**Cause:** A data access instance was specified that the PDF generator could not support. The PDF generator supports only data access instances that implement the DataAccess2 interface.

**Action:** See the Discoverer log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process



---

## BI-PLUS-00001 to BI-PLUS-00050

**BI-PLUS-00001: Could not set the selected LookAndFeel: {0}**

**Cause:** The selected LookAndFeel was not set.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00002: The crosstab cannot be sorted because it does not contain any items.**

**Cause:** The crosstab did not contain any items.

**Action:** Add items to the crosstab.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00003: The crosstab cannot be sorted because it currently contains no data.**

**Cause:** The crosstab did not contain any data.

**Action:** Add data to the crosstab.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00004: The condition cannot be applied because it is unrelated to the items in the current sheet.**

**Cause:** The specified condition was unrelated to the items in the sheet.

**Action:** Select a condition that applies to the items in the sheet.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00005: The formula of this condition is invalid.**

**Cause:** There was a syntax error in the formula for this condition.

**Action:** Check the syntax of the formula for this condition.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00006: Error in condition name.**

**Cause:** The user supplied an invalid condition name.

**Action:** Use only alphabetic characters for the condition name.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00007: Another condition with that name already exists. Please type a different name.**

**Cause:** The user supplied an invalid condition name.

**Action:** Enter a different condition name.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00008: This condition cannot be viewed or edited in this version of Discoverer Plus because it contains a subquery. You may still activate and deactivate the condition.**

**Cause:** An attempt was made to view or edit a condition that contained a subquery, but the version of Oracle Business Intelligence Discover Plus was unable to handle the subquery.

**Action:** Check the log file for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00009: One of the function arguments has an incorrect datatype: {0}**

**Cause:** An incorrect data type was found in a function argument.

**Action:** Ensure that all data types in the function arguments are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00010: You cannot create a condition because there are no items or calculations in this worksheet.**

**Cause:** The worksheet did not contain any items or calculations.

**Action:** Add some items or calculations to this worksheet.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00011: No matching close quote found in string.**

**Cause:** The string had an opening quotation mark but no closing quotation mark.



---

**Action:** Supply the missing closing quotation mark in the condition.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00012: Invalid quote in string.**

**Cause:** The string contained an invalid quotation mark.

**Action:** Supply the proper quotation mark for the condition.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00013: Badly placed quote in string.**

**Cause:** The string contained a misplaced quotation mark.

**Action:** Ensure that quotation marks are correctly placed in the condition.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00014: {0} cannot be included in the worksheet because the database that you are connected to does not support these kinds of advanced conditions.**

**Cause:** The database to which the user was connected could not support the advanced condition.

**Action:** Check the log file for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00015: The calculation cannot be displayed because it is unrelated to the items in the current sheet.**

**Cause:** The calculation was unrelated to the items in the worksheet.

**Action:** Use a calculation that is related to items in the current sheet.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00016: Cannot combine a detail data point with an aggregate data point.**

**Cause:** A calculation syntax error occurred.

**Action:** Use a detail data point only with other detail data points in a calculation.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00017: Error in formula.**

**Cause:** A calculation syntax error occurred.

---

**Action:** Check the formula.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00018: Error in calculation name.**

**Cause:** The user supplied an invalid calculation name.

**Action:** Use only alphabetic characters for the calculation name.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00019: Another Calculation or Percentage with that name already exists.**

**Please type a different name.**

**Cause:** A calculation name conflict occurred.

**Action:** Use another name for this calculation.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00020: {0} cannot be included in the worksheet because the database that you are connected to does not support these kinds of advanced calculations.**

**Cause:** The database to which the user was connected could not support the advanced calculations.

**Action:** Check the log file for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00021: The query failed. Do you want to restore the previous data in your sheet? - Click Yes to undo your changes. - Click No to continue, but your sheet will be empty.**

**Cause:** Query failed.

**Action:** Check the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00022: Could not obtain list of drill items from server.**

**Cause:** Could not obtain list of drill items from server.

**Action:** Check the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**BI-PLUS-00023: Invalid default value: {0}**

**Cause:** An invalid default value was specified for the parameter.

**Action:** Choose a default value for this parameter from the list of values.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00024: A parameter named \"{0}\" already exists. Please type in a different name.**

**Cause:** A parameter name conflict occurred.

**Action:** Enter another name for this parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00025: Export Failed.**

**Cause:** The attempted export operation failed.

**Action:** Check the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00026: An error occurred writing to the export file. Check adequate space is available.**

**Cause:** The attempted export operation failed due to insufficient disk space.

**Action:** Ensure that adequate disk space is available and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00027: You cannot export the graph because it does not contain any data.**

**Cause:** The export operation failed because the graph did not contain any data.

**Action:** Add some data to the graph.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00028: Connection Error**

**Cause:** The connection failed.

**Action:** Check the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**BI-PLUS-00029: {0} The graph for the worksheet cannot be printed.**

**Cause:** A graph printing error occurred.

**Action:** Check the log file for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00030: {0} The graph for worksheet {1} cannot be printed.**

**Cause:** A graph printing error occurred.

**Action:** Check the log file for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00031: The graph for the worksheet cannot be printed.**

**Cause:** A graph printing error occurred.

**Action:** Check the log file for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00032: The graph for worksheet {0} cannot be printed.**

**Cause:** A graph printing error occurred.

**Action:** Check the log file for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00033: Printing Failed.**

**Cause:** A printing error occurred.

**Action:** Check the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00034: At least one view must be printed.**

**Cause:** No view was chosen to be printed.

**Action:** Print at least one view.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00035: The title of the worksheet could not be printed with the graph.**

**Cause:** An attempt was made to print the graph and title together.

---

**Action:** Print the graph without the title.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00036: The title of worksheet {0} could not be printed with the graph.**

**Cause:** An attempt was made to print the graph and title together.

**Action:** Print the graph without the title.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00037: The title of the {0} worksheet is too long to fit on the printed page.**

**The title will therefore be truncated.**

**Cause:** The worksheet title was too long to print.

**Action:** The title will be printed in truncated form. No action is needed.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00038: The text area of the {0} worksheet is too long to fit on the printed page. The text area will therefore be truncated.**

**Cause:** The worksheet text area is too long to print.

**Action:** The text area will be printed in truncated form. No action is needed.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00039: You cannot print the graph because it does not contain any data.**

**Cause:** A printing error occurred because the graph did not contain any data.

**Action:** Add some data to the graph to be printed.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00040: The worksheet cannot be printed because the margins are too large.**

**Cause:** A printing error occurred because the worksheet margins were too large.

**Action:** Reduce the margins in the worksheet.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00041: Select at least {0} or graph for export.**

**Cause:** The export operation failed because nothing was selected for export.

---

**Action:** Select an object to be exported.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00042: The exported graph may not be identical to the graph seen in Discoverer. There was an error in setting the graph properties**

**Cause:** Export failed. Graph properties could not be set.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00043: Export incomplete. The user chose not to overwrite an existing file**

**Cause:** The user chose not to overwrite an existing file.

**Action:** Export the file that was not exported.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00044: The current operation was canceled at the users request**

**Cause:** The export operation failed.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00045: Graph cannot be exported because the worksheet has no rows**

**Cause:** The export operation failed because the worksheet has no rows.

**Action:** Ensure that rows exist in the worksheet that is to be exported.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00046: Only positive data values are plotted on the graph. This graph type does not support data values that are negative, null, or zero.**

**Cause:** The data values provided for the graph contained negative, null or zero

**Action:** Use only positive values for plotting the graph.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00047: A graph cannot be plotted because all of the data values are negative, null, or zero.**

**Cause:** The data values provided for the graph were negative, null, or zero.

---

**Action:** Provide positive values for plotting the graph.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00048: Scheduling Error**

**Cause:** Scheduling did not occur.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00049: Find operation failed**

**Cause:** The Find operation failed.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-PLUS-00050: An error occurred while executing the Find operation.**

**Cause:** The Find operation failed.

**Action:** See the log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process





---

## BI-POPVD-00001 to BI-POPVD-00053

**BI-POPVD-00001: No worksheet is selected. Select a worksheet**

**Cause:** No worksheet was selected.

**Action:** Select a worksheet.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00002: An error occurs while externalizing the model state.**

**Cause:** An error occurred while externalizing the model state.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00003: An error occurs while reconstituting the model state.**

**Cause:** An error occurred while reconstituting the model state.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00004: An error occurs while handling the request in the controller.**

**Cause:** An error occurred while handling the request in the controller.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00005: The selected crosstab has data points on the page axis. This layout is not supported by the Discoverer Gauges portlet.**

**Cause:** A crosstab was selected that had data points on the page axis. This layout is not supported by the Discoverer Gauges portlet.

**Action:** Please choose a different crosstab for Discoverer to display gauges portlet.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00006: There is no measure data source selected. Select row items and column items.**

**Cause:** No measure data source was selected.

**Action:** Select row items and column items.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00007: There are no workbooks selected for building the List of Worksheets.**

**Cause:** No workbooks were selected for building the List of Worksheets.

**Action:** Select workbooks.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00008: There are no worksheets selected for building the List of Worksheets.**

**Cause:** No worksheets were selected for building the List of Worksheets.

**Action:** Select worksheets.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00009: Only the owner of this portlet can edit the defaults.**

**Cause:** The portlet owner can only edit the defaults.

**Action:** Log in as the owner to edit this portlet.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00010: An error occurs while handling the BIBean event.**

**Cause:** An error occurred while handling the BIBean event.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00011: An error occurs while parsing the event.**

**Cause:** An error occurred while parsing the event.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00012: An error occurs while initializing the graph renderer.**

**Cause:** An error occurred while initializing the graph renderer.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00013: The graph renderer is already initialized.**

**Cause:** The graph renderer was already initialized.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00014: The graph renderer is not initialized.**

**Cause:** The graph renderer was not initialized.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00015: An error occurs while rendering the graph.**

**Cause:** An error occurred while rendering the graph.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00016: The length of one or more parameter values exceeds the defined limit of 3000 characters**

**Cause:** The length of one or more parameter values exceeded the defined limit of 3000 characters

**Action:** Shorten the parameter values to less than 3000 characters.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00017: The session pool is at maximum capacity.**

**Cause:** The session pool was at maximum capacity.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00018: unsupported presentation type for view**

**Cause:** Unsupported presentation type for view.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00019: unsupported presentation type for graph**

**Cause:** Unsupported presentation type for graph.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00020: An error occurs while reading the cached portlet content for the view.**

**Cause:** An error occurred while reading the cached portlet content for the view.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00021: An error occurs while reading the cached portlet content for the graph.**

**Cause:** An error occurred while reading the cached portlet content for the graph.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00022: An error occurs while reading the cached result.**

**Cause:** An error occurred while reading the cached result.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00023: The selected worksheet is not a valid crosstab worksheet for Discoverer Gauges portlet.**

**Cause:** Not a valid crosstab worksheet selected for Discoverer Gauges portlet.

**Action:** Choose a valid crosstab worksheet.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00024: This portlet is refreshing.**

**Cause:** An attempt was made to access a portlet while its data was being refreshed

**Action:** Wait till the portlet refreshes.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00025: An error occurs while refreshing this portlet.**

**Cause:** An error occurred while refreshing this portlet.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00026: An error occurs while setting the refresh options for this portlet.**

**Cause:** An error occurred while setting the refresh options for this portlet.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00027: An error occurs while reading the refresh options for this portlet.**

**Cause:** An error occurred while reading the refresh options for this portlet.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00028: An error occurs while trying to detect the last refresh date for this portlet.**

**Cause:** An error occurred while trying to detect the last refresh date for this portlet.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00029: An error occurs while trying to ensure persistence of the portlet defaults.**

---

**Cause:** An error occurred while trying to ensure persistence of the portlet defaults.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00030: An error occurs while trying to ensure persistence of the portlet customization.**

**Cause:** An error occurred while trying to ensure persistence of the portlet customization.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00031: An error occurs while trying to read the refresh options from the state string.**

**Cause:** An error occurred while trying to read the refresh options from the state string.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00032: An error occurs while trying to parse the refresh date and time.**

**Cause:** An error occurred while trying to parse the refresh date and time.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00033: The default cached result is null.**

**Cause:** An error occurred while refreshing this portlet.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00034: An error occurs while attempting to update the portlet cache from the Single Worksheet Viewer.**

**Cause:** An error occurred while attempting to update the portlet cache from the Single Worksheet Viewer.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00035: An error occurs while trying to determine if the user cache was updated.**

**Cause:** An error occurred while trying to determine if the user cache was updated.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00036: An error occurs while trying to determine if the default cache was updated.**

**Cause:** An error occurred while trying to determine if the default cache was updated.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00037: Connection to portlet is not available to unauthenticated users.**

**Cause:** A user connection for unauthenticated users was requested for a Portlet that is not displayed to unauthenticated users.

**Action:** Log in as an authenticated user.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00038: The user connection is null for displaying the List of Worksheets.**

**Cause:** The user connection was null to display the List of Worksheets.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00039: The publisher connection is null for displaying the List of Worksheets.**

**Cause:** The publisher connection was null to display the List of Worksheets.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00040: An error occurs while retrieving the view information.**

**Cause:** An error occurred while retrieving the view information.

---

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00041: The last scheduled refresh failed.**

**Cause:** The last scheduled refresh failed.

**Action:** Click for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00042: Refresh Fails.**

**Cause:** An attempt to refresh the data in the portlet failed.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00043: The publisher's Connection list is empty.**

**Cause:** The publisher's Connection list was empty.

**Action:** Create one or more publisher's connections.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00044: No connections are available for the current user to view this portlet. Contact the publisher of this Portal page or the Oracle Business Intelligence Discoverer administrator.**

**Cause:** No connections were available for the user to view this portlet.

**Action:** Contact the publisher of this Portal page or the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00045: The publisher's connection is not found in the list of available connections. Select a connection from the list.**

**Cause:** The publisher's connection was not found in the list of available connections.

**Action:** Select a connection from the list.

**Level:** 1

**Type:** ERROR

**Impact:** Process



---

**BI-POPVD-00046: The connection selected for logged in users is not found in the list of available connections. Select a connection from the list.**

**Cause:** The connection selected for logged in users was not found in the list of available connections.

**Action:** Select a connection from the list.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00047: The connection selected for not logged in users is not found in the list of available connections.**

**Cause:** The connection selected for not logged in users was not found in the list of available connections.

**Action:** Select a connection from the list.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00048: An error occurs while trying to get a list of worksheets.**

**Cause:** An error occurred while trying to get a list of worksheets.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00049: An error occurs while trying to get portlet data limits.**

**Cause:** An error occurred while trying to get portlet data limits.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00050: An error occurs while trying to create a cached bean from a live bean.**

**Cause:** An error occurred while trying to create a cached bean from a live bean.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00051: {0} must be a number**

**Cause:** Not a valid number

**Action:** Enter valid number.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00052: not enough memory, gauge set size too big**

**Cause:** gauge set size was too big.

**Action:** Enter appropriate gauges size.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-POPVD-00053: The gauge data point is not found.**

**Cause:** The gauge data point was not found.

**Action:** Select a different data point.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

## BI-SVR-00300 to BI-SVR-03964

**BI-SVR-00300: Error in formula.**

**Cause:** The formula entered does not follow the SQL expression syntax.

**Action:** Re-enter the formula following SQL syntax conventions. See the Oracle SQL Language Reference Manual for a description.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-00709: Inconsistent datatypes in condition.**

**Cause:** The data types of items used in this condition are mismatched.

**Action:** Check the formula to correct the error or change the data type of the items by using TO\_CHAR, TO\_DATE or TO\_NUMBER functions.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-00720: Invalid join configuration - includes a master with two separately joined detail folders.**

**Cause:** An attempt was made to join a master folder with two detail folders at the same time. The resulting Cartesian product would give potentially confusing or incorrect results from the database. This combination of joins is not allowed within Oracle Business Intelligence Discoverer.

**Action:** Construct the join so that the folder specified as the master actually contains the master key and the folders specified as detail actually contain the detail keys. If the join configuration includes a master with two separately joined detail folders then create a complex folder to hide one of the joins. This is normally only the case where the relationship between the folders is one-to-one, and there is no actual master folder.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-01251: Failed to create summaries - automated summary management is not available**

**Cause:** The summary creation failed, because automatic summary management was not available.

---

**Action:** Contact the system administrator for further details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03141: You do not have access to any End User Layer tables**

**Cause:** The user did not have privileges to access any of the End User Layers.

**Action:** Create an End User Layer for the user or grant access to at least one End User Layer using Oracle Business Intelligence Discoverer Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03142: You do not have access to any Business Areas**

**Cause:** The user did not have privileges to access any of the Business Areas.

**Action:** Create a business area for the user or grant access to a business area using Oracle Business Intelligence Discoverer Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03146: Insufficient privilege to run Discoverer Administrator**

**Cause:** A user with sufficient privileges tried to access Oracle Business Intelligence Discoverer Administrator.

**Action:** Grant sufficient privileges to the user to access Oracle Business Intelligence Discoverer Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03150: This item is used in a filter or a hierarchy and cannot be hidden**

**Cause:** The user attempted to hide an item used in a filter or hierarchy.

**Action:** Remove the item from the hierarchy or filter where it is used. Then try hiding it.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03199: %1!s %2!s referenced in the export was not found in this End User Layer**

**Cause:** An attempt was made to export items not found in the End User Layer.

**Action:** Export only items that are found in the End User Layer.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**BI-SVR-03200: %1!s %2!s was not loaded because of a missing dependency**

**Cause:** An attempt was made to export items not found in the End User Layer.

**Action:** Export only items that are found in the End User Layer.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03206: Failed to connect to database**

**Cause:** An attempt was made to connect to the database with an invalid username and password or with an incorrect connect string.

**Action:** Ensure that the username and password and the connect string are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03207: Internal EUL Error: InvalidId - Failed to find EUL element by id**

**Cause:** No element exists in EUL for the given element Id

**Action:** TBD

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03208: Internal EUL Error: ExprParseNodeType - Invalid type in canonical formula**

**Cause:** Invalid argument in the expression

**Action:** Correct the expression with valid arguments.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03209: Internal EUL Error: ExprParseBracketErr - No bracket found in canonical formula**

**Cause:** Missing bracket in expression

**Action:** Check expression has proper brackets.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03210: Invalid formula**

**Cause:** An invalid expression was entered.

**Action:** Enter a valid expression.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**BI-SVR-03211: Invalid number of arguments**

**Cause:** The expression contained an invalid number of arguments.

**Action:** Enter a valid number of arguments in the expression.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03212: Invalid operator in formula**

**Cause:** The expression contained an invalid operator.

**Action:** Remove the invalid operator from the expression.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03213: Internal EUL Error: TransError - Unexpected transaction error**

**Cause:** The EUL transaction failed to execute

**Action:** TBD

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03220: Internal EUL Error: UniqueKeyViolation - internal id is used by another EUL element**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03221: Internal EUL Error: ObjectNotFound - Can't find EUL element**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**BI-SVR-03222: Internal EUL Error: PrivilegeNotFound - No privilege record found for this user**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03223: No joins found where required**

**Cause:** An operation was attempted where a join is required to another folder, and no join was found.

**Action:** Determine which joins are required to support the operation and enter the joins first.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03224: Invalid join configuration - includes a master with two separately joined detail folders**

**Cause:** An attempt was made to join a master folder with two detail folders at the same time. The resulting Cartesian product would give potentially confusing or incorrect results from the database. This combination of joins is not allowed within Oracle Business Intelligence Discoverer.

**Action:** Construct the join so that the folder specified as the master actually contains the master key and the folders specified as detail actually contain the detail keys. If the join configuration includes a master with two separately joined detail folders then create a complex folder to hide one of the joins. This is normally only the case where the relationship between the folders is one-to-one, and there is no actual master folder.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03228: Internal EUL Error: NoTransaction - there is no current transaction**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03229: Internal EUL Error: DataError = Invalid function type**

---

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03234: Internal EUL Error: DrillFromItemNotInQR - Item drilled on is not in the Query Request**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03235: Internal EUL Error: InvalidDrillOption - Invalid drill option requested**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03237: Internal EUL Error: InvalidItem - Item is not valid in this context**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03238: Internal EUL Error: InvalidString - String or string length is not valid**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.



---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03239: Internal EUL Error: InvalidStringLength - String length is not valid**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03240: Internal EUL Error: InvalidRollupOnQR - Rollup item is not in the Query Request**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03241: Internal EUL Error: RollupValueMismatch - filter does not contain rollup value**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03242: Internal EUL Error: TokenStreamError - Error tokenising input stream**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**BI-SVR-03243: Error in formula - uncategorized error**

**Cause:** An unspecified error was found in the formula.

**Action:** Check the formula and correct the error. See the Oracle SQL Language Reference Manual for formula syntax conventions.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03244: Error in formula - unexpected end of formula**

**Cause:** The formula ends unexpectedly.

**Action:** The formula was unfinished, possibly ending in an operator or function name.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03245: Error in formula - unrecognized item name or missing quotes around value**

**Cause:** The formula contains some text that was not recognized as an item name.

**Action:** Change the item name to a valid item name and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03246: Error in formula - ambiguous or duplicate item names**

**Cause:** The supplied formula contains unqualified item names that appeared in multiple folders.

**Action:** Qualify item names with the folder name (for example, Employee.Name).

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03256: Internal EUL Error: InvalidSummaryTableDef - The specified server table is invalid**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03257: Internal EUL Error: InvalidRefreshSetType - Invalid summary refresh set type**

---

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03258: Internal EUL Error: ItemNotInServerObject - Column specified does not exist**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03266: Internal EUL Error: Failed to get summary status from the server**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03267: Error in Formula - unknown function name**

**Cause:** The formula contains a function that is not registered in the End User Layer.

**Action:** Edit the formula correct function name and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03268: Error in formula - mismatched ( ) 's**

**Cause:** Mismatched parentheses were found in the formula.

**Action:** Check the formula to determine if the function name is wrong and if so, correct it. If the function named in the formula is the correct function, then choose Register PL/SQL Function in the Tools menu to register the function in the End User Layer. Retry the formula with the registered function name.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**BI-SVR-03269: Error in formula - Nested aggregate functions are not allowed**

**Cause:** The formula contained unsupported content. Oracle Business Intelligence Discoverer does not directly support the use of nested aggregates, such as AVG(SUM(SAL)).

**Action:** Remove the nested aggregate.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03271: Error in formula - item is not in scope of the folders available for this formula**

**Cause:** The formula contained an item that was not in the folders that this formula can reference.

**Action:** Correct the item name and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03272: Error in formula - circular recursive expression detected**

**Cause:** The formula contained a reference to an item whose formula references this formula.

**Action:** Modify the formula to remove the circular reference and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03273: Internal EUL Error: InvalidConstructOpt - Invalid handle constructor option**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03280: Internal EUL Error: MapInsertFailed - insert failed in PrivateAddObjectToMap**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation might not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**BI-SVR-03281: Internal EUL Error: ExportIdAlreadyExists - Object has already reserved this id**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03282: Internal EUL Error: ExportInvalidCType**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation might not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03283: Error in End User Layer import file - ParseError**

**Cause:** The End User Layer import file was corrupted or was not a valid import file.

**Action:** Export the business area into an new file and import it again. Retry the operation that failed.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03284: Error in End User Layer import file - NoTypeFound**

**Cause:** The End User Layer import file was corrupted or was not a valid import file.

**Action:** Export the business area into an new file and import it again. Retry the operation that failed.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03285: Invalid End User Layer import file**

**Cause:** The End User Layer import file was corrupted or was not a valid import file.

**Action:** Export the End User Layer into an new file and import it again.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**BI-SVR-03286: Error in End User Layer import file - InvalidClass**

**Cause:** The End User Layer import file was corrupted or was not a valid import file.

**Action:** Export the business area into an new file and import it again. Retry the operation that failed.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03291: Internal EUL Error: InvalidDQ4Query - error importing DQ4 query**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation might not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03295: Internal EUL Error: HierarchyNodeNotConnected - this hierarchy node is not connected**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03296: Internal EUL Error: HierarchyNodeNotConnected.**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03297: Internal EUL Error: HierarchySegNotConnected.**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

---

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03298: Internal EUL Error: InvalidSegInHierarchy - Invalid segment found in hierarchy**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03299: Internal EUL Error: InvalidNode - Invalid Hierarchy Node**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03301: Internal EUL Error: ItemNotInNode - The item to be removed is not in this hierarchy node**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03305: Internal EUL Error: LXInitializationFailure - lxinit failed to allocate memory**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**BI-SVR-03308: Internal EUL Error: NotSimpleFilter - complex element found in simple filter**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03309: Internal EUL Error: DestroyFailure - failed to destroy EUL element**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03311: Invalid date format**

**Cause:** An invalid date or time format was entered.

**Action:** Reenter a date or time that complies with the date format MM/DD/YY and the time format HH:MM.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03314: Error found parsing SQL statement**

**Cause:** An unspecified error was detected when parsing an SQL statement. The SQL statement might contain an error, or the type of SQL query might not be currently supported by the Oracle Business Intelligence Discoverer import parser.

**Action:** Check the SQL statement for errors. Correct the error and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03315: This item is used in a hierarchy and cannot be hidden**

**Cause:** An attempt was made to hide an item used in a filter or hierarchy.

**Action:** Remove the item from the hierarchy or filter where it is used. Then try hiding it.

**Level:** 1

**Type:** ERROR



---

**Impact:** Process

**BI-SVR-03351: This user does not have sufficient privileges to create a procedure**

**Cause:** An attempt was made to create or edit procedures in the server, but the user did not have the database privileges required.

**Action:** Ask your system administrator to grant you the CREATE PROCEDURE privilege using SQL\*Plus.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03352: This user does not have sufficient privileges to create a view**

**Cause:** An attempt was made to create or edit views in the server, but the user did not have the database privileges required.

**Action:** Ask the system administrator to grant user the CREATE VIEW privilege using SQL\*Plus.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03353: This user does not have sufficient privileges to create a table**

**Cause:** An attempt was made to create table in the server, but the user did not have the database privileges required.

**Action:** Ask your system administrator to grant you the CREATE TABLE privilege using SQL\*Plus and ensure that the user has quota and privileges necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03359: This user does not have sufficient privileges to insert into specified table**

**Cause:** An attempt was made to insert into a table in the server, but the user did not have the database privileges required.

**Action:** Ask the system administrator to grant user the INSERT privilege on specified table using SQL\*Plus and to ensure that the user has quota and privileges necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03360: This user does not have sufficient privileges to delete from specified table**

**Cause:** An attempt was made to delete from a specified table in the server, but the user did not have the database privileges required.

**Action:** Ask the system administrator to grant user the DELETE privilege on the specified table using SQL\*Plus.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03361: This user does not have sufficient privileges to update specified table**

**Cause:** An attempt was made to update a specified table in the server, but the user did not have the database privileges required.

**Action:** Ask the system administrator to grant the user UPDATE privilege on the specified table using SQL\*Plus.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03362: This user does not have sufficient privileges to select from specified table**

**Cause:** An attempt was made to select from a specified table in the server, but the user did not have the database privileges required.

**Action:** Ask the system administrator to grant the user the SELECT privilege on specified table using SQL\*Plus.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03363: This operation will cause some summaries to be disabled**

**Cause:** The user lacked the database privileges required to create or edit tables in the server.

**Action:** Ask the system administrator to grant the user the CREATE TABLE privilege using SQL\*Plus and to ensure that the user has sufficient privileges create tables in a tablespace.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03373: Unsupported date arithmetic requested**

**Cause:** An attempt was made to use DATE type items in a formula in an invalid combination. Typically this is caused by trying to add, subtract, multiply, or divide two dates.

**Action:** See the Oracle SQL Language Reference Manual for information about date arithmetic syntax.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03899: The custom SQL entered contains enhanced aggregation and is therefore invalid.**

---

**Cause:** A custom SQL query was entered that contained enhanced aggregations such as GROUPING SETS.

**Action:** Remove the enhanced aggregation constructs from the custom SQL query.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03900: Internal EUL Error: Unable to generate query**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03901: Internal EUL Error: Unable to generate query**

**Cause:** An internal error has occurred in Oracle Business Intelligence Discoverer. User might be able to continue working, but the current operation may not have been performed correctly.

**Action:** Report the actions that immediately preceded this error to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03959: No joins found between component folders of complex folder with %1!s '%2!s'.**

**Cause:** An attempt was made to connect database not supported by Discoverer.

**Action:** Try connecting to database, whose version is supported by Oracle Business Intelligence Discoverer.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-SVR-03964: Connection to 8i Database not supported**

**Cause:** An attempt was made to connect to a database that is not supported by Oracle Business Intelligence Discoverer.

**Action:** Connect to a database whose version is supported by Oracle Business Intelligence Discoverer.

**Level:** 1

**Type:** ERROR

**Impact:** Process



---

## BI-VIEWER-00001 to BI-VIEWER-01245

**BI-VIEWER-00001: Empty input (or null input) is not allowed.**

**Cause:** Empty input (or null input) is not allowed.

**Action:** Input a non-null value.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-00002: Length of supplied value is too long.**

**Cause:** Supplied value length was too long.

**Action:** Shorten the length of the supplied value.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-00003: The following character is not valid: {0}**

**Cause:** An invalid character was supplied.

**Action:** Enter a valid character.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-00004: The following character is required: {0}**

**Cause:** Specified character is required.

**Action:** Enter data with the specified character.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-00005: Zero length and null strings are not allowed.**

**Cause:** Zero length and null strings are not allowed.

**Action:** Enter nonzero length or non-null strings.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-00006: Negative values are not allowed.**

**Cause:** Negative values were not allowed.

**Action:** Enter nonnegative values.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-00007: The numerical value entered is too low.**

**Cause:** The numerical value entered was too low than allowed.

**Action:** Enter a higher value.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-00008: The numerical value entered is too high.**

**Cause:** The numerical value entered was too high than allowed.

**Action:** Enter a lower value.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-00009: An error occurs while constructing cached Thin Bean for Portlet Provider.**

**Cause:** An error occurred while constructing cached Thin Bean for Portlet Provider.

**Action:** Contact the Oracle Business Intelligence Discoverer administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-00010: Oracle BI Discoverer is unable to read the configuration file. The following expression is invalid: {0}.**

**Cause:** Oracle BI Discoverer was unable to read the configuration file. provided expression was invalid.

**Action:** Enter a valid expression.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-00011: Oracle BI Discoverer is unable to read the configuration file. A number could not be derived from the following expression: {0}.**

**Cause:** Oracle BI Discoverer was unable to read the configuration file. A number could not be derived from the specified expression.

---

**Action:** Check the configuration file so that a number could be derived from the specified expression.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-00012: Oracle BI Discoverer is unable to read the configuration file. A value is required for the following expression: {0}.**

**Cause:** Oracle BI Discoverer was unable to read the configuration file . Value provided for the specified expression might be wrong.

**Action:** Revise the configuration file to provide a value for the specified expression.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-00013: Oracle BI Discoverer is unable to read the configuration file. The configuration file must be local.**

**Cause:** Oracle BI Discoverer was unable to read the configuration file. The configuration file must be local.

**Action:** Ensure that if the configuration file is local. If not, please make it local.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-00014: OracleAS Single Sign-On is not enabled for Oracle BI Discoverer. The customizations displayed here are default customizations, including the connection. To enable user customizations and the ability to save to Portal, enable OracleAS Single Sign-On for Oracle BI Discoverer.**

**Cause:** OracleAS Single Sign-On was not enabled for Oracle BI Discoverer. The customizations displayed were default customizations, including the connection.

**Action:** To enable user customizations and the ability to save to Oracle Portal, enable OracleAS Single Sign-On for Oracle BI Discoverer.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-00015: Attempting to launch Viewer using a private connection with OracleAS Single Sign-On disabled Oracle BI Discoverer application. This is not supported.**

**Cause:** An attempt was made to launch Viewer using a private connection with OracleAS Single Sign-On not enabled for Oracle BI Discoverer.

**Action:** Enable OracleAS Single Sign-On for Oracle BI Discoverer and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**BI-VIEWER-00016: No Default Connection details are found for this Viewer Request because OracleAS Single Sign-On is not enabled and this portlet is not displayed to unauthenticated users.**

**Cause:** OracleAS Single Sign-On was not enabled and this portlet is not displayed to unauthenticated users.

**Action:** Enable OracleAS Single Sign-On for Discoverer and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01001: A irrecoverable application error has occurred. Review the Oracle BI Discoverer application log file and consult with the Oracle Fusion Middleware administrator.**

**Cause:** A irrecoverable application error has occurred.

**Action:** Review the Oracle BI Discoverer application log file and consult with the Oracle Fusion Middleware administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01002: An error occurred while handling the event. See the application log for more details. {0}**

**Cause:** An error occurred while handling the event.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01003: The event requested is not supported. {0}**

**Cause:** The event requested is not supported.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01004: The application cannot find a method with the appropriate signature, invalid method or invalid return type: {0}.**

**Cause:** The application could not find a method with the appropriate signature. The method or return type was invalid.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01005: The application cannot find the mapping requested: {0}.**

**Cause:** The application could not find the mapping requested.



---

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01006: The application cannot find the required event parameter.**

**Cause:** The application could not find the required event parameter.

**Action:** Enter the event parameter again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01007: The application encounters an invalid state. {0}.**

**Cause:** The application encountered an invalid state.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01008: The link contains an invalid state string.**

**Cause:** The link contained an invalid state string.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01009: No state matches the state identifier provided. This can happen if user session timed out. Start the operation again.**

**Cause:** The session might have timed out.

**Action:** Start the operation again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01010: The specified state identifier is invalid. This can happen if you have mistakenly tried to type parameters on the URL.**

**Cause:** The user might have mistakenly tried to type parameters on the URL.

**Action:** Edit the URL. Check discoverer application guide for valid URL parameters.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01011: The configuration file was not found at the specified location or the location was invalid.**

---

**Cause:** The configuration file was not found at the specified location or the location was invalid.

**Action:** Provide a valid location, check discoverer configuration guide for the configuration file location.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01012: illegal access error, check the Discoverer application log for more details.**

**Cause:** An illegal access error occurred.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01013: Oracle BI Discoverer is unable to obtain a class instance. Check the Discoverer application log for more details.**

**Cause:** Oracle BI Discoverer was unable to get a class instance.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01014: Oracle BI Discoverer is unable to find a required class. Check the Discoverer application log for more details.**

**Cause:** Oracle BI Discoverer was unable to find a required class.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01015: Oracle BI Discoverer is unable to find a method with the required signature. Check the Discoverer application log for more details.**

**Cause:** Oracle BI Discoverer was unable to find a method with the required signature.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01016: Empty input is not allowed.**

**Cause:** Null value was not allowed for the specified input.

**Action:** Enter non empty value.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01017: The following character is not valid: {0}.**

**Cause:** An invalid character was specified.

**Action:** Specify a valid character.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01018: The following character is required: {0}.**

**Cause:** A required character was not specified.

**Action:** Enter the required character.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01019: Negative values are not allowed.**

**Cause:** One or more negative values were specified.

**Action:** Enter only positive values.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01020: The numerical value entered is too low.**

**Cause:** The numerical value entered was too low.

**Action:** Enter a higher value.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01021: illegal format for pair string**

**Cause:** Format of the pair string was illegal.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01022: A state string key is missing. (There was an odd number of values in the state string.)**

**Cause:** A state string key did not have an associated value. (There might be an odd number of values in the state string.)

**Action:** Provide an even number of values.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01023: The state string is missing a required key value pair: {0}.**

**Cause:** The state string did not contain a required key value pair.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01024: unexpected error during state string decompression**

**Cause:** An unexpected error occurred during state string decompression.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01025: The requested print options page does not exist.**

**Cause:** The requested print options page does not exist.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01026: Start from the connections page to create or edit a connection.  
Try again.**

**Cause:** An attempt was made to create or edit a connection.

**Action:** Try again, this time from the connections page.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01027: The remote user is different. Log out and reenter this application.**

**Cause:** The remote user has changed.

**Action:** Log out and reenter this application.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01028: The error handler supplied is not the correct type.**

**Cause:** The error handler supplied was not the correct type.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01029: Query execution is unsuccessful.**

**Cause:** Query execution was not successful.

**Action:** Try executing the query again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01030: The workbook or worksheet search fails.**

**Cause:** The workbook or worksheet search failed.

**Action:** Check whether the worksheet or workbook exists. If it does not, then specify another worksheet or workbook.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01031: Oracle BI Discoverer is unable to find the requested worksheet.**

**Cause:** Oracle BI Discoverer was unable to find the worksheet that was requested.

**Action:** Ensure that the worksheet exists, or specify worksheet workbook.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01032: Oracle BI Discoverer is unable to find the workbook.**

**Cause:** Oracle BI Discoverer was unable to find the workbook.

**Action:** Ensure that the workbook exists, or specify another workbook.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01033: cannot restore the worksheet state. Check the Discoverer application log for more details.**

**Cause:** Unable to restore the worksheet state.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01034: Oracle BI Discoverer is unable to restore the application state specified on the URL. Check the Discoverer application log for more details.**

**Cause:** Oracle BI Discoverer was unable to restore the application state specified on the URL.

**Action:** Check the Discoverer application log for more details.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01035: The specified connection type is invalid.**

**Cause:** An invalid connection type was specified.

**Action:** Specify a valid connection type.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01036: The specified preferences return page is invalid.**

**Cause:** An invalid preferences return page was specified.

**Action:** Specify a valid preferences return page.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01037: The specified locale string is invalid.**

**Cause:** An invalid locale string was specified.

**Action:** Specify a valid locale String.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01038: The connection store is in an invalid state.**

**Cause:** The connection store is in an invalid state.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01039: The connection list is currently unavailable.**

**Cause:** The connection list was unavailable.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01040: unable to create a new connection because user-defined connections are not enabled or connection management is currently disabled**

**Cause:** User-defined connections were not enabled or connection management was disabled.

**Action:** Enable user-defined connections and connection management.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01041: A connection does not exist for the given connection key.**

**Cause:** A connection did not exist for the given connection key.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01042: Oracle BI Discoverer is unable to connect. Check the Discoverer application log for more details.**

**Cause:** Oracle BI Discoverer was unable to connect.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01043: The specified connection type {0} is invalid.**

**Cause:** The specified connection type is invalid.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01044: The specified summary option is invalid.**

**Cause:** An invalid summary option was specified.

**Action:** Provide a valid summary option.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01045: The specified workbook type {0} is invalid.**

**Cause:** An invalid workbook type was specified.

**Action:** Change workbook type.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01046: The specified catalog type {0} is invalid.**

**Cause:** An invalid catalog type was specified.

**Action:** Change the catalog type.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01047: The specified Oracle Discoverer Beans connection type is invalid.**

**Cause:** An invalid Oracle Discoverer Beans connection type was specified.

**Action:** Provide a valid connection Type.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01048: The specified role is invalid.**

**Cause:** An invalid role was specified.

**Action:** Provide a valid role.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01049: The specified EUL is invalid.**

**Cause:** An invalid end user layer was specified.

**Action:** Provide a valid end user layer.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01050: The Oracle BI Discoverer Beans connection fails. Check the Discoverer application log for more details.**

**Cause:** The Oracle BI Discoverer Beans connection failed.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01051: The Oracle BI Discoverer Beans authentication fails. Check the Discoverer application log for more details.**

**Cause:** The Oracle BI Discoverer Beans authentication failed.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01052: No EULs are available for the given connection details.**

**Cause:** No end user layers (EULs) were available for the given connection details.

**Action:** Try another connection.

**Level:** 1



---

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01053: No responsibilities are available for the given connection details.**

**Cause:** No responsibilities were available for the provided connection details.

**Action:** Try another connection.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01054: An unknown error occurred.**

**Cause:** An unknown error occurred.

**Action:** Reconnect, or Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01055: No data is available for export.**

**Cause:** Work sheet export failed as no data was available for export.

**Action:** Check the worksheet data and try exporting again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01056: The document requested is no longer available. This can happen if user session times out or user log out and returns to the page using back or forward in the browser. Perform the export operation again.**

**Cause:** The requested document was not available. This can happen if the session times out or if the user logs out and returns to the page using back or forward in the browser.

**Action:** Perform export operation again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01057: No data is available for export. This is due to an issue within Oracle BI Discoverer. Contact Oracle Support Services.**

**Cause:** No data was available for export, due to an issue within Oracle BI Discoverer.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

---

**BI-VIEWER-01058: The specified export type is invalid. Choose a different export type.**

**Cause:** An invalid export type was submitted.

**Action:** Specify a valid export type.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01059: Parameters are not supported for OLAP data sources.**

**Cause:** Parameters were supplied for OLAP data sources, which are not supported.

**Action:** Use parameters for relational data sources.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01060: The state string key already exists. This is due to an issue within Oracle BI Discoverer. Contact Oracle Support Services.**

**Cause:** An attempt was made to provide a state string key that already exists, due to an issue within Oracle BI Discoverer.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**BI-VIEWER-01061: A gradient is set on a series item that does not exist.**

**Cause:** A gradient was set on a series item that does not exist.

**Action:** Reset the gradient on a series item that exists.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01062: The specified margin value is illegal.**

**Cause:** An illegal margin value was supplied.

**Action:** Try with a different value.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01063: The selected page orientation is illegal. Try with a different value.**

**Cause:** An illegal page orientation was selected.

**Action:** Try with a different value.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01064: The selected paper size is illegal. Contact the OracleAS Discoverer administrator.**

**Cause:** An illegal paper size was selected.

**Action:** Try with a different value.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01065: The value supplied for the selection of when to print the title, footnote, or page items is invalid.**

**Cause:** An illegal value was supplied for the selection of when to print the title, footnote, or page items.

**Action:** Try with different value.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01066: The specified scaling value is illegal. Try with a different value.**

**Cause:** An illegal scaling value was supplied.

**Action:** Try with a different value.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01067: The specified URL is invalid.**

**Cause:** The URL supplied was invalid.

**Action:** Specify a valid URL.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01068: The deferred event is invalid. Start the operation from the beginning.**

**Cause:** The deferred event was invalid.

**Action:** Start the operation from the beginning.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01069: The deferred request is malformed. The request cannot be processed.**

**Cause:** Because the deferred request was malformed, the request could not be processed.

---

**Action:** Try again with a different request.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01070: The specified attachment permission is invalid. It should be either "server" or "client".**

**Cause:** An invalid attachment permission was specified.

**Action:** Specify either "server" or "client"

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01071: The specified client type is invalid. A client type should be either "Viewer" or "Plus".**

**Cause:** An invalid client type was specified.

**Action:** Specify either "Viewer" or "Plus" .

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01072: An error occurs while removing security-sensitive parameters from the URL {0}.**

**Cause:** An error occurred while removing security-sensitive parameters from the URL

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01073: An invalid encoding type is found during string encoding.**

**Cause:** Invalid encoding type was found during string encoding.

**Action:** Change the encoding type to a valid one.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01074: An invalid encoding type is found during string decoding.**

**Cause:** Invalid encoding type was found during string decoding.

**Action:** Change the decoding type to a valid one.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01075: The specified sort direction {0} is invalid.**

---

**Cause:** An invalid sort direction was specified.

**Action:** Change the sort direction to a valid one.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01076: The requested page requires a connection that no longer exists. Select a connection from the list below and use the links provided in subsequent pages to navigate to the desired location.**

**Cause:** A page was requested that required a connection that no longer exists.

**Action:** Select a connection from the list provided, and use the links in subsequent pages to navigate to the desired location.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01077: A connection error. {0}**

**Cause:** A connection error has occurred.

**Action:** Check the Discoverer application log for more details

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01078: An error occurs while logging out. {0}**

**Cause:** An error occurred while logging out.

**Action:** Try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01079: The worksheet name does not exist as a parameter on the URL. The request is invalid.**

**Cause:** The worksheet name did not exist as a parameter on the URL.

**Action:** Provide valid URL with work sheet name in URL parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01080: The specified worksheet name or workbook name is invalid. The following character is invalid: {0}. Change the name and try again.**

**Cause:** An invalid worksheet or workbook name was specified.

**Action:** Change the name and try again

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**BI-VIEWER-01081: The specified user name is invalid. Change the user name and try again.**

**Cause:** An invalid user name was specified.

**Action:** Change the user name and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01082: The specified password is invalid. Change the password and try again.**

**Cause:** An invalid password was specified.

**Action:** Change the password name and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01083: The specified database is invalid. Change the database and try again.**

**Cause:** An invalid database was specified.

**Action:** Change the database and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01084: The specified end user layer (EUL) is invalid. Change the end user layer and try again.**

**Cause:** An invalid end user layer was specified.

**Action:** Change the end user layer and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01085: The specified connection name is invalid. Change the connection name and try again.**

**Cause:** An invalid connection name was specified.

**Action:** Change the connection name and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01086: The specified description is invalid. Change the description and try again.**

**Cause:** An invalid description was specified.

**Action:** Change the description and try again.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01087: The specified sender is invalid. Change the sender and try again.**

**Cause:** An invalid sender was specified.

**Action:** Change the sender and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01088: The specified recipient is invalid. Change the recipient and try again.**

**Cause:** An invalid recipient was specified.

**Action:** Change the recipient and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01089: The specified carbon copy (CC) is invalid. Change the CC and try again.**

**Cause:** An invalid carbon copy (CC) was specified.

**Action:** Change the CC and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01090: The specified blind carbon copy (BCC) is invalid. Change the BCC and try again.**

**Cause:** An invalid blind carbon copy (BCC) was specified

**Action:** Change the BCC and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01091: The specified subject is invalid. Change the subject and try again.**

**Cause:** An invalid subject was specified.

**Action:** Change the subject and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01092: The specified body is invalid. Change the body and try again.**

**Cause:** An invalid body was specified.

---

**Action:** Change the body and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01093: The specified connection key is invalid. Correct the connection key and try again.**

**Cause:** An invalid connection key was specified.

**Action:** Correct the connection key and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01094: The specified row or column value is invalid. The values specified must be greater than zero. Press "Back" button, change the values, and submit them again.**

**Cause:** The specified row or column value was not greater than zero, as required.

**Action:** Press "Back" button, change the values, and submit them again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01095: The specified graph height is invalid. Change the graph height and try again.**

**Cause:** An invalid graph height was specified.

**Action:** Change the graph height and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01096: The specified graph width is invalid. Change the graph width and try again.**

**Cause:** An invalid graph width was specified.

**Action:** Change the graph width and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01097: The specified page orientation is invalid. Change the page orientation and try again.**

**Cause:** An invalid page orientation was specified.

**Action:** Change the page orientation and try again.

**Level:** 1

**Type:** ERROR



---

**Impact:** Process

**BI-VIEWER-01098: The specified paper size is invalid. Change the paper size and try again.**

**Cause:** An invalid paper size was specified.

**Action:** Change the paper size and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01099: The specified right margin is invalid. Change the right margin and try again.**

**Cause:** An invalid right margin was specified.

**Action:** Change the right margin and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01100: The specified left margin is invalid. Change the left margin and try again.**

**Cause:** An invalid left margin was specified.

**Action:** Change the left margin and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01101: The specified bottom margin is invalid. Change the bottom margin and try again.**

**Cause:** An invalid bottom margin was specified.

**Action:** Change the bottom margin and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01102: The specified top margin is invalid. Change the top margin and try again.**

**Cause:** An invalid top margin was specified.

**Action:** Change the top margin and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01103: The specified scaling is invalid. Change the scaling and try again.**

**Cause:** An invalid scaling was specified.

**Action:** Change the scaling and try again.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01104: Oracle BI Discoverer Viewer cannot find a connection for the given connection key.**

**Cause:** Oracle BI Discoverer Viewer was unable to find a connection for the given connection key.

**Action:** Try again with different connection, and check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01105: Oracle BI Discoverer Viewer cannot retrieve the connection type for the specified connection.**

**Cause:** Oracle BI Discoverer Viewer was unable to retrieve the connection type for the specified connection.

**Action:** Try again with different connection, and check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01106: unable to retrieve connection list**

**Cause:** Unable to retrieve connection list.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01107: The locale specified is not available on this system. Choose a different locale.**

**Cause:** An unavailable locale was specified.

**Action:** Choose a different locale.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01108: error while creating the session, check for other errors.**

**Cause:** An error occurred while creating the session.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**BI-VIEWER-01109: cannot find the exported file, try again.**

**Cause:** The exported file was not found.

**Action:** Try to export again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01110: Oracle BI Discoverer Viewer is unable to scroll the graph to its proper position.**

**Cause:** Oracle BI Discoverer Viewer was unable to scroll the graph to its proper position.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01111: trying to validate the connection, but password is missing.**

**Cause:** The password was missing while trying to validate the connection.

**Action:** Provide a password.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01112: Oracle BI Discoverer Viewer cannot update the connection. Check for other errors.**

**Cause:** Oracle BI Discoverer Viewer was unable to update the connection.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01113: Oracle BI Discoverer Viewer cannot save the connection. Check for other errors.**

**Cause:** Oracle BI Discoverer Viewer was unable to save the connection.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01114: Nothing is selected to print. Either the crosstab, table, or graph must be selected in order to print.**

**Cause:** Nothing was selected to print.

**Action:** Select the crosstab, table, or graph to print.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01115: An error occurs while trying to perform the export. Try again.**

**Cause:** An error occurred while trying to perform the export.

**Action:** Try to export again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01116: The PDF generator cannot calculate the column widths.**

**Cause:** The PDF generator was unable to calculate the column widths.

**Action:** Specify the column widths and Check the log file for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01117: Oracle BI Discoverer Viewer cannot create the view toolbar.**

**Cause:** Oracle BI Discoverer Viewer was unable to create the view toolbar.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01118: The view tool event specified is not supported. {0}**

**Cause:** An unsupported view tool event was specified.

**Action:** Use another tool.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01119: The specified worksheet layout is invalid.**

**Cause:** An invalid worksheet layout was specified.

**Action:** Change to a valid worksheet layout.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01120: A worksheet must be open before performing this event.**

**Cause:** An attempt was made to perform an event, but the worksheet was not open.

**Action:** Open the worksheet, and try again.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**BI-VIEWER-01121: Oracle BI Discoverer Viewer did not have the open connection required to perform this event.**

**Cause:** Oracle BI Discoverer Viewer must have an open connection before performing this event.

**Action:** Open a connection.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01122: Oracle BI Discoverer Viewer cannot create the URL event with the supplied URL parameters. Correct the parameters and try again.**

**Cause:** Oracle BI Discoverer Viewer was unable to create the URL event in response to the supplied URL parameters.

**Action:** Correct the parameters, and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01123: The URL API parameter {0} is invalid. Correct the parameter, and try again.**

**Cause:** An invalid URL API parameter was specified.

**Action:** Correct the parameter, and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01124: Oracle BI Discoverer Viewer cannot find the data necessary to display the results of this event. Correct any errors, and try again.**

**Cause:** Oracle BI Discoverer Viewer was unable to find the necessary data for displaying the results of this event.

**Action:** Correct any errors, and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01125: Oracle BI Discoverer Viewer was unable to locate the definition file necessary to construct the results of this event. Contact the Oracle Fusion Middleware administrator.**

**Cause:** Oracle BI Discoverer Viewer was unable to locate the definition file necessary to construct the results of this event.

**Action:** Contact the Oracle Fusion Middleware administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**BI-VIEWER-01126: Oracle BI Discoverer Viewer cannot access the definition file necessary to construct the results of this event. Contact the Oracle Fusion Middleware administrator.**

**Cause:** Oracle BI Discoverer Viewer was unable to access the definition file necessary to construct the results of this event.

**Action:** Contact the Oracle Fusion Middleware administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01127: unable to generate a PDF using the current settings, change the settings by choosing the "Printable page" link in the actions section of the open worksheet**

**Cause:** Unable to generate a PDF using the current settings.

**Action:** Change the settings by choosing the "Printable page" link in the actions section of the open worksheet.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01128: Oracle BI Discoverer Viewer cannot find the warning type in the warning message. Contact the Oracle Fusion Middleware administrator.**

**Cause:** There was a warning message, but Oracle BI Discoverer Viewer was unable to find the warning type.

**Action:** Contact the Oracle Fusion Middleware administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01129: A workbook already exists with the name specified, and it is owned by another user. Specify a different name and try again.**

**Cause:** A workbook name was specified but could not be used, because it is owned by another user.

**Action:** Specify a different name and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01130: Changed preferences might affect the data. Rerun the query to enable these preferences in the currently open worksheet.**

**Cause:** Some preferences have changed that might affect the data in the open worksheet.

**Action:** Rerun the query so that these preferences can take effect in the currently open worksheet.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**BI-VIEWER-01131: Oracle BI Discoverer Viewer is unable to reconstitute to a different state while there is a deferred request. Use the back button in your browser to go back several pages and try again.**

**Cause:** Oracle BI Discoverer Viewer is unable to reconstitute to a different state while there is a deferred request.

**Action:** Use the back button in your browser to go back several pages, and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01132: Oracle BI Discoverer is unable to read the configuration file. A number cannot be derived from the following expression: {0}.**

**Cause:** Oracle BI Discoverer was unable to read the configuration file. A number could not be derived from the expression.

**Action:** Specify the number again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01133: Oracle BI Discoverer is unable to read the configuration file. A value is required for the following expression: {0}**

**Cause:** Oracle BI Discoverer was unable to read the configuration file. A value is required for the expression.

**Action:** Specify the value again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01134: Oracle BI Discoverer is unable to read the configuration file. The configuration file must be local.**

**Cause:** Oracle BI Discoverer was unable to read the configuration file. The configuration file must be local

**Action:** Provide the valid location again, check Discoverer configuration guide for configuration file location.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01135: error with the e-mail server message is not sent.**

**Cause:** The e-mail message was not sent due to an error with the e-mail server.

**Action:** Correct any errors pertaining to the server, and try again.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**BI-VIEWER-01136: The outgoing e-mail server cannot be found. Contact the Oracle Fusion Middleware administrator.**

**Cause:** The outgoing e-mail server could not be found.

**Action:** Contact the Oracle Fusion Middleware administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01137: Oracle BI Discoverer times out while sending your e-mail. The e-mail may be sent anyway.**

**Cause:** Oracle BI Discoverer timed out while sending your e-mail.

**Action:** E-mail may have been sent, if not sent it again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01138: Oracle BI Discoverer is unable to create an e-mail session.**

**Ensure that the e-mail server is accessible.**

**Cause:** Oracle BI Discoverer was unable to create an e-mail session.

**Action:** Ensure that the e-mail server is accessible.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01139: The e-mail attachment file size is too large. The size must be less than (KB): {0}.**

**Cause:** The e-mail attachment file size was too large.

**Action:** Reduce the file size.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01140: User lacks appropriate permissions to send server-side e-mail attachments.**

**Cause:** The user did not have the appropriate permissions to send server-side e-mail attachments.

**Action:** Obtain the permissions necessary to send server-side e-mail attachments.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01141: The e-mail cannot be sent successfully. Check the Discoverer application log for more details.**

**Cause:** The e-mail was not sent successfully.



---

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01142: deleting the e-mail attachment, click on the Send as e-mail link to send again.**

**Cause:** The e-mail attachment has been deleted.

**Action:** Click on the Send as e-mail link to send again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01144: unexpected error during state string compression.**

**Cause:** An unexpected error occurred during state string compression.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01143: The character encoding specified during message assembly is invalid.**

**Cause:** The character encoding that was used during message assembly was invalid.

**Action:** Attach and send mail again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01145: Oracle BI Discoverer cannot generate the PDF requested.**

**Cause:** Oracle BI Discoverer was unable to generate the PDF requested.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01146: The PDF printing status is invalid. Check the Discoverer application log for more details.**

**Cause:** The PDF printing status was invalid.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01147: The width specified for the column at position {0} is invalid.**

---

**Cause:** An invalid width was specified for the column.

**Action:** Change the column width specified.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01148: unable to open the worksheet requested: {0}**

**Cause:** Unable to open the worksheet requested.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01149: BI Beans cannot handle the event: {0}.**

**Cause:** The BI Bean was unable to handle the event.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01150: Query scheduling fails; the request cannot be processed.**

**Cause:** Query scheduling failed.

**Action:** Try to reschedule query and check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01151: unable to cancel query**

**Cause:** Unable to cancel query.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01152: Creation of the parameters component fails.**

**Cause:** Creation of the parameters component failed.

**Action:** Try creating the component again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01153: Creation of the list of values component fails. {0}**

**Cause:** Creation of the list of values component failed.

---

**Action:** Try creating the component again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01154: Cannot find a required parameter: {0}**

**Cause:** Could not find a required parameter.

**Action:** Specify the parameter again

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01155: The specified form class {0} is invalid.**

**Cause:** An invalid form class was specified.

**Action:** Specify a valid form class.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01156: The worksheet must be open to run a query.**

**Cause:** The worksheet was not open when the user tried to run a query.

**Action:** Open the worksheet.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01157: The initial setup is incorrect; the query cannot be run.**

**Cause:** The initial setup was not performed properly.

**Action:** Perform the initial setup again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01158: unable to fetch query estimate {0}**

**Cause:** Failed to fetch the query estimate.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01159: Oracle BI Discoverer is encountering a query state that was not expected. {0}**

**Cause:** Oracle BI Discoverer encountered a query state that was not expected.

**Action:** Check the Discoverer application log for more details.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01160: unable to apply selected parameters, check the Discoverer application log for more details**

**Cause:** Unable to apply selected parameters.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01161: The old password is invalid.**

**Cause:** The old password was entered incorrectly.

**Action:** Type the old password again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01162: new password or verification password are invalid**

**Cause:** Invalid new password or verification password.

**Action:** Type the new password and verification password again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01163: New passwords do not match**

**Cause:** The new password entered for verification did not match the new password.

**Action:** Type the new password and verification password again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01164: The specified workbook and worksheet {0} are invalid.**

**Cause:** An invalid workbook and worksheet were specified.

**Action:** Specify a valid worksheet and a valid workbook.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01165: The specified workbook {0} is invalid.**

**Cause:** An invalid workbook was specified.

**Action:** Specify a valid workbook.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01166: The specified worksheet {0} is invalid.**

**Cause:** An invalid worksheet was specified.

**Action:** Specify a valid worksheet.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01167: Oracle BI Discoverer is unable to retrieve the connection when opening the requested worksheet.**

**Cause:** Unable to retrieve the connection when opening the requested worksheet.

**Action:** Try to connect again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01168: Oracle BI Discoverer is unable to retrieve the end user layer when opening the requested worksheet.**

**Cause:** Unable to retrieve the EUL when opening the requested worksheet.

**Action:** Try to connect again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01169: Oracle BI Discoverer is unable to retrieve the workbook when opening the requested worksheet.**

**Cause:** Unable to retrieve the connection when opening the requested workbook.

**Action:** Try to connect again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01170: Oracle BI Discoverer is unable to retrieve the requested worksheet.**

**Cause:** Unable to retrieve the requested worksheet.

**Action:** Try to connect again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01171: The link contains an invalid state string. None of the expected connection details are found.**

---

**Cause:** None of the expected connection details are found.

**Action:** Provide the connection details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01172: The link contains an invalid state string. None of the expected workbook details are found.**

**Cause:** None of the expected workbook details are found.

**Action:** Provide the workbook details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01173: Oracle BI Discoverer is unable to restore the explorer state.**

**Cause:** The explorer state was invalid.

**Action:** Open the worksheet or work book , and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01174: Oracle BI Discoverer is unable to export the graph. Check the Discoverer application log for more details.**

**Cause:** Oracle BI Discoverer was unable to export the graph

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01175: Oracle BI Discoverer is unable to export the Web query file. Check the Discoverer application log for more details.**

**Cause:** Oracle BI Discoverer was unable to export the Web query file.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01176: The export operation fails, check the Discoverer application log or other errors on the screen for more details.**

**Cause:** Export operation failed.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**BI-VIEWER-01177: The provided information must be in the form of <host>:<port>:<sid>.**

**Cause:** An invalid host port SID was specified.

**Action:** Resubmit the information in <host>:<port>:<sid> form.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01178: Oracle BI Discoverer cannot determine the connection type.**

**Cause:** Oracle BI Discoverer was unable to determine the connection type.

**Action:** Specify the correct connection type and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01179: Oracle BI Discoverer is unable to complete the connection initialization.**

**Cause:** A connection initialization problem occurred.

**Action:** Initialize the connection again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01180: Oracle BI Discoverer is unable to complete the session initialization.**

**Cause:** A session initialization problem occurred.

**Action:** Initialize the session again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01181: Oracle BI Discoverer is unable to completely close the session.**

**Cause:** Oracle BI Discoverer was unable to completely close the session.

**Action:** Try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01182: Oracle BI Discoverer is unable to authenticate using the password provided. This can happen due to an invalid password or because the password was lost while using back, forward, or refresh in your browser. Enter the password again to continue.**

**Cause:** Either the password was invalid, or the password was lost while using back, forward or refresh in the browser.

**Action:** Provide a valid password.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01183: Session hijacking is not supported for OLAP connections.**

**Cause:** An unsupported action was attempted.

**Action:** Do not try session hijacking for OLAP Connections.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01184: An error occurs while setting options. Check the Discoverer application log for more details.**

**Cause:** Options were not set appropriately.

**Action:** Reset the options. Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01185: An error occurs while setting page items. Check the Discoverer application log for more details.**

**Cause:** Page items were not set appropriately]

**Action:** Set page items correctly. Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01186: Cannot retrieve connection list . Check the Discoverer application log for more details.**

**Cause:** Connection list could not be retrieved.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01187: Cannot retrieve connection details. Check the Discoverer application log for more details.**

**Cause:** Connection details could not be retrieved.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01188: Oracle BI Discoverer cannot find the workbook owner. Check the Discoverer application log for more details.**



---

**Cause:** Oracle BI Discoverer could not find the workbook owner.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01189: Oracle BI Discoverer cannot determine if the worksheet contains page items. Check the Discoverer application log for more details.**

**Cause:** Oracle BI Discoverer was unable to determine if the worksheet contains page items.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01190: Oracle BI Discoverer cannot create the sort customize page. Check the Discoverer application log for more details.**

**Cause:** Oracle BI Discoverer was unable to create the sort customize page.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01191: Oracle BI Discoverer cannot create the format customize page. Check the Discoverer application log for more details.**

**Cause:** Oracle BI Discoverer was unable to create the format customize page.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01192: Oracle BI Discoverer cannot create the layout customize page. Check the Discoverer application log for more details.**

**Cause:** Oracle BI Discoverer was unable to create the layout customize page.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01193: Oracle BI Discoverer cannot create the drill page. Check the Discoverer application log for more details.**

**Cause:** Oracle BI Discoverer was unable to create the drill page.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01194: Oracle BI Discoverer cannot create the save as dialog. Check the Discoverer application log for more details.**

**Cause:** Oracle BI Discoverer was unable to create the save as dialog.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01195: An error occurs while linking or unlinking the layout. Check the Discoverer application log for more details.**

**Cause:** An error occurred while linking or unlinking the layout.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01196: Oracle BI Discoverer is unable to save the workbook.**

**Cause:** Oracle BI Discoverer was unable to save the workbook.

**Action:** Verify that the necessary saving permissions are assigned; if not, try save as.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01197: The specified drill-out URL is invalid. Correct the URL and try again.**

**Cause:** The drill-out URL specified was invalid.

**Action:** Correct the URL and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01198: Error while processing the specified link. Check the Discoverer application log for more details.**

**Cause:** An error occurred while processing the specified link.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01199: Invalid or unsupported protocol {0}**

**Cause:** An invalid or unsupported protocol was supplied.

**Action:** Change the protocol.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01200: Oracle BI Discoverer is unable to open the last saved version of the workbook or worksheet requested.**

**Cause:** Oracle BI Discoverer was unable to open the last saved version of the workbook or worksheet requested.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01201: unable to open workbook because item "{0}" is missing**

**Cause:** Unable to open workbook because item is missing.

**Action:** Specify the missing item.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01202: Form field validation fails. Fix the error and try again.**

**Cause:** The form field validation failed.

**Action:** Correct the form fields, and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01203: The destination for the preferences page is invalid.**

**Cause:** An invalid destination was found for the preferences page.

**Action:** Try again with a valid destination.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01204: The query prediction warning value is invalid. Change the value and try again.**

**Cause:** An invalid query prediction warning value was specified.

**Action:** Provide a valid value, and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01205: The query time limit value is invalid. Change the value and try again.**

**Cause:** An invalid query time limit was specified.

---

**Action:** Provide a valid query time limit value.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01206: The query maximum rows limit value is invalid. Change the value and try again.**

**Cause:** An invalid query maximum rows limit was specified.

**Action:** Provide a valid query maximum rows limit value.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01207: The query incremental fetch value is invalid. Change the value and try again.**

**Cause:** An invalid query incremental fetch valid was specified.

**Action:** Provide a valid query incremental fetch value.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01208: The LOV time limit value is invalid. Change the value and try again.**

**Cause:** An invalid LOV time limit value was specified.

**Action:** Provide a valid LOV time limit value.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01209: The specified measurement unit for printing is invalid. Change the value and try again.**

**Cause:** An invalid measurement unit was specified for printing.

**Action:** Provide a valid measurement unit value used for printing, and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01210: The specified axis label type value is invalid. Change the value and try again.**

**Cause:** An invalid axis label type value was specified.

**Action:** Provide a valid axis label value, and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**BI-VIEWER-01211: The specified rows per page value is invalid. Change the value and try again.**

**Cause:** An invalid rows per page value was specified.

**Action:** Specify a valid rows per page value.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01212: The specified columns per page value is invalid. Change the value and try again.**

**Cause:** An invalid columns per page value was specified.

**Action:** Specify a valid columns per page value.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01213: The specified summary data value is invalid. Change the value and try again.**

**Cause:** An invalid summary data value was specified.

**Action:** Specify a valid summary data value.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01214: The specified locale is invalid. Change the value and try again.**

**Cause:** An invalid locale was specified.

**Action:** Specify a valid locale.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01215: The integer value must be between the following two values: {0}**

**Cause:** An invalid integer was specified.

**Action:** Specify a value between the two given values.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01216: The visible option must be set to ALL or DISPLAYED.**

**Cause:** The visible option was not set to ALL or DISPLAYED.

**Action:** Set the visible option to ALL or DISPLAYED.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**BI-VIEWER-01217: Oracle BI Discoverer is unable to generate PDF documents as the PDF printing pool is no longer valid. Restart the application and try again.**

**Cause:** The PDF printing pool was no longer valid.

**Action:** Restart Application.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01218: The specified graph position is invalid. Contact the Oracle Fusion Middleware administrator.**

**Cause:** An invalid graph position was specified.

**Action:** Contact the Oracle Fusion Middleware administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01219: The Oracle BI Discoverer Plus plugin URL is invalid. Contact the Oracle Fusion Middleware administrator.**

**Cause:** An invalid Oracle BI Discoverer Plus plugin URL was specified.

**Action:** Contact the Oracle Fusion Middleware administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01220: No page sizes are configured for printing, add at least one page size to the list of available page sizes.**

**Cause:** No page size configured for printing.

**Action:** Configure the page size for printing.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01222: An attribute is missing or is invalid.**

**Cause:** An attribute was missing or was invalid.

**Action:** Provide a valid attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01221: The workbook no longer exists.**

**Cause:** The workbook has been deleted.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**BI-VIEWER-01223: A calculation is missing or is invalid.**

**Cause:** A calculation was missing or was invalid.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01224: A dimension is missing or is invalid.**

**Cause:** A dimension was missing or was invalid.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01225: A hierarchy is missing or is invalid.**

**Cause:** A hierarchy was missing or was invalid.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01226: A level is missing or is invalid.**

**Cause:** A level was missing or was invalid.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01227: A measure is missing or is invalid.**

**Cause:** A measure was missing or was invalid.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01228: invalid query definition; cannot load the query.**

**Cause:** An invalid query definition was supplied.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01229: A saved selection is missing or is invalid.**

---

**Cause:** A saved selection was missing or was invalid.

**Action:** See the application log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01231: Removing the worksheet to allow work to continue. Edit the worksheet using Oracle BI Discoverer Plus for OLAP to correct the problem.**

**Cause:** Worksheet has been removed to allow user to continue.

**Action:** Edit the worksheet using Oracle BI Discoverer Plus for OLAP to correct the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01232: This worksheet may not display data correctly. Edit this worksheet using Oracle BI Discoverer Plus for OLAP to correct the problem.**

**Cause:** Worksheet may not display data correctly.

**Action:** Edit the worksheet using Oracle BI Discoverer Plus for OLAP.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01233: The developer key is not unique.**

**Cause:** The developer key was not unique.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01234: The workbook already exists.**

**Cause:** The workbook has been modified by another user.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01235: The workbook content is altered by another user.**

**Cause:** The workbook has been modified by another user.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process



---

**BI-VIEWER-01236: unable to open workbook**

**Cause:** Unable to open workbook.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01237: unable to save the workbook**

**Cause:** Unable to save the workbook.

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01238: The specified developer key is illegal.**

**Cause:** An illegal developer key was specified.

**Action:** Specify a legal developer key.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01239: The specified name is invalid.**

**Cause:** An invalid name was specified.

**Action:** Specify a valid name.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01240: insufficient database privileges to save this workbook**

**Cause:** The user did not have the necessary privileges to save workbook.

**Action:** Obtain the necessary privileges to save the workbook. Contact the OracleAS Discoverer administrator to obtain this.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01241: insufficient query privileges to save this workbook**

**Cause:** The user did not have the necessary privileges to save workbook.

**Action:** Obtain the necessary privileges to save the workbook. Contact the OracleAS Discoverer administrator to obtain this.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**BI-VIEWER-01243: Zero length and null strings are not allowed.**

**Cause:** Illegal string values were supplied.

**Action:** Enter proper string values.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01242: The workbook was not found.**

**Cause:** The workbook was not found

**Action:** Check the Discoverer application log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01244: The PDF document requested is no longer available. This can happen if user session times out or user log out and come back to the page using back or forward in the browser. Perform the PDF generation again.**

**Cause:** The session timed out, or the user logged out and returned to this page using back or forward in the browser.

**Action:** Perform the PDF generation again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**BI-VIEWER-01245: Oracle BI Discoverer cannot read the configuration file. The following expression is invalid: {0}.**

**Cause:** Oracle BI Discoverer was unable to read the configuration file might be a wrong expression specified in it.

**Action:** Check the configuration file location and specified invalid expression again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

## BPM-09708 to BPM-40011

**NOTE:** Some errors are shared between SOA and BPM, and their prefix may be "BPM" instead of the correct prefix "ORABPEL". However, the error number is always accurate. If you cannot locate a particular error in this file -- if the prefix does not match with the error number, then consider the error number while searching for a solution.

**BPM-09708: Error while querying workflow task {0}**

**Cause:** Error while querying workflow task {0}

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-09713: Invalid logical operator in predicate**

**Cause:** An invalid logical operator was used in the predicate.

**Action:** Specify a valid logical operator (AND or OR) for the predicate.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-09714: Invalid predicate operator**

**Cause:** Invalid predicate operator {0}

**Action:** Specify a valid logical operator for the predicate.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-09715: Invalid predicate operator for list values**

**Cause:** Invalid predicate operator for list values. List values are only supported for IN and NOT\_IN operator

**Action:** Use appropriate operator in the predicate for list values.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-09716: Invalid value type for predicate**

**Cause:** Invalid value type {0} for predicate column type {1}

**Action:** Provide a valid value type for the predicate specified. Refer to TableConstants for data types

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-09717: Predicate values are null**

**Cause:** Predicate values are null for operator {0}

**Action:** Provide a valid predicate value for the predicate.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-09719: Trying to update a deleted task {0}**

**Cause:** The task {0} was already deleted.

**Action:** Execute the query to fetch new tasks.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-09732: Persistency service internal error**

**Cause:** Persistency service internal error

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10000: Dynamic Exception Test Case.**

**Cause:** Dynamic Exception Test Case thrown: {0}

**Action:** This error happens in dynamic exception test case sceannrios. Refer to the soainfra log files for details and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10101: Error while updating task**

**Cause:** Error while updating task {0}

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**BPM-10107: Error in withdrawing task**

**Cause:** Error while withdrawing task {0}.

**Action:** Check the error stack and fix the cause of the error. Contact Oracle Support Services if the error persists.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10129: Notification for task could not be processed**

**Cause:** Notification for task {2} could not be processed.

**Action:** Make sure that the notification configuration is correct and the messages are specified correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10197: Error in computing workflow auto release duration**

**Cause:** Error in computing workflow auto release duration for task "{0}".

**Action:** Make sure that the auto release configuration is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10199: Error in computing the next workflow reminder time**

**Cause:** Error in computing the next workflow reminder time for task "{0}".

**Action:** Make sure that the notification reminder configuration is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10200: Error in workflow reminder configuration**

**Cause:** Error in workflow reminder configuration for task "{0}". Reminders are configured in the routing slip XML file.

**Action:** Verify that the routing slip file is valid and conforms to its schema. The common errors are invalid RECCURENCE integer value, invalid RELATIVE value, invalid DURATION value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10206: Error in retrieving task metadata**

**Cause:** Error in retrieving task metadata because the task is no longer valid.

**Action:** Only valid tasks can be looked up.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10207: Error in retrieving task metadata**

**Cause:** Error in retrieving task metadata because because business process "{1}" version "{2}" that created the task is either undeployed or turned off in the domain "{0}".

**Action:** If the process is undeployed, the task is no longer valid. If the process was turned off, the task metadata can be retrieved when the process state is turned on.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10301: Email account does not exist**

**Cause:** Email Account {0} does not exist

**Action:** Check Workflow Notification Configuration. Verify that email account is configured

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10302: Email account already exists**

**Cause:** Email account {0} already exists

**Action:** Check Workflow Notification Configuration. Ensure that each account has unique name

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10303: Fax cover page details does not exist**

**Cause:** Fax cover page details for cover page {0} does not exist

**Action:** Check Workflow Notification Configuration. Verify that fax cover page exists

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10304: Fax cover page details already exist**

**Cause:** Fax cover page details for cover page {0} already exists

**Action:** Check Workflow Notification Configuration. Ensure that a page detail is not entered twice

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**BPM-10305: Illegal Argument**

**Cause:** name cannot be null

**Action:** Check Workflow Notification Configuration. Configuration name cannot be null

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10306: Illegal Argument**

**Cause:** Old name or new name cannot be null

**Action:** Check Workflow Notification Configuration. Configuration name cannot be null

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10307: Illegal Argument**

**Cause:** name, file location or mimetype cannot be null

**Action:** Check Workflow Notification Configuration. name, file location or mimetype cannot be null

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10310: xml parsing error in configuration file**

**Cause:** Error in parsing notification service configuration file {}

**Action:** Internal Error. Check Workflow Notification Configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10311: Email protocol not supported**

**Cause:** Email protocol {} is not supported

**Action:** Check Workflow Notification Configuration. Change Email protocol.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10312: Invalid Post Read Operation**

**Cause:** Invalid Post Read Operation

**Action:** Protocol specified does not support Post Read Operation. Modify Workflow Notification Configuration.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-10313: No Outgoing e-mail settings**

**Cause:** E-mail account {0} does not have outgoing e-mail settings

**Action:** Check Workflow Notification Configuration. Configure outgoing e-mail settings

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10314: No General e-mail settings**

**Cause:** E-mail account {0} does not have general e-mail settings

**Action:** Check Workflow Notification Configuration. Configure general e-mail settings

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10315: No Incoming e-mail settings**

**Cause:** E-mail account {0} does not have incoming e-mail settings

**Action:** Check Workflow Notification Configuration. Configure Incoming e-mail settings

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10316: E-mail Receiver already associated**

**Cause:** An e-mail receiver is already associated with {0} e-mail account

**Action:** Internal Error. Ensure that only one receiver is registered for an e-mail account.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10317: E-mail folder does not exist**

**Cause:** E-mail folder {0} does not exist

**Action:** Check Workflow Notification Configuration. Verify folder name in Incoming e-mail settings

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10318: Cannot connect to iAS Wireless notification webservice**

**Cause:** Cannot connect to iAS wireless notification webservice running at {0}

**Action:** Check Workflow Notification Configuration. Configure IAS Wireless settings



---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10319: iAS Wireless notification error**

**Cause:** iAS Wireless notification error

**Action:** Check IAS Wireless settings in Notification Configuration

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10320: iAS Wireless settings not configured**

**Cause:** iAS Wireless settings not configured

**Action:** Check IAS Wireless settings in Notification Configuration

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10321: Notification Channel not supported**

**Cause:** Notification Channel {0} is not supported

**Action:** IAS Wireless does not support requested channel.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10322: Illegal Argument**

**Cause:** Folder Name cannot be null

**Action:** Check Workflow Notification Configuration. Folder Name for Post Read Operation cannot be null.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10323: Internal Error**

**Cause:** Cannot create {0} object

**Action:** Refer to the log file that is configured for oracle.soa.services.notification for more details on this error and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10324: Cannot read fax cover page file**

**Cause:** Cannot read fax cover page from file {0}

**Action:** Check Workflow Notification Configuration. Ensure that the FAX cover page exists as specified in configuration.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10325: Mime-Type not supported**

**Cause:** mime-type {0} is not supported for channel {1}

**Action:** Internal Error. Ensure that payload content's mime type is one of supported types.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10326: Illegal Argument**

**Cause:** From account is not set in e-mail payload

**Action:** Check Workflow Notification Configuration. From account is not set in payload.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10327: From Account is not configured**

**Cause:** From account {0} is not configured

**Action:** Check Workflow Notification Configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10328: Error in sending e-mail message**

**Cause:** Error in sending e-mail message

**Action:** Check Workflow Notification Configuration. Ensure that the Email Server could be connected.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10329: user-id not set**

**Cause:** user-id field is not set in the user payload

**Action:** Internal Error. Payload does not contain user id

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10330: group-id is not set**

**Cause:** group-id field is not set in the group payload

**Action:** Internal Error. Payload does not contain group id

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10331: Could not send notification to user**

**Cause:** Could not send notification to user {0}

**Action:** Check Workflow Notification Configuration. Ensure that underlying channels are configured.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10332: Error in post-read operation**

**Cause:** Error while doing post-read operation on e-mail account {0}

**Action:** Check Workflow Notification Configuration. Check folder name and post read operation for incoming setting.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10333: Error in reading e-mail message**

**Cause:** Error in reading e-mail message from account {0}

**Action:** Check Workflow Notification Configuration. Ensure that the Email Server could be connected.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10334: Error in closing e-mail folder**

**Cause:** Error in closing e-mail folder {0}

**Action:** Check Workflow Notification Configuration. Verify folder name in incoming setting.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10335: Error in notification service initialization**

**Cause:** Error in notification service initialization

**Action:** Internal Error. Ensure that the Notification Configuration file is valid and could be loaded.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10336: Invalid recipient address**

---

**Cause:** Recipient address specified for {0} notification is invalid : {1}

**Action:** Check Workflow Notification Configuration. Ensure that Email/IM recipient address is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10337: Invalid entry in workflow-notification-config.xml**

**Cause:** Invalid configuration specified for {0}

**Action:** Please ensure that notification component is configured correctly

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10338: Incoming message could not be processed**

**Cause:** Incoming message could not be processed

**Action:** Ensure that the incoming response message is not corrupted.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10339: Error while sending auto reply**

**Cause:** Could not send {0} auto reply

**Action:** Internal Error. Ensure that the message being replied to is not corrupted.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10340: Error while Receiving response**

**Cause:** Could not process received message

**Action:** Ensure that incoming accounts in human workflow Mailer and Email Driver match and are configured correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10341: Error while Sending test notification**

**Cause:** Could not send test notification

**Action:** Ensure that human workflow mailer and underlying driver are configured correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**BPM-10342: Could not send notification**

**Cause:** Error while sending {0} notification

**Action:** Check configuration of underlying Channel specific driver.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10343: Error while creating notification content**

**Cause:** Could not create notification content

**Action:** Ensure that the files being used for attachment exist and not corrupted.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10344: Could not send notification**

**Cause:** Could not send {0} notification, since notification mode is set to {1}

**Action:** Ensure that Notification Mode in workflow-notification-config is set to either EMAIL or ALL to send email notifications. For rest of the channels it should be set to ALL

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10345: Error in Notification Service startup**

**Cause:** Could not start notification service

**Action:** Failed to start notification service. This is a system error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10346: Error in Notification Service shutdown**

**Cause:** Could not shutdown notification service correctly

**Action:** Errors while notification service shutdown. This is a system error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10347: Cannot send Notification to specified address**

**Cause:** Cannot send {0} notification to {1} address. The address is being marked as 'invalid' and no further notification would be sent to this address.

**Action:** Make sure that : the address specified is correct; the Email/Gateway server is up and running. Once the problem is corrected, please remove the address from invalid address list using EM.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**BPM-10348: Incoming message content is invalid**

**Cause:** Incoming message could not be processed due to invalid content

**Action:** Please ensure that the response message is not corrupted; Actionable notifications should be responded from the same email account to which it was sent.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10349: No NID Placeholder**

**Cause:** Incoming message content does not contain Notification ID placeholders

**Action:** Please ensure that the response message is not corrupted

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10350: Incoming message could not be processed**

**Cause:** Incoming message {0} could not be processed

**Action:** Please ensure that Human-Workflow Mailer is correctly configured also ensure that the response message is not corrupted

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10351: Underlying SDPMESSAGING layer could not send notification.**

**Cause:** Underlying SDPMESSAGING layer could not send {0} Notification(MessageId:{1}) to {2}.

**Action:** Possible causes : SDPMessaging Driver not configured; Invalid 'To' Address; Email server/Messaging gateway is down; using IP address as part of email id insted of domain name;

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10352: Actionable Email has been responded from a different account.**

**Cause:** Actionable Email had been sent to {0}, but received response from {1}.

**Action:** Actionable notifications should be responded from the same email account to which it was sent.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10353: Could not register/un register/fetch spam sources**

---

**Cause:** Could not register/un register/fetch spam sources: {0}  
**Action:** Possible cause : Invalid address is being registered/unregistered

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10500: Illegal Action name**

**Cause:** Illegal Action name "{0}"

**Action:** Unsupported action by name "{0}"

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10501: Illegal argument**

**Cause:** Illegal argument

**Action:** This is because an unexpected value, possibly null, was passed as an argument. Check the error stack and fix the cause of the error. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10502: Could not get Application role grantees**

**Cause:** Failed to get Grantees to Application role "{0}" for application identified by "{1}"

**Action:** Check if the application role exists and has grantees in the repository associated with the application. Check the error stack and fix the cause of the error. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10503: Could not get granted roles to Application role**

**Cause:** Failed to get Granted roles to Application role "{0}" for application identified by "{1}"

**Action:** Check if the application role exists and has granted roles in the repository associated with the application. Check the error stack and fix the cause of the error. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10504: Identity "{0}" membership in group "{1}" in configuration "{2}" could not be checked.**

**Cause:** Error in checking membership of identity "{0}" in group "{1}" in configuration "{2}".

---

**Action:** Please make sure that both the identity name and group name are valid and exist in the repository. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10505: Service "{0}" in configuration "{1}" could not be initialized.**

**Cause:** Error in initializing service "{0}" in configuration "{1}".

**Action:** Please make sure that identity service configuration is well formed and correct. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10506: Cannot get roles**

**Cause:** Cannot get roles for identity "{0}" through configuration "{1}"

**Action:** The underlying APIs threw an exception. Check if the repository is configured properly and available. Check the error stack and fix the cause of the error. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10507: Only SSO authentication allowed.**

**Cause:** Only SSO based authentication is allowed.

**Action:** Refer workflow configurations to change this policy. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10508: Error invoking remote service method.**

**Cause:** Error occurred while invoking the remote position service method "{0}" for id "{1}"

**Action:** Ensure that a remote position service provider is configured correctly, the service is accessible and is active. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10509: User not found**

**Cause:** User "{0}" is not found in configuration "{1}"

**Action:** Check if the user exists in the repository specified by the configurations. Check the error stack and fix the cause of the error. Contact oracle support if error is not fixable.



---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10510: Application role not found**

**Cause:** Application role "{0}" could not be found for application identified by "{1}"

**Action:** Check if the application role exists in the repository associated with the application. Check the error stack and fix the cause of the error. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10511: Group not found**

**Cause:** Group "{0}" is not found in configuration "{1}"

**Action:** Check if the group exists in the repository specified by the configurations. Check the error stack and fix the cause of the error. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10512: Cannot get application role "{0}" for application identified by "{1}"**

**Cause:** Cannot get role "{0}" from configuration "{1}"

**Action:** Check if the application role exists in the repository associated with the application. Check the error stack and fix the cause of the error. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10513: Cannot get application roles from application identified by "{0}"**

**Cause:** An error occurred while getting application roles from application identified by "{0}"

**Action:** The underlying APIs threw an exception. Check the error stack and fix the cause of the error. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10514: Cannot get group**

**Cause:** Cannot get group "{0}" for configuration "{1}"

**Action:** The underlying APIs threw an exception. Check the error stack and fix the cause of the error. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-10515: Cannot get groups**

**Cause:** An error occurred while getting groups from configuration "{0}"

**Action:** The underlying APIs threw an exception. Check the error stack and fix the cause of the error. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10516: Cannot find user**

**Cause:** An error occurred while getting user "{0}" from configuration "{1}"

**Action:** Check if the user exists in the repository specified by the configurations. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10517: Cannot get users**

**Cause:** An error occurred while getting users from configuration "{0}"

**Action:** The underlying APIs threw an exception. Check the error stack and fix the cause of the error. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10518: Failed to load Identity Service Configuration**

**Cause:** An error occurred while loading configurations from "{0}"

**Action:** Ensure that the identity service configurations are well formed and correct. Check the error stack and fix the cause of the error. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10520: Invalid application role name**

**Cause:** Invalid application role name "{0}"

**Action:** Specify a valid application role name. Check the error stack and fix the cause of the error. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10521: Invalid group name**

**Cause:** Invalid group name "{0}"

---

**Action:** Specify a valid role name. Check the error stack and fix the cause of the error. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10522: Manager with title "{0}" not found.**

**Cause:** No manager with title "{0}" in management chain for user "{1}" in configuration "{2}"

**Action:** Given title "{0}" was not found among management chain for specified user "{1}" in configuration "{2}"

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10523: Hierarchy Provider "{0}" could not be loaded correctly.**

**Cause:** Error occurred while loading configured hierarchy provider "{0}", in the identity service configuration.

**Action:** Check the log file for errors, check hierarchy service provider "{0}" configurations and make sure provider service is accessible and functional.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10528: Identity Service Authentication failure**

**Cause:** Identity Service Authentication failure

**Action:** Either the user name or password are incorrect. Check the error stack and fix the cause of the error. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10536: Identity service provider not found**

**Cause:** Identity service provider not found

**Action:** Ensure that a provider corresponding to the operation being performed is configured. Check the error stack and fix the cause of the error. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10537: user locale not found**

**Cause:** user locale not found

**Action:** Ensure that the user locale is passed while calling the operation. Check the error stack and fix the cause of the error. Contact oracle support if error is not fixable.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10540: Cannot find specified user in management chain**

**Cause:** Cannot find specified user "{0}" in management chain for user "{1}" in configuration "{2}"

**Action:** User "{0}" is not in management chain for user "{1}" in configuration "{2}".

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10541: Cannot find context "{0}" in JPS configuration**

**Cause:** Cannot find context "{0}" in JPS configuration

**Action:** Ensure that the JPS configuration file is well formed and has the specified context. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10542: Cannot set context "{0}".**

**Cause:** Cannot set context "{0}".

**Action:** Ensure that the JPS configuration file is well formed and has the specified context. Check the error stack and fix the cause of the error. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10543: Unsupported filter**

**Cause:** Specified search filter is unsupported or contains error.

**Action:** Correct the search filter. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10546: Unsupported attribute**

**Cause:** Attribute "{0}" is not supported

**Action:** Ensure that the attribute is not null. Refer to the documentation for supported attributes. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10551: Custom Identity Service class cannot be loaded**

---

**Cause:** Identity Service cannot load "{0}" class

**Action:** Check whether the file "{0}" in the classpath. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10555: Identity Service Configuration error**

**Cause:** Identity Service Configuration has error

**Action:** Please refer to the identity service configuration guidelines and correct the Identity Service configurations. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10557: Error in identity service XPath extension function ora:getManager**

**Cause:** Error in executing identity service XPath extension function ora:getManager for user name "{0}" in configuration "{1}".

**Action:** Please make sure that the user name is valid and exists in the repository and is associated with a manager. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10558: Error in identity service XPath extension function ora:getUserProperty**

**Cause:** Error in executing identity service XPath extension function ora:getUserProperty for property "{0}" for user name "{1}" for configuration "{2}".

**Action:** Please make sure that the user name is valid and exists in the repository. Also ensure that the property has been defined for the user. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10559: Error in identity service XPath extension function ora:getGroupProperty**

**Cause:** Error in executing identity service XPath extension function ora:getGroupProperty for property "{0}" for group name "{1}" for configuration "{2}".

**Action:** Please make sure that the group name is valid and exists in the repository. Also ensure that the property has been defined for the group. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**BPM-10560: Error in identity service XPath extension function ora:lookupUser**

**Cause:** Error in executing identity service XPath extension function ora:lookupUser for user name "{0}" in configuration "{1}".

**Action:** Please make sure that the user name is valid and exists in the repository. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10561: Error in identity service XPath extension function ora:lookupGroup**

**Cause:** Error in executing identity service XPath extension function ora:lookupGroup for group name "{0}" in configuration "{1}".

**Action:** Please make sure that the group name is valid and exists in the repository. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10562: Error in identity service XPath extension function ora:isUserInRole**

**Cause:** Error in executing identity service XPath extension function ora:isUserInRole for user "{0}" and group "{1}" in configuration "{2}".

**Action:** Please make sure that both the user name and group name are valid and exist in the repository. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10563: Error in identity service XPath extension function ora:getReportees**

**Cause:** Error in executing identity service XPath extension function ora:getReportees for user name "{0}" for configuration "{1}".

**Action:** Please make sure that the user name is valid and exists in the repository. Also ensure that reportees to this user exist. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10564: Error in identity service XPath extension function ora:getUsersInGroup**

**Cause:** Error in executing identity service XPath extension function ora:getUsersInGroup for group name "{0}" in configuration "{1}".

**Action:** Please make sure that the group name is valid and exists in the repository. Also ensure that users have been enlisted as participants to this group. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**BPM-10565: Error in identity service XPath extension function ora:getUserRoles**

**Cause:** Error in executing identity service XPath extension function ora:getUserRoles for user name "{0}" in configuration "{1}".

**Action:** Please make sure that the user name is valid and exists in the repository. Also ensure that roles have been granted to this user. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10566: Error in identity service XPath extension function**

**ora:getDefaultRealmName**

**Cause:** Error in executing identity service XPath extension function ora:getDefaultRealmName.

**Action:** Ensure that a default configuration exists. Irrespective of the number of configurations, one must be defined as default. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10567: Error in identity service XPath extension function**

**ora:getSupportedRealms**

**Cause:** Error in executing identity service XPath extension function ora:getDefaultRealmName.

**Action:** Ensure that the configurations are correct. Please check the exception stack trace for the reasons. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10575: Provider is not defined in configuration.**

**Cause:** Provider "{0}" is not defined in configuration "{1}".

**Action:** Configure provider in configuration file. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10576: Configuration already exists**

**Cause:** Configuration "{0}" already exists.

**Action:** Two or more configurations have the same name. Specify a different name for the configurations. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**BPM-10577: Default configuration is not defined**

**Cause:** Default configuration is not defined in configuration file "{0}".

**Action:** Specify default configuration in the file "{0}". Irrespective of the number of configurations, one should always be marked as default. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10578: More than one default configurations are defined**

**Cause:** More than default configurations are defined in configuration file "{0}".

**Action:** There can be only one default. Specify only one default configuration in configuration file "{0}". Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10579: Name is not defined for one of configurations**

**Cause:** Name is not specified for one of configurations in configuration file "{0}".

**Action:** Specify name for each configuration if few configurations are defined in configuration file "{0}". Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10580: Identity Service Extension name is already defined earlier in the identity service configuration**

**Cause:** Identity Service Extension name "{0}" is already defined earlier in the identity service configuration.

**Action:** Make sure the extension name is unique and defined only once in the identity service configuration file. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10581: Service Provider {0} invocation error**

**Cause:** Service Provider name "{0}" could not invoke method {1}.

**Action:** This errors occurs when service provider {0} is not available or not configured in the identity configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10584: Identity Service wsif error.**

**Cause:** {0} has wsif error in method {1} for soap message: "{2}".



---

**Action:** Ensure that the soap message is properly formed and has all necessary attributes and elements. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10585: Service error.**

**Cause:** Internal Error; Service error occurs in {0} in method {1}.

**Action:** Refer to the log file that is configured for oracle.soa.services.identity for more details on this error and contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10586: Could not get grantees for "{0}" in configuration "{1}".**

**Cause:** Error in getting grantees for "{0}" in configuration "{1}".

**Action:** Ensure that a group with the given name exists and has grantees. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10587: Error in getting owners for "{0}" in configuration "{1}".**

**Cause:** Error occurred in getting owners for "{0}" in configuration "{1}".

**Action:** Ensure that the group name is valid and has associated owners. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10588: Error in getting owned groups for "{0}" in configuration "{1}".**

**Cause:** Error occurred in getting owned groups for "{0}" in configuration "{1}".

**Action:** Ensure that the identity name is valid and owns groups. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10589: Manager "{0}" not found for user "{1}" in configuration "{2}".**

**Cause:** Manager with name "{0}" was not found for user "{1}" in configuration "{2}".

**Action:** Ensure that a user with the given name exists and is a manager for the given user. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-10590: Manager name could not be resolved for "{0}" in configuration "{1}".**

**Cause:** Error in resolving manager name for user "{0}" in configuration "{1}".

**Action:** Ensure that a user with the given name exists and has a manager. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10591: Could not get reportees for "{0}" in configuration "{1}".**

**Cause:** Error in getting reportees for "{0}" in configuration "{1}".

**Action:** Ensure that a user with the given name exists and has reportees. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10592: Identity Service soap error.**

**Cause:** {0} encountered soap error in method {1} for with fault "{2}".

**Action:** Ensure that the soap message is properly formed and has all necessary attributes and elements. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10593: Cannot find application "{0}".**

**Cause:** Cannot find specified application name "{0}" in policy store.

**Action:** Check if the specified application "{0}" exists in policy store. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10597: Attempt to execute privileged action.**

**Cause:** An attempt to execute a privileged action was made.

**Action:** Ensure that the codebase being used has the necessary permissions and privileges. If not, grant the same in the application's policy file. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10598: Identity "{0}" in configuration "{1}" is not of a supported type.**

**Cause:** Unsupported identity type for identity "{0}" in configuration "{1}".

---

**Action:** Ensure that a identity with the given name exists and is of a supported type. Refer to the documentation for all supported identity types. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10599: Role name "{0}" in configuration "{1}" could not be resolved.**

**Cause:** Error in resolving role name "{0}" in configuration "{1}".

**Action:** Ensure that a role with the given name exists. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10600: Reports Error.**

**Cause:** A problem occurred while processing reports data. {0}

**Action:** Please examine the log file to determine the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10601: JMS connection factory lookup failed**

**Cause:** The JMS connection factory lookup failed. The related reporting data will not be published Please ensure the JNDI name {0} is valid.

**Action:** Please verify the JMS configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10602: JMS connection setup failed**

**Cause:** A problem occurred while setting up a connection to the JMS Destination {0} using the connection factory {1}.

**Action:** Please verify the JMS configuration as well as the error to determine the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10603: JMS publish failed**

**Cause:** An error occurred while publishing reporting data to the JMS destination "{0}".

**Action:** Please verify the JMS destination is valid.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-10604: JMS destination lookup failed**

**Cause:** The JMS destination lookup failed. The related reporting data will not be published. Please ensure the JNDI name {0} is valid.

**Action:** Please configure the JMS Destination or correct its JNDI name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10605: Data Publisher failed.**

**Cause:** The Reporting Data Publisher {0} of type {1} failed.

**Action:** Please examine the log file for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10606: Invalid Variable Target.**

**Cause:** The variable target {0} used in sensor {1} is invalid.

**Action:** Please make sure the variable target is correct by validating the variable name as well as the part and xpath query if any was provided.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10607: Sensor Initialization Error.**

**Cause:** An error occurred while initializing the {0} sensor.

**Action:** Please correct the problem and reinitialize the business process.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10608: Sensor Data Capture Error.**

**Cause:** An error occurred while gathering data for the {0} sensor. The related reporting data might not have been published.

**Action:** Please examine the log file and correct the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10609: Invalid Adapter Namespace.**

**Cause:** An error occurred while gathering reporting data for the {0} adapter sensor. The {1} namespace is not a recognized adapter namespace.

**Action:** Please provide a valid header variable that is defined in the appropriate namespace.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10610: Invalid Adapter Header Variable.**

**Cause:** An error occurred while gathering reporting data for the {0} adapter sensor. The header variable {1} could not be found in the BPEL process definition.

**Action:** Please ensure the header variable provided in the sensor definition file exists in the BPEL process.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10611: JMS connection cleanup failed**

**Cause:** A problem occurred while releasing the JNDI resources used to publish to the destination {0}.

**Action:** Please verify the JMS configuration as well as the error to determine the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10612: Data Router failed.**

**Cause:** The Reporting Data Publisher {0} of type {1} failed.

**Action:** Please examine the log file for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10613: Creation of Sensor Registry failed.**

**Cause:** Creation of the Sensor Registry failed.

**Action:** Please examine the log file for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10614: Creation of Reports Schema Publisher failed.**

**Cause:** Creation of the Reports Schema Publisher failed.

**Action:** Please examine the log file for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10615: Load of sensors into Sensor Registry failed.**

**Cause:** The Sensor Registry failed to load sensors for process {0}-{1}.

---

**Action:** Please check the sensor definitions and examine the log file for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10616: Import of sensors failed.**

**Cause:** The Sensor Registry failed to import sensors for process {0}-{1}.

**Action:** Please check the sensor definitions and examine the log file for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10617: Import of sensor actions failed.**

**Cause:** The Sensor Registry failed to import sensor actions for process {0}-{1}.

**Action:** Please check the sensor action definitions and examine the log file for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10618: Import of SLA's failed.**

**Cause:** The Sensor Registry failed to import SLA's for process {0}-{1}.

**Action:** Please check the SLA properties in the deployment descriptor and examine the log file for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10619: Sensor validation failed.**

**Cause:** The Sensor Registry failed to validate the sensor {2} for process {0}-{1}.

**Action:** Please revisit the definition of the sensor and examine the log file for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10620: Sensor Action validation failed.**

**Cause:** The Sensor Registry failed to validate the sensor action {2} for process {0}-{1}.

**Action:** Please revisit the definition of the sensor action and examine the log file for more details.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-10621: Data publisher creation failed.**

**Cause:** The Sensor Agency encountered an error while trying to instantiate {}.

**Action:** Please ensure the specified Data Publisher class and all of its dependencies exist in the system or process classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10622: Sensors not supported.**

**Cause:** Sensors are not supported on this application server platform.

**Action:** If sensor functionality is required, please switch to a supported platform.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10623: Sensors not supported.**

**Cause:** Sensors are not supported on this database platform.

**Action:** If sensor functionality is required, please switch to a supported platform.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10700: Infrastructure services not enabled**

**Cause:** The infrastructure feature for the domain has not been enabled.

**Action:** This is an irrecoverable error with installation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10701: Server connection failure**

**Cause:** Failed to connect to the PCBPEL server.

**Action:** Please check that the PCBPEL server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10702: PCBPEL Server domain authentication enabled.**

**Cause:** PCBPEL Server domain authentication has been enabled, need to turn it off.

**Action:** Please check if PCBPEL server has domain authentication enabled. Please look for property "domain-auth-enabled" in the file collaxa-config.xml and turn it off.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**BPM-10703: BPEL Archive could not be found at the specified location.**

**Cause:** BPEL Archive name or location is incorrect.

**Action:** Please check the name of the BPEL archive and its location.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10704: jndi.properties could not be found in the classpath.**

**Cause:** jndi.properties could not be found in the classpath.

**Action:** Please ensure that jndi.properties is in the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10705: Authentication failure.**

**Cause:** The user name password combination is not authenticated for deployment.{0}

**Action:** Please ensure that the password is correct and user has deployment privileges.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10706: Server Internal Error.**

**Cause:** Server error.{0}

**Action:** Please report this error to the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10707: Connection to server refused**

**Cause:** Server connection refused.

**Action:** Please ensure that the server is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10708: Problem with Network Connection to server**

**Cause:** The network connection to the server is slow. The request has already been sent to the server. Please check the console to see if the process is already deployed.



---

**Action:** The request was sent to the server. The response from server is taking longer than expected. Please check the console to see if the process is already deployed.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-10709: Error while deploying payload jsp**

**Cause:** Deploying payload jsp on platform {0} not supported

**Action:** Please ensure that server platform is supported

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30001: Error in reading routing slip**

**Cause:** Error while reading routing slip {0}. This routing slip is used by workflow {1}

**Action:** Make sure that the routing slip is available at the specified URL.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30002: Error in evaluating routing slip**

**Cause:** Error while evaluating the routing slip {0}. This routing slip is used by workflow {1}

**Action:** Check the underlying exception and correct the error in the routing slip.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30003: Invalid routing slip**

**Cause:** The routing slip at {0} does not conform to the routing slip XML schema definition. The errors are {1}

**Action:** Make sure that the routing slip conforms to the routing slip XML schema definition.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30004: Error in validating routing slip**

**Cause:** The routing slip at {0} could not be validated against the routing slip XML schema definition

**Action:** Make sure that the routing slip is available at the specified URL.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-30005: Error in setting task attributes**

**Cause:** The task attribute {2} could not be set for the task {0}. The task belongs to the workflow {1}

**Action:** This error is likely because of invalid user/group being set as {2}. Make sure that the user/group is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30006: Error in getting manager of user**

**Cause:** The manager of user {2} could not be retrieved for the task {0}. The task belongs to the workflow {1}

**Action:** Make sure that user {2} is valid and that the manager for user {2} is defined in the user directory.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30007: Error in creating task from WSIF Java Web Services message**

**Cause:** The task object could not be created from the message passed to Web Services

**Action:** Check the Web Service input for correctness. The input could also be validated against XML schema definition that describes the operation input.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30008: Error in creating parameters from WSIF Java Web Services message**

**Cause:** The {0} could not be created because expected element {1} is not be found in the element {2} in the parameter passed to Web Services

**Action:** Check the Web Service input for correctness. The input could also be validated against XML schema definition that describes the operation input.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30009: Parameters in Web Services message is invalid**

**Cause:** The parameter {0} is invalid as expected type is {1}, but received value {2} in the parameter passed to WSIF Java Web Services

**Action:** Check the Web Service input for correctness. The input could also be validated against XML schema definition that describes the operation input.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**BPM-30010: Error in creating reply message for Web Services**

**Cause:** Error in creating reply message for Web Services

**Action:** The Web Service input could be invalid causing this exception. Check the Web Service input for correctness. The input could also be validated against XML schema definition that describes the operation input. If being valid, this is a system error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30011: Invalid workflow configuration**

**Cause:** The workflow configuration at {0} could not be read. The workflow configuration is associated with workflow {1}

**Action:** Make sure that the workflow configuration is available at the specified URL and that it is a valid XML document.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30012: Invalid workflow configuration**

**Cause:** The workflow configuration at {0} does not conform to the workflow configuration XML schema definition. The workflow configuration is associated with workflow {1}. The errors are {2}

**Action:** Make sure that the workflow configuration conforms to the workflow configuration XML schema definition.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30013: Error in validating workflow configuration**

**Cause:** The workflow configuration at {0} could not be validated against the workflow configuration XML schema definition. The workflow configuration is associated with workflow {1}

**Action:** Make sure that the workflow configuration is available at the specified URL. If available check the underlying exception and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30014: Error in retrieving previous approvers of task**

**Cause:** The previous approvers of task {0} could not be retrieved. The task is associated with workflow {1}

**Action:** Make sure that the task for which the previous approvers are retrieved is valid. If being valid, this is a system error.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-30015: Error in posting message to BPEL process instance**

**Cause:** Error in posting message to BPEL process instance {1} for callback operation {2}. The task is associated with workflow {0}

**Action:** This could be caused if the BPEL instance is terminated. It is not, this is possibly a system error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30016: Error in invoking routing slip callbacks**

**Cause:** Error in invoking routing slip Java callback {3} for task {1}. The task is associated with workflow {0}

**Action:** Make sure that the routing slip callback class is specified correctly without any errors. The class name should be fully qualified. Also make sure that the class and its dependencies are available in the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30017: Invalid task definition**

**Cause:** The task definition at {0} could not be read. The task definition is associated with workflow {1}

**Action:** Make sure that the task definition is available at the specified URL and that it is a valid XML document.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30018: Invalid task definition**

**Cause:** The task definition at {0} does not conform to the task definition XML schema definition. The task definition is associated with workflow {1}. The errors are {2}

**Action:** Make sure that the task definition conforms to the task definition XML schema definition.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30019: Error in validating task definition**

**Cause:** The task definition at {0} could not be validated against the task definition XML schema definition. The task definition is associated with workflow {1}

**Action:** Make sure that the task definition is available at the specified URL and that it is a valid XML document.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-30020: Invalid workflow task display configuration**

**Cause:** The workflow task display configuration at {0} could not be read. The workflow task display configuration is associated with workflow {1}

**Action:** Make sure that the workflow task display configuration is available at the specified URL and that it is a valid XML document.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30021: Invalid workflow task display configuration**

**Cause:** The workflow task display configuration at {0} does not conform to the workflow task display configuration XML schema definition. The workflow task display configuration is associated with workflow {1}. The errors are {2}

**Action:** Make sure that the workflow task display configuration conforms to the workflow task display configuration XML schema definition.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30022: Error in validating workflow task display configuration**

**Cause:** The workflow task display configuration at {0} could not be validated against the workflow task display configuration XML schema definition. The workflow task display configuration is associated with workflow {1}

**Action:** Make sure that the workflow task display configuration is available at {1} and that it conforms to the workflow task display configuration XML schema definition.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30023: Internal workflow error**

**Cause:** An internal workflow error occurred

**Action:** Refer to the log file that is configured for oracle.soa.services.workflow.\* for more details on this error and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30024: The task is already modified**

**Cause:** The task was modified before the current action could be performed.

**Action:** Refresh the task and perform the action again if the action is still relevant on the refreshed task.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-30025: Error unmarshalling from org.w3c.dom.Element to JAXB.**

**Cause:** Internal Error : Attempt to unmarshall element {0} using JAXB context {1} resulted in error: {2}

**Action:** Refer to the log file that is configured for oracle.soa.services.workflow.\* for more details on this error and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30026: Error creating soap message.**

**Cause:** Error in creating soap message during Web service invocation of operation {1} in {0}

**Action:** Refer to the log file that is configured for oracle.soa.services.workflow.\* for more details on this error and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30028: Invalid configuration file workflow-config.xml**

**Cause:** The configuration file workflow-config.xml not be read.

**Action:** Make sure that the configuration file workflow-config.xml is available and is a valid XML document.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30029: Error in invoking task service**

**Cause:** An client side error occurred in invoking the task service.

**Action:** Verify that the connection information of the server is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30030: Error in invoking task service**

**Cause:** An client side error occurred in invoking the task service operation {0}.

**Action:** Verify that the connection information of the server is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30031: Failed to query flexfield mappings**

**Cause:** Task metadata service was unable to query flexfield mappings for task definition: {0}

---

**Action:** Check the underlying error. Verify that the workflow datasource is correctly configured, and that database server is available.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30032: Invalid task definition lookup**

**Cause:** There is no task definition associated with the task definition ID {0}

**Action:** Verify the that the task definition ID is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30033: Invalid task metadata service invocation**

**Cause:** Task metadata service operation was invoked with empty task definition ID.

**Action:** Make sure that the operation is invoked with a valid task definition ID

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30034: Invalid task display region parameter value**

**Cause:** The task display region parameter value {0} is invalid when applied to task {1}.

**Action:** Make sure that the task display region parameter value is correct if it is an XPath expression

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30035: Push back not supported**

**Cause:** Push back is not supported for the task {0} as there are no more users to push back the task to.

**Action:** This is an invalid operation on the task.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30036: Invalid action on workflow task or user does not have privilege to perform this action**

**Cause:** Action {0} on task {1} cannot be performed by {2}

**Action:** Make sure that the action is valid with respect to the current state of the task or ensure that the user has privilege to perform this action on the workflow task

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**BPM-30037: Error in invoking task metadata service**

**Cause:** An client side error occurred in invoking the task metadata service.

**Action:** Verify that the connection information of the server is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30038: Error in evaluating task service XPath extension function**

**Cause:** Error in evaluating task service XPath extension function {1} against task {1}

**Action:** It is possible that the extension function is not valid against the particular task. Check the error to correct the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30039: Error in routing slip**

**Cause:** The type of the first participant in the routing slip is expected to be Participant, but it is {1}. The routing slip is associated with task {0}

**Action:** Check the routing slip and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30040: Error in routing slip**

**Cause:** Adhoc routing can be performed only when the isAdhocSupported flag is set to true in the routing slip participants or the current participant is adhoc, but it is {1}. The routing slip is associated with task {0}

**Action:** Adhoc routing is an invalid action at the current state of the task.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30043: Error in evaluating workflow service XPath extension function**

**Cause:** Error in evaluating task service XPath extension function {1}

**Action:** Check the error stack and fix the cause of the error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30044: Error in workflow service Web service operation invocation**

**Cause:** Error in workflow service Web service operation invocation. The error is {0}.



---

**Action:** Verify that the SOAP connection information for the server is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30045: Error in invoking workflow state machine decision service.**

**Cause:** Error occurred when invoking workflow routing state machine decisions service {0}. The error is {1}.

**Action:** Check the error underlying error. Verify that the composite and workflow componentType are correctly configured, and that the correct decisionServiceComponentName is specified in the workflow definition.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30046: Error in routing slip**

**Cause:** The expiration specified in the routing slip could not be evaluated. The error is {0}. The routing slip is associated with the task definition {1}

**Action:** Make sure that the expiration duration is specified correctly. The value should conform to XML duration specifications

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30047: Error in routing slip**

**Cause:** Error in evaluating parameter {0} in the routing slip. The error is {1}. The routing slip is associated with the task definition {2}

**Action:** Make sure that the parameter {0} is specified correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30048: Error in routing slip**

**Cause:** An error occurred during evaluating escalation policy in the routing slip. The error is {0}. The routing slip is associated with the task definition {1}

**Action:** Make sure that the escalation policy is specified correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30049: Error in routing slip**

**Cause:** The task is assigned to an invalid user {0} in realm {1}. The routing slip is associated with the task definition {2}

**Action:** Verify that the user is specified correctly in the routing slip in the task definition

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30050: Error in routing slip**

**Cause:** The task is assigned to an invalid group {0} in realm {1}. The routing slip is associated with the task definition {2}

**Action:** Verify that the group is specified correctly in the routing slip in the task definition

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30051: Error in routing slip**

**Cause:** An error occurred during evaluating renewal policy in the routing slip. The error is {0}. The routing slip is associated with the task definition {1}

**Action:** Make sure that the renewal policy is specified correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30052: Error in routing slip**

**Cause:** An error occurred in evaluating the assignees of the task from the routing slip for participant {0}. The error is {1}. The routing slip is associated with the task definition {2}

**Action:** Check the routing slip in the task definition and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30053: System error in evaluating routing slip**

**Cause:** A system error occurred in evaluating the routing slip. The error is {0}. The routing slip is associated with the task definition {1}

**Action:** Refer to the log file that is configured for oracle.soa.services.workflow.task for more details on this error and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30054: Error in evaluating assignment service in routing slip**

**Cause:** Cannot instantiate assignment service {0}. The error is {1}. The assignment service is used in the routing slip that is associated with the task definition {2}

**Action:** Check the routing slip and correct the error. Make sure that the assignment service is available in the classpath of the soa-infra application.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**BPM-30055: Error in evaluating assignment service in routing slip**

**Cause:** Cannot create property bag for assignment service. The error is {0}. The assignment service is used in the routing slip that is associated with the task definition {1}

**Action:** Check the routing slip and correct the error in specifying the properties for the assignment service.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30056: Error in escalating the task on expiration**

**Cause:** The task has expired and the system could not compute the management chain from user {0} upto levels {1} upto title {2} to identify the next user to escalate the task to

**Action:** Make sure that the escalation policy is specified correctly. Also verify that the users are seeded correctly to compute the management chain.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30057: Error in evaluating management chain participant**

**Cause:** Could not compute the management chain from user {0} upto levels {1} upto title {2}. The management chain is used in the routing slip that is associated with the task definition {3}

**Action:** Verify that the users are seeded correctly to compute the management chain.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30058: Error in state machine rules return parameter**

**Cause:** The forwarding rule specifies goto, but does not specify the logical name of the participant to goto. The task is associated with the task definition {0}

**Action:** Check the state machine rule definitions. Ensure that the rules are setting a participant logical name in the GOTO action.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30059: Error in forwarding rules return parameter**

**Cause:** The forwarding rule specifies goto, but the logical name of the participant {0} to goto is not a valid name. The task is associated with the task definition {0}

**Action:** Check the state machine rule definitions. Ensure that the rules are setting a valid logical participant name in the GOTO action.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30060: Error in task assignment rules evaluation**

**Cause:** Error in task assignment rules evaluation for user {0}. The error is {1}

**Action:** Make sure that the rules specified for user {0} are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30061: Cyclic assignment during task assignment rules evaluation**

**Cause:** During task assignment rules evaluation, there is a cyclic assignment involving user {0}.

**Action:** Correct the assignment rules to avoid this error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30062: Error in task assignment rules evaluation**

**Cause:** Error in task assignment rules evaluation for group {0}. The error is {1}

**Action:** Make sure that the rules specified for group {0} are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30063: Cyclic assignment during task assignment rules evaluation**

**Cause:** During task assignment rules evaluation, there is a cyclic assignment involving group {0}.

**Action:** Correct the assignment rules to avoid this error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30064: Error in routing slip**

**Cause:** The task is assigned to an invalid application role {0} in application context {1}. The routing slip is associated with the task definition {2}

**Action:** Verify that the application role is specified correctly in the routing slip in the task definition

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30065: Error in task definition**

---

**Cause:** Error in evaluating parameter {0} in the task definition. The error is {1}.  
The task definition {2}

**Action:** Make sure that the parameter {0} is specified correctly in the task definition.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30066: Invalid arguments to requestInfoForTask operation**

**Cause:** Invalid arguments to requestInfoForTask operation. The reapproval assignees parameter must contain one or more valid user, group or role.

**Action:** Correct the error in the client usage.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30067: Invalid access to task**

**Cause:** The user does not have access to the task.

**Action:** Check that the task is being accessed in an authenticated context and that you are involved in this task in some manner.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30068: Invalid task definition ID or namespace**

**Cause:** There is no task definition with the provided ID {0}. This ID is either the ID of the task definition or the namespace of the task definition

**Action:** Verify the that the task definition ID is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30069: Task definition not found using namespace**

**Cause:** There is no active SCA composite with the referenced task definition. The provided task definition namespace is {0}

**Action:** Verify the that the composite containing the task definition is active.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30070: Assignee Time Distribution Statistic Service Internal error.**

**Cause:** An internal error occurred in the Assignee Time Distribution Statistic Service. Task assignment statistic is not recorded for {0} for the operation {1}. This may lead to loss of some Task assignment statistic data

**Action:** Check the underlying exception and correct the error. Contact Oracle Support Services if the error persists.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30071: No workflow admin user seeded**

**Cause:** There must be atleast one workflow admin user seeded in the system.

**Action:** Seed an workflow admin user or grant the workflow admin role to an existing user.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30072: Task owner user not seeded**

**Cause:** Task owner {0} is not found in realm {1}. This task is associated with task definition {2}

**Action:** Either set a seeded owner or seed this owner who is not found.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30073: Task owner group not seeded**

**Cause:** Task owner {0} is not found in realm {1}. This task is associated with task definition {2}

**Action:** Either set a seeded owner or seed this owner who is not found.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30074: There is no user to escalate the task to**

**Cause:** There is no user to escalate the task to. The task is assigned to user {0}. This task is associated with task definition {1}

**Action:** Ensure that this user has a manager to escalate the task to.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30075: Invalid task attachment name**

**Cause:** The task attachment {0} does not exist

**Action:** Ensure that the task attachment name is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30076: ToDo task cannot be created as a sub task for a task that is not in the assigned state**

---

**Cause:** Parent task {0} is not assigned. ToDo task cannot be created as a sub task for a task that is not in the assigned state.

**Action:** Ensure that the ToDo task is created for an assigned task.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30077: Error in invoking Notification callbacks**

**Cause:** Error in invoking routing slip Java callback {3} for task {1}. The task is associated with workflow {0}

**Action:** Make sure that the Notification callback class is specified correctly without any errors. The class name should be fully qualified. Also make sure that the class and its dependencies are available in the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30078: Error in evaluating the restricted assignment service in routing slip**

**Cause:** Cannot instantiate restricted assignment service {0}. The error is {1}. The restricted assignment service is used in the routing slip that is associated with the task definition {2}

**Action:** Check the routing slip and correct the error. Make sure that the restricted assignment service is available in the classpath of the soa-infra application.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30079: Attempt to reassign/route to an invalid assignee.**

**Cause:** The assignee {0} in realm {1} for task definition {2} is not permitted as per the restricted assignment callback configured by the administrator.

**Action:** Check the routing slip and correct the error. Make sure that restricted assignees are not used in the task definition.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30080: Task owner role not seeded**

**Cause:** Task owner {0} is not found in application {1} and realm {2}. This task is associated with task definition {3}

**Action:** Either set a seeded owner or seed this owner who is not found.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30081: Workflow Service Engine callback to SOA mesh failed.**

**Cause:** Callback operation {0} from {1} to {2} failed with error: {3}

---

**Action:** Check the underlying exception. Ensure that the SOA composite is configured correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30082: WorkflowServiceEngine request to another component failed.**

**Cause:** Request operation {0} from {1} to {2} failed with Business Fault: {3}

**Action:** Check the underlying fault. Check target SOA component for cause.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30083: WorkflowServiceEngine request to SOA mesh failed.**

**Cause:** Request operation {0} from {1} to {2} failed with error: {3}

**Action:** Check the underlying exception. Ensure that the SOA composite is configured correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30085: Missing task metadata identifiers in task object.**

**Cause:** Task metadata corresponding to a task is identified by either the taskDefinitionId or taskDefinitionURI (deprecated in 11). At least one of those task elements should be set.

**Action:** Set either the taskDefinitionId or taskDefinitionURI in the task instance.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30086: No duration specified.**

**Cause:** Invalid task duration: {0}.

**Action:** Specify a valid duration.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30087: Operation not supported in disconnected mode.**

**Cause:** The attempted operation cannot be performed whilst disconnected from the server.

**Action:** Connect to the server before attempting the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic



---

**BPM-30088: No task definitions found matching specified namespace and version.**

**Cause:** No task definitions found with task definition namespace {0} and composite version {1}.

**Action:** Check that the specified task definition namespace and composite version are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30089: No active composite found corresponding to specified namespace.**

**Cause:** No active composite found containing a task component with definition namespace of {0}.

**Action:** Specify a composite version to query by, or make a composite version active.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30090: Can not compute management chain list.**

**Cause:** The management chain can not be completely computed because the starting point in the management chain is not a single user. Management chain can not be computed from group(s), application role(s) and/or list of users. This exception is related to task definition {0}.

**Action:** Correct the errors in workflow process modeling or the rule that returned the management chain list parameters.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30091: Can not restart the task**

**Cause:** Can not restart the task {0} in {1} state either because it is not a root task or the state is invalid for restart

**Action:** Check the error stack and fix the cause of the error. Contact Oracle Support Services if error the error persists.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30092: Error in invoking attachment callback**

**Cause:** Error in invoking attachment callback {2} for task {1}. The task is associated with workflow {0}

**Action:** Make sure that the attachment callback class is specified correctly without any errors. The class name should be fully qualified. Also make sure that the class and its dependencies are available in the classpath.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-30093: Error in invoking comment callback**

**Cause:** Error in invoking comment callback {2} for task {1}. The task is associated with workflow {0}

**Action:** Make sure that the comment callback class is specified correctly without any errors. The class name should be fully qualified. Also make sure that the class and its dependencies are available in the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30094: Bulk update is not allowed for this Task.**

**Cause:** This task expects the user to view task details before acting on it.

**Action:** Make sure that the task is approved/rejected from task details page. Also ensure that TaskService API which takes task Object as input is used instead of the API which takes taskID as input.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30095: User comments are expected for this Task.**

**Cause:** This task expects the user to provide comments while acting on it.

**Action:** Make sure that the comments are provided while acting on this task.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30096: Can not reevaluate the task.**

**Cause:** This task {0} does not belongs to a sequential or parallel participant.

**Action:** Check the error stack and fix the cause of the error. Contact Oracle Support Services if the error persists.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30097: Routing slip can not be reevaluated.**

**Cause:** Current routing slip participant for the task {0} is not generated by a list builder.

**Action:** This task can not be reevaluated. Make sure the participant is generated using List builder.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30098: Error in task action validation**

---

**Cause:** Error in validation task action {2} for task {1}.The task definition is associated with workflow {0}. The error(s) is/are: {3}

**Action:** Make sure the validation errors are corrected before invoking the task action.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30099: Error in invoking task validation callbacks**

**Cause:** Error in invoking task validation Java callback {2} for task {1}. The task is associated with workflow {0}

**Action:** Make sure that the task validation callback class is specified correctly without any errors. The class name should be fully qualified. Also make sure that the class and its dependencies are available in the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30100: Error in setting Task Sequence Changes**

**Cause:** Task has been modified. Mismatch on saving ad hoc changes for task with correlation Id {0}

**Action:** Refresh list to get current list of assignees and redo the changes.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30101: Invalid attribute label for flexfield mapping defined in task definition.**

**Cause:** No attribute label named {0} for flexfield attribute {1} exists.

**Action:** Create an appropriate attribute label, or specify a different label in the task definition.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30102: Error in routing slip**

**Cause:** The task is assigned to an invalid position {0} in application context {1}. The routing slip is associated with the task definition {2}

**Action:** Verify that the position is specified correctly in the routing slip in the task definition

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30103: Ruleset didn't return any results.**

**Cause:** Ruleset {0} didn't return any results.

**Action:** Model the ruleset so that it returns a list builder specification.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30104: Ruleset returned different types of list builders.**

**Cause:** Ruleset {0} returned different types of list builders.

**Action:** Ruleset results should all be of the same list builder type. Correct the ruleset.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30105: Ruleset returned unexpected list builder type.**

**Cause:** Ruleset {0} returned list builder of type {2} when list builder of type {1} was expected.

**Action:** Correct the ruleset.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30106: Error setting starting point implicitly.**

**Cause:** Starting Point not specified and Task Creator is same as UptoApprover: {0}

**Action:** Set the starting point explicitly to some one below the Upto Approver.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30107: Error fetching manager list using Hierarchy Provider.**

**Cause:** Failed to walk up the hierarchy for principal: {0}

**Action:** Check Starting Point/Task Creator and Upto Approver values and Hierarchy Provider setup.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30108: Error NULL Hierarchy Principal provided.**

**Cause:** Failed to fetch jobLevel for principal: NULL

**Action:** Check Hierarchy Provider setup.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30109: Error fetching jobLevel using Hierarchy Provider.**

**Cause:** Failed to fetch jobLevel for principal: {0}

**Action:** Check Hierarchy Provider setup.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30110: Error walking up Hierarchy.**

**Cause:** Failed to fetch upto approver for principal: {0}

**Action:** Check UptoApprover value in List Builder Specifications.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30111: Invalid user.**

**Cause:** The task is assigned to an invalid user {0} in realm {1}.

**Action:** Assign to a valid user.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30112: Invalid group.**

**Cause:** The task is assigned to an invalid group {0} in realm {1}

**Action:** Assign to a valid group.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30113: Invalid application role.**

**Cause:** The task is assigned to an invalid application role {0} in application context {1}.

**Action:** Assign to a valid application role.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30114: Invalid position.**

**Cause:** The task is assigned to an invalid application role {0} in application context {1}.

**Action:** Assign to a valid position.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30115: Error in invoking document callback**

**Cause:** Error in invoking document callback {2} for task {1}. The task is associated with workflow {0}

---

**Action:** Make sure that the document callback class is specified correctly without any errors. The class name should be fully qualified. Also make sure that the class and its dependencies are available in the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30116: Invalid value of Levels.**

**Cause:** The levels constraint for the Supervisory List Builder is not a postive integer: {0}

**Action:** Assign to a positive number for the levels parameter in the Supervisory List Builder Specification.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30117: Invalid value of Levels.**

**Cause:** Both AtLeast and AtMost constraints for Job Level List Builder are not postive integers:, At Least {0}, At Most: {1}

**Action:** Assign positive integer values to one or both as required.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30118: Invalid value of Levels.**

**Cause:** Both AtLeast and AtMost constraints for Position List Builder are not postive integers:, At Least {0}, At Most: {1}

**Action:** Assign positive integer values to one or both as required.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30119: Partial task update is not allowed**

**Cause:** The task being updated is a partial task that was retrieved using query APIs. Such partial tasks cannot be directly used for update.

**Action:** Obtain the complete tasks using `getTaskDetailsById` before updating it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30120: Invalid task document name**

**Cause:** The task document {0} does not exist

**Action:** Ensure that the task document name is valid.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-30121: Error in invoking document callback**

**Cause:** Error in invoking document callback {2} for task {1}. The task is associated with workflow {0}

**Action:** Make sure that the document callback class is specified correctly without any errors. The class name should be fully qualified. Also make sure that the class and its dependencies are available in the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30122: Error while querying task document**

**Cause:** Error while querying task document {0} for task {1} with version{2}

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30123: Error while deploying task metadata.**

**Cause:** The task namespace {0} is already used as a template namespace.

**Action:** Check if the project you are deploying now is a template project. Please avoid deploying template projects. Please use a different namespace for the task definition to fix the problem or set the suffixNamespace flag to true.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30124: Error while deploying task metadata.**

**Cause:** the template namespace {0} is already in use as a task namespace

**Action:** Check if a template project with namespace {0} was deployed earlier. Please avoid deploying template projects. Please use a different namespace for the current task definition to fix the problem. The task flow associated with the template project will not work with this project anymore if the namespace is changed.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30125: Attachment already exists.**

**Cause:** Process attachment names are unique. Please delete the existing attachment with the same name and then try to add it.

**Action:** To add the attachment with the same name, delete the existing attachment and upload again

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-30126: Position provider invalid or cont available.**

**Cause:** Position provider could not be loaded, position list builder could not be used.

**Action:** Unable to load the position provider, please check the position provider configuration and make sure it is valid. Position list builder uses provider to get the hierarchy.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30251: Error while querying workflow task display**

**Cause:** Error while querying workflow task display based on task metadata and application name

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30252: Error while inserting workflow task display**

**Cause:** Error while inserting workflow task display

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30253: Error while updating workflow task display**

**Cause:** Error while updating workflow task display.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30254: Error while deleting workflow task display**

**Cause:** Error while deleting workflow task display.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30257: Error while Querying workflow task metadata**



---

**Cause:** Error while Querying workflow task metadata

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30258: Error while inserting workflow task metadata**

**Cause:** Error while inserting workflow task metadata

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30259: Error while updating workflow task metadata**

**Cause:** Error while updating workflow task metadata {0}

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30260: Error while deleting workflow task metadata**

**Cause:** Error while deleting workflow task metadata {0}

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30261: The task namespace {0} is already in use by the task component {1}.**

**Cause:** Task component target namespaces must be unique.

**Action:** Specify a different target namespace for this task component.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30265: Error while querying users which are on vacation**

**Cause:** Error while querying users which are on vacation

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-30266: Error while querying user vacation information**

**Cause:** Error while querying user {0} vacation information

**Action:** Check the underlying exception and the database connection information.  
If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30267: Error while inserting user vacation information**

**Cause:** Error while inserting user {0} vacation information

**Action:** Check the underlying exception and the database connection information.  
If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30268: Error while updating user vacation information**

**Cause:** Error while updating user {0} vacation information

**Action:** Check the underlying exception and the database connection information.  
If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30269: Error while deleting user vacation information**

**Cause:** Error while deleting user {0} vacation information

**Action:** Check the underlying exception and the database connection information.  
If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30274: Error while querying workflow message attributes**

**Cause:** Error while querying workflow message attributes for task {0} with  
version {1}

**Action:** Check the underlying exception and the database connection information.  
If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30275: Error while querying workflow task history**

**Cause:** Error while querying workflow task history for task {0} with version{1}

---

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30276: Error while querying workflow task history**

**Cause:** Error while querying workflow task history for task {0} with version{1}

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30277: Error while querying task attachment**

**Cause:** Error while querying task attachment {0} for task {1} with version{2}

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30278: Error while inserting task**

**Cause:** Error while inserting task {0}

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30279: Error while locking the task during update**

**Cause:** Error while locking the task {0} during update

**Action:** The task is being updated by another user, merge and update the task later

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30280: Error while inserting task payload**

**Cause:** Error while inserting task payload {0} for task {1}

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-30281: Error while updating task payload**

**Cause:** Error while updating task payload {0} for task {1}

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30282: Error while deleting data**

**Cause:** Error while deleting data from table {0}

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30283: Error while querying task user comments**

**Cause:** Error while querying task user comments for task {0} with version{1}

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30284: Error while querying task composite created time**

**Cause:** Error while querying task composite created time for task {0}

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30291: Error while inserting task routing slip**

**Cause:** Error while inserting task {1} routing slip

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30292: Error while locking the routing slip during update**

**Cause:** Error while locking the routing slip during update of routing slip for task {0}

---

**Action:** The task is being updated by another user, merge and update the task later

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30293: Attempt to update already deleted routing slip**

**Cause:** Attempt to update already deleted routing slip for task {0}

**Action:** Refresh the task list by a new query.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30294: Error while updating routing slip**

**Cause:** Error while updating routing slip for task {0}

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30295: Error while querying routing slip**

**Cause:** Error while querying routing slip for task {0}

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30296: Error while deleting routing slip**

**Cause:** Error while deleting routing slip for task {0}

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30297: Error while initializing persistency service**

**Cause:** Error while initializing persistency service

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**BPM-30298: Error during persistency service commit**

**Cause:** Error during persistency service commit

**Action:** Check the underlying exception and the database connection information.  
If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30299: Error during persistency service rollback**

**Cause:** Error during persistency service rollback

**Action:** Check the underlying exception and the database connection information.  
If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30300: Error while closing persistency service**

**Cause:** Error while closing persistency service

**Action:** Check the underlying exception and the database connection information.  
If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30301: Error while creating prepared statement in persistency service**

**Cause:** Error while creating prepared statement for {0} in persistency service

**Action:** Check the underlying exception and the database connection information.  
If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30302: Invalid join operator**

**Cause:** Invalid join operator {0}

**Action:** Change the operator in the given predicate.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30303: Predicate join columns are null**

**Cause:** Predicate join columns are null

**Action:** Specify valid, non null, join columns for the given predicate.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-30304: Error while joining columns of different types in predicate**

**Cause:** Error while joining columns of different types in predicate

**Action:** Joined columns are of different type, verify the types of columns in the predicate.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30305: Invalid value type in predicate**

**Cause:** Invalid value type {0} in predicate

**Action:** Unrecognized value type specified in the predicate, pass the appropriate value type for the column.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30306: Transaction is open**

**Cause:** Transaction is open

**Action:** Close the current transaction and then open a new one.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30307: Transaction is open**

**Cause:** Transaction is open

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30308: Transaction is close**

**Cause:** Transaction is close

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30312: Error while creating attribute label map**

**Cause:** Error while creating attribute label map

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30313: Error while updating attribute label map**

**Cause:** Error while updating attribute label map for {0}

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30314: Error while deleting attribute label map**

**Cause:** Error while deleting attribute label map for {0}

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30315: Error while querying attribute label map**

**Cause:** Error while querying attribute label map

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30316: Error while creating attribute usages**

**Cause:** Error while creating attribute label usages for AttributeLabel type {0}

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30317: Error while deleting attribute usages**

**Cause:** Error while deleting attribute label usages for AttributeLabel type {0}

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30318: Error while querying attribute usages**



---

**Cause:** Error while querying attribute label usages

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30319: Error while inserting workflow task timer**

**Cause:** Error while inserting workflow task timer {0}

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30320: Error while querying workflow task timer**

**Cause:** Error while querying workflow task timer based on task metadata and application name

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30321: Error while deleting workflow task timer**

**Cause:** Error while deleting workflow task timer {0}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30322: Error while querying workflow task**

**Cause:** Error while querying workflow task {0}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30323: Error while inserting workflow task**

**Cause:** Error while inserting workflow task {0}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**BPM-30324: Error while updating workflow task**

**Cause:** Error while deleting workflow task {0}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30325: Error while deleting workflow task**

**Cause:** Error while updating workflow task timer {0}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30326: Current user does not have the WRITE privilege on task attribute: {1}**

**Cause:** Current user {0} does not have WRITE privilege for {1} on task with taskId {2}

**Action:** Grant the WRITE access for the current user/role. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30327: Current user does not have the ADD privilege on task attribute: {1}**

**Cause:** Current user {0} does not have ADD privilege for {1} on task with taskId {2}

**Action:** Grant the ADD access for the current user/role. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30328: Current user does not have the READ privilege on task attribute: {1}**

**Cause:** Current user {0} does not have READ privilege for {1} on task with taskId {2}

**Action:** Grant the READ access for the current user/role. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**BPM-30329: Error while querying workflow task assignment statistic**

**Cause:** Error while querying workflow task assignment statistic {0}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30330: Error while inserting workflow task assignment statistic**

**Cause:** Error while inserting workflow task assignment statistic {0}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30331: Error while updating workflow task assignment statistic**

**Cause:** Error while deleting workflow task assignment statistic {0}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30332: Error while deleting workflow task**

**Cause:** Error while updating workflow task timer {0}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30333: Error while Inserting Evidence**

**Cause:** Insertion of task evidence : {0}, resulted in error : {1}

**Action:** Check Application server data source properties for BPEL-Workflow connections. Check schema and verify database connections. Ensure that a valid Evidence is being inserted by the worklist application.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30334: Error while Updating Evidence**

**Cause:** Updation of task evidence : {0}, resulted in error : {1}

**Action:** Check Application server data source properties for BPEL-Workflow connections. Check schema and verify database connections

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30335: Error while Fetching Evidence**

**Cause:** Querying for task evidence matching {0} condition, resulted in error : {1}

**Action:** Check Application server data source properties for BPEL-Workflow connections. Check schema and verify database connections

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30336: Error while Inserting Evidence Service data**

**Cause:** Inserting into {0} table, resulted in error : {1}

**Action:** Check Application server data source properties for BPEL-Workflow connections. Check schema and verify database connections

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30337: Error while Updating Evidence Service data**

**Cause:** Updating record(s) of {0} table, resulted in error : {1}

**Action:** Check Application server data source properties for BPEL-Workflow connections. Check schema and verify database connections

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30338: Error while Deleting Evidence Service data**

**Cause:** Deleting record(s) from {0} table, resulted in error : {1}

**Action:** Check Application server data source properties for BPEL-Workflow connections. Check schema and verify database connections

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30339: Error while Fetching Evidence Service data**

**Cause:** Fetching records from {0} table, resulted in error : {1}

**Action:** Check Application server data source properties for BPEL-Workflow connections. Check schema and verify database connections

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30340: Error while Inserting header properties data**

---

**Cause:** Inserting into {0} table, resulted in error : {1}

**Action:** Check the underlying exception and the database connection information.  
If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30341: Error while Deleting header properties data**

**Cause:** Deleting from {0} table, resulted in error : {1}

**Action:** Check the underlying exception and the database connection information.  
If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30342: Error while Fetching header properties data**

**Cause:** Fetching records from {0} table, resulted in error : {1}

**Action:** Check the underlying exception and the database connection information.  
If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30343: Error while Inserting rule dictionary data.**

**Cause:** Inserting into {0} table, with dictionary {1}, package {2} resulted in error: {3}

**Action:** Check the underlying exception and the database connection information.  
If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30344: Error while Deleting rule dictionary data.**

**Cause:** Deleting from {0} table, with dictionary {1}, package {2} resulted in error: {3}

**Action:** Check the underlying exception and the database connection information.  
If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30345: Error while Updating rule dictionary data.**

**Cause:** Updating {0} table, with dictionary {1}, package {2} resulted in error: {3}

**Action:** Check the underlying exception and the database connection information.  
If the error persists, contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30346: Error while Fetching rule dictionary data.**

**Cause:** Fetching records from {0} table, with dictionary {1}, package {2} resulted in error: {3}

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30347: Cannot write dictionary with outstanding updates.**

**Cause:** Dictionary {0}, package {1} has outstanding updates that must be committed.

**Action:** Commit all dictionary edits by calling update method on RuleDictionary before writing to database.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30348: Cannot update a read-only dictionary.**

**Cause:** Dictionary {0}, package {1} is marked as 'read only' and cannot be updated in the database.

**Action:** Dictionaries can be marked as read-only or otherwise using the WFRuleDictionaryFinder class.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30349: Rule Dictionary name conflict.**

**Cause:** A dictionary with the name {0} and package {1} already exists in the database.

**Action:** Specify a different name and/or package for the dictionary.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30350: Error while inserting approval group.**

**Cause:** Inserting approval group {0} resulted in error: {1}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-30351: Error while updating approval group.**

**Cause:** Updating approval group {0} resulted in error: {1}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30352: Error while deleting approval group.**

**Cause:** Deleting approval group {0} resulted in error: {1}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30353: Error while getting approval group.**

**Cause:** Getting approval group {0} resulted in error: {1}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30354: Error while getting approval groups.**

**Cause:** Getting approval groups with search string {0} and search type {1} resulted in error: {2}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30360: Error while inserting approval record.**

**Cause:** Inserting approval record with task Id {0} and record ID {1} resulted in error: {2}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30361: Error while updating approval record.**

---

**Cause:** Updating approval record with task Id {0}, subtask ID {1}, history version {2}, dimension instance ID {3}, and stage instance ID {4} resulted in error: {5}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30362: Error while deleting approval record.**

**Cause:** Deleting approval record with task Id {0} resulted in error: {1}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30363: Error while getting approval record.**

**Cause:** Getting approval record with task Id {0} and version {1} resulted in error: {2}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30370: Error while inserting approval instance.**

**Cause:** Inserting approval instance {0} resulted in error: {1}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30371: Error while updating approval instance.**

**Cause:** Updating approval instance {0} with task Id {1}, instance type {2}, and entity name {3} resulted in error: {4}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30372: Error while deleting approval instance.**

**Cause:** Deleting approval instance with task Id equals {0} resulted in error: {1}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.



---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30373: Error while getting approval instance.**

**Cause:** Getting approval instance with approval instance Id {0} resulted in error: {1}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30374: Error while getting approval instances.**

**Cause:** Getting approval instance with approval task Id {0} resulted in error: {1}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30380: Error while inserting approval record reason.**

**Cause:** Inserting approval record reason with reason Id {0}, reason code {1}, and reason type {2} resulted in error: {3}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30381: Error while updating approval record reason.**

**Cause:** Updating approval record reason with reason Id {0}, reason code {1}, and reason type {2} resulted in error: {3}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30382: Error while deleting approval record reason.**

**Cause:** Deleting approval record reason with reason Id {0} and sequence {1} resulted in error: {2}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-30383: Error while getting approval record reason.**

**Cause:** Getting approval record reason with reason Id {0} and sequence {1} resulted in error: {2}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30385: Error while inserting task sequence change.**

**Cause:** Inserting task sequence change with correlation Id {0}, anchor chain {1}, change type {2} resulted in error: {3}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30386: Error while updating task sequence change.**

**Cause:** Updating task sequence change with correlation Id {0} resulted in error: {1}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30387: Error while deleting task sequence change.**

**Cause:** Deleting task sequence change with correlation Id {0} resulted in error: {1}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30388: Error while getting task sequence change.**

**Cause:** Getting task sequence change with correlation Id {0} resulted in error: {1}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30390: Error during update.**

---

**Cause:** No matching row found while updating {0} with parameter {1}.

**Action:** Verify that the row is available during update.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30391: Error while querying task payload collection targets**

**Cause:** Error while querying task payload collection targets for task {1} with version {2}

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30392: Error while performing {0} operation related to task aggregation**

**Cause:** Error while performing {0} operation related to task aggregation

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30400: Error occurred while inserting a task attachment record.**

**Cause:** Error occurred whilst inserting attachment {0} for task {1}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30401: Error occurred while versioning a task attachment record.**

**Cause:** Error occurred whilst versioning attachment {0} for task {1}, version {2}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30402: Error occurred while generating a new Task Number.**

**Cause:** Generation of a new Task Number failed with the error: {0}

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**BPM-30403: Error occurred while creating a new task history entry.**

**Cause:** Creation of task history entry for task id {0} failed with the error: {1}

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30404: Error occurred while writing task translation data.**

**Cause:** Write of task translation data for task id {0} failed with the error: {1}

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30405: Failed to query task number for task.**

**Cause:** Attempt to query task number for task id {0} failed.

**Action:** Check the task id is correct, and that the task has not been deleted. Check any underlying exception, and the database connection.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30406: Unsupported database type for human workflow persistency.**

**Cause:** The database type {0} is not supported by human workflow services persistency.

**Action:** Check your installation settings, and ensure that RCU install completed correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30407: Error querying the process instances based on the logged in user.**

**Cause:** Error in querying process instances based on the logged in user {0}

**Action:** Check your installation settings, and ensure that RCU install completed correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30408: Error in querying instance stake holder for logged in user.**

**Cause:** Error in querying instance stake holder for logged in user {0}.

---

**Action:** Check your installation settings, and ensure that RCU install completed correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30409: Error in deleting process instance attachment**

**Cause:** Error in deleting process instance {0} attachment {1}.

**Action:** Check your installation settings, and ensure that RCU install completed correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30410: Error while deleting workflow task metadata**

**Cause:** Error while deleting workflow task metadata {0}

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30411: Error occurred while inserting a pre-initiated task attachment record.**

**Cause:** Error occurred while inserting attachment {0} for task correlationId {1}.

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30412: Error occurred updating attachment record to add pre-initiated task attachment to the task**

**Cause:** Error occurred while updating attachment records for correlationId {0} to add it to task {1}

**Action:** Check the underlying exception and the database connection information. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30450: JAXB-Toplink conversion failed.**

**Cause:** Conversion of {0} to {1} failed with error {2}

**Action:** Check the underlying exception.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-30451: Persistency not supported for this object type.**

**Cause:** The class {0} does not support persistency of objects of type {1}.

**Action:** Check the type of object and the class being used to persist it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30501: Error in authenticating user**

**Cause:** Error in authenticating and creating a workflow context for user {0}

**Action:** Verify that the user credentials and identity service configurations are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30502: Error in Verification Service when creating Context**

**Cause:** Error in Verification Service when creating Context. {0}

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30503: Invalid Token Error in Verification Service**

**Cause:** Invalid Token Error in Verification Service. Received invalid token in {0}

**Action:** Verify that correct token is passed.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30504: Internal Error in Verification Service**

**Cause:** Internal Error in Verification Service for user {0}. {1}

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30506: Runtime error in Task Query Service**

**Cause:** Runtime error in Task Query Service. {0}

**Action:** Verify that the parameters passed are correct.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-30507: Runtime error in Task Report Service**

**Cause:** Runtime error in Task Report Service. {0}

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30508: Error while invoking URL to display the content**

**Cause:** Error while invoking URL. {0}

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30509: Insufficient privileges to authenticate on-behalf of another user.**

**Cause:** User {0} cannot authenticate on-behalf of user {1} without admin privileges.

**Action:** Only users with admin privileges can authenticate on-behalf of another user.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30513: Insufficient privileges to access the task info for this task**

**Cause:** User {0} cannot access the task info for task: {1}

**Action:** Ensure that the user has been granted appropriate privileges to access the task info for this task.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30514: Session timed out**

**Cause:** Session has timed out, because it was inactive for {0} minutes and {1} seconds.

**Action:** Relogin in to the application.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30515: Access to internal workflow context is denied**

**Cause:** Requested access to internal workflow context is not allowed according to security policy

---

**Action:** Ensure that correct security policy is used. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30516: Token decryption failed**

**Cause:** Could not extract information from Workflow context token

**Action:** Ensure that the Workflow context is not corrupted and it was generated from one of the nodes in the same cluster.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30701: Insufficient privileges to access metadata for another user.**

**Cause:** User {0} attempted to access metadata for user {1} without having appropriate administrator privileges.

**Action:** Ensure that the appropriate privileges have been granted before attempting to access metadata belonging to another user.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30704: Failed to instantiate workflow rule repository service**

**Cause:** Could not create repository service for workflow rule dictionary {1}, package {2}

**Action:** Check underlying exception. Ensure dictionary name and package are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30705: Failed to get workflow rules**

**Cause:** Could not get workflow rules for {0}

**Action:** Check underlying exception. Ensure user or group name is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30706: Rule tests for task payload cannot be defined in this release**

**Cause:** Definition of rules with tests that check the task payload is not supported in this release.

**Action:** Remove any payload tests from the rule definition.

**Level:** 1

**Type:** ERROR



---

**Impact:** Programmatic

**BPM-30707: Invalid workflow rule action.**

**Cause:** Action type {0} is not a valid rule action type.

**Action:** Specify a valid rule action type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30708: Failed to update rule dictionary.**

**Cause:** Update of dictionary {0} failed with error: {1}

**Action:** Check underlying exception. Ensure that workflow rules dictionary name is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30709: Failed to load ruleset.**

**Cause:** Failed to load ruleset from dictionary {0} for rule with ID {1}.

**Action:** Check underlying exception. Ensure dictionary name and rule ID are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30710: Failed to create ruleset.**

**Cause:** Failed to create ruleset in dictionary {0}.

**Action:** Check underlying exception. Ensure dictionary name is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30711: Invalid authentication context.**

**Cause:** Invalid authentication context has been passed to user metadata service.

**Action:** Ensure valid authentication context is passed.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30712: Failed to execute workflow ruleset.**

**Cause:** Rules engine reported error when executing workflow ruleset in dictionary {0}.

**Action:** Check underlying exception. Ensure rules are correctly defined in ruleset.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-30713: Failed to parse workflow ruleset.**

**Cause:** Rules repository reported error when generating RuleLanguage for workflow ruleset in dictionary {0}.

**Action:** Check underlying exception. Ensure rules are correctly defined in ruleset.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30714: Missing date in date range.**

**Cause:** Both start date and end date must be specified.

**Action:** Specify both a start date and an end date.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30715: End date is before start date.**

**Cause:** End date cannot occur before the start date.

**Action:** Specify an end date that occurs after the start date.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30716: Invalid workflow rule test attribute**

**Cause:** Workflow rule test {0} uses an invalid task attribute: {1}.

**Action:** Specify valid task attributes when defining workflow rules.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30717: Invalid operator in workflow rule test expression.**

**Cause:** The workflow rule test {0} uses the invalid operator {1}.

**Action:** Ensure that a valid operator is specified and that it is appropriate for the datatype of the attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30718: Cannot specify null value in workflow rule test expression.**

**Cause:** The workflow rule test {0} compares the task attribute to null.

**Action:** A valid value must be specified for the test expression.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-30719: Cannot define a rule test for a Duration attribute.**

**Cause:** The workflow rule test {0} is for an attribute of type Duration.

**Action:** Rule tests for Duration attribute types are not supported. Select another attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30720: Error in invoking user metadata service.**

**Cause:** A client side error occurred in invoking the user metadata service.

**Action:** Verify that the connection information for the server is correct, and that the server hosting the user metadata service is available.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30721: Error in invoking user metadata service operation.**

**Cause:** An client side error occurred in invoking the user metadata service operation {0}.

**Action:** Verify that the connection information for the server is correct, and that the server hosting the user metadata service is available.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30722: Fault reported by user metadata Web service.**

**Cause:** The user metadata service returned a fault for the following error: {0}

**Action:** Refer to the error reported by the fault.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30723: User does not exist.**

**Cause:** There is no such user as {0}.

**Action:** Enter a valid user name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30724: Group does not exist.**

**Cause:** There is no such group as {0}.

**Action:** Enter a valid group name.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**BPM-30725: Cannot reassign to user or group.**

**Cause:** {0} does not have the necessary permissions to assign tasks to {1}

**Action:** Select a different user or group.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30726: Rule name is not unique.**

**Cause:** A rule named {0} already exists for {1}.

**Action:** Specify a different name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30727: Cannot update GrantedTaskView grant type.**

**Cause:** Updates to UserTaskView grants cannot change grant type.

**Action:** Do not change the grant type when updating UserTaskView ViewGrants.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30728: Invalid ViewGrant type.**

**Cause:** Invalid View Grant type of {0} was specified for grant of view {1} to {2}.

**Action:** Valid ViewGrant types are SHARE\_DATA and SHARE\_DEFINITION.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30729: Invalid UserTaskView type.**

**Cause:** {0} is not a valid value for view type.

**Action:** Valid UserTaskView types are VIEW and STANDARD\_VIEW.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30730: Public UserTaskView access error.**

**Cause:** User {0} does not have permission to manage views of type STANDARD\_VIEW.

**Action:** Only users with workflow administrator privilege can create, update or delete UserTaskViews of type PUBLIC\_VIEW.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**BPM-30731: View for update does not exist.**

**Cause:** Cannot update view {0}. No view exists with ID {1}.

**Action:** Check that the view ID is correct, and that another user has not deleted the view being updated.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30732: Invalid OptionalInfo value specified.**

**Cause:** {0} specifies an invalid OptionalInfo value of {1}.

**Action:** Specify a valid OptionalInfo value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30733: Invalid column specified for ordering clause.**

**Cause:** {0} specifies an invalid ordering column name of {1}.

**Action:** Specify a valid Task column name in the ordering clause.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30734: Invalid sort order specified for ordering clause.**

**Cause:** {0} specifies an invalid sort order of {1} for the column {2}.

**Action:** Specify a valid sort order in the ordering clause.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30735: Invalid column specified for view chart group by column.**

**Cause:** The view {0} specifies an invalid chart group by column name of {1}.

**Action:** Specify a valid Task column name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30736: Rules cannot be associated with 'TODO' tasks.**

**Cause:** The rule {0} illegally specifies the 'TODO' task type {1}.

**Action:** Associate the rule with a different task type, or with no task type.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-30737: Application role does not exist.**

**Cause:** There is no such role as {0} in application {1}.

**Action:** Specify a valid role and application name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30738: Invalid Participant type.**

**Cause:** Participant named {0} specifies an invalid type of {1}.

**Action:** Specify a valid ParticipantType. Valid types are USER, GROUP, APPROLE.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30739: Invalid Arguments specified.**

**Cause:** Atleast one among {0} , {1} and {2} seems to be invalid .

**Action:** Specify valid arguments.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30740: Policy Object already exists.**

**Cause:** Policy object {0} already exists in the policy store.

**Action:** .

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30741: Policy Store error.**

**Cause:** Failed to perform the desired operation.

**Action:** See the exception log for the reason behind the failure to fix the issue.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30742: Attempt to execute privileged action.**

**Cause:** An attempt to execute a privileged action was made.

**Action:** Ensure that the codebase being used has the necessary permissions and privileges. If not, grant the same in the application's policy file. Contact oracle support if error is not fixable.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-30743: Application Role in use.**

**Cause:** Application Role named {0} is in use, the desired operation cannot be performed.

**Action:** Clear all the dependencies on the app role {0} before performing this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30744: Policy Object not found.**

**Cause:** Atleast one policy object among {0},{1} not found in the policy store.

**Action:** Provide valid arguments

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30745: Invalid Application type.**

**Cause:** Application named {0} specifies an invalid type.

**Action:** Specify a valid Application Type. Valid types are soa-infra, OracleBPM, OracleBPMComposer.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30746: Invalid User type.**

**Cause:** User {0} does not have administrator privileges.

**Action:** Login as an administrator to perform this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30747: UserApplicationData not found.**

**Cause:** No UserApplicationData found with the id {0}

**Action:** Check the id is correct. The UserApplicationData may have been deleted.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30748: Presentation not found.**

**Cause:** No Presentation found with the id {0}

**Action:** Check the id is correct. The Presentation may have been deleted.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-30749: Invalid PresentationDataType.**

**Cause:** The presentation {0} specifies an invalid PresentationDataType of {1}. Valid values are: {2}.

**Action:** Specify a valid PresentationDataType.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30750: Presentation type mismatches View type.**

**Cause:** The view {0} is associated with Presentation {1}, which is of type {2}, instead of the expected type {3}.

**Action:** Views must be associated with Presentations of matching type. Associate the view with a Presentation of the appropriate type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30751: Dynamic Assignment Framework function {0} experienced error querying the workflow schema: {1}**

**Cause:** A Dynamic Assignment Function experienced an error whilst attempting to query data from the workflow schema.

**Action:** Check the underlying error. Verify that the workflow datasource is correctly configured, and that database server is available. If this is a custom dynamic assignment function, ensure that the SQL being executed is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30752: Group {0} not found by Authorization Service**

**Cause:** The Dynamic Assignment Framework was unable to locate a group named {0} using the Authorization Service.

**Action:** Check that the group name is correct. If the group name is correct, check that the Authorization Service is configured correctly, and that the directory it uses contains the specified group.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30753: Dynamic Assignment Framework experienced error invoking Authorization Service: {0}**

**Cause:** The Dynamic Assignment Framework experienced an error whilst attempting to invoke the Authorization Service.

**Action:** Check the underlying error, and verify that the identity service is configured correctly.

**Level:** 1



---

**Type:** ERROR

**Impact:** Programmatic

**BPM-30755: No such Dynamic Assignment Function as {0}**

**Cause:** There is no such function as {0} registered with the Dynamic Assignment Framework. Specify a valid function name

**Action:** Check that a correct function name is specified. If this is a correct function name, ensure that the function is registered in the workflow configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30756: Dynamic Assignment Function {0} does not support user assignment.**

**Cause:** The Dynamic Assignment Function {0} does not allow dynamic assignment to users. Only assignment to groups is supported.

**Action:** Only use this function for group assignments. To enable user assignment, the java class that implements this function must be modified to implement the IDynamicUserAssignment interface.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30757: Dynamic Assignment Function {0} does not support group assignment.**

**Cause:** The Dynamic Assignment Function {0} does not allow dynamic assignment to groups. Only assignment to users is supported.

**Action:** Only use this function for user assignments. To enable group assignment, the java class that implements this function must be modified to implement the IDynamicGroupAssignment interface.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30758: Could not locate Dynamic Assignment Function implementation class: {0}**

**Cause:** The Dynamic Assignment Framework could not locate function implementation class: {0} Either the class name is incorrect, or the class is not in the classpath

**Action:** Check that the specified class is located in the classpath. Check that the correct classname is specified in the workflow configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30759: Dynamic Assignment Function class interface implementation error.**

**Cause:** Dynamic Assignment Function class Classes that implement {0} does not implement IDynamicUserAssignmentFunction or IDynamicGroupAssignmentFunction.

---

**Action:** Dynamic Assignment Functions must implement at least one of the interfaces IDynamicUserAssignmentFunction or IDynamicGroupAssignmentFunction. Check the specified class and ensure it implements one of the interfaces.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30760: Failed to instantiate instance of Dynamic Assignment Function class.**

**Cause:** The Dynamic Assignment Framework could not instantiate the Dynamic Assignment Function class: {0} because it is not a concrete class.

**Action:** Ensure that the class {0} is not an interface or abstract class.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30761: Dynamic Assignment Function class constructor error.**

**Cause:** The Dynamic Assignment Framework could not instantiate an instance of {0} because there is no accessible no-argument constructor.

**Action:** Ensure that the class {0} is public, and provides a public, no-argument constructor.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30762: Dynamic Assignment Function class does not implement IDynamicAssignmentFunction.**

**Cause:** Dynamic Assignment Function class {0} must implement the interface IDynamicAssignmentFunction.

**Action:** Check the specified class and ensure it implements the interface IDynamicAssignmentFunction.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30801: Error selecting user metadata from repository.**

**Cause:** An attempt to select data from table {0} resulted in the error: {1}

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30802: Error inserting user metadata into repository.**

**Cause:** An attempt to insert user data into table {0} resulted in the error: {1}

---

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30803: Error updating user metadata in repository.**

**Cause:** An attempt to update user data in table {0} resulted in the error: {1}

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30804: Error deleting user metadata from repository.**

**Cause:** An attempt to delete user data from table {0} resulted in the error: {1}

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30805: Operation not supported for this column type.**

**Cause:** The operator {0} is not supported for columns of type {1}.

**Action:** Use a different operator when specifying predicate conditions for this column.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30851: User has insufficient privileges to update workflow runtime configuration data.**

**Cause:** User {0} attempted to update runtime configuration data without having the required {1} privilege.

**Action:** Ensure that the user has been granted the appropriate workflow privileges before updating runtime configuration data.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30852: Invalid task message attribute specified in attribute label.**

**Cause:** The flexfield label {0} uses the invalid task flexfield column name {1}.

**Action:** Specify a valid task flexfield column name.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-30853: Workflow definition does not exist.**

**Cause:** No workflow definition found with ID {0}.

**Action:** Specify a valid workflow definition ID.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30854: Failed to retrieve list of Dynamic Assignment Functions.**

**Cause:** Could not get list of Dynamic Assignment Functions.

**Action:** Check underlying exception. Ensure Dynamic Assignment Functions are configured correctly in the workflow configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30855: Flexfield mappings for complex payload attributes must specify an xpath expression.**

**Cause:** Payload attribute {0} is a complex type. Mappings must provide an xpath to a simple type property.

**Action:** Provide a valid xpath expression that maps to a simple-type property of the complex type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30856: Payload attribute type does not match flexfield label type.**

**Cause:** Payload attribute {0} has a type that does not match the type for flexfield label {1}.

**Action:** Use a flexfield label of the appropriate type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30857: Workflow payload attribute not found.**

**Cause:** Workflow task type {0} does not have a payload attribute named {1}.

**Action:** Ensure that workflow task type and payload attribute name are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30858: Error in invoking runtime config service.**

**Cause:** A client side error occurred in invoking the runtime config service.

**Action:** Verify that the connection information for the server is correct, and that the server hosting the runtime config service is available.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30859: Error in invoking runtime config service operation**

**Cause:** An client side error occurred in invoking the runtime config service operation {0}.

**Action:** Verify that the connection information for the server is correct, and that the server hosting the runtime config service is available.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30860: Fault reported by runtime config service**

**Cause:** The runtime config service returned a fault for the following error: {0}

**Action:** Refer to the error reported by the fault.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30861: Label name is already in use.**

**Cause:** A label with the name {0} already exists.

**Action:** Specify a different name for the label.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30862: Workflow definition does not exist.**

**Cause:** No workflow definition found with task definition namespace {0}.

**Action:** Specify a valid workflow definition namespace.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30863: Cannot delete an attribute label for which payload mappings exist.**

**Cause:** Payload mappings exist for the attribute label {0}.

**Action:** Remove all payload mappings before deleting the attribute label.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30864: Label is already in use by this task component definition.**

**Cause:** The attribute label {0} is already being used by this workflow definition.

**Action:** Specify a different label.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30865: Invalid attribute type.**

**Cause:** An invalid attribute type of {0} was specified.

**Action:** Specify a valid attribute type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30866: Flexfield is already in use by this task component definition.**

**Cause:** The flexfield {0} is already being used by this workflow definition in a mapping to the label {1}.

**Action:** Specify another label that uses a different flexfield.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30890: Approval Group already exists**

**Cause:** An Approval Group with this name already exists:{0}

**Action:** Use a different name for the Approval Group or use updateApprovalGroup method if referring to this Approval Group .

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30891: Approval Group not found.**

**Cause:** Approval Group with the given name doesnot exist: {0}

**Action:** Verify that the Approval Group name is correct and whether it has been correctly created.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30892: Approval Group not deleted.**

**Cause:** The specified Approval Group could not be deleted: {0}

**Action:** Verify that the Approval Group name is correct and whether it had been correctly created.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30893: Approval Group member not in list.**

---

**Cause:** The specified Approval Group member was not found in the member list for the given Approval Group: {0}

**Action:** Verify that the Approval Group name is correct and that the specified member had been correctly created in the group.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30894: Approval Group member not created.**

**Cause:** The specified member could not be added to the given Approval Group: {0}

**Action:** Verify that the Approval Group name is correct and that the member is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30895: Approval Group member not updated.**

**Cause:** The specified member could not be updated in the given Approval Group: {0}

**Action:** Verify that the Approval Group name is correct and that the member had been correctly created.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30897: Approval Group member not deleted.**

**Cause:** The specified member could not be deleted from the given Approval Group: {0}

**Action:** Verify that the Approval Group name is correct and whether the member had been correctly created.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30898: Approval Group member already exists.**

**Cause:** The specified member already exists in the given Approval Group: {0}

**Action:** Use the updateInGroup api instead.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30899: No matching Approval Group found.**

**Cause:** There are no Approval Groups matching the given search condition: {0}

**Action:** Verify the search condition and search type specified.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30900: Unable to log adhoc approver insertion .**

**Cause:** There was an error trying to log the adhoc approver insertion information in the AMX Change table: {0}

**Action:** Verify that the stage name and task ID provided are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30901: Task Evidence does not exist.**

**Cause:** No Evidence found in the repository.

**Action:** Ensure that an evidence corresponding to the operation exists in the repository.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30902: Task Evidence JAXB Model is malformed.**

**Cause:** This could either be because the XML data for the model does not confirm to the schema or there was an internal JAXB error.

**Action:** Ensure that the XML data being passed confirms to the Task Evidence Service schema.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30903: Certificate does not exist.**

**Cause:** A certificate with Serial Number {0} and Issuer DN {1} was not found.

**Action:** Upload the certificate before proceeding. Also ensure that the CA and the URL have been uploaded.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30904: The evidence is not valid.**

**Cause:** All required parameters are not set.

**Action:** Ensure that all required parameters are set into the evidence object.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30905: The certificate with Serial Number {0} and Issuer DN {1} is not valid.**



---

**Cause:** The certificate could have expired. The certificate could also be in an unsupported format or malformed.

**Action:** Ensure that the certificate is as supplied by the certificate authority.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30906: The signature is not valid.**

**Cause:** The signature does not confirm to the content and certificate. The signature may also be in an unsupported format or malformed.

**Action:** Ensure that the signature is not modified once it is created.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30907: Internal Error.**

**Cause:** The underlying Security APIs have thrown an exception.

**Action:** Look at the exception trace for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30908: CRL validation error for certificate Id {0} and CA name {1}.**

**Cause:** The CRL could not be validated.

**Action:** Ensure that the CA URL exists and is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30909: Certificate cannot be uploaded.**

**Cause:** The certificate could not be uploaded. Only X.509 certificates are supported.

**Action:** Ensure that the file or string contains a X.509 certificate in a supported format. Also, ensure that the certificate or any other certificate in the chain do not exist in the system. All those certificate which did not exist in the system would have been uploaded.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30910: Invalid Access Error.**

**Cause:** User {0} does not have permission to perform {1}.

**Action:** Ensure the user has been granted appropriate privileges.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**BPM-30911: Unable to initialize the queue connection factory for queue {0}**

**Cause:** Unable to initialize the queue connection factory for queue {0}

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30912: Error in invoking task evidence service**

**Cause:** A client side error occurred in invoking the task evidence service.

**Action:** The service could be down. Check the exception error stack to identify the error. If the error persists, contact Oracle Support Services..

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30913: Error in task evidence SOAP service**

**Cause:** An error occurred in invoking the task evidence service over SOAP.

**Action:** Ensure that soap messages are proper and well formed. Check the exception error stack to identify the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30951: Invalid view ID.**

**Cause:** The view ID: {0} does not match any view stored in the repository.

**Action:** Ensure that a correct view ID is being passed.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30952: Invalid display column.**

**Cause:** The display column {0} is not a valid Task column.

**Action:** Specify a valid column name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30953: User has insufficient privileges to use given filter.**

**Cause:** The user {0} in identity context {1} does not have sufficient privileges to query tasks with {2} filter.

**Action:** Ensure that proper privileges are granted to the user.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30954: Invalid assignment filter value specified for predicate.**

**Cause:** The predicate specifies an invalid AssignmentFilter value of {0}.

**Action:** Specify a valid AssignmentFilter value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30955: Invalid column name used in predicate.**

**Cause:** The predicate specifies a column named {0} which does not exist on the table {1}.

**Action:** Specify a valid column and table in the predicate.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30956: Invalid logical operator used in predicate.**

**Cause:** The predicate uses an invalid logical operator of {0}.

**Action:** Use a valid logical operator. Valid values are AND and OR.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30957: Invalid operator used in predicate.**

**Cause:** The predicate uses an invalid operator value of {0} with column {1}.

**Action:** Specify a valid operator value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30958: Predicate specifies an invalid operator for a null value.**

**Cause:** The operator {0} cannot be used with a value of null.

**Action:** Specify a value, or use the EQ, NEQ, IS\_NULL or IS\_NOT\_NULL operators.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30959: Predicate clause with ValueListType must use IN or NOT\_IN operator.**

**Cause:** The operator {0} cannot be used with a value list.

**Action:** Use the IN or NOT\_IN operators when using a value list.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30960: Invalid value specified for N\_DAYS operator in predicate clause.**

**Cause:** The predicate value {0} is not valid for the operator {1}.

**Action:** Specify an integer value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30961: Invalid value specified in predicate clause.**

**Cause:** The value {0} for column {1} is invalid for the column's datatype.

**Action:** Specify a value that is of the correct type, or is another column with a matching datatype.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30962: Invalid Presentation type.**

**Cause:** The specified Presentation {0} is of type {1}, but the required type is {2}.

**Action:** Specify a different Presentation of the correct type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-30963: Invalid View type.**

**Cause:** The specified View {0} is of type {1}, which is not valid for querying tasks.

**Action:** Specify a different View of a correct type (VIEW or STANDARD\_VIEW).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-31002: Error while publishing message to notification queue**

**Cause:** Error while publishing message to notification queue

**Action:** Check Application server data source properties for BPEL-Workflow connections. Check schema and verify database connections.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-31003: Unable to initialize the queue connection factory for queue {0}**

**Cause:** Unable to initialize the queue connection factory for queue {0}

**Action:** Check Application server data source properties for BPEL-Workflow connections. Check schema and verify database connections.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-31004: Error while querying notification from repository for ID {0}**

**Cause:** Error while querying notification from repository for ID {0}

**Action:** Check Application server data source properties for BPEL-Workflow connections. Check schema and verify database connections.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-31005: Error while inserting notification in repository**

**Cause:** Error while inserting notification in repository

**Action:** Check Application server data source properties for BPEL-Workflow connections. Check schema and verify database connections.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-31006: Error while updating notification in repository for ID {0}**

**Cause:** Error while updating notification in repository for ID {0}

**Action:** Check Application server data source properties for BPEL-Workflow connections. Check schema and verify database connections.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-31007: Error while deleting notification in repository for ID {0}**

**Cause:** Error while deleting notification in repository for ID {0}

**Action:** Check Application server data source properties for BPEL-Workflow connections. Check schema and verify database connections.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-31008: Incoming message could not be processed**

**Cause:** Incoming message could not be processed

**Action:** Ensure that the response message is not corrupted

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-31009: Incoming message content is invalid**

**Cause:** Incoming message could not be processed due to invalid content

---

**Action:** Ensure that the response message is not corrupted: The encrypted response should begin and end with '[[NID]]'

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-31010: No NID Placeholder**

**Cause:** Incoming message content does not contain Notification ID placeholders

**Action:** Ensure that the response message is not corrupted

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-31011: Error while updating table**

**Cause:** Error while updating {0} table

**Action:** Check Application server data source properties for BPEL-Workflow connections. Check schema and verify database connections.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-31012: Error while inserting into table**

**Cause:** Error while inserting into {0} table

**Action:** Check Application server data source properties for BPEL-Workflow connections. Check schema and verify database connections.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-31013: Error while deleting from table**

**Cause:** Error while deleting from {0} table

**Action:** Check Application server data source properties for BPEL-Workflow connections. Check schema and verify database connections.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-31014: Error while selecting from table**

**Cause:** Error while selecting from {0} table

**Action:** Check Application server data source properties for BPEL-Workflow connections. Check schema and verify database connections.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**BPM-31015: Error while sending notification**

**Cause:** Error while sending notification to {0}

**Action:** Check the underlying exception and fix it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-31016: Error while receiving notification response**

**Cause:** Error while receiving response from {0} at {1}; for message {2}

**Action:** Ensure that response message is not corrupted; User should respond to actionable notifications from the same email account to which it was sent; Task status has not changed

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-31017: Cannot create notification object**

**Cause:** Error while creating {0} object

**Action:** Internal Error; Cannot create Notification Object

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-31018: Incorrect Notification Configuration**

**Cause:** Incorrect Configuration : {0}

**Action:** NotificationMode in workflow-notification-config.xml should be either EMAIL or ALL to send Email notifications; It should be ALL to send any other type of notifications

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-31019: MimeType not supported**

**Cause:** MimeType {0} is not supported for channel type{1}

**Action:** In the application, Use only supported mime types for sending notifications

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-31020: Auto Reply Error**

**Cause:** Error while sending auto reply on {0} channel

**Action:** Internal Error. Ensure that the message being replied to is not corrupted

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**BPM-31021: Invalid Parameters**

**Cause:** Invalid parameters supplied for Notification : {0}

**Action:** Provide valid notification inputs like recipient Address, Channel type etc

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-31022: Could not register/un register/fetch spam sources**

**Cause:** Could not register/un register/fetch spam sources: {0}

**Action:** Possible cause : Invalid address is being registered/unregistered

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-31023: Cannot send Notification to specified address**

**Cause:** Cannot send {0} notification to {1} address. The address is being marked as 'invalid' and no further notification would be sent to this address.

**Action:** Make sure that : the address specified is correct; the Email/Gateway server is up and running. Once the problem is corrected, remove the address from invalid address list using EM.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-31024: Invalid recipient address**

**Cause:** Recipient address specified for {0} notification is invalid : {1}

**Action:** Check Workflow Notification Configuration; Ensure that Email/IM recipient address is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-31025: Actionable Email/IM has been responded from a different account.**

**Cause:** Actionable {2} had been sent to {0}, but received response from {1}.

**Action:** Actionable notifications should be responded from the same account to which it was sent.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-31026: user-ID not set**

**Cause:** user-ID field is not set in the user payload

**Action:** Ensure that the payload contains user ID



---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-31027: group-ID is not set**

**Cause:** group-ID field is not set in the group payload

**Action:** Ensure that Payload contains group ID

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-31028: Could not send notification to user**

**Cause:** Could not send notification to user {0}

**Action:** Check Workflow Notification Configuration. Ensure that underlying channels are configured.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-31029: Notification Channel not supported**

**Cause:** Notification Channel {0} is not supported

**Action:** Requested channel is not supported.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-31030: Error while creating notification content**

**Cause:** Could not create notification content

**Action:** Ensure that the files being used for attachment exist and not corrupted.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-31031: Incorrect incoming Notification Configuration**

**Cause:** Incorrect Incoming Configuration : {0}

**Action:** The AccountName in workflow-config.xml should be one of the names used in workflow-notification-config.xml

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-31032: Error status received from UMS.**

**Cause:** Status detail : Status type : {0}, Status Content : {1}, Addressed to : {2}, UMS Driver : {3}, UMS Message Id : {4}, Gateway message Id : {5}, Status Received at : {6}

---

**Action:** Check status details and fix the underlying reason, which caused error

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-32001: Error in Identity Service**

**Cause:** Error occurs while using Identity Service

**Action:** Check underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-32002: Error in create parameters from WSIF Java Web Services message**

**Cause:** The {0} could not be created because expected element {1} is not be found in the element {2} in the parameter passed to WSIF Java Web Services

**Action:** Check the message passed to the Web service. Also check underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-35001: Configuration file {0} not found.**

**Cause:** Could not locate configuration file with the path: {0}

**Action:** Ensure that the path is correct, and that there is a configuration file at the specified path.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-35002: Configuration file format error whilst parsing file {0}: {1}**

**Cause:** Could not parse the configuration file {0} because of the error: {1}

**Action:** Check the underlying error, and ensure that the configuration file is formatted correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-35003: Error saving configuration file {0}: {1}**

**Cause:** Failed to save the configuration file to {0} because of the error: {1}

**Action:** Check the underlying error. Ensure that the path {0} is correct, and that if the file already exists that it is in a writeable state.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-35004: Workflow deployment is not supported**

**Cause:** Workflow deployment is not supported in platform {0}

**Action:** Check the underlying error. Ensure that the platform {0} is correct

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-35005: Unable to deploy workflow files**

**Cause:** Unable to deploy workflow files

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-35006: Unable to undeploy workflow files/metadata**

**Cause:** Unable to undeploy workflow files/metadata

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-35007: Unable to load service client configuration file**

**Cause:** Unable to load service client configuration file {0}.

**Action:** Check if service client configuration file {0} exists in the classpath. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-35008: Unable to find service definition in client configuration file**

**Cause:** Unable to find service {0} definition in client configuration file {1}

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-35009: Unable to obtain scheduler to schedule workflow service timers**

**Cause:** Unable to obtain scheduler to schedule workflow service timers

**Action:** Retry the action if possible. If the error persists, contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-35010: Unable to Encrypt data**

**Cause:** Unable to Encrypt data

**Action:** Check installation/post-installation steps for errors. Check for errors during SOA server startup.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-35011: Unable to Decrypt data**

**Cause:** Unable to Decrypt data

**Action:** Check for corrupted encrypted data. Check installation/post-installation steps for errors. Check for errors during SOA server startup.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-35012: Unable to fetch/generate encryption key**

**Cause:** Unable to fetch/generate encryption key

**Action:** Check installation/post-installation steps for errors. Check for errors during SOA server startup.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36001: Internal error.**

**Cause:** An internal error occurred in the Decision Service, info code {0}

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36011: Error while initializing decision service.**

**Cause:** Error while initializing decision service.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36012: Error creating a JAXB marshaller for the decision service.**

---

**Cause:** Error while creating a JAXB marshaller for the decision service.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36013: Error creating a JAXB unmarshaller for the decision service.**

**Cause:** Error while creating a JAXB unmarshaller for the decision service.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36050: Error in decision service interaction pattern.**

**Cause:** An error occurred in interpreting the interaction pattern {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36051: Error while executing interaction pattern Assert.**

**Cause:** Error while executing interaction pattern Assert for path {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36052: Error while executing interaction pattern AssertExecute.**

**Cause:** Error while executing interaction pattern AssertExecute for path {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36053: Error while executing interaction pattern Watch.**

**Cause:** Error while executing interaction pattern Watch for path {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**BPM-36054: Error while executing interaction pattern AssertExceuteWatchStateless.**

**Cause:** Error while executing interaction pattern AssertExceuteWatchStateless for path {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36055: Error while executing interaction pattern AssertExceuteWatchStateful.**

**Cause:** Error while executing interaction pattern AssertExceuteWatchStateful for path {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36056: Error while executing interaction pattern CallFunctionStateless.**

**Cause:** Error while executing interaction pattern CallFunctionStateless for path {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36057: Error while executing interaction pattern CallFunctionStateful.**

**Cause:** Error while executing interaction pattern CallFunctionStateful for path {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36101: Error while initializing the decision service cache.**

**Cause:** Error while initializing the decision service cache.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**BPM-36102: Error reading configuration file.**

**Cause:** Error while trying to read the configuration file {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36103: Error creating the payload.**

**Cause:** Error while trying to create the payload for element {0}, namespace {1}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36104: Error creating the decision document.**

**Cause:** Error while trying to create the decision document for {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36105: Error creating the decision service error SOAP element.**

**Cause:** Error while trying to create the decision service error SOAP element for service {0}, pattern {1}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36106: Error creating the SOAP element from decision.**

**Cause:** Error while trying to create the SOAP element from the decision of service {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36107: Error unmarshalling the decide context.**

**Cause:** Error while trying to unmarshal the payload for pattern {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36108: Decision Service metadata not in cache.**

**Cause:** Cannot find metadata in path {0} for {1}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36109: Error caching the Decision Services metadata.**

**Cause:** Error caching the decision services metadata for path {0}.

**Action:** Check the underlying exception and correct the error. This is most likely due to a rule modeling issue. Validate the rule dictionary in rule designer and fix any errors and warnings. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36110: Error unmarshalling decision services configuration.**

**Cause:** Error while trying to unmarshal decision services configuration from URL {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36111: Error validating the decision service request.**

**Cause:** The request for path {0}, service {1} pattern {2} is not valid.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36112: A Decision Service of the given name doesn't exist.**

**Cause:** The component {1} in composite {0} does not expose a service {2}

**Action:** Check the services that are exposed by component {1}. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic



---

**BPM-36150: Decision Service configuration not available.**

**Cause:** No configuration information available for service {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36151: Error while creating deployment directory.**

**Cause:** Error while creating deployment directory {0} for service {1}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36152: Error while creating WSDL for backend decision service.**

**Cause:** Error while creating the WSDL for the backend decision service {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36153: Error while creating service configuration file for backend decision service.**

**Cause:** Error while creating the service configuration file for the backend decision service {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36154: Error while copying supporting XSD files for decision service.**

**Cause:** Error while copying supporting XSD files for decision service {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36155: Error while generating JAXB classes for decision service.**

**Cause:** Error while generating JAXB classes from {0} for the backend decision service {1}.

---

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36156: Error while creating deployment descriptor for decision service.**

**Cause:** Error while creating deployment descriptor {0} for the backend decision service {1}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36157: Error while copy rule repository file to deployment directory.**

**Cause:** Error while copy the file {0} to {1} for decision service {2}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36158: Error while creating partnerlink WSDL.**

**Cause:** Error while creating partnerlink WSDL for {0} in {1}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36159: Error compiling fact classes.**

**Cause:** Error while compiling fact classes for service {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36160: Error copying decision service configuration file.**

**Cause:** Error copying decision service configuration file to {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-36161: Error copying decision service files.**

**Cause:** The target directory {0} does not exist.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36162: Rule engine not found.**

**Cause:** Unable to find rule engine provider {1} for {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36163: XML schema type not found.**

**Cause:** Unable to find XML schema type for {0}.

**Action:** Check the rule model and decision service interaction. Make sure that all the required XSD schema files are part of the project.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36164: Type not supported.**

**Cause:** Unable to create XML schema element for type {0}.

**Action:** Check the rule model and decision service interaction. Make sure that all the required XSD schema files are part of the project.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36200: Error while initializing the rule engine factory.**

**Cause:** Error while initializing the rule engine factory.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36201: Error while loading a rule engine.**

**Cause:** Error while loading a rule engine for {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36202: Error while loading a fact context.**

**Cause:** Error while loading a fact context for {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36203: Error while creating a rule engine.**

**Cause:** Error while creating rule engine for provider {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36204: Error while creating the fact context.**

**Cause:** Error while creating the fact context for {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36205: Error while creating a rule engine.**

**Cause:** No rule engine class loaded for provider {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36206: Error while creating the fact context.**

**Cause:** No fact context class loaded for fact context {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36207: JAXB context not available for fact.**

---

**Cause:** No JAXB fact context available for fact {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36208: The type is not supported by decision service.**

**Cause:** The type {0} is not supported by decision service.

**Action:** Remodel rules and decision service interaction to use supported types.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36311: Unknown rule repository type.**

**Cause:** The rule repository type {0} is unknown or unsupported in this context.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36312: Error while initializing the rule repository.**

**Cause:** The rule repository cannot be initialized.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36313: Error while loading the rule catalog.**

**Cause:** The rule catalog cannot be loaded.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36314: Error while trying to close the rule engine.**

**Cause:** The rule engine cannot be closed.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-36321: Error while loading the rule set.**

**Cause:** The rule set cannot be loaded.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36322: A rule catalog could not be found.**

**Cause:** The catalog {1} in package {0} could not be found.

**Action:** Make sure that the rule catalog {0}.{1} exists in the path {2}. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36331: Error while initializing the rule session.**

**Cause:** The rule session {0} failed to initialize.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36332: Error while resetting the rule session.**

**Cause:** The rule session {0} reset failed.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36333: Error while executing the rule session.**

**Cause:** The rule session {0} failed to execute.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36334: Error while executing a rule session unit of work.**

**Cause:** The rule session {0} failed to execute step {1} {2}

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36335: Fact not found in the rule engine working memory, rule session execution failed.**

**Cause:** The rule session {0} failed because an instance of the fact {1} could not be found in the working memory of the rule session.

**Action:** This is most likely a rule modeling error. The decision service interaction expects the fact instance to exist in the working memory of the rule session. Check the rule actions in rule designer and make sure that a fact of the expected type is being asserted. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36336: Error while executing a rule session unit of work, duplicate fact instances found.**

**Cause:** The rule session {0} failed because more than one fact instance of the fact {1} exists in the rule session working memory. The decision service cannot identify which one to take.

**Action:** This is most likely due to a rule modeling issue. Make sure that the fact of the given type is asserted only once. One common issue is that the rule conditions are not mutually exclusive and as a result of that more than one rule action is executed. In case the rule action has a assert new statement of the given fact type then multiple fact instances are created in the rule session working memory and the decision service is not able to identify the one that should be returned as the result of the decision service interaction. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36337: Number of facts requested does not match number of facts retrieved from rule engine.**

**Cause:** There are {0} facts requested but the rule engine returned {1} facts.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36338: Wrong fact from rule engine.**

**Cause:** The requested fact name is {0} whereas the one given by the rule engine is {1}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**BPM-36341: Rule session pool object does not exist.**

**Cause:** The requested rule session pool object for path {0} and key {1} does not exist.

**Action:** Check the underlying exception and correct the error. This is most likely due to a rules validation error. Validate the rule dictionary in Rule Designer and correct the validation error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36351: Error loading fact types into the datamodel.**

**Cause:** The data model failed to load fact types.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36352: Error loading functions into the datamodel.**

**Cause:** The data model failed to load functions.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36353: URL error while reading XSD.**

**Cause:** The data model failed to read the XSD {0} because of an URL error.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36354: Error building the XML schema for a XSD.**

**Cause:** The data model failed to build the XML schema from XSD {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36355: Element not found in XML-Schema file.**



---

**Cause:** The element for fact type {0} could not be found in XML Schema file {1}.

**Action:** Make sure that the element {0} exists in the schema file {1} or in one of the schema files that is imported by {1}. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36356: Element not unique in XML-Schema file.**

**Cause:** The element for fact type {0} could not be identified in XML Schema file {1}. There exists multiple elements that could define the fact type {0}: {2}

**Action:** Make sure that the element for fact type {0} is unique in the schema file {1} or in one of the schema files that is imported by {1}. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36357: The function doesn't exist in the datamodel .**

**Cause:** The requested function {0} does not exist in the rule dictionary data model of decision service {1}.

**Action:** Check the rule dictionary of decision service {1}. Make sure that the function {0} exists and has correct parameter and package name settings. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36358: The XML-Schema file for the fact {0} could not be found in the composite.**

**Cause:** The XML-Schema file {2} could not be found in the composite. The XML fact {0} of target namespace {1} assumes the existence of the schema file in the composite.

**Action:** Check the composite for the schema {2} and make sure it has target namespace {1}. The schema is expected in the project xsd or businessCatalog folder. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36610: No rule engine provider implementation found for Ilog JRules.**

**Cause:** Rule Engine provider implementation for Ilog JRules not found.

**Action:** Check the configuration file DecisionServicesConfiguration.xml. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-36611: Error communicating with Rule Execution Server.**

**Cause:** Rule Execution Server communication error, {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services..

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36612: Unsupported Ilog JRules session provider class**

**Cause:** The rule session provider class {0} is unsupported or does not exist.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36615: Error reading Rule Application Archive.**

**Cause:** Failed to read rule application archive {0} because of {1}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36616: Error creating unmarshaller.**

**Cause:** Failed to create an unmarshaller for {1}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36617: Error unmarshalling metadata from the rule application.**

**Cause:** Failed to unmarshal metadata from {0}.

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36620: Creation of rule session failed.**

**Cause:** Failed to create a rule session for {0} {1}

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36621: Error in rule execution.**

**Cause:** Failed to execute rule session {0} {1}

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36622: Error in rule execution, issue with remote connection to Rule Execution Server**

**Cause:** Failed to execute rule session {0} because of a remote error. {1}

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36623: Error resetting rule session.**

**Cause:** Failed to reset rule session {0} {1}

**Action:** Check the underlying exception and correct the error. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36801: Error initializing the Rule Management Service Factory.**

**Cause:** Attempt to initialize the Rule Management Service Factory failed because of a JAXB error

**Action:** Refer to the soainfra log files for details and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36820: Error {0} in Oracle Business Rules.**

**Cause:** Error {0} occurred in the backend rule engine. The error message is {1}

**Action:** Fix the error and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36841: Error unmarshalling from org.w3c.dom.Element to JAXB.**

---

**Cause:** Attempt to unmarshall element {0} using JAXB context {1} resulted in error: {2}

**Action:** Refer to the soainfra log files for details and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-36842: Error in rule management service Web service operation invocation**

**Cause:** Error in rule management service Web service operation invocation. The error is {0}.

**Action:** Verify that the SOAP connection information for the server is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-37001: Error adding List Builder property.**

**Cause:** Failed to add property: {0}

**Action:** Verify validity of list builder properties.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-37002: Error setting starting point implicitly.**

**Cause:** Failed to walk up the hierarchy as requestor or requestor role is already top approver: {0}

**Action:** Set the starting point explicitly to some one below the top Approver.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-37003: Error setting hierarchy provider instance in list builder.**

**Cause:** Failed to set hierarchy provider instance {0} in list builder.

**Action:** Set the valid hierarchy provider instance in the list builder.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-37012: Approval Group is empty.**

**Cause:** The specified Approval Group is empty: {0}

**Action:** Set the ALLOW\_EMPTY\_GROUP property to true or populate the Approval Group with members.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-37013: Dynamic Approval Group expansion error.**

**Cause:** Couldnot retrieve approvers from the dynamic Approval Group: {0}

**Action:** Ensure that the Dynamic Approval Group has been correctly implemented.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-37014: Approval Group could not be expanded.**

**Cause:** The specified Approval Group could not be expanded to retrieve approvers: {0}

**Action:** Verify the contents and member list of the Approval Group.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-37051: Invalid preference for the list builder.**

**Cause:** Invalid preference set for the list builder: {0}

**Action:** Set the preference to a value greater than 0.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-37052: No voting regime i set for the list builder.**

**Cause:** No voting regime is set for the list builder: {0}

**Action:** Set the voting regime to a valid value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-37053: Constraint is not set.**

**Cause:** No constraint is set.

**Action:** Set the constraint to a valid value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-37054: Constraint Level is not valid.**

**Cause:** Constraint Level is not valid.

**Action:** Set the level to a value greater than 0.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-37055: Approval Group name is empty.**

**Cause:** Approval Group name is empty.

**Action:** Populate the Approval Group name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-37056: Identification key is not found.**

**Cause:** Identification key is not found in the Task object.

**Action:** Populate the Identification key.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-37057: Invalid approver list builder map value.**

**Cause:** The approver list builder map value {0} is invalid.

**Action:** Verify that the approver list builder map value is correct in the task definition.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-37058: Invalid value for xpath expression.**

**Cause:** The xpath expression {0} is invalid for the task.

**Action:** Verify that the xpath expression is valid for the task data.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-37059: Invalid approver list builder constraint value.**

**Cause:** The approver list builder constraint value {0} is invalid.

**Action:** Verify that the approver list builder constraint value is correct in the task definition.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-37100: List Builder had unfulfilled constraints**

**Cause:** The following constraints were unfulfilled: {0}

**Action:** Verify validity of input properties.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-37101: List Builder failed to initialize principal hierarchy**

**Cause:** List Builder could not initialize principal hierarchy service.

**Action:** Verify availability of user hierarchy service.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-37102: List Builder failed while crawling principal hierarchy**

**Cause:** List Builder failed while crawling principal hierarchy.

**Action:** Verify availability of user hierarchy service and validity of user data.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-37103: Service provider failed to initialize.**

**Cause:** Service provider {0} initialization failed.

**Action:** This error occurs due to error in service provider configuration or if it is not found in config file. Please check configuration for service provider {0} and verify that it is accessible. Please check actual exception below for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-37104: Service provider invocation error.**

**Cause:** Failed to invoke web method on Service provider {0} .

**Action:** This error occurs when service provider is unavailable, unreachable, or if error in configuration. This error may occur during invocation of web methods of the provider due to above reason. Please check the log file for more specific exception and actual cause of the error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-37105: Service provider class definition error.**

**Cause:** Failed to load the class required for the provider {0} .

**Action:** This error occurs when a service provider class is not specified correctly in the configuration file. Check the documentation for correct class name for provider {0}.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-37106: Service provider could not be loaded.**

**Cause:** Service provider {0} load failed.

---

**Action:** This exception occurs when service provider could not be loaded or used as defined in the configurations and the flag `mustUseSpecifiedProvider` is set to true. Please check configuration for service provider {0} and verify that it is accessible. Please check actual exception in the log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-37150: Approval Management Decision Handler Error - Missing required parameter.**

**Cause:** Missing one or more of the required parameter(s) - {0}.

**Action:** Make sure parameter is passed properly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-37151: Error while calling Approval Management Prescription Action.**

**Cause:** Calling Approval Management Prescription Action with decision point name {0}, stage name {1}, and rule name {2} result in error {3}.

**Action:** Verify underlying exception(s) for details.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-37152: Error while calling Approval Management Decision Service.**

**Cause:** Calling Approval Management Decision Service result in error {0}.

**Action:** Verify underlying exception(s) for details.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-37153: Error in invoking the approval management Service.**

**Cause:** Approval management service evaluates the rule in the routing slip corresponding to the task definition {0}. During evaluation of this rule, there was an error. See the underlying exception for details.

**Action:** See the underlying exception(s) for details.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-37154: Payload Error in Approval Management Service.**

**Cause:** Mandatory payload element {0} missing.

**Action:** Populate the element {0} in the payload.

**Level:** 1

**Type:** ERROR



---

**Impact:** Programmatic

**BPM-37155: No Rule Error in Approval Management Service.**

**Cause:** No valid rule could be found.

**Action:** Verify the rule setup is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-38001: Error in invoking activity guide metadata service**

**Cause:** An client side error occurred in invoking the activity guide metadata service.

**Action:** Verify that the connection information of the server is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-38002: Error in invoking activity guide query service**

**Cause:** An client side error occurred in invoking the activity guide query service.

**Action:** Verify that the connection information of the server is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-38003: Insufficient privileges to access the activity guide.**

**Cause:** User {0} cannot access the activity guide with ciKey: {1}

**Action:** Ensure that the user has been granted appropriate privileges to access the activity guide info.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-38004: Insufficient privileges to use the ADMIN assignment filter.**

**Cause:** User {0} does not have the activity guide administration privilege required for the using of the ADMIN assignment filter.

**Action:** Only users with activity guide administrator privilege can use the ADMIN assignment filter when invoking the activity guide query service.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-38005: Error while querying activity guide instance {0}**

**Cause:** Error while querying activity guide instance {0}

**Action:** Verify that the parameters passed are correct.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**BPM-38006: Runtime error in AG Query Service**

**Cause:** Runtime error in AG Query Service. {0}

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-38007: Invalid input AG display column.**

**Cause:** The column name, {0}, specified in the AG display column list does not map to a valid AG field.

**Action:** Refer to the AG query service javadoc to find a list of valid AG columns, and make sure that the input AG columns are in the list.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-38101: Activity Guide instance {0} not found in registration cache.**

**Cause:** The Activity Guide instance is not found in the registration cache.

**Action:** Re-register the activity guide instance.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-38201: Messaging Service cannot create JNDI initial context.**

**Cause:** Messaging service cannot create JNDI context.

**Action:** Contact your system Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-38202: Messaging Service time out occurred on a receive.**

**Cause:** Messaging service receive timed out while waiting on JMS topic.

**Action:** Confirm that message producer is functioning and message consumer is listening on correct topic.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-38203: Messaging service fail to lookup JMS object {0} in JNDI.**

**Cause:** Messaging service cannot create JNDI object.

**Action:** Check if the JMS object {0} is configured in JNDI.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**BPM-39001: Unauthorized user**

**Cause:** User, {0}, is not authorized to finish this operation

**Action:** Login with appropriate user

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-39002: MDS is not supporting versioning**

**Cause:** Configured MDS is not supporting versioning.

**Action:** Check soa-infra MDS configuration and configure it to point to a store that supports versioning. Ex: database

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-39003: Generic MDS Error**

**Cause:** Error occurred while performing MDS operation. Error: {0}

**Action:** Contact system administrator

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-39004: SOAP Element conversion error**

**Cause:** Error occurred while converting the result object into SOAP message

**Action:** Contact system administrator

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-39005: Empty sandbox name**

**Cause:** Sandbox name cannot be empty

**Action:** Specify a valid name for the sand box

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-39501: Configuration error**

**Cause:** Clients are not configured

**Action:** Specify a FederatedClient in configuration

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-39502: No server name in client configuration**

**Cause:** Client configuration doesn't contain proper server name

**Action:** Specify a server name in client configuration

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-39504: Duplicate server name in client configuration**

**Cause:** Client configuration contain duplicate names {0}

**Action:** Specify a correct server name in client configuration

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-39505: Client configuration error**

**Cause:** Client configuration error for server {0}

**Action:** Review server information in client configuration

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-39506: Requested client type isn't supported**

**Cause:** Requested client type for server {0} isn't supported

**Action:** Specify a correct client type for server {0} in client configuration

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-39507: No connection to servers**

**Cause:** Either client aren't configured, or there is an issue with the existing client configuration.

**Action:** Verify that at least one client connection is configured for this application, and that no unresolved "ConfigurationExceptions" exceptions are logged.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-39508: More items not currently available**

**Cause:** Data are not available from some servers

**Action:** Check failed servers and client configuration

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**BPM-39509: Information not currently available**

**Cause:** Information not currently available for all servers

**Action:** Check failed servers and client configuration

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-39510: Server has more data**

**Cause:** Only the first {0} tasks display for this server

**Action:** Specify a correct client type in client configuration

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-39511: Several servers have more data**

**Cause:** Only the first {0} tasks display for these servers

**Action:** Specify a correct client type in client configuration

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-39512: No default server in client configuration**

**Cause:** Confuration needs to have one default server

**Action:** Specify a correct default server in client configuration

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-39513: Duplicate default server in client configuration**

**Cause:** Confuration needs to have only one default server in client configuration

**Action:** Specify one default server in client configuration

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-39514: Cannot find client configuration**

**Cause:** Cannot find client configuration for server {0}

**Action:** Specify correct server name which can found in client configuration

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-39515: Not defined client type**

---

**Cause:** Request does not specify client type

**Action:** Specify correct client type

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-39516: Encryption issue in client configuration file.**

**Cause:** Encryption failed in client configuration file.

**Action:** Please verify if the encryption algorithm {0} is supported. Also check if the key is valid and of correct length.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-39517: Decryption issue in client configuration file.**

**Cause:** Decryption failed in client configuration file.

**Action:** Please verify if the decryption algorithm {0} is supported. Also check if the key is valid and of correct length.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-40001: Calendar not defined**

**Cause:** The calendar with id {0} is not defined

**Action:** Specify an existing calendar

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-40002: OrganizationalUnit not defined**

**Cause:** The OrganizationalUnit with id {0} is not defined

**Action:** Specify an existing OrganizationalUnit

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-40003: Parent OrganizationalUnit not defined**

**Cause:** The Parent OrganizationalUnit with id {0} is not defined

**Action:** Specify an existing OrganizationalUnit as a parent OrganizationalUnit

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-40004: OrganizationalUnit name not specified**

---

**Cause:** The OrganizationalUnit name for the OrganizationalUnit with id {0} is not specified

**Action:** Specify the OrganizationalUnit name

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-40005: OrganizationalUnit Id not specified**

**Cause:** The Id for OrganizationalUnit is not specified

**Action:** Specify the OrganizationalUnit Id

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-40006: Id for the association between ApplicationRole, OrganizationalUnit, and CalendarRule not specified**

**Cause:** Id for the association between ApplicationRole, OrganizationalUnit, and CalendarRule not specified

**Action:** Specify the association Id

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-40007: CalendarRule for the association between ApplicationRole, OrganizationalUnit, and CalendarRule not specified**

**Cause:** The CalendarRule Id for the association between ApplicationRole, OrganizationalUnit, and CalendarRule not specified

**Action:** Specify the CalendarRule Id

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-40008: OrganizationalUnit for the association between ApplicationRole, OrganizationalUnit, and CalendarRule not specified**

**Cause:** The OrganizationalUnit Id for the association between ApplicationRole, OrganizationalUnit, and CalendarRule not specified

**Action:** Specify the OrganizationalUnit Id

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-40009: Association between ApplicationRole, OrganizationalUnit, and CalendarRule is not defined**

**Cause:** The association between ApplicationRole, OrganizationalUnit, and CalendarRule with Id {0} is not defined

---

**Action:** Specify an existing association between ApplicationRole, OrganizationalUnit, and CalendarRule

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-40010: OrganizationalUnit with Id {0} exists**

**Cause:** The OrganizationalUnit with the specified Id exists

**Action:** Specify a unique Id for the OrganizationalUnit

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**BPM-40011: Association between ApplicationRole, OrganizationalUnit, and CalendarRule with Id {0} exists**

**Cause:** The association between ApplicationRole, OrganizationalUnit, and CalendarRule with the specified Id exists

**Action:** Specify a unique Id for the association between ApplicationRole, OrganizationalUnit, and CalendarRule

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic



---

---

## BRW-15000 to BRW-16976

**BRW-15000: Internal error in Query Builder error handler**

**Cause:** Error handler could not be started.

**Action:** Contact support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15001: {1}**

**Cause:** Message not found

**Action:** Check Query Builder directory in Oracle Home for message file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15002: Out of memory!**

**Cause:** Out of memory.

**Action:** Save documents and restart Query Builder.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15003: Invalid file name: {1}**

**Cause:** User entered an invalid file name (for example, too many characters).

**Action:** Enter a new, valid file name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15004: Internal error ({1}:{2})**

**Cause:** Internal Error Occurred -- Query Builder is in an unreliable state.

**Action:** Contact support.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**BRW-15005: No file name specified**

**Cause:** User did not enter a filename in the Export Data Dialog.

**Action:** Enter a filename.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15006: Unable to DESCRIBE data table**

**Cause:** Internal message.

**Action:** Contact support.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BRW-15007: SQL statement is too complex to display.**

**Cause:** Exceeded the edit buffer size on MSWINDOWS.

**Action:** Exclude some columns from the query to reduce the SQL statement size.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15009: Insufficient privileges to login through Query Builder**

**Cause:** Connect privileges are disabled in the SYSTEM.BROWSER\_PROFILE table.

**Action:** Contact your DBA.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15010: Insufficient privileges to edit schema through Query Builder**

**Cause:** Schema Editing privileges are not enabled in the SYSTEM.BROWSER\_PROFILE table.

**Action:** Contact your DBA.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15011: Insufficient privileges to edit data through Query Builder**

**Cause:** Data Editing privileges are not enabled in the SYSTEM.BROWSER\_PROFILE table.

**Action:** Contact your DBA.

**Level:** 1

---

**Type:** ERROR

**Impact:** Data

**BRW-15012: Cannot edit schema with DICTIONARY=ENDUSER command-line option**

**Cause:** Query Builder cannot invoke the Schema Builder when DICTIONARY=ENDUSER.

**Action:** Run Query Builder with the DICTIONARY=NATIVE command line option.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15013: Insufficient privileges to edit End User Layer through Query Builder**

**Cause:** Meta-data Editing privileges are not enabled in the SYSTEM.BROWSER\_PROFILE table.

**Action:** Contact your DBA.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15025: Unable to load list of database roles**

**Cause:** Schema internal error in loading list of database roles.

**Action:** Contact support if this is not expected.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15065: Syntax error**

**Cause:** User typed a formula incorrectly.

**Action:** Re-type the expression.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15066: Expression is too complex**

**Cause:** Expression is too complex.

**Action:** Simplify the expression.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15068: Invalid function: {1}**

**Cause:** User entered an invalid function name.

**Action:** Specify a valid function.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15069: Invalid column: {1}**

**Cause:** User entered an invalid column name.

**Action:** Enter a valid column name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15070: Invalid table: {1}**

**Cause:** User entered an invalid table name.

**Action:** Enter a valid table name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15071: Invalid owner: {1}**

**Cause:** User entered an invalid user or business area name.

**Action:** Enter a valid user or business area name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15072: Invalid condition**

**Cause:** User entered an invalid condition.

**Action:** Delete the condition and enter a valid condition.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15073: Invalid expression**

**Cause:** User entered an invalid expression (usually blank).

**Action:** Enter a valid expression.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15074: Invalid use of reserved word {1}**

**Cause:** User used a reserved word as an identifier.

**Action:** Identifiers cannot be reserved words. Refer to the help or documentation for details.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**BRW-15075: Invalid number of arguments to function {1}**

**Cause:** User entered too few or too many arguments for the given function.

**Action:** Enter the appropriate arguments. Refer to the help or documentation for details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15077: Ambiguous name: {1}**

**Cause:** User entered an ambiguous column name.

**Action:** Enter a specific column name, include any qualifiers.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15078: Redefinition of name: {1}**

**Cause:** User redefined a column or data table using a name that already exists.

**Action:** Define the column or table using a new name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15079: No columns selected in query**

**Cause:** Query was either built or entered with no displayed columns.

**Action:** Select columns before re-executing the query.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15080: No tables specified in query**

**Cause:** User entered a query without specifying any tables.

**Action:** Select tables before re-executing the query.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15081: START WITH requires CONNECT BY**

**Cause:** SQL statement contained a START WITH clause without a CONNECT BY clause.

**Action:** Specify a CONNECT BY clause if using START WITH.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**BRW-15082: PRIOR requires CONNECT BY**

**Cause:** SQL statement contained a PRIOR clause without a CONNECT BY clause.

**Action:** Specify a CONNECT BY clause if using PRIOR.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15083: Bad argument type to function {1}**

**Cause:** User entered the wrong argument type for the function.

**Action:** Enter the correct argument type.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15084: Unterminated comment**

**Cause:** Buffer being read in has an unterminated C-type comment in it.

**Action:** Edit the file (see that it terminates correctly), and reopen from Query Builder.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15085: Circular reference detected in defined column**

**Cause:** Modification of a defined column has led to a circular reference.

**Action:** Redefine the column so that it does not refer to itself in its own definition.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15086: Arguments to a correlated subquery function must be columns**

**Cause:** A complex argument was given, such as avg (sal, deptno\*2).

**Action:** Specify only valid columns, not expressions, in the subquery.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15087: Invalid location: {1}**

**Cause:** User entered an invalid database location for a table.

**Action:** Enter a valid database location.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**BRW-15088: Ambiguous table: {1}**

**Cause:** User entered an ambiguous data table name (more than one table uses this name).

**Action:** User must further qualify the data table. Refer to the help or

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15089: Only one PRIOR operator allowed on an expression**

**Cause:** User typed 2 or more PRIOR clauses in an expression.

**Action:** Remove one of the PRIOR clauses.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15090: The name {1} is already in use**

**Cause:** User entered a name that was already being used.

**Action:** Enter a new name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15091: Invalid name: {1}**

**Cause:** User entered an invalid name (with spaces or unprintable chars).

**Action:** Enter a new name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15092: Bad usage of outer relationship**

**Cause:** User specified an outer relationship on a non-column element.

**Action:** Outer relationships are only valid for columns.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15093: Invalid number of elements in corresponding record**

**Cause:** User entered two records with different numbers of elements.

**Action:** Reenter the condition.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**BRW-15094: Group function is nested too deeply**

**Cause:** User entered a double(triple) aggregate condition(expression).

**Action:** Simplify aggregate condition/expression.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15096: Table name conflicts with {1}, renamed to {2}**

**Cause:** When opening a query, a table alias name conflicts with a new column.

**Action:** ---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15097: Name conflicts with {1}, renamed to {2}**

**Cause:** When loading a saved query, an alias name conflicts with a new column.

**Action:** ---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15098: Duplicate table {1} in FROM clause**

**Cause:** Data table appears more than once in FROM clause (without an alias).

**Action:** Remove the duplicate data tables in the FROM clause.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15099: Subquery returns incorrect number of values**

**Cause:** Subquery returns either too many or too few values.

**Action:** Reenter condition.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15100: Correlated expressions are not allowed here**

**Cause:** User entered a correlated expression outside a condition.

**Action:** Reenter the condition/expression.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15101: Table alias cannot be reused in the same FROM clause: {1}**

**Cause:** User tried to use an alias in the same FROM clause it was defined in.



---

**Action:** Remove the reference to the alias.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15102: Too many elements in record**

**Cause:** User entered a record with more than 254 elements.

**Action:** Reduce the number of elements--split the condition into an OR.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15103: Unnamed SELECT statement in FROM clause**

**Cause:** SQL contained a query in the FROM clause without name.

**Action:** Add the query name and repars.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15110: Invalid number or precision exceeded: {1}**

**Cause:** Non-numeric input or the number exceeded this column's precision.

**Action:** Re-enter a valid number and precision.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15111: Invalid date: {1}**

**Cause:** Could not format using the columns format mask or either default mask.

**Action:** Re-enter a valid format mask.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15112: Entry exceeds the size limit for this column: {1}**

**Cause:** User entered a string longer than the limit for this column.

**Action:** Enter a shorter string.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15113: Not all parameters have been specified**

**Cause:** User attempted to execute a query without defining all parameters

**Action:** Specify parameters or exclude parameterized expressions and retry.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15114: Parameters can only be constant expressions**

**Cause:** User attempted to enter a parameter value that depended on a column value.

**Action:** Specify a valid parameter, one that does not depend on the value in a column.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15115: Bad usage of parameter {1}**

**Cause:** User entered a parameter name for a column or table.

**Action:** Specify a valid parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15116: Invalid parameter name {1}**

**Cause:** User entered an invalid parameter name.

**Action:** Specify a valid parameter name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15117: Invalid parameter {1}**

**Cause:** User entered an invalid parameter.

**Action:** Specify valid parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15128: Parser internal error: {1}**

**Cause:** Internal error in the parser/scanner.

**Action:** Contact support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15129: Defined column {1} cannot be used in correlated subquery function**

**Cause:** Use of derived columns (DQ4) in correlated subquery.

**Action:** Remove that argument from the correlated subquery.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15130: Query execution failed**

**Cause:** Database access error.

**Action:** Check database error and rerun query.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15131: Invalid relational operator**

**Cause:** User applied an invalid operator to a condition.

**Action:** Enter a valid operator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15132: FROM clause was not found where expected**

**Cause:** Encountered no FROM clause or GROUP/HAVING clause before a FROM clause.

**Action:** Edit SQL statement.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15133: FROM clause was found without corresponding SELECT clause**

**Cause:** Encountered FROM clause before SELECT clause.

**Action:** Edit SQL statement.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15135: Condition cannot be changed**

**Cause:** user attempted to change the top condition in Schema Builder.

**Action:** Perform the operation on the children conditions.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15136: SQL contains set operators**

**Cause:** Set operations are not supported.

**Action:** Run the query in SQLPlus.

**Level:** 1

---

Type: ERROR

Impact: Other

**BRW-15137: Unable to generate names for complex expressions**

Cause: Encountered expressions without names when opening a SQL file.

Action: Define Names for columns in the .sql file.

Level: 1

Type: ERROR

Impact: Other

**BRW-15138: CONNECT BY clause existed, and was ignored**

Cause: Connect By is not supported at this (top) level.

Action: Run the query in SQLPlus, if results of CONNECT BY were desired.

Level: 1

Type: ERROR

Impact: Other

**BRW-15139: Cannot ungroup condition**

Cause: Attempt to ungroup top condition.

Action: This operation is not supported.

Level: 1

Type: ERROR

Impact: Other

**BRW-15141: Query table cannot contain parameters**

Cause: Encountered one or more parameters when creating a view.

Action: Exclude parameters from query or ignore.

Level: 1

Type: ERROR

Impact: Other

**BRW-15142: Two or more columns have the same name: {1}**

Cause: Encountered duplicate column names when creating view.

Action: Use the Define command to rename duplicate columns.

Level: 1

Type: ERROR

Impact: Other

**BRW-15143: {1} is already a display column**

Cause: User tried to specify a duplicate display column.

Action: If duplicate column is desired, define a new name for it and re-display it.

Level: 1

Type: ERROR

Impact: Other

---

**BRW-15144: {1} is already a sort column**

**Cause:** User tried to specify a duplicate sort column.

**Action:** If duplicate column is desired, define a new name for it and re-sort.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15145: {1} is already a group column**

**Cause:** user tried to specify a duplicate group column.

**Action:** If duplicate column is desired, define a new name for it and re-group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15146: Internal error in opening query**

**Cause:** Internal error in opening query.

**Action:** Contact support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15147: Internal error in saving query**

**Cause:** Internal error in saving query.

**Action:** Contact support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15148: Relationship must be between compatible data types/size**

**Cause:** User tried to relate two columns with incompatible data types.

**Action:** Relate only compatible datatypes. Refer to the help or documentation for details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BRW-15150: Cannot define a self-relationship**

**Cause:** User tried to define a relationship within a data table.

**Action:** Alias the data table and then define the relationship.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15151: User-defined relationship already exists**

---

**Cause:** User tried to define a relationship that already exists.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15152: Illegal column in defined relationship**

**Cause:** User specified an illegal expression when defining a relationship.

**Action:** Retype in a new column.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15153: Table alias name cannot end with \_A<number>**

**Cause:** Illegal alias name.

**Action:** Input a new name that does not end with \_A<number>.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15154: Cannot remove database relationship**

**Cause:** User tried to remove data dictionary relationship.

**Action:** Only user-defined relationships can be deleted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15155: The following documents may have been affected:{1}**

**Cause:** A saved query was being used as a data table in other query documents.

**Action:** If you change or delete this query, you will affect these other queries.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15156: Cannot include table with the same name as the query**

**Cause:** User attempted to include data table D in query document D.

**Action:** Rename the query before including this table.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15157: Cannot sort, group, or break on LONG columns**

**Cause:** Trying to sort, group or break on LONG column type.

**Action:** Cancel the operation. Oracle does not support this.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15158: Cannot sort, group, or break on RAW columns**

**Cause:** Trying to sort, group or break on RAW column type.

**Action:** Cancel the operation. Oracle does not support this.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15159: Cannot display LONG columns from remote databases**

**Cause:** Trying to include LONG column type from remote database data table.

**Action:** Cancel the operation. Oracle does not support this.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15160: Maximum number ({1}) of columns exceeded**

**Cause:** User exceeded maximum number of display/group/sort columns supported.

**Action:** Delete some unwanted columns, then re-include what you need.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15161: Error in opening {1} display column(s)**

**Cause:** Unable to open DISPLAY column because database has changed since save.

**Action:** This column may have changed or no longer exist in the database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15162: Error in opening {1} sort column(s)**

**Cause:** Unable to open SORT column because database has changed since save.

**Action:** This column may have changed or no longer exist in the database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15163: Error in opening {1} group column(s)**

**Cause:** Unable to open GROUP column because database has changed since save.

**Action:** This column may have changed or no longer exist in the database.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15164: Error in opening {1} break column(s)**

**Cause:** Unable to open BREAK column because database has changed since save.

**Action:** This column may have changed or no longer exist in the database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15165: Maximum number ({1}) of break columns exceeded**

**Cause:** User exceeded the maximum number of break columns supported.

**Action:** Delete some unwanted break columns, then re-include what you need.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15166: Error in opening {1} condition(s)**

**Cause:** Unable to open conditions because database has changed since save.

**Action:** Tables or columns used in this condition may no longer exist in the database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15167: Alias must be {1} bytes or less: {2}**

**Cause:** alias name too long.

**Action:** Try typing in an alias less than or equal to 30 bytes long.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15168: Cannot group on aggregate expression**

**Cause:** Tried to group on an aggregate expression.

**Action:** Group on another expression.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15169: {1} has already been included as a break column**

**Cause:** User tried to specify a duplicate break column.

**Action:** If duplicate column is desired, define a new name for it and re-break.

**Level:** 1



---

**Type:** ERROR

**Impact:** Other

**BRW-15170: Invalid Constraint for table {1}**

**Cause:** User entered an invalid constraint for the selected table.

**Action:** Reenter constraint.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15171: Invalid Constraint for table column {1}**

**Cause:** User entered an invalid constraint for the selected column.

**Action:** Reenter constraint.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15172: Subqueries are not allowed in Constraints**

**Cause:** User entered an invalid constraint.

**Action:** Reenter constraint.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15173: Aggregate conditions are not allowed in Constraints**

**Cause:** User entered an invalid constraint.

**Action:** Reenter constraint.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15174: Constraints can only be on one table**

**Cause:** User entered an invalid constraint.

**Action:** Reenter constraint.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15175: Table not loaded because all columns are hidden**

**Cause:** All columns are hidden. At least one column needs to be displayed.

**Action:** Use the Browser Administrator Utility to display hidden columns.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**BRW-15188: Query returns 1 row**

**Cause:** Status message for 1-row Query Count.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15189: Query returns {1} rows**

**Cause:** Status message for n-row Query Count.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15190: Unable to count without executing; Query returns <= {1} row(s)**

**Cause:** Status message for n-row Query Count Distinct.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15192: Illegal format '{1}' for column '{2}'**

**Cause:** User typed an unrecognizable format for a display column.

**Action:** Try another format.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15193: Illegal format**

**Cause:** User typed an unrecognizable format for a display column

**Action:** Try another format.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15195: Incompatible column type in relationship: {1}**

**Cause:** Trying to create illegal relationship.

**Action:** Column types are incompatible. Refer to the help or documentation for details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15196: Error in opening {1} table(s)**

---

**Cause:** Unable to open data tables because database was modified or object does not exist.

**Action:** Check your connect string (or contact your DBA).

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15197: Error in restoring position for {1} column(s)**

**Cause:** Unable to reposition column because database was modified or object does not exist.

**Action:** Check your connect string (or contact your DBA).

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15198: Error in restoring join: {1}**

**Cause:** Unable to restore link during open because database was modified or object does not exist.

**Action:** Check your connect string (or contact your DBA).

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15199: Error in restoring inclusion state for join: {1}**

**Cause:** Unable to set the inclusion state during open because database was modified or object does not exist.

**Action:** Check your connect string (or contact your DBA).

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15200: Error in restoring outer join state for join: {1}**

**Cause:** Unable to set the outer join during open because database was modified or object does not exist.

**Action:** Check your connect string (or contact your DBA).

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15258: Invalid document name: {1}**

**Cause:** User entered an invalid document name.

**Action:** Enter a valid document name.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**BRW-15259: Document exceeds 64K size limit**

**Cause:** User attempted to save/open a document larger than 64K.

**Action:** Reduce size of document.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15260: Document {1} does not exist**

**Cause:** User specified a nonexistent document.

**Action:** Specify another document.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15261: Document {1} already exists**

**Cause:** User tried to save under the name of an existing document.

**Action:** Specify another document name or delete the existing document.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15262: Multiple documents named {1}**

**Cause:** Multiple documents with same name exist.

**Action:** Delete all but one.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15263: Database object {1} already exists**

**Cause:** User tried to save under the name of an existing object.

**Action:** Specify another document name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15264: Table {1} does not exist**

**Cause:** Data Table view corresponding to a saved document has been removed.

**Action:** Re-save the document (it no longer exists as a query view).

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15265: Table {1} has been removed or modified**

---

**Cause:** Data Table view corresponding to a saved document has been modified.

**Action:** Re-save the document.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15266: File {1} does not exist**

**Cause:** User specified a nonexistent file.

**Action:** Specify another file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15267: File {1} already exists**

**Cause:** User tried to save under the name of an existing file.

**Action:** Specify another file name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15268: Unable to open file {1}**

**Cause:** I/O core was unable to open a file.

**Action:** Specify another file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15269: Unable to lock file {1}**

**Cause:** I/O core was unable to lock a file.

**Action:** Specify another file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15270: Error reading file {1}**

**Cause:** Operating system error or file was not of the correct format.

**Action:** Specify another file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15271: Error writing file {1}**

**Cause:** Operating system error or I/O core error.

**Action:** Retry operation.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15272: Obsolete Query Builder document {1}**

**Cause:** User attempted to open an old unsupported document.

**Action:** Specify another document.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15273: File {1} is not a Query Builder file**

**Cause:** User attempted to open a non-Browser file.

**Action:** Specify another file to open.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15274: File {1} is not a valid SQL file**

**Cause:** User attempted to import an invalid SQL file.

**Action:** Specify another file to import.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15275: No data to export or print**

**Cause:** User attempted to export or print a query (or region) with no data.

**Action:** Specify another region; execute query; change query.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BRW-15277: Unable to overwrite current table {1}**

**Cause:** Error in trying to delete/rename old data table in save.

**Action:** Fix problem with data table and re-save.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15278: Document saved, but view {1} could not be created**

**Cause:** The query is not a valid view. It has been saved, but not as a database view.

**Action:** Redefine query as a valid view, or ignore (query will be saved, but not as a view).

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15279: '{1}' is not a recognized SQL literal**

**Cause:** User attempted to import a non-SQLPlus file.

**Action:** Specify another file to import.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15320: Internal I/O core error ({1}, line {2})**

**Cause:** Internal State is invalid.

**Action:** Contact support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15321: Resource not found ({1}).**

**Cause:** Resource names do not match Browser code (or file is corrupted).

**Action:** Get a correct version of the Browser resource file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15322: Resource file not found.**

**Cause:** directory structure incorrect, or file is missing for some reason.

**Action:** Locate the resource file (check NLS\_LANG file name).

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15323: Query already open in current application ({1})**

**Cause:** User attempted to open multiple queries with the same name.

**Action:** Specify another file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15324: Unable to start up windowing system**

**Cause:** Incorrect/missing environment variables (for example, DISPLAY, APIPATH).

**Action:** All required environment variables must be set correctly.

**Level:** 1

---

Type: ERROR

Impact: Other

**BRW-15337: Maximum columns in index is {1}**

Cause: Maximum columns in index reached.

Action: Create/modify index with less columns.

Level: 1

Type: ERROR

Impact: Other

**BRW-15338: Cannot remove/modify index used to enforce unique/primary key**

Cause: User tried to remove/modify the index used to enforce unique/primary key.

Action: First remove/modify primary key or unique key.

Level: 1

Type: ERROR

Impact: Other

**BRW-15339: Cannot create, modify, or remove index on synonyms**

Cause: User tried to create, modify, or remove the index for a synonym

Action: Create, modify, or remove index from base table instead.

Level: 1

Type: ERROR

Impact: Other

**BRW-15340: Cannot modify constraints for a synonym.**

Cause: Modifying constraints of a synonym is not allowed.

Action: Modify constraint of base data table instead.

Level: 1

Type: ERROR

Impact: Other

**BRW-15341: Base table can only be modified after committing duplicated table**

Cause: User tried to modify a base data table that has been duplicated.

Action: Commit the duplicated table first.

Level: 1

Type: ERROR

Impact: Other

**BRW-15342: Unable to find snapshot information**

Cause: This database does not support snapshots (or database error).

Action: Check that you have a snapshot dictionary table.

Level: 1

Type: ERROR



---

**Impact:** Other

**BRW-15343: Insufficient privileges to use DICTIONARY=NATIVE**

**Cause:** You do not have access privileges to use the NATIVE dictionary.

**Action:** Use DICTIONARY=ENDUSER instead. This can be specified on the command line.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15344: Insufficient privileges to use DICTIONARY=ENDUSER**

**Cause:** You do not have access privileges to use the ENDUSER dictionary

**Action:** Use DICTIONARY=NATIVE instead. This can be specified on the command line.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15345: Cannot load MVIEW\$\_ or SNAP\$\_ tables. Load snapshot instead.**

**Cause:** Trying to import sql which uses MVIEW\$\_ or SNAP\$\_ of snapshot.

**Action:** Load the snapshot itself instead.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15346: Cannot REVOKE privileges you did not grant**

**Cause:** User trying to revoke privileges that he/she did not grant.

**Action:** The user who grants the privileges should revoke those privileges.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15347: Cannot grant EXECUTE privilege on tables**

**Cause:** Trying to grant EXECUTE privilege on tables.

**Action:** EXECUTE privilege is only allowed on packages.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15348: ALTER, INDEX, REFERENCES, or EXECUTE privileges not allowed on views**

**Cause:** Trying to grant ALTER, INDEX, REFERENCES, or EXECUTE on views.

**Action:** This is not allowed.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**BRW-15349: Only SELECT privilege is allowed on snapshots**

**Cause:** SELECT privilege is only allowed for snapshots.

**Action:** Grant only SELECT privilege on snapshots.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15350: No privileges is allowed for synonyms**

**Cause:** Trying to grant privileges on synonyms.

**Action:** This is not allowed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15351: Insufficient privileges. Operation denied.**

**Cause:** User try to perform an operation without sufficient privileges.

**Action:** Try again after obtaining proper privileges from your DBA.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15352: Cannot remove existing table columns**

**Cause:** Trying to remove an existing table column.

**Action:** This operation is not supported by the database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15354: Cannot rename existing table columns**

**Cause:** Trying to rename an existing data table column.

**Action:** This action is not supported by the database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15355: Cannot change indexed column datatype to LONG**

**Cause:** Trying to change an indexed column type to a LONG datatype.

**Action:** This action is not supported by the database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15356: Removed tables cause referenced synonyms to be removed**

---

**Cause:** User removed some data tables that have synonyms refer to them.  
**Action:** None. This is a warning that synonyms are removed automatically.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15357: Error in removing constraint {1}**

**Cause:** Error in removing constraint.

**Action:** Try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15358: Error in enabling/disabling constraints for {1}**

**Cause:** Error in enabling/disabling constraints.

**Action:** Try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15359: Cannot disable a key referred by a newly created FOREIGN key**

**Cause:** Trying to disable a primary or unique key that a foreign key depends upon.

**Action:** Commit the foreign key first, then disable.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15360: Foreign key refers to disabled PRIMARY/UNIQUE key {1}**

**Cause:** Foreign key refers to a disabled primary key.

**Action:** Enable primary key for the foreign key to be created successfully.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15361: Error in creating PRIMARY/UNIQUE constraints for {1}**

**Cause:** Error in creating PRIMARY/UNIQUE constraints.

**Action:** Try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15362: Error in creating FOREIGN constraints for {1}**

**Cause:** Error in creating FOREIGN constraints.

---

**Action:** Try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15363: Error in creating CHECK constraints for {1}**

**Cause:** Error in creating CHECK constraints.

**Action:** Try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15364: Length of VARCHAR2 column must be between {1} and {2}**

**Cause:** Illegal range for length of VARCHAR2 column.

**Action:** Specify a legal length parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15365: Non-unique INDEX column cannot have PRIMARY/UNIQUE constraint**

**Cause:** User tried to create PRIMARY/UNIQUE constraints on a non-unique index.

**Action:** Remove the index, and recreate as a unique index.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15366: PRIMARY/UNIQUE column cannot have non-unique index**

**Cause:** Trying to create a non-unique index with PRIMARY/UNIQUE columns.

**Action:** Set the index to UNIQUE. Remove and recreate.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15367: Cannot rename snapshots**

**Cause:** User tried to rename a snapshot

**Action:** This is not allowed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15368: Error in altering snapshot {1}**

**Cause:** Internal error.

---

**Action:** Try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15369: Error in creating snapshot {1}**

**Cause:** Internal error.

**Action:** Try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15370: Cannot add columns to a table duplicated with data**

**Cause:** Trying to add columns to an uncommitted data table (duplicated with data).

**Action:** Commit first, then add columns

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BRW-15371: Comment too long (max {1} bytes)**

**Cause:** The comment specified for the data table or column is too long.

**Action:** Shorten the comment.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15372: Cannot set comment for synonym**

**Cause:** User tried to create a comment for a synonym.

**Action:** Create the comment on the table or view instead.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15373: Cannot create primary, unique, foreign key, or index on LONG columns**

**Cause:** These operations cannot be performed on LONG columns.

**Action:** Do not attempt to perform this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15374: Cannot remove tables that are referenced**

**Cause:** User tried to remove a table with primary or unique keys that are referenced.

---

**Action:** Remove referencing table first.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15375: Cannot create index through database link**

**Cause:** User tried to create an index through a database link.

**Action:** Login directly then create index.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15376: Cannot create constraint through database link**

**Cause:** User tried to create a constraint through a database link.

**Action:** Login directly then create constraint.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15377: Create or remove constraint is only for table**

**Cause:** User tried to create or remove a constraint on non-table database object.

**Action:** This action is not supported.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15378: Table already removed. Create/remove on constraint ignored**

**Cause:** User tried to create or remove a constraint on an already removed table.

**Action:** Revert table before further modifying it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15379: Primary or unique already exists**

**Cause:** Duplicate primary or unique key.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15380: Foreign key must reference primary or unique key**

**Cause:** The specified foreign key does not reference a primary or unique key.

**Action:** Make sure the foreign key references a primary or unique key.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15381: Number of columns mismatch between foreign and primary/unique key**

**Cause:** The foreign key does not match the number of columns in the primary or unique key.

**Action:** Make sure the number of columns are the same.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15382: Foreign key already exists**

**Cause:** Foreign key already exists.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15383: A table can only have one primary key**

**Cause:** User tried to specify more than one primary key per table.

**Action:** Remove the old primary key and recreate it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15384: Cannot remove or modify a keys referenced by foreign keys**

**Cause:** Primary or unique key is referenced by foreign keys.

**Action:** Remove foreign keys first then remove primary / unique keys.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15385: Cannot duplicate view from PUBLIC database link as a view**

**Cause:** Unable to read SQL statement (LONG column) from PUBLIC database link.

**Action:** This action is not supported.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15386: Circular reference detected in synonym {1}**

**Cause:** The synonym has a circular reference in the data dictionary.

**Action:** Do not include the particular synonym.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15387: Login failed**

**Cause:** Database or SQLNet error occurred.

**Action:** Check the login information and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15388: Unable to load database relationships**

**Cause:** Schema internal error in loading database relationships.

**Action:** Contact support if this is not expected.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15389: Unable to load list of accessible owners**

**Cause:** Schema internal error in loading list of accessible owners.

**Action:** Contact support if this is not expected.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15390: Unable to load list of accessible tables**

**Cause:** Schema internal error in loading list of data tables.

**Action:** Contact support if this is not expected.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15391: Unable to load table**

**Cause:** Schema internal error in loading data table.

**Action:** Contact support if this is not expected.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15392: Unable to load table**

**Cause:** Schema internal error in loading table.

**Action:** Contact support if this is not expected.

**Level:** 1

**Type:** ERROR



---

**Impact:** Other

**BRW-15393: Unable to load synonym**

**Cause:** Schema internal error in loading synonym.

**Action:** Contact support if this is not expected.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15394: Unable to load query**

**Cause:** Schema internal error in loading query.

**Action:** Contact support if this is not expected.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15395: Unable to load table column information**

**Cause:** Schema internal error in loading column information.

**Action:** Contact support if this is not expected.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15396: Unable to load synonym column information**

**Cause:** Schema internal error in loading synonym column information.

**Action:** Contact support if this is not expected.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15397: Unable to load constraints**

**Cause:** Schema internal error in loading constraints.

**Action:** Contact support if this is not expected.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15398: Unable to find primary key information**

**Cause:** Schema internal error in finding primary keys.

**Action:** Contact support if this is not expected.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15399: Unable to find foreign key information**

---

**Cause:** Schema internal error in finding foreign keys.

**Action:** Contact support if this is not expected.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15400: Unable to load table and column comments**

**Cause:** Schema internal error in getting comments.

**Action:** Contact support if this is not expected.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15401: Error in loading database link {1}**

**Cause:** Schema internal error in loading database link.

**Action:** Refer to accompanying error messages for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15402: Error in loading owner {1}**

**Cause:** Schema internal error in loading database link.

**Action:** Refer to accompanying error messages for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15403: Error in loading table {1}**

**Cause:** Schema internal error in loading data table.

**Action:** Refer to accompanying error messages for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15404: Error in loading primary key constraint for {1} ({2})**

**Cause:** Schema internal error in loading primary constraint.

**Action:** Refer to accompanying error messages for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15405: Error in loading foreign key constraint {1}**

**Cause:** Schema internal error in loading foreign constraint.

**Action:** Refer to accompanying error messages for more information.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15406: Error in loading synonym {1}**

**Cause:** Schema internal error in loading primary constraint.

**Action:** Refer to accompanying error messages for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15407: Table referred to by synonym {1} no longer exists**

**Cause:** User tried to create a synonym for a nonexistent data table.

**Action:** Recreate the synonym.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15408: Error in loading column information for {1}**

**Cause:** Oracle error or the data table has been removed.

**Action:** Recreate the data table.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15409: Error in loading constraint information for {1} ({2})**

**Cause:** Oracle error.

**Action:** Try it again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15410: Table that foreign key {1} ({2}) refers to is inaccessible**

**Cause:** The table that the foreign key refers to is inaccessible.

**Action:** Grant the table to the current user.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15411: Logout failed**

**Cause:** Internal error in logging out.

**Action:** Exit or close the document.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**BRW-15412: Table of query {1} was modified. Query loaded as view.**

**Cause:** The view that the query depends on has been modified after the last save.

**Action:** Open the query and save it again to use it as a data table.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15413: Table of query {1} was removed. Query will not be loaded.**

**Cause:** The view that the query depends on has been removed.

**Action:** Open the query, and save it again to use it as a data table.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15414: Table {1} no longer exists**

**Cause:** This data table no longer exists in the database.

**Action:** Contact system administrator if you need this table.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15415: Maximum number (254) of table columns exceeded**

**Cause:** User tried to load a data table that has more than 254 columns.

**Action:** Contact system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15416: Maximum number (8192) of tables per user exceeded**

**Cause:** User owns too many data tables.

**Action:** Contact system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15417: Maximum number (1024) of owners and databases exceeded**

**Cause:** User tried to load too many user, owner, and database links.

**Action:** Contact system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15418: Unable to find database link information**

---

**Cause:** This database does not support database link, or database error.

**Action:** Try again later if this is unexpected.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15419: Unable to find synonym information**

**Cause:** This database does not support synonyms, or database error.

**Action:** Try again later if this is unexpected.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15420: Unable to find constraint information**

**Cause:** This database does not support constraints, or database error.

**Action:** Try again later if this is unexpected.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15421: Unable to find table comment table**

**Cause:** This database does not support comments on table, or database error.

**Action:** Try again later if this is unexpected.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15422: Unable to find table Column comments table**

**Cause:** This database does not support comments on column, or database error.

**Action:** Try again later if this is unexpected.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15423: Synonym to SEQUENCE is not currently supported**

**Cause:** User tried to load a synonym that refers to a sequence.

**Action:** This action is not supported.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15424: Maximum number of login attempts (3) exceeded**

**Cause:** User tried to login too many times.

---

**Action:** Contact system administrator for correct username, password, and connect strings.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15425: End User Layer dictionary not installed**

**Cause:** The End User Layer meta-data dictionary was not found.

**Action:** Install the End User Layer dictionary or run with DICTIONARY=NATIVE option.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15430: Index information not loaded**

**Cause:** Cannot find index table.

**Action:** This is a non-Oracle database; try an ODBC driver.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15433: Create snapshot with only {1} maximum columns.**

**Cause:** User tried to create more than the maximum number of allowed columns in a snapshot.

**Action:** Create fewer columns.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15434: Maximum columns in table is {1}**

**Cause:** User tried to create more than the maximum number of allowed columns in a table.

**Action:** Create fewer columns.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15435: DBA privilege is needed to perform this operation**

**Cause:** Need DBA privileges.

**Action:** Ask your system administrator to grant you DBA privilege.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15437: Index already exists**

---

**Cause:** User tried to create an index that is the same as an already existing index.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15438: Index must be on columns from the same table**

**Cause:** user tried to create an index on columns from different tables.

**Action:** Create the index on columns from the same table.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15439: Cannot create new tables through database links**

**Cause:** User tried to create data tables through database links.

**Action:** This operation is not allowed. Login directly then create.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15440: New columns cannot be created through database links**

**Cause:** User tried to create columns through database links.

**Action:** This operation is not allowed. Login directly and create.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15441: User has no CREATE INDEX privilege**

**Cause:** User tried to create an index on data table without proper privileges

**Action:** Obtain CREATE INDEX privilege on this data table.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15444: Adding columns is only supported for tables**

**Cause:** User tried to add columns to a view, snapshot, synonym, or query.

**Action:** This operation is not allowed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15445: Cannot remove columns of synonyms, duplicated views or snapshots**

**Cause:** User tried to remove columns from a view, snapshot, synonym, or query.

**Action:** This operation is not allowed.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15446: Unable to copy constraints for {1}**

**Cause:** Error duplicating constraints.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15447: Cannot remove Query. Use File Delete... from Query window**

**Cause:** User tried to remove a query.

**Action:** This is not legal from the Schema Builder. Use the Query window instead.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15448: Cannot copy Query. Use File Save As... from Query window**

**Cause:** User tried to copy a query.

**Action:** This is not legal from the Schema Builder. Use the Query window instead.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15449: Cannot copy with data from table with only LONG columns**

**Cause:** User tried to copy a table with a LONG column.

**Action:** Database does not support this.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BRW-15450: Operation not allowed on removed table**

**Cause:** User tried to do something to a removed data table.

**Action:** Undo the remove first.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15451: Operation not allowed on removed column**

**Cause:** User tried to do something to a removed column.

**Action:** Undo the remove first.

**Level:** 1

**Type:** ERROR



---

**Impact:** Other

**BRW-15452: Cannot rename another owner's table**

**Cause:** User tried to set the name of a granted data table.

**Action:** This is not allowed. Ask the owner to do it for you.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15453: Cannot rename table at database link**

**Cause:** User tried to set the name on a data table at a database link.

**Action:** Ask the owner to do this for you.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15454: Renaming columns is only supported on table and view columns**

**Cause:** User tried to set column name for a snapshot, synonym, or query.

**Action:** This is not allowed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15455: Setting column type is only supported on table columns**

**Cause:** User tried to set column type for a view, snapshot, synonym, or query.

**Action:** This is not allowed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15456: Cannot change column type of an existing column**

**Cause:** User tried to change column type of an existing column.

**Action:** This is not allowed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15457: Default values are allowed only on table columns**

**Cause:** User tried to set default for a synonym, snapshot, view, or query.

**Action:** This is not allowed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15458: Setting length is supported only on table columns**

---

**Cause:** User tried to set length for a synonym, snapshot, view, or query.

**Action:** This is not allowed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15459: Cannot set length for DATE, LONG, or ROWID datatypes**

**Cause:** User tried to set the length for DATE, LONG, or ROWID datatypes.

**Action:** This is not allowed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15460: Setting scale is allowed only on table columns**

**Cause:** User tried to set scale for synonym, snapshot, view, or query columns.

**Action:** This is not allowed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15461: Cannot set scale for DATE, LONG, or ROWID datatypes**

**Cause:** User tried to set scale for DATE, LONG, or ROWID columns.

**Action:** This is not allowed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15462: Setting precision is allowed only on table columns**

**Cause:** User tried to set precision for synonym, snapshot, view, or query columns.

**Action:** This is not allowed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15463: Setting precision is allowed only on NUMBER datatype**

**Cause:** User tried to set precision on columns other than NUMBER.

**Action:** This is not allowed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15464: Altering column position is allowed only on table columns**

**Cause:** User tried to set column position on non-table database objects.

**Action:** This is not allowed.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15465: Cannot change the position of existing column.**

**Cause:** User tried to change column position of existing table.

**Action:** This is not allowed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15466: Table name too long (Max {1} bytes)**

**Cause:** Data Table name too long.

**Action:** Shorten the name and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15467: Name already in use. Please choose another name.**

**Cause:** Name already in use.

**Action:** Choose another name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15468: Column name too long (Max {1} bytes)**

**Cause:** Column name too long.

**Action:** Shorten the name and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15469: Length of NUMBER column must be between {1} and {2}**

**Cause:** Illegal range for length of NUMBER column.

**Action:** Specify a legal length parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15470: Length of CHAR or RAW column must be between {1} and {2}**

**Cause:** Illegal range for length of CHAR column.

**Action:** Specify a legal length parameter.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**BRW-15471: Precision must be between {1} and {2}**

**Cause:** Illegal range for precision.

**Action:** Specify a legal length parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15472: Cannot decrease length of existing column**

**Cause:** User tried to decrease the length of an existing column.

**Action:** This is not allowed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15473: Cannot decrease scale of existing column**

**Cause:** User tried to decrease scale of an existing column.

**Action:** This is not allowed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15474: Cannot decrease precision of existing column**

**Cause:** User tried to decrease precision of an existing column.

**Action:** This is not allowed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15475: Table can have at most one LONG column**

**Cause:** User tried to create more than one LONG or RAW column per table.

**Action:** This is not allowed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15476: Error in loading index for {1}**

**Cause:** Internal error.

**Action:** Contact support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15477: Error in creating table {1}**

---

**Cause:** Internal error.  
**Action:** Contact support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15478: Error in creating view {1}**

**Cause:** Internal error.

**Action:** Contact support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15479: Error in creating synonym {1}**

**Cause:** Internal error.

**Action:** Contact support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15480: Error in creating index {1}**

**Cause:** Internal error.

**Action:** Contact support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15481: Error in dropping {1}**

**Cause:** Internal error.

**Action:** Contact support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15482: Error in dropping table {1}**

**Cause:** Internal error.

**Action:** Contact support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15483: Error in dropping view {1}**

**Cause:** Internal error.

**Action:** Contact support.

---

**Level:** 1  
**Type:** ERROR  
**Impact:** Other  
**BRW-15484: Error in dropping synonym {1}**  
**Cause:** Internal error.  
**Action:** Contact support.

**Level:** 1  
**Type:** ERROR  
**Impact:** Other  
**BRW-15485: Error in dropping index {1}**  
**Cause:** Internal error.  
**Action:** Contact support.

**Level:** 1  
**Type:** ERROR  
**Impact:** Other  
**BRW-15486: Error in renaming {1}**  
**Cause:** Internal error.  
**Action:** Contact support.

**Level:** 1  
**Type:** ERROR  
**Impact:** Other  
**BRW-15487: Error in setting comment for table {1}**  
**Cause:** Internal error.  
**Action:** Contact support.

**Level:** 1  
**Type:** ERROR  
**Impact:** Other  
**BRW-15488: Error in setting comment for column {1}**  
**Cause:** Internal error.  
**Action:** Contact support.

**Level:** 1  
**Type:** ERROR  
**Impact:** Other  
**BRW-15489: Error in loading index {1} for {2}**  
**Cause:** Internal error.  
**Action:** Contact support.

**Level:** 1  
**Type:** ERROR

---

**Impact:** Other

**BRW-15490: Error in loading table privilege for {1}**  
**Cause:** Internal error.  
**Action:** Contact support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15491: Error in loading column privilege for {1}**  
**Cause:** Internal error.  
**Action:** Contact support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15492: Error in altering table {1}**  
**Cause:** Internal error.  
**Action:** Contact support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15493: Operation currently not supported**  
**Cause:** Internal error.  
**Action:** Contact support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15494: Error in loading SQL text of views**  
**Cause:** Internal error.  
**Action:** Contact support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15495: Error in loading SQL text for view {1}**  
**Cause:** Internal error.  
**Action:** Contact support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15496: Scale must be between {1} and {2}**

---

**Cause:** Illegal value for scale.  
**Action:** Input legal value for scale.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15497: Index can only be created on TABLE columns**

**Cause:** User tried to create index on a database object other than a TABLE.

**Action:** Create index on TABLE columns only.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15498: Cannot modify a query**

**Cause:** It is not legal to modify a query.

**Action:** Open the query and modify it as a Browser document.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15499: Cannot set column attributes of table duplicated with data**

**Cause:** User tried to set the column type of a table duplicated with data.

**Action:** First commit the table then try again.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BRW-15500: {1}**

**Cause:** Oracle error

**Action:** None.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15501: No more application virtual memory**

**Cause:** No more disk space or system memory for Virtual Memory Manager.

**Action:** Close a document or make some room on your disk.

**Level:** 1

**Type:** ERROR

**Impact:** Memory

**BRW-15502: Can only have {1} rows per document**

**Cause:** Exceeded self-imposed, compile-time row maximum.

**Action:** Consider adding conditions to the query.



---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15504: Unable to determine database character set**

**Cause:** There was a problem with SELECT USERENV('LANGUAGE') FROM DUAL.

**Action:** Non-Oracle database--not supported.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15505: Unable to open virtual memory file**

**Cause:** No write permission or file system full.

**Action:** Change permission on directory or delete some files.

**Level:** 1

**Type:** ERROR

**Impact:** Memory

**BRW-15506: Unable to close virtual memory file**

**Cause:** Operating system error.

**Action:** Ask system administrator for assistance.

**Level:** 1

**Type:** ERROR

**Impact:** Memory

**BRW-15507: Unable to read from virtual memory file**

**Cause:** Virtual memory file does not exist.

**Action:** Make sure the virtual memory file is opened.

**Level:** 1

**Type:** ERROR

**Impact:** Memory

**BRW-15508: Unable to write to virtual memory file**

**Cause:** File system is full, or virtual memory file was not opened.

**Action:** Delete some files. Make sure virtual memory file is opened.

**Level:** 1

**Type:** ERROR

**Impact:** Memory

**BRW-15509: Unable to create virtual memory manager**

**Cause:** Internal error, or out of memory.

**Action:** Ask system administrator for assistance.

**Level:** 1

---

**Type:** ERROR

**Impact:** Memory

**BRW-15511: Maximum virtual memory size exceeded**

**Cause:** User input is too big for virtual memory size.

**Action:** Try again.

**Level:** 1

**Type:** ERROR

**Impact:** Memory

**BRW-15513: Null value in command '{1}'**

**Cause:** User entered &lt;command>= on the command line with no option selected.

**Action:** Add a value for &lt;command>.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15514: Null command in command line**

**Cause:** User entered =&lt;value> at command line but did not specify a command.

**Action:** Add the command.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15515: Unrecognized command '{1}' in command line**

**Cause:** User entered an illegal command at command line.

**Action:** Change command.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15516: Command '{1}' specified twice in command line**

**Cause:** User entered a command twice at command line.

**Action:** Remove one.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15517: Incompatible commands '{1}' and '{2}' specified**

**Cause:** User entered 2 incompatible commands at command line.

**Action:** Remove one.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**BRW-15518: Invalid option '{1}' in command '{2}'**

**Cause:** User entered an illegal option to a command at command line.

**Action:** Change option.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15519: Multiple login specifications in command line**

**Cause:** User entered 2 login specifications at command line.

**Action:** Remove one.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15520: Invalid document name '{1}' in command line**

**Cause:** User entered an illegal document name at command line.

**Action:** Change document name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15521: '{1}' command specified without a document**

**Cause:** User entered a command without specifying a document at command line.

**Action:** Add missing document.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15522: '{1}' command specified without '{2}'**

**Cause:** User entered a command without another required command.

**Action:** Add missing command.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15523: Mismatched parentheses in '{1}' command**

**Cause:** User entered mismatched parentheses in the command line.

**Action:** Correct mismatched parentheses.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**BRW-15530: Cannot edit a deleted row**

**Cause:** User tried to edit a row which is marked for deletion.

**Action:** Undelete the row first.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15531: Row has been deleted from the database**

**Cause:** Another user deleted this row since you last ran the query.

**Action:** Contact support. This should never happen.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15532: Row has been modified by another user. Requery.**

**Cause:** Another user updated this row since you last ran the query.

**Action:** Try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15533: Row is currently locked by another user.**

**Cause:** Someone else is editing this row.

**Action:** Try again later.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15539: Error in inserting {1} row(s)**

**Cause:** One or more rows in input file failed on insert.

**Action:** Modify input file or ignore.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15540: Operation not allowed on data of this type**

**Cause:** User tried to edit a cell with data of an uneditable type.

**Action:** Unknown.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BRW-15541: Too many edited rows. Please select Commit**

**Cause:** Too many pending INSERTS, UPDATES or DELETES in a document.

---

**Action:** Select Commit or Revert.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15545: Error in reading QXF file. Parsing halted.**

**Cause:** Syntax error in reading QXF file.

**Action:** Fix QXF file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15546: Parse Error: Line {1}**

**Cause:** Syntax at that particular line.

**Action:** Debug that line.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15547: Operator unspecified in relationship block.**

**Cause:** Operator unspecified in relationship block in QXF File.

**Action:** Specify an operator field within the block.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15548: Error: Argument missing in {1} of relationship block.**

**Cause:** No argument in a column field in a relationship block. No argument in the CONDITION\_TEXT field within condition block.

**Action:** Specify the column name in that field. Specify the CONDITION\_TEXT field.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15550: Illegal INCLUSION\_ORDER value ({1}) in expression {2}.**

**Cause:** Illegal INCLUSION\_ORDER value in expression.

**Action:** Correct INCLUSION\_ORDER value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15551: Expression {1} included but INCLUSION\_ORDER unspecified.**

**Cause:** The INCLUSION\_ORDER unspecified for an included expression block.

---

**Action:** Specify the INCLUSION\_ORDER field.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15552: Expression {1} not included but INCLUSION\_ORDER is non-null**

**Cause:** Expression is not included (INCLUDED = FALSE) but INCLUSION\_ORDER is non-null.

**Action:** Correct the values in these fields.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15553: Error: Empty TEXT string in expression {1}.**

**Cause:** The TEXT string is unspecified within a QXF expression block.

**Action:** Specify the TEXT string.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15554: Error: SORT\_PRIORITY unspecified for sorted expression {1}.**

**Cause:** SORT\_PRIORITY unspecified for sorted expression.

**Action:** Specify the SORT\_PRIORITY.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15555: Illegal INCLUSION\_ORDER value for field {1} in table {2}.**

**Cause:** Illegal INCLUSION\_ORDER value for field.

**Action:** Correct the INCLUSION\_ORDER value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15556: Field {1} in table {2} included but INCLUSION\_ORDER is null.**

**Cause:** Field is included (INCLUDED = FALSE) but INCLUSION\_ORDER is unspecified.

**Action:** Correct the values in these fields.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15557: Field {1} (table {2}) excluded but INCLUSION\_ORDER exists.**

**Cause:** The field in specified data table is not included but the INCLUSION\_ORDER is non-null.

---

**Action:** Correct the values in these fields.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15558: SORT\_PRIORITY unspecified for sorted field {1} in table {2}.**

**Cause:** SORT\_PRIORITY unspecified for a sorted field.

**Action:** Specify the SORT\_PRIORITY for that field.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15559: Error: Illegal value ({1}) for INCLUSION\_ORDER in table {2}.**

**Cause:** A negative value in inclusion order.

**Action:** Correct that value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15560: Table {1} included but INCLUSION\_ORDER unspecified.**

**Cause:** Data Table included (INCLUDED = TRUE) but INCLUSION\_ORDER is unspecified.

**Action:** Correct the values in these fields.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15561: Table {1} is excluded but INCLUSION\_ORDER is non-null.**

**Cause:** Data Table not included (INCLUDED = FALSE) but INCLUSION\_ORDER is non-null.

**Action:** Correct the values in these fields.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15562: Error: There should be no more than one main condition block.**

**Cause:** There are more than one main (root) condition blocks.

**Action:** Eliminate some condition blocks, or use a conjunction.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15563: Error: QXF file version 1.0 expected.**

**Cause:** Illegal version number specified in VERSION field.

---

**Action:** Modify the version.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15564: Parse Error: Line {1}: Invalid font style {2}.**

**Cause:** Invalid font style.

**Action:** Check font style and correct it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15565: Parse Error: Line {1}: Invalid font style argument.**

**Cause:** Invalid font style argument.

**Action:** Check font style strings and correct them.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15566: Parse Error: Line {1}: Invalid aggregate function {2}**

**Cause:** Invalid aggregate function name.

**Action:** Correct the function name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15567: Parse Error: Line {1}: Invalid summarize argument.**

**Cause:** Invalid summarize field argument.

**Action:** Correct the field argument.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15568: Parse Error: Line {1}: Invalid field argument.**

**Cause:** Invalid field argument.

**Action:** Correct field argument.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15569: Warning: QXF file is only partially loaded because of error.**

**Cause:** Error in loading QXF file.

**Action:** Correct those errors.



---

**Level: 1**

**Type: ERROR**

**Impact: Other**

**BRW-15570: Parse Error: Line {1}: Invalid operator {2} in relationship block.**

**Cause:** Invalid Operator within relationship block.

**Action:** Check operator and correct it.

**Level: 1**

**Type: ERROR**

**Impact: Other**

**BRW-15571: Parse Error: Line {1}: Invalid operator field argument.**

**Cause:** Invalid Object ID within Derived Item Expression.

**Action:** Correct Object ID in dictionary.

**Level: 1**

**Type: ERROR**

**Impact: Other**

**BRW-15572: Inconsistent object IDs in derived item expression.**

**Cause:** Invalid operator field argument within relationship block.

**Action:** Check operator strings and correct them.

**Level: 1**

**Type: ERROR**

**Impact: Other**

**BRW-15580: Unable to load list of accessible business areas**

**Cause:** End User Layer is missing business area tables.

**Action:** Reinstall End User Layer. Ask system administrator for assistance.

**Level: 1**

**Type: ERROR**

**Impact: Other**

**BRW-15581: Cannot add columns to table created with duplicate data**

**Cause:** User tried to add columns to a table created with duplicate table data.

**Action:** Commit the duplicated table then try again.

**Level: 1**

**Type: ERROR**

**Impact: Data**

**BRW-15582: New or duplicate table is only allowed on existing table.**

**Cause:** Create new table on another new/duplicate/modified table.

**Action:** Commit the new/duplicate/modified table first.

**Level: 1**

**Type: ERROR**

---

**Impact:** Other

**BRW-15583: Index requires at least one column**

**Cause:** User tried to remove the last column of an index.

**Action:** Add other columns then remove.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15584: Column {1} is of type LONG and will not be copied**

**Cause:** Cannot copy a LONG column when creating a snapshot.

**Action:** Column cannot be copied.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15600: Syntax not supported**

**Cause:** Attempted to parse unsupported syntax

**Action:** Use alternate Oracle 8 syntax.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15601: Invalid Oracle 8 SQL syntax**

**Cause:** Cannot use Oracle 8 language syntax

**Action:** Use Oracle 7 SQL.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15602: Type Constructor in Oracle 8 SQL is not supported**

**Cause:** Oracle 8 SQL's type constructors are not supported.

**Action:** Revert to Oracle 7.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15603: REF in Oracle 8 SQL is not supported**

**Cause:** Oracle 8 SQL's REF is not supported.

**Action:** Use Oracle 7 instead.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15604: CAST in Oracle 8 SQL is not supported**

---

**Cause:** Oracle 8 SQL's CAST is not supported.

**Action:** Use Oracle 7 instead.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15605: MULTISSET in Oracle 8 SQL is not supported**

**Cause:** Oracle 8 SQL's MULTISSET is not supported.

**Action:** Use Oracle 7 instead.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15606: METHODS in Oracle 8 SQL is not supported**

**Cause:** Oracle 8 SQL's METHODS is not supported.

**Action:** Use Oracle 7 instead.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15607: THE subquery in Oracle 8 SQL is not supported**

**Cause:** Oracle 8 SQL's THE subquery is not supported.

**Action:** Use Oracle 7 instead.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15608: PARTITION of tables in Oracle 8 SQL is not supported**

**Cause:** Oracle 8 SQL's PARTITION of tables is not supported.

**Action:** Use Oracle 7 instead.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15609: The TABLE keyword in a subquery in Oracle 8 SQL is not supported**

**Cause:** TABLE in subquery is not supported.

**Action:** Use Oracle 7 instead.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15610: Rename the Table as a Table Alias**

**Cause:** Attempt to use a table instead of a table alias

**Action:** Rename the table with a table alias.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15641: Help system initialization failed. Help will be unavailable.**

**Cause:** Unable to locate help document or help resource file.

**Action:** User may continue but help menu is unavailable. Use online or paper documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15643: Resource file not found ({1}), trying default resource file.**

**Cause:** NLS\_LANG set but file not found.

**Action:** Try to open the resource file using the default language.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15644: Unable to locate help document ({1}), trying default help document.**

**Cause:** NLS\_LANG set but file not found.

**Action:** Try to open the help doc using the default language.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15647: Unable to locate help document**

**Cause:** Could not find help file in correct directory with correct language.

**Action:** Check Browser directory structure. Make sure NLS\_LANG is set correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15648: Help system creation error**

**Cause:** Help system could not start up.

**Action:** Browser could not find the help resource file, or NLS\_LANG is not set, or memory is low.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15649: Input for {1} was too low. Minimum valid number is {2}.**

**Cause:** The value input was too low.

**Action:** Try again with a higher value.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15650: Input for {1} was too high. Maximum valid number is {2}.**

**Cause:** The value input was too high.

**Action:** Try again with a lower value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15651: Input for {1} was out of range. Must be between {2} and {3}.**

**Cause:** The value input was out of the valid range.

**Action:** Try again with a valid number.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15652: Value was reset to {1}.**

**Cause:** The value input was changed because it was out of the valid range.

**Action:** Try again with a valid number or Browser will use the value shown.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15653: Pref file error: Value {1} was too low. Minimum valid number is {2}.**

**Cause:** The value input was too low.

**Action:** Try again with a higher value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15654: Pref file error: Value {1} was too high. Maximum valid number is {2}.**

**Cause:** The value input was too high.

**Action:** Try again with a lower value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15655: Pref file error: Value {1} out of range. Must be between {2} and {3}.**

**Cause:** The value input was out of the valid range.

**Action:** Try again with a valid number.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**BRW-15656: Pref file error: Value for {1} not recognized**

**Cause:** The value set in the preference file was invalid.

**Action:** Try again with a valid number.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15657: Value for OWNERLIST=NAME must contain at least one name**

**Cause:** The value for OWNERLIST=NAME was NULL.

**Action:** Try again with a valid name

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15900: Unable to find time period information**

**Cause:** This database does not support time periods, or database error.

**Action:** Try again later if this is unexpected.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15901: Data source {1} referred to by object {2} no longer exists**

**Cause:** Base data source of object has been removed.

**Action:** Refresh/delete object.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BRW-15902: Table referred to by object {1} no longer exists**

**Cause:** Base data source of object has been removed.

**Action:** Refresh/delete object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15903: Opposite table {1} is not in a business area. Join info inaccessible.**

**Cause:** Relationship: Opposite data table/object not in any group.

**Action:** Grant that object to a group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15904: Relationship name cannot be longer than {1} bytes**

---

**Cause:** Relationship Name longer than limit.

**Action:** Use a shorter name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15905: Column heading cannot be longer than {1} bytes**

**Cause:** Item Heading longer than limit.

**Action:** Use a shorter heading.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15906: Column format cannot be longer than {1} bytes**

**Cause:** Item Format longer than limit.

**Action:** Use a shorter format.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15907: Column display width cannot have more than {1} digits**

**Cause:** Item Display Width Precision longer than limit.

**Action:** Use Shorter Display width.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15908: Time period name cannot be longer than {1} bytes**

**Cause:** Time Period Name too long.

**Action:** Use a shorter time period name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15909: Period column and sequence column of time period are the same**

**Cause:** Period and sequence columns of time period set to the same column.

**Action:** make sure period and sequence columns are different.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15910: Unable to load time period {1}**

**Cause:** Schema internal error in loading time period.

**Action:** Refer to accompanying error messages for more information.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15911: Time period {1} already exists**

**Cause:** Time period name must be unique.

**Action:** Create time period under a different name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15912: Illegal display width value.**

**Cause:** Illegal display width value.

**Action:** Re-enter a legal value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15913: {1} key text cannot be empty.**

**Cause:** Foreign or Primary Key text is empty.

**Action:** Enter text for primary or foreign key.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15914: Relationship name cannot be empty.**

**Cause:** Relationship name is null.

**Action:** Enter relationship name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15924: Business area name cannot be empty**

**Cause:** Business area name is empty or contains only spaces.

**Action:** Enter a new name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15925: Table {1} has already been imported as {2}**

**Cause:** Table can only be imported once with a given name.

**Action:** Import table under a different name.

**Level:** 1

**Type:** ERROR



---

**Impact:** Other

**BRW-15926: Business area {1} already exists**

**Cause:** Business area name must be unique.

**Action:** Create business area under a different name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15927: Business area {1} already contains a table named {2}**

**Cause:** Table name must be unique within a business area.

**Action:** Rename/reimport table and add to business area.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15928: Business area name too long (Max {1} bytes)**

**Cause:** Business area name too long.

**Action:** Shorten the name and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15929: Business area description too long (Max {1} bytes)**

**Cause:** Business area description too long.

**Action:** Shorten the description and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15930: Error committing table {1}**

**Cause:** Error occurred while committing table.

**Action:** Try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15931: Error committing business area {1}**

**Cause:** Error occurred while committing business area.

**Action:** Try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15932: Error committing time period {1}**

---

**Cause:** Error occurred while committing time period.

**Action:** Try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15933: Error committing relationship {1}**

**Cause:** Error occurred while committing relationship

**Action:** Try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15937: Error generating SQL for table {1}**

**Cause:** Error occurred while generating SQL for a table.

**Action:** Try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15938: Error generating SQL for business area {1}**

**Cause:** Error occurred while generating SQL for a business area.

**Action:** Try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15939: Error generating SQL for time period {1}**

**Cause:** Error occurred while generating SQL for a time period.

**Action:** Try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15940: Error generating SQL for relationship {1}**

**Cause:** Error occurred while generating SQL for relationship.

**Action:** Try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15950: No Query Builder tables--Database open/save is disabled**

**Cause:** There is no Query Builder system query table in the database.

**Action:** Create a system query table (run the Query Builder install script).

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15951: Product user profile information not loaded**

**Cause:** Cannot load the user profile table.

**Action:** Ask system administrator to create one.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15952: User privilege table not loaded**

**Cause:** Missing USER\_USERS table (Non Oracle or oracle V7 database).

**Action:** None available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15953: Table privilege table not loaded**

**Cause:** Cannot find Privilege table.

**Action:** Non-Oracle database or Oracle V7 database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15954: Oracle Query Builder 2.5 tables are missing or not installed properly**

**Cause:** No BROWSER\_DOCS\_SQL table.

**Action:** Re-install Query Builder 2.5 tables.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-15955: Query returned zero rows**

**Cause:** Query returned no rows.

**Action:** Modify the query so that it requests data that exists in the database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16000: Document saved using End User Layer, not Native dictionary.  
Continue?**

**Cause:** User tried to open in Native mode a document saved using the End User Layer.

**Action:** Run with DICTIONARY=ENDUSER or End User Layer objects will be inaccessible.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16001: Document saved using Native dictionary, not End User Layer.**

**Continue?**

**Cause:** User tried to open in ENDUSER mode a document saved using the Native dictionary.

**Action:** Run with DICTIONARY=NATIVE or some database objects may be inaccessible.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16250: Document already exists. Do you want to overwrite?**

**Cause:** User tried to Save As over an existing document.

**Action:** User may overwrite or cancel.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16251: Table has been modified. Continue?**

**Cause:** View was removed and recreated; may be inconsistent with document.

**Action:** Either continue or abort save.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16500: Memory not available for local sort. Re-execute?**

**Cause:** All rows not yet fetched for local sort.

**Action:** Re-execute query now or later.

**Level:** 1

**Type:** ERROR

**Impact:** Memory

**BRW-16503: Data not available for local sort. Re-execute?**

**Cause:** All rows not yet fetched for local sort.

**Action:** Re-execute query now or later.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BRW-16504: Data not available for local break. Re-execute?**

**Cause:** All rows not yet fetched for local break.

**Action:** Re-execute query now or later.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BRW-16525: Query may require a Cartesian product. Continue?**

**Cause:** Query combines results of unrelated tables.

**Action:** Ignore message or relate tables before executing. Refer to help or documentation for details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16531: Redefine parameter {1}?**

**Cause:** User entered previously deleted parameter in expression or condition.

**Action:** Press OK if this is what you intended.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16532: Parameter {1} does not exist. Define?**

**Cause:** User entered new parameter in expression or condition.

**Action:** Press OK if this is what you intended.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16549: Revert will undo all changes on these tables. Revert anyway?**

**Cause:** Confirmation before reverting data tables.

**Action:** Select OK to revert all selected data tables, Cancel to cancel the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16550: Table %s has primary/unique keys that are referenced. Remove?**

**Cause:** Table contains constraints.

**Action:** Select OK to remove the data table, Cancel to cancel the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16551: Column has primary/unique keys or indexes. Remove anyway?**

**Cause:** Column is used by constraints or indexes.

**Action:** Select OK to remove the column, Cancel to cancel the operation.

**Level:** 1

---

Type: ERROR

Impact: Other

**BRW-16552: Disable all constraints?**

Cause: Message to confirm that all constraints should be disabled.

Action: User may confirm or cancel.

Level: 1

Type: ERROR

Impact: Other

**BRW-16553: Enable all constraints?**

Cause: Message to confirm that all constraints should be enabled.

Action: User may confirm or cancel.

Level: 1

Type: ERROR

Impact: Other

**BRW-16575: There are uncommitted edits which will be lost. Commit?**

Cause: User has tried to exit the Data Editor without committing changes.

Action: Select Commit or lose changes.

Level: 1

Type: ERROR

Impact: Other

**BRW-16576: Defined Column, Summary or Break values may not be current.  
Re-execute?**

Cause: Values edited while displaying breaks, summaries, or defined columns.

Action: Execute query to update values.

Level: 1

Type: ERROR

Impact: Other

**BRW-16620: Save changes to query document '%s'?**

Cause: Message to prompt user to save changes when closing/quitting.

Action: User may save or abort changes, or cancel.

Level: 1

Type: ERROR

Impact: Other

**BRW-16621: Revert to previously saved version of document '%s'?**

Cause: Message to prompt user to revert to older document version.

Action: User may continue or cancel operation.

Level: 1

Type: ERROR

---

**Impact:** Other

**BRW-16622: File %s already exists. Do you want to overwrite?**

**Cause:** Message for overwrite alert in export data.

**Action:** User may overwrite file or cancel.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16623: There is no data available for this operation.**

**Cause:** Alert message if number of rows or columns available to print is zero.

**Action:** User should try re-executing the query, or include some columns.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BRW-16624: Query definition has changed. Data may not be current. Continue?**

**Cause:** Query document has changed since last execute.

**Action:** Either re-execute the query, continue export, or cancel.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BRW-16625: The printer does not support all fonts needed. Substitute fonts?**

**Cause:** The font or some style or weight does not exist for the selected printer.

**Action:** User may continue with font substitution or cancel.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16626: Not enough memory for Print Preview.**

**Cause:** Unable to create bitmap for print preview.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Memory

**BRW-16627: There is no data available for this operation. Execute query?**

**Cause:** Alert message if export data called with empty worksheet.

**Action:** User should try executing the query or cancel.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BRW-16628: Unable to get printer device. Printing will be unavailable. Continue?**

---

**Cause:** Error creating a toolkit printer surface with uiprc().

**Action:** User may continue with no printing or cancel.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16629: Do you want to update the container before exiting?**

**Cause:** Message to prompt user to save changes when closing/quitting OLE doc.

**Action:** User may save or abort changes, or cancel.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16632: No SQL is available because no columns were selected. Quit?**

**Cause:** Message to alert user that so sql statement was created.

**Action:** User may exit or continue in query builder.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16650: The printer does not support all fonts needed. Substitute fonts?**

**Cause:** The font or some style or weight does not exist for the selected printer.

**Action:** User may continue with font substitution or cancel.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16651: No printer has been chosen. Use Default?**

**Cause:** The user has not explicitly named a printer to use.

**Action:** User may continue with the system default printer or cancel.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16652: Margins for this document are too wide and must be reset.**

**Cause:** The user has set the margins to be too large leaving no content.

**Action:** User must reset the margins.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16653: No printer has been chosen. Use Default?**

**Cause:** The user has not explicitly named a printer to use.

**Action:** User may continue with the system default printer or cancel.



---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16654: No pages printed.**

**Cause:** User has set copies to 0 or the start/end page outside the range.

**Action:** Reset page range.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16660: Query definition has changed. Data may not be current. Re-execute?**

**Cause:** Query document has changed since last DDE update.

**Action:** Re-execute the query before DDE update, or update without executing.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BRW-16661: Commit changes to %s?**

**Cause:** Message to prompt user to commit changes when closing Schema Builder.

**Action:** User may commit or abort changes, or cancel.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16767: Abandon current parameter settings and cancel query?**

**Cause:** In parameters dialog, ask user before cancelling settings.

**Action:** User may continue the cancel or return to the dialog.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16776: Apply settings before closing dialog?**

**Cause:** Asks user if settings changes should be committed before close.

**Action:** User may apply the changes or exit without committing those changes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16780: Cannot paste condition on LONG column.**

**Cause:** Cannot paste a condition on a long column from the find dialog.

**Action:** This action is not supported.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**BRW-16807: Accept the definition for the new business area?**

**Cause:** Business Area Define - validate Complete NEW business area

**Action:** Accept or cancel

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16808: Cancel the incomplete definition for the new business area?**

**Cause:** Business Area Define - validate Incomplete NEW business area

**Action:** Confirm or cancel

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16809: Accept the modified business area definition?**

**Cause:** Business Area Define - validate MODified business area

**Action:** Confirm or cancel

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16810: Accept the definition for the new column?**

**Cause:** Data Table Expressions - validate Complete NEW expression

**Action:** Confirm or cancel

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16811: Cancel the incomplete definition for the new column?**

**Cause:** Data Table Expressions - validate Incomplete NEW expression

**Action:** Confirm or cancel

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16812: Accept the modified column definition?**

**Cause:** Data Table Expressions - validate MODified expression

**Action:** Confirm or cancel

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16813: Accept the definition for the new relationship?**

---

**Cause:** Data Table Relationships - validate Complete NEW relationship

**Action:** Confirm or cancel

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16816: Accept the changes to the column's format options?**

**Cause:** Data Table Format - validate MODified format options

**Action:** Confirm or cancel

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16817: Commit changes?**

**Cause:** User tries to quit with uncommitted changes

**Action:** Confirm or cancel

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16833: Rollback all changes?**

**Cause:** Confirmation before rollback

**Action:** OK to rollback all changes. Cancel to cancel operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16837: Business area description cannot be empty.**

**Cause:** Business area description is null.

**Action:** Enter a description.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16840: Business area name cannot be empty.**

**Cause:** Business area name is null.

**Action:** enter a name

**Level:** 1

**Type:** ERROR

**Impact:** Other

**BRW-16841: Time period definition is incomplete.**

**Cause:** Some time period attributes have not been specified.

**Action:** Complete the time period definition.

---

**Level: 1**

**Type: ERROR**

**Impact: Other**

**BRW-16852: User is already imported. Reimport?**

**Cause:** User has already been imported.

**Action:** Confirm or cancel reimport.

**Level: 1**

**Type: ERROR**

**Impact: Other**

**BRW-16961: Document '%s' has unsaved publishers.**

**Cause:** Message (1 of 2) to prompt user to save changes on close/quit.

**Action:** User may save or abort changes, or cancel.

**Level: 1**

**Type: ERROR**

**Impact: Other**

**BRW-16962: They will be lost unless the document is saved.**

**Cause:** Message (2 of 2) to prompt user to save changes on close/quit

**Action:** User may save or abort changes, or cancel.

**Level: 1**

**Type: ERROR**

**Impact: Other**

**BRW-16965: Memory is low. Close open documents or restart with more memory.**

**Cause:** Low memory (<1MB)

**Action:** Close extra documents, restart with more memory

**Level: 1**

**Type: ERROR**

**Impact: Memory**

**BRW-16966: Out of memory. Restart application with a larger memory size.**

**Cause:** No memory

**Action:** Close extra documents, restart with more memory

**Level: 1**

**Type: ERROR**

**Impact: Memory**

**BRW-16967: This application requires System 7.0 or higher.**

**Cause:** Operating System version is lower than 7.0

**Action:** Upgrade operating system and restart

**Level: 1**

**Type: ERROR**

---

**Impact:** Other

**BRW-16975: Cannot resolve data table '{1}'. Select a new data table?**

**Cause:** Query Choose Table

**Action:** Confirm or cancel

**Level:** 1

**Type:** ERROR

**Impact:** Data

**BRW-16976: Cannot resolve column '{1}' in data table '{2}'. Select a new column?**

**Cause:** Query Choose Column

**Action:** Confirm or cancel

**Level:** 1

**Type:** ERROR

**Impact:** Data



---

## CFGFWK-60001 to CFGFWK-72080

**CFGFWK-60001:** The user name must not contain commas, tabs, or any of the following characters: <>#|&?(){}

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60002:** The string must have a minimum length of {0} characters

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60003:** The value {0} is greater than the maximum allowable value of {1}

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60004:** The value {0} is less than the minimum allowable value of {1}

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60005:** WebLogic domain requires the password to be minimum 8 characters

**Cause:**

**Action:**

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60006: The value must be one of the following: {0}.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60050: Property "{0}" of {1} "{2}" is invalid.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60051: Property "{0}" of {1} with original name "{2}" is invalid.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60052: Space characters are not allowed.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60053: The string cannot be converted.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60054: The property value is required.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR



---

**Impact:** Configuration

**CFGFWK-60055: The property value is duplicated.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60056: The property is disabled.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60057: The property is not supported.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60058: The class name must have the format "xxx.xxx.xxx.xxx".**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60059: The properties string must contain fields formatted as "name=value" separated by ";".**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60060: The known definition of property "{0}" cannot be changed.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**CFGFWK-60061: The additional property "{0}" must be defined.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60062: If "All Local Addresses" is selected, no additional address should be provided.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60063: The list of address is empty.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60064: The confirmed password does not match the entered one.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60065: Invalid input**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60066: The returned row set is null.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60100: At most {0} entries can be created.**

---

**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-60101: At most 1 entry can be created.**

**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-60102: At least {0} entries must be provided.**

**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-60103: At least 1 entry must be provided.**

**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-60150: The server has the same combination of listen address and port as other server.**

**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-60151: The server has the same combination of listen address and SSL port as other server.**

**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

---

**CFGFWK-60152: The server has the same combination of listen address and port as admin server.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60153: The server has the same combination of listen address and SSL port as admin server.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60154: The server has the same port and SSL port.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60155: Listen port cannot be empty.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60156: The IP address must have the proper v6 format like**

**"xxxx:xxxx:xxxx:xxxx:xxxx:xxxx:xxxx:xxxx" or "xxxx:xxxx:xxxx:xxx.xxx.xxx.xxx" or other supported format.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60157: The IP address must have the format "xxx.xxx.xxx.xxx".**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

---

**Impact:** Configuration

**CFGFWK-60158:** Each segment of the IP address must contain an integer in the range of 0 to 255.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60159:** Each segment of the IP address must contain an integer in the range of 0 to 255.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60160:** The IP multicast address must be in the range of 224.0.0.1 to 239.255.255.255.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60161:** The host name does not allow leading or trailing dot (.).

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60162:** The host name does not allow multiple dots (.).

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60163:** No member of the hostname may begin or end with a dash (-).

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**CFGFWK-60164:** The entered value is not a valid hostname. Please use only alphanumeric characters and dot (.) and dash (-).

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60165:** The right most domain label can never start with a digit.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60166:** Each entry must be expressed as <hostname> or <hostname>:<port>.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60167:** The port number must be an integer.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60168:** The port number must be an integer in the range of 1 to 65535.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60200:** The targets of the distributed destination should cover all the servers that host the members.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**CFGFWK-60201:** The distributed topic "{0}" that distributed topic member "{1}" belongs to is not deployed.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60202:** The JMS Server "{0}" that topic "{1}" belongs to is not deployed.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60203:** The distributed queue "{0}" that distributed queue member "{1}" belongs to is not deployed.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60204:** The JMS Server "{0}" that queue "{1}" belongs to is not deployed.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60205:** Group(s) assigned to "Admin" role must contain at least one user.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60206:** Admin role must be assigned at least one group or one user.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**CFGFWK-60207: The JDBC (Tx) DataSource specifies a nonexistent JDBC Connection Pool.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60208: The JDBC Multi Pool specifies a nonexistent JDBC Connection Pool.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60209: The JDBCConnectionPool "{0}" could not be undeployed from target "{1}", because it is used by the JMSJDBCStore "{2}", which is used by the deployed JMSServer "{3}".**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60250: The JNDI name is duplicated in JMS server "{0}"**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60300: You must specify a WebLogic domain name.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60301: The name of the WebLogic domain and the server/cluster names within it must be unique. A server/cluster already exists with the WebLogic domain name you specified.**

**Cause:**

**Action:**



---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60302:** A domain with an identical name exists at the location you have selected. Change the domain name or location.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60303:** The domain directory you specified contains files. You may only create a domain in an empty directory.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60304:** The applications directory you specified contains files. Applications may only be written to an empty directory.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60305:** The specified domain name must include only alphanumeric characters, hyphens ('-') or underscore characters ('\_'). The domain name must contain at least one letter or digit.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60306:** The domain location must not contain spaces.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60307:** The domain location must be specified.

---

**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-60308: The domain location must have write permission.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-60309: The application location must not contain spaces.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-60310: The application location must be specified.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-60311: The application location must have write permission.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-60312: You must specify a Template Jar Name to Create.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-60313: The specified template name must include only alphanumeric characters, hyphens ('-') or underscore characters ('\_'). The template name must contain at least one letter or digit.**

---

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60314: The template location must not contain spaces.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60315: The template location must be specified.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60316: The template location must have write permission.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60317: The "Servers, Clusters and Machines" configuration in your domain is invalid. Try to resolve the issue by clicking Cancel and returning to this section in the wizard. If you cannot resolve the issue, either click Cancel and exit the wizard, or click OK to continue. If continuing, you may want to start the server in the domain and review the messages to identify the invalid configuration.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60318: The "JDBC" configuration in your domain is invalid. Try to resolve the issue by clicking Cancel and returning to this section in the wizard. If you cannot resolve the issue, either click Cancel and exit the wizard, or click OK to continue. If continuing, you may want to start the server in the domain and review the messages to identify the invalid configuration.**

**Cause:**

**Action:**

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60319:** The "JMS" configuration in your domain is invalid. Try to resolve the issue by clicking Cancel and returning to this section in the wizard. If you cannot resolve the issue, either click Cancel and exit the wizard, or click OK to continue. If continuing, you may want to start the server in the domain and review the messages to identify the invalid configuration.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60320:** The "Security" configuration in your domain is invalid. Try to resolve the issue by clicking Cancel and returning to this section in the wizard. If you cannot resolve the issue, either click Cancel and exit the wizard, or click OK to continue. If continuing, you may want to start the server in the domain and review the messages to identify the invalid configuration.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60321:** Duplicate Server listen ports exist in your domain configuration.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60322:** Server listen ports in your domain configuration conflict with ports in use by active processes on this host.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60323:** An unknown section of your configuration is invalid. Either click Cancel and exit the wizard or click OK to continue. If you continue, you may want to start the server in the domain and review the messages to identify the invalid configuration.

**Cause:**

**Action:**

---

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60324: The domain location is not a directory.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60325: The directory location is invalid.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60326: Directory names must include only alphanumeric characters, hyphens ('-') or underscore characters ('\_') and must contain at least one letter or digit.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60327: A directory name cannot be null.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60328: The application location is not a directory.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60329: The following templates require entry of a KeyStore password:**

**Cause:**

**Action:**

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60330:** Use the `storeKeyStorePassword(template_location, password)` command for each template listed above to enter required KeyStore passwords. The command must be entered after adding templates and before updating the domain.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60367:** The "Servers, Clusters and Machines" configuration in your domain is invalid. Try to resolve the issue by entering Previous and returning to this section in the wizard. If you cannot resolve the issue, either Exit the wizard now, or enter Next to continue. If continuing, you may want to start the server in the domain and review the messages to identify the invalid configuration.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60368:** The "JDBC" configuration in your domain is invalid. Try to resolve the issue by entering Previous and returning to this section in the wizard. If you cannot resolve the issue, either Exit the wizard now, or enter Next to continue. If continuing, you may want to start the server in the domain and review the messages to identify the invalid configuration.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60369:** The "JMS" configuration in your domain is invalid. Try to resolve the issue by entering Previous and returning to this section in the wizard. If you cannot resolve the issue, either Exit the wizard now, or enter Next to continue. If continuing, you may want to start the server in the domain and review the messages to identify the invalid configuration.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**CFGFWK-60370:** The "Security" configuration in your domain is invalid. Try to resolve the issue by entering Previous and returning to this section in the wizard. If you cannot resolve the issue, either Exit the wizard now, or enter Next to continue. If continuing, you may want to start the server in the domain and review the messages to identify the invalid configuration.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60371:** Duplicate Server listen ports exist in your domain configuration.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60372:** Server listen ports in your domain configuration conflict with ports in use by active processes on this host.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60373:** An unknown section of your configuration is invalid. You can either Exit the wizard now or enter Next to continue. If you continue, you may want to start the server in the domain and review the messages to identify the invalid configuration.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60417:** The "Servers, Clusters and Machines" configuration in your domain is invalid. Try to resolve the issue by reviewing your script. The wizard will continue, but you may want to start the server in the domain and review the messages to identify the invalid configuration.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**CFGFWK-60418:** The "JDBC" configuration in your domain is invalid. Try to resolve the issue by reviewing your script. The wizard will continue, but you may want to start the server in the domain and review the messages to identify the invalid configuration.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60419:** The "JMS" configuration in your domain is invalid. Try to resolve the issue by reviewing your script. The wizard will continue, but you may want to start the server in the domain and review the messages to identify the invalid configuration.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60420:** The "Security" configuration in your domain is invalid. Try to resolve the issue by reviewing your script. The wizard will continue, but you may want to start the server in the domain and review the messages to identify the invalid configuration.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60421:** Duplicate Server listen ports exist in your domain configuration.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60422:** Server listen ports in your domain configuration conflict with ports in use by active processes on this host.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration



---

**CFGFWK-60423: An unknown section of your configuration is invalid. Try to resolve the issue by reviewing your script. The wizard will continue, but you may want to start the server in the domain and review the messages to identify the invalid configuration.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60450: The default admin user could not be deleted.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60451: Cannot add built-in groups "everyone" or "users".**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60452: Built-in roles "Admin" and "Anonymous" must be provided.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60453: The supplied user password for "{0}" is too short**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60454: The supplied user name for "{0}" is not in required format.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

---

**CFGFWK-60455: The password must be at least 8 alphanumeric characters with at least one number or special character.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60500: The {0} must be specified.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60501: The following must be specified:**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60502: The {0} and {1} do not match.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60503: The {0} must be an integer.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60504: The selected data sources do not share any common database drivers. The wizard will deselect data sources to allow selection of compatible drivers.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

---

**CFGFWK-60505: The selected component schemas do not share any common database drivers. The wizard will deselect component schemas to allow selection of compatible drivers.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60550: Script execution aborted. The script may contain an error.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60551: Details in the log file:**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60600: Before booting this domain, it is necessary to run the SQL file located at {0} in order to initialize a domain security admin user in the database.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60601: Unable to add template: Required component not found.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60650: The location does not exist.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

---

**CFGFWK-60651: Select another directory location**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60655: The location does not exist or not a directory.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60656: No domains found under selected directory.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60660: The location is invalid.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60665: Error getting connection info!**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60666: Database Load Failed! Check the log located at:**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60667: There are no files available to load into the database.**

**Cause:**

---

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60668: Test Failed!**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60675: The template you selected can't be applied because the following dependencies have not been satisfied:**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60676: Select an available template from the list**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60677: Selection does not contain a domain template.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60678: Fatal error**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60679: Select a valid domain template**

**Cause:**

**Action:**

---

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-60680: Unable to add application template**  
**Cause:**  
**Action:**

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-60685: The path specified was invalid.**  
**Cause:**  
**Action:**

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-60686: No template exists at**  
**Cause:**  
**Action:**

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-60687: The template you selected can't be applied because the following dependencies have not been satisfied:**  
**Cause:**  
**Action:**

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-60688: Unable to load template.**  
**Cause:**  
**Action:**

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-60689: Selection does not contain a domain template.**  
**Cause:**  
**Action:**

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60690: Select a valid domain template**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60691: Some of the application templates you have selected are incompatible with each other due to conflicting application and/or service names.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60692: Unable to add application template**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60695: User password does not match confirmed password.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60700: Unable to determine if the directory you selected contains a valid JDK. Do you want to proceed**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60701: You must specify a JDK location.**

**Cause:**

**Action:**

**Level:** 1

---

Type: ERROR

Impact: Configuration

**CFGFWK-60705: Some of the configuration extensions you have selected are incompatible with each other due to conflicting application and/or service names.**

Cause:

Action:

Level: 1

Type: ERROR

Impact: Configuration

**CFGFWK-60706: The Configuration Template Builder is not supported in console mode.**

Cause:

Action:

Level: 1

Type: ERROR

Impact: Configuration

**CFGFWK-60707: The template is already selected.**

Cause:

Action:

Level: 1

Type: ERROR

Impact: Configuration

**CFGFWK-60800: There is a problem with the template!**

Cause:

Action:

Level: 1

Type: ERROR

Impact: Configuration

**CFGFWK-60801: No template was selected!**

Cause:

Action:

Level: 1

Type: ERROR

Impact: Configuration

**CFGFWK-60802: Select a specific domain.**

Cause:

Action:

Level: 1



---

Type: ERROR

Impact: Configuration

**CFGFWK-60803: This is not a valid configuration! Correct the following error in config.xml:**

Cause:

Action:

Level: 1

Type: ERROR

Impact: Configuration

**CFGFWK-60804: The Configuration Wizard encountered problems attempting to load the configuration you selected. Would you like to generate a log file which will be located at**

Cause:

Action:

Level: 1

Type: ERROR

Impact: Configuration

**CFGFWK-60805: The domain in this directory is not a supported version.**

Cause:

Action:

Level: 1

Type: ERROR

Impact: Configuration

**CFGFWK-60806: The Configuration Wizard was unable to generate the log file located at**

Cause:

Action:

Level: 1

Type: ERROR

Impact: Configuration

**CFGFWK-60807: Failed to create busMember {0}**

Cause:

Action:

Level: 1

Type: ERROR

Impact: Configuration

**CFGFWK-60808: No bus members defined for bus {0}**

Cause:

Action:

---

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-60809: Datasource provider was not found for {0}**  
**Cause:**  
**Action:**

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-60810: There is a problem with the template!**  
**Cause:**  
**Action:**

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-60811: There were no standard components found in your installation.**  
**Browse to a custom component**  
**Cause:**  
**Action:**

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-60812: Some of the extension templates you have selected are incompatible with each other due to conflicting application and/or service names.**  
**Cause:**  
**Action:**

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-60813: The extension template you selected can't be applied because the following dependency has not been satisfied:**  
**Cause:**  
**Action:**

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-60814: The template you selected can't be applied because the following dependencies have not been satisfied:**

---

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60815: The configuration extension listed below contains a component that is already defined in the existing domain. Indicate how to resolve this conflict.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60816: Select a valid domain template**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60817: The config.xml is invalid or missing in the template selected.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60818: The selected template is designed to extend an existing domain. It is defined as an extension template and does not express a dependency on a domain template. Select another template or choose one of the above checkbox selections.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60819: Select an available template from the list or select an existing template below**

**Cause:**

**Action:**

**Level:** 1

---

**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-60820: Specify valid template path.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-60821: Specified template does not exist.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-60825: Unable to create HTTP proxy application(s)**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-60826: You have chosen a managed server which is already a proxy for a cluster. It is recommended that a managed server only proxy a single cluster. Click OK to keep your assignment and continue, otherwise click Cancel to change it.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-60827: The managed server chosen as a HTTP proxy for a cluster is invalid. Its Listen Address should be a valid host name or an IP address.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-60828: The Listen Address for all servers in a cluster with an HTTP proxy should be a valid host name or an IP address.**  
**Cause:**  
**Action:**

---

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60830: There must be files to load.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60831: You must select a file first.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60832: You must select a file first.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60833: You must select a file first.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60834: The URL entered may not end with forward slash ("/").**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60835: The URL entered was malformed.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

---

**Impact:** Configuration

**CFGFWK-60837: Test Failed!**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60838: Error getting connection information!**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60839: Database Load Failed!**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60840: Error encountered starting PointBase server or the server process was killed!**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60841: For possible information regarding the error check the log located at:**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60842: Error encountered stopping the PointBase server! Check log file:**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**CFGFWK-60843: Error Writing Log File:**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60850: Test Failed!**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60851: Error getting connection information!**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60852: The jdbc connection data for data source {0} is incomplete. Fix the data before testing.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60853: A connection was established to the database but no rows were returned from the test SQL statement.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60855: Name cannot be empty. Re-enter.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**CFGFWK-60856: Version cannot be empty. Re-enter.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60857: Version should be in the format N.N.N.N where N is a positive number. Re-enter.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60860: Link Name and Program fields must be specified.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60865: This file type is not editable**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60870: Path cannot start or end with a path separator.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60875: The selected directory is a representation of a location that will be selected by the user when using this configuration and cannot be removed.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR



---

**Impact:** Configuration

**CFGFWK-60876:** You cannot remove the files in red or their parent directories because they comprise this configuration's applications.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60877:** You must first select a file to remove.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60878:** You must select a source file or directory on the left.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60879:** You must select a destination location on the right.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60880:** The selected directory is a representation of a location that will be selected by the user when using this configuration and files cannot be added.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-60881:** The selected file cannot be added to your domain directory because it is a reserved file. This usually means that the file will be auto-generated by the configuration wizard and does not need to be added.

**Cause:**

**Action:**

**Level:** 1

---

**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-60885:** Error encountered preparing template from jar.  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-60890:** Unable to determine if the selected directory contains a valid JDK.  
Do you want to proceed?  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-60891:** Unable to determine if the specified directory contains a valid  
JDK. Do you want to proceed?  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-60892:** The specified directory does not exist. Enter a valid JDK directory.  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-60893:** The selected JDK version doesn't match the jdk version pattern.  
Click Cancel and select a different jdk or Click OK to proceed with same jdk.  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-60894:** The recommended minimum JDK version doesn't match the jdk  
version pattern.  
**Cause:**  
**Action:**

---

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60895: The selected jdk version is lower than recommended minimum version. Click Cancel and select a different jdk or Click OK to proceed with same jdk.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60900: You must select a file first**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60901: You must select a file first**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60905: Password does not match**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60906: The field {0} cannot be empty.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-60907: The field {0} must be an integer.**

**Cause:**

**Action:**

---

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-60908:** The password/confirm password field is empty.  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-60909:** The password entered should match the confirm password field.  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-64001:** The value must be one of the following: {0}.  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-64010:** Property "{0}" of {1} "{2}" is invalid.  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-64011:** Property "{0}" of {1} with original name "{2}" is invalid.  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-64012:** Space characters are not allowed.  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR

---

**Impact:** Configuration

**CFGFWK-64013: The string cannot be converted.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64014: The property value is required.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64015: The property value is duplicated.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64016: The property is disabled.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64017: The property is not supported.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64018: The confirmed password does not match the entered one.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64019: Invalid input**

---

**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-64020: Property "{0}" of {1} with the new name "{2}" is invalid.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-64025: At most {0} entries can be created.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-64026: At most 1 entry can be created.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-64027: At least {0} entries must be provided.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-64028: At least 1 entry must be provided.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-64029: Disabled entry may not be removed.**  
**Cause:**  
**Action:**

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64035:** The {0} "{1}" could not be assigned to the target "{2}" since each target can have only one {0} assigned.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64040:** The template you selected can't be applied because the following dependencies have not been satisfied:

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64041:** Select an available template from the list

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64042:** Selection does not contain a domain template.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64043:** Fatal error

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64044:** Select a valid domain template

**Cause:**

**Action:**

---

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-64045: Unable to add application template**  
**Cause:**  
**Action:**

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-64050: No template was selected!**  
**Cause:**  
**Action:**

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-64051: Select a specific domain.**  
**Cause:**  
**Action:**

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-64052: This is not a valid configuration! Correct the following error in config.xml:**  
**Cause:**  
**Action:**

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-64053: The Configuration Wizard encountered problems attempting to load the configuration you selected. Would you like to generate a log file which will be located at**  
**Cause:**  
**Action:**

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-64054: The domain in this directory is not a supported version.**  
**Cause:**  
**Action:**



---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64055: The Configuration Wizard was unable to generate the log file located at**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64056: There is a problem with the template!**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64057: There were no standard components found in your installation. Browse to a custom component**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64058: Some of the extension templates you have selected are incompatible with each other due to conflicting application and/or service names.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64059: The extension template you selected can't be applied because the following dependency has not been satisfied:**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64060: The template you selected can't be applied because the following dependencies have not been satisfied:**

---

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64061: The configuration extension listed below contains a component that is already defined in the existing domain. Indicate how to resolve this conflict.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64062: Select a valid domain template**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64063: The config.xml is invalid or missing in the template selected.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64064: The selected template is designed to extend an existing domain. It is defined as an extension template and does not express a dependency on a domain template. Select another template or choose one of the above checkbox selections.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64065: Select an available template from the list or select an existing template below**

**Cause:**

**Action:**

**Level:** 1

---

**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-64066: Specify valid template path.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-64067: Specified template does not exist.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-64068: There is a problem with the template {0}!**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-64069: The following prerequisites were found to be missing:**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-64070: The following templates are both prerequisites and conflicts for the current selection:**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-64071: The selection conflicts with templates already installed in the domain:**  
**Cause:**  
**Action:**  
**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64072: One of the following needs to be selected:**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64073: The template is not selectable in the current mode**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64074: Given template is not present**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64075: The template is already installed**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64076: The template is already selected**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64077: The template is not selected**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**CFGFWK-64100: No such help topic exists**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64101: Help is not configured**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64102: Invalid help type**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64103: Errors occurred while loading Help. Check log for details.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64104: Value of console width is too low! Please set higher value.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64150: Internal Error: panel does not support help.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64151: Configuration Error: no help URI configured.**

**Cause:**

---

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64152: Configuration Error: invalid help URI.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-64153: Unable to open help: {0}**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68001: Duplicate Server listen ports exist in your cell configuration.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68010: The password must be at least 8 alphanumeric characters with at least one number or special character.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68020: The {0} must be specified.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68021: The following must be specified:**

**Cause:**

**Action:**

---

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-68022: The {0} and {1} do not match.**  
**Cause:**  
**Action:**

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-68023: The {0} must be an integer.**  
**Cause:**  
**Action:**

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-68024: The selected data sources do not share any common database drivers. The wizard will deselect data sources to allow selection of compatible drivers.**  
**Cause:**  
**Action:**

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-68025: The selected component schemas do not share any common database drivers. The wizard will deselect component schemas to allow selection of compatible drivers.**  
**Cause:**  
**Action:**

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-68026: Unable to encrypt password:**  
**Cause:**  
**Action:**

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-68028: The port value {0} must be in range of 0 to 65535.**  
**Cause:**

---

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68029: The port value {0} must be integer.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68030: Initialization error: {0}**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68031: The system wasn't initialized properly.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68032: The python interpreter is not set.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68033: Unable to create template catalog.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68034: Found no templates with {0} name and {1} version.**

**Cause:**

**Action:**



---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68035:** Found {2} templates with {0} name and {1} version.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68036:** Unable to load template from [{0}].

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68037:** Unable to load cell configuration.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68038:** The template is already selected.

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68039:** The following previously selected templates conflict with the new selection:

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68040:** The selected templates are not compatible with each other.

**Cause:**

**Action:**

**Level:** 1

---

**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-68041: Unable to add template with {0} name and {1} version: {2}.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-68042: Unable to save configuration.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-68043: Unknown scope defined: {0}.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-68044: Unable to copy : {0}**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-68045: Cell configuration not loaded.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-68046: Unable to register Oracle home information : {0}**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

---

**CFGFWK-68047: No templates were selected!**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68048: The name or type {1}:{0} can not be null.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68049: The requested type {0} is not supported.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68050: The {0}:{1} was not found in a requested scope {2}.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68051: Duplicate Server listen ports exist in your cell configuration.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68052: Server listen ports in your cell configuration conflict with ports in use by active processes on this host.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**CFGFWK-68053: The property {0} is not allowed to be modified; use listAttributes() for supported types.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68054: The {0} with name {1} was not found.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68055: The property {0} is not a supported type; use listTypes() for supported types.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68056: The property {0} is not a supported attributes; use listAttributes() for supported types.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68057: The property {0} is not valid; use listAttributes() or listTypes() for supported attributes and types.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68058: Unsupported profile type; select a deployment manager profile or a remotely federated custom profile : {0}**

**Cause:**

**Action:**

**Level:** 1

---

**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-68059: The requested {0};{1} could not be deleted.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-68060: The specified property {0} is read-only.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-68061: The requested operation is not allowed here.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-68062: The specified value {0} is not supported or is invalid!**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-68063: Specify path to deployment manager profile.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-68064: The specified value {0} for {1} is of incompatible type or out of range.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR

---

**Impact:** Configuration

**CFGFWK-68065: JDBC datasource validation failed:**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68066: The specified type is read-only.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68067: The specified operation {0}:{1} is not supported for WebSphere STANDALONE Cell.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68068: validation failed for : {0}**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68069: {0} assignment not supported.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68070: Test Failed!**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**CFGFWK-68071: Error getting connection information!**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68072: A connection was established to the database but no rows were returned from the test SQL statement.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68073: The value of attribute {0} is not allowed to be read.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68074: Run OracleMWConfig.dumpStack() to view the full Exception**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68075: Required attribute not specified: {0}**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68076: Source : {0} already assigned to Destination : {1}**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68077: Source : {0} not assigned to Destination : {1}**

---

**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-68078: Destination not found : {0}**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-68079: Could not complete {0} to {1} assignment. {2}**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-68080: The options map of {0} may not be null.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-68081: "{0}" is a required option of {1}.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-68082: The IP address must have the proper v6 format like  
"xxxx:xxxx:xxxx:xxxx:xxxx:xxxx:xxxx:xxxx" or "xxxx:xxxx:xxxx:xxx.xxx.xxx.xxx"  
or other supported format.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-68083: The IP address must have the format "xxx.xxx.xxx.xxx".**



---

**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-68084: Each segment of the IP address must contain an integer in the range of 0 to 255.**

**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-68085: Each segment of the IP address must contain an integer in the range of 0 to 255.**

**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-68086: The IP multicast address must be in the range of 224.0.0.1 to 239.255.255.255.**

**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-68087: The host name does not allow leading or trailing dot (.).**

**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-68088: The host name does not allow multiple dots (.).**

**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

---

**CFGFWK-68089: No member of the hostname may begin or end with a dash (-).**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68090: The entered value is not a valid hostname. Please use only alphanumeric characters and dot (.) and dash (-).**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68091: The right most domain label can never start with a digit.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68100: Errors occurred while loading OracleHelp. Check log for details.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68110: Error obtaining key from properties file**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-68111: Invalid prefix obtained from properties file**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-69500: Attempt to execute command "{0}" in invalid state: {1}**

---

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-69501: The method "{0}" is not available.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-69502: Assignment Target not found for type: {0}**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-69503: Could not find {0} : {1}**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-69504: Invalid Target : {0}**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-69510: Fatal internal error**

**Cause:** An unexpected internal condition was detected. The wizard cannot continue.

**Action:** Check the logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72001: Initialization error: {0}**

**Cause:**

---

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72002: The system wasn't initialized properly.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72003: The python interpreter is not set.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72004: Unable to create template catalog.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72005: Found no templates with {0} name and {1} version.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72006: Found {2} templates with {0} name and {1} version.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72007: Unable to load template from [{0}].**

**Cause:**

**Action:**

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72008: Unable to load JBoss configuration.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72009: The template is already selected.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72010: The following previously selected templates conflict with the new selection:**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72011: The selected templates are not compatible with each other.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72012: Unable to add template with {0} name and {1} version: {2}.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72013: Unable to save configuration.**

**Cause:**

**Action:**

**Level:** 1

---

**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-72014: JBoss configuration not loaded.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-72015: No templates were selected!**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-72016: JBOSS\_HOME has not been specified!**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-72017: JBOSS\_HOME {0} not found!**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-72018: JDBC datasource validation failed:**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CFGFWK-72020: JBoss server name cannot be empty.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

---

**CFGFWK-72021: JBoss configuration has not been read.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72022: The name or type {1}:{0} can not be null.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72023: The requested type {0} is not supported.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72024: The {0} with name {1} was not found.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72025: The requested {0}:{1} cannot be deleted.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72026: This config wrapper object from a previous session has been invalidated.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72027: validation failed for : {0}**

---

**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-72028: The property {0} is not allowed to be modified; use listAttributes() for supported types.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-72029: The specified property {0} is not writable.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-72030: The specified value {0} for {1} is of incompatible type or out of range.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-72031: The property {0} is not a supported attribute; use listAttributes() for supported types.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-72032: The property {0} is not a supported type; use listTypes() for supported types.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration



---

**CFGFWK-72033: The requested type {0} is not supported.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72034: The specified type is read-only.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72035: The requested {0}:{1} can not delete.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72036: A valid JBoss server name or absolute server directory path must be provided.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72037: Invalid prefix obtained from properties file**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72038: JBOSS\_HOME {0} is not a valid JBoss installation!**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72039: Duplicate Server listen ports exist in your cell configuration.**

---

**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-72040: The {0} must be specified.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-72041: The following must be specified:**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-72042: The {0} and {1} do not match.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-72043: The {0} must be an integer.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-72044: The selected data sources do not share any common database drivers. The wizard will deselect data sources to allow selection of compatible drivers.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

---

**CFGFWK-72045: The selected component schemas do not share any common database drivers. The wizard will deselect component schemas to allow selection of compatible drivers.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72046: The property {0} is not valid; use listAttributes() or listTypes() for supported attributes and types.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72047: The specified value {0} is not supported or is invalid!**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72048: The value of attribute {0} is not allowed to be read.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72049: The requested operation is not allowed.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72050: and more validation errors ...**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**CFGFWK-72051: Server listen ports in your cell configuration conflict with ports in use by active processes on this host.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72055: Test Failed!**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72056: Error getting connection information!**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72057: A connection was established to the database but no rows were returned from the test SQL statement.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72058: A valid server name must be provided.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72059: A server already exists with that name.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**CFGFWK-72060: Run OracleMWConfig.dumpStack() to view the full Exception**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-72061: The Configuration Wizard encountered an error loading the configuration from the server directory specified:**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-72062: The port value {0} must be in range of 0 to 65535.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-72063: The port value {0} must be integer.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-72064: Duplicate Server listen ports exist in your cell configuration.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-72065: Errors occurred while loading OracleHelp. Check log for details.**

**Cause:**

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**CFGFWK-72066: A valid server parent directory must be provided.**

---

**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-72067: The directory you selected is not a JBoss server which was configured by the Configuration Wizard.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-72070: The property "{0}" is not a supported attribute of the {1} type.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-72075: {0} assignment not supported.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-72076: Assignment Target not found for type: {0}**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-72077: Could not find {0} : {1}**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CFGFWK-72079: The assign of {0}:{1} to {2} failed**  
**Cause:**

---

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CFGFWK-72080: The unassign of {0}:{1} from {2} failed**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Configuration





---

## CLONE-27010 to CLONE-28400

**CLONE-27010: One or more ADF Connection types for {0} are not supported and will not be included in the moveplan.xml.**

**Cause:** One or more ADF Connection MBean does not provide the movableProperty annotation for at least one attribute.

**Action:** Validate that all ADF Connection MBean in your application have at least one property with movableProperty annotation with a value of "true".

**Level:** 1

**Type:** WARNING

**Impact:** Other

**CLONE-27020: ADF Connection MBean {0}.{1} is read only. Changes for this ADF Connection will not be applied.**

**Cause:** The ADF Connection MBean is read only.

**Action:** Validate that your application is configured with a writable Oracle MDS.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**CLONE-27100: Application {0} does not have ADF Connection MBean properties.**

**Cause:** Application {0} does not have ADF Connection MBeans.

**Action:** Validate that the ADF web application module's web.xml was configured for ADF Connection MBeans or if the application does not have any ADF Connections.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**CLONE-27500: No Move Plan available.**

**Cause:** Either ADF T2P plugin copy command failed, or the file is missing or corrupted.

**Action:** Validate that the Move Plan is valid after extraction from the copy command result.

**Level:** 1

**Type:** WARNING

---

**Impact:** Other

**CLONE-28000: Unable to apply ADF Connection properties for Application "{0}"**

**Cause:** This could be caused by an invalid Oracle MDS configuration in your application or a failure while attempting to apply attributes using JMX.

**Action:** Please validate that the application is configured with writable Oracle MDS.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**CLONE-28400: No ADF Connection MBean with name {0}**

**Cause:** OBJECT\_NAME\_PROPERTY field for mbean object name might be changed accidentally.

**Action:** Use the value of OBJECT\_NAME\_PROPERTY from other attributes under the same ADF Connection MBean in Move Plan to correct the wrong one.

**Level:** 1

**Type:** WARNING

**Impact:** Other

---

## CONF-30000 to CONF-35141

**CONF-30000: Error creating Management Admin Server.**

**Cause:** Oracle Instance directory {0} already exists.

**Action:** Provide a valid instance home path.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30001: Error creating Management Admin Server.**

**Cause:** {0}

**Action:** See the log for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30002: Error creating AS Component {0} of type {1}.**

**Cause:** {0}

**Action:** See the log for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30003: Error creating AS Component {0} of type {1}.**

**Cause:** {0}

**Action:** See the log for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30004: Error creating routing relationship to provider.**

**Cause:** An internal error has occurred.

**Action:** See the log for more information.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**CONF-30005: Error creating routing relationship to provider. Relation {0} already exists.**

**Cause:** An internal error has occurred.

**Action:** See the log for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30006: Timed out while waiting for Management Admin Server to start.**

**Cause:** The process is taking more time or not listening at this time.

**Action:** See the log for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30007: Management Admin Server appears to be unavailable.**

**Cause:** {0}

**Action:** Make sure that the admin server is running and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30008: Error creating routing relationship. Invalid user or provider components. User:{0}. Provider:{1}.**

**Cause:** The user or provider components are not valid.

**Action:** Make sure that the user and providers are valid components.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30009: Cannot create Application Server. OracleInstance directory {0} already exists.**

**Cause:** The oracle instance home exists

**Action:** Choose a different oracle instance home

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30010: An error occurred while provisioning an AS Instance (oracleInstance:{0} instanceName:{1}).**

**Cause:** {0}

**Action:** See log for more information.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30011: Unable to access the Process Control Service.**

**Cause:** Process Control Service is not available

**Action:** Try again after the process control service is available

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30012: Error occurred while starting {0} of type {1} in AS Instance {2}. See internal exception for details.**

**Cause:** Internal error has happened.

**Action:** See log for more details

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30013: Error occurred while stopping {0} of type {1} in AS Instance {2}. See internal exception for details.**

**Cause:** Some internal error has happened

**Action:** See error logs for more options

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30014: An unknown exception was generated while executing the configuration workflow. See internal exception for more details.**

**Cause:** Workflow internal exception

**Action:** See logs for more information

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30015: Operation to provision an AS Instance (Instance Name:{0} Instance Home: {1}) timed out.**

**Cause:** Timeout exception has happened

**Action:** See logs for more information

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30016: Failed to start an AS Instance (oracle instance:{0}, oracle home:{1}).**

**Cause:** {0}

---

**Action:** See logs for more details

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30017: Error creating routing relationship. Relationship details { User:{0} Provider:{1} RelationshipName:{2} }.**

**Cause:** {0}

**Action:** See logs for more details

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30018: Error creating AccessPoint {0}.**

**Cause:** {0}

**Action:** See logs for more details

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30019: Unable to obtain the DeploymentManager. Deployment URI:{0}**

**Cause:** Connected Deployment manager could not be found.

**Action:** See logs for more details

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30020: Error deploying a J2EE Application. See internal exception for details.**

**Cause:** Internal Exception

**Action:** See logs for more details

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30021: Unable to locate the target for deployment.Target: {0}**

**Cause:** The deployment target does not exist

**Action:** Make sure that the target exists

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30022: Error creating UnmanagedNetworkDevice {0}.**

**Cause:** {0}

**Action:** See logs for more details

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30023: Error updating metric rule {0}.**

**Cause:** {0}

**Action:** See logs for more details

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30024: Error Executing asctl command through ASconfig: {0}.**

**Cause:** {0}

**Action:** See logs for more details

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30025: Unable to locate the endpoint - {0}.**

**Cause:** The specified end point does not exist

**Action:** Specify a valid end point

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30026: Failed to start a MAS Transaction.**

**Cause:** {0}

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30027: Failed to commit a MAS Transaction.**

**Cause:** {0}

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30028: Failed to roll back a MAS Transaction.**

**Cause:** {0}

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**CONF-30029: Failed to register an LDAP Server as an unmanaged topology node.**

**LDAP Server name:**{0} **LDAP Server type:**{1}

**Cause:** {0}

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30030: Invalid LDAP Server Name. Specify a valid LDAP server name and try again.**

**Cause:** Invalid LDAP server

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30031: Failed to register an LDAP Server as an unmanaged topology node.**

**Cause:** Invalid LDAP Server Type {0}.

**Action:** Specify one of the following valid supported LDAP Server Types:

'UnmanagedLDAPServer', 'UnmanagedOIDComponent',  
'UnmanagedActiveDirectory'

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30032: Error while registering database schema {0} to MAS .**

**Cause:** {0}

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30033: Error while calling configuration assistant {0}**

**Cause:** {0}

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30034: Error occurred while trying restart {0} of type {1} in AS Instance {2}. See internal exception for details.**

**Cause:** {0}

**Action:** See logs for more details.



---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30035: Failed to create a routing relationship to provider.**

**Cause:** {0}

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30036: Error generating Provisioning workflow**

**Cause:** Invalid FarmName

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30037: Error updating Bootstrap Credentials for IDStore**

**Cause:** {0}

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30038: Error updating Bootstrap Credentials for IDStore**

**Cause:** {0}

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30039: Error creating a Synchronized Group {0}.**

**Cause:** {0}

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30051: Error locating the ASInstance in the Farm with the given canonical path {0}**

**Cause:** {0}

**Action:** Provide the correct canonical path for the ASInstance

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**CONF-30052: Error locating the ASJ2EEApplication in the Farm with the given canonical path {0}**

**Cause:** {0}

**Action:** Provide the correct canonical path for the ASJ2EEApplication

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30053: Error locating the SystemComponent in the Farm with the given canonical path {0}**

**Cause:** {0}

**Action:** Provide the correct canonical path for the SystemComponent

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30054: Error obtaining InstanceHome location for {0}**

**Cause:** {0}

**Action:** See logs for more details

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30055: Error obtaining the OracleHome associated with {}**

**Cause:** {0}

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30056: TopologyNode {0} does not exist in farm.**

**Cause:** Invalid canonical path

**Action:** Provide a valid canonical path

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30057: An exception was generated while executing the provisioning workflow.**

**Cause:** {0}

**Action:** See logs for more details

**Level:** 1

---

**Type:** ERROR  
**Impact:** Configuration  
**CONF-30060: Error while calling validation assistant {0}**  
**Cause:** {0}  
**Action:** See log for more details.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CONF-30090: The given node is not a valid MDS schema. {0}**  
**Cause:** Invalid MDS schema  
**Action:** Provide a valid MDS Schema.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CONF-30091: Error deploying a J2EE Application. {0}**  
**Cause:** Internal Exception  
**Action:** See logs for more details.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CONF-30092: The process has been interrupted**  
**Cause:** The process has been interrupted  
**Action:** See logs for more details.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CONF-30093: The application archive could not be loaded as a deployable object**  
**Cause:** Some deployment Exception has happened  
**Action:** See logs for more details.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**CONF-30094: File not found. The specified file {0} is not found.**  
**Cause:** File is not present  
**Action:** See logs for more details.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

---

**CONF-30095: Configuration Exception happened. See the embedded exception for more details.**

**Cause:** Internal Exception

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30096: Unable to get the deployment configuration.**

**Cause:** The application archive {0} is a invalid archive.

**Action:** Check the archive and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30097: Unable to locate application archive. "{0}"**

**Cause:** The location to archive is not correct.

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30098: Unable to obtain the DeploymentManager. Deployment URI:{0}**

**Cause:** Internal Exception

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30099: Unable to locate the target for deployment. Target: {0}**

**Cause:** Invalid deployment target

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30100: Error creating an Oracle Load Balancer {0}.**

**Cause:** {0}

**Action:** See logs for more details

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-30101: Error associating ASInstance(s) with an Oracle Load Balancer {0}.**

---

**Cause:** {0}  
**Action:** Specify valid ASInstances.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CONF-30111: Error while registering unmanaged SSO Server to MAS .**

**Cause:** {0}  
**Action:** See logs for more details.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CONF-30112: Failed to stop an AS Instance (oracle instance:{0}).**

**Cause:** {0}  
**Action:** See logs for more details  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CONF-30113: See logs for more details.**

**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CONF-30114: See logs for more details.**

**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CONF-30115: Error storing entries in Credential Store**

**Cause:** {0}  
**Action:** See logs for more details.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CONF-30116: Error retrieving entries from Credential Store**

**Cause:** {0}  
**Action:** See logs for more details.

---

**Level: 1**  
**Type: ERROR**  
**Impact: Configuration**  
**CONF-30117: Error deleting entries from Credential Store**  
**Cause:** {0}  
**Action:** See logs for more details.

**Level: 1**  
**Type: ERROR**  
**Impact: Configuration**  
**CONF-30121: Error assigning AccessPoint {0} to {1}**  
**Cause:** {0}  
**Action:** See logs for more details.

**Level: 1**  
**Type: ERROR**  
**Impact: Configuration**  
**CONF-35001: Invalid host value provided to config framework.**  
**Cause:** Invalid host value provided to config framework.  
**Action:** Provide a valid host value to config framework

**Level: 1**  
**Type: ERROR**  
**Impact: Configuration**  
**CONF-35002: Invalid port value provided to config framework.**  
**Cause:** Invalid port value provided to config framework.  
**Action:** Provide a valid port value to config framework

**Level: 1**  
**Type: ERROR**  
**Impact: Configuration**  
**CONF-35003: Error while creating the domain.**  
**Cause:** An internal operation has failed.  
**Action:** See logs for more details.

**Level: 1**  
**Type: ERROR**  
**Impact: Configuration**  
**CONF-35004: Error while creating Managed Server.**  
**Cause:** An internal operation has failed: {0}  
**Action:** See logs for more details.

**Level: 1**  
**Type: ERROR**

---

**Impact:** Configuration

**CONF-35005: Error while starting the domain.**

**Cause:** An internal WLST operation has failed.

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35006: Unable to connect to the AdminServer.**

**Cause:** An internal operation has failed:{0}

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35007: Error while setting control flag {0}.**

**Cause:** An internal operation has failed: {0}

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35009: Error while stopping the domain.**

**Cause:** An internal operation has failed: {0}

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35010: Error while deploying the Application {0} .**

**Cause:** An internal operation has failed: {0}

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35011: Error while starting the Application {0} .**

**Cause:** An internal operation has failed: {0}

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35012: Error while stopping the Application {0} .**

---

**Cause:** An internal operation has failed: {0}  
**Action:** See logs for more details.

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CONF-35015: Error while creating Group {0} .**  
**Cause:** An internal operation has failed: {0}  
**Action:** See logs for more details.

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CONF-35020: Error while creating DataSource {0} .**  
**Cause:** An internal operation has failed: {0}  
**Action:** See logs for more details.

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CONF-35025: Error while creating JMSResource {0}.**  
**Cause:** An internal operation has failed: {0}  
**Action:** See logs for more details.

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CONF-35030: Error while creating Authenticator {0}.**  
**Cause:** An internal operation has failed: {0}  
**Action:** See logs for more details.

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CONF-35035: Error while executing WLS script located at {0}.**  
**Cause:** An internal operation has failed: {0}  
**Action:** See logs for more details.

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**CONF-35040: Error while creating Network Channel {0}.**  
**Cause:** An internal operation has failed: {0}  
**Action:** See logs for more details.



---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35075: Error creating ASInstance {0}.**

**Cause:** An internal operation has failed: {0}

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35076: Error creating ASComponent {0}.**

**Cause:** An internal operation has failed: {0}

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35080: Error Applying template.**

**Cause:** A WLST Error occurred: {0}

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35081: Error Applying template.**

**Cause:** Domain Home cannot be empty.

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35082: Error creating Domain {0}.**

**Cause:** A WLST Error occurred.

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35085: Error creating Cluster {0}.**

**Cause:** See logs for more details.

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**CONF-35090: Error while starting the domain.**  
**Cause:** Starting the Admin\_Server timed out.  
**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35091: Error while starting the domain.**  
**Cause:** An error occurred while starting the domain.  
**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35092: Error Setting target for Startup class {0}.**  
**Cause:** An internal error has occurred.  
**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35095: Error setting target for Shutdown class {0}.**  
**Cause:** An internal error has occurred.  
**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35100: Error starting and enrolling Node Manager**  
**Cause:** An internal operation has failed.  
**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35105: Error Creating Multi Data Source {0}**  
**Cause:** An internal operation has failed  
**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35110: Error Extending Targets With JRF Template.**

---

**Cause:** WLST Error. {0}  
**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35111: Error Extending Targets With JRF Template.**

**Cause:** Domain Home cannot be empty.

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35115: Error Setting target to Managed Server {0}.**

**Cause:** Check the logs for details.

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35120: Error Starting Managed Server {0}.**

**Cause:** An internal error has occurred : {0}

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35122: Number Format Exception thrown when trying to get nodemanager port.**

**Cause:** The Nodemanager Listen port entry is not present in the nodemanager.properties file or it is not set to numeric value.

**Action:** Add the Nodemanager port (for example, ListenPort=5556) to the nodemanager.properties file and press Retry button to continue the configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35124: Stage Modes 'EXTERNAL\_STAGE' and 'NOSTAGE' cannot be set simultaneously.**

**Cause:** Both stage modes 'EXTERNAL\_STAGE' and 'NOSTAGE' have been set.

**Action:** Use only 'EXTERNAL\_STAGE' or 'NOSTAGE' mode for deployment

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**CONF-35126: Node Manager Listen Port is set to a negative number.**

**Cause:** Node Manager Listen Port is set to a negative number.

**Action:** Add the Nodemanager port(Eg: ListenPort=5556) to the nodemanager.properties file and press Retry button to continue the configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35128: Unable to set Attribute 'StartScriptEnabled'.**

**Cause:** Unable to set Attribute 'StartScriptEnabled' since the NodeManager is already running.The installer needs to set it to 'true'

**Action:** Stop the Node Manager and retry the installer.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35130: Unable to set Attribute 'StartScriptEnabled'.**

**Cause:** Unable to set Attribute 'StartScriptEnabled' since the NodeManager is already running.The installer needs to set it to 'true'

**Action:** Stop the Node Manager and retry the installer.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35132: Unable to set Attribute 'NativeVersionEnabled'.**

**Cause:** Unable to set Attribute 'NativeVersionEnabled' since the NodeManager is already running.The installer needs to set it to 'true'

**Action:** Stop the Node Manager and retry the installer.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35134: Unable to set Attribute 'NativeVersionEnabled'.**

**Cause:** Unable to set Attribute 'NativeVersionEnabled' since the NodeManager is already running.The installer needs to set it to 'true'

**Action:** Stop the Node Manager and retry the installer.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35136: Error while starting the Managed Server.**

**Cause:** An interanal WLST operation has failed.

**Action:** See logs for more details.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**CONF-35137: Managed Server {0} started in FAILED state.**

**Cause:** An internal error has occurred : {0}

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35140: Managed Server shutdown command Failed.**

**Cause:** An internal error has occurred : {0}

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**CONF-35141: Managed Server {0} shutdown timed out.**

**Cause:** An internal error has occurred : {0}

**Action:** See logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration



---

## DFW-40004 to DFW-40204

**DFW-40004: The requested diagnostic dump {0} is unknown.**

**Cause:** The diagnostic dump {0} has either not been registered or the given name is incorrect.

**Action:** Ensure that a valid dump name is specified.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**DFW-40005: The mandatory dump argument {0} is not specified.**

**Cause:** A request to execute a dump was made without specifying all mandatory arguments.

**Action:** Ensure that all mandatory arguments are specified.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**DFW-40006: ignoring dump argument {0} as it is not defined for diagnostic dump {1}**

**Cause:** The dump does not accept the specified argument.

**Action:** Ensure that only arguments defined by the dump are specified.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Programmatic

**DFW-40007: The diagnostic dump argument {0} should be of type {1}.**

**Cause:** The specified argument is of the wrong type.

**Action:** Ensure that arguments are of the correct type.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**DFW-40008: failed to execute diagnostic dump {0}**

**Cause:** An error occurred during the execution of the dump.

**Action:** Check process logs for more information.

---

**Level:** 1

**Type:** WARNING

**Impact:** Process

**DFW-40009: failure creating dump file**

**Cause:** An error occurred creating a dump file

**Action:** See base error for root cause and check process logs for more information.

**Level:** 1

**Type:** WARNING

**Impact:** Process

**DFW-40100: failed to create ADR Base directory {0}**

**Cause:** An error occurred whilst attempting to create the ADR Base directory required to store captured diagnostics data. This may be due to file or process permissions.

**Action:** Check that the process has permission to create the directory.

**Level:** 1

**Type:** ERROR

**Impact:** Operating System

**DFW-40102: failure during incident rule processing of incident {0}**

**Cause:** During the processing of the incident rules an error occurred.

**Action:** See base error for root cause and check process logs for more information.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**DFW-40103: failed to execute dump during creation of incident {0}**

**Cause:** An error occurred during the execution of a diagnostic dump.

**Action:** See base error for root cause and check process logs for more information.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**DFW-40105: failed to execute dump {0} during creation of incident {1}**

**Cause:** An error occurred during the execution of the dump.

**Action:** See base error for root cause and check process logs for more information.

**Level:** 1

**Type:** WARNING

**Impact:** Process

**DFW-40106: failed to load diagnostic rules schema {0}**

**Cause:** The diagnostic rules schema could not be loaded.

**Action:** Check that the specified schema exists and is readable.



---

**Level:** 1

**Type:** WARNING

**Impact:** Process

**DFW-40107: failed to parse diagnostic rules**

**Cause:** The diagnostic rules do not conform to the schema.

**Action:** Fix the diagnostic rules XML to make the rules valid.

**Level:** 1

**Type:** WARNING

**Impact:** Process

**DFW-40108: invalid diagnostic rules document**

**Cause:** The diagnostic rules document has invalid content.

**Action:** See base error for root cause and check process logs for more information.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**DFW-40109: failed to write and register incident {0} readme file with ADR**

**Cause:** An issue occurred during the registration of the readme file. This does not impact the associated diagnostic dump data.

**Action:** Check that the process writing the readme file has sufficient privileges.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Process

**DFW-40110: failure parsing ADRCI XML output**

**Cause:** The XML returned by the ADRCI show incidents command could not be parsed.

**Action:** Check the process logs for more information.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**DFW-40111: failed to determine incident id and path from adrci output "{0}"**

**Cause:** There was an error executing the command to create an incident using ADRCI.

**Action:** Ensure that command line tool "adrci" can be executed from the command line.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DFW-40112: failed to execute the adrci commands "{0}"**

---

**Cause:** There was an error executing adrci commands; the following errors have been found "{0}"

**Action:** Ensure that command line tool "adrci" can be executed from the command line.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**DFW-40113: failed to execute adrci commands; adrci returned "{0}"**

**Cause:** There was an error executing adrci commands.

**Action:** Ensure that command line tool "adrci" can be executed from the command line.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**DFW-40114: The ADR Product ID exceeds the maximum length {0}.**

**Cause:** The given ADR Product ID is too long.

**Action:** The ADR Product ID will automatically be truncated. No further action is required.

**Level:** 1

**Type:** WARNING

**Impact:** Files

**DFW-40115: The ADR Instance ID exceeds the maximum length {0}.**

**Cause:** The given ADR Instance ID is too long.

**Action:** The ADR Instance ID will automatically be truncated. No further action is required.

**Level:** 1

**Type:** WARNING

**Impact:** Files

**DFW-40116: failure creating incident**

**Cause:** An error occurred during the creation of an incident.

**Action:** See base error for root cause and check process logs for more information.

**Level:** 1

**Type:** WARNING

**Impact:** Process

**DFW-40118: ADR incident creation is disabled; incident not created.**

**Cause:** Diagnostics Framework was unable to initialize ADR, resulting in ADR creation being disabled.

**Action:** Check the process logs for more information on why ADR could not be initialized.

**Level:** 1

---

**Type:** NOTIFICATION

**Impact:** Process

**DFW-40119: file {0} cannot be added to incident {1} as it exceeds the maximum filename length of {2} characters**

**Cause:** The specified filename length exceeds the maximum allowed by ADR.

**Action:** Specify a filename whose length does not exceed the maximum allowed length.

**Level:** 1

**Type:** WARNING

**Impact:** Files

**DFW-40121: failure creating incident from WLDF notification**

**Cause:** An error occurred whilst attempting to create an incident.

**Action:** See the base exception for details, and check the process logs for more information.

**Level:** 1

**Type:** WARNING

**Impact:** Process

**DFW-40123: file {0} is not registered with incident {1}**

**Cause:** The specified filename is not associated with the incident

**Action:** Specify the name of a file that is registered with the incident

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Programmatic

**DFW-40125: incident flood controlled with Problem Key "{0}"**

**Cause:** The specified Problem Key is under flood control, due to the volume of incidents with that Problem Key exceeding the maximum incident count.

**Action:** Inspect the reason for the creation of incidents with the specified Problem Key and resolve the issue.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**DFW-40126: incident with Problem Key "{0}" could not be created due to lack of available disk space for incidents; configured maximum is {1} bytes and used is {2} bytes**

**Cause:** The incident with the specified Problem Key could not be created due to lack of available disk space allocated for incidents.

**Action:** Purge old incidents or increase the maximum allowed disk space for incidents in dfw\_config.xml.

**Level:** 1

**Type:** WARNING

**Impact:** Other

---

**DFW-40200: failed to load diagnostics configuration schema {0}**

**Cause:** The diagnostics configuration schema could not be loaded. See base exception for root cause

**Action:** Check that the specified schema exists and is readable.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**DFW-40201: failed to parse diagnostics configuration**

**Cause:** The diagnostics configuration document does not conform to the schema.

**Action:** Fix the diagnostic configuration XML to make the configuration valid.

**Level:** 1

**Type:** WARNING

**Impact:** Process

**DFW-40203: failure initializing diagnostics security context**

**Cause:** An error occurred initializing the internal Diagnostic Framework security context.

**Action:** See the base exception for details, and check the process logs for more information.

**Level:** 1

**Type:** WARNING

**Impact:** Process

**DFW-40204: invalid ADR Home path {0}**

**Cause:** The specified ADR Home is not a valid path.

**Action:** Specify a valid ADR Home path of the form diag/<productType>/<productId>/<instanceId>

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

---

## DIP-00003 to DIP-87002

**DIP-00003: Error in closing Oracle Internet Directory server connection.**

**Cause:** An unexpected error occurred in closing of Oracle Internet Directory connection.

**Action:** Make sure Oracle Internet Directory host, port, user, password values are correct or server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**DIP-00004: Error in connecting to Oracle Internet Directory Server.**

**Cause:** Could not connect to Oracle Internet Directory server.

**Action:** Contact oracle support.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**DIP-00006: Error while DIP schema creation.**

**Cause:** Failed to create DIP schema due to invalid file content.

**Action:** Contact oracle support.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**DIP-00007: Error while creating RootOracleContext.**

**Cause:** Failed to create DIP root oracle context with invalid file or invalid file content.

**Action:** Contact oracle support.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**DIP-00009: Error while creating template profiles.**

**Cause:** Failed to create DIP template sync profiles due to invalid file content.

**Action:** Contact oracle support.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**DIP-00010: Error in modifying attributes.**

**Cause:** Update of attribute {0} of {1} by LDAP operation.

**Action:** Contact oracle support.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-00013: Error in reading DIP Schema details.**

**Cause:** Invalid query for container DN {0} from DIP schema.

**Action:** Contact oracle support.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-00014: Error in setting DIP password.**

**Cause:** Failed to set DIP password in CSF

**Action:** Contact oracle support.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-00019: Errors occurred while performing LDAP operation**

**Cause:** User has no access rights to modify particular Distinguished Name or attribute to modify does not exist.

**Action:** Contact oracle support.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-00020: obtaining LDAP connection failed in attempt number :{0} - Retrying**

**Cause:**

**Action:**

**Level:** 1

**Type:** WARNING

**Impact:** Network

**DIP-00021: maximum LDAP connection retry count reached.**

**Cause:**

**Action:**

**Level:** 1

---

**Type:** WARNING

**Impact:** Network

**DIP-00022: Connection to LDAP server failed.**

**Cause:** Directory Integration Platform Server was not able to connect to the LDAP server.

**Action:** Contact oracle support.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**DIP-10004: Error in closing newly created context.**

**Cause:** Unable to close the connection with the directory Server.

**Action:** Check the server is running properly.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**DIP-10006: Error in executing reconciler : {0}**

**Cause:** Execution of reconciliation failed in agent thread

**Action:** Check the log file and if required contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**DIP-10008: error in mapping engine {0} .**

**Cause:** Errors occurred in map engine it might have caused by errors in map rule.

**Action:** Validate the profile to confirm that the map rules are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10009: error in proxy connection through the profile.**

**Cause:** Failed to connect to Oracle Internet Directory through the proxy.

**Action:** Check if profile (the proxy) is running properly

**Level:** 1

**Type:** ERROR

**Impact:** Network

**DIP-10010: error in setting legacy ldap control**

**Cause:** Failed to set up the legacy ldap control

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Network

**DIP-10011: error in updating the status of profile execution.**

**Cause:** Failed to connect to Oracle Internet Directory or update or metrics data.

**Action:** Check if odip group has permissions to update the container 'cn=subscriber profile,cn=changelog subscriber,cn=Oracle Internet Directory'.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10013: Exception**

**Cause:** Unknow errors occurred in execution.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10017: Directories are in a inconsistent state,entry reconcile {0} is inconsistent.**

**Cause:** Tried to add-delete or add-modify operation for same entry.

**Action:** Start the reconciler or delete that entry from the connected directory so that it gets synchronized properly at the next interval.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10025: reader initialization failed.**

**Cause:** Failed connect to the source directory during synchronization.

**Action:** Check the connection details of the source directory for synchronization profile.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10028: Interrupted while waiting to retry the profile execution.**

**Cause:** Another job has interrupted during retry process.

**Action:** Restart the Directory Integration Platform server.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**DIP-10030: Target directory is unable to process this entry: {0}.**

**Cause:** Failed to make change in the directory, might have caused by error in the entry.

**Action:** Check the log file for details.

**Level:** 1



---

**Type:** ERROR

**Impact:** Data

**DIP-10038: Incorrect Format: first Line after TAG should be an <attribute:value> pair.**

**Cause:** Config file is not in proper format.

**Action:** Correct the format of config file.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10045: FATAL ERROR:Connect Information Format {0} is Incorrect!!**

**Cause:** Wrong format of connection information

**Action:** Give the connection information in proper format

**Level:** 1

**Type:** ERROR

**Impact:** Network

**DIP-10046: Error in opening logFile: {0}.**

**Cause:** Failed to create a log file.

**Action:** Check permissions of the directory and the file path specified in j2ee-logging.xml file is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**DIP-10047: Error Reading : {0} : For Mode : {1} : Exception : {2}.**

**Cause:** Failed to initialize the last applied change key.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10048: exception in reading netdescription String.**

**Cause:** Failed to initialize destination connector.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10066: scheduling interval not specified.**

**Cause:** Scheduler interval was not specified in the properties file while creating a profile.

**Action:** Specify the scheduling interval in the profile.

**Level:** 1

---

**Type:** ERROR

**Impact:** Data

**DIP-10072: Unknown interface Type specified - {0}.**

**Cause:** Interface type specified in the config file was not valid.

**Action:** Specify the supported interface type.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10074: Class Not Found: {0}**

**Cause:** Failed to load the class specified in the synchronization profile configuration.

**Action:** Check the class name specified in the synchronization profile configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10075: Error in reading mapping.**

**Cause:** Exceptions thrown while reading mapping information.

**Action:** Confirm that the mapping rules are correctly specified in the profile. validate the profile mapping rules using the manageSyncProfile command.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10076: Error in reading reconciler information.**

**Cause:** Exceptions occurred while reading reconciliation information.

**Action:** Confirm that the reconciler information is correctly specified along with mapping rules and reconciliation attributes are properly specified in the profile. Check the documentation for details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10077: Exception encountered in forming agent execution command.**

**Cause:** Exception is thrown while initializing execution command.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**DIP-10078: Exception in initializing profile.**

**Cause:** failed to initialize the profile.

**Action:** Check if the contents of the profile are correct in properties file.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10079: Exception in reading profile attributes.**

**Cause:** Failed to read profile information

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10090: Invalid reduceFilterTime default reduceFilterTime will be 0.**

**Cause:** Invalid reduce filter time parameter specified in profile.

**Action:** reduceFilterTime attribute should have integer value. Modify the profile with proper value for the additional config attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10091: Not able to get reduceFilterTime default reduceFilterTime will be 0.**

**Cause:** Reduce filter time parameter is not specified in the additional config parameter.

**Action:** reduceFilterTime attribute should have integer value. Modify the profile with proper value for the additional config attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**DIP-10100: Could not add version 1.0 Profile. Initialization failure : {0}.**

**Cause:** Failed to add version 1.0 profile in the provisioning list.

**Action:** Check the value of all properties in the properties file.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10101: Could not add version 2.0 Profile. Initialization failure : {0}.**

**Cause:** Failed to add version 2.0 profile in the provisioning list.

**Action:** Check the value of all properties in the properties file.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10103: Error in getting last change number from Oracle Internet Directory.**

**Cause:** Exceptions thrown while reading last change number from Oracle Internet Directory.

---

**Action:** Check the exception trace and confirm that change log has been enabled in Oracle Internet Directory.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10104: Error reading reconciliation profile.**

**Cause:** Details for reconciliation could not be read properly from the profile.

**Action:** Check the reconciliation information specified in the profile.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10105: Error in refreshing the Profile : {0}**

**Cause:** Exception thrown while refreshing the profile.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10106: Error in scheduler initialization.**

**Cause:** Exceptions thrown while initializing the scheduler

**Action:** Check the server config parameters for details check the log file.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**DIP-10107: Error while setting the privacy control in ldap context.**

**Cause:** Exceptions thrown while setting the control in the directory server in the scheduler

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**DIP-10108: Exception in adding version 2 profile.**

**Cause:** Failed to add version 2 profile in the prov list

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10109: Exception in adding provisioning profile.**

**Cause:** Failed to add provisioning profile for scheduling

---

**Action:** Check that the profile is not already scheduled else check the log file.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10110: Exception encountered in reconnecting to Oracle Internet Directory.**

**Cause:** Failed to connect to Oracle Internet Directory

**Action:** Check OID host and port details in server configuration and also verify that OID server is running properly

**Level:** 1

**Type:** ERROR

**Impact:** Network

**DIP-10116: Not able to add version 1 profile.**

**Cause:** Failed to add version 1 profile in the provisioning job list.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**DIP-10117: Security encryption algorithm not supported in the library.**

**Cause:** Given security encryption algorithm not supported.

**Action:** Check the encryption algorithm is given properly.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**DIP-10122: Scheduler error.**

**Cause:** Exceptions thrown in synchronization profile scheduler.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**DIP-10123: Scheduler interrupted**

**Cause:** Scheduler was interrupted by another running thread.

**Action:** Try restarting the DIP server.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**DIP-10124: Error reading profiles for scheduling.**

**Cause:** Exceptions thrown while reading the profile information.

---

**Action:** Check that the profile specified is indeed present in the Oracle Internet Directory server.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10132: Exception in adding profile**

**Cause:** Exceptions thrown while adding profile in the list.

**Action:** Check that profile is not already scheduled.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10133: Exception encountered in reconnecting to Oracle Internet Directory.**

**Cause:** Exception is thrown while connecting to OID

**Action:** Check Oracle Internet Directory host and port details and it is running properly

**Level:** 1

**Type:** ERROR

**Impact:** Network

**DIP-10139: Error in schedulling.**

**Cause:** Generic exception was thrown while scheduling provisioning profiles.

**Action:** Check if profile is valid or not.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**DIP-10145: Error in configuring logging.**

**Cause:** Invalid debug level specified in DIP server configuration set.

**Action:** Correct the debug level specified in DIP server configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**DIP-10146: Connection to directory server failed, will retry after {0} ms.**

**Cause:** Failed to connect to directory server.

**Action:** Check the host and port of directory server and also check it is running.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**DIP-10184: Error reading entrydn {0}.**

**Cause:** Failed to read the target dn entry.

---

**Action:** Check if the entry exists in Target Directory Server.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10185: Error reading ObjectGUID.**

**Cause:** Error occurred while reading Object GUID of target dn.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10187: Error in adding user to domain admin group.**

**Cause:** Exceptions thrown while adding user to a group.

**Action:** Check log file for details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10188: Failed to read useraccountcontrol value.**

**Cause:** Exception thrown while reading user account control attribute.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10191: Error in getting the GUID of the entry. Skipping**

**Cause:** Errors occurred while reading GUID of the entry.

**Action:** Check log file for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10192: Error in updating the status for user with GUID : {0}.**

**Cause:** Errors occurred while updating the user entry with GUID.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10193: NoSuchElementException in getting next entry.**

**Cause:** Errors occurred while getting the next item

**Action:** No action required.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10194: Unknown exception**

**Cause:** Unknown exception

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10195: Unable to obtain local host name.**

**Cause:** Failed to get the host name and ip address.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**DIP-10196: Error in parsing the modifytimestamp.**

**Cause:** Errors occurred while reading modifytimestamp attribute

**Action:** Check the modifytimestamp is in proper format for the profile.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10200: Error in getting the local Hostname : {0}.**

**Cause:** Failed to get the host name and ip address.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**DIP-10201: Directory Context Exception:**

**Cause:** Exception is thrown while searching on the directory context

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**DIP-10202: LDAP Context Exception:**

**Cause:** Exception is thrown while searching on the ldap context

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR



---

**Impact:** Configuration

**DIP-10203: LDAP CommuncationException.**

**Cause:** Communication failure with directory server.

**Action:** Check the host and port detail of directory server and it is running.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**DIP-10205: NamingException.**

**Cause:** Errors occured while connecting to directory server.

**Action:** Check log file for details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10206: LDAP AuthenticationException.**

**Cause:** Failed to bind to directory server

**Action:** Check the credential information of directory server.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**DIP-10218: Exception in calculating new DN during MODDN operation.**

**Cause:** Errors occured while performing modRDN operation.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10219: Exception creating entry : {0}.**

**Cause:** Failed to create an entry in the directory server.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10220: Exception while performing delete operation for entry : {0}.**

**Cause:** Failed while performing delete operation.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10221: Exception deleting entry : {0}.**

- 
- Cause:** Exception is thrown while deleting an entry  
**Action:** Contact Oracle Support Services.
- Level:** 1  
**Type:** ERROR  
**Impact:** Data
- DIP-10223: Exception in looking for: {0}.**  
**Cause:** Exception is thrown while searching for an entry.  
**Action:** Contact Oracle Support Services.
- Level:** 1  
**Type:** ERROR  
**Impact:** Data
- DIP-10224: Exception while performing modify operation for entry : {0}.**  
**Cause:** Exception is thrown while performing modify operation.  
**Action:** Contact Oracle Support Services.
- Level:** 1  
**Type:** ERROR  
**Impact:** Data
- DIP-10225: Exception modifying entry : {0}.**  
**Cause:** Exception is thrown while modifying an entry  
**Action:** Contact Oracle Support Services.
- Level:** 1  
**Type:** ERROR  
**Impact:** Data
- DIP-10226: Exception doing ModRDN operation for entry : {0}.**  
**Cause:** Exception is thrown while performing mod RDN operation on an entry  
**Action:** Contact Oracle Support Services.
- Level:** 1  
**Type:** ERROR  
**Impact:** Data
- DIP-10238: Error in enumerating LDAP search result.**  
**Cause:** Failed whiled iterating over the search records.  
**Action:** Contact Oracle Support Services.
- Level:** 1  
**Type:** ERROR  
**Impact:** Data
- DIP-10239: Error initializing last applied timestamp.**  
**Cause:** Failed to apply last applied timestamp.  
**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10240: Create change record error.**

**Cause:** Failed while creating a change record.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10241: Error in LDAP search operation.**

**Cause:** Search operation caused errors.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10242: Error get next change.**

**Cause:** Errors occurred in retrieving next change record.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10246: MAPPING: exception in B64 Decoding.**

**Cause:** Failed while decoding attribute value

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**DIP-10247: Not able to construct DN.**

**Cause:** DIP Server was not able to construct the destination DN.

**Action:** Check the domain level mapping rules.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**DIP-10249: MAPPING: Mapping Domain Failed - DstChangeRecord : {0}**

**Cause:** Failed while trying to map to the destination change record

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Data

**DIP-10250: MAPPING: Mapping Domain Failed - setting DstChangeRecord to null.**

**Cause:** DIP Server was not able to map the source domain to the destination domain.

**Action:** Check the domain level mapping rules.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10253: Destination directory connection failed, retry count= {0}.**

**Cause:** Failed to connect to directory server.

**Action:** Check the host and port details of the directory server and check the directory server is running properly.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**DIP-10257: Exception in reconcile() in source subset criteria : {0}.**

**Cause:** Exception was thrown while searching for deleted entries.

**Action:** Check log files for details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10265: Source directory connection failed, retry count= {0}**

**Cause:** Failed to connect to source directory

**Action:** Check the host and port details of source directory and it is running properly

**Level:** 1

**Type:** ERROR

**Impact:** Network

**DIP-10266: Unable to check the entry in Source Directory.**

**Cause:** Failed to read entries in the source directory.

**Action:** Check the source directory server is running properly and also check its host and port details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10267: Unable to delete the entry : {0}.**

**Cause:** Failed to delete entry from the directory server

**Action:** Contact Oracle Support Services.

**Level:** 1

---

**Type:** ERROR

**Impact:** Data

**DIP-10268: Unable to do the search in destination directory.**

**Cause:** Failed while searching for entries in the destination directory.

**Action:** Check destination directory is running properly.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10269: Unable to do the search in source directory due to exception.**

**Cause:** Failed while searching for entries in the source directory server.

**Action:** Check source directory server is running properly.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10270: CommunicationException in PagedSearch.**

**Cause:** communication failure in Paged search.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**DIP-10271: Exception in getSearchResults().**

**Cause:** Search for entries caused exceptions.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10274: Unable to parse the source subset criteria {0} due to exception.**

**Cause:** DIP is failing while parsing the source subset criteria.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**DIP-10275: Unable to parse the target subset criteria due to exception.**

**Cause:** Failed while parsing the target subset criteria.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**DIP-10277: Unable to delete the entry : {0} as the binddn does not have permission to delete it.**

**Cause:** Failed Delete of an entry from the connected directory server.

**Action:** Check the permission of bind dn and password.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10284: Unable to check the Page Control Search support.**

**Cause:** Exception thrown while checking for the Page Control Search support.

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10285: Unable to get the Page Size Limit.**

**Cause:** Exception thrown while getting the Page Size Limit.

**Action:** Check the exception trace or or Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10501: Unable to add version 1.0 provisioning profile {0}.**

**Cause:** Directory Integration Platform was not able to add version 1.0 provisioning profile.

**Action:** Check the Directory Integration Server logs.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10502: Exception in adding version 2.0 profile : {0}**

**Cause:** Directory Integration Platform was not able to add version 2.0 provisioning profile.

**Action:** Check the server log.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10503: Exception in adding version 3.0 profile : {0}**

**Cause:** Directory Integration Platform was not able to add version 3.0 provisioning profile.

**Action:** Check the server log.

**Level:** 1

**Type:** ERROR

---

**Impact:** Data

**DIP-10504: Ignoring invalid profile**

**Cause:** Directory Integration Platform was not able to add it as the profile entry was invalid.

**Action:** Check the profile entry for Version 3.0.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10505: Scheduler: unable to add profile {0}, refer to log file.**

**Cause:** Directory Integration Platform tried to add a profile {0} but was not able to add it.

**Action:** Check the profile entry {0}.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**DIP-10506: Unable to retrieve update timestamp attribute.**

**Cause:** Directory Integration Platform was not successful in retrieving update timestamp attribute for one iteration of provisioning profile.

**Action:** Check the update timestamp attributes.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10507: Unable to instantiate the schema for Directory Integration Platform.**

**Cause:** The Directory Integration Platform schema was either invalid or not found.

**Action:** Check the Directory Integration Platform schema entry in Oracle Internet Directory.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**DIP-10508: Unable to get the update attributes for the provisioning profile {0}.**

**Cause:** Directory Integration Platform was not successful in retrieving the attribute of the provisioning profile - {0}.

**Action:** Check the profile entry in Oracle Internet Directory.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10509: Error in executing provisioning profile.**

**Cause:** Directory Integration Platform was not successful in provisioning all the data during this iteration for profile.

---

**Action:** Check the log files for the error.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**DIP-10510: Error in updating profile status.**

**Cause:** Directory Integration Platform was not successful in updating the profile status.

**Action:** Check the log files for the error.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10511: Error in initializing the classes for the provisioning profiles.**

**Cause:** Directory Integration Platform was not successful in initializing the classes for the prov profiles.

**Action:** Check the log files for the error.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**DIP-10512: Error in making a remote call to provisioning bean : {0}**

**Cause:** Directory Integration Platform was not successful making remote call to initialize provisioning bean.

**Action:** Check whether Directory Integration Platform Prov Bean is up in the Enterprise Manager.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**DIP-10513: Error while initializing the classes for enterprise scheduler : {0}**

**Cause:** Directory Integration Platform was not successful in initializing the classes for the enterprise scheduler.

**Action:** Check the Enterprise Scheduler Service runtime and metadata Enterprise Java Beans in the Enterprise Manager.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**DIP-10515: Enterprise Scheduler Service was not able to schedule all the jobs successfully {0}**

**Cause:** An error occurred while scheduling jobs in the ESS.

**Action:** Refer to the Enterprise Scheduler Service stack trace.

**Level:** 1

**Type:** ERROR



---

**Impact:** Requests/Responses

**DIP-10516: Exception occurred in adding provisioning profiles.**

**Cause:** Directory Integration Platform was not successful in adding provisioning profiles.

**Action:** Check the log files.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**DIP-10517: Scheduler is not able to connect to Oracle Internet Directory, tried {0} times.**

**Cause:** Directory Integration Platform was not able to connect to Oracle Internet Directory.

**Action:** Check the Oracle Internet Directory server status and configuration in Enterprise Manager.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**DIP-10518: Oracle Internet Directory version {0} is not supported.**

**Cause:** Server was not started as the version was not valid.

**Action:** Check the Directory Integration Platform server current version and the valid versions in documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**DIP-10519: Exception : during Directory Integration Platform startup.**

**Cause:** Failed to retrieve the version attribute of Directory Integration Platform registration.

**Action:** Check if the Directory Integration Platform registration was successful.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**DIP-10520: ODI server instance registration failure**

**Cause:** Some other Directory Integration Platform instance with same config set is already running.

**Action:** Start the Directory Integration Platform in another configset.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**DIP-10521: Directory Integration Platform server was not able to locate the current configset.**

---

**Cause:** Directory Integration Platform Server was not able to locate the current configset {0}.

**Action:** Check the configset entry in Oracle Internet Directory or MBEAN.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10523: Directory Integration Platform was not able to retrieve latest changenumber.**

**Cause:** An error occurred when Directory Integration Platform tried to get the last changenumber from Oracle Internet Directory.

**Action:** Refer to server log.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10524: Error in parsing last update change number.**

**Cause:** Directory Integration Platform Server was not able to initialize Scheduler Service components.

**Action:** Refer to server log.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10526: Error in update operation of current groups**

**Cause:** Directory Integration Platform Server was not able to update the group changes successfully.

**Action:** Refer to server log.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10527: Unable to update the changes made in synchronization profile.**

**Cause:** An error occurred while DIP was trying to update the profile job.

**Action:** Refer to server log.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10528: Scheduler exception in refreshing profiles {0}**

**Cause:** Directory Integration Platform Server could not refresh provisioning profiles of version 1.0 and 2.0.

**Action:** Refer to server log.

**Level:** 1

---

**Type:** ERROR

**Impact:** Data

**DIP-10530: Error in deleting profile {0}.**

**Cause:** Directory Integration Platform server was not able to delete profile job.

**Action:** Refer to server log.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**DIP-10531: Error in locating the Directory Integration Platform provisioning class.**

**Cause:** Directory Integration Platform Server was not able to look up the provisioning class.

**Action:** Check if the Directory Integration Platform status of Mbean is up in the Enterprise Manager.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10532: Error in completing one iteration of provisioning profile.**

**Cause:** Directory Integration Platform Server was not able to complete execution of provisioning profile.

**Action:** Refer to server log.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**DIP-10533: Error in locating Directory Integration Platform synchronization class.**

**Cause:** Directory Integration Platform Server was not able to look up the synchronization class.

**Action:** Check if the Directory Integration Platform ProvBean is up in the Enterprise Manager.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10534: Error in completing one iteration of synchronization profile.**

**Cause:** Directory Integration Platform Server was not able to complete one iteration of synchronization profile.

**Action:** Refer to server log.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**DIP-10544: Scheduler is not able to parse reconciliation time interval : {0}.**

**Cause:** The reconciliation time was in wrong format.

---

**Action:** Refer to Directory Integration Platform documentation for required date format.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10545: Unable to process the profile : {0}.**

**Cause:** The profile entry in the profilestore Oracle Internet Directory has been modified using unauthorized tools.

**Action:** Set the profile status to enable or disable using the manageSyncProfiles command.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10546: Scheduler is not able to read profile : {0}.**

**Cause:** The profile has a different version number other than what is supported.

**Action:** Delete the profile and recreate the profile using the manageSyncProfiles command.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10547: Error in merging profile attributes {0}.**

**Cause:** The provisioning profile entries were handled using unauthorized tools.

**Action:** Delete the profile and recreate the profile using the oidProvtool.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10548: Exception in propagating event : {0}.**

**Cause:** Directory Integration Platform Server was not able to propagate the event successfully.

**Action:** Refer to server log.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10549: Directory Integration Platform Server was not able to update the changes made to provisioning profile : {0}.**

**Cause:** An error occurred when Directory Integration Platform was trying to update the profile job.

**Action:** Refer to server log.

**Level:** 1

**Type:** ERROR

---

**Impact:** Data

**DIP-10550: Error in completing one iteration of reconciliation.**

**Cause:** Directory Integration Platform Server was not able to complete one iteration of reconciliation.

**Action:** Refer to server log.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**DIP-10567: Error in closing scheduler service: {0}.**

**Cause:** Directory Integration Platform Server was not able to close scheduler handles.

**Action:** Refer to server log.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**DIP-10568: Profile version not supported {0} : {1}**

**Cause:** Directory Integration Platform Server does not support profile version.

**Action:** Refer to Directory Integration Platform documentation for valid profile versions.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10570: Connection to LDAP server failed - Check configuration of DIP server.**

**Cause:** Directory Integration Platform Server was not able to connect to the LDAP server.

**Action:** Check the Oracle Internet Directory server.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**DIP-10581: Directory Integration Platform is not able to get the context with the given details : {0}.**

**Cause:** Error occurred in getting the LDAP context.

**Action:** Check if the registration is proper and Oracle Internet Directory is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**DIP-10585: Directory Integration Platform was not able to execute mapping plugin function : {0}.**

**Cause:** Illegal syntax used while calling mapping plugin function.

---

**Action:** Check the mapping rules and correct the syntax of plugin function.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10586: Error in loading mapping plugin - class not found : {0}.**

**Cause:** Mapping plugin class was not found.

**Action:** Check the mapping plugin name and check if the mapping plugin class is copied to appropriate location.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10587: Error in loading mapping plugin : {0}.**

**Cause:** Mapping plugin instantiation has failed.

**Action:** Check the mapping plugin implementation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10588: exception in executing mapping plugin : {0}**

**Cause:** Plugin implementation is not handling the exceptions.

**Action:** Check the mapping plugin Implementation is having correct entries.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10599: Errors encountered while starting Directory Integration Platform Scheduler : {0}**

**Cause:** The configset and the group entries could not be retrieved.

**Action:** Check the configset and profile group entries in Oracle Internet Directory.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**DIP-10600: Exception encountered while reconnecting to Oracle Internet Directory.**

**Cause:** Due to some failure in connection to Oracle Internet Directory, the connection was retried. The attempt to reconnect has failed.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**DIP-10606: Error occurred while shutting down scheduler**

---

**Cause:** Directory Integration Platform Server was not able to stop the scheduled jobs.

**Action:** Refer to server log.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**DIP-10608: error occurred while shutting down scheduler**

**Cause:** Directory Integration Platform Server was not able to write to audit.

**Action:** Refer to audit logger.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10622: Key store location not updated or key store not readable.**

**Cause:** Directory Integration Platform Server was not able to locate or read key store.

**Action:** Make sure key store location is updated and key store is readable.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-10623: Key store password not found in credential store.**

**Cause:** Directory Integration Platform Server was not able to retrieve key store password.

**Action:** Make sure key store password is updated.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-11018: Initialization of the LDIF {0} connector - {0} failed**

**Cause:** The LDIF connector "{0}" could not be initialized.

**Action:** Check the stack trace or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**DIP-11019: Initialization of the Directory Server source connector - {0} to read - {1} failed**

**Cause:** The Directory Server source connector could not be initialized.

**Action:** Check the stack trace or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Network

---

**DIP-11020: Initialization of the Directory Server source connector {0} failed**

**Cause:** The Directory Server destination connector could not be initialized.

**Action:** Check the stack trace or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**DIP-11021: Error occurred while applying the filter {0}. Ignoring - {1}**

**Cause:** Could not apply the filter.

**Action:** Check the stack trace or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-11022: Error occurred while reading {0}**

**Cause:** Could not read the entry.

**Action:** Check the stack trace or contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**DIP-11023: Error occurred while mapping {0}. Ignoring {1}**

**Cause:** Could not map the entry

**Action:** Check the stack trace or contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-11024: Error occurred while loading {0}. Ignoring {1}**

**Cause:** Could not load the entry

**Action:** Check the stack trace or contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-11025: Error occurred while writing {0}.**

**Cause:** Could not write the entry

**Action:** Check the stack trace or contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**DIP-11041: Error in adding user to group**



---

**Cause:** During bootstrap adding a user to a group that is handled by a plugin fails.

**Action:** Check the ACI policies in the directory that is bootstrapped.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-11042: Mandatory parameter missing - {0}**

**Cause:** A mandatory attribute is not specified

**Action:** Specify the following attribute - {0}

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-11043: Application name is not specified in the configuration.**

**Cause:** The application name was not specified

**Action:** Provide an application name

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-11044: Error loading the {0} class**

**Cause:** Could not load the class

**Action:** Check the stack trace for more details

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-11045: Error while reading the configuration file**

**Cause:** Could not read the configuration file

**Action:** Check the stack trace for more details

**Level:** 1

**Type:** ERROR

**Impact:** Files

**DIP-11046: Error while cleaning up**

**Cause:** Could not cleanup

**Action:** Check the stack trace for more details

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-11047: Error while connecting to OID**

**Cause:** Could not create the context

---

**Action:** Check the stack trace for more details

**Level:** 1

**Type:** ERROR

**Impact:** Network

**DIP-20001: Unable to update the status.**

**Cause:** Directory Integration Platform could not update the status as profile name or mode or version is null.

**Action:** Specify the value for profile name, mode and version.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20002: Application Distinguished Name is missing from v3 profile.**

**Cause:** Application Distinguished Name was not specified in the profile.

**Action:** Specify Distinguished Name in the provisioning profile.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**DIP-20003: Application Globally Unique Identifier(GUID) is missing.**

**Cause:** Application GUID was not specified in the Provisioning Profile.

**Action:** Specify GUID in provisioning profile.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**DIP-20004: Organization Globally Unique Identifier(GUID) is missing.**

**Cause:** Organization GUID was not specified in the provisioning profile

**Action:** Specify Organization GUID in profile

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**DIP-20006: Error occurs while initializing the plugin.**

**Cause:** Exception was thrown while initializing the plugin.

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**DIP-20008: Profile not found while updating the profile status.**

**Cause:** Exception was thrown while updating the profile status.

**Action:** Check the exception trace or Contact Oracle Support Services.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**DIP-20009: Failed to update the status.**

**Cause:** Directory Integration Platform failed to update the profile Status.

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**DIP-20010: Error occurs while initializing the provisioning profile.**

**Cause:** Exception was thrown while initializing the provisioning profile.

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**DIP-20033: ProvScheduler is interrupted.**

**Cause:** ProvScheduler is interrupted by another thread.

**Action:** No action

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**DIP-20039: Error occurs while updating profile status.**

**Cause:** Exception thrown while updating profile status.

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**DIP-20052: Exception on connecting to DB.**

**Cause:** Directory Integration Platform failed while connecting to database.

**Action:** Check the database is running properly on the given host and port.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**DIP-20053: Exception connecting to DB using service name.**

**Cause:** Directory Integration Platform failed while connecting to DB using the given service name.

**Action:** Check the service name is proper and it is running or Contact Oracle Support Services.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Network

**DIP-20061: Database configuration information is missing.**

**Cause:** Directory Integration Platform was not able to find the configuration information.

**Action:** Check if the Database configuration information is provided.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**DIP-20065: Error occurs while binding arguments for the prepared statement.**

**Cause:** Exception thrown while binding for the prepared statement.

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Requests/Responses

**DIP-20066: Error occurs while fetching the next row from the resultset.**

**Cause:** Exception thrown while getting the next row.

**Action:** Check the exception trace or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**DIP-20067: Exception occurs while configuring SQL operation.**

**Cause:** Exception thrown while configuring SQL operation.

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Requests/Responses

**DIP-20068: Exception occurs while initializing DB reader.**

**Cause:** Exception thrown while initializing DB reader

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**DIP-20069: Exception occurs while forming new change record.**

**Cause:** Exception thrown while forming new change record.

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

---

**Type:** INCIDENT\_ERROR

**Impact:** Data

**DIP-20070: Exception occurs while getting column count.**

**Cause:** Exception thrown while reading column count

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Requests/Responses

**DIP-20071: Exception occurs while getting query metadata.**

**Cause:** Exception thrown while getting query metadata.

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**DIP-20072: Exception while preparing the SQL statement.**

**Cause:** Exception thrown while preparing the SQL statement.

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Requests/Responses

**DIP-20073: Exception occurs during query execution.**

**Cause:** Exception thrown while executing a query.

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**DIP-20074: Could not find the key {0} in key array.**

**Cause:** Corruption in the profile attribute that stores the last ChangeKey for sync from DB.

**Action:** Look at the last ChangeKey value in the profile using the Profile Manager and set it to the timestamp from when the changes need to be synchronized.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**DIP-20080: Key values are not compliant with keys.**

**Cause:** Key value was not compliant with key.

**Action:** Check the key value or Contact Oracle Support Services.

**Level:** 1

---

**Type:** INCIDENT\_ERROR

**Impact:** Data

**DIP-20084: Missing attribute list in MapInfo**

**Cause:** Attribute list is missing in MapInfo.

**Action:** Check the mapping information

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20085: ChangeKey attribute is not found in profile.**

**Cause:** Directory Integration Platform was not able to find ChangeKey attribute value in profile.

**Action:** Check the ChangeKey attribute is present in the Profile.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**DIP-20086: ChangeKey attribute value is not found in profile.**

**Cause:** DIP was not able to find the changekey attribute value in profile.

**Action:** Check the ChangeKey attribute value present in profile.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**DIP-20094: Error occurs while getting the bind variables.**

**Cause:** Exception was thrown while getting the bind attributes.

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**DIP-20095: Error while creating statement object.**

**Cause:** Exception thrown while creating statement object

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**DIP-20096: Database Driver or Source Error Code : {0}**

**Cause:** Exception thrown while getting driver information.

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Network

**DIP-20097: Error occurs while deleting from the table : {0}.**

**Cause:** Directory Integration Platform failed when it tries to delete from the table.

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20101: Invalid argument format for attribute: {0}.**

**Cause:** Attribute {0} was not in proper format.

**Action:** Give attribute argument format in proper format.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20102: Operation type {0} is not valid.**

**Cause:** An invalid operation type was specified.

**Action:** Specify a valid operation type.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20110: Value for attribute: {0} not found in change record.**

**Cause:** Value of attribute {0} was not found in the change record.

**Action:** Check the attribute value is present or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**DIP-20123: Failed to open file for writing : {0}**

**Cause:** Directory Integration Platform (DIP) failed to create a file for writing.

**Action:** Check DIP has permission to create a file or enough disk space for file.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**DIP-20127: Error while creating callable statement object.**

**Cause:** Exception thrown while creating callable statement object.

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Requests/Responses

---

**DIP-20128: Events received ( {0} ), and Event Status events being sent back ( {1} ) are not same. Errors are encountered.**

**Cause:** Event index and number of events were not same.

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20130: Error occurs while propagating event status.**

**Cause:** Exception thrown while propagating event status.

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**DIP-20138: Error occurs while reading an event.**

**Cause:** Exception thrown while reading an event.

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**DIP-20139: Error occurs while searching for more events.**

**Cause:** Exception thrown while searching for more events.

**Action:** Check the exception trace or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20141: Error occurs while fetching the next Change Record.**

**Cause:** Exception is thrown while fetching the next Change Record.

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**DIP-20161: Error occurs while creating event from change.**

**Cause:** Exception thrown while creating event from change.

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**DIP-20162: Error occurs while propagating events.**



---

**Cause:** Exception thrown while propagating events.

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Requests/Responses

**DIP-20166: Exception occurs while adding or sending an event.**

**Cause:** Exception thrown while sending or adding an event.

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Requests/Responses

**DIP-20186: Insufficient privileges to read application user information.**

**Cause:** Directory Integration Platform (DIP) does not have permission to read application user information.

**Action:** Check that Directory Integration Platform has permission to read the application user information.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**DIP-20193: Error occurs while propagating event {0} for ObjectGUID {1} for ObjectName {2}.**

**Cause:** Exception thrown while propagating event.

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**DIP-20194: Not able to delete the user.**

**Cause:** Directory Integration Platform (DIP) failed while deleting the user.

**Action:** Check that DIP has permission to delete a user or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**DIP-20199: SQLException : {0} {1}**

**Cause:** Exception thrown while performing SQL operation.

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

---

**DIP-20200: Error occurs while preparing status update.**

**Cause:** Exception thrown while preparing status update.

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**DIP-20225: Error retrieving user create base from mappings.**

**Cause:** User create base was not specified.

**Action:** Check if user create base is specified.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20226: Error occurs while modifying identity.**

**Cause:** Exception thrown while modifying identity.

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**DIP-20227: Exception occurs while creating identity ( {0} ).**

**Cause:** Exception thrown while creating identity.

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**DIP-20228: Exception occurs while processing event.**

**Cause:** Exception thrown while processing event.

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**DIP-20229: Exception in setting up subscription information.**

**Cause:** Exception thrown while setting up subscription information.

**Action:** Check the exception trace or contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**DIP-20230: Event type {0} is unknown.**

**Cause:** Event type was unknown.

---

**Action:** Check the event type.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20231: Event ID and Status Event ID mismatches**

**Cause:** Event ID and Event Status ID were not same.

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Data

**DIP-20232: Util Exception occurs while searching identity : {0}.**

**Cause:** Exception thrown while searching for identity.

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**DIP-20259: Insufficient privileges to read the base user information.**

**Cause:** Insufficient Privileges to read the base user information.

**Action:** The application user defined in the 'applicationdn' of the profile doesn't have privileges to read the users in the 'usersearchbase'. Set the privileges accordingly.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20262: Failed to add rule : {0}.**

**Cause:** Directory Integration Platform Server was not able to parse the event mapping rules for the provisioning profile.

**Action:** Correct the event mapping rules for the provisioning profile.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20264: Event is null.**

**Cause:** The event to which the status needs to be set found null.

**Action:** No action required. If the status is not set for a event, the provisioning action will be retried.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20265: Exception while processing the event.**

---

**Cause:** Exception thrown while processing event.

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**DIP-20274: Error occurs while initializing ProvAppToOIDSync.**

**Cause:** Exception thrown while initializing ProvAppToOIDSync.

**Action:** Check the exception trace or Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**DIP-20307: Exception in filter processing**

**Cause:** Exception was thrown while processing the filter.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20318: Exception in filter processing**

**Cause:** Exception was thrown while processing filter.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20323: Error while processing next change From Oracle Internet Directory**

**Cause:** Exception was thrown while processing the next change from Oracle Internet Directory.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20324: Error while reading next change from Oracle Internet Directory**

**Cause:** Exception was thrown while reading next change from Oracle Internet Directory.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

---

**Type:** ERROR

**Impact:** Data

**DIP-20325: Error while processing ADD operation**

**Cause:** Directory Integration Platform was failing while adding an entry.

**Action:** Check if the entry is in proper format.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20326: Error while processing MODIFY operation**

**Cause:** Directory Integration Platform was failing while modifying an entry

**Action:** Check the entry is in proper format

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20343: Error while fetching next change.**

**Cause:** Reading the change for provisioning has failed.

**Action:** The change will be read during next iteration.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20344: Error while adding provisioning event for sending**

**Cause:** Exception was thrown while adding provisioning event.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20345: Error while initializing ProvPLSQLWriter**

**Cause:** Exception was thrown while initializing ProvPLSQLWriter.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**DIP-20348: Error while searching tombstone**

**Cause:** Directory Integration Platform has failed while searching Tombstone in ProvReader.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20349: Exception in getting change from Oracle Internet Direcotory**

**Cause:** Exception was thrown while getting change from Oracle Internet Direcotory in ProvReader.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20350: Exception in next change from Oracle Internet Directory**

**Cause:** ODI Exception was thrown while getting next change from Oracle Internet Directory.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20361: Error while notifying event**

**Cause:** Exception was thrown while notifying event.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**DIP-20362: Exception in event notification**

**Cause:** Exception was thrown while notifying an event.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**DIP-20363: Exception in initialization**

**Cause:** Exception is thrown while initializing the ProvWriter.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**DIP-20364: Exception in user group lookup or event propagation**

**Cause:** Exception was thrown while looking up for user or group.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20365: Unsupported interface type : {0}**

**Cause:** Given interface type is not supported by Directory Integration Platform.

**Action:** Check if the interface type is specified properly.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20375: Exception creating group**

**Cause:** Directory Integration Platform failed while creating a group.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20376: Exception while creating identity ( {0} )**

**Cause:** Directory Integration Platform has failed while creating the identity.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20378: Exception getting user attributes**

**Cause:** Directory Integration Platform has failed while trying to access user attributes.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20379: Exception during MODRDN operation**

**Cause:** Directory Integration Platform has failed while performing modRDN operation.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20380: Exception sending event**

**Cause:** Exception was thrown while sending event.

**Action:** Check if the application is running properly.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**DIP-20381: Exception subscribing identity ( {0} ) {1}**

**Cause:** Exception was thrown when Directory Integration Platform subscribed to the identity.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20382: Exception un-subscribing identity ( {0} ) {1}**

**Cause:** Exception was thrown when Directory Integration Platform tried to un-subscribe the identity.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20383: Exception sending event**

**Cause:** ODI exception is thrown while sending the event.

**Action:** Check if the application is running properly or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**DIP-20384: Exception creating group ( {0} ) : {1}**

**Cause:** Util exception was thrown while creating the group.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20385: Exception deleting identity : {0}**



---

**Cause:** Util exception was thrown while deleting the identity.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20386: Exception deleting identity :**

**Cause:** Util exception was thrown while deleting the identity.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20387: Exception deleting group**

**Cause:** Util exception was thrown while deleting the group.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20388: Exception modifying identity : {0}**

**Cause:** Util exception was thrown while modifying the identity.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20389: Exception modifying group**

**Cause:** Util exception was thrown while modifying the group.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20390: Exception searching group : {0}**

**Cause:** Util exception was thrown when searching for the group {0}.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

---

**Type:** ERROR

**Impact:** Data

**DIP-20391: Exception subscribing to identity : {0}**

**Cause:** Util exception was thrown when subscribing to the identity.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20392: Exception un-subscribing identity : {0}**

**Cause:** Util exception was thrown when un-subscribing the identity.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20394: Error modifying identity - identity not found : {0}**

**Cause:** Directory Integration Platform tried to modify an identity that did not exist.

**Action:** Verify that the identity exists. If it does not, then contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20408: error deleting Identity : {0}**

**Cause:** Exception was thrown while deleting an identity.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20409: error subscribing identity - identity to be subscribed not found : {0}**

**Cause:** Exception was thrown while subscribing identity.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20412: error un-subscribing identity - identity to be un-subscribed not found : {0}**

---

**Cause:** Exception was thrown while un-subscribing identity  
**Action:** Verify that the identity exists or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20421: ignoring invalid {0} : {1}**

**Cause:**

**Action:**

**Level:** 1

**Type:** WARNING

**Impact:** Data

**DIP-20422: ignoring GROUP\_ADD event with no attributes**

**Cause:** Invalid group add event was sent by the application.

**Action:** Check the application event generation mechanism.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20425: error modifying group - group not found : {0}**

**Cause:** Directory Integration Platform tried to modify a group which did not exist.

**Action:** Check if group exists. If not, then contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20430: exception modifying group**

**Cause:** Directory Integration Platform fails when it tried to modify a group.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20431: error deleting group - group not found : {0}**

**Cause:** Directory Integration Platform tried to delete a group that did not exist.

**Action:** Verify that the group exists or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20433: error deleting group**

---

**Cause:** Exception was thrown while deleting a group.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20447: error initializing ProvOIDToAppSync**

**Cause:** Exception was thrown while initializing ProvOIDToAppSync.

**Action:** Check the exception trace for more information or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-20453: obtaining LDAP connection failed in attempt number :{0} - Retrying**

**Cause:**

**Action:**

**Level:** 1

**Type:** WARNING

**Impact:**

**DIP-20454: maximum LDAP connection retry count reached**

**Cause:**

**Action:**

**Level:** 1

**Type:** WARNING

**Impact:**

**DIP-20455: an error occurred while retrieving the changenumber**

**Cause:** An error occurred when DIP tried to get the last changenumber from Oracle Internet Directory.

**Action:** Refer to server log and trace files.

**Level:** 1

**Type:** ERROR

**Impact:**

**DIP-20456: an error occurred in opening the Control file**

**Cause:** An error occurred while opening the control file.

**Action:** Ensure that the file is available and that no other applications are using the same.

**Level:** 1

**Type:** ERROR

**Impact:**

---

**DIP-20457: an error occurred in reading the Control file**

**Cause:** An error occurred while opening the control file.

**Action:** Ensure that the file is available and that no other applications are using the same.

**Level:** 1

**Type:** ERROR

**Impact:**

**DIP-20458: The DN does not exist in the connected directory.**

**Cause:** The DN being processed was not found in the connected directory.

**Action:** Verify that the data is in a consistent state.

**Level:** 1

**Type:** ERROR

**Impact:**

**DIP-20459: The Event Plugin was not initialized properly.**

**Cause:** The Event Plugin configuration might be incorrect.

**Action:** Verify that the profile and plugin are compatible.

**Level:** 1

**Type:** ERROR

**Impact:**

**DIP-20460: An Error occurred while setting LDAP host :{0}, port :{1}.**

**Cause:** The LDAP host and port could not be set.

**Action:** Check the host and port setting and LDAP availability.

**Level:** 1

**Type:** ERROR

**Impact:**

**DIP-20462: Directory Integration Platform MBean Registration has failed**

**Cause:** The Application server did not initialize itself correctly or the Directory Integration Platform configuration is incorrect.

**Action:** Check the Application server and Directory Integration Platform logs.

**Level:** 1

**Type:** ERROR

**Impact:**

**DIP-20463: Directory Integration Platform Runtime MBean Registration has failed**

**Cause:** The Application server did not initialize itself correctly or the DIP configuration is incorrect.

**Action:** Check the Application server and Directory Integration Platform logs.

**Level:** 1

**Type:** ERROR

**Impact:**

---

**DIP-30001: Exception while removing unwanted attributes.**

**Cause:** Exception is thrown while removing attribute from the attribute list after checking that attribute is required or not

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-30003: Exception while printing attributes.**

**Cause:** Exception is thrown while printing attributes and its value

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-30004: Nickname attribute is not found Default nickname attribute = uid**

**Cause:** Nick name attribute is not found

**Action:** Setting it to default value

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-30013: Exception in getting event**

**Cause:** Exception is thrown while reading the event

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-30028: Exception while setting Provisioning policies.**

**Cause:** Exception is thrown while adding rule in the set of event rule

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-30044: Exception while searching in Tombstone.**

**Cause:** Exception is thrown while searching entries in Tombstone.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-30048: Error in updating the entry status**

---

**Cause:** Exception is thrown while updating the event status

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-30056: Exception in filtering the entry**

**Cause:** Exception is thrown while filtering out the events

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-52706: Key store file is not existing or it is not readable.**

**Cause:** Directory Integration Platform Server was not able to locate or read key store.

**Action:** Make sure key store file is existing and readable.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-60001: The Sensor {0} was not found.**

**Cause:** The DIP tried to access a Metrics sensor that doesn't exist.

**Action:** Create a Bug against DIP.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**DIP-60002: The following DMS Noun could not be created: {0}.**

**Cause:** The DIP tried to create a Metrics Noun but the provided Noun Path is invalid.

**Action:** Create a Bug against DIP.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**DIP-60003: The following DMS Noun was not found in DMS: {0}**

**Cause:** The DIP tried to access a Metrics Noun that doesn't exist.

**Action:** Create a Bug against DIP.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**DIP-60004: The Default Sensor Array is invalid.**

---

**Cause:** The DIP tried to create the default Metrics sensors, but failed. The Metrics default array is invalid.

**Action:** Create a Bug against DIP.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**DIP-60005: The following DMS Sensor failed to create: {0}**

**Cause:** The DIP failed to create a Metrics sensor, probably because of a wrong Noun Path.

**Action:** Create a Bug against DIP.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**DIP-60006: Failed to delete/destroy the Sensor hierarchy for profile: {0}**

**Cause:** The DIP tried to delete several Metrics sensors but failed, probably because of invalid Noun Paths.

**Action:** Create a Bug against DIP.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**DIP-80001: Exception while connecting to directory server.**

**Cause:** Directory Integration Platform tried to get a connection to the directory server, but failed.

**Action:** Check the connection details and credentials, also check whether the directory server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**DIP-80002: Exception while populating the server config: {0}.**

**Cause:** Directory Integration Platform tried to access a server configset, but failed.

**Action:** Specify a correct server configset number.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-80003: Exception while retrieving server configset.**

**Cause:** Directory Integration Platform tried to get all server configset, but failed.

**Action:** Contact administrator or Oracle Support Services.

**Level:** 1

**Type:** ERROR



---

**Impact:** Data

**DIP-80004: Exception while storing configset: {0}.**

**Cause:** Directory Integration Platform tried to store the server configset, but failed.

**Action:** Contact administrator or Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-80005: Exception while creating configset: {0}.**

**Cause:** Directory Integration Platform tried to create a new server configset, but failed.

**Action:** Contact administrator or Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-80006: Exception while deleting configset: {0}.**

**Cause:** Directory Integration Platform tried to delete a server configset, probably because of wrong configset number.

**Action:** Contact administrator or Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-80007: Exception while retrieving configset: {0}.**

**Cause:** Directory Integration Platform tried to locate a server configset, probably because of wrong configset.

**Action:** Contact administrator or Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-80008: Exception while deleting a profile group {1} from configset {0}.**

**Cause:** Directory Integration Platform tried to delete a profile group, but failed.

**Action:** Contact administrator or Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-80009: Exception while retrieving default configset.**

**Cause:** Directory Integration Platform tried to get default server configset, but failed.

**Action:** Contact administrator or Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-80010: Exception while updating default configset.**

**Cause:** Directory Integration Platform tried to set default server configset, but failed.

**Action:** Contact administrator or Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-80101: Directory meta data does not exists in persistent data store.**

**Cause:** Directory Integration Platform tried to populate a directory meta data which does not exist.

**Action:** Specify a correct directory name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-80102: Exception while retrieving directory meta data.**

**Cause:** Directory Integration Platform tried to populate a directory meta data, but failed.

**Action:** Contact administrator or Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-80103: Exception while retrieving operational or special attributes.**

**Cause:** Directory Integration Platform tried to get operational or special attributes, but failed.

**Action:** Contact administrator or Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-80104: Exception while adding operational attributes.**

**Cause:** Directory Integration Platform tried to add operational attributes, probably because wrong directory name has specified.

**Action:** Contact administrator or Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-80105: Exception while checking whether an attribute is operational or not.**

---

**Cause:** Directory Integration Platform tried to check whether an attribute is operational or not, probably because wrong directory name has specified.

**Action:** Contact administrator or Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-80106: Exception while deleting operational attribute from persistent data store.**

**Cause:** Directory Integration Platform tried to delete an operational attributes, but failed.

**Action:** Contact administrator or Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-80107: Exception while deleting operational attribute from persistent data store.**

**Cause:** Directory Integration Platform tried to delete an operational attributes which does not exists in specified directory meta -data.

**Action:** Specify a correct attribute name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-80201: failed to connect to directory server**

**Cause:** Directory Integration Platform failed to connect directory server with given details.

**Action:** Check the directory server connection details.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**DIP-80202: Error in reading provisioning profiles.**

**Cause:** Directory Integration Platform failed to search the directory server for provisioning profiles.

**Action:** Check the directory server connection details and the provisioning profile containers.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-80203: Error in reading attributes of provisioning profile {0}.**

**Cause:** Directory Integration Platform failed to find provisioning profile in directory server.

**Action:** Check the directory server connection details and the provisioning profile.

**Level:** 1

---

**Type:** ERROR

**Impact:** Data

**DIP-80204: Error in reading attribute {0} of provisioning profile {1}.**

**Cause:** Directory Integration Platform failed to find attribute.

**Action:** Check the directory server connection details and the provisioning profile.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-80205: Exception while deleting provisioning profile {0}.**

**Cause:** Directory Integration Platform failed to delete the provisioning profile either for insufficient access or invalid profile name or invalid connection details.

**Action:** Check the directory server connection details and the provisioning profile.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-80206: Exception while modifying provisioning profile {0}.**

**Cause:** Directory Integration Platform failed to modify the provisioning profile either for insufficient access or invalid profile name or invalid connection details.

**Action:** Check the directory server connection details and the provisioning profile.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-80207: Failed to modify provisioning profile {0}. Modifying the attribute {1} is not supported for provisioning profile {0} with version {2}.**

**Cause:** Modifying the attribute is not supported for this version of provisioning profile.

**Action:** Check for provisioning profile version.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-80208: Filename is mandatory parameter for bulkprov :{0}.**

**Cause:** Filename was found missing for bulkprov operation.

**Action:** Provide a valid ldif file for bulkprov operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-81001: Exception while adding connector group in directory server {0}.**

**Cause:** Directory Integration Platform tried to add a new connector group but failed, probably because this connector group already exists.

**Action:** Specify a correct connector group.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-81002: Exception while renaming connector group {0} to {1}.**

**Cause:** Directory Integration Platform tried to rename a connector group but failed, probably because this connector group does not exist.

**Action:** Specify a correct connector group or check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-81003: Exception while deleting connector group in directory server {0}.**

**Cause:** Directory Integration Platform tried to delete a connector group but failed, probably because this connector group does not exist.

**Action:** Specify a correct connector group.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-81004: Exception while retrieving connector group from profile.**

**Cause:** Directory Integration Platform tried to get all the connector groups from Oracle Internet Directory but failed.

**Action:** Contact administrator or Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-81008: Exception while retrieving list of all unassociated profiles.**

**Cause:** Directory Integration Platform tried to get the list of unassociated profiles from Oracle Internet Directory, but failed

**Action:** Contact administrator or Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-81012: Exception while retrieving profile Distinguished Name.**

**Cause:** Directory Integration Platform tried to get profile DN, but failed.

**Action:** Contact administrator or Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-81013: Exception while retrieving profile container.**

**Cause:** Directory Integration Platform tried to get profile container, but failed

---

**Action:** Contact administrator or Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85001: Error connecting to the directory server.**

**Cause:** Directory Integration Platform tried to connect to the directory server, but failed.

**Action:** Check the connection details and the credentials. Also check if the directory server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**DIP-85002: Exception while retrieving profile name {0}.**

**Cause:** Directory Integration Platform failed to find the profile in Oracle Internet Directory.

**Action:** Check if the profile name is correct and the profile exists.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85003: Error retrieving attributes from the directory server.**

**Cause:** Directory Integration Platform failed to retrieve the profile attributes from the directory server.

**Action:** Check the stack trace for the exact error.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85004: Error occurred while writing the attribute to the directory server**

**Cause:** Directory Integration Platform failed to save the attribute value.

**Action:** Check the stack trace for the exact error.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85008: The profile {0} already exists.**

**Cause:** A profile with the same name as the profile being created already exists.

**Action:** Delete the existing profile or select a different name for the new profile.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85009: The profile name is invalid.**

---

**Cause:** The DN formed for the profile was not valid.  
**Action:** Contact administrator or Oracle Support Services.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Data

**DIP-85010: Exception while creating the synchronization profile.**

**Cause:** Directory Integration Platform failed to create the synchronization profile.  
**Action:** Contact administrator or Oracle Support Services.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Data

**DIP-85011: Exception while deleting the profile.**

**Cause:** Directory Integration Platform failed to delete the profile.  
**Action:** Contact administrator or Oracle Support Services.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Data

**DIP-85012: cannot retrieve value for attribute {0}**

**Cause:**  
**Action:**  
**Level:** 1  
**Type:** WARNING  
**Impact:** Data

**DIP-85013: cannot construct DN for the profile**

**Cause:**  
**Action:**  
**Level:** 1  
**Type:** WARNING  
**Impact:** Data

**DIP-85014: Exception while updating the profile last applied change number.**

**Cause:** Directory Integration Platform failed to update last applied change number for the profile.  
**Action:** Contact administrator or Oracle Support Services.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Data

**DIP-85015: Exception while retrieving bootstrap attributes.**

**Cause:** Directory Integration Platform failed to get bootstrap attributes.

---

**Action:** Contact administrator or Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85016: profile already associated to ODIP group**

**Cause:**

**Action:**

**Level:** 1

**Type:** WARNING

**Impact:** Data

**DIP-85019: Exception while performing bootstrap operation.**

**Cause:** Directory Integration Platform failed to perform the bootstrap operation.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85031: Exception while creating subset criteria.**

**Cause:** Directory Integration Platform failed to create the subset criteria.

**Action:** Contact administrator or Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85032: Exception while updating bootstrap status.**

**Cause:** Directory Integration Platform failed to update the bootstrap status.

**Action:** Contact administrator or Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85033: The profile is not valid.**

**Cause:** The validation of the profile indicated invalid values for some attributes.

**Action:** Update the profile with proper values.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85034: Exception while setting up the external authentication plug-in.**

**Cause:** Directory Integration Platform failed to set up the external authentication plug-in.

**Action:** Check the stack trace for more details



---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**DIP-85035: Exception while setting up credential store key for pre 4.0 profiles.**

**Cause:** Directory Integration Platform failed to set a credential store key for a pre-4.0 profile.

**Action:** Set the user account and the password in the profile.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**DIP-85036: Exception while retrieving credential store key for pre 4.0 profiles.**

**Cause:** Directory Integration Platform failed to retrieve a credential store key from a pre-4.0 profile.

**Action:** Get the user account and the password from the profile.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**DIP-85041: Incorrect type of external directory specified.**

**Cause:** The specified directory was not supported.

**Action:** Specify supported directory.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85042: Exception while updating the directory server.**

**Cause:** Directory Integration Platform failed to update the directory server.

**Action:** Contact administrator or Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85044: Exception while retrieving plugin configuration entries.**

**Cause:** Directory Integration Platform failed to find the plugin configuration entries.

**Action:** Check the stack trace for more details or contact the LDAP administrator

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**DIP-85045: Unrecognized property - {0}.**

**Cause:** The specified property was not supported.

**Action:** Specify a valid property to be set or modified.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85046: Exception while deleting invalid profile - {0}.**

**Cause:** The profile is invalid and was created in directory server, but could not be deleted from after validation.

**Action:** Manually delete the invalid profile and try creating it again.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85047: Exception while retrieving synchronization profile container.**

**Cause:** Directory Integration Platform tried to get sync profile container, but failed.

**Action:** Check the exception stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85048: The value for property '{0}' cannot be null.**

**Cause:** An attribute was being set with a null value.

**Action:** Specify a non null legal value when setting an attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85049: An unexpected exception encountered.**

**Cause:** Directory Integration Platform failed to perform the operation.

**Action:** Contact administrator or Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85050: No value found in profile {0} for attribute "{1}".**

**Cause:** The value for required attribute was not set.

**Action:** Set a value for the missing attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85051: Incorrect associated profile name {0} provided.**

**Cause:** This profile cannot be set as associated profile for the current profile.

**Action:** Use profile with proper synchronization mode and connected directory type.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85052: Exception while retrieving profile.**

**Cause:** Either profile name is incorrect or profile does not exist in the directory server.

**Action:** Contact administrator or Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85085: The property {0} cannot be updated using this operation, and will be ignored.**

**Cause:** A property which cannot be updated was passed to the operation.

**Action:** Look at the docs to see how this property can be modified.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85086: Invalid value specified for provisioning profile attribute "orclodipinterfaceconnectinformation".**

**Cause:** The provisioning profile attribute "orclodipinterfaceaccountinformation" was specified with incorrect syntax.

**Action:** Make sure that the profiles conform to the syntax specified.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85089: Authentication fails for user {0}.**

**Cause:** Authentication failed for user {0}.

**Action:** Check the user credentials.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85090: Access denied for java key store.**

**Cause:** Directory Integration Platform failed to access java key store for insufficient permissions.

**Action:** Check for java key store permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85091: Directory service unavailable at {0}:{1}**

---

**Cause:** Service was unavailable at {0}:{1}  
**Action:** Check for given host and port details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85092: update Change number may not have succeeded on profile creation**

**Cause:** The connected directory server may have been down.

**Action:** Check the connected directory server, and try again using manageSyncProfiles updatechgnum operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85093: profile store operation encountered some exceptions, check logs.**

**Cause:** The profile have encountered validation or other issues while being stored.

**Action:** Check the logs and profile for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85094: validation of the profile indicated invalid values for some attributes**

**Cause:** The validation of the profile indicated invalid values for some attributes.

**Action:** Check the values of the attributes and update the profile with correct values before activating it.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85095: validation of the profile indicated invalid values for mapping rules or some other attributes.**

**Cause:** The validation of the profile indicated invalid values for mapping rules or some other attributes.

**Action:** Update the profile with correct mapping rules and/or correct values of the attributes before activating it.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85096: cannot connect directory server at {0} : {1}**

**Cause:** Directory Integration Platform failed to connect the directory server at {0} : {1}

**Action:** Check the server host and port details.

**Level:** 1

---

**Type:** ERROR

**Impact:** Data

**DIP-85097: unable to connect to Oracle Internet Directory.**

**Cause:** Directory Integration Platform failed to connect to Oracle Internet Directory.

**Action:** Check the Oracle Internet Directory server details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85102: Mandatory profile property "{0}" missing.**

**Cause:** Directory Integration Platform failed to find mandatory profile property.

**Action:** Provide required profile property.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85103: Error while parsing map rules for exclusion rules.**

**Cause:** Directory Integration Platform failed to parse map exclusion rules.

**Action:** Contact administrator or Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85104: The username value entered is invalid.**

**Cause:** The username value entered is invalid.

**Action:** Ensure that it does not contain white spaces.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85105: The password value entered is invalid.**

**Cause:** The password value entered was invalid.

**Action:** Provide a legal value for password.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85106: The SSL setting value entered is invalid.**

**Cause:** The SSL setting value entered is invalid.

**Action:** Ensure that it is an integer less than or equals 2.

**Level:** 1

**Type:** ERROR

---

**Impact:** Data

**DIP-85107: The profile {0} is associated to other profile(s).**

**Cause:** Directory Integration Platform failed to delete the profile because it is associated to other profile(s).

**Action:** Dissociate the profile to other profile(s) to deregister.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85108: Key store location not updated or key store not readable.**

**Cause:** Directory Integration Platform Server was not able to locate or read key store.

**Action:** Make sure key store location is updated and key store is readable.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85109: Key store password not found in credential store.**

**Cause:** Directory Integration Platform Server was not able to retrieve key store password.

**Action:** Make sure key store password is updated.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-85110: Profile {0} is already activated. Hence the profile is not scheduled for test.**

**Cause:** Directory Integration Platform failed to schedule the profile for test because it is already activated.

**Action:** Deactivate the profile to schedule the profile for test.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-86000: all arguments passed is null**

**Cause:** No arguments passed.

**Action:** Pass all the required arguments.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-86001: parameter passed is null**

**Cause:** Argument or their values passed were null.

**Action:** Arguments passed cannot be null, pass the required values.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-86002: failed to setup the destination host**

**Cause:** Directory Integration Platform failed to setup the destination host.

**Action:** Check the destination host and port settings.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**DIP-86003: invalid credentials or, host and port settings**

**Cause:** Directory Integration Platform failed to connect destination with given connection details.

**Action:** Check the credentials for destination connection details.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**DIP-86004: invalid credentials or host-port details for connected directory**

**Cause:** Required connected directory details are not provided.

**Action:** Make sure you provide proper details for connected directory.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**DIP-86005: cannot find the default container**

**Cause:** Directory Integration Platform failed to find default {0} container.

**Action:** Check if the default container exists or create the default container.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-86006: cannot find the value of default container**

**Cause:** Directory Integration Platform failed to find value for default {0} container.

**Action:** Check the value for default container.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-86007: parameter value is null**

**Cause:** The value for attribute {0} was missing.

**Action:** Check value for the parameter, it cannot be null.

**Level:** 1

---

**Type:** ERROR

**Impact:** Data

**DIP-86008: parameter name not found**

**Cause:** Directory Integration Platform failed to find the parameter {0}.

**Action:** Check the parameter name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-86009: cannot create a profile from template profile**

**Cause:** Directory Integration Platform failed to create the profile from the template profile.

**Action:** Check if template profile exists

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-86010: cannot associate profile with the profile group**

**Cause:** Directory Integration Platform failed to associate profile with group.

**Action:** Check the profile group name to which the profile will be added exists.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-87000: cannot initialize the schema**

**Cause:** Directory Integration Platform encountered an exception while initializing the schema.

**Action:** Check the stack trace for more details

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DIP-87001: cannot get the directory server context**

**Cause:** Directory Integration Platform encountered an exception while getting the directory server context.

**Action:** Check the stack trace for more details

**Level:** 1

**Type:** ERROR

**Impact:** Network

**DIP-87002: Exception while getting the connected directory context.**

**Cause:** Directory Integration Platform failed to obtain the connected directory context.

**Action:** Check the stack trace for more details



---

**Level:** 1

**Type:** ERROR

**Impact:** Network



---

## DISCMAN-00100 to DISCMAN-80213

**DISCMAN-00100: Invalid input parameter.**

**Cause:** Error encountered while processing input parameter.

**Action:** Check if input parameter is correct.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-00101: Invalid {0} input parameter.**

**Cause:** Error encountered while processing input parameter.

**Action:** Check if input parameter is correct.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10000: Sample Error Messages**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-10001: ODL message for id ={0} isn't found.**

**Cause:** Failed to get error message by id.

**Action:** Update client version.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10002: Web service endpoint initialization has failed.**

**Cause:**

**Action:**

**Level:** 32

---

**Type:**

**Impact:**

**DISCMAN-10003: Full mapping fact is not found, id={0}**

**Cause:** Selected item is inconsistency.

**Action:** Reload client and try again.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10004: Instance Preview (IsUSGaapTaxonomyUsed: {0}; UseSecViewer: {1})**

**Cause:** Showing XBRL report.

**Action:**

**Level:** 32

**Type:** INFO

**Impact:**

**DISCMAN-10005: Creating US GAAP Instance Transformer (instance path: {0}; taxonomy path: {1})**

**Cause:** Initialization US GAAP viewer.

**Action:**

**Level:** 32

**Type:** INFO

**Impact:**

**DISCMAN-10006: Creating Generic Viewer transformer (instance path: {0}; generic report path: {1})**

**Cause:** Initialization generic viewer.

**Action:**

**Level:** 32

**Type:** INFO

**Impact:**

**DISCMAN-10007: Creating Xbrl transformer (instance path: {0})**

**Cause:** Initialization XBRL report viewer.

**Action:**

**Level:** 32

**Type:** INFO

**Impact:**

**DISCMAN-10008: Error appeared while getting doclet range. Ranges count is not equal 1: ({0})**

**Cause:** Selected doclet is inconsistency.

**Action:** Reload client and try again.

---

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10009: Web Service failed to remove mapping with id={0}**

**Cause:** Failed to remove mapping on server side.

**Action:** Check if mapping exists, probably it was removed by another user.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10010: Mapping to concept '{0}' failed. Document is associated with taxonomy '{1}' but concept belongs to taxonomy '{2}'**

**Cause:** Failed to create mapping for other taxonomy.

**Action:** Change taxonomy for document.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10011: Could not create mapping object. Unknown mapping object type {0}.**

**Cause:** Failed to create mapping object for this type.

**Action:** Update client version.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10012: Could not create web service. Unknown web service type {0}.**

**Cause:** Failed to create web service.

**Action:** Update client version.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10013: MappingToolWS.QueryDocumentMappings exception={0}**

**Cause:** Failed to call MappingTool web service (method QueryDocumentMappings).

**Action:** Check if the MappingTool Web Service is configured correctly.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10014: MappingToolWS.QueryGridMappings exception={0}**

**Cause:** Failed to call MappingTool web service (method QueryGridMappings).

**Action:** Check if the MappingTool Web Service is configured correctly.

---

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10015: MappingToolWS.Generate exception={0}**

**Cause:** Failed to call MappingTool web service (method Generate).

**Action:** Check if the MappingTool Web Service is configured correctly.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10016: MappingToolWS.RemoveMapping exception={0}**

**Cause:** Failed to call MappingTool web service (method RemoveMapping).

**Action:** Check if the MappingTool Web Service is configured correctly.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10017: MappingToolWS.ChangeMappingsTaxonomy exception={0}**

**Cause:** Failed to call MappingTool web service (method ChangeMappingsTaxonomy).

**Action:** Check if the MappingTool Web Service is configured correctly.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10018: MappingToolView: UpdateTupleInfos is failed**

**Cause:** Failed to update TupleInfos.

**Action:** Reload client and try again.

**Level:** 32

**Type:** WARN

**Impact:**

**DISCMAN-10019: MappingToolView: Mapping abstract element "{0}:{1}" is failed**

**Cause:** You cannot map abstract element.

**Action:** Select not abstract element.

**Level:** 32

**Type:** WARN

**Impact:**

**DISCMAN-10020: MappingToolView: documentMap.addXbrlDimension is failed**

**Cause:** Failed to call MappingToolView (method documentMap.addXbrlDimension).

**Action:** Reload client and try again.

---

**Level:** 32

**Type:** WARN

**Impact:**

**DISCMAN-10021: MappingToolView: registerDocumentMaps is failed**

**Cause:** Failed to call MappingToolView (method registerDocumentMaps).

**Action:** Reload client and try again.

**Level:** 32

**Type:** WARN

**Impact:**

**DISCMAN-10022: MappingToolView: setContexts is failed**

**Cause:** Failed to call MappingToolView (method setContexts).

**Action:** Reload client and try again.

**Level:** 32

**Type:** WARN

**Impact:**

**DISCMAN-10023: MappingToolView: SetTupleInstanceContext is failed**

**Cause:** Failed to call MappingToolView (method SetTupleInstanceContext).

**Action:** Reload client and try again.

**Level:** 32

**Type:** WARN

**Impact:**

**DISCMAN-10024: MappingToolView: setVirtualContexts is failed**

**Cause:** Failed to call MappingToolView (method setVirtualContexts).

**Action:** Reload client and try again.

**Level:** 32

**Type:** WARN

**Impact:**

**DISCMAN-10025: MappingToolView: setUnits is failed**

**Cause:** Failed to call MappingToolView (method setUnits).

**Action:** Reload client and try again.

**Level:** 32

**Type:** WARN

**Impact:**

**DISCMAN-10026: MappingToolView: setFootnotes is failed**

**Cause:** Failed to call MappingToolView (method setFootnotes).

**Action:** Reload client and try again.

**Level:** 32

**Type:** WARN

---

**Impact:**

**DISCMAN-10027: Disclosure Management main menu item is not created**

**Cause:** Client initialization is failed (main menu item is not created).

**Action:** Update client version.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10028: Unpacking Instance Package into {0}**

**Cause:**

**Action:**

**Level:** 32

**Type:** INFO

**Impact:**

**DISCMAN-10029: Couldn't create document UI: unknown native document type.**

**Cause:** Document initialization is failed (unknown native document type).

**Action:** Select other document.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10030: Document is not a standalone DiscMan document.**

**Cause:** You need standalone DiscMan Document for this operation.

**Action:** Select other document.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10031: Only Word Document can be converted to Master Document.**

**Cause:** You need Ms Word Document for this operation.

**Action:** Select MS Word document.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10032: Failed to convert to Master master document. Couldn't connect to security service.**

**Cause:** Failed to connect to security web service (creating Master Document).

**Action:** Check if Authorization system is configuration.

**Level:** 32

**Type:** ERROR

**Impact:**



---

**DISCMAN-10033: Expected resources not found. The following files are required:**  
**{0}, {1}, {2}**  
**Cause:** Failed to get resource from server.  
**Action:** Check server side configuration.

**Level:** 32  
**Type:** ERROR  
**Impact:**

**DISCMAN-10034: Failed to generate instance preview. Path to SecViewer source files is invalid.**  
**Cause:** SEC View path is not defined.  
**Action:** Open client Options and configure SEC View path.

**Level:** 32  
**Type:** ERROR  
**Impact:**

**DISCMAN-10035: {0}**  
**Cause:** Error SEC View module.  
**Action:** Check SEC View configuration.

**Level:** 32  
**Type:** ERROR  
**Impact:**

**DISCMAN-10036: Global template is not installed. Customization will work with Normal.dot**  
**Cause:** Client initialization is failed (cannot created global template).  
**Action:** Check MS Office configuration.

**Level:** 32  
**Type:** WARN  
**Impact:**

**DISCMAN-10037: DiscManDocument.CheckMappingDocumentId: generated new MappingDocumentId value = \"{0}\"**  
**Cause:**  
**Action:**

**Level:** 32  
**Type:** INFO  
**Impact:**

**DISCMAN-10038: Doclet storage is already initialized.**  
**Cause:** Client initialization is failed (doclet storage is already initialized).  
**Action:** Restart client.

**Level:** 32  
**Type:** ERROR

---

**Impact:**

**DISCMAN-10039: PublishExcel method failed. Worksheet name is not defined.**

**Cause:** Worksheet name is not defined.

**Action:** Select correct worksheet before operation.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10040: Error appeared while getting doclet subdocument.**

**Cause:** Document initialization is failed (subdocument not found).

**Action:** Reopen document.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10041: A primary item mapping must exist prior to domain or member mapping**

**Cause:** Cannot create dimension mapping without concept mapping.

**Action:** Create concept mapping before dimension mapping.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10042: Highlight is impossible in locked document**

**Cause:** Cannot highlight mapping inside read only Doclet.

**Action:** Open Doclet separately.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10043: CommandBarHandler: Unrecongized Office Application {0}**

**Cause:** Unsupported MS Office application.

**Action:** See documentation for supported MS Office applications.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10044: Version: {0}**

**Cause:** Client version.

**Action:**

**Level:** 32

**Type:** INFO

**Impact:**

---

**DISCMAN-10045: Expected Smart View Version: {0} (Build {1})**

**Cause:** SmartView version.

**Action:**

**Level:** 32

**Type:** INFO

**Impact:**

**DISCMAN-10046: Disclosure Management Smart View Extension is shut down**

**Cause:** Client shutdown.

**Action:**

**Level:** 32

**Type:** INFO

**Impact:**

**DISCMAN-10047: Disclosure Management Smart View Extension is started up**

**Cause:** Client startup.

**Action:**

**Level:** 32

**Type:** INFO

**Impact:**

**DISCMAN-10048: Cannot get id for message={0}.**

**Cause:** Failed to parse message id.

**Action:** Update client version.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10049: Failed to replace new page section break with the section break in new doclet. Exception: {0}**

**Cause:** Resources leak.

**Action:** Restart workstation.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10050: Failed to align table to left. Exception: {0}**

**Cause:** Resources leak.

**Action:** Restart workstation.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10051: Failed to add a subdocument to document. Exception: {0}**

---

**Cause:** A document of a part of the document is readonly.

**Action:** Choose the right place in the document for doclet adding.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10052: Error while connecting to the mapping tool web service. Please check your settings or server state.**

**Cause:** Failed to connect to mapping tool web service.

**Action:** Check your settings and server state.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10053: MappingToolView: registerDocumentMaps is failed. Exception: {0}**

**Cause:** Failed to call MappingToolView (method registerDocumentMaps).

**Action:** Reload client and try again.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10054: Web Service failed to remove mapping with id={0}. Exception: {1}**

**Cause:** Failed to remove mapping on server side.

**Action:** Check server side log.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10055: SessionService: IsAlive is failed. Exception: {0}**

**Cause:** Failed to update session.

**Action:** Check server side log.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10056: Repository: {0} is failed. Exception: {1}**

**Cause:** Failed to call repository session.

**Action:** Check server side log.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10057: Excel's Doclet publish is failed. Exception: {1}**

---

**Cause:** Failed to publish Excel's Doclet.  
**Action:** Restart workstation and try again.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10058: Web Service failed to ChangeMappingsTaxonomy {0}. Exception: {1}**

**Cause:** Failed to update server side information.

**Action:** Check server side log.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10059: Common View is not initialized.**

**Cause:** Client initialization was failed.

**Action:** Update client version.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10060: Mapping Tool Web Service initialization failed (Url={0}). Exception: {1}**

**Cause:** Failed to create mapping tool web service.

**Action:** Check your settings and server state.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10061: Unpacking Instance Package is failed. Exception: {0}**

**Cause:** Failed to extract data from package.

**Action:** Reload client and try again.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10062: Validation is failed. Exception: {0}**

**Cause:** Failed to validate report.

**Action:** Reload client and try again.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10063: Deleting of {0} is failed. Exception: {1}**

---

**Cause:** Failed to delete file.  
**Action:** Reload client and try again.  
**Level:** 32  
**Type:** ERROR  
**Impact:**

**DISCMAN-10064: Writing of {0} is failed. Exception: {1}**  
**Cause:** Failed to write file.  
**Action:** Reload client and try again.  
**Level:** 32  
**Type:** ERROR  
**Impact:**

**DISCMAN-10065: Export is failed. Exception: {0}**  
**Cause:** Failed to export report.  
**Action:** Reload client and try again.  
**Level:** 32  
**Type:** ERROR  
**Impact:**

**DISCMAN-10066: QueryDocumentMappings is failed (DocumentId={0}). Exception: {1}**  
**Cause:** Failed to server side mappings.  
**Action:** Check your settings and server state.  
**Level:** 32  
**Type:** ERROR  
**Impact:**

**DISCMAN-10067: Url is inconsistence. Exception: {0}**  
**Cause:** Failed to create url.  
**Action:** Check your settings and try again.  
**Level:** 32  
**Type:** ERROR  
**Impact:**

**DISCMAN-10068: Report Web Service initialization failed (Url={0}). Exception: {1}**  
**Cause:** Failed to create report web service.  
**Action:** Check your settings and server state.  
**Level:** 32  
**Type:** ERROR  
**Impact:**

**DISCMAN-10069: Create Doclet is failed. Exception: {0}**  
**Cause:** Failed to create doclet on server side.

---

**Action:** Check server side log.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10070: Create Report is failed. Exception: {0}**

**Cause:** Failed to create report on server side.

**Action:** Check server side log.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10071: Repository Web Service initialization failed (Url={0}). Exception: {1}**

**Cause:** Failed to create repository web service.

**Action:** Check your settings and server state.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10072: Security: {0} is failed. Exception: {1}**

**Cause:** Failed to call security service.

**Action:** Check server side log.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10073: UsGaapInstanceTransformer: GenerateReport is failed. Exception: {0}**

**Cause:** Error SEC View module.

**Action:** Check SEC View configuration.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-10074: Word Add-In cannot work with such user selection.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-20000: Sample Error Messages**

**Cause:**

---

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-20201: Failed to parse doclet mapping storage XML.**

**Cause:** Failed to parse doclet mapping storage XML.

**Action:** Check if doclet storage XML is well formed.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-20202: Failed to read doclet mapping storage file.**

**Cause:** Error encountered during reading doclet mapping storage file.

**Action:** Check if mapping storage file exists and accessible.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-20203: Doclet mapping storage file must be writable.**

**Cause:** Error encountered during writing doclet mapping storage file.

**Action:** Check if mapping storage file exists and accessible.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-20204: Failed to save doclet mapping.**

**Cause:** Error encountered during writing doclet mapping storage file.

**Action:** Check if mapping storage file exists and accessible.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-20205: Can't access session.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-20206: Can't login to content repository.**

**Cause:**

**Action:**



---

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-20207: Can't access content repository.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-20208: Repository path not found.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-20209: Can't read incoming document content.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-20210: Failed to generate doclet local identifier.**

**Cause:** Error encountered during generating doclet identifier.

**Action:** Check if database is up.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-20211: Specified doclet has not been found.**

**Cause:** Error encountered during checkOut doclet.

**Action:** Check if database is up and if doclet is created.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-20212: Failed to check in doclet.**

**Cause:** Error encountered during checkIn doclet.

**Action:** Check if database is up and if doclet is created.

**Level:** 32

**Type:** ERROR

---

**Impact:**

**DISCMAN-20213: Can't check in doclet. It must be checked out first.**

**Cause:** Error encountered during checkIn doclet.

**Action:** Check if report is checked out.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-20214: Checking in user has to be same who checked the doclet out.**

**Cause:** Error encountered during checkIn doclet.

**Action:** Check if user are allowed to check in.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-20215: Failed to check out doclet.**

**Cause:** Error encountered during checkOut doclet.

**Action:** Check if repository is up.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-20216: The doclet has never been checked in. There is no corresponding content in the repository.**

**Cause:** Error encountered during getting doclet content.

**Action:** Check if repository is up and if doclet is created.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-20217: The doclet has already been checked out.**

**Cause:** Error encountered during checkOut doclet.

**Action:** Check if doclet is already checked out.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-20218: Failed to get doclet's content.**

**Cause:** Error encountered during getting doclet content.

**Action:** Check if repository is up.

**Level:** 32

**Type:** ERROR

**Impact:**

---

**DISCMAN-30000: Sample Error Messages**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-30201: Failed to parse report storage XML.**

**Cause:** Error encountered during parsing report storage XML.

**Action:** Check if report storage XML is well formed.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-30202: Failed to read report storage file.**

**Cause:** Error encountered during reading report storage XML.

**Action:** Check if report storage XML is well formed.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-30203: Report storage file must be writable.**

**Cause:** Error encountered during writing report storage XML.

**Action:** Check if report storage XML has writable permission.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-30204: Failed to save report.**

**Cause:** Error encountered during saving report.

**Action:** Check if Repository Web Service is up.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-30205: Can't access session.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-30206: Report with the specified id has not been found.**

**Cause:** Error encountered during creating master document.

---

**Action:** Check if database is up and if report is created.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-30207: Failed to log audit record.**

**Cause:** Error encountered during auditing.

**Action:** Check if Audit Web Service is up.

**Level:** 32

**Type:** INFO

**Impact:**

**DISCMAN-40000: Sample Error Messages**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-40201: Authentication system is unavailable.**

**Cause:** Error encountered during Authentication system configuration.

**Action:** Check if Authentication system is configuration.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-40202: No state with given id found.**

**Cause:** Error encountered during Authentication system configuration.

**Action:** Check if Authentication system is configuration.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-40210: The user name or password is incorrect.**

**Cause:** Error encountered during login.

**Action:** Check if CSS is up and if input parameter credentials is correct.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-40220: Authorization failed. Your have no or limited access to Disclosure Management application.**

**Cause:** Error encountered during authorization.

**Action:** Check if Authorization system is configuration.

---

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-50000: Failed to initialize XBRL Processor.**

**Cause:** XBR not initialized properly.

**Action:** Check if resources are present for the XBRL Processing Engine.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-50001: Failed to shut down XBRL Processor.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50002: Failed to load the taxonomy.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50003: Failed to generate the tree structure for this taxonomy.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50004: Failed to get the tree node detail information.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50005: Failed to build ADF tree model.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

---

**Impact:**  
**DISCMAN-50006: Failed to get all links for taxonomy.**  
**Cause:**  
**Action:**  
**Level:** 32  
**Type:**  
**Impact:**

**DISCMAN-50007: Failed to get tree node information for this taxonomy.**  
**Cause:**  
**Action:**  
**Level:** 32  
**Type:**  
**Impact:**

**DISCMAN-50008: Error executing request for mapping tool. See Error logs for details.**  
**Cause:**  
**Action:**  
**Level:** 32  
**Type:**  
**Impact:**

**DISCMAN-50009: Failed to load property file mappingtool.properties.**  
**Cause:**  
**Action:**  
**Level:** 32  
**Type:**  
**Impact:**

**DISCMAN-50010: Please set up DISCMAN\_HOME in server first.**  
**Cause:**  
**Action:**  
**Level:** 32  
**Type:**  
**Impact:**

**DISCMAN-50011: Incorrect number of parameters passed. Expecting {0}, found {1}**  
**Cause:**  
**Action:**  
**Level:** 32  
**Type:**  
**Impact:**

---

**DISCMAN-50012: Error in generating XBRL instance. Please check server logs for details.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50013: Invalid date argument passed.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50014: Error in saving the mapping.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50015: Error in parsing the XML.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50016: Invalid argument passed in the generation of XBRL Instance. The taxonomy name is null or empty.**

**Cause:** The client passed an invalid parameter.

**Action:** Check if the document has mappings.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-50017: Error encountered in the querying of Grid mappings.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

---

**DISCMAN-50018: Error encountered in the querying of Document mappings.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50019: Invalid Argument passed when retrieving the taxonomy concept.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50020: Unknown application id passed.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50021: No reference specified in the context.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50022: No entity specified in the context.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50023: Failed to generate the dimension member tree for selected primary item.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50024: Failed to generate the tuple group tree.**



---

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50025: Unable to create explicit dimension mapping for dimension name {0} with dimension value {1}.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50026: Unable to create typed dimension mapping for dimension name {0} with dimension value {1}.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50027: Unable to create taxonomy selection tree.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50028: No XBRL concept mappings found. Cannot generate XBRL instance.**

**Cause:** No mapping was passed to the instance generator.

**Action:** Make sure at least one mapping is present when generating an instance.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-50029: Error in creating temporary file.**

**Cause:** Unable to create temporary file.

**Action:** Make sure the system temp file is present or user running the service has access to it.

**Level:** 32

**Type:** ERROR

**Impact:**

---

**DISCMAN-50030: Failed to load the taxonomy file list.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50031: Failed to generate the taxonomy file list tree.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50032: Failed to create UBMatrixTaxoAdapter object.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50033: Failed to close XBRL Processor.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50034: Failed to build the XBRL Query.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50035: Failed to get the concept label.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50036: Failed to get the concept.**

**Cause:**

---

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50037: Failed to find the arc for the taxonomy.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50038: Failed to find the dimension list for the taxonomy.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50039: Failed to validate instance document**

**Cause:** Failed to validate instance document.

**Action:** Check processing engine configured properly and taxonomy file is also valid.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-50040: Failed to execute DTS query**

**Cause:** Failed to generate HTML instance report from instance document.

**Action:** Check that instance document is proper and valid one.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-50041: Failed to generate HTML instance report from DTS object**

**Cause:** Failed to generate HTML instance report from DTS object.

**Action:** Check that DTS object is proper and valid one.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-50042: Failed to generate HTML instance report from instance file**

**Cause:** Failed to execute DTS query.

**Action:** Check the query syntax and other details passed.

---

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-50043: No mappings with specified id were found**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50044: Original taxonomy can't be found**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50045: Target taxonomy can't be found**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50046: Failed to change taxonomy**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-50047: Error encountered when registering the Document mappings.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-70000: Sample Error Messages.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

---

**Impact:**

**DISCMAN-70200: Error in the Audit Web Service.**

**Cause:** Error encountered while working with Audit Web Service.

**Action:** Check if the Audit Web Service is configured correctly.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-70210: Error while operating with storage.**

**Cause:** Error encountered while operating with storage.

**Action:** Check if the storage server is up or the storage connection.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-80000: Sample Error Messages.**

**Cause:**

**Action:**

**Level:** 32

**Type:**

**Impact:**

**DISCMAN-80200: Error in the Repository Web Service.**

**Cause:** Error encountered while working with Repository Web Service.

**Action:** Check if the Repository Web Service is configured correctly.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-80210: Error while operating with storage.**

**Cause:** Error encountered while operating with storage.

**Action:** Check if the storage server is up or the storage connection.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-80211: Error while connecting to the repository.**

**Cause:** Error encountered while connecting to the repository.

**Action:** Check user credentials.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-80212: Repository item doesn't exist at the specified path.**

---

**Cause:** Error encountered while getting item from the repository.

**Action:** Check if item exists.

**Level:** 32

**Type:** ERROR

**Impact:**

**DISCMAN-80213: Error while reading input content.**

**Cause:** Error encountered while reading input content.

**Action:** Check if input content is correct.

**Level:** 32

**Type:** ERROR

**Impact:**

---

## DMS-50700 to DMS-58045

**DMS-50700: initialization error**

**Cause:** (See message)

**Action:** Review the exception chain in log files for the cause and correct the specific problem.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**DMS-50701: security error**

**Cause:** (See message)

**Action:** Review the exception chain in log files for the cause and make sure that the appropriate permission has been granted.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**DMS-50702: The DMS Java class "{0}" could not be found.**

**Cause:** (See message)

**Action:** Review the classpath of the application and ensure that the class is available in a jar file or directory listed therein.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**DMS-50703: The LogWriter name "{0}" is reserved.**

**Cause:** (See message)

**Action:** Use a different name.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**DMS-50704: unable to create a new LogWriter: {0}**

**Cause:** (See message)

---

**Action:** Review the exception chain in log files for the cause and correct the specific problem.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**DMS-50705: attempting to create a concrete LogWriter instance with an invalid class ({0})**

**Cause:** (See message)

**Action:** Correct the declaration for the LogWriter to use a valid class.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**DMS-50706: invalid configuration property: name = "{0}", value = "{1}"**

**Cause:** (See message)

**Action:** Remove the property or correct its name or value to comply with the set of supported property names. If the property value is at fault then reviewing the base exception may provide more information on the manner of the fault (e.g. missing class, invalid directory name).

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**DMS-50707: unable to load configuration file "{0}"**

**Cause:** (See message)

**Action:** Review the exception chain in log files for the cause and make sure that the configuration file exists and the permissions on the file permit it to be read.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**DMS-50708: unable to parse metric rule document**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**DMS-50709: The metric rule resource {0} could not be read. Aggregation is off.**

**Cause:** (See message)

**Action:** Check that the resource is available and if necessary correct the content of the classpath.

**Level:** 1



---

**Type:** WARNING

**Impact:** Files

**DMS-50710: duplicated table "{1}" in metric table "{0}"**

**Cause:** (See message)

**Action:** Remove the <Union> or <Select> table from the metric table (it is already in use therein).

**Level:** 1

**Type:** WARNING

**Impact:** Other

**DMS-50711: Value "{1}" is invalid for attribute "{0}".**

**Cause:** (See message)

**Action:** Review the documentation for the correct use of the specific attribute.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**DMS-50713: invalid metric rule syntax**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to the metric rule documentation.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**DMS-50714: no DMS Archiver found**

**Cause:** (See message)

**Action:** Review the exception chain in log files for the cause and correct the specific problem.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**DMS-50715: no ONS found**

**Cause:** (See message)

**Action:** Review the exception chain in log files for the cause and correct the specific problem.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**DMS-50716: unable to create DMS ONS RPC server**

**Cause:** (See message)

**Action:** Review the exception chain in log files for the cause and correct the specific problem.

---

**Level:** 1

**Type:** WARNING

**Impact:** Other

**DMS-50717: unable to create DMS Publisher "{0}"**

**Cause:** (See message)

**Action:** Review the exception chain in log files for the cause and correct the specific problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**DMS-50719: unable to connect to the server and retrieve metrics at "{0}"**

**Cause:** (See message)

**Action:** Review the exception chain in log files for the cause and make sure that the server starts up.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**DMS-50720: unable to retrieve DMS metrics**

**Cause:** The HTTP server failed to handle the metric request.

**Action:** Make sure the HTTP server is able to handle metric requests.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**DMS-50722: unable to parse DMS metric document**

**Cause:** (See message)

**Action:** Review the exception chain in log files for the cause and correct the specific problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**DMS-50723: The reference to table {0} for aggregating DMS metrics is invalid.**

**Cause:** Columns from tables created by select and union elements are not valid in this context.

**Action:** Correct the aggregation statement in the metric rules.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**DMS-50725: unable to bind to port "{0}"**

**Cause:** (See message)

---

**Action:** Review the exception chain in log files for the cause and make sure port is free.

**Level:** 1

**Type:** ERROR

**Impact:** Ports

**DMS-50726: The metric configuration resource {0} could not be read.**

**Cause:** (See message)

**Action:** Check that the resource is available and if necessary correct the content of the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**DMS-50727: invalid metric configuration syntax**

**Cause:** (See message)

**Action:** Refer to XML schema "metric\_config.xsd" and correct the configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**DMS-50728: No writable metric repository directory "{0}" is available. The default metric archiving is off.**

**Cause:** (See message)

**Action:** Make sure that a writable metric repository exists.

**Level:** 1

**Type:** WARNING

**Impact:** Files

**DMS-50730: The repository directory "{0}" is not readable.**

**Cause:** (See message)

**Action:** Make sure that a readable metric repository exists.

**Level:** 1

**Type:** WARNING

**Impact:** Files

**DMS-50731: invalid value type "{0}" for column "{1}"**

**Cause:** (See message)

**Action:** Refer to the metric rule documentation for valid value types.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**DMS-50732: invalid value type for "Concat" operation: should be string**

**Cause:** (See message)

---

**Action:** Refer to the metric rule documentation for valid value types.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**DMS-50733: Arithmetic expression cannot be string type.**

**Cause:** (See message)

**Action:** Refer to the metric rule documentation for details of defining metrics.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**DMS-50734: missing value type for column <{0} Name="{1}">**

**Cause:** (See message)

**Action:** Refer to the metric rule documentation and add an explicit value type to the column.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**DMS-50735: invalid system function <Function Name="{0}">**

**Cause:** (See message)

**Action:** Refer to the metric rule documentation for a list of valid system functions.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**DMS-50736: missing an argument in <Expression> for column "{0}"**

**Cause:** (See message)

**Action:** Refer to the metric rule documentation and add an argument for the expression.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**DMS-50737: circular dependency found on aggregated metric tables {0}**

**Cause:** (See message)

**Action:** Remove circular dependency among aggregated tables.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**DMS-50738: invalid operation "{0}"**

**Cause:** (See message)

---

**Action:** Refer to the metric rule documentation for a list of valid operations.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**DMS-50742: Exception occurred while performing individual refresh operation for metric "{0}".**

**Cause:** (See message)

**Action:** Refer to log files for the cause and, if possible, correct the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**DMS-50743: Exception occurred while performing group refresh operation for metric "{0}". This failed refresh may have affected other metrics too.**

**Cause:** (See message)

**Action:** Refer to log files for the cause and, if possible, correct the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**DMS-50744: illegal argument values passed to method: {0}**

**Cause:** This is in internal error: a set of arguments have been passed to a method within the DMS component that are not appropriate for that method. This state should not have occurred and is indicative of a series of conditions that were not anticipated during development.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**DMS-50745: illegal program state detected: {0}**

**Cause:** This is in internal error: a program state has been detected within the DMS component that is unexpected or contradictory.

**Action:** Refer to log files for the cause and, if possible, correct the problem.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**DMS-50747: attempt to read an older metric rule document "{0}"**

**Cause:** Metric rule document "{0}" was older than the one currently used in the system.

**Action:** Make sure the version of the metric rules is equal to or higher than the one currently used in the system.

**Level:** 1

---

**Type:** WARNING

**Impact:** Configuration

**DMS-50748: attempt to read an metric rule document "{0}" that is equal to or older than the one currently used in the system**

**Cause:** The version of the metric rule document "{0}" was equal to or older than the one currently used in the system.

**Action:** Make sure the version of the metric rules is higher than the one currently used in the system.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**DMS-50749: OPMN is down.**

**Cause:** (See message)

**Action:** Start OPMN.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**DMS-50750: Metric parameter is null.**

**Cause:** (See message)

**Action:** Pass in a non-null metric.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**DMS-50751: Metric "{0}" passed in does not belong to "{1}".**

**Cause:** (See message)

**Action:** Pass in an appropriate metric.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**DMS-50752: One of the parameters for "{0}" is null or empty: {1}**

**Cause:** (See message)

**Action:** Do not pass in null or empty parameters.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**DMS-50753: wrong value type**

**Cause:** (See message)

**Action:** Pass in value with appropriate type.

**Level:** 1

---

**Type:** WARNING

**Impact:** Data

**DMS-50754: One of the parameters for "{0}" has unexpected value "{1}".**

**Cause:** (See message)

**Action:** Pass in correct values.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**DMS-50755: server unavailable: {0}**

**Cause:** (See message)

**Action:** Specify valid server or cluster names.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**DMS-50903: Metric aggregation is off due to errors.**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50904: unable to parse metric rule document: {0}**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**DMS-50907: Metric table "{0}" will not be built due to exception.**

**Cause:** (See message)

**Action:** Review the exception chain in log files for the cause and correct the specific problem.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50908: Name attribute is invalid in <ColumnDef> for metric table "{0}".**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

---

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50909: duplicated <ColumnDef Name="{1}"> for metric table "{0}"**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50910: Type attribute is invalid in <ColumnDef Name="{1}"> for metric table "{0}".**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50915: wrong value type "{2}" for column "{1}" in metric table "{0}". Expect value type "{3}".**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50916: Column "{0}" is missing in table "{1}" for metric table "{2}".**

**Cause:** (See message)

**Action:** Make sure to match <ColumnDef> with <Column>.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50917: Name attribute is empty in <ColumnGroup>.**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50918: Type attribute is invalid in <ColumnGroup Name="{1}">.**



---

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50919: empty group member in <ColumnGroup Name="{1}">**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50920: Attribute "{3}" of <{0}> is invalid in table "{1}" for metric table "{2}".**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50921: Column "{0}" is not defined in table "{1}" for metric table "{2}".**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50922: Attribute "{4}" of <{3} Name="{0}"> is invalid in table "{1}" for metric table "{2}".**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50923: Number of arguments for column "{3}" in <Expression> is "{0}" in table "{1}" for metric table "{2}", which is less than expected.**

**Cause:** (See message)

**Action:** Make sure to have at least two arguments.

**Level:** 1

---

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50924: Arguments for column "{2}" in <Expression> are missing in table "{0}" for metric table "{1}".**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50925: unexpected <Aggregation> in <Where> in table "{0}" for metric table "{1}"**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50926: Metric table "{2}" should not reference column "{0}" defined in table "{1}".**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50927: duplicated <{0}> in table "{1}" for metric table "{2}"**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50928: missing <{0}> in table "{1}" for metric table "{2}"**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

---

**DMS-50929: unexpected <{0}> in <Union Name="{1}"> for metric table "{2}"**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50930: unable to resolve column "{2}" in table "{0}" for metric table "{1}"**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50932: The value of attribute "{0}", "{1}", is less then the minimum "{2}".**

**Cause:** (See message)

**Action:** Review the documentation for the correct use of the specific attribute and give a valid value.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50933: unable to convert the value of attribute "{0}", "{1}", to a number**

**Cause:** (See message)

**Action:** Review the documentation for the correct use of the specific attribute and give a valid value.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50934: Sampling is not enabled for metric table "{0}".**

**Cause:** (See message)

**Action:** Refer to log files for the cause and, if possible, correct the problem.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50935: unable to convert value "{0}" to a number**

**Cause:** (See message)

**Action:** Refer to log files for the cause and, if possible, correct the problem.

**Level:** 1

**Type:** NOTIFICATION

---

**Impact:** Configuration

**DMS-50938: duplicated <{3} Name="{0}"> in table "{1}" for metric table "{2}"**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50940: The value of Attribute "Name" for <OrderBy> fails to match one of column names in table "{0}" for metric table "{1}".**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50941: unable to convert the value of <RowRetained>, "{0}", in table "{1}" to a number for metric table "{2}"**

**Cause:** (See message)

**Action:** Review the documentation for the correct use of the specific element and give a valid value.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50942: Only two tables can be referred to in outer join in table "{0}" for metric table "{1}".**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50945: missing <And>, <Or>, <Not>, or <Condition> in table "{0}" for metric table "{1}"**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50946: invalid <{0}> in table "{1}" for metric table "{2}"**

---

**Cause:** (See message)

**Action:** Specify one of <And>, <Or>, <Not>, or <Condition>.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50947: Number of arguments for condition is "{0}" in table "{1}" for metric table "{2}", which is less than expected.**

**Cause:** (See message)

**Action:** Make sure to have at least two arguments.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50948: missing condition argument in table "{0}" for metric table "{1}"**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50949: <Null> is not valid when operator is "{0}".**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50950: Exception occurred while retrieving metrics from metric repository.**

**Cause:** (See message)

**Action:** Review the exception chain in log files for the cause and correct the specific problem.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50951: wrong number of tokens in auto aggregation table name "{0}"**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

---

**Impact:** Configuration

**DMS-50952: invalid auto aggregation table name "{0}"**

**Cause:** (See message)

**Action:** Make sure that auto aggregation table names follow the patterns of <prefix>/<opcode>/<table\_name> or <prefix>/<opcode>/groupby/<column\_name1>/.../<column\_nameN>/<table\_name>.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50953: invalid aggregation operation "{1}" in auto aggregation table name "{0}".**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50955: invalid metric prefetch interval "{0}"**

**Cause:** (See message)

**Action:** Make sure to give a valid value for the metric prefetch interval in seconds.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50956: invalid metric prefetch removal cycle "{0}"**

**Cause:** (See message)

**Action:** Make sure to give a valid value for the metric prefetch removal cycle.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50957: Value of column "{1}" in table "{0}" is not a number.**

**Cause:** (See message)

**Action:** Review the documentation for the correct use of the specific element and make sure to give valid value.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50960: Column <{2}> should not be type "{3}" in table "{0}" for metric table "{1}".**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

---

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50961: Operation "{2}" should be type "{3}" in table "{0}" for metric table "{1}".**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50962: Arithmetic expression should not be String type in table "{0}" for metric table "{1}".**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50963: Column "{0}" expects a number.**

**Cause:** (See message)

**Action:** Review the exception chain in log files for the cause and correct the specific problem.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50964: Column <{2} Name="{3}"> is missing value type in table "{0}" for metric table "{1}".**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50965: <Function Name="{0}"> has invalid function name in table "{1}" for metric table "{2}".**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

---

**Impact:** Configuration

**DMS-50966: Metric table "{0}" has no key column. It will not be collected.**

**Cause:** (See message)

**Action:** Review the content of the metric rule document and check it for errors with respect to standard XML syntax rules and the metric rule documentation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50973: Caught Exception.**

**Cause:** (See message)

**Action:** Review the exception chain in log files for the cause and correct the specific problem.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50976: The use of one or more of the following deprecated properties [{0}] has been detected.**

**Cause:** (See message)

**Action:** Cease use of the deprecated properties and use one or more of these properties [{1}] instead.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**DMS-50977: a potentially conflicting use of properties. The use of one or more of the following deprecated properties [{0}] has been detected.**

**Cause:** (See message)

**Action:** Cease use of the deprecated properties and use one or more of these properties [{1}] instead. The deprecated properties will be ignored.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**DMS-50978: Exception occurred while registering metric rules "{0}"**

**Cause:** (See message)

**Action:** Review the exception chain in log files for the cause and correct the specific problem.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50980: Exception occurred while looking up runtime mbean server by JNDI name "{0}".**



---

**Cause:** (See message)

**Action:** Review the exception chain in log files for the cause and correct the specific problem.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**DMS-50981: Exception occurred while reading metric rules "{0}".**

**Cause:** (See message)

**Action:** Review the exception chain in log files for the cause and correct the specific problem.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**DMS-50983: Exception occurred while reading metric configuration file "{0}".**

**Cause:** (See message)

**Action:** Review the exception chain in log files for the cause and correct the specific problem.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**DMS-50985: Exception occurred while retrieving metrics from address "{0}" with query string "{1}".**

**Cause:** (See message)

**Action:** Review the exception chain in log files for the cause and correct the specific problem.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**DMS-50989: Exception occurred while retrieving metrics from address "{0}".**

**Cause:** (See message)

**Action:** Review the exception chain in log files for the cause and correct the specific problem.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**DMS-50990: Unable to register MBean "{0}"**

**Cause:** (See message)

**Action:** Review the exception chain in log files for the cause and correct the specific problem.

**Level:** 1

---

**Type:** NOTIFICATION

**Impact:** Other

**DMS-57003: Failed to process the wrapped DMS execution context {0} sent by {1} (user-agent: {2}) when requesting the resource {3}.**

**Cause:** By scrutinizing the incoming HTTP request DMS has attempted to detect and, if appropriate, make use of a wrapped execution context. That process has failed. This should not affect the processing of the servlet handling the request, but the ability to correlate the processing of this request with others to which it may related will have been adversely affected. A DMS execution context is an object that contains context information about the piece of work being performed at a particular moment in time. The type of context information carried by the DMS execution context may include the URL of the http request, the unique correlation key (ECID) assigned to that piece of work, etc - information that is useful for tracking requests though the system. The execution context does not carry user names, passwords or general application parameters. The DMS execution context should not be confused with application specific context objects, such as ADF-context or Faces-context, which are vital to the accurate execution of the application concerned.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**DMS-57004: Failed to initialize the DMS trace to be associated with DMS execution context {0}, that itself is associated with a request of resource {1}.**

**Cause:** A problem has occurred in the initialization of the trace system for this request. This should not affect the processing of the servlet handling the request but will be a problem if the trace (aggregate, debug or triggered) data was of value to the system's administrator.

**Action:** If the trace of this request was important, and has been affected by this error, then contact Oracle Support Services

**Level:** 1

**Type:** WARNING

**Impact:** Other

**DMS-57005: Failed to terminate the DMS trace associated with DMS execution context {0}, that itself is associated with a request of resource {1}.**

**Cause:** A problem has occurred in the finalization of the trace system for this request. This should not affect the processing of the servlet handling the request but will be a problem if the trace (aggregate, debug or triggered) data was of value to the system's administrator.

**Action:** If the trace of this request was important, and has been affected by this error, then contact Oracle Support Services

**Level:** 1

**Type:** WARNING

**Impact:** Other

**DMS-57006: Failed to deactivate the DMS execution context, {0}, associated with a request of resource {1}.**

---

**Cause:** A problem has occurred in the termination of the DMS execution context in place during the processing of the HTTP request. This should not affect the servlet handling the request, but may result in an invalid execution context being in place for the processing of future requests and possibly prevent accurate trace data from being gathered.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**DMS-57007: Failed to url-decode a wrapped execution context ({0}) due to a problem in the decoding process itself: {1}**

**Cause:** A problem has occurred while trying to url-decode a wrapped execution context found as a url-parameter. The consequence is that the execution context being passed from client to server can not be used. A failure in the DMS execution context feature does not generally result in a complete failure of the system or application making use of it, but it can result in misleading trace output or misleading correlation keys (ECID) in log messages: generally only the administrator will be aware of such changes in the behavior of an affected application.

**Action:** Determine if there is any code in the system that integrates with the Oracle DMS Context API (java package oracle.dms.context) but was not produced by Oracle. If there is no such code then contact Oracle Support Services. Otherwise scrutinize and test the non-Oracle code, and if necessary contact Oracle Support Services.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**DMS-57008: The execution context put in place at the start of the request, {0}, is not the execution context in place at the end of the request, {1}. The request is as follows: {2}**

**Cause:** When enabled to do so DMS associates an execution context with the resources (typically a thread) assigned to process an incoming request. In this case the context that DMS assigned at the start of the processing is not the one in place at the end of the processing. At some point during the processing the context has been changed. This could result in the loss of the ability to correlate the work performed across the complete request lifecycle for this request. A failure in the DMS execution context feature does not generally result in a complete failure of the system or application making use of it, but it can result in misleading trace output or misleading correlation keys (ECID) in log messages: generally only the administrator will be aware of such changes in the behavior of an affected application.

**Action:** Determine if there is any code in the system that integrates with the Oracle DMS Context API (java package oracle.dms.context) but was not produced by Oracle. If there is no such code then contact Oracle Support Services. Otherwise scrutinize and test the non-Oracle code, and if necessary contact Oracle Support Services.

**Level:** 1

**Type:** WARNING

---

**Impact:** Other

**DMS-57009: An error prevented selection of an appropriate execution context implementation for this environment - the feature will be disabled.**

**Cause:** At the point of initialization DMS needs to determine the environment in which it is operating in order to select the most appropriate implementation of the execution context feature. An unexpected error has occurred during that process. The DMS execution context feature will be disabled.

**Action:** Review the error to see if it can be resolved and then restart the server.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**DMS-58002: Could not create trace output directory ({0}) - Disabling {1} traces.**

**Cause:** An attempt to create a file system directory, into which trace files were to be written, has failed. Consequently no trace information can be saved and therefore, to save unnecessary burden on the system, trace information will not be collected.

**Action:** Check that the system user that owns the process has permissions to create such a directory. Check that the system has sufficient disk space to create a new directory.

**Level:** 1

**Type:** WARNING

**Impact:** Files

**DMS-58005: ignoring exception: {0}**

**Cause:** An unanticipated problem has occurred for which the runtime code can not take automatic remedial action.

**Action:** Refer to the base exception to see if there is a problem with the system that can be addressed (e.g. run low in disk space, run out of memory, etc).

**Level:** 1

**Type:** WARNING

**Impact:** Other

**DMS-58006: Problem encountered while removing old files from trace output directories.**

**Cause:** DMS was attempting to remove old files from the trace output directories but for some reason (see base exception) has failed.

**Action:** The system is unlikely to fail as a consequence of this error, but disk space will be used that would otherwise have been released. Refer to the base exception to see if the problem can be addressed, and consider deleting unrequired files manually (DMS no longer needs these old files so any or all of them can be removed).

**Level:** 1

**Type:** WARNING

**Impact:** Files

**DMS-58007: Problem encountered when closing file and associated streams.**

---

**Cause:** As part of the termination of a normal read or write operation on a file the file could not be closed.

**Action:** If a file can not be properly closed then the operating system's file-handle associated with that file may not be properly released. An operating system can manage only a finite number of file-handles and if they are not released then new file-handles can not be created. One consequence of a depletion of file-handles is that file input/output on the machine concerned may be forced to come to a stop. It is more likely, however, that this is a one-off problem and that Java will tidy up the file-handle internally. This type of problem suggests a problem with either the JVM, the operating system or the state of the machine on which they are running. Review the base exception to see if the issue can be resolved (e.g. memory issues, disk space issues, file access issues, etc.). In order to understand the scale of the problem continue to monitor the system for similar or related issues. If necessary stop and start the product to fully reinitialize the JVM on which it runs.

**Level:** 1

**Type:** WARNING

**Impact:** Files

**DMS-58008: error writing trace data to disk**

**Cause:** DMS has failed to create or use the objects required to write trace output to disk. The output intended to be written will be discarded.

**Action:** This type of problem suggests a problem with either the JVM, the operating system or the state of the machine on which they are running. Review the base exception to see if the issue can be resolved (e.g. memory issues, disk space issues, file access issues, etc.). In order to understand the scale of the problem continue to monitor the system for similar or related issues. If necessary stop and start the product to fully reinitialize the JVM on which it runs.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**DMS-58013: Problem encountered aggregating trace: {0}.**

**Cause:** DMS has failed to perform the aggregation process on the trace data collected during the handling of this particular task or servlet request. A DMS trace is composed of a series of DMS trace events that represent an operation performed within DMS. Examples of trace events are: a sensor update, the start and end of an HTTP request. An aggregate trace is the result of aggregating trace data for tasks (typically HTTP requests) associated with the same URI. Failure to perform the aggregation processing for this task will mean that the summary data for the URI concerned will not be accurate.

**Action:** Review exception details and the log for any seemingly related messages. If the problem has come from the JVM itself: This type of problem suggests a problem with either the JVM, the operating system or the state of the machine on which they are running. Review the base exception to see if the issue can be resolved (e.g. memory issues, disk space issues, file access issues, etc.). In order to understand the scale of the problem continue to monitor the system for similar or related issues. If necessary stop and start the product to fully reinitialize the JVM on which it runs. Otherwise the problem is with the code written to run on the JVM: Determine if there is any code in the system that integrates with the Oracle DMS Trace API (java package oracle.dms.trace) but was not produced by

---

Oracle. If there is no such code then contact Oracle Support Services. Otherwise scrutinize and test the non-Oracle code in order to isolate the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**DMS-58014: Failed to handle REQUEST\_BEGIN for {0}. The trace will not be aggregated.**

**Cause:** DMS did not find the trace event that marks the start of the series of trace events to be associated with an HTTP request. Without that particular trace event DMS can not be sure that the set of collected trace events will accurately represent the actions performed during that HTTP request and consequently will not process them further. Failure to perform the aggregation processing for this task will mean that the summary data for the URI concerned will not be accurate.

**Action:** Review exception details and the log for any seemingly related messages. If the problem has come from the JVM itself: This type of problem suggests a problem with either the JVM, the operating system or the state of the machine on which they are running. Review the base exception to see if the issue can be resolved (e.g. memory issues, disk space issues, file access issues, etc.). In order to understand the scale of the problem continue to monitor the system for similar or related issues. If necessary stop and start the product to fully reinitialize the JVM on which it runs. Otherwise the problem is with the code written to run on the JVM: Determine if there is any code in the system that that integrates with the Oracle DMS Trace API (java package oracle.dms.trace) but was not produced by Oracle. If there is no such code then contact Oracle Support Services. Otherwise scrutinize and test the non-Oracle code in order to isolate the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**DMS-58015: Can not get the current task's execution context and therefore the trace events that occurred during this task's lifecycle can not be used to contribute to the aggregate trace associated with the task's URL.**

**Cause:** In order to perform the process of trace aggregation for a completed task the execution context for that task is required. In this case the execution context could not be found; without the execution context object the trace aggregation process can not be performed. A DMS trace is composed of a series of DMS trace events that represent an operation performed within DMS. Examples of trace events are: a sensor update, the start and end of an HTTP request. An aggregate trace is the result of aggregating trace data for tasks (typically HTTP requests) associated with the same URI. Failure to perform the aggregation processing for this task will mean that the summary data for the URI concerned will not be accurate.

**Action:** Determine if there is any code in the system that that integrates with the Oracle DMS Trace API (java package oracle.dms.trace) but was not produced by Oracle. If there is no such code then contact Oracle Support Services. Otherwise scrutinize and test the non-Oracle code in order to isolate the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

---

**DMS-58016: Can not get the URI associated with the current thread's recent activities.**

**Cause:** In order to perform the process of trace aggregation for a completed task the URI associated with that task is required. In this case the URI could not be found; without the URI the trace information collected cannot be aggregated. A DMS trace is composed of a series of DMS trace events that represent an operation performed within DMS. Examples of trace events are: a sensor update, the start and end of an HTTP request. An aggregate trace is the result of aggregating trace data for tasks (typically HTTP requests) associated with the same URI. Failure to perform the aggregation processing for this task will mean that the summary data for the URI concerned will not be accurate.

**Action:** Determine if there is any code in the system that integrates with the Oracle DMS Trace API (java package oracle.dms.trace) but was not produced by Oracle. If there is no such code then contact Oracle Support Services. Otherwise scrutinize and test the non-Oracle code in order to isolate the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**DMS-58017: The maximum number of allowed aggregates has already been reached. Traces referring to URLs not already being aggregated will not contribute to aggregate information.**

**Cause:** In order to prevent too much memory being consumed by the DMS trace system the current request will not be added to the aggregate trace set because the maximum number of URIs for which trace data will be aggregated has already been reached. A DMS trace is composed of a series of DMS trace events that represent an operation performed within DMS. Examples of trace events are: a sensor update, the start and end of an HTTP request. An aggregate trace is the result of aggregating trace data for tasks (typically HTTP requests) associated with the same URI.

**Action:** If aggregate trace information is not required for this request there is no action required. Otherwise please review the value of the system property oracle.dms.trace.maxAggregates.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**DMS-58018: Cannot delete old trace file: {0}.**

**Cause:** An attempt to delete a file system file has failed (the deletion attempt was intended to keep files organized and their number manageable). The system is unlikely to fail as a consequence of this error, but disk space will be used that would otherwise have been released.

**Action:** This type of problem suggests a problem with either the JVM, the operating system or the state of the machine on which they are running. Review the base exception to see if the issue can be resolved (e.g. memory issues, disk space issues, file access issues, etc.). In order to understand the scale of the problem continue to monitor the system for similar or related issues. If necessary stop and start the product to fully reinitialize the JVM on which it runs.

**Level:** 1

**Type:** WARNING

---

**Impact:** Files

**DMS-58019: Cannot generate aggregate trace data because the trace system failed initialization.**

**Cause:** (See message)

**Action:** Review the log files for reports of other problems relating to initialization failure. Where possible correct those other problems and restart the system. Failure of the trace subsystem should not affect the ability of the system to execute, but will prevent traces from being produced.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**DMS-58020: failure writing DMS configuration file {0}**

**Cause:** An error occurred attempting to save the DMS configuration file.

**Action:** Check that the process has permission to write the configuration file. Review log files for more information on this issue.

**Level:** 1

**Type:** WARNING

**Impact:** Files

**DMS-58021: failure loading DMS configuration file {0}**

**Cause:** An error occurred attempting to load the DMS configuration file.

**Action:** Check that the process has permission to read the configuration file, and the file exists. Review log files for more information on this issue.

**Level:** 1

**Type:** WARNING

**Impact:** Files

**DMS-58022: failure registering DMS configuration MBean {0}**

**Cause:** An error occurred attempting to register the DMS configuration MBean.

**Action:** Check that the J2EE container is up. Review log files for more information.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**DMS-58023: failure activating DMS configuration**

**Cause:** An error occurred attempting to activate the DMS configuration.

**Action:** Review the log files for more information.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**DMS-58024: cannot create a condition for filter {0}**

**Cause:** A condition could not be created for the condition filter at runtime.



---

**Action:** Check that the filter has been configured correctly.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**DMS-58025: cannot instantiate class {0} for destination with id = {1}**

**Cause:** A Destination could not be created at runtime.

**Action:** Check that the Destination has been configured correctly.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**DMS-58026: cannot not set property {0} on an instance of class {1} for destination with id = {2}**

**Cause:** The configuration of a destination specified one or more properties to be set on the destination before the destination was used. A problem was encountered trying to set the property listed in the message the precise details of which are also shown in the message.

**Action:** Verify that the property exists on the class being instantiated as the destination, and that the value is legal for that property.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**DMS-58028: will not associate filter {0} and destination {1} - one or both are null or have null IDs.**

**Cause:** (See message)

**Action:** Check the configuration of the filter and destination, and search the log file for other messages that may report problems creating instances of the filter or destination.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**DMS-58033: Can not associate a destination, id={0}, with a filter, id={1} if the filter declares that it will not pass any events.**

**Cause:** An instance of a filter should declare the set of event types in which it has an interest. In this particular case the set is empty and thus the filter is apparently interested in no events at all. Such a filter serves no sensible purpose and therefore will be ignored.

**Action:** Check the log file for other error relating to this filter to see if there were problems in its construction. Also verify the configuration of the filter and its associated destination (some filters are created implicitly to cooperate with a destination, so the configuration may only specify details of the destination).

**Level:** 1

**Type:** WARNING

---

**Impact:** Configuration

**DMS-58035: The required JRockit Flight Recorder classes can not be found. The JFRDestination can not function without them.**

**Cause:** The JRockit Flight Recorder classes are only available on Oracle JRockit.

**Action:** Check that the system is running using JRockit.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**DMS-58040: The FlightRecorder class is declaring that it is not the JRockit native implementation and thus DMS will not use it.**

**Cause:** DMS only makes use of the JRockit FlightRecorder implementation that is native to JRockit. The FlightRecorder class available to DMS is apparently not a native implementation and will therefore not be used by DMS.

**Action:** This situation will not affect the runtime operation of the system, but in order to avoid the message being reported again either switch to using the JRockit JVM or remove the eventRoute with id=JFRDestination from dms\_config.xml.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**DMS-58042: The DMS configuration file is invalid, and may not be viewed. No updates are allowed until the file has been fixed manually.**

**Cause:** The DMS configuration file is invalid. No updates are allowed until the file has been fixed.

**Action:** Review the log files for more information, and correct the problem in the configuration file

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**DMS-58045: DMS classic tracing will not be performed because the DMS context manager is disabled.**

**Cause:** The classic trace features of DMS are dependent upon the DMS context manager being enabled. The DMS context manager is not enabled, and therefore the classic trace features can not operate.

**Action:** Review the java startup parameters to see if the DMS context manager has been disabled (check for properties with a prefix of 'oracle.dms.context')

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

---

## DVT-02012 to DVT-26021

**DVT-02012: Column {0} exceeds boundary {1}.**

**Cause:** The specified column number was greater than the total number of columns.

**Action:** Get the total number of columns, by calling the getColumnCount method of the graph or of the column header in the pivot table. Then specify a column that does not exceed the total number of columns.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-02013: Row {0} exceeds boundary {1}.**

**Cause:** The specified row number was greater than the total number of rows.

**Action:** Get the total number of rows, by calling the getRowCount method of the graph or of the column header in the pivot table. Then specify a row that does not exceed the total number of rows.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-02015: Slice {0} exceeds boundary {1}.**

**Cause:** The specified slice number was greater than the total number of slices.

**Action:** Specify a slice that does not exceed the total number of slices.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-02016: Layer {0} exceeds boundary {1}.**

**Cause:** The specified layer was greater than the total number of layers that are available on the given edge.

**Action:** Specify a layer that does not exceed the total number of layers.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**DVT-02017: Series {0} exceeds boundary {1}.**

**Cause:** The specified series was greater than the total series that is available in the graph.

**Action:** Specify a zero-based series index that does not exceed the total series. The `Graph.getDisplaySeries` method should provide the number of series that are displayed in the graph. Or, if `Graph.isDataRowShownAsASeries` returns true, then `Graph.getRowCount` returns the number of series that can be displayed. If `Graph.isDataRowShownAsASeries` returns false, then `Graph.getColumnCount` returns the total number of series that can be displayed.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-02018: Edge {0} exceeds boundary {1}.**

**Cause:** The specified edge was greater than the total number of edges that are available on the given edge. Valid edges for methods that require an edge are: `DataDirector.COLUMN_EDGE`, `DataDirector.ROW_EDGE`, and `DataDirector.PAGE_EDGE`.

**Action:** Specify a valid edge constant.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-02019: Current DataSource does not support required type: {0}.{1}.**

**Cause:** The `DataSource` did not support the required type of data in its `DataMap`. For example, the view requested `DataMap.DATA_GROUPSORT` information, and the `DataSource` that the view uses did not supply group sort information.

**Action:** Request support for the required data types in the `DataSource`, or use a different `DataSource`.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-02020: DTD file cannot be found.**

**Cause:** The specified DTD could not be found. The XML parser needed the DTD in order to validate XML files.

**Action:** Ensure that the specified DTD file exists, or disable XML validation. DTDs for Data Visualization components are in their respective packages. To turn off validation, call `Dataview.setXMLValidated(false);`.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-03000: No Mergeable object is provided.**

**Cause:** No default Mergeable object was provided to resolve rules.

---

**Action:** Provide at least one default Mergeable object, so that rules can be resolved. For more information about Mergeable objects, see the Javadoc for the `oracle.dss.rules.Mergeable` interface.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-03001: attempt to call merge(Mergeable) on an incompatible Mergeable class**

**Cause:** An attempt was made to merge incompatible Mergeable classes. Only Mergeable objects of the same class can be merged. For example, `ViewStyle` objects can be merged, but a `ViewStyle` cannot be merged with a `ViewFormat`.

**Action:** Merge two classes that are compatible. For more information, see the Javadoc for the `oracle.dss.rules.RuleBundle` class.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-06000: unexpected data error from Pivot Table data model**

**Cause:** An unexpected exception was thrown by the Pivot Table's data model.

**Action:** Log a bug against the application. Verify that the Pivot Table's data model is configured properly.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DVT-06001: no Converter for data type {0} during Pivot Table text formatting**

**Cause:** The application could not create a Converter for a specific data type. The most likely reason was that a Converter was not registered for that data type.

**Action:** Log a bug against the application. Verify that the application can create a default Converter for all data types rendered by the Pivot Table.

**Level:** 1

**Type:** TRACE

**Impact:** Configuration

**DVT-08000: unexpected data error from Data Model**

**Cause:** An invalid operation was performed by Data Model.

**Action:** Log a bug against the application. Verify that the Data model is configured properly.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**DVT-09042: MetadataManager cannot return the measure dimension.**

**Cause:** Invalid or corrupt metadata was found in the database.

**Action:** Repair problems with or rebuild the database schema.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-09511: illegal pivot operation**

**Cause:** Dimensions or locations were provided that would not result in a legal pivot operation.

**Action:** Check the given arguments and reconcile them with the layout of the current query.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-09512: illegal swap operation**

**Cause:** Dimensions or locations were provided that would not result in a legal swap operation.

**Action:** Check the given arguments and reconcile them with the layout of the current query.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-09513: illegal swap edges operation**

**Cause:** Edges were provided that would not result in a legal swap operation.

**Action:** Check the given edges and reconcile them with the layout of the current query.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-09515: No query is defined.**

**Cause:** A method was called that requires an existing query.

**Action:** Create a query before calling the method.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-09532: The specified dimension or item is invalid: {0}.**

**Cause:** A dimension or item name was specified that cannot be found in the current database.

**Action:** Ensure that all named dimensions or items are in the current database.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-10000: Event is not consumable.**

---

**Cause:** An attempt was made to consume an event that is not consumable.

**Action:** No action is necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-10101: Handler fails to handle UserObject.**

**Cause:** A failed attempt was made to bind or look up an object whose state could not be set or retrieved.

**Action:** Check the underlying error stack to find the root cause of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-10105: BSession is not specified.**

**Cause:** An instance of BSession was not set on the MetadataManager object.

**Action:** Set a BSession on the MetadataManager object, using the setSession method.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-10107: User cannot set the specified property: {0}.**

**Cause:** An attempt was made to set a property other than Label on an MDOObject.

**Action:** Ensure that only the Label property is set on the MDOObject.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-10108: MetadataManager cannot disconnect the connection.**

**Cause:** MetadataManager could not disconnect the connection.

**Action:** Check the underlying error stack to find the root cause of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-10109: MetadataManager cannot free the connection.**

**Cause:** The MetadataManager could not release the connection.

**Action:** Check the underlying error stack to find the root cause of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-10110: MetadataManager cannot retrieve the OracleConnection.**

---

**Cause:** The MetadataManager could not retrieve the OracleConnection.

**Action:** Check the underlying error stack to find the root cause of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-10300: cannot bind a context**

**Cause:** An attempt was made to save a folder using the bind method.

**Action:** To create a new folder, use the createSubcontext method. To copy a folder to another folder, use the copy method. To move a folder to another folder, use the move method.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-10301: The specified attribute is not valid.**

**Cause:** The key or the value of one or more attributes in the method was not valid.

**Action:** Specify a valid attribute key and value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-10302: Name {0} is invalid; the name must not be an empty string.**

**Cause:** The specified name was not valid. For any methods of BIContext that require a name argument, the user cannot specify a null value. The following methods also require that the name argument not be an empty string: bind, rebind, createSubcontext, destroySubcontext, rename and unbind.

**Action:** Specify a name whose value is not an empty string.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-10303: The specified object is invalid.**

**Cause:** An attempt was made to save a UserObject that contains an object that is not accepted by the specific driver.

**Action:** Set the appropriate object in UserObject for the specified driver type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-10304: The specified search control is invalid.**

**Cause:** The specified search control was not valid for one of the following reasons: The search scope was not valid. It must be one of the following: OBJECT\_SCOPE, ONELEVEL\_SCOPE, SUBTREE\_SCOPE, ONELEVEL\_SCOPE\_WITH\_FOLDERS,



---

or SELECTIVE\_ONELEVEL\_SCOPE. The specified time limit was a negative number. The specified count limit was a negative number.

**Action:** Review the possible reasons and take the appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-10305: Object with name {0} already exists.**

**Cause:** An attempt was made to save an object with a name that was already bound to an object in the storage system, or the destination folder already contained an object that was bound to that particular name when the copy or move operation was performed.

**Action:** If this is a save operation, then use the rebind method to overwrite the existing object that is bound with that name. If this is a copy operation, then specify a different target name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-10306: Object with name {0} cannot be found.**

**Cause:** An attempt was made to retrieve, copy, or move an object that does not exist.

**Action:** No action is necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-10307: User lacks sufficient privileges to perform the operation.**

**Cause:** An attempt was made to perform an operation that requires specific privileges, for example, saving an object to a folder in which the user does not have write access.

**Action:** Request that the owner or user of the folder with full-control privileges assign sufficient privileges to the appropriate user to perform the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-10308: The object is not a valid context.**

**Cause:** Depending on the operation, this error could occur because: The destination folder for copy or move operations was not a valid folder. The name argument in list, listBindings, or search operations did not resolve to a folder.

**Action:** Specify a valid folder name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**DVT-10309: This operation is not supported.**

**Cause:** The operation was not supported by the driver in which the operation was invoked.

**Action:** No action is necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-10310: unknown exception**

**Cause:** An unknown error occurred.

**Action:** Check the underlying error stack to find the root cause of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-10311: error while adding, removing, or modifying attributes**

**Cause:** An error has occurred while performing the modifyAttributes operation.

**Action:** Check the underlying error stack to find the root cause of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-10313: A circular reference is detected.**

**Cause:** The operation attempted to use aggregated, copied, or moved objects that cause a circular reference.

**Action:** If this is a bind or rebind operation, then ensure that no circular reference exists in the aggregate tree. If this is a copy or move operation on a folder, then ensure that the parent folder is not copied or moved to the subfolder.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-10315: The specified folder path is invalid.**

**Cause:** An attempt was made to save an object in a folder path that does not exist.

**Action:** Specify a valid folder path.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-10500: MetadataManager driver cannot be instantiated.**

**Cause:** A failure occurred while creating an instance of the MetadataManager driver. The failure can happen only if the MetadataManager drivers are interfaces or are abstract classes.

**Action:** Check the underlying error stack to find the root cause of the problem.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**DVT-10501: illegal attempt to access the MetadataManager driver**

**Cause:** A failure occurred while creating an instance of the MetadataManager driver. The failure can happen only if the MetadataManager drivers are not public or are not in the MetadataManager package.

**Action:** Check the underlying error stack to find the root cause of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-10502: MetadataManager driver is not found.**

**Cause:** A failure occurred while creating an instance of the MetadataManager driver. The failure can happen only if the necessary jar files are not referenced in the CLASSPATH setting.

**Action:** Ensure that all necessary classes are included in the CLASSPATH setting.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-10503: User cannot set the specified property: {0}.**

**Cause:** An attempt was made to set a property other than Label on the MeasureDimension MDOObject.

**Action:** Ensure that only the Label property is set on the MeasureDimension MDOObject.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-10504: MetadataManager cannot retrieve the OracleConnection.**

**Cause:** The MetadataManager could not retrieve the OracleConnection.

**Action:** Check the underlying error stack to find the root cause of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-12000: unexpected error**

**Cause:** An unknown exception occurred in a call to a different class.

**Action:** Check the underlying error stack to find the root cause of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-16001: BISession is not specified.**

**Cause:** An instance of BISession was not set on the Connection object.

---

**Action:** Set a BSession on the Connection object using the setSession method.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-16002: Operation is incomplete because there is no database connection.**

**Cause:** The connection was not initialized.

**Action:** Invoke the connect method before performing this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-16003: cannot set the connection object because a connection already exists**

**Cause:** Could not set the connection object because a connection already exists.

**Action:** Disconnect and set the connection object again.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-16004: The operation cannot complete because the object retrieved is a nonserializable object.**

**Cause:** The operation was not completed because the retrieved object was not serializable.

**Action:** Retrieve an object only if it does not require serialization.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-16400: Connection driver cannot be instantiated.**

**Cause:** A failure occurred while creating an instance of the Connection driver. The failure can happen only if the Connection drivers are interfaces or abstract classes.

**Action:** Check the underlying error stack to find the root cause of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-16401: illegal attempt to access the Connection driver**

**Cause:** A failure occurred while creating an instance of the Connection driver. The failure can happen only if the Connection drivers are not public or are not in the Connection package.

**Action:** Check the underlying error stack to find the root cause of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**DVT-16402: Connection driver is not found.**

**Cause:** A failure occurred while creating an instance of the Connection driver. The failure can happen if the necessary jar files are not referenced in the CLASSPATH setting.

**Action:** Ensure that all necessary classes are included in the CLASSPATH setting.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-18008: No QueryContext is defined.**

**Cause:** A method was called that requires an existing QueryContext object.

**Action:** Create a QueryContext object before calling the method.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-18009: No Selection is defined.**

**Cause:** A method was called that requires an existing Selection object.

**Action:** Create a Selection object before calling the method.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-18010: The QueryAccess object cannot be created.**

**Cause:** A QueryAccess object could not be created.

**Action:** Verify that a valid QueryContext object exists. To create a QueryAccess object, use syntax such as queryContext.createQueryAccess.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-18011: A DataAccess object cannot be created.**

**Cause:** A DataAccess object could not be created.

**Action:** Verify that a valid QueryAccess object exists and that the dimension that is specified for the Selection is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-18012: unexpected error**

**Cause:** An unknown exception occurred in a call to a different class.

**Action:** Check the underlying error stack to find the root cause of the problem.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**DVT-26000: unable to find connection in {0}**

**Cause:** Either the map configuration was not valid, or connection information was missing.

**Action:** Check the map configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-26001: theme \"{0}\" cannot be displayed: missing value property**

**Cause:** The value attribute of the theme was null.

**Action:** Check the value attribute of the theme.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-26002: theme \"{0}\" cannot be displayed: invalid row key at row {1}**

**Cause:** The specified row either did not have a row key, or the row id in the row key was null.

**Action:** Check the key and row id for the specified row.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-26004: theme \"{0}\" cannot be displayed: row {1} with id={2} does not have a data value**

**Cause:** The specified row did not have a data value.

**Action:** Check the data value for the specified row.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-26005: theme \"{0}\" cannot be displayed: row {1} with id={2} does not have a location value**

**Cause:** The specified row did not have a location value.

**Action:** Check the location value for the specified row.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-26006: Labels for one or more rows of theme \"{0}\" are missing.**

**Cause:** Some rows in the theme did not have a location label.

**Action:** Check the location labels in the theme.

**Level:** 1

---

Type: WARNING

Impact: Programmatic

**DVT-26008: Theme \"{0}\" does not have any data.**

**Cause:** The specified theme did not return any rows.

**Action:** Check whether the specified theme is correctly returning no data.

Level: 1

Type: WARNING

Impact: Data

**DVT-26009: unable to geocode data at row {0} of theme \"{1}\": {2}**

**Cause:** The specified data could not be geocoded.

**Action:** Change the location value for the specified row.

Level: 1

Type: WARNING

Impact: Data

**DVT-26010: The mouse click behavior of {0} is to render a popup, but there is no popup facet in the map.**

**Cause:** The map had no popup facet, but the leftClickBehavior property was specified to render a popup.

**Action:** Check whether the mouse click behavior is correct.

Level: 1

Type: WARNING

Impact: Data

**DVT-26011: The right-click behavior of {0} is to render a popup, but there is no popup facet in the map.**

**Cause:** The map had no popup facet, but the rightClickBehavior property was specified to render a popup.

**Action:** Check whether the right-click behavior is correct.

Level: 1

Type: WARNING

Impact: Data

**DVT-26012: The number of labels specified in legendLabels does not match the number of buckets. Legend labels: {0}, Buckets: {1}**

**Cause:** The number of legend labels and buckets did not match.

**Action:** Check the number of legend labels.

Level: 1

Type: WARNING

Impact: Data

**DVT-26013: unable to geocode the theme data: no Geocoder URL specified in {0}**

**Cause:** Either the map configuration was not valid, or connection information for the Geocoder was missing.

---

**Action:** Check the map configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-26014: unable to show all theme data for theme \"{0}\": multiple data values for {1} are specified but only the first data value is shown**

**Cause:** Duplicate location data values were found.

**Action:** Check the data for duplicate location values.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**DVT-26015: theme \"{0}\" cannot be displayed: no longitude data at row {1}**

**Cause:** The specified row did not have a longitude value.

**Action:** Check the longitude for the specified row.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-26016: theme {0} cannot be displayed: no latitude data at row {1}**

**Cause:** The specified row did not have a latitude value.

**Action:** Check the latitude for the specified row.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-26017: unable to connect to MapViewer at {0}**

**Cause:** A MapViewer server was not found at the specified map URL.

**Action:** Check whether the connection URL is correct and the MapViewer servlet can accept new requests.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-26018: unable to connect to Geocoder at {0}**

**Cause:** The component was unable to connect to the Geocoder at the specified URL.

**Action:** Check whether the connection URL is correct and the Geocoder can accept new requests.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-26019: unable to find a map of id {0} for mapToolbar {1}**



---

**Cause:** The mapId attribute of the specified mapToolbar was not correct.

**Action:** Check the mapId attribute of the specified mapToolbar.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-26020: A map tag cannot have more than one mapOverview tag.**

**Cause:** There were more than one mapOverview tags in the map tag.

**Action:** Remove any extra mapOverview tags.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**DVT-26021: A map tag cannot have more than one mapLegend tag.**

**Cause:** There were more than one mapLegend tags in the map tag.

**Action:** Remove any extra mapLegend tags.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic



---

## ECSF-10001 to ECSF-11405

**ECSF-10001: Error: {0}**

**Cause:** An error occurred.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ECSF-10002: unexpected error. Cmd {0} fails.**

**Cause:** An unexpected error occurred.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10003: I/O error when reading input.**

**Cause:** An I/O error occurred.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10004: cannot access system.console to obtain password securely**

**Cause:** System.console was not available.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10005: invalid command; cannot connect**

**Cause:** An invalid command was specified.

**Action:** Specify a valid command.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**ECSF-10006: not connected; cannot execute command**

**Cause:** A command was issued before a connection was made.

**Action:** Issue the CONNECT command before proceeding.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10007: Command {0} is invalid.**

**Cause:** An invalid command was specified.

**Action:** Specify a valid command.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10008: invalid command syntax**

**Cause:** A command with invalid syntax was issued.

**Action:** Specify the command using the correct syntax.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10009: already connected; cannot execute command**

**Cause:** User was already connected.

**Action:** Disconnect before attempting to reconnect.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10010: already disconnected; cannot execute command**

**Cause:** User was already disconnected.

**Action:** Reconnect before attempting to disconnect.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10011: already managing an instance; cannot execute command**

**Cause:** The command was issued while an instance was already being managed.

**Action:** Specify a valid command.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**ECSF-10012: Invalid ID passed in for {0}. ID value must be a number.**

**Cause:** The ID specified was not a number.

**Action:** Specify a valid ID.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10013: command not issued in an engine instance context; cannot execute command**

**Cause:** The command was not issued from within an engine instance context.

**Action:** Manage an instance with the MANAGE command before proceeding.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10014: command not initialized; cannot execute command**

**Cause:** An invalid command was issued.

**Action:** Specify a valid command.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10015: searchable object {0} already active; cannot execute command**

**Cause:** Activate command was issued while searchable object was already activated.

**Action:** Specify a valid command.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10016: searchable object {0} already inactive; cannot execute command**

**Cause:** Deactivate was issued while searchable object was already deactivated.

**Action:** Specify a valid command.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10017: searchable object {0} not deployed; cannot execute command**

**Cause:** Requested command could not be performed.

**Action:** Specify a valid command.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**ECSF-10018: searchable object {0} already deployed; cannot execute command**

**Cause:** The command was issued while searchable object was already deployed.

**Action:** Specify a valid command.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10019: cannot set up context**

**Cause:** An error occurred while setting up the context.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10020: {0} {1} is currently deployed and cannot be deleted.**

**Cause:** The requested command could not be performed.

**Action:** Specify a valid command.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10021: {0} {1} is currently deployed and cannot be updated.**

**Cause:** The requested command could not be performed.

**Action:** Specify a valid command.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10022: The searchable object with id {0} cannot be removed from search category {1}, which is currently deployed.**

**Cause:** The command was issued on a deployed search category.

**Action:** Undeploy the search category before you remove the searchable object from it.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10023: The searchable object with id {0} cannot be added to search category {1}, which is currently deployed.**

**Cause:** The command was issued on a deployed search category.

**Action:** Undeploy the search category before you add the searchable object to it.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**ECSF-10024: cannot find {0} with ID {1}**

**Cause:** The requested command could not be performed.

**Action:** Specify a valid object.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10025: {0} is invalid parameter; cannot execute command**

**Cause:** An invalid parameter was specified.

**Action:** Specify a valid parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10026: the searchable object with id {0} already associated with schedule {1}; cannot execute command**

**Cause:** The command was issued while the searchable object was already associated to a schedule.

**Action:** Object can only be associated with one schedule.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10027: the searchable object with id {0} is not associated with an instance; cannot execute command**

**Cause:** The command was issued while the searchable object was not associated with an instance.

**Action:** Associate the searchable object with an instance before proceeding.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10028: the searchable object with id {0} is not associated with category id {1}; cannot execute command**

**Cause:** The command was issued while the searchable object was not associated with the category.

**Action:** Associate the searchable object with a category before proceeding.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10029: the searchable object {0} is not deployed; cannot execute command**

**Cause:** An attempt was made to associate an undeployed searchable object.

**Action:** Deploy the searchable object to SES before proceeding.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**ECSF-10030: searchable object {0} activated; cannot execute command**

**Cause:** An attempt was made to undeploy the searchable object while it was activated.

**Action:** Deactivate the searchable object before proceeding.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10031: index schedule {0} not deployed; cannot execute command**

**Cause:** An attempt was made to start the index schedule before it was deployed.

**Action:** Deploy the index schedule before proceeding.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10032: searchable objects not associated with {0} {1}; cannot execute command**

**Cause:** An attempt was made to deploy without associated searchable objects.

**Action:** Associate one or more searchable objects before proceeding.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10033: the searchable object {0} is not associated with the instance {1}**

**Cause:** An attempt was made to remove the searchable object from an instance that it is not associated with.

**Action:** Specify a valid command.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10034: invalid value {0} passed in for field {1}, value must be of type {2}**

**Cause:** Invalid values were entered.

**Action:** Specify a valid value.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10035: Valid value for {0} should be of type {1}.**

**Cause:** An invalid value was entered.

**Action:** Specify a valid value.

**Level:** 1



---

**Type:** ERROR

**Impact:** Process

**ECSF-10036: Valid values for {0} are {1} or {2}.**

**Cause:** Invalid values were entered.

**Action:** Specify a valid value.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10037: {0} is not a valid LOV value for field {1}.**

**Cause:** An invalid value was entered.

**Action:** Specify a valid value.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10038: The value entered is too long for field {0}. The value must be less than {1} characters.**

**Cause:** An invalid value was entered.

**Action:** Specify a valid value.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10039: invalid field name. {0} does not exist in {1}.**

**Cause:** An invalid field name was entered.

**Action:** Specify a valid field name.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10040: field {0} in {1} not updatable**

**Cause:** An attempt was made to update a non-updatable field.

**Action:** Do not attempt to update this field.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10041: cannot set field {0} in {1} during {2}**

**Cause:** An attempt was made to set a field when this action was not allowed.

**Action:** Specify a valid command.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**ECSF-10042: The following required fields must contain values.**

**Cause:** Values were not set for all the required fields.

**Action:** Set values for all the required fields before proceeding.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10043: Instance {0} is being managed; Use UNMANAGE before deleting the instance.**

**Cause:** An attempt was made to delete a managed instance.

**Action:** Unmanage the instance before deleting it.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10044: {0} are not found.**

**Cause:** The object was not found.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10045: scope {LOCAL | GLOBAL} not found**

**Cause:** The scope was not found.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10046: searchable object not activated**

**Cause:** The requested command could not be performed.

**Action:** Specify a valid command.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10047: the searchable object has not been associated**

**Cause:** The requested command could not be performed.

**Action:** Specify a valid command.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**ECSF-10048: cannot connect. Use CONNECT command to try again.**

**Cause:** The requested command could not be performed.

**Action:** Specify a valid command.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10049: object not created**

**Cause:** The requested command could not be performed.

**Action:** Specify a valid command.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10050: searchable object not deactivated**

**Cause:** The requested command could not be performed.

**Action:** Specify a valid command.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10051: object not deleted**

**Cause:** The requested command could not be performed.

**Action:** Specify a valid command.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10052: object not deployed**

**Cause:** The requested command could not be performed.

**Action:** Specify a valid command.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10053: cannot disconnect**

**Cause:** The requested command could not be performed.

**Action:** Specify a valid command.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10054: cannot import**

**Cause:** The requested command could not be performed.

---

**Action:** Specify a valid command.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10055: context for instance not created**

**Cause:** The requested command could not be performed.

**Action:** Specify a valid command.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10056: {0} not registered.**

**Cause:** The requested command could not be performed.

**Action:** Specify a valid command.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10057: searchable object not disassociated**

**Cause:** The requested command could not be performed.

**Action:** Specify a valid command.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10058: parameter not updated**

**Cause:** The requested command could not be performed.

**Action:** Specify a valid command.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10059: schedule not started**

**Cause:** The requested command could not be performed.

**Action:** Specify a valid command.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10060: schedule not stopped**

**Cause:** The requested command could not be performed.

**Action:** Specify a valid command.

---

**Level: 1**

**Type: ERROR**

**Impact: Process**

**ECSF-10061: object not undeployed**

**Cause:** The requested command could not be performed.

**Action:** Specify a valid command.

**Level: 1**

**Type: ERROR**

**Impact: Process**

**ECSF-10062: instance context not reset**

**Cause:** The requested command could not be performed.

**Action:** Specify a valid command.

**Level: 1**

**Type: ERROR**

**Impact: Process**

**ECSF-10063: object not updated**

**Cause:** The requested command could not be performed.

**Action:** Specify a valid command.

**Level: 1**

**Type: ERROR**

**Impact: Process**

**ECSF-10064: cannot find file {0}; automation aborted**

**Cause:** The file could not be found.

**Action:** Contact the system administrator.

**Level: 1**

**Type: ERROR**

**Impact: Process**

**ECSF-10065: cannot load database driver**

**Cause:** The database driver could not be found.

**Action:** Ensure that the database driver is available in the class path.

**Level: 1**

**Type: ERROR**

**Impact: Process**

**ECSF-10066: cannot connect to database**

**Cause:** The database connection could not be established.

**Action:** Contact the system administrator.

**Level: 1**

**Type: ERROR**

---

**Impact:** Process

**ECSF-10067: database connection not released**

**Cause:** The database connection could not be released.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10068: Frequency Type cannot be null.**

**Cause:** A null value was entered for Frequency Type.

**Action:** Set Frequency Type to a non-null value.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10069: invalid Time Between Launches value for hourly schedule; valid values are from 1 to 23.**

**Cause:** An invalid Time Between Launches value was entered for the hourly schedule.

**Action:** Enter a Time Between Launches value from 1 to 23 for the hourly schedule.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10070: invalid Time Between Launches value for daily schedule; valid values are from 1 to 99.**

**Cause:** An invalid Time Between Launches value was entered for the daily schedule.

**Action:** Enter a Time Between Launches value from 1 to 99 for the daily schedule.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10071: invalid Time Between Launches value for the weekly/monthly schedule; valid values are from 1 to 12.**

**Cause:** An invalid Time Between Launches value was entered for the weekly/monthly schedule.

**Action:** Enter a Time Between Launches value from 1 to 12 for the weekly/monthly schedule.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10072: invalid Schedule Launch Day value for weekly schedule; valid values are from Monday to Sunday.**

---

**Cause:** An invalid Schedule Launch Day value was entered for the weekly schedule.

**Action:** Enter a Schedule Launch Day value from Monday to Sunday for the weekly schedule.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10073: invalid Schedule Launch Day value for monthly schedule; valid values are from 1 to 31.**

**Cause:** An invalid Schedule Launch Day value was entered for the monthly schedule.

**Action:** Enter a Schedule Launch Day value from 1 to 31.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10074: invalid Schedule Launch Time value; valid values are from 1:00 AM to 12:00 AM.**

**Cause:** An invalid Schedule Launch Time value was entered.

**Action:** Enter a Schedule Launch Time value from 1:00 AM to 12:00 AM.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10076: the searchable object with id {0} is not associated with a schedule; cannot execute command**

**Cause:** The command was issued while the searchable object was not associated with a schedule.

**Action:** Associate the searchable object with a schedule before proceeding.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10077: The searchable object with id {0} cannot be removed from schedule {1}, which is currently deployed.**

**Cause:** The command was issued on a deployed index schedule.

**Action:** Undeploy the schedule before removing the searchable object.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10078: The searchable object with id {0} cannot be added to schedule {1}, which is currently deployed.**

**Cause:** The command was issued on a deployed index schedule.

**Action:** Undeploy the schedule before adding the searchable object.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10079: The searchable object {0} is not associated with the schedule {1}**

**Cause:** An attempt was made to remove the searchable object from a schedule that it is not associated with.

**Action:** Specify a valid command.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10101: Searchable object {0} cannot be found; cannot deploy searchable object.**

**Cause:** An invalid searchable object was specified.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10102: Search category {0} cannot be found; cannot deploy search category.**

**Cause:** An invalid search category was specified.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10103: Searchable object {0} cannot be found; cannot undeploy searchable object.**

**Cause:** An invalid searchable object was specified.

**Action:** Ensure that the searchable object is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10104: Search category {0} cannot be found; cannot undeploy search category.**

**Cause:** An invalid search category was specified.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10105: cannot deploy searchable object {0} to SES**

**Cause:** An attempt was made to deploy a searchable object to SES. This is not allowed.

**Action:** Check the exception message for more information.



---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10106: cannot deploy search category {0} to SES**

**Cause:** An attempt was made to deploy a search category to SES. This is not allowed.

**Action:** Check the exception message for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10107: Search category {0} contains no searchable objects; cannot deploy search category.**

**Cause:** An attempt was made to deploy a search category containing no searchable objects.

**Action:** Ensure that one or more searchable objects are associated with the search category before deploying it.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10108: cannot deploy index schedule {0}**

**Cause:** An error occurred while deploying the index schedule.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10109: cannot undeploy searchable object {0}**

**Cause:** Searchable object did not exist in SES.

**Action:** Check the exception message for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10110: cannot undeploy search category {0}**

**Cause:** Search category did not exist in SES.

**Action:** Check the exception message for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10111: cannot undeploy index schedule {0}**

**Cause:** Index schedule did not exist in SES.

---

**Action:** Check the exception message for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10112: Searchable object {0} is deployed, but LastTimeCrawled cannot be set.**

**Cause:** LastTimeCrawled could not be set for the searchable object in the database.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10113: cannot register identity plug-in to SES for user {0}**

**Cause:** An error occurred while registering the identity plug-in.

**Action:** Check the exception message for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10114: cannot start schedule {0} on engine instance {1}; schedule cannot be started in its current state: {2}**

**Cause:** An attempt was made to start a schedule with status Launching or Executing or Stopping.

**Action:** Ensure that the schedule is not in a Launching, Executing, or Stopping state.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10115: cannot stop schedule {0} on engine {1}; schedule cannot be stopped in its current state: {2}**

**Cause:** An attempt was made to stop a schedule with status Failed or Scheduled or Stopping.

**Action:** Ensure that the schedule is not in a Failed, Scheduled, or Stopping state.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10116: cannot start schedule {0} on engine instance {1}**

**Cause:** An error occurred while starting the schedule.

**Action:** Check the exception message for more information.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**ECSF-10117: cannot stop schedule {0} on engine instance {1}**

**Cause:** An error occurred while stopping the schedule.

**Action:** Check the exception message for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10118: cannot get search categories from SES; SES\_QUERY\_SERVICE parameter for the engine instance cannot be null.**

**Cause:** The proxy URL for the engine instance was missing.

**Action:** Ensure that the SES\_QUERY\_SERVICE parameter is set for the engine instance.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10119: cannot get search categories from SES**

**Cause:** An error occurred while getting the search categories from the SES.

**Action:** Check the exception message for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10120: cannot get SES session for engine {0}**

**Cause:** An error occurred while getting the SES session.

**Action:** Check the exception message for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10121: cannot get status for schedule {0} on engine instance {1}**

**Cause:** An error occurred while getting this schedule status from the SES.

**Action:** Check the exception message for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10122: cannot get schedules for engine instance {0}**

**Cause:** An error occurred while getting the schedules from the SES.

**Action:** Check the exception message for more information.

**Level:** 1

**Type:** ERROR

---

**Impact:** Data

**ECSF-10123: cannot get schedule {0} on engine instance {1}**

**Cause:** An error occurred while getting this schedule from the SES.

**Action:** Check the exception message for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10124: The {0} parameter for the engine instance cannot be null.**

**Cause:** One of the service URL parameter value was null or invalid.

**Action:** Ensure that all service URL parameters are set in the engine instance.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10125: cannot initialize deployment manager**

**Cause:** An error occurred during initialization of deployment manager.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10126: cannot find security plug-in class for searchable object {0}**

**Cause:** No security plug-in class was defined for the searchable object.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10128: invalid repetitive interval for the index schedule**

**Cause:** Valid schedule interval was not specified.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10129: cannot log on to the SES server**

**Cause:** Invalid login credentials were entered.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**ECSF-10130: cannot find view object {0}**

---

**Cause:** The view object did not exist in the deployed application.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10131: cannot log out of SES session**

**Cause:** An error occurred during SES proxy service logout operation.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**ECSF-10132: cannot find SES reference for search category {0}**

**Cause:** One or more of the search categories bound to this query did not exist on the SES instance.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10133: The access URL length is greater than max 740 characters allowed by SES. Truncating the access URL by excluding stored attributes. Action: {0} in SO: {1}.**

**Cause:** The access URL exceeded 740 characters in length.

**Action:** Ensure that the SearchAction definition is properly configured.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**ECSF-10134: cannot convert date {0} for attribute {1} in searchable object {2} to format: EEE MMM dd HH:mm:ss z yyyy**

**Cause:** The date in the attribute was formatted incorrectly.

**Action:** Ensure that the attribute values are in the correct format.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10135: cannot convert number {0} to BigDecimal format**

**Cause:** The number in the attribute was formatted incorrectly.

**Action:** Ensure that the attribute values are in the correct format.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**ECSF-10136: cannot find data groups on SES instance {0}**

**Cause:** Data groups were not found on this SES instance.

**Action:** Ensure that valid data groups are created on the SES instance.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10137: Field {0} does not exist on the search category used for this query.**

**Cause:** A nonexistent field was used in the query.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10138: cannot generate redirect URL for action {0}**

**Cause:** Null values were specified for the primary keys.

**Action:** Ensure that the values for the primary keys are not null.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10139: unexpected ECSF Query Error: {0}**

**Cause:** An unexpected query error occurred.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10140: cannot log in to SES at {2} with proxy name {0} for user {1}**

**Cause:** An error occurred during SES proxy service login operation.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**ECSF-10141: Security service is not responding; cannot execute query.**

**Cause:** The security service was not responding.

**Action:** Retry the query. If the same problem occurs, then contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10142: cannot re-query SES after session reset**

---

**Cause:** The security service was not running on the ECSF server.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10143: cannot update searchable object {0} in SES**

**Cause:** Searchable object could not be updated in the SES.

**Action:** Check the exception message for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10144: cannot update spelling correction flag in SES**

**Cause:** An error occurred while setting the spelling correction flag.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10145: cannot retrieve query configuration from SES**

**Cause:** An error occurred while retrieving the query configuration.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10201: cannot create {0} {1}**

**Cause:** An error occurred while creating a new record in the database.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10202: cannot update {0} {1}**

**Cause:** An error occurred while updating the record in the database.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10203: cannot delete {0} {1}**

**Cause:** An error occurred while deleting the record from the database.

**Action:** Contact the system administrator.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10204: cannot select {0} {1}**

**Cause:** An error occurred while executing the SELECT statement against the database.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10205: The global parameters can not be listed.**

**Cause:** An error occurred while executing the SELECT statement against the database.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10206: cannot remove searchable object {0} from search category {1}**

**Cause:** An error occurred while deleting the record from the ECSF\_SIO\_SIG\_INT table.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10207: cannot associate searchable object {0} to search category {1}**

**Cause:** An error occurred while associating the searchable object to the search category.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10208: cannot commit current transaction**

**Cause:** An error occurred while committing the current transaction.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10209: cannot roll back current transaction**

**Cause:** An error occurred during roll back operation.



---

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10210: {0} of {1} does not result in a single row in the database for ID {2} {3} - rows {4}.**

**Cause:** The return value of the executeUpdate SQL operation was not equal to one.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10212: Searchable Object {1} is deployed in SES server; cannot delete search engine instance {0}.**

**Cause:** An attempt was made to delete the search engine instance while a searchable object associated with the instance was deployed on the SES server.

**Action:** Undeploy the searchable object before deleting the search engine instance.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10213: Search category {1} is deployed in SES server; cannot delete search Engine Instance {0}.**

**Cause:** An attempt was made to delete the search engine instance while a search category associated with the instance was deployed on the SES server.

**Action:** Undeploy the search category before deleting the search engine instance.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10214: Index schedule {1} is deployed on SES server; cannot delete search engine instance {0}.**

**Cause:** An attempt was made to delete the search engine instance while an index schedule associated with the instance was deployed on the SES server.

**Action:** Undeploy the index schedule before deleting the search engine instance.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10215: No searchable objects are associated with index schedule {0}; cannot deploy.**

**Cause:** An attempt was made to deploy an index schedule that had no searchable objects associated with it.

---

**Action:** Associate one or more searchable objects with the index schedule before deploying it.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10216: cannot list global parameters**

**Cause:** An error occurred while retrieving the global parameters from the database.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10217: cannot update the parameter**

**Cause:** An error occurred while updating the parameter in the database.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10218: cannot list search engine instances**

**Cause:** An error occurred while retrieving the search engine instances from the database.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10219: cannot update the search engine instance**

**Cause:** An error occurred while updating the search engine instance record in the database.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10220: cannot create the search engine instance**

**Cause:** An error occurred while creating the search engine instance record in the database.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**ECSF-10221: cannot delete the search engine instance**

**Cause:** An error occurred while deleting the search engine instance record from the database.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10222: cannot register the identity plug-in on this SES instance**

**Cause:** An error occurred while registering the identity plug-in on the SES instance.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10223: cannot list search engine types**

**Cause:** An error occurred while retrieving the search engine types from the database.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10224: cannot create the searchable object**

**Cause:** A record in the ECSF\_SEARCH\_INDEX\_OBJECT table in the database could not be created.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10225: cannot delete the searchable object**

**Cause:** A record from the ECSF\_SEARCH\_INDEX\_OBJECT table in the database could not be deleted.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10226: cannot update the searchable object**

**Cause:** A record in the ECSF\_SEARCH\_INDEX\_OBJECT table in the database could not be updated.

**Action:** Contact the system administrator.

**Level:** 1

---

**Type:** ERROR

**Impact:** Data

**ECSF-10227: cannot list searchable objects that are not associated with any engine instance**

**Cause:** An attempt was made to get a list of searchable objects that were not associated with any engine instances.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10228: cannot deploy the searchable object to SES**

**Cause:** There was an error deploying this searchable object to SES.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10229: cannot undeploy the searchable object from SES**

**Cause:** There was an error undeploying this searchable object from SES.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10230: cannot create a search category**

**Cause:** A record in the ECSF\_SEARCH\_INDEX\_GROUP table in the database could not be created.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10231: cannot delete the search category**

**Cause:** A record from the ECSF\_SEARCH\_INDEX\_GROUP table in the database could not be deleted.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10232: cannot update the search category**

**Cause:** A record in the ECSF\_SEARCH\_INDEX\_GROUP table in the database could not be updated.

**Action:** Contact the system administrator.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10233: cannot associate searchable object to a search category**

**Cause:** A record in the ECSF\_SIO\_SIG\_INT table in the database could not be created to associate the searchable object with the search category.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10234: cannot remove searchable object from a search category**

**Cause:** A record from the ECSF\_SIO\_SIG\_INT table in the database could not be deleted.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10235: cannot deploy the search category**

**Cause:** There was an error deploying this search category to SES.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10236: cannot undeploy the search category**

**Cause:** There was an error undeploying this search category from SES.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10237: cannot import external search categories**

**Cause:** There was an error importing external categories from SES.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10238: cannot create the index schedule**

**Cause:** A record in the ECSF\_INDEX\_SCHEDULE table in the database could not be created.

**Action:** Contact the system administrator.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10239: cannot update the index schedule**

**Cause:** A record in the ECSF\_INDEX\_SCHEDULE table in the database could not be updated.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10240: cannot delete the index schedule**

**Cause:** A record from the ECSF\_INDEX\_SCHEDULE table in the database could not be deleted.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10241: cannot deploy the index schedule**

**Cause:** There was an error deploying this index schedule to SES.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10242: cannot undeploy the index schedule**

**Cause:** There was an error undeploying this index schedule from SES.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10243: cannot start the index schedule**

**Cause:** There was an error while attempting to start the schedule operation.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10244: cannot stop the index schedule**

**Cause:** There was an error while attempting to stop the schedule operation.

**Action:** Contact the system administrator.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10245: cannot localize the connection**

**Cause:** An error occurred while localizing the connection.

**Action:** Contact the database administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10246: cannot save the password to the credential store**

**Cause:** The password for the given user on the engine instance could not be saved.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10247: unknown error while validating a customized field**

**Cause:** An unknown error occurred during validation of a customized field expression.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10248: cannot validate the customized title**

**Cause:** The customized title expression was not valid.

**Action:** Use a valid expression for the customized title.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10249: cannot validate the customized body**

**Cause:** The customized body expression was not valid.

**Action:** Use a valid expression for the customized body.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10250: cannot validate the customized keywords**

**Cause:** The customized keywords expression was not valid.

**Action:** Use a valid expression for the customized keywords.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10251: cannot validate customized default action title**

**Cause:** The customized default action title expression was not valid.

**Action:** Use a valid expression for the customized default action title.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10252: The engine types cannot be listed.**

**Cause:** An error occurred while executing the SELECT statement against the database.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10253: Engine instances for engine type {0} cannot be listed**

**Cause:** An error occurred while executing the SELECT statement against the database.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10254: The searchable objects cannot be listed.**

**Cause:** An error occurred while executing the SELECT statement against the database.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10255: The searchable objects for schedule {0} cannot be listed.**

**Cause:** An error occurred while executing the SELECT statement against the database.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10256: The search categories for instance {0} cannot be listed.**



---

**Cause:** An error occurred while executing the SELECT statement against the database.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10257: The external categories for instance {0} cannot be listed.**

**Cause:** An error occurred while executing the SELECT statement against the database.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10258: Index schedules for instance {0} cannot be listed.**

**Cause:** An error occurred while executing the SELECT statement against the database.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10259: Searchable objects for instance {0} cannot be listed.**

**Cause:** An error occurred while executing the SELECT statement against the database.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10260: SQL statement {0} cannot be executed for id {1}**

**Cause:** An error occurred while executing the SELECT statement against the database.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10261: cannot retrieve external search categories**

**Cause:** There was an error retrieving external categories from SES.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

---

**Impact:** Data

**ECSF-10301: cannot convert the given ROWID to String**

**Cause:** An invalid ROWID value was provided.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10302: cannot delete the change log records for range {0} to {1}**

**Cause:** An error occurred while attempting to delete the change log records.

**Action:** Check the database.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10303: cannot close the prepared statement**

**Cause:** An error occurred while attempting to close the prepared statement.

**Action:** Check the database.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10304: cannot construct an attachment**

**Cause:** An error occurred during the construction of the attachment.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10305: cannot link {0} with predicate {1}; error message: {2}**

**Cause:** An error occurred during the crawl for child documents.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10306: cannot create child documents**

**Cause:** An error occurred during the crawl for child documents.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10307: cannot create {0}**

---

**Cause:** An error occurred during the creation of the crawlable factory.

**Action:** Check the configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ECSF-10308: cannot handle custom incremental crawl**

**Cause:** An error occurred during the start of an initial or incremental crawl operation.

**Action:** Check the configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ECSF-10309: No searchable object is specified; cannot start data crawl.**

**Cause:** An attempt was made to start the data crawl when no searchable object was specified.

**Action:** Check the configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ECSF-10310: cannot set status**

**Cause:** An error occurred at the end of an initial or incremental crawl operation.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10311: cannot execute `getAcl(SearchContext, IndexableDocument) {0}`**

**Cause:** An error occurred while crawling a secure document.

**Action:** Check the configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**ECSF-10312: cannot split table**

**Cause:** An error occurred while starting the RowIdSplitter operation.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10313: cannot get number of blocks**

---

**Cause:** An error occurred during the get number of blocks operation.

**Action:** Check the database.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10314: cannot get number of records during EnvInfoProvider initialization**

**Cause:** An error occurred during EnvInfoProvider initialization.

**Action:** Check the database.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10315: cannot load properties from properties file**

**Cause:** An error occurred during EnvInfoProvider initialization.

**Action:** Check the configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ECSF-10316: cannot set up search context; searchable object is null.**

**Cause:** Searchable object was null.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ECSF-10317: CreateCrawlable returns null; cannot start crawler**

**Cause:** CreateCrawlable returned null.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10318: cannot start crawler**

**Cause:** An error occurred while attempting to create the control feed.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10319: The crawler is not started.**

**Cause:** An error occurred while attempting to start the crawler.

**Action:** Contact the system administrator.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10320: cannot close indexer**

**Cause:** An error occurred while closing the indexer.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10321: cannot index the documents**

**Cause:** An error occurred while indexing the documents.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10322: cannot start crawler**

**Cause:** An error occurred while starting the crawler.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10323: cannot close resultset to complete the crawl**

**Cause:** An error occurred while attempting to close the resultset.

**Action:** Check the database.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10324: cannot close statement to complete the crawl**

**Cause:** An error occurred while attempting to close the statement.

**Action:** Check the database.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10325: cannot get predicate for workunit**

**Cause:** An error occurred while getting a predicate for the workunit.

**Action:** Check the configuration.

**Level:** 1

**Type:** ERROR

---

**Impact:** Data

**ECSF-10326: cannot index documents due to indexing error**

**Cause:** An error occurred while indexing the documents.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10327: cannot create indexed document**

**Cause:** An error occurred while attempting to create the indexed document.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10328: cannot evaluate the expression for {0} of {1}**

**Cause:** An error occurred while processing the expression fields.

**Action:** Check the configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ECSF-10329: cannot start crawler due to failed connection**

**Cause:** A connection was not made.

**Action:** Check the database.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10330: cannot close indexer**

**Cause:** An error occurred while closing the indexer.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10331: cannot split ECSF change log table**

**Cause:** An error occurred during the CREATE CHANGE LOG WORK UNITS operation.

**Action:** Check the database.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**ECSF-10332: cannot process date range**

**Cause:** An error occurred during the incremental crawl operation.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10333: Last crawl time of {0} is null.**

**Cause:** An error occurred during the incremental crawl operation.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10334: cannot create child documents**

**Cause:** An error occurred during the extract operation.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10335: cannot release the connection**

**Cause:** An error occurred during the release of the connection.

**Action:** Check the database.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10336: cannot load the display name for the search category**

**Cause:** An error occurred during the get display name operation.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ECSF-10337: cannot load the display name for the searchable object**

**Cause:** An error occurred during the get display name operation.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ECSF-10338: cannot read searchable object**

**Cause:** An error occurred while the searchable object was loading.

---

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ECSF-10339: cannot create facet entries for {0} on {1}**

**Cause:** An error occurred while creating the FacetDef object.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ECSF-10340: cannot load engine parameters**

**Cause:** An error occurred during engine instance loading.

**Action:** Check the configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ECSF-10341: Facets are not supported for this searchable object.**

**Cause:** An attempt was made to load facets for this searchable object that does not support facets.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ECSF-10342: cannot get search engine**

**Cause:** An error occurred while attempting to get the search engine.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ECSF-10343: cannot create configuration file {0}**

**Cause:** An error occurred during the get configuration file operation.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ECSF-10344: The SES\_QUERY\_SERVICE parameter is missing for the engine instance; cannot get search categories from SES.**

**Cause:** The SES\_QUERY\_SERVICE parameter value for this engine instance was missing from the ECSF\_PARAMETER table in the database.



---

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10345: cannot get search categories from SES**

**Cause:** Search categories could not be obtained from SES.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10346: cannot load searchable object {0} for category {1} in engine instance {2}**

**Cause:** The searchable object defined in the database was not properly configured.

**Action:** Ensure that the searchable object defined in the database is properly configured.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10347: failed DBMS\_PARALLEL\_EXECUTE\_EXTENTS view check**

**Cause:** An error occurred while attempting to find a view.

**Action:** Check the database.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10348: cannot find the DBMS\_PARALLEL\_EXECUTE\_EXTENTS view; will use ECSF\_AD\_EXTENTS view instead**

**Cause:** The specified database version was incorrect.

**Action:** Check the database.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10365: cannot index documents due to security error**

**Cause:** A security error occurred during indexing.

**Action:** Check the configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**ECSF-10366: cannot create NUM type workunit because VO contains no key fields**

**Cause:** An error occurred while attempting to create the NUM workunit.

---

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10367: cannot create NUM type workunit because VO contains more than one key field**

**Cause:** An error occurred while attempting to create the NUM workunit.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10368: cannot use NUM Splitter because VO contains no key fields**

**Cause:** An error occurred while attempting to use the NUM Splitter.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10369: cannot use NUM Splitter because VO contains more than one key field**

**Cause:** An error occurred while attempting to use the NUM Splitter.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10370: data type {1} of field {2} is not supported for NUM Splitter**

**Cause:** An error occurred while attempting to use the NUM Splitter.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10401: cannot get GUID for user {0}**

**Cause:** An error occurred during the get user GUID operation.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**ECSF-10402: The specified permission is denied for user {0}.**

**Cause:** The user was not granted with the specified permission for the current security context.

---

**Action:** Check the security configuration to make sure that the user is provisioned with the proper security permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**ECSF-10403: cannot assert user {0}**

**Cause:** An error occurred during the user assertion operation.

**Action:** Check the user.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**ECSF-10404: cannot encode URL in UTF-8**

**Cause:** An error occurred during URL encoding.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10405: cannot decode URL in UTF-8**

**Cause:** An error occurred during URL decoding.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ECSF-10406: cannot provision engine instances**

**Cause:** An error occurred during the provisioning of engine instances.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ECSF-10407: cannot create security service**

**Cause:** An error occurred during security service creation.

**Action:** Check the configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ECSF-10408: cannot retrieve application ID from topology**

**Cause:** An error occurred during Application ID retrieval from Topology.

**Action:** Check the configuration.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ECSF-10409: cannot retrieve application ID from EJB properties**

**Cause:** An error occurred during Application ID retrieval from EJB properties.

**Action:** Check the configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ECSF-10410: cannot read attachment for attached document**

**Cause:** An error occurred while attempting to read the attachment.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10411: cannot retrieve business event connection factory to raise event using Fabric**

**Cause:** An attempt was made to raise an event when BusinessEventConnectionFactory was not configured properly.

**Action:** Ensure that the Business Events are configured properly.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10412: cannot create business event connection to raise event using Fabric**

**Cause:** Raise event using Fabric failed because BusinessEventConnection could not be created.

**Action:** Ensure that the Business Events are configured properly.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10413: cannot raise event using SQL**

**Cause:** An attempt was made to raise events using SQL when the event could not be written to the ECSF\_SEARCHABLE\_CHANGE\_LOG table in the database.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10414: invalid business event connection**

---

**Cause:** An attempt was made to raise an event while BusinessEventConnectionFactory was invalid.

**Action:** Ensure that the Business Events are configured properly.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ECSF-10415: invalid SearchContext; user not bound to it**

**Cause:** A user was not bound to SearchContext.

**Action:** Bind a user to the SearchContext before performing any search related actions.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10416: password not available in credential store; cannot get password for user {0}**

**Cause:** Password was not available in the credential store.

**Action:** Update passwords in credential store using ECSF Admin Utility.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**ECSF-10417: cannot retrieve Application IDs for the ECSF component**

**Cause:** Topology and ECSF Application Id override returned no Application Ids.

**Action:** Check Topology and/or ECSF Application Id override configuration.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ECSF-10418: invalid Plugin ID in properties file; the ID must be a number.**

**Cause:** An invalid Plugin ID specified in the Properties file.

**Action:** Check the properties file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ECSF-10419: cannot provision ID Plugin**

**Cause:** An error occurred while provisioning the ID plugin.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**ECSF-10420: cannot check permission for user {0}**

**Cause:** An error occurred while checking permission.

**Action:** Check the configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**ECSF-10451: cannot set encoding format on HTTP request**

**Cause:** An unexpected error occurred.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ECSF-10452: invalid request parameters**

**Cause:** An error occurred during the doPost operation.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ECSF-10453: cannot authenticate user**

**Cause:** An error occurred during the doPost operation.

**Action:** Check the user.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10454: cannot construct error response**

**Cause:** An error occurred during the doPost operation.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**ECSF-10456: Forcing feedType = Error. Cannot parse ErrorFeed content for {0}**

**Cause:** An unexpected error occurred.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ECSF-10457: Error status received for {0} ControlFeed; lastCrawlDate is not updated in database.**

---

**Cause:** An unexpected error occurred.  
**Action:** Contact the system administrator.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other

**ECSF-10458: Error status received for {0} DataFeed; calling cf.reset().**

**Cause:** An unexpected error occurred.  
**Action:** Contact the system administrator.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other

**ECSF-10459: Error status received for {0} DataFeed; cannot call cf.reset().**

**Cause:** An unexpected error occurred.  
**Action:** Contact the system administrator.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other

**ECSF-10460: cannot invoke search servlet {0} because: {1}. See log for more details.**

**Cause:** An unexpected error occurred.  
**Action:** Contact the system administrator.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other

**ECSF-10461: password for the user {0} cannot be null**

**Cause:** An error occurred during the doPost operation.  
**Action:** Check the user  
**Level:** 1  
**Type:** ERROR  
**Impact:** Data

**ECSF-10464: attachment stream for attachment with ATTACHED\_DOCUMENT\_ID={0} is null**

**Cause:** An error occurred during the FusionAttachmentImpl.read operation.  
**Action:** Contact the system administrator.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Data

**ECSF-10501: cannot authenticate user {0}**

**Cause:** An error occurred while authenticating the user.

---

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10502: the searchContext is null.**

**Cause:** The search context was null.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**ECSF-10503: Username is null or empty.**

**Cause:** There was no username.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**ECSF-10504: cannot authenticate user {0}**

**Cause:** An error occurred while authenticating the user.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**ECSF-10505: Identity Storage Service is not configured: {0}**

**Cause:** A JPS Security configuration error occurred.

**Action:** Configure an Identity Store Service in the application security configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**ECSF-10506: cannot validate user {0}**

**Cause:** An error occurred while validating the user.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**ECSF-10507: cannot find searchable object {0}**

**Cause:** The searchable object was not found.

**Action:** Contact the system administrator.



---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10508: Searchable object {0} is not active.**

**Cause:** The searchable object was not active.

**Action:** Activate the searchable object.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**ECSF-10509: {0} is not an instance of Securable.**

**Cause:** A search plug-in not of type Securable was specified for the searchable object.

**Action:** Use a search plug-in that is of type Securable.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**ECSF-10510: cannot get security keys for {0} on {1}**

**Cause:** A JPS error occurred.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**ECSF-10511: User {0} is invalid.**

**Cause:** An invalid user was specified.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**ECSF-10512: The number of keys {0} exceeds 200.**

**Cause:** The number of security keys specified exceeded the maximum limit of 200.

**Action:** Specify 200 or fewer keys for the search plug-in.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**ECSF-10513: invalid security request**

**Cause:** The security request was null.

**Action:** Pass in a valid security request.

**Level:** 1

---

**Type:** ERROR  
**Impact:** Security  
**ECSF-10514: security service error: {0}**  
**Cause:** A security service error occurred.  
**Action:** Contact the system administrator.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Security  
**ECSF-10515: unsupported SecurityService request**  
**Cause:** The security request entered was invalid.  
**Action:** Enter a valid security request.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Security  
**ECSF-10517: cannot authorize user {0}**  
**Cause:** There was an error authorizing the user.  
**Action:** Contact the system administrator.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Process  
**ECSF-10518: cannot get login context**  
**Cause:** There was an error getting the login context.  
**Action:** Contact the system administrator.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Process  
**ECSF-10519: UserId format {0} is not supported.**  
**Cause:** The UserId format specified was not supported by the search plug-in.  
**Action:** Specify a supported UserId format for the search plug-in.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Security  
**ECSF-10520: UserId format is not specified in the security request. Defaulting to FND format.**  
**Cause:** No UserId format was specified.  
**Action:** Specify a valid UserId format.  
**Level:** 1  
**Type:** ERROR

---

**Impact:** Security

**ECSF-10522: cannot convert username for {0} of format {1}**

**Cause:** Invalid id format

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**ECSF-10601: cannot run query for search category {0}**

**Cause:** An attempt was made to run the query on an invalid search category.

**Action:** Ensure that the search category/categories used in this query is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10602: cannot run query without a query string**

**Cause:** The QueryMetaData object used in this query did not contain a search string.

**Action:** Ensure that the search string is bound to the QueryMetaData before executing the query.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10603: cannot run query without search categories**

**Cause:** The QueryMetaData object used in this query did not contain a search category.

**Action:** Ensure that the search category is bound to the QueryMetaData before executing the query.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10604: cannot delete saved search {0}**

**Cause:** The saved search could not be deleted from the ECSF\_SVSEARCH and ECSF\_SVSEARCH\_DETAILS tables in the database.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10605: cannot save search {0}**

**Cause:** The saved search could not be saved to the ECSF\_SVSEARCH and ECSF\_SVSEARCH\_DETAILS tables in the database.

**Action:** Contact the system administrator.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10606: cannot get DisplayName for runtime object {0}**

**Cause:** The get display name operation failed for this runtime object.

**Action:** Check ECSF component server logs for details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10607: cannot find ECSF\_QUERY\_SERVICE\_REF\_NAME parameter for this ECSF component**

**Cause:** The ECSF\_QUERY\_SERVICE\_REF\_NAME parameter was not set correctly.

**Action:** Contact the database administrator to check that the ECSF\_QUERY\_SERVICE\_REF\_NAME parameter is set correctly for this ECSF component in the ECSF\_PARAMETER table.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10608: cannot execute federation query for {0}**

**Cause:** The query execution failed.

**Action:** For global context, check ECSF component server logs for details. For local context, check the exception message.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10609: cannot get engine instances from the ECSF components**

**Cause:** An error occurred while getting the engine instances from the ECSF components.

**Action:** Check the ECSF component server logs for details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10610: cannot get global saved searches from the ECSF components**

**Cause:** Could not get saved searches from the ECSF components.

**Action:** Check the ECSF component server logs for details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10611: thread error while calling ECSF component**

---

**Cause:** An exception occurred with one of the threads while calling the ECSF components.

**Action:** Check the ECSF component server logs for details.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**ECSF-10612: cannot serialize QueryMetaData to ByteArrayOutputStream**

**Cause:** An I/O error occurred while reading the input stream.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10613: cannot deserialize QueryMetaData**

**Cause:** An I/O error occurred while reading the input stream.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-10614: cannot deserialize QueryMetaData**

**Cause:** The class of a serialized object could not be found.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ECSF-10615: cannot get SavedSearch details**

**Cause:** Could not get SavedSearch details.

**Action:** For global context, check the ECSF component server logs. For local context, check the exception message.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-10616: cannot serialize the SearchException stacktrace.**

**Cause:** The exception stacktrace on this ECSF component could not be written to XML.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** WARNING

**Impact:** Process

---

**ECSF-10617: The application ID for global Search Group {0} is not set in the database.**

**Cause:** The Search Group was missing the application ID.

**Action:** Contact the database administrator.

**Level:** 1

**Type:** WARNING

**Impact:** Process

**ECSF-10618: Action {0} cannot be evaluated for searchable object {1}.**

**Cause:** An exception occurred while evaluating actions for this searchable object.

**Action:** Check the ECSF component server logs for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**ECSF-11404: cannot retrieve the attributes of the searchable object**

**Cause:** The searchable object could not be found or was invalid.

**Action:** Ensure a valid searchable object is deployed to the ECSF server.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ECSF-11405: cannot retrieve the customized fields of the searchable object**

**Cause:** The searchable object could not be found or was invalid.

**Action:** Ensure that a valid searchable object is deployed to the ECSF server.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**EM-00251 to EM-02674**

**EM-00251: No connection to the WebLogic managed server {0}.**

**Cause:** The WebLogic managed server was down.

**Action:** Verify that the managed server is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-00252: Error in accessing proxy MBean for this system component in WebLogic managed server {0}**

**Cause:** Component was down

**Action:** Start the component, or verify that the component has been deployed on the managed server.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-00268: Error in querying ports configuration for system component {0}**

**Cause:** Component was down

**Action:** Start the component.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-00301: Error in fetching data from target application.**

**Cause:** Target application is down.

**Action:** Ensure target application is running.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-00302: Error fetching data from target server in the Oracle WebLogic Server domain.**

**Cause:** The target WebLogic server is down.

**Action:** Make sure the target server is up and running.

---

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-00303: Error in discovering web service endpoints for target application.**

**Cause:** Target application is down.

**Action:** Ensure target application is running.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-00351: Unable to connect to Oracle WSM Policy Manager.**

**Cause:** The Oracle WSM Policy Manager was down or not accessible.

**Action:** Make sure Oracle WSM Policy Manager (wsm-pm application) is up and accessible. Also, ensure you have right roles to access the Service.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-00360: Unable to parse WSDL from {0}**

**Cause:** Either the URL did not refer to a valid address, or the WSDL document did not contain valid Web services definition.

**Action:** Make sure that the given WSDL URL is accessible and ensure the WSDL contains valid WS definition.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-00426: Unable to save changes to registered service**

**Cause:** The service repository is unavailable.

**Action:** Ensure that the service repository is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-00428: Unable to delete registered service**

**Cause:** The service is no longer valid.

**Action:** Ensure that the service is valid and is registered. Make sure the endpoint and WSDL for the service are accessible.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-00430: Unable to register service due to duplicate service name**

**Cause:** The service name is already registered.



---

**Action:** Ensure that the service name is unique.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-00432: Invalid WSIL URL**

**Cause:** The WSIL URL is invalid. The URL is unreachable or doesn't contain a valid WSIL.

**Action:** Ensure that the WSIL URL is valid and available.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-00434: Invalid WSIL File**

**Cause:** The WSIL file is invalid. The file is not a valid WSIL document.

**Action:** Ensure that the uploaded file is a valid WSIL document.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-00440: Service repository operation failed**

**Cause:** Service repository is unavailable.

**Action:** Ensure that the service repository is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-00449: Unexpected error occurred**

**Cause:** Unknown

**Action:** Unknown. Please contact Oracle Support for further guidance.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-00451: Failed to access WSDL**

**Cause:** Invalid WSDL location or WSDL is not accessible

**Action:** Make sure you provide a valid WSDL location. If the location is valid, make sure it is accessible. Also, make sure you have proper privileges to access the WSDL with username and password.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-00452: Failed to parse WSDL file**

**Cause:** Invalid WSDL content

---

**Action:** Ensure that the WSDL is syntactically and semantically correct.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-00453: Failed to invoke operation**

**Cause:** Invalid input arguments

**Action:** Make sure you provide the required input argument values, and that the values are the proper type (for example, integer, string, and so on).

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-00454: Failed to invoke operation**

**Cause:** Unable to read SOAP action for selected operation

**Action:** Make sure right SOAP Action value is set.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-00455: Fail to change view from 'XML View' to 'Tree View'**

**Cause:** Invalid payload contents in XML format

**Action:** Make sure you provide a valid payload to parse and check if any required tag is missing or broken.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-00456: Fail to change view from 'XML View' to 'Tree View'**

**Cause:** Invalid input argument

**Action:** Make sure you provide the required input argument values, and that the values are the proper type (for example, integer, string, and so on).

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-00501: TopLink Sessions were not found**

**Cause:** TopLink MBeans were not found

**Action:** Ensure that the application has been accessed to register the MBeans. Make sure that "-Declipselink.register.dev.mbean=true" and "-Declipselink.register.run.mbean=true" are part of \$JAVA\_OPTIONS

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

---

**EM-00601: Error in getting WSDL for Web service client.**

**Cause:** Target web service application is down.

**Action:** Ensure target web service application is running.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-00602: Error in attaching/detaching policies.**

**Cause:** Target application or Oracle WSM Policy Manager is down.

**Action:** Ensure target application and Oracle WSM Policy Manager is running.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-00603: Error in getting policy subject from target application.**

**Cause:** Target web service application is down.

**Action:** Ensure target Web service application is running.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-01052: Error in querying OPSS application policy MBean object name.**

**Cause:** The WebLogic managed server was down.

**Action:** Verify that the managed server is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-01053: Application stripe entry {0} does not exist in policy store.**

**Cause:** Application stripe ID used to access policies from policy store did not have any data.

**Action:** Check the application stripe ID data provided in configuring Fusion MiddleWare control application deployment wizard security task.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-01055: Error in querying OPSS system policy MBean object name.**

**Cause:** The WebLogic managed server was down.

**Action:** Verify that the managed server is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

---

**EM-01061: Error in querying OPSS credential store MBean object name.**

**Cause:** The WebLogic managed server was down.

**Action:** Verify that the managed server is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-01321: Cannot obtain application information**

**Cause:** The application is not active

**Action:** Make sure that the application is active or running

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-01322: Cannot obtain MDS information for selected application**

**Cause:** MDS is not properly configured for the application

**Action:** Make sure that MDS config mbean is accessible on the mbean server. If it is not, verify that appropriate MDS configuration file (web.xml) contains ADFConfigRuntimeLifeCycleCallBack listener to register MDS config mbean and MDS is configured properly in adf-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-01323: Error while performing MDS runtime (import, export or purge) operation**

**Cause:** MDS runtime mbean is not found on runtime mbean server

**Action:** Make sure that the MDS runtime mbean is accessible on runtime mbean server. If it is not, verify that appropriate MDS configuration file (weblogic-application.xml) contains WLLifecycleListener listener to register MDS runtime mbean.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-01324: Error while retrieving data from page cache**

**Cause:** JavaBean stored in the session has expired or was destroyed

**Action:** Start a fresh session by logging into EM again.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-01325: Cannot obtain MDS target repository information**

**Cause:** MDS target repository is not configured

**Action:** Verify the MDS configuration by checking the contents of the configuration files (for example, adf-config.xml and mds-config.xml).

---

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-01951: Error connecting to soa-infra runtime.**

**Cause:** The soa-infra application is down or not started completely.

**Action:** Verify that the soa-infra application is up and running, and verify that the database where the SOA schemas are installed is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-01952: Error getting composite details.**

**Cause:** The SOA composite application was undeployed or not discovered by Enterprise Manager.

**Action:** Select Refresh Farm from the Farm menu.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-01953: Error getting composite runtime details.**

**Cause:** The SOA composite application was not loaded.

**Action:** View the log files and review any errors reported by the soa-infra application.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02006: Error retrieving Config MBeans for ADFConnectionMBeans {0}.**

**Cause:** The ADF connection and config MBean is not available or accessible.

**Action:** Configuration options currently unavailable. The application might be down, did not start properly, or is incorrectly packaged. Check the log files for further details.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02056: Error getting DAD MBean.**

**Cause:** The DAD MBean is not available or accessible.

**Action:** Configuration options currently unavailable. The application might be down, did not start-up properly, or is incorrectly packaged. Check the log files for further detail.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

---

**EM-02057: Error getting Cache MBean Object Name.**

**Cause:** The Cache MBean is not available or accessible.

**Action:** Configuration options currently unavailable. The application might be down, did not start-up properly, or is incorrectly packaged. Check the log files for further detail.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02058: Error getting Middle Tier MBean Object Name.**

**Cause:** The Middle Tier MBean is not available or accessible.

**Action:** Configuration options currently unavailable. The application might be down, did not start-up properly, or is incorrectly packaged. Check the log files for further detail.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02063: Error getting Portal site URL.**

**Cause:** Wiring MBean Could not connect to the Portal repository.

**Action:** The Portal Database maybe down or the Portal DAD has incorrect username, password or connect string information. Check the log files for further detail.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02201: Error connecting to the WebLogic server.**

**Cause:** The WebLogic server was down.

**Action:** Ensure the target WebLogic server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02202: Error getting the list of folders from the credential store**

**Cause:** There were issues with the JPS credential store MBean.

**Action:** Ensure the JPS credential store MBean is registered and working properly through the System MBean Browser.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02251: Error connecting to Forms Config MBeans**

**Cause:** The managed server that hosts the Forms application was down, or the Forms application was down or not deployed on this server.

---

**Action:** Depending on the specific cause, start the managed server if it is down, start the Forms application if it is down, or deploy the Forms application on this domain if haven't been deployed already.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02451: cannot initialize home page**

**Cause:** The Homepage PageModel bean was not instantiated.

**Action:** [1.] Check the .jspx code for correct reference usage. [2.] Check if the Homepage Page Model bean class is in the emai\_ecsf.jar file. [3.] Check the ADFc configuration file emai-ecsf.xml for correct class association.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02452: cannot initialize home page**

**Cause:** The Homepage Model bean was not instantiated.

**Action:** [1.] Check if the Homepage Model bean class is in the emai\_ecsf.jar file. [2.] Check the ADFc configuration file emai-ecsf.xml for correct class association.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02453: cannot initialize admin page**

**Cause:** The Admin PageModel bean was not instantiated.

**Action:** [1.] Check the .jspx code for correct reference usage. [2.] Check if the Admin Page Model bean class is in the emai\_ecsf.jar file. [3.] Check emai-ecsf.xml configuration file for correct class association.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02454: cannot initialize admin page**

**Cause:** The Admin Model bean was not instantiated.

**Action:** [1.] Check if the Admin Model bean class is in the emai\_ecsf.jar file. [2.] Check emai-ecsf.xml configuration file for correct class association.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02455: cannot create the new engine instance**

**Cause:** The ECSF mbean was not found, the name specified for the search engine instance was not unique, a duplicate record was created, a search engine with the default name already exists, or no search engine instance was selected.

---

**Action:** Check the logging messages on the ECSF runtime server and make the necessary corrections.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02456: cannot create the new search category**

**Cause:** The ECSF mbean was not found, the name specified for the search category was not unique, a duplicate record was created, a search category with the default name already exists, or no search engine instance was selected.

**Action:** Check the logging messages on the ECSF runtime server and make the necessary corrections.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02457: cannot create the new index schedule**

**Cause:** The ECSF mbean was not found, the name specified for the index schedule was not unique, a duplicate record was created, an index schedule with the default name already exists, or no search engine instance was selected.

**Action:** Check the logging messages on ECSF runtime server and make the necessary corrections.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02458: cannot update the record**

**Cause:** The ECSF mbean was not found, the name for the record was not unique, a duplicate record was created, a search engine instance parameter with the same name already exists, or no search engine instance was selected.

**Action:** Check the logging messages on the ECSF runtime server and make the necessary corrections.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02459: cannot delete the search engine instance**

**Cause:** The ECSF mbean was not found, or the search engine instance was not deleted in the DB.

**Action:** Check the logging messages on the ECSF runtime server and make the necessary corrections.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02460: cannot deploy the selected artifact**



---

**Cause:** The ECSF mbean was not found, the artifact was not available on the ECSF runtime server, or the search engine failed to deploy the artifact.

**Action:** Check the logging messages on the ECSF runtime server and make the necessary corrections.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02461: cannot undeploy the selected artifact**

**Cause:** The ECSF mbean was not found, the artifact was not available on the ECSF runtime server, or the search engine failed to undeploy the artifact.

**Action:** Check the logging messages on the ECSF runtime server and make the necessary corrections.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02462: cannot activate the searchable object**

**Cause:** The ECSF mbean was not found or the searchable object was not updated in the DB.

**Action:** Check the logging messages on the ECSF runtime server and make the necessary corrections.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02463: cannot deactivate the searchable object**

**Cause:** The ECSF mbean was not found or the searchable object was not updated in the DB.

**Action:** Check the logging messages on the ECSF runtime server and make the necessary corrections.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02464: cannot start the index operation**

**Cause:** The ECSF mbean was not found or the search engine failed to crawl the data incrementally.

**Action:** Check the logging messages on the ECSF runtime server and make the necessary corrections.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02465: cannot stop the index operation**

---

**Cause:** The ECSF mbean was not found or the search engine failed to stop the crawling.

**Action:** Check the logging messages on the ECSF runtime server and make necessary corrections.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02466: cannot start the full index operation**

**Cause:** The ECSF mbean was not found or the search engine failed to fully crawl the data.

**Action:** Check the logging messages on the ECSF runtime server and make the necessary corrections.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02467: cannot deploy the searchable object**

**Cause:** No search engine instance was selected.

**Action:** Select a search engine instance before you click the deploy button.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02468: cannot deploy the searchable object**

**Cause:** No searchable object was selected.

**Action:** Select a searchable object before you click the deploy button.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02469: cannot deploy the searchable object**

**Cause:** No parameters were defined or parameters were defined incorrectly for the selected search engine instance.

**Action:** Add parameters to the selected search engine instance before you deploy the searchable object.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02470: cannot register the search engine instance**

**Cause:** No parameters were defined or parameters were defined incorrectly for the selected search engine instance.

**Action:** Add parameters to the selected search engine instance before you register it.

---

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02471: cannot import the external search groups**

**Cause:** The ECSF mbean was not found or the search engine failed to import the external search categories.

**Action:** Check the logging messages on the ECSF runtime server and make the necessary corrections.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02472: cannot proceed with the operation**

**Cause:** No record was selected.

**Action:** Select a record.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02473: cannot proceed with the operation**

**Cause:** A value for the Name field of the selected record was not specified.

**Action:** Specify a value for the Name field of the selected record.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02474: cannot register the searchable object**

**Cause:** The ECSF mbean was not found, the name for the record was not unique, or the searchable object is invalid.

**Action:** Check the logging messages on the ECSF runtime server and make the necessary corrections.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02475: cannot initialize unregister searable object page**

**Cause:** The unregister searchable object bean was not instantiated.

**Action:** [1.] Check the .jspx code for correct reference usage. [2.] Check if the Page Model bean class is in the emai\_ecsf.jar file. [3.] Check emai-ecsf.xml configuration file for correct class association.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02476: cannot unregister the searchable object**

---

**Cause:** The ECSF mbean was not found, the name for the record was not unique, or the searchable object is invalid.

**Action:** Check the logging messages on the ECSF runtime server and make the necessary corrections.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02652: error while initializing data for the BI Instance {0}**

**Cause:** The server for Fusion Middleware Control failed to correctly communicate with the server for the BI Instance.

**Action:** Ensure that the server for the BI Instance is running.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02653: error while initializing data for the BI Instance {0}**

**Cause:** The server for Fusion Middleware Control failed to correctly communicate with the server for the BI Instance.

**Action:** Ensure that the server for the BI Instance is running.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02658: The {1} operation can not be performed on the {0} component.**

**Cause:** The specified Oracle Business Intelligence component failed to respond to the operation.

**Action:** See the log files for the Oracle Business Intelligence component to determine the cause of the error.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02668: The configuration for BI Instance can not be locked.**

**Cause:** The BI Instance was already locked by another user.

**Action:** Determine which user has locked the BI Instance and request that it be released.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02669: The changes to the BI Instance can not be committed.**

**Cause:** The BI Instance failed to commit all recent changes.

**Action:** See the log files for the BI Instance to determine the cause of the error.

**Level:** 1

---

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02670: The changes to the BI Instance can not be reverted.**

**Cause:** The BI Instance failed to revert all recent changes.

**Action:** See the log files for the BI Instance to determine the cause of the error.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02672: The BI Instance can not be started.**

**Cause:** The BI Instance could not respond correctly to the start command.

**Action:** See the log files for the BI Instance to determine the cause of the error.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02673: The BI Instance can not be stopped.**

**Cause:** The BI Instance could not respond correctly to the stop command.

**Action:** See the log files for the BI Instance to determine the cause of the error.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager

**EM-02674: The BI Instance can not be restarted.**

**Cause:** The BI Instance could not respond correctly to the restart command.

**Action:** See the log files for the BI Instance to determine the cause of the error.

**Level:** 1

**Type:** ERROR

**Impact:** Enterprise Manager



---

## ENS-00000 to ENS-00213

**ENS-00000: listener thread create (%s)**

**Cause:** An error occurred while creating the listener thread.

**Action:** \*Define: ONS\_LISTENER\_THREAD\_CREATE\_ERROR

**Level:**

**Type:**

**Impact:** Other

**ENS-00001: Connection %s unknown message type: %s**

**Cause:** The connection message type is unknown. This may be a malicious attack on the specified ONS port.

**Action:** \*Define: ONS\_HTTP\_UNKNOWN\_MSGTYPE

**Level:**

**Type:**

**Impact:** Other

**ENS-00002: Connection %s '%s' not found in message%s**

**Cause:** The message does not contain the notification type.

**Action:** \*Define: ONS\_INTERNAL\_EVENTTYPE\_NOTFOUND

**Level:**

**Type:**

**Impact:** Other

**ENS-00003: Connection %s register is missing %s**

**Cause:** The register message is missing subscriber id.

**Action:** \*Define: ONS\_INTERNAL\_REGISTER\_MISSING\_SUBSCRIBERID

**Level:**

**Type:**

**Impact:** Other

**ENS-00004: Connection %s register invalid subscriber ID: %s**

**Cause:** The register message has an invalid subscriber id.

**Action:** \*Define: ONS\_INTERNAL\_REGISTER\_INVALID\_SUBSCRIBERID

**Level:**

---

**Type:**  
**Impact:** Other

**ENS-00005: Connection %s register missing: %s**  
**Cause:** The register message is missing a register id.  
**Action:** \*Define: ONS\_INTERNAL\_REGISTER\_MISSING\_REGISTERID  
**Level:**  
**Type:**  
**Impact:** Other

**ENS-00006: Connection %s register duplicate ID: %s**  
**Cause:** A duplicate ID in the connection register.  
**Action:** \*Define: ONS\_INTERNAL\_REGISTER\_DUPLICATEID  
**Level:**  
**Type:**  
**Impact:** Other

**ENS-00007: Connection %s register bad subscriber ID: %d**  
**Cause:** The register has a bad subscriber ID.  
**Action:** \*Define: ONS\_INTERNAL\_REGISTER\_BAD\_SUBSCRIBER\_ID  
**Level:**  
**Type:**  
**Impact:** Other

**ENS-00008: Connection %s register subscriber ID %d already registered**  
**Cause:** The subscriber ID is already registered.  
**Action:** \*Define: ONS\_INTERNAL\_SUBSCRIBER\_ALREADY\_REGISTERED  
**Level:**  
**Type:**  
**Impact:** Other

**ENS-00009: Connection %s unregister missing: %s**  
**Cause:** The unregister message is missing the register id.  
**Action:** \*Define: ONS\_INTERNAL\_UNREGISTER\_MISSING\_REGISTERID  
**Level:**  
**Type:**  
**Impact:** Other

**ENS-00010: SELECT (%s)**  
**Cause:** The listener thread encountered an error in the select system call while listening for incoming connections.  
**Action:** \*Define: ONS\_LISTENER\_SELECT\_ERROR  
**Level:**  
**Type:**



---

**Impact:** Other

**ENS-00011: %s: ACCEPT (%s)**

**Cause:** The listener thread encountered an error in the accept system call while accepting an incoming connection.

**Action:** \*Define: ONS\_LISTENER\_ACCEPT\_ERROR

**Level:**

**Type:**

**Impact:** Other

**ENS-00012: Could not get address information for %s %s.**

**Cause:** The listener could not obtain address information for the given host or ip and port specification.

**Action:** \*Define: ONS\_LISTENER\_GETINFO\_ERROR

**Level:**

**Type:**

**Impact:** Other

**ENS-00013: Listener thread terminated**

**Cause:** The listener thread has terminated.

**Action:** \*Define: ONS\_LISTENER\_TERMINATED

**Level:**

**Type:**

**Impact:** Other

**ENS-00014: %s: received invalid discovery announcement (%d bytes).**

**Cause:** The listener received an invalid discovery message.

**Action:** \*Define: ONS\_LISTENER\_INVALID\_DISCOVER

**Level:**

**Type:**

**Impact:** Other

**ENS-00015: %s: SOCKET (%s)**

**Cause:** In initializing the network for the listener thread, a socket error was encountered.

**Action:** \*Define: ONS\_LISTENER\_SOCKET\_ERROR

**Level:**

**Type:**

**Impact:** Other

**ENS-00016: %s: SETSOCKOPT %s (%s)**

**Cause:** In initializing the network for the listener thread, a socket option error was encountered.

**Action:** \*Define: ONS\_LISTENER\_SETSOCKOPT\_ERROR

**Level:**

---

**Type:**

**Impact:** Other

**ENS-00017: %s: BIND (%s)**

**Cause:** In initializing the network for the listener thread, an error was encountered in the bind system call.

**Action:** \*Define: ONS\_LISTENER\_BIND\_ERROR

**Level:**

**Type:**

**Impact:** Other

**ENS-00018: %s: LISTEN (%s)**

**Cause:** An error was encountered in the listen system call while initializing the network for the listener thread.

**Action:** \*Define: ONS\_LISTENER\_LISTEN\_ERROR

**Level:**

**Type:**

**Impact:** Other

**ENS-00019: Connection %s Subscribe missing %s**

**Cause:** The subscription message is missing a subscribe id.

**Action:** \*Define: ONS\_SUBSCRIPTION\_SUBSCRIBE\_MISSING\_SUBSCRIBEID

**Level:**

**Type:**

**Impact:** Other

**ENS-00020: Connection %s Subscribe invalid %s%s**

**Cause:** The subscription message has an invalid subscriber id.

**Action:** \*Define: ONS\_SUBSCRIPTION\_SUBSCRIBE\_INVALID\_SUBSCRIBEID

**Level:**

**Type:**

**Impact:** Other

**ENS-00021: Connection %s Duplicate subscriber id %d**

**Cause:** The subscription message has a duplicate subscriber id.

**Action:** \*Define: ONS\_SUBSCRIPTION\_DUPLICATE\_SUBSCRIBEID

**Level:**

**Type:**

**Impact:** Other

**ENS-00022: Connection %s Subscribe missing %s**

**Cause:** The subscription message is missing the subscription string.

**Action:** \*Define: ONS\_SUBSCRIPTION\_SUBSCRIBE\_MISSING\_SUBSCRIPTION

**Level:**

---

**Type:**

**Impact:** Other

**ENS-00023: RMD %s missing name**

**Cause:** The RMD element is missing the name attribute.

**Action:** \*Define: OPMN\_RMD\_MISSING\_NAME

**Level:**

**Type:**

**Impact:** Other

**ENS-00024: Connection %s Subscriber %d subscription error%s**

**Cause:** There was a subscription error.

**Action:** \*Define: ONS\_SUBSCRIPTION\_ERROR

**Level:**

**Type:**

**Impact:** Other

**ENS-00025: Connection %s Unsubscribe missing %s**

**Cause:** A subscriber from this connection's list sent an unsubscribe message. The message is missing a subscriber ID.

**Action:** \*Define: ONS\_SUBSCRIPTION\_UNSUBSCRIBE\_MISSING\_SUBSCRIBEID

**Level:**

**Type:**

**Impact:** Other

**ENS-00026: Connection %s Unsubscribe invalid %s%s**

**Cause:** This connection received an invalid subscriber ID in the unsubscribe message.

**Action:** \*Define: ONS\_SUBSCRIPTION\_UNSUBSCRIBE\_INVALID\_SUBSCRIBEID

**Level:**

**Type:**

**Impact:** Other

**ENS-00027: RMD %s invalid interval**

**Cause:** The RMD interval attribute value is  $\leq 0$ .

**Action:** \*Define: OPMN\_RMD\_INVALID\_INTERVAL

**Level:**

**Type:**

**Impact:** Other

**ENS-00028: Connection %s Subscriber %d not found**

**Cause:** The subscriber with the subscriber ID in the unsubscribe message was not found.

**Action:** \*Define: ONS\_SUBSCRIPTION\_SUBSCRIBER\_NOTFOUND

---

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00029: Connection %s Subscriber %d\t%s**  
**Cause:** An error was encountered in parsing the subscription.  
**Action:** \*Define: ONS\_SUBSCRIPTION\_SUBSCRIBER\_ERR

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00030: %s dlopen failed:%s**  
**Cause:** Failed to open the specified shared library.  
**Action:** \*Define: ONS\_SYSTEM\_DLOPEN\_FAILED

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00031: %s: symbol not found**  
**Cause:** Attempted to get the address of the symbol with the given name. However, could not find the symbol.  
**Action:** \*Define: ONS\_SYSTEM\_DLSYM\_FAILED

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00032: %s LoadLibrary failed: %d**  
**Cause:** Could not load the shared library with the given file name.  
**Action:** \*Define: ONS\_SYSTEM\_LOADLIB\_FAILED

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00033: worker thread create (%s)**  
**Cause:** An error occurred while creating the worker thread.  
**Action:** \*Define: ONS\_WORKER\_THREAD\_CREATE\_ERR

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00034: Read failed from %s (%s) [%d/%d]**  
**Cause:** The server failed to read from the form factor file.  
**Action:** \*Define: ONS\_SERVER\_FORMFACTORFILE\_READ\_ERR

**Level:**

---

**Type:**

**Impact:** Other

**ENS-00035: Worker Thread %d SND error [%d:%d] (%s): connection %s**

**Cause:** The worker thread got an error while sending a block of data to the connection.

**Action:** \*Define: ONS\_WORKER\_SND\_ERROR

**Level:**

**Type:**

**Impact:** Other

**ENS-00036: %s: received invalid announcement addr (%u bytes).**

**Cause:** The listener received a discovery message with an invalid addr string length.

**Action:** \*Define: ONS\_LISTENER\_INVALID\_ANNOUNCE

**Level:**

**Type:**

**Impact:** Other

**ENS-00037: %s: ons\_subscriber\_create() failed: %s**

**Cause:** Creation of a dedicated subscriber failed during initialization of the pm ons broadcast interface.

**Action:** \*Define: ONS\_PM\_DEDICATED\_SUBSCRIBER\_CREATE\_FAILED

**Level:**

**Type:**

**Impact:** Other

**ENS-00038: %s: ons\_publisher\_create() failed**

**Cause:** Creation of a dedicated publisher failed during initialization of the pm ons broadcast interface.

**Action:** \*Define: ONS\_PM\_DEDICATED\_PUBLISHER\_CREATE\_FAILED

**Level:**

**Type:**

**Impact:** Other

**ENS-00039: ons\_init\_pm: responseThread create failed (errno=%d)**

**Cause:** Creation of response processing thread failed during initialization of the pm ons broadcast interface.

**Action:** \*Define: ONS\_PM\_RESP\_PROCESSING\_THR\_CREATE\_FAILED

**Level:**

**Type:**

**Impact:** Other

**ENS-00040: %s: request %u broadcast failed**

**Cause:** In order to get information from remote PMs, a broadcast was attempted, which failed.

---

**Action:** \*Define: ONS\_PM\_REQ\_BROADCAST\_FAILED

**Level:**

**Type:**

**Impact:** Other

**ENS-00041: %s: ons\_notification\_create() failed (register)**

**Cause:** The Register command notification creation failed.

**Action:** \*Define: ONS\_PM\_NOTIFICATION\_CREATE\_FAILED

**Level:**

**Type:**

**Impact:** Other

**ENS-00042: %s: register: unexpected response: %s**

**Cause:** Got an unexpected response to a register notification.

**Action:** \*Define: ONS\_PM\_REGISTER\_UNEXPECTED\_RESP

**Level:**

**Type:**

**Impact:** Other

**ENS-00043: %s: register: bad status: %s (%s)**

**Cause:** Got a bad status in response to a register notification.

**Action:** \*Define: ONS\_PM\_REGISTER\_BAD\_STATUS

**Level:**

**Type:**

**Impact:** Other

**ENS-00044: %s: ons\_notification\_create() failed (broadcast)**

**Cause:** Creation of a broadcast notification failed.

**Action:** \*Define: ONS\_PM\_BROADCAST\_NOTIF\_CR\_FAILED

**Level:**

**Type:**

**Impact:** Other

**ENS-00045: %s: ons\_subscriber\_receive() failed**

**Cause:** The response thread could not receive an incoming notification.

**Action:** \*Define: ONS\_PM\_SUBSCRIBER\_RECV\_FAILED

**Level:**

**Type:**

**Impact:** Other

**ENS-00046: ons\_init\_pm: processBroadcastThread create failed (errno=%d)**

**Cause:** The response thread failed to create a process broadcast thread.

**Action:** \*Define: ONS\_PM\_BROADCAST\_THR\_CR\_FAILED

---

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00047: %s: unknown response type: %s**  
**Cause:** The response thread received an unknown notification type.  
**Action:** \*Define: ONS\_PM\_UNKNOWN\_EVENT\_TYPE

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00048: %s: no response type**  
**Cause:** The response thread received a null notification type.  
**Action:** \*Define: ONS\_PM\_NULLEVENT\_TYPE

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00049: %s: response thread terminated**  
**Cause:** The response thread has terminated.  
**Action:** \*Define: ONS\_PM\_RESP\_THR\_TERMINATED

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00050: %s: no data!**  
**Cause:** The incoming data notification contained no data body.  
**Action:** \*Define: ONS\_PM\_NO\_DATA\_IN\_DATA\_EVENT

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00051: %s: dest = 0x%x, stamp = 0x%x, route = 0x%x**  
**Cause:** The dest, stamp or route field in an incoming data query notification is missing.  
**Action:** \*Define: ONS\_PM\_DATAQUERY\_DATA\_MISSING

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00052: %s: ons\_notification\_create() failed (reply to broadcast)**  
**Cause:** Creation of a reply to a data query notification failed.  
**Action:** \*Define: ONS\_PM\_REPLY\_TO\_BROADCAST\_FAILED

**Level:**

---

**Type:**  
**Impact:** Other

**ENS-00053: %s: missing %s**  
**Cause:** The notification is missing the server down identifier.  
**Action:** \*Define: ONS\_PM\_MISSING\_SERVER\_DOWN\_IDENTIFIER  
**Level:**  
**Type:**  
**Impact:** Other

**ENS-00054: %s: %s not set in broadcast reply**  
**Cause:** ID not found in broadcast reply.  
**Action:** \*Define: ONS\_PM\_ID\_NOTFOUND  
**Level:**  
**Type:**  
**Impact:** Other

**ENS-00055: %s: getServerAddr: address error: %s**  
**Cause:** cannot scan adress from the given data stream  
**Action:** \*Define: ONS\_PM\_ADDRESS\_ERROR  
**Level:**  
**Type:**  
**Impact:** Other

**ENS-00056: Connection thread create %s (%s)**  
**Cause:** The dedicated connection thread could not be created.  
**Action:** \*Define: ONS\_CONN\_THREAD\_CREATE\_ERR  
**Level:**  
**Type:**  
**Impact:** Other

**ENS-00057: Closing active connection %s**  
**Cause:** The active connection is being stopped.  
**Action:** \*Define: ONS\_CONN\_ACTIVE\_CLOSE  
**Level:**  
**Type:**  
**Impact:** Other

**ENS-00058: Passive connection %s missing connect**  
**Cause:** In a passive connection, the first message must be a connect. This may be a malicious attack on the specified ONS port.  
**Action:** \*Define: ONS\_CONN\_MISSING\_CONNECT  
**Level:**  
**Type:**



---

**Impact:** Other

**ENS-00059: Local connection %s missing form factor%**

**Cause:** The local passive connection must contain the current form factor. This message is logged when it does not, which is caused either by an OPMN managed process started as a different user than OPMN, or an attempt is being made to issue an OPMN request as a user other than the one that started OPMN.

**Action:** Check if an OPMN managed process was manually started as a different user than OPMN (and stop it). Check if requests to OPMN are being issued by the wrong user. \*Define: ONS\_CONN\_MISSING\_FORMFACTOR

**Level:**

**Type:**

**Impact:** Other

**ENS-00060: Local connection %s invalid form factor%**

**Cause:** The local connection contains an invalid form factor. This is caused either by an old application left running from an alternate ORACLE\_HOME with the same notification-server local port as the current OPMN, or the local port was changed in opmn.xml without first shutting down OPMN.

**Action:** Check if an OPMN managed process was started from a different ORACLE\_HOME than the current running OPMN (and stop it). Check if the notification-server local port in opmn.xml was changed without shutting OPMN down first (stop this OPMN). \*Define: ONS\_CONN\_INVALID\_FORMFACTOR

**Level:**

**Type:**

**Impact:** Other

**ENS-00061: Request connection %s invalid connect message**

**Cause:** The request port received an invalid connect message. This may be a malicious attack on the OPMN request port.

**Action:** \*Define: ONS\_CONN\_REQPORT\_INVALIDFORMAT

**Level:**

**Type:**

**Impact:** Other

**ENS-00062: Passive connection %s send reply failed**

**Cause:** The server tried to send a reply to a connect and failed.

**Action:** \*Define: ONS\_CONN\_PASSIVECONNECT\_REPLY\_FAILED

**Level:**

**Type:**

**Impact:** Other

**ENS-00063: Server connection %s not on remote port**

**Cause:** The server connection is not on remote port. This may be a malicious attack on the specified ONS port.

**Action:** \*Define: ONS\_CONN\_NOTON\_REMOTEPORT

**Level:**

---

**Type:**

**Impact:** Other

**ENS-00064: Failed to create connection manager thread**

**Cause:** The server failed to create the connection manager thread.

**Action:** \*Define: ONS\_CONN\_MANAGER\_THR\_CREATE\_ERR

**Level:**

**Type:**

**Impact:** Other

**ENS-00065: Passive connection %d %s overrides Active %d %s**

**Cause:** The passive connection overrides the active connection and will be used for communication with the remote server.

**Action:** \*Define: ONS\_CONN\_USE\_PASSIVE\_CONN

**Level:**

**Type:**

**Impact:** Other

**ENS-00066: Passive connection %s yields to Active %s**

**Cause:** The active connection to the remote server will be used. The passive connection will be terminated.

**Action:** \*Define: ONS\_CONN\_USE\_ACTIVE\_CONN

**Level:**

**Type:**

**Impact:** Other

**ENS-00067: Connection %s connect reply failed**

**Cause:** The server attempted to send a success reply for a connection to the remote server and failed.

**Action:** \*Define: ONS\_CONN\_REPLYFAILED

**Level:**

**Type:**

**Impact:** Other

**ENS-00068: Shared connection %s send reply (success) failed**

**Cause:** The server attempted to send a reply to the connect message and failed.

**Action:** \*Define: ONS\_CONN\_SHAREDCONN\_REPLYFAILED1

**Level:**

**Type:**

**Impact:** Other

**ENS-00069: Connection %s status reply for connect failed**

**Cause:** The server attempted to send a reply in response to the connect message and failed.

**Action:** \*Define: ONS\_CONN\_STATUS\_REPLY\_FAILED

---

**Level:**

**Type:**

**Impact:** Other

**ENS-00070: Connection %s header RCV failed (%s) coFlags=%x**

**Cause:** The server tried to read a message from a socket and got a RCV error.

**Action:** \*Define: ONS\_CONN\_HEADER\_RCV\_FAILED

**Level:**

**Type:**

**Impact:** Other

**ENS-00071: RMD %s duplicate entry**

**Cause:** The same name has been specified for more than one RMD in a block.

**Action:** \*Define: OPMN\_RMD\_DUPLICATE\_NAME

**Level:**

**Type:**

**Impact:** Other

**ENS-00072: %s: SNDTO failed (%s)**

**Cause:** The listener encountered an error when sending a discovery message.

**Action:** \*Define: ONS\_LISTENER\_SNDTO\_ERROR

**Level:**

**Type:**

**Impact:** Other

**ENS-00073: %s: RCVFROM failed (%s)**

**Cause:** The listener encountered an error when receiving a discovery message.

**Action:** \*Define: ONS\_LISTENER\_RCVFROM\_ERROR

**Level:**

**Type:**

**Impact:** Other

**ENS-00074: Connection %s SOCKET (%s)**

**Cause:** The socket system call returned an error during creation of an active connection.

**Action:** \*Define: ONS\_CONN\_SOCKET\_ERR

**Level:**

**Type:**

**Impact:** Other

**ENS-00075: Connection %s connect (%s)**

**Cause:** The connect system call returned an error during creation of an active connection.

**Action:** \*Define: ONS\_CONN SOCK\_CONNECT\_ERR

---

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00076: Connection %s SND connect (%s)**  
**Cause:**  
**Action:** \*Define: ONS\_CONN SOCK\_WRITE\_ERR

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00077: Active connection %s missing status**  
**Cause:** The status reply on an active connection is missing.  
**Action:** \*Define: ONS\_CONN\_GETMSGERR

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00078: Connection %s connect status: bad format:%s**  
**Cause:** The status message from an active connection has a badly formatted header.  
**Action:** \*Define: ONS\_CONN\_BADFORMAT\_HEADER

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00079: Connection %s connect status: failed: %s**  
**Cause:** The active connection failed.  
**Action:** \*Define: ONS\_CONN\_FAILED

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00080: Connection %s body RCV failed (%s) coFlags=%x**  
**Cause:** The server tried to read a message from a socket and got a RCV error.  
**Action:** \*Define: ONS\_CONN\_BODY\_RCV\_FAILED

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00081: Connection %s invalid notification header length: %u.**  
**Cause:** A notification been received with a header longer than the maximum allowable size.  
**Action:** \*Define: ONS\_CONN\_HEADER\_MAX

---

**Level:**

**Type:**

**Impact:** Other

**ENS-00082: Connection %s socket data stream is out of sync**

**Cause:** The data stream between the local connection and the remote connection is out of sync.

**Action:** \*Define: ONS\_CONN\_OUT\_OF\_SYNC

**Level:**

**Type:**

**Impact:** Other

**ENS-00083: Connection %s: could not resolve IP for configured host name (%s)**

**Cause:** IP could not be resolved.

**Action:** \*Define: ONS\_CONN\_COULD\_NOT\_RESOLVE\_IP

**Level:**

**Type:**

**Impact:** Other

**ENS-00084: Connection %s invalid notification header:%s**

**Cause:** The connection received an invalid notification header. This may be a malicious attack on the specified ONS port.

**Action:** \*Define: ONS\_CONN\_INVALID\_HEADER

**Level:**

**Type:**

**Impact:** Other

**ENS-00085: Failed to create ons monitor thread**

**Cause:** The server failed to create the ons monitor thread.

**Action:** \*Define: ONS\_SERVER\_PERF\_THR\_CREATE\_ERR

**Level:**

**Type:**

**Impact:** Other

**ENS-00086: Failed to initialize network layer**

**Cause:** The server failed to initialize the network layer.

**Action:** \*Define: ONS\_SERVER\_NETWORK\_INIT\_FAILED

**Level:**

**Type:**

**Impact:** Other

**ENS-00087: Connection %s notification missing origin:%s**

**Cause:** The connection received a notification that is missing the origin field in the header.

**Action:** \*Define: ONS\_CONN\_MISSING\_ORIGIN

---

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00088: Connection %s notification invalid origin:%s**  
**Cause:** The connection received a notification with an invalid origin field in the header.  
**Action:** \*Define: ONS\_CONN\_INVALID\_ORIGIN

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00089: Failed to get host name (%s)**  
**Cause:** The server failed to get a host name.  
**Action:** \*Define: ONS\_SERVER\_GETHOSTNAME\_FAILED

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00090: ONS server initiated**  
**Cause:** The multi-threaded ONS server has been initiated!  
**Action:** \*Define: ONS\_SERVER\_INITIATED

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00091: worker thread creation error (%d)**  
**Cause:** During the process of worker threads' creation, the server encountered a failure. This is a fatal error.  
**Action:** \*Define: ONS\_SERVER\_WORKERTHREAD\_CREATE\_ERROR

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00092: Could not open %s (%s)**  
**Cause:** The server could not open or create the form factor file.  
**Action:** \*Define: ONS\_SERVER\_FORMFACTORFILE\_CREATE\_ERR

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00093: Write failed to %s (%s) [%d/%d]**  
**Cause:** The server failed to write to the form factor file.  
**Action:** \*Define: ONS\_SERVER\_FORMFACTORFILE\_WRITE\_ERR

---

**Level:**

**Type:**

**Impact:** Other

**ENS-00094: topology syntax error: invalid discover syntax: \"%s\"**

**Cause:** unable to parse the discover entry

**Action:** \*Define: ONS\_SERVER\_INVALID\_DISCOVER\_FORMAT

**Level:**

**Type:**

**Impact:** Other

**ENS-00095: Connection %s notification missing stamp:%s**

**Cause:** The connection received a notification that is missing the stamp field in the header.

**Action:** \*Define: ONS\_CONN\_MISSING\_STAMP

**Level:**

**Type:**

**Impact:** Other

**ENS-00096: Connection %s notification invalid stamp:%s**

**Cause:** The connection received a notification with an invalid stamp field in the header.

**Action:** \*Define: ONS\_CONN\_INVALID\_STAMP

**Level:**

**Type:**

**Impact:** Other

**ENS-00097: Connection %s notification missing content-length:%s**

**Cause:** The connection received a notification that is missing the content-length field in the header.

**Action:** \*Define: ONS\_CONN\_MISSING\_CONTENT\_LENGTH

**Level:**

**Type:**

**Impact:** Other

**ENS-00098: topology syntax error: invalid hostname:port syntax \"%s\"**

**Cause:** unable to parse the hostname:port

**Action:** \*Define: ONS\_SERVER\_INVALID\_HOSTNAME\_PORT\_FORMAT

**Level:**

**Type:**

**Impact:** Other

**ENS-00099: XML parse: %s:\tunknown process-set %s.**

**Cause:** An invalid process-set was specified for the dependency in opmn.xml.

**Action:** \*Define: OPMN-NLS\_MSG\_00162

---

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00100: XML parse: %s:\tunknown process-type %s.**  
**Cause:** An invalid process-type was specified for the dependency in opmn.xml.  
**Action:** \*Define: OPMN-NLS\_MSG\_00163

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00101: XML parse: %s:\tunknown component %s.**  
**Cause:** An invalid component was specified for the dependency in opmn.xml.  
**Action:** \*Define: OPMN-NLS\_MSG\_00164

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00102: XML parse: %s\tunknown ias instance %s\tAssuming remote dependency.**  
**Cause:** An unknown ias instance was specified for the dependency in opmn.xml  
-- this dependency will be assumed to be for a managed process-set on a remote OPMN server.  
**Action:** \*Define: OPMN-NLS\_MSG\_00165

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00103: XML parse: circular managed process dependency:%s**  
**Cause:** A managed process dependency has been configured in opmn.xml that eventually leads to a dependency upon itself.  
**Action:** \*Define: OPMN-NLS\_MSG\_00166

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00104: %s: Proc %u:%u could not schedule %s (%s)**  
**Cause:** The specified job could not be scheduled for the process referenced by the given dependency for autostop or autorestart.  
**Action:** \*Define: OPMN-NLS\_MSG\_00167

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00105: XML parser init: character set initialization failed.**



---

**Cause:** The XML parser failed its character set initialization.

**Action:** \*Define: OPMN-NLS\_MSG\_00175

**Level:**

**Type:**

**Impact:** Other

**ENS-00106: Connection %s notification excessive content-length %u**

**Cause:** The connection received a notification with a content-length that exceeds the maximum allowed value.

**Action:** \*Define: ONS\_CONN\_INVALID\_CONTENT\_LENGTH

**Level:**

**Type:**

**Impact:** Other

**ENS-00107: XML parser init: error %d.**

**Cause:** The XML parser encountered the given error during init.

**Action:** \*Define: OPMN-NLS\_MSG\_00177

**Level:**

**Type:**

**Impact:** Other

**ENS-00108: XML parse failed: error %d.**

**Cause:** The XML parser encountered the given error while parsing opmn.xml.

**Action:** \*Define: OPMN-NLS\_MSG\_00179

**Level:**

**Type:**

**Impact:** Other

**ENS-00109: XML: no root element.**

**Cause:** opmn.xml does not have a root element.

**Action:** Verify that \$ORACLE\_HOME/conf/opmn.xml is correct. \*Define: OPMN-NLS\_MSG\_00180

**Level:**

**Type:**

**Impact:** Other

**ENS-00110: XML schema validation failed: error %d.**

**Cause:** The schema validation for opmn.xml failed.

**Action:** Verify that \$ORACLE\_HOME/conf/opmn.xml is correct. \*Define: OPMN-NLS\_MSG\_00181

**Level:**

**Type:**

**Impact:** Other

---

**ENS-00111: XML parser terminate failed: error %d.**

**Cause:** The XML parser encountered the given error while terminating.

**Action:** \*Define: OPMN-NLS\_MSG\_00182

**Level:**

**Type:**

**Impact:** Other

**ENS-00112: XML parse: notification-server is missing.**

**Cause:** The notification-server section is missing from opmn.xml.

**Action:** Verify that \$ORACLE\_HOME/conf/opmn.xml is correct. \*Define: OPMN-NLS\_MSG\_00183

**Level:**

**Type:**

**Impact:** Other

**ENS-00113: XML parse: notification-server ports are missing.**

**Cause:** The notification-server ports element is missing from opmn.xml.

**Action:** Verify that \$ORACLE\_HOME/conf/opmn.xml is correct. \*Define: OPMN-NLS\_MSG\_00184

**Level:**

**Type:**

**Impact:** Other

**ENS-00114: XML parse: notification-server local port is missing.**

**Cause:** The notification-server local port is not configured.

**Action:** At a minimum the local port for the notification server must be configured. \*Define: OPMN-NLS\_MSG\_00185

**Level:**

**Type:**

**Impact:** Other

**ENS-00115: XML parse: process-manager is missing.**

**Cause:** The process-manager section is missing from opmn.xml.

**Action:** Verify that \$ORACLE\_HOME/conf/opmn.xml is correct. \*Define: OPMN-NLS\_MSG\_00186

**Level:**

**Type:**

**Impact:** Other

**ENS-00116: XML parse: no ias instance is configured.**

**Cause:** At least one ias instance must be configured in opmn.xml.

**Action:** Verify that \$ORACLE\_HOME/conf/opmn.xml is correct. \*Define: OPMN-NLS\_MSG\_00187

**Level:**

---

**Type:**

**Impact:** Other

**ENS-00117: XML parse: process module is missing path.**

**Cause:** A process module configured in opmn.xml does not have a specified path.

**Action:** Verify that \$ORACLE\_HOME/conf/opmn.xml is correct. \*Define:  
OPMN-NLS\_MSG\_00188

**Level:**

**Type:**

**Impact:** Other

**ENS-00118: XML parse: module %s unknown status: %s.**

**Cause:** The given module is configured with an invalid status.

**Action:** Verify that \$ORACLE\_HOME/conf/opmn.xml is correct. \*Define:  
OPMN-NLS\_MSG\_00189

**Level:**

**Type:**

**Impact:** Other

**ENS-00119: XML parse: module %s module-id is missing id.**

**Cause:** The given module is configured without an id attribute.

**Action:** Verify that \$ORACLE\_HOME/conf/opmn.xml is correct. \*Define:  
OPMN-NLS\_MSG\_00190

**Level:**

**Type:**

**Impact:** Other

**ENS-00120: XML parse: ias instance is missing config home.**

**Cause:** If multiple ias instances are configured, a config-home value must be specified.

**Action:** Verify that \$ORACLE\_HOME/conf/opmn.xml is correct. \*Define:  
OPMN-NLS\_MSG\_00191

**Level:**

**Type:**

**Impact:** Other

**ENS-00121: XML parse: duplicate ias instance config home (%s).**

**Cause:** Multiple ias instances are configured with the same config-home.

**Action:** Verify that \$ORACLE\_HOME/conf/opmn.xml is correct. \*Define:  
OPMN-NLS\_MSG\_00192

**Level:**

**Type:**

**Impact:** Other

**ENS-00122: XML parse: %s: ias component is missing id.**

**Cause:** The given ias component is missing the id attribute.

---

**Action:** \*Define: OPMN-NLS\_MSG\_00193

**Level:**

**Type:**

**Impact:** Other

**ENS-00123: XML parse: %s: component %s unknown status: %s.**

**Cause:** The given component is configured with an invalid status.

**Action:** \*Define: OPMN-NLS\_MSG\_00194

**Level:**

**Type:**

**Impact:** Other

**ENS-00124: XML parse: %s: duplicate component (%s).**

**Cause:** More than one component with the same id has been configured for the same ias instance.

**Action:** \*Define: OPMN-NLS\_MSG\_00195

**Level:**

**Type:**

**Impact:** Other

**ENS-00125: XML parse: %s: process-type is missing id.**

**Cause:** The given process-type is missing the id attribute.

**Action:** \*Define: OPMN-NLS\_MSG\_00196

**Level:**

**Type:**

**Impact:** Other

**ENS-00126: XML parse: %s: process-type %s unknown status: %s.**

**Cause:** The given process-type is configured with an invalid status.

**Action:** \*Define: OPMN-NLS\_MSG\_00197

**Level:**

**Type:**

**Impact:** Other

**ENS-00127: XML parse: %s: duplicate process-type (%s).**

**Cause:** More than one process-type with the same id has been configured for the same component.

**Action:** \*Define: OPMN-NLS\_MSG\_00198

**Level:**

**Type:**

**Impact:** Other

**ENS-00128: XML parse: %s: process-type %s is missing module-id.**

**Cause:** The given process-type is missing the module-id attribute.

---

**Action:** \*Define: OPMN-NLS\_MSG\_00199

**Level:**

**Type:**

**Impact:** Other

**ENS-00129: XML parse: %s: No module for process-type (%s).**

**Cause:** The module-id specified for the given process-type has no associated module.

**Action:** \*Define: OPMN-NLS\_MSG\_00200

**Level:**

**Type:**

**Impact:** Other

**ENS-00130: XML parse: %s: process-set is missing id.**

**Cause:** The given process-set is missing the id attribute.

**Action:** \*Define: OPMN-NLS\_MSG\_00201

**Level:**

**Type:**

**Impact:** Other

**ENS-00131: XML parse: %s: process-set %s unknown status: %s.**

**Cause:** The given process-set is configured with an invalid status.

**Action:** \*Define: OPMN-NLS\_MSG\_00202

**Level:**

**Type:**

**Impact:** Other

**ENS-00132: XML parse: %s: duplicate process-set (%s).**

**Cause:** More than one process-set with the same id has been configured for the same process-type.

**Action:** \*Define: OPMN-NLS\_MSG\_00203

**Level:**

**Type:**

**Impact:** Other

**ENS-00133: XML parse: %s: Invalid numprocs (%s) for %s.**

**Cause:** A non-numeric invalid value has been specified for numprocs.

**Action:** \*Define: OPMN-NLS\_MSG\_00204

**Level:**

**Type:**

**Impact:** Other

**ENS-00134: XML parse: %s: Invalid minprocs (%s) for %s.**

**Cause:** A non-numeric invalid value has been specified for minprocs.

---

**Action:** \*Define: OPMN-NLS\_MSG\_00205

**Level:**

**Type:**

**Impact:** Other

**ENS-00135: XML parse: %s: Invalid maxprocs (%s) for %s.**

**Cause:** A non-numeric invalid value has been specified for maxprocs.

**Action:** \*Define: OPMN-NLS\_MSG\_00206

**Level:**

**Type:**

**Impact:** Other

**ENS-00136: XML parse: %s: numprocs used with min/maxprocs for %s.**

**Cause:** numprocs may not be specified with minprocs and maxprocs.

**Action:** \*Define: OPMN-NLS\_MSG\_00207

**Level:**

**Type:**

**Impact:** Other

**ENS-00137: XML parse: %s: numprocs or both min/maxprocs must be set for %s.**

**Cause:** numprocs or both minprocs and maxprocs must be configured.

**Action:** \*Define: OPMN-NLS\_MSG\_00208

**Level:**

**Type:**

**Impact:** Other

**ENS-00138: XML parse: %s: maxprocs <= minprocs for %s.**

**Cause:** maxprocs must be greater than minprocs.

**Action:** \*Define: OPMN-NLS\_MSG\_00209

**Level:**

**Type:**

**Impact:** Other

**ENS-00139: XML parse: %s: port is missing id.**

**Cause:** The port element is missing the id attribute.

**Action:** \*Define: OPMN-NLS\_MSG\_00210

**Level:**

**Type:**

**Impact:** Other

**ENS-00140: XML parse: %s: duplicate port id (%s).**

**Cause:** A duplicate port id was specified for the same process-type.

**Action:** \*Define: OPMN-NLS\_MSG\_00211

---

**Level:**

**Type:**

**Impact:** Other

**ENS-00141: XML parse: %s: port %s is missing range.**

**Cause:** The port element is missing the range attribute.

**Action:** \*Define: OPMN-NLS\_MSG\_00212

**Level:**

**Type:**

**Impact:** Other

**ENS-00142: XML parse: %s: invalid port range for %s.**

**Cause:** The port element has an invalid port range.

**Action:** \*Define: OPMN-NLS\_MSG\_00213

**Level:**

**Type:**

**Impact:** Other

**ENS-00143: XML parse: %s: invalid port value for %s.**

**Cause:** The port element has an invalid port value.

**Action:** \*Define: OPMN-NLS\_MSG\_00214

**Level:**

**Type:**

**Impact:** Other

**ENS-00144: XML parse: %s: high port value < low for %s.**

**Cause:** The high port value in a port range must be greater than or equal to the low port value.

**Action:** \*Define: OPMN-NLS\_MSG\_00215

**Level:**

**Type:**

**Impact:** Other

**ENS-00145: XML parse: %s: invalid retry value for %s.**

**Cause:** An invalid retry value was specified.

**Action:** \*Define: OPMN-NLS\_MSG\_00216

**Level:**

**Type:**

**Impact:** Other

**ENS-00146: XML parse: %s: invalid interval value for %s.**

**Cause:** An invalid interval value was specified.

**Action:** \*Define: OPMN-NLS\_MSG\_00217

**Level:**

---

**Type:**  
**Impact:** Other

**ENS-00147: XML parse: %s: invalid timeout value for %s.**  
**Cause:** An invalid timeout value was specified.  
**Action:** \*Define: OPMN-NLS\_MSG\_00218

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00148: Connection %s: notification missing generating node%s**  
**Cause:** The connection received a notification missing the generating node field in the header.  
**Action:** \*Define: ONS\_CONN\_MISSING\_GNODE

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00149: XML parse: %s: DB dependency is missing db-connect-info.**  
**Cause:** A database dependency configuration is missing the db-connect-info attribute.  
**Action:** \*Define: OPMN-NLS\_MSG\_00220

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00150: XML parse: %s: OID dependency is missing address.**  
**Cause:** An OID dependency configuration is missing the address attribute.  
**Action:** \*Define: OPMN-NLS\_MSG\_00221

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00151: XML parse: %s: OSSO dependency is missing host.**  
**Cause:** An OSSO dependency configuration is missing the host attribute.  
**Action:** \*Define: OPMN-NLS\_MSG\_00222

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00152: XML parse: %s: OSSO dependency is missing port.**  
**Cause:** An OSSO dependency configuration is missing the port attribute.  
**Action:** \*Define: OPMN-NLS\_MSG\_00223

**Level:**



---

**Type:**

**Impact:** Other

**ENS-00153: XML parse: %s: OSSO dependency is missing URI.**

**Cause:** An OSSO dependency configuration is missing the URI attribute.

**Action:** \*Define: OPMN-NLS\_MSG\_00224

**Level:**

**Type:**

**Impact:** Other

**ENS-00154: XML parse: %s: Managed process dependency is missing component.**

**Cause:** A managed process dependency configuration is missing the component attribute.

**Action:** \*Define: OPMN-NLS\_MSG\_00225

**Level:**

**Type:**

**Impact:** Other

**ENS-00155: XML parse: %s: Managed process dependency is missing process-type.**

**Cause:** A managed process dependency configuration is missing the process-type attribute.

**Action:** \*Define: OPMN-NLS\_MSG\_00226

**Level:**

**Type:**

**Impact:** Other

**ENS-00156: XML parse: %s: Managed process dependency is missing process-set.**

**Cause:** A managed process dependency configuration is missing the process-set attribute.

**Action:** \*Define: OPMN-NLS\_MSG\_00227

**Level:**

**Type:**

**Impact:** Other

**ENS-00157: XML parse: %s: data category is missing id.**

**Cause:** The data-category id attribute is missing.

**Action:** \*Define: OPMN-NLS\_MSG\_00228

**Level:**

**Type:**

**Impact:** Other

**ENS-00158: XML parse: %s: environment is missing id.**

**Cause:** The environment id attribute is missing.

**Action:** \*Define: OPMN-NLS\_MSG\_00229

**Level:**

---

**Type:**

**Impact:** Other

**ENS-00159: XML parse: %s: environment %s is missing value.**

**Cause:** The given environment configuration is missing the value attribute.

**Action:** \*Define: OPMN-NLS\_MSG\_00230

**Level:**

**Type:**

**Impact:** Other

**ENS-00160: XML parse: %s: missing log-file.**

**Cause:** The log-file element is missing.

**Action:** \*Define: OPMN-NLS\_MSG\_00231

**Level:**

**Type:**

**Impact:** Other

**ENS-00161: XML parse: %s: duplicate launch-target id.**

**Cause:** A duplicate launch id was configured in opmn.xml.

**Action:** \*Define: OPMN\_XML\_PARSE\_DUP\_LAUNCH\_TARGET

**Level:**

**Type:**

**Impact:** Other

**ENS-00162: XML parse: %s: missing or invalid comp attribute -- %s**

**Cause:** The log or debug element is missing the comp attribute, or the specified string is invalid.

**Action:** \*Define: OPMN-NLS\_MSG\_00233

**Level:**

**Type:**

**Impact:** Other

**ENS-00163: XML parse: %s: minimum log rotation-size is %d.**

**Cause:** rotation-size is configured below the minimum value -- the minimum value will be used.

**Action:** \*Define: OPMN-NLS\_MSG\_00234

**Level:**

**Type:**

**Impact:** Other

**ENS-00164: Connection %s notification missing cluster id%s**

**Cause:** The connection received a notification missing the cluster id field in the header.

**Action:** \*Define: ONS\_CONN\_MISSING\_CLUSTER\_ID

**Level:**

---

**Type:**

**Impact:** Other

**ENS-00165: Connection %s notification missing cluster name%s**

**Cause:** The connection received a notification missing the cluster name field in the header.

**Action:** \*Define: ONS\_CONN\_MISSING\_CLUSTER\_NAME

**Level:**

**Type:**

**Impact:** Other

**ENS-00166: Connection %s notification missing instance id%s**

**Cause:** The connection received a notification missing the instance id field in the header.

**Action:** \*Define: ONS\_CONN\_MISSING\_INSTANCE\_ID

**Level:**

**Type:**

**Impact:** Other

**ENS-00167: XML parse: %s: circular environment variable definition for %s.**

**Cause:** The environment variable references another environment variable that eventually leads to a reference to this environment variable.

**Action:** \*Define: OPMN-NLS\_MSG\_00238

**Level:**

**Type:**

**Impact:** Other

**ENS-00168: XML parse: ONS topology %s missing list attribute**

**Cause:** The given topology element is missing the list attribute.

**Action:** \*Define: OPMN\_ONS\_TOPO\_MISSING\_LIST

**Level:**

**Type:**

**Impact:** Other

**ENS-00169: XML parse: unknown ONS topology element: %s**

**Cause:** The given ONS topology element is unknown.

**Action:** \*Define: OPMN\_ONS\_TOPO\_UNKNOWN

**Level:**

**Type:**

**Impact:** Other

**ENS-00170: XML parse: missing instance id attribute**

**Cause:** The the ias-instance id was not configured.

**Action:** \*Define: OPMN\_INST\_NO\_ID

**Level:**

---

**Type:**

**Impact:** Other

**ENS-00171: XML parse: missing instance name attribute -- using instance id**

**Cause:** The the ias-instance name attributwe was not configured -- using the id attribute value.

**Action:** \*Define: OPMN\_INST\_NO\_NAME

**Level:**

**Type:**

**Impact:** Other

**ENS-00172: Failed to retrieve the path of the windows directory: %d**

**Cause:** Windows system error: GetWindowsDirectory() call failed.

**Action:** \*Define: OPMN-NLS\_MSG\_00243

**Level:**

**Type:**

**Impact:** Other

**ENS-00173: Failed to retrieve the path of the system directory: %d**

**Cause:** Windows system error: GetSystemDirectory() call failed.

**Action:** \*Define: OPMN-NLS\_MSG\_00244

**Level:**

**Type:**

**Impact:** Other

**ENS-00174: XML parse: %s: %s dependency is missing wallet-file while ssl is enabled**

**Cause:** The wallet-file attribute is missing from ssl configuration for dependency check

**Action:** \*Define: OPMN-NLS\_MSG\_00257

**Level:**

**Type:**

**Impact:** Other

**ENS-00175: topology syntax error: invalid gateway syntax: \"%s\"**

**Cause:** unable to parse the gateway entry

**Action:** \*Define: ONS\_SERVER\_INVALID\_GATEWAY\_FORMAT

**Level:**

**Type:**

**Impact:** Other

**ENS-00176: XML parse: %s: number of procs can not be specified for %s.**

**Cause:** The module for the given process-set dynamically sets the value for numprocs, and so numprocs, minprocs and maxprocs must not be configured.

**Action:** \*Define: OPMN-NLS\_PARSE\_AUTONUMPROCS

---

**Level:**

**Type:**

**Impact:** Other

**ENS-00177: Connection %s notification missing instance name%s**

**Cause:** The connection received a notification missing the instance name field in the header.

**Action:** \*Define: ONS\_CONN\_MISSING\_INSTANCE\_NAME

**Level:**

**Type:**

**Impact:** Other

**ENS-00178: %s: missing request field**

**Cause:** The request field in an incoming data query notification is missing.

**Action:** \*Define: ONS\_PM\_DATAQUERY\_REQ\_MISSING

**Level:**

**Type:**

**Impact:** Other

**ENS-00179: Can not resolve %s for interface %s**

**Cause:** The given host or ip could not be resolved within the specified ip interface.

**Action:** \*Define: ONS\_UNRESOLVED\_INTERFACE

**Level:**

**Type:**

**Impact:** Other

**ENS-00180: getaddrinfo(%s, %s, %d) failed (%s): %s**

**Cause:** The given hostInternal, port and type could not be resolved.

**Action:** \*Define: ONS\_UNRESOLVED\_ADDRINFO

**Level:**

**Type:**

**Impact:** Other

**ENS-00181: XML parse: %s: unsupported ip interface**

**Cause:** The specified IP interface is not supported on this system.

**Action:** \*Define: OPMN\_XML\_PARSE\_UNSUPPORTED\_INTERFACE

**Level:**

**Type:**

**Impact:** Other

**ENS-00182: XML parse: %s: unknown ip interface**

**Cause:** The specified IP interface is unknown.

**Action:** \*Define: OPMN\_XML\_PARSE\_UNKNOWN\_INTERFACE

**Level:**

---

**Type:**

**Impact:** Other

**ENS-00183: Unresolved discovery multicast address and port: %s, %s**

**Cause:** The given hostInternal, and port for multicast discovery cannot be resolved.

**Action:** \*Define: ONS\_UNRESOLVED\_DISCOVER\_INFO

**Level:**

**Type:**

**Impact:** Other

**ENS-00184: Unable to resolve address for host: %s. %s**

**Cause:** The call to gethostbyname for the hostname failed

**Action:** \*Define: ONS\_SERVER\_GETHOSTBYNAME\_FAILED

**Level:**

**Type:**

**Impact:** Other

**ENS-00185: Invalid protocol to host: %s.**

**Cause:** Invalid protocol returned for the host

**Action:** \*Define: ONS\_CONN\_INVALID\_PROTOCOL\_TYPE

**Level:**

**Type:**

**Impact:** Other

**ENS-00186: XML parse: %s libraries are configured with %s SSL layer.**

**Cause:** The SSL layer configured does not match the loadbale library configuration.

**Action:** \*Define: OPMN-NLS\_XML\_SSL\_LIBRARY\_MISMATCH

**Level:**

**Type:**

**Impact:** Other

**ENS-00187: Connection %s: invalid ONS version (%d).**

**Cause:** An OPMN server or client program using a deprecated version of the ONS protocol attempted to connect with this OPMN server

**Action:** \*Define: ONS\_CONN\_INVALID\_ONS\_VERSION

**Level:**

**Type:**

**Impact:** Other

**ENS-00188: Connection %s: invalid ONS v3 connect header\t%s: %s.**

**Cause:** An OPMN server attempted to connect with this OPMN server using an invalid header

**Action:** \*Define: ONS\_CONN\_INVALID\_HEADER\_V3

---

**Level:**

**Type:**

**Impact:** Other

**ENS-00189: XML parse: %s: service fail-over process type may only have one process-set (%s).**

**Cause:** A process set configured with service-failover=true can have only one process-set, but this process-type is configured with two.

**Action:** \*Define: OPMN\_PARSE\_SERVICE\_SINGLE\_PSET

**Level:**

**Type:**

**Impact:** Other

**ENS-00190: XML parse: %s: service-weight must be >= 1.**

**Cause:** The service-weight attribute was configured with a value < 1.

**Action:** \*Define: OPMN\_PARSE\_SERVICE\_INVALID\_WEIGHT

**Level:**

**Type:**

**Impact:** Other

**ENS-00191: XML parse: %s: service-weight may only be specified when service-failover=true.**

**Cause:** The service-weight attribute may only be specified when service-failover=true.

**Action:** \*Define: OPMN\_PARSE\_SERVICE\_IMPROPER\_WEIGHT

**Level:**

**Type:**

**Impact:** Other

**ENS-00192: XML parse: %s: %s may not be specified when service-failover=true.**

**Cause:** The numprocs attribute may not be specified for service failover types.

**Action:** \*Define: OPMN\_PARSE\_SERVICE\_EXCLUSION

**Level:**

**Type:**

**Impact:** Other

**ENS-00193: Failed to create connection status thread.**

**Cause:** The server failed to create the connection status thread.

**Action:** \*Define: ONS\_CONN\_STATUS\_THR\_CREATE\_ERR

**Level:**

**Type:**

**Impact:** Other

**ENS-00194: Failed to initialize remote pm interface.**

**Cause:** Internal error while initializing module interface.

---

**Action:** \*Define: OPMN\_ONS\_PM\_INIT\_FAILED

**Level:**

**Type:**

**Impact:** Other

**ENS-00195: Connection %s missing join.**

**Cause:** Server connections must exchange join messages when they connect, but the remote server did not send one when expected.

**Action:** \*Define: ONS\_CONN\_MISSING\_JOIN

**Level:**

**Type:**

**Impact:** Other

**ENS-00196: Connection %s: join message missing field %s.**

**Cause:** The join message from the remote server was missing the expected field.

**Action:** \*Define: ONS\_CONN\_JOIN\_INCOMPLETE

**Level:**

**Type:**

**Impact:** Other

**ENS-00197: Connection %s: io timeout (%u).**

**Cause:** IO for the connection timed out.

**Action:** \*Define: ONS\_CONN\_TIMEOUT

**Level:**

**Type:**

**Impact:** Other

**ENS-00198: RMD %s conditional missing value attribute**

**Cause:** The conditional is missing the value attribute.

**Action:** \*Define: OPMN\_RMD\_COND\_NOVALUE

**Level:**

**Type:**

**Impact:** Other

**ENS-00199: RMD %s action missing value attribute**

**Cause:** The action is missing the value attribute.

**Action:** \*Define: OPMN\_RMD\_ACTION\_NOVALUE

**Level:**

**Type:**

**Impact:** Other

**ENS-00200: RMD %s exception missing value attribute**

**Cause:** The exception is missing the value attribute.

**Action:** \*Define: OPMN\_RMD\_EXCEPTION\_NOVALUE



---

**Level:**

**Type:**

**Impact:** Other

**ENS-00201: RMD %s unknown element**

**Cause:** The RMD has an unknown element type declared.

**Action:** \*Define: OPMN\_RMD\_UNKNOWN\_ELT

**Level:**

**Type:**

**Impact:** Other

**ENS-00202: RMD %s duplicate conditional**

**Cause:** The RMD has more than one conditional defined.

**Action:** \*Define: OPMN\_RMD\_COND\_DUP

**Level:**

**Type:**

**Impact:** Other

**ENS-00203: RMD %s missing conditional**

**Cause:** The RMD is missing the conditional element.

**Action:** \*Define: OPMN\_RMD\_NO\_COND

**Level:**

**Type:**

**Impact:** Other

**ENS-00204: RMD %s missing action**

**Cause:** The RMD is missing an action element.

**Action:** \*Define: OPMN\_RMD\_NO\_ACTION

**Level:**

**Type:**

**Impact:** Other

**ENS-00205: RMD %s action or exception referenced element outside of conditional scope**

**Cause:** An action or exception for the RMD referenced an element outside the scope of the conditional.

**Action:** \*Define: OPMN\_RMD\_BAD\_LEVEL

**Level:**

**Type:**

**Impact:** Other

**ENS-00206: RMD %s conditional parse error: %s**

**Cause:** The conditional syntax is invalid.

**Action:** \*Define: OPMN\_RMD\_COND\_PARSE

---

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00207: RMD %s invalid conditional %s operand**  
**Cause:** A conditional operand is invalid.  
**Action:** \*Define: OPMN\_RMD\_COND\_INVALID\_OPERAND

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00208: RMD %s invalid action or exception timeout: %s**  
**Cause:** An action or exception has a timeout value <= 0.  
**Action:** \*Define: OPMN\_RMD\_ACTION\_INVALID\_TIMEOUT

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00209: RMD %s invalid action or exception syntax: %s**  
**Cause:** An action or exception has an invalid value string.  
**Action:** \*Define: OPMN\_RMD\_ACTION\_INVALID\_SYNTAX

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00210: RMD %s unknown action or exception type: %s**  
**Cause:** An action or exception has an invalid value string.  
**Action:** \*Define: OPMN\_RMD\_ACTION\_UNKNOWN

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00211: RMD %s invalid action or exception argument count: %s**  
**Cause:** An action or exception has an invalid number of arguments.  
**Action:** \*Define: OPMN\_RMD\_ACTION\_INVALID\_ARGCOUNT

**Level:**  
**Type:**  
**Impact:** Other

**ENS-00212: XML parse: %s: process-type %s status: %s, ias-component status is phantom.**  
**Cause:** The process-type status must be "phantom" if the ias-component status is "phantom".  
**Action:** \*Define: OPMN\_NLS\_PTYPE\_NOT\_PHANTOM

---

**Level:**

**Type:**

**Impact:** Other

**ENS-00213: XML parse: %s: process-set %s status: %s, process-type status is phantom.**

**Cause:** The process-set status must be "phantom" if the process-type status is "phantom".

**Action:** \*Define: OPMN-NLS\_PSET\_NOT\_PHANTOM

**Level:**

**Type:**

**Impact:** Other



---

## EPMBPMUI-00101 to EPMBPMUI-01804

**EPMBPMUI-00101: Initializing configuration factory**

**Cause:** The application is initializing its configuration factory at application startup.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-00102: Terminating configuration factory**

**Cause:** The application is shutting down its configuration factory at application shutdown.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-00201: Parameter "{0}" has value "{1}"**

**Cause:** Reports the value of a configuration factory parameter during startup.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-00204: Failed to initialize the class {0} with its default constructor.**

**Cause:** The configuration factory could not create a configuration class.

**Action:** Consult the application configuration log for further details.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-00205: Failed to instantiate the class {0}**

**Cause:** The configuration factory could not create a configuration class.

**Action:** Consult the application configuration log for further details.

---

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-00206: Failed to initialize the configuration class.**

**Cause:** The configuration factory could create, but could not initialize, a configuration class.

**Action:** Consult the application configuration log for further details.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-00207: Failed to resolve the class {0}**

**Cause:** The configuration factory could not find a named class definition to create.

**Action:** Consult the application configuration log for further details.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-00208: Failed to initialize the configuration class.**

**Cause:** The configuration factory could create, but could not initialize, a configuration class.

**Action:** Consult the application configuration log for further details.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-00209: Configuration class application parameter "{0}" was not specified in web.xml**

**Cause:** A required parameter for the configuration factory was not specified in the application configuration.

**Action:** Verify that the named parameter is present in the file web.xml, and that any customizations of this file did not remove it.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-00210: The configuration Factory's configuration instance was null. There was an initialization error during application startup.**

**Cause:** Due to previous errors, the configuration factory was not able to create a configuration instance.

**Action:** Consult the application configuration logs for previous errors.

**Level:** 32

**Type:** ERROR

**Impact:**

---

**EPMBPMUI-00211: There was an error during configuration instance termination.**

**Cause:** The configuration factory was unable to terminate a configuration instance.

**Action:** This error is not immediately fatal, but may result in a memory leak over time if repeated.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-00212: The Configuration instance was not initialized. Ensure the context parameter "{0}" is set correctly, and check for errors during application startup.**

**Cause:** The configuration factory could not initialize its configuration instance due to a missing parameter in web.xml.

**Action:** Verify that the named parameter is present in the file web.xml, and that any customizations of this file did not remove it.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-00402: There was an error getting the context configuration parameter: {0}.**

**Cause:** The application was unable to load the path to its context configuration from the configuration parameter BpmContextConfig.

**Action:** Verify that application configuration completed successfully, and that any customizations to this application did not remove this parameter.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-00403: There was an error getting the common install version number.**

**Cause:** The application was unable to determine the version number of the common installer.

**Action:** Verify that the file EPM\_ORACLE\_HOME/common/config/11.1.2.0/installer\_version.xml exists, is accessible, and is a valid XML file.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-00501: Failed to load and parse {0}**

**Cause:** The configuration class failed to load the named file.

**Action:** Consult the application configuration log for further errors.

**Level:** 32

**Type:** ERROR

**Impact:**

---

**EPMBPMUI-00502: Failed to initialize the authentication helper**

**Cause:** The configuration class could not initialize the security system due to previous errors.

**Action:** Consult the application security log for previous errors.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-00503: The property "{0}" has value "{1}"**

**Cause:** Reports the named property and value.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-00601: Loaded properties from {0}**

**Cause:** Reports that the configuration class loaded its application properties from the named EPM Registry component.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-00602: Failed to load properties from {0}**

**Cause:** The configuration class could not load its configuration properties from the named EPM Registry component.

**Action:** Verify connection to the EPM Registry and EPM Registry contents.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-00603: Loaded properties from {0} [{1}={2}]**

**Cause:** Reports that the configuration class loaded its application properties from the named EPM Registry component.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-00701: There was an error during authentication.**

**Cause:** Reports a generic error during authentication. This message is a generic message for the user interface which obscured the actual security system error.

**Action:** Consult the application security log for the full error details.

**Level:** 32



---

**Type:** ERROR

**Impact:**

**EPMBPMUI-00702: Intercepting request for authentication: {0}**

**Cause:** The security system is intercepting the named request for an authentication check.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-00703: Intercepting with static logon page: {0}**

**Cause:** The security system is using the named logon page to prompt for user credentials.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-00801: Redirecting request for authentication: {0}**

**Cause:** The security system is redirecting the named request to the main application logon page.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-00901: Logon bean class name was not specified in web.xml.**

**Cause:** The name of a security class implementation was not found in the application configuration.

**Action:** This is not a fatal error; a default implementation will be used.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-00902: Using the default logon bean implementation.**

**Cause:** The security system will use a default security class implementation.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-00903: There was an error instantiating the logon bean.**

**Cause:** The security system was unable to instantiate the security class implementation.

---

**Action:** Consult the application security log for previous errors from the security API

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-00904: The Logon bean class does not have a default public constructor.**

**Cause:** The security class implementation does not have a required constructor.

**Action:** Verify that the application deployment is not damaged and that all service fixes were applied properly.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-00905: Logon bean Java class is not resolvable.**

**Cause:** The security system could not resolve the class name of the security class implementation.

**Action:** Verify that any customizations to web.xml did not remove or damage this parameter.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-00906: Failed to initialize the logon bean.**

**Cause:** The security system could not initialize the security class implementation.

**Action:** Consult the application security log for prior errors from the security API.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-00907: There was an error during logon bean initialization.**

**Cause:** The security system could not initialize the security class implementation.

**Action:** Consult the application security log for prior errors from the security API.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-01001: Blocking request: {0}**

**Cause:** The named request has been blocked by the security system.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-01201: The CSS mode is: {0}**

---

**Cause:** Reports the deployment mode of the security system.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-01202: Failed to determine CSS mode. Will use EPM mode.**

**Cause:** Indicates that the security system could not determine its deployment mode and is using the default mode.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-01203: Initializing security framework**

**Cause:** Indicates that the security class is initializing the security API/

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-01204: Security framework was initialized successfully.**

**Cause:** Indicates that the security class initialized the security API without error.

**Action:** No action was required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-01205: There was an error initializing security framework.**

**Cause:** Indicates that the security class failed to initialize the security API.

**Action:** Consult the application security logs for prior error messages.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-01207: This session will be invalidated.**

**Cause:** Indicates that an already-extant session is being invalidated during logon to be replaced with a new session.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-01208: Logging on user {0} at {1}**

---

**Cause:** Records a successful user logon for the named user at the given time.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-01210: There was an error determining if direct logon is permitted.  
Direct logons will be denied.**

**Cause:** The security system was unable to determine if direct logons are permitted even if an SSO agent is enabled. Such logons will be disallowed.

**Action:** Verify that the application was deployed correctly and that any customization to its configuration did not remove any parameters.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-01211: User's password is about to expire.**

**Cause:** Informative message at logon indicating the the current user's password will soon expire.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-01212: Failed to store user in session**

**Cause:** The security system failed to create a session for an authenticated user.

**Action:** Consult the application security log for further details.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-01213: Failed to retrieve user from session**

**Cause:** The security system could not verify a user from an existing session.

**Action:** Consult the application security log for further details.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-01214: Terminating session for user: {0}**

**Cause:** Indicates that a user session is terminated.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

---

**EPMBPMUI-01216: Session created at: {0}**

**Cause:** Gives the creation time of a terminated user session.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-01217: There was an error during Fusion logon:**

**Cause:** Reports an error from the Fusion Middleware logon system.

**Action:** Consult the application security log for further details.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-01301: Attempt to create a J2EE session on an unauthorized request path. The attempt was blocked. The request path was: {0}**

**Cause:** An unauthorized request attempted to create an application session and was blocked in the attempt.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-01501: read parameter name: {0} value: {1}**

**Cause:** Indicates a preferences system configuration value read during startup.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-01502: There was an error during preferences system initialization.**

**Cause:** Reports an error during preferences initialization.

**Action:** Consult the application preferences log for further details.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-01503: Preferences servlet initialized**

**Cause:** Indicates that the preferences servlet is initialized.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

---

**EPMBPMUI-01504: There was an error saving preferences.**

**Cause:** Indicates an error saving preferences for a given user.

**Action:** Consult both the application security and applicaion preferences logs for more details.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-01505: There was an error saving preferences for multiple users.**

**Cause:** Indicates an error saving preferences for multiple users.

**Action:** Consult both the application security and applicaion preferences logs for more details.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-01506: Ther was an error during preferences system shutdown.**

**Cause:** Reports an error during preference system shutdown during application shutdown.

**Action:** The application has shut down, so no action is possible.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-01801: There was an error checking the client debug setting: all requests blocked.**

**Cause:** The security system was unable to determine if client debugging requests are permitted; these requests will be blocked by default.

**Action:** Verify that application configuration completed successfully, and that any customizations to this application did not remove this parameter.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-01802: Permitting request: {0}**

**Cause:** The security system is permitting the named client debugging request.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMBPMUI-01803: Blocking request: {0}**

**Cause:** The security system is blocking the named client debugging request.

**Action:** No action is required.

**Level:** 32

---

**Type:** ERROR

**Impact:**

**EPMBPMUI-01804: You do not have access to see this page because client debugging is disabled. Contact your system administrator.**

**Cause:** This message indicates that the request was blocked because client debugging is enabled. A system administrator must enable this setting for the application.

**Action:** Contact your system administrator.

**Level:** 32

**Type:** ERROR

**Impact:**





---

## EPMFR-00001 to EPMFR-00343

**EPMFR-00001: Duplicate arc exists in the linkbase. From: ({0}) to: ({1})**

**Cause:** Duplicate arc nodes were provided for a linkbase.

**Action:** Ensure that the taxonomy does not use duplicate arc nodes.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00002: Error while trying to get content at URL: ({0}). Trying path: ({1}) instead.**

**Cause:** The taxonomy's relative path was used instead of the URL location.

**Action:** Ensure that the taxonomy's URL location is properly formed.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00003: URL: ({0}) missing**

**Cause:** The URL for the taxonomy was not found.

**Action:** Ensure that the taxonomy exists at the given location. Also ensure that the given taxonomy's URL is properly formed.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00004: {0} <element> attribute: {1} will not be processed. It is not recognized by the parser.**

**Cause:** An unrecognized taxonomy element attribute was found by the taxonomy parser. It will be ignored.

**Action:** Ensure that the taxonomy being parsed does not use unrecognized element attributes.

**Level:** 32

**Type:** ERROR

**Impact:**

---

**EPMFR-00005: {0} <schema> attribute: {1} will not be processed. It is not recognized by the parser.**

**Cause:** An unrecognized schema attribute was found by the taxonomy parser. It will be ignored.

**Action:** Ensure that the taxonomy being parsed does not use unrecognized schema attributes.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00006: Linkbase:{0} <linkbaseRef> attribute: {1} will not be processed. It is not recognized by the parser.**

**Cause:** An unrecognized linkbase attribute was found by the taxonomy parser. It will be ignored.

**Action:** Ensure that the taxonomy being parsed does not use unrecognized linkbase attributes.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00007: processImportAttributes:{0} <import> attribute: {1} will not be processed. It is not recognized by the parser.**

**Cause:** An unrecognized import attribute was found by the taxonomy parser. It will be ignored.

**Action:** Ensure that the taxonomy being parsed does not use unrecognized import attributes.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00008: {0} <include> attribute: {1} will not be processed. It is not recognized by the parser.**

**Cause:** An unrecognized include attribute was found by the taxonomy parser. It will be ignored.

**Action:** Ensure that the taxonomy being parsed does not use unrecognized include attributes.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00009: Error writing binary data to file: ({0})**

**Cause:** Write permissions to file may be denied due to user permission settings or disk space limitations.

**Action:** Ensure that the user has write permissions to the file and there is enough disk space.

**Level:** 32

---

**Type:** ERROR

**Impact:**

**EPMFR-00010: Error reading binary data from file: ({0})**

**Cause:** File is missing or not accessible at this time.

**Action:** Verify that the file exists and is available, or try later.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00011: Cannot load bursting file: {0}. Internal unique identifier of this file is: [{1}].**

**Cause:** The file that was accessed does not exist.

**Action:** Select a file that exists and rerun.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00012: Cannot load bursting file: {0}. Internal unique identifier of this file is: [{1}].**

**Cause:** The file that was accessed does not exist.

**Action:** Select a file that exists and rerun.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00013: GIF no longer supported**

**Cause:** An unsupported Graphic Interchange Format (GIF) file was encountered as a report image.

**Action:** Convert the GIF file to a Bitmap (BMP) file and reload.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00014: GIF no longer supported**

**Cause:** An unsupported Graphic Interchange Format (GIF) file was encountered as a report image.

**Action:** Convert the GIF file to a Bitmap (BMP) file and reload.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00015: GIF no longer supported**

**Cause:** An unsupported Graphic Interchange Format (GIF) file was encountered as a report image.

**Action:** Convert the GIF file to a Bitmap (BMP) file and reload.

---

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00016: Batches run successfully will be cleaned up after {0} milliseconds.**

**Cause:** The batches were run successfully and will be cleaned up.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00017: The thread which cleans up scheduled batches will wake up every {0} milliseconds.**

**Cause:** The thread that cleaned the scheduled batches occurs every number of milliseconds.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00019: Cannot not find binary file: {0}**

**Cause:** The reported file could not be found and may result in missing data, text, or images.

**Action:** Ensure that the selected .BES file is correct and corresponds to the loaded .DES file.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00021: Attempted to cancel job, but could not find JobId: {0}**

**Cause:** The selected job no longer exists.

**Action:** Check if the job already completed or was removed by another user.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00022: Unable to open connection to data source. Failure result: {0}.**

**Cause:** Either a connection to the data source was not established, or the user credentials for the data source were incorrect.

**Action:** Verify that the connectivity to the data source and verify that the user credentials for the data source are accurate.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00023: Cannot find job definition {0}**

---

**Cause:** The selected batch job was not found.

**Action:** Refresh the display and verify that the requested batch exists, then try again.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00026: Key '{0}' already exists for {1}**

**Cause:** The given extended link was not added to the element because it already exists.

**Action:** Ensure that the taxonomy does not attempt to add duplicate extended links to the same element.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00027: Unable to load error message for key: {0}**

**Cause:** The resource for the error message was not found.

**Action:** An error message or translated message is missing from the resource file. Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00028: Unable to load error message for key: {0}**

**Cause:** The resource for the error message was not found.

**Action:** An error message or translated message is missing from the resource file. Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00029: Unable to load error message for key: {0}**

**Cause:** The resource for the error message was not found.

**Action:** An error message or translated message is missing from the resource file. Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00030: Unable to load error message for key: {0}**

**Cause:** The resource for the error message was not found.

**Action:** An error message or translated message is missing from the resource file. Contact Oracle Support Services.

**Level:** 32

---

**Type:** ERROR

**Impact:**

**EPMFR-00031: Class '{0}' must extend from the ReportAddOn class**

**Cause:** This is custom code in which the AddOn class did not extend the ReportAddOn class.

**Action:** The Java class in the Reports AddOn needs to extend the ReportAddOn class.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00032: Error executing batch: {0}**

**Cause:** The Reports Web Server was not available, the report to be run was not located, or there were no correct user credentials supplied for the batch routine.

**Action:** Verify the availability of the Reports Web Server, that the report in the batch exists, and that the user credentials for the batch routine are correct.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00033: Type {0} of a service on {1} is shutting down.**

**Cause:** A service on the noted server was shut down and removed from the registry.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00034: Type {0} of a service on {1} is started.**

**Cause:** A service on the noted server was started and added to the registry.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00035: Initializing Financial Reporting Analytic Data Model Service**

**Cause:** The Financial Reporting Analytic Data Model Service was about to initialize.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00036: Failure to initialize Financial Reporting Analytic Data Model Service**

---

**Cause:** There was most likely an installation or configuration error that caused the initialization error.

**Action:** Check the installation and configuration logs for more information.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00037: Stopping Financial Reporting Analytic Data Model Service**

**Cause:** The Financial Reporting Analytic Data Model Service was stopping.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00038: Failure to stop Financial Reporting Analytic Data Model service**

**Cause:** There most likely was a memory issue on the system.

**Action:** Check the system hardware for memory usage issues.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00039: Initializing Financial Reporting Printing Service**

**Cause:** The Financial Reporting Printing Service was initializing.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00040: Failure to start Financial Reporting Printing Service**

**Cause:** The Financial Reporting Printing Service failed to initialize.

**Action:** Look at the installation and configuration logs for possible errors; check the system for memory errors, disk space, or other system related issues.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00041: Stopping Financial Reporting Printing Service**

**Cause:** The Financial Reporting Printing Service Service stopped.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00042: Failure to stop Financial Reporting Printing Service**

---

**Cause:** The Financial Reporting Printing Service failed to stop.

**Action:** Check the logs for print jobs running. Also, check the system for memory errors or other system-related issues.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00043: Initializing and starting Financial Reporting Reporting Service**

**Cause:** The Financial Reporting Reporting Service initialized.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00044: Failure to start Financial Reporting Reporting Service**

**Cause:** The Financial Reporting Reporting Service failed to initialize due to one of a few possible reasons.

**Action:** Look at the installation and configuration logs for possible errors; check the system for memory errors, disk space, or other system related issues.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00045: Stopping Financial Reporting Reporting Service**

**Cause:** The Financial Reporting Reporting Service has stopped.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00046: Failure to stop Financial Reporting Reporting Service**

**Cause:** The Financial Reporting Reporting Service failed to stop.

**Action:** Check the logs for running reports, batch jobs, or any other running report process. Also, check the system for memory errors or other system-related issues.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00047: Financial Reporting Scheduler Service initialized**

**Cause:** The Financial Reporting Scheduler Service was initializing.

**Action:** No action is required

**Level:** 32

**Type:** INFORMATION



---

**Impact:**

**EPMFR-00048: Failure to start Financial Reporting Scheduler Service**

**Cause:** The Financial Reporting Scheduler Service failed to initialize.

**Action:** Look at the installation and configuration logs for possible errors; check the system for memory errors, disk space, or other system-related issues.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00049: The Financial Reporting Scheduler Service stopped**

**Cause:** The Financial Reporting Scheduler Service has stopping.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00050: Failure to stop Financial Reporting Scheduler Service**

**Cause:** The Financial Reporting Scheduler Service failed to initialize.

**Action:** Check the logs for scheduled jobs that may have failed. Also, check the system for memory errors or other system-related issues.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00051: Returning HsServer from machine {0}**

**Cause:** The Reports server was successfully selected from the registry.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00052: Cannot get Report Server object**

**Cause:** Failed to get the Report Server object from the registry. There may be an access or connectivity issue.

**Action:** Verify that the registry, RMI, and Reports Servers are all operational and that there are no network issues. Also verify all user credentials. Contact Oracle Support Services if this issue cannot be resolved.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00053: Unable to find Print Server**

**Cause:** Failed to get the print server object from the registry; possible access or connectivity issue.

---

**Action:** Verify that the registry, RMI, and Reports Servers are all operational and that there are no network issues. Also verify all user credentials. Contact Oracle Support Services if this issue cannot be resolved.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00054: Cannot connect to server on {0}**

**Cause:** Failure to connect to the specified server is most likely due to an RMI (Remote Method Invocation) issue.

**Action:** Verify that the RMI (Remote Method Invocation) service is running without errors. Also look for possible network issues. Contact Oracle Support Services if additional assistance is needed.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00055: Could not connect to server on {0}**

**Cause:** Failed to connect to the specified server most likely due to an RMI issue.

**Action:** Verify the RMI (Remote Method Invocation) service is running without errors. Also look for possible network issues. Contact Oracle Support Services if additional assistance is needed.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00056: Cannot obtain report server list from server.**

**Cause:** Failed to get a report server list because the Hyperion Registry is not accessible.

**Action:** Verify that the Hyperion Registry is running without errors. Also look for possible network issues. Contact Oracle Support Services if additional assistance is needed.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00057: Cannot obtain print server list from server**

**Cause:** Failed to get a print server list because the Hyperion Registry is not accessible.

**Action:** Verify that the Hyperion Registry is running without errors. Also look for possible network issues. Contact Oracle Support Services if additional assistance is needed.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00058: Cannot obtain scheduler server from server**

---

**Cause:** Failed to get a scheduler server list because the Hyperion Registry is not accessible.

**Action:** Verify that the Hyperion Registry is running without errors. Also look for possible network issues. Contact Oracle Support Services if additional assistance is needed.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00059: Invalid login: ({0})**

**Cause:** The login security credentials for a given data source were invalid.

**Action:** Provide data source credentials to view the portlet content.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00060: Invalid report: ({0})**

**Cause:** The specified Financial Reports report failed to be generated by the portlet.

**Action:** Ensure that the specified report exists or can be run using the Financial Reports Web preview.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00061: Cannot retrieve Row & Column Template [{0}] into Grid '{1}'. The template may have been moved, renamed or deleted from the repository.**

**Cause:** A reference to a Row and Column template was not found in the repository.

**Action:** Ensure that the template exists in the expected folder within the repository. It could have been renamed, moved, or deleted. But it needs to exist in the specified path.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00062: Error adding incompatible Row & Column template [{0}] to Grid '{1}'. The template and/or grid may have been modified such that they are no longer compatible. The insert error code is {2}.**

**Cause:** Dimensions on row or column have changed making the Row & Column template invalid for the grid.

**Action:** No action is required. The invalid Row & Column template was removed.

**Level:** 32

**Type:** ERROR

**Impact:**

---

**EPMFR-00063: The maximum calculation limit of {0} has been reached. Further processing of this cell calculation will not occur**

**Cause:** The report contained unevaluated cells due to reaching the maximum calculations limit.

**Action:** Update the MaximumCalculationIterations setting. Refer to the documentation for instructions.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00064: Error while opening connection for user: {0} to the datas source: {1};{2}**

**Cause:** An error occurred when attempting to establish a connection with a selected data source.

**Action:** Ensure that the data source exists and is available. Also, verify user credentials to selected data source are accurate.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00065: Financial Management server {0} is not responding**

**Cause:** A connection could not be made to the Financial Management server. The Financial Management server is either offline or has been reconfigured.

**Action:** Verify the Financial Management connection information and ensure that the server or cluster is online.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00066: Attempting to cancel Essbase report script for ID: {0}**

**Cause:** User issued a cancel request for the essbase report script.

**Action:** No action is required. The Essbase report script will be canceled if possible.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00067: Canceling run for job with instanceId: {0}**

**Cause:** The job with the associated ID was canceled.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00068: Invalid attempt to access controlled file: {0}**

**Cause:** The file path was incorrect.

**Action:** Enter the correct file location and try again.

---

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00069: START: JobId: {0}; User: {1}; Name: {2}**

**Cause:** The START time of the associated job with the given ID was marked.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00070: END: JobId: {0}**

**Cause:** The END time of the associated job with the given ID was marked.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00071: Custom Socket Factories loaded successfully**

**Cause:** The sockets connecting to the RMI server were successfully established.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00072: Unable to establish port within established range**

**Cause:** The established range of ports selected to access the RMI server were unavailable.

**Action:** Either reestablish a different range with available ports, or, stop nonessential processes that are occupying the port range, and then retry.

**Level:** 32

**Type:** FATAL

**Impact:**

**EPMFR-00073: User preferences or ReportServer object are not properly initialized.  
Unable to save User Preferences.**

**Cause:** The connection to the server possibly was disrupted.

**Action:** Log out and try again.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00074: User preferences or ReportServer object are not properly initialized.  
Unable to save User Preferences.**

**Cause:** The connection to the server possibly was disrupted.

---

**Action:** Log out and try again.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00075: Cannot connect to Related Content destination. status = {0}.**

**Cause:** The Related Content destination was not available.

**Action:** Verify that the Related Content destination exists and that the calling object has it set correctly.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00076: Substituting related content attributes. Reference String is: [{0}]**

**Cause:** The related content attributes were substituted.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00077: Error exporting file: {0}**

**Cause:** The file may have been deleted.

**Action:** Refresh the browser and try the operation again.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00078: Error exporting file: {0}**

**Cause:** The file may have been deleted.

**Action:** Refresh the browser and try the operation again.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00079: Error getting folder: {0}**

**Cause:** The folder may have been deleted.

**Action:** Refresh the browser and retry the operation.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00080: Error retrieving report or snapshot: {0}**

**Cause:** The book contains a report or snapshot that was not found.

**Action:** Ensure that the report or snapshot exists in the book.

---

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00081: Connected to server: {0}**

**Cause:** A successful connection was made to the Report Server.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00082: Unable to stop job {0}**

**Cause:** The selected data source was not responding to the cancel request.

**Action:** Verify that the selected data source is accessible and operating. Check the logs of the data source for any other issues.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00083: Unable to delete job: {0}**

**Cause:** The Report Server could not be accessed.

**Action:** Verify that the Report Server is running and verify that the user has permissions to delete the scheduled job.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00084: Error executing member selection: [{0}]**

**Cause:** Either the member selection was not valid or the data source connection failed.

**Action:** Check connection to the data source.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00085: Error executing member selection: [{0}]**

**Cause:** Either the member selection was not valid or the data source connection failed.

**Action:** Check the connection to the data source.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00086: HFM (Hyperion Financial Management) indicates that either data or metadata has changed.**

---

**Cause:** HFM (Hyperion Financial Management) indicates that either data or metadata had changed.

**Action:** The current connection needs to be discarded and a new connection acquired, then rerun the book or report.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00087: Error in setting up the 'Org By Period Filter'**

**Cause:** Either the member selection was not valid or the data source connection failed.

**Action:** Check connection to the data source.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00088: External authentication successful for user: [{0}] succeeded in {1} ms.**

**Cause:** The user logon was successful in the associated time in milliseconds.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00089: user [{0}] has no access to Financial Reporting.**

**Cause:** A user without any Financial Reporting roles tried to access Financial Reporting.

**Action:** Review the user's credentials for security purposes.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00090: Failure to initialize ADM**

**Cause:** The Financial Reporting Server did not initialize the ADM component for data source communication.

**Action:** A configuration issue is the likely cause, so verify that the ADM is specified within the classpath or path.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00091: Starting Report Server and modules**

**Cause:** The Report Server and associated modules were started.

**Action:** No action is required.

**Level:** 32



---

**Type:** INFORMATION

**Impact:**

**EPMFR-00092: Error starting Report Server**

**Cause:** The report server did not start.

**Action:** Check a variety of possible failures including: Port conflicts or other configuration issues, system hostname incorrectly configured, and that the RMI registry is available.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00093: Successful start for Financial Reporting Authentication, Repository and Reports modules.**

**Cause:** The Financial Reporting Authentication, Repository and Reports modules started successfully.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00094: Error during datasource connection cleanup**

**Cause:** Another request to close the datasource connections may have been issued previous to the current request.

**Action:** Check the list of active sessions and retry, closing any existing sessions.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00095: Invalid command line parameters**

**Cause:** The number of command line parameters was incorrect.

**Action:** Ensure that the correct number of parameters are entered when starting from the command line.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00096: Error while writing the binary data of the report object to file: ({0})**

**Cause:** An error occurred while writing the binary data of the report object to the specified file.

**Action:** Verify that the user has permission to write to the file and ensure that there is enough disk space.

**Level:** 32

**Type:** ERROR

**Impact:**

---

**EPMFR-00097: Removing annotation on existing snapshot as duplicate annotation is generated: {0}**

**Cause:** The annotation on the existing snapshot was a duplicate and was removed.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00098: Retrieving annotations from repository: {0}**

**Cause:** Annotations were retrieved from the repository

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00099: In method Instance.createDuplicateAnnotationsForSnapshot() annotation count: {0}**

**Cause:** In method Instance.createDuplicateAnnotationsForSnapshot() annotation count: {0}

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00100: Creation of duplicate annotations for snapshot successful: {0}**

**Cause:** Duplicate annotations for snapshot were completed: {0}

**Action:** No Action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00101: Not expecting Context Value; Finding: {0}; Expected: {1}**

**Cause:** An invalid Context Value was received and might not exist in the repository.

**Action:** Verify that the instance exists in the repository.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00102: Error in sending e-mail: {0}**

**Cause:** An error occurred while sending an e-mail and can be caused by network issues or invalid information.

**Action:** Verify the e-mail address and check if mail server is available.

**Level:** 32

---

**Type:** ERROR

**Impact:**

**EPMFR-00103: Error while getting dimension: {0}**

**Cause:** The datasource connection was either lost or not established. Otherwise an internal error in the data source occurred.

**Action:** Verify that the data source is running and accessible, and then retry. Otherwise, check the data source logs for any data access issues.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00104: Error while getting dimension: {0}**

**Cause:** The datasource connection was either lost or not established. Otherwise an internal error in the data source occurred.

**Action:** Verify that the data source is running and accessible, and then retry. Otherwise check the datasource logs for any data access issues.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00105: Error while getting member selections**

**Cause:** The datasource connection was either lost or not established. Otherwise an internal error in the data source occurred.

**Action:** Verify that the data source is running and accesible, and then retry. Otherwise check the datasource logs for any data access issues.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00106: Failure in exporting user session for use in static HTML generation**

**Cause:** Access to the Report Server connection might have been lost.

**Action:** Verify the Remote Method Invocation (RMI) service is operational and the same with the Report Server. Ensure that all communication routes between the services are also available. Contact Oracle Support Services if all services and communication routes are operational.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00107: Error while storing PDF with the instance: {0}**

**Cause:** The PDF file was not stored, likely due to: The central repository was not available or access was revoked, an invalid file name was specified, or the print server was not available.

**Action:** Verify that the central repository is accessible and that everything is configured with the correct credentials. Also, ensure that the print server is available and that the file name to be saved has a valid file name.

---

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00108: Error while storing PDF with the instance: {0}**

**Cause:** The PDF file was not stored, likely due to: The central repository was not available or access was revoked, an invalid file name was specified, or the print server was not available.

**Action:** Verify that the central repository is accessible and that everything is configured with the correct credentials. Also, ensure that the print server is available and that the file name to be saved has a valid file name.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00109: Error while storing PDF with the instance: {0}**

**Cause:** The PDF file was not stored, likely due to: The central repository was not available or access was revoked, an invalid file name was specified, or the print server was not available.

**Action:** Verify that the central repository is accessible and that everything is configured with the correct credentials. Also, ensure that the print server is available and that the file name to be saved has a valid file name.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00110: Error while storing PDF with the instance: {0}**

**Cause:** The PDF file was not stored, likely due to: The central repository was not available or access was revoked, an invalid file name was specified, or the print server was not available.

**Action:** Verify that the central repository is accessible and that everything is configured with the correct credentials. Also, ensure that the print server is available and that the file name to be saved has a valid file name.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00111: Error while storing PDF with the instance: {0}**

**Cause:** The PDF file was not stored, likely due to: The central repository was not available or access was revoked, an invalid file name was specified, or the print server was not available.

**Action:** Verify that the central repository is accessible and that everything is configured with the correct credentials. Also, ensure that the print server is available and that the file name to be saved has a valid file name.

**Level:** 32

**Type:** ERROR

**Impact:**

---

**EPMFR-00112: Error while storing PDF with the instance: {0}**

**Cause:** The PDF file was not stored, likely due to: The central repository was not available or access was revoked, an invalid file name was specified, or the print server was not available.

**Action:** Verify that the central repository is accessible and that everything is configured with the correct credentials. Also, ensure that the print server is available and that the file name to be saved has a valid file name.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00113: Cannot find the static book template root directory**

**Cause:** The static book template root directory within the scheduler properties was not found.

**Action:** Check if there are any product configuration issues within the config logs. Check if the SchedulerTemplate is defined in fr\_scheduler.properties.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00114: Error creating zip file. File does not exist: {0}.**

**Cause:** The specified file and path did not exist.

**Action:** Verify that the file and path specified exist.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00115: Data source names to validate: {0}**

**Cause:** A status message lists the data sources that were validated.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00116: Data source names to validate: {0}**

**Cause:** A status message that lists the data sources that were validated.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00117: Connecting to Report Server: {0}**

**Cause:** The Report Server was connected for validation.

**Action:** No action is required.

**Level:** 32

---

**Type:** INFORMATION

**Impact:**

**EPMFR-00118: Users to validate: {0}**

**Cause:** Users were validated.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00119: Users to validate: {0}**

**Cause:** User were validated.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00120: Finding {0} match(es).**

**Cause:** A status message was provided with the data source information from the user's point of view.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00121: This action will delete {0} POVs**

**Cause:** A status message was provided that stated the number of POVs that were deleted.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00122: Not finding POVs**

**Cause:** A status message was provided that stated that no POVs were found.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00123: User POV import LoginID = {0}**

**Cause:** A status message was provided that listed the user ID while importing a user POV.

**Action:** No action is required.

**Level:** 32

---

**Type:** INFORMATION

**Impact:**

**EPMFR-00124: Not finding user: {0}**

**Cause:** There was an unforeseen condition where user information could not be extracted from security.

**Action:** Generally this error should not happen. An extreme condition where this may occur is if security were to intermittently fail. Check the foundation services and the network for possible issues. Contact Oracle Support Services if unable to be resolved.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00125: Member missing: {0}**

**Cause:** The member name was not found within the data source because it either did not exist or could not be seen by the current user. It will not be imported.

**Action:** By default, the member name is skipped. However, if the member name is needed, then it must be made available either by adjusting the datasource security access for the user, or by entering the member name into the data source.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00126: No DATASOURCE\_NAME in XML file**

**Cause:** The XML file being imported for user POV information was missing a datasource name.

**Action:** Supply a valid datasource name in the XML file.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00127: Error loading config file: {0}**

**Cause:** The specified config file did not exist or was not accessible.

**Action:** Supply a valid and accessible file name as a parameter.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00128: Missing AdminUser**

**Cause:** The configuration file did not have an administrative user (AdminUser) specified.

**Action:** In the configuration file, specify a user (AdminUser) with Administrator access.

**Level:** 32

**Type:** ERROR

---

**Impact:**

**EPMFR-00129: No AdminPassword**

**Cause:** The configuration file did not have an administrator password (AdminPassword) specified.

**Action:** In the configuration file, specify an administrator password (AdminPassword) for the user.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00130: No ImportFileName**

**Cause:** The configuration file did not have a user POV import file name (ImportFileName).

**Action:** Specify a valid import file name (ImportFileName) when running in import mode.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00131: ImportFileName missing: {0}**

**Cause:** The specified user POV import file name (ImportFileName) was invalid.

**Action:** Specify a valid import file name (ImportFileName) when running in import mode.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00132: Error while reading the ImportFile**

**Cause:** An error occurred while reading the import file. This could be caused by a file access issue or any other error while processing the import file.

**Action:** Verify that the file is still accessible and readable to the user. Look for other issues within both the Report Server and connecting data sources for other possible causes. Contact Oracle Support Services for additional assistance.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00133: Error while reading the ImportFile**

**Cause:** An error occurred while reading the import file. This could be caused by a file access issue or any other error while processing the import file.

**Action:** Verify that the file is still accessible and readable to the user. Look for other issues within both the Report Server and connecting data sources for other possible causes. Contact Oracle Support Services for additional assistance.

**Level:** 32

**Type:** ERROR



---

**Impact:**

**EPMFR-00134: No ExportFileName**

**Cause:** The user POV export file name (ExportFileName) was not specified.

**Action:** Specify a valid user POV export file name (ExportFileName).

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00135: No ReportServer**

**Cause:** A valid and working Report Server (ReportServer) was not specified.

**Action:** Specify a valid and working Report Server (ReportServer).

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00136: Starting Hyperion Financial Reporting ManageUserPOV Utility at: {0}**

**Cause:** A status message indicating the ManageUserPOV utility has started and accompanied by a time stamp to monitor the time lapse.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00137: Ending Hyperion Financial Reporting ManageUserPOV Utility at: {0}**

**Cause:** The ManageUserPOV utility was ended and accompanied by a time stamp to mark the end of the time lapse.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00138: Usage: ManageUserPov Mode ConfigFile\tMode = import | export | delete\tConfigFile = configuration file name such as ManageUserPov.properties**

**Cause:** An instruction about how to use the ManageUserPov utility was provided.

**Action:** Follow the instructions of the message.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00139: Data source does not exist: {0}, A new one will be created.**

**Cause:** The data source was not previously configured but the utility attempted to create a connection with the specified data source automatically.

**Action:** No action is required unless a new data source cannot be created automatically.

---

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00140: Creating data source: {0}**

**Cause:** The data source was created successfully.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00141: Exception: {0} in loading locale strings for locale: {1}**

**Cause:** The file that contains the translated messages either was not found or the file contained errors.

**Action:** Look at the installation and configuration logs for possible errors. Contact Oracle Support Services for additional assistance.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00142: Error while storing PDF**

**Cause:** The PDF file was not stored properly, likely due to: The central repository was not available or access was revoked, an invalid file name was specified, The print server was not available.

**Action:** Verify that the central repository is accessible and that everything is configured with the correct credentials. Also, ensure that the print server is available and that the file name to be saved has a valid file name.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00143: Error while storing PDF**

**Cause:** The PDF file was not stored properly, likely due to: The central repository was not available or access was revoked, An invalid file name was specified, The print server was not available.

**Action:** Verify that the central repository is accessible and that everything is configured with the correct credentials. Also, ensure that the print server is available and that the file name to be saved has a valid file name.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00144: Error while storing PDF**

**Cause:** The PDF file was not stored properly, likely due to: The central repository was not available or access was revoked, An invalid file name was specified, The print server was not available.

---

**Action:** Verify that the central repository is accessible and that everything is configured with the correct credentials. Also, ensure that the print server is available and that the file name to be saved has a valid file name.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00145: Error while storing PDF**

**Cause:** The PDF file was not stored properly, likely due to: The central repository was not available or access was revoked, An invalid file name was specified, The print server was not available.

**Action:** Verify that the central repository is accessible and that everything is configured with the correct credentials. Also, ensure that the print server is available and that the file name to be saved has a valid file name.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00146: Error storing PDF**

**Cause:** The PDF file was not stored properly, likely due to: The central repository was not available or access was revoked, An invalid file name was specified, The print server was not available.

**Action:** Verify that the central repository is accessible and that everything is configured with the correct credentials. Also, ensure that the print server is available and that the file name to be saved has a valid file name.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00147: Error storing PDF.**

**Cause:** The PDF file was was not stord properly, likely due to: The central repository was not available or access was revoked, An invalid file name was specified, The print server was not available.

**Action:** Verify that the central repository is accessible and that everything is configured with the correct credentials. Also, ensure that the print server is available and that the file name to be saved has a valid file name.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00148: Start of print server job**

**Cause:** print server job, like printing of report or book, was started.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

---

**EPMFR-00149: Completed printing of book or report**

**Cause:** The book or report printing was completed.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00150: Cannot get page number count for instance '{0}'. Continuous page numbers may not be correct.**

**Cause:** There was no page count for instance '{0}'. Continuous page numbers may be applied incorrectly.

**Action:** Verify that the print server is installed correctly.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00152: Cannot find BookTOCPrintTemplate {0} entry in properties file. Cannot generate Book TOC.**

**Cause:** The specified BookTOCPrintTemplate entry was not found in the properties file. The Book TOC was not generated.

**Action:** Verify that the print server is installed correctly.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00153: Cannot print report '{0}' within Book '{1}'**

**Cause:** The specified report was not printed within the specified book.

**Action:** Ensure that all external object links in the book are correct, that the book is valid, and that the report exists in the repository.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00157: Cannot obtain page count from file '{0}'. The file type is not supported for printing.**

**Cause:** The page count was not obtained from the specified file. The file type is not supported for printing.

**Action:** Verify that all the external links are satisfied and the instance runs correctly in HTML.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00160: Cannot retrieve the document file: '{0}'**

**Cause:** The specified document file was not retrieved.

**Action:** Verify that the PDF output location is correct in the property file.

---

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00161: Error generating print for report instance '{0}'. Return code: {1}**

**Cause:** There was an error when trying to generate a printing of the specified report instance.

**Action:** Verify that the instance runs correctly in HTML and if it has attachments, that the links are valid.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00162: Start of run for {0} job {1}**

**Cause:** The specified print job was started.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00163: End of run for {0} end**

**Cause:** The specified print job ended.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00164: Cannot print using printer '{0}'. The printer is either not available to the Print Server or not configured for the host computer's services.**

**Cause:** The specified printer was not used because either it was not available to the print server, or it was not configured for the host computer's services.

**Action:** Ensure that the print server is installed correctly.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00165: Error when printing an instance**

**Cause:** There was an error generated when the instance was printing.

**Action:** Verify that the instance runs correctly in HTML and if it has attachments, that the links are valid.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00166: No page count for the table of contents in book '{0}'**

---

**Cause:** The page count for the table of contents in the specified book was not obtained.

**Action:** Verify that all external object links in the book are correct and that the book is valid.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00167: No table of contents in book '{0}'**

**Cause:** The table of contents in the book was not produced.

**Action:** Verify that all external object links in the book are correct and that the book is valid.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00168: Cannot merge PDF file '{0}'. The file does not exist.**

**Cause:** The specified PDF file was not merged because the file did not exist.

**Action:** Verify that the print server is installed correctly and Ghostscript is there.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00169: Error in merging PDF file ({0})**

**Cause:** The attempt to merge the specified PDF file generated an error.

**Action:** Verify that the print server is installed correctly and that Ghostscript is there.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00170: Cannot get page number count for instance '{0}'. Continuous page numbers may not be correct.**

**Cause:** There was no page count or continues page numbers because the print server might be installed incorrectly.

**Action:** Verify that all external object links in the book are correct and that the book is valid.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00171: Cannot print instance: '{0}'. The PostScript file for the instance does not exist.**

**Cause:** The specified instance was not printed. The PostScript file for the instance did not exist.

**Action:** Ensure that Ghostscript is installed.

---

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00172: Cannot print instance: '{0}'. The PostScript file for the instance does not exist.**

**Cause:** The specified instance was not printed. The PostScript file for the instance did not exist.

**Action:** Ensure that Ghostscript is installed.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00173: Error generating the bookmark outline for '{0}'**

**Cause:** The bookmark outline for the specified PDF file generated an error.

**Action:** Ensure that the iText version is correct.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00174: Error generating the book table of contents for '{0}'**

**Cause:** The book table of contents for the specified PDF file generated an error.

**Action:** Verify that the iText version is correct.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00175: Cannot print document file: '{0}' \tError code: {1}, Last Error: {2}**

**Cause:** The specified document file was not printed.

**Action:** Verify that the external document link is correct.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00176: Cannot print document file: '{0}' \tError code: {1}, Last Error: {2}**

**Cause:** The specified document file was not printed.

**Action:** Verify that the external document link is correct.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00177: Cannot obtain page count from file '{0}'. The file type is not supported for printing.**

**Cause:** The page count was not obtained from the specified file. The file type is not supported for printing.

---

**Action:** Ensure that the file type is supported by print server.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00178: Error writing external file '{0}'. It will not be included in the PDF output.**

**Cause:** There was an error when writing the specified external file.

**Action:** Verify that the PDF output location is correct in the property file.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00179: Error reading external PDF file '{0}'. It will not be included in the PDF output.**

**Cause:** There was an error when reading the specified external PDF file.

**Action:** Verify that iText has the correct version.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00180: Cannot retrieve the document file: '{0}' The returned error code is: {1}, Last error: {2}**

**Cause:** The specified document files was not retrieved.

**Action:** Verify that the external object's link is correct.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00181: Cannot produce the PDF output for the external document '{0}'**

**Cause:** The specified external document file did not produce PDF output.

**Action:** Verify that external link in the print object is correct.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00182: Cannot produce the PDF output for the book or instance '{0}'. The returned error code is: {1}, Last error: {2}**

**Cause:** The specified book or instance did not produce PDF output.

**Action:** Ensure that the HRDocumentPrinting.dll file is installed correctly.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00183: Cannot print instance or book: '{0}'. The print file is not produced.**



---

**Cause:** The specified instance or book was not printed. The print file was not produced.

**Action:** Verify that Ghostscript is installed correctly.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00184: Cannot send output to system printer. No printer specification.**

**Cause:** Because no printer was specified, the output was not sent to the system printer.

**Action:** Verify that the physical printer is correct.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00185: Cannot send instance output to system printer ('{0}'). No instance retrieval.**

**Cause:** The instance was not retrieved because the instance output was not sent to the system printer.

**Action:** Ensure that the server which has the repository is up and the object is running.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00186: Cannot send book output to system printer ('{0}'). No book retrieval.**

**Cause:** The book was not retrieved because the book output was not sent to the system printer.

**Action:** Ensure that the server which has the repository is up and the book is running.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00187: Invalid object type '{0}'. Cannot send output to system printer('{1}')**

**Cause:** Due to an invalid file type, the output was not sent to the specified system printer.

**Action:** Verify that the file type is supported by the print server.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00188: Successful printing '{0}' on system printer '{1}'**

**Cause:** The specified document was successfully printed on the specified system printer.

**Action:** No action is required.

---

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00189: FReexecute has invalid cell reference '{0}'**

**Cause:** FReexecute referenced an invalid cell.

**Action:** Verify that the FReexecute function's parameters are valid.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00190: FReexecute cannot generate an image for component '{0}'**

**Cause:** FReexecute could not generate an image for the specified component.

**Action:** Verify that the FReexecute function's parameters are valid.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00191: Cannot replace FReexecute function with the result.**

**Cause:** The FReexecute function could not be replaced with the result.

**Action:** Verify that Microsoft Word is installed on the machine where the print server is located.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00192: Cannot load Ghostscript or Distiller.**

**Cause:** Ghostscript or Distiller could not be loaded.

**Action:** Ensure that a supported version of Ghostscript or Distiller is properly installed on the print server.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00193: Error by Ghostscript in converting to PostScript.**

**Cause:** A supported version of Ghostscript may not be installed on the print server.

**Action:** Ensure that a supported version of Ghostscript is installed on the print server. If the problem persists, please contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00194: PDF root directory is {0}**

**Cause:** The cited directory name was the root directory of the PDF file.

**Action:** No action is required.

---

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00195: The report: [{0}] not cancelling**

**Cause:** The specified report failed to cancel.

**Action:** Verify that the Print Server or Network is not down.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00196: Printer {0} not accessible on print server: {1}**

**Cause:** Printer [{0}] was not accessible on print server: {1}.

**Action:** Verify that the print server is running and that the printer is available.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00198: ERROR: duplicate member in a prompt. Duplicate member will be removed.**

**Cause:** A duplicate member was found during member selection from the data source.

**Action:** No action is required. A duplicate member was removed from the member selection display.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00199: Over 50 dimensions in the data source. Removing the following dimensions which are set to the default member:**

**Cause:** An SAP data source with more than 50 dimensions was found. The SAP BAPI driver does not support accessing a data source with more than 50 dimensions.

**Action:** Reduce the number of dimensions in the data source or use a different data source.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00200: Error while setting POV:**

**Cause:** There was probably a connection error with the data source while setting the POV.

**Action:** Verify that the selected data source is available, access credentials are correct, or review the logs from the data source for other possible issues.

**Level:** 32

**Type:** WARNING

---

**Impact:**

**EPMFR-00201: Exception while getting dimension {0}**

**Cause:** There were datasource access issues or an internal error in the data source.

**Action:** Verify that the selected data source is available, access credentials are correct, or review the logs from the data source for other possible issues.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00202: Exception while getting dimension {0}**

**Cause:** There were datasource access issues or an internal error in the data source.

**Action:** Verify that the selected data source is available, access credentials are correct, or review the logs from the data source for other possible issues.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00203: Using Enterprise Scheduling Services for scheduling**

**Cause:** The Enterprise Scheduling Service was used.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00204: Error while starting Scheduler Server**

**Cause:** There was no access to the Global Service Manager.

**Action:** Verify that the Global Service Manager (GSM) is configured, running and available. Contact Oracle Support Services for additional assistance.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00205: Scheduler not ready to publish itself. Retry in {0} minutes.**

**Cause:** No Report servers were running.

**Action:** Ensure that the Report Server is running. Retry in the specified minutes.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00206: Successful start of Scheduler Server**

**Cause:** The Scheduler Server was started successfully.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

---

**Impact:**

**EPMFR-00207: Scheduler cannot contact any Report Server. Exiting.**

**Cause:** The Scheduler did not start because it did not contact any Report Server.

**Action:** Check on the availability of configured Reports Servers.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00208: Cannot start scheduler service:**

**Cause:** An unexpected error occurred while the Scheduler Service was binding to the Report Server.

**Action:** Contact Oracle Support Services for assistance.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00210: Scheduler Server stopped**

**Cause:** The Scheduler Server was stopped.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00213: Batch Job file: {0} not found. Error reported:**

**Cause:** The specified scheduled batch job file was not found. The file may have been deleted or moved to another location.

**Action:** Verify that the specified file exists in the expected location and rerun the job.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00215: Schema '{0}' missing. Attempting to create a new one.**

**Cause:** The given schema was not previously loaded. An attempt to load it occurred.

**Action:** Ensure that the given schema is valid and can be loaded. Look for additional warnings.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00216: Error while parsing a new schema:{0}**

**Cause:** The given error was produced while attempting to parse a schema.

**Action:** Ensure that the schema is valid and complies with the XBRL 2.1 specification.

---

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00217: Schema: '{0}' missing. Cannot delete it.**

**Cause:** The given schema was not found.

**Action:** Ensure that the given schema exists and can be removed from the file system.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00218: Schema: '{0}' missing. Cannot delete it.**

**Cause:** The given schema was not found.

**Action:** Ensure that the given schema exists and can be removed from the file system.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00219: Error during the auto-update of Schemas:{0}**

**Cause:** The error occurred while attempting to auto-update the schemas in the file system.

**Action:** Ensure that the schema exists, is valid and complies to the XBRL 2.1 specification.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00220: Error attempting to create a row and column template**

**Cause:** An unexpected error occurred while attempting to add a row and column template into a grid.

**Action:** Review the Report Server log file for details on the error.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00221: Error attempting to add a row or column from a template.**

**Cause:** An unexpected error occurred while attempting to add a row or column from a template into a grid.

**Action:** Review the Report Server log file for details on the error.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00222: Port number of 1099 is assumed due to error**

---

**Cause:** The Start Registry utility was unable to determine the Remote Method Invocation (RMI) port number automatically or through an incorrect user-passed parameter and has defaulted to port number 1099.

**Action:** If the port number was passed as a parameter, ensure that the port number is within the range above 1024 and below 32767. Also, ensure that the Remote Method Invocation (RMI) server is configured correctly.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00223: Port number of 1099 is assumed due to error**

**Cause:** The Start Registry utility was unable to determine the Remote Method Invocation (RMI) port number automatically or through an incorrect user-passed parameter and has defaulted to port number 1099.

**Action:** If the port number was passed as a parameter, ensure that the port number is within the range above 1024 and below 32767. Otherwise make sure the Remote Method Invocation (RMI) server is configured correctly.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00224: RMI registry already running on port: {0}. Cannot start a new registry.**

**Cause:** The Remote Method Invocation (RMI) registry was already running on the port number specified in the error message.

**Action:** If the registry is already running, no action is required. Otherwise, shut down the current Remote Method Invocation (RMI) registry session and rerun.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00225: Cannot create an RMI registry on port: {0}**

**Cause:** The Remote Method Invocation (RMI) registry was not created on the specified port number, most likely due to an unavailable valid port number.

**Action:** Retry using an available valid port number.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00226: Created an Remote Method Invocation (RMI) registry on port: {0}**

**Cause:** The Remote Method Invocation (RMI) registry was successfully created.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00227: Binding to Remote Method Invocation (RMI) registry**

---

**Cause:** The RMI registry was successfully bound.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00228: Financial Reporting Communication Server initialization complete**

**Cause:** The Financial Reporting Communication Server started and bound with the Remote Method Invocation (RMI) registry successfully.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00229: Already bound to Remote Method Invocation (RMI) registry. Cannot continue.**

**Cause:** The Financial Reporting Communication Server was already bound to the Remote Method Invocation (RMI) registry.

**Action:** Verify that the Financial Reporting Communication service is running normally with the Remote Method Invocation (RMI) registry on the intended port. Otherwise, restart the Financial Reporting Communication Server service and the RMI service, and retry.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00230: Report Server bound to the Remote Method Invocation (RMI) Registry**

**Cause:** The Report Server established a connection to the Remote Method Invocation (RMI) Registry.

**Action:** No action is required

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00231: Report Server started**

**Cause:** The Report Server has started successfully.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00232: Report Server stopped**

**Cause:** The Report Server has stopped successfully.

**Action:** No action is required.



---

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00233: Error while getting content at: ({0}). Trying ({1}/{2}) instead.**

**Cause:** The path for the taxonomy was not found.

**Action:** Ensure that the taxonomy exists for the given path.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00234: Unknown linkbase role: {0} found. Linkbase will not be included.**

**Cause:** The given linkbase could not be added as a reference from a taxonomy.

**Action:** Ensure that the given linkbase is valid and can be added as a reference to a taxonomy.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00235: The presentation linkbase '{0}' is empty. A flat taxonomy tree may display.**

**Cause:** The taxonomy's presentation linkbase was empty, which typically causes a flat taxonomy tree to be rendered.

**Action:** Provide a presentation linkbase for the given taxonomy.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00236: TaxonomyElement: {0} not found.**

**Cause:** The presentation linkbase had a reference to a taxonomy element that could not be found.

**Action:** Ensure that the presentation linkbase has references to valid taxonomy elements.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00237: Taxonomy Element Node: {0} not found**

**Cause:** A taxonomy element node could not be obtained referenced by the given element ID.

**Action:** Ensure that the taxonomy element exists with the taxonomy.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00238: Taxonomy element '{0}' already exists.**

---

**Cause:** The given taxonomy element had already been processed. The taxonomy seemed to have a duplicate element declaration.

**Action:** Ensure that the taxonomy does not contain duplicate taxonomy element declarations.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00239: The taxonomy element {0} was not mapped, as it is an abstract type.**

**Cause:** The given element could not exist within an instance document. Typically, this is because an abstract element was mapped.

**Action:** Ensure that only mappable taxonomy elements are mapped within a report. Do not map abstract elements.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00240: Element specified in the locator: {0} {1} not found**

**Cause:** The given taxonomy element could not be found from the given locator.

**Action:** Ensure that the taxonomy's locators have valid references to taxonomy elements.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00241: Element specified in the locator: {0} {1} not found**

**Cause:** The given taxonomy element could not be located from the given locator.

**Action:** Ensure that the taxonomy's locators have valid references to taxonomy elements.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00242: Error in TextCell {0} Col {1} Row {2} Formula: '{3}'\t Error: {4}**

**Cause:** There was a syntax error in the function.

**Action:** Fix the syntax error that is described in the error message.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00243: Error in TextObject Formula: '{0}'\t Error: {1}**

**Cause:** There was a syntax error in the function.

**Action:** Fix the syntax error that is described in the error message.

**Level:** 32

---

**Type:** ERROR

**Impact:**

**EPMFR-00244: Report Server Initializing**

**Cause:** The Report Server initialized.

**Action:** No action is required

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00245: Report Server started**

**Cause:** The Report Server initialized and started successfully.

**Action:** No action is required

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00246: Error while starting the Report Server**

**Cause:** The Report Server failed to initialize.

**Action:** Check a variety of possible failures including: Port conflicts or other configuration issues, incorrect system hostname configuration, and availability of the Remote Method Invocation (RM0).

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00247: Hyperion Financial Management reports that either Metadata or Data has changed. Discarding the current connection and reconnecting.**

**Cause:** Possible metadata or data load was performed on the Hyperion Financial Management (HFM) server.

**Action:** Rerun the book or report.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00248: Book contains reports not found: {0}**

**Cause:** The book contained reports which could not be found.

**Action:** Ensure that the contained report(s) exists.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00249: Cannot find data source ID: {0} {1}. Attempting to find data source with same name.**

**Cause:** A connection to the data source could not be made by using the stored data source ID.

---

**Action:** Verify that the data source is started or restored, and the credentials are correct.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00250: Could not find data source ID: {0} {1}. Creating a new data source.**

**Cause:** A connection to the data source could not be made by using the stored data source name.

**Action:** Verify that data source is started or restored, and the credentials are correct.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00251: Cannot not find data source ID: {0} {1}. Failed to create a new data source for it.**

**Cause:** A connection to the data source could not be made by using the stored data source ID or name, and failed to create a new data source automatically for it.

**Action:** Verify that the data source is started or restored, and the credentials are correct.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00252: Cannot find data source ID: {0} {1}. Attempting to find data source with same name.**

**Cause:** A connection to the data source could not be made by using the stored data source ID.

**Action:** Verify that the data source is started or restored, and the credentials are correct.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00253: Cannot find data source ID: {0} {1}. Attempting to find data source with same name.**

**Cause:** A connection to the data source could not be made by using the stored data source ID.

**Action:** Verify that the data source is started or restored, and the credentials are correct.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00254: Cannot not find data source ID: {0} {1}. Creating a new data source.**

---

**Cause:** A connection to the data source could not be made by using the stored data source name.

**Action:** Verify that the data source is started or restored, and the credentials are correct.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00255: Cannot find data source ID: {0} {1}. Creating a new data source.**

**Cause:** A connection to the data source could not be made by using the stored data source name.

**Action:** Verify that the data source is started or restored, and the credentials are correct.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00256: Cannot find data source ID: {0} {1}. Failed to create a new data source for it.**

**Cause:** Could not make a connection to the data source by using the stored data source ID or name, and failed to create a new data source automatically for it.

**Action:** Verify that the data source is started or restored, and the credentials are correct.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00257: Could not find data source ID: {0} {1}. Attempting to find data source with same name.**

**Cause:** A connection to the data source could not be made by using the stored data source ID.

**Action:** Verify that the data source is started or restored, and the credentials are correct.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00258: Could not find data source ID: {0} {1}. Attempting to find data source with same name.**

**Cause:** A connection to the data source could not be made by using the stored data source ID.

**Action:** Verify that the data source is started or restored, and the credentials are correct.

**Level:** 32

**Type:** WARNING

**Impact:**

---

**EPMFR-00259: Could not find data source ID: {0} {1}. Creating a new data source.**

**Cause:** A connection to the data source could not be made by using the stored data source ID.

**Action:** Verify that the data source is started or restored, and the credentials are correct.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00260: Could not find data source ID: {0} {1}. Creating a new data source.**

**Cause:** A connection to the data source could not be made by using the stored data source ID.

**Action:** Verify that the data source is started or restored, and the credentials are correct.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00261: Could not find data source ID: {0} {1}. Failed to create a new data source for it.**

**Cause:** A connection to the data source could not be made by using the stored data source ID or name, and failed to create a new data source automatically for it.

**Action:** Verify that the data source is started or restored, and the credentials are correct.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00262: Schema '{0}' not found. Attempting to create a new one.**

**Cause:** The given schema was not previously loaded. An attempt to load it occurred.

**Action:** Ensure that the given schema is valid and can be loaded. Look for additional subsequent warnings.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00263: XBRL Schema Manager not properly initialized**

**Cause:** The XBRL Schema Manager was not properly configured.

**Action:** Reconfigure the XBRL Schema Manager.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00264: XBRL Schema Manager not properly initialized**

**Cause:** The XBRL Schema Manager was not properly configured.

---

**Action:** Reconfigure the XBRL Schema Manager.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00265: Schema {0} was not found attempting to create a new one**

**Cause:** The given schema was not previously loaded. An attempt to load it occurred.

**Action:** Make sure the given schema is valid and can be loaded. Look for subsequent warnings.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00266: Taxonomy '{0}' does not have any namespace**

**Cause:** The given taxonomy did not declare a namespace and was not be processed.

**Action:** Ensure that the given taxonomy declares a valid namespace.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00267: Taxonomy '{0}' does not have any namespace**

**Cause:** The given taxonomy did not declare a namespace and was not processed.

**Action:** Ensure that the given taxonomy declares a valid namespace.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00268: Error while creating directories for emails:**

**Cause:** The Schedule Server attempted to create a directory for e-mails but failed, most likely due to a system disk access issue.

**Action:** Verify that the disk is not full and that the user has both read and write access to the drive.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00269: XBRL Footnote error retrieving report value. Report: {0}. Invalid Row ({1}) and Column ({2})**

**Cause:** An error occurred while retrieving the report value. Invalid row and/or column reference were given.

**Action:** Ensure that the mapped footnote has valid row and column references to a grid.

**Level:** 32

---

Type: ERROR

Impact:

**EPMFR-00270: XBRL No language definition in footnote**

**Cause:** A footnote in the report did not provide a valid language definition.

**Action:** Assign a language to every footnote.

Level: 32

Type: ERROR

Impact:

**EPMFR-00271: Report using unsupported version of XBRL. XBRL data is ignored.**

**Cause:** The report had embedded XBRL data. However the version was unrecognized and could not be processed.

**Action:** Ensure that the XBRL data in the report definition is saved with the proper Financial Reports version.

Level: 32

Type: ERROR

Impact:

**EPMFR-00272: Instance generation failed. File name specified: {0} is invalid.**

**Cause:** The specified filename for the instance report was null or invalid. The instance document was not generated.

**Action:** Provide a valid file name for the instance document.

Level: 32

Type: ERROR

Impact:

**EPMFR-00273: XBRL Footnote for '{0}' not properly set up**

**Cause:** The XBRL footnote had a reference to an invalid report object.

**Action:** Ensure that all XBRL footnotes have valid references to a report object (grid or text).

Level: 32

Type: ERROR

Impact:

**EPMFR-00274: Taxonomy element '{0}' is linked to an unregistered taxonomy '{1}'**

**Cause:** The given taxonomy element belongs to an unregistered taxonomy.

**Action:** Ensure that the taxonomy used within a report is registered in the taxonomy repository.

Level: 32

Type: ERROR

Impact:

**EPMFR-00275: Taxonomy element '{0}' has no context defined. It will not be persisted in the instance document.**



---

**Cause:** A taxonomy element was mapped to data in a report, but there was no XBRL context associated with it. The element was ignored and not added to the instance document.

**Action:** Ensure that all mapped taxonomy elements in a report have a corresponding mapped context.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00276: Taxonomy element '{0}' has no associated report object. It will not be persisted in the instance document.**

**Cause:** A mapped taxonomy element was mapped to an invalid report object (grid or text).

**Action:** Ensure that all taxonomy elements are mapped to a valid report object.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00277: Taxonomy element '{0}' has an unregistered taxonomy ('{1}'). It will not be persisted in the instance document.**

**Cause:** A mapped taxonomy element belonged to an unregistered taxonomy. The element was ignored and not added to the instance document.

**Action:** Ensure that all mapped taxonomy elements in a report belong to a taxonomy that is registered in the Financial Reports system.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00278: Cannot connect to server on {0}**

**Cause:** Connection to the specified server failed, most likely due to an Remote Method Invocation (RMI) issue.

**Action:** Verify that the Remote Method Invocation (RMI) service is running without errors. Also look for possible network issues. Contact Oracle Support Services if additional assistance is needed.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00279: Unable to find appropriate Service at {0}**

**Cause:** Connection to the specified server failed, most likely due to an Remote Method Invocation (RMI) issue.

**Action:** Verify that the Remote Method Invocation (RMI) service is running without errors. Also look for possible network issues. Contact Oracle Service Support if additional assistance is needed.

**Level:** 32

**Type:** ERROR

---

**Impact:**

**EPMFR-00280: Large imported file denied by the annotation UI**

**Cause:** A file exceeding the AttachedFileMaxSize property limit was loaded.

**Action:** Reduce the file size or increase the AttachedFileMaxSize property.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00281: Cannot create a Remote Method Invocation (RMI) registry on port: {0}**

**Cause:** Another Remote Method Invocation (RMI) registry was running at the specified port number.

**Action:** Verify the configuration for the Remote Method Invocation (RMI) registry to avoid conflicts.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00282: RMI (Remote Method Invocation) registry created on port: {0}**

**Cause:** The Remote Method Invocation (RMI) registry was created on the specified port.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00283: Unable to create registry**

**Cause:** An error occurred while attempting to establish a connection with the Remote Method Invocation (RMI) registry.

**Action:** Verify the configuration of the Remote Method Invocation (RMI) registry and ensure that it is running without errors.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00284: Financial Reporting Print Server started**

**Cause:** The print server started successfully.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00285: Print server not started**

**Cause:** An error occurred while attempting to establish a connection with the Remote Method Invocation (RMI) registry.

---

**Action:** Verify the configuration of the Remote Method Invocation (RMI) registry and ensure that it is running without errors.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00292: Element specified in the locator: {0} {1} not found.**

**Cause:** The given taxonomy element could not be located from the given locator.

**Action:** Ensure that the taxonomy's locators have valid references to taxonomy elements.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00293: Cannot initialize XBRL Schema Collection**

**Cause:** Most likely, there were no schemas in the specified XBRL Location.

**Action:** This message is harmless if you do not intend to use XBRL. If you do, ensure that you have created the appropriate schemas in the specified location.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00294: Invalid attempt accessing server controlled properties**

**Cause:** The client side code tried to access a server-only controlled property.

**Action:** No action needed.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00295: Unable to extract OBIEE session**

**Cause:** Attempt to get administration level session failed.

**Action:** Verify the administrator user configuration in OBIEE.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00297: Initialization of CredentialStore failed**

**Cause:** The credential store could not be located or could not be initialized.

**Action:** Ensure that the credential store is properly configured.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00298: Failed obtaining credentials from security store for {0}**

**Cause:** Expected credentials could not be retrieved from credential store.

---

**Action:** Verify the credentials stored in credential store.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00299: Failed obtaining credentials from security store for {0}**

**Cause:** Expected credentials could not be retrieved from credential store.

**Action:** Verify credentials stored in credential store.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00300: Attempt to get an undefined configuration property ({0})**

**Cause:** A property was not defined or set. A default property was not available.

**Action:** Contact Oracle Support Services to obtain the correct default property value and instructions to configure it.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00301: Attempt to get undefined configuration property ({0})**

**Cause:** A property was not defined or set. A default property was not available.

**Action:** Contact Oracle Support Services to obtain the correct default property value and instructions to configure it.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00303: Invalid attempt to authenticate with elevated user credentials**

**Cause:** The configured elevated user credentials caused exception when trying to authenticate.

**Action:** Check the configured elevated user credentials.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00304: Error while setting the POV for data source ID: {0}**

**Cause:** There was a problem storing the current POV.

**Action:** Verify access to the repository.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00305: PDFRootDirectory {0} not created. PDFs not generated.**

**Cause:** The folder required to create the PDF files could not be created.

---

**Action:** Create the required folder on the Print Server.

**Level:** 32

**Type:** FATAL

**Impact:**

**EPMFR-00306: getObjectById:Objects requested={0}, but objects returned is {1}**

**Cause:** Some of the objects were not accessible.

**Action:** No action is required.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00307: Cannot print using printer '{0}'. The printer is either not available to the Print Server or not configured for the host computer's services.**

**Cause:** The specified printer was not used because either it was not available to the print server, or it was not configured for the host computer's services.

**Action:** Ensure that the print server is installed correctly.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00308: Cannot print document file: '{0}' \tError code: {1}, Last Error: {2}**

**Cause:** The specified document file was not printed.

**Action:** Verify that the external document link is correct.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00309: Cannot print document file: '{0}' \tError code: {1}, Last Error: {2}**

**Cause:** The specified document file was not printed.

**Action:** Verify that the external document link is correct.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00310: Error writing external file '{0}'. It will not be included in the PDF output.**

**Cause:** There was an error when writing the specified external file.

**Action:** Verify that the PDF output location is correct in the property file.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00311: Cannot print instance: '{0}'. The PostScript file for the instance does not exist.**

---

**Cause:** The specified instance was not printed. The PostScript file for the instance did not exist.

**Action:** Ensure that Ghostscript is installed.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00312: Invalid attempt accessing server controlled properties**

**Cause:** The client side code tried to access a server-only controlled property.

**Action:** No action needed.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00313: Invalid attempt to authenticate with elevated user credentials**

**Cause:** The configured elevated user credentials caused exception when trying to authenticate.

**Action:** Check the configured elevated user credentials.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00314: Financial Reports is configured to use Classic Print Engine. Please start the Print Server separately**

**Cause:** This is a status message stating that the Financial Reporting Printing Service is configured to use the Classic Print Engine.

**Action:** Start the Print Server separately.

**Level:** 32

**Type:** INFORMATION

**Impact:**

**EPMFR-00315: Invalid user defined preferred date format ({1})**

**Cause:** User defined date format contains Invalid date format characters

**Action:** Update user preferences with valid a date format

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00316: Custom Socket Factories loaded successfully**

**Cause:** A status message stating that the sockets connecting to the RMI Server has successfully been established.

**Action:** No action is required.

**Level:** 32

**Type:** INFORMATION

---

**Impact:**

**EPMFR-00317: Unable to establish port within established range**

**Cause:** The established range of ports selected to access the RMI server are all unavailable.

**Action:** Either reestablish a different range with available ports, or, stop nonessential processes that are occupying the port range and then retry.

**Level:** 32

**Type:** FATAL

**Impact:**

**EPMFR-00318: Custom Socket Factories could not be loaded**

**Cause:** The configured socket factory classes could not be loaded.

**Action:** Check the configuration for the Socket classes and ensure the entries are correct.

**Level:** 32

**Type:** FATAL

**Impact:**

**EPMFR-00319: Book contains reports not found: {0}**

**Cause:** Book contains reports which could not be found.

**Action:** Ensure that the contained report(s) exists.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00323: FRExecute has invalid cell reference '{0}'**

**Cause:** FRExecute referenced an invalid cell.

**Action:** Verify that the FRExecute function's parameters are valid.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00324: FRExecute cannot generate an image for component '{0}'**

**Cause:** FRExecute could not generate an image for the specified component.

**Action:** Verify that the FRExecute function's parameters are valid.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00325: FRExecute cannot generate an image for component '{0}'**

**Cause:** FRExecute could not generate an image for the specified component.

**Action:** Verify that the FRExecute function's parameters are valid.

**Level:** 32

**Type:** ERROR

---

**Impact:**

**EPMFR-00326: FRExecute cannot generate an image for component '{0}'**

**Cause:** FRExecute could not generate an image for the specified component.

**Action:** Verify that the FRExecute function's parameters are valid.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00327: Cannot replace FRExecute function with the result.**

**Cause:** The FRExecute function could not be replaced with the result.

**Action:** Verify that Microsoft Word is installed on the machine where the print server is located.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00329: Error writing external file '{0}'. It will not be included in the PDF output.**

**Cause:** There was an error when writing the specified external file.

**Action:** Verify that the PDF output location is correct in the property file.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00330: Error writing external file '{0}'. It will not be included in the PDF output.**

**Cause:** Error writing the specified external file. It will not be included in the PDF output.

**Action:** Verify that the pdf output location is correct in property file.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00331: Cannot print document file: '{0}' \tError code: {1}, Last Error was: {2}**

**Cause:** The specified document file was not printed.

**Action:** Verify that the external document link is correct.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00332: Cannot print document file: '{0}' \tError code: {1}, Last Error was: {2}**

**Cause:** The specified document file was not printed.

**Action:** Verify that the external document link is correct.

**Level:** 32



---

**Type:** ERROR

**Impact:**

**EPMFR-00333: Cannot print report '{0}' within Book '{1}'. Make sure the report exists in the repository.**

**Cause:** The specified report was not printed within the specified book.

**Action:** Ensure that all external object links in book are correct, that the book is valid, and that the report exists in the repository.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00334: Cannot print report '{0}' within Book '{1}'. Make sure the report exists in the repository.**

**Cause:** The specified report was not printed within the specified book..

**Action:** Ensure that all external object links in book are correct, that the book is valid, and that the report exists in the repository.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00335: Error retrieving DataSourceList XML**

**Cause:** Error retrieving DataSourceList XML from the repository. A new DataSourceList XML will be created.

**Action:** No action needed.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00336: Could not find data source ID: {0} {1}. Attempting to find data source with same name.**

**Cause:** A connection to the data source could not be made by using the stored data source ID.

**Action:** Verify that the data source is started or restored, and the credentials are correct.

**Level:** 32

**Type:** WARNING

**Impact:**

**EPMFR-00337: Could not find data source ID: {0} {1}. Creating a new data source.**

**Cause:** A connection to the data source could not be made by using the stored data source ID.

**Action:** Verify that the data source is started or restored, and the credentials are correct.

**Level:** 32

**Type:** WARNING

---

**Impact:**

**EPMFR-00338: Could not find data source ID: {0} {1}. Failed to create a new data source for it.**

**Cause:** A connection to the data source could not be made by using the stored data source ID or name, and failed to create a new data source automatically for it.

**Action:** Verify that the data source is started or restored, and the credentials are correct.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00339: Usage: ManageUserPov Mode ConfigFile\tMode = import | export | delete\tConfigFile = configuration file name such as ManageUserPov.properties**

**Cause:** An instruction about how to use the ManageUserPov utility was provided.

**Action:** Follow the instructions of the message.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00340: Error loading config file: {0}**

**Cause:** The specified config file did not exist or was not accessible.

**Action:** Supply a valid and accessible file name as a parameter.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00341: Missing AdminUser**

**Cause:** The configuration file did not have an administrative user (AdminUser) specified.

**Action:** In the configuration file, specify a user (AdminUser) with Administrator access.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00342: Cannot print document file: '{0}' \tError code: {1}, Last Error: {2}**

**Cause:** The specified document file was not printed.

**Action:** Verify that the external document link is correct.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMFR-00343: Financial Reporting server is set to use embedded Print Server. Will not register myself with it**

**Cause:** Financial Reporting server is set to use embedded printing

---

**Action:** If you would like to use this external print server, please disable embedded printing in the Financial Reporting server

**Level:** 32

**Type:** ERROR

**Impact:**



---

## EPMWKSP-00101 to EPMWKSP-02508

**EPMWKSP-00101: Found application registration with ID "{0}" and name "{1}".**

**Cause:** Indicates the application registration which was found and is recognized by Workspace.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00102: Failed to generate context XML.**

**Cause:** Context information is invalid or could not be retrieved from the registry.

**Action:** Verify products have been properly configured by running Config Tool.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00103: Initializing Workspace Configuration.**

**Cause:** Workspace is initializing the system using information from the registry.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00104: There is an error detecting application ID for role checking.**

**Cause:** An application ID could not be retrieved for CSS role checking.

**Action:** Verify in the registry that all registered products have a valid value for property applicationId.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00105: Default Application ID for role checking is {0}.**

**Cause:** Indicates the application ID that will be used for CSS role checking.

**Action:** No action is required.

---

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00106: There was an error determining the URL.**

**Cause:** The logical webapp URL could not be obtained or is invalid.

**Action:** Verify that the logical webapp URLs specified in the registry for all registered products are valid.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00107: There was an error determining the context.**

**Cause:** The logical webapp context could not be obtained or is invalid.

**Action:** Verify that the logical webapp context specified in the registry for all registered products are valid.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00108: There was an error parsing file {0}.**

**Cause:** The xml in WSPProducts.xml could not be parsed or is invalid.

**Action:** Verify the file exists and that the xml is valid.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00109: There was an error initializing system registry: {0}.**

**Cause:** The system registry was not properly installed or configured.

**Action:** Verify connection to the registry is valid and re-run the config tool.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00110: Registry default properties: failed to check and set property {0}.**

**Cause:** The default properties could not be set.

**Action:** Verify the default registry properties file exists and that the values are valid.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00111: There was an error loading product configuration data: {0}**

**Cause:** The configuration file for at least one product could not be loaded.

**Action:** Check the Workspace configuration log for further error details.

---

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00112: Failed to initialize the BPMUI authentication class: {0}**

**Cause:** The class could not be found or initialization failed.

**Action:** Verify that the class is accessible and the entry in web.xml is valid.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00113: There was an error loading product configuration data: {0}**

**Cause:** The configuration file for at least one product could not be loaded.

**Action:** Check the Workspace configuration log for further error details.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00114: Workspace initialization complete.**

**Cause:** Workspace has initialized and processed the information from the registry.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00115: Workspace is running normally.**

**Cause:** No errors were detected during initialization.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00116: Parsing the product file generated the following warnings:**

**Cause:** Indicates the start of the list of possible issues encountered while parsing Workspace's Product file.

**Action:** Verify the Workspace's Products file exists and that the entries are valid.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00117: Workspace may not function properly unless these are fixed: {0}  
{1}**

**Cause:** Indicates the xml may not comply with the dtd.

**Action:** Resolve the issue specified in the warning.

---

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00118: End of warning messages.**

**Cause:** Indicates the end of the list of possible issues encountered while parsing Workspace's Product file.

**Action:** Verify all warnings are resolved or inconsequential.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00119: Product file parsed without errors.**

**Cause:** The Workspace's Product file was successfully processed.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00120: Attempting registry connection using:{0}{1}{2}{3}**

**Cause:** Indicates the registry information is being obtained to initialize Workspace.

**Action:** No action required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00122: Looking for the Workspace Product component (type: {0})**

**Cause:** Indicates the Product that is currently being validated and processed as one of the installed products in Workspace.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00123: Found component object: {0}**

**Cause:** Indicates the Workspace component that was discovered in the EPM Registry.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00124: Could not find the Workspace Product component. Check Registry connection and content.**



---

**Cause:** The registry connection or content may be invalid.

**Action:** Check Registry connection and content.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00125: Looking for Workspace Logical Webapp (child of Workspace Product, type: {0})**

**Cause:** Indicates that Workspace is searching the EPM Registry for its Logical Webapp.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00126: Could not find the Workspace logical webapp. Check Registry contents.**

**Cause:** The registry connection or content may be invalid.

**Action:** Check Registry contents.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00127: Could not find the Workspace Web Server component.**

**Cause:** Workspace was not configured properly.

**Action:** Check the web server is running and configured. Run config tool.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00128: Could not find the logical webapp as a child of the Workspace product node. Check Registry contents.**

**Cause:** Workspace was not properly registered.

**Action:** Check Registry contents. Run config tool.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00129: Workspace product node has multiple logical webapps. Check Registry contents.**

**Cause:** Workspace should have exactly one component of type LOGICAL\_WEB\_APP in the EPM Registry.

**Action:** Verify Registry contents and check configuration tool logs for deployment errors.

**Level:** 32

---

**Type:** ERROR

**Impact:**

**EPMWKSP-00130: Could not find the Workspace Web Server component as a child of the Workspace product node.**

**Cause:** Workspace was not properly configured.

**Action:** Check Registry contents. Run config tool.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00131: Found {0} webapps plugged in to the HTTP proxy at {1}:{2}**

**Cause:** Indicates the webapps using the HTTP proxy.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00132: Found webapp: {0}**

**Cause:** Indicates the webapp that is under the HTTP proxy.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00133: Web application type: {0}**

**Cause:** Indicates the type of a webapp found while scanning the EPM Registry for products.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00134: This is the web application for EPM Workspace.**

**Cause:** Indicates that a webapp discovered during a registry scan is EPM Workspace.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00135: Checking for Workspace configuration file(s)**

**Cause:** Indicates if Workspace configuration file(s) were found.

**Action:** No action is required.

**Level:** 32

---

**Type:** ERROR

**Impact:**

**EPMWKSP-00136: Checking for configuration file named: {0}**

**Cause:** Indicates the specific configuration file being located.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00137: Found configuration file.**

**Cause:** Indicates that the configuration file is found and accessible.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00138: ERROR: configuration file does not declare sharedServicesId.  
Product cannot be identified or loaded from product file.**

**Cause:** The configuration file does not contain a node with sharedServicesId as an attribute.

**Action:** Verify that the product file being loaded is valid and has shreadServicesId declared.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00139: Loaded product with name {0}**

**Cause:** Indicates the product was successfully loaded.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00140: Static file configuration matches version {0}; discarding registry file.**

**Cause:** Indicates that Workspace's Product file has a configuration which matches a configuration in the registry and the configuration found in the Workspace's Product file will be used.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00141: Product not in static configuration file, initializing.**

---

**Cause:** Indicates that a product's configuration information is being loaded from the registry.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00142: Static file configuration is for version(s): {0} but registered product version is {1}**

**Cause:** Indicates that there is a different version of a configuration for the same registered product specified in Workspace's product file.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00143: Discarding static configuration.**

**Cause:** Indicates that the product configuration from the registry will be used instead of the one found in Workspace's product file.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00144: NOTE: Product version for display is {0}**

**Cause:** Indicates the product version to display in the Help->About.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00145: Skipping integration for this product.**

**Cause:** The version for the product failed the version test.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00146: Product file configuration matches version {0}**

**Cause:** Allow integration of product since it passes the version test.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

---

**EPMWKSP-00147: NOTE: Product version for display is {0}**

**Cause:** The product version was found in the product configuration information.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00148: Skipping integration for this product.**

**Cause:** The product configuration information could not be found in registry or in the Workspace's product file.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00149: Product not in static configuration file. Initializing product.**

**Cause:** The product's configuration information was found in the registry but not in the Workspace's product file. Product will be configured with information from the registry.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00150: Product file configuration matches version {0}**

**Cause:** Indicate the supported version.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00151: Product file configuration is for version(s): {0} but registered product version is {1}**

**Cause:** Versions between product file configuration version and registered product version are mismatched.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00152: Discarding old configuration.**

**Cause:** A more recent configuration was found and used.

**Action:** No action is required.

**Level:** 32

---

Type: ERROR

Impact:

**EPMWKSP-00153: Setting product to use external configuration.**

**Cause:** Indicates that a product does not have a configuration loaded from Workspace's static configuration files, and that the product configuration will be loaded from the EPM Registry.

**Action:** No action is required.

Level: 32

Type: ERROR

Impact:

**EPMWKSP-00154: NOTE: Product version for display is {0}**

**Cause:** Indicates the product version that is displayed in Workspace.

**Action:** No action is required.

Level: 32

Type:

Impact:

**EPMWKSP-00155: Product {0}-{1} was not registered. Deactivating product.**

**Cause:** The product may be not supported with the current Workspace version.

**Action:** No action is required.

Level: 32

Type: ERROR

Impact:

**EPMWKSP-00156: Product {0} has been explicitly disabled. Deactivating product.**

**Cause:** The products configuration has specified the disabled attribute.

**Action:** No action is required.

Level: 32

Type: ERROR

Impact:

**EPMWKSP-00157: Product {0} was forcibly enabled and set at version {1}, but the internal configuration is valid for versions {2}.**

**Cause:** The products configuration has the forceEnabled attribute set but the versions set may not be compatible with the current Workspace version.

**Action:** No action is required.

Level: 32

Type: ERROR

Impact:

**EPMWKSP-00159: Setting product to use external configuration.**

**Cause:** Indicates that a product does not have a configuration loaded from Workspace's static configuration files, and that the product configuration will be loaded from the EPM Registry.

---

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00162: There was an error building the sorted product list.**

**Cause:** Workspace was unable to determine the correct order in which to display integrated products.

**Action:** Consult Workspace logs for preceeding error messages. This is likely a consequence of prior errors while scanning the registry.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00163: There was an error refreshing display version for product {0} {1}.**

**Cause:** Workspace could not determine a version number for a product.

**Action:** This error is not fatal, but product version numbers will be incorrect. Consult Workspace configuration log for further error messages.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00164: Read {0} bytes from the registry.**

**Cause:** Indicates the number of bytes of data successfully processed from the registry.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00165: Missing product context {0}**

**Cause:** The products context configuration information may be missing or invalid.

**Action:** Verify the products registration file is valid or run the config tool.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00166: Found and loaded context for {0}**

**Cause:** A product's context was successfully loaded.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00167: Could not find product context for {0}. This product will not load.**

---

**Cause:** A product's context could not be loaded.

**Action:** Verify the products configuration has a valid context configuration or run the config tool.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00168: Failed to parse HSS response for product {0}**

**Cause:** The response may contain an invalid content type or the xml may be invalid.

**Action:** Verify the response is xml content type and that the xml is valid.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00169: Failed to connect and retrieve info for product {0}**

**Cause:** The product's webapp may not be started, the url to the config xml may be invalid or the config xml is returning an invalid response.

**Action:** Verify the product's webapp is running, is properly configured and is returning a valid response.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00170: Failed to connect and retrieve info for product {0}**

**Cause:** The product's webapp may not be started, the url to the config xml may be invalid or the config xml is returning an invalid response.

**Action:** Verify the product's webapp is running, is properly configured and is returning a valid response.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00171: Product file reports the following parse problems.**

**Cause:** The xml is invalid and cannot be parsed.

**Action:** Try to resolve the reported parse problems.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00172: Workspace may not function properly unless these are fixed:{0}  
{1}**

**Cause:** The xml could not be parsed.

**Action:** Try to resolve the reported issues.

**Level:** 32



---

Type: ERROR

Impact:

**EPMWKSP-00173: End of warning messages.**

Cause: Indicates the end of the warning messages that needs attention.

Action: No action is required.

Level: 32

Type: ERROR

Impact:

**EPMWKSP-00174: Product file parsed without errors.**

Cause: Indicates the product file was valid.

Action: No action is required.

Level: 32

Type: ERROR

Impact:

**EPMWKSP-00175: Checking HSS with product code {0}**

Cause: Information is being retrieved from HSS for this product.

Action: No action is required.

Level: 32

Type: ERROR

Impact:

**EPMWKSP-00176: Recovered {0} bytes from HSS.**

Cause: The query to HSS was successful.

Action: No action is required.

Level: 32

Type: ERROR

Impact:

**EPMWKSP-00177: Failed to recover configuration from HSS.**

Cause: Information on this product could not be retrieved from HSS.

Action: Verify HSS connection is valid and the product is properly configured.

Level: 32

Type: ERROR

Impact:

**EPMWKSP-00178: There was an error loading default registry properties.**

Cause: File was not found or could not be accessed.

Action: Verify file exists and is accessible.

Level: 32

Type: ERROR

Impact:

---

**EPMWKSP-00179: Parsing product file: {0}**

**Cause:** Product file is parsed.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00180: Looking for Workspace Web Server (child of Workspace product with type: {0})**

**Cause:** Indicates the Workspace Web Server.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00181: Found {0} HTTP proxy instance(s).**

**Cause:** Indicates the number of HTTP proxy instances discovered when scanning the EPM Registry.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00182: File not found. Ending search.**

**Cause:** Indicates that a product did not have a Workspace configuration file in the EPM Registry.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00183: EPM System Common Install Version: {0}**

**Cause:** Indicates the version of the Common Installer.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00184: Checking product version numbers:**

**Cause:** Product versions numbers must be compatible.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

---

**EPMWKSP-00185: Version number mismatch between the Workspace and BPMUI components detected. All version numbers must be at the same patchset level (first four parts of the the version number).**

**Cause:** Workspace and BPMUI versions are mismatched.

**Action:** Locate a patch that is compatible with the current version.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00186: All versions are at the same patchset level.**

**Cause:** System was patched correctly.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00187: Version number check skipped due to missing version numbers.**

**Cause:** The version number was not specified in the configuration information.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00188: Checking Registry version numbers:**

**Cause:** Indicate the current registry version numbers.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00189: Compiled against Registry version: {0}**

**Cause:** Indicates the version of the EPM Registry API against which Workspace was compiled.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00190: WORKSPACE component version: {0}**

**Cause:** Indicates the Workspace build number.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

---

**EPMWKSP-00191: LOGICAL\_WEB\_APP component version: {0}**

**Cause:** Indicates the component version of Workspace's Logical Webapp component in the EPM Registry.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00192: WEB\_SERVER component version: {0}**

**Cause:** Indicates the component version of Workspace's Web Server component in the EPM Registry.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00193: Version number mismatch between the Workspace and registry components detected. All version numbers must be at the same release level (first three parts of the the version number).**

**Cause:** Workspace and registry components are not on the same release level.

**Action:** Install and configure the matching Workspace and registry components.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00194: All version numbers are at the same release level.**

**Cause:** Version numbers are from the same release.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00195: WARNING: Product registry version does not match Workspace registry version. Skipping integration for this product.**

**Cause:** Product failed the version test.

**Action:** No action is required as it may be the product configuration is left over from an upgrade.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00196: Product {0} has at least one string bundle that is not statically loaded. Deactivating product.**

**Cause:** The product's webapp is not running or the files are not there.

**Action:** No action is required.

---

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00197: BPMUI Java: {0}**

**Cause:** Reports the version number of the BPMUI Java library.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00198: BPMUI Web: {0}**

**Cause:** Reports the version number of the BPMUI shared web application.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00199: Workspace Java: {0}**

**Cause:** Reports the version number of the Workspace Java library.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00201: Property "{0}" is not in the Registry. Default value is used.**

**Cause:** Mentioned property is absent in the Registry.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00202: Message cache was cleared by admin request.**

**Cause:** Admin user has changed server settings related to messaging system.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00203: Message cache expired. The message will be reread from the Registry.**

**Cause:** Time of cache expiration has passed

**Action:** No action is required.

**Level:** 32

---

Type: ERROR

Impact:

**EPMWKSP-00204: Empty message is stored in the Registry.**

Cause: No message is stored in the Registry.

Action: No action is required.

Level: 32

Type: ERROR

Impact:

**EPMWKSP-00205: Can't find the file with name "{0}" in the Registry.**

Cause: No message is stored in the Registry.

Action: No action is required.

Level: 32

Type: ERROR

Impact:

**EPMWKSP-00206: There was an error reading message from the Registry.**

Cause: Unexpected error occurred during reading message from the Registry.

Action: Verify HSS connection.

Level: 32

Type: ERROR

Impact:

**EPMWKSP-00301: Product "{0}" has been excluded from the list of SmartView providers.**

Cause: Product is in list of excluded products.

Action: No action is required.

Level: 32

Type: ERROR

Impact:

**EPMWKSP-00302: There was an error loading the list of products excluded from the list of SmartView providers.**

Cause: The file with list of excluded products is corrupted or absent.

Action: Verify the file with list of excluded products.

Level: 32

Type: ERROR

Impact:

**EPMWKSP-00401: Error getting Workspace configuration instance.**

Cause: System is not properly initialized.

Action: Verify system is properly initialized.

Level: 32

---

**Type:** ERROR

**Impact:**

**EPMWKSP-00402: There was an error during authentication.**

**Cause:** User has entered wrong credentials.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00403: No credentials provided in the SmartView request.**

**Cause:** User has not entered credentials.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00404: There was an error during processing:**

**Cause:** Unexpected error occurred.

**Action:** Verify system is properly initialized.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00405: There was an error parsing the request.**

**Cause:** Invalid request was sent

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00406: There was an error building handshake response.**

**Cause:** Unexpected error occurred.

**Action:** Check log details and verify that system is properly initialized.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00408: There was an error building response.**

**Cause:** Unexpected error occurred.

**Action:** Check log details and verify that system is properly initialized.

**Level:** 32

**Type:** ERROR

**Impact:**

---

**EPMWKSP-00507: There was an error determining the instanced product list.**

**Cause:** Workspace was unable to determine the list of products that use per-instance provisioning.

**Action:** This is usually caused by an error when loading product configuration info. Check the Workspace configuration logs for other errors.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00508: There was an error determining the provisioned application list.**

**Cause:** Workspace was unable to determine the list of applications for which the current user is provisioned.

**Action:** Check the Workspace security log for detailed errors from the security API.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00509: There was an error fetching an application registration**

**Cause:** Workspace cannot fetch an application registration from Hyperion Shared Services and/or the EPM Registry.

**Action:** The Workspace configuration or security logs will contain further errors. Verify the registration of the product and application in Hyperion Shared Services.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00510: Fetching registration for product {0} application {1}**

**Cause:** Indicates the product registration for an application is being retrieved.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00511: Fetched {0} bytes from HSS.**

**Cause:** Indicates that the product registration information for an application has been retrieved from HSS successfully.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00512: Parsing the instance file caused the following warnings:**

**Cause:** Indicates a list of warnings generated when parsing the application's registration file.



---

**Action:** These issues may cause the application to not function properly in Workspace. Verify the product registration in Shared Services.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00513: Instance may not function properly unless these are fixed:{0}{1}**

**Cause:** Indicates a list of warnings generated when parsing the application's registration file.

**Action:** These issues may cause the application to not function properly in Workspace. Verify the product registration in Shared Services.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00514: End of warning messages.**

**Cause:** Indicates all the warning messages has been listed.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00515: Instance file parsed without errors.**

**Cause:** An application instance file was successfully processed by Workspace.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00601: Log on failed: error while checking user roles.**

**Cause:** The user attempting to log on does not have the necessary role requirements for log on.

**Action:** Verify the user is properly provisioned to log on.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00602: Log on failed: error while checking user preferences.**

**Cause:** The user preferences repository could not be accessed.

**Action:** Verify the connection to the user preferences repository is valid.

**Level:** 32

**Type:** ERROR

**Impact:**

---

**EPMWKSP-00603: There was an error while creating the Reporting and Analysis security token.**

**Cause:** Workspace could not obtain a Reporting and Analysis security token.

**Action:** Verify the Reporting and Analysis webapp and services is running.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00604: There was an error determining user accessibility settings.**

**Cause:** Obtaining accessibility mode setting from request parameter, CSS Session (Fusion), User Preference (EPM) or extant cookie may have failed.

**Action:** Verify accessibility mode settings is valid and in request parameter, CSS Session (Fusion), User Preference (EPM) or extant cookie.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00605: There was an error determining user theme settings.**

**Cause:** Obtaining theme settings from request parameter, CSS Session (Fusion), User Preference (EPM) or extant cookie may have failed.

**Action:** Verify theme settings is valid and in request parameter, CSS Session (Fusion), User Preference (EPM) or extant cookie.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00606: There was an error determining user locale settings.**

**Cause:** There was an error obtaining the locale from the CSS session or request parameter.

**Action:** Verify the local is valid and in the CSS session or request parameter.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-00607: There was an error validating user theme selection.**

**Cause:** The theme selection does not match one of the supported themes.

**Action:** Verify the user theme selection is one of the supported themes.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01301: Could not resolve role: {0}**

**Cause:** Workspace was unable to verify the existence of the named role.

**Action:** Verify the user provisioning and product registration in Shared Services. The named role will not be used by Workspace.

---

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01302: Exception while checking user roles**

**Cause:** Workspace was unable to check a user's provisioned roles.

**Action:** Check the Workspace security log for further errors from the security API

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01401: There was an error while parsing {0}**

**Cause:** Workspace was unable to parse its own role definition file.

**Action:** Verify that the Workspace deployment has not been corrupted. Contact technical support for further guidance.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01402: Mapping role name {0} to role ID {1}**

**Cause:** Indicates that a role has been successfully matched to a Shared Services LDAP ID or a Reporting and Analysis GUID.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01501: Searching for users matching '{0}' as user {1}**

**Cause:** Indicates a search request for users conducted by an administrator.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01502: Found {0} result(s).**

**Cause:** Indicates the number of users found by an administrative search for users.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01503: Invalid user/group search filter '{0}' specified.**

**Cause:** Indicates that an administrative search for users included an invalid search specification.

---

**Action:** Use a valid search string. Search strings for user names are Unicode alphabet character strings preceded or followed with '\*' as a wildcard.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01601: The value for parameter "{0}" was invalid.**

**Cause:** Specified parameter's value is invalid.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01602: Validating parameter "{0}" with value "{1}".**

**Cause:** Parameter is being validated

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01603: Loading list of supported locales from default configuration.**

**Cause:** Default list of supported locales is loaded

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01604: There was an error loading default list of supported locales.**

**Cause:** System is not properly initialized.

**Action:** Verify system is properly initialized.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01701: There was an error evaluating product-level Constraints for {0}.  
Deactivating product.**

**Cause:** There was an issue with one of the product-level constraints.

**Action:** Verify the product-level constraints are valid.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01702: There was an error generating product path**

**Cause:** The direct-access URL, non-proxied path to the product could not be obtained.

---

**Action:** Verify the product's webapp is running and correctly configured.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01801: Redirecting From Url: {0}**

**Cause:** This is the URL before the redirect.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01802: Redirecting To Url: {0}**

**Cause:** This is the URL after the redirect.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01803: Get Logical WebApp Info.**

**Cause:** This is the information retrieved on the logical webapp.

**Action:** Registration may have failed. Try re-registering the products by running the configuration tool.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01804: Get Logical WebApp Info for workspace failed, using default.**

**Cause:** The logical webapp information for Workspace could not be retrieved. Assuming the context is /workspace.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01805: Current Context Path: {0}**

**Cause:** Indicates the current context path before the redirect.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01806: Redirect Context Path: //{0}**

**Cause:** Indicates the context path after the redirect.

---

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01807: Form Post Redirect**

**Cause:** Indicates that redirect was handled by performing a form post.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01808: Send Redirect with Cookie {0}: {1}**

**Cause:** Indicates the redirect was handled by a send redirect. Cookies are included in the redirect.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01809: The servlet failed, invalid token or url.**

**Cause:** Indicates the URL or token may be invalide which caused the redirect to fail.

**Action:** Verify the URL is valid and user is properly provisioned.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01810: The servlet failed, bad redirect url or token: {0}**

**Cause:** User is not authenticated.

**Action:** Verify the user is properly provisioned.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01811: Processed {0} urls to redirect using form post.**

**Cause:** Indicates the URLs that must be redirected using a form post.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01812: The servlet failed to initialize the form post list: {0}**

**Cause:** An error was encountered while attempting to retrieve information on the URLs.

---

**Action:** Verify in the web.xml under the redirect servlet node that the entries for FormPostList are valid.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01813: Processed {0} parameters to omit from redirect.**

**Cause:** Indicates the number of parameters that were found and should be omitted from the redirect.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01814: The servlet failed to initialize the param omit list: {0}**

**Cause:** An error was encountered while attempting to retrieve the list of parameters to omit from the redirect.

**Action:** Verify in the web.xml under the redirect servlet node that the entries for ParamOmitList are valid.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01815: isFormPostUrl: {0} in {1} {2}**

**Cause:** Indicates if the current URL should be redirected with a form post.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01816: isParamOmit: {0}**

**Cause:** Indicates if the current parameter should be omitted from the redirect.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01901: The "{0}" persistence unit is already open**

**Cause:** Indicates that while attempting to initialize the persistence, a previous attempt to terminate failed.

**Action:** This unexpected state should be reported, although the code will continue on and not attempt to initialize the persistence.

**Level:** 32

**Type:** ERROR

---

**Impact:**

**EPMWKSP-01902: Initializing persistence with the connection configured in "{0}"**

**Cause:** Indicates that an attempt is being made to initialize the persistence with the connection information in the specified file.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01903: Loading the "{0}" persistence unit**

**Cause:** Indicates that an attempt is being made to load the specified persistence unit.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01904: Unloading the "{0}" persistence unit**

**Cause:** Indicates that an attempt is being made to unload the specified persistence unit.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01905: The "{0}" persistence unit is not open**

**Cause:** Indicates that while attempting to terminate the persistence, a previous attempt to initialize failed.

**Action:** This unexpected state should be reported, although the code will continue on and not attempt to terminate the persistence.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01906: Started the migration**

**Cause:** Indicates that the migration has started.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01907: Ended the migration**

**Cause:** Indicates that the migration has ended.

**Action:** No action is required.



---

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01908: Started the migration initialization**

**Cause:** Indicates that the migration initialization has started.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01909: Ended the migration initialization**

**Cause:** Indicates that the migration initialization has ended.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01910: Started the migration termination**

**Cause:** Indicates that the migration termination has started.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01911: Ended the migration termination**

**Cause:** Indicates that the migration termination has ended.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01912: Started the migration to Talleyrand**

**Cause:** Indicates that the migration to the Talleyrand release has started.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01913: Couldn't find the user with identity "{0}"**

**Cause:** Indicates that the identity of an existing user could not be located in the security system.

**Action:** The specified identity should be recorded to see why they are no longer in the security system (such as leaving the company, or a name change that affects the identity).

---

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01914: User={0}, Properties={1}**

**Cause:** Indicates a user and their properties that are being migrated

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01915: Ended the migration to Talleyrand**

**Cause:** Indicates that the migration to the Talleyrand release has ended.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01916: Started the connection acquisition for component type "{0}"**

**Cause:** Indicates that the connection acquisition for the specified component type has started.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01917: JdbcDriver={0}**

**Cause:** Indicates the JDBC driver that is being used for the connection acquisition.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01918: JdbcUrl={0}**

**Cause:** Indicates the JDBC URL that is being used for the connection acquisition.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01919: JdbcUserName={0}**

**Cause:** Indicates the JDBC username that is being used for the connection acquisition.

**Action:** No action is required.

---

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01920: JdbcPassword={0}**

**Cause:** Indicates the JDBC password that is being used for the connection acquisition.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01921: JdbcDataSourceName={0}**

**Cause:** Indicates the JDBC data source name that is being used for the connection acquisition.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01922: JndiName={0}**

**Cause:** Indicates the JNDI name that is being used for the connection acquisition.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-01923: Ended the connection acquisition for component type "{0}"**

**Cause:** Indicates that the connection acquisition for the specified component type has started.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02101: An empty search term was passed into Dynamic Help. The client search pages filter for this, so the submission may be from a source other than the search form.**

**Cause:** An empty search term was passed in.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02102: No topics matched the search criteria.**

---

**Cause:** Indicates that no topics matched the user's search criteria.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02103: Exact phrase search - add quotes to set term string as {0}**

**Cause:** Indicates the user specified an exact phrase search.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02104: query string: {0}**

**Cause:** Logs the search query string.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02105: parsed query: {0}**

**Cause:** Logs the parsed query.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02106: Dynamic Help could not create the Lucene query parser:**

**Cause:** Unknown cause.

**Action:** Verify that the Lucene search engine .jars are available.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02107: Version number not returned from Workspace. The path to the Lucene index thus cannot be resolved for module: {0}**

**Cause:** Could not obtain the product's version number from the Workspace Registry for an unknown reason.

**Action:** Try the search again. If the same issue occurs, validate that the product is correctly registered with Workspace.

**Level:** 32

**Type:** ERROR

**Impact:**

---

**EPMWKSP-02108: adding Lucene index path {0}**

**Cause:** Logging the search engine index location for the product.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02109: The Lucene index for the {0} module was not found in {1}**

**Cause:** The search engine index for the product and locale may be missing, or the EPM\_ORACLE\_HOME system variable may not be properly set.

**Action:** If the logged index path begins with null, the EPM\_ORACLE\_HOME system variable is not set; if so, set it. Otherwise, check whether the search index for the product and locale is installed in the specified location.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02110: The Lucene search index could not be found, so no search was conducted.**

**Cause:** No search engine indices were found.

**Action:** Check whether the search index for the product and locale is installed in the specified location. Also, make sure the EPM\_ORACLE\_HOME system variable is correctly set.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02111: parsed CJK query: {0}**

**Cause:** Logging the parsed query for an Asian locale.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02112: Dynamic Help could not create the Lucene CJK query parser:**

**Cause:** Unknown cause.

**Action:** Verify that the Lucene search engine .jars are available.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02113: I18N QueryFilter: {0}**

**Cause:** Logging the query filter for an Asian locale.

**Action:** No action is required.

**Level:** 32

---

**Type:** ERROR

**Impact:**

**EPMWKSP-02114: internationalized query: {0}**

**Cause:** Logging the query for searches on multiple locales.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02115: Dynamic Help could not execute search**

**Cause:** Search cannot be executed for an unknown reason.

**Action:** Try searching again. If the same issue occurs, a component help depends upon may be mis-configured or unavailable.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02201: Error in setting tools context ID data.**

**Cause:** Could not obtain data from the Workspace Registry for the Reporting and Analysis Framework products' help.

**Action:** Validate that the Registry entries for the Reporting and Analysis Framework products are correctly defined.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02202: Error in setting IR help path.**

**Cause:** Unknown cause.

**Action:** Make sure that the Workspace Registry Dynamic Help entries for the tools context are correctly defined.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02203: Error in setting SQR help path.**

**Cause:** Unknown cause.

**Action:** Make sure that the Workspace Registry Dynamic Help entries for the tools context are correctly defined.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02204: Error in adding IR help paths:**

**Cause:** Unknown cause.

---

**Action:** Make sure that the Workspace Registry Dynamic Help entries for the tools context are correctly defined.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02205: Error in adding SQR help paths:**

**Cause:** Unknown cause.

**Action:** Make sure that the Workspace Registry Dynamic Help entries for the tools context are correctly defined.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02206: Error in adding IR launch pages:**

**Cause:** Unknown cause.

**Action:** No action is required; minor issue.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02207: Error in adding SQR launch pages:**

**Cause:** Unknown cause.

**Action:** No action is required; minor issue.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02208: Workspace Registry returned no name for the product code {0}.  
Dynamic Help will display the product code as a fallback.**

**Cause:** The product's displayName Workspace Registry attribute may not be set.

**Action:** Set the displayName attribute.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02301: UPK URL is an empty string.**

**Cause:** The UPK URI obtained from Workspace is an empty string.

**Action:** Make sure that a valid UPK URI is set in the Workspace Server Settings dialog.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02302: UPK URL is null.**

---

**Cause:** Workspace is indicating that UPK should be displayed, but the UPK URI value is not available.

**Action:** Make sure that a valid UPK URI is set in the Workspace Server Settings dialog.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02303: Exception trying to redirect to UPK:**

**Cause:** For an unknown reason, an error occurred when forwarding to UPK.

**Action:** Verify that a valid UPK URI is set in the Workspace Server Settings dialog, then try accessing UPK again. If that does not work, as a workaround try accessing UPK through the UPK toolbar icon in help.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02401: Error testing for string in array:**

**Cause:** Unknown cause.

**Action:** If help is not displaying in the correct locale, try accessing help again.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02501: There was an error getting version number for module {0}.**

**Cause:** Could not obtain the product's version number from the Workspace Registry.

**Action:** Validate the product's Workspace Registry entry.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02502: There was an error in getting the product name for product {0}.**

**Cause:** An Exception occurred for unknown reasons when help tried to obtain a product name from the Workspace Registry.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02503: The help system path is: {0}**

**Cause:** Logging the path to the help system.

**Action:** No action is required.

**Level:** 32



---

**Type:** ERROR

**Impact:**

**EPMWKSP-02504:** There was an error setting the help system path for module: {0}  
guide: {1} locale: {2}

**Cause:** Unknown cause.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02505:** There was an error retrieving registered Workspace products.

**Cause:** Unknown cause.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02506:** Dynamic help could not create array of products and guides.

**Cause:** Unknown cause.

**Action:** Validate that the products' Workspace Registry entries are correctly defined.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02507:** There was an error getting the launch page.

**Cause:** Unknown cause.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**

**EPMWKSP-02508:** There was an error getting the language for the help guide. Using English.

**Cause:** Unknown cause.

**Action:** No action is required.

**Level:** 32

**Type:** ERROR

**Impact:**



---

**ESS-00001 to ESS-09405****ESS-00001: Internal error. {0}**

**Cause:** Internal error occurred.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-00002: Constraint error for property {0} with value {1}.**

**Cause:** An attempt was made to change the value of an object that is read-only.

**Action:** Retry the operation without changing the value of the object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-00003: Failed to find resource {0}. {1}**

**Cause:** A JNDI lookup of the given resource failed.

**Action:** Ensure the resource is deployed properly and is available via jndi lookup.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-00004: Incorrect timestamp format: {0}. {1}**

**Cause:** An invalid value was specified for a timestamp.

**Action:** Specify a correct value for the parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-00005: SQL bind operation not supported for parameter data type: {0}**

**Cause:** A value being used for an SQL bind parameter has a data type that is not suitable for the SQL Statement.

**Action:** Specify a parameter value having an appropriate data type.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-00006: Enterprise Scheduler configuration is not initialized.**

**Cause:** An operation attempted to access Enterprise Scheduler configuration information before the configuration was initialized.

**Action:** Re-try the operation at a later time.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-00007: Operation intended for group, {0}. Configured group is {1}.**

**Cause:** An Enterprise Scheduler instance received an event, message, or other data that was intended for an instance of a different group.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-00100: Install plan is not present for application {0}.**

**Cause:** The install plan is not present for the application being deployed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**ESS-00101: Global data source, {0}, could not be created.**

**Cause:** The global data source could not be created.

**Action:** Check the underlying cause for details.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**ESS-00102: Dependent component, {0}, has not been deployed.**

**Cause:** A dependent component of this component has not been deployed. An error may have occurred when deploying dependent component.

**Action:** Check log for errors in deploying dependent component.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**ESS-00103: Error finding application {0}.**

**Cause:** An error occurred while attempting to find the specified application.

**Action:** Perform the action specified in the chained exception.

---

**Level:** 1

**Type:** WARNING

**Impact:** Installation

**ESS-00120: Invalid value for dispatcher poll interval.**

**Cause:** Attempted to configure an invalid value for the dispatcher minimum or maximum poll interval.

**Action:** Retry the operation with a non-negative numeric value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-00121: Dispatcher poll interval minimum value cannot exceed maximum value.**

**Cause:** Attempted to configure a value for the dispatcher maximum poll interval that is less than the minimum value.

**Action:** Retry the operation with a value that is equal to or greater than the minimum value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-00122: Invalid value for processor threads.**

**Cause:** Attempted to configure an invalid value for the processor maximum threads.

**Action:** Retry the operation with a non-negative numeric value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-00123: Invalid value for processor starvation threshold.**

**Cause:** Attempted to configure an invalid value for the processor starvation threshold.

**Action:** Retry the operation with a non-negative numeric value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-00124: Unable to validate metadata for work assignment {0}.**

**Cause:** Attempted to add or remove bindings for an work assignment.

**Action:** Retry the operation with a valid work assignment name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-00300: Invalid value ({0}) for {1} argument.**

---

**Cause:** The value specified for an argument is not valid.

**Action:** Retry the operation using a valid value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-00301: TopologyNodeType, {0}, is not supported for this operation.**

**Cause:** The operation is not supported on the specified topology node type.

**Action:** Retry the operation on OC4JComponent or Group.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-00310: Work assignment, {0}, already exists.**

**Cause:** Attempted an operation using a work assignment that already exists.

**Action:** Retry the operation with an assignment that does not exist.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-00311: Work assignment, {0}, does not exist.**

**Cause:** Attempted an operation using a work assignment that does not exist.

**Action:** Retry the operation with an assignment that exists.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-00312: Group, {0}, does not exist.**

**Cause:** Attempted an operation using a group that does not exist.

**Action:** Retry the operation with a group that exists.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-00313: Failed to read the configuration document.**

**Cause:** Failed to read the configuration document.

**Action:** Check the underlying cause for details.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-00314: Failed to write the configuration document.**

**Cause:** Failed to write the configuration document.

**Action:** Check the underlying cause for details.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-00315: Invalid Wait Queue polling interval; minimum ({0}) > maximum ({1}).**

**Cause:** Invalid Wait Queue polling interval.

**Action:** Provide a valid polling interval.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-00316: Invalid minimum Wait Queue polling interval ({0}).**

**Cause:** Invalid minimum Wait Queue polling interval.

**Action:** Provide a valid polling interval.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-00317: Invalid maximum Wait Queue polling interval ({0}).**

**Cause:** Invalid maximum Wait Queue polling interval.

**Action:** Provide a valid polling interval.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-00318: Invalid threshold ({0}) for processing low priority jobs.**

**Cause:** Threshold is invalid.

**Action:** Correct the threshold value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-00319: Invalid value ({0}) for threads to be available for request processing.**

**Cause:** Threads used for request processing are invalid.

**Action:** Call Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-00400: Insufficient information to execute the command.**

**Cause:** A valid command was specified but the supplied information was not adequate to execute the command, possibly due to missing command switches or keywords.

**Action:** Review the help and syntax for the command. Retry the operation with additional information.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-00401: Error attempting to execute the "{0}" operation. {1}**

**Cause:** Encountered an error while trying to execute the specified operation.

**Action:** Review the error information to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-00402: Invalid work assignment mode ({0}).**

**Cause:** Value specified for a work assignment mode is not valid.

**Action:** Retry the operation with a valid value; "primary" or "secondary".

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-00403: Work assignment is required.**

**Cause:** A work assignment is required for the operation but none was specified.

**Action:** Retry the operation with at least one work assignment.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-00404: Invalid topoNode "{0}".**

**Cause:** Invalid topoNode

**Action:** Provide a valid topoNode value and make sure the Config MBean is registered with ESSAPP

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-00405: The Config MBean "{0}" is not registered with the ESSAPP.**

**Cause:** Config MBean is not registered with the ESSAPP

**Action:** Make sure the Config MBean is registered with ESSAPP and then retry

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-00500: Failed to create metadata service handle.**

**Cause:** An error occurred while starting a Metadata session.

**Action:** See the base exception for details.

**Level:** 1



---

**Type:** WARNING

**Impact:** Other

**ESS-00501: Failed to close metadata service handle.**

**Cause:** An error occurred while closing a Metadata session.

**Action:** See the base exception for details.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01000: Failed to open runtime service. {0}**

**Cause:** An error occurred opening the RuntimeService handle

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01001: Failed to close runtime service handle. {0}**

**Cause:** An error occurred closing the RuntimeService handle

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01002: Illegal attempt to validate request, {0}, when current state, {1}, is not PENDING\_VALIDATION.**

**Cause:** A request is in an illegal state for validation.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01003: Illegal operation for an unvalidated request {0}.**

**Cause:** The operation is not supported for an unvalidated request.

**Action:** Do not attempt this operation unless the request is validated.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01004: Illegal attempt to set state of request, {0}, to VALIDATION\_FAILED when current state, {1}, is not PENDING\_VALIDATION.**

**Cause:** An internal error occurred.

**Action:** None

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01005: Parameter {0} does not exist for request {1}.**

**Cause:** The given parameter name does not exist for this request.

**Action:** Specify an existing parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01006: RuntimeServiceHandle is marked for rollback only.**

**Cause:** The ESS runtime service handle has been marked for rollback only.

**Action:** Close the ESS runtime service session. Another session may be created for further operations.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01007: RuntimeServiceHandle is null.**

**Cause:** The ESS runtime service handle is null.

**Action:** Specify a valid ESS runtime service handle.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01008: Value for parameter, {0}, has an invalid data type: {1}.**

**Cause:** The value for a parameter has an unsupported data type.

**Action:** Specify a value which has a supported data type for the parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01009: Value for parameter, {0}, is not valid.**

**Cause:** The value for a parameter is not valid.

**Action:** Specify a valid value for the parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01010: Value for parameter, {0}, must not be null.**

**Cause:** The given parameter does not support a null value, or empty string for string parameter.

**Action:** Specify a non-null value for the parameter.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01011: Parameter, {0}, is required but was not specified.**

**Cause:** The given parameter is required but was not specified.

**Action:** Specify the required parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01012: Request {0} not found.**

**Cause:** A request that was the target of a RuntimeService operation was not found in the runtime store.

**Action:** Specify a valid request identifier.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01013: Failed to lock request {0}. Request not found.**

**Cause:** Attempted to lock a request that was not found in the runtime store.

**Action:** Specify a valid request identifier.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01014: Error occurred attempting to lock request {0}.**

**Cause:** An error occurred attempting to lock a request in the runtime store.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01015: Failed to generate a request identifier.**

**Cause:** An error occurred attempting to generate a new request identifier.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01016: Failed to generate a request handle.**

**Cause:** An error occurred attempting to generate a new request handle.

---

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01017: Error attempting to access information for request {0}.**

**Cause:** An error occurred attempting to access information for a request.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01018: Error attempting to update information for request {0}.**

**Cause:** An error occurred attempting to update information for a request.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01019: Request {0} is not in {1} state. Current state is {2}.**

**Cause:** An operation was attempted when the request was not in an expected state.

**Action:** Retry the operation when the request is the correct state.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01022: Error occurred retrieving summary data. {0}**

**Cause:** An error occurred attempting to retrieve request or application summary information.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01023: Parameter {0} for request {1} is read-only.**

**Cause:** Attempted to modify the value for a request parameter that is read-only.

**Action:** None

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**ESS-01024: This operation is illegal for this request. {0}**  
**Cause:** The invoked operation is not legal for this request.  
**Action:** None  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic

**ESS-01025: The request does not have a schedule. {0}**  
**Cause:** This operation can only be applied to a request with a schedule.  
**Action:** None  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic

**ESS-01026: Schedule for request {0} cannot be changed when in state {1}**  
**Cause:** The schedule for this request cannot be replaced in the current state.  
**Action:** None  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic

**ESS-01027: Failed to convert schedule to string**  
**Cause:** The schedule cannot be converted to a string.  
**Action:** None  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic

**ESS-01028: Request submission or validation failed. {0}**  
**Cause:** An error occurred during request submission or validation.  
**Action:** None  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic

**ESS-01029: Failed to create child request for parent request {0}.**  
**Cause:** An error occurred while attempting to create a child request for a parent that was submitted with a Schedule or Trigger.  
**Action:** None  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic

---

**ESS-01030: Failed to create JobSet step request for parent request {0}, step {1}.**

**Cause:** An error occurred while attempting to create a request for a JobSet step.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01031: Application {0} was not found.**

**Cause:** Attempted to submit a request for an application associated with a logical name but no such application was found.

**Action:** Deploy the application

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01032: Application {0} was found in more than one process group.**

**Cause:** Attempted to submit a request for an application that is deployed to multiple process groups. Unable to determine correct group to use.

**Action:** Application should be deployed to only one group.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01033: Application {0} was not found for process group {1}.**

**Cause:** Attempted to submit a request for an application that is deployed to multiple process groups. Unable to determine correct group to use.

**Action:** Application should be deployed to only one group.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01034: Unable to determine the deployed application name for logical application {0}.**

**Cause:** Unable to determine the name of the deployed application for the specified logical name.

**Action:** Check for deployment errors.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01035: Unable to determine a logical application name for new request.**

**Cause:** Unable to determine the logical application that should be used for a submitted request.

**Action:** Specify a value for the SystemProperty.EFFECTIVE\_APPLICATION parameter in the metadata for the JobDefinition or JobSet.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01036: Unable to determine a process group for new request.**

**Cause:** Unable to determine the process group that should be used for a submitted request.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01037: Job definition is required for a non-Adhoc request submission.**

**Cause:** A submit operation was attempted for a non-adhoc job but no metadata id for a JobDefinition or JobSet was given.

**Action:** Retry the submit operation and specify a job definition.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01038: Read-Only violation for request parameter {0}.**

**Cause:** The given parameter is marked as read-only and was specified as a request parameter.

**Action:** Retry the operation without the parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01039: Parameter, {0}, is not allowed in request submission parameters.**

**Cause:** The given parameter is not allowed to be included as a request parameter for a submit operation. Usually such parameters can be set only via a metadata parameter.

**Action:** Retry the operation without the given parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01040: Invalid parameter {0}. Scoped parameters are only supported for JobSet.**

**Cause:** A scoped parameter was included in the request parameters specified for the request submission of a JobDefinition. Scoped parameters are supported only for a JobSet.

**Action:** Retry the submit operation without the scoped parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**ESS-01041: Parameter, {0}, is not allowed as a scoped request parameter for JobSet step {1}.**

**Cause:** The request parameters for a JobSet submission include a scoped parameter that is not allowed to be specified as a scoped parameter for a JobSet step.

**Action:** Retry the submit operation without the scoped parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01042: Metadata type, {0}, is not supported for a sub-request.Only JobDefinition is supported.**

**Cause:** Attempted to submit a sub-request for an unsupported definition type. Subrequest supported only for a JobDefinition.

**Action:** Retry the operation using a valid definition type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01043: Failed to get XML for an adhoc Schedule.**

**Cause:** Error occurred creating XML representation of an adhoc Schedule.

**Action:** Fix the adhoc Schedule and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01044: Failed to get XML for an adhoc Trigger.**

**Cause:** Error occurred creating XML representation of an adhoc Trigger.

**Action:** Fix the adhoc Trigger and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01045: Failed to validate Trigger expression against the schema.**

**Cause:** Error occurred validating the XML for a Trigger expression.

**Action:** Fix the Trigger expression and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01046: Start time must be before the end time.**

**Cause:** Attempted to submit a request where the start time is after the end time.

**Action:** Retry the operation with valid start and end times.

**Level:** 1



---

**Type:** ERROR

**Impact:** Programmatic

**ESS-01047: End time must be after the current time.**

**Cause:** Attempted to submit a request where the end time is before the current time.

**Action:** Retry the operation with value end time.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01048: Schedule has expired and no executions are possible.**

**Cause:** Attempted to submit a request with a Schedule that has expired.

**Action:** Retry the operation with a different Schedule.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01049: No executions are possible before the given end date.**

**Cause:** Attempted to submit a request with a Schedule for which there no executions prior to the end date.

**Action:** Retry the operation with a different Schedule.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01050: One or more requests are currently pending for definition: {0}**

**Cause:** The SystemProperty.ALLOW\_MULT\_PENDING property is disabled for the request being submitted. Execution is already pending for one or more requests with the same job definition.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01051: Incompatible with parent request {0} due to Incompatibility definition: {1}**

**Cause:** Attempted to submit a sub-request that is incompatible with its parent request due to an Incompatibility definition

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01052: Request handle is not valid for the current execution context of parent request {0}.**

---

**Cause:** The SystemProperty.ALLOW\_MULT\_PENDING property is disabled for the request being submitted. Execution is already pending for one or more requests with the same job definition.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01053: Cannot cancel request {0}. Current state is {1}.**

**Cause:** Attempted to cancel a request whose current state does not allow the operation to be performed.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01054: Cannot hold request {0}. Current state is {1}.**

**Cause:** Attempted to hold a request whose current state does not allow the operation to be performed.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01055: Cannot release request {0}. Current state is {1}.**

**Cause:** Attempted to release a request whose current state does not allow the operation to be performed.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01056: Cannot delete request {0}. Current state is {1}, process phase is {2}.**

**Cause:** Attempted to delete a request whose current state or process phase does not allow the operation to be performed.

**Action:** Retry the operation at a later time.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01057: Cannot purge request {0}. Current state is {1}, process phase is {2}.**

**Cause:** Attempted to purge a request whose current state or process phase does not allow the operation to be performed.

**Action:** Retry the operation at a later time.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**ESS-01058: Cannot change priority for request {0}. Current state is {1}.**

**Cause:** Attempted to change the priority for a request whose current state does not allow the operation to be performed.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01059: Delete failed for request {0}. This operation is not supported for a sub-request or JobSet step.**

**Cause:** Attempted to perform a delete operation on a child request. Only an absolute parent or instance parent can be the target of a delete operation.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01060: Purge failed for request {0}. This operation not supported for a sub-request or JobSet step.**

**Cause:** Attempted to perform a purge operation on a child request. Only an absolute parent or instance parent can be the target of a purge operation.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01061: Failed to purge request {0}.**

**Cause:** An error occurred attempting to purge a request.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01062: Invalid priority value. Valid range is {0} to {1}.**

**Cause:** An invalid value for request priority is specified.

**Action:** Specify a value in the indicated range.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01063: Failed to retrieve Schedule for request {0}.**

**Cause:** Failed to retrieve the Schedule associated with the given request.

---

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01064: Failed to retrieve Trigger for request {0}.**

**Cause:** Failed to retrieve the Trigger associated with the given request.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01065: Cannot recover request {0} with incomplete child requests.**

**Cause:** An attempt was made to manually recover a request with at least one child not in ProcessPhase.Complete.

**Action:** Wait for the incomplete child to complete or recover.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01066: Request state {0} not allowed for manual recovery. State should be canceling or terminal. {1}**

**Cause:** An attempt was made to manually recover a request that was in an illegal state.

**Action:** Cancel the request.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01067: Error occurred mapping Filter to CompositeData.**

**Cause:** Error occurred mapping Filter to CompositeData.

**Action:** Correct the invalid CompositeData instance.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01068: Unexpected type, {0}, for Filter value {1}.**

**Cause:** Unexpected Filter type for Filter value.

**Action:** Correct the invalid Filter type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01069: Invalid Null input for a Filter {0}.**

**Cause:** Unexpected null input for a filter.

---

**Action:** Provider a non null value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01070: Cannot change start time or end time for request of type {0}**

**Cause:** The start and end times cannot be updated for a request this type.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01071: Schedule for request {0} cannot be for a retry attempt**

**Cause:** The schedule for this request cannot be replaced during a retry.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01072: Metadata schedule and adhoc schedule were specified. Only one schedule can be used.**

**Cause:** A metadata schedule and an adhoc schedule were specified for an operation. Only one schedule should be specified.

**Action:** Retry the operation with only one schedule

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01073: Failed to open runtime service: {0}. {1}**

**Cause:** An error occurred opening the RuntimeService handle

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01074: Failed to open runtime service due to resource error. {0}**

**Cause:** A resource error occurred opening the RuntimeService handle.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01075: Cannot delete execution group, {0}, because active instances exist.**

---

**Cause:** A execution group must not be deleted when active instances exist in its cluster.

**Action:** Use only when the cluster associated with the execution group no longer exists.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01076: Execution group {0} is already being deleted.**

**Cause:** The execution group is already being deleted.

**Action:** Wait for first deletion to complete.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**ESS-01077: Failed to get async request information for message {0}.**

**Cause:** Failed to retrieve information for web service asynchronous callback.

**Action:** Check the logs.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01078: Request {0} is required to be asynchronous for this operation.**

**Cause:** This operation cannot be executed on a synchronous request.

**Action:** Do not invoke the operation on this request.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01079: Error attempting to access request information.**

**Cause:** An error occurred attempting to access request information.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01080: Failed to persist request information.**

**Cause:** An error occurred attempting to persist request information to the runtime store.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**ESS-01081: Failed to persist request parameter {0}, scope {1}.**

**Cause:** An error occurred attempting to store a request parameter.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01082: Failed to persist read-only constraint for parameter {0}.**

**Cause:** An error occurred attempting to store parameter read-only constraint.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01083: Error attempting to retrieve parameters for request {0}.**

**Cause:** An error occurred attempting to retrieve request parameters.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01084: Error attempting to update parameter, {0}, for request {1}.**

**Cause:** An error occurred attempting to update a request parameter.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01084: Error attempting to update parameter, {0}, for request {1}.**

**Cause:** An error occurred attempting to add a request parameter.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01086: Operation not supported for scoped parameter, {0}.**

**Cause:** A scoped parameter was specified for an operation that is not supported for scoped parameter.

**Action:** None

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01087: Failed to convert Document to byte sequence.**

**Cause:** An error occurred converting a Document to byte sequence.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01088: Failed to convert byte sequence to Document.**

**Cause:** An error occurred converting a byte sequence to a Document.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01089: Failed to get storable value for parameter, {0}.**

**Cause:** An error occurred converting a parameter value to its stored representation.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01090: Failed to get typed value for parameter, {0}, data type, {1}.**

**Cause:** An error occurred converting a parameter value from its stored representation to a typed value.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01096: Query result handle is null.**

**Cause:** The value of the query result handle argument is null.

**Action:** Specify an argument value that is not null.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01097: Request, {0}, is not of expected type, {1}.**

**Cause:** The request was found in ESS runtime storage but was not of the expected execution type.

**Action:** Specify a request identifier for a request of the correct execution type.



---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01098: No request is found for id {0} {1}**

**Cause:** A request was not found in ESS runtime storage corresponding to the indicated request identifier.

**Action:** Specify a request identifier for an existing request.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01099: An error occurred invoking the RuntimeService MBean. {0}**

**Cause:** An error occurred invoking the RuntimeService MBean.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01100: Error retrieving details about Oracle Scheduler job {0} for request {1}.**

**Cause:** An error occurred while trying to retrieve details about the Oracle Scheduler job associated with an ESS request identifier.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01101: Error retrieving the OUTPUT\_LIST for parallel children of request {0}.**

**Cause:** An error occurred while trying to retrieve the OUTPUT\_LIST for parallel child requests for an ESS request identifier.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01102: Failed to register application, {0}, with instance {1}. {2}**

**Cause:** Application registration failed with ESS.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01103: Failed to unregister all applications for instance {0}. {1}**

---

**Cause:** Application deregistration failed with ESS.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01104: Failed to unregister application, {0}, for instance {1}. {2}**

**Cause:** Application deregistration failed with ESS.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01105: Failed to check in instance {0}. {1}**

**Cause:** Registration update of ESS instance failed.

**Action:** Check that database is running and data source is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01106: Failed to clear checkin entry for instance {0}. {1}**

**Cause:** Unregistration of ESS instance failed.

**Action:** Check that database is running and data source is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01107: Failed to remove timed out instance registrations. {0}**

**Cause:** Unregistration of ESS timed-out instances failed.

**Action:** Check that database is running and data source is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01108: Failed to fetch elements from wait queue. {0}.**

**Cause:** An error occurred attempting to fetch elements from the wait queue.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01109: Failed to access wait queue element for request {0}. {1}**

**Cause:** An error occurred attempting to access a wait queue element.

---

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01110: Failed to lock wait queue element for request {0}. {1}**

**Cause:** Failed to obtain a lock on the wait queue element for a request.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01111: Failed to insert wait queue element for request {0}. {1}**

**Cause:** An error occurred while attempting to add an element to the wait queue.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01112: Failed to delete wait queue element for request {0}. {1}**

**Cause:** An error occurred while attempting to remove an element from the wait queue.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01113: Failed to hold wait queue element for request {0}. {1}**

**Cause:** An error occurred attempting to hold the wait queue element for a request.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01114: Failed to release wait queue element for request {0}. {1}**

**Cause:** An error occurred attempting to release the wait queue element for a request.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**ESS-01115: Failed to undefer wait queue element for request {0}. {1}**

**Cause:** An error occurred attempting to undefer the wait queue element for a request.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01116: Query field name, {0}, is not a valid name.**

**Cause:** A query filter was specified with an unknown query field.

**Action:** Remove that query field from the filter, or specify a known name for the query field.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01117: Value for query field, {0}, has an unsupported data type: {1}**

**Cause:** A query filter was specified in which the value for a query field has an unsupported data type.

**Action:** Specify a query value whose data type is a supported type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01118: Query field, {0}, has a null value which is not supported for the {1} operator.**

**Cause:** A query filter was specified with a field that has a null value and a comparator that does not support a null value. A null query value requires an EQUALS or NOT\_EQUALS comparator.

**Action:** Specify a non-null value for that query field, or specify an EQUALS or NOT\_EQUALS comparator.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01119: Query field, {0}, has a value with a data type, {1}, that is not supported for the {2} comparator.**

**Cause:** A query filter was specified with a field that has a value whose data type is not supported for the specified comparator.

**Action:** Specify a query value whose data type is supported by the comparator being used.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**ESS-01120: Query field, {0}, does not support the {1} comparator.**

**Cause:** A query filter was specified with a field that does not support the specified comparator.

**Action:** Specify a comparator that is supported by that query field.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01121: Failed to retrieve field {0}.**

**Cause:** A failure occurred while retrieving the specified field.

**Action:** Check that database is running and data source is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01122: Error attempting to access information for incompatibility {0} for request {1}.**

**Cause:** An error occurred attempting to access request incompatibility information.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01123: Error attempting to update information for incompatibility {0} for request {1}.**

**Cause:** An error occurred attempting to update request incompatibility information.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01124: Error attempting to add information for incompatibility {0} for request {1}.**

**Cause:** An error occurred attempting to add request incompatibility information.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**ESS-01125: Size of request parameter {0} used for incompatibility {1} is too large.**

**Cause:** The value for a request parameter that would be used for an Incompatibility is too large.

**Action:** Use a smaller value for the parameter value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01126: Application {0} is active in more than one group.**

**Cause:** An application with the same name is already a member of another ESS group.

**Action:** Redeploy the current application with a unique deployment name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01127: Application {0} is not active in any ESS instance.**

**Cause:** The application could not be found in the current ESS group.

**Action:** Ensure the application is deployed and running in the correct ESS group.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01128: Application with deployed name {0} exists with multiple logical names.**

**Cause:** An application with the same deployment name but different logical name is already a member of this ESS group.

**Action:** Redploy this application with a unique deployment name. If this application is the same application as the conflicting app, then change the logical name to match.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01129: Application with deployed name {0} was not found.**

**Cause:** The application is not a member of this ESS group.

**Action:** Ensure the application is deployed and running in the correct ESS group.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01130: Application with logical name {0} exists with multiple deployed names.**

**Cause:** An application with the same logical name but different deployment name is already a member of this ESS group.

**Action:** Redploy this application with a unique logical application name. If this application is the same application as the conflicting app, then change the deployment name to match.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01131: Application with logical name {0} was not found.**

**Cause:** The application is not a member of this ESS group.

**Action:** Ensure the application is deployed and running in the correct ESS group.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01132: Unable to access processor bindings. {0}**

**Cause:** Processor bindings in the runtime store could not be accessed.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01133: Processor binding {0} could not be found.**

**Cause:** Processor binding could not be found.

**Action:** Check that you specified the correct binding name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01134: Processor binding {0} already exists.**

**Cause:** Processor binding already exists.

**Action:** Change the name of the binding.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01135: Unable to notify server of processor bindings change. {0}**

**Cause:** Unable to notify server of bindings change.

**Action:** Check that database is running and data source is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01136: Unable to access processor bindings change notification. {0}**

**Cause:** Unable to access bindings change notification.

**Action:** Check that database is running and data source is correct.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**ESS-01137: Unable to notify server to refresh selector. {0}**

**Cause:** Unable to notify server to refresh selector.

**Action:** Check that database is running and data source is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01138: Unable to access refresh selector notification. {0}**

**Cause:** Unable to access refresh selector notification.

**Action:** Check that database is running and data source is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01139: Value, {1}, for query field, {0}, is invalid.**

**Cause:** A query filter was specified in which the value for a query field was invalid.

**Action:** Specify a valid query value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01140: Error accessing async throttle information for ({0}, {1}). {2}**

**Cause:** An error occurred while accessing runtime async throttle information.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01141: Async throttle already exists for Workshift = {0}. {1}**

**Cause:** The throttle is already configured for the Workshift.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01142: Async throttle not found for Workshift = {0}.**

**Cause:** The throttle was not found for the Workshift.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.



---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01143: Failed to process filter {0}.**

**Cause:** Filter evaluation failed.

**Action:** Correct the invalid Filter.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01144: Failed to retrieve timed out instance registrations. {0}**

**Cause:** Query of ESS timed out registrationsinstance failed.

**Action:** Check that database is running and data source is correct.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01145: Failed to lock instance {0}. {1}**

**Cause:** Locking the ESS instance registration failed.

**Action:** Check that database is running and data source is correct.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01146: Error accessing runtime async throttle information. {0}**

**Cause:** An error occurred while accessing the throttle configuration.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01147: Failed to get DiagnosticState for instance {0}. {1}**

**Cause:** Failed to get DiagnosticState for the instance.

**Action:** None

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**ESS-01148: Failed to clear registrations for execution group {0}, isolation group {1}. {2}**

**Cause:** Failed to clear registrations for execution group.

**Action:** None. Registrations will be automatically retried

---

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01149: Error accessing unthrottled work assignments ({0}). {1}**

**Cause:** An error occurred while accessing the unthrottled work assignments.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01150: Unable to delete workshift with outstanding async workers: {0}**

**Cause:** A workshift that has outstanding async workers not be deleted.

**Action:** Wait until all async workers have completed and then delete the workshift.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01151: Error accessing async limit information for workshift = {0}. {1}**

**Cause:** An error occurred while accessing runtime async limit information.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01152: Error accessing async allocation information for work assignment = {0}. {2}**

**Cause:** An error occurred accessing runtime async allocation information.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01200: Error attempting to insert {0} work unit for request {1}.**

**Cause:** An error occurred inserting a work unit into the persistent store.

**Action:** Review the log file to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01201: Error attempting to insert {0} work unit.**

---

**Cause:** An error occurred inserting a work unit into the persistent store.

**Action:** Review the log file to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01202: Failed to update work stage for work {0}.**

**Cause:** An error occurred updating the work stage of a work unit.

**Action:** Review the log file to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01203: Failed to delete work for request {0}.**

**Cause:** An error occurred deleting work units.

**Action:** Review the log file to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01204: Failed to delete work {0} for request {1}.**

**Cause:** An error occurred deleting work units.

**Action:** Review the log file to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01205: Failed to delete work unit {0}.**

**Cause:** An error occurred deleting work units.

**Action:** Review the log file to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01206: Failed to check in work unit {0} for request {1}.**

**Cause:** An error occurred checking in work units.

**Action:** Review the log file to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01207: Failed to check in work unit {0}.**

**Cause:** An error occurred checking in work units.

**Action:** Review the log file to determine the nature of the problem.

---

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01208: Failed to undefer DeleteProcessGroup work for execution group {0}.**

**Cause:** An error occurred undeferring a DeleteProcessGroupEvent.

**Action:** Review the log file to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01209: Failed to update information for work {0} for request {1}.**

**Cause:** An error occurred updating a work unit.

**Action:** Review the log file to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01210: Failed to undefer work for request {0}.**

**Cause:** An error occurred undeferring a work unit.

**Action:** Review the log file to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01211: Failed to check in work for instance {0}.**

**Cause:** An error occurred checking in all the work units for an ESS instance.

**Action:** Review the log file to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01212: Error retrieving available work units.**

**Cause:** Error occurred while retrieving work units to process.

**Action:** Review the log file for runtime cause.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01213: Failed to retrieve work unit {0}.**

**Cause:** Error occurred while retrieving a work unit to process.

**Action:** Review the log file for runtime cause.

**Level:** 1

**Type:** WARNING

---

**Impact:** Other

**ESS-01214: Failed to determine if work {0} is checked out to instance {1}.**

**Cause:** Failed to determine if the work is checked out to this instance.

**Action:** Review the log file for runtime cause.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01215: Error occurred querying check out work units for instance {0}.**

**Cause:** Failed to determine the work units checked out to the instance.

**Action:** Review the log file for runtime cause.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01216: Failed to access work unit {0}.**

**Cause:** Error occurred attempting to access work unit.

**Action:** Review the log file for runtime cause.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01217: Error waiting for work.**

**Cause:** Error occurred while waiting for new work.

**Action:** Review the log file for runtime cause.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01218: Error waiting for work. Operation returned: {0}.**

**Cause:** Operation used to work for new work returned the specified result.

**Action:** Review the log file for runtime cause.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01219: Work unit {0} is not checked out to instance {1}.**

**Cause:** The work unit is not checked out to the specified instance.

**Action:** None

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01220: Failed to lock work unit {0} by instance {1}.**

---

**Cause:** Failed to lock the work unit by the specified instance.

**Action:** None

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01250: Error retrieving available event work.**

**Cause:** Error occurred while retrieving event work to process.

**Action:** Review the log file for runtime cause.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01251: Failed to access event work {0}.**

**Cause:** Error occurred attempting to access event work.

**Action:** Review the log file for runtime cause.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01252: Failed to update event work {0}.**

**Cause:** Error occurred attempting to update event work.

**Action:** Review the log file for runtime cause.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01253: Failed to delete event work {0}.**

**Cause:** Error occurred attempting to delete event work.

**Action:** Review the log file for runtime cause.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01254: Failed to delete event work for request {0}.**

**Cause:** Error occurred attempting to delete event work for a request.

**Action:** Review the log file for runtime cause.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01255: Failed to check in event work {0}.**

**Cause:** Error occurred attempting to check in event work.

**Action:** Review the log file for runtime cause.

---

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01256: Failed to check in event work for instance {0}.**

**Cause:** Error occurred attempting to check in event work for an instance.

**Action:** Review the log file for runtime cause.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01257: Failed to add event. Event name: {0}, request: {1}.**

**Cause:** Error occurred attempting to insert event work.

**Action:** Review the log file for runtime cause.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01258: Event work not found: {0}.**

**Cause:** The specified event work was not found.

**Action:** None

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**ESS-01259: Error waiting for event work.**

**Cause:** Error occurred while waiting for new event work.

**Action:** Review the log file for runtime cause.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01260: Error waiting for event work. Operation returned: {0}.**

**Cause:** Operation used to work for new event work returned the specified result.

**Action:** Review the log file for runtime cause.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01262: Event work {0} is not checked out to instance {1}.**

**Cause:** The event work is not checked out to a specific instance.

**Action:** None

**Level:** 1

**Type:** WARNING

---

**Impact:** Other

**ESS-01263: Invalid event listener class, {0}.**

**Cause:** The class name configured for the request listener is not a valid event listener class.

**Action:** None

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01264: Unable to instantiate event listener for class, {0}.**

**Cause:** Unable to instantiate an instance of an event listener class name.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01265: Unable to retrieve information needed to dispatch an event for request {0}.**

**Cause:** Failed to retrieve information needed to dispatch an event.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01266: Failed to lock event work {0} by instance {1}.**

**Cause:** Failed to lock the event work by the specified instance.

**Action:** None

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01500: Dispatcher cannot be started while in {0} state.**

**Cause:** Attempted to start the dispatcher when it is in a state for which the operation is not allowed.

**Action:** Retry the operation when the dispatcher state is STOPPED.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01501: Dispatcher cannot be stopped while in {0} state.**

**Cause:** Attempted to stop the dispatcher when it is in a state for which the operation is not allowed.



---

**Action:** Retry the operation when the dispatcher state is STARTING or RUNNING.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01502: Processor cannot be started while in {0} state.**

**Cause:** Attempted to start the processor when it is in a state for which the operation is not allowed.

**Action:** Retry the operation when the processor state is STOPPED.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01503: Processor cannot be stopped while in {0} state.**

**Cause:** Attempted to stop the processor when it is in a state for which the operation is not allowed.

**Action:** Retry the operation when the processor state is STARTING or RUNNING.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01504: Cannot add endpoint {0} for application {1} because endpoint {2} already exists for application {3}.**

**Cause:** The endpoint to add conflicts with an already existing endpoint.

**Action:** Modify the endpoint name.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**ESS-01505: Failed to retrieve information for request {0}.**

**Cause:** Failed to retrieve runtime information for a request.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01601: JobSet request {0} completed with an invalid final state {1}.**

**Cause:** A JobSet request has been marked as completed, but has an unexpected final state.

**Action:** Review the log file for errors pertaining to the request.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**ESS-01602: First step is not defined in serial JobSet: {0}.**

**Cause:** Cannot process a JobSet request due to invalid JobSet definition. The first step of a serial JobSet is not defined.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01603: Error dispatching subrequests for parent request {0}.**

**Cause:** An error occurred while attempting to dispatch subrequests for a parent request in PAUSED state.

**Action:** Review the log file to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01604: Failed to create {0} work unit for request {1}.**

**Cause:** Unable to create the specified work unit for a request.

**Action:** Review the log file to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01605: Failed to create event, {0}, for request {1}.**

**Cause:** An error occurred while attempting to create an event for a request.

**Action:** Review the log file to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01606: Failed to mark request {0} as completed.**

**Cause:** An error prevented the request from being marked completed

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01607: Request {0} cannot be marked complete. State is {1}, process phase is {2}.**

**Cause:** The request state and/or process phase prevents a request from being completed.

**Action:** None

**Level:** 1

---

**Type:** WARNING

**Impact:** Other

**ESS-01700: Unrecognized request type : {0}.**

**Cause:** The job type used for the request is not supported.

**Action:** Correct the job type definition.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01701: Unable to instantiate executable wrapper for class {0}.**

**Cause:** Unable to instantiate wrapper class used to process the request.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**ESS-01702: Unable to instantiate pre-process callback handler for request {0} using class name, {1}.**

**Cause:** Failed to instantiate an object for the pre-process callback handler class associated with a request.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01703: Unable to instantiate post-process callback handler for request {0} using class name, {1}.**

**Cause:** Failed to instantiate an object for the post-process callback handler class associated with a request.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01704: Error occurred at initiate stage during execution of request {0}. {1}**

**Cause:** An error occurred during the initiate stage of a request execution.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

- 
- ESS-01705: Error occurred at finalize stage during execution of request {0}. {1}**  
**Cause:** An error occurred during the finalize stage of a request execution.  
**Action:** Review the log file for attached exceptions to determine the nature of the problem.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic
- ESS-01706: Invalid execution result code, {0}, for request {1}.**  
**Cause:** A REQUEST\_FINALIZATION event contained an unknown result code.  
**Action:** This indicates an internal error. Contact Oracle Support Services.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic
- ESS-01707: Unable to instantiate Executable for Java request {0} using class name, {1}.**  
**Cause:** Failed to instantiate Executable object for a Java request.  
**Action:** Review the log file for attached exceptions to determine the nature of the problem.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic
- ESS-01708: Database job for request {0} ended with error: {1}.**  
**Cause:** Execution of a SQL request has ended with a error.  
**Action:** Review the log file for attached exceptions to determine the nature of the problem.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic
- ESS-01709: Database job for request {0} ended with warning: {1}.**  
**Cause:** Execution of a SQL request has ended with a warning.  
**Action:** None.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic
- ESS-01710: Database job for request {0} was cancelled.**  
**Cause:** Execution of a SQL request has been cancelled.  
**Action:** None.  
**Level:** 1  
**Type:** NOTIFICATION

---

**Impact:** Programmatic

**ESS-01711: Database job for request {0} was paused. Paused state value: {1}.**

**Cause:** Execution of a SQL job request has been paused to allow one or more sub-requests to execute.

**Action:** None. The execution of the paused request will be resumed once the sub-requests have completed.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Programmatic

**ESS-01712: Failed to create database job for request {0}.**

**Cause:** An error occurred trying to create an Oracle Scheduler job used to execute a SQL job request.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01713: Error cancelling database job for request {0}.**

**Cause:** An error occurred during post-execution clean tasks for an Oracle Scheduler job used to execute a SQL job request.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01714: Database job for request {0} ended with business error: {1}.**

**Cause:** Execution of a SQL request has ended with a biz error.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01715: Failed to create database job for request {0} using Oracle Scheduler job class {1}.**

**Cause:** An error occurred trying to create an Oracle Scheduler job used to execute a SQL job request with the given Oracle Scheduler job class.

**Action:** Verify the EXECUTE privilege on the Oracle Scheduler job class has been granted to the ESS schema user. Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**ESS-01900: Error constructing ESS command {0}. {1}**

**Cause:** An error is present in the command format.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01901: Unsupported value, {0}, for attribute {1}.**

**Cause:** An unknown value was specified for a parameter.

**Action:** Specify a valid attribute value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-01903: Unknown command type {0}. {1}**

**Cause:** An unknown command type was submitted.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-01904: Document is not valid for work {0}.**

**Cause:** The command document is invalid for this Enterprise Scheduler server

**Action:** None. The command will be deferred.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01905: Attribute {0} value {1} from command document does not match value {2} from command creation.**

**Cause:** The internal command state is inconsistent for the given attribute.

**Action:** Contact administrator.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01906: Error retrieving available command work.**

**Cause:** Error occurred while retrieving command work to process.

**Action:** Review the log file for runtime cause.

**Level:** 1

**Type:** WARNING

**Impact:** Other

---

**ESS-01907: Failed to access command work {0}.**

**Cause:** Error occurred attempting to access command work.

**Action:** Review the log file for runtime cause.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01908: Failed to update command work {0}.**

**Cause:** Error occurred attempting to update command work.

**Action:** Review the log file for runtime cause.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01909: Failed to delete command work {0}.**

**Cause:** Error occurred attempting to delete command work.

**Action:** Review the log file for runtime cause.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01910: Failed to delete command work for request {0}.**

**Cause:** Error occurred attempting to delete command work for a request.

**Action:** Review the log file for runtime cause.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01911: Failed to check in command work {0}.**

**Cause:** Error occurred attempting to check in command work.

**Action:** Review the log file for runtime cause.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01912: Failed to check in command work for instance {0}.**

**Cause:** Error occurred attempting to check in command work for an instance.

**Action:** Review the log file for runtime cause.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01913: Command work not found: {0}.**

**Cause:** The specified command work was not found.

---

**Action:** None

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**ESS-01914: Command work {0} is not checked out to instance {1}.**

**Cause:** The command work is not checked out to a specific instance.

**Action:** None

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01915: Failed to lock command work {0} by instance {1}.**

**Cause:** Failed to lock the command work by the specified instance.

**Action:** None

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01980: Batch delete initialization failed.**

**Cause:** An error occurred during initialization of batch delete support.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**ESS-01981: Failed to delete request {0}. Reason: {1}**

**Cause:** An error occurred attempting to delete a request.

**Action:** None

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**ESS-01982: Insufficient privileges to delete request {0}.**

**Cause:** Execution user of a batch delete job does not have sufficient privileges to delete the request.

**Action:** Batch delete job should be submitted only by ESS administrator

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**ESS-01983: Error determining requests for batch delete.**

**Cause:** An error occurred attempting to determine requests to delete.



---

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**ESS-01984: Error occurred while executing batch delete request {0}. Cause: {1}**

**Cause:** An error occurred during request execution.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-01985: Execution of request {0} was cancelled.**

**Cause:** Request execution was canceled.

**Action:** None

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**ESS-01987: Runtime store error during batch delete.**

**Cause:** Runtime store error occurred during batch delete operation.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**ESS-01988: Failed to lock request for batch delete.**

**Cause:** Unable to lock one or more requests during batch delete operation

**Action:** None

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**ESS-01989: Batch delete request {0} failed to delete request {1}. Reason: {2}**

**Cause:** Batch delete job failed to delete the specified request.

**Action:** Review log file to determine the reason.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**ESS-02001: User {0} does not have execute permission on metadata object {1}.**

**Request {2} execution is aborted.**

---

**Cause:** User {0} does not have execute permission on metadata object {1}. Request {2} execution is aborted.

**Action:** Check the policy assignment..

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-02002: User {0} does not have sufficient privilege to perform operation {1}.**

**Cause:** User {0} does not have sufficient privilege to perform operation {1}.

**Action:** Grant the policy to the user {0}..

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-02003: User {0} does not have sufficient privilege to perform operation {1} on request {2}.**

**Cause:** User {0} does not have sufficient privilege to perform operation {1} on request {2}.

**Action:** Grant the policy to the user {0}..

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-02004: User or appid {0} is not a valid entry in the idstore configured in jps-config.xml.**

**Cause:** {0} can not be authenticated.

**Action:** Check the user settting.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-02005: User {0} does not have {1} privilege on metadata object {2}. Request {3} validation failed.**

**Cause:** User {0} does not have {1} privilege on metadata object {2}. Request {3} validation failed.

**Action:** Check the policy assignment..

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-02006: User {0} does not have sufficient privilege to perform operation {1} on jobset {2}, failed steps are {3}.**

**Cause:** User {0} does not have sufficient privilege to perform operation {1} on jobset {2}, failed steps are {3}.

**Action:** Grant the policy to the user {0}..

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-02007: User or appid {0} whom job {1} runas is not a valid entry in the idstore configured in jps-config.xml.**

**Cause:** The user or appid {0} is not a valid identity or can not be authenticated.

**Action:** Check your metadata definition.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-02200: Mismatched request handles for request {0}.**

**Cause:** The request may have been retried.

**Action:** Update with request execution context from new execution if desired.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-02220: Failed to deliver web service callback for message {0} for request {1}.**

**Cause:** The web service asynchronous callback message could not be delivered.

**Action:** The action may be retried. Check the log files.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-05000: Error occurred. {0}**

**Cause:** Enterprise Scheduler Service encountered an error.

**Action:** Review the log file for indications of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-05010: Request {0} not found.**

**Cause:** Request with the given request id can not be found in the database.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-05013: Request {0}. Process phase {1} not in valid phases {2}.**

**Cause:** The process phase of the request is inconsistent with its current status.

**Action:** None

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**ESS-05021: Failed to begin transaction.**

**Cause:** Being of a user transaction failed.

**Action:** Review the log file for runtime cause.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-05022: Failed to commit transaction.**

**Cause:** Failed to commit the transaction.

**Action:** Review the log file for runtime cause.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-05023: Failed to rollback transaction.**

**Cause:** Failed to rollback the transaction.

**Action:** Review the log file for runtime cause.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-05024: Failed to set transaction timeout.**

**Cause:** Failed to set transaction timeout.

**Action:** Review the log file for runtime cause.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-05038: Failed to find JNDI resource for {0}.**

**Cause:** Failed to perform a JNDI lookup for a given resource name.

**Action:** Verify the configuration for the resource.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ESS-05039: Error occurred closing JNDI naming context.**

**Cause:** An error occurred while trying to close a JNDI naming context.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

---

**Impact:** Other

**ESS-05043: Failed to commit SQL transaction.**

**Cause:** An error occurred trying to commit database transaction.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-05044: Failed to rollback SQL transaction.**

**Cause:** An error occurred trying to rollback database transaction.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-05045: Error using SQL ResultSet. {0}**

**Cause:** An error occurred while using an SQL ResultSet.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-05046: Failed to close an SQL ResultSet.**

**Cause:** An error occurred trying to close an SQL ResultSet.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-05047: Failed to close an SQL Statement.**

**Cause:** An error occurred trying to close an SQL Statement.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-05048: Failed to obtain a database connection.**

**Cause:** An error occurred trying to obtain a database connection.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-05049: Failed to close a database connection.**

**Cause:** An error occurred trying to close a database connection.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-05053: Failed to map object of type {0} to CompositeData.**

**Cause:** An error occurred converting an ESS object to a javax.management.openmbean.CompositeData object

**Action:** Contact Oracle Support Services

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Other

**ESS-05054: Failed to map CompositeData object to {0}.**

**Cause:** An error occurred converting a javax.management.openmbean.CompositeData object to an ESS object

**Action:** Contact Oracle Support Services

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Other

**ESS-05055: Illegal state transition from {0} to {1} for request {2}.**

**Cause:** An update event's timing may have tried to change the state after the request has begun a transition to a terminal state.

**Action:** This warning can be ignored.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-05100: Operator {1} is invalid with query field {0}. Valid operators are: {2}.**

**Cause:** Operator is invalid for the given query field.

**Action:** Use a valid operator.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-05101: Comparator {1} is invalid with query field {0}. Valid comparators are: {2}.**

**Cause:** Comparator is invalid for the given query field.

---

**Action:** Use a valid comparator.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-05102: Value of type {1} is invalid with query field {0}. Valid value types are: {2}.**

**Cause:** Value type is invalid for the given query field.

**Action:** Use a valid value type.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-05103: Value of type null is invalid with query field {0}.**

**Cause:** Null value type is invalid for the given query field.

**Action:** Use a valid non-null value type.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-05104: Failed to check in {0} work unit {1} for request {2}. {3}**

**Cause:** The work unit for the given request could not be checked in or deleted.

**Action:** The work unit operation should be automatically retried, so no action is necessary.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-05105: Metadata of type {0} cannot be customized. Only metadata of the following types can be customized: {1}.**

**Cause:** An invalid metadata type was provided.

**Action:** Provide a valid customizable metadata type.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-05106: Property {0} cannot be assigned a value of type {1}. Values for property {0} can only have the following types: {2}.**

**Cause:** The data type of the provided property is not valid.

**Action:** Provide a value with the correct data type.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-05107: An error occurred while parsing the metadata object id string: {0}**

**Cause:** An error occurred while parsing a metadata object id string.

---

**Action:** See base exception for detailed underlying cause.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-05108: The user provided metadata type of {0} does not match the metadata type of {1} in the metadata object id string**

**Cause:** The metadata type specified by the user does not match the metadata type specified by the metadata object id string.

**Action:** Check the metadata repository to ensure the metadata is correct or specify the correct type and try again.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-05109: While performing a metadata query, the following problem was detected with one of the query results: {1} The query will continue but exclude the piece of metadata with name {0}. This may affect the expected query results.**

**Cause:** A problem occurred while processing a result of the metadata query.

**Action:** Check the piece of metadata causing the problem for any issues and check the health of the metadata repository.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-05110: An error occurred while retrieving the metadata object with name {0} of type {1}.**

**Cause:** A problem occurred while retrieving a piece of metadata.

**Action:** See the base exception for the cause then check the piece of metadata causing the problem for any issues and check the health of the metadata repository.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-05490: Service MBeans registration failed.**

**Cause:** Service MBeans registration failed.

**Action:** Review the log file for underlying causes.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-05700: Failed to obtain a metadata service instance. {0}**

**Cause:** Failed to obtain a metadata service instance.

**Action:** Review the log file for underlying causes.



---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-05704: An error occurred invoking the MetadataService MBean. {0}**

**Cause:** An error occurred invoking the RuntimeService MBean.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-05705: Failed to save the {0} with name {1}.**

**Cause:** Failed to save the metadata object.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-05706: {0} with name {1} does not exist.**

**Cause:** Unable to find the metadata object.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-05707: {0} with name {1} already exists.**

**Cause:** The metadata object already exists.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-05708: Failed to delete the {0} with name {1}.**

**Cause:** Unable to delete the metadata object

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-05709: Parameter {0} starts with {1} which is a reserved parameter keyword.**

---

**Cause:** A property defined by the metadata object contains a reserved keyword.

**Action:** Remove the reserved keyword from the property name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-05710: A validation error occurred while validating JobSet step {0}.**

**Cause:** A JobSet step failed validation.

**Action:** See the base validation exception for the original validation error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-05711: A null value cannot be used when querying the {0} field.**

**Cause:** A value of null was used as the query value.

**Action:** Provide a non-null argument.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06000: Failed to obtain a runtime service instance. {0}**

**Cause:** Failed to obtain a runtime service instance.

**Action:** Review log file for underlying cause.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-06002: Failed to close runtime service handle. {0}**

**Cause:** Failed to close runtime service handle.

**Action:** Review the log file for underlying causes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-06003: Runtime service system failure. {0}**

**Cause:** Runtime service system failure.

**Action:** Review the log file for underlying causes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-06100: No request found for the given id {0}.**

**Cause:** A request was not found in ESS runtime storage corresponding to the indicated request identifier.

---

**Action:** Specify a request identifier for an existing request.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-06102: An error occurred invoking the RuntimeService MBean.**

**Cause:** An error occurred invoking the RuntimeService MBean.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06521: Failed to start request dispatcher.**

**Cause:** An error occurred while trying to start the request dispatcher.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06522: Failed to start request processor.**

**Cause:** An error occurred while trying to start the request processor.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06523: Failed to start system event service.**

**Cause:** An error occurred while trying to start the system event service.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-06524: Failed to start application event service.**

**Cause:** An error occurred while trying to start the application event service.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**ESS-06525: Failed to start heartbeat monitor.**

**Cause:** An error occurred while trying to start the heartbeat monitor.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06526: Failed to update configuration information.**

**Cause:** An error occurred while trying to update configuration information.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-06527: Failed to start deferred monitor.**

**Cause:** An error occurred while trying to start the deferred monitor.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-06528: Failed to start work unit worker.**

**Cause:** An error occurred while trying to start the work unit worker.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-06530: Dispatcher cannot be started when it is in the {0} state.**

**Cause:** Dispatcher cannot be started when it is in the specified state.

**Action:** Start the dispatcher when it is in STOPPED state.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06531: Dispatcher cannot be stopped when it is in the {0} state.**

**Cause:** Dispatcher cannot be stopped when it is in the specified state.

**Action:** Stop the dispatcher when it is in STARTING or RUNNING state.

**Level:** 1

**Type:** WARNING

---

**Impact:** Other

**ESS-06532: Processor cannot be started when it is in the {0} state.**

**Cause:** Processor cannot be started when it is in the specified state.

**Action:** Start the processor when it is in STOPPED state.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06533: Processor cannot be stopped when it is in the {0} state.**

**Cause:** Processor cannot be stopped when it is in the specified state.

**Action:** Stop the processor when it is in STARTING or RUNNING state.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06538: No endpoint is available for {0}.**

**Cause:** An application using the specified endpoint application name is not deployed.

**Action:** Review the log file for underlying causes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-06539: Could not create endpoint for {0}.**

**Cause:** An error occurred creating an application endpoint.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-06540: Failed to get an endpoint to run dispatcher for application {0}.**

**Cause:** Dispatch monitor was unable to obtain an application endpoint. This may happen when the system is busy and does not necessary indicate a problem.

**Action:** Review the log file for indications of a problem if this persists.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**ESS-06541: Error during dispatch for application {0}.**

**Cause:** Error during dispatch for application.

**Action:** Review the log for underlying causes.

**Level:** 1

**Type:** WARNING

---

**Impact:** Other

**ESS-06542: Error getting applications to dispatch.**

**Cause:** Error getting applications for dispatch.

**Action:** Review the log for underlying causes.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06543: Failed to deactivate endpoint for application {0}.**

**Cause:** An error occurred while removing an application endpoint.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-06551: Failed processing trigger for {0} event.**

**Cause:** Failed processing event trigger.

**Action:** Review the log for underlying causes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-06552: Failed processing trigger for {0} event for request {1}.**

**Cause:** Failed processing event trigger.

**Action:** Review the log for underlying causes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-06553: Failed processing lifecycle for {0} event for request {1}.**

**Cause:** Failed processing lifecycle event for a request.

**Action:** Review the log for underlying causes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-06557: Failed to start heartbeat worker {0}.**

**Cause:** ESS heart beat monitor failed to start due to a system failure.

**Action:** Check the causeBy clause of this exception to find more details.

**Level:** 1

**Type:** WARNING

**Impact:** Other

---

**ESS-06558: Failed to get an endpoint to run a heartbeat for application {0}.**

**Cause:** Heartbeat monitor was unable to obtain an application endpoint. This may happen when the system is busy and does not necessary indicate a problem.

**Action:** Review the log file for indications of a problem if this persists.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**ESS-06560: Error encountered by event worker.**

**Cause:** Error encountered by event worker.

**Action:** Review the log for underlying causes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-06570: Failed to get metadata for work assignment {0}.**

**Cause:** Unable to retrieve work assignment metadata when analyzing work assignment bindings. The work assignment is ignored.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06571: Failed to get workshift metadata ({0}) for work assignment {1}.**

**Cause:** Unable to retrieve workshift metadata when analyzing a work assignment binding. The work assignment processing will ignore the workshift.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06572: Failed to get schedule metadata ({0}) for work assignment {1}.**

**Cause:** Unable to retrieve schedule metadata when analyzing a work assignment binding. The work assignment processing will ignore the workshift associated with the schedule.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06573: Failed to start work assignment {0}.**

**Cause:** Unable to start the first worker for the work assignment. The start will be retried in a short time.

---

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06574: Failed to start starvation thread for work assignment {0}.**

**Cause:** Unable to start the starvation worker for the work assignment. The work assignment will be activated without the starvation worker.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06575: Skipping inactive work assignment {0}.**

**Cause:** The work assignment is defined as inactive and is being skipped.

**Action:** If the work assignment should be active, change it to active and reload work assignment metadata.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**ESS-06576: Binding default work assignment.**

**Cause:** The default work assignment is being bound because no user-defined work assignments were bound.

**Action:** No action is necessary.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**ESS-06577: Skipping inactive workshift {0} for work assignment {1}.**

**Cause:** The workshift is being skipped because it is inactive. It may have an allocation of 0 or a duration of 0.

**Action:** No action is necessary.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**ESS-06578: Started work assignment {0}.**

**Cause:** Started the work assignment.

**Action:** No action is necessary.

**Level:** 1

**Type:** NOTIFICATION



---

**Impact:** Other

**ESS-06579: Stopped work assignment {0}.**

**Cause:** Stopped the work assignment.

**Action:** No action is necessary.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**ESS-06580: Skipping invalid work assignment {0}.**

**Cause:** The work assignment is being ignored because it is invalid.

**Action:** Check the work assignment and correct the problem. Ensure the work assignment has at least one workshift defined.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-06581: Skipping invalid work assignment binding {0}.**

**Cause:** The work assignment is being ignored because the binding is invalid.

**Action:** Check the work assignment binding mode and correct the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-06582: Skipping completed work assignment {0}.**

**Cause:** The work assignment has completed and will never again become active. It is being skipped.

**Action:** If the work assignment should not be completed, check the workshift schedules to ensure they are correct and reload work assignment metadata.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**ESS-06583: Cannot delete bound work assignment {0}.**

**Cause:** A work assignment that is bound may not be deleted.

**Action:** Unbind the work assignment and then delete it.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06584: Reloading metadata for work assignment {0}.**

**Cause:** Reloaded the work assignment metadata.

**Action:** No action is necessary.

**Level:** 1

**Type:** NOTIFICATION

---

**Impact:** Other

**ESS-06585: Unable to bind work assignment {0} due to invalid workshift {1}.**

**Cause:** In order to bind a work assignment, each of its workshifts must have an allocation of at least one. If the workshift has a schedule, the schedule must be unexpired, and the workshift duration must be > 0.

**Action:** Fix the workshift and try again to bind the work assignment.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06586: Work assignment {0} is invalid and cannot be bound.**

**Cause:** To be bound, a work assignment must have at least one workshift and be active. To be bound in exclusive mode, a work assignment must have a non-empty specialization.

**Action:** Fix the work assignment and try again to bind it.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06587: Invalid update of a bound work assignment {0}.**

**Cause:** A work assignment that is bound may not be changed to inactive.

**Action:** Unbind the work assignment and then update it.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06590: Error encountered by the worker for work assignment {0}.**

**Cause:** Error encountered by worker for work assignment.

**Action:** Review the log file for underlying causes.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06592: Error while processing request {0} for application {1}.**

**Cause:** Error while processing request for application

**Action:** Review the log file for underlying causes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-06593: Required property, {0}, is not present in message received for work assignment {1}.**

**Cause:** Required property is not present in message received for work assignment.

**Action:** Add the required request property for work assignment.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-06594: Failed to schedule additional work for work assignment {0}. {1}**

**Cause:** Failed to schedule additional work for work assignment.

**Action:** Review the log file for underlying causes.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06595: Failed to update request history for request {0}.**

**Cause:** Failed to update request history for request.

**Action:** Review the log file for underlying causes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-06610: Failed processing request {0}, {1} stage.**

**Cause:** Failed processing request.

**Action:** Review the log file for underlying causes.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06617: Failed to extract event information for event name {0}.**

**Cause:** Failed to extract event information for event name.

**Action:** Review the log file for underlying causes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-06618: Error while dispatching event {0}, request {1}, to request listeners.**

**Cause:** Error while dispatching event to request listeners.

**Action:** Review the log file for underlying causes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-06619: Error during trigger processing of event {0}, application {1}.**

**Cause:** Error during trigger processing of event for the application.

**Action:** Review the log file for underlying causes.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**ESS-06620: Failed to get an endpoint for application {0}.**

**Cause:** Failed to get an endpoint for application. Endpoint not available for processing.

**Action:** Make sure endpoint application is available for processing.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06621: Error while calling endpoint for application {0}.**

**Cause:** Failure encountered while calling endpoint for application.

**Action:** Ensure application is deployed and running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-06622: Error while calling endpoint for application {0}, method {1}.**

**Cause:** Error occurred while calling endpoint for application.

**Action:** Ensure application is deployed and running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-06640: Error encountered by worker.**

**Cause:** Error encountered by worker.

**Action:** Review the log file for underlying causes.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06641: Failed to schedule additional work. {0}**

**Cause:** Failed to schedule additional work.

**Action:** Review the log file for underlying causes.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06700: Failed to check in event work {0} for {1} event, request {2}.**

**Cause:** The event work for the given event could not be checked in or deleted.

**Action:** The event work operation should be automatically retried, so no action is necessary.

**Level:** 1

**Type:** WARNING

---

**Impact:** Other

**ESS-06701: Failed to publish request listener event during processing of work {0}.  
Event: {1}, request: {2}.**

**Cause:** An error occurred during an attempt to publish an event to be sent to the event listener of a request.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06710: Unable to dispatch event {0} for request {1} to event listener.**

**Cause:** The event work is not checked out to a specific instance.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06711: Error invoking event listener for request {0}. Event name: {1}, event request: {2}**

**Cause:** Event listener was invoked and failed with an error.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06712: Event listener action for event {0}, request {1}. Status: [{2}], Message: [{3}]**

**Cause:** Information from EventListenerAction returned by the listener.

**Action:** None

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06713: Delivery limit reached for event {0}, request {1}. No further delivery attempts will be made.**

**Cause:** The event has been delivered to the event listener the maximum allowed times.

**Action:** None

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06714: Failed to authenticate user {0}. Dispatch event {1} for request {2} as an unprivileged call. Error: [{3}]**

---

**Cause:** Failed to authenticate user. Event listener will be invoked in an unprivileged block.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06800: Error handling {0} event for request {1} by request dispatcher.**

**Cause:** Error handling event for request by request dispatcher.

**Action:** Review the log for underlying causes.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06805: Request {0} is in illegal state {1} ({2}). Skipping processing and deleting from wait queue.**

**Cause:** Request is in illegal state. Skipping processing and deleting from wait queue.

**Action:** Review the log for underlying causes.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06806: Request {0} not found in runtime store. Skipping processing and deleting from wait queue.**

**Cause:** Request not found in runtime store. Skipping processing and deleting from wait queue.

**Action:** No Action is necessary.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06807: Error occurred while dispatching requests.**

**Cause:** An error occurred while attempting to dispatch one or more requests.

**Action:** Review the log file to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06816: Error processing request {0} by request dispatcher.**

**Cause:** An error occurred during the request dispatching process for the given request.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

---

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06817: No subrequests exist for paused request {0}. Request execution will be resumed.**

**Cause:** No sub-requests are active for this paused request.

**Action:** None

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**ESS-06820: Failed to retrieve Schedule for request {1}.**

**Cause:** Failed to retrieve Schedule needed to determine the next schedule execution time.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-06821: Failed to update error information for request {0}. {1}**

**Cause:** Failed to update the error information for a request.

**Action:** Review the log file for to determine the nature of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-06830: Error occurred processing post-execution work for request {0}. WorkId: {1}**

**Cause:** An error occurred while processing a post-execution work unit.

**Action:** Review the log file to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-06831: Cannot process post-execution work for request {0}. State is {1}, process phase is {2}. WorkId: {3}**

**Cause:** The request state and/or process phase prevents a post-execution work unit for a request from being processed. The work will be discarded.

**Action:** None

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-07000: Error handling {0} event for request {1} by request processor.**

---

**Cause:** Error handling event for request by request processor.

**Action:** Review the log file for underlying causes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-07001: Error processing request {0}.**

**Cause:** Error processing request.

**Action:** Review the log file for underlying causes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-07002: Failed to obtain system executable wrapper for request {0}.**

**Cause:** Possible causes include unknown job type, user login error, classloading issues...

**Action:** Review the causeBy exception clause to determine the specific failure.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**ESS-07003: Execution warning for request {0}. Reason: {1}**

**Cause:** Execution error warning for request.

**Action:** Review the log file for underlying causes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-07004: Execution error for request {0}. Reason: {1}**

**Cause:** Execution error for request.

**Action:** Review the log file for underlying causes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-07005: Execution cancelled for request {0}. Reason: {1}**

**Cause:** The job execution has been cancelled.

**Action:** Check the cause for the exception. If the cause is not given, you can adjust logging level to fine and retry it.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-07006: Failed to cancel request {0}.**



---

**Cause:** Failed to cancel request.

**Action:** Review the log file for underlying causes.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-07012: Invalid action ({0}) returned from pre-process callout for request {1}.  
Setting to {2} state.**

**Cause:** Invalid action returned from pre-process callout for the request.

**Action:** Review the log for underlying causes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-07013: Invalid action ({0}) returned from post-process callout for request {1}.  
Setting to {2} state.**

**Cause:** Invalid action returned from pre-process callout for the request.

**Action:** Review the log for underlying causes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-07014: Delaying processing of request {0} by {1} minutes.**

**Cause:** The pre-process callback return value indicated that request processing should be delayed.

**Action:** No action required. The request will be retried after the delay.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**ESS-07015: Error occurred during cleanup of database job for request {0}. {1}**

**Cause:** An error occurred while performing post-execution clean tasks for an Oracle Scheduler job used to execute a SQL job request.

**Action:** Review the log file for attached exceptions to determine the nature of the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-07016: Failed processing update event for request {0}.**

**Cause:** An error occurred processing an update event.

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** WARNING

---

**Impact:** Other

**ESS-07017: Cannot process update event for request {0} in state {1}.**

**Cause:** The request is in an illegal state for an update event.

**Action:** None

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-07018: Cannot process update event for request {0} in state {1}.**

**Cause:** The request is in an illegal state for an update event.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-07019: Error processing request {0}. {1}**

**Cause:** Error processing request.

**Action:** Review the log file for underlying causes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-07020: Failed get an endpoint for application {0}.**

**Cause:** Failed get an endpoint for application.

**Action:** No action is necessary.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-07021: Invalid work unit action for request {0}, work unit {1}, action {2}.**

**Cause:** Invalid work unit action for request.

**Action:** Report the failure to Oracle support as it could be a bug in ESS.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-07022: Invalid endpoint action for request {0}, stage {1}, action {2}.**

**Cause:** Invalid endpoint action for request.

**Action:** Report the failure to oracle support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-07023: Error processing timed out requests. {0}.**

---

**Cause:** An error occurred attempting to process a timed out request.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-07024: Rejecting update event for request {0}. {1}. Result status = {2}. Result message = {3}. Message body = {4}.**

**Cause:** The request is in an illegal state for an update event.

**Action:** None

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-07025: Failed to allocate an asynchronous worker for request {0}. ({1}, {2}). ExecutionType = {3}.**

**Cause:** Failed to allocate an asynchronous worker.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-07026: Failed to release an asynchronous worker for request {0}. ({1}, {2}). ExecutionType = {3}.**

**Cause:** Failed to release an asynchronous worker.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-07027: Failed to terminate request {0}.**

**Cause:** Failed to terminate request.

**Action:** Review the log file for underlying causes.n

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-07028: Error invoking or executing application endpoint for request {0}. Check application status of logical application {1}.**

**Cause:** Error occurred invoking or executing in application's endpoint.

**Action:** Check that the application is deployed and running successfully.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**ESS-07029: Asynchronous throttle configuration does not exist for Workshift = {0}.**

**Cause:** The async throttle configuration does not exist for the workshift.

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-07030: Recovering update work unit {0} for request {1} that may have been executing. There is a possibility of redelivery.**

**Cause:** An update event is being recovered from a stage where redelivery is possible.

**Action:** None

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-07031: Error in transaction processing for request {0}. The transaction is eligible to be retried**

**Cause:** A recoverable SQL error was encountered

**Action:** None

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-07500: Error parsing attribute {0}. {1}**

**Cause:** An error is present in a command attribute format.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-07501: Error starting command worker. {0}**

**Cause:** An error occurred starting a command worker.

**Action:** None

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-07502: Failed to set request state to VALIDATION\_FAILED for request {0}. {1}**

**Cause:** An error occurred while setting the state of the request to VALIDATION\_FAILED.

**Action:** None

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**ESS-07503: Document conversion failed for command work {0}. Command type: {1}, request: {2}.**

**Cause:** Failed converting DOC Document for command work.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-07505: Validation of request {0} failed.**

**Cause:** Validation of the request has failed.

**Action:** Check logs and error information for details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-07506: Failed to check in command work {0} for {1} command, request {2}.**

**Cause:** The work for the given command could not be checked in or deleted.

**Action:** The command work operation should be automatically retried, so no action is necessary.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-07507: Unknown command type, {0}, for command work {1}.**

**Cause:** The command work has an unknown command type.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-07508: Error calling endpoint for application {0} during processing of {1} command for request {2}.**

**Cause:** The command work has an unknown command type.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-07509: Failed to execute command {0} for request {1} for command work {2}.**

**Cause:** An error occurred executing the command.

**Action:** Review the log file for the cause.

**Level:** 1

**Type:** WARNING

---

**Impact:** Other

**ESS-07510: Failed to update command {0} for request {1} for command work {2}.**

**Cause:** An error occurred updating the command.

**Action:** Review the log file for the cause.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-07540: Failed to complete request {0} during group cleanup for execution group {1}, isolation group {2}.**

**Cause:** Clean up of request failed during execution group removal.

**Action:** None. The action will be automatically retried.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-07541: Failed to get list of incomplete requests for execution group {0}, isolation group {1}.**

**Cause:** Retrieving requests during execution group removal failed.

**Action:** None. The action will be automatically retried.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-07542: Failed to remove registrations for execution group {0}, isolationGroup{1}.**

**Cause:** Removing instance or application registrations failed during execution group removal.

**Action:** None. The action will be automatically retried.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-07543: Failed to lock recovery delete table.**

**Cause:** Failed to lock the recovery delete table.

**Action:** None. The action will be automatically retried.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-07544: Failed to insert row for process group {0}, isolationGroup {1}, action {2}.**

**Cause:** Failed to insert the entry into recovery delete table.

**Action:** None. The action will be automatically retried.

**Level:** 1

**Type:** WARNING

---

**Impact:** Other

**ESS-07545: Failed to delete row for process group {0}, isolationGroup {1}, action {2}.**

**Cause:** Failed to delete the entry from recovery delete table.

**Action:** None. The action will be automatically retried.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-07546: Failed to query row for process group {0}, isolationGroup {1}, action {2}.**

**Cause:** Failed to query for the entry from recovery delete table.

**Action:** None. The action will be automatically retried.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ESS-08000: The value of filter is null.**

**Cause:** The value of filter is null

**Action:** Provide the correct privilege name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-08001: Invalid sec filter comparator.**

**Cause:** Invalid sec filter comparator.

**Action:** Choose correct comparator, GRANTED.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ESS-09000: Translation service with resource bundles {0} for Locale {1} can not be performed due to runtime error.**

**Cause:** ESS runtime encountered a failure for the given translation request.

**Action:** Correct the bundle id, make sure it exists in the application environment.

**Level:** 1

**Type:** TRACE

**Impact:** Programmatic

**ESS-09001: Message with requested key {0} is not found in the associated resource bundles.**

**Cause:** Message with the requested key is not found in the resource bundle.

**Action:** Make sure the key is entered correctly.

**Level:** 1

**Type:** TRACE

---

**Impact:** Programmatic

**ESS-09002: {0}is not a valid {1} implementation.**

**Cause:** The implementation class is not of expected interface type.

**Action:** Make sure the implementation class implements the proper interface.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-09003: Failed to instantiate the translation service factory implementation {0}.**

**Cause:** Error while instantiating an instance of translation service factory.

**Action:** Check the log to find exception details.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-09004: Failed to retrieve a valid instance of underlying oracle.javatools  
ResourceBundleManager. Design time metadata translation is not supported.**

**Cause:** Error while instantiating an instance of  
oracle.javatools.resourcebundle.ResourceBundleManager.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-09005: Encountered MDS exception while performing MDS operations.**

**Cause:** Encountered MDS exception.

**Action:** Check the exception for details.

**Level:** 1

**Type:** TRACE

**Impact:** Programmatic

**ESS-09400: Encountered an execution context exception.**

**Cause:** Encountered exception while invoking DMS execution context API(s).

**Action:** Check exception stack trace for details.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**ESS-09402: Failed to compile recurrence expression.**

**Cause:** Failed to compile recurrence expression

**Action:** Correct the invalid recurrence expression.

**Level:** 1

**Type:** ERROR



---

**Impact:** Programmatic

**ESS-09403: Schedule list limit must be a non-negative integer.**

**Cause:** Schedule List limit is invalid.

**Action:** List limit must be a non-negative integer.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-09404: Schedule list begin date cannot be null.**

**Cause:** Invalid Null Schedule Begin date.

**Action:** Provide a non-null begin date for the schedule.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ESS-09405: Schedule begin date can not be after end date.**

**Cause:** Begin Date for the schedule is after the end date.

**Action:** Correct the invalid begin date or end date.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic



---

## FED-10102 to FED-20102

**FED-10102: The LDAP connection settings have not been configured.**

**Cause:** The configuration properties for LDAP connection have not been set.

**Action:** Enter the LDAP connection settings in the Oracle Identity Federation Data Stores configuration..

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10104: A name identifier update using protocol version {0} cannot be performed on a federation created with protocol version {1}**

**Cause:** Unable to perform a name identifier update with the current version.

**Action:** Try using a different protocol version.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10105: Attribute Service location not found in provider metadata for {0}**

**Cause:** Attribute service location was not in the provider metadata.

**Action:** Verify that the provider metadata contains the attribute service location.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10106: AssertionID service location not found in provider metadata for {0}**

**Cause:** AssertionID service location was not in the provider metadata.

**Action:** Verify that the provider metadata contains the AssertionID service location.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10107: Federation does not exist: cannot complete the requested operation**

**Cause:** Federation does not exist for the user with the peer provider.

**Action:** Verify that the federation exists, or configure the server to create one.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10108: Cannot create federation with opaque name identifier: invalid data store**

**Cause:** An opaque name identifier was used without a federation data store.

**Action:** Use a federation data store when an opaque identifier is used or configure Oracle Identity Federation to use a non-opaque Name ID.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10109: The name identifier format is not correctly configured: {0}**

**Cause:** The name identifier format was enabled, but it was not mapped to a user attribute.

**Action:** Map the name identifier format to a user attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10110: Cannot find service provider metadata for Affiliation={0};affiliationID type={1}**

**Cause:** The federation did not contain a service provider that is part of the affiliation.

**Action:** Import the metadata of a service provider that is a member of the affiliation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10111: Cannot find provider metadata for providerID={0}; providerID type={1}**

**Cause:** There was no metadata available for the provider with the given ID.

**Action:** Verify that the provider ID is correct or that the provider is included in the federation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10112: No default identity provider was set for the single sign-on operation.**

**Cause:** The default single sign-on identity provider configuration property was not set.

**Action:** Set the default single sign-on identity provider in the Oracle Identity Federation configuration.

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**FED-10113: Federation termination protocol not enabled**

**Cause:** The federation termination protocol was not enabled.

**Action:** Verify that the federation termination protocol is enabled.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10114: NameIDPolicy not supported: {0}**

**Cause:** The NameIDPolicy requested is not supported or not enabled.

**Action:** Check that the requested name identifier format is supported and enabled.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10115: Cannot find the AssertionConsumerServiceURL in the requester metadata.**

**Cause:** Could not find the AssertionConsumerServiceURL in the requester's provider metadata.

**Action:** Verify that the AssertionConsumerServiceURL is present in the provider metadata.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10117: Provider is not enabled: {0}**

**Cause:** The peer provider is not enabled in the federation.

**Action:** Verify that the provider is enabled.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10118: Single sign-on binding unknown: {0}**

**Cause:** The single sign-on binding is not one of the known bindings.

**Action:** Verify that the single sign-on binding is one of the bindings known by Oracle Identity Federation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10119: The specified binding ({0}) for single sign-on with {1} is not supported by the peer provider.**

**Cause:** The binding specified is not one of the bindings supported by the peer provider.

---

**Action:** Verify that the binding specified is supported by the peer provider.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10120: Unable to find a suitable binding to send the request.**

**Cause:** Oracle Identity Federation could not find a binding to send the request.

**Action:** Verify that Oracle Identity Federation and the remote providers have a common binding for the profile.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10121: Unable to start identity provider-initiated single sign-on: Unknown metadata version.**

**Cause:** The service provider metadata version was not recognized.

**Action:** Verify that the metadata version is one of the versions supported by the identity provider.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10122: Unable to start identity provider-initiated single sign-on: SP {0} does not belong to affiliation {1}.**

**Cause:** The target service provider was not part of the affiliation.

**Action:** Check the provider federation to verify that the target service provider is in the affiliation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10123: Unknown NameIDPolicy {0}**

**Cause:** The NameIDPolicy is not one of the known policies.

**Action:** Verify that the NameIDPolicy is one of the policies that is accepted by Oracle Identity Federation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10124: User cannot be located for federation with provider ID {0} and name identifier {1}**

**Cause:** Federation does not exist between the user, Oracle Identity Federation and the given peer provider.

**Action:** Verify that the federation exists, or configure the server to create one.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**FED-10125: AssertionID responder functionality is not enabled.**

**Cause:** The AssertionID responder functionality has been disabled in the Oracle Identity Federation configuration.

**Action:** Enable the AssertionID responder functionality.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10126: Attribute Query requester functionality is not enabled.**

**Cause:** The Attribute Query requester functionality has been disabled in the Oracle Identity Federation configuration.

**Action:** Enable the AttributeQuery requester functionality.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10127: AssertionID requester functionality is not enabled.**

**Cause:** The AssertionID requester functionality has been disabled in the Oracle Identity Federation configuration.

**Action:** Enable the AssertionID requester functionality.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10128: Attribute Query responder functionalities are not enabled.**

**Cause:** The Attribute Query responder functionality has been disabled in the Oracle Identity Federation configuration.

**Action:** Verify that the Attribute Query responder functionality is enabled.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10129: Authentication Query responder functionalities are not enabled.**

**Cause:** The Authentication Query responder functionality has been disabled in the Oracle Identity Federation configuration.

**Action:** Verify that the Authentication Query requester functionality is enabled.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10130: No metadata exists for protocol {0} used by provider {1}**

**Cause:** Metadata for this provider was not found.

**Action:** Load metadata for the provider.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10131: Unknown service provider: {0}**

**Cause:** The service provider is not in the federation.

**Action:** Verify the trusted provider federation configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10132: Single sign-on functionality is not enabled**

**Cause:** The single sign-on functionality has been disabled in the Oracle Identity Federation configuration.

**Action:** Verify that the single sign-on functionality is enabled.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10133: Identity provider functionality is not enabled.**

**Cause:** The identity provider functionality has been disabled in the Oracle Identity Federation configuration.

**Action:** Verify that the identity provider functionality is enabled.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10134: Incoming authentication request uses a protocol profile which is not enabled: {0}**

**Cause:** Protocol profile has not been enabled in the Oracle Identity Federation configuration.

**Action:** Verify that the profile used for the authentication request is enabled.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10135: Incoming request uses a protocol profile which is not enabled: {0}**

**Cause:** Protocol profile has not been enabled in the Oracle Identity Federation configuration.

**Action:** Verify that profile used for the incoming request is enabled.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10136: Incoming assertion uses a protocol profile which is not enabled: {0}**



---

**Cause:** Protocol profile has not been enabled in the Oracle Identity Federation configuration.

**Action:** Verify that the profile used in the assertion is enabled.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10137: Liberty ID-FF 1.1 protocol functionality is not enabled.**

**Cause:** The Liberty ID-FF version 1.1 protocol has been disabled in the Oracle Identity Federation configuration.

**Action:** Verify that the Liberty ID-FF version 1.1 protocol is enabled.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10138: Liberty ID-FF 1.2 protocol functionality is not enabled.**

**Cause:** The Liberty ID-FF version 1.2 protocol has been disabled in the Oracle Identity Federation configuration.

**Action:** Verify that the Liberty ID-FF version 1.2 protocol is enabled.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10139: Register Name Identifier protocol is disabled.**

**Cause:** The Register Name Identifier protocol has been disabled in the Oracle Identity Federation configuration.

**Action:** Verify that the Register Name IdentifierProtocol is enabled.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10140: SAML 1.0 protocol functionality is not enabled.**

**Cause:** The SAML version 1.0 protocol has been disabled in the Oracle Identity Federation configuration.

**Action:** Verify that the SAML version 1.0 protocol is enabled.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10141: SAML 1.1 protocol functionality is not enabled.**

**Cause:** The SAML version 1.1 protocol has been disabled in the Oracle Identity Federation configuration.

**Action:** Verify that the SAML version 1.1 protocol is enabled.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**FED-10142: SAML 2.0 protocol functionality is not enabled.**

**Cause:** The SAML version 2.0 protocol has been disabled in the Oracle Identity Federation configuration.

**Action:** Verify that the SAML version 2.0 protocol is enabled.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10143: Service provider functionality is not enabled**

**Cause:** Service provider functionality has been disabled in the Oracle Identity Federation configuration

**Action:** Verify that service provider functionality is enabled.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10146: Could not locate the X.509 certificate for {0}, for use {1}**

**Cause:** The X.509 certificate for the given provider and for the specified use was not found.

**Action:** Check the metadata and the configuration for the given provider.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10147: Invalid federations configuration file for providerID: {0}.**

**Cause:** The federations configuration cot.xml file has an invalid or missing XML element.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10152: LDAP BindDN or password is incorrect.**

**Cause:** The LDAP BindDN or password was configured incorrectly.

**Action:** Check the LDAP configuration entry for BindDN and bind password.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**FED-10153: Unable to read the federations configuration file.**

**Cause:** The federations configuration file cot.xml is invalid, missing or has incorrect permissions.

**Action:** Verify the valid existence of the cot.xml file.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**FED-10154: Unable to read the configuration file: {0}.**

**Cause:** One of the configuration files is invalid, missing or has incorrect permissions

**Action:** Verify the valid existence of configuration file.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**FED-10155: Unable to write to the federations configuration file.**

**Cause:** The file cot.xml could not be written to.

**Action:** Ensure that the cot.xml is present in the configuration directory and that it is writeable.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**FED-10158: Unable to find the exception handler mapping for the exception {0}.**

**Cause:** ExceptionHandler mapping for this exception was missing in the configuration file.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**FED-10159: Unable to find the request handler mapping for this URL {0}.**

**Cause:** RequestHandler mapping for this URL was missing in the configuration file.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**FED-10160: Unable to find the response handler mapping for this event response {0}.**

**Cause:** ResponseHandler mapping for this EventResponse cannot be found in configuration file.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**FED-10161: Unable to locate a mapping for {0}.**

---

**Cause:** Mapping for this class could not be located.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**FED-10162: Data source configuration file is invalid: {0} has an invalid number of {1} elements in dependencies.**

**Cause:** Configuration for data source is invalid in configuration file.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**FED-10163: Invalid configuration or configuration not found for: {0}.**

**Cause:** Configuration for this Oracle Identity Federation Server instance is invalid or missing.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**FED-10164: Invalid peer provider configuration for: {0}**

**Cause:** Metadata for this peer provider is invalid.

**Action:** Load metadata for this peer provider.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**FED-10168: DiscoveryProvider was not found for {0}.**

**Cause:** A DiscoveryProvider for this type of provider is not configured.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**FED-10169: EventFactory was not found for {0}.**

**Cause:** EventFactory for this class was not registered.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**FED-10170: Handler was not found for URL: {0}.**

---

**Cause:** Handler for this response is missing from configuration file.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**FED-10171: Message-to-Event mapping was not found for this SAML protocol message of version {0}.**

**Cause:** Message-to-Event mapping is missing for this SAML Protocol Message.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**FED-10174: Property was not found: {0}.**

**Cause:** Property is not set in configuration file.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**FED-10175: First package-search-order is used as default package search order.**

**Cause:** Group of package-search-order was found in configuration file.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**FED-10178: Metadata version parameter unknown: {0}**

**Cause:** The metadata version parameter is unknown.

**Action:** Check that the metadata version parameter is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10179: Mapping was not defined for action {0}**

**Cause:** Mapping for the specified action was not defined in the configuration.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10180: Business Processing Plugin error: {0} does not implement OperationListener**

---

**Cause:** Business Processing Plugin configuration is incorrect.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**FED-10181: Property is not type of Boolean: {0}**

**Cause:** Property was not correctly set in configuration file.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**FED-10182: Property is not of type Long: {0}**

**Cause:** Property was not correctly set in configuration file.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**FED-10183: Property is not of type Set: {0}**

**Cause:** Property was not correctly set in configuration file.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**FED-10184: Property is not of type List: {0}**

**Cause:** Property was not correctly set in configuration file.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**FED-10185: Property is not of type Map: {0}**

**Cause:** Property was not correctly set in configuration file.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**FED-10186: Property is not of type String: {0}**

**Cause:** Property was not correctly set in configuration file.

**Action:** Contact Oracle Support Services to rectify the issue.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**FED-10187: Logout configuration error: webContext (= {0}) and/or relativePath (= {1}) for logout are incorrect.**

**Cause:** The webContext and/or relativePath for logout were incorrectly configured.

**Action:** Verify that the webContext and relativePath for logout are correctly configured.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10188: Invalid name identifier format**

**Cause:** The name identifier format is invalid, or custom name ID format is disabled.

**Action:** Verify that the name identifier format is valid, or that customizable name ID format is enabled.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10189: Attribute authority does not support any appropriate name identifier formats.**

**Cause:** The attribute authority does not support the requested subject name identifier format.

**Action:** Either use a subject format other than "userid", or use a different attribute authority.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10190: Identity provider is not configured for single sign-on: {0}.**

**Cause:** The identity provider was not configured to support single sign-on.

**Action:** Verify that the identity provider is configured to support single sign-on protocols.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10191: The service provider integration module is not enabled: {0}.**

**Cause:** The service provider integration module is disabled in the Oracle Identity Federation configuration.

**Action:** Enable the appropriate service provider integration module.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**FED-10192: Oracle Access Server SDK could not be initialized.**

**Cause:** There was an error during initialization of the Oracle Access Manager SDK.

**Action:** Check the Access Server SDK logs for diagnostic information.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**FED-10193: Error while configuring OAM: {0}**

**Cause:** An error occurred while configuring Oracle Access Manager.

**Action:** Check the Access Server SDK logs for diagnostic information.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10194: Error while configuring the OAM Authentication Schemes: {0}**

**Cause:** An error occurred while configuring the Authentication Schemes in Oracle Access Manager.

**Action:** Check the Access Server SDK logs for diagnostic information.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10195: Authentication engine configuration error: WebContext={0} ; RelativePath={1}**

**Cause:** The Web Context and/or the Relative Path properties of the authentication engine configuration were not set.

**Action:** Check that the authentication engine configuration defines the required web context and relative path.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10196: Service provider integration module configuration error: WebContext={0} ; RelativePath={1}**

**Cause:** The Web Context and/or the Relative Path properties of the service provider integration module configuration were not set.

**Action:** Check that the service provider integration module configuration defines the required web context and relative path.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration



---

**FED-10197: The service provider anonymous user ID was not set.**

**Cause:** The Oracle Identity Federation server needed to create a session of type anonymous but the Anonymous User ID is not set in the configuration.

**Action:** Set the Anonymous User ID in the Oracle Identity Federation configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10198: Could not locate the configuration element in the database for: {0}**

**Cause:** The configuration element was not present in the database.

**Action:** Check the RDBMS Configuration table to see if the configuration element is present.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**FED-10199: SQL error while executing configuration update: {0}**

**Cause:** An SQL exception occurred while trying to perform a configuration update.

**Action:** Check the logs and the RDBMS Configuration Data Store settings.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10200: XML error while saving configuration data to database: {0}**

**Cause:** An XML error occurred while saving XML configuration data to the RDBMS Configuration Data Store.

**Action:** Check the XML configuration files for incorrect format.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10201: Unknown certificate use parameter: {0}**

**Cause:** The requested certificate use parameter was not recognized.

**Action:** Check that the requested certificate use parameter is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FED-10202: Unknown certificate type parameter: {0}**

**Cause:** The requested certificate type parameter was not recognized.

**Action:** Check that the requested certificate type parameter is correct.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**FED-10203: Property could not be retrieved from the Credential Store Framework: {0}**

**Cause:** The Credential Store Framework did not refresh.

**Action:** Set the credentials again using Enterprise Manager or restart the WLS Managed Server where Oracle Identity Federation is running.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**FED-11000: Unable to import metadata for ProviderID: {0}**

**Cause:** Metadata could not be imported due to existing metadata for this provider.

**Action:** Remove the existing metadata for this provider and try importing the metadata again.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**FED-11002: Cannot retrieve the unique user federation ID from the federation record.**

**Cause:** Could not retrieve the unique user federation ID from the federation record.

**Action:** Verify that the federation record is correctly formatted.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**FED-11004: SQL error while retrieving user attributes.**

**Cause:** User may not have the necessary privileges to execute the query.

**Action:** Verify that the configured database user has the necessary privileges to execute the query.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**FED-11005: Error while deserializing data, mismatched classes while reading database records: expected {0}, got {1}**

**Cause:** The data could not be deserialized.

**Action:** Check that the entry contains valid data.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**FED-11008: RequestHandlerMapping {0} already exists.**

**Cause:** RequestHandlerMapping was already present.

**Action:** No Action.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**FED-11009: ResponseHandlerMapping {0} already exists.**

**Cause:** ResponseHandlerMapping was already present.

**Action:** No Action.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**FED-11010: Replacement RequestHandlerMapping is: {0}.**

**Cause:** RequestHandlerMapping was replaced with the new RequestHandlerMapping.

**Action:** No Action.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**FED-11011: Replacement ResponseHandlerMapping is: {0}.**

**Cause:** ResponseHandlerMapping was replaced with the new ResponseHandlerMapping.

**Action:** No Action.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**FED-11013: SQL error while interacting with the database.**

**Cause:** SQL query may not have been properly formed.

**Action:** Check log entries and database connection configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**FED-11017: Unexpected error occurred while querying LDAP server: {0}**

**Cause:** Incorrect LDAP query values.

**Action:** Verify the query values are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**FED-11018: Unexpected error occurred while connecting to the database {0}**

**Cause:** Incorrect database connection information.

**Action:** Verify that the RDBMS connection settings are correct in the configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**FED-11019: Unexpected error occurred while connecting to LDAP server: {0}**

**Cause:** Incorrect LDAP connection information.

**Action:** Verify that the LDAP connection settings are correct in the configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**FED-11020: Unexpected error occurred while querying RDBMS server: {0}**

**Cause:** Incorrect SQL query values.

**Action:** Verify that the SQL query values are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**FED-11021: Invalid comparator: {0}**

**Cause:** Invalid comparator in LDAP search filter condition.

**Action:** Verify that the comparator is supported.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**FED-11022: Invalid operator: {0}**

**Cause:** Invalid operator in LDAP search filter condition.

**Action:** Verify that the operator is supported.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**FED-11700: Cannot connect to the LDAP server.**

**Cause:** The LDAP credentials were incorrect.

**Action:** Verify the LDAP credentials in the Oracle Identity Federation configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Network

---

**FED-11701: Cannot connect to the database.**

**Cause:** The network is down.

**Action:** Verify that the network connection is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**FED-11703: Exception while trying to connect to LDAP server.**

**Cause:** Oracle Identity Federation could not open a connection to the LDAP server.

**Action:** Verify the connection settings in the Oracle Identity Federation configuration and that LDAP server is up.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**FED-11704: Cannot close LDAP connection.**

**Cause:** Problem while closing the LDAP connection.

**Action:** Check the LDAP server logs.

**Level:** 1

**Type:** WARNING

**Impact:** Network

**FED-12000: XML time value is empty.**

**Cause:** An empty string was passed in as an XML time value attribute.

**Action:** Verify that none of the time value attributes are empty.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12003: Unsupported handler parameter type: {0}**

**Cause:** Parameter type was not supported.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**FED-12004: UTF-8 encoding is not supported: {0}**

**Cause:** UTF-8 encoding was not supported in the String class.

**Action:** Verify the character encodings supported by the JVM.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

---

**FED-12006: Unsupported attribute value type Object {0}**

**Cause:** Attribute value object received from the peer provider was not of a supported type.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**FED-12007: Data Object {0} is no longer valid.**

**Cause:** Object was destroyed.

**Action:** No Action.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**FED-12009: Multiple certificates are found for the public key, attempting to select a valid one.**

**Cause:** Multiple certificates were present in the certificate store.

**Action:** No Action.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**FED-12010: Previous RequestHandlerMapping is replaced with the new RequestHandlerMapping for URL {0}.**

**Cause:** New RequestHandlerMapping was found for this URL.

**Action:** No Action.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**FED-12011: Previous ResponseHandlerMapping is replaced with the new ResponseHandlerMapping for URL {0}.**

**Cause:** New ResponseHandlerMapping was found for this URL.

**Action:** No Action.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**FED-12012: Unsupported type for attribute value {0}, type={1}**

**Cause:** One of the retrieved values for the attribute was of an unsupported type.

**Action:** No Action.

**Level:** 1

**Type:** WARNING

---

**Impact:** Other

**FED-12013: Discovery Create Exception: unable to create object in the repository: {0}**

**Cause:** Unable to create a data object in the repository.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12014: Discovery Finder Exception: unable to locate object in the repository: {0}**

**Cause:** Unable to locate a data object in the repository.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12015: Federation Exception: error while accessing or creating the federation record of a user: {0}**

**Cause:** An error occurred while accessing or creating the federation record of a user.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12016: Message Creation Exception: unable to create the message: {0}**

**Cause:** Could not create the protocol message.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12017: Communication Exception: unable to communicate with directory or naming service: {0}**

**Cause:** Could not communicate with directory or naming service.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12018: Duplicate Entry Exception: duplicate entry in the data store: {0}**

**Cause:** There was a duplicate entry in the data store.

**Action:** Check the data store for duplicate entries.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**FED-12019: Transformer Exception: unable to transform message to or from XML: {0}**

**Cause:** There was a problem transforming the message to or from XML.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12020: Translation Exception: unable to translate message: {0}.**

**Cause:** There was a problem marshalling or unmarshalling the message.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12026: No Such Algorithm Exception: cryptographic algorithm was not recognized: {0}**

**Cause:** JCE provider was incorrectly configured.

**Action:** Check that the JCE provider is configured correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12028: Notification Processing Exception: could not call the notifier: {0}.**

**Cause:** Could not process the notification.

**Action:** Please check any plugins or listeners, or contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12029: Attribute Processing Exception: error when processing attributes for mapping and filtering: {0}**

**Cause:** Could not process attributes for mapping and filtering.

**Action:** Check the configuration for assertion attribute mapping and filtering.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12030: IOException: {0}**

**Cause:** There was an error during Input/Output an operation.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR



---

**Impact:** Other

**FED-12031: NamingException: error while interacting with an LDAP server or JNDI module**

**Cause:** There was an error during interaction with an LDAP or JNDI module

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12032: InterruptedException: thread interrupt occurred during sleep() {0}**

**Cause:** Thread interrupt occurred during sleep() method.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**FED-12033: Invocation Target Exception: error while invoking method {0}**

**Cause:** There was an error while invoking a method.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12034: No Such Method Exception: a particular method could not be found {0}**

**Cause:** There was an error while finding a method.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12036: Persistence Exception: error while creating or modifying data in the backend store {0}**

**Cause:** Could not create or modify data in the backend store.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12037: SAML Artifact Exception: {0}**

**Cause:** An error occurred while creating or parsing a SAML Artifact.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**FED-12038: SAML Protocol Exception: {0}**

**Cause:** An error occurred while creating or parsing a SAML Protocol message.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12039: SAML Version Exception: {0}**

**Cause:** An unexpected protocol version was found in a SAML message.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12040: Unsupported Encoding Exception: {0}**

**Cause:** The specified character encoding was not supported.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12041: Unknown Provider Exception: {0}**

**Cause:** The specified peer provider was not known.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12042: Error while generating Oracle Identity Federation provider metadata.**

**Cause:** An error occurred while creating the Oracle Identity Federation provider metadata.

**Action:** Check logs and configuration, or contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12043: Discovery Registration Exception: {0}**

**Cause:** An error occurred while registering a Discovery Provider.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**FED-12044: No Such Discovery Provider Exception: {0}**

**Cause:** Could not find the specified Discovery Provider.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12045: Parser Configuration Exception: {0}**

**Cause:** An error occurred while parsing an XML document.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12047: SAX Exception: {0}**

**Cause:** An error occurred while handling XML documents.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12048: SOAP Exception: {0}**

**Cause:** An error occurred while handling SOAP messages.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12049: Event Exception: {0}**

**Cause:** An error occurred while processing an Event.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12050: Action Listener Init Exception: {0}**

**Cause:** An error occurred during Action Listener initialization.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12051: Mapping Exception: {0}**

---

**Cause:** An error occurred while accessing handler mappings.  
**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12052: No Such Target Exception: {0}**

**Cause:** An error occurred while setting up handler mappings.  
**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12053: SAX Parse Exception: {0}**

**Cause:** An error occurred while parsing an XML document.  
**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12054: Malformed URL Exception: {0}**

**Cause:** Either no legal protocol could be found in a specification string or the string could not be parsed.  
**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12055: No Such Mapping Exception: {0}**

**Cause:** Could not find the handler mapping.  
**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12056: Class Not Found Exception: {0}**

**Cause:** Tried to load class with specified name but could not find definition for such class.  
**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12057: Instantiation Exception: {0}**

---

**Cause:** Tried to load an interface or an abstract class.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12058: Illegal Access Exception: {0}**

**Cause:** Tried to use a field, method, or constructor using reflection, whose definition is not accessible.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12059: Action Registry Exception: {0}**

**Cause:** An error occurred while registering Action Listener.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12060: Service Locator Exception: {0}**

**Cause:** Could not allocate Service Locator.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12061: Algorithm Identifier Exception: {0}**

**Cause:** Inappropriate or unsupported parameters were provided to an algorithm, or an unknown algorithm was requested.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12062: AuditException: {0}**

**Cause:** An error occurred while auditing an event.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12063: OPSS Exception: {0}**

---

**Cause:** An error occurred while using Oracle Platform Security Services libraries.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12064: Exception: {0}**

**Cause:** An error occurred.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12065: Target Exception: {0}**

**Cause:** An error occurred while handling the Target of a Servlet handler.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12066: Servlet Exception: {0}**

**Cause:** An error occurred while initializing or using Servlet.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12067: An HTTP error occurred during SOAP Exchange.**

**Cause:** An HTTP error occurred in SOAP Exchange.

**Action:** Check Oracle Identity Federation logs for HTTP error code.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12068: SAMLRequestException: there was an exception pertaining to the SAML protocol {0}**

**Cause:** An error occurred during the processing of the SAML protocol request.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-12069: Length of input exceeds maximum.**

**Cause:** Length of input exceeds maximum allowed length.

---

**Action:** Check that the incoming request is correctly formatted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FED-13000: Cannot complete the logout process.**

**Cause:** Oracle Identity Federation could not complete the logout process, due to a lack of profile support from the service providers.

**Action:** Perform the logout process using another binding or check that the various peer providers support appropriate logout profiles.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**FED-13002: Cannot serialize an XML message for class {0} child of class {1}**

**Cause:** XML serialization rules were not defined for this message.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**FED-13003: Remove operation not supported.**

**Cause:** The Iterator method remove() was invoked, but is not supported by the implementation.

**Action:** Replace the remove operation with alternate remove option.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**FED-13004: EntrySet operation not supported.**

**Cause:** The SoftHashMap method entrySet() was invoked, but is not supported by the implementation.

**Action:** Replace the call to entrySet() with alternate option.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**FED-13006: Internal Error: Unable to register {0} as a provider for {1}**

**Cause:** Unable to register Discovery Provider.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**FED-13008: Cannot create temporary federations.**

---

**Cause:** Temporary federation store is unavailable.

**Action:** Check configuration of data store. Make sure the data store is up and has space available.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**FED-13009: Cannot have an empty response name.**

**Cause:** Response name was empty.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**FED-13010: Cannot locate class with root name of {0}**

**Cause:** Could not locate class.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**FED-13011: Deregistering object failed.**

**Cause:** Deregistered object does not match expected object.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**FED-13013: Internal Server Error**

**Cause:** Internal Server Error

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**FED-13014: Servlet cannot be configured.**

**Cause:** Servlet configuration failed.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**FED-13017: Initializing {0}**

**Cause:** An internal error has occurred.



---

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**FED-13018: Cannot create a permanent federation record with a transient data store.**

**Cause:** Could not create a permanent federation due to the store being unavailable.

**Action:** Check configuration of data store. Make sure the data store is up and has space available.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**FED-13019: The Authentication Engine ID and Service Provider Engine ID are null.**

**Cause:** The engine did not return an authentication engine ID or a service provider engine ID.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**FED-13020: Both the Authentication Engine ID and Service Provider Engine ID are set.**

**Cause:** The engine returned both an authentication engine ID and an service provider engine ID, where only one should be set.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**FED-13021: Cannot retrieve session during logout flow.**

**Cause:** The session could not be retrieved.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**FED-15002: Cannot find User for UserID {0} in User Data Store.**

**Cause:** The user ID was incorrect or the user record does not exist.

**Action:** Verify that the user ID is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**FED-15003: No value in user record for NameIDPolicy requested: {0}**

**Cause:** There was no value for the requested name identifier type.

**Action:** Verify that name identifier is correct and that the attribute for the requested name identifier exists.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15005: Name identifier registration is already in progress.**

**Cause:** A name identifier registration was in progress when a new registration was initiated.

**Action:** Wait until the name identifier registration finishes.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15006: The single sign-on Assertion has been marked as logged out.**

**Cause:** A non-expired logout request containing the Assertion SessionIndex invalidated the single sign-on assertion.

**Action:** Perform single sign-on again.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15007: The single sign-on Assertion has been marked as logged out.**

**Cause:** A non-expired logout request with no SessionIndex invalidated the single sign-on Assertion.

**Action:** Perform single sign-on again.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15008: A SAML 2.0 name identifier update cannot be performed on a non-SAML 2.0 federation record.**

**Cause:** Tried to perform a SAML 2.0 name identifier update.

**Action:** Try a different protocol version.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15009: An error occurred while dereferencing the SAML 2.0 Artifact: {0} - {1}**

**Cause:** A problem occurred with the SAML 2.0 Artifact.

**Action:** Verify the contents of the SAML 2.0 Artifact.

**Level:** 1

---

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15010: Artifact not present**

**Cause:** The artifact was not present in the request.

**Action:** Verify that the artifact is set in the request

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15011: Cannot find the authentication request associated with the assertion.**

**Cause:** The assertion was replayed.

**Action:** Verify that the assertion has not been replayed.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15012: Cannot select the binding to use to send the request.**

**Cause:** Either the profile was not supported by the remote server, or could not agree with the Oracle Identity Federation server on a common binding.

**Action:** Verify that the remote server and the Oracle Identity Federation server have a common binding.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15013: Cannot select the binding to use to send the response.**

**Cause:** Either the profile was not supported by the remote server, or could not agree with the Oracle Identity Federation server on a common binding.

**Action:** Verify that the remote server and the Oracle Identity Federation server have a common binding.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15015: Error encountered while parsing XML element {0}, child of {1} in incoming XML message.**

**Cause:** Could not parse an XML element from the incoming XML message.

**Action:** Verify that the incoming XML message is valid and correctly formatted.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15018: Error while decoding the authentication result: user ID missing.**

**Cause:** The user ID was missing in the result returned by the authentication process.

---

**Action:** Verify that the user ID is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15020: Name identifier format not supported or missing for attribute responder: {0}**

**Cause:** The name identifier format for the attribute responder was unknown or not accepted.

**Action:** Verify that the name identifier format is one of the formats that is accepted by Oracle Identity Federation.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15021: Name identifier format not supported or missing for authentication responder: {0}**

**Cause:** The name identifier format for the authentication responder was unknown or not accepted.

**Action:** Verify that the name identifier format is one of the formats that is accepted by Oracle Identity Federation.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15022: Error processing response message.**

**Cause:** Was unable to process the response message.

**Action:** Check the Oracle Identity Federation logs for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15024: Query received is not an Attribute Query.**

**Cause:** Internal server error; expected an AttributeQuery message, but received a different message.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15025: Query received is not an Authentication Query.**

**Cause:** Internal server error; expected an AuthenticationQuery message, but received a different message.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

---

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15026: Issuer is not set in the incoming assertion request message: the provider is unknown**

**Cause:** The issuer attribute was not set in the assertion request message.

**Action:** Verify that the issuer attribute is set in the assertion request message.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15027: Issuer is not set in the incoming attribute query message: the provider is unknown**

**Cause:** The issuer attribute was not set in the attribute query message.

**Action:** Verify that the issuer attribute is set in the attribute query message.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15028: Issuer is not set in the incoming authentication query message: the provider is unknown**

**Cause:** The issuer attribute was not set in the authentication query message.

**Action:** Verify that the issuer attribute is set in the authentication query message.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15032: No service provider federation found for provider {0} and name identifier format {1} and name identifier value {2}**

**Cause:** Unable to find the service provider federation corresponding to this provider and name identifier in the federation data store.

**Action:** Check the federation data store to verify that a user identity federation exists with the provider ID and name identifier submitted in the query.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15033: Outgoing assertion protocol profile is not supported or not enabled: {0}**

**Cause:** The outgoing assertion protocol profile was not supported, or enabled.

**Action:** Verify that the assertion protocol profile is supported by Oracle Identity Federation.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15034: Profile is unknown: {0}**

---

**Cause:** The profile was unknown.

**Action:** Verify that the profile version is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15035: Provider ID is missing from the authentication request**

**Cause:** The provider ID was missing from the authentication request.

**Action:** Verify that the provider ID is present in the authentication request.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15037: Request destination is invalid**

**Cause:** The request destination was not a valid URL.

**Action:** Verify that the request destination is a valid URL and correspond to the URL where the request was posted.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15038: Response destination is invalid**

**Cause:** The response destination was not a valid URL.

**Action:** Verify that the response destination is a valid URL and correspond to the URL where the response was posted.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15039: Response does not correspond to any requests**

**Cause:** The response was replayed

**Action:** verify that the response is not replayed

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15040: SSL client certificate required to access SOAP service URL**

**Cause:** No SSL Certificate was presented when accessing the SOAP service.

**Action:** Contact the client to notify that an SSL Certificate is required when accessing the SOAP service.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**FED-15041: Cannot process the incoming request**

**Cause:** Single sign-on is required with peer provider in order to fulfill the current request.

**Action:** Perform single sign-on before attempting to execute the protocol operation.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15042: The InResponseTo header does not correspond to a ManageNameID request.**

**Cause:** The InResponseTo pointed to a message other than ManageNameID.

**Action:** Check with the peer provider.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15043: The received assertion does not contain an AuthenticationStatement**

**Cause:** The assertion did not contain an authentication statement.

**Action:** Contact the peer provider for more details on why the assertion does not contain an authentication statement, and examine the assertion for possible information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15044: The response does not contain any assertions**

**Cause:** The identity provider did not include any assertions in the response.

**Action:** Check that the identity provider includes an assertion with the response.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15046: Unexpected confirmation method: {0}**

**Cause:** Oracle Identity Federation did not recognize the specified confirmation.

**Action:** Check that the confirmation method included in the Assertion is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15047: Unknown authentication context comparison: {0}**

**Cause:** Oracle Identity Federation did not recognize the authentication context comparison.

**Action:** Check that the authentication context comparison included in the authentication request is valid.

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15048: Unknown condition in assertion: {0}.**

**Cause:** Oracle Identity Federation did not recognize the specified condition.

**Action:** Check that the condition included in the assertion is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15049: The contents of the SOAP request body are null. Closing the connection.**

**Cause:** The Oracle Identity Federation server encountered an error while trying to deserialize the incoming message.

**Action:** Check that the message is correctly formatted.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15050: Error while translating an incoming message: cannot parse version from parameters**

**Cause:** The version number was missing or was not a valid integer.

**Action:** Verify that the version parameter is a valid integer.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15052: A time value is invalid**

**Cause:** A string was passed in as a time value that was in an invalid format.

**Action:** Verify that all of the time value attributes are in the correct format.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15053: Invalid major version number: {0}, expected version number: {1}**

**Cause:** Major version did not match the protocol version.

**Action:** Verify that the major version matches the protocol version.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15054: Invalid minor version number: {0}, expected version number: {1}**

**Cause:** Minor version did not match the protocol version.

**Action:** Verify that the minor version matches the protocol version.



---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15055: Invalid version format in the active identity provider federation entry:**  
{0}

**Cause:** The version format was incorrect.

**Action:** Verify that the version parameter is in a valid format.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15056: Invalid version number: {0}**

**Cause:** The version format was incorrect.

**Action:** Verify that the version format is correct. Version should consist of a major part and a minor part separated by a period.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15057: Invalid version: {0}, majorVersion={1}, minorVersion={2}**

**Cause:** Either the major or the minor version was negative.

**Action:** Verify that both the major and minor versions are non-negative.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15058: Error while processing the SOAP envelope.**

**Cause:** Oracle Identity Federation could not process the incoming SOAP envelope.

**Action:** Check that the SOAP envelope format is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15059: Invalid message on the single sign-on service URL.**

**Cause:** A message other than an authentication request was received on the identity provider's single sign-on service URL.

**Action:** Verify that the message sent to the service URL is of type authentication request.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15060: Unknown message parameter: {0}**

---

**Cause:** One of the message parameters was not recognized.

**Action:** Verify that all of the message parameter names are recognized by Oracle Identity Federation.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15061: Unknown message: {0}**

**Cause:** A protocol message was sent on the incorrect service URL.

**Action:** Verify that the message sent to the service URL is of correct type.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15062: Authentication request destination is invalid**

**Cause:** The authentication request destination was not a valid URL.

**Action:** Verify that the authentication responder functionalities are enabled.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15063: Authentication request is expired.**

**Cause:** The authentication request has expired or is not yet valid.

**Action:** Verify the time settings between this server and the peer provider are synchronized. Alternatively the server clock drift can be increased in the Oracle Identity Federation configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15064: Destination URL cannot be validated: {0}**

**Cause:** Destination URL could not be validated.

**Action:** Verify that the URL is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15065: The destination field ({0}) from the SAML 2.0 message does not match the actual request URL {1}**

**Cause:** The message was submitted on a URL that is different from the URL that was specified by the remote provider in the destination field.

**Action:** Contact remote provider.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**FED-15067: Invalid response.**

**Cause:** Protocol response was corrupt.

**Action:** Verify that an XML message is well-formed and correct.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15068: Subject confirmation data {0} differs from artifact {1}**

**Cause:** Subject confirmation data must be the same as the artifact used to obtain the assertion.

**Action:** Verify that the query is properly formed.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15069: Protocol error.**

**Cause:** The received assertion is not a Liberty assertion.

**Action:** Check with the remote provider.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15070: The response cannot be validated.**

**Cause:** Message does not follow the configuration requirements.

**Action:** Check previous error messages for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15071: The server is not included in the AudienceRestrictionCondition.**

**Cause:** The value of the provider ID entry in the federations for the identity provider was incorrect.

**Action:** Verify that the federations entry corresponding to the assertion consumer is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15072: Unknown version in factory request.**

**Cause:** The protocol version sent back from the peer provider is not valid.

**Action:** Verify that the peer provider is configured to the correct protocol version.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**FED-15073: The profile is not supported.**

**Cause:** The profile is not supported or is not enabled.

**Action:** Verify that the profile is supported by Oracle Identity Federation.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15074: The user authenticated at identity provider is different from the user specified in the request message.**

**Cause:** For security reasons, the user authenticated at the identity provider must be the same user that was specified in the request.

**Action:** Verify that the user authenticated at the identity provider is the same user as indicated in the request.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15075: User from existing session ({0}) is different from user received in single sign-on assertion ({1}).**

**Cause:** The user from the existing session was different than the user in the assertion.

**Action:** Action is not allowed.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15076: Cannot validate the SubjectConfirmation's InResponseTo field with the authentication request**

**Cause:** The value of the InResponseTo field did not correspond to an authentication request.

**Action:** Contact administrator, remote server, or Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15078: Unsupported protocol.**

**Cause:** Protocols supported are Liberty 1.x, SAML1.x/2.0 and WS-Federation.

**Action:** Ensure the protocol used is either Liberty 1.x or SAML1.x/2.0 or WS-Federation.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15079: The user previously performed a single sign-on operation with a protocol version ({0}) different from Liberty 1.2.**

---

**Cause:** The federation was created with a single sign-on of different protocol version.

**Action:** Single sign-on can only be performed with same protocol version for the particular service provider

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15080: The user previously performed a single sign-on operation with a protocol version ({0}) different from SAML2.0.**

**Cause:** The federation was created with a single sign-on of different protocol version.

**Action:** Single sign-on can only be performed with same protocol version for the particular service provider

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15081: User tried to initiate protocol with a federation belonging to another user.**

**Cause:** User tried to initiate protocol with a federation belonging to another user.

**Action:** Cannot initiate protocol as another user.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15083: There is no value for a parameter.**

**Cause:** Parameter was sent without a value.

**Action:** Ensure that the parameters are passed with valid value.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Requests/Responses

**FED-15084: The response handler expects an event response that implements Target.**

**Cause:** EventResponse object was not of the type Target.

**Action:** Pass EventResponse object of the type Target to the response handler.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Requests/Responses

**FED-15085: Throwing a runtime exception.**

**Cause:** An internal error has occurred.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

---

**Type:** INCIDENT\_ERROR

**Impact:** Requests/Responses

**FED-15086: Multiple users are found during attribute responder operation for name identifier: {0} and name identifier format = {1}.**

**Cause:** Multiple users were present in the user data store which satisfies the search criteria of name identifier value.

**Action:** Check the data store and correct any errors.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**FED-15088: Multiple users are found during automatic account linking for name identifier: {0} and name identifier format = {1}.**

**Cause:** Multiple users were present in the user data store which satisfies the search criteria of name identifier value.

**Action:** Check the data store and correct any errors.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**FED-15089: User was not found during attribute responder operation for name identifier: {0} and name identifier format = {1}.**

**Cause:** User was not present in the user data store which satisfies the search criteria of name identifier value.

**Action:** Check the data store and correct any errors.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**FED-15091: User was not found during automatic account linking for name identifier: {0} and name identifier format = {1}.**

**Cause:** User was not present in the user data store which satisfies the search criteria of name identifier value.

**Action:** Check the data store and correct any errors.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**FED-15092: RegisterNameIdentifier was not successful.**

**Cause:** Status of RegisterNameIdentifier response was in error.

**Action:** Check global name identifier format of this Oracle Identity Federation server or with the uploaded peer provider metadata.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

---

**FED-15093: A federation for this user does not exist locally.**

**Cause:** The identity provider sent a federation name identifier, but the federation was not found locally.

**Action:** Enable auto account linking property for SAML20 protocol to create the federation for this user. Enable allow federation creation property to create the federation for this user.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**FED-15095: The identity provider sent an assertion with version 1.1 different from the existing single sign-on version: {0}.**

**Cause:** Existing session was not of the single sign-on version 1.1.

**Action:** Logout the user to delete the existing session.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**FED-15096: The identity provider sent an assertion with version 1.2 different from the existing single sign-on version: {0}.**

**Cause:** Existing session was not of the single sign-on version 1.2.

**Action:** Logout the user to delete the existing session.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**FED-15097: The identity provider sent an assertion with version 2.0 different from the existing single sign-on version: {0}.**

**Cause:** Existing session was not of the single sign-on version 2.0.

**Action:** Logout the user to delete the existing session.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**FED-15098: Unknown condition ignored: {0}.**

**Cause:** Peer provider sent a message which contains unknown conditions in the message.

**Action:** Check with the peer provider.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**FED-15099: The wtrealm parameter is empty.**

**Cause:** A WS-Federation signin request was received with an empty wtrealm parameter.

**Action:** Verify that the wtrealm parameter is not empty.

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15100: There is no assertion consumer URL in the requester's configuration.**

**Cause:** There was no assertion consumer URL in the requester configuration.

**Action:** Enter the assertion consumer URL of the requester in the Oracle Identity Federation configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15101: WS-Federation protocol is not enabled.**

**Cause:** The WS-Federation protocol was not enabled in the Oracle Identity Federation configuration.

**Action:** Enable the WS-Federation protocol in the Oracle Identity Federation configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15102: Default name identifier format for SAML 1.x assertion cannot be processed: {0}**

**Cause:** The default name identifier format cannot be processed.

**Action:** Verify that the default name identifier format is correct in the Oracle Identity Federation configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15103: Default name identifier format for SAML 1.1 assertion cannot be processed: {0}**

**Cause:** The default name identifier format cannot be processed.

**Action:** Verify that the default name identifier format is correct in the Oracle Identity Federation configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15104: The user previously performed a single sign-on operation with a protocol version ({0}) different from WS-Fed 1.1.**

**Cause:** The user previously performed a single sign-on operation with a protocol version other than WS-Federation 1.1

**Action:** No action.

**Level:** 1

**Type:** ERROR



---

**Impact:** Requests/Responses

**FED-15105: The identity provider sent an assertion with WS-Fed version 1.1 different from the existing single sign-on version: {0}.**

**Cause:** The single sign-on version in the assertion was different than the existing single sign-on version.

**Action:** Verify that the peer provider is configured to the correct protocol version.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**FED-15106: Multiple users were found during attribute based authentication using NameID mapping for name identifier: {0} and name identifier format = {1}.**

**Cause:** Multiple users were present in the user data store which satisfies the search criteria of name identifier value.

**Action:** Check the data store and correct any errors.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**FED-15107: Multiple users were found during attribute based authentication using Attribute mapping for name identifier: {0} and name identifier format = {1}.**

**Cause:** Multiple users were present in the user data store which satisfies the search criteria of attribute values.

**Action:** Check the data store and correct any errors.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**FED-15108: User was not found during attribute based authentication using NameID mapping for name identifier: {0} and name identifier format = {1}.**

**Cause:** User was not present in the user data store which satisfies the search criteria of name identifier value.

**Action:** Check the data store and correct any errors.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**FED-15109: User was not found during attribute based authentication using Attribute Mapping for name identifier: {0} and name identifier format = {1}.**

**Cause:** User was not present in the user data store which satisfies the search criteria of attribute values.

**Action:** Check the data store and correct any errors.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

---

**FED-15110: User mapping based on name identifier and attribute features are not enabled for attribute based authentication for name identifier: {0} and name identifier format: {1}.**

**Cause:** User mapping based on name identifier and attribute features were not enabled for attribute based authentication.

**Action:** Verify that user mapping based on NameID and attribute features are enabled for attribute based authentication.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15111: The message is not a request security token response.**

**Cause:** The message received from the identity provider was not a Request Security Token Response.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15112: The message contains an assertion with an empty issuer attribute.**

**Cause:** The message contained an assertion with an empty issuer attribute.

**Action:** Verify that the peer provider is configured to use the correct provider ID for the issuer.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15113: The action parameter (wa={0}) is not one of the actions currently recognized by the identity provider.**

**Cause:** The value of the action parameter was not one of the values recognized by Oracle Identity Federation.

**Action:** Verify that the peer provider is using the correct version of the WS-Federation protocol.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15114: Unknown WS-Federation request message: {0}**

**Cause:** The WS-Federation Request message contained in the wreq parameter is unknown or incorrect.

**Action:** Contact remote provider.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15115: Error while interacting with remote providers via SOAP protocol.**

---

**Cause:** An error occurred while sending or receiving a SOAP message to a remote provider.

**Action:** Check with the peer provider.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15116: The identity provider discovery service returned an empty string as the identity provider.**

**Cause:** The discovery service returned the empty string as the identity provider's provider ID.

**Action:** The identity provider's providerID parameter should either be missing or contain a value. Check with the discovery service

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15117: The identity provider discovery service returned an empty or null refid.**

**Cause:** The discovery service did not include the required refID parameter.

**Action:** Check with the discovery service

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15118: Could not find provider ID for issuer of request.**

**Cause:** Oracle Identity Federation cannot identify the SOAP requester as it did not authenticate via HTTP Basic/SSL Client.

**Action:** Configure OHS so that it protects the SAML 1.x SOAP URL to require HTTP basic authentication or SSL client authentication

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15119: Incoming message does not contain a SAML 1.x Request.**

**Cause:** The incoming SOAP Request does not contain a SAML 1.x request and Oracle Identity Federation was expecting one.

**Action:** Verify that the SOAP Requestor is sending a SAML 1.x Request; verify that the SOAP Requestor is not sending a non SAML 1.x message to the SAML 1.x SOAP URL

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15120: UserID was not sent from user provisioning system.**

**Cause:** Request from user provisioning system does not contain UserID attribute.

---

**Action:** Verify that request from user provisioning system contains UserID attribute

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15121: Attribute response is malformed.**

**Cause:** The attribute response was malformed.

**Action:** Verify that the attribute response is not malformed.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15122: Unknown identity provider: {0}**

**Cause:** The identity provider is unknown.

**Action:** Verify that the identity provider is in the federations configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15123: Invalid subject format for protocol version SAML 1.x**

**Cause:** The subject format was invalid.

**Action:** Verify that the peer provider is using the correct subject format.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15124: Provider federation does not exist for userID: {0}.**

**Cause:** Provider federation has been deleted or the userID is not valid.

**Action:** Check the request or retry.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15125: Single sign-on response was not signed.**

**Cause:** The single sign-on response signature requirements were not met.

**Action:** Verify that a signature was present in the single sign-on response and that Oracle Identity Federation is using the correct certificate for signature validation.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15128: An internal error occurred while processing the credentials**

**Cause:** The authentication engine did not return the required refID parameter.

---

**Action:** Check that the authentication flow correctly sent the refID parameter to the Oracle Identity Federation server

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15129: InfoCard error: incoming token is not a SAML token: {0}**

**Cause:** The incoming WS-Trust token is not a SAML assertion.

**Action:** Check with the WS-Trust provider

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15130: AssertionID parameter not present**

**Cause:** The AssertionID was not present in the request.

**Action:** Verify that the AssertionID is set in the request

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15131: Certificate was missing when trying to verify digital signature.**

**Cause:** Certificate missing when trying to verify incoming signature.

**Action:** Verify that the requester specified its identity when making the request, either in the message or by authenticating to the Oracle Identity Federation server via SSL or HTTP Basic Authentication

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15132: Unknown refID**

**Cause:** User previously accessed the Oracle Identity Federation server with a different host name than the one in the current request and cookies were not transmitted.

**Action:** Use the same hostname and fully qualified domain URL to access the Oracle Identity Federation server.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15133: Unknown FedID: {0}**

**Cause:** No federation record exists with specified fedID in the configured federation data store.

**Action:** Check federation data store configuration and verify that federation record with specified fedID exists in data store.

**Level:** 1

---

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15134: The service provider could not map the identity provider response to a user**

**Cause:** The Oracle Identity Federation service provider was not able to map the response from the identity provider to a user record.

**Action:** Check the message sent from the identity provider and error logs in the service provider.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-15135: "Unknown Identity Provider; SuccinctID:{0}"**

**Cause:** The identity provider is unknown.

**Action:** Verify that the identity provider is in the federations configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FED-18002: The assertion has already been processed**

**Cause:** The assertion has been replayed.

**Action:** Verify that the assertion is not replayed.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18003: Assertion is not signed.**

**Cause:** The assertion was not signed.

**Action:** Verify that the assertion was signed.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18004: Attribute authority is not trusted.**

**Cause:** The attribute authority is not marked as trusted in the federations.

**Action:** Configure the peer provider as a trusted provider to enable protocol exchanges.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18005: Identity provider is not trusted**

**Cause:** The identity provider is not marked as trusted in the federations.

**Action:** Verify configuration of the provider in the federations settings of the Oracle Identity Federation configuration.

---

**Level: 1**

**Type: ERROR**

**Impact: Security**

**FED-18006: Message cannot be validated.**

**Cause:** Incoming message is invalid.

**Action:** Please check previous log entries for more specific information.

**Level: 1**

**Type: ERROR**

**Impact: Security**

**FED-18007: Message has expired or is not yet valid.**

**Cause:** The message validity period has expired.

**Action:** Verify the time settings between this server and the peer provider are synchronized. Alternatively, the server clock drift can be increased in the Oracle Identity Federation configuration.

**Level: 1**

**Type: ERROR**

**Impact: Security**

**FED-18008: Message is not signed.**

**Cause:** The message was not signed.

**Action:** Verify that the message is signed.

**Level: 1**

**Type: ERROR**

**Impact: Security**

**FED-18009: Provider is unknown: {0}**

**Cause:** The provider is not known.

**Action:** Verify that the provider exists in the list of federations

**Level: 1**

**Type: ERROR**

**Impact: Security**

**FED-18010: The service provider is not part of the affiliation.**

**Cause:** The provider is not part of the affiliation.

**Action:** Verify that the provider is part of the affiliation in the federations

**Level: 1**

**Type: ERROR**

**Impact: Security**

**FED-18011: Service provider is not trusted.**

**Cause:** Service provider is not in the federations configuration.

**Action:** Verify configuration of the federations

---

**Level: 1**

**Type: ERROR**

**Impact: Security**

**FED-18012: Assertion cannot be validated.**

**Cause:** Assertion could not be validated.

**Action:** Check the message to verify that the assertion is valid, and after check with the peer provider that sent the assertion.

**Level: 1**

**Type: ERROR**

**Impact: Security**

**FED-18013: Assertion cannot be validated: confirmation method is missing.**

**Cause:** The confirmation method was missing from the assertion.

**Action:** Check the message to verify that the assertion is valid, and after check with the peer provider that sent the assertion.

**Level: 1**

**Type: ERROR**

**Impact: Security**

**FED-18014: Assertion cannot be validated: InResponseTo is missing.**

**Cause:** The InResponseTo attribute was missing from the assertion.

**Action:** Check the message to verify that the assertion is valid, and after check with the peer provider that sent the assertion.

**Level: 1**

**Type: ERROR**

**Impact: Security**

**FED-18015: Assertion cannot be validated: recipient is missing.**

**Cause:** The recipient was missing from the assertion.

**Action:** Check the message to verify that the assertion is valid, and after check with the peer provider that sent the assertion.

**Level: 1**

**Type: ERROR**

**Impact: Security**

**FED-18016: Assertion cannot be validated: validity time is missing.**

**Cause:** The validity time was missing from the assertion.

**Action:** Check the message to verify that the assertion is valid, and after check with the peer provider that sent the assertion.

**Level: 1**

**Type: ERROR**

**Impact: Security**

**FED-18017: The AssertionConsumerServiceURL found in the authentication request message cannot be validated.**



---

**Cause:** URL was not one of the assertion consumer support URL found in the metadata.

**Action:** Verify that the URL is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18018: Assertion has expired or is not yet valid: {0}**

**Cause:** The assertion validity period has expired.

**Action:** Verify the time settings between this server and the peer provider are synchronized. Alternatively, the server clock drift can be increased in the admin console.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18020: Authentication request is not signed.**

**Cause:** Authentication request was not signed.

**Action:** Authentication request needs to be signed.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18022: Certificate is expired: {0}**

**Cause:** Certificate has expired.

**Action:** A new certificate needs to be obtained.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18023: Certificate is revoked: {0}**

**Cause:** Certificate has been revoked.

**Action:** A new certificate needs to be obtained.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18024: Certificate verification failed with the trusted Certificate Authority : {0}**

**Cause:** Certificate verification failed.

**Action:** Verify that both servers are using the correct certificates.

**Level:** 1

**Type:** ERROR

**Impact:** Security

---

**FED-18026: Error while reading the client SSL certificate**

**Cause:** Client SSL certificate is corrupt.

**Action:** Obtain a new client SSL certificate.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18027: Evaluation of the assertion's conditions failed.**

**Cause:** Assertion conditions were not valid.

**Action:** Check logs for more detailed error messages.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18028: Invalid use specified for X509 certificate: {0}.**

**Cause:** The use specified for the X509 certificate is invalid.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18030: No trusted Certificate Authority for certificate: {0}.**

**Cause:** There was no trusted Certificate Authority found for the certificate.

**Action:** Check the existing certificate for valid trusted Certificate Authority or add the Certificate Authority to the list of trusted CAs.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18032: Trusted Certificate expired: {0}.**

**Cause:** Trusted Certificate has expired.

**Action:** Get a new certificate to replace the expired certificate.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18034: Untrusted server certificate chain.**

**Cause:** Certificate Authority certification keystore in JRE did not contain the Certificate Authority certificate.

**Action:** Add the Certificate Authority certificate of the LDAP server to the Certificate Authority certs keystore of the JRE.

**Level:** 1

**Type:** ERROR

**Impact:** Security

---

**FED-18035: URL query signature verification failed.**

**Cause:** The message or signature may have been tampered with.

**Action:** Contact administrator to investigate transport error or possible security incident.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18036: URL query signature verification failed: extra parameters present.**

**Cause:** The URL or signature may have been tampered with.

**Action:** Contact administrator to investigate transport error or possible security incident.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18038: Signature verification failed.**

**Cause:** The message or signature may have been tampered with.

**Action:** Contact administrator to investigate transport error or possible security incident.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18039: Invalid use specified for X509 certificate: {0}.**

**Cause:** Use was not specified in the X509 event.

**Action:** Contact Oracle Support Services to rectify the issue.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18040: Cannot locate temporary federations.**

**Cause:** The temporary federation did not exist, possibly expired.

**Action:** No Action.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18041: Illegal UTF encoding**

**Cause:** The UTF encoding was not supported.

**Action:** Verify the UTF encoding to be a valid one.

**Level:** 1

**Type:** ERROR

**Impact:** Security

---

**FED-18043: Unexpected recipient: {0}**

**Cause:** The recipient in the assertion did not match the configured provider.

**Action:** Contact remote provider to verify the provider information.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18045: Unsupported liberty version: {0}**

**Cause:** The version of liberty was not supported.

**Action:** The supported versions of liberty are 1.1 and 1.2.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18046: Unknown descriptor type: {0}**

**Cause:** Unknown descriptor type .

**Action:** Contact remote provider for verifying the metadata.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18047: Certificate {0} is replaced with the certificate {1}.**

**Cause:** Old certificate was replaced with the newer one.

**Action:** Ensure correct certificate is uploaded for normal functioning of the Oracle federation server.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**FED-18048: The certificate corresponding to the private key is expired: {0}**

**Cause:** The certificate was expired.

**Action:** Use the certificate with the correct validity period.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**FED-18049: Public key algorithm is not known:{0}.**

**Cause:** Public key algorithm was unknown.

**Action:** Use the correct certificate with the correct public key algorithm.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**FED-18050: User is not authenticated.**

---

**Cause:** User was not authenticated.

**Action:** Login to the federation server using the correct user.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**FED-18051: Authentication instant was not sent from the authentication engine.**

**Cause:** The authentication engine did not send an authentication instant.

**Action:** Check the authentication engine implementation.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**FED-18052: Authentication mechanism was not sent from the authentication engine.**

**Cause:** The authentication engine did not send an authentication mechanism.

**Action:** Check the authentication engine implementation.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**FED-18053: Trusted certificate not yet valid: {0}**

**Cause:** Trusted certificate is not yet valid.

**Action:** Wait until certificate becomes valid, or get a new certificate to replace the certificate that is not yet valid.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18054: Certificate not yet valid: {0}**

**Cause:** Certificate is not yet valid.

**Action:** Wait until certificate becomes valid, or get a new certificate to replace the certificate that is not yet valid.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18055: Unknown pseudo-random number generator configured. Using Java default.**

**Cause:** Default pseudo-random number generator configured is unknown.

**Action:** No Action.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

---

**FED-18056: Authentication error, the authentication mechanism is not enabled: {0}**

**Cause:** The Authentication Mechanism used to authenticate the user is disabled.

**Action:** A user tried to use a disabled authentication mechanism/engine to login.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18057: Authentication error, the authentication engine is not enabled: {0}**

**Cause:** The Authentication Engine used to authenticate the user is disabled.

**Action:** A user tried to use a disabled authentication mechanism/engine to login.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18058: Service provider engine error, the service provider engine is not enabled: {0}**

**Cause:** The service provider engine used to integrate with the AAA server is disabled.

**Action:** Enable the service provider engine.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18059: User from existing session ({0}) is different from user locally authenticated ({1})**

**Cause:** A user already authenticated in Oracle Identity Federation re-authenticated but with a different user ID.

**Action:** Check the user's activity and session status, and report a possible security incident to the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18060: User has already existing session with SessionID={0} and the authentication engine specified a different SessionID={1}**

**Cause:** A user already authenticated in Oracle Identity Federation with a SessionID that is different from the one specified by the authentication engine

**Action:** Check the authentication engine implementation to be sure that it returns the correct SessionID.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18061: The personal card issuer is not enabled, or its mode is not set to Infocard.**

---

**Cause:** Personal card issuer is not enabled in the federations, or the single sign-on Infocard mode is not enabled for Infocard.

**Action:** Check the Oracle Identity Federation configuration for the personal card issuer.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18062: Personal card issuer was selected for this authentication mechanism, but the personal card issuer does not exist in the federations: {0}**

**Cause:** The personal card issuer is not present in the federations list.

**Action:** Create an entry for the personal card issuer in the federations configuration of provider type Identity Provider, with the ProviderID set to <http://schemas.xmlsoap.org/ws/2005/05/identity/issuer/self>

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18063: Infocard mode not enabled for this provider: {0}**

**Cause:** The Infocard mode is disabled for that provider.

**Action:** Check the Oracle Identity Federation configuration to enable the Infocard mode for that provider.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18064: Infocard error: the authentication engine cannot process transient name identifiers**

**Cause:** The Infocard authentication engine cannot process transient name identifiers.

**Action:** Check with the WS-Trust provider.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18065: Infocard error: the authentication engine could not find the federation record for: {0} ({1} / {2})**

**Cause:** The Infocard authentication engine could not find the SAML 2.0 federation record.

**Action:** The federation record needs to exist prior to use Infocard as an authentication engine. Check with the WS-Trust provider to use another name identifier, or create the record.

**Level:** 1

**Type:** ERROR

**Impact:** Security

---

**FED-18066: Authentication failed**

**Cause:** The authentication process failed, the credentials could not be validated.

**Action:** Check the connection settings.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**FED-18067: Authentication failed: digest error, unknown algorithm {0}**

**Cause:** The authentication process failed, the digest method specified is unknown.

**Action:** Check the Oracle Identity Federation configuration for the digest method for RDBMS table engine.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18068: Authentication failed: WebGate did not authenticate the user**

**Cause:** The WebGate module did not authenticate the user.

**Action:** Check the WebGate deployment, the Oracle Identity Federation configuration and whether or not the user was authenticated by Oracle Access Manager

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18069: Authentication failed: unknown user attribute for Oracle Single Sign-On authentication engine: {0}**

**Cause:** The Oracle Identity Federation configuration specifies an unknown HTTP Header containing the UserID.

**Action:** Check the Oracle Identity Federation configuration for which HTTP Header used by Oracle Single Sign-On to hold the UserID is specified.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18070: Service provider Oracle Single Sign-On integration module: could not decrypt the token with current key, and old key expired**

**Cause:** The Oracle Identity Federation server could not decrypt the data sent by the Oracle Single Sign-On server. The Oracle Identity Federation server will use the second key.

**Action:** Check that the encryption key used by Oracle Identity Federation and Oracle Single Sign-On is in sync. If necessary, regenerate a new key in the Oracle Identity Federation configuration and copy it to the Oracle Single Sign-On server.

**Level:** 1

**Type:** ERROR

**Impact:** Security



---

**FED-18071: Service provider Oracle Single Sign-On integration module: could not decrypt the token with current key**

**Cause:** The Oracle Identity Federation server could not decrypt the data sent by the Oracle Single Sign-On server. The Oracle Identity Federation server will use the second key.

**Action:** Check that the encryption key used by Oracle Identity Federation and Oracle Single Sign-On is in sync. If necessary, regenerate a new key in the Oracle Identity Federation configuration and copy it to the Oracle Single Sign-On server.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**FED-18072: Service provider Oracle Single Sign-On integration module: could not encrypt the token**

**Cause:** The Oracle Identity Federation server could not encrypt the data to be sent to the Oracle Single Sign-On server.

**Action:** Check that the encryption key used by Oracle Identity Federation is valid. If necessary, regenerate a new key in the Oracle Identity Federation configuration and copy it to the Oracle Single Sign-On server.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18073: An error occurred during a cryptographic operation: {0}**

**Cause:** The Oracle Identity Federation encountered an error while invoking the crypto engine for signature creation/verification, encryption/decryption operations.

**Action:** Check the logs for more detailed error messages, and correct the problem related to the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18074: Signature verification failed for provider ID {0}**

**Cause:** The signature might be have been spoofed.

**Action:** Contact Administrator to verify

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18075: Decryption operation failed for message sent by provider ID {0}**

**Cause:** The message is not intended for Oracle Identity Federation.

**Action:** Contact Administrator to verify

**Level:** 1

**Type:** ERROR

**Impact:** Security

---

**FED-18076: Security services exception: {0}**

**Cause:** An error occurred while verifying/signing/encrypting/decrypting a message.

**Action:** Please check previous log entries for more specific information.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18077: XML decryption error: EncryptedData element not found**

**Cause:** The XML EncryptedData element was not found when trying to decrypt the incoming data.

**Action:** Check the message and contact the remote server administrator if necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18078: XML decryption error: could not get the decryption secret key**

**Cause:** The key to decrypt the EncryptedData element could not be retrieved.

**Action:** Check the message and contact the remote server administrator if necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18079: The return URL could not be validated: {0}**

**Cause:** The specified return URL could not be validated against the list of approved hostnames/domains.

**Action:** Check if the return URL points to a valid host name/domain, and update if necessary the list of approved host names/domains. If the return URL is not recognized or invalid, do not update the list of approved host names/domains.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18080: Could not retrieve key from the key store. Please verify that the key password is equal to the key store password.**

**Cause:** Invalid key or key password is not equal to the key store password.

**Action:** Verify that the key is valid and the key password is equal to the key store password.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-18081: Authentication Failed - HTTP Header not set in order to authenticate the user**

---

**Cause:** The HTTP Header was not set in order to authenticate the user.

**Action:** Check the User's browser, Agent used in the deployment, the Oracle Identity Federation configuration and whether or not the user was authenticated by the Web Access Management

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FED-20000: Cannot open the key store.**

**Cause:** Invalid or unsupported key store, or incorrect password. During installation, this error is expected.

**Action:** Verify that password is correct and the store is a valid PKCS #12 PFX wallet or Java KeyStore file. During installation, this error can be ignored.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**FED-20100: The Oracle Identity Federation transient data store cleanup process was unexpectedly terminated.**

**Cause:** The cleanup process could not connect the Oracle Identity Federation transient data store, or an error occurred while destroying expired entries.

**Action:** Check the Oracle Identity Federation transient data store.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**FED-20101: The Oracle Identity Federation RDBMS config data store process was unexpectedly terminated.**

**Cause:** The RDBMS Configuration process could not connect the Oracle Identity Federation configuration data store, or an error occurred while retrieving data from the database.

**Action:** Check the RDBMS used as the Oracle Identity Federation configuration data store.

**Level:** 1

**Type:** WARNING

**Impact:** Threads

**FED-20102: The configuration data could not be retrieved from the RDBMS configuration data store: {0}**

**Cause:** The Oracle Identity Federation server could not retrieve configuration data from the RDBMS configuration data store.

**Action:** Check the RDBMS used as the Oracle Identity Federation configuration data store.

**Level:** 1

**Type:** ERROR

**Impact:** Threads



---

## FRC-60000 to FRC-60107

**FRC-60000: fatal error configuring FRCommon component**

**Cause:** FRCommon component provisioning failed.

**Action:** Examine the stack trace that accompanies this message for the possible cause of failures and correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRC-60001: fatal error removing FRCommon component**

**Cause:** FRCommon component deprovisioning failed.

**Action:** Examine the stack trace that accompanies this message for the possible cause of failures and correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRC-60002: failed to load the registration document {0}**

**Cause:** An error occurred while reading the FRCommon component registration document.

**Action:** Do one of the following: 1. Make sure that the registration document is valid. 2. If the registration document is accidentally deleted or modified then reinstall ORACLE\_HOME.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRC-60003: error reading ORACLE\_HOME registry file {0}**

**Cause:** An error occurred while reading the ORACLE\_HOME registry file.

**Action:** Do one of the following: 1. Make sure that the ORACLE\_HOME registry file exists. 2. If the ORACLE\_HOME registry file is accidentally deleted or modified then reinstall ORACLE\_HOME.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**FRC-60004: I/O error reading CA preferences file {0}**

**Cause:** An I/O error occurred while reading the CA preferences file.

**Action:** Examine the stack trace that accompanies this message for the possible cause of failures and correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRC-60101: error converting the configuration object to the relevant CompositeType**

**Cause:** Failed to convert the configuration object to the relevant CompositeType.

**Action:** Examine the stack trace which accompanies this message for the possible cause of failures and correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRC-60102: error converting the configuration object to the relevant CompositeData**

**Cause:** Failed to convert the configuration object to the relevant CompositeData.

**Action:** Examine the stack trace which accompanies this message for the possible cause of failures and correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRC-60103: error registering child config mbean for the application section {0}**

**Cause:** Failed to register the child config mbean for the given application section.

**Action:** Examine the stack trace which accompanies this message for the possible cause of failures and correct it.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRC-60104: error deregistering child config mbean for the application section {0}**

**Cause:** Failed to deregister the child config mbean for the given application section.

**Action:** Examine the stack trace which accompanies this message for the possible cause of failures and correct it.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**FRC-60105: error deleting application section {0}**

**Cause:** An attempt was made to delete the default application section or a section that does not exist.

**Action:** Choose the correct section name.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRC-60106: error creating application section {0}**

**Cause:** An attempt was made to create an application section that already exists or has an invalid section name.

**Action:** Choose an alternative name for the section.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRC-60107: error duplicating application section {0} to {1}**

**Cause:** Failed to duplicate an application section because of one of the following reasons: 1. An attempt was made to duplicate an invalid application section. 2. An attempt was made to create an application section that already exists.

**Action:** Do one of the following: 1. Choose a correct section name for the duplicated application section. 2. Choose an alternative name for the newly created application section.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration





---

## FRM-41838 to FRM-99999

**FRM-41838: runtime process unable to open temporary record buffer file {0}**

**Cause:** The runtime process was unable to open the file used as the temporary record buffer.

**Action:** Verify that the file system or directory in which the file resides exists and that the runtime process has permissions to read and write to the file system or directory.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**FRM-41839: runtime process: disk I/O error on temporary record buffer file {0}**

**Cause:** An I/O error occurred while the runtime process was attempting to read or write a record to the temporary record buffer file.

**Action:** Verify that the file system or directory in which the file resides exists, and that the runtime process has permissions to read and write to the file system or directory, and that the file system contains sufficient space.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**FRM-60000: fatal error configuring Forms component**

**Cause:** Forms component provisioning failed.

**Action:** Examine the stack trace that accompanies this message for the possible cause of failures and correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60001: fatal error removing Forms component**

**Cause:** Forms component deprovisioning failed.

**Action:** Examine the stack trace that accompanies this message for the possible cause of failures and correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**FRM-60002: error reading Forms component registration document {0}**

**Cause:** An error occurred while reading the Forms component registration document.

**Action:** Do one of the following: 1. Make sure that the registration document is valid. 2. If the registration document is accidentally deleted or modified then reinstall ORACLE\_HOME.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60003: error reading ORACLE\_HOME registry file {0}**

**Cause:** An error occurred while reading the ORACLE\_HOME registry file.

**Action:** Do one of the following: 1. Make sure that the ORACLE\_HOME registry file exists. 2. If ORACLE\_HOME registry file is accidentally deleted or modified then reinstall ORACLE\_HOME.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60004: error obtaining text contents of the configuration file {0}**

**Cause:** Failed to read the text contents of the configuration file.

**Action:** Examine the stack trace which accompanies this message for the possible cause of failures and correct it.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60005: Directory {0} exists; renaming it to {1}.**

**Cause:** The subdirectory under the Oracle Instance directory already exists and the provisioning process renamed the existing subdirectory.

**Action:** No action is required.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**FRM-60101: error registering Forms J2EE application mbeans during the application startup**

**Cause:** An error occurred while registering the Forms J2EE application runtime mbean or custom configuration files mbeans.

**Action:** Examine the stack trace that accompanies this message for the possible cause of failures and correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**FRM-60102: error deregistering Forms J2EE application mbeans during the application shutdown**

**Cause:** An error occurred while deregistering the Forms J2EE application runtime mbean or custom configuration files mbeans.

**Action:** Examine the stack trace that accompanies this message for the possible cause of failures and correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60103: invalid or missing ODL configuration file {0}**

**Cause:** A fatal error occurred while reading the logging configuration file.

**Action:** Do one of the following: 1. Make sure that the ODL configuration file exists and it does not have any syntax errors caused by accidental modification. 2. Make sure that the domain is updated with the JRF template. 3. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60104: Forms is not configured under Oracle Instance {0}. Aborting deployment of Forms J2EE application {1}.**

**Cause:** An attempt was made to deploy the Forms J2EE application without configuring the Forms component under Oracle Instance.

**Action:** Provision the Forms component before deploying the Forms J2EE application.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60105: Forms is configured in non-ssso mode.**

**Cause:** The user configured Forms in non-ssso mode.

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**FRM-60106: Forms is configured in non-ssso mode: No install plan provided during deployment.**

**Cause:** The user deployed the Forms J2EE application using WLST or WLS admin console.

**Action:** No action is required.

**Level:** 1

---

**Type:** NOTIFICATION

**Impact:** Configuration

**FRM-60107: error reading the install plan {0}**

**Cause:** An error occurred reading the install plan due to one of the following reasons: 1. Invalid entries in the install plan. 2. Inadequate privilege to access the install plan.

**Action:** Examine the stack trace that accompanies this message for the possible cause of failures and correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60108: error creating Forms J2EE application handler entry in the ODL configuration file {0}**

**Cause:** An error occurred while creating the Forms J2EE application handler entry in the ODL configuration file.

**Action:** Examine the stack trace that accompanies this message for the possible cause of failures and correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60109: error reading the ODL configuration file {0}**

**Cause:** An error occurred reading the ODL configuration file.

**Action:** Examine the stack trace that accompanies this message for the possible cause of failures and correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60110: error writing to the ODL configuration file {0}**

**Cause:** An error occurred writing to the ODL configuration file.

**Action:** Examine the stack trace that accompanies this message for the possible cause of failures and correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60111: error removing Forms J2EE application handler entry from the ODL configuration file {0}**

**Cause:** An error occurred while removing the Forms J2EE application handler entry from the ODL configuration file.

---

**Action:** Examine the stack trace that accompanies this message for the possible cause of failures and correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60112: error registering Forms J2EE application with the Forms Component MBean**

**Cause:** An error occurred while registering the Forms J2EE application with the Forms Component MBean.

**Action:** Examine the stack trace that accompanies this message for the possible cause of failures and correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60113: error deregistering Forms J2EE application with the Forms Component MBean**

**Cause:** An error occurred while deregistering the Forms J2EE application with the Forms Component MBean.

**Action:** Examine the stack trace that accompanies this message for the possible cause of failures and correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60114: error reading default configuration path**

**Cause:** An error occurred while obtaining the default configuration location using JMX Framework.

**Action:** Examine the stack trace that accompanies this message. If the stack trace indicates a possible cause, correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60201: error reading OID properties file {0}**

**Cause:** An error occurred while reading the OID properties file.

**Action:** Examine the stack trace that accompanies this message for the possible cause of failures and correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**FRM-60202: Forms J2EE application {0} is already registered with OID host {1} under the container {2}. Deregistering it.**

**Cause:** An attempt was made to re-create an existing Forms J2EE application footprint in OID. This may occur when the same Forms J2EE application is redeployed to the domain.

**Action:** No action is required.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**FRM-60203: error creating Forms J2EE application {0} footprint in OID host {1}**

**Cause:** The Forms application footprint in OID failed to be created due to one of the following causes: 1. OID was not accessible. 2. The Forms J2EE application footprint password failed to be seeded in CSF on the mid-tier. 3. An I/O error occurred during storing of OID information from the Forms OID properties file.

**Action:** Examine the stack trace which accompanies this message for the possible cause of failures and correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60204: error deregistering Forms J2EE application {0} footprint in OID host {1}**

**Cause:** An error status was returned while deregistering the Forms J2EE application with OID.

**Action:** Do one of the following: 1. Examine the stack trace which accompanies this message, look for status of the IM tier and resolve the issue. 2. If using Fusion Middleware Control, make sure that information passed to deregister the Forms J2EE application with OID host is valid. 3. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60205: error removing the Forms J2EE application {0} footprint from OID host {1}**

**Cause:** Failed to remove the Forms J2EE application footprint from OID due to one of the following causes: 1. OID was not accessible. 2. An error status was returned while deregistering the Forms J2EE application footprint with OID. 3. Failed to fetch the Forms J2EE application footprint password from CSF on the mid-tier. 4. An I/O error occurred while cleaning OID information from the Forms OID properties file.

**Action:** Examine the stack trace which accompanies this message for the possible cause of failures and correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**FRM-60207: error storing credentials to CSF**

**Cause:** Failed to store the credentials to CSF.

**Action:** Examine the stack trace which accompanies this message for the possible cause of failures and correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60208: error deleting credentials from CSF**

**Cause:** Failed to delete the credentials from CSF.

**Action:** Examine the stack trace which accompanies this message for the possible cause of failures and correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60209: error obtaining credentials from CSF**

**Cause:** Failed to get the credentials from CSF.

**Action:** Examine the stack trace which accompanies this message for the possible cause of failures and correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60210: error obtaining MBean Server connection**

**Cause:** Failed to connect to the MBean Server.

**Action:** Examine the stack trace which accompanies this message for the possible cause of failures and correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60301: invalid character in the file name argument {0}**

**Cause:** An error occurred due to an invalid character in the file name.

**Action:** Remove the invalid character from the file name and execute the operation again.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**FRM-60302: error duplicating the configuration file {0} to {1}**

**Cause:** An error occurred duplicating the configuration file due to one of the following causes: 1. MBean registration failed. 2. Failure to create a new file on the file system.

**Action:** Examine the stack trace which accompanies this message for the possible cause of failures and correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60303: error duplicating the configuration file {0}: invalid document type {1}**

**Cause:** Invalid document type argument passed to operation.

**Action:** Invoke the 'duplicate file' operation only on the supported valid document types (Type\_default.env).

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60304: error duplicating configuration file {0}: invalid argument {1} are passed to 'duplicate file' operation**

**Cause:** The file the user tried to create already exists.

**Action:** Pass a different file name for the new file that has to be created.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60305: error deleting the configuration file {0}**

**Cause:** An error occurred deleting the configuration file due to one of the following causes: 1. MBean deregistration failed. 2. Failure to delete the file from the file system.

**Action:** Examine the stack trace which accompanies this message for the possible cause of failures and correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60306: error deleting the configuration file {0}: invalid document type {1}**

**Cause:** An invalid document type argument was passed to the operation.

**Action:** Invoke the 'duplicate file' operation only on the supported valid document types (Type\_default.env).

**Level:** 1

**Type:** ERROR

**Impact:** Configuration



---

**FRM-60307: error converting the configuration object to the relevant CompositeType**

**Cause:** Failed to convert the configuration object to the relevant CompositeType.

**Action:** Examine the stack trace which accompanies this message for the possible cause of failures and correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60308: error converting the configuration object to the relevant CompositeData**

**Cause:** Failed to convert the configuration object to the relevant CompositeData.

**Action:** Examine the stack trace which accompanies this message for the possible cause of failures and correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60309: error registering child config mbean for the application section {0}**

**Cause:** Failed to register the child config mbean for the given application section.

**Action:** Examine the stack trace which accompanies this message for the possible cause of failures and correct it.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60310: error deregistering child config mbean for the application section {0}**

**Cause:** Failed to deregister the child config mbean for the given application section.

**Action:** Examine the stack trace which accompanies this message for the possible cause of failures and correct it.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60311: error deleting application section {0}**

**Cause:** An attempt was made to delete the default application section or a section that does not exist.

**Action:** Choose the correct section name.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60312: error creating application section {0}**

**Cause:** An attempt was made to create an application section that already exists or has an invalid section name.

---

**Action:** Choose an alternative name for the section.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-60313: error duplicating application section {0} to {1}**

**Cause:** Failed to duplicate an application section because of one of the following reasons: 1. An attempt was made to duplicate an invalid application section. 2. An attempt was made to create an application section that already exists.

**Action:** Do one of the following: 1. Choose a correct section name for the duplicated application section. 2. Choose an alternative name for the newly created application section.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-91109: internal error in runtime process: application startup failure**

**Cause:** An unexpected error occurred while the runtime process was attempting to start the Toolkit component.

**Action:** If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**FRM-91111: internal error in runtime process: window system startup failure**

**Cause:** An unexpected error occurred while the runtime process was attempting to start the window system.

**Action:** If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**FRM-91112: internal error in runtime process: resource manager startup failure**

**Cause:** An unexpected error occurred while the runtime process was attempting to start the Toolkit Resource Manager.

**Action:** If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**FRM-91116: internal error in runtime process: Oracle\*Image startup failure**

**Cause:** An unexpected error occurred while the runtime process was attempting to start Oracle\*Image.

**Action:** If the problem persists, contact Oracle Support Services.

**Level:** 1

---

**Type:** INCIDENT\_ERROR

**Impact:** Process

**FRM-91119: internal error in runtime process: Oracle\*VGS startup failure**

**Cause:** An unexpected error occurred while the runtime process was attempting to start Oracle\*VGS.

**Action:** If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**FRM-91124: fatal error in runtime process: {0} specified for FORMS\_DECIMAL\_PREFIX. Should be zero or the empty string**

**Cause:** An invalid value was specified for the environment variable FORMS\_DECIMAL\_PREFIX.

**Action:** Do one of the following: 1. Specify FORMS\_DECIMAL\_PREFIX as '0' to force a zero before a leading decimal point in any number displayed without a format mask in the application. 2. Specify FORMS\_DECIMAL\_PREFIX as "" (the empty string).

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-91126: fatal error in runtime process: invalid value {0} specified for environment variable {1}**

**Cause:** An invalid environment variable value was specified. An example would be an invalid timezone for an environment variable that specifies a timezone.

**Action:** Correct the environment variable value.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-91127: fatal error in runtime process: invalid directory name specified for environment variable {0}**

**Cause:** An invalid value was specified for an environment variable that represents the name of a directory. Specifically, the value is too long: either it is itself longer than a system-imposed maximum, or a subdirectory name that Forms needs to construct would be longer than the system-imposed maximum.

**Action:** Correct the environment variable value.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-91129: fatal error in runtime process: no value specified for required environment variable {0}**

**Cause:** A required environment variable was not set or was set to the empty string.

---

**Action:** Set the environment variable to a non-empty value.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-91130: fatal error in runtime process: timezone file {0} is missing**

**Cause:** The timezone file (specified by the environment variable FORMS\_TZFILE) was not found.

**Action:** Correct the FORMS\_TZFILE environment variable value. It should specify \$ORACLE\_HOME/oracore/zoneinfo/timezone.dat or \$ORACLE\_HOME/oracore/zoneinfo/timezlg.dat.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-91131: fatal error in runtime process: timezone file {0} not loaded - required memory unavailable**

**Cause:** The timezone file (specified by the environment variable FORMS\_TZFILE) could not be loaded. This probably indicates insufficient swap space.

**Action:** Increase the size of the swap file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-91132: fatal error in runtime process: invalid data in timezone file {0}**

**Cause:** The timezone file (specified by the environment variable FORMS\_TZFILE) was found to contain invalid data.

**Action:** Correct the FORMS\_TZFILE environment variable value. It should specify \$ORACLE\_HOME/oracore/zoneinfo/timezone.dat or \$ORACLE\_HOME/oracore/zoneinfo/timezlg.dat.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-91135: fatal error in runtime process: message file {0} is missing**

**Cause:** The specified message file was not found.

**Action:** Verify that the file has not been moved or deleted. If necessary, reinstall it.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-91143: internal error in runtime process: unable to create runform global context**

**Cause:** An unexpected error occurred while the runtime process was attempting to create the runform global context.

**Action:** If the problem persists, contact Oracle Support Services.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**FRM-91144: internal error in runtime process: unable to parse user name**

**Cause:** An unexpected error occurred while the runtime process was attempting to parse the user name.

**Action:** If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**FRM-91150: internal error in runtime process: unable to initialize Oracore program manager**

**Cause:** An unexpected error occurred while the runtime process was attempting to initialize the Oracore program manager.

**Action:** If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**FRM-91151: internal error in runtime process: unable to initialize Oracle NLS**

**Cause:** An unexpected error occurred while the runtime process was attempting to initialize Oracle NLS.

**Action:** If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**FRM-91152: internal error in runtime process: unable to set environment variable {0}**

**Cause:** An unexpected error occurred while the runtime process was attempting to set an environment variable to a new value.

**Action:** If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**FRM-91153: internal error in runtime process: unable to initialize Common Area component**

**Cause:** An unexpected error occurred while the runtime process was attempting to initialize the Common Area component.

**Action:** If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

---

**FRM-91154: internal error in runtime process: unable to initialize Oracore date component**

**Cause:** An unexpected error occurred while the runtime process was attempting to initialize the Oracore date component.

**Action:** If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**FRM-91157: internal error in runtime process: unable to redirect stderr to stdout**

**Cause:** An unexpected error occurred while the runtime process was attempting to redirect stderr to stdout. This error should never occur at a customer site.

**Action:** If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**FRM-91170: runtime process: JVM exiting with code {0}**

**Cause:** The runtime process had started a JVM (in order to run Oracle Reports or the Forms debugger, or to update a password in Oracle Internet Directory). That JVM started exiting.

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Process

**FRM-91171: runtime process: JVM aborting**

**Cause:** The runtime process had started a JVM (in order to run Oracle Reports or the Forms debugger, or to update a password in Oracle Internet Directory). That JVM started aborting.

**Action:** No action is required. However, if there appear to be problems running Oracle Reports or the Forms debugger, or updating a password in Oracle Internet Directory, this message may help to indicate the cause.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Process

**FRM-91190: fatal error in runtime process: unable to allocate {0} bytes of memory**

**Cause:** A critical memory allocation request failed. This may indicate insufficient swap space. Execution of the runtime process was terminated.

**Action:** Increase the size of the swap file.

**Level:** 1

**Type:** ERROR

**Impact:** Memory

---

**FRM-91191: runtime process: unable to allocate {0} bytes of memory; attempting to continue execution**

**Cause:** A memory allocation request failed. This may indicate insufficient swap space. Execution continued, but the current operation (e.g. the loading of a form) failed. And a subsequent critical memory allocation may have failed, thereby terminating the runtime process.

**Action:** Increase the size of the swap file.

**Level:** 1

**Type:** ERROR

**Impact:** Memory

**FRM-91193: runtime process: unable to memory-map {0} bytes of memory; attempting to continue execution**

**Cause:** A memory-map request failed. This probably indicates insufficient swap space. Execution continued, but the current operation (e.g. the loading of a form) failed. And a subsequent critical memory allocation may have failed, thereby terminating the runtime process.

**Action:** Increase the size of the swap file.

**Level:** 1

**Type:** ERROR

**Impact:** Memory

**FRM-91199: internal error in runtime process: assertion failure: file {0}, line {1}**

**Cause:** An assertion failed in code that the runtime process was executing.

**Action:** If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**FRM-91200: fatal error in runtime process: error reading HTTP header**

**Cause:** A fatal error occurred while attempting to read an HTTP header.

**Action:** Check for problems on the network that connects the Forms Java Client with the Forms Listener Servlet and the runtime process.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**FRM-91210: fatal error in runtime process: error reading HTTP data**

**Cause:** A fatal error occurred while attempting to read HTTP data.

**Action:** Check for problems on the network that connects the Forms Java Client with the Forms Listener Servlet and the runtime process.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**FRM-91220: fatal error in runtime process: error writing HTTP data**

---

**Cause:** A fatal error occurred while attempting to write HTTP data.

**Action:** Check for problems on the network that connects the Forms Java Client with the Forms Listener Servlet and the runtime process.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**FRM-91230: fatal error in runtime process: timeout on connection to Java client**

**Cause:** The runtime process was waiting for a message from the Java client, but none appeared within the timeout interval. (This interval defaults to 15 minutes, but can be overridden by the FORMS\_TIMEOUT environment variable.)

**Action:** Check for problems on the network that connects the Forms Java Client with the Forms Listener Servlet and the runtime process. Also check to see if the Forms applet on the Java client experienced a fatal error.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**FRM-91260: internal error in runtime process: unable to initialize the Winsock DLL**

**Cause:** An unexpected error occurred while the runtime process was attempting to initialize the Winsock DLL.

**Action:** If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**FRM-91270: runtime process unable to allocate socket for protocol {0}: {1}**

**Cause:** The runtime process was unable to allocate a socket for the indicated protocol (IPv4 or IPv6). The error message from the operating system is displayed. NOTE: If this error was detected for an IPv4 socket, the runtime process continued execution (and subsequently attempted to configure an IPv6 socket). If this error was detected for an IPv6 socket and an IPv4 socket was not successfully configured, then the runtime process was terminated.

**Action:** If the error message from the operating system indicates a possible cause, correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**FRM-91272: runtime process unable to set close-on-exec on socket for protocol {0}: {1}**

**Cause:** The runtime process was unable to configure the socket that it allocated for the indicated protocol (IPv4 or IPv6), to set close-on-exec. The error message from the operating system is displayed. The runtime process attempted to continue execution.

**Action:** If the error message from the operating system indicates a possible cause, correct it. If the problem persists, contact Oracle Support Services.



---

**Level:** 1

**Type:** WARNING

**Impact:** Process

**FRM-91273: runtime process unable to enable local address reuse on socket for protocol {0}: {1}**

**Cause:** The runtime process was unable to configure the socket that it allocated for the indicated protocol (IPv4 or IPv6), to enable local address reuse. The error message from the operating system is displayed. NOTE: If this error was detected for an IPv4 socket, the runtime process continued execution (and subsequently attempted to configure an IPv6 socket). If this error was detected for an IPv6 socket and an IPv4 socket was not successfully configured, then the runtime process was terminated.

**Action:** If the error message from the operating system indicates a possible cause, correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**FRM-91274: runtime process unable to translate hostname ({0}) to an address for protocol {1}: {2}**

**Cause:** The runtime process was unable to configure the socket that it allocated for the indicated protocol (IPv4 or IPv6) correctly, because the hostname could not be translated to an address. The error message from the operating system is displayed. NOTE: If this error was detected for an IPv4 socket, the runtime process continued execution (and subsequently attempted to configure an IPv6 socket). If this error was detected for an IPv6 socket and an IPv4 socket was not successfully configured, then the runtime process was terminated.

**Action:** If the error message from the operating system indicates a possible cause, correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**FRM-91275: runtime process unable to bind socket address for port {0} to socket for protocol {1}: {2}**

**Cause:** The runtime process was unable to configure the socket that it allocated for the indicated protocol (IPv4 or IPv6), to bind the socket address for the indicated port to it. The error message from the operating system is displayed. NOTE: If this error was detected for an IPv4 socket, the runtime process continued execution (and subsequently attempted to configure an IPv6 socket). If this error was detected for an IPv6 socket and an IPv4 socket was not successfully configured, then the runtime process was terminated.

**Action:** If the error message from the operating system indicates a possible cause, correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**FRM-91276: runtime process unable to obtain port number of socket for protocol {0}; {1}**

**Cause:** The runtime process was unable to obtain the port number of the socket that it allocated for the indicated protocol (IPv4 or IPv6). The error message from the operating system is displayed. This error should never occur at a customer site.

**Action:** If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**FRM-91277: internal error in runtime process: unable to write port and process ID information to stderr**

**Cause:** An unexpected error occurred while the runtime process was attempting to write port and process ID information to standard error. This error should never occur at a customer site.

**Action:** If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**FRM-91278: runtime process unable to listen for connections on socket for protocol {0}; {1}**

**Cause:** The runtime process was unable to configure the socket that it allocated for the indicated protocol (IPv4 or IPv6), to listen for connections. The error message from the operating system is displayed. NOTE: If this error was detected for an IPv4 socket, the runtime process continued execution (and subsequently attempted to configure an IPv6 socket). If this error was detected for an IPv6 socket and an IPv4 socket was not successfully configured, then the runtime process was terminated.

**Action:** If the error message from the operating system indicates a possible cause, correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**FRM-91280: runtime process unable to set non-blocking I/O on socket for protocol {0}; {1}**

**Cause:** The runtime process was unable to set non-blocking I/O on the socket that it allocated for the indicated protocol (IPv4 or IPv6). The error message from the operating system is displayed. The runtime process attempted to continue execution.

**Action:** If the error message from the operating system indicates a possible cause, correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** WARNING

**Impact:** Process

---

**FRM-91292: internal error in runtime process: invalid initial message from Java client**

**Cause:** The initial message from the Java client to the runtime process was not in the expected format.

**Action:** If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**FRM-91293: internal error in runtime process: invalid initial message from servlet**

**Cause:** The initial message from the servlet to the runtime process was not in the expected format.

**Action:** If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**FRM-91299: fatal error in runtime process: unable to create a connection to the Java client**

**Cause:** An unexpected error occurred while the runtime process was attempting to create a connection to the Java client. Usually, a previous message provides more detail.

**Action:** If a previous error message indicates a possible cause, correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**FRM-93100: Initializing the Forms Servlet. Initialization parameters are:{0}**

**Cause:** The Forms Servlet was being initialized.

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**FRM-93110: No Forms Servlet configuration file is specified.**

**Cause:** The configFileName initialization parameter was not specified.

**Action:** Specify the full name in the servlet parameter configFileName, the system property oracle.forms.configFileName, or the servlet context parameter configFileName.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-93111: Cannot find Forms Servlet configuration file {0}.**

---

**Cause:** The Forms Servlet configuration file (specified by the configFileName initialization parameter) was not found.

**Action:** Verify that the configFileName initialization parameter specifies the correct value. (The value is taken from the servlet parameter configFileName, the system property oracle.forms.configFileName, or the servlet context parameter configFileName.) Create the file if necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-93112: error reading Forms Servlet configuration file {0}**

**Cause:** An I/O error occurred while reading the specified file.

**Action:** If the error persists, determine if the file has been damaged. Re-create the file if necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**FRM-93113: syntax error at line {0} in configuration file {1}: invalid section name "{2}"**

**Cause:** The specified configuration file contained an invalid section name.

**Action:** Provide a valid section name.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-93114: Forms Servlet configuration file {0} contains invalid data.**

**Cause:** A syntax error was detected while parsing the specified file.

**Action:** A preceding FRM-93113 or FRM-93142 error message will provide more information. Take the action indicated for the FRM-93113 or FRM-93142 message.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-93115: error reading configuration file FormsOIDConfig.xml via Forms Servlet.**

**Cause:** An I/O error occurred while reading configuration file FormsOIDConfig.xml.

**Action:** Check if file exists in configuration directory.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**FRM-93121: Cannot find environment variable configuration file {0}.**

**Cause:** One of the following occurred. (The first is by far the most likely.) Note that an envFile parameter may specify a relative path; if it was not found in the

---

current directory, Forms will search for it in the directory that contains the Forms Servlet configuration file. 1. The envFile configuration parameter for this application specified a nonexistent file. A preceding FRM-93141 error message provides details. 2. The envFile configuration parameter for this application specified a file that existed when the Forms Servlet extracted the parameter, but the file subsequently disappeared. 3. No envFile configuration parameter that would apply to this application was specified, and the envFile servlet parameter specified a nonexistent file.

**Action:** Take action depending on the cause. 1. Take action indicated for the preceding FRM-93141 error message. 2. Re-create the file, or correct the envFile configuration parameter. 3. Verify that the envFile servlet parameter specifies the correct value. Create the file if necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-93122: error reading environment variable configuration file {0}**

**Cause:** An I/O error occurred while reading the specified file.

**Action:** If the error persists, determine if the file has been damaged. Re-create the file if necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**FRM-93124: Environment variable configuration file {0} contains invalid data.**

**Cause:** The specified configuration file contained an invalid section name.

**Action:** Provide a valid section name.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-93130: No base HTML file is specified.**

**Cause:** The basehtml configuration parameter was not specified, nor was the basehtmljpi configuration parameter, where relevant. (See Oracle Fusion Middleware Forms Services Deployment Guide for details about which configuration parameter is appropriate.) The FRM-93140 error message provides details about which configuration sections were searched. (Note that the error message will always refer to the basehtml configuration parameter, not the basehtmljpi configuration parameter.)

**Action:** Specify the appropriate configuration parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-93131: Cannot find base HTML file {0}.**

**Cause:** The specified file was not found. This file is typically specified by the basehtml configuration parameter, but in certain cases may be specified by the basehtmljpi configuration parameter. The FRM-93141 error message provides

---

details. Note that the parameter may specify a relative path; if the file is not found in the current directory, Forms will search for the file in the directory that contains the Forms Servlet configuration file.

**Action:** Verify that the parameter specifies the correct file. Create the file if necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-93132: error reading base HTML file {0}**

**Cause:** An I/O error occurred while reading the specified file.

**Action:** If the error persists, determine if the file has been damaged. Re-create the file if necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**FRM-93140: Section [{0}] of Forms Servlet configuration file {1} does not specify (or inherit) a value for the required parameter {2}.**

**Cause:** A required configuration parameter was not specified in the indicated configuration section or in a parent section.

**Action:** Specify the parameter value in the indicated section, or in a parent section. (See Oracle Fusion Middleware Forms Services Deployment Guide for details about what values are expected.)

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-93141: Section [{0}] of Forms Servlet configuration file {1} specifies the nonexistent file {2} for parameter {3}.**

**Cause:** A configuration parameter in the indicated configuration section specified the name of a nonexistent file.

**Action:** Verify that the parameter specifies the correct file. Create the file if necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-93142: Section [{0}] of Forms Servlet configuration file {1} specifies the invalid value "{2}" for parameter {3}.**

**Cause:** An invalid configuration parameter value was specified in the indicated configuration section. Note that invalid values for certain crucial parameters (such as HTMLdelimiter) will cause a subsequent error, FRM-93114.

**Action:** Correct the parameter value. (See Oracle Fusion Middleware Forms Services Deployment Guide for details about what values are expected.)

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**FRM-93153: New connections to this Forms Servlet are not being allowed.**

**Attempting to redirect connection attempt to {0}.**

**Cause:** The allowNewConnections configuration parameter was false, and a value was specified for the connectionDisallowedURL configuration parameter. Redirection will be attempted to that URL.

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**FRM-93154: The Forms Servlet is not allowing new connections.**

**Cause:** The allowNewConnections configuration parameter was false, and either no value was specified for the connectionDisallowedURL configuration parameter, or else redirection to the specified URL failed.

**Action:** If a value is specified for the connectionDisallowedURL configuration parameter (as indicated in error message FRM-93153), check to see if the specified URL is malformed; if so, correct the URL. Otherwise, no action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**FRM-93156: The Forms Servlet is unable to contact the Forms Load Balancing Server at {0}:{1}.**

**Cause:** The Forms Servlet was unable to contact the indicated Forms Load Balancing Server, and the MetricsServerErrorURL configuration parameter was not specified.

**Action:** Do one or both of the following. 1. Determine why the server is unavailable, and correct the condition. 2. Specify a value for the MetricsServerErrorURL parameter in the Forms Servlet configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-93160: unexpected error while obtaining the JVM pid**

**Cause:** An Exception was encountered while obtaining the JVM process ID.

**Action:** Examine the stack trace that accompanies this message. If the stack trace indicates a possible cause, correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**FRM-93176: Command "{0}" is using default ORACLE\_HOME setting: {1}.**

**Cause:** A test command has retrieved the specified value for the ORACLE\_HOME environment variable, from the environment variable configuration file specified

---

by the envFile parameter in the default section of the Forms Servlet configuration file.

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**FRM-93180: Initializing ListenerServlet. Initialization parameters are: {0}**

**Cause:** The Forms Listener Servlet was being initialized.

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**FRM-93196: Process list file {0} does not exist or is not writable; process list disabled.**

**Cause:** When a runtime process was started or stopped, an attempt was made to write an updated list of runtime processes to the specified file, but it did not exist or was not writable. Note that the name of the process list file is obtained from the em\_process\_file parameter in the URL, the Forms Servlet configuration file, or the environment variable configuration file.

**Action:** Verify that the em\_process\_file parameter specifies the correct file. If necessary, create the file or make it writable, or both.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**FRM-93197: unexpected error while obtaining the application name from JRF**

**Cause:** An Exception was encountered while obtaining the application name from JRF.

**Action:** Examine the stack trace that accompanies this message. If the stack trace indicates a possible cause, correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-93211: error decoding query string using {0} encoding. Spaces generated from "+" in the value of otherparams may be converted to "%20".**

**Cause:** There was a mismatch between the way that the browser encoded multibyte characters and the way that the Forms Servlet decoded them. This could indicate an invalid value for the defaultcharset parameter in the configuration file, or possibly a problem in either the browser or Oracle software.

**Action:** If the site uses the otherparams parameter in any URLs, verify that the defaultcharset parameter in the configuration file is correct; if the defaultcharset parameter is correct, contact Oracle Support Services. Otherwise, no action is required.

**Level:** 1



---

**Type:** WARNING

**Impact:** Configuration

**FRM-93214: internal buffer ({0} bytes) not big enough to read request content ({1} bytes)**

**Cause:** An internal buffer was not big enough to read the content of a request from the Java client. The FRM-93214 error message provides supplemental detail for the FRM-93218 error message.

**Action:** If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FRM-93217: unable to read whole request from client: expected {0}, got {1}**

**Cause:** A fatal error occurred while reading the content of a request from the Java client. The FRM-93217 error message provides supplemental detail for the FRM-93218 error message.

**Action:** Check for problems on the network that connects the Forms Java Client with the Forms Listener Servlet.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FRM-93218: fatal error reading client request content**

**Cause:** A fatal error occurred while attempting to read the content of a request from the Java client. A preceding FRM-93214 or FRM-93217 error message might provide more detail.

**Action:** Check for problems on the network that connects the Forms Java Client with the Forms Listener Servlet.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FRM-93228: fatal error writing response to client**

**Cause:** A fatal error occurred while writing a response to the Forms Java client.

**Action:** Check for problems on the network that connects the Forms Java Client with the Forms Listener Servlet.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FRM-93230: fatal error creating the HTTP session**

**Cause:** An unexpected Exception was encountered while attempting to create and initialize the HTTP session for the Forms application. Typically, a session initialization error would cause a more specific message.

---

**Action:** Examine the stack trace that accompanies this message. If the stack trace indicates a possible cause, correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**FRM-93240: connection from new browser window not supported**

**Cause:** The user selected File, then New, then Browser Window (or Ctrl+N) in Internet Explorer while the servlet session was being tracked using cookies (that is, session cookies were enabled). In this case Forms does not support creating a new session for the second window.

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Browser

**FRM-93250: Forms session started.**

**Cause:** This message was generated on the initial request from the browser to the Forms Servlet, before an HTTP session was created.

**Action:** No action is required.

**Level:** 16

**Type:** NOTIFICATION

**Impact:** Session

**FRM-93251: Runtime session started for client {0} (IP address {1}).**

**Cause:** This message was generated when the runtime process was created (typically just after the HTTP session was created). If performance monitoring was requested, it started at this point.

**Action:** No action is required.

**Level:** 16

**Type:** NOTIFICATION

**Impact:** Session

**FRM-93252: Forms session ended.**

**Cause:** This message was generated when the runtime process was terminated. If performance monitoring was requested, it stopped at this point.

**Action:** No action is required.

**Level:** 16

**Type:** NOTIFICATION

**Impact:** Session

**FRM-93301: Fatal authentication error: Unable to connect to Oracle Internet Directory.**

**Cause:** A NamingException occurred while attempting to connect to Oracle Internet Directory.

---

**Action:** Verify that the Oracle Internet Directory is up.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FRM-93304: No resource information found for key {0}.**

**Cause:** No resource information was found for the specified key in Oracle Internet Directory. This message might be followed by error message FRM-93330 or FRM-93318.

**Action:** If a subsequent error message appears, take the action indicated for that error. Otherwise, no action is required.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**FRM-93306: Encountered {0} while attempting to retrieve database credentials from Oracle Internet Directory.**

**Cause:** A UtilException was encountered while attempting to retrieve database credentials from Oracle Internet Directory. This message might be followed by error message FRM-93330, FRM-93316, or FRM-93318.

**Action:** If a subsequent error message appears, take the action indicated for that error. Otherwise, no action is required.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**FRM-93310: Encountered {0} while attempting to decode headers from mod\_osso.**

**Cause:** An Exception was encountered while attempting to decode headers from mod\_osso.

**Action:** If a subsequent error message appears, take the action indicated for that error. Otherwise, no action is required.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**FRM-93316: Encountered {0} while attempting to obtain user credentials. Redirecting to Delegated Administration Services.**

**Cause:** A NoPermissionException occurred while attempting to obtain credentials. The user will be redirected to Delegated Administration Services.

**Action:** If a subsequent error message appears, take the action indicated for that error. Otherwise, no action is required.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**FRM-93318: Encountered {0} while attempting to obtain user credentials. Redirecting to Delegated Administration Services or to the SSO error URL.**

---

**Cause:** A NamingException that is not a NoPermissionException occurred while attempting to obtain user credentials.

**Action:** If a subsequent error message appears, take the action indicated for that error. Otherwise, no action is required.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**FRM-93320: unable to obtain application entity credential from CSF**

**Cause:** The Forms servlet could not retrieve application credential from CSF to connect to OID. One of the following was true: 1. The Forms application did not have privileges to connect to CSF. 2. CSF alias and key values were invalid.

**Action:** Check whether credentials exist and are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FRM-93322: unable to obtain user credentials; redirecting to Delegated Administration Services**

**Cause:** User credentials were not obtained, and either the symptom was a NoPermissionException, or the ssoDynamicResourceCreate configuration parameter was true.

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

**FRM-93324: Encountered {0} while attempting to obtain the Delegated Administration Services URL.**

**Cause:** A UtilException was encountered while attempting to obtain the Delegated Administration Services URL.

**Action:** Verify that Delegated Administration Services is up.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FRM-93326: Delegated Administration Services URL generated: {0}**

**Cause:** The Forms application was running in SSO mode, the user did not have proper credentials configured in Oracle Internet Directory, and redirection to Delegated Administration Services was requested. This message provides the URL for Delegated Administration Services.

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

---

**FRM-93328: User credentials not obtained; redirecting to the SSO error URL.**

**Cause:** User credentials were not obtained. The error was not due to a `NoPermissionException`. The `ssoDynamicResourceCreate` configuration parameter was not true. If the `ssoErrorURL` configuration parameter was not defined, this message will be followed by error message FRM-93140, which will provide details.

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

**FRM-93330: Fatal authentication error: User does not have proper credentials configured in Oracle Internet Directory.**

**Cause:** The user did not have proper credentials configured in Oracle Internet Directory, and one of the following was true: 1. The `ssoDynamicResourceCreate` configuration parameter was true, or the user did not have the necessary permissions to access Oracle Internet Directory. The Delegated Administration Services URL could not be generated. The preceding FRM-93324 error message provides more detail. 2. The `ssoDynamicResourceCreate` configuration parameter was not true, and the user had the necessary permissions to access Oracle Internet Directory. The `ssoErrorURL` configuration parameter was not defined. The preceding FRM-93140 error message provides more detail.

**Action:** Add the user credentials to Oracle Internet Directory, if appropriate. Alternatively, define the `ssoErrorURL` configuration parameter. Alternatively, ensure that the Delegated Administration Services URL can be generated.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FRM-93340: Session requires SSO user authentication.**

**Cause:** The session was not SSO-authenticated or had expired.

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

**FRM-93350: failure in SSO user validation**

**Cause:** The Listener Servlet decoded a request's SSO headers, but the values did not match the values from the Forms Servlet. The user was prompted to log in again.

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

**FRM-93360: This session is in SSO mode.**

**Cause:** The `ssoMode` parameter was specified as true in the base configuration file, and the servlet supported authentication.

---

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

**FRM-93362: unable to update password in Oracle Internet Directory**

**Cause:** The user did not have proper credentials configured in Oracle Internet Directory to update entries.

**Action:** Check with the Oracle Internet Directory administrator to see if the user has permissions to update entries in Oracle Internet Directory.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**FRM-93364: Cannot dynamically create resource in Oracle Internet Directory: URL specifies invalid value "{0}" for the config parameter.**

**Cause:** The Forms application was running in SSO mode, the user did not have proper credentials configured in Oracle Internet Directory, and SSO dynamic resource creation was enabled. However, dynamic resource creation requires a valid configuration section in the base configuration file, but the user specified a nonexistent configuration section.

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

**FRM-93365: error running Forms in SSO mode**

**Cause:** Forms is not configured to run in SSO mode.

**Action:** Configure Forms to run in SSO mode.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**FRM-93410: unexpected error while prestarting runtime processes**

**Cause:** An unchecked Exception or Error was encountered while prestarting runtime processes. The prestarting of runtime processes might not have occurred at all, or it might have been partially completed.

**Action:** Examine the stack trace that accompanies this message. If the stack trace indicates a possible cause, correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**FRM-93412: There are {0} prestarted runtime processes in the runtime process pool for configuration section [{1}].**

---

**Cause:** During runtime process pool initialization, the indicated number of runtime processes were prestarted for the indicated configuration section, because the configuration section specified a value of true for the prestartRuntimes parameter. (The number of runtime processes is derived from the prestartInit parameter.)

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Process

**FRM-93421: starting the timer for the runtime process pool for configuration section [{0}]**

**Cause:** During runtime process pool initialization, a timer task was started for the indicated configuration section, because the configuration section specified a positive value for the prestartTimeOut parameter.

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Process

**FRM-93423: adding {0} runtime processes to the runtime process pool for configuration section [{1}] because the pool has gone below the minimum**

**Cause:** A prestarted runtime process was removed from the runtime process pool for the indicated configuration section, in order to start a new Forms application. This caused the number of prestarted runtime processes to fall below the value specified by the prestartMin parameter. As a result, the indicated number of prestarted runtime processes (derived from the prestartIncrement parameter) were added to the pool.

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Process

**FRM-93424: removing the prestarted runtime processes for configuration section [{0}]**

**Cause:** The servlet was being shut down, or the prestarting of runtime processes timed out (as indicated by message FRM-93425). As a result, prestarted processes were removed from the pool.

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Process

**FRM-93425: The prestarting of runtime processes for configuration section [{0}] has timed out.**

**Cause:** The thread that was filling the runtime process pool for the indicated configuration section timed out, after running for the number of minutes specified

---

by the `prestartTimeOut` parameter for the indicated configuration section. Any prestarted processes in the pool were subsequently removed.

**Action:** Determine why prestarting was taking an unexpectedly long time, or increase the value of the `prestartTimeOut` parameter.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Process

**FRM-93426: The prestarting of runtime processes for configuration section [{0}] is terminated.**

**Cause:** A concurrent process removed the indicated configuration section's entry in the `PoolManager` while its runtime process pool was being filled. Any prestarted processes in the pool were subsequently removed.

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Process

**FRM-93500: unexpected error while attempting to create the runtime process**

**Cause:** An unchecked Exception or Error was encountered while attempting to create the runtime process. Typically, a runtime process creation error would cause a more specific message.

**Action:** Examine the stack trace that accompanies this message. If the stack trace indicates a possible cause, correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**FRM-93520: Runtime process not created: Maximum permissible number of runtime processes is exceeded.**

**Cause:** The `maxRuntimeProcesses` configuration parameter specified a positive decimal number, and there appeared to be that many runtime processes already executing.

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**FRM-93530: unable to switch to working directory {0}**

**Cause:** The specified file did not exist or was not a directory. Note that the name of the working directory is obtained from one of the following: 1. The `workingDirectory` parameter in the Forms Servlet configuration file. 2. The `workingDirectory` servlet parameter. 3. `<oracle_home>/forms`, where `<oracle_home>` is derived from the `ORACLE_HOME` parameter in the environment variable configuration file. 4. `<oracle_home>/forms`, where `<oracle_home>` is derived from the `ORACLE_HOME` environment variable.



---

**Action:** For cases 1 and 2, verify that the workingDirectory parameter specifies the correct directory. For cases 3 and 4, verify that the ORACLE\_HOME parameter or environment variable specifies the correct directory. If necessary, create the directory.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-93531: cannot create runtime process: unable to switch to working directory**

**Cause:** Refer to error message FRM-93530 (which always precedes this message). The FRM-93530 message provides the name of the directory.

**Action:** Refer to error message FRM-93530.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FRM-93534: unable to execute startup command {0}**

**Cause:** The specified command (which was intended to start the runtime process) threw an Exception. The command was retried with <oracle\_home>/bin prefixed, but that too threw an Exception. A stack trace accompanies the following FRM-93535 error message. This error should never occur at a customer site. Note that <oracle\_home> is derived from one of the following: 1. The ORACLE\_HOME parameter in the environment variable configuration file. 2. The ORACLE\_HOME environment variable.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**FRM-93535: cannot create runtime process: unable to execute startup command**

**Cause:** Refer to error message FRM-93534 (which always precedes this message). The FRM-93534 error message specifies the command. This error should never occur at a customer site.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**FRM-93536: cannot create runtime process: unable to create temporary logging file**

**Cause:** An IOException occurred while trying to create a temporary logging file to capture the standard output and standard error streams of the newly created runtime process.

**Action:** Verify that the Forms Listener Servlet has the necessary permissions and disk space to create a temporary file.

**Level:** 1

**Type:** ERROR

---

**Impact:** Files

**FRM-93543: cannot connect to runtime process: unable to get I/O streams from newly created runtime process**

**Cause:** The Forms Listener Servlet encountered an Exception when attempting to obtain a BufferedInputStream for the standard output or standard error streams produced by the newly created runtime process. This error should never occur at a customer site.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**FRM-93546: external message from runtime process: {0}**

**Cause:** The runtime process wrote the specified message to stderr or stdout, but the message does not appear to have been written by the frmweb executable. It typically will be an O/S message identifying an error that occurred while attempting to load the executable. In such a case, this message will be followed immediately by FRM-93552.

**Action:** Examine the external message. If it identifies a fatal error, correct it, if possible. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**FRM-93548: Runtime process ID is {0}.**

**Cause:** The newly created runtime process sent its process ID back to the Forms Listener Servlet.

**Action:** No action is required.

**Level:** 16

**Type:** NOTIFICATION

**Impact:** Process

**FRM-93550: cannot connect to runtime process: no response from newly created runtime process**

**Cause:** The Forms Listener Servlet waited several times (for a total of roughly 4 minutes) for the initial response from the newly created runtime process, but no response arrived.

**Action:** If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**FRM-93552: cannot connect to runtime process: Newly created runtime process has terminated abnormally.**

**Cause:** The Forms Listener Servlet created the runtime process, but the process terminated abnormally. The preceding error message provides more detail.

**Action:** Take the action indicated for the preceding error message.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**FRM-93553: cannot connect to runtime process: unable to establish a socket connection to newly created runtime process**

**Cause:** The Forms Listener Servlet created the runtime process, but was unable to establish a socket connection to the process.

**Action:** If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**FRM-93558: cannot connect to runtime process: error reading data from newly created runtime process**

**Cause:** The Forms Listener Servlet encountered an IOException while attempting to receive data from the newly created runtime process.

**Action:** Examine the stack trace that accompanies this message. If the stack trace indicates a possible cause, correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**FRM-93566: unexpected error while attempting to stop runtime process**

**Cause:** An unchecked Exception or Error was encountered while attempting to stop the runtime process. Processing continued. However, the runtime process might have been left in existence (thereby consuming resources), and messages from the runtime process might not have been written to the Oracle Diagnostic Log.

**Action:** Examine the stack trace that accompanies this message. If the stack trace indicates a possible cause, correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** WARNING

**Impact:** Process

**FRM-93572: error reading messages from runtime process**

**Cause:** An I/O error occurred while reading the temporary file to which messages from the runtime process were written. Processing continued. However, messages from the runtime process were not written to the Oracle Diagnostic Log.

**Action:** Examine the stack trace that accompanies this message. If the stack trace indicates a possible cause, correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** WARNING

**Impact:** Files

---

**FRM-93574: Application server does not support Oracle character set {0}.**

**Cause:** The runtime process used the specified Oracle character set when it wrote messages for the Oracle Diagnostic Log, but the application server did not support that character set. Processing continued, using the ISO-8859-1 Java character set. However, some multibyte characters (those in variable arguments) in messages from the runtime process might have been displayed incorrectly in the Oracle Diagnostic Log.

**Action:** Verify that the environment variable configuration file specifies the correct value for NLS\_LANG (specifically, the correct character set). If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**FRM-93600: unexpected error while attempting to communicate with the client or the runtime process**

**Cause:** An unchecked Exception or Error was encountered while attempting to communicate with the client or the runtime process. Typically, a communication error would cause a more specific message.

**Action:** Examine the stack trace that accompanies this message. If the stack trace indicates a possible cause, correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**FRM-93614: invalid or absent Content-Length from runtime process**

**Cause:** This message provides more detail for the following FRM-93618 error message.

**Action:** Refer to error message FRM-93618.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**FRM-93618: fatal error reading data from runtime process**

**Cause:** The runtime process was still running, but the Forms Listener Servlet encountered an IOException while attempting to receive data from the process. A preceding message might provide more detail. The accompanying stack trace represents the state of the process when the previous detail message was logged.

**Action:** Examine the stack trace that accompanies this message. If the stack trace indicates a possible cause, correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**FRM-93624: internal buffer ({0} bytes) not big enough to hold header ({1} bytes) for message from servlet to runtime process**

---

**Cause:** An internal buffer was not big enough to hold the header for a message from the servlet to the runtime process. The FRM-93624 error message provides supplemental detail for the FRM-93628 error message.

**Action:** If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FRM-93625: internal buffer ({0} bytes) not big enough to generate initial message from servlet to runtime process**

**Cause:** An internal buffer was not big enough to generate the initial message from the servlet to the runtime process. The FRM-93625 error message provides supplemental detail for the FRM-93628 error message.

**Action:** If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**FRM-93628: fatal error writing data to runtime process**

**Cause:** The runtime process was still running, but the Forms Listener Servlet encountered a fatal error while attempting to write data to the process. A preceding FRM-93624 or FRM-93625 error message might provide more detail.

**Action:** Examine the stack trace that accompanies this message. If the stack trace indicates a possible cause, correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**FRM-93652: The runtime process has terminated abnormally.**

**Cause:** The Forms Listener Servlet attempted to communicate with the runtime process, but the process had terminated prematurely. The preceding error message provides more detail.

**Action:** Take the action indicated for the preceding error message.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**FRM-93654: Runtime process {0} is terminating due to external action.**

**Cause:** The runtime process was running on a UNIX platform, and received a signal 9 (SIGKILL) or 15 (SIGTERM), or the runtime process was running on a Windows platform, and exited with exit code 1. Presumably the runtime process was terminated explicitly, either via the Enterprise Manager, or via a 'kill' command (UNIX) or the task manager (Windows). As a result, the runtime process terminated abnormally. This message provides more detail for a following FRM-93552 or FRM-93652 error message.

**Action:** No action is required.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**FRM-93656: Runtime process {0} is terminating due to signal {1}.**

**Cause:** The runtime process was running on a UNIX platform, and received a signal other than 9 (SIGKILL) or 15 (SIGTERM). The signal caused the runtime process to terminate abnormally. This message provides more detail for a following FRM-93552 or FRM-93652 error message. If the FORMS\_CATCHTERM environment variable was not set to a value that is equivalent to FALSE, there will typically be a stack trace. If the FORMS\_C\_STACK\_TRACE\_TO\_FILE environment variable was set to a value that is equivalent to FALSE, the stack trace will accompany this message; otherwise, the stack trace will appear in a file named frmweb\_dump\_<pid> in the Forms trace directory, where <pid> is the process ID. If the FORMS\_CATCHTERM environment variable was set to a value that is equivalent to FALSE, there may be a core file that contains a stack trace.

**Action:** Examine the stack trace for the runtime process. If the stack trace indicates a possible cause, correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**FRM-93657: Runtime process {0} is terminating due to exception {1}.**

**Cause:** The runtime process was running on a Windows platform, and encountered an exception (which is displayed as 8 hexadecimal digits in the error message, in some cases followed by a descriptive phrase). The exception caused the runtime process to terminate abnormally. This message provides more detail for a following FRM-93552 or FRM-93652 error message. If the FORMS\_CATCHTERM environment variable was not set to a value that is equivalent to FALSE, there will typically be a stack trace. If the FORMS\_C\_STACK\_TRACE\_TO\_FILE environment variable was set to a value that is equivalent to FALSE, the stack trace will accompany this message; otherwise, the stack trace will appear in a file named frmweb\_dump\_<pid> in the Forms trace directory, where <pid> is the process ID.

**Action:** Examine the stack trace for the runtime process. If the stack trace indicates a possible cause, correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**FRM-93658: Stack trace for runtime process {0} is being written to file {1}.**

**Cause:** The runtime process encountered a signal or an exception (identified by the preceding "FRM-93656" or "FRM-93657" message), and the FORMS\_C\_STACK\_TRACE\_TO\_FILE environment variable was not set to a value that is equivalent to FALSE.

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Process

---

**FRM-93659: Stack trace for runtime process {0} cannot be written to file {1}.**

**Cause:** The runtime process encountered a signal or an exception (identified by the preceding "FRM-93656" or "FRM-93657" message), and the FORMS\_C\_STACK\_TRACE\_TO\_FILE environment variable was not set to a value that is equivalent to FALSE. However, the stack trace file could not be created.

**Action:** Ensure that the FORMS\_TRACE\_DIR environment variable (if set) and the ORACLE\_INSTANCE environment variable each specify a valid directory with write permissions and adequate space.

**Level:** 1

**Type:** WARNING

**Impact:** Process

**FRM-93700: Request duration is {0} seconds. Request size is {1} bytes; response size is {2} bytes.**

**Cause:** Performance monitoring at the request level was requested.

**Action:** No action is required.

**Level:** 16

**Type:** TRACE

**Impact:** Performance

**FRM-93710: Total duration of network exchanges is {0}. Total number of network exchanges is {1} ({2} long ones over {3} sec). Average time for one network exchange (excluding long ones) is {4}. Total number of bytes sent is {5}. Total number of bytes received is {6}.**

**Cause:** Performance monitoring at the session level was requested.

**Action:** No action is required.

**Level:** 1

**Type:** TRACE

**Impact:** Performance

**FRM-93840: Proctest: Warning: nProcs configuration parameter is nonnumeric - using 1.**

**Cause:** A nonnumeric value was specified for the nProcs parameter in the base configuration file. The value will default to 1.

**Action:** Correct the nProcs configuration parameter.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**FRM-93841: Proctest: Process test starting with {0} processes.**

**Cause:** The Proctest command started.

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Process

---

**FRM-93842: Proctest: Creating process {0}.**

**Cause:** The Proctest command started creating a runtime process.

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Process

**FRM-93843: Proctest: Failure to create process {0} - aborting test.**

**Cause:** An Exception occurred while attempting to create a runtime process. The preceding error message identifies the problem, and includes a stack trace.

**Action:** Refer to the preceding error message.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**FRM-93844: Proctest: Connecting to process {0}.**

**Cause:** The Proctest command started connecting to a newly created runtime process.

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Process

**FRM-93845: Proctest: Failure to connect to process {0} - aborting test.**

**Cause:** An Exception occurred while attempting to connect to a newly created runtime process. The preceding error message identifies the problem, and includes a stack trace.

**Action:** Refer to the preceding error message.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**FRM-93846: Proctest: unexpected error in process test**

**Cause:** This message precedes error message FRM-93843 or FRM-93845 if the problem was an Error or an unchecked Exception that was not caught by Forms code. A stack trace is included.

**Action:** Examine the stack trace that accompanies this message. If the stack trace indicates a possible cause, correct it. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**FRM-93847: Proctest: Number of processes started and connected to is {0}.**

**Cause:** The Proctest command created the requested number of runtime processes, and successfully connected to them.



---

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Process

**FRM-93848: Proctest: Stopping the {0} runtime processes.**

**Cause:** The Proctest command reached the point in its processing where it was about to stop the runtime processes that it had previously created.

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Process

**FRM-93849: Proctest: Process test complete.**

**Cause:** The Proctest command completed.

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Process

**FRM-93880: Testsession: Successful creation of new servlet session.**

**Cause:** The Testsession command successfully created a new servlet session.

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Session

**FRM-93881: Testsession: Attempting to establish session tracking using cookies. Sending redirect to {0}.**

**Cause:** The Testsession command started to establish session tracking using cookies.

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Session

**FRM-93882: Testsession: Failure to establish session tracking using cookies; attempting URL rewriting. Sending redirect to {0}.**

**Cause:** The Testsession command failed to establish session tracking using cookies.

**Action:** No action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Session

---

**FRM-93884: error in Testsession command**

**Cause:** An internal error occurred. Probable cause: an attempt to invoke the `HttpServletRequest.isRequestedSessionIdFromUrl` method caused a `NoSuchMethodError`. This probably indicates that the JDK does not support the deprecated spelling. (The supported spelling is `"isRequestedSessionIdFromURL"`, but JServ / Servlet API 2.0 supports only the deprecated spelling.)

**Action:** If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Session

**FRM-94170: File {0} is missing from the current directory, looking in {1}.**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94171: File is missing from {0}.**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94172: Environment variable configuration file is {0}.**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94178: Enterprise Manager configuration details: {0}**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94200: FormsServlet receiving {0} request. Details: {1}**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

---

**Impact:** Other

**FRM-94201: ListenerServlet receiving {0} request. Details: {1}**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94202: HTTP request headers: {0}**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94212: Unable to get the Sequence Number from Pragma Header (Mac Client).  
Obtaining the seqNumber from the Accept header instead.**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94213: forwarding 0 length request to runtime in response to request to close  
Forms session**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94231: starting new servlet session**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94232: FormsServlet: encodeUrl() has no effect.**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

---

**Impact:** Other

**FRM-94233: Server URL is rewritten. Details:{0}**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94241: ListenerServlet: encodeUrl() has no effect.**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94252: Servlet session is invalidated.**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94281: No current servlet session ID.**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94282: Existing servlet session, ID = {0}**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94283: No current servlet session.**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94284: requesting a servlet session with invalid session ID = {0}**

---

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94285: Session ID is from cookie.**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94286: Session ID is not from cookie.**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94302: Encountering {0} while attempting to proxy the Oracle Internet Directory connection to the SSO user.**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94332: Starting session in SSO mode. Details: {0}**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94334: User name from Oracle Internet Directory: {0}**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94430: Trying to get a prestarted process.**

**Cause:** This message is intended primarily for Oracle Support Services.

---

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94431: Prestarted process is available and selected.**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94432: Prestarted process is not available.**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94522: Creating new runtime process using default executable.**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94523: Creating new runtime process using executable "{0}".**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94532: RunformProcess.startProcess(): executing {0}**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94533: RunformProcess.startProcess(): execution failure, trying again using {0}**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

---

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94538: successful creation of new runtime process**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94542: Getting stderr of child process.**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94547: port number from message: {0}**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94554: successful connection to runtime process after {0} attempts**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94556: successful connection to runtime process at port {0}**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-94562: RunformSession.valueUnbound(): stopping runtime process.**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

---

**Impact:** Other

**FRM-94610: Read timeout. Sending Response Pending with retry time = {0}.**

**Cause:** This message is intended primarily for Oracle Support Services.

**Action:** No action is required.

**Level:** 32

**Type:** TRACE

**Impact:** Other

**FRM-99999: Error {0}: See the release notes file (relnotes) for information about this error.**

**Cause:** See the release notes.

**Action:** Take action as documented in the release notes.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration



---

## FTS-40001 to FTS-40006

**FTS-40001: Service Error {0} {1} {2}**

**Cause:** Service failed to return a success response.

**Action:** See service error code.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**FTS-40002: Configuration for connector missing.**

**Cause:** The connector configuration was not found.

**Action:** Add connector configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FTS-40003: Configuration parameter {0} missing.**

**Cause:** Configuration parameter was not found.

**Action:** Add the parameter and its value indicated in the error message.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FTS-40004: Invalid value {0} for configuration parameter {1}**

**Cause:** The value specified for the configuration parameter is invalid.

**Action:** Specify a valid value for the configuration parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**FTS-40005: Stale data presented for update.**

**Cause:** The data presented for update is stale.

**Action:** Refresh the data to get the latest version.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**FTS-40006: Failed to transform PIM xml: {0}**

**Cause:** The PIM xml retrieved could not be transformed to hub xml format.

**Action:** Correct the PIM data and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

## HELP-00001 to HELP-30008

**HELP-00001: Error when creating HelpXmlPullParser due to XmlPullParserException for location: {0}**

**Cause:** An XmlPullParserException was thrown while running `_processDocument` in the HelpXmlPullParser constructor.

**Action:** Verify that the location of the JavaHelp-format file exists.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**HELP-00002: Error when creating HelpXmlPullParser due to IOException for location: {0}**

**Cause:** An IOException was thrown when running `Process Document` in the HelpXmlPullParser constructor.

**Action:** Verify that the location of the JavaHelp-format file exists

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**HELP-00003: Error when executing search in SearchModel.**

**Cause:** SearchModel threw a SearchException when starting the search.

**Action:** Log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**HELP-00004: View passed to SearchModel does not contain data in QueryHandler format.**

**Cause:** The view object passed to SearchModel did not contain data in the expected QueryHandler format.

**Action:** Log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

---

**HELP-00005: Unexpected exception occurring in Help Share.**

**Cause:** An unexpected exception occurred in the code.

**Action:** Log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-00006: Error when parsing document using XML parser**

**Cause:** An XMLParseException was thrown when processing the XML document.

**Action:** Log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**HELP-10001: Unexpected exception occurring in OHW Share.**

**Cause:** An unexpected exception occurred in the code.

**Action:** Log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10002: Adding book {0} to library fails because of LibraryException.**

**Cause:** A LibraryException was thrown.

**Action:** Log a bug against the application.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**HELP-10003: encountering severe exception when parsing locale from file**

**Cause:** A ConfigParseException was thrown when creating PerLocaleInfo from file.

**Action:** Log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10004: class name attribute is required on [localeFromProvider]**

**Cause:** The class attribute was missing for the localeFromProvider tag.

**Action:** Add the class name attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10005: error in loading per locale provider {0}**

---

**Cause:** An unexpected exception was caught when loading the per locale provider.

**Action:** Log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10006: unrecognized tag {0} in {1} section**

**Cause:** There was an unrecognized tag in the configuration section.

**Action:** Check the configuration file for unrecognized tags in the configuration section.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10007: no [locale] section in [locales]**

**Cause:** The required [locale] section was missing in [locales].

**Action:** Check the help configuration file to ensure that [locales] has at least one child [locale].

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10008: error in loading custom protocol class: {0}**

**Cause:** An unexpected exception was caught when loading the Custom Protocol class.

**Action:** Verify that the Custom Protocol class is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10009: error in loading branding provider: {0}**

**Cause:** An unexpected exception was caught when loading the Branding Provider class.

**Action:** Verify that the Branding Provider class is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10010: configuration file is empty**

**Cause:** The Help configuration file was empty.

**Action:** Verify that the Help configuration file exists and contains content.

**Level:** 1

**Type:** ERROR

---

**Impact:** Logging

**HELP-10011: {0} attribute is required on [helpConfiguration]**

**Cause:** The version attribute was not available on the [helpConfiguration] section.

**Action:** Add the version attribute to the [helpConfiguration] section of the Help configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10012: Version {0} is not a recognized version. Accepted versions are: {1}**

**Cause:** The version provided was not recognized as an accepted version.

**Action:** Verify that an accepted version is used in the Help configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10013: duplicate {0} section in the Help configuration file**

**Cause:** There was a duplicate section in the Help configuration file.

**Action:** Check the Help configuration file for duplicate sections and remove them.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10014: tag {0} is not recognized**

**Cause:** Unrecognized tags were found in the Help configuration file.

**Action:** Remove all unrecognized tags from the Help configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10015: no {0} section found**

**Cause:** A required section was not found in the Help configuration file.

**Action:** Add the required section to the Help configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10017: The {0} attribute is missing in [customProtocol].**

**Cause:** The attribute was missing in the Custom Protocol definition.

**Action:** Add the required attribute to the Custom Protocol definition.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

---

**HELP-10018: The attribute {0} is missing in [alias].**

**Cause:** The required attribute was missing from the navigator alias definition.

**Action:** Add the required attribute to the navigator alias definition.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10019: Text or image source attribute is required in [branding].**

**Cause:** The text or image attribute was missing from the [branding] section of the Help configuration file.

**Action:** Ensure that the text or image attribute is non-empty and points to a valid location.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10020: The {0} attribute on the [branding] tag cannot be empty.**

**Cause:** The required attribute was missing from the [branding] section.

**Action:** Add the required attribute to the [branding] section.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10021: Text key or image source key attribute is required in [brandingFromResource].**

**Cause:** The text key or image source attribute was missing from [brandingFromResource].

**Action:** Ensure that the text or image attribute is non-empty and points to a valid location.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10022: The {0} attribute is required on [brandingFromResource].**

**Cause:** The required attribute was missing from the [brandingFromResource] section.

**Action:** Add the required attribute to the [brandingFromResource] section.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10023: The {0} attribute is required on [brandingFromProvider]**

**Cause:** The required attribute was missing from the [brandingFromProvider] section.

**Action:** Add the required attribute to the [brandingFromProvider] section.

---

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10024: error finding configuration file at: {0}**

**Cause:** The configuration file was not found at the specified location.

**Action:** Verify that the location of the configuration file is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10026: trying to access site with invalid path: {0}**

**Cause:** There was an attempt to access a file through an invalid path.

**Action:** Verify that the file path is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10027: missing or empty {0} attribute in [localeFromFile]**

**Cause:** A required attribute was missing or empty in the [localeFromFile] section.

**Action:** Add the required attribute to the Help configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10028: Location of locale file is not valid.**

**Cause:** The location of the locale file was not valid.

**Action:** Supply a valid location for the locale file in the Help configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10029: Locale file is empty.**

**Cause:** The locale file has no content.

**Action:** Supply a valid locale file.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10030: The locale file cannot be found.**

**Cause:** The locale file was not available at the location specified in the Help configuration file.

**Action:** Verify that the locale file exists at the location specified in the Help configuration file.



---

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10031: The {0} locale is not allowed without a corresponding country section.**

**Cause:** The locale was used without an accompanying country section.

**Action:** Add a country section for this locale.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10032: unrecognized book: {0}**

**Cause:** An unrecognized book tag was found in the Help configuration file.

**Action:** Check the Help configuration file for helpSet or helpBook tags and remove or correct the unrecognized book tag.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10033: no books in [books] section**

**Cause:** There was no book child in the books parent tag in the Help configuration file.

**Action:** Add a book child element to the books parent tag.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10034: Attribute {0} is missing in helpSet.**

**Cause:** The required attribute was missing from the helpSet tag.

**Action:** Add the required attribute to the helpSet tag.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10035: duplicate helpSet or helpBook {0} : {1}**

**Cause:** A duplicate helpSet or helpBook attribute was encountered.

**Action:** Remove the duplicate entry from the helpset configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10036: Location of {0} is not valid.**

**Cause:** The location of the file was not valid.

**Action:** Ensure that the location of the file is valid.

---

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10037: Attribute {0} is missing in helpBook.**

**Cause:** The required attribute was missing from the helpBook tag.

**Action:** Add the required attribute to the helpBook tag in the Help configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10038: Attribute {0} is missing in contentLocation tag.**

**Cause:** The required attribute was missing from the contentLocation tag.

**Action:** Add the required attribute to the contentLocation tag in the Help configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10039: Content location is not valid.**

**Cause:** The content location path was invalid.

**Action:** Ensure that the Help configuration file contains a valid content location base URI.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10040: duplicate {0} attribute {1} for content location**

**Cause:** There was a duplicate attribute for the content location.

**Action:** Remove the duplicate entry from the Help configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10041: Content location is missing or malformed.**

**Cause:** The content location was missing or malformed

**Action:** Verify that the content location path exists, and that it is a valid path.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10042: no known locales**

**Cause:** There was no known locale information available.

**Action:** Verify that the Help configuration file contains a known locale.

---

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10043: CustomProtocolName and converter must not be null.**

**Cause:** The custom protocol name and the converter were not valid.

**Action:** Verify that the custom protocol name and the converter are not null in the Help configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10044: PerLocaleConfiguration cannot be used in unloaded state.**

**Cause:** The PerLocaleConfiguration was not loaded into memory before an attempt was made to use it.

**Action:** Log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10045: error creating book information for id: {0}**

**Cause:** There was an error while creating the book information.

**Action:** Log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10046: passed null per locale configuration**

**Cause:** A null PerLocaleConfiguartion object was passed.

**Action:** Log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10047: calling init method for a second time in navigator manager**

**Cause:** The init method was called a second time in AbstractNavigatorManager.

**Action:** Log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-10048: FastMessageFormat supports only numeric arguments.**

**Cause:** The FastMessageFormat method was passed non-numeric arguments.

**Action:** Log a bug against the application.

---

**Level:** 1  
**Type:** ERROR  
**Impact:** Logging

**HELP-10049: end of pattern symbol not found**  
**Cause:** The end of pattern symbol was not found.  
**Action:** Log a bug against the application.

**Level:** 1  
**Type:** ERROR  
**Impact:** Logging

**HELP-10050: FastMessageFormat: empty argument - {}.**  
**Cause:** An empty argument was passed to FastMessageFormat.  
**Action:** Log a bug against the application.

**Level:** 1  
**Type:** ERROR  
**Impact:** Logging

**HELP-10051: The operation {0} is not supported.**  
**Cause:** The execution of this method was not supported.  
**Action:** Log a bug against the application.

**Level:** 1  
**Type:** ERROR  
**Impact:** Logging

**HELP-10054: invalid topic id link: {0} reported from {1}**  
**Cause:** An invalid topic id was found.  
**Action:** Review the help topic map file and the topic content file and correct the invalid topic id.

**Level:** 1  
**Type:** WARNING  
**Impact:** Logging

**HELP-20002: cannot find required servlet context parameter: {0}**  
**Cause:** The required servlet context parameter was not found.  
**Action:** Log a bug against the application.

**Level:** 1  
**Type:** ERROR  
**Impact:** Logging

**HELP-20003: critical error in OHW configuration**  
**Cause:** There was a critical error in the Help configuration file.  
**Action:** Verify the correctness of the Help configuration file.

**Level:** 1

---

**Type:** ERROR

**Impact:** Logging

**HELP-20005: cannot instantiate navigator of type: {0}**

**Cause:** The navigator could not be instantiated.

**Action:** Verify the correctness of this navigator type in the Help configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-20006: cannot update auto sync component**

**Cause:** There was a failure when updating the auto sync UI component.

**Action:** Log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-20010: cannot find required ohwConfigFileURL**

**Cause:** OHW Help Provider requires an OHW configuration file, but this file was not found.

**Action:** Ensure that the path points to a valid OHW configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-20011: unable to create global configuration**

**Cause:** The global configuration object could not be created.

**Action:** Log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-20012: unexpected exception when trying to get embedded content for Rich Help Provider**

**Cause:** An unexpected exception was caught when trying to get the embedded content for Rich Help Provider.

**Action:** Log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-30001: cannot find required servlet init parameter {0}**

**Cause:** The required init parameter for the Help servlet was not found.

**Action:** Check the Help servlet definition in the web.xml file of the application.

**Level:** 1

---

**Type:** ERROR

**Impact:** Logging

**HELP-30002: critical error in OHW configuration: {0}**

**Cause:** There was a critical error in the OHW configuration file that caused a MalformedURLException.

**Action:** Correct the OHW configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-30003: Critical error in OHW configuration. Config URL: {0}**

**Cause:** There was a critical error in the OHW configuration file.

**Action:** Correct the OHW configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-30004: failing to load UIX file**

**Cause:** There was a failure when loading the UIX file.

**Action:** Ensure that the UIX file is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-30007: OHW is encountering an unexpected error.**

**Cause:** There was an unexpected error in OHW-UIX.

**Action:** Log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**HELP-30008: cannot instantiate navigator of type {0}**

**Cause:** The specified navigator could not be instantiated.

**Action:** Log a bug against the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

---

## IAU-01023 to IAU-62023

**IAU-01023: Invalid filter preset. The Valid choices are {0}**

**Cause:** The given audit level(filter preset) is invalid.

**Action:** Give a valid audit level(filter preset) like Low,Medium,None,Custom.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01024: Max Dir Size should be atleast double that of min File Size and min File Size should be 4K**

**Cause:** Error in setting the maximum directory size or file size for audit logs.

**Action:** Give a valid value for maximum directory and file size.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01025: Unknown componentType {0} at character position:{1}**

**Cause:** The component type given in custom event expression is invalid.

**Action:** Enter valid component type. listAuditEvents() command gives a list of component types.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01026: Invalid Event Name: {0}**

**Cause:** The event name in custom event expression is invalid.

**Action:** Enter valid event name. listAuditEvents() command gives a list of all the events for a given component.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01027: Invalid component Type: {0}**

**Cause:** The component type given in custom event expression is invalid.

---

**Action:** Give valid component type.`listAuditEvents()` command gives a list of component types.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01028: Can't read components\_dir {0}**

**Cause:** Install is possibly corrupted.

**Action:** Check your install and contact Oracle Customer Support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01029: User {0} not found**

**Cause:** The user to be removed is not in the list of special users(users to always audit).

**Action:** Check for the list of special users(users to always audit)already present using `getAuditPolicy()` command.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01030: Unknown construct . expecting eventName at character position:{0}**

**Cause:** Invalid syntax in custom event expression.

**Action:** Event name is expected at that position.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01031: Unknown event {0} at character position:{1}**

**Cause:** Invalid event in custom event expression.

**Action:** Enter a valid event name. `listAuditEvents()` command gives a list of all the events for a given component.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01032: Expecting SUCCESSIONONLY or FAILURESONLY after the dot at charcter position:{0}**

**Cause:** Invalid syntax in custom event expression.

**Action:** The events name should be qualified with either `SUCCESSIONONLY` or `FAILURESONLY` after the dot.

**Level:** 1

**Type:** ERROR



---

**Impact:** Other

**IAU-01033: Unknown construct . expecting componentType at character position {0}**

**Cause:** componentType is expected at that position.

**Action:** Enter valid component type.listAuditEvents() command gives a list of component types.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01034: Component type {0} is repeated at character position:{1}**

**Cause:** Invalid syntax in custom event expression.

**Action:** Specify a component exactly once giving the list of all events to be added or removed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01035: Missing character after backslash at character position:{0}**

**Cause:** The string at the specified position is invalid.

**Action:** Remove the trailing backslash.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01036: Unterminated quoted string at character position:{0}**

**Cause:** No matching end quote in the string.

**Action:** Check the specified string and add the matching end quote.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01037: custom events can only be specified for custom filter preset**

**Cause:** Custom events are added when the audit level(filter preset) is not Custom.

**Action:** Change the audit level(filter preset) to Custom.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01038: Unexpected token {0} found at character position {1}**

**Cause:** Invalid syntax in custom events expression.

**Action:** Check the custom events expression given.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**IAU-01039: Unfinished string that started at position {0}**

**Cause:** Custom event expression string is not terminated.

**Action:** Check the string and terminate it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01040: Unrecognized token at position {0}**

**Cause:** Invalid syntax in custom events expression.

**Action:** Check for the syntax of custom events expression.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01041: Expecting RHS for the boolean operator {0} at position {1}**

**Cause:** Invalid syntax in custom event expression.

**Action:** Give a RHS value for the boolean operator to evaluate.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01042: Unexpected token {0} found. Expecting -and or -or or ')' at position {1}**

**Cause:** Invalid syntax in custom events expression.

**Action:** Check for the syntax of custom events expression.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01043: Expecting ')' corresponding to '(' at {0}**

**Cause:** There is no matching end brace in custom events expression string.

**Action:** Check the expression and add a closing brace at the end to match with the beginning brace.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01044: Expecting a relation expression at position {0}**

**Cause:** Invalid syntax in custom events expression.

**Action:** Check for the syntax of custom events expression.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**IAU-01045: Operator {0} is not applicable for an attribute of type {1} at position {2}**

**Cause:** Invalid operator given for an attribute in custom events expression.

**Action:** Use an operator that is allowed to be used with the attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01046: Invalid boolean operator {0}**

**Cause:** Invalid syntax in custom events expression.

**Action:** Give a valid boolean operator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01047: Attribute {0} needs a string at position {1}**

**Cause:** The value given for the attribute is not a string.

**Action:** Give a string value in double quotes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01048: Attribute {0} needs a boolean at position {1}**

**Cause:** The value given for the attribute in custom events expression is of a different type.

**Action:** Give a boolean value(true or false) for this attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01049: Attribute {0} needs a number at position {1}**

**Cause:** The value given for the attribute in custom events expression is of a different type.

**Action:** Give a number value for this attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01050: Attribute {0} needs a date at position {1}**

**Cause:** The value given for the attribute in custom events expression is of a different type.

**Action:** Give a date value for this attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**IAU-01051: Cannot parse {0} into a date. Error {1} at {2}**

**Cause:** Date value entered is invalid.

**Action:** Give a valid date value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01052: Unparseable date {0} at position {1}**

**Cause:** Date value entered is invalid.

**Action:** Give a valid date value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01053: Unparseable time {0} at position {1}**

**Cause:** Invalid time given in the custom events expression.

**Action:** Enter valid time format.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01054: Error in expression: unknown operator**

**Cause:** Invalid operator given in a custom events expression.

**Action:** Give a valid operator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01055: Expecting a Boolean value for attrib:{0}**

**Cause:** The value given for the attribute in custom events expression is of a different type.

**Action:** Give a boolean value for the attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01056: Expecting a Number value for attrib:{0}**

**Cause:** The value given for the attribute in custom events expression is of a different type.

**Action:** Give a number value for the attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**IAU-01057: No relational expressions allowed for Binary operator**

**Cause:** Binary attribute is present in the custom events expression.

**Action:** Remove binary attribute from the custom events expression.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01058: Expecting a Date value for attrib:{0}**

**Cause:** A non-date value is given to the date attribute.

**Action:** Give a date value for the attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01059: trailing backslash in special users**

**Cause:** Invalid special users(Users to always audit) string.

**Action:** Remove the trailing back slash in special users(Users to always audit)string.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-01060: Invalid config file**

**Cause:** Config file given in importAuditConfig() command is possibly corrupted.

**Action:** Contact Oracle Customer Support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-05011: Audit Loader initialization failed. The Audit loader is disabled. Caught Exception {0}**

**Cause:** An error prevented the Audit Loader from starting.

**Action:** Check the diagnostic logs and contact Oracle Customer Support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-05042: Error in reading component definition from {0}**

**Cause:** Install might be corrupted.

**Action:** Check the install and contact Oracle Customer Support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**IAU-05043: Cannot create directory for saving AuditLoader state {0}**

**Cause:** OS error in creating directory.

**Action:** Check file permissions and disk space.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-05044: Cannot save AuditLoader state to file {0}**

**Cause:** OS error in writing to state file.

**Action:** Check file permissions and disk space.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-05045: Cannot read AuditLoader state from file {0}**

**Cause:** OS error in reading state file.

**Action:** Check file permissions or the file is possibly corrupted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-05046: Stopping AuditLoader, caught exception: {0}**

**Cause:** An error prevented Audit Loader from continuing.

**Action:** Check the diagnostic logs and contact Oracle Customer Support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-05047: Problem in transferring audit record from file:{0} position:{1} will retry in next cycle. caught exception {2}**

**Cause:** The database containing Audit store is probably down.

**Action:** Check the database availability. Restart the database if required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-05048: Problem in transferring audit record to Repository {0}. Please verify your Repository Configuration**

**Cause:** The database configuration is invalid or the database is down.

**Action:** Check Audit Store configuration and bring up the database if it is down.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**IAU-06001: Error in reading audit configuration file from {0}.**

**Cause:** Install might be corrupted.

**Action:** Check the install and contact Oracle Customer Support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-06002: Invalid {0} directory: {1}.**

**Cause:** Invalid directory path.

**Action:** Check that the directory path is valid and the directory is writable.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-06003: Cannot create directory: {0}.**

**Cause:** Unable to create directory.

**Action:** Check the directory path is valid and the directory is writable.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-06004: Cannot write to {0}: {1}.**

**Cause:** Unable to create directory.

**Action:** Check the directory path is valid and the directory is writable.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-06005: Denied access to log directory: {0}.**

**Cause:** Unable to read/write from/to directory

**Action:** Check the directory path is valid and the directory is writable.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-06006: Error in parsing audit component events definition from {0}.**

**Cause:** Audit configuration file is possibly corrupted.

**Action:** Check the diagnostic logs and contact Oracle Customer Support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-06007: Failed while reloading audit configuration.**

**Cause:** Audit configuration file is possibly corrupted.

---

**Action:** Check the diagnostic logs and contact Oracle Customer Support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-06008: Error while evaluating event auditability.**

**Cause:** Audit configuration file is possibly corrupted.

**Action:** Check the diagnostic logs and contact Oracle Customer Support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-06009: Failed to log audit event.**

**Cause:** Error in loading audit configuration or writing to audit logs.

**Action:** Check the diagnostic logs and contact Oracle Customer Support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-62000: auditor initialization failed**

**Cause:** The auditor structure passed to the initialize audit function was NULL.

**Action:** Check the diagnostic logs and contact Oracle Customer Support.

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Other

**IAU-62001: audit context initialization failed**

**Cause:** Initialization of the audit context had failed.

**Action:** Check the diagnostic logs and contact Oracle Customer Support.

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Other

**IAU-62002: initialization of the xml context failed**

**Cause:** The creation of the xml context used for parsing the xml files had failed.

**Action:** Check the diagnostic logs and contact Oracle Customer Support.

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Other

**IAU-62003: parsing of component\_events.xml file failed**

**Cause:** Install is possibly corrupted.

**Action:** Check the install. Contact Oracle Customer Support if needed.



---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-62004: parsing of auditconfig.xml file failed**

**Cause:** Install is possibly corrupted.

**Action:** Check the install. Contact Oracle Customer Support if needed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-62005: parsing of generic\_events.xml file failed**

**Cause:** Install is possibly corrupted.

**Action:** Check the install. Contact Oracle Customer Support if needed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-62006: ORACLE\_HOME environment variable not set**

**Cause:** The environment variable ORACLE\_HOME was not set.

**Action:** Set the ORACLE\_HOME environment variable.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-62007: COMPONENT\_CONFIG\_PATH environment variable not set**

**Cause:** The environment variable COMPONENT\_CONFIG\_PATH was not set.

**Action:** Set the COMPONENT\_CONFIG\_PATH to point to the location of the auditconfig.xml file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-62008: ORACLE\_INSTANCE environment variable not set**

**Cause:** The environment variable ORACLE\_INSTANCE was not set.

**Action:** Set the ORACLE\_INSTANCE environment variable.

**Level:** 1

**Type:** Error

**Impact:** Other

**IAU-62009: COMPONENT\_NAME environment variable not set**

**Cause:** The COMPONENT\_NAME environment variable was neither set nor was the component\_events.xml file present in the expected default location.

---

**Action:** Check if the component\_events.xml file is present in the expected default location or set the COMPONENT\_NAME environment variable to point to the correct component name.

**Level:** 1

**Type:** Error

**Impact:** Other

**IAU-62010: COMPONENT\_TYPE environment variable was not set**

**Cause:** The COMPONENT\_TYPE environment variable was neither set nor was the component\_events.xml file present in the expected default location.

**Action:** Check if the component\_events.xml file is present in the expected default location or set the COMPONENT\_TYPE environment variable to point to the correct component type.

**Level:** 1

**Type:** Error

**Impact:** Other

**IAU-62011: auditor event failure**

**Cause:** NLL audit event structure was passed.

**Action:** Check the diagnostic logs and contact Oracle Customer Support.

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Other

**IAU-62012: audit event creation failed**

**Cause:** The creation of the audit event failed.

**Action:** Contact Oracle Customer Support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-62013: audit event name not set**

**Cause:** The audit event name was not set.

**Action:** Contact Oracle Customer Support.

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Other

**IAU-62014: audit event category not set**

**Cause:** The audit event category name was not set.

**Action:** Contact Oracle Customer Support.

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Other

---

**IAU-62015: audit custom expression parsing failed**

**Cause:** Parsing of the custom expression had failed.

**Action:** Check if the custom expression used in the audit configuration is valid.

**Level:** 1

**Type:** Error

**Impact:** Other

**IAU-62016: audit log file creation failed**

**Cause:** OS error in creating the file.

**Action:** Check file permissions and disk space.

**Level:** 1

**Type:** Error

**Impact:** Other

**IAU-62017: logging of audit data failed**

**Cause:** Error in loading audit configuration or writing to the audit logs.

**Action:** Check the diagnostic logs for more info. Contact Oracle Customer Support if needed.

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Other

**IAU-62018: timestamp error**

**Cause:** There was a problem with getting the current date and time.

**Action:** Check the diagnostic logs and contact Oracle Customer Support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-62019: audit enabled check failed**

**Cause:** Invalid values assigned to audit event attributes.

**Action:** Check the diagnostic logs and contact Oracle Customer Support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-62020: busstop initialization failed**

**Cause:** The initialization of the busstop structure failed.

**Action:** Contact Oracle Customer Support.

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Other

**IAU-62021: busstop open failed**

---

**Cause:** OS error in creating or opening the bus-stop file.

**Action:** Check the file permissions and disk space.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**IAU-62023: audit config reload failed**

**Cause:** There was a problem in reloading the audit config data that has been modified.

**Action:** Check the diagnostic logs and contact Oracle Customer Support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

## INST-01000 to INST-08013

**INST-01000: Internal Error: Undefined module found: {0}.**

**Cause:** The module {0} present in engineConfig.xml is undefined.

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01001: Abnormal Program Termination.**

**Cause:** The program has experienced an error for some internal or unexpected reason.

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01002: Error: Undefined flag: {0}.**

**Cause:** The flag {0} specified on the command line is not supported.

**Action:** Refer to the usage: setup.exe -help

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-01003: Error: Response file not specified.**

**Cause:** A response file must be provided when installing in the {0} mode.

**Action:** Specify a valid response file. Usage: setup.exe -s -response <Full path to response file>

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-01004: Internal Error: File not found: {0}.**

**Cause:** Page data definition {0} for page {1} not found.

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

---

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01005: Internal Error: Multiple pages found with "{0}" attribute set to true.**

**Cause:** There can be only one page with {0} attribute set to true.

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01006: Internal Error: No page found with the "{0}" attribute set to true.**

**Cause:** At least one page must have the "{0}" attribute set to true.

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01007: Error: Invalid input: "{0}"**

**Cause:** This error is caused due to invalid input on the command line

**Action:** Refer to the command line usage.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-01008: Internal Error: Operation not specified**

**Cause:** Engine did not find an operation to run in this configuration.

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01009: Error: Invalid flags specified for operation "{0}": "{1}"**

**Cause:** Flags specified by the user on the command line are not supported for this operation:{0}

**Action:** Refer to the command line usage.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-01010: Internal Error: Parse error:{0}**

**Cause:** A parse error occurred. The file:"{0}" is not in proper format.

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

---

**Type:** INTERNAL\_ERROR  
**Impact:** Installation

**INST-01011: Internal Error: More than one incompatible operation specified: "{0}", "{1}"**  
**Cause:** Incompatible operation specified  
**Action:** Provide the following files to Oracle Support Services: "{0}""{1}"

**Level:** 1  
**Type:** INTERNAL\_ERROR  
**Impact:** Installation

**INST-01012: Internal Error: More than one incompatible mode is specified at a time: "{0}", "{1}"**  
**Cause:** Incompatible modes specified  
**Action:** Provide the following files to Oracle Support Services: "{0}""{1}"

**Level:** 1  
**Type:** INTERNAL\_ERROR  
**Impact:** Installation

**INST-01013: Internal Error: Default mode not specified for operation:{0}**  
**Cause:** Default mode not specified  
**Action:** Provide the following files to Oracle Support Services: "{0}""{1}"

**Level:** 1  
**Type:** INTERNAL\_ERROR  
**Impact:** Installation

**INST-01014: Internal Error: Default Operation not specified.**  
**Cause:** Default Operation not specified  
**Action:** Contact Oracle Support Services with these log files {0}{1}.

**Level:** 1  
**Type:** INTERNAL\_ERROR  
**Impact:** Installation

**INST-01015: Internal Error: Found cyclic references to page: "{0}". Verify file: "{1}".**  
**Cause:** Cyclic references to other pages were found in the page data file: {0}  
**Action:** Provide the following files to Oracle Support Services: "{0}""{1}"

**Level:** 1  
**Type:** INTERNAL\_ERROR  
**Impact:** Installation

**INST-01016: Internal Error: Multiple references of page: "{0}" found in the "{1}" section for page: "{2}"**  
**Cause:** Multiple next page references are not supported by the Oracle Install Engine.  
**Action:** Provide the following files to Oracle Support Services: "{0}""{1}"

---

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01017: Internal Error: The following pages do not have a default next page specified: "{0}"**

**Cause:** Default Next Page is mandatory for each page.

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01018: Internal Error: Duplicate definition found for pages: "{0}"**

**Cause:** Duplicate definition of pages detected.

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01019: Internal Error: Next page sequence not specified for the following pages: "{0}"**

**Cause:** In cases where multiple next pages follow this page, next page sequence is mandatory to define the page flow.

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01020: Internal Error: Page definition not found for: "{0}"**

**Cause:** Each Page should be accompanied by its page definition in the page data file.

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01021: Internal Error: Page name not specified for file: "{0}"**

**Cause:** Page name not specified

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01022: Internal Error: Page name mismatch. Names specified: "{0}" and "{1}"**

**Cause:** Page name mismatch



---

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01023: Internal Error: Unable to provide usage**

**Cause:** No usage available for this option: {0}. For more help refer this to Oracle Support Services.

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01024: Invalid checkpoint file: {0}.**

**Cause:** The existing checkpoint file is not in the correct format.

**Action:** Delete the invalid checkpoint file:{0}

**Level:** 1

**Type:** WARNING

**Impact:** Installation

**INST-01025: Invalid checkpoint file: {0}. The release and/or version of the product in the checkpoint does not match the current product. {1}.**

**Cause:** Not a valid checkpoint file for the current release/version.

**Action:** Delete the invalid checkpoint file

**Level:** 1

**Type:** WARNING

**Impact:** Installation

**INST-01026: Response File parse error at Line no: {0} - {1}**

**Cause:** The response file may be corrupted or has errors

**Action:** Correct the errors in the response file and try the install operation again. Check if you have missed specifying square brackets around the section names

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-01027: Section name cannot be empty and should be enclosed in square brackets.**

**Cause:** The Response File is not a valid response file. The Section Name is not specified or is not specified properly.

**Action:** The Response Files are organized into 4 sections namely ENGINE, GENERIC, SYSTEM AND APPLICATIONS. Each Section Should be enclosed in square brackets and appropriate entries should be specified under them (Example: [Generic]). Check the Section Names.

---

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-01028: Error: No Section defined.**

**Cause:** The Response File does not have any valid sections specified. The Response File is organized into 4 sections namely ENGINE, GENERIC, SYSTEM and APPLICATIONS. All Section Names are specified within square brackets.

**Action:** Verify the Specified Response Files for valid Section Names and Syntaxes

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-01029: Response File Parse Error : No Equal Symbol "=" was found**

**Cause:** The Format of specifying the value for a variable inside the response file is as VARIABLE\_NAME=VALUE. The Equal Symbol "=" was missed

**Action:** Correct the Response File to specify the value for a variable as VARIABLE\_NAME=VALUE. Insert the Equal Symbol "=" in appropriate position to correct the same

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-01030: Response File Parse Error**

**Cause:** The Variable {0} was not Found in the Response File

**Action:** Specify the Variable in the Response File. The Syntax of specifying a variable is as VARIABLE\_NAME=VALUE

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-01031: Response File Parse Warning. No value found. Ignoring.**

**Cause:** The Variable {0} was found in the Response File with no value assigned to it and hence it was ignored while the Response File was Parsed.

**Action:** Specify the corresponding value.

**Level:** 1

**Type:** WARNING

**Impact:** Installation

**INST-01032: Internal Error: Unable to create the Configuration Manager.**

**Cause:** Configuration Files are not proper:{0}

**Action:** Provide the following files to Oracle Support Services: "{0}""{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

---

**INST-01033: Internal Error: Fatal Error Occurred while loading Configuration Actions.**

**Cause:** Configuration Action Locations specified are incorrect:{0}

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01034: Internal Error: Fatal Error Occurred while publishing Configuration Actions.**

**Cause:** Configuration Actions are improper:{0}

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01035: Internal Error: Fatal Error Occurred while loading Configuration Actions.**

**Cause:** Configuration Actions are improper:{0}

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01036: Internal Error: Fatal Error Occurred while setting data for Configuration Actions.**

**Cause:** Variable: {0} required by Action: {1} not found.

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01037: Internal Error: Fatal Error Occurred while initializing data for Configuration Action.**

**Cause:** Variable: {0} required by Action: {1} not initialized.

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01038: Internal Error: Fatal Error Occurred while loading Configuration Action:{0}.**

**Cause:** Class: {0} not found.

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

---

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01039: Internal Error: Fatal Error Occurred while running lifecycle methods for Configuration Actions.**

**Cause:** Lifecycle Error

**Action:** Provide the following files to Oracle Support Services: "{0}""{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01040: Internal Error: There was an error while copying files to this location: {0}. Installation cannot continue.**

**Cause:** Error in copying files

**Action:** Provide the following files to Oracle Support Services: "{0}""{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01041: Response File Location:{0} is not readable.**

**Cause:** Response File does not exist or does not have read permission. Response File path contains special characters.

**Action:** Ensure that the response file exists and is readable. The response file path must not contain any special characters.Only Alphanumeric, \_, dot, and space characters are allowed.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-01042: An error occurred while reading the response file.**

**Cause:** Response File does not exist at the specified location. Response file is not in the correct format.

**Action:** Ensure that the response file exists. Ensure that the Response File is in the correct format. The Response Files are organized into 4 sections namely ENGINE, GENERIC, SYSTEM AND APPLICATIONS.Each Section Should be enclosed in square brackets and appropriate entries should be specified under them.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-01043: Internal Error: Response File location not defined.**

**Cause:** The file location provided to the writer is empty.

**Action:** Provide the following files to Oracle Support Services: "{0}""{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

---

**INST-01044: Response File Location: {0} is not writable.**

**Cause:** The specified file already exists or user does not have write permission in the given location. Response File path contains special characters.

**Action:** Ensure that the response file location is writable. The response file path must not contain any special characters. Only Alphanumeric, \_, dot and space characters are allowed.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-01045: Response File Parse Error: Section Name "{0}" is invalid.**

**Cause:** Section "{0}" does not exist.

**Action:** Ensure that the Section name is one of the following 1. ENGINE 2. GENERIC 3. SYSTEM 4. APPLICATIONS

**Level:** 1

**Type:** WARNING

**Impact:** Installation

**INST-01046: Internal Error: Invalid Install Session.**

**Cause:** Data Model is empty.

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01047: Silent Install cannot continue, error {0}.**

**Cause:** Data provided in the response file is insufficient to complete this installation. Data provided in the response file is incorrect and did not pass all the validations.

**Action:** Fill the indicated information in the response file and restart installation. Verify and change the indicated values specified in the response file and restart installation.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-01048: Internal Error: Aborting Silent Install.**

**Cause:** Error while running silent install

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01049: There was a problem in creating the page sequence. Response File Data is incomplete. Error: {0}**

---

**Cause:** Data provided in the response file is insufficient to complete this installation.

**Action:** Fill the indicated information in the response file and restart installation.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-01050: Some required prerequisites for this installation have failed.  
Installation cannot continue**

**Cause:** Response File does not exist at the specified location. Response file is not in the correct format.

**Action:** Ensure that the response file exists. Ensure that the Response File is in the correct format. The Response Files are organized into 4 sections namely ENGINE, GENERIC, SYSTEM AND APPLICATIONS. Each Section Should be enclosed in square brackets and appropriate entries should be specified under them.

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01051: Some required prerequisites for this installation have failed.  
Installation cannot continue**

**Cause:** Failed Prerequisite: {0}

**Action:** Take a look at the failed prerequisites and fix the necessary items. Restart the installation after you are done.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Installation

**INST-01052: Error: Property: {0} does not belong to the Section: {1}. It will be ignored.**

**Cause:** All variables in the response files are associated with a valid section. The variable specified in the response file does not belong to the section it appears in.

**Action:** Check if the variable is actually a valid property name and is present in the appropriate section.

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01053: [CONFIG]:: ACTION: {0} running.**

**Cause:**

**Action:**

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Installation

**INST-01054: [CONFIG]:: STEP {0} running.**

---

**Cause:**

**Action:**

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Installation

**INST-01055: Configuration Directory:{0} does not exist.**

**Cause:**

**Action:**

**Level:** 1

**Type:** UNKNOWN

**Impact:** Installation

**INST-01056: The file:{0} cannot be loaded as a configuration action.**

**Cause:** The Configuration framework loads the configuration actions from jars or xml files. This file does not represent a configuration action.

**Action:** Correct the file and retry

**Level:** 1

**Type:** WARNING

**Impact:** Installation

**INST-01057: Invalid Log level: {0} specified.**

**Cause:** Log levels that can be specified on the command line can be: INFO, ERROR, DEBUG

**Action:** Specify a valid log level.

**Level:** 1

**Type:** WARNING

**Impact:** Installation

**INST-01058: Log level changed to: {0}**

**Cause:**

**Action:**

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Installation

**INST-01059: Following checks will be retried by the Prerequisites checker:{0}**

**Cause:**

**Action:**

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Installation

**INST-01060: Error: Prerequisite check: {0} has failed.**

---

**Cause:** Prerequisite check: {0} has failed  
**Action:** Correct the failed prerequisite and retry

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Installation

**INST-01061: Warning: An optional Prerequisite check: {0} has failed.**

**Cause:**

**Action:**

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Installation

**INST-01062: Invalid Inventory Pointer location: {0} specified on the command line.**

**Cause:** Inventory pointer file does not exist. Directory specified for the inventory cannot be created.

**Action:** Create a valid inventory pointer file at the location which is specified on the command line. Inventory pointer file is a property file containing two entries  
inventory\_loc=<Directory where new inventory is present or to be created>  
GROUP=<group of the installing user>

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-01063: Invalid inventory location:{0}.**

**Cause:** Directory specified for the inventory cannot be created.

**Action:** Provide a writable directory for the inventory.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-01064: Oracle home value was not set by the Installer.**

**Cause:** Required Oracle home value not set

**Action:** Provide the following files to Oracle Support Services: "{0}""{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01065: Library: {0} required for Action: {1} not found.**

**Cause:** Required library not found

**Action:** Provide the following files to Oracle Support Services: "{0}""{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation



---

**INST-01066: Configuration Data Store not found.**

**Cause:** Required Configuration Data Store not found

**Action:** Provide the following files to Oracle Support Services: "{0}""{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01067: Error while loading Configuration Actions from file: {0}**

**Cause:** Problem while loading the configuration actions

**Action:** Provide the following files to Oracle Support Services: "{0}""{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01068: No configurations defined for this installation.**

**Cause:**

**Action:**

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Installation

**INST-01069: Internal Error: Unable to load Configuration Action: {0}**

**Cause:** Class not found: {0}

**Action:** Provide the following files to Oracle Support Services: "{0}""{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-01070: Internal Error: Entry Point for Configuration Not Found.**

**Cause:** Entry point not found

**Action:** Provide the following files to Oracle Support Services: "{0}""{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-03000: Error: ClassName is blank in roadmap file for page: {0}**

**Cause:** The ClassName provided for the page named {0} is either null or blank or the class is nonexistent.

**Action:** Provide the following files to Oracle Support Services: "{0}""{1}"

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-03001: Error: ClassName is null or not provided in roadmap file for page: {0}**

---

**Cause:** The ClassName provided for the page named {0} is either null or blank or the class is nonexistent.

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-03002: Error: Class {0} is not found.**

**Cause:** Either Class {0} is not present or it has an invalid format or it has been compiled with a different version of java compiler.

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-03003: Internal Error: Runtime error occurred while loading page : {0}**

**Cause:** Error occurred while loading the class for page {0}

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-03004: Internal Error: The Resource Key name provided is blank**

**Cause:** Resource Key name provided is blank

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-03005: Internal Error: Exception occurred while constructing the Navigation Tree**

**Cause:** Error while constructing the Navigation Tree

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-03006: Internal Error: Exception occurred while preparing the Action Queue**

**Cause:** Error occurred while preparing the Action Queue

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

---

**INST-03007: Internal Error: Exception occurred while loading the help files.**

**Cause:** The help files are corrupt or the help files are not present.

**Action:** Provide the following files to Oracle Support Services: "{0}""{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-03008: Internal Error: Exception occurred while parsing the displayConfig.xml file**

**Cause:** The format of displayConfig.xml is corrupt.

**Action:** Provide the following files to Oracle Support Services: "{0}""{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-03009: Internal Error: Exception occurred launching the welcome window.**

**Cause:** Error occurred launching the welcome window

**Action:** Provide the following files to Oracle Support Services: "{0}""{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-03010: Internal Error: Exception occurred launching the Wizard.**

**Cause:** Error occurred launching the Wizard

**Action:** Provide the following files to Oracle Support Services: "{0}""{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-03011: Internal Error: Exception occurred while setting the UI default properties.**

**Cause:** Error occurred while setting the UI default properties

**Action:** Provide the following files to Oracle Support Services: "{0}""{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-03012: Internal Error: Unknown Exception occurred.**

**Cause:** Unknown exception occurred during installation

**Action:** Provide the following files to Oracle Support Services: "{0}""{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

---

**INST-03013: Internal Error: Exception while creating the Wizard Sequence**

**Cause:** The sequence provided in roadmap.xml is not proper.

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-03014: Internal Error: Exception occurred while creating the validation tree**

**Cause:** Error occurred while creating the validation tree

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-03015: Internal Error: Exception occurred while selecting the next page.**

**Cause:** Error occurred while selecting the next page

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-03016: Internal Error: Exception occurred while updating the data model with user-specified data**

**Cause:** Error occurred while updating the data model with user-specified data

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-03017: Internal Error: Exception occurred while restoring the data from checkpoint.**

**Cause:** The checkpoint data is corrupted.

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-03018: Internal Error: Exception occurred while shrinking the image.**

**Cause:** Either the image is corrupted or the machine has not enough memory to perform the operation.

**Action:** Provide the following files to Oracle Support Services: "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

---

**INST-03019: Internal Error: Error while fetching the image.**

**Cause:** Either the image is not present or the image is corrupted.

**Action:** Provide the following files to Oracle Support Services: "{0}""{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-03020: Error in connecting to the Database. Connect string is missing**

**Cause:** Connect String is missing

**Action:** Provide a valid value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-03021: Error in connecting to the Database**

**Cause:** Unable to connect to the Database with the given credentials

**Action:** Check the values. Make sure the Database is up and running and connect string, user name and password are correct. Enter a valid user name with DBA privileges

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-03022: Error in validating Database details. Schema Type is missing**

**Cause:** Schema Type is missing

**Action:** Provide a valid value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-03023: Error in validating Database details**

**Cause:** Unable to connect to the Database with the given credentials. Listener could be down

**Action:** Check the values. Make sure the Database is up and running and connect string, user name and password are correct. Enter a valid user name with DBA privileges

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-03024: Error in validating Database details**

**Cause:** Unable to connect to the Database with the given credentials. Invalid user name/password

**Action:** Check the values. Make sure the Database is up and running and connect string, user name and password are correct. Enter a valid user name with DBA privileges

---

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-03025: Error in validating Database details**

**Cause:** Unable to connect to the Database with the given credentials. User is not a SYSDBA

**Action:** Check the values. Make sure the Database is up and running and connect string, user name and password are correct. Enter a valid user name with DBA privileges

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-03026: Error in validating Database details**

**Cause:** Unable to connect to the Database with the given credentials. Database could be down

**Action:** Check the values. Make sure the Database is up and running and connect string, user name and password are correct. Enter a valid user name with DBA privileges

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-03027: Error in validating Database details**

**Cause:** Unable to connect to the Database with the given credentials. Invalid service id

**Action:** Check the values. Make sure the Database is up and running and connect string, user name and password are correct. Enter a valid user name with DBA privileges

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-03028: Error in validating Database details**

**Cause:** Unable to connect to the Database with the given credentials. Invalid service name

**Action:** Check the values. Make sure the Database is up and running and connect string, user name and password are correct. Enter a valid user name with DBA privileges

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-03029: Error in validating Database details**

**Cause:** Could not find {0} type Schema in the Database

---

**Action:** Check the values. Make sure the Database is up and running and connect string, user name and password are correct. Enter a valid user name with DBA privileges

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05100: Error in obtaining default DN Value**

**Cause:** Error in processing the handler

**Action:** No default DN provided

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05115: Error in selection of component configuration.**

**Cause:** At least one component needs to be selected for configuration

**Action:** Select at least one of Oracle Directory Integration Platform, Oracle Internet Directory, Oracle Virtual Directory or Oracle Directory Service Manager component to configure.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05116: Error in obtaining Schema names.**

**Cause:** One or more of the Database Connection parameters is missing.

**Action:** Enter all the fields in the screen.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05117: Error in obtaining Schema names.**

**Cause:** The format of Database Host field value is improper.

**Action:** Enter Database Host field in proper format.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05118: The specified username does not have Database Administrator privileges.**

**Cause:** Username {0} does not have Database Administrator privileges.

**Action:** Enter the username with Database Administrator privileges.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

---

**INST-05119: Error in retrieving schema details for component {0}.**

**Cause:** The Schema for corresponding component is not loaded in the Database

**Action:** Make sure that the Database is loaded with the schema {0} or unselect the component {1} from Applications To Configure Screen.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05120: Error in retrieving schema version.**

**Cause:** Schema version for component {0} is missing.

**Action:** Check the values. Make sure the Database is loaded with required schemas.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05121: An unsupported schema is detected.**

**Cause:** The Schema Version for component {0} is less than 10.1.2.0.0

**Action:** This is an unsupported schema version. Upload the newer schema to continue installation.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05122: Upgrade Scenario Detected**

**Cause:** The Schema Version for component Oracle Internet Directory is {0}.

**Action:** The database you selected is associated with a previous version of Oracle Application Server. After the installation is complete, you must run the Oracle Fusion Middleware Upgrade Assistant. Choose YES to continue or NO to go back to the same screen and specify different database details.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05123: Error while retrieving the schema Name.**

**Cause:** The Schema Name for component {0} is missing.

**Action:** Enter valid Database details.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05124: Error in connecting to the Database.**

**Cause:** Could not connect to the Database with the given credentials

**Action:** Check the values. Make sure the Database is up and running and connect string, username and password are correct.



---

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05125: Error in retrieving schema details.**

**Cause:** Database schemas were not found in the Database

**Action:** Run Oracle Metadata Repository Creation Utility and load the schemas.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05126: Error in connecting to the LDAP.**

**Cause:** One or more of LDAP Connection parameters is missing

**Action:** Enter all the fields in the screen.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05127: Error in connecting to the LDAP.**

**Cause:** Could not connect to the LDAP with the given credentials on SSL port

**Action:** Check the values of LDAP Connect parameters. Make sure LDAP HostName and SSL Port are in proper format.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05128: Error while retrieving {0} password from LDAP.**

**Cause:** The {0} password retrieved from LDAP is empty

**Action:** Check the values. Make sure the LDAP details are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05129: Error in connecting to the LDAP.**

**Cause:** Could not connect to the LDAP with the given credentials on SSL port.

**Action:** Check the values. Make sure the LDAP is up and running on SSL port and LDAP Connect String, username and password are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05131: Error in component selection for Oracle Identity Management installation.**

**Cause:** No components selected for Oracle Identity Management installation.

**Action:** Select at least one component for installation.

---

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05135: Error in retrieving default JPS attributes from LDAP.**

**Cause:** The LDAP hostname is missing.

**Action:** Specify a valid Oracle Database eligible for OID upgrade.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05136: Error in retrieving default JPS attributes from LDAP.**

**Cause:** The LDAP port number is missing.

**Action:** Specify a valid Oracle Database eligible for OID upgrade.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05137: Error in retrieving Oracle Internet Directory Details from the database**

**Cause:** The Oracle Internet Directory Details in the database are not available.

**Action:** Check the repository mentioned for Oracle Single Sign On upgrade.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05138: Error in retrieving Oracle Internet Directory Details from the database**

**Cause:** Exception thrown while retrieving Oracle Internet Directory Details from the repository

**Action:** Check the repository mentioned for Oracle Single Sign On upgrade.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05139: Upgrade Scenario Detected**

**Cause:** The Schema Version for component Oracle Single Sign On is {0}

**Action:** The database you selected is associated with a previous version of Oracle Application Server. After the installation is complete, you must run the Oracle Fusion Middleware Upgrade Assistant. Choose YES to continue or NO to go back to the same screen and specify different database details.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05141: Missing Schema Detected**

**Cause:** The {0} component schema is not loaded.

---

**Action:** One or more component schemas are not loaded in the specified database. Choose YES to continue or NO to go back to the same screen and specify different database details.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05142: Missing Schema Detected**

**Cause:** The {0} component schema is not loaded.

**Action:** One or more component schemas are not loaded in the specified database. Choose YES to continue or NO to go back to the same screen and specify different database details.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05145: Error in checking for second OID installation against same database.**

**Cause:** Exception thrown during second OID installation check.

**Action:** Choose valid ODS schema in the screen. Make sure that OID is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05146: ODS Schema in use**

**Cause:** ODS Schema is in use.

**Action:** The ODS schema chosen is already being used by an existing OID. Hence, the new OID being configured would reuse the same schema. Choose YES to continue or NO to choose a different ODS schema.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05147: Missing Schemas Detected**

**Cause:** The {0} component schemas are not loaded.

**Action:** One or more component schemas are not loaded in the specified database. Choose YES to continue or NO to go back to the same screen and specify different database details.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05149: Error in selection of component configuration.**

**Cause:** Selecting DIP only is not allowed for create domain scenario.

**Action:** Select OID also whenever DIP is selected.

---

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05150: Error in selection of component configuration.**

**Cause:** None of the components are selected for configuration.

**Action:** Select at least one component for configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05151: Error in retrieving default JPS attributes from LDAP.**

**Cause:** One or more of LDAP Connection parameters is missing

**Action:** Check the values. Make sure the LDAP details are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05152: Error in validating LDAP Attributes.**

**Cause:** Error in validating LDAP Attributes.

**Action:** Check the values. Make sure the LDAP details are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05155: Error in JPS Attributes validation.**

**Cause:** The value entered in the {0} field is incorrect.

**Action:** Check the value. Make sure the value is present in LDAP.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05156: Error in connecting to LDAP.**

**Cause:** Could not connect to the LDAP with the given credentials.

**Action:** Check the values. Make sure the LDAP is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05159: Partial Schema Detected.**

**Cause:** Partial Schema Detected.

**Action:**

**Level:** 1

**Type:** ERROR

---

**Impact:** Installation

**INST-05162: Error in connecting to LDAP.**

**Cause:** The value entered for OID Administrator Password is incorrect.

**Action:** Check the value. Make sure you have entered a valid value for OID Administrator Password.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05163: Error in connecting to LDAP.**

**Cause:** Error in connecting to LDAP.

**Action:** The LDAP is not up and running. Choose YES to continue or NO to choose a different ODS schema.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05164: {0} is missing.**

**Cause:** {0} is missing.

**Action:** Enter valid value for {0}.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05165: {0} is not valid.**

**Cause:** Error in validating {0}.

**Action:** Enter valid value for {0}.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05166: An unsupported database version is detected.**

**Cause:** The Database version {0} is not supported.

**Action:** Enter Database with version equal to or higher than 10.2.0.4.0 in 10g or version equal to higher than 11.1.0.6.0 in 11g.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05167: Database Initialization Parameter Warning**

**Cause:** The Database initialization parameter 'processes' has a value less than 500.

**Action:** Recommended value for Database initialization parameter 'processes' is 500. Choose YES to continue or NO to go back to the same screen and specify different database details.

---

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05168: Prereqs Error**

**Cause:** Prerequisites requirement check failed. The value of session\_cached\_cursors is less than 100.

**Action:** Required value of session\_cached\_cursors is 100. Specify another Database details.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05169: Validation of Host name failed. Invalid Host**

**Cause:** The host name entered is not valid

**Action:** Provide a valid host name in format host:port

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05170: Validation of Host URL failed. Invalid Host URL**

**Cause:** The host URL entered is not valid

**Action:** Provide a valid host URL in format ldap://host:port or ldaps://host:port

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05171: Error in validating LDAP Credentials**

**Cause:** Specified LDAP Type ( {0} ) is not valid

**Action:** Valid values are "{0}". Enter a valid LDAP Type

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05172: Cannot connect. Specified schema account is locked**

**Cause:** Specified {0} schema account is locked

**Action:** Unlock the {0} schema account.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05173: Multilingual Support Warning**

**Cause:** Multilingual Support Warning

**Action:** The database you are connecting is with non-AL32UTF8 character set. Oracle strongly recommends using AL32UTF8 as the database character set.

---

Choose YES to continue or NO to go back to the same screen and specify different database details.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05174: Schemas existing in Database**

**Cause:** Required schemas are already loaded in the specified database.

**Action:** Specify another database details or select the Use Existing Schema option.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05175: Validation of LDAP Type failed. Invalid LDAP Type**

**Cause:** The LDAP type entered is not valid

**Action:** Provide a valid LDAP type.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05176: Validation of Host URL failed. Invalid Host URL**

**Cause:** The host URL entered is not valid.

**Action:** Provide a valid SSL LDAP connection URL of the format  
ldaps://host:port

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05177: Invalid Oracle Identity Federation schema**

**Cause:** The username entered is not a valid Oracle Identity Federation schema.

**Action:** Provide a valid Oracle Identity Federation schema name.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05178: Error in connecting to LDAP.**

**Cause:** Could not connect to the LDAP in SSL mode with the given credentials.

**Action:** Check the values. Make sure the LDAP is up and running. Provide valid SSL LDAP connection details.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05179: Error in validating Database details**

---

**Cause:** Unable to connect to the Database with the given credentials. Invalid service id

**Action:** Check the values. Make sure the Database is up and running and connect string, user name and password are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05180: Error in validating Database details**

**Cause:** Unable to connect to the Database with the given credentials. Invalid service name

**Action:** Check the values. Make sure the Database is up and running and connect string, user name and password are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05181: Error in validating Database details**

**Cause:** Unable to connect to the Database with the given credentials for {0}. Listener could be down

**Action:** Check the values. Make sure the Database is up and running and connect string, user name and password for {0} are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05182: Error in validating Database details**

**Cause:** Unable to connect to the Database with the given credentials. Invalid user name/password

**Action:** Check the values. Make sure the Database is up and running and connect string, user name and password are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05183: Error in validating Database details**

**Cause:** Unable to connect to the Database with the given credentials. User is not a SYSDBA

**Action:** Check the values. Make sure the Database is up and running and connect string, user name and password are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05184: Error in validating Database details**



---

**Cause:** Unable to connect to the Database with the given credentials. Database could be down

**Action:** Check the values. Make sure the Database is up and running and connect string, user name and password are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05185: Error in validating login table**

**Cause:** The Login Table is not valid.

**Action:** Enter valid Login Table name.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05186: Error in validating user id attribute**

**Cause:** The User ID Attribute is not valid.

**Action:** Enter valid User ID Attribute value.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05187: Error in validating user id attribute**

**Cause:** The User Description Attribute is not valid.

**Action:** Enter valid User Description Attribute value.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05188: Error in validating Oracle Identity Federation User Store RDBMS Attributes**

**Cause:** The Oracle Identity Federation User Store RDBMS Attributes are not valid.

**Action:** Enter valid values for Login Table, User ID Attribute and User Description Attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05189: An unsupported database version is detected.**

**Cause:** The Database version {0} is not supported for upgrade scenario.

**Action:** Enter Database with version equal to or higher than 10.2.0.3.0 or 11.1.0.6.0.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

---

**INST-05190: Unable to connect to Oracle WebLogic Middleware Administration Server. Host name is missing.**

**Cause:** Unable to connect to Oracle WebLogic Middleware Administration Server. Host name is missing.

**Action:** Enter a valid host name

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05191: Error in obtaining connection with Oracle WebLogic Middleware Administration Server**

**Cause:** Unable to connect to Oracle WebLogic Middleware Administration Server. Credentials entered are empty or contain invalid characters

**Action:** Make sure the Middleware Administration Server is up and host name, port, user name and administration password are correct

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05192: Unable to connect to Oracle WebLogic Middleware Administration Server. Port number is missing.**

**Cause:** Unable to connect to Oracle WebLogic Middleware Administration Server. Port number is missing.

**Action:** Enter a valid port

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05193: Unable to connect Oracle WebLogic Middleware Administration Server. Admin User name is missing.**

**Cause:** Unable to connect Oracle WebLogic Middleware Administration Server. Admin User name is missing.

**Action:** Enter a valid admin user name

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05194: Error in obtaining connection with Oracle WebLogic Middleware Administration Server**

**Cause:** Unable to connect to Oracle WebLogic Middleware Administration Server.

**Action:** Make sure the Oracle Middleware Administration Server is up and host name, port, user name and administration password are correct

**Level:** 1

**Type:** ERROR

**Impact:** Installation

---

**INST-05195: Error in installing DIP/ODSM in two different machines.**

**Cause:** Unable to install DIP/ODSM in two different machines.

**Action:** Make sure DIP and ODSM are configured on the same machine.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05196: Error in getting the IP address for the localhost.**

**Cause:** Unable to get the IP Address for the localhost.

**Action:** Make sure that the security manager existing on the system allows access to the IP Address.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05197: Error in validating LDAP Attributes.**

**Cause:** Error in validating Domain Name.

**Action:** Check the values. Make sure the Domain Name is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05198: Specified Oracle Identity Federation schema is not empty.**

**Cause:** Error in validating Oracle Identity Federation schema.

**Action:** Check the values. Make sure the Oracle Identity Federation schema is not loaded with Oracle Identity Federation configuration data.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05199: Error in validating {0}.**

**Cause:** Unable to validate the field {0}.

**Action:** Check the values. Make sure the value for {0} is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05200: Error in validating {0} home location**

**Cause:** Enter a valid value for {0} home location

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Installation

---

**INST-05201: Error in validating {0} home location**

**Cause:** Specified {0} home location does not exist

**Action:** Provide an existing {0} home location

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05202: Error in validating {0} home location**

**Cause:** Specified {0} home location does not have read/write permissions

**Action:** Provide read/write permissions for the {0} home location

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05203: Error in validating {0} home location**

**Cause:** Specified {0} home location is either not valid or empty

**Action:** Enter a valid {0} home location

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05204: Error in validating {0} home location**

**Cause:** Specified {0} home location is not a valid location

**Action:** Enter a valid {0} home location

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05205: Error in validating {0} home location**

**Cause:** An unexpected error occurred during the validation of {0} home location

**Action:** Check the values

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05206: Error in validating Database block size.**

**Cause:** The Database block size is less than 8KB.

**Action:** Make sure that the Database block size is greater than 8KB.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05207: Error in connecting to OID.**

**Cause:** Unable to connect to OID with the given credentials.

---

**Action:** Make sure that the OID is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05208: Missing Schema Detected**

**Cause:** The {0} component schema is not loaded.

**Action:** One or more component schemas are not loaded in the specified database.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05209: Unable to configure DIP and ODSM in two different machines.**

**Cause:** Installer has detected that DIP is already configured on a different machine in the domain, unable to configure ODSM on this machine.

**Action:** Make sure that DIP and ODSM are configured on the same machine.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05210: Unable to configure DIP and ODSM in two different machines.**

**Cause:** Installer has detected that ODSM is already configured on a different machine in the domain, unable to configure DIP on this machine.

**Action:** Make sure that DIP and ODSM are configured on the same machine.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05211: Error in selection of component configuration.**

**Cause:** The values entered for the components to configure are either not valid or empty.

**Action:** Provide valid values for the components to configure.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05212: Error in selection of component configuration.**

**Cause:** Select DIP or ODSM or OIF for configuration in expand cluster flow.

**Action:** Make sure that at least one cluster is selected for configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05213: Warning**

**Cause:** The Database version {0} is not supported.

---

**Action:** Enter Database with version equal to or higher than 10.2.0.4.0 in 10g or version equal to higher than 11.1.0.7.0 in 11g. Refer to the certification matrix for supported database versions.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05214: Error in providing cluster connection information.**

**Cause:** The values entered to connect the cluster are either not valid or empty.

**Action:** Provide valid values to connect the cluster.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05215: Error in finding cluster.**

**Cause:** Could not find a cluster of Identity Management Components in the domain.

**Action:** Make sure to configure at least one cluster in the domain.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05216: Error in obtaining connection with Oracle WebLogic Middleware Administration Server**

**Cause:** Unable to connect to Oracle WebLogic Middleware Administration Server.

**Action:** Make sure the Oracle Middleware Administration Server is up and hostname, port, user name and administration password are correct

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05217: Error in detecting machine platform or JVM bits.**

**Cause:** Unable to detect machine platform or JVM bits.

**Action:** Make sure machine platform and JVM are supported.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05218: Cannot install or configure IDM on a 32-bit JVM on a 64-bit machine.**

**Cause:** Unable to install or configure IDM on a 32-bit JVM on a 64-bit machine.

**Action:** Make sure to install and configure IDM in supported modes.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

---

**INST-05219: Error in providing OID with compatible version.**

**Cause:** OID version is incompatible.

**Action:** Provide OID with compatible version.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-05223: Error in validating Domain.**

**Cause:** Specified domain is not a valid IDM Domain.

**Action:** Provide valid IDM domain details.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07000: Error in validating {0} location**

**Cause:** {0} location specified is null or contains invalid characters

**Action:** The directory name may only contain alphanumeric, underscore (\_), hyphen (-), or dot (.) characters, and it must begin with an alphanumeric character. Provide a different directory name.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07001: Validation of {0} location failed. Null Value**

**Cause:** Provide a valid value for {0} location.

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07002: Validation of {0} location failed. String is too long.**

**Cause:** Specified {0} location: {1} is too long

**Action:** Change the path to a value that is less than or equal to 128 characters

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07003: Validation of {0} location failed. Not Absolute.**

**Cause:** {0} location is not absolute path

**Action:** Provide an absolute path

**Level:** 1

**Type:** ERROR

**Impact:** Installation

---

**INST-07004: Validation of {0} location failed. Invalid Characters.**

**Cause:** {0} location contains one or more invalid characters

**Action:** The directory name may only contain alphanumeric, underscore (\_), hyphen (-), or dot (.) characters, and it must begin with an alphanumeric character. Provide a different directory name.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07005: Validation of {0} location failed. Directory already Exists.**

**Cause:** Validation of {0} location failed. The location specified already exists and is a nonempty directory

**Action:** Provide an empty or nonexistent directory location

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07006: Validation of {0} location failed. No read/write permission.**

**Cause:** Validation of {0} location failed. The location specified does not have read/write permissions

**Action:** Provide a location with read/write permission

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07007: Validation of {0} location failed. Directory exists as a file.**

**Cause:** Validation of {0} location failed. The location specified already exists and is a file

**Action:** Provide an empty or nonexistent directory location

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07008: Validation of {0} location failed. No create permission.**

**Cause:** Validation of {0} location failed. User does not have permission to create home/instance location

**Action:** Make sure that you have the required permission to create the directory

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07009: Error in validating {0} location**

**Cause:** An unexpected error occurred while validating {0} location

**Action:** Enter a valid directory

**Level:** 1



---

**Type:** ERROR

**Impact:** Installation

**INST-07010: Error in validating the Front End URL**

**Cause:** Front End URL value is null or contains invalid characters

**Action:** Provide a valid URL in [http://host.domainname:port] format

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07011: Validation of Front End URL failed. Null Value**

**Cause:** Provide a valid value for Front End URL

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07012: Validation of Front End URL failed. Invalid Protocol**

**Cause:** Validation of Front End URL failed. The protocol entered is not valid

**Action:** Provide a valid protocol. The valid protocol list is {0}

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07013: Validation of Hostname failed. Invalid Host**

**Cause:** The hostname entered is not valid

**Action:** Provide a valid hostname

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07014: Validation of port value failed. Invalid port**

**Cause:** The port entered is not valid

**Action:** Provide a valid port number

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07015: Validation of Front End URL failed. Invalid format**

**Cause:** Validation of Front End URL failed. The front end URL entered is not valid

**Action:** Provide a valid URL in [http://host.domainname:port] format

**Level:** 1

**Type:** ERROR

**Impact:** Installation

---

**INST-07016: Error in validating the Front End URL**

**Cause:** An unexpected error occurred while validating the Front End URL

**Action:** Provide a valid value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07017: Error in obtaining free space**

**Cause:** Error in obtaining free space. Value for drive name contains invalid characters

**Action:** Provide a valid value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07018: Error in obtaining free space. Null Value**

**Cause:** Error in obtaining free space. Value for drive name is null

**Action:** Provide a valid value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07019: Error in obtaining free space**

**Cause:** An unexpected error occurred while calculating available free space

**Action:** Provide a valid value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07020: Error in obtaining default {0} location**

**Cause:** An unexpected error occurred while obtaining default home location

**Action:** Provide a valid value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07021: Error in obtaining available Oracle homes**

**Cause:** An unexpected error occurred while obtaining available Oracle homes

**Action:** Provide a valid value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07033: Error in validating the {0} field value**

---

**Cause:** {0} field value is null or contains invalid characters.

**Action:** Provide a valid value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07034: Error in validating the {0} field value**

**Cause:** Provide a value for {0}

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07035: Error in validating the {0} field value. Length less than minimum length**

**Cause:** {0} has less than {1} characters

**Action:** Length should be at least {0} characters

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07036: Error in validating the {0} field value. Length greater than maximum length**

**Cause:** {0} has more than {1} characters

**Action:** Length should not be greater than {0} characters

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07037: Error in validating the {0} field value. Invalid characters**

**Cause:** {0} field value contains one or more invalid characters or the value is not in proper format.

**Action:** Enter valid characters

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07038: Error in validating the {0} field value. Invalid Start character**

**Cause:** {0} field value contains one or more invalid start characters

**Action:** Enter valid start character

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07039: Error in validating the {0} field value**

---

**Cause:** An unexpected error occurred while validating {0} field value

**Action:** Enter a valid value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07040: Error in Password Check**

**Cause:** Passwords entered were null or contained invalid characters

**Action:** Provide valid values

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07041: Error in Password Check**

**Cause:** An unexpected error occurred while processing the handler

**Action:** Enter passwords that match

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07042: Error in Password Check. Password value null**

**Cause:** Password value is null

**Action:** Enter a valid value for password

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07043: Error in Password Check. Confirm password value null.**

**Cause:** Confirm Password value is null

**Action:** Enter a valid value for confirm password

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07044: Error in Password Check. Passwords do not match**

**Cause:** Passwords entered do not match

**Action:** Enter identical passwords

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07045: Error in validating the {0} field value**

**Cause:** An unexpected error occurred while validating {0} field value

**Action:** Enter a valid number

---

**Level: 1**

**Type: ERROR**

**Impact: Installation**

**INST-07046: Error in validating the {0} field value**

**Cause:** Provide a valid value for {0}

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Installation**

**INST-07047: Error in validating the {0} field value. Not a number**

**Cause:** {0} field value is not a number

**Action:** Enter a valid number

**Level: 1**

**Type: ERROR**

**Impact: Installation**

**INST-07048: Error in Validating {0} and {1}**

**Cause:** Values specified are null or contain invalid characters

**Action:** Provide valid values

**Level: 1**

**Type: ERROR**

**Impact: Installation**

**INST-07049: Error in Validating {0} and {1}**

**Cause:** An unexpected error occurred while validating {0} and {1}

**Action:** Enter values that do not match

**Level: 1**

**Type: ERROR**

**Impact: Installation**

**INST-07050: Error in Validating {0} and {1}. Null Value**

**Cause:** Provide a valid value for {0}

**Action:**

**Level: 1**

**Type: ERROR**

**Impact: Installation**

**INST-07051: Error in Validating {0} and {1}. Values do not match**

**Cause:** {0} and {1} are different

**Action:** Enter same values

**Level: 1**

**Type: ERROR**

---

**Impact:** Installation

**INST-07052: Error in Validating {0} and {1}. Values match**  
**Cause:** {0} and {1} are the same  
**Action:** Enter different values

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07053: Error in validating the {0} field value**  
**Cause:** {0} field value is null or contains invalid characters  
**Action:** Provide valid values

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07054: Error in validating the {0} field value**  
**Cause:** An unexpected error occurred while validating {0} field value  
**Action:** Enter a valid host name

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07055: Error in validating the {0} field value. Host name value null**  
**Cause:** Provide a valid value for {0}  
**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07056: Error in validating the {0} field value. Invalid host name**  
**Cause:** {0} field value is not a valid host name  
**Action:** Enter a valid value for host name

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07057: Error in validating the {0} field value. Host is not up and running**  
**Cause:** Error in validating the {0} field value. Entered host is not up and running  
**Action:** Make sure that the host is up and running

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07058: Error in validating Oracle home location**

---

**Cause:** An unexpected error occurred while validating Oracle home location

**Action:** Provide a valid value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07059: Error in validating Oracle home location**

**Cause:** Oracle home location Specified is missing. Provide a valid Oracle home location

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07060: Error in validating Oracle home location**

**Cause:** The Oracle home location specified is not a valid {0} home location

**Action:** Provide a valid {0} home location

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07061: Error in obtaining default port file location**

**Cause:** An unexpected error occurred while obtaining default port file location

**Action:** Provide a valid value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07062: Error in connecting to the Database**

**Cause:** An unexpected error occurred while trying to connect to the Database

**Action:** Check the values. Make sure the Database is up and running and connect string, user name and password are correct. Enter a valid user name with DBA privileges

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07063: Error in connecting to the Database. Connect String is missing**

**Cause:** Connect string is missing

**Action:** Provide a valid value for Connection String

**Level:** 1

**Type:** ERROR

**Impact:** Installation

---

**INST-07064: Error in connecting to the Database**

**Cause:** Unable to connect to the Database with the given credentials

**Action:** Check the values. Make sure the Database is up and running and connect string, user name and password are correct. Enter a valid user name with DBA privileges

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07065: Error in validating Database details**

**Cause:** An unexpected error occurred while trying to connect to the Database

**Action:** Try again and check the values. Make sure the Database is up and running and connect string, user name and password are correct. Enter a valid user name with DBA privileges

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07066: Error in validating Database details. Schema Type is missing**

**Cause:** Schema type is missing

**Action:** Provide a valid value for Schema Type

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07067: Error in validating Database details. Schema name is missing**

**Cause:** Schema is missing

**Action:** Provide a valid value for Schema Name

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07068: Error in validating Database details. Invalid Schema**

**Cause:** Specified {0} schema does not exist in the given Database

**Action:** Check the schema name and the Database credentials

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07069: Validation of {0} location failed. Existing Oracle home**

**Cause:** Validation of {0} location failed. The location specified is an existing Oracle home

**Action:** Provide an empty or nonexistent directory location

**Level:** 1



---

**Type:** ERROR

**Impact:** Installation

**INST-07072: Error in validating Oracle home location**

**Cause:** The Oracle home location specified is an existing Oracle home

**Action:** Provide an empty or nonexistent directory location

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07073: Error in validating Oracle home location**

**Cause:** The Oracle home location specified is not a valid {0} home location

**Action:** Provide an empty or nonexistent directory location or a valid {0} home location

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07074: Error in validating Database details. Null Value**

**Cause:** User name is missing

**Action:** Provide a valid user name with DBA privileges

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07075: Error in validating Database details. Invalid user**

**Cause:** User does not have DBA privileges

**Action:** Provide a user with DBA privileges

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07076: Error in validating Database details**

**Cause:** An unexpected error occurred while trying to connect to the Database

**Action:** Try again and check the values. Make sure the Database is up and running and connect string, user name and password are correct. Enter a valid user name with DBA privileges

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07077: Error in validating Oracle home and Oracle Instance home**

**Cause:** Oracle home is inside the Oracle Instance home

**Action:** Enter a different location

**Level:** 1

---

**Type:** ERROR

**Impact:** Installation

**INST-07078: Error in validating LDAP credentials**

**Cause:** An unexpected error occurred while validating LDAP credentials

**Action:** Provide a valid value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07079: Error in validating LDAP credentials**

**Cause:** Could not connect to LDAP with the given credentials.

**Action:** Verify the credentials. Make sure that hostname, port and password are correct

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07080: Error in validating available disk space**

**Cause:** Space required is missing or not a valid value

**Action:** Provide a valid value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07081: Error in validating available disk space**

**Cause:** Insufficient space to install the selected components

**Action:** Specify a different Oracle home or increase disk space.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07082: Error in validating available disk space**

**Cause:** An unexpected error occurred while validating available disk space

**Action:** Provide a valid value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07083: Error in validating port file**

**Cause:** Specified port file location is missing

**Action:** Provide a valid value

**Level:** 1

**Type:** ERROR

- 
- Impact:** Installation
- INST-07084: Error in validating port file**  
**Cause:** Specified port file is invalid  
**Action:** Specify a valid file
- Level:** 1
- Type:** ERROR
- Impact:** Installation
- INST-07085: Error in validating port file**  
**Cause:** Specified port file does not exist  
**Action:** Specify a valid file
- Level:** 1
- Type:** ERROR
- Impact:** Installation
- INST-07086: Error in validating port file**  
**Cause:** An unexpected error occurred while parsing the port file  
**Action:** Verify the file. Check if the values are provided in the proper format. There should be at least one section in the file.
- Level:** 1
- Type:** ERROR
- Impact:** Installation
- INST-07087: Error in validating port file**  
**Cause:** An unexpected error occurred while validating port file  
**Action:** Provide a valid value. Check if the values are provided in the proper format. There should be at least one section in the file.
- Level:** 1
- Type:** ERROR
- Impact:** Installation
- INST-07093: Error in validating port file**  
**Cause:** Keys {0} does not have proper values  
**Action:** Provide valid values. Ensure that the port is free, valid and it is not used by any other Oracle home
- Level:** 1
- Type:** ERROR
- Impact:** Installation
- INST-07094: Error in validating port file**  
**Cause:** Ports {0} are not free or not valid  
**Action:** Ensure that the port is free, valid and it is not used by any other Oracle home. If ports are specified using a file, check if proper values are given for key.
- Level:** 1

---

**Type:** ERROR

**Impact:** Installation

**INST-07095: Error in validating port file**

**Cause:** Key {0} does not have proper value

**Action:** Provide a valid value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07096: Required component not found in Oracle home**

**Cause:** One or more of the required components required for the install options selected may be missing from the Oracle home

**Action:** Specify a valid Oracle home with all required Components

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07097: Error in validating component name**

**Cause:** Component name specified is not correct

**Action:** Provide a valid component name

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07098: Error in validating Oracle home location**

**Cause:** Component {0} is not available in the Oracle home but selected for configuration.

**Action:** Deselect the above component for configuration

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07099: Error in validating Oracle home location**

**Cause:** Components {0} are not available in the Oracle home but selected for configuration.

**Action:** Deselect the above components for configuration

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07100: Error in validating port file**

**Cause:** Port {0} is duplicated

**Action:** Provide different ports

**Level:** 1

---

**Type:** ERROR

**Impact:** Installation

**INST-07101: Error in validating port file**

**Cause:** Ports {0} are duplicated

**Action:** Provide different ports

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07102: Error in validating port file**

**Cause:** Port {0} is already used by existing Oracle homes

**Action:** Provide a port which is valid and free

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07103: Error in validating port file**

**Cause:** Ports {0} are already used by existing Oracle homes

**Action:** Provide port values which are valid and free

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07104: Error in validating port file**

**Cause:** Key {0} should not be specified as a range

**Action:** Provide a single port which is valid and free

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07105: Error in validating port file**

**Cause:** Key {0} should not be specified as a range

**Action:** Provide single port values which are valid and free

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07106: Error in validating port file**

**Cause:** Port {0} is not free or not valid

**Action:** Ensure that the port ( a number between 0 - 65535 ) is free and it is not used by any other Oracle home. If ports are specified using a file, check if proper values are given for key

**Level:** 1

---

**Type:** ERROR

**Impact:** Installation

**INST-07107: Error in validating port value**

**Cause:** An unexpected error occurred while validating port value

**Action:** Provide a valid value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07108: Error in validating components selected for configuration**

**Cause:** An unexpected error occurred while processing the handler

**Action:** Select valid components

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07109: Error in validating components selected for configuration**

**Cause:** At least one component should be selected for configuration

**Action:** Select at least one component for configuration

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07110: Error in validating Database details**

**Cause:** Unable to connect to the Database with the given credentials. Invalid service id

**Action:** Check the values. Make sure the Database is up and running and connect string, user name and password are correct. Enter a valid user name with DBA privileges

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07111: Error in validating Database details**

**Cause:** Unable to connect to the Database with the given credentials. Invalid service name

**Action:** Check the values. Make sure the Database is up and running and connect string, user name and password are correct. Enter a valid user name with DBA privileges

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07112: Error in obtaining schema details**

**Cause:** An unexpected error occurred while trying to get schema details

---

**Action:** Try executing again and check the values. Make sure the Database is up and running and connect string, user name and password are correct. Enter a valid user name with DBA privileges

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07113: Error in obtaining schema details**

**Cause:** Error in validating schema details. Could not fetch schema details from database

**Action:** Try executing again and check the values. Make sure the Database is up and running and connect string, user name and password are correct. Enter a valid user name with DBA privileges

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07114: Error in obtaining schema details**

**Cause:** Error in validating schema details. Schema Registry table does not exist

**Action:** Provide a Database which has schemas loaded

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07115: Error in validating {0} schema details**

**Cause:** An unexpected error occurred while validating {0} schema details

**Action:** Try again and check the values. Make sure the Database is up and running and connect string, user name and password are correct. Enter a valid user name with DBA privileges

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07119: Error in validating Database details**

**Cause:** Unable to connect to the Database with the given credentials. Listener could be down

**Action:** Check the values. Make sure the Database is up and running and connect string, user name and password are correct. Enter a valid user name with DBA privileges

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07120: Error in validating Database details**

**Cause:** Unable to connect to the Database with the given credentials. Invalid user name/password

---

**Action:** Check the values. Make sure the Database is up and running and connect string, user name and password are correct. Enter a valid user name with DBA privileges

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07121: Error in validating Database details**

**Cause:** Unable to connect to the Database with the given credentials. User is not a SYSDBA

**Action:** Check the values. Make sure the Database is up and running and connect string, user name and password are correct. Enter a valid user name with DBA privileges

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07122: Error in validating Database details**

**Cause:** Unable to connect to the Database with the given credentials. Database could be down

**Action:** Check the values. Make sure the Database is up and running and connect string, user name and password are correct. Enter a valid user name with DBA privileges

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07123: Error in validating port file**

**Cause:** Specified file is empty or does not contain valid entries

**Action:** Provide a valid file

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07124: Error in validating Oracle home location**

**Cause:** Component {0} is not available in the Oracle home but selected for installation.

**Action:** Deselect the above component

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07125: Error in validating Oracle home location**

**Cause:** Components {0} are not available in the Oracle home but selected for installation.

**Action:** Deselect the above components



---

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07132: Error in validating jpsRootDN value**

**Cause:** User(s) {0} are not present in the specified LDAP

**Action:** Users "fmwadmin" and "systemuser" must be present. The user must also have privileges to create users and groups

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07133: Error in obtaining LDAP bindpass**

**Cause:** User {0} does not have permission to create {1}

**Action:** Users "fmwadmin" and "systemuser" must be present. The user must also have privileges to create users and groups

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07134: Error in validating Oracle Configuration Manager Service credentials**

**Cause:** Customer Identification Number is missing or invalid

**Action:** Provide a valid value for Customer Identification Number

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07135: Error in validating Oracle Configuration Manager Service credentials**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07136: Error in validating Oracle Configuration Manager Service credentials**

**Cause:** Country Code value is incorrect

**Action:** Provide a valid value for Country Code

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07137: Error in validating Oracle Configuration Manager Service credentials**

**Cause:** Could not connect Oracle Configuration Manager Service with the specified credentials

---

**Action:** Verify the values. Make sure the Customer Identification Number, My Oracle Support User Name and the Country code are correct

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07138: Error in validating Oracle Configuration Manager Service credentials**

**Cause:** An unexpected error occurred while validating the Oracle Configuration Manager Service credentials

**Action:** Verify the values and try again

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07139: Error in validating Oracle Configuration Manager Service credentials**

**Cause:** Provide a valid value for Customer Identification Number

**Action:** CSI number must contain numeric characters only

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07144: Error in validating LDAP Credentials**

**Cause:** Specified LDAP Type ( {0} ) is not valid

**Action:** Valid values are "{0}". Enter a valid LDAP Type

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07150: Error in validating jpsRootDN value**

**Cause:** Specified JPS Root DN value is not valid

**Action:** Provide a valid value. Make sure that the root DN provided is an empty container.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07151: Error in validating jpsRootDN value**

**Cause:** Provide a valid value for JPS Root DN

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07152: Error in obtaining LDAP Host**

**Cause:** An unexpected error occurred while processing the handler

---

**Action:** Provide a valid value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07153: Error in obtaining LDAP Port**

**Cause:** An unexpected error occurred while processing the handler

**Action:** Provide a valid value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07154: Error in obtaining LDAP binddn**

**Cause:** An unexpected error occurred while processing the handler

**Action:** Provide a valid value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07155: Error in obtaining LDAP bindpass**

**Cause:** An unexpected error occurred while processing the handler

**Action:** Provide a valid value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07156: Error in validating URL**

**Cause:** Provide a valid value the URL

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07157: Error in validating URL**

**Cause:** URL {0} is not valid

**Action:** Provide a valid URL in [hostname.domainname:port] format and make sure the given URL is accessible

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07158: Error in validating URL**

**Cause:** URL {0} is not accessible.

**Action:** Provide a valid URL which is accessible.

---

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07159: Error in validating URL**

**Cause:** An unexpected error occurred while validating the URL

**Action:** Verify the values and try again

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07169: Error in validating port file**

**Cause:** Port range {0} is not valid. Start range is greater than end range

**Action:** Provide a valid port range

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07172: Error in validating port file**

**Cause:** Key {0} is missing in the section [{1}]

**Action:** Provide a value for the key

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07173: Error in validating port file**

**Cause:** Keys {0} are missing in the section [{1}]

**Action:** Provide valid value for the keys

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07174: Error in validating port file**

**Cause:** Key {0} is not valid in the section [{1}]

**Action:** Valid keys for section [{0}] are {1}

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07175: Error in validating port file**

**Cause:** Keys {0} were not valid in the section [{1}]

**Action:** Valid keys for section [{0}] are {1}

**Level:** 1

**Type:** ERROR

---

**Impact:** Installation

**INST-07176: Error in validating port file**  
**Cause:** Key {0} is duplicated  
**Action:** Remove duplicate entries  
**Level:** 1  
**Type:** ERROR  
**Impact:** Installation

**INST-07177: Error in validating port file**  
**Cause:** Keys {0} are duplicated  
**Action:** Remove duplicate entries  
**Level:** 1  
**Type:** ERROR  
**Impact:** Installation

**INST-07179: Error in validating port file**  
**Cause:** Port range {0} are not valid. Start range is greater than end range  
**Action:** Provide a valid port range  
**Level:** 1  
**Type:** ERROR  
**Impact:** Installation

**INST-07180: Error in validating port file**  
**Cause:** Specified Port range {0} does not have free port.  
**Action:** Provide a different range. Check if the same range is mentioned more than once in the file.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Installation

**INST-07181: Error while obtaining registry key value**  
**Cause:** An error occurred while obtaining a registry key value  
**Action:** Provide a valid value for Registry Key  
**Level:** 1  
**Type:** ERROR  
**Impact:** Installation

**INST-07182: Error while obtaining registry key value**  
**Cause:** An error occurred while obtaining a registry key value  
**Action:** Provide a valid value for Registry Sub Key  
**Level:** 1  
**Type:** ERROR  
**Impact:** Installation

---

**INST-07183: Error while obtaining registry key value**

**Cause:** An error occurred while obtaining a registry key value

**Action:** Provide a valid value for Registry Property Name

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07184: Error while obtaining registry key value**

**Cause:** An unexpected error occurred while obtaining registry key value

**Action:** Verify the values and try again

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07185: Error in validating proxy credentials**

**Cause:** Provide a valid value for Proxy Server

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07186: Error in validating proxy credentials**

**Cause:** Provide a valid value for Proxy Port

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07187: Error in validating proxy credentials**

**Cause:** Specified Proxy port is not a valid value

**Action:** Provide a valid number for Proxy Port

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07188: Error in validating proxy credentials**

**Cause:** Could not establish connection to the specified proxy credentials

**Action:** Verify the values. Make sure the proxy server, proxy port values are correct

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07189: Error in validating proxy credentials**

---

**Cause:** An unexpected error occurred while obtaining registry key value

**Action:** Verify the values and try again

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07202: Error in validating container name**

**Cause:** Provide a valid value for container name

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07203: Error in validating container name**

**Cause:** Specified value is a reserved key word.

**Action:** Provide value other than {0}

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07204: Error in validating container name**

**Cause:** An unexpected error occurred while validating the URL

**Action:** Verify the values and try again

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07205: Error in validating port file**

**Cause:** Port {0} is duplicated for keys {1}

**Action:** Provide different ports

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07206: Error in validating port file**

**Cause:** Port {0} (JMX Port No + 1 ) is not free

**Action:** JMX Port No + 1 will be used as Java Object Cache Local Port No. Specify a value for Java Object Cache Local Port No key or provide a JMX Port No which has also (JMX Port No + 1 ) free

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07207: Error in validating port file**

---

**Cause:** Port {0} (JMX Port No + 2 ) is not free

**Action:** JMX Port No + 2 will be used as Java Object Cache Remote Port No. Specify a value for Java Object Cache Remote Port No key or provide a JMX Port No which has also (JMX Port No + 2 ) free

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07208: Error in validating port file**

**Cause:** Reserved ports are not allowed under section [{0}]. Key(s) {1} have Operating System reserved port entries.

**Action:** Provide different port(s)

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07210: Error in obtaining 10g SSO information**

**Cause:** An unexpected error occurred while obtaining 10g SSO information

**Action:** Verify the LDAP credentials. Make sure that hostname, port, binddn, password are correct

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07211: Error in obtaining Oracle Internet Directory version**

**Cause:** An unexpected error occurred while processing the handler

**Action:** Provide a valid value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07212: Error in checking the version of Oracle Internet Directory**

**Cause:** Version of the given Oracle Internet Directory is not {0}

**Action:** Provide an alternate Oracle Internet Directory location

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07213: Error in checking the version of Oracle Internet Directory**

**Cause:** An unexpected error occurred while checking the version of Oracle Internet Directory

**Action:** Verify the LDAP credentials. Make sure that hostname, port, binddn, password are correct

**Level:** 1



---

**Type:** ERROR

**Impact:** Installation

**INST-07214: Error in validating URL**

**Cause:** Specified URL is not valid

**Action:** Provide a valid value for the URL

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07215: Error in validating URL**

**Cause:** Specified URL is not correct format

**Action:** Provide a valid URL

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07216: Error in validating URL**

**Cause:** Specified URL is not accessible

**Action:** Provide a valid URL

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07217: Error in validating URL**

**Cause:** Specified URL is not accessible

**Action:** Provide a valid URL

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07221: Error in validating database details**

**Cause:** Specified connect string is not in a valid format

**Action:** Provide the value in the following format. Format:  
hostname:port:servicename , For Real Application Cluster Database  
hostname1:port1^hostname2:port2@servicename

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07222: Error in validating database details**

**Cause:** Specified connect string is not in a valid format

**Action:** Provide the value in the following format. Format: hostname:port:sid , For  
a Real Application Cluster Database, use  
hostname1:port1^hostname2:port2@servicename

---

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07223: Error in obtaining work repository details**

**Cause:** Work repository table does not exist

**Action:** Provide a Database which has repositories loaded

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07224: Error in obtaining work repository details**

**Cause:** Error in obtaining work repository details. Could not fetch repository details from database

**Action:** Try executing again and check the values. Make sure the Database is up and running and connect string, user name and password are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07225: Error in validating work repository details**

**Cause:** An unexpected error occurred while validating work repository details

**Action:** Try again and check the values. Make sure the Database is up and running and connect string, user name and password are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07226: Error in validating Database details. Invalid Work Repository**

**Cause:** Specified {0} repository does not exist in the given Database

**Action:** Check the {0} repository name and the Database credentials

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07227: Error in validating work repository details**

**Cause:** Provide a valid {0} repository name

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07228: Error in connecting to the Database**

**Cause:** Unable to connect to the Database with the given credentials

---

**Action:** Check the values. Make sure the Database is up and running and connect string, user name and password are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07229: Error in validating Database details**

**Cause:** Unable to connect to the Database with the given credentials. Listener could be down

**Action:** Check the values. Make sure the Database is up and running and connect string, user name and password are correct

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07230: Error in validating Database details**

**Cause:** Unable to connect to the Database with the given credentials. Invalid user name/password

**Action:** Check the values. Make sure the Database is up and running and connect string, user name and password are correct

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07231: Error in validating Database details**

**Cause:** Unable to connect to the Database with the given credentials. User is not a SYSDBA

**Action:** Check the values. Make sure the Database is up and running and connect string, user name and password are correct

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07232: Error in validating Database details**

**Cause:** Unable to connect to the Database with the given credentials. Database could be down

**Action:** Check the values. Make sure the Database is up and running and connect string, user name and password are correct

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07233: Error in validating Database details**

**Cause:** Unable to connect to the Database with the given credentials. Invalid service id

---

**Action:** Check the values. Make sure the Database is up and running and connect string, user name and password are correct

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07234: Error in validating Database details**

**Cause:** Unable to connect to the Database with the given credentials. Invalid service name

**Action:** Check the values. Make sure the Database is up and running and connect string, user name and password are correct

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07235: Error in validating the {0} field value**

**Cause:** Please enter the {0} field value in the range {1} - {2}

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07236: Error in validating the agent name**

**Cause:** Provide a valid value for the agent name

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07237: Error in validating the agent name**

**Cause:** Agent name already exists. Provide a different value

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07238: Error in validating the agent name**

**Cause:** Unable to verify the agent name

**Action:** Verify the values. Make sure the Master Database is up and running and connect string, user name, password, ODI supervisor username and ODI supervisor password are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

---

**INST-07239: Error in validating Database details. Invalid Schema**

**Cause:** Not able to connect to the specified {0} Schema

**Action:** Check the schema name and the Database credentials

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07240: Error in obtaining {0}components from Oracle WebLogic Middleware Administration Server.**

**Cause:** Error in obtaining {0}components from Oracle WebLogic Middleware Administration Server.

**Action:** Check the given credentials. Make sure the Oracle WebLogic Middleware Administration Server is up and hostname, port, user name and administration password are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07241: Error in obtaining connection with Oracle WebLogic Middleware Administration Server**

**Cause:** Unable to connect to Oracle WebLogic Middleware Administration Server. Credentials entered are null or contains invalid characters

**Action:** Make sure the Middleware Administration Server is up and hostname, port, user name and administration password are correct

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07242: Error in obtaining connection with Oracle WebLogic Middleware Administration Server**

**Cause:** Unable to connect to Oracle WebLogic Middleware Administration Server.

**Action:** Make sure the Oracle Middleware Administration Server is up and hostname, port, user name and administration password are correct

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07243: Unable to connect to Oracle WebLogic Middleware Administration Server. Hostname is missing.**

**Cause:** Unable to connect to Oracle WebLogic Middleware Administration Server. Hostname is missing.

**Action:** Enter a valid hostname

**Level:** 1

**Type:** ERROR

**Impact:** Installation

- 
- INST-07244: Unable to connect to Oracle WebLogic Middleware Administration Server. Port number is missing.**  
**Cause:** Unable to connect to Oracle WebLogic Middleware Administration Server. Port number is missing.  
**Action:** Enter a valid port  
**Level:** 1  
**Type:** ERROR  
**Impact:** Installation
- INST-07245: Unable to connect Oracle WebLogic Middleware Administration Server. Admin User name is missing.**  
**Cause:** Unable to connect Oracle WebLogic Middleware Administration Server. Admin User name is missing.  
**Action:** Enter a valid admin user name  
**Level:** 1  
**Type:** ERROR  
**Impact:** Installation
- INST-07246: Error in validating {0} home location**  
**Cause:** Enter a valid value for {0} home location  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Installation
- INST-07247: Error in validating {0} home location**  
**Cause:** Specified {0} home location is either not valid or missing  
**Action:** Enter a valid {0} home location  
**Level:** 1  
**Type:** ERROR  
**Impact:** Installation
- INST-07248: Error in validating {0} home location**  
**Cause:** Specified {0} home location is not a valid location  
**Action:** Enter a valid {0} home location  
**Level:** 1  
**Type:** ERROR  
**Impact:** Installation
- INST-07249: Error in validating {0} home location**  
**Cause:** An unexpected error occurred during the validation of {0} home location  
**Action:** Check the values  
**Level:** 1  
**Type:** ERROR

---

**Impact:** Installation

**INST-07250: Error in validating Middleware home and WebLogic home**

**Cause:** Specified WebLogic home is not associated with the given Middleware home

**Action:** Enter a WebLogic home which is associated with the specified Oracle Middleware home

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07251: Error in validating Middleware home and WebLogic home**

**Cause:** An unexpected error occurred during the validation of Oracle Middleware home and WebLogic home

**Action:** Check the values

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07252: Error while obtaining default Middleware home and WebLogic home directories**

**Cause:** An unexpected error occurred while obtaining default Oracle Middleware home and WebLogic home directories

**Action:** Check the values

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07253: Error in validating instance name**

**Cause:** Specified instance name is not a valid instance name

**Action:** Enter a valid instance name associated with the specified instance home

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07254: Error in validating instance name**

**Cause:** An unexpected error occurred during the validation of instance name

**Action:** Check the values

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07255: Error in validating instance name**

**Cause:** instance name is incorrect

**Action:** Enter a valid value for instance name

---

**Level:** 1  
**Type:** ERROR  
**Impact:** Installation

**INST-07256: Error in validating {0} component name**  
**Cause:** Component type failed validation  
**Action:** Enter a valid value for {0} component name

**Level:** 1  
**Type:** ERROR  
**Impact:** Installation

**INST-07257: Error in validating component type**  
**Cause:** Component type failed validation  
**Action:** Enter a valid value for component type

**Level:** 1  
**Type:** ERROR  
**Impact:** Installation

**INST-07258: Error in validating component name**  
**Cause:** An unexpected error occurred during the validation of component name  
**Action:** Verify the instance home location

**Level:** 1  
**Type:** ERROR  
**Impact:** Installation

**INST-07259: Error in validating {0} component name**  
**Cause:** Specified value for {0} component name already exists  
**Action:** Provide a different value

**Level:** 1  
**Type:** ERROR  
**Impact:** Installation

**INST-07260: Error in validating {0} component name**  
**Cause:** Specified value for {0} component name is not valid. A directory with the same name already exists under INST\_HOME/config/{0}  
**Action:** Provide a different value

**Level:** 1  
**Type:** ERROR  
**Impact:** Installation

**INST-07261: Error in validating component name**  
**Cause:** Specified component name is not a valid component name  
**Action:** Enter a valid component name associated with the specified instance

**Level:** 1



---

**Type:** ERROR

**Impact:** Installation

**INST-07262: Error in validating instance details in the domain**

**Cause:** Specified instance details are not valid

**Action:** Enter a valid instance name available in the domain. Make sure the instance home entered is in conjunction with the instance name.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07263: Error in validating instance name**

**Cause:** Specified instance name is not valid

**Action:** Enter a valid instance name available in the domain.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07264: Error in validating instance details in the domain**

**Cause:** An unexpected error occurred during the validation of instance details

**Action:** Check the values. Verify the instance name and instance home location

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07265: Error in validating instance name**

**Cause:** An unexpected error occurred during the validation of instance name

**Action:** Check the values. Verify the instance name

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07266: Error in validating component name in the domain**

**Cause:** Specified {0} component name already exists in the domain

**Action:** Provide a different value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07267: Error in validating component name in the domain**

**Cause:** An unexpected error occurred during the validation of component name

**Action:** Check the values. Verify the component name

**Level:** 1

**Type:** ERROR

---

**Impact:** Installation

**INST-07268: Error in validating component name in the domain**

**Cause:** Specified {0} component name does not exist in the domain

**Action:** Enter an existing component name

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07269: Error while obtaining default values for instance name and instance location**

**Cause:** An unexpected error occurred while obtaining default values for instance name and instance location

**Action:** Check the values and try again

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07270: Error in validating instance name in the domain**

**Cause:** Specified instance name already exists in the domain

**Action:** Provide a different value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07271: Error in validating instance name in the domain**

**Cause:** An unexpected error occurred during the validation of instance name

**Action:** Check the values. Verify the instance name

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07272: Error while obtaining the component names from the instance home**

**Cause:** An unexpected error occurred while obtaining the component names from the instance home

**Action:** Check the values. Verify the instance home location

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07273: Error while obtaining the component names of a given component type from the instance home**

**Cause:** An unexpected error occurred while obtaining the component names of a given component type from the instance home

**Action:** Check the values. Verify the instance home location

---

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07274: Error in validating port value**

**Cause:** Port {0} is not valid. Privileged ports are not allowed

**Action:** Provide a different value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07275: Error in validating {0} home location**

**Cause:** Specified {0} home location does not have read/write permissions

**Action:** Provide read/write permissions for the {0} home location

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07276: Error in validating {0} home location**

**Cause:** Enter a valid value for {0} home location

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07277: Error in validating {0} name**

**Cause:** Specified {0} name is either not valid or the corresponding location is not empty

**Action:** Enter a valid {0} name

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07278: Error in validating {0} home location**

**Cause:** Specified {0} home location does not have Read/Write permissions

**Action:** Provide Read/Write permissions for the specified {0} home location

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07279: Error in validating {0} home location**

**Cause:** An unexpected error occurred during the validation of {0} home location

**Action:** Check the values

**Level:** 1

---

**Type:** ERROR  
**Impact:** Installation  
**INST-07280: Error in validating domain credentials**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Installation  
**INST-07281: Error in validating domain credentials**  
**Cause:** {0} is not set up in the specified domain  
**Action:** Enter a domain which has {0} set up  
**Level:** 1  
**Type:** ERROR  
**Impact:** Installation  
**INST-07282: Error in validating {0} home location**  
**Cause:** Specified {0} home location does not exist  
**Action:** Provide an existing {0} home location  
**Level:** 1  
**Type:** ERROR  
**Impact:** Installation  
**INST-07283: Error in validating My Oracle Support Details**  
**Cause:** Specified My Oracle Support Details are not proper  
**Action:** Enter valid values  
**Level:** 1  
**Type:** ERROR  
**Impact:** Installation  
**INST-07284: Error in validating My Oracle Support Details**  
**Cause:** An unexpected error occurred while validating My Oracle Support Details  
**Action:** Check the values  
**Level:** 1  
**Type:** ERROR  
**Impact:** Installation  
**INST-07285: Error in validating Database details. Invalid Schema**  
**Cause:** The schema name {0} and schema type {1} do not match  
**Action:** Provide a valid schema name for {1}  
**Level:** 1  
**Type:** ERROR  
**Impact:** Installation

---

**INST-07286: Error in validating Middleware home location**

**Cause:** Specified Oracle Middleware home location does not have version {0} of WebLogic server. If the version is incorrect then configuring with the Weblogic server will fail.

**Action:** Provide a Oracle Middleware home location which contains WebLogic server with version {0} or upgrade the Weblogic server to {0} and restart the install.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07287: Error in obtaining connection with Oracle WebLogic Middleware Administration Server**

**Cause:** Unable to connect to Oracle WebLogic Middleware Administration Server. Server is not running.

**Action:** Make sure the Middleware Administration Server is up

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07288: Error in obtaining connection with Oracle WebLogic Middleware Administration Server**

**Cause:** Unable to connect to Oracle WebLogic Middleware Administration Server. Invalid username/password

**Action:** Enter a valid username and password

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07289: Error in validating WebLogic Server Directory**

**Cause:** Specified WebLogic Server Directory is either not valid or empty

**Action:** Enter a valid WebLogic Server Directory

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07290: Error in validating Oracle home location**

**Cause:** Specified Middleware home already has a {0} home. Only one {0} home location can reside under a Middleware home.

**Action:** Provide a different Middleware home location

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07291: Error in validating Oracle home location**

**Cause:** Top Component name specified is null.

**Action:** Provide a valid component name

---

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07292: Error in validating Middleware home location**

**Cause:** Middleware home location specified is not a valid location. Provide a valid Middleware home location

**Action:** Provide a valid Middleware home location.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07293: Error in validating SSO credentials**

**Cause:** Given OID does not have a proper SSO.

**Action:** Provide an OID with a 10g SSO.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07294: Error in validating SSO credentials**

**Cause:** Could not retrieve SSO information with the given credentials.

**Action:** Verify the credentials. Make sure that hostname, port and password are correct

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07295: Error in validating UCM Installer Location**

**Cause:** Specified UCM Installer Location is not valid

**Action:** Provide a valid value for UCM Installer Location.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07296: Error in validating UCM Installer Location**

**Cause:** An unexpected error occurred while processing the handler

**Action:** Provide a valid value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07297: Error in validating Web Server HTTP Address**

**Cause:** Webserver HTTP Address is missing

**Action:** Provide a valid value for Webserver HTTP Address

---

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07298: Error in validating Web Server HTTP Address**

**Cause:** Specified Web Server HTTP Address is not valid

**Action:** The Web Server HTTP Address has to be in  
http(s)://[host]:[port]?/[webroot] format

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07299: Error in validating Web Server HTTP Address**

**Cause:** An unexpected error occurred while processing the handler

**Action:** Provide a valid value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07300: Error in validating UCM Installer Location**

**Cause:** UCM Installer Location is missing

**Action:** Provide a valid value for UCM Installer Location

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07301: Error in validating UCM Installer Location**

**Cause:** Specified UCM Installer Location is empty

**Action:** Provide a valid value for UCM Installer Location.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07302: Error in validating Domain**

**Cause:** Specified domain cannot be used for Expand Cluster configuration

**Action:** Specify a domain which has clusters

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07303: Error in validating Domain**

**Cause:** Specified domain cannot be used for Extend Domain configuration

**Action:** Specify a domain which has at least one component not configured

**Level:** 1

---

**Type:** ERROR

**Impact:** Installation

**INST-07304: Validation of User Name failed. Invalid User Name**

**Cause:** The user name entered is not valid

**Action:** Provide a valid user name

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07305: Validation of password value failed. Invalid password**

**Cause:** The password entered is not valid

**Action:** Provide a valid password

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07306: Error in validating Database details. RAC Database is not supported**

**Cause:** RAC Database is not supported for {0}

**Action:** {0}

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07307: Error in validating Oracle home location**

**Cause:** Oracle home location specified is not inside Middleware home location.  
Provide a valid location for Oracle home.

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07308: Oracle Universal Content Management is already installed and configured at location {0}**

**Cause:** Oracle Universal Content Management is already installed and configured at location {0}

**Action:** Either select not to configure again or uninstall Oracle Universal Content Management and then try to reconfigure

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07309: Error in validating master repository details**

**Cause:** Specified Master Repository credentials are not valid.



---

**Action:** Verify the values. Make sure the Master Database is up and running and connect string, user name, password, ODI supervisor username and ODI supervisor password are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07310: Error in validating database details**

**Cause:** Specified connect string is not in a valid format

**Action:** Provide the value in the following format. Format:  
hostname:port:serviceName

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07311: Error in validating database details**

**Cause:** Specified connect string is not in a valid format

**Action:** Provide the value in the following format. Format: hostname:port:sid

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07312: Error in validating database details**

**Cause:** Specified connect string is not in a valid format

**Action:** Provide the value in the following format. Format:  
hostname:port:serviceName , For Real Application Cluster Database  
hostname1:port1^hostname2:port2@serviceName

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07313: Error in validating database details**

**Cause:** Specified connect string is not in a valid format

**Action:** Provide the value in the following format. Format: hostname:port:sid , For a Real Application Cluster Database, use  
hostname1:port1^hostname2:port2@serviceName

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07314: Error in validating port file**

**Cause:** Port {0} is not valid

**Action:** Provide a valid port number ( a number between {0} )

**Level:** 1

**Type:** ERROR

---

**Impact:** Installation

**INST-07315: Error in validating port value**

**Cause:** An unexpected error occurred while validating port value

**Action:** Provide a valid value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07316: Error in validating port file**

**Cause:** Port {0} is not free or not valid

**Action:** Ensure that the port ( a number between 1024 - 65535 ) is free and it is not used by any other Oracle home. If ports are specified using a file, check if proper values are given for key.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07317: Validation of {0} location failed. Directory does not exist.**

**Cause:** Validation of {0} location failed. The location specified does not exist.

**Action:** Enter a valid existing directory

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07318: Validation of {0} location failed. Directory s empty.**

**Cause:** Validation of {0} location failed. The location specified is empty.

**Action:** Enter a nonempty directory

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07404: Error in validating Oracle home**

**Cause:** Specified Oracle home value is null

**Action:** Specify the correct Oracle home name

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07405: Error in validating Oracle home**

**Cause:** The specified Oracle home does not match with the Domain Oracle home

**Action:** Specify Oracle home name same as that of the Domain Oracle home

**Level:** 1

**Type:** ERROR

---

**Impact:** Installation

**INST-07406: Error in validating {0} home location**

**Cause:** Specified {0} home location is either not valid or is empty

**Action:** Enter a valid {0} home location

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07407: Error in detecting machine platform or JVM bits.**

**Cause:** Unable to detect machine platform or JVM bits.

**Action:** Make sure machine platform and JVM are supported.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07408: Cannot install or configure the product on a 32-bit JVM on a 64-bit machine.**

**Cause:** Unable to install or configure the product on a 32-bit JVM on a 64-bit machine.

**Action:** Make sure to install and configure the product in supported modes.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07409: Error in validating instance name**

**Cause:** Unexpected error in validating instance name

**Action:** Make sure entered values are correct

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07410: Error in validating instance name**

**Cause:** Specified instance name is not valid, a windows service with the specified instance name already exists

**Action:** Provide a different instance name

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07411: Error in validating oracle home**

**Cause:** Provide valid value for Oracle Home Directory.

**Action:**

**Level:** 1

**Type:** ERROR

---

**Impact:** Installation

**INST-07412: Error in validating oracle home**

**Cause:** Oracle Home Directory name cannot be oracle\_common.

**Action:** Provide a different value for Oracle Home Directory.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07413: Error in validating oracle home**

**Cause:** Unexpected error in validating Oracle Home Directory

**Action:** Make sure entered values are correct

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07414: Error in validating {0}**

**Cause:** Specified {0} is not valid

**Action:** Provide a valid value {0}

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07415: Error in validating Home Type**

**Cause:** Home Type Specified is not Correct

**Action:** Provide a valid a valid Home Type

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07416: Error in validating {0}**

**Cause:** An unexpected error occurred while validating {0}

**Action:** Provide a valid value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07417: Error in validating the {0}**

**Cause:** {0} has not been installed in the specified {1}. Provide a different Location

**Action:** Provide a different {0}

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07420: Error in validating oracle home**

---

**Cause:** Oracle Home Directory name cannot be {0}.

**Action:** Provide a different value for Oracle Home Directory.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07421: Error in executing the software update flow**

**Cause:** An error occurred while validating the values for software updates

**Action:** Make sure entered values are correct

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07422: Error in validating library**

**Cause:** The library {0} does not exists in the provided location

**Action:** Make sure the library {0} exists in the provided location

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07423: Error in validating library**

**Cause:** The library {0} does not exists in the provided location

**Action:** Make sure the library {0} exists in the provided location

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07424: Error in validating library**

**Cause:** The version of library at the provided location is not as expected

**Action:** Make sure the version of library at the provided location is correct

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07425: Error in verifying version of Application Server**

**Cause:** Could not access versionInfo script under the Application Server Directory provided

**Action:** Make sure the the Application Server directory has versionInfo script under bin folder

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07426: Error in verifying version of Application Server**

---

**Cause:** The version of Application Server is not valid

**Action:** Make sure the the version of Application Server is between {0} and {1}

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07427: Error in verifying Application Server**

**Cause:** The Application Server Directory does not refer to WebSphere Application Server

**Action:** Provide the directory location of WebSphere Application Server

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07440: Error in validating Application Server Type**

**Cause:** Validation of Application Server Type failed. Supported Application Server Types are WLS and WAS.

**Action:** Specify a valid Application Server Type. Supported Application Server Types are WLS and WAS.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07441: Error in validating Application Server Type**

**Cause:** Validation of Application Server Type failed. Specified Application Server Type does not match with the Application Server detected in the Middleware home.

**Action:** Specify a valid Application Server Type.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07520: Error in validating {0} home location**

**Cause:** Enter a valid value for {0} home location

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07521: Error in validating {0} home location**

**Cause:** Specified {0} home location does not exist

**Action:** Provide an exisiting {0} home location

**Level:** 1

**Type:** ERROR

---

**Impact:** Installation

**INST-07522: Error in validating {0} home location**

**Cause:** Specified {0} home location does not have read/write permissions

**Action:** Provide read/write permissions for the {0} home location

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07523: Error in validating {0} home location**

**Cause:** Specified {0} home location is either not valid or empty

**Action:** Enter a valid {0} home location

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07524: Error in validating {0} home location**

**Cause:** Specified {0} home location is not a valid location

**Action:** Enter a valid {0} home location

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07525: Error in validating {0} home location**

**Cause:** An unexpected error occurred during the validation of {0} home location

**Action:** Check the values

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07526: Error in validating {0} home location**

**Cause:** Specified {0} home location is not a valid location

**Action:** Enter a valid {0} home location

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07527: Error in validating Middleware home location**

**Cause:** Specified Oracle Middleware home location does not have appropriate version of WebLogic server

**Action:** Provide a Oracle Middleware home location which contains WebLogic server with a supported version

**Level:** 1

**Type:** ERROR

---

**Impact:** Installation

**INST-07528: Validation of {0} location failed. Directory does not exist.**

**Cause:** Validation of {0} location failed. The location specified does not exist.

**Action:** Enter a valid existing directory

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07529: Error in validating Farm Name**

**Cause:** Farm Name cannot be {0}.

**Action:** Enter a different Farm Name.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07530: Patchset component found in Oracle home**

**Cause:** This Patchset has already been applied to the Oracle home

**Action:** Specify an Oracle home where the patchset has not already been applied.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07531: Error in validating contents of Oracle home**

**Cause:** The Oracle home provided does not contain {0}.

**Action:** In order to patch your existing version please provide an Oracle home that contains the product mentioned above. If you choose to continue, only the oracle\_common directory and any components that both products have in common will be patched.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07532: Error in validating contents of Oracle home**

**Cause:** The Oracle home provided does not contain {0}.

**Action:** In order to patch your existing version please provide an Oracle home that contains the product mentioned above. If you choose to continue, only the oracle\_common directory and any components that both products have in common will be patched.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07533: Error in validating Middleware home location**

**Cause:** Middleware home location specified is missing.

**Action:** Provide a valid Middleware home location



---

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07534: Error in validating Oracle home location**

**Cause:** Oracle home location specified is not inside Middleware home location. Provide a directory name only for Oracle home.

**Action:** Provide a different Oracle home location which is inside Middleware home.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07535: Error in obtaining hostname**

**Cause:** An unexpected error occurred while retrieving hostname

**Action:** Provide a valid value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07536: Error in validating Oracle home location**

**Cause:** Middleware home location specified does not have the required Oracle homes installed in it. The Oracle homes for the following components are not installed: {0}.

**Action:** Provide a different Middleware home location or install the required Oracle Products and try the install again

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07537: The weblogic server processes are still running.**

**Cause:** Unable to install while the weblogic processes are running.

**Action:** Make sure that the node manager and the weblogic servers are shutdown before the installation.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-07538: The OPMN processes are still running.**

**Cause:** Unable to install while the OPMN processes are running.

**Action:** Make sure that opmnctl stopall is run before the installation.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-08001: Validation of Middleware home location failed. Directory path invalid**

---

**Cause:** Validation of Middleware home location failed. The location specified contains missing, mandatory directories

**Action:** Make sure that Oracle/Middleware is in the path

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-08002: SSO Registration Failed.**

**Cause:** IP Address of this machine cannot be obtained.

**Action:** Check the network configuration of this machine

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-08003: Internal Error: SSO Registration Failed.**

**Cause:** There was an error while modifying the Oracle HTTP Server's configuration file.

**Action:** Provide the following files to Oracle Support : "{0}""{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-08004: Internal Error: Installation of Oracle Web Cache failed.**

**Cause:** An unexpected error occurred while trying to create Web Cache component

**Action:** Provide the following files to Oracle Support : "{0}""{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-08005: Internal Error: Installation of Oracle HTTP Server failed.**

**Cause:** An unexpected error occurred while trying to create Oracle HTTP Server component.

**Action:** Provide the following files to Oracle Support : "{0}""{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-08006: Internal Error: Starting OPMN failed.**

**Cause:** An exception occurred while trying to start OPMN

**Action:** Provide the following files to Oracle Support : "{0}""{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

---

**INST-08007: Internal Error: Reload OPMN failed.**

**Cause:** An exception occurred while trying to reload OPMN.

**Action:** Provide the following files to Oracle Support : "{0}""{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-08008: Internal Error: Creation of ReportsServer Component failed.**

**Cause:** An exception occurred while creating the ReportsServer Component

**Action:** Provide the following files to Oracle Support : "{0}""{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-08009: Internal Error: Creation of ReportsTools Component failed.**

**Cause:** An exception occurred while creating the ReportsTools Component

**Action:** Provide the following files to Oracle Support : "{0}""{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-08010: An error occurred while registering the schema: {0} with the WebLogic Server.**

**Cause:** Registering Schema failed with the exception: {0}

**Action:** Check if the Database: {0} is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**INST-08011: Internal Error: Creation of Forms System Component failed.**

**Cause:** An exception occurred while creating the Forms System Component

**Action:** Provide the following files to Oracle Support : "{0}""{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-08012: Internal Error: Creation of FRSystemComponent failed.**

**Cause:** An exception occurred while creating the FRSystemComponent

**Action:** Provide the following files to Oracle Support : "{0}""{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

**INST-08013: Internal Error: Creation of Discoverer System Component failed.**

---

**Cause:** An exception occurred while creating the Discoverer System Component

**Action:** Provide the following files to Oracle Support : "{0}" "{1}"

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Installation

---

## IRM-00001 to IRM-03012

**IRM-00001: The class {0} cannot be found and cannot be unmarshalled by JAXB.**

**Cause:** A class was specified in XML that could not be found.

**Action:** Verify that the class is available and on the class path.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**IRM-00002: The value {0} is not a valid UUID format and cannot be unmarshalled by JAXB.**

**Cause:** A UUID was specified in XML that could not be parsed.

**Action:** Verify the format of the UUID.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**IRM-00003: Creating a field value resulted in an exception.**

**Cause:** Creating a field value resulted in an exception.

**Action:** Review the exception cause for further information.

**Level:** 1

**Type:** WARNING

**Impact:** data

**IRM-00501: The offline store cannot be accessed. It will be recreated.**

**Cause:** The offline store is not from this instance.

**Action:** This is a notification and no action is required.

**Level:** 16

**Type:** NOTIFICATION

**Impact:** data

**IRM-01001: The context identified with UUID {0} does not exist.**

**Cause:** A context was specified that does not exist.

**Action:** Ensure that the context UUID value corresponds to a context stored in the server and retry the operation.

---

**Level:** 32

**Type:** TRACE

**Impact:** Data

**IRM-01002: The test content identified by the name {0} does not exist.**

**Cause:** Test content was specified that does not exist.

**Action:** Each piece of test content is identified by a unique name. Ensure that the provided test content name is correct.

**Level:** 32

**Type:** TRACE

**Impact:** Data

**IRM-01003: There has been an error using a cryptography algorithm.**

**Cause:** An error was encountered while using a cryptography algorithm.

**Action:** Most cryptography exceptions are caused by an exception from the cryptography algorithm implementation. Refer to the exception cause to further diagnose the error. Typical examples of a cryptography exception include attempting to generate a key for a key size that is not supported, or a failure to decrypt due to corrupt data.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**IRM-01004: Unknown or unsupported cryptography schema {0}.**

**Cause:** The cryptographic schema is not known to the system.

**Action:** Ensure that the provided cryptographic schema identity value is supported by the system.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**IRM-01005: The cryptography schema \"{0}\" is unsupported on this platform or configuration.**

**Cause:** An operation was attempted that would have caused a mix of FIPS and non-FIPS key sets to be present in the system.

**Action:** When a key set is created, the cryptography schema details are recorded with the key set. The server is unable to deliver a mix of FIPS and non-FIPS key sets to the desktop. Ensure that the cryptography schema used is compatible with the cryptography schemas already in use by the system.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**IRM-01006: The key set identified with UUID {0} already exists.**

**Cause:** A key set was specified that already exists.

**Action:** Generate a new UUID for the key set and retry the operation.

---

**Level:** 32

**Type:** TRACE

**Impact:** Programmatic

**IRM-01007: The key set identified with UUID {0} does not exist.**

**Cause:** A key set was specified that does not exist.

**Action:** Ensure that the key set specified exists and retry the operation.

**Level:** 16

**Type:** TRACE

**Impact:** Data

**IRM-01008: The {0} wrapping key algorithm is not supported.**

**Cause:** An unsupported key type was supplied for the wrapping key.

**Action:** Ensure that the wrapping key stored in the key store uses a supported algorithm. The supported key types are AES, DESede, and RSA.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**IRM-01010: An exception occurred parsing sealed content: {0}.**

**Cause:** Sealed content was provided that has been corrupted.

**Action:** Obtain a non-corrupted copy of the sealed content. The exception reason will provide more details of what part of the sealed content is corrupt.

**Level:** 16

**Type:** TRACE

**Impact:** Data

**IRM-01011: The sealing process requires non-empty content.**

**Cause:** Content was provided for sealing that was empty.

**Action:** Provide non-empty data to the sealing operation.

**Level:** 32

**Type:** TRACE

**Impact:** Data

**IRM-01012: There has been an error using the key store.**

**Cause:** An error was reported loading or accessing a key store.

**Action:** Examine the exception cause to diagnose the problem further. Typical reasons for this exception include the key store file not being in the configured location and incorrect passwords.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**IRM-01013: The key {0} does not exist in the key store {1}.**

---

**Cause:** A key alias was provided that identified a key that does not exist in the key store.

**Action:** Use tools such as keytool to ensure that the contents of the key store include the key with the specified key alias.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01014: The MIME type {0} is syntactically invalid.**

**Cause:** A MIME type was specified that is syntactically invalid.

**Action:** Correct the MIME type value. The MIME type should consist of a type and subtype (for example, text/plain).

**Level:** 16

**Type:** TRACE

**Impact:** Data

**IRM-01015: Unknown content type/format.**

**Cause:** The content format could not be determined as the content-type HTTP header was missing.

**Action:** Ensure the web service correctly specifies the content type in the HTTP response.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01016: Unsupported content type: {0}.**

**Cause:** An unsupported content type was provided for sealing.

**Action:** None. Sealing cannot be performed on a format that is not supported.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01017: Group accounts are not supported. The group {0} cannot be used in this context.**

**Cause:** A group account was provided to an operation that does not support the use of group accounts.

**Action:** Specify a user and retry the operation.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01018: An error has occurred accessing user or group information.**

**Cause:** An internal exception occurred when accessing the user and group repository (for example LDAP).

**Action:** Refer to the exception cause to further diagnose the error.



---

**Level:** 1

**Type:** WARNING

**Impact:** Data

**IRM-01019: The account identified by {0} is unknown.**

**Cause:** An unknown account was specified.

**Action:** Correct the account UUID or name and retry the operation.

**Level:** 16

**Type:** TRACE

**Impact:** Data

**IRM-01020: The classification is unknown to the system. The classification may have been deleted, may have never existed, or the classification details may be incorrect.**

**Cause:** The classification is unknown to the system. The classification may have been deleted, may have never existed, or the classification details may be incorrect.

**Action:** Correct the classification details and retry the operation.

**Level:** 16

**Type:** TRACE

**Impact:** Data

**IRM-01021: The classification system {0} is not supported.**

**Cause:** A classification system was specified that the server does not support.

**Action:** Check with the server administrator and ensure that the classification system is supported.

**Level:** 16

**Type:** TRACE

**Impact:** Data

**IRM-01022: The configuration setting {0} is not specified, is invalid, or cannot be read.**

**Cause:** A required configuration setting is missing from the configuration, is invalid, or could not be read.

**Action:** Correct the configuration settings.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**IRM-01023: The desktop is repudiated.**

**Cause:** A user's desktop software has been repudiated and can no longer contact the server.

**Action:** Ensure that the client has the appropriate software installed.

**Level:** 16

**Type:** NOTIFICATION

**Impact:** Security

---

**IRM-01024: The feature with id {0} is not present in the list of available features.**

**Cause:** A feature was specified that is not present in the list of available features.

**Action:** Correct the feature id and retry the operation.

**Level:** 32

**Type:** TRACE

**Impact:** Programmatic

**IRM-01025: Licenses are available, but are on the following device(s): {0}.**

**Cause:** A license was requested but all licenses available were in use on other devices.

**Action:** Check in licenses from the listed devices and retry opening content. If licenses must be used on multiple devices at the same time increase the server device count configuration setting.

**Level:** 1

**Type:** TRACE

**Impact:** Other

**IRM-01026: An exception occurred processing a desktop SOAP message: {0}.**

**Cause:** An error occurred while processing a desktop SOAP request or response message.

**Action:** Review the reason property of the exception for further details. This exception typically means that a corrupt or incorrect message was sent to the server.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**IRM-01027: Unsupported protocol version {0}. The required protocol version is {1}.**

**Cause:** A desktop protocol version was provided that the server does not support.

**Action:** Use a lower protocol version and retry the request. The valid range of protocol versions will be specified in the exception details.

**Level:** 16

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**IRM-01028: A new version ({0}) of the desktop is available.**

**Cause:** An upgrade was available for a client's desktop software.

**Action:** Upgrade the desktop software on the client.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**IRM-01029: The account \"{0}\" has already been assigned an administrator role.**

**Cause:** An account could not be assigned the administrator role because it is already assigned.

**Action:** No action is required.

---

**Level:** 32

**Type:** TRACE

**Impact:** Programmatic

**IRM-01030: The account \"{0}\" has already been assigned the role \"{1}\".**

**Cause:** An account could not be assigned the specified role because it is already assigned.

**Action:** No action is required.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01031: The account \"{0}\" has already been assigned an inspector role.**

**Cause:** An account could not be assigned the inspector role because it is already assigned.

**Action:** No action is required.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01032: The account \"{0}\" has already been assigned a manager role.**

**Cause:** An account could not be assigned the manager role because it is already assigned.

**Action:** No action is required.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01033: The specified accounts cannot be removed as this action would remove all administrators.**

**Cause:** The specified accounts could not be removed because there must be at least one administrator for a Domain.

**Action:** Ensure that an administrator will remain following the request and then retry the operation.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01034: The context \"{0}\" cannot be deleted as there are rights assigned within this context.**

**Cause:** A context could not be deleted because there are rights assigned with the context.

**Action:** Remove all rights assigned with the context and retry the operation.

**Level:** 16

**Type:** TRACE

---

**Impact:** Programmatic

**IRM-01035: The context template \"{0}\" cannot be deleted.**

**Cause:** A context template could not be deleted because there are context instances that refer to it.

**Action:** Remove all context instances that refer to the template and retry the operation.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01036: The document role \"{0}\" cannot be deleted as there are rights assigned to this role.**

**Cause:** A document role could not be deleted because there are rights assigned to the role.

**Action:** Remove all rights assigned to the role and retry the operation.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01037: The specified accounts cannot be removed as this action would remove all managers.**

**Cause:** An account could not be removed because there must be at least one manager for a Domain.

**Action:** Ensure that a manager will remain following the request and then retry the operation.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01038: A context with \"{0}\" already exists.**

**Cause:** A context instance UUID was specified that already exists.

**Action:** Use a different context UUID.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01039: The context template \"{0}\" already exists.**

**Cause:** A context template UUID was specified that already exists.

**Action:** Use a different context template UUID. A context template UUID must be unique within the same domain.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01040: The document role \"{0}\" already exists.**

---

**Cause:** A document role UUID was specified that already exists within the domain.

**Action:** Use a different document role UUID. A role UUID must be unique within the same domain.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01041: The domain \"{0}\" already exists.**

**Cause:** A domain UUID was specified that already exists.

**Action:** Use a different UUID.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01042: There are no domains created in the system.**

**Cause:** No domains were available in the system.

**Action:** Create at least one domain in the system.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01043: The context template \"{0}\" is inactive and cannot be used to create contexts.**

**Cause:** An inactive context template was specified.

**Action:** Activate the context template and retry the operation.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01044: The role \"{0}\" cannot be used with template \"{1}\" as their domains do not match.**

**Cause:** An attempt was made to add a role to a template that does not belong to the same domain.

**Action:** Specify a role from the same domain as the template.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01045: The \"{0}\" role must have at least one primary feature.**

**Cause:** A specified document role did not have a primary feature.

**Action:** Add at least one primary feature to the role.

**Level:** 16

**Type:** TRACE

---

**Impact:** Programmatic

**IRM-01046: The \"{0}\" role must have a refresh period greater than one minute.**

**Cause:** A document role specified an invalid time period.

**Action:** Provide a refresh period greater than one minute.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01047: The context template with UUID \"{0}\" on domain \"{1}\" does not exist.**

**Cause:** An unknown context template was specified.

**Action:** Correct the context template UUID and retry the operation.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01048: The right with UUID \"{0}\" does not exist.**

**Cause:** An unknown right was specified.

**Action:** Ensure that the UUID corresponds to a right.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01049: The document role with UUID \"{0}\" on domain \"{1}\" does not exist.**

**Cause:** An unknown document role was specified.

**Action:** Ensure that the UUID corresponds to a document role.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01050: The domain with UUID \"{0}\" does not exist.**

**Cause:** An unknown domain was specified.

**Action:** Ensure that the UUID corresponds to a domain.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01051: The context \"{1}\" does not support role \"{0}\".**

**Cause:** A role was assigned to an account which was not supported by the context.

**Action:** Add the role to the related context template.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

---

**IRM-01052: A dynamic class contains either two stubs or head slices. The duplicate slice class is {0}.**

**Cause:** A dynamic class contained either more than one stub slice or more than one head slice.

**Action:** Alter the dynamic class configuration such that it has at most one stub and one head slice.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**IRM-01053: The dynamic class {0} [{1}] does not contain any implementation slices.**

**Cause:** A dynamic class did not contain any implementation slices.

**Action:** Alter the dynamic class configuration such that it has at least one implementation slice.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**IRM-01054: An error occurred during injection of the {1} on class {0}.**

**Cause:** Injected data was provided for a dynamic class and an error occurred injecting that data.

**Action:** Ensure that the injected data is valid for the dynamic class.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**IRM-01055: Injection data cannot be found for the mandatory injected field {1} on class {0}.**

**Cause:** Injected data was not provided for a dynamic class that required it.

**Action:** Ensure that all mandatory injected data is provided for the dynamic class.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**IRM-01056: The class {0} cannot be used as a slice.**

**Cause:** A dynamic class contained a class that could not be used as a slice.

**Action:** Ensure that the class is derived from the appropriate slice class.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**IRM-01057: The method {1} is not a supported method on the {0} class.**

**Cause:** A slice class provided a list of implemented methods that contained a method not supported by the slice class.

**Action:** Ensure that all implemented methods in the definition are supported by the slice class.

---

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**IRM-01058: The class {0} must implement all the slice methods.**

**Cause:** A dynamic class definition included a stub class that did not implement all of the methods available.

**Action:** Correct the definition of the stub class.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**IRM-01059: The slice purpose annotation on class {0} is not specified.**

**Cause:** A slice class did not specify its purpose using the aspect annotation.

**Action:** Add an appropriate aspect annotation to the slice class implementation.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**IRM-01060: The dynamic class definition file {1} for {0} cannot be loaded.**

**Cause:** The definition for a dynamic class could not be found.

**Action:** Correct the resource path specified for the dynamic class.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**IRM-01061: Not authorized to perform this operation.**

**Cause:** A sealed content operation was attempted which was not authorized.

**Action:** Ensure that the authenticated user has the appropriate license to perform the sealing, resealing, peeking, or unsealing operation. Check that the classification key set is valid. Check the the classification URL is correct. Check that the licenses are not checked out to a different device.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

**IRM-01062: A duplicate {0} element is supplied where a duplicate is not allowed or expected.**

**Cause:** A duplicate element was provided where a duplicate is not allowed/expected.

**Action:** Ensure that the input data does not contain duplicates.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01063: The parameter {1} passed into {0} has an illegal value.**



---

**Cause:** An illegal value was passed as a method argument.

**Action:** Correct the invalid value and retry the operation.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01064: The {0} {1} property cannot exceed {4} characters in length. The invalid value provided was {2}, which has {3} characters.**

**Cause:** A value was used as a property which exceeded the maximum permitted length.

**Action:** Correct the invalid property and retry the operation.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01065: The {0} {1} property has an illegal value.**

**Cause:** An illegal value was specified for a property.

**Action:** Correct the invalid value and retry the operation.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01066: The {0} {1} is immutable and cannot be modified.**

**Cause:** An attempt was made to alter a property that is read-only or immutable.

**Action:** Make a copy of the property to make changes.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01067: An unexpected error has occurred. If this exception does not include details of the cause, then examine the diagnostic logs for more details.**

**Cause:** An unexpected error occurred.

**Action:** Review the exception cause for further details.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**IRM-01068: The parameter {1} passed into {0} is mandatory.**

**Cause:** A mandatory argument was not specified.

**Action:** Provide the value and retry the operation.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

---

**IRM-01069: The {0} {1} property is mandatory.**

**Cause:** A mandatory property was not specified.

**Action:** Provide the value and retry the operation.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01070: The enumeration value {0} is unsupported in this context.**

**Cause:** An unsupported enumeration value was provided.

**Action:** Correct the value and retry the operation.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01071: A response could not be found for method {0} on class %Class%.**

**Cause:** A method invocation required a fixed response and one could not be found.

**Action:** Correct the fixed responses provided to the response slice.

**Level:** 1

**Type:** TRACE

**Impact:** Programmatic

**IRM-01072: The transaction has been rolled back. If this exception does not include details of the cause then examine the diagnostic logs for more details.**

**Cause:** A transaction commit failed.

**Action:** Review the exception cause for further information.

**Level:** 1

**Type:** TRACE

**Impact:** Data

**IRM-01073: The response or method {0} is unsupported by class {1}.**

**Cause:** A response or the method provided to a response slice is not supported.

**Action:** Correct the fixed responses provided to the response slice.

**Level:** 1

**Type:** TRACE

**Impact:** Programmatic

**IRM-01074: The web service endpoint address for the service {0} is missing.**

**Cause:** A web service endpoint address was not specified.

**Action:** Provide the endpoint address for the endpoint.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

---

**IRM-01075: The credentials for the web service could not be determined.**

**Cause:** Web service credentials were not provided.

**Action:** Provide the credentials in the IRM credential store using the web service address as the key.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**IRM-01076: Status page redirected to URI.**

**Cause:** A status page request has been redirected to another system.

**Action:** This is not an error and no action is required by the system administrator.

**Level:** 16

**Type:** TRACE

**Impact:** Requests/Responses

**IRM-01076: The item constraints for role \"{0}\" cannot be altered as the role has been assigned to a user or group.**

**Cause:** An attempt has been made to alter the role item constraints for a role that has been assigned to a user or group.

**Action:** Unassign the users and groups that are using the role.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01077: The encrypted content block size must be a direct multiple of the cipher block size. The cipher block size is {0}, but the encrypted content block size has been set as {1}.**

**Cause:** An illegal encrypted content block size was provided during sealing.

**Action:** Use a block size that is a direct multiple of the cipher block size. Block sizes are typically multiples of 16.

**Level:** 32

**Type:** TRACE

**Impact:** Programmatic

**IRM-01078: The public header cannot exceed {1} bytes in length. The current public header when written as XML has a length of {0} bytes. Reduce the amount of data provided in the custom data or classification cookie.**

**Cause:** A public header exceeded the maximum length.

**Action:** Reduce the amount of data provided in the classification labels or custom data.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01079: The parameter {1} passed into {0} cannot exceed {4} characters in length. The invalid value provided was {2} which has {3} characters.**

---

**Cause:** A value was passed as a method argument which exceeded the permitted length.

**Action:** Correct the invalid value and retry the operation.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01080: Licenses are available, but they cannot be used for the following reasons: {0}.**

**Cause:** A license was available to the user but could not be used for the specified classification.

**Action:** Check the exception for the list of licenses and associated availability status. The availability will provide the reason why the license cannot be used. For example, the license may not support the requested feature or the license may have time constraints that disallow use of the license at the time of the license request.

**Level:** 1

**Type:** TRACE

**Impact:** Other

**IRM-01081: A wrapping key {1} bits in size is insufficient to wrap a {0} bit key.**

**Cause:** A wrapping key could not be used to wrap a key as it was of insufficient size.

**Action:** Increase the size of the wrapping key used or reduce the size of the key being wrapped.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**IRM-01081: The expected size of the unsealed content was {0} bytes in length. The actual number of bytes read from the input stream was {1}.**

**Cause:** The unsealed content size does not match the amount of data read from a stream.

**Action:** Ensure the unsealed content size matches the amount of data provided in the input stream.

**Level:** 16

**Type:** TRACE

**Impact:** Data

**IRM-01082: The locale value {0} is unsupported. Supported locales are {1}.**

**Cause:** An unsupported locale value was specified.

**Action:** Use one of the supported locale values and retry the operation.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

---

**IRM-01083: The device count {0} must be greater than zero and less than or equal to {1}.**

**Cause:** An illegal device count value was specified.

**Action:** Change the device count to a valid value and retry the operation.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01084: The refresh period {0} is too small. Specify a refresh period of one minute or greater.**

**Cause:** An illegal refresh period was specified.

**Action:** Use a refresh period of one minute or greater and retry the operation.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-01085: The scheduled task interval of {0} is illegal. Specify a positive time period.**

**Cause:** An illegal task interval was specified.

**Action:** Use a positive time period greater and retry the operation.

**Level:** 16

**Type:** TRACE

**Impact:** Programmatic

**IRM-03001: An exception occurred retrieving the rights for the context.**

**Cause:** An exception occurred retrieving the rights for a context.

**Action:** Review the exception cause for further information.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**IRM-03002: An exception occurred retrieving the context managers.**

**Cause:** An exception occurred retrieving context managers.

**Action:** Review the exception cause for further information.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**IRM-03003: An exception occurred reading the uploaded file - {0}.**

**Cause:** An exception occurred reading an uploaded file.

**Action:** Review the exception cause for further information.

**Level:** 1

**Type:** WARNING

**Impact:** Data

---

**IRM-03004: An exception occurred retrieving the refresh periods.**

**Cause:** An exception occurred retrieving refresh periods.

**Action:** Review the exception cause for further information.

**Level:** 1

**Type:** SEVERE

**Impact:** Data

**IRM-03005: An exception occurred retrieving the global features.**

**Cause:** An exception occurred retrieving the global features.

**Action:** Review the exception cause for further information.

**Level:** 1

**Type:** SEVERE

**Impact:** Data

**IRM-03006: An exception occurred retrieving the primary features.**

**Cause:** An exception occurred retrieving the primary features.

**Action:** Review the exception cause for further information.

**Level:** 1

**Type:** SEVERE

**Impact:** Data

**IRM-03007: An exception occurred retrieving the feature labels.**

**Cause:** An exception occurred retrieving the feature labels.

**Action:** Review the exception cause for further information.

**Level:** 1

**Type:** SEVERE

**Impact:** Data

**IRM-03008: An exception occurred determining the available locales.**

**Cause:** An exception occurred determining the available locales.

**Action:** Review the exception cause for further information.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**IRM-03009: IRM EJBs are not deployed.**

**Cause:** The IRM EJBs could not be found by the management console.

**Action:** Ensure that the IRM EJBs are deployed and accessible by the web application.

**Level:** 1

**Type:** SEVERE

**Impact:** Installation

**IRM-03010: Domain is not seeded.**

---

**Cause:** No domain was found.

**Action:** Log in to the management console to trigger seeding of the initial domain.

**Level:** 1

**Type:** SEVERE

**Impact:** Configuration

**IRM-03011: User has no role.**

**Cause:** No role could be found for a user.

**Action:** Assign an appropriate role to the user.

**Level:** 32

**Type:** TRACE

**Impact:** Configuration

**IRM-03012: An exception occurred retrieving user details.**

**Cause:** An exception occurred retrieving user details.

**Action:** Review the exception cause for further information.

**Level:** 1

**Type:** WARNING

**Impact:** Data





---

## J2EE HTTPC-00004 to J2EE HTTPC-12011

**J2EE HTTPC-00004: Unable to parse header value: name={0}, value="{1}".**

**Cause:** null

**Action:** null

**Level:** 16

**Type:** TRACE

**Impact:** Requests/Responses

**J2EE HTTPC-00015: Unable to read response for method={0}, path+query="{1}".**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**J2EE HTTPC-00016: Unable to read response for input stream hashCode={0}.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**J2EE HTTPC-00017: Socks: V4 request failure: {0}**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**J2EE HTTPC-01000: Unable to register built-in AuthenticationScheme {0}.**

**Cause:** null

**Action:** null

**Level:** 16

---

**Type:** TRACE

**Impact:** Requests/Responses

**J2EE HTTPC-01001: Unable to register AuthenticationScheme {0} for scheme name {1}.**

**Cause:** null

**Action:** null

**Level:** 16

**Type:** TRACE

**Impact:** Requests/Responses

**J2EE HTTPC-01002: Unable to add NTLM credentials. The AuthorizationHandler does not implement the AuthenticationSchemeRegistryHolder interface.**

**Cause:** null

**Action:** null

**Level:** 16

**Type:** TRACE

**Impact:** Requests/Responses

**J2EE HTTPC-01004: Unable to add NTLM credentials. NTLM AuthenticationScheme was not found in the AuthorizationHandler's AuthenticationSchemeRegistry.**

**Cause:** null

**Action:** null

**Level:** 16

**Type:** TRACE

**Impact:** Requests/Responses

**J2EE HTTPC-01010: AuthM: Handling deferred authorization challenge.**

**Cause:** null

**Action:** null

**Level:** 32

**Type:** TRACE

**Impact:** Requests/Responses

**J2EE HTTPC-01011: AuthM: Sending request with Authorization = "{0}".**

**Cause:** null

**Action:** null

**Level:** 32

**Type:** TRACE

**Impact:** Requests/Responses

**J2EE HTTPC-01012: AuthM: Sending request with Proxy-Authorization = "{0}".**

**Cause:** null

**Action:** null

---

**Level:** 32  
**Type:** TRACE  
**Impact:** Requests/Responses  
**J2EE HTTPC-01013: AuthM: Preemptively sending Proxy-Authorization "{0}".**  
**Cause:** null  
**Action:** null

**Level:** 32  
**Type:** TRACE  
**Impact:** Requests/Responses  
**J2EE HTTPC-01014: AuthM: Preemptively sending Authorization "{0}".**  
**Cause:** null  
**Action:** null

**Level:** 32  
**Type:** TRACE  
**Impact:** Requests/Responses  
**J2EE HTTPC-01015: AuthM: Server refused the given Authorization info {0} times, aborting request.**  
**Cause:** null  
**Action:** null

**Level:** 32  
**Type:** TRACE  
**Impact:** Requests/Responses  
**J2EE HTTPC-01016: AuthM: Status {0} not handling - request has an output stream.**  
**Cause:** null  
**Action:** null

**Level:** 32  
**Type:** TRACE  
**Impact:** Requests/Responses  
**J2EE HTTPC-01017: AuthM: Deferring handling of status {0} due to use of an output stream.**  
**Cause:** null  
**Action:** null

**Level:** 32  
**Type:** TRACE  
**Impact:** Requests/Responses  
**J2EE HTTPC-01018: AuthM: Handling status: {0} "{1}".**  
**Cause:** null  
**Action:** null

---

**Level:** 32  
**Type:** TRACE  
**Impact:** Requests/Responses  
**J2EE HTTPC-01019: AuthM: Resending request with Authorization "{0}".**  
**Cause:** null  
**Action:** null  
**Level:** 32  
**Type:** TRACE  
**Impact:** Requests/Responses  
**J2EE HTTPC-01020: AuthM: Resending request with Proxy-Authorization "{0}".**  
**Cause:** null  
**Action:** null  
**Level:** 32  
**Type:** TRACE  
**Impact:** Requests/Responses  
**J2EE HTTPC-01021: AuthM: Not handling status {0} because finding no Authorization information.**  
**Cause:** null  
**Action:** null  
**Level:** 32  
**Type:** TRACE  
**Impact:** Requests/Responses  
**J2EE HTTPC-01022: AuthM: Parsing {0} challenges:**  
**Cause:** null  
**Action:** null  
**Level:** 32  
**Type:** TRACE  
**Impact:** Requests/Responses  
**J2EE HTTPC-01023: AuthM: Challenge {0}**  
**Cause:** null  
**Action:** null  
**Level:** 32  
**Type:** TRACE  
**Impact:** Requests/Responses  
**J2EE HTTPC-02001: ContentEncMod: pushing gzip-input-stream**  
**Cause:** null  
**Action:** null  
**Level:** 32

---

Type: TRACE  
Impact: Requests/Responses  
**J2EE HTTPC-02002: ContentEncMod: pushing inflater-input-stream**  
Cause: null  
Action: null  
Level: 32  
Type: TRACE  
Impact: Requests/Responses  
**J2EE HTTPC-02003: ContentEncMod: pushing uncompress-input-stream**  
Cause: null  
Action: null  
Level: 32  
Type: TRACE  
Impact: Requests/Responses  
**J2EE HTTPC-02004: ContentEncMod: ignoring "identity" token**  
Cause: null  
Action: null  
Level: 32  
Type: TRACE  
Impact: Requests/Responses  
**J2EE HTTPC-02005: ContentEncMod: Unknown content encoding "{0}".**  
Cause: null  
Action: null  
Level: 1  
Type: TRACE  
Impact: Requests/Responses  
**J2EE HTTPC-03000: ContentMD5Mod: Received digest: "{0}" - pushing md5-check-stream**  
Cause: null  
Action: null  
Level: 32  
Type: TRACE  
Impact: Requests/Responses  
**J2EE HTTPC-03001: ContentMD5Mod: Expecting digest in trailer - pushing md5-check-stream**  
Cause: null  
Action: null  
Level: 32

---

Type: TRACE

Impact: Requests/Responses

**J2EE HTTPC-03003: ContentMD5Mod: successfully verifying hash**

Cause: null

Action: null

Level: 32

Type: TRACE

Impact: Requests/Responses

**J2EE HTTPC-04006: Cookie: Bad Set-Cookie header: "{0}". Finding no equal sign(=) for token starting at position {1}.**

Cause: null

Action: null

Level: 1

Type: TRACE

Impact: Requests/Responses

**J2EE HTTPC-04007: Cookie: Ignoring cookie: {0}**

Cause: null

Action: null

Level: 1

Type: TRACE

Impact: Requests/Responses

**J2EE HTTPC-04008: Cookie: Bad Set-Cookie header: "{0}", invalid date "{1}"**

Cause: null

Action: null

Level: 1

Type: TRACE

Impact: Requests/Responses

**J2EE HTTPC-04009: Bad Set-Cookie header: "{0}", Max-Age "{1}" is negative.**

Cause: null

Action: null

Level: 1

Type: TRACE

Impact: Requests/Responses

**J2EE HTTPC-04011: Cookie: Bad Set-Cookie header: "{0}", domain is empty - ignoring domain.**

Cause: null

Action: null

Level: 1

---

Type: TRACE

Impact: Requests/Responses

**J2EE HTTPC-04012: Cookie: Bad Set-Cookie header: "{0}", current domain "{1}" does not match given parsed "{2}".**

Cause: null

Action: null

Level: 1

Type: TRACE

Impact: Requests/Responses

**J2EE HTTPC-04013: Cookie: Bad Set-Cookie header: "{0}", domain attribute "{1}" is not .local and does not have at least two dots.**

Cause: null

Action: null

Level: 1

Type: TRACE

Impact: Requests/Responses

**J2EE HTTPC-04014: Cookie: Bad Set-Cookie header: "{0}", domain attribute "{1}" is more than one level below current domain {2}.**

Cause: null

Action: null

Level: 1

Type: TRACE

Impact: Requests/Responses

**J2EE HTTPC-04015: Cookie2: Bad Set-Cookie2 header: "{0}", path "{1}" is not a prefix of the request URI "{2}".**

Cause: null

Action: null

Level: 1

Type: TRACE

Impact: Requests/Responses

**J2EE HTTPC-04016: Cookie2: Bad Set-Cookie2 header: "{0}", domain "{1}" is not ".local" and does not contain two "."s.**

Cause: null

Action: null

Level: 1

Type: TRACE

Impact: Requests/Responses

**J2EE HTTPC-04017: Cookie2: Bad Set-Cookie2 header: "{0}", domain "{1}" does not match current host "{2}".**

Cause: null

---

**Action:** null

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**J2EE HTTPC-04018: Cookie2: Bad Set-Cookie2 header: "{0}", domain "{1}" is more than one dot(.) away from host "{2}".**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**J2EE HTTPC-04019: Cookie2: Bad Set-Cookie2 header: "{0}", port list does not include current port {1}.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**J2EE HTTPC-05000: Not handling status {0} {1} because exceeding maximum number of retries.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**J2EE HTTPC-05001: IOE closing InputStream for status 411: {0}**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**J2EE HTTPC-09000: HTTPConnection instance {0} has chunking enabled: {1}.**

**Cause:** null

**Action:** null

**Level:** 32

**Type:** TRACE

**Impact:** Requests/Responses

**J2EE HTTPC-09001: HTTPConnection instance {0} has chunk size set to {1}.**

**Cause:** null



---

**Action:** null

**Level:** 32

**Type:** TRACE

**Impact:** Requests/Responses

**J2EE HTTPC-12000: Setting Maximum Authorization retries to {0}.**

**Cause:** null

**Action:** null

**Level:** 16

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**J2EE HTTPC-12001: "{0}" is enabled**

**Cause:** null

**Action:** null

**Level:** 16

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**J2EE HTTPC-12002: "{0}" is disabled**

**Cause:** null

**Action:** null

**Level:** 16

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**J2EE HTTPC-12003: Version: {0}**

**Cause:** null

**Action:** null

**Level:** 16

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**J2EE HTTPC-12004: Enabling deferred handling of responses to streamed requests.**

**Cause:** null

**Action:** null

**Level:** 16

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**J2EE HTTPC-12005: Setting Socket Idle Timeout to {0} seconds.**

**Cause:** null

**Action:** null

---

**Level:** 16  
**Type:** NOTIFICATION  
**Impact:** Requests/Responses  
**J2EE HTTPC-12006: Adding module {0}.**  
**Cause:** null  
**Action:** null  
**Level:** 16  
**Type:** NOTIFICATION  
**Impact:** Requests/Responses  
**J2EE HTTPC-12007: Adding module {0} to {1} list.**  
**Cause:** null  
**Action:** null  
**Level:** 16  
**Type:** NOTIFICATION  
**Impact:** Requests/Responses  
**J2EE HTTPC-12008: Removing module {0} from {1} list.**  
**Cause:** null  
**Action:** null  
**Level:** 16  
**Type:** NOTIFICATION  
**Impact:** Requests/Responses  
**J2EE HTTPC-12009: Default HTTP proxy set to {0}:{1,number,0}.**  
**Cause:** null  
**Action:** null  
**Level:** 16  
**Type:** NOTIFICATION  
**Impact:** Requests/Responses  
**J2EE HTTPC-12010: Setting Socket Connection Timeout to {0} milliseconds**  
**Cause:** null  
**Action:** null  
**Level:** 16  
**Type:** NOTIFICATION  
**Impact:** Requests/Responses  
**J2EE HTTPC-12011: Setting Socket Read Timeout to {0} milliseconds**  
**Cause:** null  
**Action:** null  
**Level:** 16  
**Type:** NOTIFICATION

---

**Impact:** Requests/Responses



---

## J2EE JMX-46000 to J2EE JMX-47006

---

**J2EE JMX-46000: It is not possible to start a state-manageable instance while it is being stopped.**

**Cause:** A resource that was being stopped was asked to start.

**Action:** Wait until the resource is fully stopped before attempting to restart it.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46001: A state-manageable object is not started. The reason is "{0}".**

**Cause:** A resource could not be started.

**Action:** Correct the root cause cited in the generated message.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46002: It is not possible to stop a state-manageable instance while it is being started.**

**Cause:** A resource that was being started was asked to stop.

**Action:** Wait until the resource is fully started before attempting to stop it.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46003: A state-manageable object is not stopped. The reason is "{0}".**

**Cause:** A resource could not be stopped.

**Action:** Correct the root cause cited in the generated message.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46004: The Notifications and Notification annotations cannot be used together.**

**Cause:** An MBean interface was annotated with both the @Notification and @Notifications annotations.

---

**Action:** Use either @Notification or @Notifications to annotate the MBean interface, but not both.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46005: The Notifications and Notification annotations cannot be used on both the management and implementation classes.**

**Cause:** The @Notification or @Notifications annotation was used on both the MBean interface and MBean implementation class. Only the MBean interface should be annotated with @Notification or @Notifications.

**Action:** Remove the conflicting annotation from the implementation class.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46006: Could not find MBean operation "{0}" for MBean registered under "{1}" and implemented by "{2}"**

**Cause:** Operation signature might not match

**Action:** Verify operation signature against MBean metadata or MBean implementation class

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46007: Error getting MBeanServer for Config MBean "{0}" implemented by "{1}"**

**Cause:** Internal error.

**Action:** No action is required. The default MBeanServer association will be used.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46008: Error initializing the JMX FRamework SPI "{0}"**

**Cause:** Internal error. See nested exception.

**Action:** Based on nested exception root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46009: Error loading the JMX FRamework SPI "{0}"**

**Cause:** Internal error. See nested exception.

**Action:** Based on nested exception root cause.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**J2EE JMX-46010: JMX Portable Framework initialized with platform SPI "{0}"**

**Cause:** The message is informational only.

**Action:** No action is required.

**Level:** 1

**Type:** TRACE

**Impact:** Programmatic

**J2EE JMX-46011: The @Inject annotation can be used only on a method that exposes a single parameter whose type is the type of the resource to be injected.**

**Cause:** The JMX MBean @Inject annotation was used on a method that did not have a single parameter with the proper type.

**Action:** Change the associated MBean method to have a single parameter with the proper type or replace the @Inject annotation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46012: Error registering MBean whose ObjectName is "{0}" and implementation class is "{1}"**

**Cause:** See nested exception.

**Action:** Based on nested exception root cause.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46013: The {0} argument cannot be null.**

**Cause:** An argument was passed a null value, which is invalid. The name of the argument is specified as part of the generated message.

**Action:** Change the argument value to be a valid non-null value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46014: A notification listener for MBean "{0}" cannot be added.**

**Cause:** The MBean did not declare that it sends notifications.

**Action:** Change the MBean code to declare that it sends notifications or remove the code that attempts to register a notification listener for the MBean.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46015: The resource with key "{0}" and bundle "{1}" declared in the Description annotation on attribute "{2}" of MBean "{3}" cannot be found.**

---

**Cause:** The resource defined by the Description annotation that was associated with an MBean attribute was missing. The generated message specified the MBean, attribute, resource key and resource bundle.

**Action:** Ensure that the Description annotation includes the correct resourceBundleBaseName key and that the default resource bundle exists.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46016: The resource with key "{0}" and bundle "{1}" declared in the Description annotation on operation "{2}" of MBean "{3}" cannot be found.**

**Cause:** The resource defined by a Description annotation that was associated with an MBean operation was missing. The generated message specified the MBean, operation, resource key and resource bundle.

**Action:** Ensure that the Description annotation includes the correct resourceBundleBaseName key and that the default resource bundle exists.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46017: The resource with key "{0}" and bundle "{1}" declared in the Description annotation on parameter "{2}" of operation "{3}" of MBean "{4}" cannot be found.**

**Cause:** The resource defined by a Description annotation that was associated with an MBean operation parameter was missing. The generated message specified the MBean, operation, parameter name, resource key and resource bundle.

**Action:** Ensure that the Description annotation includes the correct resourceBundleBaseName and that the default resource bundle exists.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46018: The resource with key "{0}" and bundle "{1}" declared in the Description annotation on MBean "{2}" cannot be found.**

**Cause:** The resource defined by a Description annotation that was associated with an MBean interface was missing. The generated message specified the MBean, resource key and resource bundle.

**Action:** Ensure that the Description annotation includes the correct resourceBundleBaseName key and that the default resource bundle exists.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46019: The resource with key "{0}" and bundle "{1}" declared in the Description annotation on feature "{2}" of MBean "{3}" cannot be found.**

**Cause:** A resource that was defined in one of the MBean descriptors properties (descriptionResourceKey or descriptionResourceBundleBaseName) was missing. The generated message specified the MBean, resource key and resource bundle.



---

**Action:** Add the resource or change the MBean descriptor property.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**J2EE JMX-46020: No PersistenceManager is declared for MBean "{0}".**

**Cause:** The PersistenceManagers were missing.

**Action:** When PMCompositeConfigMBeanSupport is used, specify a shared PersistenceManager or specify individual PersistenceManagers for the two config files (use injection-name 'file1' and 'file2' in mbeans.xml).

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46021: The Persistable for MBean "{0}" is not defined.**

**Cause:** The expected Persistable for the MBean was missing.

**Action:** Provide the Persistable for the MBean.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46022: A resource bundle name must be specified in order to use message localization methods.**

**Cause:** The resource bundle name was missing.

**Action:** Define the resource bundle name.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46023: A shared PersistenceManager and an individual PersistenceManager cannot both be declared for MBean "{0}".**

**Cause:** Both a shared and an individual PersistenceManager were declared for the MBean.

**Action:** When PMCompositeConfigMBeanSupport is used, specify either one shared persistence manager with no injection name, or two persistence managers with injection names "file1" and "file2", in mbeans.xml.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46024: At least one configuration object used by MBean "{0}" for type "{1}" is not registered.**

**Cause:** At least one of the configuration objects used by a Composite ConfigMBean was not registered.

**Action:** Register the appropriate configuration object.

---

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46025: The type "{1}" used for MBean "{0}" is not valid for either configuration object "{2}" or "{3}".**

**Cause:** The type used for a configuration object for the MBean was not valid.

**Action:** Use the correct type for the configuration object.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46026: The configuration file with injection name "{1}" for MBean "{0}" cannot be found.**

**Cause:** The configuration file is missing or the injection name is incorrect.

**Action:** Verify that the injection name and the configuration file path are properly specified.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46027: The configuration at URI "{0}" cannot be loaded.**

**Cause:** The value for location in the configuration file was invalid.

**Action:** Verify that the value of location in the configuration file is properly specified.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46028: MBean "{0}" cannot be registered,**

**Cause:** An MBean was already registered with the same name. It should have been removed when the application was either stopped or undeployed.

**Action:** Examine and correct the errors that resulted when the application was stopped or undeployed, and repeat the stop or undeployment operation.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46029: The configuration file "{0}" for MBean "{1}" cannot be found.**

**Cause:** The value for location in the configuration file was invalid.

**Action:** Verify that the value of location in the configuration file is properly specified.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

---

**J2EE JMX-46030: failure to register MBean "{0}" during application initialization.**

**Cause:** Registering the MBean during application initialization caused an error.

**Action:** Use the information from the exception stack trace to determine the cause of the error.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46031: failure to unregister MBean "{0}" during application shutdown.**

**Cause:** Unregistering the MBean during application shutdown caused an error.

**Action:** Use the information from the exception stack trace to determine the cause of the error.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46032: The RequiredApplicationPermission or RequiredSystemPermission annotation is incorrect.**

**Cause:** The RequiredApplicationPermission or RequiredSystemPermission annotation did not specify a nonempty action array.

**Action:** Specify a nonempty action array.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46033: The Description annotation on method "{0}" of class "{1}" is incorrect.**

**Cause:** The Description annotation resourceKey was null.

**Action:** Ensure that the resourceKey for the Description annotation is not null for the method cited in the error message.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46034: No annotation should be put on attribute mutator parameter "{0}".**

**Cause:** The mutator parameter for an attribute has an annotation.

**Action:** Remove all annotation from the attribute's mutator parameter.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46035: The Description annotations on the mutator and accessor of attribute "{0}" are in conflict.**

**Cause:** Both the mutator and the accessor were annotated. Ideally, only the mutator should be annotated. The message key and the message bundle were not identical on both the mutator and the accessor, and must be if both are annotated.

---

**Action:** Either remove the annotation on the accessor or ensure that the message key and the message bundle are identical on both the accessor and the mutator.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46036: OpenType "{0}" cannot be converted to a Class<?> instance.**

**Cause:** The OpenType was not an instance of Class or ParameterizedType or GenericArrayType, and it must be.

**Action:** Ensure that the OpenType is an instance of Class or ParameterizedType or GenericArrayType.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46037: The class "{0}" cannot be converted to OpenType.**

**Cause:** The custom type was wrong.

**Action:** Use a custom type that can be converted to OpenType.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46038: There is an OpenType conversion error "{0}".**

**Cause:** An OpenType conversion resulted in an error.

**Action:** See the information cited within the error message for details about the error.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46039: The ModelMBeanInfo for class "{0}" does not have a Descriptor.**

**Cause:** The ModelMBeanInfo did not have a Descriptor.

**Action:** Add a Descriptor to the ModelMBeanInfo.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Programmatic

**J2EE JMX-46040: A key for the resource bundle "{0}" cannot be null.**

**Cause:** The key for the message was null.

**Action:** Provide a resource bundle key that is not null.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46041: The resource for bundle "{0}" with key "{1}" cannot be found.**

---

**Cause:** There was no resource found in the resource bundle for the given key.

**Action:** Add the key to the resource bundle.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46042: The resource in bundle "{0}" for key "{1}" is not a String.**

**Cause:** The resource found for the given key was not a String.

**Action:** Ensure that the resource is a String.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46043: The JMX Config Session instance passed to the Config MBean Factory is null.**

**Cause:** The JMX Config Session instance passed to the Config MBean Factory was null.

**Action:** Associate the MBean creation with a valid JMX Config Session instance.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46044: Resource bundle "{0}" cannot be found.**

**Cause:** The resource bundle was missing.

**Action:** Provide the resource bundle.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46045: An error occurred while processing MBeanInfo for MBean "{0}".**

**Cause:** The MBeanInfo was not correct.

**Action:** Use the error information to correct the MBeanInfo.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46046: The ConfigMBean PersistenceManager is not of type DualDataSourcePersistenceManager.**

**Cause:** The PersistenceManager was not of type DualDataSourcePersistenceManager.

**Action:** Correct the type of the PersistenceManager.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**J2EE JMX-46047: The method "{0}" required by DualDataSourcePersistenceManager cannot be found.**

**Cause:** The required method was missing.

**Action:** Add the method to the MBean.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46200: federation error: "{0}"**

**Cause:** A federation operation resulted in an error from the federated target.

**Action:** See the remote exception cited within the error message for details on the error.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46201: The federation namespace "{0}" cannot be found.**

**Cause:** A Namespace that did not exist was specified during a federation operation.

**Action:** Use a valid federated namespace name.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46202: The domain of ObjectName "{0}" does not start with "{1}".**

**Cause:** An improper domain was used during federation ObjectName processing.

**Action:** Use the expected federation domain: oracle.as.jmx.federation

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46203: federation namespace handler registration error: "{0}".**

**Cause:** An error occurred while registering a new federation namespace handler.

**Action:** See the base exception information cited within the error message for details on the error.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46204: namespace handler unregistration error: "{0}".**

**Cause:** An error occurred while unregistering a federation namespace handler.

**Action:** See the base exception information cited within the error message for details on the error.

**Level:** 1

---

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46205: error closing connection for "{0}": "{1}".**

**Cause:** An error occurred while closing a federation JMX connector.

**Action:** See the base exception information cited within the error message for details on the error.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46206: The "{0}" parameter cannot be null.**

**Cause:** A required method parameter was null.

**Action:** Provide a non-null parameter to the method.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46207: Removing the federation namespace from "{0}" results in an invalid ObjectName.**

**Cause:** Removing the federation prefix resulted in an invalid ObjectName.

**Action:** Correct the specified ObjectName.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46208: A federated object is not serializable.**

**Cause:** A nonserializable object was encountered during federation serialization.

**Action:** Make the object serializable.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46209: A federated object is not serializable because a class cannot be found: "{0}".**

**Cause:** A class needed by federation serialization cannot be found.

**Action:** Verify that the class can be found using the class path.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46210: The object that is being federated is not serializable: "{0}".**

**Cause:** A nonserializable object was encountered during federation serialization.

**Action:** Make the object serializable.

**Level:** 1

---

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46211: The FederationMBeanServerImpl constructor is being called incorrectly.**

**Cause:** The constructor for FederationMBeanServerImpl was called more than once, which is not allowed.

**Action:** Call the constructor for FederationMBeanServerImpl only once.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46212: The operation "{0}" is not supported for namespace "{1}".**

**Cause:** The operation that was invoked is not supported by the namespace.

**Action:** Change the calling code so that the operation is not invoked.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46213: The remote namespace handler constructor is being called incorrectly.**

**Cause:** The connection information for the remote MBean server was not correct.

**Action:** Correct the connection information.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46214: Namespace "{0}" cannot be found.**

**Cause:** A namespace that did not exist was specified during a federation operation.

**Action:** Use a valid federated namespace name.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46215: ObjectName "{0}" is invalid.**

**Cause:** An ObjectName was created with an invalid constructor argument.

**Action:** Correct the ObjectName constructor argument.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46216: Error unregistering MBean whose ObjectName is "{0}" and implementation class is "{1}"**

**Cause:** See nested exception.

**Action:** Based on nested exception root cause.



---

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46218: An error occurred while persisting the state for the Config MBean registered under "{0}" and implemented by "{1}"**

**Cause:** See associated exception

**Action:** Fix issue described by the associated exception

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46219: No registered mapper can convert "{0}" to an Open MBean Type**

**Cause:** Needed mapper could not be found

**Action:** Add the required mapper

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46220: Cannot map nongeneric collections to Open MBean Type: "{0}"**

**Cause:** Cannot map nongeneric collections to Open MBean Type

**Action:** Fix collection type

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46221: JMXFrameworkStateFactory is not initialized.**

**JMXStateFactoryImpl.init() should have been called prior to calling this method**

**Cause:** JMXFrameworkStateFactory is not initialized.

**Action:** JMXStateFactoryImpl.init() should have been called prior to calling this method.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46222: No such property "{0}" in "{1}"**

**Cause:** Attempted to set a nonexistent property.

**Action:** Check the name of the property begin set.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46223: Failed to set property "{0}" to value "{1}".**

**Cause:** Could not set the given property.

**Action:** Check the exception.

---

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46224: No setter for property.**

**Cause:** Could not find the necessary setter method.

**Action:** Add the needed setter method.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46225: #params for setter != 1.**

**Cause:** Invalid number of parameter for setter method.

**Action:** Correct the parameter list of the setter call.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46226: Conversion to type "{0}" failed.**

**Cause:** Type conversion failed.

**Action:** Check the exception.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46227: Cannot find the Config MBeans declaration file {0} in the application.**

**Cause:** The required META-INF/mbeans.xml file is missing from the application.

**Action:** Add the META-INF/mbeans.xml in the application

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46228: Error processing MBeans associated with mbeans.xml located at: "{0}"**

**Cause:** Format issue, or missing class

**Action:** Check the exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46229: Only one of two security annotations**

**OperationRequiredGlobalSecurityRole and**

**OperationRequiredCustomSecurityGroup can be applied to MBean operation {0}.{1}**

---

**Cause:** Two security annotations on the MBean operation

**Action:** Apply only one or none security annotation the the MBean operation

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46230: The following security Annotation(s) cannot be applied to MBean operation {0}.{1}: {2}**

**Cause:** Invalid security annotation(s) on MBean operation

**Action:** Remove invalid security annotation(s)

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46231: Only one of two security annotations**

**AttributeGetterRequiredGlobalSecurityRole and  
AttributeGetterRequiredCustomSecurityGroup can be applied to MBean  
Attribute Getter {0}.{1}**

**Cause:** Two security annotations on the MBean attribute getter

**Action:** Apply only one or none security annotations to the MBean attribute  
getter.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46232: The following security Annotation(s) cannot be applied to MBean attribute getter {0}.{1}: {2}**

**Cause:** Invalid security annotation(s) on MBean attribute getter

**Action:** Remove invalid security annotation(s)

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46233: Only one of two security annotations**

**AttributeSetterRequiredGlobalSecurityRole and  
AttributeSetterRequiredCustomSecurityGroup can be applied to MBean  
Attribute Setter {0}.{1}**

**Cause:** Two security annotations on the MBean attribute setter

**Action:** Apply only one or none security annotations to the MBean attribute setter.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46234: The following security Annotation(s) cannot be applied to MBean attribute setter {0}.{1}: {2}**

**Cause:** Invalid security annotation(s) on MBean attribute setter

---

**Action:** Remove invalid security annotation(s)

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46235: Only one of two security annotations**

**MBeanRequiredGlobalSecurityRole and**

**MBeanRequiredCustomSecurityGroup can be applied to MBean interface {0}**

**Cause:** Two security annotations on the MBean interface

**Action:** Apply only one or none security annotations to the MBean interface.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46236: Do not know how to map nonserializable type: "{0}" to Open**

**MBean Type.**

**Cause:** A type that does not implement Serializable cannot be mapped by the jmx framework

**Action:** Implement Serializable

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46237: Error while executing ServletContextListener initialization**

**Cause:** See embedded root exception

**Action:** Fix issue related with embedded root exception

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46238: Cannot map nonserializable type "{0}" to Open MBean Type for mbean interface {1}, attribute {2}.**

**Cause:** A type that does not implement Serializable cannot be mapped by the jmx framework

**Action:** Implement Serializable

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46239: Cannot map nonserializable type "{0}" to Open MBean Type for mbean interface {1}, the return type of operation {2} .**

**Cause:** A type that does not implement Serializable cannot be mapped by the jmx framework

**Action:** Implement Serializable

**Level:** 1

---

Type: WARNING

Impact: Programmatic

**J2EE JMX-46240: Cannot map nonserializable type "{0}" to Open MBean Type for mbean interface {1}, parameter {2} of operation {3}.**

**Cause:** A type that does not implement Serializable cannot be mapped by the jmx framework

**Action:** Implement Serializable

Level: 1

Type: WARNING

Impact: Programmatic

**J2EE JMX-46241: Error while delivering JMX notification "{0}" to listener "{1}"**

**Cause:** See embedded root exception

**Action:** Fix issue related with embedded root exception

Level: 1

Type: ERROR

Impact: Programmatic

**J2EE JMX-46242: Cannot load class "{0}" for MBean operation "{1}" using ClassLoader "{2}"**

**Cause:** See embedded root exception

**Action:** Fix issue related with embedded root exception

Level: 1

Type: ERROR

Impact: Programmatic

**J2EE JMX-46243: Cannot find method "{0}" for attribute "{1}"**

**Cause:** See embedded root exception

**Action:** Fix issue related with embedded root exception

Level: 1

Type: ERROR

Impact: Programmatic

**J2EE JMX-46244: Error converting annotation "{0}" to descriptor. Could not get value for "{1}"**

**Cause:** See embedded root exception

**Action:** Fix issue related with embedded root exception

Level: 1

Type: WARNING

Impact: Programmatic

**J2EE JMX-46245: Error creating ConstraintValidator "{0}" with ClassLoader "{1}"**

**Cause:** See embedded root exception

**Action:** Fix issue related with embedded root exception

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46246: Error mapping java array or collection of type "{0}" to open type array. Individual element mapping resolved to "{1}"**

**Cause:** See embedded root exception

**Action:** Fix issue related with embedded root exception

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46247: Cannot load class "{0}" using ClassLoader "{1}"**

**Cause:** See embedded root exception

**Action:** Fix issue related with embedded root exception

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46248: Error mapping java Map of type "{0}" to open type TabularData. Key mapping resolved to "{1}", and Value mapping resolved to "{2}"**

**Cause:** See embedded root exception

**Action:** Fix issue related with embedded root exception

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46249: Error mapping java Map entry of TabularType "{0}". Mapped Key instance is "{1}", and mapped Value instance is "{2}"**

**Cause:** See embedded root exception

**Action:** Fix issue related with embedded root exception

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46250: Internal error: the setPersistable() invoked twice on config mbean**

**Cause:** internal error

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**J2EE JMX-46251: The MBean is no longer registered so no notification is delivered.**

**Cause:** The mbean has been unregistered.

**Action:** The notification is no longer delivered.

---

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Programmatic

**J2EE JMX-46252: Error during {0} for MBean {1}**

**Cause:** See nested exception for root cause.

**Action:** Fix root cause, to ensure that the MBean gets registered.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46300: Class "{0}" is not compatible with the annotation on method "{1}" of class "{2}".**

**Cause:** When a MinValue, MaxValue or LegalValues annotation was used, the class that the annotation applied to did not have either a public static valueOf(String) method or a public constructor with only a String parameter.

**Action:** Change the class that the MinValue, MaxValue or LegalValues annotation applies to so that it either has a public static valueOf(String) method or a public constructor with only a String parameter.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46301: An object cannot be obtained for the minimum value for "{0}" for method "{1}" of class "{2}".**

**Cause:** An instance of the class that a MinValue annotation applied to was not constructed. The associated IllegalArgumentException indicates the reason.

**Action:** Examine the associated IllegalArgumentException information to determine what action to take.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46302: An object cannot be obtained for the maximum value for "{0}" for method "{1}" of class "{2}".**

**Cause:** An instance of the class that a MaxValue annotation applied to was not constructed. The associated IllegalArgumentException indicates the reason.

**Action:** Examine the associated IllegalArgumentException information to determine what action to take.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46303: An object cannot be obtained for the valid value "{0}" for method "{1}" of class "{2}".**

**Cause:** An instance of the class that a LegalValues annotation applied to was not be constructed. The associated IllegalArgumentException indicates the reason.

---

**Action:** Examine the associated `IllegalArgumentException` information to determine what action to take.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46304: The parameters being validated for method "{0}" of class "{1}" based on annotations do not match the method parameter types.**

**Cause:** A constraint declared using the `MinValue`, `MaxValue` or `LegalValues` annotation was being enforced, but the number of arguments passed to the method was wrong.

**Action:** Change the code that has the call to the method to have the correct number of arguments.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46305: Parameter "{0}" of method "{1}" of class "{2}" is less than the `MinValue`.**

**Cause:** The value for an attribute or parameter that was annotated with the `MinValue` annotation failed the minimum value constraint test.

**Action:** Change the value so that it does not fail the minimum value constraint test or change the annotation.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46306: Parameter "{0}" of method "{1}" of class "{2}" is greater than the `MaxValue`.**

**Cause:** The value for an attribute or parameter that was annotated with the `MaxValue` annotation failed the maximum value constraint test.

**Action:** Change the value so that it does not fail the maximum value constraint test or change the annotation.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46307: Parameter "{0}" of method "{1}" of class "{2}" cannot be compared to the `MinValue` annotation value.**

**Cause:** The class to which the `MinValue` annotation applied did not implement the `Comparable` interface.

**Action:** Use a different class that implements the `Comparable` interface or modify the existing class so that it implements the `Comparable` interface.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic



---

**J2EE JMX-46308: Parameter "{0}" of method "{1}" of class "{2}" cannot be compared to the MaxValue annotation value.**

**Cause:** The class to which the MaxValue annotation applied did not implement the Comparable interface.

**Action:** Use a different class that implements the Comparable interface or modify the existing class so that it implements the Comparable interface.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46309: Parameter "{0}" of method "{1}" of class "{2}" does not match any value in the LegalValues annotation.**

**Cause:** The value for an attribute or parameter that was annotated with the LegalValues annotation did not match any valid value.

**Action:** Change the value so that it is one of the valid values, or change the annotation.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46310: Parameter "{0}" of method "{1}" of class "{2}" violates the constraint that the LegalValues annotation cannot be used with a MinValue or MaxValue annotation.**

**Cause:** The LegalValues annotation was used at the same location with either a MaxValue or MinValue annotation.

**Action:** Either use the LegalValues annotation, or use the MaxValue or MinValue annotation.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46311: The value of the MinValue annotation is greater than the value of the MaxValue annotation for parameter "{0}" of method "{1}" of class "{2}".**

**Cause:** The value used for the MinValue annotation was greater than the value used for the MaxValue annotation.

**Action:** Change the annotations so that the value used for MinValue annotation is less than the value used for the MaxValue annotation.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46312: The type used for parameter "{0}" of method "{1}" of class "{2}" is improper.**

**Cause:** The value passed to an attribute or method parameter that was annotated with the MinValue or MaxValue annotation was not compared with an instance of the class used for the annotation because the type of the value was incorrect.

---

**Action:** Use the correct value for the attribute or method call, or change the annotation type.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46313: The delegate MBeanServerConnection cannot be null.**

**Cause:** A PatternBaseDelegationHandler was being constructed without the required MBeanServerConnection argument.

**Action:** Change the code to supply the required MBeanServerConnection argument.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46314: No handler for ObjectName "{0}" is registered.**

**Cause:** No handler existed for the object name being used.

**Action:** Register a handler that is appropriate for the object name that is used, or use a different object name.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46315: There is no registered handler to instantiate class "{0}".**

**Cause:** No handler was found to instantiate the class for the object name being used.

**Action:** Register a handler that is appropriate for the object name that is used, or use a different object name.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46318: An error occurs when registering an MBean with the ObjectName "{0}" and the implementation class "{1}".**

**Cause:** An error occurred when the MBean was being registered.

**Action:** See the associated Throwable exception information cited within the error message for details on the error.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46319: An error occurs when unregistering an MBean with the ObjectName "{0}" and implementation class "{1}".**

**Cause:** An error occurred when the MBean was being unregistered.

**Action:** See the associated Throwable exception information cited within the error message for details on the error.

---

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46320: An error occurs when parsing an mbeans.xml file.**

**Cause:** The mbeans.xml file had incorrect XML syntax.

**Action:** Correct the XML syntax in the mbeans.xml file.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46324: The MBeanServer object parameter for the MBeanServerForwarder is null, or it is equal to the MBeanServerForwarder, or an MBeanServer object is already set.**

**Cause:** The MBeanServer argument was not valid.

**Action:** Correct the MBeanServer argument.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46329: Error when parsing {0}.**

**Cause:** The META-INF/mbeans.xml is empty or has syntax error.

**Action:** Correct the META-INF/mbeans.xml with the correct syntax.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46330: Cannot find any jmx config mbeans in parsed mbeans.xml file**

**Cause:** No config mbeans declared in META-INF/mbeans.xml in the application.

**Action:** Declare the config mbeans class, interface, config files in META-INF/mbeans.xml.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46331: The numbers of configuration files and persistence managers for the mbean {0} in mbeans.xml do not match**

**Cause:** The injectNames for configuration files and persistence managers in mbeans.xml is inconsistent.

**Action:** Update the mbeans.xml to use correct configuration files and persistence managers.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46333: Cannot find config file {0} in the application for mbean {1}**

---

**Cause:** The location of config file is not correct or the config file is missing in the application.

**Action:** Fix the application.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46334: This helper class "{0}" only supports a single config file per MBean. However the MBean "{1}" specified "{2}" config files.**

**Cause:** Only one config file per MBean is supported from this helper class

**Action:** Fix the calling code

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46335: MBean attribute access denied. MBean: {0} {1} for attribute {2}**

**Detail:** {3}

**Cause:** Security check failed.

**Action:** Access the MBean attribute with the user in right role or group.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46336: MBean operation access denied. MBean: {0} Operation: {1} Detail: {2}**

**Cause:** Security check failed.

**Action:** Access the MBean operation with the user in right role or group.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46337: RegisterMBean denied: MBean: {0} Detail: {1}**

**Cause:** Security check failed.

**Action:** RegisterMBean is allowed to the user ADMIN role.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46338: DeregisterMBean denied: MBean: {0} Detail: {1}**

**Cause:** Security check failed.

**Action:** DeregisterMBean is allowed to the user ADMIN role.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**J2EE JMX-46339: Cannot find any jmx runtime mbeans in parsed mbeans.xml file**

**Cause:** No runtime mbeans declared in META-INF/mbeans.xml in the application.

**Action:** Declare the config mbeans class, interface, config files in META-INF/mbeans.xml.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46340: EntityResolver "{0}" failed to retrieve mbeans.xml xsd "{1}"**

**Cause:** Either XSD is invalid, or proper Java Security Permissions have not been granted to JMX Framework jars if Security Manager is turned on.

**Action:** Verify xsd in mbeans.xml file, and ensure proper Security Permissions are granted to JMX Framework jars if Security Manager is turned on.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46341: Failed to create application stripe Id. Missing key: {0}, MBean: {1}**

**Cause:** The key is missing from MBean ObjectName.

**Action:** Check MBean interface security annotation, make sure the key is available.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46342: Failed to remove old backup of config file {0}**

**Cause:** unknown.

**Action:** regular backup config directory may help in this case.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46343: Failed to rename old config file {0} to backup file {1}**

**Cause:** unknown.

**Action:** regular backup config directory may help in this case.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46344: Access denied. Current subject: {0}; Required app roles: {1}**

**Cause:** Current user is not member of any required application roles.

**Action:** Try again with the user that is member of any of required application roles.

**Level:** 1

---

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46345: Internal error: invalid security object. type {0}, value {1}**

**Cause:** unknown.

**Action:** Contact support.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46346: EntityResolver "{0}" failed to retrieve the JMX Framework configuration xsd "{1}"**

**Cause:** Either XSD is invalid, or proper Java Security Permissions have not been granted to JMX Framework jars if Security Manager is turned on.

**Action:** Verify xsd in JMX Framework configuration file, and ensure proper Security Permissions are granted to JMX Framework jars if Security Manager is turned on.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46347: An error occurs when parsing the JMX Framework configuration file.**

**Cause:** The JMX Framework configuration file had incorrect XML syntax.

**Action:** Correct the JMX Framework configuration file XML syntax.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46348: Unexpected xml tag {0}, when parsing the JMX framework configuration file.**

**Cause:** Invalid JMX Framework configuration file.

**Action:** Make sure your JMX Framework Configuration file is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46349: Missing JMX Framework configuration file**

**Cause:** Cannot find the JMX Framework configuration file.

**Action:** Ensure that you either specify a valid configuration location, or that the default configuration is included in jmxspi.jar under the META-INF directory

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**J2EE JMX-46350: Error parsing JMX Framework Configuration. Invalid value "{0}" for attribute "{1}" defined in XML element "{2}".**

**Cause:** The value for the attribute is not valid

**Action:** Please correct the value in the JMX Framework configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46351: Invalid ID "{0}". No internal MBean interceptor is associated with that ID.**

**Cause:** The wrong value was specified.

**Action:** Please correct the value in the JMX Framework configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46352: Invalid URL for custom MBean interceptor "{0}" jar location "{1}"**

**Cause:** The wrong value was specified in the JMX Framework configuration file for the MBean interceptor jar location.

**Action:** Please correct the value in the JMX Framework configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46353: Custom MBean interceptor "{0}" jar file cannot be found at the specified location "{1}"**

**Cause:** Missing jar file, or incorrect location specified in the JMX Framework configuration file.

**Action:** Please correct the value in the JMX Framework configuration file, or make sure the jar file is present

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46354: An error was raised while instantiating the JMX Framework MBean interceptor chain.**

**Cause:** See root exception.

**Action:** Please correct the issue associated with the root exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46355: An error occurred while initializing the JMX Framework MBean level logging interceptor.**

**Cause:** See root exception.

**Action:** Please correct the issue associated with the root exception.

---

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Programmatic

**J2EE JMX-46383: Error while merging configuration for files "{0}" and "{1}" with ConfigMerger instance {2}.**

**Cause:** See nested exception for root cause.

**Action:** Fix root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46400: The Config MBean jar file "{0}" does not exist.**

**Cause:** The configuration MBeans jar file specified in the "location" attribute of the "config-mbeans" tag did not exist

**Action:** Correct the path to the configuration MBeans jar file.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46401: Attribute "{0}" is unexpected.**

**Cause:** An unexpected attribute was encountered in the MBeans XML file.

**Action:** Remove the unexpected attribute.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46402: Tag "{0}" is unexpected.**

**Cause:** An unexpected tag was encountered in the MBeans XML file.

**Action:** Remove the unexpected tag.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46403: Tag "{0}" is missing the required attribute "{1}"**

**Cause:** A required attribute was missing from the MBeans XML file.

**Action:** Add the missing attribute.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46404: Tag "{0}" is missing the required tag "{1}"**

**Cause:** A required tag is missing from the MBeans XML file.

**Action:** Add the missing tag.



---

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46406: Class "{0}" does not exist.**

**Cause:** A jmx-config-mbean class or management-interface specified in the MBeans XML file did not exist.

**Action:** Correct the class reference.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46407: Multiple persistence managers are not allowed for single configuration file.**

**Cause:** Multiple persistence managers were specified for a single configuration file.

**Action:** Specify only one persistence manager.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46408: An invalid location is defined in mbeans.xml for the config file: "{0}"**

**Cause:** An invalid jmx-config-mbean config-file path was encountered in the MBeans XML file.

**Action:** Correct the path to the configuration file.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46409: The Runtime MBean jar file "{0}" does not exist.**

**Cause:** The Runtime MBeans jar file specified in the "location" attribute of the "runtime-mbeans" tag did not exist

**Action:** Correct the path to the Runtime MBeans jar file.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46410: When specifying multiple "{0}" elements, the injection-name attribute is required**

**Cause:** Your MBean must include a name as part of the @Injection annotations to match resources defined in mbeans.xml

**Action:** Correct the @Inject annotations in your MBean to reference resources defined in your mbeans.xml

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**J2EE JMX-46502: internal session error: "{0}".**

**Cause:** A session operation resulted in an error.

**Action:** See the base exception information cited within the error message for details on the error.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**J2EE JMX-46503: The "{0}" call to the MBean with ObjectName "{1}" is not made in the context of a JMX configuration session.**

**Cause:** The call that was made needed to be made in the context of a JMX configuration session.

**Action:** Create a JMX configuration session and then make the call.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46504: A call to commit or roll back the session is not made by the owner of the JMX configuration session.**

**Cause:** The call was not made by the owner of the JMX configuration session.

**Action:** This call must be made by the owner of the JMX configuration session.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46505: The Config MBean implementation object "{0}" for ObjectName "{1}" does not implement MBeanServerSupport.**

**Cause:** The Config MBean implementation did not implement MBeanServerSupport.

**Action:** Correct the Config MBean implementation so that it implements MBeanServerSupport.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46506: The parent MBean for "{0}" cannot be found.**

**Cause:** The MBean specified a parent MBean that was missing.

**Action:** Correct the MBean implementation so that it specifies the correct parent.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46507: The ObjectName "{0}" is specified when adding or removing a notification listener in a JMX configuration session.**

---

**Cause:** Specifying ObjectName when adding or removing a notification listener is not supported in a JMX configuration session.

**Action:** Add or remove the notification listener without specifying ObjectName.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46508: The createMBean method is called for the ObjectName "{0}".**

**Cause:** An attempt was made to create a ConfigMBean using the createMBean method.

**Action:** Use the registerMBean method.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46509: MBean custom persistence method error for ObjectName "{0}": "{1}"**

**Cause:** An MBean custom persistence operation resulted in an error.

**Action:** See the base exception information cited within the error message for details on the error.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46510: JAXB persistence method error: "{0}"**

**Cause:** An MBean JAXB Persistence operation resulted in an error.

**Action:** See the base exception information cited within the error message for details on the error.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46511: MBean validation error prior to committing for ObjectName "{0}": "{1}"**

**Cause:** An error occurred during validation of an MBean before committing it.

**Action:** See the base exception information cited within the error message for details on the error.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46512: MBean session life-cycle callback error for ObjectName "{0}": "{1}"**

**Cause:** This error occurred when the MBean session life-cycle callback was called.

**Action:** See the base exception information cited within the error message for details on the error.

**Level:** 1

---

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46513: unexpected error: "{0}"**

**Cause:** An unexpected error occurred.

**Action:** See the base exception information cited within the error message for details on the error.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**J2EE JMX-46514: An MBean of type "{0}" implements Persistable directly or implements an unknown subclass of Persistable.**

**Cause:** The MBean must not implement Persistable directly and must not implement an unknown subclass of Persistable.

**Action:** Remove the use of Persistable.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46515: A configuration session already exists.**

**Cause:** A configuration session was started when one was already active.

**Action:** Do not attempt to start a second configuration session. Use the previously started configuration session.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46516: configuration session start error: "{0}".**

**Cause:** There was a failure to start the JMX configuration session due to an error.

**Action:** See the base exception information cited within the error message for details on the error.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46517: configuration session commit error: "{0}".**

**Cause:** There was a failure to commit the JMX configuration session due to an error.

**Action:** See the base exception information cited within the error message for details on the error.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46518: configuration session roll back error: "{0}".**

---

**Cause:** There was a failure to roll back the JMX configuration session due to an error.

**Action:** See the base exception information cited within the error message for details on the error.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46519: cannot lock MBean: "{0}"**

**Cause:** The MBean was in special domain oracle.as.jmx or was a delegate MBean.

**Action:** Provide an MBean whose object name is not in the special domain oracle.as.jmx and is not a delegate MBean.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46520: MBean "{0}" cannot be found in the session MBean server.**

**Cause:** The MBean was not registered in the session MBean server.

**Action:** Register the MBean.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46600: The groupby attribute "{0}" is invalid.**

**Cause:** The groupby attribute or property specified did not exist.

**Action:** Ensure that the groupby attribute specified refers to an MBean attribute or property.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46601: An aggregation attribute or property such as groupbyAttrs, aggOps, or aggAttrs is null.**

**Cause:** An aggregation attribute or property was null.

**Action:** Ensure that the specified aggregation attribute or property exists.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46602: The aggregation operation "{0}" is invalid.**

**Cause:** An invalid aggregation operator was specified.

**Action:** Verify that the aggregation operator specified is among OPERATION\_AVG through OPERATION\_GROUPBY defined in oracle.as.jmx.framework.bulkoperations.BulkOperationsMBean.

**Level:** 1

---

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46603: The groupby key "{0}" cannot be used for aggregation.**

**Cause:** Aggregation was incorrectly specified on a groupby attribute or property.

**Action:** Specify either aggregation key or groupby key, but not both, on the attribute or property.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-46604: BulkOperationsMBean NamespaceHelper instance creation error: "{0}"**

**Cause:** The provided MBean server is invalid.

**Action:** Correct the MBean server that is being provided. See the base exception information cited within the error message for details on the error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46605: Parameter count ("'{0}'") does not match mbean count ("'{1}'")**

**Cause:** The number of parameter arrays passed in does not match the number of mbeans that should be invoked

**Action:** Ensure that the correct number of parameter arrays are being passed.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46606: non-numeric attribute {0} in aggregation**

**Cause:** BulkOperationMBean Aggregation operation requires all attributes to have numeric values

**Action:** Do not use attributes with non-numeric values when using the aggregation operation provided by the BulkOperationMBean

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-46607: In BulkOperationMBean Aggregation operation, aggOps and aggAttrs need to be the same length**

**Cause:** In BulkOperationMBean Aggregation operation, aggOps and aggAttrs need to be the same length

**Action:** Ensure that aggOps and aggAttrs are the same length

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**J2EE JMX-46608: A "null" value was passed to a BulkOperationsMBean method as part of an ObjectName[] parameter. We will ignore that value, as it would cause all MBeans to be selected. If this is the intended behavior use new ObjectName("\*:\*") in place of null**

**Cause:** This could be due to some user code logic error, and not intended.

**Action:** If this is the intended behavior use new ObjectName("\*:\*") in place of null

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JMX-47000: Property "{0}" is not set.**

**Cause:** The expected property was not set.

**Action:** Add the expected property to the mbeans.xml file.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-47001: A JAXB error occurred during unmarshalling.**

**Cause:** Some data in the xml file is invalid.

**Action:** Use the JAXB error information to correct the xml file.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-47002: A JAXB error occurred during marshalling of "{0}".**

**Cause:** Some data to be marshalled is invalid.

**Action:** Correct the data to be marshalled.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-47003: An error occurred during initialization of the JAXB context using the contextpath "{0}"**

**Cause:** The contextpath in the mbeans.xml file is invalid.

**Action:** Correct the contextpath.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JMX-47006: Persistence manager "{0}" does not implement "{1}".**

**Cause:** Persistence manager implementation inheritance incorrect.

**Action:** Correct the persistence manager implementation.

**Level:** 1

**Type:** WARNING

---

**Impact:** Programmatic



---

## J2EE JOC-00001 to J2EE JOC-00859

**J2EE JOC-00001: exception caught in the load callback**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00002: exception caught in the verify callback**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00003: internal error in the cache**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00004: error in the disk cache**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00005: error locking the disk cache**

**Cause:** null

**Action:** null

**Level:** 1

---

Type: WARNING

Impact: Data

**J2EE JOC-00006: The metadata file for the disk cache is corrupted.**

Cause: null

Action: null

Level: 1

Type: WARNING

Impact: Data

**J2EE JOC-00007: incorrect object ID**

Cause: null

Action: null

Level: 1

Type: WARNING

Impact: Data

**J2EE JOC-00008: invalid handle**

Cause: null

Action: null

Level: 1

Type: WARNING

Impact: Data

**J2EE JOC-00009: invalid object**

Cause: null

Action: null

Level: 1

Type: WARNING

Impact: Data

**J2EE JOC-00010: negative number**

Cause: null

Action: null

Level: 1

Type: WARNING

Impact: Data

**J2EE JOC-00011: negative reference count**

Cause: null

Action: null

Level: 1

Type: WARNING

Impact: Data

---

**J2EE JOC-00012: A group cannot belong to itself.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00013: cannot find loader object**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00014: An exception occurred while waiting for a condition.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00015: The specified event is not supported.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00016: The SSL configuration is invalid, either keystore or storepass cannot be found.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Security

**J2EE JOC-00017: The cache is full.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00018: The region is full.**

---

**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** WARNING  
**Impact:** Data

**J2EE JOC-00019: The cache is not available.**

**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** WARNING  
**Impact:** Data

**J2EE JOC-00020: The named cache is not available.**

**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** WARNING  
**Impact:** Data

**J2EE JOC-00021: The disk cache is not available.**

**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** WARNING  
**Impact:** Data

**J2EE JOC-00022: The caller must have ownership of the object before executing this method.**

**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** WARNING  
**Impact:** Data

**J2EE JOC-00023: An inconsistency in the use of a group is detected.**

**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** WARNING  
**Impact:** Data

**J2EE JOC-00024: One of the specified arguments is not valid.**

**Cause:** null

---

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00025: The specified group is not valid.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00026: The handle being used is not valid.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00027: The object accessed is not valid.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00028: A loading conflict is occurring, such as trying to update an object while it is being loaded.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00029: The cache message system is offline.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00030: The object is not a pool.**

**Cause:** null

**Action:** null

---

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00031: There are currently no objects available from the pool.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00032: The object cannot be retrieved.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00033: This functionality is not implemented.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00034: The current object is null.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00035: The object name or group name is null.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00036: An object already exists with the same name.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

---

**Impact:** Data

**J2EE JOC-00037: cannot find the following object**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00038: the object or group is not synchronized:**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00039: cannot find region**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00040: cannot find group**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00041: A failure is occurring during the requested operation at a remote cache.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00042: The object or file cannot be created.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

---

**J2EE JOC-00043: base exception:**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00044: An exception is occurring in the method.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00045: The following object is already defined:**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00046: A DiskObject cannot be updated.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00047: This object is synchronized, getOwnership must be called before executing this method on:**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00048: This synchronized object has been destroyed. This operation is no longer valid for:**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data



---

**J2EE JOC-00049: This object already exists in the cache as a distributed disk object.  
It cannot be redefined as a local object:**  
Cause: null  
Action: null  
  
Level: 1  
Type: WARNING  
Impact: Data

**J2EE JOC-00050: The following remote cache cannot be found:**  
Cause: null  
Action: null  
  
Level: 1  
Type: WARNING  
Impact: Network

**J2EE JOC-00051: unable to destroy named cache**  
Cause: null  
Action: null  
  
Level: 1  
Type: WARNING  
Impact: Data

**J2EE JOC-00052: A named cache name cannot contain a region separator.**  
Cause: null  
Action: null  
  
Level: 1  
Type: WARNING  
Impact: Data

**J2EE JOC-00053: cannot add index**  
Cause: null  
Action: null  
  
Level: 1  
Type: WARNING  
Impact: Data

**J2EE JOC-00054: cannot remove index**  
Cause: null  
Action: null  
  
Level: 1  
Type: WARNING  
Impact: Data

**J2EE JOC-00055: The index MessageKeys.EXpression is null.**

---

**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** WARNING  
**Impact:** Data

**J2EE JOC-00056: The index name is null.**

**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** WARNING  
**Impact:** Data

**J2EE JOC-00057: error evaluating index MessageKeys.EXpression**

**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** WARNING  
**Impact:** Data

**J2EE JOC-00058: distributed cache initialization failure**

**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** WARNING  
**Impact:** Data

**J2EE JOC-00600: group communication internal error**

**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** WARNING  
**Impact:** Network

**J2EE JOC-00601: invalid destination address**

**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** WARNING  
**Impact:** Network

**J2EE JOC-00602: group communication exception, base exception:**

**Cause:** null  
**Action:** null

---

**Level: 1**  
**Type: WARNING**  
**Impact: Network**  
**J2EE JOC-00603: invalid channel state**  
**Cause: null**  
**Action: null**

**Level: 1**  
**Type: WARNING**  
**Impact: Network**  
**J2EE JOC-00604: The view information is empty.**  
**Cause: null**  
**Action: null**

**Level: 1**  
**Type: WARNING**  
**Impact: Network**  
**J2EE JOC-00605: The view is null.**  
**Cause: null**  
**Action: null**

**Level: 1**  
**Type: WARNING**  
**Impact: Network**  
**J2EE JOC-00606: The local host address cannot be found.**  
**Cause: null**  
**Action: null**

**Level: 1**  
**Type: WARNING**  
**Impact: Network**  
**J2EE JOC-00607: The configured network port is in use.**  
**Cause: null**  
**Action: null**

**Level: 1**  
**Type: WARNING**  
**Impact: Ports**  
**J2EE JOC-00608: The socket cannot be initialized.**  
**Cause: null**  
**Action: null**

**Level: 1**  
**Type: WARNING**

---

**Impact:** Network

**J2EE JOC-00609: invalid parameter**  
**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** WARNING  
**Impact:** Data

**J2EE JOC-00610: null pointer**  
**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** WARNING  
**Impact:** Data

**J2EE JOC-00611: empty reply information**  
**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** WARNING  
**Impact:** Requests/Responses

**J2EE JOC-00612: no network connection to**  
**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** WARNING  
**Impact:** Network

**J2EE JOC-00613: invalid view information**  
**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** WARNING  
**Impact:** Network

**J2EE JOC-00614: Group communication layer is terminated or not initialized properly.**  
**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** WARNING  
**Impact:** Network

---

**J2EE JOC-00615: Transferring files is not supported in object stream mode, switch to HTTP transfer mode and try again.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00616: The InputStream is not valid.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00617: The HTTP request is not valid.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**J2EE JOC-00618: The socket input stream is closed.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00619: unable to instantiate SSL provider:**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Security

**J2EE JOC-00620: cannot find SSL provider:**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Security

**J2EE JOC-00621: is not an instance of java.security.Provider.**

---

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Security

**J2EE JOC-00622: invalid SSL Configuration information**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Security

**J2EE JOC-00623: SSLServerSocket creation failure**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Security

**J2EE JOC-00624: SSLSocket creation failure**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Security

**J2EE JOC-00700: The file name cannot be null.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Files

**J2EE JOC-00701: The file does not exist.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Files

**J2EE JOC-00702: invalid parameters passed in**

**Cause:** null

**Action:** null

---

**Level:** 1  
**Type:** WARNING  
**Impact:** Files  
**J2EE JOC-00703: This operation is not allowed.**  
**Cause:** null  
**Action:** null

**Level:** 1  
**Type:** WARNING  
**Impact:** Files  
**J2EE JOC-00704: internal error**  
**Cause:** null  
**Action:** null

**Level:** 1  
**Type:** WARNING  
**Impact:** Files  
**J2EE JOC-00800: The maximum group communication initialization retry limit is being exceeded: {0}**  
**Cause:** null  
**Action:** null

**Level:** 1  
**Type:** WARNING  
**Impact:** Network  
**J2EE JOC-00801: group communication client initialization error**  
**Cause:** null  
**Action:** null

**Level:** 1  
**Type:** WARNING  
**Impact:** Network  
**J2EE JOC-00802: unable to generate a global unique ID for a group communication member**  
**Cause:** null  
**Action:** null

**Level:** 1  
**Type:** WARNING  
**Impact:** Network  
**J2EE JOC-00803: unexpected EOF during read**  
**Cause:** null  
**Action:** null

---

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00804: timeout while registering a new client: {0} seconds**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00805: no connection for member: {0}**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00806: unable to parse network address**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00807: unable to create a new view**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00808: unable to serialize object: {0}**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00809: failure during packet processing**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING



---

**Impact:** Requests/Responses

**J2EE JOC-00810: distributor initialization timeout: {0}**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00811: unexpected interrupt while waiting for a read/write lock**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00812: timeout after waiting for a packet delivery confirmation for {0} seconds**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00813: invalid SSL provider, name: {0}**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Security

**J2EE JOC-00814: unable to create SSL provider, name: {0}**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Security

**J2EE JOC-00815: unknown SSL provider, name: {0}**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Security

---

**J2EE JOC-00816: unable to create SSL server socket on port: {0}**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Security

**J2EE JOC-00817: unable to initialize SSL Manager**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Security

**J2EE JOC-00818: invalid SSL configuration file**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Security

**J2EE JOC-00819: The SSL configuration file is malformed. {0}**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Security

**J2EE JOC-00820: Group communication has been terminated or is not available.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00821: The delivery cannot be confirmed due to a distributor failover scenario.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00822: The specified instance name: {0} is in use.**

---

**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** WARNING  
**Impact:** Network

**J2EE JOC-00823: unable to contact the packet-distributor at {0}**  
**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** WARNING  
**Impact:** Network

**J2EE JOC-00824: unable to join group at {0} due to unexpected I/O problems**  
**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** WARNING  
**Impact:** Network

**J2EE JOC-00825: no response from the packet-distributor at {0}**  
**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** WARNING  
**Impact:** Network

**J2EE JOC-00826: invalid group communication member, ID: {0}**  
**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** WARNING  
**Impact:** Network

**J2EE JOC-00827: receiving an invalid group view, unable to join group**  
**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** WARNING  
**Impact:** Network

**J2EE JOC-00828: unable to serialize an outgoing message**  
**Cause:** null  
**Action:** null

---

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00829: unable to send a packet to the packet-distributor at {0} after {1} retries**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00830: The delivery cannot be confirmed due to an unexpected I/O error.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00831: unable to process an incoming packet: {0}**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**J2EE JOC-00832: Group communication service is terminated unexpectedly while waiting for a packet delivery confirmation**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00833: unexpected interruption while waiting for a packet delivery confirmation**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00834: unable to restore a sequence token for handling total-order delivery**

**Cause:** null

---

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00835: no listener for the packet-distributor is defined in the group communication configuration**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00836: unable to contact the group coordinator at {0} due to unexpected error**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00837: unable to run as a dedicated group coordinator**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00838: unable to initialize an EndPointConnection due to unexpected I/O error**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00839: The specified group member alias or ID: {0} does not exist in view {1}.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

---

**J2EE JOC-00840: unable to automatically assign a listener address for the packet-distributor**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00841: An HTTP handler cannot be created. The I/O stream is invalid.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**J2EE JOC-00842: The size of an incoming HTTP packet has exceeded the default maximum limit of {0}.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**J2EE JOC-00843: The HTTP header is shorter than the specified length: {0}.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**J2EE JOC-00844: The header length is missing from an incoming HTTP packet.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**J2EE JOC-00845: The file length from an incoming HTTP packet is shorter than expected.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

---

**J2EE JOC-00846: The file length from an incoming HTTP packet is {0} bytes shorter than expected.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**J2EE JOC-00847: invalid HTTP header**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**J2EE JOC-00848: The packet-distributor is unable to open a server socket at {0}.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00849: unable to initialize an UDP multicast channel at {0}**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00850: invalid group communication packet type: {0}**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**J2EE JOC-00851: unable to deserialize a group communication packet**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Data

**J2EE JOC-00852: unable to create a receipt holder for tracking confirmation**

---

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00853: unable to parse a sequence token for handling total-order delivery**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00854: unexpected group view management error**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00855: missing mandatory packet-distributor address for client-mode configuration**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00856: Neither the listener address nor the packet-distributor location is defined with the label {0}.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00857: No packet-distributor listener address is defined with the label {0}.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00858: The connection is being closed.**



---

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Network

**J2EE JOC-00859: The port {0} is unavailable, the packet-distributor cannot be started.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Ports



---

## J2EE JSP-00002 to J2EE JSP-00302

**J2EE JSP-00002: an internal JSP error occurred. Additional information follows: {0}.**

**Cause:** JSP encountered an unexpected situation. This may be a bug in the JSP servlet.

**Action:** Contact Oracle Support Services. Oracle Support Services may recommend increasing the log level to FINER to help understand the situation.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**J2EE JSP-00003: unable to fully process the TLD cache for the following reason: {0}.**

**Cause:** An error occurred while the Tag Library Descriptor cache was created or accessed.

**Action:** Check the TLD for validity and fix the TLD, or remove it if it is not used in the application. If the logging level is set to FINER more information should be available in the exception contained in the error message.

**Level:** 1

**Type:** WARNING

**Impact:** Deployment

**J2EE JSP-00005: unable to send the following error in the response. Response code: {0} Error message: {1}.**

**Cause:** An exception occurred that prevented the error status from being sent in the response.

**Action:** See the exception cited in the error message. It may be necessary to increase the logging level to FINER to see the exception.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**J2EE JSP-00009: unable to return the following error in the response: {0}.**

**Cause:** An input-output error occurred while trying to write an error message to the servlet response stream.

**Action:** The logged message contains the error message that could not be returned in the response, and the associated exception. It may be necessary to increase the logging level to FINER to see the exception. Scan the log files for additional error messages that may reveal the root cause of this problem.

---

**Level:** 1

**Type:** WARNING

**Impact:** Files

**J2EE JSP-00011: Invalid JSP tag library location. {0} does not exist or is not a directory.**

**Cause:** An invalid or nonexistent directory name was supplied as a tag library location.

**Action:** Correct the directory name and insure that it is available.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JSP-00026: missing required uri element in external TLD: {0}**

**Cause:** Encountered a Tag Library Descriptor with an invalid or missing uri-element where one is required. For example, global tag libraries and those extrenal to the application must have URI elements.

**Action:** Supply the URI element in the TLD file or move the tag library to the application level.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JSP-00027: unable to parse TLD file: {0}**

**Cause:** The TLD at the given location could not be parsed.

**Action:** Check for invalid XML syntax, especially unbalanced angle brackets or start and end tags.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JSP-00028: duplicate URI element, {0}, in TLD, {1}, and TLD, {2}**

**Cause:** More than one tag library descriptor encountered using the same URI element. URI elements visible to the application must be unique.

**Action:** Change one of the uri element values or exclude one of the tag libraries from the this application.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JSP-00029: unable to obtain cache key: {0}**

**Cause:** A corrupted cache key was encountered in the TLD cache.

**Action:** Stop the server, delete the TLD cache files from the application's persistence directory and from the global directory, tldcache and restart the application server. Contact Oracle Support Services if this problem persists.

**Level:** 1

---

**Type:** WARNING

**Impact:** Deployment

**J2EE JSP-00030: unable to obtain the JSP parameters**

**Cause:** A unknown problem was encountered when attempting to initialize JSP configuration parameters.

**Action:** Verify the XML syntax in orion-web.xml, especially in the attributes of ojsp-init element if used. Verify the syntax of any init-parameters supplied to the JspServlet in web.xml or global-web-applications.xml. Then redeploy the application. If that fails, or if errors were found in the global-web-application.xml, restart the server. If the problem persists contact Oracle Support Services

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**J2EE JSP-00033: unable to process an invalid or unsupported TLD version: {0}**

**Cause:** An invalid or unsupported value of the taglib element's attribute, version, element was supplied.

**Action:** The taglib element is the root element for all TLD's. The element's attribute, version, must be either 2.0 or 2.1.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JSP-00036: unable to obtain Tag Library listeners: {0}**

**Cause:** An error was encountered while obtaining Tag Library listeners during the parsing of Tag Library Descriptors.

**Action:** Verify that classes given in the listener-classes element are available in the application's class path. Check for general XML syntax (i.e., unmatched quotes or start/end tags) in the application's TLD's.

**Level:** 1

**Type:** WARNING

**Impact:** Deployment

**J2EE JSP-00037: cannot load tag library {0} specified in web.xml**

**Cause:** A tag library defined in the application's web.xml file was not loaded.

**Action:** Verify that the taglib-uri and taglib-location are correctly formatted and point to valid values, and that the tag library implementations classes are available to the application.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JSP-00038: error preparing dependency file for tag file:**

**Cause:** An error was encountered while writing or preparing the dependency file for a tag file.

---

**Action:** Recompile the page that accesses the tag file after checking factors that impact file writing such as disk space, permissions, and file handles.

**Level:** 1

**Type:** WARNING

**Impact:** Files

**J2EE JSP-00039: invalid tag file: {0}. File must end with .tag or .tagx and start with /WEB-INF/tags or /META-INF/tags.**

**Cause:** Encountered a tag file path that is an invalid or non-existent location.

**Action:** Correct the tagfile-path element value by ensuring that it ends with either .tag or .tagx, and starts with either /WEB-INF/tags or /META-INF/tags.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JSP-00040: duplicate tag name : {0}. TLD is invalid**

**Cause:** A tag name that was used in more than one Tag Library Descriptor was visible to the application and caused an error.

**Action:** Tag names must be unique. Change the duplicate name in that tag or tag file element.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JSP-00041: The value {0} is invalid for main mode.**

**Cause:** An invalid value for the main mode was detected.

**Action:** Valid values for the main mode are recompile, reload and justrun.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**J2EE JSP-00042: The value {0} is invalid for debug.**

**Cause:** An invalid JSR45 debug parameter was specified.

**Action:** Valid values for debug are none, file and class.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**J2EE JSP-00043: The value {0} is invalid for tags reuse.**

**Cause:** An invalid tags reuse parameter was specified.

**Action:** Valid values for tag reuse are compiletime, compiletime-with-release and none.

**Level:** 1

**Type:** WARNING

---

**Impact:** Configuration

**J2EE JSP-00044: error invoking the following JSP tag life-cycle method: {0}**

**Cause:** An internal error occurred. The JSP runtime failed to execute a method provided by the Oracle JSF Injection Provider. The JSP page in which the error occurred will not be serviced.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JSP-00045: unable to scan annotation for tag {0}: {1}**

**Cause:** The tag implementation class given in the error text could not be scanned for annotations.

**Action:** See the error cited in the error message to determine what action is required.

**Level:** 1

**Type:** WARNING

**Impact:** Files

**J2EE JSP-00046: Unable to load class {0} while scanning for annotated JSP tags.**

**Cause:** The tag class for annotations cited in the error message was not scanned. The class appeared to be missing, or was unloadable.

**Action:** Make sure that the missing class is available in the application class path. Verify that the class file was generated with a jdk version that supports annotations.

**Level:** 1

**Type:** WARNING

**Impact:** Files

**J2EE JSP-00047: unable to scan annotation {0}. It is not a JSP tag.**

**Cause:** The class to be scanned does not implement the JspTag interface or cannot be loaded.

**Action:** Make sure the class is available in the application classpath and that it implements the javax.servlet.jsp.tagext.JspTag interface.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JSP-00048: annotation scanning is incomplete: {0}**

**Cause:** Scanning for annotations in the Tag Library Descriptors, visible to the application, was not completed.

**Action:** Verify that the class is available in the applications classpath. If so, check application server log files for problems such as out of memory, file permissions, network access.

**Level:** 1

**Type:** WARNING

---

**Impact:** Files

**J2EE JSP-00050: Parameter {0} is no longer supported as of Oracle Containers for J2EE 11g. The parameter is ignored.**

**Cause:** An application attempted to use the parameter cited in the error message that was desupported as of release 11G.

**Action:** You can avoid this message by removing the given parameter.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**J2EE JSP-00053: The value {0} is an invalid value for generic servlet mode.**

**Cause:** An invalid parameter for the generic servlet mode was specified.

**Action:** Use a valid parameter value. They include shared, single, none, and single\_and\_persist.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**J2EE JSP-00054: Unable to retrieve HttpApp object through ThreadState.**

**Cause:** An application that did not use the default OC4J HttpApplication object failed to supply its own application context object.

**Action:** Supply the application context or allow the use of the default one.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**J2EE JSP-00056: The web.xml at {0} is version 2.3 but has a <jsp-config> element. Ignoring <jsp-config> element.**

**Cause:** Web.xml version 2.3 does not include support for <jsp-config>

**Action:** Either remove the <jsp-config> element or upgrade the web.xml to version 2.4 or higher

**Level:** 1

**Type:** WARNING

**Impact:** Other

**J2EE JSP-00057: unable to determined the last-modified date of the file at path, {0}.**

**Cause:** This is usually caused by an IO error. However this error may related to something that happened before this instance of OC4J started. This has been known to happen if at some point two processes attempted to write to the same file at the same time. This error can also occur if the file was last modified within one second of EPOCH (at 0 hour on January 1, 1970), in this case it should be ignored.

**Action:** Verify that the file is not corrupted. If it is not, this error can be ignored. You may use the touch command, in unix, to update the last modified date of the file to prevent subsequent logging of this error. If the file is corrupted attempt to determine the cause of the corruption and fix it, or Contact Oracle Support Services.



---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**J2EE JSP-00058: error attempting to parse web.xml at {0}.**

**Cause:** Error parsing the web.xml file located at the path location listed in the log message.

**Action:** Attempt to fix the error in the web.xml file base on the information contained in the log message.

**Level:** 1

**Type:** WARNING

**Impact:** Deployment

**J2EE JSP-00069: Name space, {0}, also known as {1} will override name space {2}**

**Cause:** The namespace definition in the last tld defining the namespace overrided any previous definition of that namespace.

**Action:** See error message.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**J2EE JSP-00070: an unlikely, but generally harmless, situation has been detected.**

**Additional information follows: {0}.**

**Cause:** JSP encountered an rare situation. This should not cause any adverse effect on yor application.

**Action:** If this occurs in the absence of other errors, this is most likely a benign situation, if accompanied by other error messages, this may held diagnose the root cause of the problem reported by the other error messages. You may Contact Oracle Support Services to help us improve the product in future releases. Oracle Support Services may recommend increasing the log level to FINER to help understand the situation.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**J2EE JSP-00101: Inconsistent use of the DMS (statistics aggregation) framework. The problem occured in application, {0}, for this uri: {1}. {2}**

**Cause:** Internal error. Inconsistent gathering of performance statistics

**Action:** Examine the error message to determine which statistics are inconsistent; those statistics should not be trusted. Contact Oracle Support Services and give them the full error message.

**Level:** 1

**Type:** ERROR

**Impact:** Performance

**J2EE JSP-00111: the Oracle DMS framework is unavailable.**

**Cause:** The JSP servlet could not find the Oracle DMS classes.

---

**Action:** If using a third-party application server, the DMS functionality will simply not be available. If using an Oracle Application Server, this message indicates that there is something wrong with the installation. In that case, contact Oracle Support Services and give them the full error message.

**Level:** 1

**Type:** WARNING

**Impact:** Installation

**J2EE JSP-00300: unable to access osgi.syspath, {0}, even though it exists.**

**Cause:** There is a problem with the path corresponding to System property `osgi.syspath`.

**Action:** Check that the path is valid, unlocked, and that WebSphere has read/write permissions for it.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**J2EE JSP-00301: unable to extract the local classpath field.**

**Cause:** There is a problem extracting the local class path from the WebSphere class loader.

**Action:** Contact Oracle Support Services and ask for a patch if this prevents `ojsp.next` from functioning normally.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**J2EE JSP-00302: unable to determine the osgi plugin classpath.**

**Cause:** There is a problem assembling the osgi plugin class path.

**Action:** Contact Oracle Support Services and ask for a patch if this prevents `ojsp.next` from functioning normally.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

## JBO-24000 to JBO-80008

**JBO-24000: no JAAS Context. Permission information is not available.**

**Cause:** An error occurred while initializing the Java Authentication and Authorization Service (JAAS).

**Action:** Make sure that the JAAS configuration is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-24001: Role {0} is not found.**

**Cause:** An error occurred while retrieving the role.

**Action:** Make sure that the role information is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-24002: User {0} is not found.**

**Cause:** An error occurred while retrieving the user.

**Action:** Make sure that the user information is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-24003: Attribute {2} in entity {1} is not updatable.**

**Cause:** An attempt was made to update the attribute, but the user did not have permission or the attribute was not updatable.

**Action:** Make sure that the user permission and updatable setting for the attribute are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-24004: Rows cannot be removed from entity {0}.**

**Cause:** An attempt was made to remove the row, but the user did not have permission or the entity was read-only.

---

**Action:** Make sure that the user permission and read-only setting for the entity are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-24005: Rows cannot be created in entity {0}.**

**Cause:** An attempt was made to create a row, but the user did not have permission or the entity was read-only.

**Action:** Make sure that the user permission and read-only setting for the entity are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-24006: The entity already has permission defined.**

**Cause:** The entity already has permission defined.

**Action:** Modify permission def is not allowed.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25000: SQL type {0} is invalid.**

**Cause:** An attempt was made to generate a null value for a domain with an invalid SQL type.

**Action:** Provide a valid SQL type name for the domain. Examples include VARCHAR, CHAR and NUMBER. See `oracle.jbo.server.OracleTypeMapEntries` for a full list.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25001: Object {1} of type {0} already exists.**

**Cause:** An attempt was made to load a business component with the same name and type as another business component already loaded by the application module.

**Action:** Provide a different name for the business component. If a null value or null string is provided for the name, the framework will create a unique name within the scope of the application module.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25002: Definition {1} of type {0} is not found.**

**Cause:** A definition object with the given name could not be found.

---

**Action:** Provide a correct name for the business component definition (using the format 'packagename.objectname') and ensure that the definition is available on the classpath. This error can also occur if there is a case conflict, as when the database expects 'DEPTNO' and receives 'Deptno' instead.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25003: Object {1} of type {0} is not found.**

**Cause:** A business component object with the given name could not be found in the application module.

**Action:** Provide a different name for the business component object or create a new business component with the given name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25004: Definition name {1} of type {0} is invalid.**

**Cause:** An attempt has been made to load an invalid definition name or associate a definition name with a type for which it is not valid.

**Action:** Ensure that the name is a valid Java identifier with no spaces or punctuation, and conforms to the format 'packagename.objectname'.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25005: Object name {1} of type {0} is invalid.**

**Cause:** An attempt has been made to associate a business component name with an object for which it is not valid.

**Action:** Ensure that the name is a valid Java identifier with no spaces or punctuation, and conforms to the format 'packagename.objectname'.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25006: Value {2} passed as parameter {1} to method {0} is invalid: {3}.**

**Cause:** An attempt was made to invoke a business components method with an invalid parameter value.

**Action:** Pass a correct value for the parameter. To determine the allowed values for a given parameter, check the Javadoc for the method that throws this exception. For example, Javadoc indicates that the 'DBTransactionImpl.executeCommand' method throws this exception when the 'command' parameter is empty.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**JBO-25007: The validation flag cannot be reset for a default iterator.**

**Cause:** An attempt was made to reset the row validation flag for the default iterator of a rowset or view object.

**Action:** Reset the row validation flag for the rowset or view object instead. This will create a secondary iterator to allow the rowset or viewobject to navigate to another row without validating.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25008: Object {0} cannot be removed because it is referenced by object {1}.**

**Cause:** An attempt was made to remove a view object that is participating in a view link.

**Action:** Remove the view link before removing the view object.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25009: Cannot create an object of type:{0} from type:{2} with value:{1}**

**Cause:** A domain object could not be created with the given value. Either a domain constructor that accepts the given value does not exist, or there is no conversion method in the domain object for the given value type, or the domain constructor threw an unexpected exception.

**Action:** Ensure that the value being passed is valid with respect to the domain type being created. For example, passing the string value 'one' to the 'oracle.jbo.domain.Number' constructor will throw this exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25010: A validation failure has occurred while creating a domain with value {0}.**

**Cause:** Validation failed with the given value in a domain constructor. This exception is thrown in the domain type 'validate()' method.

**Action:** Provide a valid value for the domain type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25011: Rowset {0} is forward only.**

**Cause:** An attempt was made to invoke an invalid navigation method on a forward-only view object or rowset.

**Action:** Either remove the forward-only setting for the view object or rowset, or do not invoke navigation methods other than 'next()' on the forward-only view object or rowset.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**JBO-25012: View object {0} does not have entity {1} as its primary base.**

**Cause:** The client attempted to locate a view row that has the given entity row as its primary entity row. However, the entity row's entity definition does not match the entity definition of the view object's primary entity object base.

**Action:** Ensure that the entity row used to locate view rows is based on the same entity definition as the view object's primary entity object base.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25013: Too many objects match the primary key {0}.**

**Cause:** An attempt was made to add a newly fetched or created entity to the cache, but the new entity has the same primary key as an existing entity. The primary key must be unique for this entity type.

**Action:** Add more attributes to the key definition for the entity type, so that each row for this entity is uniquely identifiable. Or fix the primary key value so that this entity has a unique key identifier.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25014: Another user has changed the row with primary key {0}.**

**Cause:** The database value does not match the cached value for this entity object. This could happen when another user or operation has committed modifications to the same entity row in the database. This exception can also be thrown if the 'equals' method on one of the domain type attributes in the entity fails.

**Action:** Choose from the following options: 1. Verify that another user or operation has not modified the same row in the database. If this entity has attributes of a domain type verify that the `equals()` method on these domains do not fail when comparing the existing cached value with the newly fetched value. 2. For any attributes/columns that are updated by the database, modify the entity attribute definition by selecting 'Refresh after update' on the Attribute Settings page of the Entity Object Wizard. 3. Use 'view.executeQuery()' frequently, especially after any operations that result in data being changed.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25015: Query collection {0} is closed.**

**Cause:** An attempt was made to execute a query or access a row from a closed or removed view object or rowset.

**Action:** Verify that the view object or rowset is not removed or closed.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**JBO-25016: View object {0} is read-only.**

**Cause:** An attempt was made to modify data for a view object which is declared to be read-only. This includes creating a new row for this view object, removing a row, or modifying attributes of a view row for this view object.

**Action:** Create a view object with the read-only flag set to 'false' in order to modify data.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25017: New entity row of type {0} cannot be created.**

**Cause:** An unexpected exception occurred while creating a new entity instance.

**Action:** Ensure that the entity has a public default constructor. Fix the cause of the `InstantiationException` or `IllegalAccessException` that appears in the details of this exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25018: New view row of type {0} cannot be created.**

**Cause:** An unexpected exception occurred while creating a new view row instance.

**Action:** Ensure that the view row has a public default constructor. Fix the cause of the `InstantiationException` or `IllegalAccessException` that appears in the details of this exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25019: Entity row with key {1} is not found in {0}.**

**Cause:** An attempt was made to lock a nonexistent row in the database. This could occur when the cache has an entity which was subsequently deleted from the database by another user or operation.

**Action:** Remove the current entity from the entity cache by calling 'remove'. Or, synchronize the cache with the database by rolling back the current transaction or by committing the existing set of changes and then dropping the entity cache.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25020: View row with key {1} is not found in {0}.**

**Cause:** An attempt to find a referenced entity in the view row failed due to a changed foreign key value.

**Action:** Provide a valid foreign key value or remove the current one.

**Level:** 1

**Type:** ERROR



---

**Impact:** Programmatic

**JBO-25021: Domain object type {0} cannot be created.**

**Cause:** A domain object could not be created with the given value. Either a domain constructor that accepts the given value does not exist, or there is no conversion method in the domain object for the given value type, or the domain constructor threw an unexpected exception.

**Action:** Ensure that the value being passed is valid with respect to the domain type being created. For example, passing the string value 'one' to the 'oracle.jbo.domain.Number' constructor will throw this exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25022: A view link {0} already exists between source view object {1} and destination view object {2}.**

**Cause:** An attempt was made to set the master rowset for this rowset more than once.

**Action:** Do not invoke 'setMasterRowSetIterator' more than once on a rowset.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25023: Operation {0} on domain value {1} of class {2} cannot be performed.**

**Cause:** An unexpected domain exception occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25024: Method {0} is obsolete.**

**Cause:** An attempt was made to use an obsolete type map constructor.

**Action:** Verify that the type map is compatible with this version of the framework. See example type maps in 'oracle.jbo.server.OracleTypeMapEntries'.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25025: Rowset with XML tag {0} cannot be loaded.**

**Cause:** An error occurred while reading the XML data for a view object. This exception might contain other ReadXMLExceptions.

**Action:** Fix the contained row-level or attribute-level exceptions in the details for this exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**JBO-25026: Row {1} with XML tag {0} cannot be loaded.**

**Cause:** An error occurred while reading the XML data for a view row. This exception might contain other ReadXMLExceptions for contained rowsets or attributes.

**Action:** Fix the rowset-level or attribute-level exceptions in the details for this exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25027: Attribute {1} at index {2} with XML tag {0} cannot be loaded.**

**Cause:** An error occurred while reading the XML data for an attribute of a view row. This exception might contain other JboExceptions thrown from the set method for this attribute.

**Action:** Fix the JboException in the details for this exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25028: Domain object type {0} cannot be created: {1}.**

**Cause:** A domain object could not be created with the given value. Either a domain constructor that accepts the given value does not exist, or there is no conversion method in the domain object for the given value type, or the domain constructor threw an unexpected exception.

**Action:** Ensure that the value being passed is valid with respect to the domain type being created. For example, passing the string value 'one' to the 'oracle.jbo.domain.Number' constructor will throw this exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25029: Domain class {0} is not found.**

**Cause:** The named data class (typically a domain) could not be found.

**Action:** Ensure that the data class is accessible from the CLASSPATH and is a valid data class.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25030: Detail entity {0} with row key {1} cannot find or invalidate its owning entity.**

**Cause:** No container entity was found for a detail entity in a composition association. This could occur if a nonexistent master key value was passed in during creation of a new detail entity instance, or if the foreign key value of this entity was modified so that it no longer matched any master entity.

**Action:** Pass a valid foreign key value to the 'create' method or 'setAttribute' method so that an appropriate master row is found for this entity.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25031: View row for view object {0} is missing entity row for {1}.**

**Cause:** The client attempted to access an attribute of a view which is mapped to an entity row, but the corresponding entity row is null. If the view object consists of multiple entity object bases and if the secondary entity object bases are reference-only, the entity rows could be null if the foreign key linking the primary entity to the secondary entity object is null.

**Action:** Do not try to access attributes of missing entity rows in this situation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25032: Passivation to target store {1} is unsuccessful.**

**Cause:** A failure occurred while trying to passivate the application module or transaction state.

**Action:** Resolve the detail exception raised by the passivation target store (Database, File or Memory).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25033: Activating state with id {0} from target store {1} is unsuccessful.**

**Cause:** A failure occurred while trying to activate the application module or transaction state.

**Action:** Resolve the detail exception raised by the passivation target store (Database, File or Memory) and ensure that the state snapshot ID exists in the target store.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25034: Row with handle {1} is not found in rowset {0}.**

**Cause:** The client attempted to locate a row with a stale row handle. This error might be raised if the client tries to take a row out of one query collection and use its handle to find a row in another query collection. Note that if the client calls `executeQuery` on a rowset, it might receive a new query collection. Thus, this error might occur if the client retrieves a row from a rowset, takes its row handle, calls `executeQuery`, and then tries to locate the row using the saved handle. This exception might also be raised if a row reference is used across transaction boundaries and the row handle has become stale and hence the corresponding row cannot be found.

**Action:** Make sure that the row handle is not stale. One approach is to find the row again using its primary key before attempting to act on the row.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**JBO-25035: The application module passivation store is invalid.**

**Cause:** An application attempted to change an application module's passivation store after it had been initialized. The passivation store (Database, File or Memory) can only be initialized once. If the customer application logic has not specified a passivation store when the serialization framework is invoked, the passivation store is initialized by the framework.

**Action:** Check the client application logic for invocations of `ApplicationModuleImpl.setStoreForPassiveState` which are invoked after the application module passivation store has been initialized.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25036: An invalid object operation was invoked on type {0} with name {1}**

**Cause:** An application invoked an object operation that is not supported in the object's current state.

**Action:** Remove the invalid operation invocation or provide exception handling logic.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25037: Detail row set {0} is missing a master row set iterator for view link {1}, master view object {2}.**

**Cause:** This row set is a detail in a master-detail relationship, but it is missing a master row set iterator. Most likely, this occurred because a master row set iterator was removed through a call to `removeMasterRowSetIterator()` and has not been replaced with an appropriate one.

**Action:** Call `setMasterRowSetIterator()` to provide a valid master row set iterator.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25038: Value {2} passed as parameter {1} to method {0} is invalid.**

**Cause:** An attempt was made to invoke a business components method with an invalid parameter value.

**Action:** Refer to the documentation of error message JBO-25006 (EXC\_INVALID\_PARAMETER) for more information. The difference between this error message and EXC\_INVALID\_PARAMETER is that this version does not include an explanation. In general, Oracle recommends using JBO-25006 instead of JBO-25038.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**JBO-25039: No current row in row set iterator {0}**

**Cause:** The client attempted to work with the current row of a row set iterator, but the iterator has no current row.

**Action:** Position the iterator to the correct row and perform the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25040: Row should be locked before getting an output stream from an attribute.**

**Cause:** The row containing a large object was not locked before attempting to call a method on the large object that could potentially change the data of the object.

**Action:** Lock the row before attempting to get an output stream or write into a large object domain instance.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25041: Type map cannot convert data from {1} to {0} with operation {2}.**

**Cause:** The TypeFactory class asked the TypeMapEntries class to convert data, but the TypeMapEntries class did not know how to perform the conversion. This is typically an issue with the TypeMapEntries implementation.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25042: Row of trans post listener handle {0} not found in list.**

**Cause:** Entity row of the given handle is not found in transaction post listener list. Most likely cause of this error is as follows: the user requests certain operation. The operation tries to get access to the row in database. This fails for whatever reason (this exception's detail might have further information). The system tries to fix the problem at the entity level. It looks for the entity row in the transaction post listener list. The specified row is not found.

**Action:** Look at the details and see if the cause can be determined from them. Check to see if concurrent updates to database could have caused the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25043: Extraneous key {0} of index {1} (in key-value array) passed to findByKey for view object {2}.**

**Cause:** Extraneous key passed in to findByKey(). For example, suppose the View Object expects no more than a two-part key, but the key passed into findByKey is a three-part key. Then, this exception will be thrown.

**Action:** Provide a valid key.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**JBO-25044: Application state snapshot is based on an older version of the application definition metadata.**

**Cause:** An attempt was made to activate application module or transaction state based on an older metadata definition into an application module with a later metadata definition.

**Action:** Ensure that snapshots used for state activation were generated from the currently running version of the application definition metadata.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25045: Row set iterator {0} has detected an implicit synchronization attempt.**

**Cause:** An attempt was made to implicitly synchronize an iterator in a 3-tier running environment. When the application module synchronization mode is set to SYNC\_BATCH, iterator synchronization must be done explicitly.

**Action:** Remove code that attempts to synchronize the iterator implicitly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25046: Requested row not available in row set iterator {0}.**

**Cause:** This exception is thrown when running in 3 tier SYNC\_BATCH mode. The user requested a row, but that row is not available in the cache.

**Action:** Make appropriate API calls to bring the required row into cache. Then, try to get the row again.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25047: Attempt to make call to server detected for application module {0}.**

**Cause:** An attempt to make a call to server detected for an operation that is supposed to work only with client cache.

**Action:** Remove code/operation that attempts to call server.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25048: Operation {0} is invalid for a working set object.**

**Cause:** This operation is invalid for this working set object. It might be because the operation doesn't make sense in batch mode, or because the batch communication mode (`WSApplicationModuleImpl.getBatchCommMode()`) does not allow this operation.

**Action:** Remove code/operation that calls the named method of set the batch communication mode to allow this operation.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25049: Entity {0} cannot be set to batch mode because a key attribute is marked as refresh-on-insert or refresh-on-update.**

**Cause:** An attempt was made to set batch mode on an entity that has a primary key marked as refresh-on-insert or refresh-on-update.

**Action:** Remove the refresh-on-insert or refresh-on-update setting of the primary key attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25050: Batch mode post operation failed. See Exception details for a list of failures.**

**Cause:** Posting entities in batch mode failed with a set of exceptions

**Action:** Fix the cause for each of the exceptions in the details array.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25051: Row of range index {1} is not found in RowSetIterator {0}.**

**Cause:** The client has attempted to locate a row with a range index, but the Row Set Iterator's range does not have a row at the index. It might be that the range index is too big ( $\geq$  the range size), or that the range is at the bottom and the range index is beyond the last row of the Row Set. Or, the Row Set might have been reset because of operations like rollback and clear-cache. Hence, the range is empty and no row is found

**Action:** Make sure that the row set iterator is open and has rows in its range. Also, make sure that the range index falls between the first and the last row of the range.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25052: View object {0} with no key attributes cannot be activated.**

**Cause:** A view object with no key attributes was configured to passivate one or more of its transient attributes. However, a view object without key attributes cannot participate in state passivation.

**Action:** Define one or more key attributes for this view object.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25053: Cannot navigate with unposted rows in a RangePaging RowSet.**

**Cause:** An attempt has been made to navigate a rowset in Range Paging mode when the rowset has inserted/removed rows.

---

**Action:** Post this transaction before navigating.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25054: Cannot locate the specified stack snapshot id: {0}**

**Cause:** An attempt has been made to activate a stack snapshot that does not exist. The specified snapshot might already have been activated or the stack might already have been cleared by a previous rollback/commit.

**Action:** Ensure that stack snapshot ids are maintained by the application across transaction boundaries.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25055: Snapshot {0} cannot be removed.**

**Cause:** An attempt was made to remove a persistent snapshot that is referenced by the snapshot stack.

**Action:** Clear the snapshot stack before attempting to remove the referenced snapshot.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25056: Cannot call removeFromCollection() or removeAndRetain() on an Entity row: Entity name {0}**

**Cause:** An attempt has been made to call removeFromCollection() on an Entity row. It is illegal to call removeFromCollection() on an Entity row.

**Action:** Remove code that calls removeFromCollection() on an Entity row.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25057: Entity row update operation did not find matching row: Entity name {0}, key {1}**

**Cause:** In LOCK\_OPTUPDATE locking mode, an attempt was made to update an Entity row. The update operation failed to update any row.

**Action:** Another user might have modified the row and committed the changes.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25058: Definition {1} of type {0} is not found in {2}.**

**Cause:** No business component definition found with the given name in the project classpath.



---

**Action:** Provide a correct name for the business component definition and ensure the definition is available on the classpath. Names are of the format `<code>myProjectPackage.BusinessPackage.BusinessComponent</code>`. This error can also occur if there is a case conflict, as when the database expects 'DEPTNO' and receives 'Deptno' instead.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25059: View Object {0} has ManageRowsByKey turned on, but its key definition is empty**

**Cause:** This View Object is not Entity based, and its ManageRowsByKey flag is true. Yet, its key definition is empty. Restated, the user has asked for the View rows to be managed by keys, but the key definition is empty (which would produce empty keys for all rows).

**Action:** In order to manage EO-less View Object by key, a meaningful (non-empty) key definition must be supplied.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25060: Unexpected error encountered while trying to retrieve the next row from JDBC ResultSet for collection {0}**

**Cause:** An unexpected exception was thrown while retrieving the next row from JDBC ResultSet.

**Action:** Take a look at the detail exception for further information and fix underlying problems.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25061: Cannot enable passivation for internal ViewObjects and rowsets.**

**Cause:** ViewRowSetImpl.setPassivationEnabled called for internal rowset

**Action:** Create a datamodel ViewObject instance and use rowsets from that ViewObject to make them passivation enabled.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25062: Cannot find a matching detail ViewObject. Link definition: {0}, master row set iterator {1}.**

**Cause:** An attempt was made to create detail rowset. However, no matching detail view object could be found.

**Action:** Ensure that a matching view object is present before attempting to create a detail rowset.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**JBO-25063: Operation {0} cannot be performed because the working set object is not bound.**

**Cause:** This operation is invalid for this working set object because the working set object is not bound to actual implementation object.

**Action:** This action must be performed after the working set object is bound.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25064: Variable {1} in RowSet {0} is not a where-clause parameter. It is of kind {2}.**

**Cause:** A call was made to define or set a named where-clause parameter value. However, the named variable's 'kind' is not 'where'. That is, the variable is not a where-clause parameter.

**Action:** Make sure that the variable name is correct and that the named variable is a where-clause parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25065: Named where-clause parameter {0} does not belong to ViewObject {1}. It belongs to an object of type {2}.**

**Cause:** An attempt was made to remove a named where-clause parameter. However, this where-clause parameter is owned by neither the RowSet nor the ViewObject. Therefore, the parameter cannot be removed.

**Action:** It is illegal to try to remove a named where-clause parameter that does not belong to either the RowSet or the ViewObject.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25066: View Object {0} is based on an Entity built from Row Set. For such a View Object, cannot include QUERY\_MODE\_SCAN\_DATABASE\_TABLES in its query mode.**

**Cause:** An attempt was made to include QUERY\_MODE\_SCAN\_DATABASE\_TABLES in the View Object's query mode (through a call to setQueryMode()). However, this View Object can perform query only through Entity Object. Hence, QUERY\_MODE\_SCAN\_DATABASE\_TABLES is inappropriate.

**Action:** The View Object is probably based on an Entity, which in turn is based on a RowSet (EntityDefOverRowSet). It is illegal to use QUERY\_MODE\_SCAN\_DATABASE\_TABLES for a View Object built on top of an Entity which is built over a Row Set. Do not include QUERY\_MODE\_SCAN\_DATABASE\_TABLES in the setQueryMode() invocation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**JBO-25067: Entity {0} has a subclass EO {1} and no discriminator. Therefore this base Entity cannot be used to create an Entity Row.**

**Cause:** An attempt was made to create a new instance of an Entity Row. However, this Entity Definition has a subclass Entity Definition with no discriminator. That is, this Entity Definition should really be abstract.

**Action:** Typically in this situation, the base class should not instantiate any row. Use the subclass Entity to create the row

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25068: Entity {0} has a base EO {1} with no discriminator, but base EO has rows in its cache. Cannot populate both caches.**

**Cause:** An attempt was made to create a new instance of an Entity Row. However, this Entity Definition is a subclass Entity Definition with no discriminator, and a base EO has a row already instantiated. A conflict exists because nothing discriminates this Entity from the base Entity.

**Action:** Typically in this situation, the base class should not instantiate any row. Use the subclass Entity to create the row

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25069: Row definition {0} has two sibling subclasses defs, {1} and {2}, but no discriminator to distinguish them.**

**Cause:** Two sibling subclasses of a Row Definition are found, but the Row Definition has no discriminator. This condition is disallowed because when a row is either retrieved or created, the framework cannot determine the correct row class. That is, the hierarchy forks without a discriminator. The only situation whether subclassing is allowed without discriminator is when the tree is straight lined and only one of the classes in the hierarchy line is used to instantiate rows.

**Action:** Either define discriminator attributes, or do not create siblings in the row class hierarchy.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25070: Where-clause param variable {0} needs ordinal index array.**

**Cause:** This view object of entity is using Oracle number style binding (:1, :2, ... binding, not named binding) or JDBC style (? binding). A variable of where-clause-param kind is found, but the extended int array that designates where the value should be bound is missing.

**Action:** When defining a variable for where-clause param in conjunction with a binding style which is not Oracle named binding, specify an int array that designates where the value should be bound.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**JBO-25071: Applying List binding {1} with given set of values leads to multiple matching rows for a row of type:{0}, key {2}**

**Cause:** ListBinding results in more than one matching row for the given set of mapping values. Only one matching row is expected.

**Action:** Provide a new set of mapping values that will end up in a single matching row or adjust the StructureDef metadata to allow defaulting to the first matching row.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25072: Applying List binding {1} with given set of values leads to no matching row for a row of type :{0}, key {2}**

**Cause:** ListBinding failed to find any matching row for the given set of mapping values.

**Action:** Provide a new set of mapping values that will end up in a single matching row or adjust the StructureDef metadata to allow defaulting to the first matching row.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25073: Definition {1} of type {0} is hidden**

**Cause:** Def object is hidden. An attempt was made to access a hidden def object.

**Action:** This particular operation is disallowed on a hidden def object. Avoid this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25074: Definition {1} of type {0} is hidden in {2}, operation: {3}**

**Cause:** Def object is hidden. An attempt was made to access a hidden def object in the specified container object.

**Action:** This particular operation is disallowed on a hidden def object. Avoid this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25075: Definition {0} of type {1} is read-only. Cannot modify it**

**Cause:** Attempting to modify or save data for a def object which is read-only.

**Action:** If the def object is shared, do not attempt to modify anything. If the def object is session scoped, do not modify it if there are running instances of that definition. If the def object is session scoped and is not being used by any running instance, mark it editable before modifying it.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25076: Expression validator does not allow setting a value to source attribute:{0}.**

**Cause:** Expression validator does not allow direct assignment of a value to an attribute. This is to avoid possible cycle of assignments/validations.

**Action:** Remove direct assignments. If assignment is necessary, verify there is no cycle, and then use constructs like 'source.MyVar = ..'.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25077: Name {0} not found in the given object: {1}.**

**Cause:** An invalid name was passed in an expression.

**Action:** Fix the expression by passing in a correct name for a property.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25078: Key attribute {1} for {0} not populated**

**Cause:** While building the where-clause statement for an entity row operation (e.g., fault-in, delete, or update), the named key attribute value is not populated.

**Action:** This entity row operation requires the key attributes to be populated. Make sure that all key attributes have values in them.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25079: The list of discriminator attributes for subclass {0} is different from that of the base {1}**

**Cause:** In a subclass hierarchy of RowDefs, found a subclass RowDef whose discr attr list has more attrs than the base class. It is disallowed for a subclass to change discr attr list in the subclass hierarchy.

**Action:** Make sure that subclass RowDefs have the same set of discr attributes as the base class.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25080: Definition name: {0} does not match the file in which it is loaded from: {1}**

**Cause:** An attempt has been made to load a definition metadata file named differently from the name or id of the top level xml element in the file.

**Action:** The name should be a valid Java identifier with no spaces or punctuation. The name or id of the top level xml element in the file should match the file name.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25081: The new fetch size {0} passed into setFetchSize() for a view object {2} is invalid. It is smaller than the old value {1}.**

**Cause:** The fetch size passed into `ViewObjectImpl.setFetchSize()` is smaller than the previous value. Fetch size of a view object cannot decrease.

**Action:** Specify a value which is bigger than the current value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25082: Cannot change the access mode for the row set {0} because either the VO has more than one RS or the RS has more than one iterator.**

**Cause:** An attempt has been made to change the row set's access mode from scrollable/forward-only to range-paging or vice versa. This is allowed only if the VO has one or no row set. Or, an attempt has been made to set the row set's access mode to forward-only, but this is allowed only if the row set has one or no iterator.

**Action:** Close other row sets or iterators before changing the access mode.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25083: Cannot create a secondary iterator on row set {0} because the access mode is forward-only or range-paging**

**Cause:** An attempt has been made to create a new row set iterator on a row set whose access mode is either forward-only or range-paging.

**Action:** Creation of secondary row set iterator is allowed if the row set's access mode is scrollable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25084: Cannot call last() on row set {0} because the access mode uses range-paging**

**Cause:** An attempt has been made to jump to the last row on a row set whose access mode uses range-paging.

**Action:** Replace 'last' with 'setRangeStart' for the range-paging based access mode.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25085: The value being set for attribute {0} does not match the value derived from list binding {1}**

---

**Cause:** An attribute value being set does not match the attribute value derived from a list binding. This typically happens in the following situations. First, suppose the user sets values for Deptno from 10 to 20 and Dname from ABC to DEF. If a list binding is triggered by Deptno and if it sets Dname to XYZ, the result is an inconsistent state where DEF does not match XYZ. In this situation, this exception is thrown. Second, suppose there is an EmpDept view object with Emp and Dept entity bases. Suppose Dept is reference and read-only and there is a list binding on Dept.Dname whose derived attribute is Emp.Deptno. If the user selects a new Dept through the dept name, a new Dept entity row is brought in (because a new Emp.Deptno is chosen). After this, the framework checks to make sure that the Dname coming from the new entity row matches the original selection from the list binding. If they do not match, this exception is thrown.

**Action:** Make sure the list binding definition and attribute set values end up in a consistent result (i.e., the derived values from the list binding match the row's attribute values).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25086: Operation {1} cannot be performed until definition {0} is resolved.**

**Cause:** An attempt was made to use a def object before resolving it. The def object must be resolved first.

**Action:** Make sure resolveDefObject() is called before this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25087: Cannot call getRowCount() on row set {0} because the access mode uses range-paging**

**Cause:** An attempt has been made to get the row count of a row set whose access mode uses range-paging.

**Action:** Replace getRowCount() with getEstimatedRowCount() for range-paging based access mode.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25088: Persdef {0} has no static definition set**

**Cause:** An attempt was made to perform an operation on a persdef that requires the static definition object, but the persdef has no static definition.

**Action:** Set the static definition object before attempting the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25089: View object {0} attempted to fetch rows beyond the row limit**

**Cause:** The view object attempted to fetch rows beyond a global row limit.

---

**Action:** If in a search region narrow down the results by providing more search criteria otherwise contact your system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25090: Attribute value {3} leads to duplicate keys for this entity type {1}.**

**Cause:** An attempt was made to set an attribute value that leads to addition of a newly fetched or created entity to the cache, but this value makes the entity key same as another existing entity. The primary key must be unique for this entity type.

**Action:** Add more attributes to the key definition for the entity type, so that each row for this entity is uniquely identifiable. Or fix the key value so that this entity has a unique key identifier.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25200: Application module is not connected to a database.**

**Cause:** The application module is not connected to the database.

**Action:** Provide a valid set of connection credentials to connect to a database.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25201: A database connection already exists.**

**Cause:** An attempt was made to reestablish a database connection.

**Action:** Disconnect the current database connection before trying to reestablish the JDBC connection.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25221: Method {0} not supported**

**Cause:** Attempting to call a method that is either not implemented or not supported.

**Action:** This method is not available on the called object. E.g. `setAttribute()` in `oracle.jbo.Key` class is not implemented and will throw this exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25222: Unable to create application module.**

**Cause:** The application module was typically not created for one of the following reasons: 1. Business components deployed in local mode were not found on the



---

classpath. 2. Unresolved classes existed on the server. 3. Java2 permissions were not granted. 4. Java pool size was too small.

**Action:** Depending on the cause, chose from the following actions: If business components are deployed in local mode, they might not be on the classpath. <br>If this is the cause of the error, the exception will usually be followed by a different exception, JBO-25002: NoDefException. If this occurs, try the following: Make a library for the business components. Add the library to the client's project properties. Include the library on the 'libraries' page when creating a deployment profile for the client (whether the client was a web application or a command-line application). Copy the library with the client to the target platform (whether the client was a web application or a command-line application). Include all the copied files (including the library) when setting the classpath on the target platform. There might be unresolved classes on the server. Try the following procedure to resolve any unresolved classes on the database. In the System Navigator, right-click the JDBC connection used to deploy the Business Components project. Choose Invoke SQLPlus from the context menu. Copy and paste the following SQLPlus script into the SQLPlus window. set termout off set echo off set heading off set pages 999 set linesize 2000 set feedback off select 'alter java class "' || replace(dbms\_java.longname(object\_name),'/','') || '" resolve;' from user\_objects where object\_type='JAVA CLASS' and status = 'INVALID' spool C:\temp\resolve.sql / spool off set echo on set termout on @C:\temp\resolve.sql There might be missing Java2 permissions. If this is the cause of the error, there will be permissions errors in the database trace file. To correct the problem, see the help topic 'Granting Permissions on a Business Components EJB' for information on granting Java2 permissions. Note: The location of the database trace file varies from installation to installation, but in a default Windows NT installation, the file will be in the directory ORACLE\_HOME\admin\orcl\udump and will have the form orclnnnn.trc. The Java pool size might be too small Business Components for Java deployed as EJBs work best with a Java pool size of at least 50MB. Edit the init.ora file and check the <code>java\_pool\_size</code> parameter. If it is under 50MB, change it, restart the database, and try the connection again.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25223: Cannot create multiple root application modules.**

**Cause:** When business components are running inside JServer, only one root application module can be created. This is because JServer (already) provides one transaction context.

**Action:** It is illegal to attempt to create multiple root transactions when running inside JServer.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25224: Could not disconnect and retain application module state because database state exists for current connection.**

**Cause:** Trying to retain the application module state during a transaction disconnect failed.

**Action:** The disconnect and retain application module state target requires that no database state exist before the transaction connection is closed. Examples of

---

database state include open database cursors in non-forward only view objects, database locks, and uncommitted database changes. The client should clean up this state by fetching or resetting any open view objects and committing any uncommitted changes.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25226: Application module definition {0} contains recursive AM reference.**

**Cause:** This application module definition contains recursive references to child application modules. For example, if application module definition appMod1 contains a child application module of appMod2, and appMod2 contains appMod1, this error will be raised.

**Action:** Remove recursive application module definition references.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25227: Recursive view links found. Master-detail chain: {0}.**

**Cause:** The user has attempted to create a view link (in an application module) that will result in a recursive loop of view links. The error message should show a chain of recursive master-detail relationships.

**Action:** If a static view link is causing the recursion, remove the view link from the application module. If a dynamic view link is causing the recursion, remove the code that creates the recursive view link.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25228: Unable to register a database change notification request for {0} view object**

**Cause:** The View Object that has auto refresh turned on failed to register an Oracle database change notification request.

**Action:** Ensure that the database user is granted CHANGE NOTIFICATION privilege. Look at the exception details for further troubleshooting.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25229: Unable to unregister a database change notification request for {0} view object**

**Cause:** The View Object that has auto refresh turned on failed to unregister an Oracle database change notification request.

**Action:** Look at the exception details for further troubleshooting.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**JBO-25230: XML document {0} has no stream to save**

**Cause:** An attempt was made to save XML document, but the document has not been persisted (most likely saveXMLContents() is called without a call to writeXMLContents()).

**Action:** Call writeXMLContents() first.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25301: Application module {0} is not a root app module but has no parent**

**Cause:** While traversing the parenthood chain for application modules, a child application module was found with no container (parent) application module.

**Action:** If this application has added custom business component classes, the application code might be attempting to access a child application module before it is fully initialized. If this is not the case, this error probably represents some internal error in the framework, in which case contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25302: Component object {0} has no parent**

**Cause:** A business component is found without a container (parent) application module.

**Action:** If this application has added custom business component classes, the application code might be attempting to access a business component before it is fully initialized. If this is not the case, this error probably represents some internal error in the framework, in which case contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25303: Cannot clear entity cache {0} because it has modified rows**

**Cause:** A dirty entity cache cannot be cleared. The client asked to clear an entity cache but some rows in the entity cache have been modified. An entity cache with modified rows cannot be cleared.

**Action:** Do not attempt to clear an entity cache with modified rows in it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25306: Design-time attribute {0} of type {1} could not be persisted**

**Cause:** Could not persist a design-time attribute into the XML file.

**Action:** Identify the offending design-time attribute and contact Oracle Support Services.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**JBO-25307: XML file not open**

**Cause:** XML file is not open.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25308: The primary key of an existing entity bean cannot be modified for entity facade {0}.**

**Cause:** An attempt was made to modify the primary key of an existing entity bean. This is disallowed by EJB.

**Action:** Do not modify primary key of an old (not-new) entity bean.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-25309: The primary key of an entity bean cannot be null for entity facade {0}.**

**Cause:** The primary key of an entity bean is null. This is disallowed by EJB.

**Action:** Set the primary key to be not null.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26000: A Generic exception occurred during loading Customizations.**

**Cause:** Metadata objects failed to load due to unexpected or corrupt data in the XML file.

**Action:** Verify that the XML metadata for various components is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26001: XML File not found for the Container {0}**

**Cause:** Could not open the named XML file for reading.

**Action:** Try the following: Make sure that the file is present. In particular, if the file is to be found in a Zip/JAR file, make sure that the Zip/JAR file is included in the CLASSPATH. This error is also reported if the name of the XML file does not match the object Name specified in the XML file. If the file system supports case insensitive file names (e.g., Windows NT), make sure that the file name matches the object Name in the XML file in case-sensitive fashion. For a JPX file, this error is reported if the JPX file is missing the JboProject XML tag. Check the JPX file to make sure that the valid tag is in there. One XML file might be extending another XML file (specified by the Extends element in this XML file). This error is reported if the base XML file is not found. When loading the XML file for a package (JboPackage tag), this error is reported if some unexpected error occurs while

---

loading a contained object. In all of the above cases, a more descriptive message might be printed on Diagnostic. To see these messages, run the application with Diagnostic turned on, as in 'java -Djbo.debugoutput=console ...', to see Diagnostic messages.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26002: Error Parsing the XML file "{0}".**

**Cause:** Some XML parsing exception  
(`<code>oracle.xml.parser.v2.XMLParseException</code>`) was thrown.

**Action:** The XMLParseException information is output to Diagnostic. To see diagnostic messages, run the application with diagnostic turned on, for example 'java -Djbo.debugoutput=console ...'

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26003: Mismatch in the attribute indices declared in Java versus the indices in the definition for entity {0}.**

**Cause:** An error occurred while loading entity object definitions. An attribute index in the Java class for this entity has a mismatch with the index in the definition, or an attribute index is missing in the Java class.

**Action:** Ensure that the indices of attributes in the definition for this entity match the indices defined in the Java class for this entity.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26004: A recursive base definition is found while attempting to set the base definition of {0} to {1}.**

**Cause:** An attempt was made to set the base definition of another definition object, e.g., setting B's base definition to A (i.e., B Extends A). However, A already extends B. Setting a recursive (circular) subclassing relationship among definition objects is illegal.

**Action:** Review the subclassing hierarchy of the definition objects and correct errors.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26005: FetchMode must be either FETCH\_AS\_NEEDED, FETCH\_ALL or FETCH\_DEFAULT. View object {0}**

**Cause:** The fetch mode specified in the view definition XML file is not valid.

**Action:** Check the content of the XML file for the view definition. Look for an XML element named 'FetchMode'. Make sure that the value for that element is valid. Valid values are: 'FETCH\_AS\_NEEDED', 'FETCH\_ALL', and 'FETCH\_DEFAULT'

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26006: FetchSize must be a positive integer. View object {0}**

**Cause:** The fetch size specified in the view definition XML file is not valid.

**Action:** Check the content of the XML file for the view definition. Look for an XML element named 'FetchSize'. Make sure that the value for the element is a positive integer.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26007: MaxFetchSize should be MAX\_FETCH\_UNLIMITED, MAX\_FETCH\_DEFAULT or integer. View object {0}**

**Cause:** The maximum fetch size specified in the view definition XML file is not valid.

**Action:** Check the content of the XML file for the view definition. Look for an XML element named 'MaxFetchSize'. Make sure that the value for the element is a non-negative integer, or 'MAX\_FETCH\_UNLIMITED', or 'MAX\_FETCH\_DEFAULT'. A MaxFetchSize of 0 is the same as MAX\_FETCH\_UNLIMITED.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26008: Could not resolve reference to "{0}".**

**Cause:** A problem is found in resolving a view link definition or an association. In case of a view link, this error might be caused by the fact that the source or destination view object cannot be found. Or, if the view link ends have attribute names, this error might indicate that the named attributes cannot be found. Similarly, for an association, this error indicates that either source or destination entity object or attributes involved in the association cannot be found.

**Action:** Make sure the XML definition for the view link/association has correct view object/entity object/attribute names.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26009: Serialized file "{0}" is invalid. The root object is not a Business Component object.**

**Cause:** This error occurs if the application uses meta object serialization files (.ser files) instead of XML files. It indicates that after the .ser file was deserialized, the top level object returned from deserialization was not an instance of oracle.jbo.server.xml.JboElementImpl.

**Action:** Repair the corrupt .ser file.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**JBO-26010: Invalid Entity Attribute Name "{1}" specified for the View Attribute "{0}"**

**Cause:** Entity attribute name in the view definition XML file is invalid or is not found.

**Action:** Make sure that the entity name is valid. Also, check to make sure that the named attribute does exist in the entity object. The entity object is identified by the EntityUsage element.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26011: SQLType not specified for the View Attribute "{0}"**

**Cause:** Attribute definition found in XML file is invalid. It is missing SQLType value.

**Action:** Correct the error in the XML file.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26012: Invalid View Link Definition "{0}". View Link must have two ViewLinkDefEnds.**

**Cause:** The view link definition in the XML file is missing either the source or destination view link end. For a view link XML file, two elements named ViewLinkDefEnd should be found.

**Action:** Correct the error in the XML file.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26013: Naming Exception occurred while looking up the object "{0}".**

**Cause:** Meta object name passed for lookup is invalid.

**Action:** Normally, the meta object name is a dot-separated name of the meta object. For an entity object named Emp in package1.example, the correct name would be `<code>package1.example.Emp</code>`. To correct, locate where the invalid name is coming from (could be meta object names mentioned in an XML file, or the name of the project, etc.) and change the name to a valid one.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26015: View object {0} does not include a discriminator column {2} of entity base {1}.**

**Cause:** A view definition does not include a discriminator column of an entity base. If an entity base has discriminator columns, it must include all of them in the view object's attribute mapping.

**Action:** Change the view definition to include discriminator column attributes.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26016: Cannot set user query to view "{0}" because it is a destination in a view link**

**Cause:** An attempt was made to call 'setQuery()' on a detail view object in a master detail view link.

**Action:** Do not call setQuery() if the view object is a detail.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26017: Association or view link definition {0} has an invalid attribute list.**

**Cause:** The association or view link definition has a missing or invalid attribute list.

**Action:** Correct the error(s) in the XML file.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26018: Entity {0} cannot be posted to the database because it has no attributes set.**

**Cause:** An attempt was made to post a row with no attribute set. Some databases (Oracle Database in particular) do not allow an INSERT statement with no VALUE specified.

**Action:** Set some attributes on the row before attempting to insert it into the database.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26019: Attempting to remove a parent entity without removing all children entities**

**Cause:** Attempting to remove a master which has detail entities. In the case of a composition, a master cannot be removed if it has details.

**Action:** Remove all the details of this master by accessing the details via an association and removing all of them.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26020: Attempting to insert row with no matching EO base**

**Cause:** The application code tried to take a row from one row set (or view object) and insert it into another row set (view object). In response, the framework will make a copy of the row in the new row set. This new row will share references to the underlying entity objects. However, if the source and destination row sets do



---

not share any entity object bases at all, this operation will fail as it does not find any entity rows to share.

**Action:** When attempting to take a row from one row set and insert into another, make sure that they share at least one entity object base.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26021: NullPointerException while parsing XML file "{0}". Perhaps missing DTD file?**

**Cause:** A NullPointerException was thrown while parsing an XML file. A possible cause for this is that the DTD file is missing (oracle.jbo.dtd.jbo.dtd).

**Action:** Make sure the appropriate DTD file is present.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26022: Custom class {0} cannot be found.**

**Cause:** A custom class could not be found and loaded. The custom class might be for a component (for example, view object), a definition (for example, view definition), or a row (for example, view row or entity row).

**Action:** Make sure that the named class is reachable from the CLASSPATH. The detail exception (if present) provides more specific reasons why the attempt to locate and load the custom class failed.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26023: Custom class {0} is not assignable to {1}**

**Cause:** Custom class was found and loaded, but it is invalid in that it is not assignable to a framework (super) class.

**Action:** Make sure that the custom class subclasses the appropriate framework (super) class.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26024: An error occurred while creating InitialContext**

**Cause:** An error occurred while creating initial context. This error usually carries a detail exception which will give further information on the cause of the error.

**Action:** When running inside JServer, make sure that the database user (schema) has the setContextClassLoader permission. To grant this, the database system administrator can invoke the following PL/SQL procedure: EXEC DBMS\_JAVA.GRANT\_PERMISSION('&&1', 'SYS:java.lang.RuntimePermission', 'setContextClassLoader', null);

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**JBO-26025: An error occurred while trying to get System properties**

**Cause:** An error occurred while trying to get System properties. Specifically, System.getProperties() call failed.

**Action:** When running inside JServer, make sure that the database user (schema) has the proper property permission. To grant this, database system can invoke the following PL/SQL procedure: EXEC DBMS\_JAVA.GRANT\_PERMISSION('&&1', 'SYS:java.util.PropertyPermission', ', ', 'read');

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26026: An error occurred while loading properties from a properties file {0}**

**Cause:** An error occurred while trying to get load properties.

**Action:** Check to see if the named properties file contains valid Java properties.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26027: Unable to find resource. {0}**

**Cause:** Unable to find a resource

**Action:** Check to see if the resource exists and the framework code has adequate permissions to load the resource.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26028: View object {0} does not include a primary key attribute {2} of entity base {1}.**

**Cause:** A view definition does not include a primary key attribute of an entity base. When a view object uses an entity as one of its entity bases, it must include all primary key attributes of the underlying entity object.

**Action:** Change the view definition to include all primary key attributes.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26029: Could not find and load the type map class {0}**

**Cause:** Custom type map class could not be found and loaded.

**Action:** Make sure that the named class is reachable from the CLASSPATH. If jbo.TypeMapEntries property is specified, make sure that the property value is correct. Also, though unlikely, this might be caused by an improper implementation of SQLBuilder where it is returning an incorrect value for type map class name. The detail exception (if present) will provide more specific reasons why the attempt to locate and load the custom class failed.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26030: Failed to lock the record, another user holds the lock.**

**Cause:** This row has already been locked by another user or transaction.

**Action:** Try locking the row again and the operation should succeed after the other user or transaction has released the lock.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26031: Association end {0} of assoc {1} invalid for entity base {2} in view object {3}.**

**Cause:** Problem in secondary entity base definition in view definition. The named entity base is supposed to use the named entity association end to join it with another entity base, but, when resolved with the association definition, the association end does not resolve to the same entity. For example, suppose one builds a view object with Dept and Emp. Emp is supposed to join with Dept using the EmpEnd of the DeptEmp association. For such a view definition, the framework verifies that EmpEnd indeed is from Emp entity. If EmpEnd was from another entity, say Person (or Dept), it would not be correct to use that association end to perform join.

**Action:** Most commonly, this is caused by incorrect information in the view object XML file. Make sure that the association end for the named entity usage is not pointing at the wrong end of association.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26032: Operation {0} is invalid for a ViewCriteria or ViewCriteriaRow.**

**Cause:** The attempted operation is invalid for a ViewCriteria or ViewCriteriaRow.

**Action:** Remove code that attempts this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26033: Cannot find Application Data Model with name :{0}**

**Cause:** Cannot find application definition of the given name

**Action:** Fix the application definition name or make the appropriate .cpx file available in the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26034: Cannot find Configuration with name :{0}**

**Cause:** Cannot find configuration information in the application definition file

---

**Action:** Fix the Configuration name or make the appropriate .cpx file available in the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26035: Secondary entity usage {0} is missing parts of association description.**

**Cause:** A view definition is found with an entity usage definition where the secondary entity usage's association description is incomplete.

**Action:** Examine the view object's XML file. A secondary entity usage's association description should have the following elements: 'Association', 'AssociationEnd', and 'SourceUsage'. Check to see if any of these are missing.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26036: The configuration of meta object {0} causes recursive substitution.**

**Cause:** An attempt was made to set up meta object substitution that leads to recursion. For example, consider a substitution where C substitutes B, and B substitutes A, and A substitutes C. This results in a recursive substitution and will cause this error.

**Action:** Review the meta object substitution and correct errors.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26037: Cannot find matching EO from discriminator columns for view object {0}, entity base {1}, discr value {2}.**

**Cause:** While creating a new view row, the system found an entity object base with discriminator column attributes. However, the discriminator column values coming from the view row do not match any of the entity objects (the entity for the entity object base or any of its extended entities).

**Action:** Make sure that the view row discriminator column values match one and only one entity object.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26038: Cannot find an entity usage for entity {1} in view link definition {0}, view link end {2}.**

**Cause:** The view link definition is based on an entity association. One of its ends specifies the named entity definition, but the view definition for that view link end does not have an entity usage for that entity definition.

**Action:** Correct the error in the view link definition (XML file). In particular, check to see if the view link source and destination are not switched with those of the entity association.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**JBO-26039: View object {0} does not include an alternate key attribute {2} of entity base {1}, entity key {3}.**

**Cause:** A view definition does not include an alternate key attribute of an entity base. When a view object uses an entity as one of its entity bases, and when it defines a view object level alternate key using one of the entity alternate keys, it must map the entity attributes that make up the alternate key.

**Action:** Change the view definition to include all necessary alternate key attributes.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26040: Failed to post entity {1} to database during "{0}": SQL Statement "{2}".**

**Cause:** Some database error occurred while posting (writing) an entity to the database in JDBC batch mode. This error normally carries a detail exception from the database which will give further information about the database failure.

**Action:** Look at the details of the exception and address the database problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26041: Failed to post data to database during "{0}": SQL Statement "{1}".**

**Cause:** Some database error occurred while posting (writing) an entity to the database. This error normally carries a detail exception from the database which will give further information about the database failure.

**Action:** Look at the details of the exception and address the database problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26042: Failed to generate REF and OID on entity {0}.**

**Cause:** A database failure occurred while trying to generate an object ID (OID) and object reference (REF). When a new row is created on an entity which maps to an Oracle object table, an OID and REF for the new row are generated. This executes a SQL statement like select a.oid, make\_ref(table-name, a.oid) ... Somehow, this statement is failing.

**Action:** Ensure that : The Oracle database version is correct. The table in question is an object table. This error normally carries a detail exception from the database, which will give further information about the database failure. Take a look at the detail exception and address the database problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26043: REF and OID not supported by this SQLBuilder on entity {0}.**

---

**Cause:** An attempt was made to generate an object ID (OID) and/or a reference (REF) on a database system that does not support Oracle objects.

**Action:** Do not try to create OID or REF on a database system that does not support Oracle objects.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26044: Error while getting estimated row count for view object {0}, statement {1}.**

**Cause:** The application tried to get an estimated row count (getEstimatedRowCount()) on a row set. While building the appropriate query statement, executing it, and retrieving the estimated count, an error occurred. This error is accompanied by the SQL statement that caused the error. Also, it normally carries a detail exception from database, which will give further information about the database failure.

**Action:** Take a look at the SQL statement and the detail exception and address the database problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26045: Failed to generate PK-Based REF on entity {0}.**

**Cause:** A database error occurred while trying to generate an object ID (OID) from the primary key. This operation is valid only if the table in question is an object table and if the table specifies that the reference (REF) is PK based.

**Action:** Ensure that: The Oracle database version is correct. The table in question is an object table. The object table uses a PK-based REF. This error normally carries a detail exception from database which will give further information about the database failure. Take a look at the detail exception and address the database problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26046: PK-Based REF not supported by this SQLBuilder on entity {0}.**

**Cause:** An attempt was made to generate Oracle o8 object ref from a non-Oracle database SQLBuilder. This is not supported.

**Action:** Make sure that the correct SQLFlavor (i.e., SQLBuilder) is being used for the application and switch to the right one.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26047: LOCK\_OPTUPDATE mode update operation missing change indicator value: Entity {0}, key {1}.**

**Cause:** An attempt was made to update a row in LOCK\_OPTUPDATE mode and the change indicator attribute value is not present.

---

**Action:** Look at the attribute mapping of the View Object that read in this Entity row and make sure that the View Object includes the change indicator attribute. The LOCK\_OPTUPDATE mode requires the value to be present.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26048: Constraint "{2}" is violated during post operation "{0}" using SQL statement "{1}".**

**Cause:** A constraint violation occurred in the database while posting (writing) an entity to the database. This error carries a detail exception from the database which will give further information about the database failure.

**Action:** Fix the cause for the constraint violation. Look at the details of the exception and address the database problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26049: An error occurred during loading definition {0}.**

**Cause:** Metadata objects failed to load due to unexpected or corrupt data in the XML file.

**Action:** Verify that the XML metadata for various components is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26050: An error occurred while writing personalization definition {0}.**

**Cause:** An I/O error occurred while writing personalization definition.

**Action:** Check the detail I/O exception and make necessary correction.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26051: Unrecognized XML element tag {1} found in meta object {0}.**

**Cause:** The element tag of the XML file is not recognized.

**Action:** Examine the XML file and make sure that the element tag is one of the recognized ones.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26053: Invalid association or view link definition "{0}". Invalid unbound attribute list.**

**Cause:** An association or view link definition end has an invalid unbound attribute list. This error is raised if the unbound attribute is not one of the association/view link end attributes.

---

**Action:** Correct the error(s) in the XML file.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26054: Invalid version number for {0}. Require {1} or greater, but found {2}.**

**Cause:** The XML document is either missing the version number or has a version number which is lower than the required version number.

**Action:** Check to see if the XML document has gone through a proper migration process. If not, migrate the application.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26055: Failed to delete XML document {0}.**

**Cause:** An attempt was made to delete an XML document from disk, but this operation failed.

**Action:** When running with MDS, make sure that the metadata store supports the delete operation. Check the detail exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26056: Multiple occurrences of XML element {1} found in {0}. Only one expected.**

**Cause:** Multiple occurrences of an element were found in the XML document when only one was expected.

**Action:** Examine the XML document and see which element shows up multiple times. If the issue looks like a problem in the framework's persistence code, report it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26057: Recursive entity references found in view def {0}. Entity refs: {1}**

**Cause:** An attempt was made to create a view definition whose entity references have a cycle in it. For example, a view definition contains two entity references E and F, where E's source reference is F, and F's is E.

**Action:** Review your code that builds the view def. Make sure that entity references do not have a recursion in it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26058: Cannot define view link {0} in application module {1}. The view object {2} is in application module {3} and the view link's application module is not a child of the view object's application module.**



---

**Cause:** An attempt was made to establish a data model view link in an application module, but either the master or the detail view object is in an AM which is not the same AM as the view link's, or is not a parent of the view link's AM.

**Action:** When creating a data model VL, the VL's AM must be the same as the VO's, or must be a child (nested) AM of the VO (for both master and detail).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26059: Invalid View Link Usage "{0}". Either the source "{1}" or the destination "{2}" is not defined.**

**Cause:** The ViewLink Usage is not correctly defined.

**Action:** Specify both source and destination for the ViewLink Usage.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26060: Error while registering JDBC driver.**

**Cause:** A SQLException occurred while trying to register a JDBC driver.

**Action:** Fix the underlying SQLException.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26061: Error while opening JDBC connection.**

**Cause:** A SQLException occurred while trying to open a JDBC connection.

**Action:** Fix the underlying SQLException.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26062: Error while closing JDBC connection.**

**Cause:** A SQLException occurred while trying to close a JDBC connection.

**Action:** Fix the underlying SQLException.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26064: Error while closing JDBC statement.**

**Cause:** A SQLException occurred while trying to close a JDBC connection.

**Action:** Fix the underlying SQLException.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**JBO-26065: Error during commit.**

**Cause:** A SQLException occurred during the commit phase of this transaction.

**Action:** Fix the underlying SQLException.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26066: Error during rollback.**

**Cause:** A SQLException occurred during the rollback phase of this transaction.

**Action:** Fix the underlying SQLException.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26067: Failed to add JDBC connection to the connection pool, connection pool is full.**

**Cause:** An exception occurred while adding a JDBC connection to a pool that was already full.

**Action:** Modify the class that is using the pool to check the pool size before adding a new connection to the pool.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26068: Failed to return JDBC connection to the connection pool, connection does not belong to the pool.**

**Cause:** The user attempted to return a connection to a pool that was not responsible for managing that connection.

**Action:** Modify the class that is using the pool to ensure that the connection belongs to the pool before returning the connection to the pool.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26069: Client request was timed out while waiting for a connection to be returned to the connection pool.**

**Cause:** A client request was timed out while waiting for a connection to be returned to the pool.

**Action:** Increase the maximum pool size in order to accommodate 2x the maximum expected active request size.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26070: Column definition retrieval from JDBC failed on view object {0}.**

**Cause:** A SQLException occurred while setting up metadata JDBC statement.

---

**Action:** Fix the underlying SQLException. There might be a datatype mismatch between the attributes of the view object and columns in the SQL for it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26071: Access mode {1} is invalid. View object {0}**

**Cause:** The access mode specified in the view definition XML file is not valid.

**Action:** Check the content of the XML file for the view definition. Look for an XML element named 'AccessMode'. Make sure that the value for that element is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26080: Error while selecting entity for {0}**

**Cause:** An unexpected exception occurred while executing the SQL to fetch data for an entity instance or lock it.

**Action:** Fix the cause for the SQLException in the details of this exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26081: Error while getting datum for attribute {1} in {0}**

**Cause:** A SQLException occurred when converting data from JDBC to `oracle.jbo.domain.Struct` attributes.

**Action:** Fix the conversion errors as suggested in SQLException.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26083: Comparison operator {0} has a string code for its description, but the message bundle class cannot be found.**

**Cause:** A comparison operator was specified with string code, but the message bundle class could not be loaded. When specifying a string code for translatable operator description, the framework first checks to see if the operator specification includes a message bundle class name. If so, it attempts to find the string in that message bundle. If not, then the framework tries to find the string in the owning object's (either view object or entity object) message bundle. If both fail, this error is raised.

**Action:** Make sure that the comparison operator specification is correct in the XML file.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**JBO-26084: Invalid association definition "{0}". Association must have two AssociationEnds.**

**Cause:** The association definition in the XML file is missing either the source or destination association end. For an association XML file, two elements named AssociationEnd should be found.

**Action:** Correct the error in the XML file.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26085: Missing association name in EO-exists validator {0} of {1}.**

**Cause:** The EO-exists validator is missing the association name in its definition.

**Action:** Correct the error in the XML file.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26086: Association attributes do not match the destination EO's primary keys in EO-exists validator {0} of {1}.**

**Cause:** The EO-exists validator's source side attribute list does not match the destination EO's primary keys. For example, suppose there is a PurchaseOrder EO which includes an EO-exists validator to Customer EO. PurchaseOrder EO is using association CustToPurch to validate. In this case, the association attribute list on the PurchaseOrder side match with Customer's PK exactly (order does not matter--they must equal as sets).

**Action:** Correct the error in the XML file.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26100: An error occurred after commit was performed.**

**Cause:** An exception occurred in the afterCommit notification phase of the transaction.

**Action:** Verify the exception in the details of this exception. Fix the failing afterCommit() overridden methods in the entities or transient TransactionListener objects registered with the transaction to listen into the commit/rollback cycle.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-26101: An error occurred after posting was performed.**

**Cause:** An exception occurred in the afterPost phase of the transaction.

**Action:** Verify the exception in the details of this exception. Fix the failing afterPost() overridden methods in the entities or transient TransactionPostListener objects registered with the transaction to listen into the post cycle.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**JBO-26102: An error occurred after rollback was performed.**

**Cause:** An exception occurred in afterRollback notification phase of the transaction.

**Action:** Verify the exception in the details of this exception. Fix the failing afterRollback() overridden methods in the entities or transient TransactionListener objects registered with the transaction to listen into the commit/rollback cycle.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27001: Association attribute {2} included in {0} {1} is not updatable**

**Cause:** This association attribute is marked readonly.

**Action:** Cannot modify the value of the association attribute as it is marked readonly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27002: Entity validation with key {1} failed in entity object {0}**

**Cause:** A custom validation rule failed to validate an attribute value.

**Action:** Fix the attribute value so that it passes the custom validation rule.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27003: Validation of rows in view object {0} failed**

**Cause:** Modified or new entities in this view object failed to validate.

**Action:** Fix the failing entity values and revalidate the view object.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27004: Attribute set for {2} in entity {1} failed**

**Cause:** Attempting to modify a read-only entity-attribute.

**Action:** Do not modify a read-only attribute value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27005: Validation of rows in application module {0} failed**

**Cause:** Modified or new entities within this application module or nested application module failed to validate.

**Action:** Fix the failing entities and then revalidate this application module.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27006: Validation failed because attribute {2} is not found in {0} {1}**

**Cause:** An attribute cannot be found by the given name during validation.

**Action:** Entity metadata could be corrupt as there is an attribute which is to be validated but no definition could be found for that attribute in the metadata.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27007: Validation of a view row in view object {0} failed**

**Cause:** Attempting to validate a ViewRow failed.

**Action:** Fix the failing entities or attributes as found in the details of this exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27008: Attribute {2} in view object {1} cannot be set.**

**Cause:** An attempt was made to modify a view row attribute that is read-only.

**Action:** Modify the updatable setting of the view attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27009: Batch set of attributes in view object {1} failed**

**Cause:** Attempting to validate entities and attributes failed during validation of buffered attributes in Deferred Validation mode. (Not available in 3.x)

**Action:** Fix the failure cases.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27010: Attribute set with value {3} for {2} in {1} has invalid precision/scale**

**Cause:** For strings, the length of the string value provided for an attribute is more than the max-length this attribute expects. For Numeric values, the length of the value (in string form) is more than what the attribute expects.

**Action:** Fix the attribute value with respect to the precision and scale information for the failing attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27011: Attribute set with value {3} for {2} in {1} failed**

---

**Cause:** A validation rule for an attribute failed either due to an unexpected exception in validating the attribute with that rule, or due to failure in evaluating the NOT operation on the rule.

**Action:** Fix the attribute value so that it validates against the failing rule.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27012: Row validation method {2} failed for row with key {1} in {0}**

**Cause:** The custom method validator attached to an entity returned false, indicating a failure in the validation for that entity.

**Action:** Fix the cause for failure in the custom validation method for this attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27013: Attribute set validation method {4} failed for attribute {2} in {1}**

**Cause:** The custom method validator attached to an attribute returned false indicating a failure in validation for that attribute in the custom method.

**Action:** Fix the cause for failure in the custom validator method for this attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27014: Attribute {2} in {1} is required.**

**Cause:** The attribute value cannot be null as it has been marked mandatory.

**Action:** Provide non-null values for mandatory attributes.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27015: {0} contained entity/s still invalid**

**Cause:** In validating a master, some child entities were found that could not be validated. This occurs only in the case when there is a composition association between the master and detail entities.

**Action:** Fix the attribute values in the child entities so that they are valid when the child entities are validated by the master

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27016: Invalid attribute kind for column {0}.**

**Cause:** An unexpected attribute kind found in the definition for a view object.

**Action:** Fix the attribute kind information in the xml-metadata definition for attributes in this view object.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27017: The primary key for Entity {0} could not be determined.**

**Cause:** While loading the metadata definition for this entity, there was no attribute marked as the primary key.

**Action:** Set at least one attribute as the primary key for this entity type, so that entities of this type can be uniquely identified.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27018: Attribute set with value {3} for {2} in {1} failed because of type mismatch**

**Cause:** The type of attribute value provided as an argument to the set() method for this attribute is not an instance of the Java type that this attribute expects.

**Action:** Convert the argument to a proper Java type, such that it is an instance of the Java type that this attribute expects.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27019: The get method for attribute "{2}" in {1} cannot be resolved.**

**Cause:** An unexpected exception occurred in the getAttribute method. Getter methods should throw a subclass of JboException so that custom exception messages are thrown/shown to the caller. This exception could also be thrown if the getter is not a public Java method.

**Action:** Do not throw any exception other than subclasses of JboException from any business logic code in the getter method for an attribute. Also verify that the getter method is a public Java method.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27020: The set method for attribute "{2}" in {1} cannot be resolved.**

**Cause:** An unexpected exception occurred in the setAttribute method. Setter methods should throw a subclass of JboException so that custom exception messages are thrown/shown to the caller. This exception could also be thrown if the setter is not a public Java method.

**Action:** Do not throw any exception other than subclasses of JboException from any business logic code in the setter method for an attribute. Also verify that the setter method is a public Java method.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic



---

**JBO-27021: Failed to load custom data type value at index {0} with java object of type {1} due to {2}.**

**Cause:** An unexpected exception occurred during fetching values from a JDBC result set into an attribute for a row object. There could be conversion errors between the return type from JDBC for the attribute and its Java type.

**Action:** Verify that the JDBC-SQL type and Java type for the attribute are compatible. Fix any conversion errors or domain exceptions that are in the details of this exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27022: Failed to load value at index {0} with java object of type {1} due to {2}.**

**Cause:** An unexpected exception occurred during fetching values from a JDBC result set into an attribute for a row object. There could be conversion errors between the return type from JDBC for the attribute and its Java type.

**Action:** Verify that the JDBC-SQL type and Java type for the attribute are compatible. Fix any conversion errors or domain exceptions that are in the details of this exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27023: Failed to validate all rows in a transaction.**

**Cause:** An unexpected exception occurred during validating changes in a transaction.

**Action:** Verify the details for DeferredRowValidationException and fix those errors.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27024: Failed to validate a row with key {1} in {0}**

**Cause:** An unexpected exception occurred during validating a row.

**Action:** Verify the details for DeferredRowValidationException and fix those errors at the row level. The details can also contain DeferredAttrValidationExceptions which needs to be fixed as well.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27025: Failed to validate attribute {2} with value {3}**

**Cause:** An unexpected exception occurred during validating an attribute of a row.

**Action:** Verify the details for JboExceptions and fix those errors at the row level.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**JBO-27026: Set method threw an exception found in the details of this exception.**

**Cause:** An unexpected exception occurred during a setter method for an attribute. This exception should not be seen outside of the framework.

**Action:** Verify the details for JboExceptions and fix those errors

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27027: Missing mandatory attributes for a row with key {1} of type {0}**

**Cause:** An unexpected exception occurred during validating attributes of a row for mandatory fields.

**Action:** Verify the details for JboExceptions and fix those attributes with null values.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27028: Variable {2} in manager {1} is not updatable.**

**Cause:** An attempt was made to set the value of a variable that is not updatable.

**Action:** Change the updatable setting of the variable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27029: Key definitions in definition {1} cannot be modified after it is resolved.**

**Cause:** An attempt was made to modify the key definition after the definition is resolved (resolveDefObject()).

**Action:** It is illegal to modify key definitions after the definition is resolved. If key definitions are to be modified, it should be done before.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27030: An entity row without a primary key cannot be locked.**

**Cause:** An attempt was made to lock an entity row with key which is not the primary key.

**Action:** For locking an entity row, only the primary key can be used (and not an alternate key). Do not use a non-primary key for locking.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27031: At least one of the following attributes {2} in {1} is required.**

**Cause:** At least one of the list attributes must be not null.

---

**Action:** Provide a non-null value for one of these attributes.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27032: Session definition full name must start with {0}**

**Cause:** The specified session definition full name is invalid.

**Action:** Session definition full name must start with the package name, 'sessiondef'. Make sure that the full name starts with it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27033: Validator {0} cannot be designated transaction level because it does not implement JboTransValidatorInterface**

**Cause:** An attempt was made to set a validator to transaction level validator, but the validator does not implement oracle.jbo.rules.JboTransValidatorInterface.

**Action:** Before setting the transaction level flag, make sure the validator class implements oracle.jbo.rules.JboTransValidatorInterface.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27034: Invalid kind for attribute {0} from the corresponding superclass attribute.**

**Cause:** Attribute kind is different between an entity or view object and the corresponding superclass.

**Action:** Fix the attribute kind information in the xml-metadata definition for attributes in this entity or view object.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27035: Attribute {2} is required.**

**Cause:** The attribute value cannot be null as it has been marked mandatory.

**Action:** Provide non-null values for mandatory attributes.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27036: At least one of the following attributes {2} is required.**

**Cause:** At least one of the list attributes must be not null.

**Action:** Provide a non-null value for one of these attributes.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**JBO-27037: Please provide a value that does not begin with a wildcard character for attribute {2}.**

**Cause:** The attribute value may not begin with a wildcard character.

**Action:** Please provide a value that does not begin with a wildcard character.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27101: Attempt to access dead entity in {0}, key={1}**

**Cause:** Trying to refer to an invalid/obsolete entity. This could occur if some business logic has held on to an entity reference which was removed and the transaction has been posted or committed. It could also occur if a reference entity has been removed from the cache and any ViewRow is attempting to access it.

**Action:** Use findByPrimaryKey to find a valid entity of the desired key instead of holding on to a reference to an entity instance.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27102: Attempt to access dead view row of persistent id {0}**

**Cause:** Trying to access a ViewRow which is part of an obsolete/invalid collection. This could happen if a reference to the ViewRow is held by some business logic while the containing view object was removed.

**Action:** Find the referenced ViewRow either by re-querying or using findByKey methods to get a valid reference to the ViewRow.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27120: SQL error during query execution. Statement: {0}**

**Cause:** Failed to execute a query. This could occur when trying to execute a query for a SQLValue domain class or a Sequence domain.

**Action:** Fix the cause for the SQLException thrown by JDBC found in the details of this exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27121: SQL error during statement execution. Statement: {0}**

**Cause:** Failed to execute a SQL statement.

**Action:** Fix the cause for the SQLException thrown by JDBC found in the details of this exception.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**JBO-27122: SQL error during statement preparation. Statement: {0}**

**Cause:** Failed to prepare a JDBC PreparedStatement.

**Action:** Fix the cause for the SQLException thrown by JDBC found in the details of this exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27123: SQL error during call statement preparation. Statement: {0}**

**Cause:** Failed to prepare a JDBC CallableStatement.

**Action:** Fix the cause for the SQLException thrown by JDBC found in the details of this exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27124: SQL error during empty statement creation**

**Cause:** Failed to create a JDBC Statement object with the given set of parameters.

**Action:** Fix the cause for the SQLException thrown by JDBC found in the details of this exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27125: Cannot find matching type-map entries for all columns in a dynamic ViewObject-query**

**Cause:** Failed to find a Java type for a column-type in the given dynamic ViewObject query.

**Action:** Either provide a typemap that maps the selected columns in the query or leave out the erring column-type from the query.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27126: Long running query "{0}" has been canceled.**

**Cause:** The view object's query timeout was reached or the user requested cancellation of a long query.

**Action:** Review the query implementation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27127: The effective date operation for Entity {0} will introduce gaps or overlaps. key={1}**

---

**Cause:** Effective date constraint violation while creating or updating a row. The operation will cause gaps or overlaps in the effective date timeline

**Action:** Change the start or end effective date if it is a new row. If it is an update choose a different mode.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27128: The effective date update operation for Entity {0} failed because an existing row has the effective start date that matches the effective date. key={1}**

**Cause:** Effective date row update with UPDATE mode is disallowed because the start effective date of an existing row matches the effective date.

**Action:** Choose a different mode to update the row like correction mode.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27129: The effective date row for Entity {0} has end date less than start date, key={1}**

**Cause:** Effective end date is greater than the start date.

**Action:** Change the start or end effective date.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27130: Current mode {0} is not supported in Multiple Changes Per Day.**

**Cause:** Current mode is not supported in Multiple Changes Per Day.

**Action:** Switch to Update Change Insert mode.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27131: Current mode {0} is supported only in Multiple Changes Per Day.**

**Cause:** Current mode is not supported in Multiple Changes Per Day.

**Action:** Switch to Update Change Insert mode.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27132: Current operation cannot be performed in {0} mode because no future rows exist. key={1}**

**Cause:** Current operation cannot be performed when no future rows exist.

**Action:** Switch to Update mode.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**JBO-27133: Current operation cannot be performed in {0} mode because no previous rows exist. key={1}**

**Cause:** Current operation cannot be performed when no previous rows exist.

**Action:** Switch to a different mode or navigate to a row where previous rows exist.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27134: Current Multiple Changes Per Day operation can be performed only on first sequenced row. key={0}**

**Cause:** Current Multiple Changes Per Day operation can be performed only on first sequenced row.

**Action:** Navigate to first sequenced row.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27200: JNDI failure. Unable to lookup {0} at context {1}**

**Cause:** JNDI lookup failed. It can be caused by an incorrect data source name, particularly for the internal connection, or an internal error.

**Action:** Check the internal data source name to see if it is valid. If the error is not caused by the internal connection problem, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27201: Error suspending current transaction**

**Cause:** An error occurred while suspending a global transaction for JTA pcoll manager.

**Action:** Check the detail exception to determine the root cause of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-27202: Error resuming current transaction**

**Cause:** An error occurred while resuming a global transaction for JTA pcoll manager.

**Action:** Check the detail exception to determine the root cause of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**JBO-27203: Cannot use the default connection for persistence with global transactions.**

**Cause:** While using global transactions, an attempt was made to use the transactional data source for acquiring the internal connection.

**Action:** Explicitly specify the jdbc url that should be used for creating the internal connection by setting the oracle.jbo.common.PropertyConstants.INTERNAL\_CONNECTION\_PARAMS property

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28000: PersistManager class {0} not found**

**Cause:** The client specified a custom persistent collection through the jbo.pcoll.mgr property. However, the class specified could not be located or loaded.

**Action:** Make sure that the name specified for jbo.pcoll.mgr is for a valid class name. The class name should be fully qualified with the package name. A special keyword None represents no persistent collection manager, i.e., no spilling to disk will occur.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28001: Cannot connect to database**

**Cause:** An error occurred while attempting to get a JDBC connection for persistent collection management.

**Action:** Make sure that the database connection URL is correct. The detail to this exception will give further information on the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28002: Could not create persistence control table {0}**

**Cause:** An error occurred while creating the persistent collection control table. Normally, the control table's name is PCOLL\_CONTROL.

**Action:** Check to make sure that the connection has appropriate authority to create a table. The detail to this exception will give further information on the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28003: Could not delete row in control table for table {0}**

**Cause:** An unexpected error occurred while attempting to delete the persistent collection control row.

**Action:** Look at the details of this exception for further information on the problem and how to address it.



---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28004: Could not lock row in control table for table {0}**

**Cause:** An error occurred while trying to lock the persistent collection control row. This error is thrown in two situations: An unexpected database error occurred while attempting to lock the row. After the persistent collection manager committed changes to database, it tried to lock the control row. Between the time of commit and lock attempt, another user somehow managed to lock the row and not release it within a set time. In this case, the detail will be null.

**Action:** In the first case, see the details of this exception for further information on the database problem. In the second case, make sure that no other user locks the control rows outside the Business Components framework.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28005: Could not update row in control table for table {0}**

**Cause:** An unexpected error occurred while attempting to update the persistent collection control row.

**Action:** Look at the details of this exception for further information on the problem and how to address it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28006: Could not create persistence table {0}**

**Cause:** An error occurred while attempting to create a database table to store persistent collection material.

**Action:** Look at the details of this exception for further information on the problem and how to address it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28007: Could not commit while working on persistence table {0}**

**Cause:** An unexpected error occurred while attempting to commit persistent collection changes

**Action:** Look at the details of this exception for further information on the problem and how to address it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28008: Could not create an index {0} on table {1} for persistent collection**

---

**Cause:** An error occurred while attempting to create an index on a database table that stores persistent collection material.

**Action:** Look at the details of this exception for further information on the problem and how to address it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28009: Error while getting current time from database**

**Cause:** An unexpected error occurred while attempting to get the system date from the database. For the Oracle persistent manager, the SQL statement used for this would be 'select sysdate from dual'.

**Action:** Look at the details of this exception for further information on the problem and how to address it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28010: Error while getting next sequence value for {0} from database**

**Cause:** An error occurred while attempting to get the next value of a database sequence.

**Action:** Make sure that the sequence object exists in the database. Also look at the details of this exception for further information on the problem and how to address it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28011: Error while querying for the next id from column {1} of table {0}, collection id {2}**

**Cause:** An error occurred while attempting to query for the next id from a pers coll table.

**Action:** Look at the details of this exception for further information on the problem and how to address it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28012: Could not add key column {0} to table {1}**

**Cause:** An error occurred while attempting to create add a key column on a database table that stores persistent collection material.

**Action:** Look at the details of this exception for further information on the problem and how to address it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**JBO-28013: Could not create key info table {0}**

**Cause:** An error occurred while attempting to create a database table to store key info for persistent collection material.

**Action:** Look at the details of this exception for further information on the problem and how to address it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28020: Passivation error on collection {0}, collection id {1}, persistent id {2}**

**Cause:** An unexpected error occurred while passivating objects into the persistent store. An exception might have been thrown during serialization.

**Action:** Look at the details of this exception for further information on the problem and how to address it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28021: Activation error on collection {0}, collection id {1}, persistent id {2}**

**Cause:** An unexpected error occurred while activating objects from the persistent store. An exception might have been thrown during deserialization.

**Action:** Look at the details of this exception for further information on the problem and how to address it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28030: Could not insert row into table {0}, collection id {1}, persistent id {2}**

**Cause:** An unexpected error occurred while inserting a passivation row into the persistent store table.

**Action:** Look at the details of this exception for further information on the problem and how to address it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28031: Could not update row into table {0}, collection id {1}, persistent id {2}**

**Cause:** An unexpected error occurred while updating a passivation row in the persistent store table.

**Action:** Look at the details of this exception for further information on the problem and how to address it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28032: Could not delete row from table {0}, collection id {1}, persistent id {2}**

---

**Cause:** An unexpected error occurred while deleting a passivation row from the persistent store table.

**Action:** Look at the details of this exception for further information on the problem and how to address it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28033: Could not retrieve row from table {0}, collection id {1}, persistent id {2}**

**Cause:** An unexpected error occurred while retrieving a passivation row from the persistent store table.

**Action:** Look at the details of this exception for further information on the problem and how to address it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28034: Retrieval by id not supported for collection {0}, collection id {1}. Call enableAccessById()**

**Cause:** The client attempted to retrieve a row in a persistent collection by an id, but the by-id access is not enabled on the persistent collection.

**Action:** Enable by-id access by calling PCollection.enableIdAccess.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28035: Persistent id {1} is invalid for a collection {0}, collection id {1}. It should be > 0**

**Cause:** The client attempted to retrieve a row by an id, but the id value is invalid. The id must be greater than 0.

**Action:** Give a valid id.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28036: Object of id {2} is already active in its parent {3} in a persistent collection {0}, collection id {1}**

**Cause:** While attempting to activate an object of a given id, an internal integrity problem was found. In particular, a node which was thought to be passivated was found to be active.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**JBO-28037: Object of id {2} not found in its parent {3} in a persistent collection {0}, collection id {1}**

**Cause:** While attempting to activate an object of a given id, an internal integrity problem was found. In particular, a child node/element expected to be found in a node is missing.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28038: Could not delete all rows for collection of id {1} from table {0}**

**Cause:** An unexpected error occurred while deleting all passivation rows from the persistent store table.

**Action:** Look at the details of this exception for further information on the problem and how to address it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28039: Root node for collection {0} is invalid, collection id {1}, persistent id {2}**

**Cause:** While attempting to activate an object of a given id, an internal integrity problem was found. In particular, the root node of the persistent collection is no good. It is either (1) `null`, (2) has younger or older sibling, or (3) has a parent node. None of these should apply to the root node.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28040: Could not retrieve ids of rows whose key id is {1} and hash is {2} from table {0}**

**Cause:** An unexpected error occurred while retrieving an array of persistent ids of rows from the persistent store table of given key hash code at the given key index.

**Action:** Look at the details of this exception for further information on the problem and how to address it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28041: Update found multiple rows or no matching row. Persistence table {0}, collection id {1}, persistent id {2}**

**Cause:** The system tried to update a row in the persistence store table, but it found either no row or more than one matching row.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**JBO-28100: The resource pool, {0}, failed to create a pooled resource instance.**

**Cause:** Either the JDBC connection pool or the application pool were unable to create a new pooled JDBC connection or application module.

**Action:** If the exception details indicate that an exception occurred while creating a JDBC connection then check the JDBC connection description to ensure that it references a valid, live database instance. If the exception details indicate that an exception occurred while creating an application module then check the application module configuration to ensure that it references a valid, live application server and application application module class.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28101: An application attempted to set a pooled resource that might be in use as available.**

**Cause:** The application attempted to mark a pooled resource which has already been available in the resource pool as available.

**Action:** Remove the application logic that invokes {@link oracle.jbo.pool.ResourcePool#setAvailable(Object)}, or move the application logic such that it occurs only once before the resource is made available.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28102: A request was timed out while waiting for a resource to be returned to the resource pool, {0}.**

**Cause:** A client request timed out while waiting for a resource to be returned to the resource pool.

**Action:** Increase the maximum resource pool size in order to accommodate the maximum expected active request size. If the exception details indicate that the exception was thrown while waiting for an application module in the application pool then the maximum pool size can be increased with the property, `jbo.ampool.maxpoolsize`. If the exception details indicate that the exception was thrown while waiting for a JDBC connection in the JDBC connection pool then the maximum pool size can be increased with the property, `jbo.maxpoolsize`.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28103: A pool operation was specified for a pooled resource that does not belong to the resource pool.**

**Cause:** A pool request was made for a resource that does not belong to the pool.

**Action:** Ensure that the pool request is accessing the same pool instance that was used to acquire the resource instance.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**JBO-28200: Validation threshold limit reached. Invalid Entities still in cache**

**Cause:** Invalid entities still found in the validation list of the transaction after attempting to validate all invalid entities for the `VALIDATION_THRESHOLD` 10 times (by default).

**Action:** Fix any logic that invalidates entity instances in the validation cycle (perhaps in overridden `validateEntity()` methods) such that all entities are valid before the `VALIDATION_THRESHOLD` limit is reached.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28201: Post threshold limit reached. Some entities yet to be posted.**

**Cause:** There are invalid entities or entities in the post list of the transaction after trying to post all changes for the `POST_THRESHOLD` 10 times (by default).

**Action:** Fix any logic that places entities in the transaction's list of entities to be validated or posted in the post cycle, such that all entities get posted before the `POST_THRESHOLD` is reached.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28202: Entities invalidated in `beforeCommit()`. Need to revalidate and post.**

**Cause:** Invalid entity instances found in the transaction in the `beforeCommit` phase.

**Action:** Fix any business logic that invalidates entity instances in `postChanges()` such that there are no more invalid entities after all changes are posted during the commit cycle.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28203: The updated row cannot be refreshed because its key values are unset or modified by database triggers.**

**Cause:** The row could not be refreshed after update because the value of its primary or unique key was not set or unknown.

**Action:** Ensure values are set for at least one primary or unique key that can be used to fetch the row that is being updated. If that is not possible, use a custom `SQLBuilder` with `doRefreshSQL()` defined to refresh the row.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-28204: Too many objects match the alternate key {0} for entity {1}, key {2}.**

**Cause:** Attempting to add a new entity to the cache with alternate key that is same as an existing entity. This exception is thrown when uniquing a newly fetched/created entity with the cached set of entities.

---

**Action:** Fix the named alternative value of the row. Or, the alternate key definition might have to be augmented with additional attributes.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-29000: Unexpected exception caught: {0}, msg={1}**

**Cause:** If an unexpected exception occurs during a framework operation, this exception is thrown, with the unexpected exception included in the details of this exception.

**Action:** Fix the cause for the exception in the details for this JboException.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-29001: Type mismatch. Expected {0}. Actual {0}**

**Cause:** During creation of application module in the EJB deployment mode, the object returned by the EJB home is not an instance of `oracle.jbo.common.remote.ejb.RemoteApplicationModule`.

**Action:** This usually means that the wrong EJB home is being invoked to create a remote application module. Fix it to point to the correct home.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-29004: Server-side configuration for creating the pool not specified.**

**Cause:** A configuration was not specified for the remote `ApplicationModule` usage.

**Action:** Use the design time to specify a configuration for the remote `ApplicationModule` usage.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JBO-29100: Attribute {0} is not selected**

**Cause:** Def object is not selected. An attempt was made to access a nonselected def object.

**Action:** This particular operation is disallowed on a nonselected def object. Avoid this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-29101: Attribute {0} is not selected in {1}, operation: {2}**

**Cause:** Def object is not selected. An attempt was made to access a nonselected def object in the specified container object.



---

**Action:** This particular operation is disallowed on a nonselected def object. Avoid this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-29102: The S\_ROW\_ID table is unable to generate a new row ID.**

**Cause:** No more row IDs were available in the database's configured row ID range.

**Action:** Contact the system administrator. The row ID table in the database needs to be refreshed with a new row ID range.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-29103: Internal error: {0} cannot be null**

**Cause:** This is an internal exception. The specified argument cannot be NULL.

**Action:** Contact the System Administrator. The specified argument cannot be NULL.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-29104: Unable to create RowId generator application Module. Add the RowIdAM application module in the AM Usage for the current application.**

**Cause:** The RowIdAM application module is not a shared application module of the current application module.

**Action:** Add the RowIdAM application module in the AM Usage for the current application or contact the System Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-29105: Attributes referenced in view criteria {0}.{1} with property AppliedIfJoinSatisfied do not map to the same entity usage.**

**Cause:** The attributes used in the View Criteria do not map to the same entity usage.

**Action:** Make sure the attributes used in the View Criteria all map to the same entity usage if AppliedIfJoinSatisfied is set to true.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-29106: Attributes referenced in view criteria {0}.{1} with property AppliedIfJoinSatisfied map to the primary entity usage.**

---

**Cause:** The attributes used in the View Criteria cannot map to the primary entity usage.

**Action:** Make sure the attributes used in the View Criteria all map to a non-primary entity usage if `AppliedIfJoinSatisfied` is set to true.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-29107: View criteria {0}.{1} with property `AppliedIfJoinSatisfied` must be used with an entity-based view object.**

**Cause:** The view criteria cannot be used with a non-entity based view object

**Action:** The view criteria can only be used with an entity-based view object if `AppliedIfJoinSatisfied` is set to true.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-29108: The value specified for the property {0} in the `rowidam.properties` file is invalid.**

**Cause:** Invalid value specified in the `rowidam.properties` file. The values cannot be  $\leq 0$ .

**Action:** Update the properties to specify accepted values. The property values should be  $> 0$ .

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-29109: The value specified for column {0} in the `S_ROW_ID` table is invalid.**

**Cause:** One or more column values in `S_ROW_ID` table are invalid.

**Action:** Update the `S_ROW_ID` table with accepted values. The column values should be greater than zero.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-29110: Unable to cast the class type specified for `RowId` comparison to `GeneratorSequenceImpl` or `BigDecimal`.**

**Cause:** Invalid value specified for comparison.

**Action:** The value to be compared with the `RowId` should be of type `BigDecimal` or any other type that can be converted to `BigDecimal`.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-29111: View criteria {0} is a union VC and contains an invalid element of type {1} at index {2}**

---

**Cause:** This view criteria is marked for union query but contains a view criteria element which is neither a ViewCriteria nor ViewCriteriaUsage.

**Action:** A union view criteria can only contain ViewCriteria or ViewCriteriaUsage. Correct the view criteria definition.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-29112: The time zone "{0}" defined in adf-config.xml or**

**TimeZone.getDefault().getID() does not exist in your Oracle database table V\$TIMEZONE\_NAMES. Please set an available time zone in your TZ environment variable or user.timezone Java system property.**

**Cause:** The time zone could not be set as the value defined in adf-config.xml or TimeZone.getDefault().getID() does not exist in Oracle database table V\$TIMEZONE\_NAMES.

**Action:** Set an existing time zone defined in your Oracle database table V\$TIMEZONE\_NAMES in TZ environment variable or user.timezone Java system property.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-29113: Encountered database recoverable exception. Please retry your request.**

**Cause:** Encountered database recoverable exception.

**Action:** Retry your request after performing some recovery steps such as acquiring a new connection.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-30000: Application module pool {0} has already been created.**

**Cause:** The application attempted to create an application pool with the same name as an existing application pool.

**Action:** Correct the application logic that is creating an application pool. Validate that a pool with the given name has not already been registered with the pool manager.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-30001: Cookie {0} is invalid.**

**Cause:** Deprecated.

**Action:** N/A

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**JBO-30002: The pool signature for the cookie is invalid.**

**Cause:** Deprecated.

**Action:** N/A

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-30003: Application pool {0} fails to check out an application module due to the following exception:**

**Cause:** The pool failed to create an application module instance during checkout. Typically this exception occurs when the pool has been configured with an invalid application module name, EJB server, etc. or when an invalid JDBC username, password, URL, or datasource name has been specified.

**Action:** See the exception details for more information regarding the failure. Correct the application's configuration properties appropriately.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-30004: An application module that was not checked out was checked into the pool, {0}**

**Cause:** The application attempted to check in an application module that was not checked out from the pool.

**Action:** Remove redundant `releaseApplicationModule()` invocations from the application logic.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-30005: A pool operation was specified for an application module instance that was not created by that pool.**

**Cause:** The application attempted to invoke an application pool method with an application module that was not created by that application pool instance.

**Action:** Correct the application logic. Use the session cookie that was used to acquire the application module instance to acquire a reference to the application pool that created that application module instance.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-30006: The cookie for session {0} and application {1} is not a valid handle for application pool, {2}. The cookie cannot be used to access this pool instance.**

**Cause:** The application attempted to access the application pool with a session cookie that is not registered with that application pool.

**Action:** Correct the application logic. The application should not reference the application pool directly. Use the session cookie interface for all application pool interaction.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-30009: A thread attempted to set as 'available' an application module that could already be in use. An application module's availability cannot be changed from outside of the pool once it has been made available.**

**Cause:** The application attempted to modify the availability status of an application module that is already in active pool use.

**Action:** Remove the application logic that is updating the application module availability status.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-30010: The cookie for session {0} and application {1} cannot be replicated with an active cookie instance.**

**Cause:** The web server attempted to replicate a session cookie with an existing, active cookie.

**Action:** Internal exception. Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-30011: A null session cookie application id, session id, or application pool reference ({0}, {1}, {2}) was specified during cookie construction. The cookie could not be constructed.**

**Cause:** The application attempted to create a session cookie with an invalid set of cookie parameters.

**Action:** Correct the application logic that creates the session cookie. Verify that the cookie session id, application id, and application pool reference are all not null.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-30012: A cookie for session {0} and application {1} has already been registered with application pool {2}. The cookie must be removed first.**

**Cause:** The application attempted to create a session cookie in an application pool that already contains that session cookie.

**Action:** Correct the application logic that creates the session cookie. Remove the existing session cookie before creating a new one in that pool.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-30013: The cookie environment for session {0} and application {1} cannot be reset after the cookie has become active.**

---

**Cause:** The application attempted to change the session cookie environment after the session cookie became active.

**Action:** Correct the application logic that sets the session cookie environment. Move all logic that changes the session cookie such that it occurs before the session cookie becomes active. A session cookie is active after it is first used to acquire an application module.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JBO-30014: The cookie for session {0} and application {1} cannot be removed from the application pool while it has an application module checked out.**

**Cause:** Correct the application logic that sets the session cookie environment. Move all logic that changes the session cookie such that it occurs before the session cookie becomes active. A session cookie is active after it is first used to acquire an application module.

**Action:** Correct the application logic that removes the session cookie from the application pool. Be sure to invoke `SessionCookie.releaseApplicationModule()` before invoking `ApplicationPool.removeCookie(SessionCookie)`.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-30015: The cookie for session {0} and application {1} cannot be serialized while in use.**

**Cause:** The application attempted to serialize a session cookie while that cookie had an application module instance checked out or which the cookie was locked by a client request thread.

**Action:** Correct the serialization logic such that the session cookie is serialized after the session cookie application module has been released to the application pool and after all client requests have released their cookie locks.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-30016: The request thread for session {0} and application {1} was timed out while waiting for an available application module in the pool, {2}.**

**Cause:** The application request thread timed out while waiting for an available application module instance in the pool.

**Action:** Prevent wait timeouts by increasing the maximum pool size.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-30017: The cookie for session {0} and application {1} cannot be reset while an ApplicationModule is reserved.**

**Cause:** `ApplicationModuleRef.resetState()` was invoked while the `ApplicationModuleRef` was referencing a reserved `ApplicationModule` instance.

---

**Action:** Release the ApplicationModule with ApplicationModuleRef.releaseApplicationModule(true, boolean) before invoking resetState.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-30018: The cookie configuration does not match the specified configuration. applicationId: {0}, sessionId: {1}, cookieConfig: {2}, specifiedConfig: {3}.**

**Cause:** oracle.jbo.http.HttpContainer.findSessionCookie was invoked with a configName which was different than the configuration that was used to create the specified SessionCookie.

**Action:** Use a distinct applicationId to identify the cookie for each distinct Configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JBO-30019: An unavailable cookie state is detected while attempting to use a cookie from application {0}, session {1}.**

**Cause:** An application pool method was invoked for a cookie that was not currently available. A cookie can be in an unavailable state if another thread is currently updating the cookie. For example, consider the following scenario: 1. cookie 1 releases an ApplicationModule with the managed state option 2. cookie 2 targets that ApplicationModule for recycling 3. Before cookie 2 has passivated the ApplicationModule state for cookie 1, cookie 1 requests another ApplicationModule In this instance the ApplicationPool could throw an unavailable exception. Note that most of the occurrences of this exception should be handled by the pooling framework.

**Action:** Report the exception to Oracle Support Services. Attempt the invalid operation again.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-30020: An invalid SessionCookie release mode was specified. applicationId: {0}, sessionId: {1}.**

**Cause:** oracle.jbo.common.ampool.SessionCookie.releaseApplicationModule was invoked with an unsupported releaseMode.

**Action:** Invoke releaseApplicationModule(int) with a valid releaseMode attribute. Valid releaseModes include: SessionCookie.SHARED\_MANAGED\_RELEASE\_MODE SessionCookie.SHARED\_UNMANAGED\_RELEASE\_MODE SessionCookie.RESERVED\_MANAGED\_RELEASE\_MODE SessionCookie.RESERVED\_UNMANAGED\_RELEASE\_MODE

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**JBO-33000: Configuration file {0} is not found.**

**Cause:** The requested configuration file could not be found.

**Action:** Provide a correct name for the configuration file. Or, make sure that the named configuration file can be found in one of the accessible paths.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-33001: Configuration file {0} is not found in the classpath.**

**Cause:** The requested configuration file could not be found in the class paths.

**Action:** Make sure that the named configuration file can be located in one of the class paths.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-33003: Connection name {0} is not defined.**

**Cause:** The specified connection could not be found. Or an error occurred during processing of the specified connection.

**Action:** Make sure that the connection name is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-33004: Configuration file cannot be parsed.**

**Cause:** An error occurred while parsing configuration file.

**Action:** Check to make sure that the configuration file is a valid XML file. See the detail exception for further information.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-33005: Configuration {0} is not found.**

**Cause:** The named configuration parameter was not found in the configuration.

**Action:** The system expects to find the named configuration parameter, but could not. Check the configuration content to make sure that it contains the named configuration parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JBO-33006: Data source {0} is not supported.**

**Cause:** This error message indicates that the underlying SQLBuilder does not support datasource.

**Action:** For this SQLBuilder, do not use datasource.



---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-33007: Data source {0} is not found.**

**Cause:** The specified datasource could not be found.

**Action:** Make sure that the datasource name is correct. See the detail exception for further info.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-33020: Current time is not available from SQL statement "{0}".**

**Cause:** An error occurred while getting the current time from the database.

**Action:** If there is a detail exception, it will give further information about what went wrong. If no detail exception was provided, that means the SQL statement to get the current time returned no result (no row). Check the SQL statement for correctness.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-33021: User {0} cannot be authenticated.**

**Cause:** An error occurred while authenticating the user.

**Action:** Make sure that the user authentication information is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JBO-33022: Thread {0} has timed out while waiting to acquire a lock.**

**Cause:** A thread timed out while waiting for a resource that was protected with an 'oracle.jbo.common.Lock'.

**Action:** Verify that all threads that have acquired a lock have properly released that lock in a 'finally' code block.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-33023: Thread {0} is attempting to release a session cookie lock that it did not acquire.**

**Cause:** The application attempted to release a {@link oracle.jbo.common.Lock} that it did not hold.

**Action:** Internal exception. Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**JBO-33024: Graph nodes cannot be sorted due to a cycle in the graph.**

**Cause:** A cycle was detected in the dependency graph.

**Action:** Check the edges in the graph and remove any cycles.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-33025: Failed to release application module {0}. Cookie handle not found.**

**Cause:** Failed to release application module due to missing cookie handle.

**Action:** Invoke the correct, counterpart releaseAM method.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-33026: Value must be between {MinVal} and {MaxVal}**

**Cause:** Input values failed the range validator test.

**Action:** Provide values that are within the range validator paramters.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-33027: Value must be greater than {MinVal}**

**Cause:** Input values failed the minimum validator test.

**Action:** Provide values that are greater than the minimum.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-33028: Value must be less than {MaxVal}**

**Cause:** Input values failed the maximum validator test.

**Action:** Provide values that are less than the maximum.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-33029: Value must have exactly {MinLength} characters**

**Cause:** Input values must be longer than minimum length.

**Action:** Provide values that are longer than the minimum length.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-33030: Value can have at most {MaxLength} characters**

---

**Cause:** Input values exceeded maximum length length.

**Action:** Provide values that are less than or equal to maximum length.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-33031: Value must have at least {MinLength} and at most {MaxLength} characters**

**Cause:** Value must have at least (minLen) and at most (maxLen) characters.

**Action:** Provide values that are between minimum and maximum length.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-33032: Value must have exactly {MaxLength} characters**

**Cause:** alue must be exactly (maxLen) characters.

**Action:** Provide values that is exactly the maximum length.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-34000: Definition class name missing in XML file of type {0}**

**Cause:** Name of the definition Java class missing in the JClient XML file.

**Action:** Every metaobject in JClient must have name of the definition object's Java class in the XML file. Correct the error by regenerating XML file in the design time.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-34001: Iterator binding {0} is not of the expected class {1}**

**Cause:** The iterator binding is of the wrong Java class. Some controls expect to work with a JUIterRowBinding, while others with JUIterRangeBinding. This error indicates that the supplied iterator binding is not of the expected class.

**Action:** If the error is caused by some client code that supplies an iterator binding, correct the code to supply an iterator binding of the correct class. If the error is caused by framework code, contact Oracle Support Services with the stack trace.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-34002: The application obj has already been set for form binding {0}. Cannot do it again**

**Cause:** The form binding has already been registered with an application (JUApplication) object. It is illegal to try to set the form binding's application object again.

---

**Action:** This error typically means a program error. Contact Oracle Support Services with the stack trace.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-34003: No iterators bound with the given name :{0}**

**Cause:** No iterator binding found with the given name.

**Action:** Fix the iterator binding name before attempting to change the iterator associated with it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-34004: No matching row found for entered or selected item in the LOV iterator for a list-binding.**

**Cause:** No matching row found for a selected value in a List binding.

**Action:** Enter/Select a valid item from the list so that the matching row in the LOV iterator can be found.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-34005: Exceptions occurred in synchronizing updates from this application. Click Details to see the complete list.**

**Cause:** Exceptions occurred in synchronizing data from the client Application into the Business Components tier.

**Action:** Fix the exceptions displayed in the details list and then reapply the changes.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-34006: Method that creates the iterator for this object returns null.**

**Cause:** Collection to which this iterator is bound returns null.

**Action:** Fix the return value so that a valid collection is available for this iterator to bind to.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-34007: A value is not passed for mandatory parameter {0}.**

**Cause:** Mandatory Parameter was not set by the calling code either programmatically or by overriding it in a nested container usecase.

**Action:** Set the mandatory parameter value

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-34008: Final parameter {0} cannot be modified.**

**Cause:** Mandatory Parameter was not set by the calling code either programmatically or by overriding it in a nested container usecase.

**Action:** Set the mandatory parameter value

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-34009: ListBinding definition :{0} not found.**

**Cause:** Server side ListBinding could not be found with the given usage name.

**Action:** Fix the server side ListBinding usage name in List binding metadata

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-34010: The "{0}" descriptor appears in the application classpath more than once:**

- {1} - {2}

**Cause:** The cpx classpath name has already been found at a different source in the classpath. It is illegal to have the same relative cpx name in the classpath more than once.

**Action:** Refactor one of the indicated URLs in the message so it appears under a different relative package in the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-34011: Validator expression {0} did not result in a valid object for bindingContainer:{1}**

**Cause:** Expression for custom validator does not resolve into a valid object that as a public method of name validateBindingContainer and that takes the bindingContainer as the only parameter.

**Action:** Provide a different expression or fix the expression so that an object whose class has a method with following signature: public validateBindingContainer(DCBindingContainer ctr)

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-34012: Attempting to register a Swing binding factory when Faces version is already installed.**

**Cause:** Faces binding factory is already installed for ADF Model bindings. Attempt to install a Swing version will break the application due to binding class incompatibilities.

---

**Action:** Remove or replace references to juimodel in namespace attributes, in pagedef xml files in the application with:  
<http://xmlns.oracle.com/adfm/uimodel>.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-34013: Enter a non empty string and a string not equal to '%' in the list:{0} to filter the list of values.**

**Cause:** Empty string or % was entered to filter list datasource for a list binding.

**Action:** Enter any other string to filter by in the list component bound to this list binding.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-36000: An unexpected expression token is found.**

**Cause:** Unexpected token found.

**Action:** Found an unexpected expression token. Make sure that the words are spelled correctly and that the expression makes sense.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-36001: Mismatching parentheses are found.**

**Cause:** Mismatching parentheses.

**Action:** Examine the expression and ensure that open parentheses match up with closing parentheses.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-36002: The method call specification is invalid. "," or ")" is expected.**

**Cause:** Invalid method call. After a method parameter, ',' or ')' is expected, but neither was found.

**Action:** Examine the expression and correct method invocation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-36003: An expression token is not found.**

**Cause:** Expecting a token. The expression string was terminated unexpectedly.

**Action:** Examine the expression and ensure that the expression does not end unexpectedly.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**JBO-36004: Mismatching square brackets are found. An invalid array index is specified.**

**Cause:** Mismatching square brackets.

**Action:** Examine the expression and ensure that open square brackets (for array index) match up with closing brackets.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-36005: Variable {0} is not found.**

**Cause:** Variable not found.

**Action:** Examine the expression and ensure that the variable name is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-36006: cannot convert {0} into {1}**

**Cause:** Cannot convert data.

**Action:** Cannot convert data from one class to another. Examine the expression and ensure that the data assignment does not cause incompatible conversion of data.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-36007: Binary operation {0} is invalid for strings.**

**Cause:** An attempt was made to invoke an invalid binary operation on two strings.

**Action:** Examine the operation ID and correct the expression so that the invalid binary operation is not attempted on strings. The expression runtime only recognizes addition as a valid binary operation between two strings.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-36008: The AND separator for a BETWEEN operator cannot be found. Token {0} is found instead.**

**Cause:** A BETWEEN operator was found but no AND for the two comparison expressions.

**Action:** Take a look at the expression string. The correct syntax for BETWEEN is 'testVal BETWEEN value1 AND value2'. The expression parser could not find the AND keyword. Correct the expression.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**JBO-55001: A value of type {1} cannot be set to a value of type {0}.**

**Cause:** Unexpected type was provided to Variant utility.

**Action:** Provide an expected type as reported in the exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-55002: Variant type {0} is invalid.**

**Cause:** The data-type passed to the Variant utility from a Validation rule is invalid. This could be due to a corrupt XML-metadata definition in the component's XML file.

**Action:** Fix the component XML for the offending validation rule.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-55003: Variant name {0} is invalid.**

**Cause:** The name of the variant type passed to the Variant utility from a Validation rule is invalid. This could be due to a corrupt XML meta data definition in the component's XML file.

**Action:** Fix the component XML for the offending validation rule.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-56001: Row value is missing for data object {0}.**

**Cause:** The Row Value for a SDOValueStore is null.

**Action:** Should not use SDOValueStore with a NULL row value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-56002: Operation {0} on object {1} is not supported.**

**Cause:** An attempt was made to invoke an invalid service operation.

**Action:** Ensure that this service operation is defined at design time.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-56003: Nonpersistent attribute {0} cannot be used in a database mode view criteria.**

**Cause:** A nonpersistent attribute is used for DB ViewCriteriaItem.

**Action:** Make sure the attribute is persistent.



---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-56004: Non-ViewLink accessor attribute {0} cannot be used for a view criteria item that has nested view criteria.**

**Cause:** A non-ViewLink accessor is used for DB ViewCriteriaItem that has nested ViewCriteria.

**Action:** Make sure the attribute is a ViewLink accessor.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-56005: SDO type is not found for ViewObject {0} with namespace {1} and name {2}.**

**Cause:** SDO Type is not found for a ViewObject.

**Action:** Make sure the viewobject is SDO enabled.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-56101: Nonpersistent attribute {0} cannot be sorted upon.**

**Cause:** A nonpersistent attribute is used for DB SortCriteria.

**Action:** Make sure the attribute is persistent.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-56102: Dependencies specified for view attribute {0} conflict with dependencies specified on the underlying entity attribute.**

**Cause:** View attribute dependencies conflict with the entity attribute dependencies.

**Action:** Ensure that the dependencies are not specified on both the view and entity attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JBO-56103: View object {0} is not prepared.**

**Cause:** This is the exception that gets thrown by ViewObjectImpl when attempting an operation on a declarative view object on which prepareVOForQuery has not been called, such as findByAltKey (bug 7455860) or createAndInitRow (bug 7504211).

**Action:** Call ViewObjectImpl.prepareVOForQuery before calling findByAltKey or createAndInitRow for the first time.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**JBO-80000: Connection is already open.**

**Cause:** An open operation was attempted on a URL connection that is already open and in a active state.

**Action:** Ensure that a close operation has been called before invoking the open operation on the connection.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**JBO-80001: Connection is not open.**

**Cause:** An interaction with the URL was attempted without opening the connection.

**Action:** Ensure that the connection has been opened and is active before starting an interaction with the URL.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**JBO-80002: Connection description cannot be created.**

**Cause:** There was an internal error creating the metadata fragment for the URLConnection.

**Action:** Verify if the details necessary to create a new URL connection are provided.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**JBO-80003: Operation is invalid. Connection is already released to the pool.**

**Cause:** An operation was attempted on a connection that had already been released to the pool.

**Action:** Obtain a new active reference to the connection from the connections context.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**JBO-80004: Authentication provider "{0}" cannot be initialized.**

**Cause:** Either the metadata describing the authentication provider was corrupted or the class registered in the metadata for the authentication could not be loaded.

**Action:** Ensure that the class is available in the class path of the application. Contact Oracle Support Services if the corrupt metadata cannot be recovered.

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Other

**JBO-80005: The connection cannot be created. Connection metadata is invalid.**

**Cause:** The connection metadata in the repository has been corrupted possibly due to an external edit.

**Action:** Contact Oracle Support Services to recover the corrupted metadata.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**JBO-80006: The connection instance cannot be created. Resource endpoint is not provided.**

**Cause:** A URLConnection could not be created as the URI / URL to the resource endpoint was not supplied.

**Action:** Provide a valid URL / URI to create the connection.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**JBO-80007: The connection fails to open. Resource endpoint "{0}" does not exist.**

**Cause:** The URL resource could not be accessed after the connection was created. If the connection describes an HTTP URL resource outside a firewall, the proxy settings might not have been correctly configured to access the URL.

**Action:** Ensure that the URL is active and can be accessed. If the connection describes an HTTP URL outside a firewall, verify that the correct proxy settings are configured.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**JBO-80008: Proxy is not supported for file connection protocol.**

**Cause:** An attempt was made to configure proxy information for a file connection protocol.

**Action:** Proxy configuration is not supported for a file connection protocol. Remove any proxy configuration done for this connection.

**Level:** 1

**Type:** ERROR

**Impact:** Other



---

## JPS-00001 to JPS-90641

**JPS-00001: The method {0} is not supported.**

**Cause:** An unsupported method was used.

**Action:** This operation is not supported. It cannot be used.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**JPS-00003: The HTTP response callback is null.**

**Cause:** HTTP response callback was null.

**Action:** Check the log files and provide a valid HTTP response callback.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**JPS-00004: The HTTP response is null.**

**Cause:** HTTP response was null.

**Action:** Check the log files and provide a valid HTTP response.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**JPS-00005: HTTP request callback is null.**

**Cause:** HTTP request callback was null.

**Action:** Check the log files and provide a valid HTTP request callback.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**JPS-00006: The HTTP request is null.**

**Cause:** HTTP request was null.

**Action:** Check the log files and provide a valid HTTP request.

**Level:** 1

---

**Type:** ERROR

**Impact:** Session

**JPS-00008: The application ID {0} is invalid.**

**Cause:** Application ID was NULL.

**Action:** Provide a valid application ID.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**JPS-00009: The subject is read-only, and it cannot be modified.**

**Cause:** Attempted to modify a read-only subject.

**Action:** A read-only subject cannot be modified.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-00011: The service instance {0} already exists.**

**Cause:** The named service instance was already in use.

**Action:** Use a different name for this service instance.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00012: The service instance {0} is missing.**

**Cause:** The service instance with the name {0} was not found.

**Action:** Ensure the service instance name is present in the file jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00013: The login module {0} already exists.**

**Cause:** The login module with the name {0} was already present.

**Action:** Ensure the login module name is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00014: The login module with {0} is missing.**

**Cause:** The login module with the name {0} did not exist.

**Action:** Ensure the login module name is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**JPS-00015: All available service instance names are already in use.**

**Cause:** All service instance names were in use.

**Action:** Remove unwanted service instances from jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00016: All available service provider names are already in use.**

**Cause:** All service provider names were in use.

**Action:** Remove unwanted service providers form jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00017: The LDAP type is invalid.**

**Cause:** An invalid LDAP type was specified.

**Action:** Provide a valid LDAP type. Valid types are XML, OID, ACTIVE\_DIRECTORY, IPLANET and OVD. See the documentation for details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00018: The keystore path {0} is null or invalid.**

**Cause:** Keystore path was null.

**Action:** Provide a valid keystore path.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00019: The key type {0} is not supported.**

**Cause:** Invalid key type was provided.

**Action:** Provide a valid key type.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00020: LDAP URL {0} is null or invalid.**

**Cause:** Invalid or null LDAP URL was provided.

**Action:** Provide a valid LDAP URL.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00021: An Object named {0} does not exist.**

---

**Cause:** Object with the name {0} did not exist.

**Action:** Verify that the object name is valid and exists.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00022: Callback handler missing for this login module request.**

**Cause:** The callback handler was null.

**Action:** Provide an appropriate callback handler to invoke this login module.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-00023: The callback used for this operation has no HTTP request value.**

**Cause:** The callback did not have a request method.

**Action:** Verify that the callback is initialized with the correct HTTP request value.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-00024: The callback used for this operation has no digest response object value.**

**Cause:** The callback did not have any digest response object.

**Action:** Verify that the callback is initialized with the correct digest response value.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-00025: The {0} subscriber {1} from the HTTP header is different from the subscriber configured by the identity store as {2}.**

**Cause:** Found a subscriber mismatch.

**Action:** Check the identity store subscriber configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00026: The value {0} is invalid for the application {1}.**

**Cause:** An invalid value was provided for this application.

**Action:** Provide the correct value for the application.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-00027: internal error {0}**



---

**Cause:** Internal system error was found.

**Action:** See the log files or contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-00028: The property runas.mode is deprecated and supported only for backward compatibility.**

**Cause:** The property runas.mode has been deprecated.

**Action:** Use instead the oracle.security.jps.jaas.mode property in jps-config.xml.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**JPS-00029: The audit service initialization failed for the application {0}. Reason {1}.**

**Cause:** Audit service failed.

**Action:** Check the audit service configuration in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00030: Cannot complete exist operation.**

**Cause:** Could not find entity.

**Action:** Verify that the entity exist.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00031: Cannot load the required class {0}. Reason {1}.**

**Cause:** Could not load a class.

**Action:** Ensure the class is in the class path.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-00032: The migration cannot write directly to the specified LDAP identity store; specify an alternate LDIF file to create.**

**Cause:** Could not perform a direct LDAP write operation.

**Action:** See the log files for details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

---

**JPS-00033: The direct policy store should be XML-based, and it can be specified as an XML file or as an input stream.**

**Cause:** The policy store specification was invalid.

**Action:** Check the policy store specification.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-00035: The WSS digest value {0} is invalid.**

**Cause:** Found missing WSS digest value in callback.

**Action:** Verify that the callback has a valid WSS digest value.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-00036: The WSS digest nonce {0} is invalid.**

**Cause:** Found missing WSS digest nonce in callback.

**Action:** Verify that the callback has a valid WSS digest nonce.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-00037: The WSS digest created {0} is invalid.**

**Cause:** Found missing WSS digest created in callback.

**Action:** Verify that the callback has a valid WSS digest created.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-00038: Cannot create or retrieve a ContextFactory.**

**Cause:** Cannot retrieve or create a JPS ContextFactory.

**Action:** Check jps-config.xml for correctness.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**JPS-00039: The service instance with provider {0} and name {1} is missing.**

**Cause:** A service instance configuration was missing.

**Action:** Check the service instance configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00040: The JPS audit component events file {0} is missing or invalid.**

---

**Cause:** Cannot find the audit component events file.

**Action:** Make sure the audit component events file is available and valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**JPS-00041: Cannot load the JpsAdminService class.**

**Cause:** The class JpsAdminService or a dependent class could not be loaded.

**Action:** Review the cause to resolve the error.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**JPS-00043: Cannot establish an LDAP connection after {0} attempts.**

**Cause:** The connection could not be established.

**Action:** Check the LDAP configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-00044: The LDAP URL format must be ldap://<host>:<port> or ldaps://<host>:<port>; but found {0}.**

**Cause:** Invalid LDAP URL format was found.

**Action:** The format of the LDAP URL must be ldap://<host>:<port> or ldaps://<host>:<port> format.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00045: The LDAP principal {0} is invalid.**

**Cause:** The LDAP principal was invalid.

**Action:** Provide a correct value for principal.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00046: The LDAP credential is invalid.**

**Cause:** The LDAP credential was invalid.

**Action:** Provide the correct credential value.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00047: The Subject parameter cannot be null.**

---

**Cause:** The supplied parameter was null.

**Action:** Check the Subject parameter supplied in the method call.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**JPS-00048: Principals are missing in the Subject.**

**Cause:** No principals were not found in the Subject.

**Action:** Verify that the supplied Subject contains principals.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**JPS-00049: The authenticated user principal is missing in the Subject.**

**Cause:** Authenticated user principal was not found in the Subject.

**Action:** Verify that the supplied Subject contains an authenticated user principal.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**JPS-00050: Invalid Subject parameter supplied.**

**Cause:** The Subject contained an anonymous user principal and an authenticated user principal.

**Action:** Ensure that the Subject does not contain the anonymous user principal.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**JPS-00051: The oracle.security.jps.config property not set.**

**Cause:** The oracle.security.jps.config property was not set.

**Action:** Set the oracle.security.jps.config property to an appropriate value.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-00052: Failed to Refresh Audit Service with new configuration.**

**Cause:** Failed to reload the audit configuration.

**Action:** Check the audit configuration file to see if the latest changes are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00053: Component events file is missing for {0} at {1}.**

**Cause:** The component events file for the given component type was missing.

---

**Action:** Verify that the properties set for the component files are correct in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00054: Failed to create the auditor for {0}.**

**Cause:** Failed to create the auditor object.

**Action:** Ensure that the component events file is not missing or corrupt and check the log files additional errors.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00055: Bootstrap credential store service is not intialized for the service configurator.**

**Cause:** The bootstrap credetial store service was not initialised.

**Action:** Make sure the bootstrap credetial store service is initialized before any other services.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**JPS-00056: Failed to create identity store service instance {0}. Reason: {1}.**

**Cause:** Failed to create identity store service instance {0}. Cause: {1}.

**Action:** Check the log files to resolve the error.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**JPS-00057: Failed to set OutputProperty for indent or XML encoding. Reason {0}.**

**Cause:** Failed to setOutputProperty for indent or XML encoding. Cause: {0}

**Action:** Check the XML Transformer implementation.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**JPS-00058: Failed to set XML output encoding to UTF-8 in OutputStreamWriter. Reason {0}.**

**Cause:** Failed to set XML output encoding to UTF-8 in OutputStreamWriter. Cause: {0}

**Action:** Check the JDK OutputStreamWriter supported encodings.

**Level:** 1

**Type:** WARNING

---

**Impact:** Configuration

**JPS-00059: The specified enterprise identity is null or invalid.**

**Cause:** An enterprise identity provided was null or invalid

**Action:** Provide a valid enterprise identity value.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00060: The specified enterprise identity {0} is not found in identity store.**

**Cause:** The specified enterprise identity {0} was not found in the identity store.

**Action:** Provide a valid enterprise identity value.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00061: No platform specific factory is found to create the platform principals.**

**Check errors in the log files.**

**Cause:** No platform specific factory was found to create platform principals.

**Action:** Check the log files for the errors.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00062: No identity store associate with policy store found.**

**Cause:** No identity store associate with policy store found

**Action:** Contact system administrator

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00063: Jps servlet filter creation failed. Reason: {0}.**

**Cause:** Jps Servlet Filter creation failed

**Action:** Contact system administrator

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**JPS-00064: Jps ejb interceptor creation failed. Reason: {0}.**

**Cause:** Jps EJB Interceptor creation failed

**Action:** Contact system administrator

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

---

**JPS-00065: Jps platform factory creation failed. Reason: {0}.**

**Cause:** Jps Platform Factory creation failed

**Action:** Contact system administrator

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**JPS-00066: Jps property value retrieval failed. Reason: {0}.**

**Cause:** Jps property value retrieval failed

**Action:** Check the property values in jps configuration files

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00068: Ldap security checking failed. The LDAP url should start with ldaps and oracle.ldap.wtlloc system property should be set. Reason : {0}.**

**Cause:** Is LDAP secure failed

**Action:** Contact system administrator

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-00069: Ldap credential store provider missing.**

**Cause:** LDAP credential provider missed

**Action:** Ensure ldap credential store provider is configured

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-00070: Ldap policy store provider missing.**

**Cause:** LDAP policy store provider missing

**Action:** Ensure ldap policy store is configured

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-00071: Ldap bootstrap credential retrieval failed. Reason:{0}.**

**Cause:** Retrieval of bootstrap credential failed

**Action:** Check the credential store configuration for credential types, maps and key

**Level:** 1

**Type:** ERROR

**Impact:** Security

---

**JPS-00072: Policy schema upgrade not required. Store Schema version {0} is compatible to the seed schema version {1}**

**Cause:** Comparison of policy schema version in the store against to seed schema version.

**Action:** No action required

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**JPS-00073: Policy store schema version not found**

**Cause:** Trying to determine version of the policy schema in the store

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**JPS-00074: Policy store schema version {0} is less than the latest schema version {1}, upgraded the Policy store schema to latest version.**

**Cause:** Comparison of the Policy schema version in the store against the schema to seed

**Action:** No action required

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**JPS-00075: Unable to query Policy store schema version under "{0}", Cause {1}**

**Cause:** Query of Policy schema from the store failed

**Action:** Confirm the Policy store schema containers are present in the store

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**JPS-00076: Policy schema version set to {0}**

**Cause:** Version of the policy schema has been set in the store

**Action:** No action required

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**JPS-00077: Setting version of policy schema in the store failed. Cause {0}**

**Cause:** Unexpected error occurred while setting the version of the Policy schema in the store

**Action:** Confirm the container is present in the store and caller has sufficient privileges to perform this operation

**Level:** 1



---

**Type:** ERROR

**Impact:** Configuration

**JPS-00078: Credential store schema upgrade not required. Store Schema version {0} is compatible to the seed schema version {1}**

**Cause:** Comparison of Credential schema version in the store against the seed schema version.

**Action:** No action required

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**JPS-00079: Credential store schema version not found**

**Cause:** Check if the DN exists, or if the Credential Store schema version attribute is present at the specified location

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00080: Credential store schema version {0} is less than the latest schema version {1}, upgraded the Credential store schema to latest version.**

**Cause:** Comparison of the Credential schema version in the store against the schema to seed

**Action:** No action required

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**JPS-00081: Unable to query Credential store schema version under "{0}", Cause {1}**

**Cause:** Query of Credential schema from store failed

**Action:** Confirm the Credential store schema container in the store is present

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**JPS-00082: Credential schema version set to {0}**

**Cause:** Version of the credential schema has been set in the store

**Action:** No action required

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**JPS-00083: Setting version of credential schema in the store failed. Cause {0}**

**Cause:** Unexpected error occurred while setting the version of the credential schema in the store

---

**Action:** Confirm the container is present in the store and caller has sufficient privileges to perform this operation

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00084: IOException raised from FileLocker {0}.**

**Cause:** Closing IO objects in FileLocker

**Action:** Check the file system for access privileges and disk space availability.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**JPS-00085: OID version is unavailable.**

**Cause:** OID version is unavailable

**Action:** Check the ldap url against the server type passed.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**JPS-00086: Error while encoding search string: {0} to UTF-8 encoding**

**Cause:** Unable to encode user string to UTF-8 encoding

**Action:** Check the search string.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**JPS-00087: The subject parameter is null.**

**Cause:** The subject parameter is null

**Action:** Make sure the subject parameter is not null

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-00088: The user name parameter is null.**

**Cause:** The user name parameter is null

**Action:** Make sure the user name parameter is not null

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-00089: The subject from the current AccessControlContext is null.**

**Cause:** No subject is associated with the current AccessControlContext.

---

**Action:** Ensure that the subject is associated with the current AccessControlContext.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-00090: Failed to create policy store service instance {0}. Cause: {1}.**

**Cause:** Failed to create policy store service instance {0}. Cause: {1}.

**Action:** Check the log files to resolve the error.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**JPS-00091: No {0} available.**

**Cause:** No {0} available.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-00092: The ldap service was null.**

**Cause:** The ldap service was null.

**Action:** Ensure the ldap service is not null.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-00093: Class {0} was not type of {1}.**

**Cause:** Class {0} was not type of {1}.

**Action:** Ensure class name is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-00095: {0} system properties not set.**

**Cause:** System properties {0} not set.

**Action:** Set the system properties.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**JPS-00096: No {0} defined for {1}.**

**Cause:** No {0} defined for {1}.

**Action:** Defined the specified object.

---

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**JPS-00097: {0} missing in message : {1}.**

**Cause:** {0} missing in message : {1}.

**Action:** Check the input.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**JPS-00098: Duplicate error message.**

**Cause:** Duplicate error message.

**Action:** Check the input.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**JPS-00099: {0} already exists.**

**Cause:** {0} already exists.

**Action:** Check the input.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**JPS-00100: Failed to instantiate {0}.**

**Cause:** Failed to instantiate {0}.

**Action:** Check the object type.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**JPS-00101: {0} not match {1}.**

**Cause:** {0} not match with {1}.

**Action:** Check the object type.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**JPS-00102: Unhandled entry {0}**

**Cause:** Unhandled entry {0}.

**Action:** Check the entry.

**Level:** 1

**Type:** WARNING

---

**Impact:** Configuration

**JPS-00103: Invalid login module type {0}.**  
**Cause:** Invalid login module type {0}.  
**Action:** Use valid login module type.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**JPS-00104: System policy does not exist.**  
**Cause:** System policy does not exist.  
**Action:** Ensure system policy exist.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**JPS-00105: Failed to create temp dir {0}.**  
**Cause:** Failed to create temp dir {0}.  
**Action:** Check the log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00106: InputStream has no more data to read.**  
**Cause:** InputStream had no more data to read.  
**Action:** Check the log for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**JPS-00110: Failed to decode {0}. Reason {1}.**  
**Cause:** Failed to decode {0}. Reason: {1}.  
**Action:** Check log for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-00111: Current timer interval ({0} seconds) is too short.**  
**Cause:** Current timer interval ({0} seconds) is too short.  
**Action:** Please set a longer interval in the configuration file.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-00112: Set property {0} to value {1}.**

---

**Cause:** Set property {0} to value {1}.

**Action:** Check log for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-00113: Failed to parse condition {0}. Reason {1}.**

**Cause:** Failed to parse condition {0}. Reason {1}.

**Action:** Check log for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-00114: Failed to load data file {0}.**

**Cause:** Failed to load data file {0}.

**Action:** Please check file location.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-00115: Failed to modify JPS Schema.**

**Cause:** Failed to modify JPS Schema.

**Action:** Check log for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-00116: Failed to read JPS Schema.**

**Cause:** Failed to read JPS Schema.

**Action:** Check log for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-00117: Failed to delete System Policy name {0}. Reason {1}.**

**Cause:** Failed to delete System Policy name {0}. Reason {1}.

**Action:** Check log for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-00118: {0} not found.**

**Cause:** {0} not found.

**Action:** Check log for more details.

---

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-00119: Failed to create ResourceEntry name: {0}, action: {1}, cause: {2}.**

**Cause:** Failed to create ResourceEntry name: {0}, action: {1}, cause: {2}.

**Action:** Check log for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-00120: Failed to seed attribute {0}, ldap object class {1}.**

**Cause:** Failed to seed attribute {0}, ldap object class {1}.

**Action:** Check the LDAP configuration to resolve the error.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00121: Failed to parse LDIF record {0}. Reason: {1}.**

**Cause:** Failed to parse LDIF record {0}. Reason: {1}.

**Action:** Check the LDAP configuration to resolve the error.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00122: Farm DN {0} does not exist.**

**Cause:** Farm DN {0} does not exist.

**Action:** Ensure farm DN is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00123: RDN {0} not found under farm {1}.**

**Cause:** RDN {0} not found under farm {1}.

**Action:** Check LDAP server type.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00124: {0} was not supported.**

**Cause:** {0} was not supported.

**Action:** Use a valid type.

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**JPS-00125: Property {0} was null.**

**Cause:** Property {0} was null.

**Action:** Ensure property is not null.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-00127: Failed to create igf service instance {0}. Reason: {1}.**

**Cause:** Failed to create igf service instance {0}. Cause: {1}.

**Action:** Check the log files to resolve the error.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**JPS-00128: Keystore schema upgrade not required. Store Schema version {0} is compatible to the seed schema version {1}**

**Cause:** Comparison of Keystore schema version in the store against the seed schema version.

**Action:** No action required

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**JPS-00129: Keystore schema version not found**

**Cause:** Check if the DN exists, or if the Keystore schema version attribute is present at the specified location

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00130: Keystore schema version {0} is less than the latest schema version {1}, upgraded the Keystore schema to latest version.**

**Cause:** Comparison of the Keystore schema version in the store against the schema to seed

**Action:** No action required

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**JPS-00131: Unable to query Keystore schema version under "{0}", Cause {1}**

**Cause:** Query of Keystore schema from store failed

**Action:** Confirm the Keystore schema container in the store is present



---

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**JPS-00132: Keystore schema version set to {0}**

**Cause:** Version of the keystore schema has been set in the store

**Action:** No action required

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**JPS-00133: Setting version of keystore schema in the store failed. Cause {0}**

**Cause:** Unexpected error occurred while setting the version of the keystore schema in the store

**Action:** Confirm the container is present in the store and caller has sufficient privileges to perform this operation

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-00134: The offline deployment staging directory {0} does not exist.**

**Cause:** The cause may be that the product was installed improperly.

**Action:** Install the product properly.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**JPS-00135: Exception occurs on saving ear file {0}.**

**Cause:** The cause may be due to bad ear file or insufficient permission.

**Action:** Check the ear file and the file system permission.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**JPS-00136: Exception occurs on saving offline deployment property file in application directory {0}.**

**Cause:** The cause may be due to insufficient permission.

**Action:** Check the file system permission.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**JPS-00138: Exception occurs on opening the staging application in {0}.**

**Cause:** This may be caused by bad .ear file on the disk.

**Action:** Check the .ear file on the disk.

---

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**JPS-00139: Exception occurs on loading the property file of the staging application in {0}.**

**Cause:** Failed to open the property file.

**Action:** Check the property file on the disk.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**JPS-00141: Cannot handle offline deployed application due to the required system property {0} is not set.**

**Cause:** The cause may be that the product was installed improperly.

**Action:** Install the product properly.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**JPS-00143: Error on migrating security artifacts.**

**Cause:** Error on migrating security artifacts.

**Action:** Check security related files in your application, such as opss-application.xml, jazn-data.xml, cwallet.sso, etc.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**JPS-00144: Error on opening ear file {0}.**

**Cause:** Error on opening ear file.

**Action:** Check the ear file.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**JPS-00145: Found no installed application at {0}.**

**Cause:** Found no installed application at {0}.

**Action:** Check the installed application at {0}.

**Level:** 1

**Type:** WARNING

**Impact:** Deployment

**JPS-00146: Failed to create identity store service instance {0}. Reason: the service does not enable the virtualize flag, but references other service instance.**

---

**Cause:** Failed to create identity store service instance {0}. Cause: the service does not enable the virtualize flag, but references other service instance.

**Action:** Either make the virtualize flag true, or directly define the ldap configuration instead of using service reference

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**JPS-00147: Keystore re-association not supported.**

**Cause:** Configuration of key store was not suitable for re-association.

**Action:** Confirm the key store configuration is updated.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**JPS-01000: The credential map {0} is invalid.**

**Cause:** The specified credential map name was invalid.

**Action:** Ensure the credential map name is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-01001: The credential key {0} is invalid.**

**Cause:** The specified credential key name was invalid.

**Action:** Ensure the credential key name is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-01002: The value {0} is invalid in this password credential.**

**Cause:** The specified password credential was invalid.

**Action:** Use only a supported credential type. The supported types are {0}.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-01003: The value of name {0}, url {1}, of port {2} is invalid in this datasource credential.**

**Cause:** The specified datasource credential was invalid.

**Action:** Use only a supported credential type. The supported types are {0}.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**JPS-01004: The value {0} is invalid in this generic credential.**

**Cause:** The specified generic credential was invalid.

**Action:** Use only a supported credential type. The supported types are {0}.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-01005: The credential type {0} is not supported.**

**Cause:** The specified credential type was invalid.

**Action:** Use only a supported credential type. The supported types are {0}.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-01006: The credential expired on {0}.**

**Cause:** This credential expired on {0}.

**Action:** Create a new credential.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-01007: The credential with map {0} and key {1} already exists.**

**Cause:** This credential already existed.

**Action:** Use a credential with different map name or key.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-01008: The credential map name {0} already exists.**

**Cause:** This credential map name already existed.

**Action:** Use a different map name.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-01009: The credential with map {0} and key {1} does not exist.**

**Cause:** This credential did not exist.

**Action:** Check the credential map name and key.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-01010: The credential map {0} does not exist.**

**Cause:** This credential map name did not exist.

---

**Action:** Check the credential map name.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-01011: The credential store location property {0} is not configured, or the configured value {1} is invalid.**

**Cause:** The credential store location was not specified.

**Action:** Check the value of the location attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01012: The credential property {0} is invalid or not defined.**

**Cause:** The credential property {0} was invalid or not defined.

**Action:** Check the configuration of this property.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-01013: The credential store DN {0} is missing in the LDAP store; the target DN must be pre-configured.**

**Cause:** The expected credential store DN {0} was missing.

**Action:** Configure this DN during the bootstrap process.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-01014: The credential {0} is invalid.**

**Cause:** This credential was invalid.

**Action:** Use only a supported credential type. The supported types are password or generic.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-01015: Cannot retrieve credential {0}.**

**Cause:** This credential was invalid.

**Action:** Use only a supported credential type. The supported types are password or generic.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-01016: A password credential is expected; instead found {0}.**

---

**Cause:** Wrong credential type was found.

**Action:** Use the password credential type. Expecting password credential but found {0}.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**JPS-01017: A generic credential is expected; instead found {0}.**

**Cause:** Wrong credential type was found.

**Action:** Use the generic credential type. Expecting generic credential but found {0}.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**JPS-01018: A password credential is missing in the credential store.**

**Cause:** The password credential was not found in the credential store.

**Action:** Ensure that the credential is present in the credential store.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**JPS-01019: The credential store {0} has been moved or deleted.**

**Cause:** The specified credential store did not exist.

**Action:** Ensure that the credential store location is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01020: Cannot create store {0}.**

**Cause:** Could not create the credential store.

**Action:** Verify the store location, that sufficient permissions are in place, and that sufficient disk space is available.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01021: The generic credential {0} is not serializable.**

**Cause:** This generic credential was not serializable.

**Action:** Make this credential serializable.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**JPS-01022: The expiration time {0} is invalid: the expiration time must be later than the creation time.**

**Cause:** Invalid credential expiration time.

**Action:** Set the expiration time to a time later than the credential creation time.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-01048: Modifying of credential failed. Reason {0}**

**Cause:** Modification of credential failed

**Action:** Contact system administrator

**Level:** 1

**Type:** WARNING

**Impact:** Compliance

**JPS-01049: Reading all credentials from the store failed. Reason {0}**

**Cause:** Read of all credentials failed

**Action:** Contact system administrator

**Level:** 1

**Type:** WARNING

**Impact:** Compliance

**JPS-01050: Opening of wallet based credential store failed. Reason {0}**

**Cause:** Credential wallet could not be opened

**Action:** Contact system administrator

**Level:** 1

**Type:** WARNING

**Impact:** Compliance

**JPS-01051: Credential audit events cannot be logged. Reason {0}**

**Cause:** Credential store audit events logging not enabled

**Action:** Check the audit configuration to ensure auditing enabled

**Level:** 1

**Type:** WARNING

**Impact:** Compliance

**JPS-01052: Credential audit event logging failed. Reason {0}**

**Cause:** Credential audit event logging failed

**Action:** Contact system administrator

**Level:** 1

**Type:** WARNING

**Impact:** Compliance

**JPS-01053: Creation of new credential map failed. Reason {0}**

---

**Cause:** Creation of new credential map failed

**Action:** Ensure all jps libraries are in setup properly in the runtime

**Level:** 1

**Type:** WARNING

**Impact:** Compliance

**JPS-01054: Refresh of credential wallet failed. Reason {0}**

**Cause:** Refresh of credstore wallet failed

**Action:** Contact system administrator

**Level:** 1

**Type:** WARNING

**Impact:** Compliance

**JPS-01055: Could not create ldap credential store instance. Reason {0}**

**Cause:** Could not create ldap credential store instance

**Action:** Contact system administrator

**Level:** 1

**Type:** WARNING

**Impact:** Compliance

**JPS-01056: The credential store location {0} was invalid. It should be a directory or full path to cwallet.sso file.**

**Cause:** The credential store location {0} was invalid. It should be a directory or full path to cwallet.sso file.

**Action:** Check the value of the location property

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01057: The credential map was invalid. Reason {0}**

**Cause:** The credential map was null.

**Action:** Check the value of the credential map

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-01058: The credential dn {0} was invalid.**

**Cause:** The credential dn was invalid.

**Action:** Ensure the credential dn is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-01059: The credential store instance {0} was not fully initialized.**



---

**Cause:** The credential store was not fully initialized until data source is available.

**Action:** Wait and retry later

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01500: The anonymous service configuration is missing.**

**Cause:** The anonymous service configuration was missing in jps-config.xml.

**Action:** Configure the anonymous service in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01501: The anonymous identity store provider instance {0} is not found.**

**Cause:** The anonymous identity store provider configuration was invalid.

**Action:** Check the anonymous identity store provider configuration in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01502: The LDAP identity store provider instance {0} is not found.**

**Cause:** Invalid or missing LDAP identity store provider configuration.

**Action:** Check LDAP identity store provider configuration in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01503: The XML identity store provider instance {0} is not found.**

**Cause:** Invalid or missing XML identity store provider configuration.

**Action:** Check the XML identity store provider configuration in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-01504: The secret store provider for provider {0} and instance {1} does not exist.**

**Cause:** The credential provider was missing.

**Action:** Check the configuration of the credential store provider in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-01505: The key store provider {0} is missing or not configured.**

**Cause:** The keystore provider configuration was missing in jps-config.xml.

---

**Action:** Configure a keystore provider in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01506: Invalid context name.**

**Cause:** Invalid context name found.

**Action:** Check the configurations of contexts in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01507: Invalid login module name.**

**Cause:** Invalid login module name found.

**Action:** Check the login module configurations in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01508: Invalid login module descriptor.**

**Cause:** Invalid login module descriptor found.

**Action:** Check the login module instance configurations in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01509: Invalid login module class name.**

**Cause:** Invalid login module class name found.

**Action:** Check the loginModuleClassName property in the login module instance configuration in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01510: Invalid login module entries.**

**Cause:** Invalid login module entries found.

**Action:** The expected login module to be invoked is not present or misconfigured. Check the login module instance configurations in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01511: Invalid login module entry.**

**Cause:** The login module entries were not valid in the jps-config.xml file.

---

**Action:** Correct the login module entries in service instances and service providers.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01512: Missing login module entry.**

**Cause:** The login module entries were missing in the jps-config.xml file.

**Action:** Add the appropriate login module entries in service instances and service providers.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01513: The configuration of the JAAS login provider {0} and the service instance {1} are missing.**

**Cause:** The login module provider was missing.

**Action:** Ensure that a login module provider is configured in the jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01514: The default context is missing in jps-config.xml.**

**Cause:** Default context was missing in jps-config.xml.

**Action:** Add a default context to jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01515: A context named anonymous is missing in jps-config.xml.**

**Cause:** Context named anonymous was missing in jps-config.xml.

**Action:** Add a context named anonymous in jps-config.xml file with an anonymous service instance reference.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01516: The default credential store service is missing in default jps-config.xml.**

**Cause:** The default credential store service was missing in the default context in jps-config.xml.

**Action:** There must be at least one credential store service configured in the default context.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**JPS-01517: The generic identity store provider is missing.**

**Cause:** Invalid or missing generic identity store provider configuration.

**Action:** Check the generic identity store provider configuration in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01518: The anonymous service is not available in the application context.**

**Cause:** The anonymous service was not available in context.

**Action:** Check the context in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**JPS-01519: The default context configuration is missing in jps-config.xml.**

**Cause:** The default context configuration was not available in jps-config.xml.

**Action:** Ensure that the default context is present in jps-config.xml.

**Level:** 1

**Type:** WARNING

**Impact:** Session

**JPS-01520: Cannot initialize identity store.**

**Cause:** Could not initialize identity store.

**Action:** Correct the identity store configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01521: Identity store file path is invalid.**

**Cause:** Identity store file path was invalid or null.

**Action:** Ensure that the path configured with the property ADF\_IM\_FILE\_PATH is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01522: The Jps configuration is invalid.**

**Cause:** JPS configuration was null or invalid.

**Action:** Verify configuration in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**JPS-01523: The service instance {0} is invalid or not configured in jps-config.xml.**

**Cause:** A service instance configuration was not valid.

**Action:** Verify that the instance is correctly configured in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01524: The service instance {0} is invalid or not configured in jps-config.xml.**

**Cause:** A service provider configuration was invalid.

**Action:** Verify that the provider is correctly configured in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01525: The identity store service is not properly configured.**

**Cause:** Found invalid identity store service configuration in jps-config.xml.

**Action:** Ensure a valid identity store configuration in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01526: Configured identity store, user manager, or role manager is invalid. The error is {0}.**

**Cause:** Found null value for configured identity store, user manager, or role manager.

**Action:** Correct the identity store configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01527: The identity store factory name is not configured.**

**Cause:** Could not find identity store factory name.

**Action:** Use the property ADF\_IM\_FACTORY\_CLASS to specify the factory class.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01528: Idm identity store is invalid.**

**Cause:** The identity store was not configured correctly.

**Action:** Correct the configuration of the identity store in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**JPS-01529: The context {0} contains multiple services of type {1}.**

**Cause:** The context {0} contains multiple services of type {0}.

**Action:** Check jps-config.xml for correctness.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01530: The anonymous service is already configured in the context {0}.**

**Cause:** The anonymous service is already configured in the context {0}.

**Action:** Check jps-config.xml for correctness.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**JPS-01531: Configuration location {0} is a directory. File name expected.**

**Cause:** Configuration location {0} is a directory. File name expected.

**Action:** Provide a valid configuration file location, including a file name.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01532: The service instance location {0} is invalid or not configured in jps-config.xml.**

**Cause:** A service instance configuration was invalid.

**Action:** Verify that the location of the instance is correctly configured in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-01533: Failed to create service instance {0} for application {1}.**

**Cause:** Failed to create service instance {0} for application {1}.

**Action:** Check the log files to resolve the error.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**JPS-01534: Failed to get identity store configuration.**

**Cause:** Failed to get identity store configuration.

**Action:** Ensure the configuration is available.

**Level:** 1

**Type:** ERROR

**Impact:** Security

---

**JPS-01535: Failed to get configuration name {0}.**

**Cause:** Failed to get configuration name {0}.

**Action:** Check the log files to resolve the error.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**JPS-01536: Failed to evaluate XML expression on Object {0}.**

**Cause:** Failed to evaluate XML expression on Object {0}.

**Action:** Check the log files to resolve the error.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**JPS-01538: The default policy provider was not found.**

**Cause:** The default policy provider was not found.

**Action:** Ensure policy provider configuration is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-01539: The Ovd IGF service provider instance {0} is not found.**

**Cause:** Invalid or missing Ovd IGF service provider configuration.

**Action:** Check Ovd IGF service provider configuration in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02001: The authentication of user {0} failed.**

**Cause:** User authentication failed.

**Action:** Ensure the user exists in the identity store. Check the user credentials that are being sent for authentication.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-02003: Authentication failed.**

**Cause:** Could not authenticate user.

**Action:** Ensure that authentication uses valid user name and password.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-02004: Cannot authenticate user {0}.**

---

**Cause:** Could not authenticate user.

**Action:** Ensure that the credentials provided for authentication are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-02005: Cannot login user {0} because {1}. Check the log files for more details.**

**Cause:** Encountered an error while authenticating user.

**Action:** Contact the domain administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-02008: Authenticated role name is invalid: property {0} is invalid or not configured.**

**Cause:** Found invalid or undefined authentication role name property.

**Action:** Ensure that authentication role name properties are valid in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02009: SAML trusted assertion issuer is not configured: property set {0} is not configured.**

**Cause:** Could not find configuration for SAML trusted assertion issuer.

**Action:** Set the property saml.trusted.issuers in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02010: Cannot verify SAML assertion.**

**Cause:** Found invalid assertion; SAML trusted assertion issuer was not configured.

**Action:** Check assertion and set the property saml.trusted.issuers in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-02011: SAML assertion is missing name identifier.**

**Cause:** Found invalid assertion: name identifier was missing.

**Action:** Ensure the use of a valid assertion.

**Level:** 1

**Type:** ERROR



---

**Impact:** Requests/Responses

**JPS-02012: SAML assertion subject name is invalid.**

**Cause:** Found invalid assertion: subject name was null.

**Action:** Ensure the use of a valid assertion.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-02013: SAML assertion issuer name is invalid.**

**Cause:** Found invalid assertion: issuer name was invalid.

**Action:** Ensure the use of a valid assertion.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-02014: SAML assertion is invalid.**

**Cause:** Found invalid assertion.

**Action:** Ensure the use of a valid assertion.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-02015: SAML assertion has missing subject.**

**Cause:** Found invalid assertion: subject statement was missing.

**Action:** Ensure the use of a valid assertion.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-02016: SAML assertion is missing conditions.**

**Cause:** Found invalid assertion: condition statement was missing.

**Action:** Ensure the use of a valid assertion.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-02017: Found invalid condition "not before" in SAML assertion. Current**

**Time:{0}, {1} milli seconds, {2} Time:{3}.**

**Cause:** Found invalid condition "not before" in SAML assertion. Current Time:{0}, {1} milli seconds, {2} Time:{3}.

**Action:** Verify that the condition "not before" in the SAML assertion is set to a date earlier than or equal to today's date.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**JPS-02018: Found invalid condition "on or after" in SAML assertion. Current Time:{0}, {1} milli seconds, {2} Time:{3}.**

**Cause:** Found invalid condition "on or after" in SAML assertion. Current Time:{0}, {1} milli seconds, {2} Time:{3}.

**Action:** Verify that the condition "on or after" in the SAML assertion is set to a valid date.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-02019: SAML assertion is missing assertion issuers signature.**

**Cause:** Found invalid assertion: assertion issuers signature was missing.

**Action:** Ensure the use of a valid assertion.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-02020: Signature for SAML assertion issuer is invalid.**

**Cause:** Found invalid signature in SAML assertion issuer.

**Action:** Ensure the use of a valid assertion.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02021: Signature certificate (X509 Data) for SAML assertion issuer is invalid.**

**Cause:** Found invalid signature certificate (X509 Data) in SAML assertion.

**Action:** Ensure the use of a valid assertion.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02022: Cannot verify signature for SAML assertion.**

**Cause:** Failed to verify issuers signature in assertion.

**Action:** Check the assertion and set the property `saml.trusted.issuers` in `jps-config.xml`.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02023: Cannot verify SAML assertion signature certificate path.**

**Cause:** Found invalid assertion signature.

**Action:** Check the assertion and set the property `saml.trusted.issuers` in `jps-config.xml`.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02024: Cannot retrieve trusted CA policy for issuer {0}.**

**Cause:** Found invalid assertion.

**Action:** Check the assertion and set the property `saml.trusted.issuers` in `jps-config.xml`.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02025: Cannot modify read-only Subject.**

**Cause:** Could not modify a read-only subject.

**Action:** Ensure the program logic is correct and that the program does not attempt to modify a read-only subject.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-02026: X509 certificate is invalid.**

**Cause:** The X509 certificate passed to the callback handler was null or invalid.

**Action:** Ensure that the callback handler uses a valid X509 certificate.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**JPS-02027: The property set {0} is missing in jps-config.xml.**

**Cause:** Could not find property set in `jps-config.xml`.

**Action:** Configure the property set in `jps-config.xml`.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02028: The extended property set {0} is missing in jps-config.xml.**

**Cause:** Could not find extended property set in `jps-config.xml`.

**Action:** Configure the extended property set in `jps-config.xml`.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02029: The default realm is not configured in identity store service {0}.**

**Cause:** Could not find the default realm in the identity store service.

**Action:** Configure the default realm property in the identity store service.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02030: The default realm configured in identity store service {0} is empty or null.**

**Cause:** Found null default realm configured in identity store service.

**Action:** Configure the default realm property in the identity store service.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02031: The invalid realm name property {0} is configured in identity store service {1}.**

**Cause:** Found invalid realm name property in identity store service.

**Action:** Configure the correct realm name property in the identity store service.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02032: The duplicate realm name {0} is configured in identity store service {1}.**

**Cause:** Found duplicate realm in identity store service.

**Action:** Remove duplicate realm configuration from the identity store service.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02033: The realm name {0} passed for authentication is invalid. Was expecting {1}, but found {0}.**

**Cause:** Found invalid realm name {0}. Was expecting {1}, but found {0}.

**Action:** Check the realm name passed to the authentication of user name.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02034: Realm name is missing in user name for authentication in multi-realm configuration.**

**Cause:** The realm name was not supplied for authentication of multi-realm configuration.

**Action:** Ensure that the realm name value is passed in the user name when authenticating a multi-realm configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02035: Cannot properly initialize the Kerberos authenticator.**

---

**Cause:** Could not initialize the Kerberos authenticator.

**Action:** Check the log files for errors and contact the domain administrator.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**JPS-02036: Browser does not support Kerberos authentication.**

**Cause:** Could not find support for Kerberos authentication, or it was not configured correctly.

**Action:** Verify that the browser is set to allow Kerberos authentication.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**JPS-02037: The SAML assertion issuer {0} certificate is missing from the keystore.**

**Cause:** Could not find SAML assertion certificate in keystore.

**Action:** Store the SAML assertion issuer's certificate in the keystore, and configure the trustpoint alias in JpsSAMLLoginModule.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02038: The SAML assertion {0} is missing a signature.**

**Cause:** Could not find expected signature in assertion.

**Action:** Check that the assertion sent has a valid signature.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**JPS-02039: Cannot assert certificate. Reason {0}.**

**Cause:** Found invalid certificate, or could not find corresponding user in identity store.

**Action:** Make sure that the assertion is valid.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**JPS-02040: Both user identity and token were provided for assertion. Either user identity or token should be provided, not both.**

**Cause:** Both user identity and token were provided for assertion.

**Action:** Provide either user identity or a token for assertion, not both.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**JPS-02041: Assertor class was configured as {0}, but does not implement {1}.**

**Cause:** Assertor class was configured as {0}, but does not implement {1}.

**Action:** Provide an Assertor that implements {1}.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**JPS-02042: Token assertion failed.**

**Cause:** Token assertion failed.

**Action:** Check detailed logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**JPS-02043: User name cannot be null or empty.**

**Cause:** User name cannot be null or empty.

**Action:** Check that the user name is not null or empty.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-02044: Found invalid attesting entity in SAML assertion. Attesting entity: {0}.**

**Cause:** Found invalid attesting entity in SAML assertion. Attesting entity: {0}.

**Action:** Check that the attesting entity for the SAML assertion is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-02045: Audience URI for SAML assertion is invalid.**

**Cause:** SAML assertion audience URI is invalid.

**Action:** Check that the audience URI for the SAML assertion is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-02046: Found invalid name identifier in SAML assertion. Can not find the specified user in id store: {0}.**

**Cause:** Found invalid name identifier in SAML assertion. Can not find the specified user in id store: {0}.

**Action:** Check that the name identifier for the SAML assertion is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**JPS-02047: SAMLNameIdentifierMapper class was configured as {0}, but does not implement**

**oracle.security.jps.internal.jaas.module.saml.SAMLNameIdentifierMapper.**

**Cause:** SAMLNameIdentifierMapper class was configured as {0}, but does not implement

oracle.security.jps.internal.jaas.module.saml.SAMLNameIdentifierMapper.

**Action:** Provide an SAMLNameIdentifierMapper that implements oracle.security.jps.internal.jaas.module.saml.SAMLNameIdentifierMapper.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**JPS-02048: Incorrect password was provided.**

**Cause:** Incorrect password was provided.

**Action:** Ensure that authentication uses correct password.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-02049: Null or empty password was provided.**

**Cause:** Null or empty password was provided.

**Action:** Ensure that authentication uses correct password.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-02500: The principal name is invalid.**

**Cause:** Found null principal name.

**Action:** Check the principal name.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-02501: The principal type {0} is invalid.**

**Cause:** Found invalid principal type.

**Action:** Check the principal type.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-02502: The password {0} is invalid.**

**Cause:** Found invalid password.

**Action:** Check the password passed to create user account.

**Level:** 1

---

**Type:** ERROR

**Impact:** Data

**JPS-02503: The user name {0} is invalid.**

**Cause:** Found invalid user name.

**Action:** Ensure that the user name used to create, fetch, or remove the account is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**JPS-02504: The user range starting at {0} and ending at {1} is not a valid range.**

**Cause:** The user range was invalid.

**Action:** Check the start and end range. The start range cannot be less than 0, and the end range cannot be less than start range.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**JPS-02505: The group {0} is invalid.**

**Cause:** Group name was invalid.

**Action:** Check the group name that is being sent for creating/fetching/removing group.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**JPS-02506: The group range starting at {0} and ending at {1} is not valid range.**

**Cause:** The JPSUserManager.getGroups() method was invoked with invalid start or end range.

**Action:** Check the start and end range. The start range cannot be less than 0, and the end range cannot be less than start range.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**JPS-02507: The anonymous user is not found.**

**Cause:** The anonymous user was not found.

**Action:** Ensure that a valid anonymous user is configured.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**JPS-02508: The anonymous user name is invalid; property {0} is invalid or not defined.**



---

**Cause:** The anonymous.user.name property was not configured in the anonymous service configuration.

**Action:** Configure the anonymous.user.name property to a valid user name in the identity store while configuring the Anonymous Service.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02509: The user {0} already exists in the store; choose a different user name.**

**Cause:** The specified user name already existed in the store.

**Action:** Provide a different user name.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-02510: The group {0} already exists in the store; choose a different group name.**

**Cause:** The specified group name already existed in the store.

**Action:** Provide a different group name.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-02511: The role for group {0} is invalid.**

**Cause:** Found null role in group.

**Action:** Check the group's name.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-02512: Cannot create a new user {0}.**

**Cause:** Could not create user.

**Action:** Ensure that the user name is valid and distinct from any other existing user name.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02513: Cannot drop user {0}.**

**Cause:** Could not drop the user.

**Action:** Ensure this user already exists.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**JPS-02514: Cannot retrieve user profile.**

**Cause:** Could not get profile for user.

**Action:** Ensure that the user exists.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02515: Cannot update user profile.**

**Cause:** Could not set profile for user.

**Action:** Ensure that the user exists.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02516: Cannot retrieve role profile.**

**Cause:** Could not get role profile.

**Action:** Ensure that the role exists.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02517: Cannot update role profile.**

**Cause:** Could not set role profile.

**Action:** Ensure that the role exists.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02518: Cannot create role {0}.**

**Cause:** Could not create role.

**Action:** Ensure that the role exists.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-02519: Cannot drop role {0}.**

**Cause:** Could not drop role.

**Action:** Ensure that the role exists.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02520: Cannot grant role to the principal.**

**Cause:** Could not grant permission to role.

---

**Action:** Ensure that the permission is set for the role.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02521: Cannot revoke role from principal.**

**Cause:** Could not revoke role.

**Action:** Check that the correct permission to revoke the role is set.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02522: Cannot add user to role owners.**

**Cause:** Could not add owner to role.

**Action:** Check log files and correct the appropriate configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02523: Cannot remove user from role owners.**

**Cause:** Could not remove owner from role.

**Action:** Check log files and correct the appropriate configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02524: Cannot retrieve role owners.**

**Cause:** Could not get role owners.

**Action:** Check log files and correct the appropriate configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02525: Cannot retrieve role grantees.**

**Cause:** Could not get role grantees.

**Action:** Check log files and correct the appropriate configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02526: Cannot retrieve the roles granted to principal.**

**Cause:** Could not get granted roles.

**Action:** Check log files and correct the appropriate configuration.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02527: Cannot close identity store.**

**Cause:** Could not close identity store.

**Action:** Check log files and correct the appropriate configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02528: Cannot obtain a handle for role manager MBean.**

**Cause:** Could not get role manager object name.

**Action:** Check log files and correct the appropriate configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02529: Cannot obtain a handle for user manager MBean.**

**Cause:** Could not get user manager object name.

**Action:** Check log files and correct the appropriate configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02530: Cannot get a list of searchable attributes.**

**Cause:** Could not get searchable attributes.

**Action:** Check log files and correct the appropriate configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02531: Cannot get list of user property names.**

**Cause:** Could not get user property names.

**Action:** Check log files and correct the appropriate configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02532: Cannot parse principals of role.**

**Cause:** Could not parse role principals.

**Action:** Check log files and correct the appropriate configuration.

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**JPS-02533: Cannot parse principals of user.**

**Cause:** Could not parse user principals.

**Action:** Check log files and correct the appropriate configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02534: Cannot find role {0}.**

**Cause:** Could not complete search role operation.

**Action:** Correct the role name and, if necessary, contact the domain administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02535: Cannot complete search for roles.**

**Cause:** Could not complete search for multiple roles.

**Action:** Correct role names and, if necessary, contact the domain administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02536: Cannot complete search for user {0}.**

**Cause:** Could not complete user search.

**Action:** Correct user name and, if necessary, contact the domain administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02537: Cannot complete search for users.**

**Cause:** Could not complete search for multiple users.

**Action:** Correct user names and, if necessary, contact the domain administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02538: Cannot complete search operation.**

**Cause:** Failed to complete search.

**Action:** Correct the search query.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02539: Cannot change password of user {0}.**

---

**Cause:** Could not change password.  
**Action:** Contact the domain administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02540: User {0} not found in the identity store.**

**Cause:** User {0} not found in the identity store.

**Action:** Ensure user is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02541: Identity store has an invalid configured subscriber name.**

**Cause:** Found invalid subscriber name.

**Action:** Correct the configuration of property subscriber.name.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02542: unknown identity store service type {0}.**

**Cause:** Found unknown identity store service type {0}.

**Action:** Correct the identity store configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02543: Search type {0} is invalid.**

**Cause:** Found invalid search type {0}.

**Action:** Correct the type passed for the search.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**JPS-02544: Operation type {0} is invalid.**

**Cause:** Found invalid operation type {0}.

**Action:** Correct the type passed for the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**JPS-02545: Search filter type {0} is invalid.**

**Cause:** Found invalid search filter type {0}.

**Action:** Correct the type passed for the search filter.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**JPS-02546: Scope type is invalid {0}.**

**Cause:** Found invalid scope type {0}.

**Action:** Correct the type passed for the scope.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**JPS-02547: Cannot create realm {0}.**

**Cause:** Could not created realm.

**Action:** Check log files for error details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-02548: Cannot delete realm {0}.**

**Cause:** Could not delete realm.

**Action:** Check log files for error details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-02549: A realm with the specified name already exists.**

**Cause:** A realm with the specified name already exists.

**Action:** Choose a different realm name.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**JPS-02550: The realm {0} does not exist.**

**Cause:** Could not find realm with the name {0}.

**Action:** Correct the supplied realm name.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**JPS-02551: Cannot perform an unsupported operation on a serialized object.**

**Cause:** Could not perform operation on serialized object.

**Action:** Check log files for error details.

**Level:** 1

**Type:** TRACE

---

**Impact:** Requests/Responses

**JPS-02552: Cannot add a duplicate owner.**

**Cause:** Attempted to add already present owner.

**Action:** Correct the owner's name.

**Level:** 1

**Type:** TRACE

**Impact:** Data

**JPS-02553: Cannot remove an owner that is not present.**

**Cause:** Attempted to remove a non existing owner.

**Action:** Correct the owner's name.

**Level:** 1

**Type:** TRACE

**Impact:** Data

**JPS-02554: Cannot add a duplicate member.**

**Cause:** Attempted to add already present member.

**Action:** Correct the member's name.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**JPS-02555: Cannot complete identity store operation. The error is {0}.**

**Cause:** Could not perform identity store operation.

**Action:** Check error log files for details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-02556: Run into error {0} while using identity store.**

**Cause:** Run into an internal identity store error.

**Action:** Check error log files for details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-02557: The group {0} is invalid.**

**Cause:** Found null or invalid group.

**Action:** Correct the group's name.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-02558: Operation isOwnedBy failed.**



---

**Cause:** Could not perform operation isOwnedBy.

**Action:** Correct the owner's name.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02559: Operation isManagedBy failed.**

**Cause:** Could not perform operation isManagedBy.

**Action:** Correct the name.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02560: Cannot update role.**

**Cause:** Could not update role.

**Action:** Verify that the role name is correct and, if necessary, contact the domain administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02561: The realm entry {0} is missing in the identity store XML file.**

**Cause:** Could not find realm entry {0} in XML-based identity store.

**Action:** Ensure that the realm name is present in the XML-based identity store.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02562: Identity store entry is missing in the identity store XML file.**

**Cause:** Could not find identity store entry in XML-based identity store.

**Action:** Ensure that entry is present in the XML-based identity store.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02563: Length of the name attribute should be more than {0}.**

**Cause:** Found attribute name with less than {0} characters.

**Action:** Ensure that the length of the attribute name is at least the minimum length.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02564: Length of the name attribute should be less than {0}.**

---

**Cause:** Found attribute name with more than {0} characters.

**Action:** Ensure that the length of the attribute name is at most the maximum length.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02565: Name attribute contains invalid characters.**

**Cause:** Found invalid characters in attribute name.

**Action:** Ensure that attribute names have characters in the following sets only: [a-z], [A-Z], [0-9], ['.', '-', '\_].

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02566: The identity store config property {0} with value {1} is invalid.**

**Cause:** Found invalid identity store configuration property.

**Action:** Correct the configuration of the identity store property.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02567: The credential with map {0} and key {1} does not exist.**

**Cause:** Could not find credential with map and key names provided.

**Action:** Ensure that a credential with given map and key is present in the credential store.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02568: The password credential with map {0} and key {1} is invalid.**

**Cause:** Found invalid user name or password.

**Action:** Ensure that the user name and password in the credential store are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02569: Cannot find the XML file {0}.**

**Cause:** Could not find XML file for XML-based identity store {0}.

**Action:** Check the path of the XML file specified for the identity store.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**JPS-02570: XML file is unspecified.**

**Cause:** Could not determine XML file.

**Action:** Specify the XML file for the XML-based repository.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02571: The algorithm {0} to encode passwords is not supported.**

**Cause:** Found invalid password encoding algorithm.

**Action:** Specify a valid algorithm for password encoding.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02572: Caller does not have IdentityAssertion permission to execute this operation. Reason {0}.**

**Cause:** Caller did not have IdentityAssertion permission.

**Action:** Make sure the caller has IdentityAssertion permission to execute this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-02573: Cannot grant a role to itself.**

**Cause:** Attempted to grant a role to itself.

**Action:** Verify that no role is being granted to itself.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02574: Cannot delete default realm.**

**Cause:** Could not delete default realm.

**Action:** The default realm cannot be deleted: assign another realm as the default realm before deleting this one.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-02575: A user with the specified name does not exist.**

**Cause:** Could not find user with the specified name.

**Action:** Check the user name.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

---

**JPS-02576: A role with the specified name already exists.**

**Cause:** Role with the specified name already existed.

**Action:** Use a different role name.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**JPS-02577: A role with the specified name does not exist.**

**Cause:** Could not find role with the specified name.

**Action:** Check the role name.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**JPS-02578: The principal type {0} is invalid for the identity store type {1}.**

**Cause:** Found unsupported principal type {0} for identity store type {1}.

**Action:** Verify that principals have supported types.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**JPS-02579: Identity store type for application {0} is null or empty.**

**Cause:** Found null identity store type configured in identity store.

**Action:** Pass one of the following identity store types: XML, OID, ACTIVE\_DIRECTORY, IPLANET, EDIRECTORY, OPEN\_LDAP, COREID, OVD, or CUSTOM.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**JPS-02580: Cannot grant role {0} to {1} because it would lead to a cyclic dependency.**

**Cause:** Could not grant role {0} to {1}, because it would lead to a cyclic dependency.

**Action:** Revoke the grant which would create the cyclic dependency, and try again.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**JPS-02582: LDAP user or group search base is invalid.**

**Cause:** Found invalid LDAP user or group search base.

**Action:** Check that the user and group search base properties are valid.

**Level:** 1

**Type:** NOTIFICATION

---

**Impact:** Requests/Responses

**JPS-02583: JPS principal "{0}" with identity store type "{1}" cannot be created.**

**Cause:** JPS principal "{0}" with identity store type "{1}" cannot be created.

**Action:** Ensure the principal value is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-02584: JPS user name "{0}", principal type "{1}" with identity store type "{2}" cannot be created.**

**Cause:** JPS user name "{0}", principal type "{1}" with identity store type "{2}" cannot be created.

**Action:** Ensure the user value is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-02585: JPS enterprise role name "{0}", principal type "{1}" with identity store type "{2}" cannot be created.**

**Cause:** JPS enterprise role name "{0}", principal type "{1}" with identity store type "{2}" cannot be created.

**Action:** Ensure the enterprise role value is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-02586: JPS application role name "{0}", principal type "{1}" cannot be created.**

**Cause:** JPS application role name "{0}", principal type "{1}" cannot be created.

**Action:** Ensure the application role value is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-02587: Principal class "{0}", name "{1}" cannot be created.**

**Cause:** Principal class "{0}", name "{1}" cannot be created.

**Action:** Ensure the principal value is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-02588: Enterprise user principal "{0}" cannot be created.**

**Cause:** Enterprise user principal "{0}" cannot be created.

**Action:** Ensure the user principal value is valid.

**Level:** 1

---

**Type:** ERROR

**Impact:** Security

**JPS-02589: Enterprise role principal "{0}" cannot be created.**

**Cause:** Enterprise role principal "{0}" cannot be created.

**Action:** Ensure the role principal value is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-02590: Token type {0} cannot be supported. Supported types are: {1}.**

**Cause:** Token type {0} cannot be supported. Supported types are: {1}.

**Action:** Use the Supported types.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-02591: Guid {0} is assigned to principal {1}.**

**Cause:** Guid {0} is assigned to principal {1}.

**Action:** Check log for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-02592: Failed to push ldap config data to libOvd for IGFSservice "{0}" in JPS context "{1}", cause: {2}**

**Cause:** Failed to push ldap config data to libOvd for IGFSservice "{0}" in JPS context "{1}", cause: {2}

**Action:** Check libOvd log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-02593: Failed to get IGF UserManager or RoleManager instance from IGF API, cause: {0}**

**Cause:** Failed to get IGF UserManager or RoleManager instance from IGF API, cause: {0}

**Action:** Check IGF API or libOvd log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-02594: The IGFSservice "{0}" in JPS context "{1}" has no LDAP instance configured**

**Cause:** The IGFSservice "{0}" in JPS context "{1}" has no LDAP instance configured

---

**Action:** Check jps-config.xml to make sure the IGF service has either the IDStore instance defined, or use the WlsLdapIdStoreConfigProvider to get LDAP config from WLS Authentication providers.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-02595: The IGFSservice specified ldap "{0}" is not defined in the JPS service instances**

**Cause:** The IGFSservice specified ldap "{0}" is not defined in the JPS service instances

**Action:** Check jps-config.xml to make sure the specified ldap is defined as a JPS service instance.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-02596: The provider class type for the specified ldap instance "{0}" is configured as "{1}", which not the expected type of "oracle.security.jps.internal.idstore.ldap.LdapIdentityStoreProvider"**

**Cause:** The provider class type for the specified ldap instance "{0}" is configured as "{1}", which not the expected type of "oracle.security.jps.internal.idstore.ldap.LdapIdentityStoreProvider"

**Action:** Check jps-config.xml to make sure the provider type class for ldap instance is "oracle.security.jps.internal.idstore.ldap.LdapIdentityStoreProvider".

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-02597: You configured a custom Authentication Provider or WLS generic LDAPAuthenticator, which is a custom type and not supported by libOvd**

**Cause:** You configured a custom Authentication Provider or WLS generic LDAPAuthenticator, which is a custom type and not supported by libOvd

**Action:** The "idstore.type" property must be specified in jps-config.xml file as specific type such as OID, OVD etc. Alternatively, select a specific WLS LDAP Authentication provider that matches your LDAP server.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-02598: Pushed ldap name and types info to libOvd. Ldaps : {0}.**

**Cause:** libOvd is enabled so Ldap configuration info is passed to libOvd

**Action:** No action required

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

---

**JPS-03000: Cannot instantiate permission class "{0}", target "{1}", or actions "{2}" as defined in the application policy context "{3}".**

**Cause:** Could not load a permission class.

**Action:** Ensure that the class name is correct and available in the current class loader.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-03001: Cannot instantiate permission class "{0}", target "{1}", or actions "{2}" as defined in the system policy context.**

**Cause:** Could not load a class.

**Action:** Ensure that the class name is correct and is available in the current class loader.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-03004: Cannot log check authorization event to the audit service.**

**Cause:** Could not log check authorization events to the audit service.

**Action:** Ensure that auditing is configured correctly in your environment and application.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-03005: LDAP policy store contains invalid configuration parameters.**

**Cause:** Found invalid parameters in LDAP policy store configuration.

**Action:** Check the configuration of the LDAP policy store.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-03006: The name "{0}" of application role "{1}" is missing or invalid.**

**Cause:** Found missing or invalid name in application role.

**Action:** The internal identifier generated by the policy store seems malformed, due to an internal policy store error; contact Oracle Support Services.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-03008: Authorization check permission failed.**

**Cause:** Current Subject or source code did not have required permissions

**Action:** Provide the required permissions.

**Level:** 1



---

**Type:** WARNING

**Impact:** Security

**JPS-03012: Error occurred when computing application roles in application context {0} for subject {1}. Exception: {2}**

**Cause:** Error occurred when computing application roles in application context {0} for subject {1}. Exception: {2}

**Action:** Refer to the base exception in logs to resolve the issue.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-03013: Unsupported API method call.**

**Cause:** Unsupported API method call.

**Action:** Check the policy provider.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-03014: Failed to distribute policy by timer.**

**Cause:** Failed to distribute policy by timer.

**Action:** Check the log for more details or contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-03015: Resource-Actions '{0}' will be skipped in bulk authorization evaluation for Application: '{1}'.**

**Cause:** Application name not set in the resource-actions.

**Action:** Set the Application name in the resource-actions

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**JPS-03016: Resource-Actions '{0}' will be skipped in bulk authorization. Reason: '{1}'**

**Cause:** Failed to convert the Resource-Actions into a Permission instance.

**Action:** Check the logs for more information to resolve the error.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**JPS-03017: Failed to compute Application roles for Subject '{0}'. Reason '{1}'**

**Cause:** Unable to get the ApplicationRoles granted to a principal.

**Action:** Check the logs for more information to resolve the error.

**Level:** 1

---

Type: WARNING

Impact: Configuration

**JPS-03018: The authorization result is ignoring policies from application {0} as the application is not available**

**Cause:** The application is not available at runtime, or the application is not defined in the polystore.

**Action:** Check if the application is provisioned in the polystore.

Level: 1

Type: WARNING

Impact: Configuration

**JPS-03019: Policy evaluation in the application {0} failed. Reason: {1}**

**Cause:** Error occurred while evaluating policies.

**Action:** Refer to the logs to rectify the problem.

Level: 1

Type: WARNING

Impact: Configuration

**JPS-03020: Policy evaluation in the system policy failed. Reason: {0}**

**Cause:** Error occurred while evaluating system policies.

**Action:** Refer to the logs to rectify the problem.

Level: 1

Type: WARNING

Impact: Configuration

**JPS-03021: Admin Policy evaluation in the application {0} failed. Reason: {1}**

**Cause:** Error occurred while evaluating administrative policies.

**Action:** Refer to the logs to rectify the problem.

Level: 1

Type: WARNING

Impact: Configuration

**JPS-03150: Error during setting the field of a provider MBean. {0}**

**Cause:** Error during setting the field of a provider MBean. {0}.

**Action:** Refer to the log files for details and correct the error.

Level: 1

Type: ERROR

Impact: Security

**JPS-03151: getSecurityService returning null for requested service type of {0} for realm {1}**

**Cause:** getSecurityService returning null for requested service type of {0} for realm {1}.

**Action:** Refer to the log files for details and correct the error.

---

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-03152: Query Atz Cache specified but no response collector supplied**

**Cause:** Query Atz Cache specified but no response collector supplied.

**Action:** Supply the response collector in the request.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03153: Error parsing atz. cache flush time.**

**Cause:** Error parsing atz. cache flush time.

**Action:** Verify that the value is an integer.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03154: Authorization cache has been flushed. Time={0}**

**Cause:** Authorization cache has been flushed. Time={0}.

**Action:** No actions are required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

**JPS-03155: cannot locate class: {0}**

**Cause:** Cannot locate class: {0}.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03156: The exception has been thrown by ARME. The authorization result is set to deny.**

**Cause:** The exception has been thrown by ARME. The authorization result is set to deny.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03157: Error during initialization of the security framework.**

**Cause:** Error during initialization of the security framework.

**Action:** Refer to the log files for details and correct the error.

---

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03158: Failed to parse reesource cache size: {0}**

**Cause:** Failed to parse reesource cache size: {0}

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03159: Invalid built in type in Value object: {0}**

**Cause:** Invalid built in type in Value object: {0}

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03160: attempt to {0} value for type: {1}**

**Cause:** Attempt to {0} value for type: {1}

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03161: identifier not found in symbol table: {0}**

**Cause:** Identifier not found in symbol table: {0}

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03162: ERROR: PARSE: reason:==>**

**Cause:** ERROR: PARSE: reason:==>

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03163: invalid Declaration type received by setDeclType**

**Cause:** Invalid Declaration type received by setDeclType.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

---

**Impact:** Security

**JPS-03164: Got exception**

**Cause:** Got exception.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03165: Invalid declaration type found: {0}**

**Cause:** Invalid declaration type found: {0}.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03166: Unexpected PolicyParserTokenType: {0}**

**Cause:** Unexpected PolicyParserTokenType: {0}.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03167: Invalid attribute type: {0}**

**Cause:** Invalid attribute type: {0}.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-03168: Invalid attribute value type: {0}**

**Cause:** Invalid attribute value type: {0}.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-03169: Invalid configuration**

**Cause:** Invalid configuration.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03170: Try to get {0}, but JPS Policy tree is not available.**

---

**Cause:** Try to get {0}, but JPS Policy tree is not available.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03171: Unable to update policy: unable to get {0} instance**

**Cause:** Unable to update policy: unable to get {0} instance.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03172: Unspecified error in {0}**

**Cause:** Unspecified error in {0}.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03173: commit error: {0}**

**Cause:** Commit error: {0}.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03174: arme can not find state.chk file.**

**Cause:** ARME can not find state.chk file.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03175: !!!>>>Invalid mac found in write check, rewrite policies and mac**

**Cause:** !!!>>>Invalid mac found in write check, rewrite policies and mac

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03176: Failed to write check file.**

**Cause:** Failed to write check file.

**Action:** Refer to the log files for details and correct the error.

---

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03177: Failed to close check file writer**

**Cause:** Failed to close check file writer.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03178: Failed to write mac, which will cause Mac verification error in the future.**

**Cause:** Failed to write mac, which will cause Mac verification error in the future.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03179: Prepare request in invalid state for update**

**Cause:** Prepare request in invalid state for update.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03180: Error happens: {0}**

**Cause:** Error happened: {0}.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03181: ArmeRuntimeException happens**

**Cause:** ArmeRuntimeException happened.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03182: Cannot get AppGuardInstanceii, so cannot get information to request policy update from PD.**

**Cause:** Cannot get AppGuardInstanceii, so cannot get information to request policy update from PD.

**Action:** Refer to the log files for details and correct the error.

---

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03183: Internal error. The local PD registration is required but LocalPdPort object has not been set. The registration process cannot be completed.**

**Cause:** Internal error. The local PD registration is required but LocalPdPort object has not been set. The registration process cannot be completed.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03184: no host specified in the ARME configuration, attempting to determine host address...**

**Cause:** No host specified in the ARME configuration, attempting to determine host address...

**Action:** No actions are required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

**JPS-03185: No {0} found in the ARME configuration. Cannot contact PD**

**Cause:** No {0} found in the ARME configuration. Cannot contact PD.

**Action:** Verify configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03186: instanceName not found in arme configuration, using LocalName and host**

**Cause:** InstanceName not found in arme configuration, using LocalName and host.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03187: no {0} from ARME, unable to contact PD**

**Cause:** No {0} from ARME, unable to contact PD.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03188: Exception initializing SSL. Unable to contact PD**



---

**Cause:** Exception initializing SSL. Unable to contact PD.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03189: error getting attribute: {0}**

**Cause:** Error getting attribute: {0}.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03190: Failed to close File reader while reading salt.**

**Cause:** Failed to close File reader while reading salt.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03191: Could not obtain digest algorithm {0}**

**Cause:** Could not obtain digest algorithm '{0}'.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03192: index of ListValue is wrong**

**Cause:** Index of ListValue is wrong.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03193: PBEService is not initialized**

**Cause:** PBEService is not initialized.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03194: port is not number type**

**Cause:** Port is not number type.

**Action:** Verify that the port value is an integer.

---

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03195: can not get host IP information, use default IP address: {0}**

**Cause:** Cannot get host IP information, use default IP address: {0}.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03196: can not get host IP information.**

**Cause:** Cannot get host IP information.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03197: ARME shutdown failed: {0}**

**Cause:** ARME shutdown failed: {0}.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03198: can not get enablePerfStats from arme config file**

**Cause:** Cannot get enablePerfStats from arme config file.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03199: configuration file is [{0}]**

**Cause:** Configuration file is [{0}].

**Action:** No actions are required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

**JPS-03200: getDebugStore: IOException happens**

**Cause:** getDebugStore: IOException happens.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

---

**Impact:** Security

**JPS-03201: privilege name error: {0}**  
**Cause:** privilege name error: {0}.  
**Action:** Refer to the log files for details and correct the error.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Security

**JPS-03202: Resource name or application name invalid.**  
**Cause:** Resource name or application name invalid.  
**Action:** Refer to the log files for details and correct the error.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Security

**JPS-03203: resource name is wrong according to ALES naming logic**  
**Cause:** Resource name is wrong according to ALES naming logic.  
**Action:** Refer to the log files for details and correct the error.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Security

**JPS-03204: Invalid object name**  
**Cause:** Invalid object name.  
**Action:** Refer to the log files for details and correct the error.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Security

**JPS-03205: Logical name {0} is invalid**  
**Cause:** Logical name {0} is invalid.  
**Action:** Refer to the log files for details and correct the error.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Security

**JPS-03206: Logical name {0} is undefined**  
**Cause:** Logical name {0} is undefined.  
**Action:** Refer to the log files for details and correct the error.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Security

**JPS-03207: ioexception occurs when storing logical names {0}**

---

**Cause:** ioexception occurred when storing logical names {0}.  
**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03208: Logical names record is not correct**

**Cause:** Logical names record is not correct.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03209: objectTree is initialized properly**

**Cause:** ObjectTree is initialized properly.

**Action:** No actions are required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

**JPS-03210: can not close data files: {0}**

**Cause:** Cannot close data files: {0}.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03211: blocking queue is broken**

**Cause:** Blocking queue is broken.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03212: Session data could not be loaded. Session abandoned**

**Cause:** Session data could not be loaded. Session abandoned.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03213: args value is null or wrong type**

**Cause:** Args value is null or wrong type.

**Action:** Refer to the log files for details and correct the error.

---

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03214: Could not add attribute(s) to cache**

**Cause:** Could not add attribute(s) to cache.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-03215: caught BadParameterException while get attribute: {0}**

**Cause:** Caught BadParameterException while getting attribute: {0}.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03216: Installing custom retriever: {0}**

**Cause:** Installing custom retriever: {0}.

**Action:** No actions are required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

**JPS-03217: Caught exception while retrieving attribute from context: {0} Continue retrieving static attribute value.**

**Cause:** Caught exception while retrieving attribute from context: {0} Continue retrieving static attribute value.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03218: failed to transport AttributeValue to AttributeElement, caught {0}: {1}**

**Cause:** Failed to transport AttributeValue to AttributeElement, caught {0}: {1}.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03219: AttributeValue type error, not single and list, return null**

**Cause:** AttributeValue type error, not single and list, return null.

**Action:** Refer to the log files for details and correct the error.

---

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03220: Exception from the LDAP server, code: {0}, trying alternate connection**

**Cause:** Exception from the LDAP server, code: {0}, trying alternate connection.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-03221: Alternate LDAP connection failed, code: {0}**

**Cause:** Alternate LDAP connection failed, code: {0}.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03222: Null extendedContext is passed to attribute retriever, cannot look for value.**

**Cause:** Null extendedContext is passed to attribute retriever, cannot look for value.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-03223: Caught exception while retrieving attribute: {0}**

**Cause:** Caught exception while retrieving attribute: {0}.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03224: Parameter value is null or wrong type.**

**Cause:** Parameter value is null or wrong type.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03225: Calling RBACEvals:{0}**

**Cause:** Calling RBACEvals:{0}.

**Action:** No actions are required.

---

**Level: 1**

**Type: NOTIFICATION**

**Impact: Security**

**JPS-03226: Empty Application name or Obligation name is passed to report\_obligation function.**

**Cause:** Empty Application name or Obligation name is passed to report\_obligation function.

**Action:** Refer to the log files for details and correct the error.

**Level: 1**

**Type: ERROR**

**Impact: Security**

**JPS-03227: Unexpected error: invalid parameter instances.**

**Cause:** Unexpected error: invalid parameter instances.

**Action:** Refer to the log files for details and correct the error.

**Level: 1**

**Type: ERROR**

**Impact: Security**

**JPS-03228: args is null**

**Cause:** args is null.

**Action:** Refer to the log files for details and correct the error.

**Level: 1**

**Type: ERROR**

**Impact: Security**

**JPS-03229: Error during initialization of RetrieverConfiguration.**

**Cause:** Error during initialization of RetrieverConfiguration.

**Action:** Refer to the log files for details and correct the error.

**Level: 1**

**Type: ERROR**

**Impact: Security**

**JPS-03230: args value type is null or wrong type value**

**Cause:** args value type is null or wrong type value.

**Action:** Refer to the log files for details and correct the error.

**Level: 1**

**Type: ERROR**

**Impact: Security**

**JPS-03231: {0} supplied to subject\_in\_group is not a qualified group, will qualify**

**Cause:** {0} supplied to subject\_in\_group is not a qualified group, will qualify.

**Action:** Refer to the log files for details and correct the error.

---

**Level: 1**

**Type: ERROR**

**Impact: Security**

**JPS-03232: qualified group is {0}**

**Cause:** qualified group is {0}.

**Action:** Refer to the log files for details and correct the error.

**Level: 1**

**Type: ERROR**

**Impact: Security**

**JPS-03233: args should be String[]**

**Cause:** args should be String[].

**Action:** Refer to the log files for details and correct the error.

**Level: 1**

**Type: ERROR**

**Impact: Security**

**JPS-03234: No value is passed to {0}**

**Cause:** No value is passed to {0}.

**Action:** Refer to the log files for details and correct the error.

**Level: 1**

**Type: ERROR**

**Impact: Security**

**JPS-03235: No attribute name is passed to sys\_obj\_exists**

**Cause:** No attribute name is passed to sys\_obj\_exists.

**Action:** Refer to the log files for details and correct the error.

**Level: 1**

**Type: ERROR**

**Impact: Security**

**JPS-03236: Failed to get attribute {0} for eval function {0}**

**Cause:** Failed to get attribute {0} for eval function {0}.

**Action:** Refer to the log files for details and correct the error.

**Level: 1**

**Type: ERROR**

**Impact: Security**

**JPS-03237: value passed to {0} is not valid, {1}**

**Cause:** Value passed to {0} is not valid, {1}.

**Action:** Refer to the log files for details and correct the error.

**Level: 1**

**Type: ERROR**



---

**Impact:** Security

**JPS-03238: {0} is not a valid value for {1}**

**Cause:** {0} is not a valid value for {1}.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03239: valid\_timeval called for unexpected eval function {0}**

**Cause:** valid\_timeval called for unexpected eval function {0}.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03240: unknown eval function {0} used in valid\_until\_timeofday**

**Cause:** Unknown eval function {0} used in valid\_until\_timeofday.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03241: Disabling extended performance data...**

**Cause:** Disabling extended performance data...

**Action:** No actions are required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

**JPS-03242: The extended performance data have been retrieved. The total number of attributes is {0}, the total number of functions is {1}.**

**Cause:** The extended performance data have been retrieved. The total number of attributes is {0}, the total number of functions is {1}.

**Action:** No actions are required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

**JPS-03243: Unexpected mbean attribute get method: {0}**

**Cause:** Unexpected mbean attribute get method: {0}.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

---

**Impact:** Security

**JPS-03244: {0} specified but no response collector supplied**

**Cause:** {0} specified but no response collector supplied.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03245: received {0} in isProtectedResource**

**Cause:** Received {0} in isProtectedResource.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03246: null role object passed into wles atz provider, ignoring**

**Cause:** Null role object passed into wles atz provider, ignoring.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03247: A SecurityRole object passed to the authorization engine has role name equal to null. The object will be ignored. The string representation of the object is {0}.**

**Cause:** A SecurityRole object passed to the authorization engine has role name equal to null. The object will be ignored. The string representation of the object is {0}.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03248: Error {0}**

**Cause:** Error {0}.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03249: ASI shutdown failed**

**Cause:** ASI shutdown failed.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

---

**Type:** ERROR

**Impact:** Security

**JPS-03250: getInstance: Warning: The parent classloaders are different.**

**Cause:** getInstance: Warning: The parent classloaders are different.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03251: addClassJars: {0}**

**Cause:** addClassJars: {0}.

**Action:** Refer to the log files for details.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03252: Missing JAR file: {0}**

**Cause:** Missing JAR file: {0}.

**Action:** Refer to the log files for details.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03253: Error initializing URLs in classloader. Vector: {0}**

**Cause:** Error initializing URLs in classloader. Vector: {0}.

**Action:** Refer to the log files for details.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03254: lazy getRoles failed with error {0}**

**Cause:** lazy getRoles failed with error {0}.

**Action:** Refer to the log files for details.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03255: null value returned in roles list, ignoring**

**Cause:** null value returned in roles list, ignoring.

**Action:** Refer to the log files for details.

**Level:** 1

**Type:** ERROR

**Impact:** Security

---

**JPS-03256: Internal error. Method queryRoles has returned role {0} that starts with an incorrect prefix for a role. The role will be ignored.**

**Cause:** Internal error. Method queryRoles has returned role {0} that starts with an incorrect prefix for a role. The role will be ignored.

**Action:** Refer to the log files for details.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03257: passed an non URLResource, in getAttributeValue**

**Cause:** Passed a non URLResource, in getAttributeValue.

**Action:** Refer to the log files for details.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03258: Initializing UserUtils; {0}**

**Cause:** Initializing UserUtils; {0}.

**Action:** No actions are required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

**JPS-03259: Invalid built in type received**

**Cause:** Invalid built in type received.

**Action:** Refer to the log files for details.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-03260: Attempt to {0} when CRED is wrong type**

**Cause:** Attempt to {0} when CRED is wrong type.

**Action:** Refer to the log files for details.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-04000: Cannot get the default policy store.**

**Cause:** Could not find to the default policy store.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** WARNING

**Impact:** Security

---

**JPS-04001: Cannot read the default policy store.**

**Cause:** Could not read the default policy store.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04002: Cannot get application policy for application "{0}".**

**Cause:** Encountered a policy store internal error.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04003: Duplicate principal present "{0}" in a grant request.**

**Cause:** Found that list of principals in the grantee for the grant contains duplicate

**Action:** Correct the list of principals in the grantee.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04004: Duplicate permission present "{0}" in a grant request.**

**Cause:** Found that list of permissions in the grant contains duplicate.

**Action:** Correct the list of permissions in the grant.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04021: Cannot create application policy context "{0}".**

**Cause:** Encountered two application policy contexts with identical names.

**Action:** Modify an application policy context to have a distinct name.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04022: Cannot create application policy context "{0}".**

**Cause:** Failed to complete persist operation while creating an application policy.

**Action:** Refer to the base exception in log files and correct the error.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04026: Cannot delete application policy context "{0}".**

**Cause:** Could not find a policy context with the provided name.

---

**Action:** Verify that a context with the provided name exists.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04027: Role with name "{0}" does not exist.**

**Cause:** Could not find a role with name {0}.

**Action:** Verify that a role with the provided name exists.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04028: Application with name "{0}" does not exist.**

**Cause:** Could not find application with name {0}.

**Action:** Verify that an application with the provided name exists.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04029: Cannot create principal with class name "{0}".**

**Cause:** Could not create principal with class name {0}.

**Action:** Verify that the provided class name is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04030: Cannot delete application policy context "{0}".**

**Cause:** Failed to complete persist operation while deleting an application policy.

**Action:** Refer to the base exception in log files and correct the error.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04031: Parameter "{0}" is null.**

**Cause:** Supplied parameter {0} was null.

**Action:** Verify that the supplied parameter is non-null. If it is of type String, ensure that its length is positive.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04032: Parameter "{0}" supplied is not the instance of "{1}".**

**Cause:** Parameter {0} supplied is not the instance of {1}.

**Action:** Ensure parameter is of correct datatype.

---

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04033: Parameter "{0}" supplied is not of the type "{1}" (as expected).**

**Cause:** Parameter {0} supplied is not of the type {1} (as expected).

**Action:** Ensure parameter is of correct datatype.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04034: Failed to modify properties for Application "{0}".**

**Cause:** Cannot modify application policy.

**Action:** Check the logs for errors.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04035: AttributeName {0} supplied should start with alphabet or an underscore.**

**Name cannot contain characters contain other than alphanumeric and/or underscores.**

**Cause:** AttributeName {0} supplied should start with alphabet or an underscore.  
Name cannot contain characters contain other than alphanumeric and/or underscores.

**Action:** Ensure attribute name is of correct datatype.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04036: Function Name {0} supplied should start with alphabet or an underscore.**

**Name cannot contain characters contain other than alphanumeric and/or underscores.**

**Cause:** Function Name {0} supplied should start with alphabet or an underscore.  
Name cannot contain characters contain other than alphanumeric and/or underscores.

**Action:** Ensure function name is of correct datatype.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04037: Name '{0}' starts or ends with whitespace.**

**Cause:** Object name should not start with or end with whitespace.

**Action:** Ensure object name has no whitespace in the beginning and end.

**Level:** 1

**Type:** WARNING

---

**Impact:** Security

**JPS-04080: Scanning of system policy failed. Reason {0}**

**Cause:** Scan of system policy failed.

**Action:** Check the system policy setup and the provider setup.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04081: Policy store purge thread interrupted. Reason {0}.**

**Cause:** Purge thread interrupted in policy caching.

**Action:** Check the policy setup and the provider setup

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04082: Deletion of system policy failed. Reason {0}**

**Cause:** Deletion of system policy failed.

**Action:** Provide legal non empty values for policy name

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04083: Creation of system policy failed. Reason {0}**

**Cause:** Creation of system policy failed.

**Action:** Provide legal non empty values for policy name

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04084: Migration of application policy failed. Reason: {0}.**

**Cause:** Exception in migration of application policy

**Action:** Check application policy setup or contact system administrator

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04085: Migration of codebase policy failed. Reason: {0}.**

**Cause:** Exception in migration of codebase policy

**Action:** Check codebase policy setup or contact system administrator

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04086: Could not perform isPolicyModified. Reason {0}**



---

**Cause:** Is policy modification check failed.

**Action:** Contact system administrator

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04089: Could not get policy cache count. Reason {0}**

**Cause:** Could not retrieve policy cache count.

**Action:** Contact system administrator

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04090: The policy store property {0} is invalid or not defined.**

**Cause:** The policy store property {0} was invalid or not defined.

**Action:** Check the configuration of this property.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-04091: Application {0} is being deployed with policy migration option set to {1}, start policy migration.**

**Cause:** Start application policy migration

**Action:** No action required

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

**JPS-04092: Application {0} is being deployed with policy migration option set to neither OVERWRITE nor MERGE, skip policy migration.**

**Cause:** Skip application policy migration

**Action:** No action required

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

**JPS-04093: Application policy migration for application {0} is completed successfully.**

**Cause:** Complete application policy migration

**Action:** No action required

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

---

**JPS-04094: Start removing application policies for Application {0}.**

**Cause:** Start application policy removal

**Action:** No action required

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

**JPS-04095: Application policy removal for application {0} is completed successfully.**

**Cause:** Complete application policy removal

**Action:** No action required

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

**JPS-04096: Application policies for application {0} was NOT removed in application undeployment with jps.policystore.removal set to OFF.**

**Cause:** Skip application policy removal

**Action:** No action required

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

**JPS-04097: Application {0} is being deployed without existing application policies found in static deployment, start policy migration.**

**Cause:** Start application policy migration in static deployment

**Action:** No action required

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

**JPS-04098: Start codebase policy migration for application {0}.**

**Cause:** Start codebase policy migration

**Action:** No action required

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

**JPS-04099: Codebase policy migration for {0} is completed successfully.**

**Cause:** Complete codebase policy migration

**Action:** No action required

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

---

**JPS-04100: Cannot create application role "{0}".**

**Cause:** Encountered two roles with identical names.

**Action:** Modify a role to have a distinct name.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04101: Cannot create application role "{0}".**

**Cause:** Failed to complete persist operation while creating an application role.

**Action:** Refer to the base exception in logs to resolve the issue.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04102: Cannot create application role. Cause: Invalid Argument -- Multiple role categories supplied for single application role**

**Cause:** Persist operation failed because more than one role category supplied for create role

**Action:** Ensure supplied parameters are correct.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04110: Cannot delete application role "{0}". Cause: Application role not found.**

**Cause:** Could not find an application role in the application policy.

**Action:** Check the name of the application role.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04111: Cannot delete application role "{0}".**

**Cause:** Could not remove application role from policy store.

**Action:** Refer to the base exception in log files and correct the error.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04112: Cannot delete application role "{0}".**

**Cause:** Could not remove application role "{0}" because it may be in use; this role is a member of one or more other application roles (nested role hierarchy).

**Action:** Flatten the nested role hierarchy, and then remove the desired role. Alternatively, remove the application role using the option force set to true.

**Level:** 1

**Type:** WARNING

---

**Impact:** Security

**JPS-04113: Cannot delete application role "{0}".**

**Cause:** Could not remove application role "{0}" because it may be in use, or contains enterprise groups or enterprise users.

**Action:** Remove the enterprise groups and enterprise users from the application role, or remove the application role using the option force set to true.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04114: Cannot delete application role "{0}".**

**Cause:** Could not remove application role "{0}" because it may be in use; this role has one or more permissions granted to it.

**Action:** Revoke the permission(s) from the application role, and then remove the role. Alternatively, remove the application role using the option force set to true.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04120: Cannot add principal to application role.**

**Cause:** Encountered an internal policy store error.

**Action:** Refer to the base exception in log files and correct the error.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04121: Cannot add principal to application role.**

**Cause:** Could not find application role in the application policy context.

**Action:** Ensure the application role is present in the application policy.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04122: Cannot add principal to application role.**

**Cause:** Found that principal {0} is already a member of the application role {1}.

**Action:** Correct the principal name.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04123: Cannot add principal to the application role.**

**Cause:** Attempted to insert an application role as a member of itself.

**Action:** Correct the application role principal name. The containment in the role hierarchy must be cycle-free.

---

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04124: The application role {0} added to {1} has no GUID defined.**

**Cause:** The application role {0} added to {1} has no GUID defined.

**Action:** Ensure the application role has GUID before adding it as a member of an application role.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-04125: Application Role {0} granted to role category {1} cannot be found in application {2}**

**Cause:** Application Role {0} granted to role category {1} cannot be found in application {2}

**Action:** Ensure application role exists before assigning it to a role category

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04130: Cannot remove principal from application role.**

**Cause:** Encountered an internal policy store error.

**Action:** Refer to the base exception in log files and correct the error.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04131: Cannot remove principal from application role; cannot find application role "{0}" in application policy context.**

**Cause:** Could not find the specified application role in the application policy context.

**Action:** Correct the application role name.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04132: Cannot remove principal from application role; principal "{0}" is not member of application role "{1}".**

**Cause:** See error message.

**Action:** Correct the principal role name.

**Level:** 1

**Type:** WARNING

**Impact:** Security

---

**JPS-04140: Cannot complete application role search because search expression "{0}" is incorrect.**

**Cause:** Found an invalid search pattern.

**Action:** Refer to the base exception in log files and correct the error.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04141: Cannot complete application role search because of internal error {0}.**

**Cause:** Encountered an internal policy store error while searching the policy store.

**Action:** Refer to the base exception in log files and correct the error.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04142: Cannot complete application role search because search role attribute "{0}" is incorrect.**

**Cause:** Could not complete the search because the application role attribute {0} was invalid.

**Action:** Supply a valid role attribute name.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04143: Cannot find application role "{0}".**

**Cause:** Could not find application role in the application policy context.

**Action:** Supply the name of an existing application role name.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04144: Cannot get granted application role for principal "{0}".**

**Cause:** Encountered an internal policy store error.

**Action:** Refer to the base exception in log files and correct the error.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04145: Cannot get all application roles for application "{0}".**

**Cause:** Encountered an internal policy store error.

**Action:** Refer to the base exception in log files and correct the error.

**Level:** 1

**Type:** WARNING

**Impact:** Security

---

**JPS-04146: Cannot complete application role search because search role attribute name is null.**

**Cause:** Could not complete the search because the role attribute name was NULL.

**Action:** Provide a non-null role attribute name.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04147: Cannot get members of application role "{0}".**

**Cause:** Could not find application role in the application policy context.

**Action:** Supply the name of an existing application role name.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04150: Cannot alter application role.**

**Cause:** Encountered the policy store error {0}.

**Action:** Check the error details to resolve the issue.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04151: Cannot alter application role.**

**Cause:** Could not find application role {0} in the application policy context.

**Action:** Provide an existing application role name.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04154: Refresh of application policy failed. Reason {0}**

**Cause:** Refresh of application policy failed.

**Action:** Check the application policy setup and the provider setup

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04155: Scanning of application policy failed. Reason {0}**

**Cause:** Scan of application policy failed.

**Action:** Check the application policy setup and the provider setup

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04156: RoleCategory modification attribute "{0}" is invalid.**

---

**Cause:** Invalid RoleCategory modify attribute

**Action:** Check whether the attribute you are trying to modify is valid or not.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04160: Cannot find PermissionSet {0}.**

**Cause:** Could not find PermissionSet in policy store.

**Action:** Provide the name of a valid PermissionSet.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04161: Search for PermissionSet {0} by name yielded more than one result.**

**Cause:** Found a duplicate PermissionSet name in search context.

**Action:** Ensure that all PermissionSet names in the current search context are distinct.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04162: PermissionSet {0} already exists in policy store.**

**Cause:** Permission Set already exists.

**Action:** Create a PermissionSet with a different name.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04163: PermissionSet {0} cannot have empty ResourceActions.**

**Cause:** PermissionSet {0} has empty ResourceActions.

**Action:** Ensure PermissionSet has ResourceActions.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04164: Resource {0} referenced by MemberResources not found in application {1}.**

**Cause:** Resource {0} referenced by MemberResources not found in application {1}.

**Action:** Ensure the Resource exists in the PolicyStore.

**Level:** 1

**Type:** WARNING

**Impact:** Security



---

**JPS-04165: ResourceType {0} referenced by MemberResource {1} not found in application {2}.**

**Cause:** ResourceType {0} referenced by MemberResource {1} not found in application {2}.

**Action:** Ensure the ResourceType exists in the PolicyStore.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04166: MemberResource {0} of type {1} does not have actions defined.**

**Cause:** MemberResource {0} of type {1} does not have actions defined.

**Action:** Ensure the MemberResource has valid actions.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04167: MemberResource {0} of type {1} has actions defined.**

**Cause:** MemberResource {0} of type {1} has actions defined.

**Action:** Ensure the MemberResource does not have actions.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04168: PermissionSet {0} cannot be created without ResourceActions.**

**Cause:** PermissionSet {0} cannot be created without ResourceActions.

**Action:** Create a PermissionSet with ResourceActions.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04169: ResourceAction {0} used to modify PermissionSet {1} has invalid actions for ResourceType {2}.**

**Cause:** ResourceAction {0} used to modify PermissionSet {1} has invalid actions for ResourceType {2}.

**Action:** Modify PermissionSet using a ResourceAction that has valid actions.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04173: The resource type {0} is not found in store**

**Cause:** Unsupported Resource Type {0}.

**Action:** Check Resource Type.

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**JPS-04190: Cannot find resource.**

**Cause:** Could not find resource in the resource store.

**Action:** Modify your search query.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04191: Cannot find unregistered resource finder for resource type "{0}".**

**Cause:** Could not find a registered resource finder for the resource type.

**Action:** Provide a resource finder implementation for the resource type, and register it with JPS.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04192: Cannot load resource finder with provider name "{0}".**

**Cause:** Found an incorrect implementation: argumentless public constructor is missing.

**Action:** Revisit the implementation to provide an argumentless public constructor.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04193: Cannot load resource finder with provider name "{0}" and class "{1}".**

**Cause:** Could not load resource finder class: error encountered while reading a registered class file for resource finder.

**Action:** Check the configuration of the class property in jps-config.xml.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04194: Cannot initialize resource finder with provider name "{0}" and class name "{1}".**

**Cause:** Found an error while initializing a registered class for resource finder.

**Action:** Check the configuration of the class property in jps-config.xml.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04195: Cannot load the resource finder with provider "{0}".**

**Cause:** Found an error in external resource finder configuration: a required property was missing.

**Action:** Check the configuration of the class property in jps-config.xml.

---

**Level: 1**

**Type: WARNING**

**Impact: Security**

**JPS-04200: Cannot grant policy due to a policy store internal error.**

**Cause:** Encountered a policy store error.

**Action:** Check the error details to resolve the issue.

**Level: 1**

**Type: WARNING**

**Impact: Security**

**JPS-04201: Cannot grant permission(s). Grant already exists for grantee {0}.**

**Cause:** Permissions already granted to grantee.

**Action:** Grant a different set of permissions.

**Level: 1**

**Type: WARNING**

**Impact: Security**

**JPS-04202: Cannot revoke policy.**

**Cause:** Encountered an internal policy store error while revoking a policy.

**Action:** Refer to the base exception in log files and correct the error.

**Level: 1**

**Type: WARNING**

**Impact: Security**

**JPS-04203: Cannot revoke permission.**

**Cause:** Found that a permission has not been granted.

**Action:** Provide the appropriate permission to the grantee.

**Level: 1**

**Type: WARNING**

**Impact: Security**

**JPS-04204: Cannot revoke permissions.**

**Cause:** Found that permissions have not been granted.

**Action:** Provide the appropriate permissions to the grantee.

**Level: 1**

**Type: WARNING**

**Impact: Security**

**JPS-04205: Cannot revoke permissions.**

**Cause:** Found that permissions have not been granted to principals.

**Action:** Provide the appropriate permissions to principals.

**Level: 1**

**Type: WARNING**

---

**Impact:** Security

**JPS-04206: Cannot revoke permissions.**

**Cause:** Found that permissions have not been granted to code source.

**Action:** Correct the code source grantee.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04207: Cannot revoke permissions.**

**Cause:** Found that permissions have not been granted to principals or code source.

**Action:** Correct the list of principals and code source in the grantee, or revoke permissions granted to this grantee.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04208: Cannot modify policy due to a policy store internal error.**

**Cause:** Encountered an internal policy store error while modifying the policy store.

**Action:** Refer to the base exception in log files and correct the error.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04209: Cannot modify property {0}.**

**Cause:** Could not modify a property.

**Action:** Supply the name of a property that can be modified.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04210: Modification code {0} is invalid.**

**Cause:** Found an unsupported modification code.

**Action:** Ensure that the modification code is ADD, REMOVE, or REPLACE.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04211: Cannot query, update, or delete Object with type "{0}" and name "{1}".**

**Cause:** Attempted to query, update, or delete an invalid policy store object.

**Action:** Ensure that the object to be queried, updated, or deleted belongs to the appropriate policy domain

**Level:** 1

---

Type: WARNING

Impact: Security

**JPS-04212: PermissionSet "{0}" is in use, cannot delete.**

**Cause:** Permission set already existed.

**Action:** Permission set with the same name cannot be created. Use different name.

Level: 1

Type: WARNING

Impact: Security

**JPS-04213: Cannot modify a grant with an empty permission entry.**

**Cause:** Encountered empty permission entry list while modifying a grant

**Action:** Pass a non empty permission entry list while modifying a grant

Level: 1

Type: WARNING

Impact: Security

**JPS-04216: Cannot grant/revoke permissions because type "{0}" is not known.**

**Cause:** Resource type validation for Permission set failed

**Action:** Check whether the grant's permission's resourcetype is provisioned in the polycystore.

Level: 1

Type: WARNING

Impact: Security

**JPS-04217: Grant/revoke failed for grantee "{0}", permission class "{1}", resource name "{2}", permission actions "{3}", resource type "{4}". Reason: permission actions is not a subset of resource type actions "{5}".**

**Cause:** Resource type validation for Permission set failed

**Action:** Check whether the actions in the Permission are valid actions for the resource type provisioned in the policy store.

Level: 1

Type: WARNING

Impact: Security

**JPS-04218: Grant/revoke failed for grantee "{0}", permission class "{1}", resource Name "{2}", permission actions "{3}", resource type "{4}". Reason: permission class is not equal to resource type matcher class "{5}".**

**Cause:** Resource type validation for Permission set failed

**Action:** Check whether the matcher class in the Permission is valid for the resource type provisioned in the policy store.

Level: 1

Type: WARNING

Impact: Security

**JPS-04219: The action {0} is invalid for resource type {1}.**

---

**Cause:** The action {0} is invalid for resource type {1}.

**Action:** Check the ResourceActionsEntry parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-04220: Cannot search because the search query "{0}" was empty (has no child query).**

**Cause:** The search query {0} was empty (has no child query).

**Action:** Provide a non-empty search query in.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-04221: Cannot search because the grant search query "{0}" has illegal object type for search property "{1}".**

**Cause:** The grant search query {0} has wrong object type in search value for search property {1}.

**Action:** Provide an object type corresponding to the search property.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04227: The object name {0} is invalid.**

**Cause:** The object name {0} is invalid.

**Action:** Pass a correct object name in.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-04300: Cannot save policy.**

**Cause:** Could not save policy. Cause {0}.

**Action:** Check the log files and resolve the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-04301: Cannot read from policy store.**

**Cause:** Could not read from the policy store.

**Action:** Check the log files and resolve the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

---

**JPS-04302: Cannot read from policy store.**

**Cause:** Could not find the location property {1} in instance {0}.

**Action:** Ensure the location is set to a valid policy store file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04303: Cannot read from policy store.**

**Cause:** Could not find value for system property '{0}' or for location property '{2}' in instance '{1}'.

**Action:** Ensure the location is set to a valid policy store file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04304: Policy store instance descriptor {0}, location value {1} is ignored.**

**Cause:** Could not find value for the system property '{0}', which overrides the descriptor property {1} in the policy store service instance.

**Action:** Unset the system property so that the location is picked up from configuration in jps-config.xml.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**JPS-04410: Cannot create JACC module policy context "{0}" for application {1}.**

**Cause:** Could not create application policy because found two application module contexts with identical names.

**Action:** Ensure that all application module context names are distinct.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04411: Cannot create application "{0}" JACC module policy context "{1}".**

**Cause:** Could not create application module policy; persist operation failed.

**Action:** Refer to the base exception in log files and correct the error.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04412: Cannot delete JACC module "{0}".**

**Cause:** Could not find JACC policy context to delete.

**Action:** Check the JACC policy context name.

**Level:** 1

**Type:** WARNING

---

**Impact:** Security

**JPS-04413: Cannot delete JACC module policy context "{0}".**

**Cause:** Could not delete JACC policy; persist operation failed.

**Action:** Refer to the base exception in log files and correct the error.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04420: Application policy context name is missing from application role {0}.**

**Cause:** Could not find application policy context in the application role principal.

**Action:** Ensure that the application role principal has an application context.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04421: Administrator role name is invalid.**

**Cause:** Found an invalid administrator role name.

**Action:** Correct the name of the administrator role.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04422: Policy is malformed.**

**Cause:** Found system policy that granted permissions to application role(s).

**Action:** Grants to application roles are not allowed in a system policy. Remove such grants.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04423: Application role name is invalid.**

**Cause:** Found invalid application role name {0}.

**Action:** Verify that the application role name conforms with the role name syntax.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04502: Java SSO Login**

**Cause:** This was JSSO page title.

**Action:** No action needed.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses



---

**JPS-04503: Enter your single sign-on username and password.**

**Cause:** User name and password were required for logging into JSSO.

**Action:** Enter a valid user name and password.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**JPS-04504: Username**

**Cause:** This was JSSO login user name.

**Action:** No action needed.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**JPS-04505: Password**

**Cause:** This was JSSO login user password.

**Action:** No action needed.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**JPS-04508: Failed.**

**Cause:** JSSO login failed.

**Action:** Check user name and password used for login.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-04512: application error**

**Cause:** Encountered and internal error.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-04513: The Java SSO application is not properly configured.**

**Cause:** The Java SSO application was not correctly configured.

**Action:** Reconfigure the application.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04522: The authentication type {0} is invalid.**

**Cause:** JSSO did not support this authentication type.

---

**Action:** Reconfigure the type to a supported type.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04523: Token is no longer valid.**

**Cause:** The incoming token was no longer valid.

**Action:** Login again.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-04524: Cannot create token from JSSO cookie.**

**Cause:** Could not create token from the JSSO cookie; cookie may have expired.

**Action:** Login again.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-04528: An error occurred while encoding JSSO token.**

**Cause:** Could not encode JSSO token.

**Action:** Specify a valid, supported encoding.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04530: Algorithm is unsupported.**

**Cause:** Specified algorithm was unsupported.

**Action:** Check documentation for the list of supported algorithms.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04531: Error creating cipher.**

**Cause:** Could not create cipher.

**Action:** Check documentation for the list of supported cipher algorithms.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04532: JSSO logout URL is not configured.**

**Cause:** The logout URL was not configured or invalid.

**Action:** Check the logout URL configuration properties, and reconfigure it to a valid URL.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04533: JSSO has encountered an unexpected error.**

**Cause:** An internal error occurred.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-04534: JSSO symmetric key is missing.**

**Cause:** The symmetric key configuration was missing.

**Action:** Ensure that the properties "custom.sso.cred.key" and "custom.sso.cred.alias" are configured in the service instance, and that the symmetric key is present in the credential store.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04535: Identity name is invalid.**

**Cause:** User identity was invalid or missing.

**Action:** Provide a valid user identity.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04536: The token name {0} is missing in request object.**

**Cause:** Token name was missing in the request object.

**Action:** Ensure that the token name is present in the request object.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04537: No token name is specified for token collector {0}.**

**Cause:** Token collector was invalid or missing.

**Action:** Configure a valid token collector with the property "idm.token.collector.class".

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04538: The request object class is invalid.**

**Cause:** The request object class was invalid.

**Action:** Ensure that the request object is valid.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04539: Token collector is not properly initialized.**

**Cause:** Could not initialize the token collector.

**Action:** Ensure that the token collector is correctly configured and initialized.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04540: The tokenasserter is not properly initialized.**

**Cause:** Could not initialize the tokenasserter.

**Action:** Ensure that the tokenasserter is correctly configured and initialized.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04541: Cannot find authenticated identity.**

**Cause:** Authentication failed.

**Action:** Provide a valid identity.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04542: The token collector class {0} is not properly configured in the configuration file.**

**Cause:** Token collector class was missing.

**Action:** Configure a valid token collector class with the property "idm.token.collector.class".

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04543: No login module is configured for application.**

**Cause:** Could not find configured login module.

**Action:** Configure a login module in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04544: The subject of the identity is invalid.**

**Cause:** Subject was missing.

**Action:** Ensure that the valid Subject is present.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04545: Cannot verify the Subject {0}.**

**Cause:** Could not verify Subject.

**Action:** Check the user credentials.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04546: The configuration (idm.subject.loginmodule.disabled=true) specifies that the Subject is populated by the token assertter.**

**Cause:** Could not find Subject assertter.

**Action:** Configure an assertter to use a login module that returns a valid Subject.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04547: The token type {0} is not properly configured in the configuration file.**

**Cause:** Could not find token type configuration.

**Action:** Configure a token type in the service instance with the property "idm.token.type property".

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04548: The token assertter class {0} is not properly configured in the configuration file.**

**Cause:** Could not find token assertter class configuration.

**Action:** Configure a token assertter class in the service instance with the property "idm.token.assertter.class".

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04549: Token is no longer valid.**

**Cause:** Found invalid or expired token.

**Action:** Check that the token is valid and has not expired.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04550: Token type is invalid: expected type is HEADER\_TOKEN, but found {0}.**

**Cause:** Token type was invalid: it should be HEADER\_TOKEN.

---

**Action:** Reconfigure the token type to a valid type.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04551: The number of OSSO headers is zero or an invalid number.**

**Cause:** Could not find OSSO header in HTTP request.

**Action:** Login again, or contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-04552: The required Oracle Access Manager property {0} is missing or invalid.**

**Cause:** A required Oracle Access Manager property was missing or invalid.

**Action:** Configure the property "access.sdk.install.path" in the service instance in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04553: The user identity {0} for Oracle Access Manager is invalid.**

**Cause:** The user identity for Oracle Access Manager was invalid.

**Action:** Login again.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-04554: The user password for Oracle Access Manager is invalid.**

**Cause:** The user password for Oracle Access Manager was invalid.

**Action:** Login again.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-04555: The user {0} is not logged in to Oracle Access Manager. The error is {1}.**

**Cause:** The user was not logged in Oracle Access Manager.

**Action:** Login again.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-04556: The user {0} is not authorized to access a resource type authentication in Oracle Access Manager.**

**Cause:** The user was not logged in Oracle Access Manager.

---

**Action:** Login again.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-04557: Invalid parameter {0} supplied. Cannot be null or empty.**

**Cause:** Invalid parameter {0} supplied. Cannot be null or empty.

**Action:** Ensure parameter is non-null. If the parameter is a String type, ensure the value is non-null and the length is greater than zero.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**JPS-04558: The SSO service is not properly configured: {0}.**

**Cause:** The SSO service is not properly configured: {0}.

**Action:** Check the SSO Service configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-04559: Failed to create the {0} token. Cause: {1}.**

**Cause:** Failed to create the {0} token. Cause: {1}.

**Action:** Re-login.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-04601: Cannot obtain audit service for policy store.**

**Cause:** Could not query audit service about audit logging level for policy store messages.

**Action:** Ensure that auditing is configured correctly.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-04602: Cannot log policy management event to the audit service.**

**Cause:** Could not log policy management audit messages to the audit service.

**Action:** Ensure that auditing is configured correctly in your environment and application.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-05500: Cannot create the user manager MBean.**

**Cause:** Could not create the user manager MBean.

---

**Action:** Check errors in log files and contact the domain administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-05501: Cannot create the role manager MBean.**

**Cause:** Could not create the role manager MBean.

**Action:** Check the log files for errors and contact domain administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-05502: Cannot create the identity store MBean.**

**Cause:** Could not create the identity store MBean.

**Action:** Check log files and contact the domain administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-05513: Failed to determine realms to migrate file {0}. Reason {1}.**

**Cause:** Failed determine realms to migrate file {0}. Reason {1}.

**Action:** Check log files and try again.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**JPS-05521: Invalid jaas.login.controlFlag {0} found for {1} service instance. Valid values should be {2}.**

**Cause:** Invalid jaas.login.controlFlag {0} found for {1} service instance. Valid values should be {2}.

**Action:** Use a valid value.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-05542: Bootstrap credential store context missing**

**Cause:** Could not find bootstrap credstore context

**Action:** Contact aystem administrator

**Level:** 1

**Type:** WARNING

**Impact:** Compliance

**JPS-05546: Bootstrap credential store service missing**

**Cause:** Could not find bootstrap credstore service



---

**Action:** Contact system administrator

**Level:** 1

**Type:** WARNING

**Impact:** Compliance

**JPS-06000: The source context {0} is missing in jps-config.xml.**

**Cause:** While migrating a security store, found that the context, specified as source {0}, did not exist in jps-config.xml.

**Action:** Provide a context for source that is present in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-06001: The destination context {0} is missing in jps-config.xml.**

**Cause:** While migration of a security store, found that the context, specified as destination {0}, did not exist in jps-config.xml.

**Action:** Provide a context for destination that is present in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-06002: Cannot clean the destination credential store. Reason {0}.**

**Cause:** A codebase grant was found without the required permissions.

**Action:** Set the right permissions to the codebase grant.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**JPS-06003: Cannot migrate credential folder/key {0}/{1}.Reason {2}.**

**Cause:** Cannot migrate this credential.

**Action:** Verify that the credential is correctly specified.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**JPS-06004: Cannot migrate an unknown user. Reason {0}.**

**Cause:** Cannot migrate this user.

**Action:** Verify that the user is correctly specified.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**JPS-06005: Cannot get password of user {0}. Reason {1}.**

**Cause:** Cannot get this user password.

---

**Action:** Verify that the password is correctly specified.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**JPS-06006: Cannot migrate user {0}. Reason {1}.**

**Cause:** Cannot migrate this user name.

**Action:** Verify that the user name is correctly specified.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**JPS-06007: Cannot migrate an unknown role. Reason {0}.**

**Cause:** Cannot migrate this role.

**Action:** Verify that the role is correctly specified.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**JPS-06008: Cannot migrate role {0}. Reason {1}.**

**Cause:** Cannot migrate this role name.

**Action:** Verify that the role name is correctly specified.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**JPS-06009: Cannot migrate any member of role {0}. Reason {1}.**

**Cause:** Cannot migrate members.

**Action:** Verify that the members are correctly specified.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**JPS-06010: Cannot migrate an unknown member of role {0}. Reason {1}.**

**Cause:** Cannot migrate this member.

**Action:** Verify that the member is correctly specified.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**JPS-06011: Cannot migrate member {0} of role: {1}. Reason {2}.**

**Cause:** Cannot migrate this member name.

**Action:** Verify that the member name is correctly specified.

---

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**JPS-06012: cannot migrate a global grant. Reason {0}.**

**Cause:** Could not migrate a global grant. Reason {0}.

**Action:** Verify that the grant is correctly specified.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06013: cannot migrate an application grant. Reason {0}.**

**Cause:** Could not migrate an application grant. Reason {0}.

**Action:** Verify that the application grant is correctly specified.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06014: Cannot migrate an indirect password for {0}. Reason {1}.**

**Cause:** Could not migrate an indirect password due to an exception.

**Action:** Verify that the indirect password is correctly specified.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**JPS-06015: Cannot migrate an indirect password for {0} because the specified realm is null.**

**Cause:** Could not migrate an indirect password because the given realm was null.

**Action:** Provide a non-null realm.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**JPS-06016: Cannot migrate an indirect password for {0} because the specified user name is null.**

**Cause:** Could not migrate an indirect password because the given user name was null.

**Action:** Provide a non-null user name.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**JPS-06017: Cannot migrate an indirect password for {0} because the specified realm does not exist.**

---

**Cause:** Could not migrate an indirect password because the input realm does not exist.

**Action:** Provide an existing realm.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**JPS-06018: Cannot migrate an indirect password for {0} because the specified user does not exist.**

**Cause:** Could not migrate an indirect password because the input user does not exist.

**Action:** Provide an existing user.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**JPS-06019: The identity store associated with context {0} is missing in jps-config.xml.**

**Cause:** While migration of a policy store, found that the context, specified as containing the associated identity store {0}, did not exist in jps-config.xml.

**Action:** Provide a context to associate identity store that is present in jps-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-06020: The principal class {0} specified in the source policy store cannot be loaded. Reason {1}.**

**Cause:** Could not load a class. Reason {0}.

**Action:** Ensure the class is in the class path.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06021: Cannot migrate the credentials in the folder {0}. Reason: {1}.**

**Cause:** Cannot migrate the credentials in this folder.

**Action:** Check the folder in the source credential store.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**JPS-06022: Cannot determine the folder to be migrated.**

**Cause:** The credential store has more than one folder and the folder to be migrated was not defined.

**Action:** Specify the folder to be migrated.

**Level:** 1

---

**Type:** WARNING

**Impact:** Upgrade

**JPS-06023: The input file {0} specified for migration or upgrade is not valid.**

**Cause:** The file {0} was non-readable, empty, or did not exist.

**Action:** Provide a valid file.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06024: Cannot initialize the destination identity store.**

**Cause:** One or more required configuration properties were not be properly defined.

**Action:** Check the configuration of the destination identity store.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06025: There are undefined credential properties for the destination identity store.**

**Cause:** One or more required configuration properties for credentials were not defined.

**Action:** Check the configuration of the destination identity store.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06026: Cannot get credentials for the destination identity store from the domain credential store.**

**Cause:** Credentials were not found in the domain credential store.

**Action:** Ensure that the domain credential store has the appropriate credentials.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06027: Cannot migrate the specified realm.**

**Cause:** The specified realm was not found in the source store.

**Action:** Specify a valid realm name.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06028: The required identity store property {0} required for migration is undefined.**

**Cause:** A property required for migration was not configured in the identity store.

**Action:** Specify the missing configuration property.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**JPS-06029: JAZN properties cannot be read from config file {0}.**

**Cause:** JAZN properties could not be read from config file {0}.

**Action:** Check the configuration file and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06030: The required JAZN property {0} could not be read.**

**Cause:** A required JAZN property {0} could not be read.

**Action:** Check the configuration file and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06031: No application is configured in the source policy store.**

**Cause:** No application was configured in the source policy store.

**Action:** Check the source policy store.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06032: Unable to determine the application policy to migrate.**

**Cause:** More than one application was configured in the source policy store.

**Action:** Check the source policy store.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06033: The source credential store contains no credentials.**

**Cause:** The requested credential was not found in the credential store.

**Action:** Ensure that the credential store has the requested credential.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-06034: The folder {0} is missing in the credential store.**

**Cause:** The requested map name was not found in the credential store.

**Action:** Ensure that the credential store contains the requested map name.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**JPS-06035: The destination file {0} already exists; the existing LDIF file will not be appended or overwritten.**

**Cause:** The destination file is already present.

**Action:** Delete the destination file, or provide the name of a non-existing file.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-06036: Cannot determine the default realm to migrate file {0}. Reason {1}.**

**Cause:** An internal error occurred while determining the default realm.

**Action:** Check log files and try again.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**JPS-06037: Cannot initialize the source credential store.**

**Cause:** The configuration for the credential store was invalid.

**Action:** Verify that the credential store configuration is correct and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06038: Cannot initialize the destination credential store.**

**Cause:** The configuration for the credential store was invalid.

**Action:** Verify that the credential store configuration is correct and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06039: Cannot migrate property {0} of user {1}. Reason {2}.**

**Cause:** Cannot migrate property {0} for user {1}. Reason {2}.

**Action:** Check the log files and retry migrating.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**JPS-06040: Cannot migrate property {0} of role {1}. Reason {2}.**

**Cause:** Cannot migrate property {0} for role {1}. Reason {2}.

**Action:** Check the log files and retry migrating.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

---

**JPS-06041: The switch or keyword "{0}" is not applicable to "{1} = {2}".**

**Cause:** One or more optional switches or keywords were invalid.

**Action:** Refer to the command documentation for the correct usage.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-06042: Invalid scope for migration.**

**Cause:** Value of scope keyword was invalid.

**Action:** Enter only one of the defined values/alias of scope as a value for the keyword scope.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-06043: The source application is undefined but required to migrate application-specific policies.**

**Cause:** Optional keyword srcApp was not defined.

**Action:** Specify, in the parameter srcApp, the value of the application whose policies are to be migrated.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-06044: Cannot create the temporary file {0}.**

**Cause:** Could not write the XML file.

**Action:** Check permissions or disk space in the java.io.tmpdir directory.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JPS-06045: Cannot parse the file {0}.**

**Cause:** Could not parse the XML file.

**Action:** Check that the file is present in the java.io.tmpdir directory, and that it contains well-formed XML.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JPS-06046: Cannot delete the file {0}.**

**Cause:** The temp file could not be deleted.

**Action:** Check that the file is not being accessed by other applications.

**Level:** 1

**Type:** ERROR



---

**Impact:** Programmatic

**JPS-06047: Cannot migrate user credentials of user {0}.**

**Cause:** The source identity store was configured not to give cleartext password.

**Action:** Configure the source identity store to obfuscate password.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**JPS-06048: Null values passed in for username or application stripes.**

**Cause:** The user name or the application stripe was null.

**Action:** The user name must not be null. The list of application names must be null if only global policies are to be extracted.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**JPS-06049: Application list is empty. Only global policies will be extracted.**

**Cause:** The list of applications was empty.

**Action:** Only global policies are collected.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Programmatic

**JPS-06050: file {0} was not found**

**Cause:** The xml file was not found.

**Action:** Check if the file is present in the java.io.tmpdir directory.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**JPS-06051: Processing of privilege roles is supported only when migrating an XML Policy store to an LDAP Policy Store.**

**Cause:** Processing of privilege roles was supported only when migrating an XML policy store to an LDAP policy store.

**Action:** Make sure that the source store is XML-based and the destination store is LDAP-based.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06052: Error while processing a PermissionSet grant.**

**Cause:** Error encountered while processing permissionSet grant.

**Action:** Check log files for details.

**Level:** 1

---

**Type:** ERROR

**Impact:** Upgrade

**JPS-06053: Processing privilege roles failed. Cause {0}**

**Cause:** The processing of privilege roles failed.

**Action:** Check log files for details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06054: Error in creating resourceTypes in destination store. Cause {0}**

**Cause:** Error encountered while creating resourceTypes in destination store.

**Action:** Check log files for details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06055: Location of the ldif file containing resourceType definitions cannot be null.**

**Cause:** Location of the LDIF file containing resourceType definitions was null or not found.

**Action:** Provide the absolute path for the resource file.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06056: Error while reading resourcetype file {0}.**

**Cause:** Error encountered while reading the resourcetype file {0}.

**Action:** Ensure that the file exists and that it has the expected format.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06057: Resource type name or matcher class cannot be null.**

**Cause:** Resource type name or matcher class was null.

**Action:** Provide a valid name and matcher class for the resource type.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06058: Permission class {0} with more than one matching resource type found.**

**Cause:** Permission class had more than one matching resource type.

**Action:** Ensure that the a permission class has just one matching resource type.

**Level:** 1

---

**Type:** ERROR

**Impact:** Upgrade

**JPS-06059: A grant entry containing {0} as one of principals has multiple principal entries. This entry cannot be processed.**

**Cause:** A grant for a privilege role had multiple principals.

**Action:** Ensure that the privilege role grant has a single principal.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**JPS-06060: The resource type definition file is missing.**

**Cause:** The resource type definition file was not found.

**Action:** Provide the absolute path location for the resource definition file in LDIF format when using the option procPrivOption.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06061: The switch or keyword "{0}" is not defined for "{1} = {2}".**

**Cause:** One or more optional switches or keywords were invalid.

**Action:** Refer to the command documentation for the correct usage.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-06062: Application role {0} corresponding to a member application role not defined.**

**Cause:** Application role not defined.

**Action:** Check logs for details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06063: No Matching resource type definition found for permission class {0}.**

**Cause:** Permission class representing resource granted to a privileged role does not have corresponding resource type definition.

**Action:** Make sure a permission class has one matching resource type.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06064: Error getting the application role {0} from the source policy store**

**Cause:** The application role was either not present or defined multiple times.

**Action:** Check the source policy store and make sure that the application role is uniquely defined.

---

**Level: 1**  
**Type: ERROR**  
**Impact: Upgrade**  
**JPS-06065: Report generation failed**  
**Cause:** .  
**Action:** .

**Level: 1**  
**Type: ERROR**  
**Impact: Configuration**  
**JPS-06066: Invalid value for mode.**  
**Cause:** Invalid value for mode  
**Action:** Make sure the value for mode is valid

**Level: 1**  
**Type: ERROR**  
**Impact: Security**  
**JPS-06067: {0} config file either not found or not a valid file.**  
**Cause:** {0} config file either not found or not a valid file  
**Action:** Make sure to provide a valid config file

**Level: 1**  
**Type: ERROR**  
**Impact: Upgrade**  
**JPS-06068: Unable to read configurations from jazn config file : {0}.**  
**Cause:** Unable to read configurations from jazn data file : {0}.  
**Action:** Check the jazn data file.

**Level: 1**  
**Type: ERROR**  
**Impact: Upgrade**  
**JPS-06069: Provider referred from jazn config file {0} is of type XML and not LDAP.**  
**Cause:** Provider referred from jps-config file {0} is of type XML and not LDAP.  
**Action:** Refer to a provider of type LDAP.

**Level: 1**  
**Type: ERROR**  
**Impact: Upgrade**  
**JPS-06070: Unable to read policies from policy store.**  
**Cause:** Unable to read policies from policy store.  
**Action:** Check the policy store.

**Level: 1**  
**Type: ERROR**

---

**Impact:** Upgrade

**JPS-06071: Unable to read global policies from policy store.**

**Cause:** Unable to read global policies from policy store.

**Action:** Check the policy store.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06072: Unable to read permissions for grantee {0} from policy store.**

**Cause:** Unable to read permissions for grantee {0} from policy store.

**Action:** Check the policy store.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06073: Unable to read realm policies from policy store.**

**Cause:** Unable to read realm policies from policy store.

**Action:** Check the policy store.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06074: Unable to read realm policies from realm {0} from policy store.**

**Cause:** Unable to read realm policies from realm {0} from policy store.

**Action:** Check the policy store.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06075: Unsupported resource type file format. Use either an ldif file or a jazn-data with only resource type definitions.**

**Cause:** Unsupported resource type file format.

**Action:** Use either an ldif file or a jazn-data with only resource type definitions.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06076: A Resource Type referred by {0} is expected to have a matching class {1} but has {2}.**

**Cause:** A Resource Type referred by a Permission is expected to have the same matching class as defined in the Permission

**Action:** Make sure a permission class has one matching resource type with the same class name.

**Level:** 1

---

**Type:** ERROR

**Impact:** Upgrade

**JPS-06077: A Resource Type referred by {0} is not defined.**

**Cause:** A Resource Type referred by a Permission is not defined.

**Action:** Make sure a permission class has one matching resource type.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06078: Cannot migrate keystore/stripe {0}/{1}.Reason {2}.**

**Cause:** Cannot migrate the keystore in this stripe.

**Action:** Check the keystore and stripe in the source keystore service.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**JPS-06079: Cannot determine the stripe to be migrated.**

**Cause:** The keystore service has more than one stripes and the stripe to be migrated was not defined.

**Action:** Specify the stripe to be migrated.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**JPS-06080: The source keystore service contains no keystore.**

**Cause:** The requested keystore was not found in the keystore service.

**Action:** Ensure that the keystore service has the requested keystore.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**JPS-06082: Cannot initialize the source keystore service.**

**Cause:** The configuration for the keystore service was invalid.

**Action:** Verify that the keystore service configuration is correct and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06083: Cannot initialize the destination keystore service.**

**Cause:** The configuration for the keystore service was invalid.

**Action:** Verify that the keystore service configuration is correct and try again.

**Level:** 1

**Type:** ERROR

---

**Impact:** Upgrade

**JPS-06084: Cannot clean the destination keystore service. Reason {0}.**

**Cause:** A codebase grant was found without the required permissions.

**Action:** Set the right permissions to the codebase grant.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**JPS-06085: Resource types not defined for the application {0}.**

**Cause:** Resource Types not found for the application {0}.

**Action:** Define the resource types for the application {0}.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-06086: Cannot upgrade policies for application {0}.**

**Cause:** Exception during policy upgradation.

**Action:** Check the Causing exception and fix the error.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**JPS-07000: Provide a valid jps configuration file.**

**Cause:** The jps configuration file was invalid.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07001: Provide a valid application name.**

**Cause:** Application ID was invalid.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07002: Provide a valid jazn-data file. .**

**Cause:** The jazn-data file was invalid.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07003: Provide a valid folder name.**

---

**Cause:** The patch delta folder was invalid.

**Action:** Provide a valid folder for generating patch delta files.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07004: ApplicationPolicy object is null/empty.**

**Cause:** ApplicationPolicy object was null

**Action:** Make sure to create a not null ApplicationPolicy object

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07005: The "{0}" jazn data file does not exists.**

**Cause:** Jazn data file does not exists.

**Action:** Make sure to provide an existing jazn-data file.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07006: "{0}" Not a folder. Please provide a valid folder.**

**Cause:** Not a folder.

**Action:** Make sure to provide a valid folder.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07007: "{0}" folder does not exists**

**Cause:** The folder does not exists.

**Action:** Make sure to provide an existing folder.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07008: The {0} jps configuration file does not exist.**

**Cause:** The jps configuration file does not exists.

**Action:** Make sure to provide an existing jps configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07009: The "{0}" folder for generating patch delta files does not exist.**

**Cause:** The folder to generate the patch delta files does not exists.

**Action:** Make sure to provide an existing folder.



---

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07010: The AppRole "{0}" cannot be created. Cause {1} .**

**Cause:** The approle could not be created.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-07011: The AppRole object is null while persisting to Addition Safe Changes.**

**Cause:** The required parameter was null.

**Action:** Ensure to provide a valid AppRole Object.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07012: The ResourceType object is null while persisting to Addition Safe Changes.**

**Cause:** The required parameter was null.

**Action:** Enusre to provide a valid ResourceType Object.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07013: The AppRole list is null/empty while persisting to Addition Safe Changes.**

**Cause:** The required parameter was null.

**Action:** Ensure to provide a valid AppRole List.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07014: The Resource object is null while persisting to Addition Safe Changes.**

**Cause:** The required parameter was null.

**Action:** Ensure to pass a valid Resource object.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07015: The PermissionSet object is null while persisting to Addition Safe Changes.**

**Cause:** The required parameter was null.

**Action:** Ensure to provide a valid PermissionSet object.

---

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07016: The Association object is null while persisting to Addition Safe Changes.**

**Cause:** The required parameter was null.

**Action:** Ensure to provide a valid Association object.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07017: Internal Error.**

**Cause:** That was an internal error.

**Action:** Refer to the log files for details and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07018: Application Role: "{0}" cannot be added. Reason {1} .**

**Cause:** Policy store reported an error.

**Action:** Check the Reason and fix the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-07019: Permission Set: "{0}" cannot be added. Reason {1}.**

**Cause:** Policy store reported an error.

**Action:** Check the Reason and fix the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-07020: Resource: "{0}" cannot be added. Reason {1}.**

**Cause:** Policy store reported an error.

**Action:** Check the Reason and fix the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-07021: Resource Type "{0}" cannot be added. Reason {1}.**

**Cause:** Policy store reported an error.

**Action:** Check the Reason and fix the problem.

**Level:** 1

**Type:** WARNING

---

**Impact:** Security

**JPS-07022: Member:** name "{0}" ,class "{1}" cannot be granted an application role: "{2}". Reason {3}.

**Cause:** Policy store reported an error.

**Action:** Check the Reason and fix the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-07023: Resource Actios:** name "{0}", actions "{1}" cannot be added in permission set: "{2}". Reason {3}.

**Cause:** Policy store reported an error.

**Action:** Check the Reason and fix the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-07024: Permission:** "{0}" cannot be granted to grantee "{1}". Reason {2}.

**Cause:** Policy store reported an error.

**Action:** Check the Reason and fix the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-07025: Permission set:** "{0}" cannot be granted to grantee "{1}". Reason {2}

**Cause:** Policy store reported an error.

**Action:** Check the Reason and fix the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-07026: Application Role:** "{0}" cannot be modified. Reason {1}.

**Cause:** Policy store reported an error.

**Action:** Check the Reason and fix the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-07027: Permission Set:** "{0}" cannot be modified. Reason {1}.

**Cause:** Policy store reported an error.

**Action:** Check the Reason and fix the problem.

**Level:** 1

**Type:** WARNING

---

**Impact:** Security

**JPS-07028: Resource: "{0}" cannot be modified. Reason {1}.**

**Cause:** Policy store reported an error.

**Action:** Check the Reason and fix the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-07029: Resource Type: "{0}" cannot be modified. Reason {1}**

**Cause:** Policy store reported an error.

**Action:** Check the Reason and fix the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-07030: Application Role: "{0}" cannot be deleted. Reason {1}.**

**Cause:** Policy store reported an error.

**Action:** Check the Reason and fix the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-07031: Permission Set: "{0}" cannot be deleted. Reason {1}.**

**Cause:** Policy store reported an error.

**Action:** Check the Reason and fix the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-07032: Resource: "{0}" cannot be deleted. Reason {1}.**

**Cause:** Policy store reported an error.

**Action:** Check the Reason and fix the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-07033: Resource Type: "{0}" cannot be deleted. Reason {1}**

**Cause:** Policy store reported an error.

**Action:** Check the Reason and fix the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Security

---

**JPS-07034: Member: name "{0}", class "{1}" cannot be revoked from application role: "{2}". reason {3}.**

**Cause:** Policy store reported an error.

**Action:** Check the Reason and fix the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-07035: Resource Actions: name "{0}", actions "{1}" cannot be deleted from permission set: "{2}". Reason {3}.**

**Cause:** Policy store reported an error.

**Action:** Check the Reason and fix the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-07036: Permission: "{0}" cannot be revoked from grantee: "{1}". Reason {2}.**

**Cause:** Policy store reported an error.

**Action:** Check the Reason and fix the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-07037: Permission set: "{0}" cannot be revoked from grantee: "{1}". Reason {2}.**

**Cause:** Policy store reported an error.

**Action:** Check the Reason and fix the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-07038: Additions cannot be read. Reason {0}.**

**Cause:** Policy store reported an error.

**Action:** Check the Reason and fix the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-07039: Deletions cannot be read. Reason {0}.**

**Cause:** Policy store reported an error.

**Action:** Check the Reason and fix the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Security

---

**JPS-07040: Modifications cannot be read. Reason {0}.**

**Cause:** Policy store reported an error.

**Action:** Check the Reason and fix the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-07041: The argument "{0}" is not applicable for phase "{1}".**

**Cause:** Extra argument provided

**Action:** Please provide only relevant parameters

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07042: Illegal value provided for argument "{0}".**

**Cause:** Illegal value provided for an argument

**Action:** Please provide a legal value for the argument.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07043: Cannot find application policy {0}.**

**Cause:** Could not find application policy {0}.

**Action:** Check the application name passed.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07044: Cannot retrieve newline application policy.**

**Cause:** Could not retrieve newline application policy.

**Action:** Check the application name passed.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07045: Cannot retrieve baseline application policy.**

**Cause:** Could not retrieve baseline application policy.

**Action:** Check the application name passed.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07046: Cannot retrieve customer application policy.**

**Cause:** Could not retrieve customer application policy.

---

**Action:** Check the application name passed.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07047: This artifact is newly added in patch version.**

**Cause:** The required parameter was null.

**Action:** Enusre to provide a valid RoleCategory Object.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07056: Addition conflicts initialization failed.**

**Cause:** Internal Error occured when attempting to load Addition Conflicts from Patch Delta.

**Action:** Check the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07057: Modification conflicts initialization failed.**

**Cause:** Internal Error occured when attempting to load Modification Conflicts from Patch Delta.

**Action:** Check the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07058: Deletion conflicts initialization failed.**

**Cause:** Internal Error occured when attempting to load Deletion Conflicts from Patch Delta.

**Action:** Check the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07059: Resolve addition conflicts.**

**Cause:** Addition conflicts are not resolved.

**Action:** Resolve addition conflicts.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07060: Resolve modification conflicts.**

**Cause:** Modification conflicts are not resolved.

---

**Action:** Resolve modification conflicts.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07061: Resolve deletion conflicts.**

**Cause:** Deletion conflicts are not resolved.

**Action:** Resolve deletion conflicts.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07062: Additions Writer initialization failed for resolve.**

**Cause:** Additions Writer initialization failed for resolve.

**Action:** Check the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07063: Deletions Writer initialization failed for resolve.**

**Cause:** Additions Writer initialization failed for resolve.

**Action:** Check the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07064: Modifications Writer initialization failed for resolve.**

**Cause:** Modification Writer initialization failed for resolve.

**Action:** Check the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07065: Dependency artifact {0} is not resolved for artifact {1}.**

**Cause:** Dependency artifact {0} is not resolved for artifact {1}.

**Action:** Check the resolutions.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-07066: Dependency artifact {0} resolution is not valid for artifact {1}.**

**Cause:** Dependency artifact {0} resolution is not valid for artifact {1}.

**Action:** Check the resolutions.



---

**Level: 1**

**Type: ERROR**

**Impact: Security**

**JPS-07067: Artifact not resolved {0}.**

**Cause:** Artifact not resolved {0}.

**Action:** Check the resolutions.

**Level: 1**

**Type: ERROR**

**Impact: Security**

**JPS-07601: Complete staging offline deployment for application {0} in {1}**

**Cause:** Complete staging offline deployment for application {0} in {1}

**Action:** No action required

**Level: 1**

**Type: NOTIFICATION**

**Impact: Security**

**JPS-09000: Resource type {0} already in use for {1}.**

**Cause:** Resource type was already in use.

**Action:** Use a different resource type name.

**Level: 1**

**Type: WARNING**

**Impact: Security**

**JPS-09001: Resource matching class name is missing. A subtype must not have its own matching algorithm.**

**Cause:** Resource matching class name was missing.

**Action:** A subtype must not have its own matching algorithm.

**Level: 1**

**Type: WARNING**

**Impact: Security**

**JPS-09002: The parameter {0} of type {1} does not exist.**

**Cause:** This parameter did not exist.

**Action:** See the log files for more details.

**Level: 1**

**Type: WARNING**

**Impact: Security**

**JPS-09003: For the parameter {0} more than expected values found and they are {1}.**

**Cause:** More than expected values for given parameter found.

**Action:** See the log files for more details.

**Level: 1**

---

Type: WARNING

Impact: Security

**JPS-09004: For type {0} the modification is not allowed for {1}.**

Cause: Modify operation was not allowed.

Action: See the log files for more details.

Level: 1

Type: WARNING

Impact: Security

**JPS-09005: For the parameter {0} the given value {1} is invalid.**

Cause: The value for the given parameter was invalid.

Action: Provide the valid value for the given paramter.

Level: 1

Type: WARNING

Impact: Security

**JPS-09006: Resource {0} already in use for {1}.**

Cause: Resource was already in use.

Action: Use a different resource name.

Level: 1

Type: WARNING

Impact: Security

**JPS-09007: Role category {0} already in use for {1}.**

Cause: Role category was already in use.

Action: Use a different role category name.

Level: 1

Type: WARNING

Impact: Security

**JPS-09008: Application policy for application {0} does not exist.**

Cause: Application policy did not exist.

Action: The application policy must exist. Check the policy store.

Level: 1

Type: WARNING

Impact: Security

**JPS-09009: Only limited set of properties are supported for resource action search.  
See the documentation for more details.**

Cause: The property user to search resource action was invalid.

Action: Only limited set of properties are supported for resource action search.  
See the documentation for more details.

Level: 1

---

**Type:** WARNING

**Impact:** Security

**JPS-09010: Cannot create permission set {0} with a non existent resource type {1}.**

**Cause:** Permission set could not be created without resource type.

**Action:** Resource type must be pre-defined to create the permission set.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-09011: Cannot create permission set {0} with a non existent resource {1}.**

**Cause:** Permission set could not be created without resource.

**Action:** Resource must be pre-defined to create the permission set.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-09012: Search value cannot be null. It can be null only if MATCHER is ANY.**

**Cause:** Search value was null. It could be null only if MATCHER is ANY.

**Action:** Verify the search value for the given query.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-09013: This application roles {0} does not belong to this application {1}.**

**Cause:** This application role did not belong to this application.

**Action:** Ensure this application role belongs to this application.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-09014: The application role {0} cannot have null name or unique name for the application {1}.**

**Cause:** The name or unique name of this application role was null or invalid.

**Action:** Ensure the name or unique name of this application role is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-09015: Application role does not exist in current application.**

**Cause:** Application role was not found in current application.

**Action:** Ensure the application role belongs to this application.

**Level:** 1

**Type:** WARNING

---

**Impact:** Security

**JPS-09016: Unknown policy store service type {0}.**

**Cause:** Unknown policy store service type {0}.

**Action:** Correct the policy store configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-09017: Policy entry {0} cannot be found.**

**Cause:** Policy entry {0} cannot be found.

**Action:** Correct the policy entry.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-09018: Policy objet {0} cannot be found.**

**Cause:** Policy object {0} cannot be found.

**Action:** Correct the policy object.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-09019: {0} did not be cached.**

**Cause:** {0} did not be cached.

**Action:** Ensure the Resource has valid actions.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-09020: Principal entry class "{0}", name "{1}" cannot be created.**

**Cause:** Principal entry class "{0}", name "{1}" cannot be created.

**Action:** Ensure that the principal entry class is correct and entry value is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-09021: Permission entry class "{0}", target "{1}", action "{2}" cannot be created.**

**Cause:** Permission entry class "{0}", target "{1}", action "{2}" cannot be created.

**Action:** Ensure that the permission entry class is correct and entry value is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-09022: Resource entry type "{0}", resource "{1}" cannot be created.**

---

**Cause:** Resource entry type "{0}", resource "{1}" cannot be created.

**Action:** Ensure that the resource entry class is correct and entry value is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-09023: Resource type entry name "{0}", matcher class "{1}", provider "{2}" cannot be created.**

**Cause:** Resource type entry name "{0}", matcher class "{1}", provider "{2}" cannot be created.

**Action:** Ensure that the resource type entry class is correct and entry value is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-09024: Resource action entry type "{0}", name "{1}" cannot be created.**

**Cause:** Resource action entry type "{0}", name "{1}" cannot be created.

**Action:** Ensure that the resource action entry class is correct and entry value is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-09025: Permissionset entry name "{0}", actions "{1}" cannot be created.**

**Cause:** Permissionset entry name "{0}", actions "{1}" cannot be created.

**Action:** Ensure that the permissionset entry class is correct and entry value is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-09026: Role category entry name "{0}" cannot be created.**

**Cause:** Role category entry name "{0}" cannot be created.

**Action:** Ensure that the role category entry class is correct and entry value is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-09027: Grantee DN was missing for principal {0}.**

**Cause:** Grantee DN was missing for principal {0}.

**Action:** Check principal value.

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**JPS-09028: Failed to get permission for principal {0}. Reason: {1}.**

**Cause:** Failed to get permission for principal {0}. Reason: {1}.

**Action:** Check principal value.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-09029: Total Time to getPermissions in the Application {0} with {1} number of Grantees is: {2} ms.**

**Cause:** Total Time to getPermissions in the Application {0} with {1} number of Grantees is: {2} ms.

**Action:** Check log for details.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**JPS-09030: Code signer data {0} cannot be migrated due to limitaion in the destination policy store.**

**Cause:** Code signer data {0} cannot be migrated due to limitaion in the destination policy store.

**Action:** Check log for details.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**JPS-09031: Failed to read java policies for Application: {0}. Reason: {1}.**

**Cause:** Failed to read java policies for Application: {0}. Reason: {1}.

**Action:** Check log for details.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**JPS-09032: Only one of permission array {0} and permission entry list {1} can be null or non-null.**

**Cause:** Only one of permission array {0} and permission entry list {1} can be null/non-null.

**Action:** Ensure one of permission array or permission entry list values is null or non-null.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-09033: No grantee found for grantee entry {0}.**

**Cause:** No grantee found for grantee entry {0}.

---

**Action:** Ensure the grantee exist in the policy store.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-09034: Modification on single-value attribute {0} but contains multiple attribute values.**

**Cause:** Modification on single-value attribute {0} but contains multiple attribute values.

**Action:** Check modification details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-09035: Failed to create DN for {0}. Reason: {1}.**

**Cause:** Failed to create DN for {0}. Reason: {1}.

**Action:** Check DN name.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-09036: Failed to read JACC policy {0}. Reason: {0}.**

**Cause:** Failed to read JACC policy {0}. Reason: {0}.

**Action:** Check LDAP configuration to resolve this error.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-09037: No application DN found for name {0} under farm {1}.**

**Cause:** No application DN found for name {0} under farm {1}.

**Action:** Check DN name.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JPS-09038: Resource type {0} does not exist for resource {1}**

**Cause:** This resource type does not exist.

**Action:** Provide a valid resource type.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10000: There was an internal error in the policy store.**

**Cause:** There was an internal error in the policy store.

---

**Action:** Refer to the base exception in logs to resolve the issue.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10100: The policy domain, {0}, does not exist.**

**Cause:** The policy domain does not exist

**Action:** Check the policy domain name.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10151: Application role {0} does not exist**

**Cause:** The application role does not exist.

**Action:** Provide correct application role.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10152: Application Role {0} is used.**

**Cause:** Application Role is used.

**Action:** Remove the objects which use this application role.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10153: Application role {0} does not belong to current application.**

**Cause:** Application role does not belong to current application policy.

**Action:** Modify the application role with application role manager from correct application policy.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10154: Class {0} is not supported.**

**Cause:** The principal class specified is not supported.

**Action:** Provide correct principal class.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10155: The application role attribute {0} is not supported for app role search.**

**Cause:** The application role attribute specified is not supported.

**Action:** Provide supported attribute.



---

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10200: Administration role {0} already exists**

**Cause:** Cannot have two administration roles with the same name.

**Action:** Provide a new name to the administration role.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10201: Administration role {0} does not exist**

**Cause:** Administration role is not found.

**Action:** Check the administration role name.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10202: Administration role {0} is used**

**Cause:** Administration role is used.

**Action:** Remove administration role members first.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10203: Administration role {0} does not belong to current context**

**Cause:** Administration role does not belong to current context.

**Action:** Use it in correct context.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10204: Cannot create admin role with default name {0}**

**Cause:** Cannot create admin role with reserved name.

**Action:** Use another name for admin role.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10205: Cannot delete default admin role {0}**

**Cause:** Cannot delete default admin role.

**Action:** Check the admin role name for deletion.

**Level:** 1

**Type:** WARNING

---

**Impact:** Security

**JPS-10206: Cannot grant {0}, {1} to admin role because its super admin role has no such privilege**

**Cause:** Cannot grant privileges to admin role whose super role has not.

**Action:** Check the admin resource action to grant.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10207: Admin resource {0} is not for this scope {1}**

**Cause:** This admin resource is not for this scope

**Action:** Check the admin resource to grant.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10208: Cannot change rights of default admin role {0}**

**Cause:** Cannot change rights of default admin role for a scope

**Action:** Check the admin role name.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10209: The value for the SEARCH\_PROPERTY.PRINCIPAL does implement the java.security.Principal interface. It is of type '{0}'.**

**Cause:** The search by value is not an instance of java.security.Principal

**Action:** Supply an object of type java.security.Principal

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10210: The value for the SEARCH\_PROPERTY.PRINCIPAL\_NAME is not of type java.lang.String. It is of type '{0}'.**

**Cause:** The search by value is not an instance of java.lang.String

**Action:** Supply an object of type java.lang.String

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10250: Resource type reference should not be null.**

**Cause:** The parameter resource type reference is null.

**Action:** Use a valid object.

**Level:** 1

**Type:** WARNING

---

**Impact:** Security

**JPS-10251: The resource type reference is invalid.**

**Cause:** The current resource type reference is invalid.

**Action:** Use a valid resource type reference.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10252: The resource type {0} already exists.**

**Cause:** The resource type has existed.

**Action:** Make sure the resource type does not exist.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10253: The super resource type {0} does not exist.**

**Cause:** The resource type is referring an invalid super resource type.

**Action:** Make sure the super resource type exist.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10254: The resource type {0} should not have its own matcher since it has super type.**

**Cause:** The resource type has both its own matching algorithm and super type.

**Action:** Remove matching algorithm if the resource type should have super type. Otherwise, remove super type.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10255: Resource type search context should not be null.**

**Cause:** The resource type context could not be gotten.

**Action:** Make sure the application policy is available.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10256: Could not get an available data manager.**

**Cause:** The data manager is invalid.

**Action:** Make sure policy store and related configuration are correct.

**Level:** 1

**Type:** WARNING

---

**Impact:** Security

**JPS-10257: The modification operator {0} is invalid.**

**Cause:** The operator in ModificationItem is invalid.

**Action:** Make sure the operation is one of DirContext.ADD\_ATTRIBUTE, DirContext.REPLACE\_ATTRIBUTE and DirContext.REMOVE\_ATTRIBUTE.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10258: The property name {0} is unknown.**

**Cause:** The attribute ID in ModificationItem is undefined.

**Action:** Make sure the attribute ID is a valid one.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10259: The name of resource type could not be modified.**

**Cause:** Resource type name could not be modified.

**Action:** Do not put resource type name in ModificationItem.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10260: The super type of resource type could not be modified.**

**Cause:** The super type of resource type could not be modified.

**Action:** Do not put super type in ModificationItem.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10261: The matching algorithm of resource type could not be modified.**

**Cause:** The matching algorithm of resource type could not be modified.

**Action:** Do not put matching algorithm in ModificationItem

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10262: The action delimiter of resource type could not be modified.**

**Cause:** The action delimiter of resource type could not be modified.

**Action:** Do not put action delimiter in ModificationItem.

**Level:** 1

**Type:** WARNING

**Impact:** Security

---

**JPS-10263: The operation REPLACE\_ATTRIBUTE could not be used to the allowed actions of resource type.**

**Cause:** The operation REPLACE\_ATTRIBUTE could not be used to the allowed actions of resource type.

**Action:** Use REMOVE\_ATTRIBUTE and ADD\_ATTRIBUTE in ModificationItem.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10264: The property {0} of resource type is single, could not have more than one value.**

**Cause:** The property could not have more than one value.

**Action:** First remove the existing value before adding new one.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10265: Could not add or replace the property {0} since there is no value provided.**

**Cause:** There is no value provided when trying to add or replace an property.

**Action:** Provide the new value.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10266: The value data type of property {0} should be String.**

**Cause:** The value data type of property is not String.

**Action:** Use a String object as value.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10267: The resource type {0} does not exist.**

**Cause:** The resource type does not exist.

**Action:** Make sure the resource type exist.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10268: The resource type {0} is in use, could not be deleted.**

**Cause:** The resource type could not be deleted without cascade since it is in use.

**Action:** Cascade delete it or first remove all referring objects.

**Level:** 1

**Type:** WARNING

---

**Impact:** Security

**JPS-10269: The operation REPLACE\_ATTRIBUTE could not be used to the resource type attribute**

**Cause:** The operation REPLACE\_ATTRIBUTE could not be used to the resource type attribute

**Action:** Use REMOVE\_ATTRIBUTE and ADD\_ATTRIBUTE in ModificationItem.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10270: The resource type attribute {0} is used in policy(-ies) and can not be deleted.**

**Cause:** The resource type attribute being deleted was used in one or more policies and could not be deleted.

**Action:** Before deleting the resource attribute, make sure it is not used.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10271: The resource matcher class of resource type {0} could not be modified to {1}.**

**Cause:** The resource type matcher class was changed while modifying.

**Action:** Keep matcher class unchanged.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10400: Resource reference should not be null.**

**Cause:** The parameter resource reference is null.

**Action:** Use a valid object.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10401: The resource reference is invalid.**

**Cause:** The current resource reference is invalid.

**Action:** Use a valid resource reference.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10402: The resource {0} does not exist.**

**Cause:** The resource does not exist.

**Action:** Make sure the resource exist.

---

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10403: Could not get an available data manager.**

**Cause:** The data manager is invalid.

**Action:** Make sure policy store and related configuration are correct.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10404: The resource type {0} does not exist.**

**Cause:** The resource type does not exist.

**Action:** Make sure the resource type exist.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10405: The resource {0} with type {1} already exists in current application policy.**

**Cause:** The resource to be created has existed.

**Action:** Make sure the resource does not exist.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10406: The modification operator {0} is invalid.**

**Cause:** The operator in ModificationItem is invalid.

**Action:** Make sure the operation is one of DirContext.ADD\_ATTRIBUTE, DirContext.REPLACE\_ATTRIBUTE and DirContext.REMOVE\_ATTRIBUTE.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10407: The property name {0} is unknown.**

**Cause:** The attribute ID in ModificationItem is undefined.

**Action:** Make sure the attribute ID is a valid one.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10408: The name and type of resource could not be modified.**

**Cause:** The name and type of resource could not be modified.

**Action:** Do not put resource name and type in ModificationItem.

**Level:** 1

---

Type: WARNING

Impact: Security

**JPS-10409: The property {0} of resource is single, could not have more than one value.**

**Cause:** The property could not have more than one value.

**Action:** First remove the existing value before adding new one.

Level: 1

Type: WARNING

Impact: Security

**JPS-10410: Could not add or replace the property {0} since there is no value provided.**

**Cause:** There is no value provided when trying to add or replace an property.

**Action:** Provide the new value.

Level: 1

Type: WARNING

Impact: Security

**JPS-10411: The resource {0} is in use, could not be deleted.**

**Cause:** The resource could not be deleted without cascade since it is in use.

**Action:** Cascade delete it or first remove all referring objects.

Level: 1

Type: WARNING

Impact: Security

**JPS-10412: The resource attribute {0} already exists in the current entry.**

**Cause:** The resource attribute could not be added since it already exists.

**Action:** Remove duplicate resource attributes.

Level: 1

Type: WARNING

Impact: Security

**JPS-10413: The resource action {0} already exists in the current entry.**

**Cause:** The resource action could not be added since it already exists.

**Action:** Remove duplicate resource actions

Level: 1

Type: WARNING

Impact: Security

**JPS-10414: The resource attribute {0} could not be deleted since it does not exist.**

**Cause:** The resource attribute could not be deleted since it does not exist.

**Action:** Check if the resource attribute exists.

Level: 1



---

**Type:** WARNING

**Impact:** Security

**JPS-10415: The resource action {0} could not be deleted since it does not exist.**

**Cause:** The resource action could not be deleted since it does not exist.

**Action:** Check if the resource action exists

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10416: Resource {0} does not belong to the context.**

**Cause:** The resource does not belong to current context

**Action:** Pass in correct resource.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10417: Resource query across different resource type is not allowed.**

**Cause:** Resource query across different resource type is not allowed

**Action:** Pass in correct query parameter.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10451: Permission set {0} does not belong to the context.**

**Cause:** The permission set does not belong to current context

**Action:** Pass in correct permission set.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10452: Permission set {0} has ResourceActionsEntry with null ResourceEntry and null ResourceNameExpression.**

**Cause:** Both ResourceEntry and Resource name expression of ResourceActionsEntry is null

**Action:** Pass in correct ResourceActionsEntry.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10454: No resources or actions have been identified by the permissionset.**

**Cause:** No resources or actions have been identified by the permissionset.

**Action:** Ensure that the permission set is created with valid resource actions.

**Level:** 1

---

**Type:** WARNING

**Impact:** Security

**JPS-10455: Resource is not protected by a Java Permission.**

**Cause:** Resource is not protected by a Java Permission.

**Action:** Ensure that the permission set is created with valid resource object.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10456: ResourceExpression and ResourceAction cannot be specified at the same time.**

**Cause:** ResourceExpression and ResourceAction cannot be specified at the same time.

**Action:** PermissionSet ResourceAction should contain either Resource expression or ResourceEntry.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10457: Not able to perform operation due to invalid parameter. Cause: "{0}".**

**Cause:** Not able to perform operation due to invalid parameter. Cause: {0}.

**Action:** Ensure that the operation is called with valid parameters.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10458: ResourceExpression and ResourceAction cannot be null at the same time.**

**Cause:** ResourceExpression and ResourceAction cannot be null at the same time.

**Action:** PermissionSet ResourceAction should contain either Resource expression or ResourceEntry.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10459: The modified permission set {0} contains resources of multiple resource types. It is not permitted as there is policy(-ies) that references that permission set and uses resource attributes.**

**Cause:** The modified permission set contained resources of multiple resource types. It was not permitted if there was a policy that referenced that permission set and used resource attributes.

**Action:** Fix the permission set or modify the policy(-ies).

**Level:** 1

**Type:** WARNING

**Impact:** Security

---

**JPS-10460: The permission set search query {0} is not supported**

**Cause:** The permission set search query is not supported.

**Action:** Use supported query scenario.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10470: The resource type name "{0}", does not match the resourceType in the encoded target name: "{1}". Permission class is "{2}"**

**Cause:** Invalid resource type in permission target.

**Action:** Refer to the log files for details.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-10471: Resource type is missing in the target name: "{0}", for permission: "{1}"**

**Cause:** Resource type missing in permission target.

**Action:** Refer to the log files for details.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-10472: Target "{0}" is missing the prefix '=resourceName='. Unable to determine the resource name for permission: "{1}"**

**Cause:** Target name missing in permission target.

**Action:** Refer to the log files for details.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-10473: The target name "{0}" is invalid. Should start with "{1}"**

**Cause:** Target name encoding is not correct.

**Action:** Refer to the log files for details.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**JPS-10474: The parameter: "{0}", value: "{1}" cannot be null**

**Cause:** Permission target is null.

**Action:** Refer to the log files for details.

**Level:** 1

**Type:** ERROR

**Impact:** Security

---

**JPS-10500: The target policy, {0}, does not exist.**

**Cause:** The policy object does not exist.

**Action:** Check if the target policy exists.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10501: Policy query contains unrecognizable information.**

**Cause:** Policy query contains unrecognizable information.

**Action:** Check the policy query object.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10502: Policy rule information is missing.**

**Cause:** Policy rule information is missing.

**Action:** Check if policy rule information exists in policy repository.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10503: Obligation information is missing.**

**Cause:** Obligation information is missing.

**Action:** Check if obligation information exists in policy repository.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10504: Permission set information is missing.**

**Cause:** Permission set information is missing.

**Action:** Check if permission set information exists in policy repository.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10505: Grantee information is missing.**

**Cause:** Grantee information is missing.

**Action:** Check if grantee information exists in policy repository.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10506: The policy rule, {0}, does not exist.**

**Cause:** The policy rule does not exist.

---

**Action:** Check the policy rule name passed in.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10507: The condition string is in wrong format, {0}.**

**Cause:** Condition string is in wrong format.

**Action:** Check condition string in policy repository.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10508: Policy condition contains an unknown function, {0}.**

**Cause:** Policy condition contains an unknown function.

**Action:** Check condition string in policy repository.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10509: Policy condition parsing error.**

**Cause:** Policy condition parsing error.

**Action:** Check condition string in policy repository.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10510: The expression, {0}, is unknown.**

**Cause:** The policy expression is unknown.

**Action:** Check condition string in policy repository.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10511: The data type, {0}, is unknown.**

**Cause:** The data type is unknown

**Action:** Check condition string in policy repository.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10512: A ResourceActionsEntry should contain either resource entry or resource name expression.**

**Cause:** The ResourceActionsEntry object does not contain resource information.

**Action:** Check ResourceActionsEntry passed in.

---

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10513: The search value type {0} is not supported for {1}.**

**Cause:** Query criteria type does not support.

**Action:** Pass in a correct query value.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10514: Cannot add PermissionSet to PolicyEntry if it has ResourceType.**

**Cause:** Resource type is already defined in PolicyEntry.

**Action:** clear resource type of PolicyEntry before adding PermissionSetEntry.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10515: Cannot set ResourceType to PolicyEntry if it has PermissionSet.**

**Cause:** Permission Set is already defined in PolicyEntry.

**Action:** clear Permission Set of PolicyEntry before setting Resource Type.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10516: Cannot add Rule if there is rule already in PolicyEntry**

**Cause:** Add rule to policy when the policy already has rule.

**Action:** Delete existing rule before adding new rule to policy.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10517: Delete rule not existing in PolicyEntry**

**Cause:** rule does not belong to the PolicyEntry.

**Action:** Check the rule before deleting rule from PolicyEntry.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10518: Delete permission set not existing in PolicyEntry**

**Cause:** permission set does not belong to the PolicyEntry.

**Action:** Check the permission set before deleting permission set from PolicyEntry.

**Level:** 1

**Type:** WARNING

---

**Impact:** Security

**JPS-10519: Delete obligation not existing in PolicyEntry**

**Cause:** obligation does not belong to the PolicyEntry.

**Action:** Check the obligation before deleting obligation from PolicyEntry.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10520: Delete Principal not existing in PolicyEntry**

**Cause:** principal does not belong to the PolicyEntry.

**Action:** Check the principal before deleting principal from PolicyEntry.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10521: The obligation {0} already exists.**

**Cause:** The obligation already exists in the policy entry.

**Action:** Check ObligationEntry passed in.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10522: The parameters passed in is invalid, we expect {0}, but {1} is passed in.**

**Cause:** The parameter passed in the function is not valid.

**Action:** Pass in correct parameters.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10523: The function return type is invalid, we expect OpssBoolean, but {0} is passed in.**

**Cause:** The return type of the function is not valid.

**Action:** Pass in a function with OpssBoolean return type.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10524: The query with search property {0}, comparor type {1} and matcher {2} are not supported.**

**Cause:** Such query is not supported.

**Action:** Pass in a supported query value.

**Level:** 1

**Type:** WARNING

---

**Impact:** Security

**JPS-10525: The attribute assignment {0} could not be added since it already exists.**

**Cause:** The attribute assignment could not be added since it already exists.

**Action:** Remove duplicate attribute assignments.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10526: The permission set {0} could not be added since it already exists.**

**Cause:** The permission set could not be added since it already exists.

**Action:** Remove duplicate permission sets.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10527: The principal {0} could not be added since it already exists.**

**Cause:** The principal could not be added since it already exists.

**Action:** Remove duplicate principals.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10528: The Policy {0} referenced multiple resource types and resource attribute is used in policy condition or obligation.**

**Cause:** Policies that used resource attributes in their conditions or obligations could not reference one or more permission sets that contain resources of multiple types.

**Action:** Split the policy to reference only one resource type in each policy.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10529: The resource attribute {0} used in policy condition or obligation is invalid resource attribute of type {1}.**

**Cause:** The resource attribute used in policy condition was invalid for the referenced resource type

**Action:** Fix the policy condition to use only valid attributes for the given resource type.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10530: Cannot create a policy {0} with AdminRole(s) {1}.**

**Cause:** Cannot create a policy with AdminRoleEntry(s).

**Action:** Remove the AdminRole principals from the principal list.



---

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10531: Cannot grant permission to AdminRole(s) {0}.**

**Cause:** Cannot grant permission to AdminRoleEntry(s).

**Action:** Remove the AdminRole principals from the principal list.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10532: Cannot grant AdminRole {0} to another AdminRole {1}.**

**Cause:** Cannot grant AdminRole to another AdminRole.

**Action:** Change to grant AdminRole to either enterprise role or user.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10533: Cannot revoke AdminRole {0} from another AdminRole {1}.**

**Cause:** Cannot revoke AdminRole from another AdminRole.

**Action:** Change to revoke AdminRole from either enterprise role or user.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10534: Cannot grant AdminRole {0} to an AppRole {1}.**

**Cause:** Cannot grant AdminRole to an AppRole.

**Action:** Change to grant AdminRole to either enterprise role or user.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10535: Cannot revoke AdminRole {0} from an AppRole {1}.**

**Cause:** Cannot revoke AdminRole from an AppRole.

**Action:** Change to revoke AdminRole from either enterprise role or user.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10536: AdminRole {0} cannot be managed outside of the AdminManager.**

**Cause:** AdminRole cannot be managed outside of AdminManager.

**Action:** Use AdminManager for all AdminRole related administrative tasks.

**Level:** 1

**Type:** WARNING

---

**Impact:** Security

**JPS-10537: Cannot modify grant permission to AdminRole(s) {0}.**

**Cause:** Cannot modify grant permission to AdminRoleEntry(s).

**Action:** Remove the AdminRole principals from the principal list.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10538: Cannot revoke permission from AdminRole(s) {0}.**

**Cause:** Cannot revoke permission from AdminRoleEntry(s).

**Action:** Remove the AdminRole principals from the principal list.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10539: Basic policy cannot have {0} information.**

**Cause:** Basic policy cannot have {0} information.

**Action:** Remove the information from basic policy.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10540: Basic policy cannot have ResourceActionsEntry without ResourceEntry.**

**Cause:** Basic policy cannot have ResourceActionsEntry without ResourceEntry.

**Action:** Use ResourceActionsEntry with ResourceEntry for basic policy.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10541: Basic policy cannot use Resource {0} without Resource Matcher Class.**

**Cause:** Basic policy cannot use Resource {0} without Resource Matcher Class.

**Action:** Use Resource with Resource Matcher Class for basic policy.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10550: Attribute {0} already exists**

**Cause:** Cannot have two attributes with the same name.

**Action:** Provide a new name to the attribute.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10551: Attribute {0} does not exist**

---

**Cause:** Attribute not found.  
**Action:** Check the attribute name.

**Level:** 1  
**Type:** WARNING  
**Impact:** Security

**JPS-10552: Attribute {0} is used.**

**Cause:** Attribute is already used.  
**Action:** Remove the objects which use this attribute.

**Level:** 1  
**Type:** WARNING  
**Impact:** Security

**JPS-10553: Attribute {0} does not belong to current application.**

**Cause:** Attribute does not belong to current application policy.  
**Action:** Modify the attribute with extension manager from correct application policy.

**Level:** 1  
**Type:** WARNING  
**Impact:** Security

**JPS-10554: The name of Attribute in policy repository is missing**

**Cause:** Attribute in policy store has no name.  
**Action:** Check the underline policy repository.

**Level:** 1  
**Type:** WARNING  
**Impact:** Security

**JPS-10555: The type of Attribute in policy repository is missing**

**Cause:** Attribute in policy store has no type.  
**Action:** Check the underline policy repository.

**Level:** 1  
**Type:** WARNING  
**Impact:** Security

**JPS-10556: The category of Attribute in policy repository is missing**

**Cause:** Attribute in policy store has no category.  
**Action:** Check the underline policy repository.

**Level:** 1  
**Type:** WARNING  
**Impact:** Security

**JPS-10557: Cannot overwrite a built-in attribute, {0}.**

**Cause:** Try to overwrite a built-in attribute.

---

**Action:** Do not overwrite a built-in function.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10558: Cannot modify a built-in attribute, {0}.**

**Cause:** Try to modify a built-in attribute.

**Action:** Do not modify a built-in attribute.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10559: Cannot delete a built-in attribute, {0}.**

**Cause:** Try to delete a built-in attribute.

**Action:** Do not delete a built-in attribute.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10581: Cannot overwrite a built-in function, {0}.**

**Cause:** Try to overwrite a built-in function.

**Action:** Do not overwrite a built-in function.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10582: The function does not exist, {0}.**

**Cause:** The function does not exist.

**Action:** Check the function name passed in.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10583: The function is in use, {0}.**

**Cause:** The function is in use.

**Action:** Cannot delete a function in use.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10584: The function is used in some policies, your changes on return type may lead to unpredictable issues.**

**Cause:** The function is in use.

**Action:** Cannot change return type of a function in use.

---

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10585: The function is used in some policies, your changes on parameter types may lead to unpredictable issues.**

**Cause:** The function is in use.

**Action:** Cannot change parameter types of a function in use.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10586: Cannot modify a built-in function, {0}.**

**Cause:** Try to modify a built-in function.

**Action:** Do not modify a built-in function.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10587: Cannot delete a built-in function, {0}.**

**Cause:** Try to delete a built-in function.

**Action:** Do not delete a built-in function.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10600: Failed to initialize PD instance.**

**Cause:** Failed to initialize PD instance.

**Action:** Refer to the base exception in logs to resolve the issue.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10601: Failed to initialize PolicyDistributionManager instance.**

**Cause:** Failed to initialize PolicyDistributionManager instance.

**Action:** Refer to the base exception in logs to resolve the issue.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10602: PD has not been initialized.**

**Cause:** PD has not been initialized.

**Action:** Check if OPSS policy store provider has been initialized successfully.

**Level:** 1

---

**Type:** WARNING

**Impact:** Security

**JPS-10603: FAILURE: Retry {0} failed after {1} times retries.**

**Cause:** PD operation failed to retry.

**Action:** Check connectivity to backend repository.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-10700: The value of attribute {0} should be unique**

**Cause:** The unique attribute has duplicated values.

**Action:** Keep attribute value unique.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-90600: Security Module with the configuration id {0} already exists.**

**Cause:** Security Module with the configuration id {0} already exists.

**Action:** Provide a unique configuration id.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-90601: Failed to create Security Module with the configuration id {0}, with error {1}**

**Cause:** Failed to create Security Module with the configuration id {0}, with error {1}

**Action:** Check error message for further details.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-90602: Security Module with the configuration id {0} not found.**

**Cause:** Security Module with the configuration id {0} not found.

**Action:** Make sure the configuration id is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-90603: Audit Service is not initializable.**

**Cause:** Audit Service is not initializable.

**Action:** Configure an audit server for audit trails

**Level:** 1

---

**Type:** WARNING

**Impact:** Security

**JPS-90608: Failed to modify Security Module with the configuration id {0}, with error {1}**

**Cause:** Failed to modify PIP with the configuration id {0}, with error {1}

**Action:** Check error message for further details.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-90620: PIP with the configuration id {0} already exists.**

**Cause:** PIP with the configuration id/name {0} already exists.

**Action:** Provide a unique configuration id/name.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-90621: Failed to create PIP with the configuration id {0}, with error {1}**

**Cause:** Failed to create PIP with the configuration id {0}, with error {1}

**Action:** Check error message for further details.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-90622: PIP with the configuration id {0} not found.**

**Cause:** PIP with the configuration id/name {0} not found.

**Action:** Make sure the configuration id/name is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-90627: Failed to modify PIP with the configuration id {0}, with error {1}**

**Cause:** Failed to modify PIP with the configuration id {0}, with error {1}

**Action:** Check error message for further details.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-90630: Application Policy with the configuration id {0} not found.**

**Cause:** Application with the id {0} not found.

**Action:** Make sure the Application Policy is valid.

**Level:** 1

**Type:** WARNING

---

**Impact:** Security

**JPS-90637: Failed to create SM binding with the configuration id {0}, with error {1}**

**Cause:** Failed to create SM binding with the configuration id {0}, with error {1}

**Action:** Check error message for further details.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-90638: Failed to create PIP binding with the configuration id {0}, with error {1}**

**Cause:** Failed to create PIP binding with the configuration id {0}, with error {1}

**Action:** Check error message for further details.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-90639: Application {0} already bound to configuration {1}**

**Cause:** Application {0} already bound to configuration {1}

**Action:** No need to bind again

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-90640: Failed to unbind SM configuration**

**Cause:** Failed to unbind SM with the configuration id {0}, with error {1}

**Action:** Check error message for further details.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**JPS-90641: Failed to unbind PIP Configuration**

**Cause:** Failed to unbind PIP with the configuration id {0}, with error {1}

**Action:** Check error message for further details.

**Level:** 1

**Type:** WARNING

**Impact:** Security



---

## JRF-10001 to JRF-20030

**JRF-10001: Fail to retrieve the application identifier. The internal exception is: {0}.**

**Cause:** The MBean server could not be accessed to retrieve the application name.

**Action:** Verify that the MBean server is running and accessible.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-10002: Fail to retrieve the WebLogic domain adminserver server name. The internal exception is: {0}.**

**Cause:** The MBean server could not be accessed to retrieve the admin server name.

**Action:** Verify that the MBean server is running and accessible.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-10003: Fail to retrieve the current server name. The internal exception is: {0}.**

**Cause:** The MBean server could not be accessed to retrieve the server name based on the current thread.

**Action:** Verify that the MBean server is running and accessible.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-10004: Fail to check if the current server is admin server. The internal exception is: {0}.**

**Cause:** The MBean server could not be accessed to verify that the server in the current thread is the admin server.

**Action:** Verify that the MBean server is running and accessible.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-10005: Fail to retrieve the server log path. The internal exception is: {0}.**

---

**Cause:** The MBean server could not be accessed to retrieve the server log path.

**Action:** Verify that the MBean server is running and accessible.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-10006: Fail to copy the config file from {0} to the server directory {1}. The internal exception is: {2}.**

**Cause:** The server config directory could not be accessed.

**Action:** Use the applyJRF() wlst command to ensure that the server has been properly configured.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-10007: Fail to retrieve the system property domain.home.**

**Cause:** The system property domain.home was not specified during WebLogic server startup.

**Action:** Specify the system property domain.home when starting the WebLogic server.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-10012: Fail to retrieve the property for the Common Components Home.**

**Cause:** The Common Components Home property was not set.

**Action:** Set the Oracle Home property using the system property common.components.home or the environment variable COMMON\_COMPONENTS\_HOME.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-10013: The specified Oracle Home directory {0} does not exist.**

**Cause:** The Common Components Home directory did not exist.

**Action:** Verify that Common ComponentsHome, specified through the system property common.components.home or environment variable COMMON\_COMPONENTS\_HOME, is a valid directory.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-10014: Fail to retrieve the current server name. The internal exception is: {0}.**

**Cause:** The MBean server could not be accessed to retrieve the application server platform information.

**Action:** Verify that the MBean server is running and accessible.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-10015: The specified application server platform {0} is not supported by JRF.**

**Cause:** JRF does not support the specified platform.

**Action:** Contact Oracle Support Services for the JRF supported application server platforms.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-10016: The initialization of the server config directory from the Oracle Home {0} with domain directory {1} for copying fails. The internal exception is: {2}.**

**Cause:** Could not retrieve the servers from the domain config.xml file.

**Action:** Verify that the domain contains a valid config.xml file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-10017: Unable to invoke {0} because the domain {1} has not been extended with JRF template.**

**Cause:** Domain has not been extended with JRF template.

**Action:** Apply JRF template to the domain.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-10018: Server or cluster "{0}" is not found.**

**Cause:** The server or cluster is not found.

**Action:** Create the server or cluster.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-10019: Could not obtain edit lock on the domain**

**Cause:** Domain is being edited by someone else

**Action:** Wait until the edit lock on the domain is released and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-10020: Could not load/instantiate a WebLogic server platform support instance.**

**Cause:** Could not load/instantiate a WebLogic server platform support instance.

---

**Action:** Check if the server platform support class can be loaded/instantiated by the classloader.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-10021: Could not load/instantiate a WebSphere server platform support instance.**

**Cause:** Could not load/instantiate a WebSphere server platform support instance.

**Action:** Check if the server platform support class can be loaded/instantiated by the classloader.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-10022: Could not load system property 'oracle.domain.config.dir'.**

**Cause:** Could not load system property 'oracle.domain.config.dir'.

**Action:** Verify JRF is installed and provisioned properly and the system property 'oracle.domain.config.dir' is set.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-10023: Could not load system property 'oracle.server.config.dir'.**

**Cause:** Could not load system property 'oracle.server.config.dir'.

**Action:** Verify JRF is installed and provisioned properly and the system property 'oracle.server.config.dir' is set.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-10024: JRF is unable to determine the current application server platform.**

**Cause:** JRF is unable to determine the current platform.

**Action:** Contact Oracle Support Services for the JRF supported application server platforms.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-10025: Could not load/instantiate a JBoss server platform support instance.**

**Cause:** Could not load/instantiate a JBoss server platform support instance.

**Action:** Check if the server platform support class can be loaded/instantiated by the classloader.

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**JRF-10026: Failed to get application server edition**

**Cause:** JRF Failed to retrieve application server edition

**Action:** Verify that the application server is installed and accessible.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-10027: Operation is not supported on this application server edition**

**Cause:** Operation is not supported on this platform edition.

**Action:** Verify it is the right application server edition.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-20008: No domain has been read**

**Cause:** JRF detects that domain has not been read.

**Action:** Read the domain offline or connect online before invoke JRF WLST command.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-20009: JRF component or service with type "{0}" and name "{1}" is not found.**

**Cause:** The WLST applyJRF command is out-of-sync with the template that is used to extend the domain, or domain has not been installed with JRF.

**Action:** Use the wlst.sh/cmd from the same Oracle Home that contains the JRF template, which was used to extend the domain; or extend the domain with JRF template if JRF is not installed

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-20010: {0} is not found.**

**Cause:** file not found

**Action:** Verify oraclehomeproperties.xml exist

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-20011: Node GUID does not exist or node is empty in {0}.**

**Cause:** node not found or no value

**Action:** Verify oraclehomeproperties.xml exist

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**JRF-20013: Target does not exist or not valid : {0}.**

**Cause:** target not found or not valid

**Action:** Verify target exists and valid

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-20014: Failed to create library at : {0}.**

**Cause:** Creating shared library failed

**Action:** Verify server connection

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-20015: Failed to create custom service : {0}.**

**Cause:** Creating custom service failed

**Action:** Verify server connection

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-20016: JRF\_FAILED\_CREATE\_URLPROVIDER : {0}.**

**Cause:** Creating URL Provider failed

**Action:** Verify server connection

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-20017: Failed to config jvm args for : {0}.**

**Cause:** Config JVM memory arguments failed

**Action:** Verify server connection

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-20018: Failed to add jvm system property for : {0}.**

**Cause:** Adding system property failed

**Action:** Verify server connection

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**JRF-20019: Failed to parse template: {0}.**

**Cause:** Template has error

**Action:** Verify template

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-20020: Failed to get variable {0} from {1}.**

**Cause:** Get variable failed

**Action:** Verify variable.xml

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-20021: Failed to update targets of application {0}.**

**Cause:** Failed to update application target

**Action:** Verify application

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-20022: Failed to update {0}.**

**Cause:** Failed to update oracle jdbc driver path

**Action:** Verify server

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-20023: Failed to install application {0}.**

**Cause:** Failed to install application

**Action:** Verify application

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-20024: Failed to create variable {0} for {1}.**

**Cause:** Failed to create variable

**Action:** Verify server

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-20025: Need to apply jrf template to cell.**

**Cause:** Cell is not jrf enabled

---

**Action:** Apply jrf template to the cell since this cell is not jrf enabled

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-20026: Could not load/instantiate {0} JRFService instance.**

**Cause:** Could not load/instantiate a JRFService implementation class instance.

**Action:** Check if JRFService implementation class in the error message can be loaded/instantiated by the classloader.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-20028: JRFService not supported**

**Cause:** JRFService is not supported.

**Action:** Check if the server has related JRFService available.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-20029: MapModulesToServers is disabled, cannot modify target of application {0}.**

**Cause:** MapModulesToServers is disabled, cannot modify target of application.

**Action:** Enable MapModulesToServers task for this application

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**JRF-20030: Enable StartupBeansService failed on server {0}.**

**Cause:** Enable StartupBeansService failed

**Action:** Verify server connection

**Level:** 1

**Type:** ERROR

**Impact:** Configuration



---

## MAPVIEWER-00001 to MAPVIEWER-03107

**MAPVIEWER-00001: No 'xml\_request' parameter found in the request.**

**Cause:** The incoming HTTP request did not contain the mandatory parameter named 'xml\_request'.

**Action:** Ensure the HTTP request for MapViewer contains the required parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-00002: Could not get a free MapMaker. Server is busy?**

**Cause:** MapViewer could not obtain the necessary resource to process an incoming request.

**Action:** Try increase the value of the "number\_of\_mappers" attribute in the definition of the involved data source.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-00003: SQL error occurred while generating map.**

**Cause:** MapViewer encountered an error while executing a SQL query.

**Action:** Check the MapViewer server logs for details about the SQL exception and take corresponding actions.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-00004: Unable to add a predefined theme.**

**Cause:** MapViewer could not add or load a pre-defined theme while processing the current map request.

**Action:** Ensure the pre-defined theme exists in the database or is accessible via the given data source.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**MAPVIEWER-00005: Error while compressing raw image data.**

**Cause:** MapViewer could not successfully compress a generated map image into the requested file format.

**Action:** Check the MapViewer server logs for the actual stack trace and take corresponding actions.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-00006: Location for saving map image files not specified.**

**Cause:** MapViewer could not obtain the path information for saving generated map files.

**Action:** Check the MapViewer config file and make sure a path for saving image files are specified or the default path is a valid one.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-00007: No map image generated.**

**Cause:** MapViewer did not generate a map image.

**Action:** Check the MapViewer server logs for details/exceptions and take corresponding actions.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-00008: Unable to add local theme(s).**

**Cause:** MapViewer could not create a new local theme for the current map request.

**Action:** Check the MapViewer server logs for details/exceptions and take corresponding actions. Make sure the individual Geo-Features are in proper format.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-00009: Unable to add JDBC theme(s).**

**Cause:** MapViewer could not create a new JDBC (dynamic) theme for the current map request.

**Action:** Check the MapViewer server logs for details/exceptions and take corresponding actions. Make sure the data source information is correct, and characters in the user supplied SQL query are properly escaped for XML.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**MAPVIEWER-00010: Error loading MapViewer configuration file.**

**Cause:** MapViewer could not properly load its configuration file.

**Action:** Make sure the XML configuration file is in valid and well-formed format.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-00011: Error creating a map data source.**

**Cause:** MapViewer could not create a new data source.

**Action:** Make sure correct database connection info are supplied, including host name, database instance name/sid, listener port and login user/password. Also make sure the host name or IP address is reachable by the host running MapViewer server.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-00012: Error obfuscating data source password in the config file.**

**Cause:** MapViewer could not obfuscate the login password for a data source defined in its config file.

**Action:** Make sure the password is prefixed with an exclamation point (!).

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-00013: Clear-text passwords in the config file must be prefixed with a '!' (exclamation mark).**

**Cause:** Clear text password in the MapViewer config file was not pre-fixed with '!'.

**Action:** Make sure the database login password for any data source defined in the config file is prefixed with an exclamation point (!).

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-00014: Error adding a MARKER style from an image URL.**

**Cause:** MapViewer could not create a dynamic MARKER style that is based on a URL.

**Action:** Make sure the URL of the image is reachable from the host running MapViewer server. If MapViewer is running behind a firewall, you may need to setup HTTP proxy information in MapViewer's config file, or via JVM run-time properties.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**MAPVIEWER-00015: Cannot fetch image from given URL**

**Cause:** MapViewer could not fetch and load an image from a given URL.

**Action:** Make sure the URL of the image is reachable from the host running MapViewer server. If MapViewer is running behind a firewall, you may need to setup HTTP proxy information in MapViewer's config file, or via JVM run-time properties.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-00016: Error while attempting to clear a mapping metadata cache.**

**Cause:** MapViewer could not clear the cached mapping metadata (style/theme/basemap definitions) for a given data source from the memory.

**Action:** Make sure a correct data source name is specified. Also check MapViewer server logs for possible exceptions and stack traces.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-00017: MapViewer is not ready. Please try again later.**

**Cause:** MapViewer was still starting core services such as the mapping servlet. If this error still occurs 30 seconds after starting MapViewer, it may have stuck trying to connect to certain database instance(s).

**Action:** Check and monitor MapViewer server logs to see which server has not been started yet. Check data source definitions in the config file and make sure all the database instances involved are up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-00018: Error parsing XML map request.**

**Cause:** MapViewer encountered error while parsing an XML map request.

**Action:** Make sure a well formed and valid XML map request is sent to the MapViewer server.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-00019: Specified data source does not exist.**

**Cause:** A specified data source did not exist or is known by this MapViewer server.

**Action:** Make sure a correct data source name is supplied.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**MAPVIEWER-00020: Invalid general-purpose or admin XML request.**

**Cause:** The incoming admin or non-map request was invalid or not supported.

**Action:** Make sure only valid and supported requests are sent to the MapViewer

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-00021: No data source specified in the XML request.**

**Cause:** The incoming request did not specify any data source name, and the MapViewer server has no default data source.

**Action:** Make sure a valid data source is specified as part of the request.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-00101: XML map request: invalid 'geoFeature' element found.**

**Cause:** The incoming map request contained an invalid 'geoFeature' element.

**Action:** Make sure all the 'geoFeature' elements have valid syntax.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-00102: XML map request: invalid 'box' element found.**

**Cause:** The incoming map request contained an invalid 'box' element.

**Action:** Make sure the 'box' element has valid syntax.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-00103: XML map request: 'geoFeature' element must have a geometry defined.**

**Cause:** The incoming map request contained one or more 'geoFeature' elements that do not contain any geometry data.

**Action:** Make sure all 'geoFeature' elements contain a geometry.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-00104: XML map request: invalid geometry definition found.**

**Cause:** A 'geoFeature' element with invalid geometry data was found in the XML map request.

**Action:** Make sure all 'geoFeature' elements contain a valid geometry.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**MAPVIEWER-00105: XML map request: 'geoFeature' does not support postal address.**

**Cause:** A 'geoFeature' element with postal/street address was found in the XML map request.

**Action:** Currently 'geoFeature' elements could not use street address string to specify the location.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-00106: XML map request: invalid JDBC theme definition.**

**Cause:** The incoming map request contained an invalid JDBC theme.

**Action:** Make sure the JDBC theme(s) have proper syntax.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-00107: XML map request: 'center' element does not contain a 'geoFeature' sub-element.**

**Cause:** The 'center' element of the incoming map request did not contain a 'geoFeature' sub-element.

**Action:** The 'center' element must have a 'geoFeature' sub-element that specifies a point geometry for the map center.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-00108: XML map request: 'center' element must define either a 'size' or 'scale' attribute.**

**Cause:** The 'center' element of the incoming map request did not contain any size or map-scale information.

**Action:** The 'center' element must have either a 'size' or 'scale' attribute that defines the map data window.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-00109: XML map request: invalid map size or scale value.**

**Cause:** The 'center' element of the incoming map request contained an invalid size or scale value.

**Action:** Make sure a proper value is specified for the 'size' or 'scale' attribute of the 'center' element in the XML map request.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**MAPVIEWER-00110: XML map request: invalid map height/width.**

**Cause:** The incoming map request specified an invalid image width or height value.

**Action:** Make sure a proper value (positive integer) is specified for both the width and height attributes of the root 'map\_request' element.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-00111: XML map request: invalid theme (min/max) scale range.**

**Cause:** Some theme(s) in the incoming map request contained invalid min/max scale range specification.

**Action:** Make sure proper value scale ranges are set for all themes in the map request.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-00112: XML map request: invalid WMS theme specified.**

**Cause:** The incoming map request contained an invalid WMS theme.

**Action:** Make sure all WMS theme(s) are properly defined in the XML map request.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-00113: Permission denied for this operation.**

**Cause:** The requested operation was not permitted by the MapViewer server.

**Action:** Make sure your operation is permitted by MapViewer. For instance the server may disallow JDBC themes in the map request, or disable direct INFO requests. You will need to either avoid performing these operations or modify MapViewer configuration to allow these.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-00114: Invalid type for dynamic binding parameter.**

**Cause:** The incoming map request supplied invalid value(s) for a theme's binding variable.

**Action:** Make sure values for your theme's binding parameters are all of correct type.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**MAPVIEWER-00115: list\_predefined\_themes: No base map found for map tile layer.**

**Cause:** The 'list\_predefined\_themes' request specified a map tile layer that is based on a non-existent base map.

**Action:** Make sure the base map for the specified map tile layer exists in the database view.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-00116: list\_predefined\_themes: Map tile layer not found.**

**Cause:** The 'list\_predefined\_themes' request specified a map tile layer that is not found.

**Action:** Make sure the specified map tile layer exists in the database view.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-06001: FOI width value is wrong.**

**Cause:** MapViewer received an invalid width value for a FOI request.

**Action:** This typically indicates an application coding error, for instance, the JavaScript function MVMapView.display() may have been invoked before the map container DIV object is fully materialized by the browser.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-06002: FOI height value is wrong.**

**Cause:** MapViewer received an invalid height value for a FOI request.

**Action:** This typically indicates an application coding error, for instance, the JavaScript function MVMapView.display() may have been invoked before the map container DIV object is fully materialized by the browser.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-06003: FOI ratX value is wrong.**

**Cause:** MapViewer received an invalid ratX value for a FOI request.

**Action:** This typically indicates an application coding error, for instance, the JavaScript function MVMapView.display() may have been invoked before the map container DIV object is fully materialized by the browser.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-06004: FOI ratY value is wrong.**

**Cause:** MapViewer received an invalid ratY value for a FOI request.



---

**Action:** This typically indicates an application coding error, for instance, the JavaScript function MVMapView.display() may have been invoked before the map container DIV object is fully materialized by the browser.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-06005: FOI bounding box value is wrong.**

**Cause:** MapViewer received an invalid bounding box for a FOI request.

**Action:** This error should never happen. Contact Oracle Support if the issue persists.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-06006: Error rendering an FOI.**

**Cause:** N/A

**Action:** N/A

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-06007: Error rendering a FIG.**

**Cause:** MapViewer encountered an error while rendering a feature of interest (FOI) object.

**Action:** Check the MapViewer server side log files for the actual cause.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-06008: Error rendering a POI.**

**Cause:** MapViewer encountered an error while rendering a point of interest (POI) image.

**Action:** Check the MapViewer server side log files for the actual cause.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-06009: Error processing an FOI request.**

**Cause:** MapViewer encountered an error while processing a feature of interest (FOI) request.

**Action:** Check the MapViewer server side log files for the actual cause.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**MAPVIEWER-06010: Can not get style feature information from database.**

**Cause:** N/A

**Action:** N/A

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-06011: Unsupported FOI request type.**

**Cause:** MapViewer encountered an unknown type of feature of interest (FOI) request.

**Action:** You should never see this error.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-06012: Incorrect FOI version number.**

**Cause:** N/A

**Action:** N/A

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-06013: Incorrect FIG 'gtype' number.**

**Cause:** MapViewer encountered an invalid geometry type ('figgtype') in a FIG request.

**Action:** Contact Oracle Support if the issue persists.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-06014: FOI style not found.**

**Cause:** MapViewer could not find the style specified in the FOI request.

**Action:** Make sure the style specified in your individual FOI or theme-based FOI layer request exists.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-06015: Map cache name is missing for bounding FOI theme.**

**Cause:** MapViewer could not find the required map tile layer name in a bounding theme request.

**Action:** Make sure a map tile layer has been added to your map before issuing a bounding theme request.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-06016: JDBC theme based FOI support is disabled for the given data source.**

**Cause:** MapViewer is configured to disable JDBC theme based FOI on the given data source.

**Action:** Enable JDBC theme based FOI support in data source definition.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-06017: Create tile admin task: Map tile layer not found.**

**Cause:** N/A

**Action:** N/A

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01000: No themes to render.**

**Cause:** The Map request had no base map or themes defined.

**Action:** Add a base map that contains a list of themes or define individual themes on your request.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01001: Cannot load base map.**

**Cause:** A database error may have happened while reading the base map definition from USER\_SDO\_MAPS view. Or the requested base map was not defined.

**Action:** Make sure the basemap exists in the database; also check MapViewer log for database error and additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01002: Cannot load theme.**

**Cause:** A database error may have happened while reading the theme definition from USER\_SDO\_THEMES view. Or the requested theme was not defined.

**Action:** Make sure the theme exists in the database; also check log for database error and additional details.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**MAPVIEWER-01003: Cannot load style.**

**Cause:** A database error may have happened while reading the style definition from USER\_SDO\_STYLES view. Or the requested style was not defined.

**Action:** Make sure the style exists in the database; also check log for database error and additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01004: Bounding Themes returned null MBR. Themes were not rendered.**

**Cause:** Bounding themes may have been used to define the query window for the map request, but it produced no spatial feature. The map request was aborted due to this condition.

**Action:** Change the bounding theme or themes definition, so the definition defines a select statement that returns one or more features. In MapBuilder this message can happen when previewing base maps with full extent (no center and size defined). MapBuilder uses the first theme of the base map as the bounding theme when a full extent is applied. If this first theme returns no features for a full extent request, then you should remove it from the base map list of themes.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01005: No spatial data to render.**

**Cause:** A full extent request (no center and size defined) returned no features.

**Action:** Change the theme or themes definition to select one or more features.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01006: Invalid style type for Point features.**

**Cause:** The style type used could not be applied to render point features.

**Action:** Do not use AREA or LINE styles to render point features.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01007: Feature has no geometric representation.**

**Cause:** The feature geometry was null.

**Action:** Check the feature geometry column in the database table.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**MAPVIEWER-01008: Cannot parse xml style string: missing closing "**

**Cause:** XML string was not correct and could not be parsed.

**Action:** Check the missing closing character "".

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01009: Invalid style class specified in xml style string.**

**Cause:** Attribute class on the xml definition was undefined.

**Action:** Assign a valid value to attribute class  
(COLOR,LINE,TEXT,MARKER,AREA).

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01010: Style cannot be created from a xml string that does not define the style class.**

**Cause:** Unknown style class type defined.

**Action:** Change the attribute class value to a known type  
(COLOR,LINE,TEXT,MARKER,AREA).

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01011: Cannot find a custom image renderer for format:**

**Cause:** Image theme format was not supported and there was no custom image renderer defined for this format.

**Action:** Use a known image format (GIF,JPEG,PNG,TIFF) or implement a custom image renderer for this format.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01012: Cannot create image to render from byte array.**

**Cause:** Image array of bytes may be null or corrupted.

**Action:** Check image data source. If it comes from a database column, verify if the column contents is not null. If image contents seems OK, then report error to Oracle.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01013: Invalid base map definition.**

**Cause:** XML string for base map definition could not be parsed.

**Action:** Fix the XML string that defines the base map.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01014: Invalid styling rules definition.**

**Cause:** XML string for theme styling rules could not be parsed.

**Action:** Fix the XML string that defines the theme styling rules.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01015: Unable to retrieve theme definition.**

**Cause:** Theme did not exist in USER\_SDO\_THEMES view.

**Action:** Add a theme definition to user themes view.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01016: Theme with undefined styling rules.**

**Cause:** Styling rules section of theme XML definition was null.

**Action:** Theme styling rules section must be defined on the theme definition.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01017: Undefined image column attribute in image theme definition.**

**Cause:** Image theme definition did not contain the image column attribute.

**Action:** Define attribute 'image\_column' on image theme definition.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01018: Undefined image format attribute in image theme definition.**

**Cause:** Image theme definition did not contain the image format attribute.

**Action:** Define attribute 'image\_format' on image theme definition.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01019: One or more attributes missing in image theme definition.**

**Cause:** Some mandatory attributes were missing from image theme definition.

**Action:** Attributes to defined image column ('image\_column') and image format ('image\_format') must be defined on image theme definition.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01020: Undefined network name attribute in network theme definition.**

**Cause:** Network theme definition did not contain the network name attribute.

**Action:** Define attribute 'network\_name' on network theme definition.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01021: Undefined topology name attribute in topology theme definition.**

**Cause:** Topology theme definition did not contain the topology name attribute.

**Action:** Define attribute 'topology\_name' on topology theme definition.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01022: Undefined WFS service URL attribute in WFS theme definition.**

**Cause:** WFS theme definition did not contain the service URL attribute.

**Action:** Define attribute 'service\_url' on WFS theme definition.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01023: Unable to find entry in ALL\_SDO\_GEOM\_METADATA table for theme:**

**Cause:** Theme base table and spatial column have not been registered on user metadata view (USER\_SDO\_GEOM\_METADATA).

**Action:** Register the theme base table and spatial column on user metadata view, by inserting a row in USER\_SDO\_GEOM\_METADATA view.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01024: Unable to convert query window SRID to theme SRID.**

**Cause:** Conversion of map request query window projection to theme projection has failed. The database procedure sdo\_cs.transform was used to convert coordinates from one SRID to another SRID.

**Action:** Check log for database errors.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**MAPVIEWER-01025: Cannot use ratio scale mode with theme that has unknown SRID.**

**Cause:** Request with a ratio scale was attempted, but the data did not contain a valid Oracle SRID.

**Action:** Assign a valid SRID to the spatial data.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01026: Unable to get an instance of spatial provider.**

**Cause:** Custom spatial provider was not be defined in MapViewer's configuration file, or provider class path was not accessible.

**Action:** Check spatial provider section on MapViewer's configuration file for the definition of the provider. If it is defined there, check the library jar file path, and make sure it is part of the classpath application.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01027: Custom geometry theme must have a spatial data provider defined.**

**Cause:** Custom geometry theme definition did not contain the spatial provider attribute.

**Action:** Define attribute 'provider\_id' on custom theme definition.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01028: Custom spatial data provider is null.**

**Cause:** Custom spatial data provider was not initialized and is null.

**Action:** Check if provider name is defined on theme definition, and also check if provider class library is defined on MapViewer's configuration file and is part of the application classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01029: Undefined geometry column for dynamic geometry theme.**

**Cause:** Dynamic geometry theme definition did not contain the spatial column attribute.

**Action:** Define attribute 'spatial\_column' on dynamic geometry theme definition.

**Level:** 1

**Type:** ERROR

**Impact:** Process



---

**MAPVIEWER-01030: A set of four question marks separated by commas is required to define a geometry theme with a dynamic SDO\_FILTER.**

**Cause:** A set of question marks must be used in the SDO\_ORDINATE\_ARRAY, for a dynamic geometry theme with a SQL expression that also includes the spatial filter operator (SDO\_FILTER). These question marks will be replaced with values based on the map request center and size.

**Action:** Use the following pattern for the ordinate array on the SDO\_FILTER expression: SDO\_ORDINATE\_ARRAY(?,?,?,?).

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01031: Not enough binding parameters defined.**

**Cause:** The theme definition contained binding parameters on its query expression, but the parameters were not provided in the map request.

**Action:** Pass the theme binding parameters to your theme definition, using the methods provided by the javascript API (Oracle Maps), or by the java API, or if issuing a direct XML request define the binding parameters on the theme section.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01032: GeoRaster spatial extent is null.**

**Cause:** The GeoRaster object contained a null geometry as its spatial extent.

**Action:** Update the GeoRaster spatial extent using the PLSQL procedure sdo\_geor.generateSpatialExtent.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01033: Invalid image stretch low value.**

**Cause:** Image stretch low value must be numeric and ranging from 0 to 256. The default value 0 is used if number is out of this range.

**Action:** Define a numeric value within the specified range.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01034: Invalid image stretch high value.**

**Cause:** Image stretch high value must be numeric and ranging from 0 to 256. The default value 100 is used if number is out of this range.

**Action:** Define a numeric value within the specified range.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**MAPVIEWER-01035: Invalid brightness value.**

**Cause:** Image brightness value must be numeric and ranging from 0 to 256. The default value 0 is used if number is out of this range

**Action:** Define a numeric value within the specified range.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01036: Undefined brightness value for image processing.**

**Cause:** Image brightness value must be defined when brightness operation is to be applied on a GeoRaster object.

**Action:** Define parameter 'value' for brightness in the theme definition.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01037: Invalid contrast value.**

**Cause:** Image contrast value must be numeric and ranging from 0 to 256. The default value 256 is used if number is out of this range

**Action:** Define a numeric value within the specified range.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01038: Undefined contrast value for image processing.**

**Cause:** Image contrast value must defined when contrast operation is to be applied on a GeoRaster object.

**Action:** Define parameter 'value' for contrast in the theme definition.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01039: Invalid threshold value.**

**Cause:** Image threshold value must be numeric and ranging from 0 to 256. The default value 0 is used if number is out of this range

**Action:** Define a numeric value within the specified range.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01040: Invalid low threshold value.**

**Cause:** Image threshold low value must be numeric and ranging from 0 to 256. The default value 0 is used if number is out of this range

**Action:** Define a numeric value within the specified range.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01041: Invalid high threshold value.**

**Cause:** Image threshold high value must be numeric and ranging from 0 to 256. The default value 0 is used if number is out of this range

**Action:** Define a numeric value within the specified range.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01042: Invalid image column type for image theme.**

**Cause:** Image theme data must be stored in a column of type BLOB or ORDIMAGE.

**Action:** Assign a valid image column to the image theme definition.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01043: Network category is null.**

**Cause:** Network model category information was null on the metadata view.

**Action:** Check the contents of column 'network\_category' on the network metadata USER\_SDO\_NETWORK\_METADATA.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01044: Network geometry type is null.**

**Cause:** Network model geometry type information was null on the metadata view.

**Action:** Check the contents of column 'geometry\_type' on the network metadata USER\_SDO\_NETWORK\_METADATA.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01045: Undefined topology column for topology theme.**

**Cause:** Topology theme definition did not contain the spatial column attribute.

**Action:** Define attribute 'spatial\_column' on topology theme definition.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01046: WFS theme server URL is null.**

**Cause:** WFS server URL was not been defined.

**Action:** Check if WFS theme definition has a value for attribute 'service\_url'.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01047: WMS theme server URL is null.**

**Cause:** WMS server URL was not been defined.

**Action:** Check if WMS theme definition has a value for attribute 'service\_url'.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01048: Cannot load WMS map image.**

**Cause:** Unable to retrieve image from WMS server.

**Action:** Check if WMS server URL defined on theme definition is accessible.  
Change timeout value on theme definition if timeout has happened.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-01049: X or Y column not found in SQL query.**

**Cause:** N/A

**Action:** N/A

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-02000: There is no database connection loaded.**

**Cause:** Operation could not be performed unless a database connection has been added or loaded.

**Action:** Use MapBuilder interface options to create or to add (load) a connection.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-02001: Connection test failed.**

**Cause:** Connection parameters may be wrong, database may be down or listener may not be running.

**Action:** Check MapViewer log or console for database error, and change connection parameters if needed.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-02002: Unable to register data source connection.**

---

**Cause:** Connection parameters may be wrong, database may be down or listener may not be running.

**Action:** Check MapViewer log or console for database error. If connection has been already added to MapBuilder, check connections parameters in MapBuilder preferences file (default file is oasmapbuilder.xml), and modify them if needed. Restart MapBuilder to load the current preferences file. If it is a new connection being added, change the connection parameters and test it before trying to add it.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-02050: Unable to save base map definition.**

**Cause:** Database error may have happened while saving base map in USER\_SDO\_MAPS view.

**Action:** Check MapViewer log for database error.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-02051: Unable to save style definition.**

**Cause:** Database error may have happened while saving style in USER\_SDO\_STYLES view.

**Action:** Check MapViewer log for database error.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-02052: Unable to save theme definition.**

**Cause:** Database error may have happened while saving theme in USER\_SDO\_THEMES view.

**Action:** Check MapViewer log for database error.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-02053: Unable to save tile layer definition.**

**Cause:** Database error may have happened while saving tile layer in USER\_SDO\_CACHED\_MAPS view.

**Action:** Check MapViewer log for database error.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-02054: Unable to duplicate metadata.**

**Cause:** Database error may have happened while saving a duplicate metadata. Make sure the new metadata name does not exist on the target database.

---

**Action:** Check MapViewer log for database error.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-02055: Unable to delete metadata.**

**Cause:** Database error may have happened while removing metadata from database view.

**Action:** Check MapViewer log for database error.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-02100: Invalid advanced style type.**

**Cause:** Style XML definition contains an invalid or unknown advanced style type.

**Action:** Fix the style XML definition with an external tool, and refresh the connection in MapBuilder.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-02101: Unable to build theme definition.**

**Cause:** Database error may have happened while reading theme parameters.

**Action:** Check MapViewer log for database error.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-02102: Unable to parse hexadecimal value.**

**Cause:** String value is not recognized as a valid hexadecimal expression.

**Action:** Use pattern #xxxxxx to represent the hexadecimal color value. Character # must be first followed by six digits or letters. Each x may be a digit between 0 and 9, or one of the letters "a,b,c,d,e,f".

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-02103: Unable to parse style definition.**

**Cause:** Database related errors or SQL exceptions may have happened while reading style parameters.

**Action:** Check MapViewer log for database related errors or SQL exceptions.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**MAPVIEWER-02104: System will not be able to save this file.**

**Cause:** The file path is not accessible to the system.

**Action:** Define a file name with a valid system path.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-02105: Unable to save HTML file.**

**Cause:** IO error may have happened while saving file in disk.

**Action:** Check MapViewer log for error details, and change file name if needed.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-02200: Invalid raster block size.**

**Cause:** Block size must be a positive even number and power of two.

**Action:** Define a value that is positive and power of two such as 64, 128 or other.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-02201: Unable to create GeoRaster table.**

**Cause:** Database related errors or SQL exceptions may have happened while creating a GeoRaster table.

**Action:** Check MapViewer log for database related errors or SQL exceptions.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-02202: Unable to create GeoRaster raster data table.**

**Cause:** Database related errors or SQL exceptions may have happened while creating a GeoRaster raster data table. A raster data table name can not be repeated over cross schemas.

**Action:** Check MapViewer log for database related errors or SQL exceptions.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-02203: Unable to insert GeoRaster record.**

**Cause:** Database related errors or SQL exceptions may have happened while creating a new GeoRaster record.

**Action:** Check MapViewer log for database related errors or SQL exceptions.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**MAPVIEWER-02204: Unable to import image file.**

**Cause:** Database related errors or SQL exceptions may have happened while importing image into a GeoRaster record.

**Action:** Check MapViewer log for database related errors or SQL exceptions.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-02205: Unable to georeference GeoRaster object.**

**Cause:** Database related errors or SQL exceptions may have happened while georeferencing the GeoRaster object.

**Action:** Check MapViewer log for database related errors or SQL exceptions, and change georeferencing parameters if needed.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-02206: Unable to update spatial extent of GeoRaster object.**

**Cause:** Database related errors or SQL exceptions may have happened while updating the spatial extent of the GeoRaster object.

**Action:** Check MapViewer log for database related errors or SQL exceptions.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-02207: Unable to generate pyramids for GeoRaster object.**

**Cause:** Database related errors or SQL exceptions may have happened while generating pyramids for the GeoRaster object. MapBuilder uses resampling mode NN.

**Action:** Check MapViewer log for database related errors or SQL exceptions.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-02208: Unable to retrieve GeoRaster object size.**

**Cause:** Database related errors or SQL exceptions may have happened while retrieving GeoRaster size from metadata.

**Action:** Check MapViewer log for database related errors or SQL exceptions.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-02209: Unable to save GeoRaster metadata.**



---

**Cause:** Database related errors or SQL exceptions may have happened while registering GeoRaster spatial extent on USER\_SDO\_GEOM\_METADATA view.

**Action:** Check MapViewer log for database related errors or SQL exceptions.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-02210: Unable to create spatial indexes for GeoRaster table.**

**Cause:** Database related errors or SQL exceptions may have happened while creating spatial indexes on GeoRaster SPATIALEXTENT attribute.

**Action:** Check MapViewer log for database related errors or SQL exceptions.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-02300: Spatial data provider is not registered.**

**Cause:** List of registered spatial data providers does not contain the provider name.

**Action:** Check MapBuilder preferences file (default file is oasmapbuilder.xml) to see if it defines the provider parameters. Spatial providers are registered at MapBuilder startup if they are defined on the preferences file.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-02301: Unable to initialize spatial data provider.**

**Cause:** Missing initialization parameters or they are not accepted by the spatial provider.

**Action:** Check spatial provider documentation for initialization parameters.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-02302: Unable to create an instance of spatial provider class.**

**Cause:** Library jar file location may not be accessible to application.

**Action:** Check spatial provider parameters on the preferences file (default file is oasmapbuilder.xml), and modify the jar file location if needed.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-03001: MapViewer cannot process your map request. Check MapViewer log for details.**

**Cause:** MapViewer could not process a map request sent by your Java application.

**Action:** Check the MapViewer server logs written when the error occurred. Correct any mistakes accordingly.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-03002: Cannot check the existence of**

**Cause:** MapViewer could not find the specified mapping metadata or spatial data table.

**Action:** Make sure the mentioned item (metadata such as style/theme/basemap or spatial data table) exists in the data base.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-03003: Cannot add a datasource:**

**Cause:** MapViewer could not add a new data source per your map request.

**Action:** Adding a data source on-the-fly using the Java client API is no longer allowed. Data sources should be defined in the config file or added using the admin web page.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-03004: cannot list pre-defined themes in:**

**Cause:** MapViewer could not get the list of themes in the specified base map.

**Action:** Make sure the base map exists in the database and that it contains pre-defined themes.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-03005: invalid image format specified.**

**Cause:** The image format (for the map response) specified is invalid or not supported.

**Action:** Make sure only image formats specified in the API are used in your code.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-03006: Failed to establish HTTP connection to MapViewer service.**

**Cause:** The client failed to connect to the MapViewer servlet.

**Action:** Make sure the networking configs (such as proxy settings) are correct in the client. Also make sure the correct MapViewer URL is supplied.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**MAPVIEWER-03007: Failed to locate image URL in the XML map response.**

**Cause:** The XML map response from the server does not contain a map image URL.

**Action:** Check MapViewer server logs to see if there is any error when processing the map request.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-03101: Cannot obtain a client handle to the MapViewer service!**

**Cause:** N/A

**Action:** N/A

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-03102: No query string found in the addJDBCTheme JSP tag.**

**Cause:** N/A

**Action:** N/A

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-03103: Missing datasource or JDBC connection information.**

**Cause:** N/A

**Action:** N/A

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-03104: Unknown parameter name specified in the getParam JSP tag.**

**Cause:** N/A

**Action:** N/A

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-03105: Must specify a location/point on the map to identify.**

**Cause:** N/A

**Action:** N/A

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**MAPVIEWER-03106: Error while executing your current map request.**

**Cause:** N/A

**Action:** N/A

**Level:** 1

**Type:** ERROR

**Impact:** Process

**MAPVIEWER-03107: Failed to process map legend request/response.**

**Cause:** N/A

**Action:** N/A

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

## MDS-00001 to MDS-91019

**MDS-00001: exception in Metadata Services layer**

**Cause:** An exception occurred in the Metadata Services layer.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00002: unexpected internal error**

**Cause:** An unexpected internal error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**MDS-00003: error connecting to the database**

**Cause:** A database connection to the metadata repository could not be established.

**Action:** Contact the database administrator or system administrator to get the problem resolved.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00005: unable to find XML element or text "{0}"**

**Cause:** The XML element with the given local name or the text node containing the given data could not be located by traversing through the document while applying customizations to a metadata object. The internal in-memory MDocument structure may be corrupted.

**Action:** Retry the operation. Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

---

**MDS-00008: Attribute "{0}" is not allowed for element {1} namespace {2} in metadata object {3}.**

**Cause:** An attempt was made to add an attribute to an element that does not conform to the element's schema definition.

**Action:** If the Bean API is being used, then determine if the beans need to be regenerated. Otherwise, inspect the element definition for valid attributes.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00010: DuplicateRefException. In document {0} there are multiple elements with the same ID {1}.**

**Cause:** Either an element was being added with an ID that already existed within the document, or a preexisting document had multiple elements with the same ID.

**Action:** Change the ID of the elements so that there is no ID duplication.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00011: unable to create configuration object or MDSInstance due to invalid configuration information: {0}**

**Cause:** The MDS configuration was invalid.

**Action:** Refer to the MDS specification and correct the configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00012: invalid value "{0}" for attribute {1} (type = "{2}") in metadata object {3}**

**Cause:** The value provided for the named attribute was invalid. For example, this error could occur if a named JNDI connection name is incorrect.

**Action:** Provide a valid attribute value.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00013: no metadata found for metadata object "{0}"**

**Cause:** MDS was unable to locate the given metadata object.

**Action:** Confirm the name and location of the metadata object, its existence in the configured metadata stores, and that it is in an accessible namespace.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00016: Ignoring customization for instruction type "{0}" in metadata object "{1}" for customization layer "{2}"/"{3}": not finding element with local reference "{4}"**

---

**Cause:** A customization was not applied because the underlying element to be customized was not found.

**Action:** If the element is expected, examine the base document and any customizations to locate the element.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00017: Customization instruction using local reference(s) : "{0}" is not upgrade safe.**

**Cause:** The customization instruction contained a local reference that was not deemed safe for an upgrade operation.

**Action:** Ensure that the local reference used in the customization instruction would be safe during an upgrade operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00018: Fixed customization for instruction type "{0}" in metadata object "{1}" for customization layer "{2}"/"{3}": not able to find the referenced element with local reference "{4}", inserted the customized element at the best possible location.**

**Cause:** A customization was fixed because the referenced element was not found.

**Action:** Correct the customized element's position if needed.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00019: Customization document contains an invalid instruction "{0}".**

**Cause:** A customization document that was being applied contained an unrecognized instruction.

**Action:** Retry the operation. If necessary, either remove the customization document, or edit it to correct or remove the offending instruction.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00020: Layer value "{0}" contains an invalid character.**

**Cause:** Using a layer value that has an invalid character.

**Action:** Layer value should conform to MDS naming standards.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00029: Invalid namespace: The namespace "{0}" has not been registered with the MetadataManager.**

---

**Cause:** An attempt was made to access a document in an unknown location or namespace.

**Action:** Ensure that the namespace reported is registered in the MDS configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00032: cannot parse the input file: {0}**

**Cause:** An exception occurred while parsing the file.

**Action:** Record the accompanying error and contact the developers of the application.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00033: cannot load the input file: {0}**

**Cause:** An exception occurred while loading the file.

**Action:** Record the accompanying error and contact the developers of the application.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**MDS-00034: cannot write to the output file: {0}**

**Cause:** An attempt to write to the output file failed.

**Action:** Record the accompanying error and contact the developers of the application.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**MDS-00035: cannot load the class: {0}.**

**Cause:** The class file could not be loaded.

**Action:** Ensure the class is available on the classpath so that it can be loaded by the application.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00036: cannot instantiate the class: {0}**

**Cause:** An exception occurred while instantiating a class.

**Action:** Record the accompanying error and contact the developers of the application.

**Level:** 1



---

**Type:** ERROR

**Impact:** Configuration

**MDS-00037: cannot access the class: {0}**

**Cause:** An attempt was made to access an inaccessible class file.

**Action:** Record any accompanying errors and contact the developers of the application.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00039: error while attempting to parse the document {0} using SAX.**

**Cause:** A SAX parsing exception occurred while trying to parse a document.

**Action:** Record the accompanying error and contact the developers of the application.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00040: There are no namespaces registered.**

**Cause:** The operation attempted requires at least one registered namespace.

**Action:** Correct the MDS configuration to include the required namespace schemas.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00041: invalid classpath entry "{0}"**

**Cause:** An entry on the application's classpath did not exist or was invalid.

**Action:** Correct the application's classpath to remove the invalid entry.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00042: Classpath "{0}" does not contain any valid directories or jar files.**

**Cause:** The application's classpath contained no valid entries.

**Action:** Correct the application's classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00043: A name pattern mapping for path {0} already exists.**

**Cause:** The MDS configuration had duplicate namespace mappings.

**Action:** The MDS configuration must be corrected to remove the duplicate namespace mappings.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00044: Metadata for MetadataObject with name {0} already exists in the configured store.**

**Cause:** An attempt was made to create a new Metadata Object. However an object with the same MDSReference already existed.

**Action:** The name or location of one of the objects must be changed.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00047: Use the flushChanges method on the MDSSession to commit the changes.**

**Cause:** Commit was disabled in the PTransaction that was being used.

**Action:** Use the flushChanges method on the MDSSession to commit the changes.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00054: The file to be loaded {0} does not exist.**

**Cause:** An attempt was made to load a persistent document using a URL but the underlying document was not found in the store.

**Action:** Check that the document name is correct and that the store is correctly configured.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00058: Invalid Metadata Path: Metadata Path cannot be null.**

**Cause:** The path used to create a FileMetadataStore was empty. It must point to a directory.

**Action:** Correct the metadata store definition in the application configuration to specify a metadata path.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00068: Unable to find a type definition for: namespace = {0}, local name = {1}, file location = {2}**

**Cause:** A request was made to locate a definition that did not exist in the named schema.

**Action:** Ensure the document contains only elements which are defined in the schema for the indicated namespace.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**MDS-00084: Parameter {0} is invalid.**

**Cause:** The supplied parameter was not of the expected type.

**Action:** Ensure the parameter is of the expected type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00085: Parameter {0} is missing.**

**Cause:** The named parameter was not supplied.

**Action:** Ensure that the named parameter is supplied. If transferring documents ensure a parameter file name is supplied.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00089: Parameter {0} must have a value.**

**Cause:** A required parameter was null.

**Action:** Ensure that the indicated parameter is not null when the method is called.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00090: Error in JNDI lookup operation on MDSInstance name {0}, JNDI name {1}: object found {2} is an instance of class {3} classloader {4}, expected an instance of class {5} classloader {6}.**

**Cause:** An object of an unexpected type was found, and it was bound to the JNDI context as the MDSInstance.

**Action:** Make sure no user-written code is binding anything to the same JNDI name. If the error occurs again try restarting the application. If the error still occurs, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**MDS-00091: Unable to customize {0}, empty or null value for tip customization layer {1}**

**Cause:** The customization layer configured as the tip, has a null or empty value.

**Action:** Ensure that a valid value is supplied for the tip customization layer.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**MDS-00092: DuplicateNodeException. The same bean instance {0} already exists in document {1}.**

**Cause:** An element was being added that already exists as the same bean instance within the document.

**Action:** Either create a new bean instance or remove the duplicate before attempting to insert in the document.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00093: List of values provided for customization layer {0} was empty or null.**

**Cause:** The list of customization layer values was either empty or null.

**Action:** Ensure that a valid list of layer values for the customiizatn layer is provided.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00094: List of CustLayerUsage objects provided was empty or null.**

**Cause:** The list of CustLayerUsage objects was either empty or null.

**Action:** Ensure that a valid list of CustLayerUsage objects is provided.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00111: The value of the property {0} for the component {1} must be set to the default value.**

**Cause:** The indicated component property did not have a default value.

**Action:** Ensure the component property is given a default value.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00153: invalid value for indicator**

**Cause:** The production of merged XML failed.

**Action:** Verify the validity of XML documents and any schemas. If necessary forward these on to Oracle Support Services with the exception message and stack trace.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**MDS-00154: The ContentHandler {0} does not implement org.xml.sax.ext.LexicalHandler.**

**Cause:** MergedXML was passed a ContentHandler that does not implement org.xml.sax.ext.LexicalHandler.

---

**Action:** Use a ContentHandler that implements org.xml.sax.ext.LexicalHandler.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00155: unable to create a JSP file for document {0}**

**Cause:** Oracle MDS was unable to create a JSP source document.

**Action:** Examine the MDS base document, as well as any customizations and translations. If necessary, forward these to Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Files

**MDS-00156: unable to create a JSP output directory {0}**

**Cause:** MDS-JSP integration failed because a problem was encountered while creating a directory.

**Action:** Verify that you have permission to create this directory.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**MDS-00157: unable to write to JSP file {0}**

**Cause:** MDS-JSP integration failed because a problem was encountered while trying to write to a file.

**Action:** Verify that you have permission to create this file.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**MDS-00158: invalid directory: {0}**

**Cause:** MDS-JSP integration failed. An attempt was made to write to an invalid directory.

**Action:** Verify the value of the invalid directory.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**MDS-00159: Invalid value "{0}" for {1} attribute (type = "{2}") in document {4}.**

**Cause:** An attempt was made to write an invalid value to an attribute.

**Action:** Double-check the value and attribute type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00160: no local name has been specified for a resource**

---

**Cause:** An attempt was made to create a resource without giving it a name.

**Action:** Verify that the resource that was created is given a local name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00161: no local name has been specified**

**Cause:** An attempt was made to create a resource without giving it a local name.

**Action:** Verify that the resource that was created is given a local name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00162: invalid attribute value**

**Cause:** An attempt was made to give to an invalid value to an attribute.

**Action:** Verify that the attribute has a valid value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00163: property value missing from element**

**Cause:** An element was missing a property value.

**Action:** Ensure that each parameter used to create the element has a property value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00164: There is a concurrent "{1}" operation on the document "{0}".**

**Cause:** The document on which modification was being attempted had been updated by another user after it was retrieved.

**Action:** Retrieve the document again.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00165: metadata Object "{0}" has changed**

**Cause:** The creation, updating, or renaming of a metadata object failed due to conflicting changes made by another user.

**Action:** Retrieve the document containing the metadata object again.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**MDS-00166: unable to locate the unique identifier, {0}:{1}, that has been configured for the element {2}**

**Cause:** The element that required a unique identifier was created without one.

**Action:** Add a unique identifier attribute to the element.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00167: Invalid local name for mapping "{0}" - an empty string is not allowed.**

**Cause:** A local name was given a null or empty value.

**Action:** Supply a valid local name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00168: MDS object {0} is being used after it or its MDSInstance or PManager has been released.**

**Cause:** An MDS object was used after it or its MDSInstance or PManager had been released

**Action:** Create a new MDSInstance and re-create the MDS object.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**MDS-00169: The MDS instance is not ready for use because metadata deployment is in progress (status is "{0}"). Deployment messages so far are: "{1}".**

**Cause:** The MDS instance cannot be used until metadata deployment has finished.

**Action:** Try again later after metadata deployment has completed.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00170: The MDS instance is not usable because metadata deployment failed with status "{0}".**

**Cause:** Metadata deployment failed with the given status.

**Action:** Please fix the error and redeploy the application's metadata using the importMAR operation on MDS Application Runtime MBean. Also, refer to the error messages that describe the cause exception in the application logs for more information on the actual reason for failure.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00171: Document "{0}" already has unsaved updates on another instance of this metadata object in this session.**

---

**Cause:** An attempt was made to update metadata using more than one instance of the same metadata object at the same time in the same session.

**Action:** Save the changes on the metadata object that already has updates before attempting to update it via another metadata object, or make further modifications on the metadata object on which updates have already been made.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00172: The value "{0}" of local unique attribute {1} on the {2} element that is being inserted or updated in document {3}, is already used by a sibling element.**

**Cause:** An attempt was made to have two local unique attributes with the same value on elements that share the same parent.

**Action:** Use a different value for the local unique attribute on the element that is being inserted or updated.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00173: Attribute {0} of element {1} in document {2} has a null value.**

**Cause:** The value of the named attribute was null.

**Action:** Provide a non-null value for the attribute or remove the attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00500: No metadata store is configured to save the document {0}.**

**Cause:** An attempt was made to save a document, when no writable store was configured.

**Action:** Provide a writable metadata store to save the document.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00501: Document {0} cannot be deleted because no metadata store is configured.**

**Cause:** An attempt to delete a document failed because there was no writable store configured.

**Action:** To delete the document, provide a writable metadata store.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00503: The metadata path "{0}" does not contain any valid directories.**

**Cause:** Either the metadata path was empty or directories on the metadata path did not exist.



---

**Action:** Ensure that the metadata path is not empty and that the directories on the metadata path exist.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00504: failure to create document {0} because metadata store "{1}" is read-only**

**Cause:** An attempt to create a document on a read-only metadata store failed.

**Action:** To create the document, provide a writable metadata store.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00505: failure to save document {0} because metadata store "{1}" is read-only**

**Cause:** An attempt to save a document to a read-only metadata store failed.

**Action:** To save the document, provide a writable metadata store.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00506: failure to get child resources of package {0} because package does not exist in metadata store**

**Cause:** Child resources for the package were not found because specified package did not exist in the metadata store.

**Action:** Verify that the package exists in the metadata store, and then retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00507: failure to delete document {0} because metadata store "{1}" is read-only**

**Cause:** An attempt to delete a document from a read-only metadata store failed.

**Action:** To delete the document, provide a writable metadata store and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00508: There is no content to be read for {0}.**

**Cause:** An attempt was made to read empty metadata.

**Action:** Verify that the metadata has valid content, and then retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**MDS-00509: failure to delete document {0} with file {1}**

**Cause:** An error occurred while the document was being deleted.

**Action:** Verify that the document exists and then retry the operation, or provide a document that exists in the store.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00510: failure to read document {0} because it is not found in the metadata path "{1}"**

**Cause:** The document to be read was not found.

**Action:** Verify that the metadata path is correct and that the document exists in the metadata path.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00511: failure to create document {0} at file {1}**

**Cause:** An error occurred while creating the document in the file store.

**Action:** Retry the operation. Also, refer to the error messages that describe the cause exception in the application logs for more information on the actual reason for failure.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**MDS-00512: failure to create document {0} because file {1} already exists**

**Cause:** An attempt was made to create a file that already existed in the metadata store.

**Action:** Provide a different name for the file to be created, or delete the existing file first, and then retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**MDS-00513: failure to create package {0} because directory {1} already exists**

**Cause:** An attempt to create a package failed because a directory by the same name already existed.

**Action:** Provide a different name for the package to be created and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**MDS-00514: failure to save document {0} to file {1}**

**Cause:** An error occurred while saving the document to a file.

---

**Action:** Retry the operation. Also, refer to the error messages that describe the cause exception in the application logs for more information on the actual reason for failure.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**MDS-00515: failure to create document {0} in the metadata repository**

**Cause:** An error occurred while the document was being created in the metadata repository.

**Action:** Retry the operation. Also, refer to the error messages that describe the cause exception in the application logs for more information on the actual reason for failure.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00516: failure to create document {0} because it already exists in the metadata repository**

**Cause:** An error occurred while the document was being created in the metadata repository because the document already existed.

**Action:** Provide a different name or delete the existing document first, and then retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00517: failure to create package {0} because it already exists in the metadata repository**

**Cause:** An error occurred while the package was being created in the metadata repository because the package already existed.

**Action:** Provide a different package name or delete the existing package first, and then retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00518: failure to create package {0} in the metadata repository**

**Cause:** An error occurred while the package was being created in the metadata repository.

**Action:** Retry the operation. Also, refer to the error messages that describe the cause exception in the application logs for more information on the actual reason for failure.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**MDS-00519: failure to delete document {0} from the metadata repository**

**Cause:** An error occurred while the document was being deleted from the metadata repository.

**Action:** Retry the operation. Also, refer to the error messages that describe the cause exception in the application logs for more information on the actual reason for failure.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00520: failure to read document {0} because it is not in the metadata repository**

**Cause:** The document was not read because it did not exist in the metadata repository.

**Action:** Verify that the document name is correct and that it exists in the metadata repository, and then retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00521: error while reading document {0} from metadata repository**

**Cause:** An error occurred while the document was being read from the metadata repository.

**Action:** Retry the operation. Also, refer to the error messages that describe the cause exception in the application logs for more information on the actual reason for failure.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00522: failure to save document {0} to the metadata repository**

**Cause:** An error occurred while the document was being saved to the metadata repository.

**Action:** Retry the operation. Also, refer to the error messages that describe the cause exception in the application logs for more information on the actual reason for failure.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00526: failure to generate SAX parsing events for document {0}**

**Cause:** An error occurred while parsing the XML document.

**Action:** Verify that the XML document is well-formed. Refer to the error messages that describe the cause exception in the application logs for more information on the actual reason for failure.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**MDS-00531: failure to write to "{0}" because output to "{1}:" protocol is not supported**

**Cause:** An attempt to write modified metadata to a URL failed because the protocol is not supported.

**Action:** Retry writing modified metadata to a supported protocol.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00533: Exception: {3} Attribute "{0}" with an invalid MDS reference "{1}" in document "{2}" is not stored as a typed dependency in the database repository.**

**Cause:** An error occurred while adding a typed dependency from the specified attribute.

**Action:** Refer to the error messages that describe the cause exception in the application logs for more information on the actual reason for failure.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00534: Exception: {3} Subobject {0} in document {2} has invalid value "{1}" for unique identifier; typed dependencies from this subobject are not stored in the database repository.**

**Cause:** An error occurred because the component had an invalid ID.

**Action:** Provide the correct ID value for the application metadata. Also, refer to the error messages that describe the cause exception in the application logs for more information on the actual reason for failure.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00535: cannot change TypeManager associated with a PManager after it is initialized**

**Cause:** An attempt was made to associate TypeManager with PManager after it was initialized.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**MDS-00536: cannot change FileTypeManager associated with a PManager after it is initialized**

**Cause:** An attempt was made to associate FileTypeManager with PManager after it was initialized.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Programmatic

**MDS-00537: unable to rename {0} to {1}**

**Cause:** An error occurred during a rename operation.

**Action:** Retry the rename operation. Also, refer to the error messages that describe the cause exception in the application logs for more information on the actual reason for failure.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00538: failure to rename document {0} because metadata store "{1}" is read-only**

**Cause:** An error occurred during rename operation because the metadata store was configured as read-only.

**Action:** To rename a document, provide a store that can be written to, that is not read-only.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00539: A document can be renamed only within its source store. The new name {1} in this rename operation does not map to the same store as the old name {0}.**

**Cause:** An error occurred during a rename operation. An invalid new name for the rename operation caused the renamed document to be stored in another metadata store.

**Action:** Provide a new, valid document name that maps to the same metadata store that contains the original document.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00541: SAX events cannot be generated for non-XML document {0}.**

**Cause:** An attempt was made to generate SAX events for non-XML documents.

**Action:** Retry the operation. Also, refer to the error messages that describe the cause exception in the application logs for more information on the actual reason for failure.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00547: The read operation is not supported for packages from Web content from the servlet context.**

**Cause:** A read operation was attempted for packages from Web content, which is not supported.

**Action:** The read operation is not supported, therefore no action is required.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**MDS-00550: Updates across multiple stores are not allowed in the same transaction.**

**Cause:** An attempt was made to perform updates across multiple stores in the same transaction.

**Action:** Verify that the document is being saved to the same store on which it exists.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00551: failure to delete package {0} because it is not empty**

**Cause:** An attempt was made to delete a package that was not empty.

**Action:** Delete the contents of the package to be deleted first, and then retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00552: failure to delete package {0} with directory {1}**

**Cause:** An error occurred while deleting the directory for the package.

**Action:** Ensure no files from the directory are opened in other applications and retry the operation. Also, refer to the error messages in the application logs for more information on the actual reason for failure.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**MDS-00554: Package {0} cannot be found in the specified store.**

**Cause:** The requested operation was not completed because the package name that was supplied was invalid.

**Action:** Provide a valid package name and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00555: The partitionName {0} is invalid.**

**Cause:** The requested operation was not completed because the partition name that was supplied was invalid.

**Action:** Provide a valid partition name and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00557: Resource {0} is already locked or is being modified.**

---

**Cause:** An attempt was made to modify a document that was already being modified by another user.

**Action:** Retry modifying the document after the lock is released by the other users. Also, refer to the error messages in the application logs for more information on the actual reason for failure.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**MDS-00558: The partitionName {0} is not available.**

**Cause:** No partition with that name existed.

**Action:** Provide a partition name that exists.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00559: A partition with name {0} already exists.**

**Cause:** The name provided for creating a new partition was already in use by another partition.

**Action:** Provide a different name for the new partition.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00560: The MDS repository is incompatible with the archive. The repository version is {0} whereas archive version is {1}.**

**Cause:** The MDS repository was not compatible with the archive provided.

**Action:** Upgrade the target MDS repository or use a compatible archive for the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**MDS-00561: The create operation is not supported for metadata stores of type "{0}".**

**Cause:** An attempt was made to create a new document or package in a read-only metadata store.

**Action:** Reconfigure the application to use a writable metadata store.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00562: The delete operation is not supported for metadata stores of type "{0}".**

**Cause:** An attempt was made to delete a document from a read-only metadata store.

**Action:** Reconfigure the application to use a writable metadata store.



---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00563: The save operation is not supported for metadata stores of type "{0}".**

**Cause:** An attempt was made to save a document to a read-only metadata store.

**Action:** Reconfigure the application to use a writable metadata store.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00564: GUID feature is not supported for metadata stores of type "{0}".**

**Cause:** An attempt was made to get a document by GUID from a metadata store that does not support GUIDs.

**Action:** Reconfigure the application to use a metadata store that supports GUIDs, such as DBMetadataStore.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00565: The rename operation is not supported for metadata stores of type "{0}".**

**Cause:** An attempt was made to rename a document or package in a read-only store.

**Action:** Reconfigure the application to use a writable metadata store.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00566: The DOM content is NULL for {0}.**

**Cause:** DOM document content provided was null.

**Action:** Provide valid DOM content and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00567: The metadata changes for document "{0}" cannot be written in the underlying store because read-only mode is enabled in the configuration.**

**Cause:** An attempt to change metadata was made while changes were disabled for maintenance operations.

**Action:** Reconfigure the application to not specify read-only mode in the configuration and use a writable metadata store to persist metadata changes.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00568: MetadataStore initialization failure because "{0}" is invalid**

---

**Cause:** The URL store mapping was invalid.

**Action:** Provide a valid URL store mapping.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**MDS-00569: unable to read document {0} from "{1}"**

**Cause:** There was an error reading the document from the URL metadata store.

**Action:** Retry the operation. If the problem persists, verify that the URL metadata store exists.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00570: The name or content exceeds the MDS repository schema size for {0}.**

**Cause:** The metadata name or the content exceeded the schema size.

**Action:** Reduce the length of the metadata name or content, and then retry the operation. Refer to the documentation for the allowed sizes for names and content.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00571: The bean content is NULL for {0}.**

**Cause:** The bean content was null.

**Action:** Provide valid bean content, and then retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00572: failure to get the ConnectionManager because the DBContext is null**

**Cause:** The DBContext value is null. Also, using any MetadataStore, PManager, or MDSInstance that has already been released might lead to this error.

**Action:** Do not use any metadata store, PManager, or MDSInstance that is already released.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00573: The metadata store is already associated with a PManager.**

**Cause:** The PConfig provided for creating the PManager or MDSInstance was already used by another PManager or MDSInstance.

**Action:** Provide a new PConfig when creating the PManager or MDSInstance.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**MDS-00574: The document {0} does not exist in the configured metadata store.**

**Cause:** The document being locked did not exist in the configured metadata store.

**Action:** Ensure that the document to be locked exists, and that the name of the document is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00575: failure to acquire write lock for {0}**

**Cause:** An attempt to acquire a write lock for a document failed.

**Action:** Refer to the cause exception message in application logs for details on the actual cause of the failure.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00576: failure to process {0} because metadata store "{1}" is read-only**

**Cause:** An attempt was made to modify metadata in a read-only metadata store.

**Action:** Provide a writable metadata store to allow modification of the document.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00577: Could not acquire read/write lock for {0} within the default waiting time interval**

**Cause:** Read/Write lock could not be obtained for a file within the waiting time interval.

**Action:** Try the operation again after some time.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**MDS-00578: Failed to process document {0} due to a critical error writing to the repository**

**Cause:** A critical error occurred while the metadata document was being written to the repository.

**Action:** Contact the application administrator with cause exception message details to resolve the repository error.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00579: The document {0} does not have version {1} in the repository.**

**Cause:** Specified version does not exist for the document.

---

**Action:** Provide an existing version for the document.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00580: operation failed for {0} because no metadata-store was defined in the configuration for metadata-store-usage {0}.**

**Cause:** incomplete configuration, no metadata-store was defined for the metadata-store-usage

**Action:** Define the metadataStore for the empty metadata-store-usage.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00581: error deleting partition {0} in file repository {1}**

**Cause:** The directory represented by the file repository or partition is read only.

**Action:** Verify that the metadata path to the repository and partition exist and are writable.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00582: The MetadataStore {0} is writable but does override getMetadataStoreCommunicator() method.**

**Cause:** Configuration used a MetadataStore that was writable but not supporting MetadataStoreCommunicator interface.

**Action:** Override getMetadataStoreCommunicator() in the MetadataStore class to return an appropriate MetadataStoreCommunicator instance.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00583: Could not release read/write lock for {0} because the lock was not found.**

**Cause:** Read/Write lock could not be released because it was already removed from the lock cache.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**MDS-00584: The MDS repository's database platform is different that of the archive. The repository's database platform is {1} whereas the archive's platform is {0}.**

**Cause:** The MDS repository platform was not compatible with the archive provided.

**Action:** Use a platform compatible archive for the operation.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00585: Failure to create deployment lineage because metadata store "{0}" is read-only**

**Cause:** An attempt was made to create deployment lineage in a read-only metadata store. Deployment lineage in repository represents Application name and MAR module name.

**Action:** Configure a metadata store that supports deployment management, typically a DBMetadataStore.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00586: ArchiveMetadataStore is restricted to be used with MDS Transfer operation only. Reading or writing files in ArchiveMetadataStore is not supported outside of transfer.**

**Cause:** An attempt was made to read or write files in ArchiveMetadataStore outside of transfer.

**Action:** ArchiveMetadataStore is not supported outside of transfer. Either use this ArchiveMetadataStore for MDS transfer operation or use some other MetadataStore to store your files.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00588: Cannot replace the original archive file {0} with the final archive file {1} because the final archive file could not be renamed to {0}.**

**Cause:** The final archive file could not be renamed to the original archive file name.

**Action:** Look at the cause exception for more details and take corresponding actions.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00589: Error occurred while creating the final archive file {0}.**

**Cause:** Some exception occurred while creating the final archive.

**Action:** Look at the cause exception for more details and take corresponding actions.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00590: Error occurred while opening or closing the input/output stream for archive file {0}.**

---

**Cause:** Some exception occurred while opening or closing the input/output stream for archive file.

**Action:** Look at the cause exception for more details and take corresponding actions.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00591: "{0}" operation is not supported in ArchiveMetadataStore.**

**Cause:** An unsupported operation has been attempted in ArchiveMetadataStore.

**Action:** Look at the ArchiveMetadataStore javadoc for supported operations.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00592: Error occurred while initializing FileMetadataStore connection for the temporary directory.**

**Cause:** An error occurred while initializing the FileMetadataStore connection for the temporary directory.

**Action:** Look at the cause exception for more details and take corresponding actions.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00593: Unable to read the file {0} from archive {1}.**

**Cause:** Some I/O Exception occurred while reading the given file from archive.

**Action:** Look at the cause exception for more details and take corresponding actions.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00594: Unable to write the file {0} to archive {1}.**

**Cause:** Some I/O Exception occurred while writing the given file to archive.

**Action:** Look at the cause exception for more details and take corresponding actions.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00595: The parent directory {0} given in archive file path does not exist. Cannot create ArchiveMetadataStore for the archive file {1}.**

**Cause:** The parent directory mentioned in archive file path does not exist.

**Action:** Provide valid parent directory in archive file path to create ArchiveMetadataStore.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00596: Failure to read document {0} because it is not found in "{1}"**

**Cause:** The document to be read was not found.

**Action:** Verify that the document exists in the ArchiveMetadataStore before reading the document.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00597: Failure to open the archive file {0}. Cannot create ArchiveMetadataStore for the archive file {0}.**

**Cause:** Could not open the given archive file.

**Action:** Try creating ArchiveMetadata store with a valid archive file.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00598: Cannot create an intermediary archive during export to the archive file {0}.**

**Cause:** Either the intermediary archive file could not be created in the default temporary-file directory or an I/O error occurred.

**Action:** Look at the cause exception for more details and take action accordingly.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00599: Cannot obtain a connection to the Archive Metadata Store for archive file {0}.**

**Cause:** There was a problem obtaining a connection to the Archive Metadata Store.

**Action:** Retry the operation. Also, refer to the error messages that describe the cause exception in the application logs for more information on the actual reason for failure.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00601: The XLIFF document has invalid target language {0}.**

**Cause:** The target language specified was either null or empty.

**Action:** Specify a valid target language and retry the operation.

**Level:** 1

**Type:** ERROR

---

**Impact:** Data

**MDS-00703: The name {0} is not a valid name under package {1} because {2} resource not considered child of the package.**

**Cause:** A specified child resource was not a child of the package.

**Action:** Specify a valid child resource name, and then retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00704: invalid value {0} for property {1} on component {2}**

**Cause:** An invalid property value was provided.

**Action:** Provide a valid property value and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00771: A component with {0} "{1}" already exists.**

**Cause:** The specified component already existed.

**Action:** Retry the operation. Also, refer to the error messages that describe the cause exception in the application logs for more information on the actual reason for failure.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00907: unable to save document "{0}" because either a document or package of the same name already exists**

**Cause:** A document or package with the same name already existed in the repository, perhaps because it was just created by another user.

**Action:** Retry the operation. If necessary, choose another name for the object being saved.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00908: unable to create package "{0}" because a document or package of the same name already exists**

**Cause:** A document or package with the same name already existed in the repository, perhaps because it was just created by another user.

**Action:** Retry the operation. If necessary choose another name for the object being saved.

**Level:** 1

**Type:** ERROR

**Impact:** Data



---

**MDS-00910: unable to save the document because the database sequence "MDS\_DOCUMENT\_ID\_NN\_S" is corrupt**

**Cause:** The database sequence used for generating the unique document ID was corrupt.

**Action:** Retry the operation after deploying metadata to another MDS database repository partition.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00911: Document with name "{0}" and version {1} does not exist in the repository.**

**Cause:** The document was not found in the MDS repository.

**Action:** Specify a correct name for the document and retry the operation. Check if the document is deleted by another user.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00912: MDS repository is incompatible with the middle tier. Repository version "{0}" is older than minimum repository version "{1}" required.**

**Cause:** The MDS repository was older than minimum version required by the middle tier.

**Action:** Upgrade the MDS repository to the required version.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**MDS-00913: MDS repository is incompatible with the middle tier. MDS version "{0}" is older than minimum MDS version "{1}".**

**Cause:** The MDS version was older than the minimum required version for using the MDS repository.

**Action:** Upgrade the MDS library to the required version.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**MDS-00915: MDS repository is incompatible with the middle tier for dumping or restoring metadata.**

**Cause:** The MDS repository was older than minimum version required by the middle tier to dump or restore metadata.

**Action:** Retry the operation after upgrading the MDS repository to newer version or use compatible middle tier to perform the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

---

**MDS-00916: MetadataStore configured for {0} does not support deployment management.**

**Cause:** The metadata store configured for the resource did not support deployment management.

**Action:** Deployment management is supported in MDS repository version 11.1.1.4.0 (11gR1 PS3 patchset) onwards. Upgrade the repository to this version or later.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00918: Connection details for the MDS repository are incomplete. The values for "{0}" are invalid**

**Cause:** The MDS repository connection details were invalid or missing.

**Action:** Specify correct values for the MDS repository details in the configuration and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00919: Internal error: The database context for this repository appears to be corrupt.**

**Cause:** The database context was invalid.

**Action:** Verify that the repository details are correct in the configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00922: The ConnectionManager "{0}" cannot be instantiated.**

**Cause:** There was an error instantiating the ConnnectionManager class

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**MDS-00923: Unable to create sandbox "{0}"**

**Cause:** An error occurred during creation of sandbox.

**Action:** Look in the error message log for the exact reason for the failure.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00928: Invalid document reference, package "cust" should appear before package "trans" in the names of customization translation documents.**

---

**Cause:** An internal MDS document (one in package mdssys) was found with an invalid name, or an attempt was made to create a name object with such an invalid name.

**Action:** Avoid using package or document names containing path element "mdssys" which is reserved for internal MDS use. If necessary, remove such invalid documents from the metadata store.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-00929: unable to look up name "{0}" in JNDI context**

**Cause:** The implementation class to use for initial context was not found.

**Action:** Verify that environment properties are configured using system properties or application resources files.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00930: The JNDI location details for the registered datasource are incomplete.**

**Cause:** JNDI location details were found to be incomplete.

**Action:** Provide complete JNDI location information in the configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00931: The database version is {0}.{1}, but MDS requires at least {2}.{3}.**

**Cause:** The database version is older than the minimum database version required for hosting MDS repository.

**Action:** Upgrade the database to the minimum required version. Contact the database administrator for assistance.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**MDS-00932: unknown database vendor {0}**

**Cause:** The database vendor could not be identified.

**Action:** Verify that the MDS repository is hosted on supported database vendors.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**MDS-00933: cannot create data source using URL "{0}"**

**Cause:** An error occurred while creating the data source using the specified URL.

**Action:** Verify that the URL specified is correct and retry the operation.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**MDS-00934: XDB is not supported on database platform {0}.**

**Cause:** An attempt was made to store XML metadata in a non-XDB database.

**Action:** Verify that the correct MDS repository is being used.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-00935: Unable to complete operation even after maximum connection retries ({0}).**

**Cause:** An error occurred while performing operation.

**Action:** Ensure that the database is running. Retry the operation later.

**Level:** 1

**Type:** ERROR

**Impact:** High Availability

**MDS-00936: Fast Connection Failover is not supported on the underlying database connection ({0}).**

**Cause:** The underlying database connection did not support fast connection failover, and retry-connection was set to true in either the config file, or programmatically.

**Action:** Either stop and then restart the database connection and configure it to allow fast connection failover, or do not attempt to set retry-connection to true.

**Level:** 1

**Type:** ERROR

**Impact:** High Availability

**MDS-00937: A local transaction operation like commit or rollback cannot be used in a global transaction on connection "{0}".**

**Cause:** The database connection was configured for global transactions, but MDS was not configured to support global transactions.

**Action:** Reconfigure the database connection to use local transactions. Change "tx-level" attribute on the MDS datasource to "local".

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-00938: Unable to get an ADF library class loader**

**Cause:** MDS expects to retrieve a resource from an ADF library, but is unable to obtain an ADF library classloader.

**Action:** Consider whether the resource should be repackaged in an ADF library rather than an ordinary jar.

**Level:** 1

**Type:** ERROR

---

**Impact:** Data

**MDS-01059: document with the name {0} missing in the source metadata store**

**Cause:** The document to be transferred did not exist in the source metadata store.

**Action:** Verify that the document name is correct, and that it exists in the source metadata store.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01061: Listener {0} cannot be instantiated.**

**Cause:** The listener class did not exist.

**Action:** Verify that the name of the listener class is correct. Ensure that the class is available on the class path.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01104: finding no documents for processing that match the pattern provided**

**Cause:** No documents were found on the source metadata store that matched the pattern provided, or that matched the document name.

**Action:** Provide another pattern or document name, or provide another metadata store in which to look for the documents.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01105: invalid label {0}**

**Cause:** The label specified for the source metadata store did not exist.

**Action:** Verify that the label name is correct, or provide a label that exists in the source metadata store.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01106: The TransferTypeRestriction {0} can not be associated with given TransferType {1}.**

**Cause:** The given TransferTypeRestriction can not be associated with the specified TransferType.

**Action:** Ensure that given TransferTypeRestriction is valid for the specified TransferType.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01107: Post transfer label cannot be created in target store.**

---

**Cause:** Post transfer label cannot be created in the target store. Examine the cause exception messages to find the root cause of it.

**Action:** Examine any accompanying messages to decide if further action is required.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01108: TransferType cannot be null for ExtendedTransferType.**

**Cause:** TransferType provided to create ExtendedTransferType was null.

**Action:** Provide valid TransferType to create ExtendedTransferType.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01109: The target archive configured in ArchiveMetadataStore already exists. Cannot export the documents into an existing archive file.**

**Cause:** The target archive already exists. Exporting the documents into an existing archive is not allowed.

**Action:** Export the documents into a non existing archive file.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01110: Sandbox export operation allowed only from a database metadata store to an archive metadata store.**

**Cause:** Either source metadata store is not a database or the target metadata store is not an archive in sandbox export operation.

**Action:** Configure source metadata store to be a database and target metadata store to be an archive in sandbox export operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01111: Sandbox import operation allowed only from Archive Metadata Store to a Database Metadata store.**

**Cause:** Either source metadata store is not an archive metadata store or the target metadata store is not a database in sandbox import operation.

**Action:** Configure source metadata store to be an archive metadata store and target metadata store to be a database in sandbox import operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01113: Sandbox metadata file required for import to a new sandbox operation.**

---

**Cause:** Sandbox metadata file missing in source Archive metadata store in import to a new sandbox operation.

**Action:** Import to a new sandbox only from an archive store whose contents were exported from a sandbox and contain sandbox metadata document.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01114: Sandbox with same name as the one imported in a sandbox import operation exists on the target metadata store.**

**Cause:** Sandbox with same name already exists on the target metadata store and the flag to force creation of sandbox is not set to true.

**Action:** Pass true for forceSBCreation to TransferParams.createForSandboxImport() or destroy sandbox already existing with same name on the target metadata store in sandbox import operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01115: Source sandbox in a sandbox export operation does not contain metadata.**

**Cause:** Source sandbox in export operation was not created with metadata.

**Action:** Export from a Sandbox that was created with metadata.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01116: Existing target sandbox in import operation does not contain metadata.**

**Cause:** Target sandbox in an import into an existing sandbox operation was not created with metadata.

**Action:** Import into an existing sandbox that was created with metadata.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01117: Sandbox archive imported into an existing sandbox.**

**Cause:** The archive imported into an existing sandbox contains sandbox metadata.

**Action:** Import only regular archives(that do not contain sandbox metadata) into an existing sandbox.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01118: Sandbox export operation not supported because the source MDS database repository is of older version that does not support this feature.**

---

**Cause:** Sandbox metadata is needed to transfer documents from sandbox. Source store being used does not support storing metadata for sandbox.

**Action:** Sandbox metadata is supported in MDS repository version 11.1.1.4.0 (11gR1 PS3 patchset) onwards. Upgrade the repository to this version or later.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01119: Sandbox import operation not supported because the target MDS database repository is of older version that does not support this feature.**

**Cause:** Sandbox metadata is needed to transfer documents from sandbox. But target store being used does not support storing metadata for sandbox.

**Action:** Sandbox metadata is supported in MDS repository version 11.1.1.4.0 (11gR1 PS3 patchset) onwards. Upgrade the repository to this version or later.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01120: Sandbox transfer unit list creation not supported because the source MDS database repository is of older version that does not support this feature.**

**Cause:** Sandbox metadata is needed to transfer documents from sandbox. Source store being used does not support storing metadata for sandbox.

**Action:** Sandbox metadata is supported in MDS repository version 11.1.1.4.0 (11gR1 PS3 patchset) onwards. Upgrade the repository to this version or later.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01121: Document "mds-transfer-config.xml" cannot be read by MDSTransfer.**

**Cause:** The /meta-inf/mds-transfer-config.xml document cannot be read from source store. Refer to cause exception for more information on the actual reason for failure.

**Action:** Look for messages that describe the cause exception, and then take the appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01122: Metadata Object Name "{0}" specified in the mds-transfer-config.xml to preserve user updated documents in target repository is not a valid metadata object name.**

**Cause:** Metadata object name specified in /meta-inf/mds-transfer-config.xml to preserve user updated documents in target repository is not a valid metadata object name.

**Action:** Make sure the document name specified in mds-transfer-config.xml is a valid metadata object name but not a special document name.

**Level:** 1



---

**Type:** ERROR

**Impact:** Data

**MDS-01123: The metadata path "{0}" specified in the mds-transfer-config.xml to preserve user updated documents in target repository is not a valid metadata path.**

**Cause:** The metadata path specified in /meta-inf/mds-transfer-config.xml to preserve the user updated documents in target repository is not a valid metadata path.

**Action:** Make sure the metadata path specified in mds-transfer-config.xml is a valid metadata path.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01150: Reference is null or empty.**

**Cause:** A reference value was null or empty.

**Action:** Use a valid reference value that is not empty or null.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01151: Id/LocationPath reference is null or missing.**

**Cause:** An Id/LocationPath reference value was null or empty.

**Action:** Use a valid Id/LocationPath reference value that is not empty or null.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01153: invalid LocationPath expression "{0}"**

**Cause:** The LocationPath expression was invalid.

**Action:** Use a valid LocationPath format. The LocationPath expression should follow the format "/text()" or "/text()[x]", where 'x' is the index of "text block".

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01154: invalid LocationPath expression "{0}"**

**Cause:** The node index in the LocationPath expression was invalid.

**Action:** Change the node index in the LocationPath expression to a number greater than or equal to 1.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01158: Expecting a base document. Reference "{0}" is a special document.**

---

**Cause:** A base document was expected, but the reference was a special document.

**Action:** Use a valid base document.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01159: Expecting absolute document reference. Reference "{0}" has local element reference portion.**

**Cause:** The supplied reference was not the expected type.

**Action:** Ensure the reference is of the expected type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01160: Expecting absolute document reference. Reference "{0}" is a relative reference to the document.**

**Cause:** The supplied reference was not the expected type.

**Action:** Ensure the reference is of the expected type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01161: Reference "{0}" has an invalid character "{1}".**

**Cause:** The supplied reference did not follow the MDS naming standard.

**Action:** Use valid characters for the reference.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01162: Reference "{0}" has an invalid XML attribute character.**

**Cause:** The supplied reference did not follow the MDS naming standard.

**Action:** Use valid characters for the reference.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01163: invalid reference "{0}"**

**Cause:** The supplied reference did not follow the MDS naming standard.

**Action:** Ensure that the reference follows the MDS naming standard.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01165: invalid reference "{0}" for a customization document**

---

**Cause:** The supplied reference did not have the expected document extension (.xml).

**Action:** Use the correct extension, .xml, for the customization document.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01166: invalid reference "{0}" for a metadata extension document**

**Cause:** The supplied reference did not have the expected document extension (.rdf).

**Action:** Use the correct extension, .rdf, for the metadata extension document.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01167: There is no namespace declaration for the prefix "{1}" used in LocationPath expression "{0}".**

**Cause:** The LocationPath expression was incomplete.

**Action:** Use a valid LocationPath format.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01168: Partition name "{0}" starts or ends with character "{1}". Partition name cannot contain leading or trailing spaces, ".", "-"**

**Cause:** The supplied partition name contained leading or trailing spaces, ".", "-".

**Action:** Ensure that the partition name follows the MDS naming standard for partitions.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01169: Partition name "{0}" has an invalid character "{1}".**

**Cause:** The supplied partition name did not follow the MDS naming standard.

**Action:** Use valid characters for the partition name.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01170: Partition name is null or empty.**

**Cause:** Partition name value was null or empty.

**Action:** Use a valid partition name that is not empty or null.

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**MDS-01171: The ID prefix generated by concatenating the layer name "{0}" and layer value "{1}" is not a valid MDS ID.**

**Cause:** The ID prefix generated by concatenating the layer name with layer value did not follow the MDS ID naming standard.

**Action:** Ensure that the ID prefix generated by concatenating the layer name with layer value follows the MDS ID naming standard.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01200: This operation is not supported.**

**Cause:** An MDS query operation was attempted, but this particular operation is not supported.

**Action:** Note the stack backtrace and context of the operation, and contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**MDS-01201: An invalid parameter cannot be used when constructing a query condition.**

**Cause:** An invalid parameter was passed to the class ConditionFactory.

**Action:** Note the stack backtrace and context of the operation, and contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**MDS-01205: A SQL error is occurring when performing the query: "{0}" with binds {1}.**

**Cause:** An MDS query on a database store led to a SQL error.

**Action:** Note the stack backtrace and context of the operation, including the reported SQL query and error, and contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**MDS-01206: The array size for the query must be greater than zero.**

**Cause:** An MDS query specified a fetch unit size that was not positive.

**Action:** Note the stack backtrace and context of the operation and contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

---

**MDS-01207: The namespace mapping for the prefix "{0}" specified in the location path, is missing.**

**Cause:** During XPath evaluation, the namespace prefix was used, but the prefix was not mapped to a namespace.

**Action:** Note the stack backtrace and context of the operation and contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**MDS-01250: The file path "{0}" does not exist.**

**Cause:** An invalid path was provided.

**Action:** Retry the operation with a valid file path.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**MDS-01251: The parameter file {0} has no namespace on the document element.**

**Cause:** A namespace was missing from the parameter file provided.

**Action:** Provide a parameter file with valid namespace information.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01252: The parameter file {0} must have either {1} or {2} definition.**

**Cause:** No source stores or target stores information were provided in the parameter file.

**Action:** Check the parameter file to have source and target store information and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01253: The parameter file {0} must not have both {1} and {2} definitions.**

**Cause:** An attempt was made to transfer from source directory to target directory. Both source and target as directories is not supported.

**Action:** Provide correct source and target definition. Either source or target should be a metadata store.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01254: The parameter file {0} contains same store definition for sourceStore and targetStore.**

**Cause:** An attempt was made to transfer from and to the same store. The definition for sourceStore cannot be the same as the definition for targetStore.

---

**Action:** Provide correct source and target information. Change either source or target store definition.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01255: The property {0} has not been supplied.**

**Cause:** The required property was missing from the parameter file.

**Action:** Check the parameter file and supply the required property. Refer to the MDS documentation for the correct syntax. A sample parameter file is also part of documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01258: The value {0} for property {1} is invalid.**

**Cause:** An invalid property value was provided in the parameter file.

**Action:** Provide a valid property value. Refer to the MDS documentation for the correct syntax. A sample parameter file is also part of documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01259: The metadata store "{0}" cannot be instantiated.**

**Cause:** An error occurred during the instantiation of the class for the metadata store.

**Action:** Verify that correct values are provided in the parameter file. Refer to the error messages in application logs that describe the cause exception for more information on the actual reason for failure.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01260: failure to process command-line arguments**

**Cause:** Invalid command-line parameters were provided.

**Action:** Provide valid command-line parameters, and retry the operation. Refer to the MDS documentation for syntax of the tool parameters, or run the tool without parameters in order to get the Help message.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01262: failure of transfer operation on a read-only target metadata store**

**Cause:** The target metadata store used for transfer was read-only, for example a classpath store.

**Action:** Provide a writable target metadata store.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01263: operation failure on the resource {0} because source metadata store is read-only**

**Cause:** An attempt was made to delete, create, update or get a mutable metadata object from a read-only source metadata store.

**Action:** Provide a writable source metadata store.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01264: The given element must contain either "customization" or "translation" configuration.**

**Cause:** A customization or a translation configuration was missing for an element.

**Action:** Examine the transfer parameter file for valid MDS configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01265: Invalid parameter file {0}. Reason: <{1}:{2}> {3}**

**Cause:** Parameter file provided was not valid.

**Action:** Provide a valid parameter file. Refer to the MDS documentation for the correct syntax. A sample parameter file is also part of documentation. Refer to sample parameter for correct syntax.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**MDS-01266: The associated customization document is missing for a given customization class {0} for the given document name {1}.**

**Cause:** The associated customization document for the given customization class did not exist.

**Action:** If the associated customization document was to be transferred, verify that it exists. Otherwise, no action is required.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01268: The associated extended metadata document for the given document name {0} is missing.**

**Cause:** No associated extended metadata document for the given document name existed.

**Action:** If the document was to be transferred, verify that the document exists. Otherwise, no action is required.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01270: Opening and closing parentheses do not match.**

**Cause:** Either an opening or closing parentheses was missing.

**Action:** Check and correct the namespace mappings provided. Each opening parentheses should have an equivalent closing parentheses and vice versa.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01271: Cannot get the dependency registry**

**Cause:** An error occurred while getting the dependency registry.

**Action:** Retry the operation. If the problem persists, look for messages that describe the cause exception for more information on the actual reason for failure.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01272: unable to read mds-webapp-config.xml file**

**Cause:** The mds-webapp-config.xml file was invalid.

**Action:** Confirm that the mds-webapp-config.xml file for the application is well formed, and valid.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**MDS-01273: The operation on the resource {0} failed because source metadata store mapped to the namespace {1} is read only.**

**Cause:** An attempt was made to delete, create, update or get a mutable metadata object from a readonly source metadata store.

**Action:** Provide a writable source metadata store.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01301: Element "{1}", namespace "{0}" is not a valid child under parent "{3}", namespace "{2}".**

**Cause:** An attempt was made to add, insert or replace a child element of the wrong type.

**Action:** Check the schema definition and ensure that the child element is the correct type.

**Level:** 1

**Type:** ERROR



---

**Impact:** Programmatic

**MDS-01302: failure to load schema file "{0}"**

**Cause:** An exception occurred in the XMLEF layer during processing of the schema definitions.

**Action:** Look for messages that describe the cause exception, and then take the appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01303: failure to register grammar from schema file "{0}"**

**Cause:** An exception occurred in the XMLEF layer during addition of schema definitions.

**Action:** Look for messages that describe the cause exception, and then take the appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01305: failure to locate schema file "{0}".**

**Cause:** The schema definition file was not found.

**Action:** Verify that the schema file name is correct, and that it is in the correct location.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01306: Grammar from a Web application can be added only once.**

**Cause:** There were multiple method calls to add grammar from a web application.

**Action:** Verify that a grammar definition has already been added for the given MDSInstance and ServletContext. If it has then remove the calls to add it multiple times.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01307: no schema files for processing**

**Cause:** No schema files were found against which beans can be generated.

**Action:** Pass an existing schema file to the bean generator.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01308: Event "{0}" is not supported.**

---

**Cause:** An attempt was made to use event types that are not supported for the selected content model.

**Action:** Use only the event types that are allowed for the selected content model.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01309: ContentModelPipeline is empty.**

**Cause:** The contentModelPipeline contained an empty or null builder list.

**Action:** A list of one or more valid builders must be available in the ContentModelPipeline.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01310: Invalid ContentModelPipeline. Missing {0}.**

**Cause:** The expected builder was not available in builder list of the ContentModelPipeline.

**Action:** Valid builders must be supplied to the ContentModelPipeline.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01311: The DOM tree does not support the DOM event model.**

**Cause:** This DOM Document did not implement EventTarget interface.

**Action:** Verify whether the Oracle XML Developer's Kit is used.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01312: Change-list transaction state is invalid.**

**Cause:** The current change-list transaction state is invalid for the customization operation performed.

**Action:** Ensure Change-list to be in valid transaction state to perform the necessary customization operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01313: The argument for document cannot be null.**

**Cause:** The argument for DocumentName was null.

**Action:** Provide a valid DocumentName.

**Level:** 1

**Type:** ERROR

---

**Impact:** Data

**MDS-01314: TypeAnnotationProvider cannot be null.**

**Cause:** The argument for TypeAnnotationProvider was null.

**Action:** Provide a valid TypeAnnotationProvider.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01316: Support for XPath is not implemented yet.**

**Cause:** Support for XPath has not been implemented yet.

**Action:** Provide a valid Configurable ID.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01319: JAXP support is not available. Falling back to using Oracle XML Developer's Kit for parsing the document {0}.**

**Cause:** JAXP support was not available.

**Action:** None.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01320: Modifying the prefix declaration for {0} from "{1}" to "{2}" in document {3} through customizations is not supported.**

**Cause:** An attempt was made to change an existing prefix declaration.

**Action:** Avoid attempts to change existing prefix declarations.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01321: Node type should be one of ImmutableModelNode.ELEMENT or ImmutableModelNode.TEXT or ImmutableModelNode.CDATA.**

**Cause:** The node was not of the type ImmutableModelNode.ELEMENT or ImmutableModelNode.TEXT or ImmutableModelNode.CDATA.

**Action:** Ensure the node type is one of the following types: ImmutableModelNode.ELEMENT or ImmutableModelNode.TEXT or ImmutableModelNode.CDATA.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01322: Value "{0}" does not satisfy "{1}" type.**

**Cause:** The data type conversion failed.

---

**Action:** Verify that the expected XSD built-in simple data type and the passed-in string value are convertible.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01323: Value "{0}" has an incorrect number of characters for a base64Binary.**

**Cause:** The value did not represent a valid Base64Binary.

**Action:** Verify that the input value is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01324: Unknown XML schema built-in type "{0}"**

**Cause:** An attempt was made to use an unknown XML schema built-in type.

**Action:** Use only valid XML schema built-in types.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01325: unable to load type definition "{0}"**

**Cause:** Could not load this type definition because the specified location did not exist.

**Action:** Ensure that the specified location for the type definition exists.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01326: Loading of type definition from element "{0}" is not supported.**

**Cause:** An attempt was made to load a type definition from the specified element that is not supported in the MDS configuration.

**Action:** Examine the schema definition to ensure that the entry specified in type definition is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01327: unable to load data from "{0}" into {1}**

**Cause:** An error occurred while loading the content of this configuration element.

**Action:** Examine the schema definition to ensure that the content of this configuration element is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**MDS-01328: unable to load element "{0}" into {1}**

**Cause:** An error occurred while loading this configuration element.

**Action:** Examine the schema definition to ensure this configuration element is correctly specified in the MDS configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01329: unable to load element "{0}"**

**Cause:** An error occurred while loading this configuration element.

**Action:** Examine the schema definition to ensure this configuration element is correctly specified in the MDS configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01330: unable to load MDS configuration document**

**Cause:** An I/O or parsing error occurred while loading the MDS configuration document.

**Action:** Verify that the URL is correct, and ensure that the document contains valid MDS configuration information.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**MDS-01331: unable to load MDS configuration document "{0}"**

**Cause:** An error occurred in loading the content of MDS configuration document.

**Action:** Verify that the URL is correct, and ensure that the document contains valid MDS configuration information.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**MDS-01332: Class {0} is not a subclass or implementation of {1}.**

**Cause:** The class specified in the configuration information did not extend the required class, or implement the required interface.

**Action:** Ensure that the class specified in the configuration information extends the correct class, or implements the correct interface.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01333: missing element "{0}"**

**Cause:** This element was missing from the MDS configuration information.

**Action:** Ensure that the element is specified in the configuration information.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01334: missing element "{0}" in document "{1}"**

**Cause:** This element was missing from the MDS configuration information.

**Action:** Ensure that this element is specified in the configuration document.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01335: namespace "{0}" mapped to metadata-store-usage "{1}" but its definition was not found in MDS configuration.**

**Cause:** Metadata-store-usage element that was referenced by a namespace not found in MDS configuration.

**Action:** Ensure that this element is specified in MDS configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01336: No XML element is provided to create {0}.**

**Cause:** A null XML element was passed to the constructor of this configuration object.

**Action:** Ensure that a valid XML element is provided to create a new instance of this configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01337: No URL is provided to create {0}.**

**Cause:** A null URL was passed to the constructor of this configuration object.

**Action:** Ensure that a valid URL is provided to create a new instance of this configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01340: More than one metadata store can be resolved for the namespace "{0}".**

**Cause:** There were multiple namespace to metadata store mappings in the persistence configuration that satisfied the request for the metadata store of a given namespace.

**Action:** Correct the namespace mapping in persistence configuration to ensure that the namespace is mapped to only one metadata store.

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**MDS-01341: Namespace mapping for "{0}" is overridden by namespace mapping for "{1}"; the first mapping is not used.**

**Cause:** A conflicting mapping to this namespace has already been defined in the persistence configuration.

**Action:** Correct the namespace mapping in the persistence configuration to ensure that there is no conflicting mapping to this namespace.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01342: No metadata store is mapped to the namespace "{0}".**

**Cause:** No namespace mapping could be found in the persistence configuration for the specified namespace.

**Action:** Ensure that a correct namespace is passed into the method concerned, or alter the application configuration to define the specified namespace.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01343: There is a duplicate file extension mapping for "{0}".**

**Cause:** A mapping to this file extension has already been defined in the file type configuration.

**Action:** Remove the duplicate file extension mapping from the file type configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01344: cannot create {0} due to null parameter**

**Cause:** A null parameter was passed to the constructor of this configuration object.

**Action:** Ensure that a valid parameter is provided to create a new instance of this configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01346: The given namespace path "{0}" is not a valid path.**

**Cause:** An invalid path was provided to create a namespace.

**Action:** Ensure that a valid path is provided to create a namespace.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**MDS-01347: Base restriction is supported only for classpath store or servlet context store: namespace "{0}" mapped to "{1}".**

**Cause:** The base restriction was specified for a metadata store other than the classpath metadata store and servlet context store.

**Action:** Correct the namespace mapping in the configuration to ensure that the base restriction is specified only for the classpath store or servlet context store.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01348: unable to save configuration document to "{0}"**

**Cause:** An I/O error occurred while writing the configuration to a file.

**Action:** Check the file system and ensure that the file location is writable.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**MDS-01349: unable to read existing configuration document "{0}" to be updated**

**Cause:** An I/O or parsing error occurred while reading the configuration file.

**Action:** Ensure that the configuration file does exist and has valid contents.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**MDS-01350: Adding namespace "{0}" mapped to "{1}" conflicts with existing namespace "{2}" mapped to "{3}".**

**Cause:** An attempt was made to add a new namespace that conflicted with an existing namespace because it mapped to a different repository.

**Action:** Ensure that the new namespace does not map to a different repository if the new namespace is a super-namespace or sub-namespace of existing namespaces.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01351: Adding namespace "{0}" with "{1}" restriction conflicts with existing namespace "{2}" with "{3}" restriction.**

**Cause:** An attempt was made to add a new namespace that conflicted with an existing namespace in the namespace restriction.

**Action:** Ensure that the new namespace does not conflict with existing namespaces in the namespace restriction if the new namespace is a super-namespace or sub-namespace of existing namespaces.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration



---

**MDS-01352: Customization configuration with granular mapping "{0}" is unsupported; only the slash, "/", is allowed.**

**Cause:** An attempt was made to add an invalid namespace mapping of the customization configuration. Only one namespace to customization class list mapping is currently allowed, and that namespace has to be a slash (/).

**Action:** Ensure that only the slash (/) is specified in the namespace mapping of the customization configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01353: unable to retrieve customization layer values from "{0}"**

**Cause:** An I/O or parsing error occurred while reading the specified file to retrieve customization layer values.

**Action:** Ensure that the file does exist and has valid contents.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**MDS-01355: Both TypeConfig parameters contain Grammar Providers. Only one Grammar Provider is allowed.**

**Cause:** A Grammar Provider was specified in multiple type configuration sources.

**Action:** Ensure that only one Grammar Provider is specified in the type Configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01356: Both TypeConfig parameters contain Metadata Providers. Only one Metadata Provider is allowed.**

**Cause:** A Metadata Provider was specified in multiple type configuration sources.

**Action:** Ensure that only one Metadata Provider is specified in the type Configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01357: MDS configuration is not compatible with JAXB 1.0.**

**Cause:** JAXB 1.0 jar file (xml.jar) was found on the classpath before any JAXB 2.0 jar files.

**Action:** Ensure that JAXB 2.0 jar files appear on the classpath before JAXB 1.0 jar file (xml.jar).

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**MDS-01358: Invalid MDS configuration. Configuring multiple metadata stores as the default repository for customizations.**

**Cause:** Multiple metadata stores were configured as the default repository for customizations in the MDS configuration.

**Action:** Ensure that only a single metadata store is configured as the default repository for customizations.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01359: The namespace used ([http://xmlns.oracle.com/mds/config\\_10\\_1\\_3\\_001](http://xmlns.oracle.com/mds/config_10_1_3_001)) in the configuration document is deprecated. Update the configuration document to use "<http://xmlns.oracle.com/mds/config>" as the namespace.**

**Cause:** The namespace used ([http://xmlns.oracle.com/mds/config\\_10\\_1\\_3\\_001](http://xmlns.oracle.com/mds/config_10_1_3_001)) in the configuration document is deprecated.

**Action:** Update the configuration document to use "<http://xmlns.oracle.com/mds/config>" as the namespace.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**MDS-01360: Invalid MDS configuration. The attribute file-type-extension on the file-type element is missing for file type configuration.**

**Cause:** The attribute file-type-extension was not specified on the file-type element for file type configuration.

**Action:** Ensure that a valid file-type-extension attribute is specified for every file-type element.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01361: cannot add XSD grammar**

**Cause:** An attempt was made to add XSD grammar made by passing in a SchemaGrammarProvider.

**Action:** Ensure that the grammar provider is obtained using `oracle.jdeveloper.webapp.runtime.WebAppDesignContext`.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01362: Failed to auto-purge MDS repository: "{0}".**

**Cause:** MetadataStore was scheduled for auto-purge after the MDSInstance was released

**Action:** Try later and contact support if persists.

**Level:** 1

**Type:** WARNING

---

**Impact:** Other

**MDS-01363: Failed to locate datasource with JNDI name "{0}" configured for the DBMetadataStore, defaulting to use ClassPathMetadataStore.**

**Cause:** Application was configured with DBMetadataStore using JNDI datasource and JNDI lookup failed when running outside application server.

**Action:** No action required if defaulting to ClasspathMetadataStore is acceptable. Otherwise, use appropriate configuration such as FileMetadataStore.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**MDS-01365: Multiple metadata stores found with deploy-target attribute set to true, only one allowed per configuration.**

**Cause:** Multiple metadata stores were configured as the deployment target.

**Action:** Ensure that only a single metadata store is configured for deployment.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01366: Cannot find a metadata store with deploy-target attribute set to true**

**Cause:** A single metadata store must be configured as a deploy target. None was found.

**Action:** Ensure that a single metadata store is configured for deployment.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01367: Failed to create {0}. Invalid MDS configuration specified in: "{1}"**

**Cause:** Declarative MDS configuration is invalid.

**Action:** Specify correct mds configuration information and try creating the configuration again.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01368: Variable "{0}" used in configuration document is not defined either as system property or as environment variable.**

**Cause:** This variable was not defined.

**Action:** Ensure that this variable is defined before loading the configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01369: Variable declaration in "{0}" in configuration document is incorrect.**

**Cause:** Variable did not either start with "\${" or it did not end with "}".

---

**Action:** Ensure that the configuration variable is correctly declared in the form \${var}.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01370: MetadataStore configuration for metadata-store-usage "{0}" is invalid.**

**Cause:** MetadataStore class or some of its properties were not valid.

**Action:** Ensure that the MetadataStore class exists and all required properties are valid. See message of the cause exception for more information on the actual reason for failure.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01371: ADF security is not configured in "{0}", password can not be securely processed.**

**Cause:** ADF security configuration was not found in the config file.

**Action:** Set the password using JDeveloper to ensure required configuration is generated.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01373: unable to retrieve password.**

**Cause:** unable to retrieve the password due to exception in security layer.

**Action:** See message of the cause exception for more information on the actual reason for failure.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01374: unable to save password.**

**Cause:** unable to save the password due to exception in security layer.

**Action:** See message of the cause exception for more information on the actual reason for failure.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01375: No password defined for DBMetadataStore in configuration file or in the wallet file.**

**Cause:** DBMetadataStore uses JDBC based configuration but no password specified.

**Action:** Set the password for the DBMetadataStore using JDeveloper.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01376: Unable to get database connection from data source "{1}" configured with JNDI name "{0}".**

**Cause:** Failed to retrieve a database connection from the data source either because the data source is not configured correctly or the database details are not correct.

**Action:** Test the data source to check if it is correctly configured and if the database can be accessed. See message of the cause exception for more information on the actual reason for failure.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01377: Unable to get database connection from data source configured with JNDI name "{0}".**

**Cause:** Failed to retrieve a database connection from the data source either because the data source is not configured correctly or the database details are not correct.

**Action:** Test the data source to check if it is correctly configured and if the database can be accessed. See message of the cause exception for more information on the actual reason for failure.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01400: Read-only extended metadata resource "{0}" is not writable.**

**Cause:** An attempt was made to update a read-only extended metadata resource.

**Action:** Ensure that the metadata object is mutable before getting the extended metadata.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01401: Updating a node in one document "{1}" using a node from a different document "{0}" is not allowed.**

**Cause:** The node being added or inserted was from a different metadata object. They must be from the same base document.

**Action:** Ensure that the node being inserted is from the correct metadata object.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01402: attempting to update an immutable MElement: "{0}"**

**Cause:** The MElement being updated was immutable.

---

**Action:** Check that the MElement in question really is mutable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01403: Updating a mutable MELEMENT using an immutable MELEMENT: "{0}" is not allowed.**

**Cause:** An attempt was made to update a mutable MELEMENT using an immutable MELEMENT.

**Action:** Verify that the child MELEMENT being used for the update is mutable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01404: Customization to replace root node of {0} is not allowed.**

**Cause:** An attempt was made to replace the root node as part of a customization.

**Action:** Replace the root node in the base document, or modify the existing root node instead.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01450: missing GUID**

**Cause:** The application removed an object's GUID while editing its XML metadata content.

**Action:** Fix the application so it does not tamper with MDS GUIDs.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01451: GUIDs do not match.**

**Cause:** The application altered an object's GUID while editing its XML metadata content.

**Action:** Fix the application so it does not tamper with MDS GUIDs.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01452: GUID is null.**

**Cause:** An attempt was made to retrieve a metadata object or document by GUID, but the given GUID was null.

**Action:** Fix the application so it passes a valid GUID to the method in question.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**MDS-01455: multiple GUIDs on metadata object {0}**

**Cause:** The application set multiple GUID values while editing an object's XML metadata content.

**Action:** Fix the application so it does not tamper with MDS GUIDs.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01456: invalid GUID on metadata object {0}**

**Cause:** The application set an object's GUID to an invalid value while editing its XML metadata content.

**Action:** Fix the application so it does not tamper with MDS GUIDs.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01457: GUID feature not available**

**Cause:** The application attempted to retrieve an object by GUID from a metadata store that does not yet support this.

**Action:** Fix the application so it does not attempt this, or configure the application to use a different type of metadata store.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01458: GUID must not be present.**

**Cause:** The application set an object's GUID value while editing its XML metadata content.

**Action:** Fix the application so it does not tamper with MDS GUIDs.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01460: GUIDs on DOM Document do not match.**

**Cause:** The application set an object's GUID to a different value while editing its XML metadata content.

**Action:** Fix the application so it does not tamper with MDS GUIDs.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01461: unable to create document {0} in the metadata repository; a document with the same name or GUID already exists**

---

**Cause:** An attempt was made to import or create a document with a name or GUID that is already used by an existing document.

**Action:** Delete the document in the MDS repository prior to import or creation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01462: GUID feature is not supported in the classpath store.**

**Cause:** The application attempted to retrieve an object by GUID from the classpath metadata store that does not support this.

**Action:** Fix the application so it does not attempt retrieval by GUID, or configure the application to use a different type of metadata store.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01464: unable to save GUIDRegister {0}**

**Cause:** The GUID register (GUID index files) could not be written.

**Action:** Verify that the application has write permission for the given file, and that the disk is not full.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**MDS-01465: unable to remove node {0} from the GUIDRegister**

**Cause:** The given node was not removed from the GUID register, possibly because it was not found.

**Action:** Delete the GUID register files, restart the application and try the operation again. If that fails, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**MDS-01466: unable to create GUIDRegister directory {0}**

**Cause:** The owning directories for the GUID register (GUID index files) were not created.

**Action:** Verify that you have permission to create the parent directories for the given file name.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**MDS-01468: A different GUID is already registered for document {0}.**

**Cause:** The GUID register has become corrupted.

**Action:** Delete the GUID register files and restart the application (the files will then be re-created).



---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01469: unable to remove old GUIDRegister store path {0}**

**Cause:** Old GUID register files were not deleted.

**Action:** Verify that you have permission to delete these files.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**MDS-01470: more than one GUID is registered for document {0}**

**Cause:** The GUID register has become corrupted.

**Action:** Delete the GUID register files and restart the application (the files will then be re-created).

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01471: more than one document is registered for GUID {0}**

**Cause:** The GUID register has become corrupted.

**Action:** Delete the GUID register files and restart the application (the files will then be re-created).

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01472: GUID is missing in file {0}**

**Cause:** No GUID was found in the given file but the metadata object type definition indicated there should be one.

**Action:** Re-create the metadata object or correct its type definition not to require a GUID.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01500: The MDSObject {0} is an XML document and cannot be loaded using StreamedObject API.**

**Cause:** An attempt was made to load an XML document via StreamedObject API.

**Action:** Retry the operation using MetadataObject API or use a non-XML document.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**MDS-01501: The MDSObject {0} is not an XML document and cannot be loaded from MetadataObject API.**

**Cause:** An attempt was made to load a streamed object (non-XML document) using MetadataObject API.

**Action:** Retry the operation using StreamedObject API or use a document containing valid XML.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01502: The MDSObject "{0}" is an XML document and cannot be saved using StreamedObject API.**

**Cause:** An attempt was made to save an XML document using StreamedObject API.

**Action:** Retry the operation using MetadataObject API.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01503: The content of StreamedObject {0} cannot be read.**

**Cause:** An attempt to read the StreamedObject content failed.

**Action:** Look at the error message and exception stack in the application logs to determine the reason for the failure.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01504: The document {0} is either registered as a streamed file type or is a non-XML file extension and cannot be created using MetadataObject API.**

**Cause:** An attempt was made to create an MDSObject named with a streamed object (non-XML) extension using MetadataObject API.

**Action:** Retry the operation using StreamedObject API.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01600: The Dependency Analyzer requires a DependencyFilter.**

**Cause:** Either no filter was supplied, or the filter supplied was null.

**Action:** Supply a non-null filter.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01601: The relationship role name {0} is a duplicate.**

**Cause:** A role name defined in a relationship had already been used.

---

**Action:** Ensure that the toParentRole and toChildRole in a relationship have not already been used by another relationship.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01602: cannot locate the element type {0} in namespace {1} defined for the relationship**

**Cause:** The element type did not exist in the given namespace.

**Action:** Ensure that the element type exists in the given namespace.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01604: The relationship from {0} to {1} is invalid because the latter is not a valid MDS reference.**

**Cause:** An invalid MDS reference was specified as the parent.

**Action:** Ensure the parent reference is a valid MDS reference.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01605: The relationship from {0} to {1} is invalid because the latter does not exist.**

**Cause:** No parent element was found matching the MDS reference supplied.

**Action:** Ensure that the parent reference in the relationship points to an existing element.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01606: The relationship from {0} to {1} is invalid because the latter is of incorrect type.**

**Cause:** The child element referenced a parent of the wrong type.

**Action:** Ensure that the parent type matches the one stipulated in the relationship definition.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01607: The relationship from {0} to {1} is invalid because type information is not available for the latter.**

**Cause:** No type definition could be found for the parent.

**Action:** Ensure that the parent type information is available.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**MDS-01608: The relationship from {0} to {1} is invalid because the latter maps to a different store.**

**Cause:** The parent and child objects in the relationship have been mapped to different stores.

**Action:** Ensure that the parent maps to the same store as the child object.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01609: The document {0} contains relationships that do not conform to the relationship definition.**

**Cause:** Constraints in this document's relationship definitions were violated.

**Action:** Ensure that the relationships conform to the constraints in the relationship definition.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01610: Some of the changes in the MDS session are not valid.**

**Cause:** A change was made in the MDS session that was not valid.

**Action:** Check the changes made and ensure each of them is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01611: not saving changes in MDS session because some changes are not valid**

**Cause:** A change made in the MDS session was not valid.

**Action:** Check all the changes made and ensure that all changes are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01612: The object {0} cannot be deleted because it is referenced by {1}.**

**Cause:** An attempt was made to delete an element that was being referenced by a child object.

**Action:** Remove the child reference to this object so the object can be deleted.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01613: The MetadataObject {0} cannot be deleted because of relationship integrity constraints.**

**Cause:** An attempt was made to delete an object that was still being referenced.

---

**Action:** Remove the child references to the metadataObject so that it can be deleted.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01614: Rename is not allowed because integrity checking is not turned on in the object {1} in MetadataObject {0}.**

**Cause:** Integrity checking was switched off so it was not possible to check whether the rename would have broken any relationship integrity constraints.

**Action:** Ensure that integrity checking is turned on.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01615: failure to rename {0} because there is no reference attribute in MetadataObject {1}, element {2}**

**Cause:** A child object could not reference the renamed object as its current reference was invalid.

**Action:** Confirm that all the references in the child object are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01620: The untyped dependency with the following registration details cannot be inserted: {0}, {1}, {2}, {3}.**

**Cause:** The dependency could not be registered in the database repository due to a SQL exception.

**Action:** Correct the cause of the SQL exception and retry the untyped dependency registration.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01621: The untyped dependency information for {0} could not be removed.**

**Cause:** An attempt to remove untyped dependency information failed either because the document was invalid or there was a SQL exception.

**Action:** Verify that the document and its dependencies are valid, or correct the cause of any SQL exceptions.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01622: There is no analyzer to unregister.**

**Cause:** No analyzers were supplied to be unregistered.

**Action:** Supply the DependencyAnalyzer to be unregistered.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01630: invalid operation in a customized context on an element that could participate in a relationship: {0}**

**Cause:** Within a customized context there was an attempt to insert an element without first deleting it as part of a composite move.

**Action:** Within the customized context, do not attempt inserts on elements without first deleting them as part of a composite move.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01631: In a customized context, an element that could participate in a relationship as a child cannot be modified. The reference is {0} on {1}.**

**Cause:** Within a customized context, an attribute being customized could have been a parent reference within a relationship.

**Action:** Do not attempt to modify or remove an attribute that could be a parent reference within a relationship.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01633: In a customized context, an element that could participate in a relationship cannot be deleted: {0}.**

**Cause:** Within a customized context an attempt was made to delete an element that could participate in a relationship.

**Action:** Do not attempt to delete an entity while in a customized context.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01634: In {0}, a {1} element that participates in a relationship lacks a configurable ID.**

**Cause:** An operation was attempted on a participant in a relationship that lacked a configurable ID.

**Action:** Add a configurable ID to the element on which it is missing. If necessary, refer to the element's schema definition to identify the configurable ID attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01635: Skipping the relationship validation for {0} in the metadata object {1} because the element contains an invalid MDS reference.**

**Cause:** Validation of the object's relationships was not performed because the element contained an invalid MDS reference.

---

**Action:** Correct the MDS references in the MetadataObject specified.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01700: MElementBeanImpl.\_setSimpleChild cannot be called on a non-simpleType element: name={0}, namespace={1}**

**Cause:** An attempt was made to set a bean element to a simple type, but the definition in the schema was not a simple type. The generated beans may not have matched the registered schema.

**Action:** Regenerate the beans from the schema definitions and ensure that the correct versions are on the classpath. Check that the schemas are registered with the MDS instance.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01701: Cannot set the value on an element that is not based on a simpleType: name={0}, namespace={1}**

**Cause:** An attempt was made to set an element to a simple type, but the definition in the schema was not a simple type.

**Action:** Regenerate the beans from the schema definitions and ensure that the correct versions are on the classpath. Check that the schemas are registered with the MDS instance.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01702: The method getBean() is not valid for metadata object {0} - it is allowed on only bean metadata objects.**

**Cause:** An attempt was made to access the metadata object using the bean API but the metadata object was not a bean metadata object. The schema for the root element may not have been registered with MDS, or the beans were not available on the classpath.

**Action:** Regenerate the beans from the schema definitions and ensure that the correct versions are on the classpath. Check that the schemas are registered with the MDS instance.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01703: error unmarshalling bean element: name={0}, namespace={1} in metadata object {2} - no object factory can be found or jaxb.properties cannot be found**

**Cause:** An element was found in the metadata object that did not have a corresponding bean class. The schema for the element may not have been registered with MDS, or the beans were not available on the classpath.

---

**Action:** Regenerate the beans from the schema definitions and ensure that the correct versions are on the classpath. Check that the schemas are registered with the MDS instance.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01705: error unmarshalling bean element: name={0}, namespace={1} in metadata object {2} - object factory class {3} does not have the expected unmarshal() method**

**Cause:** The bean object factory found for the element did not appear to have been generated by the MDS bean generation tool.

**Action:** Regenerate the beans from the schema definitions and ensure that the correct versions are on the classpath. Check that the schemas are registered with the MDS instance.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01706: error unmarshalling bean element: name={0}, namespace={1} in metadata object {2} - object factory class {3} failure in unmarshal() method**

**Cause:** An unexpected exception occurred while creating a bean object for the element.

**Action:** Contact the developers of the application, providing the cause exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01800: Sandbox is not supported for {0} configured on {1}.**

**Cause:** An underlying metadata store did not support the sandbox feature.

**Action:** Provide a metadata store that supports sandbox feature.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01801: Document name {0} should not refer to the raw sandbox resource name.**

**Cause:** A resource name pointed directly to a resource in the sandbox component.

**Action:** Provide a logical document name to resolve the issue.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01802: A sandbox by name {0} already exists in the {1} store.**

**Cause:** A sandbox with the same name already existed in the store.

**Action:** Use a different name or destroy the existing sandbox before reusing the same name.



---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01803: Sandbox Persistence manager cannot be constructed using an instance of SandboxPManager.**

**Cause:** An attempt was made to construct an instance of sandbox persistence manager using an instance of SandboxPManager.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**MDS-01804: Sandbox {0} configured with {1} namespace, {2} store and {3} label from mainline is not compatible with {4} label created on {5} namespace.**

**Cause:** A label was used that is different from the mainline label associated with the sandbox.

**Action:** Use a label that is compatible with the sandbox and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01805: Sandbox {0} missing in {1}.**

**Cause:** The specified sandbox was not found in the underlying metadata store.

**Action:** Provide the name of an existing sandbox, or create a new sandbox if necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01806: failure to remove {0} from {1}, because it is not a valid document in the sandbox**

**Cause:** The specified document to be removed was not found in the sandbox.

**Action:** Verify that the document exists in the sandbox.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-01807: failure to delete sandbox {0}**

**Cause:** An error occurred while deleting the sandbox.

**Action:** Refer to the error messages that describe the cause exception in the application logs for more information on the actual reason for failure.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**MDS-01808: SandboxUsage with the sandbox name set to {0} does not return any namespaces.**

**Cause:** No namespaces were found on the SandboxUsage.

**Action:** Configure the SandboxUsage with namespaces that are associated with the sandbox.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01809: failure to list sandboxes matching {0}**

**Cause:** An error occurred while listing or querying the sandboxes.

**Action:** Look for error messages to determine the actual cause of the failure.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01810: failure to refresh sandboxes to target label {0}**

**Cause:** Target label is older than the current source label.

**Action:** Specify a target label which is later than current label.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01811: failure to list sandboxes matching customization for {0}, layer: {1}, value: {2}**

**Cause:** An error occurred while listing or querying the sandboxes.

**Action:** Look for error messages to determine the actual cause of the failure.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01812: sandbox name {0} exceeds the maximum limit of {1} characters**

**Cause:** Sandbox name is more than the supported size.

**Action:** Use a shorter sandbox name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01813: sandbox metadata for {0} can not be saved because it is being updated by another user.**

**Cause:** More than one user is updating the sandbox metadata at the same time.

**Action:** Get the sandbox metadata again and retry saving after making the changes.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**MDS-01814: sandbox metadata for {0} cannot be changed because it is read only.**

**Cause:** Sandbox metadata is read only and cannot be updated

**Action:** To update get an instance of sandbox and then get the sandbox metadata from the instance

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01815: store configured for sandbox {0} does not support sandbox metadata.**

**Cause:** Sandbox metadata is not supported on the repository.

**Action:** Sandbox metadata is supported in MDS repository version 11.1.1.4.0 (11gR1 PS3 patchset) onwards. Upgrade the repository to this version or later to use this feature.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01816: {0} is not a valid name for a sandbox.**

**Cause:** The specified sandbox name is either an MDS reserved package part name or contains invalid characters.

**Action:** Ensure that the specified sandbox name is neither an MDS reserved package part name nor does it contain invalid characters as per the MDS Resource name specification.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01817: sandbox {0} is either active or applied to mainline. The undo operation cannot continue.**

**Cause:** The sandbox is either applied or is in the active state.

**Action:** Check that the sandbox is in the intermediary state

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01818: sandbox {0} is in applied\_with\_undo state. No further updates except finalized are allowed.**

**Cause:** The sandbox is in applied\_with\_undo state and no further updates can be done to the sandbox.

**Action:** The only allowed operations in the intermediary state are: finalize and undo.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**MDS-01819: Lock on sandbox {0} cannot be taken. A concurrent management operation may be in progress.**

**Cause:** A management operation on the sandbox is in progress and has locked the sandbox.

**Action:** Retry the operation after a while.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01820: Metadata for sandbox {0} is not available. The sandbox management operation cannot proceed without sandbox metadata.**

**Cause:** Sandbox was created without metadata.

**Action:** Use the management APIs that are available for sandboxes without metadata.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01900: None of the configured metadata stores support versioning.**

**Cause:** The underlying metadata store did not support versioning.

**Action:** Configure a metadata store that supports versioning, and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01901: specifying multiple labels for a namespace not allowed**

**Cause:** Multiple labels were provided for a namespace that pointed to a metadata store.

**Action:** Provide a single label to map to a namespace and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01902: Label or namespace is invalid.**

**Cause:** Either the namespace or the label was invalid.

**Action:** Verify that the namespace and the label are correct, and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01903: Specified label {0} does not exist for {1} namespace.**

---

**Cause:** The specified label did not exist in the metadata store mapped to the namespace.

**Action:** Verify that the label name is correct and that the label exists, and then retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01906: A label with same name {0} already exists.**

**Cause:** An attempt was made to create a label that already existed.

**Action:** Create a label with a different name, and then retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01907: The label {1} is already configured for the store "{0}", so the same store cannot be configured with another label "{2}".**

**Cause:** An attempt was made to map a label for a store when a label-to-store mapping already existed for that store.

**Action:** De-associate the existing label mapped to the store first, and then retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01908: failure to delete versions of the document {0}**

**Cause:** An error had occurred while versions were being deleted.

**Action:** Refer to the error messages that describe the cause exception in the application logs for more information on the actual reason for failure.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01909: No namespaces are specified for creating label {0}.**

**Cause:** No namespace information was found for creating a label.

**Action:** Provide a namespace for creating a label, and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01910: The namespace {0} is already registered with the label {1}, so the super/sub namespace {2} cannot be assigned with the label {3}.**

**Cause:** An attempt was made to associate multiple labels with a namespace, or an attempt was made to associate multiple namespaces with a single label.

**Action:** Associate a single label with a single namespace, and retry the operation.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01911: failure of the metadata purge operation for the requested repository partition**

**Cause:** An error occurred during a purge operation.

**Action:** Retry the operation. Also, refer to the error messages that describe the cause exception in the application logs for more information on the actual reason for failure.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01912: MetadataStore configured for {0} does not support versioning.**

**Cause:** The metadata store configured for the resource did not support versioning.

**Action:** Configure a metadata store that supports versioning or verify that the resource name is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-01913: A deployment lineage with same application name "{0}" and deployment module name "{1}" already exists.**

**Cause:** An attempt was made to create a lineage that already existed.

**Action:** Create a lineage with a different application or MAR name, and then retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-01914: The application name and deployment module name cannot be null to create DeploymentInfo.**

**Cause:** An attempt was made to create DeploymentInfo with null values.

**Action:** Make sure that the values for application name and deployment module name are non-null.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-02024: Setting or modifying the unique identifier of an existing node through customizations is not supported.**

**Cause:** An attempt was made to customize a configurable ID.

**Action:** Remove any customization that is attempting to modify the unique identifier of an XML element.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**MDS-02025: The requested change is incompatible with changes already pending on the MDS session.**

**Cause:** An attempt was made to perform a change operation on the MDS session which would update the same MetadataObject part as another change operation that has been done. For example, if you change a customization of a metadata object then attempt to delete all of its customizations, the latter operation will fail because it conflicts with the former. You must save the former change first before doing the second.

**Action:** Save the changes that have already been made on the session (by calling flushChanges), then retry the failed operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-02201: type validation failure for the metadata object "{0}"**

**Cause:** The content of the metadata object was not valid against the registered XSDs.

**Action:** Ensure that the metadata object content is valid with respect to the registered XSDs.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-02202: Content of the metadata object "{0}" is not valid.**

**Cause:** The content was not valid either with respect to the registered XSDs or with the registered relationships.

**Action:** Check the content of the metadata object and correct the content as necessary to make it valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-02203: type validation error for the metadata object "{0}" at the node "{1}"**

**Cause:** A validation error occurred at the specified node.

**Action:** Check the content at the specified node for compliance with registered XSDs and relationships.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-02204: type validation warning for the metadata object "{0}" at the node "{1}"**

**Cause:** A validation warning occurred at the specified node.

**Action:** Check the content at the specified node for compliance with registered XSDs.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-02301: The rename unit is invalid because either "{0}" or "{1}" is reused in the rename plan.**

**Cause:** The resource name provided in the rename plan was used more than once.

**Action:** Provide distinct names for source and target names while renaming.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-02302: subobjects "{1}" not found in metadata object "{0}"**

**Cause:** The specified subobjects were not found in the metadata object.

**Action:** Look in the error message log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-02303: The given rename plan syntax is invalid**

**Cause:** The rename plan syntax specified was invalid.

**Action:** Look in the error message log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-02304: RenameOperation failed for StreamedObject "{0}" because subobjects were specified for this streamed object.**

**Cause:** Streamed objects do not support subobjects.

**Action:** Remove the RenameObject that contains reference to the streamed object and subobject references from the RenamPlan.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-02401: The operation {0} on the {1} node is not allowed.**

**Cause:** An attempt was made to customize a node that was not customizable.

**Action:** If the attempted customization is valid, the customization restrictions need to be modified to provide this ability. The customization restrictions can be defined in: the XML schema definition, standalone XML file or an extended metadata file. Also check the customization policy for the MDS session in use and the customization configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration



---

**MDS-02402: The type definition for {1} does not allow customization of {0}.**

**Cause:** An attempt was made to customize a node that was not customizable.

**Action:** If the attempted customization is valid, the customization restrictions need to be modified to provide this ability. The customization restrictions can be defined in: the XML schema definition, standalone XML file, tag library definition file, or an extended metadata file. Also check the customization policy for the MDS session in use and the customization configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-02404: The subelement {1} in the MDX document does not allow customization of {0}.**

**Cause:** An attempt was made to customize a node that was not customizable.

**Action:** Check the customization restriction information which can be located in the schema definition, standalone xml file or an extended metadata file. Also check the customization policy for the MDSSession in use and the customization configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-02405: The attribute {2} in element {1} in the MDX document does not allow customization of {0}.**

**Cause:** An attempt was made to customize a node that was not customizable.

**Action:** If the attempted customization is valid, the customization restrictions need to be modified to provide this ability. The customization restrictions can be defined in: the XML schema definition, standalone XML file or an extended metadata file. Also check the customization policy for the MDS session in use and the customization configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-02406: Customization of {0} is not allowed because it is not explicitly allowed by any type definition nor any extended metadata entry.**

**Cause:** An attempt was made to customize a node that was not customizable.

**Action:** If the attempted customization is valid, the customization restrictions need to be modified to provide this ability. The customization restrictions can be defined in: the XML schema definition, standalone XML file or an extended metadata file. Also check the customization policy for the MDS session in use and the customization configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-02407: Customization of {0} is not allowed because the local reference was not found in the document.**

---

**Cause:** An enquiry about the customizability of a node supplied a local reference that wasn't found in the document.

**Action:** Ensure that the local reference applies to the document.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-02408: The operation {0} on the {1} node is not allowed because the metadata object reference was not found in the change event.**

**Cause:** A document change is not allowed because the metadata object reference was null.

**Action:** Ensure that the change document exists.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-02500: Cannot find a valid MDSSession object for accessing the MDS document using ORAMDS URL**

**Cause:** A valid MDSSession object was not set before accessing the document using the "oramds://" protocol.

**Action:** Use the MDSURLHelper.setMDSSession() method to set a valid MDSSession object before accessing MDS documents using the oramds protocol.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-02501: cannot load the ORAMDS URL "{0}" because MDS session could not be created or resolved**

**Cause:** An error occurred while creating or resolving an MDS session object.

**Action:** Look for messages describing the cause exception in the error message log for more information on the actual reason for failure.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-02600: configuration migration failure because the configuration document contains more than one mds-config element**

**Cause:** The given configuration document contained more than one mds-config element.

**Action:** Correct the configuration document to contain a single mds-config element.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**MDS-02601: configuration migration failure because it contains more than one persistence-config element**

**Cause:** The configuration document contained more than one persistence-config element.

**Action:** Correct the configuration document to contain a valid persistence-config element.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-02602: configuration migration failure because it contains more than one metadata-stores element**

**Cause:** The configuration document contained more than one metadata-stores element

**Action:** Correct the configuration document to be a valid 10.1.3 configuration document.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-02603: configuration migration failure because it contains an invalid metadata-store element**

**Cause:** The configuration document contained an invalid metadata-store element.

**Action:** Correct the configuration document to be a valid 10.1.3 configuration document.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**MDS-05786: Unable to deploy the metadata archive: {0}.**

**Cause:** Metadata archive (MAR) is corrupt.

**Action:** Validate that the metadata archive (MAR) is valid and readable.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-05787: Partition name is not specified in adf-config.xml file.**

**Cause:** A property with name partition-name was not found as a child of the metadata-store element.

**Action:** Specify the target partition as a child property of the metadata-store element in adf-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-05788: Unable to find the JNDI datasource in the file adf-config.xml.**

---

**Cause:** A property with name jndi-datasource was not found as a child of the metadata-store element.

**Action:** Specify the JNDI datasource a child property of the metadata-store element in adf-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-05789: Unable to deploy the metadata archive.**

**Cause:** Metadata archive (MAR) was not found.

**Action:** Ensure that the metadata archive (MAR) is packaged with the application.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-05790: The metadata store definition is either missing or incorrectly specified in the application configuration.**

**Cause:** The metadata store definition is either missing or incorrectly configured in the file adf-config.xml.

**Action:** Ensure that the metadata store definition is present and contains the correct repository configuration

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-05791: An error occurred during the deployment of the metadata archive (MAR) {0}.**

**Cause:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action.

**Action:** Ensure that the metadata store configuration is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-05792: Unable to load MDS configuration from "{0}"**

**Cause:** The MDS configuration is either not defined or incorrect.

**Action:** Ensure that the MDS configuration is correctly defined.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-05793: Metadata path {2} for partition {1} of MDS file repository {0} specified in adf-config.xml is either invalid or unreachable.**

**Cause:** The metadata path named in the error message for the MDS file repository partition cited in the error message was either invalid or unreachable.

---

**Action:** Ensure that the MDS file repository named in the error message is registered and that the metadata partition cited in the error message is configured with a valid metadata path in adf-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-05794: Unable to load MDS persistence configuration from "{0}"**

**Cause:** The MDS persistence configuration is either not defined or incorrect.

**Action:** Ensure that the MDS persistence configuration is correctly defined.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-10001: Error:**

**Cause:** An error occurred. Details are usually given in the accompanying messages.

**Action:** Look for messages describing the cause and take the appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-10003: The specified {0} argument is null or empty.**

**Cause:** A required program argument was null or empty.

**Action:** Record any accompanying exception messages and contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**MDS-10009: The transfer of the document {0} is not successful.**

**Cause:** Document transfer failed

**Action:** Examine any accompanying messages to decide if further action is required.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**MDS-10010: Deleting the document {0} is not successful.**

**Cause:** Document deletion failed

**Action:** Examine any accompanying messages to decide if further action is required.

**Level:** 1

**Type:** WARNING

---

**Impact:** Data

**MDS-10011: The operation on {0} has been rolled back. Total number of documents failed during the operation is {1}.**

**Cause:** The transfer was rolled back

**Action:** Examine any accompanying messages to decide if further action is required.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**MDS-10012: The operation has failed.**

**Cause:** The operation has failed.

**Action:** Examine any accompanying messages to decide if further action is required.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**MDS-10013: {0} operation started.**

**Cause:** Transfer started.

**Action:** Transfer started, no action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Data

**MDS-10014: {0} is completed. Total number of documents successfully processed : {1}, total number of documents failed : {2}.**

**Cause:** Transfer complete.

**Action:** Check any accompanying messages to decide if any action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Data

**MDS-10015: Failure occurred while committing the {0} operation. The operation has been rolled back.**

**Cause:** Failure occurred while committing the operation.

**Action:** Examine any accompanying messages to decide if further action is required.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-10020: Querying checksum data from target repository to avoid transferring unchanged documents.**

---

**Cause:** To apply transfer restriction CHANGED, transfer queries the target repository to check whether documents being transferred already exist with same content.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Data

**MDS-10022: Query to get the checksum of the documents from target repository completed successfully.**

**Cause:** To apply transfer restriction CHANGED, transfer queries the target repository to check whether documents being transferred already exist with same content.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Data

**MDS-10023: No valid exclusion rules are specified in mds-transfer-config.xml to preserve documents in target store.**

**Cause:** No valid namespaces or metadata object names specified in /meta-inf/mds-transfer-config.xml to preserve the documents in target store.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**MDS-10024: Preparing the list of documents to be excluded during transfer as per the configuration given in mds-transfer-config.xml.**

**Cause:** To preserve the documents in target store as specified in the given /meta-inf/mds-transfer-config.xml, MDSTransfer prepares the list of documents to be excluded by looking at source and target stores.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Data

**MDS-10025: Following metadata paths are configured in mds-transfer-config.xml to preserve existing documents under this metadata path in target repository. Configured metadata paths are as follows {0}:**

**Cause:** Some metadata paths are configured in mds-transfer-config.xml to preserve existing documents in target repository.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

---

**MDS-10026: Following Metadata object names are configured in mds-transfer-config.xml to preserve existing metadata objects with same name in target repository. Configured metadata object names are {0}:**

**Cause:** Some metadata object names are configured in mds-transfer-config.xml to preserve existing documents in target repository.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**MDS-10027: To preserve documents in target store, the following documents from source store are marked as excluded by transfer {0}.**

**Cause:** To preserve documents in target store, some documents from source store are marked as excluded by transfer.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**MDS-11001: The type information for "{0}" is not obtainable though the document exists in the MetadataStore.**

**Cause:** Could not get type information for a document, a possibly non-wellformed XML document.

**Action:** Examine the document

**Level:** 1

**Type:** WARNING

**Impact:** Data

**MDS-11002: The type information for "{0}" is not obtainable because of exception "{1}"**

**Cause:** Failed to get type information because an exception was raised.

**Action:** Examine the exception and the document.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**MDS-11003: Failed to force timestamp advance on file {0}: original timestamp = {1}, new timestamp = {2}.**

**Cause:** Failed to advance the timestamp on a file which is being saved.

**Action:** Examine the file and its permissions.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**MDS-11006: Directory {0} does not exist.**



---

**Cause:** The value of a name condition package did not have a corresponding file system directory.

**Action:** Check if the directory was expected and determine why it is not present.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Files

**MDS-11007: Skipping directory {0} because {1} does not match the condition.**

**Cause:** The query considered the given directory, but it could only contain documents that would not match the query.

**Action:** If you expected results from the directory, check that the query is correctly specified.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Programmatic

**MDS-11008: Skipping directory {0} because it is a filestore root.**

**Cause:** The query considered the directory, but it was another root path of the metadata store. This can arise when file store configuration includes multiple root paths and one of these is contained in another.

**Action:** If you expected results from the directory, check that the file store is configured correctly.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Files

**MDS-11009: Skipping directory {0} because {1} is not a valid package name.**

**Cause:** The query skipped the directory because the corresponding package name is invalid.

**Action:** If you expected results from the directory, check the directory name for validity.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Programmatic

**MDS-11010: Document cache {0} exceeds its maximum number of entries {1}, so the cache is cleared.**

**Cause:** The document cache exceeded its defined maximum size so it was cleared. If memory allows, the cache should be large enough for all documents for optimum performance but this is not required.

**Action:** Edit the adf-config.xml file and increase the size of the document cache.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

---

**MDS-11011: Attempting to get failover connection to retry the operation because the database connection failed.**

**Cause:** The connection to the database failed.

**Action:** No action is required. The database is configured with FCF so failover will be attempted.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**MDS-11012: Cache collision has been detected when adding key {0}, label set {1}, sandbox name {2}, scope {3}.**

**Cause:** The described document was being added to the cache, but it was already present. This can be caused by an incorrect miss in the preceding lookup, or very rarely by the document having been just inserted by another thread.

**Action:** If this occurs frequently, contact Oracle Support Services.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Programmatic

**MDS-11013: Cannot store the object of type {0} in the Java Object Cache because the cache or cache region is full**

**Cause:** A CacheFullException or RegionFullException was reported when attempting to store an object in the Java Object Cache.

**Action:** Consider increasing the size of the configured MDS Cache by modifying the cache-config entry in adf-config.xml.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**MDS-11014: Purge-Repos Diagnostics [auto-purge, partition-name, partition-id, #versions purged]: [{0}, {1}, {2}, {3}].**

**Cause:** An auto-purge occurred on a metadata-store.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**MDS-11017: Started creating the final archive file at {0}.**

**Cause:** ArchiveMetadataStore has started to create final archive file with all the changes done on the archive file so far.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

---

**MDS-11018: The final archive file has been created successfully. The archive file is available at {0}.**

**Cause:** ArchiveMetadataStore has created final archive file with all the changes done on the archive file so far.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**MDS-11019: The default CharSet {0} is not a unicode character set. File names with non-ASCII characters may not operate as expected. Check locale settings.**

**Cause:** The Java default CharSet is used to convert file names to and from Java Strings. When this CharSet is a non-unicode character encoding, filenames that contain non-ASCII characters may not be correctly mapped to Java characters.

**Action:** Check the locale environment variable settings for the process that is running the JVM that MDS is running in to ensure that a UTF encoding is being used. For example, the LC\_ALL and LANG settings may be relevant.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**MDS-11020: Cannot delete the intermediary archive file {0}.**

**Cause:** The intermediary archive file could not be deleted.

**Action:** Try deleting the file outside of MDS.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**MDS-90013: The metadata partition with name "{0}" does not exist in the metadata repository "{1}".**

**Cause:** The metadata partition with the specified name was not found in the metadata repository.

**Action:** Create a metadata partition with the specified name in the metadata repository before trying this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Topology

**MDS-90014: cannot update the metadata because the application is read-only**

**Cause:** No metadata update was made because the ReadOnlyMode attribute was enabled.

**Action:** Disable the ReadOnlyMode attribute of the target application configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Topology

---

**MDS-90015: The metadata repository with name "{0}" does not exist.**

**Cause:** The metadata repository with the specified name was not found.

**Action:** Verify that the repository name is spelled correctly. If the repository does not exist, create one with the specified name and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Topology

**MDS-90016: There are no applications deployed to partition "{0}".**

**Cause:** An attempt was made to perform this operation on a partition that is not associated with a deployed application.

**Action:** Specify a partition that is associated with a deployed application.

**Level:** 1

**Type:** ERROR

**Impact:** Topology

**MDS-90017: The application to be used for this operation is not specified.**

**Cause:** Could not determine which application configuration to use for this operation since there is more than one application deployed to partition "{0}".

**Action:** Specify an application that is deployed to partition "{0}" to be used for this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Topology

**MDS-90018: Application "{1}" is not deployed to partition "{0}".**

**Cause:** The specified application was not deployed to the specified partition.

**Action:** Specify an application that is deployed to the partition.

**Level:** 1

**Type:** ERROR

**Impact:** Topology

**MDS-90019: cannot set the user property on the driver: {0}**

**Cause:** A problem occurred while setting the user property on the driver.

**Action:** Ensure that the database server is running properly.

**Level:** 1

**Type:** ERROR

**Impact:** Topology

**MDS-90020: Metadata store cannot be assigned to server "{0}".**

**Cause:** A problem occurred while assigning resource to the server.

**Action:** Ensure that the server is running properly.

**Level:** 1

**Type:** ERROR

---

**Impact:** Topology

**MDS-90021: Metadata path {0} is invalid.**

**Cause:** The path used to create a FileMetadataStore was invalid. It must point to a directory.

**Action:** Correct the metadata path.

**Level:** 1

**Type:** ERROR

**Impact:** Topology

**MDS-90022: The host name of the database repository cannot be empty.**

**Cause:** The host name of the database repository was empty or null.

**Action:** Use a valid host name.

**Level:** 1

**Type:** ERROR

**Impact:** Topology

**MDS-90023: The database name of the database repository cannot be empty.**

**Cause:** The database name of the database repository was empty or null.

**Action:** Use a valid database name.

**Level:** 1

**Type:** ERROR

**Impact:** Topology

**MDS-90024: The user name of the database repository cannot be empty.**

**Cause:** The user name of the database repository was empty or null.

**Action:** Use a valid user name.

**Level:** 1

**Type:** ERROR

**Impact:** Topology

**MDS-90025: The password of the database repository cannot be empty.**

**Cause:** The password of the database repository was empty or null.

**Action:** Use a valid password.

**Level:** 1

**Type:** ERROR

**Impact:** Topology

**MDS-90026: The server name cannot be empty.**

**Cause:** The server name was empty or null.

**Action:** Use a valid server name.

**Level:** 1

**Type:** ERROR

**Impact:** Topology

---

**MDS-90027: cannot find server "{1}" to register the metadata repository "{0}"**

**Cause:** The server name was invalid.

**Action:** Use a valid server name.

**Level:** 1

**Type:** ERROR

**Impact:** Topology

**MDS-90028: Metadata repository with name "{0}" already exists.**

**Cause:** Metadata repository with the specified name already exists.

**Action:** Verify that the repository name is spelled correctly. If the repository already exists, create one with a different name and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Topology

**MDS-90029: The metadata db repository with name "{0}" does not exist.**

**Cause:** The metadata db repository with the specified name was not found.

**Action:** Verify that the db repository name is spelled correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Topology

**MDS-90030: The metadata file repository with name "{0}" does not exist.**

**Cause:** The metadata file repository with the specified name was not found.

**Action:** Verify that the file repository name is spelled correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Topology

**MDS-90031: The JDBC resource of metadata db repository "{0}" cannot be found.**

**Cause:** The JDBC resource was not found.

**Action:** Verify that the metadata db repository is set up correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Topology

**MDS-90032: The metadata store of metadata file repository "{0}" cannot be found.**

**Cause:** The metadata store was not found.

**Action:** Verify that the metadata file repository is set up correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Topology

**MDS-90033: unknown DB vendor code: "{0}"**

---

**Cause:** The DB vendor code is invalid.

**Action:** Use a valid DB vendor code, such as 0 (ORACLE), 1 (MSSQL), or 2 (IBMDB2).

**Level:** 1

**Type:** ERROR

**Impact:** Topology

**MDS-90034: The source directory or archive "{0}" for importing metadata is invalid.**

**Cause:** The directory or archive location used to import metadata was invalid. It must point to a valid, existing directory or archive.

**Action:** Correct the source directory or archive location.

**Level:** 1

**Type:** ERROR

**Impact:** Topology

**MDS-90035: The target directory or archive "{0}" for exporting metadata is invalid.**

**Cause:** The directory or archive location used to export metadata was invalid. It must point to a valid location.

**Action:** Correct the target directory or archive file location.

**Level:** 1

**Type:** ERROR

**Impact:** Topology

**MDS-90036: The application does not have a valid MAR file path.**

**Cause:** The MAR path used to import MAR was invalid. It must point to a valid, existing MAR file.

**Action:** Make sure the MAR file exists and is located in the correct directory of the application.

**Level:** 1

**Type:** ERROR

**Impact:** Topology

**MDS-90037: The archive "{0}" does not contain valid contents.**

**Cause:** The archive used to import metadata was invalid. It must be to a valid, existing zip or jar file.

**Action:** Make sure the archive is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Topology

**MDS-90038: The database authentication alias "{0}" already exists. To reuse the same authentication alias, try the operation again without specifying user and password.**

**Cause:** An attempt was made to configure a database authentication alias that already existed in Websphere server.

---

**Action:** Delete the existing authentication alias and try again, or specify a new authentication alias, or reuse the existing authentication alias by not specifying user and password.

**Level:** 1

**Type:** ERROR

**Impact:** Topology

**MDS-90039: The database authentication alias "{0}" cannot be found. To create the authentication alias, try the operation again with user and password specified.**

**Cause:** An attempt was made to use a database authentication alias that was not configured in Websphere server.

**Action:** Make sure the specified database authentication alias is properly configured in Websphere server, or automatically create the authentication alias by specifying user and password.

**Level:** 1

**Type:** ERROR

**Impact:** Topology

**MDS-90040: failed to connect to database**

**Cause:** An error occurred when trying to connect to database.

**Action:** Make sure the database connection details are correct. Look at the cause exception for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Topology

**MDS-91001: MDS domain runtime MBean is not available. "{0}" operation failure.**

**Cause:** MDS domain runtime MBean was not available in the server.

**Action:** Ensure the MDS domain runtime MBean is available in the server.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-91002: MDS Application runtime MBean for "{0}" is not available. "{1}" operation failure.**

**Cause:** MDS Application runtime MBean was not available in the server.

**Action:** Ensure the MDS Application runtime MBean for the application is available in the server.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-91003: Multiple MDSAppRuntimeMBean exist for "{0}". To execute the command, parameter "applicationVersion" is required. "{1}" operation failure.**

**Cause:** Multiple MDSAppRuntimeMBean for the application were found in the server.



---

**Action:** Provide the 'applicationVersion' parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-91004: MDS domain runtime MBean commands can be executed only from the Admin server. "{0}" operation failure.**

**Cause:** WLST was not connected to the Admin server.

**Action:** Connect to an Admin server before executing the command.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-91005: No connection to a "{0}" server exists. The operation "{1}" can be executed only in the online mode.**

**Cause:** Command was executed in the offline mode.

**Action:** Ensure WLST/WSADMIN is connected to the server.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-91006: Expecting a "{0}" for parameter "{1}" but encountering "{2}". "{3}" operation failure.**

**Cause:** Parameter type passed to the command was not correct.

**Action:** Ensure the correct type of parameters are passed to the command.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-91007: dbVendor should be one of ORACLE, MSSQL, or IBMDB2. "{0}" operation failure.**

**Cause:** dbVendor value was not correct.

**Action:** Ensure the dbVendor value is one of ORACLE, MSSQL, or IBMDB2.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-91008: The "{0}" parameter is required. Provide a valid value and retry the operation.**

**Cause:** Required parameter for the command was not given.

**Action:** Provide the required parameters for the command.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**MDS-91009: Operation "{0}" failure.**

**Cause:** Exception occurred during the execution of the command.

**Action:** Provide the required parameters for the command.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-91010: The "adf-config" element is not available in the given archive file. "{0}" operation failure.**

**Cause:** The "adf-config" element is not available in the given archive file.

**Action:** Ensure the "adf-config" element is available in the adf-config.xml of the given archive file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-91011: No "mds-config" element exists in the adf-config.xml of the given archive. "{0}" operation failure.**

**Cause:** No mds-config element existed in the adf-config.xml file of the archive file.

**Action:** Ensure the "mds-config" element is available in the adf-config.xml file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-91012: Metadata repository connection type value should be either "File" or "DB". "{0}" operation failure.**

**Cause:** Metadata repository connection type value is not correct.

**Action:** Ensure the metadata repository connection type value is either 'File' or 'DB'.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-91013: For the metadata repository's DB connection type, JNDI location is a required parameter. "{0}" operation failure.**

**Cause:** JNDI location not provided for DB connection type.

**Action:** Provide the JNDI location string while updating the repository connection to DB.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-91014: For the metadata repository's File connection type, path location is a required parameter. "{0}" operation failure.**

**Cause:** The path value was not provided for File connection type.

---

**Action:** Provide the path location string while updating the repository connection to File.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-91015: All parameters are required to update shared metadata repository configuration in adf-config.xml. At present, source archive has no connection details for the namespace "{0}". "{1}" operation failure.**

**Cause:** Complete connection information was not provided to set the shared repository for the given namespace.

**Action:** Provide complete connection information in case the adf-config.xml file does not have any metadata repository connection information for the given namespace already.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-91016: All parameters are required to define new application metadata repository configuration in adf-config.xml. The source archive configuration does not contain any application metadata repository at present. "{0}" operation failure.**

**Cause:** Complete connection information was not provided to set the application target repository.

**Action:** Provide complete connection information in case the adf-config.xml does not have any metadata repository connection information for the application target repository already.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-91017: The given namespace "{0}" to set the shared repository is not valid. Ensure that the namespace is available in the adf-config.xml file and it is not a sub-namespace of any other namespace. "{1}" operation failure.**

**Cause:** The namespace provided to set the shared repository details is not valid.

**Action:** Ensure that the namespace is available in the adf-config.xml file and it is not a subnamespace of any other namespace in that file.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**MDS-91018: No namespaces are mapped to any shared repository in the source archive adf-config.xml configuration file. Shared repository details cannot be set. "{0}" operation failure.**

**Cause:** No namespaces were mapped to any shared repository in the source archive adf-config.xml configuration file.

**Action:** To set the shared repository connections, ensure at least one namespace is mapped to shared repository in the source archive adf-config.xml file.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**MDS-91019: Multiple MDSAppRuntimeMBean exist for application "{0}". Ensure that the "application" "node" and "server" parameters are correct. "{1}" operation failure.**

**Cause:** Multiple MDSAppRuntimeMBean for the application were found in the server.

**Action:** Ensure that the "application" "node" and "server" parameters are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

## MODPLSQL-00001 to MODPLSQL-00868

**MODPLSQL-00001: mod\_plsql: Out of memory**

**Cause:** System has run out of memory

**Action:** Reduce memory usage in the system

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**MODPLSQL-00010: mod\_plsql: Out of memory**

**Cause:** System has run out of memory

**Action:** Reduce memory usage in the system

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**MODPLSQL-00102: mod\_plsql: Wrong language, territory or charset in NLS\_LANG value**

**Cause:** Incorrect NLS\_LANG value specified

**Action:** Refer to RDBMS and NLS documentation for the acceptable NLS\_LANG value

**Level:** 1

**Type:** ALERT

**Impact:** Configuration

**MODPLSQL-00350: mod\_plsql: Bad Procedure/Argument name in the request**

**Cause:** The procedure name and/or the argument is not a legal PL/SQL identifier

**Action:** Correct the procedure name and the arguments to be legal PL/SQL identifiers

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**MODPLSQL-00367: mod\_plsql: Illegal PLSQL identifier in input**

**Cause:** The procedure name and/or the argument is not a legal PL/SQL identifier

---

**Action:** Correct the procedure name and the arguments to be legal PL/SQL identifiers

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**MODPLSQL-00368: mod\_plsql: No target procedure specified for invocation**

**Cause:** The procedure name to invoke is not specified in the URL

**Action:** Specify a legal PL/SQL procedure to invoke

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**MODPLSQL-00369: mod\_plsql: Illegal procedure name, part exceeds 32 bytes**

**Cause:** The procedure name specified exceeds the legal PLSQL identifier length

**Action:** Correct the procedure name to be a legal PL/SQL identifier

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**MODPLSQL-00370: mod\_plsql: Illegal procedure name, has an empty part**

**Cause:** The procedure name is not a legal PLSQL identifier

**Action:** Correct the procedure name to be a legal PL/SQL identifier

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**MODPLSQL-00371: mod\_plsql: Illegal procedure name, too many parts**

**Cause:** The procedure name is not a legal PLSQL identifier

**Action:** Correct the procedure name to be a legal PL/SQL identifier

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**MODPLSQL-00868: mod\_plsql: Failed to validate configuration parameters**

**Cause:** Illegal configuration property specified in the mod\_plsql configuration

**Action:** Refer to the logs for more details, and correct the offending configuration property

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

## OAAM-00000 to OAAM-70026

**OAAM-00000: Invalid Message**

**Cause:** Unable to find Message Definition. Internal Error

**Action:** Report to Administrator

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-00001: System internal Error has occurred. System cannot complete the operation at this time.**

**Cause:** System Internal Error has occurred. This is usually due to some constraint or unavailability of the resources that oaam is using.

**Action:** Please try the operation again one more time. If the resource problem is transient then operation may succeed or will at least give some other application error message. However if the operation does not succeed please, report to Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-00002: Operation not allowed**

**Cause:** User may not have sufficient privileges

**Action:** Report to the Administrator about insufficient privileges

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-00003: Database Error**

**Cause:** Database may not be available

**Action:** Try again or Report to Administrator

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-00004: Insufficient context Data. Required: {0}**

---

**Cause:** Expected context information is not provided

**Action:** Report to Administrator about insufficient context data

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-00005: Database Error, exception message is {0}**

**Cause:** Database unavailability or some db querying exception.

**Action:** Report to Administrator with the database error message

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-01001: Property name is required.**

**Cause:** Property name is missing from the data.

**Action:** Please make sure that property name is provided for the operation

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-01002: Property value is required.**

**Cause:** Property value is missing from the data.

**Action:** Please make sure that property value is provided for the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-01003: Property with name {0} already exists.**

**Cause:** Property with the name already exists.

**Action:** Please use a different property name and try this operation again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-01004: Property with name {0} does not exist.**

**Cause:** Property with the name was not found in the system.

**Action:** Please make sure the property name provided is correct and then try this operation again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-01005: Property search query is required to search properties.**

**Cause:** Property search query was not provided for the search.



---

**Action:** Please make sure that the valid property search query is provided for the operation and then try this operation again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-01101: Object type was not specified for finding usage.**

**Cause:** For finding usage the required object type was not specified.

**Action:** Find usage function needs the object type to be specified. Please specify a non-null integer value and re-try this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-01102: Object unique key was not specified for finding usage.**

**Cause:** For finding usage the required object unique key (primary key) was not specified.

**Action:** Find usage function needs the object unique (primary) key to be specified. Please specify a non-null long value and re-try this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-01103: Usage cannot be computed for object type {0}**

**Cause:** Usage API supports certain types of objects. Specified object is not specified by usage API.

**Action:** Please specify the object type which can be referenced by other objects in the system.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-01104: Usage information for the primary object of type {0} with an unique id of {1} cannot be determined.**

**Cause:** Usage API is trying to find usage of an object that does not exist.

**Action:** A unique id of object was provided which was not found in the system. Please make sure that the unique id and the object are correct and re-try this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-10006: Invalid Application {0} and Login {1} Combination**

**Cause:** Combination may be incorrect or User name is used in place of login name

**Action:** Report to Administrator

---

**Level: 1**

**Type: ERROR**

**Impact: Process**

**OAAM-10301: Note cannot be null or empty**

**Cause:** Note cannot be null or empty String

**Action:** Provide a valid note

**Level: 1**

**Type: ERROR**

**Impact: Process**

**OAAM-10302: Closed case, {0}, cannot be escalated.**

**Cause:** Closed case, {0}, cannot be escalated.

**Action:** Reopen the closed case before trying to escalate.

**Level: 1**

**Type: ERROR**

**Impact: Process**

**OAAM-10303: The Case {0}, is not a CSR case hence it cannot be escalated.**

**Cause:** The Case {0}, is not a CSR case hence it cannot be escalated.

**Action:** The case type for case {0} should be changed to CSR for escalation.

**Level: 1**

**Type: ERROR**

**Impact: Process**

**OAAM-10304: Query cannot be null**

**Cause:** Query cannot be null

**Action:** Provide a valid Query object

**Level: 1**

**Type: ERROR**

**Impact: Process**

**OAAM-10305: No Query Expression found.**

**Cause:** No Query Expression found.

**Action:** Provide the required parameters for the query expression

**Level: 1**

**Type: ERROR**

**Impact: Process**

**OAAM-10306: No Records found**

**Cause:** No Records found

**Action:** Change the criteria before doing the operation.

**Level: 1**

**Type: ERROR**

---

**Impact:** Process

**OAAM-10307: No linked Sessions found.**

**Cause:** No Linked Sessions found.

**Action:** For the given case no linked Sessions found.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-10308: No Sessions to Link**

**Cause:** No Sessions to Link.

**Action:** Provide sessions to link

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-10309: No Sessions to unlink.**

**Cause:** No Sessions to unlink

**Action:** Provide sessions to unlink.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-11111: User unauthorized to access the method {0}.**

**Cause:** User unauthorized to access the method {0}.

**Action:** Retry accessing the method {0} with valid authorization.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-11112: Session Id of admin users is required for case action.**

**Cause:** Session id was not provided for performing the case action.

**Action:** Retry the same case action and provide the valid admin user session id for that API call.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-11113: Action Id is required for case action.**

**Cause:** Action was not provided for performing the case action.

**Action:** Retry the same case action and provide the valid action id for that API call. Action id is actually case action enum.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**OAAM-11114: Sub action Id is required for case action.**

**Cause:** Sub action was not provided for performing the case action.

**Action:** Retry the same case action and provide the valid sub-action id for that API call. Sub action id is actually case action enum.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-11115: New status required for case change status action.**

**Cause:** New status was not provided for performing the change status case action.

**Action:** Retry the same case action and provide the valid new status (Integer object) for that API call. New status is actually case status enum.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-11116: Reopen the closed case before trying to edit : Case id {0}**

**Cause:** The case is in closed state. In this state case disposition or expiration cannot change.

**Action:** The case is closed and in this state its disposition, severity or expiration cannot change. To change these attributes, also change the status of the case along with new severity, expiration time or disposition

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-11117: Case with id {0} is expired. It can not be edited.**

**Cause:** The case is in expired state. In this state case disposition or expiration date cannot change.

**Action:** The case is expired and in this state its disposition, severity or expiration cannot change. Please re-open the case first and then try this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-11120: Case reset action cannot be done because: {0}**

**Cause:** Case reset action cannot be performed due to mentioned reason.

**Action:** Retry the same case action after fixing the above issue.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-11121: Challenge question related case action cannot be done because: {0}**

---

**Cause:** Challenge question related case action cannot be performed due to the mentioned reason.

**Action:** Retry the same case action after fixing the above issue.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-11122: Cannot reset user, as user's image, phrase and questions are already reset!**

**Cause:** User has image, phrase and questions already reset.

**Action:** Cannot reset user's image, phrase and questions since they are not active.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-11123: Cannot reset user's image, as it is not set!**

**Cause:** User does not have image set.

**Action:** Cannot reset user's image. This is because either user is not registered or image is not active for user.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-11124: Cannot reset user's phrase, as it is not set!**

**Cause:** User does not have phrase set.

**Action:** Cannot reset user's phrase. This is because either user is not registered or phrase is not active for user.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20000: Policy name cannot be null or empty**

**Cause:** Policy name cannot be null or empty

**Action:** Provide a valid Policy name

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20001: Policy weight must be between {0} and {1}**

**Cause:** Policy weight must be between {0} and {1}

**Action:** Ensure that the Policy weight is between {0} and {1}

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**OAAM-20002: Policy description cannot be null or empty**

**Cause:** Policy description cannot be null or empty

**Action:** Provide a valid Policy description

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20003: A Policy with name {0} already exists**

**Cause:** A Policy with name {0} already exists

**Action:** A Policy with name {0} already exists. Please use a different name

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20004: PolicyId cannot be null**

**Cause:** PolicyId cannot be null

**Action:** Provide a non null policyId

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20005: Policy with policyId {0} does not exist**

**Cause:** Policy with policyId {0} does not exist

**Action:** Provide a valid policyId

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20009: Rule Id cannot be null**

**Cause:** Rule Id cannot be null

**Action:** Provide a non null rule Id

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20010: Rule with the given Id not found**

**Cause:** Rule with the given Id not found

**Action:** Provide a valid rule Id

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20011: Profile rule map for the given map id not found**

**Cause:** Profile rule map for the given map id not found

---

**Action:** Provide a valid profile rule map id

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20012: Profile for the given map id not found**

**Cause:** Profile for the given map id not found

**Action:** Provide a valid map id with profile

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20013: Profile rule map id cannot be null**

**Cause:** Profile rule map id cannot be null

**Action:** Provide a non null profile rule map id

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20014: Rule condition map id cannot be null**

**Cause:** Rule condition map id cannot be null

**Action:** Provide a non null rule condition map id

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20015: Rule Param Value not found**

**Cause:** Rule Param Value not found

**Action:** Provide a valid map id

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20016: Rule Param not found**

**Cause:** Rule Param not found

**Action:** Provide a valid map id

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20017: The following policies depend on some of the policies being deleted:  
{0}**

**Cause:** The following policies depend on some of the policies being deleted: {0}

**Action:** The policies cannot be deleted until dependency is removed.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20018: Rule parameter value not found for the given rule parameter. Rule may not work as expected unless this error is fixed.**

**Cause:** Rule parameter value not found for the given rule parameter.

**Action:** Each rule parameter is associated with its value when added to a policy. System was not able to find a corresponding value for the rule parameter in the policy data. Please verify the rule and its details. Make sure the migration had no errors if this rule has been migrated from previous release.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20019: Rule name cannot be null**

**Cause:** Rule name cannot be null

**Action:** Provide a valid Rule Name

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20020: Rule description cannot be null**

**Cause:** Rule description cannot be null

**Action:** Provide a valid Rule description

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20021: Rule score must be between {0} and {1}**

**Cause:** Rule score must be between {0} and {1}

**Action:** Provide a rule score value between {0} and {1}

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20022: Rule weight must be between {0} and {1}**

**Cause:** Rule weight must be between {0} and {1}

**Action:** Provide a rule weight between {0} and {1}

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20023: Minimum device score must be between {0} and {1}**

**Cause:** Minimum device score must be between {0} and {1}



---

**Action:** Provide a minimum device score between {0} and {1}

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20024: Maximum device score must be between {0} and {1}**

**Cause:** Maximum device score must be between {0} and {1}

**Action:** Provide a maximum device score between {0} and {1}

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20025: Maximum Device Score must not be less than Minimum Device Score**

**Cause:** Maximum Device Score must not be less than Minimum Device Score

**Action:** Provide a maximum device score that is more than or equal to minimum device score

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20026: Minimum country score must be between {0} and {1}**

**Cause:** Minimum country score must be between {0} and {1}

**Action:** Provide a minimum country score value between {0} and {1}

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20027: Maximum country score must be between {0} and {1}**

**Cause:** Maximum country score must be between {0} and {1}

**Action:** Provide a maximum country score value between {0} and {1}

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20028: Maximum country score must not be less than Minimum country score**

**Cause:** Maximum country score must not be less than Minimum country score

**Action:** Provide a maximum country score that is more than or equal to minimum country score

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20029: Minimum state score must be between {0} and {1}**

---

**Cause:** Minimum state score must be between {0} and {1}  
**Action:** Provide a minimum state score value between {0} and {1}  
**Level:** 1  
**Type:** ERROR  
**Impact:** Process

**OAAM-20030: Maximum state score must be between {0} and {1}**  
**Cause:** Maximum state score must be between {0} and {1}  
**Action:** Provide a maximum state score value between {0} and {1}  
**Level:** 1  
**Type:** ERROR  
**Impact:** Process

**OAAM-20031: Maximum state score must not be less than Minimum state score**  
**Cause:** Maximum state score must not be less than Minimum state score  
**Action:** Provide a maximum state score that is more than or equal to minimum state score  
**Level:** 1  
**Type:** ERROR  
**Impact:** Process

**OAAM-20032: Minimum city score must be between {0} and {1}**  
**Cause:** Minimum city score must be between {0} and {1}  
**Action:** Provide a minimum city score value between {0} and {1}  
**Level:** 1  
**Type:** ERROR  
**Impact:** Process

**OAAM-20033: Maximum city score must be between {0} and {1}**  
**Cause:** Maximum city score must be between {0} and {1}  
**Action:** Provide a maximum city score value between {0} and {1}  
**Level:** 1  
**Type:** ERROR  
**Impact:** Process

**OAAM-20034: Maximum city score must not be less than Minimum city score**  
**Cause:** Maximum city score must not be less than Minimum city score  
**Action:** Provide a maximum city score that is more than or equal to minimum city score  
**Level:** 1  
**Type:** ERROR  
**Impact:** Process

**OAAM-20035: A rule with name {0} already exists in this policy**

---

**Cause:** A rule with name {0} already exists in this policy

**Action:** Provide a different rule name.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20036: Policy Rule Map with id {0} does not exist**

**Cause:** Policy Rule Map with id {0} does not exist

**Action:** Create the appropriate policy-rule mapping

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20037: ConditionId cannot be null**

**Cause:** ConditionId cannot be null

**Action:** Provide a valid conditionId

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20038: Condition with conditionId {0} does not exist**

**Cause:** Condition with conditionId {0} does not exist

**Action:** Provide a valid conditionId

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20039: {0} is not a valid runmode**

**Cause:** {0} is not a valid runmode

**Action:** Provide a valid runmode

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20040: {0} is not a valid policy type**

**Cause:** {0} is not a valid policy type

**Action:** Provide a valid policy type

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20041: {0} is not a valid checkpoint**

**Cause:** {0} is not a valid checkpoint

**Action:** Provide a valid checkpoint

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20042: Destination policy cannot be same as source policy**

**Cause:** Destination policy cannot be same as source policy

**Action:** Provide a destination policy different from source policy

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20043: Override with overrideId {0} does not exist**

**Cause:** Override with overrideId {0} does not exist

**Action:** Provide a valid overrideId

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20044: Override with overrideId {0} does not belong to policyId {1}**

**Cause:** Override with overrideId {0} does not belong to policyId {1}

**Action:** Provide an overrideId that belongs to the specified policy.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20045: Override id cannot be null or empty**

**Cause:** OverrideId cannot be null or empty

**Action:** Provide a valid overrideId

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20046: Column id cannot be null or empty**

**Cause:** ColumnId cannot be null or empty

**Action:** Provide a valid columnId

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20047: Ruleset Result with column id {0} does not belong to policy id {1}**

**Cause:** RuleSet Result with columnId {0} does not belong to policyId {1}

**Action:** Provide a columnId that belongs to the specified policy.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**OAAM-20048: The provided overrides set is not complete for this policy.**

**Cause:** The provided orderedOverRideIds array does not contain all the overrideIds for the policy

**Action:** Provide an array having all the overrideIds for the policy

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20049: Override cannot be added for policy with policyId = {0}, since no rules have been added to the policy**

**Cause:** Override cannot be added for policy with policyId = {0}, since no rules have been added to the policy

**Action:** For adding override the policy should have a rule

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20050: Condition id list provided is null or empty**

**Cause:** Condition Id List provided is null or empty

**Action:** Provide a non null and non empty list

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20051: Rule Id is null or Rule for the given id not found**

**Cause:** Rule Id is null or Rule for the given id not found

**Action:** Provide a valid Rule object.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20052: Rule Condition for the given condition Id not found**

**Cause:** Rule Condition for the given condition Id not found

**Action:** Provide a valid and existing Rule Condition Id.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20053: Policy Rule Map cannot be null.**

**Cause:** Policy Rule Map cannot be null.

**Action:** Provide a non null Policy Rule Map

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**OAAM-20054: Number of conditions mismatch with the number of conditions that exists.**

**Cause:** Number of conditions mismatch with the number of conditions that exists.

**Action:** Provide the same number of conditions available.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20055: Condition Map provided does not exist**

**Cause:** Condition Map provided does not exist

**Action:** Provide a valid and existent Condition Map Id.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20056: Group is already linked and cannot be linked again.**

**Cause:** Group is already linked and cannot be linked again.

**Action:** Provide a valid and unlinked group for linking.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20057: Group Id cannot be null.**

**Cause:** Group Id cannot be null.

**Action:** Provide a valid and non null Group Id.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20058: Some of the groups are not linked and hence cannot be unlinked.**

**Cause:** Some of the groups are not linked hence cannot be unlinked.

**Action:** WARNING:Provide all the linked groups for unlinking

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20059: The condition type for condition {0} is not compatible with the checkpoint for policy {1}**

**Cause:** The condition type for condition {0} is not compatible with the checkpoint for policy {1}

**Action:** Provide a condition whose condition type is compatible with the checkpoint of policy

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**OAAM-20060: The condition [{0}] you are attempting to delete is associated with one or more policies and hence it cannot be deleted.**

**Cause:** The condition [{0}] you are attempting to delete is associated to one or more policies and hence it cannot be deleted.

**Action:** Remove the condition from the policies before deleting the condition

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20061: The policy type and checkpoint for the policy {0} do not match with that of the parent policy {1}**

**Cause:** The policy type and checkpoint for the policy {0} do not match with that of the parent policy {1}

**Action:** Ensure that policy type and checkpoint for the child policy is same as that of parent policy

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20062: Score must be between {0} and {1}**

**Cause:** Score must be between {0} and {1}

**Action:** Provide a score between {0} and {1}

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20063: {0} is not a valid result type**

**Cause:** {0} is not a valid result type

**Action:** Provide a valid result type

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20064: {0} is not a valid rule result**

**Cause:** {0} is not a valid rule result

**Action:** Provide a valid value for rule result

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20065: Rule results for columns {0} and {1} are same**

**Cause:** Rule results for columns {0} and {1} are same

**Action:** Provide different rule results for each column

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20066: Filter key type was not provided for retrieving filter key.**

**Cause:** Filter key type must be provided as an integer value. This error occurred because the value was not provided to get the correct filter based on the key type.

**Action:** Provide a non-null value for filter key type and retry this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20067: Transaction definition id was not provided for retrieving filter key.**

**Cause:** Transaction definition id provided must be a long value. This error occurred because the value was not provided to get the correct filter based on the filter key type and transaction definition.

**Action:** Provide a non-null value for transaction definition id and retry this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20068: Transaction not found for the given transaction definition id.**

**Cause:** Transaction definition id provided did not match with any of the transaction definitions in the system.

**Action:** Provide a valid transaction definition id and re-try this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20069: Filter condition key was not provided.**

**Cause:** Filter condition lookup key that was provided was either null or empty.

**Action:** Provide a valid filter condition lookup key string and retry this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20070: Condition filter was not found based on filter Condition key {0}.**

**Cause:** Filter key provided does not match any condition filter.

**Action:** Please provide a correct condition filter descriptor key and then retry this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20071: The provided filter key is invalid.**



---

**Cause:** Filter key provided was either null or empty.

**Action:** Please provide a valid lookup string. Also note that any spaces at the beginning and end of the lookup string will be ignored.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20072: No filter descriptor found for key {0}**

**Cause:** Though Filter key provided was valid, there is no filter key descriptor that matched the key provided.

**Action:** Please provide a lookup string that matches one of the filter keys in the system. Make sure the format is right and there are no typo errors.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20073: Number of Rule set results is not equal to the number of rules in the policy.**

**Cause:** Number of RuleSetResults is not equal to the number of rules in the policy.

**Action:** Number of RuleSetResults should be equal to the number of rules in the policy

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-20074: Filter key descriptor is invalid.**

**Cause:** Filter key provided was either null or empty.

**Action:** Please provide a lookup string that is not null or empty. Also notice that any spaces at the beginning and end of the lookup string will be ignored.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-30001: Group data is required to complete this operation.**

**Cause:** Operation needs the group data and that was not provided.

**Action:** Provide valid group data and please retry this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-30002: {0} Group with name {1} already exists.**

**Cause:** Group by the name and value type already exists.

**Action:** Please try a different group name for the given type of group.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**OAAM-30003: Group type {0} not found.**

**Cause:** Group type provided for the operation was not correct.

**Action:** Please try a different group type. Group types can be found in value.type.enum thru system enumerations user interface.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-30004: Group name is incorrect.**

**Cause:** Group name is incorrect. It is not a valid group name.

**Action:** Please provide a alphanumeric string as group name.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-30005: Group description is incorrect.**

**Cause:** Group description is incorrect. It is not a valid group description.

**Action:** Please provide an alphanumeric string for group description.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-30006: Group cache type is incorrect.**

**Cause:** Group cache type is incorrect. It is not a valid group cache type.

**Action:** Please provide a correct cache type. Please refer to cache type enum for the possible values.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-30007: Group with given information not found: {0}.**

**Cause:** Group with given information not found.

**Action:** Please provide correct information so group can be retrieved. You can use searchGroups feature to find groups in the system.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-30008: Group type cannot be changed.**

**Cause:** Type of a group is part of basic function in the way the group is used in the system. Group type cannot be changed at this time.

**Action:** Please create another group with required value type and then use it.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-30009: Group type {0} not found.**

**Cause:** Group type provided for the operation was not correct.

**Action:** Please try a different group type. Group types can be found in value.list.type.enum thru system enumerations user interface.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-30010: Group type cannot be changed.**

**Cause:** Type of a group is part of basic function in the way the group is used in the system. Group type cannot be changed at this time.

**Action:** Please create another group with required type and then use it.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-30011: Group element {0} is invalid for this group.**

**Cause:** Group element is null or group element type is not compatible with the group type.

**Action:** Please provide an element that is compatible with the group type.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-30012: List of groups is required for this operation.**

**Cause:** List of groups that is required for this operation was not found.

**Action:** This operation needs a list of groups to work on. That list is found to be null. Please provide a valid list of groups and then re-try this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-30013: List of groups has invalid group information.**

**Cause:** List of groups that is required for this operation contains invalid group information.

**Action:** This operation needs a list of groups to work on. That list is found to have some groups related information which is incorrect. Please provide a valid list of groups that has non-null group ids and then re-try this operation. Any duplicates in the list will be ignored.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**OAAM-30014: Query returned multiple groups from different group types**

**Cause:** Query returned multiple groups of mixed type

**Action:** Use more specific search criteria to limit the number of groups returned.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-30015: Group element with given information not found {0}.**

**Cause:** Group element with given information not found.

**Action:** Please provide correct information so the group element can be retrieved. You can use searchGroupElements feature to find group elements in the system.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-30016: Element {0} is not a member of group {1}.**

**Cause:** Element is not a member of the group.

**Action:** Please provide a correct combination of element and group.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-30017: The group {0} cannot be deleted. Because it is linked to following policies {1}**

**Cause:** Policies are linked to this group. Hence the group cannot be deleted.

**Action:** The group is linked to policies and might contain session and transaction data associated with this group. Hence this group cannot be deleted.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-30018: The group {0} cannot be deleted. Because it is used by rules.**

**Cause:** Rule parameters are using this group as parameter value. Hence the group cannot be deleted.

**Action:** The group is used as a parameter value in some rules in some models. Please remove the group name or id as value of rule parameter(s) and then re-try this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-30019: The group {0} cannot be deleted. Because it is used by user groups.**

**Cause:** Some user groups are referring to this group. Hence the group cannot be deleted.

---

**Action:** The group is used by some user groups. Please remove the group name or id from those user groups and then re-try this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-30020: The IP Cluster object cannot be null**

**Cause:** The OARMIPCluster object cannot be null

**Action:** Pass a non null OARMIPCluster object

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-30021: The label for IP Cluster cannot be null**

**Cause:** The label for IP Cluster cannot be null

**Action:** Pass a non null label for IP Cluster

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-30022: IP Cluster with label {0} already exists**

**Cause:** IP Cluster with label {0} already exists

**Action:** Provide a different label for IP Cluster

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-30023: Invalid IP Address Range. From IP Address cannot be greater than To IP Address**

**Cause:** Invalid IP Address Range. From IP Address cannot be greater than To IP Address

**Action:** Provide a From IP Address that is lesser than To IP Address

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-30024: The IP Address {0} is invalid**

**Cause:** The IP Address {0} is invalid

**Action:** Provide a valid IP Address

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-30025: The list of cluster Ids cannot be null**

**Cause:** The list of clusterIds cannot be null

---

**Action:** Provide a non null list of clusterIds

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-30026: The IP Cluster with clusterId {0} does not exist**

**Cause:** The IP Cluster with clusterId {0} does not exist

**Action:** Provide a valid clusterId

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-30027: The IP Cluster with clusterId {0} is being used by one or more groups and cannot be deleted**

**Cause:** The IP Cluster with clusterId {0} is being used by one or more groups and cannot be deleted

**Action:** Remove the IP Cluster from the groups and then try to delete it

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-30028: Duplicate element {0} cannot be added to group {1}.**

**Cause:** Element is already present in the group. Duplicate elements cannot be added to group.

**Action:** Duplicate elements are not permitted. Please add a different element to the group.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-35001: {0} is a duplicate of enum {1}. Please enter another {2}.**

**Cause:** Enum already exists in the database. Duplicate enums cannot be added

**Action:** Enter an unique enum and retry this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-35002: Default Property cannot be deleted.**

**Cause:** Default Property cannot be deleted.

**Action:** Select other property and retry this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-40001: Import failed error : {0}**

---

**Cause:** Import failed error : {0}  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Process

**OAAM-40002: Invalid profile type : {0}**  
**Cause:** Invalid profile type : {0}  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Process

**OAAM-40003: Invalid policy type : {0}**  
**Cause:** Invalid policy type : {0}  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Process

**OAAM-40004: No policy data for policy : {0}**  
**Cause:** No policy data for policy : {0}  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Process

**OAAM-40005: Policy already exists in the database with name {0}.**  
**Cause:** Policy already exists in the database with name {0}.  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Process

**OAAM-40006: Import failed, No Group : {0}. ruleInstance : {1}**  
**Cause:** Import failed No Group : {0}. ruleInstance : {1}  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Process

**OAAM-40007: Import failed, unable to set Override action : {0}**  
**Cause:** Import failed unable to set Override action : {0}  
**Action:**

---

**Level:** 1  
**Type:** ERROR  
**Impact:** Process  
**OAAM-40008: Import failed, unable to set override alert : {0}**  
**Cause:** Import failed unable to set Override alert : {0}  
**Action:**

**Level:** 1  
**Type:** ERROR  
**Impact:** Process  
**OAAM-40009: Bad Rule Data, Policy : {0}, ruleGlobalId : {1}**  
**Cause:** Bad Rule Data, Policy : {0}, ruleGlobalId : {1}  
**Action:**

**Level:** 1  
**Type:** ERROR  
**Impact:** Process  
**OAAM-40010: Policy : {0}, ruleGlobalId : {1} Not present**  
**Cause:** Policy : {0}, ruleGlobalId : {1} Not present  
**Action:**

**Level:** 1  
**Type:** ERROR  
**Impact:** Process  
**OAAM-40011: Import failed, unable to set AlertGroup : {0} ruleInstance : {1}**  
**Cause:** Import failed, unable to set AlertGroup : {0} ruleInstance : {1}  
**Action:**

**Level:** 1  
**Type:** ERROR  
**Impact:** Process  
**OAAM-40012: Import failed, unable to set ActionGroup : {0} ruleInstance : {1}**  
**Cause:** Import failed, unable to set ActionGroup : {0} ruleInstance : {1}  
**Action:**

**Level:** 1  
**Type:** ERROR  
**Impact:** Process  
**OAAM-40013: Import failed, unable to set ExcludeGroup : {0} ruleInstance : {1}**  
**Cause:** Import failed, unable to set ExcludeGroup : {0} ruleInstance : {1}  
**Action:**

**Level:** 1  
**Type:** ERROR



---

**Impact:** Process

**OAAM-40014: Question category not found**  
**Cause:** Question category not found  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Process

**OAAM-40015: Validation not found**  
**Cause:** Validation not found  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Process

**OAAM-40016: Question locale not found**  
**Cause:** Question locale not found  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Process

**OAAM-40017: Question with questionId {0} not found**  
**Cause:** Question with questionId {0} not found  
**Action:** Provide a valid questionId  
**Level:** 1  
**Type:** ERROR  
**Impact:** Process

**OAAM-40018: Configurable action with actionId {0} not found**  
**Cause:** Configurable action with actionId {0} not found  
**Action:** Provide a valid actionId  
**Level:** 1  
**Type:** ERROR  
**Impact:** Process

**OAAM-40019: Transaction with transactionId {0} not found**  
**Cause:** Transaction with transactionId {0} not found  
**Action:** Provide a valid transactionId  
**Level:** 1  
**Type:** ERROR  
**Impact:** Process

**OAAM-40020: Pattern with patternId {0} not found**

---

**Cause:** Pattern with patternId {0} not found  
**Action:** Provide a valid patternId  
**Level:** 1  
**Type:** ERROR  
**Impact:** Process

**OAAM-40021: Entity with entityId {0} not found**  
**Cause:** Entity with entityId {0} not found  
**Action:** Provide a valid entityId  
**Level:** 1  
**Type:** ERROR  
**Impact:** Process

**OAAM-40022: Group with listId {0} not found**  
**Cause:** Group with listId {0} not found  
**Action:** Provide a valid listId  
**Level:** 1  
**Type:** ERROR  
**Impact:** Process

**OAAM-40023: Policy Set with policySetId {0} not found**  
**Cause:** Policy Set with policySetId {0} not found  
**Action:** Provide a valid policySetId  
**Level:** 1  
**Type:** ERROR  
**Impact:** Process

**OAAM-40024: Answer Hint with answerHintId {0} not found**  
**Cause:** Answer Hint with answerHintId {0} not found  
**Action:** Provide a valid answerHintId  
**Level:** 1  
**Type:** ERROR  
**Impact:** Process

**OAAM-40025: Validation with validationId {0} not found**  
**Cause:** Validation with validationId {0} not found  
**Action:** Provide a valid validationId  
**Level:** 1  
**Type:** ERROR  
**Impact:** Process

**OAAM-40026: Task Group with groupId {0} not found**  
**Cause:** Task Group with groupId {0} not found  
**Action:** Provide a valid groupId

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-40027: A Configurable action with the name {0} already exists**

**Cause:** A Configurable action with the name {0} already exists

**Action:** Change the name of the existing configurable action

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50001: Fully qualified transaction key must be a valid string.**

**Cause:** Transaction key supplied to look up the transaction definition is not correct. It should be a non empty string.

**Action:** Please verify that the transaction key provided is correct and is a non-empty string. Please retry this operation with a valid key.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50002: No transaction definition found for the key {0}**

**Cause:** The key provided does not match any transaction definition.

**Action:** Please verify that the transaction key provided is correct and is a non-empty string. Please retry this operation with a valid key.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50003: Transaction def Id is null**

**Cause:** Transaction def Id is null

**Action:** Provide a valid transaction def Id

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50004: Transaction def Id is invalid or non existent**

**Cause:** Transaction def Id is invalid or non existent

**Action:** Provide a valid and existent transaction def Id

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50005: Transaction name is null or invalid**

**Cause:** Transaction name is null or invalid

**Action:** Provide a valid transaction name.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50006: Transaction def cannot be null**

**Cause:** Transaction def cannot be null

**Action:** Provide a valid Transaction def object.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50007: Transaction def Id is null**

**Cause:** Transaction def Id is null

**Action:** Provide a non null transaction def id.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50008: Transaction def Id is invalid or non existent**

**Cause:** Transaction def Id is invalid or non existent

**Action:** Provide a valid and existent transaction def Id

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50009: Transaction def could not be updated.**

**Cause:** Transaction def could not be updated.

**Action:** Transaction def could not be updated, see error log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50010: Transaction def Id list is null or empty**

**Cause:** Transaction def Id list is null or empty

**Action:** Provide a valid transaction def Id list.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50011: Transaction def for the given Transaction Def {0} not found.**

**Cause:** Transaction def for the given Transaction Def {0} not found.

**Action:** Provide a valid transaction def Id

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**OAAM-50012: Transaction input data mapping is missing for Transaction Id, {0}**

**Cause:** Transaction input data mapping is missing for Transaction Id, {0}

**Action:** Transaction input data mapping is required to activate the Transaction, {0}

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50013: Transaction def for the given Transaction Def {0} not found.**

**Cause:** Transaction def for the given Transaction Def {0} not found.

**Action:** Provide a valid Transaction Def Id.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50014: Transaction input data mapping is missing for Transaction Id, {0}**

**Cause:** Transaction input data mapping is missing for Transaction Id, {0}

**Action:** Transaction input data mapping is required to activate the Transaction, {0}

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50015: Source data is missing for Transaction id, {0}**

**Cause:** Source data is missing for Transaction id, {0}

**Action:** Source data is required to activate for Transaction id, {0}

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50016: Transaction data mapping is missing for Transaction Id, {0}.**

**Cause:** Transaction data mapping is missing for Transaction Id, {0}.

**Action:** Transaction data mapping is required to activate for Transaction Id, {0}

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50017: Transaction data mapping is missing for Transaction Id, {0}.**

**Cause:** Transaction data mapping is missing for Transaction Id, {0}.

**Action:** Transaction data mapping is required to activate for Transaction Id, {0}

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50018: Entity Mapping could not be found for Transaction Id, {0}**

---

**Cause:** Entity Mapping could not be found for Transaction Id, {0}  
**Action:** Entity Mapping is required to activate for Transaction Id, {0}

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50019: Transaction and Entity mapping is missing for Transaction Id, {0}**

**Cause:** Transaction and Entity mapping is missing for Transaction Id, {0}.

**Action:** Transaction and Entity Mapping is required to activate for Transaction Id, {0}.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50020: Transaction Entity Def Map Id cannot be null**

**Cause:** Transaction Entity Def Map Id cannot be null.

**Action:** Provide a valid Transaction Entity Def Map Id.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50021: Transaction Def Id missing while creating Transaction Entity Map**

**Cause:** Transaction Def Id missing while creating Transaction Entity Map

**Action:** Provide a valid Transaction Def Id

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50022: Entity Def Id missing while creating Transaction Entity Map**

**Cause:** Entity Def Id missing while creating Transaction Entity Map

**Action:** Provide a valid Entity def Id

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50023: Entity Def validation failed. Operation cannot be performed.**

**Cause:** Entity Def validation failed. Operation cannot be performed.

**Action:** Provide a valid Entity Def

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50024: Entity Name validation failed.**

**Cause:** Entity Name validation failed.

---

**Action:** Provide a valid and unique entity Name.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50025: Invalid Entity relation**

**Cause:** Invalid Entity relation

**Action:** Provide a valid Entity relation

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50026: Invalid Display order.**

**Cause:** Invalid Display order

**Action:** Provide a valid Display order.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50027: Duplicate Entity Name.**

**Cause:** Duplicate Entity Name.

**Action:** Provide a valid and unique Entity Name.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50028: Invalid and non-unique Entity Relation**

**Cause:** Invalid and non-unique Entity Relation

**Action:** Provide a valid and unique Entity Relation.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50029: Invalid and non-unique Display Order**

**Cause:** Invalid and non-unique Display Order

**Action:** Provide a valid and unique Display Order.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50030: Transaction Def Id missing while updating Transaction Entity Map**

**Cause:** Transaction Def Id missing while updating Transaction Entity Map

**Action:** Provide a valid and non null Transaction Def Id

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50031: Entity Def Id missing while updating Transaction Entity Map**

**Cause:** Entity Def Id missing while updating Transaction Entity Map

**Action:** Provide a valid and non null Entity def Id

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50032: Transaction Delete is not allowed.**

**Cause:** Transaction Delete is not allowed.

**Action:** Select a valid Transaction for delete

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50033: Data Element Def cannot be null**

**Cause:** Data Element Def cannot be null

**Action:** Provide a valid Data Element Def.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50034: Data Element Def Array cannot be null or empty.**

**Cause:** Data Element Def Array cannot be null or empty.

**Action:** Provide a non-null and valid Data Element Def Array.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50035: Attribute Validation failed.**

**Cause:** Attribute Validation failed.

**Action:** Provide a valid Attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50036: Creating the Attribute failed.**

**Cause:** Creating the Attribute failed.

**Action:** Provide the valid entry for creating the attribute.

**Level:** 1

**Type:** ERROR



---

**Impact:** Process

**OAAM-50037: Attribute not found.**

**Cause:** Attribute not found.

**Action:** Provide a valid and non-null Attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50038: Cannot find a matching Data Element Def**

**Cause:** Cannot find a matching Data Element Def

**Action:** Provide a valid entry having a matching Data Element Def.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50039: No Attribute found to delete.**

**Cause:** No Attribute found to delete.

**Action:** Provide a valid attribute for delete.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50040: Source Validation failed.**

**Cause:** Source Validation failed.

**Action:** Provide a valid source data.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50041: Cannot find a matching Transaction data mapping**

**Cause:** Cannot find a matching Transaction data mapping Id

**Action:** Provide a valid and matching Transaction data mapping Id.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50042: Transaction Data Mapping is null or empty.**

**Cause:** Transaction Data Mapping Ids is null or empty.

**Action:** Provide a non null or valid Transaction Data Mapping Id

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50043: No Transaction Mapping found to delete.**

---

**Cause:** No Transaction Mapping found to delete.

**Action:** Transaction should have one or more mapping to delete.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50044: No Entity mapping found to delete.**

**Cause:** No Entity mapping found to delete.

**Action:** Entity should have one or more mapping to delete.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50045: Transaction name is null or empty.**

**Cause:** Transaction name is null or empty.

**Action:** Provide a valid and non-null Transaction name

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50046: Transaction key is null or empty.**

**Cause:** Transaction key is null or empty.

**Action:** Provide a valid and non-null Transaction key

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50047: Transaction description is null or empty.**

**Cause:** Transaction description is null or empty.

**Action:** Provide a valid and non-null Transaction description

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50048: Duplicate Transaction, validation failed.**

**Cause:** Validation failed because of duplicate Transaction

**Action:** Provide a valid and unique Transaction.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50049: Transaction Entity Map for the Id, {0} does not exist.**

**Cause:** Transaction Entity Map for the Id, {0} does not exist.

**Action:** Provide a valid Transaction Entity Map Id.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50050: Transaction Entity Map Id cannot be null**

**Cause:** Transaction Entity Map Id cannot be null

**Action:** Provide a valid and non null Transaction Entity Map Id.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50102: Display/Name scheme is not set for entity {0}**

**Cause:** Display/Name scheme is not set for entity {0}

**Action:** Please set the Display/Name scheme before activating

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50103: ID scheme is not set for entity {0}**

**Cause:** ID scheme is not set for entity {0}

**Action:** Please set the ID scheme before activating

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50104: No Data Element Definitions exist for entity {0}**

**Cause:** No Data Element Definitions exist for entity {0}

**Action:** Add Data Element Definitions before activating

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50105: Row and Column values are not unique/valid for Data Element : [{0}] for entity {1}**

**Cause:** Row and Column values are not unique/valid for Data Element : [{0}] for entity {1}

**Action:** Please provide unique row and column values for data elements within an entity

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50106: There is more than one DataElement with same Internal Id: [{0}] for entity{1}**

---

**Cause:** There is more than one DataElement with same Internal Id: [{0}] for entity{1}

**Action:** Please provide unique internal Ids for data element definitions within an entity

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50107: Index for Numeric Data Elements is not between [{0}] and [{1}] for entity {2}**

**Cause:** Index for Numeric Data Elements is not between [{0}] and [{1}] for entity {2}

**Action:** Ensure that index for Numeric Data Elements is between [{0}] and [{1}] for entity{2}

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50108: Index for Non-Numeric Data Elements is not between [{0}] and [{1}] for entity {2}**

**Cause:** Index for Non-Numeric Data Elements is not between [{0}] and [{1}] for entity {2}

**Action:** Ensure that index for Non-Numeric Data Elements is between [{0}] and [{1}] for entity{2}

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50109: No Display Scheme elements are available for entity {0}**

**Cause:** No Display Scheme elements have been added for entity {0}

**Action:** Add Display Scheme elements before activating

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50110: There is more than one Display data Element with same Internal Id: [{0}] for entity {1}**

**Cause:** There is more than one Display data Element with same Internal Id: [{0}] for entity {1}

**Action:** Entity should not have more than one Display data Element with same Internal Id

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**OAAM-50111: There is more than one Display data Element with same order: [{0}] for entity {1}**

**Cause:** There is more than one Display data Element with same order: [{0}] for entity {1}

**Action:** Please correct the ordering for Display data Elements for entity {1}

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50112: No ID Scheme elements are available for entity {0}**

**Cause:** No ID Scheme elements have been added for entity {0}

**Action:** Add ID Scheme elements before activating

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50113: There is more than one ID Scheme Data Element with same Internal Id: [{0}] for entity {1}**

**Cause:** There is more than one ID Scheme Data Element with same Internal Id: [{0}] for entity {1}

**Action:** Entity should not have more than one ID Scheme data Element with same Internal Id

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50114: There is more than one ID Scheme data Element with same order: [{0}] for entity {1}**

**Cause:** There is more than one ID Scheme data Element with same order: [{0}] for entity {1}

**Action:** Entity should not have more than one ID Scheme data Element with the same order

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50115: Database Error**

**Cause:** Database Error

**Action:** Database Error

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50116: Entity Name cannot be blank**

**Cause:** Entity Name cannot be blank

**Action:** Please provide an Entity Name

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50117: Entity Key cannot be blank**

**Cause:** Entity Key cannot be blank

**Action:** Please provide an Entity Key

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50118: Entity Description cannot be blank**

**Cause:** Entity Description cannot be blank

**Action:** Please provide an Entity Description

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50119: Another Entity Definition with the same name already exists**

**Cause:** Another Entity Definition with the same name already exists

**Action:** Please provide an unique name for Entity Definition

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50120: Internal Id of Data Elements cannot be blank**

**Cause:** Internal Id of Data Elements cannot be blank

**Action:** Please provide an Internal Id for Data Elements

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50121: Data Type of Data Elements cannot be blank**

**Cause:** Data Type of Data Elements cannot be blank

**Action:** Please provide Data Type for Data Elements

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50122: Row number of Data Elements cannot be less than zero**

**Cause:** Row number of Data Elements cannot be less than zero

**Action:** Please provide a positive integer as Row number for Data Elements

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**OAAM-50123: Column number of Data Elements cannot be less than zero**

**Cause:** Column number of Data Elements cannot be less than zero

**Action:** Please provide a positive integer as Column number for Data Elements

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50124: Internal Id of Data Element should be unique**

**Cause:** Internal Id of Data Element should be unique

**Action:** Please ensure that Internal Id of Data Element is unique

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50125: Name of Data Element should be unique**

**Cause:** Name of Data Element should be unique

**Action:** Please ensure that Name of Data Element is unique

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50126: There is more than one Data Element Definition having same row and column**

**Cause:** There is more than one Data Element Definition having same row and column

**Action:** Please ensure that row and column is unique for Data Element Definitions

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50127: Validation Error: Data Element Definition Id should not be set for creating a new Data Element Definition**

**Cause:** Validation Error: DataElemDefId should not be set for creating a new DataElement Def

**Action:** Validation Error: DataElemDefId should not be set for creating a new DataElement Def

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50128: Column for Numeric Data Elements should be between [{0}] and [{1}]**

**Cause:** Column for Numeric Data Elements should be between [{0}] and [{1}]

**Action:** Column for Numeric Data Elements should be between [{0}] and [{1}]

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50129: Column for Non-Numeric Data Elements should be between [1] and [{0}]**

**Cause:** Column for Non-Numeric Data Elements should be between [1] and [{0}]

**Action:** Column for Non-Numeric Data Elements should be between [1] and [{0}]

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50130: The entity {0} cannot be disabled as it is used by one or more active Transactions**

**Cause:** The entity {0} cannot be disabled as it is used by one or more active Transactions

**Action:** The entity {0} cannot be disabled as it is used by one or more active Transactions

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50131: The entity with entityId {0} cannot be deleted as it is used by one or more active Transactions**

**Cause:** The entity with entityId {0} cannot be deleted as it is used by one or more active Transactions

**Action:** The entity with entityId {0} cannot be deleted as it is used by one or more active Transactions

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50132: EntityDefId cannot be null**

**Cause:** EntityDefId cannot be null

**Action:** EntityDefId cannot be null

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50133: Data Profile Definition not found for the Entity Definition Id**

**Cause:** Data Profile Definition not found for the Entity Definition Id

**Action:** Data Profile Definition not found for the Entity Definition Id

**Level:** 1

**Type:** ERROR

**Impact:** Process



---

**OAAM-50134: Data Definition Id does not match with Data Definition Id of the Data Profile.**

**Cause:** Data Definition Id does not match with Data Definition Id of the Data Profile.

**Action:** Data Definition Id does not match with Data Definition Id of the Data Profile.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50135: Unable to create External Id Data Definition for the Entity Definition Id**

**Cause:** Unable to create External Id Data Definition for the Entity Definition Id

**Action:** Unable to create External Id Data Definition for the Entity Definition Id

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50136: The element having elementId {0} cannot be deleted as it is used by one or more active Transactions**

**Cause:** The element having elementId {0} cannot be deleted as it is used by one or more active Transactions

**Action:** The element having elementId {0} cannot be deleted as it is used by one or more active Transactions

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50137: Data Element having dataDefElementId {0} does not exist**

**Cause:** Data Element having dataDefElementId {0} does not exist

**Action:** Data Element having dataDefElementId {0} does not exist

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50138: Identification Scheme cannot be NULL**

**Cause:** Identification Scheme cannot be NULL

**Action:** Identification Scheme cannot be NULL

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50139: Data Definition Element Id cannot be null**

**Cause:** DataDefElementId cannot be null

**Action:** DataDefElementId cannot be null

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50140: System Error while loading entities**

**Cause:** System Error while loading entities

**Action:** System Error while loading entities

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50141: Error loading object {0} with primary key {1} from database. {2}**

**Cause:** Error loading object {0} with primary key {1} from database. {2}

**Action:** Error loading object {0} with primary key {1} from database. {2}s

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-50142: Error inserting object {0} to database. {1}**

**Cause:** Error inserting object {0} to database. {1}

**Action:** Error inserting object {0} to database. {1}

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-60001: PatternId cannot be null**

**Cause:** PatternId cannot be null

**Action:** PatternId cannot be null

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-60002: Pattern with name {0} already exists**

**Cause:** Pattern with name {0} already exists

**Action:** Pattern with name {0} already exists

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-60003: Comparision value is required**

**Cause:** Comparision value is required

**Action:** Comparision value is required

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**OAAM-60004: The value {0} is invalid**

**Cause:** The value {0} is invalid

**Action:** The value {0} is invalid

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-60005: The value {0} is not a valid Integer value**

**Cause:** The value {0} is not a valid Integer value

**Action:** The value {0} is not a valid Integer value

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-60006: The value {0} is not a valid Long value**

**Cause:** The value {0} is not a valid Long value

**Action:** The value {0} is not a valid Long value

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-60007: The value {0} is not a valid Boolean value**

**Cause:** The value {0} is not a valid Boolean value

**Action:** The value {0} is not a valid Boolean value

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-60008: The value {0} is not a valid Float value**

**Cause:** The value {0} is not a valid Float value

**Action:** The value {0} is not a valid Float value

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-60009: The value {0} is not a valid Date value**

**Cause:** The value {0} is not a valid Date value

**Action:** The value {0} is not a valid Date value

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-60010: The value {0} is not a valid Double value**

---

**Cause:** The value {0} is not a valid Double value

**Action:** The value {0} is not a valid Double value

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-60011: Entered Values overlaps with {0}-{1} range**

**Cause:** Entered Values overlaps with {0}-{1} range

**Action:** Entered Values overlaps with {0}-{1} range

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-60012: The attribute already exists**

**Cause:** The attribute already exists

**Action:** The attribute already exists

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-60013: Pattern parameter with paramId {0} does not exist**

**Cause:** Pattern parameter with paramId {0} does not exist

**Action:** Pattern parameter with paramId {0} does not exist

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-60014: ParamId cannot be null**

**Cause:** ParamId cannot be null

**Action:** ParamId cannot be null

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-70001: Kba Question, {0} cannot be deleted as it is linked to the user.**

**Cause:** Kba Question, {0} cannot be deleted as it is linked to the user.

**Action:** Either unlink the user to this question or delete some other question.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-70002: Selected question id cannot be updated to the given status**

**Cause:** Selected question id cannot be updated to the given status

---

**Action:** Selected question id cannot be updated to the given status, select different.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-70003: IDs in the list cannot be null or empty**

**Cause:** IDs in the list cannot be null or empty

**Action:** Provide a valid Id list.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-70004: Invalid status**

**Cause:** Invalid status

**Action:** Provide a valid status, ACTIVE, DISABLED

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-70005: Invalid and non existent question Id**

**Cause:** Invalid and non existent question Id

**Action:** Provide a valid and existent question Id.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-70006: Question id should not be null**

**Cause:** Question id should not be null

**Action:** Provide a valid question Id.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-70007: Name,{0} already exists.**

**Cause:** Name already exists.

**Action:** Provide an unique name

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-70008: Kba Category cannot be deleted as users are registered to questions from this category.**

**Cause:** Kba Category cannot be deleted as users are registered to questions from this category.

---

**Action:** Kba Category cannot be deleted as users are registered to questions from this category.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-70009: Invalid category.**

**Cause:** Invalid category Id.

**Action:** Provide a valid category Id.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-70010: Category cannot be null**

**Cause:** Category cannot be null

**Action:** Provide a valid and non null Category

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-70011: Name cannot be empty or null**

**Cause:** Name cannot be empty or null

**Action:** Provide a valid and non null name

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-70012: Invalid or empty category name**

**Cause:** Invalid or empty category name

**Action:** Provide a valid and non null category name

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-70013: Invalid or empty validation name**

**Cause:** Invalid or empty validation name

**Action:** Provide a valid and non null validation name

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-70014: Validation cannot be null**

**Cause:** Validation cannot be null

**Action:** Provide a valid and non null Validation

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-70015: Invalid validation Id**

**Cause:** Invalid validation Id

**Action:** Provide a valid validation Id.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-70016: Validations, {0} are used in the kba configurations and cannot be deleted.**

**Cause:** Validations are found linked and cannot be deleted

**Action:** Select only the unlinked validations for deleting.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-70017: Validation Id, {0} is invalid and cannot be deleted**

**Cause:** Validation Id is invalid and cannot be deleted

**Action:** Provide a valid and existent validation Id.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-70018: Validation Id, {0} has been already added as Global Validation**

**Cause:** Validation Id will not be added again as Global Validation.

**Action:** WARNING: Select a new validation Id which is not part of the Global Validation List.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-70019: Validation Id is not in the Global Validation List**

**Cause:** Validation Id is not found in the Global Validation List

**Action:** Select a validation Id which is part of the Global Validation List.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-70020: No validation available in Global Validation List for delete**

**Cause:** No validation available in Global Validation List for delete

**Action:** No validation available in Global Validation List for delete.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-70021: Config value, {0} is not a positive number**

**Cause:** Config value should be a positive number.

**Action:** Provide a positive number for the Config Value.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-70022: Config Value, {0} cannot exceed the category count**

**Cause:** Config Value cannot exceed the category count

**Action:** Provide the config value within the allowed category count.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-70023: No validation available in Global Validation List for delete**

**Cause:** No validation available in Global Validation List for delete

**Action:** No validation available in Global Validation List for delete.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-70024: Insufficient questions in the system for configuring {0} questions for each user with {1} questions per menu.**

**Cause:** There are not enough questions in the system for each user to register for number of questions per menu.

**Action:** Import/create more questions so that number of questions that user needs to register times questions per menu is less than total number of questions available.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OAAM-70025: Too few number of questions are being configured for users. Please try to register at least {0} questions for user.**

**Cause:** You have tried to set the number questions too low. This can lead to security vulnerability.

**Action:** For best mix of security and usability please register at least 3 and at most 5 or so questions. These settings are dependent on your particular system implementation.

**Level:** 1

**Type:** ERROR



---

**Impact:** Process

**OAAM-70026: Too many number of questions are being configured for users. Please try to register at most {0} questions for user.**

**Cause:** You have tried to set the number questions too high. This can lead to usability issues.

**Action:** For best mix of security and usability please register at least 3 and at most 5 or so questions. These settings are dependent on your particular system implementation.

**Level:** 1

**Type:** ERROR

**Impact:** Process



---

## OAM-00001 to OAM-24001

**OAM-00001: Cannot parse the session token.**

**Cause:** The session token appears to be invalid.

**Action:** For more details, start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-00002: Error occurred while handling the request.**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-00003: Request-Response handler configuration is incomplete.**

**Cause:** A request handler mapping was missing.

**Action:** Add the missing handler mapping to the configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-00004: Cannot initialize the Diagnostic Engine.**

**Cause:**

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-00005: Cannot locate the custom login page.**

**Cause:** The custom login page was not found.

**Action:** Verify the configuration.

**Level:** 15

---

**Type:** ERROR

**Impact:** Other

**OAM-00006: Cannot locate the configuration of the custom login page.**

**Cause:** The custom custom login page was not specified in the configuration.

**Action:** Add the custom login page location to the configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-00007: Cannot edit the custom login page**

**Cause:** The file permissions of the custom login page do not allow write access.

**Action:** Change the file permissions to allow write access.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-00008: Cannot close the custom login page**

**Cause:** The source code of the custom login page does not support closing of the login page.

**Action:** Check the custom login page source code.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-02001: Retrieve SSO session operation failed.**

**Cause:** Cannot retrieve the SSO session from the request context. Session might have expired.

**Action:** For more details, start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-02002: Error while processing the submitted credentials.**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-02003: Error while processing credential collection.**

**Cause:** An internal error occurred.

**Action:** Check the authentication scheme configuration.

**Level:** 15

---

**Type:** ERROR

**Impact:** Other

**OAM-02004: Error while processing authorization request.**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-02005: Error while parsing the SSO session token.**

**Cause:** Error while parsing the SSO session token. Wrong session token format.

**Action:** Retry. If the error persists verify the key roll-over configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-02006: Insufficient authentication level to access the resource.**

**Cause:** An insufficient authentication level was used to access the resource.

**Action:** Step up the authentication level by re-authenticating to the required level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-02007: Insufficient privileges. Authorization Denied.**

**Cause:** Insufficient privileges.

**Action:** Check the authorization permissions.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-02052: SME Adapter initialization Failed.**

**Cause:** SME adapter initialization failed.

**Action:** Verify the SME configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-02053: Component {1} initialization Failed.**

**Cause:** Component initialization failed.

**Action:** Verify the server configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

---

**OAM-02054: SSO session creation failed.**

**Cause:** Session Management Engine error.

**Action:** Check Session Management Engine error logs.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-02055: Retrieve SSO session operation failed.**

**Cause:** Session might be expired.

**Action:** If the problem persists contact the administrator.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-02056: An error occurred while parsing the server token.**

**Cause:** TPE token parsing failed.

**Action:** check Token Processing Engine logs.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-02057: Wrong Flow Controller configuration for {1}**

**Cause:** Wrong Flow controller configuration

**Action:** Check flow controller class name and configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-02058: Event Flow goes in infinite loop.**

**Cause:** Wrong configuration or too many allowed login attempts.

**Action:** Check event flow configuration and login attempt configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-02059: Flow Controller Cannot handle Event**

**Cause:** Wrong Flow controller configuration

**Action:** Check error log more details.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-02060: Flow Controller :{0} Cannot handle Event :{1}**

**Cause:** Wrong Flow controller configuration

---

**Action:** Check event to flow controller mapping.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-02061: Event Handler error.**

**Cause:** Wrong event handler configuration

**Action:** Check error log more details.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-02062: Event Handler cannot handle the event.**

**Cause:** Wrong event handler configuration

**Action:** Check event to event handler controller mapping.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-02063: Event Handler :{0} Cannot handle Event :{1}**

**Cause:** Wrong event handler configuration

**Action:** Check event to event handler controller mapping.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-02064: Authentication Error during policy matching.**

**Cause:** Authentication Error

**Action:** Check error log more details.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-02065: Configuration Service Adapter initialization Failed.**

**Cause:** SConfiguration Service failed.

**Action:** Verify the system configuration file

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-02066: Event Factory is not configured create the requested event.**

**Cause:** Wrong event factory configuration

**Action:** Check error log more details.

---

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-02067: Wrong event configuration. No event handler specified for event {0}.**

**Cause:** Wrong event factory configuration

**Action:** Check error log more details.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-02068: Error occurred while configuring the request cache.**

**Cause:** Wrong request cache handler class configuration.

**Action:** Check error log more details.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-02069: Error occurred while loading cache handler for class Name {0}**

**Cause:** Wrong request cache handler class configuration.

**Action:** Check error log more details.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-02070: An error occurred while loading server aliases.**

**Cause:** TPE token parsing failed.

**Action:** check system configuration if the aliases are set up properly logs.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-02071: No host configuration found for the alias {0}.**

**Cause:** TPE token parsing failed.

**Action:** check system configuration if the aliases are set up properly logs.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-02072: Ignoring failure during Identity Store operation.**

**Cause:** Operation to read or update user attribute in Identity Store resulted in exception.

**Action:** Check the availability of configured Identity Store.

**Level:** 15



---

**Type:** WARNING

**Impact:** Other

**OAM-02073: Error while checking if the resource is protected or not.**

**Cause:** TPE token parsing failed.

**Action:** check system configuration if the aliases are set up properly logs.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-02074: Error while checking if the resource {0} is protected or not.**

**Cause:** TPE token parsing failed.

**Action:** check system configuration if the aliases are set up properly logs.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-02075: Component {0} initialized successfully.**

**Cause:** None

**Action:** None

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-02076: {0} Engine initialized successfully.**

**Cause:** None

**Action:** None

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-02077: SSO Engine initialized Successfully.**

**Cause:** None

**Action:** None

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-02078: Processing Event {0}**

**Cause:** None

**Action:** None

**Level:** 15

**Type:** INFO

**Impact:** Other

---

**OAM-02079: SSO session created with session ID {0} for request ({1})**

**Cause:** None

**Action:** None

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-02080: Cache data sync:{0} for request {1};**

**Cause:** None

**Action:** None

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-02081: Created {0} : {1}**

**Cause:** None

**Action:** None

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-02082: Diagnostic Engine Registration failed for Controller Collector.**

**Cause:** Diagnostic Engine Registration failed.

**Action:** None

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-02083: Diagnostic Engine Registration failed for Credential Collector Controller.**

**Cause:** Diagnostic Engine Registration failed.

**Action:** None

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-02084: Credential collection process success.**

**Cause:**

**Action:** None

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-02085: Successfully validated the submitted credentials.**

---

**Cause:**  
**Action:** None  
**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-02086: {0}: processing Event:{1}.**  
**Cause:**  
**Action:** None  
**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-02087: Policy ID : {0}**  
**Cause:**  
**Action:** None  
**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-02088: Scheme result : {0}**  
**Cause:**  
**Action:** None  
**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-02089: Is Resource Protected status : {0}**  
**Cause:**  
**Action:** None  
**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-02090: Status : {0}**  
**Cause:**  
**Action:** None  
**Level:** 15  
**Type:** ERROR  
**Impact:** Other

**OAM-02091: Challenge URL : {0}**  
**Cause:**  
**Action:** None

---

**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-02092: Session Updation Failed**  
**Cause:**  
**Action:** None

**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-02093: Session response name {0} is reserved for OAM Server. Value for this response will not be updated in session.**  
**Cause:** A session response is configured with name that is internally reserved for OAM Server  
**Action:** Please change the name of the session response not to conflict with OAM Server reserved names

**Level:** 15  
**Type:** WARNING  
**Impact:** Other

**OAM-04001: Configuration parameter type mismatch. Param {0}. Expected type {1}. Actual type {2}**  
**Cause:** The configuration parameter type was invalid.  
**Action:** Validate the configuration parameter.

**Level:** 16  
**Type:** NOTIFICATION  
**Impact:** Other

**OAM-04002: Unsupported value for config parameter. Parameter {0} . Value {1}. {2}**  
**Cause:** The specified configuration parameter was not valid.  
**Action:** Validate the configuration parameter.

**Level:** 16  
**Type:** NOTIFICATION  
**Impact:** Other

**OAM-04003: OAM proxy started. Listening on port {0}.**  
**Cause:** The OAM proxy has started listening on the specified port.  
**Action:**

**Level:** 16  
**Type:** NOTIFICATION  
**Impact:** Other

**OAM-04004: Read configuration parameter {0} = {1}.**  
**Cause:** The OAM proxy has loaded its configuration.

---

**Action:**

**Level:** 16

**Type:** NOTIFICATION

**Impact:** Other

**OAM-04005: Client connection accepted.**

**Cause:** A client TCP/IP connection was accepted.

**Action:**

**Level:** 16

**Type:** NOTIFICATION

**Impact:** Other

**OAM-04006: Client connection closed. Connection id {0}.**

**Cause:** A client TCP/IP connection was closed.

**Action:**

**Level:** 16

**Type:** NOTIFICATION

**Impact:** Other

**OAM-04007: Message received from client. Message {0}, Host : {1} Port : {2}.**

**Cause:** A message was received from a client on the NAP channel.

**Action:**

**Level:** 16

**Type:** NOTIFICATION

**Impact:** Other

**OAM-04008: Message sent to client. Message {0}, Host : {1} Port : {2}.**

**Cause:** A message was sent to a client on the NAP channel.

**Action:**

**Level:** 16

**Type:** NOTIFICATION

**Impact:** Other

**OAM-04009: New Outbound connection created with OAM Access Server.**

**Cause:** An outbound connection was created with an OAM 10g server.

**Action:**

**Level:** 16

**Type:** NOTIFICATION

**Impact:** Other

**OAM-04010: Message received on outbound channel from OAM Access server.**

**Message {0}, Host : {1} Port : {2}.**

**Cause:** A message was received from an OAM 10g server.

**Action:**

---

**Level:** 16

**Type:** NOTIFICATION

**Impact:** Other

**OAM-04011: Message sent on outbound channel to OAM 10g Access server.**

**Message {0}, Host : {1} Port : {2}.**

**Cause:** A message was sent to an OAM 10g server.

**Action:**

**Level:** 16

**Type:** NOTIFICATION

**Impact:** Other

**OAM-04012: Outbound connection closed.**

**Cause:** A connection with an OAM 10g server was closed.

**Action:**

**Level:** 16

**Type:** NOTIFICATION

**Impact:** Other

**OAM-04013: Unexpected message received from client. Message {0}**

**Cause:** An unexpected message was received when a simple mode handshake message from the client was expected.

**Action:** Check the NAP mode configuration of the WebGate and the Server.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**OAM-04014: Malformed message received from client. Details {0}**

**Cause:** The length of message received from client was less than 0.

**Action:** Restart the WebGate if the message is being received repeatedly.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**OAM-04015: Outbound connection to Access Server not found.**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**OAM-04016: Session ID is missing in AmResponse**

**Cause:** The session ID was not present in the OAM token.

**Action:** Retry the request.

---

**Level:** 1

**Type:** WARNING

**Impact:** Other

**OAM-04017: OAM proxy end point activation failed. Exception {0}**

**Cause:** The specified listening port is not available, or is already being used.

**Action:** Restart the server or contact the system administrator.

**Level:** 1

**Type:** SEVERE

**Impact:** Other

**OAM-04018: Required configuration parameter missing. Required {0}**

**Cause:** The required configuration parameters were missing.

**Action:** Verify the configuration.

**Level:** 1

**Type:** SEVERE

**Impact:** Other

**OAM-04019: Work manager JNDI lookup failed. Exception {0}**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 1

**Type:** SEVERE

**Impact:** Other

**OAM-04020: Exception encountered while processing the request message.**

**Exception {0}**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 1

**Type:** SEVERE

**Impact:** Other

**OAM-04021: NMP initialization failed.**

**Cause:** The NAP handshake with the client failed or an unsupported application was trying to connect to the OAM proxy.

**Action:** Verify the client version.

**Level:** 1

**Type:** SEVERE

**Impact:** Other

**OAM-04022: SSL configuration is not specified for SIMPLE or CERT mode**

**Cause:** The SSL configuration was required but not supplied for the SIMPLE or CERT mode.

**Action:** Verify the SSL Configuration and rerun the operation.

---

**Level:** 1

**Type:** SEVERE

**Impact:** Other

**OAM-04023: SSL handshake failed. Exception {0}**

**Cause:** The NAP handshake with a client was not successful.

**Action:** Check the client configuration.

**Level:** 1

**Type:** SEVERE

**Impact:** Other

**OAM-04024: Exception in outbound message processing. Cause {0} . Message details {1}**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 1

**Type:** SEVERE

**Impact:** Other

**OAM-04025: Error in connecting to Access server. {0}**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 1

**Type:** SEVERE

**Impact:** Other

**OAM-04026: Error in NAP handshake with AAA server {0}**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 1

**Type:** SEVERE

**Impact:** Other

**OAM-04027: Cannot create Executor instance**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 1

**Type:** SEVERE

**Impact:** Other

**OAM-04028: Outbound Resource Adapter initialization error. {0}**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 1



---

**Type:** SEVERE

**Impact:** Other

**OAM-04029: Error in generating AMEvent. Details {0}**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 1

**Type:** SEVERE

**Impact:** Other

**OAM-04030: Partner loopup failed. Partner id {0}**

**Cause:** The retrieval of partner metadata during client authentication was not successful.

**Action:** Check if the partner is registered with the Access Server.

**Level:** 1

**Type:** SEVERE

**Impact:** Other

**OAM-04031: NAP version mismatch during the NAP handshake. Client Message {0}**

**Cause:** An unsupported NAP version was sent by the client.

**Action:** Check the client configuration and version. Older clients may need to be upgraded.

**Level:** 1

**Type:** SEVERE

**Impact:** Other

**OAM-04032: PAT API error. Details {0}**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 1

**Type:** SEVERE

**Impact:** Other

**OAM-04033: Error in retrieving secret information. {0} {1}**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 1

**Type:** SEVERE

**Impact:** Other

**OAM-04035: Error while reading token cache size from configuration.**

**Cause:** The cache configuration was invalid.

**Action:** Fix cache configuration and rerun the operation.

**Level:** 15

---

**Type:** ERROR

**Impact:** Other

**OAM-04036: Channel security mode is different as specified in configuration {0}**

**Cause:** The agent tried to communicate in a mode different from its configuration.

**Action:** Check the agent mode. This may be a security issue if the configuration mode of agent is correct.

**Level:** 1

**Type:** SEVERE

**Impact:** Other

**OAM-06001: Cannot parse the session token.**

**Cause:** The session token is invalid or the wrong decryption key is present in the configuration.

**Action:** Verify the key roll-over configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-10001: Cannot load the configuration file.**

**Cause:** The configuration file location was invalid.

**Action:** Verify the location of the configuration file.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-10002: Cannot initialize the PAT Adapter.**

**Cause:** The PAT configuration was invalid.

**Action:** Verify the PAT configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-10003: Cannot initialize the Cache Handlers.**

**Cause:** The request cache handler configuration was invalid.

**Action:** Verify the request cache handler configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-10004: Cannot initialize the Controller.**

**Cause:** The configuration for Controller events was invalid.

**Action:** Verify the Controller configuration.

**Level:** 15

---

**Type:** ERROR

**Impact:** Other

**OAM-10005: Cannot initialize the Controller.**

**Cause:** The configuration for the Flow controllerd was invalid.

**Action:** Verify the Controller configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-10006: Cannot initialize the Controller.**

**Cause:** The configuration for the Flow Mapping was invalid.

**Action:** Verify the Controller configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-10007: Cannot initialize the Controller.**

**Cause:** The configuration for the Event Handlers was invalid.

**Action:** Verify the Controller configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-10008: Cannot initialize the Controller.**

**Cause:** The configuration for the Event UI was invalid.

**Action:** Verify the Controller configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-10009: Cannot initialize the Controller.**

**Cause:** The Event Handler configuration was invalid.

**Action:** Verify the Controller configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-10010: Cannot initialize the Controller.**

**Cause:** The Event Factory configuration was invalid.

**Action:** Verify the Controller configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

---

**OAM-10011: An invalid Cookie Domain**

**Cause:** The cookie domain was invalid.

**Action:** Verify the configuration file.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-10012: Cannot load audit configuration.**

**Cause:** The audit configuration was invalid.

**Action:** Verify the audit configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-10013: Cannot load audit configuration.**

**Cause:** Mismatch between logger and resource configuration.

**Action:** Verify the audit configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-10014: Invalid done URL specified during logout - {0}.**

**Cause:** Done URL specified during logout is not in proper URL format.

**Action:** Verify the done URL.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-10017: Cannot initialize the server key.**

**Cause:** Unable to retrieve server key from configuration.

**Action:** Verify the configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-12001: Cannot load audit configuration.**

**Cause:** The specified configuration file does not exist, or the audit configuration is invalid.

**Action:** Check the server error logs.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-12002: User name value specified for special user is invalid.**

---

**Cause:** The input value format is invalid, or exceeds 30 characters.

**Action:** Correct the input value.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-12003: Maximum directory size specified is invalid.**

**Cause:** The input value format is invalid, is less than 1 or exceeds 1024.

**Action:** Correct the input value.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-12004: Maximum file size specified is invalid.**

**Cause:** The input value format is invalid, is less than 1 or exceeds 1024.

**Action:** Correct the input value.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-12005: Map of audit events is invalid.**

**Cause:** The audit event configuration is missing, or invalid.

**Action:** Verify the configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-12006: Invalid path for audit event definitions file.**

**Cause:** The audit event definitions file location is incorrect.

**Action:** Verify the configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-12007: Invalid path for audit bustop directory.**

**Cause:** The audit bustop location is missing, or invalid.

**Action:** Verify the configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-12501: Getting ServerTokenMapper for: {0}.**

**Cause:** Getting ServerTokenMapper for {0}

**Action:** None

---

**Level:** 16  
**Type:** NOTIFICATION  
**Impact:** Other  
**OAM-12502: Server Token Not available in the Response.**  
**Cause:** Server Token Not available in the Response.  
**Action:** None

**Level:** 16  
**Type:** NOTIFICATION  
**Impact:** Other  
**OAM-12503: 10g SSO\_ID Token set {0} .**  
**Cause:** 10g SSO\_ID Token set.  
**Action:** None

**Level:** 16  
**Type:** NOTIFICATION  
**Impact:** Other  
**OAM-12504: 10g SSO\_ID Decrypted successfully : {0}**  
**Cause:** 10g SSO\_ID Decrypted successfully.  
**Action:** None

**Level:** 16  
**Type:** NOTIFICATION  
**Impact:** Other  
**OAM-12505: Removing the SSO\_ID Cookie at Logout.**  
**Cause:** Removing the SSO\_ID Cookie at Logout.  
**Action:** None

**Level:** 16  
**Type:** NOTIFICATION  
**Impact:** Other  
**OAM-12506: "Creating session token with values - " + "Domain: {0}, Version: {1}, Age: {2}, Secure: {3}, " + "Value: {4}";**  
**Cause:** Created Session Token with values  
**Action:** None

**Level:** 16  
**Type:** NOTIFICATION  
**Impact:** Other  
**OAM-12507: Token Version not found.**  
**Cause:** Token Version not found.  
**Action:** Validate the config to include the Token Version.

**Level:** 15

---

**Type:** ERROR  
**Impact:** Other  
**OAM-12508: 10g SSO\_ID Decryption failed.**  
**Cause:** 10g SSO\_ID Decryption failed.  
**Action:** Verify if the 10gSSO Server Key is present in the config  
**Level:** 15  
**Type:** ERROR  
**Impact:** Other  
**OAM-12509: Could not get token mapper for token for {0}.**  
**Cause:** Could not get token mapper for token.  
**Action:** Validate the config to include the Token Version.[v1.2, v1.4]  
**Level:** 15  
**Type:** ERROR  
**Impact:** Other  
**OAM-12510: 10g SSO\_ID Token NOT created.**  
**Cause:** 10g SSO\_ID Token NOT created.  
**Action:** Verify if the 10gSSO Server Key/Token Version is present in the config  
**Level:** 15  
**Type:** ERROR  
**Impact:** Other  
**OAM-12511: Error while creating SSO Transport token.**  
**Cause:** Error while creating Transport Token  
**Action:** Validate the config to check for the 10g SSO Server Key  
**Level:** 15  
**Type:** ERROR  
**Impact:** Other  
**OAM-12512: Cannot retrieve the 10g SSO Key**  
**Cause:** Cannot retrieve the 10g SSO Key  
**Action:** Validate the config to check for the 10g SSO Server Key  
**Level:** 1  
**Type:** SEVERE  
**Impact:** Other  
**OAM-12513: Diagnostic Engine Failed to Start**  
**Cause:** Diagnostic Engine Failed  
**Action:** None  
**Level:** 16  
**Type:** NOTIFICATION  
**Impact:** Other

---

**OAM-12514: Request Handling Error**

**Cause:** Request Handling Error

**Action:** None

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-12515: Session Token Not Found**

**Cause:** Session Token Not Found

**Action:** None

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-12516: 10g SSO Server Config Details Missing**

**Cause:** 10g SSO Server Config Details Missing

**Action:** Add the Config details to oam-config.xml

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-14001: Unregistration of OAM Management MBean failed.**

**Cause:** An internal error occurred.

**Action:** Check the OAM Server logs.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-14002: OAM Server configuration update failed.**

**Cause:** Failed to update OAM Policy or System Configuration.

**Action:** Check the OAM Server MBean logs.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-14003: Invalid HostIdentifier configuration for AppDomain {0} in OAM Policy.**

**Cause:** Definition of HostIdentifier for application domain was invalid.

**Action:** Re-check Application Domain configuration in OAM Policy.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-14005: Validation of a input parameter failed.**



---

**Cause:** One of the input parameter value was illegal.

**Action:** Check the OAM Server MBean logs.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-14007: Cannot retrieve OAM Server configuration for {0}.**

**Cause:** Cannot retrieve data from OAM System configuration.

**Action:** Check the OAM Server MBean logs.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-14008: Cannot retrieve Partner configuration for {0}.**

**Cause:** Cannot get the details of Partner from OAM System Configuration.

**Action:** Check the OAM Server MBean logs.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-14009: Application Domain not found in OAM Policy {0}.**

**Cause:** None

**Action:** None

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-14100: Host Information is already registered in OAM HostIdentifier with host {0} and port {1}.**

**Cause:** None

**Action:** None

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-14101: Starting Enable OIM Configuration.**

**Cause:** None

**Action:** None

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-14102: Starting Disable OIM Configuration.**

**Cause:** None

---

**Action:** None

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-14103: Completed OAM Server Policy Configuration update.**

**Cause:** None

**Action:** None

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-14104: Completed OAM Server System Configuration update.**

**Cause:** None

**Action:** None

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-14105: Completed OIM Configuration.**

**Cause:** None

**Action:** None

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-14106: Completed validation of Input values.**

**Cause:** None

**Action:** None

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-14107: Successfully updated OAM Partner data.**

**Cause:** None

**Action:** None

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-14108: Successfully updated OAM Configuration.**

**Cause:** None

**Action:** None

---

**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAM-14109: Enables OIM Integration.**  
**Cause:** None  
**Action:** None

**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAM-14110: Disables OIM Integration.**  
**Cause:** None  
**Action:** None

**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAM-14111: Registration of OAM Management MBean failed.**  
**Cause:** An internal error occurred.  
**Action:** Check the OAM Server logs.

**Level:** 15  
**Type:** ERROR  
**Impact:** Other  
**OAM-16001: Cannot parse the session token.**  
**Cause:**  
**Action:**

**Level:** 15  
**Type:** ERROR  
**Impact:** Other  
**OAM-18001: User Identity Store Configuration is not valid.**  
**Cause:** The user identity store configuration was missing, or was invalid.  
**Action:** Verify the user identity store configuration.

**Level:** 15  
**Type:** ERROR  
**Impact:** Other  
**OAM-18002: Server Configuration is not valid.**  
**Cause:** The server configuration was missing, or was invalid.  
**Action:** Verify the server configuration.

**Level:** 15  
**Type:** ERROR

---

**Impact:** Other

**OAM-18016: Validation Failure : "{0}" attributes missing in User Identity Store.**

**Cause:** The required attributes were not present in the user identity store.

**Action:** Add the attributes to the user identity store and rerun the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAM-18017: Validation Failure : "{0}" attributes missing in OAM Server Instance.**

**Cause:** The required attributes were not specified for the server instance.

**Action:** Add the attributes to the server instance and rerun the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAM-18018: Validation Failure : "{0}" attributes missing in {1} Authentication Module.**

**Cause:** The required attributes were not specified for the authentication module.

**Action:** Add the attributes to the authentication module and rerun the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAM-18019: Validation Failure - Object not found for deletion.**

**Cause:** The object supplied for deletion has been deleted, or does not exist.

**Action:** Use the correct data and rerun the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAM-18020: Validation Failure : {0} Module cannot be deleted. (Referred in Scheme).**

**Cause:** The module was being referred to in a scheme.

**Action:** Remove the reference from the scheme and then delete the module.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAM-18021: Authentication module configuration is not valid.**

**Cause:** The authentication module configuration was missing, or was invalid.

**Action:** Verify the authentication module configuration.

**Level:** 15

**Type:** ERROR

---

**Impact:** Other

**OAM-20001: Deleted application domain {0}.**

**Cause:**

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-20002: Duplicated application domain {0}.**

**Cause:**

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-20003: Saved authentication scheme {0}.**

**Cause:**

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-20004: Deleted authentication scheme {0}.**

**Cause:**

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-20005: Duplicated authentication scheme {0}.**

**Cause:**

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-20006: Button with id {0} is disabled {1}**

**Cause:**

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-20007: Set authentication scheme {0} as the default scheme.**

---

**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-20008: Set {0} as the default authenticationn scheme.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-20009: Saved host identifier {0}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-20010: Deleted host identifier {0}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-20011: Duplicated host identifier{0}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-20012: Deleted host identifier entry with key {0}**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-20013: Saved resource {0}.**  
**Cause:**  
**Action:**

---

**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAM-20014: Deleted resource {0}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAM-20015: Duplicated resource {0}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAM-20016: Saved authentication policy {0}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAM-20017: Deleted authentication policy {0}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAM-20018: Duplicated authentication policy {0}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAM-20019: Saved authorization policy {0}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO

---

**Impact:** Other

**OAM-20020: Deleted authorization policy {0}.**

**Cause:**

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-20021: Duplicated authorization policy {0}.**

**Cause:**

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-20022: Saving authentication policy response {0}, {1}, {2}.**

**Cause:**

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-20023: Saved authentication policy response {0}.**

**Cause:**

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-20024: Deleted authentication policy response row with key {0}.**

**Cause:**

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-20025: Deleted authentication policy response {0}.**

**Cause:**

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-20026: Saved authentication policy resource {0}.**



---

**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-20027: Deleted authentication policy resource with key {0}.**

**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-20028: Deleted authentication policy resource {0}.**

**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-20029: Saving authorization policy response {0}, {1}, {2}.**

**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-20030: Saved authorization policy response {0}.**

**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-20031: Deleted authorization policy response with key {0}.**

**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-20032: Deleted authorization policy response {0}.**

**Cause:**  
**Action:**

---

**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAM-20033: Saved authorization policy resource {0}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAM-20034: Deleted authorization policy resource with key {0}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAM-20035: Deleted authorization policy resource {0}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAM-20036: Added {0}:{1}:{2} constraint.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAM-20037: Added constraint {0}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAM-20038: Saved constraint {0}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO

---

**Impact:** Other

**OAM-20039: Deleted constraint with key {0}.**

**Cause:**

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-20040: Deleted constraint {0}.**

**Cause:**

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-20041: Fetching details for master constraint {0}:{1}:{2}.**

**Cause:**

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-20042: Saved details for temporal constraint {0}.**

**Cause:**

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-20043: Cancelled detail changes for temporal constraint {0}.**

**Cause:**

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-20044: Saved details for ip4 constraint {0}.**

**Cause:**

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-20045: Cancelled detail changes for ip4 constraint {0}.**

---

**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-20046: Saved details for identity constraint {0}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-20047: Cancelled detail changes for identity constraint {0}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-20048: Added {0}:{1} under identity constraint.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-20049: Deleted key {0}:{1} under identity constraint.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-20050: Deleted {0}:{1} under identity constraint.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-20051: Searching for {0}:{1}.**  
**Cause:**  
**Action:**

---

**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAM-20052: Saved component {0}:{1}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAM-20053: Created component {0}:{1}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAM-20054: Duplicated component {0}:{1}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAM-20055: Deleted component {0}:{1}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAM-20056: Recording action:{0}, childnode:{1}, appdomain name:{2}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAM-20057: Cancelled application domain {0}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO

---

**Impact:** Other

**OAM-20058: Cancelled authentication scheme {0}.**

**Cause:**

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-20059: Cancelled host identifier {0}.**

**Cause:**

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-20060: Cancelled resource {0}.**

**Cause:**

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-20061: Cancelled authentication policy {0}.**

**Cause:**

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-20062: Cancelled authorization policy {0}.**

**Cause:**

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-20063: Successfully saved application domain {0}.**

**Cause:**

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-20100: Cannot save application domain {0}.**

---

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-20101: Cannot delete application domain {0}.**

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-20102: Cannot duplicate application domain{0}.**

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-20103: Cannot save authentication scheme {0}.**

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-20104: Cannot delete authentication scheme {0}.**

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-20105: Cannot duplicate authentication scheme {0}.**

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-20106: Cannot set {0} as the default authentication scheme.**

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

---

**Level:** 15  
**Type:** ERROR  
**Impact:** Other  
**OAM-20107: Cannot save host identifier {0}.**  
**Cause:** An internal error occurred.  
**Action:** For more details,start logging at the FINE level.

**Level:** 15  
**Type:** ERROR  
**Impact:** Other  
**OAM-20108: Cannot delete host identifier {0}.**  
**Cause:** An internal error occurred.  
**Action:** For more details,start logging at the FINE level.

**Level:** 15  
**Type:** ERROR  
**Impact:** Other  
**OAM-20109: Cannot duplicate host identifier {0}.**  
**Cause:** An internal error occurred.  
**Action:** For more details,start logging at the FINE level.

**Level:** 15  
**Type:** ERROR  
**Impact:** Other  
**OAM-20110: Cannot save resource {0}.**  
**Cause:** An internal error occurred.  
**Action:** For more details,start logging at the FINE level.

**Level:** 15  
**Type:** ERROR  
**Impact:** Other  
**OAM-20111: Cannot delete resource {0}.**  
**Cause:** An internal error occurred.  
**Action:** For more details,start logging at the FINE level.

**Level:** 15  
**Type:** ERROR  
**Impact:** Other  
**OAM-20112: Cannot duplicate resource {0}.**  
**Cause:** An internal error occurred.  
**Action:** For more details,start logging at the FINE level.

**Level:** 15  
**Type:** ERROR



---

**Impact:** Other

**OAM-20113: Cannot save authentication policy {0}.**

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-20114: Cannot duplicate authentication policy {0}.**

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-20115: Cannot delete authentication policy {0}.**

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-20116: Cannot save authorization policy {0}.**

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-20117: Cannot duplicate authorization policy {0}.**

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-20118: Cannot delete authorization policy {0}.**

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-20119: Cannot initialize authentication policy response.**

---

**Cause:** An internal error occurred.  
**Action:** For more details,start logging at the FINE level.  
**Level:** 15  
**Type:** ERROR  
**Impact:** Other

**OAM-20120: Cannot save authentication policy response {0}.**  
**Cause:** An internal error occurred.  
**Action:** For more details,start logging at the FINE level.  
**Level:** 15  
**Type:** ERROR  
**Impact:** Other

**OAM-20121: Cannot delete authentication policy response {0}.**  
**Cause:** An internal error occurred.  
**Action:** For more details,start logging at the FINE level.  
**Level:** 15  
**Type:** ERROR  
**Impact:** Other

**OAM-20122: Cannot save authentication policy resource {0}.**  
**Cause:** An internal error occurred.  
**Action:** For more details,start logging at the FINE level.  
**Level:** 15  
**Type:** ERROR  
**Impact:** Other

**OAM-20123: Cannot delete authentication policy resource {0}.**  
**Cause:** An internal error occurred.  
**Action:** For more details,start logging at the FINE level.  
**Level:** 15  
**Type:** ERROR  
**Impact:** Other

**OAM-20124: Cannot initialize authorization policy response.**  
**Cause:** An internal error occurred.  
**Action:** For more details,start logging at the FINE level.  
**Level:** 15  
**Type:** ERROR  
**Impact:** Other

**OAM-20125: Cannot save authorization policy response {0}.**  
**Cause:** An internal error occurred.  
**Action:** For more details,start logging at the FINE level.

---

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-20126: Cannot delete authorization policy response {0}.**

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-20127: Cannot save authorization policy resource {0}.**

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-20128: Cannot delete authorization policy resource {0}.**

**Cause:** AuthzPolicyResource delete failed.

**Action:** AuthzPolicyResource delete failed.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-20129: Cannot save constraint {0}.**

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-20130: Cannot delete constraint {0}.**

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-20131: Cannot save details for temporal constraint {0}.**

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

**Level:** 15

**Type:** INFO

---

**Impact:** Other

**OAM-20132: Cannot cancell detail changes for temporal constraint {0}.**

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-20133: Cannot save details for ip4 constraint {0}.**

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-20134: Cannot cancel detail changes for ip4 constraint {0}.**

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-20135: Cannot save details for identity constraint {0}.**

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-20136: Cannot cancel detail changes for identity constraint {0}.**

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

**Level:** 1

**Type:** INFO

**Impact:** Other

**OAM-20137: Cannot save details for identity constraint {0}.**

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-20138: Cannot delete details under identity constraint {0}.**

---

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-20139: Error occurred while searching for {0}:{1}.**

**Cause:**

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-20140: Cannot save component {0}:{1}.**

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-20141: Cannot create component {0}:{1}.**

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-20142: Cannot duplicate component {0}:{1}.**

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-20143: Cannot delete component {0}:{1}.**

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-20144: Cannot cancel action for component {0}:{1}.**

**Cause:** An internal error occurred.

**Action:** For more details,start logging at the FINE level.

---

**Level:** 15  
**Type:** ERROR  
**Impact:** Other  
**OAM-20145: Cannot cancel application domain {0}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAM-20146: Cannot cancel authentication scheme {0}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAM-20147: Cannot cancel hostidentifier {0}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAM-20148: Cannot cancel resource {0}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAM-20149: Cannot cancel authentication policy {0}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAM-20150: Cannot cancel authorization policy {0}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO

---

**Impact:** Other

**OAM-22001: Error occurred during cleanUpPolicy : {0}**  
**Cause:** Error occurred during cleanUpPolicy.  
**Action:** Check the OAM t2p logs.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-22002: Error occurred during cleanUpApplicationDomains : {0}**  
**Cause:** Error occurred during cleanUpApplicationDomains.  
**Action:** Check the OAM t2p logs.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-22003: Error occurred during initialization : {0}**  
**Cause:** Error occurred during initialization.  
**Action:** Check the OAM t2p logs.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-22004: Error occurred during copying HostIdentifiers : {0}**  
**Cause:** Error occurred during copying HostIdentifiers.  
**Action:** Check the OAM t2p logs.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-22005: Error occurred during copying policy changes : {0}**  
**Cause:** Error occurred during copying policy changes.  
**Action:** Check the OAM t2p logs.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAM-22006: Fetched partners from OAM server.**  
**Cause:** None  
**Action:** None

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAM-22007: Applied partners to OAM server.**

---

**Cause:** None  
**Action:** None  
**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-22008: Switching off policy distribution.**  
**Cause:** None  
**Action:** None  
**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-22009: Cleaned up policy file : {0}.**  
**Cause:** None  
**Action:** None  
**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-22010: Copied policy changes to the intermediate file.**  
**Cause:** None  
**Action:** None  
**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-22011: Switching on policy distribution.**  
**Cause:** None  
**Action:** None  
**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-22012: Copied policy changes from the intermediate file.**  
**Cause:** None  
**Action:** None  
**Level:** 15  
**Type:** INFO  
**Impact:** Other

**OAM-22013: Added host {0}:{1} to {2}.**  
**Cause:** None  
**Action:** None



---

**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAM-22014: Removed host {0}:{1} from {2}.**  
**Cause:** None  
**Action:** None

**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAM-22015: Removed resource {0} and policies using this resource from application domain {1}.**  
**Cause:** None  
**Action:** None

**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAM-22016: Error occurred during creating application domain : {0}**  
**Cause:** Error occurred during creating application domain.  
**Action:** Check the OAM t2p logs.

**Level:** 15  
**Type:** ERROR  
**Impact:** Other  
**OAM-22017: Error occurred during removing resource : {0}**  
**Cause:** Error occurred during creating application domain.  
**Action:** Check the OAM t2p logs.

**Level:** 15  
**Type:** ERROR  
**Impact:** Other  
**OAM-22018: Error occurred during decrypting key : {0}**  
**Cause:** Error occurred during decrypting key.  
**Action:** Check the OAM t2p logs.

**Level:** 15  
**Type:** ERROR  
**Impact:** Other  
**OAM-22019: Error occurred during encrypting key : {0}**  
**Cause:** Error occurred during encrypting key.  
**Action:** Check the OAM t2p logs.

**Level:** 15

---

**Type:** ERROR

**Impact:** Other

**OAM-24001: Cannotfind LdapProperties file**

**Cause:** The session token appears to be invalid.

**Action:** For more details, start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

---

## OAMAP-60501 to OAMAP-60521

**OAMAP-60501: The Access Server entry was not specified in the required format:****host:port****Cause:** One or more Oracle Access Manager Access Server entries were not specified correctly.**Action:** Contact your Oracle Access Manager administrator to ensure that Access Server entries are specified with host:port format. host is the DNS host name of the computer where the Access Server is installed and port is the Access Server port number.**Level:** 1**Type:** ERROR**Impact:** Configuration**OAMAP-60502: No CallbackHandler was supplied to the Identity Asserter/Authenticator.****Cause:** No CallbackHandler was found during Identity Asserter/Authenticator initialization.**Action:** Contact your Oracle single sign-on administrator with exception/error information.**Level:** 1**Type:** ERROR**Impact:** Internal Error**OAMAP-60503: A required callback was not found.****Cause:** A required callback was not found by the Identity Authenticator.**Action:** Contact your Oracle single sign-on administrator with exception/error information.**Level:** 1**Type:** ERROR**Impact:** Internal Error**OAMAP-60504: Unable to read user input from the CallbackHandler.****Cause:** The Identity Authenticator failed to read user input from the CallbackHandler.**Action:** Ensure that you have entered the appropriate credentials.**Level:** 1

---

**Type:** ERROR

**Impact:** Data

**OAMAP-60505: Found an unsupported token type.**

**Cause:** The Identity Asserter was invoked with an unsupported token type.

**Action:** Contact your Oracle single sign-on administrator with exception/error information.

**Level:** 1

**Type:** ERROR

**Impact:** Internal Error

**OAMAP-60506: Found an unsupported token class.**

**Cause:** The Identity Asserter received an unknown token class "{0}". Expected: a byte[].

**Action:** Contact your Oracle single sign-on administrator with exception/error information.

**Level:** 1

**Type:** ERROR

**Impact:** Internal Error

**OAMAP-60507: Found an invalid SSO Token.**

**Cause:** The Identity Asserter received an SSO token with no characters.

**Action:** Contact your Oracle single sign-on administrator with exception/error information.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMAP-60508: Authentication failed. An invalid ObSSOCookie was found.**

**Cause:** An invalid ObSSOCookie was received.

**Action:** Contact your Oracle Access Manager administrator to ensure that the ObSSOCookie is not corrupted or timedout before it is passed to the Identity Asserter.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMAP-60509: The Identity Authenticator does not support NameCallback.**

**Cause:** NameCallback was not found in the callback array.

**Action:** Contact your Oracle single sign-on administrator with exception/error information.

**Level:** 1

**Type:** ERROR

**Impact:** Internal Error

**OAMAP-60510: The Identity Authenticator does not support PasswordCallback.**

---

**Cause:** PasswordCallback was not found in the callback array.

**Action:** Contact your Oracle single sign-on administrator with exception/error information.

**Level:** 1

**Type:** ERROR

**Impact:** Internal Error

**OAMAP-60511: Resource "{0}" is not protected by an Oracle Access Manager policy domain.**

**Cause:** The Identity Asserter/Authenticator detected that resource "{0}" is not protected by an Oracle Access Manager policy domain.

**Action:** Contact your Oracle Access Manager administrator to ensure that the Resource type, Resource Name, and Resource operations are specified correctly for identity assertion, and that the resource specified by the Resource Name is protected by an Oracle Access Manager policy domain and access policies.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OAMAP-60512: Unable to get the user name from Return Actions configured in the Oracle Access Manager policy domain.**

**Cause:** The Identity Asserter/Authenticator didn't get any Return Action named uid from the Access Server.

**Action:** Contact your Oracle Access Manager administrator to ensure that the Return Action in the Oracle Access Manager policy domain is configured correctly to return the user's login name.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OAMAP-60513: Required parameters are not configured for the Identity Asserter/Authenticator.**

**Cause:** The Identity Asserter/Authenticator did not find one or more required parameters.

**Action:** Contact your Oracle Access Manager administrator to ensure that the AccessGate Name, AccessGate Password, Primary/Secondary Access Server Name parameters are specified correctly in the Access System Console.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OAMAP-60514: Unable to get the user name.**

**Cause:** No user name was found in NameCallback.

**Action:** Specify a user name when asked during the authentication challenge.

**Level:** 1

**Type:** ERROR

---

**Impact:** Data

**OAMAP-60515: The AccessGate Name is not recognized by the Access Server.**

**Cause:** An incorrect AccessGate name was found.

**Action:** Contact your Oracle Access Manager administrator to ensure that the AccessGate name configured for the Identity Asserter/Authenticator exists in a profile in the Access System Console.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OAMAP-60516: Unable to create the AccessGate entry for identity assertion/authentication.**

**Cause:** AccessGate instance creation failed.

**Action:** See the Identity Asserter/Authenticator log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OAMAP-60517: Failed to validate the SSO Token.**

**Cause:** The Identity Asserter failed to validate the SSO token.

**Action:** See the Identity Asserter log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMAP-60518: Authentication failed.**

**Cause:** The user could not be authenticated with the provided credentials.

**Action:** See the Identity Authenticator log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMAP-60519: Cannot find the SSO Token in the callback.**

**Cause:** The SSO Token was not found in the CallbackHandler.

**Action:** Contact your Oracle single sign-on administrator with exception/error information.

**Level:** 1

**Type:** ERROR

**Impact:** Internal Error.

**OAMAP-60520: Cannot get a logger instance.**

**Cause:** Cannot create a logger instance.

**Action:** Contact your Oracle single sign-on administrator with exception/error information.

---

**Level:** 1

**Type:** ERROR

**Impact:** Internal Error.

**OAMAP-60521: Found an invalid value for parameter "{0}".**

**Cause:** The Identity Asserter/Authenticator parameter value contains a whitespace.

**Action:** Ensure that the value for Identity Asserter/Authenticator parameter doesn't contain any whitespaces.

**Level:** 1

**Type:** ERROR

**Impact:** Config





---

## OAMCFG-60001 to OAMCFG-60080

**OAMCFG-60001: Error in initializing logging.**

**Cause:** System error

**Action:** Check Java system logger settings.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**OAMCFG-60002: Unable to establish connection to directory server.**

**Cause:** Incorrect input given for LDAP directory server parameters.

**Action:** Verify input values for the following parameters: ldap\_host, ldap\_port, ldap\_userdn, and ldap\_userpassword.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OAMCFG-60003: Error in parsing command-line parameters.**

**Cause:** One or more required parameters are missing.

**Action:** Provide all required parameters. Use -help option to see the list of parameters.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60004: Cannot write LDIF to console.**

**Cause:** A request was made to write LDIF output to the console.

**Action:** Specify a proper LDIF file name using the output\_ldif\_file parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**OAMCFG-60005: The same file name cannot be used for the log file and the LDIF output file.**

**Cause:** The same name was specified for output\_ldif\_file and log\_file parameters.

**Action:** Specify different names for output\_ldif\_file and log\_file parameters.

---

**Level: 1**

**Type: ERROR**

**Impact: Files**

**OAMCFG-60006: In VALIDATE mode, the test\_username parameter is mandatory**

**Cause:** The test\_username parameter was not specified during validation.

**Action:** Specify the test\_username parameter during validation.

**Level: 1**

**Type: ERROR**

**Impact: Data**

**OAMCFG-60007: In VALIDATE mode, the test\_userpassword is mandatory**

**Cause:** The test\_userpassword parameter was not specified during validation.

**Action:** Specify the test\_userpassword parameter during validation.

**Level: 1**

**Type: ERROR**

**Impact: Data**

**OAMCFG-60008: Oracle Access Manager version {0} cannot be configured.**

**Cause:** An unsupported version of Oracle Access Manager is specified on the command line.

**Action:** Specify the correct, supported Oracle Access Manager version.

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**OAMCFG-60009: The app\_domain parameter is mandatory**

**Cause:** The app\_domain parameter was not specified.

**Action:** Specify the app\_domain parameter.

**Level: 1**

**Type: ERROR**

**Impact: Data**

**OAMCFG-60010: The specified LDAP port number is invalid**

**Cause:** An invalid LDAP port was specified.

**Action:** Specify a valid LDAP port.

**Level: 1**

**Type: ERROR**

**Impact: Data**

**OAMCFG-60011: The ldap\_userdn parameter is mandatory.**

**Cause:** The ldap\_userdn parameter was not specified.

**Action:** Specify the ldap\_userdn parameter.

**Level: 1**

---

**Type:** ERROR

**Impact:** Data

**OAMCFG-60012: The specified Oracle Access Manager port number is invalid.**

**Cause:** An invalid Oracle Access Manager port number was specified.

**Action:** Specify the correct Oracle Access Manager port number.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60013: Found Oracle Access Manager version {0} which is incompatible.**

**Cause:** The tool found an incompatible version of Oracle Access Manager configured in the directory.

**Action:** Use the tool with a compatible Oracle Access Manager version.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OAMCFG-60014: Oracle Access Manager is not configured with this directory.**

**Cause:** Oracle Access Manager is not configured for the specified directory.

**Action:** Contact your Oracle Access Manager administrator to configure Oracle Access Manager for the specified directory.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OAMCFG-60015: Invalid value detected for oam\_aaa\_host or oam\_aaa\_port.**

**Cause:** Cannot find the Access Server based on the specified host or port in configuration. Or check if oam\_mode is correctly specified. Default is open mode

**Action:** Specify a valid Access Server host and port.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OAMCFG-60016: Error in closing file handles.**

**Cause:** An error occurred when closing file handles used by the tool.

**Action:** Check the file system for consistency.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**OAMCFG-60017: Cannot decode URI : {0} due to its length. Actual length: {1}**

**Cause:** The URI in the directory is an illegal length. The encoded URI length must always be even.

**Action:** Contact your Oracle Access Manager administrator to correct or delete the URI in the directory.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60018: Cannot decode URI :{0}**

**Cause:** The URI was found to contain illegal hexadecimal characters.

**Action:** Contact your Oracle Access Manager administrator to correct or delete the URI in the directory.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60019: Cannot send the cache flush request to server {0} running on port {1} in mode {2}.**

**Cause:** The Access server is down.

**Action:** Contact your Oracle Access Manager administrator to ensure that the Access Server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OAMCFG-60020: A cache flush request cannot be sent using the desired transport security mode {0}.**

**Cause:** The Access Server is not available with the specified transport security mode.

**Action:** Contact your Oracle Access Manager administrator to ensure that the Access Server is running in the desired transport security mode.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OAMCFG-60021: Found multiple policy stores in the directory:: {0}.**

**Cause:** Multiple Access Server Policy Stores are configured in the directory.

**Action:** Use the ldap\_base parameter to specify the correct searchbase.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OAMCFG-60022: Access Server is not configured in this directory.**

**Cause:** The Access Server is not configured.

**Action:** Contact your Oracle Access Manager administrator to configure the Access Server.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**OAMCFG-60023: A problem occurred when communicating with the LDAP directory server.**

**Cause:** The LDAP directory server is down.

**Action:** Contact your LDAP directory server administrator to ensure the directory is running.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OAMCFG-60024: The LDAP operation failed.**

**Cause:** Either incorrect configuration or invalid parameters and values were specified.

**Action:** Confirm that your parameters and values are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60025: A problem occurred while trying to fetch the Oracle Access Manager details from configuration.**

**Cause:** An Oracle Access Manager instance matching the specified input could not be found.

**Action:** Confirm parameters oam\_aaa\_host and oam\_aaa\_port are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60026: Cannot get Global Sequence Number in the specified Oracle Access Manager policy store: {0}.**

**Cause:** The configuration data in the LDAP directory server is missing Global Sequence Number information.

**Action:** Contact your Oracle Access Manager administrator to configure Oracle Access Manager with the LDAP directory.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OAMCFG-60027: Found {0} entries that match the name: {1}.**

**Cause:** Multiple names match the given name.

**Action:** Contact your Oracle Access Manager administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60028: Found no entries that match the specified name:{0} of type:{1}.**

**Cause:** Entries matching the specified name cannot be found.

**Action:** Confirm the name.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60029: Error while loading template:{0} to LDAP**

**Cause:** Not all information could be loaded to LDAP directory.

**Action:** Contact your Oracle Access Manager administrator to validate that all data has been loaded.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60030: The app\_agent\_password parameter is mandatory when creating a Web domain.**

**Cause:** The app\_agent\_password parameter was not specified.

**Action:** Specify the app\_agent\_password when creating a Web domain.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60031: The template file {0} cannot be located.**

**Cause:** The specified template could not be found in either the file system or the Jar file.

**Action:** Obtain the Jar file again. If your template was customized, ensure it is in the expected file system location.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**OAMCFG-60032: The template file {0} cannot be read from file system.**

**Cause:** The template file or file system (or both) might be corrupted.

**Action:** Ensure that the template file or file system error (or both) are corrected.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**OAMCFG-60033: Problem locating a template file in JAR file:{0}**

**Cause:** The JAR file does not contain the required templates.

**Action:** Ensure that the correct JAR file is specified in the CLASSPATH.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**OAMCFG-60034: The specified LDAP SSL mode is invalid**

**Cause:** An invalid LDAP SSL mode was specified.

---

**Action:** Specify a valid LDAP SSL mode: 1, 2 or 3.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60035: The specified application domain, {0}, cannot be used.**

**Cause:** The value provided for app\_domain parameter contains illegal characters.

**Action:** Specify app\_domain parameter with legal characters.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60036: The specified web domain, {0}, cannot be used.**

**Cause:** The value provided for web\_domain parameter contains illegal characters.

**Action:** Specify web\_domain parameter with legal characters.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60037: ldap\_userpassword is mandatory**

**Cause:** The ldap\_userpassword parameter was not specified.

**Action:** Specify the ldap\_userpassword parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60038: The URIs file parameter should not be empty**

**Cause:** The uris\_file param is empty.

**Action:** If you are using the uris\_file parameter, then specify an appropriate value. This value should list the full path to a file, containing protected and public uris

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60039: The specified uris\_file, {0}, could not be found**

**Cause:** The file specified by uris\_file param does not exist.

**Action:** Make sure the path you have specified for the file containing uris is correct

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60040: uris\_file, {0}, cannot be read**

**Cause:** There is some issue in reading the file

---

**Action:** Contact your administrator

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60041: uris\_file, {0}, could not be closed**

**Cause:** The file could not be closed

**Action:** No action needs to be taken, if there are no other errors

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60042: uris\_file, {0}, does not have protected uris**

**Cause:** No Protected uris have been specified

**Action:** Contact the file owner

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60043: Protected URIs have already been listed in the uris file**

**Cause:** Protected uris are being specified again

**Action:** Include the protected uris, specified in command line, in the uris file and do not pass the protected\_uris parameter

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60044: Public URIs have already been listed in the uris file**

**Cause:** Public uris are being specified again

**Action:** Include the public uris, specified in command line, in the uris file and do not pass the public\_uris parameter

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60045: Invalid Authenticating Webgate URL**

**Cause:** The Authenticating Webgate URL is not formatted correctly

**Action:** Ensure that the URL is of the form, 'http://host.us.oracle.com:port' or 'https://host.us.oracle.com:port'. Note that it is important to specify the URL with a FQDN, a domain in which your cookie would be valid.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60046: LDAP\_HOST parameter is mandatory**



---

**Cause:** LDAP\_HOST parameter is not specified

**Action:** Specify LDAP\_HOST parameter in command line

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60047: OAM\_AAA\_HOST parameter is mandatory**

**Cause:** OAM\_AAA\_HOST parameter is not specified

**Action:** Specify OAM\_HOST parameter in command line

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60048: APP\_DOMAIN, {0}, does not exist**

**Cause:** APP\_DOMAIN, {0}, does not exist

**Action:** Specify a APP\_DOMAIN parameter that exists in OAM

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60049: URI, {0}, does not exist**

**Cause:** URI, {0}, does not exist

**Action:** Specify a URI that exists in OAM

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60050: Authentication scheme, {0}, does not exist**

**Cause:** Authentication scheme, {0}, does not exist

**Action:** Specify a valid Authentication Scheme

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60051: Webdomain, {0}, does not exist**

**Cause:** Webdomain, {0}, does not exist

**Action:** Specify a valid Host Identifier as part of Web\_domain

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60052: Simple Mode Passphrase is mandatory for Simple mode**

**Cause:** Simple Mode Passphrase has not been provided

**Action:** Specify a Simple Mode Passphrase

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60053: OAM\_AAA\_PORT parameter is mandatory**

**Cause:** OAM\_AAA\_PORT parameter is not specified

**Action:** Specify OAM\_AAA\_PORT parameter in command line

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60054: Specify protected or public uris either in command line or in a file**

**Cause:** Both protected\_uris and public\_uris have not been specified for Create mode

**Action:** Specify protected or public uris either in command line or in a file

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60055: One of the default authentication schemes is in use and cannot be deleted**

**Cause:** Some policies are using the default authentication schemes that you wish to delete

**Action:** First delete the policies that are using the authentication scheme specified

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60056: The default authentication scheme,**

**OraDefaultAWGFormAuthNScheme, is in use and cannot be deleted**

**Cause:** Some policies are using this authentication scheme that you wish to delete

**Action:** First delete the policies that are using the authentication scheme specified

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60057: The default authentication scheme,**

**OraDefaultI18NFormAuthNScheme, is in use and cannot be deleted**

**Cause:** Some policies are using this authentication scheme that you wish to delete

**Action:** First delete the policies that are using the authentication scheme specified

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60058: The web\_domain specified, {0}, is in use and cannot be deleted**

---

**Cause:** Some policies are using the web domain that you wish you delete

**Action:** First delete the policies that are using the web domain

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60059: Either app\_domain or uris or web domain or authn schemes need to be provided. See help**

**Cause:** Required parameters have not been specified for DELETE mode

**Action:** Specify whether app domain or uris or web domain or authn schemes need to be deleted

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60060: An error occurred while modifying the ldap attribute, {0}**

**Cause:** An error occurred while modifying the ldap attribute, {0}

**Action:** Contact your OAM administrator

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60061: The Webgate with id, {0}, does not exist**

**Cause:** The specified Webgate does not exist in OAM

**Action:** Specify the correct webgate id using the parameter, {0}

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60062: LogoutRedirectUrl has already been configured for the WebGate, {0}**

**Cause:** LogoutRedirectUrl parameter is not empty for the specified WebGate

**Action:** You cannot reconfigure the parameter logoutRedirectUrl using the Config tool. Use OAM Policy Manager UI for this., {0}

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60063: The LogoutRedirectUrl element tag has been messed up in the attribute, 'obcompounddata' attribute for the WebGate, {0}**

**Cause:** LogoutRedirectUrl element is not formatted correctly in the DS for the specified WebGate

**Action:** Contact the OAM Administrator

**Level:** 1

---

**Type:** ERROR

**Impact:** Data

**OAMCFG-60064: The LogoutRedirectUrl param cannot be configured without AWG**

**Cause:** authenticating\_wg\_url param is not specified

**Action:** Specify authenticating\_wg\_url param

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60065: The logouturi parameter is not a valid uri**

**Cause:** The logouturi parameter needs to have an value beginning with '/'

**Action:** Specify a valid uri

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60066: An unexpected parameter has been passed to the tool, {0}**

**Cause:** An unexpected parameter is present as part of the command line arguments

**Action:** Make sure that none of the parameters have been misspelled and that all the parameters specified are indeed valid

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60067: OimOhsHostPort needs to be specified if authenticating\_wg\_url parameter is mentioned**

**Cause:** OimOhsHostPort has not been specified and authenticating\_wg\_url parameter is mentioned

**Action:** Specify OimOhsHostPort parameter

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60068: The Authentication Scheme specified by {0} would be given preference over the default i18n authentication scheme**

**Cause:** The default i18n authentication scheme specified by usei18nlogin flag would not be used because of the parameter default\_authn\_scheme

**Action:** One of the two parameters should be specified

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60069: The Access Server Id, {0}, mentioned as part of the parameter, {1} is not present in OAM**

---

**Cause:** This Access Server Id does not exist in OAM

**Action:** Make sure that the Access Server Id passed is present in OAM

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60070: The param, {0}, contains some values that are not valid. Check log for details**

**Cause:** Some of the Access Server Id's mentioned are not valid

**Action:** Make sure that the Access Server Id's mentioned are all valid

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60071: The transport security mode of WebGate, {0}, differs from Access Server, {1}**

**Cause:** There is a transport security mismatch

**Action:** Make sure the transport security matches between the WebGate and Access Server

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60072: The Access Management Service mode of WebGate, {0}, differs from Access Server, {1}**

**Cause:** There is a mismatch between Access Management Service modes

**Action:** Make sure the Access Management Service matches between the WebGate and Access Server

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60073: {0} has been specified as part of both Primary and Secondary server params**

**Cause:** Same value has been specified as part of both Primary and Secondary servers

**Action:** Make sure that you have unique values for both Primary and Secondary Servers

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OAMCFG-60074: The value, {0}, has been specified more than once in a comma separated input parameter**

**Cause:** Duplicate values have been provided in one of the input parameters

**Action:** Make sure that you have unique values specified as part of input parameters

---

**Level: 1**

**Type: ERROR**

**Impact: Data**

**OAMCFG-60075: The provided parameter, {0}, is not a valid integer**

**Cause:** An invalid integer was passed

**Action:** Make sure the value provided is a valid integer

**Level: 1**

**Type: ERROR**

**Impact: Data**

**OAMCFG-60076: The URL for Impersonation Consent Form is mandatory**

**Cause:** The URL for Impersonation Consent Form has not been passed

**Action:** Make sure you provide a URL for Impersonation Consent Form

**Level: 1**

**Type: ERROR**

**Impact: Data**

**OAMCFG-60077: The path to the Impersonation Authz Plugin is mandatory**

**Cause:** The path to the Impersonation Authz Plugin has not been passed

**Action:** Make sure you provide a path to the Impersonation Authz Plugin

**Level: 1**

**Type: ERROR**

**Impact: Data**

**OAMCFG-60078: Impersonation Authz Scheme has not been configured and hence would not be used**

**Cause:** Impersonation Authz Scheme has not been configured

**Action:** Configure the Impersonation Authn/ Authz plugins, if required

**Level: 1**

**Type: ERROR**

**Impact: Data**

**OAMCFG-60079: The Authz rule, {0} already exists for this app domain, {1}**

**Cause:** Authz rules already exists

**Action:** No action needs to be taken.

**Level: 1**

**Type: ERROR**

**Impact: Data**

**OAMCFG-60080: Authorization scheme, {0}, does not exist**

**Cause:** Authorization scheme, {0}, does not exist

**Action:** Specify a valid Authorization Scheme

**Level: 1**

---

**Type:** ERROR  
**Impact:** Data





---

## OAMSSA-00001 to OAMSSA-16006

**OAMSSA-00001: Service provider configuration {0} is not valid.**

**Cause:** The service provider configuration in the system configuration was invalid.

**Action:** Verify the identity and registration service provider configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-00002: Cannot instantiate service provider.**

**Cause:** The service provider configuration was invalid.

**Action:** Verify the identity and registration service provider configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-00003: Identity service configuration is not valid.**

**Cause:** The identity service configuration was invalid.

**Action:** Verify the identity service configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-00004: User self service configuration is not valid.**

**Cause:** The user self service configuration was invalid.

**Action:** Verify the user self service configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-00005: Identity Manager Integration is enabled {0}.**

**Cause:**

**Action:**

**Level:** 15

---

**Type:** INFO  
**Impact:** Other  
**OAMSSA-00006: User Self Service is enabled {0}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAMSSA-00007: Policy Evaluation result {0}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAMSSA-00008: Constructed URL {0}.**  
**Cause:**  
**Action:**  
**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAMSSA-00114: no LdapCtxFactory available**  
**Cause:** No LdapCtxFactory available  
**Action:** Ensure that an LDAP Context factory is available and configured.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**OAMSSA-00115: cannot instantiate LdapCtxFactory {0}, exception: {1}**  
**Cause:** An attempt to instantiate LdapCtxFactory failed.  
**Action:** Ensure that LdapCtxFactory is available.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**OAMSSA-00116: cannot instantiate user-specified LdapCtxFactory: {0}**  
**Cause:** An attempt to instantiate a user-specified LdapCtxFactory failed.  
**Action:** Ensure that the external LdapCtxFactory is available and properly configured.  
**Level:** 1  
**Type:** ERROR

---

**Impact:** Configuration

**OAMSSA-00118: specifying invalid load balancing policy: {0}**

**Cause:** An invalid load balancing policy was specified.

**Action:** Ensure that load balancing policy is properly configured and conforms to correct interface.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OAMSSA-00121: specifying invalid abandoned connection timeout: {0}**

**Cause:** An invalid abandoned connection timeout value was specified.

**Action:** Ensure that abandoned connection timeout value is in acceptable range.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OAMSSA-00122: specifying invalid connection harvest maximum count: {0}**

**Cause:** An invalid connection harvest max count was specified.

**Action:** Ensure that invalid connection harvest max count is in acceptable range.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OAMSSA-00123: specifying invalid connection harvest trigger count: {0}**

**Cause:** An invalid connection harvest trigger count was specified.

**Action:** Ensure that invalid connection harvest trigger count is in acceptable range.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OAMSSA-00124: specifying invalid connection wait timeout: {0}**

**Cause:** An invalid connection wait timeout was specified.

**Action:** Ensure that invalid connection wait timeout is in acceptable range.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OAMSSA-00125: Failover option {0} is not supported for this pool.**

**Cause:** An invalid failover value was specified.

**Action:** Ensure that invalid failover value is consistent with pool.

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**OAMSSA-00126: specifying invalid inactive timeout value: {0}**

**Cause:** An invalid inactive connection timeout value was specified.

**Action:** Ensure that inactive connection timeout value is in acceptable range.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OAMSSA-00127: specifying invalid initial pool size: {0}**

**Cause:** An invalid initial pool size setting was specified.

**Action:** Ensure that initial pool size setting is in acceptable range.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OAMSSA-00128: specifying invalid maximum pool size: {0}**

**Cause:** An invalid maximum pool size setting was specified.

**Action:** Ensure that maximum pool size is in acceptable range.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OAMSSA-00129: specifying invalid minimum pool size: {0}**

**Cause:** An invalid minimum pool size setting was specified.

**Action:** Ensure that minimum pool size is in acceptable range.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OAMSSA-00130: Run-time load balancing setting {0} is not supported for this pool.**

**Cause:** An invalid run-time load balancing setting was specified.

**Action:** Ensure that run-time load balancing setting is consistent with pool.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OAMSSA-00131: specifying invalid timeout check interval: {0}**

**Cause:** An out of range invalid timeout check interval was specified.

**Action:** Ensure that timeout check interval is in acceptable range.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OAMSSA-00132: specifying invalid time-to-live value: {0}**

---

**Cause:** An out of range time-to-live-value was specified.

**Action:** Ensure that the time-to-live value is in an acceptable range.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OAMSSA-00134: failure of pool {0} to start**

**Cause:** The LDAP connection pool did not start.

**Action:** Ensure the pool is properly configured.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-00138: Invalid configuration for maximum connection reuse count: {0}**

**Cause:** An invalid maximum connection reuse count value was specified.

**Action:** Ensure that maximum connection reuse count value is in acceptable range.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OAMSSA-00139: Invalid configuration for maximum connection reuse time: {0}**

**Cause:** An invalid maximum connection reuse time value was specified.

**Action:** Ensure that maximum connection reuse time value is in acceptable range.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OAMSSA-02001: Session not found for sessionid: {0}**

**Cause:** Requested session object has expired, has been deleted, or does not exist.

**Action:** Verify that the session exists before making the call.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-02002: Session not found for userid: {0} and sessionindex: {1}**

**Cause:** The requested session object has expired, has been deleted, or does not exist.

**Action:** Verify that the session exists before making the call.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-02003: Cannot find method {0} on class {1}**

---

**Cause:** An attempt was made to access a method that does not exist.

**Action:** Verify that the method exists before making the call.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-02004: Cannot to execute method {0} on class {1}**

**Cause:** An attempt to execute a method that is not supported.

**Action:** Use a supported method.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-02006: SessionManager type not present: {0}**

**Cause:** The requested implementation was not specified in configuration files.

**Action:** Add the SessionManager type to the configuration files

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-02007: Factory class does not have factory methods.**

**Cause:** Factory class does not have factory methods.

**Action:** None.

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAMSSA-02008: Cannot instantiate the persistence access implementation for class {0}.**

**Cause:** An attempt was made to instantiate an invalid persistence access implementation.

**Action:** Verify the settings in the configuration file.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-02009: Cannot extract attribute for method {0}.**

**Cause:** An incorrect method was used to extract an attribute value.

**Action:** Use the correct API call.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-02010: UpdateProcessor is in invalid mode for entry {0}.**

---

**Cause:** UpdateProcessor serialization failure.

**Action:** Verify the configuration files, and the deployment.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-02011: Cannot update attribute for method {0}.**

**Cause:** An incorrect method was used to update the attribute value.

**Action:** Use the correct API call.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-02012: Session count for user {0} has reached the maximum session limit per user.**

**Cause:** Session count for user has reached the maximum session limit per user.

**Action:** Log out of some of the sessions before attempting to create new sessions.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-02013: SME expired session reaper thread not started: failed to get the MBean server instance.**

**Cause:** MBean server not available.

**Action:** Verify that the server started without errors.

**Level:** 15

**Type:** WARNING

**Impact:** Other

**OAMSSA-04001: Operation {0} is not supported.**

**Cause:** The requested operation was not supported.

**Action:** Use a supported operation.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-04002: Incorrect number of parameters {0} passed for operation {1}**

**Cause:** An incorrect number of parameters was passed to the expression builder.

**Action:** Pass the correct number of parameters required for the expression.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-04003: Unable to get data store instance.**

---

**Cause:** An invalid configuration file was supplied.

**Action:** Verify the configuration file.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-04004: Cannot get extractor list from passed configuration.**

**Cause:** An incorrect extractor list was supplied.

**Action:** Verify the supplied configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-04005: Data store established but data connection cannot be made.**

**Cause:** Database connection information was invalid.

**Action:** Verify configuration files.

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAMSSA-04006: Cannot get connection from data source.**

**Cause:** Data source configuration was invalid.

**Action:** Verify configuration files.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-04007: Key is not unique: {0}**

**Cause:** The key in the database was not unique.

**Action:** Verify data integrity.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-04008: Data source definition not found. Store will be in-memory only.**

**Cause:**

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAMSSA-04009: Invalid parameter type passed to construct {0}**

**Cause:** The function parameter type was invalid.

**Action:** Verify client implementation.



---

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-04010: OAM Configuration for Coherence property {0} not found. Default configuration will be used.**

**Cause:** No overrides were specified.

**Action:** None.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-04011: Cannot resolve address for server instance {0}.**

**Cause:** Server Instance listed in the Configuration is invalid.

**Action:** Correct the configuration and rerun the operation.

**Level:** 15

**Type:** WARNING

**Impact:** Other

**OAMSSA-04012: Cannot set local host values for this server instance.**

**Cause:** Unable to set permissions for local host.

**Action:** Please verify the network configuration and rerun this operation.

**Level:** 15

**Type:** WARNING

**Impact:** Other

**OAMSSA-04013: Coherence property type update is not supported for property {0}.**

**Supported types include String, Integer, Boolean.**

**Cause:** An unsupported Coherence configuration property type was specified.

**Action:** Use a supported Coherence configuration property type.

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAMSSA-04014: Cannot set override properties for Coherence due to exception.**

**Cause:** The supplied Coherence configuration properties are invalid.

**Action:** Correct the configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-04015: Datasource not found for provided name {0}.**

**Cause:** The supplied Datasource name is invalid.

**Action:** Correct the configuration.

---

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-04016: Cannot store key {0} in data store.**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-04017: Cannot erase key {0} in data store.**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-04018: Cannot get Iterator of keys from data store.**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-04019: Cannot acquire distribution lock.**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-04020: Distribution version is {0}. Version requested for distribution is {1}.**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-04021: Exception on finalize of component {0}.**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 15

---

**Type:** ERROR  
**Impact:** Other  
**OAMSSA-04022: Exception on bootstrap of component {0}.**  
**Cause:** An internal error occurred.  
**Action:** For more details, start logging at the FINE level.  
**Level:** 15  
**Type:** ERROR  
**Impact:** Other  
**OAMSSA-04023: Cannot initialize configuration.**  
**Cause:** An internal error occurred.  
**Action:** For more details, start logging at the FINE level.  
**Level:** 15  
**Type:** ERROR  
**Impact:** Other  
**OAMSSA-04024: Stale data exception encountered for config version {0}.**  
**Cause:** An internal error occurred.  
**Action:** For more details, start logging at the FINE level.  
**Level:** 15  
**Type:** ERROR  
**Impact:** Other  
**OAMSSA-04025: Distribution event of version {0} received for config of version {1}.**  
**Cause:** An internal error occurred.  
**Action:** For more details, start logging at the FINE level.  
**Level:** 15  
**Type:** ERROR  
**Impact:** Other  
**OAMSSA-04026: Received null object as distribution event.**  
**Cause:** A null object was received as the distribution event.  
**Action:** Verify the distributed data at the origin.  
**Level:** 15  
**Type:** ERROR  
**Impact:** Other  
**OAMSSA-04027: Cannot handle distribution notification.**  
**Cause:** An internal error occurred.  
**Action:** For more details, start logging at the FINE level.  
**Level:** 15  
**Type:** ERROR  
**Impact:** Other

---

**OAMSSA-04028: Cannot acquire lock for configuration update.**

**Cause:** Unable to acquire lock for configurable update.

**Action:** Identify source of contention and remove it.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-04029: Cannot upload physical file change to configuration.**

**Cause:** Unable to upload physical file change to configuration.

**Action:** Verify that the physical file is well formed.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-04030: Mxbean attribute is null.**

**Cause:** The Mxbean attribute was null.

**Action:** Size of document may be large causing this failure.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-04031: Cannot handle config change notification.**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-04032: Incorrect type of parameters {0} passed for operation {1}.**

**Cause:** An invalid parameter type was passed to the expression builder.

**Action:** Pass the correct parameters required for the expression.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-04033: Failed to get encryption key.**

**Cause:** Shared Key for encryption not found.

**Action:** Verify that installation completed without errors.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-06014: Unable to initialize Policy Runtime Provider.**

**Cause:** An invalid configuration.

---

**Action:** Try again by setting proper configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06015: Exception encountered while processing get authentication scheme request!**

**Cause:** An internal exception occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06016: Unable to reload the policy data for runtime.**

**Cause:** An internal exception occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06017: Exception encountered while creating runtime responses.**

**Cause:** An internal exception occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06018: Unable to load cache.**

**Cause:** An internal exception occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06019: Unable to load host identifiers from policy store.**

**Cause:** An internal exception occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06020: Exception encountered while evaluating authentication policy.**

**Cause:** An internal exception occurred.

**Action:** For more details, start policy logging at FINE level.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06021: Unable to obtain constraints from authorization policy.**

**Cause:** No constraints were found.

**Action:** Check if policy has constraints and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06022: Unable to obtain InetAddress from given IP Address.**

**Cause:** An invalid IP Address was supplied.

**Action:** Check if the IP Address is valid (Only IP version 4 is supported). Try again with valid IP Address.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06023: Unable to match a host identifier for the input resource: request={0}.**

**Cause:** No host identifier was configured for incoming resource.

**Action:** Update the policy, add the host identifier to the given resource and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06024: Unable to process Runtime Resource for getting URL path.**

**Cause:** An invalid incoming resource URL.

**Action:** Correct the resource URL and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06025: Exception encountered while adding to the bucket.**

**Cause:** An internal exception occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06026: Object {0} with the name already exists.**

**Cause:** That name has already been used to create an object.

**Action:** Modify the name and try to create the object once again.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06027: Error while creating input stream for the policy file.**

**Cause:** An internal error occurred. One of the many cause can be policy file not found.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06028: Error while creating a new policy distributor instance.**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06029: ID of an element cannot be NULL.**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06030: Error while retrieving DATA SOURCE and RESPONSE TYPE values from policy.xml!**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06031: Error while reading ConstraintClass, ConstraintType from the constraint template. The type and class maybe incorrect.**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06032: Error while creating jaxb marshaller/unmarshaller.**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06033: Error while unmarshalling. Data may be corrupt in policy.xml**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06034: Policy data write failed with exception.**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06035: Error while creating input stream for policy file.**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06036: Cannot find the file "{0}" in the classpath or on the filesystem**

**Cause:** The policy file was not in the classpath.

**Action:** Add policy file to the classpath and run the program again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06037: XML data validation Error. Data in the input XML String maybe corrupt.**

**Cause:** The policy file was invalid.

**Action:** Validate policy file against the schema and run the program again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06038: Validation Error while unmarshalling. Data in the input XML String maybe corrupt.**

**Cause:** The policy file was invalid.

**Action:** Validate policy file against the schema and run the program again.



---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06039: Cannot create temporal constraint. Require either DayOfWeek or TimeOfDay.**

**Cause:** The attribute required to create a temporal constraints was not valid.

**Action:** Either DayOfWeek or TimeOfDay is missing. Add the required attribute and run the program again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06040: Invalid ConstraintClass in policy.xml :: classIs="{0}"**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06041: Unable to distribute policy changes.**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06042: NULL passed during modify operation.**

**Cause:** Object passed to modify operation was null.

**Action:** Rerun with actual object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06043: Validation Failure - name cannot be NULL.**

**Cause:** During object creation, name value was null.

**Action:** Rerun the operation with a valid name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06044: Validation Failure - name {0} exceeds maximum allowed length of {1} characters.**

**Cause:** During object creation, invalid name attribute was passed.

**Action:** Rerun the operation with a valid name attribute.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06045: Validation Failure - an object of this type named "{0}" already exists.**

**Cause:** Policy object names must be unique for each object type and scope (global or domain).

**Action:** Choose a different name for this object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06046: Validation failure - Mandatory attribute "{0}" is missing.**

**Cause:** A required attribute was missing during policy object creation.

**Action:** Rerun the operation with the required attribute. When authn-level is the required attribute, set a positive value and rerun the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06047: Validation Failure - "name" or "description" attribute missing in Module Property.**

**Cause:** A name or description attribute was missing in a module property.

**Action:** Rerun the operation with required attribute set.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06048: Validation Failure - Object not found for deletion.**

**Cause:** Incorrect data was sent for the deletion operation.

**Action:** Rerun the operation with with proper data.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06049: Validation Failure - Module cannot be deleted. (Referred in Scheme).**

**Cause:** Module is being referred to in the scheme.

**Action:** Remove the reference from the scheme and then delete the module.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06050: NULL passed during isDefaultAuthnScheme operation.**

---

**Cause:** Null passed while performing the default authn scheme operation.

**Action:** Rerun the operation with the valid scheme.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06051: Validation failure - One of the challenge parameter key values is empty.**

**Cause:** A challenge param key value was empty.

**Action:** Set the proper key value and then rerun the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06052: Challenge URL is invalid.**

**Cause:** An invalid Challenge URL was entered.

**Action:** Rerun the operation with valid challenge URL value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06053: Validation Failure - Challenge URL is null.**

**Cause:** The URL entered is null.

**Action:** Re-run the operation with a valid URL value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06054: Validation failure - Scheme referring to invalid authentication module.**

**Cause:** The scheme was referring to an invalid authentication module.

**Action:** Rerun the operation after setting a valid authentication module.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06055: Validation Failure - Scheme cannot be deleted. Referenced in an existing authentication policy.**

**Cause:** The scheme is being referred to in a policy.

**Action:** Remove the reference from the policy and then delete the scheme.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**OAMSSA-06056: Validation Failure - default authentication scheme cannot be deleted.**

**Cause:** An attempt was made to delete the default authentication scheme, which is not allowed.

**Action:** Rerun the operation with another authentication scheme.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06057: Validation failure - Invalid host format.**

**Cause:** The host format was invalid.

**Action:** Rerun the operation with a valid host.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06058: Validation Failure - host "{0}" is already part of another host identifier("{1}").**

**Cause:** The host is already part of a HostIdentifier.

**Action:** Rerun the operation with a different HostIdentifier.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06059: Validation Failure - Host Identifier cannot be deleted. (Referred to in a resource).**

**Cause:** Host is being referred to in a resource.

**Action:** Remove the reference from the resource and then delete the host.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06060: Resource ["url={0}", "hostIdentifierName={1}"] not found within Application Domain.**

**Cause:** The referred to resource is not present in the application domain.

**Action:** Rerun the test by referring to a resource in the same application domain.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06061: Validation Failure - Resource ["url={0}"] is referred to in another authentication policy ["referredPolicyName={1}"].**

**Cause:** The resource is already being referred to in an authentication policy.

**Action:** Rerun the operation after removing the resource from the authentication policy which currently refers to it.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06062: Validation Failure - Resource ["url={0}"] is referred to in another authorization policy ["referredPolicyName={1}"].**

**Cause:** The resource is already being referred to in an authorization policy.

**Action:** Rerun the operation after removing the resource from the authorization policy which currently refers to it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06063: Validation failure - Invalid operation format.**

**Cause:** The operation list was invalid.

**Action:** Rerun the operation with a valid operation list.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06064: Validation Failure - HostIdentifier is null.**

**Cause:** A null HostIdentifier was passed to the operation.

**Action:** Rerun the operation with a valid host identifier.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06065: Validation Failure - Invalid HostIdentifier.**

**Cause:** No HostIdentifier was found in the policy.

**Action:** Rerun the operation with a valid host identifier.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06067: Resource URL format is not valid.**

**Cause:** URL \* was not followed by a .extension, or URL pattern (\*any string) \* was not followed by a character string, or URL \* was preceded by a string (e.g. checking\*.jsp is invalid), or URL pattern was invalid (e.g. "..." pattern is only allowed once).

**Action:** Rerun the operation with a valid resource url.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06068: Validation Failure - Cannot delete resource ["url={0}"]. Referred to in Authentication Policy ["referredPolicyName={1}"]**

---

**Cause:** The resource to be deleted was referred to in an authentication policy.  
**Action:** Delete the resource from the authentication and then rerun the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06069: Validation Failure - Cannot delete resource ["url={0}"]. Referred to in Authorization Policy ["referredPolicyName={1}"]**

**Cause:** The resource to be deleted was referred to in an authorization policy.

**Action:** Delete the resource from the authorization policy and then rerun the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06070: Unable to obtain policy manager for application domain id: "{0}"**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06071: Temporal constraint validation failure for {0}.**

**Cause:** Missing DayOfWeek or TimeOfDay required to create temporal constraint, or no day selected in DayOfWeek constraint, or Begin/End time not supplied for Temporal Constraint, or End time is less than Begin time.

**Action:** Rerun the operation with a valid temporal constraint.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06072: Identity constraint validation failure for {0}.**

**Cause:** User or group list was not supplied for identity constraint creation, or users list was empty, or group list was empty.

**Action:** Rerun the operation with a valid temporal constraint.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06073: IP4Range constraint validation failure for {0}.**

**Cause:** A null value was present in either start or end range.

**Action:** Rerun the operation with valid a temporal constraint.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**OAMSSA-06074: {0} does not exist, id = {1}**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06075: Unable to obtain a host identifier for the input name : hostIdName = {0}.**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06076: Time of Day Constraint is not created as either beginTime or endTime is missing.**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06077: Cannot create Constraint object.**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06078: Error while creating Constraint of type: "{0}", class: "{1}".**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06079: Error while reading response with name = "{0}".**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**OAMSSA-06080: Error while creating response from policy store object with name = "{0}".**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06081: Cannot open file.**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06082: Exception occurred while converting admin elements to runtime elements.**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06083: No Client IPAddress found in AccessContext Map.**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06084: Null Authentication Scheme Id.**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06085: Constraints not supported for Authentication Policy. Pass null during Constraint creation.**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR



---

**Impact:** Other

**OAMSSA-06086: OAM Admin Provider class not found : "{0}".**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06087: Unable to instantiate OAM Provider class : "{0}".**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06088: OAM provider class in the configuration does not implement PolicyAdminProvider: "{0}".**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06089: OAM Runtime Provider class not found : "{0}".**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06090: Unable to instantiate OAM Runtime Provider class : "{0}".**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06091: OAM provider class in the configuration does not implement PolicyRuntimeProvider: "{0}".**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**OAMSSA-06093: Error while reading policy result cache size from configuration.**

**Cause:** Cache configuration was invalid.

**Action:** Fix the cache configuration and the rerun the operation.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-06098: Validation Failure - Resource "{0}" already exists in policy "{1}".**

**Cause:** The resource already exists as part of an Authentication/ Authorization Policy.

**Action:** Rerun the operation using another resource.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06099: Validation Failure - Response "{0}" already exists in policy "{1}".**

**Cause:** The response already exists as part of an Authentication/ Authorization Success/Failure List.

**Action:** Rerun the operation using another response.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06100: Validation Failure - Constraint "{0}" already exists in policy "{1}".**

**Cause:** The constraint already exists as part of an Authorization policy.

**Action:** Rerun the operation using another constraint.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06102: Unable to process policy change event for change record number: "{0}".**

**Cause:** An internal exception occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06103: Unable to acquire write lock on the XML policy store file, for change record number: "{0}".**

**Cause:** The XML policy store file is locked by another thread for more than the configured wait time.

**Action:** For more details, start policy logging at FINE level.

---

**Level: 1**

**Type: ERROR**

**Impact: Other**

**OAMSSA-06104: Success URL is invalid.**

**Cause:** The success redirect URL was invalid..

**Action:** Rerun the operation with a valid URL.

**Level: 1**

**Type: ERROR**

**Impact: Other**

**OAMSSA-06105: Failure URL is invalid.**

**Cause:** The failure redirect URL was invalid.

**Action:** Rerun the operation with a valid URL.

**Level: 1**

**Type: ERROR**

**Impact: Other**

**OAMSSA-06106: Resource URL is invalid.**

**Cause:** The resource URL entered is invalid.

**Action:** Re-run the operation with valid resource URL value.

**Level: 1**

**Type: ERROR**

**Impact: Other**

**OAMSSA-06107: Validation Failure - description for field {0} exceeds maximum allowed length of {1} characters.**

**Cause:** During object creation, invalid description attribute is passed.

**Action:** Re-run the operation with valid description attribute.

**Level: 1**

**Type: ERROR**

**Impact: Other**

**OAMSSA-06108: Validation Failure - operation list is empty.**

**Cause:** During object creation, invalid operation list attribute is passed.

**Action:** Re-run the operation with valid operation list attribute.

**Level: 1**

**Type: ERROR**

**Impact: Other**

**OAMSSA-06109: Resources belonging to a policy must be of the same type.**

**Cause:** The policy already contains resources of another type.

**Action:** Apply the resource to a different policy.

**Level: 1**

---

**Type:** ERROR

**Impact:** Other

**OAMSSA-06110: Resource type must not be null.**

**Cause:** Resource type must not be null.

**Action:** Set the resource type.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06111: Unable to find HTTP resource type.**

**Cause:** The required HTTP resource type does not exist.

**Action:** Create a new resource type with name "HTTP".

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06112: Application Domain should be empty before it is deleted.**

**Cause:** Application Domain is not empty.

**Action:** Delete all resources and policies in an application domain before deleting the domain.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06113: The resource URL cannot contain a query string.**

**Cause:** The resource URL cannot contain a query string.

**Action:** Remove the query string component from the resource URL.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06114: The requested method is not supported by this policy object type.**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-06115: An unsupported operation was unexpectedly requested.**

**Cause:** An internal error occurred.

**Action:** For more details, start policy logging at FINE level.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**OAMSSA-06116: Validation Failure - a host identifier or resource type named "{0}" already exists.**

**Cause:** Names of host identifiers or resource types must be unique across both sets of objects.

**Action:** Choose a different name for this object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-08001: Cannot get {0} value from configuration for key {1}. Object {2} found.**

**Cause:** An attempt was made to access a configuration setting that does not exist.

**Action:** Verify configuration file.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08002: Cannot get wrapper class instance.**

**Cause:** An attempt was made to access a wrapper class instance that does not exist.

**Action:** Verify configuration file.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08003: Type in configuration is not supported by utility for updates: {0}.**

**Cause:** An invalid configuration type was specified.

**Action:** Verify configuration file.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08004: Implementation type {0} not present in path {1}.**

**Cause:** The requested implementation was not specified in configuration file.

**Action:** Verify configuration files.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08005: Cannot get implementation for type {0}.**

**Cause:** The requested implementation was not specified in configuration file.

**Action:** Verify configuration files.

**Level:** 15

---

**Type:** ERROR  
**Impact:** Other  
**OAMSSA-08006: Factory methods not declared for type: {0}.**  
**Cause:** None.  
**Action:** None.  
**Level:** 15  
**Type:** INFO  
**Impact:** Other  
**OAMSSA-08007: Cannot find file {0} in the classpath or on the filesystem.**  
**Cause:** The configuration file was not found.  
**Action:** Verify the configuration file location.  
**Level:** 15  
**Type:** ERROR  
**Impact:** Other  
**OAMSSA-08008: No parameters are defined for method {0}.**  
**Cause:** An invalid configuration definition was supplied.  
**Action:** Correct the configuration definition.  
**Level:** 15  
**Type:** ERROR  
**Impact:** Other  
**OAMSSA-08009: Cannot retrieve method {0} from class {1} for setting {2}. Loading MethodObject instead.**  
**Cause:** An invalid configuration definition was supplied.  
**Action:** Correct the configuration definition.  
**Level:** 15  
**Type:** ERROR  
**Impact:** Other  
**OAMSSA-08010: Cannot notify listener of file {0}.**  
**Cause:** Notification error.  
**Action:** Verify if notification listener is valid.  
**Level:** 15  
**Type:** ERROR  
**Impact:** Other  
**OAMSSA-08011: Unknown file notification error.**  
**Cause:** File notifier error.  
**Action:** Verify file change notification listeners.  
**Level:** 15  
**Type:** ERROR

---

**Impact:** Other

**OAMSSA-08012: Stale data exception encountered for configuration version {0}.**

**Cause:** File version is old.

**Action:** Refresh to the latest file version.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08013: Configuration update failed with errors.**

**Cause:** Configuration update failed.

**Action:** Correct the cause of update failure.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08014: Configuration path is null.**

**Cause:** Request path value is null.

**Action:** Provide the path parameter in method call.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08015: Configuration initial load failed.**

**Cause:** Initial load of configuration failed.

**Action:** Verify that the configuration file exists and is valid.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08016: Configuration does not exist for path {0}.**

**Cause:** Configuration for the path was null.

**Action:** Verify the path provided.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08017: Element {0} is not a map.**

**Cause:** Configuration for the path was invalid.

**Action:** Verify the path.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08018: Instance identifier is null.**

---

**Cause:** The input parameter was invalid.

**Action:** Validate the input parameter.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08019: Component at path {0} must contain Global, Profile, and Instance sections.**

**Cause:** The configuration path was invalid.

**Action:** Validate the input parameter.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08020: File is locked for updates by context {0}.**

**Cause:** An attempt was made to update a locked file.

**Action:** Release the lock before updating file from another context.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08021: Cannot acquire notification lock.**

**Cause:** Lock is being held by other configuration service instances.

**Action:** Retry after a delay.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08022: Cannot apply compensating transaction on version:{0}.**

**Cause:** Failure is due to a cause that does not allow restoration of original values.

**Action:** Verify file system.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08023: Instance at {0} does not specify a {1}.**

**Cause:** Server instance definition incorrect.

**Action:** Correct the definition in the configuration file.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08024: Element type of xsd:string required at path {0}{1}{2}.**

**Cause:** Server instance profile type should be of type string.



---

**Action:** Correct the definition in the configuration file.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08025: Profile {0} specified by {1} does not exist.**

**Cause:** Server instance profile does not exist.

**Action:** Correct the definition in the configuration file.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08026: Profile {0} specified by {1} should be of type htf:map.**

**Cause:** Server instance profile should be of type map.

**Action:** Correct the definition in the configuration file.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08027: Global section under {0} should be of type htf:map.**

**Cause:** Server global section should be of type map.

**Action:** Correct the definition in the configuration file.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08028: Error parsing the configuration file.**

**Cause:** Error parsing the configuration file.

**Action:** Verify the configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08029: Configuration file open error.**

**Cause:** An error occurred when opening the file.

**Action:** Verify the file location. Ensure that it is on the classpath or that its location is defined as a system property.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08030: Cannot get xml for configuration.**

**Cause:** Cannot get xml for configuration.

**Action:** Correct the error indicated by the exception.

---

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08031: Cannot load configuration from InputStream.**

**Cause:** Cannot load configuration from InputStream.

**Action:** Correct the error indicated by the exception.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08032: Configuration event dispatch failed.**

**Cause:** Dispatch of the configuration event failed.

**Action:** Correct the error indicated by the exception.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08033: Settinghandler not found for type: {0}.**

**Cause:** Configuration setting does not have a corresponding handler.

**Action:** Verify that the setting type is defined correctly.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08051: Configuration file is not loaded.**

**Cause:** Configuration file was not loaded. See exception for cause.

**Action:** Correct the configuration file if it is badly formed.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08052: Configuration model is not found for object type {0}.**

**Cause:** Configuration file was not loaded. See exception for cause.

**Action:** Correct the configuration file if it is badly formed.

**Level:** 15

**Type:** WARNING

**Impact:** Other

**OAMSSA-08053: Error during construction of configuration model instantiation.**

**Cause:** Invalid configuration data.

**Action:** Verify the configuration data for correctness.

**Level:** 15

**Type:** ERROR

---

**Impact:** Other

**OAMSSA-08054: Configuration file is not saved.**

**Cause:** Configuration file was not saved. See exception for cause.

**Action:** Correct the configuration file if it is badly formed.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08055: Configuration file does not support List of Lists construct.  
Ignoring element {0}.**

**Cause:** Configuration file has an unsupported data construct.

**Action:** Correct the configuration file if it is badly formed.

**Level:** 15

**Type:** WARNING

**Impact:** Other

**OAMSSA-08056: Path {0} and key set in the CompositeData {1} do not match.**

**Cause:** Call made with inconsistent data.

**Action:** Correct the parameters of the call.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08057: Single valued data type found for multi-valued property on key {0}.**

**Cause:** Call made on invalid data type

**Action:** Correct the parameters of the call.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08058: Multi-valued data type found for single valued property on key {0}.**

**Cause:** Call made on invalid data type.

**Action:** Correct the parameters of the call.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08059: Operation returned type {0}. Expecting type {1}.**

**Cause:** Property type accessed not found.

**Action:** Use the correct operation for the type.

**Level:** 15

**Type:** ERROR

---

**Impact:** Other

**OAMSSA-08060: Cannot apply document to configuration. Exception message is {0}.**

**Cause:** Document application failed.

**Action:** Use the correct operation for the type.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08061: Jar definitions provided for path {0} are invalid.**

**Cause:** The path does not exist, or the jars are missing.

**Action:** Correct the configuration file with the right values.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08062: Jar definition {0} provided is invalid.**

**Cause:** The path does not exist, or the jar is missing.

**Action:** Correct the configuration file with the right value.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08063: Distribution event of version {0} received for configuration of version {1}.**

**Cause:** Distribution values are not updated with latest configuration settings.

**Action:** Restart the server to ensure that it is synchronized with other servers.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08064: Received null object as distribution event.**

**Cause:** Some server has not placed the document on the distributor.

**Action:** Locate the server and restart it.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08065: Cannot handle distribution notification.**

**Cause:** An unexpected failure.

**Action:** Diagnose the problem from the stacktrace and address it.

**Level:** 15

**Type:** ERROR

**Impact:** Other

---

**OAMSSA-08066: Cannot find the map for key {0}**

**Cause:** An attempt was made to add a value to a map that does not exist.

**Action:** Ensure that the map exists before adding the property for the map

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-08067: Invalid data {0} provided for time interval**

**Cause:** Invalid data provided for construction of time interval.

**Action:** Correct the data in the configuration file.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-10001: SSO server token parsing failed.**

**Cause:** The SSO server token was invalid.

**Action:** Verify the server token key size and algorithm configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-10002: SSO server token Marshaling failed.**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-10003: SSO Session is not valid.**

**Cause:** The SSO session was missing, has been deleted, or has expired.

**Action:** For more details, start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-10004: Initialization of the SME adapter failed.**

**Cause:**

**Action:**

**Level:** 1

**Type:** INFO

**Impact:** Other

**OAMSSA-10005: Initialization of the PAT Adapter failed.**

**Cause:**

---

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAMSSA-10006: Initialization of the SSO Engine is complete.**

**Cause:**

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAMSSA-12001: CSS Toolkit location {0} is invalid.**

**Cause:** The CSS Toolkit location does not exist, or was not valid.

**Action:** Verify the CSS Toolkit location in the configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-12002: CSS Configuration is not valid.**

**Cause:** The CSS configuration in the configuration was invalid.

**Action:** Verify the CSS Toolkit location and configuration.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-12003: Cannot initialize CSS Authentication Module.**

**Cause:** The CSS Authentication module configuration was invalid.

**Action:** Check the CSS Authentication module configuration. Verify the Identity store properties like DN, User and Search-bases.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-12004: Authentication using CSS Authentication Module failed.**

**Cause:** An internal error occurred.

**Action:** Check the CSS Authentication module configuration. Verify the Identity store properties like DN, User and Search-bases.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-12005: Authentication Subject {0}.**

**Cause:**

---

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAMSSA-12006: Server Instance Name {0}.**

**Cause:**

**Action:**

**Level:** 15

**Type:** INFO

**Impact:** Other

**OAMSSA-12102: Failed to initialize Authentication Engine Controller.**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-12104: Authentication Module Executor is unable to get configuration parameters.**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**OAMSSA-12105: Cannot initialize authentication scheme executor.**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**OAMSSA-12106: Authentication Failed.**

**Cause:** The authentication was not successful.

**Action:** For more details, start logging at the FINE level.

**Level:** 1

**Type:** TRACE

**Impact:** Other

**OAMSSA-12107: Invalid SPNEGO token in the request.**

**Cause:** The SPNEGO token in the incoming request was either invalid or missing.

**Action:** For more details, start logging at the FINE level.

---

**Level:** 1

**Type:** SEVERE

**Impact:** Other

**OAMSSA-12111: No user found in User Identity Store for the User certificate with certificate attribute {0} value {1}.**

**Cause:** The mapping of the user certificate to an user entry was incorrectly configured.

**Action:** Verify the configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-12112: Cannot find the certificate of the OCSP server.**

**Cause:** No OCSP server certificate was present in the keystore.

**Action:** Ensure that correct value is configured for the parameter OCSP\_SERVER\_CERT\_ALIAS.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-12113: Initialization of the X509ModuleExecutor failed.**

**Cause:** The keystore file was missing, or could not be read.

**Action:** Verify the configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-12114: Initialization of the X509ModuleExecutor failed.**

**Cause:** An internal error occurred.

**Action:** Verify the configuration setting for the CERTMAPPERCLASS parameter of X509 Authentication Module and ensure that the class is present in the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-12116: Cannot find the user certificate.**

**Cause:** An internal error occurred.

**Action:** Verify the configuration and rerun this operation using a valid user certificate.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**OAMSSA-12117: Cannot validate the user certificate.**



---

**Cause:** An internal error occurred.

**Action:** For more details, start login at the FINE level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-12118: Cannot load the configuration for authentication module {0}.**

**Cause:** An internal error occurred.

**Action:** For more details, start login at the FINE level. Check the log file and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-12119: Multiple users found in User Identity Store for the User certificate with certificate attribute {0} value {1}.**

**Cause:** The mapping of the user certificate to an user entry was incorrectly configured.

**Action:** Verify the configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OAMSSA-14002: Unable to initialize authorization engine.**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-14003: Policy runtime failed.**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-14004: Response processing failed.**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

---

**OAMSSA-16002: Initialization of Module {0} failed.**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-16003: Module {0} is null.**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-16005: Configuration Entry is null.**

**Cause:** No configuration was provided to initialize the token modules.

**Action:** Verify the configuration and rerun this operation.

**Level:** 15

**Type:** ERROR

**Impact:** Other

**OAMSSA-16006: Unable to instantiate/initialize {0} module. (class={1})**

**Cause:** An internal error occurred.

**Action:** For more details, start logging at the FINE level.

**Level:** 15

**Type:** ERROR

**Impact:** Other

---

## OBI\_OFFICE-00001 to OBI\_OFFICE-00072

**OBI\_OFFICE-00001: Access denied for user**

**Cause:** The user does not have permission to access the analysis

**Action:** Make sure the user has permission to access the analysis

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00002: Access denied to folder**

**Cause:** The user does not have permission to access the folder

**Action:** Make sure the user has permission to access the folder

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00003: The connection name already exists. Please choose a different name.**

**Cause:** A connection with this name already exists

**Action:** Choose a different name for the connection.

**Level:** 2

**Type:** Information

**Impact:** Programmatic

**OBI\_OFFICE-00004: Could not insert BI Object**

**Cause:** An error occurred while inserting the view object

**Action:** Examine the log for details on the error.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00005: Could not save as a valid connection, please enter valid connection parameters.**

**Cause:** Unable to save the invalid connection.

**Action:** Please provide the correct connection parameters and try again.

---

**Level: 2**  
**Type: Error**  
**Impact: Network**  
**OBI\_OFFICE-00006: Empty result set. No rows will be displayed.**  
**Cause:** The server returned no data.  
**Action:**

**Level: 2**  
**Type: Warning**  
**Impact: Programmatic**  
**OBI\_OFFICE-00007: Empty result set. A blank chart will be displayed.**  
**Cause:** The server returned no data.  
**Action:**

**Level: 2**  
**Type: Warning**  
**Impact: Programmatic**  
**OBI\_OFFICE-00008: Empty result set. A default chart will be inserted.**  
**Cause:** The server returned no data.  
**Action:**

**Level: 2**  
**Type: Warning**  
**Impact: Programmatic**  
**OBI\_OFFICE-00009: Error while adding image:**  
**Cause:** Failed to insert title view image  
**Action:** Examine the log for details on the error.

**Level: 2**  
**Type: Error**  
**Impact: Programmatic**  
**OBI\_OFFICE-00010: Error during Oracle BI application creation:**  
**Cause:** Unable to load Oracle BI Office Addin.  
**Action:** Examine the log for details on the error.

**Level: 2**  
**Type: Error**  
**Impact: Programmatic**  
**OBI\_OFFICE-00011: Error while inserting Filter view:**  
**Cause:** Failed to insert filter view.  
**Action:** Examine the log for details on the error.

**Level: 2**  
**Type: Error**

---

**Impact:** Programmatic

**OBI\_OFFICE-00012: Error while inserting Title view:**  
**Cause:** Failed to insert title view.  
**Action:** Examine the log for details on the error.  
**Level:** 2  
**Type:** Error  
**Impact:** Programmatic

**OBI\_OFFICE-00013: Error while creating chart:**  
**Cause:** Error occurred while inserting chart view.  
**Action:** Examine the log for details on the error.  
**Level:** 2  
**Type:** Error  
**Impact:** Programmatic

**OBI\_OFFICE-00014: Error while creating chart: Error due to edit mode!**  
**Cause:** Error occurred while inserting chart view due to edit mode.  
**Action:** Please unselect the chart and try again.  
**Level:** 2  
**Type:** Error  
**Impact:** Programmatic

**OBI\_OFFICE-00015: Error while getting clipboard content:**  
**Cause:** Unable to access Clipboard contents  
**Action:** Examine the log for details on the error.  
**Level:** 2  
**Type:** Error  
**Impact:** Programmatic

**OBI\_OFFICE-00016: Error while initializing Oracle BI Add-in:**  
**Cause:** Error while initializing Oracle BI Office addin  
**Action:** Examine the log for details on the error.  
**Level:** 2  
**Type:** Error  
**Impact:** Programmatic

**OBI\_OFFICE-00017: Error while loading Oracle BI Add-in:**  
**Cause:** Error while loading the Oracle BI Office addin  
**Action:** Examine the log for details on the error.  
**Level:** 2  
**Type:** Error  
**Impact:** Programmatic

**OBI\_OFFICE-00018: Error while naming the sheet**

---

**Cause:** A worksheet with the same name exists

**Action:** Examine the log for details on the error.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00019: Failed to connect to Server, please check the connection and try again.**

**Cause:** Server connection has become unavailable.

**Action:** Please check the server connection and try again.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00020: Failed to get child items.**

**Cause:** Unable to get Analysis/Views at this path.

**Action:** Please check the path in Answers.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00021: Failed to get child items. The folder maybe empty.**

**Cause:** Unable to get Analysis/Views as the folder might be empty.

**Action:** Please check the folder at this path and make sure it is not empty, and the user has permission to access it.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00022: Failed to insert Oracle BI view.**

**Cause:** Failed to insert the view.

**Action:** Examine the log for details on the error.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00023: Failed to insert Oracle BI view. Error due to edit mode!**

**Cause:** Error occurred while inserting the view due to edit mode.

**Action:** Please unselect the view by pressing Esc key and try again.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00024: Filter view not inserted as it is empty.**

---

**Cause:** Failed to insert filter view.

**Action:** Examine the log for details on the error.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00025: Filter view removed as it is empty.**

**Cause:** The filterview inserted was empty and therefore has been removed.

**Action:** Please make sure the filter view is not empty.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00026: Insufficient space in worksheet.**

**Cause:** The view is too large to fit into one worksheet.

**Action:** Consider using redesign the Analysis so that it fits in one worksheet. You may also consider upgrading to Office 2007.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00027: Invalid Oracle BI Office server URL or network is not available. Working offline.**

**Cause:** Network connection is not available.

**Action:** Please make sure the network connection is available and try again.

**Level:** 2

**Type:** Error

**Impact:** Network

**OBI\_OFFICE-00028: Invalid analysis definition. Analysis must have at least one dimension and one measure**

**Cause:** The analysis is invalid.

**Action:** Please make sure that the analysis contains at least one dimension and one measure.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00029: You must enter a \$1 type for \$2**

**Cause:** A wrong type value has been entered for the defined prompt column.

**Action:** Please enter a numeric value for numeric data type, or a date or datetime for date and datetime types.

**Level:** 2

**Type:** Error

---

**Impact:** Programmatic

**OBI\_OFFICE-00030: Invalid URL. Please check your Oracle BI Office server name and port number.**

**Cause:** The BI Office server connection is invalid.

**Action:** Please edit the connection to make sure that the connection parameters are correct. Test the connection and try again.

**Level:** 2

**Type:** Error

**Impact:** Network

**OBI\_OFFICE-00031: Login failed. Please check your username, password and Oracle BI Office server availability.**

**Cause:** Either the username/password is incorrect, or the server is not available.

**Action:** Please make sure the username/password is correct and the server is available. Please check 'Test Connection' in connection details dialog under Preferences.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00032: You have no access right to Oracle BI from Microsoft Office.**

**Cause:** You have no access right to Oracle BI from Microsoft Office.

**Action:** Please contact your administrator.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00033: No Oracle BI Office server connections found. Please add at least one server connection.**

**Cause:** No connections have been entered so far.

**Action:** Please follow the instructions to enter a new BIOffice server connection. You can enter or modify the connection at any time by selecting 'Preferences' from the Oracle BI menu.

**Level:** 2

**Type:** Warning

**Impact:** Programmatic

**OBI\_OFFICE-00034: No Oracle BI view in clipboard.**

**Cause:** The clipboard is either empty or does not have a BI view copied.

**Action:** Please go to Answers using your webbrowser and click on 'Copy' link displayed at the bottom on the view.

**Level:** 2

**Type:** Warning

**Impact:** Programmatic

**OBI\_OFFICE-00035: No prompts and/or levels defined.**



---

**Cause:** No prompts and/or levels defined for this analysis.

**Action:**

**Level:** 2

**Type:** Warning

**Impact:** Programmatic

**OBI\_OFFICE-00036: Only one BI Object can be edited at a time.**

**Cause:** Multiple BI views have been selected.

**Action:** Please make sure to select only one view, and then click on Edit Prompts and Levels.

**Level:** 2

**Type:** Warning

**Impact:** Programmatic

**OBI\_OFFICE-00037: Oracle BI view not found.**

**Cause:** The view no longer exists in Answers

**Action:** Please make sure that the view exists at that specified path on the server.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00038: Please enter a Office server name before test connection.**

**Cause:** A name is not entered in the BI Office server name box.

**Action:** Please enter a valid name for the BI Office server.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00039: Please select a slide before inserting an Oracle BI view.**

**Cause:** A slide has not been selected for the view to be inserted in.

**Action:** Please select a slide to insert the view into.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00040: Please select a slide to refresh.**

**Cause:** A slide has not been selected to refresh.

**Action:** Please select a slide to refresh.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00041: Port numbers 9703 and 9706 are reserved by Oracle BI EE Server. Please verify your port number.**

---

**Cause:** An invalid port number has been entered in the connection detail dialog.

**Action:** Please make sure that a valid port number (other than 9703 and 9706) have been entered in the connection detail dialog.

**Level:** 2

**Type:** Error

**Impact:** Network

**OBI\_OFFICE-00042: Analysis not found.**

**Cause:** An analysis has not been found at the specified path.

**Action:** Please make sure that the analysis exists at the specified path.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00043: Server configuration file has wrong host name.**

**Cause:** BIOffice.xml file on the BI Office server has incorrect hostname specified in the SAWBASEURL parameter.

**Action:** Please make sure the URL specified in as the SAWBASEURL in bioffice.xml file is valid and reachable.

**Level:** 2

**Type:** Error

**Impact:** Network

**OBI\_OFFICE-00044: Server configuration file has wrong port number.**

**Cause:** BIOffice.xml file on the BI Office server has incorrect port number in the SAWBASEURL parameter.

**Action:** Please make sure the URL specified in as the SAWBASEURL in bioffice.xml file is valid and reachable.

**Level:** 2

**Type:** Error

**Impact:** Network

**OBI\_OFFICE-00045: Server has wrong SSL configuration (SSL Handshake exception thrown).**

**Cause:** BIOffice.xml file on the BI Office server has incorrect SSL URL in the SAWBASEURL parameter.

**Action:** Please make sure the URL specified in as the SAWBASEURL in bioffice.xml file is valid and reachable.

**Level:** 2

**Type:** Error

**Impact:** Network

**OBI\_OFFICE-00046: Server configuration file has wrong URL, or other runtime HTTP exception has been thrown. Please check server configuration and/or server log files for more information.**

---

**Cause:** Server configuration file has wrong URL, or other runtime HTTP exception has been thrown.

**Action:** Please check server configuration and/or server log files for more information.

**Level:** 2

**Type:** Error

**Impact:** Network

**OBI\_OFFICE-00047: Selected view no longer exists on the Oracle BI server.**

**Cause:** Selected view no longer exists on the Oracle BI server.

**Action:** Please make sure that the view exists at the specified path on the server.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00048: Edit Prompts/Levels is not supported for this type of view**

**Cause:** Edit Prompts/Levels action is initiated on Title or Filter view

**Action:** Please make sure to select a view other than Title and Filter in order to Edit Prompts/Levels.

**Level:** 2

**Type:** Warning

**Impact:** Programmatic

**OBI\_OFFICE-00049: Selected object is not a valid BI Object**

**Cause:** Object selected is not an Oracle BI View.

**Action:** Please make sure to select a valid BI view object.

**Level:** 2

**Type:** Warning

**Impact:** Programmatic

**OBI\_OFFICE-00050: Test connection failed.**

**Cause:** Unable to test connectivity to the Oracle BI Office server.

**Action:** Please make sure the connection parameters for this connection are set correctly and try again.

**Level:** 2

**Type:** Error

**Impact:** Network

**OBI\_OFFICE-00051: The folder is empty.**

**Cause:** The folder you are trying to access is empty.

**Action:** Please make sure to select a non-empty folder.

**Level:** 2

**Type:** Information

**Impact:** Programmatic

---

**OBI\_OFFICE-00052: These Oracle BI views are not supported so will not be pasted**

**Cause:** Some of the copied views are not supported by the BI Office addin and therefore will not be pasted.

**Action:** Try pasting the unsupported views as images or flash(PowerPoint).

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00053: This chart type is not supported.**

**Cause:** The specified chart type is not supported by BI Office addin.

**Action:** Try inserting the chart as image or flash(Powerpoint)

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00054: This Oracle BI view type is not supported.**

**Cause:** The specified view type is not supported.

**Action:** Please make sure to insert a view that is supported by the addin.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00055: Title view not inserted as it is empty :**

**Cause:** The title view is empty and therefore not inserted.

**Action:** Please make sure the titleview is not empty.

**Level:** 2

**Type:** Warning

**Impact:** Programmatic

**OBI\_OFFICE-00056: Unknown error occurred.**

**Cause:** An unknown error occurred on BI Office server.

**Action:** Examine the logs on BI Office server to get more details.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00057: You must select an operator**

**Cause:** An operator has not been selected in the prompt dialog.

**Action:** Please make sure you enter a valid operator in the prompt selection dialog.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

---

**OBI\_OFFICE-00058: You must enter a connection name.**

**Cause:** A connection name has not been entered in connection details dialog.

**Action:** Please make sure you enter a valid connection name in the prompt selection dialog.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00059: You must enter a date at row:**

**Cause:** A valid date has not been entered in the prompt selection dialog.

**Action:** Please make sure you enter a valid date in the prompt selection dialog.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00060: You must enter office application name.**

**Cause:** A BIOffice application name has not been entered in connection dialog.

**Action:** Please enter a valid application name for BI Office server connection.

Default : biooffice

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00061: You must enter a different value**

**Cause:** Same date or datetime value has been entered in case of between operator.

**Action:** Please enter a different date or datetime for getting data in the specified time range.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00062: You must enter a number at row:**

**Cause:** The value entered at the specified row is non-numeric.

**Action:** Please enter a numeric value at the specified row.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00063: You must enter a value for**

**Cause:** Prompt value is not entered for a prompt column that is defined as mandatory (cannot be skipped).

**Action:** Please enter or select value for the defined prompt column.

**Level:** 2

**Type:** Error

---

**Impact:** Programmatic

**OBI\_OFFICE-00064: You must login again for this change to take effect.**

**Cause:** You have made changes to the connection information while being connected to the same connection.

**Action:** Please logout and login again.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00065: Please select at least one section to insert.**

**Cause:** You have not selected one or more sections of the pivottableview to insert.

**Action:** Please select at least one section to insert in pivottable view.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00066: You must select at least one level**

**Cause:** You have not selected one or more levels to insert in insert view dialog.

**Action:** Please select at least one level in the level selection tab of insert view dialog.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00067: The table being inserted contains more than \$1 rows, insertion could be slow.**

**Cause:** The table view or pivot table view being inserted has large number of rows.

**Action:** Select OK to proceed, or Cancel to stop the insertion.

**Level:** 2

**Type:** Information

**Impact:** Programmatic

**OBI\_OFFICE-00068: The table being inserted contains more than \$1 rows, please wait until insertion is complete or Click Cancel to stop.**

**Cause:** The table view or pivot table view being inserted has large number of rows.

**Action:** Select OK to proceed, or Cancel to stop the insertion.

**Level:** 2

**Type:** Information

**Impact:** Programmatic

**OBI\_OFFICE-00069: The table being inserted contains more than \$1 columns, insertion could be slow.**

---

**Cause:** The table view or pivot table view being inserted has large number of columns.

**Action:** Select OK to proceed, or Cancel to stop the insertion.

**Level:** 2

**Type:** Information

**Impact:** Programmatic

**OBI\_OFFICE-00070: The table being inserted contains more than 65,535 columns, please wait until insertion is complete or Click Cancel to stop.**

**Cause:** The table view or pivot table view being inserted has large number of columns.

**Action:** Select OK to proceed, or Cancel to stop the insertion.

**Level:** 2

**Type:** Information

**Impact:** Programmatic

**OBI\_OFFICE-00071: This chart type is not supported.**

**Cause:** The chart type you have selected to insert is not supported by Oracle BI Office Addin.

**Action:** Select a different chart type to insert.

**Level:** 2

**Type:** Error

**Impact:** Programmatic

**OBI\_OFFICE-00072: Unknown server error has occurred. Please check the server logs.**

**Cause:** Unknown server error has occurred.

**Action:** Please check the server logs.

**Level:** 2

**Type:** Error

**Impact:** Programmatic





---

---

## ODI-01100 to ODI-30094

**ODI-01100: Agent {0} successfully cleaned up {1} stale sessions from work repository {2} using {3}**

**Cause:** null

**Action:** null

**Level:** 16

**Type:** NOTIFICATION

**Impact:** Other

**ODI-01101: Agent {0} successfully completed session {1} ({2}) (for scenario {3}) on {4} using context {5} with statistics: Rows {6} Inserts {7} Updates {8} Deletes {9} Errors {10}**

**Cause:** null

**Action:** null

**Level:** 16

**Type:** NOTIFICATION

**Impact:** Other

**ODI-01102: Agent {0} successfully completed session {1} ({2}) on {3} using context {4} with statistics: Rows {5} Inserts {6} Updates {7} Deletes {8} Errors {9}**

**Cause:** null

**Action:** null

**Level:** 16

**Type:** NOTIFICATION

**Impact:** Other

**ODI-01103: Agent {0} successfully completed step {1} in session {2}**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** TRACE

**Impact:** Other

**ODI-01104: Agent {0} successfully connected to master repository using {1}**

**Cause:** null

---

**Action:** null  
**Level:** 16  
**Type:** TRACE  
**Impact:** Other

**ODI-01105: Agent {0} successfully connected to work repository {1} using {2}**  
**Cause:** null  
**Action:** null  
**Level:** 16  
**Type:** TRACE  
**Impact:** Other

**ODI-01106: Agent {0} created load plan {1}**  
**Cause:** null  
**Action:** null  
**Level:** 16  
**Type:** TRACE  
**Impact:** Other

**ODI-01107: Agent {0} created session {1} ({2}) in {3}**  
**Cause:** null  
**Action:** null  
**Level:** 16  
**Type:** TRACE  
**Impact:** Other

**ODI-01108: Agent {0} created session {1} ({2}) from scenario {3} in {4} using context {5}**  
**Cause:** null  
**Action:** null  
**Level:** 16  
**Type:** TRACE  
**Impact:** Other

**ODI-01109: Agent {0} is delegating session {1} on {2} to agent {3}**  
**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** TRACE  
**Impact:** Other

**ODI-01110: Agent {0} successfully retrieved {1} schedules from work repository {2} using {3}**  
**Cause:** null  
**Action:** null

---

**Level:** 16

**Type:** NOTIFICATION

**Impact:** Other

**ODI-01111: Agent {0} started. Agent version: {1}. Port: {2}. JMX Port: {3}.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**ODI-01112: Agent {0} received a request to recalculate its schedule on {1}**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** TRACE

**Impact:** Other

**ODI-01113: Agent {0} received a data server test request for {1}**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** TRACE

**Impact:** Other

**ODI-01114: Agent {0} received a request to stop load plan instance {1} on {2}**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** TRACE

**Impact:** Other

**ODI-01115: Agent {0} received a ping request**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** TRACE

**Impact:** Other

**ODI-01116: Agent {0} received a request to retrieve its schedule on {1}**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** TRACE

---

**Impact:** Other

**ODI-01117:** Agent {0} received a request to restart load plan instance {1}, {2} on {3} using context {4}

**Cause:** null

**Action:** null

**Level:** 1

**Type:** TRACE

**Impact:** Other

**ODI-01118:** Agent {0} received a request to start load plan {1} on {2} using context {3}

**Cause:** null

**Action:** null

**Level:** 1

**Type:** TRACE

**Impact:** Other

**ODI-01119:** Agent {0} received a request to start scenario {1}. {2} on {3} using context {4}

**Cause:** null

**Action:** null

**Level:** 1

**Type:** TRACE

**Impact:** Other

**ODI-01120:** Agent {0} received a request to restart session {1} on {2} using context {3}

**Cause:** null

**Action:** null

**Level:** 1

**Type:** TRACE

**Impact:** Other

**ODI-01121:** Agent {0} received a request to stop session {1} on {2}

**Cause:** null

**Action:** null

**Level:** 1

**Type:** TRACE

**Impact:** Other

**ODI-01122:** Agent {0} successfully restarted {1} queued sessions from work repository {2} using {3}

**Cause:** null

**Action:** null

**Level:** 16

**Type:** NOTIFICATION

---

**Impact:** Other

**ODI-01123: Agent {0} sent a request to agent {1}**

**Cause:** null

**Action:** null

**Level:** 16

**Type:** TRACE

**Impact:** Other

**ODI-01124: Agent {0} started load plan {1}**

**Cause:** null

**Action:** null

**Level:** 16

**Type:** NOTIFICATION

**Impact:** Other

**ODI-01125: Agent {0} started session {1} ({2}) from scenario {3} in {4} using context {5}**

**Cause:** null

**Action:** null

**Level:** 16

**Type:** NOTIFICATION

**Impact:** Other

**ODI-01126: Agent {0} started session {1} ({2}) in {3} using context {4}**

**Cause:** null

**Action:** null

**Level:** 16

**Type:** NOTIFICATION

**Impact:** Other

**ODI-01127: Agent {0} started step {1} in session {2}**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** TRACE

**Impact:** Other

**ODI-01128: Agent {0} is starting. Application Server: {1}. Agent Version: {2}. Port: {3}. JMX Port: {4}**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

---

**ODI-01129: Agent {0} stopped**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**ODI-01130: Agent {0} is stopping**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**ODI-01131: Agent {0} encountered an error: {1}**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01132: Agent {0} encountered an warning: {1}**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ODI-01133: Agent {0} detected that the work repository {1} went down**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01134: Agent {0} encountered an error: {1}**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ODI-01135: Agent {0} detected that the master repository went down**

**Cause:** null

---

**Action:** null  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other

**ODI-01136: Starting Schedulers on Agent {0}**  
**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** NOTIFICATION  
**Impact:** Other

**ODI-01137: Scheduler started for work repository {0} on Agent {1}**  
**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** NOTIFICATION  
**Impact:** Other

**ODI-01138: Migrating Schedulers for Agent {0}**  
**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** NOTIFICATION  
**Impact:** Other

**ODI-01139: The current task of the session ({0}) does not support stop immediate. This session will be stopped normally by the Agent ({1}) before next task begins.**  
**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** WARNING  
**Impact:** Other

**ODI-01140: Unable to stop session ({0}) immediately. This session will be stopped by the agent ({1}) before next task begins.**  
**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** WARNING  
**Impact:** Other

**ODI-01141: Starting load plan instance "{0}", run {1} on agent {2}**  
**Cause:** null

---

**Action:** null

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**ODI-01142: Load plan instance "{0}", run {1} is complete**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**ODI-01143: Starting load plan processing for instance "{0}", run {1}, from step id {2}, on agent {3}**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** TRACE

**Impact:** Other

**ODI-01144: Completed load plan processing for instance "{0}", run {1} on agent {2}**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** TRACE

**Impact:** Other

**ODI-01145: Could not find physical agent "{0}" when trying to stop session with id "{1}"**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ODI-01146: Invocation error when trying to stop session with id "{0}": {1}**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ODI-01147: Stopped load plan instance "{0}", run number {1}**

**Cause:** null



---

**Action:** null

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**ODI-01148: Executing load plan log purge for repository "{0}" at {1}**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**ODI-01149: Purge failed for load plan instance "{0}": "{1}"**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ODI-01150: Purge failed for load plan instance "{0}": "{1}"**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ODI-01151: Can not continue load plan instance {0}, run number {1}, because the instance has been deleted**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ODI-01152: Continuing load plan processing for instance "{0}", run {1} on agent {2}**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** TRACE

**Impact:** Other

**ODI-01200: Session start failure: the request is incorrectly formed.**

**Cause:** A malformed request was sent to the agent.

**Action:** Verify the request format and parameters sent to the agent.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01201: Session start failure on agent {0}: JDBC connection error occurs while connecting to the master repository.**

**Cause:** An incorrect connection was used for the master repository database, or repository database was down.

**Action:** Verify the master repository connection information and the status of the master repository database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01202: Session start failure on agent {0}: data source for master repository does not contain a master repository.**

**Cause:** The master repository connection information pointed to a database schema that did not contain a master repository.

**Action:** Verify the master repository connection information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01203: Session start failure on agent {0}: the master repository is in an invalid state.**

**Cause:** The master repository was in a state that did not allow connections. This is the case if an upgrade was being performed.

**Action:** Verify the state of the master repository.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01204: Session start failure on agent {0}: the master repository version {1} is not compatible with the agent version {2}.**

**Cause:** The master repository was upgraded but not this agent, or the agent was upgraded but not the master repository.

**Action:** Upgrade the master repository version or the agent version.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01205: Session start failure on agent {0}: an authentication error occurs while connecting to the master repository.**

**Cause:** An incorrect ODI user or password was specified for this master repository.

**Action:** Verify the ODI user and password used for connecting.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01206: Session start failure on agent {0}: the agent is not defined in the topology for master repository.**

**Cause:** The session was not found in the master repository.

**Action:** Verify that a session with this ID exists in the repository.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01207: Session start failure on agent {0}: JDBC connection error occurs while connecting to the work repository {1}.**

**Cause:** An incorrect connection was used for the work repository database, or repository database was down.

**Action:** Verify the work repository connection information and the status of the work repository database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01208: Session start failure on agent {0}: database schema {1} does not contain a work repository.**

**Cause:** The work repository connection information pointed to a database schema that did not contain a work repository.

**Action:** Verify the work repository connection information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01209: Session start failure on agent {0}: work repository {1} is in an invalid state.**

**Cause:** The work repository was in a state that did not allow connections. This is the case if an upgrade was being performed.

**Action:** Verify the state of the work repository.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01210: Session start failure on agent {0}: work repository {1} version {2} is not compatible with the agent version {3}.**

**Cause:** The work repository was upgraded but not this agent, or the agent was upgraded but not the work repository.

**Action:** Upgrade the work repository version or the agent version.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**ODI-01211: Session start failure on agent {0}: work repository {1} is not bound to the master repository.**

**Cause:** The work repository specified in the request was not found in the list of work repositories attached to this master.

**Action:** Verify that work repository name matches an existing one.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01212: Session preparation failure: scenario {0} does not exist in work repository {1}.**

**Cause:** The session request was received, but the agent was unable to find the named scenario in the work repository.

**Action:** Verify that the scenario name matches an existing scenario name in the work repository.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01213: Session preparation failure: scenario {0} version {1} does not exist in work repository {2}.**

**Cause:** The session request was received, and the scenario existed in the work repository, but not with the specified version.

**Action:** Ensure that the scenario version matches an existing scenario version in the work repository.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01214: Session preparation failure: context {0} does not exist in the master repository.**

**Cause:** The session request was received, but the agent was unable to find the context in the master repository.

**Action:** Ensure that the context matches an existing context code in the Topology.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01215: Session preparation failure: privileges are insufficient to run scenario {0}.{1} in repository {2}.**

**Cause:** User privileges were not sufficient for running this scenario in this repository.

**Action:** Ensure that the user has sufficient privileges for this task.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**ODI-01216: Session preparation failure: insufficient privileges to use Context {0} ({1}).**

**Cause:** User privileges were not sufficient for using this context.

**Action:** Ensure that the user has sufficient privileges for this task.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01217: Session {0} ({1}) fails with return code {2}.**

**Cause:** The session finished in an error state.

**Action:** Review the session execution details in the Operator Navigator or Repository Explorer.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01218: Session preparation failure: database error occurs while connecting to the master repository.**

**Cause:** The agent received a database error from the master repository while creating the session.

**Action:** Verify the state of the master repository database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01219: Session preparation failure: database error while connecting to work repository {0}.**

**Cause:** The agent received a database error from the work repository while creating the session.

**Action:** Verify the state of the work repository database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01220: Session preparation failure: an unexpected exception occurred.**

**Cause:** The remote agent faced an unexpected error while attempting to create the session.

**Action:** Contact Oracle Support Services. Provide the error message, a description of the action causing this fault, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**ODI-01221: Unable to restart session {0}: session is not found in work repository {1}.**

**Cause:** The session to restart did not exist in the repository. This session may have been deleted, or an incorrect session ID or work repository was supplied.

**Action:** Verify that a session with this ID exists in the repository.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01222: Session start failure on agent {0}: logical schema {1} cannot be found in the master repository.**

**Cause:** The object to be executed referred to a logical schema not present in the master repository.

**Action:** Ensure that the logical schema configuration exists in your master repository.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01223: Database error while connecting to the master repository.**

**Cause:** The connection for the master repository database was incorrect, or the repository database was down.

**Action:** Verify the master repository connection information and the status of the master repository database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01224: Database error while connecting to work repository {0}**

**Cause:** The connection for the work repository database was incorrect, or the repository database was down.

**Action:** Verify the work repository connection information and the status of the master repository database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01225: An unexpected exception occurred.**

**Cause:** The agent faced an unexpected exception.

**Action:** Contact Oracle Support Services. Provide the error message, a description of the action causing this fault, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01226: Step {0} fails after {1} attempt(s).**

---

**Cause:** This is an execution warning. The session step failed to execute after the maximum number of retries. If step failure was not handled in the package design, the session finished in an error state.

**Action:** Review the session execution details in the Operator Navigator or Repository Explorer.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ODI-01227: Task {0} ({1}) fails on the source {2} connection {3}.**

**Cause:** This is an execution warning. The command on the source for this task finished with an error.

**Action:** Review the session execution details in the Operator Navigator or Repository Explorer.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ODI-01228: Task {0} ({1}) fails on the target {2} connection {3}.**

**Cause:** This is an execution warning. The command on the target for this task finished with an error.

**Action:** Review the session execution details in the Operator Navigator or Repository Explorer.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ODI-01229: An error occurred while performing a {0} operation on model code {1}.**

**Cause:** This is an execution warning. The operation specified failed on the model.

**Action:** Review the session execution details in the Operator Navigator or Repository Explorer.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ODI-01231: An error occurred while performing a {0} operation on datastore {1}.**

**Cause:** This is an execution warning. The operation specified failed on the datastore.

**Action:** Review the session execution details in the Operator Navigator or Repository Explorer.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ODI-01232: Procedure {0} execution fails.**

**Cause:** This is an execution warning. The procedure execution failed.

---

**Action:** Review the session execution details in the Operator Navigator or Repository Explorer.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ODI-01233: Error while evaluating variable the following expression: {0} {1} {2}**

**Cause:** This is an execution warning. The variable evaluation failed.

**Action:** Review the session execution details in the Operator Navigator or Repository Explorer.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ODI-01235: Error while incrementing variable {0} to value {1}**

**Cause:** This is an execution warning. The variable increment failed.

**Action:** Review the session execution details in the Operator Navigator or Repository Explorer.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ODI-01236: Error while refreshing variable {0}.**

**Cause:** This is an execution warning. The variable refresh failed.

**Action:** Review the session execution details in the Operator Navigator or Repository Explorer.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ODI-01237: Error while setting variable {0} to value {1}.**

**Cause:** This is an execution warning. The set variable operation failed.

**Action:** Review the session execution details in the Operator Navigator or Repository Explorer.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ODI-01238: Flow {0} fails because the maximum number of allowed errors ({1} rows) is exceeded during the flow check. This flow loads target table {2}.**

**Cause:** This is an execution warning. The interface failed because the number of errors detected in the flow exceeded the value defined in the interface.

**Action:** Review the session execution details in the Operator Navigator or Repository Explorer. Review the erroneous records for this interface in the error table.



---

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ODI-01239: Flow {0} fails because the maximum percentage of allowed errors ({1} %) is exceeded during the flow check. This flow loads target table {2}.**

**Cause:** This is an execution warning. The interface failed because the percentage of errors detected in the flow exceeded the value defined in the interface.

**Action:** Review the session execution details in the Operator Navigator or Repository Explorer. Review the erroneous records for this interface in the error table.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ODI-01240: Flow {0} fails while performing a {1} operation. This flow loads target table {2}.**

**Cause:** This is an execution warning. The interface failed because one of the statements returned an error return code.

**Action:** Review the session execution details in the Operator Navigator or Repository Explorer.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ODI-01241: Oracle Data Integrator tool execution fails.**

**Cause:** This is an execution warning. The tool execution failed.

**Action:** Review the session execution details in the Operator Navigator or Repository Explorer.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ODI-01242: Operating system command execution fails.**

**Cause:** This is an execution warning. Execution of the operating system command failed.

**Action:** Review the session execution details in the Operator Navigator or Repository Explorer.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ODI-01243: Session {0} ({1}) fails because work repository {2} went down.**

**Cause:** Work repository database went down while session was being executed.

**Action:** Verify the state of the work repository database. The session must be restarted.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01244: Session {0} {1} was prepared successfully but fails because work repository {2} went down before execution could begin.**

**Cause:** Work repository database went down while session was starting its execution.

**Action:** Verify the state of the work repository database. The session must be restarted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01245: Session preparation failure: work repository {0} went down during session preparation.**

**Cause:** Work repository went down while session was being prepared.

**Action:** Verify the state of the work repository database. The session must be restarted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01246: The Logical Schema has not been set for {0}.**

**Cause:** Because the logical schema had not been set, the object could not be executed.

**Action:** Verify the object that you are trying to execute, and set the logical schema for this object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01247: Session {0} {1} was prepared successfully but fails because master repository went down before execution could begin.**

**Cause:** Master repository database went down while session was starting its execution.

**Action:** Verify the state of the master repository database. The session must be restarted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01248: Session preparation failure by Agent {0}: master repository went down during session preparation.**

**Cause:** Master repository went down while session was being prepared.

**Action:** Verify the state of the master repository database. The session must be restarted.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01249: Session {0} ({1}) fails because master repository went down.**

**Cause:** Master repository database went down while session was being executed.

**Action:** Verify the state of the master repository database. The session must be restarted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01250: Session {0} ({1}) could not be stopped by Agent {2} because session {0} {1} already completed execution.**

**Cause:** The session has already completed and cannot be stoppped.

**Action:** Review the session execution details in the Operator Navigator or Repository Explorer.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01251: Session ({0}) could not be stopped by Agent {1} because session ({0}) was not found in work repository {2}.**

**Cause:** The session was not found in the work repository.

**Action:** Verify that a session with this ID exists in the repository.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01252: Session ({0}) could not be stopped by Agent {1}: insufficient privileges to access session.**

**Cause:** User privileges were not sufficient for accessing this session in this agent.

**Action:** Ensure that the user has sufficient privileges for this task.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01253: Session {0} ({1}) could not be stopped by Agent {2}: an unknown error occurred.**

**Cause:** An unexpected Exception occurred.

**Action:** Verify your Agent configuration and make sure other operations on Agent are working correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**ODI-01254: Session {0} ({1}) could not be stopped by Agent {2}: a JDBC error occurred on work repository {3}.**

**Cause:** The agent had incorrect connection for the work repository database, or repository database was down.

**Action:** Verify the work repository connection information and the status of the work repository database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01255: Session {0} ({1}) could not be stopped by Agent {2}: insufficient privileges to stop the session.**

**Cause:** User privileges were not sufficient for stopping this session in this agent.

**Action:** Ensure that the user has sufficient privileges for this task.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01256: Session {0} ({1}) stopped (Normal) by user {2}.**

**Cause:** Session was stopped by the user.

**Action:** Review the session execution details in the Operator Navigator or Repository Explorer.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01257: Session {0} ({1}) stopped (Immediate) by user {2}.**

**Cause:** Session was stopped by the user.

**Action:** Review the session execution details in the Operator Navigator or Repository Explorer.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01258: Session {0} ({1}) stopped (Abort) by user {2}.**

**Cause:** Session was aborted by the user.

**Action:** Review the session execution details in the Operator Navigator or Repository Explorer.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01259: Session Task {0} ({1}) stopped (Normal) by user {2}.**

**Cause:** Task was stopped by the user.

**Action:** Review the task execution details in the Operator Navigator or Repository Explorer.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01260: Session Task {0} ({1}) stopped (Immediate) by user {2}.**

**Cause:** Task was stopped by the user.

**Action:** Review the task execution details in the Operator Navigator or Repository Explorer.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01261: Session Task {0} ({1}) stopped (Abort) by user {2}.**

**Cause:** Task was aborted by the user.

**Action:** Review the task execution details in the Operator Navigator or Repository Explorer.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01262: Session {0} ({1}) could not be stopped by Agent {2}: a JDBC error occurred on master repository.**

**Cause:** The agent had incorrect connection for the master repository database, or repository database was down.

**Action:** Verify the master repository connection information and the status of the master repository database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01263: Step {0} stopped (Normal) by user {1}.**

**Cause:** Step was stopped by the user.

**Action:** Review the step execution details in the Operator Navigator or Repository Explorer.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01264: Step {0} stopped (Immediate) by user {1}.**

**Cause:** Step was stopped by the user.

**Action:** Review the step execution details in the Operator Navigator or Repository Explorer.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**ODI-01265: Step {0} stopped (Abort) by user {1}.**

**Cause:** Step was aborted by the user.

**Action:** Review the step execution details in the Operator Navigator or Repository Explorer.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01266: Agent {0} detected Session as stale session and set to error status.**

**Cause:** The agent detected a stale session and the session status was set to error status.

**Action:** Review the session execution details in the Operator Navigator or Repository Explorer.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01267: Session ({0}) could not be stopped by Agent {1} because stop type {2} provided in the request is an invalid stop type.**

**Cause:** The agent attempted to stop a session with an invalid stop type.

**Action:** Review the session execution details in the Operator Navigator or Repository Explorer.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01268: Agent {0} does not support stopping asynchronous child sessions.**

**Cause:** The agent attempted to stop an asynchronous child session and this is not supported.

**Action:** Review the session execution details in the Operator Navigator or Repository Explorer.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01269: Session {0} ({1}) could not be stopped by Agent {2}: session is being run by another Agent with the same name.**

**Cause:** The agent attempted to stop a session that is being run by a different agent.

**Action:** Review the session execution details in the Operator Navigator or Repository Explorer.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**ODI-01270: Session {0} ({1}) could not be stopped by Agent {2}; session {0} ({1}) is being run by {3} Agent which is not a listener Agent.**

**Cause:** The agent attempted to stop a session that is being run by the internal agent and this is not supported.

**Action:** Review the session execution details in the Operator Navigator or Repository Explorer.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01271: The asynchronous jndi name cannot be null for asynchronous jobs. The ESS job status cannot be updated.**

**Cause:** The agent attempted to set the status of the asynchronous ESS job and its jndi name was not set.

**Action:** Review the jndi name supplied to the Enterprise Scheduler job.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ODI-01272: The Logical Schema has not been set on {0} for {1}.**

**Cause:** The logical schema for this object has not been set.

**Action:** Verify that the logical schema has been set in the Topology.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01273: The selected technology {0} is not supported on source for {1}.**

**Cause:** The selected technology is not supported for this object.

**Action:** Verify that the object has a valid technology.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01274: Agent Exception**

**Cause:** An error was detected by the agent when performing an operation.

**Action:** Review the underlying exception for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01275: An error occurred while performing a {0} operation on submodel step {1} of the model code {2}.**

**Cause:** This is an execution warning. The operation specified failed on the submodel operation.

**Action:** Review the session execution details in the Operator Navigator or Repository Explorer.

---

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ODI-01276: An error occurred while executing the OnConnect command on JDBC connection created for data server {0} with transaction label {1}.**

**Cause:** An error was occurred while executing the OnConnect command on the JDBC connection created to the data server.

**Action:** Review the underlying exception and update the OnConnect command definition configured for the data server.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01277: An error occurred while executing the OnDisconnect command on JDBC connection created for data server {0} with transaction label {1}.**

**Cause:** An error was occurred while executing the OnDisconnect command on the JDBC connection created to the data server.

**Action:** Review the underlying exception and update the OnDisconnect command definition configured for the data server.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01400: Agent {0} start failure: JDBC connection error occurs while connecting to the master repository.**

**Cause:** The master repository information was incorrect, or the repository database was down.

**Action:** Verify the master repository connection information and the status of the master repository database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01401: Agent {0} start failure: data source for master repository did not contain a master repository.**

**Cause:** The master repository connection information pointed to a database schema that did not contain a master repository.

**Action:** Verify the master repository connection information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01402: Agent {0} start failure: the master repository is in an invalid state.**

**Cause:** The master repository was in a state that did not allow connections. This is the case when an upgrade is being performed.

**Action:** Verify the state of the master repository.



---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01403: Agent {0} start failure: the master repository version {1} is not compatible with the agent version {2}.**

**Cause:** The master repository was upgraded but not this agent, or the agent was upgraded but not the master repository.

**Action:** Upgrade the master repository version or the agent version.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01404: Agent {0} start failure: an authentication error occurred while connecting to the master repository.**

**Cause:** An incorrect ODI user or password was specified for this master repository.

**Action:** Verify the ODI user and password used for connecting.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01405: Agent {0} start failure: the agent is not defined in the topology for master repository.**

**Cause:** This agent was not declared in the topology.

**Action:** Add this physical agent in the list of agents in the ODI topology.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01406: Agent {0} started with warning: JDBC connection error occurs while connecting to the work repository {1}.**

**Cause:** The work repository information was incorrect, or the repository database was down.

**Action:** Verify the work repository connection information and the status of the work repository database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01407: Agent {0} started with warning: connection details of {1} do not contain a work repository.**

**Cause:** The work repository connection information pointed to a database schema that did not contain a work repository.

**Action:** Review the work repository connection information and revise it as necessary.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01408: Agent {0} started with warning: work repository {1} is in an invalid state.**

**Cause:** The work repository was in a state that did not allow connections. This is the case when an upgrade is being performed.

**Action:** Verify the state of the work repository.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01409: Agent {0} started with warning: work repository {1} version {2} is not compatible with the agent version {3}.**

**Cause:** The work repository was upgraded but not this agent, or the agent was upgraded but not the work repository.

**Action:** Upgrade the work repository version or the agent version.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01410: Agent {0} started with warning: work repository {1} is not bound to the master repository.**

**Cause:** The work repository specified in the request was not found in the list of work repositories attached to this master.

**Action:** Ensure that work repository name matches an existing one.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01411: Agent {0} started with warning: a database error occurs while cleansing stale sessions.**

**Cause:** The agent encountered a database error while attempting to close stale sessions.

**Action:** Review the status of the sessions for this agent, and manually remove the stale sessions.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01412: Agent {0} started with warning: an unexpected error occurs while cleaning stale sessions.**

**Cause:** The agent encountered an unexpected error while attempting to close stale sessions.

**Action:** Contact Oracle Support Services. Provide the error message, a description of the action causing this fault, and the exception stack trace in the log files (with

---

the logging level set to debug mode). Verify the status of the sessions for this agent, and manually remove the stale sessions.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01413: Request is incorrectly formed.**

**Cause:** A malformed request was sent to the agent.

**Action:** Review the request format and parameters sent to the agent.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01414: Error connecting to agent {0}: a JDBC error occurs while connecting to the master repository.**

**Cause:** The remote agent had incorrect connection for the master repository database, or repository database was down.

**Action:** Verify the master repository connection information and the status of the master repository database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01415: Error connecting to agent {0}: data source for master repository did not contain a master repository.**

**Cause:** The master repository connection information for the remote agent pointed to a database schema that did not contain a master repository.

**Action:** Review the master repository connection information and revise it as necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01416: Error connecting to agent {0}: the master repository is in an invalid state.**

**Cause:** The master repository was in a state that did not allow connections from the remote agent. This is the case when an upgrade is being performed.

**Action:** Verify the state of the master repository.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01417: Error connecting to agent {0}: the master repository version {1} is not compatible with the agent version {2}.**

**Cause:** The master repository was upgraded but not the remote agent, or the remote agent was upgraded but not the master repository.

**Action:** Upgrade the master repository version or the agent version.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01418: Error connecting to agent {0}: an authentication error occurs while connecting to the master repository.**

**Cause:** An incorrect ODI user or password was specified for this master repository.

**Action:** Verify the ODI user and password used for connecting.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01419: Warning connecting to Agent {0}: JDBC connection error occurs while connecting to the work repository {1}.**

**Cause:** The remote agent had incorrect connection for the work repository database, or the repository database was down.

**Action:** Verify the work repository connection information and the status of the work repository database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01420: Warning connecting to Agent {0}: connection details of {1} do not contain a work repository.**

**Cause:** The work repository connection information for the remote agent pointed to a database schema that did not contain a work repository.

**Action:** Verify the work repository connection information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01421: Warning connecting to Agent {0}: work repository {1} is in an invalid state.**

**Cause:** The work repository was in a state that did not allow connections from the remote agent. This is the case when an upgrade is being performed.

**Action:** Verify the state of the work repository.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01422: Warning connecting to Agent {0}: work repository {1} version {2} is not compatible with the agent version {3}.**

**Cause:** The work repository was upgraded but not the remote agent, or the remote agent was upgraded but not the work repository.

**Action:** Upgrade the work repository version or the agent version.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01423: Warning connecting to Agent {0}: work repository {1} is not bound to the master repository.**

**Cause:** The work repository specified in the request was not found in the list of work repositories attached to the master.

**Action:** Verify that work repository name matches an existing one.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01424: Agent host or port cannot be reached using {0}.**

**Cause:** Incorrect host or port information was provided, or the agent was not started on the remote host.

**Action:** Correct the host or port information or start the agent.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01425: Agent application cannot be reached using {0}.**

**Cause:** An incorrect application name was provided for this agent, or the agent application was not started on the host.

**Action:** Correct the application name used in the URL or verify the agent status.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01426: Agent {0} is not defined in the topology for the master repository.**

**Cause:** This agent was not declared in the topology.

**Action:** Add this physical agent to the list of agents in the ODI topology.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01427: invalid parameters**

**Cause:** Invalid parameters were supplied in the request.

**Action:** Check the parameters that were supplied as part of the request. Ensure that parameter names and cases are correct.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ODI-01428: internal error**

---

**Cause:** An agent internal error occurred.

**Action:** Contact Oracle Support Services. Provide the error message, a description of the action causing this fault, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** FATAL

**Impact:** Other

**ODI-01429: The user {0} is not authorized to perform request {1} on Agent {2}.**

**Cause:** The user had insufficient privileges for performing this request against the remote agent.

**Action:** Amend the user privileges.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01430: Agent {0} cannot clean the stale sessions in work repository {1} due to a database error.**

**Cause:** The remote agent faced a database error while attempting to close stale sessions.

**Action:** Examine the status of the sessions for this agent, and manually remove the stale sessions.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01431: Agent {0} cannot clean the stale sessions in work repository {1} because the work repository {1} is still down.**

**Cause:** The remote agent was not able to connect to the work repository while attempting to close stale sessions.

**Action:** Determine the status of the repository. Once this repository is running, manually remove the stale sessions.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01432: Agent {0} cannot clean the stale sessions in work repository {1} due to an unexpected error.**

**Cause:** The remote agent faced an unexpected error while attempting to close stale sessions.

**Action:** Contact Oracle Support Services. Provide the error message, a description of the action causing this fault, and the exception stack trace in the log files (with the logging level set to debug mode). Determine the status of the sessions for this agent, and manually remove the stale sessions.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**ODI-01433: The Internal agent does not support cleaning stale sessions from multiple work repositories.**

**Cause:** Empty string value was passed for the work repository name in the Clean Stale Sessions request sent to the Internal Agent.

**Action:** Specify a non-empty valid work repository name in the Clean Stale Sessions request sent to the Internal Agent. If you want to clean the stale sessions across the work repositories, perform this operation on a Remote physical Agent.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01434: Agent {0} start failure: error while trying to use JMX Port {1}.**

**Cause:** JMX Registry was unable to use the given port.

**Action:** Specify a different port by using the command-line parameter JMXPORT.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01435: Storage space for the IDs of some object types is low in Repository {0}.**

**When no storage space is available, it will not be possible to create objects of these types. Consider creating a new repository for the following object types (Object Type: Number Remaining) {1}.**

**Cause:** Storage space was low for some IDs in this repository.

**Action:** Consider creating a new repository.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ODI-01436: Error retrieving ID statistics for repository {0}.**

**Cause:** The ID statistics for this repository could not be verified.

**Action:** Verify the statistics for this repository manually.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ODI-01437: Error retrieving information from the credential store map.**

**Cause:** Could not retrieve information from the credential store map.

**Action:** Verify that the credentials have been entered correctly into the credential store map.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01438: Agent {0} cannot be stopped by user {1}: a JDBC error occurred on master repository {2}.**

---

**Cause:** Some SQL Exception occurred on the Master Repository.

**Action:** Verify that other operations on the Agent are working correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01439: Agent {0} cannot be stopped by user {1}: a JDBC error occurred on work repository {2}.**

**Cause:** Some SQL Exception occurred on the Work Repository.

**Action:** Verify that other operations on the Agent are working correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01440: Agent {0} cannot be stopped by user {1}: an unknown error occurred.**

**Cause:** An unexpected Exception occurred.

**Action:** Verify your Agent configuration and make sure other operations on Agent are working correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01441: Unable to connect to the master repository at JDBC URL={0} with USER={1}.**

**Cause:** An SQLException occurred while creating connection to the master repository with the given parameters.

**Action:** Verify your Agent configuration and make sure the master repository connection parameters are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01442: Unable to load JDBC Driver {0} configured for master repository connection.**

**Cause:** ClassNotFoundException occurred while loading the driver class.

**Action:** Verify your Agent configuration and make sure the driver specified for master repository connection is correct and the corresponding jar is present under driver folder.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01443: Error while starting agent : {0}**

**Cause:** Error occurred while starting the embedded web container.

**Action:** Verify your Agent configuration and make sure that the specified ports are available.



---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01500: SQL Exception when accessing work repository {0} while executing load plan instance {1} - {2}**

**Cause:** A SQLException was thrown when trying to update the work repository

**Action:** The same set of updates will be attempted later, potentially from a different agent

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01501: Cannot find variable "{0}" in the definition of load plan instance with ID {1}.**

**Cause:** The start/restart load plan request contained startup values for variables that are not defined in the load plan

**Action:** User error or problem in the IDE invocation code

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01502: Load plan instance with ID {0} is in an inconsistent state: {1}**

**Cause:** Indicates a problem in the ODI code, like a wrapped IllegalStateException

**Action:** null

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01503: Load plan logs for instance {0}, run {1} are corrupted: {2}**

**Cause:** Indicates a problem in the ODI code, it is a wrapped IllegalStateException

**Action:** null

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01504: Trying to update variables during execution of step "{0}" (load plan instance {1}, run {2}), as part of the exception handler for step "{3}", but variable updates during exception handlers are not supported.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**ODI-01505: Current value "{0}" of variable "{1}" (while evaluating When clause "{2}") is not a valid value of type {3} (load plan instance {4}, run {5}).**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01506: "Comparison value of step "{2}" ("'{0}") is not a valid value of type {3} (load plan instance {4}, variable tested "{1}").**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01507: Load Plan Instance restart called for Load Plan Instance with id "{0}", but no previous runs found.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01508: Load Plan Instance start called for Load Plan Instance with id "{0}", but previous runs have been found.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01509: Load Plan Instance with id "{0}" cannot be restarted because the previous run ({1}) did not finish with an "Error" status.**

**Cause:** null

**Action:** null

**Level:** 1

**Type:** ERROR

**Impact:** Other

**ODI-01510: The same load plan instance with id "{0}" simultaneously started by two agents.**

**Cause:** null

**Action:** null

**Level:** 1

---

Type: ERROR

Impact: Other

**ODI-01511: Step "{0}" should have already been marked as started before adding value for variable "{1}" (load plan instance {2}, run {3}).**

Cause: null

Action: null

Level: 1

Type: ERROR

Impact: Other

**ODI-01512: Variable "{0}" is defined as having datatype "{1}" in Load Plan instance with ID "{2}", but as having type "{3}" in scenario "{4}" (version {5}), Load Plan instance step "{6}".**

Cause: null

Action: null

Level: 1

Type: ERROR

Impact: Other

**ODI-01513: Error reading load plan information for session number {0}: "{1}"**

Cause: null

Action: null

Level: 1

Type: ERROR

Impact: Other

**ODI-01514: Error trying to stop load plan instance {0}: run {1} not found.**

Cause: null

Action: null

Level: 1

Type: ERROR

Impact: Other

**ODI-01515: Load Plan instance {0} could not be stopped by agent {1} because stop type ({2}) provided in the request is invalid.**

Cause: null

Action: null

Level: 1

Type: ERROR

Impact: Other

**ODI-01516: Can not start load plan: load plan with name "{0}" does not exist in work repository "{1}".**

Cause: null

Action: null

---

**Level:** 1  
**Type:** ERROR  
**Impact:** Other

**ODI-01517: Load Plan instance {0}, run {1} could not be stopped because that run is already completed (with status "{2}").**  
**Cause:** null  
**Action:** null

**Level:** 1  
**Type:** ERROR  
**Impact:** Other

**ODI-01518: Parallel step "{0}" failed; {1} child step(s) in error, which is more than the maximum number of allowed errors ({3}) defined for the parallel step. Failed child steps: {2}**  
**Cause:** null  
**Action:** null

**Level:** 1  
**Type:** ERROR  
**Impact:** Other

**ODI-01519: Serial step "{0}" failed because child step "{1}" is in error.**  
**Cause:** null  
**Action:** null

**Level:** 1  
**Type:** ERROR  
**Impact:** Other

**ODI-01520: Case-When/Else step "{0}" failed because child step "{1}" is in error.**  
**Cause:** null  
**Action:** null

**Level:** 1  
**Type:** ERROR  
**Impact:** Other

**ODI-01521: Case step "{0}" failed; the selected child "{1}" is in error.**  
**Cause:** null  
**Action:** null

**Level:** 1  
**Type:** ERROR  
**Impact:** Other

**ODI-01522: Run Scenario step failed during invocation. Error message was: {0}**  
**Cause:** null  
**Action:** null

---

**Level:** 1  
**Type:** ERROR  
**Impact:** Other  
**ODI-01523:** Exception handler for step "{0}" failed, because the root exception serial step "{1}" is in error.  
**Cause:** null  
**Action:** null

**Level:** 1  
**Type:** ERROR  
**Impact:** Other  
**ODI-01524:** Physical agent {0} could not be found.  
**Cause:** null  
**Action:** null

**Level:** 1  
**Type:** ERROR  
**Impact:** Other  
**ODI-01525:** Physical agent not found for logical agent name "{0}" and context "{1}" while executing step "{2}".  
**Cause:** null  
**Action:** null

**Level:** 1  
**Type:** ERROR  
**Impact:** Other  
**ODI-01526:** Error encountered while trying to start scenario "{1}{2}" (step "{3}"): {0}  
**Cause:** null  
**Action:** null

**Level:** 1  
**Type:** ERROR  
**Impact:** Other  
**ODI-01527:** Error refreshing variable "{0}": the associated SQL query returned no results.  
**Cause:** null  
**Action:** null

**Level:** 1  
**Type:** ERROR  
**Impact:** Other  
**ODI-01528:** Error refreshing variable "{0}": {1}  
**Cause:** null  
**Action:** null

---

**Level:** 1  
**Type:** ERROR  
**Impact:** Other  
**ODI-01529: Refresh of variable "{0}" failed.**  
**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other  
**ODI-01530: Load plan instance was stopped by user request.**  
**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other  
**ODI-01531: Timeout triggered while executing step "{0}".**  
**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other  
**ODI-01532: Timeout triggered on a parent step "{0}" while executing step "{1}".**  
**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other  
**ODI-01533: Error refreshing variable "{0}": could not get a connection to the logical schema "{1}" using context {2}.**  
**Cause:** null  
**Action:** null  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other  
**ODI-01534: Could not get SQL query text for variable "{0}" while trying to refresh it.**  
**Cause:** null  
**Action:** null  
**Level:** 1

---

Type: ERROR

Impact: Other

**ODI-01535: Can not continue load plan instance {0}, run number {1}, because the instance has been deleted.**

Cause: null

Action: null

Level: 1

Type: ERROR

Impact: Other

**ODI-01536: Load plan instance {0}, run number {1} failed to launch scenario: scenario {2} does not exist in work repository {3}.**

Cause: null

Action: null

Level: 1

Type: ERROR

Impact: Other

**ODI-01537: Load plan instance {0}, run number {1} failed to launch scenario: Version {3} of scenario {2} does not exist in work repository {4}.**

Cause: null

Action: null

Level: 1

Type: ERROR

Impact: Other

**ODI-01538: Unexpected unknown Exception occurred while executing Load plan instance {0}, run number {1}.**

Cause: null

Action: null

Level: 1

Type: ERROR

Impact: Other

**ODI-01539: Continuing load plan processing for instance "{0}", run {1} on agent {2} failed: {3}**

Cause: null

Action: null

Level: 1

Type: ERROR

Impact: Other

**ODI-01800: Exception {0} has occurred as ESS-EM linking is disabled.**

Cause: Unable to connect to master repository.

---

**Action:** Check if the master repository is accessible and up. This is not mandatory since master repositories can be down.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ODI-01801: Agent target discovery mbean registration has failed due to {0}.**

**Cause:** A runtime error has occurred.

**Action:** Check the log for details on the error and take corrective action.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-01802: Agent target discovery mbean unregistration has failed due to {0}.**

**Cause:** A runtime error has occurred.

**Action:** Check the log for details on the error and take corrective action.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-01803: Error {0} has occurred during mbean registration.**

**Cause:** A runtime error has occurred.

**Action:** Check the log for details on the error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-01804: Error {0} has occurred during mbean deregistration.**

**Cause:** A runtime error has occurred.

**Action:** Check the log for details on the error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-01805: Error {0} has occurred during notification listener registration.**

**Cause:** A runtime error has occurred.

**Action:** Check the log for details on the error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-01806: Error {0} has occurred during notification listener deregistration.**

**Cause:** A runtime error has occurred.

**Action:** Check the log for details on the error.



---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-01807: Error {0} has occurred during deregistration of ODI Service Mbean {1}.**

**Cause:** A runtime error has occurred.

**Action:** Check the log for details on the error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-01808: Error {0} has occurred during registration of Agent Service Mbean.**

**Cause:** A runtime error has occurred.

**Action:** Check the log for details on the error, fix the server and restart the OdiConsole application.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-01809: Error {0} has occurred during registration of Master Repository Service Mbean.**

**Cause:** A runtime error has occurred.

**Action:** Check the log for details on the error, fix the error and restart the OdiConsole application.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-01810: Error {0} has occurred during registration of Work Repository Service Mbean.**

**Cause:** A runtime error has occurred.

**Action:** Check the log for details on the error, fix the error and restart the OdiConsole application.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-01811: Error {0} has occurred during registration of Session Service Mbean.**

**Cause:** A runtime error has occurred.

**Action:** Check the log for details on the error, fix the error and restart the OdiConsole application.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-01812: Error {0} has occurred during registration of Event Service Mbean.**

---

**Cause:** A runtime error has occurred.

**Action:** Check the log for details on the error, fix the error and restart the OdiConsole application.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-01813: Error {0} has occurred during registration of Session Search Service Mbean.**

**Cause:** A runtime error has occurred.

**Action:** Check the log for details on the error, fix the error and restart the OdiConsole application.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-01814: No repository definition found for work repository {0} in repositories.xml. Search will be disabled for this repository.**

**Cause:** A configuration error has occurred.

**Action:** Add the jndi entries for all the work repositories for each of the master repositories in repositories.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ODI-01815: Exception {0} has occurred during Session Search by id.**

**Cause:** A runtime error has occurred.

**Action:** No action is required. The session id mentioned for search is not available.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-01816: Session status passed {0} is invalid.**

**Cause:** A runtime error has occurred.

**Action:** Check the log for details on the error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-01817: Error {0} has occurred while fetching statistics for agents. Statistics shown might not be complete.**

**Cause:** A runtime error has occurred.

**Action:** Check the log for details on the error.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**ODI-01818: Agent Service Mbean is not initialized. Re-initialization of agents in tree is disabled.**

**Cause:** A runtime error has occurred.

**Action:** Check the log for details on the error, fix the same and restart the OdiConsole application.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-01819: Event Service Mbean is not initialized. Re-initialization of event notification listeners is disabled.**

**Cause:** A runtime error has occurred.

**Action:** Check log for details on the error, fix the same and restart the OdiConsole application.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-01820: Agent {0} is not up at {1} for reason {2}.**

**Cause:** A runtime error has occurred.

**Action:** Check the log for details on the error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03000: error in creating repository connection {0}**

**Cause:** An unexpected error occurred.

**Action:** Check the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03001: error in updating repository connection {0}**

**Cause:** An unexpected error occurred.

**Action:** Check the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03002: error in deleting repository connection {0}**

**Cause:** An unexpected error occurred.

**Action:** Check the logs.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03016: Creation of Work Repository failed because a previous Work repository was found, and the user had asked not to overwrite any existing repository.**

**Cause:** Work repository already exists and overwriting of the repository was not chosen

**Action:** Select overwriting of Work Repository

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODI-03017: Exception occurred while creating Work Repository at {0} failed. Failure reason {1}.**

**Cause:** An unexpected error occurred.

**Action:** Check the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03018: Test connection failed due to {0}.**

**Cause:** Connection to DB failed

**Action:** Check the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODI-03019: Exception occurred while exporting Master Repository. Failure reason {0}.**

**Cause:** An unexpected error occurred.

**Action:** Check the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODI-03020: Only zip files can be uploaded , the {0} upload was unsuccessful.**

**Cause:** A file with extension other than zip was uploaded.

**Action:** Make sure file uploaded has zip as extension

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODI-03021: Exception occurred while importing Work Repository. Failure reason {0}.**

**Cause:** An unexpected error occurred.

---

**Action:** Check the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODI-03031: Creation of Master Repository failed at {0}.**

**Cause:** Creation of Master Repository Failed

**Action:** Check the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODI-03032: Exception occurred while creating Master Repository at {0} failed.**

**Failure reason {1}.**

**Cause:** An unexpected error occurred.

**Action:** Check the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03033: Supervisor Password and Confirm Supervisor Password fields should match.**

**Cause:** Supervisor Password and Confirm Supervisor Password fields must match

**Action:** Input same passwords

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODI-03034: Test connection failed due to {0}.**

**Cause:** Testing of DB connection failed

**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODI-03035: Supervisor Password and Confirm Supervisor Password fields should match and only zip files can be uploaded , the {0} upload was unsuccessful.**

**Cause:** Both the password match and zip files to be uploaded conditions failed

**Action:** Make sure both the passwords are same and file uploaded is zip file

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODI-03036: Only zip files can be uploaded , the {0} upload was unsuccessful.**

---

**Cause:** zip files to be uploaded condition failed

**Action:** Make sure file uploaded is zip file

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODI-03037: Exception occurred while exporting Master Repository. Failure reason {1}.**

**Cause:** An unexpected error occurred.

**Action:** Check the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03038: Exception occurred while exporting Physical Topology. Failure reason {1}.**

**Cause:** An unexpected error occurred.

**Action:** Check the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03039: Exception occurred while Importing Master Repository. Failure reason {1}.**

**Cause:** An unexpected error occurred.

**Action:** Check the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03046: unable to find the agent for given logical agent and context code**

**Cause:** Physical Agent mapping was not defined for selected logical agent and context.

**Action:** A different set of credentials is required or the mapping needs to be defined.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODI-03047: exception while executing {0}. Failure reason {1}**

**Cause:** An unexpected error occurred.

**Action:** Check the logs.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**ODI-03048: Only XML files can be uploaded: the {0} upload fails**

**Cause:** File selected for import was not a XML file.

**Action:** Provide the XML file.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODI-03049: exception while importing {0}. Failure reason {1}**

**Cause:** An unexpected error occurred.

**Action:** Check the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03076: exception while killing {0}. Failure reason {1}**

**Cause:** An unexpected error occurred.

**Action:** Check the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03077: Selected Session {0} is in {1} State, and therefore cannot be killed.**

**Cause:** The selected session was in Done, Error, or Warning state.

**Action:** No action is required.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODI-03078: Selected Session {0} is in {1} State, and therefore cannot be restarted.**

**Cause:** The selected session was not in Error state.

**Action:** No action is required.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODI-03079: exception while restarting {0}. Failure reason {1}**

**Cause:** An unexpected error occurred.

**Action:** Check the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03080: exception while clearing stale sessions. Failure reason {0}**

---

**Cause:** An unexpected error occurred.  
**Action:** Check the logs.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic

**ODI-03101: import of {1} from {0} failed**  
**Cause:** An unexpected error occurred  
**Action:** Check the logs  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic

**ODI-03102: export of {1} to {0} failed**  
**Cause:** An unexpected error occurred  
**Action:** Check the logs  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic

**ODI-03103: failed to stop a loadplan instance id : {0}**  
**Cause:** An unexpected error occurred  
**Action:** Check the logs  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic

**ODI-03104: failed to start a loadplan : {0}**  
**Cause:** An unexpected error occurred  
**Action:** Check the logs  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic

**ODI-03105: failed to start a scenario : {0} ? {1}**  
**Cause:** An unexpected error occurred  
**Action:** Check the logs1  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic

**ODI-03106: failed to restart session : {0}**  
**Cause:** An unexpected error occurred  
**Action:** Check the logs



---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03107: failed to clean stale sessions for repository : {0}**

**Cause:** An unexpected error occurred

**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03108: failed to stop session : {0}**

**Cause:** An unexpected error occurred

**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03109: Creation of work runtime repository at {0} failed. Failure reason {1}**

**Cause:** An unexpected error occurred

**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03110: Update of work runtime repository at {0} failed. Failure reason {1}**

**Cause:** An unexpected error occurred

**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03111: failed to read config.properties**

**Cause:** An unexpected error occurred

**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03112: shared config dir path is not valid : {0}**

**Cause:** An unexpected error occurred

**Action:** Check the logs

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**ODI-03114: {0} not set**  
**Cause:** An unexpected error occurred  
**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03115: {0} is not correct**  
**Cause:** An unexpected error occurred  
**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03116: failed to read**  
**Cause:** An unexpected error occurred  
**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03117: datasource not located at {0}**  
**Cause:** An unexpected error occurred  
**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03118: Could not get the service locator. JpsServiceLocator service is not configured.**  
**Cause:** An unexpected error occurred  
**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03119: JPS Exception {0} was thrown. Credential Store might not be configured.**  
**Cause:** An unexpected error occurred  
**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**ODI-03120: Credential store could not be found.**

**Cause:** An unexpected error occurred

**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03121: Not populating any values in credential store**

**Cause:** An unexpected error occurred

**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03122: Exception in purging Session/Load Plan Executions**

**Cause:** An unexpected error occurred

**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03123: Exception occurred while inserting usedInContext in Physical Schema**

**Cause:** An unexpected error occurred

**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03124: Exception occurred while deleting usedInContext in Physical Schema**

**Cause:** An unexpected error occurred

**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03125: Exception occurred while inserting usedInContext in Edit Physical Schema**

**Cause:** An unexpected error occurred

**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03126: Exception in adding an entity**

---

**Cause:** An unexpected error occurred  
**Action:** Check the logs  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic

**ODI-03127: Odi object not found**  
**Cause:** An unexpected error occurred  
**Action:** Check the logs  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic

**ODI-03128: Exception in update**  
**Cause:** An unexpected error occurred  
**Action:** Check the logs  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic

**ODI-03129: Unable to find odi object {0}**  
**Cause:** An unexpected error occurred  
**Action:** Check the logs  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic

**ODI-03130: Loading of entity failed**  
**Cause:** An unexpected error occurred  
**Action:** Check the logs  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic

**ODI-03131: Unauthorized to delete entity of type**  
**Cause:** An unexpected error occurred  
**Action:** Check the logs  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic

**ODI-03132: error occurred while executing method**  
**Cause:** An unexpected error occurred  
**Action:** Check the logs

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03133: no repository definition found for alias {0}**

**Cause:** An unexpected error occurred

**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03134: login failed for user {0}=**

**Cause:** An unexpected error occurred

**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03135: version mismatch**

**Cause:** An unexpected error occurred

**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03136: unable to connect to repository with alias {0}**

**Cause:** An unexpected error occurred

**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03137: Error occurred in EMIntegrationServlet.doOperation() - {0}**

**Cause:** An unexpected error occurred

**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03138: failed to init jview diagrammer**

**Cause:** An unexpected error occurred

**Action:** Check the logs

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**ODI-03139: repositories.xml path not set**  
**Cause:** An unexpected error occurred  
**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03140: {0} file does not exist at {1}**  
**Cause:** An unexpected error occurred  
**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03141: failed to create RepositoryDefinitionRegistry**  
**Cause:** An unexpected error occurred  
**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03142: error logging out a user after session expired**  
**Cause:** An unexpected error occurred  
**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03143: Creation of work dev repository at {0} failed. Failure reason {1}**  
**Cause:** An unexpected error occurred  
**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03144: Creation of Master Repository failed at {0}. Failure reason {1}**  
**Cause:** An unexpected error occurred  
**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03146: ???**

---

**Cause:** An unexpected error occurred

**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03147: Delete operation failed**

**Cause:** An unexpected error occurred

**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03148: Maximum number of sessions should be in between 0 and 99999.**

**Cause:** An unexpected error occurred

**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03149: Port Number should not be non negative.**

**Cause:** An unexpected error occurred

**Action:** Check the logs

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03265: Exception occurred while creating Datasource. Failure reason {0}.**

**Cause:** An unexpected error occurred.

**Action:** Check the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03266: Constraint Violation Exception occurred while creating Datasource.**

**Cause:** An unexpected error occurred.

**Action:** Check the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ODI-03267: No valid repository alias is found. Click on management link on top right corner to create one.**

---

**Cause:** Either there were no repository connection aliases, or those that were created did not have a valid JNDI name

**Action:** Create a new repository connection alias.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODI-03276: Tab limit reached.Please close at least one tab.**

**Cause:** Max limit on the number of tabs that can be open has been met.

**Action:** Close at least one tab

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODI-03277: Object cannot be found.**

**Cause:** The object might have been deleted.

**Action:** Refresh your view.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODI-03278: View operation fails with the following exception {0}. See the server log for details.**

**Cause:** An unexpected error occurred.

**Action:** Check the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODI-03279: Add operation failed with the following exception {0}. Please see the server log for details.**

**Cause:** An unexpected error occurred.

**Action:** Check the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODI-03280: Edit operation failed with the following exception {0}. Please see the server log for details.**

**Cause:** An unexpected error occurred.

**Action:** Check the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Data



---

**ODI-03290: You are not authorized to add a new entity of this type.**

**Cause:** User doesn't have required privileges to add an new entity of a particular type

**Action:** No action

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODI-03326: Please specify a valid search text**

**Cause:** Invalid search text was specified

**Action:** Provide a valid search text

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODI-03327: Please choose at least one model or project type.**

**Cause:** No model or project type was selected

**Action:** Select at least one model or project type so that search criteria is valid

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODI-03328: Please choose at least one topology type.**

**Cause:** No topology type was selected

**Action:** Select at least one topology type so that search criteria is valid

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODI-03329: Please choose at least one runtime type.**

**Cause:** No runtime type was selected

**Action:** Select at least one runtime type so that search criteria is valid

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODI-10001: Action unauthorized for this license: {0}**

**Cause:** Action was unauthorized for this license.

**Action:** Choose another license.

**Level:** 32

**Type:** ERROR

**Impact:** Security

**ODI-10002: Only one local repository can be defined; {0} were found.**

---

**Cause:** More than one local repository was found.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10004: File already exists.**

**Cause:** File already existed.

**Action:** Choose another file.

**Level:** 32

**Type:** ERROR

**Impact:** File

**ODI-10005: Repository is expected to be a master repository.**

**Cause:** Repository was expected to be a master repository.

**Action:** Choose master repository.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10006: Repository is expected to be enterprise repository.**

**Cause:** Repository was expected to be an enterprise repository.

**Action:** Choose enterprise repository.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10007: Object must be in editable state before using set methods.**

**Cause:** The object was not in editable state.

**Action:** Edit this object.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10008: Object must be in consult mode before using methods get.**

**Cause:** The object was not in consult mode.

**Action:** Consult the object.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10009: Object does not exist in the repository.**

**Cause:** The repository did not contains this object.

**Action:** Choose another object or create first this one.

---

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10010: This type of object cannot be updated.**

**Cause:** Object could not be updated.

**Action:** Do not update this object.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10011: Invalid object; it has been updated by another user.**

**Cause:** Object was updated by another user.

**Action:** Refresh the object.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10012: Object cannot be inserted**

**Cause:** Object could not be inserted.

**Action:** Check object.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10013: This import action has been cancelled because it could damage your repository (problem with the identifier sequences)**

**Cause:** Import could damage your repository.

**Action:** Check identifier sequences.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10015: The work repository {0} is not declared in this master repository, the import process has been cancelled.**

**Cause:** Work repository was not declared in this master repository.

**Action:** Declare work repository and try again.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10016: Import aborted.**

**Cause:** Import was aborted.

**Action:** Check objects and try again.

---

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10017: This import is forbidden: the text {0} has a different origin in the repository and in the import file.**

**Cause:** The text has a different origin in the repository and in the import file.

**Action:** Check import file and try again.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10018: The repository {0} is not coherent between the current repository and the import file.**

**Cause:** The repository was not coherent between the current repository and the import file.

**Action:** Check import file.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10019: Impossible to create the directory {0}.**

**Cause:** I was not possible to create the directory.

**Action:** Check your system rights for creating directory; directory's path and name.

**Level:** 32

**Type:** ERROR

**Impact:** File

**ODI-10020: Impossible to replace the file**

**Cause:** It was not possible to replace the file.

**Action:** Check, if you have enough rights for this operation.

**Level:** 32

**Type:** ERROR

**Impact:** File

**ODI-10021: Unspecified save directory.**

**Cause:** Directory to save environment information was unspecified.

**Action:** Specify the directory for saving the environment information file.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10022: You must specify all options.**

**Cause:** Missed one or more options.

**Action:** Specify missed options.

---

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10023: Invalid license. This license is suitable for {0}.**

**Cause:** Invalid license.

**Action:** Check license.

**Level:** 32

**Type:** ERROR

**Impact:** Security

**ODI-10024: Your installation of Oracle Data Integrator is corrupted.**

**Cause:** The technology description file contains errors.

**Action:** Reinstall Oracle Data Integrator.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10025: Your installation of Oracle Data Integrator is corrupted.**

**Cause:** The technology description file is missing.

**Action:** Reinstall Oracle Data Integrator.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10026: Error while testing the Master Repository technology.**

**Cause:** Error occurred while testing the Master Repository technology.

**Action:** Check parameters.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10027: The import is cancelled because at least one object is locked by another user.**

**Cause:** At least one object was locked by another user.

**Action:** Check objects' locks.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10028: It is forbidden to import a log into a repository having the same ID.**

**Cause:** The log had the same ID as repository.

**Action:** Check log and/or repository id.

**Level:** 32

---

**Type:** ERROR  
**Impact:** Other  
**ODI-10029: Version {0} for object {1} already exists.**  
**Cause:** Version already existed.  
**Action:** Choose another version.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other  
**ODI-10031: Object {0}: {1} is locked by user {2}**  
**Cause:** Object was locked by another user.  
**Action:** Wait until object is unlocked.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other  
**ODI-10032: You cannot import this object. The referencing objects do not exist in the repository.**  
**Cause:** The referencing objects did not exist in the repository.  
**Action:** Check import file.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other  
**ODI-10033: You cannot delete this object because it is locked by another user ({0}).**  
**Cause:** This object was locked by another user.  
**Action:** Wait until object is unlocked.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other  
**ODI-10034: The technology hosting your master repository does not support Versioning.**  
**Cause:** The technology did not support versioning.  
**Action:** Choose another repository or technology.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other  
**ODI-10035: {0} : {1} violates alternate key constraint {2} {3} for values {4}**  
**Cause:** Object violated alternate key constraint.  
**Action:** Check object properties and constraint's values.  
**Level:** 32

---

**Type:** ERROR  
**Impact:** Other  
**ODI-10036: Importing object {0} : {1} failed.**  
**Cause:** Import failed.  
**Action:** Check import file and try again.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other  
**ODI-10037: Import-replace for this node is supported for action groups only. The import file is invalid.**  
**Cause:** Import-replace for this node was supported for action groups only.  
**Action:** Check import file.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other  
**ODI-10038: The interface you are trying to use ({0}) is related to a logical schema ({1}) that no longer exists.**  
**Cause:** Logical schema was not found.  
**Action:** Check interface.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other  
**ODI-10040: Cannot create directory**  
**Cause:** Directory could not be created.  
**Action:** Check directory path/name.  
**Level:** 32  
**Type:** ERROR  
**Impact:** File  
**ODI-10044: Unable to save the interface. Maximum number of source datastores exceeded.**  
**Cause:** Maximum number of source datastores was exceeded.  
**Action:** Contact Oracle Support Services.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other  
**ODI-10045: a2.getCargo() not instance of SAPSegment**  
**Cause:** a2.getCargo() not instance of SAPSegment  
**Action:** Check SAP Tree.  
**Level:** 32

---

**Type:** ERROR  
**Impact:** Other

**ODI-10046: No IDoc.**  
**Cause:** Missed IDoc.  
**Action:** Check IDoc.

**Level:** 32  
**Type:** ERROR  
**Impact:** Other

**ODI-10047: Repository is not a development work repository**  
**Cause:** Repository was not a development work repository.  
**Action:** Choose development work repository.

**Level:** 32  
**Type:** ERROR  
**Impact:** Other

**ODI-10048: No work repository found.**  
**Cause:** No work repository was found.  
**Action:** Check your connection settings or database.

**Level:** 32  
**Type:** ERROR  
**Impact:** Other

**ODI-10049: Missing parameter**  
**Cause:** Parameter was missing.  
**Action:** Check all parameters.

**Level:** 32  
**Type:** ERROR  
**Impact:** Other

**ODI-10050: Missing parameter at: {0} SQL: {1}**  
**Cause:** Parameter was missing.  
**Action:** Check all parameters.

**Level:** 32  
**Type:** ERROR  
**Impact:** Other

**ODI-10051: Some objects cannot be exported because they do not exist in the repository: {0} {1}**  
**Cause:** Objects did not exist in the repository.  
**Action:** Check objects state.

**Level:** 32  
**Type:** ERROR



---

**Impact:** Other

**ODI-10052: A problem occurred in your repository.**

**Cause:** A problem occurred in your repository.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10053: Problem retrieving JCOFunction object. {0}**

**Cause:** Problem occurred retrieving JCOFunction object.

**Action:** Check JCO Function object.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10054: Unable to find the XML file corresponding to your technology.**

**Cause:** XML file corresponding to your technology was not found.

**Action:** Check technology and/or XML file for the technology.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10055: This ID is already in use in the repository**

**Cause:** This ID was already in use in the repository.

**Action:** Change ID.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10056: This repository ID already exists. This repository cannot be created.**

**Cause:** Repository ID already existed.

**Action:** Change repository ID.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10057: Unrecognized export type.**

**Cause:** Export type was unrecognized.

**Action:** Check export type.

**Level:** 32

**Type:** ERROR

**Impact:** Other

---

**ODI-10058: You are trying to import objects from a master repository of an older version into {0} version. This action is forbidden. Master repositories must be upgraded using the upgrade assistant, not using the export/import facility.**

**Cause:** You tried to import objects from a master repository of an older version.

**Action:** Master repositories must be upgraded using the upgrade assistant, not using the export/import facility.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10059: Repository is null**

**Cause:** Repository was null.

**Action:** Check repository.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10060: Saputil is mandatory.**

**Cause:** Saputil was mandatory.

**Action:** Check Saputil

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10061: Empty XML Character Set**

**Cause:** XML Character Set was empty.

**Action:** Fill XML Character Set.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10062: Unable to find license key {0}. An exception {1} occurred with message: {2}**

**Cause:** An exception occurred.

**Action:** Check license key.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10063: Unable to check the license key. An exception {0} occurred with message: {1}**

**Cause:** An exception occurred.

**Action:** Check license key.

**Level:** 32

---

Type: ERROR

Impact: Other

**ODI-10064: The interface must have a JMS datastore as a source or target. Another license is required otherwise.**

**Cause:** The interface must have a JMS datastore as a source or target.

**Action:** Check datastore type and/or license.

Level: 32

Type: ERROR

Impact: Other

**ODI-10065: Your license does not include these features. Please contact your reseller.**

**Cause:** Your license does not include these features.

**Action:** Please contact your reseller.

Level: 32

Type: ERROR

Impact: Other

**ODI-10066: The interface is using a Datastore defined in Model "{0}" which is linked to a logical schema "{1}" that no longer exists.**

**Cause:** Logical schema was not found.

**Action:** Correct interface.

Level: 32

Type: ERROR

Impact: Other

**ODI-10067: Target file already exists.**

**Cause:** Target file already existed.

**Action:** Choose another target file name.

Level: 32

Type: ERROR

Impact: File

**ODI-10068: SnpsConnection: Isolation level not supported**

**Cause:** Isolation level not supported.

**Action:** Check isolation level.

Level: 32

Type: ERROR

Impact: Other

**ODI-10069: Unsupported XML Character Set: {0}**

**Cause:** Unsupported XML Character Set.

**Action:** Check XML charset.

Level: 32

---

**Type:** ERROR  
**Impact:** Other  
**ODI-10070: Cannot delete this object. It is being edited or viewed**  
**Cause:** Object was being edited or viewed.  
**Action:** Stop edit or view object and try again.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other  
**ODI-10071: Cannot delete this object**  
**Cause:** Could not delete this object.  
**Action:** Check object state.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other  
**ODI-10073: A repository already exists on this data server**  
**Cause:** A repository already existed on this data server.  
**Action:** Choose another data server.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other  
**ODI-10080: Incorrect License ....**  
**Cause:** Incorrect License.  
**Action:** Contact your seller.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other  
**ODI-10081: You are not authorized to Insert the Object: {0}: {1} / {2}**  
**Cause:** You were not authorized to Insert the Object.  
**Action:** Login with user with right privileges.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Security  
**ODI-10082: You are not authorized to View the Object: {0}: {1}**  
**Cause:** You were not authorized to View the Object.  
**Action:** Login with user with right privileges.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Security

---

**ODI-10083: You are not authorized to Delete the Object: {0}: {1} / {2}**

**Cause:** You were not authorized to Delete the Object.

**Action:** Login with user with right privileges.

**Level:** 32

**Type:** ERROR

**Impact:** Security

**ODI-10084: You are not authorized to Edit the Object: {0}: {1} / {2}**

**Cause:** You were not authorized to Edit the Object.

**Action:** Login with user with right privileges.

**Level:** 32

**Type:** ERROR

**Impact:** Security

**ODI-10085: You cannot consult this object**

**Cause:** You could not consult this object.

**Action:** Login with user with right privileges.

**Level:** 32

**Type:** ERROR

**Impact:** Security

**ODI-10086: You cannot edit this object**

**Cause:** You could not edit this object.

**Action:** Login with user with right privileges.

**Level:** 32

**Type:** ERROR

**Impact:** Security

**ODI-10087: You can only give Supervisor Access Privileges if you are a Supervisor.**

**Cause:** You could only give Supervisor Access Privileges if you are a Supervisor.

**Action:** Login with user with right privileges.

**Level:** 32

**Type:** ERROR

**Impact:** Security

**ODI-10088: Empty Java Character Set.**

**Cause:** Java Character Set was empty.

**Action:** Fill Java charset.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10089: You cannot modify another user's password**

**Cause:** You cannot modify another user's password

---

**Action:** Login with user with right privileges.

**Level:** 32

**Type:** ERROR

**Impact:** Security

**ODI-10090: Object {0} {1} is referenced by: {2}. Cannot remove.**

**Cause:** Object was referenced by another one.

**Action:** Check object's references.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10092: Some objects cannot be exported. They do not exist in the repository.**

**Cause:** Objects did not exist in the repository.

**Action:** Check objects' state.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10093: You are importing an object from another repository with the same identifier. It is forbidden.**

**Cause:** You tried to import an object from another repository with the same identifier.

**Action:** Change repository ID.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10094: Problem while computing new name.**

**Cause:** A problem occurred while computing new name.

**Action:** Try again.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10098: No connection available. Check connection parameters.**

**Cause:** No connection was available.

**Action:** Check connection parameters.

**Level:** 32

**Type:** ERROR

**Impact:** Network

**ODI-10099: Object cannot be exported because the file with name {0} could not be created.**

**Cause:** Object could not be exported because the file could not be created.

---

**Action:** Check your system rights to write files and file name.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10100: Empty XML Version**

**Cause:** XML version was empty.

**Action:** Fill XML Version.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-10101: Invalid XML Version: {0}**

**Cause:** XML Version was invalid.

**Action:** Check XML version.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-14064: Error while applying DDL from file {0}**

**Cause:** Exception during execution of session.

**Action:** Check session.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-14066: upgrade error while executing {0} params = {1}**

**Cause:** Wrong parameters at Sql query.

**Action:** Check parameters.

**Level:** 32

**Type:** ERROR

**Impact:** Upgrade

**ODI-15000: BSF Not Present**

**Cause:** Bean Scripting Framework manager cannot be found.

**Action:** Ensure that class org.apache.bsf.BSFManager is available in the classpath.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15001: No End Separator for the following text:**

**Cause:** No end delimiter found for a delimited text in the expression.

**Action:** Add an end delimiter to the delimited text.

- 
- Level:** 32  
**Type:** ERROR  
**Impact:** Programmatic
- ODI-15002: The string to be transformed cannot be null.**  
**Cause:** Parsing failed for an expression reference tag.  
**Action:** Fix the expression.
- Level:** 32  
**Type:** ERROR  
**Impact:** Programmatic
- ODI-15003: Error during Code Interpreter creation**  
**Cause:** Code generator internal error.  
**Action:** Contact Oracle support.
- Level:** 32  
**Type:** ERROR  
**Impact:** Programmatic
- ODI-15005: The datatype source: {0} for the technology: {1} does not exist.**  
**Cause:** The datatype for a column is not supported by the technology.  
**Action:** Change the datatype or the technology of the execution location.
- Level:** 32  
**Type:** ERROR  
**Impact:** Programmatic
- ODI-15006: The source datatype is null for the column: {0}, and the technology: {1}**  
**Cause:** The datatype for a column is null for the technology.  
**Action:** Change the datatype or the technology of the execution location.
- Level:** 32  
**Type:** ERROR  
**Impact:** Programmatic
- ODI-15007: Syntax not set for 'Create Table' for the datatype: {0} for the technology: {1}.**  
**Cause:** The execution location technology does not have any "Create Table" syntax set up.  
**Action:** Edit the technology definition and add "Create Table" syntax.
- Level:** 32  
**Type:** ERROR  
**Impact:** Programmatic
- ODI-15009: No text for the 'Writable Datatype Syntax' for the datatype: {0} in technology: {1}**  
**Cause:** The datatype does not have a "Writable Datatype Syntax" property value set up for the execution location technology.



---

**Action:** Edit the datatype in the technology to add a "Writable Datatype Syntax".

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15010: No conversion for the datatype {0}, for the source technology {1} and for the target technology {2}**

**Cause:** No conversion is defined for the source technology datatype to the target technology datatype.

**Action:** Edit the source or target technology datatype to add a conversion from the source to the target datatype.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15011: The variable does not exist in the database.**

**Cause:** A variable is being referenced but it does not exist in the repository.

**Action:** Create the variable in the repository.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15012: Sequence does not exist in database**

**Cause:** A sequence is referenced but does not exist in the repository.

**Action:** Create the sequence in the repository.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15013: The table {0} has fatal errors.**

**Cause:** The table cannot be processed.

**Action:** Check the table for inconsistencies.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15014: The referenced text does not exist in the database.**

**Cause:** The text reference in the expression does not exist in the repository.

**Action:** Repository corruption has occurred, contact Oracle support.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15015: Too much recursion in this text resolution.**

**Cause:** The expression text references other text recursively too many times.

---

**Action:** Review the expression and try to simplify.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15016: Commands Undefined.**

**Cause:** KM is missing a block of lines.

**Action:** Check the KM.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15017: Table not selected (null).**

**Cause:** Target table not found.

**Action:** Check interface for consistency.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15018: CKM not selected.**

**Cause:** The CKM is not selected for the object.

**Action:** Select a CKM.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15019: Missing context**

**Cause:** The context object cannot be found.

**Action:** Check the context selection.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15020: No JKM available**

**Cause:** JKM has not been set or is not found.

**Action:** Set a valid JKM for the interface.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15021: Journalizing requires a Primary Key on the Table:**

**Cause:** Journalizing is enabled, but the target table has no primary key.

**Action:** Add a primary key to the target table.

---

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15022: No RKM Set.**

**Cause:** RKM has not been set or is not found.

**Action:** Set a valid RKM for the object.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15023: Cannot perform standard reverse. Choose customized reverse and set RKM.**

**Cause:** Standard reverse engineering is not supported for this object.

**Action:** Select customized reverse engineering for the object and select an RKM.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15025: The interface clause text does not exist.**

**Cause:** The interface clause refers to text that does not exist.

**Action:** Check interface clauses for (join, filter, etc.) for consistency.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15026: Interface clauses are missing.**

**Cause:** the code generator cannot find the clause collection for the interface.

**Action:** Check the interface for consistency.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15027: Interface source tables are missing.**

**Cause:** the code generator cannot find the source table collection for the interface.

**Action:** Check the interface for consistency.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15028: Interface result collection is null.**

**Cause:** Internal error.

**Action:** Contact Oracle support.

**Level:** 32

---

**Type:** ERROR

**Impact:** Programmatic

**ODI-15029: Interface error clause collection is missing.**

**Cause:** Internal error.

**Action:** Contact Oracle support.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15030: Interface is missing the integration work table collection.**

**Cause:** Internal error.

**Action:** Contact Oracle support.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15031: Technology not selected.**

**Cause:** No technology is selected for the interface target execution location.

**Action:** Check the technology selection for the interface target.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15032: Unknown object in interface source table collection**

**Cause:** Internal Error.

**Action:** Contact Oracle support.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15033: The expression: {0} does not have an associated column.**

**Cause:** The expression should represent a column, but no column is found for the name.

**Action:** Fix the expression.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15034: A scenario with the same name and the same number already exists.  
Please select other values.**

**Cause:** Cannot create a duplicate scenario with the same name and version number as an existing scenario.

**Action:** Give the scenario a different name or version.

**Level:** 32

---

**Type:** ERROR

**Impact:** Programmatic

**ODI-15036: Scenario's name and/or number are missing.**

**Cause:** A scenario must have a name and version, but the name or version is missing.

**Action:** Set values for name and version for the scenario.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15037: The interface {0} has fatal errors.**

**Cause:** The interface has fatal errors.

**Action:** Check and fix interface issues.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15038: The scenario name substitution pattern {0} is not supported. Please check the user parameter for the scenario naming convention.**

**Cause:** Invalid substitution pattern used for scenario name.

**Action:** Change the substitution pattern.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15039: The interface {0} use native sequence. Native sequence are not allowed for Derived Table (sub select statement)**

**Cause:** Native sequence was used in a sub-select or derived interface.

**Action:** Remove the native sequence usage.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15040: Errors detected when building SQL clauses.**

**Cause:** An error occurred when generating code for the SQL clauses.

**Action:** Fix the interface clauses.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15041: An aggregation function may not be used in a join condition. Please use a separate interface for the aggregation and join the result in this interface.**

**Cause:** An aggregation function was used inside a join condition expression.

**Action:** Change the join condition to remove the aggregation function.

---

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15042: Unable to regenerate this scenario. It references an package that does not exist.**

**Cause:** The scenario must reference a package, but it does not.

**Action:** Delete the scenario and create a new one.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15043: Unable to regenerate this scenario from a Runtime repository.**

**Cause:** The scenario must cannot be regenerated from the runtime repository.

**Action:** Delete the scenario and create a new one.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15044: Invalid pScenSource type when calling  
SnpGeneratorSQLCIT.mainGenScenSourceScenario**

**Cause:** Internal error.

**Action:** Contact Oracle support.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15045: Invalid value for KM type.**

**Cause:** An invalid value was specified for the KM type.

**Action:** Specify a valid value.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15046: The column cache is null during code generation.**

**Cause:** Internal Error.

**Action:** Contact Oracle support.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15047: The cached column is null in the column cache during code generation.**

**Cause:** Internal Error.

**Action:** Contact Oracle support.

---

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15050: Flow Control not possible if no key is declared in your target datastore**

**Cause:** Flow control is enabled for the interface, but the target datastore has no primary key defined.

**Action:** Define a primary key for the target datastore object, and re-add the target datastore.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15051: Missing mapping instance for interface.**

**Cause:** The target column does not have any mapping.

**Action:** Add a mapping expression for the target column.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15052: The interface is missing a dataset.**

**Cause:** There is no dataset for the interface source.

**Action:** Check the interface for consistency.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15055: Character "]" missing in: {0}.**

**Cause:** A bracketed tag inside a KM line is missing a closing bracket ("]") character.

**Action:** Fix the KM line.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15057: Non-ordered outer join not supported for technology.**

**Cause:** Non-ordered outer join syntax disabled for technology.

**Action:** Correct join.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15059: I\_TXT is mandatory.**

**Cause:** A call was made to SnpTxtCachedHashMap.getInstance, but the pITxt parameter was null.

---

**Action:** Contact Oracle support.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15060: The JKM line {0} uses an unsupported execution channel: {1}**

**Cause:** A line in the JKM uses an execution channel that is not supported.

**Action:** Change the line in the JKM to use a supported channel.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15061: The JKM line {0} uses an unsupported commit type: {1}**

**Cause:** A line in the JKM uses a commit type that is not supported.

**Action:** Change the line in the JKM to use a supported commit type.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15062: Invalid commit type: {0}**

**Cause:** An invalid commit type was passed to  
SnpServiceGenerator.convertCommitType

**Action:** Contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15063: The alternate key {0} is not unique.**

**Cause:** An alternate key defined by the repository is found to be non-unique.

**Action:** Check the data or the alternate key definitions.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15064: The primary key {0} is not unique.**

**Cause:** A primary key defined by the repository is found to be non-unique.

**Action:** Check the data or primary key definitions.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15065: Join error ({0}) between the table {1} and the table {2}.**

**Cause:** A foreign key relationship is not found.



---

**Action:** A foreign key relationship between 2 tables defined in the repository is not valid.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15066: The column {0} cannot be null.**

**Cause:** The column is marked in the repository as not nullable.

**Action:** Check the data, or change the not null value.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15067: The datatype value "{0}" is incorrect.**

**Cause:** An invalid datatype has been found.

**Action:** The repository table contains an invalid datatype.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15068: Unknown flexfield code.**

**Cause:** An undefined flex field code is being referenced

**Action:** Check the flex field references in the KM, and the flex field definitions

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15069: {0} Is not valid without session context.**

**Cause:** A current session context does not exist.

**Action:** Check session definition.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15070: Unable to find method object: PythonInterpreter.initialize(Properties, Properties, String[]) method**

**Cause:** The python method used by the script is not found.

**Action:** Check the KM step.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-15071: Error occurred**

**Cause:** An exception was thrown while executing a python script in the KM step.

---

**Action:** Check the cause.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-15072: There is no PK constraint**

**Cause:** There is a call to "getPK" in the KM, but no PK is found.

**Action:** Check the KM and the PK definitions.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15073: There is no index**

**Cause:** There is a call to "getIndex" in the KM, but no index is found.

**Action:** Check the KM and the index definitions.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15076: no dataset**

**Cause:** A KM line is calling "getDataSet", but no data set is found.

**Action:** Check the KM or the DataSet definitions.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15077: No Current Model Set**

**Cause:** There is a call to "getModel" in the KM, but no model is found.

**Action:** Check the KM and the model definitions.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15078: There is no Not Null column**

**Cause:** There is a call to "getNotNullCol" in the KM, but no not null column is found.

**Action:** Check the KM and the not null column definitions.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15079: There is no current Pop.**

**Cause:** There is a call to "getPop" in the KM, but no interface is found.

**Action:** Check the KM and the interface definitions.

---

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15080: There is no Step**

**Cause:** There is a call to "getStep" in the KM, but no step is found.

**Action:** Check the KM and the step definitions.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15081: There is no Target Table**

**Cause:** There is a call to "getTargetTable" in the KM, but no target table is found.

**Action:** Check the KM and the interface target table definitions.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15083: Multiple Primary Keys have been detected for {0} .**

**Cause:** A repository table can only have one primary key defined, but multiple primary keys are defined.

**Action:** Edit the table's primary key definitions and remove all but one.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15084: There is no session**

**Cause:** There is a call to "getSession" in the KM, but no session is found.

**Action:** Check the KM and the session definitions.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15085: The value : "{0}" is unknown.**

**Cause:** A KM line has a templated call which contains an unknown bracketed property.

**Action:** Fix the KM.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15086: There is no Temporary Index**

**Cause:** There is a call to "getTemporaryIndex" in the KM, but no temporary index is found.

**Action:** Check the KM and the temporary index definitions.

---

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15087: There is no current execution context defined.**

**Cause:** There is a call to "getContext" in the KM, but no context is found.

**Action:** Check the KM and the context definitions.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15088: Not in designer mode**

**Cause:** A KM line has a call to access design information, but the interpretation location is not set to designer.

**Action:** Make sure that the interpretation location is set to designer when this line is executed.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15089: asked '({0})' and available value are between 0 and ({1}).**

**Cause:** A KM line is calling "getDataSet", but the specified index is out of range.

**Action:** Fix the KM or the DataSet definitions.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15090: Table "{0}" not found on model "{1}", schema "{2}"**

**Cause:** Attempt to initialize data services from a table that cannot be found

**Action:** Change data services reference or make sure that table exists

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15091: Impossible to connect to JPS MBean Server**

**Cause:** Cannot connect to JPS MBean server.

**Action:** Internal Error.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-15092: Unable to generate data service - the column {0} does not exist in the database.**

**Cause:** A data service references a column that does not exist

**Action:** Fix the data service reference or make sure that the column exists

---

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15093: Unable to regenerate this scenario. It references a null package.**

**Cause:** The scenario must reference a package, but the package is null.

**Action:** Delete the scenario and create a new one.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15094: You must give a name for the published entity for each datastore.**

**Cause:** A web services data store does not have a name.

**Action:** Give the data store a name.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-15095: Invalid entity for datastore: {0}**

**Cause:** A web services data store has an invalid entity.

**Action:** Associate the data store with a valid entity.

**Level:** 32

**Type:** SET\_AT\_RUNTIME

**Impact:** Other

**ODI-15096: Property name must not be null.**

**Cause:** The KM line is calling "isColAttrChanged", but the property value is null.

**Action:** Internal error, contact Oracle support.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15097: Unknown value {0} for property**

**Cause:** The KM line is making a templated call, but the property value is unknown.

**Action:** Fix the KM.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15098: You must define a data source for the model.**

**Cause:** The model used by a web service does not have any data source.

**Action:** Define a data source for the model.

**Level:** 32

---

**Type:** SET\_AT\_RUNTIME

**Impact:** Other

**ODI-15099: You must specify a JKM for the model.**

**Cause:** The model used by a web service does not have an associated JKM.

**Action:** Define a JKM for the model.

**Level:** 32

**Type:** SET\_AT\_RUNTIME

**Impact:** Other

**ODI-15100: You must define a Java package for the model.**

**Cause:** The model used by a web service does not have an associated Java package.

**Action:** Define a Java package for the model.

**Level:** 32

**Type:** SET\_AT\_RUNTIME

**Impact:** Other

**ODI-15101: Invalid Java package format: {0}**

**Cause:** The Java package associated with a model has an invalid package format.

**Action:** Correct the package format for the model.

**Level:** 32

**Type:** SET\_AT\_RUNTIME

**Impact:** Other

**ODI-15103: Invalid namespace: {0}**

**Cause:** A model namespace used by a web service is invalid.

**Action:** Correct the namespace for the model.

**Level:** 32

**Type:** SET\_AT\_RUNTIME

**Impact:** Other

**ODI-15104: You must specify an SKM for the model.**

**Cause:** A model used by a web service does not have an associated SKM.

**Action:** Add an SKM to the model.

**Level:** 32

**Type:** SET\_AT\_RUNTIME

**Impact:** Other

**ODI-15105: You must specify which schema the model will be deployed to.**

**Cause:** No web service deployment schema is specified for the model.

**Action:** Specify a schema to which the model will be deployed.

**Level:** 32

**Type:** SET\_AT\_RUNTIME

---

**Impact:** Other

**ODI-15106: You must specify a name for the Data Service for the model.**

**Cause:** The data service for the model does not have a name.

**Action:** Set a valid name for the data service.

**Level:** 32

**Type:** SET\_AT\_RUNTIME

**Impact:** Other

**ODI-15107: Invalid model name: {0}. It should follow the Java identifiers naming conventions.**

**Cause:** The web service model name does not follow the standard Java identifier naming convention.

**Action:** Set a valid name for the model.

**Level:** 32

**Type:** SET\_AT\_RUNTIME

**Impact:** Other

**ODI-15108: Invalid model Data Service name: {0}. It should follow the Java identifiers naming conventions.**

**Cause:** The web service model Data Service name does not follow the standard Java identifier naming convention.

**Action:** Set a valid name for the model Data Service.

**Level:** 32

**Type:** SET\_AT\_RUNTIME

**Impact:** Other

**ODI-15109: Invalid web service name for datastore: {0}**

**Cause:** The web service model data store has an invalid name.

**Action:** Set a valid name for the model data store.

**Level:** 32

**Type:** SET\_AT\_RUNTIME

**Impact:** Other

**ODI-15110: SKM is empty**

**Cause:** The web service SKM has no valid lines.

**Action:** Add some lines to the SKM.

**Level:** 32

**Type:** SET\_AT\_RUNTIME

**Impact:** Other

**ODI-15111: Problem during deployment**

**Cause:** Internal error.

**Action:** Contact Oracle support.

**Level:** 32

---

**Type:** SET\_AT\_RUNTIME

**Impact:** Deployment

**ODI-15113: Reverse table {0} for model {1} already exists.**

**Cause:** An attempt was made to reverse engineer a table, but it already exists in the model.

**Action:** Move or rename the data store in the model, or skip reverse engineering for the table.

**Level:** 32

**Type:** SET\_AT\_RUNTIME

**Impact:** Other

**ODI-15116: There is not enough data in the target file to proceed with the reverse-engineering. Please make sure the file has at least one non-empty line and number of rows to skip is correct.**

**Cause:** An attempt was made to reverse engineer a target file that is empty, or the number of skipped rows is larger than the number of rows in the file.

**Action:** Set the number of skipped lines to a lower value, or add some data to the file.

**Level:** 32

**Type:** SET\_AT\_RUNTIME

**Impact:** Other

**ODI-15117: Not allowed (OLD and NEW are involved)**

**Cause:** The KM line is calling "getColumn", but the ADH action origin is not "NEW" or "OLD".

**Action:** Change the ADH action origin.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15118: Invalid FTP URL**

**Cause:** The URL given for a web services FTP connection is not correct.

**Action:** Check the URL for the FTP connection.

**Level:** 32

**Type:** SET\_AT\_RUNTIME

**Impact:** Network

**ODI-15119: Column {0} has no Java datatype.**

**Cause:** The column being processed has no java datatype.

**Action:** Internal Error: contact Oracle support.

**Level:** 32

**Type:** SET\_AT\_RUNTIME

**Impact:** Programmatic

**ODI-15120: Column {0} has no String datatype.**



---

**Cause:** The column being processed has no string datatype.

**Action:** Internal Error: contact Oracle support.

**Level:** 32

**Type:** SET\_AT\_RUNTIME

**Impact:** Programmatic

**ODI-15121: Selector must be not null**

**Cause:** The ADH selector value must not be null when "getColumn" is called from the KM line.

**Action:** Change the ADH selector value.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15122: Exception getPKColList**

**Cause:** An exception was found when calling "getPKColList" during KM execution.

**Action:** Fix the KM or the PK definitions.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15123: There is no AK constraint**

**Cause:** There is a call to "getAK" in the KM, but no AK is found.

**Action:** Check the KM and the AK definitions.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15125: Missing DataSet.**

**Cause:** The interface is missing a dataset.

**Action:** Check interface for consistency.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15126: The sub-model must be set.**

**Cause:** The sub-model is not set for the source or target.

**Action:** Check the interface for consistency.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15127: There is no CK constraint**

---

**Cause:** There is a call to "getCK" in the KM, but no CK is found.

**Action:** Check the KM and the CK definitions.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15128: There is no FK constraint**

**Cause:** There is a call to "getFK" in the KM, but no FK is found.

**Action:** Check the KM and the FK definitions.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15129: Selector value must be 'OLD' or 'NEW'**

**Cause:** The ADH selector value must be 'OLD' or 'NEW' when "getColumn" is called from the KM line.

**Action:** Change the ADH selector value.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15130: Unknown object in interface source table list**

**Cause:** Internal Error.

**Action:** Contact Oracle support.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15131: You must define the name of each web service to be generated for each datastore.**

**Cause:** A web service associated with a data store has no name.

**Action:** Give a name to the web service.

**Level:** 32

**Type:** SET\_AT\_RUNTIME

**Impact:** Other

**ODI-15132: Exception getPK**

**Cause:** An exception was found when calling "getPK" during KM execution.

**Action:** Fix the KM or the PK definitions.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15135: There is no current index.**

---

**Cause:** The current index can not be found for the property name.

**Action:** Check the reference.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-15140: Unable to regenerate the following scenario:**

**Cause:** The scenario must reference a package, but it does not

**Action:** Delete the scenario and create a new one

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15141: Repository is not a development work repository**

**Cause:** When getting a connection used to execute the KM, it was determined that the provided connection information does not point to a development work repository

**Action:** Fix the connection information

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15142: [PROPERTY: {0}] not found.]**

**Cause:** The bracketed property in the KM line (e.g. "[COL\_NAME]") is not found.

**Action:** Fix the KM line to specify a correct property name.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15143: Invalid isolation level : {0}**

**Cause:** An invalid isolation level value was passed to SnpServiceGenerator.convertIsolationLevel

**Action:** Contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15200: Tried to retrieve an int with an {0} object**

**Cause:** Attempted to read the column from RDB as an integer, but the column type is not integer

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

---

**ODI-15201: Tried to retrieve a short with an {0} object**

**Cause:** Attempted to read the column from RDB as a short type, but the column type is not short

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15202: This resultset accepts only FETCHFORWARD requests**

**Cause:** Attempted to set the fetch direction to something other than FETCH\_FORWARD for a RDB result set read

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15203: This function is unsupported: the software you are using might not be compatible with this driver.**

**Cause:** A jdbc call was made that is not supported by the currently loaded jdbc driver for RDB

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15204: The {0} call is not implemented in this result set class.**

**Cause:** A result set call was made that is not implemented by the ODI RDB result set class

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15205: The call is not supported in this result set class.**

**Cause:** A result set call was made that is not supported by the ODI RDB result set class

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15207: Unmanaged numeric type {0}**

**Cause:** When selecting a parent row based on a primary key, multiple rows were returned

**Action:** Internal Error: contact Oracle support

---

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15208: The PK column of the root table has an unknown type: {0}**

**Cause:** When unloading data from the RDB, the PK column of the parent table has an unknown type

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15209: Unsupported technology (Driver: {0}, Url: {1})**

**Cause:** The jdbc driver is not supported by the ODI RDB

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15210: Unsupported technology: HSQL cannot create FKs after the tables have been created**

**Cause:** The Hypersonic SQL engine cannot create FK after the table is already created

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15211: Unsupported technology: HSQL cannot create PKs after the tables have been created**

**Cause:** The Hypersonic SQL engine cannot create PK after the table is already created

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15212: Datatype NULL (0) unsupported**

**Cause:** The Hypersonic SQL engine does not support the null datatype

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15213: JDBC Datatype '{0}' unsupported**

---

**Cause:** The Hypersonic SQL engine does not support the datatype  
**Action:** Internal Error: contact Oracle support  
**Level:** 32  
**Type:** ERROR  
**Impact:** Programmatic

**ODI-15214: JDBC Datatype '{0}' with length parameter unsupported**  
**Cause:** The Hypersonic SQL engine does not support the datatype with length  
**Action:** Internal Error: contact Oracle support  
**Level:** 32  
**Type:** ERROR  
**Impact:** Programmatic

**ODI-15215: JDBC Datatype '{0}' with length and scale parameters unsupported**  
**Cause:** The Hypersonic SQL engine does not support the datatype with scale  
**Action:** Internal Error: contact Oracle support  
**Level:** 32  
**Type:** ERROR  
**Impact:** Programmatic

**ODI-15216: JDBC Datatype '{0}' unsupported**  
**Cause:** The internal MS Sql Server database does not support the datatype  
**Action:** Internal Error: contact Oracle support  
**Level:** 32  
**Type:** ERROR  
**Impact:** Programmatic

**ODI-15217: JDBC Datatype '{0}' with length parameter unsupported**  
**Cause:** The internal MS SQL Server database does not support the datatype with length  
**Action:** Internal Error: contact Oracle support  
**Level:** 32  
**Type:** ERROR  
**Impact:** Programmatic

**ODI-15218: JDBC Datatype '{0}' with length and scale parameters unsupported**  
**Cause:** The internal MS SQL Server database engine does not support the datatype with length and scale  
**Action:** Internal Error: contact Oracle support  
**Level:** 32  
**Type:** ERROR  
**Impact:** Programmatic

**ODI-15219: Please transform your URL into: {0};SelectMethod=cursor**

---

**Cause:** The internal MS SQL Server database engine does not recognize the supplied URL

**Action:** Change the format of the connection URL

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15220: need length param**

**Cause:** The internal Oracle database does not support the selected type without a length param

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15221: Datatype NULL (0) unsupported**

**Cause:** The internal Oracle SQL engine does not support the null datatype

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15222: JDBC Datatype '{0}' unsupported**

**Cause:** The internal Oracle database does not support the datatype

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15223: JDBC Datatype '{0}' with length parameter unsupported**

**Cause:** The internal Oracle database does not support the datatype with length

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15224: JDBC Datatype '{0}' with length and scale parameters unsupported**

**Cause:** The internal Oracle database engine does not support the datatype with length and scale

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

---

**ODI-15225: No key found on table {0}**

**Cause:** The internal database table does not have a key

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15226: The root table {0} has no data**

**Cause:** The internal database table does not have any data

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15227: Multiple keys found on table {0}**

**Cause:** The internal database table has multiple keys

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15228: \*\*\* FATAL \*\*\* Table {0} could not be validated**

**Cause:** The internal database cannot validate the table

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15229: \*\*\* FATAL \*\*\* Table {0} could not be found**

**Cause:** The internal database cannot find the table

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15230: Could not convert object {0} to a {1}**

**Cause:** The internal database cannot convert the datatype of the selected column

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15231: No '=' sign found on line {0} of bundle {1}**



---

**Cause:** The internal database engine encountered a syntax error when reading the property file

**Action:** Fix the property file

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15232: The alias {0} for table {1} is already used by another table, when reading bundle {2}**

**Cause:** The internal database found a duplicate table alias in a property file

**Action:** Fix the property file

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15233: Table {0} is used twice. Make sure that the table names and aliases do not conflict.**

**Cause:** The internal database found a duplicate table name in the property bundle

**Action:** Fix the property file

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15234: Internal RDB database table {0} not found**

**Cause:** The requested table cannot be found in the internal database

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15235: Internal RDB database key {0} not found**

**Cause:** The requested key cannot be found in the internal database

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15236: Unknown table {0}**

**Cause:** The requested table cannot be found in the internal database

**Action:** Correct the model

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

---

**ODI-15237: Duplicate table**

**Cause:** The internal database table is a duplicate table

**Action:** Correct the model

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15238: Could not find table although we should have created it!**

**Cause:** The newly created table cannot be found

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15239: Only SnpsRDBDiffActionImportDifference are supported for now.**

**Cause:** When processing diff actions in a diff operation, an unsupported diff action class was found

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15240: Unknown key {0}**

**Cause:** When processing diff actions in a diff operation, a nonexistent key was specified by the diff action

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15241: This type of difference is not managed for now: {0}**

**Cause:** When processing diff actions in a diff operation, an unsupported diff action class was found

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15242: Unknown difference type: {0}**

**Cause:** When processing diff actions in a diff operation, an unknown diff class was found

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

---

**Impact:** Programmatic

**ODI-15243: Bad model number: {0}**

**Cause:** When processing diff actions in a diff operation, the 2 models that are being compared are internally numbered as model 1 and 2. A model number other than 1 or 2 was used internally in a call to getModel.

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15244: Could not add a key because {0} is not an ID key.**

**Cause:** When building a model, the specified key class instance was not an id key

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15246: Unknown key type: {0}**

**Cause:** When building a model, an unknown key class was found

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15247: The table {0} cannot be found. It is referenced by key: {1}.**

**Cause:** When building a model, an table name is referenced by a key, but the table cannot be found

**Action:** Check the model

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15248: The column {0} in table {1} cannot be found. It is referenced by key: {2}.**

**Cause:** When building a model, an column name is referenced by a key, but the column cannot be found

**Action:** Check the model

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15249: An {0} was caught while adding a key which is not an FK. Very strange.**

**Cause:** When building a model, an column name is referenced by a key, but the column cannot be found

**Action:** Check the model

---

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15250: The key {0} referenced by table {1} cannot be found.**

**Cause:** When building a model, a key name is referenced by a table, but the key cannot be found

**Action:** Check the model

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15251: A duplicate key was found: {0}**

**Cause:** When dropping a model, a duplicate key was found in the model

**Action:** Check the model

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15252: Key already exists: {0}**

**Cause:** When updating a model, a duplicate key was found in the model

**Action:** Check the model

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15253: Key not found: {0}**

**Cause:** When updating a model, the key was not found

**Action:** Check the model

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15254: Could not find a constructor with a key name for class {0}**

**Cause:** When creating a key class instance, the constructor could not be found

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15255: Could not instantiate an object of class {0}**

**Cause:** Could not instantiate the key class

**Action:** Internal Error: contact Oracle support

**Level:** 32

---

**Type:** ERROR

**Impact:** Programmatic

**ODI-15256: Could not create an object for class {0} for security reasons**

**Cause:** Could not instantiate the key class, due to a security failure

**Action:** Check security settings

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15257: Could create an object for class {0} because a {1} occurred saying {2}**

**Cause:** Could not instantiate the key class, due to an invocation target exception

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15258: Column {0} not found**

**Cause:** The column could not be found

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15259: The key class {0} is not an ID key class.**

**Cause:** The specified key class instance was not a SnpsRDBIdKey instance

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15260: Could not add column {0}: Unsupported datatype: {1}**

**Cause:** Cannot add the column to the model because the datatype is not supported by the technology

**Action:** Correct the model

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15261: Unsupported action: {0}**

**Cause:** The action class is not supported by the ODI RDB

**Action:** Internal Error: contact Oracle support

**Level:** 32

**Type:** ERROR

---

**Impact:** Programmatic

**ODI-15262: Cannot drop column {0}. It is used in a foreign key!**

**Cause:** An attempt was made to drop a column that participates in a foreign key

**Action:** Drop the key first, then the column

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15263: Cannot drop column {0}. It is used in a primary key!**

**Cause:** An attempt was made to drop a column that participates in a primary key

**Action:** Drop the key first, then the column

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15264: Cannot modify this column. It is used in a foreign key!**

**Cause:** An attempt was made to modify a column that participates in a foreign key

**Action:** Drop the key first, then modify the column

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15265: Cannot modify this column. It is used in a primary key!**

**Cause:** An attempt was made to modify a column that participates in a primary key

**Action:** Drop the key first, then modify the column

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15268: Table not found: {0}**

**Cause:** When attempting to drop a table during an update, the table name is not found

**Action:** Check the model

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15270: Key type {0} is not supported here.**

**Cause:** The key type is not supported

**Action:** Correct the model

**Level:** 32

**Type:** ERROR

---

**Impact:** Programmatic

**ODI-15272: An error occurred while executing a RDB command: {0}**

**Cause:** When executing a command action, an exception was thrown

**Action:** Check root cause

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15273: {0}; action is not accepted: {1}**

**Cause:** Attempt to execute a command action, but it is not accepted

**Action:** Check root cause

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15274: Multiple PKs are not allowed on a table**

**Cause:** When reverse engineering a primary key, multiple primary keys were found for the table

**Action:** Check the model

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15275: An exception occurred while retrieving a table primary key: {0}**

**Cause:** When reverse engineering a table, a primary key could not be retrieved

**Action:** Check the model

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15276: An exception occurred while retrieving the indexes of a table: {0}**

**Cause:** When reverse engineering a table, the indexes could not be retrieved

**Action:** Check the model

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15277: An exception occurred while retrieving a table foreign keys: {0}**

**Cause:** When reverse engineering a table, the foreign keys could not be retrieved

**Action:** Check the model

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

---

**ODI-15278: An exception occurred while retrieving the check constraints of a table: {0}**

**Cause:** When reverse engineering a table, the check constraints could not be retrieved

**Action:** Check the model

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15279: An exception occurred while retrieving the alternate keys of a table: {0}**

**Cause:** When reverse engineering a table, the alternate keys could not be retrieved

**Action:** Check the model

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15280: \*\*\* FATAL \*\*\* Table {0} is duplicate as root**

**Cause:** The table is duplicated as the root when determining the root tables of the model

**Action:** Check the model

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15281: \*\*\* FATAL \*\* Table {0} is unknown**

**Cause:** The root table is unknown

**Action:** Check the model

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15282: Table {0} is unknown though it was reversed**

**Cause:** The table cannot be found in the ODI model, although it was reversed

**Action:** Retry the reverse engineering

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15283: Duplicate declaration for table {0}**

**Cause:** The model XML contains a duplicate table declaration

**Action:** Fix the XML

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic



---

**ODI-15285: FK {0} references a table with no PK.**

**Cause:** The model XML contains a foreign key that references a table with no defined primary key

**Action:** Fix the XML

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15286: Unknown PK table for foreign key {0}: please check the name and order of the tables and FK.**

**Cause:** The model XML contains a foreign key that references an unknown primary key table

**Action:** Fix the XML

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15287: Unknown element: {0}**

**Cause:** The model XML contains an unknown element

**Action:** Fix the XML

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15288: An {0} error occurred with the following message: {1}**

**Cause:** An error occurred when writing the model to a file

**Action:** See root cause

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15290: Column {0} was not found in table {1}**

**Cause:** The column was not found when building the columns from column names

**Action:** Check the model

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15291: \*\*\* FATAL \*\*\* Could not rename table {0} to {1}**

**Cause:** Could not rename table

**Action:** Check permissions and security settings

**Level:** 32

**Type:** ERROR

---

**Impact:** Programmatic

**ODI-15292: \*\*\* FATAL \*\*\* Could not rename table {0} because it was not found in the model!**

**Cause:** Could not rename table, because the table to be renamed does not exist

**Action:** Check the model

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15293: Unknown FK table for foreign key {0}: please check the name and order of the tables and FK.**

**Cause:** The model XML contains a foreign key that references an unknown table

**Action:** Fix the XML

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15294: unknown element: {0}**

**Cause:** The model XML contains an unknown XML element

**Action:** Fix the XML

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15295: Unsupported datatype: {0}**

**Cause:** The datatype is unsupported when creating the column from attributes

**Action:** Check the model

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15300: A {0} occurred while creating the helper of class {1}. Error message: {2}**

**Cause:** INTERNAL ERROR: A helper cannot be created.

**Action:** Internal error: contact Oracle support.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-15301: Choose: {0}**

**Cause:** Choose one of the displayed options.

**Action:** Choose one of the displayed options.

**Level:** 32

**Type:** ERROR

---

**Impact:** Other

**ODI-15302: FK is null: {0}**

**Cause:** The FK is null, may indicate repository corruption.

**Action:** Internal error: contact Oracle support.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-15400: Error in generating data service**

**Cause:** Exception thrown when creating the data service used for DDL generation and reverse engineering.

**Action:** Check the root cause.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15401: Unknown key {0}**

**Cause:** Unknown key encountered when processing diff class instances during DDL generation.

**Action:** Check the model.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15402: Exception thrown in the DDL generation service: {0}**

**Cause:** An exception was thrown while generating DDL.

**Action:** Check the root cause.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15403: The method is not supposed to sort something else than the expected actors. Attempting to sort class instances: {0}, {1}**

**Cause:** While sorting action commands, the DDL generator service encountered an unknown class instance type.

**Action:** Internal Error: contact Oracle support.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15404: Scenario generation has not been implemented for this container.**

**Cause:** During DDL generation, an attempt was made to generate a scenario for an object that does not support it.

**Action:** Internal Error: contact Oracle support.

---

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15405: Scenario generation exception: {0}**

**Cause:** An exception was thrown during scenario generation.

**Action:** Check root cause.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15500: Column {0} is executed on the target**

**Cause:** Possible Cause

**Action:** Suggested Action

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15501: Cannot attach a data store to a target mapping because column {0} is not found.**

**Cause:** The specified target column was not found.

**Action:** Verify that the correct column has been specified.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15502: Target mapping not found for column {0}**

**Cause:** The specified column is not mapped.

**Action:** Map the specified column.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15503: Cannot set the attached datastore because the mapping is not executed on the SOURCE**

**Cause:** The mapping has been configured for execution on the target.

**Action:** Configure the mapping for execution on the source.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15504: Unknown indicator type: {0}**

**Cause:** An invalid indicator type has been specified.

**Action:** Specify one of the following indicator types from the IndicatorType enumeration: CHECK\_NOT\_NULL, INSERT, UPDATE, or UPDATE\_KEY.

---

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15505: Invalid UD number: {0}**

**Cause:** An invalid UD number has been specified.

**Action:** Specify a UD number 1 to 10.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15506: The specified target column was not found: {0}**

**Cause:** The specified target column was not found when attempting to remove a column from a temporary data store.

**Action:** Only remove columns which exist in the temporary target datastore.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15507: Column {0} may not be removed. It is used in other mappings, join clauses, or filter clauses**

**Cause:** The specified target column is used in other mappings, filters, or joins. This dependency prevents removal of the column.

**Action:** Only remove a column after mapping, filter, or join dependencies have been removed.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15508: Column {0} may not be removed because it is referenced in interface {1}.**

**Cause:** The specified target column is referenced in a filter or join clause in another interface. This dependency prevents removal of the column.

**Action:** Only remove a column after other references have been removed.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15509: The specified target column was not found: {0}**

**Cause:** The specified target column was not found.

**Action:** Verify the column name.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15510: A column was not found while updating the key**

---

**Cause:** The update key contains a column that does not exist.

**Action:** Check the columns of the update key.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15511: The join must be attached to the datastore to expand a lookup.**

**Cause:** The join is not attached to a datastore, so a valid lookup does not exist.

**Action:** Only use the lookup expansion, with a pCreateLookup parameter value of false, on valid lookups.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15512: Cannot transform a normal datastore into a normal lookup.**

**Cause:** The data store is already a non-lookup data store.

**Action:** Do not use this transformation on a non-lookup data store. If the datastore and join are non-lookup, use a pCreateLookup parameter value of true to create a lookup from a normal join and normal datastore.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15513: Cannot transform a normal, non-lookup join into a normal join.**

**Cause:** The join is already a normal join, not a lookup join, so expansion to a normal, non-lookup join is not possible.

**Action:** Do not use this transformation on a normal join. If the datastore and join are non-lookup, use a pCreateLookup parameter value of true to create a lookup from a normal join and normal datastore.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15514: Cannot transform a lookup datastore into a lookup.**

**Cause:** The data store is already designated as a lookup, so transforming to a lookup is not possible.

**Action:** Do not use this transformation on a lookup. If the datastore and join are designated for lookup, use a pCreateLookup parameter value of false to expand a lookup to a normal join and normal datastore.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15515: Cannot transform a lookup join into a lookup.**

**Cause:** The join is already designated as a lookup, so transforming to a lookup is not possible.

---

**Action:** Do not use this transformation on a lookup. If the datastore and join are designated for lookup, use a pCreateLookup parameter value of false to expand a lookup to a normal join and normal datastore.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15516: The join must be attached to the datastore to make a lookup.**

**Cause:** The join is not properly attached to data sources, so transforming to a lookup is not possible.

**Action:** Designate data sources for the join.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15517: Cannot add a column with the same name as an existing target column: {0}.**

**Cause:** The column being added already exists.

**Action:** Add a column with a unique name.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15518: A dataset is already assigned the order: {0}.**

**Cause:** Another dataset has already been assigned the order that is being set.

**Action:** Assign a unique order to the dataset.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15519: The target datastore cannot be changed. Interface {0} is used in interface(s) {1} as a source datastore.**

**Cause:** The interface is used as a source datastore of another interface, so the target datastore cannot be changed.

**Action:** Create a separate interface to avoid the source datastore dependency in the other interface.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15520: Temporary interface from another project is not allowed.**

**Cause:** The interface is used as a source datastore of another interface, so the target datastore cannot be changed.

**Action:** Create a separate interface to avoid the source datastore dependency in the other interface.

---

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15521: A source datastore with alias {0} already exists.**

**Cause:** The datastore alias has already been used.

**Action:** Specify a unique alias.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15522: Cannot transform a join into a CrossJoin or natural join if it does not have both attached datastores set.**

**Cause:** The join does not have datastores attached yet.

**Action:** Attach both join datastores before transforming to a cross join.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15523: LKM {0} not accepted for source set {1}**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15524: LKM {0} not accepted for staging area to target**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15525: CKM {0} not accepted for target technology**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15526: IKM {0} not accepted for staging and target technology**

**Cause:**

**Action:**

**Level:** 32



---

**Type:** ERROR  
**Impact:** Programmatic  
**ODI-15527: IKM {0} not accepted for target technology**  
**Cause:**  
**Action:**  
**Level:** 32  
**Type:** ERROR  
**Impact:** Programmatic  
**ODI-15528: Mapping expression cannot be set because the target column {0} was not found.**  
**Cause:** The column was not found when setting the expression for a mapping.  
**Action:** Specify a valid column for the expression.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Programmatic  
**ODI-15529: Action was not reversible.**  
**Cause:** The actions causing an impact are not reversible.  
**Action:** Avoid the sequence of actions causing the impact.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Programmatic  
**ODI-15530: The interface does not have a source set.**  
**Cause:** The interface does not have a source set.  
**Action:** Add a source set to the interface.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Programmatic  
**ODI-15531: The execution location parameter for the computeExpression method is invalid.**  
**Cause:** The execution location parameter for the computeExpression method is invalid.  
**Action:** Specify an execution location parameter of ExecutionLocation.SOURCE, ExecutionLocation.WORK, or ExecutionLocation.TARGET.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Programmatic  
**ODI-15532: The pExecutableTextHolder parameter for the getLogicalSchemaForTextHolder method does not have a valid execution location.**

---

**Cause:** The pExecutableTextHolder parameter for the getLogicalSchemaForTextHolder method does not have a valid execution location.

**Action:** Specify an execution location parameter of ExecutionLocation.SOURCE, ExecutionLocation.WORK, or ExecutionLocation.TARGET.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15533: The physical schema could not be mapped from logical schema {0} and context {1}.**

**Cause:** The getPhysicalSchema method failed to map and logical schema and context to a physical schema.

**Action:** Ensure that logical to physical schema mappings are created or check the logical schema and context parameters.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15534: Sub interface must not be null.**

**Cause:** The pSubInterface parameter passed to the checkSubInterfaceValid method is null.

**Action:** A non-null sub interface parameter is required for the checkSubInterfaceValid method.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15535: The technology {0} of the source temporary interface {1} used as a derived table does not support derived tables.**

**Cause:** The pSubInterface parameter passed to the checkSubInterfaceValid method is null.

**Action:** A non-null sub interface parameter is required for the checkSubInterfaceValid method.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15536: Source temporary interface {0} cannot be used as a derived table. Its source datastore {1} defined in logical schema {2} has no associated physical schema in the optimization context {3}.**

**Cause:** The temporary interface cannot be used because a physical schema has not been mapped to the logical schema for the source.

**Action:** Create a mapping between the logical schema, context, and physical schema for the source data store.

**Level:** 32

**Type:** ERROR

---

**Impact:** Programmatic

**ODI-15537: Source temporary interface {0} cannot be used as a derived table. The logical schema of the target datastore {1} has no associated physical schema in context {2}.**

**Cause:** The temporary interface cannot be used because a physical schema has not been mapped to the logical schema for the target.

**Action:** Create a mapping between the logical schema, context, and physical schema for the target data store.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15538: Source temporary interface {0} cannot be used as a derived table. The logical schema of the staging area {1} has no associated physical schema in the optimization context {2}.**

**Cause:** The temporary interface cannot be used because a physical schema has not been mapped to the logical schema for the staging area.

**Action:** Create a mapping between the logical schema, context, and physical schema.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15539: Source temporary interface {0} cannot be used as a derived table. Source datastore {1} is not on the same data server as the target.**

**Cause:** The temporary interface cannot be used because the source data store is not on the same data server as the target.

**Action:** Ensure that the source and target datastores are on the same data server.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15540: Source temporary interface {0} cannot be used as a derived table. Staging area and target datastores are not in the same data server. You may have forced the target context to a different context than the optimization context.**

**Cause:** The temporary interface cannot be used because the staging data store is not on the same data server as the target.

**Action:** Ensure that the staging and target datastores are on the same data server.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15541: Source temporary interface {0} uses a journalized datastore and cannot be used as a derived table.**

**Cause:** The temporary interface cannot be used because it uses a journalized datastore.

**Action:** Use only non journalized data stores in temporary interfaces.

---

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15542: Source temporary interface {0} cannot be used as a derived table. All source datastores of this interface should be in the same data server as the target and should not be journalized.**

**Cause:** The temporary interface cannot be used because it uses a journalized datastore.

**Action:** Use only non journalized data stores in temporary interfaces.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15543: Another interface with the same name already exists in this folder. Please choose a unique interface name.**

**Cause:** Another interface with the same name already exists in this folder.

**Action:** Specify a unique interface name.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15544: The interface must have a name.**

**Cause:** The interface does not have a name.

**Action:** Specify a unique interface name.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15545: Temporary target datastore has no name.**

**Cause:** The temporary target datastore has no name

**Action:** Specify a unique datastore name.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15546: The interface must have a logical schema.**

**Cause:** The interface does not have a logical schema.

**Action:** Specify a logical schema for the interface.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15547: Could not fix a missing reference correctly.**

**Cause:** The interface is missing one or more references.

---

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15548: The source datastore has already been set.**

**Cause:** The source datastore has already been set.

**Action:** Only invoke setSourceDataStore once.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15549: Cannot set the source filter because the source datastore is not set.**

**Cause:** The source datastore has not been set prior to setting the filter.

**Action:** Set the source datastore prior to setting the filter.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15550: The target datastore has already been set.**

**Cause:** The source datastore has already been set.

**Action:** Only invoke setSourceDataStore once.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15551: Mappings on the target are not allowed in this helper.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15552: A source filter requires a source datastore.**

**Cause:** The interface cannot be saved because it contains a filter without a source datastore.

**Action:** Create a source datastore before creating a source filter.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15553: The target datastore must be set.**

**Cause:** The target datastore for the interface has not been set.

**Action:** Set the target datastore before saving the interface.

---

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15554: An LKM must be set on the source set.**

**Cause:** A loading knowledge module has not been assigned to the source set.

**Action:** Set the LKM for the source set before saving the interface.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15555: Target IKM must be set on the target table.**

**Cause:** An integration knowledge module has not been assigned to the target table.

**Action:** Set the IKM for the target before saving the interface.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15556: Unknown generic clause type: {0}**

**Cause:** An unknown generic clause class was passed to the createSnpPopClauseFromGenericClause method.

**Action:** Pass only generic clause classes for join or filter.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15557: Unknown execution location type: {0}**

**Cause:** An unknown execution location enumeration was passed to the getStringExeDbFromExecutionLocation method.

**Action:** Pass only location enumerations of ExecutionLocation.SOURCE, ExecutionLocation.WORK, ExecutionLocation.TARGET.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15558: There is a conflict between physical schemas**

**Cause:** There is a conflict between the various physical schemas used to obtain the data, such as multiple data stores in the same source set connected using different physical schemas.

**Action:** Ensure that physical schemas of a source set have consistent connection information.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

---

**ODI-15559: Unsupported component: {0}**

**Cause:** An unsupported component was passed as a parameter to createDataAccessinfo.

**Action:** For the pInterfaceSubComponents parameter, supported components are SourceDataStore, ISourceColumn, TargetMapping, and GenericClause.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15560: Fatal interface condition: {0}**

**Cause:** A fatal issue was discovered while saving or verifying an interface.

**Action:** Correct the interface issue before saving it.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15561: Could not find column {0} which choosing a mapping.**

**Cause:** The MappingChooserFirst.chooseMapping method was called with an column name that does not exist.

**Action:** Check the column name passed to chooseMapping.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15562: Source sets cannot be computed because one execution area doesn't have a physical schema. Check the errors on the interface.**

**Cause:** Source sets cannot be computed because one execution area doesn't have a physical schema.

**Action:** Check the errors on the interface.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15563: Source sets cannot be computed because the staging area is not properly defined. Check your target datastore and the staging area's physical schema in the Definition tab.**

**Cause:** Source sets cannot be computed because the staging area is not properly defined.

**Action:** Check your target datastore and the staging area's physical schema in the Definition tab.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15564: There should be one source set on the interface.**

**Cause:** The interface has more than one source set.

---

**Action:** Ensure that only one source set is defined.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15565: Column {0} not found while setting the update key.**

**Cause:** A column specified for the update key does not exist.

**Action:** Recheck the column names used to define the update key.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15566: No target column was found while setting the target data store.**

**Cause:** No target column was found while setting the target data store.

**Action:** Define columns before setting the target datastore.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15567: Target column {0} was not found.**

**Cause:** No specified target column was not found in the target data store.

**Action:** Check the column name parameter in the  
RealBasicInterfaceCreationHelper.getTargetColumn method call.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15568: Column {0} not found on datastore {1}.**

**Cause:** A referenced column was not found in a source data store.

**Action:** Check the source datastore columns and references for a mismatch.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15569: Cannot create a data source.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15570: Cannot add a datastore of type {0} as source.**

**Cause:** An invalid datastore type has been specified.



---

**Action:** Specify a datastore of type TargetDataStore, SourceDataStore, or OdiDataStore.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15571: Unexpected join type {0}**

**Cause:** An invalid join type has been specified when setting join properties.

**Action:** Specify a join type of INNER, CROSS, or NATURAL.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15572: Unexpected join state.**

**Cause:** An invalid join state has been reached. The expected join type is CROSS or NATURAL.

**Action:** .

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15573: Failed to create an interface helper instance.**

**Cause:** A general exception was encountered while constructing an interface helper.

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15574: General exception encountered in the interface helper while preparing to persist.**

**Cause:** General exception encountered in the interface helper while preparing to persist.

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15575: Two journalized datastores have been found. There should be only one.**

**Cause:** Two journalized datastores have been found. There should be only one.

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

---

**ODI-15576: Two journalized filters have been found. There should be only one.**

**Cause:** Two journalized filters have been found. There should be only one.

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15577: Unmanaged type: {0}**

**Cause:** An invalid element type was passed to the prepareSQLStatement method.

**Action:** Pass only valid element types such as GenericClause, SourceDataStore, TargetDataStore, ISourceColumn, TargetMapping, SourceSet, DataSet, or TargetColumn.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15578: No interface was found in the elements.**

**Cause:** No interface could be traced to the elements passed to the prepareSQLStatement method.

**Action:** Create an interface.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15579: No dataset was found in the elements.**

**Cause:** No data set could be traced to the elements passed to the prepareSQLStatement method.

**Action:** Ensure that a dataset has been created first.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15580: The target is a temporary table.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15581: Cannot build the query because the ordered joins are not correct.**

**Cause:** The SQL clause cannot be generated because the ordered joins are not correct.

**Action:** Ensure that all joins are correct.

**Level:** 32

---

**Type:** ERROR

**Impact:** Programmatic

**ODI-15582: This operation is not supported on joined file datastores.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15583: This operation is not supported on multiple file datastores.**

**Cause:** More than one source datastore was found.

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15584: Elements are from different interfaces.**

**Cause:** The components passed to prepareSQLStatement are from different interfaces.

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15585: Elements are from different datasets.**

**Cause:** The components passed to prepareSQLStatement are from different data sets.

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15586: Unsupported component: {0}**

**Cause:** An invalid component type was passed to connectionForData.

**Action:** Only pass components of type SourceDataStore, ISourceColumn, TargetMapping, TargetColumn, GenericClause, or TargetDataStore.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15587: Journalization filter not found for the journalized table.**

**Cause:** The journalized table does not have a filter.

**Action:** Define a journalizing filter for the table.

**Level:** 32

---

**Type:** ERROR

**Impact:** Programmatic

**ODI-15588: The SQL join clause is not valid for a cross join.**

**Cause:** A join clause has been specified for a cross join.

**Action:** Remove the join condition or change the join type.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15589: Cannot change the ON\_TARGET indicator on a temporary interface.**

**Cause:** An attempt was made to set the ON\_TARGET indicator for a temporary datastore.

**Action:** Do not change the ON\_TARGET indicator for a temporary datastore.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15590: Unknown indicator type: {0}**

**Cause:** An unknown value was passed to the constructor for InterfaceActionOnStagingAreaSetIndicator.

**Action:** Use valid values of DISTINCT\_ROW, ON\_TARGET, or ON\_USER\_DATABASE\_SCHEMA for the pIndicatorType parameter.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15591: Staging Area is on the target and cannot be switched to another logical schema.**

**Cause:** The staging area is on the target and uses the target schema. It cannot be switched.

**Action:** Do not attempt to switch the schema, or use a separate staging area.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15592: GenericClause is of unknown type: {0}**

**Cause:** InterfaceActionRemoveGenericClause was constructed with an invalid generic clause.

**Action:** Use a generic clause type of JOIN or FILTER.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15593: Could not set LKM for object of type {0}**

**Cause:** An LKM is being set for a TargetDataStore or some other invalid type.

---

**Action:** Only set an LKM for a SourceSet or StagingArea.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15594: Could not set the CKM for a holder of type {0}**

**Cause:** A CKM is being set for a SourceSet, StagingArea, or some other invalid type.

**Action:** Only set a CKM for a TargetDataStore.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15595: Could not set the IKM for a holder of type {0}**

**Cause:** An IKM is being set for a SourceSet, StagingArea, or some other invalid type.

**Action:** Only set an IKM for a TargetDataStore.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15596: Invalid KM type: {0}**

**Cause:** An invalid object type is being used to set a KM.

**Action:** Only set a KM of type LKM, CKM, or IKM.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15597: Could not set the LKM option for a holder of type {0}**

**Cause:** An LKM is being set for a TargetDataStore or some other invalid type.

**Action:** Only set an LKM option for a SourceSet or StagingArea.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15598: Could not set the CKM option for a holder of type {0}**

**Cause:** A CKM option is being set for a SourceSet, StagingArea, or some other invalid KM holder type.

**Action:** Only set a CKM option for a KM holder of type TargetDataStore.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15599: Could not set the IKM option for a holder of type {0}**

---

**Cause:** An IKM option is being set for a SourceSet, StagingArea, or some other invalid KM holder type.

**Action:** Only set an IKM option for a KM holder of type TargetDataStore.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15600: Dataset 1 was not found in the list of the interface datasets used with the interface.**

**Cause:** The first dataset given as a parameter in the construction of the InterfaceActionSwitchDataSetOrders class is not used in the interface.

**Action:** Recheck the datasets being switched for this interface. Both datasets must be used in the interface.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15601: Dataset 2 was not found in the list of the datasets used with the interface.**

**Cause:** The second dataset given as a parameter in the construction of the InterfaceActionSwitchDataSetOrders class is not used in the interface.

**Action:** Recheck the datasets being switched for this interface. Both datasets must be used in the interface.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15602: Dataset 2 was not found in the list of the datasets used with the interface.**

**Cause:** An unimplemented method has been called. This is an ODI internal error.

**Action:** Do not call this method.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15603: Cannot create an alias for a datastore of type {0}**

**Cause:** The method computeAliasForDataStore was called with an invalid datastore type.

**Action:** Only call computeAliasForDataStore for datastores of type TargetDataStore or OdiDataStore.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15604: A non ordered clause was passed to the buildTreeSet method.**

---

**Cause:** A non ordered clause is passed to the construction of ordered joins trees method.

**Action:** Use ordered join clauses with this method.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15605: Multiple ordered joins in this dataset use the same order number.**

**Cause:** One or more join clauses uses the same order number in the call to buildTreeSet.

**Action:** Ensure that all clauses of an ordered join have unique order numbers.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15606: Join references the same table twice (directly or indirectly).**

**Cause:** A join clause contains two references to the same table.

**Action:** Ensure that the join clause only references one table.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15607: Join references the same table twice through other joins.**

**Cause:** A join clause contains two references to the same table.

**Action:** Ensure that the join clause only references one table.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15608: Subcomponent type of {0} is not supported.**

**Cause:** An unsupported type was passed to getIssuesComputer.

**Action:** Only pass types of OdiInterface, DataSet, SourceDataStore, Filter, Join, StagingArea, TargetDataStore, SourceSet, TargetMapping, or TargetColumn.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15609: Invalid KM holder type: {0}**

**Cause:** An anvalid KM holder type was passed to InterfaceKMHolderFactory.getKMHolderFor

**Action:** Only pass KM holder types of SOURCE\_SET\_LKM, STAGING\_AREA\_LKM, TARGET\_CKM, or TARGET\_IKM.

**Level:** 32

**Type:** ERROR

---

**Impact:** Programmatic

**ODI-15610: Component must be a source datastore or a source colum.**

**Cause:** ReferenceManagerAbstract.getReferencesTo was called with an invalid subcomponent.

**Action:** Only pass subcomponent types of SourceDataStore or ISourceColumn.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15611: Column not found from an xref.**

**Cause:** A column referenced in an expression was not found in a datastore. It may have been deleted.

**Action:** Ensure that all columns referenced in the expression exist.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15612: Failed to attach an element of type {0} to a source set.**

**Cause:** An invalid type of component was found when attaching elements to a source set.

**Action:** Elements being attached to a source set must be of type SourceDataStore, Join, Filter, or TargetMapping.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15613: Interface must have only one dataset.**

**Cause:** This sourceset computer can only handle a single dataset, and more than one was found.

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15614: Interface must have only one source table.**

**Cause:** This sourceset computer can only handle a single table, and more than one dataset was found.

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15615: Interface must not have joins.**

**Cause:** This sourceset computer can only handle a single table, and the interface contains a join.



---

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15616: Source datastore must be a real table**

**Cause:** This sourceset computer can only handle a single, real table.

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15617: Invalid type for a TextHolder: {0}**

**Cause:** The method getExecutableTextHolderFor was called with an invalid TextHolder component type.

**Action:** Valid types are TargetMapping, TargetColumn, Filter, and Join.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15618: Cannot set a source set on a target column.**

**Cause:** SetSourceSet was called for a target column, which is not a valid usage. This method is specified for the interface, but is not valid for this class.

**Action:** SetSourceSet should never be invoked for this class.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15619: Inconsistent filter with a clauseType of {0}**

**Cause:** The Filter.getFilterType method was called, but the clause type was not a filter type.

**Action:** Ensure that the filter has a type of SnpPopClause.CLAUSE\_TYPE\_FILTER or SnpPopClause.CLAUSE\_TYPE\_JRN\_FILTER.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15620: Execution location is null. Target technology cannot be determined**

**Cause:** The execution filter for the location was not set.

**Action:** The execution location should be set in the Filter constructor or by invoking setExecutionLocation.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

---

**ODI-15621: Attached dataStore is null. Target technology cannot be determined**

**Cause:** The attached datastore for the execution location was not set.

**Action:** The datastore should be set in the Filter constructor or by invoking `setAttachedDataStore`.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15622: Staging area does not have a logical schema. Target technology cannot be determined**

**Cause:** The attached datastore for the execution location was not set.

**Action:** The datastore should be set in the Filter constructor or by invoking `setAttachedDataStore`.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15623: Invalid technology for the given index type**

**Cause:** The technology of the clause and index type do not match.

**Action:** Ensure that the index type technology matches the clause technology.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15624: Inconsistent join with clauseType = {0} and joinType = {1}**

**Cause:** The join clause type is invalid.

**Action:** This exception is thrown from a deprecated method. Use `isCross` or `isOrdered` methods instead.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15625: Cannot set OdiDataType on a journalized source column**

**Cause:** The `setDataType` method has been invoked for a journalized source column, but the datatype cannot be set for journalized columns.

**Action:** Do not invoke this method for a journalized column.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15626: Cannot set the length on a journalized source column**

**Cause:** The `setLength` method has been invoked for a journalized source column, but the length cannot be set for journalized columns.

**Action:** Do not invoke this method for a journalized column.

**Level:** 32

---

**Type:** ERROR

**Impact:** Programmatic

**ODI-15627: Cannot set the scale on a journalized source column**

**Cause:** The setScale method has been invoked for a journalized source column, but the scale cannot be set for journalized columns.

**Action:** Do not invoke this method for a journalized column.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15628: Cannot set the data type on a source column**

**Cause:** The setDataType method has been invoked for a source column, but the datatype cannot be set for source columns.

**Action:** Do not invoke this method for a source column.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15629: Cannot set the length on a source column**

**Cause:** The setLength method has been invoked for a source column, but the length cannot be set for source columns.

**Action:** Do not invoke this method for a source column.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15630: Cannot set the scale on a source column**

**Cause:** The setScale method has been invoked for a source column, but the scale cannot be set for source columns.

**Action:** Do not invoke this method for a source column.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15631: Connection information is not available.**

**Cause:** The physical schema has not been set.

**Action:** Define physical and logical schemas.

**Level:** 32

**Type:** ERROR

**Impact:** Programmatic

**ODI-15632: Column {0} may not be removed because it is mapped in interface {1}.**

**Cause:** The specified target column is mapped in another interface. This dependency prevents removal of the column.

**Action:** Only remove a column after mapping dependencies have been removed.

- 
- Level:** 32  
**Type:** ERROR  
**Impact:** Programmatic
- ODI-17500: Invalid old password.**  
**Cause:** Old password did not match current password.  
**Action:** Provide the correct password.
- Level:** 32  
**Type:** ERROR  
**Impact:** Security
- ODI-17501: Temporary table has no column.**  
**Cause:** No column have been defined for the temporary table.  
**Action:** Define a column mapping to the temporary table.
- Level:** 32  
**Type:** ERROR  
**Impact:** Other
- ODI-17502: No next value returned.**  
**Cause:** No sequence next value was found for given context code.  
**Action:** Verify sequence definition or context code.
- Level:** 32  
**Type:** ERROR  
**Impact:** Other
- ODI-17504: An ordered join references the same table twice (directly or indirectly).**  
**Cause:** A same table was referenced twice by a join.  
**Action:** Check interface definition.
- Level:** 32  
**Type:** ERROR  
**Impact:** Other
- ODI-17505: An ordered join references the same table twice through another join.**  
**Cause:** A join was referencing the same table twice through another join.  
**Action:** Check interface definition.
- Level:** 32  
**Type:** ERROR  
**Impact:** Other
- ODI-17506: Variable has no value**  
**Cause:** Variable had no value.  
**Action:** Provide value for variable.
- Level:** 32  
**Type:** ERROR

---

**Impact:** Other

**ODI-17507: Key does not exist**  
**Cause:** Key was unknown.  
**Action:** Provide a known key.

**Level:** 32  
**Type:** ERROR  
**Impact:** Other

**ODI-17508: No conversion for data type "{0}" from source technology "{1}" to destination technology "{2}"**  
**Cause:** No data type conversion between technology was found.  
**Action:** Define corresponding data type conversion.

**Level:** 32  
**Type:** ERROR  
**Impact:** Other

**ODI-17509: Query to access value for specific sequence {0} has failed. Query="{1}"**  
**Cause:** Query for sequence has failed.  
**Action:** Check sequence definition.

**Level:** 32  
**Type:** ERROR  
**Impact:** Other

**ODI-17510: Driver does not exist.**  
**Cause:** Driver was not found.  
**Action:** Check repository.

**Level:** 32  
**Type:** ERROR  
**Impact:** Other

**ODI-17511: No value to be set to variable {0}.**  
**Cause:** No value was returned to be set to the variable.  
**Action:** Check variable value.

**Level:** 32  
**Type:** ERROR  
**Impact:** Other

**ODI-17512: Sequence is already locked**  
**Cause:** The sequence was already locked.  
**Action:** Unlock the sequence.

**Level:** 32  
**Type:** ERROR  
**Impact:** Other

---

**ODI-17513: Variable does not exist**

**Cause:** Variable was not found.

**Action:** Check variable.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17514: Unrecognized Oracle Data Integrator built-in function: {0}**

**Cause:** Oracle Data Integrator built-in function was not recognized.

**Action:** Check function syntaxe.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17515: Invalid loading command (INSERT,UPDATE...).**

**Cause:** Loading command was invalid.

**Action:** Check loading command.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17517: Error during task interpretation. Task: {0} {1} Text: {2}.**

**Cause:** A task interpretation error has occurred.

**Action:** Check tasks and try again.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17518: Error while interpreting the user name.**

**Cause:** User name interpretation has failed.

**Action:** Check user name.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17519: Error while interpreting the URL**

**Cause:** URL interpretation has failed

**Action:** Check URL.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17520: Error while interpreting the password**

**Cause:** Password interpretation has failed.

---

**Action:** Check password.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17521: Error while interpreting the driver**

**Cause:** Driver interpretation has failed.

**Action:** Check driver.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17522: Empty column name are not allowed**

**Cause:** A empty column name was found.

**Action:** Fill column name.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17523: There is no connection for this logical schema / context pair: {0} / {1}.**

**Cause:** No connection was found for this logical schema / context pair.

**Action:** Check schema and context assignment.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17524: Cannot set an empty alias for a source table.**

**Cause:** Source table's alias was empty.

**Action:** Fill alias of source table.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17525: Cannot set an empty source set name.**

**Cause:** Source set name was empty.

**Action:** Fill alias of a source table.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17526: Cannot set Longc value in a PopCol having a column**

**Cause:** Cannot set Longc value in a PopCol having a column.

**Action:** Check interface's columns.

---

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17527: Cannot set SourceDt value in a PopCol having a column**

**Cause:** Cannot set SourceDt value in a PopCol having a column.

**Action:** Check interface`s columns.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17528: Cannot set Scalec value in a PopCol having a column**

**Cause:** Cannot set Scalec value in a PopCol having a column.

**Action:** Check interface`s columns.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17529: Reference check failure**

**Cause:** Reference check has failed.

**Action:** Check control conditions.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17530: Incomplete join may result in partial cross join**

**Cause:** An incomplete join was found.

**Action:** Check joins.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17531: KM already encrypted.**

**Cause:** KM has been already encrypted.

**Action:** Skip encryption.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17532: KM not encrypted.**

**Cause:** KM was not encrypted.

**Action:** Check KM.

**Level:** 32

**Type:** ERROR



---

**Impact:** Other

**ODI-17533: Clause set to cross join on a technology that does not support cross joins.**

**Cause:** Technology did not support cross joins.

**Action:** Correct joins.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17534: Clause set to full join on a technology that does not support full joins.**

**Cause:** Technology did not support full joins.

**Action:** Correct joins.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17535: Clause set to outer join on a technology that does not support left outer joins or right outer joins.**

**Cause:** Technology did not support left outer joins.

**Action:** Correct joins.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17536: Incomplete clause (Missing order number).**

**Cause:** Order number was missing.

**Action:** Correct clause.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17537: Incomplete clause (table1 and/or table2 must be set).**

**Cause:** Table1 and/or table2 were undefined.

**Action:** Set clause's table1 and/or table2 tables.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17538: Filter is not properly set (The table must be defined)**

**Cause:** The table must have been set.

**Action:** Set filter's table.

**Level:** 32

**Type:** ERROR

---

**Impact:** Other

**ODI-17539: Clause is ordered on a technology that does not support it**

**Cause:** Technology did not support ordering.

**Action:** Remove ordering.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17540: Connection is not set for this source set {0}.**

**Cause:** Source set's connection was not set.

**Action:** Set connection.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17542: Sequence must be locked before using this function**

**Cause:** Sequence was not locked.

**Action:** Lock sequence and try again.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17543: Technology does not support joins**

**Cause:** Technology did not support joins.

**Action:** Check technology and/or joins.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17544: This Technology does not support the WHERE clause**

**Cause:** Technology did not support the WHERE clause

**Action:** Check technology and/or clause.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17545: Technology not set for this source set {0}**

**Cause:** Source set's technology was undefined.

**Action:** Set technology.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17546: Specified variable not found in the Repository**

---

**Cause:** Variable was not found in the Repository.

**Action:** Define variable and try again.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17547: Data type "{0}" for the technology "{1}" does not exist.**

**Cause:** Data type for the technology did not exist.

**Action:** Check data type and/or technology.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17548: The file reverse-engineering is only possible for delimited files.**

**Cause:** The file reverse-engineering was performed against a not delimited file.

**Action:** Use delimited files.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17549: Source data type "{0}" for the technology "{1}" does not exist.**

**Cause:** Source data type was not found.

**Action:** Check data type and/or technology.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17550: Missing default Physical Schema for Data Server "{0}"**

**Cause:** Default Physical Schema was undefined.

**Action:** Specify default Physical Schema.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17551: Duplicate clause order numbers**

**Cause:** Duplicated order numbers were found.

**Action:** Check clause definition.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17552: Duplicate join order numbers**

**Cause:** Duplicated join order numbers were found.

**Action:** Check join.

---

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17553: Exceeded the maximum number of errors allowed.**

**Cause:** The maximum number of errors allowed were exceeded.

**Action:** Check maximum error numbers.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17554: Agent "{0}" does not exist.**

**Cause:** Agent was not found.

**Action:** Check agent definition.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17555: You cannot unlock this object. Only the lock owners and Supervisors can unlock objects.**

**Cause:** An attempt was made to unlock objects that were locked by another user.

**Action:** Login as Supervisor or as the lock owners and try again.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17556: Error during decryption of text.**

**Cause:** Text decryption has failed.

**Action:** Try again.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17557: No condition defined for this rule.**

**Cause:** No condition have been defined for this rule.

**Action:** Define conditions.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17558: The field for this rule is not specified.**

**Cause:** The field was unspecified.

**Action:** Specify field for this rule.

**Level:** 32

---

**Type:** ERROR

**Impact:** Other

**ODI-17559: The operator for this rule is not specified.**

**Cause:** The operator was unspecified.

**Action:** Specify operator for this rule.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17560: The value to test is not defined.**

**Cause:** The value to test was not defined.

**Action:** Specify value.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17561: This operator is not supported.**

**Cause:** This operator was not supported.

**Action:** Correct operator.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17562: This operator cannot be used with this field.**

**Cause:** The operator could not be used with the given field.

**Action:** Correct operator.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17563: There is no work repository matching the name "{0}".**

**Cause:** Work repository was not found.

**Action:** Check work repository with the given name exists.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17564: More than one work repository found with the name "{0}" for this master repository.**

**Cause:** More than one work repository with the specified name was found for this master repository.

**Action:** Contact Oracle Support Services.

**Level:** 32

---

**Type:** ERROR  
**Impact:** Other  
**ODI-17565: Scenario has been already encrypted. No encryption was performed.**  
**Cause:** Scenario has been already encrypted.  
**Action:** Decrypt and try again.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other  
**ODI-17566: Scenario is not encrypted. No decryption was performed.**  
**Cause:** Scenario was not encrypted.  
**Action:** Check Scenario.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other  
**ODI-17567: A Scenario generated from a Variable cannot be encrypted or decrypted.**  
**Cause:** An attempt was made to encrypt or decrypt a Scenario generated from a Variable.  
**Action:** Change Scenario" source component.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other  
**ODI-17568: Could not connect to the database referenced by the context and the logical schema**  
**Cause:** Connection to the database failed.  
**Action:** Check context and logical schema.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Network  
**ODI-17569: Unable to update sequence"s next value.**  
**Cause:** Updating sequence was not possible.  
**Action:** Check sequence definition.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other  
**ODI-17570: Your text is too long. Please shorten it or choose the "LONG TEXT" datatype.**  
**Cause:** Text was too long.  
**Action:** Shorten the text or choose the LONG TEXT data type.  
**Level:** 32

---

**Type:** ERROR

**Impact:** Other

**ODI-17571: Password does not respect the following rule: "{0}".**

**Cause:** The password did not respect the rule.

**Action:** Choose another password.

**Level:** 32

**Type:** ERROR

**Impact:** Security

**ODI-17572: This SnpFfValuee does not exist.**

**Cause:** Value was not found.

**Action:** Check FlexField value.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17573: This SnpFfValuem does not exist.**

**Cause:** Value was not found.

**Action:** Check FlexField value.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17574: This SnpFfValuew does not exist.**

**Cause:** Value was not found.

**Action:** Check FlexField value.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17575: SnpLicense does not exist.**

**Cause:** SnpLicense was not found.

**Action:** Check License.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17576: Unknown actual constraint type for an interface constraint.**

**Cause:** Interface constraint type was unknown.

**Action:** Check constraint type.

**Level:** 32

**Type:** ERROR

**Impact:** Other

---

**ODI-17577: Unknown variable data type.**

**Cause:** Variable data type was unknown.

**Action:** Check variable data type.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17578: Name "{0}" is already used.**

**Cause:** Name was already used.

**Action:** Use another name or change mode of import.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17579: Type of clause is not set.**

**Cause:** Type of clause was not set.

**Action:** Set type of clause.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17580: Type of join is not set.**

**Cause:** Type of join was not set.

**Action:** Set type of join.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17581: A non ordered clause is passed to the construction of ordered joins trees method.**

**Cause:** A non ordered clause was passed to the construction of ordered joins trees method.

**Action:** Check clauses.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17582: Missing order number for an ordered clause.**

**Cause:** Clause order was not set.

**Action:** Set the clause order.

**Level:** 32

**Type:** ERROR

**Impact:** Other



---

**ODI-17583: More than one unique constraint associated to an interface constraint.**

**Cause:** More than one unique constraint associated to an interface constraint was found.

**Action:** Check constraints.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17584: URL does not exist.**

**Cause:** URL was not found.

**Action:** Check URL.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17585: Key cannot be checked.**

**Cause:** Key could not be checked.

**Action:** Check key definition.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17586: Field separator is mandatory for a delimited file.**

**Cause:** Field separator was missing.

**Action:** Check separator and/or file type.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17587: Object name "{0}" is too long for the technology "{1}" (Logical schema : "{2}" ; Context Code : "{3}")**

**Cause:** Object name was too long.

**Action:** Correct object name.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17588: Unable to load work repository info.**

**Cause:** Work repository was not found.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

---

**ODI-17589: Logical schema has not been specified for sequence "{0}"**

**Cause:** Logical schema was not specified.

**Action:** Specify logical schema.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17590: Code {0} for model "{1}" is already used by another model.**

**Cause:** An already used code was assigned.

**Action:** Change code for model.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17591: Name "{0}" is already used.**

**Cause:** A name already used was assigned.

**Action:** Change name.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17592: Object is not in execution work repository.**

**Cause:** Object was not in execution work repository.

**Action:** Check object and/or repository.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17593: Maximum number or source/target technologies exceeded. Current limit is {0}.**

**Cause:** Maximum number or source/target technologies was exceeded.

**Action:** Check limit and number of technologies.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17594: Cannot encrypt already encrypted action.**

**Cause:** This action has been already encrypted.

**Action:** Skip encryption.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17595: This action is not encrypted.**

---

**Cause:** This action was not encrypted.

**Action:** Check parameters and try again.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17596: Query to retrieve value for native sequence "{0}" has failed Query="{1}"**

**Cause:** Query has failed.

**Action:** Check query.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17597: Cannot mix ordered and non-ordered join syntax within a dataset for technology.**

**Cause:** Mixed join not allowed within a dataset.

**Action:** Change all joins in dataset to same join syntax (either ordered or non-ordered).

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17598: Non-ordered natural join is not supported.**

**Cause:** Non-ordered natural join is not supported.

**Action:** Change natural join to use ordered syntax.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17599: Ordered inner join is not supported.**

**Cause:** Ordered inner join is disabled for technology.

**Action:** Change join type.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17600: Ordered left outer join is not supported.**

**Cause:** Ordered left outer join is disabled for technology.

**Action:** Change join type.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-17601: Ordered right outer join is not supported.**

---

**Cause:** Ordered right outer join is disabled for technology.

**Action:** Change join type.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20001: ODI-20001: Cannot check the key because the Datastore does not exist in the database.**

**Cause:** The Datastore referenced by this key did not exist in the database.

**Action:** Ensure the Datastore refers to an existing database table.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20002: ODI-20002: Invalid key**

**Cause:** An invalid encryption key file was selected.

**Action:** Select a valid encryption key file.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20003: ODI-20003: Cannot edit the condition**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20004: ODI-20004: Cannot edit the reference**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20005: ODI-20005: Cannot edit the variable**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20006: ODI-20006: Cannot display table's data. Data is probably already displayed.**

---

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20007: ODI-20007: Cannot display table's data.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20008: ODI-20008: You cannot Display this Column Data. Data is probably already displayed**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20009: ODI-20009: Cannot display data. The datastore resource name is {0} characters long which is longer than allowed by the technology ({1}). Please review the technology settings in Topology.**

**Cause:** The datastore resource name exceeded the limit allowed by its technology.

**Action:** Ensure the maximum table name length setting in the corresponding technology is correct. Consider changing the datastore resource name to comply.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20010: ODI-20010: Cannot display this Column Data**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20011: ODI-20011: Cannot perform this action: a Column of this Datastore is currently being edited**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

---

**Impact:** Other

**ODI-20012: ODI-20012: Cannot perform this action: the Datastore containing this Column is currently being modified**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20013: ODI-20013: Unable to perform the action because the package is currently being modified**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20014: ODI-20014: Cannot encrypt the Procedure: it is currently being modified**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20015: ODI-20015: Cannot initialize the Flexfields values**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20016: ODI-20016: Unable to add project user functions**

**Cause:** An unsupported action was attempted.

**Action:** No action required as Project user functions are not a valid selection to be added to a solution.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20017: ODI-20017: Unable to add project sequences**

**Cause:** An unsupported action was attempted.

**Action:** No action required as Project sequences are not a valid selection to be added to a solution.

**Level:** 32

---

**Type:** ERROR

**Impact:** Other

**ODI-20018: ODI-20018: Unable to add project variables**

**Cause:** An unsupported action was attempted.

**Action:** No action required as Project variables are not a valid selection to be added to a solution.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20019: ODI-20019: Unable to get GBO object**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20020: ODI-20020: Cannot change CKM**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20021: ODI-20021: Cannot change the order of this Command because you do not have 'Edit' privileges on this Object**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20022: ODI-20022: Could not change the KM**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20023: ODI-20023: Cannot Duplicate a Command**

**Cause:**

**Action:**

**Level:** 32

---

Type: ERROR

Impact: Other

**ODI-20024: ODI-20024: Cannot create the cross reference for the condition**

Cause:

Action:

Level: 32

Type: ERROR

Impact: Other

**ODI-20025: ODI-20025: Cannot create the cross references for the reference**

Cause:

Action:

Level: 32

Type: ERROR

Impact: Other

**ODI-20026: ODI-20026: Cannot view this Datastore: one of its Columns is currently being edited**

Cause:

Action:

Level: 32

Type: ERROR

Impact: Other

**ODI-20027: ODI-20027: Cannot view this Column: its Datastore is currently being edited**

Cause:

Action:

Level: 32

Type: ERROR

Impact: Other

**ODI-20028: ODI-20028: Cannot start execution.**

Cause:

Action:

Level: 32

Type: ERROR

Impact: Other

**ODI-20029: ODI-20029: Cannot move a line**

Cause:

Action:

Level: 32



---

**Type:** ERROR

**Impact:** Other

**ODI-20030: ODI-20030: Cannot start the generation. The file is probably already open.**

**Cause:** Attempt to open report file for output failed.

**Action:** Ensure the specified file is not currently open and the file permissions allow for write access before retrying the operation. Consider choosing a different file for output.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20031: ODI-20031: Cannot Delete a Command being Edited.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20032: ODI-20032: Cannot Delete a Command**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20033: ODI-20033: Cannot find the KM description**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20034: ODI-20034: Cannot find the Options list for a Command**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20035: ODI-20035: Could not find a description for the KM**

**Cause:**

**Action:**

**Level:** 32

---

**Type:** ERROR

**Impact:** Other

**ODI-20036: ODI-20036: Impossible to find the technology name, please check your privileges.**

**Cause:** The ODI security permissions were insufficient to allow access to the specified technology.

**Action:** Ensure the ODI user security permissions are correct.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20037: ODI-20037: Cannot find data transferred by the Drag'n'Drop**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20038: ODI-20038: Could not connect**

**Cause:** A connection was not established to the selected Logical Schema.

**Action:** Ensure the connection data for the Physical Schema of the selected Logical Schema is valid.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20039: ODI-20039: Incorrect context**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20040: ODI-20040: Problem encountered when determining the context**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20041: ODI-20041: No candidate datastore was found.**

**Cause:** There were no datastores in the current model usable as candidates for generating OUT interfaces.

**Action:** Consider creating an interface to load data into a datastore of the current model.

---

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20042: ODI-20042: Property key is empty**

**Cause:** The Property key for one of the specified Data Server's properties was not specified.

**Action:** Ensure a non-empty key value is supplied or remove the property with this key.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20043: ODI-20043: Invalid property key entered. Property key maximum length is 250 characters**

**Cause:** The Property key for one of the specified Data Server's properties had a length greater than 250 characters.

**Action:** Ensure a key value with the valid length is supplied or remove the property with this key.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20044: ODI-20044: Invalid property value entered. Property value maximum length is 250 characters**

**Cause:** The Property value for one of this Data Server's properties had a length greater than 250 characters.

**Action:** Ensure a value with the valid length is supplied or remove the property with this value.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20046: ODI-20046: Unable to change an open object**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20047: ODI-20047: Unable to change Value**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

---

**Impact:** Other

**ODI-20048: ODI-20048: Invalid Value entered. Value maximum length is 250 characters**

**Cause:** The Value for one of this object's FlexFields had a length greater than 250 characters.

**Action:** Ensure the value supplied has a valid length.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20049: ODI-20049: You cannot copy a folder into a folder belonging to another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Folders cannot be copied into hierarchy of another projects.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20050: ODI-20050: You cannot copy a knowledge module into another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Knowledge modules cannot be copied into hierarchy of another projects.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20051: ODI-20051: You cannot copy a package into a folder belonging to another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Packages cannot be copied into hierarchy of another projects.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20052: ODI-20052: You cannot copy an interface into a folder belonging to another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Interfaces cannot be copied into hierarchy of another projects.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20053: ODI-20053: You cannot copy a procedure into a folder belonging to another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Procedures cannot be copied into hierarchy of another projects.

---

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20054: ODI-20054: You cannot move a folder into a folder belonging to another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Folders cannot be moved into hierarchy of another projects.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20055: ODI-20055: You cannot move a knowledge module into another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Knowledge modules cannot be moved into hierarchy of another projects.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20056: ODI-20056: You cannot move a package into a folder belonging to another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Packages cannot be moved into hierarchy of another projects.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20057: ODI-20057: You cannot move an interface into a folder belonging to another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Interfaces cannot be moved into hierarchy of another projects.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20058: ODI-20058: You cannot move a procedure into a folder belonging to another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Procedures cannot be moved into hierarchy of another projects.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20059: ODI-20059: You cannot copy a knowledge module into a package belonging to another project.**

---

**Cause:** An unsupported operation was attempted.

**Action:** Knowledge modules cannot be copied into packages from another projects.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20060: ODI-20060: You cannot copy an interface into a package belonging to another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Interfaces cannot be copied into packages from another projects.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20061: ODI-20061: You cannot copy a procedure into a package belonging to another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Procedures cannot be copied into packages from another projects.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20062: ODI-20062: You cannot move a knowledge module into a package belonging to another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Knowledge modules cannot be moved into packages from another projects.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20063: ODI-20063: You cannot move an interface into a package belonging to another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Interfaces cannot be moved into packages from another projects.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20064: ODI-20064: You cannot move a step into a package belonging to another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Package steps cannot be moved into packages from another projects.

**Level:** 32

---

**Type:** ERROR

**Impact:** Other

**ODI-20065: ODI-20065: You cannot move a procedure into a package belonging to another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Procedures cannot be moved into packages from another projects.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20066: ODI-20066: You cannot copy a folder into another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Folders cannot be copied into hierarchy of another projects.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20067: ODI-20067: You cannot copy a procedure into another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Procedures cannot be copied into hierarchy of another projects.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20068: ODI-20068: You cannot copy a variable into another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Variables cannot be copied into hierarchy of another projects.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20069: ODI-20069: You cannot move a folder into another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Folders cannot be moved into hierarchy of another projects.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20070: ODI-20070: You cannot move a sequence into another project. Copy the sequence instead.**

**Cause:** An unsupported operation was attempted.

**Action:** Sequences cannot be moved into hierarchy of another projects.

**Level:** 32

---

**Type:** ERROR

**Impact:** Other

**ODI-20071: ODI-20071: You cannot move a procedure into another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Procedures cannot be moved into hierarchy of another projects.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20072: ODI-20072: You cannot move a variable into another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Variables cannot be moved into hierarchy of another projects.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20073: ODI-20073: You cannot copy a schedule into a scenario belonging to another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Schedules cannot be copied into hierarchy of another projects.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20074: ODI-20074: You cannot move a schedule into a scenario belonging to another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Schedules cannot be moved into hierarchy of another projects.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20075: ODI-20075: You cannot move a folder into one of its subfolders.**

**Cause:** An unsupported operation was attempted.

**Action:** Folders cannot be moved into their subfolders.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20076: ODI-20076: You cannot copy a knowledge module into a package step belonging to another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Knowledge modules cannot be copied into package steps from another projects.



---

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20077: ODI-20077: You cannot copy an interface into a package step belonging to another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Interfaces cannot be copied into package steps from another projects.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20078: ODI-20078: You cannot copy a procedure into a package step belonging to another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Procedures cannot be copied into package steps from another projects.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20079: ODI-20079: You cannot move a knowledge module into a package step belonging to another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Knowledge modules cannot be moved into package steps from another projects.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20080: ODI-20080: You cannot move an interface into a package step belonging to another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Interfaces cannot be moved into package steps from another projects.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20081: ODI-20081: You cannot move a step into a package step belonging to another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Steps cannot be moved into package steps from another projects.

**Level:** 32

**Type:** ERROR

**Impact:** Other

---

**ODI-20082: ODI-20082: You cannot move a procedure into a package step belonging to another project.**

**Cause:** An unsupported operation was attempted.

**Action:** Procedures cannot be moved into package steps from another projects.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20083: ODI-20083: Unable to perform the operation. {0} is being edited.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20084: ODI-20084: Only variables from the same project can be placed in a package.**

**Cause:** An unsupported operation was attempted.

**Action:** Variables from another projects cannot be placed in packages.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20085: ODI-20085: Only interfaces from the same project can be placed in a package.**

**Cause:** An unsupported operation was attempted.

**Action:** Interfaces from another projects cannot be placed in packages.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20086: ODI-20086: Only procedures from the same project can be placed in a package.**

**Cause:** An unsupported operation was attempted.

**Action:** Procedures from another projects cannot be placed in packages.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20087: ODI-20087: Error while duplicating**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

---

**Impact:** Other

**ODI-20088: ODI-20088: Error while generating the scenario**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20089: ODI-20089: Error during parameter initialization**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20090: ODI-20090: Error while duplicating**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20091: ODI-20091: An unexpected error occurred.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20092: ODI-20092: An error occurred while replacing the version.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20093: ODI-20093: Scenario generation is not allowed for non-saved object**

**Cause:** Scenario generation could not be performed because the source object was not saved.

**Action:** Ensure the source object is saved before attempting scenario generation for it.

**Level:** 32

**Type:** ERROR

---

**Impact:** Other

**ODI-20094: ODI-20094: Specify the object name to generate Scenario**

**Cause:** Scenario generation could not be performed because the source object's name was not specified.

**Action:** Ensure the source object's name is specified before attempting scenario generation for it.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20095: ODI-20095: Marker Group save was cancelled**

**Cause:** Marker group save was cancelled by a user.

**Action:** No action required.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20096: ODI-20096: Unable to edit the action line.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20097: ODI-20097: The line Name is mandatory**

**Cause:** A value for the Action Line Name field was not specified.

**Action:** Enter a non-empty value for the Action Line Name field.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20098: ODI-20098: Some Datatype Conversions between current and new Technologies are absent**

**Cause:** Changing the selected Model's Technology failed because the Physical Architecture did not provide datatype conversion rules for datatypes used by columns of datastores belonging to the selected model.

**Action:** Ensure datatype conversion rules exist for all datatypes used by columns of datastores belonging to the selected model or do not use datatypes that cannot be converted.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20099: ODI-20099: Unable to create execution window**

**Cause:**

---

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20100: ODI-20100: Unable to access a join or a filter**

**Cause:** Access to a join or filter failed due to insufficient ODI security permissions.

**Action:** Ensure the ODI user security permissions are correct for the join or filter object.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20101: ODI-20101: Unable to find mapping alias**

**Cause:** Access to the target mapping failed due to insufficient ODI security permissions.

**Action:** Ensure the ODI user security permissions are correct for the target mapping.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20102: ODI-20102: Unable to find source table alias**

**Cause:** Access to the source table failed due to insufficient ODI security permissions.

**Action:** Ensure the ODI user security permissions are correct for the source table.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20103: ODI-20103: Unable to access a target column**

**Cause:** Access to the target column failed due to insufficient ODI security permissions.

**Action:** Ensure the ODI user security permissions are correct for the target column.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20105: ODI-20105: "Schema", "Table", "Column" and "Filter" are mandatory fields.**

**Cause:** Values for the mandatory "Schema", "Table", "Column" and "Filter" fields were not supplied.

**Action:** Ensure values are supplied for these mandatory fields.

---

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20106: ODI-20106: Schema and Native sequence name are mandatory fields**

**Cause:** Values for the mandatory Schema and Native sequence name fields were not supplied.

**Action:** Ensure values are supplied for these mandatory fields.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20107: ODI-20107: A project sequence with the name "{0}" already exists in the project "{1}"**

**Cause:** Saving the project sequence failed because the Sequence name was not unique within the Project.

**Action:** Ensure the sequence name entered is unique.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20108: ODI-20108: A global sequence with the name "{0}" already exists**

**Cause:** Saving the Global sequence failed because the Global Sequence name was not unique.

**Action:** Ensure the sequence name entered is unique.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20109: ODI-20109: Error while restoring the version**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20110: ODI-20110: No version of this element exist.**

**Cause:** The selected version of this object was not found in version repository.

**Action:** Create or restore the selected version of the object.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20111: ODI-20111: Sub-model code cannot be empty.**

**Cause:** A value of the mandatory Sub-model code field was not supplied.

---

**Action:** Enter a non-empty value for the Sub-model code field.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20112: ODI-20112: The path defined in the logical schema is incorrect.**

**Cause:** Incorrect path was specified in physical schema which is linked to the logical schema of this datastore in the current context.

**Action:** Ensure the path specified in physical schema is correct.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20113: ODI-20113: The GUID that was supplied does not match the GUID for this user in the external identity store. Please retrieve the correct GUID before saving.**

**Cause:** The supplied GUID did not match GUID from external identity store.

**Action:** Provide a valid GUID.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20114: ODI-20114: Error while subscribing**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20115: ODI-20115: Error while stopping journalizing**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20116: ODI-20116: Aliases are specified and are not unique.**

**Cause:** Duplicate Alises were detected.

**Action:** Change the name of the join key alias.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20117: ODI-20117: Error while executing command line.**

**Cause:** An unexpected error occurred while trying to open the Report.

---

**Action:** Review the error details for further information.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20118: ODI-20118: Error while building the menu.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20119: ODI-20119: Error during generation.**

**Cause:** An unexpected error occurred during the report generation.

**Action:** Review the error details for further information.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20120: ODI-20120: Error while journalizing**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20121: ODI-20121: Error while saving the diagram**

**Cause:** An unexpected error occurred during the saving the diagram.

**Action:** Review the error details for further information.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20122: ODI-20122: Error while unsubscribing**

**Cause:** An unexpected error occurred during the unsubscribing action.

**Action:** Review the error details for further information.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20123: ODI-20123: Error while executing query**

**Cause:**

**Action:** Check the error details for further actions.



---

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20124: ODI-20124: Operation cancelled.**

**Cause:** Operation cancelled

**Action:** Review the other messages for further actions.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20126: ODI-20126: TreeTableColumn cannot be added**

**Cause:** TreeTableColumn with this order number already exists

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20127: ODI-20127: This TreeTableColumn cannot be removed.**

**Cause:** TreeTableColumn does not exist.

**Action:** Contact Oracle Support Servies.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20128: ODI-20128: Could not rollback.**

**Cause:** An error occurred during rollback operation.

**Action:** Review other messages for further information.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20129: ODI-20129: Exception occurred.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20130: ODI-20130: You must select a folder.**

**Cause:** A folder was not selected.

**Action:** Select a folder before attempting this action.

**Level:** 32

**Type:** ERROR

---

**Impact:** Other

**ODI-20131: ODI-20131: Cannot retrieve the table list**

**Cause:** An error occurred while trying to retrieve a list of tables.

**Action:** Review the message log for more information. If problem persists contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20132: ODI-20132: An interface cannot be moved to another project**

**Cause:** An unsupported drag and drop operation was attempted.

**Action:** No action required.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20133: ODI-20133: A procedure cannot be moved to another project**

**Cause:** An unsupported drag and drop operation was attempted.

**Action:** No action required.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20134: ODI-20134: A variable cannot be moved to another project**

**Cause:** An unsupported drag and drop operation was attempted.

**Action:** No action required

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20135: ODI-20135: A step cannot be moved to another package**

**Cause:** An unsupported drag and drop operation was attempted.

**Action:** No action required

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20138: ODI-20138: An error occurred during: dragGesture**

**Cause:** An unexpected error occurred while dragging an object.

**Action:** Review the message log for more information. If problem persists contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

---

**Impact:** Other

**ODI-20139: ODI-20139: An error occurred during: dragEnter**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20140: ODI-20140: An error occurred during: Drop**

**Cause:** An unexpected error occurred while dropping an object.

**Action:** Review the message log for more information. If problem persists contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20141: ODI-20141: Login Creation Error**

**Cause:** An unexpected error occurred while creating a new Login.

**Action:** Review the error details for further information.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20142: ODI-20142: Popup Menu Creation Error**

**Cause:** An unexpected error occurred while creating a popup menu.

**Action:** Review the error details for further information.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20144: ODI-20144: Error while Deleting**

**Cause:** An unexpected error occurred while deleting a tree object.

**Action:** Review the error details for further information.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20145: ODI-20145: Error while Opening splitframe.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

---

**ODI-20146: ODI-20146: Error occurred during duplication**

**Cause:** An unexpected error occurred while duplicating an object.

**Action:** Review the error details and message log for more information.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20148: ODI-20148: An error occurred during: drag over the object**

**Cause:** An unexpected error occurred while dragging an object over another object.

**Action:** Review the error details and message log for more information.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20149: ODI-20149: Logical schema can't be undefined**

**Cause:** A Logical schema was not defined.

**Action:** Define a Logical schema.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20150: ODI-20150: KM or Procedure already encrypted. No encryption was performed.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20151: ODI-20151: File is not found. Invalid file location**

**Cause:** The specified file could not be located in the file system.

**Action:** Ensure file location specified is valid and accessible.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20152: ODI-20152: Object cannot be deleted**

**Cause:** The specified object could not be deleted.

**Action:** Ensure the specified object exists and the security permissions permit deletion.

**Level:** 32

**Type:** ERROR

**Impact:** Other

---

**ODI-20155: ODI-20155: Changing the Logical Schema may require a re-generation of your Interfaces. It may be better to modify the Topology information instead.**

**Cause:**

**Action:**

**Level:** 32

**Type:** WARNING

**Impact:** Other

**ODI-20158: ODI-20158: Datastores distribution failed.**

**Cause:** An error occurred during the datastore distribution process.

**Action:** Review the message details and message log for more information. If problem persists contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20159: ODI-20159: The Column {0} is used as a Reference**

**Cause:** An attempt was made to delete a column referenced by another object.

**Action:** Delete the object which references this column then retry deleting this column.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20160: ODI-20160: The table {0} does not exist.**

**Cause:** An error occurred while executing the SQL request

**Action:** Review the message details for more information. If problem persists contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20161: ODI-20161: Standard reverse-engineering failed.**

**Cause:** An error occurred during the standard reverse-engineering process.

**Action:** Ensure the technology or driver supports standard reverse-engineering. Otherwise choose Customized Reverse and select an appropriate RKM for the technology.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20162: ODI-20162: The context is not valid.**

**Cause:** A Context was not specified.

**Action:** Specify a Context.

**Level:** 32

---

**Type:** ERROR

**Impact:** Other

**ODI-20163: ODI-20163: Unable to add object**

**Cause:** An error occurred while dragging and dropping an object.

**Action:** Review the message details and message log for more information.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20164: ODI-20164: The line Name is mandatory**

**Cause:** A name was not specified.

**Action:** Specify a Line name.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20165: ODI-20165: The project name {0} is a reserved word.**

**Cause:** A reserved word was used as the name of a project.

**Action:** Enter a different project name.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20166: ODI-20166: The project code {0} is a reserved word.**

**Cause:** A reserved word was used as the project code.

**Action:** Enter a different project code.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20167: ODI-20167: Logical schema is not set for the current context**

**Cause:** A Logical schema was not set for the current context.

**Action:** Ensure the Logical Schema is not set to "Undefined" in the Context editor.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20168: ODI-20168: Logical schema is not set for the current context**

**Cause:** A Logical schema was not set for the current context.

**Action:** Ensure the Logical Schema is not set to "Undefined" in the Context editor.

**Level:** 32

**Type:** ERROR

**Impact:** Other

---

**ODI-20169: ODI-20169: The field {0} is mandatory.**

**Cause:** A mandatory field was not specified.

**Action:** Enter a value for this field.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20170: ODI-20170: You are trying to insert this versioned object but the version was deleted. Please re-create a version for this object.**

**Cause:** The requested version of the object did not exist in the repository.

**Action:** Recreate the required version of this object.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20171: ODI-20171: The solution already contains a child of {0}. To add {1} to the solution, you should delete {2} {3}. It is advised to use the button "synchronize" later to check the solution's coherence.**

**Cause:** The solution already contained the specified object as a child.

**Action:** Delete the child object from the solution before retrying the addition. Consider using the synchronize option to verify the solution's coherence.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20172: ODI-20172: The solution already contains a parent of {0}. To add {1} to the solution, you should delete {2} {3}. It is advised to use the button "synchronize" later to check the solution's coherence.**

**Cause:** The solution has already contained the specified object as a parent of {0}.

**Action:** Delete the parent object from the solution before retrying the addition. Consider using the synchronize option to verify the solution's coherence.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20173: ODI-20173: An error occurs while generating the procedure**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20174: ODI-20174: Folder {0} already contains an interface named {1}**

**Cause:** An interface of the same name already existed in the specified folder.

**Action:** Specify another name for the interface.

---

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20175: ODI-20175: You cannot give an empty name to an interface**

**Cause:** The Interface's name was not specified.

**Action:** Enter a non-empty value for the interface's name.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20176: ODI-20176: You cannot create multiple interfaces with the same name**

**Cause:** An interface of the same name already existed.

**Action:** Specify a different name for the interface.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20177: ODI-20177: You must select a generation folder**

**Cause:** The Generation folder was not selected.

**Action:** Select a generation folder.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20178: ODI-20178: Folder {0} already contains an interface named {1}**

**Cause:** An interface of the same name already existed in the specified folder.

**Action:** Specify another name for the interface.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20179: ODI-20179: You cannot create multiple interfaces with the same name**

**Cause:** An interface of the same name already existed.

**Action:** Specify a different name for the interface.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20180: ODI-20180: You cannot choose an expiration date in the past.**

**Cause:** Entered expiration date was in the past.

**Action:** Enter valid expiration date.

**Level:** 32

**Type:** ERROR



---

**Impact:** Other

**ODI-20181: ODI-20181: You cannot set an expiration date if there is no password.**

**Cause:** No password was entered.

**Action:** Enter a password before setting an expiration date.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20182: ODI-20182: Error while opening window**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20183: ODI-20183: Error while refreshing Solution**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20184: ODI-20184: The request to retrieve the sequence list has not been defined on the technology.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20185: ODI-20185: Error while opening window**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20186: ODI-20186: Error while saving**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

---

**ODI-20187: ODI-20187: Error while adding the marker**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20188: ODI-20188: This object is locked by another user. You cannot edit its markers.**

**Cause:** The object was locked by another user.

**Action:** Wait until the object is unlocked. Consider contacting the user who has the object locked.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20189: ODI-20189: You do not have the sufficient privileges to reverse-engineer a model**

**Cause:** The model could not be reverse-engineered due to insufficient privileges.

**Action:** Ensure the SUPERVISOR or owner of model grants the appropriate permissions.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20190: ODI-20190: You cannot reverse engineer a model in 'Standard' mode: the model technology assumes RKM to be selected.**

**Cause:** No RKM was specified for this model.

**Action:** Select an RKM for this model.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20191: ODI-20191: The model you want to reverse-engineer references a logical schema that no longer exists.**

**Cause:** The referenced Logical Schema for the Model was not found.

**Action:** Ensure a valid Logical Schema is assigned for the Model.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20192: ODI-20192: Error while replacing versioned object**

**Cause:**

**Action:**

**Level:** 32

---

**Type:** ERROR  
**Impact:** Other  
**ODI-20193: ODI-20193: An error occurred during the versioning operation.**  
**Cause:**  
**Action:**  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other  
**ODI-20194: ODI-20194: Your license does not allow Versioning operations.**  
**Cause:**  
**Action:**  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other  
**ODI-20195: ODI-20195: Unable to unlock this object**  
**Cause:**  
**Action:**  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other  
**ODI-20196: ODI-20196: You must select an object version**  
**Cause:** No version selected for checkout.  
**Action:** Select version for checkout.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other  
**ODI-20197: ODI-20197: Your license does not allow Versioning operations.**  
**Cause:**  
**Action:**  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other  
**ODI-20198: ODI-20198: Error while creating the version.**  
**Cause:**  
**Action:**  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other

---

**ODI-20199: ODI-20199: Your license does not allow Versioning operations.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20200: ODI-20200: An error happened while comparing the versions**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20201: ODI-20201: Error while refreshing.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20202: ODI-20202: Synchronisation was stopped by the user.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20203: ODI-20203: The current version for this object no longer exists. Please create a new version for this object.**

**Cause:** The current version for this object was not found in the repository.

**Action:** Create a new version for this object.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20205: ODI-20205: Could not delete object. This object is being used.**

**Cause:** The object deletion failed because it was already in use.

**Action:** Remove the usage of the selected object before retrying the deletion.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20206: ODI-20206: Could not delete object. This object is being displayed.**

---

**Cause:** The object deletion failed because it was being displayed.

**Action:** Close object before retrying the deletion.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20208: ODI-20208: A code was duplicated:**

**Cause:** A Flex field with the same code already existed.

**Action:** Enter another Flex field code.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20209: ODI-20209: An error occurred.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20210: ODI-20210: Error When Printing...**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20211: ODI-20211: Error When Displaying Node...**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20212: ODI-20212: An error occurred while checking errors**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20213: ODI-20213: An error occurred while recovering an object in a node**

**Cause:**

**Action:**

---

**Level:** 32  
**Type:** ERROR  
**Impact:** Other  
**ODI-20214: ODI-20214: An error occurred while deleting**  
**Cause:**  
**Action:**  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other  
**ODI-20215: ODI-20215: An Error occured while**  
**Cause:**  
**Action:**  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other  
**ODI-20216: ODI-20216: Error while deleting**  
**Cause:**  
**Action:**  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other  
**ODI-20217: ODI-20217: Error while executing the reverse-engineering**  
**Cause:**  
**Action:**  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other  
**ODI-20218: ODI-20218: Error during duplication ...**  
**Cause:**  
**Action:**  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other  
**ODI-20219: ODI-20219: Error while opening**  
**Cause:**  
**Action:**  
**Level:** 32  
**Type:** ERROR

---

**Impact:** Other

**ODI-20220: ODI-20220: Error during data loading ....**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20221: ODI-20221: Error during execution ...**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20222: ODI-20222: Error during scenario creation ...**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20223: ODI-20223: Error When Purging Log**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20224: ODI-20224: An interface with the same name already exists in this folder. Please change the name of the new interface.**

**Cause:** An interface with the same name already existed in this folder.

**Action:** Specify another name for the interface.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20225: ODI-20225: Error while creating the popup menu**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

---

**ODI-20226: ODI-20226: Error while applying the changes**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20227: ODI-20227: You cannot copy this column. Column name already in use.**

**Cause:** Column copy failed because the Datastore already contained a column with the same name.

**Action:** Select another column to drop to datastore.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20228: ODI-20228: Error while creating the popup menu**

**Cause:** Retrieval of the Available Methods for the column failed.

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20229: ODI-20229: Unable to create condition.**

**Cause:** The editor for the Condition could not be opened.

**Action:** Ensure the repository database connection is not broken and the ODI Security permissions are correct.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20230: ODI-20230: Error while creating the popup menu**

**Cause:** Retrieval of the Available Methods for the Condition failed.

**Action:** Ensure the repository database connection is not broken and the ODI Security permissions are correct.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20231: ODI-20231: Unable to create a synonym for this table.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other



---

**ODI-20232: ODI-20232: Error while deleting columns**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20233: ODI-20233: Error during the drag-and-drop operation**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20234: ODI-20234: You do not have the sufficient privileges to add this object.**

**Cause:** The operation failed due to insufficient ODI security on Column.

**Action:** Ensure the ODI user security permissions are correct specifically the Column Duplication setting.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20235: ODI-20235: Error during the drag-and-drop operation**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20236: ODI-20236: You do not have the sufficient privileges to add this object.**

**Cause:** The operation failed due to insufficient ODI security on DataStore.

**Action:** Ensure the ODI user security permissions are correct.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20237: ODI-20237: Unable to duplicate the column.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20238: ODI-20238: Unable to duplicate the table.**

---

**Cause:**  
**Action:**  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other

**ODI-20239: Error during the action**  
**Cause:**  
**Action:**  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other

**ODI-20240: ODI-20240: Error while deleting**  
**Cause:**  
**Action:**  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other

**ODI-20241: ODI-20241: Unable to apply changes.**  
**Cause:** The changes to the filter could not be applied.  
**Action:** Save the object before retrying to apply the filter.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other

**ODI-20242: ODI-20242: Error while creating the popup menu**  
**Cause:** Retrieval of the Available Methods for the filter failed.  
**Action:** Ensure the repository database connection is not broken and the ODI Security permissions are correct.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other

**ODI-20243: ODI-20243: Unable to add column.**  
**Cause:**  
**Action:**  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other

**ODI-20244: ODI-20244: Unable to add reference**  
**Cause:**

---

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20245: ODI-20245: Unable to add table**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20246: ODI-20246: Error while applying the changes**

**Cause:** The reference to the Model could not be created.

**Action:** Ensure the repository database connection is not broken and the ODI Security permissions are correct.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20247: ODI-20247: Unable to add key.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20248: ODI-20248: Error while opening window**

**Cause:** The editor could not be opened.

**Action:** Save the object before retrying the edit.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20249: ODI-20249: Error while creating the popup menu**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20250: ODI-20250: Error while**

**Cause:**

**Action:**

---

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20251: ODI-20251: An unexpected error has occurred**

**Cause:** Unable to access the Security Authorization settings.

**Action:** Ensure the repository database connection is not broken and the ODI Security permissions are correct.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20252: ODI-20252: Unable to apply changes.**

**Cause:** Saving the model condition failed.

**Action:** Ensure the repository database connection is not broken and the ODI Security permissions are correct.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20253: ODI-20253: The object was deleted by another user**

**Cause:** The operation could not be performed because the specified object could not found.

**Action:** Refresh the view and retry the operation.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20254: ODI-20254: The marker was deleted by another user**

**Cause:** The operation could not be performed because the specified Marker object was in an Inconsistent state.

**Action:** Refresh the view and retry the operation.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20255: ODI-20255: Marker name is mandatory**

**Cause:** Marker could not be saved because the mandatory Name field was not entered.

**Action:** Enter a value in the Maker name field.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20256: ODI-20256: You do not have the sufficient privileges to change the marker**

---

**Cause:** Modification of the Marker failed due to insufficient ODI security privileges.

**Action:** Ensure the ODI user security permissions are correct.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20257: ODI-20257: The Where text is mandatory when the Filter is active for a static control.**

**Cause:** The WHERE clause was null or empty.

**Action:** Ensure the WHERE clause is valid.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20258: ODI-20258: It is not possible to check the expression due to DBMS connection failure**

**Cause:** Connection to the DBMS failed.

**Action:** Ensure the DBMS is available and the connection information to it is correctly specified.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20259: ODI-20259: cannot show the data since the join points to different connections**

**Cause:** Unable to retrieve data due to a conflict between the physical schemas involved.

**Action:** Ensure the Topology or Context settings are correct and multiple data stores in the same Source Set are not connected using different Physical Schemas.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20260: ODI-20260: Name and Code columns of the FlexField cannot be empty.**

**Cause:** FlexField name or code were found to be empty or null.

**Action:** Enter a name and a code for the FlexField.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20261: ODI-20261: The "Procedure Name" is mandatory.**

**Cause:** The "Procedure Name" field value was not specified.

**Action:** Enter a value for the "Procedure Name" field.

**Level:** 32

---

**Type:** ERROR

**Impact:** Other

**ODI-20300: ODI-20300: Error while printing the diagram**

**Cause:** An unexpected condition has occurred in the print system.

**Action:** Check the printer settings and physical printer.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20301: ODI-20301: Error while saving the diagram**

**Cause:** The save file could not be created.

**Action:** Check the destination folder is writable and that there is sufficient disk space.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20310: Unsupported Flavor**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20311: ODI-20311: An unexpected exception occurred while reading or writing a text in a business object. Please contact Oracle technical support.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20312: ODI-20312: An error occurred while printing.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20313: ODI-20313: Could not double click**

**Cause:** An unexpected error has occurred.

**Action:** Contact Oracle Support Services.

**Level:** 32

---

**Type:** ERROR

**Impact:** Other

**ODI-20315: ODI-20315: Invalid Password**

**Cause:** The Password is incorrect.

**Action:** Correct the password and try again.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20316: ODI-20316: A timeout occurred while trying to establish a connection.**

**Cause:** A timeout error occurred while connecting to the database.

**Action:** Verify that the Database Connection details are correct and the database is available.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20317: ODI-20317: The field "{0}" is mandatory.**

**Cause:** A value has not been provided for a required field.

**Action:** Enter a value for the named field.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20318: ODI-20318: The icon {0} cannot be found.**

**Cause:** An unexpected error has occurred.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20319: ODI-20319: {0} is not a valid date for field {1}. The format is: {2}**

**Cause:** The format of the date does not match the required format.

**Action:** Enter a valid date using the correct date format.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20320: ODI-20320: Error when applying changes.**

**Cause:** An unexpected error has occurred.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

---

**Impact:** Other

**ODI-20321: ODI-20321: Error when initializing the panel.**

**Cause:** An unexpected error has occurred.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20322: ODI-20322: Unable to add a Step.**

**Cause:** An unexpected error has occurred.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20323: ODI-20323: Unable to execute the step**

**Cause:** An unexpected error has occurred.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20324: ODI-20324: Cannot execute the Package**

**Cause:** An unexpected error has occurred.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20325: ODI-20325: Unable to open the linked object.**

**Cause:** An unexpected error has occurred.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20326: ODI-20326: Unable to edit the text**

**Cause:** An unexpected error has occurred.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20327: ODI-20327: Unable to modify the value.**



---

**Cause:** An unexpected error has occurred.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20328: ODI-20328: Unable to define the next Step.**

**Cause:** An unexpected error has occurred.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20329: ODI-20329: Unable to delete Steps(s). You do not have Edit privileges.**

**Cause:** An unexpected error has occurred.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20330: ODI-20330: Unable to delete Link(s). You do not have Edit privileges.**

**Cause:** You must have Edit privilege on each steps of the link.

**Action:** Review the Security settings for the steps and ensure that you have the correct permissions.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20331: ODI-20331: The Step diagram is not be accessible.**

**Cause:** You do not have permission to access this step.

**Action:** Check the diagram security settings and verify that you have permission to access the diagram.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20332: ODI-20332: Cannot change the position of this object**

**Cause:** An unexpected error has occurred.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20333: ODI-20333: Cannot view this Step because the Package is being edited**

---

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20335: ODI-20335: Printing Options not accessible.**

**Cause:** An unexpected error has occurred.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20336: ODI-20336: Unknown event sent to the Package event manager.**

**Cause:** An unexpected error has occurred.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20337: ODI-20337: A Knowledge Module cannot be added as a Step.**

**Cause:** Only a DataStore,Model,Sub Model,Interface,Procedure or Variable can be added as a Step.

**Action:** Use a valid object type for your step creation.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20338: ODI-20338: A starting Step must be defined.**

**Cause:** A Starting step has been defined.

**Action:** Select the first step in the package and mark it as the starting step.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20339: ODI-20339: One or more Steps are not linked.**

**Cause:** All steps must be linked.

**Action:** Ensure that all steps are linked .

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20340: ODI-20340: Only one starting Step can be defined.**

**Cause:** A package must have one and only one starting steps.

---

**Action:** Ensure that you have only one starting step defined .

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20341: ODI-20341: You don't have the appropriate privileges.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20342: ODI-20342: Cannot open the Expression Editor**

**Cause:** An unexpected error has occurred.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20343: ODI-20343: There are errors in your diagram**

**Cause:** The diagram may contain objects that are not connected, or objects that are not completely defined.

**Action:** Check the diagram and ensure that all objects are connected and fully defined.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20344: ODI-20344: Cannot launch the editor for this expression**

**Cause:** An error occurred while retrieving the language for the expression. This may be due to an unexpected exception, or the language may not be available for the schema's technology.

**Action:** Review the message log for additional errors. Ensure that the schema has a valid technology for which the language is set.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20345: ODI-20345: Cannot change the clause position**

**Cause:** An unexpected internal exception has occurred.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

---

**ODI-20346: ODI-20346: Cannot get the boolean value of an option**

**Cause:** The boolean value of the option could not be retrieved due to a security error.

**Action:** Review the message log and contact Oracle Support Services for further assistance.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20347: ODI-20347: Error during data transfer for drag and drop**

**Cause:** An internal error occurred while dropping the object into the diagram.

**Action:** Review the message log for additional information and contact Oracle Support Services for further assistance.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20348: ODI-20348: An interface with the same name already exists in this folder. Please change the name of the new interface.**

**Cause:** An interface with the specified name exists in the folder. The interface name must be unique within a folder.

**Action:** Enter a new interface name that is unique within the folder.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20349: ODI-20349: Unknown event detected by the event manager. Please contact Oracle Support Services.**

**Cause:** The Package Event Manager was called to action an unknown event.

**Action:** Contact Oracle Support Services for further assistance.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20350: ODI-20350: Your diagram contains one or more FATAL/CRITICAL errors preventing display of the Flow Editor**

**Cause:** The diagram is incomplete or contains errors that prevent the Flow Editor being displayed.

**Action:** Return to the diagram tab and review the error messages using the errors and warnings button in the toolbar. Fix the errors in order to access the Flow Editor.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20351: ODI-20351: Error adding source to Quick Edit source table.**

---

**Cause:** An internal error occurred which prevented the source being added.

**Action:** Contact Oracle Support Services for further assistance.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20352: ODI-20352: Error adding target datastore to Quick Edit mapping table.**

**Cause:** An internal error occurred which prevented the target being added.

**Action:** Contact Oracle Support Services for further assistance.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20353: ODI-20353: Only a single column may be pasted into a Quick Edit table.**

**Cause:** The clipboard contains multiple columns. Quick Edit only supports pasting a single cell into a table.

**Action:** Select the cells to be copied and paste them one at a time.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20354: ODI-20354: Paste targets must be in the same column as the previous copy. This does not apply to Expression columns (Lookup Expression, Join Expression, Filter Expression, and Mapping Expression).**

**Cause:** You have selected a value from one column, and tried to paste it into a different column. This is only supported for Expression Columns.

**Action:** Please enter the values into the cell manually.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20355: ODI-20355: Duplicate value is not supported on this column.**

**Cause:** The paste operation is not permitted in the Alias and Target Column Name fields as these fields must contain a unique value.

**Action:** Please enter the Alias or Name field manually.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20356: ODI-20356: Can not perform paste into a read-only column.**

**Cause:** The Paste operation is not permitted on read-only columns.

**Action:** You may not update this value in the table.

**Level:** 32

**Type:** ERROR

---

**Impact:** Other

**ODI-20357: ODI-20357: Can not perform deletion because the target datastore is not temporary.**

**Cause:** An attempt was made to delete a row in the target, but the target datastore is not a temporary table. Only rows in a temporary target table may be deleted.

**Action:** You cannot delete the row.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20358: ODI-20358: Interface cannot be saved because it has a fatal error: {0}.**

**Cause:** The Interface could not be saved because it contains a fatal error which must be resolved.

**Action:** Review the errors in the Diagram tab and resolve the fatal errors.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20359: ODI-20359: Only one cell can be copied one at a time.**

**Cause:** More than one cell was selected. Quick Edit only supports copying a single cell.

**Action:** Select and copy a single cell.

**Level:** 32

**Type:** SET\_AT\_RUNTIME

**Impact:** Other

**ODI-20701: ODI-20701: The Name field is mandatory.**

**Cause:** The Name field was not entered.

**Action:** Enter a name for the Load Plan.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20702: ODI-20702: The name given for the Load Plan is already used by another load plan. Please provide another name.**

**Cause:** The name provided for the Load Plan was not unique.

**Action:** Enter a unique name for the Load Plan.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20703: ODI-20703: Variable "{0}" is not found.**

**Cause:** The variable could not be found.

**Action:** Provide another name for the variable.

---

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20704: ODI-20704: Datatype of variable "{0}" has been changed.**

**Cause:** The datatype of the original variable is different to the datatype of the load plan variable.

**Action:** Verify the datatype of the variable and ensure that the types of the original and load pln variables match.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20705: ODI-20705: This variable is used in one or more case steps. Removing it will trigger deletion of those case steps, and all of their child steps. Do you want to continue?**

**Cause:** An attempt was made to remove a variable which is used in one or more case steps.

**Action:** o remove the variable and its associated case steps, click Yes. Otherwise, click No, and nothing will be removed.

**Level:** 32

**Type:** WARNING

**Impact:** Other

**ODI-20706: ODI-20706: The Step Name is mandatory.**

**Cause:** The Step Name field was not entered.

**Action:** Enter a name for the Step.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20707: ODI-20707: The Variable is mandatory.**

**Cause:** A Variable was not selected.

**Action:** Select a variable.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20708: ODI-20708: The Scenario is mandatory.**

**Cause:** A Scenario was not selected.

**Action:** Select a Scenario.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20709: ODI-20709: The Value is mandatory.**

---

**Cause:** A Value was not provided.

**Action:** Enter a Value.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20710: ODI-20710: The Value format is not valid.**

**Cause:** An incorrect format was given for the Value.

**Action:** Check the format of the Value and correct it.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20711: ODI-20711: The Step Name is mandatory.**

**Cause:** The Step Name field was not entered.

**Action:** Provide the name of the Step.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20712: ODI-20712: The Variable is mandatory.**

**Cause:** A Variable was not selected.

**Action:** Select a Variable.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20713: ODI-20713: The Scenario is mandatory.**

**Cause:** A Scenario was not selected.

**Action:** Select a Scenario.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20714: ODI-20714: The Context is mandatory.**

**Cause:** A Context was not selected for execution.

**Action:** Select an execuion Context.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20715: ODI-20715: The Logical Agent is mandatory.**

**Cause:** A Logical Agent was not selected for execution.

**Action:** Select a Logical Agent.



---

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20716: ODI-20716: No Physical Agent is defined for the selected Logical Agent and Context. Edit Logical Agent "{0}", and define a Physical Agent for Context "{1}".**

**Cause:** There was no Physical Agent associated with this Logical Agent in the specified context.

**Action:** Associate a Physical Agent with the Logical Agent in the selected context.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20717: ODI-20717: No Physical Agents are running. A Physical Agent must be running in order to Restart a Load Plan.**

**Cause:** There were no Physical Agents running.

**Action:** Start a Physical Agent before restarting the Load Plan.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20718: ODI-20718: No Physical Agents are running. A Physical Agent must be running in order to Stop a Load Plan.**

**Cause:** There were no Physical Agents running.

**Action:** Start the Agent before executing the Load Plan.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20719: ODI-20719: Scenario "{0}" is not found.**

**Cause:** The scenario was not found.

**Action:** Specify an exiting scenario.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-20720: ODI-20720: Physical Agent "{0}" - which is defined in Logical Agent "{1}" to be used for Context "{2}" - is not responding. Verify that Physical Agent "{0}" has been started.**

**Cause:** The Physical Agent was not reachable.

**Action:** Check the Physical Agent and start it.

**Level:** 32

**Type:** ERROR

**Impact:** Other

---

**ODI-20721: ODI-20721: Interface contains one or more errors. You should correct the errors before attempting to execute it**

**Cause:** The interface contains errors which prevent it from being executed.

**Action:** Review the errors shown in the interface editor and update the interface to fix the problems.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23001: ODI-23001: The import process failed**

**Cause:** The work repository export file specified could not be imported.

**Action:** Ensure the specified file is readable and is a valid work repository export file.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23006: ODI-23006: Agent Test failed**

**Cause:** Agent could not be contacted using the specified connection details.

**Action:** Ensure the Agent connection details are correct and the Agent is running.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23007: ODI-23007: Data Source already exists for "{0}".**

**Cause:** The Data Source has already been associated with this Agent.

**Action:** No action is necessary as the Data Source is already associated with this Agent. Consider removing the Data Source from this Agent and retrying this action.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23010: ODI-23010: Please enter first a name, an expression and a help text for this language element.**

**Cause:** The Name, Expression or Help Text parameter values for this Language Element were not entered in the Definition panel. These are mandatory parameters.

**Action:** Return to the Definition panel and ensure the Name, Expression and Help Text parameters have valid values.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23011: ODI-23011: Name is empty**

---

**Cause:** A value for the Name parameter of the Language Element Implementation was not entered. This is a mandatory parameter.

**Action:** Enter a valid value for the Name parameter before saving this Language Element.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23012: ODI-23012: Expression is empty**

**Cause:** A value for the Expression parameter of the Language Element Implementation was not entered. This is a mandatory parameter.

**Action:** Enter a valid value for the Expression parameter before saving this Language Element.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23013: ODI-23013: Help is undefined**

**Cause:** A value for the Help Text parameter of the Language Element Implementation was not entered. This is a mandatory parameter.

**Action:** Enter a value for the Help Text parameter before saving this Language Element.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23014: ODI-23014: Technology is undefined**

**Cause:** A value for the Technology parameter of the Language Element Implementation was not entered. This is a mandatory parameter.

**Action:** Enter a value for the Technology parameter before saving this Language Element.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23015: ODI-23015: Logical Schema {0} is already linked to a physical schema in context {1}.**

**Cause:** A Physical Schema has already been defined for this Context and Logical Schema combination.

**Action:** Remove the Context and Logical Schema combination from the Context editor, then retry saving the Physical Schema.

**Level:** 32

**Type:** ERROR

**Impact:** Other

- 
- ODI-23016: ODI-23016: The context is either invalid or no longer exists in the database.**  
**Cause:** One of the Contexts used by the Physical Schema is invalid or no longer exists in the Master Repository.  
**Action:** Ensure the Context for the Physical Schema is correct by either selecting a valid Context for the Physical Schema or recreating the missing Context.
- Level:** 32  
**Type:** ERROR  
**Impact:** Other
- ODI-23017: ODI-23017: This Physical Schema already exists for this data server.**  
**Cause:** A Physical Schema referencing this Data Server has already been defined in the Master Repository.  
**Action:** Specify the correct Physical Schema for this Data Server to use.
- Level:** 32  
**Type:** ERROR  
**Impact:** Other
- ODI-23018: ODI-23018: Unable to connect to Work Repository**  
**Cause:** The Work Repository could not be accessed using the connection details defined for it. This may be due to the database or host not being available, or the password could have changed.  
**Action:** Ensure the Work Repository host and database are active. Using the Work Repository editor, ensure the connection details for it are correct.
- Level:** 32  
**Type:** ERROR  
**Impact:** Other
- ODI-23019: ODI-23019: Error Detected during Repository Installation. Invalid connection parameters.**  
**Cause:** The repository installation process was unable to connect to the repository database.  
**Action:** Correct any errors identified in the installation log and retry the installation. If the problem persists then contact Oracle Support Services.
- Level:** 32  
**Type:** ERROR  
**Impact:** Other
- ODI-23020: ODI-23020: Error Detected during Repository Installation. Invalid External Authentication credentials.**  
**Cause:** The ODI Supervisor credentials supplied did not match the credentials held in the External Password Store.  
**Action:** Retry the installation, ensuring the Supervisor user name and password match those held in the external store.
- Level:** 32  
**Type:** ERROR

---

**Impact:** Other

**ODI-23021: ODI-23021: Error Detected during Repository Installation. Invalid External Authentication configuration.**

**Cause:** A connection to the External Authentication Store could not be established.

**Action:** Ensure the External Authentication Store is available and the connection details specified in the JPS configuration file are valid.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23022: ODI-23022: An error occurred during the generation of the Data Service.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23023: ODI-23023: The Schema path ({0}) is not supported**

**Cause:** The Model's Physical Schema attempted to define the Schema path using an unsupported protocol (ftp, http or file).

**Action:** Change the Physical Schema to not use ftp, http or file protocol to reference the file.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23024: ODI-23024: The URL is mandatory.**

**Cause:** The URL field has not been entered and is a mandatory parameter.

**Action:** Enter the URL parameter. A template chosen from the drop down list may help to ensure the syntax is correct.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23025: ODI-23025: The ID is mandatory.**

**Cause:** The Repository ID parameter has not been entered and is a mandatory parameter.

**Action:** Enter an integer value for the Repository ID parameter.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23026: ODI-23026: The ID must be an integer value.**

**Cause:** The value entered for the Repository ID is not a valid integer.

---

**Action:** Enter an integer value for the Repository ID parameter.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23027: ODI-23027: The driver is mandatory.**

**Cause:** A JDBC Driver was not specified and is a mandatory parameter.

**Action:** Select a JDBC Driver from the list of values.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23028: ODI-23028: The password is mandatory.**

**Cause:** The Supervisor user's Password parameter was not specified.

**Action:** Enter the Supervisor password.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23029: ODI-23029: The confirm password is mandatory.**

**Cause:** The Supervisor user's Confirm Password parameter was not specified.

**Action:** Enter the Supervisor user's password in the Confirm Password parameter.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23030: ODI-23030: Password and Confirm Password are different**

**Cause:** The Password and Confirm Password parameters are not the same.

**Action:** Ensure the same value is entered for both the Password and Confirm Password parameters.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23031: ODI-23031: The Supervisor username is mandatory.**

**Cause:** The Supervisor User parameter was not entered.

**Action:** Enter a value for the Supervisor User parameter ensuring it matches a user in the external enterprise identify store, or switch to ODI Authentication.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23032: ODI-23032: Maximum number of sessions cannot be less or equal to 0.**

**Cause:** The Maximum Number of Sessions parameter value was specified as 0.

---

**Action:** Change the Maximum Number of Sessions parameter in the Agent Definition tab to a value greater than 0.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23033: ODI-23033: The file reverse-engineering is only possible for delimited files.**

**Cause:** The file format for the specified file was not delimited.

**Action:** Select a delimited format file and retry the reverse-engineering action.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23035: ODI-23035: Can not update the scheduling - This agent may not be running**

**Cause:** The Update Scheduling action could not be performed because the ODI Client could not connect to the Agent.

**Action:** Check that the Agent connection details are correct and that the agent is running. Use the Agent Test button to check the connection details.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23036: ODI-23036: Logical Schema not set for this Context**

**Cause:** A Logical Schema entry in the Physical Schema's Context was specified as <Undefined>.

**Action:** Ensure none of the Logical Schemas on the Physical Schema's Context tab are set to <Undefined>.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23037: ODI-23037: To use scheduling please associate a Logical Agent to a Physical Agent via the Logical Architecture Accordion in the Topology Navigator**

**Cause:** There are no logical agents available to use for scheduling.

**Action:** Associate a logical agent with a physical agent using the Topology Navigator and then resubmit your schedule request.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23038: ODI-23038: Cannot resolve the table name. Check the masks defined for this physical schema.**

---

**Cause:** The table and schema format could not be calculated. This is because the object mask has not been set for the Physical Schema that contains this table.

**Action:** From the Topology Navigator edit the Physical Schema containing this table and ensure the Masks parameter value is valid for the schema based on its technology (for example "%SCHEMA.%OBJECT").

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23039: ODI-23039: You cannot carry out this type of export.**

**Cause:** The export type specified is not supported.

**Action:** Retry the export. If the problem persists then contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23040: ODI-23040: Import file "{0}" error**

**Cause:** An error occurred during the import file process.

**Action:** Correct any errors identified in the error log and retry the import process. If the problem persists then contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23042: ODI-23042: An error occurred while changing the repository number.**

**Cause:** An error occurred while changing the repository number.

**Action:** Correct any errors identified in the message log and retry the action. If the problem persists then contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23043: ODI-23043: The Repository ID must be numeric.**

**Cause:** The value specified for the Repository ID parameter was not a valid numeric value.

**Action:** Enter a valid numeric value for the Repository ID parameter.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23044: ODI-23044: The new ID you have chosen is already in use as a table "{0}" primary key. The renumbering has been aborted. No changes have been made.**

**Cause:** The Repository ID specified is already used by an existing object.

**Action:** Enter a different value for the Repository ID parameter ensuring it is unique within the repository.



---

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23045: ODI-23045: You may not renumber a repository before version 11. Please upgrade your repository first.**

**Cause:** The renumber functionality is not supported for ODI Repository versions prior to version 11.

**Action:** Upgrade the repository to version 11 (or higher) and then renumber it.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23046: ODI-23046: An error was encountered during the test.**

**Cause:** An attempt to connect a Work Repository failed.

**Action:** Correct any errors identified in the message log. Ensure the Work Repositories are available and the connection information is correctly specified in the Master Repository. Retry the test.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23047: ODI-23047: Could not connect to the work repository. The renumbering process has been aborted. No changes have been made.**

**Cause:** An attempt to connect a Work Repository failed.

**Action:** Correct any errors identified in the message log. Ensure the Work Repositories are available and the connection information is correctly specified in the Master Repository. Retry the test.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23048: ODI-23048: Import report generation error**

**Cause:** The import was performed, but there was an unexpected error while opening the Import Report.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-23049: ODI-23049: Error Detected during Repository Installation**

**Cause:** An error occurred during the creation or import of the Master Repository.

**Action:** Correct any errors described in the message log and retry the installation process. If the problem persists then contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

---

**Impact:** Other

**ODI-24004: ODI-24004: There are no supervisor accounts in the ODI repository with matching entries in the identity store. Please provide a suitable supervisor account.**

**Cause:** The ODI repository does not have any supervisor account that matches the entries in the identity store.

**Action:** Create a supervisor account in the ODI repository that matches an entry in the identity store.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-24005: ODI-24005: An error occurred while checking the status of the master repository.**

**Cause:** An unexpected error occurred.

**Action:** Check the exception to see if it gives details about the error and contact Oracle Support Services for further assistance.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-24006: ODI-24006: An error occurred while switching the authentication mode for the master repository.**

**Cause:** An unexpected error occurred.

**Action:** Check the exception to see if it gives details about the error and contact Oracle Support Services for further assistance.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-25001: ODI-25001: Unable to input a larger element**

**Cause:** The total length of all keywords exceeds the maximum length.

**Action:** Remove one or more of the keywords, or decrease their lengths.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-25002: ODI-25002: The end date cannot be before the start date.**

**Cause:** The end date is before the start date.

**Action:** Set the end date to be after the start date.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-25003: ODI-25003: Error while starting session**

---

**Cause:** An unexpected error occurred while starting the session.

**Action:** Check the error details for further information and contact Oracle Support Services for further assistance.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-25004: ODI-25004: Date Format Not Valid**

**Cause:** One of the Date fields is invalid. This may be the From or To Date.

**Action:** Click the button to the right of the field to invoke a dialog for entering a valid Time and Date.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-25005: ODI-25005: Incorrect date format . The format is {0}.**

**Cause:** The date format is incorrect.

**Action:** Use the format that is presented in the error message.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26001: ODI-26001: Boolean does not correspond to the Field Update Object Layer.**

**Cause:** The repository contained an invalid value of the Field Update property for a checkbox or radio group.

**Action:** Ensure the repository value is a boolean for checkbox or a valid action command for a radio group.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26002: ODI-26002: This object is referenced by another object. View the details for more information. You may also see where this object is used in the hierarchy.**

**Cause:** The specified object could not be used because it is referenced by another object.

**Action:** Remove references to this object. The "Used in" hierarchy may be useful in finding objects references.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26003: ODI-26003: This object cannot be removed: it is referenced by another object.**

---

**Cause:** The specified object could not be deleted because it is referenced by another object.

**Action:** Remove references to this object before deleting it. The "Used in" hierarchy may be useful in finding objects references.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26004: ODI-26004: Action denied:**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26005: ODI-26005: You are importing an object from another repository with the same identifier. It is forbidden.**

**Cause:** An object in the import file has an identifier which already exists in the repository.

**Action:** Consider manually changing the "com.sunopsis.dwg.dwgobj.SnpImportRep" object section of the import XML file to use a unique identifier.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26006: ODI-26006: The specified encryption key is invalid.**

**Cause:** The encryption key specified was found to be invalid during the decrypting phase.

**Action:** Ensure a valid encryption key is utilized.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26007: ODI-26007: KM or Procedure not encrypted. No decryption was performed.**

**Cause:** Decryption was requested for a non-encrypted KM or Procedure.

**Action:** Do not attempt to decrypt a non-encrypted KM or Procedure.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26008: ODI-26008: Scenario not encrypted. No decryption was performed.**

**Cause:** Decryption was requested for a non-encrypted Scenario.

**Action:** Do not attempt to decrypt a non-encrypted Scenario.

---

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26009: ODI-26009: Action not encrypted. No decryption was performed.**

**Cause:** Decryption was requested for a non-encrypted Action.

**Action:** Do not attempt to decrypt a non-encrypted Action.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26010: ODI-26010: Incompatible key or encrypted data.**

**Cause:** The data used for the key was invalid. It is likely the data decryption failed.

**Action:** Ensure the encrypted data is correct and the decryption key is correctly specified.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26011: ODI-26011: unable to find specified encryption API**

**Cause:** The specified cryptographic algorithm requested was not available in the environment.

**Action:** Ensure the environment can access the DES/ECB/PKCS5Padding algorithms and padding.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26012: ODI-26012: invalid encrypted data.**

**Cause:** The BASE64 content may be invalid or the zip file contents may be corrupted.

**Action:** Ensure the encrypted data is correct and the decryption key is correctly specified.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26013: ODI-26013: Your security parameters are insufficient to perform this action.**

**Cause:** The ODI user security parameters do not specifically permit the user to perform this particular action.

**Action:** Ensure this ODI user is granted the security access to perform this action.

**Level:** 32

**Type:** ERROR

---

**Impact:** Other

**ODI-26014: ODI-26014: The code of your {0} is already used by another {1}. Please give another code to save this {2}.**

**Cause:** The value entered for code must be unique for the entire work repository.

**Action:** Ensure the a unique value is entered.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26015: ODI-26015: You do not have sufficient privileges to perform this operation.**

**Cause:** The ODI user security parameters do not specifically permit the user to perform this particular operation.

**Action:** Ensure this ODI user is granted the security access to perform this operation.

**Level:** 32

**Type:** ERROR

**Impact:** Security

**ODI-26016: ODI-26016: The requested operation cannot succeed. The object no longer exists.**

**Cause:** The specified ODI object cannot be accessed because it no longer exists in the repository (it may have been deleted by another ODI user).

**Action:** Recreate the specified ODI object. Consider importing the object from a backup.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26017: ODI-26017: Error.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26018: ODI-26018: Key Error.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26019: ODI-26019: Action Denied.**

**Cause:**

---

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26020: ODI-26020: Retrieve method incorrect.**

**Cause:** Retrieve method is incorrect. Must be "set" or "get".

**Action:** Please change the retrieve method to "set" or "get".

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26021: ODI-26021: Object initialization denied.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26022: ODI-26022: Unrecoverable error during object saving, the editor will be closed.**

**Cause:** The object could not be saved. This is possibly due to a repository connection error, or inconsistent data values supplied.

**Action:** Ensure the repository database is available and the data values supplied are valid.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26023: ODI-26023: Cannot create object.**

**Cause:** An unexpected error occurred during the object creation process.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26024: ODI-26024: Cannot stop update operation.**

**Cause:** An unexpected error occurred during the update operation.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26025: ODI-26025: Display Initialization denied.**

**Cause:** An unexpected error occurred during the display initialization process.

---

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26026: ODI-26026: Cannot refresh.**

**Cause:** An unexpected error occurred during the refresh process.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26027: ODI-26027: Security not set for the instance. The instance will not be added to the tree.**

**Cause:** Instance security permissions "By repository" were chosen but a concrete repository is not specified.

**Action:** Ensure a repository is specified.

**Level:** 32

**Type:** ERROR

**Impact:** Security

**ODI-26028: ODI-26028: Cannot save your modifications.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26029: ODI-26029: Could not deploy the datasource automatically.**

**Cause:** Weblogic Administration server is not up and running, the server connection parameters are wrong.

**Action:** Please check Weblogic Administration server connection parameters and the server state.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26030: ODI-26030: The new password does not meet the password policy. Your change could not be saved.**

**Cause:** The new password does not meet the password policy.

**Action:** Please verify that the new password meets the password policy (go to the "Security Navigator -> Password Policy...").

**Level:** 32

**Type:** ERROR



---

**Impact:** Other

**ODI-26031: ODI-26031: You may not delete work repository {0} because you are connected to it. To delete this repository, reconnect to a different work repository or use a master repository only connection.**

**Cause:** Deletion of a work repository which is currently connected is not supported.

**Action:** Disconnect from the repository and then connect utilizing a Master Repository Only connection or a different work repository before attempting to delete the specified work repository.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26032: ODI-26032: This object was modified by {0} on {1} at {2}. Your changes cannot be saved.**

**Cause:** The object was changed in the repository after the editor was opened for this object.

**Action:** Close the editor without saving changes. Open the editor again and reapply the edits and save. Note: consider using the lock object facility to disallow current modifications to an object.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26033: ODI-26033: You cannot edit this object because it is locked by another user ({0}). You can only view it.**

**Cause:** The ODI object opened for editing is locked by another user. Other ODI users can only view such objects.

**Action:** Try to edit the object later.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26034: ODI-26034: An error occurred while deleting executions.**

**Cause:** The specified executions could not be deleted. This is possibly caused by the repository database connection problems.

**Action:** Retry to delete the executions. If problem persists, contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26035: ODI-26035: Error.**

**Cause:**

**Action:**

**Level:** 32

---

**Type:** ERROR

**Impact:** Other

**ODI-26036: ODI-26036: Error while encrypting.**

**Cause:** A general error occurred during the encrypting process, possibly caused by caused by repository database access problems, lack of security permissions, or encryption engine failures,

**Action:** Retry the encrypt action again.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26037: ODI-26037: Encryption key is not valid.**

**Cause:** An invalid encryption key was entered causing an encryption engine failure.

**Action:** Enter a valid encryption key and retry the action.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26038: ODI-26038: Unable to execute, the selected Logical Agent is not associated to a Physical Agent in the desired Context.**

**Cause:** A Logical Agent was not associated with this Physical Agent in this Context.

**Action:** Ensure a valid "Logical Agent - Physical Agent" association exists in the desired Context.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26039: ODI-26039: Connection failed.**

**Cause:** The attempt to connect to the repository failed. This may be due to one or more of the following: invalid connection parameters specified, database problems, network problems.

**Action:** Ensure the repository database is available and accessible and the repository connection parameters are correct.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26040: ODI-26040: error while updating**

**Cause:** Failed to update the ODI logins file: snps\_login\_work.xml.

**Action:** Ensure write-access is granted to the ODI logins file: snps\_login\_work.xml.

**Level:** 32

**Type:** ERROR

---

**Impact:** Other

**ODI-26041: ODI-26041: Error while attempting to get FieldData from ObjectDisplay.**

**Cause:** An unexpected error occurred obtaining FieldData from ObjectDisplay.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26042: ODI-26042: Error while attempting to set FieldUpdate from ObjectUpdate.**

**Cause:** An unexpected error occurred updating FieldUpdate from ObjectUpdate.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26043: ODI-26043: Window closing cancelled by the User.**

**Cause:** User asked to close the parent window where child lines were modified.

**Action:** No action performed on that.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26044: ODI-26044: Host Variable Not Found.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26045: ODI-26045: Unable to perform the drop operation.**

**Cause:** Dropped entity is invalid.

**Action:** Check whether the dropped entity is valid and perform the drag-n-drop action again.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26046: ODI-26046: MethodGetter was not found**

**Cause:** An unexpected error occurred obtaining the getter method.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

---

**Impact:** Other

**ODI-26047: ODI-26047: Object on method setObjectDisplay(Object pObjectDisplay) is not an array.**

**Cause:** This is caused by programmatic error.

**Action:** ODI users should normally never see this message.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26048: ODI-26048: Object on method setObjectDisplay(Object pObjectDisplay) is not a vector.**

**Cause:** This is caused by programmatic error.

**Action:** ODI users should normally never see this message.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26049: ODI-26049: Parameters not valid.**

**Cause:** An unexpected error occurred due to an invalid parameter value.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26050: ODI-26050: Master repository not installed on this connection.**

**Cause:** This is caused by programmatic error.

**Action:** ODI users should normally never see this message.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26051: ODI-26051: XML Export Error.**

**Cause:** An error occurred during the creation of the XML Export file.

**Action:** Ensure the repository is accessible and the export file and its directory are writable.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26052: ODI-26052: XML Import Error.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

---

**Impact:** Other

**ODI-26053: ODI-26053: An error occurred during initialization.**

**Cause:** Initialization failed possibly due a repository access failure or insufficient ODI security permissions.

**Action:** Ensure the repository database is available, and the ODI user security permissions permit connection.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26054: ODI-26054: Page not available.**

**Cause:** The selected page number was invalid.

**Action:** Ensure the page number entered is greater than 0 and less than the total number of pages.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26055: ODI-26055: The password does volates the following rule: "{0}". Select another password.**

**Cause:** The password supplied was invalid.

**Action:** Enter a valid password.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26056: ODI-26056: Error while disconnecting.**

**Cause:** This error is ocured while closing the repository database connection after "Test query" action completed.

**Action:** This error may be ignored.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26057: ODI-26057: Unable to connect the agent. The agent is probably not started.**

**Cause:** The connection request to the agent failed.

**Action:** Ensure the agent is started and available. Ensure the connection information is valid.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26058: ODI-26058: Unable to connect the agent. The agent URL cannot be found.**

---

**Cause:** The connection request to the agent failed using the given URL.

**Action:** Ensure the agent is started and available. Ensure the connection URL information is valid.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26059: ODI-26059: Object on method setObjectDisplay(Object pObjectDisplay) is not a List.**

**Cause:** An unexpected error occurred setting ObjectData.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26060: ODI-26060: The Password and Confirmation Password do not match.**

**Cause:** The values entered for Password and Confirmation Password did not match.

**Action:** Enter the same value for Password and Confirmation Password.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26061: ODI-26061: The minimum password length is {0} characters.**

**Cause:** The length of the Password entered is less than specified in password policy rule.

**Action:** Enter a Password whose length is greater than or equal to the specified minimum length.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26062: ODI-26062: The password does violates the following rule: "{0}". Select another password.**

**Cause:** The password supplied was invalid.

**Action:** Enter a valid password.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26063: ODI-26063: Invalid password.**

**Cause:** The password supplied was invalid.

**Action:** Enter a valid password.

**Level:** 32

---

**Type:** ERROR

**Impact:** Other

**ODI-26064: ODI-26064: Error while exporting.**

**Cause:** An error occurred during the creation of the Export file.

**Action:** Ensure the repository is accessible and the export file and its directory are writable.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26065: ODI-26065: You must specify all the options.**

**Cause:** This is caused by programmatic error.

**Action:** ODI users should normally never see this message.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26066: ODI-26066: An unexpected error has occurred.**

**Cause:** An unexpected error occurred this process.

**Action:** Retry action. If problem persists then contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26067: ODI-26067: mandatory field "Java charset" not entered**

**Cause:** A value for the "Java character set" field was not entered.

**Action:** Enter a value for the "Java character set" field.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26068: ODI-26068: unable to load export list in the module: {0}**

**Cause:** The contents of the export file list was not formatted correctly.

**Action:** Correct the format of the export list file specified.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26069: ODI-26069: The specified export directory does not exist.**

**Cause:** The specified export directory is invalid.

**Action:** Ensure the specified export directory exists and is writable.

**Level:** 32

**Type:** ERROR

---

**Impact:** Other

**ODI-26070: ODI-26070: The Open Tool class name must not begin with "Snp" or "Odi".**

**Cause:** The Open Tool class name begins with "Snp" or "Odi".

**Action:** Ensure the Open Tool class name does not begin with "Snp" or "Odi".

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26071: ODI-26071: Open Tool not activated. Your Open Tool references a class which not found.**

**Cause:** The class name specified in this Open Tool was not found.

**Action:** Ensure the Open Tool class name specified is valid and available in the class path.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26072: ODI-26072: Your Open Tool has been installed. You can now use it in a procedure or package.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26073: ODI-26073: Could not activate Open Tool. Check that it is in the "oracledi/userlib" directory.**

**Cause:** The Open Tool references a class which was not found.

**Action:** Ensure the Open Tool class exists in the "oracledi/userlib" directory.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26074: ODI-26074: Policy "Name" is a mandatory field.**

**Cause:** A value for the Policy "Name" field value was not entered.

**Action:** Enter a value for the Policy "Name" field.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26075: ODI-26075: Policy "Name" must be unique.**

**Cause:** A Policy with the same name already exists.

**Action:** Enter a unique value in Policy "Name" field.



---

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26076: ODI-26076: You do not have enough memory to generate this report. Increase the maximum Java heap size value (-Xmx).**

**Cause:** There was not enough memory allocated to generate the report.

**Action:** Increase the maximum Java heap size value by using the "-Xmx" JVM option.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26077: ODI-26077: Target file name is not specified.**

**Cause:** The Target file name is mandatory and was not specified.

**Action:** Enter a value for the target file name.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26078: ODI-26078: Error while creating the version**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26079: ODI-26079: Version already exists, versioning aborted.**

**Cause:** A version with the specified version number already exists.

**Action:** Enter a unique version number.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26080: ODI-26080: Unable to delete version {0} for {1} {2}. It is referenced by solution {3}**

**Cause:** Deletion of a version of an object referenced by a Solution was attempted.

**Action:** Delete the solution referencing the object version. Then retry deleting the object version.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26081: ODI-26081: Unable to delete version {0} for {1} {2}. It is referenced by version {3} of solution {4}**

---

**Cause:**  
**Action:**  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other

**ODI-26082: ODI-26082: No difference found**  
**Cause:**  
**Action:**  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other

**ODI-26083: ODI-26083: No difference found.**  
**Cause:**  
**Action:**  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other

**ODI-26084: ODI-26084: Could not compare versions of different objects.**  
**Cause:** Objects of different types were selected for comparison.  
**Action:** Select objects of the same type before performing comparison.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other

**ODI-26085: ODI-26085: You cannot restore several versions of the same object.**  
**Cause:** Multiple versions were selected for restoring.  
**Action:** Select a single version when performing this action.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other

**ODI-26086: ODI-26086: You cannot select more than one version at the same time.**  
**Cause:** Multiple version were selected for this action.  
**Action:** Select a single version when performing this action.  
**Level:** 32  
**Type:** ERROR  
**Impact:** Other

**ODI-26087: ODI-26087: You must select a version.**  
**Cause:** A version was not selected.  
**Action:** Select a version before performing this action.

---

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26088: ODI-26088: You must select the version to restore.**

**Cause:** A version to restore was not selected.

**Action:** Select a version to restore.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26089: ODI-26089: This object is currently locked by user: {0}. Version restoration cancelled.**

**Cause:** The object selected for restoration was locked by another user.

**Action:** Ensure the selected object is not locked by another user before retrying the operation.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26090: ODI-26090: Object version list is empty.**

**Cause:** The object selected was not versioned.

**Action:** Select a versioned object before retrying the operation.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26091: ODI-26091: An array with an invalid size was passed to SnpsObjectTableColumnTextIntrospectMapper.createMapFromArrayOfArrays.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26092: ODI-26092: Table Model must have at least one Column.**

**Cause:** The Model for this Table did not contain any Columns.

**Action:** Add at least one Column to the Table's Model.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26093: ODI-26093: Unable to open window.**

**Cause:**

**Action:**

---

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26094: ODI-26094: Your license does not allow Changed Data Capture operations.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26095: ODI-26095: This object is locked by {0}. You cannot edit it unless it is unlocked.**

**Cause:** Object could not be opened for write access because it was already locked by another user.

**Action:** Ensure the selected object is not locked by another user before retrying the operation.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26096: ODI-26096: Replacement of object failed.**

**Cause:** The file specified did not contain correctly formed XML.

**Action:** Ensure the XML in the specified file is valid before retrying the operation.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26097: ODI-26097: Replace failed due to an SQL exception.**

**Cause:** The file used to replace this object is not a valid XML format.

**Action:** Select a valid XML file format before performing this replace object action.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26098: ODI-26098: You must specify an Export Path or File.**

**Cause:** Either the Export Path or File was not specified.

**Action:** Specify a value for either the Export Path or File.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26099: ODI-26099: You don't have the appropriate license to use this KM**

**Cause:**

---

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26100: ODI-26100: You don't have the appropriate privileges on Step objects.**

**Cause:** Package Steps operation failed due to insufficient ODI security permissions.

**Action:** Ensure the ODI user security permissions are correct for the Package Steps object.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26101: ODI-26101: The Data Check cannot be performed. A CKM is not selected on the Model.**

**Cause:** No CKM was assigned to the Model.

**Action:** Enter a CKM for the Model before performing the Data Check. Consider using the Model editor to make this entry.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26102: ODI-26102: The Service cannot be generated. A Service is not selected on the Model.**

**Cause:** No Service was assigned to the Model.

**Action:** Enter a Service for the Model before performing Generate Service. Consider using the Model editor to make entry.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26103: ODI-26103: You must specify a connection parameter**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26104: ODI-26104: You must specify a query parameter**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

---

**Impact:** Other

**ODI-26105: ODI-26105: Test failed**

**Cause:** The value of Schema, Table, Column or Filter was invalid.

**Action:** Ensure the Schema, Table, Column and Filter are valid. Consult the details for additional information.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26106: ODI-26106: Decryption failed. Data has been restored.**

**Cause:** The Decryption process failed.

**Action:** Consult the details for additional information.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26107: ODI-26107: Cannot find this {0} icon**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26108: ODI-26108: The specified path is not valid.**

**Cause:** The specified path was invalid or was not found on the file system.

**Action:** Ensure a valid file system path is entered.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26109: ODI-26109: Error while reading the search criteria. Invalid file**

**Cause:** The selected file did not contain search criteria in a valid format.

**Action:** Ensure the selected file is one exported from the ODI search UI and contains correctly formatted search criteria information.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26110: ODI-26110: An error occurred while saving.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

---

**Impact:** Other

**ODI-26111: ODI-26111: Error while accessing the file**

**Cause:** The specified file could not be opened.

**Action:** Ensure the specified file exists and is accessible.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26112: ODI-26112: Error while performing the search**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26113: ODI-26113: XML parser configuration error**

**Cause:** The selected file is not a valid search criteria file format.

**Action:** Select a valid search criteria file exported from the ODI search UI.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26114: ODI-26114: Host cannot be empty.**

**Cause:** The Host field is mandatory and was not specified.

**Action:** Enter a valid Host name.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26115: ODI-26115: Port number must be an integer between 1024 and 65535.**

**Cause:** The value for Port Number was not valid.

**Action:** Enter a valid integer value between 1024 and 65535 for Port Number.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26116: ODI-26116: User cannot be empty.**

**Cause:** The User field is mandatory and was not supplied.

**Action:** Enter a valid User Name.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26117: ODI-26117: Connection failed. Reason:**

---

**Cause:** Could not connect to a repository with the specified connection details.  
**Action:** Ensure the repository database is available and valid connection details are supplied.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26118: ODI-26118: External password storage connection test failed.**

**Cause:** Could not connect to the external password storage with the specified connection details.

**Action:** Ensure the external password storage is available and valid connection details are supplied.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26119: ODI-26119: Exception when computing the value**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26120: ODI-26120: Fields compared are not the same**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26121: ODI-26121: Error while exploring version**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26122: ODI-26122: Exception when getting the children list**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other



---

**ODI-26123: ODI-26123: Cannot connect to the repository with the provided login information.**

**Cause:** Could not connect to a repository with the specified connection details.

**Action:** Ensure the repository database is available and valid connection details are supplied.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26124: ODI-26124: Exception during connection to the repository with the provided login information:**

**Cause:** Could not connect to a repository with the specified connection details.

**Action:** Ensure the repository database is available and valid connection details are supplied.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26125: ODI-26125: The configured external password storage is not accessible. Instead, use the Password Storage Switch service to change the configuration.**

**Cause:** Could not connect to the external password storage with the specified connection details.

**Action:** Ensure the external password storage is available and valid connection details are supplied. Consider using the Password Storage Switch service to change the configuration.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26126: ODI-26126: Error while opening window.**

**Cause:** An unexpected error occurred while opening window.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26127: ODI-26127: The selected master repository configured to use internal password storage. Recovery is possible only for external storages.**

**Cause:** Recovery was attempted for a master repository configured to use internal password storage.

**Action:** Select a master repository not configured to use internal password storage.

**Level:** 32

**Type:** ERROR

**Impact:** Other

---

**ODI-26128: ODI-26128: Unable to open Editor**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26129: ODI-26129: Unable to open Editor: Technology could not be opened twice**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26130: ODI-26130: Could not connect to repository**

**Cause:** Could not connect to a repository with the specified connection details.

**Action:** Ensure the repository database is available and valid connection details are supplied.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26131: ODI-26131: Specify Import Path**

**Cause:** A value for Import Path is a mandatory and it was not supplied.

**Action:** Enter the correct value for the Import Path.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26132: ODI-26132: Repository id {0} or Repository name {1} is already used in your master repository.**

**Cause:** The ID or Name specified for the master repository were already used.

**Action:** Enter valid unique values for Repository ID and Repository name.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26134: ODI-26134: Invalid number format for port number.**

**Cause:** The value specified for Port Number was not in a valid format and number range.

**Action:** Enter a valid Port Number. See SQL\*Net documentation for additional information regarding format and range.

**Level:** 32

---

**Type:** ERROR

**Impact:** Other

**ODI-26135: ODI-26135: The Network Adapter could not establish the connection.**

**Cause:** Connection via the Network Adapter could not be established.

**Action:** Ensure the network resource is available and the connection details in the Network Adapter are correct..

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26136: ODI-26136: The specified character set is not supported.**

**Cause:** The specified character set was not supported.

**Action:** Select a supported character set.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26137: ODI-26137: The context or type are incorrect.**

**Cause:** The selected ODI context is invalid: it was probably removed from the repository database.

**Action:** Reopen Execution dialog again so that the list of ODI contexts will be reloaded.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26150: ODI-26150: Incorrect Context.**

**Cause:** A valid Context was not specified.

**Action:** Select a Context from the list. If none are available then create one from the Topology Navigator.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26151: ODI-26151: Problem encountered when determining the context.**

**Cause:** A valid Context was not specified.

**Action:** Select a Context from the list. If none are available then create one from the Topology Navigator.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26152: ODI-26152: Error while drag & dropping. Read the details.**

**Cause:**

**Action:**

---

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26153: ODI-26153: Connection failed; JDBC Error**

**Cause:** An unexpected JDBC error was encountered during the connection process.

**Action:** Ensure the resource referenced is available and the connection information is correct.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26154: ODI-26154: Context Error.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26155: ODI-26155: No Master Repository on this connection**

**Cause:** A connection to the Master Repository could not be established.

**Action:** Ensure the Master Repository is available and valid connection details are provided.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26156: ODI-26156: Designer cannot connect to an Execution repository. The operation will be canceled.**

**Cause:** Unable to establish a connection to the Execution repository.

**Action:** Ensure the Execution repository is available and the connection details are correct.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26157: ODI-26157: Connection Error**

**Cause:** A connection to the Master Repository could not be established.

**Action:** Ensure the Master Repository is available and valid connection details are provided.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26158: ODI-26158: Work Repository Attachment Error**

---

**Cause:** A connection to the Work Repository could not be established.

**Action:** Ensure the Work Repository is available and valid connection details are provided.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26159: ODI-26159: Error while creating Work Repository**

**Cause:** An unexpected error occurred while creating the Work Repository.

**Action:** Correct any issues described in the error details.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26160: ODI-26160: URL not referenced in the list.**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26161: ODI-26161: File Not Found**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26162: ODI-26162: Connection failure**

**Cause:** A connection to the repository could not be established.

**Action:** Ensure the repository is available and valid connection details are provided.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26163: ODI-26163: Access Denied**

**Cause:** A connection to the repository could not be established because of insufficient user privilege.

**Action:** Ensure the ODI user has sufficient privilege to connect to the specified repository.

**Level:** 32

**Type:** ERROR

**Impact:** Other

---

**ODI-26164: ODI-26164: The reverse cannot be executed. Your Model will be created.**

**Cause:** The specified technology or driver did not support standard reverse-engineering.

**Action:** Ensure the technology or driver supports standard reverse-engineering. Otherwise choose Customized Reverse and select an appropriate RKM for the technology.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26165: ODI-26165: This driver has no match in the URL list**

**Cause:**

**Action:**

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26166: ODI-26166: The template was not generated: {0}**

**Cause:** The WLS Template could not be generated.

**Action:** Correct any errors identified in the error log and retry the operation.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-26167: ODI-26167: File System Error: {0}**

**Cause:** Creation of the WLS Template file failed due to an error detected by the file system.

**Action:** Correct any errors identified in the error log. Ensure the file system location is accessible and retry the operation.

**Level:** 32

**Type:** ERROR

**Impact:** Other

**ODI-30094: Log files can only be imported in SYNONYM INSERT MODE**

**Cause:** The value of parameter -IMPORT\_MODE is invalid for this type of object.

**Action:** Modify the value of parameter -IMPORT\_MODE to SYNONYM\_INSERT

**Level:** 32

**Type:** ERROR

**Impact:** Other

---

## ODL-52001 to ODL-52501

**ODL-52001: deleting log file: {0}, size: {1} bytes**

**Cause:** A log file was deleted because of the rules defined in the current configuration.

**Action:** This is an information message, no action is needed.

**Level:** 16

**Type:** NOTIFICATION

**Impact:** Logging

**ODL-52002: invalid value for parameter {0}: {1}. Value must be greater than zero.**

**Cause:** An invalid value was assigned to a numeric parameter that require a positive value.

**Action:** Use a value that is greater than zero value for the parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52003: invalid value for parameter maxLogSize: {0}. Value must be greater than the value of maxFileSize ({1}).**

**Cause:** The value used for the maxLogSize parameter is smaller than the value used for the maxFileSize parameter, which is not valid.

**Action:** Enter a value for the maxLogSize parameter that is greater than the value of the maxFileSize parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52004: invalid encoding: {0}**

**Cause:** The value used for encoding parameter is not valid.

**Action:** Enter a valid encoding value.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52006: Path cannot be null.**

---

**Cause:** A null value was used for the log file path.

**Action:** Enter a non-null value for the path.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52007: The log path is not a directory: {0}.**

**Cause:** The value used for the log path is not a directory. Some log types require that the log path be a directory, not a file, because the log file name is fixed.

**Action:** Enter a directory path instead of a file path.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52008: unable to create log directory: {0}**

**Cause:** One or more directories that were used in the log path could not be created.

**Action:** Make sure that the process has permission to create the directories, or enter a different path. It may also be possible to create the directories manually.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52009: The log directory is not writable: {0}.**

**Cause:** The process could not write to the log directory.

**Action:** Make sure that the process has permission to write to the log directory, or enter a different path.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52010: no permission to access log directory: {0}**

**Cause:** The process could not access the log directory.

**Action:** Make sure that the process has permission to access the log directory, or enter a different path.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52011: attempting to operate on a closed LogWriter**

**Cause:** There was an attempt to perform an operation on a log writer that is already closed.

**Action:** This is possible a programming error. Contact Oracle Support Services. If the problem occurs during process shut down, it is possible that some component is attempting to log a message after the logging system has already shut down.



---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ODL-52012: attempting to write to a closed LogWriter**

**Cause:** There was an attempt to write a message to a log writer that is already closed.

**Action:** This is possible a programming error. Contact Oracle Support Services. If the problem occurs during process shut down, it is possible that some component is attempting to log a message after the logging system has already shut down.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ODL-52013: attempting to flush a closed LogWriter.**

**Cause:** There was an attempt to flush a log writer that is already closed.

**Action:** This is possible a programming error. Contact Oracle Support Services. If the problem occurs during process shut down, it is possible that some component is attempting to log a message after the logging system has already shut down.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ODL-52014: Maximum log size is reached.**

**Cause:** The maximum size for the log defined in the configuration was reached and the current configuration does not enable automated removal of older log messages.

**Action:** Review the logging configuration. It may be necessary to increase the maxLogSize parameter, or enable a policy for the automatic removal of older messages.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52015: unable to delete old archived file**

**Cause:** There was an attempt to delete an old log file, but the file could not be deleted.

**Action:** Check that the process has permission to delete the log file.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52016: failure to rotate log file: {0}**

**Cause:** There was an attempt to rename a log file, but the operation failed.

**Action:** Check that the process has permission to rename files.

**Level:** 1

---

**Type:** ERROR

**Impact:** Logging

**ODL-52017: out of log file names**

**Cause:** There was an attempt to rename a log file, but there are no more names that can be used.

**Action:** Remove some or all of the archived files.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52018: unable to write to log "{0}": {1}**

**Cause:** There was an error when writing messages to a log file.

**Action:** See the error message for the root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52019: unable to close log "{0}": {1}**

**Cause:** There was an error when closing a log file.

**Action:** See the error message for the root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52020: failed to get a lock on file "{0}" after {1} milliseconds**

**Cause:** A log file lock could not be acquired within the specified time period, and the log write operation has time-out.

**Action:** Check that other processes are not holding a lock to the log file.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52021: thread interrupted while waiting to lock file "{0}"**

**Cause:** The thread was interrupted while waiting to acquire a lock on a lock file.

**Action:** Check that other processes are not holding a lock to the log file.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52030: invalid property name: {0}**

**Cause:** An invalid property name was used in the logging configuration.

**Action:** Review the configuration and enter a valid property name.

**Level:** 1

---

**Type:** ERROR

**Impact:** Logging

**ODL-52031: required property "{0}" is not found**

**Cause:** A required property was not present in the configuration of a log handler.

**Action:** Review the configuration and add the required property.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52032: invalid format: {0}. Valid formats are: {1}.**

**Cause:** An invalid value for the 'format' property was used in the configuration of an ODLHandler.

**Action:** Review the configuration and add a valid value for the format property.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52033: invalid value for property {0}: {1}.**

**Cause:** An invalid value for used for an ODLHandler property.

**Action:** Review the configuration and add a valid value for the property.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52034: Configuration is invalid: {0} cannot be less than {1}.**

**Cause:** An invalid value for used for a size property in an ODLHandler configuration.

**Action:** Review the configuration and make sure that the value of the 'maxFileSize' property is not greater than the value of the 'maxLogSize' property.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52035: failure to create ODLHandler: {0}**

**Cause:** An ODLHandler instance could not be created.

**Action:** Check the error message for the root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52036: invalid level: {0}. Check spelling and verify that the value is a valid ODL or Java level.**

**Cause:** An invalid level was used in the configuration of a logger or handler.

**Action:** Review the configuration and enter a valid level.

---

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52040: failure to initialize class {0}: property {1} must be defined.**

**Cause:** A required system property was not defined.

**Action:** Review the process configuration and make sure that the required system property is defined.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52041: Use of {0} in logging configuration is deprecated; replacing it with {1}. (File: {2}).**

**Cause:** A deprecated property was used in the logging configuration.

**Action:** Review the logging configuration and consider replacing the deprecated property. While the configuration may be valid, use of deprecated properties should be avoided.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ODL-52042: undefined property: {0}.**

**Cause:** An undefined property was used in the logging configuration.

**Action:** Review the logging and process configuration and either replace the invalid property in the logging configuration, or define a value for the property.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52043: expecting one element of type "{0}"**

**Cause:** The logging configuration contained more than one XML element of a given type, when only one was expected.

**Action:** Review the logging configuration and remove the extra XML elements.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52044: cannot find handler: {0}**

**Cause:** The logging configuration assigned a handler to one or more loggers, but the handler was not defined.

**Action:** Review the logging configuration and either add the missing handler, or remove any references to the handler.

**Level:** 1

**Type:** ERROR

---

**Impact:** Logging

**ODL-52045: invalid class: {0}**

**Cause:** The logging configuration defined an invalid class for a handler.

**Action:** Review the logging configuration and make sure that the handler class is valid. The handler class must be either a subclass of `java.util.logging.Handler`, or implement the `oracle.core.ojdl.logging.HandlerFactory` interface.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52046: cannot find class: {0}**

**Cause:** The logging configuration defined a handler, filter, or error manager class, but that class could not be found.

**Action:** Review the logging and process configuration and make sure that the class is available in the system classpath, or that the class is visible to the classloader that loads the ODL configuration classes.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52047: cannot load or link class "{0}": {1}**

**Cause:** The logging configuration defined a handler, filter, or error manager class, but that class could not be loaded due to a linkage error.

**Action:** Review the logging and process configuration and make sure that the class is available in the system classpath, or that the class is visible to the classloader that loads the ODL configuration classes, or that the correct version of the class is being used..

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52048: Class "{0}" is not of expected type "{1}".**

**Cause:** The logging configuration defined a handler, filter, or error manager class, but that class is not a handler, filter or error manager instance.

**Action:** Review the logging and process configuration and make sure that the class is of the correct type.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52049: cannot create instance of class "{0}": {1}**

**Cause:** The logging configuration defined a handler, filter, or error manager class, but an instance of that class could not be created.

**Action:** Review the error message for the root cause.

**Level:** 1

**Type:** ERROR

---

**Impact:** Logging

**ODL-52050: unable to process file "{0}", XML parse exception (line: {1}, column: {2}): {3}**

**Cause:** The logging configuration could not be processed due to an XML error in the configuration file.

**Action:** Review the error message for a description of the XML error, and correct the problem in the configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52051: unable to process file "{0}"; exception: {1}**

**Cause:** The logging configuration could not be processed due to a unexpected XML parser error.

**Action:** Review the error message for a description of the root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52052: unable to find resource: {0}**

**Cause:** The logging configuration could not be processed due to a missing XML schema or DTD.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ODL-52053: unable to create handler instance using class "{0}"; exception: {1}**

**Cause:** The creation of a handler instance failed because the handler factory threw an exception.

**Action:** Review the error message for the root cause.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ODL-52054: The logger "{0}" is already defined.**

**Cause:** There was an attempt to add a new logger to the configuration file, but the logger is already defined.

**Action:** Verify that the logger name is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52055: The handler "{0}" is already defined.**

---

**Cause:** There was an attempt to add a new handler to the configuration file, but a handler is already defined.

**Action:** Verify that the handler name is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52056: The logger "{0}" is not defined.**

**Cause:** There was an attempt to access a logger in the logging configuration but the logger is not defined.

**Action:** Verify if the logger name is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52057: The handler "{0}" is not defined.**

**Cause:** There was an attempt to access a handler in the logging configuration but the handler is not defined.

**Action:** Verify if the handler name is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52058: The handler "{0}" cannot be removed because it is being used by logger "{1}".**

**Cause:** There was an attempt to remove a handler from the logging configuration, but the handler could not be removed because it is being used by a logger.

**Action:** Verify that the handler name is correct, or remove the handler from all the loggers first before attempting to remove the handler.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52059: The logger "{0}" already has handler "{1}".**

**Cause:** There was an attempt to add a handler to a logger but the logger already has the given handler.

**Action:** Verify if the logger and handler names are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52060: The logger "{0}" does not have handler "{1}".**

**Cause:** There was an attempt to remove a handler from a logger, but the logger does not contain the given handler.

**Action:** Verify if the logger and handler names are correct.

---

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52061: The handler "{0}" does not have property "{1}".**

**Cause:** There was an attempt to remove a property from a handler, but the handler does not have a property with the given name.

**Action:** Verify if the handler and property are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52062: Illegal value for "{0}": {1}**

**Cause:** There was an attempt to set a property for a handler or logger, but the value of the property is not valid.

**Action:** Verify if the handler or loggers properties are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52063: Unable to load logging configuration from "{0}"; exception: {1}**

**Cause:** There was an error while loading the logging configuration file.

**Action:** Review the error message for the root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52064: The handler "{0}" is already defined in the target logging configuration document.**

**Cause:** There was an attempt to add a handler to a logging configuration file, but a handler with the given name already exists in the target file.

**Action:** Review the definition of the new handler.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52065: The logger "{0}" or a descendant is already defined in the target logging configuration document.**

**Cause:** There was an attempt to add a logger to a logging configuration file, but the logger or one of its descendants is already defined in target logging configuration.

**Action:** Review the definition of the new logger.

**Level:** 1

**Type:** ERROR

**Impact:** Logging



---

**ODL-52081: unable to read logging configuration from file "{0}"; exception: {1}**

**Cause:** There was an error reading the logging configuration from the given file.

**Action:** Review the error message for the root cause.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ODL-52083: unable to register log dump; exception: {0}**

**Cause:** There was an error registering the log dump with the FMW Diagnostics Framework.

**Action:** Review the error message for the root cause. The system may still work, but the log dump will not be available.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**ODL-52084: unable to initialize ODL; exception: {0}**

**Cause:** There was an error initializing Oracle Diagnostic Logging (ODL).

**Action:** Review the error message for the root cause. Oracle Diagnostic Logging is not properly configured in this system.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**ODL-52086: unable to reload logging configuration from file "{0}"; exception: {1}**

**Cause:** There was an error reloading the logging configuration from the given file.

**Action:** Review the error message for the root cause.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ODL-52087: suspicious logging configuration reload. The original configuration was read from file "{0}", but the new configuration is being read from "{1}".**

**Cause:** The logging configuration is being reloaded, but the configuration file is different from the configuration file used for the initial configuration.

**Action:** This is probably an error, there should only be one configuration file.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ODL-52088: The java.util.logging configuration was reloaded.**

**Cause:** The java.util.logging configuration was reloaded, probably via the invocation of LogManager.readConfiguration.

**Action:** The java.util.logging configuration should not be reloaded programmatically, as this can override the ODL configuration.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**ODL-52501: Unable to get OPMN connection for target "{0}"; check that the instance and component names are valid and that OPMN is running.**

**Cause:** There was an attempt to invoke an operation on a OPMN managed target, but a connection to that target could not be created.

**Action:** Check the target argument and make sure that the instance and component names are valid, and that OPMN is running.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

---

## ODSM-00001 to ODSM-01007

**ODSM-00001: ODSM disconnected from OID server as the server is stopped.**

**Cause:** OID server is stopped or ODSM is unable to contact OID server.

**Action:** Ensure that OID server is up and running. Refer OID server's log file to find out why it was stopped.

**Level:** 1

**Type:** ERROR

**Impact:** ODSM

**ODSM-00002: Invalid Credentials.**

**Cause:** Wrong username or password was provided.

**Action:** Provide valid username or password.

**Level:** 1

**Type:** ERROR

**Impact:** ODSM

**ODSM-00003: Bind failed.**

**Cause:** It may be due to wrong host name or port number or OID server may not be up. Refer exception for more details.

**Action:** Provide valid host name and port number and ensure that OID server is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** ODSM

**ODSM-00004: ODSM disconnected from OID server due to time out error.**

**Cause:** ODSM to OID connection was idle for long time.

**Action:** ODSM will reestablish the connection. No action needed from the user.

**Level:** 1

**Type:** ERROR

**Impact:** ODSM

**ODSM-00005: Size limit exceeded.**

**Cause:** The number of search entries exceeds the size limit setting.

---

**Action:** Use the "Advanced Search" or "Configure Search Filter" options to retrieve the specific entries.

**Level:** 1

**Type:** ERROR

**Impact:** ODSM

**ODSM-00006: Unable to load password policy entries.**

**Cause:** Error occurred while retrieving password policy entries from OID server.

**Action:** Refer exception and OID server's log file to take further action.

**Level:** 1

**Type:** ERROR

**Impact:** ODSM

**ODSM-00007: SSL connection failed.**

**Cause:** You may not have provided valid SSL port number and host. Or ODSM may not be able to read its trust store or may not have access to Credential Store Framework. Refer exception to find actual cause.

**Action:** Ensure that you have provided valid SSL port number and host details. Ensure that ODSM has access to Credential Store Framework and is able to read its trust store.

**Level:** 1

**Type:** ERROR

**Impact:** ODSM

**ODSM-00008: Certificate validation failed.**

**Cause:** Certificate presented by the server is invalid. Refer exception for more details.

**Action:** Connect to a server that is authentic and has valid certificate.

**Level:** 1

**Type:** ERROR

**Impact:** ODSM

**ODSM-00009: LDAP operation has failed.**

**Cause:** OID server is unwilling to perform this operation. In case ODSM is connected to OID server in High Availability mode and if OID to which ODSM is connected has gone down, this error can occur.

**Action:** Refer OID server's log file to take appropriate action. In later case, ODSM will reestablish connection to other available OID server and no action is required from the user.

**Level:** 1

**Type:** ERROR

**Impact:** ODSM

**ODSM-00010: Unable to load password verifier entries.**

**Cause:** Error occurred while retrieving password verifier entries from OID server.

**Action:** Refer exception and OID server's log file to take further action.

---

**Level:** 1

**Type:** ERROR

**Impact:** ODSM

**ODSM-00011: Unable to load access control policies.**

**Cause:** Error occurred while searching OID for access control policies.

**Action:** Refer exception and OID server's log file to take further action.

**Level:** 1

**Type:** ERROR

**Impact:** ODSM

**ODSM-00012: Posn: -1, Size: 0.**

**Cause:** When JNDI is unable to handle error code returned by OID server, above error message is returned.

**Action:** Repeat your current action using command line tools supplied with OID server to find out actual error message returned by OID server and take appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** ODSM

**ODSM-01000: Error connecting to OVD.**

**Cause:** OVD server is not running or ODSM is unable to contact OVD server.

**Action:** Ensure that OVD server is up and running. Also check if the server is SSL enabled.

**Level:** 1

**Type:** ERROR

**Impact:** ODSM

**ODSM-01001: Failed to save configuration to OVD server.**

**Cause:** Configuration validation has failed. Refer exception for more details.

**Action:** Provide valid configuration.

**Level:** 1

**Type:** ERROR

**Impact:** ODSM

**ODSM-01002: SSL connection failed.**

**Cause:** SSL mode is not enabled in OVD server.

**Action:** Ensure that SSL mode is enabled in OVD server.

**Level:** 1

**Type:** ERROR

**Impact:** ODSM

**ODSM-01003: Invalid host name.**

**Cause:** Invalid host name is provided.

---

**Action:** Provide valid host name.

**Level:** 1

**Type:** ERROR

**Impact:** ODSM

**ODSM-01004: Incorrect version error.**

**Cause:** Configuration version number sent by ODSM does not match with that of OVD server.

**Action:** Refresh configuration from OVD server and redo the changes.

**Level:** 1

**Type:** ERROR

**Impact:** ODSM

**ODSM-01005: Failed to save access control policies to OVD server.**

**Cause:** Validation of access control policy has failed at OVD server.

**Action:** Provide valid access control policies.

**Level:** 1

**Type:** ERROR

**Impact:** ODSM

**ODSM-01006: Failed to save adapter configuration to OVD server.**

**Cause:** Validation of adapter configuration has failed at OVD server.

**Action:** Provide valid adapter configuration.

**Level:** 1

**Type:** ERROR

**Impact:** ODSM

**ODSM-01007: Failed to retrieve mapping file from OVD server.**

**Cause:** Request mapping file is not available. Refer exception and OVD server log file for more details.

**Action:** Provide valid mapping file.

**Level:** 1

**Type:** ERROR

**Impact:** ODSM

---

---

## ODV-00011 to ODV-00168

**ODV-00011: OraDAV: OCI Error {0}/{1}: {2}**

**Cause:** There was an unexpected error from an OCI call.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Network

**ODV-00048: OraDAV: Oracle DAVParam {0}, {1} or {2} needed**

**Cause:** The OraDAV configuration is incorrect.

**Action:** Add connection information to the configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ODV-00049: OraDAV: Conversion of {0} to {1} as a service name failed**

**Cause:** The OraDAV configuration is incorrect.

**Action:** Correct the database connection information.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ODV-00051: OraDAV: Oracle DAVParam {0} missing**

**Cause:** The OraDAV configuration is incorrect.

**Action:** Add the required DAVParam.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ODV-00052: OraDAV: Oracle DAVParam {0}, {1}, or {2} missing**

**Cause:** The OraDAV configuration is incorrect.

**Action:** Add a required DAVParam.

**Level:** 1

---

Type: WARNING

Impact: Other

**ODV-00053: OraDAV: Oracle DAVParam {0} is invalid.**

Cause: The OraDAV configuration is incorrect.

Action: Correct the value of the DAVParam.

Level: 1

Type: ERROR

Impact: Configuration

**ODV-00055: OraDAV: Oracle DAVParam {0} not decoded**

Cause: The OraDAV configuration is incorrect.

Action: Correct the value of the DAVParam.

Level: 1

Type: ERROR

Impact: Configuration

**ODV-00057: OraDAV: Caching DAVParams are incorrect. Both {0} and {1} must be specified, or neither can be specified.**

Cause: The OraDAV configuration is incorrect.

Action: Either specify both DAVParams or neither.

Level: 1

Type: ERROR

Impact: Configuration

**ODV-00058: OraDAV: Caching DAVParams are incorrect. DAVParam {0} can only be specified if both {1} and {2} are specified.**

Cause: The OraDAV configuration is incorrect.

Action: Specify both DAVParams.

Level: 1

Type: ERROR

Impact: Configuration

**ODV-00059: OraDAV: Oracle Caching DAVParams are incorrect. DAVParam {0} must refer to an existing directory.**

Cause: The OraDAV configuration is incorrect.

Action: Specify a valid directory.

Level: 1

Type: ERROR

Impact: Configuration

**ODV-00060: OraDAV: Caching DAVParam is incorrect. The value {0} is invalid for DAVParam {1}. This must be a positive numeric value optionally followed by KB, MB, or GB.**

Cause: The OraDAV configuration is incorrect.

Action: Specify a valid numeric value.



---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ODV-00063: OraDAV: Caching DAVParam is incorrect. The value {0} is invalid for DAVParam {1}. The value must be an integer between 1 and 100 inclusive.**

**Cause:** The OraDAV configuration is incorrect.

**Action:** Specify a valid numeric value.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ODV-00064: OraDAV: Caching DAVParams are incorrect. The value given for {0} ({1}) is greater than the value given for {2} ({3}).**

**Cause:** The OraDAV configuration is incorrect.

**Action:** Specify valid values for these DAVParams.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**ODV-00065: OraDAV: Failure connecting to Oracle service {0}**

**Cause:** There was a communications error between the module and the repository database.

**Action:** Contact the system or database administrator to resolve the issue.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**ODV-00068: OraDAV: Failure in call to dav\_ora\_init\_driver**

**Cause:** The module was not able to contact the database driver.

**Action:** Check the database status and connections.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**ODV-00069: OraDAV driver API mismatch: Apache OraDAV range = ({0},{1}), {2} range = ({3},{4})**

**Cause:** The module and driver versions are inconsistent.

**Action:** Upgrade either the module or the driver.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**ODV-00071: OraDAV: Failure in call to get\_oradav\_driver\_info**

**Cause:** The module was not able to connect to the database driver.

---

**Action:** Check the database status and connections.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**ODV-00072: OraDAV: Unable to read CLOB value returned in get\_oradav\_driver\_info.**

**Cause:** The module was not able to get the CLOB from the database driver.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**ODV-00073: OraDAV: Error parsing oradav\_driver\_info XML document.**

**Cause:** The module was not able to read the driver information.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**ODV-00074: OraDAV: Error setting oradav\_driver\_info, {0}.**

**Cause:** The module was not able to set the driver information.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**ODV-00079: OraDAV: Error: request context is missing database connection pointer.**

**Cause:** The module could not connect the database for this request.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ODV-00108: OraDAV: version detection failure**

**Cause:** The module and driver versions are inconsistent.

**Action:** Upgrade the database driver.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**ODV-00115: OraDAV: dav\_toutf16 conversion error {0}**

**Cause:** There was an internationalization conversion error.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ODV-00116: OraDAV: OCICollectionToUnicode conversion error {0}**

**Cause:** There was an internationalization conversion error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ODV-00117: OraDAV: OCICollectionToUnicode conversion error {0}**

**Cause:** There was an internationalization conversion error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ODV-00118: OraDAV: dav\_toutf8 conversion error {0}**

**Cause:** There was an internationalization conversion error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ODV-00119: OraDAV: An undefined namespace prefix was used.**

**Cause:** The client has issued an invalid request.

**Action:** Correct the namespace prefix and reissue the request.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODV-00120: OraDAV: A namespace prefix was defined with an empty URI.**

**Cause:** The client has issued an invalid request.

**Action:** Correct the setting for the URI and reissue the request.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODV-00121: OraDAV: There was an error within the XML request body.**

**Cause:** The client has issued an invalid request.

**Action:** Correct the XML request body and reissue the request.

**Level:** 1

**Type:** ERROR

---

**Impact:** Data

**ODV-00122: OraDAV: XML parser error code: {0} ({1}).**

**Cause:** The client has issued an invalid request.

**Action:** Correct the XML request body and reissue the request.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODV-00123: OraDAV: DLL initialization failed, error creating mutex.**

**Cause:** The module was not able to initialize.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Operating System

**ODV-00126: OraDAV: Forcing HTTP\_INTERNAL\_SERVER\_ERROR. NLS href conversion error while converting href {0} to a utf8 value.**

**Cause:** There was an internationalization conversion error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ODV-00127: OraDAV: [DAVOraUseNLS On] UTF8 conversion of URLNative href value:\t{0}UTF8 href value:\t{1} (NLS\_LANG={2})**

**Cause:** There was an internationalization conversion error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ODV-00132: OraDAV: An invalid Depth header was specified.**

**Cause:** The client has issued an invalid request.

**Action:** Correct the Depth header and reissue the request.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODV-00133: OraDAV: An invalid Overwrite header was specified.**

**Cause:** The client has issued an invalid request.

**Action:** Correct the Overwrite header and reissue the request.

**Level:** 1

**Type:** WARNING

---

**Impact:** Data

**ODV-00134: OraDAV: No {0} has been configured.**

**Cause:** The OraDAV configuration is incorrect.

**Action:** Specify valid values in the configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**ODV-00137: OraDAV: Depth must be infinity for DELETE of a collection.**

**Cause:** The client has issued an invalid request.

**Action:** Set the Depth to infinity and reissue the request.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODV-00138: OraDAV: Depth cannot be set to 1 for DELETE.**

**Cause:** The client has issued an invalid request.

**Action:** Set the Depth to infinity and reissue the request.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODV-00140: OraDAV: The propfind element was not found.**

**Cause:** The client has issued an invalid request.

**Action:** Provide a valid propfind element and reissue the request.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODV-00141: OraDAV: The propfind element does not contain one of the required child elements (the specific command).**

**Cause:** The client has issued an invalid request.

**Action:** Provide a valid propfind element and reissue the request.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODV-00142: OraDAV: The request body does not contain a propertyupdate element.**

**Cause:** The client has issued an invalid request.

**Action:** Provide a valid propertyupdate element and reissue the request.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**ODV-00143: OraDAV: A prop element is missing inside the propertyupdate command.**

**Cause:** The client has issued an invalid request.

**Action:** Provide a valid propertyupdate element and reissue the request.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODV-00144: OraDAV: Unknown Transfer-Encoding {0}**

**Cause:** The client has issued an unsupported request.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ODV-00145: OraDAV: Invalid Content-Length: {0}**

**Cause:** The client has issued an unsupported request.

**Action:** Reissue the request with proper Content-Length.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODV-00146: OraDAV: The request is missing a Destination header.**

**Cause:** The client has issued an unsupported request.

**Action:** Reissue the request with proper Content-Length.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODV-00149: OraDAV: Depth must be 0 or infinity for COPY or MOVE.**

**Cause:** The client has issued an invalid request.

**Action:** Set Depth to 0 or infinity and reissue the request.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODV-00150: OraDAV: Depth must be infinity to MOVE a collection.**

**Cause:** The client has issued an invalid request.

**Action:** Set Depth to infinity and reissue the request.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODV-00151: OraDAV: Depth must be 0 or infinity for LOCK.**

---

**Cause:** The client has issued an invalid request.  
**Action:** Set Depth to infinity and reissue the request.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODV-00152: OraDAV: Unlock failed for {0}. No Lock-Token was specified in the header.**

**Cause:** The client has issued an invalid request.

**Action:** Provide a valid Lock-Token and reissue the request.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**ODV-00157: OraDAV: Failed to initialize OCI environment.**

**Cause:** The module was unable to initialize the OCI connection.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ODV-00165: OraDAV: Error creating connection list mutex**

**Cause:** OraDAV was not able to initialize the internal structures.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Operating System

**ODV-00168: OraDAV: Error acquiring connection list mutex.**

**Cause:** OraDAV was not able to initialize the internal structures.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Operating System





---

## OHS-03501 to OHS-03813

**OHS-03501: File copy failed because of {0} exception.**

**Cause:**

**Action:** Check OHS Component provisioning files.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03502: {0} exception occurred while removing configuration files.**

**Cause:**

**Action:** Check configuration files.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03503: {0} exception occurred while creating component.**

**Cause:**

**Action:** See exception to identify problem.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03504: {0} exception occurred while registering the OHS content dir with BR Service.**

**Cause:**

**Action:** See exception to identify problem.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03505: List KeyStore exception**

**Cause:**

**Action:**

**Level:** 1

---

**Type:** ERROR  
**Impact:** Runtime  
**OHS-03506: OHS audit configuration load failed**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Runtime  
**OHS-03507: OHS audit configuration save failed**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Runtime  
**OHS-03508: Unable to set Custom Log configuration**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Runtime  
**OHS-03509: CustomLog configuration is wrong**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Runtime  
**OHS-03510: Exception while disabling OHS module**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Runtime  
**OHS-03511: {0} exception occurred while trying to get configuration from configService.**  
**Cause:**  
**Action:** See exception to identify problem.  
**Level:** 1  
**Type:** ERROR

---

**Impact:** Runtime

**OHS-03512: Configuration document not found.**

**Cause:**

**Action:** Check for configuration document.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03513: {0} exception occurred while trying to read document.**

**Cause:**

**Action:** See exception to identify problem or check document.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03514: {0} exception occurred while trying to write document.**

**Cause:**

**Action:** See exception to identify problem.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03515: {0} exception occurred while trying to read config segment.**

**Cause:**

**Action:** See exception to identify problem.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03516: Null parameter(s) passed.**

**Cause:**

**Action:** Pass non-null parameters.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03517: {0} exception occurred while parsing directive.**

**Cause:**

**Action:** See exception to identify problem.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03518: {0} exception occurred while attempting to read httpd.conf.**

---

**Cause:**

**Action:** See exception to identify problem or check the httpd.conf file.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03519: {0} exception occurred while attempting to write httpd.conf.**

**Cause:**

**Action:** See exception to identify problem or check the httpd.conf file.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03520: Nothing to save.**

**Cause:**

**Action:** Create or load a file.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03521: {0} exception occurred while attempting to write mod\_osso.conf.**

**Cause:**

**Action:** See exception to identify problem or check the mod\_osso.conf file.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03522: VirtualServer {0} does not exist**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03523: {0} exception occurred while attempting to write mod\_oc4j.conf.**

**Cause:**

**Action:** See exception to identify problem or check the mod\_oc4j.conf file.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03524: Can not find IfModule mod\_oc4j.c container in mod\_oc4j.conf**

**Cause:**

**Action:** Check the mod\_oc4j.conf file.

---

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03525: mod\_oc4j.conf file not present**

**Cause:**

**Action:** Check for the mod\_oc4j.conf file.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03526: Failed to read file {0}, because of {1} exception.**

**Cause:**

**Action:** Check file path or directory location.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03527: Failed to write file {0}, because of {1} exception.**

**Cause:**

**Action:** Check file path or directory location.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03528: Can not find value for directive {0}.**

**Cause:**

**Action:** Check file for directive if it is actually required.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03529: httpd.conf has not been loaded.**

**Cause:**

**Action:** Check the httpd.conf file.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03530: failed to delete directive**

**Cause:**

**Action:** See exception to identify problem.

**Level:** 1

**Type:** ERROR

---

**Impact:** Runtime

**OHS-03531: Object passed in is of an invalid class.**

**Cause:**

**Action:** Pass an object of a valid class.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03532: mod\_osso.conf has not been loaded.**

**Cause:**

**Action:** Check the mod\_osso.conf file.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03533: mod\_oc4j.conf has not been loaded.**

**Cause:**

**Action:** Check the mod\_oc4j.conf file.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03534: Exception in getPropertiesFromBinaryFile: {0}**

**Cause:**

**Action:** Check that the file has been created correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03535: 902 format is not supported. Exception is {0}.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03536: 902 format supported.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03537: Exception occurred while obfuscating string contents. Exception is {0}.**

---

**Cause:**

**Action:** See exception to identify problem.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03538: Exception occurred while writing to osso.conf file. Exception is {0}.**

**Cause:**

**Action:** See exception to identify problem.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03539: Exception in getOSSOConfFile: {0}**

**Cause:**

**Action:** See exception to identify problem.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03540: Error reading configuration document: {0}**

**Cause:**

**Action:** Check that the location of the document has been correctly specified.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03541: Input parameters are null.**

**Cause:**

**Action:** Provide appropriate arguments when calling mod\_osso registration code.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03542: SSO DB partner version received is null.**

**Cause:**

**Action:** Check that SSO DB version is supplied when calling partner registration code.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03543: Partner application site ID received is null.**

**Cause:**

---

**Action:** Check that partner site ID is supplied when calling partner registration code.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03544: Partner application site token received is null.**

**Cause:**

**Action:** Check that partner site token is supplied when calling partner registration code.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03545: Partner application login URL received is null.**

**Cause:**

**Action:** Check that login URL is supplied when calling partner registration code.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03546: Partner application logout URL received is null.**

**Cause:**

**Action:** Check that logout URL is supplied when calling partner registration code.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03547: Partner application timeout cookie received is null.**

**Cause:**

**Action:** Check that timeout cookie is supplied when calling partner registration code.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03548: Partner application timeout key received is null.**

**Cause:**

**Action:** Check that timeout key is supplied when calling partner registration code.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03549: Partner application urlc version received is null.**

**Cause:**



---

**Action:** Check that urlc version is supplied when calling partner registration code.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03550: Partner application preencryption mask received is null.**

**Cause:**

**Action:** Check that preencryption mask is supplied when calling partner registration code.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03551: Partner application post-encryption mask received is null.**

**Cause:**

**Action:** Check that post-encryption mask is supplied when calling partner registration code.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03552: Partner application cancel URL received is null.**

**Cause:**

**Action:** Check that cancel URL is supplied when calling partner registration code.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03553: Partner application non-SSL SSO host received is null.**

**Cause:**

**Action:** Check that non-SSL SSO host is supplied when calling partner registration code.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03554: Partner application OSSO configuration file path received is null.**

**Cause:**

**Action:** Check that configuration file path is supplied when calling partner registration code.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03555: Exception occurred during reading of input values. Error was: {0}**

---

**Cause:**

**Action:** Check that all necessary inputs are correctly supplied to the partner registration tool.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03556: The osso.conf file was added successfully.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03557: Status: {0}**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03558: The osso.conf file was not added. Operation failed.**

**Cause:**

**Action:** Check previous exception for additional information.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03559: The osso.conf file was retrieved successfully.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03560: The osso.conf file could not be retrieved. Operation failed.**

**Cause:**

**Action:** Check previous exception for additional information.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03561: The osso.conf file was deleted successfully.**

**Cause:**

---

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03562: The osso.conf file could not be deleted. Operation failed.**

**Cause:**

**Action:** Check previous exception for additional information.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03563: Already enabled. Configuration document already exists.**

**Cause:**

**Action:** Check name or select a different module.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03564: Null MAS configuration object encountered.**

**Cause:**

**Action:** See exception to identify problem.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03565: ManagementException occurred reading {0}.**

**Cause:**

**Action:** Check previous exception for additional information.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03566: IOException occurred reading {0}.**

**Cause:**

**Action:** Check previous exception for additional information.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03567: failed to update file {0}.**

**Cause:**

**Action:** Check previous exception for additional information.

---

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03568: failed to update file due to invalid contents.**

**Cause:**

**Action:** Check previous exception for additional information.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03569: Null exception reference encountered when attempting handling exception.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03570: ThreadLimit may not exceed**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03571: ServerLimit may not exceed**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03572: Max Clients exceeds range, raise ServerLimit.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03573: Max Clients exceeds range, raise ServerLimit or ThreadPerChild.**

**Cause:**

**Action:**

**Level:** 1

---

**Type:** ERROR

**Impact:** Runtime

**OHS-03574: mod\_osso is not enabled. mod\_osso must be enabled before modifying osso related directives.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03575: The value of ThreadLimit cannot be less than the value of ThreadsPerChild.**

**Cause:**

**Action:** Use a larger value for ThreadLimit or lower the ThreadsPerChild value.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03576: The value of ThreadsPerChild cannot be greater than the value of ThreadLimit.**

**Cause:**

**Action:** Use a smaller value for ThreadsPerChild or raise the value of ThreadLimit.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03577: The value of ServerLimit cannot be less than the value of MaxClients.**

**Cause:**

**Action:** Use a larger value for ServerLimit or lower the value of MaxClients.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03578: The value of ServerLimit \* ThreadsPerChild cannot be less than the value of MaxClients.**

**Cause:**

**Action:** Use a larger value for ServerLimit and/or ThreadsPerChild, or lower the value of MaxClients.

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03579: Virtual Host Already Exists**

**Cause:**

---

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03580: Not a proper Virtual Host Name**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03581: Enable Module failed**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03582: Module is not installed**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03583: Register child MBean api failed**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03584: Proxy Port MBean registration failed**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03585: Audit MBean registartion failed**

**Cause:**

**Action:**

---

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03586: Parsing error while loading MBeans**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03587: Exception occurred while loading MBeans**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03588: Virtual Host creation failed**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03589: Duplicate virtual host found**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03590: Base Virtual host creation failed**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03591: Configuration file parsing failed**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

---

**Impact:** Runtime

**OHS-03592: OraDev config MBean registration failed**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03593: Unregister of Keystore MBean success**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03594: Unregister of configuration MBeans failed**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03595: Unable to get VH objects from root OHS MBean**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03596: Load wallets failed**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03597: Removal of Virtual Host failed**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Runtime

**OHS-03598: Removal of Listen failed while removing VH**



---

**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Runtime

**OHS-03599: Configuration Restore failed**

**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Runtime

**OHS-03600: Configuration validation failed**

**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Runtime

**OHS-03601: Load failed with IOException**

**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Runtime

**OHS-03602: Module Name is wrong**

**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Runtime

**OHS-03603: Unable to find the MPM Name, Setting it to default Worker**

**Cause:**  
**Action:**  
**Level:** 1  
**Type:** ERROR  
**Impact:** Runtime

**OHS-03604: Unable to find Server Name, Setting it to default AdminServer**

**Cause:**  
**Action:**

---

**Level: 1**  
**Type: ERROR**  
**Impact: Runtime**  
**OHS-03701: Error log configuration not valid**  
**Cause:**  
**Action:**

**Level: 1**  
**Type: WARNING**  
**Impact: Runtime**  
**OHS-03702: Saving wallet is null**  
**Cause:**  
**Action:**

**Level: 1**  
**Type: WARNING**  
**Impact: Runtime**  
**OHS-03703: PWallet is null, not able to load cwallet**  
**Cause:**  
**Action:**

**Level: 1**  
**Type: WARNING**  
**Impact: Runtime**  
**OHS-03704: CWallet is null, not able to load cwallet**  
**Cause:**  
**Action:**

**Level: 1**  
**Type: WARNING**  
**Impact: Runtime**  
**OHS-03705: Directive does not exist**  
**Cause:**  
**Action:**

**Level: 1**  
**Type: WARNING**  
**Impact: Runtime**  
**OHS-03706: WLPort not configured; Illegal Usage**  
**Cause:**  
**Action:**

**Level: 1**  
**Type: WARNING**

---

**Impact:** Runtime

**OHS-03707: WLHost not configured; Illegal Usage**

**Cause:**

**Action:**

**Level:** 1

**Type:** WARNING

**Impact:** Runtime

**OHS-03708: WLCluster not configured; Not allowed to call listWLCluster**

**Cause:**

**Action:**

**Level:** 1

**Type:** WARNING

**Impact:** Runtime

**OHS-03709: DynamicServerList is not configured ; Illegal Usage**

**Cause:**

**Action:**

**Level:** 1

**Type:** WARNING

**Impact:** Runtime

**OHS-03710: CertValidationPath is not configured**

**Cause:**

**Action:**

**Level:** 1

**Type:** WARNING

**Impact:** Runtime

**OHS-03711: CertValidation is not configured ; Illegal Usage**

**Cause:**

**Action:**

**Level:** 1

**Type:** WARNING

**Impact:** Runtime

**OHS-03712: SSLWallet is not configured ; Illegal Usage**

**Cause:**

**Action:**

**Level:** 1

**Type:** WARNING

**Impact:** Runtime

**OHS-03713: SSLAuthType is not configured ; Illegal Usage**

---

**Cause:**

**Action:**

**Level:** 1

**Type:** WARNING

**Impact:** Runtime

**OHS-03714: SSLCiphers is not configured ; Illegal Usage**

**Cause:**

**Action:**

**Level:** 1

**Type:** WARNING

**Impact:** Runtime

**OHS-03715: SSLVersions is not configured ; Illegal Usage**

**Cause:**

**Action:**

**Level:** 1

**Type:** WARNING

**Impact:** Runtime

**OHS-03716: SSLEnabled is not configured ; Illegal Usage**

**Cause:**

**Action:**

**Level:** 1

**Type:** WARNING

**Impact:** Runtime

**OHS-03801: Load Operation failed in VH SSLResource**

**Cause:**

**Action:**

**Level:** 1

**Type:** INFORMATION

**Impact:** Runtime

**OHS-03802: Load Operation finished in VH SSLResource**

**Cause:**

**Action:**

**Level:** 1

**Type:** INFORMATION

**Impact:** Runtime

**OHS-03803: Configuration file backup success**

**Cause:**

**Action:**

---

**Level: 1**

**Type: INFORMATION**

**Impact: Runtime**

**OHS-03804: Load operation success**

**Cause:**

**Action:**

**Level: 1**

**Type: INFORMATION**

**Impact: Runtime**

**OHS-03805: Module is already configured**

**Cause:**

**Action:**

**Level: 1**

**Type: INFORMATION**

**Impact: Runtime**

**OHS-03806: Unregistered all configuration MBeans**

**Cause:**

**Action:**

**Level: 1**

**Type: INFORMATION**

**Impact: Runtime**

**OHS-03807: Wildcard char, allow processing**

**Cause:**

**Action:**

**Level: 1**

**Type: INFORMATION**

**Impact: Runtime**

**OHS-03808: Error log configuration mode is not apache**

**Cause:**

**Action:**

**Level: 1**

**Type: INFORMATION**

**Impact: Runtime**

**OHS-03809: Error log Mode is apache**

**Cause:**

**Action:**

**Level: 1**

**Type: INFORMATION**

---

**Impact:** Runtime

**OHS-03810: Listen Directive not configured**

**Cause:**

**Action:**

**Level:** 1

**Type:** INFORMATION

**Impact:** Runtime

**OHS-03811: Listen Directive already exist for specified port**

**Cause:**

**Action:**

**Level:** 1

**Type:** INFORMATION

**Impact:** Runtime

**OHS-03812: Configuration Restore success**

**Cause:**

**Action:**

**Level:** 1

**Type:** INFORMATION

**Impact:** Runtime

**OHS-03813: OHS Validation successfull**

**Cause:**

**Action:**

**Level:** 1

**Type:** INFORMATION

**Impact:** Runtime

---

---

## OID-03053 to OID-23737

**OID-03053: Cannot add nonbase schema outside cn=subschemasubentry.**

**Cause:** A schema addition was attempted outside cn=subschemasubentry.

**Action:** Ensure schema additions are made to cn=subschemasubentry.

**Level:** 16

**Type:** ERROR

**Impact:** Compliance

**OID-12501: Password Policy Error :%d: %s : Your account is locked. Contact your OID administrator.**

**Cause:** The configured maximum for consecutive bind failures allowed as the given user was exceeded.

**Action:** Set orclpwdaccountunlock on the user entry to 1. This action can be performed only by users with the appropriate privileges.

**Level:** 16

**Type:** ERROR

**Impact:** Security

**OID-23001: OID is unable to come up using the configured port.**

**Cause:** The port configured for use by OID was not available.

**Action:** Ensure that the port numbers used for OID are available.

**Level:** 16

**Type:** ERROR

**Impact:** Ports

**OID-23002: Creating a new DB connection failed with ORA-%d.**

**Cause:** OID server was unable to log in to the database.

**Action:** Verify the 'PROCESS' database parameter in the init.ora file.

**Level:** 16

**Type:** ERROR

**Impact:** Network

**OID-23004: Unable to read replication configuration information**

---

**Cause:** This error occurred because the replication server was unable to connect to OID, was unable to get the replication DN and password, or the replication system configuration was not present.

**Action:** The error message will be followed by other log messages indicating action to be taken.

**Level:** 16

**Type:** ERROR

**Impact:** Configuration

**OID-23005: %s: No replication agreement to process**

**Cause:** Replication agreements were not set up with other node(s).

**Action:** Set up the replication agreement with other node(s) before starting the replication server.

**Level:** 16

**Type:** ERROR

**Impact:** Configuration

**OID-23006: In %s, failure to enqueue %s into queue=%s**

**Cause:** The replication enqueue routine failed.

**Action:** This is an internal error. Use the oidcmprec tool to compare and reconcile this entry from the supplier to the consumer. For further help contact Oracle Support Services.

**Level:** 1

**Type:** WARNING

**Impact:** Session

**OID-23007: In %s, failing to bind with the supplier on server=%s**

**Cause:** Either the OID server was down or the replication password was incorrect.

**Action:** Ensure that the OID server on the supplier is running. If the password has changed restart the replication server.

**Level:** 16

**Type:** ERROR

**Impact:** Session

**OID-23008: In %s, failing to read attribute values from change log entry, agreement=%s, operation=%s.**

**Cause:** Change log entries may be corrupted or certain attributes in the change log entry were not found.

**Action:** Check the associated error messages and look for the entry that failed. Using oidcmprec tool, compare and reconcile this entry from supplier to consumer.

**Level:** 16

**Type:** ERROR

**Impact:** Data



---

**OID-23009: In %s, error moving successfully applied change log items to purge queue, error=%s, changeNo=%d.**

**Cause:** Failed to update the change log entry status.

**Action:** Resolve the associated errors logged in the Replication server log and the OID server log. For further help contact Oracle Support Services.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**OID-23010: Memory allocation failure in %s for %d bytes.**

**Cause:** The replication server was unable to allocate the required memory space.

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Memory

**OID-23011: In %s, failure connecting to server, %s.**

**Cause:** Either the OID server is down or the replication password is incorrect.

**Action:** Ensure that the OID server is running. If the replication password has changed restart the replication server.

**Level:** 16

**Type:** ERROR

**Impact:** Session

**OID-23012: In %s, cannot bind to the consumer, server=%s**

**Cause:** Either the OID server is down or the replication password is incorrect.

**Action:** Ensure that the OID server on the consumer is running. If the replication password has changed restart the replication server.

**Level:** 16

**Type:** ERROR

**Impact:** Session

**OID-23013: In %s, failure reading replica state of supplier from server=%s, DN=%s.**

**Cause:** The replica entry was either corrupt or not found.

**Action:** Using remtool, clean up the replication and set up the replication again. \*{1} is the status of bootstrapping stage, {2} is hostname and {3} is agreement id.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23014: Failure updating replica status to %s at server=%s for agreement id =%s.**

**Cause:** Could not update the replication configuration entry for the replica.

**Action:** Look at the OID server log and resolve the corresponding errors reported in the log.

**Level:** 16

---

**Type:** ERROR

**Impact:** Session

**OID-23015: In %s, failure initializing last changenumber for bootstrapping, agreement=%s, supplierChangeNo=%d, consChangeNo=%d, errorCode=%d.**

**Cause:** Could not get the last change number from the replica or could not update the replication configuration entry with the change number.

**Action:** Look at the OID server log and resolve the corresponding errors reported in the log.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23016: In %s, failure beginning hash iteration for included namecontext. Server=%s, agreement=%s.**

**Cause:** No naming context was included for the replication agreement.

**Action:** Add the naming context for the replication agreement. If this does not resolve the problem contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Configuration

**OID-23017: In %s, failure when bootstrapping %d out of %d naming context(s) from the supplier, %s.**

**Cause:** Indicated in the following associated error messages in the log file.

**Action:** More specific messages will accompany this message. Refer to those messages for the appropriate action.

**Level:** 16

**Type:** ERROR

**Impact:** Session

**OID-23018: In %s, failing in subtree delete on DN=%s, server=%s, error=%s.**

**Cause:** The ldap\_delete operation failed.

**Action:** Check the OID server log and resolve the corresponding errors reported in the log. Contact Oracle Support Services for additional assistance.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Session

**OID-23019: In %s, failure enqueueing %s into queue=%s.**

**Cause:** An internal error caused the enqueue routine to fail.

**Action:** Contact Oracle Support Services.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Session

---

**OID-23020: In %s, ldap\_search failure against server=%s where basedn=%s, scope=%d, filter=%s, attrs=%s, error=%s.**

**Cause:** Either the entry did not exist or this was an internal error where ldap\_search failed.

**Action:** Examine the OID server logs and resolve the corresponding errors reported.

**Level:** 16

**Type:** ERROR

**Impact:** Session

**OID-23021: In %s, ldap\_result failure against server=%s where basedn=%s, scope=%s, filter=%s, attrs=%s, error=%s.**

**Cause:** An internal error occurred where ldap\_result could not process the records.

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Session

**OID-23022: In %s, failure parsing paging control response on server=%s, basedn=%s, scope=%s, filter=%s, attrs=%s, error=%s.**

**Cause:** An internal error occurred where the paging control parsing failed.

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Session

**OID-23024: In %s, NULL LDAPMod structure returned for DN=%s, agreement=%s.**

**Cause:** An internal error occurred where the LDAPMod build routine returned NULL.

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23025: In %s, during bootstrapping operation, synchronization of entry DN=%s failing as this entry does not exist at supplier. Supplier=%s, consumer=%s.**

**Cause:** The entry might have been deleted at the supplier during the bootstrap process.

**Action:** Restart the bootstrap process.

**Level:** 16

**Type:** ERROR

**Impact:** Data

---

**OID-23026: In %s, ldap\_add failure for DN=%s where supplier=%s and consumer=%s with error=%s.**

**Cause:** The target DN may have been added by some other process on the consumer node during the bootstrap process.

**Action:** Restart the bootstrap process.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23027: In %s, ldap\_modify failure for DN=%s where supplier=%s and consumer=%s with error=%s.**

**Cause:** The target DN may have been deleted by some other process on the consumer node during the bootstrap process.

**Action:** Restart the bootstrap process.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23028: In %s, failure running DBMS\_STATS.gather\_schema\_stats on server=%s.**

**Cause:** Gathering of the schema statistics has failed.

**Action:** Manually run the job to gather the schema statistics.

**Level:** 16

**Type:** ERROR

**Impact:** Process

**OID-23029: In %s, failure creating Hashtable. %s.**

**Cause:** An internal error occurred where the Hashtable routine failed.

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Memory

**OID-23030: In %s, Hash Insert failure. %s.**

**Cause:** An internal error occurred where the HashTable insert routine failed.

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23031: In %s, ldap\_search failed for ASR agreement on server=%s where basedn=%s, scope=%s, filter=%s, attrs=%s, error=%s.**

**Cause:** For ASR replication, either the agreement DN was corrupt or not found.

**Action:** Using remtool, clean up the replication (asrcleanup) and set up the replication (asrsetup) again.

---

**Level:** 16

**Type:** ERROR

**Impact:** Session

**OID-23032: In %s, failure inserting agreement for GroupDSA. Agreement=%s.**

**Cause:** See the associated error messages for the actual cause.

**Action:** More specific messages will accompany this message. Refer to the other messages for the appropriate action.

**Level:** 16

**Type:** ERROR

**Impact:** Session

**OID-23033: In %s, failure reading GroupDSA of Agreement: %s.**

**Cause:** An internal error occurred where insert to DnList failed.

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Session

**OID-23034: In %s, failure reading attribute=%s from ASR replication agreement DN, %s.**

**Cause:** ASR agreement DN was either corrupt or not set up properly.

**Action:** Using remtool, clean up the replication (asrcleanup) and set up the replication (asrsetup) again.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23035: In %s, unknown agreement protocol=%s under replication agreement DN, %s.**

**Cause:** Wrong protocol attribute value under the agreement.

**Action:** Using remtool, clean up the replication and set up the replication again.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23036: In %s, failure getting current time. %s**

**Cause:** An internal error occurred where the CurrentTime routine failed.

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Operating System

**OID-23037: In %s, failure initializing mutex for agreement DN=%s.**

**Cause:** An internal error occurred where the mutex routine failed.

---

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Memory

**OID-23038: In %s, local replica context is NULL on server=%s, agreement=%s.**

**Cause:** An internal error occurred where the local replica's context was not loaded.

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23039: In %s, failure reading replication configuration on server=%s with basedn=%s, scope=%s, filter=%s, attrs=%s, error=%s.**

**Cause:** The replication configuration entry (cn=Replication Configuration) was either corrupt or not found for the replica.

**Action:** Look at the OID server log and resolve the corresponding errors reported in the log. For further help contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23040: In %s, failure reading attribute=%s from LDAP replication agreement DN=%s on Server=%s.**

**Cause:** LDAP agreement DN was either corrupt or not set up properly.

**Action:** Using remtool, delete the node and add the node with the right configuration.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23041: In %s, failure to get replica context,%s, from agreement,%s, on server=%s.**

**Cause:** An internal error occurred where the replica context was not found in the list for an agreement.

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Session

**OID-23042: In %s, failure to load the LDAP agreement=%s for replica context=%s.**

**Cause:** See the associated error messages for the actual cause

**Action:** More specific messages will accompany this message. Refer to the other messages for the appropriate action.

---

**Level:** 16

**Type:** ERROR

**Impact:** Session

**OID-23043: In %s, failure initializing LDAP name context for agreement, %s.**

**Cause:** See the associated error messages for the actual cause

**Action:** More specific messages will accompany this message. Refer to the other messages for the appropriate action.

**Level:** 16

**Type:** ERROR

**Impact:** Session

**OID-23044: In %s, failure duplicating hash table. %s**

**Cause:** An internal error occurred where the HashTable routine failed.

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Memory

**OID-23045: In %s, failure to get replication DN and password from the wallet where consumer=%s.**

**Cause:** See the associated error messages for the actual cause

**Action:** More specific messages will accompany this message. Refer to the other messages for the appropriate action.

**Level:** 16

**Type:** ERROR

**Impact:** Session

**OID-23046: In %s, failure getting the replication system configuration. Server=%s, Error=%s.**

**Cause:** The entry "configset0" for replication does not exist

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Session

**OID-23047: In %s, failure to normalize naming context, %s. Server=%s, ErrorCode=%d.**

**Cause:** An internal error occurred where the ldap routine failed.

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23048: In %s, invalid replica DN entry under the replication configuration on server=%s.**

---

**Cause:** Replication configuration subentry was either corrupt or not configured properly.

**Action:** Using remtool, clean up the replication and set up the replication again.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23049: In %s, failure to read attribute=%s from replicaDN=%s on server=%s.**

**Cause:** Replica DN was either corrupt or not set up properly.

**Action:** Update this attribute with the correct value by using either ODSM or the command line. If this does not resolve the issue, use remtool to clean up replication, then set up replication again.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23050: In %s, failure to parse the URI value in replicaDN. %s.**

**Cause:** Replica DN was either corrupt or not set up properly.

**Action:** Update this URI with the correct value by using either ODSM or the command line. If this does not resolve the issue, use remtool to clean up replication, then set up replication again.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23051: In %s, failure spawning thread. %s.**

**Cause:** An internal error occurred where the spawning of a thread failed.

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Threads

**OID-23052: In %s, failure reading the replica id from replica DN=%s.**

**Cause:** An internal error occurred where the DN parsing routine failed.

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23053: In %s, failure creating the queue, %s. %s.**

**Cause:** An internal error occurred where the Queue routine failed.

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR



---

**Impact:** Session

**OID-23054: In %s, failure getting the attribute=%s from the changeStatusEntry.  
Server=%s, agreement=%s, operation=%s.**

**Cause:** Invalid changestatusentry DN.

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Session

**OID-23055: In %s, failure getting the attribute=%s from the root DSE. Server=%s,  
error=%d.**

**Cause:** Either this attribute was corrupt or an internal error occurred in ldap\_  
search.

**Action:** Look at the OID server log and resolve the corresponding errors reported  
in the log. For further help contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23056: In %s, Replica, %s is in offline mode.**

**Cause:** Was unable to start the replication as the replica was in offline mode.

**Action:** Update the replica state to ONLINE and restart the replication server.

**Level:** 16

**Type:** ERROR

**Impact:** Session

**OID-23057: In %s, failure beginning hash iteration for excluded namecontext.  
Server=%s, agreement=%s.**

**Cause:** Either the agreement DN was corrupt or an internal error occurred in  
which the routine failed to get excluded namecontext.

**Action:** Using remtool, clean up the replication and set up the replication again.  
For further help contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23058: In %s, failure loading schema. Server=%s, error=%s.**

**Cause:** An internal error occurred causing schema load to fail.

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23059: In %s, failure finding %s in the schema. Server=%s.**

**Cause:** An internal error occurred causing schema load to fail.

---

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23060: In %s, error while loading %s from the schema. Server=%s.**

**Cause:** An internal error occurred causing schema load to fail.

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23061: In %s, failure binding to server. Server=%s, port=%d.**

**Cause:** Either OID server was down or the replication password was incorrect.

**Action:** Ensure that the OID server is running. If the replication password has changed, restart the replication server.

**Level:** 16

**Type:** ERROR

**Impact:** Network

**OID-23062: In %s, failure to initialize %s naming context checking rules. Server=%s, agreement=%s, error=%d.**

**Cause:** An internal error occurred where initialization of the naming context checking rules failed.

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Session

**OID-23063: In %s, failure to initialize excluded attribute checking rules. Server=%s, agreement=%s, error=%s.**

**Cause:** An internal error occurred where initialization of the excluded attribute checking rules failed.

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Session

**OID-23064: In %s, failure getting CORE context.**

**Cause:** An internal error occurred where getCOREcontext failed.

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Memory

---

**OID-23065: In %s, failure beginning hash iteration. Server=%s, Error=%d.**

**Cause:** An internal error occurred where the hash routine failed.

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Memory

**OID-23066: In %s, failure getting the error change log count.**

**Cause:** See the associated error messages for the actual cause

**Action:** More specific messages will accompany this message. Refer to the other messages for the appropriate action.

**Level:** 16

**Type:** ERROR

**Impact:** Session

**OID-23067: In %s, failure in comparing and reconciling schema of supplier, %s, and consumer, %s.**

**Cause:** Comparison and reconciliation of attributes and objectclasses in the schema failed.

**Action:** Look at the replication server log and resolve the associated errors reported in the log. For further help contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23068: In %s, failure to update changestatusEntry. Consumer=%s, supplier=%s, agreement=%s, changeno=%d.**

**Cause:** See the associated error messages for the actual cause

**Action:** More specific messages will accompany this message. Refer to the other messages for the appropriate action.

**Level:** 16

**Type:** ERROR

**Impact:** Session

**OID-23069: In %s, failure parsing count control response. Server=%s, agreement=%s, error=%s.**

**Cause:** An internal error occurred where parse control failed.

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Session

**OID-23070: In %s, failure binding to server. Server=%s, port=%d.**

**Cause:** Either OID server was down or the replication password was incorrect.

**Action:** Ensure that the OID server is running. If the replication password has changed restart the replication server.

---

**Level:** 16

**Type:** ERROR

**Impact:** Network

**OID-23071: In %s, finding only one replica, %s, for the agreement, %s.**

**Consumer=%s.**

**Cause:** LDAP agreement was either corrupt or not set up properly.

**Action:** Using remtool, clean up the replication and set up the replication again.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**OID-23072: In %s, bootstrapping against non-leaf replica is not allowed. %s**

**Cause:** Status of the replica was set to BOOTSTRAP, which is not allowed for non-leaf replica.

**Action:** Set the status to ONLINE for the replication to start, for this replica.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23073: In %s, bootstrap against master replica is not allowed. %s**

**Cause:** Status of the replica was set to BOOTSTRAP, which is not allowed for master replica.

**Action:** Set the status to ONLINE for the replication to start, for this replica.

**Level:** 16

**Type:** ERROR

**Impact:** Configuration

**OID-23075: In gslsbaAddEntry, orclpassword must not be in cleartext if the userpassword attribute is not present in the entry.**

**Cause:** An attempt was made to add or modify the orclpassword attribute with a cleartext value while the userpassword attribute was not present in the entry.

**Action:** Ensure that the orclpassword attribute value is in a hash format.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23076: Trying to register more than the maximum number of plug-ins allowed.**

**Cause:** There were 128 plug-ins configured in the OID. No more are allowed.

**Action:** Please check the existing plug-ins and make sure the total number of plug-ins is within the maximum limitation.

**Level:** 16

**Type:** ERROR

**Impact:** Configuration

**OID-23077: In gslsbaUniqueCheck, objectclass is missing in the entry with DN %s.**

---

**Cause:** The given entry was missing values for the objectclass attribute.

**Action:** Provide objectclass attributes with values in the entry being added.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23078: In gslsbpmCGetSubscriberpwdPolicy, unable to find root password policy.**

**Cause:** The pwdpolicysubentry attribute in the root DSE was not populated, or the DN described in the pwdpolicysubentry attribute value did not exist.

**Action:** Ensure that the pwdpolicysubentry attribute is populated with the DN of a valid password policy entry.

**Level:** 16

**Type:** ERROR

**Impact:** Security

**OID-23079: %s is not in UTC format. Unable to determine account validity for %s.**

**Cause:** The orclactiveenddate or orclactivestartdate attribute in the entry associated with this message was not in UTC format.

**Action:** Ensure that orclactiveenddate and orclactivestartdate are always in UTC format.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23080: In gslbpvGenO3LogonVerifier, username is NULL.**

**Cause:** When generating O3LogonVerifier, OID was unable to locate or construct a username (DN) by internal search or by user input.

**Action:** Ensure that the username (DN) is available.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23082: Encountering unsupported plug-in configuration.**

**Cause:** An invalid plug-in configuration was found in OID.

**Action:** Examine all existing plug-in configurations and ensure all the plug-in conditions are specified correctly.

**Level:** 16

**Type:** ERROR

**Impact:** Configuration

**OID-23083: Server with Process ID = %d is running but not responding.**

**Cause:** The state of the server process with the specified PID was unstable and therefore the server did not respond.

**Action:** After the dispatcher process has retried checking status 1000 times, if the the server is still unresponsive, the dispatcher starts a new server process.

---

Alternately, terminate the server process, which will result in a new server being launched automatically.

**Level:** 16

**Type:** ERROR

**Impact:** Process

**OID-23084: ServerDispatcher: The new maximum instance specific concurrent connections setting is not immediately effective.**

**Cause:** The new instance specific maximum concurrent connections limit was less than the total number of already established connections.

**Action:** The setting will automatically become effective when the number of established connections falls below the new limit. Alternatively, restart the instance for the new setting to be effective immediately.

**Level:** 16

**Type:** ERROR

**Impact:** Session

**OID-23085: An invalid change log entry is being added to the shadow change log.**

**Cause:** An internal error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23086: In gsldbb\_AddAttrBVal, size of binary attribute to be added exceeds the max supported size.**

**Cause:** Size of this binary attribute value exceeds max limit (4MB).

**Action:** Ensure that the binary attribute value's size is within max size limit and retry the operation.

**Level:** 16

**Type:** ERROR

**Impact:** Compliance

**OID-23087: In gsldbb\_AddAttrBVal, no value to add for binary attribute name.**

**Cause:** The binary attribute value was empty.

**Action:** Ensure that the binary attribute value is not empty and then retry the operation.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23088: Detecting Illegal change log search condition %d.**

**Cause:** An internal error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 16

---

**Type:** ERROR

**Impact:** Session

**OID-23089: In gsldma\_Modify, invalid value for attribute orclrefreshdgrmems.**

**Cause:** Invalid value provided for dynamic group membership refresh attribute.

**Action:** Ensure that value of dynamic group membership refresh attribute - orclrefreshdgrmems - is either 0 or 1.

**Level:** 16

**Type:** ERROR

**Impact:** Compliance

**OID-23090: In gslfadADoAdd, no value(s) provided for attribute %s.**

**Cause:** No value(s) was given for this attribute in the ldapadd operation.

**Action:** Provide value(s) for the attribute and retry the ldapadd operation.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23091: In gslfbigciGetControlInfo, illegal format of control information.**

**Cause:** The format of the control sent was invalid.

**Action:** Ensure that the format of the control sent is valid and retry the operation.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**OID-23092: In gslfbigciGetControlInfo, illegal format of control Object ID.**

**Cause:** The format of the sent control's OID is invalid.

**Action:** Ensure that the format of the sent control's OID is valid and retry the operation.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**OID-23093: In gslfbirbiReadBindInfo, unsupported LDAP version %d.**

**Cause:** Version of the client protocol used in the operation was not supported by the OID server.

**Action:** Ensure that client protocol version is supported.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**OID-23094: In gslfbiSetAuthFromSSL, the certificate DN %s matches more than one entry in OID.**

**Cause:** The client certificate does not uniquely identify an user entry in OID.

**Action:** Ensure that the certificate to DN mapping is n to 1 and retry the operation.

---

**Level:** 16

**Type:** ERROR

**Impact:** Security

**OID-23095: In gslfblsafsSetAuthFromSSL, selected credential does not support client authentication.**

**Cause:** The client did not send the client certificate credential required by the server.

**Action:** Check the client SSL credential.

**Level:** 16

**Type:** ERROR

**Impact:** Security

**OID-23096: In gslfblsafsSetAuthFromSSL, the certificate DN %s does not exist.**

**Cause:** The client certificate contains a user DN that does not exist in the directory.

**Action:** Verify that the client certificate has a valid user DN in the directory and retry the operation.

**Level:** 16

**Type:** ERROR

**Impact:** Security

**OID-23097: In gslfblsafsSetAuthFromSSL, illegal DN %s in the certificate.**

**Cause:** The subject DN in the client certificate was invalid.

**Action:** Ensure that the subject DN in the client certificate is valid and retry the operation.

**Level:** 16

**Type:** ERROR

**Impact:** Security

**OID-23098: In gslfdeADoDelete, Ldap v2 clients need to bind first.**

**Cause:** Client was using protocol with LDAP version 2 and did not perform a ldapbind operation before issuing this LDAP operation.

**Action:** Ensure that if the client is using LDAP version 2, an ldapbind performed before any other LDAP operation.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**OID-23099: In gslfseADoSearch, Ldap v2 clients need to bind first.**

**Cause:** Client was using LDAP version 2 and did not perform an ldapbind operation before issuing this LDAP operation.

**Action:** Ensure that if the client is using LDAP version 2, an ldapbind is performed before any other LDAP operation.

**Level:** 16

**Type:** ERROR



---

**Impact:** Requests/Responses

**OID-23100: In gslfseADoSearch, filter is invalid.**

**Cause:** The search filter in the ldapsearch operation was not valid.

**Action:** Ensure that the search filter in the ldapsearch operation is valid.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**OID-23101: In gslfseADoSearch, filter must be single AVA for user certificate binary for exact match.**

**Cause:** In an exact match certificate search, the filter supplied was not a single attribute value assertion.

**Action:** Ensure that for the exact match certificate search, the filter supplied is a single attribute value assertion.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**OID-23102: Unknown filter choice %d.**

**Cause:** The filter choice in the ldapsearch operation was not valid.

**Action:** Ensure that the filter choice in the ldapsearch operation is valid.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**OID-23103: In gsldbb\_AddAttrBVal, failure retrieving certificate information from certificate (%d).**

**Cause:** The certificate was not valid.

**Action:** Ensure the validity of the certificate.

**Level:** 16

**Type:** ERROR

**Impact:** Security

**OID-23104: In gsldbb\_AddAttrBVal, failure converting certificate serial number from binary to base 64-encoded string (%d).**

**Cause:** Invalid certificate serial number.

**Action:** Check the serial number in the certificate.

**Level:** 16

**Type:** ERROR

**Impact:** Security

**OID-23105: Line %d: missing < = > in (or value after) < %s > in to clause.**

**Cause:** Attribute list was not provided in ACI directive clause governing attributes.

---

**Action:** Examine ACI syntax documentation and provide attribute list in required format.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23106: Line %d: erroneous attribute list < %s > in to clause.**

**Cause:** The attribute list was incorrectly formatted.

**Action:** Examine ACI syntax documentation and reformat the ACI clause to adhere to the expected format.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23107: Attribute %s not defined in schema (entrydn=%s).**

**Cause:** An attribute not defined in the directory schema was part of the ACI clause.

**Action:** Remove all attributes not defined in the directory schema from ACI directives.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23108: gslecLRU: Entry cache is full, could not free up size %u.**

**Cause:** Entry Cache is FULL.

**Action:** Increase the Entry Cache size.

**Level:** 16

**Type:** ERROR

**Impact:** Memory

**OID-23109: oidctl: instance parameter is missing.**

**Cause:** Instance name is missing.

**Action:** Provide the instance name and retry.

**Level:** 16

**Type:** ERROR

**Impact:** Process

**OID-23110: oidctl: Config set entry cn=configset%u,%s does not exist.**

**Cause:** An attempt was made to bring up an instance with a nonexistent configset entry.

**Action:** Ensure that the configset entry exists and retry.

**Level:** 16

**Type:** ERROR

**Impact:** Data

---

**OID-23111: oidctl: Invalid parameters passed in flags.**

**Cause:** Parameters passed in flags were invalid.

**Action:** Ensure that parameters in flags are valid and retry.

**Level:** 16

**Type:** ERROR

**Impact:** Process

**OID-23112: Key %s already in use.**

**Cause:** Multiple realms may be pointing to the same usersearchbase.

**Action:** Ensure that usersearchbase definitions in realms do not collide.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23113: In %s, failure cleaning up the change logs from supplier, %s to consumer, %s.**

**Cause:** See the associated error messages for the actual cause.

**Action:** More specific messages will accompany this message. Refer to the other messages for the appropriate action.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23116: %s : Memory allocation failed for %s.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Memory

**OID-23117: DispatcherController : OS : Error creating thread management queue.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Threads

**OID-23118: DispatcherController : OS : Error creating thread sync mutex.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

---

**Type:** ERROR

**Impact:** Threads

**OID-23119: DispatcherController : Error in creating dispatcher process server queue.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Process

**OID-23120: OS %d : Failed to enqueue in %s.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Operating System

**OID-23121: Unable to register %s.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Operating System

**OID-23122: Polling port failed with error %d.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Operating System

**OID-23123: DispatcherController : OS %d : Opening of communication control port failed.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Operating System

**OID-23124: The server with Process ID = %d is not running.**

**Cause:** The server process failed.

---

**Action:** Check the core dump or the stack trace and contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Process

**OID-23125: The server with Process ID=%d is not responsive; restarting the server.**

**Cause:** Server process is not responding because the system might be busy.

**Action:** The original unresponsive process will be killed.

**Level:** 16

**Type:** ERROR

**Impact:** Process

**OID-23127: OS Error -(%d) :Error in polling.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Operating System

**OID-23128: In gslsflAcceptConnAndSend, OS %d : unable to accept new TCP connection.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Operating System

**OID-23130: %s : OS %d : Setting up/attaching of shared memory failed.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Operating System

**OID-23132: ServerController : OS : Error creating internal queues.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

---

**Impact:** Operating System

**OID-23135: ServerController : OS : error initializing SM thread condition variable's mutex.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Operating System

**OID-23137: ServerController: hash table creation for user operations failed.**

**Cause:** System resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Operating System

**OID-23138: ServerController: error initializing r/w lock for user operations hash.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Operating System

**OID-23141: Signalling dispatcher thread failed.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Operating System

**OID-23142: No free connection available; dropping the connId = %d.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Operating System

**OID-23144: Exceeding maximum number of connections allowed. Num Conns = %d, Max Conns = %d, Closing the connection.**

---

**Cause:** The number of LDAP connections to OID server exceeded the maximum limit.

**Action:** Check for applications or users with leaked or improperly prolonged LDAP connections and perform the appropriate corrective actions. In addition, if deemed necessary, relaunch the OID server instance with more server processes in order to achieve adequate connection handling capacity.

**Level:** 16

**Type:** ERROR

**Impact:** Programmatic

**OID-23145: Socket fd=%d greater than system max=%d numconns=%d. Closing the connection.**

**Cause:** The number of sockets or file descriptors to OID server have reached system maximum limit.

**Action:** Check for system maximum number of file descriptors. Check for applications with leaked or improperly prolonged LDAP connections and perform the appropriate corrective actions. In addition, if deemed necessary, relaunch the OID server instance with more server processes in order to achieve adequate connection handling capacity.

**Level:** 16

**Type:** ERROR

**Impact:** Operating System

**OID-23147: ServerListener : OS %d : unable to contact dispatcher.**

**Cause:** Either the dispatcher failed or the administrator is initiating a shutdown.

**Action:** Check the core dump or stack trace. For further assistance contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Operating System

**OID-23148: ServerListener : Lost contact with dispatcher.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Operating System

**OID-23155: In gslsflInitnzoscontext, nzos initialization failed with NZ %d.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Operating System

---

**OID-23157: In gsIsfliInitnzoscontext, creation of nzos context failed.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Operating System

**OID-23158: In gsIsfliInitnzoscontext, failure initializing the DML context.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Operating System

**OID-23159: In gsIsfliInitnzoscontext, failure with NZ %d when opening wallet %s.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Operating System

**OID-23160: In gsIsfliInitnzoscontext, failure setting credentials in nzos context.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Operating System

**OID-23161: In gsIsfliInitnzoscontext, failure setting cipher choice in nzos context.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Operating System

**OID-23162: ServerWorker : OS : gslesioIBerAlloc failed.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16



---

**Type:** ERROR

**Impact:** Operating System

**OID-23163: Database connection is unavailable. Shutting down.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Operating System

**OID-23164: ServerWorker : OS : BER allocation failed.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Operating System

**OID-23165: ServerWorker : Received unknown operation tag.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Operating System

**OID-23166: In gslarswWorker, memory allocation of maxFiltSize = %d failed.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Memory

**OID-23167: Too many unique constraints: > %d.**

**Cause:** The number of unique constraints was larger than the maximum allowed.

**Action:** Reduce the number of unique constraints.

**Level:** 16

**Type:** ERROR

**Impact:** Configuration

**OID-23168: Database error in gsIsbaAddEntry [gsldpoOperationComplete].**

**Cause:** Commit or rollback failed.

**Action:** Check the database log and apply appropriate corrective measures.

---

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23169: In gslsbaAddEntry, entry cache update failed after commit to database.**

**Cause:** System Resource constraint.

**Action:** Check the database log and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23170: In gslsbaAddEntry, failure reallocating memory to modify subschema\_subentries attribute in backend struct.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Memory

**OID-23171: In gslbDeleteEntry, failure to remove subschemasubentry DN from Root DSE because memory allocation failed.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Memory

**OID-23172: In gslsbmModify, schema hash search failed for attr %s.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Memory

**OID-23173: In gslsbmdModifyDN, update of dynamic group memberships failed.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Memory

**OID-23174: In gslsbmdModifyDN, update of dynamic group DNs in cache failed.**

---

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Memory

**OID-23175: In gslsbmdModifyDN, reload of password policy failed.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Memory

**OID-23176: In gslsbmdModifyDN, error in deleting component subschema-subentry DN from root DSE entry.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Operating System

**OID-23177: In gslsbmdModifyDN, error in adding component subschema-subentry DN to root DSE entry.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Operating System

**OID-23178: In gslsbmdModifyDN, database error [gsldpoOperationComplete].**

**Cause:** Commit or roll back failed

**Action:** Check the database log and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23180: In gslsbmdModifyDN, error in orclacpgroup cache reload.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

---

**Type:** ERROR

**Impact:** Memory

**OID-23183: In gsldazb\_InsertAttrib, certificate hash generation failed (%d).**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Memory

**OID-23184: In gsldasaDbInsUserStats, hash table pointer for user %s operation is NULL.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Memory

**OID-23185: In gsldasaDbInsUserStats, Op: %s lcvb2werr() returned invalid base error for Eid string %s. Setting dummy value %d for Eid.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23186: In gsldasaDbInsUserStats, Op: %s \* lcvb2werr() returned overflow error for Eid string %s. Setting dummy value %d for Eid.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23187: In gsldasaDbInsUserStats, lcvb2werr() returned invalid input for Eid string %s. Setting dummy value %d for Eid.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Data

---

**OID-23188: In gsldasaDbInsUserStats, OpName: %s beginning of read-only iteration of 2nd level (comp obj) hash table has failed.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23189: In gsldasaDbInsUserStats, ORA-%d occurred while inserting compare (detail) SM stats.**

**Cause:** Database error occurred.

**Action:** Check the database log and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23190: In gsldasaDbInsUserStats, ORA-%d while inserting user stats.**

**Cause:** Database error occurred.

**Action:** Check the database log and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23191: In gsldasaDbInsUserStats, ORA-%d while inserting user stats. Error = %s.**

**Cause:** Database error occurred.

**Action:** Check the database log and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23192: In gsldbdbDelAttrBVal, size of binary attribute to be deleted exceeds the max supported size.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Compliance

**OID-23193: In gsldbdbDelAttrBVal, no value to delete for binary data.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

---

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23194: In gsldbc\_DelAttrBVal, failure retrieving certificate information (%d).**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23195: In gsldbc\_DelAttrBVal, failure converting certificate serial number from binary to base 64 encoded string (%d).**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Memory

**OID-23196: In gsldmf\_BVal2StrCertHashList, error generating certificate hash.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Memory

**OID-23197: In gsldusaGetCtxNmSpcParVal, ORA-%d:%s encountered.**

**Cause:** Database error occurred.

**Action:** Check the database log and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23198: In gslesrdBerGetNext, memory allocation failed len %d ber->ber\_len %d.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Memory

---

**OID-23199: In gsleswrrwRawWrite %d, writing to network failed due to hard or unknown error.**

**Cause:** Client is not responding after sending the operation request.

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Network

**OID-23201: OS %d : error spawning dispatcher thread.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Operating System

**OID-23202: In gslffiCGetSubstringFilter, substring filter is not supported for usercertificate binary attribute.**

**Cause:** Unsupported substring filter was provided for usercertificate attribute search.

**Action:** Provide valid filter for usercertificate attribute search.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**OID-23203: In gslffiGBldBinFltrSrchParam, either the separator is missing or the certificate match value in filter string %s is incomplete.**

**Cause:** Filter provided for certificate match value for usercertificate attribute search was invalid.

**Action:** Provide valid certificate match value for filter in usercertificate attribute search.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**OID-23204: Unsupported filter choice.**

**Cause:** Filter provided for the search operation was not supported or was unknown.

**Action:** Provide valid filter for the search operation and retry.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**OID-23205: In gslarswWorker, received HA down event. Requesting new DB connection.**

**Cause:** The database has gone down.

---

**Action:** No user action needed, OID will handle database connection failover automatically.

**Level:** 16

**Type:** ERROR

**Impact:** High Availability

**OID-23206: In gslarutbDequeueDBConnection, connection dequeued received HA down event. Creating new DB connection.**

**Cause:** Database has gone down.

**Action:** No user action needed, OID will handle database connection failover automatically.

**Level:** 16

**Type:** ERROR

**Impact:** High Availability

**OID-23207: In gsldhacHACallback, HA Callback Event Thread Id: %d Event type:**

**%d HA Source: %s Host name: %s Database name: %s Instance name: %s**

**Timestamp: %s Service name: %s HA status: %s**

**Cause:** Database has come up or gone down.

**Action:** No user action needed, OID will handle database connection failover automatically.

**Level:** 16

**Type:** ERROR

**Impact:** High Availability

**OID-23208: In gsluirscLoadSchema, error in %s %s line %d in gsluirscLoadSchema.**

**Cause:** Incorrect definition in schema.

**Action:** Correct the definition in schema.

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23209: In gsfliniInitnzoscontext, failure setting orclsslinteropmode flag in nzos context.**

**Cause:** System Resource constraint.

**Action:** Check the system resource utilization on the machine and apply appropriate corrective measures.

**Level:** 16

**Type:** ERROR

**Impact:** Operating System

**OID-23210: One or more of the required indexes (rp\_dn, st\_orclnormdn, ei\_attrstore) are missing. Server will operate in READ-MODIFY mode.**

**Cause:** bulkload index=true was not run.

**Action:** Run bulkload index=true to re-create the indexes.



---

**Level:** 16

**Type:** ERROR

**Impact:** Data

**OID-23211: In %s, failure to parse entry count control response. Server=%s, basedn=%s, scope=%s, filter=%s, attrs=%s, error=%s.**

**Cause:** An internal error occurred where the entry count control parsing failed.

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Session

**OID-23212: Failure accessing Oracle database (oracle errcode=%d).**

**Cause:** A database connection was terminated.

**Action:** Check if the database was shut down or check the database alert log for further details.

**Level:** 16

**Type:** ERROR

**Impact:** Session

**OID-23734: In %s, failure initializing synchronization lock, %s.**

**Cause:** An internal error occurred where the lock routine failed.

**Action:** Contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Session

**OID-23736: Replication DN password expired. Replication DN=%s and server=%s.**

**Cause:** The replication user's account has expired.

**Action:** Reset the replication DN password.

**Level:** 16

**Type:** ERROR

**Impact:** Security

**OID-23737: Replication DN account is locked. Replication DN=%s, Server=%s.**

**Cause:** The configured maximum consecutive bind failures allowed for Replication DN was exceeded.

**Action:** Unlock the replication DN account.

**Level:** 16

**Type:** ERROR

**Impact:** Security



---

## OPM-00500 to OPM-00745

**OPM-00500: Could not route request to specified scope.**

**Cause:** The specified scope was not found in the local OPMN server's table.

**Action:** \*Define: OPMN\_NLS\_UNRESOLVED\_SCOPE

**Level:**

**Type:**

**Impact:** Other

**OPM-00501: StartPset startpSet Proc %u:%u could not schedule new start (%s)**

**Cause:** A new process could not be started as part of an autostart dependency requirement.

**Action:** \*Define: OPMN\_NLS\_MSG\_00115

**Level:**

**Type:**

**Impact:** Other

**OPM-00502: Monitor Proc %u:%u invalid action: %d**

**Cause:** An internal OPMN process action state had an invalid value

**Action:** \*Define: OPMN\_NLS\_MSG\_00116

**Level:**

**Type:**

**Impact:** Other

**OPM-00503: DMS segment in the notification body has null element name or value.**

**Cause:** Invalid DMS data reported by client process.

**Action:** \*Define: OPMN\_NLS\_MSG\_00117

**Level:**

**Type:**

**Impact:** Other

**OPM-00504: Invalide DMS element name: %s**

**Cause:** Invalid DMS element name reported by client process.

**Action:** \*Define: OPMN\_NLS\_MSG\_00118

**Level:**

---

**Type:**

**Impact:** Other

**OPM-00505: module specific error**

**Cause:** The process module encountered an error: see the associated text.

**Action:** \*Define: OPMN\_NLS\_GENERIC\_MODULE

**Level:**

**Type:**

**Impact:** Other

**OPM-00506: RMD %s no duration for operator**

**Cause:** A duration resource could not be found for the operator.

**Action:** \*Define: OPMN\_RMD\_NO\_DURATION

**Level:**

**Type:**

**Impact:** Other

**OPM-00507: RMD %s conditional invalid time comparison**

**Cause:** A conditional contains a comparison of time value against another operand type.

**Action:** \*Define: OPMN\_RMD\_COND\_TIME\_COMPARE

**Level:**

**Type:**

**Impact:** Other

**OPM-00508: RMD %s conditional invalid integer comparison**

**Cause:** A conditional contains a comparison of an integer value against a non numerical value.

**Action:** \*Define: OPMN\_RMD\_COND\_INTEGER\_COMPARE

**Level:**

**Type:**

**Impact:** Other

**OPM-00509: Failed to create pm publisher.**

**Cause:** Internal error while creating an ONS publisher.

**Action:** \*Define: OPMN\_NLS\_MSG\_00123

**Level:**

**Type:**

**Impact:** Other

**OPM-00510: Failed to create pm monitor thread.**

**Cause:** Internal error while creating monitor thread for processes.

**Action:** \*Define: OPMN\_NLS\_MSG\_00124

**Level:**

---

**Type:**

**Impact:** Other

**OPM-00511: PROC\_READY subscription failed.%s%s**

**Cause:** Internal error while subscribing to client PROC\_READY notifications.

**Action:** \*Define: OPMN-NLS\_MSG\_00125

**Level:**

**Type:**

**Impact:** Other

**OPM-00512: Module %s: library load error:%s**

**Cause:** The shared library for the specified module could not be loaded.

**Action:** Check the path for the module in opmn.xml. \*Define: OPMN-NLS\_MSG\_00126

**Level:**

**Type:**

**Impact:** Other

**OPM-00513: Module %s: no initialization callback**

**Cause:** The specified module does not have an initialization function.

**Action:** Check the path for the module in opmn.xml. \*Define: OPMN-NLS\_MSG\_00127

**Level:**

**Type:**

**Impact:** Other

**OPM-00514: XML parse: %s, process-type: %s, module: %s is missing start callback.**

**Cause:** The module for the specified process type does not have an start function.

**Action:** Check the path for the module in opmn.xml. \*Define: OPMN-NLS\_MSG\_00128

**Level:**

**Type:**

**Impact:** Other

**OPM-00515: Module %s: cron interval configured but no cron function**

**Cause:** A cron interval has been configured for the specified module, but the module library does not have a cron function.

**Action:** Check the path for the module in opmn.xml or remove the configured cron interval for the module in opmn.xml. \*Define: OPMN-NLS\_MSG\_00129

**Level:**

**Type:**

**Impact:** Other

**OPM-00516: Module %s: critical module initialization failed.**

**Cause:** Initialization for a module configured as critical has failed.

**Action:** \*Define: OPMN-NLS\_MSG\_00130

---

**Level:**  
**Type:**  
**Impact:** Other

**OPM-00517: Module %s: initialization failed (base)**  
**Cause:** The module's initialization base call failed.  
**Action:** \*Define: OPMN-NLS\_MSG\_00131

**Level:**  
**Type:**  
**Impact:** Other

**OPM-00518: Module %s: initialization failed (proc type %s)**  
**Cause:** The module's initialization process-type call failed.  
**Action:** \*Define: OPMN-NLS\_MSG\_00132

**Level:**  
**Type:**  
**Impact:** Other

**OPM-00519: Module %s: initialization failed (proc set %s)**  
**Cause:** The module's initialization process-set call failed.  
**Action:** \*Define: OPMN-NLS\_MSG\_00133

**Level:**  
**Type:**  
**Impact:** Other

**OPM-00520: Create pm state directory: %s**  
**Cause:** The OPMN state directory will be created.  
**Action:** \*Define: OPMN-NLS\_MSG\_00134

**Level:**  
**Type:**  
**Impact:** Other

**OPM-00521: Failed to create pm state directory (%s): %s**  
**Cause:** The OPMN state directory could not be created.  
**Action:** Check the directory permissions to \$ORACLE\_HOME/opmn/logs or the id of the user attempting to start OPMN. \*Define: OPMN-NLS\_MSG\_00135

**Level:**  
**Type:**  
**Impact:** Other

**OPM-00522: PM state directory exists: %s**  
**Cause:** The OPMN state directory already exists.  
**Action:** \*Define: OPMN-NLS\_MSG\_00136

**Level:**

---

**Type:**

**Impact:** Other

**OPM-00523: Failed to create pm state file (%s): %s**

**Cause:** The OPMN state file could not be created.

**Action:** Check the directory permissions to \$ORACLE\_HOME/opmn/logs/state or the id of the user who started OPMN. \*Define: OPMN-NLS\_MSG\_00137

**Level:**

**Type:**

**Impact:** Other

**OPM-00524: Failed to create static process state file (%s): %s**

**Cause:** The OPMN process static state file could not be created.

**Action:** Check the directory permissions to \$ORACLE\_HOME/opmn/logs/state or the id of the user who started OPMN. \*Define: OPMN-NLS\_MSG\_00138

**Level:**

**Type:**

**Impact:** Other

**OPM-00525: Proc %u:%u rename (%s) %s to %s**

**Cause:** The rename of the process static state file to the process specific state file failed.

**Action:** Check the directory permissions to \$ORACLE\_HOME/opmn/logs/state or the id of the user who started OPMN. \*Define: OPMN-NLS\_MSG\_00139

**Level:**

**Type:**

**Impact:** Other

**OPM-00526: PM state file does not exist: %s**

**Cause:** The OPMN state file does not exist.

**Action:** \*Define: OPMN-NLS\_MSG\_00140

**Level:**

**Type:**

**Impact:** Other

**OPM-00527: Failed to open pm state directory (%s): %s**

**Cause:** The OPMN state directory could not be opened.

**Action:** Check the directory permissions to \$ORACLE\_HOME/opmn/logs/state or the id of the user who started OPMN. \*Define: OPMN-NLS\_MSG\_00141

**Level:**

**Type:**

**Impact:** Other

**OPM-00528: Recovery: Proc %u:%u -- %s: line %d\tError on %s**

**Cause:** An error was encountered at the given line of the process state file.

**Action:** \*Define: OPMN-NLS\_MSG\_00143

---

**Level:**

**Type:**

**Impact:** Other

**OPM-00529: Recovery: %s: %s**

**Cause:** The process state file could not be accessed.

**Action:** Check the directory permissions to \$ORACLE\_HOME/opmn/logs/state or the id of the user who started OPMN. \*Define: OPMN-NLS\_MSG\_00144

**Level:**

**Type:**

**Impact:** Other

**OPM-00530: Recovery: Proc %u:%u -- process-set not found\t%s, %s, %s, %s**

**Cause:** The given process-set for the given process is no longer configured.

**Action:** \*Define: OPMN-NLS\_MSG\_00146

**Level:**

**Type:**

**Impact:** Other

**OPM-00531: Recovery: Proc %u:%u configuration disabled -- stopping**

**Cause:** The given process is being stopped as part of OPMN recovery.

**Action:** \*Define: OPMN-NLS\_MSG\_00147

**Level:**

**Type:**

**Impact:** Other

**OPM-00532: Recovery: Proc %u:%u port configuration conflict -- stopping**

**Cause:** The given process' ports now conflict with what is configured in opmn.xml.

**Action:** \*Define: OPMN-NLS\_MSG\_00148

**Level:**

**Type:**

**Impact:** Other

**OPM-00533: Rename (%s) %s to %s**

**Cause:** The rename of the process state file to a stale process state file failed.

**Action:** Check the directory permissions to \$ORACLE\_HOME/opmn/logs/state or the id of the user who started OPMN. \*Define: OPMN-NLS\_MSG\_00149

**Level:**

**Type:**

**Impact:** Other

**OPM-00534: Recovery: Proc %u:%u numprocs/maxprocs configuration exceeded -- stopping**



---

**Cause:** The given process will be stopped because the configured number of processes for its process-set is now exceeded.

**Action:** \*Define: OPMN-NLS\_MSG\_00150

**Level:**

**Type:**

**Impact:** Other

**OPM-00535: Failed to create %s notification for %u**

**Cause:** OPMN could not create a notification for the specified process event.

**Action:** \*Define: OPMN-NLS\_MSG\_00151

**Level:**

**Type:**

**Impact:** Other

**OPM-00536: Job %x %u result:%s**

**Cause:** Log of an OPMN internal job result.

**Action:** \*Define: OPMN-NLS\_MSG\_00152

**Level:**

**Type:**

**Impact:** Other

**OPM-00537: Sched SyncExit: monitor timed out**

**Cause:** Shutdown wait for monitor thread timed out.

**Action:** \*Define: OPMN-NLS\_MSG\_00153

**Level:**

**Type:**

**Impact:** Other

**OPM-00538: RMD %s conditional invalid floating point comparison**

**Cause:** A conditional contains a comparison of a floating point value against a non numerical value.

**Action:** \*Define: OPMN\_RMD\_COND\_FLOAT\_COMPARE

**Level:**

**Type:**

**Impact:** Other

**OPM-00539: Pm/Ons confirm subscription failed: %sSubscription: %s**

**Cause:** Creation of ONS subscription for ONS queue drain detection failed.

**Action:** \*Define: OPMN-NLS\_MSG\_00155

**Level:**

**Type:**

**Impact:** Other

**OPM-00540: Pm/Ons confirm notification create failed**

---

**Cause:** Creation of ONS notification for ONS queue drain detection failed.

**Action:** \*Define: OPMN-NLS\_MSG\_00156

**Level:**

**Type:**

**Impact:** Other

**OPM-00541: Pm/Ons confirm notification timeout**

**Cause:** Shutdown wait for ONS queue drain timed out.

**Action:** \*Define: OPMN-NLS\_MSG\_00157

**Level:**

**Type:**

**Impact:** Other

**OPM-00542: Request response socket send error: %s**

**Cause:** ONS request response socket write failed.

**Action:** \*Define: OPMN-NLS\_MSG\_00159

**Level:**

**Type:**

**Impact:** Other

**OPM-00543: ONSpmInfoUtil: request %x timed out**

**Cause:** The given remote request timed out.

**Action:** \*Define: OPMN-NLS\_MSG\_00160

**Level:**

**Type:**

**Impact:** Other

**OPM-00544: ONSpmInfoUtil: remote dependency instance name %s was not found**

**Cause:** No OPMN server could be mapped to the given managed process dependency.

**Action:** The remote OPMN server may be down, or an invalid ias instance was configured for the dependency in opmn.xml. \*Define: OPMN-NLS\_MSG\_00161

**Level:**

**Type:**

**Impact:** Other

**OPM-00545: RMD %s conditional invalid string operator**

**Cause:** A conditional contains a string operand with a operator other than = or != .

**Action:** \*Define: OPMN-RMD\_COND\_STRING\_OPERATOR

**Level:**

**Type:**

**Impact:** Other

**OPM-00546: RMD %s conditional invalid string comparison**

---

**Cause:** A conditional contains a comparison of string value against another operand type.

**Action:** \*Define: OPMN\_RMD\_COND\_STRING\_COMPARE

**Level:**

**Type:**

**Impact:** Other

**OPM-00547: RMD %s exec failed (%s) for %s**

**Cause:** The execution of an RMD action failed.

**Action:** \*Define: OPMN\_RMD\_EXEC\_FAILED

**Level:**

**Type:**

**Impact:** Other

**OPM-00548: RMD %s exec error (%s) for %s**

**Cause:** The execution of an RMD action encountered the given error.

**Action:** \*Define: OPMN\_RMD\_EXEC\_ERROR

**Level:**

**Type:**

**Impact:** Other

**OPM-00549: RMD %s exec exited with non 0 status (%d) for %s**

**Cause:** The execution of an RMD action exited with a non 0 code.

**Action:** \*Define: OPMN\_RMD\_EXEC\_STATUS

**Level:**

**Type:**

**Impact:** Other

**OPM-00550:**

**Cause:**

**Action:** \*Define: OPMN\_PM\_UNUSED1

**Level:**

**Type:**

**Impact:** Other

**OPM-00551:**

**Cause:**

**Action:** \*Define: OPMN\_PM\_UNUSED2

**Level:**

**Type:**

**Impact:** Other

**OPM-00552: RMD %s could not create request thread for %s**

**Cause:** A thread could not be created to execute the request.

---

**Action:** \*Define: OPMN\_RMD\_REQ\_THREAD

**Level:**

**Type:**

**Impact:** Other

**OPM-00553: RMD %s request error code %d for %s**

**Cause:** An action or exception request returned the given error code.

**Action:** \*Define: OPMN\_RMD\_REQ\_ERROR

**Level:**

**Type:**

**Impact:** Other

**OPM-00554:**

**Cause:**

**Action:** \*Define: OPMN\_PM\_UNUSED3

**Level:**

**Type:**

**Impact:** Other

**OPM-00555: Comp code contains invalid brace syntax**

**Cause:** The comp parameter has invalid syntax for ons[] or pm[].

**Action:** \*Define: OPMN-NLS\_DEBUG\_COMPOPEN

**Level:**

**Type:**

**Impact:** Other

**OPM-00556: Debug \"all\" component code can not be negated**

**Cause:** The "all" component code can not be negated.

**Action:** \*Define: OPMN-NLS\_DEBUG\_NEGALL

**Level:**

**Type:**

**Impact:** Other

**OPM-00557: invalid error code.**

**Cause:** Internal request error code is set to an invalid value.

**Action:** \*Define: OPMN-NLS\_NONE

**Level:**

**Type:**

**Impact:** Other

**OPM-00558: module specified no arguments for process creation**

**Cause:** A module did not specify arguments for process creation.

**Action:** \*Define: OPMN-NLS\_NOSTARTARGS

---

**Level:**

**Type:**

**Impact:** Other

**OPM-00559: working directory not set for an un-managed process**

**Cause:** A module did not specify a working directory for process creation.

**Action:** \*Define: OPMN\_NLS\_WORKDIR

**Level:**

**Type:**

**Impact:** Other

**OPM-00560: can not use working directory**

**Cause:** A module specified an invalid working directory for process creation.

**Action:** \*Define: OPMN\_NLS\_BAD\_WORKDIR

**Level:**

**Type:**

**Impact:** Other

**OPM-00561: stdin descriptor can not be OpmnPathDefault**

**Cause:** A module tried to specify the default io path as stdin for process creation.

**Action:** \*Define: OPMN\_NLS\_STDIN

**Level:**

**Type:**

**Impact:** Other

**OPM-00562: stdout descriptor can not be OpmnPathDefault for an un-managed process**

**Cause:** A module tried to specify the default io path for an unmanaged process.

**Action:** \*Define: OPMN\_NLS\_STDOUT

**Level:**

**Type:**

**Impact:** Other

**OPM-00563: stderr descriptor can not be OpmnPathDefault for an un-managed process**

**Cause:** A module tried to specify the default io path for an unmanaged process.

**Action:** \*Define: OPMN\_NLS\_STDERR

**Level:**

**Type:**

**Impact:** Other

**OPM-00564: file name is empty**

**Cause:** A module specified a zero length file name for process creation.

**Action:** \*Define: OPMN\_NLS\_FILENAME

---

**Level:**

**Type:**

**Impact:** Other

**OPM-00565: time out while waiting for a process to exit**

**Cause:** A time out occurred while waiting for a child process to exit.

**Action:** \*Define: OPMN-NLS\_WAIT\_TIMEOUT

**Level:**

**Type:**

**Impact:** Other

**OPM-00566: no port available from the port range**

**Cause:** No port was available from the configured port range.

**Action:** \*Define: OPMN-NLS\_PORT\_NOT\_FOUND

**Level:**

**Type:**

**Impact:** Other

**OPM-00567: failed to set the process status to ProcStatusAlive**

**Cause:** A module could not set a process status to Alive.

**Action:** \*Define: OPMN-NLS\_SET\_ALIVE

**Level:**

**Type:**

**Impact:** Other

**OPM-00568: failed to set the process status to ProcStatusBounce**

**Cause:** A module could not set a process status to Bounce.

**Action:** \*Define: OPMN-NLS\_SET\_BOUNCE

**Level:**

**Type:**

**Impact:** Other

**OPM-00569: failed to set the process status to ProcStatusBounceFail**

**Cause:** A module could not set a process status to Bounce Failed.

**Action:** \*Define: OPMN-NLS\_SET\_BOUNCEFAIL

**Level:**

**Type:**

**Impact:** Other

**OPM-00570: failed to set the process status to ProcStatusRestart**

**Cause:** A module could not set a process status to Restart.

**Action:** \*Define: OPMN-NLS\_SET\_RESTART

**Level:**

**Type:**

---

**Impact:** Other

**OPM-00571: failed to set the process status to ProcStatusInitFail**

**Cause:** A module could not set a process status to Init Failed.

**Action:** \*Define: OPMN\_NLS\_SET\_INITFAIL

**Level:**

**Type:**

**Impact:** Other

**OPM-00572: Debug unknown ons component code**

**Cause:** An unknown component code was specified within the ons[] field.

**Action:** \*Define: OPMN\_NLS\_DEBUG\_ONS\_UNKNOWN

**Level:**

**Type:**

**Impact:** Other

**OPM-00573: failed to schedule a start job for the managed process**

**Cause:** A module could not schedule a start job for the managed process.

**Action:** \*Define: OPMN\_NLS\_SCHED\_START\_JOB

**Level:**

**Type:**

**Impact:** Other

**OPM-00574: failed to schedule a stop job for the managed process**

**Cause:** A module could not schedule a stop job for the managed process.

**Action:** \*Define: OPMN\_NLS\_SCHED\_STOP\_JOB

**Level:**

**Type:**

**Impact:** Other

**OPM-00575: failed to schedule a restart job for the managed process**

**Cause:** A module could not schedule a restart job for the managed process.

**Action:** \*Define: OPMN\_NLS\_SCHED\_RESTART\_JOB

**Level:**

**Type:**

**Impact:** Other

**OPM-00576: failed to start a managed process after the maximum retry limit**

**Cause:** A managed process failed to start after the configured maximum number of retries was reached.

**Action:** \*Define: OPMN\_NLS\_START\_REACH\_RETRY

**Level:**

**Type:**

**Impact:** Other

---

**OPM-00577: time out while waiting for a managed process to start**

**Cause:** A managed process failed to start within the configured time out period.

**Action:** \*Define: OPMN-NLS\_START\_TIMEOUT

**Level:**

**Type:**

**Impact:** Other

**OPM-00578: failed to restart a managed process after the maximum retry limit**

**Cause:** A managed process failed to restart after the configured maximum number of retries was reached.

**Action:** \*Define: OPMN-NLS\_RESTART\_REACH\_RETRY

**Level:**

**Type:**

**Impact:** Other

**OPM-00579: time out while waiting for a managed process to restart**

**Cause:** A managed process failed to restart within the configured time out period.

**Action:** \*Define: OPMN-NLS\_RESTART\_TIMEOUT

**Level:**

**Type:**

**Impact:** Other

**OPM-00580: time out while waiting for a managed process to stop**

**Cause:** A managed process failed to stop within the configured time out period.

**Action:** \*Define: OPMN-NLS\_STOP\_TIMEOUT

**Level:**

**Type:**

**Impact:** Other

**OPM-00581: unknown module parse error**

**Cause:** A module specified an unknown error while parsing a request.

**Action:** \*Define: OPMN-NLS\_MOD\_PARSE

**Level:**

**Type:**

**Impact:** Other

**OPM-00582: no processes or applications matched this request**

**Cause:** The request matched no managed processes or applications.

**Action:** \*Define: OPMN-NLS\_NO\_MATCH\_PROC

**Level:**

**Type:**

**Impact:** Other

**OPM-00583: Unknown parameter for this request**



---

**Cause:** The specified parameter for the request is not valid for the command.

**Action:** Check the request argument list for errors. \*Define: OPMN-NLS\_UNKNOWN\_PARAMETER

**Level:**

**Type:**

**Impact:** Other

**OPM-00584: not enabled**

**Cause:** The specified feature is not enabled.

**Action:** \*Define: OPMN-NLS\_NOT\_ENABLED

**Level:**

**Type:**

**Impact:** Other

**OPM-00585: OPMN is terminating**

**Cause:** The request was rejected because OPMN is terminating.

**Action:** \*Define: OPMN-NLS\_PM\_TERMINATE

**Level:**

**Type:**

**Impact:** Other

**OPM-00586: no enabled components for this request**

**Cause:** A request was issued for an ias component, process type or process set that was not enabled.

**Action:** \*Define: OPMN-NLS\_NO\_ENABLED\_PROC

**Level:**

**Type:**

**Impact:** Other

**OPM-00587: database dependency failed**

**Cause:** A dependency check on a database failed.

**Action:** \*Define: OPMN-NLS\_DATABASE\_DEPEND\_FAILED

**Level:**

**Type:**

**Impact:** Other

**OPM-00588: osso dependency failed**

**Cause:** A dependency check on an OSSO server failed.

**Action:** \*Define: OPMN-NLS\_OSSO\_DEPEND\_FAILED

**Level:**

**Type:**

**Impact:** Other

**OPM-00589: oid dependency failed**

---

**Cause:** A dependency check on an OID server failed.

**Action:** \*Define: OPMN-NLS\_OID\_DEPEND\_FAILED

**Level:**

**Type:**

**Impact:** Other

**OPM-00590: managed-process dependency failed**

**Cause:** A dependency check on a managed process failed.

**Action:** \*Define: OPMN-NLS\_UNIT\_DEPEND\_FAILED

**Level:**

**Type:**

**Impact:** Other

**OPM-00591: module dependency failed**

**Cause:** A dependency check on a module failed.

**Action:** \*Define: OPMN-NLS\_MODULE\_DEPEND\_FAILED

**Level:**

**Type:**

**Impact:** Other

**OPM-00592: dependency initiated stop**

**Cause:** A stop of a managed process was initiated via a configured dependency with autostop.

**Action:** \*Define: OPMN-NLS\_DEPEND\_STOP

**Level:**

**Type:**

**Impact:** Other

**OPM-00593: dependency initiated restart**

**Cause:** A restart of a managed process was initiated via a configured dependency with autorestart.

**Action:** \*Define: OPMN-NLS\_DEPEND\_RESTART

**Level:**

**Type:**

**Impact:** Other

**OPM-00594: Unknown remote ias instance.**

**Cause:** A managed process dependency is configured with an ias instance not managed by this OPMN server nor any other OPMN server currently connected to this one.

**Action:** \*Define: OPMN-NLS\_DEPEND\_UNKNOWN\_REMOTE

**Level:**

**Type:**

**Impact:** Other

---

**OPM-00595: Request command must begin with '/'.**

**Cause:** The OPMN http request command must begin with a forward slash.

**Action:** \*Define: OPMN\_NLS\_REQ\_BEGINSYNTAX

**Level:**

**Type:**

**Impact:** Other

**OPM-00596: Invalid ping syntax.**

**Cause:** The OPMN ping request has invalid syntax.

**Action:** \*Define: OPMN\_NLS\_REQ\_PINGSYNTAX

**Level:**

**Type:**

**Impact:** Other

**OPM-00597: Scope is invalid with ping request.**

**Cause:** Request scope may not be configured with a ping request.

**Action:** \*Define: OPMN\_NLS\_REQ\_PINGSCOPE

**Level:**

**Type:**

**Impact:** Other

**OPM-00598: Ping succeeded.**

**Cause:** The ping request succeeded.

**Action:** \*Define: OPMN\_NLS\_REQ\_PINGSUCCESS

**Level:**

**Type:**

**Impact:** Other

**OPM-00599: Command can only be: start, stop, restart, quiesc, ping, reload, shutdown, dump, set, query, module or debug.**

**Cause:** Only the specified requests are supported by OPMN.

**Action:** \*Define: OPMN\_NLS\_REQ\_BADCOMMAND

**Level:**

**Type:**

**Impact:** Other

**OPM-00600: Unknown command**

**Cause:** The specified command is not supported by OPMN.

**Action:** \*Define: OPMN\_NLS\_REQ\_UNKNOWNCOMMAND

**Level:**

**Type:**

**Impact:** Other

**OPM-00601: Invalid parameter: %sParameters must be of the form 'key=value'**

---

**Cause:** OPMN request parameters must be of the specified form.

**Action:** \*Define: OPMN\_NLS\_REQ\_INVALIDPARAM

**Level:**

**Type:**

**Impact:** Other

**OPM-00602: Communication error with the OPMN server local port. Check the OPMN log files**

**Cause:** The request client could not connect with the OPMN server, or lost connection with the OPMN server.

**Action:** Check that ORACLE\_HOME is set correctly, or check the OPMN log files.

\*Define: OPMN\_NLS\_REQ\_COMMERR

**Level:**

**Type:**

**Impact:** Other

**OPM-00603: Format of parameters for this request is incorrect.**

**Cause:** The format of the parameters for this request is incorrect.

**Action:** \*Define: OPMN\_NLS\_REQ\_PARAMFORMAT

**Level:**

**Type:**

**Impact:** Other

**OPM-00604: No name for a parameter: syntax is name=value.**

**Cause:** The parameter is missing the name field.

**Action:** \*Define: OPMN\_NLS\_REQ\_PARAMNONAME

**Level:**

**Type:**

**Impact:** Other

**OPM-00605: Missing ']'.**

**Cause:** The special name=[value] parameter syntax is missing the closing brace.

**Action:** \*Define: OPMN\_NLS\_REQ\_PARAMNOCLOSE

**Level:**

**Type:**

**Impact:** Other

**OPM-00606: Bad format for name=[value] parameter.**

**Cause:** The special name=[value] parameter syntax is invalid.

**Action:** \*Define: OPMN\_NLS\_REQ\_PARAMBAD SQUARE

**Level:**

**Type:**

**Impact:** Other

---

**OPM-00607: No value for a parameter: syntax is name=value.**

**Cause:** The parameter is missing the value field.

**Action:** \*Define: OPMN-NLS\_REQ\_PARAMNOVALUE

**Level:**

**Type:**

**Impact:** Other

**OPM-00608: A duplicate dmsarg was specified.**

**Cause:** Only one dmsarg option is allowed per request.

**Action:** \*Define: OPMN-NLS\_REQ\_DUPDMSARG

**Level:**

**Type:**

**Impact:** Other

**OPM-00609: Mode can only be: async or sync.**

**Cause:** The request mode may only be async or sync.

**Action:** \*Define: OPMN-NLS\_REQ\_BADMODE

**Level:**

**Type:**

**Impact:** Other

**OPM-00610: Timeout must be >= 15.**

**Cause:** The timeout value must be greater than or equal to 15.

**Action:** \*Define: OPMN-NLS\_REQ\_BADTIMEOUT

**Level:**

**Type:**

**Impact:** Other

**OPM-00611: Debug unknown pm component code**

**Cause:** An unknown component code was specified within the pm[] field.

**Action:** \*Define: OPMN-NLS\_DEBUG\_PM\_UNKNOWN

**Level:**

**Type:**

**Impact:** Other

**OPM-00612: Uniqueid must be > 0.**

**Cause:** The uniqueid value must be greater than 0.

**Action:** \*Define: OPMN-NLS\_REQ\_BADUID

**Level:**

**Type:**

**Impact:** Other

**OPM-00613: Interval is only allowed for dump and debug.**

**Cause:** The interval parameter is only allowed for dump and debug commands.

---

**Action:** \*Define: OPMN-NLS\_REQ\_INTERVALUSAGE

**Level:**

**Type:**

**Impact:** Other

**OPM-00614: Interval must be > 0.**

**Cause:** The interval value must be greater than 0.

**Action:** \*Define: OPMN-NLS\_REQ\_BADINTERVAL

**Level:**

**Type:**

**Impact:** Other

**OPM-00615: Count is only allowed for dump and debug.**

**Cause:** The count parameter is only allowed for dump and debug commands.

**Action:** \*Define: OPMN-NLS\_REQ\_COUNTUSAGE

**Level:**

**Type:**

**Impact:** Other

**OPM-00616: Count must be > 0.**

**Cause:** The count value must be greater than 0.

**Action:** \*Define: OPMN-NLS\_REQ\_BADCOUNT

**Level:**

**Type:**

**Impact:** Other

**OPM-00617: Debug specific module negation with no modules selected.**

**Cause:** A specific module or list of modules was negated without first selecting all modules.

**Action:** \*Define: OPMN-NLS\_DEBUG\_PM\_NEGMOD

**Level:**

**Type:**

**Impact:** Other

**OPM-00618: Numprocs must be > 0.**

**Cause:** The numprocs value must be greater than 0.

**Action:** \*Define: OPMN-NLS\_REQ\_BADNUMPROCS

**Level:**

**Type:**

**Impact:** Other

**OPM-00619: Unknown component code.**

**Cause:** The comp parameter contains an unknown component code.

**Action:** \*Define: OPMN-NLS\_DEBUG\_COMP

---

**Level:**

**Type:**

**Impact:** Other

**OPM-00620: A uniqueid may not be specified with process scope parameters.**

**Cause:** The uniqueid parameter may not be specified with other process scope parameters (such as process-set, for example).

**Action:** \*Define: OPMN\_NLS\_REQ\_UIDSCOPE

**Level:**

**Type:**

**Impact:** Other

**OPM-00621: Both interval and count must be set or neither.**

**Cause:** Both the interval and count parameters must be used together.

**Action:** \*Define: OPMN\_NLS\_REQ\_INTERVALCOUNT

**Level:**

**Type:**

**Impact:** Other

**OPM-00622: A process set must be explicitly specified with numprocs.**

**Cause:** For the numprocs parameter a process-set configured with min/max procs must be specified as part of the request.

**Action:** \*Define: OPMN\_NLS\_REQ\_FULLNUMPROCS

**Level:**

**Type:**

**Impact:** Other

**OPM-00623: Unknown parameters for this request.**

**Cause:** Unknown parameters were specified for this request.

**Action:** \*Define: OPMN\_NLS\_REQ\_PARAMUNKNOWN

**Level:**

**Type:**

**Impact:** Other

**OPM-00624: Invalid request state.**

**Cause:** The request state is invalid because the specified target can no longer be acted upon.

**Action:** \*Define: OPMN\_NLS\_REQ\_INVALIDSTATE

**Level:**

**Type:**

**Impact:** Other

**OPM-00625: No process matched the given uniqueid.**

**Cause:** The uniqueid value did not match a managed process.

**Action:** \*Define: OPMN\_NLS\_REQ\_UIDNOMATCH

---

**Level:**

**Type:**

**Impact:** Other

**OPM-00626: No processes or applications match the specified configuration.**

**Cause:** No managed processes or applications matched the request parameters.

**Action:** \*Define: OPMN-NLS\_REQ\_NOPROC

**Level:**

**Type:**

**Impact:** Other

**OPM-00627: Unknown server error**

**Cause:** The server encountered an error while processing the request.

**Action:** \*Define: OPMN-NLS\_REQ\_SERVERERRORUNKNOWN

**Level:**

**Type:**

**Impact:** Other

**OPM-00628: Request timed-out**

**Cause:** The request timed out in the server.

**Action:** \*Define: OPMN-NLS\_REQ\_RESPTIMEOUT

**Level:**

**Type:**

**Impact:** Other

**OPM-00629: Bad request**

**Cause:** The request is bad.

**Action:** Check the request syntax, scope, command and parameters. \*Define: OPMN-NLS\_REQ\_RESPBADREQ

**Level:**

**Type:**

**Impact:** Other

**OPM-00630: Unacceptable request**

**Cause:** The request can not be processed on the server.

**Action:** Either no processes or applications matched the request on the server, or the remote request was rejected for security reasons. \*Define: OPMN-NLS\_REQ\_RESPUNACCREQ

**Level:**

**Type:**

**Impact:** Other

**OPM-00631: Request partial success**

**Cause:** Some of the managed processes responded successfully to the request.

**Action:** \*Define: OPMN-NLS\_REQ\_RESPPARTSUCCESS



---

**Level:**

**Type:**

**Impact:** Other

**OPM-00632: Request failure**

**Cause:** None of the managed processes responded successfully to the request.

**Action:** \*Define: OPMN\_NLS\_REQ\_RESPFAILURE

**Level:**

**Type:**

**Impact:** Other

**OPM-00633: Server error**

**Cause:** An internal server error was encountered while processing the request.

**Action:** \*Define: OPMN\_NLS\_REQ\_RESPSERVERERROR

**Level:**

**Type:**

**Impact:** Other

**OPM-00634: Mangled server response**

**Cause:** The server request response is in an unknown format.

**Action:** \*Define: OPMN\_NLS\_REQ\_RESPMANGLEDSEVER

**Level:**

**Type:**

**Impact:** Other

**OPM-00635: Debug specific module with all modules already selected.**

**Cause:** A specific module or list of modules was selected after all modules were selected.

**Action:** \*Define: OPMN\_NLS\_DEBUG\_PM\_DUPMOD

**Level:**

**Type:**

**Impact:** Other

**OPM-00636: DMS is not enabled in OPMN.**

**Cause:** DMS metrics are not enabled in this OPMN server.

**Action:** \*Define: OPMN\_NLS\_DMS\_DISABLED

**Level:**

**Type:**

**Impact:** Other

**OPM-00637: : specified scope instance name not found.**

**Cause:** The given instance name specified in the scope of the request was not found.

**Action:** \*Define: OPMN\_NLS\_REQ\_SCOPEINSTANCENOTFOUND

---

**Level:**

**Type:**

**Impact:** Other

**OPM-00638: The specified option is not valid with this request type**

**Cause:** A module specific option was given which is not supported by the request.

**Action:** \*Define: OPMN-NLS\_REQ\_INVALIDACTION

**Level:**

**Type:**

**Impact:** Other

**OPM-00639: Invalid scope instance list syntax.**

**Cause:** The syntax of the instance list option for request scope is instance:<instance name>:<instance name>...

**Action:** \*Define: OPMN-NLS\_REQ\_SCOPEINSTANCEBADFORMAT

**Level:**

**Type:**

**Impact:** Other

**OPM-00640: Invalid combination of component target options**

**Cause:** A module specific option was given that was mutually exclusive with the given process target options (ias-component, process-type, process-set, etc.).

**Action:** \*Define: OPMN-NLS\_REQ\_INVALIDTARGETS

**Level:**

**Type:**

**Impact:** Other

**OPM-00641: Scope must be instance, cluster or \*.**

**Cause:** The request scope must specify one of the given identifiers.

**Action:** \*Define: OPMN-NLS\_REQ\_SCOPEINVALID

**Level:**

**Type:**

**Impact:** Other

**OPM-00642: Remote request with weak authentication.**

**Cause:** The request was run remotely, but the wallet file is not secure: it is either an example wallet file or does not have a password.

**Action:** Replace the wallet-file specification in opmn.xml with the path to a real, secure wallet file. \*Define: OPMN-NLS\_REQ\_AUTH\_WEAK

**Level:**

**Type:**

**Impact:** Other

**OPM-00643: Oracle SSL/authentication libraries were not found**

---

**Cause:** The Oracle core SSL/authentication libraries were not found.

**Action:** Make sure the core Oracle libraries have been installed. \*Define: OPMN\_NLS\_SSL\_NOLIBS

**Level:**

**Type:**

**Impact:** Other

**OPM-00644: The connection SSL initialization failed**

**Cause:** The connection SSL initialization failed.

**Action:** \*Define: OPMN\_NLS\_SSL\_INITFAILED

**Level:**

**Type:**

**Impact:** Other

**OPM-00645: The connection authentication failed**

**Cause:** The connection authentication failed.

**Action:** Check the configured wallet file path and password. \*Define: OPMN\_NLS\_SSL\_WALLETFAILED

**Level:**

**Type:**

**Impact:** Other

**OPM-00646: The connection SSL/authentication handshake failed**

**Cause:** The connection SSL/authentication handshake failed.

**Action:** \*Define: OPMN\_NLS\_SSL\_CONNECTFAILED

**Level:**

**Type:**

**Impact:** Other

**OPM-00647: Remote request refused because authentication is not configured:%s**

**Cause:** OPMN has not been configured to use authentication when connecting to other OPMN servers, and so remote requests for stop, restart, stop and shutdown are not allowed.

**Action:** \*Define: OPMN\_NLS\_REQ\_REFUSED

**Level:**

**Type:**

**Impact:** Other

**OPM-00648: The connection send failed**

**Cause:** The connection send failed.

**Action:** \*Define: OPMN\_NLS\_SSL\_SNDFAILED

**Level:**

**Type:**

**Impact:** Other

---

**OPM-00649: The connection receive failed**

**Cause:** The connection receive failed.

**Action:** \*Define: OPMN-NLS\_SSL\_RCVFAILED

**Level:**

**Type:**

**Impact:** Other

**OPM-00650: The connection send timed out**

**Cause:** The connection send timed out.

**Action:** \*Define: OPMN-NLS\_SSL\_SNDTIMEDOUT

**Level:**

**Type:**

**Impact:** Other

**OPM-00651: The connection receive timed out**

**Cause:** The connection receive timed out.

**Action:** \*Define: OPMN-NLS\_SSL\_RCVTIMEDOUT

**Level:**

**Type:**

**Impact:** Other

**OPM-00652: An IO request on a pipe timed out**

**Cause:** An IO request on a pipe timed out.

**Action:** \*Define: OPMN-NLS\_PIPE\_IOTIMEOUT

**Level:**

**Type:**

**Impact:** Other

**OPM-00653: The event script is not executable**

**Cause:** The event script does not have execute permission.

**Action:** \*Define: OPMN-NLS\_SCRIPT\_NOEXEC

**Level:**

**Type:**

**Impact:** Other

**OPM-00654: The event script timed out**

**Cause:** The event script timed out.

**Action:** \*Define: OPMN-NLS\_SCRIPT\_TIMEDOUT

**Level:**

**Type:**

**Impact:** Other

**OPM-00655: failed to start a managed process because a dependency check failed**

**Cause:** A managed process was not started because a dependency check failed.

---

**Action:** \*Define: OPMN-NLS\_START\_DEPEND\_FAIL

**Level:**

**Type:**

**Impact:** Other

**OPM-00656: failed to start a managed process because the event-script failed**

**Cause:** A managed process was not started because the event-script failed.

**Action:** \*Define: OPMN-NLS\_START\_SCRIPT\_FAIL

**Level:**

**Type:**

**Impact:** Other

**OPM-00657: failed to restart a managed process because a dependency check failed**

**Cause:** A managed process was not restarted because a dependency check failed.

**Action:** \*Define: OPMN-NLS\_RESTART\_DEPEND\_FAIL

**Level:**

**Type:**

**Impact:** Other

**OPM-00658: failed to restart a managed process because an event-script failed**

**Cause:** A managed process was not restarted because an event-script failed.

**Action:** \*Define: OPMN-NLS\_RESTART\_SCRIPT\_FAIL

**Level:**

**Type:**

**Impact:** Other

**OPM-00659: failed to stop a managed process because the event-script failed**

**Cause:** A managed process was not stopped because the event-script failed.

**Action:** \*Define: OPMN-NLS\_STOP\_SCRIPT\_FAIL

**Level:**

**Type:**

**Impact:** Other

**OPM-00660: Process Crashed: %s~%s~%s~%u (%u:%u) - Restarting**

**Cause:** Process no longer visible from the OS, will be restarted

**Action:** Examine console log associated with the process and examine logs maintained by the component. \*Define: OPMN-NLS\_MSG\_00258

**Level:**

**Type:**

**Impact:** Other

**OPM-00661: Process Crashed: %s~%s~%s~%u (%u:%u) - Not restarting**

**Cause:** Process no longer visible from the OS, will not be restarted

---

**Action:** Examine console log associated with the process and examine logs maintained by the component. An explicit start request must be made to start the process. \*Define: OPMN-NLS\_MSG\_00259

**Level:**

**Type:**

**Impact:** Other

**OPM-00662: Starting Process: %s~%s~%s~%u (%u:0)**

**Cause:** About to start a managed process

**Action:** No action. Informational use only. \*Define: OPMN-NLS\_MSG\_00260

**Level:**

**Type:**

**Impact:** Other

**OPM-00663: Stopping Process: %s~%s~%s~%u (%u:%u)**

**Cause:** About to stop a managed process

**Action:** No action. Informational use only. \*Define: OPMN-NLS\_MSG\_00261

**Level:**

**Type:**

**Impact:** Other

**OPM-00664: Restarting Process: %s~%s~%s~%u (%u:%u)**

**Cause:** About to restart a managed process

**Action:** No action. Informational use only. \*Define: OPMN-NLS\_MSG\_00262

**Level:**

**Type:**

**Impact:** Other

**OPM-00665: Process Alive: %s~%s~%s~%u (%u:%u)**

**Cause:** Process started and initialization completed

**Action:** No action. Informational use only. \*Define: OPMN-NLS\_MSG\_00263

**Level:**

**Type:**

**Impact:** Other

**OPM-00666: Process Stopped: %s~%s~%s~%u (%u:%u)**

**Cause:** Process stop operation completed.

**Action:** No action. Informational use only. \*Define: OPMN-NLS\_MSG\_00264

**Level:**

**Type:**

**Impact:** Other

**OPM-00667: Request %x Started. Command: %s**

**Cause:** User request about to be handled by opmn.

---

**Action:** No action. Informational use only. \*Define: OPMN\_NLS\_MSG\_00265

**Level:**

**Type:**

**Impact:** Other

**OPM-00668: Request %x Completed. Command: %s**

**Cause:** Opmn finished handling user request, about to return response.

**Action:** No action. Informational use only. \*Define: OPMN\_NLS\_MSG\_00266

**Level:**

**Type:**

**Impact:** Other

**OPM-00669: Invalid specified process configuration**

**Cause:** You must specify either a list of OPMN configuration elements (all ias-components, all process-types or all process-sets) or a single configuration tree (one ias-component, process-type or process-set)

**Action:** Change the request to conform to the OPMN supported convention.

\*Define: OPMN\_NLS\_REQ\_BAD\_CONFIG

**Level:**

**Type:**

**Impact:** Other

**OPM-00670: failed to get an IP for the hostname**

**Cause:** The operating system could not find an IP address for the hostname.

**Action:** \*Define: OPMN\_NLS\_GETIP\_FAILED

**Level:**

**Type:**

**Impact:** Other

**OPM-00671: Module %s initialization failed: disabled**

**Cause:** The specified module has been disabled because module initialization failed.

**Action:** \*Define: OPMN\_NLS\_MODULE\_FAILED

**Level:**

**Type:**

**Impact:** Other

**OPM-00672: Process skipped because module is disabled: %s~%s~%s~%u (%u:%u)**

**Cause:** The specified process will not be monitored by OPMN because the module initialization failed.

**Action:** \*Define: OPMN\_NLS\_PROC\_SKIPPED

**Level:**

**Type:**

**Impact:** Other

---

**OPM-00673: Process crashed during soft restart: %s~%s~%s~%u (%u:%u)**

**Cause:** The process unexpectedly crashed during a soft restart request.

**Action:** Examine console log associated with the process and examine logs maintained by the component. \*Define: OPMN\_NLS\_BOUNCE\_FAIL

**Level:**

**Type:**

**Impact:** Other

**OPM-00674: process crashed during restart**

**Cause:** The process unexpectedly crashed during a soft restart request.

**Action:** Examine console log associated with the process and examine logs maintained by the component. \*Define: OPMN\_NLS\_RESTART\_DEATH

**Level:**

**Type:**

**Impact:** Other

**OPM-00675: OPMN server ready. Request handling enabled.**

**Cause:** Opmn server has been completely started. Requests sent to the opmn server prior to this point in time will not be handled.

**Action:** No action. Informational only. \*Define: OPMN\_NLS\_MSG\_OPMN\_SERVER\_STARTED

**Level:**

**Type:**

**Impact:** Other

**OPM-00676: OPMN server stopped. Request handling disabled.**

**Cause:** The opmn server received a request to either shutdown or reload. At this point in time the opmn server will abort all current requests and no new requests will be accepted.

**Action:** No action. Informational only. \*Define: OPMN\_NLS\_MSG\_OPMN\_SERVER\_STOPPED

**Level:**

**Type:**

**Impact:** Other

**OPM-00677: Process Ping Failed: %s**

**Cause:** A ping attempt could not be initiated or timed out. Where possible, the opmn server periodically makes an attempt to ping a process it is managing to determine if the process is reachable by a client. A ping attempt can fail during the connection attempt or if the connection is successful but the process does not respond within a configured number of seconds.

**Action:** If ping attempts are timing out it may be necessary to increase the ping timeout configured for the process in opmn.xml. \*Define: OPMN\_NLS\_PROC\_PING\_FAIL

**Level:**

**Type:**



---

**Impact:** Other

**OPM-00678: Process Unreachable: %s**

**Cause:** Reached the maximum configured consecutive ping failures. Process declared unreachable. Process will be restarted.

**Action:** If this occurs frequently, determine if there is something wrong with this type of process by examining the logs associated with the component. It may be necessary to increase the ping timeout configured for the process in opmn.xml.

\*Define: OPMN\_NLS\_PROC\_HUNG

**Level:**

**Type:**

**Impact:** Other

**OPM-00679: Forcefully Terminating Process: %s**

**Cause:** Process did not respond to stop request or request timed out.

**Action:** An initial attempt is made by the opmn server to stop a process by a graceful means. If the process does not respond within the configured time then the process will be stopped forcefully. It may be necessary to increase the configured stop timeout for the process to give it sufficient time to stop gracefully.

\*Define: OPMN\_NLS\_PROC\_FORCEFUL\_TERMINATE

**Level:**

**Type:**

**Impact:** Other

**OPM-00680: Process Start Error: %s**

**Cause:** An error occurred while attempting to start a process.

**Action:** May be caused by bad configuration or insufficient availability of system resources. \*Define: OPMN\_NLS\_PROC\_START\_ERROR

**Level:**

**Type:**

**Impact:** Other

**OPM-00681: Process Restart Error: %s**

**Cause:** An error occurred while attempting to restart a process.

**Action:** May be caused by bad configuration or insufficient availability of system resources. \*Define: OPMN\_NLS\_PROC\_RESTART\_ERROR

**Level:**

**Type:**

**Impact:** Other

**OPM-00682: Process Stop Error: %s**

**Cause:** An error occurred while attempting to stop a process.

**Action:** May be caused by bad configuration or insufficient availability of system resources. \*Define: OPMN\_NLS\_PROC\_STOP\_ERROR

**Level:**

**Type:**

---

**Impact:** Other

**OPM-00683: Process Reverse Ping Error: %s**

**Cause:** An error occurred while consuming a reverse ping message sent from a process.

**Action:** May be caused by wrong or missing information in the contents of the reverse ping message. \*Define: OPMN\_NLS\_PROC\_REVPING\_ERROR

**Level:**

**Type:**

**Impact:** Other

**OPM-00684: Service fail over start failure**

**Cause:** An error occurred while starting a service fail over

**Action:** \*Define: OPMN\_NLS\_SERVICE\_START\_FAIL

**Level:**

**Type:**

**Impact:** Other

**OPM-00685: Service fail over start timeout**

**Cause:** A time out occurred while starting a service fail over

**Action:** \*Define: OPMN\_NLS\_SERVICE\_START\_TIMEOUT

**Level:**

**Type:**

**Impact:** Other

**OPM-00686: Service fail over stop failure**

**Cause:** An error occurred while stopping a service fail over

**Action:** \*Define: OPMN\_NLS\_SERVICE\_STOP\_FAIL

**Level:**

**Type:**

**Impact:** Other

**OPM-00687: Service fail over stop timeout**

**Cause:** A time out occurred while stopping a service fail over

**Action:** \*Define: OPMN\_NLS\_SERVICE\_STOP\_TIMEOUT

**Level:**

**Type:**

**Impact:** Other

**OPM-00688: Service fail over restart failure**

**Cause:** An error occurred while restarting a service fail over

**Action:** \*Define: OPMN\_NLS\_SERVICE\_RESTART\_FAIL

**Level:**

**Type:**

---

**Impact:** Other

**OPM-00689: Service fail over restart timeout**

**Cause:** A time out occurred while restarting a service fail over

**Action:** \*Define: OPMN\_NLS\_SERVICE\_RESTART\_TIMEOUT

**Level:**

**Type:**

**Impact:** Other

**OPM-00690: Could not create service manager thread**

**Cause:** OPMN could not create the service failover manager thread

**Action:** \*Define: OPMN\_NLS\_SERVICE\_THREAD\_CREATE

**Level:**

**Type:**

**Impact:** Other

**OPM-00691: Service: bad participant id data: %s**

**Cause:** The service failover manager encountered bad participant data.

**Action:** \*Define: OPMN\_NLS\_SERVICE\_BAD\_PART\_DATA

**Level:**

**Type:**

**Impact:** Other

**OPM-00692: Service: could not start service process (%s)**

**Cause:** The service failover process could not be started.

**Action:** \*Define: OPMN\_NLS\_SERVICE\_STARTPROC\_FAIL

**Level:**

**Type:**

**Impact:** Other

**OPM-00693: Service: could not stop service process (%s)**

**Cause:** The service failover process could not be stopped.

**Action:** \*Define: OPMN\_NLS\_SERVICE\_STOPPROC\_FAIL

**Level:**

**Type:**

**Impact:** Other

**OPM-00694: Service: could not restart service process (%s)**

**Cause:** The service failover process could not be restarted.

**Action:** \*Define: OPMN\_NLS\_SERVICE\_RESTARTPROC\_FAIL

**Level:**

**Type:**

**Impact:** Other

---

**OPM-00695: Debug specific module negation can not be used with specific module selection.**

**Cause:** Specific modules may be listed for exclusion or inclusion but not both.

**Action:** \*Define: OPMN-NLS\_DEBUG\_PM\_CLASHMOD

**Level:**

**Type:**

**Impact:** Other

**OPM-00696: Comp code argument contains invalid parentheses syntax**

**Cause:** The comp argument has invalid syntax for modules().

**Action:** \*Define: OPMN-NLS\_DEBUG\_ARGOPEN

**Level:**

**Type:**

**Impact:** Other

**OPM-00697: Specific module id does not exist.**

**Cause:** The comp argument specifies a specific module id that does not exist.

**Action:** \*Define: OPMN-NLS\_DEBUG\_PM\_NOMOD

**Level:**

**Type:**

**Impact:** Other

**OPM-00698: A process-set specified in the request does not support min/max procs.**

**Cause:** If numprocs is specified in the request, then only process-sets that are configured with min/max procs must be specified.

**Action:** \*Define: OPMN-NLS\_REQ\_NOMINMAX

**Level:**

**Type:**

**Impact:** Other

**OPM-00699: The request for the specified application is not supported by the process-module.**

**Cause:** A request was issued for an application which the process-module for the owning process does not support.

**Action:** \*Define: OPMN-NLS\_REQ\_APP\_NOSUPPORT

**Level:**

**Type:**

**Impact:** Other

**OPM-00700: The application must be specified for this request.**

**Cause:** An application or list of applications must be specified with this request.

**Action:** \*Define: OPMN-NLS\_REQ\_APP\_ONLY

**Level:**

**Type:**

---

**Impact:** Other

**OPM-00701: An application for this request was removed.**

**Cause:** An application taking part in this request was removed from the process.

**Action:** \*Define: OPMN-NLS\_APP\_REMOVE

**Level:**

**Type:**

**Impact:** Other

**OPM-00702: The application process has terminated.**

**Cause:** The process for an application taking part in this request has terminated.

**Action:** \*Define: OPMN-NLS\_APP\_PROC\_DEAD

**Level:**

**Type:**

**Impact:** Other

**OPM-00703: The request failed for this application.**

**Cause:** The request failed for this application.

**Action:** \*Define: OPMN-NLS\_APP\_REQ\_FAIL

**Level:**

**Type:**

**Impact:** Other

**OPM-00704: The request timed-out for this application.**

**Cause:** The request timed-out for this application.

**Action:** \*Define: OPMN-NLS\_APP\_REQ\_TIMEOUT

**Level:**

**Type:**

**Impact:** Other

**OPM-00705: Duplicate target for set or query request.**

**Cause:** The set or query request specifies more than one target.

**Action:** \*Define: OPMN-NLS\_SET\_DUP\_TARGET

**Level:**

**Type:**

**Impact:** Other

**OPM-00706: Duplicate comp for set or query request.**

**Cause:** The set or query request specifies more than one comp.

**Action:** \*Define: OPMN-NLS\_SET\_DUP\_COMP

**Level:**

**Type:**

**Impact:** Other

**OPM-00707: No target for set or query request.**

---

**Cause:** The set or query request does not specify a target.

**Action:** \*Define: OPMN-NLS\_SET\_NO\_TARGET

**Level:**

**Type:**

**Impact:** Other

**OPM-00708: No comp for set request.**

**Cause:** The set request does not specify a comp.

**Action:** \*Define: OPMN-NLS\_SET\_NO\_COMP

**Level:**

**Type:**

**Impact:** Other

**OPM-00709: Invalid target for set or query request.**

**Cause:** The set or query request specifies an invalid target.

**Action:** \*Define: OPMN-NLS\_SET\_INVALID\_TARGET

**Level:**

**Type:**

**Impact:** Other

**OPM-00710: Comp code contains extra characters after the closing brace.**

**Cause:** The component code has extra characters after the closing brace.

**Action:** \*Define: OPMN-NLS\_DEBUG\_COMPCLOSE

**Level:**

**Type:**

**Impact:** Other

**OPM-00711: Only one module may be specified for this request.**

**Cause:** Multiple modules were specified for this request, which only allows one.

**Action:** \*Define: OPMN-NLS\_MODULE\_MULT

**Level:**

**Type:**

**Impact:** Other

**OPM-00712: The specified module is not configured.**

**Cause:** The specified module is not configured.

**Action:** \*Define: OPMN-NLS\_MODULE\_UNKNOWN

**Level:**

**Type:**

**Impact:** Other

**OPM-00713: The specified module does not support this request.**

**Cause:** The specified module does not support this request.

**Action:** \*Define: OPMN-NLS\_MODULE\_NOSUPPORT

---

**Level:**

**Type:**

**Impact:** Other

**OPM-00714: No module was specified.**

**Cause:** This request requires that a module be specified.

**Action:** \*Define: OPMN\_NLS\_MODULE\_NOMODULE

**Level:**

**Type:**

**Impact:** Other

**OPM-00715: The specified module is disabled.**

**Cause:** The specified module is disabled.

**Action:** \*Define: OPMN\_NLS\_MODULE\_DISABLED

**Level:**

**Type:**

**Impact:** Other

**OPM-00716: No components matched this request.**

**Cause:** No components matched the options specified for this request.

**Action:** \*Define: OPMN\_NLS\_REQ\_NOCOMPONENT

**Level:**

**Type:**

**Impact:** Other

**OPM-00717: No addresses for the request.**

**Cause:** There were no registered addresses for the request.

**Action:** \*Define: OPMN\_NLS\_REQ\_ADDRNONE

**Level:**

**Type:**

**Impact:** Other

**OPM-00718: No addresses matched the properties for the request.**

**Cause:** No registered addresses matched the properties specified in the request.

**Action:** \*Define: OPMN\_NLS\_REQ\_ADDRSNOMATCH

**Level:**

**Type:**

**Impact:** Other

**OPM-00719: Failed to initialize DMS publisher.**

**Cause:** The server code not initialize the DMS publisher: OPMN metrics will not be available via the metric request.

**Action:** \*Define: OPMN\_NLS\_DMS\_PUBLISHER\_FAIL

**Level:**

---

**Type:**

**Impact:** Other

**OPM-00720: Failed to create RPC client.**

**Cause:** The server code not create the ONS RPC client.

**Action:** \*Define: OPMN-NLS\_RPC\_CLIENT\_FAIL

**Level:**

**Type:**

**Impact:** Other

**OPM-00721: Invalid operation for metric.**

**Cause:** The op argument for the metric request must be set to query or list.

**Action:** \*Define: OPMN-NLS\_REQ\_METRICOP

**Level:**

**Type:**

**Impact:** Other

**OPM-00722: Scope is invalid with launch request.**

**Cause:** Request scope may not be configured with a launch request.

**Action:** \*Define: OPMN-NLS\_REQ\_LAUNCHSCOPE

**Level:**

**Type:**

**Impact:** Other

**OPM-00723: No target specified for launch request.**

**Cause:** A configured target must be specified with the launch request.

**Action:** \*Define: OPMN-NLS\_REQ\_LAUNCHNOTARGET

**Level:**

**Type:**

**Impact:** Other

**OPM-00724: Invalid target specified for launch request.**

**Cause:** The target specified with the launch request is not configured.

**Action:** \*Define: OPMN-NLS\_REQ\_LAUNCHINVALIDTARGET

**Level:**

**Type:**

**Impact:** Other

**OPM-00725: Launch target at maximum concurrency.**

**Cause:** The target specified with the launch request is at the configured maximum concurrency.

**Action:** \*Define: OPMN-NLS\_REQ\_LAUNCHMAXCONCURR

**Level:**

**Type:**



---

**Impact:** Other

**OPM-00726: Launch target process start error: %s %d %s (%s)**

**Cause:** The process for the launch target failed to start.

**Action:** \*Define: OPMN-NLS\_REQ\_LAUNCHPROCERROR

**Level:**

**Type:**

**Impact:** Other

**OPM-00727: Launch target process pipe read error: %s %d (%s).**

**Cause:** The server failed on a read from the launch target process pipe.

**Action:** \*Define: OPMN-NLS\_REQ\_LAUNCHPROCPPIPE

**Level:**

**Type:**

**Impact:** Other

**OPM-00728: Launch target process hung: %s %d pid %u.**

**Cause:** The process for the launch target failed to start. The process will be killed.

**Action:** \*Define: OPMN-NLS\_REQ\_LAUNCHPROCHUNG

**Level:**

**Type:**

**Impact:** Other

**OPM-00729: Launch target process signal error: %s %d pid %u (%s).**

**Cause:** The server could not send the hung launch target process a signal.

**Action:** \*Define: OPMN-NLS\_REQ\_LAUNCHPROCSIG

**Level:**

**Type:**

**Impact:** Other

**OPM-00730: Launch target request client send error: %s %d.**

**Cause:** The server could not send the launch target process output to the request client.

**Action:** \*Define: OPMN-NLS\_REQ\_LAUNCHSENDERERROR

**Level:**

**Type:**

**Impact:** Other

**OPM-00731: Scope is invalid with phantom request.**

**Cause:** Request scope may not be configured with a phantom request.

**Action:** \*Define: OPMN-NLS\_REQ\_PHANTOMSCOPE

**Level:**

**Type:**

**Impact:** Other

---

**OPM-00732: Invalid pid specified with phantom request.**

**Cause:** The pid must be an integer of value > 1.

**Action:** \*Define: OPMN-NLS\_REQ\_PHANTOMINVALIDPID

**Level:**

**Type:**

**Impact:** Other

**OPM-00733: Disabled ias-component for the phantom request.**

**Cause:** The ias-component specified with the phantom request does not have a configuration status of enabled or phantom.

**Action:** \*Define: OPMN-NLS\_REQ\_PHANTOMDISCOMP

**Level:**

**Type:**

**Impact:** Other

**OPM-00734: Disabled process-type for the phantom request.**

**Cause:** The process-type specified with the phantom request does not have a configuration status of enabled or phantom.

**Action:** \*Define: OPMN-NLS\_REQ\_PHANTOMDISPTYPE

**Level:**

**Type:**

**Impact:** Other

**OPM-00735: Disabled process-set for the phantom request.**

**Cause:** The process-set specified with the phantom request does not have a configuration status of enabled or phantom.

**Action:** \*Define: OPMN-NLS\_REQ\_PHANTOMDISPSET

**Level:**

**Type:**

**Impact:** Other

**OPM-00736: No process-set for the phantom request.**

**Cause:** No configured phantom process-set matched the phantom request.

**Action:** \*Define: OPMN-NLS\_REQ\_PHANTOMNOPSET

**Level:**

**Type:**

**Impact:** Other

**OPM-00737: Ambiguous process-set for the phantom request.**

**Cause:** Multiple phantom process-sets matched the phantom request, but the request requires only one matching process-set.

**Action:** \*Define: OPMN-NLS\_REQ\_PHANTOMAMBIGPSET

**Level:**

**Type:**

---

**Impact:** Other

**OPM-00738: Invalid executable file path.**

**Cause:** The path to the executable file is invalid: the path either does not exist or has incorrect permissions.

**Action:** Validate the path configured in opmn.xml for the specified failure and ensure it is correct, and permissions for the path are correct for the OPMN user to execute it. \*Define: OPMN\_NLS\_EXECUTE\_INVALID

**Level:**

**Type:**

**Impact:** Other

**OPM-00739: Executable file does not have execute permission.**

**Cause:** The executable file does not have system execute permissions for the OPMN user.

**Action:** Ensure the executable file has execute permissions set for the OPMN user. \*Define: OPMN\_NLS\_EXECUTE\_PERM

**Level:**

**Type:**

**Impact:** Other

**OPM-00740: Missing operation for metric.**

**Cause:** The op argument for the metric request must be specified and set to query or list.

**Action:** \*Define: OPMN\_NLS\_REQ\_NOMETRICOP

**Level:**

**Type:**

**Impact:** Other

**OPM-00741: More than one address matched the properties for the request.**

**Cause:** The properties specified in the request matched more than one registered address.

**Action:** \*Define: OPMN\_NLS\_REQ\_ADDRSNOTUNIQUE

**Level:**

**Type:**

**Impact:** Other

**OPM-00742: Process is still alive -- check configuration.**

**Cause:** An error occurred while attempting to access a process, but the process is still alive.

**Action:** Usually caused by bad component configuration. Check component log files. \*Define: OPMN\_NLS\_PROC\_ALIVE

**Level:**

**Type:**

**Impact:** Other

**OPM-00743: Process terminated.**

---

**Cause:** An error occurred while accessing a process, and the process terminated.

**Action:** May be caused by bad configuration or insufficient availability of system resources. Check component log files. \*Define: OPMN\_NLS\_PROC\_DEAD

**Level:**

**Type:**

**Impact:** Other

**OPM-00744: Invalid process state.**

**Cause:** An error occurred while accessing a process leaving the process in an invalid state.

**Action:** May be caused by bad configuration or insufficient availability of system resources. Check component log files. \*Define: OPMN\_NLS\_PROC\_INVALID\_STATE

**Level:**

**Type:**

**Impact:** Other

**OPM-00745: Process restart failed.**

**Cause:** An error occurred while attempting to restart a process.

**Action:** May be caused by bad configuration or insufficient availability of system resources. Check component log files. \*Define: OPMN\_NLS\_PROC\_RESTART\_FAIL

**Level:**

**Type:**

**Impact:** Other

---

## ORABPEL-00006 to ORABPEL-20511

---

**ORABPEL-00006: failure to load the JCE cipher "{0}"**

**Cause:** The environment may not have been set correctly.

**Action:** JCE library files must be installed in the JRE installation as an extension. Copy the jar files from "{1}\install\java\jce1.2.2" directory to "(jdk\_path)\jre\lib\ext" directory (where jdk\_path is JDK installation directory).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-00007: failure to decrypt cipher text with transformation "{0}"; exception reported is: {1}**

**Cause:** This was an internal error. It may have been caused by an incorrect cipher state or an invalid padding size being specified.

**Action:** Contact Oracle Support Services. Provide the error message and the process that appeared to cause the problem.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-00008: failure to encrypt plain text with transformation "{0}"; exception reported is: {1}**

**Cause:** This was an internal error. It may have been caused by an incorrect cipher state or an invalid padding size being specified.

**Action:** Contact Oracle Support Services. Provide the error message and the process that appeared to cause the problem.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-00015: failure to create jar file {0}**

**Cause:** The Sun tools.jar may not have been installed on the local machine or included in the class path.

**Action:** Verify that tools.jar is installed on this machine and is included in the class path.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-00016: failure to execute javac compiler on file(s) "{0}"; exception reported is: {1}**

**Cause:** The Sun tools.jar may not have been installed on the local machine or included in the class path.

**Action:** Verify that tools.jar is installed on this machine and is included in the class path.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-00017: failure to compile file(s) "{0}"; exception reported is: {1}**

**Cause:** The generated Java class(es) had errors and/or all the required libraries to compile the class(es) were not available.

**Action:** Verify that the file named in the error message is valid Java file and that all required libraries are included in the class path.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-00018: cannot find the Java source directory "{0}"**

**Cause:** The specified Java source directory did not exist or it could not be written to.

**Action:** Create the source directory named in the error message and set the write permission accordingly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-00019: cannot create the Java destination directory "{0}"**

**Cause:** The parent directory permissions prevented the creation of this directory.

**Action:** Verify that the parent directory for the directory named in the error message is writable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-00020: failure to write the Javadoc argument file "{0}"; exception reported is: "{2}"**

**Cause:** The Javadoc file named in the error message was not written to the directory "{1}".

**Action:** Verify that the directory "{1}" can be written to.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**ORABPEL-00021: failure to execute Javadoc with the argument file "{0}"**

**Cause:** The Javadoc executable was not found in the system path or was not executed.

**Action:** Verify that Javadoc is installed on this machine in the <JDK>\bin directory and that this directory is included in the machine system path.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-00024: failure to schedule the "{0}" agent with the scheduler; exception reported is: {1}**

**Cause:** The Quartz scheduler did not schedule the job named in the error message. This is typically an internal scheduler error.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-00025: failure to unschedule the "{0}" agent with the scheduler; exception reported is: {1}**

**Cause:** The Quartz scheduler did not unschedule the job named in the error message. This is typically an internal scheduler error.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-00026: error while attempting to execute the job "{0}" for agent "{1}"; exception reported is: {2}**

**Cause:** This error was a wrapper for an internal exception thrown by the underlying scheduler job.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-00201: cannot return system authentication token for caller "{0}"**

**Cause:** This was an internal error. The agent "{0}" was not added to the allowed callers list for the system token.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

---

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-00209: The domain identifier "{0}" is not registered with the server.**

**Cause:** All domain identifiers were kept in the domain table; this table may have been modified incorrectly.

**Action:** Restart the application server; if the domain directory is present, the identifier will be automatically registered again.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-00210: domain ref "{0}" is not registered with the server.**

**Cause:** All domain identifiers were kept in the domain table; this table may have been modified incorrectly.

**Action:** Restart the application server; if the domain directory is present, the identifier will be automatically registered again.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-00214: The OraBPEL server has not finished initializing yet; the initialization process may be complete in a few moments.**

**Cause:** A request was sent to the server before it finished initializing.

**Action:** Resubmit the request. If this does not solve the problem, check the logs (with logging level set to debug mode) for error messages.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-00215: error while attempting to instantiate the JDK adapter class "{0}" for run-time version "{1}"; exception reported is: {2}**

**Cause:** The JDK adapter class named in the error message was not in the system class path or there was an incompatibility with the JDK used to compile the class and the current JVM version.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-00216: JDK adapter class "{0}" for run-time version "{1}" does not implement the IJDKAdapter interface**

**Cause:** This was an internal error. All JDK adapters registered with the system must conform to the IJDKAdapter interface.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with logging level set to debug mode).



---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-00217: JDK version "{0}" is not supported by the OraBPEL run-time; currently only JDK versions 1.4 and 1.5 are supported**

**Cause:** A JDK adapter was not specified for the JVM version with which the container was started.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-00219: cannot instantiate an instance for the class "{0}"**

**Cause:** The class "{1}" was not granted sufficient permissions by the JVM to instantiate the class "{0}".

**Action:** Verify that the OraBPEL run-time class "{1}" has the necessary security permissions to access the class specified in the error message.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-00220: class "{0}" (for the platform adapter for platform "{1}") does not implement the IPlatformAdaptor interface**

**Cause:** This was an internal error. All platform adapters registered with the system must conform to the IPlatformAdaptor interface.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-00221: error while attempting to instantiate the class "{0}" as the adapter for platform "{1}"; exception reported is: {2}**

**Cause:** The platform adapter class "{0}" was not in the system class path, or there was an incompatibility with the JDK used to compile the class and the current JVM version.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-00222: class for platform adapter "{0}" (platform "{1}") cannot be found**

**Cause:** The platform adapter class "{0}" was not in the system class path.

---

**Action:** Ensure that Oracle BPEL libraries are set correctly in the system class path.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-00227: class "{0}" (for the database adapter for "{1}") does not implement the IDatabaseAdaptor interface**

**Cause:** This was an internal error. All database adapters registered with the system must conform to the IDatabaseAdaptor interface.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-00228: error while attempting to instantiate the class "{0}" as the database adapter, data source "{1}"; exception reported is: {3}**

**Cause:** The database adapter class "{0}" was not in the system class path, or there was an incompatibility with the JDK used to compile the class and the current JVM version.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-00229: database adapter class name for data source "{0}" has not been specified**

**Cause:** The database adapter class "{0}" was not in the system class path.

**Action:** Ensure that the Oracle BPEL libraries are set correctly in the system class path. If the libraries are configured correctly, the adapter configuration files may have been modified incorrectly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-00230: adapter resource file "{0}" cannot be found in the current class path**

**Cause:** The resource file named in the error message contained all the JNDI mappings required for the BPEL process domain to initialize.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

---

**ORABPEL-00231: error while attempting to instantiate the class "{0}" as the adapter manifest for "{1}", data source "{2}"; exception reported is: {3}**

**Cause:** The adapter manifest class "{0}" was not in the system class path, or there was an incompatibility with the JDK used to compile the class and the current JVM version.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-00232: class "{0}" (for the adapter manifest for "{1}", data source "{2}") does not implement the IServerAdaptorManifest interface; all adapter manifests used by the OraBPEL server must implement this interface**

**Cause:** This was an internal error. All adapter manifests registered with the system must conform to the IServerAdaptorManifest interface.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-00233: adapter manifest class name for "{0}", data source "{1}" is not specified.**

**Cause:** The adapter manifest class "{0}" was not in the system class path.

**Action:** Ensure that the Oracle BPEL libraries are set correctly in the system class path. If the libraries are configured correctly, the adapter configuration files may have been modified incorrectly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-00235: The component identifier "{0}" has not been registered with the server.**

**Cause:** All component identifiers were kept in the "component" table; this table may have been modified incorrectly.

**Action:** Restart the application server; when the component is loaded, the identifier will be automatically registered again.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-00236: The component reference "{0}" is not registered with the server.**

**Cause:** All component references were kept in the "component" table; this table may have been modified incorrectly.

**Action:** Restart the application server; when the component is loaded, the reference will be automatically registered again.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-00237: failure to create the component reference for "{0}"**

**Cause:** The maximum number of components ({1}) were reached.

**Action:** Contact Oracle Support Services. At the current time, the maximum number of components has been set to 32767.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-00238: exception while reading the component index from the data source; the exception reported is: {0}**

**Cause:** There was a problem with connecting to the data source where the component index is stored.

**Action:** There are three things to verify. Verify that the machine hosting the data source is physically connected to the network. Verify that the connection pool properties as defined in the application server startup properties are valid. Verify that the database schema for the OraBPEL server has been installed in the data source.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-00239: exception while writing the component index (application\_name "{0}", composite\_name "{1}", revision "{2}", label "{3}", component\_name "{4}") to the data source; the exception reported is: {5}**

**Cause:** There was a problem with connecting to the data source where the component index is stored.

**Action:** There are three things to verify. Verify that the machine hosting the data source is physically connected to the network. Verify that the connection pool properties as defined in the application server startup properties are valid. Verify that the database schema for the OraBPEL server has been installed in the data source.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-00240: exception occurs while removing the component index (dn "{0}", ref "{1}") from the data source; the exception reported is: {2}**

**Cause:** There was a problem with connecting to the data source where the component index is stored.

**Action:** There are three things to verify. Verify that the machine hosting the data source is physically connected to the network. Verify that the connection pool properties as defined in the application server startup properties are valid. Verify that the database schema for the OraBPEL server has been installed in the data source.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-01005: failure to compile the generated BPEL classes for BPEL process "{0}" of composite "{1}"**

**Cause:** The class path setting is incorrect.

**Action:** Ensure that the class path is set correctly. If this happens on the server side, verify that the custom classes or jars which this BPEL process is depending on are deployed correctly. Also verify that the run time is using the same release/version.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-01007: build directory "{0}" for the BPEL process "{1}" of composite "{2}" cannot be found or accessed**

**Cause:** The compiler could not find or create the directory "{0}".

**Action:** Ensure that the parent directory of "{0}" is a valid directory and that it is not read-only.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-01010: failure to generate the BPEL process file "{0}".**

**Cause:** Could not generate named BPEL process file. The exception reported was "{1}".

**Action:** Ensure that the file "{0}" is a valid file to be generated.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-01027: trying to manipulate the nonexistent part "{1}" in a message of type "{0}"**

**Cause:** An invalid request was made to manipulate the invalid part "{1}".

**Action:** Ensure that the client request is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-01028: cannot find propertyAlias definition that associates the BPEL correlation "{0}" of correlationSet "{1}" to messageType "{2}"**

**Cause:** A propertyAlias must be defined to associate the BPEL correlation to a correlationSet. The run time could not find it.

**Action:** Ensure that the mentioned propertyAlias is in one of the WSDL files that are referenced by the composite. Redeploy the composite.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-01029: cannot find property definition for "{0}" in any of the WSDL files**

**Cause:** The BPEL correlation property needs to be defined. But the run time could not find it.

**Action:** Define the mentioned BPEL property in one of the WSDL files referenced by the composite.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-01030: cannot generate debug model file "{0}"**

**Cause:** The named BPEL debug model file was not generated. The exception reported was: "{1}".

**Action:** Correct the error reported by the error message.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-01032: specified process ID "{0}" is invalid**

**Cause:** The specified process identifier did not follow the naming constraints.

**Action:** Valid process identifiers might start with a letter, a "\$" or "\_" character; process characters (other than the first character) include a letter, a digit, a "\$", a "\_" or "-" character. The max length permitted is 100. Ensure that the component name specified in the composite descriptor conforms to the above mentioned constraints.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02000: The class "{0}" for the block element "{1}" does not implement the ICubeBlock interface.**

**Cause:** This was an internal error. All block elements contained within the process domain must implement this interface.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02001: error while attempting to instantiate the class "{1}" for the block element "{0}"; exception reported is: {2}**

---

**Cause:** This was an internal error. The block class "{0}" was not in the composite class path, or there was an incompatibility with the JDK used to compile the class and the current JVM version.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02002: block element "{0}" missing its class name; this element cannot be created without its class name**

**Cause:** This was an internal error. The block element class "{0}" was not in the composite class path.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02003: A Cube element is missing its "ID" property. Every Cube element in the process domain is uniquely identified by its "ID" property.**

**Cause:** This was an internal error. The element was not generated correctly by the BPEL compiler.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02005: The parent block element "{0}" specified by node or block element "{1}" is not defined in the service class map. All nodes or blocks contained in the map must be bound to a valid parent block element.**

**Cause:** This was an internal error. The element was not generated correctly by the BPEL compiler.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02006: The node or block element "{0}" is missing a parent block identifier. All nodes or blocks contained in the service class map must be bound to a parent block element.**

---

**Cause:** This was an internal error. The element was not generated correctly by the BPEL compiler.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02007: Multiple method block elements are specified in the service class map. A valid map can only contain one method block element.**

**Cause:** This was an internal error. The element was not generated correctly by the BPEL compiler.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02008: No block elements are specified in the service class map. All valid maps must contain at least one block element (the root block).**

**Cause:** This was an internal error. The block map was not generated correctly by the BPEL compiler.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02009: No node elements are specified in the service class map. All valid maps must contain at least one node element.**

**Cause:** This was an internal error. The block map was not generated correctly by the BPEL compiler.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02010: No method block element is specified for the service class map. All valid maps must contain one method block element.**

**Cause:** This was an internal error. The block map was not generated correctly by the BPEL compiler.



---

**Action:** Contact Oracle Support Services. Provide the error message, the composite source and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02011: The class "{0}" for the node element "{1}" does not implement the ICubeNode interface.**

**Cause:** This was an internal error. All node elements contained within the process domain must implement this interface.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02012: error while attempting to instantiate the class "{1}" for the node element "{0}"; the exception reported is: {2}**

**Cause:** This was an internal error. The node class "{0}" was not in the composite class path or there was an incompatibility with the JDK used to compile the class and the current JVM version.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02013: The class "{0}" cannot be found in the current class path.**

**Cause:** This was an internal error. The node element class "{0}" was not in the composite class path.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02014: The node element "{0}" is missing its class name; this element cannot be created without its class name.**

**Cause:** This was an internal error. The node class name should be generated by the BPEL compiler.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source and the exception trace in the log files (with logging level set to debug mode).

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02015: The BPEL process "{0}" (revision "{1}") has been compiled with an older version of SCAC; current BPEL process domain cannot execute this process.**

**Cause:** An attempt to deploy a process that was compiled with an older version of SCAC failed.

**Action:** Recompile the BPEL process using the SCAC tool bundled with the current process domain.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02016: The process "{0}" is not initializing because of the error: "{1}".**

**Cause:** This error contained the exceptions thrown by the underlying process loading module.

**Action:** Check for possible cause in the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02017: cannot compress the data stream with GZIP algorithm; exception reported is: {0}**

**Cause:** This error contained the exceptions thrown by the underlying compression layer.

**Action:** Check for possible cause in the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02018: cannot uncompress the data stream with GZIP algorithm; exception reported is: {0}**

**Cause:** This error contained the exceptions thrown by the underlying compression layer.

**Action:** Check for possible cause in the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02019: cannot compute the md5 checksum; exception reported is: {0}**

**Cause:** This error contained exceptions thrown by the underlying digest layer.

---

**Action:** Check for possible cause in the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02020: failure to serialize the audit trail for instance "{0}" to its binary representation; exception reported is: {1}**

**Cause:** This was an internal error. This error contained the exceptions thrown by the underlying XML marshalling module.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02022: The value "{0}" for the tag "{1}" in the XML serialized text for the audit trail for instance "{2}" is not a numeric value.**

**Cause:** The tag "{1}" did not contain a numeric value.

**Action:** Ensure that the value for tag "{1}" conforms to the expected numeric format.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02023: failure to activate the block "{0}" for the instance "{1}"; exception reported is: {2}**

**Cause:** This error contained the exceptions thrown by the underlying routing system.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02024: failure to invoke the method "until" on the block "{0}" for the instance "{1}"; exception reported is: {2}**

**Cause:** This error contained the exceptions thrown by the underlying routing system.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Programmatic

**ORABPEL-02025: failure of the block "{0}" to handle a business exception for the instance "{1}"; exception reported is: {2}**

**Cause:** This error contained the exceptions thrown by the underlying routing system.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02026: failure to invoke the canActivate method on the block "{0}" for the instance "{1}"; exception reported is: {2}**

**Cause:** This error contained the exceptions thrown by the underlying routing system.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02027: failure to deserialize the instance "{0}" from binary format; exception reported is: {1}**

**Cause:** This error contained the exceptions thrown by the underlying serialization system.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02028: failure to serialize the instance "{0}" to binary format; exception reported is: {1}**

**Cause:** This error contained the exceptions thrown by the underlying serialization system.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

---

**ORABPEL-02029: The process domain cannot create the bean "{0}"; this bean is responsible for generating a unique key for a new instance. The exception reported is: "{1}".**

**Cause:** The SOA application or class path was not configured correctly.

**Action:** Verify that the instance key generator bean has been properly deployed to the server and can be properly mounted from a java class.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02030: failure to marshall the instance "{0}" to XML format; exception reported is: {1}**

**Cause:** This error contained the exceptions thrown by the underlying serialization system.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02031: The instance "{0}" is created from the domain "{1}"; the current domain is "{2}". A process can be loaded only from the domain from which it was created.**

**Cause:** The instance was not accessed because it was created in a different domain.

**Action:** If this instance is being accessed from the API, try looking up the instance "{0}" from the "{1}" domain (change the domain ID parameter to the Locator initializer).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02032: The instance "{0}" is created with process guid "{1}"; the current guid for the process "{2}" (revision "{3}") is "{4}".**

**Cause:** Whenever a process is deployed on top of an existing process with the same process ID and revision tag, all instances created from the previous process are marked as stale.

**Action:** If this instance is being accessed from the console, the browser may be referring to an out-of-date page; click the Instances tab to get the current list of active instances.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02033: failure to construct a valid instance key from the string "{0}"; exception reported is: {2}**

**Cause:** The instance did not consist of a single integer value.

---

**Action:** If the instance key has not been constructed by the process domain, ensure that the key format is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02037: exception while trying to create a context object; the exception reported is: {0}**

**Cause:** This error contained the exceptions thrown by the underlying JNDI environment.

**Action:** Verify that the directory service on the application server has been configured correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02038: The process domain is unable to look up the context object using the bind name "{0}"; the exception reported is: {1}**

**Cause:** This error contained the exceptions thrown by the underlying JNDI environment.

**Action:** Verify that the JNDI identifier is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02040: exception while trying to destroy a context object; the exception reported is: {0}**

**Cause:** This error contained the exceptions thrown by the underlying JNDI environment.

**Action:** Verify that the directory service on the application server has been configured correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02041: The action "{0}" cannot be performed on the instance "{1}" because of its current state ("{2}").**

**Cause:** The current instance state did not allow the requested action to be performed.

**Action:** Consult the product documentation for a list of all the permissible actions that can be performed on an instance when it is in the "{2}" state.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02042: The action "{0}" cannot be performed on the work item "{1}" because of its current state ("{2}").**

---

**Cause:** The current work item state did not allow the requested action to be performed.

**Action:** Consult the product documentation for a list of all the permissible actions that can be performed on a work item when it is in the "{2}" state.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02043: The action "{0}" cannot be performed on the scope "{1}" because of its current state ("{2}").**

**Cause:** The current scope state did not allow the requested action to be performed.

**Action:** Consult the product documentation for a list of all the permissible actions that can be performed on a scope when it is in the "{2}" state.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02044: The process domain is failing to write the audit trail for instance "{0}"; the exception reported is: {1}**

**Cause:** This error contained the exceptions thrown by the underlying persistence framework.

**Action:** Check the log for the underlying exception trace after setting the logging level to debug mode.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02046: The process domain is failing to write the debug trace for instance "{0}"; the exception reported is: {1}**

**Cause:** This error contained the exceptions thrown by the underlying serialization layer.

**Action:** Check the log for the underlying exception trace after setting the logging level to debug mode.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02047: The process domain is failing to write the instance trace for instance "{0}"; the exception reported is: {1}**

**Cause:** This error contained the exceptions thrown by the underlying serialization layer.

**Action:** Check the log for the underlying exception trace after setting the logging level to debug mode.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**ORABPEL-02048: The process domain is unable to handle the work item "{0}"; the exception reported is: {1}**

**Cause:** This error contained the exceptions thrown by the underlying process execution layer.

**Action:** Check the log for the underlying exception trace after setting the logging level to debug mode.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02050: The invocation for method "{0}" on the instance "{1}", process "{2}" (revision "{3}") is cancelled. The return value for this method cannot be determined in this case.**

**Cause:** The instance "{1}" was cancelled or aborted.

**Action:** Check the audit trail for instance "{1}" for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02051: The invocation for method "{0}" on the instance "{1}", process "{2}" (revision "{3}") is not complete. The return value for this method cannot be fetched until the method has completed.**

**Cause:** The instance "{1}" was not complete yet.

**Action:** Resubmit this request after several minutes. Note that the method may contain some asynchronous interactions that could take an indeterminate amount of time to complete.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02052: The BPEL domain "{0}" is missing.**

**Cause:** The BPEL domain "{0}" may not have initialized properly.

**Action:** Check the log for the underlying exception trace after setting the logging level to debug mode.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02053: The BPEL domain "{0}" is not finished initializing yet.**

**Cause:** The domain initialization procedure was not finished yet.

**Action:** Resubmit the request in few minutes. The initialization progress can be monitored in the server log; set the logging level to debug mode.

**Level:** 1

**Type:** ERROR



---

**Impact:** Programmatic

**ORABPEL-02054: The BPEL domain "{0}" is currently uninitialized; the domain may not be accessed.**

**Cause:** The domain was uninitialized.

**Action:** Restart the application server. If the domain uninitialized due to an exception, check the server log for the underlying exception trace (be sure to set the logging level to debug mode).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02055: failure to handle a fault thrown from a scope, by any blocks in the scope chain**

**Cause:** This exception occurred because the fault thrown in the BPEL flow was not handled by any fault handlers and reached the top-level scope.

**Action:** A top-level fault handler should be added to the flow to handle faults not caught from within the flow.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02057: The block element "{0}" is not defined in the service class map.**

**Cause:** This was an internal error. The flow was not generated correctly by the BPEL compiler.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02058: The node element "{0}" is not defined in the service class map.**

**Cause:** This was an internal error. The flow was not generated correctly by the BPEL compiler.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02059: The process domain is unable to fetch the work item "{0}" from the memory repository.**

**Cause:** This was an internal error. The work item was not correctly registered from the previous transaction.

---

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02060: failure to activate the node "{0}" for the instance "{1}"; the exception reported is: {2}**

**Cause:** An exception was thrown by the underlying routing subsystem.

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace related to the instance.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02061: failure to finalize the node "{0}" for the work item "{1}"; the exception reported is: {2}**

**Cause:** An exception was thrown by the underlying routing subsystem.

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace related to the work item.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02062: failure to invoke the canActivate method on the node "{0}" for the instance "{1}"; the exception reported is: {2}**

**Cause:** An exception was thrown by the underlying routing subsystem.

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace related to the instance.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02063: failure to deserialize the delivery callback messages for conversation "{0}", message "{1}" from the binary format; the exception reported is: {2}**

**Cause:** An exception was thrown by the underlying delivery subsystem.

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace related to the conversation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02064: failure to serialize the delivery callback messages for conversation "{0}", message "{1}" to the binary format; the exception reported is: {2}**

---

**Cause:** An exception was thrown by the underlying delivery subsystem.

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace related to the conversation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02065: failure to serialize the delivery properties for conversation "{0}" to the binary format; the exception reported is: {1}**

**Cause:** An exception was thrown by the underlying delivery subsystem.

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace related to the conversation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02066: failure to deserialize the delivery properties for conversation "{0}" from the binary format; the exception reported is: {1}**

**Cause:** An exception was thrown by the underlying delivery subsystem.

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace related to the conversation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02067: failure to marshall the delivery callback messages for conversation "{0}", message "{1}" to XML; the exception reported is: {2}**

**Cause:** An exception was thrown by the underlying delivery subsystem.

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace related to the conversation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02068: Failure to call method "{0}" of the delivery persistence service with parameter "{1}". This operation is not supported.**

**Cause:** This was an internal error. Delivery persistence service does not support advanced persistence features such as lazy loading. The persistence manager should not have used those related operations.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

---

**ORABPEL-02069: The delivery service fails to load the message content from the data store; the exception reported is: {0}**

**Cause:** This was an internal error. Either the load() method was not working properly if the object type was imported into the process, or the delivery message content might have been edited manually in the data store.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02070: The delivery service fails to store the object "{0}" of type "{1}" to the data source. The exception reported is: {2}**

**Cause:** This was an internal error. The save() method was not working properly if the object type was imported into the process.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02071: failure to copy the object "{0}" of type "{1}"; the exception reported is: {2}**

**Cause:** An exception was thrown by the underlying persistence subsystem.

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace related to the object.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02072: failure to release the moniker "{0}"; the exception reported is: {1}**

**Cause:** An attempt was made to remove the last reference to a moniker before the object referred to by the moniker had been loaded.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02073: failure to delete the object "{0}" of type "{1}"; the exception reported is: {2}**

**Cause:** An exception was thrown by the underlying persistence subsystem.

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace related to the object.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02074: The target element with ID "{0}" cannot be located in the current XML document. The node "{1}" has a reference link to this element.**

**Cause:** The document was corrupt; it might have been edited manually.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02075: The element "{0}" does not have an "xsi:type" attribute specifying the schema type of the underlying Java object. An XML fragment cannot be properly unmarshalled to its Java representation without this information.**

**Cause:** The document was corrupt; it might have been edited manually.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02076: failure to deserialize an object from its moniker format; the exception reported is: {0}**

**Cause:** An exception was thrown by the underlying persistence subsystem.

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace related to the deserialization failure.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02077: Assertion failure: object "{0}" has negative reference count "{1}".**

**Cause:** This was an internal error. An object had a reference count less than zero because it fell out of scope and had its reference count decremented.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02078: failure to marshall the object "{0}" of type "{1}" to XML; the exception reported is: {2}**

**Cause:** An exception was thrown by the underlying marshalling subsystem.

---

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace related to the object.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02079: failure to prepare the object "{0}" of type "{1}" for marshalling; the exception reported is: {2}**

**Cause:** An exception was thrown by the underlying marshalling subsystem.

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace related to the object.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02080: failure to prepare the object "{0}" of type "{1}" for saving; the exception reported is: {2}**

**Cause:** An exception was thrown by the underlying persistence subsystem.

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace related to the object.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02081: failure to read an object's moniker from the deserializer stream; the exception reported is: {0}**

**Cause:** An exception was thrown by the underlying persistence subsystem.

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02082: failure to save the object "{0}" of type "{1}"; the exception reported is: {2}**

**Cause:** An exception was thrown by the underlying persistence subsystem.

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace related to the object.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02083: failure to unmarshall the object "{0}" of type "{1}" from XML; the exception reported is: {2}**

**Cause:** An exception was thrown by the underlying marshalling subsystem.

---

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace related to the object.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02084: failure to write an object's moniker into the serializer stream; the exception reported is: {0}**

**Cause:** An exception was thrown by the underlying persistence subsystem.

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02085: The metadata for object "{0}" is not registered with the persistence service.**

**Cause:** This was an internal error. Every Java object type in the scope must be registered.

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace related to the object.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02086: The metadata for object "{0}" does not contain an embedded moniker.**

**Cause:** This was an internal error. One or more of the linked variants in the scope did not contain an embedded moniker that contained the actual bytes defining the object.

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace related to the object.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02087: The node "{0}" is missing its reference identifier.**

**Cause:** This was an internal error. Any element with an "href" attribute did not contain a non-empty reference ID that could be resolved to another element in the document.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

---

**ORABPEL-02088: An instance's root scope cannot be routed.**

**Cause:** This was an internal error. The flow was not generated correctly by the BPEL compiler.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02089: failure to construct a valid scope activation key from the string "{0}".**

**Cause:** This was an internal error. The expected format was: "param1-param2", where the two parameters were: instance ID (integer) and scope ID (string) respectively.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02090: failure to unmarshall the metadata for the scope tree of instance "{0}"; the exception reported is: {1}**

**Cause:** This was an internal error. A variant's metadata did not contain "guid", "class name" and "ref-count" attributes; or the "ref-count" attribute was not an integral value while it should be.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02091: failure to release an instance's root scope from the scope tree.**

**Cause:** This was an internal error. The flow was not generated correctly by the BPEL compiler.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02092: failure to unmarshall a scope for the instance "{0}" from an XML document; the exception reported is: {1}**

**Cause:** An exception was thrown by the underlying marshalling subsystem.



---

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace related to the instance.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02093: The tag "{0}" is missing from the serialized XML text for the scope data for the instance "{1}".**

**Cause:** This was an internal error. The XML document for this instance did not contain a value for the tag named in the error message.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02094: The scope "{0}" is not defined in the current instance.**

**Cause:** This was an internal error. The scope was either closed or released, and it was not reachable.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02095: The scope associated with the block element "{0}" is not defined in the current instance.**

**Cause:** This was an internal error. The scope metadata was corrupt.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02096: The value "{0}" for the tag "{1}" in the serialized XML text for instance "{2}" is not a parseable integral value.**

**Cause:** This was an internal error. The value for tag named in the error message did not conform to the expected format.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Programmatic

**ORABPEL-02097: cannot read the XML model file for process "{0}" (revision "{1}"); the exception reported is: {2}**

**Cause:** An exception was thrown by the underlying operating system.

**Action:** Verify that the BPEL archive for the process named in the error message (for the cited revision) has been deployed correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02100: cannot find the content file "{0}" for process "{1}" (revision "{2}").**

**Cause:** The content file named in the error message might not have been deployed with the process named in the error message.

**Action:** Verify that the path named in the error message is correct, and that it refers to a file that has been included as a part of the deployment archive.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02101: cannot read the content file "{0}" for process "{1}" (revision "{2}"); the exception reported is: {3}**

**Cause:** The content file named in the error message might not have been deployed with the process named in the error message.

**Action:** Verify that the path named in the error message is correct, and that it refers to a file that has been included as a part of the deployment archive.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02102: Method "{0}" is missing.**

**Cause:** This was an internal error. The flow was not generated correctly by the BPEL compiler.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02103: The map for node element "{0}" is not defined in the process class.**

**Cause:** This was an internal error. The flow was not generated correctly by the BPEL compiler.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

---

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02104: New instances cannot be created when the process "{0}" is not active; existing instances are permitted to complete as usual.**

**Cause:** The process named in the error message was not active and therefore could not create new instances.

**Action:** The process life cycle can be changed to active through the EM console.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02106: The process "{0}" has not been turned on. No operations can be performed on the process or any instance belonging to the process if the process is turned off.**

**Cause:** The process named in the error message was not turned on; therefore it did not process any requests.

**Action:** Consult the administrator if this process has not been turned on.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02107: The process domain is unable to fetch the scope activation message with key "{0}" from the data source.**

**Cause:** The scope activation message with the key named in the error message was not found in the data source.

**Action:** This row may have been manually removed from the data source; in which case the instance should be aborted.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02108: cannot create a copy of the scope "{0}"**

**Cause:** This was an internal error. Scopes are not cloneable.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02109: The process domain is unable to deserialize the scope data for instance "{0}" from its binary representation; the exception reported is: {1}**

**Cause:** An exception was thrown from the underlying serialization subsystem.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02110: failure to marshall the scope data for instance "{0}" into XML; the exception reported is: {1}**

**Cause:** An exception was thrown from the underlying serialization subsystem.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02111: failure to serialize the scope data for instance "{0}" into a binary byte stream; the exception reported is: {1}**

**Cause:** An exception was thrown from the underlying serialization subsystem.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02112: The absolute scope ID "{0}" does not conform to the expected format for a scope identifier.**

**Cause:** This was an internal error. The expected scope ID format is (block id + relative scope id).

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02113: failure to fetch the return or header value from the root scope.**

**Cause:** This was an internal error. Only top-level scopes can contain return or header values.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02114: The requested variant "{0}" is not a primitive variant type. Reference variants cannot be cast to a primitive type.**

---

**Cause:** This was an internal error. The code accessing the variant named in the error message was assuming that that variant was a reference variant.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02115: The requested variant "{0}" is not a reference variant type. Primitive variants cannot be cast to a reference type.**

**Cause:** This was an internal error. The code accessing the variant named in the error message was assuming that that variant was a primitive variant.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02116: The variant object associated with key "{0}" in the scope tree is neither a primitive nor a reference variant.**

**Cause:** This was an internal error. The type of the declared variant "{0}" in the scope tree is not contained in the list of supported types (serializable and deserializable), including primitive (all Java primitive types) and reference (java.lang.String, java.util.Date, BPEL documents, EJB entity beans and one-dimensional arrays of any primitive or reference type).

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02117: A variable with key "{0}" is already declared in the current scope.**

**Cause:** This was an internal error. The flow was not generated correctly by the BPEL compiler.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02118: The variable "{0}" is not declared in the current scope. All variables must be declared in the scope before being accessed.**

**Cause:** This was an internal error. The flow was not generated correctly by the BPEL compiler.

---

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02121: failure to marshall the object "{0}" of class "{1}" to XML; the exception reported is: {2}**

**Cause:** An exception was thrown by the underlying marshalling subsystem.

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace related to the marshalling failure.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02122: The type class "{0}" is missing a "{1}" tag.**

**Cause:** The XML fragment for this type was missing a required tag; the XML document might have been edited manually.

**Action:** Set the logging level to debug mode. Check the log for the any exception related to the type class.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02123: The value "{0}" of the tag "{1}" in the serialized XML text for the type class "{2}" is not a parseable integral value.**

**Cause:** The value for the tag named in the error message did not conform to the expected format.

**Action:** Set the logging level to debug mode. Check the log for the any exception related to the type class.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02124: failure to deserialize the work item "{0}" from the binary format; the exception reported is: {1}**

**Cause:** This error contained the exceptions thrown from the underlying serialization subsystem.

**Action:** Set the logging level to debug mode. Check the log for the any exception related to the work item.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02125: failure to serialize the work item "{0}" to the binary format; the exception reported is: {1}**

---

**Cause:** An exception was thrown from the underlying serialization subsystem.

**Action:** Set the logging level to debug mode. Check the log for the any exception related to the work item.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02126: failure to deserialize the work items for instance "{0}" to the binary format; the exception reported is: {1}**

**Cause:** An exception was thrown from the underlying serialization subsystem.

**Action:** Set the logging level to debug mode. Check the log for the any exception related to the instance.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02127: failure to serialize the work items for instance "{0}" to the binary format; the exception reported is: {1}**

**Cause:** An exception was thrown from the underlying serialization subsystem.

**Action:** Set the logging level to debug mode. Check the log for the any exception related to the instance.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02128: failure to marshall the work item "{0}" to the XML format; the exception reported is: {1}**

**Cause:** An exception was thrown from the underlying marshalling subsystem.

**Action:** Set the logging level to debug mode. Check the log for the any exception related to the work item.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02129: cannot construct a valid work item key from the string "{0}"**

**Cause:** The string was of wrong format to construct a valid work item key. The expected key format is: "param1-param2-param3-param4", where the parameters are: instance ID (integer), node ID (string), scope ID (string) and count ID (integer) respectively.

**Action:** If the work item key string has not been constructed by the process domain, ensure that the key format is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**ORABPEL-02130: The tag "{0}" is missing from the serialized XML text for work item "{1}".**

**Cause:** The XML document for this instance was missing a value for the tag named in the error message.

**Action:** Set the logging level to debug mode. Check the log for the any exception related to the work item.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02131: The activity "{0}" is throwing a null exception.**

**Cause:** This was an internal error. Exceptions thrown from the activity cannot be null.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02132: The value "{0}" for the tag "{1}" in the serialized XML text for work item "{2}" is not a parseable integral value.**

**Cause:** The value for tag "{1}" was not an integer.

**Action:** If the work item XML has not been constructed by the process domain, ensure that the XML format is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02133: error while attempting to expire the work item "{0}" (located at node "{1}"); the exception reported is: "{2}"**

**Cause:** An exception was thrown from the underlying process execution subsystem.

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace related to the work item.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02134: error while attempting to extend the work item "{0}" (located at node "{1}"); the exception reported is: "{2}"**

**Cause:** An exception was thrown from the underlying process execution subsystem.

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace related to the work item.

**Level:** 1



---

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02135: error while attempting to execute the manage method on the work manager for node "{0}"; the exception reported is: "{1}"**

**Cause:** An exception was thrown from the underlying process execution subsystem.

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace related to the node.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02136: error while attempting to resume the work item "{0}" (located at node "{1}"); the exception reported is: "{2}"**

**Cause:** An exception was thrown from the underlying process execution subsystem.

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace related to the work item.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02137: error while attempting to suspend the work item "{0}" (located at node "{1}"); the exception reported is: "{2}"**

**Cause:** An exception was thrown from the underlying process execution subsystem.

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace related to the work item.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02138: The method invocation "{0}" is returning an invalid number of callback arguments.**

**Cause:** This was an internal error. More than one return value was returned. Currently, a maximum of one return value is permitted from a method invocation; the actual number of values returned for this invocation was "{1}".

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02139: The method invocation "{0}" is throwing an invalid exception object.**

---

**Cause:** This was an internal error. The exception object did not extend the Throwable class. The object thrown was of class "{1}".

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02140: failure to invoke the method "{0}" on the performer "{1}"; the exception reported is: "{2}"**

**Cause:** An exception was thrown while performing a callback to an activity.

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace related to the performer.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02141: error while attempting to execute the cancelPerform method on the work performer for node "{0}"; the exception reported is: "{1}"**

**Cause:** An exception was thrown while canceling an activity.

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace related to the node.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02142: error while attempting to execute the perform method on the work performer for node "{0}"; the exception reported is: "{1}"**

**Cause:** An exception was thrown while executing an activity.

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace related to the node.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02143: error while attempting to throw the exception "{0}" from the activity "{1}"; the exception reported is: "{2}"**

**Cause:** An exception is thrown while throwing an exception from an activity.

**Action:** Set the logging level to debug mode. Check the log for the underlying exception stack trace related to the activity.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**ORABPEL-02149: The instance identifier "{0}" is missing its domain ID; this ID specifies the BPEL domain from which the instance is generated.**

**Cause:** This was an internal error. The instance domain ID was not set upon creation and rehydration.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02150: The process domain is unable to fetch the activity "{0}" from the data source.**

**Cause:** The activity key "{0}" did not refer to a valid activity, or the activity was removed from the data source.

**Action:** Check the work\_item database table with the activity key; if the referred row cannot be found, check the audit trail for the instance.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02151: More than one activity from domain "{1}" is returned when querying with the key "{0}".**

**Cause:** Multiple activities were bound to the custom key "{0}". Only one activity should be returned per key.

**Action:** If the key is a user-specified custom key, ensure that the key is unique.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02152: The process domain is unable to fetch the instance with key "{0}" from the data source.**

**Cause:** The instance key "{0}" did not refer to a valid instance, or the instance was removed from the data source (this might have been the case if the BPEL global transaction was modified by an external source).

**Action:** Check the cube\_instance database table with the instance key; if the referred row cannot be found, check the server logs for traces related to this instance key.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02154: Multiple instances are returned when querying with the key "{0}", while only one instance is expected.**

**Cause:** Multiple instances of a business process were created with the key "{0}". Each instance should be uniquely identified by a key.

**Action:** If the key is a user-specified custom key, ensure that the key is unique.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02155: The process domain is unable to fetch the bytes for the business document "{0}" from the data source.**

**Cause:** The document key "{0}" did not refer to a valid document, or the document was removed from the data source.

**Action:** Check the xml\_document database table with the document key; if the referred row cannot be found, check the server logs for traces related to this document key.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02156: The process domain is unable to fetch the scope context data for the instance with key "{0}" from the data source.**

**Cause:** The instance key "{0}" did not refer to a valid instance, or the instance was removed from the data source.

**Action:** Check the cube\_scope database table with the instance key; if the referred row cannot be found, check the server logs for traces related to this instance key.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02157: failure to read the audit trail for instance "{0}"; the exception reported is: {1}**

**Cause:** An exception was thrown while writing the audit trail bytes to the in-memory buffer after those bytes were read from the data store.

**Action:** Set the logging level to debug mode, check the log for the underlying exception stack trace related to this in-memory buffer writing problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02158: failure to create the scope deserializer object for instance "{0}"; the exception reported is: {1}**

**Cause:** An exception was thrown while creating a deserializer from the scope bytes.

**Action:** Set the logging level to debug mode, check the log for the underlying exception stack trace related to this deserializer creation problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02159: The process domain is unable to fetch the invocation content for the message "{0}" from the data source.**

---

**Cause:** The message key "{0}" did not refer to a valid invocation message, or the invocation message was removed from the data source (this might have been the case if the BPEL global transaction was modified by an external source).

**Action:** Check the invoke\_message database table with the message key; if the referred row cannot be found, check the server logs for traces related to this message key.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02160: The process domain is unable to fetch the callback content for the message "{0}" from the data source.**

**Cause:** The message key "{0}" did not refer to a valid callback message, or the callback message was removed from the data source (this might have been the case if the BPEL global transaction was modified by an external source).

**Action:** Check the dlvc\_message database table with the message key; if the referred row cannot be found, check the server logs for traces related to this message key.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02161: The process domain is unable to fetch the audit detail bytes for the instance "{0}", detail ID "{1}" from the data store.**

**Cause:** The instance identifier "{0}" or detail identifier "{1}", or both, did not refer to a valid entry in the audit\_details table; this row might have been manually removed from the table.

**Action:** Check the audit\_details database table with the identifiers named in the error message; if the referred row cannot be found, check the server logs for traces related to these identifiers.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02162: The instance index "{0}" is not within the valid range.**

**Cause:** The index "{0}" for instance "{1}" was out of range.

**Action:** Change the index value in the xpath function or the facade API call to conform to the valid index range. Try a value between 1 and {2} (inclusive).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02163: cannot access scope "{0}"; scope is already released**

**Cause:** This was an internal error. An attempt was made to access a scope that has already been released.

**Action:** Contact Oracle Support Services. Provide the error message, the composite source, and the exception stack trace in the log files (with the logging level set to debug mode).

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-02164: An unknown cache policy "{0}" is specified for property "{1}".**

**Cause:** The cache policy "{0}" was not recognized. The list of valid cache policies is { lru, auto, soft-filo, soft-lru, hybrid }.

**Action:** Change the cache policy configuration property to one of the recognized values. The valid cache policies are lru, auto, soft-filo, soft-lru, and hybrid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02165: cannot initialize connection pool for connection factory "{0}"; the reason is {1}**

**Cause:** An exception was thrown while initializing the JMS connection pool.

**Action:** Set the logging level to debug mode, check the log for the underlying exception stack trace.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02166: failure to finalize the compensation node "{0}" for the second time; the exception reported is: {1}**

**Cause:** An exception was thrown while attempting to execute a compensation activity.

**Action:** Set the logging level to debug mode, check the log for the underlying exception stack trace.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02167: The process ("{1}", revision "{2}") for instance "{0}" is not loaded by the domain; the instance is marked as stale.**

**Cause:** The archive for process "{1}" of revision "{2}" might have been deleted from the domain manually. In this case, the domain would not have been able to mark all instances that belonged to the process as being stale.

**Action:** Check if the process has been manually deleted from the domain.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02168: A problem occurs while reading the sensor file "{0}"; the exception reported is: {1}**

**Cause:** An exception was thrown while trying to access the sensor file named in the error message.

---

**Action:** Ensure that the file exists. If it has been manually deleted, then redeploy the process.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02169: A problem occurs while reading the sensor action file "{0}"; the exception reported is: {1}**

**Cause:** An exception was thrown while trying to access the sensor action file named in the error message.

**Action:** Ensure that the file exists. If the file has been manually deleted, then redeploy the process.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02171: A problem occurs while updating the label status "{0}" in instance "{1}".**

**Cause:** This label was not detected during process compilation.

**Action:** Redeploy the process and try again. If the redeployment step does not work, then contact Oracle Support Services. Provide the error message, the composite source, and the exception trace in the server log files (with the logging level set to debug mode).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02177: failure to create the data source "{0}"; the exception reported is: {1}**

**Cause:** An exception was thrown while attempting to create a data source.

**Action:** Set the logging level to debug mode, check the log for the underlying exception trace related to this data source creation problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02178: the BPEL process "{0}" with revision "{1}" is not loaded.**

**Cause:** The process was not initialized properly, or the process was disabled.

**Action:** Set the logging level to debug mode, check the log for the underlying exception trace related to this process loading problem.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02180: The current JTA transaction is aborting due to an user rollback fault being thrown from the BPEL code.**

---

**Cause:** This exception was caused by a bpelx:rollback fault being thrown. The user had directed the BPEL engine to roll back the current JTA transaction.

**Action:** There is no action recommended.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02181: The current JTA transaction is marked as rollback-only when performing the activity "{0}".**

**Cause:** The reason was {1}.

**Action:** Check on the activity which invokes a subprocess or downstream process that results in the JTA transaction being marked as rollback-only.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02182: catching unhandled fault "{0}" when processing instance "{1}" for process "{2}"**

**Cause:** The exception was {3}.

**Action:** Check the error log file and the audit trail for instance "{1}" for more information. Try to use BPEL fault handlers to catch the faults in the BPEL process "{2}". If this is a system exception, please report this to the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02183: bpel engine can not execute activities without an active transaction. please debug the invoked subsystem on why the transaction is not in active status. the bpel instance id is "{0}".**

**Cause:** The reason was {1}.

**Action:** Consult the system administrator regarding this error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02184: The process domain was unable to serialize the activity guide milestone state data for instance "{0}" into a binary byte stream. The exception reported is: {1}**

**Cause:** This error is a wrapper for exceptions thrown from the underlying serialization sub-system.

**Action:** Please contact Oracle support. Be sure to provide the error message, the composite source and the exception trace in the log files (with loggers set to debug mode).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic



---

**ORABPEL-02185: The process domain was unable to deserialize the activity guide milestone state data for instance "{0}" from its binary byte representation. The exception reported is: {1}**

**Cause:** This error is a wrapper for exceptions thrown from the underlying serialization sub-system.

**Action:** Please contact Oracle support. Be sure to provide the error message, the composite source and the exception trace in the log files (with loggers set to debug mode).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02186: The process domain was unable to fetch the activity guide instance with key "{0}" from the datasource.**

**Cause:** The instance key "{0}" does not refer to a valid activity guide instance, or the instance has been removed from the datasource (this may be case if the BPEL global transaction has been modified by an external source).

**Action:** Check the "ag\_instance" database table; if the row cannot be found, check the server logs.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02187: Failed to load activity guide instance with key "{0}" from the datasource. The exception reported is: {1}**

**Cause:** This error is a wrapper for exceptions thrown while loading activity guide instance from the datasource.

**Action:** Please check the log for the underlying exception trace. Be sure to set the logging level to debug mode.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02188: Failed to insert activity guide instance with key "{0}" to the datasource. The exception reported is: {1}**

**Cause:** This error is a wrapper for exceptions thrown while inserting activity guide instance to the datasource.

**Action:** Please check the log for the underlying exception trace. Be sure to set the logging level to debug mode.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02189: Failed to update activity guide instance with key "{0}" in the datasource. The exception reported is: {1}**

**Cause:** This error is a wrapper for exceptions thrown while updating activity guide instance to the datasource.

---

**Action:** Please check the log for the underlying exception trace. Be sure to set the logging level to debug mode.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02190: Failed to evaluate expression "{0}" in field "{1}" in activity guide instance with key "{2}". The exception reported is: "{3}"**

**Cause:** The expression may not have been constructed correctly.

**Action:** Make sure that the expression is constructed correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02191: The activity guide definition at "{0}" could not be read.**

**Cause:** The activity guide definition either is missing or invalid.

**Action:** Make sure that the activity guide definition is available at the specified URL and that it is a valid XML document.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02192: The activity guide definition at "{0}" does not conform to the activity guide definition XML schema definition. The errors are "{1}"**

**Cause:** The activity guide definition does not conform to the activity guide definition XML schema.

**Action:** Make sure that the activity guide definition conforms to the activity guide definition XML schema definition.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02193: The activity guide definition at "{0}" could not be validated against the activity guide definition XML schema definition.**

**Cause:** The activity guide definition is missing.

**Action:** Make sure that the activity guide definition is available at the specified URL and that it is a valid XML document.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02194: The milestone instance with name "{0}" cannot be found in activity guide instance with ciKey "{1}".**

**Cause:** This is an internal error. This may have been caused by some logical errors in the program.

---

**Action:** Please contact Oracle support. Be sure to provide the error message, the composite source and the exception trace in the log files (with loggers set to debug mode).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02195: The "{0}" operation on milestone "{1}" with status "{2}" in activity guide instance "{3}" is invalid. This operation can only be performed on milestones with status "{4}".**

**Cause:** This is an internal error. This may have been caused by some logical errors in the program.

**Action:** Please contact Oracle support. Be sure to provide the error message, the composite source and the exception trace in the log files (with loggers set to debug mode).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02196: The "{0}" operation on activity guide instance "{1}" with status "{2}" is invalid. This operation can only be performed on activity guide instances with status "{3}".**

**Cause:** This is an internal error. This may have been caused by some logical errors in the program.

**Action:** Please contact Oracle support. Be sure to provide the error message, the composite source and the exception trace in the log files (with loggers set to debug mode).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02197: The "{0}" operation on activity guide instance "{1}" for milestone "{2}" is invalid.**

**Cause:** The milestone's expiration date is not set or milestone is configured to continue post expiration

**Action:** Please check configuration settings for the milestone "{2}" in BPEL designer.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02198: The current JTA transaction is aborting due to an user rollback fault being thrown. The upstream component should retry in a new JTA transaction upon catching this fault.**

**Cause:** This exception was caused by a global retry fault being thrown from downstream component. The user had directed the BPEL engine to roll back the current JTA transaction and retry within new JTA transactions for the specified number of times and retry interval.

---

**Action:** There is no action recommended.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02199: The transaction became inactive when executing activity "{0}" for instance "{1}", bpel engine can not proceed further without an active transaction. please debug the invoked subsystem on why the transaction is not in active status. the transaction status is "{2}".**

**Cause:** The reason was {3}.

**Action:** Consult the system administrator regarding this error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-02200: Master conversation ID is not available in context when executing work item "{0}" in component "{1}".**

**Cause:** Master conversation ID was not supplied by the master process when initiating the call to the detail process.

**Action:** Make sure the master process's invoke activity to have bpelx:invokeAsDetail and bpelx:detailLabel attributes properly supplied.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-03001: The process domain is unable to determine the database type. The version table contains the vendor type for the current data source. The exception reported is: {0}**

**Cause:** There was a problem with connecting to the data source where the version information was stored.

**Action:** Check all of the following to determine the location of the problem with connecting to the data source. Verify that the machine that hosts the data source is physically connected to the network. Verify that the connection pool properties as defined in the application server startup properties are valid. Verify that the database schema for OraBPEL has been installed in the data source.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-03002: The server is unable to look up the database schema version. The exception reported is: {0}**

**Cause:** There was a problem with connecting to the data source where the version information is stored.

**Action:** Check all of the following to determine the location of the problem with connecting to the data source. Verify that the machine that hosts the data source is physically connected to the network. Verify that the connection pool properties as defined in the application server startup properties are valid. Verify that the database schema for OraBPEL has been installed in the data source.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-03003: The database schema version {0} from the database does not match the version {1} expected by the server.**

**Cause:** The database schema for the SOA installation was not properly installed, or the installation was using a database schema installed for a prior release.

**Action:** The database schema currently in place has probably been configured for a previous release. Reinstall the database schema and start the server again.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-03004: The database table "version" does not contain a data source vendor type**

**Cause:** The database schema may have been modified by hand.

**Action:** Reinstall the database schema and start the process domain again.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-03005: The database table "version" does not contain a version guid.**

**Cause:** The database schema may have been modified by hand.

**Action:** Reinstall the database schema and start the server again.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-03010: error while trying to instantiate the class {0} as the adapter manifest for {1}, data source {2}, the exception reported is: {3}**

**Cause:** The adapter manifest class named in the error message was not in the system class path, or there was an incompatibility with the JDK used to compile the class and the current JVM version.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-03011: The class {0} (for the adapter manifest for {1}, data source {2}) does not implement the IServerAdaptorManifest interface**

**Cause:** This was an internal error. All adapter manifests registered with the system must conform to the IServerAdaptorManifest interface, and this one does not.

**Action:** Contact Oracle Support Services. Be sure to provide the error message and the exception trace in the log files (with loggers set to debug mode).

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-03012: The adapter manifest class name for {0}, data source {1} is not specified**

**Cause:** The adapter manifest class named in the error message was not in the system class path.

**Action:** Ensure that the Oracle BPEL libraries are set correctly in the system class path. If the libraries are configured correctly, the adapter configuration files might have been modified.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-03013: cannot instantiate an instance for the class {0}**

**Cause:** This was an internal error. Java class {0} that must be dehydrated or rehydrated within the OraBPEL server must implement the java.io.Serializable interface. And it must implement a default constructor.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-03410: error while trying to instantiate the agent class {0}; The exception reported was: {1}**

**Cause:** The agent class might have relied on a class that was not found in the class path, or it might have relied on a JDK feature that was not compatible with the current JVM version.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-03411: invalid agent class**

**Cause:** This was an internal error. The agent class {0} did not implement the IAgent interface. All agents managed by the system must implement this interface.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-03800: The process domain is not able to resolve which correlation set definition to apply to the received callback message for the operation {0}.**

---

**Cause:** Correlation set definitions were registered with the process domain using operation name and process ID. The callback message was most likely missing the process ID.

**Action:** If the callback client is external, check that the callback URL contains the process identifier. If the client is another BPEL process, check that the correlation set is defined correctly in the receiving BPEL process.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-03801: The received callback message is missing the operation name parameter. The process domain cannot resolve which correlation set definition to apply to the message without this parameter.**

**Cause:** The callback message did not pass the operation name in the SOAP action property.

**Action:** If the callback client is external, check that the operation name is being passed in the message correctly. If the client is another BPEL process, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-03802: The correlation set definition for operation {0}, process {1}, is not registered with the server.**

**Cause:** The correlation set was not defined in the process.

**Action:** Redeploy the process to the container.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-03803: The process domain cannot look up the engine bean; this bean is responsible for processing the callback of a received message. The exception reported is: {0}**

**Cause:** This was an internal error. The SOA installation was not configured properly.

**Action:** Check that the engine bean has been properly deployed to the server and can be properly mounted from a Java class.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-03804: The synchronous polling thread is timing out waiting for a result from instance "{0}".**

**Cause:** The callee was a durable synchronous process that had not reached its reply activity within the allotted timeout period.

**Action:** There may be a problem completing instance named in the error message. Check the process console for more information.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-03805: The process domain is unable to find the protocol handler for the conversation type "{0}".**

**Cause:** This was an internal error. Only the SOAP protocol handler is active by default.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with the logging set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-03806: The process domain is unable to process the callback for received message "{0}", for conversation "{1}", and the subscriber "{2}". The exception reported is: {3}**

**Cause:** This error contained exceptions thrown from the underlying callback handler layer.

**Action:** Check the exception trace in the log (with the logging level set to debug mode).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-03810: A similar receive activity is being declared in the same process.**

**Cause:** Another receive activity or equivalent (currently, onMessage branch in a pick activity) has already been enabled with the partnerLink "{0}", operation name "{1}" and correlation set "{2}" (or conversation ID). Appendix A - Standard Faults in the BPEL 1.1 specification specifies a fault should be thrown under these conditions.

**Action:** Redeploy the process after removing the conflicting receive activities.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-03811: No correlation sets are defined for operation "{0}" (process "{1}").**

**Cause:** There were no correlation sets defined for the operation and process named in the error message. All receive operations that do not use WS-Addressing to correlate messages must define at least one correlation set.

**Action:** Check the BPEL source to ensure that at least one correlationSet is defined for the operation named in the error message.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-03812: cannot find the property alias "{0}", message type "{1}"**



---

**Cause:** The property alias named in the error message was not defined in the BPEL/WSDL source.

**Action:** Check the BPEL/WSDL source to ensure that the property alias named in the error message has been defined.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-03813: failure to evaluate the correlationAlias query "{0}" on the element "{1}".**

**Cause:** The property alias was not defined correctly in the BPEL/WSDL source, or the payload is not as expected.

**Action:** Check the BPEL/WSDL source to ensure that property alias is defined correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04000: The process domain is unable to count the number of instances. The exception reported is: {0}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04001: The process domain is unable to count the number of instances for the process "{0}" (revision "{1}"). The exception reported is: {2}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04002: An attempt to fetch the instances using the where condition "{0}" from the data source fails. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source, or the SQL statement was constructed incorrectly.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04003: An attempt to fetch the work items using the where condition "{0}" from the data source fails. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source, or the SQL statement has been constructed incorrectly.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04004: The process domain is unable to insert the current log entries for the instance "{0}" to the audit trail table. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source, or the data segment was full.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04005: The process domain is unable to insert the current audit trail detail entries for the instance "{0}" to the audit details table. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source, or the data segment was full.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04006: The process domain is unable to store the work items for the synchronous instance "{0}" to the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source, or the data segment was full.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**ORABPEL-04007: The process domain is unable to store the audit trail for the synchronous instance "{0}" to the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source, or the data segment was full.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04008: Unable to set the auto commit level for the current data source connection. The exception reported is: {0}**

**Cause:** There was a problem accessing the SOA data source, or the current transaction settings prohibit this action.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04009: unable to commit the current data source transaction; the exception reported is: {0}**

**Cause:** There was a problem accessing the SOA data source, or the current transaction settings prohibit this action.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04010: The process domain is unable to purge the instances from the data source. The exception reported is: {0}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04011: The process domain is unable to delete the document "{0}" from the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

---

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04012: The process domain is unable to delete all the instances for the process "{0}" (revision "{1}") from the data source. The exception reported is: {2}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04013: The process domain is unable to fetch a list of the expired work items in the data source. The exception reported is: {0}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04014: The process domain is unable to look up the type for the instance "{0}" in the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04017: The process domain is unable to find the work items for the instance "{0}" in the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**ORABPEL-04018: The process domain is unable to find the audit trail entry for the instance "{0}" in the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04019: The process domain is unable to find the work items for the synchronous instance "{0}" in the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04020: The process domain is unable to find the audit trail for the synchronous instance "{0}" in the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04025: The process domain is unable to decode the properties for message GUID {0}, which are stored in column {1}; the exception reported is: {2}**

**Cause:** This is an internal error. The properties have not been encoded properly.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with the logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-04026: The process domain is unable to find any pending callback messages in the data source. The exception reported is: {0}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04027: The process domain is unable to find any pending invoke messages in the data source. The exception reported is: {0}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04028: The process domain is unable to find any pending subscriptions in the data source. The exception reported is: {0}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04029: The process domain is unable to mark all instances (and activities) with process GUID {0} as stale. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04030: An attempt to fetch the audit details for the instance "{0}" (detail ID {1}) from the data source fails. The exception reported is: {2}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04031: An attempt to fetch the audit details for the instance "{0}" from the data source fails. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

---

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04032: The process domain is unable to read the audit detail for detailId "{0}" from the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source, or the current transaction settings prohibit this action.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04033: The process domain is unable to fetch the document "{0}" from the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04034: The process domain is unable to find the closed instances for the domain "{0}" from the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04035: The process domain is unable to fetch the instance "{0}" from the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**ORABPEL-04036: The process domain is unable to fetch the scope activation message with key "{0}" from the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04037: The process domain is unable to fetch the work item "{0}" from the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04038: The process domain is unable to update or insert the document "{0}" into the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source, or the data segment was full.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04039: The process domain is unable to update the key table "{0}". The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04040: The process domain is unable to update the LOB column "{0}" in the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source, or the data segment was full.



---

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04041: The process domain is unable to update or insert the instance "{0}" into the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source, or the data segment was full.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04042: The process domain is unable to update or insert the serialized scope for the instance "{0}" into the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source, or the data segment was full.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04043: The process domain is unable to delete or insert the scope activation message with key "{0}" from the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source, or the data segment was full.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04044: The process domain is unable to update or insert the work item "{0}" in the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source, or the data segment was full.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04045: The process domain is unable to batch update or insert the work items for the instance "{0}" in the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source, or the data segment was full.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04046: The process domain is unable to batch insert a series of synchronous work items into the data source. The exception reported is: {0}**

**Cause:** There was a problem accessing the SOA data source, or the data segment was full.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04048: The process domain is unable to insert the delivery data for conversation "{0}", subscriber "{1}" in the data source. The exception reported is: {2}**

**Cause:** There was a problem accessing the SOA data source, or the data segment was full.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04049: The process domain is unable to select the delivery data for conversation "{0}" (subscriber "{1}") from the data source. The exception reported is: {2}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**ORABPEL-04050: The process domain is unable to select the delivery data for conversation "{0}" from the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04052: The process domain is unable to select the delivery data for subscriber "{0}" from the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04053: The process domain is unable to update the state of the delivery subscription "{1}" for conversation "{0}". The exception reported is: {2}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04054: The process domain is unable to update the state of the delivery subscription "{0}". The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04055: The process domain {0} is unable to delete handled delivery subscriptions. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04056: The process domain is unable to insert the delivery data for the message {0} and the operation {1} in the data source. The exception reported is: {2}**

**Cause:** There was a problem accessing the SOA data source, or the data segment was full.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04057: The process domain is unable to delete the delivery data for the message {0} from the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04058: The process domain "{0}" is unable to delete the handled delivery data from the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04059: The process domain is unable to select the delivery data for the message {0} from the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**ORABPEL-04060: The process domain is unable to select the delivery data for the message {0} and the operation {1} from the data source. The exception reported is: {2}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04061: The process domain is unable to update the state of the delivery the message {0}. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04062: The process domain is unable to delete the invocation data for the message {0} from the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04063: The process domain "{0}" is unable to delete the handled invocation data from the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04064: The process domain is unable to select the invocation data for the message {0} from the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04065: The process domain is unable to select the invocation data for the process "{0}" from the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04066: The process domain is unable to insert the invocation data for the message {0} and the operation {1} in the data source. The exception reported is: {2}**

**Cause:** There was a problem accessing the SOA data source, or the data segment was full.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04067: The process domain is unable to update the state of the invocation the message {0}. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04069: The process domain is unable to fetch a list of the stale instances belonging to the process "{0}" (revision "{1}"). The exception reported is: {2}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04076: The process domain is unable to look up the TX data source "{0}".**

---

**Cause:** The J2EE container was not configured properly; a data source with the expected name has not been created or has been removed.

**Action:** Verify that the machine hosting the data source is physically connected to the network. In addition, verify that the connection pool properties, as defined in the application server startup properties, are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04077: The process domain is unable to establish a connection with the data source with the connection URL "{0}". The exception reported is: {1}**

**Cause:** The J2EE container was not configured properly; the connection parameters for the data source might not have been correct.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04078: The process domain is unable to release its data source connection. The exception reported is: {0}**

**Cause:** There was a problem accessing the SOA data source, or the transaction has become corrupt.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04079: cannot read BLOB stream from the data source with key "{0}"; the exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source, or the current transaction settings prohibited this action.

**Action:** Verify that the machine hosting the data source is physically connected to the network. In addition, verify that the connection pool properties, as defined in the application server startup properties, are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04080: The data stream for the instance or activity object "{0}" is not found in the data source.**

**Cause:** The data stream with the instance or activity object key named in the error message was not found.

---

**Action:** Verify that the instance or activity key named in the error message refers to a valid instance or activity that has been started and not removed from the process domain.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04082: The process domain is unable to delete the instance "{0}" from the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04083: The process domain is unable to insert or update the exception entry for the activity "{0}" in the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source, or the data segment was full.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04084: The process domain is unable to delete the exception entry for the activity "{0}" from the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04085: The process domain is unable to find the activity in the domain "{0}" with the custom key "{1}". The exception reported is: {2}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR



---

**Impact:** Programmatic

**ORABPEL-04087: failure to find schedulable activities for domain "{0}". The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04090: The process domain is unable to read the serialized scope for the instance "{0}" from the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04091: The process domain is unable to read the indexes for the instance "{0}" from the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04092: The process domain is unable to update or insert the indexes for the instance "{0}" into the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source, or the data segment was full.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04099: The process domain is unable to find instances with root ID "{0}" in the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

---

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04100: The process domain is unable to find any invoke messages with the specified where condition in the data source. The exception reported is: {0}**

**Cause:** There was a problem accessing the SOA data source, or the SQL statement has been constructed incorrectly.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04101: The process domain is unable to find any callback messages with the specified where condition in the data source. The exception reported is: {0}**

**Cause:** There was a problem accessing the SOA data source, or the SQL statement has been constructed incorrectly.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04102: The process domain is unable to insert the process event for process "{0}" (revision "{1}") in the data source. The exception reported is: {2}**

**Cause:** There was a problem accessing the SOA data source, or the data segment was full.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04103: The process domain is unable to find any process events with the specified where condition in the data source. The exception reported is: {0}**

**Cause:** There was a problem accessing the SOA data source, or the SQL statement has been constructed incorrectly.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04108: The process domain is unable to select the attachment by the key "{0}" in the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04109: The process domain is unable to delete the attachment by the key "{0}" in the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04110: The process domain is unable to insert the attachment into the data source. The exception reported is: {0}**

**Cause:** There was a problem accessing the SOA data source, or the data segment was full.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04111: The process domain is unable to select the attachment reference "{0}" from the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04112: The process domain is unable to insert the attachment reference into the data source. The exception reported is: {0}**

---

**Cause:** There was a problem accessing the SOA data source, or the data segment was full.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04113: The process domain is unable to remove the attachment reference of the instance "{0}" in the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04121: An attempt to fetch the test details using the where condition "{0}" from the data source fails. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source, or the SQL statement has been constructed incorrectly.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04122: The process domain is unable to insert or update test details for the instance "{0}" in the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source, or the data segment was full.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04123: The process domain is unable to update the state of the following delivery messages "{0}". The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04124: The process domain is unable to update the state of the following delivery subscriptions "{0}". The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04125: The process domain is unable to select the number of detail instances for the master instance specified by the conversation ID "{0}".**

**Cause:** There was a problem accessing the SOA data source, or the SQL statement has been constructed incorrectly.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04126: The process domain is unable to select document references for the instance ID "{0}". The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04127: The process domain is unable to insert document references for the instance ID "{0}". The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source, or the data segment was full.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**ORABPEL-04128: The process domain is unable to select document references for delivery message GUID "{0}". The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04129: The process domain is unable to insert document references for delivery message GUID "{0}". The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source, or the data segment was full.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04132: cannot read CLOB stream from the data source with the key "{0}"; the exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source, or the current transaction settings prohibited this action.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Additionally verify that the connection pool properties as defined in the application server startup properties are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04138: The process domain is unable to store the test definition for process "{0}", revision "{1}", test suite "{2}", location "{3}" in the data source. The exception reported is: {4}**

**Cause:** There was a problem accessing the SOA data source, or the data segment was full.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04139: The process domain is unable to delete the test definition for the process "{0}", revision "{1}", test suite "{2}", location "{3}" in the data source. The exception reported is: {4}**

**Cause:** There was a problem accessing the SOA data source.

---

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04140: The process domain is unable to delete test definitions for the process "{0}", revision "{1}" in the data source. The exception reported is: {2}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04141: The process domain is unable to delete the events logged for the process "{0}", revision "{1}" from the data source. The exception reported is: {2}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04142: The process domain is unable to delete the events logged for the domain. The exception reported is: {0}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04143: The process domain is unable to insert the fault entry for the activity "{0}" from the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source, or the data segment was full.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**ORABPEL-04144: The process domain is unable to update the fault entry for the activity "{0}" from the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source, or the data segment was full.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04145: The process domain is unable to find the fault entry for the activity "{0}" from the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04146: The process domain is unable to delete the fault entry for the activity "{0}" from the data source. The exception reported is: {1}**

**Cause:** There was a problem accessing the SOA data source.

**Action:** Verify that the machine hosting the data source is physically connected to the network. Otherwise, verify that the data source connection parameters (user/password) are currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04147: The process domain was unable to fetch the activity guide instance with key "{0}" from the datastore. The exception reported is: {1}**

**Cause:** There is a problem accessing the SOA datasource.

**Action:** Please check that the machine hosting the datasource is physically connected to the network. Otherwise, check that the datasource connection parameters (user/password) is currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04148: The process domain was unable to update the activity guide instance with key "{0}" in the datastore. The exception reported is: {1}**

**Cause:** There is a problem accessing the SOA datasource, or the data segment may be full.



---

**Action:** Please check that the machine hosting the datasource is physically connected to the network. Otherwise, check that the datasource connection parameters (user/password) is currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04149: The process domain was unable to insert the activity guide instance with key "{0}" to the datastore. The exception reported is: {1}**

**Cause:** There is a problem accessing the SOA datasource, or the data segment may be full.

**Action:** Please check that the machine hosting the datasource is physically connected to the network. Otherwise, check that the datasource connection parameters (user/password) is currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04150: The process domain was unable to insert the audit counter for instance "{0}". The exception reported is: {1}**

**Cause:** There is a problem accessing the SOA datasource.

**Action:** Please check that the machine hosting the datasource is physically connected to the network. Otherwise, check that the datasource connection parameters (user/password) is currently valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04151: The process domain was unable to update the audit counter for the instance "{0}". The exception reported is: {1}**

**Cause:** Please check that the machine hosting the datasource is physically connected to the network. Otherwise, check that the datasource connection parameters (user/password) is currently valid.

**Action:** There is a problem accessing the SOA datasource, or the data segment may be full.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-04152: The process domain was unable to select the audit counter for the instance "{0}" from the datastore. The exception reported is: {1}**

**Cause:** Please check that the machine hosting the datasource is physically connected to the network. Otherwise, check that the datasource connection parameters (user/password) is currently valid.

**Action:** There is a problem accessing the SOA datasource.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**ORABPEL-04153: The process domain was unable to select for update on the audit counter for the instance "{0}" from the datastore. The exception reported is: {1}**

**Cause:** Please check that the machine hosting the datasource is physically connected to the network. Otherwise, check that the datasource connection parameters (user/password) is currently valid.

**Action:** There is a problem accessing the SOA datasource.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-05000: failure to fetch the dispatcher trace for the engine "{0}"; the exception reported is: {1}**

**Cause:** The dispatcher trace XML file was written to an output buffer that was not sized correctly.

**Action:** Contact Oracle Support Services. Provide the error message and the process that appeared to cause the problem.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-05001: The message handler for the class {0} is not registered.**

**Cause:** This was an internal error. It occurred because the dispatcher message handler was not registered in the MessageRegistry class.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-05002: error while attempting to process the message "{0}"; the reported exception is: {1}**

**Cause:** This error contained an exception thrown by the message handler.

**Action:** Check the exception trace in the log (with logging level set to debug mode).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-05003: No message local handler is implemented for the message "{0}".**

**Cause:** This was an internal error. It occurred when a remote message was handled locally.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Programmatic

**ORABPEL-05004: error while sending a batch message to the dispatch queue; the exception reported is: {0}**

**Cause:** There was a problem with enqueueing the message to the JMS queue or the dispatcher EJB could not be found in the JNDI context.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-05005: The process domain is unable to send a message to the JMS queue "{0}". The exception reported is: {1}**

**Cause:** There was a problem with enqueueing the message to the JMS queue; the queue configuration might be incorrect.

**Action:** Verify that the JMS service for the application server has been configured properly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-05006: error while scheduling a batch message with the dispatcher; the exception reported is: {0}**

**Cause:** There was a problem finding the dispatcher EJB in the current JNDI context.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-05007: there is no active transaction while scheduling a message with the dispatcher**

**Cause:** this usually happens if the underlying subsystem rollback back the transaction without bubbling up the system or transaction exception to the bpel layer

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-05213: The process identifier "{0}" for the BPEL process archive "{1}" is not valid.**

**Cause:** The process identifier for the BPEL process archive named in the message was not valid.

---

**Action:** Ensure that the deployment descriptor contained in the BPEL process archive named in the error message has a valid process ID. Process identifiers might start with a letter, a dollar sign (\$) or an underscore (\_); process characters (other than the first character) include a letter, a number, a dollar sign (\$), an underscore (\_) or a hyphen (-).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-05214: The process revision tag "{0}" for the BPEL process archive "{1}" is not valid.**

**Cause:** The process revision tag for the BPEL process archive named in the message was not valid.

**Action:** Ensure that the deployment descriptor contained in the BPEL process archive named in the error message has a valid revision tag. Valid revision tags may contain the following characters: a letter, a number, a dollar sign (\$), an underscore (\_), a hyphen (-), or a period (.).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-05215: The process domain is encountering the following errors while loading the process "{0}" (composite "{1}"): {2}.**

**Cause:** This error contained an exception thrown by the underlying process loader module.

**Action:** Check the exception trace in the log (with logging level set to debug mode). If there is a patch installed on the server, verify that the bpelcClasspath domain property includes the patch classes.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-05216: The class {0} for the process "{1}" (revision "{2}") does not implement the ICubeProcess interface.**

**Cause:** The current BPEL component named in the error message was probably compiled with an older version of SCAC. All process classes contained within the process domain must implement this interface.

**Action:** Recompile the SOA composite again.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-05217: error while attempting to instantiate the class {0} for the process "{1}" (revision "{2}"); the exception reported was: {3}**

**Cause:** This error contained an exception thrown by the underlying process loader module.

**Action:** Verify the exception trace in the log (with logging level set to debug mode).

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-05222: cannot find class for type {0}**

**Cause:** This was an internal error. The persistence manager for the type named in the error message could not be found in the class path. All required persistence managers should be registered by default.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-05225: The persistence manager class {0} for the type {1} does not implement the IPersistenceManager interface.**

**Cause:** This was an internal error. All persistence managers registered with the system must conform to the IPersistenceManager interface.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-05226: error while attempting to instantiate the persistence manager class {0} for type {1}; the exception reported was: {2}**

**Cause:** The persistence manager class named in the error message was not in the system class path or there was an incompatibility with the JDK used to compile the class and the current JVM version.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-05243: failure to obtain load lock for process "{0}"; the exception reported is: {1}**

**Cause:** The lock timeout was too small for the current load or there was a large number of process modification requests.

**Action:** The default timeout is 120 seconds. If this is not sufficient, customize the value using the JVM system property orabpel.process.lock.timeout, which is added to the JVM start line.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**ORABPEL-05244: failure to obtain load lock for process "{0}"; timed out after {1} seconds.**

**Cause:** The lock timeout was too small for the current load or there was a large number of process modification requests.

**Action:** The default timeout is 120 seconds. If this is not sufficient, customize the value using the JVM system property `orabpel.process.lock.timeout`, which is added to the JVM start line.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-05250: error while attempting to deploy the BPEL component file "{0}"; the exception reported is: {1}**

**Cause:** This error contained an exception thrown by the underlying deployment module.

**Action:** Verify the exception trace in the log (with logging level set to debug mode).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-05252: The bpel container could not find persistence manager {0} for type {1} in the classpath**

**Cause:** During dehydration the bpel container would serialize all the objects in the scope, each object in the scope should have a persistence manager registered or available in the classpath, otherwise bpel container would not know how to serialize the object for the dehydration store.

**Action:** Please make sure the persistence manager {0} for type {1} is available in classpath. please refer the documentation on how to write a persistence manager.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-08015: cannot find operation {0} of portType {1} in the WSDLs of composite "{2}"**

**Cause:** In the composite named in the error message, either the WSDL that defined portType named in the error message was changed, or there were multiple definitions of the same portType.

**Action:** Ensure that there is only one definition of portType named in the error message and redeploy the composite.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09004: cannot convert the object of the class {0} to XML text**

**Cause:** The object of the class named in the error message was not converted to XML text because of the exception: {1}

---

**Action:** Ensure that a valid marshaller is registered for the class named in the error message and refer to the BPEL developer guide about how to create a marshaller for a JAVA type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09006: A mismatch of a schema-generated object version cannot be used in the system.**

**Cause:** Either the XML schema class {0} has been compiled with an older version of SCHEMAC, or the BPEL process domain to which the class is deployed could not use the helper classes that were generated for this class.

**Action:** Recompile XML schema using the SCHEMAC tool that is bundled with the current process domain.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09007: error while attempting to instantiate the XML marshaller class {0}**

**Cause:** The exception reported was: {1}

**Action:** Ensure that marshaller is defined, and that it is available in the class path.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09008: error while marshalling the object to XML**

**Cause:** The class {0} did not implement the com.collaxa.cube.engine.xml.IMarshaller interface.

**Action:** Ensure that the marshaller class {0} implements the correct interface. All XMLmarshallers used in the BPEL must implement this interface.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09009: The BPEL service engine is not able to instantiate the schema registry.**

**Cause:** The class {0} (for the run-time schema registry) did not implement the ISchemaRegistry interface.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with logging level set to debug mode)

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-09010: error attempting to create the schema registry class {0}**

**Cause:** This is an internal error. The exception reported was: {1}

---

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with logging level set to debug mode)

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-09200: When performing the assign operation, the to node {0} is invalid.**

**Cause:** The node named in the error message was either null or an empty node set, and it was not an instance of org.w3c.Element.

**Action:** Verify the node value at line number {1} is not null and is an instance of org.w3c.Element.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09204: The result of from-spec is null.**

**Cause:** Either the from node value or the xpath query in the from node value was invalid.

**Action:** According to BPEL4WS spec 1.1 section 14.3, the from node value should not be empty. Verify the from node value at line number {0} in the BPEL source.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09205: The assign activity of the to node query is returning zero node.**

**Cause:** Either the to node data or the xpath query in the to node was invalid.

**Action:** According to BPEL4WS spec 1.1 section 14.3, verify the to node value at line number {1} in the BPEL source.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09207: There is an error while parsing the xml data.**

**Cause:** The XML data was not valid; the reason was {0}.

**Action:** Ensure the XML data is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09219: failure to save the element {0} during dehydration**

**Cause:** This element was not a root element and the scope had reference to this element. The scope should have references only to root element.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with logging level set to debug mode).

**Level:** 1



---

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-09221: failure to serialize the element {0} to the binary format during dehydration**

**Cause:** The exception reported was: {1}

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with logging level set to debug mode)

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-09222: failure to deserialize the document {0} from binary format during dehydration**

**Cause:** The exception reported was: {1}

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with logging level set to debug mode)

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09223: The assign activity part and query {0} are returning multiple nodes.**

**Cause:** The assign activity part and query named in the error message returned multiple nodes. It should return single node.

**Action:** According to BPEL4WS specification 1.1 section 14.3, the assign activity part and query named in the error message should not return multiple nodes. Verify the part and xpath query named in the error message at line number {1} in the BPEL source.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09224: cannot set a nonelement value to an element-based variable**

**Cause:** An attempt to assign a nonelement value to an element-based variable failed.

**Action:** Verify the BPEL source for invalid assign activities.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09225: cannot set a nonmessage value to a message-based variable**

**Cause:** An attempt to assign a nonmessage value to a message-based variable failed.

**Action:** Verify the BPEL source for invalid assign activities.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09226: cannot use a simple type variable in the setVariableData method**

**Cause:** It was not allowed to use simple type variable in setVariableData method.

**Action:** Verify the BPEL JAVA exec source code for invalid assign activities.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09227: The from-spec for {2} operation must return either an attribute list or an element list.**

**Cause:** The from-spec did not return an attribute list or an element list.

**Action:** Verify the assign activity for the operation named in the error message at line number {1} in the BPEL source.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09228: The message part {2} of the WSDL variable {3} is not an XML element; {4} operation cannot be performed.**

**Cause:** The operation named in the error message was not performed because the named message part of the WSDL variable named in the error message was not an XML element.

**Action:** Verify the message part named in the error message is a valid XML element at line number {1} in the BPEL source.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09229: The to-spec does not yield any data; the {1} operation cannot be performed.**

**Cause:** The operation named in the error message was not performed because to-spec did not yield any data.

**Action:** Verify the to-spec of the assign activity at line number {0} in the BPEL source.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09230: The parent of the selection result {1} does not exist or is not an XML element; the {2} operation cannot be performed.**

**Cause:** The operation named in the error message was not performed because the parent of the selection result named in the error message did not exist or was not an XML element.

**Action:** Verify the element of the assign activity at line number {0} in the BPEL source.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09231: The selection result at list entry {1} does not have a parent node; the {2} operation cannot be performed.**

**Cause:** The operation named in the error message was not performed because the selection result at the list entry named in the error message did not have a parent node.

**Action:** Verify the list entry of the assign activity at line number {0} in the BPEL source.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09232: The selection result at list entry {1} is not an XML node; the {2} operation cannot be performed.**

**Cause:** The operation named in the error message was not performed because the selection result at the list entry named in the error message was not an XML node.

**Action:** Verify the list entry of the assign activity at line number {0} in the BPEL source.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09233: The selection result at list entry {1} is not an XML element; the {2} operation cannot be performed.**

**Cause:** The operation named in the error message was not performed because the selection result at the list entry named in the error message was not an XML element.

**Action:** Verify the list entry of the assign activity at line number {0} in the BPEL source.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09234: The selection result of {1} is not an XML element; the {2} operation cannot be performed.**

**Cause:** The operation named in the error message was not performed because the selection result named in the error message was not an XML element.

**Action:** Verify the assign activity at line number {0} in the BPEL source and ensure the run-time data is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09240: failure of the copyList assign operation**

---

**Cause:** The element list specified by the to-spec used in the copyList operation was not contiguous.

**Action:** Verify the copyList operation of the assign activity at line number {0} in the BPEL source.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09241: The copyList assign operation fails due to a type mismatch.**

**Cause:** The from-list of copyList was element-based, while the to-list was not element-based.

**Action:** Verify the copyList operation of the assign activity at line number {0} in the BPEL source.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09242: The copyList assign operation fails due to a type mismatch.**

**Cause:** The from-list of the copyList operation was attribute-based, but the to-list was not attribute-based.

**Action:** Verify the copyList operation of the assign activity at line number {0} in the BPEL source.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09243: The copyList assign operation fails.**

**Cause:** The element returned from the to-list spec of the copyList operation did not have an element parent.

**Action:** Verify the copyList operation of the assign activity at line number {0} in the BPEL source and ensure that the run-time to-list data is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09244: The copyList assign operation fails.**

**Cause:** The element returned from the to-list spec of the copyList operation did not have a parent node.

**Action:** Verify the copyList operation of the assign activity at line number {0} in the BPEL source and ensure the run-time to-list data is valid

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09245: The copyList assign operation fails.**

---

**Cause:** The members of the to-list spec of the copyList operation did not share the same parent node.

**Action:** Verify the copyList operation of the assign activity at line number {0} in the BPEL source and ensure the run-time to-list data is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09248: cannot instantiate document builder {0}**

**Cause:** The reason was: {1}

**Action:** Ensure that document builder class named in the error message exists in the class path.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09249: error while parsing the XML text {0}**

**Cause:** The XML text was invalid because {1}.

**Action:** Verify that the XML text is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09250: error while creating the XML document**

**Cause:** The reason was {0}.

**Action:** Contact Oracle Support Services. Provide the error message and the exception trace in the log files (with logging level set to debug mode)

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**ORABPEL-09251: cannot perform copy XMLNS for prefix:{0}**

**Cause:** Namespaces conflicted: {1} and {2}

**Action:** Verify the from element data of the assign operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09500: An error occurs while processing the XPath expression; the expression is {0}.**

**Cause:** The XPath expression failed to execute; the reason was: {1}.

**Action:** Check the detailed root cause described in the exception message text and verify that the XPath query is correct.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09501: An error occurs while registering the XPath function {0}.**

**Cause:** Registering the XPath function failed; the reason was: {1}.

**Action:** Check the detailed root cause described in the exception message text and verify that the XPath function named in the error message is defined in the domain property file.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09502: The syntax error occurs while parsing XPath expression {0}, at position {1}.**

**Cause:** The XPath query syntax was wrong; the exception was: {2}

**Action:** Check the detailed root cause described in the exception message text and verify that the XPath expression named in the error message is correct. The XPath expression is defined in the BPEL process.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09503: an error occurs while parsing XPath expression {0}**

**Cause:** The XPath expression was invalid; the reason was: {1}.

**Action:** Check the detailed root cause described in the exception message text and verify that the XPath expression named in the error message is correct. The XPath expression is defined in the BPEL process.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09504: The XPath variable or expression {0} is empty at line {1}.**

**Cause:** An attempt to read or copy data referenced or computed by the XPath expression either had invalid data, according to the XML schema, or did not contain certain optional data.

**Action:** Ensure that the variable or expression result named in the error message is not empty. Enable XML schema validation of related variables to ensure the run-time data is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09505: The XPath variable or expression {0} is empty at line {1}.**

**Cause:** An attempt to create the missing to data by the XPath expression failed. Attribute ignoreMissingToData does not apply to this expression.

**Action:** Make sure the expression uses only: PathExpr ::= "/"RelativePathExpr  
RelativePathExpr ::= ForwardStep ("/" ForwardStep)\* ForwardStep ::=

---

(ForwardAxis QName) | AbbrevForwardStep AbbrevForwardStep ::= "@"?  
QName ForwardAxis ::= ("child" ":::") | ("attribute" ":::").

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09705: An error occurs while initializing BPEL variable {0}; the schema processor cannot find the element {1} in the following schemas: {2}.**

**Cause:** The XSD element on which the variable was based was not properly defined in XSD or the WSDL.

**Action:** Ensure that the element named in the error message is valid in the XSD or the WSDL.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09706: An error occurs while initializing BPEL variable {0} at line {1}; the schema processor cannot find type {2} for part {3} in the following schemas: {4}.**

**Cause:** The XSD type on which the variable was based was not properly defined in XSD or the WSDL.

**Action:** Ensure that the type named in the error message is valid in the WSDL.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09707: cannot initialize variable {0} at line {2}**

**Cause:** The reason was: {1}.

**Action:** Ensure that the variable named in the error message is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-09717: validation of variable {0} failed**

**Cause:** The reason was: {1}.

**Action:** Pleasehandle the exception in bpel.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20300: A problem occurs while processing reports data {0}.**

**Cause:** The DataCaptureAgency class reported an exception.

**Action:** Examine the log file to determine the problem.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**ORABPEL-20301: The Reporting Data Publisher {0} fails.**

**Cause:** The data publisher reported an exception.

**Action:** Examine the log file for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20302: A problem occurs while setting up a connection to the JMS destination {0} using the connection factory {1}.**

**Cause:** The JMS configuration was incorrect.

**Action:** Verify that the JMS configuration is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**ORABPEL-20303: An error occurs while publishing report data to the JMS destination {0}.**

**Cause:** The JMS configuration was incorrect.

**Action:** Verify that the JMS destination is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20304: The JMS destination lookup fails. The related report data will not be published.**

**Cause:** The JMS configuration was incorrect.

**Action:** Verify that the JMS destination or JNDI name {0} is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20305: The JMS connection factory lookup fails. The related report data will not be published.**

**Cause:** The JMS configuration was incorrect.

**Action:** Verify that JNDI name {0} is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20306: A problem occurs while releasing the JNDI resources used to publish to the destination {0}.**

**Cause:** The JMS configuration was incorrect.

**Action:** Verify that JNDI name is correct.



---

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**ORABPEL-20307: The custom data publisher class {0} cannot be loaded.**

**Cause:** The custom data publisher class named in the error message was not found.

**Action:** Verify that the class file and all dependencies can be loaded from the suitcase or from the application class path.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20308: The custom data publisher class {0} cannot be initialized properly.**

**Cause:** An attempt to create the custom data publisher class named in the error message failed.

**Action:** Examine the log file for a class creation exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20309: The sensor cannot be registered because it has no name.**

**Cause:** The sensor name was missing.

**Action:** Specify the sensor name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20310: The sensor {0} cannot be registered because a sensor with the same name is already registered.**

**Cause:** The sensor name was a duplicated name.

**Action:** Specify a unique sensor name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20311: The sensor-sensor action association for sensor {0}, action {1} cannot be created because no sensor named {2} exists in the registry.**

**Cause:** The sensor name was missing.

**Action:** Specify a valid sensor name in the association.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20312: The sensor-sensor action association for sensor {0}, action {1} cannot be created because no sensor action named {2} exists in the registry.**

---

**Cause:** The sensor name was missing.

**Action:** Register the sensor action before specifying an association.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20313: The sensor action cannot be registered because it has no name.**

**Cause:** The sensor name was missing.

**Action:** Specify the sensor action name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20314: The sensor action {0} cannot be registered because a sensor action with the same name is already registered.**

**Cause:** The sensor action name was a duplicated name.

**Action:** Specify a unique sensor action name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20315: An error occurs while loading sensors and sensor actions for the process {1}, revision {2} in the domain {0}.**

**Cause:** The loading of sensors failed.

**Action:** Examine the log file for the exception of loading sensors.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20316: No target is specified for sensor {0}.**

**Cause:** The target information was missing.

**Action:** Specify a target.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20317: The target {1} for sensor {0} is invalid.**

**Cause:** The target information was wrong.

**Action:** Specify a dollar sign (\$) before the variable name and ensure that the variable exists.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**ORABPEL-20318: The configuration for sensor {0} is missing.**

**Cause:** The sensor configuration was missing.

**Action:** The variableConfig element must be specified for variable sensors.  
Complete the variable sensor definition.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20319: The sensor {0} is a variable sensor but has activity or fault configurations defined.**

**Cause:** The sensor configuration was wrong.

**Action:** Remove the unnecessary configuration elements.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20320: The sensor {0} is a fault sensor but has activity or variable configurations defined.**

**Cause:** The sensor configuration was wrong.

**Action:** Remove the unnecessary configuration elements.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20321: The configuration for sensor {0} is missing.**

**Cause:** The sensor configuration was missing.

**Action:** The activityConfig element must be specified for activity sensors.  
Complete the activity sensor definition.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20322: The sensor {0} is an activity sensor but has variable or fault configurations defined.**

**Cause:** The sensor configuration was wrong.

**Action:** Remove the unnecessary configuration elements.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20323: The sensor {0} is invalid because {1} is an unrecognized sensor kind.**

**Cause:** The sensor kind was wrong.

**Action:** Specify a valid sensor kind.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20324: The sensor action {0} is invalid because it publishes to a JMS destination but no destination is specified.**

**Cause:** The JMS destination was missing in the sensor action.

**Action:** Specify the JMS destination property in the sensor action.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20325: The sensor action {0} is invalid because it publishes to a JMS destination but no connection factory is specified.**

**Cause:** The JMS connection factory information was wrong.

**Action:** Specify the JMS connection factory.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20326: The sensor action {0} is invalid because it publishes to a custom publisher but no publisher class is specified.**

**Cause:** The custom publisher class name was wrong.

**Action:** Specify the fully qualified class name of the custom data publisher.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20327: The sensor action {0} is invalid because {1} is an unrecognized publish type.**

**Cause:** The publish type was wrong.

**Action:** Specify a valid publish type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20328: The sensor action {0} is invalid because the associated sensor {1} cannot be found.**

**Cause:** The associated sensor named in the error message was missing.

**Action:** Ensure that sensor names used in the sensor action file match those defined in the sensor file.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20329: The sensor action {0} is invalid because the connection name is not specified.**

---

**Cause:** The connection name in the sensor action named in the error message was missing.

**Action:** Specify the connection name property in the sensor action.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20330: The Sensor.xsd schema cannot be loaded from the class path.**

**Cause:** The installation of Sensor.xsd was missing

**Action:** Ensure that the Sensor.xsd file has not been modified in any way.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20331: The JMS Adapter cannot be loaded from the class path.**

**Cause:** The loading of the JMS adapter failed.

**Action:** Ensure that the JMS adapter has been properly deployed in the application server.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20501: An error occurs while loading monitor model for the process {1}, revision {2} in the domain {0}.**

**Cause:** The loading of monitor model failed.

**Action:** Examine the log file for the exception of loading monitor model.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20502: An error occurs while monitor database executing command {1}, for database {0}.**

**Cause:** The monitor database command execution failed.

**Action:** Examine the log file for the exception of executing a monitor database command.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20503: An error occurs while monitor business indicator evaluates the xpath {0}.**

**Cause:** The monitor business indicator xpath evaluation execution failed.

**Action:** Examine the log file for the exception of executing a monitor business indicator xpath evaluation.

**Level:** 1

---

Type: ERROR

Impact: Programmatic

**ORABPEL-20504: An error occurs while monitor process activity execution for activity {0} and event {1}.**

**Cause:** The monitor process activity execution failed.

**Action:** Examine the log file for the exception of executing a monitor process activity.

Level: 1

Type: ERROR

Impact: Programmatic

**ORABPEL-20505: An error occurs while monitor creates the registry. This error does not interfere in the BPEL process.**

**Cause:** The monitor files are not found or an error occurs while loading the monitor files.

**Action:** Examine the log file for the exception of creating a monitor registry.

Level: 1

Type: WARNING

Impact: Programmatic

**ORABPEL-20506: An error occurs while monitor loads the configuration.**

**Cause:** The monitor config load failed.

**Action:** Examine the log file for the exception of loading a monitor config.

Level: 1

Type: ERROR

Impact: Programmatic

**ORABPEL-20507: An error occurs while monitor publishes data to BAM.**

**Cause:** The monitor BAM publish failed.

**Action:** Examine the log file for the exception of publishing monitor data to BAM publisher.

Level: 1

Type: ERROR

Impact: Programmatic

**ORABPEL-20508: An error occurs while monitor get the activity path information.**

**Cause:** The monitor get activity path failed.

**Action:** Examine the log file for the exception of getting activity path information.

Level: 1

Type: ERROR

Impact: Programmatic

**ORABPEL-20509: Composite: {0}, Process: {1}, Process Revision: {2}, Business Indicator: {3}, Metric: {4}, Activity: {5}, Evaluation Event: {6}.Skipping evaluation**

---

**for all metrics in this Business Indicator/Activity/Evaluation Event. No rows will be inserted.**

**Cause:** The XPATH Evaluation of Business Indicator failed.

**Action:** Check XPath expression in conjunction with process variable state.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20510: Composite: {0}, Process: {1}, Process Revision: {2}, Business Indicator: {3}, Metric: {4}, Activity: {5}, Evaluation Event: {6}.A null value will be inserted for this metric.**

**Cause:** The Metric XPATH Evaluation of Business Indicator failed.

**Action:** Check Metric XPath expression in conjunction with process variable state.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORABPEL-20511: An attempt to connect BAM failed. Error Message: {0}**

**Cause:** Either BAM adapter credentials are incorrect or SOA/BAM trusted domain configuration is missing.

**Action:** See "Configuring the Oracle BAM Adapter" in Oracle Fusion Middleware Administrators Guide for Oracle SOA Suite for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic





---

## ORAMED-01001 to ORAMED-09001

**ORAMED-01001: Error occurred while assigning to target "{0}" using expression "{1}".**

**Cause:** Error occurred while assigning to target "{0}" using expression "{1}".

**Action:** Check if source message has right values or source expression is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-01002: Metadata error occurred while assigning. Check if source and target expression are valid. ["{0}"].**

**Cause:** Metadata error occurred while assigning. Check if source and target expression are valid. ["{0}"].

**Action:** Modify source or target for valid expression. Empty string, null and invalid expressions are not allowed

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-01003: Invalid source used while assigning. Check if source expression is valid. ["{0}"].**

**Cause:** Invalid source used while assigning. Check if source expression is valid. ["{0}"].

**Action:** Modify source for valid expression.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-01004: Source expression "{0}" resulted in multiple node for source message which is not supported.**

**Cause:** Source expression "{0}" resulted in multiple node for source message which is not supported.

**Action:** Check the expression for correctness. Modify the source expression based on the requirement, or contact Oracle Support Services.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-01005: Target creation for target expression "{0}" failed.**

**Cause:** Target creation for target expression "{0}" failed.

**Action:** Check if the target expression is valid, otherwise, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-01006: Encountered variable which is not supported or implemented "{0}".**

**Cause:** Encountered variable which is not supported or implemented "{0}".

**Action:** Check if source and target expression for valid variable like \$in, \$out, \$initial and so forth, otherwise Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-01007: Header variable "{0}" not recognized.**

**Cause:** Header variable "{0}" not recognized.

**Action:** Header variable should be of the format \$in.header.<prefix>\_<root-elem>. Fix the header variable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-01008: Property "{0}" not found in "{1}" message.**

**Cause:** Property "{0}" not found in "{1}" message.

**Action:** Check source and target expression for valid property name otherwise Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-01009: Failed to assign element "{0}" to element "{1}". Parent node not found.**

**Cause:** Failed to assign element "{0}" to element "{1}". Parent node not found.

**Action:** Check target expression for valid element associated with proper owner document, otherwise Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**ORAMED-01010: Failed to assign source "{0}" to target part "{1}". Assigning Text data to part is not supported unless target part is available.**

**Cause:** Failed to assign source "{0}" to target part "{1}". Assigning Text data to part is not supported unless target part is available.

**Action:** Check source and target expression for valid expression, otherwise Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-01011: Failed to assign attachment "{0}" from source to target. Attachment not available in source message.**

**Cause:** Failed to assign attachment "{0}" from source to target. Attachment not available in source message.

**Action:** Check source expression is valid, otherwise Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-01101: Error evaluating filter expression.**

**Cause:** Error evaluating filter expression.

**Action:** Ensure that the filter expression is valid, otherwise Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-01102: Error evaluating filter expression, "{0}".**

**Cause:** Error evaluating filter expression, "{0}".

**Action:** Ensure that the filter expression metadata is valid, otherwise Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-01201: Error occurred while transforming payload using "{0}" for target part "{1}".**

**Cause:** Error occurred while transforming payload using "{0}" for target part "{1}".

**Action:** Review the XSL or source payload. Either the XSL defined does not match with the payload or payload is invalid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**ORAMED-01202: Fatal error occurred while transforming payload using XSL "{0}" for target part "{1}".**

**Cause:** Fatal error occurred while transforming payload using XSL "{0}" for target part "{1}".

**Action:** Review the XSL for any syntax error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-01203: No part exists with name "{0}" in source message.**

**Cause:** No part exists with name "{0}" in source message.

**Action:** Review the transformation definition in mplan. Contact Oracle Support Services if the error cannot be fixed.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-01204: Initial source message is not available in the context. Failed evaluating "{0}".**

**Cause:** Initial source message is not available in the context. Failed evaluating "{0}".

**Action:** Review the transformation/assign definition in mplan. Accessing initial source message is not supported during callback.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-01301: Schematron validation fails with error "{0}".**

**Cause:** Schematron validation fails with error "{0}".

**Action:** Fix the payload.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-01302: Response payload for operation "{0}" is invalid.**

**Cause:** Response payload for operation "{0}" is invalid.

**Action:** Response received by Mediator was either invalid or null. Examine why the service being invoked by Mediator is returning a null/invalid response. You can also try invoking the service directly and see if it sends back proper response.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-01303: XSD schema validation fails with error "{0}".**

**Cause:** XSD schema validation fails with error "{0}".

**Action:** Fix payload and resubmit.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-01304: Schematron validation failure.**

**Cause:** Schematron validation failure.

**Action:** Fix payload or schematron definition and resubmit.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-01305: Group ID validation failure.**

**Cause:** Group ID validation failure.

**Action:** XPATH Expression returned null Group Id. Check the XPATH expression, fix the payload and resubmit.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-01306: Sequence ID validation failure."{0}"**

**Cause:** Sequence ID validation failure."{0}"

**Action:** SequenceID value is incorrect. Either XPATH Expression returned null or sequenceID value does not fall within the sequence range. Check the XPATH expression, fix the payload and resubmit.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-01351: Unable to execute "{0}" method on callout instance of "{1}"**

**Cause:** Unable to execute "{0}" method on callout instance of "{1}"

**Action:** Check server log for any exceptions. Check if there is an issue in implementation of Java callout class.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-01360: Wrong source message type. Neither a NormalizedMessage nor a BusinessEvent, message type class :{1}**

**Cause:** Wrong source message type. Neither a NormalizedMessage nor a BusinessEvent, message type class :{1}

**Action:** Contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-01361: Mediator does not support the Resequencing strategy."{0}"**

---

**Cause:** Mediator does not support the Resequencing strategy "{0}"

**Action:** Mediator does not support the Resequencing strategy. Refer to the documentation of resequencer for more details. You can also contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-01362: Unexpected runtime error occurred while processing the message.**

**Cause:** Unexpected runtime error occurred while processing the message.

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-01363: Mediator does not have content to respond to the request-response type operation "{0}".**

**Cause:** Mediator does not have content to respond to the request-response type operation "{0}".

**Action:** Examine your design to rectify, or reset the property oracle.soa.mediator.twoway.allowNullReply to true.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-02001: This error occurs because of invalid filter expression "{0}".**

**Cause:** This error occurs because of invalid filter expression "{0}".

**Action:** Review the filter expression and check for possible syntax errors in the filter expression.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-02002: Invalid filter metadata "{0}". Either no filter expression specified or expression may be invalid.**

**Cause:** Invalid filter metadata "{0}". Either no filter expression specified or expression may be invalid.

**Action:** Fix the filter condition metadata.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-02051: Invalid callout implementation "{0}".**

**Cause:** Invalid callout implementation "{0}".

**Action:** Fix the callout implementation.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-02101: Cannot load XSL transform into the cache for XSL or XSLT "{0}".**

**Cause:** Cannot load XSL transform into the cache for XSL or XSLT "{0}".

**Action:** Check XSL file for any syntax error and fix the same.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-02102: Invalid part type "{0}".**

**Cause:** Invalid part type "{0}".

**Action:** Ensure that the parts provided in transformation/xpath are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-02103: Invalid assign expression "{0}".**

**Cause:** Invalid assign expression "{0}".

**Action:** Check assign xpath expression for any syntax error. If there are any syntax errors, correct the xpath expression.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-02201: Could not load schema document into the cache for XSD "{0}".**

**Reason :** {1}

**Cause:** Could not load schema document into the cache for XSD "{0}". Reason : {1}

**Action:** Check the XSD schema for any syntax error and fix the same.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-02202: Invalid part name in metadata for schematron validator "{0}".**

**Cause:** Invalid part name in metadata for schematron validator "{0}".

**Action:** Fix the schematron metadata.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-02203: Could not load schematron file {0}.**

**Cause:** Could not load schematron file {0}.

**Action:** Provide the correct schematron document.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-02204: Could not load wsdl interface for message with component dn "{0}".**

**Cause:** Could not load wsdl interface for message with component dn "{0}".

**Action:** Fix the component to point to valid wsdl.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-02205: Schematron document for schematron file {0} is invalid.**

**Cause:** Schematron document for schematron file {0} is invalid.

**Action:** Fix the schematron document.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-02206: Could not create XSD validator for schema with target namespace "{0}" for message "{1}".**

**Cause:** Could not create XSD validator for schema with target namespace "{0}" for message "{1}".

**Action:** Check XML schema for any syntax error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-02301: Could not load mediator mplan information. Reason : {0}**

**Cause:** Could not load mediator mplan information. Reason : {0}

**Action:** Check your mediator mplan for any syntax error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-02302: Could not load metadata manager. Reason : {0}.**

**Cause:** Could not load metadata manager. Reason : {0}.

**Action:** Check your composite configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-02303: Composite reference {0} not found for operation {1}.**

**Cause:** Composite reference {0} not found for operation {1}.

**Action:** Check your composite.



---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-02304: Could not load mediator mplan for componentDN "{0}" . It may be undeployed.**

**Cause:** Could not load mediator mplan for componentDN "{0}" . It may be undeployed.

**Action:** Using SOA Enterprise Manager, check if composite is deployed. If the composite is not deployed, you can try deploying the composite again.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-02305: Could not find mediator case for case name "{0}" . Mediator component may be redeployed with different case names.**

**Cause:** Could not find mediator case for case name "{0}" . Mediator component may be redeployed with different case names.

**Action:** This message will be put in error state. Fix the mplan by adding the right case and then recover it through EM.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-02306: Encountered message "{0}" containing streaming attachment for mediator with one or more parallel case. Message will not be processed and if available any other mediator cases will be ignored.**

**Cause:** Encountered message "{0}" containing streaming attachment for mediator with one or more parallel case. Message will not be processed and if available any other mediator cases will be ignored.

**Action:** This message will be errored out. Mediator with one or more parallel case for streaming attachment is not supported.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-02307: Encountered message "{0}" containing streaming attachment for mediator with resequencer enabled. Message will not be processed.**

**Cause:** Encountered message "{0}" containing streaming attachment for mediator with resequencer enabled. Message will not be processed.

**Action:** This message will be errored out. Mediator with resequencer type case for streaming attachment is not supported.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-02401: Got invalid response from decision service : {0}**

---

**Cause:** Got invalid response from decision service : {0}

**Action:** Ensure that the decision service used by the mediator is configured properly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-02402: Could not invoke decision service : {0}**

**Cause:** Could not invoke decision service : {0}

**Action:** Ensure that the decision service used by the mediator is configured properly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-02403: Dynamic mplan returned by decision service is invalid. Mplan returned by decision service : {0}**

**Cause:** Dynamic mplan returned by decision service is invalid. Mplan returned by decision service : {0}

**Action:** Ensure that the decision service used by the mediator is configured properly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03001: Unable to lock Resequencer Groups for container ID "{0}" and timestamp "{1}".**

**Cause:** Unable to lock Resequencer Groups for container ID "{0}" and timestamp "{1}".

**Action:** Unable to lock Resequencer Groups. Check your database connection.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03002: Unable to retrieve locked Resequencer Groups for containerId "{0}" and timestamp "{1}".**

**Cause:** Unable to retrieve locked Resequencer Groups for containerId "{0}" and timestamp "{1}".

**Action:** Unable to retrieve lock Resequencer Groups. Check your database connection.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03003: Unable to store Resequencer Group."{0}".**

**Cause:** Unable to store Resequencer Group."{0}".

---

**Action:** Unable to store Resequencer Group. Check your database connection or check data.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03004: Unable to store Resequencer Message."{0}"**

**Cause:** Unable to store Resequencer Message."{0}"

**Action:** Unable to store Resequencer Message. Check your database connection or check data.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03005: Unable to unlock Resequencer Groups for container ID "{0}" and timestamp "{1}".**

**Cause:** Unable to unlock Resequencer Groups for container ID "{0}" and timestamp "{1}".

**Action:** Unable to unlock Resequencer Groups. Check your database connection.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03006: Unable to retrieve Resequencer message. "{0}"**

**Cause:** Unable to retrieve Resequencer message. "{0}"

**Action:** Unable to retrieve Resequencer message. Check your database connection.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03101: Unable to get subscriptions for message "{0}"**

**Cause:** Unable to get subscriptions for message "{0}"

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03102: Error creating cache for cache policy "{0}". Reason : {1}**

**Cause:** Error creating cache for cache policy "{0}". Reason : {1}

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**ORAMED-03103: Cannot load Cache entry with NULL or EMPTY key.**

**Cause:** Cannot load Cache entry with NULL or EMPTY key.

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03104: Do not cache RuntimeESBSystem object for NULL or EMPTY system GUID.**

**Cause:** Do not cache RuntimeESBSystem object for NULL or EMPTY system GUID.

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03105: Could not read WSDL Definition for WSDL with NULL or EMPTY file name.**

**Cause:** Could not read WSDL Definition for WSDL with NULL or EMPTY file name.

**Action:** The WSDL file being read is not available or reachable. Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03106: Do not cache WSDL Definition for NULL or EMPTY WSDL file name.**

**Cause:** Do not cache WSDL Definition for NULL or EMPTY WSDL file name.

**Action:** The WSDL file being read is not available or reachable. Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03107: Could not read Schema Document for XSD with NULL or EMPTY file name.**

**Cause:** Could not read Schema Document for XSD with NULL or EMPTY file name.

**Action:** The XSD schema file being read is not available or reachable. Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**ORAMED-03108: Do not cache Schema Document for NULL or EMPTY XSD file name.**

**Cause:** Do not cache Schema Document for NULL or EMPTY XSD file name.

**Action:** The XSD schema file being read is not available or reachable. Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03109: Could not read parsed filter expression for NULL or EMPTY expression.**

**Cause:** Could not read parsed filter expression for NULL or EMPTY expression.

**Action:** The filter expression is null or empty. Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03110: Information to process an incoming callback message is not available.**

**Cause:** Information to process an incoming callback message is not available.

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03201: Retry of deferred message failed.**

**Cause:** Retry of deferred message failed.

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03202: Retry of callback message failed.**

**Cause:** Retry of callback message failed.

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03203: Retry of timeout message failed.**

---

**Cause:** Retry of timeout message failed.

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03301: Unexpected exception in case execution "{0}".**

**Cause:** Unexpected exception in case execution "{0}".

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03302: Unexpected exception in one-way operation "{0}" on reference "{1}".**

**Cause:** Unexpected exception in one-way operation "{0}" on reference "{1}".

**Action:** Check whether the reference service is properly configured and running or look at exception for analyzing the reason or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03303: Unexpected exception in request response operation "{0}" on reference "{1}".**

**Cause:** Unexpected exception in request response operation "{0}" on reference "{1}".

**Action:** Check whether the reference service is properly configured and running or look at exception for analyzing the reason or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03304: Unexpected exception in asynchronized request execution "{0}".**

**Cause:** Unexpected exception in asynchronized request execution "{0}".

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03401: Context lookup failed "{0}".**

**Cause:** Context lookup failed "{0}".

**Action:** Ensure that the topic is mapped to a JNDI tree.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03402: Error creating "{0}".**

**Cause:** Error creating "{0}".

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03403: Subscriber does not exist for system "{0}".**

**Cause:** Subscriber does not exist for system "{0}".

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03405: Error converting field "{0}".**

**Cause:** Error converting field "{0}".

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03406: Publisher does not exist for system "{0}".**

**Cause:** Publisher does not exist for system "{0}".

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03408: Unable to store deferred message "{0}".**

**Cause:** Unable to store deferred message "{0}".

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03409: Invalid, premature, or already-handled callback message. No correlation found for message with conversation ID "{0}".**

---

**Cause:** Invalid, premature, or already-handled callback message. No correlation found for message with conversation ID "{0}".

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03501: Unable to start transaction; transaction status is "{0}".**

**Cause:** Unable to start transaction; transaction status is "{0}".

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03502: Unable to resume transaction.**

**Cause:** Unable to resume transaction.

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03503: Unable to commit transaction. Transaction has been rolled back.**

**Cause:** Unable to commit transaction. Transaction has been rolled back.

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03504: Unable to rollback transaction.**

**Cause:** Unable to rollback transaction.

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03505: "{0}" object not found in JNDI tree.**

**Cause:** "{0}" object not found in JNDI tree.

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1



---

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03506: Unable to get transaction status.**

**Cause:** Unable to get transaction status.

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03507: Unable to set rollback only for transaction; transaction status is "{0}".**

**Cause:** Unable to set rollback only for transaction; transaction status is "{0}".

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03508: One of the routing rule execution resulted in a transaction rollback.**

**Cause:** One of the routing rule execution resulted in a transaction rollback.

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03509: Unable to suspend transaction.**

**Cause:** Unable to suspend transaction.

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03510: Error obtaining Transaction Manager.**

**Cause:** Error obtaining Transaction Manager.

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03511: "{0}" object not found in jndi tree**

---

**Cause:** "{0}" object not found in jndi tree

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03601: Unable to create transformer. It could be because of transformation file or configuration issues. Reason : "{0}"**

**Cause:** Unable to create transformer. It could be because of transformation file or configuration issues. Reason : "{0}"

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03602: Unable to create document.**

**Cause:** Unable to create document.

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03603: Unable to register base function "{0}" for "{1}".**

**Cause:** Unable to register base function "{0}" for "{1}".

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03651: Unable to create callout instance for "{0}".**

**Cause:** Unable to create callout instance for "{0}".

**Action:** Ensure that your callout configuration is correct. Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03652: Unable to execute "{0}" method on callout instance of "{1}".**

**Cause:** Unable to execute "{0}" method on callout instance of "{1}".

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03701: Unable to configure xpath transformer.**

**Cause:** Unable to configure xpath transformer.

**Action:** Check log file for any exceptions to fix the configuration otherwise contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03801: Unable to initialize filter/validator. "{0}" is not supported.**

**Cause:** Unable to initialize filter/validator. "{0}" is not supported.

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03802: Unable to create initial context.**

**Cause:** Unable to create initial context.

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-03803: Unable to initialize Container ID Manager.**

**Cause:** Unable to initialize Container ID Manager.

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-04001: Error executing service due to server down "{0}". Reason : {1}**

**Cause:** Error executing service due to server down "{0}". Reason : {1}

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-04002: Error executing service due to server down "{0}". Reason : {1}**

---

**Cause:** Error executing service due to server down "{0}". Reason : {1}

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-04004: Error persiting reseguencer message,"{0}" , due to internal Error..**

**Reason :** {1}

**Cause:** Error persiting reseguencer message,"{0}" , due to internal Error.. Reason : {1}

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-04101: Error receiving DB message.**

**Cause:** Error receiving DB message.

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-04102: Error publishing DB message.**

**Cause:** Error publishing DB message.

**Action:** Check log file for any exceptions and contact Oracle Support Services for further help.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**ORAMED-09001: Parameter name contains "{0}" qname "{1}".**

**Cause:** Parameter name contains "{0}" qname "{1}".

**Action:** Verify Name-Value parameters to be of the form 'name1=value1 name2=value2' with value not having any spaces.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

## OSSOIAP-90001 to OSSOIAP-90005

**OSSOIAP-90001: The Identity Asserter received an unknown token type "{0}".**

**Expected:** "{1}"

**Cause:** Incorrect token type.

**Action:** Contact your Oracle single sign-on administrator to ensure that Proxy-Remote-User is the active token type.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OSSOIAP-90002: The Identity Asserter received an unknown token class "{0}".**

**Expected:** a byte array

**Cause:** Incorrect token class.

**Action:** Contact your Oracle single sign-on administrator with exception/error information.

**Level:** 1

**Type:** ERROR

**Impact:** Internal Error

**OSSOIAP-90003: The Identity Asserter received an empty token byte array.**

**Cause:** Incorrect token conversion.

**Action:** Contact your Oracle single sign-on administrator with exception/error information.

**Level:** 1

**Type:** ERROR

**Impact:** Internal Error

**OSSOIAP-90004: The Identity Asserter received an empty username.**

**Cause:** System Error.

**Action:** Contact your Oracle single sign-on administrator with exception/error information.

**Level:** 1

**Type:** ERROR

**Impact:** Internal Error

---

**OSSOIAP-90005: The Identity Asserter received an unrecognized callback.**

**Cause:** The Identity Asserter received an unsupported callback.

**Action:** Contact your Oracle single sign-on administrator with exception/error information.

**Level:** 1

**Type:** ERROR

**Impact:** Internal Error

---

## OVD-01000 to OVD-80015

**OVD-01000: Failure in loading configuration from Oracle Virtual Directory server.**

**Cause:** The Oracle Virtual Directory server might be down.

**Action:** Possible network issue or server down.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01001: Failure in saving configuration to Oracle Virtual Directory server.**

**Cause:** The Oracle Virtual Directory server might be down.

**Action:** Possible network issue or server down.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01002: Failure in registering children Proxy MBean.**

**Cause:** Check the error message for the cause.

**Action:** Make sure AdminServer is running properly.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01003: Failure in opening file: {0}**

**Cause:** File does not exist.

**Action:** Check if the file exists. If not, check AdminServer log for possible causes

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01004: Failure in retrieving credential from file-based CSF.**

**Cause:** Possible corrupt CSF wallet file.

**Action:** Sync the CSF wallet file from Oracle Virtual Directory component to AdminServer.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**OVD-01005: Failure in retrieving credential from JPS.**

**Cause:** Possible corrupt CSF service.

**Action:** Make sure CSF service is ok.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01006: Failure in setting credential into WebLogic Server CSF.**

**Cause:** Possible corrupt CSF service.

**Action:** Make sure CSF service is ok.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01007: Failure in loading the Oracle Virtual Directory credential from wallet file into WebLogic Server CSF.**

**Cause:** Possible corrupt CSF service.

**Action:** Make sure CSF service is ok.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01008: The IP Address: {0} is invalid.**

**Cause:** Invalid IP Address value or format.

**Action:** Provide a valid IP Address.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01009: Failure in saving listener config XML.**

**Cause:** The Oracle Virtual Directory server might be down.

**Action:** Possible network issue or server down.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01010: Failure in registering children listener proxy MBean.**

**Cause:** Check the error message for the cause.

**Action:** Make sure AdminServer is running properly.

**Level:** 1

**Type:** ERROR



---

**Impact:** Configuration

**OVD-01011: Failure in deregistering children listener proxy MBean.**

**Cause:** Check the error message for the cause.

**Action:** Make sure AdminServer is running properly.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01012: Failure in getting listener configuration name.**

**Cause:** Check the error message for the cause.

**Action:** Make sure AdminServer is running properly.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01013: Invalid parameters to create a new listener configuration.**

**Cause:** The key count and value count does not match.

**Action:** Input matched key/value pairs.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01014: Missing parameters to create a new listener configuration.**

**Cause:** Parameter id is missing for the listener to be created.

**Action:** Specify a unique listener id.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01015: Invalid id value.**

**Cause:** Check the error message for the cause.

**Action:** Provide valid id value.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01016: Failure in building the listener MBean ObjectName.**

**Cause:** Check the error message for the cause.

**Action:** Input proper parameters for MBean ObjectName to be constructed.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01017: Invalid id value.**

---

**Cause:** Specified id is already used by existing listener.

**Action:** Specify a unique listener id.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01018: Missing parameters to create a new listener configuration.**

**Cause:** Port number is missing for the new listener.

**Action:** Specify a free port.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01019: Not allowed to create an admin port.**

**Cause:** You are trying to create new admin port.

**Action:** No action.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01020: Failure in creating the new listener.**

**Cause:** Check the error message for the cause.

**Action:** Fix the mistakes according to the error message.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01021: Not allowed to delete or disable the admin port or "LDAP SSL Endpoint".**

**Cause:** You are trying to delete or disable the admin port or "LDAP SSL Endpoint".

**Action:** No action.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01022: Failure in setting port in listener config.**

**Cause:** Check the error message for the cause.

**Action:** Fix the issue reported in the error message.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01023: Invalid host name: {0}.**

---

**Cause:** Invalid host name.  
**Action:** Input a valid host name or IP Address.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01024: Invalid port number: {0}.**

**Cause:** Invalid port number.

**Action:** Input a valid port number.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01025: Port number {0} is already in use.**

**Cause:** The port number is used by other ports.

**Action:** Input a free port.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01026: The value {0} contains one or more invalid special characters as in list: "{1}".**

**Cause:** The input value contains invalid characters.

**Action:** Input a new value without any special characters.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01027: Invalid logger name: {0}.**

**Cause:** The logger name is already in use.

**Action:** Specify a unique logger name.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01028: Invalid logger name: {0}.**

**Cause:** The logger is not defined.

**Action:** Specify an existing logger.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01029: Handler {0} is being used by Logger {1}.**

**Cause:** The Handler is used.

---

**Action:** Do not remove a handler that is in use.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01030: Unknown listener type.**

**Cause:** The listener type is unknown.

**Action:** Using LDAP or HTTP as the listener type.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01031: Invalid handler name {0}.**

**Cause:** The handler is not defined.

**Action:** Use an existing handler.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01032: Invalid handler name {0}.**

**Cause:** The handler name is already in use.

**Action:** Specify a unique handler name.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01033: Logger {0} not defined.**

**Cause:** Encountered an unexisting logger.

**Action:** Reload the configuration then retry.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01034: Missing property name.**

**Cause:** The property name is not defined.

**Action:** Input a property name.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-01035: Missing input handler object.**

**Cause:** Handler object to be validated is missing.

**Action:** Input the handler object to be validated.

---

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**OVD-01036: Missing handler name.**

**Cause:** Handler name is missing from the handler object.

**Action:** A handler object must have a unique handler name.

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**OVD-01037: Missing handler classname.**

**Cause:** Handler classname is missing from the handler object.

**Action:** A classname must be specified for a handler object.

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**OVD-01038: Missing input logger object.**

**Cause:** Logger object to be validated is missing.

**Action:** Input the logger object to be validated.

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**OVD-01039: Missing logger name.**

**Cause:** Logger name is missing from the logger object.

**Action:** A logger object must have a unique logger name.

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**OVD-01040: Missing logger name.**

**Cause:** Did not input a logger name.

**Action:** Input a logger name.

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**OVD-01041: Missing handler name.**

**Cause:** Did not input a handler name.

**Action:** Input a handler name.

**Level: 1**

**Type: ERROR**

- 
- Impact:** Configuration
- OVD-01042: Invalid level: {0}.**  
**Cause:** The level value is invalid.  
**Action:** Provide a valid logging level.
- Level:** 1  
**Type:** ERROR  
**Impact:** Configuration
- OVD-01043: Logger {0} already has handler {1}.**  
**Cause:** The handler is already used in the logger.  
**Action:** Do not add the same handler to a logger more than once.
- Level:** 1  
**Type:** ERROR  
**Impact:** Configuration
- OVD-01044: Logger {0} does not have handler {1}.**  
**Cause:** The handler is not used by the logger.  
**Action:** Do not remove a handler from a logger which does not use it.
- Level:** 1  
**Type:** ERROR  
**Impact:** Configuration
- OVD-01045: Invalid handler attribute name: {0}.**  
**Cause:** The attribute name is invalid.  
**Action:** Specify a valid attribute name.
- Level:** 1  
**Type:** ERROR  
**Impact:** Configuration
- OVD-01046: Not allowed to change SSL authentication type for "LDAP SSL Endpoint" port.**  
**Cause:** You are trying to change SSL authentication type for "LDAP SSL Endpoint" port.  
**Action:** No action.
- Level:** 1  
**Type:** ERROR  
**Impact:** Configuration
- OVD-01047: Not allowed to disable SSL for "LDAP SSL Endpoint" port.**  
**Cause:** You are trying to disable SSL for "LDAP SSL Endpoint" port.  
**Action:** No action.
- Level:** 1  
**Type:** ERROR

---

**Impact:** Configuration

**OVD-01048: Failed to add schema location: {0}**

**Cause:** MBean might be out-of-sync with server configuration file.

**Action:** Reload the MBean Configuration and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60002: Unable to close the file: {0}.**

**Cause:** Unable to close the file.

**Action:** Verify that the file exists.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60003: Error occurred in communicating with client: {0}.**

**Cause:** Client side of channel was closed for writing.

**Action:** Restart the client.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60004: Critical error: Printing stack trace.**

**Cause:** Critical error occurred when processing client request.

**Action:** Ensure that the request from client is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60005: Invalid DN specified in Access Control List.**

**Cause:** The DN specified in the Access Control List was incorrect.

**Action:** Specify a valid DN in valid DN format. Eg: cn=Jim Smith, ou=People, o=Division B, c=UK

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60006: Error in parsing backend types file.**

**Cause:** Error parsing the configuration file.

**Action:** Verify if the configuration file conforms to the schema.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**OVD-60007: Error in parsing backend properties.**

**Cause:** Improper properties file was used.

**Action:** No action.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60008: Error in instantiating {0}.**

**Cause:** Could not start the object mentioned in the log file.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60009: Error in starting {0} : {1}.**

**Cause:** Could not start the object mentioned in the log file.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60010: Cannot modify root DSE.**

**Cause:** Modification of root DSE operation failed.

**Action:** Verify if the server allows modification of root DSE.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60011: bad value**

**Cause:** The specified value was not appropriate.

**Action:** No action.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60012: Replace not supported on object.**

**Cause:** Replace operation was not supported on the object.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60013: Failure in writing schema file: {0}.**

**Cause:** Could not write to schema configuration files.



---

**Action:** Verify if the file system is writeable.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60014: Unable to modify.**

**Cause:** Could not perform modification on the object.

**Action:** Check if the backend server allows modification.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60015: Error in opening mapping file: {0}.**

**Cause:** Invalid file or no permissions or incorrect file location or file did not exist.

**Action:** Ensure a valid mapping file exists with correct permissions and in the correct location.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60016: IO error while reading the mapping file.**

**Cause:** The Oracle Virtual Directory Server was unable to read mapping file.

**Action:** Ensure that the file system is available where mapping files are deployed.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60017: Invalid DN created by mapping rules: {0}.**

**Cause:** The mapping rule was incorrectly specified.

**Action:** The DN composed from the mapping rules is incorrect.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60018: {0} Invalid DN as suffix: {1}.**

**Cause:** Invalid DN.

**Action:** Provide a valid DN.Eg:cn=Jim Smith,ou=People,o=Division B,c=UK

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60019: {0} Invalid DN as base: {1}.**

**Cause:** Invalid DN.

**Action:** Provide a valid DN.Eg:cn=Jim Smith,ou=People,o=Division B,c=UK

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60020: {0} Unable to open database mapping file {1}.**

**Cause:** Invalid file or no permissions or incorrect file location or file did not exist.

**Action:** Ensure a valid mapping file exists with correct permissions and in the correct location.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60021: IO error while reading the Database Adapter Mapping file.**

**Cause:** Oracle Virtual Directory Server was unable to read mapping files.

**Action:** Check Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60022: Invalid DN {0} is used as adapter root value.**

**Cause:** Invalid DN.

**Action:** Provide a valid DN.Eg:cn=Jim Smith,ou=People,o=Division B,c=UK

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60023: Remote hosts are unavailable: {0}.**

**Cause:** Could not establish a connection to the remote LDAP server.

**Action:** Ensure that the LDAP server is available.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-60024: Connection error: {0}.**

**Cause:** Could not establish a connection due to incorrect connection details or LDAP server was unavailable.

**Action:** Ensure LDAP server is available and connection details are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-60025: Unable to modify.**

**Cause:** LDAP operations error.

**Action:** Check Oracle Virtual Directory server logs for more details.

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60026: Attempted to uses name: {0}.**

**Cause:** Invalid DN.

**Action:** Ensure that the DN is valid.Eg:cn=Jim Smith,ou=People,o=Division B,c=UK

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60027: IO problem while initializing the datafile: {0}.**

**Cause:** Error happened while accessing Local Store Adapter data files.

**Action:** Contact Oracle Virtual Directory administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Operating System

**OVD-60028: Problem while initializing the datafile: {0}.**

**Cause:** Error happened while accessing Local Store Adapter data files.

**Action:** Contact Oracle Virtual Directory administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Operating System

**OVD-60029: Unable to modify data file.**

**Cause:** IO exception happened while trying to free map file.

**Action:** Contact Oracle Virtual Directory administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Operating System

**OVD-60030: Error while updating free space file.**

**Cause:** IO exception happened while trying to free map file.

**Action:** Contact Oracle Virtual Directory administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Operating System

**OVD-60031: Error: {0}.**

**Cause:** Exception happened while trying to free map file.

**Action:** Contact Oracle Virtual Directory administrator.

**Level:** 1

---

**Type:** ERROR  
**Impact:** Operating System  
**OVD-60032: IO Error writing EID#{0} to datafile: {1}.**  
**Cause:** Writing data to data file failed.  
**Action:** Contact Oracle Virtual Directory administrator.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Operating System  
**OVD-60033: Error writing EID#{0} to datafile: {1}.**  
**Cause:** Writing data to data file failed.  
**Action:** Contact Oracle Virtual Directory administrator.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Data  
**OVD-60034: Error deleting EID#{0} to datafile: {1}.**  
**Cause:** Removing data from data file failed.  
**Action:** Contact Oracle Virtual Directory administrator.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Data  
**OVD-60035: Error reading entry #{0} : {1}.**  
**Cause:** Reading data from data file failed.  
**Action:** Contact Oracle Virtual Directory administrator.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Data  
**OVD-60036: Error parsing entry #{0} : {1}.**  
**Cause:** Reading data from data file failed.  
**Action:** Contact Oracle Virtual Directory administrator.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Data  
**OVD-60037: Error modifying EID#{0} in datafile: {1}.**  
**Cause:** Writing data from data file failed.  
**Action:** Contact Oracle Virtual Directory administrator.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Data

---

**OVD-60038: Error renaming EID#{0} in datafile: {1}.**

**Cause:** Writing data from data file failed.

**Action:** Contact Oracle Virtual Directory administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60039: Unable to expire random access file: {0}.**

**Cause:** Tried to expire the random access file and IO exception encountered.

**Action:** Contact Oracle Virtual Directory administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60040: Unable to open files.**

**Cause:** Failed to open the files.

**Action:** Contact Oracle Virtual Directory administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60041: Error writing {0} ADD to transaction log: {1}.**

**Cause:** Tried to write transaction log and it failed.

**Action:** Contact Oracle Virtual Directory administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60042: Error writing entry#{0} DELETE to transaction log: {1}.**

**Cause:** Tried to write transaction log and it failed.

**Action:** Contact Oracle Virtual Directory administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60043: Error writing {0} MODIFY to transaction log: {1}.**

**Cause:** Tried to write transaction log and it failed.

**Action:** Contact Oracle Virtual Directory administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60044: Error writing {0} RENAME to transaction log: {1}.**

**Cause:** Tried to write transaction log and it failed.

---

**Action:** Contact Oracle Virtual Directory administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60045: Error opening the Transaction Log: {0}.**

**Cause:** Tried to open transaction log and it failed.

**Action:** Contact Oracle Virtual Directory administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60046: Error truncating transaction log.**

**Cause:** The access log file could not be truncated.

**Action:** Manually truncate the access log files.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60047: Corrupt Transaction at {0}.**

**Cause:** Local Store Adapter transaction corrupted.

**Action:** Contact OVD administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60048: {0} Unable to open file: {1}.**

**Cause:** File not found.

**Action:** Ensure that the file exists.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60049: {0} Invalid DN suffix: {1}.**

**Cause:** The suffix used for DN was incorrect.

**Action:** Use correct suffix for rules for constructing a DN.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60050: {0} Invalid DN: {1}={2},{3}.**

**Cause:** The DN composed as shown was not correct.

**Action:** Make changes to the rules for constructing the DN to ensure valid DN syntax.

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60051: Modification is not supported on this {0}.**

**Cause:** Modification of this object is not supported.

**Action:** No action.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60052: Unable to listen on Port {0}:{1}.**

**Cause:** Port may be occupied.

**Action:** Ensure that the port is free.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-60053: Error accepting connection from server socket: {0}.**

**Cause:** Error while accepting connection from client.

**Action:** Retry starting the listener.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-60054: Critical error on server socket: {0}.**

**Cause:** OS error was encountered.

**Action:** Check network settings.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-60055: Out of memory error: Printing stack trace.**

**Cause:** Out of memory.

**Action:** Contact the Oracle Virtual Directory administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-60056: Cannot stop server socket.**

**Cause:** Error occurred while closing server socket.

**Action:** Retry stopping the listener.

**Level:** 1

**Type:** ERROR

---

**Impact:** Network

**OVD-60057: Error setting socket on new connection: {0}.**  
**Cause:** Error occurred while setting socket on the new client connection.  
**Action:** Retry starting the listener.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Network

**OVD-60058: Critical error: Printing stack trace. {0}.**  
**Cause:** Critical error while processing the client connection.  
**Action:** Check Oracle Virtual Directory log file for more details.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Network

**OVD-60059: Error instantiating listener of type {0}:{1}.**  
**Cause:** Error while starting the listener.  
**Action:** Check Oracle Virtual Directory log files for more details.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Network

**OVD-60060: An error occurred.**  
**Cause:** An error occurred while processing the request.  
**Action:** Correct the error and re-submit the request.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses

**OVD-60061: Directory Error#{0}: {1}.**  
**Cause:** An error occurred while processing the request.  
**Action:** Correct the error and re-submit the request.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses

**OVD-60062: Error transforming DSML using: {0}.**  
**Cause:** Transforming DSML request failed.  
**Action:** Turn on debug to get more error information.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses

**OVD-60063: Error in XSLT frontend: {0}.**



---

**Cause:** Failed when processing incoming requests to get query information.

**Action:** Turn on debug to get more error information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60064: Missing MD5 capability.**

**Cause:** Error with MD5 hashing compatability.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**OVD-60065: Error getting entry {0}:{1}.**

**Cause:** Could not retrieve the specified entry.

**Action:** Verify that the specified entry exists in the directory.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60066: Error truncating change log: {1}.**

**Cause:** No action required. Deprecated.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60067: Error opening changelog database: {1}.**

**Cause:** Deprecated.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60068: Error closing changelog database: {1}.**

**Cause:** Deprecated.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60069: Error reading changelog entry#: {1}.**

**Cause:** Deprecated.

**Action:** No action required.

---

**Level: 1**  
**Type: ERROR**  
**Impact: Data**  
**OVD-60070: Error parsing replication properties.**  
**Cause:** Deprecated.  
**Action:** No action required.

**Level: 1**  
**Type: ERROR**  
**Impact: Data**  
**OVD-60071: Unable to locate agreement..**  
**Cause:** Deprecated.  
**Action:** No action required.

**Level: 1**  
**Type: ERROR**  
**Impact: Data**  
**OVD-60072: Cannot update replica status file for.**  
**Cause:** Deprecated.  
**Action:** No action required.

**Level: 1**  
**Type: ERROR**  
**Impact: Data**  
**OVD-60073: File not found: {0}.**  
**Cause:** Could not find the file specified in the log message.  
**Action:** Check that the file is present on the file system.

**Level: 1**  
**Type: ERROR**  
**Impact: Data**  
**OVD-60074: IO error: {0}.**  
**Cause:** Encountered error in writing files to the disk.  
**Action:** Check that the file system is working properly.

**Level: 1**  
**Type: ERROR**  
**Impact: Data**  
**OVD-60075: Error closing files: {0}.**  
**Cause:** Error encountered in closing file mentioned in the log message.  
**Action:** Ensure that the file system is working properly.

**Level: 1**  
**Type: ERROR**

---

**Impact:** Data

**OVD-60076: Error writing to changelog file: {0}.**  
**Cause:** Deprecated.  
**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60077: Cannot update replica status file for {0}.**  
**Cause:** Deprecated.  
**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60078: Error Connecting to Consumer: {0} port {1}.**  
**Cause:** Deprecated.  
**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60079: Agreement {0}: Skipping Change#{1} - Already Exists on Consumer.**  
**Cause:** Deprecated.  
**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60080: Agreement {0}: Error Transmitting Change#{1} - {2}.**  
**Cause:** Deprecated.  
**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60081: Agreement {0}: Skipping Change#{1} - Doesn't Exist on Consumer.**  
**Cause:** Deprecated.  
**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60082: Agreement {0}: Invalid Changetype:{1} in change#{2}.**

---

**Cause:** Deprecated.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60083: Failure in parsing schema: {0}.**

**Cause:** LDAP schema specified in the xml file was incorrect.

**Action:** Make sure the schema conforms to the standard.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60084: Missing object class.**

**Cause:** Object class definition not found.

**Action:** Ensure that LDAP schema has the definition for object class.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60085: Missing attributes: {0}, Not allowed attributes: {1}.**

**Cause:** The attributes specified are missing in the LDAP schema.

**Action:** Ensure LDAP schema has definition for the attributes.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60086: Error parsing XML file.**

**Cause:** Error encountered when parsing the configuration xml files.

**Action:** Ensure that XML files are consistent with the xsd.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60087: Error instantiating XML Handler.**

**Cause:** Could not satisfy the requested configuration.

**Action:** Verify that the currently configured XML parameters are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60088: Error writing XML file.**

**Cause:** Could not write the XML file to disk.

**Action:** Verify the file has write permissions.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60089: Usage: java InitReplica AgreementName filename.**

**Cause:** Deprecated.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60090: Unable to locate agreement: {0}.**

**Cause:** Deprecated.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60091: Cannot update replica status file for {0}.**

**Cause:** Deprecated.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60092: Not an LDAP URL.**

**Cause:** URL specified was not a valid LDAP URL.

**Action:** Ensure LDAP URL follows the standard format as defined in LDAP v3 Protocol.Format Eg: ldap://host:port/DN?attributes?scope?filter?

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60093: Invalid LDAP URL.**

**Cause:** URL specified was not a valid LDAP URL.

**Action:** Ensure LDAP URL follows the standard format as defined in LDAP v3 Protocol.Format Eg: ldap://host:port/DN?attributes?scope?filter?

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60094: Bad LDAP filter.**

**Cause:** Incorrect LDAP filter specified.

**Action:** Specifiy LDAP filter per the LDAP V3 protocol specification.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-60095: Failure in LDAP search: {0}.**

**Cause:** LDAP search failed with the error.

**Action:** Check the LDAP error code and resolve the error appropriately.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60096: Error opening {0} for writing: {1}.**

**Cause:** OS error encountered when opening IO for writing.

**Action:** Check OS error and correct the issue.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60097: Failure in exporting LDAP entries to LDIF format: {0}.**

**Cause:** Failed to export LDAP entries in LDIF format.

**Action:** Verify the input parameters provided for LDIF export is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60098: Error adding entry: {0}.**

**Cause:** Error encountered while adding entry specified in the log file.

**Action:** Check the LDAP error code and resolve the error accordingly.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60099: Schema violation adding {0}: {1}.**

**Cause:** LDAP schema error encountered when adding an entry.

**Action:** Ensure that the entry being added conforms to the LDAP schema.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60100: Error reading input: {0}.**

**Cause:** OS error encountered when reading input.

**Action:** Check the OS error logged and correct the issue.

**Level:** 1

**Type:** ERROR

---

**Impact:** Data

**OVD-60101: Bad LDAP Filter.**

**Cause:** Incorrect LDAP filter specified.

**Action:** Specify LDAP filter per the LDAP V3 protocol specification.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-60102: Invalid Adapter Suffix: {0}.**

**Cause:** The suffix used for adapter did not exist.

**Action:** Specify the right suffix for the adapter.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60104: Failure (null pointer) in instantiating adapter: {0}.**

**Cause:** Error encountered in creating adapter.

**Action:** Ensure that the adapter configuration is proper.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60105: Join view adapter is disabled because primary adapter {0} is not defined**

**Cause:** Primary adapter not defined.

**Action:** Define a primary adapter.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60106: {0} Unable to instantiate join#{1} of type {2}({3}) on adapter#{4}.**

**Cause:** Unable to instantiate join.

**Action:** Check Oracle Virtual Directory log file for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60107: Modification is invalid on {0}.**

**Cause:** Trying to modify an invalid entry.

**Action:** Check the target entry and see if it is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**OVD-60108: Name not found {0}.**

**Cause:** Entry not found.

**Action:** Check whether entry exists.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60109: Missing target adapter for shadow join .**

**Cause:** No target adapter was defined for shadow join.

**Action:** Define a target adapter.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60110: Attempt to join to undefined/unavailable target adapter #{0}.**

**Cause:** Target adapter was undefined/unavailable for join.

**Action:** Define a target adapter.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60111: ERROR: rule has missing backend(adapter#{0}).**

**Cause:** Backend adapter specified in the join rule was undefined/unavailable.

**Action:** Define a valid backend adapter.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60112: Shadow Joiner exception querying joined entries.**

**Cause:** Exception while retrieving joined entries.

**Action:** Check Oracle Virtual Directory log file for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60113: Shadow Joiner exception processing join results.**

**Cause:** Exception while processing join results.

**Action:** Check Oracle Virtual Directory log file for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60114: Missing join rule relationship.**

**Cause:** Join rule relationship was missing.



---

**Action:** Add a valid join rule relationship.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60115: Missing target adapter for simple join.**

**Cause:** Target adapter for simple join missing.

**Action:** Add a target adapter for simple join.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60116: Attempt to join to undefined/unavailable target adapter #{0}.**

**Cause:** An attempt was made to join to a undefined/unavailable target adapter.

**Action:** Provide an available target adapter to join.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60117: Error no join relationships defined.**

**Cause:** No join relationship defined.

**Action:** Define a join relationship.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60118: Transaction file failed to initialize.**

**Cause:** Tried to start transaction processor and it failed.

**Action:** Contact Oracle Virtual Directory administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60119: Error, missing suffix name for local store adapter {0}.**

**Cause:** Incorrect Local Store Adapter configuration.

**Action:** Check Local Store Adapter configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60120: Error initializing mapping:.**

**Cause:** Error while initializing mapping in the DB Adapter.

**Action:** Check the Oracle Virtual Directory server logs for more details.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60121: {0} Invalid DN: {1}.**

**Cause:** The DN specified was not a valid DN.

**Action:** Provide a valid DN.Eg:cn=Jim Smith,ou=People,o=Division B,c=UK

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60122: Error creating TLS tunnel: {0}.**

**Cause:** Error encountered when connecting to backend server over TLS.

**Action:** Check error code and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60123: Invalid format.**

**Cause:** Invalid string representation of attribute type or object class.

**Action:** Specify a valid RFC2252-style string for attribute type and object class.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60124: haveattr requires attribute type as argument.**

**Cause:** Attribute type was not specified for the operation.

**Action:** Specify a valid attribute type.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60125: haveattrval requires an argument specifying attribute=value.**

**Cause:** Missing or invalid argument for the operation.

**Action:** Specify the argument in correct format.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60126: Matchdn requires a distinguished name argument.**

**Cause:** Distinguished name was not specified for the operation.

**Action:** Specify a valid distinguished name.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**OVD-60127: rename requires newattr=oldattr as argument.**

**Cause:** Missing or invalid argument for the operation.

**Action:** Specify the argument in correct format.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60128: copy requires newattr=oldattr as argument.**

**Cause:** Missing or invalid argument for the operation.

**Action:** Specify the argument in correct format.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60129: cappend requires newattr=oldattr as argument.**

**Cause:** Missing or invalid argument for the operation.

**Action:** Specify the argument in correct format.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60130: rappend requires newattr=oldattr as argument.**

**Cause:** Missing or invalid argument for the operation.

**Action:** Specify the argument in correct format.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60131: addvalue requires attribute=value as argument.**

**Cause:** Missing or invalid argument for the operation.

**Action:** Specify the argument in correct format.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60132: deletevalue requires attribute=value as argument.**

**Cause:** Missing or invalid argument for the operation.

**Action:** Specify the argument in correct format.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60133: replacevalue requires attribute=value as argument.**

- 
- Cause:** Missing or invalid argument for the operation.  
**Action:** Specify the argument in correct format.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses
- OVD-60134: Setdn requires distinguished name as an argument.**  
**Cause:** Distinguished name was not specified for the operation.  
**Action:** Specify a valid distinguished name.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses
- OVD-60135: splitvals requires attribute=delimiter as argument.**  
**Cause:** Wrong number of arguments specified for the operation.  
**Action:** Specify the argument in correct format.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses
- OVD-60136: Unknown operation specified in mapping file: {0}.**  
**Cause:** Invalid operation specified in mapping file.  
**Action:** Specify a valid operation.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses
- OVD-60137: No DN Specified at line: {0}.**  
**Cause:** Distinguished name missing at the specified line in mapping file.  
**Action:** Specify a valid distinguished name.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses
- OVD-60138: Error at line#{0}: {1}.**  
**Cause:** Failed to compile the mapping file.  
**Action:** Verify the mapping file is correct.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Data
- OVD-60139: Joiner: Missing backend handle for adapter#{0}.**  
**Cause:** No backend found for join.  
**Action:** Define a backend for join.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60140: Usage: ImportLDIF filename.ldif.**

**Cause:** Usage string.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60141: {0} Bad Suffix: {1}.**

**Cause:** Invalid DN.

**Action:** Provide a valid DN.Eg:cn=Jim Smith,ou=People,o=Division B,c=UK

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60142: Usage: ExportLDIF suffix filename.ldif.**

**Cause:** Usage String.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60143: {0} Unable to create connection to {1} as {2}.**

**Cause:** Incorrect connection details.

**Action:** Check the connection details.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-60144: {0} Error opening database file:{1}.**

**Cause:** Data file for the Local Store Adapter might be corrupted.

**Action:** Contact Oracle Virtual Directory administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60145: {0} Error initializing transaction processor:{1}.**

**Cause:** Error happened when trying to start a transaction.

**Action:** Contact Oracle Virtual Directory administrator.

**Level:** 1

**Type:** ERROR

- 
- Impact:** Process
- OVD-60146: Error searching for {0}: {1}.**  
**Cause:** Could not find the specified group.  
**Action:** Ensure that the group is available in datastore.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses
- OVD-60148: GetBindDN: Missing backend handle.**  
**Cause:** No backend found for join.  
**Action:** Define a backend for join.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration
- OVD-60149: IO Error Starting Listener: {0}.**  
**Cause:** Error starting listener.  
**Action:** Check Oracle Virtual Directory log file for more details.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Network
- OVD-60150: Error starting connection acceptor: {0}.**  
**Cause:** Error while accepting client request.  
**Action:** Check Oracle Virtual Directory server logs for more details.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration
- OVD-60151: Bad Basic Encoding Rules tag.**  
**Cause:** Error while processing the LDAP client request.  
**Action:** Valid LDAP client request required.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses
- OVD-60152: Indefinite length encoding not supported.**  
**Cause:** Indefinite length encoding was found in the Basic Encoding Rules.  
**Action:** Valid LDAP client request required.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses
- OVD-60154: Paged result control construction failure {0}.**

---

**Cause:** An error occurred while constructing a paged result control.

**Action:** Check Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-60155: Unexpected schema type NULL for {0}.**

**Cause:** Schema type was unavailable for attribute.

**Action:** Ensure that the schema is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60156: Error retrieving BLOB data.**

**Cause:** Error retrieving attribute value.

**Action:** Check Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60158: Remote server failure: {0}.**

**Cause:** Search failed in the remote LDAP server.

**Action:** Check Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60159: Unable to create connection to {0};{1} as {2}.**

**Cause:** Could not create a connection to the LDAP server.

**Action:** Ensure connection details are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-60160: Failure in loading database metadata {0}.**

**Cause:** Error while initializing metadata for the DB Adapter.

**Action:** Ensure that the DB Adapter is correctly configured.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60161: Unable to map entry to database.**

**Cause:** No database mapping details found for the given entry.

**Action:** Provide correct mapping details.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60162: Multi-table modify is not supported.**

**Cause:** The mapping spans multiple DB tables.

**Action:** Provide a valid modify request or modify the DB mapping.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60163: Database object class modification prohibited.**

**Cause:** Object class modification not supported for database adapter.

**Action:** Provide a valid modify request.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60164: No such attribute: {0}.**

**Cause:** Attribute did not exist in the DB mapping.

**Action:** Provide a valid modify request or modify the DB mapping.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60165: Multiple changetypes to the same attribute in a single modify is not allowed by DB adapter.**

**Cause:** DB adapter did not support multiple changetypes for the same attribute.

**Action:** Provide a valid modify request.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60166: Unable to delete rows.**

**Cause:** Internal error.

**Action:** Check the Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60167: Unable to re-insert rows.**

**Cause:** Internal error.

**Action:** Check the Oracle Virtual Directory server logs for more details.

**Level:** 1



---

**Type:** ERROR

**Impact:** Data

**OVD-60168: DB Adapter has restrictions on mixed modify types when multiple values are used.**

**Cause:** DB adapter did not support using multiple values for mixed modify types.

**Action:** Provide a valid modify request.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60169: Unable to replace rows.**

**Cause:** Internal error.

**Action:** Check the Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60170: Unable to insert rows.**

**Cause:** Internal error.

**Action:** Check the Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60171: {0} Change contains unmapped attribute:{1} (dn: {2}).**

**Cause:** Attribute did not exist in the DB mapping.

**Action:** Provide a valid moddn request or modify the DB mapping.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60172: Error getting matches.**

**Cause:** Error while retrieving results matching criteria.

**Action:** Check Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60173: Remote server failure: {0}.**

**Cause:** Remote LDAP server was unavailable or busy.

**Action:** Ensure LDAP server is available.

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**OVD-60174: Remote server unreachable and marked inactive: {0}:{1}.**

**Cause:** Remote LDAP server was unavailable.

**Action:** Ensure LDAP server is available.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-60176: JNDI exception: {0}.**

**Cause:** LDAP operations error.

**Action:** Check the Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60177: Invalid DN exception - unconverted DN: {0}.**

**Cause:** Invalid DN.

**Action:** Ensure that the DN is valid. Eg: cn=Jim Smith,ou=People,o=Division B,c=UK

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60178: Paged search control failure: {0}.**

**Cause:** LDAP search failed with the paged search control.

**Action:** Check the Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60179: Cannot connect for {0} milliseconds.**

**Cause:** Could not connect to server.

**Action:** Ensure server is available.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-60180: Cannot search for {0} milliseconds.**

**Cause:** Could not connect to server to perform search.

**Action:** Ensure server is available.

**Level:** 1

**Type:** ERROR

**Impact:** Network

---

**OVD-60182: Exception: {0}.**

**Cause:** An exception has occurred while processing the request.

**Action:** Check Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60183: Invalid backend requested for search: {0}.**

**Cause:** An attempt to lookup target adapter has failed.

**Action:** Ensure parameters of search request are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60184: LDAP exception: {0}.**

**Cause:** An exception has occurred while processing the request.

**Action:** Check Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60185: Repairing truncated deletion log.**

**Cause:** Delete log was corrupted.

**Action:** Information only and no further action required.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**OVD-60186: Error renaming old files, aborting compaction.**

**Cause:** Renaming old data files failed.

**Action:** Contact Oracle Virtual Directory administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**OVD-60187: Compaction error: {0}.**

**Cause:** IO exception happened while compacting the data file.

**Action:** Contact Oracle Virtual Directory administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**OVD-60188: Upgrade error: {0}.**

**Cause:** IO exception happened while upgrading.

---

**Action:** Contact Oracle Virtual Directory administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**OVD-60189: Missing entry to be joined, received NULL.**

**Cause:** Entry to be joined was missing in the primary adapter.

**Action:** Check if entry is present in the primary adapter.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60191: Shadow Joiner exception processing alternative join results(rename detection processing).**

**Cause:** Exception while processing alternative join results.

**Action:** Check Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60192: Failure in setting request control {0}.**

**Cause:** Internal error.

**Action:** Check Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**OVD-60193: Error no join relationships defined.**

**Cause:** No join relationships defined.

**Action:** Define a join relationship.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60194: Unable to create new value with syntax {0}.**

**Cause:** Could not create an instance of the specified syntax class.

**Action:** Ensure that the specified syntax class can be instantiated.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60196: No search root for user entries defined (srchroot missing).**

**Cause:** Property srchroot missing.

**Action:** Define srchroot for user entries.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60197: No username to entry matching attributes (matchattrs undefined).**

**Cause:** Property matchattrs not defined.

**Action:** Define matchattrs property.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60198: Fatal error connecting to directory handler.**

**Cause:** No backend available.

**Action:** Verify the backends and Oracle Virtual Directory server are running properly.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-60199: Fatal error connecting to DoS tracker.**

**Cause:** DoS connection not available.

**Action:** Verify Oracle Virtual Directory server is running properly.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-60200: LDAP Error Code {0}.**

**Cause:** Performed an operation causing constraint violation error.

**Action:** Check the operation parameters.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60201: Invalid DN {0}.**

**Cause:** The specified DN was invalid.

**Action:** Check the DN syntax and value. Eg: cn=Jim Smith, ou=People, o=Division B, c=UK

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60202: Error processing dynamic group : {0}.**

**Cause:** Error encountered while procesing dynamic group entry.

**Action:** No action required.

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60203: Cannot retrieve SOAP response.**

**Cause:** Failed to retrieve SAX parameters from the SOAP response message.

**Action:** The SOAP server may be busy. Try again later.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60204: Cannot listen on host.**

**Cause:** The admin host was invalid or unreachable.

**Action:** Provide a valid admin host.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-60205: Cannot instantiate Admin service.**

**Cause:** Missing adminService.war or dsmlv2Admin.war file.

**Action:** Ensure that Oracle Home has those files.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60206: Cannot start Admin service.**

**Cause:** Failed to start Admin server.

**Action:** Check the configuration for admin service and start the server again.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60207: Cannot authenticate.**

**Cause:** Invalid user name or password.

**Action:** Provide a valid authentication credential.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60208: Cannot instantiate the local JDBC driver.**

**Cause:** Failed to load DB drivers.

**Action:** Reinstall the correct JDBC drivers on the server and retry.

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**OVD-60209: Driver {0} not found. Use Manage Server Libraries command to install the correct JDBC drivers on the server.**

**Cause:** DB service driver was invalid.

**Action:** Reinstall the JDBC driver.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**OVD-60210: Cannot load tables.**

**Cause:** Failed to load the DB schema.

**Action:** Verify the validity of the DB Schema and its access authorization.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60211: Cannot load table columns.**

**Cause:** Access the schema table column was restricted or it might be invalid.

**Action:** Check the validity of the table column and its accessibility.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60212: Cannot load primary keys.**

**Cause:** The primary key to DB Schema was invalid or inaccessible.

**Action:** Verify the primary key setup and the server array .

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60213: Cannot load results.**

**Cause:** The result may be too big or inaccessible .

**Action:** Check query size or the DB access credential.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60214: Cannot set Access Control Lists enabled.**

**Cause:** Access Control List format could be invalid or not setup properly.

**Action:** Check the Access Control List configuration and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**OVD-60215: Error stopping server.**

**Cause:** The server could be in an invalid state or down.

**Action:** Check the server processes and clean up manually.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-60216: Cannot start Oracle Virtual Directory server: {0}.**

**Cause:** The configuration could be invalid or system resources were missing.

**Action:** Verify all the server configuration and the system resources.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-60217: Cannot reload server.**

**Cause:** The server may be in an invalid state.

**Action:** Try shutdown and start up server again.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-60218: An attempt to restart Oracle Virtual Directory server failed.**

**Cause:** An internal error has occurred.

**Action:** Check the server log for errors.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-60219: Cannot start listener {0}.**

**Cause:** Listener configuration could be invalid.

**Action:** Verify and fix listener configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Ports

**OVD-60220: Cannot stop listener {0}.**

**Cause:** The listener could be down or in an invalid state.

**Action:** Manually verify the listener and cleanup needed.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**OVD-60221: Cannot enable adapter {0}.**

**Cause:** Invalid adapter configuration.



---

**Action:** Setup the adapter configuration correctly and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60222: Cannot disable adapter {0}.**

**Cause:** The adapter may be in a transaction or down.

**Action:** Wait for all transactions to finish and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60223: Cannot retrieve adapter configs.**

**Cause:** Adapter configuration file may be corrupted or invalid format.

**Action:** Verify the adapter configuration file and using the management tool to fix it.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60224: Cannot get adapter config for {0}.**

**Cause:** The configuration for the adapter may be invalid.

**Action:** Fix the adapter configuration and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60225: Cannot get listener configs.**

**Cause:** The listener configurations could be invalid.

**Action:** Verify the validity of the configurations and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60226: Cannot get listener config {0}.**

**Cause:** The configuration for the listener was wrong.

**Action:** Correct the listener configuration and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60227: Cannot provision server.**

**Cause:** The disk space may be full or file system was not writable.

**Action:** Check the configuration path or file system problem.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60228: Cannot provision listeners.**

**Cause:** The disk space may be full or file system was not writable.

**Action:** Check the configuration path or file system problem.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60229: Error Setting Adapter {0}.**

**Cause:** The disk space may be full or file system was not writable.

**Action:** Fix the configuration path or file system problem.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60230: Cannot provision adapters.**

**Cause:** The disk space may be full or file system was not writable.

**Action:** Fix the configuration path or file system problem.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60231: Cannot load adapters.**

**Cause:** The adapters configuration was invalid.

**Action:** Check the validity the configuraton and reload the adapters.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60232: Cannot provision adapter before {0}.**

**Cause:** The named adapter may be invalid.

**Action:** Verify the named adapter and retry the provision again.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60233: Cannot move adapter {0}, up={1}.**

**Cause:** The adapter may be at the top or the potential bug.

**Action:** Check the position of the adapter.

**Level:** 1

**Type:** ERROR

- 
- Impact:** Configuration
- OVD-60234: Cannot remove provisioned listener {0}.**  
**Cause:** The disk may not be writable.  
**Action:** Check the file system and its accessibility.
- Level:** 1  
**Type:** ERROR  
**Impact:** Configuration
- OVD-60235: Cannot rename provisioned listener from {0} to {1}.**  
**Cause:** The old name or the new name may be invalid.  
**Action:** Check the name and try with a different name.
- Level:** 1  
**Type:** ERROR  
**Impact:** Configuration
- OVD-60236: Cannot load listeners.**  
**Cause:** The server may be down or resource was busy.  
**Action:** Make sure the server is up and resource is available.
- Level:** 1  
**Type:** ERROR  
**Impact:** Threads
- OVD-60237: Cannot remove provisioned adapter {0}.**  
**Cause:** The adapter name may be wrong.  
**Action:** Verify the adapter name and try again.
- Level:** 1  
**Type:** ERROR  
**Impact:** Configuration
- OVD-60238: Cannot rename provisioned adapter from {0} to {1}.**  
**Cause:** The configuration versions may be invalid or the name was wrong.  
**Action:** Verify the configuration versions or the adapter names.
- Level:** 1  
**Type:** ERROR  
**Impact:** Configuration
- OVD-60239: Cannot Store.**  
**Cause:** File system may be full or inaccessible.  
**Action:** Check the disk space or file permissions.
- Level:** 1  
**Type:** ERROR  
**Impact:** Files
- OVD-60240: Cannot store schema to {0}.**

---

**Cause:** File system was not accessible.

**Action:** Check the file system accessibility and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**OVD-60241: Cannot provision Access Control Lists.**

**Cause:** The file system may be full or not accessible.

**Action:** Verify the file system and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**OVD-60242: Cannot start Access Control Lists.**

**Cause:** Access Control Lists format may be invalid.

**Action:** Check the validity of the Access Control Lists and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60243: Cannot store file {0}.**

**Cause:** File system may be full of inaccessible.

**Action:** Check the file system and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**OVD-60244: Cannot retrieve file {0}.**

**Cause:** The file system may be corrupted or inaccessible.

**Action:** Check the file system and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**OVD-60245: Cannot find tail of {0}.**

**Cause:** The file may be corrupted.

**Action:** Fix the file formate and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**OVD-60246: Cannot store mapping {0}.**

**Cause:** File system may be full or inaccessible.

**Action:** Check the file system and permission.

---

**Level:** 1

**Type:** ERROR

**Impact:** Files

**OVD-60247: Cannot restart adapter {0}, nice={1}.**

**Cause:** Backend Handler or routing handler was having problem.

**Action:** Make sure the system is not too busy then retry.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60248: Cannot restart listener {0}.**

**Cause:** The listener may be down.

**Action:** Try to start up listener instead.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**OVD-60249: Cannot deploy JAR.**

**Cause:** The jar file may be missing or not readable.

**Action:** Check the validity and access to the jar file.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**OVD-60250: Cannot push to server.**

**Cause:** File system may be full or inaccessible.

**Action:** Check the file system and its file permission.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**OVD-60251: Cannot load plugin "{0}".**

**Cause:** The plugin jar file may be invalid or missing.

**Action:** Verify the jar file path.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**OVD-60252: Cannot load path {0}.**

**Cause:** The file may be missing or corrupted.

**Action:** Please verify the file path.

**Level:** 1

**Type:** ERROR

---

**Impact:** Files

**OVD-60253: Cannot retrieve mapping information.**

**Cause:** The mapping file was missing or corrupted.

**Action:** Check the mapping file.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**OVD-60254: Cannot load joiner "{0}".**

**Cause:** The joiner jar file was missing or corrupted.

**Action:** Check the joiner jar file and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**OVD-60255: Error retrieving status information.**

**Cause:** The server configuration file was missing or corrupted.

**Action:** Check the server.os\_xml.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**OVD-60256: Cannot retrieve hosts.**

**Cause:** The DNS server may be down or not setup properly.

**Action:** Check the DNS server status and its setup.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-60257: Cannot generate key.**

**Cause:** PKI key store path may be wrong or key parameters were invalid.

**Action:** Check the key store path and the validity of the key parameters.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60258: Cannot delete key.**

**Cause:** The key may be protected from deletion or did not exist.

**Action:** Check the key and its file permission.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60259: Cannot import certificate into alias {0}.**

---

**Cause:** The certificate may be invalid or its format was not supported by the server.

**Action:** Verify the certificate using key tool tools such as Oracle Wallet Manager.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60260: Cannot generate certificate request.**

**Cause:** The key store may be missing. Otherwise, the PKI parameters could be invalid or not supported.

**Action:** Check the key store path and its parameters for certificate request generation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60261: Cannot retrieve server certificate.**

**Cause:** The certificate may not exist or the key store was corrupted.

**Action:** Using Oracle Wallet Manager or Sun keytool to verify its content first.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60262: Cannot retrieve keystore entries.**

**Cause:** The keystore may be corrupted or missing.

**Action:** Check the key store path and use keytool to verify its validity.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60263: Cannot reset BackendHandler.**

**Cause:** Failed to shutdown backend handler.

**Action:** No actions required.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60264: Cannot continue to wait ... .**

**Cause:** Adapter sleep thread was interrupted.

**Action:** No actions required.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

---

**OVD-60265: Cannot instantiate the Schema Adapter.**

**Cause:** Failed to initialize schema adapter.

**Action:** Make sure configuration files are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60266: Cannot instantiate the Root Adapter.**

**Cause:** Failed to initialize root adapter.

**Action:** Make sure configuration files are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60267: Cannot Modify Schema.**

**Cause:** Failed to modify schema.

**Action:** Make sure proper values are provided for schema modification.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60268: Error performing modify : {0}.**

**Cause:** Ldap operations error.

**Action:** Check the Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-60269: Cannot instantiate the local driver manager.**

**Cause:** Error while loading driver manager class.

**Action:** Check Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60270: Cannot connect to: {0} - {1}.**

**Cause:** Could not create a connection to database.

**Action:** Ensure JDBC URL and JDBC driver properties are valid. Check Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60271: Unable to locate RDN component: {0}.**



---

**Cause:** Could not locate the RDN in the DB mapping.

**Action:** Ensure that the mapping is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60272: Unable to discover remote LDAP servers via DNS for: {0}.**

**Cause:** No/Incorrect LDAP server information in DNS.

**Action:** Provide correct LDAP server information in DNS.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-60273: No remote host available.**

**Cause:** Could not establish connection to remote host.

**Action:** Check the connection details.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-60274: Cannot return the connection.**

**Cause:** Could not establish a connection to the LDAP server.

**Action:** Ensure LDAP server is available and connection details are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-60275: Unknown error.**

**Cause:** Ldap operations error.

**Action:** Check Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-60276: Error during search.**

**Cause:** Ldap operations error.

**Action:** Check Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-60277: DNS failure: {0}.**

**Cause:** Unable to establish connection with DNS.

**Action:** Ensure DNS server information is correct.

---

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-60278: Cannot close connection.**

**Cause:** Could not close connection to the LDAP server.

**Action:** Check the Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-60279: Not a context holder.**

**Cause:** Internal error.

**Action:** Check the Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-60280: Checkin called.**

**Cause:** Internal error.

**Action:** Check the Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-60281: Cannot retrieve entry.**

**Cause:** Could not retrieve entry from the LDAP results.

**Action:** Check the Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-60282: Unexpected Exception.**

**Cause:** Internal error.

**Action:** Check the Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-60283: Logging Exception when trying to create a LoginContext {0}.**

**Cause:** Internal error.

**Action:** Check the Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**OVD-60284: Logging Exception when trying to call login {0}.**

**Cause:** Incorrect username or password.

**Action:** Ensure username and password are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60285: Logging exception when trying to call logout {0}.**

**Cause:** Error while trying to logout.

**Action:** Check the Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-60286: Zero byte read request.**

**Cause:** Internal error.

**Action:** Check the Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60287: Cannot create SSL socket factory.**

**Cause:** The SSL configuration was not setup correctly or the wallet file was missing.

**Action:** Check the SSL configuration and its wallet file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60288: Cannot retrieve remote server information.**

**Cause:** Could not retrieve remote server information.

**Action:** Provide remote server information.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60289: Error registering new stream: {0}.**

**Cause:** Internal error.

**Action:** Check the Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**OVD-60290: Cannot write to file.**

**Cause:** Write Local Store Adapter data to data file and IO exception occurred.

**Action:** Contact Oracle Virtual Directory administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Operating System

**OVD-60291: Cannot load GlobalServicesInterface.**

**Cause:** Failed to load global plugins.

**Action:** Make sure global plugins are properly configured in server.os\_xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60292: Security exception. Cannot instantiate {0}.**

**Cause:** Security violation, thrown by JVM security manager.

**Action:** Debug the plugin class to find the violation.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**OVD-60293: Cannot instantiate {0}.**

**Cause:** Failed to instantiate the specified class.

**Action:** Make sure the specified class is not an interface nor an abstract class.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**OVD-60294: Invalid permissions on class {0}.**

**Cause:** Failed to access to the definition of the specified class or constructor.

**Action:** Make sure the specified class is accessible.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**OVD-60295: Cannot Find Class {0}.**

**Cause:** The definition of specified class could not be found.

**Action:** Make sure the specified class exists.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**OVD-60296: Cannot instantiate plugin : {0}.**

**Cause:** Failed to instantiate the specified plugin.

---

**Action:** Make sure the plugin class can be instantiated.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**OVD-60297: Failed to parse configuration file : {0}.**

**Cause:** Serious configuration error.

**Action:** Check the configuration file syntax.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60298: Invalid library path. {0}.**

**Cause:** The classpath settings was incorrect.

**Action:** Ensure that the class path settings are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60299: Failed to get entry for DN: {0}.**

**Cause:** The entry did not exist.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-60300: Cannot instantiate wrapper plugin {0}.**

**Cause:** Failed to instantiate the specified plugin.

**Action:** Ensure that the correct class name is provided.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60301: This plugin only works on {0} adapters.**

**Cause:** The plugin was configured to wrong type of adapters.

**Action:** Configure the plugin only on proper adapters.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60302: Invalid DN in addEntry.**

**Cause:** Failed while adding entry to cache because of invalid entry DN.

**Action:** No action required.

---

**Level:** 1  
**Type:** ERROR  
**Impact:** Data  
**OVD-60303: Cache exception: {0}.**  
**Cause:** Cache plugin failed.  
**Action:** No action required.

**Level:** 1  
**Type:** ERROR  
**Impact:** Process  
**OVD-60304: Null entryname.**  
**Cause:** Failed to unregister the query of this entry from entry cache.  
**Action:** No action required.

**Level:** 1  
**Type:** ERROR  
**Impact:** Data  
**OVD-60305: Unable to start "{0}". May not be configured as global plug-in.**  
**Cause:** The base adapter name for the plugin was missing.  
**Action:** Make sure the plugin is deployed as part of an existing adapter.

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration  
**OVD-60306: Invalid criteria due to invalid filter: {0}.**  
**Cause:** The criteria was invalid LDAP filter.  
**Action:** Check criteria syntax and provide a valid filter.

**Level:** 1  
**Type:** ERROR  
**Impact:** Data  
**OVD-60307: ERROR copying filter: {0}.**  
**Cause:** Error while parsing filter.  
**Action:** Provide a valid filter.

**Level:** 1  
**Type:** ERROR  
**Impact:** Data  
**OVD-60308: If the directoryType is configured, an activation attribute is required.**  
**Cause:** Activation attribute was missing.  
**Action:** Provide activation attribute.

**Level:** 1  
**Type:** ERROR

---

**Impact:** Data

**OVD-60309: If activation is configured, activation values are required.**

**Cause:** Activation attribute was missing.

**Action:** Provide values for activation attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60310: If activation is configured, deactivation values are required.**

**Cause:** Deactivation attribute was missing.

**Action:** Provide values for deactivation attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60311: Cannot execute mapping.**

**Cause:** Exception encountered while executing mapping.

**Action:** Ensure that the mapping file is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60312: Cannot instantiate Mapper.**

**Cause:** Failed to instantiate a mapper.

**Action:** Make sure the mapping file existing and correct.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60314: Cannot generate a filter that always passes.**

**Cause:** Failed to generate an all pass filter.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-60315: Cannot adjust filter.**

**Cause:** Failed to reset to an all pass filter.

**Action:** Check the search request syntax.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60316: Invalid DN Exception creating adapter base entry.**

---

**Cause:** Incorrect DN specified when creating a new adapter entry.  
**Action:** Make sure a valid DN is specified in adapter configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60317: The version of this system must be greater than or equal to 3.0.2 to run this plug-in.**

**Cause:** The version of plugin was not supported in this version.

**Action:** Upgrade Oracle Virtual Directory server.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**OVD-60318: Failure in appending the new adapter - type : {0}, name : {1}.**

**Cause:** Failed when creating a new adapter instance.

**Action:** Check syntax of the new adapter.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60319: An attempt to start Oracle Virtual Directory server failed.**

**Cause:** Could not start admin service.

**Action:** Ensure that the configured admin service port is available.

**Level:** 1

**Type:** ERROR

**Impact:** Ports

**OVD-60320: Cannot parse schema {0}.**

**Cause:** Could not parse the specified schema file.

**Action:** Make sure the schema file exists, and syntax of the schemas are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60321: Error parsing product version of server configuration.**

**Cause:** Error encountered while checking schema version in server configuration file.

**Action:** Check schvers in the header of server.os\_xml.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60322: Error parsing adapters. {0}.**



---

**Cause:** Error encountered while parsing adapter configuration.

**Action:** Check syntax of adapters.os\_xml.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60323: Error upgrading {0} configuration file.**

**Cause:** Upgrading schema version of the specified configuration file.

**Action:** Check schvers in the header of the configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**OVD-60324: Cannot load configuration.**

**Cause:** Error encountered while parsing the configuration.

**Action:** Fix the error.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60325: Cannot parse schemas.**

**Cause:** Error encountered while parsing schema files.

**Action:** Fix the error.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60326: Cannot verify checksums.**

**Cause:** Failed to verify checksum while parsing configuration.

**Action:** Make sure configuration files exist and correct.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60327: Exception getting provisioned {0}: {1}.**

**Cause:** Error encountered when parsing the specified configuration file.

**Action:** Correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-60328: Cannot store {0} configuration.**

**Cause:** Not able to write specified configuration file.

**Action:** Make sure the file is writable.

---

**Level:** 1

**Type:** ERROR

**Impact:** Operating System

**OVD-60330: Cannot parse DSML.**

**Cause:** Error parsing DSML request.

**Action:** Make sure the DSML request is properly created.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60331: Failure in LDAP Add.**

**Cause:** Error performing add operation.

**Action:** Ensure that the servers allows the operation to be performed.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-60332: Failure in LDAP Rename.**

**Cause:** Error while performing moddn operation.

**Action:** Ensure that the servers allows the operation to be performed.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-60333: Failure in LDAP Modify.**

**Cause:** Error while performing moddn operation.

**Action:** Ensure that the servers allows the operation to be performed.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-60334: Failure in LDAP Delete.**

**Cause:** Error while performing moddn operation.

**Action:** Ensure that the servers allows the operation to be performed.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-60335: Failure in getting LDAP 1.**

**Cause:** Failed to connect to LDAP server.

**Action:** Ensure LDAP server is available.

**Level:** 1

**Type:** ERROR

---

**Impact:** Network

**OVD-60336: Failure in getting LDAP 2.**

**Cause:** Failed to read the next entry in the result.

**Action:** Ensure that the connection to server is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-60337: Cannot close selector.**

**Cause:** Error while stopping the listener.

**Action:** Retry stopping the listener.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-60338: Cannot stop ReadSelector.**

**Cause:** Error while stopping the listener.

**Action:** Retry stopping the listener.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-60339: Null ReadSelector.**

**Cause:** Error while starting the listener.

**Action:** Retry starting the listener.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-60340: ReadSelector not open.**

**Cause:** Error while starting the listener.

**Action:** Retry starting the listener.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-60341: Key not ready.**

**Cause:** Error while accepting pending client requests.

**Action:** Restart the listener and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-60342: Cannot obtain socket from RDS.**

---

**Cause:** Could not obtain the socket from the Resource Discovery Service.

**Action:** Contact the Oracle Virtual Directory administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Ports

**OVD-60343: Cannot start web listener.**

**Cause:** Could not start the web listener.

**Action:** Check the Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-60344: Error parsing join condition filter: {0}, error: {1}.**

**Cause:** Invalid join condition filter provided.

**Action:** Provide a valid join condition filter.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60345: Cannot Load Joined Entry Set: {1}.**

**Cause:** Could not load the joined entry set.

**Action:** Check Oracle Virtual Directory server logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-60346: Critical error while performing ADD {0}.**

**Cause:** Error occurred when performing add operation.

**Action:** Check the error logged to see the exact LDAP error reported.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-60347: Critical error while performing COMPARE {0}.**

**Cause:** Error occurred when performing compare operation.

**Action:** Check the error logged to see the exact LDAP error reported.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-60348: Critical error while performing SEARCH {0}.**

**Cause:** Error occurred when performing search operation.

**Action:** Check the error logged to see the exact LDAP error reported.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-60350: Cannot instantiate the changelog.**

**Cause:** Not supported operation anymore.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-60351: Error encrypting passwords in the configuration file.**

**Cause:** Could not encrypt the password stored in the configuration file.

**Action:** No action. Try restarting the server.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**OVD-60352: No version 3 schema (".xsd") files located in conf directory. Upgrade aborted.**

**Cause:** Cannot find (".xsd") files.

**Action:** Make sure (".xsd") files exists in conf directory.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**OVD-60353: Error initializing XML: {0}.**

**Cause:** Failed initialize specified configuration file during upgrading.

**Action:** Make sure the XML files are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**OVD-60354: Unable to upgrade version information in server configuration.**

**Cause:** Server could not update the version information in the server configuration.

**Action:** Restart the server to see if the problem goes away.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60355: An attempt to start Oracle Virtual Directory server failed.**

**Cause:** Cannot start Process Control Service client.

**Action:** Ensure Process Control Service agent is running.

---

**Level: 1**  
**Type: ERROR**  
**Impact: Process**

**OVD-60356: Cannot stop the server.**  
**Cause:** Error stopping server.  
**Action:** Use PCS service to stop the server.

**Level: 1**  
**Type: ERROR**  
**Impact: Process**

**OVD-60357: Debug license may not be used in standalone server environment.**  
**Cause:** Not an issue anymore. .  
**Action:** No action required.

**Level: 1**  
**Type: ERROR**  
**Impact: Log**

**OVD-60358: ThreadWorkGroup is destroyed: {0}.**  
**Cause:** The thread group has been destroyed.  
**Action:** No action required.

**Level: 1**  
**Type: ERROR**  
**Impact: Threads**

**OVD-60359: ChainException verifying if user is authenticated.**  
**Cause:** Failed when verifying user authentication.  
**Action:** Make sure Oracle Virtual Directory server is running properly.

**Level: 1**  
**Type: ERROR**  
**Impact: Security**

**OVD-60360: Invalid vde.home setting: {0}.**  
**Cause:** Not able to find vde.home directory.  
**Action:** Make sure vde.home system property is correct.

**Level: 1**  
**Type: ERROR**  
**Impact: Configuration**

**OVD-60361: Modified against a read-only adapter.**  
**Cause:** No read-write backend LDAP server is configured.  
**Action:** Make sure at least one Read/Write host exists in the Remote Hosts list for update operation

**Level: 1**

---

**Type:** ERROR

**Impact:** Configuration

**OVD-60362: Caught LoginException {0}.**

**Cause:** Incorrect login name or password.

**Action:** Provide correct login name and password.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**OVD-60363: Caught NamingException {0}.**

**Cause:** Error while kerberos login.

**Action:** Contact Oracle Virtual Directory administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**OVD-60364: Did not get backend LDAP connection.**

**Cause:** Not able to get connection to LDAP server.

**Action:** Ensure LDAP server is available and the connection details are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-60365: There is no stub implementation for the interface: {0}.**

**Cause:** The Web Service has no port for the given interface.

**Action:** Ensure Web Service is running properly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**OVD-60366: Cannot set endpoint address for unknown port {0}.**

**Cause:** The port name was unknown to the service.

**Action:** Ensure that the Web Service is running properly, and the port name is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Ports

**OVD-60367: Object class {0} not defined in server schema. adapter start aborting.**

**Cause:** The specified object class was not defined.

**Action:** Define object class in server schema.

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**OVD-60368: No backend present for adapter plugins.**

**Cause:** No backend repository available for adapter plugins.

**Action:** Ensure that the backend of concerned adapters are accessible.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-60369: An Oracle Virtual Directory Plugin's class must be specified.**

**Cause:** Plugin class element was missing or empty.

**Action:** Add Plugin class element with proper class name.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**OVD-60370: Cannot load the class {0}.**

**Cause:** The specified plugin class not able to be found.

**Action:** Ensure that the class is in the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**OVD-60371: Cannot instantiate the plugin {0}.**

**Cause:** Failed to instantiate the specified plugin class.

**Action:** Make sure the plugin class exists and has been properly deployed.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**OVD-60372: Illegal access to plugin class.**

**Cause:** The plugin class was not allowed for access.

**Action:** Make sure proper privilege are set to load/run the plugins.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**OVD-60373: Error Parsing at line #{0}: {1}.**

**Cause:** Error occurred while parsing configuration files.

**Action:** Check the configuration file and make correction.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60374: Unknown Element : {0}.**



---

**Cause:** The specified element did not exist.

**Action:** Ensure that the element exists in the schema of the concerned object.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60375: Illegal value : {0} for element: {1}.**

**Cause:** The value did not exist for the specified element.

**Action:** Provide a valid value for the specified element.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60376: Listener {0} does not exist.**

**Cause:** No such Listener.

**Action:** Check the Listener configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60377: No schema supplied.**

**Cause:** No schema supplied.

**Action:** Provide user schema to write.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60378: Invalid JAR File.**

**Cause:** The specified JAR file not recognized by Oracle Virtual Directory.

**Action:** Verify the file name is correct, which should end with zip/jar.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60379: Unknown syntax {0}, valid values are**

**BinarySyntax,DirectoryString,IA5String,IntegerSyntax.**

**Cause:** Syntax specified was incorrect.

**Action:** Make sure the syntax specified is one of the valid syntaxes.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60380: Cannot load syntax.**

**Cause:** Error occurred when mapping the syntax.

---

**Action:** Ensure syntax is one of BinarySyntax,DirectoryString,IA5String,IntegerSyntax.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60381: Alias required.**

**Cause:** Alias for the certificate not specified.

**Action:** Specify the alias for the certificate.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60382: DN required.**

**Cause:** Operation requires a dn value which was not specified.

**Action:** Ensure a valid DN value is specified.Eg:cn=Jim Smith,ou=People,o=Division B,c=UK

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60383: Cannot retrieve certificate.**

**Cause:** Error retrieveing X509 Certificate.

**Action:** Verify if the certificates are provisioned.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**OVD-60384: Requested trust manager not supported.**

**Cause:** The trust manager used was not supported.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**OVD-60385: SSL certificate error.**

**Cause:** The wallet was empty or certificate was not valid.

**Action:** Use wallet manager or keytool to verify the wallet. The SSL configuration must be setup correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**OVD-60386: Cannot load keystore.**

**Cause:** The key store path was wrong or the key store was not readable.

---

**Action:** Use a keytool to verify the key store.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**OVD-60387: No Remote Servers Available.**

**Cause:** No remote LDAP servers available.

**Action:** Ensure LDAP servers are available and connection details are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-60388: Attribute type or value exists: {0}.**

**Cause:** Attribute type or value specified already exists.

**Action:** Ensure that the add of attribute values of attribute is on non-unique values.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60389: No database connection available in cache to process the request.**

**Cause:** All database connections in the cache are active. No new connection can be created as the maximum limit was reached.

**Action:** Modify DB adapter configuration to increase the database connection limit.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**OVD-60390: Cannot parse Admin Group URL: {0}.**

**Cause:** Invalid LDAP URL format for Admin Group.

**Action:** Provide a valid LDAP URL format.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60391: No LDAP connection available to process request for DN: {0}.**

**Cause:** All LDAP connections in the cache are active. No new connection can be created as the maximum limit was reached.

**Action:** Modify LDAP adapter configuration to increase the LDAP connection limit.

**Level:** 1

**Type:** ERROR

**Impact:** Session

---

**OVD-60392: Invalid DN.**

**Cause:** The specified DN has more than 4000 characters.

**Action:** Check the DN value.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60393: Cannot retrieve database schema.**

**Cause:** Database might not be available.

**Action:** Validate the database connection.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60394: Syntax {0} not defined.**

**Cause:** Invalid syntax for the attribute.

**Action:** Correct the syntax for the attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60395: Object ID {0} already in use.**

**Cause:** The oid was already taken by another class.

**Action:** Use another oid.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60396: Can not retrieve admin credentials.**

**Cause:** Credential Store Framework might be unavailable.

**Action:** Check Oracle Virtual Directory server log for more detail. Reset admin user name/password in ASCTL.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**OVD-60397: Can not set admin credentials.**

**Cause:** Credential Store Framework might be unavailable.

**Action:** Check Oracle Virtual Directory server log for more detail.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**OVD-60398: Can not refresh credentials.**

---

**Cause:** Credential Store Framework might be unavailable.

**Action:** Check Oracle Virtual Directory server log for more detail.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**OVD-60399: Cannot load Log configuration.**

**Cause:** Log configuration could be invalid.

**Action:** Verify and fix Log configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60400: Object ID {0} has syntax error.**

**Cause:** The Object ID had an incorrect syntax.

**Action:** Correct the Object ID.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60401: Password Encryption type {0} not supported**

**Cause:** Oracle Virtual Directory does not support specified Password Encryption type

**Action:** Change Password Encryption type in backend datasource to one of the supported types

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-60500: Failure in initializing Auditor.**

**Cause:** AuditException happened when initialize Auditor.

**Action:** Find the cause in the error message and fix it.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**OVD-60501: Failure in logging audit message.**

**Cause:** AuditException happened when logging the audit message.

**Action:** Enlarge the maxFileSize or maxDirSize, or cleanup old audit log files.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**OVD-60502: Failure in Auditor shutdown.**

---

**Cause:** AuditException happened when shutdown Auditor.

**Action:** Find the cause in the error message and fix it.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**OVD-60503: Not able to find component Events file: {0}.**

**Cause:** Not able to find specified file.

**Action:** Make sure the specified file exists.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**OVD-60504: Not able to close component Events file: {0}.**

**Cause:** Not able to close specified file.

**Action:** Find the cause in the error message.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**OVD-60505: Unable to reset admin password or DN.**

**Cause:** Password wallet might be unavailable.

**Action:** Find the cause in the error message.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**OVD-60506: AuditService for Oracle Virtual Directory is Null.**

**Cause:** JPS Configuration for Oracle Virtual Directory AuditService might be wrong.

**Action:** Validate the JPS configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**OVD-60507: Oracle Virtual Directory Auditor is Null and not properly initialized.**

**Cause:** JPS Configuration for Oracle Virtual Directory AuditService might be wrong.

**Action:** Validate the JPS configuration file and restart Oracle Virtual Directory server.

**Level:** 1

**Type:** ERROR

**Impact:** Security

---

**OVD-60508: Failure in reloading audit configuration.**

**Cause:** JPS Configuration for Oracle Virtual Directory AuditService might be wrong.

**Action:** Validate the JPS configuration file and restart Oracle Virtual Directory server.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-60509: Failure in auditing {0} operation.**

**Cause:** Error happened while generating auditing message for the operation.

**Action:** Validate the configuration file, it might fail to be parsed.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**OVD-60600: Cannot set password : {0}.**

**Cause:** Exception when set password.

**Action:** Make sure Oracle Virtual Directory and backend LDAP server are running properly.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**OVD-60601: Cannot rollback addition : {0}.**

**Cause:** Exception when rollback addition operation.

**Action:** Make sure Oracle Virtual Directory and backend LDAP server are running properly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**OVD-60602: Cannot convert.**

**Cause:** The encoding was not supported.

**Action:** Use supported encoding.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60603: Message: {0}.**

**Cause:** Error encountered in Jetty Logger.

**Action:** Restart the Oracle Virtual Directory server.

**Level:** 1

**Type:** ERROR

---

**Impact:** Log

**OVD-60604: Cannot Create SSL Socket Factory.**

**Cause:** Error creating SSL socket.

**Action:** Verify the backend servers are properly configured for SSL.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**OVD-60605: Failure in allocating RDS port {0}.**

**Cause:** Failed in RDS API call to allocate port for Oracle Virtual Directory process.

**Action:** Ensure MAS instance is running properly.

**Level:** 1

**Type:** ERROR

**Impact:** Ports

**OVD-60606: Failure in jaxb process.**

**Cause:** Failed when trying to obtain RDS Socket.

**Action:** Check MAS instance is running properly.

**Level:** 1

**Type:** ERROR

**Impact:** Ports

**OVD-60607: Failure in releasing RDS port {0}.**

**Cause:** Not able to release RDS port.

**Action:** Make sure MAS and RDS are running properly.

**Level:** 1

**Type:** ERROR

**Impact:** Ports

**OVD-60608: Failure in releasing RDS ports.**

**Cause:** Not able to release RDS ports.

**Action:** Make sure MAS and RDS are running properly.

**Level:** 1

**Type:** ERROR

**Impact:** Ports

**OVD-60609: Cannot load key for alias: {0}.**

**Cause:** Failed to load private key.

**Action:** Make sure the key specified in configuration is the right key.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**OVD-60610: Cannot load certificate chain.**



---

**Cause:** Exception when loading certification chain.

**Action:** Verify the SSL configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**OVD-60611: Invalid LDAP URL**

**Cause:** LDAP URL provided is null or empty

**Action:** Provide a valid LDAP URL

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60612: LDAP URL does not include ://**

**Cause:** LDAP URL provided is not valid

**Action:** Provide a valid LDAP URL

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60613: Invalid scheme:**

**Cause:** Invalid protocol scheme provided in LDAP URL

**Action:** Provide a valid protocol (ldap or ldaps) in LDAP URL

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60614: Missing closing bracket for IPv6**

**Cause:** Invalid IPv6 address due to missing brackets

**Action:** Provide a valid IPv6 address in LDAP URL

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60615: IPv6 Host is empty**

**Cause:** Invalid IPv6 address due to empty host

**Action:** Provide a valid IPv6 address

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60616: Unexpected character:**

**Cause:** Invalid IPv6 address due to unexpected character

**Action:** Provide a valid IPv6 address in LDAP URL

---

**Level: 1**  
**Type: ERROR**  
**Impact: Data**

**OVD-60617: Port outside valid range**  
**Cause:** Invalid port which is outside the valid range  
**Action:** Provide a valid port which is between 1 & 65535 in LDAP URL

**Level: 1**  
**Type: ERROR**  
**Impact: Data**

**OVD-60618: Invalid port number**  
**Cause:** Invalid port which is not a number  
**Action:** Provide a valid port which is between 1 & 65535 in LDAP URL

**Level: 1**  
**Type: ERROR**  
**Impact: Data**

**OVD-60619: Invalid attribute list**  
**Cause:** Invalid attribute list  
**Action:** Provide a valid attribute list in LDAP URL

**Level: 1**  
**Type: ERROR**  
**Impact: Data**

**OVD-60620: Attribute list ends with comma**  
**Cause:** Invalid attribute list that ends with comma  
**Action:** Provide a valid attribute list in LDAP URL

**Level: 1**  
**Type: ERROR**  
**Impact: Data**

**OVD-60621: Invalid search scope**  
**Cause:** Invalid search scope provided in LDAP URL  
**Action:** Provide a valid scope in LDAP URL

**Level: 1**  
**Type: ERROR**  
**Impact: Data**

**OVD-60700: XSL Transform exception ({0}), {1}.**  
**Cause:** Error encountered with performins XSL transformation.  
**Action:** Verify the XSLT file.

**Level: 1**  
**Type: ERROR**

---

**Impact:** Data

**OVD-60701: Service Configuration Not Present.**

**Cause:** Can not find WebService configuration.

**Action:** Tag context might be missing from http listener config.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60702: Cannot load security realm.**

**Cause:** Failed to load security realm.

**Action:** Ensure security realm is correct in http listener config.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60703: Cannot Retrieve User Name.**

**Cause:** Failed while getting user name.

**Action:** Ensure username is provided.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60704: Could Not Bind, Invalid User Name.**

**Cause:** Bind failed using provided username and password.

**Action:** Ensure that the username/password are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60705: Invalid Syntax for Attribute: {0} Attribute Value: {1}.**

**Cause:** Invalid syntax for attribute value.

**Action:** Ensure that the attribute value has correct syntax.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-60800: Failed to construct user DN**

**Cause:** Error encountered while construct entry DN.

**Action:** Check the bind user DN

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-61252: Alias {0} is not a key in the provided keystore.**

---

**Cause:** The specified alias was not a key entry in the keystore.

**Action:** Provide a valid alias from the keystore.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**OVD-61258: Admin Domain restricts modification of attribute: {0}.**

**Cause:** Server did not allow addition or modification of operational attributes.

**Action:** Ensure operational attributes are not added or modified.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-61259: Modifying distinguished value of the entry without modifying the DN.**

**Cause:** Modify operation cannot be used to modify distinguished value of the entry.

**Action:** Modify DN operation should be used to rename an entry.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-61260: Attribute {0} is not present in the entry.**

**Cause:** Named entry did not contain the specified attribute.

**Action:** Perform modify operation on attributes present in the entry.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-61261: Attribute {0} does not contain value {1}.**

**Cause:** Named entry did not contain the specified attribute value.

**Action:** Perform modify operation on attribute values present in the entry.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-61262: Provided value cannot be parsed as a valid distinguished name.**

**Cause:** Distinguished name of the request did not conform to the required syntax.

**Action:** Ensure that the distinguished name conforms to the required syntax.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-61263: Attribute {0} has no values for entry: {1}**

**Cause:** Named entry has attribute which has no values

---

**Action:** Ensure all attributes present in the entry has values

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-61264: TLS already established on this connection**

**Cause:** Attempting to perform TLS on TLS enabled connection

**Action:** TLS not required for this connection

**Level:** 1

**Type:** ERROR

**Impact:** Security

**OVD-61265: Outstanding LDAP operations on this connection**

**Cause:** One or more LDAP operations outstanding on this connection

**Action:** Retry after outstanding operations are completed

**Level:** 1

**Type:** ERROR

**Impact:** Security

**OVD-61266: StartTLS cannot be enabled on this connection**

**Cause:** The corresponding LDAP listener is configured to reject StartTLS requests

**Action:** Enable StartTLS in listener configuration

**Level:** 1

**Type:** ERROR

**Impact:** Security

**OVD-61400: Unable to get local host name.**

**Cause:** Not able to query local host name.

**Action:** Refer Operation System manual to configure host name

**Level:** 1

**Type:** ERROR

**Impact:** Operating System

**OVD-61401: Failure in getting DiameterFactory instance.**

**Cause:** Internal error

**Action:** Check Oracle Virtual Directory log for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**OVD-61402: Unable to create Diameter Client Stack.**

**Cause:** Internal error

**Action:** Check Oracle Virtual Directory log for more information.

---

**Level:** 1

**Type:** ERROR

**Impact:** Session

**OVD-61403: Unable to create listening point for incoming connections.**

**Cause:** Ports might be occupied.

**Action:** Make sure listening ports are available.

**Level:** 1

**Type:** ERROR

**Impact:** Ports

**OVD-61404: Failure in creating routing table.**

**Cause:** Internal error

**Action:** Check Oracle Virtual Directory log for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Ports

**OVD-61405: Failure in CreateAndSendUDR.**

**Cause:** Requested information might be missing to construct Diameter UDR.

**Action:** Check the request and make sure sufficient information with correct syntax were provided.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-61406: Failure in CreateAndSendPUR.**

**Cause:** Requested information might be missing to construct Diameter PUR

**Action:** Check the request and make sure sufficient information with correct syntax were provided.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-61407: dataReference String Array is corrupted. Can not create UDR.**

**Cause:** The value of DataReference control was not correct.

**Action:** Check syntax and value of DataReference control in the request.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-61408: Error while creating UDR.**

**Cause:** Syntax error or missing information to construct UDR.

**Action:** Check Oracle Virtual Directory log for more information.

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-61409: Error while cleaning up Diameter connection.**

**Cause:** Failed to cleanup objects for Diameter connection.

**Action:** Check Oracle Virtual Directory log for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-61410: No dataReference specified.**

**Cause:** No value provided to DataReference control.

**Action:** Specify proper value for DataReference control.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-61411: serverName is missing for InitialFilterCriteria.**

**Cause:** serverName value was missing in DataReference control while querying InitialFilterCriteria.

**Action:** Provide serverName in the DataReference control.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-61412: serviceIndication is missing for RepositoryData.**

**Cause:** serviceIndication was missing in DataReference control while querying RepositoryData.

**Action:** Specify serviceIndication in the DataReference control.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-61413: Error while creating Diameter connection.**

**Cause:** Not able to create connection to HSS server.

**Action:** Check Diameter Adapter configuration parameters and make sure they are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-61414: Error while performing modify against Diameter Adapter.**

**Cause:** Failed the ldapmodify operation against HSS server.

**Action:** Check Oracle Virtual Directory log for more information.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-61415: UnsupportedEncodingException caught when constructing RDN of base entry from filter**

**Cause:** Syntax error of Diameter Adapter root DN.

**Action:** Correct root DN of the Diameter Adapter.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-61416: Attribute Type {0} is not valid for Diameter Adapter**

**Cause:** The RDN attribute type in search request was not supported in the Diameter Adapter.

**Action:** Use a valid Diameter RDN in search base DN or filter.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-61417: Can not obtain connection to HSS Service.**

**Cause:** HSS Service was not available

**Action:** Check if HSS service not available

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-61418: Response waiting time exceeded maximum limit.**

**Cause:** Either HSS service was not available or HSS was handling other transaction

**Action:** Check if HSS service is available, or try again later

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OVD-61419: Unknown result. Missing result Code.**

**Cause:** HSS returned a message which did not contain a result code.

**Action:** Make sure HSS server functions properly.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-61420: Requested data does not exist in the HSS.**

**Cause:** The requested data did not exist in the HSS.

**Action:** Create the data first before querying it.



---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-61421: The HSS can not fulfil the received request for reasons unknown: {0}**

**Cause:** HSS server internal error.

**Action:** Check HSS server for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-61422: The data required in the XML schema does not match what specified within the HSS**

**Cause:** The requested data did not exist in the HSS.

**Action:** Add the data to the HSS before querying or updating it.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-61423: The RDN attribute of rootDN: {0} is not valid**

**Cause:** The RDN attribute type in the rootDN of the Diameter Aapter was not valid.

**Action:** Use one of the following attribute as the RDN attribute type: ou, dc, c, cn

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-61424: The requested operation is not allowed for the user.**

**Cause:** The user was not allowed for the requested operation against the HSS.

**Action:** Make sure the user has privilege for the operation

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-61425: The requested user data is not allowed to be read.**

**Cause:** The data referenced in the request was not allowed to be read.

**Action:** Make sure the user data in the HSS is allowed to be read.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-61426: The requested user data is not allowed to be modified.**

**Cause:** The data in the HSS was not allowed to be updated.

**Action:** Check the HSS that the UUP is permitted to update the referenced data.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-61427: The size of the data pushed to the receiving entity exceeded its capacity.**

**Cause:** There was more data than the HSS is prepared to accept.

**Action:** Reduce the size of the data in the update request.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-61428: The request to update the repository data at the HSS could not be completed.**

**Cause:** The requested update was based on an out-of-date version of the HSS repository schema.

**Action:** Execute a query to retrieve the current version of the data from the HSS.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-61429: The requested user data is not available at this time to satisfy the requested operation.**

**Cause:** The requested user data was not available at this time to satisfy the requested operation.

**Action:** Check the request is against an existing user.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-61430: The request to update the repository data at the HSS could not be completed.**

**Cause:** The related repository data was being updated by another entity.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OVD-61431: Search Operation Failure in Parsing HSS Data Reference Control.**

**Cause:** Syntax error.

**Action:** Verify syntax of specified DataReference control.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-61432: Missing mandatory parameter: remotePeers.**

---

**Cause:** remotePeers parameter was missing from Diameter adapter plugin configuration.

**Action:** Edit plugin and add remotePeers parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-61433: Invalid value for the DiameterAdapter plug-in interface parameter: {0}**

**Cause:** The interface parameter specified in the DiameterAdapter plug-in was not supported.

**Action:** The valid DiameterAdapter plugin-in interface parameters are: [Sh, Cx, Dx, Ro, Rf, Base]

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-61434: Cannot retrieve XSS Ruleset for this URL {0}.**

**Cause:** Failed to retrieve the rule set for this URL .

**Action:** Set the rule set and try again later.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-61600: Invalid operation for anonymous user.**

**Cause:** The requested operation is not allowed to anonymous users.

**Action:** Refer product documents for details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OVD-80001: An attempt to start Oracle Virtual Directory server failed.**

**Cause:** One or more mandatory system properties are missing.

**Action:** Ensure that all mandatory system properties are set.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**OVD-80002: System Exiting....**

**Cause:** The system was shut down because of missing plug-in files.

**Action:** Ensure that the plugins that are configured, the plugin source is available.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**OVD-80003: Fatal Error! Downgrading configuration not supported.**

**Cause:** Changing configuration file schema version to older value.

**Action:** Make sure the new schema version is greater than the current schvers in configuration files.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-80004: Errors occurred while parsing {0}. Correct before starting. Shutting down...**

**Cause:** Syntax errors in the specified configuration file.

**Action:** Correct the syntax errors in the configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-80005: Cannot read file : {0}.**

**Cause:** Not able to open the specified file.

**Action:** Make sure the file exists and accessible.

**Level:** 1

**Type:** ERROR

**Impact:** Operating System

**OVD-80006: Parse Error : {0}.**

**Cause:** Error parsing configuration xml file.

**Action:** Correct the parsing error.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-80007: Errors occurred while parsing adapters. Correct before starting.**

**Cause:** Error in parsing adapters.os\_xml file.

**Action:** Correct the adapters.os\_xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-80008: Configuration Error: {0} - {1}.**

**Cause:** Error encountered when loading the configuration file.

**Action:** Make sure the configuration file is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**OVD-80009: Errors occurred while parsing listeners. Correct before starting.**

**Cause:** Error encountered when loading the listener configuration file.

**Action:** Correct the listeners.os\_xml file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-80010: Errors occurred while parsing the server configuration.**

**Cause:** Error encountered when loading the server configuration file.

**Action:** Correct the errors in server.os\_xml file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-80011: Cannot parse Adapters.**

**Cause:** Error occurred when parsing adapters configuration.

**Action:** Check the adapters configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-80012: Invalid data file: {0}.**

**Cause:** Filename specified in configuration was invalid.

**Action:** Provide valid filename in configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-80013: Configuration handler failure: {0}.**

**Cause:** Configuration files might be missing.

**Action:** Make sure configuration files are in the right directory.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-80014: EUS Reversible Password Configuration Error: {0}.**

**Cause:** Could not retrieve reversible password from the backend LDAP server.

**Action:** Make sure the EUS configuration for the backend LDAP server is done correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OVD-80015: Null admin user.**

---

**Cause:** The admin user was null.

**Action:** Make sure that you have a valid CSF configuration containing admin user and password.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

## OWS-00016 to OWS-65005

**OWS-00016: no method to retrieve the daylight savings offset (getDSTSavings) defined on TimeZone**

**Cause:** Oracle did not find a method for setting daylight savings time for the default timezone on this system.

**Action:** Check that default timezone is set correctly. Check that the Java Runtime Environment(TM) (JRE) that is used is complete.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OWS-00017: literal ArraySerializer.initialize error encountered: Exception message is {0} Stack trace is {1}**

**Cause:** Could not initialize Literal Array Serializer for JAXRPC databinding

**Action:** System Internal Error - Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**OWS-00029: Error reading WSM client configuration file: {0}.**

**Cause:** The client side proprietry descriptor is invalid

**Action:** Validate the client proprietary descriptrtor as per the schema "http://xmlns.oracle.com/oracleas/schema/11/oracle-webservices-client-11\_1.xsd"

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OWS-00030: Failed to find wsm client configuration file {0}**

**Cause:** The user specified client side oracle webservices proprietary configuration file is missing.

**Action:** Ensure the valid location of client side config file is provided or it's available in classpath

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**OWS-00032: Error reading WSM server configuration file: {0}.**

**Cause:** Cannot read WSM server configuration file

**Action:** Ensure given WSM configuration file(Oracle proprietry descriptor) at server side is valid

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OWS-00033: Failed to find deployment descriptor file {0}**

**Cause:** Could not find deployment descriptor file

**Action:** Ensure server side deployment descriptor file is not missing

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OWS-00046: Cannot update web.xml file, <url-pattern> {0} already exists.**

**Cause:** The file output/war/WEB-INF/web.xml already contains a URL pattern that the system wants to use for another servlet mapping.

**Action:** Specify a unique uri argument or change the url-pattern in the existing web.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00047: Could not update web.xml because <servlet-name> "{0}" already exists.**

The value of <servlet-name> generated by Web Services Assembler is the port name. If bottom-up assembly is used, specify a portName argument value that does not already exist. If topdown assembly or the genDDs command is used, put the two Web services in different WAR files, so that they do not share deployment descriptors.

**Cause:** The file output/war/WEB-INF/web.xml contained the URL and it was assigned to another servlet.

**Action:** For bottom-up assembly specify a different portName. For top-down assembly or genDDs separate two Web services into different WAR files or change the name of the servlet in the web.xml file.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00048: Could not update webservicess.xml because**

<webservice-description-name> "{0}" already exists. The value of the <webservice-description-name> generated by Web Services Assembler is always the service name. If bottom-up assembly is used, specify a serviceName argument value that does not already exist. If topdown assembly or the genDDs command is used, put the two Web services in different WAR files so they do not share deployment descriptors.



---

**Cause:** The file output/war/WEB-INF/webservices.xml already contains a webservice-description-name. The system wants to re-use this name for a new Web service. The value of the <webservice-description-name> generated by the system is always the service name.

**Action:** If bottom-up assembly is used, specify a serviceName argument value that does not already exist. If top-down assembly or the genDDs command is used, put the two Web services in different WAR files, so that they do not share deployment descriptors.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00049: Could not update webservices.xml because <port-component-name> "{0}" already exists. The value of <port-component-name> generated by Web Services Assembler is always the port name. If bottom-up assembly is used, specify a portName argument value that does not already exist. If topdown assembly or the genDDs command is used, put the two Web services in different WAR files, so they do not share deployment descriptors.**

**Cause:** The file output/war/WEB-INF/webservices.xml already contains a port-component-name that the system wants to use for a new port. The value of the <port-component-name> generated by the system is always the port name.

**Action:** If bottom-up assembly is used, specify a portName argument value that does not already exist. If top-down assembly or the genDDs command is used, put the two Web services in different WAR files, so that they do not share deployment descriptors.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00050: Could not update oracle-webservices.xml because <webservice-description> name "{0}" already exists. The name of the <webservice-description> generated by Web Services Assembler is always the service name. If bottom-up assembly is used, specify a serviceName argument value that does not already exist. If topdown assembly or the genDDs command is used, put the two Web services in different WAR files, so they do not share deployment descriptors.**

**Cause:** The file output/war/WEB-INF/oracle-webservices.xml already contains a webservice-description-name that the system wants to use for a new webservice. The value of the <webservice-description-name> generated by the system is always the service name.

**Action:** If bottom-up assembly is used, specify a serviceName argument value that does not already exist. If top-down assembly or the genDDs command is used, put the two Web services in different WAR files so they do not share deployment descriptors.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00051: Could not update oracle-webservices.xml because <port-component> name "{0}" already exists. The value of <port-component> name generated by**

---

**Web Services Assembler is always the port name. If bottom-up assembly is used, specify a portName argument value that does not already exist. If topdown assembly or the genDDs command is used, put the two Web services in different WAR files so they do not share deployment descriptors.**

**Cause:** The file output/war/WEB-INF/webservices.xml already contains a port-component name that the system wants to use for a new port. The value of the <port-component> name generated by the system is always the port name.

**Action:** If bottom-up assembly is used, specify a portName argument value that does not already exist. If top-down assembly or the genDDs command is used, put the two Web services in different WAR files so they do not share deployment descriptors.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00052: Could not update oracle-webservices.xml because <endpoint-address-uri> "{0}" already exists. Specify a uri argument value that does not already exist.**

**Cause:** The file output/war/WEB-INF/oracle-webservices.xml already contains an endpoint-address-uri that the system wants to use for a new webservice port.

**Action:** Specify a uri argument value that does not already exist.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00054: When "linkReceiveWithReplyTo" is true, either receive destination/connection-factory or reply-to destination/connection-factory must be set.**

**Cause:** The linkReceiveWithReplyTo argument requires the receive or reply-to arguments defined so the system can make the values the same.

**Action:** Specify replyToConnectionFactoryLocation and (replyToQueueLocation or replyToTopicLocation) or specify receiveConnectionFactoryLocation and (receiveQueueLocation or receiveTopicLocation).

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00055: When "linkReceiveWithReplyTo" is true, the value of parameter "{0}" and parameter "{1}" should be same.**

**Cause:** When the argument linkReceiveWithReplyTo is set to true and both replyTo\* and receive\* arguments are specified they must have the same value.

**Action:** Either remove one of the arguments shown in the message or set the arguments to the same value.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00070: No matching type found for the custom type mapping with QName {0}**

---

**Cause:** A custom type has been defined in an oracle-webservices.xml file but no associated type can be found in the schemas associated with the webservice.

**Action:** Remove the custom type mapping or correct the name of the custom type mapping so it matches a type in the schema.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**OWS-00073: A failure occurred during Oracle Web Services Management agent interceptor {0} processing. {1}**

**Cause:** Could not process Oracle Web Services Management Agent interceptor

**Action:** System Internal Error - Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00084: Failed to find Oracle Web Services Management agent configuration {0}**

**Cause:** Could not find Oracle Web Services Management agent configuration file

**Action:** Ensure correct location of OWSM agent configuration file is provided

**Level:** 1

**Type:** ERROR

**Impact:** Files

**OWS-00101: Mapped {0} to javax.xml.soap.SOAPElement.**

**Cause:** The system defaults to a SOAP element, since it could not determine how to map the specified schema type to a Java Bean.

**Action:** Switching to a different data binding like JAXB may allow the system to create Java objects for the type.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-00114: use of an unimplemented feature.**

**Cause:** An unimplemented feature is used in the schema.

**Action:** Avoid the unimplemented feature or use the SAAJ API to construct the XML element.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-00115: the base type is not supported.**

**Cause:** An unimplemented feature is used in the base type definition.

**Action:** Avoid the unimplemented feature or use the SAAJ API to construct the XML element.

**Level:** 1

---

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-00139: The body of the method by name "{0}" could not be merged. The new method required code is "{1}"**

**Cause:** During top-down generation JDeveloper could not merge the generated code and modified code.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00140: No body expected for the method "{0}".**

**Cause:** During top-down generation JDeveloper found unexpected code in the Java source file provided by the user.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00141: HTTP transport error: {0}**

**Cause:** Error while getting the SOAPConnectionFactory object due to unsupported SAAJ communication infrastructure

**Action:** System Internal Error - Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00142: local transport error: {0}**

**Cause:** Error occurred while processing request

**Action:** System Internal Error - Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00143: service error: {0}**

**Cause:** Service Invocation failed. It might be because of an error while generating the stub implementation class or a dynamic proxy.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00144: not an interface: {0}**

**Cause:** In the createService(Class serviceInterface, QName name) method client code has provided an interface that is not a Service interface.

---

**Action:** Ensure that the supplied interface extends javax.xml.rpc.Service

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00145: cannot locate service implementation class for service: {0}**

**Cause:** An error occurred while generating a stub implementation class or a dynamic proxy. The service implementation class could not be found in the classpath.

**Action:** Ensure that the service implementation class is available in the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00146: failed to create service implementation instance: {0}**

**Cause:** An error occurred while generating a stub implementation class or a dynamic proxy. The service implementation class does not implement a concrete service interface and thus could not be instantiated.

**Action:** Ensure that specified service implementation class implements JAXRPC service interface and it's available in the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00147: dynamic invocation error: {0}**

**Cause:** Unexpected Error while invoking the service method.

**Action:** Ensure that the DII client that invoking the service is configured correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00148: service: {0} does not contain port: {1}**

**Cause:** Service Invocation failed because the <wsdl:service> element does not contain any ports.

**Action:** Ensure that the <wsdl:service> element has at least one port defined.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00149: port: {0} does not contain operation: {1}**

**Cause:** Service Invocation failed because service endpoint does not contain specified operation.

**Action:** Ensure that DII client invoking the operation that advertised in the service descriptor i.e WSDL.

**Level:** 1

---

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00150: property: "{0}" must be set on a Call object before it can be invoked in this configuration**

**Cause:** The Dynamic Invocation Interface (DII) client has not set the required property on the Call object.

**Action:** For DII client, ensure that all required properties are set correctly on Call object before invoking service.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00156: call object cannot be created without a TypeRegistry**

**Cause:** Service Invocation failed because the InternalTypeMappingRegistry for serialization/deserialization provided to the Call object is null

**Action:** System Internal Error - Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00157: cannot set unrecognized property: {0} on a Call object**

**Cause:** Client code is trying to set a property that is not specified for Call objects.

**Action:** Check the name of the property that is being set. Use only properties specified for Call objects.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00158: cannot get unrecognized property: {0} on a Call object**

**Cause:** Client code is trying to get a property that is not specified for Call objects.

**Action:** Check the name of the property that client side code is trying to access. Use only properties specified for Call objects.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00159: WSDL data missing, this operation is not available**

**Cause:** An unconfigured Dynamic Invocation Interface (DII) client is using the getCalls(Qname portName) method on a Service object that does not have an associated WSDL.

**Action:** Either use a fully configured DII client, or use a createCall() method that explicitly specifies all required port and operation information to create a Call object instance.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**OWS-00160: WSDL data missing, {}**

**Cause:** An unconfigured (Dynamic Invocation Interface (DII) client uses getPort method on Service Implementation object which is not supported when WSDL information is missing

**Action:** Use the configured DII client by getting the service implementation object using createService(java.net.URL wsdlDocLoc, QName name) method on ServiceFactory object

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00161: output parameters are only available after invoke() has been called**

**Cause:** Dynamic Invocation Interface (DII) client code is trying to get the output parameters before invoking the service

**Action:** Ensure that the client code has invoked the service first before accessing the value of output parameters.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00162: cannot set parameter or return types on this Call object**

**Cause:** Dynamic Invocation Interface (DII) client attempted to set parameter or return types on a Call object when service operation does not require input parameter and does not return anything.

**Action:** Check whether Call object requires to set parameter or return type by calling isParameterAndReturnSpecRequired() on Call object

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00163: operation style: "{0}" not supported**

**Cause:** Dynamic Invocation Interface (DII) Client sets the Call.OPERATION\_STYLE\_PROPERTY to other than 'rpc' or 'document'

**Action:** Set Call.OPERATION\_STYLE\_PROPERTY to either 'rpc' or 'document'

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00164: encoding style: "{0}" not supported**

**Cause:** Dynamic Invocation Interface (DII) client sets the ENCODINGSTYLE\_URL\_PROPERTY to an unsupported value i.e other than 'http://schemas.xmlsoap.org/soap/encoding' or null

**Action:** Use either 'encoded' or 'literal' encoding style.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**OWS-00165: could not find service: {0} in the specified WSDL file. The service names found were: {1}**

**Cause:** Service name provided by client code is not available in the specified WSDL.

**Action:** Check the Service name used by the client code and ensure that correct Service name is used as per the specified WSDL.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00166: could not dispatch to method: {0} known methods are: {1}**

**Cause:** Operation that Dynamic Invocation Interface (DII) client code is trying to invoke does not match with any operation provided by the service.

**Action:** Make sure correct Operation name is used by the DII client code while configuring Call Object.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00167: The attachment DataHandler object cannot be null**

**Cause:** The attachment DataHandler object cannot be null

**Action:** Make sure DataHandler attached to Call object is not null

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00168: error.build.wsdl.model: {0}**

**Cause:** Error in the WSDL Model generation at the client side during service invocation. The useWSI property was set to true, but the WSDL does not conform to the WSI basic profile.

**Action:** Ensure that the specified WSDL is compliant to Web Services Interoperability(WS-I) Basic Profile.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00169: Wrong value type {0} for property {1}. java.io.File or org.w3c.dom.Element is expected**

**Cause:** An unexpected value was set on a Call object. The value must be either of type java.io.File or of type org.w3c.dom.Element.

**Action:** Check the type of the value being set on the Call object.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses



---

**OWS-00170: serialization error: {0}**

**Cause:** Serializer class is missing.

**Action:** Make sure the serializer class is defined and available from the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00171: deserialization error: {0}**

**Cause:** Deserializer failed.

**Action:** Check the incoming message.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00172: encoding error: {0}**

**Cause:** Failed to initialize dynamic serializer/deserializer for RPC/ENC request

**Action:** System Internal Error - Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00173: malformed array type: {0}**

**Cause:** The array index is less than 0 or the end index is less than the start index.

**Action:** Check the incoming message.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00174: serialized array has too many elements**

**Cause:** At least one array element position is outside the array boundaries in the inbound message.

**Action:** Check the incoming message

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00175: illegal array element position: {0}**

**Cause:** Either the array dimension is empty and the element position is not one, or the array dimension length is not equal to the element position length.

**Action:** Check the incoming message

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**OWS-00176: missing array position attribute**

**Cause:** Sparse array does not have a position attribute

**Action:** Check the incoming message

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00177: array element position is out of bounds: {0}**

**Cause:** An array position value is outside the array bounds

**Action:** Check the incoming message

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00178: unexpected null value during serialization or deserialization**

**Cause:** Deserializer cannot deserialize null to a non-nillable object.

**Action:** Check the incoming message.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00180: unexpected reference element during deserialization; the element "{0}" is not defined as a referenceable type**

**Cause:** Failed to deserialize the request message. The request element uses a reference type which is not specified in the WSDL.

**Action:** Correct the WSDL definition or correct the request message.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00181: unexpected element type: expected={0}, actual={1}**

**Cause:** Failed to deserialize the request message. The request element type does not match what is defined in the WSDL.

**Action:** Correct the WSDL definition or correct the request message.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00182: unexpected element name: expected={0}, actual={1}**

**Cause:** Failed to deserialize the request message. The request element name does not match what is defined in the WSDL.

**Action:** Correct the WSDL definition or correct the request message.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**OWS-00183: unexpected array element type: expected={0}, actual={1}**

**Cause:** The type of an array element does not match its definition in the schema.

**Action:** Verify that the type of the array element being sent matches the type defined in the schema.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00184: non-local reference (href): {0}**

**Cause:** The href attribute, used to reference an attachment, is not specified using the "cid" (Content-ID) protocol string.

**Action:** Change the value of the href attribute, used to reference an attachment, to a string that begins with "cid:".

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00185: trailing block elements must have an id attribute**

**Cause:** An element in the SOAP message contains a reference to another element. However no element was found with an id attribute matching the reference.

**Action:** Validate the correctness of the received message.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00186: malformed array dimensions: {0}**

**Cause:** The bounds of the array are invalid. For example the lower bound of the array is larger than the upper bound.

**Action:** See error message.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00187: multi-dimensional array is not regular**

**Cause:** One level in a multi-dimensional array instance is null or contains an invalid size.

**Action:** Ensure that all levels of the multi-dimensional array contain valid values.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00188: illegal array offset: {0}**

**Cause:** The value specified in the "offset" attribute of an array element is invalid.

---

**Action:** Ensure that the value specified in the offset attribute of the array element in the SOAP message is within the range of the array dimensions.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00189: array has unexpected rank: expected={0}, actual={1}, arrayType={2}**

**Cause:** The rank of an array does not match the rank specified in the schema.

**Action:** Verify that the soapenc:rank attribute of the array element in the schema matches with the actual dimensions of the array in the SOAPMessage.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00190: array has unexpected dimensions: expected={0}, actual={1}, arrayType={2}**

**Cause:** The dimensions of an array in the SOAP element do not match those of the element defined in the Schema.

**Action:** Verify that the SOAP message matches the WSDL definition

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00191: unexpected encoding style: expected={0}, actual={1}**

**Cause:** The encoding style being used in the message is invalid for the SOAP version. For example, SOAP 1.1 expects the encoding style <http://schemas.xmlsoap.org/soap/encoding/> while SOAP 1.2 expects a range of values, one of which is <http://www.w3.org/2003/05/soap-encoding>.

**Action:** Ensure that the encoding style uri of the SOAP message is valid for the version of SOAP in use. Check the SOAP 1.1 and SOAP 1.2 for acceptable values.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00192: cannot encode XML type because it was not specified**

**Cause:** Unable to find XML type for object.

**Action:** System Internal Error - Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00193: member {0} has already been defined**

**Cause:** While deserializing the SOAP message a duplicate member variable or setter/getter was found in the target object.

**Action:** System Internal Error - Contact Oracle Support Services

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00194: incomplete object encountered while deserializing**

**Cause:** Failure during deserialization (XML to Java).

**Action:** System Internal Error - Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00195: circular reference detected while serializing: {0}**

**Cause:** An object is referenced from another object that it references. For example A->B->A. This circular reference is not supported in RPC-Literal or Doc-Literal web services.

**Action:** Remove the circular dependency or change the web service to RPC-Encoded.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00196: no attachment with cid (Content-ID) "{0}" found in message**

**Cause:** The cid (Content-ID) for a particular attachment that was referenced from the SOAP body was not found.

**Action:** Make sure that the cid is formatted properly. Examine the cid in the soap body with the Content-Id header of the SOAP Message MIME attachment and verify that they match.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00197: multiple attachments with the same cid (Content-ID) "{0}" found in message**

**Cause:** Found multiple attachments with the same cid (Content-ID). This field must be unique

**Action:** If the SOAP message was manually constructed, verify that all the Content-ID headers contain a unique value.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00198: missing cid (Content-ID header) for attachment**

**Cause:** An attachment was missing the Content-Id header.

**Action:** Examine the SOAP message and verify that all Content-Id headers contain a value.

**Level:** 1

---

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00199: non "cid:" (Content-ID) reference: {0}**

**Cause:** A SwaRef attachment was found with an invalid reference to a MIME attachment. MIME attachment references must begin with the string "cid:".

**Action:** Verify that the attachment reference begins with "cid".

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00203: serializeAsAttachment specified but no AttachmentEncoder was provided for type: "{0}"**

**Cause:** Missing serializer for a particular attachment type.

**Action:** System Internal Error - Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00204: a deserializer must be registered with a deserialization state before it will accept listeners**

**Cause:** A serializer class was not found during initialization of the serializer framework.

**Action:** System Internal Error - Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00205: cannot decode XML type "{0}"**

**Cause:** Unable to construct an object from an XML instance (element).

**Action:** System Internal Error - Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00206: cannot serialize type "{0}"**

**Cause:** An appropriate default serializer for the specified type could not be found.

**Action:** A custom serializer must be used for the indicated type. Implementing a custom serializer for a Web service is described in the Oracle Application Server Web Services Developer's Guide.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00207: null soap version not allowed.**

---

**Cause:** The SOAP message did not contain enough information to determine the version of the SOAP specification used.

**Action:** Typically the SOAP version is determined by inspecting the namespace declared on the root element (Envelope) of the SOAP message. This value should be one of <http://schemas.xmlsoap.org/soap/envelope/> for SOAP 1.1 or <http://www.w3.org/2003/05/soap-envelope> for SOAP 1.2.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00208: cannot have enc:id and enc:ref attributes on the same element.**

**Cause:** The SOAP message element contains both an id and a ref attribute. Using both on the same element is illegal.

**Action:** The Webservice client that created the message must be modified so that invalid SOAP messages are not created.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00209: unexpected element name: expected={0}, actual={1}**

**Cause:** The deserializer encountered an unexpected element name when processing the SOAP message.

**Action:** The Webservice client that created the message must be modified so that the SOAP messages it creates conform to the messages described in this Webservice's WSDL.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00210: unexpected element type: expected={0}, actual={1}**

**Cause:** The deserializer encountered an unexpected element type when processing the SOAP message.

**Action:** The Webservice client that created the message must be modified so that the SOAP messages it creates conform to the messages described in this Webservice's WSDL.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00211: unexpected null**

**Cause:** The (de)serializer encountered an unexpected null element/object when processing the SOAP message.

**Action:** The Webservice client that created the message must be modified so that the SOAP messages it creates conform to the messages described in this Webservice's WSDL.

**Level:** 1

---

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00212: unknown prefix in QName literal: {0}**

**Cause:** The deserializer cannot figure out the Namespace URI for the given prefix when processing the SOAP message.

**Action:** The Webservice client that created the message must be modified so that invalid SOAP messages are not created.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00213: invalid XSD date: {0}**

**Cause:** The deserializer encountered an invalid XSD date when processing the SOAP message.

**Action:** The Webservice client that created the message must be modified so that SOAP messages with invalid XSD dates are not created.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00214: invalid XSD boolean value: {0}**

**Cause:** The deserializer encountered an invalid XSD boolean when processing the SOAP message.

**Action:** The Webservice client that created the message must be modified so that SOAP messages with invalid XSD boolean are not created.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00215: attachment location not found on element**

**Cause:** The deserializer cannot determine the attachment location on an element with binary type.

**Action:** The Webservice client that created the message must be modified so that SOAP messages with attachments will correctly reference the attachments.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00216: attachment with id {0} not found in message**

**Cause:** The deserializer cannot find the attachment from the specified location on an element with binary type.

**Action:** The Webservice client that created the message must be modified so that SOAP messages with attachments will correctly reference the attachments.

**Level:** 1

**Type:** ERROR



---

**Impact:** Requests/Responses

**OWS-00217: invalid XSD positiveInteger value: {0}**

**Cause:** The deserializer encountered an invalid XSD positiveInteger when processing the SOAP message.

**Action:** The Webservice client that created the message must be modified so that SOAP messages with invalid XSD positiveInteger are not created.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00218: invalid XSD nonNegativeInteger value: {0}**

**Cause:** The deserializer encountered an invalid XSD nonNegativeInteger when processing the SOAP message.

**Action:** The Webservice client that created the message must be modified so that SOAP messages with invalid XSD nonNegativeInteger are not created.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00219: invalid XSD negativeInteger value: {0}**

**Cause:** The deserializer encountered an invalid XSD negativeInteger when processing the SOAP message.

**Action:** The Webservice client that created the message must be modified so that SOAP messages with invalid XSD negativeInteger are not created.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00220: invalid XSD nonPositiveInteger value: {0}**

**Cause:** The deserializer encountered an invalid XSD nonPositiveInteger when processing the SOAP message.

**Action:** The Webservice client that created the message must be modified so that SOAP messages with invalid XSD nonPositiveInteger are not created.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00222: invalid XSD unsignedLong value: {0}**

**Cause:** The deserializer encountered an invalid XSD unsignedLong when processing the SOAP message.

**Action:** The Webservice client that created the message must be modified so that SOAP messages with invalid XSD unsignedLong are not created.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**OWS-00223: invalid XSD unsignedInt value: {0}**

**Cause:** The deserializer encountered an invalid XSD unsignedInt when processing the SOAP message.

**Action:** The Webservice client that created the message must be modified so that SOAP messages with invalid XSD unsignedInt are not created.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00224: invalid XSD unsignedShort value: {0}**

**Cause:** The deserializer encountered an invalid XSD unsignedShort when processing the SOAP message.

**Action:** The Webservice client that created the message must be modified so that SOAP messages with invalid XSD unsignedShort are not created.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00225: invalid XSD unsignedByte value: {0}**

**Cause:** The deserializer encountered an invalid XSD unsignedByte when processing the SOAP message.

**Action:** The Webservice client that created the message must be modified so that SOAP messages with invalid XSD unsignedByte are not created.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00227: error in initialization of standard type mapping: {0}**

**Cause:** Internal error initializing the standard type mapping.

**Action:** System Internal Error - Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00228: {0} : is not a supported (de)serialization mechanism**

**Cause:** The (de)serializer factory does not support the reported XML processing mechanism type.

**Action:** System Internal Error - Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00229: type mapping registration failed: {0}**

**Cause:** An unexpected error occurred during registration of a Java to XML mapping. Check the nested error for the real cause.

**Action:** Look at the nested error to determine what action to take.

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00230: type mapping retrieval failed: {0}**

**Cause:** An unexpected error occurred during retrieval of a Java to XML mapping. Check the nested error for the real cause.

**Action:** Look at the nested error to determine what action to take.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00231: type mapping does not support the specified encoding style: {0}**

**Cause:** The system does not support the specified schema type and encoding.

**Action:** Change the encodingStyle defined in the SOAP binding in the WSDL to a supported value.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00232: there is no type mapping for the specified encoding style: {0}**

**Cause:** The system does not support the specified encoding.

**Action:** Change the encodingStyle defined in the SOAP binding in the WSDL to a supported value.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00233: no serializer is registered for ({0}, {1})**

**Cause:** The system could not find a serializer that can convert the Java object to XML.

**Action:** Create a custom type mapping and serializer that can convert the Java object to XML.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00234: no deserializer is registered for (java type: {0}, schema type: {1})**

**Cause:** The system could not find a deserializer that can convert the XML to a Java object.

**Action:** Create a custom type mapping and serializer that can convert the XML to a Java object.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**OWS-00235: no deserializer is registered for schema type: {0}**

**Cause:** The system could not find a deserializer that can convert the XML to a Java object.

**Action:** Create a custom type mapping and serializer that can convert the XML to a Java object.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00236: no deserializer is registered for java type: {0}**

**Cause:** The system could not find a deserializer that can convert the XML to a Java object.

**Action:** Create a custom type mapping and serializer that can convert the XML to a Java object.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00237: dynamic resolution failed to find a serializer for java type:{0}, xml type {1}**

**Cause:** An entry in a list or collection is a type that is not supported by the system.

**Action:** Change the instance of the entry to a supported Java type.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00238: dynamic resolution failed to find a serializer for java type: {0}, xmlType: {1}**

**Cause:** An entry in a list or collection is a type that is not supported by the system.

**Action:** Change the instance of the entry to a supported Java type.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00241: Map entry key cannot be of java type:"{0}", xml type "{1}"**

**Cause:** The key for a map entry has a type mapping for an object that the system does not support.

**Action:** Change the signature of the Java class to a supported Java type or change the instance of the key to a supported type.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00242: Map entry value cannot be of Java type:"{0}", XML type was "{1}"**

**Cause:** The value for a map entry has a type mapping for an object that the system does not support.

---

**Action:** Change the signature of the Java class to a supported Java type or change the instance of the value to a supported type.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00243: Item in array cannot be of java type:"{0}"**

**Cause:** An item in an array is a type that is not supported by the system.

**Action:** Change the signature of the Java class to a supported Java type or change the instance of the value to a supported type.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00245: unexpected null value for literal data**

**Cause:** The element defined in the schema has a nillable attribute set to false but no value was found in the message.

**Action:** Change the client to supply a value for the literal type, or change the schema to accept nillable types.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00246: unexpected element name: expected={0}, actual={1}**

**Cause:** A message contains an element that the system does not expect.

**Action:** Change the client to send messages corresponding to the schema, or change the schema to correspond to the messages.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00247: expected element is missing: {0}**

**Cause:** The message does not contain an element that is defined as required in the schema.

**Action:** Change the schema to make the element optional, or change the client so that the message will include the required element.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00248: expected simple content, found element name: {0}**

**Cause:** The system was expecting a simple content in the message but found an element instead.

**Action:** Change the client to send messages corresponding to the schema, or change the schema to correspond to the messages.

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00249: object not initialized before use**

**Cause:** A serializer was not initialized before calling a method that requires initialization.

**Action:** System Internal Error - Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00250: {0} is not an array type**

**Cause:** The system found a Java object that is not an array when an array is expected.

**Action:** System Internal Error - Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00251: expected {0} parameter(s) but received: {1}. Expected parameters: {3}, received parameters:{4}**

**Cause:** The number of parameters in the request SOAP message is incorrect.

**Action:** Confirm that the client is based on the correct version of the WSDL definition.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00252: illegal deserialization state: no deserializer is available for the current element**

**Cause:** There is no deserializer registered for the element.

**Action:** A custom serializer must be used for the indicated type. Implementing a custom serializer for a Web service is described in the Oracle Application Server Web Services Developer's Guide.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00253: Invalid base64 data**

**Cause:** The SOAP request content being processed by the XSDBase64BinaryEncoder is not Base64 encoded.

**Action:** Confirm that the client is based on the correct, current version of the WSDL document.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**OWS-00254: generator error: {0}**

**Cause:** An unexpected exception occurred during a generation operation.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00255: can't write file: {0}**

**Cause:** A generated file could not be written to disk. The most likely causes include insufficient disk space or permissions.

**Action:** Free some disk space or ensure that the process in which the generator is invoked is run as a user with sufficient permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00256: can't create directory: {0}**

**Cause:** The directory for writing a generated file could not be created. The most likely causes include insufficient disk space or permissions.

**Action:** Free some disk space or ensure that the process in which the generator is invoked is run as a user with sufficient permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00257: unsupported type encountered: '{1}'>{0}**

**Cause:** Serialization is not supported for this XML type.

**Action:** A custom serializer must be used for the indicated type. Implementing a custom serializer for a Web service is described in the Oracle Application Server Web Services Developer's Guide.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00258: no Java type for XML type: {0}**

**Cause:** Unable to determine the corresponding Java type for a structured XML type when generating a serializer.

**Action:** Ensure that a Java type is associated with the structured XML type and that the custom serializer mapping is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00259: unsupported encoding encountered: {0}**

---

**Cause:** The encoding URI of custom serializer mapping does not match that of either SOAP 1.1 or SOAP 1.2.

**Action:** Correct the URI encoding of the custom serializer mapping.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00260: tie class generation error: {0}**

**Cause:** When generating the tie class for a document literal operation, either more than one non-embedded parameter was found, or there were both embedded and non-embedded parameter.

**Action:** This sanity check should not have failed. Verify that the document literal operation is correct in the WSDL.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00262: There is no management configuration for port {0} in the supplied proprietary deployment descriptor. Ensure that the port name is correct**

**Cause:** There is no management configuration information for the port in the supplied management configuration file.

**Action:** Verify that the port name is correct and the management configuration file is complete.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-00263: Could not find the Java class {0} for constructor analysis.**

**Cause:** Could not find the Java class for constructor analysis when generating its serializer.

**Action:** Check the Java class name and the classpath where the Java class is loaded.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-00264: Current SOAP Version is null. Check port to make sure SOAP version is set.**

**Cause:** Could not determine the SOAP version when generating serializer.

**Action:** Verify that the SOAP version is set in the WSDL.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses



---

**OWS-00266: When using JMS transport, either all operations must be one-way, or the replyToConnectionFactoryLocation and replyToQueueLocation must be specified.**

**Cause:** When using JMS transport for any two-way operation, the replyToConnectionFactoryLocation and replyToQueueLocation parameters must be specified with the jsmAssemble command.

**Action:** Re-run the jsmAssemble command with replyToConnectionFactoryLocation and replyToQueueLocation parameters.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-00267: cannot dispatch operation with more than one body block: {0}**

**Cause:** Cannot generate tie class for operations with more than one body block.

**Action:** Verify that the offending operation has no more than one body block.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00268: cannot dispatch operation - either operation names are non-unique, or SOAPAction strings are non-unique: {0}**

**Cause:** Cannot generate tie class for operation with non-unique operation name and non-unique SOAPAction.

**Action:** Verify that both the operation name and SOAPAction are unique in the WSDL.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00269: no encoder for type "{0}" and Java type "{1}"**

**Cause:** Unable to find an encoder for a type and its corresponding Java type when generating serializer.

**Action:** Check whether the type is valid and supported.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00270: Invalid type in xsd:list type "{0}" and Java type "{1}"**

**Cause:** Unable to find an encoder for the list item type and its corresponding Java type when generating serializer.

**Action:** Check whether the list item XML type is valid and supported.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00271: handler error: {0}**

---

**Cause:** A handler error occurred, check the nested error for the real cause.

**Action:** Look at the nested error to determine what action to take.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-00272: A HandlerChain can only contain Handler instances: {0}**

**Cause:** A non-handler instance was found in the handler chain.

**Action:** Remove the offending instance,

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00274: cannot create XSLT transformer for the WSDL**

**Cause:** Failed to create a XSLT Transformer object for presentation of WSDL.

**Action:** Check whether the web service endpoint is valid and the service is properly deployed.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00275: WSDL transformation failed**

**Cause:** XSLT Transformation failed when presenting WSDL.

**Action:** Check whether the web service endpoint is valid and the service is properly deployed.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00276: model error: {0}**

**Cause:** A nested model or modeler exception occurred, most likely caused by an invalid WSDL.

**Action:** Verify that the WSDL is a valid one.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00277: unsupported XML Schema feature ({0})**

**Cause:** An unsupported XML Schema feature was encountered during processing of WSDL schema.

**Action:** Remove the unsupported XML Schema feature from WSDL schema.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**OWS-00278: unsupported type ({0}): {2}:{1}**

**Cause:** An unsupported XML Schema type was encountered during processing of a WSDL schema element.

**Action:** Remove the unsupported type or change it to an equivalent supported type.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00279: unsupported type ({0}): {1}, caused by: {3}**

**Cause:** An unsupported XML Schema type was encountered during processing of a WSDL schema element. Error details are provided.

**Action:** Look at the error details for possible action to handle the unsupported type.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00280: unsupported anonymous type ({0}), caused by: {1}**

**Cause:** An unsupported XML Schema type was encountered during processing of an anonymous WSDL schema element. Error details are provided.

**Action:** Look at the error details for possible action to handle the unsupported type.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00281: invalid literal "{0}" in enumeration "{1}" (namespace: {2})**

**Cause:** An invalid literal value of an enumeration was encountered when processing a WSDL schema.

**Action:** Correct the offending literal value in the enumeration.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00282: uniqueness constraint violation: {0} "{1}" already exists.**

**Cause:** A component with the specified name occurs multiple times

**Action:** Check the validity of the WSDL or Java code for duplicate elements

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00283: The value type {0} can not be generated because two members result in the same name of {1}. A jaxrpc mapping file must be specified to resolve this naming conflict.**

**Cause:** There is a naming conflict - two members have the same name

---

**Action:** Use a JAX-RPC mapping file.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00285: parent of type "{0}" already set to "{1}", new value = "{2}"**

**Cause:** The specified type is duplicated within more than one parent type.

**Action:** Rewrite the type hierarchy, so that this type only occurs on one parent.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00286: parent of fault "{0}" already set to "{1}", new value = "{2}"**

**Cause:** The specified fault is duplicated as a sub-type of more than one parent.

**Action:** Ensure that the fault only occurs within a single parent.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00287: LiteralArrayWrapper element member already set.**

**Cause:** This element cannot be modeled as a LiteralArrayWrapper because it has more than one member

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00288: LiteralArrayWrapper cannot have a parent type**

**Cause:** This element cannot be modeled as a LiteralArrayWrapper because it has a parent type

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00289: LiteralArrayWrapper cannot have subtypes**

**Cause:** This element cannot be modeled as a LiteralArrayWrapper because it has a subtype

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00290: LiteralArrayWrapper cannot have a content member**

---

**Cause:** This element cannot be modeled as a LiteralArrayWrapper because it has a content member

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00293: class {0} not found.**

**Cause:** The specified Java class could not be loaded.

**Action:** The class must exist in the classpath when strictJAXRPCValidation is turned on.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00295: unexpected type: {0}**

**Cause:** An unexpected type was found during the processing of your action. In the case of top-down design the WSDL contains an unsupported or invalid type. In the case of bottom-up design, the particular class file is currently not supported.

**Action:** Top-down design pattern: Correct any problems within the WSDL file. If the WSDL is valid, then it contains types that are currently not supported.

Bottom-up design pattern: Correct any type issues within the Java class.

Otherwise, the class contains types that are currently not supported. You may want to consider using a different type.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00296: The following type is invalid because it implements java.rmi.Remote: {0}**

**Cause:** The serializable implementation class inappropriately implements java.rmi.Remote. This is not supported.

**Action:** Change the implementation class to not implement java.rmi.Remote.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00297: class {0} does not have a public accessible empty constructor**

**Cause:** The serializable implementation class does not provide a public accessible no-arg constructor.

**Action:** Provide a public no-arg constructor or provide a custom serializer.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**OWS-00299: class "{0}" cannot have a JavaBean property "{1}" and a public member of the same name.**

**Cause:** The implementation class cannot contain public members with the same name as JavaBean properties.

**Action:** Consider making the public member private or protected or renaming the property or JavaBean property.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00300: nested inner classes are not supported: {0}**

**Cause:** The implementation class contains a nested inner class, which is not supported.

**Action:** Consider refactoring the implementation class to remove the nested inner class. See the Oracle Application Server Web Services Developer's Guide.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00301: Duplicate type name "{0}" for Java type "{1}" found. To remove this error do not specify a single typeNamespace for all value types or specify a mapping file. This error could also be caused when a type name has been used more than once.**

**Cause:** The same type name has been used for multiple Java types. Probably related to inner classes. A possible explanation is the erroneous use of a given type name multiple times.

**Action:** Use separate namespaces for the value types or use a mapping file. See the Oracle Application Server Web Services Developer's Guide.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00302: Type "{0}" is used as a "{1}" and a "{2}"**

**Cause:** The same RMI Modeler type instance is used for two different XML types.

**Action:** Correct the XML type or the XML type hierarchy such that there is one Modeler per XML type, or have one type subclass the other type.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00303: Type "{0}" implements more than one interface: "{1}", "{2}" ...**

**Cause:** The implementation class may implement only a single interface (SEI).

**Action:** Consider refactoring the implementation class to implement a single interface.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**OWS-00304: Type {0} references an invalid type {1}, which is invalid for the following reason: {2}**

**Cause:** The indicated type has a reference to an invalid type.

**Action:** Consider modifying the implementation class to not reference the inappropriate type.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00305: Ignoring target namespace for schema: "{0}", WSDL target namespace is used for the value types in the same package as Service Endpoint: "{1}"**

**Cause:** The schema namespace is ignored and the WSDL target namespace will be used instead. This is because the namespace of the schema is different from the target namespace of the WSDL and the value types are in the same package as the Service Endpoint Interface (SEI).

**Action:** See error message.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-00306: The constructor for {0} has {1} arguments of type {2}; This ambiguity may result in unexpected behavior. Use a mapping file to guarantee correctness.**

**Cause:** Multiple arguments of the same type introduce ambiguity that is difficult to resolve. This may cause unexpected results.

**Action:** Consider using a JAX-RPC mapping file to eliminate the ambiguity.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-00307: Service-specific exception {0} is not allowed to extend {1}.**

**Cause:** Runtime exceptions other than SOAPFaultException are not allowed.

**Action:** Consider changing the exception to not be a runtime exception or make it a SOAPFaultException.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00308: Service-specific exception {0} is not allowed to implement {1}.**

**Cause:** Service exceptions must not implement the java.rmi.Remote interface.

**Action:** Consider changing the exception to not implement Remote.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00309: Found a suitable parameterized constructor for {0}.**

---

**Cause:** A constructor has been found that satisfies all of the member values and will be used in the creation of the fault.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**OWS-00310: Did not find a suitable parameterized constructor for {0}.**

**Cause:** A suitable constructor that satisfies all of the getter methods could not be found.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**OWS-00311: Found a default constructor and a setter for every member of {0}.**

**Cause:** The default constructor will be used in conjunction with the setter methods to satisfy all of the member variables.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**OWS-00312: Using the single java.lang.String parameter constructor for {0}.**

**Cause:** Assuming the message member is the single string argument constructor.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**OWS-00314: invalid operation: {0}**

**Cause:** Invalid WSDL operation due to incorrect parameter order.

**Action:** Correct the parameter order of the specified operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OWS-00315: invalid state while modeling operation: {0}**

**Cause:** System Internal Error

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses



---

**OWS-00316: result is "inout" parameter in operation: {0}**

**Cause:** In/out parameters are not allowed.

**Action:** Consider changing the implementation to return a value.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00317: "{0}" specified in the parameterOrder attribute of message "{1}" is not a valid part of the message.**

**Cause:** The specified parameter(s) in parameterOrder of portType operation is not a valid part of the message.

**Action:** Verify and correct the part name parameter specified in the WSDL portType: ensure that the operation parameterOrder is properly associated and used in the input and output message.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00318: one or more part names were omitted in the parameterOrder attribute of operation "{0}"**

**Cause:** A message part name was not specified in the WSDL portType operation parameterOrder.

**Action:** Verify that input and output message part name are properly specified in the WSDL portType operation parameterOrder.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00319: parameter "{0}" of operation "{1}" appears with different types in the input and output messages**

**Cause:** The parameter used in an operation appears with different types in the input and output message.

**Action:** Verify the type of the input and output message specified in the WSDL portType operation.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00320: missing header message definition for "{1}", referenced by the binding operation "{0}"**

**Cause:** The soap header message defined in the binding operation is not specified in the WSDL message definition.

**Action:** Verify the soap header message defined in the binding operation. Ensure that it is properly specified in the WSDL message definition.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**OWS-00321: missing operation "{0}" in port type, referenced by binding "{1}"**

**Cause:** The operation specified in binding does not appear in the corresponding port type.

**Action:** Verify the binding operation. Ensure that it is specified in the corresponding port type in the WSDL.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00322: input message of binding operation "{0}" does not have a SOAP body extension**

**Cause:** The input message of the binding operation does not have a SOAP body extension.

**Action:** Verify that the SOAP body extension 'soap:body' is properly specified in the input message of the binding operation in the WSDL.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00323: output message of binding operation "{0}" does not have a SOAP body extension**

**Cause:** The output message of a binding operation does not have a SOAP body extension.

**Action:** Verify that the SOAP body extension 'soap:body' is properly specified in the output message of the binding operation in the WSDL.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00324: input message of binding operation "{0}" must specify a value for the "namespace" attribute**

**Cause:** The soap request body of the input message of a binding operation must specify a value for the namespace attribute.

**Action:** Verify that the namespace attribute is properly specified in the soap request body of the input message of this binding operation in the WSDL.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00325: output message of binding operation "{0}" must specify a value for the "namespace" attribute**

**Cause:** The soap request body of the output message of a binding operation must specify a value for the namespace attribute.

**Action:** Verify that the namespace attribute is properly specified in the soap request body of the output message of this binding operation in the WSDL.

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00326: fault "{0}" in operation "{1}" matches more than one fault in the corresponding port type operation**

**Cause:** The fault in a binding operation matches more than one fault in the corresponding port type operation.

**Action:** Verify the exact correspondence between the fault name in the binding operation and in the port type operation of the WSDL.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00327: fault "{0}" in operation "{1}" does not match any fault in the corresponding port type operation**

**Cause:** The fault in a binding operation does not match any fault in the corresponding port type operation.

**Action:** Verify the the correspondence between the fault name in the binding operation and in the port type operation of the WSDL.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00328: fault "{0}" in operation "{1}" does not have a SOAP fault extension**

**Cause:** The fault in a binding operation does not have a SOAP fault extension.

**Action:** Verify that the SOAP fault extension 'soap:fault' is properly specified in this fault of the binding operation.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00329: fault "{0}" refers to message "{1}", but the message has no parts**

**Cause:** The fault refers to a message in definitions, but the message has no parts.

**Action:** Verify and ensure the fault message with properly specified part name in the WSDL.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00330: fault "{0}" refers to message "{1}", but the message has more than one parts**

**Cause:** The fault refers to a message in definitions, but the message has more than one parts.

**Action:** Verify and correct the fault message with properly and exactly specified part name in the WSDL.

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00331: in message "{0}", part "{1}" must specify a "type" attribute**

**Cause:** In this WSDL, there is part must specify a type attribute in message.

**Action:** Verify the message in WSDL to ensure some part which also need a type definitions.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00332: in message "{0}", part "{1}" must specify an "element" attribute**

**Cause:** In this WSDL, there is part in message must specify an element attribute.

**Action:** Verify the message in WSDL to ensure some part which also need an element definitions.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00334: the following naming conflicts occurred: {0}**

**Cause:** There are naming conflicts occurred in WSDL.

**Action:** Verify the naming in WSDL is properly and correctly without conflict.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00335: Unsupported DIME layout: {0}**

**Cause:** The DIME message layout specified in the operation is not supported.

**Action:** Verify and check the DIME layout specified. The supported layout are: closed-layout and open-layout.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00336: binding "{0}" uses both streaming attachments and mime-multipart**

**Cause:** There is binding which uses both streaming attachments and mime-multipart in WSDL.

**Action:** Verify and correct the WSDL binding to ensure not both streaming attachments and mime-multipart is used.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00337: binding "{0}" uses both streaming attachments and DIME**

---

**Cause:** There is binding which uses both streaming attachments and DIME message in WSDL.

**Action:** Verify and correct the WSDL binding to ensure not both streaming attachments and DIME is used.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00338: <portType> definition is not found in the WSDL**

**Cause:** There is no service and portType definition found in the WSDL.

**Action:** Verify and check the WSDL. Either service or portType has to be defined and specified.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00343: Service "{0}" does not contain any usable ports**

**Cause:** There is no port in the current WSDL that is suitable for JAXRPC based proxy generation.

**Action:** Correct the WSDL, based on the other error or warning provided, so that there is one port in the current WSDL suitable for JAXRPC based proxy generation.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-00346: ignoring port "{0}": no SOAP address specified**

**Cause:** The "service/port" element is missing a required child element for SOAP binding: "soap:address".

**Action:** Add the missing element in the original WSDL or using a local copy if you do not own the service endpoint.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-00356: binding "{0}" is ignored because it has an invalid attribute: transport="{1}"**

**Cause:** The value of the transport attribute on the soap:binding element is not recognized. The SOAP1.1 value is "http://schemas.xmlsoap.org/soap/http".

**Action:** Correct the value of the transport attribute in the original WSDL or use a local copy if you do not own the service endpoint.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-00357: ignoring document-style operation "{0}": parameters are not literal**

---

**Cause:** The value for the "use" attribute on document-style binding is invalid. the only value supported is "literal".

**Action:** Correct the original WSDL or use a local copy if you do not own the service endpoint.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-00358: ignoring operation "{0}": input message with multipart is not WS-I compliant and is not currently supported**

**Cause:** The wsdl:message referenced by the portType/operation/input element contains more than one part and doesnt comply with WS-I BP 1.1.

**Action:** If you have control over the WSDL, changes the message style for bare to wrapped, so that the WSDL comply with WS-I profile. Otherwise, use the SAAJ APIs to invoke the service without to use JAXRPC generated proxy.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-00359: ignoring operation "{0}": output message with multipart is not WS-I compliant and is not currently supported**

**Cause:** The wsdl:message referenced by the portType/operation/output element contains more than one part and doesnt comply with WS-I BP 1.1.

**Action:** If you have control over the WSDL, changes the message style for bare to wrapped, so that the WSDL comply with WS-I profile. Otherwise, use the SAAJ APIs to invoke the service without to use JAXRPC generated proxy.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-00360: The WSDL used has operations with literal and encoded use. -f:searchschema is not supported for this scenario.**

**Cause:** The WSDL has soapbinding subelements with use="literal" as well as use="encoded". Searching of Schema is not supported for this scenario.

**Action:** Modify the WSDL to have only use="literal" or use="encoded"

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00361: ignoring fault "{0}" of operation "{1}", part name "{2}" is not unique**

**Cause:** The WSDL uses the fault partname more than once.

**Action:** Update WSDL to specify unique fault part name.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

---

**OWS-00362: Notification operation "{0}" in binding "{1}" is not supported.**

**Cause:** Notification operations are not supported.

**Action:** Use a WSDL with no notification operations.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00363: Non conforming WSI WSDL used for wsdl:import**

**Cause:** WSDL import element doesnt comply with WS-I

**Action:** Update the WSDL so that the imports precede all other top level elements in the WSDL.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-00364: Non conforming WSI WSDL used for wsdl:types**

**Cause:** WSDL types element doesnt comply with WS-I

**Action:** Update the WSDL so that the wsdl:types elements appear immediately after the wsdl:imports or if no imports are present wsdl:types should be the first top level element.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-00365: parts "{0}" not found in the message "{1}", wrong WSDL**

**Cause:** The part defined in the input soap body of the binding is not specified in the input message of the operation in the port type. The part defined in the output soap body of the binding is not specified in the output message of the operation in the port type.

**Action:** Make sure all the parts that are defined in the input soap body of the binding are defined in the input message of the corresponding operation of the port type. make sure all the parts that are defined in the output soap body of the binding are defined in the output message of the corresponding operation of the port type.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00366: Custom mappings for rpc-encoded web service is not supported (operation = "{0}").**

**Cause:** the WSDL uses custom mappings and rpc encoded webservises.

**Action:** If WSDL has rpc encoded bindings do not specify custom serializers. "schema" argument to Web Services Assembler along with a message format of rpc encoded is not allowed. <type-mapping> in the oracle-webservices.xml is also not allowed with rpc encoded webservises.

**Level:** 1

---

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-00370: model is missing**

**Cause:** The system is missing a model.

**Action:** System Internal Error - Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00371: Ignoring Unique Schema Constraint**

**Cause:** The schema used by the WSDL has a unique constraint.

**Action:** Remove unique constraint

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-00372: The key element has not been implemented**

**Cause:** The WSDL uses the unsupported "key" schema element.

**Action:** Modify the schema to remove the key element

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00373: Model group definition has not been implemented**

**Cause:** The WSDL uses a schema with a model group definition

**Action:** Modify the schema to remove the model group definition

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00374: Substitution Group Attribute has not been implemented**

**Cause:** The WSDL references a schema that uses the substitutionGroup facility.

**Action:** Modify the schema to remove the substitutionGroup element

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00375: Block attribute has not been implemented**

**Cause:** The WSDL refers to a schema that uses an unsupported block attribute.

**Action:** Update your schema to set "" or #all as values for the block attribute. All other values are unsupported.

**Level:** 1

**Type:** ERROR



---

**Impact:** Requests/Responses

**OWS-00377: Base attribute must be specified in restriction tag.**

**Cause:** The base attribute is not specified in the restriction tag.

**Action:** Specify a base type from which the complex type is to be derived by restriction.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00378: Enumeration {0} is not supported**

**Cause:** The enumeration is not supported.

**Action:** Modify the schema to remove this enumeration.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00379: Attribute restriction is not supported**

**Cause:** The base type has an attribute element with the use="prohibited".

**Action:** Remove the use="prohibited" attribute on the base type.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00380: Group Schema Element has not been implemented**

**Cause:** The "group" schema element is not supported

**Action:** Modify the schema to remove the group element

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00381: Unsupported Schema Element**

**Cause:** Facets are not supported in the extension and restriction elements.

**Action:** Remove facets (elements like xsd:pattern, xsd:minInclusive etc which restrict values of an element) from your schema.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00382: Invalid value ({0}) for "minOccurs" attribute of element - {1}. Setting value to 0.**

**Cause:** Invalid "minOccurs" attribute value. Setting value to 0.

**Action:** Set minOccurs to 0 if the associating element is optional. Otherwise, set the value to 1 or more.

**Level:** 1

---

Type: WARNING

Impact: Requests/Responses

**OWS-00383: The "maxOccurs" attribute of the {0} element has an unsupported value of {1}. Currently only boundless arrays are supported. maxOccurs must be 0,1 or unbounded. Setting to default value of "unbounded".**

**Cause:** Invalid or unsupported "maxOccurs" attribute value. Setting value to 0.

**Action:** Set this value to a positive integer or unbounded to indicate there is no maximum number of occurrences.

Level: 1

Type: WARNING

Impact: Requests/Responses

**OWS-00384: Value ({0}) for "final" attribute of element -{1} is currently not supported. This attribute is ignored.**

**Cause:** Unsupported final attribute value. Ignore the attribute.

**Action:** Set this value to "#all" or ""

Level: 1

Type: WARNING

Impact: Requests/Responses

**OWS-00385: Processing {0} QNAME HINT: {1} Name: {2}**

**Cause:** Processing schema type.

**Action:** N/A

Level: 1

Type: NOTIFICATION

Impact: Requests/Responses

**OWS-00386: sender error: {0}**

**Cause:** Invalid configuration in oracle-webservices.xml or wsmgmt.xml.

**Action:** Verify the configuration setting in oracle-webservices.xml and/or wsmgmt.xml.

Level: 1

Type: ERROR

Impact: Requests/Responses

**OWS-00387: missing body information**

**Cause:** SOAP Body is missing in the request. The SOAP message was not sent.

**Action:** Verify request.getBody() returns a SOAP body instance.

Level: 1

Type: ERROR

Impact: Requests/Responses

**OWS-00388: illegal value of "mustUnderstand" attribute: "{0}"**

**Cause:** Response contains illegal value of "mustUnderstand" attribute.

---

**Action:** Verify the response SOAP message. Attribute "mustunderstand" must have a value of "0", "1", "true", or "false".

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00389: unrecognized operation (code: {0})**

**Cause:** The SOAP message is invalid. It cannot be resolved to an operation's request or response.

**Action:** Regenerate the stub using either Jdeveloper or the Web Service Assembler tool.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00390: unrecognized fault block**

**Cause:** The response fault is invalid.

**Action:** Verify the content of the fault response.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00391: received empty response**

**Cause:** No SOAP Message is returned from the server.

**Action:** Verify the corresponding WSDL operation is not oneWay.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00392: stub was not initialized**

**Cause:** The initialize() method of the stub was not invoked.

**Action:** Regenerate the stub using either JDeveloper or the Web Service Assembler tool. If problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00395: XML reader internal error: illegal state ({0})**

**Cause:** XMLReader encounters an XML element that cannot be deserialized.

**Action:** Validate the XML document.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00396: XML reader error: unexpected character content: "{0}"**

---

**Cause:** XMLReader encounters an element with an unexpected character content.

**Action:** Validate the XML document.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00397: XML reader error: {0}**

**Cause:** XMLReader cannot close the reading stream.

**Action:** Check network connection and file system connection.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00398: XML parsing error: {0}**

**Cause:** XMLReader cannot read the next element.

**Action:** Validate the XML document.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00400: XML writer error: no prefix for URI: "{0}"**

**Cause:** No prefix is specified for the URI.

**Action:** System Internal Error - Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00401: XML writer error: {0}**

**Cause:** XML Writer encounters an IOException.

**Action:** Check network connection and file system connection.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00403: unexpected XML reader state. expected: {0} but found: {1}**

**Cause:** The XML document does not have the expected start or end of an element.

**Action:** Check if any required element is missing or there are more elements where an end tag was expected.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00405: unrecognized operation: {0}**

---

**Cause:** The soap operation is not valid.

**Action:** Check the operation name in the message and correct it.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00406: cannot dispatch ambiguous operation: {0}**

**Cause:** The specified operation is overloaded.

**Action:** Remove the overloading by renaming one of the conflicting operations.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00407: unexpected header block: "{0}"**

**Cause:** The QName of the header block is not correct.

**Action:** Correct the header block by verifying its namespace.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00408: invalid SOAP envelope: body is empty**

**Cause:** The body of the soap message is empty.

**Action:** Provide the write content in the body element of the soap message.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00409: invalid SOAP envelope: body is missing**

**Cause:** The body element is either missing or its namespace is wrong.

**Action:** Add the body if missing or correct the namespace of the body element.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00410: env:Body must be present in a SOAP 1.2 envelope**

**Cause:** The body element is missing from the message. SOAP 1.2 requires that the env:Body element must be present.

**Action:** Add the soap body in the message.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00411: invalid SOAP envelope content**

**Cause:** The content of the soap envelope is invalid.

---

**Action:** Correct the content of the soap envelope.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00412: invalid SOAP envelope**

**Cause:** The root element of the message is not a soap envelope.

**Action:** Make the root element a valid soap envelope.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00413: SOAP envelope version mismatch**

**Cause:** The namespace or the version of the envelope is not correct.

**Action:** Correct the namespace of the soap envelope.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00414: Caught exception while handling request: {0}**

**Cause:** Refer to the details of the message for further information on possible causes.

**Action:** Refer to the details of the message for further information on possible actions.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00415: Caught exception while preparing response: {0}**

**Cause:** Refer to the details of the message for further information on possible causes.

**Action:** Refer to the details of the message for further information on possible actions.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00416: Caught exception while invoking the post handling hook: {0}**

**Cause:** Refer to the details of the message for further information on possible causes.

**Action:** Refer to the details of the message for further information on possible actions.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**OWS-00417: Internal Server Error ({0})**

**Cause:** Refer to the details of the message for further information on possible causes.

**Action:** Refer to the details of the message for further information on possible actions.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00418: Could not find the field in the Holder that contains the Holder value: {0}**

**Cause:** Refer to the details of the message for further information on possible causes.

**Action:** Refer to the details of the message for further information on possible actions.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00420: No jar file (or directory) found at specified path: {0}**

**Cause:** The specified jar file does not exist.

**Action:** Check if the jar file name is correct and it is in the right directory.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00422: Exception occurred while verifying EJB: Class: {0} Details: {1}**

**Cause:** Error while parsing ejb-jar.xml. Refer to the details of the message for further information on possible causes.

**Action:** Refer to the details of the message for further information on possible actions.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00423: The EJB {0} was not found in the specified ejb location**

**Cause:** The ejb-jar.xml does not contain the specified EJB.

**Action:** Check if the name of the EJB is correct and it is present in the ejb-jar.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00425: Unable to locate ejb-jar.xml in {0}**

---

**Cause:** The application does not contain an ejb-jar.xml deployment descriptor file. The deployment descriptor file is inspected to locate the endpoint service interface

**Action:** Add ejb-jar.xml and reassemble the application.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00426: Error parsing ejb-jar.xml. No session beans found.**

**Cause:** The application does not contain any session bean definition. The business functions to be exposed as webservices should be defined in a session bean.

**Action:** Write an Enterprise Java Session Bean that contains the business functions that you want to expose.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00427: Error parsing ejb-jar.xml. Stateful session beans are not supported.**

**Cause:** Creating webservices from a stateful session bean is not supported. The business functions to be exposed as webservices should be defined in a stateless session bean.

**Action:** Remove the stateful session bean, write a stateless session bean that contains the business functions that you want to expose.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00432: ERROR: {0}**

**Cause:** Server or client artifacts generation has failed.

**Action:** This is a generic error indicating an error condition. You should also see a message describing the details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00433: WARNING: {0}**

**Cause:** Server or client artifacts generation has encountered a possible error.

**Action:** This is a generic warning. You should also see a message describing the details.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-00434: INFO: {0}**

**Cause:** Oracle webservice compile tool generates this diagnostic information.

**Action:** This is used to indicate that the message follows is for informational purpose.



---

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**OWS-00440: all sources succesfully generated**

**Cause:** Oracle webservice compile tool has successfully generated all code artifacts.

**Action:** See error message.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**OWS-00442: Problem validating implementation class. {0}**

**Cause:** Supplied Service implementation class is not valid. It could be that the implementation class does not implement the interface correctly or it does not conform to JAXRPC requirements or the class is not found.

**Action:** Make sure the implementation class is JAXRPC compliant if it is a JAXRPC webservice; make sure the classpath containing the implementation class is correctly specified

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-00450: parsing failed: {0}**

**Cause:** SAXException is thrown from the parser while parsing the WSDL.

**Action:** Fix the WSDL according to the error reported by the parser.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00451: parsing failed: {0}**

**Cause:** ParserConfigurationException is thrown from the parser while parsing the WSDL.

**Action:** Unexpected internal error.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00460: Element type "{1}" is missing required attribute "{0}"**

**Cause:** The WSDL or Schema entity is missing the required attribute.

**Action:** Add the required attribute with a valid value to the WSDL or Schema entity.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**OWS-00461: Element named "{0}" of type "{2}" is missing required attribute "{1}"**

**Cause:** The WSDL or Schema entity is missing the required attribute.

**Action:** Add the required attribute with a valid value to the WSDL or Schema entity.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00463: missing required sub-entity "{0}" of element "{1}"**

**Cause:** A sub-element required by the schema or WSDL specification is missing.

**Action:** Modify the schema or WSDL to add the required sub-element.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00464: Could not find Attribute : "{0}"**

**Cause:** An attribute reference is not defined in the schema.

**Action:** Modify the schema to define the missing attribute reference.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00465: Unsupported schema feature : "{0}"**

**Cause:** An element defined in the schema is not supported by the system.

**Action:** Modify the schema.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00466: The element is not supported in this context : "{0}"**

**Cause:** A sub-element of the complex type extension/restriction definition in the schema is not supported by the system.

**Action:** Modify the complex type extension/restriction definition in the schema.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00467: Unsupported simple type definition : "{0}" inside "{1}" element**

**Cause:** A simple type defined in the schema is not supported by the system.

**Action:** Modify the simple type to a simple type supported by the system.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**OWS-00468: invalid sub-element "{0}" of element "{1}"**

**Cause:** The WSDL contains an element with a sub-element that is not supported by the system. Check WSDL 1.1 specification.

**Action:** Modify the invalid sub-element based on the WSDL 1.1 specification.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00469: invalid attribute "{0}" of element "{1}"**

**Cause:** The WSDL or schema contains an element with an attribute that is either formatted incorrectly or does not comply with the specifications support by the system. The specifications to check include SOAP, WSDL 1.1 and jaxrpc.

**Action:** See error message.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**OWS-00470: invalid value "{1}" for attribute "{0}"**

**Cause:** A attribute on a WSDL or schema element has a value that is not expected by the system.

**Action:** or WSDL to comply with the value for the schema type of the attribute or change the type of the attribute to a simple type like string or int.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00471: invalid range found (min: {0}, max: {1})**

**Cause:** A complex type in a schema defines min and max occurrence on a type that the system does not support.

**Action:** Change the max occurrences attribute to 1 so the system will except the schema.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00472: exclusive attributes: "{0}", "{1}"**

**Cause:** A complex type in a schema defines two attributes that are not supposed to be defined at the same time.

**Action:** Remove one of the specified attributes from the schema.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00474: not a simple type: "{0}"**

**Cause:** A schema type other than a simple type was found in a schema when a simple type is expected.

---

**Action:** Change the type specified in the error message to a simple schema type or change the reference to this type to a simple schema type.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00475: port type "{0}" in binding "{0}" not found.**

**Cause:** The specified WSDL is invalid or complete. A binding in a WSDL document has a reference to a portType that is not defined in the WSDL.

**Action:** Change the value of the type attribute in the binding to the name of a portType that is defined in the WSDL.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00476: message "{0}" not found.**

**Cause:** The specified WSDL is invalid or complete. An input, output or fault element has a value for the message attribute that is not defined in the WSDL.

**Action:** Change the value of the message attribute to a message that is defined in the WSDL.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00477: type "{0}" defined for the message part "{1}" could not found.**

**Cause:** The type definition is not found in the schema.

**Action:** Add the type definition to the schema, or change the value of the type attribute to the name of an existing schema type.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00478: element "{0}" defined for the message part "{1}" could not found.**

**Cause:** A schema contains a reference to an element name that does not exist in the specified set of schemas. The set of schemas can be inside of a WSDL document, imported from a WSDL document or imported from other schema documents.

**Action:** Change the reference to an element name that is found in the specified set of schemas, or define the type in the schema.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00480: Binding "{1}" used in port "{0}" not found.**

**Cause:** The specified WSDL is invalid or complete. A port in the WSDL document has a reference to a binding that is not defined in the WSDL.

---

**Action:** Change the value of the binding attribute in the port to the name of a binding that is defined in the WSDL, or define the binding.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00481: The name "{0}" is not a valid XML NCName. (see <http://www.w3.org/TR/1999/REC-xml-names-19990114/#NT-NCName>)**

**Cause:** The name is not a valid XML NCName.

**Action:** Correct the value of NCName. See <http://www.w3.org/TR/1999/REC-xml-names-19990114/#NT-NCName> for the format.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00482: The extensibility element "{0}" is unknown and has a wsdl:required attribute set to "true"**

**Cause:** During WSDL validation, found unrecognized extensibility element with wsdl:required attribute set.

**Action:** Ensure required extension registry is set with WSDLReader when reading WSDL document into WSDL definition or remove wsdl:required attribute

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00483: The WSDL contains a mixture of styles - "document" and "rpc". Only "rpc" OR "document" is supported in a WSDL, not both.**

**Cause:** WSDL contains a mixture of styles i.e both "Document" and "Rpc" style operation

**Action:** Multiple styles WSDL is not supported by JAXRPC/JAXWS. Make sure WSDL does not contain multiple styles i.e both document and rpc style binding operation.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00484: The WSDL contains a mixture of uses - "literal" and "encoded". Only "literal" OR "encoded" is supported in a WSDL, not both.**

**Cause:** WSDL contains both "literal" and "encoded" use

**Action:** Make sure WSDL does not contain mixture of uses - "literal" and "encoded". Only "literal" or "encoded" is supported in a WSDL, not both

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**OWS-00485: Operation "{0}" and "{1}" have conflicting SOAPAction values. Do not overload any operation or give unique SOAPAction value to each operation binding.**

**Cause:** Two or more operations specified in WSDL have conflicting SOAPAction values.

**Action:** Do not overload any operation or give unique SOAPAction value to each operation binding.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00486: Operation "{0}" does not have a SOAPAction value. Give it a unique value.**

**Cause:** In WSDL, overloaded operation does not contain SOAPAction value.

**Action:** Specify unique SOAPAction value for the overloaded operation.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00487: Element does not have name**

**Cause:** Element declared in schema does not have a "name" attribute set.

**Action:** Specify a name to an Element defined in a schema.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00488: Attribute group does not have name**

**Cause:** Attribute group does not contain any name.

**Action:** Specify a name to an attribute group.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00490: AttributeGroup "{0}" child missing ref attribute.**

**Cause:** Child element of Attribute group is missing "ref" attribute.

**Action:** Specify a name to a child element of Attribute group.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00491: Attribute declaration missing name.**

**Cause:** In schema, attribute declaration is missing name.

**Action:** Provide valide "name" to the attribute declaration.

**Level:** 1

---

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00492: AttributeGroup missing ref attribute**

**Cause:** During schema validation, found AttributeGroup element is missing "ref" attribute.

**Action:** Make sure AttributeGroup has "ref" attribute declared.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00494: The portType {0} is used by two bindings with different headers mapped to parameters. This usecase is not supported at this time. Map the same headers to parameters for all bindings using this port type.**

**Cause:** The portType defined in WSDL is used by two bindings with different headers mapped to parameters.

**Action:** Map the same headers to parameters for all bindings using this port type.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00495: The specified service name "{0}" was not found.**

**Cause:** In WSDL, service element does not have "name" attribute defined.

**Action:** Make sure WSDL has valid service name.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00496: Error while loading the schemas defined in WSDL "{0}": "{1}"**

**Cause:** Failed to load the schema specified in the WSDL.

**Action:** Ensure the schema location specified in the WSDL is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00499: LiteralArrayWrapper may only have one element member.**

**Cause:** LiteralArrayWrapper has more than one element member.

**Action:** Make sure LiteralArrayWrapper contains one element member.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00502: The annotations on the impl bean {0} or a referenced SEI are not consistent with the portType(s), binding(s) and service(s) in the WSDL specified by the wsdlLocation: {1}. Please refer to section 4.1.1 of the JSR-181 specification for details on the usage of wsdlLocation. The {2} was not found in the WSDL.**

---

**Cause:** The WSDL specified by a wsdlLocation attribute is inconsistent with the portType and bindings declared in the same WSDL.

**Action:** Ensure that the annotations are consistent with the WSDL. See section 4.1.1 of the JSR-181 spec.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**OWS-00505: Not a java bean**

**Cause:** The specified value type is not a valid Java Bean.

**Action:** Ensure that the all declared value types are valid Java Bean.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00506: Not a java bean. Class is not public.**

**Cause:** The specified class is not a valid Java Bean.

**Action:** Ensure the specified class has "public" modifier.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00526: Not in class path**

**Cause:** The specified class could not found in classpath.

**Action:** Ensure that all required classes or jar files containing classes are declared in classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00527: Element "{0}" can not have both a type attribute and a nested type declaration.**

**Cause:** The WSDL or schema contains an element with a type attribute and a nested type defined.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00528: Type "{0}" is not a valid JAXRPC value type or it is not serializable.**

**Cause:** SEI contains method with unserializable return type or parameter type

**Action:** Ensure that all parameter types and return type are valid value types as per JAXRPC specification.

**Level:** 1



---

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00529: Filenames "{0}" and "{1}" conflict in generated sdo type classes. Some files may be overwritten. This could happen if schemas use case-sensitive type declaration, but some file systems are case-insensitive.**

**Cause:** File names conflict.

**Action:** See error message.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**OWS-00530: WSDL is not WS-I BP compliant. Literal style WSDL at location "{0}" can not have soap encoded type.**

**Cause:** Invalid WSDL. Provided WSDL has both literal and soap encoding style.

**Action:** Make sure WSDL has either "literal" or "encoding" style, NOT both

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00531: Could not find schema from URL source, file source, classpath or application context at this location: "{0}"**

**Cause:** Could not locate the schema document from file, url, classpath or application context.

**Action:** Verify that the specified location of schema is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00532: Failed to retrieve policy**

**Cause:** Could not retrieve the policy from the Policy Accessor.

**Action:** System Internal Error - Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00533: Value {0} is not valid for {1}**

**Cause:** Invalid value encountered while deserializing a Java value from XML.

**Action:** Verify that XML datatype contains valid value as per the schema.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00534: The entity identified by systemid={2} and publicid={1} was resolved by {0}.**

**Cause:** An entity was resolved using a resolver, usually an XML catalog.

---

**Action:** See error message.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**OWS-00535: The entity identified by systemid={1} and publicid={0} could not be resolved.**

**Cause:** An entity could not be resolved. Usually occurs during an XML catalog lookup failure.

**Action:** See error message.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**OWS-00536: The output of a binding operation "{0}" is missing**

**Cause:** The output of a binding operation is missing.

**Action:** Verify that the output element is properly specified in the binding operation in the WSDL.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00537: The input element, under namespace of "http://schemas.xmlsoap.org/wsdl/", of the binding operation "{0}" is missing**

**Cause:** The input element, under namespace of "http://schemas.xmlsoap.org/wsdl/", of a binding operation is missing.

**Action:** Verify that the input element is properly specified in the binding operation in the WSDL.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00538: The value of the BindingType annotation "{0}" does not match the SOAP version "{1}" on the WSDL.**

**Cause:** The value of the BindingType annotation does not match the SOAP version on the WSDL.

**Action:** Verify the value of the BindingType annotation.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00539: The WebParam or WebResult annotation on method "{0}" does not match the WSDL or Schema; The "{1}" "{2}" element is missing.**

**Cause:** The WebParam or WebResult annotation does not exist, or does not match the WSDL/Schema.

**Action:** Verify the value of the WebParam or WebResult annotation.

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00542: Unable to initialize, missing WebServicesProcessor**

**Cause:** Unable to initialize interceptors due to missing WebService Processor

**Action:** System Internal Error - Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-00543: Unable to provision web service, cannot read WSDL. Error: {0}**

**Cause:** Could not read WSDL.

**Action:** Check the WSDL URL for correctness and try again or check the server logs for details.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**OWS-00549: The WSDL has overloaded operations "{0}".**

**Cause:** The WSDL has overloaded operations.

**Action:** Avoid using overloaded operations.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**OWS-00550: JDK1.5 enum is not supported "{0}".**

**Cause:** JDK1.5 enum is not supported

**Action:** Provide a custom seriallizer.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-03004: {0}**

**Cause:** An exception occurred while webservice management configuration.

**Action:** Verify that the oracle proprietary descriptor for configuration is valid xml file and confirms to the schema

"http://xmlns.oracle.com/oracleas/schema/11/oracle-webservices-client-11\_1.xsd"

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OWS-03009: Error reading client wsmgmt configuration {0}**

**Cause:** Unexpected error occurs while reading client configuration file

---

**Action:** NONE

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OWS-03010: Error creating default client wsmgmt configuration {0}**

**Cause:** Unexpected error occurred while creating default client side configuration file

**Action:** System Internal Error - Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OWS-03013: Error parsing client wsmgmt configuration file {0}**

**Cause:** Unexpected error occurred while parsing client webservice management configuration file

**Action:** Verify that client side configuration file is a valid xml file

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OWS-03014: Error loading policy access cache configuration {0}**

**Cause:** Policy access cache configuration file could not be loaded due to unexpected error

**Action:** System Internal Error - Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OWS-03015: Error accessing policy from cache {0}**

**Cause:** Accessing policy from cache is failed

**Action:** System Internal Error - Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OWS-03016: Error loading interceptor class {0}**

**Cause:** Failed to load the Inteceptor class

**Action:** Ensure all required webservices client side jar files available in classpath

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OWS-04011: Error in resolving the webservice endpoint: {0}**

**Cause:** Failed to determine the WebService Endpoint for the servlet

---

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-04026: An I/O error occurred for port: {0}: {1}.**

**Cause:** An unexpected IO error occurred while processing service request.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-04039: Error closing connection: {0}**

**Cause:** Failed to close the connection to specific database

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Network

**OWS-04045: Malformed Request Message: {0}**

**Cause:** Received malformed SOAP request message

**Action:** Ensure the correct SOAP message constructed at client side

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-04046: {0} {1}**

**Cause:** A server side fault occurred while handling the SOAP message

**Action:** Please see the exception or server side log for more detail

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-04061: Internal JMX error {0}**

**Cause:** Internal error while configuring JMX

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OWS-04062: XML parser configuration error {0}**

**Cause:** An unexpected error occurred while parsing configuring the XML parser

**Action:** None

---

**Level: 1**  
**Type: ERROR**  
**Impact: Configuration**

**OWS-04065: Error creating default port configuration for interceptor {0}**  
**Cause:** The default port configuration for interceptor could not be created  
**Action:** None

**Level: 1**  
**Type: ERROR**  
**Impact: Configuration**

**OWS-04066: Missing port info for service.**  
**Cause:** The Port information for the service is missing  
**Action:** Add the necessary port information while configuring dynamic service.

**Level: 1**  
**Type: ERROR**  
**Impact: Configuration**

**OWS-04067: Error reading config file {0}**  
**Cause:** Failed to read the interceptor configuration file  
**Action:** None

**Level: 1**  
**Type: ERROR**  
**Impact: Configuration**

**OWS-04068: Error serializing default config {0}**  
**Cause:** Failed to serialize the default configuration for interceptor.  
**Action:** None

**Level: 1**  
**Type: ERROR**  
**Impact: Configuration**

**OWS-04069: Error serializing global configuration for {0} interceptor {1}**  
**Cause:** Failed to serialize global configuration for interceptor.  
**Action:** None

**Level: 1**  
**Type: ERROR**  
**Impact: Configuration**

**OWS-04070: Error serializing configuration {0}**  
**Cause:** Failed to serialize the configuration  
**Action:** None

**Level: 1**  
**Type: ERROR**

---

**Impact:** Configuration

**OWS-04072: Error writing config file {0}**

**Cause:** Error writing the configuration file for interceptor to FileManager

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OWS-04086: {0}**

**Cause:** An unexpected error occurred

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OWS-04097: Error creating client default port configuration for interceptor {0}**

**Cause:** Failed to create client default port configuration for interceptor

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OWS-04105: The final WSDL path "{0}" cannot be parsed as a URL: {1}**

**Cause:** The URL path for the final WSDL is not valid

**Action:** Provide the valid URL location for the WSDL.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OWS-04106: The value of the element named "{0}" ({1}) in {2} is invalid. Please refer to the XML schema of this descriptor for acceptable values.**

**Cause:** Found invalid value of an element declared in webservice deployment descriptor

**Action:** Please refer to the XML schema of this descriptor for acceptable values for this element.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OWS-04108: An error was encountered while trying to write the runtime configuration for the web service endpoint named "{0}": {1}**

**Cause:** An error was encountered while trying to write the runtime configuration for the web service endpoint.

**Action:** None

---

**Level:** 1

**Type:** ERROR

**Impact:** Files

**OWS-04110: Error downloading import: Invalid URL**

**Cause:** The specified URL for the imported WSDL is invalid

**Action:** Provide the correct URL location for the WSDL import

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OWS-04112: The policy accessor configuration could not be loaded from {0}: {1}.  
Using default configuration instead.**

**Cause:** Failed to load policy accessor configuration

**Action:** No action required as incase of this, default policy accessor configuration will be used

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**OWS-04113: Policy advertisement failed for {0}: {1}**

**Cause:** Failed to advertise the policy in the WSDL

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-04115: An error occurred for port: {0}: {1}.**

**Cause:** A server side exception occurred while processing request or creating the response message

**Action:** Please see the server side log for the detail.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-04117: {0}**

**Cause:** Exception occurred while configuring dynamic provider based endpoint

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-04121: Invalid use of <web-site> element in  
oracle-webservices.xml.<web-site> element must have two attributes "host" and  
"port" with valid values**



---

**Cause:** <web-site> element of oracle-webservice.xml doesn't contain 'host' and 'port' attributes with valid values

**Action:** Add valid 'host' and 'port' attributes to the <web-site> element, or remove the element.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OWS-04124: Failed to register the web service Config MBeans for application: {0} endpoint: {1} the error is: {2}**

**Cause:** Failed to register the web service config MBeans for endpoint

**Action:** None

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**OWS-04125: cannot find WSDL definition required to validate input**

**Cause:** cannot load web service WSDL definition, which is required for schema validation of input

**Action:** Ensure that the WSDL is available, or set schema validation of input to false

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**OWS-04126: Input Violates Schema**

**Cause:** SOAP body element of the input message cannot be validated against schema in the WSDL

**Action:** Correct input message body, input message type in the WSDL schema, or set schema validation of input to false

**Level:** 1

**Type:** ERROR

**Impact:** Data

**OWS-04127: Invalid query string**

**Cause:** User has specified invalid URL Query String.

**Action:** Verify that the correct query string is specified for accessing the testpage.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OWS-04128: Failed to deploy/initialize the application as given archive is missing required standard webservice deployment descriptor.**

**Cause:** The user supplied war archive is missing required webservice deployment descriptor

---

**Action:** Create WAR file with required webservice deployment descriptor or use WSA's `jaxwsAssemble` command to assemble the WAR file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OWS-04129: Failed to unregister mbean : "{0}". This may later cause error to register mbean with that name.**

**Cause:** JMX Framework failed to unregister pre-existing MBean.

**Action:** See error message.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Deployment

**OWS-04130: Failed to initialize Tie class "{0}" at runtime due to Error: {1}**

**Cause:** Failed to initialize the tie class on server side due to classloading issue or java security.

**Action:** Please look the server log for exact cause of an error.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-12003: Unknown SOAP Implementation**

**Cause:** The SOAP Implementation was not for either 1.1 or 1.2

**Action:** Internal Error

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-12004: Not implemented**

**Cause:** This functionality is not implemented

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-12022: DTD is not supported by SOAP 1.2**

**Cause:** SOAP 1.2 Message contains reference to DTD

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-12034: Operation not supported**

**Cause:** This functionality is not supported for this object

---

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-12044: Unsupported protocol: {0}**

**Cause:** The specified protocol is not supported

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-12047: Root element must be: "Envelope"**

**Cause:** Invalid SOAP message - does not have root element of <Envelope>

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-12048: Envelope namespace must be: {0} is {1}**

**Cause:** Invalid SOAP message - incorrect namespace for <Envelope> element

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-12049: DTD is not supported by SOAP**

**Cause:** SOAP Message contains reference to DTD

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-12050: SOAP Version {0} is not supported**

**Cause:** The SOAP Version was not either 1.1 or 1.2

**Action:** Please use a supported SOAP Version

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-12051: Can not have a DTD declaration in SOAP envelope**

**Cause:** SOAP Message contains DTD declaration

**Action:** None

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-12052: Can not have a processing instruction in SOAP envelope**

**Cause:** SOAP Message contains processing instruction

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-12059: Illegal Operation**

**Cause:** This operation is not allowed on this object

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-12061: Not implemented for comments**

**Cause:** This functionality is not implemented for comments

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-12138: Envelope size exceeds limit**

**Cause:** The size of the SOAP envelope exceeds the limit, which was configured for this port.

**Action:** Reduce the size of SOAP envelope or increase the set limit.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-12139: Envelope nesting depth exceeds limit**

**Cause:** The depth of nesting XML elements in the SOAP body exceeds the limit, which was configured for this port.

**Action:** Reduce the nesting in the SOAP body or increase the set limit.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-12140: Error building Mime body part**

**Cause:** The current part of the MIME Multipart is syntactically invalid

**Action:** Check that headers for all parts are legitimate names and syntactically correct

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-12141: Failed to match initial boundary**

**Cause:** The MIME Multipart boundary delimiter characters '--' are missing

**Action:** Check that the sender is creating a MIME Multipart message as required

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-12142: Failed to match initial boundary**

**Cause:** The current part of the Multipart is missing the required CRLF after the boundary

**Action:** Check that the sender is creating a well-formed MIME Multipart message

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-12143: Expected boundary delimiter**

**Cause:** The MIME Multipart boundary was not found in between parts

**Action:** Check that the sender is creating a well-formed MIME Multipart message

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-12144: File has already been opened in streaming mode**

**Cause:** An attempt was made to open an attachment for streaming more than once

**Action:** Do not use streaming attachments if a part must be opened more than once

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-12145: Output stream not available for streaming**

**Cause:** An attempt was made to open a streaming attachment for writing

**Action:** Check if the code is requesting an OutputStream instead of an InputStream

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-12146: Error parsing content type: {0}**

**Cause:** The HTTP Content-Type header is syntactically invalid

---

**Action:** Check that the sender is creating a valid MIME Multipart message as required

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-12147: MIME 'boundary' parameter not found in Content-Type**

**Cause:** The HTTP Content-Type header is missing the required 'boundary' parameter

**Action:** Check that the sender is creating a valid MIME Multipart message as required

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-12148: Cannot find start part {0}**

**Cause:** The 'start' part of the MIME Multipart message cannot be determined

**Action:** Ensure that the Content-Type has a 'start' parameter or that the message has at least one part

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-15001: An extension registry was not found for the element type "{0}"**

**Cause:** An extension registry was not found for an element type

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-15002: A failure occurred in loading WSDL from "{0}"**

**Cause:** A failure occurred in loading WSDL

**Action:** Verify if the WSDL exists at the specified URL

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-15004: WSDL contains an operation type of "{0}" which is not supported for port type "{1}"**

**Cause:** WSDL contains an operation type that is not supported

**Action:** Modify the WSDL and change the operation type to a supported one

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**OWS-15005: An error occurred when invoking the method. Type of WSIF invocation was "{1}" and method name was ("{0}")**

**Cause:** An error occurred when invoking the method

**Action:** Check client code and network connection

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-15010: Exception thrown while processing asynchronous response - "{0}"**

**Cause:** Exception thrown while processing asynchronous response

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50004: The method "{0}" does not have the AsyncHandler type parameter.**

**Cause:** The callback type asynchronous method that returns `java.util.concurrent.Future` must have the last parameter of the type `AsyncHandler`.

**Action:** Add the last parameter of type `AsyncHandler` in the method, or regenerate the interface using `wsa` tool.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50005: Exception while retrieving the soap message from the internal callback handler.**

**Cause:** Refer to the details of the message for further information on possible causes.

**Action:** Refer to the details of the message for further information on possible actions.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50006: Could not deserialize the soap message to get the return value**

**Cause:** Refer to the details of the message for further information on possible causes.

**Action:** Refer to the details of the message for further information on possible actions.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50007: Could not create the instance of asynchronous response bean of type "{0}"**

---

**Cause:** Could not create the response. Refer to the details of the message for further information on possible causes.

**Action:** Check if the bean has a default constructor and the constructor is accessible.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50008: Could not set the field "{0}" in the object of type "{1}".**

**Cause:** Possible causes are invalid field name, absence of setter, inaccessible setter or mismatched field type.

**Action:** Correct the bean class based on the details of the message.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50009: The method "{0}" must have a parameterized return type.**

**Cause:** The return type must be parameterized with the ResponseBean or the actual return type of the web service call.

**Action:** Add the appropriate return type as the parameter of the AsyncHandler parameter. Or use the JAX-WS artifacts generation tools to generate the proper interface of asynchronous methods.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50010: The method "{0}" must have a parameterized AsyncHandler parameter.**

**Cause:** The AsyncHandler parameter must be parameterized with the ResponseBean or the actual return type of the web service call.

**Action:** Add the appropriate return type as the parameter of the Response. Or use the JAX-WS artifacts generation tools to generate the proper interface of asynchronous methods.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50011: Dispatch currently does not support REST style service.**

**Cause:** The REST request cannot be processed via Dispatch. The feature is not yet supported.

**Action:** Construct an HTTP Request for a RESTful webservice.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50012: Could not determine the soap version from the BindingType annotation's value "{0}". Assuming SOAP version as 1.1**



---

**Cause:** The value of the BindingType annotation is invalid.

**Action:** Use one of the valid values for the BindingType annotation. Refer to the documentation of javax.xml.ws.BindingType.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-50013: Could not determine a valid protocol binding to generate for the binding string {0}. A SOAP 1.1 binding will be the only protocol binding generated in the WSDL.**

**Cause:** The value of the BindingType is not supported or is invalid

**Action:** Only SOAP and HTTP protocols are supported. Refer to the documentation or JAX-WS specification for valid values for javax.xml.ws.BindingType.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-50014: Both @Deployment.restSupport() and @BindingType(javax.xml.ws.http.HTTPBinding.HTTP\_BINDING) were specified. Only the latter will be used.**

**Cause:** Both the @Deployment.restSupport() and @BindingType(javax.xml.ws.http.HTTPBinding.HTTP\_BINDING) were provided.

**Action:** @Deployment.restSupport() has been deprecated. It should not be used. Use @BindingType(javax.xml.ws.http.HTTPBinding.HTTP\_BINDING) instead.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-50015: The given ws-addressing namespace "{0}" is not one of the supported wsa versions.**

**Cause:** The input ws addressing version is not supported

**Action:** Correct the addressing version to use 2003/03 or 2004/08 or 2005/08.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-50016: IOException converting AddressingInfo to String.**

**Cause:** IO error converting addressing info to String

**Action:** correctAddressingInfo

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50017: Port Metadata missing from the given callback interface class.**

---

**Cause:** Metadata such as port name or targetnamespace can not be found from the given input class.

**Action:** Add the needed annotation to the interface class.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50018: The file "{0}" does not exist.**

**Cause:** The file name specified in syncInterfaceFileName could not be opened.

**Action:** Check if the file name is correct and it exist.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50019: The file "{0}" should have some class or interface defined.**

**Cause:** The syncInterfaceFileName is not containing any class.

**Action:** Check if the file has any class defined. Make sure that the file is compilable and so free of errors.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50020: There is no method in the file "{0}" to convert to asynchronous method.**

**Cause:** The interface file should have at least one method defined.

**Action:** Add the required methods in the interface file.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50021: Cannot determine what methods to convert to asynchronous in file "{0}".**

**Cause:** The interface file has more than one method defined and no method name has been specified for conversion.

**Action:** Please sepcify what methods need to be converted to asynchronous methods.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50022: The file "{0}" does not exist.**

**Cause:** The file name specified in asyncInterfaceFileName could not be opened.

**Action:** Check if the file name is correct and it exist.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**OWS-50023: The file "{0}" should have some class or interface defined.**

**Cause:** The asyncInterfaceFileName is not containing any class.

**Action:** Check if the file has any class defined. Make sure that the file is compilable and so free of errors.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50024: Java Model is not set in the file system.**

**Cause:** The file system does not have any Java Model set.

**Action:** Make sure that the file system has the Java Model set.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50025: JAX-WS endpoint bean has @SOAPBinding.use annotation that specifies the 'encoded' message format which is not supported in JAX-WS. JAX-WS 2.0 mandates 'literal' use only and supports either rpc/literal or document/literal style binding.**

**Cause:** In JAX-WS endpoint bean, @SOAPBinding.use annotation has 'encoded' value which is not supported in JAXWS

**Action:** In JAX-WS endpoint bean, use either rpc/literal or document/literal style binding.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50026: Invalid use of @WebMethod annotation on method "{0}".As per JSR-181, if 'exclude' element is specified on @WebMethod annotation then other elements must not be specified with it.**

**Cause:** In JAX-WS endpoint bean, @WebMethod annotation has 'exclude' element that is used with other elements like 'action' or 'operationName' which is against the JSR-181 spec

**Action:** Do not use 'action' or 'operationName' element if 'exclude' element is specified on @WebMethod annotation.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50027: @SOAPBinding annotation is only allowed on a method if SOAPBinding.style is "DOCUMENT". Method "{0}" specifies @SOAPBinding.style to "RPC" which is against JSR-181 so it will be ignored and default sytle "DOCUMENT/LITERAL" will be used.**

**Cause:** @SOAPBinding annotation at method level has 'rpc' style which is not valid as per JSR-181

---

**Action:** Do not specify the 'rpc' style with @SOAPBinding annotation used at method level in JAX-WS endpoint interface/bean.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50028: The parameter/return type "{0}" in the method "{1}" is not supported. This method will not be exposed.**

**Cause:** The parameter/return type is NOT supported.

**Action:** Do not use the unsupported JAVA Type in method parameter or return value.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-50029: The method "{0}" has more than one input parameter that is not mapped to a header and style is BARE. This method will not be exposed.**

**Cause:** The java method has more than one input parameter that is not mapped to a header.

**Action:** Map java parameters to a header using @WebParam annotation or use wrapped style operation.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-50030: wsdlDocumentLocation is currently not supported.**

**Cause:** WSDLDocumentLocation is currently not supported

**Action:** See error message.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-50031: Input address, serviceName and endpointName can not be all null**

**Cause:** ServiceName, PortName, or Address can not be all null.

**Action:** Supply a non null argument for one of the parameters.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50032: Service name has not been specified for a non null port name.**

**Cause:** ServiceName can not be null when port name is specified.

**Action:** Supply a non null service name.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**OWS-50033: Exception occurred building W3CEndpointReference.**

**Cause:** Exception occurred when building W3C EndpointReference.

**Action:** Verify that the Endpoint Reference address and other metadata to build W3C EndpointReference are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50034: The method "{0}" is ignored. {1}**

**Cause:** The JAVA method is ignored in WSDL generation.

**Action:** See error message.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-50035: "{0}" cannot be used as parameter type or return value in "{1}".**

**Cause:** The JAVA type cannot be used as parameter type or return value in RPC-Literal and Document-Literal-BARE.

**Action:** See error message.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-50036: Operations on portType should be unique, use**

**@WebMethod(operationName="...") on java method "{0}" to resolve conflict.**

**Cause:** Operations the WSDL port type need to be unique.

**Action:** Map non-unique JAVA method names to unique WSDL operation names using @WebParam(operation="...")

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50037: Failed to load endpoint interface class "{0}" specified with**

**@WebService.endpointInterface annotation in endpoint bean class "{1}". This may cause unexpected behavior like generated WSDL would be different from the expected one.**

**Cause:** Classloader failed to load the endpoint interface class that is implemented by the endpoint bean class

**Action:** Check that the endpoint interface class is in the classpath

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50038: Found "{0}" annotation on class "{1}" which is not allowed with PortableWebService endpoint class.**

---

**Cause:** User has specified the annotation on either webservice endpoint interface or implementation class which is not allowed with Portable WebService

**Action:** Remove annotation which is not valid with @PortableWebService annotation.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50039: Could not load callback interface "{0}". Any methods defined in the interface will be ignored**

**Cause:** Callback interface class is not available or misspelt.

**Action:** Make callback interface available.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-50040: Failed while accessing Keystore details.**

**Cause:** Keystore details are not setup.

**Action:** Configure keystore details for the server.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50042: [MessageID: {0}] Could not complete asynchronous request processing successfully. No response will be sent to the client. Analyze the details of the exception as it is most likely the server side configuration error.**

**Cause:** Asynchronous request processing resulted in exception

**Action:** Analyze the exception and take appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50043: JMS queue connection failed.**

**Cause:** JMS queues are not created, or wrong queue names are used.

**Action:** Check that queues are created and referenced with the right names.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50044: [MessageID: {0}] Could not send async request message to the JMS queue.**

**Cause:** JMS queues are not created, or wrong queue names are used.

**Action:** Check that queues are created and referenced with the right names

**Level:** 1

---

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50045: Could not close the connection to JMS queue**

**Cause:** Internal error.

**Action:** Can be ignored.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50047: [MessageID: {0}] No JMS queue specified for the request with non-anonymous replyTo for service "{1}"**

**Cause:** JMS queues are not created, or wrong queue names are used.

**Action:** Check that queues are created and referenced with the right names

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50048: ConnectionFactory for the destination "{0}" used for asynchronous service processing is not specified. Using default: "{1}"**

**Cause:** Connection factory is not specified.

**Action:** Specify connection factory if default is not good.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-50051: JMS queue for async service processing not found. Configure a JMS queue for this application.**

**Cause:** JMS queue are either not created or misspelt in the annotations.

**Action:** Verify that the JMS queues are created and the same are referred in the annotations in the service implementation class.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50056: Received a fault and user did not supply a fault listener. Details: "{0}"**

**Cause:** The web service implementation class does not have any methods annotated as FaultListener and either the input is fault, or the response from the callback service is fault.

**Action:** Add the fault listener method if desired.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-50057: Failed while re-creating the soap message from the JMS message**

**Cause:** System error

---

**Action:** Analyze the exception reported in the log.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50058: Failed while re-creating the addressing header from the JMS message**

**Cause:** System error

**Action:** Analyze the exception reported in the log.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50059: [MessageID: {0}] Error while processing the message off the JMS queue.**

**Cause:** System error

**Action:** Analyze the exception details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50060: [MessageID: {0}] Request processor MDB failed.**

**Cause:** Asynchronous request processing MDB has failed.

**Action:** Analyze the exception details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50061: Context is available locally. Should happen only while running in-process message listener.**

**Cause:** Internal system error.

**Action:** Internal system error.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-50062: [MessageID: {0}] Error while processing response. Will try the fault handler in web service implementation class.**

**Cause:** Callback service may be down or policy of the callback service is not matching with the callback client.

**Action:** Analyze the exception details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50064: [MessageID: {0}] Failed to send the response to the callback service.**



---

**Cause:** Callback service may be down, the callback URL may be wrong or callback service is not configured properly.

**Action:** Verify the configuration of callback service and take action based on the details of exception.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50066: Could not save the context for async service in JNDI with the key "{0}".**

**Cause:** Internal system error.

**Action:** Internal system error.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50067: Could not cleanup the context for async service in JNDI as it was not found.**

**Cause:** Internal system error.

**Action:** Internal system error.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-50069: Could not remove the saved context for async service in JNDI with the key "{0}".**

**Cause:** Internal system error

**Action:** Internal system error.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-50071: [MessageID: {0}] Error while trying the fault handler in web service implementation class.**

**Cause:** The fault handler method did not execute successfully.

**Action:** Check the fault handler code.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50072: [MessageID: {0}] Got SOAPFaultException while executing the asynchronous operation**

**Cause:** This might be because of invalid request, missing resources in the service implementation or a bug.

**Action:** Analyze the exception details.

**Level:** 1

---

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50073: [MessageID: {0}] Got Exception while executing the asynchronous operation.**

**Cause:** This might be because of invalid request, missing resources in the service implementation or a bug.

**Action:** Analyze the exception details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50080: [MessageID: {0}] Completed asynchronous response processing with exception. Client will not receive any response.**

**Cause:** Callback service is not up or it's configuration/policy is not matching with the async server.

**Action:** Analyze the exception and configure the callback service.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50081: [MessageID: {0}] Response processor MDB failed.**

**Cause:** Callback service is not up or it's configuration/policy is not matching with the async server.

**Action:** Analyze the exception and configure the callback service.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50082: [MessageID: {0}] Sending response will not be retried as callback service sent soap fault back. Http response code was "{1}".**

**Cause:** Callback service sent the fault back. Retrying may not help. There may be some configuration problem,

**Action:** Analyze the fault and configure the callback service properly.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50085: [MessageID: {0}] Could not create the user transaction for request processing.**

**Cause:** Internal system error.

**Action:** Analyze the exception in the log.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**OWS-50087: [MessageID: {0}] Could not begin the user transaction for request processing.**

**Cause:** Internal system error.

**Action:** Analyze the exception in the log.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50088: [MessageID: {0}] Could not create user transaction for Web Method execution.**

**Cause:** Internal system error.

**Action:** Analyze the exception in the log.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50090: [MessageID: {0}] Could not begin user transaction for Web Method execution.**

**Cause:** Internal system error

**Action:** Analyze the exception in the log.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50092: [MessageID: {0}] Could not suspend the main transaction for executing the web method.**

**Cause:** Internal system error.

**Action:** Internal system error.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50093: [MessageID: {0}] User transaction was marked for rollback after executing the web method.**

**Cause:** Web method execution marked the transaction for rollback.

**Action:** It might be because of invalid input or a bug in the web method. Analyze the failure.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50094: [MessageID: {0}] Could not rollback the user transaction after executing the web method.**

**Cause:** Internal system error.

**Action:** Analyze the exception in the log.

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50095: [MessageID: {0}] User transaction is being rolledback after getting unexpected exception in executing the web method.**

**Cause:** Web method did not complete successfully.

**Action:** It might be because of invalid input or a bug in the web method. Analyze the failure.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50096: [MessageID: {0}] User transaction is being rolledback after getting failure in getting response.**

**Cause:** There might be some problem with the callback service or its configuration.

**Action:** Check if the callback service is up and configured properly.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50100: [MessageID: {0}] Could not get the transaction manager (javax.transaction.TransactionManager).**

**Cause:** Internal system error.

**Action:** Internal system error.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50102: [MessageID: {0}] Could not resume the suspended main transaction.**

**Cause:** Internal system error

**Action:** Internal system error.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50103: [MessageID: {0}] Rolled back a user transaction after executing the web method.**

**Cause:** There might be some problem with the callback service or its configuration.

**Action:** Check if the callback service is up and configured properly.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**OWS-50104: [MessageID: {0}] Could not rollback a user transaction after executing the web method.**

**Cause:** Internal system error.

**Action:** Internal system error.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50106: [MessageID: {0}] Could not commit the user transaction for web method execution.**

**Cause:** Internal system error.

**Action:** Analyze the related exception report in the log.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50107: [MessageID: {0}] Could not rollback the main transaction**

**Cause:** Internal system error.

**Action:** Internal system error.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50108: [MessageID: {0}] Could not commit the main transaction**

**Cause:** Internal system error.

**Action:** Internal system error.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50109: [MessageID: {0}] Http response from the Callback service is "{1}".**

**Cause:** Callback service returned http response other 200 or 202.

**Action:** Analyze the details of soap message returned by call service or the http error code.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50111: [MessageID: {0}] Received soap fault from the callback.**

**Cause:** Callback has sent a soap fault as the response.

**Action:** Analyze the fault and configure the callback service properly.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**OWS-50112: [MessageID: {0}] Could not dump the soap message**

**Cause:** Internal system error.

**Action:** Internal system error.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50113: [MessageID: {0}] Could not create SSLSocketFactory.**

**Cause:** Keystore may not have been configured properly.

**Action:** Configure the keystore details for the server.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50114: [MessageID: {0}] KeyStore file locations are not available. Configure it for the server to make the SSL work.**

**Cause:** Keystore may not have been configured properly.

**Action:** Configure the keystore details for the server.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50115: Exception in handler chain**

**Cause:** Handler chain has thrown some exception

**Action:** Look at the details of exception.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50130: No web module with name of "{0}" so a new war will be created**

**Cause:** TBD

**Action:** TBD

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50131: Found web module with name of "{0}", so the generated contents will be merged.**

**Cause:** TBD

**Action:** TBD

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**OWS-50132: Can not specify war argument and have an input be an ear that contains a war with a matching context root.**

**Cause:** TBD

**Action:** TBD

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50133: Error extracting war "{0}".**

**Cause:** TBD

**Action:** TBD

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50135: Could not load jaxrpc annotation parser, the webservises in this ejb will not be manageable**

**Cause:** TBD

**Action:** TBD

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50138: Could not write operation metadata for "{0}".**

**Cause:** Exception in writing operation metadata

**Action:** Analyze the exception.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50139: HandlerChain configuration file: "{0}".**

**Cause:** TBD

**Action:** TBD

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50140: Failed to resolve HandlerChain annotation "file" value ({0}) as it is specified on "{1}"**

**Cause:** TBD

**Action:** TBD

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**OWS-50141: Fabric Registration ignored because this service does not use SDO binding.**

**Cause:** TBD

**Action:** TBD

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50147: SDO Type Registration failed due to exception: "{0}".**

**Cause:** TBD

**Action:** TBD

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50159: [MessageID: {0}] Messages could not be read while cleaning up the asynchronous message queues. Exception: "{1}".**

**Cause:** System error

**Action:** Internal error

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50162: [MessageID: {0}] Request message was found in the queue while processing the response**

**Cause:** There might be a server/jvm crash after successful execution of business logic.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-50163: [MessageID: {0}] Response is not available. The web method execution did not complete or the response was lost.**

**Cause:** Response is not available. The web method execution did not complete or the response was lost.

**Action:** Retry calling the method if it is safe to do so.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50177: Could not read the context for async service from JNDI with the key "{0}".**

**Cause:** Internal system error.

**Action:** Internal system error.



---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-50178: The password for the identity keystore could not be read from the security credential store while sending the response to the callback service. It should have been stored as key "{0}" in the map "{1}". Assuming no password is necessary.**

**Cause:** The password for the identity keystore is probably not saved in the security credentials or, the map or the key name may be wrong.

**Action:** Save the password with appropriate key and the map as specified in the error.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-50179: The password for recovering the key could not be read from the security credential store while sending the response to the callback service. It should have been stored as key "{0}" in the map "{1}". Assuming key password to be same as the identity keystore password.**

**Cause:** The password for the private key is probably not saved in the security credentials or, the map or the key name may be wrong.

**Action:** Save the password with appropriate key and the map as specified in the error.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-50180: The password for the trust keystore could not be read from the security credential store while sending the response to the callback service. It should have been stored as key "{0}" in the map "{1}". Assuming no password is necessary.**

**Cause:** The password for the trust keystore is probably not saved in the security credentials or, the map or the key name may be wrong.

**Action:** Save the password with appropriate key and the map as specified in the error.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**OWS-50181: Exception while accessing the password from the security credential store for using SSL while sending the response to the callback service.**

**Cause:** Internal system error.

**Action:** Analyze the details of the exception

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

- 
- OWS-50183: Could not get the transaction manager using "{0}". Exception: "{1}"**  
**Cause:** Method of getting transaction manager might have changed in this release.  
**Action:** Internal system error.
- Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses
- OWS-50184: Could not get the transaction manager using "{0}"Got unexpected class "{1}" instead of javax.transaction.TransactionManager.**  
**Cause:** Method of getting transaction manager might have changed in this release.  
**Action:** Internal system error.
- Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses
- OWS-50187: [MessageID: {0}] System Error: Could not get the addressing namespace and so the None URI.**  
**Cause:** Addressing namespace is not available.  
**Action:** Internal system error.
- Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses
- OWS-51001: No TypeGeneratorFactory implementation found for factory {0}.**  
**Cause:** You may have specified a wrong factory name, or your Web Service libraries are not properly configured.  
**Action:** Please ensure that you have specified a valid factory name.
- Level:** 1  
**Type:** ERROR  
**Impact:** Configuration
- OWS-51500: Unable to open or locate the following file or directory: {0}.**  
**Cause:** A file or directory was not found or accessible.  
**Action:** Ensure that the file or directory name is properly specified and accessible.
- Level:** 1  
**Type:** ERROR  
**Impact:** Files
- OWS-60002: Could not resolve schema resource for namespace "{0}" at location "{1}"**  
**Cause:** Could not resolve the schema from given schemaLocation. This may be caused by network problem or malformed or incorrect schemaLocation URL/URI  
**Action:** See error message.
- Level:** 1  
**Type:** WARNING

---

**Impact:** Files

**OWS-60003: Serializer initialization failed. Unable to define SDO data types.**

**Cause:** Failed to define SDO data types from the given schema/schemas.

**Action:** Ensure that the schema/schemas provided through schemaLocation is/are valid and none of the schemas are conflicting with each other.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**OWS-65004: Invalid URI "{0}" in Addressing element {1}.**

**Cause:** Invalid URI found while reading the Addressing headers.

**Action:** Verify that the URI used for addressing is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**OWS-65005: AttributedURI type does not support Extensibility elements.**

**Cause:** AttributedURI type has Extensibility elements.

**Action:** Do not specify Extensibility element with AttibureURI type.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses



---

---

## PKI-01001 to PKI-07007

**PKI-01001: Missing arguments in the command: {0}**

**Cause:** An incomplete command was issued. For example, the wallet password or wallet location is missing.

**Action:** Check the usage of the command-line tool and provide all required arguments.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-01002: Invalid password.**

**Cause:** Passwords must have a minimum length of eight characters and contain alphabetic characters combined with numbers or special characters.

**Action:** Make sure the password policy is followed and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-01003: Passwords did not match.**

**Cause:** When creating a wallet, the password entered the second time did not match the password entered the first time.

**Action:** Enter the same password both times.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-02001: A wallet already exists at: {0}**

**Cause:** Attempted to create a new wallet at a location where a wallet already existed.

**Action:** Remove the existing wallet, or create the new wallet at another location.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-02002: Unable to open the wallet. Check password.**

---

**Cause:** Wallet password may be wrong.

**Action:** Try again with the correct password.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-02003: Unable to load the wallet at: {0}**

**Cause:** Possible causes include a wrong password, parsing errors, or the wallet file was not found.

**Action:** Check that the wallet is present at the specified location and the password is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-02004: Unable to verify the wallet.**

**Cause:** The wallet may be corrupted.

**Action:** Make sure you have the right wallet. Try opening the wallet in enterprise manager or by orapki to make sure it is appropriate.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-02005: Unable to delete the wallet at: {0}**

**Cause:** Possible causes include insufficient permission or the wallet being used by another person.

**Action:** Obtain the necessary permission and check that the wallet is not being used.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-02006: The specified directory does not exist: {0}**

**Cause:** Wallet creation failed because the specified directory did not exist.

**Action:** Create the directory prior to the wallet creation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-02007: The specified location is not a directory: {0}**

**Cause:** Wallet creation failed because the specified location was not a directory.

**Action:** Create the wallet in an existing directory instead.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**PKI-02008: Unable to modify a read-only Auto-login wallet.**

**Cause:** Attempted to update a read-only Auto-login wallet.

**Action:** Specify the associated Password-protected (.p12 file) wallet.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-02009: Unable to create directory.**

**Cause:** OS error in creating directory.

**Action:** Check file permissions and disk space.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-02010: Invalid MAC for Wallet. Wallet verification failed.**

**Cause:** The wallet is possibly corrupted.

**Action:** Restore the wallet from a backup or recreate it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-02011: Unable to set file permissions for wallet at {0}**

**Cause:** Wallet permissions could not be set.

**Action:** Try to save the wallet in a different directory.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-03001: The entry already exists: {0}**

**Cause:** Attempted to create a new entry with a previously used alias.

**Action:** Try again with another alias or delete the existing entry.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-03002: No entry found for the alias: {0}**

**Cause:** The specified alias was not found in the secret store.

**Action:** Check the alias name and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-03003: Secrets did not match.**

---

**Cause:** The secret (password) entered the second time did not match the one entered the first time.

**Action:** Enter the same secret both times.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-03004: Unable to load the secret store.**

**Cause:** Possible causes include a wrong password, the secret store file was not found or was corrupted.

**Action:** Check that the secret store file is present at the specified location and the password is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-03005: Unable to load the Java keystore.**

**Cause:** Possible causes include a wrong password, the Java keystore file was not found or was corrupted

**Action:** Check that the Java keystore file is present at the specified location and the password is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-04001: Invalid Certificate.**

**Cause:** The given certificate did not follow the X509/DER, X509/BASE64, PKCS7/DER, or PKCS7/BASE64 format.

**Action:** Use a valid certificate format.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-04002: No valid key or certificate in the wallet.**

**Cause:** Attempted to use a wallet for authentication/signatures/SSL, but no key or certificate was found in the wallet.

**Action:** Import certificates into the wallet/keystore or use a self-signed wallet/keystore.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-04003: The trusted certificate is already present in the wallet.**

**Cause:** Attempted to import a trusted certificate that already existed in the wallet.

**Action:** No action required. The trusted certificate is already present in the wallet.



---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-04004: The user certificate is already installed in the wallet.**

**Cause:** Attempted to install a user certificate that already existed in the wallet.

**Action:** No action required. The user certificate is already installed in the wallet.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-04005: No matching certificate request in the wallet.**

**Cause:** Attempted to install a user certificate, but no matching certificate request was found in the wallet.

**Action:** Make sure that the user certificate is being installed into the wallet where the certificate request was created.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-04006: No matching private key in the wallet.**

**Cause:** Attempted to install a user certificate, but no matching private key was found in the wallet.

**Action:** Make sure that the user certificate is being installed to the wallet where the certificate request was created.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-04007: No matching certificate in the wallet for the DN: {0}**

**Cause:** Attempted to access a user certificate, but no matching certificate of the DN was found.

**Action:** Make sure that a user certificate with the given DN exists in the wallet.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-04008: The alias is already taken in the wallet: {0}**

**Cause:** Attempted to create a key or import a certificate with an alias, but the alias already existed in the wallet.

**Action:** Try again with another alias.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-04009: No matching private key or certificate request found for the alias: {0}**

---

**Cause:** Attempted to install a user certificate into a wallet with an alias, but no matching private key / certificate request was found for this alias.

**Action:** Make sure that the user certificate is being installed with the same alias as the private key / certificate request.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-04010: No matching certificate found for the alias: {0}**

**Cause:** Attempted to access a user certificate that is associated with an alias, but no matching certificate was found for this alias.

**Action:** Make sure that a user certificate exists in the wallet with the given alias.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-04011: Cannot remove the certificate request if its associated user certificate is still present in the wallet.**

**Cause:** Attempted to remove a certificate request, but its associated user certificate was still present in the wallet.

**Action:** Remove the associated user certificate first.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-04012: Incomplete certificate chain**

**Cause:** Attempted to install a user certificate whose trusted certificate was not present in the wallet.

**Action:** Ensure that the CA certificate/Certificate Chain that issued the user certificate is present as trusted certificate in the wallet.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-04013: Entry with matching alias not trusted cert.**

**Cause:** Failed to add a trusted certificate into the wallet because the entry with that alias in the keystore was not a trusted cert.

**Action:** Specify a different alias.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-04014: No entry with matching alias is present in wallet/keystore.**

**Cause:** Failed to delete an entry in wallet/keystore because no entry with that alias was present.

**Action:** Specify the correct alias.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-04015: Trusted cert cannot be removed.**

**Cause:** The trusted cert is being used in a certificate chain.

**Action:** The user cert that has the trusted cert in its certificate chain should be removed first.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-04016: No user certificate found in the wallet.**

**Cause:** No user certificate that can be used with SSL was found.

**Action:** Install a user certificate into the wallet.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-04017: Entry identified by alias not a key entry.**

**Cause:** No entry in wallet/keystore had matching alias.

**Action:** Use a correct alias.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-04018: User cert does not match pvt key for input alias.**

**Cause:** The private key with matching alias did not match the user certificate.

**Action:** Use a correct alias.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-05001: Unable to read CRL at: {0}**

**Cause:** CRL was not present at the specified location or CRL was corrupted.

**Action:** Check the CRL file at the given location.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-05002: Unable to write CRL**

**Cause:** Insufficient file permission or insufficient disk space.

**Action:** Ensure that a file can be created at the specified location.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**PKI-05003: Untrusted or expired CRL**

**Cause:** The CRL at the user-given location expired or was not signed by a trusted authority.

**Action:** Get a valid or recent CRL from the CA.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-05004: No CRL found for the issuer: {0}**

**Cause:** No CRL issued by the CA was found at the specified CRL location.

**Action:** Import the specified CA's CRL into the specified location.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-05005: CRL symlink failed with the error: {0}**

**Cause:** Failed to set up a symlink for the CRL file.

**Action:** Make sure that the target CRL file exists and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-05006: Unable to find signer for CRL.**

**Cause:** No CA certificate in wallet for the CRL issuer was found.

**Action:** Add CA certificates from CRL issuer to wallet.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-07001: Unable to login to the LDAP server.**

**Cause:** The username or password may be invalid.

**Action:** Try again with the correct credentials.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-07002: Unable to find the LDAP subtree: {0}**

**Cause:** Attempted to search for CRLs from an LDAP server, but the subtree was not found.

**Action:** Confirm that the CRL file is present at the specified location.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**PKI-07003: Insufficient privilege to perform the operation in the LDAP server: {0}**

**Cause:** Attempted to perform some operation in the LDAP server for which the user did not have permission.

**Action:** Obtain the necessary authorization or have an authorized user perform the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-07004: Peer sent no certificates.**

**Cause:** The peer sent no certificates (which was needed during handshake).

**Action:** Check peer configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-07005: Untrusted Cert Chain.**

**Cause:** No trusted certificate in wallet/keystore for peer certificate was found.

**Action:** Peer should use a different certificate or import the peer's CA certificate into your wallet.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-07006: Invalid certificate signature.**

**Cause:** Certificate signature check failed.

**Action:** Use a different user certificate/certificate chain on peer.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**PKI-07007: Certificate is revoked.**

**Cause:** The peer's certificate has been revoked.

**Action:** Use a different user certificate/certificate chain on peer.

**Level:** 1

**Type:** ERROR

**Impact:** Other



---

## PROV-40000 to PROV-40000

**PROV-40000: Unexpected error happened while provisioning AS topology**

**Cause:** Internal Exception.

**Action:** See AS provisioning logs for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Topology





---

## RCS-00001 to RCS-23000

**RCS-00001: unexpected error has occurred**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-00003: failed to instantiate an instance of class [{0}]**

**Cause:** The class could not be found in the classpath

**Action:** Ensure the class is included in the application classpath

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RCS-00002: unexpected error has occurred**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-00004: required parameter [{0}] is missing or null**

**Cause:** An attempt was made to invoke a method without passing all the required parameters

**Action:** Ensure all required parameters are passed to the method

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RCS-00006: cannot find resource [{1}] in resource bundle [{0}]**

---

**Cause:** An attempt was made to load a text resource from a resource bundle but the resource was not found. The resource key was used instead.

**Action:** Add the missing resource to the resource bundle or correct the resource reference.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RCS-00005: cannot find resource bundle [{0}]**

**Cause:** The resource bundle could not be found on the classpath

**Action:** Ensure the resource bundle is included in the application classpath

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**RCS-00007: value [{1}] for parameter [{0}] is invalid**

**Cause:** An invalid parameter value was passed to the method

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RCS-00009: operation [{0}] is not supported in this release**

**Cause:** An attempt was made to invoke a method that is not supported in this release

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RCS-00008: expected type [{1}] but received type [{2}] for parameter [{0}]**

**Cause:** An attempt was made to read a parameter value but the parameter type was invalid

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RCS-00011: no objects bound to name [{0}]**

**Cause:** An attempt was made to find an object using the specified name. No object was bound to that name.

**Action:** Verify that the named object has not been renamed or deleted and re-try the operation.

**Level:** 1

---

**Type:** ERROR

**Impact:** Logging

**RCS-00010: name [{0}] is not valid for a resource catalog object**

**Cause:** An attempt was made to access a resource catalog object using a name that does not conform to the required structure or format

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RCS-00012: error while initializing class**

**Cause:** An unexpected error occurred during execution of a static initializer while loading a Java class. The class could not be loaded

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RCS-00015: error while canceling pending changes for RCTestSession [{0}]**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-00014: error while flushing pending changes for RCTestSession [{0}]**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-00013: invalid MDS reference [{0}]**

**Cause:** An attempt was made to create an MDS Reference from a String that does not conform to the required format

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RCS-00016: error while creating a URI using catalog Id [{0}] and catalog path [{1}]**

---

**Cause:** The catalog id or catalog path contain characters that are invalid in a URI

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RCS-00018: error while creating a URI using repository [{0}] and repository path [{1}]**

**Cause:** The repository id or repository path contain characters that are invalid in a URI

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RCS-00017: error [{1}] while creating a catalog reference from URI [{0}]**

**Cause:** The specified URI could not be parsed either because it is not a Catalog Reference URI or the URI is corrupt

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RCS-00019: error while creating a repository reference from URI [{0}]**

**Cause:** The specified URI could not be parsed either because it is not a repository reference URI or the URI is corrupt

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RCS-00021: error [{0}] while setting default value [{2}] on attribute descriptor [{1}]**

**Cause:** Review the cause included in the message for more details

**Action:** Take appropriate action based on the cause included in the message and any underlying exceptions

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RCS-00020: data type [{1}] in attribute descriptor [{0}] is not supported**

**Cause:** An attempt was made to create an attribute descriptor using an invalid data type

**Action:** Change the attribute descriptor to use a supported data type.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**RCS-00023: operation [{0}] is not allowed in the current session**

**Cause:** An attempt was made to perform a catalog related operation in a session configured for connection operations only

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RCS-00022: Session properties cannot be modified after the session has been initialized.**

**Cause:** An attempt was made to modify the properties of a resource catalog session after the session had been initialized

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RCS-00026: operation canceled. operation=[{0}]. reason=[{1}]**

**Cause:** An operation was canceled by a user. This usually happens when the operation was taking too long to complete.

**Action:** No action is necessary

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**RCS-00027: search canceled. root context=[{0}]. expression=[{1}]. reason=[{2}]**

**Cause:** A search operation was canceled by a user because it may have taken too long to complete

**Action:** No action is necessary

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**RCS-00028: An attempt was made to modify an immutable Name object**

**Cause:** A program attempted to modify a immutable Name object

**Action:** Correct the program so it does not attempt to modify immutable names

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RCS-01000: The resource catalog service has not been configured for this application.**

**Cause:** Configuration parameters for the resource catalog service could not be found in the application's adf-config.xml file

---

**Action:** Refer to the resource catalog service documentation and add the necessary configuration parameters to the application's adf-config.xml file

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**RCS-01001: configuration parameter [{1}] is missing from resource catalog instance [{0}]**

**Cause:** A required configuration parameter was not specified in the adf-config.xml file.

**Action:** Refer to the resource catalog service documentation and add the missing configuration parameter to the configuration file

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**RCS-01003: error occurred initializing MDS instance [{0}]**

**Cause:** The MDS instance used by the resource catalog service could not be initialized due to an previous error

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**RCS-01002: Invalid configuration parameter. RCInstance=[{0}] Parameter=[{1}] Invalid value=[{2}] Substituted value=[{3}]**

**Cause:** The resource catalog service was configured with an invalid parameter value

**Action:** Refer to the resource catalog service documentation and correct the configuration parameters

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**RCS-01004: a resource catalog instance with Id [{0}] already exists.**

**Cause:** An attempt was made to create a new resource catalog instance using an ID that is already in use by another instance.

**Action:** Verify that the instance Id specified in adf-config.xml is unique. If it is unique, verify that the application code is not attempting to create multiple instances with the same ID instead of re-using an existing instance.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**RCS-01006: error while obtaining an MDS Session from session provider [{0}]**

---

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**RCS-01005: error while obtaining a connection context using connection context provider [{0}]**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**RCS-01007: an ADFContext has not been registered for name [{0}].**

**Cause:** The named ADFContext required by the resource catalog service cannot be found

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**RCS-01009: error while creating a connections metadata object using path [{0}]**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-01008: error while initializing the connections context**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**RCS-01010: error while deleting a connections metadata object using path [{0}]**

**Cause:** An exception was raised by an underlying component.

---

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-01011: error while opening a connections metadata object using path [{0}]**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-01013: cannot find any resource catalog extensions on the classpath**

**Cause:** The classpath did not include any jars that declare resource catalog extensions. The resource catalog requires at least one connection type and one resource catalog adapter to function.

**Action:** Add one or more jar files containing these extensions to your application classpath

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**RCS-01012: error while attempting to locate the resource catalog extensions.**

**Cause:** An exception was raised while attempting to find resource catalog extensions from the classpath

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**RCS-01015: error while instantiating CatalogItemFactoryPlugin [{0}]**

**Cause:** The specified plugin could not be instantiated or does not implement the required interface. Failure to load one plugin does not prevent the loading of others.

**Action:** Add the missing class to the classpath, modify the class to implement the correct interface or remove the declaration from META-INF/rc\_ext.xml

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**RCS-01014: error while processing a resource catalog extension using URL [{0}]**



---

**Cause:** An exception was raised while loading a resource catalog extension. Failure to load one extension does not prevent other extensions from loading

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**RCS-01017: duplicate resource type [{0}]**

**Cause:** A Resource Type with the specified ID has already been loaded. The duplicate was ignored

**Action:** Remove the declaration for the duplicate resource type from META-INF/rc\_ext.xml

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**RCS-01016: error while instantiating a resource type [{0}]**

**Cause:** The specified plugin class could not be instantiated or does not implement the required interface. Failure to load one plugin does not prevent the loading of others.

**Action:** Add the missing class to the classpath, modify the class to implement the correct interface or remove the declaration from META-INF/rc\_ext.xml

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**RCS-01019: Target directory [{0}] for resource catalog configuration files does not exist.**

**Cause:** An attempt was made to dynamically create a resource catalog instance, but the target directory specified by the client does not exist.

**Action:** Create the target directory or configure the client to use a different directory for the resource catalog configuration files

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**RCS-01021: Target directory [{0}] for resource catalog configuration files is not readable.**

**Cause:** An attempt was made to dynamically create a resource catalog instance, but the target directory specified by the client is not readable

**Action:** Change the permissions on the target directory so it is readable or configure the client to use a different path for the resource catalog configuration files.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**RCS-01020: Target path [{0}] for resource catalog configuration files is not valid.**

**Cause:** An attempt was made to dynamically create a resource catalog instance, but the target path specified by the client is not a directory

**Action:** Configure the client to use a different path for the resource catalog configuration files. The path must be a directory

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**RCS-01022: Target directory [{0}] for resource catalog configuration files is not writable.**

**Cause:** An attempt was made to dynamically create a resource catalog instance, but the target directory specified by the client is not writable

**Action:** Change the permissions on the target directory so it is writable or configure the client to use a different path for the resource catalog configuration files.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**RCS-01025: cannot find configuration template [{0}]**

**Cause:** The specified configuration file template could not be found on the application classpath

**Action:** Ensure the missing template is included in the classpath

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**RCS-01024: error while creating a resource catalog instance**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**RCS-01023: An ADFContext has already been registered using name [{0}].**

**Cause:** The named ADFContext required by the resource catalog Service cannot be registered using the specified name because the name is already in use

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Configuration

**RCS-02000: error while attempting to lookup connection [{0}]**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-02001: cannot find connection [{0}]**

**Cause:** The specified connection could not be found. The connection may have been deleted or renamed

**Action:** Create a new connection with the specified ID

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**RCS-02005: The resource catalog adapter factory [{1}] for connection type [{0}] does not implement the required interfaces.**

**Cause:** Resource catalog adapters are required to implement a specific set of interfaces. The specified adapter does not implement one or more of these interfaces.

**Action:** If the adapter was provided by Oracle, contact Oracle Support Services. Otherwise contact the provider of the adapter

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-02004: A resource catalog adapter has already been registered for connection type [{0}]. The duplicate will be ignored**

**Cause:** Two or more META-INF/rc\_ext.xml files found on the application classpath include resource catalog adapter declarations for the same connection type.

**Action:** Remove the duplicate adapter declarations from the application classpath

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**RCS-02003: error while registering resource catalog adapter factory [{1}] for connection type [{0}]**

**Cause:** An exception was raised while registering the resource catalog adapter

**Action:** Verify the connection type registered and that the resource catalog adapter factory class is included in the application classpath

**Level:** 1

**Type:** ERROR

---

**Impact:** Logging

**RCS-02006: cannot find a resource catalog adapter for connection type [{0}]**

**Cause:** A resource catalog adapter has not been registered for the specified connection type.

**Action:** Add an appropriate resource catalog adapter implementation to the application classpath

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**RCS-02010: error while closing subcontext [{0}] for repository id [{1}], repository path [{2}]**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-02009: error while creating InitialContext for repository ID [{0}], repository path [{1}] using InitialContextFactory [{2}]**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-02012: The value [{1}] of resource catalog environment parameter [{0}] is not valid.**

**Cause:** An attempt was made to read a resource catalog environment variable but the variable contained an invalid value.

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RCS-02011: cannot find resource catalog environment parameter [{0}]**

**Cause:** An expected parameter could not be found in the resource catalog environment hashtable

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Programmatic

**RCS-02013: error while obtaining the connection type for connection [{0}]**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RCS-02014: resource catalog adapter factory [{0}] returned null for repository reference [{1}]**

**Cause:** The resource catalog adapter factory returned null when a CatalogContext object was expected.

**Action:** If the resource catalog adapter was provided by Oracle, contact Oracle Support Services. Otherwise contact the provider of the adapter

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RCS-02017: error while creating InitialContext for repository ID [{0}], repository path [{1}] using InitialContextFactory [{2}]. Error was [{3}]**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-02016: cannot find connection type for connection [{0}]**

**Cause:** The resource catalog service could not determine the connection type of the specified connection.

**Action:** Declare the connection type in META-INF/rc\_ext.xml (runtime) or META-INF/extension.xml (design-time).

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**RCS-02015: unexpected object type [{1}] returned by resource catalog adapter factory [{0}] for repository reference [{2}]**

**Cause:** The resource catalog adapter factory returned an invalid object type. Adapter factories are required to return an instance or oracle.adf.rc.core.CatalogContext.

**Action:** If the InitialContextFactory was provided by Oracle, contact Oracle Support Services. Otherwise contact the provider of the InitialContextFactory

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RCS-03000: cannot find resource catalog [{0}] using MDS path=[{1}]**

**Cause:** An attempt was made to open a resource catalog, but the catalog could not be found

**Action:** Verify the catalog exists in the MDS repository. If the document exists, check the resource catalog configuration settings in adf-config.xml

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-03002: invalid resource catalog ID [{0}] using MDS path [{1}]**

**Cause:** The MDS path generated using the specified resource catalog ID was rejected by MDS

**Action:** Use an ID whose structure and characters meets the requirements for MDS references.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**RCS-03001: duplicate resource catalog ID [{0}] using MDS path [{1}]**

**Cause:** A resource catalog with the specified ID already exists.

**Action:** Open the existing catalog or choose a different catalog ID if you want to create a new catalog.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**RCS-03003: error while renaming catalog from [{0}] to [{1}]**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-03005: error while deleting resource catalog [{0}] using MDS Path [{1}]**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Logging

**RCS-03008: error while removing element [{1}] from resource catalog [{0}]**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-03010: error while adding element [{1}] to parent element [{2}] in resource catalog [{0}]**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-03011: error while processing an elementAdded event for element [{3}], folder [{2}] in resource catalog [{0}]**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-03014: unrecognized element [{1}:{2}] found in resource catalog [{0}]**

**Cause:** The resource catalog definition contains an unrecognized element type. The element was ignored.

**Action:** Remove the invalid element from the resource catalog definition

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**RCS-03013: error while processing an elementRenamed event, renaming element [{2}] to [{3}] in folder [{1}], resource catalog [{0}]**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Logging

**RCS-03012: error while processing an elementModified event for element [{3}], folder [{2}] in resource catalog [{0}]**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-03015: Element [{1}] of resource catalog [{0}] has been excluded from the catalog due to error [{2}].**

**Cause:** An exception was raised by an underlying component that prevented the specified element from being included in the catalog.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-03016: An error has occurred while creating folder [{1}] in resource catalog [{0}]. The folder was ignored.**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-03018: An error has occurred while processing expression filter [{2}] of folder [{1}] in resource catalog [{0}]. The filter was ignored.**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-03017: An error has occurred while creating dynamic folder [{1}] in resource catalog [{0}]. The dynamic folder was ignored.**

**Cause:** An exception was raised by an underlying component.



---

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-03019: An error has occurred while creating custom filter [{2}] of folder [{1}] in resource catalog [{0}]. The folder was ignored. Filter class=[{3}].**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-03021: cannot find resource using repository [{0}] and repository path [{1}]. The repository may not be accessible or the resource may have been deleted or renamed**

**Cause:** The source repository may be temporarily inaccessible or the resource may have been deleted or renamed in the source repository.

**Action:** Refresh the parent folder see the revised contents

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**RCS-03020: An error has occurred while creating custom folder [{1}] in resource catalog [{0}]. The custom folder was ignored. Factory class=[{2}]**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-03023: An error has occurred while querying source repository [{2}], repository path [{3}] for dynamic folder [{1}] in resource catalog [{0}]. The dynamic folder source was ignored**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Logging

**RCS-03022: unexpected object type returned using repository [{3}] and repository path [{4}] in resource catalog [{0}]. Expected [{1}] but received [{2}] from adapter [{5}]**

**Cause:** A resource catalog adapter returned an unexpected item type

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-03024: The custom content element [{1}] in resource catalog [{0}] does not specify a CustomContextProvider class. The element was ignored.**

**Cause:** The specified custom content element does not include a class attribute specifying the CustomContentProvider implementation. This attribute is required.

**Action:** Add the missing attribute to the specified element or remove it from the catalog.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**RCS-03027: The catalog definition filter [{1}] in resource catalog [{0}] does not implement the oracle.adf.rc.spi.plugin.catalog.CatalogDefinitionFilter interface. The filter was ignored**

**Cause:** The specified filter class does not implement the required interface.

**Action:** Modify the specified class so it implements the required interface or replace it with one that does.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**RCS-03026: An error has occurred while instantiating catalog definition filter [{1}] in resource catalog [{0}]. The filter was ignored.**

**Cause:** The specified class could not be found in the application classpath.

**Action:** Verify the specified class is included in the application classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**RCS-03025: error while creating an instance of [{2}], referenced by CustomContent element [{1}] in resource catalog [{0}]**

**Cause:** The specified class could not be found in the application classpath.

**Action:** Add the specified class to the application classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

---

**RCS-03029: An error has occurred while creating a custom folder using InitialContextFactory [{1}] in resource catalog [{0}]. The custom folder was ignored.**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-03028: An error has occurred while invoking catalog definition filter [{2}] in resource catalog [{0}]. The filter was ignored.**

**Cause:** An exception was raised by the catalog definition filter

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-03032: error while adding a transient catalog element to a persistent catalog folder.**

**Cause:** Transient catalog elements can only be added to catalogs by CustomContentProviders. They cannot be added to persistent catalog definitions.

**Action:** Change the client code that is invoking the specified API so it uses PersistentElements instead of TransientElements.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RCS-03031: An error has occurred while creating catalog item [{1}] in catalog [{0}]. The catalog item was ignored.**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-03030: An error has occurred while refreshing the contents of folder [{1}] in catalog [{0}]. Some child elements may not have been loaded.**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-03034: An attempt was made to add a persistent catalog element to a transient catalog folder.**

**Cause:** Transient catalog folders are intended for use by CustomContentProviders. They can only contain other transient elements

**Action:** Change the client code so it uses TransientElements instead of PersistentElements

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RCS-03033: operation [{1}] of interface [{0}] is not supported for transient elements.**

**Cause:** An attempt was made to invoke an unsupported operation on a transient catalog element.

**Action:** Change the client code that it does not invoke the specified method.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RCS-03038: An error has occurred while creating component [{1}] in resource catalog [{0}]. The component was ignored.**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-03037: error while opening catalog [{0}]**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-03036: cannot resolve reference to resource using repository [{2}], repository path [{3}] at element [{1}] in catalog [{0}]**

**Cause:** The specified resource element could not be resolved because the repository or repository path could not be found.

**Action:** Verify that the catalog entry is correct, the repository exists in your application and the repository path is valid.

---

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**RCS-03035: cannot resolve reference to repository using repository [{2}], repository path [{3}] at element [{1}] in catalog [{0}]**

**Cause:** The specified repository element could not be resolved because the repository or repository path could not be found.

**Action:** Verify that the catalog entry is correct, the repository exists in your application and the repository path is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**RCS-04000: error while processing predicate [{0}]**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-04001: query expression [{0}] is invalid**

**Cause:** The query string does not conform to the JNDI query syntax (RFC 2254)

**Action:** Use a query string that conforms to the JNDI query syntax (RFC 2254)

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RCS-04004: error while comparing catalog item [{0}] with [{1}]**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-04003: The type [{1}] of attribute [{0}] does not implement the Comparable interface.**

**Cause:** The specified attribute value is of an unsupported data type that does not implement the Comparable interface. All attributes declared as searchable by a resource catalog adapter schema must implement this interface.

**Action:** Modify the resource catalog schema for the source adapter so this attribute is not searchable or modify the attribute's datatype so it is Comparable.

---

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**RCS-04002: query expression [{0}] contains invalid wildcard syntax**

**Cause:** Wildcards can only be used with the EQUALS operator

**Action:** Modify the query expression so wildcards are only used with the EQUALS operator

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RCS-04010: An error has occurred while searching folder [{1}] in catalog [{0}]. The folder was skipped. Implementation class=[{2}]**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-04012: An error has occurred while searching custom folder [{1}] in catalog [{0}]. The folder was skipped. Implementation class=[{2}]**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-04011: An error has occurred while searching folder [{1}] in repository [{0}]. The folder was skipped. Implementation class=[{2}]**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-04013: attribute [{0}], value [{1}], has an unsupported data type [{2}]**

**Cause:** An attribute returned a value with an unsupported data type. The value was converted to a String.

**Action:** Ensure that the values for all resource catalog attributes correspond to one of the supported data types defined by oracle.adf.rc.attribute.AttributeConstants

---

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**RCS-05000: error processing transfer set [{0}]**

**Cause:** An exception was raised by an underlying component.

**Action:** Review the exception details for more information. If the information provided is not sufficient to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-05002: transfer set [{0}] is empty**

**Cause:** The transfer set did not include any connection or catalog entries.

**Action:** Create a transfer set containing at least one connection or one catalog and then repeat the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**RCS-05004: An error has occurred transferring connection [{1}] in transfer set [{0}].  
The failure control is set to [{2}].**

**Cause:** An exception was raised by an underlying component and the transfer process was configured to fail when encountering an error.

**Action:** Review the cause of the failure, correct it, and then restart the transfer process. Alternatively, change the failure controls to ignore errors.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**RCS-05003: An error has occurred while transferring connections in transfer set [{0}].  
The failure control is set to [{1}].**

**Cause:** An exception was raised by an underlying component and the transfer process was configured to fail when encountering an error.

**Action:** Review the cause of the failure, correct it, and then restart the transfer process. Alternatively, change the failure controls to ignore errors.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**RCS-05006: An error has occurred while transferring catalogs in transfer set [{0}].  
The failure control is set to [{1}].**

**Cause:** An exception was raised by an underlying component and the transfer process was configured to fail when encountering an error.

**Action:** Review the cause of the failure, correct it, and then restart the transfer process. Alternatively, change the failure controls to ignore errors.

---

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**RCS-05005: Connection ID [{1}] in transfer set [{0}] already exists in the target environment. The duplicates control is set to [{2}].**

**Cause:** A connection included in the specified transfer set already exists in the target environment and the duplicates control is set to fail upon detecting a duplicate.

**Action:** Remove the duplicate connection from the target environment and then restart the transfer process. Alternatively, change the duplicates control to overwrite or ignore duplicates.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**RCS-05008: Catalog ID [{1}] in transfer set [{0}] already exists in the target environment. The duplicates control is set to [{2}].**

**Cause:** A catalog included in the specified transfer set already exists in the target environment and the duplicates control is set to fail upon detecting a duplicate.

**Action:** Remove the duplicate catalog from the target environment and then restart the transfer process. Alternatively, change the duplicates control to overwrite or ignore duplicates.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**RCS-05007: An error has occurred while transferring catalog [{1}] in transfer set [{0}]. The failure control is set to [{2}].**

**Cause:** An exception was raised by an underlying component and the transfer process was configured to fail when encountering an error.

**Action:** Review the cause of the failure, correct it, and then restart the transfer process. Alternatively, change the failure controls to ignore errors.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**RCS-06001: An unexpected error has occurred destroying a pooled object. Pool=[{0}]**

**Cause:** Review the root cause of the exception for more details.

**Action:** If the root cause does not provide sufficient information to resolve the issue, contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**RCS-06002: leakage detected while destroying object pool [{0}]. In-use count=[{1}]**



---

**Cause:** An attempt was made to destroy an object pool when objects were still in use. This is a potential memory leak

**Action:** Identify the clients of the object pool and ensure all objects are returned to the pool before it is destroyed.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**RCS-23000: An unexpected error has occurred.**

**Cause:** Review the root cause of the exception in the log file for more details.

**Action:** If the root cause does not provide sufficient information to resolve the issue, contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging



---

## RCU-06000 to RCU-06138

**RCU-06000: Could not connect to the database. Some fields are empty.**

**Cause:** Could not connect to the database. Some fields are empty.

**Action:** Please enter valid values in all required fields

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06001: Invalid port number: {0}. A valid port number ranges from 0 to 65535.**

**Cause:** Invalid port number: {0}. A valid port number ranges from 0 to 65535.

**Action:** Please enter a valid port number

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06002: The specified database does not meet the minimum requirement to load metadata repository.**

**Cause:** The specified database does not meet the minimum requirement to load metadata repository.

**Action:** Please modify the prerequisite or the database configuration to meet the prerequisite requirements

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06003: RCU could not find the Schema Version Registry in the database. No metadata repository schema could be dropped.**

**Cause:** RCU could not find the Schema Version Registry in the database. No metadata repository schema could be dropped.

**Action:** Please contact the system administrator

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06004: Enter password for the SYS user.**

---

**Cause:** Enter password for the SYS user.

**Action:** Please enter the password for the sys user

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06010: No Existing Prefixes**

**Cause:** No Existing Prefixes

**Action:** Please create a new prefix

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06011: A valid prefix should be specified. Prefix can contain only alpha-numeric characters. It should not start with a number and should not contain any special characters.**

**Cause:** A valid prefix should be specified. Prefix can contain only alpha-numeric characters. It should not start with a number and should not contain any special characters.

**Action:** Please select a prefix from the existing prefixes or enter a new prefix

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06012: There are no existing prefixes.**

**Cause:** There are no existing prefixes.

**Action:** Please create a new prefix

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06013: Specified prefix does not exist. Existing prefixes are: {0}**

**Cause:** Specified prefix does not exist. Existing prefixes are: {0}

**Action:** Please specify another prefix

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06014: Specified component does not exist. Existing components for prefix: {0} are: {1}**

**Cause:** Specified component does not exist. Existing components for prefix: {0} are: {1}

**Action:** Please provide a component that exists

**Level:** 1

---

**Type:** ERROR

**Impact:** Installation

**RCU-06015: No component selected/specified. Please select/specify atleast one component.**

**Cause:** No component selected/specified. Please select/specify atleast one component.

**Action:** Please select atleast one component

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06016: The specified prefix already exists.**

**Cause:** The specified prefix already exists.

**Action:** Please specify another prefix

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06017: There was no prefix specified and the specified component already exists.**

**Cause:** There was no prefix specified and the specified component already exists.

**Action:** If the component is non-prefixable, only one instance can exist. If you want to re-create it, you have to drop it first

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06018: {0} schema owner is empty.**

**Cause:** {0} schema owner is empty.

**Action:** Please provide values for all schema owners

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06019: Invalid format for schema owner {0}. Prefixable components should have the schema owner in the following format <prefix>\_<Any String> where the prefix is {1}.**

**Cause:** Invalid format for schema owner {0}. Prefixable components should have the schema owner in the following format <prefix>\_<Any String> where the prefix is {1}.

**Action:** Please ensure that the schema owners of all prefixable components begin with the prefix, followed by "\_"

**Level:** 1

**Type:** ERROR

**Impact:** Installation

---

**RCU-06020: Schema Owner {0} is duplicated. Schema Owners must be unique.**

**Cause:** Schema Owner {0} is duplicated. Schema Owners must be unique.

**Action:** Please provide unique schema owners

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06021: The specified component ({0}) is non-prefixable and it already exists.**

**Cause:** The specified component ({0}) is non-prefixable and it already exists.

**Action:** Please deselect the non-prefixable component as it already exists

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06022: No components to resume execution. Please run in normal mode.**

**Cause:** No components to resume execution. Please run in normal mode.

**Action:** No components to resume execution. Please run in normal mode.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06030: The specified tablespace {0} for component {1} does not have enough free space to hold the repository. The required free space is {2} MB, but the available space is {3} MB.**

**Cause:** The specified tablespace {0} for component {1} does not have enough free space to hold the repository. The required free space is {2} MB, but the available space is {3} MB.

**Action:** Please modify the properties of the tablespace or change the prerequisite value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06040: Could not connect to the specified Middleware Administration Server. Some fields are empty.**

**Cause:** Could not connect to the specified Middleware Administration Server. Some fields are empty.

**Action:** Please provide valid values for all required fields

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06041: Could not connect to the specified Middleware Administration Server.**

**Cause:** Could not connect to the specified Middleware Administration Server.

**Action:** Please verify that the connection details provided are correct and try again

---

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06042: MAS registry for {0} schema already exists with the same name. Specify a different registry name.**

**Cause:** MAS registry for {0} schema already exists with the same name. Specify a different registry name.

**Action:** Component is already registered. Please de-select this component for the purpose of registration

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06043: Can not deregister, there is no MAS registry with this name.**

**Cause:** Can not deregister, there is no MAS registry with this name.

**Action:** Component is not registered. Please de-select this component for the purpose of de-registration

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06051: RCUCmdLine Error - Invalid Option passed:**

**Cause:** RCUCmdLine Error - Invalid Option passed:

**Action:** Please provide valid command-line options

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06052: RCUCmdLine Error - Invalid format/order of optionValue:**

**Cause:** RCUCmdLine Error - Invalid format/order of optionValue:

**Action:** Please ensure that the format/order of the options and values in the command-line are correct

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06053: RCUCmdLine Error - More than one mutually exclusive options passed:**

**Cause:** RCUCmdLine Error - More than one mutually exclusive options passed:

**Action:** Please provide valid command-line options

**Level:** 1

**Type:** ERROR

**Impact:** Installation

---

**RCU-06054: RCUCommandLine Error - Database type should be provided.**

**Cause:** RCUCommandLine Error - Database type should be provided.

**Action:** Please provide the database type

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06055: RCUCommandLine Error - Database connect string should be provided.**

**Cause:** RCUCommandLine Error - Database connect string should be provided.

**Action:** Please provide the database connect string

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06056: RCUCommandLine Error - Database hostname should be provided.**

**Cause:** RCUCommandLine Error - Database hostname should be provided.

**Action:** Please provide the database hostname

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06057: RCUCommandLine Error - Database port number should be provided.**

**Cause:** RCUCommandLine Error - Database port number should be provided.

**Action:** Please provide the database port number

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06058: RCUCommandLine Error - Database service name should be provided.**

**Cause:** RCUCommandLine Error - Database service name should be provided.

**Action:** Please provide the database service name

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06059: RCUCommandLine Error - Database user should be provided.**

**Cause:** RCUCommandLine Error - Database user should be provided.

**Action:** Please provide the database user

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06060: RCUCommandLine Error - Database password should be provided.**

**Cause:** RCUCommandLine Error - Database password should be provided.



---

**Action:** Please provide the database password

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06061: RCUCommandLine Error - Database role should be provided.**

**Cause:** RCUCommandLine Error - Database role should be provided.

**Action:** Please provide the database role

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06062: RCUCommandLine Error - Schema Prefix should be provided.**

**Cause:** RCUCommandLine Error - Schema Prefix should be provided.

**Action:** Please provide the schema prefix

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06063: RCUCommandLine Error - Tablespace name should be provided. Pass - DEFAULT\_VALUE if you want the default to be used.**

**Cause:** RCUCommandLine Error - Tablespace name should be provided. Pass - DEFAULT\_VALUE if you want the default to be used.

**Action:** Please provide the tablespace name

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06064: RCUCommandLine Error - Schema owner name should be provided. Pass - DEFAULT\_VALUE if you want the default to be used.**

**Cause:** RCUCommandLine Error - Schema owner name should be provided. Pass - DEFAULT\_VALUE if you want the default to be used.

**Action:** Please provide the schema owner

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06065: RCUCommandLine Error - Invalid Component Name:**

**Cause:** RCUCommandLine Error - Invalid Component Name:

**Action:** Please provide a valid component name

**Level:** 1

**Type:** ERROR

**Impact:** Installation

---

**RCU-06066: RCUCommandLine Error - Checkpoint object not found or is not readable. Cannot proceed in resume mode.**

**Cause:** RCUCommandLine Error - Checkpoint object not found or is not readable. Cannot proceed in resume mode.

**Action:** RCUCommandLine Error - Checkpoint object not found or is not readable. Cannot proceed in resume mode.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06067: RCUCommandLine Error - No pending components found in checkpoint. Cannot proceed in resume mode.**

**Cause:** RCUCommandLine Error - No pending components found in checkpoint. Cannot proceed in resume mode.

**Action:** RCUCommandLine Error - No pending components found in checkpoint. Cannot proceed in resume mode.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06068: Failed to write checkpoint object.**

**Cause:** Failed to write checkpoint object.

**Action:** Failed to write checkpoint object.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06069: RCUCommandLine Error - MAS password should be provided.**

**Cause:** RCUCommandLine Error - MAS password should be provided.

**Action:** RCUCommandLine Error - MAS password should be provided.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06080: Global prerequisite check failed - Check requirement for specified database**

**Cause:** Global prerequisite check failed - Check requirement for specified database

**Action:** Please modify the global prerequisite or the database configuration to meet the global prerequisite requirements

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06081: Failed - Obtain properties of the specified database**

**Cause:** Failed - Obtain properties of the specified database

---

**Action:** Please make sure that the database is in a proper state

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06082: Tablespace prerequisite check failed - Check tablespace requirement for each selected component**

**Cause:** Tablespace prerequisite check failed - Check tablespace requirement for each selected component

**Action:** Please modify the properties of the tablespace or change the prerequisite value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06083: Failed - Check prerequisites requirement for selected component:**

**Cause:** Failed - Check prerequisites requirement for selected component:

**Action:** Please make sure that the prerequisite requirements are met

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06084: Invalid format for Java prerequisite: {0}**

**Cause:** Invalid format for Java prerequisite: {0}

**Action:** Please make sure that the java prerequisite is in a valid format

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06085: Error while executing Java prerequisite: {0}**

**Cause:** Error while executing Java prerequisite: {0}

**Action:** Please make sure that the java prerequisite is in a valid format and all required classes and jar files are present

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06090: Skipping Main operation: Failed in Connection step validation**

**Cause:** Skipping Main operation: Failed in Connection step validation

**Action:** Please provide correct database details and try again

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06091: Component name/schema prefix validation failed.**

---

**Cause:** Component name/schema prefix validation failed.

**Action:** Please provide valid component name and prefix and try again

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06092: Component Selection validation failed. Please refer to log at {0} for details.**

**Cause:** Component Selection validation failed. Please refer to log at {0} for details.

**Action:** Please select one or more components to continue

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06093: Skipping Main operation: Failed in SchemaTablespace step validation**

**Cause:** Skipping Main operation: Failed in SchemaTablespace step validation

**Action:** Please check the properties of the database and the tablespaces specified

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06094: Skipping Main operation: Failed in MAS Registration step validation**

**Cause:** Skipping Main operation: Failed in MAS Registration step validation

**Action:** Please make sure that MAS is up and is in a proper state and try again or contact the system administrator

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06100: Encountered an Exception while trying to execute Prerequisite: {0}**

**Cause:** Encountered an Exception while trying to execute Prerequisite: {0}

**Action:** Please refer to the logs for details

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06101: Prerequisite Failure for: {0} Required Value = {1}, Current Value = {2}, Comparison Operator: "{3}"**

**Cause:** Prerequisite Failure for: {0} Required Value = {1}, Current Value = {2}, Comparison Operator: "{3}"

**Action:** Please modify the prerequisite or the database configuration to meet the prerequisite requirements

**Level:** 1

**Type:** ERROR

---

**Impact:** Installation

**RCU-06102: Prerequisite Failure. The Prerequisite: {0} returned an empty result.**

**Cause:** Prerequisite Failure. The Prerequisite: {0} returned an empty result.

**Action:** Please modify the database configuration to meet the prerequisite requirements

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06103: DB Option Prerequisite failure for: {0} Required Value = {1}, Current Value = {2}**

**Cause:** DB Option Prerequisite failure for: {0} Required Value = {1}, Current Value = {2}

**Action:** Please make sure that the DBOption has the required value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06104: DB Object Prerequisite failure for: {0} This object does not exist or its status is not VALID}**

**Cause:** DB Object Prerequisite failure for: {0} This object does not exist or its status is not VALID}

**Action:** Please make sure that the DBObject exists and is valid

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06105: DB Component Prerequisite failure for: {0} This component does not exist or its status is not VALID.**

**Cause:** DB Component Prerequisite failure for: {0} This component does not exist or its status is not VALID.

**Action:** Please make sure that the DBComponent exists and is valid

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06106: DB Version Prerequisite failure. Required Version = {0}, Current Version = {1}, Comparison Operator: "{3}"**

**Cause:** DB Version Prerequisite failure. Required Version = {0}, Current Version = {1}, Comparison Operator: "{3}"

**Action:** Please make sure that the DBVersion has the required value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

---

**RCU-06107: DB Init Param Prerequisite failure for: {0} Required Value = {1}, Current Value = {2}, Comparison Operator: "{3}"**

**Cause:** DB Init Param Prerequisite failure for: {0} Required Value = {1}, Current Value = {2}, Comparison Operator: "{3}"

**Action:** Please make sure that the DB Init parameter has the required value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06108: DB TablespaceFreeMB Prerequisite failure for: {0} Required space = {1}, Current space = {2}, Comparison Operator: "{3}"**

**Cause:** DB TablespaceFreeMB Prerequisite failure for: {0} Required space = {1}, Current space = {2}, Comparison Operator: "{3}"

**Action:** Please modify the properties of the tablespace or change the prerequisite value

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06120: Component dependencies not met for components with following ids: {0}.**

**Cause:** Component dependencies not met for components with following ids: {0}.

**Action:** Please select the dependent components

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06121: Component dependencies check failed. Please select the dependent components and try again.**

**Cause:** Component dependencies check failed. Please select the dependent components and try again.

**Action:** Please select the dependent components

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06130: Action failed - {0}**

**Cause:** Action failed - {0}

**Action:** Please check the actions for the component or contact the system administrator

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06131: Error while trying to connect to database.**

**Cause:** Error while trying to connect to database.

---

**Action:** Please provide correct database details and try again or contact the system administrator

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06132: Database type not supported - {0}**

**Cause:** Database type not supported - {0}

**Action:** Please use a database type that is supported

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06133: Error while trying to execute HostCommand action.**

**Cause:** Error while trying to execute HostCommand action.

**Action:** Please check the host command action for the component or contact the system administrator

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06134: Error while trying to execute JDBC action.**

**Cause:** Error while trying to execute JDBC action.

**Action:** Please check the jdbc action for the component or contact the system administrator

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06135: Error while trying to execute Java action.**

**Cause:** Error while trying to execute Java action.

**Action:** Please check the java action for the component or contact the system administrator

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06136: Error while trying to execute SQLPlus action.**

**Cause:** Error while trying to execute SQLPlus action.

**Action:** Please check the sqlplus action for the component or contact the system administrator

**Level:** 1

**Type:** ERROR

**Impact:** Installation

---

**RCU-06137: Error while trying to register with MAS.**

**Cause:** Error while trying to register with MAS.

**Action:** Please make sure that MAS is up and is in a proper state and try again or contact the system administrator

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**RCU-06138: User halted the operation.**

**Cause:** User halted the operation.

**Action:** Please click continue or restart the operation

**Level:** 1

**Type:** ERROR

**Impact:** Installation



---

## REP-00001 to REP-80012

**REP-00001: The Oracle Reports Builder message file cannot be found.**

**Cause:** The file of error messages could not be opened or an internal error occurred while opening it.

**Action:** Reinstall Oracle Reports Builder or contact Oracle Support Services for assistance.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00002: The string from the message file cannot be retrieved.**

**Cause:** Oracle Reports Builder could not retrieve the necessary error message or string.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00003: Global preference file cannot be opened.**

**Cause:** The global preference file could not be opened. This is just a warning, so the product will continue to run even if this occurs. The possible causes of this error include the following: Case 1: The file was not found under the specified name in the specified location. Case 2: Lack of necessary privileges to open the file. Case 3: A system error made it impossible to open the file.

**Action:** Take the following actions to correct this error: If Case 1: Verify that the file named prefs.ora is stored in the appropriate directory. For more information, contact the database administrator. If Case 2: Verify privileges necessary to access the file, and change privileges accordingly. If Case 3: Consult the operating system documentation or the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00004: User preference file cannot be opened.**

**Cause:** The local (customized) preference file could not be opened. This is just a warning, so the product will continue to run even if this occurs. The possible causes of this error include the following: Case 1: The file was not found under the

---

specified name in the specified location. Case 2: Lack of necessary privileges to open the file. Case 3: A system error made it impossible to open the file.

**Action:** Take the following actions to correct this error: If Case 1: Verify the file prefs.ora is located in the home directory, and change the directory and/or file name as appropriate. If Case 2: Verify privileges necessary to access the file, and change privileges accordingly. If Case 3: Consult the operating system documentation or contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00005: A syntax error exists at line {0} in global preference file.**

**Cause:** One or more of the preferences in the global preference file was specified incorrectly on the line number shown in the message. The most likely cause of this error is that the file has been edited and one or more preferences incorrectly specified. As a result, the Oracle Reports Builder will ignore the incorrectly specified preferences.

**Action:** Edit the global preference file and ensure that all preferences are correctly specified, and make the necessary updates.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00006: A syntax error exists at line {0} in user preference file.**

**Cause:** One or more of the preferences in the user preference file was specified incorrectly on the line number shown in the message. The most likely cause of this error is that the file has been edited and one or more preferences incorrectly specified. As a result, the Oracle Reports Builder will ignore the incorrectly specified preferences.

**Action:** Edit the global preference file and ensure that all preferences are correctly specified. If they are not, make the necessary updates.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00007: The user preference file cannot be written to.**

**Cause:** An attempt was made to save preferences and the user preference file could not be written. The possible causes of this error include the following: Case 1: Lack of necessary privileges to write the file. Case 2: A system error made it impossible to write the file.

**Action:** Take the following actions to correct this error: If Case 1: Verify privileges necessary to write the file, and change the privileges accordingly. If Case 2: Consult the operating system documentation or contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00008: An unexpected memory error occurred while initializing preferences.**

---

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Memory

**REP-00058: Data passing to a remote Reports Server is not supported.**

**Cause:** A record group was passed to a report to be run remotely.

**Action:** Do not specify a Reports Server when passing a record group.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-00059: Resources for subcomponent {0} cannot be located.**

**Cause:** One of the subcomponents of the Oracle Reports Builder could not locate its resource file. Possible causes of this error include: Case 1: The resource file does not exist. Case 2: The resource file is in the wrong place. Case 3: The environment is not configured properly.

**Action:** Take the following actions to correct this error: If Case 1: Verify that the resource files are present. If Case 2: Verify that the resource files are in the proper directory. If Case 3: Verify that the environment is set correctly. On UNIX, verify that the proper environment variable is set; on Windows, check oracle.ini.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00060: A synchronous job cannot be run concurrently with another report.**

**Cause:** An attempt was made to run a report initiated by Forms Runtime and requiring data passed from that tool, but one or more other reports are running or queued to run. Reports requiring passed data must be run immediately.

**Action:** Wait for all other reports currently listed in the Reports Server queue to run, then rerun report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00061: An internal error occurred - rxmobfree: reference count is zero.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00062: An internal error occurred - rxmobnew: size mismatch.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00063: An internal error occurred - rxmobnew: memory manager mismatch.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Memory

**REP-00064: An internal error occurred - rxmobnew: type mismatch.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00065: A virtual memory system error occurred.**

**Cause:** Oracle Reports Builder has encountered a memory error.

**Action:** Make note of the error-specific code and contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Memory

**REP-00066: An error occurred executing the CA utility.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00067: The value for keyword STYPE is invalid.**

**Cause:** In Reports Converter, an invalid value was provided for the STYPE keyword.

**Action:** Check the syntax of the keyword. Valid values are DATABASE, REXFILE, RDFFILE, PLLDB, PLLFILE, or PLDFILE. For more information, see the Command Line Keywords appendix in the Publishing Reports to the Web manual.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00068: The value for DTYPE is invalid.**

**Cause:** In Reports Converter, an invalid value was provided for the DTYPE keyword.

---

**Action:** Check the syntax of the keyword. Valid value are DATABASE, REXFILE, RDIFFILE, REPFIL, TDFFILE, PLLDB, PLLFILE, PLXFILE, or PLDFILE. For more information, see the Command Line Keywords appendix in the Publishing Reports to the Web manual.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00069: An internal error occurred**

**Cause:** An Oracle Reports Builder internal code error occurred.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00071: The SSL context cannot be allocated.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00072: The NNIT interface cannot be initialized.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00073: An unknown product cannot be run.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00074: An attempt to run another product using SSL failed.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00075: An error occurred when running the called Oracle component,**

---

**Cause:** Oracle Reports Builder encountered an error after calling Forms Runtime or Graphics Runtime. The accompanying error message displays the error encountered by the called application.

**Action:** Resolve the error encountered by the called application and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00076: An internal failure occurred in product integration.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00077: The column in query {0} too long for data passing.**

**Cause:** An attempt was made to pass data to a column of excessive size (likely a LONG column).

**Action:** Remove the column from the report definition and the calling document's definition.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-00078: A single process integration was invoked with BATCH=NO.**

**Cause:** An attempt was made to invoke Oracle Reports Builder specifying BATCH=NO with executable in which Oracle Reports Builder is linked with another product.

**Action:** Use an executable which integrates using multiple processes, or specify BATCH=YES.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**REP-00079: Value for keyword OVERWRITE is invalid.**

**Cause:** In Reports Converter, an invalid value was specified for the OVERWRITE keyword.

**Action:** Reenter the command, specifying a value of YES, NO, or PROMPT for the OVERWRITE keyword.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00080: The specified value is invalid.**

---

**Cause:** In Reports Converter, OVERWRITE=PROMPT was specified on the command line, then a value other than YES or NO was entered when prompted.

**Action:** Specify a value of YES or NO at the prompt, or CANCEL the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00081: An error occurred during the file I/O operation.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00082: An error occurred executing the SCA utility.**

**Cause:** The possible causes of this error include the following: Case 1: The initialization file is not current. Case 2: An abnormal condition.

**Action:** Take the following actions to correct this error: If Case 1: Ensure that the directory where the report is located is defined in the REPORTS\_PATH located in \$ORACLE\_HOME/bin/reports.sh. If Case 2: For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00083: The value for keyword DUNIT is invalid.**

**Cause:** In Reports Converter, an invalid value was specified for the DUNIT keyword.

**Action:** Check the syntax of the keyword. Valid values are CENTIMETER, CHARACTER, INCH, or POINT. For more information, see the Command Line Keywords appendix in the Publishing Reports to the Web manual.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00084: The value for keyword PAGESIZE is invalid.**

**Cause:** In Reports Converter, an invalid value was specified for the PAGESIZE keyword.

**Action:** Check the syntax and value of the keyword. Valid syntax is <width>x<height>. For more information, see the Command Line Keywords appendix in the Publishing Reports to the Web manual.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00085: The value for keyword FORMSIZE is invalid.**

---

**Cause:** In Reports Converter, an invalid value was specified for the FORMSIZE keyword.

**Action:** Check the syntax and value of the keyword. Valid syntax is &lt;width>x&lt;height>. For more information, see the Command Line Keywords appendix in the Publishing Reports to the Web manual.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00086: DUNIT must be different than source report's unit of measurement.**

**Cause:** In Reports Converter, an invalid value was specified for the DUNIT keyword that was in the same unit of measurement as the report to be converted.

**Action:** Check the syntax and value of the keyword. For more information, see the Command Line Keywords appendix in the Publishing Reports to the Web manual.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00087: The value for keyword DESTYPE is invalid.**

**Cause:** In Reports Runtime, an invalid value was specified for the DESTYPE keyword.

**Action:** Check the syntax and value of the keyword. Valid values are SCREEN, FILE, PRINTER, MAIL, SYSOUT, or PREVIEW. For more information, see the Command Line Keywords appendix in the Publishing Reports to the Web manual.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00088: The value for keyword ONSUCCESS is invalid.**

**Cause:** An invalid value was specified for the ONSUCCESS keyword.

**Action:** Specify COMMIT, ROLLBACK, or NOACTION either in the Runtime Settings tab of the Tools Options dialog or on the command line. To check the command line syntax, see the Command Line Keywords appendix in the Publishing Reports to the Web manual.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00089: The value for keyword ONFAILURE is invalid.**

**Cause:** An invalid value was specified for the ONFAILURE keyword.

**Action:** Specify COMMIT, ROLLBACK, or NOACTION either in the Runtime Settings tab of the Tools Options dialog or on the command line. To check the command line syntax, see the Command Line Keywords appendix in the Publishing Reports to the Web manual.

**Level:** 1

**Type:** ERROR



---

**Impact:** Other

**REP-00090: The value for keyword ACCESS is invalid.**

**Cause:** For Oracle Reports Builder, an invalid value was specified for the ACCESS keyword.

**Action:** Specify FILE or DATABASE. To check the command line syntax, see the Command Line Keywords appendix in the Publishing Reports to the Web manual.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00091: The value for parameter {0} is invalid.**

**Cause:** An invalid value was specified for the named parameter. For example, in the Reports Runtime command string, a character value was provided for a parameter with a data type of Number.

**Action:** Retry the operation, specifying a valid value for the parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00092: Version 1.1 LANGUAGE argument not supported. Use Oracle National Language environment variable instead**

**Cause:** For Oracle Reports Builder or Runtime, the LANGUAGE keyword was included in the command line string.

**Action:** Remove the LANGUAGE argument string from the command string, and set the Oracle National Language environment variable NLS\_LANG to the appropriate value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00094: FORMSIZE must be 80x24 if DUNIT is Character.**

**Cause:** While using Reports Converter with DUNIT=Character, a Parameter Form size was specified that was not equal to 80x24.

**Action:** The character-mode Parameter Form size must be 80x24. Either specify a FORMSIZE of 80x24 when DUNIT=Character, or do not specify a FORMSIZE.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00095: The value for keyword ORIENTATION is invalid.**

**Cause:** An invalid value was specified for the ORIENTATION keyword.

**Action:** Specify DEFAULT, LANDSCAPE, or PORTRAIT either in the Runtime Settings tab of the Tools Options dialog box or on the command line. To check the command line syntax, see the Command Line Keywords appendix in the Publishing Reports to the Web manual.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-00096: The value for keyword MODE is invalid.**

**Cause:** An invalid value was specified for the MODE keyword.

**Action:** Specify DEFAULT, BITMAP, or CHARACTER either in the Runtime Settings tab of the Tools Options dialog or on the command line. To check the command line syntax, see the Command Line Keywords appendix in the Publishing Reports to the Web manual.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00097: The value for keyword TRACEMODE is invalid.**

**Cause:** Either an invalid or no value was specified for the TRACEMODE keyword, or keywords were specified out of order on the command line without being named.

**Action:** Either specify Append or Replace for Trace Mode in the Trace Settings dialog or TRACE\_APPEND or TRACE\_REPLACE on the command line, or check the syntax of the command. To check the command line syntax, see the Command Line Keywords appendix in the Publishing Reports to the Web manual.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00098: The report was not run as it was canceled in the Parameter Form.**

**Cause:** The report was not executed because Cancel instead of Run Report was selected in the Runtime Parameter Form.

**Action:** No action is necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00099: The report is aborted upon user request.**

**Cause:** The report was stopped while it was executing.

**Action:** No action is necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00100: The file pointer in file {0} cannot be positioned.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

---

**REP-00101: File {0} cannot be read.**

**Cause:** Oracle Reports Builder tried to read a file, which could be opened but not read.

**Action:** Consult the operating system documentation or contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00102: File {0} cannot be written to.**

**Cause:** Oracle Reports Builder tried to write the file shown in the message and could not. The possible causes of this error include the following: Case 1: Lack of necessary privileges to write the file. Case 2: The file system does not have enough room for the file. Case 3: A system error made it impossible to open the file.

**Action:** Take the following actions to correct this error: If Case 1: Verify the privileges necessary to write the file, and change privileges accordingly. If Case 2: Make more room by deleting unnecessary files or expanding storage. If Case 3: Consult the operating system documentation or contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00103: File {0} cannot be closed.**

**Cause:** Oracle Reports Builder tried to close the file, but was unsuccessful. The most likely reason is that a system error made it impossible to close the file.

**Action:** Consult the operating system documentation or contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00104: File {0} cannot be deleted.**

**Cause:** Oracle Reports Builder tried to delete the file shown, but was unsuccessful. The most likely reason is that a system error made it impossible to delete the file.

**Action:** Consult the operating system documentation or contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00105: File {0} cannot be locked in exclusive mode.**

**Cause:** Oracle Reports Builder tried to lock the file shown, but was unsuccessful. The most likely reason is that a system error made it impossible to lock the file.

**Action:** Consult the operating system documentation or contact the system administrator.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-00106: File {0} cannot be locked in shared mode.**

**Cause:** Oracle Reports Builder tried to lock the file shown, but was unsuccessful. The most likely reason is that a system error made it impossible to lock the file.

**Action:** Consult the operating system documentation or contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00107: File {0} cannot be opened: bad name.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00108: File {0} cannot be found.**

**Cause:** Oracle Reports Builder tried to access the file shown, but could not find it.

**Action:** Verify the file name. Specify a directory before the file name, or modify the REPORTS\_PATH environment variable to include the directory where the file is located.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00109: There are too many files open.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00110: File {0} cannot be opened.**

**Cause:** Oracle Reports Builder tried to open the file shown and could not. The possible causes of this error include the following: Case 1: The file was not found under the specified name in the specified location. Case 2: Lack of necessary privileges to open the file. Case 3: A system error made it impossible to open the file.

**Action:** Take the following actions to correct this error: If Case 1: Verify that the file is stored in the specified directory under the specified name. If it is not, change the directory and/or file name as appropriate. If Case 2: Verify the privileges necessary to open the file, and change the privileges accordingly. If Case 3: Consult the operating system documentation or contact the system administrator.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-00111: Directory {0} is protected.**

**Cause:** Oracle Reports Builder attempted to read from or write to a directory that is read and write protected.

**Action:** Change the permissions on the directory as necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00112: File {0} is write-protected.**

**Cause:** Oracle Reports Builder attempted to write to a file that is write-protected.

**Action:** Change the permissions of the file as necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00113: File {0} is read-protected.**

**Cause:** Oracle Reports Builder attempted to read a file that is read-protected.

**Action:** Change the permissions of the file as necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00114: File {0} no longer exists.**

**Cause:** Oracle Reports Builder attempted to access a file that no longer exists.

**Action:** Remove the call to the file, re-create the file, or specify a different file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00115: Directory {0} cannot be read.**

**Cause:** Oracle Reports Builder attempted to read from or write to a directory that does not exist.

**Action:** Verify that the specified directory exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00116: Directory {0} cannot be accessed.**

**Cause:** Oracle Reports Builder could not access the specified directory.

**Action:** Consult the system administrator.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-00117: Exit to the host operating system failed.**

**Cause:** Oracle Reports Builder attempted to exit the program and return control to the host operating system.

**Action:** No action is necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Operating System

**REP-00118: A temporary file cannot be created.**

**Cause:** Oracle Reports Builder tried to create a temporary file but could not do so. The possible causes of this error include the following: Case 1: The environment variable that determines in what directory to create temporary files is set to an invalid directory. Case 2: There is not enough free space on the disk to create the temporary file. Case 3: A temporary file that cannot be modified already exists.

**Action:** Take the following actions to correct this error: If Case 1: Set the environment variable for temporary files to a valid directory. If Case 2: Free up some space on the disk. If Case 3: Remove the existing temporary file, if possible.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00119: File link boilerplate {0}'s Source Filename {1} cannot be found.**

**Cause:** Oracle Reports Builder could not find the source file specified in the Source Filename property for the file link boilerplate object. The possible causes of this error include the following: Case 1: The file was not found under the specified name in the specified location. Case 2: Lack of necessary privileges to open the file. Case 3: A system error made it impossible to open the file.

**Action:** Take the following actions to correct this error: If Case 1: Verify that the file is stored in the specified directory under the specified name. If it is not, change the directory and/or file name as appropriate. If Case 2: Verify the privileges necessary to open the file, and change the privileges accordingly. If Case 3: Consult the operating system documentation or contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00120: Graph {0}'s associated document {1} cannot be found.**

**Cause:** Oracle Reports Builder was unable to find the graph document. The possible causes of this error include the following: Case 1: The graph document was not found under the specified name in the specified location. Case 2: Lack of necessary privileges to open the graph document. Case 3: A system error made it impossible to open the graph document.

**Action:** Take the following actions to correct this error: If Case 1: Verify that the graph document is stored in the specified directory under the specified name. If it is not, change the directory and/or file name as appropriate. If Case 2: Verify the privileges necessary to open the graph document, and change the privileges

---

accordingly. If Case 3: Consult the operating system documentation or contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00124: The temporary file cannot be written to.**

**Cause:** Oracle Reports Builder tried to write to the temporary file but could not do so.

**Action:** Free up some space on the disk.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00125: An internal error occurred: Unable to load NLS character set.**

**Cause:** ORA\_NLS was not set, or the directory to which it points does not exist.

**Action:** Set ORA\_NLS to point to the NLS directory containing character set files.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00126: File {0} is not a known type to Oracle Reports Builder. No file conversion can be performed. Check in anyway?**

**Cause:** An attempt was made to check in a file of a type that Oracle Reports Builder cannot convert. For example, Oracle Reports Builder cannot convert a Form Builder (FMB) file.

**Action:** To continue checking in, click Yes. Otherwise, click No and nothing will be checked in.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00127: File {0} is not a known type to Oracle Reports Builder. No file conversion can be performed. Check out anyway?**

**Cause:** An attempt was made to check out a file of a type that Oracle Reports Builder cannot convert. For example, Oracle Reports Builder cannot convert a Form Builder (FMB) file.

**Action:** To continue checking out, click Yes. Otherwise, click No and nothing will be checked out.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00128: There are unsaved changes in file {0}. Save before checkin?**

**Cause:** An attempt was made to check in a file that is currently open and there are unsaved changes.

---

**Action:** To save and check in the file, click Yes. Click No to check in the file without the changes. Otherwise, click Cancel and nothing will be checked in.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00129: There are unsaved changes in file {0}. Check out anyway?**

**Cause:** An attempt was made to check out a file that is currently open and there are unsaved changes.

**Action:** To check out the file, click Yes. Note that this will overwrite all the changes made to this file. Otherwise, click No and nothing will be checked out.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00130: A module saved in the database cannot be checked in. Save it to file before checkin.**

**Cause:** Checking in a module saved in the database is not supported.

**Action:** Save the module to the filesystem first and then check it in again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00131: The communication layer cannot be initialized.**

**Cause:** The required communication files were not found.

**Action:** Check the installation and setup and update with the latest patch.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00132: A JVM cannot be started.**

**Cause:** Oracle Reports could not start up the required JVM services.

**Action:** Check the installation and setup and update with the latest patch.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00133: Java Classes cannot be found.**

**Cause:** Some required files were not found. This could be caused by an invalid installation or missing files.

**Action:** Check the installation and setup and update with the latest patch.

**Level:** 1

**Type:** ERROR

**Impact:** Other



---

**REP-00150: There are too many arguments.**

**Cause:** More than the allowable number of arguments for the command were entered.

**Action:** Check the syntax of the command. For more information, see the Command Line Keywords appendix in the Publishing Reports to the Web manual. Reenter the command correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00151: Duplicate arguments are specified for keyword {0}.**

**Cause:** An argument was entered more than once for the keyword shown. The possible causes of this error include the following: Case 1: A positional argument was entered for the keyword and then the keyword was entered with another argument. Case 2: The same keyword was entered twice (for example, KEYWORD1=YES and KEYWORD1=NO).

**Action:** Check the syntax of the command (see the Command Line Keywords appendix in the Publishing Reports to the Web manual). Take the following actions to correct this error: If Case 1: Reenter the command with just the positional argument or just the keyword argument. If Case 2: Reenter the command specifying the keyword only once.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00152: A positional argument is specified after a keyword.**

**Cause:** On the command line, an argument was entered without its keyword after being an argument was entered with its keyword. Once a keyword is used on the command line, all subsequent arguments must use keywords as well.

**Action:** Reenter the command making sure that no positional arguments (arguments where the keyword is implicit) are specified after arguments with keywords.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00153: Multiple values are not allowed for keyword {0}.**

**Cause:** In the command, more than the allowable number of values for the keyword were entered. For example, KEYWORD=(A, B) was entered, where KEYWORD accepts only a single value.

**Action:** Check the syntax of the command. For more information, see the Command Line Keywords appendix in the Publishing Reports to the Web manual. Reenter the command without the extra values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00154: The command file cannot be opened.**

---

**Cause:** A command referenced the command file shown and the file could not be opened. The possible causes of this error include the following: Case 1: The file was not found under the specified name in the specified location. Case 2: Lack of necessary privileges to open the file. Case 3: A system error made it impossible to open the file.

**Action:** Take the following actions to correct this error: If Case 1: Verify that the file is stored in the specified directory under the specified name. If it is not, change the directory and/or file name or move the file into the specified directory. If Case 2: Verify the privileges necessary to access the file, and change the privileges accordingly. If Case 3: Consult the operating system documentation or contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00155: The value for keyword {0} is invalid.**

**Cause:** The value entered for the keyword shown was not a valid value.

**Action:** Check the syntax of the keyword. For more information, see the Command Line Keywords appendix in the Publishing Reports to the Web manual. Reenter the command with the appropriate value for the keywords.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00156: The value for keyword DESTYPE is invalid.**

**Cause:** In Reports Runtime, an invalid value was provided for the DESTYPE keyword.

**Action:** Check the syntax of the keyword. Valid values are SCREEN, FILE, PRINTER, MAIL or SYSOUT. For more information, see the Command Line Keywords appendix in the Publishing Reports to the Web manual. Reenter the command with the appropriate value for the keywords.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00157: The value for {0} must be either YES or NO.**

**Cause:** A value other than YES or NO was entered for the keyword shown, and the keyword only accepts YES or NO.

**Action:** Reenter the command using a value of YES or NO for the keyword shown.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00158: The command line keyword {0} is unknown.**

**Cause:** The referenced string was entered as a keyword, but there is no such keyword.

---

**Action:** Check the syntax of the command. For more information, see the Command Line Keywords appendix in the Publishing Reports to the Web manual. Reenter the command with the appropriate value for the keywords.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00159: A syntax error exists on the command line.**

**Cause:** The string entered on the command line could not be parsed. The most likely cause of this error is that quotation marks or parentheses were entered without matching end quotation marks or parentheses.

**Action:** Check the syntax of the command. For more information, see the Command Line Keywords appendix in the Publishing Reports to the Web manual. Reenter the command using the appropriate syntax.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00160: A syntax error exists in the command file.**

**Cause:** Something entered in the command file could not be parsed. The most likely cause of this error is that quotation marks or parentheses were entered without matching end quotation marks or parentheses.

**Action:** Check the syntax of the commands. For more information, see the Command Line Keywords appendix in the Publishing Reports to the Web manual. Edit the file and modify the commands as necessary to correct the commands.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00161: No command-line arguments are specified.**

**Cause:** Reports Converter was invoked without specifying any command-line arguments.

**Action:** Specify the appropriate command-line arguments (for example, SOURCE, DEST) for Reports Converter. For more information, see the Command Line Keywords appendix in the Publishing Reports to the Web manual.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00162: The value for keyword SHOWWINDOW is invalid.**

**Cause:** The value specified for the SHOWWINDOW keyword was not valid.

**Action:** Check the syntax of the keyword. Valid values are DEFAULT, WIZARD, and PREVIEWER. For more information, see the Command Line Keywords appendix in the Publishing Reports to the Web manual.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**REP-00163: The value for keyword DESTYPE is invalid.**

**Cause:** The value specified for the DESTYPE keyword was not valid for the Reports Server.

**Action:** Check the syntax of the keyword. Valid values are FILE, PRINTER, MAIL, or CACHE.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00164: The value for keyword PARAMFORM is invalid.**

**Cause:** The value specified for the PARAMFORM keyword was not valid.

**Action:** Reenter the command, specifying a value of YES, NO, or HTML[action] for the PARAMFORM keyword.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00165: The value for keyword SITENAME is missing.**

**Cause:** No value was specified for the SITENAME keyword. A value is required for SITENAME in order to schedule a report.

**Action:** Specify a WEBDB site name for the keyword SITENAME.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00166: Read/write of the specified directory is not allowed.**

**Cause:** Oracle Reports attempted to read from or write to a directory without read/write privileges.

**Action:** Check the command line options to identify the directory name. Add the directory to REPORTS\_PATH, ORACLE\_PATH, or the sourceDir property in the engine element in the server configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00171: Output from the remote server cannot be retrieved.**

**Cause:** An error occurred when retrieving output from the remote server.

**Action:** Verify that the file is accessible, and that the server is set to allow retrieving outputs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00172: The value for keyword SERVER is missing.**

---

**Cause:** No value was specified for the mandatory keyword SERVER.

**Action:** Provide a valid argument for the keyword SERVER and rerun the command.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00173: The value for keyword SHOWJOBS is invalid.**

**Cause:** In the Reports Queue Viewer, an argument provided in command line for the SHOWJOBS keyword was not valid.

**Action:** Reenter the command, specifying a value of PAST, CURRENT or FUTURE for the SHOWJOBS keyword.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00174: An internal error occurred while obtaining the Reports Server queue information.**

**Cause:** The Reports Server did not return valid information about its queue to the queue viewer. This could be caused by one of the following reasons: Case 1: The connection to the Reports Server unexpectedly went down. Case 2: The Reports Server is in an unstable state, or has been shut down.

**Action:** Verify that the Reports Server is running. Contact the system administrator and retry the command after verifying that the Reports Server is running. If this problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00175: An internal error occurred while obtaining the Reports Server properties information.**

**Cause:** The Reports Server did not return valid information about its properties to the queue viewer. This could be caused by one of the following reasons: Case 1: The connection to the Reports Server unexpectedly went down. Case 2: The Reports Server is in an unstable state, or has been shut down.

**Action:** Verify that the Reports Server is running. Contact the system administrator and retry the command after verifying that the Reports Server is running. If this problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00176: Server {0} is shutting down.**

**Cause:** A report cannot be submitted when the specified Reports Server is shutting down.

**Action:** Submit to another Reports Server or wait until the Server is back up.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-00177: An error occurred while running in a remote server.**

**Cause:** An attempt to run a command line in the remote server failed.

**Action:** Check the command line.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00178: Reports Server {0} cannot establish connection.**

**Cause:** A proper connection could not be established to the specified Reports Server.

**Action:** Check the network and check the status of the Reports Server in question.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00179: Report execution terminated unexpectedly while running.**

**Cause:** The Reports Engine has crashed while running.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00180: The report has been canceled from the Reports Server.**

**Cause:** The report was stopped while it was executing or removed from the queue before it was started.

**Action:** No action is necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00181: An error occurred reading or writing the configuration file for the Reports Server.**

**Cause:** The configuration file cannot be opened, or its content is incomprehensible.

**Action:** Check the configuration file and its access rights. Restart the server.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**REP-00182: A syntax error occurred on command line for the Reports Server.**

**Cause:** The string entered on the command line could not be parsed. The most likely cause of this error is that quotation marks or parentheses were entered without matching end quotation marks or parentheses.

---

**Action:** Check the syntax of the command. For more information, see the Command Line Keywords appendix in the Publishing Reports to the Web manual. Reenter the command using the appropriate syntax.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00183: TNSNAME must be provided to start up the Reports Server.**

**Cause:** An attempt was made to start up the Reports Server without specifying the TNSNAME to which the Server should listen.

**Action:** Specify the TNSNAME as a command-line argument.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00184: The specified MAXCONNECTS is out of range.**

**Cause:** The MAXCONNECTS value specified is out of range for this platform. MAXCONNECTS must be at least 2, and cannot exceed 4096, and on some platforms the limit is even lower.

**Action:** Specify an appropriate value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00185: Bad load arguments were supplied when starting up the Reports Server.**

**Cause:** Inconsistent values were specified among MAXCONNECTS, MINLOAD, MAXLOAD, and INITLOAD.

**Action:** Verify that  $0 \leq \text{MINLOAD} \leq \text{INITLOAD} \leq \text{MAXLOAD} \leq \text{MAXCONNECTS}$ .

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00186: A daemon cannot listen to the port.**

**Cause:** Another daemon may be running that is already listening to the port.

**Action:** No action is necessary. Since a daemon is already running, submit the report to be run.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00187: A daemon cannot start up the engine.**

**Cause:** A daemon cannot start up the engine executable and communicate with it. This is most likely an installation issue.

**Action:** Verify that the installation is done properly.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00188: Reports Server only accepts batch jobs.**

**Cause:** A job was submitted to the Reports Server where BATCH=NO, DESTYPE=SCREEN, DESTYPE=PREVIEW, or DESTYPE=SYSOUT.

**Action:** These settings are not allowed. Change the command line accordingly.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00189: The Reports Server cache cannot be written to.**

**Cause:** Reports Server failed to write to the cache directory.

**Action:** Verify that the cache directory is specified in the server configuration file and it is writable.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00190: A report cannot be run to screen in the background.**

**Cause:** The report was specified to be run in the background, with DESTYPE=SCREEN. A report cannot run in the background while having its output sent to the screen.

**Action:** To send the output to the screen, run it in the foreground. To run the report in the background, specify a different DESTYPE.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00194: A character report cannot be run in bitmap mode using this executable.**

**Cause:** Oracle Reports attempted to use the character-mode executable to run a character-mode report with MODE=BITMAP. This is not allowed.

**Action:** Change the value of the MODE keyword to match the mode of the executable.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00195: A report cannot be run in bitmap mode to screen using this executable.**

**Cause:** Oracle Reports attempted to use the character-mode executable to run a bitmapped report to the screen. This is not allowed.

**Action:** Run the report using BATCH=YES or use a bitmapped executable.

**Level:** 1

**Type:** ERROR



---

**Impact:** Other

**REP-00196: The report cannot be run in the background.**

**Cause:** BACKGROUND=YES was specified under one of the following conditions, none of which are allowed: Case 1: Running the report from the designer. Case 2: BATCH=YES. Case 3: Running the report using the packaged procedure srw.run\_report. Case 4: The platform on running the report does not support spawning of another process.

**Action:** Ensure that BACKGROUND=NO when any of the above condition are true.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00197: BATCH=YES or BACKGROUND=YES must be specified on the command line when running a bitmapped report.**

**Cause:** Oracle Reports attempted to run a bitmapped report using the character-mode executable in the foreground or during an interactive session. This is not supported.

**Action:** To run a bitmapped report using the character-mode executable, specify either BATCH=YES or BACKGROUND=YES (unlike BATCH=YES, this setting provides access to the Runtime Parameter Form).

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00200: Enough memory cannot be allocated.**

**Cause:** Oracle Reports Builder cannot obtain enough memory from the system to complete the current task.

**Action:** Make more memory available, if possible, or ask the system administrator for assistance.

**Level:** 1

**Type:** ERROR

**Impact:** Memory

**REP-00201: A zero or negative block size was requested.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00202: A null pointer cannot be freed.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Other

**REP-00203: A null pointer was passed as a handle.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00204: The handle does not point into an mp block.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00205: There are too many simultaneous locks on one object.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00206: A null cache pointer is passed to virtual memory routine.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Memory

**REP-00207: The requested block is larger than virtual memory space.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Memory

**REP-00208: rmaloc was not given a function identifier.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00209: rmaloc was not given a structure identifier.**

---

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00210: An illegal operation was requested on a locked handle.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00211: A handle cannot be used after freeing it.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00212: No literal is specified.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00213: An attempt to lock a handle failed.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00214: A virtual memory buffer of size {0} KB cannot be allocated. Try a smaller size.**

**Cause:** Oracle Reports Builder tried to allocate a virtual memory buffer size at or below the number specified for the BUFFERS keyword.

**Action:** Specify a smaller size for BUFFERS, either on the command line or in the Runtime Settings tab of the Preferences dialog box (select Edit, then Preferences), or free up more memory. For command line syntax, see the Command Line Keywords appendix in the Publishing Reports to the Web manual.

**Level:** 1

**Type:** ERROR

---

**Impact:** Memory

**REP-00215: An error occurred locking, dereferencing, or freeing a memory handle.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Memory

**REP-00216: There is insufficient memory to save the report as a JSP or XML.**

**Cause:** The report definition file has exceeded 10 MB. The report cannot be saved as a JSP or XML if it exceeds 10 MB.

**Action:** Reduce the size of the file.

**Level:** 1

**Type:** ERROR

**Impact:** Memory

**REP-00230: An error occurred while starting a thread.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00231: An error occurred while posting thread message.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Threads

**REP-00232: An error occurred while getting thread message.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Threads

**REP-00235: The Security Server TNSNAME is not provided in the config file.**

**Cause:** Security Server TNSNAME must be specified in config file on security mode"

**Action:** Specify Security Server TNSNAME in the config file by using the keyword 'securitytnsname'.

**Level:** 1

**Type:** ERROR

---

**Impact:** Security

**REP-00236: The Security Server cannot be connected.**

**Cause:** An abnormal condition was encountered.

**Action:** Contact the system administrator. For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Security

**REP-00238: Authentication failed.**

**Cause:** The system userid/password is invalid or does not have privilege to run the report.

**Action:** Check the system userid/password to verify that it is correct or contact the system administrator to grant the necessary privilege.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**REP-00239: The Security server authentication failed: invalid user name.**

**Cause:** The system user ID is incorrect.

**Action:** Check the system user ID to verify that it is correct or contact the system administrator about the system user ID.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**REP-00240: The Security Server authentication failed: invalid password.**

**Cause:** The password for the system user ID is incorrect.

**Action:** Check the system user ID password to verify that it is correct or contact the system administrator about the system user ID password.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**REP-00241: The Security Server authentication failed: no privilege on the Reports Server.**

**Cause:** The system user ID does not have privilege to access the Reports Server.

**Action:** Contact the system administrator about the system user ID's privilege on the Reports Server.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**REP-00242: The Security Server authentication failed: no privilege on the printer.**

**Cause:** The system user ID does not have privilege to access the printer.

---

**Action:** Contact the system administrator about the system user ID's privilege on the printer.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**REP-00243: The Security Server authentication failed: no privilege on the module.**

**Cause:** The system user ID does not have privilege to access the module.

**Action:** Contact the system administrator about the system user ID's privilege on the module.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**REP-00244: The Security Server authentication failed: no privilege of this access type.**

**Cause:** The system user ID does not have privilege of this access type.

**Action:** Contact the system administrator about the system user ID's privilege of this access type.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**REP-00245: The Security Server authentication failed: no privilege of this output type.**

**Cause:** The system user ID does not have privilege of this output type.

**Action:** Contact the system administrator about the system user ID's privilege of this output type.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**REP-00246: The Security Server authentication failed: no privilege for the given time.**

**Cause:** The system user ID does not have privilege for the given time.

**Action:** Contact the system administrator about the system user ID's privilege for the given time.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**REP-00247: The Security Server authentication failed: no privilege for the given date.**

**Cause:** The system user ID does not have privilege for the given date.

**Action:** Contact the system administrator about the system user ID's privilege for the given date.

---

**Level:** 1

**Type:** ERROR

**Impact:** Security

**REP-00250: A symbol table overflow occurred.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00251: The identifier does not match a defined symbol.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00252: The path specified by environment variable {0} is too long and will be ignored.**

**Cause:** The path specified by the environment variable is too long.

**Action:** Shorten the length of the designated path.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00253: The total length of the search paths is too long and will be truncated.**

**Cause:** The combined length of search paths in the path environment is too long. The combined length cannot exceed 255 characters.

**Action:** Shorten the length of one or more paths in the path environment.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00300: An Oracle error occurred.**

**Cause:** Oracle Reports Builder encountered an Oracle error.

**Action:** Scroll through the error message to see where the error occurred and, if possible, fix it. Otherwise, contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00301: The SELECT statement may not contain an INTO clause.**

**Cause:** An INTO clause was entered in a SELECT statement, which is not allowed in Oracle Reports Builder.

---

**Action:** Remove the INTO clause.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00302: Parameter {0} cannot be found in the report.**

**Cause:** Oracle Reports referenced a parameter that is not defined in the report. The most likely cause is that a parameter was deleted but not all references to it were deleted.

**Action:** Delete all references to the deleted parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00303: The statement entered is not a SELECT statement.**

**Cause:** What was entered in the SELECT Statement field is something other than a SELECT statement. The possible causes of this error include the following: Case 1: Something besides a SELECT statement was entered in the SELECT Statement field. Case 2: An external query was referenced that did not contain a SELECT statement.

**Action:** Take the following actions to correct this error: If Case 1: Enter a valid SELECT statement. If Case 2: Modify the external query or reference another external query.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00304: & in SELECT statement was not followed by a valid lexical parameter.**

**Cause:** An ampersand (&) appears in the SELECT statement by itself. The possible causes of this error include the following: Case 1: A lexical reference either left out the name of the column or parameter altogether or there is a space between the ampersand and the name of the column or parameter. Case 2: An ampersand was accidentally typed in the SELECT statement.

**Action:** Take the following actions to correct this error: If Case 1: Verify that the column or parameter name immediately follows the ampersand with no spaces in between. If Case 2: Delete the ampersand.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00305: Reference {0} cannot be used as a lexical parameter because it is not a character value.**

**Cause:** An invalid lexical reference appears in the SELECT statement. Lexical references can only be made to parameters or columns containing character data. The possible causes of this error include the following: Case 1: The wrong column or parameter was referenced. Case 2: The reference should be a bind reference, not a lexical reference. Case 3: The parameter or column referenced was created with a non-character data type.



---

**Action:** Take the following actions to correct this error: If Case 1: Change the name that follows the ampersand (&) so it references a parameter or column with a data type of Character. If Case 2: Replace the ampersand (&) with a colon (:) when referencing the parameter or column. If Case 3: Change the data type of the parameter or column to be Character, if appropriate.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00306: The name {0} is not a valid parameter name.**

**Cause:** In making reference to a parameter, an attempt was made to create a parameter with an invalid name. For a bind reference, a parameter definition is automatically created using the name specified in the bind parameter. In this case, Oracle Reports Builder could not create the parameter because the name supplied was not a valid name.

**Action:** Check the naming conventions for data model objects and rules for parameter names. Rename the parameter and change the name in the bind reference.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00307: The SELECT statement may not contain a FOR UPDATE clause.**

**Cause:** A FOR UPDATE clause was entered in the SELECT statement, which is not allowed in Oracle Reports Builder.

**Action:** Remove the FOR UPDATE clause.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00308: An internal error occurred: Unknown column type.**

**Cause:** The possible causes of this error include the following: Case 1: An attempt was made to display the value of a column using SRW.MESSAGE, but the column's data type (for example, LONG, LONG RAW, ROWID) is not supported for that operation. Case 2: An attempt was made to pass the value of a column to Forms Runtime or Graphics Runtime as a parameter, but the column's data type (for example, LONG, LONG RAW, ROWID) is not supported for that operation.

**Action:** Do not attempt to display or pass this column's value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00309: The specified database cannot connect after three attempts. Access denied.**

**Cause:** Case 1: Some part of the logon string entered was incorrect. After three failed attempts, Oracle Reports Builder displays a dialog box with this message. Case 2: The NLS\_LANG environment variable value may be invalid.

---

**Action:** Case 1: Accept the dialog box. Confirm the logon information with the system administrator, if necessary. Go back into Oracle Reports Builder and try connecting to Oracle again. If the problem persists, the system administrator may need to create a new Oracle logon. Case 2: Verify the NLS\_LANG value is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00310: An error occurred while processing bind variables in a query.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00311: An internal error occurred: Segmented memory used for lexical parameter.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Memory

**REP-00312: An internal error occurred: Error dealing with segmented memory.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00313: An internal error occurred: Fetching data records would cause memory overflow.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**REP-00314: The column name exceeds 256 characters, and no alias is assigned.**

**Cause:** One of the SQL SELECT statements contains an expression that is longer than 256 characters, but has no alias.

**Action:** Edit the SELECT statement and assign an alias to the expression.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**REP-00315: Each SELECT statement must have the same number of columns in a compound query.**

**Cause:** A query with a UNION, INTERSECT, or MINUS set operator was entered in which the SELECT statements in the query do not have the same number of selected columns.

**Action:** Modify the SELECT statements so that they have the same number of columns.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00316: The types of corresponding columns must match in a compound query.**

**Cause:** A query with a UNION, INTERSECT, or MINUS set operator was entered in which corresponding columns have different types. For example, column 1 in the first SELECT statement has data type CHAR, while column 1 in the second SELECT statement has data type NUMBER.

**Action:** Modify the SELECT statements so that all corresponding columns have the same data type.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00320: The database cannot be connected.**

**Cause:** An attempt to connect to the database failed.

**Action:** Recheck the user ID and password and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00321: An internal error occurred: Describe of query failed.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00322: An internal error occurred: Attempt to put back fetched rows failed.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00330: An internal error occurred: Location GET\_REF parameters failed.**

---

**Cause:** A CDE\_MM.GET\_REF call in a query did not specify a parameter list.

**Action:** Add the parameter list to the call in the query's SELECT statement.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00331: The GET\_REF PL/SQL function requires 3 parameters.**

**Cause:** The parameter list of a CDE\_MM.GET\_REF call in a query was incomplete.

**Action:** Add the necessary parameters to the call in the query's SELECT statement.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00332: The GET\_REF PL/SQL function's last parameter must be of type ROWID.**

**Cause:** A parameter of type ROWID was not provided as the last parameter for a GET\_REF function.

**Action:** Check the parameter list and ensure the last parameter is of type ROWID.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00340: The role password cannot be verified, and the report is not opened.**

**Cause:** Incorrect role password. For security reasons, the report cannot be opened.

**Action:** Try opening the report again and type in the correct role password.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00341: The roles specified in the report cannot be set, and the report is not opened.**

**Cause:** The roles specified in the report cannot be set while opening the report. For security reasons, the report cannot be opened.

**Action:** Check role permissions and password.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00342: Roles specified on the command line cannot be set.**

**Cause:** The roles specified on the command line cannot be set.

**Action:** Check role permissions and password.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-00343: Default roles of the current user cannot be set.**

**Cause:** Reports is unable to set the default roles of the current user that has passwords.

**Action:** Do not use default roles with passwords.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00344: The role password was not confirmed correctly.**

**Cause:** The Confirm Password entered is different from the Role Password.

**Action:** Reenter and verify that Confirm Password exactly matches the Role Password.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00345: An empty role and a non-empty password is not valid.**

**Cause:** No role is specified, while role password is specified.

**Action:** Leave all fields empty to not associate a role with this report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00346: The role must be no longer than {0} characters. It will be truncated.**

**Cause:** The role name specified is longer than is allowable. It will be truncated.

**Action:** Specify a shorter role name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00347: The role password must be no longer than {0} characters. It will be truncated.**

**Cause:** The role password specified is longer than is allowable. It will be truncated.

**Action:** Specify a shorter role password.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00348: The role password is incorrect.**

**Cause:** The role password entered was incorrect.

**Action:** Reenter with the correct role password.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00450: PL/SQL error {0} was encountered.**

**Cause:** Oracle Reports Builder encountered the identified PL/SQL error while running a report.

**Action:** Edit and recompile the PL/SQL in the report to avoid this error.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00451: PL/SQL error {0} was encountered. {1}.**

**Cause:** Oracle Reports Builder encountered the identified PL/SQL error while running a report.

**Action:** Edit and recompile the PL/SQL in the report to avoid this error.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00452: PL/SQL error {0} was encountered. {1}. {2}.**

**Cause:** Oracle Reports Builder encountered the identified PL/SQL error while running a report.

**Action:** Edit and recompile the PL/SQL in the report to avoid this error.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00453: PL/SQL error {0} was encountered. {1}. {2}. {3}.**

**Cause:** Oracle Reports Builder encountered the identified PL/SQL error while running a report.

**Action:** Edit and recompile the PL/SQL in the report to avoid this error.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00490: An internal error occurred: Toolkit context unavailable.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00491: Data truncation is possible in column {0}.**

---

**Cause:** The database column's width in the report is defined to be less than its width in the database. This can sometimes occur when the columns in the database are updated subsequent to the report being defined. This warning is raised only when RUNDEBUG is YES.

**Action:** Force the query to be reparsed. One method is to type a space at the end of a line in the SELECT Statement field and then accept the SQL Query Statement dialog.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-00492: The token {0} is unrecognized.**

**Cause:** The SELECT statement entered contains an item that is not part of SQL syntax.

**Action:** Review the SELECT statement and ensure that it follows SQL syntax.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00493: An internal error occurred: Unable to expand lexical references.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00494: An internal error occurred: Unable to process lexical references.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**REP-00495: An internal error occurred: Unable to tokenize the query.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00496: An internal error occurred: Unable to parse the query.**

**Cause:** The SQL statement entered cannot be parsed because it contains an error.

**Action:** Review the SQL statement to ensure correct syntax. For more information, see the SQL Language Reference Manual.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-00497: An internal error occurred: Query failed in rodslt.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00498: The number of columns selected by the query is incompatible with the report definition.**

**Cause:** The query is selecting more columns than the report definition is expecting. This can happen when using an external query and the query has been changed since the report was defined.

**Action:** Update the report definition so that it accepts the changed query. For example, go to the SQL Query Statement dialog for the query that references the changed external query and modify it. Formulas, summaries, and fields that rely on any changed columns may also need to be updated.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00499: Column {0} selected by the query is incompatible with the report definition.**

**Cause:** The column from the database does not match the column in the report definition. The possible causes of this error include the following: Case 1: The definition of the column in the database has changed since the report was defined. Case 2: The report uses an external query and the external query was changed since the report was defined.

**Action:** Take the following actions to correct this error: If Case 1: Update the report definition so that it accepts the changed column. For example, if the data type of the column has changed, reaccept the SQL Query Statement dialog external query so the column in the report definition has its data type updated. Formulas, summaries, and fields that rely on the changed column may also need to be updated. If Case 2: Update the report definition so that it accepts the changed query. For example, reaccept the SQL Query Statement dialog that references the changed external query and accept it. Formulas, summaries, and fields that rely on any changed columns may also need to be updated.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00500: The number entered is out of range.**

**Cause:** The number specified is too large.

**Action:** Check the limits of the field. Look in the chapter where the field is described and enter a number that is within the limits.

**Level:** 1



---

**Type:** ERROR

**Impact:** Other

**REP-00501: The specified database cannot be connected.**

**Cause:** Oracle Reports Builder could not connect to Oracle The possible causes of this error include the following: Case 1: The Oracle database is temporarily unavailable. Case 2: The connect information was not valid.

**Action:** Take the following actions to correct this error: If Case 1: Retry the operation. Contact the system administrator if the problem persists. Note that after three failed attempts, Oracle Reports Builder closes. If Case 2: Verify the connect information, and try to connect again. Note that after three failed attempts, Oracle Reports Builder closes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00502: An error occurred attempting to open terminal file {0}.**

**Cause:** Oracle Reports Builder was unable to open the terminal definition file specified. Either the name of the file was specified incorrectly after the TERM keyword, or the file was not found.

**Action:** Verify the name of the terminal definition file, and its path. If the problem persists, contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00503: The report name is invalid.**

**Cause:** An invalid name was specified for the name of a report.

**Action:** Specify a valid report name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00504: The specified database is not connected.**

**Cause:** An attempt was made to perform an operation that requires a connection to the database, but no database connection was established.

**Action:** Select File, then Connect to connect to the database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00505: The width for this column is not valid.**

**Cause:** The value entered in Width was invalid. The possible causes of this error include the following: Case 1: Zero or a negative number was entered. Width must be greater than zero. Case 2: Something that was not a number was entered. Case 3: For a column of non-numeric data type, a width of the form (x, y) was entered, where x is the precision and y is the scale. This type of Width specification is only valid when the data type is Number.

---

**Action:** Take the following actions to correct this error: If Case 1: Enter a number greater than zero. If Case 2: Enter a number greater than zero. If Case 3: Enter a number greater than zero or, if possible, change the data type of the column to Number.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00506: Database columns cannot be moved between queries.**

**Cause:** An attempt was made to move a column into another group belonging to another query and the column is a database column. A database column must be selected by the query that owns its group.

**Action:** Select the column, if possible, in the query that owns the group to which it should be moved.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00507: The file name is invalid.**

**Cause:** In a file selection dialog box, the dialog box was accepted without specifying a file name.

**Action:** Enter a name and then accept or cancel the dialog box.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00508: The object name is invalid.**

**Cause:** In a database object selection dialog box, the dialog box was accepted without specifying an object name.

**Action:** Enter a name and then accept or cancel the dialog box.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00509: The number value is invalid.**

**Cause:** In a numeric field, something other than a digit or a decimal point was entered.

**Action:** Enter a number that contains only digits and, if necessary, a decimal point.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00510: The Unit of Measurement value is invalid.**

**Cause:** An invalid unit of measurement was entered in the Unit of Measurement field.

---

**Action:** Select the desired option from the list of values: 'Character', 'Inch', 'Centimeter' or 'Point'

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00511: The Panel Print Order value is invalid.**

**Cause:** The Panel Print Order entered was not one of the two valid options.

**Action:** Select the desired option from the list of values: 'Across/Down' or 'Down/Across'.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00512: The number value is invalid.**

**Cause:** The number entered was a decimal value and Oracle Reports Builder was expecting a non-decimal value.

**Action:** Enter a non-decimal value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00513: The Unit of Measurement value is invalid.**

**Cause:** The Unit of Measurement is blank and an attempt was made to move to another setting.

**Action:** Select an option for Unit of Measurement.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00514: The Page Size value is invalid.**

**Cause:** The Page Width and/or Page Height settings were left blank and they require a value.

**Action:** Enter a number for Page Width and/or Page Height.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00515: The Parameter Form Size value is invalid.**

**Cause:** The Parameter Form Width and/or Parameter Form Height settings were left blank and they require a value.

**Action:** Enter a number for Parameter Form Width and/or Parameter Form Height.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**REP-00516: The Page Size value is invalid.**

**Cause:** The value entered for Page Size was not in character units, and Page Size requires character units.

**Action:** Enter a value in characters for Page Size.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00517: The Form Size value is invalid.**

**Cause:** The value entered for Form Size was not in character units, and Form Size requires character units.

**Action:** Enter a value in characters for Form Size.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00518: The Object Access value is invalid.**

**Cause:** The Object Access setting entered was not one of the three valid choices.

**Action:** Select an option from the list of values: Database, File, or File/Database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00519: The Default Text Edit Mode value is invalid.**

**Cause:** The Default Text Edit Mode entered was not one of the two valid choices.

**Action:** Select an option from the list of values: Insert or Replace.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00520: The Group/Frame Indentation value is invalid.**

**Cause:** The value entered for Group/Frame Indentation was outside the valid range of values.

**Action:** Enter a number between 0 and 4.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00521: The name {0} is not valid.**

**Cause:** An object was given an invalid name.

**Action:** Verify the naming conventions for the object type.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**REP-00522: A default layout cannot be built because this report has no groups.**

**Cause:** Insert&gt;Report Block was selected or a region was drawn using the Report Block tool in the Paper Layout editor before creating a query. A data source is required in order to create a default layout.

**Action:** Create one or more queries, then retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00523: The Default Layout Style is invalid.**

**Cause:** The Default Layout Style entered is not one of the valid options.

**Action:** Select a layout style from the list of values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00524: The Print Direction is invalid.**

**Cause:** The Repeat value entered is not one of the valid options.

**Action:** Select a value for Repeat from the list of values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00525: The destination type is invalid.**

**Cause:** The destination type entered for the system parameter DESTYPE is not one of the valid options. Possible causes of this error include the following: Case 1: An invalid value was entered for Destination Type in the Runtime Parameter Form. Case 2: An invalid value was entered for Initial Value in the Parameter Property Inspector for DESTYPE.

**Action:** Take the following actions to correct this error: If Case 1: Enter one of the valid values, Screen, File, Printer, Mail, or Sysout. If Case 2: Select a value for Initial Value from the list of the values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00526: The initial value entered is longer than the parameter width.**

**Cause:** The value entered is too long for the parameter on the Parameter Property Inspector. The possible causes of this error include the following: Case 1: The Initial Value entered is too big, given what was specified for the parameter's Width. Case 2: The Width entered is too small to contain the values to be entered for the parameter.

**Action:** Take the following actions to correct this error: If Case 1: Reenter the Initial Value, making sure that it is not wider than what is specified in Width. If Case 2: Delete the Initial Value. Move to the Width setting for the parameter and

---

increase it such that it can contain the Initial Value specified. Reenter the Initial Value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00527: A system parameter cannot be deleted.**

**Cause:** An attempt was made to delete a system parameter from the Parameter Property Inspector. This is not allowed.

**Action:** To remove the system parameter from the Runtime Parameter Form, suppress the display of the parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00528: The data type value is invalid.**

**Cause:** The value entered in Datatype for the parameter is not a valid data type.

**Action:** Select a value for Datatype from the list of values: Character, Number, or Date.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-00529: The Type value is invalid.**

**Cause:** The value entered in Type for the boilerplate is not a valid type.

**Action:** Select a value for Type from the list of values: Box, Graphic, Line, or Text.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00530: The file is too long. It will be truncated to fit.**

**Cause:** An attempt was made to import a file into a field that has a maximum width less than the size of the file. Oracle Reports Builder only imported as much of the file as could fit in the field.

**Action:** To import the entire file, increase the size of the field.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00531: The Object Type is invalid.**

**Cause:** In the Navigate to Object dialog box, the value entered for Object Type was invalid.

**Action:** Select a value from the list of values.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**REP-00532: There is no object of that type with this name.**

**Cause:** The value entered in the Object Name field of the Navigate to Object dialog box does not correspond to an object of the specified type in the report.

**Action:** Verify the name and that the object is contained in the current report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00533: Import is allowed only to a text entry field.**

**Cause:** Import was selected from the Edit menu while in a non-text entry field (for example, a field that accepts only a number).

**Action:** Move to a text entry field to perform an import operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00534: Export is allowed only from a text entry field.**

**Cause:** Export was selected from the Edit menu while in a non-text entry field (for example, a field that accepts only a number).

**Action:** Move to a text entry field to perform an export operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00535: No object named {0} exists in the database.**

**Cause:** An attempt was made to perform an operation on a document stored in the database, but Oracle Reports Builder could not find the object.

**Action:** Verify the name and connection to the database where the document resides.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00536: An object in the database cannot be deleted without ownership.**

**Cause:** An attempt was made to delete an object without ownership privileges.

**Action:** Request that the owner delete the object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00537: An object in the database cannot be renamed without ownership.**

**Cause:** An attempt was made to rename an object without ownership privileges.

**Action:** Request that the owner rename the object.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00538: An object named {0} already exists in the database.**

**Cause:** The name entered for the object is already used for an existing object.

**Action:** Provide a different name for the object to avoid the conflict or delete the existing object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00539: The default Parameter Form cannot fit in {0} pages.**

**Cause:** The default Parameter Form is too big to fit on the number of pages allocated.

**Action:** In the report's Property Inspector, under Parameter Form Window, set the Number of Pages property to the maximum number of pages that the Parameter Form can span.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00540: The page size is too small for the default Parameter Form.**

**Cause:** The current Form Width and Form Height settings are too small for the default Parameter Form.

**Action:** Increase the size of the Parameter Form pages in the Report Property Inspector by changing Form Width and Form Height. Alternatively, select Tools>Default Parameter Form to default the Parameter Form and reduce its size by editing it in the Parameter Form editor.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00541: The source must be a report.**

**Cause:** For Reports Runtime, Converter, or Tools>File Conversion, something other than a report was specified as the source. These operations all require a report as their source.

**Action:** Specify a report as the source for the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00542: No date masks have been specified as preferences.**

**Cause:** While in the Parameter or Field Property Inspector of a parameter/field of Type Date, the List button was selected for Input Mask or Format Mask, but no masks are specified in the Date Mask list of the Preferences tab of the Tools Options dialog box.



---

**Action:** Enter a date format mask manually or go to the Preferences tab of the Tools Options dialog box and enter some date format masks in the Date Mask list.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00543: No number masks have been specified as preferences.**

**Cause:** While in the Parameter or Field Property Inspector of a parameter/field of Type Number, the List button was selected for Input Mask or Format Mask, but no masks are specified in the Number Mask list of the Preferences tab of the Tools Options dialog box.

**Action:** Enter a number format mask manually or go to the Preferences tab of the Tools Options dialog and enter some number format masks in the Number Mask list.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00544: The online help system is not available.**

**Cause:** Online help was not found. This may have happened because the help files are not installed or because of a help system error.

**Action:** Install Developer Tools during Oracle Fusion Middleware installation to install Oracle Reports Builder, which includes the Oracle Reports Online Help. Or, view the Reports Online Help on the Oracle Technology Network (OTN) at <http://www.oracle.com/technology/products/reports/index.html>.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00545: The number must be greater than 0.**

**Cause:** Zero (0) was entered for Page Width, Page Height, or Logical Page Size in the Report Property Inspector.

**Action:** Enter a number greater than zero for Page Width, Page Height, or Logical Page Size.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00546: The parameter value is invalid.**

**Cause:** In the Runtime Parameter Form, the parameter value entered was invalid.

**Action:** Retry the operation with a valid value for the parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00548: An error occurred initializing Oracle Toolkit.**

---

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00549: The DESTYPE value is invalid.**

**Cause:** An attempt was made to run a report in the background (that is, BATCH=YES), but DESTYPE specified was invalid for running in the background.

**Action:** Change the DESTYPE to File, Printer, Mail, or Sysout, or do not run the report with BATCH=YES.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00550: The parent group name is invalid.**

**Cause:** The name entered does not identify a valid parent group in the report being defined.

**Action:** Select a group from the list of values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00551: The parent group column is invalid.**

**Cause:** The name entered does not identify a valid parent column in the report being defined. The column specified does not exist in the parent group.

**Action:** Select a column from the list of values. If the required column does not appear, add it to the SELECT statement of the parent query of the group specified in Parent Group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00552: The child column name is invalid.**

**Cause:** The name entered does not identify a valid child column in the report being defined. The column specified does not exist in the query.

**Action:** Select a column from the list of values. If the required column does not appear, add it to the SELECT statement of the query.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00553: The condition is invalid.**

**Cause:** The Condition entered for the query is not one of the valid choices.

**Action:** Select a value from the list of values for Condition.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00554: The SQL clause value is invalid.**

**Cause:** The value entered in SQL Clause is not one of the valid choices.

**Action:** Select a value from the list of values for SQL Clause: WHERE, HAVING, or START WITH.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00555: START WITH is Oracle-specific SQL syntax. The report will not run against a non-Oracle database.**

**Cause:** The START WITH clause is only available with the Oracle database, but there is no connection or a non-Oracle database connection.

**Action:** Either run the report against an Oracle database or remove the START WITH clause before running it against a non-Oracle database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00556: No data links are created. No foreign key in the child query {0} refers to a primary key in the parent query {1}.**

**Cause:** An attempt was made to create a query-to-query link but no foreign key exists in the child query.

**Action:** Verify that the tables are accessible, and add the appropriate column constraints if desired.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-00558: The query {0} created the lexical parameter {1}.**

**Cause:** The specified query references one or more lexical parameters that did not exist.

**Action:** No action is needed. Oracle Reports Builder has already created the necessary lexical parameters.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00559: The query {0} has created the bind parameter {1}.**

**Cause:** The specified query references one or more bind parameters that did not exist.

**Action:** No action is needed. Oracle Reports Builder has already created the necessary bind parameters.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00560: The group name value is invalid.**

**Cause:** The group name entered in Group is not a valid group for the column. The group specified does not exist or cannot own the column.

**Action:** Create or modify the group such that it can own the column. A database column must be owned by the group associated with the query that selects it. A summary or formula column must be owned by a group that is below the groups that owns the columns being summarized in the group hierarchy (that is, the order of groups as they appear in the Data Model editor).

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00561: The type value is invalid.**

**Cause:** The value entered in Type for the column was not one of the valid choices.

**Action:** Select a value from the list of values for the column's Type: Formula, Summary, or Placeholder.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00562: The column data type value is invalid.**

**Cause:** The value entered in Datatype was not one of the valid choices.

**Action:** Select a value from the list of values for Datatype.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-00563: The data type value is invalid.**

**Cause:** The value entered in Datatype was not one of the valid choices.

**Action:** Select a value from the list of values for Datatype: Ascending, Descending, or blank.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-00564: The file type value is invalid.**

**Cause:** The file type value entered in Read From File was not one of the valid types.

**Action:** Select a file type from the list of values for Read from File.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**REP-00565: The function value is invalid.**

**Cause:** The function entered for Function was not one of the valid choices.

**Action:** Select one of the functions from the list of values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00566: The database column cannot be deleted.**

**Cause:** An attempt was made to delete a column with a Type of Database.

**Action:** Remove the column from the SELECT list of the query that selects it and the column will be deleted automatically.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00567: The summary source value is invalid.**

**Cause:** The column entered in Source for the summary was not one of the valid choices. The possible causes of this error include the following: Case 1: The column does not exist. Case 2: The data type of the Source is Character or Date. Numeric functions (such as Percent, Sum, or Average) require a data type of Number.

**Action:** Take the following actions to correct this error: If Case 1: Select a column from the list of values for the function. If Case 2: Enter the name of another column in Source that is of data type Number.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00568: The Value if Null value is invalid.**

**Cause:** The value of Value if Null in the Column Property Inspector is invalid for that column. For example, if data type of the column is Number, and a character string was specified in Value if Null.

**Action:** Specify a valid value for Value if Null.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00580: The filter type value is invalid.**

**Cause:** The value entered for Type under Filter was not one of the valid choices.

**Action:** Select one of the filter types from the list of values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00581: This is the only group of query {0}, and may not be deleted.**

---

**Cause:** An attempt was made to delete a group that is the only one of the query. Each query must have at least one group.

**Action:** To delete the group, delete the group's query.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00582: A group cannot be moved out of its query.**

**Cause:** An attempt was made to move a group between queries. Groups can only be moved within the set of groups belonging to the same query.

**Action:** Create a group similar to the one that was attempt to be moved under the other query, if possible.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00583: The SQL SELECT Statement is invalid.**

**Cause:** The SQL SELECT statement entered was not valid.

**Action:** Check the SELECT statement for errors and correct them. For more information, see the SQL Language Reference Manual.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00584: Lexical parameters are not permitted in external queries.**

**Cause:** A lexical reference was made in an external query. This is not allowed.

**Action:** Delete the reference altogether or, if possible, change it to a bind reference.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00585: The arent group {0} for child query {1} does not exist.**

**Cause:** A query was deleted without deleting references to its groups in data links. This usually happens when a query is deleted without cascading the deletion to its associated objects.

**Action:** Update the data link in the child query.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00586: Adding this data link will create a cycle.**

**Cause:** The group specified as the parent group for the data link is not eligible to be a parent because it is, directly or indirectly, a child of the query to which it is linked.

**Action:** If possible, move the group such that it is not a child of the query and therefore eligible to be its parent group.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-00587: The PL/SQL group filter condition value is invalid.**

**Cause:** Condition was selected for Filter Type, but no PL/SQL condition was entered.

**Action:** Enter the PL/SQL or change the Filter Type.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00588: The PL/SQL column formula value is invalid.**

**Cause:** Formula was selected as the column's Type, but no PL/SQL for the formula was entered.

**Action:** Create a formula or change the column's Type.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00590: Only {0} pages were formatted. The last page is shown.**

**Cause:** In the Previewer, an attempt was made to go to a page number that is larger than the total number of pages formatted.

**Action:** No action is needed. Do not attempt scroll down from the last page of the report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00591: The first page is already shown.**

**Cause:** In the Previewer, First was selected on the first page of the report.

**Action:** No action is needed. Do not attempt to scroll up from the first page of the report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00592: The last page is already show.**

**Cause:** In the Previewer, Last was selected on the last page of the report.

**Action:** No action is needed. Do not attempt to scroll down from the last page of the report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00593: Page {0} is the current page.**

---

**Cause:** In the Previewer, the page number of the current page was entered.

**Action:** Enter a different page number and select Go To.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00594: No report output is generated.**

**Cause:** The report generated no output.

**Action:** Check the accompanying messages for errors in the data model and layout. If the problem persists, contact Oracle Support Services for assistance.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00595: The report definition was modified. Rerunning report.**

**Cause:** A report was run and while its output was still in the Previewer, the report definition was modified. The report is rerun to reflect the most recent changes

**Action:** Save the changes, close the Previewer, and run the report again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00596: A page number cannot be greater than {0} or less than 1.**

**Cause:** An invalid value was entered for the Page Number setting on the Field Property Inspector for a Parameter Form field. The most likely cause is that values entered were zero, a negative number, or a number that is larger than the largest allowable value.

**Action:** Enter a number within the range shown in the message.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00597: This operation is invalid, since it moves objects out of bounds.**

**Cause:** An attempt was made to move editor objects in such a way that they would be off the screen.

**Action:** Retry the operation so that it will not move objects off the screen.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00598: The anchor end point is out of the boundary of the object.**

**Cause:** In moving an anchor, the end point was moved off of the boundary of the object it anchors.

**Action:** Move the anchor such that its endpoint is still on the boundary of the object.



---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00599: This text boilerplate is not editable.**

**Cause:** An attempt was made to edit the text of a file link text boilerplate object while it was displayed in the Paper Layout view.

**Action:** To edit the text of a file link text boilerplate object, exit the report and edit the file containing the boilerplate text using a text editor.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00600: No list of values is available for this field.**

**Cause:** An attempt was made to access a list of values for the current field when none is available.

**Action:** No action necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00601: The list of values for this field is empty.**

**Cause:** An attempt was made to select from a list of values and the list of values has no values. In order for some lists of values to contain values, another part of the report must be built first. For example, if a list of values is made up solely of column names and the data model is not complete, this error may display.

**Action:** Build the report fully. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00602: The accessible tables cannot be queried.**

**Cause:** The dictionary view of accessible tables is not present or not available.

**Action:** See the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00603: Table {0} cannot be described.**

**Cause:** The dictionary view of accessible tables is not present or not available.

**Action:** See the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-00604: The SELECT statement cannot be built.**

**Cause:** The Table and Columns Names dialog box was accepted without anything selected with which to build the SELECT statement.

**Action:** Select a table and, if desired, columns or the SELECT columns FROM table option, and then accept the dialog box. To exit the dialog box without building a SELECT statement, click Close.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00606: Link file {0} cannot be read.**

**Cause:** Case 1: The file specified in the Source Filename property for the file link boilerplate object cannot be found or its format does not match that specified in the File Format property. Case 2: The REPORTS\_DEFAULT\_DISPLAY environment variable is set to YES and the image format used is not supported.

**Action:** Take the following actions to correct this error: If Case 1: Verify that the file is stored in the specified directory under the specified name, and that it is saved in the specified format. If it is not, change the directory, file name, or format as appropriate. If Case 2: Verify that the image format is one of the supported formats: GIF, JPEG, JPG, PNG, BMP.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00607: Run-only file {0} may not be opened.**

**Cause:** An attempt was made to open a runfile (extension .rep). Runfiles cannot be opened, they can only be executed.

**Action:** Open the report definition that is associated with the .rep file. It should have an extension of .rdf.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00608: The Source Type is invalid.**

**Cause:** Convert was selected from the File menu and the Source Type specified is not valid.

**Action:** Select a valid Source Type from the list of values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00609: The Destination Type is invalid.**

**Cause:** Convert was selected from the File menu and the Destination Type specified is not valid.

**Action:** Select the Destination Type from the list of values.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-00610: An error occurred while attempting to print the screen. Verify that log file {0} is accessible.**

**Cause:** Oracle Reports Builder attempted to write the contents of the screen to the file printdef.dat but could not locate the file.

**Action:** To determine the proper location for printdef.dat, see the installation instructions.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00611: The Destination Type value is not valid.**

**Cause:** In the Runtime Parameter Form, the value provided for Destination Type that was not valid.

**Action:** Specify a value of Screen, File, Printer, or Mail for Destination Type.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00612: The date mask value is invalid.**

**Cause:** The date mask entered does not correspond to any of the valid date masks.

**Action:** Verify the date mask format. For more information, see the date and time format mask information in the Building Reports manual.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00613: The Format Mask value does not match mask {0}.**

**Cause:** The mask entered in Format Mask is not a valid mask. The possible causes of this error include the following: Case 1: The string entered as a mask contained invalid characters. Case 2: A number format mask was entered for a field with data type of Character.

**Action:** Take the following actions to correct this error: If Case 1: Select a value from the list of values. For more information, see the date and time format mask information in the Building Reports manual. If Case 2: Change the data type of the field to be Number, if possible. If the field is supposed to be Character data type and cannot be changed, a format mask cannot be specified for it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00614: There is no window active for the Find and Replace action.**

**Cause:** A Find and Replace operation was attempted using the Find And Replace dialog box, but the cursor was not positioned in an active Oracle Reports Builder window.

---

**Action:** Position the cursor in a text entry field before performing a Find and Replace operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00615: Find and Replace is valid only for a text entry field.**

**Cause:** A Find and Replace operation was attempted using the Find And Replace dialog box, but the cursor was not positioned in a text entry field. Find and Replace operations are valid only in text entry fields.

**Action:** Position the cursor in a entry field before performing a Find and Replace operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00616: Text cannot be replaced in an uneditable region.**

**Cause:** Using the Find And Replace dialog box, text replacement was attempted in an inaccessible field.

**Action:** Replace text only in editable regions.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00617: The Runtime Parameter Form is already open. To run a new one, close the old one and run again.**

**Cause:** An attempt was made to run a report with the Runtime Parameter Form already open.

**Action:** Close the currently open Runtime Parameter Form and try running again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00619: A report cannot be run without a layout.**

**Cause:** An attempt was made to run the report with no layout.

**Action:** Create a layout, then run the report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00621: The Vertical Elasticity value is invalid.**

**Cause:** The value entered for the object's Vertical Elasticity was not one of the valid values.

**Action:** Select a value from the list of values.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-00622: The Horizontal Elasticity value is invalid.**

**Cause:** The value entered for the object's Horizontal Elasticity was not one of the valid values.

**Action:** Select a value from the list of values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00623: The Print Condition Type value is invalid.**

**Cause:** The value entered for the Type of the Print Condition was not one of the valid values.

**Action:** Select a value from the list of values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00624: The Print Condition Object value is invalid.**

**Cause:** The value entered for the Object of the Print Condition was not one of the valid values.

**Action:** Select a value from the list of values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00625: The Text Alignment value is invalid.**

**Cause:** The value entered for Alignment was not one of the valid values. The value is not valid given the data type of the object. Flush/Left, Flush/Center, and Flush/Right are only valid for fields with data type of Character.

**Action:** Select a value from the list of values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00626: The coordinate position value is invalid.**

**Cause:** The x or y coordinate entered was not in the valid range for coordinates. Coordinates cannot be negative numbers.

**Action:** Enter a coordinate that is in the valid range.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00627: The object height or width must be a positive integer.**

**Cause:** The Width or Height value entered was not a positive, whole number.

---

**Action:** Enter a positive, whole number.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00630: The value must be between {0} and {1}.**

**Cause:** The number entered was too large or too small.

**Action:** Specify a number that is within the range shown in the message.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00631: The string must be no longer than {0} characters.**

**Cause:** The string entered was too large.

**Action:** Enter a string that is smaller than the number of characters shown in the message.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00632: The value already exists in the list.**

**Cause:** An attempt was made to add an item to a list, but the item was previously added to the list. For example, if an attempt was made to add lib1 to the report's Attached PL/SQL Library list, when lib1 was already found in the Attached PL/SQL Library list, this error displays.

**Action:** Once an item has been added to a list, do not attempt to add it again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00633: No value is specified.**

**Cause:** An attempt was made to perform a list operation on an item, but no item was specified. For example, if an attempt was made to add a PL/SQL library to the report's Attached PL/SQL Library list, but the PL/SQL Library field in the Attached PL/SQL Libraries dialog box was left blank and the Add button selected, this error displays.

**Action:** Specify the item to add in the appropriate field before choosing a button.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00634: The destination name must be shorter than {0} characters.**

**Cause:** The destination specified (probably a file name) was too long.

**Action:** Specify a destination that it is of valid length.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-00635: The value does not exist in the list.**

**Cause:** The value specified was not in the list of valid choices.

**Action:** Specify one of the valid choices in the list. If possible, use the list of values to ensure that it is a valid choice.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00636: Property name {0} must be no longer than {1} characters. It will be truncated.**

**Cause:** The string specified was longer than is allowable. It will be truncated.

**Action:** Specify a shorter string.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00637: Property name {0} must be no longer than {1} characters.**

**Cause:** The file name specified was longer than is allowable.

**Action:** Specify a shorter file name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00639: Set a valid DISPLAY value when REPORTS\_DEFAULT\_DISPLAY is set to NO.**

**Cause:** REPORTS\_DEFAULT\_DISPLAY was set to NO and DISPLAY variable was not set.

**Action:** Specify a valid value for DISPLAY when REPORTS\_DEFAULT\_DISPLAY is set to NO.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00640: The field source value is invalid.**

**Cause:** The Source value specified was invalid.

**Action:** Select a value from the list of values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00650: The source group value is invalid.**

**Cause:** The group name specified in Source for the repeating frame was invalid.

**Action:** Select a value from the list of values.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00651: The Print Direction value is invalid.**

**Cause:** The Print Direction specified was not one of the valid values (Across, Across/Down, Down, Down/ Across, and Matrix Cell).

**Action:** Select a value from the list of values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00652: The Vertical Spacing value is invalid.**

**Cause:** The Vertical Spacing specified was not a valid value.

**Action:** Enter zero or a positive integer for Vertical Spacing.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00653: The Horizontal Spacing value is invalid.**

**Cause:** The Horizontal Spacing specified was not a valid value.

**Action:** Enter zero or a positive integer for Horizontal Spacing.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00654: The Maximum Records per Page value is invalid.**

**Cause:** The Maximum Records per Page specified was not a valid value.

**Action:** Enter blank or a positive integer for Maximum Records per Page.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00655: The Minimum Widow Records value is invalid.**

**Cause:** The Minimum Widow Records specified was not a valid value.

**Action:** Enter blank or a positive integer for Minimum Widow Records.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00660: The button source value is invalid.**

**Cause:** Multimedia Column was selected as the source for the button action, but the source column was either not specified or invalid.

**Action:** Specify a valid source column for the button action, containing sounds, video, or images.



---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00661: The button source value is invalid.**

**Cause:** Multimedia File was selected as the source for the button action, but the source file was either not specified or invalid.

**Action:** Specify a valid source file for the button action, containing sounds, video, or images.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00662: The button icon value is invalid.**

**Cause:** Icon was selected as the button face, but the icon name was invalid.

**Action:** Enter the name of a valid icon file in the text field provided. Include all necessary path information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00670: The boilerplate type value is invalid.**

**Cause:** The Type specified for the boilerplate was not one of the valid values.

**Action:** Select a Type from the list of values: Box, Line, Graphic, and Text.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00671: The link file name value is invalid.**

**Cause:** The file to which the file link boilerplate object was linked is not a valid file.

**Action:** In the Property Inspector for the File Link boilerplate object, check that the Source Filename property is set to an existing file in the current directory.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00672: The Minimum Widow Lines value is invalid.**

**Cause:** The Minimum Widow Lines specified was not a valid value.

**Action:** Enter blank or a positive integer for Minimum Widow Lines.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00680: The anchoring object name value is invalid.**

---

**Cause:** The object name entered in the Anchored To field of the Anchor Position dialog box was not the name of an object to which this object can be anchored.

**Action:** Select an object name for Anchored To from the list of values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00681: The Edge value is invalid.**

**Cause:** The Edge specified was not one of the valid values (Top, Left, Right, and Bottom).

**Action:** Select a value for Parent Edge or Object Edge from the list of values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00682: The anchor point must be a percentage between 0 and 100.**

**Cause:** The % specified was not in the valid range (0 to 100).

**Action:** Enter a value in the valid range for %.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00690: The starting page number value is invalid.**

**Cause:** Start At was left blank.

**Action:** Enter zero or a positive integer for Start At.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00691: The page increment value is invalid.**

**Cause:** Increment By was blank.

**Action:** Enter zero or a positive whole number for Increment By.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00692: The page number reset value is invalid.**

**Cause:** Reset At was left blank.

**Action:** Select a repeating frame name or &Report from the list of values to indicate where to reset the page number to its Start At value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-00700: The color value is invalid.**

**Cause:** The color specified was not one of the valid choices.

**Action:** Select a color for the field from the list of values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00701: The pattern value is invalid.**

**Cause:** The pattern specified was not one of the valid choices.

**Action:** Select a pattern for the field from the list of values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00702: The pen width value is invalid.**

**Cause:** The pen width specified was not one of the valid choices.

**Action:** Select a pen width from the list of values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00703: The font value is invalid.**

**Cause:** The font specified was not one of the valid choices.

**Action:** Select a font from the list of values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00704: The text style value is invalid.**

**Cause:** The text style specified was not one of the valid styles.

**Action:** Select one of the styles from the list of values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00705: The text weight value is invalid.**

**Cause:** The text weight specified was not one of the valid weights.

**Action:** Select one of the weights from the list of values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00706: The text size value is invalid.**

**Cause:** The point size specified was not one of the valid choices.

---

**Action:** Select a valid point size from the list of values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00707: The text spacing value is invalid.**

**Cause:** The spacing value specified was not in the valid range.

**Action:** Enter a number in the valid range.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00708: The character mode attribute value is invalid.**

**Cause:** The character mode attribute specified was not valid. The values specified in Character Mode Attribute must be defined in the printer definition. To have these attributes appear in the list of values, they must also be listed in VISUAL\_PREFS in the preferences file.

**Action:** Select the desired values from the list of values. If the desired value is not in the list of values, check the printer definition to verify if the value is a valid one.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00709: Sysout is only valid in batch mode.**

**Cause:** Sysout was specified as the destination type when not running the report in batch mode. The possible causes of this error include the following: Case 1: Sysout was specified for DESTYPE in the Runtime Parameter Form. Case 2: Sysout was specified as the Initial Value for DESTYPE and was accepted when not running in batch mode. This may occur inadvertently when the Hide Parameter Form preference is checked.

**Action:** Take the following actions to correct this error: If Case 1: Run the report again, but enter a DESTYPE of something other than Sysout unless running in batch mode. If Case 2: Change the Initial Value for DESTYPE to something else or change the DESTYPE to something other than Sysout in the Runtime Parameter Form. If the Initial Value is left as Sysout, do not run in non-batch mode with Hide Parameter Form checked.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00710: The printer description file cannot be found.**

**Cause:** Oracle Reports Builder could not find the printer description file specified for DESFORMAT.

**Action:** Specify a valid printer description file for DESFORMAT (for example, dflt).

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**REP-00711: The destination type must be File, Printer, or Mail when printing from the Previewer.**

**Cause:** The Print button was selected in the Previewer, but DESTYPE was restricted to a value other than File, Printer, or Mail.

**Action:** Ensure that DESTYPE can be set to one of the valid values before attempting to print from the Previewer.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00712: No printer is specified.**

**Cause:** An attempt was made to print a report, without a printer name specified in either DESNAME or in the Printer Chooser dialog box.

**Action:** Specify a valid printer name using DESNAME. If the same printer is often used, enter the printer name in the Printer Chooser dialog box. Remember that entering a printer name using DESFORMAT will override the printer name set in the Printer Chooser dialog box.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00713: The printer name {0} specified by parameter {1} is invalid.**

**Cause:** An attempt was made to generate a report, without a valid printer name specified in DESFORMAT (if DESTYPE was File or Mail) or DESNAME (if DESTYPE was Printer).

**Action:** Specify a valid printer name for DESFORMAT if DESTYPE was File or Mail, or a valid printer name for DESNAME if DESTYPE was Printer.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00714: The mail destination value is invalid.**

**Cause:** An attempt was made to mail report output to another user, but did not specify a valid username for DESNAME.

**Action:** Specify a valid username for DESNAME.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00715: A trace file must be specified when tracing.**

**Cause:** Trace mode or trace options were specified without specifying a trace file.

**Action:** Specify a trace file.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**REP-00716: The option specified for tracing is invalid.**

**Cause:** Invalid trace options were specified.

**Action:** Respecify trace options. For more information about trace options, see the Publishing Reports to the Web manual.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00717: Options cannot be set or unset if not tracing.**

**Cause:** An attempt was made to set or unset trace options while not tracing.

**Action:** Begin tracing before attempting to set or unset options.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00718: Trace break information cannot be traced with Reports Runtime.**

**Cause:** An attempt was made to trace breaks while running the report using Reports Runtime.

**Action:** Do not specify the Break option when using Reports Runtime.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00719: Trace file {0} can be written to.**

**Cause:** A trace file was specified that does not have write permission.

**Action:** Verify the trace file name is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00720: The repeating frame value is invalid.**

**Cause:** The repeating frame specified as the Vertical or Horizontal Frame in the Matrix Property Inspector is not valid.

**Action:** Select a repeating frame name from the list of values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00721: The cross product group value is invalid.**

**Cause:** The group entered for Cross Product Group in the Matrix Property Inspector is not valid.

**Action:** Select a group name from the list of values.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-00723: Uncompiled program units exist, possibly due to no connection to the database.**

**Cause:** An attempt was made to convert a report or load an old report, containing PL/SQL which needed to be recompiled.

**Action:** Load the report using Oracle Reports Builder, connect to database, and recompile the DE program units.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00724: The value of column {0} cannot be retrieved.**

**Cause:** An attempt was made to get the value of the specified column by either issuing a command from the command line of the PL/SQL Interpreter or by executing a stand-alone PL/SQL program unit. A column value can only be retrieved during report execution.

**Action:** Do not attempt to use the PL/SQL Interpreter or a PL/SQL program unit to get the value of a column when the report has suspended execution (for example, at a breakpoint). Use an alternate method, such as one of the report-level triggers, to obtain the column value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00725: The value of column {0} cannot be set.**

**Cause:** An attempt was made to set the value of the specified column by either issuing a command from the command line of the PL/SQL Interpreter or by executing a stand-alone PL/SQL program unit. A column value can only be set during report execution.

**Action:** Do not attempt to use the PL/SQL Interpreter or a PL/SQL program unit to set the value of a column when the report has suspended execution (for example, at a breakpoint). Use an alternate method, such as one of the report-level triggers, to set the column value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00726: The value of parameter {0} cannot be retrieved.**

**Cause:** An attempt was made to get the value of the specified parameter by either issuing a command from the command line of the PL/SQL Interpreter or by executing a stand-alone PL/SQL program unit. A parameter value can only be retrieved during Parameter Form execution.

**Action:** Do not attempt to use the PL/SQL Interpreter or a PL/SQL program unit to get the value of a parameter when the report has suspended execution (for example, at a breakpoint). Use an alternate method, such as one of the report-level triggers, to obtain the parameter value.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00727: The value of parameter {0} cannot be set.**

**Cause:** An attempt was made to set the value of the specified parameter by either issuing a command from the command line of the PL/SQL Interpreter or by executing a stand-alone PL/SQL program unit. A parameter value can only be set during Parameter Form execution.

**Action:** Do not attempt to use the PL/SQL Interpreter or a PL/SQL program unit to set the value of a parameter when the report has suspended execution (for example, at a breakpoint). Use an alternate method, such as one of the report-level triggers, to set the parameter value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00728: Column {0} may not be referenced by parameter triggers.**

**Cause:** An attempt was made to reference a column in a parameter-related trigger (Before Form, After Form, Validation), which is not allowed.

**Action:** Remove the references from the parameter-related triggers and add them to the Before Report trigger.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00729: The program unit {0} of size {1} bytes is too big to be loaded for the current platform at the limit of {2}.**

**Cause:** The program unit was created on another operating platform and it too large to be loaded into the current operating platform.

**Action:** Reduce the size of the PL/SQL program unit.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00730: The bind variable is not defined.**

**Cause:** A bind reference was made to a parameter or column that has not been defined yet.

**Action:** Create the parameter definition or column before making a bind reference to it. Or, attempt to use a lexical reference rather than a bind reference.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00732: An error occurred destroying the program unit.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.



---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00733: The specified name already exists.**

**Cause:** An attempt was made to create a PL/SQL subprogram whose name is identical to an existing subprogram stored in the report.

**Action:** Rename the new subprogram so that it does not conflict with any existing subprograms.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00734: No argument is allowed.**

**Cause:** The PL/SQL function or procedure entered requires arguments in a PL/SQL field that does not allow PL/SQL with arguments—for example, in a Format Trigger field, a Formula field, or as a group filter.

**Action:** Remove the arguments from the PL/SQL source.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00735: Program unit cannot be loaded.**

**Cause:** Oracle Reports Builder could not load the entire program unit. It could be that the program unit references one or more objects stored in the database, but these objects were not found.

**Action:** Verify the connection to the correct database, and ensure that the program unit is making the correct references.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00736: Uncompiled program units exist.**

**Cause:** An attempt was made to convert a report, or load an old report, containing PL/SQL that needed to be recompiled.

**Action:** Load the report using Oracle Reports Builder and modify the program units.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00737: The return type {0} is invalid.**

**Cause:** The PL/SQL entered does not have the appropriate return type.

**Action:** Change the return type of the function to the one specified in the message.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-00738: A function is required.**

**Cause:** Something other than a function was entered where a function is required.

**Action:** Enter a function.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00739: Compiled PL/SQL from other platform cannot be executed.**

**Cause:** An attempt was made to run a report on a platform that is not the same as the platform on which the PL/SQL in the report was compiled. The report does not contain the PL/SQL source and, as a result, Oracle Reports Builder could not recompile the PL/SQL on the current platform.

**Action:** Run the report on the original platform where the PL/SQL was compiled. Alternatively, obtain a copy of the source report with the source PL/SQL and recompile it from the current platform.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00740: An anchor cannot be anchored with another object.**

**Cause:** An attempt was made to anchor an anchor to another layout object, or anchor a layout object to an anchor.

**Action:** Remove any anchors of anchors with other layout objects.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00741: A matrix cannot be anchored with another object.**

**Cause:** An attempt was made to anchor a matrix object to another layout object, or anchor a layout object to a matrix object.

**Action:** Remove any anchors of matrix objects with other layout objects.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00742: A margin cannot be anchored with another object.**

**Cause:** An attempt was made to anchor the margin to a layout object, or anchor a layout object to the margin.

**Action:** Remove any anchors of the margin to layout objects.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-00743: A matrix repeating frame cannot be anchored with another object.**

**Cause:** An attempt was made to anchor a matrix repeating frame with a Print Direction of Down or Across to another layout object.

**Action:** Remove any anchors of matrix repeating frames with Print Directions of Down or Across to other layout objects.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00744: An anchor must have different parent and child objects.**

**Cause:** An attempt was made to create an anchor whose parent and child objects are the same; that is, anchor an object to itself.

**Action:** Ensure that all anchors have different parent and child objects.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00745: An object cannot be anchored more than once.**

**Cause:** An attempt was made to create two anchors between the same two layout objects.

**Action:** Ensure that only one anchor exists between the same two layout objects.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00746: The PL/SQL references an object that does not exist.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00747: A Before Form trigger cannot reference a report column.**

**Cause:** The Before Form trigger for the report references a column in the report, which is not allowed.

**Action:** Remove any column references from the Before Form trigger. To set the value of a column, do it from the Before Report trigger.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00748: A parameter trigger cannot reference a report column.**

**Cause:** A Validation trigger for a parameter references one or more columns in the report, which is not allowed.

**Action:** Remove any column references in the Validation trigger of the Parameter Property Inspector.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00749: An After Form trigger cannot reference a report column.**

**Cause:** The After Form trigger for the report references a column in the report, which is not allowed.

**Action:** Remove any column references in the After Form trigger. To set the value of a column, do it from the Before Report trigger.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00750: An error occurred closing the PL/SQL library.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00751: An error occurred accessing program units from PL/SQL library.**

**Cause:** An abnormal condition was encountered. To save changes made to the PL/SQL library, consider saving it under a different name.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00752: The PL/SQL library cannot be saved.**

**Cause:** An abnormal condition was encountered. To save changes made to the PL/SQL library, consider saving it under a different name.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00753: An error occurred attaching PL/SQL library {0}.**

**Cause:** An attempt was made to attach an invalid PL/SQL library. This could happen because the PL/SQL library is corrupted, or because the file or object specified does not contain a PL/SQL library.

**Action:** Verify that the file or object specified contains a valid PL/SQL library.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00754: An error occurred inserting program units into a PL/SQL library.**

---

**Cause:** An attempt was made to save a program unit into a corrupted PL/SQL library, or a file or object that is not a PL/SQL library.

**Action:** Verify the file or object specified contains a valid PL/SQL library and consider saving the current program unit.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00755: An error occurred opening PL/SQL library {0}.**

**Cause:** An attempt was made to open a corrupted PL/SQL library, or a file or object that is not a PL/SQL library.

**Action:** Verify that the file or object contains a valid PL/SQL library.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00756: PL/SQL library {0} cannot be found.**

**Cause:** An attempt was made to attach a PL/SQL library that does not exist, or to open a report with one or more attached PL/SQL libraries that were not found.

**Action:** Verify that the file or object exists. If the object is a report, reattach the PL/SQL library.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00757: The external location spec cannot be created.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00758: PL/SQL library {0} is already in use.**

**Cause:** An attempt was made to attach a PL/SQL library that has the same name as another PL/SQL library that is already attached. This could happen if a file was renamed that contains a PL/SQL library, but the internal name recognized by Oracle Reports Builder was not changed.

**Action:** Save the PL/SQL library under a different name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00759: One or more PL/SQL libraries have been modified since the report was saved; the PL/SQL will be recompiled.**

---

**Cause:** An attempt was made to open or run a report that references one or more PL/SQL libraries, and part or all of the PL/SQL has been modified but not compiled since the report was last saved.

**Action:** No action is necessary; Oracle Reports Builder will recompile the PL/SQL.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00760: A print document session is currently in process.**

**Cause:** From the File menu, Administration Report was already selected to produce a report on one or more reports.

**Action:** Finish producing the current report on reports, then try again to run another report on reports.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00761: The resource for printing the report cannot be opened.**

**Cause:** Oracle Reports Builder cannot open the reports that document other reports for printing.

**Action:** Verify that the reports that document other reports (shipped with Oracle Reports Builder) are located in the proper directory. For details on the exact location of these reports, see the installation instructions.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00762: The user ID for the interoffice login is invalid.**

**Cause:** An attempt was made to save report output to the interoffice repository, but a valid connect string was not specified for the interoffice document server.

**Action:** Specify a valid connect string for the interoffice document server.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00763: The interoffice client {0} cannot be launched.**

**Cause:** An attempt was made to launch the interoffice client, but it failed to run.

**Action:** Verify that the interoffice client is properly installed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00764: Error {0} occurred running the interoffice client.**

**Cause:** The interoffice client was running to check in the documents into repository, but it failed on the indicated error code.

---

**Action:** Check the interoffice error code/message for the reason of failure.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00769: Sending to mail from the Parameter Form when the Paper Design view is open is invalid.**

**Cause:** The Paper Design is open and destype is set to mail.

**Action:** Select mail directly from the Paper Design view and not from the Parameter Form.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00770: The Before Form trigger failed.**

**Cause:** The Before Form trigger in the report returned false.

**Action:** Make the appropriate changes (either to the PL/SQL source in the Before Form trigger or to the report) to make the trigger return true.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00771: The After Form trigger failed.**

**Cause:** The After Form trigger in the report returned false.

**Action:** Make the appropriate changes (either to the PL/SQL source in the After Form trigger or to the report) to make the trigger return true.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00772: Parameter Form Fields {0} and {1} may not have the same Source.**

**Cause:** The same Source was specified for two Parameter Form fields. Fields on the Runtime Parameter Form must have unique sources.

**Action:** Change the Source of one of the fields.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00773: No Source was specified for Parameter Form Field {0}.**

**Cause:** A Source was not specified for a Parameter Form field or the source parameter was deleted from the data model. Fields on the Runtime Parameter Form must have a source.

**Action:** Specify a valid Source for the Parameter Form field.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**REP-00774: No selectable values are available for LOV parameter {0}.**

**Cause:** Either no values were specified for the LOV parameter's select list, or values were specified that cannot be selected.

**Action:** Check the SELECT statement or selectable value list of the parameter to ensure that the specified values are selectable.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00775: The data type of the first column of the SELECT statement does not match the data type of LOV parameter {0}.**

**Cause:** The data type of the first column specified in the SELECT statement does not match the data type specified for the LOV parameter.

**Action:** Check the data type of the LOV parameter, the SELECT statement, and the columns in the database tables accessed by the SELECT statement to ensure that they match.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-00776: There are columns with values in segmented memory when populating LOV parameter {0}. They will be ignored.**

**Cause:** Columns were selected with values in segmented memory for the LOV parameter's select list, which is not allowed.

**Action:** Select different columns or move the column values.

**Level:** 1

**Type:** ERROR

**Impact:** Memory

**REP-00777: There are columns whose types cannot be handled when populating LOV parameter {0}. They will be ignored.**

**Cause:** Columns were selected whose types cannot be handled (for example, binary data).

**Action:** Select different columns.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00778: Some columns cannot be formatted correctly when populating LOV parameter {0}. They will be ignored.**

**Cause:** The SELECT statement selecting values for the parameter's LOV retrieves columns whose values cannot be formatted according to their datatypes.

**Action:** Convert the values to valid ones or check the database to see if the values of the columns are valid.

**Level:** 1



---

**Type:** ERROR

**Impact:** Other

**REP-00779: Some items of LOV parameter {0} are too long. These items will be truncated.**

**Cause:** The items specified or columns selected contain some values that are too long to include in the LOV parameter's select list.

**Action:** Check the values of the items and reduce their length if necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00780: The initial value entered is invalid against the input mask {0}.**

**Cause:** The value entered in the Initial Value field violates the mask specified in the Input Mask field.

**Action:** Either enter a different value in Initial Value or change the mask in Input Mask.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00781: Bind variables are not allowed in the SELECT statement.**

**Cause:** Bbind variables were included in the SELECT statement.

**Action:** Remove the bind variables from the SELECT statement.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00782: The data type of the parameter does not match the data type of its source columns.**

**Cause:** The column selected has an invalid data type to furnish values for the LOV parameter's select list.

**Action:** Change the column's data type or specify a different column.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-00783: The possible values list has bad syntax.**

**Cause:** Incorrect syntax was specified to create the list of possible values for the LOV parameter.

**Action:** Edit the possible values list to ensure that it is a proper comma-separated list.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-00784: A possible value has invalid width.**

**Cause:** A value specified for the LOV parameter's list of possible values has an invalid width.

**Action:** Edit the possible values list so that all possible values have valid widths, or alter the width.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00785: A possible value is invalid against the input mask.**

**Cause:** A value specified for the LOV parameter's list of possible values is not formatted in accordance with the specified input mask.

**Action:** Edit the possible values list to ensure that all possible values are valid against the input mask.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00786: The initial value is not among the possible values.**

**Cause:** The initial value specified for the LOV parameter does not appear on the defined list of possible values.

**Action:** Add the initial value specified to the possible values list.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00787: The name of the first column of LOV parameter {0}'s select statement is not the same at runtime as design time.**

**Cause:** There is a discrepancy between the columns specified in the original SELECT statement and what the tables in question now contains.

**Action:** Check the database to determine if the tables in question have been updated since the parameter list was created, or reapply the LOV parameter's SELECT statement.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00788: The value of restricted LOV parameter {0} is not among the selectable values.**

**Cause:** The value specified for a LOV parameter is not on the parameter's select list.

**Action:** Select a value from the parameter's select list.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-00790: Page Width and Page Height must either both be specified or both be blank.**

**Cause:** A blank value was specified for either Page Width or Page Height in the Runtime Settings tab of the Tools Options dialog box.

**Action:** Specify a valid value for the blank setting, or make both settings blank.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00800: Select All is valid only in a text entry field.**

**Cause:** Select All was selected from the Edit menu with the cursor positioned on an element in the Property Inspector other than a text field.

**Action:** While in the Property Inspector, select Edit then Select All only in a text field.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00801: The layout canvas must remain large enough to fit all layout objects.**

**Cause:** The painting region of the Paper Layout editor was reduced by changing one or more settings in the Report Properties dialog box, or by resizing the margin, but the resized painting region is not large enough to fit all of the layout objects.

**Action:** Verify that all layout objects in the body, margin, header, and trailer sections of the report fit in the resized painting region.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00802: The Parameter Form canvas must remain large enough to fit all Parameter Form objects.**

**Cause:** The painting region of the Parameter Form editor was reduced by changing one or more settings in the Report Properties dialog box, but the resized painting region is not large enough to fit all of the Parameter Form objects.

**Action:** Verify that all Parameter Form objects fit in the resized painting region.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00803: The canvas size specified is too large.**

**Cause:** The report contains combined settings of page/form size and either logical page, maximum body page, maximum header page, maximum footer page, or number of Parameter Form pages that results in a value larger than that supported by Oracle Reports Builder (a dpi value greater than 2 gigabytes).

**Action:** Make the page/form size smaller, or decrease the value for logical page size, maximum body pages, maximum header pages, maximum footer pages, or number of Parameter Form pages.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-00804: The report definition was modified during the current run. Oracle Reports Builder cannot continue running the Parameter Form or report.**

**Cause:** While in the Runtime Parameter Form, the report was modified through an editor or Property Inspector.

**Action:** Cancel the Runtime Parameter Form and rerun the report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00805: Menus cannot be initialized.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00806: An error occurred reading window resources.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00807: The array size is missing.**

**Cause:** In the Runtime Settings dialog box, the Array Size field was left blank.

**Action:** Enter an Array Size value between 1 and 9999.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00808: The buffer size is missing.**

**Cause:** In the Runtime Settings tab of the Tools Options dialog box, the Buffer Size field was left blank.

**Action:** Enter a Buffer Size value between 1 and 9999.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00809: The long chunk size is missing.**

**Cause:** In the Runtime Settings tab of the Tools Options dialog box, the Long Chunk Size field was left blank.

**Action:** Enter a Long Chunk Size value between 1 and 9999.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00810: The Success/On Failure value is invalid.**

**Cause:** In the character-mode Runtime Settings dialog box, On Success/On Failure specified an invalid value.

**Action:** Select a valid value for On Success/On Failure: Noaction, Rollback, or Commit.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00811: The Destination Type value is invalid.**

**Cause:** In the character-mode Runtime Settings dialog, Destination Type specified an invalid value.

**Action:** Select a valid value for Destination Type: &lt;In Report Definition&gt;, Screen, File, Printer, or Mail.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00812: The Orientation value is invalid.**

**Cause:** In the character-mode Runtime Settings dialog, Orientation specified an invalid value.

**Action:** Select a valid value for Orientation: &lt;In Report Definition&gt;, Landscape, or Portrait.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00813: The Mode value is invalid.**

**Cause:** In the character-mode Runtime Settings dialog, Mode specified an invalid value.

**Action:** Select a valid value for Mode: &lt;In Report Definition&gt;, Default, Bitmap, or Character.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00814: The Background value is invalid.**

**Cause:** In the character-mode Runtime Settings dialog box, Background specified an invalid value.

**Action:** Select a valid value for Background: &lt;In Report Definition&gt;, Yes, or No.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-00815: The Orientation value is invalid.**

**Cause:** In the character-mode Runtime Parameter Form, Orientation specified an invalid value.

**Action:** Select a valid value for Orientation: Landscape or Portrait.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00816: The Mode value is invalid.**

**Cause:** In the character-mode Runtime Parameter Form, Mode specified an invalid value.

**Action:** Select a valid value for Mode: Bitmap or Character.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00817: The Background value is invalid.**

**Cause:** In the character-mode Runtime Parameter Form, Background specified an invalid value.

**Action:** Select a valid value for Background: Yes or No.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00818: The page height has changed for the Parameter Form. Parameters might be crossed by page boundaries.**

**Cause:** The height of the Runtime Parameter Form was changed in the Report Property Inspector. This might cause the page boundary to move such that it appears in the middle of an object in the Parameter Form.

**Action:** Examine the layout of the Parameter Form in the Parameter Form editor and ensure that none of the objects are directly on the page boundary (the darkened line in the editor). Alternatively, default (or redefault) the Parameter Form.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00819: AUTOCOMMIT ON for SQL Server connection cannot be set.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services. Another option is to remove all instances of SRW.DO\_SQL. If this can be done while retaining all necessary functionality in the report, it will run.

**Level:** 1

---

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-00820: cannot import specified image**

**Cause:** The specified image cannot be imported.

**Action:** Check the image file to ensure it is a valid image and has not been corrupted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00821: cannot export specified image**

**Cause:** The specified object cannot be exported as an image.

**Action:** Create or select an image to export.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00822: no drawing imported**

**Cause:** The specified drawing cannot be imported.

**Action:** Check the file to ensure it is a valid drawing and has not been corrupted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00823: no drawing exported**

**Cause:** The specified object cannot be exported as a drawing.

**Action:** Create or select a drawing to export.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00824: The data dictionary is not available on the connected database.**

**Cause:** An attempt was made to access the Table and Column Names dialog box but the Data Dictionary is not available on the connected database.

**Action:** Connect to another database.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-00825: The connected database is not Oracle or DB2. It cannot be used to store report documents.**

**Cause:** An attempt was made to store a document to a database that is neither Oracle nor DB2, which is not allowed.

**Action:** Either connect to an Oracle or DB2 database or store the document as a file.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00828: Oracle Reports Builder tables are not installed in the database: cancelling report.**

**Cause:** The report cannot be run because there are no Oracle Reports Builder tables in the database.

**Action:** Inform the database administrator that the Oracle Reports Builder tables were not successfully installed in the database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00829: Oracle Reports Builder database tables are from an older version of Oracle Reports Builder ({0}): cancelling report.**

**Cause:** Oracle Reports Builder tables in the database appear to have been installed from a previous version of the product. The report cannot run against an older version of the database tables.

**Action:** Inform the database administrator that the Oracle Reports Builder tables for this version were not successfully installed in the database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00830: Oracle Reports Builder database tables appear to be corrupted or incorrectly installed: cancelling report.**

**Cause:** The report cannot be run because the Oracle Reports Builder tables are in an unstable state.

**Action:** Inform the database administrator that the Oracle Reports Builder tables are either corrupted or incorrectly installed in the database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00831: The query could not be built.**

**Cause:** Oracle Reports Builder attempted to build a query at startup but it failed. One cause is that the database account against which the query was being built was not correct. Otherwise it is an abnormal condition.

**Action:** If Oracle Reports Builder was launched from another product, check that the database connection string in the other product is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00900: The report cannot close while PL/SQL is still executing.**



---

**Cause:** An attempt was made to close a report while associated PL/SQL was still executing.

**Action:** Finish executing the PL/SQL or abort it, then close the report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00901: Tables and Columns function is not supported for this database server.**

**Cause:** The connected database server does not have an accessible Data Dictionary to list tables and columns.

**Action:** No action is needed. Tables and Columns functionality is not available for these databases.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00910: The Cue Cards cannot be found. Reinstall the Cue Cards and try again.**

**Cause:** An attempt was made to run the Cue Cards, where have not been properly installed.

**Action:** Reinstall the Cue Cards.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-00911: The Oracle Reports page on OTN cannot be displayed. Reset the browser settings correctly.**

**Cause:** In the Welcome to Oracle Reports Builder dialog box, Getting Started was selected, which displays the Oracle Reports page on the Oracle Technology Network (OTN), but the browser settings are not set correctly.

**Action:** 1. Edit the Windows registry using a registry editor (for example, open a command prompt window and type regedit.exe). 2. Select File, then Export to back up the current registry settings. 3. Navigate to the following key: HKEY\_CURRENT\_USER\Software\Oracle\Toolkit\Tkbrowser. 4. Set the BrowserName and the BrowserPath values to the browser name and location. For example: BrowserName: Internet Explorer BrowserPath: C:\Program Files\Internet Explorer\iexplore.exe 5. Close the registry editor. 6. Shut down and restart Oracle Reports Builder. 7. In the Welcome to Oracle Reports Builder dialog box, select Getting Started and click OK. 8. In the Information Navigator Preferences dialog box that displays, specify the following values: - From the Browser list, select the desired browser (for example, Microsoft Internet Explorer). - In the Command to launch browser field, specify the correct path to the browser; click Browse to navigate to the correct path location. For example: C:\Program Files\Internet Explorer\iexplore.exe 9. Click OK to save the settings and display the Oracle Reports page on the Oracle Technology Network (OTN) using the specified browser.

**Level:** 1

**Type:** ERROR

**Impact:** Browser

---

**REP-00999: Unimplemented Error:**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01010: This name does not conform to SQL naming standards.**

**Cause:** The name entered violates one or more SQL naming conventions.

**Action:** Name the object according to the appropriate naming conventions.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01011: Object {0} must be named.**

**Cause:** The Name field was left blank for the object and a name is required.

**Action:** Name the object according to the appropriate naming conventions.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01012: There is another {0} object with this name.**

**Cause:** The name entered duplicates the name of another object of the same type.

**Action:** Change the name of at least one of the objects.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01013: This name may not be the same as a reserved word.**

**Cause:** The name entered duplicates a reserved word.

**Action:** Change the name of the parameter such that it conforms to parameter naming conventions.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01014: The name length cannot exceed 30 bytes.**

**Cause:** The name entered was greater than 30 bytes, which is the limit for SQL names.

**Action:** Reduce the size of the name to 30 bytes or less.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-01048: Owner and Access list are not overwritten.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01049: A report saved with a newer version of Oracle Reports Builder cannot be opened.**

**Cause:** An attempt was made to open a report with an older version of Oracle Reports Builder than the one with which the report was saved.

**Action:** Use the same or a more recent version of Oracle Reports Builder to open the report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01050: Document names in the database cannot be accessed.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01051: The document cannot be saved to file {0}.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01052: The document cannot be saved to the database.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01053: A new document ID cannot be obtained from the database.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

---

**REP-01054: Table {0} cannot be deleted from.**

**Cause:** An attempt was made to delete from a table and the operation failed, possibly due to lack of necessary privileges.

**Action:** Contact the system administrator to assign the necessary privileges to delete from the table.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01055: Table {0} cannot be locked.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01056: Object stored in the database cannot be renamed.**

**Cause:** An attempt was made to rename a database object and the operation failed, possibly due to lack of necessary privileges.

**Action:** Make a copy of the object, or contact the system administrator to assign the necessary privileges to change the name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01057: File {0} is not a valid Oracle Reports Builder file.**

**Cause:** An attempt was made to access a file that is not in the proper format for Oracle Reports Builder.

**Action:** Verify that the correct file is being accessed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01058: The document cannot be read from the database.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01059: unable to read document from file {0}**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

---

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01060: Oracle Reports Builder database tables have not been installed.**

**Cause:** Oracle Reports Builder failed to access the SRW2\_MODULE view in the current database.

**Action:** Verify Oracle Reports Builder was properly installed on the database. For help, contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01061: External file {0} cannot be read.**

**Cause:** Read From File was activated and a file name specified as the value of a column, but Oracle Reports Builder could not successfully open or read the specified file.

**Action:** Check the spelling of the specified file in the Column Property Inspector, and verify that the specified file exists. If the file does exist, check the permissions on the file for read access.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01062: External query {0} cannot be found.**

**Cause:** The possible causes of this error include the following: Case 1: REPORTS\_PATH is not set. Case 2: There is no database connection. Case 3: The specified external query does not exist.

**Action:** Take the following actions to correct this error: If Case 1: Set REPORTS\_PATH to a valid value. If Case 2: Connect to a database. If Case 3: Specify the correct name of the external query.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01063: The PL/SQL {0} has exceeded the platform specific size limit.**

**Cause:** The PL/SQL could not be loaded because it is too large for the operating system. It may have been created on a different platform with a higher limit.

**Action:** Reduce the size of the PL/SQL so it can be loaded on the platform.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01064: Document {0} cannot be read.**

**Cause:** An attempt was made to open a document whose definition, stored in either the database or the filesystem, has been lost or corrupted.

**Action:** This document cannot be used.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-01065: External query {0} cannot be read.**

**Cause:** An attempt was made to read an external query whose definition, stored in either the database or the filesystem, has been lost or corrupted.

**Action:** This external query cannot be used.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01066: Comment is corrupted and will be lost.**

**Cause:** A storage error caused a comment to be corrupted. It will be discarded.

**Action:** No action is necessary. If desired, re-create the comment in the designer.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01067: Some information is missing in the report.**

**Cause:** The report cannot be opened because the report definition is incomplete. It may have been corrupted.

**Action:** If the report is stored in the database, use SQL\*Plus to determine whether the Oracle Reports Builder tables have been corrupted. If the report is an .rdf file, use a file system utility to check if the file is corrupted. Take appropriate actions to recover the data.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01070: An error occurred while opening or saving a document.**

**Cause:** An error occurred while opening or saving a document.

**Action:** Verify the access privileges for the document.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01071: The end of an object or record scan was reached.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01072: The object cannot be found in the object store.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01073: The object was found in the object store when not expected.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01074: The object is too big.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01075: The object is invalid.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01076: The specified object store is invalid.**

**Cause:** An attempt was made to use an invalid file or database object.

**Action:** Verify that the object specified is a valid Oracle document, stored in a file or in the database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01077: The type specified for the object is invalid.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01078: A non-specific file error occurred.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

---

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01079: The function is unsupported.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01080: A unique key violation occurred.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01081: A page split occurred.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01082: A close error occurred.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01083: A file version error occurred.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01084: A file header is bad or missing.**

**Cause:** An operation required Oracle Reports Builder to open a file. The file either did not have a header or it did not have the expected header. The header may have been changed in an editor or the file may not be compatible with this release of Oracle Reports Builder.

**Action:** Attempt to fix the header in an editor, although it is not recommended that Oracle Reports Builder files be edited in this way. For assistance, contact Oracle Support Services.



---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01085: A file create error occurred.**

**Cause:** An operation that required Oracle Reports Builder to create a file failed, most likely due to insufficient privileges to create the file.

**Action:** Obtain the necessary privileges for the file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01086: A file open read-only error occurred.**

**Cause:** An operation that required Oracle Reports Builder to open a file failed, most likely due to insufficient privileges to open the file.

**Action:** Obtain the necessary privileges for the file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01087: A file open read-write error occurred.**

**Cause:** An operation that required Oracle Reports Builder to open a file failed, most likely due to insufficient privileges to open the file.

**Action:** Obtain the necessary privileges for the file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01088: A file write error occurred.**

**Cause:** An operation that required Oracle Reports Builder to write to a file failed, most likely due to insufficient file privileges to write to the file.

**Action:** Obtain the necessary privileges for the file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01089: A file read error occurred.**

**Cause:** An operation that required Oracle Reports Builder to read a file failed, most likely due to insufficient file privileges to read the file.

**Action:** Obtain the necessary privileges for the file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01090: A file close error occurred.**

---

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01091: The disk or file system is full.**

**Cause:** An attempt was made to save an object, but there was not enough space in which to save it.

**Action:** Either delete some unnecessary files or expand the storage space.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01092: A file unique key violation occurred.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01093: Allocate failed.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01094: Reallocate failed.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01095: Free failed.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01096: The document {0} is currently locked.**

---

**Cause:** An attempt was made to open a document that is already opened (locked) by another user.

**Action:** Wait until the other user closes the document before accessing it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01097: PRODUCT\_USER\_PROFILE or SYSTEM.PRODUCT\_PROFILE does not exist.**

**Cause:** The possible causes of this error include the following: Case 1: The table does not exist. Case 2: The necessary privileges to access the table are not granted.

**Action:** Take the following actions to correct this error: If Case 1: If the table is not already created, create it. If Case 2: Get access to the table by creating a public synonym for the table in the PRODUCT\_USER\_PROFILE table, or by making the table public via the PRODUCT\_USER\_PROFILE table.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01098: An error occurred reading PRODUCT\_USER\_PROFILE or SYSTEM.PRODUCT\_PROFILE data.**

**Cause:** The table is not created correctly.

**Action:** Ensure that the table was created with the appropriate columns. If it was not, then modify it as necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01099: Files not created with Oracle Reports Builder cannot be opened.**

**Cause:** An attempt was made to open a file that is not an Oracle Reports Builder report.

**Action:** Verify that the file is an Oracle Reports Builder report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01100: The data model is invalid for this type of report.**

**Cause:** An attempt was made to create a default layout with a layout style that does not match the data model.

**Action:** Either change the data model to match the selected layout style or select a different layout style to match the data model. For more information, see the Oracle Reports online help.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**REP-01101: Group {0} has an invalid repeat direction.**

**Cause:** An attempt was made to create a default layout, but the selected layout style requires a different repeat direction for one of the groups. Some layout styles place restrictions on the repeat directions that can be selected for groups.

**Action:** Either change the repeat direction to meet the layout style requirements or select a different layout style.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01102: The default layout cannot fit onto page of size {0}.**

**Cause:** Oracle Reports Builder tried to create the default layout selected but could not fit the entire layout on the page because the page is not wide enough.

**Action:** If possible, increase the Page Width on the Report Property Inspector or rearrange objects such that the layout will fit on the page. Otherwise, make the report multiple pages wide.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01103: No column is selected in group {0}.**

**Cause:** While trying to create a default layout, a column was not selected for a selected group. Consequently, Oracle Reports Builder cannot build a default layout because one or more of the dimensions of the layout have no value.

**Action:** In the Report Wizard, select at least one column from each selected group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01104: Page level summaries are not supported in the default layout.**

**Cause:** A default layout was generated that does not fit within the given amount of space. The possible causes of this error include the following: Case 1: The layout generated is too large given the dimensions specified in the Report Properties dialog box. Case 2: The layout is too big given the size of the marked area in the Paper Layout editor.

**Action:** Take the following actions to correct this error: If Case 1: Increase the report dimensions such that the layout can fit, or alter the layout so that it will fit within the current dimensions. If Case 2: Increase the size of the marked area.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01106: no field is generated for column {0}.**

**Cause:** When the default layout was created, a field was not generated for the column in the message. The most likely cause is that a summary was not placed in the data model correctly. For example, the source of a summary column may have been specified to be a column in a group above the summary's group, which is not allowed.

---

**Action:** Debug the data model and redefault the layout.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01107: The across or down group in cross product group {0} is missing.**

**Cause:** An attempt was made to create a default layout by selecting a Style of Matrix in the Report Wizard, but all of the dimension groups of the cross product group were assigned repeat directions of Down or Across. Each repeat direction should be assigned to the dimension groups in the cross product.

**Action:** Redisplay the Report Wizard and reassign the repeat directions of the dimension groups, making sure that each direction is assigned among the groups.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01108: The default layout cannot fit even in region extending to page boundaries.**

**Cause:** An attempt was made to create a default layout that would be too large to fit within the defined height and width of a report page.

**Action:** Go back to the Report Wizard and reduce the values of default settings (for example, shorten some field widths). Alternatively, increase the size of a report page using the Report Property Inspector. Then re-create the default layout.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01109: Multiple group selection is incompatible with single group layout style.**

**Cause:** More than one group was selected to add to the layout but the style selected only supports one group.

**Action:** Change the group selection so that only a single group is selected. Alternatively change the layout style to one that supports multiple groups.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01110: The matrix across group in cross product group {0} is missing.**

**Cause:** An attempt was made to create a default layout by selecting a Style of Matrix or Matrix with Group in the Report Wizard, but all of the dimension groups of the cross product group were assigned repeat directions of Down.

**Action:** Change the repeat direction of one of the cross product dimension groups so that there is at least one Across group and one Down group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01111: The matrix down group in cross product group {0} is missing.**

---

**Cause:** An attempt was made to create a default layout by selecting a Style of Matrix or Matrix with Group in the Report Wizard, but all of the dimension groups of the cross product group were assigned repeat directions of Across.

**Action:** Change the repeat direction of one of the cross product dimension groups so that there is at least one Down group and one Across group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01112: The matrix cross product group in the matrix report is missing.**

**Cause:** An attempt was made to create a default layout by selecting a Style of Matrix or Matrix with Group in the Report Wizard, but a cross product group was not selected to be used as the matrix group.

**Action:** Change the repeat direction of one of the cross product group to Matrix.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01113: No groups or reports level columns have been selected.**

**Cause:** While trying to create a default layout, no groups or report level columns were selected. Consequently, Oracle Reports Builder cannot build a default layout because one or more of the dimensions of the layout have no value.

**Action:** In the Report Wizard, select at least one report level column or a group to be defaulted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01114: A single group selection is incompatible with a multiple group layout style.**

**Cause:** A single group was selected to be defaulted but a defaulting style designed for a multiple groups was also selected.

**Action:** Change the group selection so that more than one group is selected. Alternatively, change the layout style to one that supports single groups.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01115: The full template layout cannot be shown because it does not fit onto the page.**

**Cause:** The template layout could not be shown properly because it is too large to fit within the defined height and width of the report page. This does not mean that the template is invalid in any way.

**Action:** To show the template layout, temporarily enlarge the width and height of the report page. To do this, select the template in the Navigator and open the Property Inspector. Increase the Width and Height properties under the Report heading. Do not forget to reset the Width and Height properties before saving the template.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01118: A cross product group in the Matrix query is missing.**

**Cause:** An attempt was made to create a query by selecting the Matrix query option in the Data Wizard, However, the cross product group does not exist in the query to be used as the matrix group.

**Action:** Restart the Data Wizard.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01200: The flow compilation failed.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01201: Query text is missing from query {0}.**

**Cause:** A query was named, but either no SELECT statement was entered for it or something that did not begin with the keyword SELECT was entered. The SQL Query Statement dialog box only accepts SQL SELECT statements.

**Action:** Enter a SQL SELECT statement that begins with the word SELECT (upper or lower case may be used).

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01202: An Oracle logon was not specified.**

**Cause:** An attempt was made to run a report without an Oracle logon specified.

**Action:** Enter a logon string in the Connect dialog box and accept the dialog box before rerunning the report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01203: Field {0} references an invalid column.**

**Cause:** The column specified as the field's Source either is invalid or does not exist.

**Action:** Select a column from the list of values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-01204: Repeating frame {0} references an invalid group.**

**Cause:** The group name specified in the Group field of the Repeating Frame Property Inspector either is invalid or does not exist.

**Action:** Select a group from the list of values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01205: There is a loop in the positional dependency tree.**

**Cause:** Explicit anchors were created such that an object is indirectly anchored to itself. For example, if object A was anchored to object B, object B to object C, and object C to object A, this error displays.

**Action:** Remove at least one of the anchors that caused the loop.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01206: An object is anchored to more than one other object.**

**Cause:** In the layout, an object was anchored to more than one other object.

**Action:** Eliminate the anchors to other objects such that the object is anchored to only one other object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01207: The PL/SQL procedure for group filter {0} is missing.**

**Cause:** The Filter Type on the Group Property Inspector specified a value of PL/SQL, but a valid filter was not specified.

**Action:** Enter a valid PL/SQL function or change the filter type.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01208: A repeating frame of matrix {0} cannot be anchored.**

**Cause:** An attempt was made to run a report with an anchor from an intersecting repeating frame of a matrix object to another object.

**Action:** Delete the anchor.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01209: Matrix {0} cannot be anchored.**

**Cause:** An attempt was made to run a report with an anchor from a matrix object to another object, which is not allowed.

**Action:** Delete the anchor.



---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01211: Object {0} is larger than its enclosing object {1}.**

**Cause:** An object is larger than its enclosing object. The most likely cause is that an attempt was made to enclose a large object within a small, fixed frame.

**Action:** Identify the object and the enclosing object and adjust their relative sizes and positions until the proper enclosure is achieved.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01212: Object {0} is not fully enclosed by its enclosing object {1}.**

**Cause:** The possible causes of this error include the following: Case 1: An object is not fully enclosed by the page. That is, the object extends beyond the page boundary. Case 2: A repeating frame that forms a matrix is one or more layers above a repeating frame that it contains. In a matrix layout, repeating frames must be below repeating frames that they contain.

**Action:** Take the following actions to correct this error: If Case 1: Move or resize the object so that it does not extend outside the page boundary. Alternatively, increase the page size in the Report Property Inspector. If Case 2: Use Arrange>Send to Back, Arrange>Bring to Front, Arrange>Move Backward, and Arrange>Move Forward to arrange repeating frames such that, in terms of layers, the following is true: repeating frames are below repeating frames that they contain and down repeating frames are below across repeating frames.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01213: Field {0} references column {1} at a frequency below its group.**

**Cause:** The source column for the field is in a group below that of the repeating frame that encloses it.

**Action:** Move the field into a repeating frame whose source group is at or above the group that contains the field's source column. Otherwise, move the field's source column into the enclosing repeating frame's group, if possible.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01214: Repeating frame {0} is enclosed by a child repeating frame.**

**Cause:** The enclosed repeating frame's source group is above the enclosing repeating frame's source group.

**Action:** In the editor, make the enclosed repeating frame the enclosing repeating frame. Alternatively, if possible, change the group hierarchy such that the enclosed object's group is below the enclosing object's group.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-01216: Object {0} has an illegal print condition.**

**Cause:** The Print Condition for the specified object was invalid. For example, an attempt may have been made to set the Print Condition of a margin object.

**Action:** Change the Print Condition of the object to another, valid setting.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01218: Object {0} cannot page break before AND keep with parent.**

**Cause:** Page Break Before was set for an object as well as Keep with Anchoring Object. The anchoring object, however, precedes the object and therefore the two settings are in conflict.

**Action:** Uncheck Page Break Before or Keep with Anchoring Object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01219: Object {0} has no size; length or width is zero.**

**Cause:** A layout object was created of zero width or height.

**Action:** Enlarge the object so that it has a non-zero height and width.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01220: Object {0} has Minimum Widow Records greater than Maximum Records per Page.**

**Cause:** Maximum Records per Page was set to a smaller value than Minimum Widow Records. This causes a conflict between the two settings and, in effect, indicates that no instances should be printed.

**Action:** Decrease Minimum Widow Records or increase Maximum Records per Page.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01222: The body size is invalid.**

**Cause:** A body page width or height was specified that is negative or out of range. This is most likely due to setting the page size to an invalid value using the PAGESIZE executable argument.

**Action:** Enter a valid value using the PAGESIZE executable argument, or adjust the body panel size by resizing the margins in the Paper Layout editor.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**REP-01223: The page size is invalid.**

**Cause:** A physical page width or height was specified that is negative or out of range. This is most likely due to setting the page size to an invalid value using the PAGESIZE executable argument.

**Action:** Enter a valid value using the PAGESIZE executable argument, or change the physical page size setting in the Report Property Inspector.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01225: The logical page size is invalid.**

**Cause:** A logical page height was specified that is negative.

**Action:** Redefine the logical panel height to ensure that it is not defined using a negative number.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01226: The body location is beyond the print area.**

**Cause:** The body panel is not enclosed within the physical page.

**Action:** Adjust the body panel size by resizing the margins in the Paper Layout editor.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01229: The spacing between records for repeating frame {0} is negative.**

**Cause:** The value for Vertical Spacing and/or Horizontal Spacing specified for a repeating frame is negative.

**Action:** Respecify the appropriate Spacing setting for the repeating frame.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01230: Field {0} has an invalid page reset group.**

**Cause:** In the Reset At field of the Page Numbering dialog box, a repeating frame was specified that does not enclose the layout field that should display the page number. An invalid repeating frame may have been specified, or the repeating frame was deleted after specifying it.

**Action:** Specify &Report or the name of a valid repeating frame as the Reset At value for the page number field.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-01231: Object {0} has an invalid text wrap style.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01232: Matrix {0} has an invalid source frame.**

**Cause:** An invalid object was specified as the source frame of the matrix object, or the repeating frames specified have invalid Print Directions.

**Action:** Change the Print Direction of horizontal source repeating frame to Down, and the Print Direction of the vertical source repeating frame to Across.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01233: The frames of matrix {0} do not fully intersect.**

**Cause:** The repeating frames that form the matrix do not completely intersect. For example, if there are two down repeating frames, two across repeating frames, and one of the across repeating frames only intersects completely with one of the down repeating frames, this error displays.

**Action:** Redefault the matrix layout, if possible, or move the repeating frames that make up the matrix such that they fully intersect one another.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01234: The position of matrix {0} is not at the intersection of its frames.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01235: An error occurred generating index for Cross Product.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01236: Query {0} is invalid.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

---

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01237: The data link is invalid.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**REP-01238: Group {0} is invalid.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01239: Column {0} is invalid.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01240: The anchor is invalid.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01241: A circular column dependency originating with column {0} exists.**

**Cause:** A column was created that directly or indirectly references itself. For example, Column A might reference Column B which in turn references Column A.

**Action:** Update or delete columns to eliminate the circular dependency.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01242: Matrices must have all down frames below all across frames.**

**Cause:** In a matrix layout, down repeating frames must be below across repeating frames.

**Action:** Using Arrange>Send to Back, Arrange>Bring to Front, Arrange>Move Backward, and Arrange>Move Forward, arrange repeating frames such that, in terms of layers, the following is true: repeating frames are

---

below repeating frames that they contain, and down repeating frames are below across repeating frames.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01243: An unimplemented type of summary is specified in column {0}.**

**Cause:** A summary function was specified that is not available.

**Action:** Specify a valid summary function.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01245: The wrong number of source columns are defined for summary function of column {0}.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01246: The graph document is not found.**

**Cause:** Oracle Reports Builder cannot find the associated graph document for the graph.

**Action:** Correct the file name and path of the graph document.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01247: The report contains uncompiled PL/SQL.**

**Cause:** An attempt was made to run the report before all referenced PL/SQL constructs was compiled.

**Action:** Compile the PL/SQL, then run the report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01248: All source columns of placeholder {0} must be in the same group.**

**Cause:** An attempt was made to set the value of a placeholder column from columns belonging to different groups.

**Action:** Change the placeholder column's group to match the group of the columns changing the placeholder column's value.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**REP-01249: Column {0} has no PL/SQL formula.**

**Cause:** A column of Type Formula was created with nothing in the Formula field.

**Action:** Create a formula for the column or change the column's Type.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01250: A circular query dependency exists.**

**Cause:** The report contains at least two queries, with each requiring the other to be executed first.

**Action:** Edit one or more of the queries to remove the circular dependency.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01251: A circular query dependency originating with query {0} exists.**

**Cause:** The report contains at least two queries, with each requiring the other to be executed first. The query listed in the message is one of the conflicting queries.

**Action:** Edit the query listed or another conflicting query to remove the circular dependency.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01252: The matrix should be surrounded by a repeating frame on group {0}.**

**Cause:** The data model for the report contains a matrix with a parent group, but in the layout the repeating frame for the parent group either does not exist or does not surround the matrix.

**Action:** Modify the layout of the report so that the parent group has a repeating frame that surrounds the matrix.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01253: Matrix objects are on different regions of the layout.**

**Cause:** The repeating frames of a matrix are on different regions of the layout (body, margin, header, or trailer).

**Action:** Move all repeating frames of the matrix to the same report region.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01254: Anchored objects are on different regions of the layout.**

---

**Cause:** The anchoring and anchored objects of an anchor are on different regions of the layout (body, margin, header, or trailer).

**Action:** Move the above-mentioned objects to the same report region.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01255: An object cannot anchor to a hidden object.**

**Cause:** The anchored object of an anchor is a hidden object.

**Action:** Either make the anchored object not hidden, or delete the anchor.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01256: File link boilerplate text is missing its source file.**

**Cause:** A file name was not specified in the Source Filename property for the file link boilerplate object.

**Action:** Specify a directory path and file name in the Source Filename property in the file link boilerplate object's Property Inspector.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01257: Oracle Reports Builder cannot fetch data for child query from caller.**

**Cause:** Oracle Reports Builder was invoked from another product, and Oracle Reports Builder has been instructed to fetch data for a child query from the caller. Data passed to Oracle Reports Builder can only be for a master query.

**Action:** Modify the caller's instructions so that Oracle Reports Builder does not request data for a child query.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-01258: Group {0} has no columns.**

**Cause:** A group was created that has no columns.

**Action:** Delete the group or assign one or more columns to the group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01259: Group {0} has no break columns.**

**Cause:** A parent group was created that has no break columns.

**Action:** Mark the Break Order checkbox of the break columns of the group.

**Level:** 1



---

**Type:** ERROR

**Impact:** Other

**REP-01260: Groups {0} and {1} are from the same query and cannot be linked.**

**Cause:** Two groups from the same query were linked with a data link, which is not allowed.

**Action:** Remove the data link or relink to another group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01261: Group {0} can have only one parent.**

**Cause:** One group has two queries as its parent (it can only have one).

**Action:** Remove data links from the same group to different queries.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01262: A circular data link dependency starting from group {0} exists.**

**Cause:** A cycle with data links was created (that is, a parent was specified as the child of itself, either directly or indirectly).

**Action:** Remove at least one of the links in the cycle.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-01263: Cross product group {0} has no or only one dimension group.**

**Cause:** A cross product group was defined that has no or only one group inside. Cross product groups must have at least two dimension groups. Multiquery cross product groups must have at least two queries within the cross product group.

**Action:** Remove the cross product group or add dimension groups, or dimension queries (if multiquery).

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01264: A data link of group {0} crosses cross a product boundary.**

**Cause:** In the multiple-query matrix report, a query has some of its groups are inside the cross product and some outside.

**Action:** Move all groups of the query to either outside or inside of the cross product group.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-01265: A cross product group {0} has no child groups.**

---

**Cause:** A cross product group has no child group, which is required. The child group acts as the cell of the matrix.

**Action:** Create a child group for the cross product group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01266: Page Level column {0} is not allowed in a cross product.**

**Cause:** A column was created in a cross product group that is or relies on a column that is a page-level summary (that is, a summary with Reset At of Page).

**Action:** Remove the column from the cross product group, or change the Reset At value of the column or the page-level summary upon which it relies.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01267: Graph {0} references an invalid column as a bind parameter.**

**Cause:** The graph references a column that does not exist. An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01268: Graph {0} references a bind column {1} at the wrong frequency.**

**Cause:** The column specified for the graph is in a group below that of the repeating frame that encloses the graph.

**Action:** Move the graph into a repeating frame whose source group is at or above the group that contains the specified column. Otherwise, move the specified column into the enclosing repeating frame's group, if possible.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01269: Graph {0} references an invalid report group.**

**Cause:** The report group specified for the graph does not exist. An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01270: Graph {0} references a report group at the wrong frequency.**

**Cause:** The report group specified for the graph is above the source group of the enclosing repeating frame.

---

**Action:** Move the graph into a repeating frame with a source group that is at or above its report group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01271: Graph column name {1} has been specified multiple times in the graph document {0}.**

**Cause:** The specified graph column or parameter has been referenced more than once in the graph document.

**Action:** Check the columns and parameters specified for the graph and delete any duplicates.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01272: Column {0} may not be used as a break column.**

**Cause:** A Break Order was specified on a summary, function, or placeholder. These types of columns cannot be used as break columns.

**Action:** Review the rules for which columns can be break columns. For more information, see the online help topic 'Break Order property'.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01273: Source groups of matrix {0} are not from the same cross product.**

**Cause:** The source groups of the repeating frames that form the dimensions of the matrix are not contained by the same cross product group. The dimensions of a matrix must be contained within the same cross product group.

**Action:** Change the source groups of the repeating frames or select different repeating frames to form the dimensions of the matrix.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01274: Invalid repeat direction combination in matrix {0}.**

**Cause:** Matrix dimension repeating frames whose source groups are in the same "family" hierarchy (that is, are descendants or ancestors of each other) within a cross product group must have the same Print Direction. Parent-child relationships within a cross product group are used to create nesting in the matrix. As a result, the repeating frames associated with such groups must print in the same direction on the page.

**Action:** Change the Print Direction of the repeating frames as necessary, select different source groups for the repeating frames, or select different repeating frames to form the dimensions of the matrix.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**REP-01275: Page level column {1} may not be referenced from format trigger {0}.**

**Cause:** PL/SQL was entered in a Format Trigger that references columns with a Reset At or Compute At of Page.

**Action:** Remove the reference to the page-level column or change the column's Reset At or Compute At to something other than Page.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01276: Placeholder {0} references one or more non-formula columns.**

**Cause:** A placeholder column contains SRW.REFERENCE, but the column referenced is not a formula column. For placeholder columns, SRW.REFERENCE must refer to a formula column.

**Action:** Change the column referenced via SRW.REFERENCE.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01277: The SELECT element is invalid.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01278: The PL/SQL procedure in {0} is invalid.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01279: Frame or repeating frame {0} is invalid.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01280: Field {0} is invalid.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

---

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01281: Boilerplate {0} is invalid.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01282: Matrix {0} is invalid.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01283: Graph document {0} is invalid.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01284: Query {0} has no groups.**

**Cause:** The data model contains a query that has no groups. Each query in the data model needs at least one group associated with it.

**Action:** Create a new group for the query.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01285: Query {0} has no SELECT elements.**

**Cause:** The data model contains a query that does not select anything. Each query in the data model must select at least one element.

**Action:** Enter a SELECT statement in the query, selecting at least one element.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01286: Group {0} is a cross product as well as a dimension.**

**Cause:** A group was specified to act as both a cross product group and as a dimension group for another cross product group, which is not allowed.

**Action:** Make the group either a cross product group or a dimension group, but not both.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01287: Cross product group {0} may not have a group filter.**

**Cause:** A group filter was specified on a cross product group, which is not allowed.

**Action:** Remove the group filter from the cross product group. Create the group filter for another group, if necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01288: The numeric argument for group filter of group {0} is missing.**

**Cause:** First or Last was specified for a group's filter, but a number dictating how many records the group should filter was not specified.

**Action:** Specify a number for the group filter.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01289: An unimplemented type of group filter is specified in group {0}.**

**Cause:** A group filter was specified that is not available or is invalid.

**Action:** Specify a valid group filter for the group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01290: The Source data type is incompatible with the summary function in column {0}.**

**Cause:** The summary column was assigned a Source whose data type is incompatible with the specified Function. For example, a temp may have been made to sum a character column.

**Action:** Verify that the data type of the source column is compatible with the Function specified in the Summary Column Property Inspector.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-01291: Column {0} has an invalid reset group.**

**Cause:** An invalid Reset At value was specified for a summary column. Reset At can be set to the same group as the summary column, any group above the summary column's, Page, or Report.

**Action:** Specify a valid Reset At value for the summary column in its Property Inspector.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-01292: Column {0} has an invalid compute group.**

**Cause:** An invalid Compute At value was specified for a summary column. Compute At can be set to the same group as the summary column, any group above the summary column's, Page, or Report.

**Action:** Specify a valid Compute At value for the summary column in its Property Inspector.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01293: Column {0} has an invalid product order.**

**Cause:** A column in a cross product group was assigned an invalid value for Product Order, or no value at all.

**Action:** Specify a valid value for Product Order (consisting of only dimension groups within the cross product) in the column's Property Inspector.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01294: The width of column {0} is too large.**

**Cause:** The column's width exceeds the maximum allowed for the operating system.

**Action:** Reduce the width of the column in the Column Property Inspector.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01295: The data format of column {0} is unsupported.**

**Cause:** Read from File was selected for a column, but an invalid or unavailable data format was specified in the Format field in the Column Property Inspector.

**Action:** Specify a valid data format in the Format field. The list of values displays all valid data formats. Note that for LONG, RAW, and LONG RAW database columns, only Text and Oracle Format (Image) are valid values for Format.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-01296: The data link child cannot be in the cross product group {0}.**

**Cause:** An attempt was made to link a column to a column in a cross product group, or to the cross product group itself.

**Action:** Create data links between columns and groups other than cross product groups and their associated columns.

**Level:** 1

---

**Type:** ERROR

**Impact:** Data

**REP-01297: The data link child column {0} must be a database column.**

**Cause:** An attempt was made to link a column to another column that is not a database column (for example, a summary, formula, or placeholder column).

**Action:** Create data links using only database columns and groups.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-01298: Columns {0} and {1} have incompatible types to be linked.**

**Cause:** The parent and child columns in the data link have incompatible datatypes that cannot be linked. For example, an attempt was made to link a Number column to a Character column.

**Action:** Verify that the parent and child columns specified in data links have compatible datatypes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01299: Groups {0} and {1} in different cross products cannot be linked.**

**Cause:** An attempt was made to create a data link between dimension groups of two different cross product groups, or between columns of the dimension groups.

**Action:** Delete data links between two different cross product groups or their columns.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01300: Text boilerplate {0} has no contents.**

**Cause:** A text boilerplate object was created that contains no text.

**Action:** Enter some text in the boilerplate object, or delete it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01301: The data link creates a sibling of group {0} within a cross product.**

**Cause:** A data link was defined that created a sibling of a dimension group within a cross product group. No siblings of dimension groups are allowed within the cross product.

**Action:** Delete the sibling of the dimension group.

**Level:** 1

**Type:** ERROR

**Impact:** Data



---

**REP-01302: The cross product has two or more child groups.**

**Cause:** A cross product group has more than one child group. Only one child is allowed per cross product group.

**Action:** Remove all but one of the child groups to the cross product group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01303: The query must be completely in or out of cross product group {0}.**

**Cause:** A query was created whose groups are not all inside the cross product, above the cross product, or below the cross product, respectively.

**Action:** Verify that each query's groups are all inside of a cross product, above a cross product, or below a cross product.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01304: Cross product group {0} contains another cross product as child.**

**Cause:** A cross product group was created that is a child of another cross product group, which is not allowed.

**Action:** Ensure that the child group of the cross product group is not a cross product group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01305: Frame {0} intersects but does not enclose object {1}.**

**Cause:** The report layout contains a frame that does not completely enclose the named object. Thus, the object is not considered to be inside the frame.

**Action:** To enclose the object with the frame, resize or move the frame.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01306: Summary column {0} has an invalid source.**

**Cause:** An invalid source was specified for the summary column. A summary column's source must be from the same group as the summary column, or from a group below the summary column.

**Action:** Change the source of the summary column to be from the same group as the summary column or from a group below the summary column.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01307: Summary column {0} has an invalid product order.**

---

**Cause:** The possible causes of this error include: Case 1: A summary exists that is not a running summary (that is, its Reset At is not Report), but its Product Order is not a subset of the source column's product order. The source column of the summary must be at least as frequent as the summary, which means that the summary's Product Order should be some subset of the source column's Product Order. Case 2: A running summary (that is, its Reset At is Report) exists with a Product Order that is not a prefix of the source column's Product Order. For example, if the source column's Product Order were A,B,C, then the summary column's Product Order would have to be either A (by itself) or A,B. The summary's Product Order could not be B,A.

**Action:** Take the following actions to correct this error: If Case 1: Change the Product Order of the summary such that it is a subset of its source column's Product Order. If Case 2: Change the Product Order of the summary such that it is a prefix of the Source column's Product Order.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01308: Placeholder column {0} is not supported in a cross product.**

**Cause:** An attempt was made to create a placeholder column inside of a cross product group. Cross product groups cannot contain placeholder columns.

**Action:** Delete the placeholder or move it outside the cross product group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01309: Report level summary {0} cannot be a percent of total.**

**Cause:** A summary was created at the report-level (that is, a summary outside of all the groups in the data model) with a Function of % of Total. This Function makes no sense for a report-level summary because it will always be 100%.

**Action:** Delete the summary or move it into a group where it will make sense.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01310: Boilerplate {0} references &{1} which is not a field.**

**Cause:** A boilerplate object has a reference to a field that does not exist. It could be that the field being referenced was deleted or renamed and so this reference in the boilerplate object is now invalid.

**Action:** Depending on circumstances, remove the reference, replace it with a reference to another field, or create the field that it references.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01311: Object {0} with page-dependent references have been changed to fixed sizing.**

---

**Cause:** A field or boilerplate object has a reference to a page calculation or a total number of pages variable. (This is known as a forward reference.) Such layout objects must be fixed in size both horizontally and vertically.

**Action:** The layout object's Horizontal and Vertical Elasticity have been set to Fixed by Oracle Reports Builder. Check the output to ensure that the values are not being truncated. If they are, enlarge the layout object so that it is large enough to contain the values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01312: Page-level column {1} may not be referenced from graph {0}.**

**Cause:** A column passed to a graph is or depends upon a page-level summary (that is, a summary with a Reset At or Compute At of Page). A column being passed to a graph cannot be or depend upon a page-level summary.

**Action:** Do not pass the column to the graph.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01313: Page-level column {1} may not be referenced from group filter {0}.**

**Cause:** A column that was referenced in a group filter is or depends upon a page-level summary (that is, a summary with a Reset At or Compute At of Page). A column referenced by a group filter cannot be or depend upon a page-level summary.

**Action:** Do not reference the column in the group filter.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01314: Format trigger {0} references column {1} at the wrong frequency.**

**Cause:** A format trigger references a column that is located at the wrong frequency.

**Action:** Remove the reference to the column from the format trigger.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01315: Group filter {0} references column {1} at the wrong frequency.**

**Cause:** A group filter attempted to reference a column that is inaccessible.

**Action:** Remove the reference to the column from the group filter.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01316: Object {0} references column {1} at the wrong frequency.**

---

**Cause:** A procedure or function attempted to reference a column that is inaccessible.

**Action:** Remove the reference to the column from the PL/SQL subprogram.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01317: Boilerplate {0} references field with source {1} at the wrong frequency.**

**Cause:** A boilerplate object referenced a field using &fieldname, but the two objects are not located at the same frequency. For example, the boilerplate object and the field it references are located within different repeating frames.

**Action:** Place the boilerplate object and field at the same frequency, or remove the reference.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01318: An error occurred while setting transaction to read-only.**

**Cause:** Having specified READONLY=YES, this error occurred at the start of report execution, while ending the current transaction (with a COMMIT) and starting the read-only transaction, or at the end of report execution, while ending the read-only transaction (with a COMMIT).

**Action:** Verify the database connection, and verify that that no cursors or locks were left pending by the previous transaction.

**Level:** 1

**Type:** ERROR

**Impact:** Transactioning

**REP-01319: Implicit anchoring algorithm cannot uniquely identify the anchoring object {0}. Arbitrarily choosing {1}.**

**Cause:** The specified object (object1) is in the "push path" of two objects and it is equidistant from both objects. As a result, Oracle Reports Builder cannot use its normal criteria (shortest distance) to determine the implicit anchor. In the absence of its normal criteria, Oracle Reports Builder randomly creates an implicit anchor to the specified object (object2). Note that the implicit anchor may vary between runs of the report.

**Action:** To avoid the random creation of an implicit anchor, explicitly anchor the specified object (object1) to another object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01320: Program unit {0} references a column with invalid ID {1}.**

**Cause:** A report was run containing invalid PL/SQL (for example, PL/SQL that did not compile). The PL/SQL source included a column reference that cannot be resolved.

**Action:** Check the column references in the PL/SQL source, recompile all of the PL/SQL source in the report, and rerun the report.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01322: Page break after on object {0} has no effect.**

**Cause:** A Page Break After was activated on an object that has no other objects anchored to it (implicitly or explicitly). In this case, Page Break After has no effect and is invalid. Notice that this is a warning, not an error message.

**Action:** Deactivate Page Break After for the object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01323: Output columns in format trigger {0} are not allowed.**

**Cause:** In the format trigger for the specified object, an attempt was made to set the value of an Oracle Reports Builder column parameter. For example, the value of a column called COUNT1 can be used in a condition (for example, IF :COUNT1=10), but its value cannot be directly set in an assignment statement (for example, COUNT1=10).

**Action:** Remove the assignment statement from the format trigger.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01324: Output columns in group filter {0} are not allowed.**

**Cause:** In the filter for the specified group, an attempt was made to set the value of an Oracle Reports Builder column or parameter. For example, the value of a column called COUNT1 can be used in a condition (for example, IF :COUNT1=10), but its value cannot be directly set in an assignment statement (for example, COUNT1=10).

**Action:** Remove the assignment statement from the group filter.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01325: Output columns in a Between Page Trigger are not allowed.**

**Cause:** In the Between Page trigger, an attempt was made to set the value of an Oracle Reports Builder column or parameter. For example, the value of a column called COUNT1 can be used in a condition (for example, IF :COUNT1=10), but its value cannot be directly set in an assignment statement (for example, COUNT1=10).

**Action:** Remove the assignment statement from the group filter.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01326: Trigger {0} writes to column {1} at the wrong frequency.**

---

**Cause:** In a report trigger, an attempt was made to set the value of an Oracle Reports Builder column at the wrong frequency in the report. Only report-level columns or parameters can be referenced and set, and any page-dependent columns (that is, Reset At of Page) or columns that rely on page-dependent columns cannot be referenced or set.

**Action:** Verify that the columns and parameters whose values are referenced or set are report-level columns and parameters.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01327: Column {0} writes to column {1} at the wrong frequency.**

**Cause:** In a formula column, an attempt was made to set the value of an Oracle Reports Builder column at the wrong frequency in the report. Only columns that are in the same group or in a higher group in the group hierarchy can be referenced and set. For example, a formula for a report-level column can only reference other report-level columns.

**Action:** Verify that the columns whose values are referenced or set are in the same group or in a higher group in the group hierarchy.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01328: A report containing ROWLABEL column {0} cannot be run in a non-trusted OS.**

**Cause:** An attempt was made to run a report that requires a secure database while connected to a non-secure database.

**Action:** Run the report while connected to a secure database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01329: Column {0} cannot be linked to column {1} because the child column is not a database column.**

**Cause:** A data link was created in which the child column is a summary, formula, or placeholder column. Only database columns can be linked.

**Action:** Create a data link using database columns.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01330: Lexical parameter {0} in query {1} must not change column dependencies.**

**Cause:** A lexical parameter was created that changes the number, type, or names of columns, or introduces new dependencies on computed columns or new bind references, when the report is run.

**Action:** Change the lexical parameter so that it does not change columns or introduce new dependencies or bind references.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01331: Column {0} cannot be linked to column {1} because the child column is determined by a lexical parameter.**

**Cause:** A data link was created in which child column's value is determined by a lexical parameter, which is not allowed.

**Action:** Replace the child column of the data link with another column.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01332: Group filter for {0} cannot reference column {1}. It is not a valid database column or it depends on a related query.**

**Cause:** A group filter was created that references a database column not in the group's query or in a query above it, or references a computed column that depends on an unrelated column.

**Action:** Remove the offending reference from the group filter.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01333: Unsupported layout: a matrix may not be inside another matrix.**

**Cause:** A matrix layout was created nested within another matrix layout, which is not allowed.

**Action:** Redesign the layout to avoid the nesting.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01335: Variable rotated text {0} is treated as fixed/contract width.**

**Cause:** The report contains a boilerplate text object that was rotated to an angle that is not a multiple of 90 degrees, although both Horizontal and Vertical Elasticity values were set to Variable or Expand. In this case, the Horizontal Elasticity is treated as Fixed (if Expand was specified) or Contract (if Variable was specified), and this warning is displayed.

**Action:** Consider changing the Horizontal and Vertical Elasticity values for this boilerplate object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01336: The source of field {0} is page-level calculation {1}. {2}.**

**Cause:** The specified field references a page summary owned by the named group, but there is no repeating frame for that group that surrounds the field.

---

**Action:** Create a repeating frame whose Source is the named group to surround the field. If such a repeating frame already exists, extend it to enclose the field.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01337: Boilerplate {3} references field {0}, whose source is page-level calculation {1}. {2}.**

**Cause:** The specified boilerplate object references the specified field, whose Source is a page-level computation. However, there is no repeating frame (whose Source is the named group) surrounding the field.

**Action:** Create a repeating frame whose Source is the named group to surround the field. If such a repeating frame already exists, extend it to enclose the field.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01338: Column mode is not allowed on repeating frame {0}.**

**Cause:** The Column Mode setting for a repeating frame does not satisfy either of the following conditions: Print Direction of Down and a Vertical Elasticity of Fixed. Print Direction of Across and a Horizontal Elasticity of Fixed.

**Action:** Change the Print Direction or Vertical/Horizontal Elasticity of the repeating frame, or deactivate Column Mode.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01339: Graph {0} is missing a data column specification.**

**Cause:** A value was specified for the graph Query, but no columns were specified to be passed from the report to the graph document.

**Action:** To pass no data from the report to the graph document, specify nothing for the graph Query and Source. To pass data, specify the columns to be passed in addition to the graph Query and Source.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-01340: Passed-in columns do not match report definition {0}.**

**Cause:** Another component (for example, Oracle Forms) passed a query to Oracle Reports Builder and there is a mismatch between the columns passed and the columns expected by Oracle Reports Builder. Possible causes of this error include: Case 1: Oracle Reports Builder was expecting more or fewer columns than the number that was actually passed by the calling application. Case 2: The parameter list of the calling application described a column differently than what Oracle Reports Builder expected. For example, if the report's query selects a character column and the calling application assigns that column a date data type, this error is raised.



---

**Action:** Take the following actions to correct this error: If Case 1: Ensure that the calling application is passing the same number of columns that Oracle Reports Builder expects. If Case 2: Ensure that the datatypes and names of the columns being passed by the calling application match the datatypes and names in the report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01341: Data truncation is possible in column {0}.**

**Cause:** The database column's width in the report is defined to be less than its width in the database. This can occur when the columns in the database are updated subsequent to the creation of the report definition.

**Action:** Force the query to be reparsed. One method is to type a space at the end of a line in the SELECT Statement and then accept the SQL Query Statement dialog box.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-01342: The type of the data link to query {0} is illegal for a non-Oracle server.**

**Cause:** A data link was created with the START WITH clause and run while connected to a non-Oracle database. START WITH is only supported by Oracle.

**Action:** Remove the data link that uses START WITH or connect to Oracle.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-01343: Button {0} is invalid.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01344: Button {0} has no action source file.**

**Cause:** An action of Multimedia File was specified for the named button, but either a source file was not specified, or a source file was specified that does not exist.

**Action:** Open the Property Inspector for the specified button and verify that a valid file was selected as source for the button action.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01345: Button {0} has an invalid source column.**

---

**Cause:** An action of Multimedia Column was specified for the named button, but either a source column was not specified, or an invalid source column was specified.

**Action:** Open the Property Inspector for the specified button and verify that a valid column was selected as source for the button action.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01346: Button {0} references source column {1} at the wrong frequency.**

**Cause:** The column specified in the Property Inspector for the named button is in a group below that of the repeating frame that encloses the button.

**Action:** Move the button into a repeating frame whose source group is at or above the group that contains the specified column. Otherwise, move the specified column into the enclosing repeating frame's group, if possible.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01347: Button {0} has an invalid icon file.**

**Cause:** Either an invalid file or a nonexistent file was specified as the icon file for the button face.

**Action:** Ensure that the specified icon file exists and is of the proper format and uncorrupted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01348: The source column of field {0} is in sound or video format.**

**Cause:** A column was specified containing sound or video as the source for a field, but fields cannot display sound and video.

**Action:** Specify another column (not sound or video) as source of the field.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01349: The PL/SQL action is missing from button {0}.**

**Cause:** The PL/SQL trigger that serves as the specified button's action references a piece of PL/SQL that does not exist.

**Action:** Debug the trigger and ensure that it references a valid program unit.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01350: Output columns in action trigger {0} are not allowed.**

---

**Cause:** The PL/SQL trigger that serves as a button action contains a bind variable that returns a value. A PL/SQL action trigger cannot return a value.

**Action:** Remove the bind variable from the PL/SQL.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01351: Icon {1} on button {0} cannot be found.**

**Cause:** The icon specified as the button face for the named button cannot be found. The report will run, but the button will appear blank.

**Action:** Open the Property Inspector for the named button and verify that the icon specified exists and is in the correct format, and that the path information is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01352: The fonts specified for this report cannot be found for the character set specified by NLS\_LANG.**

**Cause:** The NLS\_LANG environment variable specifies a character set for which no font is available.

**Action:** Select a font that exists in the character set specified by NLS\_LANG. Alternatively, use the Font Alias file to force an available font to be used, instead of the one specified in the report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01353: The Web property of layout object {0} references field or column {1} at the wrong frequency.**

**Cause:** One of the layout object properties (Bookmark, Action, Hyperlink, or Linktag) references a field or column, but the two objects are not located at the same frequency. For example, the layout object is located within a repeating frame whose source is a different group to that the column is in.

**Action:** Place the layout object in a repeating frame at the same frequency as the column object, or remove the reference.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01354: The Web property of layout object {0} references a page-dependent field or column {1}.**

**Cause:** One of the layout object properties (Bookmark, Action, Hyperlink, or Linktag) references a field or boilerplate object that has a reference to a page calculation or a total number of pages variable. Web properties may only reference columns and fields that are not based on page calculations.

**Action:** Remove the Web property reference to the page-dependent field or column.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01355: PL/SQL is missing from PL/SQL-based query {0}.**

**Cause:** A PL/SQL based query was created, but no PL/SQL was entered for it.

**Action:** Enter PL/SQL for the query.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01356: A column link is not allowed for linking to PL/SQL-based query {0}.**

**Cause:** An attempt was made to link a column to another column that is in PL/SQL-based query, which is not allowed.

**Action:** Create group links and use the columns in the PL/SQL-based query as bind variables to set up intended column link conditions.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01357: Auto foreign key column link creation is only for SQL queries.**

**Cause:** A link was dragged between two queries to automatically create column links based on foreign key relationships. However, this can be done only between two SQL queries.

**Action:** Drag a link between two SQL queries, or change the PL/SQL-based queries to SQL.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01365: A column link is not allowed for linking to Express-based query {0}.**

**Cause:** An attempt was made to link a column to another column that is an Express-based query, which is not allowed.

**Action:** Create group links and use the columns in an Express-based query as bind variables to set up intended column link conditions.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01366: The XML Settings of object {0} reference page-dependent field or column {1}.**

**Cause:** One of the object's XML properties references a field that contains a page calculation or a total number of pages variable. XML Settings cannot reference columns and fields that are based on page calculations.

**Action:** Remove the XML Settings references to the page-dependent field or column.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01367: The XML Settings of object {0} reference field or column {1} at the wrong frequency.**

**Cause:** One of the object's XML properties references a field or column that has a different frequency than the object (for example, the column may be in a different group than the object referencing it).

**Action:** Move the object such that it has the same frequency as the field or column (for example, place them in the same group) it references or remove the reference.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01368: Group {0} in the graph settings is invalid.**

**Cause:** In the graph object's graph settings, the src attribute is an invalid group name.

**Action:** Ensure that value of the src attribute is a valid group name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01369: An internal error occurred caused by form field {0}.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01370: Action {0} is unsupported.**

**Cause:** The action specified against the form field is currently not supported.

**Action:** Remove the action entry from the report definition.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01371: Form field object {0} is unsupported.**

**Cause:** This form field type is currently not supported by Oracle Reports.

**Action:** Remove the Form Field element from the report definition.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01372: The export value specified for {0} is invalid.**

---

**Cause:** Either the export value is not specified or the export value is "off".

**Action:** Specify a valid export value ("off" is a reserved word).

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01373: The validation and formatAndTreatment elements are not allowed for Form Field {0}.**

**Cause:** The 'validation' or 'formatAndTreatment' element was specified for a Check Box and Radio Button.

**Action:** Remove the 'validation' or 'formatAndTreatment' element for the Form Field object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01374: Font {0} is used to subset for the Form Field object {1}.**

**Cause:** The font that is used to render a Form Field object was subsetted, which is not allowed.

**Action:** Either remove the font entry in uifont.ali or modify the font name of the Form Field object to a font that is not subset.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01400: coxr is not initialized.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01401: A fatal PL/SQL error occurred in program unit {2}.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01402: An unhandled PL/SQL exception occurred in program unit {2}.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Other

**REP-01403: A PL/SQL procedure is suspended in program unit {2}.**

**Cause:** A PL/SQL construct was suspended during execution or generation.

**Action:** Debug and recompile the PL/SQL constructs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01404: PL/SQL compilation failed.**

**Cause:** In generating the report, PL/SQL compilation failed.

**Action:** Debug the PL/SQL constructs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01405: The PL/DQL code is not executable.**

**Cause:** A PL/SQL construct did not compile properly or could not be executed.

**Action:** Debug the PL/SQL constructs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01406: Parameterized code cannot be run directly.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01408: The PL/SQL cannot be initialized.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01409: Expected IS after PROCEDURE cannot be found.**

**Cause:** A PL/SQL syntax error occurred.

**Action:** Correct the PL/SQL procedure in trigger/program unit and compile.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01410: An error occurred executing a PL/SQL filter in program unit {2}.**

---

**Cause:** A PL/SQL syntax error occurred.

**Action:** Correct the PL/SQL procedure in trigger/program unit and compile.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01411: An error occurred executing PL/SQL formula in program unit {2}.**

**Cause:** A PL/SQL syntax error occurred.

**Action:** Correct the PL/SQL procedure in program unit of formula column or trigger. Verify the variable declarations and usage.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01412: PL/SQL function {2} returned an invalid value or no value.**

**Cause:** The report contains a PL/SQL function that does not specify a return value (for example, a format trigger that does not return TRUE or FALSE).

**Action:** Verify that the function includes a return statement for every code path.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01414: A library unit to run cannot be found in program unit {2}.**

**Cause:** This is most likely an abnormal condition.

**Action:** Check the PL/SQL code and recompile it. If this error recurs, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01415: An unknown user exit {0} was encountered in program unit {2}.**

**Cause:** A user exit was called, but it was not found.

**Action:** Verify the correct name for the user exit and that it has been compiled and linked.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01416: An error occurred in user exit {0} in program unit {2}. {1}.**

**Cause:** An error occurred in a user exit. Possible errors: a reference to an unknown column, a truncated column value, unretrievable PL/SQL source, or the user exit was not found.

**Action:** Based on the submessage, debug the user exit. Verify columns references are valid and the PL/SQL code and user exit are accessible.

**Level:** 1



---

**Type:** ERROR

**Impact:** Other

**REP-01417: An invalid integer argument was passed to procedure {0} in program unit {2}.**

**Cause:** The packaged procedure referenced expected an integer for an argument, but it was not specified.

**Action:** Verify that the PL/SQL that references the packaged procedure correctly passes it an integer. For more information about PL/SQL packaged procedures, see the Oracle Reports online help.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01418: Null arguments were passed to procedure {0} in program unit {2}.**

**Cause:** The exception SRW.NULL\_ARGUMENTS was raised, either by a user-defined PL/SQL subprogram, or because a packaged subprogram was passed one or more null arguments.

**Action:** Check any PL/SQL code that might raise this exception. Also, check the argument list that is passed to the specified packaged subprogram.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01419: The PL/SQL program was aborted in program unit {2}.**

**Cause:** A PL/SQL construct had a fatal error and was aborted.

**Action:** Check the PL/SQL constructs for errors.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01420: The PL/SQL program raised a program error in program unit {2}.**

**Cause:** The exception SRW.PROGRAM\_ERROR was raised, either by a user-defined PL/SQL subprogram, or because of an abnormal condition.

**Action:** Check any PL/SQL code that might raise this exception. If no PL/SQL raised the exception, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01421: A column of the wrong type was manipulated in procedure {0} in program unit {2}.**

**Cause:** The data type of the column whose name was passed to a packaged procedure is not the correct data type for the packaged procedure (for example, the packaged procedure was expecting a column of Character data type and it was passed a column of another data type).

---

**Action:** Debug the PL/SQL that references packaged procedures and ensure that the packaged procedure is passed the name of a column of the correct data type. Also check the syntax of the packaged procedure to ensure that its is referenced properly.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01422: A procedure by this name already exists.**

**Cause:** An attempt was made to create a new PL/SQL procedure with the same name as an existing PL/SQL procedure.

**Action:** Change the name of the new procedure or change the name of the existing procedure.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01423: Maximum rows of a query cannot be set after the query started executing in program unit {2}.**

**Cause:** SRW.SET\_MAX\_ROW was used to reduce the number of rows fetched by a query. However, SRW.SET\_MAX\_ROW was called after the query was already fetched.

**Action:** Move SRW.SET\_MAX\_ROW to the Before Report trigger.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01424: An internal error occurred while executing procedure {0} in program unit {2}.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01425: An error occurred running DO\_SQL package in program unit {2}: {0}.**

**Cause:** An error occurred while Oracle Reports Builder was executing an SRW.DO\_SQL call. Embedded in this message is an Oracle Reports Builder message and, possibly, an Oracle error message describing the exact error that occurred.

**Action:** Errors in SRW.DO\_SQL are most often the result of a SQL error. Refer to the SQL Language Reference Manual and verify that the SQL statement in the SRW.DO\_SQL call is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-01426: Procedure {0} was running from incorrect context in program unit {2}.**

**Cause:** An attempt was made to call the named packaged procedure from an invalid area. For example, SRW.SET\_ATTR cannot be called from a formula.

**Action:** Modify the PL/SQL code so that it does not call the packaged procedure from that context.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01427: A nonexistent query name was referenced in procedure {0} in program unit {2}.**

**Cause:** A call was made to the SRW.SET\_MAXROW procedure in a Before Report trigger, but the query referenced in the procedure call does not exist.

**Action:** Change the call to the SRW.SET\_MAXROW procedure so that it references an existing query in the report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01428: An error occurred while running procedure {0} in program unit {2}.**

**Cause:** The exception SRW.RUN\_REPORT\_FAILURE was raised, either by a user-defined PL/SQL subprogram, or because of an abnormal condition after SRW.RUN\_REPORT was called.

**Action:** Check any PL/SQL code that might raise this exception. If no PL/SQL raised the exception, check the command line string passed to SRW.RUN\_REPORT. Verify that BATCH=YES, that the specified report exists, and that all parameter values are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01429: Procedure {0} cannot be invoked with BATCH=NO in program unit {2}.**

**Cause:** A call was made to the SRW.RUN\_REPORT procedure with a command line string containing BATCH=NO, which is not allowed.

**Action:** Remove BATCH=NO from the SRW.RUN\_REPORT command string.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01430: A REP file for report {0} cannot be created: compilation errors found.**

**Cause:** There is an error in the PL/SQL in the report to be converted.

**Action:** Open the report and debug the PL/SQL.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-01433: An error occurred running user exit {0} in program unit {2}.**

**Cause:** While running the user exit named in the message, an error occurred.

**Action:** Debug the user exit and ensure that it is linked.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01434: Procedure {0} cannot be invoked with a user ID in program unit {2}.**

**Cause:** A call was included to the SRW.RUN\_REPORT procedure with a command line string containing a userid/password, which is not allowed.

**Action:** Remove the userid/password from the SRW.RUN\_REPORT command string.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01435: The value of column {0} was truncated in program unit {2}.**

**Cause:** A column (for example, a placeholder) was assigned a value larger than its width could contain, raising the SRW.TRUNCATED\_VALUE exception. The exception was not handled, raising this error.

**Action:** Make the column wide enough to contain the assigned value, or handle the exception in the PL/SQL source.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01436: The PL/SQL references an object that is not in the scope in program unit {2}.**

**Cause:** In a parameter's Validation Trigger field, PL/SQL source referenced a report column, which is not allowed.

**Action:** Remove the reference to the report column from the parameter's Validation Trigger.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01437: A run time error in the PL/SQL development environment (DE).**

**Cause:** This is most likely an abnormal condition.

**Action:** Refer to the accompanying development environment error message for details on the problem. For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01438: The GETREF function parameter {0} must be of type LONG, LONG RAW, or RAW.**

---

**Cause:** The second parameter in a CDE\_MM.GET\_REF call specifies a column that is not of type LONG, LONG RAW, or RAW.

**Action:** Change the second parameter to specify a column of the correct type.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01440: An unknown column name was passed to {0} in program unit {2}.**

**Cause:** A column name specified in the named program unit in one of the triggers is invalid.

**Action:** Verify the column name is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01441: A column value was not available for {0} in program unit {2}.**

**Cause:** A column name specified in the named program unit in one of the triggers is not available.

**Action:** Verify the column value is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01442: Column value {0} cannot be set in program unit {2}.**

**Cause:** A value is not settable for this column.

**Action:** Verify the procedure is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01443: Column value {0} is invalid in program unit {2}.**

**Cause:** A column value specified in the named program unit in one of the triggers is invalid.

**Action:** Verify the column value is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01444: No more rows exist in the group handle.**

**Cause:** SRW.GH\_NEXT() is called when the group handle is already at the last row.

**Action:** Catch a SRW.NO\_DATA\_FOUND exception in PL/SQL.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**REP-01445: The JAVA class cannot be found.**

**Cause:** The requested class could not be located within the Reports classpath.

**Action:** Ensure that the class is correctly specified (for example, java/lang/String) and that the class is in the Reports classpath specified in the REPORTS\_CLASSPATH environment variable.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01446: The JAVA method cannot be found.**

**Cause:** The requested method could not be located within in the specified class.

**Action:** Ensure that the method exists within the specified class and has the correct signature: '(Ljava/lang/String;)Ljava/lang/String;'.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01447: A JAVA exception was encountered.**

**Cause:** An error occurred attempting to start the JVM and access the requested Java class and method.

**Action:** Check the JVM install and environment.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01448: The data model group passed to SRW.GH\_CREATE() does not exist.**

**Cause:** The group name parameter of SRW.GH\_CREATE() is invalid.

**Action:** Ensure that the group name is correctly specified. Catch the SRW.UNKNOWN\_GROUP exception in PL/SQL.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-01508: Cross Product: value of calculation cannot be found.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01510: Group Manager: unable to compute column {0}.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01516: Reset At Page is an invalid option for column {0} in Web-based reports.**

**Cause:** A column in the report layout has Reset At Page, which is invalid for Web-based reports.

**Action:** Specify Reset At for either a group or report for Web-based reports.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01517: Column {0} references column {1}, which has incompatible frequency.**

**Cause:** A column in the data model references another column (for example, in the Formula field) in the data model, but the two columns are assigned to incompatible groups. For example, if a formula column with a Group of Report referenced a column with a Group of G\_Emp, this error is raised.

**Action:** Remove the column reference, or assign the referencing column to a group that is compatible with the group of the referenced column.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01518: Group Manager: internal error {0} occurred while processing group {1}.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01607: Record Manager: the source of report level column {0} is not available.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01610: Record Manager: a query with internal joins has Maximum Number of Rows set.**

**Cause:** SRW.SET\_MAXROW was probably used to set Maximum Number of Rows on the cell query of a multiquery cross product.

**Action:** Remove the call to SRW.SET\_MAXROW for the cell query.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-01760: Error Utility: internal error #1 occurred.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01761: Internal error {0} occurred while processing {2} {1}.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01762: Internal error {0} occurred.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01780: Stack utility: an error occurred during allocation.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01781: Stack utility: an error occurred during push.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01782: Stack utility: an error occurred during pop.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01783: Stack utility: an attempt was made to pop an empty stack.**

**Cause:** An abnormal condition was encountered.



---

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01800: A formatter error occurred.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01801: An unknown file type was encountered for a Read from File field.**

**Cause:** An attempt was made to create a file column, but the file type entered was invalid.

**Action:** Display the list of values and pick a valid file type.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01802: Contents of a field cannot be read from a text file.**

**Cause:** Read from File was selected for a column, but Oracle Reports Builder could not find the files pointed to by the column. The possible causes of this error include the following: Case 1: The files do not exist. Case 2: The necessary privileges to access the files are not granted. Case 3: A system error made it impossible to find the files.

**Action:** Take the following actions to correct this error: If Case 1: Uncheck Read from File or create the necessary files. If Case 2: Update privileges, if possible. If Case 3: Consult the operating system documentation or contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01803: Destination file {0} cannot be opened.**

**Cause:** The destination file specified for the report could not be opened.

**Action:** Consult the operating system documentation or contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01804: Printer definition file {0} cannot be opened.**

**Cause:** The printer definition file for the specified printer could not be opened.

**Action:** Consult the operating system documentation or contact the system administrator.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01805: Mail text file {0} cannot be opened.**

**Cause:** An attempt was made to send the report output to a mail message, but the file for the message could not be opened.

**Action:** Consult the Oracle\*Mail documentation or contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01806: Mail command file {0} cannot be opened.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01807: The mail report command failed.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01808: The print command file cannot be opened.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01809: The print report command failed.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01810: The Oracle Reports Builder ASCII Driver will be used to run a character report.**

**Cause:** An attempt was made to print a character-mode report to a printer or a file using either a PostScript driver or the Microsoft Windows Generic Text driver.

---

**Action:** No action necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01811: An error occurred while generating a graph.**

**Cause:** Oracle Reports Builder called Graphics Runtime to generate a graph, but no graph was created.

**Action:** Verify that the named graph document exists and will run.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01812: Too many pages formatted. There is either too much data or an error in the report's definition.**

**Cause:** The possible causes of this error include the following: Case 1: A user-defined limit set to catch too much data has been reached. Case 2: An error in the report definition has been reached.

**Action:** Take the following actions to correct this error: If Case 1: Abort running the program. Check the value of PAGE\_LIMIT in the PRODUCT\_PROFILE table. Ensure that it is either '0', which means the user is allowed to format an unlimited number of pages, or some value sufficiently large to enable the user to format the report. If Case 2: Debug the report in the Report Editor.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-01813: Object {0} is too large to fit in a matrix cell.**

**Cause:** The data fetched into a matrix cell exceeds the capacity of the cell. For example, the cell may contain a variable field, and the data may be longer than expected.

**Action:** Either enlarge the matrix cells until they are able to contain the data fetched into them, or redefine the data.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01814: The report cannot be formatted. Object {1} cannot fit within location {0}.**

**Cause:** The referenced object is causing the most recently formatted page to start with exactly the same state as the previous page. Formatting will therefore cycle until abnormally terminated. Possible causes of this error include: Case 1: An object whose Print Condition type is All overflows to the next page. Case 2: An object whose sizing is Variable or Expand does not appear to extend beyond page boundaries in the Paper Layout editor but does when the report is formatted. Case 3: A repeating frame does not appear to extend beyond page boundaries in the Paper Layout editor but does when the report is formatted.

**Action:** Using the referenced object as a guide, examine the report layout for objects that may extend beyond page boundaries. Note: The object referenced in

---

the message is the object that extends beyond the boundary. This object may be pushed beyond the boundary by another object, and this second object may need modification.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01815: A bad Oracle Number was encountered.**

**Cause:** A formula providing the value of a column failed to specify any value.

**Action:** Debug any formulas in the report columns and ensure that each formula specifies a value where necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01816: No value was specified for COPIES, and no output was created.**

**Cause:** In the Runtime Parameter Form or the Print Job dialog box, zero (0) copies was specified.

**Action:** Specify a value of one or more copies.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01817: The start page occurs after the end page. No pages were generated.**

**Cause:** In the Print Job dialog box, a starting page number was specified that is greater than the ending page number.

**Action:** Change either the starting page number or the ending page number such that the starting number is less than the ending number.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01818: Data in image format could not be read.**

**Cause:** Possible causes of this error include: Case 1: An attempt was made to read a file or database column as containing an image, but the file or column's contents are of the wrong format. Case 2: The width of the Oracle Reports Builder column specified may be truncating the image because it is too small. Case 3: REPORTS\_DEFAULT\_DISPLAY is set to YES and the image format used is not supported.

**Action:** Take the following actions to correct this error: If Case 1: Verify that the file or column specified contains an image in a valid format. If Case 2: Change the width of the Oracle Reports Builder column so that it is large enough to display the image. If Case 3: Verify that the image format is one of the supported formats: GIF, JPEG, JPG, PNG, BMP.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**REP-01819: Filename {0} is longer than the platform maximum of {1} characters.**

**Cause:** A name was specified for a file that is longer than the platform-allowed maximum. This is most likely to occur when accessing a file using Read from File, and the file name in the database is too long.

**Action:** Verify that the database is not corrupted, or run the report on a platform that accepts filenames of the specified length.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01820: The Oracle Reports Builder ASCII Driver cannot be used to run a bitmap report.**

**Cause:** An attempt was made to print a bitmapped report when the Oracle Reports Builder ASCII Driver is the default printer.

**Action:** Select a different printer, then print the report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01825: The Before Report trigger returned FALSE.**

**Cause:** The report includes a Before Report trigger that returned a value of FALSE rather than TRUE. When a trigger returns a value of FALSE, report formatting stops.

**Action:** Verify that the report trigger is meant to return a value of FALSE.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01826: The Between Page trigger returned FALSE.**

**Cause:** The report includes a Between Page trigger that returned a value of FALSE rather than TRUE. When a trigger returns a value of FALSE, report formatting stops.

**Action:** Verify that the report trigger is meant to return a value of FALSE.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01827: Parentheses in the format mask do not balance.**

**Cause:** Unmatched parenthesis exist in the format mask.

**Action:** Edit the format mask and insert the necessary parenthesis.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01828: A format mask may contain at most one set of parentheses.**

**Cause:** More than one set of parentheses was used in the format mask.

---

**Action:** Use only one set of parentheses in the format mask.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01829: Left parenthesis must precede right parenthesis in a format mask.**

**Cause:** The order of the parentheses was reversed in the format mask; that is, the right, or close, parenthesis was used before the left, or open parenthesis.

**Action:** Edit the format mask and reverse the order of the parentheses.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01830: The Exponent field in a format mask must contain exactly 4 Es.**

**Cause:** The scientific notation specified for the field contained too many or too few E's.

**Action:** Enter the format mask with four E's. To have extra E's appear in the output, put them in quotation marks ("").

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01831: A closing quotation mark in format mask is missing.**

**Cause:** An opening quotation mark (") was entered before the string in the format mask, but not a closing one. The possible causes of this error include the following: Case 1: No closing quotation mark was entered after the string. Case 2: One quotation mark was entered within the quotation marks that begin and end the string.

**Action:** Take the following actions to correct this error: If Case 1: Add an ending quotation mark after the string. If Case 2: Enter another quotation mark next to the quotation mark inside the string.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01832: Illegal character {0} was encountered in the format mask.**

**Cause:** A character was entered in a format mask that is not valid for format masks.

**Action:** Delete the illegal character. For more information, see the date and time format mask information in the Building Reports manual.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01833: A format mask must contain at least one digit.**

---

**Cause:** The format mask entered contains no digits. At least one token in the mask must represent a digit.

**Action:** Enter a token in the format mask that represents a digit. The tokens that represent digits are 0, 9, \*, and S. For more information, see the date and time format mask information in the Building Reports manual.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01834: A format mask may contain at most one < character.**

**Cause:** The format mask included two left angle brackets (<<). The angle brackets need not be entered sequentially to cause the error.

**Action:** Delete the extra left angle bracket or place it inside quotation marks (") as part of a string if it should appear in the output.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01835: A format mask may contain at most one > character.**

**Cause:** The format mask included two right angle brackets (>>). The angle brackets need not be entered sequentially to cause the error.

**Action:** Delete the extra right angle bracket or place it inside quotation marks (") as part of a string if it should appear in the output.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01836: A left angle bracket must come before a right angle bracket in a format mask.**

**Cause:** The left angle bracket (<) must come before the right angle bracket (>) in a format mask.

**Action:** Ensure that all angle brackets that are to appear in the output are placed inside quotation marks ("). For the angle brackets that delineate the beginning and ending of the decimal aligned region, ensure that the left angle bracket precedes the right angle bracket in the format mask.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01837: A format mask may contain at most one decimal point.**

**Cause:** A format mask was entered with multiple decimal points.

**Action:** To have extra decimal points appear in the output, place them in quotation marks ("). Remove any extra decimal points outside of quotation marks.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-01838: A format mask may contain at most one scale point.**

**Cause:** The token V was entered more than once within the format mask.

**Action:** To have extra V's appear in the output, place them in quotation marks (""). Otherwise, delete the V's until there is only one in the format mask.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01839: A comma is not allowed before the first digit in a format mask.**

**Cause:** A comma (,) was entered before the first digit in the format mask, which is illegal.

**Action:** To have a comma appear before the digits in the output, place it in quotation marks (") as a string. Otherwise, delete the comma.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01840: A comma is not allowed after the last digit in a format mask.**

**Cause:** A comma (,) was entered after the last digit in the format mask, which is illegal.

**Action:** To have a comma appear after the digits in the output, place it in quotation marks (") as a string. Otherwise, delete the comma.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01841: A comma is not allowed after the decimal point in a format mask.**

**Cause:** A comma (,) was entered after the decimal point in the format mask.

**Action:** To have a comma appear after the decimal point in the output, place it in quotation marks (") as a string. Otherwise, delete the comma.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01842: A format mask may contain at most one exponent field.**

**Cause:** The token EEEE was entered more than once within the format mask. This token may be entered only once per format mask.

**Action:** To have the extra E's appear in the output, place them in quotation marks ("). Otherwise, delete the extra EEEE tokens until there is only one in the format mask.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01843: Format masks with exponent fields must have exactly one digit before the decimal point.**



---

**Cause:** A scientific notation format mask was entered that had no digits or more than one digit to the left of the decimal point.

**Action:** Delete digits or add a digit until there is only one to the left of the decimal point.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01844: An internal error occurred: Bad index in a flexible array.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01845: The decimal point must come between the angle brackets in a format mask.**

**Cause:** A decimal point was placed outside the left and right angle brackets (&lt; and &gt;) of the format mask.

**Action:** Edit the format mask to either remove the decimal point or place it between the brackets.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01846: A Roman numeral format mask must be simply \"RN\" or \"rn\".**

**Cause:** A Roman numeral format mask token (RN or rn) was specified, along with other format mask tokens.

**Action:** To format the values as Roman numerals, eliminate all format mask tokens except RN or rn from Format Mask. Otherwise, do not use the RN or rn token.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01847: The current process failed while trying to set up for printing.**

**Cause:** An attempt was made to print a report. The possible causes of this error include the following: Case 1: In the Runtime Parameter Form or on the command line, Printer was specified for DESTYPE, but an invalid printer name was specified for DESNAME. Case 2: The report that was executed in turn executes a second report using SRW.RUN\_REPORT. DESTYPE for both reports is set to either File or Printer, but the first report must be run to the screen.

**Action:** Take the following actions to correct this error: If Case 1: Retry the operation, specifying a valid printer name for DESNAME. If Case 2: Change the DESTYPE for the first report to Screen or Previewer and run it again.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**REP-01848: The current process failed while trying to begin printing.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**REP-01849: The current process failed while printing.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Process

**REP-01850: An error occurred in column {0} of line {1} of printer definition file {2}:  
End of file reached inside quoted string.**

**Cause:** The printer definition file contains a quoted string that was not ended with a quote before the end of the file.

**Action:** Use the location specified in the error message to locate the error and add the end quote to the quoted string in the printer definition file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01851: An error occurred in column {0} of line {1} of printer definition file {2}:  
String is longer than {3} characters.**

**Cause:** A string in the printer definition file is longer than the maximum number of allowable characters.

**Action:** Reduce the length of the string.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01852: An error occurred in column {0} of line {1} of printer definition file {2}.**

**Cause:** An incorrect keyword is included in the printer definition file.

**Action:** Verify the printer definition file syntax.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01853: An error occurred in column {0} of line {1} of printer definition file {2}.**

**Cause:** An incorrect keyword was found in the printer definition file.

**Action:** Verify the printer definition file syntax.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01854: An error occurred in column {0} of line {1} of printer definition file {2}: Invalid control character {3}.**

**Cause:** An invalid control character was found in the printer definition file.

**Action:** Replace or remove the invalid control character in the printer definition file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01855: An error occurred in column {0} of line {1} of printer definition file {2}: Unknown character {3}.**

**Cause:** An unknown character was found in the printer definition file.

**Action:** Replace or remove the unknown character in the printer definition file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01856: An error occurred in column {0} of line {1} of printer definition file {2}: {3} is not a valid ASCII character.**

**Cause:** An invalid ASCII character appears in the printer definition file.

**Action:** Replace or remove the invalid ASCII character in the printer definition file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01857: An error occurred in column {0} of line {1} of printer definition file {2} following {3}.**

**Cause:** An unmatched parenthesis was found in the printer definition file.

**Action:** Edit the printer definition file and insert the necessary parenthesis.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01858: An error occurred in column {0} of line {1} of printer definition file {2}: octal {3} is not a valid ASCII character.**

**Cause:** The octal code for an ASCII character in the printer definition file is incorrect.

**Action:** Edit the printer definition file and correct the code for the ASCII character.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**REP-01859: An error occurred in column {0} of line {1} of printer definition file {2}: hex {3} is not a valid ASCII character.**

**Cause:** The hex code for an ASCII character in the printer definition file is incorrect.

**Action:** Edit the printer definition file and correct the code for the ASCII character.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01860: An error occurred in column {0} of line {1} of printer definition file {2}.**

**Cause:** The printer definition file contains an incomplete code string.

**Action:** Edit the printer definition file and complete the code string with the appropriate word.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01861: An error occurred in column {0} line {1} of file {2}.**

**Cause:** The printer definition file contains an incomplete "box" code string.

**Action:** Edit the printer definition file and complete the "box" code string with the appropriate word.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01862: An error occurred in column {0} of line {1} of printer definition file {2}.**

**Cause:** The printer definition file does not include the required code "printer".

**Action:** Edit the printer definition file and add the required code "printer" followed by the name of the printer in a quoted string, preferably on the first line of the printer definition file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01863: An error occurred in column {0} of line {1} of printer definition file {2}.**

**Cause:** The printer definition file contains the name of the printer after the "printer" code, but the name does not appear in a quoted string.

**Action:** Edit the printer definition file and place quotation marks (") around the name of the printer after the "printer" code.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01864: An error occurred in column {0} line {1} of file {2}.**

---

**Cause:** The printer definition file does not contain any of the code words expected in a printer definition file.

**Action:** Edit the printer definition file and add the code words that are missing.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01865: An error occurred in column {0} of line {1} of printer definition file {2}.**

**Cause:** The printer definition file contains the "width" code, but no number specifying the width of the report appears after it.

**Action:** Edit the printer definition file and insert a number specifying the width of the report after the "width" code.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01866: An error occurred in column {0} of line {1} of printer definition file {2}.**

**Cause:** The printer definition file contains the "height" code, but no number specifying the height of the report appears after it.

**Action:** Edit the printer definition file and insert a number specifying the height of the report after the "height" code.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01867: An error occurred in column {0} of line {1} of printer definition file {2}.**

**Cause:** The printer definition file contains the word "before" but not the accompanying word "report".

**Action:** Edit the printer definition file to include a complete "before report" entry.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01868: An error occurred in column {0} of line {1} of printer definition file {2}.**

**Cause:** The printer definition file contains the word "between" but not the accompanying word "pages".

**Action:** Edit the printer definition file to include a complete "between pages" entry.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01869: An error occurred in column {0} of line {1} of printer definition file {2}.**

**Cause:** The printer definition file (for a multipage report) contains the code word "after" but not the accompanying word "report".

**Action:** Edit the printer definition file to include a complete "after report" entry.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01870: An error occurred in column {0} of line {1} of printer definition file {2}.**

**Cause:** The printer definition file contains the "code" code with a user-defined string, but the string is not enclosed within quotation marks.

**Action:** Edit the printer definition file and enclose the "code" user-defined string with quotation marks.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01871: An error occurred in column {0} of line {1} of printer definition file {2}.**

**Cause:** The printer definition file contains a generalized string using "dec", but "dec" is not followed with a left parenthesis.

**Action:** Edit the printer definition file and add parentheses around the value following "dec".

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01872: An error occurred in column {0} of line {1} of printer definition file {2}.**

**Cause:** The printer definition file contains a generalized string (for example, dec or octal), but no value follows the right parenthesis.

**Action:** Edit the printer definition file and add a value between the parentheses in the generalized string.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01873: An error occurred in column {0} of line {1} of printer definition file {2}.**

**Cause:** The printer definition file contains a generalized string using "octal", but "octal" is not followed with a left parenthesis.

**Action:** Edit the printer definition file and add parentheses around the value following "octal".

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01874: An error occurred in column {0} of line {1} of printer definition file {2}.**

**Cause:** The printer definition file contains a generalized string (for example, dec or octal), but no value follows the left parenthesis.

**Action:** Edit the printer definition file and add a value between the parentheses in the generalized string.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-01875: An error occurred in column {0} of line {1} of printer definition file {2}.**

**Cause:** The printer definition file contains a generalized string using "hex", but "hex" is not followed with a left parenthesis.

**Action:** Edit the printer definition file and add parentheses around the value following "hex".

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01876: An error occurred in column {0} of line {1} of printer definition file {2}.**

**Cause:** The printer definition file contains a generalized string (for example, dec or octal), but no value follows the left parenthesis.

**Action:** Edit the printer definition file and add a value between the parentheses in the generalized string.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01877: An error occurred in column {0} of line {1} of printer definition file {2}.**

**Cause:** The printer definition file contains a generalized string using "^", but no control character follows the "^".

**Action:** Edit the printer definition file and add a control character after "^".

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01878: An error occurred in column {0} of line {1} of printer definition file {2}.**

**Cause:** The printer definition file contains a keyword and generalized string (for example, after report or before report), but no left parenthesis follows the word "control".

**Action:** Edit the printer definition file and add a left parenthesis following the word "control".

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01879: An error occurred in column {0} of line {1} of printer definition file {2}.**

**Cause:** The printer definition file contains a keyword and generalized string (for example, after report or before report), but no control character follows the left parenthesis.

**Action:** Edit the printer definition file and add a control character between the parentheses after the word "control".

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-01880: An error occurred in column {0} of line {1} of printer definition file {2}.**

**Cause:** The printer definition file contains the "box" code string, but the drawing string specified between quotation marks is more than one character long.

**Action:** Edit the printer definition file, making sure that one and only one character is specified as a drawing string.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01881: An error occurred in column {0} of line {1} of printer definition file {2}.**

**Cause:** The printer definition file contains the "box" code string, but no drawing string is specified.

**Action:** Edit the printer definition file and specify a drawing string.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01882: An error occurred in column {0} line {1} of file {2}.**

**Cause:** The printer definition file contains the "box" code string, but the following required word (one of 'horizontal', 'vertical', 'top', 'center', or 'bottom') is not specified.

**Action:** Edit the printer definition file and add the appropriate required word.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01883: Unexpected end of printer definition file was reached.**

**Cause:** Oracle Reports Builder was able to open the printer definition file, but an error occurred while reading it.

**Action:** Verify that the correct printer definition file is specified. Also, check the contents of the printer definition file. Edit the file if necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01884: A hang occurred while sending output.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01885: Output could not be sent to the printer.**



---

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-01886: Expected I after M in the format mask cannot be found.**

**Cause:** The M entered in a format mask was not followed by I. The only token that begins with M is the MI token.

**Action:** To use the MI token, enter an I after the M. To have the character M appear in the output, place it inside double quotation marks ("). Otherwise, delete the M from Format Mask.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01887: Expected R after P in the format mask cannot be found.**

**Cause:** The P entered in a format mask was not followed by R. The only token that begins with P is the PR token.

**Action:** To use the PR token, enter an R after the P. To have the character P appear in the output, place it inside double quotation marks ("). Otherwise, delete the P from Format Mask.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01888: Only one sign token is allowed.**

**Cause:** More than one sign token was entered in a format mask.

**Action:** Delete all sign tokens but one from the format mask.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01889: A trailing sign token must be at the end.**

**Cause:** A sign token was not placed at the end of the format mask.

**Action:** Place the sign token (for example, MI, PR, DB, and CR) at the end of the format mask.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01890: The S token must be at the beginning or end.**

**Cause:** The S token was not placed at the beginning or the end of the format mask.

**Action:** Place the S token at the beginning or the end of the format mask or delete it.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01891: Parentheses tokens must surround other tokens.**

**Cause:** The parentheses tokens do not surround all other tokens in the format mask.

**Action:** Place the parentheses around all of the other tokens in the format mask.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01892: The destype specified is not supported for pdf or html.**

**Cause:** An invalid destination type (destype) was specified for pdf or html output.

**Action:** Specify a destination type (destype) of file or cache for pdf or html output.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01893: The destype specified is not supported on this platform.**

**Cause:** An invalid destination type (destype) was specified for the operating system (for example, Sysout, while running on Microsoft Windows).

**Action:** Specify a valid destination type.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01894: The report definition was modified during the current run. No new pages will be generated.**

**Cause:** While previewing a report (using Oracle Reports Builder), the report's definition was modified, and then an attempt was made to view additional pages from the Previewer. Oracle Reports Builder cannot guarantee that all of the information used at runtime is still present, so formatting is halted.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01895: A date formatting error occurred while processing field {0}.**

**Cause:** Oracle Reports Builder could not format the specified date field.

**Action:** Check the format mask of the specified date field.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-01896: An error occurred in column {0} of line {1} of printer definition file {2}: Expected backspace or overstrike to follow highlight.**

**Cause:** The specified printer definition file contains the 'highlight' setting, but the setting was not completed properly.

**Action:** Add either 'overstrike' or 'backspace &lt;sequence&gt;' after 'highlight'.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01897: An error occurred in column {0} of line {1} of printer definition file {2}: Non-numeric user-defined printer codes are not supported.**

**Cause:** The specified printer definition file contains a user-defined printer code that is not a number.

**Action:** Change the user-defined printer code to a number.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01898: An error occurred in column {0} of line {1} of printer definition file {2}: Highlight setting can only be defined once.**

**Cause:** The specified printer definition file contains more than one highlight setting.

**Action:** Remove all but one of the highlight settings from the printer definition file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01899: Graphics Display or Icon cannot be converted to .gif format - image skipped.**

**Cause:** Oracle Reports Builder was unable to convert an embedded Graphics Display or icon to a GIF format for displaying within an HTML document. This only occurs when Oracle Reports Builder cannot access a window system in order to draw the image.

**Action:** Run the report using the bitmap executable under a windowing system to allow Oracle Reports Builder access to a display.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01920: Character mode runtime is incompatible with DESFORMAT of PDF, HTML, HTMLCSS, SPREADSHEET, or RTE.**

**Cause:** An attempt was made to run a report with a destination format of PDF, HTML, HTMLCSS, SPREADSHEET, or RTF. These formats are only available when running in a bitmap environment and producing a bitmap output.

**Action:** Rerun the report with a bitmap executable or set MODE=BITMAP if already running with a bitmap executable.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-01921: Input printer tray {0} is not available on the selected printer.**

**Cause:** An attempt was made to alter the input printer tray but the name of the tray specified is not available on the currently selected printer.

**Action:** Change the selected printer to one that supports the specified tray or alter the tray name to one supported by the specified printer. Use Page Setup to view the list of printer trays supported by the printer.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01922: A PDF compression error was encountered.**

**Cause:** The compression engine failed compressing this page.

**Action:** Turn off compression for this report by specifying PDFCOMP=NO on command line.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01923: A PDF Font Embed error was encountered.**

**Cause:** The font specified for embedding into the PDF document cannot be found or is invalid.

**Action:** The [PDF:Embed] section must be present in the uifont.ali file. Check to ensure that the entry of font in the uifont.ali is syntactically correct. Verify that the location of font files is added to REPORTS\_PATH in the registry/environment variable.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01924: Font file {0} cannot be found.**

**Cause:** The font file specified in UIFONT.ALI is not found.

**Action:** Verify that the font file exists in REPORTS\_PATH.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01925: Font file {0} is invalid.**

**Cause:** The font file appears to be corrupt or invalid.

**Action:** Ensure the specified file is a valid font file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-01926: Identical name {0} was specified for dissimilar form field types {1} and {2}.**

**Cause:** The name specified for a form field conflicts with an existing form field of different type.

**Action:** Select a new name for one of the form fields. Change the type of the form field to match that of the existing form field.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01927: Cannot print document or generate output in printer format because the printer is offline or paused.**

**Cause:** When destination type is printer or format is printer name, running request fails if the printer is offline or paused.

**Action:** Bring the printer online and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01940: An error occurred in column {0} line {1} of file {2}: Expected visualorder, logicalorder, contextualshaping, contextuallayout, multibyte, or pcharset.**

**Cause:** The printer definition file contains the 'nls' code string, but the required word (one of 'visualorder', 'logicalorder', 'contextualshaping', 'contextuallayout', 'multibyte', or 'pcharset') is not specified.

**Action:** Edit the printer definition file and add the required word.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01941: An error occurred in column {0} line {1} of file {2}: Expected yes or no.**

**Cause:** The printer definition file contains 'visualorder', 'logicalorder', 'contextualshaping', 'contextuallayout', 'multibyte', or 'pcharset' code string, but the required word (either 'yes' or 'no') is not specified.

**Action:** Edit the printer definition file and add the appropriate 'yes' or 'no'.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01942: An error occurred in column {0} line {1} of file {2}: Expected name of character set to follow pcharset.**

**Cause:** The printer definition file contains the 'pcharset' code string, but the required string (name of character set) is not specified.

**Action:** Edit the printer definition file and add the name of character set.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-01943: An error occurred in column {0} line {1} of file {2}: Defined printer character set is unsupported.**

**Cause:** The printer definition file contains an unsupported printer character set.

**Action:** Edit the printer definition file and specify the name of a supported character set.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01944: Invalid reference value {0} was specified for Report property {1}**

**Cause:** The value specified for the indicated property cannot be resolved or is at a wrong frequency.

**Action:** Ensure that the reference exists and resolves to a valid value. Only Report-level columns can be referenced with this property.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01950: The Source specified is invalid.**

**Cause:** The Source specified for Reports Converter is not a valid source.

**Action:** Verify that the correct object or file is specified and that the STYPE is correct for that file or object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01951: The Destination specified is invalid.**

**Cause:** The Destination specified for Reports Converter is not a valid destination.

**Action:** Verify that the correct object or file is specified and that the DTYPE is correct for that file or object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-01952: The number of Destination items must be zero or match the number of Source items.**

**Cause:** In the Convert dialog box, or while using Reports Converter, the number of Destination items specified was greater than zero and did not match the number of Source items specified.

**Action:** To have Oracle Reports Builder derive the Destination names from the specified Source names, leave Destination blank. Otherwise, verify that the number of Destination names specified matches the number of Source names specified. If wildcards are used in the Source specification, verify that the number of Destination names matches the number of Source items in the expanded wildcard list.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-02000: An error occurred in the user exit.**

**Cause:** An error occurred in the user exit.

**Action:** Debug the code or contact the database administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-02001: An error occurred in IAF GET: unknown column {0}.**

**Cause:** An unknown column name was specified in the user exit's IAF GET statement.

**Action:** Specify a valid column name in the IAF GET statement.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-02002: An error occurred in IAF PUT: unknown column {0}.**

**Cause:** An unknown column name was specified in the user exit's IAF PUT statement.

**Action:** Specify a valid column name in the IAF PUT statement.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-02003: The user exit cannot be found.**

**Cause:** Oracle Reports Builder could not find the user exit that it was supposed to run at this point. The most likely cause is that the name and/or location of the user exit code was not specified correctly.

**Action:** Verify the name and location of the code when installing it. Otherwise, contact the database administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-02004: PL/SQL source code of object {0} could not be retrieved.**

**Cause:** From the File menu, Administration Report was selected to document one or more reports, but the RWEPLS user exit failed to retrieve the PL/SQL source code of an object. This is most likely an abnormal condition.

**Action:** Check the PL/SQL source code in the named object. For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

---

**REP-02005: An error occurred in IAF PUT: the value of column {0} was truncated.**

**Cause:** The IAF PUT statement assigned a value to the named column, but the column was not wide enough to hold the entire value, causing it to truncate.

**Action:** Widen the column so that it is can hold the entire value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-02100: An error occurred in Calculation Manager.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-02101: Calculation Manager: the source column cannot use segmented memory.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-02102: Calculation Manager: the computed column cannot use segmented memory.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-02103: The PL/SQL formula returned invalid value or no value for column {0}.**

**Cause:** An SRW.DO\_SQL statement was entered that caused this Oracle message.

**Action:** Edit the SRW.DO\_SQL statement. For more information about the Oracle message, see the Oracle Messages and Codes Manual.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-02300: Error {0} occurred.**

**Cause:** An SRW.DO\_SQL statement was entered that caused this Oracle message.

**Action:** Edit the SRW.DO\_SQL statement. For more information about the Oracle message, see the Oracle Messages and Codes Manual.

**Level:** 1

**Type:** ERROR



---

**Impact:** Other

**REP-02301: An error occurred allocating a SQLDA descriptor: {0}.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-02302: An error occurred parsing the SQL statement: {0}.**

**Cause:** Oracle Reports Builder encountered an error while parsing the SRW.DO\_SQL statement.

**Action:** Refer to the Oracle message to see why the SQL statement could not be parsed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-02303: An error occurred describing bind variables: {0}.**

**Cause:** Oracle Reports Builder encountered an error while describing bind variables in an SRW.DO\_SQL statement.

**Action:** Refer to the Oracle message to see why the bind variables could not be described.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-02304: An error occurred opening a SQL cursor: {0}.**

**Cause:** Oracle Reports Builder encountered an error while opening a cursor in an SRW.DO\_SQL statement.

**Action:** Refer to the Oracle message to see why the cursor could not be opened.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-02305: An error occurred describing the SELECT list: {0}.**

**Cause:** Oracle Reports Builder encountered an error while describing the SELECT list in an SRW.DO\_SQL statement.

**Action:** Refer to the Oracle message to see why the bind variables could not be described.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-02306: An error occurred fetching bind variables: {0}.**

---

**Cause:** Oracle Reports Builder encountered an error while fetching bind variables in an SRW.DO\_SQL statement.

**Action:** Refer to the Oracle message to see why the bind variables could not be fetched.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-02307: An error occurred fetching a data record: {0}.**

**Cause:** Oracle Reports Builder encountered an error while fetching a data record in an SRW.DO\_SQL statement.

**Action:** Refer to the Oracle message to see why the data record could not be fetched.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-02308: An error occurred processing the SELECT list: {0}.**

**Cause:** Oracle Reports Builder encountered an error while processing the SELECT list in an SRW.DO\_SQL statement.

**Action:** Refer to the Oracle message to see why the SELECT list is invalid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-02309: An error occurred formatting a date field: {0}.**

**Cause:** Oracle Reports Builder encountered an error while formatting a date field in an SRW.DO\_SQL statement.

**Action:** Refer to the Oracle message to see why the date field could not format.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-02310: An error occurred putting a value into a column: {0}.**

**Cause:** Oracle Reports Builder encountered an error while trying to insert a value into a column in an SRW.DO\_SQL statement.

**Action:** Refer to the Oracle message to see why the value could not be assigned.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-02311: An error occurred during Commit: {0}.**

**Cause:** Oracle Reports Builder encountered an error while trying to do a commit in an SRW.DO\_SQL statement.

**Action:** Refer to the Oracle message to see why the commit failed.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-02312: An error occurred allocating a data record: {0}.**

**Cause:** Oracle Reports Builder encountered an error while allocating a data record in an SRW.DO\_SQL statement.

**Action:** Refer to the Oracle message to see why the record could not be allocated.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-02313: An error occurred parsing the SELECT list: {0}.**

**Cause:** Oracle Reports Builder encountered an error while parsing the SELECT list in an SRW.DO\_SQL statement.

**Action:** Refer to the Oracle message to see why the SELECT list could not be parsed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-02314: An error occurred closing a SQL cursor: {0}.**

**Cause:** Oracle Reports Builder encountered an error while trying to close a SQL cursor in an SRW.DO\_SQL statement.

**Action:** Refer to the Oracle message to see why the close cursor operation failed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-02315: An error occurred freeing a data record: {0}.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**REP-02316: Column {0} cannot be found.**

**Cause:** A column referred to in an SRW.DO\_SQL statement cannot be found.

**Action:** Debug the PL/SQL and verify that the SRW.DO\_SQL statement contains the correct column name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-02317: The value of column {0} was truncated.**

---

**Cause:** A column value obtained via an SRW.DO\_SQL statement was truncated.

**Action:** Go to the column's Property Inspector and increase its Width. Or, restrict the size of the value that the SRW.DO\_SQL statement is putting into the column.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-02400: DEBUG: internal error 0 occurred.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-02500: Error {0} occurred. See the Release Notes for further information about this error**

**Cause:** The error is documented in the Release Notes.

**Action:** See the Release Notes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-02550: The in-process server was not started: {0}.**

**Cause:** An abnormal condition was encountered.

**Action:** Refer to the in-process server message to see why it failed to start. Then restart the Oracle Reports Builder.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03000: An internal error occurred starting Oracle Toolkit.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03001: An internal error occurred initializing the File Dialog.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

---

**REP-03002: An error occurred initializing the printer. Verify that a printer is installed.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03020: An internal error occurred starting Oracle Resource Manager.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03021: An internal error occurred processing a menu resource.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03022: An internal error occurred processing a window resource.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03023: The resource file cannot be found.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03040: An internal error occurred starting Oracle Observer Model.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

---

**REP-03060: An internal error occurred initializing the color table. Checking VGS resources is recommended.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03080: An internal error occurred initializing Oracle Image.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03081: An error occurred running the image viewer.**

**Cause:** A Previewer button was selected with a defined action of displaying an image, but the image viewer is unavailable. Possible causes of this error include: Case 1: The image specified as the source is in an incorrect format. Case 2: There is no available memory. Case 3: An abnormal condition was encountered.

**Action:** Take the following actions to correct this error: If Case 1: Ensure that the image file specified as the source of the button action is in a displayable format. If Case 2: Make more memory available, if possible, or ask the system administrator for assistance. If Case 3: For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03082: An error occurred running the sound dialog.**

**Cause:** A Previewer button was selected with a defined action of playing a sound, but the sound dialog is unavailable. Possible causes of this error include: Case 1: The sound file specified as the source is in an incorrect format. Case 2: There is no available memory. Case 3: An abnormal condition was encountered.

**Action:** Take the following actions to correct this error: If Case 1: Ensure that the sound file specified as the source of the button action is in a playable format. If Case 2: Make more memory available, if possible, or ask the system administrator for assistance. If Case 3: For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03083: An error occurred running the video player.**

**Cause:** A Previewer button was selected with a defined action of playing a video, but the video player is unavailable. Possible causes of this error include: Case 1: The video file specified as the source is in an incorrect format. Case 2: There is no available memory. Case 3: An abnormal condition was encountered.

---

**Action:** Take the following actions to correct this error: If Case 1: Ensure that the video file specified as the source of the button action is in a playable format. If Case 2: Make more memory available, if possible, or ask the system administrator for assistance. If Case 3: For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03085: Multimedia source file {0} cannot be found.**

**Cause:** The button was clicked in the Previewer, but the source for the button's intended action (whether sound, image, or video) cannot be found or has been corrupted.

**Action:** Open the Property Inspector for the button in question and verify the existence, format, and path information for the specified source file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03086: The multimedia source file is not available.**

**Cause:** The button was clicked in the Previewer, but the source for the button's intended action (whether sound, image, or video) has been corrupted.

**Action:** Open the Property Inspector for the button in question and verify the existence, format, and path information for the specified source file. If it is correct, check the file itself.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03087: ImageViewer is not supported in this configuration.**

**Cause:** The platform or configuration does not support displaying images via the ImageViewer.

**Action:** No action is necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03088: Sound is not supported in this configuration.**

**Cause:** The platform or configuration does not support playback of sound files.

**Action:** No action is necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03089: Video is not supported in this configuration.**

**Cause:** The platform or configuration does not support playback of video files.

**Action:** No action is necessary.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03100: A matrix must include at least 1 Down and 1 Across repeating frame.**

**Cause:** An attempt was made to create a matrix (selecting Arrange, then Create Matrix) without the proper objects selected in the Paper Layout editor. A matrix layout requires that at least one group have a repeat direction of Down and one have a repeat direction of Across.

**Action:** Select two repeating frames--one Down, one Across--that overlap, then select Create Matrix from the Arrange Menu.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03101: All selected Down and Across repeating frames must be nested.**

**Cause:** An attempt was made to create a matrix (selecting Arrange, then Create Matrix) and the Down and Across repeating frames were not properly overlapping and nested.

**Action:** Verify that the selected Down and Across repeating frames are properly overlapping and nested before creating the matrix.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03102: Anchors, matrices, and margins cannot be grouped.**

**Cause:** Group was selected from the Arrange menu and at least one of the objects selected was an anchor, matrix, or margin.

**Action:** Deselect all anchors, matrices, and margins before grouping objects.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03103: Only text and graphical boilerplate objects can be rotated.**

**Cause:** An attempt was made to rotate a frame, a field, a margin, an anchor, a matrix object, a file link boilerplate object, or a graph. None of these can be rotated.

**Action:** Rotate any boilerplate objects except images and file link boilerplate objects. Depending on the operating system, the text of a rotated boilerplate text object may or may not be visible.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03104: Anchors and matrices cannot be scaled separately from their associated objects.**

**Cause:** An attempt was made to scale one of the layout objects listed above without also scaling its associated object, which is not allowed.



---

**Action:** Select at least one associated object (anchoring object for anchors, repeating frames for matrices), then retry the scaling operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03105: A graph Column must be selected for the graph Query.**

**Cause:** A name was entered for the graph Query, but no graph Columns were selected. If a graph Query is specified, graph Columns must also be specified.

**Action:** Specify graph Columns or remove the value from the graph Query.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03106: a graph Column was selected without a graph Query name. The selected graph Column will be ignored.**

**Cause:** A Source or graph Column was selected but a name for a graph Query was not entered.

**Action:** Enter the name of the graph query to which to pass data.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03107: Object {0} cannot be moved in front of its child {1}.**

**Cause:** An attempt was made to move a layout object in front of one or more of its own child objects.

**Action:** To move the layout object, toggle Confine mode off, then move it. Otherwise, no action is necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03108: Object {0} cannot be moved behind its container {1}.**

**Cause:** An attempt was made to move a layout object behind one or more of its own parent objects.

**Action:** To move the layout object, toggle Confine mode off, then move it. Otherwise, no action is necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03109: The alignment operation failed because of container constraints.**

**Cause:** An attempt was made to align multiple layout objects but the result of such an operation would have violated container constraints (that is, moved a field outside of its enclosing frame).

---

**Action:** Select Edit, then Undo to ensure the layout is the same as before the attempted operation. Then, either resize or reposition the container in question to perform the operation, or do nothing.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03110: Same size operation failed because of container constraints.**

**Cause:** An attempt was made to change one or more layout objects to the same size, but the result of such an operation would have violated container constraints (that is, enlarged a field beyond its enclosing frame).

**Action:** Select Edit, then Undo to ensure the layout is the same as before the attempted operation. Then, either resize or reposition the container in question to perform the operation, or do nothing.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03111: Changing the border width of {0} violates the constraints of confined mode.**

**Cause:** An attempt was made to change the border width of an object such that the result would have violated container constraints (that is, widening the border of a boilerplate object so that it extended beyond its enclosing frame).

**Action:** No action is necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03112: Objects cannot be created in the template layout body layer.**

**Cause:** An attempt was made to create an object in the layout body layer of a template. Objects may only be created in the margin, header pages, or trailer pages of a template.

**Action:** No action is necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03130: Parameter Form fields and images cannot be rotated.**

**Cause:** An attempt was made to rotate one of the Parameter Form objects, which is not allowed.

**Action:** Rotate any boilerplate objects, except images, in the Parameter Form editor. Depending on the operating system, the text of boilerplate text that is rotated may or may not be visible.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-03131: Parameter Form boilerplate text cannot fit on the page.**

**Cause:** Text was entered in the Title, Hint, Status, or Label field in the Parameter Form Builder that is too long to fit on the page.

**Action:** Reduce the length of the appropriate text field.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03140: A Program Unit Editor internal error occurred: Could not get document handle.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03150: One editor must remain open for each report.**

**Cause:** An attempt was made to close all three of the editors (Data Model, Layout, and Parameter Form) for a report. At least one editor must remain open.

**Action:** Leave one editor open for each report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03151: The width for column {0} is invalid and cannot be highlighted, since group {1} is not selected.**

**Cause:** An invalid value was entered for the Width of a column in the Report Wizard. Since the group that owns the column is not selected, the column is not listed.

**Action:** Select the group that owns the column. Scroll down to the column and enter a valid value for Width.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03152: The link, anchor, or polygon creation must be completed in the editor before this action.**

**Cause:** An attempt was made to perform some action (for example, close the report) before finishing the creation of a data link in the Data Model editor, an anchor in the Paper Layout editor, or a polygon in the Paper Layout editor or Parameter Form editor.

**Action:** Complete the unfinished object before continuing.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-03153: Insufficient resources are available to create the window.**

**Cause:** There were insufficient resources available to create the requested window.

**Action:** Make more resources available by closing windows or other applications.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03154: Insufficient resources are available to create the document.**

**Cause:** There were insufficient resources available to create the requested document (report, external query, PL/SQL library).

**Action:** Make more resources available by closing windows or other applications.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03200: Concurrent previewer actions are not allowed.**

**Cause:** An attempt was made to activate more than one button at one time, in either the same or multiple Previewers. For example, play a sound and display a video at the same time.

**Action:** Activate only one button at a time.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03290: Query Builder does not support lexical parameters.**

**Cause:** An attempt was made to pass lexical parameters to Query Builder, which is not supported. Query Builder only supports bind parameters.

**Action:** Remove all lexical parameters from the query and reenter Query Builder.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03300: A fatal error occurred: {0}.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03301: An error occurred: {0}.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Other

**REP-03302: A fatal error occurred during Quit. Exiting Oracle Reports Builder.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03335: An unhandled internal CA error occurred.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03350: An unhandled internal UI error occurred.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03351: An undefined failure in the UI occurred.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03352: An unexpected error in the UI occurred.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03353: The attribute cannot be created.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03354: The attribute cannot be set.**

---

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03355: The attribute cannot be set or retrieved.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03356: The unknown attribute cannot be set or retrieved.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03357: The attributes values are conflicting and cannot be set.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03358: The attribute cannot be set to an out of range value.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03359: This function call is out of context.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03360: The view class does not support being a scrollee.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03361: This function call provokes an illegal recursion.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03362: The internal API memory allocator failed.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Memory

**REP-03363: The client supplied memory allocation functions failed.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Memory

**REP-03364: An attempt to use an unsupported function failed.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03365: Attributes cannot be set out of context.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03366: An attempt to perform an illegal operation on a root view failed.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Other

**REP-03367: One of the parameters to the functions is out of range.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03368: The connection to the windowing system failed.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03369: The connection to the windowing system is broken.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03370: The windowing system failed.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03371: uiER\_CL\_FORMAT\_UNAVAILABLE**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03372: uiER\_CL\_FORMAT\_UNREGISTERED**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03373: The operation timed out.**



---

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03374: uiER\_NOT\_FOUND**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03375: uiER\_ILLEGAL\_TOPITEM**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03376: uiER\_SE\_BAD\_FORMAT**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03377: The view class does not support the scroller interface.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03378: An attempt to remove a readshare color from a palette failed.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03379: An attempt to create a window failed.**

**Cause:** Oracle Reports Builder was unable to create a window. There may be too many reports or windows open, and lack of memory resources.

---

**Action:** Close some reports and windows.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03380: An attempt to create a view failed.**

**Cause:** Oracle Reports Builder was unable to create a view. There may be too many reports or windows open, and lack of memory resources.

**Action:** Close some reports and windows.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03381: An attempt to create a color palette failed.**

**Cause:** Oracle Reports Builder was unable to create a color palette. There may be too many reports or windows open, and lack of memory resources.

**Action:** Close some reports and windows.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03400: An error occurred initializing DE. Checking DE resources is recommended.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03420: An internal error occurred in Oracle Reports Builder.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03430: An unhandled internal HH error occurred.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03431: The attribute value is invalid.**

**Cause:** An abnormal condition was encountered.

---

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03432: The context is invalid.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03433: The specified word cannot be found.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03434: A link to external document was found.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03435: The help session is null.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03436: The document is not a help document.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03437: The document revision is newer than help.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03438: The specified attribute is not settable.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03439: The specified attribute is not gettable.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03440: The link is invalid.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03441: Logical attributes are missing or bad.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03442: The NLS language string is missing or bad.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03443: No search string is specified.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Other

**REP-03444: The string begins with a percent sign.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03445: An unknown toolkit error occurred.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03446: An unknown object store error occurred.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03447: An out of memory condition occurred.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Memory

**REP-03448: An unknown Resource Manager error occurred.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03480: An unhandled internal REM error occurred.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03485: An unhandled internal VGS error occurred.**

---

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03500: An unhandled internal UT error occurred.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03510: An unhandled internal ZOM error occurred.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03600: Both document nodes and non-document nodes selected. Select only nodes from one of these types of nodes.**

**Cause:** Navigator>Delete was selected, but both object nodes and document nodes are selected. Documents cannot be closed and deleted in the same action.

**Action:** To delete objects, deselect all document nodes. To close documents, deselect all object nodes. Then select Navigator>Delete again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03601: This report style can only have one Section.**

**Cause:** Tabular, Form Letter, and Mailing Label report styles have only one Section each.

**Action:** Specify all overrides in the existing Section.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-03602: The minimum number of levels cannot be deleted.**

**Cause:** Tabular, Form Letter, and Mailing Label report styles have one Section each. Group Above and Group Left report styles have two sections each. Matrix and Matrix Group have one section under each normal, across, and down cell.

**Action:** Verify that the particular report style has the minimum number of levels.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-03700: Selection Observer initialization failed.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-03701: Selection Observer failed while shutting down.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-04001: An error occurred in the OLE subsystem.**

**Cause:** An unspecified OLE2 error occurred during initialization. Refer to the accompanying OLE error message for more information. Other possible causes of this error include the following: Case 1: The OLE2 server is not functioning correctly. Case 2: An error occurred during installation of Oracle Reports Builder and the OLE2 functionality did not install correctly. Case 3: An abnormal condition was encountered.

**Action:** Take the following actions to correct this error: If Case 1: Refer to the OLE2 server documentation for more information. If Case 2: Reinstall Oracle Reports Builder. If Case 3: For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-04002: An error occurred while initializing OLE subsystem.**

**Cause:** An error occurred during initialization of OLE2 libraries. Refer to the accompanying OLE error message for more information. Other possible causes of this error include the following: Case 1: The OLE2 server is not functioning correctly. Case 2: An error occurred during installation of Oracle Reports Builder and the OLE2 functionality did not install correctly. Case 3: An abnormal condition was encountered.

**Action:** Take the following actions to correct this error: If Case 1: Refer to the OLE2 server documentation for more information. If Case 2: Reinstall Oracle Reports Builder. If Case 3: For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-04003: An error occurred while creating OLE object.**

**Cause:** An attempt was made to create an OLE2 object when an OLE error occurred.

---

**Action:** Refer to the accompanying OLE2 error message for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04004: An error occurred while restoring OLE object.**

**Cause:** An attempt was made to restore an OLE2 object when an OLE error occurred.

**Action:** Refer to the accompanying OLE2 error message for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04005: An error occurred while saving OLE object.**

**Cause:** An attempt was made to save an OLE2 object when an OLE error occurred.

**Action:** Refer to the accompanying OLE2 error message for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04006: An error occurred while performing a cut/copy operation. An OLE object is not placed in the clipboard.**

**Cause:** An attempt was made to cut or copy an OLE2 object when an OLE error occurred.

**Action:** Refer to the accompanying OLE2 error message for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04007: An error occurred while pasting OLE object from clipboard.**

**Cause:** An attempt was made to paste an OLE2 object from the clipboard when an OLE error occurred.

**Action:** Refer to the accompanying OLE2 error message for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04008: An error occurred while trying to perform operation defined by an OLE object.**

**Cause:** An attempt was made to perform an action normally supported by the OLE2 server when an OLE error occurred.

**Action:** Refer to the accompanying OLE error message for more information.

**Level:** 1

**Type:** ERROR



---

**Impact:** Other

**REP-04009: An error occurred while trying to activate an OLE object.**

**Cause:** An attempt was made to activate an OLE2 object (for example, double-click on it in the Previewer) when an OLE error occurred.

**Action:** Refer to the accompanying OLE2 error message for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04020: Conversion of OLE object to a different type failed.**

**Cause:** An attempt was made to convert an OLE2 object contained in a piece of boilerplate to an OLE2 object of a different type when an OLE error occurred. This indicates a problem with the OLE2 server.

**Action:** Check that the object is correctly installed and reinstall, if necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04021: Microsoft Object Linking and Embedding is not supported on this platform**

**Cause:** An attempt was made to run a report that was created on a platform supporting OLE2, and created with OLE2 objects, on a platform that does not support OLE2.

**Action:** No action is necessary. Remove the object if desired.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04022: The incorrect version of OLE libraries are installed. OLE functionality will be disabled.**

**Cause:** The OLE2 libraries installed are incompatible with those supported by the installed version of Oracle Reports Builder. As Oracle Reports Builder cannot guarantee that the OLE2 support will function, it disabled OLE2 functionality.

**Action:** Install the correct libraries.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04023: There is insufficient memory available to complete the operation.**

**Cause:** There is not sufficient memory remaining on the system to perform the desired action.

**Action:** Exit any unnecessary applications that are running. If that does not work, see the Microsoft documentation for suggested procedures to enhance memory usage.

**Level:** 1

**Type:** ERROR

---

**Impact:** Memory

**REP-04024: DOS SHARE services are required for successful operation. SHARE is not running.**

**Cause:** The DOS SHARE utility is required, but SHARE is not running.

**Action:** Verify that SHARE is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04025: A read failure occurred.**

**Cause:** Data cannot be read from the specified device.

**Action:** Check the device to determine if it is malfunctioning, and, if so, consult the device documentation to determine the proper error recovery procedures.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04026: A write failure occurred.**

**Cause:** Data cannot be written to the specified device.

**Action:** Check the device to determine if it is read-only. If not, consult the device documentation to determine the proper error recovery procedures.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04027: Too many files opened. There are insufficient resources to open another file.**

**Cause:** An attempt was made to open more files than are supported by Windows.

**Action:** Close some applications. Also, check the config.sys file and ensure that FILES is not set below 20. Note: Remember that OLE2 boilerplate objects reserve either two or three file handles per object and so there may be more files open than expected.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04028: No space is left on the device.**

**Cause:** The device is full.

**Action:** Delete unnecessary data or write to a different device.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04029: Presentation of the OLE object failed. Cannot render OLE object.**

---

**Cause:** An attempt was made to display an OLE2 object in a report but the display aspects defined by the OLE2 server were unavailable.

**Action:** Verify that the OLE2 object has not been corrupted and that the server is correctly installed. Reinstall if necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04030: Restoration of original display aspects of the OLE object failed. Object content will be used.**

**Cause:** An attempt was made to display an OLE2 object in a report but the display aspects defined by the OLE2 server were corrupted or stored in the database and could not be restored. Oracle Reports Builder will display the object using the default aspect.

**Action:** Verify that the OLE2 server is correctly installed. Reinstall if necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04031: The server application cannot be found.**

**Cause:** An attempt was made to access an OLE2 server via an OLE2 object, but the server is currently inaccessible. The server may have been deleted, renamed, or manually reinstalled in a different location.

**Action:** Check the installation of the server and reinstall if necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04032: Connection to the linked OLE object source failed.**

**Cause:** Oracle Reports Builder is trying to connect to the specified source of the OLE2 object boilerplate but cannot.

**Action:** Verify that the OLE2 object source has not been moved or deleted, and that its file name has not been changed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04033: Connection to the linked object source failed, because it is across a network that is not connected to this machine.**

**Cause:** An attempt was made to link to an OLE2 object that is stored on a device to which there is no established network connection.

**Action:** Establish a connection to the proper device.

**Level:** 1

**Type:** ERROR

**Impact:** Network

---

**REP-04034: A file cannot be not found or an invalid file name is used by an OLE object.**

**Cause:** An OLE2 object is attempting to access a file that it cannot find.

**Action:** Verify that the file has not been corrupted, moved, or renamed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04035: A share violation has occurred while performing operation on OLE object.**

**Cause:** Possible causes: an attempt was made to link to the same file via multiple OLE2 objects, or to access the same temporary file via different applications.

**Action:** Verify multiple OLE2 objects are not attempting to access the same file at the same time. Also, check the installation of the OLE2 server.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04036: Access was denied while performing an operation on an OLE object.**

**Cause:** An attempt was made to update an OLE2 object without write access.

**Action:** Obtain the proper permissions to the file before trying to update it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04037: File operation on OLE object failed because disk is write-protected.**

**Cause:** An attempt was made to save to file an OLE2 object but it failed because the disk is write-protected.

**Action:** Save the object to a disk with write privileges, if possible. If not, no action is necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04038: Unexpected error occurred in the file system while performing an operation on an OLE object.**

**Cause:** A non-specific file error such as a corruption of the hard disk occurred.

**Action:** Refer to the operating system documentation more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04039: An unexpected error was returned by OLE.**

**Cause:** A non-specific OLE error occurred.

**Action:** Refer to the Microsoft documentation for more information.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04040: Incorrect or corrupted OLE object persistent data was encountered. The OLE object cannot be restored from this data**

**Cause:** The information used by the OLE server to restore the OLE2 object in the report is incorrect or has been corrupted. Possible causes for this error include:  
Case 1: If boilerplate, the file has become corrupted. Case 2: If field, either the database has been corrupted, or the LONG RAW column referenced does not contain OLE2 objects.

**Action:** Take the following actions to correct this error: If Case 1: Verify that the object is viable by embedding it in a container using another application. If Case 2: Use SQL\*Plus to check the table in the database and verify the contents of the column.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-04041: No operations are defined on this object or the object is static.**

**Cause:** An attempt was made to take some action on an OLE2 object but no actions have been defined as applying to the object. Possibly the object was converted to a static bitmap.

**Action:** No action is necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04042: The requested action on the OLE object is valid, but cannot be performed at this moment. The object server may be busy.**

**Cause:** An attempt to take a valid action on an OLE2 object failed, due to lack of server resources. A possible cause is that an attempt was made to open a second instance of a single-instance application.

**Action:** Check system resources (such as memory) and increase where possible, or try the operation later.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04043: The operation requested on the object is invalid and cannot be performed.**

**Cause:** The action attempted on an OLE2 object was not recognized as valid.

**Action:** Verify that the proper version of the OLE server is correctly installed. Reinstall if necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-04044: The system registry cannot be accessed.**

**Cause:** A read or write operation in the system registry failed.

**Action:** Verify that there are enough free system resources and the registry is not corrupted. Consult the Microsoft documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04045: A problem occurred in the system registry.**

**Cause:** Some information about the server is missing from the registry.

**Action:** Verify that the OLE server is installed correctly. Reinstall if necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04100: An attempt to execute data source failed.**

**Cause:** An internal error occurred while executing the specific pluggable data source.

**Action:** Look for more details in the engine trace.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-04101: An attempt to create conditions for pluggable data source failed.**

**Cause:** An internal error occurred while creating conditions for the specific pluggable data source.

**Action:** Look for more details in the engine trace in case of a custom PDS.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-04102: An attempt to fetch pluggable data source failed.**

**Cause:** An internal error occurred when fetching the resultset of the pluggable data source.

**Action:** Look for more details in the engine trace in case of a custom PDS.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-04103: An attempt to set up pluggable data source driver failed.**

**Cause:** An internal error occurred.

**Action:** Verify the installation. For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Data

**REP-04104: Pluggable data source {0} references unknown column {1}**

**Cause:** An invalid column is being referenced in the pluggable data source query.

**Action:** Verify the PDS query.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-04105: An attempt to create pluggable data source factory {0} failed.**

**Cause:** The pluggable data source factory class specification in the preference file is invalid.

**Action:** Validate the specification of pluggable data source factory classes in the preference file.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-04106: An attempt to edit the query failed because it was created with a later version ({0}) of pluggable data source factory {1}.**

**Cause:** Query was created with a later version of pluggable data source factory than the current Builder session's registered factory. For this to occur, the major version of the factories must be different. Major version is the value left of the decimal point in the factory version number.

**Action:** Upgrade the registered Oracle Reports Builder pluggable data source factory to one with the equivalent major version number.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-04107: The query will be upgraded from version {0} to current factory version {1}.**

**Cause:** The query was created with an earlier version of pluggable data source factory than the current Builder session's registered factory. For this to occur, the major version of the factories must be different. Major version is the value left of the decimal point in the factory version number.

**Action:** No action is necessary. The query will be automatically upgraded to the version number of the current factory.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04108: The version of the query {0} is different from the pluggable data source factory {1}.**

**Cause:** The query was created with version of pluggable data source factory that is slightly different than the current Builder session's registered factory. For this to occur, the minor version of the factories must be different. Minor version is the value right of the decimal point in the factory version number.

---

**Action:** No action is necessary. The Edit operation will proceed.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-04109: Factory {0} is not a registered factory class.**

**Cause:** The factory class may not be specified correctly in the preference file.

**Action:** Verify that the factory class is specified correctly in the preference file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04110: Query definition for query {0} cannot be found.**

**Cause:** Oracle Reports Builder could not connect to the data source referred in the query.

**Action:** Check the connection information for the PDS query.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04111: Pluggable data source {0} cannot be created.**

**Cause:** Case 1: There is no JVM. Case 2: There is no Oracle Reports pluggable data source driver. Case 3: Pluggable data source class failed to return new pluggable data source object.

**Action:** In Case 1: Check the Oracle Reports and Java installation on the machine. In Case 2: Check if the correct Oracle Reports jar file is in the right place. In Case 3: Check if the right pluggable data source class is in place.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-04112: Oracle Reports Builder can not display the image for pluggable data source {0}.**

**Cause:** The bitmap image may be corrupted.

**Action:** Verify that the bitmap image is not corrupted by confirming that it is saved in .gif format and it can be viewed in the appropriate image tool.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-04113: Changing the type of pluggable data source bound to this parameter may affect query behavior in the Data Model.**

**Cause:** An attempt was made to change a query of one PDS type to another.

**Action:** Verify any parameters used in the query when changing PDS type.

**Level:** 1



---

**Type:** ERROR

**Impact:** Data

**REP-04200: An error occurred in the Mail subsystem.**

**Cause:** An unspecified error occurred during one of the mail operations. Refer to the accompanying error message for more information. Other possible causes of this error include the following: Case 1: MAPI is not properly installed. Case 2: The Windows mail service provider is not properly installed.

**Action:** Take the following actions to correct this error: If Case 1: For other applications using MAPI, check to see if they are functioning properly. If not, try reinstalling MAPI. If Case 2: Verify that the Windows mail service provider is installed, and a mail account exists on the system. For assistance, ask the mail administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04201: An error occurred while initializing the Mail subsystem.**

**Cause:** Oracle Reports Builder tried to initialize MAPI, and could not. Refer to the accompanying error message for more information. Other possible causes of this error include the following: Case 1: MAPI is not installed, the MAPI DLL is out of date, or the Mail entry in the WIN.INI file or registry points to the wrong location. Case 2: There is not enough memory available to perform the operation. Case 3: While logging on, an invalid service profile name, username, or password was entered.

**Action:** Take the following actions to correct this error: If Case 1: Reinstall MAPI, or correct the Mail entry in the WIN.INI file or registry. If Case 2: Exit any unnecessary applications that are running. If that does not work, see the Microsoft documentation for suggested procedures to enhance memory usage. If Case 3: Verify that the logon information is correct, and try again. If that does not work, confirm the account information with the mail administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04202: An error occurred while logging on to the Mail subsystem.**

**Cause:** An attempt was made to log on to the Mail subsystem and an error occurred. Refer to the accompanying error message for more information. Other possible causes of this error include the following: Case 1: An invalid service profile name, username, or password was entered. Case 2: There is not enough memory available.

**Action:** Take the following actions to correct this error: If Case 1: Verify that the logon information is correct, and try again. If that does not work, confirm the account information with the mail administrator. If Case 2: Exit any unnecessary applications that are running. If that does not work, see the Microsoft documentation for suggested procedures to enhance memory usage.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

---

**REP-04203: An error occurred while sending a mail message.**

**Cause:** An error occurred while composing or sending a mail message. Refer to the accompanying error message for more information. Other possible causes of this error include the following: Case 1: There is not enough free space on the disk. Case 2: There is not enough memory available.

**Action:** Take the following actions to correct this error: If Case 1: Free up some space on the disk. If Case 2: Exit any unnecessary applications that are running. If that does not work, see the Microsoft documentation for suggested procedures to enhance memory usage.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04204: An error occurred while trying to validate recipient's name or address.**

**Cause:** Oracle Reports Builder tried to validate the destination mail address, and an error occurred.

**Action:** Confirm that the recipient has a valid mail account, or ask the mail administrator for assistance. Refer to the accompanying error message for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04220: There is a problem with the Mail subsystem.**

**Cause:** An unspecified error occurred during one of the mail operations.

**Action:** Try to free up some disk space or exit any unnecessary applications that are running. If other applications are using MAPI, check to see if they are functioning properly. If not, try reinstalling MAPI.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04221: An attachment file cannot be accessed.**

**Cause:** An error occurred while trying to access attachment file. Possible causes of this error include the following: Case 1: The attachment file cannot be found. Case 2: The attachment file could not be opened, or there was an error reading or writing it.

**Action:** Take the following actions to correct this error: If Case 1: Exit any unnecessary applications that are running. If that does not work, see the Microsoft documentation for suggested procedures to enhance memory usage. If Case 2: Free up some space on the disk.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04222: There is insufficient memory to complete the operation.**

**Cause:** The mail operation cannot be completed, because there is not enough memory available.

---

**Action:** Exit any unnecessary applications that are running. If that does not work, see the Microsoft documentation for suggested procedures to enhance memory usage.

**Level:** 1

**Type:** ERROR

**Impact:** Memory

**REP-04223: No space is left on the device.**

**Cause:** The mail operation cannot be completed because there is not enough free space available on the disk.

**Action:** Free up some space on the disk.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04224: The user name, password, or service profile name is incorrect.**

**Cause:** The logon information entered is invalid.

**Action:** Verify that the logon information is correct, and try again. If that does not work, confirm the account information with the mail administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04225: The operation cannot be completed because the user is not logged on.**

**Cause:** The mail operation could not be completed.

**Action:** Log on to the Mail subsystem, and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04226: A password is required.**

**Cause:** An attempt was made to log on to the Mail subsystem without specifying a password.

**Action:** Specify a valid password, and try again. If that does not work, contact the mail administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04227: The service configuration is invalid.**

**Cause:** The Mail subsystem is incorrectly configured.

**Action:** Contact the mail administrator.

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**REP-04228: MAPI does not support the service requested by Oracle Reports Builder.**

**Cause:** The given implementation of MAPI has limited functionality.

**Action:** Consider upgrading the Windows mail service provider. Contact the mail administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04229: The character set requested is not supported.**

**Cause:** The default character set is not supported by MAPI.

**Action:** Contact the mail administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04230: The size of the text string passed is too large.**

**Cause:** The text string passed is too large for the given implementation of MAPI.

**Action:** Shorten the string, and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-04232: Too many files are opened.**

**Cause:** The given implementation of MAPI does not support the number of files open.

**Action:** Close all unnecessary documents.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06004: Oracle Reports Builder failed to connect to the specified Express server.**

**Cause:** Express server is not running.

**Action:** Verify that Express server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06006: The Express initialization file, XPDATA.INI, cannot be found.**

**Cause:** The Express initialization file, XPDATA.INI, was not found.

**Action:** Check the existence and path of the XPDATA.INI file.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**REP-06007: The Express connection file (XCF) entry cannot be found in the [Install] section of the Express initialization file, XPDATA.INI.**

**Cause:** The Express connection file (XCF) entry was not found in the [Install] section of the Express initialization file, XPDATA.INI.

**Action:** Add an XCF entry to XPDATA.INI file, or replace with a valid XPDATA.INI.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06008: The path specified in ORACLE\_HOME cannot be found.**

**Cause:** The path specified in the the ORACLE\_HOME variable was not found.

**Action:** Check the ORACLE\_HOME setting.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06009: The Oracle SNAPI (OSN) entry cannot be found in the [Install] section of the Express initialization file, XPDATA.INI.**

**Cause:** The Oracle SNAPI (OSN) entry was not found in the [Install] section of the Express initialization file, XPDATA.INI.

**Action:** Add an OSN entry to XPDATA.INI, or replace with a valid XPDATA.INI.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06010: The Express server description cannot be found in any Express connection files (XCFs).**

**Cause:** The Express server description was not found in any Express connection files (XCFs).

**Action:** Check the XCF files.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06011: The size of the generated SQL SELECT statement exceeds the 64K limit.**

**Cause:** The size of the generated SQL SELECT statement exceeds the 64K limit.

**Action:** Modify the query to reduce the size of the SQL statement.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06013: A query failed to run. The Express Query Dialog was invoked with a set of measures/dimensions from a previous query**

---

**Cause:** The Express Query Dialog was invoked with a set of measures/dimensions from a previous query.

**Action:** Reexamine the measures/dimensions in the query.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06014: The report ID was not defined when calling the backend XPFetch[N()].**

**Cause:** The report ID was not defined before calling the backend XPFetch().

**Action:** Define the report ID and resubmit the call to the backend XPFetch().

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06015: A duplicate report ID was used when calling the backend XPPrepere().**

**Cause:** A duplicate report ID was used when the backend XPPrepere() was called.

**Action:** Select a unique report ID and resubmit the call to the backend XPPrepere().

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06017: The saved query contained incorrect or missing information.**

**Cause:** When the query was saved, it contained incorrect or missing information.

**Action:** Check the query and correct the information or supply the missing information and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06018: The internal Oracle Express system databases were not attached.**

**Cause:** The internal Oracle Express system databases were not attached.

**Action:** Attach the internal Oracle Express system databases and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06019: The Oracle Express database specified in the saved query was not attached.**

**Cause:** The Oracle Express database that was specified in the saved query was not attached.

**Action:** Attach the specified Oracle Express database to the saved query and try again.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-06021: The Oracle Express support was not installed.**

**Cause:** The Oracle Express support was not installed.

**Action:** Install the Oracle Express support and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06023: An unexpected end-of-line was received while parsing the Oracle Express query.**

**Cause:** The Oracle Express query might be missing the \s at the end of the line.

**Action:** Check the Oracle Express query for a missing \s at the end of the line, add it, and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06026: A duplicate report ID was detected.**

**Cause:** A duplicate report ID was used.

**Action:** Select a unique report ID and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06027: An undefined report ID was detected.**

**Cause:** The report ID that was used has not yet been defined.

**Action:** Define the report ID and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06030: The XCONNECT.INI file was missing or was invalid.**

**Cause:** This message probably occurred as the result of a missing XCONNECT.INI file. If the XCONNECT.INI file is not missing, then it probably has an invalid General section.

**Action:** Check in ORACLE\_HOME/OLAP/ECF620 to ensure that the XCONNECT.INI file is there. If not, then add it. If the XCONNECT.INI file is there, verify that it has a valid General section.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06031: This report contains Oracle Express queries that are 6i versions. Convert these queries?**

---

**Cause:** An older version of Oracle Express queries cannot be edited or run with the current version of Oracle Express.

**Action:** Reply YES to converting the older version of Oracle Express queries to the newer version of Oracle Express. The queries will be automatically converted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06032: The Oracle Express query {0} failed to convert.**

**Cause:** This error message could have occurred for one of the following reasons: Case 1: The Oracle Express 6i query was corrupted. Case 2: The Oracle Express pluggable data source malfunctioned.

**Action:** Take the following actions to correct this error: If Case 1: Ensure that the query is not corrupted by editing and rerunning it in the OracleAS Reports Services environment. If Case 2: For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-06033: This operation requires converting the {0} Oracle Express query to the newer version of Oracle Express. Proceed with this conversion?**

**Cause:** Older versions of Oracle Express queries cannot be edited or run with the current version of Oracle Express.

**Action:** Accept the conversion by replying YES to the conversion. The queries will be automatically converted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06051: The Oracle Portal connection failed.**

**Cause:** The database server might be down or the user ID and password authentication failed.

**Action:** Check that the database server is available, verify that the user ID and password are correct and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06052: The database requested does not contain a valid Oracle Portal definition.**

**Cause:** This error might have occurred for one of the following reasons: Case 1: The database is not a valid version for the Oracle Portal installation. Case 2: The logged in user does not have permission to read the component definition tables.

**Action:** Take the following actions to correct this error: If Case 1: Select a valid database for the Oracle Portal installation. If Case 2: Obtain permissions for the logged in user to read the component definition tables.

**Level:** 1



---

**Type:** ERROR

**Impact:** Other

**REP-06053: There are no components in Oracle Portal that can be imported.**

**Cause:** This is an information only message notifying that there are no components available to be imported.

**Action:** No action is necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06054: The requested template cannot be found.**

**Cause:** This can occur for one of the following reasons: Case 1: The REPORTS\_XSL\_TEMPLATE environment variable was incorrectly edited. Case 2: The template XSL file was removed from the location where it is supposed to be located.

**Action:** Take the following actions to correct this error: If Case 1: Correct the REPORTS\_XSL\_TEMPLATE and continue. If Case 2: Ensure the template XSL file is in the proper location and continue.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06055: A template error occurred.**

**Cause:** The XSL template file was not a well-formed template.

**Action:** Verify that the XSL template file is correct. If it is, then the best solution is to restore the original one. Experienced users can edit the file to correct the problems.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06056: A temporary directory was invalid.**

**Cause:** The transformation process requires a temporary directory to write a temporary file. The temporary directory might not exist or it might not allow a temporary file to be written to it.

**Action:** Look at the REPORTS\_TMP environment variable and ensure that it corresponds to an existing, writable temporary directory.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06057: A portal component has not been selected.**

**Cause:** OK was clicked without selecting a portal component.

**Action:** Select a portal componet or click Cancel.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-06058: Database client library error.**

**Cause:** Oracle Reports cannot connect to the portal database because of a JDBC error. A common cause is a version mismatch of a database client library in the path.

**Action:** Verify that the Oracle Reports bin directory is listed in the path search order before any other ORACLE\_HOME/bin or other directory that could have a database client. If this does not solve the problem, check the Java classpath and verify that the correct version of the JDBC library is listed before any other library.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06101: The Java Virtual Machine failed to start. Check the Java Runtime Environment setup. {0}:{1}.**

**Cause:** The Java runtime environment in the installation is not valid.

**Action:** Verify that the installation is correct. Reinstall if necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06102: The XML parser failed to start.**

**Cause:** The XML parser jar files are missing in the installation.

**Action:** Verify that the Oracle Fusion Middleware installation is correct. Reinstall if necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06103: An error occurred with the Java Runtime Environment setup.**

**Cause:** The Java runtime environment in the installation is not valid.

**Action:** Verify that the installation is correct. Reinstall if necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06104: The XML report definition is invalid.**

**Cause:** The report definition is invalid.

**Action:** Verify the XML report definition.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06105: An error occurred in the XML report definition at line {0}.**

---

**Cause:** The report definition is invalid.  
**Action:** Verify the XML report definition.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06106: An error occurred in the XML report definition at line {0} in {1}.**

**Cause:** The report definition is invalid.

**Action:** Verify the XML report definition.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06107: The URL for the XML report definition is invalid: {0}.**

**Cause:** The report definition is invalid.

**Action:** Verify the URL location / XML report definition.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06108: The XML report definition cannot be applied.**

**Cause:** This is an internal error.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-06109: The report definition file {0} cannot be saved.**

**Cause:** This is an internal error.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-06110: The query {0} cannot be created.**

**Cause:** The PDS query is invalid.

**Action:** Look into the trace information for more details in case of a custom PDS.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06111: The query {0} cannot be modified.**

**Cause:** The PDS query is invalid.

**Action:** Look into the trace information for more details in case of a custom PDS.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06112: The column {0} cannot be created.**

**Cause:** The PDS query is invalid.

**Action:** Look into the trace information for more details in case of a custom PDS.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06113: The column {0} cannot be modified.**

**Cause:** The PDS query is invalid.

**Action:** Look into the trace information for more details in case of a custom PDS.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06114: The data link {0} cannot be created.**

**Cause:** The PDS query is invalid.

**Action:** Look into the trace information for more details in case of a custom PDS.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-06115: The data link {0} cannot be modified.**

**Cause:** The PDS query is invalid.

**Action:** Look into the trace information for more details in case of a custom PDS.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-06116: The field {0} cannot be created.**

**Cause:** The PDS query is invalid.

**Action:** Look into the trace information for more details in case of a custom PDS.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06117: The field {0} cannot be modified.**

**Cause:** The PDS query is invalid.

**Action:** Look into the trace information for more details in case of a custom PDS.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**REP-06118: The layout for {0} cannot be defaulted.**

**Cause:** This is an internal error.

**Action:** Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-06119: Format exception {0} for the field {1} cannot be created.**

**Cause:** This is an internal error.

**Action:** Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-06120: Condition {0} in the format exception {1} for the field {2} is invalid.**

**Cause:** This is an internal error.

**Action:** Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-06121: The specified layout style {0} is invalid.**

**Cause:** An attempt was made to use an invalid layout style.

**Action:** Verify the layout style for the report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06122: The specified layout style {0} in {1} is invalid.**

**Cause:** An attempt was made to use invalid layout style.

**Action:** Verify the layout style for the report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06123: Source {0} for field {1} is invalid.**

**Cause:** The value used for the field is invalid.

**Action:** Verify the value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06124: A PL/SQL compilation error occurred in {0}.**

---

**Cause:** The PL/SQL procedure is invalid.

**Action:** Verify the PL/SQL procedure.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06200: Reports tag library directive cannot be found: {0} in report file**

**Cause:** Reports was unable to locate the expected JSP taglib directive in the user supplied report file.

**Action:** All Web-based reports must contain the tag library directive. Open any demo .JSP file and copy the taglib lines into the report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06201: Prefix attribute {0} in report file cannot be found.**

**Cause:** The file does not contain an rw:objects tag. The tag library directive does not contain the correct prefix attribute or is otherwise corrupted.

**Action:** The rw:objects tag supplies data for report blocks and charts. If this tag is not required in the file then this message can be ignored. If data is required, use the data wizard to add a data model to the report. Open any demo .jsp file and replace the taglib lines in the report with the lines from the demo file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06202: A rw:report tag in the template file cannot be found.**

**Cause:** The file contains a taglib directive but does not contain a rw:report tag.

**Action:** The template file can still be used but the rw:report tag must be added to a report before a data model can be added.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06203: Template file cannot be parsed.**

**Cause:** Reports was unable to parse the indicated file. Any attempt to execute the report will not run.

**Action:** Check the JSP syntax against the documentation in the Help system.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06204: The <rw:objects> tag cannot be found. Save operation aborted**

**Cause:** The <rw:objects> tag was missing or invalid JSP syntax was found within the document.

**Action:** Check the JSP syntax against the documentation in the Help system.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06205: The ID attribute of tag {0} is not unique.**

**Cause:** The report contains duplicate JSP ID attributes.

**Action:** JSP ID attributes must be unique within a page. Change the ID of the tags that are not unique.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06206: Tag {0} must be inside the rw:report tag.**

**Cause:** A Reports JSP tag is outside the rw:report tag.

**Action:** All Reports JSP tags must be inside the rw:report tag. Move the tag inside the rw:report tag. The easiest way to prevent this error is to move the </rw:report> tag to the bottom of the page.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06207: Tag {0} tag has an invalid scope.**

**Cause:** A Reports JSP tag is outside of the correct context.

**Action:** Move the tag to its correct scope.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06208: More than one rw:report tag is found. A report page can have only one rw:report tag.**

**Cause:** The report contains more than one set of rw:report tags.

**Action:** Add <rw:report> after the taglib lines at the top of the page. Add </rw:report> at the bottom of the page. Remove the extra rw:report tags.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06209: Required Reports JSP tags are missing. The required Reports JPS tags have been added to the saved file.**

**Cause:** When saving the JSP file, required Reports JSP tags were not found.

**Action:** Click OK to add the required tags and save the file. Click Cancel to prevent Oracle Reports Builder from adding the tags, and not save the file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-06210: Required Reports JSP tags are being added to the file.**

**Cause:** If the file does not contain the required Reports JSP tags when it is first opened, Oracle Reports Builder adds the Reports JSP tags to the file loaded in memory. The original file on disk is not touched.

**Action:** Click OK to continue working on the file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06211: The graph XML definition cannot be parsed.**

**Cause:** Oracle Reports was unable to parse the XML definition of the graph.

**Action:** Check the graph XML DTD against the Oracle BI Beans documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06212: The graph definition cannot be parsed.**

**Cause:** Oracle Reports was unable to parse the definition of the graph.

**Action:** Check the graph tag against the reports.tld.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06213: A report level cursor cannot be created.**

**Cause:** An internal error occurred when creating the report level cursor.

**Action:** Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-06214: A group cursor cannot be created.**

**Cause:** An internal error occurred when creating the group cursor.

**Action:** Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-06215: An error occurred retrieving the next row from the cursor.**

**Cause:** An internal error occurred when moving the group cursor to the next row.

**Action:** Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other



---

**REP-06216: Unable to create related cursor**

**Cause:** An internal error occurred when creating the related group cursor.

**Action:** Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-06217: No source specified for cursor**

**Cause:** An internal error occurred. The cursor's source (that is, report for report level cursor, group for group cursor) is not specified.

**Action:** Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-06218: Value of unknown column {0} cannot be retrieved.**

**Cause:** The column name is invalid.

**Action:** Provide a valid column name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06219: Column {0} is not in the given cursor hierarchy.**

**Cause:** The column does not belong to the cursor provided.

**Action:** Modify the report so that the column belongs to given cursor hierarchy.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06220: Value of column cannot be retrieved.**

**Cause:** An internal error occurred when getting the value of the column.

**Action:** Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-06221: Column {0} cannot be found.**

**Cause:** An internal error occurred when looking for a column.

**Action:** Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-06222: The column in the given cursor cannot be found.**

---

**Cause:** The column does not belong to the cursor provided.

**Action:** Modify the report so that column belongs to the given cursor.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-06223: Attempt to determine which cursor a column belongs to failed.**

**Cause:** An internal error occurred when trying to find out to which cursor a column belongs, among a given list of cursors.

**Action:** Contact Oracle Support Services if the problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-16500: This program can only be invoked as a CGI executable.**

**Cause:** The Web CGI executable was invoked outside the Web Server context.

**Action:** The CGI executable must be invoked by a Web server to work properly.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16501: The Reports Web Agent key map file was not set up properly.**

**Cause:** The key map file cannot be found at the location specified.

**Action:** Check the file location.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16504: The message subsystem cannot be initialized.**

**Cause:** The Oracle Reports message file cannot be found or opened.

**Action:** Check the installation. Verify that the Oracle Reports message file was installed properly.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16505: A general error occurred during initialization.**

**Cause:** A general error occurred.

**Action:** Check the installation and availability of system resources.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16506: The URL contains badly-formed escapes.**

---

**Cause:** The submitted URL is badly formed.

**Action:** See the URL rules in the Web Agent documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16507: The key is unrecognized.**

**Cause:** The key map configuration is active, but the specified key in the URL is unrecognized, and the command line cannot be built.

**Action:** Check the key value and keymap file setup and contents.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16508: Key %s is unrecognized.**

**Cause:** The key map configuration is active, but the specified key in the URL is unrecognized, and the command line cannot be built. This error may be due to bad URL syntax, or the key in the URL was not found in the key map file.

**Action:** Check the key value and keymap file setup and contents.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16509: Syntax errors are found in the key map file.**

**Cause:** Syntax errors occurred in the key map file.

**Action:** Check the key map file contents (see Web Agent documentation for rules). Check a definition of submitted key.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16510: Usage in incorrect.**

**Cause:** This is a generic error for a non-verbose run.

**Action:** Enable verbosity and check the real message.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16511: The URL contains too many parameters.**

**Cause:** The URL contains too many parameters (it is too long).

**Action:** Use a shorter URL or the key map file to shorten the URL.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-16512: out of memory**

**Cause:** There is not enough memory to perform the operation.

**Action:** Verify that enough system resources are available.

**Level:** 1

**Type:** ERROR

**Impact:** Memory

**REP-16513: Communication with the Reports Server is lost.**

**Cause:** Reports Server is not answering.

**Action:** Verify that Reports Server is up and the tnsnames.ora network setup has a correct entry for it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16514: The report cannot be run.**

**Cause:** This is a generic error for a report run failure.

**Action:** See the detailed error message from Reports Server.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16515: The report output cannot be accessed.**

**Cause:** The Web Agent cannot access Reports Server run output.

**Action:** Check the Web Agent setup (especially WEBLOC variable).

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16516: The Reports Server is being shut down.**

**Cause:** Reports Server is going down.

**Action:** Try again later.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16517: The Oracle Reports job is canceled upon user request.**

**Cause:** The Oracle Reports job was canceled.

**Action:** Try again if necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16518: The Reports Engine terminated abnormally.**

---

**Cause:** The Reports Engine had problem with the report.

**Action:** Contact the Reports Server administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16519: The Oracle Reports job has terminated with an error.**

**Cause:** This is a generic error message for report run error.

**Action:** See the detailed error message from Reports Server.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16520: An error occurred while queuing a job to Reports Server.**

**Cause:** An error occurred while enqueueing report to run.

**Action:** Try again later.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16521: An error occurred while parsing the Reports Server command line.**

**Cause:** An error occurred while attempting to run a report and process a command line.

**Action:** Contact the Reports Server administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16522: The Reports Server name is not specified.**

**Cause:** An error occurred while attempting to run a report and process a command line.

**Action:** Contact the Reports Server administrator. Check the command line for a server name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16523: A report name is not specified.**

**Cause:** An error occurred while attempting to run a report and process a command line.

**Action:** Contact the Reports Server administrator. Check the command line for a report name.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**REP-16524: A database logon is not specified.**

**Cause:** An error occurred while attempting to run a report and process a command line.

**Action:** Contact the Reports Server administrator. Check the command line for database logon.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16525: The scheduling command cannot be interpreted.**

**Cause:** An error occurred while attempting to run a report and process a command line.

**Action:** Contact the Reports Server administrator. Check the SCHEDULE parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16526: The time tolerance cannot be interpreted.**

**Cause:** An error occurred while attempting to run a report and process a command line.

**Action:** Contact the Reports Server administrator. Check the TOLERANCE parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16527: The Parameter Form type is invalid.**

**Cause:** An error occurred while attempting to run a report and process a command line.

**Action:** Contact the Reports Server administrator. Check the PARAMFORM parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16528: An error occurred while communicating with the Reports Server.**

**Cause:** A communication problem occurred.

**Action:** Try again later.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16529: The job cannot be killed.**

---

**Cause:** This is a generic message for job kill failure.

**Action:** Investigate why the job cannot be killed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16530: The job ID is invalid.**

**Cause:** The ID of the Reports Server job is invalid.

**Action:** Verify the ID.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16531: The job is already finished.**

**Cause:** The ID of the Reports Server job is invalid.

**Action:** Verify the ID.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16532: The job is not done yet. Try again later.**

**Cause:** The ID of the Reports Server job is invalid.

**Action:** Verify the ID.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16533: There are insufficient privileges to perform the requested action.**

**Cause:** The ID of the Reports Server job is invalid.

**Action:** Verify the ID and privileges.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16534: Report output cannot be accessed.**

**Cause:** The Oracle Reports output directory is not accessible.

**Action:** Check the directory specification and the setup (REPORTS\_WEBLOC or REPORTS\_WEBLOC\_TRANSLATED environment is probably invalid).

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16535: Report output cannot be accessed.**

**Cause:** The Oracle Reports output directory is not accessible.

---

**Action:** Check the directory specification and the setup (REPORTS\_WEBLOC or REPORTS\_WEBLOC\_TRANSLATED environment is probably invalid).

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16537: Report output cannot be saved.**

**Cause:** Report output of the returned name already exists in the Web directory.

**Action:** Check the Web Agent setup (REPORTS\_WEBLOC\_TRANSLATED environment probably points to the same location as a Reports Server cache).

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16538: Report output was successfully printed.**

**Cause:** The report was successfully run to the printer.

**Action:** No action is needed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16539: Report output was successfully mailed.**

**Cause:** The report was successfully run to mail.

**Action:** No action is needed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16540: Report output was successfully written to the requested destination.**

**Cause:** The report was successfully run to the requested destype.

**Action:** No action is needed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16541: Log on before running the report.**

**Cause:** It is necessary to log on before running the report.

**Action:** Log on again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16542: Report output was successfully written to the InterOffice repository.**

**Cause:** The report was successfully run to the InterOffice repository.



---

**Action:** No action is needed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16543: The report output cannot be accessed.**

**Cause:** The Oracle Reports output directory is not accessible.

**Action:** Check the directory specification. Check the setup (REPORTS\_VIRTUAL\_MAP, REPORTS\_PHYSICAL\_MAP and REPORTS\_SHARED\_CACHE environment is probably invalid.)

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-16544: The report output cannot be accessed.**

**Cause:** The Oracle Reports output directory is not accessible.

**Action:** Check directory specification. Check the setup (REPORTS\_VIRTUAL\_MAP, REPORTS\_PHYSICAL\_MAP and REPORTS\_SHARED\_CACHE environment is probably invalid.)

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-20091: Save the current document before disconnecting from the database?**

**Cause:** An open document is stored in the database. If disconnected from the database, changes cannot be saved to the database.

**Action:** Select Yes to save the document before disconnecting from the database; the document remains open to reconnect if desired and save it to the database again. Select No to disconnect from the database without saving the document; the document remains open. Select Cancel to remain connected to the database without saving; once again, the document remains open.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-20099: Printer changed while previewing. Printer font remapping could cause truncation. Continue with printing?**

**Cause:** In the time between running the report and selecting Print from the Previewer, the default printer has changed.

**Action:** Select Yes to print anyway. Select No to halt printing, then close the report and either reset the printer and run the report again, or simply run it again to format it for the current printer.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-20128: The report was not run with DESTYPE=PREVIEW. Screen font remapping could cause truncation. Continue with printing?**

**Cause:** Print was selected from the Previewer, but specified Screen instead of Preview, which formats the report as though using printer fonts and provides a more accurate view of the report's printed output.

**Action:** Select Yes to print anyway. Select No to halt printing. Then close the report and run it again while specifying Preview to format it for the printer.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-20129: Opening a report saved with a newer version of Oracle Reports Builder. Functionality may be lost. Continue?**

**Cause:** An attempt was made to open a report with a version of Oracle Reports Builder older than the version used to create the report. If the report uses functionality unavailable in the older version, that functionality will be eliminated from the report.

**Action:** To avoid losing functionality, do not open the report until after upgrading to the most recent version of Oracle Reports Builder.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-20135: A layout does not exist. Create a default layout?**

**Cause:** An attempt was made to run the report after creating a data model but before creating a layout.

**Action:** Select Yes to create a default layout using the Report Wizard. Select No to run the report without a layout.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-20136: The region chosen for the default layout is too small. Extend the region to page boundaries?**

**Cause:** The Report Block tool was used to draw a region for a layout that was not large enough to accommodate the settings specified in the Report Block Wizard.

**Action:** Select Yes to have Oracle Reports Builder extend the possible range of the layout to the boundaries of a report page, or select No and change the settings in the Report Block Wizard to shrink the size of the layout.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-20138: Oracle Reports Builder tables may not be installed in the database.**

**Cause:** Oracle Reports Builder was not able to access its tables in the database.

**Action:** Inform the database administrator that the Oracle Reports Builder tables were not successfully installed in the database.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-20139: New Parameter Form layout will not fit its current size. Increase the number of pages to fit?**

**Cause:** The new Parameter Form is too big to fit on the number of pages specified for the Parameter Form in the Report Properties dialog box.

**Action:** Either select Yes to have Oracle Reports Builder increase the number of pages in the Parameter Form, or select No and change the settings in the Report Properties dialog to enlarge the Parameter Form.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-20144: Opening a report saved with a newer version of Oracle Reports Builder. Functionality may be lost.**

**Cause:** An attempt was made to open a report with a version of Oracle Reports Builder older than the version used to create the report. If the report uses functionality unavailable in the older version, that functionality will be eliminated from the report.

**Action:** To avoid losing functionality, do not open the report until after upgrading to the most recent version of Oracle Reports Builder.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-20146: This action may invalidate references to columns in the referenced object.**

**Cause:** Collapsing a Database Ref, Database Nested Table, or Database Varray column invalidates any external use of the referenced columns. for example, in PL/SQL Program Units or in Summary Columns.

**Action:** To use the referenced columns, do not collapse the Database Ref, Database Nested Table, or Database Varray columns referencing them.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-20147: A column link for this detail SQL query cannot be implemented. Converting to group link.**

**Cause:** Oracle Reports Builder can only insert column to column links into supported SQL. It defaults to a group to group link in this case.

**Action:** Manually insert the required link clause into the detail SQL query.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-20150: Page width of report {0} was changed to fit the font for a character cell as a consequence of font-mapping.**

**Cause:** A character font has been substituted for a bitmapped font in the report, and the page width has been adjusted accordingly. A possible cause: a bitmapped report is being opened in the character-mode runtime engine.

**Action:** To map the font to a specific font, edit the font alias file (uifont.ali or Oracle Font Aliases, depending on the platform) to map the fonts to the desired ones. Otherwise, no action is necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-20151: Some fonts have been changed according to the mapping in the font aliases file.**

**Cause:** One or more fonts saved with the report have been mapped to different ones, due to a change in platform, display, report destination, or mode.

**Action:** To map the font to a specific font, edit the font alias file (uifont.ali or Oracle Font Aliases, depending on the platform) to map the fonts to the desired ones. Otherwise, no action is necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-20160: An AutoRecovery file was detected. Recover unsaved changes for {0}?**

**Cause:** Oracle Reports Builder can automatically recover unsaved report changes if it stops responding or there is a power failure.

**Action:** Either select Yes to have Oracle Reports Builder recover unsaved report changes, or select No to ignore.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-20161: Unable to save AutoRecovery file, Autosave functionality would be disabled.**

**Cause:** Oracle Reports Builder tried to write an AutoRecovery file and could not. The possible causes of this error include the following: Case 1: Lack of necessary privileges to write the file. Case 2: The file system does not have enough room for the file. Case 3: A system error made it impossible to open the file.

**Action:** Either select OK to have Oracle Reports Builder to disable Autosave, or select Cancel to take the following actions to correct this error: If Case 1: Verify the privileges necessary to write the file. If Case 2: Make more room by deleting unnecessary files or expanding storage. If Case 3: Consult the operating system documentation or contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-20190: Quit will terminate the current report, as well as any other pending reports.**

**Cause:** A request to exit the Reports Server or Reports Background Engine was issued while one or more reports are still executing or awaiting execution.

**Action:** To finish report execution, cancel the operation. Otherwise, accept the warning dialog.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-20191: Cannot exit Windows when this program is running. Close the Reports Background Engine and exit Windows.**

**Cause:** The Reports Background Engine requires Windows, but a request was issued to exit Windows while the Reports Background Engine is still running.

**Action:** Exit the Reports Background Engine before exiting Windows.

**Level:** 1

**Type:** ERROR

**Impact:** Operating System

**REP-25206: Converting {0} to {1} failed.**

**Cause:** The most likely cause of this error is that the source type specified was incorrect.

**Action:** Ensure that the source file is of the specified source type.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-25207: Invalid conversion: stype and dtype are not of the same document type.**

**Cause:** An attempt was made to convert a document of one type to another type; that is, an attempt to convert one of the possible report files to a PL/SQL file, or vice versa.

**Action:** Ensure that the source and destination of the conversion are the same type of document.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-25401: User exit .DLL file {0} cannot be found.**

**Cause:** The report attempted to execute a user exit, but the user exit .DLL file could not be located. This file typically resides in: the current directory the Windows directory (typically \\WINDOWS) the Windows system directory (typically \\WINDOWS\\SYSTEM) the directory containing the executable file for the current task the directories listed in the PATH environment variable the list of directories mapped in a network

**Action:** Locate the specified .DLL file and place it in one of the directories listed above.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-25402: An internal error occurred attempting to locate user exit .DLL file {0} within file {1}**

**Cause:** The report attempted to execute a user exit, but certain functions used to locate and execute user exits cannot be located in the user exit .DLL file. This means that the user exit .DLL was built incorrectly, because these functions are located in a .OBJ file shipped with Oracle Reports Builder, which should always be linked into the user exit .DLL.

**Action:** Rebuild the specified user exit .DLL correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-31681: Connecting to a different database may invalidate existing data model.**

**Cause:** Only one connection to a database is valid at a time. If a connection is established to different database, the existing data model may not be valid afterward.

**Action:** To keep the existing data model valid, do not reconnect to a different database unless the queries are compatible with the new database connection.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-31700: The report definition is incomplete, or the query does not have break groups. Cannot run the Web Wizard.**

**Cause:** The report definition was not completed before running the Web Wizard. To run the Web Wizard, the report definition must contain a Data Model with multiple groups and a valid Paper Layout.

**Action:** Create at least one query with multiple groups and default the layout using the Report Wizard.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-31800: Image file {0} cannot be found.**

**Cause:** Oracle Reports Builder could not locate one of its image files. Possible causes of this error include: Case 1: The image file does not exist Case 2: The image file is in the wrong place. Case 3: The environment is not configured properly.

**Action:** Take the following actions to correct this error: If Case 1: Verify that the image file is present. If Case 2: Verify that the image file is in the proper directory. If Case 3: Verify that the environment is set correctly. On UNIX, verify that the proper environment variable is set, and on MS Windows check the file oracle.ini.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-31801: Image {0} specified in the template cannot be found.**

**Cause:** Oracle Reports Builder could not locate the image corresponding to the chosen template. Possible causes of this error include: Case 1: The image file does not exist Case 2: The image file is in the wrong place. Case 3: The environment is not configured properly.

**Action:** Take the following actions to correct this error: If Case 1: Verify that the image file is present. If Case 2: Verify that the image file is in the proper directory. If Case 3: Verify that the environment is set correctly. On UNIX, verify that the proper environment variable is set, and on MS Windows check the file oracle.ini.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-31802: Enter a SQL statement on this page.**

**Cause:** In order for the wizard to create the report, a valid SQL text must exist.

**Action:** Enter a SQL statement.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-31803: SQL text cannot be checked due to no database connection.**

**Cause:** The wizard requires a connection to a database in order to check the SQL text.

**Action:** Connect to a database by typing in a login string whenever the Connect dialog is shown. Confirm logon information with the database administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-31804: The SQL is OK.**

**Cause:** The wizard has checked the SQL text against the database and has confirmed that it will work.

**Action:** No changes are needed to the SQL text.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-31805: Break level {0} has no valid break columns.**

**Cause:** Each break level must contain at least one valid break column. A break column cannot be a summary or placeholder column. Nor can it have a data type of Raw, Longraw, or Long.

**Action:** Provide at least one valid break column for the break level or move all columns that are currently in this break level to another level which contains a valid break column.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**REP-31806: All fields cannot be designated to be break fields.**

**Cause:** All fields were chosen to be break fields. Each break field designated groups the data of the fields that are not break fields. With no non-break fields, this situation is invalid.

**Action:** Designate at least one field to be a non-break field. For example, remove all break fields from the highest numbered break level (that is, from the bottom of the list of break fields).

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-31807: Template file {0} cannot be found.**

**Cause:** Oracle Reports Builder could not locate the template file with the given name. Possible causes of this error include: Case 1: The template file does not exist. Case 2: The template file is in the wrong place. Case 3: The environment is not configured properly.

**Action:** Take the following actions to correct this error: If Case 1: Verify that the template file is present. If Case 2: Verify that the template file is in the proper directory. If Case 3: Verify that the environment is set correctly. On UNIX, verify that the proper environment variable is set, and on MS Windows check the file oracle.ini.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-31808: A SQL statement must be entered.**

**Cause:** A SQL statement was not entered for the wizard to generate a report.

**Action:** Enter a SQL statement in the wizard tab.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-31809: At least one field to display must be chosen.**

**Cause:** No field has been selected to display.

**Action:** Select some fields to display.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-31810: At least one break group must be created.**

**Cause:** The current report style needs breaks groups.

**Action:** Create some break groups.

**Level:** 1

**Type:** ERROR



---

**Impact:** Other

**REP-31811: At least one matrix row must be selected.**

**Cause:** Nothing has been selected as matrix rows.

**Action:** Select some columns as matrix rows.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-31812: At least one matrix column must be selected.**

**Cause:** Nothing has been selected as matrix columns.

**Action:** Select some columns as matrix columns.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-31813: At least one matrix cell must be selected.**

**Cause:** Nothing has been selected as matrix cells.

**Action:** Select some columns as matrix cells.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-31814: At least one matrix break must be selected.**

**Cause:** Nothing has been selected as matrix breaks.

**Action:** Create some matrix break groups.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-31815: At least one field must be displayed per group.**

**Cause:** This problem is due to: 1) This field has been specified as a group field. 2) The group of this field has been defaulted, and this field is the only one that has been marked as "to be defaulted" in its group.

**Action:** 1) If this field has been specified as a group field, go to the group page to deselect this field. 2) If the group of this field has been default, go to the group page to deselect that group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-31816: Groups to be defaulted must be selected.**

**Cause:** No group has been selected to be defaulted.

**Action:** Select groups to be defaulted.

**Level:** 1

---

Type: ERROR

Impact: Other

**REP-31817: At the top of the group. Cannot move up.**

Cause: This column is at the top of its group.

Action: Do not try to move this column up.

Level: 1

Type: ERROR

Impact: Other

**REP-31818: At the bottom of the group. Cannot move down.**

Cause: This column is at the bottom of its group.

Action: Do not try to move this column up.

Level: 1

Type: ERROR

Impact: Other

**REP-31819: Report level columns cannot be reordered.**

Cause: Report level columns do not have the POS attribute.

Action: Set where to display the report level columns in the Paper Layout editor.

Level: 1

Type: ERROR

Impact: Other

**REP-31820: Selected groups have no columns in them.**

Cause: Selected groups have no columns in them, so no report can be generated.

Action: Select some other groups.

Level: 1

Type: ERROR

Impact: Other

**REP-31821: There is no text specified in the text editor.**

Cause: The text for a mailing label or form letter report is empty.

Action: Type some text in the text editor.

Level: 1

Type: ERROR

Impact: Other

**REP-31822: One group must be selected.**

Cause: No group has been selected.

Action: Go to the group page and select one group.

Level: 1

Type: ERROR

Impact: Other

---

**REP-31823: One and only one group must be selected.**

**Cause:** There is more than one group selected.

**Action:** Select one and only one group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-31824: Another group must be selected since there are no columns in the selected group.**

**Cause:** There are no columns in the selected group.

**Action:** Select another group that has columns.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-31825: Cancel the wizard and fix the problem in report editors.**

**Cause:** The data model is invalid or the default region is too small.

**Action:** Fix the problem in the Data Model editor or Paper Layout editor.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-31826: A custom template file name is not specified.**

**Cause:** A custom template is selected, but no template file name is specified.

**Action:** Type a custom template file name, or click Browse button to navigate to it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-31827: Invalid print direction or illegal defaulting of page level summary column.**

**Cause:** The print direction against one or more groups is invalid for the requested default style, or page level summary column was selected to be defaulted (page level summaries are not supported within defaulting).

**Action:** Alter the print direction against the group or the default style, or deselect all page level summaries.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-31828: The query definition is invalid.**

**Cause:** The query is not properly defined.

**Action:** Define a valid query.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-31906: This type of graph requires more categories than have been selected.**

**Cause:** The number of categories required for a graph depends on the type of graph selected. This type of graph requires more categories than were selected.

**Action:** Select the minimum number of categories required by the type of graph selected in a previous panel.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-31907: This type of graph requires more data columns than have been selected**

**Cause:** The number of data columns required for this graph depends on the type of graph selected. This type of graph requires more data columns than were selected.

**Action:** Select the minimum number of data columns required by the type of graph selected in a previous panel.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-31908: The Data Model has changed. Reselect categories and data for the created graph.**

**Cause:** The data model has been changed for an existing graph.

**Action:** Reselect the categories and data for the graph.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-31909: This type of graph requires %s categories.**

**Cause:** The number of categories required for a graph depends on the type of graph selected. This type of graph requires %s categories.

**Action:** Select the minimum number of categories required by the type of graph selected in a previous panel.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-31910: This type of graph requires %s data columns.**

**Cause:** The number of data columns required for this graph depends on the type of graph selected. This type of graph requires %s data columns.

**Action:** Select the minimum number of data columns required by the type of graph selected in a previous panel.

**Level:** 1

**Type:** ERROR

---

**Impact:** Data

**REP-31950: An error occurred in the Oracle Reports Builder graph support.**

**Cause:** An error occurred initializing the Graph Wizard.

**Action:** Verify that all components are installed properly. Restart the product.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-31951: The Graph Wizard cannot be initialized.**

**Cause:** The Graph Builder library could not be initialized.

**Action:** Verify that the Graph Wizard and Graphics Runtime are properly installed and that there are enough system resources available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-31952: The Graph Wizard cannot be initialized due to incorrect version of libraries.**

**Cause:** The Graph Builder library could not be initialized.

**Action:** Verify that the Graph Wizard libraries are properly installed and that there are enough system resources available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-31953: An error occurred in the Graph Wizard.**

**Cause:** The Graph Builder library could not be initialized.

**Action:** Verify that the Graph Wizard libraries are properly installed and that there are enough system resources available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-31954: An error occurred in the Graph Wizard user interface.**

**Cause:** The Graph Wizard failed to load properly.

**Action:** Verify that the Graph Wizard libraries are properly installed and that there are enough system resources available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-31955: An error occurred in the graph runtime executable while attempting to create a graph.**

**Cause:** The Graph Builder failed to build the graph.

---

**Action:** Verify that the Graph Wizard libraries are properly installed and that there are enough system resources available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-31980: Incorrect field mapping is specified. The graph will not be generated.**

**Cause:** Fields for both category and value axes were not specified in the Graph Wizard.

**Action:** Reenter the Graph Wizard and specify fields for both Category and Value axes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-31981: The Data Model is empty or invalid.**

**Cause:** The Graph Wizard was invoked on an empty report.

**Action:** Create report (at least a data model) and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-32600: An unexpected error occurred. Aborting.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-32601: The report already exists in a translation file.**

**Cause:** An attempt was made to overwrite an existing translation file.

**Action:** Select a different name for the translation file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-32602: Oracle Reports Builder cannot be initialized.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-32603: The VGS system cannot be initialized.**

**Cause:** An abnormal condition was encountered.

---

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-32604: A fatal error occurred loading report {0}. Check version.**

**Cause:** The specified report cannot be loaded.

**Action:** Verify that the correct version of the report is being opened.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-32605: The report file cannot be opened for reading.**

**Cause:** The report file is unreadable.

**Action:** Check the read permission of the report file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-32606: File {0} cannot be opened for reading.**

**Cause:** The specified file cannot be opened.

**Action:** Verify that the file exists and is readable.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-32607: The translation builder tree does not exist.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-32608: Translations for that language do not exist.**

**Cause:** The Translation Manager cannot translate into the given target language.

**Action:** Verify that the target language is supported.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-32609: This is not a valid report tree.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-32610: Source data file {0} does not match.**

**Cause:** The translation file being merged into the report was not created from the selected report.

**Action:** Merge the translation file into the original report.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-32612: The string for the base language cannot be merged.**

**Cause:** An attempt was made to merge the untranslated strings back into the original report.

**Action:** Translate the strings in the translation file and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-32613: A matching VGS string in NX file cannot be found.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-32614: Successfully merged strings for language {0}.**

**Cause:** The operation was completed with no errors.

**Action:** No action is necessary.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-32615: The merge operation failed.**

**Cause:** The merge operation encountered errors.

**Action:** Check the log file for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-32616: Translations in NX file cannot be found.**

**Cause:** The translation file does not contain translated strings.

**Action:** Verify that the correct translation file is used for the given report.



---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-32617: The NX file is corrupt.**

**Cause:** An abnormal condition was encountered.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-32618: The NX file cannot be opened for reading.**

**Cause:** The translation file cannot be opened.

**Action:** Verify that the file exists and is readable.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-32750: The data of image {0} cannot be unpacked. The image has been removed.**

**Cause:** Case 1: The image data is corrupted. Case 2: REPORTS\_DEFAULT\_DISPLAY is set to YES and the image format used is not supported.

**Action:** Take the following actions to correct this error: If Case 1: Import the image again. If Case 2: Verify that the image format is one of the supported formats: GIF, JPEG, JPG, PNG, BMP.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-32751: Some text segments are missing.**

**Cause:** Text segments cannot be found for some boilerplate text. The report could be corrupted.

**Action:** Check the boilerplate text objects in the report. Remove suspicious ones and create replacements for them.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-34202: A value must be entered.**

**Cause:** No value has been entered.

**Action:** Enter a value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-34203: WARNING: The user modified Format Trigger will be overwritten.**

**Continue?**

---

**Cause:** Format trigger has been modified.

**Action:** Click Yes to overwrite the user modified trigger. Click No or Cancel to retain the modified trigger.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-34205: At least one condition must be specified.**

**Cause:** No condition was specified in the Format Exception dialog box.

**Action:** Specify at least one condition.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-34300: No distribution list is available.**

**Cause:** No distribution target has been specified for the report.

**Action:** Create a distribution list.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-34301: The value for the field is invalid.**

**Cause:** An invalid value or no value has been entered for the field.

**Action:** Enter a valid value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-34302: The destination format is not compatible with the runtime mode.**

**Cause:** The destination format must be compatible with the current mode for running the report. Likewise, the destination format must be compatible with all other destination formats in the report. There is no support for mixing bitmap output with character mode output.

**Action:** Ensure all the destination formats are compatible with either character or bitmap output modes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-34305: The keyword setting for the destid={0} is invalid.**

**Cause:** Keyword settings are incorrect in the distribution file.

**Action:** Alter the distribution file to ensure that all entries have valid values.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**REP-34306: No distribution ID has been specified for the destination.**

**Cause:** In the distribution file, the ID for the destination is missing.

**Action:** Add a destination ID to the destination line. For example: Dest1:

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-34307: The destination ID is not unique.**

**Cause:** In the distribution file, the ID for the destination is not unique.

**Action:** Add a unique destination ID for the entry.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-34308: Reference parameter {0} in the distribution list is invalid.**

**Cause:** The reference parameter in the distribution list refers to a wrong group.

**Action:** Repeat on the same group as that of the reference parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-34309: A reference parameter is not allowed in a Report-level distribution list.**

**Cause:** A reference parameter was found in a Report-level distribution list.

**Action:** Remove the reference parameter distribution item from the Report-level distribution list.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-34310: A reference parameter is not allowed in a distribution list for XML destination files.**

**Cause:** An XML destination cannot have a reference parameter in the distribution list.

**Action:** Remove the reference parameter for the XML file destination from the distribution list.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-34311: The XSL transformation file cannot be found.**

**Cause:** The XSL transformation file distribution.xml could not be located.

**Action:** Ensure that the XSL file is placed in ORACLE\_HOME/reports/conf.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-34312: An error occurred in XSL template.**

**Cause:** An error occurred when applying XSL transformation. This could be due to an error in the XSL file.

**Action:** Check the XSL file and ensure the transformations are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-34313: The external file {0} specified in destination {1} cannot be found.**

**Cause:** An external file specified in the distribution list was not found.

**Action:** Verify the correct path of the external file specified.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-34314: The foreach tag cannot be used before both the mail and attach tags at destination {0}.**

**Cause:** The foreach tag was used before both the mail tag and the attach tag.

**Action:** Correct the entry in the XML distribution file to use a single level of foreach tag.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-34315: The instance attribute cannot be used without a foreach tag at destination {0}.**

**Cause:** The instance attribute was used without an enclosing foreach tag.

**Action:** Correct the entry in the XML distribution file to use a foreach tag at the appropriate level.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-34316: Reference parameters cannot be used without a foreach tag in destination {0}.**

**Cause:** Reference parameters were used without a foreach tag.

**Action:** Correct the entry in the XML distribution file to use a foreach tag appropriately.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-34317: The instance attribute cannot be used if 'srctype' is not 'report' in destination {0}.**

**Cause:** The instance attribute was used for a body or attach tag whose source is not a report section.

**Action:** Correct the entry in the XML distribution file to remove the instance attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-34318: The foreach tag cannot be used if 'srctype' is not 'report' in destination {0}.**

**Cause:** A foreach tag was used before an attach tag whose source is not a report section.

**Action:** Correct the entry in the XML distribution file to remove the foreach tag.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-34319: An unknown report section {0} was specified as the source in destination {1}.**

**Cause:** The src attribute in the include tag does not specify a valid report section.

**Action:** Correct the entry in the XML distribution file to use a valid report section. The valid report sections can be any one of 'headerSection', 'mainSection', 'trailerSection', or 'report'.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-34320: Report sections used in destination {1} do not repeat on the same group.**

**Cause:** The report sections used in include tags do not repeat on the same group.

**Action:** Modify the report definition so that all the sections used repeat on the same group. Use only those report section combinations that repeat on the same group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-34321: Only one external file can be specified in the body or attachment at destination {0}.**

**Cause:** More than one external file was specified for the corresponding body or attach tag. Each body or attach tag whose srctype is file, can have only one include tag referring to an external file.

**Action:** Correct the entry in the XML distribution file and specify only one external file for the body or attach tag.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-34322: Inline text for body or attach tag for destination {0} can be specified only if 'srctype' is 'text'.**

**Cause:** Inline text was specified for a body or an attach tag whose 'srctype' is not 'text'.

**Action:** Correct the entry in the XML distribution file and specify the correct 'srctype'.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-34323: Tag {0} specified for destination {1} cannot be empty.**

**Cause:** An empty tag was encountered. Only the include and the property tags can be empty. All other tags must have at least one child.

**Action:** Correct the entry in the XML distribution file by either removing the empty tag or inserting the appropriate child tag for it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-34324: Inline text is missing when 'srctype' is 'text' at destination {0}.**

**Cause:** Inline text was not specified for a body or an attach tag whose 'srctype' is specified as 'text'.

**Action:** Correct the entry in the XML distribution file by specifying the appropriate srctype for the corresponding body or attach tag. If the 'srctype' should be 'text', replace the include tag with inline text.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-34325: A reference parameter is not allowed in a distribution list for DelimitedData destination files.**

**Cause:** DelimitedData destination cannot have a reference parameter in the distribution list.

**Action:** Remove the reference parameter for the DelimitedData file destination from the distribution list.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-34326: SPREADSHEET format is not supported in distribution.**

**Cause:** SPREADSHEET destination cannot be used in distribution.

**Action:** Remove the SPREADSHEET destination from the distribution XML file.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-34501: A Web design tool is not registered.**

**Cause:** The mail destination specified is too long. Destination names must be less than 1024 characters. The PREFS.ORA file does not contain an entry for a Web design tool.

**Action:** Specify a mail destination the 'To' field that is less than 1024 characters. Add an entry for the Web design tool.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-34502: The Web design tool registered cannot be found or run.**

**Cause:** The Web design tool does not exist, or the file exists but cannot run.

**Action:** Correct the PREFS.ORA file and move the Web design program to the correct directory.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-34551: Feature {0} is deprecated. See the Oracle Reports documentation for more information.**

**Cause:** The feature is deprecated.

**Action:** See the Oracle Reports documentation on the Oracle Technology Network (OTN).

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-34552: The Oracle Graphics Graph in this document will not be saved.**

**Cause:** There are one or more obsolete Oracle Graphics graphs in this document that will not be saved.

**Action:** Replace the Oracle Graphics graphs with new graphs generated with the Graph Wizard.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-35000: The output image format specified is not supported.**

**Cause:** The output image format specified on the command line is not supported by Oracle Reports.

**Action:** Specify one of the supported output image formats. Refer to the Oracle Reports online help for a list of supported output image formats.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**REP-35001: An internal error occurred writing the image.**

**Cause:** The image stream may be invalid or corrupt. A failure occurred while reading the image data from the image stream.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-35002: The Reports Toolkit System is not available.**

**Cause:** An error occurred initializing the Reports Toolkit System. The required Java classes were not found.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-35003: CGM or OGD format cannot be converted to image for HTML/HTMLCSS output.**

**Cause:** CGM or OGD is used in the report. It is not supported when Display is not available.

**Action:** Remove the OGD or CGM image used in the report. Set DISPLAY and REPORTS\_DEFAULT\_DISPLAY to NO. Verify that the image format is one of the supported formats: GIF, JPEG, JPG, PNG, BMP.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-35004: The Oracle Reports Font Toolkit Subsystem is not available.**

**Cause:** An error occurred while initializing the Oracle Reports Font Toolkit Subsystem. The required Java classes were not found.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-35503: PDFOWNER and PDFUSER cannot have the same value.**

**Cause:** PDFOWNER and PDFUSER cannot be same.

**Action:** Specify different values for PDFUSER and PDFOWNER.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50000: A generic error occurred while running the job.**

**Cause:** A generic error occurred while running the job.



---

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-50001: The server is initializing.**

**Cause:** Reports Server is initializing.

**Action:** Wait until the Reports Server is ready to serve requests.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50002: The server is shutting down.**

**Cause:** The Reports Server is shutting down.

**Action:** Restart the Reports Server.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50003: The command line is invalid: {0}.**

**Cause:** An invalid command line was submitted.

**Action:** Refer to the Oracle Reports documentation for command-line arguments and syntax.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50004: No report is specified on the command line.**

**Cause:** There is no report name specified on the command line.

**Action:** Specify the name of the report on the command line.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50005: No USERID is specified on the command line.**

**Cause:** There is no USERID keyword specified on the command line.

**Action:** Specify USERID on the command line as part of the database connection information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50006: The SCHEDULE argument is invalid on the command line: {0}.**

**Cause:** The SCHEDULE argument value on the command line is not correct.

---

**Action:** Refer to the Oracle Reports documentation for the correct SCHEDULE argument syntax.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50007: The TOLERANCE argument is invalid on the command line: {0}.**

**Cause:** The TOLERANCE argument value on the command line is not correct.

**Action:** Refer to Oracle Reports documentation for correct TOLERANCE argument syntax.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50008: The report is successfully submitted.**

**Cause:** The report is successfully submitted to the Reports Server.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50009: The report is successfully run.**

**Cause:** The report ran successfully in the Reports Server.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50108: The job is waiting in the queue.**

**Cause:** The job is waiting in the queue to be executed.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50109: The report is opening to run.**

**Cause:** Opening the report to run.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50110: Report {0} is running.**

**Cause:** Running the specified report.

---

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50111: Report {0} finished successfully.**

**Cause:** The report has finished successfully.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50112: The report terminated with error: {0}.**

**Cause:** The report terminated with the stated error.

**Action:** Correct the error and rerun the report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50113: The engine crashed.**

**Cause:** The engine crashed due to an internal error.

**Action:** For assistance, contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-50114: The job is canceled upon user request.**

**Cause:** The job was canceled at the user's request.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50115: The job is canceled as the server is shutting down.**

**Cause:** The job was canceled because the Reports Server is shutting down.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50116: The job execution failed and is waiting for retry.**

**Cause:** The job execution has failed and waiting to be retried.

**Action:** No action required.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50117: The job is sending output.**

**Cause:** The job is sending output to specified destinations.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50118: Report execution is initialized.**

**Cause:** Initializing report execution.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50119: A Before Report trigger is running.**

**Cause:** The report is running a Before Report trigger.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50120: A Between Pages trigger is running.**

**Cause:** The report is running a Between Pages trigger.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50121: An After Report trigger is running.**

**Cause:** The report is running an After Report trigger.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50122: A Before Parameter Form trigger is running.**

**Cause:** The report is running a Before Parameter Form trigger.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**REP-50123: An After Parameter Form trigger is running.**

**Cause:** The report is running an After Parameter Form trigger.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50124: Page {0} is formatting.**

**Cause:** Oracle Reports is formatting the specified page.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50125: An internal exception occurred: {0}.**

**Cause:** Oracle Reports encountered an internal exception.

**Action:** For assistance, contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-50126: File {0} cannot be opened for writing.**

**Cause:** Oracle Reports cannot open the specified file for writing.

**Action:** Check the write permission of the file, or of the directory in which the file is stored.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50127: File {0} cannot be written to.**

**Cause:** Oracle Reports cannot write content to the specified file.

**Action:** Check available disk space to verify that there is enough space to write the file. Verify that no other applications are writing to the same file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50131: An attempt to bind to {0} failed.**

**Cause:** Binding to Reports Server failed.

**Action:** Verify that the Reports Server is running and that it is accessible from this machine.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**REP-50133: The job has been transferred to {0}, the new job ID is {1}.**

**Cause:** The job has been transferred to another server.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50134: Cache subitem {0} does not exist.**

**Cause:** An internal error occurred. Some of the report output is deleted unexpectedly.

**Action:** Rerun the job to get the correct output.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50135: Class {0} cannot be located.**

**Cause:** Oracle Reports cannot locate the specified class.

**Action:** Verify that the specified class is in the CLASSPATH and REPORTS\_CLASSPATH.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50136: An error occurred reading the input stream: {0}.**

**Cause:** Oracle Reports cannot read an input stream due to the stated error.

**Action:** Correct the error and rerun the report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50137: The input stream cannot be closed: {0}.**

**Cause:** Oracle Reports cannot close the input stream due to the stated error.

**Action:** For assistance, contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-50138: A mail server is not available.**

**Cause:** There is no mail server specified in Reports Server configuration file.

**Action:** Add a <mail> element with a server attribute to the Reports Server configuration file.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**REP-50139: File {0} cannot be deleted.**

**Cause:** The specified file cannot be deleted.

**Action:** The file is probably being used by another application. Close that application and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50140: An internal error {0} occurred.**

**Cause:** An internal error occurred.

**Action:** For assistance, contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-50141: File {0} cannot be opened.**

**Cause:** Oracle Reports cannot open the specified file.

**Action:** Check whether the specified file exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50142: File {0} cannot be read.**

**Cause:** Oracle Reports cannot read the specified file.

**Action:** Check read permission for specified file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50143: The job is submitted successfully.**

**Cause:** The job has been submitted successfully.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50145: Duplicate parameter {0} is specified.**

**Cause:** The parameter was specified more than once on the command line.

**Action:** Remove the duplicate parameters.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-50148: A Base64 format error occurred.**

**Cause:** An internal error occurred.

**Action:** For assistance, contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-50149: The parameter value is invalid: {0}.**

**Cause:** Bad parameter value specified.

**Action:** Refer to the Oracle Reports documentation for the correct syntax for the parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50150: The Reports Server object cannot be accessed.**

**Cause:** An incorrect signature or key to access the Reports Server object was provided.

**Action:** Verify permission to access the Reports Server, and correct pair of signature keys.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50151: An error occurred while sending the file to the printer: {0} - {1}.**

**Cause:** Error while sending file to specified printer due to the stated reason.

**Action:** Correct the error and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50152: An error occurred while sending mail: {0}.**

**Cause:** Error while sending mail due to stated reason.

**Action:** Correct the error and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50153: The mail to list is missing.**

**Cause:** Missing TO or DESNAME parameter for mail. These parameters point to the recipient list of the report.

**Action:** Add TO or DESNAME to the command line or the URL.

**Level:** 1

**Type:** ERROR



---

**Impact:** Other

**REP-50155: The job status is unknown.**

**Cause:** Unknown job status.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50156: The scheduled job has expired.**

**Cause:** The scheduled job has run for specified number of times or its expiration time has passed.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50157: An error occurred while sending the file to printer {0}. Exit with error code {1}.**

**Cause:** An error occurred while sending the file to the specified printer.

**Action:** Check if the printer or printer driver is correctly installed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50158: Job finished successfully but output is purged from cache.**

**Cause:** The job has finished successfully, but the output has been purged manually or by the cache system and is no longer available.

**Action:** Rerun the job to regenerate the output.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50159: The report generated successfully but distribution to destinations failed.**

**Cause:** The job has executed successfully, but there were some errors during the distribution of the output.

**Action:** Check the error for each destination, fix them if possible, and rerun the job.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50160: The report is distributing.**

**Cause:** Oracle Reports is distributing the report.

**Action:** No action required.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50161: The database connection string {0} is invalid.**

**Cause:** The database connection string format is not correct.

**Action:** Specify a correct database connection string in the format  
userid=&lt;username&gt; / &lt;password&gt; @ &lt;tnsname&gt;.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50162: The job output is distributing.**

**Cause:** Oracle Reports is distributing the job output.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50163: The job output is copying.**

**Cause:** Oracle Reports is copying the job output.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50164: The job output is printing.**

**Cause:** Oracle Reports is printing the job output.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50165: The job output is mailing.**

**Cause:** Oracle Reports is mailing the job output.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50166: The job output is uploading.**

**Cause:** Oracle Reports is uploading the job output.

**Action:** No action required.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-50168: A syntax error occurred in the Reports Server configuration file {0}.**

**Cause:** A syntax error occurred in the specified Reports Server configuration file.

**Action:** Refer to rwserverconf.xsd for the correct syntax for the server configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**REP-50169: The type of the value for attribute {0} is invalid.**

**Cause:** The type of the value for the specified attribute in the server configuration file is not valid.

**Action:** Refer to rwserverconf.xsd for correct syntax for the attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50170: A syntax error occurred in the Reports Server configuration XSD file {0}.**

**Cause:** A syntax error occurred in the the server configuration XSD file.

**Action:** Use the original rwserverconf.xsd, without any change.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**REP-50171: Authentication failed.**

**Cause:** Authentication failed.

**Action:** Provide the correct authentication information.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**REP-50175: File {0} cannot be found.**

**Cause:** Oracle Reports cannot find the specified file.

**Action:** Check if the file exists on the file system.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50177: The naming service is not available.**

**Cause:** The naming server is down.

**Action:** Start the naming server.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-50180: The naming service failed to shut down.**

**Cause:** Oracle Reports could not stop the naming server.

**Action:** For assistance, contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-50200: OID server cannot connect.**

**Cause:** The OID server is probably down.

**Action:** Verify that the OID server is up.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50201: The user role cannot be retrieved from the OID server.**

**Cause:** The OID server is probably down.

**Action:** Verify that the OID server is up. Also check the Reports Server trace file under \$ORACLE\_HOME/reports/logs/&lt;server>.trc for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50509: Destination ID {0} failed with error {1}.**

**Cause:** Distribution to the ID failed with specified error.

**Action:** Check the distribution list and correct the error.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50602: Servlet config file {0} cannot be parsed. {1}.**

**Cause:** The servlet config file could not be parsed. The XML syntax is incorrect.

**Action:** Correct the servlet config file and start the server.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-50603: The servlet file cannot be found {0}. {1}.**

**Cause:** The rwservlet file is not found.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**REP-51000: The Reports Server name is not specified.**

**Cause:** The Reports Server name is not specified on the command line or in the URL.

**Action:** Specify the Reports Server name as follows: server=&lt;server\_name&gt;.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-51002: Bind to Reports Server {0} failed.**

**Cause:** Failed to connect to Reports Server.

**Action:** Verify that Reports Server is running and that the Reports Server name is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-51004: Get connection object failed.**

**Cause:** Failed to get a connection object from the server. This can happen because the server has reached the maximum number of connections allowed, or the client does not have privileges to make a connection to the server.

**Action:** Increase the maxConnect attribute of the connection element and verify that the client has connect privileges to the server.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-51015: Sending job output to the client failed due to {0}.**

**Cause:** Failed to send job output to client.

**Action:** Fix the problem related to stated reason and rerun the job.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-51017: The user ID is incomplete.**

**Cause:** The value specified for the user ID was incomplete.

**Action:** Specify correct syntax for the user ID:  
&lt;username&gt;/&lt;password&gt;@&lt;tnsname&gt;.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-51018: Database user authentication is missing.**

**Cause:** No database user authentication information was provided.

**Action:** Provide valid database user authentication information.

---

**Level:** 1

**Type:** ERROR

**Impact:** Security

**REP-51019: System user authentication is missing.**

**Cause:** No system user authentication information was provided.

**Action:** Provide valid system user authentication information.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**REP-51020: Authentication for both system user and database user does not match.**

**Cause:** The system and the database user authentication information was different.

**Action:** Provide the same authentication information for the system and database user.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**REP-51021: System and database user authentication is missing.**

**Cause:** No system user and database user authentication information was provided.

**Action:** Provide valid system and database user authentication information.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**REP-51024: The client has not been connected to Reports Server.**

**Cause:** An internal error occurred. The client has not connected to Reports Server before using the server.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-51025: User {0} does not have the privilege to run command {1}.**

**Cause:** An attempt to run the indicated command failed due to insufficient privileges.

**Action:** Contact the Oracle Reports administrator to request the necessary privileges.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-51026: No output is generated for job {0}.**

---

**Cause:** No output was generated for the indicated job.  
**Action:** Check the report and job definition and rerun the job.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-51027: Engine {0} cannot be killed.**

**Cause:** An attempt was made to kill an engine in an older version of Reports Server.

**Action:** This operation is not supported.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-52001: The key map file {0} cannot be read.**

**Cause:** Failed to read the Reports key map file.

**Action:** Verify that the Reports key map file is in ORACLE\_HOME/reports/conf and that it contains valid information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-52002: The key map file {0} cannot be parsed.**

**Cause:** The Reports key map file cannot be parsed.

**Action:** Verify that the Reports key map file has valid entries.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-52003: Read Reports template {0} failed**

**Cause:** The Reports Servlet template cannot be read.

**Action:** Verify that the Reports Servlet template is in ORACLE\_HOME/reports/templates.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-52004: The authentication template {0} cannot be read.**

**Cause:** Failed to read the Reports Servlet authentication template.

**Action:** Verify that the Reports Servlet authentication template is in ORACLE\_HOME/reports/templates.

**Level:** 1

**Type:** ERROR

**Impact:** Security

---

**REP-52005: The specified key {0} does not exist in the key map file.**

**Cause:** The specified key does not exist in the Reports key map file.

**Action:** Verify that the Reports key map file contains the specified key.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-52006: The specified URL {0} cannot be decoded.**

**Cause:** The specified URL cannot be decoded.

**Action:** Verify that the URL is a valid URL.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-52007: A Parameter Form format error was encountered.**

**Cause:** The submitted Parameter Form has an invalid format.

**Action:** Check if the hidden\_run\_parameters variable in the Parameter Form is null.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-52009: No such Web command ({0}).**

**Cause:** The Web command passed in from rwservlet is not a valid command.

**Action:** Check the help page for rwservlet for a valid Web command.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-52010: The specified key map file {0} does not exist.**

**Cause:** The specified key map file does not exist.

**Action:** Verify that the Reports key map file is in ORACLE\_HOME/reports/conf.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-52242: The job with job ID {0} cannot be killed.**

**Cause:** Insufficient privileges to perform this operation, or a job with the specified jobid does not exist.

**Action:** Sufficient privileges are required for this operation. Either log in as administrator or as a user who has sufficient privileges. Specify a valid jobid in the command.

**Level:** 1

**Type:** ERROR



---

**Impact:** Other

**REP-52251: The output of job ID {0} requested on {1} cannot be retrieved.**

**Cause:** Insufficient privileges for this operation, or invalid job ID or nonexistent output.

**Action:** Sufficient privileges are required for this operation. Check if a valid job ID is provided in the command.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-52260: No Oracle Home is specified.**

**Cause:** Oracle Home is not defined in the environment.

**Action:** Define Oracle Home in the environment. See Configuration chapter in the Publishing Reports to the Web manual for details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-52261: Parameter {0} has an incorrect value {1}.**

**Cause:** The specified parameter has an invalid value.

**Action:** Provide correct value for the parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-52262: Diagnostic output is disabled.**

**Cause:** Reports Server is unsecure, the DIAGNOSTIC property is set to NO in rwservlet.properties file, and a valid AUTHID is not specified in command line.

**Action:** Specify a valid AUTHID in the command line or contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-52265: The specified Web command {0} is not supported.**

**Cause:** The web command is not a valid command for this utility.

**Action:** Check the Publishing Reports to the Web manual for a list of valid commands for this utility.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-52266: The in-process Reports Server {0} failed to start.**

**Cause:** There maybe a server with same name already existing in the network.

**Action:** Verify that the server is not already started as a stand alone server.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-52268: The specified HTML code is not allowed: {0}**

**Cause:** HTML tags were specified in the URL command.

**Action:** Either remove the HTML tags in the URL and rerun the report, or set ALLOWHTMLTAGS in rwservlet.properties to YES and restart the OC4J container. However, note that any HTML code included as part of the report request URL may lead to a security compromise as it causes certain browsers to execute any script or code in the URL. This property is set to NO by default, disallowing any malicious HTML code to be entered in the URL when running a report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-52280: An Oracle OID generic error occurred.**

**Cause:** Failed to get resource type or resource values from OID.

**Action:** Check the Oracle OID configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-52281: The connection to Oracle OID using provider URL {0} cannot be established.**

**Cause:** An attempt to connect to Oracle OID using given provider URL and user ID failed.

**Action:** Check the Reports Servlet configuration file and verify that the provider URL and user ID are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-52282: The specified resource type {0} in OID cannot be found.**

**Cause:** The specified resource type is not created in OID

**Action:** Verify that the resource type has been defined in OID.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-52283: The specified resource key {0} in OID cannot be found.**

**Cause:** The specified resource key is not created in OID

**Action:** Verify that the resource key has been defined in OID.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**REP-52284: The create resource URL cannot be retrieved from OID.**

**Cause:** The create resource URL is not defined in OID.

**Action:** Verify that the create resource URL has been defined in OID.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-52285: The user name or subscriber name cannot be found in Logon Server cookie.**

**Cause:** User is not logged on to Logon Server.

**Action:** Log on to Logon Server.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-52286: Parameter SSOCONN requires the Reports Server to be secure and Single Sign-On turned on.**

**Cause:** Either the Reports Server is running in non-secure mode, or the SINGLESIGNON parameter in rwservlet.properties is set to NO.

**Action:** Verify that the Reports Server is running in secure mode, and the SINGLESIGNON parameter in rwservlet.properties is set to YES.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-52287: Parameter SSOCONN and AUTHID cannot be used together.**

**Cause:** SSOCONN and AUTHID are both used in the command line. The AUTHID value overwrites the SSO userid, and SSOCONN requires the SSO user ID. Therefore, using the keywords together on the command line causes a conflict.

**Action:** Remove either SSOCONN or AUTHID from the command line.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**REP-53000: The connection is invalid.**

**Cause:** An internal error occurred.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-53053: Arguments for the function call are invalid.**

**Cause:** Bad arguments for the function call.

**Action:** Refer to the Oracle Reports help for the function arguments.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-53054: AUTHID is not allowed in the URL.**

**Cause:** AUTHID was specified in the URL.

**Action:** Either remove AUTHID in the URL and rerun the report, or set ALLOWAUTHID in rwservlet.properties to YES and restart the OC4J container.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**REP-54000: The cache item is not found in the cache system.**

**Cause:** The cache item has been deleted manually or by the cache system.

**Action:** Submit the request again to rerun the report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-54001: The cache group item is not found in the cache system.**

**Cause:** An internal error occurred.

**Action:** Submit the request again without use cache. There is no tolerance in the command line or URL.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-54002: The cache item is no longer valid.**

**Cause:** The cache item might have been cleaned up by the cache system due to resource constraints.

**Action:** Submit the request again to rerun the report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-54003: The syntax for the value of the time argument {0} is invalid.**

**Cause:** The syntax for the time argument is incorrect.

**Action:** Refer to the Oracle Reports documentation for the correct syntax of the time argument.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-54004: No cache directory is specified.**

**Cause:** There is no cache directory specified in the server configuration file.

---

**Action:** Specify a cache directory in the server configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-54005: The cache directory {0} does not exist.**

**Cause:** The specified cache directory does not exist.

**Action:** Create a cache directory before starting Reports Server.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-54006: The cache directory {0} cannot be created.**

**Cause:** Unable to create a cache directory.

**Action:** Ensure write permission and enough disk space for the cache directory.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-54007: The cacheSize value specified {0} is invalid.**

**Cause:** The cacheSize value specified is not valid.

**Action:** Correct the cacheSize value in the server config file and start the server.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-55005: An engine access violation occurred.**

**Cause:** An incorrect key to access the engine object was provided.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-55006: An attempt to load {0} failed.**

**Cause:** Failed to load the specified dynamic library.

**Action:** Verify that the dynamic library exists in PATH on NT or LD\_LIBRARY\_PATH on UNIX.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-55008: The report cannot be created. The command line is: {0}.**

**Cause:** An attempt to create a report in the engine specified on the command line failed.

---

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-55009: The Report Engine failed to start. Port {0} specified in the server config file may be already in use.**

**Cause:** The ORB port specified in the config file is not available for the Reports Engine.

**Action:** Specify a free port.

**Level:** 1

**Type:** ERROR

**Impact:** Ports

**REP-55010: An incorrect value is specified for the ORBPorts element.**

**Cause:** The ORB port specified is not in valid format.

**Action:** Specify a proper integer value for the ORBPorts element.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-55100: The urlparameter not specified for the job.**

**Cause:** The URL to be downloaded is not specified in the command line.

**Action:** Specify the URL in the command line using urlparameter.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-55101: A timeout occurred in accessing the URL {0}.**

**Cause:** The engine cannot access the URLstream.

**Action:** Check if the URL is accessible. If the engine is running behind a firewall, specify the necessary proxy settings in the server configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Performance

**REP-55102: An error occurred setting the proxy information.**

**Cause:** Proxy settings could not be set.

**Action:** Check if the proxy settings file is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-55103: API {0} is not applicable to the URL engine.**

**Cause:** The API used is not applicable to the URL engine.

---

**Action:** Verify the API used.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-55105: The distribution failed. Verify the distribution list.**

**Cause:** The distribution file may be invalid.

**Action:** Ensure that the XML distribution file conforms to the DTD.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-55106: The DESTYPE value is invalid.**

**Cause:** The destination type (DESTYPE) value is null.

**Action:** Specify a valid destination type (DESTYPE): FILE, PRINTER, MAIL, or CACHE.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56000: Cluster {0} cannot be joined.**

**Cause:** The Reports Server cluster was not joined because other Reports Servers could not be found.

**Action:** Verify that this machine can see other Reports Servers. Use osfind to check for other Reports Server on the network.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56001: LocationService cannot be found.**

**Cause:** Unable to locate VisiBroker's LocationService.

**Action:** This should not happen with VisiBroker 4.5. Report this problem to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56003: References for LocationService cannot be resolved.**

**Cause:** References for VisiBroker's LocationService could not be resolved.

**Action:** This should not happen with VisiBroker 4.5. Report this problem to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-56014: The arguments for function call {0} are invalid.**

**Cause:** The arguments for the specified function call were invalid.

**Action:** Refer to jasmine.idl for the function arguments.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56017: Security violation: access to job output not allowed.**

**Cause:** An attempt was made to access job output by a non-owner.

**Action:** This is security violation, and should not be attempted.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**REP-56022: Engine {0} cannot be launched due to {1}.**

**Cause:** The specified engine could not be launched for the stated reason.

**Action:** Fix the problem described in the message, and restart Reports Server.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56027: An internal error occurred: Engine registration failed.**

**Cause:** An internal error occurred when registering the engine to Reports Server.

**Action:** Contact Oracle Support Services if problem persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-56030: The initial engine number must be between minengine ({0}) and maxengine ({1}).**

**Cause:** The value of initEngine is not between the minEngine and maxEngine values specified in the server configuration file.

**Action:** Change the value of initEngine, minEngine, or maxEngine so that minEngine <= initEngine <= maxEngine.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56033: Job {0} does not exist.**

**Cause:** The requested job does not exist.

**Action:** Specify a valid ID of a job that exists in the Reports Server.

**Level:** 1

**Type:** ERROR

**Impact:** Other



---

**REP-56034: A job that is in current or scheduled queue cannot be resubmitted.**

**Cause:** An attempt was made to resubmit a job that is in the current or scheduled job queue.

**Action:** Kill or cancel the job in the current or scheduled queue, then resubmit it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56035: Connection object cannot be accessed.**

**Cause:** The client did not provide the correct key to access the connection object in Reports Server.

**Action:** This should not happen; ensure that the connection attempt is legitimate.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56036: The job has been scheduled successfully.**

**Cause:** This is a notification generated when a job has been scheduled successfully.

**Action:** This is a job submission status. No action is needed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56040: Server {0} already exists in the network.**

**Cause:** Another Reports Server in the network has the same name.

**Action:** Specify a different name for this Reports Server.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56041: Proxy server for the Reports 6i client cannot be started.**

**Cause:** A failure occurred when attempting to start the proxy server that is used for the Reports 6i client.

**Action:** Verify that the Reports Server name is defined in tnsnames.ora.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56042: This function is not supported.**

**Cause:** The invoked function is not supported.

**Action:** Do not use this function.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**REP-56043: No securityUserId is specified in the server configuration file.**

**Cause:** The securityUserId property is missing from the security element specification in the server configuration file.

**Action:** Add the securityUserId property to the security element in the server configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**REP-56044: Parameter {0} has invalid value {1}.**

**Cause:** The specified parameter has an incorrect value.

**Action:** Refer to the Oracle Reports documentation for the correct parameter value syntax and type.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56045: No Oracle Home is specified.**

**Cause:** No Oracle Home is specified in the Reports Server running environment.

**Action:** Verify that the ORACLE\_HOME environment variable is set in the environment where Reports Server runs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56046: No method {0} is defined in class {1}.**

**Cause:** No method is defined in the specified Java class.

**Action:** Add the method into the Java class.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56048: Engine {0} crashed.**

**Cause:** Reports Server detected that the specified engine crashed.

**Action:** Reports Server should restart another engine. Report the problem to Oracle Support Services with the testcase that caused the engine crash.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56049: No portalUserId is specified in the server configuration file.**

**Cause:** The portalUserId property is missing from the destination element for destype=oraclePortal in the server configuration file.

---

**Action:** Add the portalUserId property to the destination element in the server configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**REP-56050: Persistent file {0} in invalid or corrupted.**

**Cause:** An attempt to read the Reports Server persistent file failed.

**Action:** Delete the Reports Server persistent file &lt;server\_name&gt;.dat in ORACLE\_HOME/reports/server.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56051: The connection to server {0} failed.**

**Cause:** The specified server in the same cluster may be down or not ready.

**Action:** Verify that the server is up and ready.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56052: The connection to server {0} is dropped.**

**Cause:** The specified server in the same cluster has been shut down.

**Action:** This is for information only, no action is needed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56053: Cluster server {0} has been registered.**

**Cause:** The specified server in the same cluster has been registered.

**Action:** This is for information only, no action is needed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56054: A connection to server {0} is established.**

**Cause:** The new Reports Server has connected to the specified Reports Server to form a cluster.

**Action:** This is for information only, no action is needed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56055: The max connections allowed ({0}) is exceeded.**

**Cause:** There are more concurrent connection attempts than the server is allowed.

---

**Action:** Increase the value of the maxConnect attribute of the connection element in the server configuration file if desired.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56062: The repositoryConn property is missing from jobStatusRepository.**

**Cause:** The repositoryConn property is missing from the jobStatusRepository element specification in the server configuration file.

**Action:** Add the repositoryConn property to the jobStatusRepository element in the server configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56066: PL/SQL error {0} occurred when inserting job information into the database.**

**Cause:** The indicated PL/SQL error occurred when inserting job information into the database.

**Action:** Check the PL/SQL error manual for the appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56067: PL/SQL error {0} occurred when removing job information from the database.**

**Cause:** The indicated PL/SQL error occurred when removing job information from the database.

**Action:** Check the PL/SQL error manual for the appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56068: PL/SQL error {0} occurred when cleaning job information from the database.**

**Cause:** The indicated PL/SQL error occurred when cleaning information from the database.

**Action:** Check the PL/SQL error manual for the appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56069: An internal error occurred: No cache item for job {0}.**

**Cause:** No cache item associated with the specified job was found.

**Action:** Resubmit the job.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56070: Error message for error {0} cannot be retrieved.**

**Cause:** An attempt to retrieve the error message for the specified error code failed.

**Action:** Report the problem to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56071: A security check failed with error message {0}.**

**Cause:** A security check failed due to the stated reason.

**Action:** Verify the privileges to run the report.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**REP-56072: The administrator password in the secure server cannot be changed.**

**Cause:** An attempt was made to change the Oracle Reports administrator password in secure mode.

**Action:** Use Oracle Portal to change the Oracle Reports administrator password.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56073: The password is invalid.**

**Cause:** An attempt was made to change the Oracle Reports administrator password, but the old password provided was incorrect.

**Action:** Provide the correct old password.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56074: Additional privileges are required to perform the operation.**

**Cause:** An attempt was made to perform an operation for which the user does not have privileges.

**Action:** Only an Oracle Reports administrator can perform this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56075: The job cannot be reordered if not in the current queue.**

**Cause:** An attempt was made to reorder the job in the past or scheduled job queue.

---

**Action:** Reordering jobs can only be done in the current job queue.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56079: The Oracle Portal module status cannot be updated.**

**Cause:** An attempt to update the Oracle Portal module status failed.

**Action:** Report the problem to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56081: The minEngine value ({0}) must be smaller than maxEngine ({1}).**

**Cause:** The value of minEngine is larger than maxEngine in the server configuration file.

**Action:** Change the value of minEngine or maxEngine so that minEngine <= maxEngine.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56082: The maxEngine value must be larger than minEngine ({0}) and initEngine ({1}).**

**Cause:** The value of maxEngine is smaller than the values of minEngine and initEngine specified in the server configuration file.

**Action:** Change the value of initEngine, minEngine, or maxEngine so that minEngine <= initEngine <= maxEngine.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56083: The Oracle Portal folder for job {0} cannot be created.**

**Cause:** An attempt to create an Oracle Portal folder for job output failed.

**Action:** Verify permission to create the folder.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56084: The Oracle Portal folder has been created for job {0}.**

**Cause:** This is a notification message that the Oracle Portal folder has been created.

**Action:** This is for information only, no action is needed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-56085: The engineId {0} is invalid.**

**Cause:** An invalid engineId attribute for the job element is specified in the server configuration file.

**Action:** Check the engineId attribute in the server configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56091: Job {0} is redirected to engine {1} on server {2}.**

**Cause:** This a notification message that the specified job has been transferred to another server's engine.

**Action:** This is for information only, no action is needed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56092: No class is defined for destination type {0}.**

**Cause:** The class attribute is missing for the destination element in the server configuration file.

**Action:** Specify the java class name for the destination element in the reports server configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56093: Cached output for job {0} is no longer valid.**

**Cause:** The cached output has been deleted and no longer valid for use.

**Action:** Rerun the report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56095: Job {0} is waiting for the Oracle Portal folder to be created.**

**Cause:** This a notification message that the specified job is waiting for the Oracle Portal folder to be created.

**Action:** This is for information only, no action is needed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56096: Registration of the remote server is rejected because it does not participate in the cluster**

**Cause:** Another Reports Server tried to register to this Reports Server, but this server does not participate in the cluster.

**Action:** This is for information only, no action is needed.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56097: Engine {0} callback timeout is reached.**

**Cause:** The Reports engine callback timeout value was reached.

**Action:** Increase the value of the callbackTimeOut attribute for the engine element in the server configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Performance

**REP-56098: Engine name {0} is invalid.**

**Cause:** The engine name provided to the Reports Server is invalid.

**Action:** Report the problem to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56099: The specified jobtype {0} is not supported.**

**Cause:** The jobtype provided to the Reports Server is invalid.

**Action:** Check the server configuration file to see what jobtypes are supported.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56100: No engine is defined for jobtype {0}.**

**Cause:** No engine is defined for specified jobtype in the server configuration file.

**Action:** Define an engine for the specified jobtype in the server configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56101: Reports Server cannot be shut down remotely when running in process mode.**

**Cause:** An attempt was made to shut down Reports Server remotely when running in process mode.

**Action:** Shut down the process in which Reports Server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**REP-56102: The proxy server has terminated unexpectedly.**

**Cause:** The proxy server terminated unexpectedly.

**Action:** Check whether the Reports Server tnsname is included in tnsnames.ora.



---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56103: The proxy server callback has timed out.**

**Cause:** The proxy server has not called back within an expected time.

**Action:** Report the problem to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56104: The pluginParam element {0} is invalid due to {1}.**

**Cause:** An invalid value for the pluginParam element is specified in the server configuration file, most likely the file or URL does not exist.

**Action:** Verify that the file or URL that is specified for the pluginParam element in the server configuration file is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56105: Engine {0} died with error: {1}.**

**Cause:** The specified engine died for the stated reason.

**Action:** Fix the error and restart the server.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56106: Engine {0} is destroyed due to timeout.**

**Cause:** The specified Engine did not call back in the expected time.

**Action:** Increase the value of the callbackTimeout attribute of the engine element in the server configuration file if desired.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56107: The specified environment ID {0} is invalid for Job Type {1} in the command line.**

**Cause:** An invalid ENVID argument is specified in the command line.

**Action:** Specify an ENVID that is already defined in the server configuration file (id attribute of environment element) or define a environment ID in the server configuration file and restart Reports Server.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-56108: No connStr property is defined for workflow notification in the server configuration file.**

**Cause:** The connStr property is not specified for workflow notification in the server configuration file.

**Action:** Specify a valid connStr (in the format of database connection string) for workflow notification in the server configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**REP-56109: Job {0} is terminated due to a connection timeout.**

**Cause:** No activity was detected for the specified job in the timeout period. Either the client has terminated unexpectedly, the client program has hung, or the client program took too long handling other processes.

**Action:** Check client program status, or if needed, increase the idleTimeOut attribute for connection element in the server configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56110: The security repository Oracle Portal cannot be connected.**

**Cause:** An attempt to connect to Oracle Portal failed. Oracle Portal is probably down, or an invalid connection string was specified.

**Action:** Verify that Oracle Portal is up, and the connection string is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**REP-56111: Bad or damaged persist file is backed up as: {0}.**

**Cause:** Reports Server shut down abnormally while writing to the indicated file.

**Action:** Resubmit the lost current and scheduled jobs as information about past, current, and scheduled jobs might be lost. Provide the backed up file when reporting the problem to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56112: Backup of the damaged persist file {0} cannot be created.**

**Cause:** The persist file is damaged. Reports Server encountered an error while creating a backup.

**Action:** Rename the file manually, then restart Reports Server. Resubmit all current and scheduled jobs as information about past, current, and scheduled jobs will be lost.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-56113: The JSP report cannot be resubmitted.**

**Cause:** JSP reports are not stored in the Reports Server persistence cache so they cannot be rerun.

**Action:** Submit a new JSP report to the Reports Server.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56114: The attempt to bind to the naming server failed.**

**Cause:** The naming server may be down.

**Action:** Start the naming server.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56115: Engine {0} does not exist.**

**Cause:** An attempt was made to access or kill an engine that does not exist.

**Action:** Provide the correct engine name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56116: A relative path for desname {0} is not allowed when destype=file.**

**Cause:** A relative path was specified for desname when destype=file, which is not allowed.

**Action:** Specify the absolute path for desname.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56117: JOBTYPETYPE {0} is invalid.**

**Cause:** An invalid JOBTYPETYPE argument was specified in the command line.

**Action:** Correct the JOBTYPETYPE argument and resubmit the job.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56118: The report is aborted upon user request.**

**Cause:** This a notification message that the current job was cancelled.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-56119: An invalid value {0} is specified for attribute {1}.**

**Cause:** The specified value in the server configuration file is invalid for the attribute.

**Action:** Refer to the Publishing Reports to the Web manual for information about the attribute and valid values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56120: A syntax error exists on the command line for the Reports Server.**

**Cause:** The syntax for one or more arguments on the command line is invalid.

**Action:** Refer to the Publishing Reports to the Web manual for correct command-line argument syntax.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56121: Authentication failed.**

**Cause:** The AUTHID specified was invalid.

**Action:** Specify a correct AUTHID.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**REP-56122: Reports Server {0} cannot be connected.**

**Cause:** An attempt to connect to Reports Server failed.

**Action:** Verify that Reports Server is running and that the Reports Server name is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56123: An insufficient number of ports is assigned for Reports Server and engines in the config file.**

**Cause:** The number of ports assigned is less than the number required to start server and engines.

**Action:** Increase the number of ORB ports in the server configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Ports

**REP-56124: Report Server failed to start; port {0} specified in the server config file may already be in use.**

**Cause:** The ORB port specified in the server configuration file is not available for the Reports Server.

**Action:** Specify a free port.

---

**Level:** 1

**Type:** ERROR

**Impact:** Ports

**REP-56125: The ORBPorts property value in the config file is invalid.**

**Cause:** The ORB port specified in the server configuration file is not in a valid format.

**Action:** Specify proper integer values for ORB ports either as a range (4000-6000), or comma separated values (4000,5000,6000).

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56126: The server config file {0} cannot be parsed. {1}.**

**Cause:** An attempt to parse the server config file failed due to invalid XML syntax.

**Action:** Correct the server configuration file and start the Reports Server.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56127: The {0} element cannot be decrypted.**

**Cause:** An attempt to decrypt the indicated element failed.

**Action:** Verify that the encrypted property is set properly for the element in the server configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56128: The {0} destination cannot be initialized. Nested exception: {1}.**

**Cause:** An attempt to initialize the indicated destination failed.

**Action:** Check and correct the destination element in the server configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56129: Permission is denied for {0}.**

**Cause:** An attempt to run the report failed due to lack of permissions.

**Action:** Change the parameter values or contact the Oracle Reports administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56130: Permission to run Web command {0} is not granted.**

---

**Cause:** An attempt to run the indicated Web command failed due to lack of permissions.

**Action:** Contact the Oracle Reports administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56131: Permission to run Web command {0} is not granted.**

**Cause:** An attempt to run the indicated Web command failed due to lack of permissions.

**Action:** Contact the Oracle Reports administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56132: Access is denied to the report definition file.**

**Cause:** An attempt to read the report definition file failed due to lack of permissions.

**Action:** Contact the Oracle Reports administrator to obtain access privileges.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56133: Access is denied to write to the specified location.**

**Cause:** An attempt to write to the folder failed due to lack of permissions.

**Action:** Change the desname location or contact the Oracle Reports administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56134: Server config file cannot be found.**

**Cause:** The server configuration file rwserver.conf was not found.

**Action:** Contact the Oracle Reports administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56135: Reports Server is not started using PCS.**

**Cause:** The Reports Server was not started using PCS in the MAS environment.

**Action:** Start the server using PCS.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-56136: An error occurred retrieving the environment required to spawn the engine.**

**Cause:** An attempt to retrieve needed environment variables failed.

**Action:** Contact the Oracle Reports administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56137: The minEngine value must be smaller than maxEngine {0} and initEngine {1}.**

**Cause:** The value of minEngine is larger than maxEngine and initEngine in the server configuration file.

**Action:** Change the value of initEngine, minEngin, or maxEngine so that minEngine &lt;= initEngine &lt;= maxEngine.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56138: Job {0} has completed execution.**

**Cause:** An attempt was made to kill a job that was running or scheduled.

**Action:** Check the job status. Only jobs that are running or scheduled can be killed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-56139: The requested operation is unauthorized.**

**Cause:** An attempt to perform an operation failed due to lack of proper authorization.

**Action:** Contact the Oracle Reports administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-57000: An internal error occurred in the Oracle Reports API:**

**Cause:** An internal error occurred.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-57001: The in-process server is not initialized.**

**Cause:** An internal error occurred.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

---

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-57002: An attempt to load {0} failed.**

**Cause:** An internal error occurred.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-57003: A column data type {0} is not valid.**

**Cause:** A column in the report contains an unsupported data type.

**Action:** Use only supported datatypes. Refer to the Oracle Reports documentation for supported datatypes.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-57004: The value of column {0} cannot be retrieved, cursor out of range in cache.**

**Cause:** An internal error occurred.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-57005: The value of column {0} cannot be retrieved in cache.**

**Cause:** An internal error occurred.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-57052: An internal error occurred in the in-process server.**

**Cause:** An internal error occurred.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-58000: Attribute value {0} for attribute name {1} in tag {2} is invalid.**

**Cause:** The value of the attribute for the JSP tag is invalid.

**Action:** Verify that the attribute value is valid. Refer to the [Reference](#)&gt;Oracle Reports JSP tags section of the Oracle Reports online Help.

**Level:** 1



---

**Type:** ERROR

**Impact:** Other

**REP-58001: Either tag attribute {0} or {1} must exist in tag {2}.**

**Cause:** One of the specified two optional attributes must exist.

**Action:** Specify at least one of the two attributes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-58002: A cursor for group {0} cannot be created.**

**Cause:** A cursor object cannot be created for a group in an rw:foreach or an rw:graph tag.

**Action:** Verify that the group name is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-58004: Format trigger {0} cannot be run.**

**Cause:** Failed to run a PL/SQL format trigger in an rw:field tag.

**Action:** Verify that the name of the format trigger is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-58005: There is no current report for group {0}.**

**Cause:** There is no report object for the rw:foreach tag.

**Action:** Verify that a report object is created by enclosing the report block inside the rw:report tag.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-58006: There is no current report for layout object {0}.**

**Cause:** There is no report object for the rw:include tag.

**Action:** Verify that a report object is created by enclosing the report block inside the rw:report tag.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-58008: There is no current report for column {0}.**

**Cause:** There is no report object for the rw:field or rw:getValue tags.

**Action:** Verify that a report object is created by enclosing the report block inside the rw:report tag.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-58009: A cursor containing column {0} cannot be found.**

**Cause:** The column does not belong to any of the enclosing cursors.

**Action:** Verify that the column name is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-58010: Data type {0} is not supported.**

**Cause:** Invalid dataType attribute (NOT USED CURRENTLY) in rw:getValue.

**Action:** Use any of the supported data types.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-58011: ID {0} in {1} tag is used in a previous {2} tag.**

**Cause:** The value for the ID attribute is not unique.

**Action:** Use a unique ID value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-58012: Only one rw:report tag is allowed in a JSP report.**

**Cause:** There is more than one rw:report tag in the JSP report.

**Action:** Verify that there is only one rw:report tag in the JSP report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-58013: Only one rw:objects tag is allowed in a JSP report.**

**Cause:** More than one rw:objects tags exists in the JSP report.

**Action:** Verify that there is only one rw:objects tag in the JSP report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-58014: rw:objects must be the first JSP tag in rw:report body.**

**Cause:** A JSP tag other than rw:object is the first Reports JSP tag in the body of the rw:report tag.

**Action:** Verify that there is only one rw:objects tag in the body of the rw:report tag. The rw:objects tag must be the first Reports JSP tag inside the body of the rw:report tag.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-58015: breakLevel {0} in the rw:field tag does not match the ID of any enclosing rw:foreach.**

**Cause:** The value of a breakLevel attribute from an rw:field tag does not match the ID of any enclosing rw:foreach tags.

**Action:** Verify that the value for the breakLevel attribute is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-58016: The formatMask {0} attribute is not valid.**

**Cause:** The value of a formatMask attribute from an rw:field or an rw:getValue tag is invalid.

**Action:** Verify that the value for the formatMask attribute is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-58017: FormatTrigger {0} in rw:field tag is not a valid PL/SQL program unit.**

**Cause:** The value of the formatTrigger attribute from an rw:field tag is not a program unit name, or it has an invalid signature.

**Action:** Verify that the value for the formatTrigger attribute is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-58018: Column name {0} in {1} of rw:graph is not valid.**

**Cause:** A column name specified in one of the attributes of the rw:graph tag is not valid.

**Action:** Verify that the column name is valid. Refer to the [Reference&gt;Oracle Reports JSP tags](#) section of the Oracle Reports online Help for the correct syntax of the attributes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-58019: Tag {0} (ID {1}) is not in rw:report body.**

**Cause:** A Reports JSP tag is not in a rw:report tag's body.

**Action:** Add the tag in a rw:report body.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-58100: An error occurred starting the internal Web server at port {0}. Error: {1}.**

**Cause:** Errors occurred while starting the internal Web server.

**Action:** Verify that the port is not in use. Also check the .log files and log directory under (docroot)/port# for more information. Unless specified from the command line, the docroot should be located at under \$REPORTS\_TMP/docroot.

**Level:** 1

**Type:** ERROR

**Impact:** Ports

**REP-58101: An error occurred stopping the internal Web server: {0}.**

**Cause:** Errors were encountered while stopping the internal Web server.

**Action:** Check the .log files and config directory under (docroot)/port# for more information. Unless specified on the command line, the docroot is located in the \$REPORTS\_TMP/docroot directory.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-58102: An error occurred sending request {0} to the internal Web server: {1}.**

**Cause:** Errors were encountered when sending the JSP to the internal Web server.

**Action:** Check the .log files and the log directory under (docroot)/port# for more information. Unless specified on the command line, the docroot is located in the \$REPORTS\_TMP/docroot directory.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**REP-58103: An error occurred configuring the internal Web server: {0}.**

**Cause:** Errors were encountered when configuring the configuration files from the internal Web server.

**Action:** Check the .log files and config directory under (docroot)/port# for more information. Unless specified on the command line, the docroot is located in the \$REPORTS\_TMP/docroot directory.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-58104: Port {0} is in use.**

**Cause:** The port specified from the command line is in use.

**Action:** Specify a different port, or allow Reports to choose a free port.

**Level:** 1

**Type:** ERROR

**Impact:** Ports

**REP-58105: A free port within the {0} to {1} range cannot be automatically found for the internal Web server.**

---

**Cause:** All ports within the range appear to be in use.  
**Action:** Specify a free port to use from the command line.

**Level:** 1

**Type:** ERROR

**Impact:** Ports

**REP-58106: Begin port {0} must be less than end port {1}.**

**Cause:** The begin port is greater or equal to end port.

**Action:** Specify a begin port less than end port from the command line.

**Level:** 1

**Type:** ERROR

**Impact:** Ports

**REP-58107: Port numbers must be within range 1-65536.**

**Cause:** The port used is not within the specified range.

**Action:** Specify a free port in the specified range from the command line.

**Level:** 1

**Type:** ERROR

**Impact:** Ports

**REP-58108: HTML tags are not allowed: {0}.**

**Cause:** HTML tags were specified in the query string.

**Action:** Remove the HTML tags in the query string and rerun the report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-58109: Web server cannot be created.**

**Cause:** A problem was encountered while attempting to create the Web server.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-60003: An error occurred retrieving the environment required to spawn the engine.**

**Cause:** Reports Server was unable to retrieve the current environment setting prevailing on the system.

**Action:** Ensure that `rwu90.dll` is installed and available in the system path on Windows. On UNIX, ensure that `librwu90.so` is installed and available in the `LD_LIBRARY_PATH` environment variable.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-62000: Connection class {0} cannot be loaded.**

**Cause:** The connection class mentioned in the configuration file jdbcpds.conf for the selected driver is invalid.

**Action:** Ensure that a valid driver connection class is specified in the configuration file jdbcpds.conf and that it is available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-62001: No entry is present for the driver {0} in the jdbcpds.conf file.**

**Cause:** The driver used in query is not specified in the configuration file jdbcpds.conf.

**Action:** Ensure that the entry for the required driver along with the related driver information is specified in the configuration file jdbcpds.conf.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**REP-62002: The data source cannot be connected.**

**Cause:** The connection information is invalid.

**Action:** Ensure that the username, password, database, and driver type are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-62003: Configuration file jdbcpds.conf cannot be found.**

**Cause:** The configuration file jdbcpds.conf is not found in the reports/conf directory.

**Action:** Ensure that the configuration file jdbcpds.conf is available in the reports/conf directory.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**REP-62004: A parsing error occurred in the configuration file jdbcpds.conf. Number of errors: {0}**

**Cause:** The XML section in the configuration file jdbcpds.conf does not conform with its inline DTD.

**Action:** Ensure that the XML section in jdbcpds.conf refers to the correct inline DTD.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**REP-62005: An error occurred on line number {0}.**

---

**Cause:** An error was found on the specified line of the configuration file jdbcpds.conf.

**Action:** Correct the error on the specified line.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-62006: The lexical parameter {0} used in the query is invalid.**

**Cause:** The lexical parameter used in the query or procedure is invalid.

**Action:** Ensure that the query or procedure uses valid lexical parameters. Create new parameters if they are not available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-62007: A SQL error occurred: {0}.**

**Cause:** The data source has reported this SQL syntax error in the specified query or procedure.

**Action:** Ensure that the syntax of the query or procedure is valid. Refer to the documentation of the specific data source.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-62008: The query or procedure for the specified data source is invalid.**

**Cause:** The syntax of the query or procedure is invalid for the specified data source.

**Action:** Ensure that the syntax of the query or procedure is valid. Refer to the documentation of the specific data source.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-62009: The reference parameter value is invalid.**

**Cause:** The value of the reference parameter is invalid.

**Action:** Verify that the reference column types and values are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-62010: A query or procedure is missing.**

**Cause:** The query or procedure text field is empty.

**Action:** Type a valid query or procedure in the text area.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-62011: The database URL {0} is invalid.**

**Cause:** Invalid database URL.

**Action:** Verify the specified database name and the selected driver type.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-62012: Either the number of columns or the types of columns does not match the query definition.**

**Cause:** The data fetched does not match the number of columns or the column types that are specified in the query definition.

**Action:** Verify that both the number of columns and the column types match the query definition.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-62013: The column type {0} used in the query/procedure is not supported by the Reports JDBC query.**

**Cause:** This column type is not supported by the Reports JDBC query interface.

**Action:** Ensure that only column types that are supported by the Reports JDBC query interface are used. Refer to the JDBC specification and the Reports documentation for supported types.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-62014: The inline DTD section of the configuration file jdbcpds.conf has been modified.**

**Cause:** The format of the inline DTD section in the configuration file jdbcpds.conf has been altered.

**Action:** If the DTD format is modified, ensure that the configuration file is valid as per the JDBCPSDS requirement.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**REP-62015: The sign-on parameter {0} is invalid.**

**Cause:** The specified sign-on parameter for the query or procedure is invalid.

**Action:** Ensure that the sign-on parameter is available and valid for the JDBC query type in the report.

**Level:** 1

**Type:** ERROR



---

**Impact:** Other

**REP-62016: The sign-on parameter value {0} is invalid.**

**Cause:** The specified connect string for this sign-on parameter is invalid.

**Action:** Ensure that the specified connect string for this sign-on parameter is valid for the selected driver.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-62017: A reference parameter of type Date is not supported by the JDBC driver used.**

**Cause:** The driver used to connect to database does not support the Date data type as reference parameter.

**Action:** Use the String data type for the reference parameter or use a different JDBC driver that supports the Date data type as reference parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-62200: No image exists for the specified ID {0}**

**Cause:** The image ID specified does not map to an existing image object in the store.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-62201: The image source is invalid**

**Cause:** The image source is not valid.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-62202: Unsupported image format**

**Cause:** The format of the image used is not supported.

**Action:** Ensure that the report uses a supported image format as specified in the Oracle Reports documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-62203: Internal error reading the image {0}**

**Cause:** The image data appears to be corrupt or invalid.

---

**Action:** Ensure that the image is valid. For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-62204: Internal error writing the image {0}**

**Cause:** There was an internal error writing the image to the output stream.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-62205: Internal error during color reduction**

**Cause:** An error occurred doing color reduction on GIF images.

**Action:** Use a different GIF image with lesser colors or chose another image format.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-62206: The input image used is corrupt or invalid**

**Cause:** The image data appears to be corrupt or invalid.

**Action:** Ensure that the image is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-62207: Encountered an unsupported version of GIF image**

**Cause:** This GIF version is not supported.

**Action:** Ensure that the GIF images used adhere to the standards specified in the Oracle Reports documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-62350: URL {0} is invalid.**

**Cause:** The location pointed to by the URL appears to be invalid.

**Action:** Ensure that the location pointed to by the URL is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-62351: The proxy setting specified in proxyinfo.xml will be not be effective.**

**Cause:** The proxy setting was ignored due to an invalid configuration in the proxyinfo.xml file.

---

**Action:** Ensure that the proxy setting in proxyinfo.xml is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-62352: The FTP proxy server specified is not responding : {0}.**

**Cause:** The proxy specified in the proxyinfo.xml file does not support SOCKS protocol.

**Action:** Ensure that the proxy supports SOCKS protocol.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-62353: The destination file name is missing.**

**Cause:** Destination file name missing in the desname argument.

**Action:** Specify a valid destination file name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-62354: The directory specified is invalid.**

**Cause:** Invalid directory is specified in the desname argument.

**Action:** Specify a valid directory path.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-62370: URL {0} is invalid.**

**Cause:** The location pointed to by the URL appears to be invalid.

**Action:** Ensure that the location pointed by the URL is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-62371: The proxy setting specified in proxyinfo.xml is not be effective.**

**Cause:** The proxy setting was ignored due to an invalid configuration in the proxyinfo.xml file.

**Action:** Ensure that the proxy setting in proxyinfo.xml is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-63000: No URL specified for {0}**

**Cause:** There was no URL specified for either the data definition or the data source.

---

**Action:** Specify a URL for both the data definition and the data source.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-63001: Invalid stream in the Data Definition URL {0}**

**Cause:** The Data Stream pointed to by the URL appears to be invalid.

**Action:** Ensure that the XML Stream pointed to by the URL is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-63002: URL specified has an invalid XML stream: {0}**

**Cause:** The URL appears to have invalid XML stream.

**Action:** Ensure that the XML stream pointed to by the URL contains valid XML.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-63003: URL {0} read error**

**Cause:** Could not access the specified URL. A timeout occurred while accessing the URL.

**Action:** Ensure that the URL is accessible and check that the proxy information in the xmlpds.conf file is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-63004: Generic error while parsing the URL stream {0}**

**Cause:** The data stream pointed to by the URL appears to be invalid.

**Action:** Ensure that the XML stream pointed to by the URL is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-63005: The Inline DTD section of xmlpds.conf file has been modified**

**Cause:** The Inline DTD section of the configuration file xmlpds.conf has been modified.

**Action:** Ensure that the configuration file is still valid, per the XMLPDS requirement.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**REP-63006: Invalid reference parameter value**

---

**Cause:** The value of the reference parameter is invalid.

**Action:** Verify that the types and values of the referenced columns are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-63007: Configuration file xmlpds.conf not found**

**Cause:** The configuration file xmlpds.conf was not found in the reports/conf directory.

**Action:** Ensure that the configuration file xmlpds.conf is located in the reports/conf directory.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**REP-63008: Parsing error in the xmlpds.conf configuration file Number of errors: {0}**

**Cause:** The XML section in the xmlpds.conf file does not conform with the corresponding inline DTD.

**Action:** Ensure the XML section in the xmlpds.conf file conforms with the corresponding inline DTD.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**REP-63009: The proxy setting specified in xmlpds.conf will be not be effective**

**Cause:** The proxy setting was ignored due to an invalid configuration in the xmlpds.conf file.

**Action:** Ensure that the proxy setting in the configuration file xmlpds.conf is correctly specified.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**REP-63500: No URL is specified for data source {0}/**

**Cause:** There was no URL specified for the data source.

**Action:** Specify a URL for the data source.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-63501: The specified URL {0} is not compatible with the file format {1} at line number {2}.**

**Cause:** The URL appears to have invalid content.

**Action:** Ensure that the content pointed to by the URL is a valid file format.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**REP-63502: The data is invalid.**

**Cause:** Content is not compatible with the file format selected.

**Action:** Ensure that the text is valid for the file format selected.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-63503: Either the number of columns or the type of columns does not match the query definition.**

**Cause:** The data fetched does not match the number of columns or the column types that are specified in the query definition.

**Action:** Verify that both the number of columns and the column types match the query definition.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-63504: A read error occurred in accessing URL {0}.**

**Cause:** Could not access the specified URL. A timeout occurred while accessing the URL.

**Action:** Ensure that the URL is accessible and check that the proxy information in the textpds.conf file is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-63505: The Inline DTD section of textpds.conf has been modified.**

**Cause:** The Inline DTD section of the configuration file textpds.conf has been modified.

**Action:** Ensure that the configuration file is still valid, per the TextPDS requirement.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**REP-63506: The reference parameter is invalid.**

**Cause:** The reference parameter is invalid.

**Action:** Verify that the name, types, and values of the referenced columns are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**REP-63507: The configuration file textpds.conf cannot be found.**

**Cause:** The configuration file textpds.conf was not found in the reports/conf directory.

**Action:** Ensure that the configuration file textpds.conf is located in the reports/conf directory.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**REP-63508: A parsing error occurred in textpds.conf. Number of errors: {0}.**

**Cause:** The XML section in the textpds.conf file does not conform with the corresponding inline DTD.

**Action:** Ensure the XML section in the textpds.conf file conforms with the corresponding inline DTD.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-63509: The proxy setting specified in textpds.conf is invalid.**

**Cause:** The proxy setting was ignored due to an invalid configuration in the textpds.conf file.

**Action:** Ensure that the proxy setting in the configuration file textpds.conf is correctly specified.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**REP-63510: No fileFormat is specified in textpds.conf.**

**Cause:** The entry for fileFormat in textpds.conf is missing.

**Action:** Ensure that at least one fileFormat element is specified in the textpds.conf.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-63511: The fileFormat specification is invalid.**

**Cause:** The entry for fileFormat in textpds.conf is invalid.

**Action:** Ensure that fileFormat is specified per the DTD of textpds.conf.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-63512: No entry is present for fileFormat {0} in textpds.conf.**

**Cause:** The fileFormat used in the query is not defined in textpds.conf.

**Action:** Ensure that the entry for the required fileFormat along with the column information is specified in textpds.conf.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-63513: The Serialized XML section of the saved report is invalid.**

**Cause:** The Serialized XML section has been modified.

**Action:** Ensure that Serialized XML section is specified per the TextPDS format.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-63514: The column type {0} used in the query is not supported by a Text query.**

**Cause:** This column type is not supported by the Text query interface.

**Action:** Ensure that only column types that are supported by the Text query interface are used. Refer to the TextPDS specification and the Oracle Reports documentation for supported types.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-63515: The data in log file {0} is not according to the date pattern {1} specified in the config file.**

**Cause:** The data in the log file is not valid according to the date pattern specified in the config file.

**Action:** Ensure that data in the log file is specified according to the date pattern.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**REP-64000: No Oracle Home is specified.**

**Cause:** ORACLE\_HOME is missing in the command line.

**Action:** Specify ORACLE\_HOME=&lt;oracle\_home\_dir&gt; in the command line.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-64001: The Oracle Reports Bridge failed to start.**

**Cause:** The Oracle Reports Bridge failed to start.

**Action:** Check log file for detailed message and take appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-64002: The Oracle Reports Bridge initialization failed {0}.**

**Cause:** The Oracle Reports Bridge initialization failed.



---

**Action:** Check the actual message and take appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-64003: The local port is not set. One-way Oracle Reports Bridge is started.**

**Cause:** One-way Oracle Reports Bridge is started.

**Action:** No action needed. Set local port to start two-way bridge if needed.

**Level:** 1

**Type:** ERROR

**Impact:** Ports

**REP-64004: AUTHID is not specified.**

**Cause:** AUTHID argument is not specified in command line.

**Action:** Specify AUTHID=&lt;username&gt;/&lt;password&gt; in the command line.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**REP-64005: Authentication failed.**

**Cause:** The AUTHID specified was invalid.

**Action:** Specify a correct AUTHID.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**REP-64006: The Oracle Reports Bridge shutdown failed.**

**Cause:** An attempt to shut down The Oracle Reports Bridge failed.

**Action:** Check the trace for detailed message and take appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-64009: The Oracle Reports Bridge is already running.**

**Cause:** Another Oracle Reports Bridge is already running with the same port.

**Action:** Change the port in the config file and start again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-64010: The local listener failed to start.**

**Cause:** The open socket could not be opened.

**Action:** Check socket is available and usable.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-64011: Request {0} cannot be served.**

**Cause:** Unable to serve the Oracle Reports Bridge request.

**Action:** Check the actual message and take appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**REP-64012: A fatal error {0} occurred. Restart the Oracle Reports Bridge.**

**Cause:** The Oracle Reports Bridge is not able to serve any request.

**Action:** Restart the Oracle Reports Bridge.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-64013: The Oracle Reports Bridge failed to serve the request {0}.**

**Cause:** An internal error occurred.

**Action:** Check the actual message; the Oracle Reports Bridge may recover from this error.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**REP-64014: The Oracle Reports Bridge name is not specified.**

**Cause:** The NAME=&lt;bridgename&gt; argument is missing in the command line.

**Action:** Specify NAME=&lt;bridgename&gt; in the command line.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-64015: The command is invalid.**

**Cause:** Invalid command-line argument.

**Action:** Check command-line arguments.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-64016: Cannot connect to the Oracle Reports Bridge {0}.**

**Cause:** The Oracle Reports Bridge is not running on specified port.

**Action:** The Oracle Reports Bridge may be down. Or check the Bridge port in Bridge config file and try again.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-64017: The Oracle Reports Bridge config file is not found.**

**Cause:** Configuration file rwbridge.conf is not found.

**Action:** Contact the Oracle Reports administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-64018: The Oracle Reports Bridge is not started using PCS.**

**Cause:** The Oracle Reports Bridge is not started using PCS in the MAS environment.

**Action:** Start the Oracle Reports Bridge using PCS.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-65001: Communication error {0} occurred.**

**Cause:** A network IO error occurred.

**Action:** Check the actual message and take appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-65002: The communication channel {0} cannot be initialized.**

**Cause:** Multicast initialization failed.

**Action:** Check the actual message and take appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-65003: The request timed out.**

**Cause:** Waiting for a response from the server timed out.

**Action:** No action required. If all retries fail, increase the timeout value in the network config file.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**REP-65004: The naming server cannot be bound.**

**Cause:** Naming service may be down.

**Action:** Start the naming service and try again.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-65005: The network config file cannot be found.**

**Cause:** rwnetwork.conf is not found.

**Action:** Contact the Oracle Reports administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**REP-80001: An internal error occurred.**

**Cause:** Unexpected internal exception.

**Action:** For assistance, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**REP-80002: The report object is invalid.**

**Cause:** The report object is invalid, possibly invalid object handle, or an already deleted object.

**Action:** Discard this object handle and get a new one.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-80003: The report object name is invalid.**

**Cause:** The name does not follow report object naming rules; for example, it may contain an invalid character.

**Action:** Follow the report object naming rules to create a valid name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-80004: A dialog window not allowed at this time.**

**Cause:** The Plugin tried to display a dialog window when it is not allowed; for example, when Reports is running in batch mode.

**Action:** Plugin must not raise a dialog window when it is not allowed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-80005: The dialog window location is invalid.**

**Cause:** The requested dialog window location is invalid.

**Action:** Set a valid dialog window location.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-80006: The dialog window size is invalid.**

**Cause:** The requested dialog window size is invalid.

**Action:** Set a valid dialog window size.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-80007: The help system cannot be displayed.**

**Cause:** Failure to display online help.

**Action:** Check the online help system setup.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-80008: The helpset ID is invalid.**

**Cause:** Invalid helpset ID.

**Action:** Correct the helpset ID.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-80009: The help topic is invalid.**

**Cause:** The help topic is invalid.

**Action:** Correct the help topic.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-80010: The trace file cannot be written to.**

**Cause:** Fail to write to trace file.

**Action:** Check the trace file setup, file write permission, and whether the disk is full.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-80011: Sign-on parameter {0} for {1} cannot be set.**

**Cause:** The column is not a valid sign-on parameter of this plugin type.

**Action:** Use the Property Palette to set this column as a sign-on parameter of this plugin type.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**REP-80012: The link between two columns of mismatched datatypes is invalid.**

**Cause:** The column link is formed between two columns of different data types.

**Action:** Ensure the link is formed between the columns whose datatypes are compatible.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

## RUL-00000 to RUL-09043

**RUL-00000: internal error during typechecking "{5}" {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An internal error occurred during type checking.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-00001: invalid assignment target {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An invalid target of an assignment expression was encountered.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00002: operator "+" accepts only numeric and String operands {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** One of the operands of an addition expression was of an incorrect type.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00003: operator "{5}" accepts only boolean and fact set operands {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** One of the operands of a boolean expression was of an incorrect type.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**RUL-00004: operator "{5}" accepts only numeric operands {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** One of the operands of a numeric expression was of an incorrect type.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00005: operator "{5}" accepts only integer operands {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An operator that only accepts integer operands had an operand that was not an integer.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00006: operator "{5}" accepts only String, numeric, boolean, or Object operands {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** A comparison expression contained an operand of an incorrect type.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00007: operator "{5}" accepts only numeric, String, or Comparable operands {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** A comparison expression contained an operand of an incorrect type.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00008: operator "exists" accepts only fact set operands {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** The operand of an exists operator was an incorrect type.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR



---

**Impact:** Programmatic

**RUL-00009: operator "instanceof" accepts only Object operands {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** The operand of an instanceof operator was an incorrect type.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00010: cannot convert from type "{5}" to type "{6}" {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An RL expression contained an implicit conversion from one type to another and that implicit conversion was not possible.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00011: wrong number of arguments in function or method invocation {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An RL function or a Java method invocation was coded with an incorrect number of arguments.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00012: wrong argument type in function or method invocation {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An argument in an RL function or a Java method invocation was an incorrect type.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00013: nested arrays are not supported {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** RL code was written to use nested arrays.

**Action:** RL does not support nested arrays. Rewrite the offending RL code.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**RUL-00014: this rule has only {5,number,integer} logical support expressions {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** The logical rule property was assigned a value that was greater than the number of supporting expressions in the rule condition.

**Action:** Correct the value assigned to the logical property.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00015: cannot use "{5}" in a rule condition {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An RL construct that is not valid in a rule condition was encountered in a rule condition.

**Action:** Correct the offending rule condition.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00016: cannot use "{5}" outside a rule condition {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An RL construct that is only valid in a rule condition was encountered outside of a rule condition.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00017: a fact pattern cannot contain an expression {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** A fact pattern contained an expression.

**Action:** Correct the offending RL code by moving the expression to a test following the fact pattern.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00018: a fact pattern cannot contain the "new" operator {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An fact pattern contained a new operator.

---

**Action:** Correct the offending RL code by removing the new operator.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00019: a fact pattern cannot contain a function or method call {0}**  
{1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column  
{2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}

**Cause:** A fact pattern contained a function or method invocation.

**Action:** Correct the offending RL code by moving the invocation to a test following the pattern.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00020: symbol "{5}" is undefined {0}** {1,choice,0#|0<at line {1,number,integer}}  
{2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in  
{4}}

**Cause:** An undefined RL program element was encountered.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00021: symbol "{5}" is not public {0}** {1,choice,0#|0<at line {1,number,integer}}  
{2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in  
{4}}

**Cause:** An RL program element that was not public was referenced and therefore was not accessible.

**Action:** If the program element is a Java class, ensure that the class has been imported or is referenced with its fully qualified name, and that it is present in the classpath. If the program element is a Java method, a Java field, an RL function, or an RL function variable, ensure that it has been declared to be public.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00022: fact class for "{5}" should be declared earlier in rule session {0}**  
{1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column  
{2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}

**Cause:** A fact class for the offending class needed to be declared earlier in the rule session. Typically a super class was encountered in a fact context (fact class statement, rule condition, assert, retract, modify) after one or more of its subclasses has appeared in a fact context.

**Action:** Add or move a fact class statement for the class to an earlier position in the RL code.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**RUL-00023: fact class should be declared earlier** {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}

**Cause:** A fact class for the offending class needed to be declared earlier in the rule session. Typically a super class was encountered in a fact context (fact class statement, rule condition, assert, retract, modify) after one or more of its subclasses has appeared in a fact context.

**Action:** Add or move a fact class statement for the class to an earlier position in the RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00024: fact class "{5}" cannot extend both "{6}" and "{7}"** {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}

**Cause:** Fact class multiple inheritance was detected.

**Action:** Correct the offending RL code to restrict to single inheritance.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00025: fact class multiple inheritance not supported** {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}

**Cause:** Fact class multiple inheritance was detected.

**Action:** Correct the offending RL code to restrict to single inheritance.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00026: exception in invoked Java method** {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}

**Cause:** A Java method invoked from RL threw an exception.

**Action:** Investigate the root cause of the exception thrown by the Java method. It is available as the cause of the exception thrown with this message.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00027: symbol "{5}" is defined more than once** {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}

**Cause:** A RL program element was defined more than once.

---

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00030:** class "{5}" has no member named "{6}" {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}

**Cause:** An attempt to access a nonexistent member of a class was detected.

**Action:** Correct the offending reference.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00031:** class "{5}" has no static member named "{6}" {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}

**Cause:** An attempt to access a nonexistent static member of a class was detected.

**Action:** Correct the offending reference.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00032:** class "{5}" has no public member named "{6}" {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}

**Cause:** An attempt was made to access a member of a class that is not public.

**Action:** Remove the offending reference or make the member public.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00033:** fully qualified package or class name is required {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}

**Cause:** An import statement did not contain a fully qualified class name.

**Action:** Correct the import statement.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00034:** Invalid action encountered {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}

**Cause:** An invalid RL action was encountered.

**Action:** Correct the RL code.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00040:** encountered "{5}" when expecting {6} {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}

**Cause:** An unexpected program element was encountered.

**Action:** Correct the RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00041:** encountered "{5}" when expecting one of: {6} {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}

**Cause:** An unexpected program element was encountered.

**Action:** Correct the RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00042:** XML identifier "{5}" is invalid {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}

**Cause:** An invalid XML identifier was encountered.

**Action:** Correct the RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00043:** cannot use both "property" and "hide property" {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}

**Cause:** A fact class statement contained both property and hide property clauses. Only one of them may be specified.

**Action:** Correct the RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00044:** class "{6}" cannot extend final class "{5}" {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}

**Cause:** An RL class was declared to extend a second RL class which was declared to be final.

**Action:** Correct the RL code.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00045: cannot hide exposed property "{5}" {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An attempt was made to hide a property of class when that property has already been exposed. For example, an attempt to hide a property of a super class.

**Action:** Correct the RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00046: cannot expose hidden property "{5}" {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An attempt was made to expose a property of class when that property has already been hidden. For example, an attempt to expose a property of a super class which has a fact class statement that hid that property.

**Action:** Correct the RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00050: error invoking property getter when asserting fact {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An `IllegalArgumentException` was thrown when getting property. This exception is the available as the root cause exception in the exception created with this message.

**Action:** Inspect root cause exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00051: error defining property "{5}" {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An `RLIllegalArgumentException` was thrown when defining a property. This exception is the available as the root cause exception in the exception created with this message.

**Action:** Inspect root cause exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**RUL-00052: object cannot be null {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An attempt was made to dereference a null object reference.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00054: ruleset stack is empty {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An attempt was made to get a ruleset from the top of the ruleset stack when the stack was empty.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00055: ruleset "{5}" is already on the ruleset stack {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An attempt was made to push a ruleset onto the top of the ruleset stack when the same ruleset was already on the top of the stack .

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00056: ruleset "{5}" is undefined {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** A reference was made to an ruleset that was undefined.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00057: package "{5}" is undefined {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** A reference was made to an undefined package.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic



---

**RUL-00058: cannot convert xpath test type "{5}" to "{6}" {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An error in an XPATH test was detected.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00059: xpath test operator "{5}" is not supported {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An unsupported XPATH operator was encountered.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00060: xpath test constant "{5}" is not supported {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An unsupported XPATH literal was encountered.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00061: xpath "/" is not supported {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** XPATH '/' was encountered but is not supported by RL.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00062: xpath cannot begin with "{5}" {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** The XPATH cannot start with the offending text.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**RUL-00063: bad xpath syntax "{5}" {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An XPATH syntax error was encountered.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00064: property "{5}" is undefined {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An undefined property was encountered in an XPATH.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00065: property "{5}" must be public in a class that supports xpath {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** A nonpublic property was encountered in an XPATH.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00067: missing XML identifier {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An XML identifier was expected.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00068: unexpected "@" in XML name {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An unexpected '@' character was encountered in an XML name.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**RUL-00069: unexpected "/" in XML name {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An unexpected '/' character was encountered in an XML name.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00070: array index "{5,number,integer}" is out of bounds {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An attempt was made to index into an array with an index that was outside the bounds of the array.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00071: array size cannot be negative {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An attempt was made to create an array with a negative size.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00072: array element type mismatch {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An attempt was made to store the wrong type of object in an array.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00073: cannot store object of type "{5}" in array of type "{6}" {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An attempt was made to store the wrong type of object in an array.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**RUL-00074: RL object is not an array** {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}

**Cause:** An attempt was made to use an object as an array and the object was not an array.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00075: subscript must be applied to an array** {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}

**Cause:** An array reference was missing an index.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00076: subscript must be an integer type** {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}

**Cause:** A nonintegral array index was encountered.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00077: An invalid value of "{5}" is assigned to the rule property 'logical'. The value must be greater than 0.** {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}

**Cause:** A non-positive value was assigned to the logical rule property.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00080: class "{5}" does not support cloning** {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}

**Cause:** An attempt was made to clone an object whose class does not support cloning.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**RUL-00081:** cannot cast to class "{5}" {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}

**Cause:** An attempt was made to cast an object to a class to which it cannot be cast.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00082:** illegal argument "{5}" passed to "{6}" {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}

**Cause:** An illegal argument was passed to an RL function or Java method.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00083:** RL class "{5}" cannot extend a Java class {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}

**Cause:** An RL class was defined to extend a Java class which is not supported.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00084:** cannot find constructor for class "{5}" {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}

**Cause:** An applicable constructor for the class could not be found.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00085:** cannot include "{5}" because {6} {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}

**Cause:** An error occurred in an include statement.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**RUL-00086: missing return value from function {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** A function was defined to return a value but it did not contain a return statement.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00087: "return" must be used in a function or a rule action {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** A return statement was encountered in an invalid location.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00088: "catch" or "finally" must be specified {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** A try statement did not have at least one of a catch or finally clause.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00089: error: {5} {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** A divide by 0 was detected.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00090: internal error: {5} {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An internal rules engine error was encountered.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

---

**RUL-00091: The aggregate {5} was not an implementation of {6}. {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** The aggregate was did not implement the required interface.

**Action:** Correct the aggregate implementation or change the RL code to reference a correct aggregate function.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00092: The argument of aggregate function in the fact path is wrong. The argument should be association name or property of an association. {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** The argument of aggregate function in the fact path was wrong.

**Action:** The argument should be association name or property of an association.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00093: invalid boolean expression in FactPath {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** An invalid boolean expression was encountered in a FactPath.

**Action:** Correct the offending RL code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00094: The association "{6}" defined in "{5}" is reverse association, but it is corresponding to a forward reference. {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0< column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** The association in a Reverse Association was not a forward reference.

**Action:** Change the association to forward reference.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00095: Invocation of the executeRuleset method on a RuleSession obtained from a pool using peer RuleSessions is not allowed.**

**Cause:** This RuleSession was obtained from a pool and the executeRuleset method was invoked. This is not allowed when peer RuleSessions are in use.

**Action:** Eliminate the executeRuleset method invocation or do not use a RuleSession pool.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**RUL-00096: Rule "{5}" defined in rule group "{6}" must contain exactly {7} patterns.**  
{0} {1,choice,0# | 0<at line {1,number,integer}} {2,choice,0# | 0< column {2,number,integer}} {1,choice,0# | 0< } {3,choice,0# | 0<in {4}}

**Cause:** The specified rule was in a rule group with the mutex property set to true and the rule had an incorrect number of patterns (fact clauses).

**Action:** Change the rule to have the correct number of patterns.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00097: Rule "{5}" defined in rule group "{6}" has a fact clause of type "{7}" when type "{8}" is required.** {0} {1,choice,0# | 0<at line {1,number,integer}} {2,choice,0# | 0< column {2,number,integer}} {1,choice,0# | 0< } {3,choice,0# | 0<in {4}}

**Cause:** The specified rule was in a rule group with the mutex property set to true. All rules in a mutex group must have the same fact clauses with the same fact types in the same order. This rule contained a fact clause that did not match the expected fact type.

**Action:** Change the rule to specify the correct fact types in the same order as other rules in the rule group.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00098: The loop property of "{5}" did not match the loop property of the group it was a member of. All members of a rule group must have the same loop property value.** {0} {1,choice,0# | 0<at line {1,number,integer}} {2,choice,0# | 0< column {2,number,integer}} {1,choice,0# | 0< } {3,choice,0# | 0<in {4}}

**Cause:** A member of a rule group had the loop property set to a value that does not match the loop property value for the group. All members of a rule group must have the same loop property value.

**Action:** Change loop property value in either the named group member or the the named group to resolve the conflict.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-00099: The aggregate contained more than one pattern.** {0} {1,choice,0# | 0<at line {1,number,integer}} {2,choice,0# | 0< column {2,number,integer}} {1,choice,0# | 0< } {3,choice,0# | 0<in {4}}

**Cause:** The aggregate contained more than one pattern.

**Action:** Only one pattern is allowed in an aggregate. Change the the RL code to contain a single pattern.

**Level:** 1

**Type:** ERROR



---

**Impact:** Programmatic

**RUL-00100: The aggregate pattern contained an expression that could not be folded into the pattern. {0} {1,choice,0#|0<at line {1,number,integer}} {2,choice,0#|0<column {2,number,integer}} {1,choice,0#|0< } {3,choice,0#|0<in {4}}**

**Cause:** The aggregate pattern contained an expression that could not be folded into the pattern.

**Action:** All expression following the pattern in the aggregate must be folded into the pattern. Some complex tests may not be foldable. Rewrite the expression to simplify it so it may be folded into the pattern.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01001: {0} is not a valid selection with respect to the domain. Ensure sure your selection is in the valid domain.**

**Cause:** The value is not a valid selection with respect to the domain.

**Action:** Provide a valid selection with respect to the domain.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01002: Range constraint has been violated. {0} is not in the range of {1} and {2}. Ensure the value satisfies the range constraint**

**Cause:** Range constraint has been violated. The value is not in the range.

**Action:** Ensure the value satisfies the range constraint

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01003: Unable to add jar file {0} into the data model. Ensure the jar file is in the correct location, is not corrupted, and that all dependent Java classes have been imported into the data model.**

**Cause:** Unable to add jar file into the data model.

**Action:** Ensure the jar file is in the correct location, is not corrupted, and that all dependent Java classes have been imported into the data model.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01004: Unable to deserialize XML to data model. Ensure the XML element is well-formed and conforms to the data model schema.**

**Cause:** Unable to deserialize XML to data model.

**Action:** Ensure the XML element is well-formed and conforms to the data model schema.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**RUL-01005: Unable to serialize data model into XML. See the base exception for resolution.**

**Cause:** Unable to serialize data model into XML.

**Action:** See the base exception for resolution.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01006: Missing the element/attribute {0} in the data model XML document. Ensure the required element is in the data model XML document.**

**Cause:** Missing the element/attribute in the data model XML document.

**Action:** Ensure the required element is in the data model XML document.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01007: The referenced Fact Type {0} is not defined in the data model. Ensure the referenced Fact Type is defined in the data model.**

**Cause:** The referenced Fact Type is not defined in the data model.

**Action:** Ensure the referenced Fact Type is defined in the data model.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01008: The pattern {0} is not a valid regular expression. Provide a valid pattern. Refer to `java.util.regex.Pattern` for more information.**

**Cause:** The pattern is not a valid regular expression.

**Action:** Provide a valid pattern. Refer to `java.util.regex.Pattern` for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01009: The input String {0} does not match the regular expression constraint pattern {1}. Ensure the input String conforms to the given pattern. Refer to `java.util.regex.Pattern` for more information.**

**Cause:** The input String does not match the regular expression constraint pattern.

**Action:** Ensure the input String conforms to the given pattern. Refer to `java.util.regex.Pattern` for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**RUL-01010: Unable to add the new element into the data model. An element with the same name, {0}, is already in the data model. If you wish to replace this existing element, remove it from the data model and then add the new element.**

**Cause:** Unable to add the new element into the data model. An element with the same name is already in the data model.

**Action:** If you wish to replace this existing element, remove it from the data model and then add the new element.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01011: Error while deserializing range constraint. The bounds {0} and {1} are not in the correct format. Ensure the bound values in XML document are in the correct double format, or contact Oracle Support Services.**

**Cause:** Error while deserializing range constraint. The bounds are not in the correct format.

**Action:** Ensure the bound values in XML document are in the correct double format, or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01012: Unable to add JAXB class {0} into the data model. Ensure the class is in class path.**

**Cause:** Unable to add JAXB class into the data model.

**Action:** Ensure the class is in class path.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01013: Unable to add Java class {0} to the data model. Ensure the class and its associated classes, including parent classes and attribute type classes, are on the current class path.**

**Cause:** Unable to add Java class to the data model.

**Action:** Ensure the class and its associated classes, including parent classes and attribute type classes, are on the current class path.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01014: Unable to add XML schema path {0} into data model. See the base exception for resolution.**

**Cause:** Unable to add XML schema path into data model.

**Action:** See the base exception for resolution.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**RUL-01015: The user path {0} is not a directory or zip file. Ensure the user path is either a directory, zip file, or jar file.**

**Cause:** The user path is not a directory or zip file.

**Action:** Ensure the user path is either a directory, zip file, or jar file.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01016: Cannot load Java class {0}. Ensure the class and all its dependent classes are either in the class path, or user specified path.**

**Cause:** Cannot load Java class.

**Action:** Ensure the class and all its dependent classes are either in the class path, or user specified path.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01017: Cannot load Java class. The class name must be valid.**

**Cause:** Cannot load Java class.

**Action:** Provide a valid class name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01018: Cannot load Java class {0}. The class must be inside a package.**

**Cause:** Cannot load Java class.

**Action:** The class must be inside a package.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01019: Cannot reimport Java class {0}. Ensure the class and its associated classes, including parent classes and attribute type classes, are on the current class path. See base exception for detail.**

**Cause:** Cannot reimport Java class.

**Action:** Ensure the class and its associated classes, including parent classes and attribute type classes, are on the current class path. See base exception for detail.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01020: Can not load Java class {0}. The class name contains RL reserved word {1}.**

**Cause:** Cannot load Java class. The class name contains RL reserved word.

---

**Action:** Change the name of the Java class.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01021: Java Class {0} has a field {1} that is a RL reserved word.**

**Cause:** Java Class has a field that is a RL reserved word.

**Action:** Change the name of the field.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01022: Java Class {0} has a property {1} that is a RL reserved word.**

**Cause:** Java Class has a property that is a RL reserved word.

**Action:** Change the name of the property.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01023: Java Class {0} has a method {1} that is a RL reserved word.**

**Cause:** Java Class has a method that is a RL reserved word.

**Action:** Change the name of the method.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01024: Jaxb Output directory is null or an empty string.**

**Cause:** Jaxb Output directory is null or an empty string.

**Action:** Provide a valid output directory.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01025: Jaxb Output directory {0} is not a valid directory.**

**Cause:** Jaxb Output directory is not a valid directory.

**Action:** Provide a valid output directory.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01026: Jaxb Output directory {0} is not writable.**

**Cause:** Jaxb Output directory is not writable.

**Action:** Provide a writable output directory.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01027: Package name is not a valid Java Identifier.**

**Cause:** Package name is not a valid Java Identifier.

**Action:** Provide a valid Java Identifier for the package name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01028: XML Schema name is null or an empty string.**

**Cause:** XML Schema name is null or an empty string.

**Action:** Provide a valid XML Schema name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01029: XML Schema {0} does not exist.**

**Cause:** XML Schema does not exist.

**Action:** Provide an XML Schema that exists.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01030: Time out while importing XML Schema {0}. If you need to access the schema through a proxy server, properly set system properties for proxy server. Refer to document about importing an XML schema.**

**Cause:** Time out while importing XML Schema.

**Action:** If you need to access the schema through a proxy server, properly set system properties for proxy server. Refer to document about importing an XML schema.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01031: There is a circular dependency among variables.**

**Cause:** There is a circular dependency among variables.

**Action:** Resolve the circular dependency.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01032: There is a circular dependency among functions.**

**Cause:** There is a circular dependency among functions.

---

**Action:** Resolve the circular dependency.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01033: There is a circular dependency among RL Facts.**

**Cause:** There are circular dependency among RL Facts.

**Action:** Resolve the circular dependency.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01034: There is a circular dependency among variables and functions.**

**Cause:** There are circular dependency among variables and functions.

**Action:** Resolve the circular dependency.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01035: The value to be validated is null.**

**Cause:** The value to be validated is null.

**Action:** Provide a valid value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01101: Unable to serialize the ruleset into XML. See base exception for resolution.**

**Cause:** Unable to serialize the ruleset into XML.

**Action:** See base exception for resolution.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01102: Unable to deserialize the XML document into a ruleset. See the base exception for resolution.**

**Cause:** Unable to deserialize the XML document into a ruleset.

**Action:** See the base exception for resolution.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01103: Missing the element/attribute {0} in ruleset XML document. Ensure the required element is in the ruleset XML document.**

**Cause:** Missing an element/attribute in ruleset XML document.

---

**Action:** Ensure the required element is in the ruleset XML document.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01104: Unable to load dictionary document(s) from the repository due to version incompatibility. The current code version is \"{0}\", document version is \"{1}\".**

**Cause:** Unable to load dictionary document(s) from the repository due to version incompatibility. The current code version is different than the document version.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01113: Variable {0} is not in scope.**

**Cause:** Variable is not in scope.

**Action:** Specify a variable that is in scope.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01114: Interface {0} not found.**

**Cause:** Interface not found.

**Action:** Specify a valid interface.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01115: Variable {0} is no longer defined in this scope.**

**Cause:** Variable is no longer defined in this scope.

**Action:** Specify an variable that is in scope.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01116: Fact Type {0} is no longer defined.**

**Cause:** Fact Type is no longer defined.

**Action:** Remove references to Fact Type or define Fact Type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01117: Fact Type {0} has no methods named {1}.**

**Cause:** Fact Type has no methods with that name.



---

**Action:** Specify a different method.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01118: Method {0} with matching parameter list not found.**

**Cause:** Method with matching parameter list not found.

**Action:** Specify a method that exists.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01119: Expression is already used in a different RuleElement.**

**Cause:** Expression is already used in a different RuleElement.

**Action:** Use a new expression for this RuleElement.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01120: Function {0} is no longer defined.**

**Cause:** Function is no longer defined.

**Action:** Define the function again or specify a different function.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01121: In Call function or method {0}, the number of arguments does not match parameter list.**

**Cause:** In Call function or method, the number of arguments does not match parameter list.

**Action:** Provide a number of arguments that matches the parameter list.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01122: Function {0} requires argument {1}, but this is not in the call argument map.**

**Cause:** Function requires an argument, but this is not in the call argument map.

**Action:** Recreate the call to the function.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01123: Condition must have a pattern expression.**

**Cause:** Condition must have a pattern expression.

---

**Action:** Add a pattern to the condition.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01124: {0} is not a valid modifier.**

**Cause:** The value is not a valid modifier.

**Action:** Provide a valid modifier.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01125: Variable {0} must have an initial value.**

**Cause:** Variable must have an initial value.

**Action:** Provide an initial value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01126: If statement must contain at least one test block.**

**Cause:** "If" statement does contain at least one test block.

**Action:** Provide a test block for the statement.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01127: Else statement must be the last test block.**

**Cause:** "Else" statement is not the last test block.

**Action:** Make the "else" statement the last test block.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01128: Missing object name.**

**Cause:** Missing object name.

**Action:** Provide an object name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01129: Fact Type {0} not found in data model.**

**Cause:** Fact Type not found in data model.

**Action:** Add the Fact Type to the data model or select a different Fact Type.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01130: Fact Type {0} has no public constructors.**

**Cause:** Fact Type has no public constructors.

**Action:** Provide a constructor to the Fact Type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01131: Unable to locate public constructor for {0} with {1} args.**

**Cause:** Unable to locate public constructor for Fact Type with args.

**Action:** Provide a constructor with that number of arguments or use a different constructor

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01132: RL fact constructors must have named parameters.**

**Cause:** RL fact constructors must have named parameters.

**Action:** Recreate the Fact Type or refresh the element.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01133: {0} is not a valid operator.**

**Cause:** The value is not a valid operator.

**Action:** Provide a valid operator.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01134: {0} is not valid for type {1}.**

**Cause:** The value is not valid for the given type.

**Action:** Provide a valid value for this type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01135: OperatorNode cannot be used in multiple expressions.**

**Cause:** OperatorNode cannot be used in multiple expressions.

**Action:** Use the OperatorNode in only one expression.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**RUL-01136: Duplicate pattern variable name.**

**Cause:** More than one pattern contains the same variable name.

**Action:** Change the variable name on one of the patterns.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01137: Retract can only be called within the action block of a Rule.**

**Cause:** Retract can only be called within the action block of a Rule.

**Action:** Remove this retract action from its current location.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01138: Return statement can only be defined in the action block of a rule or in a function.**

**Cause:** Return statement can only be defined in the action block of a rule or in a function.

**Action:** Remove the return statement.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01139: Return statements in rule action blocks cannot return values.**

**Cause:** Return statements in rule action blocks cannot return values.

**Action:** Remove the return value from the return.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01140: RL code generator missing/incorrect for {0}.**

**Cause:** RL code generator missing/incorrect for element.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01141: RuleSet missing name.**

**Cause:** RuleSet missing name.

**Action:** Provide a name for the RuleSet.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**RUL-01142: {0} is a duplicate rule name within this rule set.**

**Cause:** Two rule sets have the same name.

**Action:** Provide a different name for one of the rule sets.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01143: There is no rule named {0} in this rule set.**

**Cause:** There is no rule with the given name in this rule set.

**Action:** Provide a different rule name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01144: Move operation {0} is not valid.**

**Cause:** Move operation is not valid.

**Action:** Do not attempt to use this move operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01201: The passed-in dictionary object is null when saving the dictionary into repository. Make sure the dictionary object was property created.**

**Cause:** The passed-in dictionary object is null when saving the dictionary into repository.

**Action:** Make sure the dictionary object was property created.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01202: Base directory for the dictionary should be given.**

**Cause:** Base directory for the dictionary should be given.

**Action:** Provide the base directory for the dictionary.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01203: Error locating repository root directory {0}. Ensure the repository path is valid and appropriate permission is granted.**

**Cause:** Error locating repository root directory.

**Action:** Ensure the repository path is valid and appropriate permission is granted.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**RUL-01204: Error writing XML document to {0}. Refer to base exception for resolution.**

**Cause:** Error writing XML document.

**Action:** Refer to base exception for resolution.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01205: Error parsing XML document from {0}. Refer to base exception for resolution.**

**Cause:** Error parsing XML document.

**Action:** Refer to base exception for resolution.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01206: The requested dictionary {0} is not in repository. Ensure the dictionary name is correct.**

**Cause:** The requested dictionary is not in repository.

**Action:** Ensure the dictionary name is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01207: Error loading dictionary {0}. Refer to the base exception.**

**Cause:** Error loading dictionary.

**Action:** Refer to the base exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01208: Error saving dictionary {0}. Check write permission for the repository directory. Refer to the base exception.**

**Cause:** Error saving dictionary.

**Action:** Check write permission for the repository directory. Refer to the base exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01209: Error removing dictionary {0}. Refer to the base exception.**

**Cause:** Error removing dictionary.

**Action:** Refer to the base exception.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01210: While deserializing the rule set, the RL function {0} could not be found in the data model. Ensure the function has been defined in data model.**

**Cause:** While deserializing the rule set, the RL function could not be found in the data model.

**Action:** Ensure the function has been defined in data model.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01211: While deserializing the rule set, the Java class {0} could not be found in the data model. Ensure the class has been defined in data model.**

**Cause:** While deserializing the rule set, the Java class could not be found in the data model.

**Action:** Ensure the class has been defined in data model.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01212: While deserializing ruleset, the Java method {0} in class {1} could not be found in the data model. Ensure the method has been defined in data model.**

**Cause:** While deserializing ruleset, the Java method in class could not be found in the data model.

**Action:** Ensure the method has been defined in data model.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01213: Error initializing the repository. Refer to the base exception.**

**Cause:** Error initializing the repository.

**Action:** Refer to the base exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01214: There is a problem with repository connection. Make sure the repository has been initialized correctly.**

**Cause:** There is a problem with repository connection.

**Action:** Make sure the repository has been initialized correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**RUL-01215: Error retrieving dictionary names. Refer to the base exception.**

**Cause:** Error retrieving dictionary names.

**Action:** Refer to the base exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01216: Error saving dictionary {0}. Refer to the base exception.**

**Cause:** Error saving dictionary.

**Action:** Refer to the base exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01217: Unable to remove dictionary {0}. The specified dictionary is not found in repository.**

**Cause:** Unable to remove dictionary. The specified dictionary is not found in repository.

**Action:** Specify a dictionary that exists in the repository.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01218: Error closing the repository. Refer to the base exception.**

**Cause:** Error closing the repository.

**Action:** Refer to the base exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01219: Dictionary {0} is not found in repository.**

**Cause:** Dictionary is not found in repository.

**Action:** Provide the name of a dictionary in the repository.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01220: Unable to mark dictionary {0}. Refer to the base exception.**

**Cause:** Unable to mark dictionary.

**Action:** Refer to the base exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic



---

**RUL-01221: Unable to list versions for dictionary {0}. Refer to the base exception.**

**Cause:** Unable to list versions for dictionary.

**Action:** Refer to the base exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01222: Unable to load dictionary {0}. Refer to the base exception.**

**Cause:** Unable to load dictionary.

**Action:** Refer to the base exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01223: Unable to load dictionary {0} version {1}. Refer to the base exception.**

**Cause:** Unable to load dictionary version.

**Action:** Refer to the base exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01224: Dictionary {0} version {1} is not found in repository.**

**Cause:** Dictionary version is not found in repository.

**Action:** Select a version of the dictionary that exists.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01225: Error removing dictionary {0} version {1}. Refer to the base exception.**

**Cause:** Error removing dictionary version.

**Action:** Refer to the base exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01226: The file path passed to function exportDictionary() is null.**

**Cause:** The file path passed to function exportDictionary() is null.

**Action:** Provide a non-null file path.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01227: Unable to export dictionary {0}. Refer to the base exception.**

**Cause:** Unable to export dictionary.

---

**Action:** Refer to the base exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01228: Unable to export dictionary {0} version {1}. Refer to the base exception.**

**Cause:** Unable to export dictionary version.

**Action:** Refer to the base exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01229: The file path passed to function importDictionary() is null.**

**Cause:** The file path passed to function importDictionary() is null.

**Action:** Provide a non-null file path.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01230: Unable to import the file {0}. Refer to the base exception.**

**Cause:** Unable to import the file.

**Action:** Refer to the base exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01231: Version {0} exists in repository.**

**Cause:** Version exists in repository.

**Action:** Provide a different version for the dictionary or remove it from the repository first.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01232: The dictionary to be saved does not have a name or the name is an empty string.**

**Cause:** The dictionary to be saved does not have a name or the name is an empty string.

**Action:** Provide a valid name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01233: The file path {0} is not a valid path leading to a file.**

**Cause:** The file path is not a valid path leading to a file.

---

**Action:** Provide a valid path that leads to a file.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01234: A dictionary with name {0} and version name {1} already exists in repository. Note dictionary and version names are case insensitive.**

**Cause:** A dictionary with the same name and version already exists in repository.

**Action:** Provide a name and version that do not exist. Note dictionary and version names are case insensitive.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01235: The dictionary to be saved does not have a version name or the version name is an empty string.**

**Cause:** The dictionary to be saved does not have a version name or the version name is an empty string.

**Action:** Provide a valid version name for the dictionary before saving.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01236: Unable to load the dictionary. It does not have a name or the name is an empty string.**

**Cause:** Unable to load the dictionary. It does not have a name or the name is an empty string.

**Action:** Provide a valid name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01237: Unable to load the dictionary. It does not have a version name or the version name is an empty string.**

**Cause:** Unable to load the dictionary. It does not have a version name or the version name is an empty string.

**Action:** Provide a valid version name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01238: Unable to remove the dictionary. The dictionary name is null or an empty string.**

**Cause:** Unable to remove the dictionary. The dictionary name is null or an empty string.

**Action:** Provide a valid dictionary name.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01239: Unable to remove the dictionary. The dictionary version name is null or an empty string.**

**Cause:** Unable to remove the dictionary. The dictionary version name is null or an empty string.

**Action:** Provide a valid dictionary version name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01240: Unable to export the dictionary. The dictionary name is null or an empty string.**

**Cause:** Unable to export the dictionary. The dictionary name is null or an empty string.

**Action:** Provide a valid dictionary name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01241: Unable to export the dictionary. The dictionary version name is null or an empty string.**

**Cause:** Unable to export the dictionary. The dictionary version name is null or an empty string.

**Action:** Provide a valid dictionary version name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01242: Unable to mark the dictionary. The new version name is null or an empty string.**

**Cause:** Unable to mark the dictionary. The new version name is null or an empty string.

**Action:** Provide a valid version name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01243: Unable to mark the dictionary. The dictionary name is null or an empty string.**

**Cause:** Unable to mark the dictionary. The dictionary name is null or an empty string.

**Action:** Provide a valid name.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**RUL-01244: Unable to mark the dictionary. The current version name is null or an empty string.**

**Cause:** Unable to mark the dictionary. The current version name is null or an empty string.

**Action:** Provide a valid version name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01245: Unable to get version names for the dictionary. The dictionary name is null or an empty string.**

**Cause:** Unable to get version names for the dictionary. The dictionary name is null or an empty string.

**Action:** Provide a valid name for the dictionary.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01246: Unable to get description for dictionary {0}.**

**Cause:** Unable to get description for dictionary.

**Action:** XYZ

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01247: Unable to get description for dictionary {0} version {1}.**

**Cause:** Unable to get description for dictionary version.

**Action:** XYZ

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01248: Unable to set description for dictionary {0}.**

**Cause:** Unable to set description for dictionary.

**Action:** XYZ

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01249: Unable to set description for dictionary {0} version {1}.**

**Cause:** Unable to set description for dictionary version.

**Action:** XYZ

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01250: While creating a rule repository instance, the parameter is null.**

**Cause:** While creating a rule repository instance, the parameter is null.

**Action:** Provide a non-null parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01251: The specified dictionary {0} version {1} does not exist in repository.**

**Cause:** The specified dictionary version does not exist in repository.

**Action:** Provide a dictionary version that exists in the repository.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01252: Unable to load 10.1.3.0.0 dictionary {0} using 10.1.3SOA code base. The dictionary might need to be fixed manually.**

**Cause:** Unable to load 10.1.3.0.0 dictionary using 10.1.3SOA code base.

**Action:** The dictionary might need to be fixed manually. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01253: Unable to load 10.1.3.0.0 dictionary {0} version {1} using 10.1.3SOA code base. The dictionary might need to be fixed manually.**

**Cause:** Unable to load 10.1.3.0.0 dictionary version using 10.1.3SOA code base.

**Action:** The dictionary might need to be fixed manually. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01301: The ruleset with name {0} already exists in the dictionary. Use a different name for the ruleset.**

**Cause:** The ruleset with name already exists in the dictionary.

**Action:** Use a different name for the ruleset.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01302: There is no data model defined for the ruleset {0}. Set a data model first before creating the ruleset.**

---

**Cause:** There is no data model defined for the ruleset.

**Action:** Set a data model first before creating the ruleset.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01303: The ruleset with the same name {0} is already in dictionary. If you want to replace the existing ruleset, remove it from dictionary first.**

**Cause:** The ruleset with the same name is already in dictionary.

**Action:** If you want to replace the existing ruleset, remove it from dictionary first.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01304: The ruleset with the name {0} is not in dictionary.**

**Cause:** The ruleset with the name is not in dictionary.

**Action:** Specify a ruleset name that exists in the dictionary.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01305: An OptionSet {0} already exists. Either remove the existing OptionSet from the dictionary, or change the name of the OptionSet being added.**

**Cause:** An OptionSet with the same name already exists.

**Action:** Either remove the existing OptionSet from the dictionary, or change the name of the OptionSet being added.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01306: The data model added to the dictionary is null. Ensure the data model is a valid object.**

**Cause:** The data model added to the dictionary is null.

**Action:** Ensure the data model is a valid object.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01307: The dictionary name is either null or an empty string. Ensure the dictionary is valid.**

**Cause:** The dictionary name is either null or an empty string.

**Action:** Ensure the dictionary is valid.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**RUL-01401: The path specified: {0} does not exist. Ensure the path exists on the host system.**

**Cause:** The path specified does not exist.

**Action:** Ensure the path exists on the host system.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01402: The dictionary specified was null or is invalid. Ensure that the constructor for RuleObjectHelper is passed a valid Dictionary.**

**Cause:** The dictionary specified was null or is invalid.

**Action:** Ensure that the constructor for RuleObjectHelper is passed a valid Dictionary.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01403: The parameter is null. Ensure that the parameter is not null.**

**Cause:** The parameter is null.

**Action:** Ensure that the parameter is not null.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01404: The Fact Type {0} was not located.**

**Cause:** The Fact Type was not located.

**Action:** Ensure the Fact Type exists or select a different name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01405: Could not parse name {0} for type {1}.**

**Cause:** Could not parse name for type.

**Action:** Choose another name for the type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01406: Unable to locate bound pattern for {0} member: {1}.**

**Cause:** Unable to locate bound pattern for member.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR



---

**Impact:** Programmatic

**RUL-01407: getObject failed to locate Fact Type for {0}.**  
**Cause:** getObject failed to locate specified Fact Type.  
**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01408: getObject failed to locate Method for {0} {1}.**  
**Cause:** getObject failed to locate Method.  
**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01409: Could not parse mapper name {0} for {1}.**  
**Cause:** Could not parse mapper name for element.  
**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01410: Failed to locate Method of name {0} and type: {1}.**  
**Cause:** Failed to locate Method.  
**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01411: Failed to locate Field {0} {1}.**  
**Cause:** Failed to locate Field.  
**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01412: Failed to lookup {0} named {1}.**  
**Cause:** Failed to lookup element.  
**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01413: Unknown getObject {0} of type {1} at {2}.**

---

**Cause:** Unknown getObject.  
**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01414: Extended type information missing for {0} when retrieving type for {1}.**

**Cause:** Extended type information missing when retrieving type.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01415: getTable failed: {0}.**

**Cause:** getTable failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01416: sub map {0} not located: {1}.**

**Cause:** Sub map not located.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01417: Missing parameter name at {0} fails with: {1}.**

**Cause:** Missing parameter name.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01418: Parameter at {0} did not have valid expression, {1}.**

**Cause:** Parameter does not have valid expression.

**Action:** Provide a valid expression for the parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01419: convertTableParm received exception from sdk: {0}**

**Cause:** convertTableParm received exception from sdk.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01420: Get raw table failed: {0}.**

**Cause:** Get raw table failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01421: An advanced expression is missing the sub map.**

**Cause:** An advanced expression is missing the sub map.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01422: The map field ADV\_BODY was not located for an expression, may be wrong type of expression.**

**Cause:** The map field ADV\_BODY was not located for an expression, may be wrong type of expression.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01423: The map field ADV\_OPERAND is missing. Internal error.**

**Cause:** The map field ADV\_OPERAND is missing. Internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01424: The map field ADV\_OPERAND true name is missing. Internal error.**

**Cause:** The map field ADV\_OPERAND true name is missing. Internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01425: The map field ADV\_FUNCTION is missing. Internal error.**

**Cause:** The map field ADV\_FUNCTION is missing. Internal error.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01426: The map field ADV\_FUNCTION true name is missing. Internal error.**

**Cause:** The map field ADV\_FUNCTION true name is missing. Internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01427: An indentifier {0} was not located attempting to parse: {1}.**

**Cause:** An indentifier was not located attempting to parse.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01428: The expression is invalid and had {0} tokens.**

**Cause:** The expression is invalid.

**Action:** Correct the expression to be valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01429: SDK Exception was received {0} {1}**

**Cause:** SDK Exception was received.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01430: Unknown instance type in an advanced expression {0}**

**Cause:** Unknown instance type in an advanced expression

**Action:** Provide a valid advanced expression.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01431: Update for Map field {0} failed with: {1}**

**Cause:** Update for Map field failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Programmatic

**RUL-01432: In routine {0} null return from addOperator conjunction for {1} root.**

**Cause:** In routine null return from addOperator conjunction for root.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01433: An illegal expression table, contains no conjunctions, but more than one entry. Conjunctions must be used to join multiple entries.**

**Cause:** An illegal expression table, contains no conjunctions, but more than one entry.

**Action:** Add conjunctions to join multiple entries.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01434: An illegal expression table, two operands require an operator. Select operator to apply to the operands.**

**Cause:** An illegal expression table, two operands require an operator.

**Action:** Select operator to apply to the operands.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01435: Expected expression table, field {0} is not a table**

**Cause:** Expected expression table, field is not a table

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01436: Failed to parse expression in row {0}.**

**Cause:** Failed to parse expression in row.

**Action:** Provide a valid expression in this row.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01437: Test Expression at {0} is missing a conjunction.**

**Cause:** Test Expression at is missing a conjunction.

**Action:** Specify a conjunction for this test expression.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**RUL-01438: Test Expression at {0} is missing operands.**

**Cause:** Test Expression is missing operands.

**Action:** Specify operands for this test expression.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01439: Test Expression at {0} is missing operator.**

**Cause:** Test Expression is missing operator.

**Action:** Specify a valid operator for this test expression.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01440: Test Expression at {0} has an invalid operator: {1} and received exception: {2}.**

**Cause:** Test Expression has an invalid operator.

**Action:** Specify a valid operator for this test expression.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01441: Test Expression at {0} has more operands than the operator allows.**

**Cause:** Test Expression has more operands than the operator will allow.

**Action:** Specify the correct number of operands.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01442: Test Expression at {0} has no operator and two operands.**

**Cause:** Test Expression has no operator and two operands.

**Action:** Provide a valid operator for the two operands.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01443: Unable to build expression for {0} return code: {1}**

**Cause:** Unable to build expression for return code.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

---

**RUL-01444: Failed to get field {0} returns {1}.**

**Cause:** Failed to get field.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01445: Name was null or empty cannot be retrieved**

**Cause:** Name was null or empty and cannot be retrieved.

**Action:** Provide a valid name to retrieve.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01446: {0} is not a valid identifier. Modify this to be valid RL identifier.**

**Cause:** Value is not a valid identifier.

**Action:** Modify this to be valid RL identifier.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01447: Failed to create the Action statements during Rule update.**

**Cause:** Failed to create the Action statements during Rule update.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01448: Assert at [{0}] parameter list could not be built, returns {1}.**

**Cause:** Assert in parameter list could not be built.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01449: Unable to parse expression for the Action {1} for number {0}, check error details. Returns {2}**

**Cause:** Unable to parse expression for the Action.

**Action:** Check the error details and provide a valid expression.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01450: Action at [{0}] failed to build parameter list, returns {1}.**

---

**Cause:** Action failed to build parameter list

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01451: Unable to build Assign statement at [0].**

**Cause:** Unable to build Assign statement at [0].

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01452: Unable to build return expression at [{0}], returns{1}.**

**Cause:** Unable to build return expression.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01453: The alias {0} is duplicated in another {1} named {2}. Change one of the aliases. Aliases must be unique within {1} type.**

**Cause:** The alias is duplicated in another component.

**Action:** Change one of the aliases. Aliases must be unique within all components of each component type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01454: Field at [{0}] is not a valid identifier. Change the name to be a valid identifier.**

**Cause:** Field is not a valid identifier.

**Action:** Change the name to be a valid identifier.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01455: Unable to locate Fact Type for field named {0} at [{1}].**

**Cause:** Unable to locate Fact Type for field

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic



---

**RUL-01456: Unknown parameter Fact Type {0} parameter at [{1}].**

**Cause:** Unknown parameter Fact Type parameter.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01457: Exception generated for add of property: {0}.**

**Cause:** Exception generated for add of property.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01458: Duplicate names are not allowed. {0} is used previously for this type.  
Change the name to be unique or delete the pre-existing entity.**

**Cause:** Duplicate names are not allowed. The name is used previously for this type.

**Action:** Change the name to be unique or delete the pre-existing entity.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01459: Exception received for add of Fact: {0}.**

**Cause:** Exception received for add of Fact.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01460: There is no matching Fact Type for {0} at position {1}.**

**Cause:** There is no matching Fact Type.

**Action:** Provide a valid Fact Type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01461: Parameter names must be valid RL identifiers. Parameter at position {0} is not a valid identifier.**

**Cause:** Parameter name is not a valid identifier.

**Action:** Specify a valid RL identifier for the name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**RUL-01462: Failed to delete function, returns {0}.**

**Cause:** Failed to delete function.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01463: Missing function rl statement. Function may be empty but must have a body.**

**Cause:** Function body is entirely empty.

**Action:** Function body does not need to contain RL statements, but must contain more than the empty string.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01464: The block table had an empty statement and was malformed, returns{0}.**

**Cause:** The block table had an empty statement and was malformed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01465: Expected expression to describe the constant. The expression was not located in the map, returns {0}.**

**Cause:** Expected expression to describe the constant. The expression was not located in the map.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01466: Constant must have a an initializing value. Add a value or an expression.**

**Cause:** Constant must have a an initializing value.

**Action:** Add a value or an expression.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01467: Failed to create expression node from advanced expression, returns {0}.**

**Cause:** Failed to create expression node from advanced expression.

**Action:** Contact Oracle Support Services.

**Level:** 1

---

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01468: Missing field {0} in map. This is an internal error {1}.**

**Cause:** Missing field in map. This is an internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01469: Failed to delete previous constant, returns {0}.**

**Cause:** Failed to delete previous constant.

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01470: Invalid range value. Ranges must be valid doubles.**

**Cause:** Invalid range value.

**Action:** Provide a valid range of double values.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01471: Invalid Constraint type: {0}.**

**Cause:** Invalid Constraint type.

**Action:** Specify a valid constraint type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01472: Could not locate {0} named {1} in dictionary.**

**Cause:** Could not locate component in dictionary.

**Action:** Specify the name of a component that exists in the dictionary.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01473: Duplicate Rule name {0} in the RuleSet change the name of the new Rule.**

**Cause:** Duplicate Rule name in the RuleSet.

**Action:** Change the name of one of the rules.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**RUL-01474: Duplicate Rule name {0} in the RuleSet, updates may not change the Rule name to that of an existing Rule. Change the Rule name.**

**Cause:** Duplicate Rule name in the RuleSet, updates may not change the Rule name to that of an existing Rule.

**Action:** Change the Rule name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01475: Invalid priority value. Rule priority must be an integer. Modify priority to contain only digits.**

**Cause:** Invalid priority value. Rule priority must be an integer.

**Action:** Modify priority to contain only digits.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01476: The dictionary does not have a data model. Internal error.**

**Cause:** The dictionary does not have a data model.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01477: Pattern table, failed to add null root at [{0}].**

**Cause:** Pattern table, failed to add null root.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01478: Failed on return from test in build pattern Test Expression for pattern {0}, return {1}.**

**Cause:** Failed on return from test in build pattern Test Expression for pattern.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01479: Pattern table {0} could not be located in the map, returns {1}.**

**Cause:** Pattern table could not be located in the map.

**Action:** Contact Oracle Support Services.

**Level:** 1

---

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01480: Pattern instance name at [{0}] is not valid. Pattern instance names must be valid rl names.**

**Cause:** Pattern instance name is not valid.

**Action:** Specify valid RL names for the pattern instance names.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01481: Pattern instance name {0} at [{1}] is a duplicate of Pattern instance name at [{2}]. Pattern instance names must be unique.**

**Cause:** Pattern instance name is a duplicate of Pattern instance name.

**Action:** Specify pattern instance names that are unique.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01482: Pattern instance name {0} at [{1}] is missing a conjunction. Patterns must be joined by conjunctions.**

**Cause:** Pattern instance name is missing a conjunction.

**Action:** Specify conjunctions between each pattern.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01483: Failed to build Pattern expression.**

**Cause:** Failed to build Pattern expression.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01484: Table {0} get length failed with {1}.**

**Cause:** Table get length failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01485: Failed while working on Statement Table, returns{0}.**

**Cause:** Failed while working on Statement Table.

**Action:** Contact Oracle Support Services.

**Level:** 1

---

**Type:** INCIDENT\_ERROR  
**Impact:** Programmatic  
**RUL-01486: Failed to parse Statement for row {0}, returns{1}.**  
**Cause:** Failed to parse Statement.  
**Action:** Contact Oracle Support Services.  
**Level:** 1  
**Type:** INCIDENT\_ERROR  
**Impact:** Programmatic  
**RUL-01487: Failed to parse a variable type name {0}, returns {1}.**  
**Cause:** Failed to parse a variable type name.  
**Action:** Contact Oracle Support Services.  
**Level:** 1  
**Type:** INCIDENT\_ERROR  
**Impact:** Programmatic  
**RUL-01488: vartype is null for var name: {0}.**  
**Cause:** vartype is null for var name.  
**Action:** Contact Oracle Support Services.  
**Level:** 1  
**Type:** INCIDENT\_ERROR  
**Impact:** Programmatic  
**RUL-01489: Invalid object type for {0}.**  
**Cause:** Invalid object type.  
**Action:** Contact Oracle Support Services.  
**Level:** 1  
**Type:** INCIDENT\_ERROR  
**Impact:** Programmatic  
**RUL-01490: Edit point {0} is not within the expression.**  
**Cause:** Edit point is not within the expression.  
**Action:** Set edit point to be within the expression.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic  
**RUL-01491: ADV\_TYPE selection is missing from the expression map, returns{0}.**  
**Cause:** ADV\_TYPE selection is missing from the expression map.  
**Action:** Contact Oracle Support Services.  
**Level:** 1  
**Type:** INCIDENT\_ERROR  
**Impact:** Programmatic

---

**RUL-01492: Failed to create the parameter mask for inserted function, returns{0}.**

**Cause:** Failed to create the parameter mask for inserted function.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01493: ADV\_CVALUE is missing from the expression map, returns{0}.**

**Cause:** ADV\_CVALUE is missing from the expression map.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01494: Constraint {0} cannot be retrieved. The Constraint may have been removed.**

**Cause:** Constraint cannot be retrieved. The Constraint may have been removed.

**Action:** Specify a constraint which exists.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01495: Operand {1} had no type and is being ignored.**

**Cause:** Operand had no type and is being ignored.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01496: Possible error, Constraint choice list has no selection.**

**Cause:** Possible error, Constraint choice list has no selection.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01497: For Constraint named: {0}, no Dictionary object could be located. Check to make sure the constraint was not deleted from the dictionary.**

**Cause:** For Constraint, no Dictionary object could be located.

**Action:** Check to make sure the constraint was not deleted from the dictionary.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**RUL-01498: Function type was set, but no Function was selected. Internal error.**

**Cause:** Function type was set, but no Function was selected.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01499: Constraint {0} cannot be retrieved. The Constraint may have been removed.**

**Cause:** Constraint cannot be retrieved. The Constraint may have been removed.

**Action:** Specify a constraint that exists in the datamodel.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01500: Dictionary object for Function operand in row [{0}] could not be located. Ensure function has not been deleted.**

**Cause:** Dictionary object for Function operand in row could not be located.

**Action:** Ensure function has not been deleted.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01501: Object lookup failed for {0}. Internal error returns {1}.**

**Cause:** Object lookup failed for component.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01502: Internal error returns {1}. External type information cannot be parsed**

**Cause:** External type information cannot be parsed

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01503: Function type was set, but no Function was selected. For {0}.**

**Cause:** Function type was set, but no Function was selected.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic



---

**RUL-01504: Dictionary object for Function operand in row [{0}] could not be located, returns{1}. Ensure function has not been deleted.**

**Cause:** Dictionary object for Function operand could not be located.

**Action:** Ensure function has not been deleted.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01505: Type Constant was set and not constant value is present. Enter or select a Constant.**

**Cause:** Type Constant was set and not constant value is present.

**Action:** Enter or select a Constant.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01506: Must select operand for an expression. No selection was located.**

**Cause:** Must select operand for an expression. No selection was located.

**Action:** Specify an operand for the expression.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01507: Failed to determine the type of the Simple {0} operand, type returned null. Internal error.**

**Cause:** Failed to determine the type of the Simple operand, type returned null.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01508: Failed to getObject for {0} at [{1}], returns {2}. Internal Error.**

**Cause:** Failed to getObject.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01509: The operand type {0} does not exist. Internal error, invalid operand type set.**

**Cause:** The operand type does not exist. Internal error, invalid operand type set.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Programmatic

**RUL-01510: Missing constant value, must have a constant. Enter either an rl expression or a literal constant.**

**Cause:** Missing constant value, must have a constant.

**Action:** Enter either an rl expression or a literal constant.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01511: Failed to pass Constraint check for {0}. Exception received: {1}**

**Cause:** Failed to pass Constraint check.

**Action:** Specify values that conform to constraints.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01512: Failed operator add, invalid root exception received {0}**

**Cause:** Failed operator add, invalid root exception received

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01513: Failed to retrieve properties for {0}. Internal Error.**

**Cause:** Failed to retrieve properties.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01514: setRootOperator received an exception {0}. Correct the operator.**

**Cause:** setRootOperator received an exception.

**Action:** Correct the operator.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01515: setRootOperator for an Assign received an exception {0}. Correct the operator.**

**Cause:** setRootOperator for an Assign received an exception.

**Action:** Correct the operator.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**RUL-01516: setRootOperator die Define received an exception {0}**

**Cause:** setRootOperator die Define received an exception.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01517: setRoot could not produce an operator for {0}.**

**Cause:** setRoot could not produce an operator for component.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01518: Improper root {0}.**

**Cause:** Improper root.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01519: Failed to build parameter table, returns {0}. See error stack for complete description.**

**Cause:** Failed to build parameter table.

**Action:** See error stack for complete description.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01520: Failed to build method parameter table, returns {0}. See error stack for complete description.**

**Cause:** Failed to build method parameter table.

**Action:** See error stack for complete description.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01521: Missing Pattern Type not selected, make a Pattern Type selection**

**Cause:** Missing Pattern Type not selected.

**Action:** Make a Pattern Type selection.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**RUL-01522: Failed to locate Pattern Type, returns{0}. Check that Pattern Type exists.**  
**Cause:** Failed to locate Pattern Type.  
**Action:** Check that Pattern Type exists.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01523: setRootPattern received an exception {0}**  
**Cause:** setRootPattern received an exception.  
**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01524: Failed to create Pattern. No Pattern type specified for the Pattern.**  
**Cause:** Failed to create Pattern. No Pattern type specified for the Pattern.  
**Action:** Specify a Pattern type for the Pattern.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01525: Attempted to add operand, without an operator. Internal Error.**  
**Cause:** Attempted to add operand, without an operator.  
**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01526: Received exception for addPattern. {0}**  
**Cause:** Received exception for addPattern.  
**Action:** Correct exception or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01527: Received exception for loadClass. {0}**  
**Cause:** Received exception for loadClass.  
**Action:** Correct exception or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01528: A {0} named {1} is not located in the current dictionary.**

---

**Cause:** Component is not located in the current dictionary.

**Action:** Specify a component that exists in the dictionary.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01529: A Rule named {0} is not part of RuleSet {1}. You may have inadvertently modified the Rule name. If you modify the Rule name, the action becomes a copy and no other fields may be modified.**

**Cause:** Rule is not part of the RuleSet.

**Action:** The Rule name may have inadvertently been modified. If the Rule name is modified, the action becomes a copy and no other fields may be modified.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01530: The map type: {0} is not correct. A map of type {1} was expected. This is an internal error.**

**Cause:** The map type is not correct. A map of another type was expected.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01531: The file specified: {0} could not be turned into a URL, which is the internal format. Check the file specification to make sure it is correct.**

**Cause:** The file specified could not be turned into a URL, which is the internal format.

**Action:** Check the file specification to make sure it is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01532: The Fully Qualified Name: {0} was not located in the list, load fails.**

**Cause:** The Fully Qualified Name was not located in the list, load fails.

**Action:** Check the name or specify a name which exists in the list.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01533: Index at {0} is out of range of the tree.**

**Cause:** Index is out of range of the tree.

**Action:** Specify an index which is in the range of the tree.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**RUL-01534: Item should be one of {0} but is: {1}. Internal error.**

**Cause:** Item should be a different value. Internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01535: Expected Row type of {0} but found {1}. Internal error.**

**Cause:** Expected Row of one type but found a different one. Internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01536: The field {0} was found, but was NOT a table. Internal error.**

**Cause:** The field was found, but was NOT a table. Internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01537: The RuleObjectHelper that returns the sub map, must use the same dictionary. The dictionaries are not the same.**

**Cause:** The RuleObjectHelper that returns the sub map, must use the same dictionary. The dictionaries are not the same.

**Action:** Specify dictionaries that are the same.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01538: Index {0} is out of range of the table.**

**Cause:** Index is out of range of the table.

**Action:** Specify an index that is within the table range.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01539: RL Generation failed.**

**Cause:** RL Generation failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

---

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01540: The row was not present that contained rowId: {0}**

**Cause:** The row was not present that contained rowId.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01541: The map is not a map that may issue an update: {0}. Only first class maps representing dictionary entities may be updated. Check the map type.**

**Cause:** The map is not a map that may issue an update. Only first class maps representing dictionary entities may be updated. Check the map type.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01542: A choice list {0} had not had a valid entry selected. Therefore no selection could be returned.**

**Cause:** A choice list had not had a valid entry selected. Therefore no selection could be returned.

**Action:** Specify a valid selection.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01543: The expression in {0} was NOT a constant.**

**Cause:** The expression in was NOT a constant.

**Action:** Specify a constant for the expression.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01544: Failed to create a customization entry. The root cause is: {0}**

**Cause:** Failed to create a customization entry.

**Action:** See root cause message.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01546: During a load class, a ClassNotFoundException was received: {0}**

**Cause:** During a load class, a ClassNotFoundException was received.

**Action:** Specify a class that exists on the classpath or add the specified class to the classpath.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01547: During the setting of a decorated choice list, a class of {0} is not handled.**

**This is an internal error.**

**Cause:** During the setting of a decorated choice list, a class is not handled. This is an internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01548: The set of a dependent field failed: {0}. Set the value correctly.**

**Cause:** The set of a dependent field failed.

**Action:** Set the value correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01549: During the setting of a decorated choice list, no match was found in the list for {0}. This is an internal error or the result of a deleted dictionary object.**

**Cause:** During the setting of a decorated choice list, no match was found in the list. This is an internal error or the result of a deleted dictionary object.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01550: During the setting of a list {0}, no match was found in the list for {1}.**

**Cause:** During the setting of a list, no match was found in the list for the specified name.

**Action:** Specify a name that exists in the list.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01551: Missing dependent field {0}. This is an internal error, the map does not have an expected field.**

**Cause:** Missing dependent field. This is an internal error, the map does not have an expected field.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic



---

**RUL-01552: Dependent field {0} failed with {1} from a helper routine.**

**Cause:** Dependent field failed with error from a helper routine.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01553: Dependent field {0} could not process the value: {1}.**

**Cause:** Dependent field could not process the value.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01554: Dependent field {0} has no handlers.**

**Cause:** Dependent field has no handlers.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01555: Expected String[] or ArrayList table and {0} is {1}.**

**Cause:** Expected String[] or ArrayList table, but returned otherwise.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01556: Missing the true name list for {0}.**

**Cause:** Missing the true name list.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01557: Missing the alias list for {0}.**

**Cause:** Missing the alias list.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01558: AddEmptyRow cannot be performed for {0} row type.**

**Cause:** AddEmptyRow cannot be performed for row type.

---

**Action:** Do not attempt this operation on this type of object.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01559: Function {0} was not located when attempting to build parameter table.**

**Cause:** Function was not located when attempting to build parameter table.

**Action:** Check that function exists or specify a different function.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01560: During parameter table building an object {0} was not selected.**

**Cause:** During parameter table building an object was not selected

**Action:** Select an object.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01561: During parameter table creation, an object {0} could not be located in the data model: {1}**

**Cause:** During parameter table creation, an object could not be located in the data model

**Action:** During parameter table creation, an object could not be located in the data model

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01562: {0} statement failed to create a parameter table: {1}**

**Cause:** Statement failed to create a parameter table

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01563: An {0} statement failed to create an expression. The expression body is missing.**

**Cause:** A statement failed to create an expression. The expression body is missing.

**Action:** Specify an expression body.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01564: {0} could not locate an expression. Expected an RLText node but got {1}.**

---

**Cause:** Component could not locate an expression. Expected an RLText node but got otherwise.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01565: List creation failed: {0}**

**Cause:** List creation failed

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01566: Unable to locate Pattern of relative row {0}. This is an internal error. The Pattern table may have been corrupted.**

**Cause:** Unable to locate Pattern of relative row.

**Action:** This is an internal error. The Pattern table may have been corrupted. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01567: Searching the Pattern table failed, no rowid. This is an internal error. The Pattern table may have been corrupted.**

**Cause:** Searching the Pattern table failed, no rowid.

**Action:** Searching the Pattern table failed, no rowid. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01568: Searching the Pattern table failed, could not locate the parent Rule map. This is an internal error. The Pattern table parent pointer may have been corrupted.**

**Cause:** Searching the Pattern table failed, could not locate the parent Rule map. .

**Action:** This is an internal error. The Pattern table parent pointer may have been corrupted. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01569: Searching the Pattern table failed, no Pattern table was located in the Rule Map. This is an internal error. The Pattern table may have been corrupted.**

**Cause:** Searching the Pattern table failed, no Pattern table was located in the Rule Map.

---

**Action:** This is an internal error. The Pattern table may have been corrupted. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01570: Failed to create Action at {0}, received exception: {1}**

**Cause:** Failed to create Action.

**Action:** See underlying exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01571: Field name at [{0}] is not a valid RL identifier. Modify the field name {1} to be a valid RL name.**

**Cause:** Field name is not a valid RL identifier.

**Action:** Modify the field name to be a valid RL name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01572: Rules must have at least one Pattern.**

**Cause:** Rules must have at least one Pattern.

**Action:** Add at least one Pattern to each Rule.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01573: Make a selection for {0}.**

**Cause:** No value selected for the component.

**Action:** Make a selection for the value of the component.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01574: Method Name {0} with no parent.**

**Cause:** Method Name with no parent.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01575: Bind Instance Name {0} not located for Condition in Rule.**

**Cause:** Bind Instance Name not located for Condition in Rule.

---

**Action:** Provide a valid bind instance name for the Condition.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01576: token: {0} at {1} is unterminated**

**Cause:** Token is unterminated.

**Action:** Terminate token.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01577: token: {0} at {1} is not a known token**

**Cause:** Token is not a known token.

**Action:** Provide a valid token in that location.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01578: token: {0} at {1} is unmatched**

**Cause:** Token is unmatched.

**Action:** Match token.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01579: token: {0} at {1} is an invalid number**

**Cause:** Token is an invalid number.

**Action:** Provide a valid number for this token.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01580: Syntax error for token '{0}' at column {1}**

**Cause:** Syntax error for token.

**Action:** Correct the syntax error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01581: token: {0} at {1} is an unknown parser error**

**Cause:** Token is an unknown parser error

**Action:** Correct parser error.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01582: properties {0} and {1} have the same aliases {2}. Aliases must be unique within a Class. Change one of the aliases.**

**Cause:** Two properties have the same aliases.

**Action:** Aliases must be unique within a Class. Change one of the aliases.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01583: methods {0} and {1} have the same aliases {2}. Aliases must be unique within a Class. Change one of the aliases.**

**Cause:** Two methods have the same aliases.

**Action:** Aliases must be unique within a Class. Change one of the aliases.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01584: The field {0} was NOT set. Select a value for {0}.**

**Cause:** The field was NOT set.

**Action:** Select a value for the field.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01585: The type specified {0}. Is not a valid node type. See documentation for the SDK and JavaNode class.**

**Cause:** The type specified. Is not a valid node type.

**Action:** See documentation for the SDK and JavaNode class.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01586: The Root Node for type {0}, could not be located in the NodeTable. Refer to the documentation for the SDK and JavaNode class.**

**Cause:** The Root Node for type, could not be located in the NodeTable.

**Action:** Refer to the documentation for the SDK and JavaNode class.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01599: An error has occurred. {0} is incorrect.**

**Cause:** An error has occurred.

---

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01600: Fact Type {0} cannot be deleted as it is used {1} time(s) in the dictionary.**

**Cause:** Fact Type cannot be deleted as it is used in the dictionary.

**Action:** Remove the references to the Fact Type and then attempt to delete it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01601: Function {0} cannot be deleted as it is used {1} time(s) in the dictionary.**

**Cause:** Function cannot be deleted as it is used in the dictionary.

**Action:** Remove the references to the Function and then attempt to delete it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01602: Constraint {0} cannot be deleted as it is used {1} time(s) in the dictionary.**

**Cause:** Constraint cannot be deleted as it is used in the dictionary.

**Action:** Remove the references to the Constraint and then attempt to delete it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01603: Variable {0} cannot be deleted as it is used {1} time(s) in the dictionary.**

**Cause:** Variable cannot be deleted as it is used in the dictionary.

**Action:** Remove the references to the Variable and then attempt to delete it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01604: Dictionary object is null, found while checking consistency for deleting Fact Type {0}.**

**Cause:** Dictionary object is null, found while checking consistency for deleting Fact Type.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01605: Fact Type {0} is used in variable {1}.**

**Cause:** Fact Type is used in variable.

---

**Action:** Remove variable before attempting to remove Fact Type

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01606: Fact Type {0} is used in function {1}.**

**Cause:** Fact Type is used in function.

**Action:** Remove function before attempting to remove Fact Type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01607: Fact Type {0} is used in another Fact Type {1} as array component type.**

**Cause:** Fact Type is used in another Fact Type as array component type.

**Action:** Remove references to this Fact Type before attempting to remove this component.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01608: Fact Type {0} is used in another Fact Type {1} as its interface.**

**Cause:** Fact Type is used in another Fact Type as its interface.

**Action:** Remove references to this Fact Type before attempting to remove this component.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01609: Fact Type {0} is used in another Fact Type {1} as its super class.**

**Cause:** Fact Type is used in another Fact Type as its super class.

**Action:** Remove references to this Fact Type before attempting to remove this component.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01610: Fact Type {0} is used in another Fact Type {1} as its field type.**

**Cause:** Fact Type is used in another Fact Type as its field type.

**Action:** Remove references to this Fact Type before attempting to remove this component.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01611: Fact Type {0} is used in method {1} of the class {2}.**



---

**Cause:** Fact Type is used in a method of the class.

**Action:** Remove references to this Fact Type before attempting to remove this component.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01612: Fact Type {0} is used in one of the constructors in the class {1}.**

**Cause:** Fact Type is used in one of the constructors in the class.

**Action:** Remove references to this Fact Type before attempting to remove this component.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01613: Fact Type {0} is used in ruleset {1} rule {2} pattern {3}.**

**Cause:** Fact Type is used in a rule pattern.

**Action:** Remove references to this Fact Type before attempting to remove this component.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01614: Fact Type {0} is used in the action of ruleset {1} rule {2}.**

**Cause:** Fact Type is used in the action of a rule.

**Action:** Remove references to this Fact Type before attempting to remove this component.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01615: Dictionary object is null while checking consistency for deleting function {0}.**

**Cause:** Dictionary object is null while checking consistency for deleting function.

**Action:** Remove references to this Fact Type before attempting to remove this component.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01616: Function {0} is used in variable {1}.**

**Cause:** Function is used in a variable.

**Action:** Remove references to this Function before attempting to remove this component.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**RUL-01617: Function {0} is used in ruleset {1} rule {2} pattern {3}.**

**Cause:** Function is used in rule pattern.

**Action:** Remove references to this Function before attempting to remove this component.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01618: Function {0} is used in the action of ruleset {1} rule {2}.**

**Cause:** Function is used in the action of rule.

**Action:** Remove references to this Function before attempting to remove this component.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01619: Dictionary object is null while checking consistency for deleting constraint {0}.**

**Cause:** Dictionary object is null while checking consistency for deleting constraint.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01620: Constraint {0} is used in variable {1}.**

**Cause:** Constraint is used in variable.

**Action:** Remove references to this Constraint before attempting to remove this component.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01621: Constraint {0} is used in ruleset {1} rule {2} pattern {3}.**

**Cause:** Constraint is used in rule pattern.

**Action:** Remove references to this Constraint before attempting to remove this component.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01622: Constraint {0} is used in the action of ruleset {1} rule {2}.**

**Cause:** Constraint is used in the action of rule.

---

**Action:** Remove references to this Constraint before attempting to remove this component.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01623: Dictionary object is null while checking consistency for deleting variable {0}.**

**Cause:** Dictionary object is null while checking consistency for deleting variable.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01624: Variable {0} is used in another variable {1}.**

**Cause:** Variable is used in another variable.

**Action:** Remove references to this Variable before attempting to remove this component.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01625: Variable {0} is used in ruleset {1} rule {2} pattern {3}.**

**Cause:** Variable is used in ruleset rule pattern.

**Action:** Remove references to this Variable before attempting to remove this component.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01626: Variable {0} is used in the action of ruleset {1} rule {2}.**

**Cause:** Variable is used in the action of rule.

**Action:** Remove references to this Variable before attempting to remove this component.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01627: The schema {0} has been imported. Delete it if you want to reimport the same schema.**

**Cause:** The schema has been imported.

**Action:** Delete it if you want to reimport the same schema.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**RUL-01701: The name cannot be blank. Enter a name.**

**Cause:** The name cannot be blank.

**Action:** Enter a name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01702: The name \"{0}\" is already in use. Enter a different name**

**Cause:** The name is already in use.

**Action:** Enter a different name

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01703: The rule must have at least one pattern. Add a pattern.**

**Cause:** The rule must have at least one pattern.

**Action:** Add a pattern.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01704: \"{0}\" is not the name of a Fact Type. Enter a valid Fact Type.**

**Cause:** The value is not the name of a Fact Type.

**Action:** Enter a valid Fact Type name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01706: The pattern variable \"{0}\" is used more than once. Change one of the names.**

**Cause:** The pattern variable is used more than once.

**Action:** Change one of the names.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01707: Priority must be blank, or a positive or negative number.**

**Cause:** Priority must be blank, or a positive or negative number.

**Action:** Specify a valid value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**RUL-01708: Data validation error: {0}**

**Cause:** Data validation error

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01709: \\"{0}\" is not a valid Fact Type.**

**Cause:** The value is not a valid Fact Type.

**Action:** Specify a valid Fact Type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01710: \\"{0}\" is not a valid choice for {1}.**

**Cause:** Selected value is not a valid choice for the component.

**Action:** Specify a valid value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01711: Expression cannot be blank. Enter an expression**

**Cause:** Expression cannot be blank.

**Action:** Enter an expression

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01712: Invalid variable name \\"{0}\": contains multiple spaces.**

**Cause:** Invalid variable name, contains multiple spaces.

**Action:** Specify a variable name that does not contain multiple spaces.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01713: Invalid rule set name \\"{0}\": Must begin with a letter and contain only letters and numbers.**

**Cause:** Invalid rule set name.

**Action:** Specify a rule set name that begins with a letter and contains only letters and numbers.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**RUL-01714: Invalid rule name \'{0}\': Must begin with a letter and contain only letters and numbers.**

**Cause:** Invalid rule name.

**Action:** Specify a rule name that begins with a letter and contains only letters and numbers.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01716: \'{0}\'' is not a valid function name.**

**Cause:** The name is not a valid function name.

**Action:** Specify a valid function name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01717: \'{0}\'' is not a valid identifier name, or a string has not been properly surrounded with quotes(\\'').**

**Cause:** The value is not a valid identifier name, or a string has not been properly surrounded with quotes('').

**Action:** Specify a valid identifier name or surround the identifier with quotes.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01718: \'{0}\'' is not a valid constraint name.**

**Cause:** The value is not a valid constraint name.

**Action:** Specify a valid constraint name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01719: Nothing to restore.**

**Cause:** Nothing to restore.

**Action:** None.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01720: Nothing to discard.**

**Cause:** Nothing to discard.

**Action:** None.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**RUL-01721: Missing test on Pattern. Confirm or supply a test**

**Cause:** Missing test on Pattern.

**Action:** Confirm or supply a test

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01722: {0} must match the pattern: {1}**

**Cause:** Value must match the pattern value.

**Action:** Specify a matching value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01723: {0} must be a number between {1} and {2}**

**Cause:** The value must be a number between the upper and lower bound.

**Action:** Specify a valid value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01724: Array {0} must be followed by []**

**Cause:** Array must be followed by []

**Action:** Add [] to array definition.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01725: {0} is not an Array and cannot be followed by []**

**Cause:** The value is not an Array and cannot be followed by []

**Action:** Specify a valid value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01726: Data type operator for {0}, at position {1}: {2} {3} {4}**

**Cause:** Data type operator error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01727: Incorrect number of parameters for function {0} at {1}**

---

**Cause:** Incorrect number of parameters for the function.

**Action:** Specify the correct number of parameters for the function.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01728: Test expression must return true or false, not `\"{0}\"`**

**Cause:** Test expression must return true or false, but did not.

**Action:** Specify a test expression that returns a boolean value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01729: Must be a literal value. Strings must be quoted with `\"\"`.**

**Cause:** Must be a literal value.

**Action:** Provide a numeric value or quote Strings.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01730: Must be a number.**

**Cause:** Value is not a number.

**Action:** Specify a numeric value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01731: The nested Pattern has an empty NestedTable. Remove the nested Pattern or add nested entries.**

**Cause:** The nested Pattern has an empty NestedTable.

**Action:** Remove the nested Pattern or add nested entries.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01801: The value {0} is not in the option list for {1}.**

**Cause:** The value is not in the option list.

**Action:** Specify a value that is in the option list.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01802: RuleComponent {0} is not associated with a Dictionary**

**Cause:** RuleComponent is not associated with a Dictionary



---

**Action:** Recreate the RuleComponent using the factory methods in the dictionary components, or contact Oracle Support Service.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01803: Action of FORM\_ASSERT\_NEW requires TARGET of class alias. See javadoc for Action.**

**Cause:** Action of FORM\_ASSERT\_NEW requires TARGET of class alias.

**Action:** Specify an alias for the Action target. See javadoc for Action.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01804: Action of FORM\_ASSIGN requires assignable target and single parameter. See javadoc for Action.**

**Cause:** Action of FORM\_ASSIGN requires assignable target and single parameter.

**Action:** Specify valid values for the Action.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01805: Action of FORM\_NESTED\_TABLE requires ActionTable. See javadoc for Action.**

**Cause:** Action of FORM\_NESTED\_TABLE requires ActionTable.

**Action:** Specify an ActionTable for the Action. See javadoc for Action.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01806: System error: unable to instantiate component copy**

**Cause:** System error: unable to instantiate component copy

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01807: Action of FORM\_ASSERT or FORM\_RETRACT requires TARGET variable (not \"{0}\"). See javadoc for Action.**

**Cause:** Action of FORM\_ASSERT or FORM\_RETRACT requires target variable.

**Action:** Specify a target variable for the Action. See javadoc for Action.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**RUL-01808: Unable to save rule set. SDK Exception: \\\"{0}\\\"**

**Cause:** Unable to save rule set.

**Action:** Correct exception or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01809: Unable to load rule set. SDK Exception: \\\"{0}\\\"**

**Cause:** Unable to load rule set.

**Action:** Correct exception or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01810: Expression parameter conflict, Form is \\\"{0}\\\" but property {1} was set.**

**Cause:** Conflicting form and property set.

**Action:** Resolve conflict. See javadoc for Action.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01811: The number of rows in this table cannot be changed.**

**Cause:** The number of rows in this table cannot be changed.

**Action:** Do not attempt to add or remove rows from this table.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01812: Row not found**

**Cause:** Row not found.

**Action:** Specify a row that exists.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01813: Enum constraint {0} contains invalid values for property {1}**

**Cause:** Enum constraint contains invalid values for property

**Action:** Remove invalid values from constraint.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**RUL-01814: Program set option list contains invalid values for {0}**

**Cause:** Program set option list contains invalid values.

**Action:** Remove invalid values from program set option list.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01815: Null values not allowed for key or value put ( {0}, {1} )**

**Cause:** Null values not allowed for key or value of put() call

**Action:** Specify a non-null value for key and value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01816: put() key must be of type String**

**Cause:** put() key must be of type String

**Action:** Specify a key of type String

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01817: Property {0} is read only**

**Cause:** Property is read only

**Action:** Do not attempt to set property.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01818: Value for property {0} must be of type {1}**

**Cause:** Value for property must be of type.

**Action:** Specify a value of the correct type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01819: \"{0}\" is not a valid property of {1}**

**Cause:** The value is not a valid property of the component.

**Action:** Specify a valid property of the component.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01820: Constraint \"{0}\" not found in data model**

**Cause:** Constraint not found in data model.

---

**Action:** Specify a Constraint in the data model

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01821: Only CUSTOM and program set OPTIONS properties can be removed**

**Cause:** Only CUSTOM and program set OPTIONS properties can be removed.

**Action:** Do not attempt to remove the specified property.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01822: Cannot set Property {0} in custom mode, has default CONSTRAINT\_FIXED.**

**Cause:** Cannot set Property in custom mode, has default CONSTRAINT\_FIXED.

**Action:** Do not attempt to set this property or change the constraint to something other than fixed.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01880: While loading ruleset {0} from persistence to editor, unable to find this ruleset in the dictionary.**

**Cause:** While loading ruleset from persistence to editor, unable to find this ruleset in the dictionary.

**Action:** Specify a different ruleset or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01881: The ruleset to be loaded contains a pattern {0}, which has nested conjunction tests. Oracle Rules Editor API currently doesn't support the nested tests.**

**Cause:** The ruleset to be loaded contains a pattern, which has nested conjunction tests. Oracle Rules Editor API currently doesn't support the nested tests.

**Action:** Remove the nested conjunction tests.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01882: The ruleset to be loaded contains a test which is not in the format (lhs op rhs). Oracle Rules Editor API only supports simple test given above.**

**Cause:** The ruleset to be loaded contains a test which is not in the format (lhs op rhs).

**Action:** Oracle Rules Editor API only supports simple test given above.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01883: Unable to save priority {0} for rule {1}. Make sure the priority is a well-formatted integer.**

**Cause:** Unable to save priority for rule.

**Action:** Ensure the priority is a well-formatted integer.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01884: While saving the editor DataModel, the type \"{1}\" of variable \"{0}\" is not found in persistent DataModel.**

**Cause:** While saving the editor DataModel, the type of the variable is not found in persistent DataModel.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01885: While saving the editor DataModel, the enumeration constraint \"{0}\" does not have a list of possible values.**

**Cause:** While saving the editor DataModel, the enumeration constraint does not have a list of possible values.

**Action:** Specify a list of values for the constraint.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01886: While saving the editor DataModel, the return type \"{1}\" of function \"{0}\" is not found in the persistent DataModel.**

**Cause:** While saving the editor DataModel, the return type of function is not found in the persistent DataModel.

**Action:** Import or define the Fact Type of the return function.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01887: While saving the editor DataModel, the parameter type \"{1}\" of function \"{0}\" is not found in the persistent DataModel.**

**Cause:** While saving the editor DataModel, the parameter type of function is not found in the persistent DataModel.

**Action:** Import or define the Fact Type of the function.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**RUL-01888: While saving the editor DataModel, the exception type `\\{1}\\` of function `\\{0}\\` is not found in the persistent DataModel.**

**Cause:** While saving the editor DataModel, the exception type of function is not found in the persistent DataModel.

**Action:** Import or define the Fact Type of the function.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01889: While saving the editor DataModel, RLFact Type `\\{0}\\` super class `\\{1}\\` is not found in the persistent DataModel.**

**Cause:** While saving the editor DataModel, RLFact Type super class is not found in the persistent DataModel.

**Action:** Import or define the Fact Type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01890: While saving the editor DataModel, the type `\\{1}\\` of property `\\{0}\\` is not found in the persistent DataModel.**

**Cause:** While saving the editor DataModel, the type of property is not found in the persistent DataModel.

**Action:** Import or define the Fact Type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01891: While saving the editor DataModel, the corresponding Java Property `\\{0}\\` is not found in the persistent DataModel.**

**Cause:** While saving the editor DataModel, the corresponding Java Property is not found in the persistent DataModel.

**Action:** Import or define the Fact Type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01892: The lower or upper bound for the range constraint `\\{0}\\` is not found in the datamodel.**

**Cause:** The lower or upper bound for the range constraint is not found in the datamodel.

**Action:** Specify an lower and upper bound for the range constraint.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**RUL-01893: The lower or upper bound \{"0"\ for the range constraint \{"1"\ is not a well formatted double.**

**Cause:** The lower or upper bound for the range constraint is not a well formatted double.

**Action:** Specify a well formatted double for both values.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01894: The global variable \{"0"\ is not initialized.**

**Cause:** The global variable is not initialized.

**Action:** Specify an initializer for the global variable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01895: While validating \{"0"\, found {1} Error(s).**

**Cause:** While validating component, an error was found.

**Action:** Correct the underlying errors.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01896: While checking for uses before a delete an invalid type of {0} was used.  
Change the type.**

**Cause:** While checking for uses before a delete an invalid type was used.

**Action:** Change the type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01897: While checking for uses before a delete, no data model was located.**

**Cause:** While checking for uses before a delete, no data model was located.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-01898: While checking for uses before a delete of a Constraint, no Form property was located.**

**Cause:** While checking for uses before a delete of a Constraint, no Form property was located.

**Action:** Specify a form property before attempting delete.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**RUL-01899: The Primitive Fact Type {0} cannot be deleted.**

**Cause:** The Primitive Fact Type cannot be deleted.

**Action:** Do not attempt to delete the fact type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01900: Unable to delete Fact Type {0}.**

**Cause:** Unable to delete Fact Type.

**Action:** Unknown.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01901: Unable to delete Constraint {0}.**

**Cause:** Unable to delete Constraint.

**Action:** Unknown

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01902: The built-in function {0} cannot be deleted.**

**Cause:** The built-in function cannot be deleted.

**Action:** Do not attempt to delete the built-in function.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01903: Unable to delete Function {0}.**

**Cause:** Unable to delete Function.

**Action:** Unknown.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01904: Unable to delete Variable {0}.**

**Cause:** Unable to delete Variable.

**Action:** Unknown.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic



---

**RUL-01905: A {0} cannot be deleted.**

**Cause:** Component cannot be deleted.

**Action:** Do not attempt to delete component.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01906: A Java property cannot be deleted.**

**Cause:** A Java property cannot be deleted.

**Action:** Do not attempt to delete the property.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01907: A constraint must have a name.**

**Cause:** A constraint must have a name.

**Action:** Specify a name for the constraint.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01908: Range Constraint {0} does not have a lower bound.**

**Cause:** Range Constraint does not have a lower bound.

**Action:** Specify a lower bound for the range constraint.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01909: Range Constraint {0} does not have a well formatted lower bound {1}.**

**Cause:** Range Constraint does not have a well formatted lower bound.

**Action:** Specify a well formatted lower bound.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01910: Range Constraint {0} does not have an upper bound.**

**Cause:** Range Constraint does not have an upper bound.

**Action:** Specify an upper bound.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01911: Range Constraint {0} does not have a well formatted upper bound {1}.**

**Cause:** Range Constraint does not have a well formatted upper bound.

---

**Action:** Specify a well formatted upper bound.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01912: Range Constraint {0} has a lower bound {1} larger than upper bound {2}.**

**Cause:** Range Constraint has a lower bound larger than upper bound.

**Action:** Specify a lower bound smaller than upper bound.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01913: Enumeration Constraint {0} does not have enumeration values defined.**

**Cause:** Enumeration Constraint does not have enumeration values defined.

**Action:** Define values for enumeration constraint.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01914: Regular Expression Constraint {0} does not have the regular expression defined.**

**Cause:** Regular Expression Constraint does not have the regular expression defined.

**Action:** Define a regular expression for the constraint.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01915: Function name {0} is not a valid identifier.**

**Cause:** Function name is not a valid identifier.

**Action:** Specify a valid function name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01916: Function name {0} is an RL reserved word.**

**Cause:** Function name is an RL reserved word.

**Action:** Specify a function name that is not an RL reserved word.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01917: Return type of function {0} has to be defined.**

**Cause:** Return type of function has to be defined.

---

**Action:** Specify return type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01918: Return type `\\\"{1}\\\"` of Function {0} is not defined in the datamodel.**

**Cause:** Return type of Function is not defined in the datamodel.

**Action:** Import or define the Fact Type or specify a return type that is in datamodel.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01919: Body of Function {0} has to be defined.**

**Cause:** Body of Function has to be defined.

**Action:** Define body of function.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01920: Function {0} has two parameters with the same name.**

**Cause:** Function has two parameters with the same name.

**Action:** Change the name of one of the duplicate parameter names.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01921: Duplicated Function Name {0}.**

**Cause:** Duplicated Function Name.

**Action:** Specify a different name for the function.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01922: Duplicated Function Alias {0}.**

**Cause:** Duplicated Function Alias.

**Action:** Specify a different alias for the function.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01923: InitValue {0} is not valid.**

**Cause:** InitValue is not valid.

**Action:** Provide a valid init value.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01924: DataModel Component {0} has an alias \"{1}\" starting with space.**

**Cause:** DataModel Component has an alias starting with space.

**Action:** Specify an alias that does not start with a space.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01925: DataModel Component {0} has an alias \"{1}\" ending with space.**

**Cause:** DataModel Component has an alias ending with space.

**Action:** Specify an alias that does not end with a space.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01926: DataModel Component {0} has an alias \"{1}\" containing double space.**

**Cause:** DataModel Component has an alias containing double space.

**Action:** Remove the double space from the alias.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01927: Property must have a name.**

**Cause:** Property must have a name.

**Action:** Specify a name for the property.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01928: Property name {0} is not a valid identifier.**

**Cause:** Property name is not a valid identifier.

**Action:** Specify a valid identifier for the property name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01929: Property name {0} is an RL reserved word.**

**Cause:** Property name is an RL reserved word.

**Action:** Specify a name that is not an RL reserved word.

**Level:** 1

---

**Type:** ERROR  
**Impact:** Programmatic  
**RUL-01930: Property {0} must have a type.**  
**Cause:** Property must have a type.  
**Action:** Specify a type for the property .  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic  
**RUL-01931: Type \"{1}\" of property {0} is not defined in the datamodel.**  
**Cause:** Type of property is not defined in the datamodel.  
**Action:** Import or define the type of the property into the datamodel or specify a type that is already in the datamodel.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic  
**RUL-01932: RL Fact Type name {0} is not a valid identifier.**  
**Cause:** RL Fact Type name is not a valid identifier.  
**Action:** Specify a valid identifier for the RL Fact Type name.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic  
**RUL-01933: RL Fact Type name {0} is an RL reserved word.**  
**Cause:** RL Fact Type name is an RL reserved word.  
**Action:** Specify a name for the RL Fact Type that is not an RL reserved word.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic  
**RUL-01934: RL Fact Type {0} contains duplicate property names.**  
**Cause:** RL Fact Type contains duplicate property names.  
**Action:** Change the name of one of the duplicate property names.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic  
**RUL-01935: RL Fact Type {0} contains duplicate property aliases.**  
**Cause:** RL Fact Type contains duplicate property aliases.  
**Action:** Change the name of one of the duplicate property names.  
**Level:** 1  
**Type:** ERROR

---

**Impact:** Programmatic

**RUL-01936: Duplicated RL Fact Type Name {0}.**

**Cause:** Duplicated RL Fact Type Name.

**Action:** Change the name of one of the duplicate fact types.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01937: Duplicated RL Fact Type Alias {0}.**

**Cause:** Duplicated RL Fact Type Alias.

**Action:** Change one of the duplicate aliases.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01938: Global Variable name {0} is not a valid identifier.**

**Cause:** Global Variable name is not a valid identifier.

**Action:** Change one of the duplicate variable names.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01939: Global Variable name {0} is a RL reserved word.**

**Cause:** Global Variable name is an RL reserved word.

**Action:** Specify a global variable name that is not an RL reserved word.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01940: Value of Global variable {0} is not set.**

**Cause:** Value of global variable is not set.

**Action:** Specify the value of the global variable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01941: Value {1} of Global variable {0} is not valid.**

**Cause:** Value of Global variable is not valid.

**Action:** Specify a valid value for the global variable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01942: Global Variable {0} must have a type.**

---

**Cause:** Global variable must have a type.

**Action:** Specify a type for the global variable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01943: Type `\\{1}\\` of Global Variable {0} is not defined in the datamodel.**

**Cause:** Type of Global Variable is not defined in the datamodel.

**Action:** Import or define the type of variable into the datamodel or specify a different type for the variable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01944: Value of Global variable {0} does not match its type {1}.**

**Cause:** Value of Global variable does not match its type.

**Action:** Specify a value that matches type or change the type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01945: Duplicated Global Variable Name {0}.**

**Cause:** Duplicated Global Variable Name.

**Action:** Change one of the variable names.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01946: Duplicated Global Variable Alias {0}.**

**Cause:** Duplicated Global Variable Alias.

**Action:** Change one of the variable aliases.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01947: One parameter in Function {0} has no name.**

**Cause:** One parameter in Function has no name.

**Action:** Specify a name for the Function parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01948: Formal Parameter name {0} is not a valid identifier.**

**Cause:** Formal Parameter name is not a valid identifier.

---

**Action:** Specify a valid identifier for the formal parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01949: Formal Parameter name {0} is a RL reserved word.**

**Cause:** Formal Parameter name is an RL reserved word.

**Action:** Specify a name that is not an RL reserved word.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01950: Type for Formal Parameter {0} has to be defined.**

**Cause:** Type for Formal Parameter has to be defined.

**Action:** Import or define type of parameter, or specify a different type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01951: Type \"{1}\" of Formal Parameter {0} is not defined in the datamodel.**

**Cause:** Type of Formal Parameter is not defined in the datamodel.

**Action:** Import or define type of parameter, or specify a different type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01952: Duplicated Property Alias {0}.**

**Cause:** Duplicated Property Alias.

**Action:** Change the name of one property alias.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01953: Duplicated Method Alias {0}.**

**Cause:** Duplicated Method Alias.

**Action:** Change the name of one method alias.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01954: Duplicated Java Fact Type Alias {0}.**

**Cause:** Duplicated Java Fact Type Alias.

**Action:** Change the name of one Java Fact Type alias.



---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01955: One parameter in Function {0} has no alias.**

**Cause:** One parameter in Function has no alias.

**Action:** Specify an alias for this parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01956: Function {0} has two parameters with the same alias.**

**Cause:** Function has two parameters with the same alias.

**Action:** Change one of the duplicate parameter aliases.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-01958: Constraint {0} is used in other component(s) of the dictionary. Remove all references in order to modify the constraint name.**

**Cause:** Constraint is used in other component(s) of the dictionary.

**Action:** Remove all references in order to modify the constraint name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-02001: See the base exception for details.**

**Cause:** Unknown.

**Action:** See the base exception for details.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-02002: File corresponding to the path {0} does not exist. Ensure the file exists in the file system.**

**Cause:** File corresponding to the path does not exist.

**Action:** Ensure the file exists in the file system.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-02102: Document ID has not been validated.**

**Cause:** A rule SDK internal failed to validate a document ID before invoking the repository store layer.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-02103: ID "{0}" is missing the dictionary name.**

**Cause:** A document ID was missing the dictionary name.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-02104: ID "{0}" is missing the document name.**

**Cause:** A document ID was missing the document name.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-02105: ID "{0}" is missing the document type.**

**Cause:** A document ID was missing the document type.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-02106: ID "{0}" contains an invalid wildcard. The wildcard character, '\*', must apply to the entire field.**

**Cause:** A invalid wildcard was supplied in the document ID.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-02107: Wildcards only valid with listDocuments, ID "{0}".**

**Cause:** A wildcard was supplied in the document ID to be used for access other than listDocuments.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-02110: No registration exists for "{0}".**

**Cause:** No RepositoryConnection implementation was available for the specified key.

---

**Action:** Verify that the key is correct and that the corresponding RepositoryConnection was successfully registered.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-02112: The dictionary name in ID "{0}" is not a legal Unicode identifier.**

**Cause:** An invalid dictionary name was specified.

**Action:** Specify a valid dictionary name. It must be a legal Unicode identifier.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-02113: The document name in ID "{0}" is not a legal Unicode identifier.**

**Cause:** A invalid document name was supplied in the document ID.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-02114: The document type in ID "{0}" is not a legal Unicode identifier.**

**Cause:** A invalid document type was supplied in the document ID.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-02115: The marker in ID "{0}" is not a legal Unicode identifier.**

**Cause:** An invalid marker was specified.

**Action:** Specify a valid marker. It must be a legal Unicode identifier.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-02116: invalid or missing registration**

**Cause:** A RepositoryConnection registration was null or one of its properties was null (not specified).

**Action:** Verify that the key is correct and that the corresponding RepositoryConnection was successfully registered.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-02117: ID "{0}" is missing the marker.**

**Cause:** A marker was not specified in the document ID.

---

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-02118: ID "{0}" is not valid for use with this repository connection.**

**Cause:** The document ID was not created with this connection.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-02119: Unable to load repository store add-in class "{0}". The store is unavailable.**

**Cause:** An error was encountered in loading the specified RepositoryConnection implementation class.

**Action:** Verify that the class is available on the class path.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-02120: repository connection factory initialization failure**

**Cause:** An error was encountered initializing the RepositoryConnection factory.

**Action:** Investigate the exception that was logged.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-02201: missing initialization property for key "{0}"**

**Cause:** A required initialization parameter was missing.

**Action:** Provide the missing initialization parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-02202: URL "{0}" is not a WebDAV collection.**

**Cause:** A WebDAV URL was expected to be a path to a folder (a WebDAV collection) but it was not.

**Action:** Verify that the URL is correct and that it does identify a folder.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-02203: WebDAV error**

**Cause:** A WebDAV error occurred.

---

**Action:** Consult the root cause exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-02204: WebDAV error occurred for URL "{0}".**

**Cause:** The URL for the WebDAV repository was incorrect.

**Action:** Supply a valid WebDAV URL.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-02205: WebDAV repository "{0}" does not exist.**

**Cause:** The specified WebDAV repository was not be found.

**Action:** Verify that the path to the repository is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-02206: null document**

**Cause:** A null XML Document was supplied.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-02207: WebDAV error occurred for document "{0}", WebDAV URL "{1}"**

**Cause:** A error occurred accessing a rule dictionary document on the WebDAV repository.

**Action:** Consult the root cause exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-02210: ID "{0}" is not valid for document access.**

**Cause:** An internal ID identifying a document that is part of a rule dictionary was not valid.

**Action:** Contact Oracle Support.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-02301: missing initialization property for key "{0}"**

**Cause:** A required initialization parameter was missing.

---

**Action:** Provide the missing initialization parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-02302: error accessing file "{0}"**

**Cause:** An I/O error occurred accessing the file repository.

**Action:** The nested exception specifies the root cause. Investigate and resolve.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-02303: null document**

**Cause:** A null XML Document was supplied.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-02305: file path "{0}" does not exist**

**Cause:** The specified file repository could not be found.

**Action:** Verify that the path to the file is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-02307: ID "{0}" is not valid for document access.**

**Cause:** An internal ID identifying a document that was part of a rule dictionary was not valid.

**Action:** Contact Oracle Support.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-02311: Unable to rename "{0}" so that it can be replaced. This can be caused by another rules based application reading the repository at the same time as this attempt to update it. The operation may be retried. If this error persists, then some other application is keeping the repository open.**

**Cause:** An attempt to rename the original repository file so that the new one can be written failed.

**Action:** Verify that it is not being accessed by another application and then retry.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**RUL-02312: Unable to rename updated file "{0}" to "{1}". The repository update failed. The old repository content is in the file "{2}". The updated repository content is in the file "{0}". To recover from this error, manually rename the file "{0}" to "{1}".**

**Cause:** An attempt to rename the new repository file to the correct name failed.

**Action:** Recover manually by renaming the files as directed in the error message.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-02313: Unable to delete the file "{0}" which contains old repository content. It may be deleted manually.**

**Cause:** An attempt to delete the old, renamed repository file failed.

**Action:** Recover by manually deleting the file as directed in the error message.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-04001: unable to instantiate RuleAdministrator**

**Cause:** An error occurred getting a JSR-94 RuleAdministrator instance.

**Action:** Verify that jsr94.jar and jsr94\_obr.jar are present.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-04002: unable to instantiate RuleRuntime**

**Cause:** An error occurred getting a JSR-94 RuleRuntime instance.

**Action:** Verify that jsr94.jar and jsr94\_obr.jar are present.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-04003: JSR-94 RuleServiceProvider registration failure**

**Cause:** An error occurred registering the Oracle Business Rules JSR-94 RuleServiceProvider.

**Action:** Verify that jsr94.jar and jsr94\_obr.jar are present.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-04004: The creation of a RuleExecutionSet from an abstract syntax tree is not supported.**

**Cause:** An attempt was made to create a RuleExecutionSet with a method that takes an abstract syntax tree. This is not supported.

**Action:** Create a RuleExecutionSet with a supported method.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-04005: null argument**

**Cause:** A null was passed to an extension to JSR-94 to programmatically create a RuleExecutionSet.

**Action:** Correct the invocation of the method.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-04009: unable to create an XML DocumentBuilder**

**Cause:** An error occurred getting a DocumentBuilder.

**Action:** Verify that the XML parser configuration is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-04010: rule execution set name missing**

**Cause:** An XML or programmatic specification of a RuleExecutionSet was missing the name of the RuleExecutionSet.

**Action:** Supply the missing name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-04011: missing repository location**

**Cause:** An XML or programmatic specification of a RuleExecutionSet was missing the repository location.

**Action:** Supply the missing repository location.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-04012: missing dictionary name**

**Cause:** An XML or programmatic specification of a RuleExecutionSet was missing the name of the rule dictionary.

**Action:** Supply the missing rule dictionary name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-04015: No RuleExecutionSet is registered under URI "{0}".**



---

**Cause:** An attempt was made to deregister a RuleExecutionSet that had not been registered.

**Action:** Verify that the URI is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-04018: Multiple dictionaries were found in the RuleExecutionSet specification. The second dictionary is named "{0}" in repository "{1}"**

**Cause:** An XML or programmatic specification of a RuleExecutionSet contained references to more than one rule dictionary.

**Action:** Limit the specification to a single rule dictionary.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-04019: missing MDS instance name**

**Cause:** An XML or programmatic specification of a RuleExecutionSet that references a rule dictionary in an MDS repository was missing the name of the MDS instance.

**Action:** Supply the missing MDS instance name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05003: The visible fact type \"{0}\" should only inherit from one visible fact type, but inherits from visible fact types \"{1}\" and \"{2}\".**

**Cause:** A visible fact type inherited from more than one visible fact type.

**Action:** Make one of the fact types not visible.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05004: The file tools.jar containing com.sun.tools.javac.Main cannot be found on the classpath. Ensure that it is on the classpath.**

**Cause:** The file tools.jar containing com.sun.tools.javac.Main could not be found on the classpath.

**Action:** Add tools.jar to the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05005: The class com.sun.tools.javac.Main does not contain the method \"invoke\".**

**Cause:** The class com.sun.tools.javac.Main does not contain the method "invoke"

**Action:** Verify that your JVM installation is not corrupted.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05006: The fact type `\"{0}\"` has the same alias as an unrelated bucketset.**

**Cause:** A bucketset has the same alias as a fact type, but the fact type or bucketset is not created from importing a Java enum.

**Action:** Provide different aliases for the fact type or bucketset.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05011: The schema `\"{1}\"` is not on schema path `\"{0}\"`.**

**Cause:** The schema root path is set, but the schema that was added is not on this same path. Set the correct schema root path or move the schema to be added.

**Action:** See the base exception for resolution.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05013: The Java class `\"{0}\"` cannot be added to the data model. Ensure that the class and its associated classes, including parent classes and attribute type classes, are on the current classpath.**

**Cause:** The Java class could not be added to the data model.

**Action:** Ensure that the class and its associated classes, including parent classes and attribute type classes, are on the current classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05015: The user path `\"{0}\"` is not a directory or zip file. Ensure that the user path is either a directory, zip file, or jar file.**

**Cause:** The user path was not a directory or zip file.

**Action:** Ensure that the user path is either a directory, zip file, or jar file.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05016: The Java class `\"{0}\"` cannot be loaded. Ensure that the class and all its dependent classes are on either the classpath or the user-specified path.**

**Cause:** Could not load Java class.

**Action:** Ensure that the class and all its dependent classes are either in the classpath, or user specified path.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**RUL-05017: The Java class cannot be loaded. The class name must be valid.**

**Cause:** Could not load Java class.

**Action:** The class name must be valid.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05018: The Java class \"{0}\" cannot be loaded. The class must be inside a package.**

**Cause:** Could not load Java class.

**Action:** The class must be inside a package.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05019: The Java class \"{0}\" cannot be imported. Ensure that the class and its associated classes, including parent classes and attribute type classes, are on the current classpath. See the base exception for detail.**

**Cause:** Could not reimport Java class.

**Action:** Ensure that the class and its associated classes, including parent classes and attribute type classes, are on the current classpath. See base exception for detail.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05020: The Java class \"{0}\" cannot be loaded. The class name contains RL reserved word \"{1}\".**

**Cause:** Could not load Java class. The class name contained an RL reserved word.

**Action:** Remove the RL reserved word from the class name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05021: The Java class \"{0}\" has a field \"{1}\" that is an RL reserved word.**

**Cause:** Java class had a field that is an RL reserved word.

**Action:** Change the name of the field.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05022: The Java class \"{0}\" has a property \"{1}\" that is an RL reserved word.**

---

**Cause:** Java class had a property that is an RL reserved word.

**Action:** Change the name of the property.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05023: The Java class `\"{0}\"` has a method `\"{1}\"` that is an RL reserved word.**

**Cause:** Java class had a method that is an RL reserved word.

**Action:** Change the name of the method.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05024: The JAXB output directory is null or an empty string.**

**Cause:** JAXB output directory was null or an empty string.

**Action:** Use a valid directory.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05025: The JAXB output directory `\"{0}\"` is not a valid directory.**

**Cause:** JAXB output directory was not a valid directory.

**Action:** Use a valid directory.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05026: The JAXB output directory `\"{0}\"` is not writable.**

**Cause:** JAXB output directory was not writable.

**Action:** Use a valid directory.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05027: The package name is not a valid Java identifier.**

**Cause:** Package name was not a valid Java identifier.

**Action:** Provide a package name that is a valid Java identifier.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05028: The XML schema name is null or an empty string.**

**Cause:** XML schema name was null or an empty string.

---

**Action:** Provide a valid schema name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05029: The XML schema `\\{0}\\` does not exist.**

**Cause:** XML schema did not exist.

**Action:** Provide an XML schema that exists.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05030: The source code generated by `\\{0}\\` in the directory `\\{1}\\` cannot be compiled.**

**Cause:** JAXB generated source code could not be compiled.

**Action:** Make sure tools.jar is in CLASSPATH.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**RUL-05034: A `\\return\\` action is missing. Add a return action or change the function return type to void.**

**Cause:** A return action was missing.

**Action:** Add a return action or change the function return type to void.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05035: The value to be validated is null.**

**Cause:** The value to be validated was null.

**Action:** Provide a value that is not null.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05036: The XSL resource named `\\{0}\\` cannot be located on the classpath.**

**Cause:** The XSL resource named could not be located on the classpath.

**Action:** Check that the XSL resource name and classpath are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05037: A circular definition exists in the data model `\\{0}\\`.**

**Cause:** Data model contained circular definitions of RL or ADF-BC Fact Types.

---

**Action:** Remove cyclical dependencies from the data model. For RL Fact Types, the cycle must be disconnected by removing properties. For ADF-BC Fact Types, the cycle must be disconnected by marking properties nonvisible.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05038: The XML schema \"{0}\" cannot be added to the data model because JAXB source cannot be generated. See the base exception for resolution.**

**Cause:** The XML schema could not be added into the data model because the JAXB source files could not be generated.

**Action:** See the base exception for resolution.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05039: The XML schema path \"{0}\" cannot be added to the data model. Could not generate JAXB mapping. See the base exception for resolution.**

**Cause:** The XML schema could not be added into the data model because the JAXB mapping could not be generated.

**Action:** See the base exception for resolution.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05040: The XML schema path \"{0}\" cannot be added to the data model because JAXB source cannot be compiled. See the base exception for resolution.**

**Cause:** The XML schema could not be added into the data model because the JAXB source could not be compiled.

**Action:** See the base exception for resolution.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05041: The XML schema path \"{0}\" cannot be added to the data model because the path cannot be added to datamodel and classloader. See the base exception for resolution.**

**Cause:** The XML schema could not be added into the data model because the schema path could not be added to the datamodel and classloader.

**Action:** See the base exception for resolution.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05042: The XML schema \"{0}\" does not exist.**

**Cause:** XML schema did not exist.

---

**Action:** Provide an XML schema that exists.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05101: The ruleset cannot be serialized to XML. See base exception for resolution.**

**Cause:** Ruleset could not be serialized to XML.

**Action:** See base exception for resolution.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05102: The XML document cannot be deserialized into a ruleset. See the base exception for resolution.**

**Cause:** XML document could not be deserialized into a ruleset.

**Action:** See the base exception for resolution.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05103: The ruleset visibility filter cannot be evaluated. Check syntax of dates, times, and numbers.**

**Cause:** Could not evaluate ruleset visibility filter.

**Action:** Check syntax of dates, times, and numbers.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05130: component does not support property \"{0}\"**

**Cause:** Component did not support the property specified.

**Action:** Do not use this property.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05140: The XML schema \"{0}\" could not be mapped to XML fact types. See base exception for detail.**

**Cause:** XML schema could not be mapped to XML fact types.

**Action:** See base exception for detail.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05148: The ADF-BC View Definition name is null.**

---

**Cause:** The ADF-BC View Definition name was null.  
**Action:** Specify a valid ADF-BC View Definition name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05149: exception while attempting to import the ADF-BC View Definition  
\\\"{0}\\\"**

**Cause:** An exception occurred while attempting to import the View Definition.

**Action:** See base exception for detail.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05161: The decision function \\\"{0}\\\" requires fact type \\\"{1}\\\", but this  
type is not part of the input.**

**Cause:** Decision function rule flow checking detected a missing fact type required by the called decision function.

**Action:** Assert the required fact types before invoking the decision function.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05162: The rule set \\\"{0}\\\" requires fact type \\\"{1}\\\", but this type is not  
part of the input.**

**Cause:** Decision function rule flow checking detected a missing fact type required by the called ruleset.

**Action:** Assert the required fact types before invoking the ruleset.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05163: The fact type \\\"{0}\\\" is not used in any ruleset called by this decision  
function.**

**Cause:** Decision function rule flow checking detected an unused fact type.

**Action:** Reference all asserted fact types in a rule condition or decision function output type list.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05164: The fact type \\\"{0}\\\" is referenced, but is not asserted nor input.**

**Cause:** Decision function rule flow checking detected a fact type referenced in a rule condition, called decision function input, or this decision function output that is not an input to this decision function, nor an output of a called decision function, and is not asserted by a ruleset in this decision function



---

**Action:** Ensure that all fact types in conditions are asserted or input to the decision function.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05165: The decision function `\"{0}\"` has two adjacent entries in the ruleset or decision function table with the name `\"{1}\"`.**

**Cause:** The decision function has two adjacent entries in the ruleset / decision function table that have the same name. This is an error, because no rules will fire when second entry is called.

**Action:** Remove one of the entries.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05170: unexpected exception**

**Cause:** An unexpected exception occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05171: A RuleDictionary instance or name is required.**

**Cause:** A RuleDictionary instance or name was not supplied.

**Action:** Provide a RuleDictionary instance or name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05172: A decision function name is required.**

**Cause:** A decision function name was not supplied.

**Action:** Provide a decision function name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05173: A transaction instance is required.**

**Cause:** A transaction instance was not supplied.

**Action:** Provide a transaction instance.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05174: A valid file name is required.**

---

**Cause:** The file name was missing or null.

**Action:** Provide a valid file name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05175: A decision point name is required.**

**Cause:** A decision point name was missing or null.

**Action:** Provide a decision point name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05176: The rule dictionary \"{0}\" cannot be found within the current classpath.**

**Cause:** The Rule Dictionary {0} could not be found within the current classpath.

**Action:** Change the classpath or provide a different rule dictionary.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05177: A fact type named \"{0}\" does not exist in the rule dictionary.**

**Cause:** The fact type did not exist in the Rule Dictionary's combined data model.

**Action:** Provide a fact type name that exists.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05178: A decision function named \"{0}\" does not exist in the rule dictionary.**

**Cause:** The Decision Function was found within the combined Rule Dictionary.

**Action:** Provide a different decision function.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05179: naming exception creating transaction**

**Cause:** A naming exception was thrown when attempting to create a transaction.

**Action:** Correct the environment configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05180: naming exception when looking up data source**

---

**Cause:** A naming exception was thrown when attempting to look up the data source.

**Action:** Correct the environment configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05181: error looking up data source**

**Cause:** An error was encountered looking up the data source.

**Action:** See the underlying exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05182: error interacting with rule session**

**Cause:** An error was encountered interacting with the rule session.

**Action:** See the underlying exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05183: error loading the view object**

**Cause:** An error was encountered loading the view object.

**Action:** See the underlying error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05184: error writing decision point dictionary**

**Cause:** An error was encountered writing the decision point dictionary.

**Action:** See the underlying error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05185: error loading or creating decision point dictionary**

**Cause:** An error was encountered loading or creating the decision point dictionary.

**Action:** See the underlying error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05186: error setting up rule session pool for decision point**

---

**Cause:** An error was encountered setting up the rule session pool for the decision point.

**Action:** See the underlying error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05187: error getting a rule session from decision point rule session pool.**

**Cause:** An error was encountered getting a rule session from the decision point rule session pool.

**Action:** See the underlying error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05188: error returning a rule session to decision point rule session pool**

**Cause:** An error was encountered returning a rule session to the decision point rule session pool.

**Action:** See the underlying error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05200: The fully qualified dictionary name is not valid for accessing a dictionary. Each component of the name {0} must begin with a letter and consist of letters, digits, or the underscore character.**

**Cause:** The fully qualified dictionary name was not valid for accessing a dictionary.

**Action:** Change the name so that each component of the name begins with a letter and consist of letters, digits, or the underscore character.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05201: The fully qualified dictionary name is not valid for obtaining a list of dictionary names.**

**Cause:** The fully qualified dictionary name was not valid for obtaining a list of dictionary names.

**Action:** Use dictionary's local name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05202: A repository type must be specified.**

**Cause:** A repository type was not specified.

**Action:** Specify a repository type.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05203: This repository connection has been closed and can no longer be used to access the repository. A new connection must be established.**

**Cause:** The repository connection was closed and could not be used to access the repository.

**Action:** Establish a new connection.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05204: A dictionary with name \\\"{0}\\\" does not exist in repository.**

**Cause:** A dictionary with the given name did not exist in repository.

**Action:** Provide the name of a dictionary that exists.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05205: A dictionary with name \\\"{0}\\\" already exists in repository.**

**Cause:** A dictionary with given name already exists in repository.

**Action:** Provide a name for the dictionary that does not already exist.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05206: There is an error when initializing the repository. Refer to the base exception.**

**Cause:** There was an error initializing the repository.

**Action:** Refer to the base exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05207: There is a repository error. Refer to the base exception.**

**Cause:** A repository error occurred.

**Action:** Refer to the base exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05208: There is a mismatch between the fully qualified name of the dictionary and the name with which it was retrieved.**

---

**Cause:** There was a mismatch between the fully qualified name of the dictionary and the name with which it was retrieved.

**Action:** Ensure that the package and name in the dictionary match the directory structure and rules file name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05209: The dictionary with name \\\"{0}\\\" cannot be saved. The dictionary has already been modified and this version is older than the latest version in the repository. Edit the dictionary again to modify the latest version.**

**Cause:** The dictionary could not be saved because the version in the repository was newer than the version being saved.

**Action:** Edit the dictionary again.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05210: The repository does not support a sandbox feature. Change the application code to test if the sandbox feature is supported and only invoke sandbox operations if it is supported.**

**Cause:** The repository did not support a sandbox feature and a sandbox operation was invoked.

**Action:** Re-code the application to test if the sandbox feature is supported and only invoke sandbox operations if it is supported.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05211: A sandbox named \\\"{0}\\\" already exists and as a result sandbox creation failed. Use the existing sandbox or use a different name.**

**Cause:** A sandbox with the supplied name already exists and as a result sandbox creation failed.

**Action:** Use the existing sandbox or use a different name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05212: The name of the sandbox is missing. Provide a nonempty sandbox name.**

**Cause:** The sandbox name was missing.

**Action:** Provide a nonempty sandbox name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**RUL-05304: The ruleset with the name \\{0}\\ is not in dictionary.**

**Cause:** The ruleset with the name was not in dictionary.

**Action:** Provide the name of a ruleset that exists in the dictionary.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05355: The same location is provided for both dictionary \\{0}\\ and output destination \\{1}\\ . The canonical path is \\{2}\\ .**

**Cause:** The same location was provided for both the dictionary and the output destination.

**Action:** Check both paths to ensure they are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05356: The dictionary path location \\{0}\\ does not exist.**

**Cause:** The dictionary path location does not exist.

**Action:** Provide a path to the dictionary that does exist.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05357: The destination path \\{0}\\ location cannot be written.**

**Cause:** The output destination location cannot be written.

**Action:** Provide a destination that is writable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05400: Another thread updated the in-memory copy of the dictionary. Try your changes again.**

**Cause:** Another thread updated the in-memory copy of the dictionary.

**Action:** Try your changes again.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05401: The path \\{0}\\ does not exist. Ensure that the path exists on the host system.**

**Cause:** The path specified did not exist.

**Action:** Ensure that the path exists on the host system.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**RUL-05403: The parameter \"{0}\" is null. Ensure that the parameter is not null.**

**Cause:** The parameter was null.

**Action:** Ensure that the parameter is not null.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05534: internal error. Item should be one of \"{0}\" but is \"{1}\".**

**Cause:** Item was not one of the required values.

**Action:** Internal error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05576: token: \"{0}\" at \"{1}\" is unterminated**

**Cause:** Token was unterminated.

**Action:** Terminate token.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05577: token: \"{0}\" at \"{1}\" is not a known token**

**Cause:** Token was not a known token.

**Action:** Provide a different token.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05579: token: \"{0}\" at \"{1}\" is an invalid number**

**Cause:** Token was an invalid number.

**Action:** Provide a valid number.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05580: syntax error for token \"{0}\" at column \"{1}\"**

**Cause:** Token contained a syntax error.

**Action:** Correct the syntax error.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05581: token: \"{0}\" at \"{1}\" is an unknown parser error**



---

**Cause:** Token caused an unknown parser error.

**Action:** Correct the error in the expression.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05582: token: `\\{0}\\` at `\\{1}\\` is unmatched**

**Cause:** Token was unmatched.

**Action:** Match token.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05583: A primitive type or a fact type is expected, but neither can be found.**

**Cause:** The parser was expecting the name of a type, but none was found.

**Action:** Select a valid type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05584: The variable `\\{2}\\` must be final to be used here.**

**Cause:** A nonfinal variable was used in a rule condition.

**Action:** Mark the variable as final, or do not use the variable here.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05600: The dictionary `\\{0}\\` must have a DictionaryFinder to resolve dictionary links.**

**Cause:** Dictionary did not have a DictionaryFinder to resolve dictionary links.

**Action:** Provide a DictionaryFinder to resolve dictionary links.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05601: The dictionary cannot be found using link `\\{0}\\`.**

**Cause:** The dictionary could not be found using the provided link.

**Action:** Provide a valid link.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05602: The dictionary link `\\{0}\\` refers to a dictionary with validation warnings.**

---

**Cause:** Dictionary link referred to a dictionary with validation warnings.

**Action:** Provide a dictionary link without validation warnings.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05701: The name cannot be blank. Enter a name.**

**Cause:** The name was blank.

**Action:** Enter a name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05702: The component attempting to be added to the table does not exist within the parent component's tree. Choose a different component to add.**

**Cause:** The component to be added to the table did not exist within the parent component's tree.

**Action:** Choose another component to add.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05703: The rule or decision table must have at least one pattern or test. Add a pattern or a test.**

**Cause:** The rule or decision table had no patterns.

**Action:** Add a pattern.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05704: The pattern must have a fact type. Enter a valid fact type.**

**Cause:** The pattern did not have a fact type.

**Action:** Enter a valid fact type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05706: The pattern variable \"{0}\" is used more than once in the same rule. Change one of the names.**

**Cause:** The pattern variable was used more than once in the same rule.

**Action:** Change one of the names.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**RUL-05707: The priority must be a predefined value such as 'high' or 'low', or a number.**

**Cause:** Priority was not a predefined value or a number.

**Action:** Priority must be a predefined value or a number.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05709: The variable `\\{0}\\` is used more than once in the same rule. Change one of the names.**

**Cause:** The variable was used more than once in the same rule.

**Action:** Change one of the names.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05710: The value chosen, `\\{0}\\`, is not a valid choice for `\\{1}\\` of `\\{2}\\`.**

**Cause:** The value was not a valid choice.

**Action:** Enter a valid choice.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05711: The expression cannot be blank.**

**Cause:** The expression was blank.

**Action:** Enter an expression.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05712: The value `\\{0}\\` of `\\{1}\\` cannot be blank. Select a value.**

**Cause:** The value was blank.

**Action:** Select a value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05713: invalid alias `\\{0}\\`, must begin with a letter and contain only letters, numbers, `\\.\\`, `\\-\\`, `\\_\\`, `\\\"\\`, `\\:\\`, `\\/\\`, and single spaces**

**Cause:** The element contained an invalid alias.

**Action:** Must begin with a letter and contain only letters, numbers, `\\.\\`, `\\-\\`, `\\_\\`, `\\\"\\`, `\\:\\`, `\\/\\` and single spaces.

**Level:** 1

---

Type: ERROR

Impact: Programmatic

**RUL-05714: invalid name \"{0}\", must begin with a letter and contain only letters and numbers**

Cause: The element contained an invalid name.

Action: Must begin with a letter and contain only letters and numbers.

Level: 1

Type: ERROR

Impact: Programmatic

**RUL-05715: The value \"{0}\" is excluded by bucketset \"{1}\".**

Cause: Expression value was excluded by a bucketset.

Action: Choose an allowed value.

Level: 1

Type: ERROR

Impact: Programmatic

**RUL-05716: The function \"{0}\" is not valid here.**

Cause: Function was not valid here.

Action: Provide the name of a valid function.

Level: 1

Type: ERROR

Impact: Programmatic

**RUL-05717: The identifier \"{0}\" is not valid here.**

Cause: Identifier was not valid here.

Action: Provide a valid identifier.

Level: 1

Type: ERROR

Impact: Programmatic

**RUL-05720: data type mismatch for test \"{0}\": {2} {3} {4}**

Cause: There was a data type mismatch for the test.

Action: Provide a different operator or provide different operands.

Level: 1

Type: ERROR

Impact: Programmatic

**RUL-05721: The result type of the expression is \"{2}\" but should be \"{3}\".**

Cause: The result type of the expression is not as expected.

Action: Provide a different expression, or add a cast to the expression.

Level: 1

Type: ERROR

---

**Impact:** Programmatic

**RUL-05724: The array `\"{0}\"` must be followed by `[]`.**

**Cause:** Array was not followed by `[]`.

**Action:** Add `[]` to the end of the array.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05725: The value `\"{0}\"` is not an array and cannot be followed by `[]`.**

**Cause:** The value was not an Array and was not allowed to be followed by `[]`.

**Action:** Remove the `[]` from the value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05726: data type mismatch for operator `\"{0}\"` at position {1}: {2} {3} {4}**

**Cause:** There was a data type mismatch for the operator.

**Action:** Provide a different operator or provide different operands.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05727: incorrect number of parameters for function `\"{0}\"` at {1}**

**Cause:** There was an incorrect number of parameters for function.

**Action:** Provide the correct number of parameters for the function.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05728: The test expression must return true or false, not `\"{0}\"`.**

**Cause:** Test expression must return true or false but did not.

**Action:** Provide a test expression that returns true or false.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05729: The value must be a literal value. Strings must be quoted with double quotes.**

**Cause:** Value was not a literal value.

**Action:** Provide a literal value. Strings must be quoted with `\"\"`.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**RUL-05730: type \"{0}\" may not be used here**

**Cause:** The provided type was not valid for use.

**Action:** Provide a valid type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05731: The nested pattern has an empty nested table. Remove the nested pattern or add nested entries.**

**Cause:** The nested Pattern had an empty NestedTable.

**Action:** Remove the nested Pattern or add nested entries.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05732: form value not set**

**Cause:** Form value not set.

**Action:** Set form value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05733: for a nested SimpleTestTable, incorrect operator \"{0}\" selected**

**Cause:** Nested SimpleTestTable had incorrect operator selected.

**Action:** Select a valid operator.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05735: cannot cast type \"{2}\" to type \"{3}\"**

**Cause:** Could not cast expression type to cast type.

**Action:** Provide a valid cast type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05736: The date \"{0}\" is invalid. It must match the selected calendar format \"{1}\".**

**Cause:** Date was invalid.

**Action:** Provide a date that matches the selected calendar format.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**RUL-05737: The effective start date \{"0\}" must be strictly less than the effective end date {1}.**

**Cause:** Effective start date was not strictly less than the effective end date.

**Action:** Provide an effective start date that is strictly less than the effective end date.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05738: The effective start date \{"0\}" must be greater than or equal to the rule set effective start date \{"1\}".**

**Cause:** Effective start date was not greater than or equal to the rule set effective start date.

**Action:** Provide an effective start date that is greater than or equal to the rule set effective start date.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05739: The effective end date \{"0\}" must be less than or equal to the rule set effective end date \{"1\}".**

**Cause:** Effective end date was not less than or equal to the rule set effective end date.

**Action:** Provide an effective end date that is less than or equal to the rule set effective end date.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05740: The \{"0\}" action does not allow nested actions in its action table. Remove all actions from the nested action table.**

**Cause:** Action table was not empty.

**Action:** The action table is not empty, but should be. Remove all actions from the action table.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05741: The action contains the wrong number of expressions. Re-create the action. If the problem persists, contact Oracle Support Services.**

**Cause:** The action contained the wrong number of expressions.

**Action:** Re-create the action. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**RUL-05742: A calendar form incompatibility detected with forms `\\{0}\\` and `\\{1}\\`. If the calendar form is set to `\\Time\\` on a rule set or any of the rules or decision tables within that ruleset then the calendar form for that entire rule set is restricted to `\\Time\\`.**

**Cause:** Calendar form was incompatible.

**Action:** If the calendar form is set to "Time" on a rule set or any of the rules or decision tables within that ruleset then the calendar form for that entire rule set is restricted to "Time".

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05743: The Action's ExpressionTable is larger than the number of parameters or properties for the Action's Target. Set the value of removed properties or parameters to the empty string and validate the Action again.**

**Cause:** The action's expression table was larger than the number of parameters or properties for the action's target.

**Action:** Set the value of removed properties or parameters to the empty string and validate the Action again.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05744: The action with form `\\expression\\` and value `\\{0}\\` is not a statement. Change the expression to be an assignment statement or method call.**

**Cause:** The Expression action did not contain a statement.

**Action:** Change the expression to be an assignment statement or method call.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05745: The instanceof expression at column {1} is always false.**

**Cause:** The instanceof expression is always false.

**Action:** Revise or remove the the expression.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05746: The instanceof expression at column {1} is always true.**

**Cause:** The instanceof expression is always true.

**Action:** Revise or remove the the expression.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic



---

**RUL-05747: To use the `\\\"new\\\"` operator with property values, fact type `\\\"{0}\\\"` at column {1} must have a visible constructor with no arguments.**

**Cause:** The new operator with property values requires a no argument constructor.

**Action:** Make a no arg constructor for the fact type visible, or use a constructor with arguments rather than property values.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05804: The action `\\\"assign\\\"` requires a variable and an expression. Select a variable from the list and enter an expression for its value.**

**Cause:** Action "assign" did not contain a variable and an expression.

**Action:** Select a variable from the list and enter an expression for its value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05806: The `\\\"{0}\\\"` action requires at least one action in its nested action table. Add a nested action.**

**Cause:** Action table was empty.

**Action:** Add at least one action to this action's nested action table.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05810: The action `\\\"modify\\\"` requires at least one property set.**

**Cause:** Action "modify" did not have at least one property set.

**Action:** Set at least one property for the Action.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05811: The actions `\\\"assert\\\"`, `\\\"retract\\\"`, `\\\"modify\\\"`, and `\\\"synchronized\\\"` require a variable. Select a variable from the list.**

**Cause:** Action type "assert", "retract", "modify", and "synchronized" did not contain a variable.

**Action:** Select a variable from the list.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05814: The program set option list contains invalid values for `\\\"{0}\\\"`.**

**Cause:** Program set option list contained invalid values.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05815: null values are not allowed for key or value put ( {0}, {1} )**

**Cause:** Null values provided for key or value in call to method put.

**Action:** Provide a non-null key or value for put.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05817: The property \"{0}\" is read-only.**

**Cause:** Property was read-only.

**Action:** Do not set the value of this read-only property.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05818: The value for property \"{0}\" must be of type \"{1}\".**

**Cause:** Value for property was of the wrong type.

**Action:** Provide a value of the correct type for the property.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05819: The value \"{0}\" is not a valid property of \"{1}\".**

**Cause:** Property specified was not a valid property of the element.

**Action:** Provide a valid property.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05821: CUSTOM and program set OPTIONS properties cannot be removed**

**Cause:** An attempt was made to remove CUSTOM and program set OPTIONS properties.

**Action:** Do not attempt to remove these properties.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05822: The property \"{0}\" cannot be customized.**

**Cause:** An attempt was made to customize the specified property.

**Action:** Do not attempt to customize this property.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**RUL-05823: RuleSet is not valid, so RL generation is not possible.**

**Cause:** Attempt to generate RL failed because RuleSet failed validation.

**Action:** Correct validation warnings.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05824: Dictionary components cannot be added or removed in customization mode.**

**Cause:** Could not add or remove dictionary components in customization mode.

**Action:** Turn customization mode off to add or remove components.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05830: The decision table bucketset reference cannot be found.**

**Cause:** Decision table bucket reference was not found.

**Action:** Provide a valid bucket reference.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05831: The decision table bucket reference cannot be found.**

**Cause:** Decision table bucket reference not found.

**Action:** Provide a valid bucket reference.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05832: The bucket name \\ "{0} \" is invalid.**

**Cause:** Bucket name was invalid.

**Action:** Provide a valid bucket name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05833: The bucket value contains invalid characters \\ "{0} \".**

**Cause:** Bucket name contained invalid characters.

**Action:** Remove invalid characters in bucket name.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**RUL-05834: The last bucket in the bucketset cannot be removed.**

**Cause:** Could not remove the last bucket in a bucketset.

**Action:** Do not attempt to remove the last bucket in the bucketset.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05835: All rules have \"don't care\" set for condition \"{0}\". Select one or more buckets in one or more condition cells.**

**Cause:** All rules had "don't care" set about condition.

**Action:** Select one or more buckets in one or more condition cells.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05836: The bucketset \"{0}\" has only one bucket. Add one or more buckets.**

**Cause:** Bucketset had only one bucket.

**Action:** Add one or more buckets.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05837: The decision table has no conditions or rules.**

**Cause:** Decision table had no conditions or rules.

**Action:** Add a condition or rule to the decision table.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05838: The decision table has no actions.**

**Cause:** Decision table had no actions.

**Action:** Add an action to the decision table.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05839: The bucketset \"{0}\" has duplicate otherwise bucket named \"{1}\". Delete one of the otherwise buckets.**

**Cause:** Bucketset had duplicate otherwise bucket.

**Action:** Delete one of the otherwise buckets.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**RUL-05840: The decision table rule cannot reference rule \\\"{0}\\\" in both NO CONFLICT and RUN BEFORE lists.**

**Cause:** Decision table rule referenced a rule in both NO CONFLICT and RUN BEFORE lists.

**Action:** Remove the decision table rule from one of NO CONFLICT and RUN BEFORE lists.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05841: The decision table rule cannot reference rule \\\"{0}\\\" in both NO CONFLICT and OVERRIDE lists.**

**Cause:** Decision table rule referenced rule in both NO CONFLICT and OVERRIDE lists.

**Action:** Remove the decision table rule from one of NO CONFLICT and OVERRIDE lists.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05842: The decision table rule cannot reference rule \\\"{0}\\\" in both OVERRIDE and RUN BEFORE lists.**

**Cause:** Decision table rule referenced rule in both OVERRIDE and RUN BEFORE lists.

**Action:** Remove the decision table rule from one of OVERRIDE and RUN BEFORE lists.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05843: The decision table rule cannot specify OVERRIDE or RUN BEFORE on itself.**

**Cause:** Decision table rule cannot specify OVERRIDE or RUN BEFORE on itself.

**Action:** Select a different option.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05846: The bucketset must have a primitive or Calendar data type.**

**Cause:** Bucketset did not have a primitive or Calendar data type.

**Action:** Provide a primitive or Calendar data type for the bucketset.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**RUL-05847: The decision table action parameter \"{0}\" is a duplicate.**

**Cause:** Decision table contained duplicate action parameter.

**Action:** Remove one of the duplicate decision table action parameters.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05848: In a decision table, an \"assign new\" action must be \"always selected\".**

**Cause:** A decision table \"assign new\" action was not always selected.

**Action:** Select a decision table \"assign new\" action.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05849: The bucketset has duplicate bucket value \"{0}\".**

**Cause:** Bucketset had a duplicate bucket value.

**Action:** Delete the duplicate bucket or choose another bucket value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05850: The condition \"{0}\" has type \"{1}\", but has bucketset of type \"{2}\".**

**Cause:** Condition expression's type was incompatible with its bucketset type.

**Action:** Associate a different bucketset with the condition expression.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05851: The decision table has unresolved conflicts.**

**Cause:** The decision table had unresolved conflicts.

**Action:** Display the conflicts and mark each with \"override\", \"run before\", or \"ignore\".

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05852: The decision table has gaps.**

**Cause:** The decision table had gaps.

**Action:** Display the gaps and add rules as needed, or check \"allow gaps\".

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**RUL-05853: Bucket value contains invalid character \\\"{0}\\\".**

**Cause:** Bucket value contained invalid char value.

**Action:** Provide a valid char value for bucket value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05854: The bucket value must be a constant expression.**

**Cause:** The bucket expression was not constant.

**Action:** Set the "constant" property of the bucket expression to "true".

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05855: The rules \\\"{0}\\\" and \\\"{1}\\\" do not conflict. Remove override information.**

**Cause:** There was no conflict between decision table rules.

**Action:** Remove the conflict overriding information.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05856: The parent object of type \\\"{0}\\\" with name \\\"{1}\\\" has more than one \\\"{2}\\\" with value \\\"{3}\\\".**

**Cause:** Two elements had the same name.

**Action:** Provide a different name for one of the elements.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05895: while validating \\\"{0}\\\", found {1} error(s)**

**Cause:** Datamodel element contained validation errors.

**Action:** Correct the errors.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05899: The primitive fact type \\\"{0}\\\" cannot be deleted.**

**Cause:** An attempt was made to delete a primitive fact type.

**Action:** Do not attempt to delete primitive fact types.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**RUL-05902: The built-in function \"{0}\" cannot be deleted.**

**Cause:** An attempt was made to delete a built-in function.

**Action:** Do not attempt to delete the built-in function.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05905: The element \"{0}\" cannot be deleted.**

**Cause:** An attempt was made to delete an element.

**Action:** Do not attempt to delete the element.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05906: A Java property cannot be deleted.**

**Cause:** An attempt was made to delete a Java property.

**Action:** Do not attempt to delete Java properties.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05916: The name \"{0}\" is an RL reserved word.**

**Cause:** An RL reserved word was provided as the name.

**Action:** Provide a different name that is not a reserved word.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05918: The function \"{0}\" has both a body and actions defined. Only one of these should be defined.**

**Cause:** Function had both a body and actions defined.

**Action:** Remove either the body or the defined actions.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05919: The body of function \"{0}\" has to be defined.**

**Cause:** Body of function was empty.

**Action:** Define the body of the function.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic



---

**RUL-05920: The parent object of type `\\ \"{0}\\ \"` with name `\\ \"{1}\\ \"` has more than one `\\ \"{2}\\ \"` with name `\\ \"{3}\\ \"`.**

**Cause:** Two elements had the same name.

**Action:** Provide a different name for one of the elements.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05921: The parent object of type `\\ \"{0}\\ \"` with name `\\ \"{1}\\ \"` has more than one `\\ \"{2}\\ \"` with alias `\\ \"{3}\\ \"`.**

**Cause:** Two elements had the same alias.

**Action:** Provide a different alias for one of the elements.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05922: Linked dictionaries cannot have the same alias `\\ \"{0}\\ \"`.**

**Cause:** Two linked dictionaries had the same alias.

**Action:** Change the alias for one of the linked dictionaries.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05923: Linked dictionaries cannot have the same fully qualified name `\\ \"{0}\\ \"`.**

**Cause:** Two linked dictionaries had the same fully qualified name.

**Action:** Change the name of one of the linked dictionaries.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05924: The alias `\\ \"{0}\\ \"` cannot start with a space.**

**Cause:** Alias started with a space.

**Action:** Change the alias so that it does not start with a space.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05925: The alias `\\ \"{0}\\ \"` cannot end with a space.**

**Cause:** Alias ended with a space.

**Action:** Change the alias so that it does not end in a space.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**RUL-05926: The alias \\\"{0}\\\" contains a double space or invalid character.**

**Cause:** Alias contained a double space or invalid character.

**Action:** Change the alias so that it does not contain a double space or invalid character.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05927: The alias cannot be blank.**

**Cause:** Alias was blank.

**Action:** Provide an alias.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05940: The value of global variable \\\"{0}\\\" is not set.**

**Cause:** The value of the global variable was not set.

**Action:** Set the value of the global variable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05942: The element \\\"{0}\\\" \\\"{1}\\\" must have a type.**

**Cause:** Element did not have a type.

**Action:** Provide a type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05943: The file corresponding to the path \\\"{0}\\\" does not exist. Ensure that the file exists in the file system.**

**Cause:** File corresponding to the path did not exist.

**Action:** Ensure that the file exists in the file system.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05945: initialization of built-in datamodel failed**

**Cause:** Initialization of built-in datamodel failed.

**Action:** If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**RUL-05946: The class not found while initializing built-in datamodel. Ensure that rl.jar is on the classpath.**

**Cause:** The class was not found while initializing built-in datamodel.

**Action:** Ensure that rl.jar is on the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05959: The result type of `\\\"{0}\\\"` cannot be aggregated.**

**Cause:** Invalid result type for aggregate expression.

**Action:** minimum and maximum must be a primitive or Comparable type. sum and average must be a primitive numeric type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05960: An aggregate pattern block must contain one pattern.**

**Cause:** An aggregate pattern block has no patterns or more than one pattern.

**Action:** Add or remove patterns from the aggregate pattern block as needed.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05961: The pattern in aggregate has operator `\\\"{0}\\\"` and form `\\\"{1}\\\"`, should have operator `OPERATOR_FOREACH` and form `FORM_FACT_TYPE`.**

**Cause:** Pattern in aggregate had invalid operator and form combination.

**Action:** Pattern in should use operator `OPERATOR_FOREACH` and form `FORM_FACT_TYPE`.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05962: The aggregate table does not contain an aggregate.**

**Cause:** Aggregate table did not contain an aggregate.

**Action:** Provide an aggregate for the aggregate table.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-05963: The aggregate variable `\\\"{0}\\\"` is used more than once. Change one of the names.**

**Cause:** The aggregate variable was used more than once.

**Action:** Change one of the aggregate variable names.

**Level:** 1

---

Type: ERROR

Impact: Programmatic

**RUL-05964: The aggregate must have an aggregate function. Specify a valid aggregate function.**

Cause: The aggregate did not specify an aggregate function.

Action: Specify a valid aggregate function.

Level: 1

Type: ERROR

Impact: Programmatic

**RUL-05965: The aggregate function `\\{0}\\` does not exist or does not implement oracle.rules.rl.Aggregate.**

Cause: The specified aggregate function did not exist or did not implement oracle.rules.rl.Aggregate.

Action: Provide a valid aggregate function.

Level: 1

Type: ERROR

Impact: Programmatic

**RUL-05966: The aggregate must have a variable set. Enter a variable.**

Cause: The aggregate did not have a variable set.

Action: Specify a variable for the aggregate.

Level: 1

Type: ERROR

Impact: Programmatic

**RUL-05967: The aggregate variable cannot contain a double space.**

Cause: Aggregate variable contained a double space.

Action: Provide an aggregate variable that does not contain a double space.

Level: 1

Type: ERROR

Impact: Programmatic

**RUL-05968: The aggregate function count does not require an expression.**

Cause: Aggregate function count did not require an expression.

Action: Remove the expression set for the count function expression.

Level: 1

Type: ERROR

Impact: Programmatic

**RUL-05969: cannot parse dictionary XML source**

Cause: Dictionary source was not valid XML.

Action: Provide a valid XML dictionary.

Level: 1

---

**Type:** ERROR

**Impact:** Programmatic

**RUL-08000: No registration exists for \\\"{0}\\\"**

**Cause:** No RepositoryConnection implementation was available for the specified key.

**Action:** Verify that the key is correct and that the corresponding RepositoryConnection was successfully registered.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-08001: invalid or missing registration**

**Cause:** A RepositoryConnection registration was null or one of its properties was null (not specified).

**Action:** Verify that the key is correct and that the corresponding RepositoryConnection was successfully registered.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-08002: unable to load repository store add-in class \\\"{0}\\\", the store is unavailable.**

**Cause:** An error was encountered in loading the specified RepositoryConnection implementation class.

**Action:** Verify that the class is available on the class path.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-08003: repository connection factory initialization failure**

**Cause:** An error was encountered initializing the RepositoryConnection factory.

**Action:** Investigate the exception that was logged.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-08201: missing initialization property for key \\\"{0}\\\"**

**Cause:** A required initialization parameter was missing.

**Action:** Provide the missing initialization parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-08202: error accessing file \\\"{0}\\\"**

**Cause:** An I/O error occurred accessing the file repository.

---

**Action:** The nested exception specifies the root cause. Investigate and resolve.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-08203: null document**

**Cause:** A null XML Document was supplied.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-08204: File \\\"{0}\\\" does not exist.**

**Cause:** The specified file repository could not be found.

**Action:** Verify that the path to the file is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-08205: unable to rename \\\"{0}\\\" so that it can be replaced. This can be caused by another rules based application reading the repository at the same time as this attempt to update it. The operation may be retried. If this error persists, then some other application is keeping the repository open.**

**Cause:** An attempt to rename the original repository file so that the new one can be written failed.

**Action:** Verify that it is not being accessed by another application and then retry.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-08206: unable to rename updated file \\\"{0}\\\" to \\\"{1}\\\". The repository update failed. The old repository content is in the file \\\"{2}\\\". The updated repository content is in the file \\\"{0}\\\". To recover from this error, manually rename the file \\\"{0}\\\" to \\\"{1}\\\".**

**Cause:** An attempt to rename the new repository file to the correct name failed.

**Action:** Recover manually by renaming the files as directed in the error message.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-08207: unable to delete the file \\\"{0}\\\" which contains old repository content, it may be deleted manually**

**Cause:** An attempt to delete the old, renamed repository file failed.

**Action:** Recover by manually deleting the file as directed in the error message.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**RUL-08300: The required MDS instance name has not been specified.**

**Cause:** The MDS instance name was not provided.

**Action:** Provide the MDS instance name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-08301: More than one MDS configuration specifier is provided. Only one of a file path, a configuration URL, or an MDSSession instance can be provided.**

**Correct by removing all but one of these.**

**Cause:** Conflicting MDS configuration data was provided.

**Action:** Resolve the conflicts.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-08302: An MDS instance with name \\\"{0}\\\" does not exist. Either correct the MDS instance name or supply either the MDS file repository path or the MDS configuration URL.**

**Cause:** An MDS instance with the supplied name did not exist.

**Action:** Supply a name of an existing MDS instance.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-08303: no dictionary supplied**

**Cause:** A null rule dictionary XML document was supplied.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**RUL-08304: The MDS file repository path is not a string.**

**Cause:** The path to the file-based MDS repository was not a string.

**Action:** Provide a valid file path.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-08305: The MDS configuration URL is not a string.**

**Cause:** The URL to an MDS configuration file was not a string.

**Action:** Provide a URL.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-08306: The MDS session is not an instance of MDSSession.**

**Cause:** The object passed as an MDSSession to use was not an instance of MDSSession.

**Action:** Provide a valid instance of MDSSession.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-08307: The MDS instance does not have persistence layer configured.**

**Cause:** The MDSInstance did not have a persistence layer configured.

**Action:** Check that MDS is configured correctly in the application.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-08308: The MDS configuration does not contain a namespace that included the expected path \\\"{0}\\\".**

**Cause:** The MDS configuration did not contain a namespace mapping that included the expected path.

**Action:** Check that MDS is configured correctly in the application.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-09002: failed to execute RL code generated from dictionary: {0}**

**Cause:** The RL code generated from the dictionary failed to execute.

**Action:** See base exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-09003: element is null: parentType0={0} , key0= {1} , valFrom0= {2} , to= + {3}**

**Cause:** A method in the SDK returned null.

**Action:** None.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-09004: could not retrieve RuleComponent advanced expression**

**Cause:** Problem retrieving advanced expression RuleComponent.

**Action:** None.



---

**Level: 1**

**Type: ERROR**

**Impact: Programmatic**

**RUL-09005: failed to connect to origin repository for location {0} , root cause: {1}**

**Cause:** Failed to connect to origin repository.

**Action:** See base exception.

**Level: 1**

**Type: ERROR**

**Impact: Programmatic**

**RUL-09006: failed to connect to origin dictionary, name {0} version {1} , root cause: {2}**

**Cause:** Failed to open origin dictionary.

**Action:** See base exception.

**Level: 1**

**Type: ERROR**

**Impact: Programmatic**

**RUL-09007: failed to close to origin repository, root cause: {0}**

**Cause:** Failed to close to origin repository.

**Action:** See base exception.

**Level: 1**

**Type: ERROR**

**Impact: Programmatic**

**RUL-09008: failed to saveAs resulting dictionary, package: {0} dictionary: {1}**

**Cause:** Failed to saveAs migrated dictionary.

**Action:** Check input parameters and source dictionary for validity.

**Level: 1**

**Type: ERROR**

**Impact: Programmatic**

**RUL-09009: destination directory {0} could not be created**

**Cause:** Failed to connect to destination repository

**Action:** See base exception.

**Level: 1**

**Type: ERROR**

**Impact: Programmatic**

**RUL-09010: dictionary: {0}:: {1} already exists, failed**

**Cause:** Dictionary indicated already exists.

**Action:** Remove the existing dictionary or provide a different name.

**Level: 1**

**Type: ERROR**

---

**Impact:** Programmatic

**RUL-09011: failed to create destination dictionary {0} {1} because {2}**  
**Cause:** Failed to create destination dictionary.  
**Action:** See base exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-09012: failed to load ruleset {0} from origin dictionary, root cause: {1}**  
**Cause:** Failed to load ruleset.  
**Action:** See base exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-09013: The origin and destinations are not set.**  
**Cause:** The origin and destinations are not set.  
**Action:** Set both the origin and destination locations.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-09014: Classpath and XML schema properties are not set**  
**Cause:** Classpath and XML schema properties are not set.  
**Action:** Specify the classpath and XML schema properties.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-09015: unable to convert pattern operator: {0}**  
**Cause:** The pattern operator was unable to be migrated.  
**Action:** Check the origin dictionary for validity.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-09016: key {0} is not valid for SDK2 so skipping, message is: {1}**  
**Cause:** The key was not a valid key for SDK2.  
**Action:** None necessary. Some properties in SDK are not valid in SDK2.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-09017: key in ruleset processing: {0} is a {1} parent is a {2}**

---

**Cause:** The value of a key in the dictionary was not of the correct type.

**Action:** Check source dictionary for validity.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-09018: missing arguments for WebDav: must supply either Oracle Wallet source or WebDAV name and password**

**Cause:** Missing arguments for WebDav.

**Action:** Supply either Oracle Wallet source or WebDAV name and password.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-09019: missing arguments for WebDav proxy, must supply a host, a port, and either a Oracle Wallet source or proxy name and password**

**Cause:** Missing arguments for WebDav proxy.

**Action:** Supply the proxy access values.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-09020: error: to= {0} , from= {1} , fromparent= {2}**

**Cause:** RuleComponent or DictionaryComponent were null.

**Action:** None.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-09021: errors ({0}) in conversion: {1}**

**Cause:** There were errors in the conversion.

**Action:** See base exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-09022: failed to get RuleSet, internal error: {0}**

**Cause:** The migration failed to retrieve the indicated rule set.

**Action:** Check that the ruleset exists. Also see base exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-09023: destination ExpressionTable is smaller than origin for target {0} : {1} > {2}**

---

**Cause:** ExpressionTable is the wrong size.  
**Action:** None.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic

**RUL-09024: invalid PROP\_FORM value: {0}**  
**Cause:** Form value was invalid.  
**Action:** Check the validity of the origin dictionary.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic

**RUL-09025: constraint {0} was not migrated, regular expression constraint does not have an equivalent component in SDK2**  
**Cause:** Source dictionary contained a regular expression constraint.  
**Action:** None. Regular expression constraints do not have an equivalent structure in SDK2.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic

**RUL-09026: value {0} could not be added to bucketset {1}**  
**Cause:** The value was invalid to add to the bucketset.  
**Action:** Ensure that the value is valid or add it manually after migration.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Programmatic

**RUL-09030: Number of {0} : {1}**  
**Cause:** None.  
**Action:** None.  
**Level:** 1  
**Type:** NOTIFICATION  
**Impact:** Programmatic

**RUL-09033: destination written, dictionary: {0} in package: {1}**  
**Cause:** None.  
**Action:** None.  
**Level:** 1  
**Type:** NOTIFICATION  
**Impact:** Programmatic

**RUL-09034: origin and destination repositories may not be the same**

---

**Cause:** The Origin and Destination Repositories were the same.

**Action:** Provide different repositories for the origin and destination.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-09035: no origin repository connection, open an origin repository**

**Cause:** No origin repository connection.

**Action:** Open an origin repository.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-09036: origin dictionary not set, open an origin dictionary.**

**Cause:** Origin dictionary was not set.

**Action:** Set the origin dictionary.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-09037: destination dictionary not set, open a destination dictionary.**

**Cause:** Destination dictionary not set.

**Action:** Set the destination dictionary.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-09038: the {0} property has not been set, set this property**

**Cause:** Property indicated was not set.

**Action:** Set the indicated property.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-09039: the element {0} has been set to an invalid value {1}**

**Cause:** The element indicated was set to an invalid value.

**Action:** Set a valid value for the element.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-09040: destination dictionary name and destination package must be null or MIGRATE\_ALL when origin dictionary is MIGRATE\_ALL**

---

**Cause:** Destination dictionary name and destination package was not null or MIGRATE\_ALL.

**Action:** Set the value to null or MIGRATE\_ALL.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**RUL-09043: an exception occurred {0}, check root exception**

**Cause:** An exception occurred.

**Action:** See base exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

## SDF-10001 to SDF-10601

**SDF-10001: Object missing from tree :**

**Cause:** TODO

**Action:** TODO

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**SDF-10201: Error instantiating application module**

**Cause:** TODO

**Action:** TODO

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**SDF-10401: Exception during Extract**

**Cause:** TODO

**Action:** TODO

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**SDF-10601: An error has occurred**

**Cause:** TODO

**Action:** TODO

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics





---

## SDP-10111 to SDP-30017

**SDP-10111: Exception when converting to string. Reason: {0}**

**Cause:** Internal error

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-10113: Property class {0} was not found.**

**Cause:** Malformed command-service.xml.

**Action:** Correct command-service.xml.

**Level:** 1

**Type:** WARNING

**Impact:** Process

**SDP-10115: Missing name element for command.**

**Cause:** Malformed command-service.xml.

**Action:** Correct command-service.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-10116: Object evicted from cache "{0}". Increase the size of the cache or change the expiry delay. Key = "{1}", value = "{2}".**

**Cause:** An object has been evicted from the cache since the cache is too small.

**Action:** Increase the size of the cache or change the expiry delay.

**Level:** 1

**Type:** WARNING

**Impact:** Process

**SDP-10195: Failed to read commands from file "{1}". Reason: {0}.**

**Cause:** Reading and/or parsing of commands failed.

**Action:** Correct the command description.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**SDP-10328: Failed to load the jmxframework.**

**Cause:** Internal Error, possibly misconfiguration or missing jars.

**Action:** Confirm JMX framework is configured / set up properly.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-11051: Error when looking up userservice.**

**Cause:** The J2EE application SubscriberDataServices may not be deployed or started.

**Action:** Ensure that the J2EE application SubscriberDataServices is running.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-11052: Error when creating userservice.**

**Cause:** The J2EE application SubscriberDataServices may not be deployed or started.

**Action:** Ensure that the J2EE application SubscriberDataServices is running.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-11180: No value for "{0}" was provided.**

**Cause:** A configuration value for the indicated property was not specified in the ejb-jar.xml file for the subscriberdataservice application.

**Action:** Specify the corresponding property.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-11185: Error performing SQL operation.**

**Cause:** A SQL operation against the database failed.

**Action:** Verify that the database is accessible and correctly configured.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-11186: Format error in public identity stored in the database.**

**Cause:** A public identity stored in the database is not a valid SIP URI.

**Action:** Correct the public identity.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**SDP-11194: Failed to get ejb environment property "{0}". Reason: {1}.**

**Cause:** The value of the given JNDI name is not in a proper format.

**Action:** Ensure that the value of the JNDI name is a boolean (that is, true or false).

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-11209: Failed to get an instance of {0}. Reason: {1}.**

**Cause:** Installation is not properly configured.

**Action:** Verify installation.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-11210: Unable to fetch verifier for "{0}". Crypto Scheme not supported.**

**Cause:** User in OID not configured properly.

**Action:** Correct the configuration of OID.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-11211: Unable to fetch verifier for "{0}". User without reversible password.**

**Cause:** User in OID not configured properly.

**Action:** Correct the configuration of OID.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-11212: Unable to fetch verifier; user name missing.**

**Cause:** User in OID not configured properly.

**Action:** Correct the configuration of OID.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-11213: Failed to obtain an error code for dynamic verifier. Reason: {0}.**

**Cause:** Problems accessing OID

**Action:** Verify the availability of OID.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**SDP-11214: Invalid response control for "{0}"**

**Cause:** User in OID not configured in a proper way.

**Action:** Correct the configuration of OID.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-11216: No {0} attribute found for verifier.**

**Cause:** User in OID not configured properly.

**Action:** Correct the configuration of OID.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-11217: Empty password attribute found for verifier.**

**Cause:** User in OID not configured properly.

**Action:** Correct the configuration of OID.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-11223: Invalid password format for LDAP credentials**

**Cause:** The format of the LDAP password is not recognized.

**Action:** Verify the configuration of the OID.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-11225: The function with ObjectName "{0}" is not a valid math function.**

**Cause:** Configuration of LockoutService uses a math function that is not recognized.

**Action:** Correct the configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-11231: Could not create ObjectName for LoginFailure pattern "{0}". Reason: {1}.**

**Cause:** Misconfigured installation.

**Action:** Correct the configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-11237: Failed to setup radius client pool. Reason: {0}.**

---

**Cause:** Configuration of Radius Client pool is probably faulty.

**Action:** Verify and correct configuration of Radius Client pool.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-25001: An unexpected exception was caught.**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25002: Unable to create JNDI Context**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details. Check the JNDI Context initialization parameters.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25003: Unable to create an instance of Driver Locator**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25005: Failed to create Sending Core instance**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25006: Failed to remove an EJB instance**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25007: An error occurred while processing an outbound message.**

---

**Cause:** The outbound JMS message does not contain a valid message or request information.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25008: An unexpected error occurred while processing an outbound message.**

**Cause:** An unexpected exception has occurred while processing the outbound message.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25009: An error occurred while storing a message.**

**Cause:** An unexpected exception has occurred while processing the message.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-25010: An error occurred while sending an outbound message.**

**Cause:** An unexpected exception has occurred while processing the outbound message.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25011: An error occurred while transforming an outbound message.**

**Cause:** An unexpected exception has occurred while processing the outbound message.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25012: An error occurred while processing error statuses.**

**Cause:** An unexpected exception has occurred while processing error statuses.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**SDP-25015: There are no transformed messages of message {0} for recipients {1}.  
Skipping message delivery to these recipients.**

**Cause:** An unexpected exception has occurred while transforming an outbound message.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25020: Unable to schedule a timed failover event**

**Cause:** An unexpected exception has occurred while scheduling a timed failover event.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25021: An error occurred while processing a timed failover event**

**Cause:** An unexpected exception has occurred while processing a timed failover event.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25030: Unable to schedule a timer to refresh the driver locator cache.**

**Cause:** An unexpected exception has occurred while scheduling a timer to refresh the driver cache.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SDP-25031: Unable to refresh the driver locator cache.**

**Cause:** An unexpected exception has occurred while refreshing the driver locator cache.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SDP-25032: An error occurred while registering driver information {0}.**

**Cause:** An unexpected exception has occurred while registering the driver information.

**Action:** Check the stack trace for more details.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SDP-25033: An error occurred while unregistering driver information {0}.**

**Cause:** An unexpected exception has occurred while unregistering the driver information.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SDP-25034: There are total {0} registered User Messaging Drivers. Driver(s): {1}**

**Cause:** A Messaging Driver registered with the Messaging Server

**Action:** None

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**SDP-25035: Messaging store not found.**

**Cause:** An unexpected exception has occurred while attempting to find the messaging store.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-25037: Error while retrieving configuration property: {0}.**

**Cause:** Unable to read from the messaging server configuration file 'configuration/appconfig.xml' or the named property does not exist.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SDP-25038: Error while loading the messaging server configuration properties. Falling back to default configuration.**

**Cause:** Unable to read from the messaging server configuration file 'configuration/appconfig.xml'.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**SDP-25040: Unable to create an instance of CommandReceiverBean.**



---

**Cause:** An unexpected exception has occurred while attempting to process a command.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-25042: An error occurred while processing a command message.**

**Cause:** An unexpected exception has occurred while attempting to process a command.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SDP-25043: An unknown command message was received, ignoring: {0}.**

**Cause:** The engine received an unknown command message and was unable to process the command.

**Action:** Check the current log file for additional details, if the system is not functional. Otherwise, ignore this warning.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**SDP-25055: Failed to create Receiving Core instance.**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25057: An error occurred while processing an inbound message.**

**Cause:** The inbound JMS message does not contain a valid message.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25058: An unexpected error occurred while processing an inbound message.**

**Cause:** An unexpected exception has occurred while processing the inbound message.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**SDP-25059: An unknown JMS message is received, ignoring: {0}.**

**Cause:** The engine received an unknown JMS message and was unable to process it.

**Action:** Check the current log file for additional details, if the system is not functional. Otherwise, ignore this warning.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-25060: There is no application that has registered this address as an access point. Message will not be delivered.**

**Cause:** There is no application that has registered this recipient address as an access point.

**Action:** Check the current log file for additional details, if the system is not functional. Otherwise, ignore this warning.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-25061: An unexpected error occurred while processing inbound message statuses.**

**Cause:** An unexpected exception has occurred while attempting to process inbound message statuses.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25062: Cannot correlate status with any message; storing for possible later processing.**

**Cause:** An inbound status arrived in an unexpected order.

**Action:** Check the current log file for additional details, if the system is not functional. Otherwise, ignore this warning.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-25063: There is no application client information for this status: {0}**

**Cause:** There is no application client information associated with this access point holder.

**Action:** Check the current log file for additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**SDP-25064: An unexpected error occurred while recording a status processing update.**

**Cause:** An unexpected exception has occurred while attempting to record a status processing update.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25065: An unexpected error occurred while sending a message to failover address {0}.**

**Cause:** An exception has occurred while sending out a failover message.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25066: An unexpected error occurred while processing an outbound message status.**

**Cause:** An unexpected exception has occurred while attempting to process an outbound message status.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25070: Unable to retrieve messaging engine sending and/or receiving queues from configuration.**

**Cause:** A severe configuration error has occurred and the system is not functional.

**Action:** Check the messaging engine configuration and the stack trace, if available, for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SDP-25080: An error occurred while converting a message.**

**Cause:** An invalid message content or inappropriate converter was used to perform the message conversion.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25082: No predicates and/or devices matched. Ignoring converter rule (MIME type: {0}, delivery type: {1}, predicate: {2}).**

**Cause:** An invalid message converter rule was provided.

---

**Action:** Check the current log file for additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25083: Message content is not an instance of MimeMultipart**

**Cause:** An invalid message content was provided to this converter.

**Action:** Check the current log file for additional details. Check User Messaging Service Javadoc on OTN for more information on sending MimeMultipart messages.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25085: Message {0} has a nonunique Message ID or recipient, and does not look like a redelivery attempt.**

**Cause:** A message was sent or received that appears to be a duplicate of an already processed message; re-enqueuing message with delay specified.

**Action:** Ensure that messages are assigned unique Message IDs.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-25088: Unable to refresh the driver locator cache, due to the following error: {0}**

**Cause:** An unexpected error has occurred while refreshing the driver locator cache.

**Action:** Check the reported error message and correct any configuration problems.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SDP-25100: An unexpected exception was caught.**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25101: Caught an unexpected database exception.**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** WARNING

---

**Impact:** Data

**SDP-25102: TopLink database platform class {0} not found. Using default database platform.**

**Cause:** No TopLink database platform class is available with the configured name.

**Action:** Add new or update existing <DatabasePlatform> with a valid TopLink database platform class in usermessagingserver/configuration/appconfig.xml.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**SDP-25103: Could not instantiate TopLink database platform class.**

**Cause:** An exception has occurred while instantiating the TopLink database platform class.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**SDP-25104: Initializing Messaging Store in transient mode.**

**Cause:** Initializing Messaging Store in transient mode. Message history will not persist across server restarts.

**Action:** n/a

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**SDP-25105: Initializing Messaging Store in {0} mode.**

**Cause:** Initializing Messaging Store in persistent mode. Message history will persist across server restarts.

**Action:** n/a

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**SDP-25106: Conflicting recipient IDs for Message {0}.**

**Cause:** A conflict between recipient identifiers has been detected.

**Action:** Ensure that applications are using unique Message IDs.

**Level:** 1

**Type:** WARNING

**Impact:** Programmatic

**SDP-25107: Message ID {0} in Status object does not match previously recorded Message ID {1}.**

**Cause:** A status object returned from a driver contained a different Message ID than expected.

---

**Action:** Ensure that drivers are mapping Gateway IDs to Message IDs correctly.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**SDP-25109: Could not initialize persistence context.**

**Cause:** An exception has occurred while initializing the persistence context.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**SDP-25110: An error occurred while initializing persistence session, with the following error message: {0}**

**Cause:** An error occurred while attempting to initialize and log in to the TopLink persistence session.

**Action:** Check the reported error message and correct any configuration or database availability problems.

**Level:** 1

**Type:** WARNING

**Impact:** Session

**SDP-25200: An unexpected exception was caught.**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25201: No endpoint URL is available for the web service callback operation.**

**Cause:** No endpoint URL is available for the web service listener callback.

**Action:** Ensure a valid callback URL is specified when registering a message or status listener.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-25250: An unexpected exception was caught.**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25251: Messaging Exception while processing Parlay X request.**

---

**Cause:** A Messaging Exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-25252: Exception while initializing Parlay X Messaging servlet.**

**Cause:** An exception occurred while initializing the Parlay X Messaging servlet.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**SDP-25253: Exception while initializing Parlay X Messaging content servlet.**

**Cause:** An exception occurred while initializing the Parlay X Messaging content servlet.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**SDP-25254: Exception while processing SOAP attachment content.**

**Cause:** An exception occurred while processing message content in a SOAP attachment.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-25255: Message contains multiple attachments. All but first attachment will be ignored.**

**Cause:** The client application sent a message with multiple attachment parts.

**Action:** Client applications should send one attachment part per message. Complex content should be sent as a MIME Multipart object.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-25256: Permission denied.**

**Cause:** The client application did not have permission to invoke the attempted operation.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** TRACE

---

**Impact:** Security

**SDP-25257: Error initializing JAXP DatatypeFactory. Some data types may not be converted correctly.**

**Cause:** Could not acquire instance of class javax.xml.datatype.DatatypeFactory. Marshalling/unmarshalling of some XML elements may not happen correctly.

**Action:** Ensure that the server's JAXP framework is configured correctly.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**SDP-25258: Error initializing the Servlet Endpoint Context. Parlay X module will not be able to service requests correctly.**

**Cause:** Could not initialize the Servlet Endpoint Context.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25259: Error initializing access to Messaging Server. Parlay X module will not be able to service requests correctly.**

**Cause:** Could not initialize internal Messaging Client endpoint.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25300: An unexpected exception was caught.**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25301: JNDI context is null.**

**Cause:** JNDI context was null.

**Action:** See the Javadoc on Oracle Technology Network (OTN) for more information about how to instantiate a JNDI context.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25302: EJB home for UserPrefsService is null.**

**Cause:** EJB home for UserPrefsService is null.

**Action:** See the Javadoc on Oracle Technology Network (OTN) for more information about how to specify an EJB home.



---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25303: Unable to connect to User Messaging Service (UMS) server at {0}.**

**Cause:** EJB Naming Exception was caught when creating a UserPrefsServices object.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25304: EJB Remote Exception was caught at server {0}**

**Cause:** EJB Remote Exception was caught.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25305: EJB Create Exception was caught at server {0}**

**Cause:** EJB Create Exception was caught.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25306: XML Document object is null.**

**Cause:** XML Document object is null.

**Action:** Specify a valid XML document object.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25307: No file to upload. File name is not set.**

**Cause:** The file name to be uploaded was not set.

**Action:** Invoke setFileName() to set the file name.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25308: The file, {0}, cannot be read.**

**Cause:** The file cannot be read.

**Action:** Check the file.

**Level:** 1

---

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25309: File not found: {0}**

**Cause:** The file with the given file name does not exist.

**Action:** Check to see if the path and file name are correct. File name must be in /path/filename or file://path/filename format.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25310: The URL is malformed: {0}**

**Cause:** The URL is malformed.

**Action:** The URL must be in file://path/filename format.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25311: The document cannot be uploaded. Parser and stack are out of sync. Tag name: {0} Local name: {1}**

**Cause:** The document cannot be uploaded because parser and stack were out of sync.

**Action:** Fix mismatched tags.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25312: Provisioning Exception was caught.**

**Cause:** Provisioning Exception was caught.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25313: Null Pointer Exception was caught.**

**Cause:** Null Pointer Exception was caught.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25314: Rule {0} is already defined.**

**Cause:** Rule with the same name was already defined.

**Action:** Choose a different rule name to avoid conflict.

**Level:** 1

---

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25316: Input parameter, UserPrefsServices, is null.**

**Cause:** The UserPrefsServices object was null.

**Action:** Pass a valid UserPrefsServices object as a parameter. Check User Messaging Service Javadoc on OTN for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25317: Required input parameter, UserID, is null.**

**Cause:** Failed to invoke method, because required input parameter, UserID, is null.

**Action:** Pass a valid UserID. Check User Messaging Service Javadoc on OTN for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25318: Invalid input parameter. DeviceAddress object is null.**

**Cause:** Input parameter, DeviceAddress object, is null.

**Action:** Pass a valid DeviceAddress object. Check User Messaging Service Javadoc on OTN for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25319: UserRuleSet is not set. Call initProcessor() first.**

**Cause:** UserRuleSet object is null.

**Action:** Call initProcessor() first to complete initialization.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25320: Rule Set is null.**

**Cause:** The Rule Set was not available or could not be created.

**Action:** Use a valid Rule Set.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25321: XML String representing the Rule Set is null.**

**Cause:** The XML document element representing the Rule Set was null or empty.

**Action:** Use a valid Rule Set XML element.

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25322: User Rule Set is null.**

**Cause:** The User Rule Set was not available or could not be created.

**Action:** Use a valid User Rule Set object.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25323: User Rule Set is inconsistent. See exception for more details.**

**Cause:** User Rule Set is inconsistent.

**Action:** Check User Rule Set for consistency.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25324: XML document is invalid. See exception for details.**

**Cause:** XML document is invalid. See stacktrace for more details.

**Action:** Validate the XML document.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25325: Cannot serialize Rule Session.**

**Cause:** Cannot serialize Rule Session, which is not critical.

**Action:** No action needed.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-25326: Filter XML is null.**

**Cause:** The Preference Rules were missing or inconsistent.

**Action:** Use a well-formed User Preference XML document.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25327: Cannot create Rule Session.**

**Cause:** Cannot create Rule Session.

**Action:** No action needed.

**Level:** 1

**Type:** WARNING

---

**Impact:** Requests/Responses

**SDP-25328: UserPrefsException was caught.**  
**Cause:** UserPrefsException was caught.  
**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-25329: Rule {0} does not exist.**  
**Cause:** The expected rule was not found.  
**Action:** Check the rule by name on the User Preference page.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25330: Business Term Type has changed.**  
**Cause:** Business Term Type has changed.  
**Action:** Recheck the Preference Rules.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-25331: Cannot instantiate User Prefs Services.**  
**Cause:** Cannot instantiate User Prefs Services due to an initialization error.  
**Action:** Check User Prefs Services configuration such as DataSource and TopLink DB Platform.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-25332: Directory for User Prefs Services File Persistence does not exist.**  
**Cause:** Directory for User Prefs Services File Persistence does not exist.  
**Action:** System will try to create the directory.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-25333: invalid directory: {0}**  
**Cause:** The given path was not a valid directory.  
**Action:** Specify a valid directory, not a file.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

---

**SDP-25334: Device name is null.**

**Cause:** Device name is null.

**Action:** Provide a valid Device name.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25335: invalid user ID: {0}**

**Cause:** An invalid user ID was specified.

**Action:** Specify a valid user ID.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-25336: Input parameter, UserPrefsObject, is null.**

**Cause:** Required parameter, UserPrefsObject, is null.

**Action:** Provide a valid UserPrefsObject.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25337: Failed to move a rule: origin rule number is out of the range of existing rules.**

**Cause:** Origin rule number is not valid.

**Action:** Specify a valid rule number.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25338: Cannot find object to update: {0}**

**Cause:** Cannot find object to update.

**Action:** Could be a problem in implementing persistence.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25339: Object already exists.**

**Cause:** Tried to persist an object that already exists.

**Action:** To overwrite existing value, use '-overwrite' flag.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25340: Object not found.**

---

**Cause:** Tried to remove an object that does not exist.

**Action:** (None)

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25341: The order of calling methods is wrong.**

**Cause:** The order of calling methods is wrong.

**Action:** Check the order of the methods being called.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25342: Cannot find default address for user {0}.**

**Cause:** The default address of that user was not set.

**Action:** Check that default address is set from UserPreference Administrator page.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25343: No devices are defined.**

**Cause:** Tried to call delivery preferences without defining devices.

**Action:** Define devices for use with delivery preferences.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25344: Invalid action {0} is found and ignored.**

**Cause:** An invalid action was detected.

**Action:** Use one of the valid actions: BROADCAST, FAIL\_OVER, and DO\_NOT\_SEND.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-25345: Runtime exception was caught.**

**Cause:** Runtime exception was caught.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**SDP-25346: No configured Business Terms are available, only system terms will be used.**

**Cause:** Business Term configuration could not be read.

**Action:** Ensure that business term configuration is correct

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**SDP-25347: Device {0} cannot be added because it is present in the list.**

**Cause:** A device was present in the list already.

**Action:** Ensure that the device to be added is not in the device list.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**SDP-25348: Failed to move a device: device ID index number is out of the range of device list.**

**Cause:** Device ID index number is not valid.

**Action:** Specify a valid device ID index number.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25349: Name of rule is not set.**

**Cause:** Rule name was not set.

**Action:** Set the name of the rule.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25350: FilterOperation of a rule is not set.**

**Cause:** FilterOperation of a rule was not set.

**Action:** Set the FilterOperation of the rule.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25351: ActionOperation of a rule is not set.**

**Cause:** ActionOperation of a rule was not set.

**Action:** Set the ActionOperation of the rule.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses



---

**SDP-25352: Condition of a rule is not set.**

**Cause:** Condition of a rule was not set.

**Action:** Set the condition of the rule.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25353: unable to send a BROADCAST message because no address is set**

**Cause:** An address has not been set for the BROADCAST action.

**Action:** Set at least one address for the BROADCAST action.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25354: A failover address is not set for the FAIL\_OVER action.**

**Cause:** An address has not been set for the FAIL\_OVER action.

**Action:** Set at least one address for the FAIL\_OVER action.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25355: error while loading the business rule terms configuration**

**Cause:** The business rule terms configuration file configuration/businessterms.xml could not be read.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**SDP-25356: Cannot persist device address {0} for user GUID {1}, because one already exists.**

**Cause:** An identical device address already exists.

**Action:** Remove the conflicting device address, overwrite it, or specify a different address.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25357: Cannot persist rule set for user GUID {0}, because one already exists.**

**Cause:** A rule set already exists for this user.

**Action:** Remove the conflicting rule set, or overwrite it.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**SDP-25358: Cannot upload rule set for user GUID {0}, because one already exists.**

**Cause:** A rule set already exists for this user.

**Action:** Try uploading the user messaging preferences using merge option 'overwrite' or 'append' (refer to command help for details).

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25359: Cannot upload user device for user GUID {0}, because one already exists.**

**Cause:** A user device already exists for this user.

**Action:** Try uploading the user messaging preferences using merge option 'overwrite' or 'append' (refer to command help for details).

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25360: Initializing User Messaging Preferences services.**

**Cause:** User Messaging Preferences services were initialized as part of application startup or deployment.

**Action:** None.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Other

**SDP-25361: The Java VM does not support the encoding {0}.**

**Cause:** The Java VM does not support the encoding used for XML string representing the RuleSet.

**Action:** Check your server Java VM and make sure it supports the encoding.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25362: This User Preference object cannot be deleted because it is backed by the user profile in the identity store: {0}.**

**Cause:** An attempt was made to delete a read-only object backed by the user profile in the identity store.

**Action:** None.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25363: No UserRuleSet exists for userID {0}.**

**Cause:** The user does not have a UserRuleSet.

**Action:** Check spelling of user ID.

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25364: setFilterOperation has not been called.**

**Cause:** Incorrect calling sequence.

**Action:** Invoke method setFilterOperation() first.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25365: Condition does not exist: {0}**

**Cause:** Condition cannot be found.

**Action:** Check spelling of condition name or ID.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25366: Source parameter is greater than the number of conditions.**

**Cause:** Source parameter is out of range.

**Action:** Provide correct source parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25367: Error creating FilterCondition, type {0} is not valid.**

**Cause:** Incorrect type has been found.

**Action:** Use correct type.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25368: Term {0} is not valid.**

**Cause:** Term is not valid.

**Action:** Use a valid term.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25369: Term of type {0} does not accept operation {1}.**

**Cause:** Unmatched type and operation.

**Action:** Use matching type and operation.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**SDP-25370: Method setFilterTerm() has not been called.**

**Cause:** setFilterTerm() method has not been called prior to current method invocation.

**Action:** Invoke setFilterTerm() first.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25371: FilterTerm should be initialized.**

**Cause:** FilterTerm has not been initialized.

**Action:** Initialize FilterTerm first.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25372: Inconsistent FilterTerm.getName() : {0}, {1}**

**Cause:** Name of filter term does not match the name of filter condition.

**Action:** Fix the inconsistency of filter term name and filter condition name.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25373: Inconsistent FilterTerm.getTypeName() : {0}, {1}**

**Cause:** Type name of filter term does not match the name of filter condition.

**Action:** Fix the inconsistency of filter term type name and filter condition type name.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25374: Term operation should be defined.**

**Cause:** Undefined term operation.

**Action:** Define operation of the term.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25375: Term of type {0} does not accept operation {1}.**

**Cause:** Operation was not accepted by the term.

**Action:** Specify an operation that can be accepted by the term.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**SDP-25376: TermOperation must be set.**  
**Cause:** TermOperation was not set.  
**Action:** Set TermOperation properly.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25377: Operand {0} just allows {1} arguments, but is given {2}.**  
**Cause:** Number of arguments does not meet the requirement of the operand.  
**Action:** Set correct number of arguments.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25378: Object {0} should be of type {1}.**  
**Cause:** Object has an incorrect Java type.  
**Action:** Correct the type of object.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25379: Type {0} is not supported.**  
**Cause:** Object's type is not supported by User Preferences.  
**Action:** Change the type of object to one of following supported Java types: String, Integer, Double and Date

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25380: User {0} does not exist in the system.**  
**Cause:** User name not found.  
**Action:** Provide the correct user name.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25381: Device not found for user {0}.**  
**Cause:** Device does not exist.  
**Action:** Provide a valid Device name or username.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**SDP-25382: DeliveryType is missing in the address {0}.**

**Cause:** Address does not have required DeliveryType.

**Action:** Provide a valid DeliveryType in the address in <DeliveryType>:<Address> format.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25383: Cannot persist device address {0}.**

**Cause:** An exception occurred when storing device address.

**Action:** Check stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25384: Cannot create RuleSet for the user {0}.**

**Cause:** An exception occurred while creating RuleSet for this user.

**Action:** Check stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25385: Saving UserRuleSet failed. Cannot get XMLString for user {0}.**

**Cause:** An exception occurred while saving RuleSet for this user.

**Action:** Check stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25386: Could not find entity to update.**

**Cause:** Unable to find the entity in storage.

**Action:** None.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25387: Rule fact for term {0} has been ignored as it does not have the correct type, {1}.**

**Cause:** The fact from user or application had an incorrect data type.

**Action:** Provide the fact with the correct data type as indicated.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

---

**SDP-25388: Device named {0} of user {1} not found.**

**Cause:** The user does not have a device with that name.

**Action:** Check username and device name.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-25400: An unexpected exception was caught.**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25401: Unable to set the parameter {0} in the configuration because of exception {1}.**

**Cause:** An exception has occurred while attempting to set the specified parameter in the configuration object.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25402: Could not find the value for the configuration parameter {0}, using default value.**

**Cause:** There is no such entry for the parameter {0} in the configuration file.

**Action:** Check configuration parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25403: Error in registering messaging Runtime MBeans.**

**Cause:** Exception was thrown.

**Action:** Check stack trace

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25404: Error in unregistering messaging Runtime MBeans.**

**Cause:** Exception was thrown.

**Action:** Check stack trace.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**SDP-25405: Naming exception thrown looking up Management Store: Unable to initialize SDP Messaging Runtime MBeans**

**Cause:** Naming exception thrown while looking up the Management Store EJB.

**Action:** Check stack trace.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25406: Create exception thrown while creating Management Store: Unable to initialize SDP Messaging Runtime MBeans.**

**Cause:** Create exception thrown while creating Management Store EJB.

**Action:** Check stack trace.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25407: Exception initializing Runtime MBean.**

**Cause:** An exception was thrown during runtime MBean initialization.

**Action:** Check stack trace.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25408: Invalid query parameter: query field: {0}, query condition: {1}, query value: {2}**

**Cause:** Invalid combination of query parameters or invalid query value.

**Action:** Check stack trace.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-25409: Unable to initialize the composite type for the MBean.**

**Cause:** OpenDataException was caught.

**Action:** Check stack trace.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25410: Unable to convert to composite type and return composite data for the MBean. Name: {0}**

**Cause:** OpenDataException was caught.

**Action:** Check stack trace.

**Level:** 1

**Type:** ERROR



---

**Impact:** Requests/Responses

**SDP-25411: Unable to load Driver properties.**

**Cause:** An exception has occurred while attempting to load the driver configuration properties.

**Action:** Check stack trace.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25413: Could not find the value for the configuration parameter {0}, using default value.**

**Cause:** There is no such entry for the parameter {0} in the configuration file.

**Action:** Check configuration parameter.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-25414: Could not find the application deployment MBean for {0}**

**Cause:** The application may not have started correctly.

**Action:** Check the application deployment status.

**Level:** 1

**Type:** WARNING

**Impact:** Process

**SDP-25415: Found multiple application deployment MBeans for {0}**

**Cause:** The application may not have started correctly.

**Action:** Check the application deployment status.

**Level:** 1

**Type:** WARNING

**Impact:** Process

**SDP-25416: Error occurred while attempting to get the parent server MBean for {0}**

**Cause:** An exception was thrown while attempting to get the parent server MBean.

**Action:** Check stack trace.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-25502: Unable to create JNDI Context**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details. Check the JNDI Context initialization parameters.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**SDP-25503: Unable to connect to the messaging server.**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details. Check that the messaging server is up. Check the JNDI Context initialization parameters.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SDP-25504: Unable to register application information with the messaging server.**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details. Check that the messaging server is up. Check the JNDI Context initialization parameters.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SDP-25505: Unable to enqueue outbound message.**

**Cause:** Engine Sending Queue may not be available.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25506: Unable to get receiving queues from application information.**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details. Check the Application information properties.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SDP-25507: Unable to enqueue inbound message status because no engine queues were found.**

**Cause:** The client is not aware of any engine queues to enqueue the status.

**Action:** Check that the application is registered successfully with the messaging server.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25508: Unable to enqueue inbound message status.**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25509: An error occurred while notifying the MessageDispatcherBean about engine queues.**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SDP-25510: An error occurred while attempting to retrieve the actual password from the credential store.**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SDP-25511: An error occurred while dequeuing a message from the application receiving queue.**

**Cause:** An invalid JMS message was dequeued by the Dispatcher MDB.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25512: An invalid message was dequeued from the application receiving queue: {0}**

**Cause:** An invalid JMS message was dequeued by the Dispatcher MDB.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25513: JNDI lookup of application callback listener failed.**

**Cause:** An invalid callback listener was previously registered and could not be invoked.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-25514: An error occurred while dispatching an inbound message to the application.**

---

**Cause:** An exception has occurred.  
**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25515: An error occurred while dispatching an inbound status to the application.**

**Cause:** An exception has occurred.  
**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25516: Message/Status listener not configured. Suspending messaging client MDB to disable asynchronous message/status callbacks.**

**Cause:** Message/Status listener was not configured by the application.  
**Action:** If the application requires asynchronous message/status callbacks, configure the listener information. Otherwise, ignore this warning.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**SDP-25517: Messaging client MDB suspend failed: {0}**

**Cause:** 1) The Messaging client was unable to access the MDB MBean because the container may not be in RUNNING state. 2) The server administrator username 'weblogic' does not exist.

**Action:** 1) Check the state of the container. Check the stack trace for more details.  
2) Specify a valid server administrator username using the system property -Doracle.ums.admin.user and restart the server.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**SDP-25520: MessagingWebServiceClientImpl.send() operation failed.**

**Cause:** An exception has occurred when invoking webservice send().  
**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25521: MessagingWebServiceClientImpl.receive() operation failed.**

**Cause:** An exception has occurred while receiving messages from webservice.  
**Action:** Check the stack trace for more details.

**Level:** 1

---

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25522: The application onMessage() callback operation failed.**

**Cause:** An exception has occurred while attempting to call the application onMessage callback method.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25523: The application onStatus() callback operation failed.**

**Cause:** An exception has occurred while attempting to call the application onStatus callback method.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25532: An error occurred while retrieving the Application Information from the application JNDI context.**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SDP-25541: An error occurred while generating received message statuses.**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25542: Security principal in client EJB Context "{0}" does not match security principal in ApplicationInfo "{1}". This may cause permission errors during future Messaging Client operations.**

**Cause:** The security principal in the current EJBContext is different from the ApplicationInfo security principal field specified when creating the Messaging Client instance (or the default value, if no principal was provided).

**Action:** Ensure that the security principals used by this application for all Messaging Client operations match one another.

**Level:** 1

**Type:** WARNING

**Impact:** Security

---

**SDP-25543: The current authenticated user "{0}" does not match the configured security principal "{1}".**

**Cause:** The security principal in effect for the current thread is different from the security principal field specified when creating the Messaging Client instance.

**Action:** Ensure that the security principals used by this application for all Messaging Client operations match one another, or avoid configuring a specific security principal.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**SDP-25600: An unexpected exception was caught.**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25700: An unexpected exception was caught.**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25701: Unable to instantiate class {0}.**

**Cause:** Unable to instantiate a class.

**Action:** Check to see if that class is in classpath or not.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25702: Unable to set content of Message object.**

**Cause:** Unable to set content of a message.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25704: Error in setMultiplePayload.**

**Cause:** An error occurred in setMultiplePayload().

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**SDP-25705: Exception printing message content.**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25706: Failed to clone message content.**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25707: Failed to clone headers. Message = {0} .**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25708: Unable to perform JNDI lookup of JMS QCF: {0}.**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25709: Unable to perform JNDI lookup.**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25710: Could not close JMS queue connection.**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25711: Received unknown object: {0}.**

---

**Cause:** An exception has occurred.  
**Action:** Check the stack trace for more details.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses

**SDP-25712: Message received with invalid format: {0}.**  
**Cause:** An exception has occurred.  
**Action:** Check the stack trace for more details.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses

**SDP-25713: Unable to perform JNDI lookup of JMS Queue: {0}.**  
**Cause:** An exception has occurred.  
**Action:** Check the stack trace for more details.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses

**SDP-25714: Access control exception was caught. Name: {0} Action:{1}.**  
**Cause:** An exception has occurred.  
**Action:** Check the stack trace for more details.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses

**SDP-25715: Invalid format, skipping: {0}**  
**Cause:** Invalid queue information.  
**Action:** Check the stack trace for more details.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses

**SDP-25716: Error occurred in looking up QueueConnectionFactory in JNDI, skipping: {0}**  
**Cause:** Error occurred in looking up QueueConnectionFactory in JNDI.  
**Action:** Check the stack trace for more details.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses

**SDP-25717: Error occurred in looking up Queue in JNDI, skipping: {0}.**  
**Cause:** Error occurred in looking up queue in JNDI.



---

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25718: Error occurred in getQueueInfoList.**

**Cause:** Error occurred in getQueueInfoList().

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25719: Failed to authenticate user {0}.**

**Cause:** Failed to authenticate a user.

**Action:** Check username and password and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25720: Sender Address is null or empty.**

**Cause:** Sender Address has an error.

**Action:** Enter a valid non-null value for sender.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25721: Recipient Address is null or empty.**

**Cause:** Recipient Address has an error.

**Action:** Enter a valid non-null value for Recipient.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25722: Message content is empty.**

**Cause:** Message content was not set properly.

**Action:** Enter a valid non-null value for the content.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25723: Message object is null.**

**Cause:** Message is null.

**Action:** Set a valid non-null value of Message object.

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25724: Message subject and content are null.**

**Cause:** Message subject and content.

**Action:** Enter a valid non-null value for subject and/or content.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25725: Message serialization failed.**

**Cause:** Failed to serialize message due to unexpected I/O Error.

**Action:** Ensure that content is being created according to recommendations for Message class.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25726: Connection failed to remote host {0} using HTTP Proxy {1}. Error: {2}.**

**Cause:** There was a problem with either the remote host or the HTTP Proxy. Check the associated connection error for the exact cause.

**Action:** Check the value of the remote host and the HTTP Proxy settings.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25727: Unable to create JMS QueueSender, {0}. Cause: There was a problem in the connection to the JMS provider.**

**Cause:** There was a problem in the connection to the JMS provider.

**Action:** Check the container log for additional errors from the JMS adapter.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-25728: Could not determine server platform type. Generic values will be used for platform-specific data.**

**Cause:** The Java EE server platform could not be determined. Either this application is executing in a Java SE environment, or the Java EE server is configured incorrectly.

**Action:** If executing in a Java SE environment, no action is necessary. Otherwise ensure that Java Required Files module is deployed to this environment.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

---

**SDP-25729: An exception occurred while enabling the WS-Security configuration: {0}**

**Cause:** An exception occurred while attaching a WS-Security policy to a web service client or endpoint.

**Action:** Ensure that any WS-Security policies are specified in the correct format.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**SDP-26000: An unexpected exception was caught.**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26001: Cannot create JNDI Context.**

**Cause:** Cannot create JNDI Context.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26006: Exception while dispatching message to driver resource adapter.**

**Cause:** Exception while dispatching message to driver resource adapter.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26010: Unable to start driver: {0}.**

**Cause:** Unable to start driver.

**Action:** Check stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-26011: Failed to invoke registerDriverInfo().**

**Cause:** Exception thrown while invoking registerDriverInfo().

**Action:** Check stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**SDP-26012: unable to remove scheduled workers**

**Cause:** An exception has occurred while removing a driver thread.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-26013: Unable to cleanly stop driver: {0}.**

**Cause:** Unable to cleanly stop driver.

**Action:** Check stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-26014: Unable to process inbound message/status.**

**Cause:** Exception occurred while processing inbound message/status.

**Action:** Check stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-26015: Unable to process command message.**

**Cause:** Exception occurred while processing command message.

**Action:** Check stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-26019: Error occurred while registering driver.**

**Cause:** Error occurred while registering driver.

**Action:** Check stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-26021: Timed out while waiting for reply from Messaging engine.**

**Cause:** The registration command timed out in the JMS queue because the Messaging engine is down or the system is under heavy load.

**Action:** Check if the Messaging engine is up and ensure the system is not under extremely heavy load.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

---

**SDP-26022: Illegal DeliveryType specified, ignoring type {0}. Exception: {1}**

**Cause:** Illegal DeliveryType specified.

**Action:** Check message delivery type.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26023: Benchmark logging is enabled for all inbound messages, which may slow down system performance. To disable it, unset environment variable sdpm\_inbound\_benchmark\_logging and restart.**

**Cause:** Benchmark logging is enabled when environment variable sdpm\_inbound\_benchmark\_logging=true.

**Action:** To disable benchmark logging, unset environment variable sdpm\_inbound\_benchmark\_logging and restart.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-26025: Error in registering messaging driver Runtime MBeans.**

**Cause:** Exception was thrown.

**Action:** Check stack trace

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26026: Error in unregistering messaging driver Runtime MBeans.**

**Cause:** Exception was thrown.

**Action:** Check stack trace

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26028: Ignoring property {0} with invalid value {1} and/or Java type {2} during driver initialization.**

**Cause:** A property with an invalid value and/or unsupported Java type was found in 'configuration/driverconfig.xml' during driver initialization.

**Action:** Use a valid value and/or one of the following valid Java types: java.lang.Boolean, java.lang.String, java.lang.Integer, java.lang.Double, java.lang.Byte, java.lang.Short, java.lang.Long, java.lang.Float, java.lang.Character

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**SDP-26029: Unable to load driver configuration properties from 'configuration/driverconfig.xml'.**

---

**Cause:** An exception occurred while attempting to load the driver configuration properties from 'configuration/driverconfig.xml'.

**Action:** Check the stack trace.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SDP-26030: Unable to schedule worker used to attempt driver registration.**

**Cause:** An exception occurred while scheduling a worker to attempt driver registration.

**Action:** Check the stack trace.

**Level:** 1

**Type:** WARNING

**Impact:** Process

**SDP-26031: Lookup of encoded credential value {0} in the credential store for property {1} failed during driver initialization. Passing through the value as-is.**

**Cause:** A property with an invalid encoded credential value was found in 'configuration/driverconfig.xml' during driver initialization.

**Action:** Use a valid encoded credential value and ensure the application has permission grants to access the credential store.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**SDP-26032: JNDI lookup of driver connection factory {0} failed with the following error message: {1}. Will retry until successful.**

**Cause:** Driver connection factory could not be located in JNDI. Driver registration will not occur until this lookup succeeds.

**Action:** Wait for server startup to proceed. If driver registration does not occur, ensure that the driver connection factory JNDI name is configured correctly.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-26033: Started messaging driver: {0}**

**Cause:** Driver was started.

**Action:** None.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Process

**SDP-26034: Stopped messaging driver: {0}**

**Cause:** Driver was stopped.

**Action:** None.

---

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Process

**SDP-26035: JNDI lookup of server command endpoint {0} failed with the following error message: {1}. Will retry until successful.**

**Cause:** Messaging Server command module could not be located in JNDI. Driver registration will not occur until this lookup succeeds.

**Action:** Wait for server startup to proceed. If driver registration does not occur, ensure that the messaging server is deployed and started.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-26100: An unexpected exception was caught.**

**Cause:** An unexpected exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26101: Content type parsing error {0}.**

**Cause:** Error occurred while trying to parse the content type.

**Action:** Check and see if the content type is specified correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26102: Error while writing e-mail message content.**

**Cause:** An exception has occurred while writing e-mail content and headers to an e-mail message.

**Action:** Check stack trace or error log.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26103: Error while writing e-mail subject.**

**Cause:** Cannot write the subject.

**Action:** Check stack trace or error log.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26104: Recipient address error.**

**Cause:** Recipient e-mail address has an error.

---

**Action:** Check and see if the recipient e-mail address is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26105: unable to deliver to following address(es): {0} Reason: {1}**

**Cause:** One or more recipient e-mail addresses had an error.

**Action:** Ensure that the e-mail address is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26106: failed to send the e-mail message**

**Cause:** Unable to login to SMTP server.

**Action:** Check SMTP server host name, port, user name, and password.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26107: failed to add header - name: {0} value: {1}**

**Cause:** Unable to add an e-mail header to a multipart message

**Action:** Check the stack trace or error log.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26108: failed to initialize e-mail driver**

**Cause:** Could not initialize Email Driver.

**Action:** Check stack trace or error log. Check e-mail driver parameters and make sure all e-mail servers are up.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26109: Caught exception while closing connection to e-mail server.**

**Cause:** An exception was caught while closing connection.

**Action:** Check stack trace or error log.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26110: Starting Email Driver failed.**

**Cause:** Could not start Email Driver.



---

**Action:** Check stack trace or error log. Check e-mail driver parameters and make sure all servers are up.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26111: Could not remove listener from Email Driver**

**Cause:** Could not remove listener from Email Driver

**Action:** Check stack trace or error log

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26112: Null protocol error**

**Cause:** Protocol was null.

**Action:** Specify an appropriate protocol for this driver.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26113: No incoming e-mail server.**

**Cause:** Incoming server was not set.

**Action:** Set incoming server parameters.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26114: Username is missing.**

**Cause:** Username was not set.

**Action:** Set the username in e-mail driver parameters.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26115: failed to receive an inbound e-mail message**

**Cause:** An exception has occurred while receiving an inbound e-mail message.

**Action:** Check stack trace or error log.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26116: Protocol {0} is not supported.**

**Cause:** An unsupported protocol was provided.

**Action:** Check the e-mail protocol name in e-mail driver parameters.

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26117: Connection information of the inbound e-mail server is missing. Check the server host name, user name, and password.**

**Cause:** Connect information was missing or incomplete.

**Action:** Provide the required connection information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26118: failed to open folder: {0}**

**Cause:** Folder name is not correct or does not exist.

**Action:** Check folder name spelling.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26119: Max retry limit reached for trying to connect to user {0}**

**Cause:** Email driver has reached Max retry limit to connect to user.

**Action:** Check stack trace or error log. Check e-mail driver parameters and make sure all servers are up.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26120: IMAP server failed to expunge e-mail messages. mail box: {0}**

**Cause:** An exception was caught when doing expunge.

**Action:** Check stack trace or error log. Check e-mail driver parameters and make sure all servers are up.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26121: Attempt to reconnect {0}. Error Count: {1} Retry Count: {2}.**

**Cause:** Attempt to reconnect to the incoming e-mail server

**Action:** Check e-mail driver parameters and make sure all servers are up.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-26122: An exception has been thrown when connecting to user {0}**

**Cause:** Email driver could not connect to user.

---

**Action:** Check username and password. Make sure the user exists and is accessible.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26123: Could not initialize Email Store for user {0}**

**Cause:** Could not initialize Email Store for user.

**Action:** Check stack trace or error log. Check username and password.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26124: invalid folder: {0}**

**Cause:** An invalid folder name was specified.

**Action:** Check and see if the specified folder is valid and accessible.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26125: An exception has occurred while sending out a message.**

**Cause:** An exception occurred while sending out a message.

**Action:** Check stack trace or error log. Check Proxy Driver parameters and remote gateway.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26126: unrecoverable message - {0}**

**Cause:** failed to recover an e-mail message

**Action:** Check stack trace or error log.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-26127: Collision on e-mail message polling. Pausing for {0} seconds.**

**Cause:** Multiple e-mail drivers polling the same e-mail account at the same time.

**Action:** (None)

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-26128: A duplicate inbound e-mail message has been discarded: gateway message ID: {0}, recipient addresses: {1}, subject: {2}.**

**Cause:** A duplicate message was detected and discarded by the e-mail receiver.

---

**Action:** (None)

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-26129: unable to deliver to following addresses: {0} Reason: {1}**

**Cause:** Recipient e-mail address was valid but sending failed for reason indicated in error message.

**Action:** Ensure that e-mail driver and SMTP server are operational and configured correctly, based on information provided in error message.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26150: An unexpected exception was caught.**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26151: Failed to process a received message in SMPP driver, because driver context is null**

**Cause:** Driver context is null

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26152: WorkManager object is null in SMPP driver.**

**Cause:** The caller of setWorkManager() passed in a null WorkManager object as an argument

**Action:** Make sure WorkManager object is not null.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26153: Received status message with incorrect format.**

**Cause:** The status received from SMSC does not have message ID or state.

**Action:** Correct the SMSC.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**SDP-26154: Failed to process received status in SMPP driver, because driver context is null.**

**Cause:** Driver Context is null

**Action:** Check driver context.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26155: unable to initialize SMPP driver, because a driver attribute, sms.account.id, is not set.**

**Cause:** The account ID was not set.

**Action:** Set the correct account information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26156: Failed to initialize SMPP Driver because driver attributes sms.server.host, sms.server.transmitter.port or sms.server.receiver.port is not set.**

**Cause:** SMSC server or account information is not correct or missing.

**Action:** Check those parameters.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26157: SMPP driver failed to send out a message, because Message object is null.**

**Cause:** Null message object.

**Action:** Check the caller of this method.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26158: Caught exception while closing connection**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26159: Illegal data length value from SMSC received and ignored: {0}**

**Cause:** SMPP Driver has detected a corrupted data field from SMSC and it is trying to recover.

**Action:** This error suggests communication errors between SMPP driver and SMSC. Check to see if this driver supports that SMSC.

**Level:** 1

---

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26160: SMPP Driver not configured. Configure and restart this driver.**

**Required Properties:** SmsAccountId, SmsServerHost, TransmitterSystemId, ReceiverSystemId, TransmitterSystemType, ReceiverSystemType, TransmitterSystemPassword, ReceiverSystemPassword, ServerTransmitterPort, ServerReceiverPort.

**Cause:** SMPP Driver was not configured.

**Action:** Configure and restart this driver. Required Properties: SmsAccountId, SmsServerHost, TransmitterSystemId, ReceiverSystemId, TransmitterSystemType, ReceiverSystemType, TransmitterSystemPassword, ReceiverSystemPassword, ServerTransmitterPort, ServerReceiverPort.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SDP-26162: Message content could not be decoded using character set {0}**

**Cause:** The message content retrieved from the SMSC could not be decoded using the specified character set.

**Action:** Ensure that the Default Encoding configuration parameter is correct.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-26163: Data stream ended unexpectedly while reading packet from SMSC**

**Cause:** The data stream ended unexpectedly while reading a packet from the SMSC. Message or command will be dropped.

**Action:** None.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-26164: Failed to bind receiver connection; will retry until bind operation is successful.**

**Cause:** Could not bind to the SMSC as a receiver. Bind operation will be retried periodically until it is successful.

**Action:** None required. Change value of configuration parameter "BindRetryDelay" to adjust retry interval.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SDP-26200: An unexpected exception was caught.**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

---

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26201: Unable to remove listener from XMPPDriver.**

**Cause:** Unable to remove listener from XMPPDriver .

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26202: Unable to shut down XMPPDriver.**

**Cause:** Unable to shut down XMPPDriver.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-26203: XMPP Driver not configured. Configure and restart this driver.**

**Required properties:** IMServerHost, IMServerUsername, IMServerPassword.

**Cause:** XMPP Driver was not configured.

**Action:** Configure and restart this driver. Required properties: IMServerHost, IMServerUsername, IMServerPassword.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SDP-26204: Error occurred while initializing {0}**

**Cause:** Error occurred while initializing driver instance.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-26209: Unable to initialize accounts**

**Cause:** Unable to initialize accounts.

**Action:** Check username, password and IM server.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SDP-26210: Unable to connect to XMPP server: {0}**

**Cause:** Check the associated stack trace for the cause of the connection failure.

**Action:** Check the XMPP server hostname and port parameters and make sure the server is up.

**Level:** 1

- 
- Type:** ERROR  
**Impact:** Configuration
- SDP-26213: Exception while sending message - from: {0} to: {1}.**  
**Cause:** Exception while sending message.  
**Action:** Check stack trace and recipient address
- Level:** 1
- Type:** ERROR  
**Impact:** Requests/Responses
- SDP-26214: Caught an exception in XMPP driver while sending out a message.**  
**Cause:** An unexpected exception was caught.  
**Action:** Check the stack trace for more details.
- Level:** 1
- Type:** ERROR  
**Impact:** Requests/Responses
- SDP-26215: The XMPP driver has no previous account to replace.**  
**Cause:** No previous XMPP (IM) account was found. Unable to replace previous account.  
**Action:** None
- Level:** 1
- Type:** WARNING  
**Impact:** Configuration
- SDP-26216: No accounts defined in XMPP driver.**  
**Cause:** No XMPP accounts defined.  
**Action:** Define a valid XMPP (IM) account.
- Level:** 1
- Type:** ERROR  
**Impact:** Configuration
- SDP-26217: Could not locate an account to deliver this message from sender {0}.  
Using the first account ( {1} ) to deliver this message.**  
**Cause:** Could not locate an account to deliver this message.  
**Action:** To retain the original message sender, add sender of the message to 'user' configuration property of the driver.
- Level:** 1
- Type:** ERROR  
**Impact:** Requests/Responses
- SDP-26218: I/O problem using HTTP Proxy {0} for account: {1}**  
**Cause:** The connection with the HTTP Proxy was broken.  
**Action:** Check stack trace for more information. Check HTTP Proxy settings to see if proxy is correct and reachable.



---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26219: Server DNS problem with account: {0}**

**Cause:** The hostname could not be resolved by DNS.

**Action:** Check the stack trace, account parameters, and DNS server.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26220: Server I/O problem with account: {0}**

**Cause:** The connection with the XMPP server was broken.

**Action:** Check the account parameters and the network connection.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26221: Third-party transport connectivity is no longer supported. Ignoring all applicable configuration properties.**

**Cause:** This is an upgraded XMPP Driver instance making use of third-party transport connectivity that is no longer supported in this version.

**Action:** None

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**SDP-26222: Agent registration failed for {0}. Error Code: {1}**

**Cause:** Agent registration failed.

**Action:** Check error code and from address.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26223: Fatal Error on Presence object build.**

**Cause:** Fatal Error on Presence object build.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26224: Exception managing presence**

**Cause:** Exception managing presence.

**Action:** Check the stack trace for more details.

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26225: Received Error Message. Code: {0} Text: {1}.**

**Cause:** Received Error Message.

**Action:** Check error code and error message.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26226: Unauthorized login to Jabber/XMPP server: {0}**

**Cause:** Invalid username and/or password was supplied.

**Action:** Check username and password.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26227: New account registration failed. It appears that the Jabber/XMPP server does not allow automatic registration. Contact the server administrator for a new account. Now disconnecting from server: {0}**

**Cause:** New account registration failed. It appears that the Jabber/XMPP server does not allow automatic registration.

**Action:** Contact the server administrator for a new account.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26228: New account registration failed. Either this account already exists and you have entered an incorrect password or there is a problem with the Jabber/XMPP server. Now disconnecting from server: {0}**

**Cause:** New account registration failed. Either this account already exists and you have entered an incorrect password or there is a problem with the Jabber/XMPP server.

**Action:** Check that the specified account does not exist. Check that your password is valid

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26229: Plaintext authentication failed; disconnecting from server: {0}**

**Cause:** Plaintext authentication failed.

**Action:** Check username and password and check with the Jabber/XMPP server administrator.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**SDP-26230: Digest authentication failed. Attempting plain-text authentication: {0}**

**Cause:** Digest authentication failed.

**Action:** Digest authentication failed. Check with the Jabber/XMPP server administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26234: Disconnecting from Jabber/XMPP server: {0}. Cause: 1) The account was disconnected by the XMPP server due to another conflicting login. 2) The XMPP server went offline. Action: 1) Identify and shut down the conflicting XMPP driver that is using the same account. 2) Check the status of the XMPP server.**

**Cause:** 1) The account was disconnected by the XMPP server due to another conflicting login. 2) The XMPP server went offline.

**Action:** 1) Identify and shut down the conflicting XMPP driver that is using the same account. 2) Check the status of the XMPP server.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**SDP-26235: Account disconnected: {0}. Cause: I/O or authentication error. Action: Check account host, username and password configuration. Check the connectivity to the XMPP server.**

**Cause:** The account was disconnected from the server either due to I/O or authentication error.

**Action:** Check account host, username and password configuration. Check the connectivity to the XMPP server.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**SDP-26236: Got an unexpected exception when receiving a message.**

**Cause:** Got an exception when receiving a message.

**Action:** Check to see if the message is well-formed.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26237: The call for conversion does not supply account information. The first account is being used for conversion.**

**Cause:** The call for conversion did not supply the necessary account information.

**Action:** Provide the correct account information.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**SDP-26238: cannot deliver to this {0} user, because {0} transport is not enabled in the driver. Set the value for driver parameter: {1}.**

**Cause:** Because transport was not enabled in the driver, delivery could not be made to the Yahoo, MSN, AOL, or ICQ user.

**Action:** Enable the transport in the driver.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26239: Invalid network name in address: {0}**

**Cause:** Invalid network name in address

**Action:** Specify a valid network name in address.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26240: Max Retry Limit ( {0} ) is reached. Restart the driver to try reconnecting for account {1}.**

**Cause:** The Max Retry Limit was reached while attempting to reconnect.

**Action:** Restart the XMPP driver to try again.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26243: Account {0} is disconnected from the server at the request of the driver.**

**Cause:** None.

**Action:** None.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**SDP-26245: Could not initialize XMPPDriver.**

**Cause:** XMPPDriver was misconfigured.

**Action:** Check driver parameters, account information and Jabber/XMPP server.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**SDP-26246: Caught exception while closing connection of XMPP server.**

**Cause:** Caught exception in XMPP driver while closing server connection.

**Action:** Check stack trace.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**SDP-26247: Caught exception while closing connection.**

**Cause:** Caught exception while closing connection.

**Action:** Check stack trace.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26250: An unexpected exception was caught.**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26251: Could not initialize Proxy Driver**

**Cause:** Could not initialize Proxy Driver.

**Action:** Check stack trace or error log. Check Proxy Driver parameters and remote gateway.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26252: Error occurred while initializing Proxy Driver: DriverConnection returned by DriverConnectionFactory is null.**

**Cause:** DriverConnection returned by DriverConnectionFactory was null

**Action:** Check stack trace or error log. Check Proxy Driver parameters and remote gateway.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26254: Failed to initialize Proxy Driver with GatewayURL={0} and Username={1}. Check driver configuration properties and remote gateway, and restart the driver.**

**Cause:** Failed to initialize Proxy Driver with the specified GatewayURL, Username and Password.

**Action:** Check stack trace or error log. Check Proxy Driver properties: GatewayURL, Username and Password. Also check the status of the remote gateway.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26255: Exception occurred while initializing Proxy Driver**

---

**Cause:** Exception occurred while initializing Proxy Driver

**Action:** Check stack trace or error log. Check Proxy Driver parameters and remote gateway.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26256: Proxy Driver has not been configured. Configure and restart this driver.**

**Required Property:** GatewayURL.

**Cause:** Proxy Driver was not configured.

**Action:** Configure and restart this driver. Required Property: GatewayURL.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SDP-26257: Exception occurred while invoking Proxy Driver remote request**

**Cause:** Exception occurred while invoking Proxy Driver remote request

**Action:** Check stack trace or error log. Check Proxy Driver configuration and remote gateway.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26350: An unexpected exception was caught.**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26351: VoiceXML Driver property VoiceXMLReceiveURL is empty.**

**Cause:** VoiceXMLReceiveURL was not set and could not be dynamically generated.

**Action:** Check the validity of the VoiceXMLReceiveURL property. Ensure the host and port are that of the server where this driver is deployed.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26352: VoiceXMLDriver: VoiceXMLOutboundServletURI cannot be null**

**Cause:** VoiceXMLOutboundServletURI is null

**Action:** Assign proper value for Outbound Servlet URL.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**SDP-26356: VoiceXMLDriver: Socket error from VoiceXML Gateway.**

**Cause:** Socket Error from the Gateway

**Action:** Check VoiceXML server URL and the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26357: VoiceXMLDriver could not initialize.**

**Cause:** Initialization failed.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26358: VoiceXMLDriver: Exception while processing the HTTP request.**

**Cause:** Exception while processing the HTTP request

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26359: VoiceXMLDriver: Caught exception while closing connection**

**Cause:** Caught exception while closing connection

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26360: VoiceXML Driver not configured. Configure and restart this driver.**

**Required Properties:** VoiceXMLOutboundServletURI.

**Cause:** VoiceXML Driver was not configured.

**Action:** Configure and restart this driver. Required Properties:  
VoiceXMLOutboundServletURI.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SDP-26400: An unexpected exception was caught.**

**Cause:** An exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**SDP-26401: Messaging Worklist Driver not configured. Configure and restart this driver. Required Properties: BPELConnectionURL.**

**Cause:** Messaging Worklist Driver was not configured.

**Action:** Configure and restart this driver. Required Properties: BPELConnectionURL.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SDP-26450: An unexpected exception was caught.**

**Cause:** An unexpected exception has occurred.

**Action:** Check the stack trace for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SDP-26451: One or more sets of extension endpoints were configured using identical protocols and mapped domains: {0}. The first endpoint listed in the configuration file will be used.**

**Cause:** Each of the listed protocol/domain pairs is used to configure multiple extension endpoints.

**Action:** Remove the conflicting endpoint configuration, or ensure that each endpoint has unique protocol and mapped domain parameters.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**SDP-26452: No extension endpoint could be found for the specified recipient address.**

**Cause:** None of the configured extension endpoints matched the protocol and domain of the message recipient.

**Action:** Ensure that an endpoint is configured for the desired protocol and domain, or configure a default (empty) domain.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**SDP-26453: No configuration element was found for this Extension Driver deployment. Create a configuration and restart this Extension Driver.**

**Cause:** No configuration element was found for this Extension Driver deployment.

**Action:** Create a configuration and restart this Extension Driver.

**Level:** 1

**Type:** ERROR



---

**Impact:** Configuration

**SDP-26454: Extension Driver not configured. Configure and restart this driver. The configuration must contain at least one Extension endpoint with a valid endpoint URL and protocol.**

**Cause:** Extension Driver was not configured.

**Action:** Configure and restart this driver. The configuration must contain at least one Extension endpoint with a valid endpoint URL and protocol.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SDP-30001: Charging is not allowed**

**Cause:** Attempted to use charging when charging is not allowed (according to the configuration).

**Action:** Verify ChargingAllowed configuration

**Level:** 1

**Type:** WARNING

**Impact:** Process

**SDP-30002: Ignore the 2xx response at state: {0}.**

**Cause:** Received a 2xx response in an illegal state.

**Action:** UNSPECIFIED ( see log/cause )

**Level:** 1

**Type:** WARNING

**Impact:** Process

**SDP-30003: Failed to ACK the 2xx repsonse.**

**Cause:** IOException received when trying to send ACK.

**Action:** UNSPECIFIED ( see log/cause )

**Level:** 1

**Type:** WARNING

**Impact:** Process

**SDP-30004: Could not ACK a dialog in the state: {0}.**

**Cause:** Illegal state when trying to ACK dialog

**Action:** UNSPECIFIED ( see log/cause )

**Level:** 1

**Type:** WARNING

**Impact:** Process

**SDP-30005: Failed to send SIP request.**

**Cause:** IOException when trying to send SIP request.

**Action:** UNSPECIFIED ( see log/cause )

**Level:** 1

---

**Type:** WARNING  
**Impact:** Process  
**SDP-30006: Could not cancel a call in the state: {0}.**  
**Cause:** Illegal state when trying to cancel call  
**Action:** UNSPECIFIED ( see log/cause )  
**Level:** 1  
**Type:** WARNING  
**Impact:** Process  
**SDP-30007: Failed to send out response to BYE.**  
**Cause:** IOException when trying to send out response to BYE.  
**Action:** UNSPECIFIED ( see log/cause )  
**Level:** 1  
**Type:** WARNING  
**Impact:** Process  
**SDP-30008: Failed to end the call leg.**  
**Cause:** Failed to send Bye.  
**Action:** UNSPECIFIED ( see log/cause )  
**Level:** 1  
**Type:** WARNING  
**Impact:** Process  
**SDP-30009: Could not cancel call in connected state.**  
**Cause:** Illegal state to cancel call.  
**Action:** UNSPECIFIED ( see log/cause )  
**Level:** 1  
**Type:** WARNING  
**Impact:** Process  
**SDP-30010: Failed to parse the SIP address.**  
**Cause:** Illegal SIP address  
**Action:** UNSPECIFIED ( see log/cause )  
**Level:** 1  
**Type:** WARNING  
**Impact:** Process  
**SDP-30011: Failed to create the call.**  
**Cause:** Check the exception.  
**Action:** UNSPECIFIED ( see log/cause )  
**Level:** 1  
**Type:** WARNING  
**Impact:** Process

---

**SDP-30012: Could not find call with id: {0}.**

**Cause:** Check the exception.

**Action:** UNSPECIFIED ( see log/cause )

**Level:** 1

**Type:** WARNING

**Impact:** Process

**SDP-30013: Failed to execute the action.**

**Cause:** Check the exception.

**Action:** UNSPECIFIED ( see log/cause )

**Level:** 1

**Type:** WARNING

**Impact:** Process

**SDP-30014: Failed to terminate the call: {0}.**

**Cause:** Check the exception.

**Action:** UNSPECIFIED ( see log/cause )

**Level:** 1

**Type:** WARNING

**Impact:** Process

**SDP-30015: Could not find the application session for call id: {0}.**

**Cause:** Check the exception.

**Action:** UNSPECIFIED ( see log/cause )

**Level:** 1

**Type:** WARNING

**Impact:** Process

**SDP-30016: Failed to create SIP Invite Message.**

**Cause:** Check the exception.

**Action:** UNSPECIFIED ( see log/cause )

**Level:** 1

**Type:** WARNING

**Impact:** Process

**SDP-30017: Failed to send INVITE to "{0}" from "{1}".**

**Cause:** Check the exception.

**Action:** UNSPECIFIED ( see log/cause )

**Level:** 1

**Type:** WARNING

**Impact:** Process



---

## SOA-00000 to SOA-00043

**SOA-00000: Malformed WS Binding port. Missing # between namespace URI and service/port names.**

**Cause:** Malformed webservice binding component port configuration

**Action:** Correct the port attribute for ws binding component in the composite configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SOA-00001: Malformed WS Binding port. Missing '/' between service and port name**

**Cause:** Malformed webservice binding component port configuration

**Action:** Correct the port attribute for ws binding component in the composite configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SOA-00002: No service name found.**

**Cause:** No service name found in webservice binding component configuration

**Action:** Add the service name attribute for ws binding component in the composite configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SOA-00003: Number of SOAP body elements and parts do not match in operation: {0}**

**Cause:** Malformed SOAP request. Number of Parts in the soap body does not match with WSDL definition.

**Action:** Correct the SOAP message.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**SOA-00004: Response message does not match output defined in the WSDL: output of operation "{0}" is null, but response message contains payload.**

**Cause:** SOAP response does not match WSDL definition.

**Action:** Correct the SOAP message.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SOA-00007: Unable to find service: {0}**

**Cause:** Specified service is not found in the WSDL.

**Action:** Either correct the wsdl or the service name.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SOA-00008: Unable to find port: {0}**

**Cause:** Specified port is not found in the WSDL.

**Action:** Either correct the wsdl or the port name.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SOA-00009: Unable to find operation: {0}**

**Cause:** Specified operation is not found in the WSDL.

**Action:** Either correct the wsdl or the operation name.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SOA-00010: Error in create Documentbuilder.**

**Cause:** Failure to create a new DocumentBuilder class.

**Action:** Server configuration may have to be corrected.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SOA-00011: Problem in parsing componentType {0}.**

**Cause:** Problem in parsing component type file.

**Action:** Correct the component type file configuraiton.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**SOA-00012: Request message does not match input defined in the WSDL: input of operation "{0}" is null, but request message contains payload.**

**Cause:** Request message does not match input defined in the WSDL. Input is not defined, but there is an input payload.

**Action:** Correct the wsdl.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SOA-00013: Malformed WSDL Interface attribute. Missing # between namespace URI and interface name.**

**Cause:** Malformed WSDL Interface attribute. Missing # between namespace URI and interface name.

**Action:** Add # between namespace URI and interface name.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SOA-00014: No interface name found.**

**Cause:** Specified interface not found in the WSDL definition.

**Action:** Correct the input wsdl or interface name.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SOA-00015: Error in getting XML input stream: {0}**

**Cause:** Failure in processing XML document.

**Action:** Make sure the xml input is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SOA-00016: Failed to concatenate the following 2 urls: home= "{0}" and relative="{1}".**

**Cause:** Failure in creating urls from the given home url and relative url.

**Action:** Correct the home or the relative urls.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SOA-00018: Failed to find a component type file: compositeDN = "{0}" and component="{1}".**

**Cause:** Failed to find component type file.

**Action:** Correct the component type file name.

**Level:** 1

---

**Type:** WARNING  
**Impact:** Requests/Responses  
**SOA-00019: Missing "{0}" delimiter**  
**Cause:** Missing a delimiter.  
**Action:** Add the missing delimiter.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses  
**SOA-00020: Unable to instantiate composite class loader due to exception {0}**  
**Cause:** Failure instantiating composite classloader.  
**Action:** Check the exception for detailed messages.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses  
**SOA-00021: No reference "{0}" defined for service "{1}"**  
**Cause:** No Reference defined for the given service.  
**Action:** Correct the composite configuration.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses  
**SOA-00022: Error Loading XML Schema {0}**  
**Cause:** Failure to find the specified schema.  
**Action:** Correct the schema location referenced.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses  
**SOA-00023: Incorrect config object type.**  
**Cause:** Incorrect Object Configuration type.  
**Action:** Correct the configuration for the object.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses  
**SOA-00025: Unable to convert to SDO: {0}**  
**Cause:** Failed to convert xml input to SDO object.  
**Action:** Check the exception message. You may have to correct the schema definition or configuration.  
**Level:** 1  
**Type:** ERROR



---

**Impact:** Requests/Responses

**SOA-00026: Error converting SDO to XML: {0}**

**Cause:** Failure in converting sdo objects to xml messages.

**Action:** Check the exception message. You may have to correct the schema definition or configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SOA-00027: Cannot remove property "{0}" that was defined in the componentType.**

**Cause:** Unable to remove the property defined in the component type file.

**Action:** Correct the component type configuraiton file.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SOA-00028: Invalid value for mode. It should be either active or retired mode.**

**Cause:** Invalid mode specified in the composite

**Action:** Provide valid mode such as active or retired.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SOA-00029: Invalid value for mode. It should be either on or off state.**

**Cause:** Invalid state specified in the composite

**Action:** Provide valid state such as on or off.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SOA-00030: Could not use reflection to get properties from the bean of class: {0}. {1}**

**Cause:** Failure in retrieving bean properties

**Action:** Check exception message for details.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**SOA-00031: Binding Type {0} is unknown.**

**Cause:** The type of binding is undefined.

**Action:** Please check document for valid binding types supported.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**SOA-00033: An MBean of name "{0}" doesnt exist. Unable to update its state.**

**Cause:** Specified mbean does not exist.

**Action:** Correct the mbean name used.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SOA-00034: Unable to load the "{0}" file from "{1}" directory.**

**Cause:** Failed to load the file using mdm configuration.

**Action:** Correct the MDM configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SOA-00035: Variable "{0}" not defined in mdm-url-resolver.xml.**

**Cause:** The variable is not defined in the mdm configuration file.

**Action:** Correct the mdm configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SOA-00036: mdm-url-resolver.xml not loaded**

**Cause:** MDM url resolver is not loaded.

**Action:** Check the server configuration for MDM setup.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SOA-00037: Malformed Java Binding port. Missing # between namespace URI and service/port names.**

**Cause:** Port type in binding component is invalid.

**Action:** Check the port type attribute and correct the syntax used.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SOA-00038: Malformed Java Binding port. Missing name of the portType**

**Cause:** Port type in binding component is invalid.

**Action:** Check the port type attribute and correct the syntax used.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**SOA-00039: Invalid composite element name "{0}". Element names in a composite have to be unique.**

**Cause:** Invalid composite file.

**Action:** Correct the element name used for the composite.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SOA-00040: Unable to convert sdo to xml, element name not found.**

**Cause:** Failed to convert sdo objects to xml messages

**Action:** Check the schema definition referenced from the wsdl.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**SOA-00043: Unable to convert sdo to xml, missing sdo metadata.**

**Cause:** Failed to convert sdo objects to xml messages. Metadata for the conversion is not found.

**Action:** Check the schema definition referenced from the wsdl.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses



---

## SSL-28750 to SSL-29249

**SSL-28750: unknown error**

**Cause:** An Oracle Security Server error of an unspecified type occurred.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28751: memory allocation failure**

**Cause:** The allocation of memory failed due to insufficient system memory.

**Action:** Terminate other processes to free up memory or add memory to the system.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28752: data source initialization failure**

**Cause:** A data source failed to initialize. Frequently, this error is caused by insufficient system resources.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28753: failure to terminate use of data source**

**Cause:** The system failed to terminate its use of a data source. This error may have been caused by memory or disk corruption, among other things.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

---

**SSL-28755: object retrieval failure**

**Cause:** The system failed to retrieve information from a file or a database.

**Action:** Check if the data source exists, or check to ensure that the correct information exists.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28756: callback failure to allocate memory**

**Cause:** A function supplied by the caller failed to allocate memory. This error could have been caused by system memory exhaustion.

**Action:** Terminate other processes to free up memory or add memory to the system.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28757: system attempt to allocate 0 bytes of memory**

**Cause:** The system attempted to allocate 0 bytes of memory because there was no available memory left to allocate. This error could have been caused by insufficient system memory.

**Action:** Terminate other processes to free up memory or add memory to the system.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28758: memory release failure**

**Cause:** The release of a memory fragment failed. This may be due to memory corruption either within the application or in the Oracle Security Server library.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28759: failure to open file**

**Cause:** The system could not open the specified file.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28763: Invalid parameter type found in configuration file.**

**Cause:** A parameter in the sqlnet.ora file may have been specified incorrectly.

---

**Action:** Check the sqlnet.ora file for this parameter value.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28764: failure to retrieve a configuration parameter**

**Cause:** The system failed to retrieve a configuration parameter from the sqlnet.ora file. This error may have occurred because a necessary configuration parameter was not specified in the sqlnet.ora file.

**Action:** Supply the needed configuration parameter in the sqlnet.ora file.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28766: failure to terminate use of data source**

**Cause:** The system failed to terminate its use of a data source. This error may have been caused by memory or disk corruption, or a system error.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28767: invalid version number**

**Cause:** Version number of the wallet was incorrect. A corrupt wallet or an incompatible wallet was provided.

**Action:** Ensure that proper wallet is being used.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28768: bad magic number**

**Cause:** An invalid magic number was specified in a data file. This could have been caused by a corrupted disk or by some other process overwriting the file.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28769: Specified method does not exist.**

**Cause:** The data access method that was specified in the configuration file is not supported.

**Action:** Specify a supported method. Consult the Oracle Security Server documentation to determine the supported types.

---

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28770: Data source is already initialized.**

**Cause:** The caller attempted to initialize a data source which was already initialized.

**Action:** This is a programming error. An application should not attempt to initialize a data source more than once.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28771: Data source is not yet initialized.**

**Cause:** The caller attempted to use a data source which had not yet been initialized.

**Action:** This is a programming error. The application must always initialize the data source before it can be used.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28773: failure to write magic and version numbers**

**Cause:** Both the magic and version numbers failed to write. This usually occurs because of insufficient disk space.

**Action:** Delete unnecessary files to free up disk space or add disk space to the system.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28774: file cannot write to disk**

**Cause:** The output of a file failed. This error usually occurs because of insufficient disk space.

**Action:** Delete unnecessary files to free up disk space or add disk space to the system.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28775: file cannot close**

**Cause:** Failed to close a file which is used by a data access method. This error usually indicates memory corruption or a system error.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001



---

**Type:** ERROR

**Impact:** Other

**SSL-28776: Output buffer supplied is too small.**

**Cause:** The data returned by a function was too large for the supplied buffer.

**Action:** Call the routine again with a larger buffer.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28777: binding creation failure**

**Cause:** Failed to create a binding for use in the parsing of a parameter value. This error can be caused by the parameter value being in an incorrect format, such as a right parenthesis was not supplied where expected, or due to insufficient system memory.

**Action:** Make sure that the parameter is specified in the correct format. If the format is correct, free up system memory by terminating processes or adding more memory.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28778: Configuration parameter is not specified in the proper format.**

**Cause:** The configuration parameter was not specified in the proper format.

**Action:** Consult the Oracle Security Server documentation for a description of the proper format for this parameter.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28779: no data access method specified in parameter**

**Cause:** No method for data access was specified in the parameter value.

**Action:** Specify a method for data access in the parameter. Consult the Oracle Security Server documentation for the supported data access methods for this data type.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28780: invalid data access method specified by the parameter**

**Cause:** The data access method specified by the parameter value is not supported.

**Action:** Specify a supported data access method. Consult the Oracle Security Server documentation for the supported data access methods for this data type.

**Level:** 00001

**Type:** ERROR

---

**Impact:** Other

**SSL-28781: No data for the access method is specified in the parameter.**

**Cause:** No data was specified in the parameter for use with the specified access method.

**Action:** Consult the Oracle Security Server documentation for the data that must be specified for the access method.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28782: data source is not allocated**

**Cause:** No memory was allocated for a data source.

**Action:** Ensure that the application calls in the data source initialization function.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28783: invalid parameter**

**Cause:** There was no match for the parameter name that was used in the configuration file.

**Action:** Check your sqlnet.ora file for the correct parameter name.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28784: file name translation failure**

**Cause:** The translation of a file name from Oracle format to native format has failed.

**Action:** Specify a correct file name. Consult your Oracle documentation for the correct file name format.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28785: parameter does not exist**

**Cause:** A necessary configuration parameter was not found in the parameter file.

**Action:** Supply the required parameter.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28786: decryption of encrypted private key failure**

**Cause:** An incorrect password was used to decrypt an encrypted private key.

**Action:** Enter the correct password.

---

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28787: private key encryption failure**

**Cause:** This may have been caused by an error in the mkwallet parameter of the sqlnet.ora file.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28788: user provided invalid information**

**Cause:** User may have responded to a prompt with unexpected input, or an unknown error occurred.

**Action:** Enter correct input, or enable tracing to check the trace file for errors.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28790: NLS string open failure**

**Cause:** The opening of a string for use by the NLS subsystem failed.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28791: certificate verification failure**

**Cause:** Verification of the certificate, which the user supplied, failed.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28794: data type attribute did not initialize**

**Cause:** The initialization of the attribute data type failed. This error may be due to insufficient system resources.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

---

**SSL-28795: data type attribute did not terminate**

**Cause:** The termination of the use of the attribute data type subsystem failed.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28796: access method is not supported**

**Cause:** The method specified to access data is not supported.

**Action:** Use a supported access method. Consult your Oracle documentation to determine which access methods are supported.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28797: invalid key data type**

**Cause:** The type specified for a key is not supported.

**Action:** Correct the key type. Consult your Oracle documentation to determine which key types are supported.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28800: data source failed to open**

**Cause:** A data source (a file or a database) failed to open.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28802: invalid mode or data source in configuration file**

**Cause:** An invalid mode or data source has been specified in the configuration file (sqlnet.ora).

**Action:** Check the method parameter in the sqlnet.ora file. If the parameter value is correct, then enable tracing to determine the exact error.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28803: I/O operation failure**

**Cause:** The system or application failed to access a data source (file or database).

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

---

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28804: Data source cannot close.**

**Cause:** The data source, which could be either a file or a database), failed to close.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28805: Cannot retrieve information from the data source.**

**Cause:** The system or application failed to retrieve information from the data source (file or database).

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28806: Cannot write to the data source.**

**Cause:** The system or application failed to write to the data source (file or database).

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28807: Cannot update the data source.**

**Cause:** The system or application failed to update the data source (file or database).

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28808: Cannot retrieve method information from the configuration file.**

**Cause:** The system or application failed to retrieve method information from the sqlnet.ora configuration file.

**Action:** Check the method configuration parameters in the sqlnet.ora file. If the method configuration parameters are correct, then enable tracing to determine the exact error.

**Level:** 00001

---

**Type:** ERROR

**Impact:** Other

**SSL-28809: Cannot delete information from the data source.**

**Cause:** The system or application failed to delete information from the data source (file or database).

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28810: Cannot create key descriptor.**

**Cause:** The system failed to create a key descriptor.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28814: Cannot convert a number in Oracle format to native format.**

**Cause:** Failed to convert a number from Oracle format to native format.

**Action:** This is an internal programming exception. Enable tracing to try and reproduce the problem. Contact Oracle customer support and supply the trace file.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28815: Cannot convert a number in native format to Oracle format.**

**Cause:** Failed to convert a number from native format to Oracle portable format failed.

**Action:** This is an internal programming exception. Enable tracing to try and reproduce the problem. Contact Oracle customer support and supply the trace file.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28818: No package context provided.**

**Cause:** The context that holds the state of the security package was not passed to a function or procedure that was expecting it.

**Action:** This is an internal error. Enable tracing to find more information. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

---

**SSL-28836: Wallet is not open.**

**Cause:** The wallet to be used has not yet been opened.

**Action:** Call the function that opens the wallet.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28840: Wallet is already open.**

**Cause:** An attempt was made to open a wallet that was already open.

**Action:** This is a programming error. A wallet should only be opened once.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28841: Operation is not supported.**

**Cause:** An attempt was made to perform an operation that is not supported.

**Action:** This is a programming error. Please refer to Oracle documentation to determine which operations are supported.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28842: Incorrect file permissions**

**Cause:** The subject file did not have the correct permissions for the operation.

**Action:** Ensure that the file permissions allow the current operation.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28843: Operating system error while creating/opening file**

**Cause:** An operating system dependent error occurred while trying to create/open the file or while trying to set the appropriate permissions on the file.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28844: No wallet present**

**Cause:** There was no wallet in the location specified.

**Action:** Check to ensure that the wallet is in the correct directory location.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

---

**SSL-28845: No certificate**

**Cause:** Either there is no certificate or the system cannot find it.

**Action:** Check to ensure that the certificate is in the specified wallet.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28846: No private key**

**Cause:** Either there is no private key or the system cannot find it.

**Action:** Check to ensure that the private key is in the specified wallet.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28847: No clear private key file**

**Cause:** Failed to retrieve private key from SSO wallet

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28848: No encrypted private key file**

**Cause:** Failed to retrieve private key from the wallet

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28849: No Trustpoints**

**Cause:** The wallet does not have any trusted certificates

**Action:** Ensure that the wallet/keystore has trusted certificates.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28853: Initialization failure**

**Cause:** Either initialization or module loading has failed.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other



---

**SSL-28854: Memory allocation failure**

**Cause:** The allocation of memory failed due to insufficient system memory.

**Action:** Terminate other processes to free up memory or add memory to the system.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28855: Unsupported SSL operation**

**Cause:** An unsupported operation was attempted, for example, an attempt was made to select a mode of operation that is not allowed.

**Action:** Refer to the SSL chapter in the product's documentation.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28857: Unknown SSL error**

**Cause:** An unknown SSL error occurred.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28858: SSL protocol error**

**Cause:** An error occurred while negotiating the SSL handshake between two processes.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28859: SSL negotiation failure**

**Cause:** An error occurred during negotiation between two processes as part of the SSL protocol. This error will occur if the two sides to the connection do not support a common cipher suite.

**Action:** Configure each process so they support a common cipher suite. Then attempt the connection again. If error occurs again, enable tracing and retry the connection. Then contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28860: Fatal SSL error**

---

**Cause:** An error occurred during the SSL connection to the peer. It is likely that this side sent data which the peer rejected.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28861: SSL connection would block**

**Cause:** This error is informational. It should never be communicated to the user.

**Action:** Enable tracing and retry the connection to determine the exact cause of the error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28862: SSL connection failed**

**Cause:** This error occurred because the peer closed the connection.

**Action:** Enable tracing on both sides and examine the trace output. Contact Oracle Customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28863: SSL session not found**

**Cause:** This error is informational. It indicates that a specified session does not exist.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28864: SSL connection closed gracefully**

**Cause:** This error is informational. It indicates that the connection closed without error.

**Action:** This error is not normally visible to the user. Enable tracing and retry the connection. If the error persists, contact Oracle customer support.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28865: SSL connection closed**

**Cause:** The SSL connection closed because of an error in the underlying transport or because the peer process quit unexpectedly.

---

**Action:** Enable tracing and retry the connection. The trace output should indicate how the failure occurred.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28866: Invalid peer certificate encoding**

**Cause:** A field from a certificate in the peer's certificate chain could not be recognized.

**Action:** Refer to Oracle Wallet Manager documentation to find out how to obtain the peer's certificate. Then contact Oracle customer support with the peer's certificate chain.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28867: Integer value is too big.**

**Cause:** The certificate presented had an integer field whose value was too large.

**Action:** Refer to Oracle Wallet Manager documentation to find out how to obtain the peer's certificate. Then contact Oracle customer support with the peer's certificate chain.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28868: Peer certificate chain check failed.**

**Cause:** The check of the certificate list presented by the peer failed. Possible causes include: 1. the expiration of one of the certificates; 2. a certificate authority in a certificate was not recognized as a trust point; 3. the signature in a certificate could not be verified.

**Action:** Refer to Oracle Wallet Manager documentation to find out how to open your wallet and ensure that: 1. all of the certificates installed in your wallet are current 2. a certificate authority's certificate from your peer's certificate chain is added as a trusted certificate in your wallet

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28869: Peer's certificate is expired.**

**Cause:** The certificate being used to authenticate a client or server has expired.

**Action:** Obtain a new certificate, which is unexpired, and attempt the connection again.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28870: Name comparison failure**

---

**Cause:** A comparison of the names contained in two certificates failed.

**Action:** This error is not normally visible to the user. Enable tracing and retry the connection. If the error persists, contact Oracle customer support.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28871: Peer certificate chain is incomplete.**

**Cause:** The peer certificate chain presented was incomplete because it did not end with a self-signed root certificate.

**Action:** Refer to Oracle Wallet Manager documentation to find out how to open your wallet and ensure that: 1. the certificate authority's root certificate is self-signed. 2. a certificate authority's certificate from your peer's certificate chain is added as a trusted certificate in your wallet

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28872: Invalid peer certificate format**

**Cause:** The peer certificate does not conform to the X.509v3 standard.

**Action:** Refer to Oracle Wallet Manager documentation to find out how to get the peer certificate. Then contact Oracle customer support with the peer's certificate.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28874: SSL: I/O closed - override goodbye kiss**

**Cause:** This error is informational. It indicates that the connection closed without error.

**Action:** This error is not normally visible to the user. Enable tracing and retry the connection. If the error persists, contact Oracle customer support.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28875: SSL: use server-gated cryptographic suites**

**Cause:** This is used as a internal status indicator and not really an error.

**Action:** This message is not normally visible to the user. Enable tracing and retry the connection. If the error persists, contact Oracle customer support.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28876: Internet Explorer SGC Error**

**Cause:** An error occurred when processing a certificate sent from Microsoft Internet Explorer.

---

**Action:** This error is not normally visible to the user. Enable tracing and retry the connection. If the error persists, contact Oracle customer support.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28879: no protocol side set**

**Cause:** An application attempted to provide credentials to an SSL connection but had not previously stated whether the process was a client or a server.

**Action:** This error is not normally visible to the user. Enable tracing and retry the connection. If the error persists, contact Oracle customer support.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28884: invalid cipher suite**

**Cause:** An invalid cipher suite string has been specified in the product's configuration file.

**Action:** Refer to the product documentation for information about supported cipher suites.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28885: No certificate with the required key usage found.**

**Cause:** Certificate not created with the appropriate X509v3 key usage extension.

**Action:** Refer to Oracle Wallet Manager documentation to find out the supported key usages.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-28890: Entrust Login Failed**

**Cause:** An application failed to log in to an Entrust Profile. Possible causes include: 1. Entrust Admin/Authority was not online. 2. Invalid password for Entrust profile was specified. 3. Invalid path to Entrust profile was specified. 4. Invalid Entrust initialization file was specified. 5. Entrust Server Login program was not executed (server-side only).

**Action:** Make sure that 1. Entrust Authority is online; 2. Password for Entrust profile is specified correctly; 3. Path to Entrust profile is specified correctly; 4. A valid Entrust initialization file is provided; 5. Entrust Server Login program is run before the database startup. For more information, enable tracing and examine the trace output to get exact the Entrust failure codes.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

---

**SSL-29000: Certificate not installed**

**Cause:** Trying to delete a certificate which has not been installed.

**Action:** Refer to the Oracle Wallet Manager documentation for information about delete option.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29002: SSL transport detected invalid or obsolete server certificate.**

**Cause:** The client detected a mismatch between the server's distinguished name specified on the server's certificate and the server's SID or service name.

**Action:** Refer to the SSL chapter in Oracle Advanced Security Administrator's Guide for information about enabling server distinguished name matching. Contact your administrator to perform the appropriate action.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29003: SSL transport detected mismatched server certificate.**

**Cause:** The client detected a mismatch between the server's distinguished name specified on the server's certificate and the server's SID or service name.

**Action:** Refer to the SSL chapter in Oracle Advanced Security Administrator's Guide for information about enabling server distinguished name matching. Contact your administrator to perform the appropriate action.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29005: The certificate is invalid.**

**Cause:** The peer certificate encoding is invalid when using SSL 2.0.

**Action:** Refer to Oracle Wallet Manager documentation to find out how to obtain the peer's certificate. Then contact Oracle customer support with the peer's certificate chain.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29006: The certificate request message is invalid when using SSL 2.0.**

**Cause:** There is an error processing the SSL 2.0 REQUEST-CERTIFICATE message.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29007: Bad Clear Key Length when using SSL 2.0**

---

**Cause:** The clear key length of an SSL 2.0 Client Master key handshake message is invalid.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29008: Bad DH Param key length**

**Cause:** The length of the Diffie-Hellman params exceeds export restrictions.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29009: Bad encrypted key length when using SSL 2.0**

**Cause:** The encrypted key length of an SSL 2.0 Client Master key handshake message is invalid.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29010: Export key length does not meet export restrictions.**

**Cause:** The server sent a ServerKeyExchange message with an export key which does not meet export restrictions. For RSA, the export key must be exactly 512 bits.

**Action:** Obtain a certificate with the appropriate key length.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29011: Finished message is incorrect.**

**Cause:** The FINISHED message data verification failed.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29012: Bad key argument length when using SSL 2.0**

**Cause:** The key argument length of an SSL 2.0 Client Master Key handshake message is invalid.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

---

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29013: SSL MAC verification failure**

**Cause:** Verification of SSL Record MAC failed.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29014: Maximum fragment length extension is incorrect.**

**Cause:** The maximum fragment length extension specified is incorrect.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29015: incorrect message length**

**Cause:** The message length is not correct.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29016: inadequate PKCS1 message padding**

**Cause:** The message was not properly padded before encryption.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29017: The premaster secret length is incorrect.**

**Cause:** The premaster secret sent by the peer has an incorrect length.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29018: The premaster secret contains an incorrect version number.**



---

**Cause:** The premaster secret must contain the same version number as the ClientHello. The version sent by the client was incorrect.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29019: The protocol version is incorrect.**

**Cause:** There is a protocol version mismatch between the two peers.

**Action:** Specify the correct protocol version in the product's configuration file.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29020: The handshake record length is too long.**

**Cause:** The handshake record length exceeds the maximum that is allowed by the SSL specification.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29021: Secret key length is incorrect when using SSL 2.0.**

**Cause:** The length of the decrypted ENCRYPTED-KEY is incorrect.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29022: Operation is being attempted on the wrong side of the client/server connection.**

**Cause:** The SSL network layer has detected that the operation has been attempted on the wrong side of the client/server connection.

**Action:** Select the protocol side (of this protocol) to be the same as the one selected with a previous protocol.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29023: The buffers are not empty.**

**Cause:** Trying to free buffers that are not empty.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

---

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29024: Certificate validation failure**

**Cause:** The certificate sent by the other side could not be validated. This may occur if the certificate has expired, has been revoked, or is invalid for another reason.

**Action:** Check the certificate to determine whether it is valid. Obtain a new certificate, alert the sender that the certificate has failed, or resend.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29025: Error found in certificate check callback.**

**Cause:** The application callback failed during additional certificate validation. Additional checks include CRL validation and extension checking.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29026: Decryption failure**

**Cause:** SSL record decryption failed.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29027: Error in entropy collection**

**Cause:** The internal entropy collection failed to generate enough seed data.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29028: Server verification failure when using SSL 2.0**

**Cause:** Processing of an SSL 2.0 SERVER-VERIFY message failed.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

---

**Impact:** Other

**SSL-29029: SSL handshake already completed**

**Cause:** The system is trying to initiate a handshake when it has already been completed.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29030: SSL handshake is requested.**

**Cause:** The peer sends this message if it wishes to renegotiate. The application can either proceed with the renegotiation or reject the request.

**Action:** This is not an error. To find out more details enable tracing and retry the connection. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29031: SSL handshake is required.**

**Cause:** Renegotiation cannot proceed before the SSL handshake is completed.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29032: The given identity is not complete.**

**Cause:** The certificate list does not contain both private key and certificate.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29034: Correct cipher suite or client authentication is needed.**

**Cause:** Before installing a private key, a cipher suite or client authentication suite using the same key exchange algorithm must be installed first. This has not been done.

**Action:** Install a cipher suite or client authentication suite that uses the same key exchange algorithm as the private key before re-installing the private key.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29036: This feature is not supported**

---

**Cause:** Operation is not supported by the current connection parameters.

**Action:** Check the Oracle documentation to determine the appropriate connection parameters required for this operation.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29037: No certificate is present**

**Cause:** The other client or server sent a certificate message that contained no certificates.

**Action:** Check the other side (client or server) to ensure they have appropriate credentials.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29038: There are no matching certificates.**

**Cause:** The other client or server sent a certificate message that contained a certificate which was not signed by a trusted certificate authority (CA).

**Action:** Check to ensure that the other client or server sends a certificate which is signed by a CA that is in your trusted list. Or, include the CA certificate for the other client or server's certificate as a trustpoint in your wallet.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29039: There are no matching cipher suites.**

**Cause:** Neither end of the handshake can agree on a cipher suite.

**Action:** Check to ensure that both sides of the handshake select cipher suites that are supported.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29040: There are no supported cipher suites.**

**Cause:** This end of the handshake cannot support any cipher suites. This connection and the peer have some matching cipher suites, however, these cipher suites cannot be negotiated because they cannot be supported by the connection.

**Action:** Check to ensure that both sides of the handshake select cipher suites that are supported by the connection. Refer to Oracle documentation for supported cipher suites.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29043: Read is required.**

---

**Cause:** Renegotiation with the peer has not yet started. There is application data which must be processed before the handshake can proceed.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29044: Renegotiation has already been requested.**

**Cause:** Renegotiation has already been requested.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29045: Renegotiation request has been refused.**

**Cause:** A renegotiated handshake has been refused by the peer.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29046: Session is resumable.**

**Cause:** Server is trying to resume a session with different session parameters.

**Action:** Server should resume the session with the correct session parameters.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29047: Mismatch in Transport Layer Security extension**

**Cause:** Neither side can agree on a TLS extension.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29048: Unexpected message received.**

**Cause:** An unexpected message has been received.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

---

**Type:** ERROR

**Impact:** Other

**SSL-29049: Unknown record**

**Cause:** The record type is unknown.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29050: Installed client authentication mode is not supported.**

**Cause:** The enabled client authentication mode(s) cannot be used within the selected cipher suite.

**Action:** Enable a client authentication mode that can be used within the selected cipher suite.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29051: The given public key type is not supported.**

**Cause:** The public key in the first certificate is not supported.

**Action:** Check to ensure that the certificate complies with the X.509v3 standard.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29052: Write buffer is not empty.**

**Cause:** There is an attempt to free a write buffer that is not empty.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29084: The parameter specified is illegal.**

**Cause:** The parameter is not correct. For example, it could be bad input, or an invalid message.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29095: Index is not correct.**

**Cause:** The instance identified by the index parameter doesn't exist.

---

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29096: The given length is incorrect.**

**Cause:** The specified length is too small or is invalid.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29100: Cannot create local key ID.**

**Cause:** Creation of local key identifier for the certificate or the private key failed.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29101: Cannot add private key bag.**

**Cause:** The private key could not be added to the PKCS#12 object. Possible reasons are: (i) A required parameter is NULL (ii) The PKCS#12 construct is not supported (iii) An ASN.1 encoding error occurred in the certificate.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29102: Cannot add certificate bag.**

**Cause:** Creation of certificate bag failed. The application could have run out of memory.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29103: Cannot create PKCS #12 wallet.**

**Cause:** Creation of PKCS#12 wallet failed possibly due to memory allocation failure.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

---

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29104: Cannot add certificate request.**

**Cause:** Adding certificate request to the PKCS#12 wallet failed.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29105: Cannot export PKCS #12 wallet.**

**Cause:** A required parameter is NULL or the PKCS#12 construct is not supported.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29106: Cannot import PKCS #12 wallet.**

**Cause:** A required parameter is NULL or the BER-encoding is malformed.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29107: Cannot create PKCS #12 wallet.**

**Cause:** PKCS#12 wallet creation failed. The application may have run out of memory.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29108: Cannot initialize random object.**

**Cause:** The random object could not be initialized or seeded. Either memory allocation has failed or the pseudo random number generator module has not been installed.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR



---

**Impact:** Other

**SSL-29109: Cannot create private key object.**

**Cause:** The private key object could not be created. Memory allocation may have failed.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29110: Invalid PKCS #12 bag type**

**Cause:** The PKCS #12 bag type is invalid. Either one of the required parameters is NULL or the requested OID is not in the list.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29111: Invalid index**

**Cause:** The index passed for getting the bag type is less than 1.

**Action:** Check to ensure that the index is greater than 1.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29112: Cannot access attributes from a PKCS #12 certificate bag.**

**Cause:** The certificate cannot be accessed. One of the required parameters is probably NULL, or the index specified by the application does not contain a certbag, or the certificate could be malformed.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29113: Cannot access attributes from a PKCS #12 key bag.**

**Cause:** Retrieval of the private key failed. One of the required parameters is probably NULL or the index specified by the application does not contain a key bag.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

---

**SSL-29114: Cannot import private key.**

**Cause:** The private key could not be imported. One of the required parameters could be NULL or the encoded private key could be malformed.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29115: Cannot export private key.**

**Cause:** The private key could not be exported. Either the application ran out of memory or the key type is not valid.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29116: Cannot get PKCS #12 attributes.**

**Cause:** Retrieval of an attribute failed. One of the required parameters could be NULL.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29117: Cannot add PKCS #12 attributes.**

**Cause:** Could not add an attribute. The attribute parameter could be NULL.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29118: Cannot create PKCS #12 attributes.**

**Cause:** Creation of the attributes failed, possibly due to a memory allocation error.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29119: Cannot import certificate.**

**Cause:** The certificate cannot be imported. One of the required parameters could be NULL or the certificate has an invalid X.509 BER or DER encoding.

---

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29120: Cannot export certificate.**

**Cause:** The certificate cannot be exported. One of the required parameters could be NULL.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29122: could not add pkcs11 info to the pkcs12 wallet**

**Cause:** Failed while adding pkcs11 information into a pkcs12 wallet.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29123: could not get pkcs11 info from the pkcs12 wallet**

**Cause:** An error was encountered while retrieving pkcs11 information from the wallet.

**Action:** Enable tracing to determine the exact cause of this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29124: pkcs11 library name already set**

**Cause:** pkcs11 library information was already set in the wallet.

**Action:** Use a different wallet that does not have this information. If issue persists, enable tracing to determine the exact cause of the error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29125: pkcs11 token label already set**

**Cause:** pkcs11 token label information was already set in the wallet.

**Action:** Use a different wallet that does not have this information. If issue persists, enable tracing to determine the exact cause of the error. Contact Oracle customer support if needed.

---

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29126: pkcs11 token passphrase already set**

**Cause:** The pkcs11 token passphrase can be set only once in the wallet.

**Action:** Use a different wallet that does not have this information. If issue persists, enable tracing to determine the exact cause of the error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29127: unknown pkcs11 information**

**Cause:** An unknown pkcs11 information type was encountered. The wallet may have been corrupted due to a system error or memory corruption.

**Action:** Enable tracing and retry the failed operation. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29128: pkcs11 library name not set**

**Cause:** The wallet does not have pkcs11 library information.

**Action:** Ensure that the wallet was created with valid library location or update the wallet with this information.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29129: pkcs11 token label not set**

**Cause:** The wallet does not have pkcs11 token label information.

**Action:** Ensure that the wallet was created with valid token label information or update the wallet with this information.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29130: pkcs11 token passphrase not set**

**Cause:** The wallet does not have pkcs11 token passphrase.

**Action:** Ensure that the wallet was created with valid token passphrase information or update the wallet with this information.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

---

**SSL-29131: pkcs11 certificate label already set in wallet**

**Cause:** The pkcs11 certificate label was already set in the wallet.

**Action:** Use an empty wallet (created with orapki).

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29135: Seed generation for Random Number Generator failed.**

**Cause:** Generation of seed for random number generator failed.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29136: The allocated buffer is too small.**

**Cause:** The output buffer is too small.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29137: The global context is incorrect.**

**Cause:** The global context is incorrectly configured or invalid.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29140: Cannot create certificate object.**

**Cause:** Creation of the certificate object failed. The application could have run out of memory.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29141: Cannot import in the der format.**

**Cause:** Cannot import the certificate into the certificate object. The reason could be a malformed certificate.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

---

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29150: DES self-test failure**

**Cause:** DES power up self-test has failed.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29151: 3DES self-test failure**

**Cause:** 3DES power up self-test has failed.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29152: SHA-1 self-test failure**

**Cause:** The SHA-1 power up self-test has failed.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29153: RSA self-test failure**

**Cause:** The RSA power up self-test has failed.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29154: deterministic RNG self-test failure**

**Cause:** The deterministic Random Number Generator power up self-test has failed.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29155: continuous key pair consistency check self-test failure**

---

**Cause:** The public-private key pair check test failed.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29156: conditional RNG self-test failure**

**Cause:** Continuous Random Number Generator test, which is needed in FIPS mode, has failed.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29157: Unable to build an absolute path to the library.**

**Cause:** Not able to construct an absolute path to the location of the library.

**Action:** Enable tracing and attempt the connection again. Contact Oracle customer support with the trace output.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29158: Unable to open library.**

**Cause:** Opening of the library failed.

**Action:** Check to ensure that the library is present in the location specified, and that it has the appropriate file permissions.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29159: Unable to read library.**

**Cause:** Not able to read the library on which the DAC check has to be performed. Read call failed.

**Action:** Check if the library has the appropriate file permissions.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29160: NZ library being used is different.**

**Cause:** The NZ library being used at runtime is not the same one on which the digest was computed for the software integrity check.

**Action:** Check to ensure that the library being used is the same as the one on which the digest was pre-computed.

---

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29161: software integrity self-test failure**

**Cause:** The software integrity check test on the NZ shared library has failed.

**Action:** Check to ensure that the library being used is the same as the one on which the digest was pre-computed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29162: Non-FIPS cipher suites being used in FIPS mode.**

**Cause:** The cipher suite being used does not contain FIPS-approved algorithms.

**Action:**

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29163: Third party PKI vendor is not supported in FIPS mode.**

**Cause:** Third party PKI vendors like Entrust and MCS are not supported in FIPS mode.

**Action:** Use only Oracle PKI when running in FIPS mode.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29164: External PKCS #12 wallet is not supported in FIPS mode.**

**Cause:** PKCS #12 wallets created using third party software cannot be used in FIPS mode.

**Action:** Use only PKCS #12 wallets created by Oracle Wallet Manager when running in FIPS mode.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29176: CRL signature verification failed**

**Cause:** A CRL is verified before being used. CRL signature cannot be verified.

**Action:** Get a new CRL from CA

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29177: certificate serial number is not in CRL**

**Cause:** Cert is not revoked



---

**Action:**

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29178: certificate serial number is in CRL**

**Cause:** Cert has been revoked

**Action:** Reject the certificate

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29179: certificate validation check failed**

**Cause:** Could not complete checking certificate status with a CRL.

**Action:** Enable tracing to find more information on this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29180: Unsupported validation protocol**

**Cause:** The certificate validation protocol is not supported

**Action:** Make sure a supported certificate validation protocol is specified

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29181: ldap\_open failed**

**Cause:** Could not connect to the LDAP server

**Action:** Ensure that correct LDAP information was provided. Enable tracing to find more information. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29182: ldap\_bind failed**

**Cause:** Could not log in to the LDAP server

**Action:** Ensure that correct LDAP credentials were provided. Enable tracing to find more information. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29183: ldap\_search failed**

**Cause:** Failed to complete search operation in LDAP server

---

**Action:** Enable tracing to find more information on this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29184: ldap\_result failed**

**Cause:** Failed to retrieve results from LDAP operation

**Action:** Enable tracing to find more information on this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29185: ldap\_first\_attribute failed**

**Cause:** Could not get the first attribute from LDAP entry.

**Action:** Enable tracing to find more information on this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29186: ldap\_get\_values\_len failed**

**Cause:** Failed to retrieve attribute values from LDAP entry

**Action:** Enable tracing to find more information on this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29187: unsupported validation mechanism**

**Cause:** The validation mechanism specified in OID is not supported

**Action:** Make sure a supported validation mechanism is set in OID

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29188: ldap\_count\_entries failed**

**Cause:** Failed to get count of entries from a search result chain.

**Action:** Enable tracing to find more information on this error. Contact Oracle customer support if needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

---

**SSL-29189: No entry found in OID**

**Cause:** CRL not found in OID

**Action:** Upload the CRL to OID

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29190: Multiple entries in OID**

**Cause:** For a given issuer name there should be only one CRL in OID

**Action:** Make sure there is only one CRL for a given issuer name in OID

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29191: OID connection information not set**

**Cause:** To connect to OID the connection information must be available

**Action:** Set the OID connection information.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29192: Validation mechanism not set in OID**

**Cause:** The validation mechanism to be used is not set in OID

**Action:** Set validation mechanism to be used in OID at cn=ValidationMechanism, cn=Validation, cn=PKI, cn=Products, cn=OracleContext

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29193: no CRL found using CRLDP mechanism**

**Cause:** A CRL could not fetched using CRL Distribution point (CRLDP)

**Action:** Contact the CA

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29194: no CRL found in cache**

**Cause:** CRL not in cache

**Action:**

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29195: CRL is expired**

---

**Cause:** CRL nextUpdate time is in the past

**Action:** Get a new CRL from the CA

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29222: Distinguished name does not match.**

**Cause:** Distinguished name (DN) on certificate doesn't match user.

**Action:** Create the global user in the database with the DN that matches with the one in the user certificate on the client side.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29223: Cannot create certificate chain.**

**Cause:** Unable to create a certificate chain with the existing trust points for the certificate that is to be installed.

**Action:** Install the trust point that signed the certificate.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29224: Cannot locate matching certificate request.**

**Cause:** No matching certificate request for the certificate was found.

**Action:** Install the correct certificate.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29225: Certificate already installed.**

**Cause:** Attempting to install a certificate into a persona which already has it.

**Action:** Do not install the certificate.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29226: No matching private key found.**

**Cause:** Could not locate a matching private key in the persona for the given certificate (public key).

**Action:**

**Level:** 00001

**Type:** ERROR

**Impact:** Other

---

**SSL-29227: Certificate is expired.**

**Cause:** Certificate is no longer valid..

**Action:** Obtain another certificate or renew this certificate.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29228: Cannot calculate the number of bytes for output.**

**Cause:** The cryptographic engine is confused about the algorithm.

**Action:** Check the parameters being used with the cryptographic functions.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29229: the magic number found in the header does not match expected**

**Cause:** The input TDU has either been corrupted or is not being used correctly.

**Action:** Check that the TDU is being used from the beginning. If possible, compare the size of the TDU upon generation to the size being used.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29230: the header length is not sufficient for message header**

**Cause:** The input TDU has either been corrupted or it is not being used correctly.

**Action:** Check that the TDU is being used from the beginning. If possible, compare the size of the TDU upon generation to the size being used.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29231: the cryptographic engine failed to initialize**

**Cause:** During initialization of the cryptographic engine, some failure occurred. Possible causes include running out of memory and trying to seed the random number generator.

**Action:** Make sure the executable has been linked with compatible library versions, and that you are not running out of swap space.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29232: the cryptographic engine key initialization failed**

**Cause:** During initialization of a key for cryptography, some failure occurred. This includes running out of memory and passing illegal arguments.

**Action:** Make sure the executable has been linked with compatible library versions, and that the correct parameters are being used for the cryptographic functions.

---

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29233: the key object could not be encoded**

**Cause:** The key object may be corrupted or may be an unsupported type.

**Action:** Check the key object being passed to the encoding routine.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29234: a key object was not extracted from encoding**

**Cause:** The encoding may be corrupted or may not be a key object at all.

**Action:** Check the encoding and parameters passed to decoding routine.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29235: the key information could not be retrieved**

**Cause:** The key may be corrupted or may be an unsupported type.

**Action:** Check the parameters being used with the cryptographic functions.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29236: the random number generator will not accept seed**

**Cause:** The cryptographic engine may have run out of memory.

**Action:** Make sure the executable has been linked with compatible library versions.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29237: the cryptographic engine could not finish the algorithm**

**Cause:** The cryptographic engine does not have enough information to correctly finish applying the algorithm.

**Action:** Check the parameters being used with the cryptographic functions.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29238: the cryptographic engine could not apply the algorithm**

**Cause:** The cryptographic engine does not have enough information to correctly apply the algorithm.

**Action:** Check the parameters being used with the cryptographic functions.

---

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29239: the cryptographic engine could not initialize the algorithm**

**Cause:** The cryptographic engine does not have enough information to correctly initialize the algorithm.

**Action:** Check the parameters being used with the cryptographic functions.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29240: the cryptographic engine does not recognize the algorithm**

**Cause:** The application may be passing wrong parameters.

**Action:** Check the parameters being used with the cryptographic functions.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29241: a buffer block needs more space but its length is fixed**

**Cause:** The application has preallocated an output buffer that is too short for the operation and has specified that the buffer should not grow as needed.

**Action:** Either preallocate a larger buffer or allow the toolkit to grow the output buffer as needed.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29242: the asymmetric key is too short to be used with the data.**

**Cause:** An asymmetric key must be at least 11 bytes longer than the data it is being used to encrypt.

**Action:** Use an asymmetric key with more bits or break the data into smaller pieces.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29243: the toolkit does not recognize the type of key being used**

**Cause:** The application may be passing wrong parameters.

**Action:** Check the parameters being used with the toolkit functions.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29245: the toolkit does not recognize the function being used**

---

**Cause:** The application is probably passing the wrong parameters.  
**Action:** Check the parameters being used with the toolkit functions.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29246: the toolkit could not parse the tdu**

**Cause:** The TDU could be corrupted.

**Action:** Check the parameters being used with the toolkit functions.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29247: an unopen toolkit object was used before it was opened**

**Cause:** Some toolkit objects must be opened before they can be used.

**Action:** Check the parameters being used with the toolkit functions.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29248: an unrecognized WRL was used to open a wallet**

**Cause:** WRL's have a specific set of types and must be formatted correctly.

**Action:** Check the parameters being used with the toolkit functions.

**Level:** 00001

**Type:** ERROR

**Impact:** Other

**SSL-29249: an unrecognized state was passed to a cryptographic function**

**Cause:** The application is probably passing the wrong parameters.

**Action:** Check the parameters being used with the toolkit functions.

**Level:** 00001

**Type:** ERROR

**Impact:** Other



---

## SSLCFG-00131 to SSLCFG-00202

**SSLCFG-00131: invalid authentication type**

**Cause:** The value specified for authentication type was not valid.

**Action:** See the FMW Admin Guide for valid authentication types.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SSLCFG-00148: unable to validate one or more cipher value(s) {0}**

**Cause:** The specified cipher value(s) was invalid.

**Action:** See the FMW Admin Guide for valid cipher values.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SSLCFG-00149: unable to validate one or more SSL version value(s) {0}**

**Cause:** The specified SSL version value(s) was invalid.

**Action:** See the FMW Security Guide for valid SSL version values.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SSLCFG-00150: version incompatible with the cipher(s)**

**Cause:** The specified SSL version was incompatible with the cipher(s).

**Action:** Use SSL version "v1" with AES ciphers.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SSLCFG-00152: ciphers are incompatible with the authentication type**

**Cause:** The specified cipher was incompatible with the authentication type.

**Action:** See the FMW Admin Guide for valid cipher and authentication type combinations.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**SSLCFG-00173: invalid certificate validation method**

**Cause:** The method specified for certificate validation was not valid.

**Action:** See the FMW Admin Guide for valid certificate validation methods.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SSLCFG-00189: path to the CRL file/directory not specified**

**Cause:** CRL file/directory path was required to be provided with the certificate validation method "crl".

**Action:** Specify a valid CRL file/directory path.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SSLCFG-00194: invalid wallet/keystore name**

**Cause:** An invalid value was provided for wallet/keystore name.

**Action:** Ensure that the wallet/keystore name is a valid file name.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SSLCFG-00197: cannot change password of auto-login wallet**

**Cause:** Password could be changed only for a password protected wallet.

**Action:** Provide a password protected wallet as input.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SSLCFG-00199: wallet/keystore required with the authentication type {0}**

**Cause:** Wallet/Keystore value was not specified.

**Action:** Provide a wallet/keystore value with this authentication type.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SSLCFG-00200: v2Hello cannot be selected by itself. Select at least one more version.**

**Cause:** The version vHello could not be selected by itself.

**Action:** Select either v1 or v3 along with v2Hello.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**SSLCFG-00201: wallet/keystore being used for SSL, deletion failed.**

**Cause:** Could not delete wallet/keystore since it was being used for SSL.

**Action:** Select a wallet/keystore that is not in use.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**SSLCFG-00202: duplicate wallet/keystore name**

**Cause:** A pre-existing wallet/keystore with this name was found.

**Action:** Provide a different name for the new wallet/keystore.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration



---

## TCM-00006 to TCM-99009

**TCM-00006: The NameId for the request is not valid.**

**Cause:** The NameId for a service request did not contain a Name or an Identifier.

**Action:** Provide either a Name or an Identifier for a service request.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-00007: The Id for the request is not valid.**

**Cause:** The document identifier for the request was not valid. The value supplied was null or an empty string.

**Action:** Provide a valid document identifier for a document service request.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-00008: The SectionFlags for the request are not valid.**

**Cause:** The wrong section flags were provided for the request.

**Action:** Consult the API documentation for the proper section flags for the request.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TCM-00009: No session has been established.**

**Cause:** A session was expected to exist but was not found. This may occur if operations were called after logging out.

**Action:** Log in and properly establish a session before attempting an operation.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-00010: The version of the JRE used by the repository is too low to support Imaging. The required minimum is {0}. The repository is using {1}.**

---

**Cause:** An attempt was made to establish a connection to a Content Server repository using the wrong JRE.

**Action:** Upgrade the Content Server JRE to the minimum required version. The required version will be stated in the error message.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-00012: Unable to log in to the UOA repository**

**Cause:** IPM could not log in to the UOA system.

**Action:** Check to make sure the UOA system is up and running properly.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-00013: Basic Authentication requires SSL.**

**Cause:** An attempt was made to log in to IPM without using SSL, which is required.

**Action:** Configure the IPM Server for SSL and use https in the web services URL.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**TCM-00015: Unable to find file {0}**

**Cause:** A file used for input could not be found.

**Action:** Check the file path given in the error message and verify that it exists.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-00016: Unable to open file {0}**

**Cause:** A file used for input could not be opened.

**Action:** Check the file path given in the error message and verify that it is readable.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-00020: Unable to authenticate user.**

**Cause:** Invalid credentials were supplied during login.

**Action:** Provide valid credentials.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

---

**TCM-00021: This session is already established.**

**Cause:** An attempt was made to log in to a session that was already established.

**Action:** Either use the existing session without logging in again, or log out to establish a new session.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**TCM-00022: Service was called without credentials. The calling user cannot be authenticated.**

**Cause:** No credentials were provided for the service request.

**Action:** Ensure the proper security credentials are applied to the login services.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**TCM-00026: The requested definition is not found.**

**Cause:** The user does not have access to the definition.

**Action:** Check the user's access to the requested definition.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-00027: User does not have permission to access this page.**

**Cause:** An attempt was made to access a definition page that the user does not have permission to access.

**Action:** Check the user's permissions to the requested definition.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-00028: The definition arrays supplied are empty.**

**Cause:** The definitions supplied for an import or export operation were empty arrays.

**Action:** Make sure that the definitions arrays are filled in with valid definition NameIds.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TCM-00029: The {0} section is read-only and cannot be modified.**

**Cause:** At least one definition section specified for modify was read only and cannot be changed.

**Action:** Remove the read-only section from the modify section set argument.

**Level:** 1

---

**Type:** ERROR  
**Impact:** Programmatic  
**TCM-00040: Encountered exception initializing regions.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** NOTIFICATION  
**Impact:** Requests/Responses  
**TCM-00041: Cache is Ready = {0}**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** NOTIFICATION  
**Impact:** Requests/Responses  
**TCM-00042: Cache Distributed = {0}**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** NOTIFICATION  
**Impact:** Requests/Responses  
**TCM-00043: Imaging region exists.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** WARNING  
**Impact:** Requests/Responses  
**TCM-00044: Cache failed during initialization and may be disabled.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** WARNING  
**Impact:** Requests/Responses  
**TCM-00045: The cache age limit must be set to a positive number**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** WARNING  
**Impact:** Requests/Responses



---

**TCM-00102: Workflow Agent login failure.**

**Cause:** The Workflow Agent failed to log in.

**Action:** Review the server logs for further information.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**TCM-00103: Workflow Agent logout failure.**

**Cause:** The Workflow Agent failed to log out.

**Action:** Review the server logs for further information.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**TCM-00104: Workflow Agent error processing a message.**

**Cause:** An error occurred trying to process a workflow agent message.

**Action:** Review the server logs for further information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-00105: Document {0} returning to workflow agent queue for retry.**

**Cause:**

**Action:**

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**TCM-00106: Workflow agent processing fault recorded for document {0}.**

**Cause:** An error was encountered processing a document. The document was identified in the error message. The error could be due to the workflow server being down.

**Action:** Review the server logs for further information. The workflow agent will attempt to reprocess the document.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-00107: Workflow agent cannot record fault for document {0}. Returning to workflow agent queue for retry.**

**Cause:** An error was encountered processing a document, and the workflow agent was unable to record the error as a fault. The document was identified in the error message.

**Action:** Review the server logs for further information. The workflow agent will attempt to reprocess the document.

---

**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses  
**TCM-00110: Constructed Input Agent Bean.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** NOTIFICATION  
**Impact:** Requests/Responses  
**TCM-00111: Destroyed Input Agent Bean.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** NOTIFICATION  
**Impact:** Requests/Responses  
**TCM-00112: Input Agent encountered an error during shutdown.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** WARNING  
**Impact:** Requests/Responses  
**TCM-00113: An error occurred trying to read the Input Agent configuration.**  
**Cause:** An error occurred trying to read the Input Agent Bean configuration.  
**Action:** Review the server logs for further information.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses  
**TCM-00114: An error occurred initializing the Input Agent Bean.**  
**Cause:** An error occurred initializing the Input Agent Bean.  
**Action:** Review the server logs for further information.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses  
**TCM-00115: Beginning Input Agent initialization.**  
**Cause:**  
**Action:**  
**Level:** 1  
**Type:** NOTIFICATION

---

**Impact:** Requests/Responses

**TCM-00116: Input Agent initialization is complete.**

**Cause:**

**Action:**

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**TCM-00118: Input Agent timer service is not initialized. Cannot continue.**

**Cause:** Input Agent timer service is not initialized.

**Action:** Check the Application Server installation and restart the service.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-00119: Input Agent configuration is empty. Cannot continue.**

**Cause:** Input Agent configuration is empty.

**Action:** Check the JDBC connection and reboot the server.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-00120: Input Agent time interval is not set. Cannot continue.**

**Cause:** Input Agent time interval is not set.

**Action:** Update the Check Interval setting to a valid value in the IPM config MBean.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-00121: An error occurred resetting an input job.**

**Cause:** An error occurred resetting an input job.

**Action:** Review the server logs for further information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-00122: An error occurred checking for work.**

**Cause:**

**Action:**

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

---

**TCM-00126: Beginning Input Agent servlet initialization.**

**Cause:**

**Action:**

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**TCM-00127: Input Agent servlet initialization is complete.**

**Cause:**

**Action:**

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**TCM-00128: The JMS Queue browser cannot be closed properly.**

**Cause:** There was a problem closing the JMS Queue browser.

**Action:** Review the server logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-00129: Input Agent is checking for work.**

**Cause:**

**Action:**

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**TCM-00150: Constructed Input Filing MDB.**

**Cause:**

**Action:**

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**TCM-00151: Destroyed Input Filing MDB.**

**Cause:**

**Action:**

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**TCM-00152: Error while unregistering Input Filing MDB.**

**Cause:** An error occurred while unregistering Input Filing MDB.

---

**Action:** Review the server logs for further information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-00153: Beginning filing for Input {0} and data source {1}.**

**Cause:**

**Action:**

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**TCM-00154: Filing {0} completed successfully with {1} documents processed successfully out of {2} documents.**

**Cause:**

**Action:**

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**TCM-00155: Filing {0} failed with {1} documents that failed to index.**

**Cause:**

**Action:**

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**TCM-00156: Error indexing document number {0}.**

**Cause:** An error occurred while indexing a document.

**Action:** Review the server logs for further information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-00157: An error occurred filing file {0}.**

**Cause:** An error occurred while filing a job.

**Action:** Review the server logs for further information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-00158: Failed to cancel job.**

**Cause:** Failed to cancel a job.

**Action:** Review the server logs for further information.

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-00159: Cannot determine what Input Source to use for job and cannot abort or cancel job.**

**Cause:**

**Action:**

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**TCM-00160: Input Filing MDB failed to log out.**

**Cause:**

**Action:**

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**TCM-00161: Failed to resume filing for data source {0} and batch {1}.**

**Cause:**

**Action:**

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**TCM-00162: Failed to load Batch for new filing.**

**Cause:**

**Action:**

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**TCM-00163: An error occurred while completing a batch.**

**Cause:**

**Action:**

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**TCM-00164: Input Agent cannot find WLS Runtime MBean server.**

**Cause:**

**Action:**

**Level:** 1

---

Type: WARNING

Impact: Requests/Responses

**TCM-00165: The Input {0} is currently marked offline, so the request to process data source {1} is being rolled back**

Cause:

Action:

Level: 1

Type: NOTIFICATION

Impact: Requests/Responses

**TCM-00166: Resubmitting job for input source {0} due to error: {1}**

Cause:

Action:

Level: 1

Type: NOTIFICATION

Impact: Requests/Responses

**TCM-00170: Constructed Ticket Agent MDB.**

Cause:

Action:

Level: 1

Type: NOTIFICATION

Impact: Requests/Responses

**TCM-00171: Destroyed Ticket Agent MDB.**

Cause:

Action:

Level: 1

Type: NOTIFICATION

Impact: Requests/Responses

**TCM-00172: Beginning Ticket Agent servlet initialization.**

Cause:

Action:

Level: 1

Type: NOTIFICATION

Impact: Requests/Responses

**TCM-00173: Ticket Agent servlet initialization is complete.**

Cause:

Action:

Level: 1

Type: NOTIFICATION

---

**Impact:** Requests/Responses

**TCM-00174: An error occurred while restarting the Ticket Agent MDB.**

**Cause:** An error occurred while restarting the Ticket Agent MDB.

**Action:** Review the server logs for further information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-00175: Ticket Agent timer service is not initialized. Cannot continue.**

**Cause:** Ticket Agent timer service is not initialized.

**Action:** Check the Application Server configuration and restart the service

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-00176: An error occurred while initializing Ticket Agent MDB.**

**Cause:** An error occurred while initializing Ticket Agent MDB.

**Action:** Review the server logs for further information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-00177: Beginning Ticket Agent initialization.**

**Cause:**

**Action:**

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**TCM-00178: Ticket Agent initialization is complete.**

**Cause:**

**Action:**

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**TCM-00179: Encountered an error while attempting to clean up expired tickets from the IPM system**

**Cause:**

**Action:**

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses



---

**TCM-00196: Encountered an error while logging out of IPM system**

**Cause:**

**Action:**

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**TCM-00199: IPM API error encountered, attempting restart.**

**Cause:** An IPM API error was encountered.

**Action:** Review the server logs for further information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-00777: A database error occurred.**

**Cause:** An operation caused an unexpected database error.

**Action:** Review the logs for the specifics of the database error. You may need to contact Oracle Support Services to resolve the issue.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TCM-00787: A repository error occurred.**

**Cause:** An unknown error has occurred with a repository.

**Action:** Review the logs to determine the cause of the error. You may need to contact Oracle Support Services to resolve the issue.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-00788: The following error is reported by the repository: {0}**

**Cause:** An error has occurred with a repository. The details of the error were part of the error message.

**Action:** Review the message and logs to determine the cause of the error. You may need to contact Oracle Support Services to resolve the issue.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-00789: The Content Server returned no data. This may be an indication of an incorrect server port number, or a connection failure during a request.**

**Cause:** The Content Server was shut down in the middle of a request

**Action:** Check to make sure the Content Server is still up and running.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**TCM-00790: UOA shared libraries are not properly deployed and targeted to this IPM server.**

**Cause:** The UOA shared libraries have not been properly deployed and targeted to this IPM server. This occurs most often when UOA is not installed at the same time as IPM from configuration wizard.

**Action:** Ensure that the UOA shared libraries are deployed and targeted to the IPM Managed Server instances.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-00791: The Content Server does not have a defined document profile field.**

**Cause:** The Content Server repository did not have a defined profile trigger.

**Action:** Configure a profile trigger in the Content Server. This can be accomplished by setting EnableIdcProfileField=1 and then restarting the Content Server.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-00888: Validation Error.**

**Cause:** Data supplied to an imaging operation was invalid.

**Action:** Correct the invalid data and resend.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**TCM-00998: Multiple errors in a subsystem. {0}**

**Cause:** An error occurred in UOA that has multiple causes.

**Action:** Review the logs for the errors. You may need to contact Oracle Support Services to resolve the issue.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-00999: Error in a subsystem. {0}**

**Cause:** An error occurred in a repository, or when communicating with a workflow server.

**Action:** Review the logs for the error. You may need to contact Oracle Support Services to resolve the issue.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**TCM-01008: Unable to add application. The application category already exists.**

**Cause:** A UOA category of the same name already exists.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-01009: Unable to add application. The system document category does not exist.**

**Cause:** A UOA system document category has not been properly configured.

**Action:** Ensure that the UOA repository has been initialized prior to creating applications.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-01010: Unable to add application. The application documents folder already exists**

**Cause:** A UOA folder used for storage of application documents already exists.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-01017: Unable to update application. User does not have proper permissions.**

**Cause:** The current user has not been given the proper rights to update the application.

**Action:** Refrain from modifying the application until the proper rights have been granted.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-01018: Unable to delete application. The application contains documents.**

**Cause:** A user attempted to delete an application that still contains documents.

**Action:** Delete all of the documents belonging to the application before attempting to delete the application.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-01019: Another application operation is in progress. Try again later.**

**Cause:** A user attempted an application operation while another operation was in progress.

**Action:** Wait 30 to 60 seconds and try again.

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-01020: This document operation is blocked by repository database inconsistencies. This may be due to concurrent application activity (for example, adding, modifying, or deleting an application). Try again later.**

**Cause:** A user attempted a document operation while the repository metadata table is in an inconsistent state. This could be due to a concurrent application operation.

**Action:** Wait 30 to 60 seconds and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-01021: Failed to delete application in the repository. Contact an administrator for assistance.**

**Cause:** The system was not able to delete the application in the repository.

**Action:** Review the logs for possible reasons.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-01025: The NameId for the application does not contain a name or an identifier.**

**Cause:** The NameId for the application did not contain a name or an identifier.

**Action:** Provide either a name or an identifier for the application.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-01027: Lifecycle policy action specification, {0}, is not found.**

**Cause:** The specified lifecycle policy action specification was not found in the UOA system.

**Action:** Ensure that UOA is configured with the specified lifecycle policy action specification.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-01028: Lifecycle policy date rule specification, {0}, is not found.**

**Cause:** The specified lifecycle policy date rule specification was not found in the UOA system.

**Action:** Ensure that UOA is configured with the specified lifecycle policy date rule specification.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**TCM-01031: Missing a closing delimiter near "{0}".**

**Cause:** An opening delimiter ([]) was found without a closing delimiter (]) in a Format Value function.

**Action:** Review the Format Value text and ensure that there are matching delimiters.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TCM-01032: The workflow mapping function, {0}, is not a known function.**

**Cause:** A workflow Format Value contains a reference to an unknown function.

**Action:** Review the API documentation for valid workflow function names.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TCM-01033: The workflow mapping function, {0}, is not allowed.**

**Cause:** A workflow function was specified in a location where it is not allowed.

**Action:** Review the API documentation for valid workflow function usage.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TCM-01034: The workflow mapping function, {0}, has too many parameters.**

**Cause:** Too many parameters were provided for a workflow function.

**Action:** Review the API documentation for valid workflow function usage.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TCM-01035: The workflow mapping function, {0}, requires a parameter.**

**Cause:** A workflow function was missing a required parameter.

**Action:** Review the API documentation for valid workflow function usage.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TCM-01036: The workflow mapping function, {0}, does not accept a parameter.**

**Cause:** A parameter was provided to a workflow function that does not accept parameters.

**Action:** Review the API documentation for valid workflow function usage.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**TCM-01037: Null applications are not allowed.**

**Cause:** A null value was provided to a function that requires an application definition.

**Action:** Provide a valid, non-null, application definition.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-01039: The document is not allowed to be updated. It is read-only.**

**Cause:** The current user was not given the proper rights to update documents belonging to the application.

**Action:** Refrain from modifying the application's documents until the proper rights have been granted.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02001: The requested document, id={0}, was not found.**

**Cause:** Document does not exist, or user does not have proper rights.

**Action:** Verify document and user rights before attempting to access the document.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02003: The requested id, {0}, is not a document.**

**Cause:** Item returned by UOA is not a document.

**Action:** Retry action against document.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02004: The document is currently locked by {0}**

**Cause:** Document is already locked.

**Action:** Unlock document and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02005: The document cannot be locked**

**Cause:** Document could not be locked to the user.

**Action:** Verify user permissions and try again.

---

**Level: 1**

**Type: ERROR**

**Impact: Requests/Responses**

**TCM-02006: The document is locked to another user: {0}**

**Cause:** Document is locked to another user.

**Action:** Administrator or current document owner must unlock document.

**Level: 1**

**Type: ERROR**

**Impact: Requests/Responses**

**TCM-02007: The document cannot be unlocked**

**Cause:** Document could not be unlocked by the user.

**Action:** Verify the document state and try to unlock document again.

**Level: 1**

**Type: ERROR**

**Impact: Requests/Responses**

**TCM-02008: The documents cannot be deleted because they are in a legislative hold in the repository.**

**Cause:** An attempt was made to delete documents that are in legislative hold.

**Action:** Refrain from deleting documents until legislative holds have been removed.

**Level: 1**

**Type: NOTIFICATION**

**Impact: Requests/Responses**

**TCM-02009: Primary application category not found.**

**Cause:** Primary application category not found in UOA.

**Action:** Verify that the UOA system has been initialized correctly for IPM.

**Level: 1**

**Type: ERROR**

**Impact: Requests/Responses**

**TCM-02011: The document is not locked to the requester**

**Cause:** Document is not locked to the user.

**Action:** Document must be unlocked before trying again.

**Level: 1**

**Type: ERROR**

**Impact: Requests/Responses**

**TCM-02012: An invalid file was received "{0}".**

**Cause:** Invalid file was given to the API.

**Action:** Verify the file and try again.

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02014: Original document field values cannot be retrieved.**

**Cause:** Document fields could not be retrieved from UOA.

**Action:** Verify user permissions and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02015: Invalid field value for field "{0}".**

**Cause:** Could not resolve field for field value.

**Action:** Verify application definition and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02016: The file name is invalid. A file name must have a file extension, cannot be empty or null, and cannot include any path information.**

**Cause:** An invalid file name was provided for the document.

**Action:** Enter a valid file name. Do not include any path information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02017: Document replacement is not allowed for this document.**

**Cause:** Document cannot be replaced because it is not locked out.

**Action:** Check out document and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02019: Replacement or versioning is not allowed for this document.**

**Cause:** Document cannot be updated.

**Action:** Document update is not allowed for documents in this application.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02020: Page Management functions are valid only with TIFF document types.**

**Cause:** Cannot modify because it is not a tiff document.

**Action:** Page management functions are only valid for tiff documents.

**Level:** 1



---

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02021: A page management operation cannot complete because of a system error.**

**Cause:** Page operation failed. System error occurred accessing image.

**Action:** Verify and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02022: The supporting content key is invalid.**

**Cause:** Supporting content key for the document is invalid.

**Action:** Enter unique supporting content key.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02023: Cannot find the field {0}, id {1} in the application context.**

**Cause:** Document missing field information. Cannot create document.

**Action:** Enter correct field information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02024: Invalid upload token.**

**Cause:** Token for the uploaded file is invalid.

**Action:** Use valid token.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02025: Cannot move document. Source and destination application are the same.**

**Cause:** Source and destination applications are the same.

**Action:** Specify different application when moving documents.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02026: The document data provided to the service is invalid**

**Cause:** Invalid data stream was given to the API

**Action:** Check the file and make sure it is valid

**Level:** 1

---

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02027: The requested supporting content for the document, id={0}, key={1}, was not found.**

**Cause:** Supporting content key does not return any results.

**Action:** Verify supporting content key is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02028: This document consists of multiple versions. The destination application does not support versioning.**

**Cause:** Document consists of multiple versions. Destination application does not support versioning.

**Action:** Choose a destination application that supports versioning.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02029: Write permissions are required on the document in order to set supporting content.**

**Cause:** Write permissions are required on the document in order to set supporting content.

**Action:** Verify user permissions are set correctly for the document

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02030: View permissions are required on the document in order to get supporting content.**

**Cause:** View permissions are required on the document in order to get supporting content.

**Action:** Verify user permissions are set correctly for the document

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02031: Copy failed, document not found.**

**Cause:** Document does not exist or user does not have rights to copy.

**Action:** Verify document and user rights before attempting to copy.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02032: Moved failed, no document move rights**

---

**Cause:** Document does not exist or user does not have rights to move.

**Action:** Verify document and user rights before attempting to move.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02033: Update failed, no document update rights**

**Cause:** Document does not exist or user does not have rights to update

**Action:** Verify document and user rights before attempting to update.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02034: The document version must be greater than 0.**

**Cause:** Document version must be greater than 0

**Action:** Set version to a value greater than 0

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02035: File, "{0}," is zero length. Documents must have a file length greater than zero.**

**Cause:** File with zero length was given to the API.

**Action:** Check the file and make sure its length is greater than zero.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02036: Either a valid file, a valid field list, or both, are required to update a document.**

**Cause:** Invalid file and field list has been passed into update document.

**Action:** Verify valid file and field list have been passed in.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02037: The supporting content key already exists.**

**Cause:** Supporting content key for the document already exists.

**Action:** Enter unique supporting content key.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02038: The document identifier, {0}, is invalid.**

---

**Cause:** The document identifier for the request was invalid.

**Action:** Enter a valid document identifier.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02039: The document action could not be performed because the document is under records management in the repository.**

**Cause:** A user attempted a document operation while the document is under records management in the repository.

**Action:** Refrain from operating on a records managed document.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-02040: The file timeout {0} is invalid for document operations. The timeout must be greater than or equal to 0.**

**Cause:** The timeout for document operations must be greater than or equal to 0. The current value is invalid

**Action:** Set timeout value to greater than or equal to 0.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-03004: Annotation list is Null**

**Cause:** Annotation list to search is Null.

**Action:** Ensure that annotation list object is not null.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-03012: An error occurred while saving annotations**

**Cause:** An error occurred while saving annotations.

**Action:** A repository-specific exception occurred when saving annotations. Check the repository-specific exception stack for diagnostic details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-03018: Error reading file {0}**

**Cause:** An error occurred while reading the file

**Action:** Check the file and its permissions

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**TCM-03024: An annotation cannot be accepted due to the lack of permission.**

**Cause:** An annotation cannot be accepted due to the lack of permission.

**Action:** Ensure that all annotations' security settings are compatible with the user's permission set.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-03029: Invalid document Id saving/retrieving document annotations: {0}**

**Cause:** Invalid document Id when saving/retrieving document annotations.

**Action:** Supply a valid document Id.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-03035: User does not have sufficient annotation permission in the destination application.**

**Cause:** User does not have sufficient annotation permission in the destination application.

**Action:** Ensure that the user has sufficient annotation permissions in the destination application for any annotations to be applied.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-03036: An error occurred retrieving annotations for the document.**

**Cause:** Annotations for the specified document could not be retrieved.

**Action:** A repository-specific exception occurred when saving annotations. Check the repository-specific exception stack for diagnostic details.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-03037: Error saving annotations to a document version that is not the current version.**

**Cause:** An attempt was made to save annotations to a document version that is not the current version.

**Action:** Annotations cannot be saved to previous versions of a document.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**TCM-04001: A valid Input name or ID must be specified for the operation to complete.**

---

**Cause:** The requested Name and ID of the input to be deleted is invalid.

**Action:** Provide a valid Name or ID for the Input to delete

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04002: No Input definitions found for the input name {0}, ID {1}.**

**Cause:** The specified Input could not be found in the system.

**Action:** Recheck the Input name or ID.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04003: Multiple Input definitions found for input name {0}, ID {1}.**

**Cause:** The name or ID provided has multiple Input Definitions associated with it.

**Action:** Examine the system for data integrity.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04004: Input name is empty**

**Cause:** The name of the Input is invalid

**Action:** Make sure the Input name is not missing, blank or only strings

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04005: Invalid Input properties**

**Cause:** The properties section of the Input Definition was invalid.

**Action:** Make sure that the Input properties section is not missing.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04006: Input source must be set**

**Cause:** The Input Definition is missing the input source

**Action:** Provide a valid input source

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04008: The Input's Source Properties section is invalid**

**Cause:** The Input Source Properties section of the Input definition is invalid.

**Action:** Check to make sure the properties are set and have valid values.

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04009: The specified data source is invalid.**

**Cause:** The Data Source in the Input Source Properties was invalid.

**Action:** Make sure that the data source is specified and has a valid value.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04010: The Input Source in the definition is invalid**

**Cause:** The Input Source is invalid.

**Action:** Check the Input Source and make sure it's valid.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04012: The Input does not define any mappings, or one or more mappings are invalid**

**Cause:** The Input Mappings section of the Input definition is invalid.

**Action:** Check to make sure mappings have been set and map between valid fields.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04013: The provided StateUpdates are invalid.**

**Cause:** No valid values were provided for updating the input's state.

**Action:** Ensure that the Input.StateFlags provided for all updates are valid.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**TCM-04014: The specified input's state cannot be updated**

**Cause:** Updating the current state for the specified input failed.

**Action:** Ensure that the specified input exists, and that the new state settings are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04015: The specified input definition cannot be updated**

**Cause:** Updating the provided sections of the input definition failed.

---

**Action:** Ensure values have been properly provided for all of the definition sections you are attempting to update

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04016: The provided Input object is null**

**Cause:** The Input object provided is null.

**Action:** Provide a valid Input, with appropriate sections completed.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04017: Cannot find the configuration file for the local Input Server settings.**

**Cause:** The configuration file specified could not be found.

**Action:** Ensure that the specified file exists, and that the user has the correct permissions

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04018: An error was encountered loading the configuration file**

**Cause:** The configuration file couldn't be opened.

**Action:** Ensure that the specified file exists, and that the user has the correct permissions

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04019: Failed to get the Input Source list**

**Cause:** Could not get a listing of available Input Sources

**Action:** Check the jar configuration files and make sure they are defined correctly

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04020: The Input Path for CSV filings has not been configured properly.**

**Cause:** The Input Path is missing from the CSV configuration file.

**Action:** Check the CSV configuration file to make sure it exists and is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04021: Input Source {0} cannot be found**

**Cause:** The requested Input Source was not found



---

**Action:** Check the /META-INF/input-agent-config.properties file of Input Source jar and make sure it's correct.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04022: Error loading Input Source Plugin**

**Cause:** An error occurred while trying to load the input source

**Action:** Check the class path to make sure the input source can be loaded.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04023: The stage path cannot be initialized for processing**

**Cause:** The stage directory could not be initialized.

**Action:** Check the permissions to the Input Directory.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04024: The file {0} cannot be moved to the directory {1}**

**Cause:** The input file could not be properly staged for processing.

**Action:** Check the input file and stage path for proper permissions.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**TCM-04025: the configuration folder path cannot be found**

**Cause:** The configuration file wasn't found

**Action:** Make sure all the configuration files are in place and are correct.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**TCM-04026: The specified Input Source "{0}" cannot be found**

**Cause:** The given Input Source name does not match any sources that the Input Server has loaded.

**Action:** Check the Input Source name.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04027: One or more of the Input Fields are mapped to multiple Application or system fields**

**Cause:** One of the input mappings is assigned to multiple locations.

---

**Action:** Remove all duplicate mappings from the definition

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04028: The requested input field isn't mapped to an application field**

**Cause:** The requested mapping wasn't found in the index

**Action:** Pass in the correct input field name

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04029: The parser has not been initialized, call StartFiling**

**Cause:** Start Filing wasn't called on the parser

**Action:** Call start filing

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04030: The input file cannot be properly closed**

**Cause:** A file error closing the input file

**Action:** Check file permissions and input file

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**TCM-04032: The specified data range is invalid**

**Cause:** Start and end positions for examining the data source are invalid

**Action:** Request a valid range

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**TCM-04033: Date value does not conform to the short, medium or long format type for the current locale, date cannot be parsed.**

**Cause:** Date format does not parse to a valid date

**Action:** Pass in a date value that conforms to the locales short, medium or long format

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04034: Cannot get the local machine name**

**Cause:** The host could not be determined.

---

**Action:** Check the error code.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04035: The application({0},{1}) specified in the mapping cannot be found.**

**Verify that the application exists and you have permissions to it.**

**Cause:** The application that the mapping is pointing to could not be found

**Action:** Check to make sure that you have access to that Application or that the Application is still valid.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04036: The mapping for input section {0} is invalid**

**Cause:** The application field specified in the Input mapping is invalid.

**Action:** Check to make sure that the specified application field ID is set and exists in the target application

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04038: Application "{0}" cannot be loaded. Verify that the application exists and you have permissions to it.**

**Cause:** The Application specified could not be loaded

**Action:** Check to make sure that the Application exists and you have access to it.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04039: The Sample Path for CSV filings has not been configured correctly.**

**Cause:** The sample path is not configured correctly

**Action:** Make sure the sample path configuration value is set to a valid location

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04040: The sample path {0} cannot be initialized for processing**

**Cause:** The sample path could not be created

**Action:** Make sure the sample path is valid, accessible by the server and has the correct permissions

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

- 
- TCM-04041: The get contents request for data source {0} cannot be processed because it is not a sample source.**  
**Cause:** User attempted to get sample data for a data source that wasn't a sample source.  
**Action:** Use only sample sources when requesting source contents.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses
- TCM-04045: The Input {0} has {1} unfinished batches open against it and cannot be deleted**  
**Cause:** There is an open batch against the Input  
**Action:** Wait for the filing to finish before deleting the Input  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses
- TCM-04046: Input {0} has active or pending jobs and cannot be deleted**  
**Cause:** There are queued jobs for the Input  
**Action:** Wait for all the work to finish before deleting the Input  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses
- TCM-04047: The Input Agent service cannot be accessed to process commands.**  
**Cause:** The Input Agent could not be found to communicate with.  
**Action:** Validate that the Imaging.ear is started and running properly.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses
- TCM-04048: Content cannot be read from the data source {0}**  
**Cause:** The data source content could not be read  
**Action:** Examine the inner exception for more information  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses
- TCM-04049: The StateUpdate value passed to the ModifyState call is invalid**  
**Cause:** The state update object passed to the API request is invalid  
**Action:** Check the StateUpdate object to make sure it's properly formed  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses

---

**TCM-04050: No Application is specified in the Input Mapping section**

**Cause:** The input definition does not have the destination application id set

**Action:** Set the Application Id in the Input mapping section

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04051: The input file locale has already been set and cannot be changed**

**Cause:** A locale has already been specified for the input file and cannot be changed

**Action:** Remove the extra locale command from the input file

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04052: The locale identifier {0} is not a valid locale identifier**

**Cause:** The locale parameter specified in the locale command is invalid

**Action:** Specify a valid locale

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04053: The locale command can only be used at the beginning of the input file**

**Cause:** The locale command was used after the start of the file

**Action:** Only use the locale command at the top of the input file

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04054: The start position {0} or range {1} specified are invalid. Make sure that the start position and range values are positive and that the range is greater than the start.**

**Cause:** The start position or range values are invalid.

**Action:** Examine the calling code and ensure that the start position and range are greater than 0 and that the range is greater than the start position

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-04055: The value {0} provided for the Input Server state update is the wrong type or is out of range.**

**Cause:** The value provided to the StateFlag request was invalid.

**Action:** Check to make sure the correct type has been passed for the StateFlag and that the value is in the correct range.

**Level:** 1

---

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-05003: The UOA Repository search failed**

**Cause:** No Search was found matching the selected search id

**Action:** Re-list the available searches

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-05004: The Search Definition supplied was null**

**Cause:** A null value was provided for the search.

**Action:** Provide a non-null search.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-05005: The Search Name supplied was null or empty**

**Cause:** Search name was null or empty

**Action:** Provide a valid search name.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-05006: The search supplied has a results formatting structure that is null.**

**Cause:** The search formatting structure was null or empty.

**Action:** Provide a valid search formatting structure.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-05007: The requested search, {0}, was not found.**

**Cause:** The user does not have access to the search.

**Action:** Check the user's access to the requested search.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-05009: A required search parameter, {0}, was missing.**

**Cause:** A required parameter was missing for this search

**Action:** Resubmit the search with the required parameter(s).

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**TCM-05012: Invalid operator used in search parameter**

**Cause:** An invalid operator was used in the search parameter

**Action:** Use an operator defined in the operator picklist.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-05013: A Search Argument was provided that was not defined in the search**

**Cause:** A search argument was provided that was not defined in the search

**Action:** Provide only those arguments defined in the search.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-05014: The search argument contains a value for a read-only parameter**

**Cause:** A search argument was provided containing a value for a read-only parameter

**Action:** Remove the read only parameter from the search arguments.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-05015: There are multiple search arguments for a single parameter.**

**Cause:** Multiple search arguments were provided for a single parameter.

**Action:** Verify that the number of the search arguments matches the number of parameters.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-05016: The type for the search argument does not match the search parameter type.**

**Cause:** A search argument with an incorrect type was provided for a search parameter.

**Action:** Use an argument with a type that matches the search parameter type.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-05017: The entered value, {0}, is < 1. The default maximum rows returned value must be >= 1.**

**Cause:** A value less than 1 was entered for the default value for the maximum number of rows to be returned from a search.

**Action:** Use a value that is greater than or equal to 1.

**Level:** 1

---

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-06001: Unable to retrieve Role: {0}**

**Cause:** The role specified was not found.

**Action:** Add the role to the security provider or use a defined role.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-06002: Access is denied.**

**Cause:** User does not have access to the requested information.

**Action:** Update the user's permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-06004: Unable to locate the security member specified.**

**Cause:** The security member does not exist.

**Action:** Add the security member to the security provider.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-06009: Unable to locate the system group: {0}**

**Cause:** The specific system group was not found.

**Action:** Add the system group using the security provider.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-06010: Agent users are only allowed to log in through the agent services.**

**Cause:** An agent user was used to attempt a log in.

**Action:** Log in using a different user.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-06011: Users assigned the 'admin' group either directly or indirectly are not allowed to log into IPM.**

**Cause:** Users assigned the 'admin' group are not allowed to log in because the repository attaches special meaning to this group.

**Action:** Log in using a different user or remove the 'admin' group association with this user.

**Level:** 1



---

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-06012: The User {0} does not exist in the policy store.**

**Cause:** The security provider was unable to locate the user specified.

**Action:** Enter the user into the security provider.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-06013: Unable to locate the default policy store.**

**Cause:** Unable to load the policy store.

**Action:** The default policy store has not been configured correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-06014: The user's principal does not contain a subject.**

**Cause:** The principal object was not found in the user token.

**Action:** Make sure the principal exists within the user token.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-06015: The Group {0} does not exist in the policy store.**

**Cause:** The authentication provider was unable to locate the group specified.

**Action:** Enter the group into the authentication provider.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-06016: Access to modify the security of this definition is denied.**

**Cause:** The user was unable to modify the security of this definition.

**Action:** Update the user permissions with the modify permission.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-06017: Access to modify the document security of this definition is denied.**

**Cause:** The user was unable to modify the document security of this definition.

**Action:** Update the user permissions to include the modify document security permission.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**TCM-07001: Requested output format does not support multiple pages**

**Cause:** An output format was requested that does not support multiple pages.

**Action:** Choose a different output format, or restrict the output request to a single page.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-07002: Invalid Document reference in render request**

**Cause:** The supplied documentObject parameter is null

**Action:** Provide a valid Document object reference when calling `RenderManager.render()`.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-07003: Invalid input stream in render request**

**Cause:** The supplied sourceStream parameter is null

**Action:** Provide a valid InputStream object reference when calling `RenderManager.render()`.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-07004: No render options in render request**

**Cause:** The supplied options parameter is null

**Action:** Provide a valid RenderOptions object reference when calling `RenderManager.render()`.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-07008: This document contains annotations that prevent the user from accessing this document in its raw format**

**Cause:** This document contains annotations that prevent the user from accessing this document in its raw format.

**Action:** Export to TIFF with the annotations burned in or contact your administrator for access to the native format.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-07009: The mime-type of "{0}" is not supported.**

**Cause:** An unsupported mime-type was requested.

---

**Action:** Correct the document content (mime) type.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-07011: An I/O error occurred during image translation.**

**Cause:** An I/O error occurred during image translation.

**Action:** Check permissions and free space in the server temp directory.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-07012: An error occurred when loading an image for translation.**

**Cause:** An error occurred when loading an image for translation.

**Action:** Image handling components failed to load the image. Check nested exception details for diagnostic information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-07013: There was an error reading TIFF headers. The file may be corrupt.**

**Cause:** There was an error reading TIFF headers. The file may be corrupt.

**Action:** Check permissions and free space in the server temp directory.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-07014: An error occurred when processing image manipulation commands during save.**

**Cause:** An error occurred when processing image manipulation commands during save.

**Action:** Image handling components failed to load the image. Check nested exception details for diagnostic information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-07016: An I/O error occurred creating the output for this request.**

**Cause:** An I/O error occurred creating the output for this request.

**Action:** Check for nested exceptions, permissions and free space in the server temp directory.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**TCM-07017: No document specified when burning annotations into image**

**Cause:** No document specified when burning annotations into image.

**Action:** Specify a valid document path to the document source.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-07019: The requested scale is not within the allowed value range; {0}-{1}**

**Cause:** The requested scale is not within the allowed value range.

**Action:** Provide a scale factor value within the supported range.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-07020: The requested fit rectangle is empty**

**Cause:** The requested fit rectangle cannot be empty.

**Action:** Provide a non-null, non-empty rectangle.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-07021: Unable to get annotation permissions from document**

**Cause:** Annotation permissions could not be determined.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-07022: The supplied document object is null**

**Cause:** The cache was given a null document object.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-07023: A cache exception occurred. {0}**

**Cause:** A RenderPageCache exception occurred: {0}

**Action:** Check the cache exception code and nested exception details for diagnostic information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-07024: A RenderPageCache object was not found**

---

**Cause:** An error occurred retrieving an object from the cache.

**Action:** Check the directory and nested exception details for diagnostic information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-07025: Page number must be a positive value.**

**Cause:** Page number must be a positive value.

**Action:** Provide page number values greater than zero.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-07026: Bounding rectangle specified is empty.**

**Cause:** Bounding rectangle specified is empty.

**Action:** Provide a non-empty rectangle definition.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-07027: The supplied outputType parameter is null.**

**Cause:** The supplied outputType parameter is null.

**Action:** Provide a value for the outputType parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-07028: An invalid argument was provided to method {0}({1}).**

**Cause:** An invalid argument was provided to a method call.

**Action:** Provide non-null values. Page specifications must be > 0.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-07029: Cannot burn the annotations into the destination file {0}.**

**Cause:** An error occurred while burning annotations into the destination tiff.

**Action:** Check the embedded exception for the specific cause of the error.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-07030: An invalid path was specified. Provide a non-null, non-empty string or an existing directory path.**

---

**Cause:** An invalid path was set for the render CacheLocation.

**Action:** Provide an empty value or an existing directory path.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-07031: An invalid value was specified. Check spelling and character case.**

**Cause:** An invalid value was specified.

**Action:** Check spelling and character case.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-07033: An invalid value was specified. Enter a value from 0 to 100.**

**Cause:** An invalid value was specified.

**Action:** Enter a value from 0 to 100.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-07036: An error occurred during document translation.**

**Cause:** An error occurred during document translation.

**Action:** Check nested exception details for diagnostic information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-07037: An error occurred retrieving a rendition to create a copy with.**

**Cause:** An error occurred retrieving a rendition to create a copy with.

**Action:** The rendering system was unable to generate a rendition of the document. Check the nested exception details for diagnostic information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-07038: The requested page number is beyond the document page range.**

**Cause:** The requested page number is beyond the document page range.

**Action:** Specify a valid page number that is within the range of document pages.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-07039: This document content is sealed. IRM content cannot be rendered.**

**Cause:** This document content is sealed. IRM content cannot be rendered.

---

**Action:** Download the native document and use Oracle IRM Desktop to access this file content.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-07040: RenderAgent is not initialized. Requests cannot be processed.**

**Cause:** RenderAgent is not initialized. Requests cannot be processed.

**Action:** RenderAgentBean initialization failed. Check the nested exception details for diagnostic information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-08001: System folder "{0}" is not found**

**Cause:** A UOA system folder was not found.

**Action:** Ensure proper UOA system installation.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**TCM-08005: User does not have create permissions.**

**Cause:** An attempt was made to create documents in an application where the user does not have create permission.

**Action:** Ensure user is granted create permission or refrains from creating documents.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**TCM-08006: User does not have delete permissions.**

**Cause:** An attempt was made to delete documents in an application where the user does not have delete permission.

**Action:** Ensure user is granted delete permission or refrains from deleting documents.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**TCM-08008: User does not have permission to access the "{0}" system folder.**

**Cause:** An attempt was made to access a system folder, but the user does not have the proper permission.

**Action:** Ensure user is granted the proper permission or refrains from accessing the folder

**Level:** 1

---

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-08009: Workspace "{0}" is not found.**

**Cause:** A workspace in UOA was not found.

**Action:** Ensure proper UOA system installation.

**Level:** 1

**Type:** ERROR

**Impact:** Installation

**TCM-08010: Interrupted during login retry. Stopping further login attempts.**

**Cause:** An agent thread was interrupted while attempting to log in.

**Action:** Check to see if the thread was shut down.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-08011: Unable to log in to the IPM system**

**Cause:** An error was encountered while logging in to the IPM system.

**Action:** Check the IPM logs and any inner exception for details on why the login failed.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-09010: An error occurred trying to list storage policy volumes.**

**Cause:** An error occurred trying to obtain a list of storage volumes from a repository.

**Action:** Ensure that the repository is running and functioning correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-09011: An error occurred trying to determine the default storage policy volume.**

**Cause:** An error occurred trying to determine the default volume for a repository.

**Action:** Ensure that the repository is running and functioning correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-09012: An error occurred trying to list retention policies.**

**Cause:** An error occurred trying to list retention policies for a repository.

**Action:** Ensure that the repository is running and functioning correctly.

**Level:** 1



---

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-09013: An error occurred trying to validate a volume.**

**Cause:** An error occurred trying to validate a volume for a repository.

**Action:** Ensure that the repository is running and functioning correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-09014: An error occurred trying to validate a storage group.**

**Cause:** An error occurred trying to validate a storage group for a repository.

**Action:** Ensure that the repository is running and functioning correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-09015: An error occurred trying to validate a retention policy.**

**Cause:** An error occurred trying to validate a retention policy for a repository.

**Action:** Ensure that the repository is running and functioning correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-09016: An error occurred trying to find a retention policy.**

**Cause:** An error occurred trying to find a retention policy in a repository.

**Action:** Ensure that the repository is running and functioning correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-09017: An error occurred trying to discover lifecycle policies.**

**Cause:** An error occurred trying to find lifecycle policies in a UOA repository.

**Action:** Ensure that UOA is running and functioning correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-09018: An error occurred trying to create a storage policy.**

**Cause:** An error occurred trying to create a storage policy in a UOA repository.

**Action:** Ensure that UOA is running and functioning correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**TCM-09019: An error occurred trying to delete a storage policy.**

**Cause:** An error occurred trying to delete a storage policy in a UOA repository.

**Action:** Ensure that UOA is running and functioning correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-09020: An error occurred trying to load action specifications.**

**Cause:** An error occurred trying to load action specifications in a UOA repository.

**Action:** Ensure that UOA is running and functioning correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-09021: An error occurred trying to load date rule specifications.**

**Cause:** An error occurred trying to load date rule specifications in a UOA repository.

**Action:** Ensure that UOA is running and functioning correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-09030: Error connecting to workflow system.**

**Cause:** An error occurred trying to connect to a workflow server.

**Action:** Ensure that the workflow server is running and functioning correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-09032: Error determining workflow composite services. The composite DN is {0}.**

**Cause:** An error occurred trying to determine services for a composite.

**Action:** Ensure that the workflow server is running and functioning correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-09033: Error getting workflow system components.**

**Cause:** An error occurred trying to determine components for a workflow server.

**Action:** Ensure that the workflow server is running and functioning correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**TCM-09034: Error reading workflow service WSDL document {0}**

**Cause:** An error occurred trying to read the workflow service WSDL document.

**Action:** Ensure that the workflow server is running and functioning correctly. If WSDL protocol is HTTPS, ensure SSL configurations for both IPM and the workflow server are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-09035: Error accessing credential key "{0}"**

**Cause:** An error occurred access a credential key in the credential store.

**Action:** Ensure that the correct key was provided and the credentials are properly configured in the credential store.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-09036: Unsupported workflow service. Service definition exceeds hierarchical depth of {0}.**

**Cause:** Workflow service Definition exceeded the maximum hierarchical depth given in the error message.

**Action:** Select a different workflow service operation.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-09037: Unsupported workflow service. Service definition contains choice elements.**

**Cause:** Workflow service definition contains unsupported choice elements.

**Action:** Select a different workflow service operation.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-10001: An error was encountered while searching the repository for closed batches**

**Cause:** An error occurred while searching the CDB repository for closed batches

**Action:** Check the associated exception and CDB log files for errors

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-10002: Batch ID {0} for Application {1} has been closed and cannot be indexed into, operation aborted**

**Cause:** The user requested to index a document into a batch that has been closed

---

**Action:** Check the calling code to determine why the batch was committed too early

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-10003: Batch ID {0} for Application {1} has already been committed**

**Cause:** The user attempted to commit a batch that was already closed

**Action:** Check the calling code to determine why the batch was committed twice

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**TCM-10004: No Batches found for the Batch Name {0}, ID {1}.**

**Cause:** The Batch could not be found in the CDB system

**Action:** Check the NameId passed to the API and make sure it exists

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-10005: The target application specified in the Batch object is invalid**

**Cause:** The target application specified in the Batch object is invalid

**Action:** Check the Batch object and ensure that the target application is valid

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-10006: No Batches found for Batch ID {0}**

**Cause:** The Batch could not be found in the CDB system

**Action:** Check the NameId passed to the API and make sure it exists

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-10007: The Batch provided is null**

**Cause:** The specified Batch is null

**Action:** Pass a valid Batch object to the API call

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-10008: The requested Batch ID {0} has documents indexed into it and cannot be removed.**

**Cause:** The requested batch could not be deleted because it had documents indexed to it.

---

**Action:** Double check that the correct batch was requested and verify that it is empty.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-11001: Turning on or off the auditing configuration failed**

**Cause:** An FDK Exception was generated by the UOA system when attempting to set the auditing configuration.

**Action:** Correct the underlying UOA repository configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-11002: The search of the audit history failed.**

**Cause:** The search of the repository for auditing data resulted in a repository exception.

**Action:** Correct the error identified in the underlying repository exception.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-14000: The provided URL ticket is invalid.**

**Cause:** The provided URL ticket was determined to be invalid.

**Action:** Pass a valid ticket to the API call.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-14001: The URL ticket is set to expire but does not have an expiration time set.**

**Cause:** The URL ticket was set to expire, but did not have an expiration time set.

**Action:** Turn off the expiration or set the expiration time for the ticket.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-14002: No parameters exist in the provided URL ticket.**

**Cause:** No parameters were specified in the URL ticket.

**Action:** Add at least 1 parameter to the URL ticket.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-14003: The parameter for value {0} in the URL ticket is missing a name.**

**Cause:** The ticket parameter did not have a name defined.

---

**Action:** Assign a name to the ticket parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-14004: The parameter {0} does not have a value assigned to it.**

**Cause:** Ticket parameter did not have a value defined.

**Action:** Assign a value to the parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-14005: The provided ticket identifier is invalid.**

**Cause:** The ticket identifier was invalid.

**Action:** Specify a valid ticket identifier.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-14006: A ticket with the identifier {0} cannot be found.**

**Cause:** The provided ticket identifier could not be found in the system.

**Action:** Verify that the ticket identifier is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-14007: The ticket agent is not processing requests.**

**Cause:** The ticket agent service could not be located.

**Action:** Verify that the IPM ear deployment is valid and is running.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-14008: A create ticket request that is set to expire has an invalid expiration date.**

**Cause:** An attempt was made to create a ticket with an expiration date in the past.

**Action:** Fix the create request so that the ticket has a date in the future.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-14009: The ticket parameter name {0} is longer than the maximum allowed name length of 200.**

**Cause:** An attempt was made to create a ticket parameter with a name that is too long.

---

**Action:** Shorten the parameter name to be less than 200 characters.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-14010: The ticket parameter value {0} is longer than the maximum allowed value length of 200.**

**Cause:** An attempt was made to create a ticket parameter with a value that is too long.

**Action:** Shorten the parameter value to be less than 200 characters.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-15000: The provided Connection object is null**

**Cause:** No Connection was provided

**Action:** Call the method with a valid Connection object

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-15001: Failed to remove the connection as it has the following application dependencies: {0}.**

**Cause:** Connection is still in use

**Action:** Remove the dependent applications prior to removing the connection

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-16001: The import data supplied is null.**

**Cause:** Data supplied for the import operation was null.

**Action:** Verify the import data is valid and not null.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-70007: The specified Input Source {0} cannot be found.**

**Cause:** An Input Source name was provided that does not match any sources that the Input Server has loaded.

**Action:** Check the Input Source name.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-70008: The server interval setting is missing from the configuration file.**

---

**Cause:** The server interval configuration is missing from the configuration file.

**Action:** Check the configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-70009: The Input Definition is invalid.**

**Cause:** The Input parameter was null.

**Action:** Supply a valid Input to the call.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-70010: No data was provided for the mapped document file section.**

**Cause:** A document file was not provided.

**Action:** Add a patch to the desired document image file to the input file.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-70013: Cannot find the field {0}, id {1} in the Application, check the Application and Input for proper mappings.**

**Cause:** The application field for a section mapping couldn't be found

**Action:** Check to make sure the application field hasn't been deleted and examine the Input field mappings

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-70015: The Batch {0} given to Input Agent is marked closed and cannot be used to add objects to.**

**Cause:** The Batch that Input Agent was assigned to file to is marked as closed

**Action:** Restart the entire input file as a new filing.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-70016: A check interval setting of {0} is invalid. Specify a value between 1 and 60.**

**Cause:** An invalid check interval was provided.

**Action:** Set the interval between 1 and 60.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses



---

**TCM-70017: An error occurred while manipulating the Input Filing Queue**

**Cause:** An error occurred while trying to browse the input queue

**Action:** Check the embedded error for more details

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-70018: The value {0} is too large or small to fit in a numeric field.**

**Cause:** The value that was parsed was outside the valid range for a numeric type.

**Action:** Fix the value so that it is inside the numeric data type range.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-70020: The retry count setting {0} is invalid, enter a value between 1 and 100**

**Cause:** An invalid retry count was set into the MBean

**Action:** Try using a retry value between 1 and 100

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-70021: The input value {0} could not be converted to a date. It does not conform to a short, medium or long date format for the current locale.**

**Cause:** An invalid date string was parsed from the input file

**Action:** Correct the value so that it is in the correct date format

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-70022: The input value {0} could not be converted to a number.**

**Cause:** An invalid decimal string was parsed from the input file

**Action:** Correct the value so that it is a valid number

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-70023: The input value {0} could not be converted to a decimal.**

**Cause:** An invalid date string was parsed from the input file

**Action:** Correct the value so that it is a valid decimal

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**TCM-70024: An existing set of state information was found for the job {0} for Input {1} and cannot be duplicated. Input Agent is ignoring this request.**

**Cause:** Existing filing State information was found for the data source and Input and cannot be added twice.

**Action:** Clear out all filings for the Input and allow the server to remove the extra state information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-70025: There is no valid document id to run the command on.**

**Cause:** The command could not be executed because the last document failed to index and no document id was specified.

**Action:** Either fix the indexing error for the last document in the file or specify a document id to apply the command to.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-70026: The supporting content key value was not found in the command.**

**Cause:** No key value was specified for the supporting content command.

**Action:** Add a supporting content key to the supporting content command.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-70027: The supporting content file path was not found in the command.**

**Cause:** The supporting content file name was not found.

**Action:** Add the supporting content's full path to the command.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-70028: The annotation file path was not found in the command.**

**Cause:** The annotation file name was not found.

**Action:** Add the annotation file's full path to the command.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-71002: The input source cannot set up the stage path correctly.**

**Cause:** The plugin encountered an error trying to set up the stage path.

**Action:** Check to make sure the plugin can get to the machine name.

**Level:** 1

---

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-71003: Encountered error {0} while writing to the error file {1}**

**Cause:** An error occurred while writing to the error file.

**Action:** Check the disk, path, and user permissions.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**TCM-71004: The failed path {0} cannot be initialized for processing.**

**Cause:** The failed directory could not be initialized.

**Action:** Check the permissions to the Input Directory and subdirectories.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-71005: The file mask {0} is invalid because it contains path information in addition to the file mask. Remove the additional path information.**

**Cause:** The file mask has at least a partial path in it, which is not supported.

**Action:** Remove the path portion of the file mask

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-71006: Cannot lock the input file {0} for processing.**

**Cause:** The input file could not be locked for processing.

**Action:** Make sure another program isn't accessing the file.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-71007: Cannot save file {0} since a file with the same name already exists there**

**Cause:** The user tried to upload a sample file with a name that already exists in the directory

**Action:** Specify a unique name before uploading to the sample directory

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-71008: Cannot save the given file to the sample directory. Error message provided is: {0}.**

**Cause:** The sample file could not be saved to the sample directory.

**Action:** Check the embedded exception for more details.

**Level:** 1

---

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-71009: The state file {0} cannot be created.**

**Cause:** The state file could not be created.

**Action:** Check the stage directory to make sure that it has enough space and the correct permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-71010: The state file {0} cannot be updated.**

**Cause:** The state file could not be updated.

**Action:** Check the stage directory to make sure that it has enough space and the correct permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-71011: No instances of the delimiter {0} were found in the current line of the input file**

**Cause:** The delimiter is missing for the input file line

**Action:** Check the delimiter in the Input Definition and make sure it's the correct one for the input file

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-71012: The file {0} is 0 bytes in length and cannot be processed.**

**Cause:** An attempt was made to process an input file that has 0 bytes.

**Action:** Process a file with data in it.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-71013: The file state information cannot be loaded for data source {0}**

**Cause:** Error loading the filing state for the input file

**Action:** Examine the database and any inner exceptions to determine the cause of the load error

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-71014: The filing state information cannot be found for data source {0}.**

**Cause:** The filing state could not be found for the input file

**Action:** Check the database to make sure that the filing state entry still exists

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-90001: Conversation ID not found: {0}**

**Cause:** Conversation identifier was not found in current session.

**Action:** Start over, if the problem persists, contact your system administrator.

**Level:** 1

**Type:** WARNING

**Impact:** Session

**TCM-90002: Task Context is unavailable.**

**Cause:** Workflow Task Context was not available.

**Action:** Start over. If the problem persists, contact your system administrator.

**Level:** 1

**Type:** WARNING

**Impact:** Session

**TCM-90003: Invalid Task ID: {0}**

**Cause:** Task ID provided was not available in request or in cache.

**Action:** Start over, if the problem persists, contact your system administrator.

**Level:** 1

**Type:** WARNING

**Impact:** Session

**TCM-90004: Task {0} already acquired by {1}**

**Cause:** The chosen workflow task has already been acquired by another user.

**Action:** Select another task and try again.

**Level:** 1

**Type:** WARNING

**Impact:** Session

**TCM-91000: An unexpected system error occurred. Contact your system administrator for support.**

**Cause:** An error has occurred.

**Action:** Contact Oracle Support Services for help determining the cause.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TCM-91001: SolutionParameter not found for: SolutionNamespace={0}, CommandNamespace={1}, ConfigurationNamespace={2}, ParameterKey={3}**

**Cause:** SolutionParameter was not found in "AXF\_SOLUTION\_PARAMETERS" table for the provided SolutionNamespace, CommandNamespace, ConfigurationNamespace, ParameterKey.

---

**Action:** Verify that the "AXF\_SOLUTION\_PARAMETERS" table contains this value.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91002: SystemParameter not found for: Namespace={0}, ParameterType={1}, ParameterKey={2}**

**Cause:** SystemParameter was not found in "AXF\_SYSTEM\_PARAMETERS" table for the provided SolutionNamespace, ParameterType, ParameterKey.

**Action:** Verify that the "AXF\_SYSTEM\_PARAMETERS" table contains this value.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91003: There was an error with the supplied XPath: {0}**

**Cause:** There was an error with the provided XPath

**Action:** Verify XPATH configuration in "AXF\_XPATH\_ATTRIBUTE" table

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91004: SolutionNamespace cannot be modified in an existing Conversation**

**Cause:** SolutionNamespace cannot be modified in an existing Conversation identifier.

**Action:** Start a new Conversation identifier for the new SolutionNamespace.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TCM-91005: SolutionNamespace not configured: {0}**

**Cause:** Provided SolutionNamespace was not configured in the "AXF\_SOLUTIONS" table.

**Action:** Ensure the SolutionNamespace entered has a matching entry in the "AXF\_SOLUTIONS" table.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91006: System cache failure**

**Cause:** The system cache failed.

**Action:** Contact Oracle Support Services with all log information, and restart your server.

**Level:** 1

**Type:** ERROR

---

**Impact:** Process

**TCM-91007: Unable to load command {0} using configured command class {1}**

**Cause:** Failed to create the instance of command provided in the "AXF\_COMMANDS" table

**Action:** Check configuration entry in "AXF\_COMMANDS" table and verify that the matching class has been loaded in the application server

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91008: Unable to find command "{0}" in the database.**

**Cause:** Unable to find the provided command in "AXF\_COMMANDS" table

**Action:** Check the command entry in "AXF\_COMMANDS" table

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91009: Unable to create named connection: {0}**

**Cause:** Failed to find the workflow connection information from the Imaging system

**Action:** Check configuration entry in "AXF\_SOLUTION\_ATTRIBUTE" table and the corresponding entry in "CONNECTION\_DETAILS" table.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91010: Unable to create named connection without a provider specified**

**Cause:** Failed to create named connection without a provider specified

**Action:** Check configuration entry in "AXF\_SOLUTION\_ATTRIBUTE" table and the corresponding entry in "CONNECTION\_DETAILS" table.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91014: Solution Parameter Key {0} has an invalid value of {1} for Solution Namespace = {2} -- Command Namespace = {3} -- Configuration Namespace = {4}**

**Cause:** The Solution Parameter Key has an invalid value in "AXF\_SOLUTION\_PARAMETERS" for the provided SolutionNamespace, ParameterType, ParameterKey.

**Action:** Verify the configuration parameter in "AXF\_SYSTEM\_PARAMETERS" table for the Redirect Command.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**TCM-91015: Error executing pl/sql procedure: {0} using connection: {1} for conversation: {2}**

**Cause:** Failed to execute pl/sql procedure in UpdateTaskFromProcedureCommand.

**Action:** Verify the configuration parameter in "AXF\_SYSTEM\_PARAMETERS" table for UpdateTaskFromProcedureCommand.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91016: Unable to retrieve database connection using JNDI name: {0}**

**Cause:** Failed to retrieve the JNDI name from Application Server.

**Action:** Verify the configuration parameter in "AXF\_SYSTEM\_PARAMETERS" table and ensure that JNDI is setup correctly in application server.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91017: Unable to retrieve the web root context from the application server.**

**Cause:** Failed to retrieve the web root context from the application server.

**Action:** Contact Oracle Support Services for help determining cause.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91018: SolutionNamespace attribute not found for: Namespace={0}, ParameterKey={1}**

**Cause:** SolutionNamespace attribute was not found in the "AXF\_SOLUTION\_ATTRIBUTES" table for the BPEL\_CONNECTION key.

**Action:** Check the "AXF\_SOLUTION\_ATTRIBUTES" Table for the missing configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91019: Command Parameter Key {0} has an invalid value of {1} for Solution Namespace = {2}, Command Namespace = {3}**

**Cause:** Command Parameter Key is missing, invalid or empty for Solution Namespace.

**Action:** Check the request parameters for command.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91020: Unable to decode the value in URL {0}**

**Cause:** This encoding is not supported.



---

**Action:** Check the encoding URL value.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91021: UCM unable to process the request - {0}**

**Cause:** UCM is unable to process the request.

**Action:** Check the UCM configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91201: Unable to create sorts for workflow**

**Cause:** Got the workflow exception while creating ordering

**Action:** Check permission for workflow user and workflow log

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91202: Unable to create predicates for workflow**

**Cause:** Got the workflow exception while creating predicate

**Action:** Check permission for workflow user and workflow log

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91203: Payload column is not supported for filtering**

**Cause:** Payload column is not supported for filtering

**Action:** Remove payload from column filtering

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91204: Attributes list is null or empty**

**Cause:** Attributes list was null or empty

**Action:** Supply at least one attribute

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91205: Unable to find the value specified by xpath : {0}**

**Cause:** Xpath found no matching element in the workload payload.

**Action:** Verify the xpath value in "AXF\_XPATH\_ATTRIBUTES" table and that the workflow payload has a corresponding entry.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91206: Workflow admin userid is missing**

**Cause:** Failed to get the workflow admin userid.

**Action:** Check the workflow admin userid in CSF of application server for the matching alias key in "CONNECTION\_DETAILS" table.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91207: Workflow admin password is missing**

**Cause:** Failed to get the workflow admin password.

**Action:** Check the workflow admin password in CSF of application server for the matching alias key in "CONNECTION\_DETAILS" table.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91208: Workflow provider url is missing**

**Cause:** Failed to get the workflow provider url.

**Action:** Check the host and port in "CONNECTION\_DETAILS" database table

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91209: Unable to authenticate from workflow**

**Cause:** Failed to authenticate with workflow server.

**Action:** Check the workflow password in CSF of application server for the matching alias key in "CONNECTION\_DETAILS" table.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91210: Unable to locate the security member specified**

**Cause:** Failed to locate the security policy store.

**Action:** Check the application server security configuration for authentication.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91211: Unable to locate the security store identity**

**Cause:** Failed to locate the security store identity.

**Action:** Check the application server security configuration for authentication.

---

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**TCM-91212: User {0} does not exist in the policy store.**

**Cause:** User did not exist in the policy store.

**Action:** Validate the user in the policy store.

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**TCM-91213: Unable to find the users in the policy store.**

**Cause:** Failed to find the users in the policy store.

**Action:** Verify that users exist in the policy store.

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**TCM-91214: Unable to find the roles in the policy store.**

**Cause:** Failed to find the roles in the policy store

**Action:** Check the application server security configuration for authentication

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**TCM-91215: Unable to find the policies in the policy store**

**Cause:** Unable to find the policies in the policy store

**Action:** Check the application server security configuration for authentication

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**TCM-91216: Unable to get the payload value for {0}**

**Cause:** Failed to find an element in workflow payload using xpath

**Action:** Verify the xpath value in "AXF\_XPATH\_ATTRIBUTES" table and the workflow payload has it

**Level: 1**

**Type: ERROR**

**Impact: Configuration**

**TCM-91217: Unable to load XML file '{0}' into XML Document**

**Cause:** Failed to load XML file into XML Document to create the views.

**Action:** Check the XML file permissions, format, and location on disk.

**Level: 1**

---

**Type:** ERROR

**Impact:** Configuration

**TCM-91218: View name is blank. It must be set to create a view. XML = {0}**

**Cause:** View name was blank in the provided XML file.

**Action:** Ensure that the view name is not empty in the XML file and node tag is /workflowSet/FFMSet/FFMDefinition/[<view name>]/FFMDetail/name.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91219: User name is blank. It must be set to create a view. XML = {0}**

**Cause:** User name was blank, it must be set to create a view.

**Action:** Ensure that the user name is not blank in the XML file and node tag is /workflowSet/viewSet/viewDefinition/[<view name>]/userList/user[<user>].

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91220: User name or realm is blank. It must be set to create a view. XML = {0}**

**Cause:** User name or realm was blank.

**Action:** Ensure that the user name or realm is blank in the XML file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91221: View Filter Column name is blank. It must be set to create a view. XML = {0}**

**Cause:** View filter Column name was blank.

**Action:** Ensure that the View Filter Column name is not blank in the XML file and node tag is /workflowSet/viewSet/viewDefinition/[<view name>]/userViewDetail/viewPredicate/clause[<position>]/column.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91222: Filter Operation is blank. It must be set to create a view. XML = {0}**

**Cause:** Filter operation was blank.

**Action:** Ensure that the Filter Operation is not blank in the XML file and node tag is /workflowSet/viewSet/viewDefinition/[<view name>]/userViewDetail/viewPredicate/clause[<position>]/operator.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91223: Filter Value is blank. XML = {0}**

---

**Cause:** Filter value was blank.

**Action:** Ensure that the Filter Value is not blank in the XML file and node tag is /workflowSet/viewSet/viewDefinition/[<view name>]/userViewDetail/viewPredicate/clause[<position>]/value.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91224: View Ordering column name is blank. XML = {0}**

**Cause:** View ordering column name was blank.

**Action:** Ensure that the View ordering column name is not blank in the XML file and node tag is /workflowSet/viewSet/viewDefinition/[<view name>]/userViewDetail/viewOrdering/clause[<position>]/column.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91225: View Ordering sort order is blank. XML = {0}**

**Cause:** View ordering sort order was blank.

**Action:** Ensure that the View ordering sort order is not blank in the XML file and node tag is /workflowSet/viewSet/viewDefinition/[<view name>]/userViewDetail/viewOrdering/clause[<position>]/sortOrder

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91226: View Creation failed. XML = {0}**

**Cause:** Failed to create the workflow View

**Action:** Check user permissions to create the view and also check the workflow server log

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91227: View Column name was blank. XML = {0}**

**Cause:** View column name was blank, it must be set to create a view

**Action:** View Column name is blank in the XML file and node tag is /workflowSet/viewSet/viewDefinition/[<view name>]/userViewDetail/viewColumns/column[<position>]

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91228: Unable to get the next task**

**Cause:** Failed to retrieve the next task from workflow.

---

**Action:** There may be no tasks for this user in workflow. Check the workflow server log.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91229: Unable to get list of tasks**

**Cause:** Failed to get list of tasks

**Action:** Workflow server may be not running or password is not correct in CSF. Check the workflow server log

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91230: Unable to get list of views**

**Cause:** Failed to get list of views

**Action:** Workflow server may be not running or password is not correct in CSF. Check the workflow server log

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91231: Unable to acquire task id {0} for user {1}**

**Cause:** Failed to acquire task id from workflow.

**Action:** The task may be already acquired by another user. Check the workflow server log.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91232: got the stale object from workflow**

**Cause:** The task from workflow is out of date.

**Action:** Log out from the application and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91233: Unable to release task id {0} for user {1}**

**Cause:** Failed to release task id from workflow.

**Action:** Verify that the task can be acquired by the current user. Check the workflow server log.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**TCM-91234: Unable to get the task detail for {0}**

**Cause:** Failed to get the task detail from workflow.

**Action:** Verify that the task is not already completed or purged in workflow.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91235: Task ID is null**

**Cause:** Task Id was invalid or null.

**Action:** Logout from application and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91236: Unable to update the task for {0}**

**Cause:** Failed to update the task in workflow.

**Action:** Verify that the task may be acquired to update the payload. Check the workflow server log.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91237: Unable to update outcome for {0}**

**Cause:** Failed to update the outcome in workflow.

**Action:** Verify that the task may be acquired to update and that the outcome is valid. Check the workflow server log.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91238: Unable to acquire next available task for {0}**

**Cause:** Failed to acquire next available task in workflow.

**Action:** There may be no task for this user in the workflow. Check the workflow server log.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91239: Unable to update transaction ID in workflow payload**

**Cause:** Failed to update transaction ID in workflow payload.

**Action:** Verify Transaction field exists in the workflow payload.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**TCM-91240: Unable to get comments**

**Cause:** Failed to get comments from workflow.

**Action:** Check the user's permission to get comments. Check the workflow server log.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91241: Comment is null.**

**Cause:** The value of Comment was null.

**Action:** Contact your system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91242: Unable to update comment in workflow**

**Cause:** Failed to update the comment in workflow.

**Action:** User may not have permission to update the comment. Check the workflow server log.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91243: Invalid URL for identity search URL**

**Cause:** Received URL was Invalid for identity search

**Action:** Check the URL for identity search in the database

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91244: Unable to open the connection for identity search URL**

**Cause:** Failed to open the connection for identity search URL.

**Action:** Verify that the Web service is available for identity search.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91245: Unable to parse the XML date received from identity search URL**

**Cause:** Failed to parse XML date received from identity search URL

**Action:** Check the XML format of input file as it may be invalid. There may be some invalid tag in the file

**Level:** 1

**Type:** ERROR

**Impact:** Configuration



---

**TCM-91246: Unable to acquire the task. Task is not assigned to the group or is assigned to a different user.**

**Cause:** Either the task was not assigned to the group or it was assigned to a different user.

**Action:** Select another task from the list.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-91247: Invalid Task attribute Key {0}**

**Cause:** Received Invalid Task attribute Key.

**Action:** Check your configuration or command for the attribute Key value

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TCM-92002: Access is denied.**

**Cause:** User does not have access to the requested information.

**Action:** Ensure user is defined with proper permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-92501: Duplicate annotation IDs exist**

**Cause:** Duplicate annotation IDs exist.

**Action:** Ensure that each annotation has a unique id. Annotations cannot be added more than once.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-92502: Null or empty annotation Id specified**

**Cause:** Null or empty annotation Id specified.

**Action:** Ensure that annotation id is not null or empty.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-92503: Null annotation object specified**

**Cause:** Invalid annotation object specified.

**Action:** Ensure that annotation object is not null and has a valid Id.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**TCM-92504: Annotation list is Null**

**Cause:** Annotation list to search is null.

**Action:** Ensure that annotation list object is not Null.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-92505: Annotation requires at least three points**

**Cause:** This annotation requires at least three points.

**Action:** Provide three points, or use a LineAnnot object.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-92506: There was an error deserializing an annotation file for this document.**

**Cause:** There was an error deserializing an annotation file for this document.

**Action:** Check the nested exception details for diagnostic information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-92507: There was an error serializing an annotation file for this document.**

**Cause:** There was an error serializing an annotation file for this document.

**Action:** Check the nested exception details for diagnostic information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-92508: An annotation list cannot be merged with itself**

**Cause:** An annotation list cannot be merged with itself.

**Action:** Specify a unique list of annotations.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-92509: A null value was supplied where an AnnotPoint object is expected.**

**Cause:** A null value was supplied where an AnnotPoint object is expected

**Action:** Provide a valid AnnotPoint object

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-92510: The requested scale is not within the allowed value range; {0}-{1}**

**Cause:** The requested scale is not within the allowed value range.

---

**Action:** Provide a proper scale value within the supported range.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-92511: Page number must be a positive value.**

**Cause:** Page number must be a positive value.

**Action:** Provide a page number that is greater than zero.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-92512: Bounding rectangle specified is empty.**

**Cause:** Bounding rectangle specified is empty.

**Action:** Supply a non-null, non-empty rectangle definition.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-92513: The Document Store provider {0} cannot be loaded**

**Cause:** The specified Document Store could not be loaded

**Action:** Make sure the provided class is correct and that it exists in the classpath

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-92514: Redact annotation cannot be assigned HIDDEN security.**

**Cause:** Redact annotation cannot be assigned HIDDEN security.

**Action:** Use a different security setting.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-92515: The page annotations include at least one annotation from another page.**

**Cause:** An attempt was made to replace page annotations with at least one annotation from a different page.

**Action:** Supply only annotations for the page specified.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-92516: Error deserializing annotations. InputStream is null.**

**Cause:** Error deserializing annotations. InputStream is null.

---

**Action:** Supply a serialized annotation stream.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-92517: Transformation process returned error code {0}.**

**Cause:** Transformation process returned an error code.

**Action:** See the transformation process return code for diagnostic information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-92518: There was an error launching the external transformation process: {0} {1}**

**Cause:** There was an error launching the external transformation process

**Action:** The transformation process failed unexpectedly. Check nested exception details for diagnostic information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-92521: The path specified for GdFontPath configuration is invalid.**

**Cause:** The path specified for GdFontPath configuration is invalid.

**Action:** Provide a valid path to a directory containing True Type Fonts.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-92522: There was an error reading TIFF headers. The file may be corrupt.**

**Cause:** There was an error reading TIFF headers. The file may be corrupt.

**Action:** Check permissions and free space in the server temp directory.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-92999: An error occurred in a subsystem. {0}**

**Cause:** An error occurred in a rendering subsystem.

**Action:** Review the logs for the error. You may need to contact Oracle Support Services to resolve the issue.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-99001: The repository definition identifier, {0}, is not valid.**

---

**Cause:** An attempt was made to add a repository configuration with a duplicate identifier.

**Action:** Use a unique identifier.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-99002: The repository definition name, {0}, is not valid.**

**Cause:** An attempt was made to add a repository configuration with a duplicate name.

**Action:** Use a unique name.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-99003: The repository definition identifier, {0}, is not unique.**

**Cause:** An attempt was made to add a repository configuration with a duplicate identifier.

**Action:** Use a unique identifier.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-99004: The repository definition name, {0}, is not unique.**

**Cause:** An attempt was made to add a repository configuration with a duplicate name.

**Action:** Use a unique name.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-99005: A system repository definition already exists.**

**Cause:** An attempt was made to add a system repository configuration when one already exists.

**Action:** Remove the existing system repository first.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-99006: The destination repository is read only and does not support this operation.**

**Cause:** An attempt was made to copy or move a document to a repository that is not writeable.

**Action:** Change the destination repository to one that is writeable.

**Level:** 1

---

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-99007: The destination repository is not the same as the source repository.**

**Cause:** An attempt was made to move a document to a different repository.

**Action:** Ensure that the source and destination repositories are the same.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-99008: The destination repository is not the same type as the source repository.**

**Cause:** An attempt was made to move a document to a different type of repository.

**Action:** Ensure that the source and destination repositories are the same type.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**TCM-99009: The repository must be initialized to support IPM prior to creating a connection.**

**Cause:** An attempt was made to create a connection to a system that is not yet configured.

**Action:** Ensure that target UCM system is configured prior to creating a connection.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

## TOP-00001 to TOP-72023

**TOP-00001: The attribute `[[0]]` is not declared as type `ValueHolderInterface`, but its mapping uses indirection.**

**Cause:** `attributeName` is not declared as type `ValueHolderInterface`, but the mapping uses indirection. The mapping is set to use indirection, but the related attribute is not defined as type `ValueHolderInterface`. It is raised on foreign reference mappings.

**Action:** If you want to use indirection on the mapping, change the attribute to type `ValueHolderInterface`. Otherwise, change the mapping associated with the attribute so that it does not use indirection.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00002: The attribute `[[0]]` is declared as type `ValueHolderInterface`, but its mapping does not use indirection.**

**Cause:** `attributeName` is declared as type `ValueHolderInterface`, but `TopLink` is unable to use indirection. The attribute is defined to be of type `ValueHolderInterface`, but the mapping is not set to use indirection. It is raised on foreign reference mappings.

**Action:** If you do not want to use indirection on the mapping, change the attribute so it is not of type `ValueHolderInterface`. Otherwise, change the mapping associated with the attribute to use indirection.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00006: Attribute name is missing.**

**Cause:** The attribute name is missing or not specified in the mapping definition.

**Action:** Specify the attribute name in the mapping by calling the method `setAttributeName(String attributeName)`.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00007: The attribute `[[0]]` should be of type `Vector` (or a type that implements `Map` or `Collection`, if using Java 2).**

---

**Cause:** When using Java 2, the specified attributeName is not defined as type vector, or a type that implements the Map or Collection interface. This occurs in one-to-many mapping, many-to-many mapping, and collection mapping when mapping is set not to use indirection, and the attribute type is not declared.

**Action:** Declare the attribute to be of type java.util.Vector.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00008: The descriptor [{0}] has been set to use inheritance, but a class indicator field has not been defined. {2}When using inheritance, a class indicator field or class extraction method must be set. {2}Parent Descriptor: [{1}]**

**Cause:** The class indicator field is defined, but the descriptor is set to use inheritance. When using inheritance, a class indicator field or class extraction method must be set. The class indicator field is used to create the right type of domain object.

**Action:** Set either a class indicator field or class extraction method.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00009: This mapping does not have a direct field name set.**

**Cause:** The direct field name from the target table is not set in the direct collection mapping.

**Action:** Specify the direct field name by calling the method setDirectFieldName(String fieldName).

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00010: This mapping does not have a field name set.**

**Cause:** The field name is not set in the mapping. It is raised from direct to field mapping, array mapping, and structure mapping.

**Action:** Specify the field name by calling the method setFieldName(String fieldName).

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00011: The foreign key information for this mapping is defined incorrectly.**

**Cause:** One-to-one mapping foreign key is defined incorrectly. Multiple foreign key fields were set for one-to-one mapping by calling the method setForeignKeyFieldName(String fieldName).

**Action:** Use the method addForeignKeyFieldName(String sourceForeignKeyName, String targetPrimaryKeyFieldName) to add multiple foreign key fields.

**Level:** 1



---

**Type:** ERROR

**Impact:** Configuration

**TOP-00012: Descriptors must use an identity map in order to use the "Check Cache" existence checking option.**

**Cause:** The descriptor has been set not to use identity map, but the existence checking is set to be performed on identity map: the descriptor must use an identity map to use the Check cache does exist option.

**Action:** Either use identity map, or set the existence checking to some other option.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00013: The instance variable [{0}] in the object [{1}] is inaccessible.**

**Cause:** TopLink is unable to access the attributeName instance variable in object objectName. The instance variable in the domain object is not accessible. This exception is raised when TopLink tries to access the instance variable using the java.lang.reflect Java package. The error is a purely Java exception, and TopLink wraps only the reflection exception.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00014: Problem in cloning the object [{0}]. The clone method [{1}] is not accessible.**

**Cause:** TopLink is unable to clone the object domainObject because the clone method methodName is not accessible. The method name specified using useCloneCopyPolicy(String cloneMethodName) or the clone() method to create the clone on the domain object, is not accessible by TopLink using Java reflection. The error is a purely Java exception, and TopLink wraps only the reflection exception.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00015: This class does not define a default constructor, which TopLink requires.**

**Cause:** The domain class does not define a public default constructor, which TopLink needs to create new instances of the domain class.

**Action:** Define a public default constructor or use a different instantiation policy.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**TOP-00016: The descriptor callback method [{0}], with parameter (DescriptorEvent), is inaccessible.**

**Cause:** The descriptor callback method eventName with DescriptorEvent as an argument is not accessible. This exception is raised when TopLink tries to access the event method using Java reflection. The error is a purely Java exception, and TopLink wraps only the reflection exception.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00017: Trying to access the method [{0}] on the object [{1}]. The underlying method is inaccessible.**

**Cause:** Attempt to invoke inaccessible methodName on the object objectName. The underlying getter method to access an attribute in the domain object is not accessible. This exception is raised when TopLink tries to access an attribute through a method using the java.lang.reflect Java package. The error is a purely Java exception, and TopLink wraps only the reflection exception.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00018: Illegal method access in a Transformation mapping using a ValueHolder.**

**Cause:** The method used by the transformation mapping using a value holder is invalid. This exception is raised when TopLink tries to access the method using Java reflection. The problem occurs when the method base valueholder is instantiated.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00019: Illegal access while invoking the attribute method on a Transformation mapping. The underlying method is inaccessible.**

**Cause:** On transformation mapping, the underlying attribute method that is used to retrieve values from the database row while reading the transformation mapped attribute is not accessible.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00020: The method [{0}] is inaccessible.**

**Cause:** On transformation mapping, the method methodName that is used to retrieve value from the object while writing the transformation mapped attribute

---

is not accessible. The error is a purely Java exception, and TopLink wraps only the reflection exception.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00021: Problem in extracting class from row [{0}]. The static method [{1}], with parameter (DatabaseRow), is not accessible.**

**Cause:** TopLink is unable to extract data row, because TopLink cannot access the row specified in the databaseRow argument of the method. The method to extract class from row on the domain object is not accessible. The error is a purely Java exception, and TopLink wraps only the reflection exception.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00022: Problem in creating new instance. The creation method [{0}] is not accessible.**

**Cause:** TopLink is unable to create a new instance, because the method methodName that creates instances on the domain class is not accessible. The error is a purely Java exception, and TopLink wraps only the reflection exception.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00023: The descriptor callback method [{0}], with parameter (Session), is inaccessible.**

**Cause:** The descriptor callback method eventName with Session as an argument is inaccessible. This exception is raised when TopLink tries to access the event method using Java reflection. The error is a purely Java exception, and TopLink wraps only the reflection exception.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00024: The instance variable [{0}] in the object [{1}] is inaccessible. {3}Argument: [{2}]**

**Cause:** The attributeName instance variable in the object objectName is not accessible through Java reflection. The error is raised by Java, and TopLink wraps only the reflection exception.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**TOP-00025: The method [{0}] with argument [{1}] is not accessible.**

**Cause:** TopLink is unable to invoke a method setMethodName on the object with parameter parameter. The attribute's set accessor method is not accessible through Java reflection. The error is raised by Java and TopLink wraps only the reflection exception.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00026: Trying to get value for instance variable [{0}] of type [{1}] from the object [{2}]. The specified object is not an instance of the class or interface declaring the underlying field.**

**Cause:** TopLink is unable to get a value for an instance variable attributeName of type typeName from the object. The specified object is not an instance of the class or interface declaring the underlying field. An object is accessed to get the value of an instance variable that does not exist.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00027: Trying to invoke the method [{0}] on the object [{1}]. The number of actual and formal parameters differs, or an unwrapping conversion has failed.**

**Cause:** TopLink is unable to invoke method methodName on the object objectName. The get accessor method declaration on the domain object differs from the one that is defined. The number of actual and formal parameters differ, or an unwrapping conversion has failed.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00028: Illegal argument while instantiating a method-based proxy in a Transformation mapping.**

**Cause:** The method that the method-based proxy uses in a transformation mapping is receiving invalid arguments when the valueholder is being instantiated. This exception is raised when TopLink tries to access the method using the java.lang.reflect Java package.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**TOP-00029: The number of actual and formal parameters differs, or an unwrapping conversion has failed.**

**Cause:** The number of actual and formal parameters differs, or an unwrapping conversion has failed. On transformation mapping, the method used to retrieve values from the database row while reading the transformation mapped attribute is getting an invalid argument.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00030: The number of actual and formal parameters differs for method [{0}], or an unwrapping conversion has failed.**

**Cause:** The number of actual and formal parameters differs for method methodName, or an unwrapping conversion has failed. On transformation mapping, the method used to retrieve value from the object while writing the transformation mapped attribute is getting an invalid argument. The error is a purely Java exception, and TopLink wraps only the reflection exception.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00031: The number of actual and formal parameters for the descriptor callback method [{0}] differs, or an unwrapping conversion has failed.**

**Cause:** The number of actual and formal parameters for the descriptor callback method eventName differs, or an unwrapping conversion has failed. The callback event method is invoked with an invalid argument. This exception is raised when TopLink tries to invoke the event method using Java reflection. The error is a purely Java exception, and TopLink wraps only the reflection exception.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00032: Trying to set value [{0}] for instance variable [{1}] of type [{2}] in the object. The specified object is not an instance of the class or interface declaring the underlying field, or an unwrapping conversion has failed.**

**Cause:** An invalid value is being assigned to the attribute instance variable. TopLink is unable to set a value for an instance variable attributeName of type typeName in the object. The specified object is not an instance of the class or interface that is declaring the underlying field, or an unwrapping conversion has failed. TopLink assigns value by using Java reflection. Java raises the error and TopLink wraps only the reflection exception.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**TOP-00033: Trying to invoke [{0}] on the object [{1}]. The number of actual and formal parameters differs, or an unwrapping conversion has failed.**

**Cause:** An illegal argument is being passed to the attribute's set accessor method. TopLink is unable to invoke method setMethodName on the object. The number of actual and formal parameters differs, or an unwrapping conversion has failed. Java raises the error and TopLink wraps only the reflection exception.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00034: This class does not define a public default constructor, or the constructor raised an exception.**

**Cause:** The class does not define a public default constructor, or the constructor raised an exception. This error occurs when you invoke the default constructor for the domain object to create a new instance of the object while building new domain objects if: The class represents an abstract class, an interface, an array class, a primitive type, or void. The instantiation fails for some other reason. Java raises the error and TopLink wraps only the reflection exception.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00035: Invalid event.**

**Cause:** Applications should never encounter this exception. This exception usually occurs at the time of developing TopLink, although in cases, where you write new mapping, it is possible to get this exception. In direct collection mapping and many-to-many mapping, the target table and relational table are populated at the end of the commit process, and if a data modification event is sent to any other mapping, then this exception is raised.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00036: Invalid event code [{0}].**

**Cause:** An application should never encounter this exception. This exception usually occurs at the time of developing TopLink, although in cases, where you write new mappings, it is possible to get this exception. In direct collection mapping and many-to-many mapping, the target table and relational table are populated at the end of the commit process, and if a data modification event is sent to these two mappings with wrong event code, then this exception is raised.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**TOP-00037: Invalid descriptor event code [{0}].**

**Cause:** An application should never encounter this exception. This exception usually occurs at the time of developing TopLink. The exception means that the descriptor event manager does not support the event code passed in the event.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00038: Identity map constructor failed because an invalid identity map was specified.**

**Cause:** The identity map constructor failed because an invalid identity map was specified. The identity map class given in the descriptor cannot be instantiated. The exception is a Java exception that is raised by a Java reflection when TopLink instantiates the identity map class. TopLink wraps only the Java exception.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00039: This descriptor does not specify a Java class.**

**Cause:** The descriptor does not define a Java class. The Java class is not specified in the descriptor.

**Action:** Specify the Java class.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00040: Descriptor is missing for [{0}]. It was probably not added to the Session.**

**Cause:** A descriptor for the referenced interface is not added to the session.

**Action:** Add that descriptor to the session.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00041: A non-read-only mapping must be defined for the sequence number field.**

**Cause:** A non-read-only mapping is not defined for the sequence number field. A mapping is required so that TopLink can put and extract values for the primary key.

**Action:** Define a mapping.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**TOP-00043: Missing class for indicator field value [{0}] of type [{1}].**

**Cause:** TopLink is missing the class for indicator field value classFieldValue of type type. There was no class entry found in the inheritance policy for the indicator field value that was read from the database. It is likely that the method addClassIndicator(Class class, Object typeValue) was not called for the field value. The class and typeValue are stored in a hash table, and later the class is extracted from the hash table by passing typeValue as a key. Because Integer(1) is not equivalent to Float(1), this exception occurs when the type of typeValue is incorrectly specified.

**Action:** Verify the descriptor.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00044: Missing class indicator field from database row [{0}].**

**Cause:** The class indicator field is missing from the database row that was read from the database. This is performed in the inheritance model where after reading rows from the database, child domain objects are to be constructed depending upon the type indicator values.

**Action:** Verify the printed row for correct spelling.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00045: Missing mapping for field [{0}].**

**Cause:** TopLink is missing a mapping for field; a mapping for the field is not specified.

**Action:** Define a mapping for the field.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00046: There should be one non-read-only mapping defined for the primary key field [{0}].**

**Cause:** A mapping for the primary key is not specified. There should be one non-read-only mapping defined for the primary key field.

**Action:** Define a mapping for the primary key.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00047: The multiple table primary key mapping must be specified when a custom multiple table join is used.**

**Cause:** The multiple table primary key mapping is not specified when a custom multiple table join is used. If multiple tables are specified in the descriptor and the join expression is customized, then the primary keys for all the tables must be specified. If the primary keys are not specified, then the exception occurs.



---

**Action:** Call the method `addMultipleTablePrimaryKeyFieldName(String fieldNameInPrimaryTable, String fieldNameInSecondaryTable)` on the descriptor to set the primary keys.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00048: Multiple writable mappings exist for the field [{0}]. Only one may be defined as writable, all others must be specified read-only.**

**Cause:** Multiple writable mappings for the field `fieldName` are defined in the descriptor. Exactly one must be defined as writable; the others must be specified as read-only. When multiple write mappings are defined for the field, TopLink is unable to choose the appropriate mapping for writing the value of the field in the database row. Therefore, the exception is raised during the validation process of descriptors. The most common cause of this problem is when the field has direct-to-field mapping, as well as one-to-one mapping. In this case, the one-to-one mapping must either be read-only or a target foreign key reference.

**Action:** Make one of those mappings read-only.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00049: An attribute transformation method name is not specified for this mapping.**

**Cause:** The attribute transformation method name in the transformation mapping is not specified. This method is invoked internally by TopLink to retrieve value to store in the domain object.

**Action:** Define a method and set the method name on the mapping by calling the method `setAttributeTransformation(String methodName)`.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00050: A field name is not set for this mapping.**

**Cause:** No field name is specified in direct-to-field mapping.

**Action:** Set the field by calling `setFieldName(String fieldName)`.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00051: No foreign keys have been specified for this mapping.**

**Cause:** Neither the selection criteria nor the foreign keys were specified on one-to-one mapping. If the selection criterion is not specified, then TopLink tries to build one from the foreign keys specified in the mapping.

**Action:** Specify the fields.

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**TOP-00052: No reference key has been specified for this mapping.**

**Cause:** No query key named queryKey is found in descriptor. No reference key from the target table is specified on direct collection mapping.

**Action:** Specify the fields by calling the method `setReferenceKeyFieldName(String fieldName)`.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00053: The relation table name is not set for this mapping.**

**Cause:** The relation table name is not set in this many-to-many mapping.

**Action:** Set the relation table name by calling the method `setRelationTableName(String tableName)`.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00054: There are no source relation keys specified for this mapping.**

**Cause:** There are no source relation keys specified in this many-to-many mapping.

**Action:** Add source relation keys to the mapping.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00055: The descriptor callback method [{0}] cannot be found. It must take a Session or a DescriptorEvent as its argument.**

**Cause:** TopLink cannot find the descriptor callback method on the domain class. It must take a Session or a DescriptorEvent as its argument. TopLink tries to invoke the method using Java reflection. It is a Java exception and TopLink is wrapping only the main exception.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00056: The method [{0}] with parameters (Record) or (Record, Session) is not found.**

**Cause:** TopLink cannot find the method `methodName(Record databaseRow)` or `methodName(Record databaseRow, Session session)`. TopLink wraps the Java reflection exception that is caused when the method is being created from the method name. This method is set by calling `setAttributeMethodName(String aMethodName)`.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**TOP-00057: Inaccessible constructor.**

**Cause:** The constructor is inaccessible to TopLink. TopLink wraps the Java reflection exception that is caused when it is creating a new instance of the domain.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00058: The method [{0}] with parameters () or (Session) not found.**

**Cause:** TopLink failed to find a method with signature methodName() or methodName(oracle.toplink.sessions.Session). TopLink wraps the Java reflection exception that was raised by its attempt to create a Method type (java.lang.reflect) from the method names in the transformation mapping.

**Action:** Ensure that the method methodName is defined on the domain class that owns the attribute mapped by the transformation mapping.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00059: The instance variable [{0}] is not defined in the domain class [{1}], or it is not accessible.**

**Cause:** The instance variable attributeName is not defined in the domain class, or it is not accessible. TopLink wraps the Java reflection exception that is caused when it is creating a Field type (java.lang.reflect.Field) from the attribute name.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00060: The method [{0}] or [{1}] is not defined in the object [{2}].**

**Cause:** The method setMethodName or getMethodName is not defined for the attribute in the domain class javaClassName, or it is not accessible. TopLink wraps the Java reflection exception that is caused when it is creating a Method type from the method name.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00061: The static class extraction method [{0}], with parameter (Record), does not exist, or is not accessible.**

**Cause:** The static class extraction method methodName(Record databaseRow) does not exist, or is not accessible. A Java reflection exception wrapped in a TopLink exception is raised when a class extraction method is being created from the method name in the inheritance policy.

---

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00062: The clone method [{0}], with no parameters, does not exist, or is not accessible.**

**Cause:** The clone method methodName() does not exist, or is not accessible. A Java reflection exception wrapped in a TopLink exception is raised when a method to create clones is being created from the method name in the copy policy.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00063: The instance creation method [{0}], with no parameters, does not exist, or is not accessible.**

**Cause:** The instance creation method methodName() does not exist, or is not accessible. A Java reflection exception wrapped in a TopLink exception is raised when a method to create the new instance is being created from the method name in the instantiation policy.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00064: No target foreign keys have been specified for this mapping.**

**Cause:** The foreign keys in the target table are not specified in one-to-many mappings. These fields are not required if a selection criterion is given in the mapping, but otherwise they must be specified.

**Action:** Set target foreign keys or selection criteria.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00065: No target relation keys have been specified for this mapping.**

**Cause:** There are no target relation keys specified in many-to-many mappings.

**Action:** Call method addTargetRelationKeyFieldName(String targetRelationKeyFieldName, String targetPrimaryKeyFieldName) to set the fields.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00066: Could not deserialize object from byte array.**

---

**Cause:** Attempt to deserialize an object from the byte array that is read from the database. The exception is raised when the serialized object mapping is converting the byte array into an object.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00067: Could not serialize object into byte array.**

**Cause:** Attempt to serialize an object into a byte array. The exception is raised when a serialized object mapping is converting the object into a byte array.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00068: The value of an aggregate in object [{0}] is null. Null values not allowed for Aggregate mappings unless "Allow Null" is specified.**

**Cause:** The value of the aggregate in the source object object is null. Null values are not allowed for aggregate mappings unless allow null is specified in the aggregate mapping.

**Action:** Call the mapping method allowNull. Provide parameters only if you are making a distinction between foo() and foo(integer).

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00069: A NullPointerException was thrown while extracting a value from the instance variable [{0}] in the object [{1}].**

**Cause:** An object is accessed to get the value of an instance variable through Java reflection. This exception is raised only on some JVMs.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00070: A NullPointerException was thrown while extracting a value through the method [{0}] in the object [{1}].**

**Cause:** The getter method is invoked to get the value of an attribute through Java reflection. This exception is raised only on some JVM.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**TOP-00071: A NullPointerException was thrown while setting the value of the instance variable [{0}] to the value [{1}].**

**Cause:** A NullPointerException has been raised while setting the value of the attributeName instance variable in the object to value. An object is accessed to set the value of an instance variable through Java reflection. This exception is raised only on some JVMs.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00072: A NullPointerException was thrown while setting a value through the method [{0}] with argument [{1}].**

**Cause:** A NullPointerException has been raised while setting the value through setMethodName method in the object with an argument argument. The set accessor method is invoked to set the value of an attribute through Java reflection. This exception is raised only on some JVMs.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00073: Cannot find descriptor for parent class [{0}].**

**Cause:** TopLink is unable to find the descriptor for the parent class. The descriptor of a subclass has no parent descriptor.

**Action:** The method setParentClass(Class parentClass) must be called on the subclass descriptor.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00074: The primary key fields are not set for this descriptor.**

**Cause:** The primary key fields are not set for this descriptor.

**Action:** Add primary key field names using method setPrimaryKeyFieldName(String fieldName).

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00075: The reference class is not specified for this descriptor.**

**Cause:** The reference class is not specified in the foreign reference mapping.

**Action:** Set the reference class by calling the method setReferenceClass(Class aClass).

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**TOP-00077: The reference descriptor for [{0}] should be set to be an Aggregate descriptor.**

**Cause:** The referenced descriptor for class className is not set to an aggregate descriptor. An aggregate mapping should always reference a descriptor that is aggregate.

**Action:** Call the method descriptorIsAggregate on the referenced descriptor.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00078: The reference field [{0}] for this mapping must exist in the reference table.**

**Cause:** The table for the reference field is not the reference table. If the reference field name that is specified in the direct collection mapping is qualified with the table name, then the table name should match the reference table name.

**Action:** Qualify the field with the proper name, or change the reference table name.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00079: The reference table is not specified for this mapping.**

**Cause:** The reference table name in the direct collection mapping is not specified.

**Action:** Use the method setReferenceTableName(String tableName) on the mapping to set the table name.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00080: The relation key field [{0}] for this mapping must exist in the relation table.**

**Cause:** The table for the relation key field is not the relation table. If the source and target relation fields names that are specified in the many-to-many mapping are qualified with the table name, then the table name should match the relation table name.

**Action:** Qualify the field with the proper name, or change the relation table name.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00081: The method [{0}] should return the type of the mapped attribute, not void.**

**Cause:** The method attributeMethodName that is specified in the transformation mapping does not have a return type set in the attribute, as it should because this method is used to extract value from the database row.

**Action:** Verify the method and make appropriate changes.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**TOP-00082: The descriptor callback method [{0}], with parameter (DescriptorEvent), is not accessible.**

**Cause:** The descriptor callback method with DescriptorEvent as an argument is not accessible. Java raises a security exception when a Method type is created from the method name using Java reflection. The method is a descriptor event callback on the domain object that takes DescriptorEvent as its parameter.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00083: The descriptor callback method [{0}], with parameter (Session), is not accessible.**

**Cause:** The descriptor callback method with Session as an argument is not accessible. Java raises a security exception when a Method type is created from the method name using Java reflection. The method is a descriptor event callback on the domain object, which takes class and session as its parameters.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00084: The method [{0}], with parameters (Record) or (Record, Session), is not accessible.**

**Cause:** Access to the method methodName(Record databaseRow) or methodName(Record databaseRow, Session session) has been denied. Java raises a security exception when a Method type is created from the attribute method name using Java reflection. The attribute method that is specified in the transformation mapping is used to extract value from the database row and set by calling setAttributeTransformation(String methodName).

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00085: The method [{0}], with parameters () or (Session), is not accessible.**

**Cause:** TopLink failed to find a method with signature methodName() or methodName(oracle.toplink.sessions.Session). Java raises a security exception when a Method type is created from the method name using Java reflection. These are the methods that extract the field value from the domain object in the transformation mapping.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR



---

**Impact:** Configuration

**TOP-00086: The instance variable [{0}] in the class [{1}] is not accessible.**

**Cause:** Access to the instance variable attributeName in the class javaClassName is denied. Java raises a security exception when creating a Field type from the given attribute name using Java reflection.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00087: The methods [{0}], [{1}] in the object [{2}] are not accessible**

**Cause:** The methods setMethodName and getMethodName in the object javaClassName are inaccessible. Java raises a security exception when creating a Method type from the given attribute accessor method name using Java reflection.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00088: The static class extraction method [{0}], with parameter (Record), is not accessible.**

**Cause:** The static class extraction method methodName(Record databaseRow) is not accessible. Java raises a security exception when creating a Method type from the given class extraction method name using Java reflection. The method is used to extract the class from the database row in the inheritance policy.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00089: The clone method [{0}], with no parameters, is not accessible.**

**Cause:** The clone method methodName() is inaccessible. Using ClassDescriptor method useCloneCopyPolicy (java.lang.String methodName), you can specify that the creation of clones within a unit of work is done by sending the methodName method to the original object. If the clone method methodName with no arguments is inaccessible (your application does not have sufficient privileges to call the method), Java raises a security exception when reflectively accessing the method with the given method name using the java.lang.reflect Java package.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00090: The instance creation method [{0}], with no parameters, is not accessible.**

**Cause:** The instance creation method methodName() is inaccessible. Using any of the ClassDescriptor methods useFactoryInstantiationPolicy (java.lang.Class factoryClass, java.lang.String methodName), useFactoryInstantiationPolicy

---

(java.lang.Class factoryClass, java.lang.String methodName, java.lang.String factoryMethodName), useFactoryInstantiationPolicy (java.lang.Object factory, java.lang.String methodName), or useMethodInstantiationPolicy(java.lang.String staticMethodName), you can specify how new instances are created. If any of the methods or factory methods are inaccessible (your application does not have sufficient privileges to call the method), Java raises a security exception when reflectively accessing the method with the given method name using the java.lang.reflect Java package.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00091: To use sequence-generated IDs, both the "Sequence Number Name" and "Sequence Number Field Name" properties must be set for this descriptor.**

**Cause:** Either the sequenceNumberName or the sequenceNumberFieldName property is not set. To use sequence-generated IDs, both the sequenceNumberName and sequenceNumberFieldName properties must be set for the descriptor.

**Action:** To use sequence-generated IDs, set both the sequence number name and field name properties.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00092: The size of the target's primary key does not match the size of the foreign key.**

**Cause:** The size of the primary keys on the target table does not match the size of the foreign keys on the source in one-to-one mapping.

**Action:** Verify the mapping and the reference descriptor's primary keys.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00093: The table [{0}] is not present in this descriptor.**

**Cause:** The table tableName is not present in the descriptor.

**Action:** Verify the qualified field names that are specified in the mappings and descriptor so that any fields that are qualified with the table name reference the correct table.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00094: Descriptors must have a table name defined.**

**Cause:** No table is specified in the descriptor. The descriptor must have a table name defined.

**Action:** Call the method addTableName(String tableName) or setTableName(String tableName) to set the tables on the descriptor.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00096: The number of target keys does not match the number of source keys.**

**Cause:** The size of the foreign keys on the target table does not match the size of the source keys on the source table in the one-to-many mapping.

**Action:** Verify the mapping.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00097: Problem cloning the object [{0}]. The clone method [{0}] triggered an exception.**

**Cause:** TopLink has encountered a problem in cloning the object domainObject clone method. The methodName triggered an exception. Java raises this exception when the cloned object is invoked while the object is being cloned. The clone method is specified on the copy policy that is usually invoked to create clones in unit of work.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00098: The underlying descriptor callback method [{0}], with parameter (DescriptorEvent), triggered an exception.**

**Cause:** A descriptor callback method eventName(DescriptorEvent event) is not accessible. The exception occurs when the descriptor event method is invoked using Java reflection.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00099: The method [{0}] on the object [{1}] triggered an exception.**

**Cause:** The method methodName on the object objectName is throwing an exception. Java is throwing an exception while getting an attribute value from the object through a method accessor.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00100: A method has triggered an exception.**

**Cause:** A method has raised an exception. Java raises this exception while instantiating a method based proxy and instantiating transformation mapping.

**Action:** Inspect the internal exception, and refer to the Java documentation.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00101: The underlying method triggered an exception.**

**Cause:** The underlying method raises an exception. Java is throwing an exception while invoking an attribute transformation method on transformation mapping. The method is invoked to extract value from the database row to set into the domain object.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00102: The method [{0}] triggered an exception.**

**Cause:** The method methodName is throwing an exception. Java is throwing exception while invoking field transformation method on transformation mapping. The method is invoked to extract value from the domain object to set into the database row.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00103: Problem in extracting class from row [{0}], using static method [{1}], with parameter (DatabaseRow). An exception was triggered.**

**Cause:** TopLink encountered a problem extracting the class type from row rowName while invoking a class extraction method.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00104: Problem in creating new instance using creation method [{0}]. The creation method triggered an exception.**

**Cause:** TopLink is unable to create a new instance. The creation method methodName caused an exception.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00105: The underlying descriptor callback method [{0}], with parameter (Session), triggered an exception.**

**Cause:** The underlying descriptor callback method eventName(Session session) raises an exception. Java is throwing an exception while invoking a descriptor event method that takes a session as its parameter.

---

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00106: The method [{0}] on the object is throwing an exception. {2}Argument: [{1}]**

**Cause:** The method setMethodName on the object raises an exception. Java is throwing an exception while invoking a set accessor method on the domain object to set an attribute value into the domain object.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00108: Cannot find value in class indicator mapping in parent descriptor [{0}].**

**Cause:** The indicator value is not found in the class indicator mapping in the parent descriptor for the class.

**Action:** Verify the addClassIndicator(Class childClass, Object typeValue) on the inheritance policy.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00109: This descriptor should not have a write lock field defined because it is a child descriptor. It inherits its parent descriptor's write lock field.**

**Cause:** The child descriptor has a write-lock field defined. This is unnecessary, because it inherits any required locking from the parent descriptor.

**Action:** Check your child descriptor, and remove the field.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00110: Descriptor is missing for class [{0}].**

**Cause:** The descriptor for the reference class className is missing from the mapping.

**Action:** Verify the session to see if the descriptor for the reference class was added.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00111: Multiple table primary key field names must be fully qualified.**

**Cause:** Multiple table primary key field names are not fully qualified. These field names are given on the descriptor if it has more than one table.

**Action:** Specify the field names with the table name.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00112: Only one table can be added by using `setTableName(String)`. Use `addTableName(String)` to add multiple tables to a descriptor.**

**Cause:** Attempt to enter more than one table through this method.

**Action:** Use the method `addTableName(String tableName)` to add multiple tables to the descriptor.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00113: The constructor was inaccessible.**

**Cause:** The constructor is inaccessible. Java is throwing this exception while invoking a default constructor to create new instances of the domain object.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00114: Problem in creating new instance using creation method `[[0]]`. The creation method is not accessible.**

**Cause:** The new instance method `methodName` creation method is inaccessible. Java is throwing an exception while calling a method to build new instance of the domain object. This method is given by the user to override the default behavior of creating new instances through a class constructor.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00115: No conversion value provided for the attribute `[[0]]`.**

**Cause:** The field conversion value for the attribute value `attributeValue` was not given in the object type mapping.

**Action:** Verify the attribute value, and provide a corresponding field value in the mapping.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00116: No conversion value provided for the value `[[0]]` in field `[[1]]`.**

**Cause:** The attribute conversion value for the field value was not given in the object type mapping.

**Action:** Verify the field value, and provide a corresponding attribute value in the mapping.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00118: The object [{0}] must not have read-only mappings to its write lock fields.**

**Cause:** The domain object className cannot have a read-only mapping for the write-lock fields when the version value is stored in the object.

**Action:** Verify the mappings on the write-lock fields.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00119: The object's [{0}] mappings to its write lock fields must be read-only.**

**Cause:** The domain object className does not have a read-only mapping for the write-lock fields when the version value is stored in the cache.

**Action:** Verify the mappings on write-lock fields.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00120: The query key [{0}] is defined in the parent descriptor [{1}], but not in the child descriptor [{2}].**

**Cause:** The query key queryKeyName is defined in the parent descriptor, but not in the child descriptor. The descriptor has not defined the abstract query key.

**Action:** Define any class that implements the interface descriptor by the abstract query key in the interface descriptor.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00122: setExistenceCheck() with argument [{0}] is not understood.**

**Cause:** The interface descriptor parent does not have at least one abstract query key defined. The string given to the method setExistenceChecking(String token) is not understood.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00125: The mapping for the attribute [{0}] uses indirection, and so must be initialized to a new ValueHolder. Currently the value is: [{1}].**

**Cause:** The mapping for the attribute getAttributeName() uses indirection and must be initialized to a new value holder.

**Action:** Ensure that the mapping uses indirection and that the attribute is initialized to a new value holder.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00126: No subclass matches this class [{0}] for this Aggregate mapping with inheritance.**

**Cause:** No subclass matches this class theClass when inheritance is in aggregate relationship mapping.

**Action:** Verify the subclass and the relationship mapping.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00127: The get method for the attribute [{0}] does not return a ValueHolderInterface, but the mapping uses indirection.**

**Cause:** The return type of the method used to get the attribute getAttributeName() of a mapping is not declared as type ValueHolderInterface, but the mapping is using indirection.

**Action:** Verify that the method used to get the attribute named getAttributeName() of DatabaseMapping returns a value holder, or change the mapping so it does not use indirection.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00128: The get method for the attribute [{0}] returns a ValueHolderInterface, but the mapping does not use indirection.**

**Cause:** The return type of the method used to get the attribute getAttributeName() of DatabaseMapping is declared as type ValueHolderInterface, but the mapping is not using indirection.

**Action:** Ensure that the mapping is using indirection, or change the return type from value holder.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00129: The set method for the attribute [{0}] does not take a ValueHolderInterface as its parameter, but the mapping uses indirection.**

**Cause:** The return type of the method used to set the attribute getAttributeName() of DatabaseMapping is not declared as type ValueHolderInterface, but the mapping is using indirection.

**Action:** Ensure that the set method parameter is declared as a valueholder, or change the mapping so it does not use indirection.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration



---

**TOP-00130: The set method for the attribute [{0}] takes a ValueHolderInterface as its parameter, but the mapping does not use indirection.**

**Cause:** The return type of the method used to set the attribute `getAttributeName()` of `DatabaseMapping` is declared as type `ValueHolderInterface`, but the mapping is not using indirection.

**Action:** Ensure that the mapping is changed to use indirection, or that the method parameter is not declared as a value holder.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00131: The get method for the attribute [{0}] should return a Vector (or a type that implements Map or Collection, if using Java 2).**

**Cause:** The return type of the method used to get the attribute `getAttributeName()` of `DatabaseMapping` is not declared as type `Vector` (or a type that implements the `Map` or `Collection` interface if using Java 2).

**Action:** Declare the return type of the method used to get the attribute `getAttributeName()` of `DatabaseMapping` as type `Vector` (or a type that implements the `map` or `collection` interface if using Java 2).

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00133: The set method for the attribute [{0}] should take a Vector as its parameter (or a type that implements Map or Collection, if using Java 2).**

**Cause:** The parameter type of the method used to set the attribute `getAttributeName()` of `DatabaseMapping` is not declared as type `Vector` (or a type that implements the `map` or `collection` interface, if using Java 2).

**Action:** Declare the parameter type of the method used to set the attribute `getAttributeName()` of `DatabaseMapping` as type `Vector` (or a type that implements the `Map` or `Collection` interface, if using Java 2).

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00135: The multiple table foreign key relationship refers to an unknown table [{0}].**

**Cause:** The table in the multiple table foreign key relationship refers to an unknown table.

**Action:** Verify the table name.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00138: The attribute [{0}] is not declared as a superclass of [{1}], but the mapping uses transparent indirection.**

**Cause:** The attribute `getAttributeName()` of `DatabaseMapping` is not declared as a supertype of `validTypeName`, but the mapping is using transparent indirection.

---

**Action:** Verify the attribute's type and the mapping setup.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00139: The get method for the attribute [{0}] does not return a superclass of [{1}], but the mapping uses transparent indirection.**

**Cause:** The return type of the method used to get the attribute `getAttributeName()` of `DatabaseMapping` is not declared as a super-type of `validTypeName`, but the mapping is using transparent indirection.

**Action:** Verify the attribute's type and the mapping setup.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00140: The set method for the attribute [{0}] does not take a superclass of [{1}] as its parameter, but the mapping uses transparent indirection.**

**Cause:** The parameter type of the method used to set the attribute `getAttributeName()` of `DatabaseMapping` is not declared as a supertype of `validTypeName`, but the mapping is using transparent indirection.

**Action:** Verify the attribute's type and the mapping setup.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00141: The field [{0}] is not present in the table [{1}] in the database.**

**Cause:** The field `fieldname` is not present in the table `tableName` in the database.

**Action:** Verify the field name for the attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00142: The table [{0}] is not present in the database.**

**Cause:** The table whose name is provided by the Descriptor method `getTableName` is not present in the database.

**Action:** Verify the table name for the descriptor.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00143: The multiple table insert order Vector specified, [{0}], has more or fewer tables than are specified in the descriptor. {2}All of the tables [{1}] must be included in the insert order Vector.**

**Cause:** The multiple table insert order vector specified the Descriptor method `getMultipleTableInsertOrder` has fewer or more tables than are specified in the

---

Descriptor method `getTables`. All the tables must be included in the insert order vector.

**Action:** Ensure that all table names for the descriptor are present and that there are no extra tables.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00144: Transparent indirection can only be used with `CollectionMappings`.**

**Cause:** Transparent indirection is being used with a mapping other than a `CollectionMapping`.

**Action:** Verify the mapping. It must be a collection mapping.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00145: The indirect container class `{0}` must implement the constructor `{1}` with parameter `(ValueHolderInterface)`.**

**Cause:** The indirect container class does not implement the constructor.

**Action:** Implement the constructor for the container.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00146: The indirect container class `{0}` could not be instantiated using the constructor `{1}(ValueHolderInterface)`.**

**Cause:** `TopLink` is unable to instantiate the indirect container class using the constructor.

**Action:** Validate the constructor for the indirect container class.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00147: The container policy `{0}` should only be used in JDK 1.1.x. It was instantiated for `{1}`.**

**Cause:** You have used a container policy with an incompatible version of the JDK. This container policy must only be used with JDK 1.3.1 or later.

**Action:** Validate the container policy being used.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00148: The container policy `{0}` is not compatible with transparent indirection.**

**Cause:** The container policy is incompatible with transparent indirection.

**Action:** Change the container policy to be compatible with transparent indirection, or do not use transparent indirection.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00149: NoIndirectionPolicy objects should not receive this message.**

**Cause:** NoIndirectionPolicy object calls this method.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00150: The mapping for the attribute [{0}] uses transparent indirection so the attribute [{0}] must be initialized to an appropriate container. Currently the value is [{1}]. {2} - Must be instance of an implementor of Collection or Map.**

**Cause:** The mapping for the attribute `getAttributeName()` of `DatabaseMapping` uses transparent indirection and must be initialized to an appropriate container.

**Action:** Initialize the mapping to an appropriate container.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00151: The operation [{0}] is invalid for this mapping.**

**Cause:** An invalid mapping operation has been used.

**Action:** See the documentation for valid mapping operations.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00152: The operation [{1}] is invalid for this indirection policy [{0}].**

**Cause:** An invalid indirection policy operation has been used.

**Action:** See the documentation for valid indirection policy operations.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00153: The reference descriptor for [{0}] should be set to be an Aggregate Collection descriptor.**

**Cause:** The reference descriptor for `className` is not set to an aggregate collection descriptor.

**Action:** Set the reference descriptor to an aggregate collection descriptor.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00154: The indirection container class [{0}] does not implement IndirectContainer.**

---

**Cause:** An invalid indirection container class has been used.

**Action:** Verify the container class.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00155: This mapping does not include a foreign key field linked to the primary key field [{0}].**

**Cause:** The mapping does not include a foreign key field linked to the primary key field.

**Action:** Link the foreign key to the appropriate primary key.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00156: The structure name is not set for this mapping.**

**Cause:** The structure name is not set.

**Action:** Set the structure name appropriately.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00157: Normal descriptors do not support non-relational extensions.**

**Cause:** Relational descriptors do not support nonrelational extensions.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00158: This descriptor's parent class has been set to itself.**

**Cause:** The descriptor's parent class has been set to itself.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00159: Proxy indirection is available only in JDK 1.3-compliant or higher virtual machines.**

**Cause:** An attempt to use proxy indirection has been made, but JDK 1.3.1 or later is not being used.

**Action:** Use JDK 1.3.1 or later.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**TOP-00160: The attribute [{0}] of class [{1}] is typed as [{2}], which was not specified in the list of interfaces given to the useProxyIndirection() method. {4}Valid interfaces are: [{3}].**

**Cause:** The attribute was not specified in the list of interfaces given to use proxy indirection.

**Action:** Verify the attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00161: The method [{0}] in class [{1}] returns a value of type [{2}], which was not specified in the list of interfaces given to the useProxyIndirection() method. {4}Valid interfaces are: [{3}].**

**Cause:** The return type for the indirection policy is invalid for the indirection policy.

**Action:** Ensure that the parameter type of the getter method is correct for the indirection policy.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00162: The method [{0}] in class [{1}] takes a parameter of type [{2}], which was not specified in the list of interfaces given to the useProxyIndirection() method. {4}Valid interfaces are: [{3}].**

**Cause:** The parameter for the setter method is incorrect for the indirection type.

**Action:** Ensure that the parameter type of the setter method is correct for the indirection policy.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00163: This mapping's attribute class does not match the collection class. [{1}] cannot be assigned to [{0}].**

**Cause:** The container policy is invalid for the collection type.

**Action:** Ensure that the container policy is correct for the collection type.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00164: The amendment method [{1}], in amendment class [{0}], is invalid, not public, or cannot be found. {2}Descriptor amendment methods must be declared "public static void" with (ClassDescriptor) as the single parameter.**

**Cause:** The amendment method that is provided is invalid, not public, or cannot be found.

**Action:** Ensure that the amendment method is public, static, returns void, and has a single argument: Descriptor.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**TOP-00165: This descriptor's amendment method [{1}] in amendment class [{0}] triggered an exception.**

**Cause:** The specified amendment method threw an exception.

**Action:** Examine the returned exception for further information.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00166: There is no mapping for the attribute [{0}].**

**Cause:** There is no mapping for the attribute.

**Action:** Validate the mapping and attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00167: A valid constructor was not found for the indirection container class [{0}].**

**Cause:** A valid constructor was not found for the indirection container class.

**Action:** Add a default constructor or a constructor with a ValueHolderInterface in the container class.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00168: Problem in creating new instance using the default constructor. The default constructor triggered an exception.**

**Cause:** The constructor is missing.

**Action:** Create the required constructor.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00169: Problem in creating new instance of factory using the default constructor. The default constructor triggered an exception.**

**Cause:** The constructor is missing.

**Action:** Create the required constructor.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00170: Problem (illegal access) in creating new instance of factory using the default constructor.**

**Cause:** Permissions do not allow access to the constructor.

---

**Action:** Adjust the Java security permissions to permit access to the constructor.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00171: The factory class does not define a public default constructor, or the constructor raised an exception.**

**Cause:** An instantiation failed inside the associated constructor.

**Action:** Determine which objects are being instantiated, and verify that all are instantiated properly.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00172: Factory constructor not found.**

**Cause:** A method call from inside the constructor is invalid because this method does not exist.

**Action:** Ensure that the factory has a default constructor for the called method.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00173: The factory constructor was inaccessible.**

**Cause:** A method on a null object was called from inside a constructor. The factory constructor was inaccessible.

**Action:** Examine the internal exception and take the appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00174: Problem in creating factory. The creation method [{0}] is not accessible.**

**Cause:** A method was called on an object from inside a factory instantiation, and Java has determined this method to be invalid.

**Action:** Determine why the method is invalid, and replace the method with a valid one.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00175: Problem creating factory using creation method [{0}]. The creation method triggered an exception.**

**Cause:** A problem was encountered creating factory using creation method. The creation method triggered an exception.

**Action:** Examine the exception and take the corresponding action.

**Level:** 1



---

**Type:** ERROR

**Impact:** Configuration

**TOP-00176: Problem in creating factory using creation method [{0}]. The creation method is not accessible.**

**Cause:** A method called to instantiate a factory threw a NullPointerException. The creation method is not accessible.

**Action:** Do not use that method to instantiate a factory.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00177: Mapping is missing for the attribute: [{0}].**

**Cause:** Mapping is missing for the attribute attributeName.

**Action:** The attribute must be mapped.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00178: Cannot find mapping for attribute [{0}] in entity bean [{1}]. The attribute must mapped.**

**Cause:** Cannot find mapping for an attribute attributeName in an entity bean beanName.

**Action:** Map the attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00179: The attribute, [{0}] uses Bidirectional Relationship Maintenance, but has ContainerPolicy, [{1}] which does not support it. The attribute should be mapped with a different collection type.**

**Cause:** The attribute uses bidirectional relationship maintenance, but has ContainerPolicy, which does not support it.

**Action:** The attribute must be mapped with a different collection type.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00181: The AttributeTransformer class, [{0}] cannot be found.**

**Cause:** The AttributeTransformer class cannot be found.

**Action:** Ensure that the AttributeTransformer class exists and is on the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00182: The FieldTransformer class, [{0}] cannot be found.**

---

**Cause:** The FieldTransformer class cannot be found.

**Action:** Ensure that the FieldTransformer class exists and is on the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00183: The class, [{0}] cannot be used as an AttributeTransformer.**

**Cause:** Invalid use of a class className as an AttributeTransformer.

**Action:** Examine the internal exception stack trace and make the appropriate correction.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00184: The class, [{0}] cannot be used as a FieldTransformer.**

**Cause:** Invalid use of a class className as a FieldTransformer.

**Action:** Do not use the class as a FieldTransformer.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00185: ReturningPolicy contains field, [{0}] with two different types: [{1}] and [{2}].**

**Cause:** ReturningPolicy contains field with two different types.

**Action:** The field was added to ReturningPolicy twice with different types. The field must be added to ReturningPolicy once. You must remove excessive addFieldForInsert and/or addInsertField calls.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00186: ReturningPolicy contains field, [{0}] added twice: using addInsertField and addInsertFieldReturnOnly.**

**Cause:** ReturningPolicy contains field that has been added twice using addInsertField and addInsertFieldReturnOnly.

**Action:** A field must be added to ReturningPolicy only once. You must remove excessive addField calls.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00187: ReturningPolicy contains field, [{0}] with type [{1}], but the same field in descriptor has type [{2}].**

**Cause:** ReturningPolicy contains field with type Type, but the same field in descriptor has type differentType.

---

**Action:** Specify field type in addField method only in the event that it cannot be obtained from the descriptor.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00188: ReturningPolicy contains unmapped field, [{0}] which requires type.**

**Cause:** ReturningPolicy contains unmapped field fieldName that requires type.

**Action:** You must specify field type in the addField method.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00189: ReturningPolicy contains mapped field, [{0}] which requires type.**

**Cause:** ReturningPolicy contains mapped field fieldName that requires type.

**Action:** You must specify field type in the addField method.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00190: ReturningPolicy contains field, [{0}] mapped with [{1}] mapping which is not supported.**

**Cause:** ReturningPolicy contains a field that is mapped with unsupported mapping.

**Action:** You cannot use ReturningPolicy with this field. Do not add it to ReturningPolicy.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00191: ReturningPolicy contains field, [{0}] which is not supported: it is either sequence field, or class type indicator, or used for locking.**

**Cause:** ReturningPolicy contains a field fieldName that is not supported. Field is either sequence field, class type indicator, or used for locking.

**Action:** You cannot use ReturningPolicy with this field. Do not add it to ReturningPolicy.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00192: ReturningPolicy contains field, [{0}] but custom [{1}] doesn't output it.**

**Cause:** ReturningPolicy contains a field fieldName, but custom query queryName does not output it.

**Action:** Update the custom query so that it outputs a value for this field.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**TOP-00193: There is no custom [{0}] set, but ReturningPolicy contains field(s) to be returned and [{1}] doesn't support generating call with returning.**

**Cause:** There is no custom query set, but ReturningPolicy contains one or more fields to be returned and doesn't support generating call with return.

**Action:** Specify a custom InsertObjectQuery or UpdateObjectQuery through DescriptorQueryManager setInsertQuery, setInsertCall, setUpdateQuery, or setUpdateCall methods that outputs values for fields added to ReturningPolicy.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00194: The class extraction method [{0}], must be a static method on the descriptor's class.**

**Cause:** The class extraction method must be a static method on the descriptor's class.

**Action:** Make the class extraction method a static method on the descriptor's class.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00195: The shared class {1} must not reference the isolated class {0}.**

**Cause:** The shared class must not reference the isolated class.

**Action:** Ensure that the shared class does not reference the isolated class.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00196: UpdateAllFields has not been set or has been set to false. When using CMPPolicy.setForceUpdate(true) you must also call CMPPolicy.setUpdateAllFields(true)**

**Cause:** updateAllFields flag has not been set or has been set to false. When using setForceUpdate(true) method of CMPPolicy you must also call setUpdateAllFields(true) method of CMPPolicy.

**Action:** Ensure that updateAllFields is set to true if forceUpdate is true.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00197: The mapping [{0}] is not the appropriate type for this descriptor**

**Cause:** A mapping of an inappropriate type has been set for this descriptor.

**Action:** The mapping type has to map the descriptor type, e.g. relational mapping for relational descriptor, EIS mapping for EIS descriptor, and XML mapping for XML descriptor.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**TOP-00198: In order to use ObjectChangeTrackingPolicy or AttributeChangeTrackingPolicy, {0} has to implement ChangeTracker interface.**

**Cause:** The object does not implement the ChangeTracker interface.

**Action:** Ensure that the object implements ChangeTrackerInterface in order to use ObjectChangeTrackingPolicy or AttributeChangeTrackingPolicy.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00199: In order to use Fetch Group, the domain class ({0}) has to implement FetchGroupTracker interface.**

**Cause:** The domain class does not implement the FetchGroupTracker interface.

**Action:** Ensure that the domain class implements the FetchGroupTracker interface in order to use the fetch group.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00200: Attempt to register an object with dead indirection as a new object. Possibly the object was deleted or removed from the cache during a merge of a serialized clone. This is a concurrency violation, consider a locking strategy.**

**Cause:** Attempt to register an object with dead indirection as a new object. Possibly, the object was deleted or removed from the cache during a merge of a serialized clone or did not exist in the cache at the time of the merge. This is a concurrency violation.

**Action:** Ensure that the object exists in the cache before attempting to merge a deserialized version into the cache. Consider a locking strategy. For more information, see "Merging Changes in Working Copy Clones" on page 112-12 and "Indirection, Serialization, and Detachment" on page 17-11.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-00201: An object was attempted to be built in the session cache, but the descriptor is marked as isolated in the unit of work, so should never be accessed outside of a unit of work.**

**Cause:** Attempt to built and object in the session cache, but the descriptor is marked as isolated in the unit of work.

**Action:** Ensure that the descriptor is never accessed outside of a unit of work.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-02001: Wait was interrupted. {0}Message: [{1}]**

---

**Cause:** In a multi threaded environment, one of the waiting threads was interrupted.

**Action:** Such exceptions are application-dependent.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**TOP-02002: Wait failure on ServerSession.**

**Cause:** A request for a connection from the connection pool has been forced to wait, and that wait has been interrupted.

**Action:** Such exceptions are application-dependent.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**TOP-02003: Wait failure on ClientSession.**

**Cause:** A request for a connection from the connection pool has been forced to wait, and that wait has been interrupted.

**Action:** Such exceptions are application-dependent.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**TOP-02004: A signal was attempted before wait() on ConcurrencyManager. This normally means that an attempt was made to {0}commit or rollback a transaction before it was started, or to rollback a transaction twice.**

**Cause:** A signal was attempted before a wait on concurrency manager. This usually means that an attempt was made to commit or roll back a transaction before it was started, or to rollback a transaction twice.

**Action:** Verify transactions in the application.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**TOP-02005: Wait failure on Sequencing Connection Handler for DatabaseSession.**

**Cause:** An InterruptedException was raised while DatabaseSession sequencing waited for a separate connection to become available.

**Action:** Examine concurrency issues involving object creation with your DatabaseSession.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**TOP-02006: Attempt to acquire sequencing values through a single Connection({0}) simultaneously in multiple threads**

---

**Cause:** Several threads attempted to concurrently obtain sequence objects from the same DatabaseSession or ClientSession.

**Action:** Avoid concurrent writing through the same DatabaseSession or ClientSession.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**TOP-02007: Max number of attempts to lock object: {0} exceeded. Failed to clone the object.**

**Cause:** Maximum number of attempts to lock object was exceed resulting in a failure to clone the object.

**Action:** Ensure that the number of attempts is within the limit.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**TOP-02008: Max number of attempts to lock object: {0} exceeded. Failed to merge the transaction.**

**Cause:** Maximum number of attempts to lock object was exceed resulting in a failure to merge the transaction.

**Action:** Ensure that the number of attempts is within the limit.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**TOP-02009: Max number of attempts to lock object exceeded. Failed to build the object. Thread: {0} has a lock on the object but thread: {1} is building the object**

**Cause:** Maximum number of attempts to lock object was exceed resulting in a failure to build the object: thread threadNumber has a lock on the object, but thread anotherThreadNumber is building the object

**Action:** Ensure that the number of attempts is within the limit.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**TOP-03001: The object [{0}], of class [{1}], could not be converted to [{2}].**

**Cause:** Attempt to convert an object object of class ObjectClass to JavaClass. The object cannot be converted to a given type.

**Action:** Ensure that the object being converted is of the right type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-03002: The object [{0}], of class [{1}], from mapping [{2}] with descriptor [{3}], could not be converted to [{4}].**

---

**Cause:** Attempt to convert an object object of class ObjectClass from mapping mappingType to JavaClass. The object cannot be converted to a given type.

**Action:** Ensure that the object being converted is of the right type.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-03003: Incorrect date format: [{0}] (expected [YYYY-MM-DD])**

**Cause:** The date in dateString is in an incorrect format. The expected format is YYYY-MM-DD.

**Action:** Verify the date format.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-03004: Incorrect time format: [{0}] (expected [HH:MM:SS])**

**Cause:** The time in timeString is in an incorrect format. The expected format is HH:MM:SS.

**Action:** Verify the time format.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-03005: Incorrect timestamp format: [{0}] (expected [YYYY-MM-DD HH:MM:SS.NNNNNNNNN])**

**Cause:** The timestamp timestampString is in an incorrect format. The expected format is YYYY-MM-DD HH:MM:SS.NNNNNNNNN.

**Action:** Verify the timestamp format.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-03006: [{0}] must be of even length to be converted to a byte array.**

**Cause:** Attempt to convert String object of uneven length to a ByteArray. This object cannot be converted to a ByteArray.

**Action:** Verify the object being converted.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-03007: The object [{0}], of class [{1}], could not be converted to [{2}]. Please ensure that the class [{0}] is on the CLASSPATH. You may need to use alternate API passing in the appropriate class loader as required, or setting it on the default ConversionManager**

**Cause:** Attempt to convert an object object of class ObjectClass to JavaClass. The class JavaClass is not on the classpath.



---

**Action:** Ensure that the class `JavaClass` is on the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-03008: Incorrect date-time format: [{0}] (expected [YYYY-MM-DD'T'HH:MM:SS])**

**Cause:** Incorrect date-time format object. The expected format is `YYYY-MM-DD'T'HH:MM:SS`.

**Action:** Ensure that the date-time object is in the expected format of `YYYY-MM-DD'T'HH:MM:SS`.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-04003: Configuration error. Class [{0}] not found.**

**Cause:** The driver class name was not found.

**Action:** Verify the class name given in `JDBCLogin`.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-04005: DatabaseAccessor not connected.**

**Cause:** The session is not connected to the database while attempting to read or write on the database.

**Action:** An application may have to log in again because the connection to the database might have been lost.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-04006: Error reading BLOB data from stream in getObject().**

**Cause:** An error occurred reading BLOB data from the database. There are two possibilities for this exception: either the BLOB data was not read properly from the result set or `TopLink` cannot process the BLOB data using `ByteArrayOutputStream`.

**Action:** Verify whether the underlying driver supports BLOBs properly. If it does, then report this problem to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-04007: Could not convert object type due to an internal error.**

**{0}java.sql.Types: [{1}]**

---

**Cause:** Attempt to convert an object type on internal error.java.sql.Types = type. The object from the result set cannot be converted to the type that was returned from the metadata information.

**Action:** Verify whether the underlying driver supports the conversion type properly. If it does, then report this problem to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-04008: You cannot logout while a transaction is in progress.**

**Cause:** Attempt to log out while the transaction is still in progress. You cannot log out while a transaction is in progress.

**Action:** Wait until the transaction is finished.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-04009: The sequence table information is not complete.**

**Cause:** The sequence information given to TopLink is not sufficiently complete to get the set of sequence numbers from the database. This usually happens on native sequencing on an Oracle database.

**Action:** Verify the data provided, especially the sequence name provided in TopLink.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-04011: Error preallocating sequence numbers. The sequence table information is not complete.**

**Cause:** An error occurred preallocating sequence numbers on the database; the sequence table information is not complete.

**Action:** Ensure the sequence table was properly created on the database.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-04015: Synchronized UnitOfWork does not support the commitAndResume() operation.**

**Cause:** A synchronized UnitOfWork does not support the commitAndResume operation. When the TopLink session is configured with an ExternalTransactionController, any unit of work requested by a client must operate within the context of a JTS external global transaction (see ). The JTS specification does not support the concept of check pointing a transaction—that is, committing the work performed and then continuing to work within the same transaction context. JTS does not support nested transactions, either. As a result, if a client code invokes commitAndResume on a synchronized unit of work, this error is reported.

**Action:** None required.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-04016: Configuration error. Could not instantiate driver [{0}].**

**Cause:** A configuration error occurred when TopLink attempted to instantiate the given driver class. TopLink cannot instantiate the driver.

**Action:** Check the driver.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-04017: Configuration error. Could not access driver [{0}].**

**Cause:** A configuration error occurred when TopLink attempted to instantiate the given driver class. TopLink cannot instantiate the driver.

**Action:** Check the driver.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-04018: The TransactionManager has not been set for the JTS driver.**

**Cause:** The transaction manager has not been set for the JTSSynchronizationListener.

**Action:** Set a transaction manager for the JTSSynchronizationListener.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-05001: An attempt was made to delete the object [{0}], but it has no version number in the identity map. {3}It may not have been read before the delete was attempted. {3}Class> {1} Primary Key> {2}**

**Cause:** Attempt to delete the object object that does not have a version number in the identity map. This object either was never read or has already been deleted.

**Action:** Use SQL logging to determine the reason for the exception. The last delete operation shows the object being deleted when the exception was raised.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-05003: The object [{0}] cannot be deleted because it has changed or been deleted since it was last read. {3}Class> {1} Primary Key> {2}**

**Cause:** The object state has changed in the database. The object object cannot be deleted because it has changed or been deleted since it was last read. This usually means that the row in the table was changed by some other application.

**Action:** Refresh the object, which updates it with the new data from the database.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**TOP-05004: An attempt was made to update the object [{0}], but it has no version number in the identity map. {3}It may not have been read before the update was attempted. {3}Class> {1} Primary Key> {2}**

**Cause:** An attempt has been made to update the object object that does not have a version number in the identity map. It may not have been read before being updated, or it has been deleted.

**Action:** Use SQL logging to determine the reason for the exception. The last update operation shows the object being updated when the exception was raised.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-05006: The object [{0}] cannot be updated because it has changed or been deleted since it was last read. {3}Class> {1} Primary Key> {2}**

**Cause:** The object state has changed in the database. The object object cannot be updated because it has changed or been deleted since it was last read. This usually means that the row in the table was changed by some other application.

**Action:** Refresh the object, which updates it with the new data from the database.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-05007: The object [{0}] must have a non-read-only mapping to the version lock field.**

**Cause:** The object object does not have a non-read-only mapping corresponding to the version lock field. The mapping, which is needed when the lock value is stored in the domain object rather than in a cache, was not defined for the locking field.

**Action:** Define a mapping for the field.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-05008: Must map the version lock field to java.sql.Timestamp when using Timestamp Locking**

**Cause:** A write lock value that is stored in a domain object is not an instance of java.sql.Timestamp.

**Action:** Change the value of the attribute to be an instance of java.sql.Timestamp.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-05009: The object of class [{1}] with primary key [{0}] cannot be unwrapped because it was deleted since it was last read.**

---

**Cause:** Attempt to unwrapped an object of class className with primary key key-the object was deleted since it had been last read.

**Action:** Ensure the existence of the object being upwrapped.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06001: Cursored SQL queries must provide an additional query to retrieve the size of the result set.**

**Cause:** Additional size-retrieving query was not specified: cursored SQL queries must provide an additional query to retrieve the size of the result set. Failure to include the additional query causes this exception.

**Action:** Specify a size query.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-06002: Aggregated objects cannot be written/deleted/queried independently from their owners. {1}Descriptor: [{0}]**

**Cause:** An aggregated object was deleted independently of its owner: aggregate objects cannot be written or deleted independent of their owners. No identity is maintained on such objects.

**Action:** Do not try to delete aggregate objects directly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06003: The number of arguments provided to the query for execution does not match the number of arguments in the query definition.**

**Cause:** The number of arguments provided to the query for execution does not match the number of arguments provided with the query definition.

**Action:** Check the query and the query execution.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06004: The object [{0}], of class [{1}], with identity hashcode (System.identityHashCode()) [{2}], {3}is not from this UnitOfWork object space, but the parent session"s. The object was never registered in this UnitOfWork, {3}but read from the parent session and related to an object registered in the UnitOfWork. Ensure that you are correctly{3}registering your objects. If you are still having problems, you can use the UnitOfWork.validateObjectSpace() method to {3}help debug where the error occurred. For more information, see the manual or FAQ.**

**Cause:** The object clone of class clone.getClass() with identity hash code (System.identityHashCode()) (System.identityHashCode(clone)) is not from this unit of work space, but from the parent session. The object was never registered in

---

this unit of work, but read from the parent session and related to an object registered in the unit of work.

**Action:** Verify that you are correctly registering your objects. If you are still having problems, use the `validateObjectSpace` method of the `UnitOfWork` to help debug where the error occurred.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06005: The object [{0}], of class [{1}], with identity hashcode (System.identityHashCode()) [{2}], {3} is the original to a registered new object. The `UnitOfWork` clones registered new objects, so you must ensure that an object {3} is registered before it is referenced by another object. If you do not want the new object to be cloned, use the `{3}UnitOfWork.registerNewObject(Object)` API. If you are still having problems, you can use the `UnitOfWork.validateObjectSpace()` {3} method to help debug where the error occurred. For more information, see the manual or FAQ.**

**Cause:** The object clone of class `clone.getClass()` with identity hash code `(System.identityHashCode()) (System.identityHashCode(clone))` is the original to a registered new object. Because the unit of work clones new objects that are registered, ensure that an object is registered before it is referenced by another object. If you do not want the new object to be cloned, use the `registerNewObject(Object)` method of the `UnitOfWork`.

**Action:** Verify that you are correctly registering your objects. If you are still having problems, use the `validateObjectSpace` method of the `UnitOfWork` to help debug where the error occurred.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06006: The mapping [{0}] does not support batch reading.**

**Cause:** The mapping that does not support batch reading was used. The optimization of batch reading all the target rows is not supported for the mapping.

**Action:** The problem is a `TopLink` development problem, and you should never encounter this error code unless the mapping is a new custom mapping. Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06007: Missing descriptor for [{0}].**

**Cause:** The descriptor for the reference class is missing. The descriptor related to the class or the object is not found in the session.

**Action:** Verify whether or not the related descriptor was added to the session, and whether or not the query is performed on the right object or class.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**TOP-06008: Missing descriptor for [{0}] for query named [{1}].**

**Cause:** The descriptor DomainClassName for the query named queryName is missing. The descriptor where named query is defined is not added to the session.

**Action:** Verify whether or not the related descriptor was added to the session, and whether or not the query is performed on the right class.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-06013: Incorrect size query given to CursoredStream.**

**Cause:** The size query given on the queries returning cursor streams is not correct. The execution of the size query did not return any size.

**Action:** If the cursor stream query was a custom query, then check the size of the query that was specified, or report this problem to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-06014: Objects cannot be written during a UnitOfWork, they must be registered.**

**Cause:** Attempt to write an object in a unit of work using modify queries. These objects must be registered.

**Action:** Prior to modification, register objects in the unit of work, so during commit the unit of work can perform the required changes to the database.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06015: Invalid query key [{0}] in expression.**

**Cause:** The query key key does not exist. Usually this happens because of a misspelled query key.

**Action:** Check the query key that was specified in the expression and verify that a query key was added to the descriptor.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06016: Objects or the database cannot be changed through a ServerSession. All changes must be done through a ClientSession's UnitOfWork.**

**Cause:** Attempt to change an object or a database through the server session: all changes must be performed through a client session's unit of work. The objects cannot be changed on the server session by modifying queries. Objects are changed in the client sessions that are acquired from this server session.

**Action:** Use the client session's unit of work to change the object.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**TOP-06020: No concrete class indicated for the type in the row [{0}].**

**Cause:** No concrete class is indicated for the type in this row. The type indicator read from the database row has no entry in the type indicator hash table or if class extraction method was used, it did not return any concrete class type. The exception is raised when subclasses are being read.

**Action:** Check the class extraction method, if specified, or check the descriptor to verify all the type indicator values were specified.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-06021: Cursors are not supported for interface descriptors, or abstract class multiple table descriptors using expressions. Consider using custom SQL or multiple queries.**

**Cause:** No cursor support is provided for abstract class multiple table descriptors using expressions.

**Action:** Consider using custom SQL or multiple queries.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06023: The list of fields to insert into the table [{0}] is empty. You must define at least one mapping for this table.**

**Cause:** There are no fields to be inserted into the table. The fields to insert into the table table, are empty.

**Action:** Define at least one mapping for this table.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06024: Modify queries require an object to modify.**

**Cause:** An object to modify has not been specified for a modify query.

**Action:** Verify that the query contains an object before executing.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06026: Query named [{0}] is not defined. Domain class: [{1}]**

**Cause:** The query is not defined. When executing a query on the session, the parameter that takes the query is null.

**Action:** Verify that the query is passed properly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic



---

**TOP-06027: Query sent to a unactivated UnitOfWork.**

**Cause:** The unit of work has been released and is now inactive.

**Action:** The unit of work, once released, cannot be reused unless the commitAndResume method is called.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06028: An attempt to read beyond the end of stream occurred.**

**Cause:** Attempt to read from the cursor streams beyond its limits (beyond the end of the stream).

**Action:** Ensure that the stream is checked for an end of stream condition before attempting to retrieve more objects.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06029: A reference class must be provided.**

**Cause:** The reference class in the query is not specified: a reference class must be provided.

**Action:** Ensure that the query is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06030: Refreshing is not possible if caching is not enabled.**

**Cause:** Attempt to refresh while the caching is not set: the read queries that skip the cache to read objects cannot be used to refresh the objects. Refreshing is not possible without identity.

**Action:** Ensure that the query is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06031: size() is only supported on expression queries, unless a size query is given.**

**Cause:** TopLink did not find a size query. Size is supported only on expression queries unless a size query is given.

**Action:** The cursor streams on a custom query should also define a size query.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06032: The SQL statement has not been properly set.**

**Cause:** The SQL statement has not been properly set. The user should never encounter this error code unless queries have been customized.

---

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-06034: Invalid query item expression [{0}].**

**Cause:** TopLink is unable to validate a query item expression.

**Action:** Validate the expression being used.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06041: The selection object passed to a ReadObjectQuery was null.**

**Cause:** The selection object that was passed to a ReadObjectQuery (or refresh) was null.

**Action:** Check setSelectionObject method on read query.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06042: A session name must be specified for non-object-level queries. See the setSessionName(String) method.**

**Cause:** Data read and data modify queries are being executed without the session name. Only object-level queries can be directly executed by the session broker, unless the query is named.

**Action:** Specify the session name.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06043: ReportQueries without primary keys cannot use readObject(). {1}ReportQueryResult: [{0}].**

**Cause:** Attempt to read the object by a ReportQuery without a primary key: the report query result that was returned is without primary key values. An object from the result can be created only if primary keys were also read.

**Action:** See the documentation about retrievePrimaryKeys method on report query.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06044: The primary key read from the row [{0}] during the execution of the query was detected to be null. Primary keys must not contain null.**

**Cause:** The primary key that was read from the row databaseRow during the execution of the query was detected to be null: primary keys must not contain null.

---

**Action:** Check the query and the table on the database.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06045: The subclass [{0}], indicated in the row while building the object, has no descriptor defined for it.**

**Cause:** The subclass has no descriptor defined for it.

**Action:** Ensure the descriptor was added to the session, or check class extraction method.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06046: Cannot delete an object of a read-only class. The class [{0}] is declared as read-only in this UnitOfWork.**

**Cause:** Attempt to delete a read-only class.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06047: Invalid operator [{0}] in expression.**

**Cause:** The operator used in the expression is not valid.

**Action:** Check ExpressionOperator class to see a list of all the operators that are supported.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06048: Illegal use of getField() [{0}] in expression.**

**Cause:** Invalid use of getField method's data in the expression. This is a TopLink development exception that you should not encounter.

**Action:** Report this problem to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06049: Illegal use of getTable() [{0}] in expression.**

**Cause:** Invalid use of getTable method's data in the expression. This is a TopLink development exception that you should not encounter.

**Action:** Report this problem to Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**TOP-06050: ReportQuery result size mismatch. Expecting [{0}], but retrieved [{1}]**

**Cause:** The number of attributes requested does not match the attributes returned from the database in report query. This can happen as a result of a custom query on the report query.

**Action:** Check the custom query to ensure it is specified, or report the problem to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06051: Partial object queries are not allowed to maintain the cache or be edited. You must use dontMaintainCache().**

**Cause:** Attempt to cache a partial object: partial objects are never put in the cache. Partial object queries are not allowed to maintain the cache or to be edited. Use the dontMaintainCache method.

**Action:** Call the dontMaintainCache method before executing the query.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06052: An outer join (getAllowingNull or anyOfAllowingNone) is only valid for OneToOne, OneToMany, ManyToMany, AggregateCollection and DirectCollection Mappings, and cannot be used for the mapping [{0}].**

**Cause:** Invalid use of an outer join: an outer join (getAllowingNull method) is valid only for one-to-one mappings and cannot be used for the mapping.

**Action:** Do not attempt to use the getAllowingNull method for mappings other than one-to-one.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06054: Cannot add the object [{0}], of class [{1}], to container class [{2}] using policy [{3}].**

**Cause:** TopLink is unable to add an object to a container class using policy. This is TopLink development exception, and you should never encounter this problem unless a custom container policy has been written.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06055: The method invocation of the method [{0}] on the object [{1}], of class [{2}], triggered an exception.**

**Cause:** The invocation of a method on the object anObject threw a Java reflection exception while accessing the method.

**Action:** Inspect the internal exception, and refer to the Java documentation.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06056: Cannot create a clone of object [{0}], of class [{1}], using [{2}].**

**Cause:** Attempt to create a clone of the object anObject using policy. This is a TopLink development exception, and you should never encounter this problem unless a custom container policy has been written.

**Action:** Report this problem to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06057: The method [{0}] is not a valid method to call on object [{1}].**

**Cause:** Invalid call of the method methodName on object aReceiver. This is a TopLink development exception, and you should never encounter this problem unless a custom container policy has been written.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06058: The method [{0}] was not found in class [{1}].**

**Cause:** The method named methodName was not found in the class aClass. This exception is raised when looking for a clone method on the container class. The clone is needed to create clones of the container in unit of work.

**Action:** Define a clone method on the container class.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06059: The class [{0}] cannot be used as the container for the results of a query because it cannot be instantiated.**

**Cause:** Attempt to instantiate a class aClass as the container for the results of a query-this class cannot be instantiated as a container. The exception is a Java exception that is raised when a new interface container policy is being created using Java reflection. TopLink wraps only the Java exception.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06060: Could not use object [{0}] of type [{1}] as a key into [{2}] of type [{3}]. The key cannot be compared with the keys currently in the Map.**

**Cause:** Attempt to use the object anObject of type ObjectClass as a key into aContainer which is of type ContainerClass. The key cannot be compared with the

---

keys currently in the map. This raises a Java reflection exception while accessing the method. TopLink wraps only the Java exception.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06061: Cannot reflectively access the method [{0}] for object [{1}], of class [{2}].**

**Cause:** Attempt to reflectively access the method aMethod for object: anObject of type ObjectClass. This raises a Java reflection exception while accessing the method. TopLink wraps only the Java exception.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06062: The method [{0}], called reflectively on object [{1}], of class [{2}], triggered an exception.**

**Cause:** The method aMethod was called reflectively on objectClass and threw an exception. The method aMethod raises a Java reflection exception while accessing a method. TopLink wraps only the Java exception.

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06063: Invalid operation [{0}] on cursor.**

**Cause:** Invalid operation operationName on the cursor. The operation is not supported.

**Action:** Check the class documentation and look for the corresponding method to use.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06064: Cannot remove the object [{0}], of class [{1}], from container class [{2}] using policy [{3}].**

**Cause:** Attempt to remove anObject of type anObjectClass from aContainerClass using policy. This is a TopLink development exception and you should never encounter this problem unless a custom container policy has been written.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06065: Cannot add the object [{0}], of class [{1}], to container [{2}].**

---

**Cause:** Attempt to add an element to the collection container policy (cannot add object anObject of type ObjectClass to a ContainerClass).

**Action:** Inspect the internal exception, and refer to the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06066: The object [{0}], of class [{1}], with identity hashCode**

**(System.identityHashCode()) [{2}], {3} has been deleted, but still has references. Deleted objects cannot be referenced after being deleted. {3} Ensure that you are correctly registering your objects. If you are still having problems, you can use the UnitOfWork.validateObjectSpace() {3} method to help debug where the error occurred. For more information, see the manual or FAQ.**

**Cause:** Object references remained after the deletion of the object: the object clone of class clone.getClass with identity hash code (System.identityHashCode()) (System.identityHashCode(clone)) has been deleted, but it still has references.

**Action:** Ensure that you are correctly registering your objects. If you are still having problems, use the validateObjectSpace() method of the UnitOfWork to help identify where the error occurred.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06068: Cannot compare table reference to [{0}] in expression.**

**Cause:** Attempt to compare table reference to data in expression.

**Action:** Check the expression.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06069: The field [{0}] in this expression has an invalid table in this context.**

**Cause:** Field has invalid table in this context for field fieldName in expression.

**Action:** Check the expression.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06070: Invalid use of a query key [{0}] representing a "to-many" relationship in an expression. Use anyOf() rather than get().**

**Cause:** Invalid use of a query key representing a one-to-many relationship in expression.

**Action:** Use the anyOf operator instead of the get operator.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**TOP-06071: Invalid use of anyOf() for a query key [{0}] not representing a to-many relationship in an expression. Use get() rather than anyOf().**

**Cause:** Invalid use of anyOf for a query key not representing a to-many relationship in expression.

**Action:** Use the get operator instead of the anyOf operator.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06072: Querying across a VariableOneToOneMapping is not supported. {2}Descriptor: [{0}] {2}Mapping: [{1}]**

**Cause:** Attempt to query across a variable one-to-one mapping. This is not supported.

**Action:** Change the expression such that the query is not performed across a variable one-to-one mapping.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06073: Malformed expression in query. Attempting to print an object reference into an SQL statement for query key [{0}].**

**Cause:** Ill-formed expression in query that is attempting to print an object reference into a SQL statement for queryKey.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06074: This expression cannot determine if the object conforms in memory. You must set the query to check the database.**

**Cause:** Expression cannot determine if the object conforms in memory.

**Action:** Set the query to check the database; change the query such that it does not attempt to conform to the results of the query.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06075: Object comparisons can only use the equal() or notEqual() operators. Other comparisons must be done through query keys or direct attribute level comparisons. {1}Expression: [{0}]**

**Cause:** Invalid operator was used for the object comparison: object comparisons can use only the equal or notEqual operators; other comparisons must be performed through query keys or direct attribute level comparisons.

**Action:** Ensure the query uses only equal and notEqual if object comparisons are being used.

**Level:** 1



---

**Type:** ERROR

**Impact:** Programmatic

**TOP-06076: Object comparisons can only be used with OneToOneMappings. Other mapping comparisons must be done through query keys or direct attribute level comparisons.** {2}Mapping: [{0}] {2}Expression: [{1}]

**Cause:** Unsupported type of mapping was used for the object comparison: object comparisons can be used only with one-to-one mappings; other mapping comparisons must be performed through query keys or direct attribute level comparisons.

**Action:** Use a query key instead of attempting to compare objects across the mapping.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06077: Object comparisons cannot be used in parameter queries. You must build the expression dynamically.** {1}Expression: [{0}]

**Cause:** Object comparison was parameterized: object comparisons cannot be used in parameter queries.

**Action:** Change the query so that it does not attempt to use objects when using parameterized queries.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06078: The class of the argument for the object comparison is incorrect.** {3}Expression: [{0}] {3}Mapping: [{1}] {3}Argument: [{2}]

**Cause:** An incorrect class of the argument was used for the object comparison.

**Action:** Ensure the class for the query is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06079: Object comparison cannot be used for target foreign key relationships. Query on the source primary key instead.** {3}Expression: [{0}] {3}Mapping: [{1}] {3}Argument: [{2}]

**Cause:** Object comparison was used for target foreign key relationships: object comparisons cannot be used for target foreign key relationships

**Action:** Query on the source primary key.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06080: Invalid database call [{0}]. The call must be an instance of DatabaseCall.**

**Cause:** Invalid database call: the call must be an instance of DatabaseCall.

**Action:** Ensure the call being used is a DatabaseCall.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06081: Invalid database accessor [{0}]. The accessor must be an instance of DatabaseAccessor.**

**Cause:** Invalid database accessor: the accessor must be an instance of DatabaseAccessor.

**Action:** Ensure the accessor being used is a DatabaseAccessor.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06082: The method [{0}] with argument types [{1}] cannot be invoked on Expression.**

**Cause:** The nonexistent method methodName with argument type argTypes was invoked on an expression.

**Action:** Ensure the method being used is a supported method.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06083: Queries using in() cannot be parameterized. Disable either query preparation or binding.**

**Cause:** The query that was using IN was parameterized: queries using IN cannot be parameterized.

**Action:** Disable the query prepare or binding.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06084: The redirection query was not configured properly. The class or method name was not set.**

**Cause:** The redirection query was not configured properly: the class or method name was not set.

**Action:** Verify the configuration for the redirection class.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06085: The redirection query's method is not defined or defined with the wrong arguments. It must be declared "public static" and have arguments (DatabaseQuery, Record, Session) or (Session, Vector). {2}Class: [{0}] {2}Method: [{1}]**

**Cause:** The redirection query's method is not defined or it is defined with the wrong arguments. It must be public static and have the following arguments: DatabaseQuery, DatabaseRow, or Session (the interface).

---

**Action:** Check the redirection query's method.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06086: The redirection query's method invocation triggered an exception.**

**Cause:** The static invoke method provided to MethodBaseQueryRedirector threw an exception when invoked.

**Action:** Check the static invoke method for problems.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06087: The example object class [{0}] does not match the reference object class [{1}].**

**Cause:** There is a class mismatch between the example object and the reference class specified for this query.

**Action:** Ensure that the example and reference classes are compatible.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06088: There are no attributes for the ReportQuery.**

**Cause:** A ReportQuery has been built with no attributes specified.

**Action:** Specify the attribute for the query.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06089: The expression has not been initialized correctly. Only a single ExpressionBuilder should be used for a query. {1}For parallel expressions, the query class must be provided to the ExpressionBuilder constructor, and the query's ExpressionBuilder must {1}always be on the left side of the expression. {1}Expression: [{0}]**

**Cause:** The expression has not been initialized correctly. Only a single ExpressionBuilder should be used for a query. For parallel expressions, the query class must be provided to the ExpressionBuilder constructor, and the query's ExpressionBuilder must always be on the left side of the expression.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06090: Cannot set ReportQuery to "check cache only".**

---

**Cause:** The checkCacheOnly method was invoked on a ReportQuery. You cannot invoke the checkCacheOnly method on a ReportQuery, because a ReportQuery returns data rather than objects and the TopLink cache is built with objects.

**Action:** Do not use a ReportQuery in this case.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06091: The type of the constant [{0}], used for comparison in the expression, does not match the type of the attribute [{1}].**

**Cause:** The type of the constant used for comparison in the expression does not match the type of the attribute.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06092: Uninstantiated ValueHolder detected. You must instantiate the relevant Valueholders to perform this in-memory query.**

**Cause:** Uninstantiated value holders have been detected.

**Action:** Instantiate the value holders for the collection on which you want to query.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06094: The parameter name [{0}] in the query's selection criteria does not match any parameter name defined in the query.**

**Cause:** An unmapped field was used in a parameterized expression.

**Action:** Map the field or define an alternate expression that does not rely on the unmapped field.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06095: Public clone method is required.**

**Cause:** A delegate class of an IndirectContainer implementation does not implement Cloneable. If you implement IndirectContainer you must also implement Cloneable. For example, see oracle.toplink.indirection.IndirectSet. The clone method must clone the delegate. For example, the IndirectSet implementation uses reflection to invoke the clone method because it is not included in the common interface shared by IndirectSet and its base delegate class, HashSet.

**Action:** Ensure that your IndirectContainer implementation or its delegate class implements Cloneable.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**TOP-06096: Clone method is inaccessible.**

**Cause:** A delegate class of an IndirectContainer implementation implements Cloneable but the IndirectContainer implementation does not have access to the specified clone method. That is, a java.lang.IllegalAccessException is raised when the delegate's clone method is invoked.

**Action:** Ensure that both the delegate clone method and the delegate class are public. Ensure permission is set for Java reflection in your VM security settings. See also the invoke method of java.lang.reflect.Method.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06097: clone method threw an exception: {0}.**

**Cause:** A delegate class of an IndirectContainer implementation implements Cloneable and the IndirectContainer implementation has access to the specified clone method, but the specified clone method raises a java.lang.reflect.InvocationTargetException when invoked.

**Action:** Verify the implementation of the delegate's clone method.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06098: Unexpected Invocation Exception: {0}.**

**Cause:** A proxy object method raises an unexpected exception when invoked (that is, some exception other than InvocationTargetException and ValidationException.)

**Action:** Review the proxy object to see where it is throwing the exception described in the exception message. Ensure this exception is no longer raised.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06099: Joining across inheritance class with multiple table subclasses not supported: {0}, {1}**

**Cause:** Joining with query across inheritance class with multiple table subclasses. This is not supported: joining cannot be used on relationships with inheritance classes that have subclasses that span multiple tables as this requires multiple separate queries. The multiple queries cannot be joined into a single query.

**Action:** Use batch reading on the relationship instead, as this will provide equivalent or better performance.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06100: Multiple values detected for single-object read query.**

---

**Cause:** Multiple values detected for single-object read query. This is a CMP compliance option that ensures the finder methods for a single object only return a single row.

**Action:** Set the system property `toplink.cts.checkMultipleRows` to false, or ensure that the finder query only returns a single row from the database.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06101: Executing this query could violate the integrity of the global session cache which must contain only the latest versions of objects. In order to execute a query that returns objects as of a past time, try one of the following: Use a `HistoricalSession` (`acquireSessionAsOf`), all objects read will be cached and automatically read as of the same time. This will apply even to triggering object relationships. Set `shouldMaintainCache` to false. You may make any object expression as of a past time, provided none of its fields are represented in the result set (i.e. used only in the where clause).**

**Cause:** Executing this query could violate the integrity of the global session cache which must contain only the latest versions of objects.

**Action:** To execute a query that returns objects of a historical nature, you must do one of the following: Use a `HistoricalSession` (`acquireSessionAsOf`). All objects read will be cached and automatically read at that time. This applies also to triggering object relationships. Set `shouldMaintainCache` to false. You may make any object expression as of a previous time, provided none of its fields are represented in the result set (i.e. used in the where clause).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06102: At present historical queries only work with Oracle 9R2 or later databases, as it uses Oracle's Flashback feature.**

**Cause:** Invalid database was used: historical queries only work with Oracle 9.2.0.4 or later databases, as it uses the Oracle database Flashback feature.

**Action:** Ensure that historical queries are only used with an Oracle 9.2.0.4 or later database.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06103: You may not execute a `WriteQuery` from inside a read-only `HistoricalSession`. To restore past objects, try the following: read the same object as it is now with a `UnitOfWork` and commit the `UnitOfWork`.**

**Cause:** Invalid query was executed on a historical session: you may not execute a `WriteQuery` from inside a read-only `HistoricalSession`. To restore historical objects, try the following: read the same object as it is now with a `UnitOfWork` and commit the `UnitOfWork`.

**Action:** To restore historical objects, read the same object as it is now with a `UnitOfWork` and commit the `UnitOfWork`.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**TOP-06104: The object, {0}, does not exist in the cache.**

**Cause:** The object does not exist in the cache.

**Action:** Ensure that the object exists in the cache.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06105: Query has to be reinitialized with a cursor stream policy.**

**Cause:** The cursor stream policy was not used on the query instantiation.

**Action:** Reinitialize the query with a cursor stream policy.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06106: The object of type [{0}] with primary key [{1}] does not exist in the cache.**

**Cause:** The object with primary key does not exist in the cache.

**Action:** Ensure that the object exists in the cache.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06107: Missing update statements on UpdateAllQuery.**

**Cause:** Missing update statements on UpdateAllQuery.

**Action:** Add update statements using the addUpdate method.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06108: Update all query does not support inheritance with multiple tables**

**Cause:** For UpdateAllQuery, inheritance was used with multiple tables:

UpdateAllQuery does not support inheritance with multiple tables.

**Action:** Do not use UpdateAllQuery in this situation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06109: The named fetch group ({0}) is not defined at the dsriptor level.**

**Cause:** The named fetch group is not defined at the descriptor level.

**Action:** Ensure the fetch group is defined in the descriptor.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**TOP-06110: Read query cannot conform the unfetched attribute ({0}) of the partially fetched object in the unit of work identity map.**

**Cause:** Read query cannot conform to the unfetched attribute of the partially fetched object in the unit of work identity map.

**Action:** Do not use unfetched attribute conforming, or explicitly fetch the attribute before conforming.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06111: The fetch group attribute ({0}) is not defined or not mapped.**

**Cause:** The fetch group attribute is not defined or mapped.

**Action:** Ensure that any attribute defined in a fetch group is defined in the class and mapped.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06112: Fetch group cannot be set on report query.**

**Cause:** A fetch group was set on report query: fetch groups cannot be set on report queries.

**Action:** Remove the fetch group setting on ReportQuery, or use ReadObjectQuery or ReadObjectQuery instead.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06113: Fetch group cannot be used along with partial attribute reading.**

**Cause:** Fetch group was used together with partial attribute reading: fetch groups cannot be used together with partial attribute reading.

**Action:** Remove the partial attribute reading setting in the query.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06114: You must define a fetch group manager at descriptor ({0}) in order to set a fetch group on the query ({1})**

**Cause:** A fetch group manager is not defined at the descriptor while attempting to set a fetch group on a query.

**Action:** You must define a fetch group manager at the descriptor in order to set a fetch group on the query.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic



---

**TOP-06115: Queries on isolated classes, or queries set to use exclusive connections, must not be executed on a ServerSession or, in CMP, outside of a transaction.**

**Cause:** An isolated query was executed on a server session: queries on isolated classes, or queries set to use exclusive connections, must not be executed on a ServerSession or in CMP outside of a transaction.

**Action:** Do not execute queries on isolated classes or queries set to use exclusive connections on a ServerSession or in CMP outside of a transaction.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06116: No Call or Interaction was specified for the attempted operation.**

**Cause:** No call or interaction method was specified for the attempted operation.

**Action:** Specify a call or interaction method.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06117: Can not set a query, that uses a cursored result, to cache query results.**

**Cause:** A query that uses a cursored result to cache query results was set.

**Action:** Do not cache query results or do not use a cursor policy.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06118: A query on an Isolated class must not cache query results on the query.**

**Cause:** Query on an isolated class attempted to cache query results on the query.

**Action:** Do not cache query results for a query on an isolated class.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06119: The join expression {0} is not valid, or for a mapping type that does not support joining.**

**Cause:** The join expression is not valid, or is for a mapping type that does not support joining.

**Action:** Joining is supported only for one-one and one-many mappings.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06120: The partial attribute {0} is not a valid attribute of the class {1}.**

**Cause:** The partial attribute attributeName is not a valid attribute of the class className.

**Action:** Ensure that this attribute exists, and is mapped.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06121: The query has not been defined correctly, the expression builder is missing. For sub and parallel queries ensure the queries builder is always on the left.**

**Cause:** The query has not been defined correctly: the expression builder is missing.

**Action:** Ensure the queries builder is always on the left for sub queries and parallel queries.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06122: The expression is not a valid expression. {0}**

**Cause:** Attempt to use an invalid expression expression.

**Action:** Ensure the correctness of the expression.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06123: The container class specified [{0}] cannot be used because the container needs to implement {1}.**

**Cause:** Invalid container class specified: the container class className cannot be used, because the container needs to implement interfaceName.

**Action:** Ensure that the class specified as a container implements the correct interface.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06124: Required query of {0}, found {1}**

**Cause:** TopLink was expecting to find the query queryName, but instead found an incorrect query queryName.

**Action:** Provide the correct query.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06125: ReadQuery.clearQueryResults() can no longer be called. The call to clearQueryResults now requires that the session be provided. clearQueryResults(session) should be called.**

**Cause:** The ReadQuery method clearQueryResults() was called: this method cannot be called anymore. The call to the clearQueryResults method now requires that the session be provided.

**Action:** Call the ReadQuery method clearQueryResults(session).

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06126: A query is being executed that uses both conforming and cached query results. These two settings are incompatible.**

**Cause:** A query is being executed that uses both conforming and cached query results. These two settings are incompatible.

**Action:** Ensure that the query uses either conforming or cached query results.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06127: A reflective call failed on the TopLink class {0}, your environment must be set up to allow Java reflection.**

**Cause:** A reflective call failed on the TopLink class className.

**Action:** Set up your environment to allow Java reflection

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06128: Batch Reading is not supported on Queries using custom Calls.**

**Cause:** Attempt to use batch reading on a query using a custom call: batch reading is not supported on queries using custom calls.

**Action:** Do not use batch reading on queries using custom calls.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-06129: Refreshing is not possible if the query does not go to the database.**

**Cause:** Attempt to refreshing the query that does not go to the database. This is not possible.

**Action:** Avoid refreshing queries that do not go to the database.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-07001: You must login to the ServerSession before acquiring ClientSessions.**

**Cause:** Attempt to allocate client sessions before logging in to the server.

**Action:** Ensure you have called login method on your server session or database session. This error also appears in multi-threaded environments as a result of concurrency issues. Check that all your threads are synchronized.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**TOP-07002: The pool named [{0}] does not exist.**

**Cause:** The pool name used while acquiring client session from the server session does not exist.

**Action:** Verify the pool name given while acquiring client session and all the existing pools on the server session.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07003: Max size must be greater than min size.**

**Cause:** The maximum number of connections in a connection pool is less than the minimum number of connections. The connection pool size must be greater than the minimum number of connections.

**Action:** Check addConnectionPool(String poolName, JDBCLogin login, int minNumberOfConnections, int maxNumberOfConnections) method on the server session.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07004: Pools must be configured before login.**

**Cause:** Attempt to add connection pools after logging in to the server session: pools must all be added before login on the server session has been done. Once logged in, you cannot add pools.

**Action:** Check addConnectionPool(String poolName, JDBCLogin login, int minNumberOfConnections, int maxNumberOfConnections) on server session. This method should be called before logging in on the server session.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07008: The Java type [{0}] is not a valid database type.**

**Cause:** The Java type javaClass is not a valid database type. The Java type of the field to be written to the database has no corresponding type on the database.

**Action:** Check the table or stored procedure definition.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07009: Missing descriptor for [{0}]. Verify that the descriptor has been properly registered with the Session.**

**Cause:** The descriptor className is not found in the session.

**Action:** Ensure that the related descriptor to the class was properly registered with the session.

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**TOP-07010: Start index is out of range.**

**Cause:** This is a TopLink development exception and you should never encounter this problem. It happens when a copy of a vector is created with a start and end index.

**Action:** Report this problem to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07011: Stop index is out of range.**

**Cause:** This is a TopLink development exception and you should never encounter this problem. It happens when a copy of a vector is created with a start and end index.

**Action:** Report this problem to Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07012: Fatal error occurred.**

**Cause:** This is a TopLink development exception and you should never encounter this problem. It happens when test cases are executed.

**Action:** Report this problem to Oracle Support Services. This error commonly occurs if you attempt to call the commit method on an invalid (or previously committed) unit of work. If cannotCommitUOWAgain method of ValidationException appears in the stack trace, verify that the commit method was called on valid UnitOfWork instances.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07013: You are using the deprecated SessionManager API and no TOPLink.properties file could be found in your classpath. No sessions could be read in from file.**

**Cause:** The toplink.properties file cannot be found on the system classpath.

**Action:** Ensure that there is a toplink.properties file located on the system classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07017: Child descriptors do not have an identity map, they share their parent's**

**Cause:** An identity map is added to the child descriptor. A child descriptor shares its parent's identity map.

**Action:** Check the child descriptor and remove the identity map from it.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**TOP-07018: File error.**

**Cause:** You should never encounter this problem. It happens when test cases are executed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07023: Incorrect login instance provided. A DatabaseLogin must be provided.**

**Cause:** The login instance provided to the login method is incorrect. A JDBCLogin must be provided.

**Action:** Use a JDBCLogin.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07024: Invalid merge policy.**

**Cause:** This is a TopLink development exception and you should never encounter it.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07025: The only valid keys for DatabaseRows are Strings and DatabaseFields.**

**Cause:** The key on the database row is not either of type String or of type DatabaseField.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07027: The sequence named [{0}] is setup incorrectly. Its increment does not match its pre-allocation size.**

**Cause:** The sequence sequenceName is set up incorrectly: increment does not match preallocation size.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07028: writeObject() is not allowed within a UnitOfWork.**

**Cause:** Attempt to use writeObject() method in a UnitOfWork.

---

**Action:** Ensure that a writeObject() method is not in the UnitOfWork.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07030: You cannot set read pool size after login.**

**Cause:** Attempt to set read pool size after the server session has already been logged in.

**Action:** Set the pool size before login.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07031: You cannot add descriptors to a SessionBroker.**

**Cause:** Attempt to add a descriptor directly to a session broker.

**Action:** Descriptors are added to the sessions contained in the session broker.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07032: There is no session registered for the class [{0}].**

**Cause:** The descriptor related to the domain class domainClass was not found in any of the sessions registered in the session broker.

**Action:** Check the sessions.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07033: There is no session registered with the name [{0}].**

**Cause:** A session sessionName is not registered in the session broker.

**Action:** Check the session broker.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07038: Error while logging message to Session log.**

**Cause:** Error while logging message to session's log.

**Action:** Check the internal exception.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07039: Cannot remove from the set of read-only classes in a nested UnitOfWork. {0}A nested UnitOfWork's set of read-only classes must be equal to or a superset of its parent's set of read-only classes.**

---

**Cause:** Attempt to remove from the set of read-only classes in a nested unit of work. A nested unit of work's set of read-only classes must be equal to or be a superset of its parent's set of read-only classes.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07040: Cannot change the set of read-only classes in a UnitOfWork after that UnitOfWork has been used. {0}Changes to the read-only set must be made when acquiring the UnitOfWork or immediately after.**

**Cause:** Attempt to change the set of read-only classes in a unit of work after that unit of work has been used. Changes to the read-only set must be made when acquiring the unit of work or immediately after.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07042: Database platform class [{0}] not found.**

**Cause:** The platform class className was not found and a reflection exception is raised.

**Action:** Check the internal exception.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07043: [{0}] does not have any tables to create on the database.**

**Cause:** A project project does not have any tables to create on the database.

**Action:** Validate the project and tables you are attempting to create.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07044: The container class specified [{0}] cannot be used as a container because it does not implement Collection or Map.**

**Cause:** Illegal attempt to use the class className as the container-this class does not implement the Collection or Map interfaces.

**Action:** Implement either the Collection or Map interfaces in the container class.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07047: The container specified [{0}] does not require keys. You tried to use the method [{1}].**



---

**Cause:** Invalid Map class was specified for the container policy. The container specified (of Class aPolicyContainerClass) does not require keys. You tried to use the method methodName.

**Action:** Use map class that implements the Map interface.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07048: Neither the instance method or field named [{0}] exists for the item class [{1}], and therefore cannot be used to create a key for the Map.**

**Cause:** The key method on the map container policy is not defined. The instance method methodName does not exist in the reference class className and therefore cannot be used to create a key in a map. A map container policy represents the way to handle an indexed collection of objects. Usually the key is the primary key of the objects stored, so the policy needs to know the name of the primary key getter method in order to extract it from each object using reflection. For instance, a user might call policy.setKeyMethodName("getId").

**Action:** Check the second parameter of the useMapClass method of DatabaseQuery.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07051: Missing attribute [{1}] for descriptor [{0}], called from [{2}]**

**Cause:** Missing attribute attributeName for descriptor descriptor called from methodName. This is a TopLink development exception, and you should never encounter it.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07052: An attempt was made to use [{0}] (with the key method [{1}]) as a container for a DirectCollectionMapping [{0}]. The useMapClass() method cannot be used, only the useCollectionClass() API is supported for DirectCollectionMappings.**

**Cause:** The method useMapClass was called on a DirectCollectionMapping. It is invalid to call the useMapClass method on a DirectCollectionMapping. TopLink cannot instantiate Java attributes mapped using a DirectCollectionMapping with a map. The useMapClass method is supported for OneToManyMapping and ManyToManyMapping. The Java 2 Collection interface is supported using the useCollectionClass method.

**Action:** Use the useCollectionClass method. Do not call the useMapClass method on DirectCollectionMapping.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

- 
- TOP-07053: release() attempted on a Session that is not a ClientSession. Only ClientSessions may be released.**  
**Cause:** TopLink is unable to release a session that is not a client session. Only client sessions can be released.  
**Action:** Modify the code to ensure the client session is not released.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration
- TOP-07054: acquire() attempted on a Session that is not a ServerSession. ClientSessions may only be acquired from ServerSessions.**  
**Cause:** TopLink is unable to acquire a session that is not a client session. Client sessions can be acquired only from server sessions.  
**Action:** Modify the code to ensure an acquire session is attempted only from server sessions.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration
- TOP-07055: Optimistic Locking is not supported with stored procedure generation.**  
**Cause:** Attempt to use optimistic locking with stored procedure generation. This is not supported.  
**Action:** Do not use optimistic locking with stored procedure generation.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration
- TOP-07056: The wrong object was registered into the UnitOfWork. The object [{0}] should be the object from the parent cache [{1}].**  
**Cause:** The wrong object was registered into the unit of work. It should be the object from the parent cache.  
**Action:** Ensure that the object is from the parent cache.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration
- TOP-07058: Invalid Connector [{0}] (must be of type DefaultConnector).**  
**Cause:** The connector selected is invalid and must be of type DefaultConnector.  
**Action:** Ensure that the connector is of type DefaultConnector.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration
- TOP-07059: Invalid data source name [{0}].**  
**Cause:** Invalid data source name dsName.  
**Action:** Verify the data source name.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07060: Cannot acquire data source [{0}].**

**Cause:** TopLink is unable to acquire the data source with the name dsName, or an error has occurred in setting up the data source.

**Action:** Verify the data source name. Check the nested SQL exception to determine the cause of the error. Typical problems include: The connection pool was not configured in your config.xml file. The driver is not on the classpath. The user or password is incorrect. The database server URL or driver name is not properly specified.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07061: Exception occurred within JTS.**

**Cause:** An exception occurred within the Java Transaction Service (JTS).

**Action:** Examine the JTS exception and see the JTS documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07062: Field-level locking is not supported outside of a UnitOfWork. To use field-level locking, a UnitOfWork must be used for ALL writing.**

**Cause:** Attempt to use FieldLevelLocking outside a unit of work. This is not supported. In order to use field-level locking, a unit of work must be used for all write operations.

**Action:** Use a unit of work for writing.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07063: Exception occurred within EJB container.**

**Cause:** An exception occurred within the EJB container.

**Action:** Examine the EJB exception and see the JTS documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07064: Exception occurred in reflective EJB primary key extraction. Please ensure your primary key object is defined correctly. {2}Key: [{0}] {2}Bean: [{1}]**

**Cause:** An exception occurred in the reflective enterprise bean primary key extraction.

**Action:** Ensure that your primary key object is defined correctly.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**TOP-07065: The remote class for the bean cannot be loaded or found. Ensure that the correct class loader is set. {2}Bean: [{0}] {2}Remote Class: [{1}]**

**Cause:** The remote class for the bean cannot be loaded or found.

**Action:** Ensure that the correct class loader is set properly.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07066: Cannot create or remove beans unless a JTS transaction is present.**

**{1}Bean: [{0}]**

**Cause:** Attempt to create or remove an enterprise bean outside of a transaction: TopLink is unable to create or remove enterprise beans unless a JTS transaction is present, bean=bean.

**Action:** Ensure that the JTS transaction is present.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07068: The project class [{0}] was not found for the project [{1}] using the default class loader.**

**Cause:** The platform class platformName was not found for the project projectName using the default class loader.

**Action:** Validate the project and platform.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07069: An exception occurred looking up or invoking the project amendment method, "{0}" on the class "{1}".**

**Cause:** An exception occurred while looking up or invoking the project amendment method amendmentMethod on the class amendmentClass.

**Action:** Validate the amendment method and class.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07070: A TOPLink.properties resource bundle must be located on the CLASSPATH in a TopLink directory.**

**Cause:** Attempt to load toplink.properties resource bundle outside the classpath: the resource bundle must be located on the classpath in a TopLink directory.

**Action:** Validate the classpath and the location of the TopLink resource bundle.

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**TOP-07071: Cannot use input/output parameters without using binding.**

**Cause:** Attempt to use input or output parameters without using binding.

**Action:** Use binding on the StoredProcedureCall.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07072: The database platform class [{0}] was not found for the project [{1}] using the default class loader.**

**Cause:** SessionManager failed to load the class identified by the value associated with properties platform-class or external-transaction-controller-class during initialization when it loads the TopLink session common properties from the TopLink global properties file (sessions.xml for non-EJB applications, or toplink-ejb-jar.xml for EJB applications).

**Action:** Ensure that your TopLink global properties file is correctly configured. Pay particular attention to the platform-class and external-transaction-controller-class properties.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07073: The Oracle object type with type name [{0}] is not defined.**

**Cause:** The Oracle object type with type name typeName is not defined.

**Action:** Ensure that the Oracle object type is defined.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07074: The Oracle object type name [{0}] is not defined.**

**Cause:** The Oracle object type typeName is not defined.

**Action:** Ensure that the Oracle object type is defined.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07075: Maximum size is not defined for the Oracle VARRAY type [{0}]. A maximum size must be defined.**

**Cause:** The Oracle VARRAY type typeName maximum size is not defined.

**Action:** Verify the maximum size for the Oracle VARRAY.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07076: When generating the project class, the project's descriptors must not be initialized. {1}Descriptor: [{0}]**

---

**Cause:** Attempt to generate a project class while descriptors have already been initialized: when generating the project class, the descriptors must not be initialized.

**Action:** Ensure that the descriptors are not initialized before generating the project class.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07077: The home interface [{0}], specified during creation of the BMPWrapperPolicy, does not contain a correct findByPrimaryKey() method. A findByPrimaryKey() method must exist that takes the PrimaryKey class for this bean.**

**Cause:** The home interface toString method specified during creation of BMPWrapperPolicy does not contain a correct findByPrimaryKey method. A findByPrimaryKey method must exist that takes the PrimaryKey class for this bean.

**Action:** Ensure that a findByPrimaryKey method exists and is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07078: The "sessionName" [{0}], specified on the deployment descriptor for [{1}], does not match any session specified in the TopLink properties file.**

**Cause:** The sessionName specified on the deployment descriptor does not match any session specified in the toplink.properties file.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07079: The descriptor for [{0}] was not found in the session [{1}]. Check the project being used for this session.**

**Cause:** The descriptor was not found in the session.

**Action:** Check the project being used for this session.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07080: A FinderException was thrown when trying to load [{0}], of class [{1}], with primary key [{2}].**

**Cause:** A FinderException is raised when attempting to load an object from the class with the primary key.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**TOP-07081: The aggregate object [{0}] cannot be directly registered in the UnitOfWork. It must be associated with the source (owner) object.**

**Cause:** Attempt to register an aggregate object directly in the unit of work. This is not supported. The aggregate object must be associated with the source (owner) object.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07082: The TopLink properties file [{0}] specified multiple project files for the server named [{1}]. Please specify one of [projectClass], [projectFile], or [xmlProjectFile].**

**Cause:** The toplink.properties file specified multiple project files for the server. Only one project file can be specified.

**Action:** Specify either projectClass, projectFile, or xmlProjectFile.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07083: The TopLink properties file [{0}] did not include any information on the TopLink project to use for the server named [{1}]. Please specify one of [projectClass], [projectFile], or [xmlProjectFile].**

**Cause:** The toplink.properties file does not include any information on the TopLink project to use for the server. One project file must be specified.

**Action:** Specify either projectClass, projectFile, or xmlProjectFile.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07084: The file [{0}] is not a valid type for reading. ProjectReader must be given the deployed XML Project file.**

**Cause:** The specified file is not a valid type for reading. ProjectReader must be given the deployed XML project file.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07085: At least one sub session need to be defined in the TopLink session broker {0}**

**Cause:** TopLink is unable to create an instance of the external transaction controller specified in the properties file.

**Action:** Contact Oracle Support Services.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**TOP-07086: The session type "{0}" of the session name "{1}" was not defined properly.**

**Cause:** The session manager cannot load the class corresponding to the session's type class name.

**Action:** Ensure that the class name of the session's type is fully qualified in the sessions.xml file or toplink.properties file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07087: The session type "{0}" was not found for the "{1}" using default class loader.**

**Cause:** The session manager cannot load the class corresponding to the session's type class name.

**Action:** Ensure that the class name of the session's type is fully qualified in the sessions.xml file or toplink.properties file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07088: Cannot create an instance of the external transaction controller [{0}], specified in the properties file.**

**Cause:** The session manager cannot load the class corresponding to the external transaction controller's class name.

**Action:** Ensure that the class name of the external transaction controller is valid and fully qualified in the sessions.xml file or toplink.properties file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07089: An exception occurred looking up or invoking the session amendment method [{0}] on the class [{1}] with parameters [{2}].**

**Cause:** The session manager cannot load the class corresponding to the amendment class name, or it cannot load the method on the amendment class corresponding to the amendment method name.

**Action:** Ensure that the class name of the amendment class is fully qualified, and the amendment method exists in the amendment class in the sessions.xml file or toplink.properties file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07091: Cannot set listener classes!**

**Cause:** TopLink is unable to create the listener class that implements SessionEventListener for the internal use of SessionXMLProject.



---

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07092: Cannot add a query whose types conflict with an existing query. Query To Be Added: [{0}] is named: [{1}] with arguments [{2}]. The existing conflicting query: [{3}] is named: [{4}] with arguments: [{5}].**

**Cause:** TopLink has detected a conflict between a custom query with the same name and arguments to a session.

**Action:** Ensure that no query is added to the session more than once or change the query name so that the query can be distinguished from others.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07093: In the query named [{0}], the class [{2}] for query argument named [{1}] cannot be found. Please include the missing class on your classpath.**

**Cause:** TopLink is unable to create an instance of the query argument type.

**Action:** Ensure that the argument type is a fully qualified class name and the argument class is included in the classpath environment.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07095: The sessions.xml resource [{0}] was not found on the resource path.**

**Check that the resource name/path and classloader passed to the SessionManager.getSession are correct. The sessions.xml should be included in the root of the application's deployed jar, if the sessions.xml is deployed in a sub-directory in the application's jar ensure that the correct resource path using "/" not "\" is used.**

**Cause:** The sessions.xml or toplink.properties file cannot be loaded.

**Action:** Ensure that the path to either of the files exists on the classpath environment. The sessions.xml should be included in the root of the deployed JAR file. When using a WAR file, the sessions.xml file should be located in the WEB-INF/classes directory. When using EJB 3.0, TopLink automatically loads the ejb3-toplink-sessions.xml file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07096: Cannot use commit() method to commit UnitOfWork again.**

**Cause:** TopLink cannot invoke commit method on an inactive unit of work that was committed or released.

**Action:** Ensure you invoke commit method on a new unit of work or invoke commitAndResume method so that the unit of work can be reused. For more information about the commitAndResume method, see Oracle TopLink API Reference.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07097: Operation not supported:** [{0}].

**Cause:** TopLink cannot invoke an unsupported operation on an object.

**Action:** Do not use the operation indicated in the stack trace.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07099: The deployment project xml resource** [{0}] **was not found on the resource path. Check that the resource name/path and classloader passed to the XMLProjectReader are correct. The project xml should be included in the root of the application's deployed jar, if the project xml is deployed in a sub-directory in the application's jar ensure that the correct resource path using "/" not "\" is used.**

**Cause:** The file name specified for the XML-based project is incorrect.

**Action:** Verify the name and location of the file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07101: No "meta-inf/toplink-ejb-jar.xml" could be found in your classpath. The CMP session could not be read in from file.**

**Cause:** The toplink-ejb-jar.xml file was not found.

**Action:** Ensure that the file is on your classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07102: Encountered a null value for a cache key while attempting to remove**{2}**an object from the identity map:** [{0}]{2}**containing an object of class:** [{1}] **(or a class in this hierarchy)**{2}**The most likely cause of this situation is that the object has already been garbage-**{2}**collected and therefore does not exist within the identity map.**{2}**Please consider using an alternative identity map to prevent this situation.**{2}**For more details regarding identity maps, please refer to the TopLink documentation.**

**Cause:** Encountered a null value for a cache key while attempting to remove an object from the identity map. The most likely cause of this situation is that the object has already been garbage-collected and therefore does not exist within the identity map.

**Action:** Ignore. The removeFromIdentityMap method of the Session is intended to allow garbage collection, which has already been done.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**TOP-07103: A null reference was encountered while attempting to invoke{1}method: [{0}] on an object which uses proxy indirection.{1}Please check that this object is not null before invoking its methods.**

**Cause:** A null reference was encountered while attempting to invoke a method on an object that uses proxy indirection.

**Action:** Check that this object is not null before invoking its methods.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07104: Sequencing login should not use External Transaction Controller.**

**Cause:** A separate connection(s) for sequencing was requested, but the sequencing login uses the external transaction controller.

**Action:** Either provide a sequencing login that does not use an external transaction controller or do not use separate connection(s) for sequencing.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07105: Error encountered converting encryptiong class: [{0}]**

**Cause:** Error encountered while converting encryption class.

**Action:** Ensure the encryption class name is correctly specified in the sessions.xml file and that the encryption class specified is available on the classpath. A common reason for this exception is the usage of JDK 1.3 and earlier versions. The TopLink JCE encryption mechanism requires JDK 1.4 and later (or JDK 1.3 configured with the JCE plug-in) to function properly.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07106: Error encountered during string encryption.**

**Cause:** Error encountered during password string encryption.

**Action:** An error is raised while trying to encrypt the password string. A common reason for this exception is the usage of JDK 1.3 and earlier versions. The TopLink JCE encryption mechanism requires JDK 1.4 and later (or JDK 1.3 configured with the JCE plug-in) to function properly.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07107: Error encountered during string decryption.**

**Cause:** Error encountered during password string decryption.

**Action:** An exception was raised while trying to decrypt the password string. A common reason for this exception is the usage of JDK 1.3 and earlier versions. The TopLink JCE encryption mechanism requires JDK 1.4 and later (or JDK 1.3 configured with the JCE plug-in) to function properly.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**TOP-07108: This operation is not supported for non-relational platforms.**

**Cause:** Attempt to use an operation that is not supported for nonrelational platforms.

**Action:** Do not use this operation on the current platform, or use a relational database platform.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07109: The login in the project used to create the session is null, it must be a valid login.**

**Cause:** The login in the project used to create the session is null meaning no login was specified for the TopLink project. The login used for the project must be a valid login.

**Action:** Add login information using TopLink Workbench or using Java code.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07110: At present HistoricalSession only works with Oracle 9R2 or later databases, as it uses Oracle's Flashback feature.**

**Cause:** Attempt to use a HistoricalSession with a non-Oracle database. At present, HistoricalSession only works with Oracle databases that have a Flashback feature (Oracle database 9.2.0.4 or later). Generic history support (see `oracle.toplink.history.HistoryPolicy`) works for any database. If a HistoryPolicy is incorrectly set, TopLink may be defaulting to using flashback instead. An `AsOfSCNClause` is implicitly flashback only.

**Action:** Ensure that the HistoryPolicy is set correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07111: You may not acquire a HistoricalSession from a UnitOfWork, another HistoricalSession, a ServerSession, or a ServerSessionBroker. You may acquire one from a regular session, a ClientSession, or a ClientSessionBroker.**

**Cause:** Invalid attempt to acquire a HistoricalSession: you may not acquire a HistoricalSession from a unit of work, another HistoricalSession, a ServerSession, or a ServerSessionBroker. You may acquire a HistoricalSession from a regular session, a ClientSession, or a ClientSessionBroker.

**Action:** To recover objects, read the objects in both a HistoricalSession and UnitOfWork, and call `mergeCloneWithReferences(historicalObject)` method on the UnitOfWork.

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**TOP-07112: You have specified that Toplink use the feature : {0}, but this feature is not available in the currently running JDK version :{1}.**

**Cause:** Attempt to use a TopLink feature that is not available in the current JDK version.

**Action:** You must use the version of the JDK that supports this feature.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07113: {0} does not support call with returning.**

**Cause:** Attempt to use an unsupported call with returning for a platform.

**Action:** Set stored procedures with output parameters in setInsertQuery, setInsertCall, setUpdateQuery, or setUpdateCall methods of the DescriptorQueryManager.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07114: Isolated Data is not currently supported within a Client Session Broker. Session named {0} contains descriptors representing isolated data.**

**Cause:** Attempt to use isolated data within a ClientSessionBroker: isolated data is not currently supported within a ClientSessionBroker. Session contains descriptors representing isolated data.

**Action:** Ensure that isolated data is not used.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07115: A Exclusive Connection cannot be used for ClientSession reads without isolated data. Please update the ConnectionPolicy, used, to remove ExclusiveConnection configuration or the project to set certain data to be exclusive.**

**Cause:** Attempt to use ExclusiveConnection for ClientSession reads without isolated data. This is not supported.

**Action:** You must update the ConnectionPolicy used to remove ExclusiveConnection configuration, or the project to set certain data to be exclusive.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07116: Invalid arguments are used. Please refer to public API of the calling method and use valid values for the arguments.**

**Cause:** Invalid arguments are used in the method.

**Action:** Refer to the public API of the calling method and use valid values for the arguments.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07117: There is an attempt to use more than one cursor in SQLCall {0}**

**Cause:** Attempt to use more than one cursor in a SQLCall.

**Action:** TopLink currently supports only one cursor per call.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07118: setCustomSQLArgumentType method was called on SQLCall {0}, but this call doesn't use custom SQL**

**Cause:** The setCustomSQLArgumentType method was invoked on SQLCall, but this method does not use custom SQL.

**Action:** Don't call this method on SQLCall that does not use custom SQL.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07119: Unprepared SQLCall {0} attempted translation**

**Cause:** Unprepared SQLCall attempted translation.

**Action:** SQLCall must be prepared before translation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07120: Parameter {0} in SQLCall {1} cannot be used as a cursor, because it is has parameter type other than OUT**

**Cause:** Attempt to use parameter in SQLCall as a cursor, but this parameter is of type other than OUT.

**Action:** Ensure that the parameter used as a cursor has parameter type OUT.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07121: {0} does not support stored functions**

**Cause:** Attempt to use stored functions for a platform that does not support stored functions.

**Action:** Do not define stored functions on this platform.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07122: The exclusive connection associated with the session is unavailable for the query on {0}**

---

**Cause:** The exclusive connection associated with the session is unavailable for the query on the object. Isolated objects with indirection read through an ExclusiveIsolatedClientSession must not have indirection triggered after the ExclusiveIsolatedClientSession has been released.

**Action:** Reread the objects through the current ExclusiveIsolatedClientSession.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07123: A successful writeChanges() has been called on this UnitOfWork. As the commit process has been started but not yet finalized, the only supported operations now are commit, commitAndResume, release, any non-object level query or SQLCall execution. The operation {0} is not allowed at this time.**

**Cause:** Attempt to perform an operation that is not allowed at this time: a successful writeChanges operation has been called on this UnitOfWork. As the commit process has been started, but not yet finalized, the only supported operations now are commit, commitAndResume, release, any nonobject level query, or SQLCall execution.

**Action:** Execute one of the supported operations to continue.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-07124: An unsuccessful writeChanges() has been called on this UnitOfWork. Given the danger that partial changes have been written to the datastore but not rolled back (if inside external transaction), the only supported operations now are release, global transaction rollback, any non-object level query or SQLCall execution. The operation {0} was attempted.**

**Cause:** Attempt to perform an operation that is not allowed at this time: an unsuccessful writeChanges operation has been called on this UnitOfWork. Given the possibility that partial changes have been written to the data store but not rolled back (if inside external transaction), the only supported operations now are release, global transaction rollback, any nonobject level query or SQLCall execution.

**Action:** Determine the cause of the original failure and retry in a new UnitOfWork.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-07125: Once the UnitOfWork has been committed and/or released, no further operation should be performed on it. The operation {0} was attempted on it.**

**Cause:** Attempt to perform an operation on an inactive unit of work: once the UnitOfWork has been committed and/or released, no further operation should be performed on it.

**Action:** Acquire a new UnitOfWork, or use the commitAndResume method instead of commit method in the future.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**TOP-07126: writeChanges cannot be called on a NestedUnitOfWork. A nested UnitOfWork never writes changes directly to the datastore, only the parent UnitOfWork does.**

**Cause:** Attempt to call a writeChanges method on a NestedUnitOfWork. This is not supported: a nested UnitOfWork never writes changes directly to the data store, only the parent UnitOfWork does.

**Action:** Call the commit method instead, and then the writeChanges method on the parent UnitOfWork.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-07127: You can only writes changes to the datastore once, just as you can only call commit once.**

**Cause:** Attempt to write changes to the data store more than once: you can only write changes to the data store once.

**Action:** You must either roll back the transaction, or call the commit method on this UnitOfWork and start a new transaction.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-07128: Session [{0}] is already logged in.**

**Cause:** Attempt to log in to a session more than once.

**Action:** Do not try to login again.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07129: The method's arguments cannot have null value.**

**Cause:** Attempt to use null values for arguments in a method that cannot have null values.

**Action:** Ensure that the method's arguments do not have a null value.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07130: Nested unit of work is not supported for attribute change tracking.**

**Cause:** Attempt to use a nested UnitOfWork with attribute change tracking. This is not supported.

**Action:** Do not use a nested UnitOfWork with attribute change tracking.

**Level:** 1

**Type:** ERROR



---

**Impact:** Configuration

**TOP-07131: {0} is the wrong type. The collection change event type has to be add or remove.**

**Cause:** The collection change event is of the wrong type. The collection change event type has to be added or removed.

**Action:** Ensure that the collection change event type used is defined in `CollectionChangeEvent`.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-07132: {0} is the wrong event class. Only `PropertyChangeEvent` and `CollectionChangeEvent` are supported.**

**Cause:** Wrong event class. Only `PropertyChangeEvent` and `CollectionChangeEvent` classes are supported.

**Action:** Ensure that the event class is either `PropertyChangeEvent` or `CollectionChangeEvent`.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-07133: Old commit is not supported for attribute change tracking.**

**Cause:** Attempt to use old commit for attribute change tracking. This is not supported.

**Action:** Do not try to use attribute change tracking with an old commit.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07134: Server platform {0} is read only after login.**

**Cause:** Attempt to make changes to the server platform after login: the server platform is read-only after login.

**Action:** Changes to the server platform must be made before login. You must either:  
CMP application: define a class that implements `oracle.toplink.ejb.cmp.DeploymentCustomization`, and customize its public `String beforeLoginCustomization(Session session)` method to change your server platform. Consult the documentation for defining a customization class in your `orion-ejb-jar.xml` file.  
Non-CMP/POJO application: define a subclass of `oracle.toplink.sessions.SessionEventAdapter`, and override the public `void preLogin(SessionEvent event)` method to change your server platform. The session is contained in the event. Consult the documentation for `sessions.xml` and using `SessionEventAdapter`.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**TOP-07135: You cannot commit and resume a unit of work containing any modify all queries**

**Cause:** Attempt to commit and resume a UnitOfWork containing an UpdateAllQuery. This is not supported.

**Action:** You must either commit and continue in a new UnitOfWork, or do not use UpdateAllQuery.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-07136: Nested unit of work is not supported for a modify all query**

**Cause:** Attempt to use a nested UnitOfWork for an UpdateAll query. This is not supported.

**Action:** Do not use a nested UnitOfWork for an UpdateAllQuery.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-07137: The object is partially fetched (using fetch group), the unfetched attribute ({0}) is not editable.**

**Cause:** Attempt to edit an unfetched attribute: the object is partially fetched (using fetch group), the unfetched attribute is not editable.

**Action:** Do not edit the unfetched attribute, or explicitly fetch the attribute before editing it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-07139: Modify all queries cannot be issued within a unit of work containing other write operations.**

**Cause:** Attempt to issue an UpdateAll query within a UnitOfWork containing other write operations.

**Action:** Do not use UpdateAllQuery within a UnitOfWork containing other write operations.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-07140: Sequence type {0} doesn't have method {1}.**

**Cause:** Sequence type does not have the method.

**Action:** Do not call this method on this type of sequence.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07144: {0}; platform {1} doesn't support {2}.**

---

**Cause:** Platform does not support sequence.

**Action:** Do not use this sequence type on this platform.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07145: {2} attempts to connect to sequence {0}, but it is already connected to {1}. Likely the two sessions share the DatasourcePlatform object**

**Cause:** Two attempts have been made to connect to sequence, but the sequence is already connected to a platform. Likely the two sessions share the DatasourcePlatform object.

**Action:** Ensure that the sequence is used by a single session only.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-07146: QuerySequence {1} doesn't have select query.**

**Cause:** QuerySequence does not have select query.

**Action:** Ensure that the sequence has a select query.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07147: Platform {0} cannot create platform default sequence - it doesn't override createPlatformDefaultSequence method**

**Cause:** Attempt to create platform default sequence by a platform that does not override the createPlatformDefaultSequence method.

**Action:** You must either override the createPlatformDefaultSequence method on the platform, or explicitly set default sequence by calling setDefaultSequence on DatasourceLogin.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07148: commitAndResume() cannot be used with a JTA/synchronized unit of work.**

**Cause:** Attempt to use commitAndResume() method with a JTA or a synchronized unit of work.

**Action:** Do not use commitAndResume() with a JTA or a synchronized unit of work.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**TOP-07149: The composite primary key attribute [{2}] of type [{4}] on entity class [{0}] should be of the same type as defined on its primary key class [{1}]. That is, it should be of type [{3}].**

**Cause:** Attempt to provide an invalid specification of the composite primary key: the names of the primary key fields or properties in the primary key class PKClassName and those of the entity bean class ClassName must correspond and their types must be the same.

**Action:** Ensure that the names of the primary key fields or properties in the primary key class PKClassName and those of the entity bean class ClassName correspond, and their types are the same.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07150: Invalid composite primary key specification. The names of the primary key fields or properties in the primary key class [{1}] and those of the entity bean class [{0}] must correspond and their types must be the same. Also, ensure that you have specified id elements for the corresponding attributes in XML and/or an @Id on the corresponding fields or properties of the entity class.**

**Cause:** Attempt to specify an invalid LAZY fetch type on an attribute attributeName within entity class ClassName.

**Action:** Provide the fetch type other than LAZY on an attribute attributeName within entity class ClassName.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07151: The type [{1}] for the attribute [{0}] on the entity class [{2}] is not a valid type for an enumerated mapping. The attribute must be defined as a Java enum.**

**Cause:** An invalid EJB 3.0 annotation annotation has been specified in the entity class ClassName on accessor method methodName. It is not supported.

**Action:** Specify a valid annotation on this accessor method.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07152: Table per class inheritance is not supported. Entity class [{0}].**

**Cause:** Table per class inheritance is not supported. Entity class ClassName.

**Action:** Use different approach.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07153: Mapping annotations cannot be applied to fields or properties that are transient or have a @Transient specified. [{0}] is in violation of this restriction.**

**Cause:** The descriptor named query query already exists. Named query names must be unique.

---

**Action:** Provide a unique name for the query.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07154: The attribute [{3}] in entity class [{2}] has a mappedBy value of [{1}] which does not exist in its owning entity class [{0}]. If the owning entity class is a @MappedSuperclass, this is invalid, and your attribute should reference the correct subclass.**

**Cause:** An annotation @AssociationTable was not found on either the owning mapping class ClassName, or nonowning mapping class DifferentClassName for the @ManyToMany annotation.

**Action:** Ensure that the annotation @AssociationTable exists.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07155: The type [{1}] for the attribute [{0}] on the entity class [{2}] is not a valid type for a serialized mapping. The attribute type must implement the Serializable interface.**

**Cause:** An annotation @AttributeOverride columns was not specified on a mapping mapping from entity class ClassName.

**Action:** Specify this annotation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07156: Unable to find the class named [{0}]. Ensure the class name/path is correct and available to the classloader.**

**Cause:** TopLink was unable to find the class ClassName. Ensure the class name/path is correct and available to the class loader.

**Action:** Ensure the class name and/or path is correct and available to the class loader.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07157: Entity class [{0}] must use a @JoinColumn instead of @Column to map its relationship attribute [{1}].**

**Cause:** Attempt to use an invalid @Column annotation by the entity class ClassName to map its relationship attribute attribute.

**Action:** Ensure the entity class ClassName uses a @JoinColumn attribute instead of a @Column attribute to map its relationship attribute attributeName.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**TOP-07158: Error encountered when building the @NamedQuery [{1}] from entity class [{0}].**

**Cause:** Error encountered when building the @NamedQuery annotation from entity class ClassName.

**Action:** Ensure the correctness of the annotation specification.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07159: The map key [{0}] on the entity class [{1}] could not be found for the mapping [{2}].**

**Cause:** Invalid use of an unnamed @NamedQuery annotation with the query string string by an entity class ClassName .

**Action:** Specify a name for @NamedQuery.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07160: @OneToMany for attribute name [{1}] in entity class [{0}] should not have @JoinColumn(s) specified. In the case where the @OneToMany is not mapped by another entity (that is, it is the owning side and is uni-directional), it should specify (optional through defaulting) a @JoinTable.**

**Cause:** @OneToMany annotation for attribute attributeName in entity class ClassName has both an @AssociationTable and @JoinColumn(s) annotations specified.

**Action:** Specify one annotation only: @AssociationTable or @JoinColumn(s).

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07161: Entity class [{0}] has no primary key specified. It should define either an @Id, @EmbeddedId or an @IdClass. If you have defined PK using any of these annotations then please make sure that you do not have mixed access-type (both fields and properties annotated) in your entity class hierarchy.**

**Cause:** Primary key annotation is not specified for the entity class ClassName.

**Action:** Define either an @Id, @EmbeddedId or an @IdClass annotation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07162: Entity class [{0}] has multiple @EmbeddedId's specified (on attributes [{1}] and [{2}]). Only one @EmbeddedId can be specified per entity.**

**Cause:** Multiple @EmbeddedId annotations are specified (on attributeName and differentAttributeName) for entity class ClassName.

**Action:** Specify only one @EmbeddedId annotation for this entity.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**TOP-07163: Entity class [{0}] has both an @EmbddeddedId (on attribute [{1}]) and an @Id (on attribute [{2}]. Both id types cannot be specified on the same entity.**

**Cause:** Entity class ClassName has both an @EmbddeddedId (on attribute attributeName) and an @Id (on attribute differentAttributeName).

**Action:** Specify only one ID type on this entity: either @EmbddeddedId or @Id.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07164: The type [{1}] for the attribute [{0}] on the entity class [{2}] is not a valid type for a lob mapping. For a lob of type BLOB, the attribute must be defined as a java.sql.Blob, byte[], Byte[] or a Serializable type. For a lob of type CLOB, the attribute must be defined as a java.sql.Clob, char[], Character[] or String type.**

**Cause:** Attribute attributeName in an entity class ClassName has an invalid type for a @Lob annotation of type BLOB.

**Action:** Define this attribute as a java.sql.Blob, byte[], Byte[] or a Serializable type.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07165: The type [{1}] for the attribute [{0}] on the entity class [{2}] is not a valid type for a temporal mapping. The attribute must be defined as java.util.Date or java.util.Calendar.**

**Cause:** Attribute attributeName in entity class ClassName has an invalid type for a @Lob annotation of type CLOB.

**Action:** Define this attribute as a java.sql.Clob, char[], Character[] or String type.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07166: A table generator that uses the reserved name [{0}] for its 'name' has been found in [{1}]. It cannot use this name since it is reserved for defaulting a sequence generator's 'sequence name'.**

**Cause:** Conflict between annotations @Annotation and @DifferentAnnotation.

**Action:** Ensure that these two annotations are not conflicting.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07167: A sequence generator that uses the reserved name [{0}] for its 'sequence name' has been found in [{1}]. It cannot use this name since it is reserved for defaulting a table generator's 'name'.**

**Cause:** Attempt to use a reserved annotation name AnnotationName by an entity class ClassName: cannot use this name, because it is reserved for name.

---

**Action:** Specify a different name for this annotation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07168: The attribute [{0}] of type [{1}] on the entity class [{2}] is not valid for a version property. The following types are supported: int, Integer, short, Short, long, Long, Timestamp.**

**Cause:** Attempt to specify a generator with type Type by an annotation @Annotation.

**Action:** Ensure that this annotation specifies a generator of a different type.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07169: Class [{0}] has two @GeneratedValues: for fields [{1}] and [{2}]. Only one is allowed.**

**Cause:** The callback method methodName on the entity listener ListenerClassName has an incorrect signature.

**Action:** Provide only one parameter of type Object for this method.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07172: Error encountered when instantiating the class [{0}].**

**Cause:** TopLink was unable to instantiate the entity listener using the @EntityListener annotation.

**Action:** Ensure that the annotation is correctly specified.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**TOP-07173: A property change event has been fired on a property with name [{1}] in [{0}]. However this property does not exist.**

**Cause:** Attempt to fire a property change event on a nonexistent property propertyName in a change event EventClassName.

**Action:** Ensure that this property exists.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-07174: The getter method [{1}] on entity class [{0}] does not have a corresponding setter method defined.**

**Cause:** The getter method methodName on an entity class ClassName does not have a corresponding setter method defined.

**Action:** Define a corresponding setter method.



---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07175: The mapping [{0}] does not support cascading version optimistic locking.**

**Cause:** Attempt to use the mapping MappingType that does not support cascading version optimistic locking.

**Action:** Use a different mapping.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07176: The mapping [{0}] does not support cascading version optimistic locking because it has a custom query.**

**Cause:** Attempt to use the mapping MappingType that does not support cascading version optimistic locking. This mapping has a custom query.

**Action:** Use a different mapping.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07177: The aggregate descriptor [{0}] has privately-owned mappings. Aggregate descriptors do not support cascading version optimistic locking.**

**Cause:** Attempt to use an aggregate descriptor DescriptorName that has privately-owned mappings: aggregate descriptors do not support cascading version optimistic locking.

**Action:** Use a different descriptor.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07178: OracleOCIPProxyConnector requires OracleOCICollectionPool datasource.**

**Cause:** Attempt to use invalid arguments in an entity callback method methodName on a OracleOCIPProxyConnector: it requires the OracleOCICollectionPool data source.

**Action:** Provide OracleOCIPProxyConnector with the OracleOCICollectionPool argument.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07179: OracleJDBC10\_1\_0\_2ProxyConnector requires datasource producing OracleConnections.**

**Cause:** Attempt to use invalid arguments in an entity callback method methodName on a OracleJDBC10\_1\_0\_2ProxyConnector.

---

**Action:** Provide OracleJDBC10\_1\_0\_2ProxyConnector with data source producing Oracle Connections.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07180: OracleJDBC10\_1\_0\_2ProxyConnector requires Oracle JDBC version 10.1.0.2 or higher so that OracleConnection declares openProxySession method.**

**Cause:** Attempt to use the OracleJDBC10\_1\_0\_2ProxyConnector with Oracle JDBC version 10.1.0.1 or earlier: OracleJDBC10\_1\_0\_2ProxyConnector requires Oracle JDBC version 10.1.0.2 or later.

**Action:** Provide OracleJDBC10\_1\_0\_2ProxyConnector with Oracle JDBC version 10.1.0.2 or later in order for the OracleConnection to declare the openProxySession method.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07181: OracleJDBC10\_1\_0\_2ProxyConnector requires "proxytype" property to be an int converted to String, for instance**

**Integer.toString(OracleConnection.PROXYTYPE\_USER\_NAME)**

**Cause:** Attempt to use an invalid type for the proxytype property on the OracleJDBC10\_1\_0\_2ProxyConnector: it requires the proxytype property to be an int converted to a String.

**Action:** On the OracleJDBC10\_1\_0\_2ProxyConnector, provide the proxytype property of type int converted to a String. For example, Integer.toString(OracleConnection.PROXYTYPE\_USER\_NAME).

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07182: EC - Could not find driver class [{0}]**

**Cause:** TopLink could not find the driver class.

**Action:** Ensure that the driver class exists and is on the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07183: Error closing persistence.xml file.**

**Cause:** TopLink cannot close persistence.xml file.

**Action:** If you modified the persistence.xml, ensure that this file is not read-only.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07184: [{0}] system property not specified. It must be set to a class that defines a "getContainerConfig()" method.**

---

**Cause:** The system property propertyName is not specified.

**Action:** Set this property to a class that defines a getContainerConfig() method.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07185: Cannot find class [{0}] specified in [{1}]**

**Cause:** TopLink cannot find class ClassName.

**Action:** Ensure that the class exists and is properly specified.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07186: Cannot invoke method [{0}] on class [{1}] specified in [{2}]**

**Cause:** TopLink cannot invoke method methodName on configuration class ClassName.

**Action:** Ensure that this method exists in this class.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07187: [{0}] should define a public static method [{1}] that has no parameters and returns Colleciton**

**Cause:** Class ClassName does not define a public static method methodName.

**Action:** In the class ClassName, define a public static method methodName that has no parameters and returns a Collection.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07188: Non-null class list is required.**

**Cause:** Class list is null.

**Action:** Provide a non-null class list.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07189: Cannot create temp classloader from current loader: [{0}]**

**Cause:** TopLink cannot create a temporary class loader from the current loader ClassLoaderName.

**Action:** Ensure the validity of the current class loader.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

---

**TOP-07190: [{0}] failed**

**Cause:** Failure in the execution of the methodName method.

**Action:** Ensure the correctness of the method.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-07191: The entity class [{0}] was not found using class loader [{1}].**

**Cause:** An entity class ClassName was not found using class loader ClassLoaderName.

**Action:** Ensure that the entity class exists and is on the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-07192: ClassFileTransformer [{0}] throws an exception when performing transform() on class [{1}].**

**Cause:** Class file transformer TransformerName threw an exception when performing transform() method on class ClassName.

**Action:** Ensure the correctness of the transform() method. Check the internal exception for details on the root cause of this exception

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-07193: Jar files in persistence XML are not supported in this version of TopLink.**

**Cause:** Attempt to use JAR files in the persistence.xml file: JAR files are not supported in this version of Toplink.

**Action:** Do not use JAR files.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**TOP-07194: Could not bind: [{0}] to: [{1}].**

**Cause:** Attempt to use an unsupported method setFlushMode().

**Action:** Do not use this method.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-07195: Exception configuring EntityManagerFactory.**

**Cause:** TopLink could not bind name to anotherName.

**Action:** Ensure the correct use of this binding.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**TOP-07196: [{0}] of type [{1}] cannot be casted to [{2}].**

**Cause:** Exception configuring EntityManagerFactory.

**Action:** Ensure the correct configuration of this factory class. Check the internal exception for details on the root cause of this exception

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07197: This operation is not supported for this class: [{0}], [{1}].**

**Cause:** TopLink could not calculate changes, because the primary key is set to null.

**Action:** Set the primary key to a non-null value.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-07198: Class: [{0}] was not found while converting from class names to classes.**

**Cause:** Attempt to cast an instance of class ClassName to AnotherClassName. This is an invalid cast.

**Action:** Provide a valid cast.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-07199: A primary table was not defined for entity {0} in the entity-mappings file: {1}. A primary table is required to process an entity relationship.**

**Cause:** An attribute attributeName in an entity class ClassName has a mappedBy value of value. This value does not exist in its owning entity class ClassName.

**Action:** If the owning entity class is an @EmbeddableSuperclass, this is invalid. Make your attribute reference the correct subclass.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-07200: The attribute [{1}] was not found on the embeddable class [{0}]. It is referenced in the @AttributeOverride for the @Embedded attribute [{3}] on class [{2}].**

**Cause:** Either name or referencedColumnName element is not specified: if there is more than one join column, both the name and the referencedColumnName elements must be specified in each @JoinColumn annotation.

**Action:** Ensure that both the name and the referencedColumnName elements are specified in each @JoinColumn annotation.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**TOP-08001: Syntax Recognition Problem parsing the query [{0}]. The parser returned the following [{1}].**

**Cause:** The TopLink EJB QL parser does not recognize a clause in the EJB QL string.

**Action:** Validate the EJB QL string.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-08002: General Problem parsing the query [{0}]. The parser returned the following [{1}].**

**Cause:** TopLink has encountered a problem while parsing the EJB QL string.

**Action:** Check the internal exception for details on the root cause of this exception.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-08003: The class [{0}] was not found. The parser returned the following [{1}].**

**Cause:** The class specified in the EJB QL string was not found.

**Action:** Ensure that the class is on the appropriate classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-08004: A parsing problem was encountered resolving the alias - [{0}].**

**Cause:** TopLink was unable to resolve the alias used in the EJB QL string.

**Action:** Validate the identifiers used in the EJB QL string.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-08005: A problem was encountered resolving the class name - The class [{0}] was not found.**

**Cause:** TopLink was unable to resolve the class for an alias. This means that the class specified cannot be found.

**Action:** Ensure that the class is specified properly and is on the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-08006: A problem was encountered resolving the class name - The descriptor for [{0}] was not found.**

---

**Cause:** The class specified in the query does not have a TopLink descriptor.

**Action:** Ensure that the class has been mapped and is specified correctly in the EJB QL string.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-08009: The expression [{0}] is currently not supported.**

**Cause:** An unsupported expression was used in the EJB QL.

**Action:** Change the query to use only supported expressions.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-08010: General Problem parsing the query [{0}].**

**Cause:** TopLink has encountered a problem while parsing the EJB QL string.

**Action:** Check the internal exception for details on the root cause of this exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-09000: Several [{0}] SessionLoaderExceptions were thrown:**

**Cause:** The session loader caught one or more XML parsing exceptions while loading session information. The specific XML exceptions follow.

**Action:** Verify your session configuration XML file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-09001: Unknown tag name: [{0}] in XML node: [{1}].**

**Cause:** An unknown tag was encountered in the specified XML node.

**Action:** Examine the specified XML node in your session configuration XML file. Ensure that you use only the tags defined for that node in the appropriate TopLink XSD. See the directory where you installed TopLink (for example, <ORACLE\_HOME>/toplink/config/xsds)

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-09002: Unable to load Project class [{0}].**

**Cause:** The specified class loader could not load a class with the name given by the project-name property.

**Action:** Verify the value of the project-name property and if correct, ensure that a class with that name is in your classpath.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-09003: Unable to process XML tag [{0}] with value [{1}].**

**Cause:** The session loader caught an exception while either parsing the value of the specified tag or calling the setter method associated with the specified tag.

**Action:** Verify the value shown for the specified tag.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-09004: The project-xml file [{0}] was not found on the classpath, nor on the filesystem.**

**Cause:** The session loader could not find the file identified by the project-xml tag on either the classpath or the file system.

**Action:** Verify the value of the project-xml tag and if correct, ensure that a project.xml file with that name exists in your classpath or file system.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-09005: An exception was thrown while loading the project-xml file [{0}].**

**Cause:** The session loader caught an exception while trying to load the file identified by the project-xml tag either because the file could not be found, or because the file could not be parsed.

**Action:** Verify the configuration of the project XML file and ensure that a project.xml file with that name specified by the project-xml tag exists in your classpath or file system.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-09006: A {0} was thrown while parsing the XML file. It occurs at line {1} and column {2} in the XML document.**

**Cause:** The session loader caught a SAX exception while trying to parse the XML at the given line and column of the specified XML file. TopLink 10g supports only UTF-8 encoding. The TopLink SAXParseException occurs if you attempt to read a non-UTF-8 formatted XML file.

**Action:** Verify that the XML is correctly formatted at the given line and column. Alternatively, ensure the Oracle parser is in your classpath and that it appears before any other XML parser.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-09007: An exception was thrown while parsing the XML file.**



---

**Cause:** The session loader caught an exception unrelated to XML parsing (for example, a premature end-of-file exception) while trying to parse the specified XML file.

**Action:** Verify the integrity of the XML file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-09008: Unexpected value [{0}] of tag [{1}].**

**Cause:** The value of an XML tag does not correspond to any known TopLink required values.

**Action:** Please verify the list of values for this tag.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-09009: Tag [{0}] has unknown attribute.**

**Cause:** There is an incorrect name value pair when processing transport properties for the XSD tag.

**Action:** Please verify that all properties have both the name and the value filled in, in the session configuration XML file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-09010: A {0} was thrown while parsing the XML file against the XML schema.**

**Cause:** An exception was raised while parsing the XML file against the XML schema.

**Action:** Examine the exception and take the appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-10001: Exception [EJB - {0}]: Exception creating bean of type [{1}].**

**Cause:** The PersistenceManager for the given application server failed to create and EJB bean (for example, a problem was encountered during the create process, such as a NullPointerException).

**Action:** Check the exception contained in the javax.ejb.CreateException for additional information.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10002: Exception [EJB - {0}]: Error removing primary key [{1}] for bean of type [{2}].**

---

**Cause:** The PersistenceManager for the given application server failed to remove an EJB bean (for example, a problem was encountered during the removal, such as a NullPointerException).

**Action:** Check the exception contained in the javax.ejb.RemoveException for additional information.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10003: Exception [EJB - {0}]: An EJB Exception has occurred in bean of type [{1}].**

**Cause:** An internal, unexpected exception was raised.

**Action:** See the exception message provided.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10004: Exception [EJB - {0}]: Cannot find bean of type [{1}] using finder: [{2}].**

**Cause:** An unexpected exception was encountered while executing the finder method.

**Action:** See the exception message provided.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10007: Exception [EJB - {0}]: Exception creating bean of type [{1}]. Bean already exists.**

**Cause:** The PersistenceManager for a given application server failed to create an EJB bean, because an EJB bean with the given primary key already exists.

**Action:** Verify the application logic to ensure the primary key is unique.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10008: Exception [EJB - {0}]: Cannot find bean of type [{1}] using finder [{2}]**

**Cause:** A scalar finder (one that returns a single object) was invoked on a home interface, and returned a null value.

**Action:** Verify the application logic to ensure the desired EJB bean exists.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10009: Exception [EJB - {0}]: Cannot find bean of type [{2}] using findByPrimaryKey with primary key [{1}].**

**Cause:** A finder method using the primary key indicated, returned a null value.

**Action:** Verify the application logic to ensure the desired EJB exists.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10010: Exception [EJB - {0}]: Exception creating bean of type [{1}]. Create cannot be invoked on this bean since it has been deployed as read only.**

**Cause:** An attempt was made to create an entity marked as read-only using session().getProject().setDefaultReadOnlyClasses (aVector). You cannot create a read-only entity.

**Action:** Read-only entities should be read from the database (not created by the home interface). Adjust the application to read the required entities beforehand.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10011: Exception [EJB - {0}]: Exception removing bean of type [{1}]. Remove cannot be invoked on this bean since it has been deployed as read only.**

**Cause:** An attempt was made to delete an entity marked as read-only using session().getProject().setDefaultReadOnlyClasses (aVector). You cannot delete a read-only entity.

**Action:** Determine whether or not the object should be read-only or not. If it should, do not try to remove it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10014: Exception [EJB - {0}]: Error in non-transactional write for bean of type [{1}].**

**Cause:** The PersistenceManager for a given application server failed to end a local transaction (made up of a non-synchronized, non-JTA UnitOfWork) after a remove, create, business method, or home method invocation.

**Action:** See the exception message provided.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10016: Exception [EJB - {0}]: An error occurred while getting transaction from TransactionManager.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10021: Exception [EJB - {0}]: An error occurred while attempting to assign sequence numbers for bean of type [{1}].**

---

**Cause:** The PersistenceManager for a given application server, whose shouldAssignSequenceNumbers method returns true, failed to assign a sequence number to an entity.

**Action:** See the exception message provided.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10022: Exception [EJB - {0}]: RemoteException on method call [{1}] for bean of type {2}.**

**Cause:** A java.rmi.RemoteException was raised when an entity was activated, loaded, passivated, or stored.

**Action:** See the exception message provided.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10023: Exception [EJB - {0}]: Sequence Exception for bean of type {1}.**

**Cause:** An exception was raised while handling a post-insert DescriptorEvent preventing the specified entity from being assigned a primary key.

**Action:** See the exception message provided.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10025: Exception [EJB - {0}]: An internal error has occurred while accessing the EJBContext [{1}].**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services if required.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10026: Exception [EJB - {0}]: An internal error has occurred locating the generated subclass [{1}].**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services if required.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10027: Exception [EJB - {0}]: An internal error has occurred in a server process. EJBContext [{1}] not properly initialized.**

**Cause:** Internal error.

**Action:** Contact Oracle Support Services if required.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10028: Exception [EJB - {0}]: The specified attribute [{1}] cannot be merged since it does not exist for beans of type [{2}].**

**Cause:** The registerOrMergeAttribute method of the SessionAccessor, called from within an EJB setter method, failed to obtain a DatabaseMapping for the given attribute from the PersistenceManager.

**Action:** Verify that the given attribute belongs to the EJB class and if it does, verify that a mapping exists for it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10029: Exception [EJB - {0}]: An internal error occurred accessing the bean or primary key class.**

**Cause:** Failed to wrap an EJB bean for return to the application because the attempt to extract the primary key from the bean failed.

**Action:** See the exception message provided.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10030: Exception [EJB - {0}]: An internal error occurred accessing the bean of type [{1}] or primary key class.**

**Cause:** Failed to initialize primary key fields due to java.lang.NoSuchFieldException.

**Action:** See the exception message provided.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10031: Exception [EJB - {0}]: Unable to prepare bean of type [{1}] with pk [{2}] for invocation.**

**Cause:** One of the following failed with an exception other than javax.ejb.ObjectNotFoundException: a conforming find using the same query as a find by primary key; an Oracle Containers for J2EE startCall method invocation for a BUSINESS METHOD operation; or a WebLogic preInvoke method invocation.

**Action:** See the exception message provided.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10032: Exception [EJB - {0}]: Finder not yet implemented: {2}{1}.**

**Cause:** Associated finder method has no implementation.

---

**Action:** Provide an implementation for the finder method.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10033: Exception [EJB - {0}]: findByPrimaryKey invoked with null primary key for bean of type [{1}].**

**Cause:** A find by primary key was called with a null primary key value.

**Action:** Ensure the primary key is not null when the finder method is invoked.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10034: Exception [EJB - {0}]: Remove on bean of type [{1}] invoked with null primary key.**

**Cause:** A find by primary key was called with a null primary key value.

**Action:** Ensure the primary key is not null when the finder method is invoked.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10036: Exception [EJB - {0}]: An error occurred during code generation.**

**Cause:** The PersistenceManager for a given application server failed to generate a bean subclass.

**Action:** See the exception message provided.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10037: Exception [EJB - {0}]: Error while executing ejbSelectMethod: [{1}] on bean of type [{2}].**

**Cause:** An EJB select failed with an exception other than javax.ejb.ObjectNotFoundException.

**Action:** See the exception message provided.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10038: Exception [EJB - {0}]: Error while executing ejbHomeMethod: [{1}].**

**Cause:** The invocation of a home interface method (excluding finder or create methods) failed.

**Action:** See the exception message provided.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**TOP-10040: Exception [EJB - {0}]: No transaction was active on invocation of {1} method.**

**Cause:** A create or remove EJB failed because the PersistenceManager does not have a transaction.

**Action:** Ensure your application has a transaction available. This may be a configuration problem related to your ejb-jar.xml file or an application logic problem in your client code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10041: Exception [EJB - {0}]: The parameter passed to the {1} method has already been deleted.**

**Cause:**

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10043: Exception [EJB - {0}]: Unable to wrap the results of the finder because " + " they have already been wrapped. If using a custom query (ex: a redirect query), " + " then be sure that you called 'setShouldUseWrapperPolicy(false)'.**

**Cause:** The results of a finder query could not be wrapped because they were already wrapped.

**Action:** If a redirect query is used, be sure to call the setShouldUseWrapperPolicy(false) method first.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10045: Exception [EJB - {0}]: Unable to wrap the results of the finder as " + " EJBLocalObjects because there is no Local interface. If executing an ejbSelect " + " query, make sure the result-type-mapping tag is correctly.**

**Cause:** Error resolving the local interface.

**Action:** Double-check your local interface configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10046: Exception [EJB - {0}]: Unable to wrap the results of the finder as " + " EJBOObjects because there is no Remote interface. If executing an ejbSelect " + " query, make sure the result-type-mapping tag is correctly.**

**Cause:** Error resolving the remote interface.

**Action:** Please double-check your remote interface configuration.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**TOP-10047: Exception [EJB - {0}]: Trying to create a bean with a null primary key. Check your " + " bean's ejbCreate method to ensure the primary key fields are set. If TopLink " + " sequencing is being used, make sure hat sequencing is setup correctly on all the " + " beans in the TopLink project.**

**Cause:** The PersistenceManager for a given application server failed to create a bean because the primary key was not defined.

**Action:** Make sure the primary key is defined properly, either in the application logic or through the sequence number configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10049: Exception [EJB - {0}]: The argument [{1}] of type [{2}] is not of the correct type for the " + " relationship. See section 10.3.6 of the EJB 2.1 specification. The argument type expected was [{3}].**

**Cause:** The argument is not of the correct type for the relationship. See section 10.3.6 of the EJB 2.1 specification.

**Action:** Check the parameter type to ensure that it is of the correct type for this collection.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10051: Exception [EJB - {0}]: An attempt was made to access a Collection/Iterator outside a transaction " + " or in one other than the one in which it was acquired. See section 10.3.8 of " + " the EJB 2.1 specification.**

**Cause:** An attempt was made to access a Collection or Iterator outside a transaction or in one other than the one in which it was acquired. See section 10.3.8 of the EJB 2.1 specification.

**Action:** Check the CMR collection to determine whether it is being accessed in the same transaction.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10052: Exception [EJB - {0}]: Cannot find bean of type [{2}] with primary key [{1}] for remote method invocation.**

**Cause:** Cannot find bean of type with primary key for remote method invocation.

**Action:** The exception will be raised if the finder method returns a null result during remote method invocation. Ensure that the bean has already existed before lookup.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic



---

**TOP-10053: Exception [EJB - {0}]: Cannot find bean of type [{2}] with primary key [{1}] for local method invocation.**

**Cause:** Cannot find bean of type with primary key for local method invocation.

**Action:** This exception will be raised if the finder method returns a null result during local method invocation. Ensure that the bean already exists before lookup.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10054: Exception [EJB - {0}]: An internal error has occurred while accessing the bean of type [{1}]**

**Cause:** An internal error has occurred while accessing the bean.

**Action:** An internal exception occurred during create bean instance. Check the internal exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10055: Exception [EJB - {0}]: An error has occurred while cascading the delete from the bean of type [{1}] to the [{2}] relationship.**

**Cause:** An error has occurred while cascading the delete from the bean to the relationship.

**Action:** An error occurred while performing cascade-delete of private owned objects. Check the underlying exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10056: Exception [EJB - {0}]: An error has occurred while performing relationship maintenance for the bean of type [{1}] with the [{2}] relationship.**

**Cause:** An error has occurred while performing relationship maintenance for the bean with the relationship.

**Action:** Check the private-owned (cascade-delete) relationship in the domain object and also the underlying exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10057: Exception [EJB - {0}]: Multiple results were found while executing the single object finder [{2}] for the bean of type [{1}].**

**Cause:** Multiple results were found while executing the single object finder for the bean.

**Action:** Check if the query is passed properly and also the underlying TopLink query exception.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**TOP-10058: Exception [EJB - {0}]: Unable to invoke method [{1}] on bean of type [{2}] because this bean is read only.**

**Cause:** Unable to invoke method on bean because this bean is read only.

**Action:** Check the bean descriptor to see if the read-only flag was specified.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10059: Exception [EJB - {0}]: Unable to invoke method [{1}] on bean of type [{2}] because the target bean " + " of type [{3}] is read only. Either the target bean's object model (in the case of bi-directional relationship) or database table would not be modified by this operation.**

**Cause:** Unable to invoke method on bean because the target bean is read only. Either the target bean's object model (in the case of a bidirectional relationship) or the database table would not be modified by this operation.

**Action:** Check the target bean descriptor for the 1:1 relationship in the domain object, to see if the read-only flag was specified.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10060: Exception [EJB - {0}]: Unable to invoke method [{1}] on collection [{2}] in bean of type [{3}] because the source bean is read only.**

**Cause:** Unable to invoke method on collection in bean because the source bean is read only.

**Action:** Check the source bean descriptor for the 1:M and M:M relationship in the domain object, to see if the read-only flag was specified.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10061: Exception [EJB - {0}]: Unable to invoke method [{1}] on collection [{2}] in bean of type [{3}] because the target bean of type [{4}] is read only. " + " Either the target bean's object model (in the case of bi-directional relationship) or database table would not be modified by this operation.**

**Cause:** Unable to invoke method on collection in bean because the target bean is read only. Either the target bean's object model (in the case of a bidirectional relationship) or the database table will not be modified by this operation.

**Action:** Check the bidirectional target bean descriptor to see if the read-only flag was specified.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10062: Exception [EJB - {0}]: Unable to retrieve underlying data for object type : {2} primary keys: {1}. Transaction must be restarted and objects refreshed.**

---

**Cause:** Unable to retrieve underlying data for object primary keys. The transaction must be restarted and objects refreshed.

**Action:** The underlying object is garbage collected and removed from the cache. Restart the transaction and refresh all objects.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10063: Exception [EJB - {0}]: Unknown collection type : {1} passed to container policy.**

**Cause:** Unknown collection type passed to container policy.

**Action:** Ensure that the correct collection type is used.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10064: Exception [EJB - {0}]: Any changes to fields must be performed within a transaction.**

**Cause:** Any changes to fields must be performed within a transaction.

**Action:** Ensure that any changes are performed within a transaction.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10065: Exception [EJB - {0}]: An error occurred while adding object {1} to collection {2}.**

**Cause:** An error occurred while adding an object to a collection.

**Action:** An error occurred during relationship maintenance for the add method. Check the underlying exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10066: Exception [EJB - {0}]: An error occurred while removing object {1} from collection {2}.**

**Cause:** An error occurred while removing an object from a collection.

**Action:** An error occurred during relationship maintenance for the remove method. Check the underlying exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10067: Exception [EJB - {0}]: An error occurred while performing relationship maintenance for the field {1}.**

**Cause:** An error occurred while performing relationship maintenance for a field.

---

**Action:** An error occurred on relationship maintenance for the cmr field. Check the underlying exception.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10068: Exception [EJB - {0}]: An error occurred with the DataSource {1}. TopLink CMP requires use of a managed-data-source. A native-data-source cannot be used.**

**Cause:** An error occurred with the data source. TopLink CMP requires use of a managed-data-source. A native-data-source cannot be used.

**Action:** Check the data-sources.xml file in OC4J. TopLink CMP requires the use of a managed-data-source.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10069: Exception [EJB - {0}]: Failed lookup of object under JNDI name: {1}.**

**Cause:** Failed lookup of object under JNDI name.

**Action:** Check the JNDI name and also the underlying javax.naming.NamingException.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-10070: Exception [EJB - {0}]: An internal error occurred accessing the bean of type [{1}] or primary key class of type [{2}].**

**Cause:** An internal error occurred accessing the bean of type or primary key class of type.

**Action:**

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-12000: Error Sending connection service to {0}.**

**Cause:** Failed to add a connection to CacheSynchronizationManager or RemoteCommandManager.

**Action:** See the generated exception for the root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-12001: Unable to Connect to {0}.**

**Cause:** CacheSynronizationManager failed to connect to the specified service.

**Action:** See the generated exception for the root cause.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-12002: Unable to propagate changes to {0}.**

**Cause:** CacheSynronizationManager failed to propagate changes to the specified service.

**Action:** See the generated exception for the root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-12003: Error in invocation: {0}.**

**Cause:** Error invoking a remote call.

**Action:** See the generated exception for the root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-17007: {0} property must be set.**

**Cause:** The specified property is not set.

**Action:** Verify your interaction and ensure that the specified property is set (see "Configuring Custom EIS Interactions for Basic Persistence Operations" on page 73-6 or "Creating an EIS Interaction for a Named Query" on page 116-26).

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-17008: Invalid {0} property encountered.**

**Cause:** Invalid property encountered.

**Action:** Verify your interaction and remove the specified property (see "Configuring Custom EIS Interactions for Basic Persistence Operations" on page 73-6 or "Creating an EIS Interaction for a Named Query" on page 116-26).

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-17009: {0} or {1} property must be set.**

**Cause:** The specified properties are not set.

**Action:** Verify your interaction and ensure that the specified properties are set (see "Configuring Custom EIS Interactions for Basic Persistence Operations" on page 73-6 or "Creating an EIS Interaction for a Named Query" on page 116-26).

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**TOP-17010: Output record contains an unsupported message type**

**Cause:** The output record contains an unsupported message type.

**Action:** Verify your interaction and ensure that you specify a supported message type. Ensure that the required connector JAR file is on your classpath (see "EIS Project Concepts" on page 68-1).

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-17011: No connection factory has been specified.**

**Cause:** The connection factory is not specified.

**Action:** Verify your interaction and ensure that you specify a connection factory (see "Configuring EIS Connection Specification Options at the Project Level" on page 70-3 or "Configuring EIS Connection Specification Options at the Session Level" on page 96-2 ).

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-17012: InteractionSpec must be a CciJMSInteractionSpec.**

**Cause:** InteractionSpec is not a CciJMSInteractionSpec.

**Action:** Verify your interaction and ensure that you specify a valid interaction specification type (CciJMSInteractionSpec). Ensure that the required connector JAR file is on your classpath (see "EIS Project Concepts" on page 68-1).

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-17013: Record must be a CciJMSRecord.**

**Cause:** Record is not a CciJMSRecord.

**Action:** Verify your interaction and ensure that you specify a valid record type (CciJMSRecord). Ensure that the required connector JAR file is on your classpath (see "EIS Project Concepts" on page 68-1).

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-17014: Unknown interaction specification type**

**Cause:** Unknown interaction specification type.

**Action:** Verify your interaction and ensure that you specify a valid interaction specification type. Ensure that the required connector JAR file is on your classpath (see "EIS Project Concepts" on page 68-1).

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**TOP-17015: Input must contain a single text element.**

**Cause:** Invalid input: input must contain a single text element.

**Action:** Verify your interaction and ensure that you specify valid input-a single text element (see "Configuring Custom EIS Interactions for Basic Persistence Operations" on page 73-6 or "Creating an EIS Interaction for a Named Query" on page 116-26).

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-17016: A timeout occurred - no message was received.**

**Cause:** A time-out occurred-no message was received.

**Action:** Verify your interaction and the EIS on which you invoked it.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-17017: Input record contains an unsupported message type.**

**Cause:** Input record contains an unsupported message type.

**Action:** Verify your interaction and ensure that you specify a valid message type. Ensure that the required connector JAR file is on your classpath (see "EIS Project Concepts" on page 68-1).

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-17018: Cannot invoke "begin()" on a non-transacted session.**

**Cause:** TopLink cannot invoke begin method on a nontransacted session.

**Action:** To be determined.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-17019: Problem testing for transacted session:**

**Cause:** Problem testing for transacted session.

**Action:** To be determined.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-17020: InteractionSpec must be an AQInteractionSpec.**

**Cause:** InteractionSpec is not an AQInteractionSpec.

**Action:** Verify your interaction and ensure that you specify a valid Oracle AQ interaction specification type (AQInteractionSpec). Ensure that the required connector JAR file is on your classpath (see "EIS Project Concepts" on page 68-1).

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-17021: Record must be an AQRecord.**

**Cause:** Record is not an AQRecord.

**Action:** Verify your interaction and ensure that you specify a valid Oracle AQ record type (AQRecord). Ensure that the required connector JAR file is on your classpath (see "EIS Project Concepts" on page 68-1).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-17022: Input must contain a single raw element.**

**Cause:** Invalid input: input must contain a single raw element.

**Action:** Verify your Oracle AQ interaction and ensure that you specify valid input-a single raw element (see "Configuring Custom EIS Interactions for Basic Persistence Operations" on page 73-6 or "Creating an EIS Interaction for a Named Query" on page 116-26).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-17023: An exception occurred setting MQQueueConnectionFactory attributes.**

**Cause:** An exception occurred setting MQQueueConnectionFactory attributes.

**Action:** Verify your interaction and ensure that you specify an appropriate IBM MQSeries connection factory (see "Configuring EIS Connection Specification Options at the Project Level" on page 70-3 or "Configuring EIS Connection Specification Options at the Session Level" on page 96-2).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-17024: Could not delete file: {0}**

**Cause:** TopLink cannot delete the specified file.

**Action:** To be determined.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-17025: This mapping requires a foreign key grouping element, as multiple foreign keys exist.**

**Cause:** No grouping element is specified: this mapping requires a foreign key grouping element, as multiple foreign keys exist.

**Action:** Verify your EIS mappings (see Chapter 74, "Introduction to EIS Mappings").



---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-18001: Error while processing incoming JMS message**

**Cause:** Failed to process the incoming JMS message.

**Action:** See the generated exception for the root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-18002: The topic created in the JMS service for the interconnection of sessions must be set in the JMSClusteringService**

**Cause:** JMSClusteringService failed to start because the Topic created in the JMS service for the interconnection of sessions is null.

**Action:** Ensure that the Topic created in the JMS service for the interconnection of sessions is set in the JMSClusteringService.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-18003: Failed to lookup the session's name defined in the env-entry element of the Message Driven Bean**

**Cause:** Failure in looking up the session's name defined in the env-entry element of the message-driven bean.

**Action:** Verify the correctness of the env-entry element definition of the Message Driven Bean.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-18004: The Message Driven Bean (MDB) cannot find the session.**

**Cause:** The message-driven bean (MDB) cannot find the session.

**Action:** Ensure that the session that this MDB's getSession() method returns is not null session.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-20001: Could not find the parameter type: [{2}], defined in the ejb-jar.xml, of the finder: [{1}] in the entity bean: [{0}].**

**Cause:** TopLink could not find the parameter type, defined in the ejb-jar.xml file of the finder in the entity bean.

**Action:** Check the finder definition in the ejb-jar.xml file and the bean home to ensure that the named finder has the specified method parameter type(s).

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**TOP-20002: The finder method: [{1}] with the parameters as: [{2}], defined in the ejb-jar.xml, is not found in the home of bean: [{0}].**

**Cause:** The finder method with the parameters as defined in the ejb-jar.xml file is not found in the home of bean.

**Action:** Check the ejb-jar.xml file and the bean home to ensure that the finder with the specified name and method parameter type(s) are defined.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-20003: The ejbSelect method: [{1}] with the parameters as: [{2}], defined in the ejb-jar.xml, is not found in the bean class of bean: [{0}].**

**Cause:** The ejbSelect method with the parameters, as defined in the ejb-jar.xml file, is not found in the bean class.

**Action:** Check the ejb-jar.xml file and the bean class to ensure that the ejbSelect method is defined with the specified name and method parameter type(s).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-20004: The finder method: [{1}] of bean: [{0}] in ejb-jar.xml file is not well defined. It should start with either 'find' or 'ejbSelect'.**

**Cause:** The finder method of bean in the ejb-jar.xml file is not well defined. It should start with either find or ejbSelect.

**Action:** Check the ejb-jar.xml file to ensure that the query name starts with find or ejbSelect, according to the EJB specification.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-20005: The abstract getter method: [{0}] is not defined in the bean: [{1}].**

**Cause:** The abstract get method is not defined in the bean.

**Action:** Check the ejb-jar.xml file and the bean class to ensure that the abstract get method is well defined.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-20006: The cmp field: [{0}] is not defined in the bean: [{1}].**

**Cause:** The CMP field is not defined in the bean.

**Action:** Check the ejb-jar.xml file and the bean class to ensure that the CMP field defined in the ejb-jar.xml file is also defined in the bean class.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**TOP-22001: Could not join multicast group**

**Cause:** DiscoveryManager failed to join a multicast group due to a java.io.IOException: either a MulticastSocket could not be created, or the invocation of the joinGroup method of the MulticastSocket failed.

**Action:** See the generated exception for the root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-22002: Could not send service announcement**

**Cause:** DiscoveryManager failed to inform other services that its service had started up.

**Action:** Consider increasing the announcement delay: the amount of time in milliseconds that the service should wait between the time that this remote service is available and a session announcement is sent out to other discovery managers. This may be needed to give some systems more time to post their connections into the naming service. See the setAnnouncementDelay method of the DiscoveryManager.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-22003: Failed doing lookup of local host**

**Cause:** DiscoveryManager failed to do the lookup of a local host.

**Action:** See the generated exception for the root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-22004: Failed trying to receive a service announcement from a remote service**

**Cause:** DiscoveryManager caught a java.io.IOException while blocking for announcements from other DiscoveryManagers.

**Action:** See the generated exception for the root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-22101: Could not obtain JNDI context with properties {0}**

**Cause:** Failure to get a JNDI context with the specified properties due to a javax.naming.NamingException.

**Action:** See the generated exception for root cause. Verify that the properties for looking up the context are correct.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**TOP-22102: Could not post connection in local naming service under name {0}**

**Cause:** Failure to post a connection in the local naming service with the name serviceName.

**Action:** See the generated exception for the root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-22103: Could not look up remote connection under name {0} with URL {1}**

**Cause:** Failure to look up a remote connection with the specified name and URL.

**Action:** See the generated exception for the root cause. Verify that the remote connection and URL are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-22104: Could not look up hostname**

**Cause:** The getLocalHost method of the java.net.InetAddress failed to look up the specified host name.

**Action:** See the generated exception for the root cause. Verify that the host is online and reachable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-22105: Could not propagate command to {0}**

**Cause:** Failure to propagate a command to the specified connection.

**Action:** See the generated exception for the root cause. Verify that the remote host of the specified connection is online and reachable if the generated exception included a CommunicationException.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-22106: Could not create external JMS connection with Topic {0}, Topic Factory {1}, and Context properties {2}**

**Cause:** Failure to create JMS connection with Topic, Topic Factory, and Context properties.

**Action:** Verify that the JMS Topic is configured correctly with the application server and the specified Topic. Topic Factory and Context properties info can be used by a Java client to the JMS Topic.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**TOP-22107: Could not remove local connection in local naming service under name {0}**

**Cause:** Failure to establish a remove local connection in local naming service under name.

**Action:** Restart the application server or use the application server tool to remove name from its JNDI if this tool is available.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-22108: Could not serialize or desirialize command**

**Cause:** Failure to serialize or deserialize command.

**Action:** If the command is a user defined command, make sure it is serializable. If it is a TopLink command, file a bug report including the stack trace.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-22109: Failed to receive JMS message from JMS provider**

**Cause:** Failure to receive JMS message from JMS provider.

**Action:** Make sure that TopLink sessions are the only publishers to the JMS Topic and that the TopLink sessions use the same project.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-22110: Failed to discover local host IP address.**

**Cause:** Failure to discover local host IP address.

**Action:** Replace the \$HOST string of the URL with the known host name or IP address.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-22111: Failed to get ServerPlatform. The ServerPlatform must be set either on Session or RemoteCommandManager.**

**Cause:** Failure to get server platform. The server platform must be set on Session or RemoteCommandManager.

**Action:** Set the correct ServerPlatform on the RemoteCommandManager. This exception is raised when the user does not use a TopLink Session and implements the CommandProcessor.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**TOP-23001: Error looking up external Transaction resource under JNDI name [{0}]**

**Cause:** Error looking up external transaction resource under JNDI name name.

**Action:** Examine the internal exception and take the appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-23002: Error obtaining status of current externally managed transaction**

**Cause:** Error obtaining the status of the current externally-managed transaction.

**Action:** Examine the internal exception and take the appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-23003: Error obtaining current externally managed transaction**

**Cause:** Error obtaining the current externally managed transaction.

**Action:** Examine the internal exception and take the appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-23004: Error obtaining the Transaction Manager**

**Cause:** Error obtaining the transaction manager.

**Action:** Examine the internal exception and take the appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-23005: Error binding to externally managed transaction**

**Cause:** Error binding to the externally managed transaction.

**Action:** Examine the internal exception and take the appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-23006: Error beginning new externally managed transaction**

**Cause:** Error beginning a new externally managed transaction.

**Action:** Examine the internal exception and take the appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-23007: Error committing externally managed transaction**

**Cause:** Error committing the externally managed transaction.

---

**Action:** Examine the internal exception and take the appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-23008: Error rolling back externally managed transaction**

**Cause:** Error rolling back the externally managed transaction.

**Action:** Examine the internal exception and take the appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-23009: Error marking externally managed transaction for rollback**

**Cause:** Error marking the externally managed transaction for rollback.

**Action:** Examine the internal exception and take the appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-23010: No externally managed transaction is currently active for this thread**

**Cause:** No externally managed transaction is currently active for this thread.

**Action:** Ensure that the transaction is still active.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-23011: UnitOfWork [{0}] was rendered inactive before associated externally managed transaction was complete.**

**Cause:** A UnitOfWork was rendered inactive before the associated externally managed transaction was complete.

**Action:** Examine the internal exception and take the appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-23012: No transaction is currently active**

**Cause:** Attempt to use an EntityTransaction while using JTA. This is an invalid operation.

**Action:** Examine the internal exception and take the appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-23013: Transaction is currently active**

**Cause:** Attempt to enlist multiple data sources in the transaction.

---

**Action:** Enlist only one data source per transaction.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-23014: Cannot use an EntityTransaction while using JTA.**

**Cause:** Exception occurred in Proxy execution.

**Action:** Examine the internal exception and take the appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-23015: Cannot enlist multiple datasources in the transaction.**

**Cause:** No entity transaction is currently active for this thread.

**Action:** Ensure that the transaction is active.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-25001: Invalid XPath string: {0}**

**Cause:** Attempt to use an invalid XPath string.

**Action:** Ensure that the XPath is specified correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-25002: An integer index could not be parsed from this XPath string: {0}**

**Cause:** An integer index could not be parsed from this XPath string.

**Action:** Update any XPath strings that contain an index, and ensure that only a single integer value is contained between the square braces.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-25003: An error occurred marshalling the object**

**Cause:** An error occurred marshalling the object.

**Action:** Check the nested exception to determine the cause of the problem. Typically, there is a problem with the object being written.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-25004: An error occurred unmarshalling the document**

**Cause:** An error occurred unmarshalling the document.



---

**Action:** Check the nested exception to determine the cause of the problem. Typically, there is a problem with the XML document being read.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-25005: An error occurred validating the object**

**Cause:** An error occurred validating the object.

**Action:** The XML generated from the object is invalid according to the schema. Ensure that any values set in the domain classes do not violate any schema constraints when marshalled.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-25006: A default root element was not specified for the XMLDescriptor mapped to {0}**

**Cause:** A default root element is not specified for the XMLDescriptor mapped to target.

**Action:** Specify the default root element for the descriptor.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-25007: A descriptor for class {0} was not found in the project**

**Cause:** A descriptor for a class was not found in the project.

**Action:** Make sure that any classes referenced through CompositeObject and/or CompositeCollection mappings have descriptors in the project.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-25008: A descriptor with default root element {0} was not found in the project**

**Cause:** A descriptor with a default root element was not found in the project.

**Action:** Set a default root element on any descriptor that maps to the root of a document. Make sure that the root element of the XML document being read in is mapped to a descriptor in the project.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-25010: A schema reference was not specified for the XMLDescriptor mapped to {0}**

**Cause:** A schema reference is not specified for the XMLDescriptor mapped to target.

**Action:** Specify the schema reference for the descriptor.

---

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-25011: A null argument was encountered**

**Cause:** A null argument was encountered.

**Action:** Ensure that this argument is not null.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-25012: An error occurred resolving the XML Schema.**

**Cause:** An error occurred resolving the XML Schema.

**Action:** Check any schema references and make sure that the schema can be accessed by the application at runtime.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-25013: An error occurred while trying to set the schemas.**

**Cause:** An error occurred while trying to set the schemas.

**Action:** An error was encountered while attempting to set schemas on an XML parser. Check the nested exception to determine the correct course of action.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-25014: An error occurred while trying to instantiate the schema platform.**

**Cause:** An error occurred while trying to instantiate the schema platform.

**Action:** An error was encountered while instantiating the schema platform. Check the nested exception to determine the correct course of action.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-25015: An error occurred trying to resolve the namespace URI for {0}. A namespace resolver was not specified on the descriptor.**

**Cause:** An error occurred while trying to resolve the namespace URI for a target. A namespace resolver was not specified on the descriptor.

**Action:** Ensure that any descriptors that make use of namespaces have a namespace resolver specified on them.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-25016: A namespace for the prefix {0} was not found in the namespace resolver.**

---

**Cause:** A namespace for the prefix was not found in the namespace resolver.

**Action:** Ensure that any namespace prefix which is used by a descriptor or mapping has a corresponding entry in that descriptor's namespace resolver.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-25017: Either enumClass or enumClassName must be set on the JAXBTypesafeEnumConverter.**

**Cause:** Enumeration class is not specified.

**Action:** Set either enumClass or enumClassName on the JAXBTypesafeEnumConverter.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-25018: The fromString method on the enum class {0} does not exist or could not be invoked.**

**Cause:** Error during the invocation of the fromString method on the enumeration class ClassName: the method does not exist or could not be invoked.

**Action:** See the generated exception for the root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-25019: The specified enum class {0} could not be found.**

**Cause:** The specified enumeration class ClassName was not found.

**Action:** Ensure the correct specification of the enumeration class.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-25020: The method getResult() must not be called before the endDocument() event has been called.**

**Cause:** Attempt to call the method getResult before the call to the endDocument event.

**Action:** Call the getResult method after the endDocument event has been called.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-25501: Cannot create URL for file [{0}] .**

**Cause:** Failure to create a URL for the specified file.

**Action:** Ensure that all specified XPath strings on mappings are valid and correct.

**Level:** 1

---

**Type:** ERROR

**Impact:** Programmatic

**TOP-26001: WLS->OC4J TopLink migration exception: There contains multiple migratable JARs in the input EAR({0}), and orion-ejb-jar.xml is also provided in the input. The migration utility only supports single migratable JAR in an EAR if orion-ejb-jar.xml is also in the input.**

**Cause:** The migration utility only supports a single migratable JAR file in an EAR file if the orion-ejb-jar.xml file is also in the input.

**Action:** Remove the orion-ejb-jar.xml file from the input directory, or keep only one migratable JAR file in the input EAR file.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-26002: The program security manager prevents the migration utility from creating a JAR class loader for Jar file({0})**

**Cause:** The program security manager prevents the migration utility from creating a JAR class loader for the JAR file.

**Action:** Configure the program security manager to grant permission on the program to create the JAR class loader.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-26003: The program security manager prevents the migration utility from creating directory({0})**

**Cause:** The program security manager prevents the migration utility from creating a directory.

**Action:** Configure the program security manager to grant permission on the program to create a local directory.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-26004: The file({0}) is not accessible by the migration utility**

**Cause:** The file is not accessible by the migration utility.

**Action:** Check to ensure that the file is on the specified path and is readable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-26005: The program security manager prevents the migration utility from deleting directory({0})**

**Cause:** The program security manager prevents the migration utility from deleting a directory.

---

**Action:** Configure the program security manager to grant permission to the program to delete files.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-26006: i/o exception occurs when reading data from an input stream**

**Cause:** A java.io.IOException occurred when reading data from an input stream.

**Action:** Check to ensure that the file is not locked and is accessible.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-26007: i/o exception occurs when closing data from an input or output stream**

**Cause:** A java.io.IOException occurred when closing data from an input or output stream.

**Action:** Check to ensure that the file is not locked and is accessible.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-26008: i/o exception occurs when closing data from an zip file**

**Cause:** A java.io.IOException occurred when closing data from a zip file.

**Action:** Check to ensure that the zip file is not locked and is accessible.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-26009: Jar file({0}) not found or accessible in the specified path**

**Cause:** The JAR file was not found or was not accessible on the specified path.

**Action:** Check to ensure that the JAR file is not locked and is accessible.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-26010: Query method({0}) with parameters({1}) of the entity({2}) defined in ejb-jar.xml is not well defined as it starts by neither 'find' nor 'ejbSelect'**

**Cause:** Query method with parameters of the entity defined in the ejb-jar.xml file is not well defined as it does not start with find or ejbSelect.

**Action:** Check the ejb-jar.xml file to ensure that the finder name starts with either find or ejbSelect according to the EJB spec.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**TOP-26011: The class({1}) defined as a parameter type of the query({0}) of the entity({2}) in ejb-jar.xml could not be loaded. Most likely, the class is not included not in the classpath.**

**Cause:** The class defined as a parameter type of the query of the entity in ejb-jar.xml could not be loaded.

**Action:** Ensure that the bean class is included on the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-26012: Finder method({0}) with parameters({1}) defined in ejb-jar.xml is not defined at the entity({2})'s (local and/or remote) home interface**

**Cause:** The finder method with parameters defined in the ejb-jar.xml file is not defined at the entity's local and/or remote home interface.

**Action:** Check the ejb-jar.xml file and the bean home to ensure that the finder method parameter types are properly defined.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-26013: ejbSelect method({0}) with parameters({1}) defined in ejb-jar.xml is not defined at the entity({2})'s bean class**

**Cause:** The ejbSelect method with parameters defined in the ejb-jar.xml file is not defined at the entity's bean class.

**Action:** Check the ejb-jar.xml file and the bean class to ensure that the ejbSelect method parameter types are properly defined.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-26014: Entity({0}) specified in weblogic-cmp-jar.xml is not defined in weblogic-ejb-jar.xml.**

**Cause:** The entity specified in the weblogic-cmp-jar.xml file is not defined in the weblogic-ejb-jar.xml file.

**Action:** Ensure that the entity is consistently defined in the deployment descriptor files.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-26015: No entity element is defined in weblogic-cmp-rdbms-jar.xml file**

**Cause:** No entity element is defined in the weblogic-cmp-rdbms-jar.xml file.

**Action:** Ensure that all entities defined in the ejb-jar.xml file are mapped in the WebLogic CMP descriptor file.

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**TOP-26016: The weblogic cmp descriptor file({0}) specified in the weblogic-ejb-jar.xml is not found in the directory ({1})**

**Cause:** The WebLogic CMP descriptor file specified in the weblogic-ejb-jar.xml file was not found in the directory.

**Action:** Ensure that the WebLogic CMP descriptor file, specified in the weblogic-ejb-jar.xml file, is included in the input directory.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-26017: The cmp descriptor file({1}) is not found in the jar({0}) file to be migrated.**

**Cause:** The CMP descriptor file is not found in the JAR file to be migrated.

**Action:** Ensure that the WebLogic CMP descriptor file, specified in the weblogic-ejb-jar.xml file, is included in the input archive JAR file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-26018: Some of the entity beans ({0}) defined at ejb-jar.xml in the jar ({1}) are not explicitly mapped in orion-ejb-jar.xml. You need to provide the completely mapped orion-ejb-jar.xml to the migration tool. You can obtain the completely mapped orion-ejb-jar.xml from the /application-deployment directory after deploying the application.**

**Cause:** Some of the entity beans EntityBeanClassName-s defined in the ejb-jar.xml file in the JAR jarName are not explicitly mapped in the orion-ejb-jar.xml file.

**Action:** Provide the completely mapped orion-ejb-jar.xml file to the migration tool. You can obtain the completely mapped orion-ejb-jar.xml file from the /application-deployment directory after deploying the application.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-26019: The entity ({0}) in orion-ejb-jar.xml is not mapped as no table or primary key mapping is specified. You need to provide the completely mapped orion-ejb-jar.xml to the migration tool. You can obtain the completely mapped orion-ejb-jar.xml from the /application-deployment directory after deploying the application.**

**Cause:** The entity EntityName in the orion-ejb-jar.xml file is not mapped, because no table is specified.

**Action:** Provide the completely mapped orion-ejb-jar.xml file to the migration tool. You can obtain the completely mapped orion-ejb-jar.xml file from the /application-deployment directory after deploying the application.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**TOP-26020: The entity ({0}) specified in orion-ejb-jar.xml is not defined in ejb-jar.xml.**

**Cause:** The entity EntityName specified in the orion-ejb-jar.xml file is not defined in the ejb-jar.xml file.

**Action:** Define this entity in the ejb-jar.xml file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TOP-27001: The XML Platform class was not found: {0}**

**Cause:** The XML platform class ClassName was not found.

**Action:** Ensure that this class is on the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-27002: The XML Platform could not be instantiated: {0}**

**Cause:** Failure to instantiate the XML platform ClassName.

**Action:** See the generated exception for the root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-27003: A new XML document could not be created.**

**Cause:** The XML platform failed to create a new XML document.

**Action:** See the generated exception for the root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-27004: The XPath was invalid.**

**Cause:** The XPath is invalid.

**Action:** See the generated exception for the root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-27005: An error occurred while validating the document.**

**Cause:** Error during the document validation.

**Action:** See the generated exception for the root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic



---

**TOP-27006: Could not resolve XML Schema: {0}**

**Cause:** Failure to resolve an XML Schema schema: XML platform parser error occurred.

**Action:** See the generated exception for the root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-27101: An error occurred while parsing the document.**

**Cause:** Failure to parse the document.

**Action:** See the generated exception for the root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-27102: File not found: [{0}]**

**Cause:** Failure to find the XML platform parser file.

**Action:** Ensure that the parser file exists and is accessible (on the classpath).

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-27103: \*\* Parsing error, line [{0}], uri [{1}] [{2}]**

**Cause:** SAX parser error at line lineNumber, URI uri.

**Action:** See the generated exception for the root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-27201: An error occurred while transforming the document.**

**Cause:** Error during the transforming of the document.

**Action:** See the generated exception for the root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**TOP-27202: Unknown type encountered: {0}**

**Cause:** Unknown type type encountered.

**Action:** See the generated exception for the root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**TOP-28001: A ValidationException was thrown while trying to create session: [{0}] .**  
**The most likely causes of this issue are that your [{1}] file is not available on the classpath or it does not contain a session called: [{0}].**

**Cause:** A ValidationException was thrown while trying to create a session  
sessionName.

**Action:** Ensure that your fileName file is on the classpath. If it is on the classpath, ensure that this file contains the session sessionName.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**TOP-28002: TopLink is attempting to load a ServerSession named [{0}] from [{1}], and not getting a ServerSession.**

**Cause:** Failure to load a ServerSession sessionName from sourceName.

**Action:** Ensure that the server session's type is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**TOP-28003: TopLink has loaded Session [{0}] from [{1}] and it either does not have a server platform specified or specifies a server platform that does not use an external transaction controller. Please specify an appropriate server platform if you plan to use JTA.**

**Cause:** Server platform specification was not found: TopLink has loaded a session sessionName from sourceName, but this session either does not have a server platform specified, or specifies a server platform that does not use an external transaction controller.

**Action:** If you plan to use JTA, specify an appropriate server platform.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**TOP-28004: Error in setup of EntityManager factory:**

**JavaSECMPInitializer.initializeFromMain returned false.**

**Cause:** Error while setting up an  
oracle.toplink.sessions.entitymanager.EntityManagerFactory.

**Action:** Ensure the correct setup of the EntityManagerFactory: initializeFromMain method of the EntityContainer returns true.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**TOP-28005: An Exception was thrown in setup of EntityManager factory.**

**Cause:** Error during the setup of  
oracle.toplink.sessions.entitymanager.EntityManagerFactory.

**Action:** See the generated exception for the root cause.

**Level:** 1

---

**Type:** ERROR

**Impact:** Deployment

**TOP-28006: ClassNotFoundException: [{0}] specified in [{1}] property.**

**Cause:** Failure to find the class ClassName specified in the property propertyName.

**Action:** Ensure that the class exists and is on the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**TOP-28007: Failed to instantiate ServerPlatform of type [{0}] specified in [{1}] property.**

**Cause:** Failure to instantiate a server platform of type ServerPlatformType specified in the property propertyName.

**Action:** See the generated exception for the root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**TOP-72000: Error reading ejb-jar.xml file**

**Cause:** Failure to read an ejb-jar.xml file due to a java.io.IOException or javax.xml.parsers.ParserConfigurationException.

**Action:** See the generated exception for the root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**TOP-72001: ejb-jar.xml does not use expected doc type -//Sun Microsystems, Inc.//DTD Enterprise JavaBeans 2.0//EN**

**Cause:** Failure to parse the specified file because it did not use the expected doctype: -//Sun Microsystems, Inc.//DTD Enterprise JavaBeans 2.0//EN

**Action:** Verify that your ejb-jar.xml file uses the correct documentation type.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**TOP-72002: There was a concrete instance variable named "{0}" already defined on the class "{1}". Please either 1) remove this instance variable from the class, refresh in the MW, and update from the ejb-jar.xml again, or 2) remove the field from the ejb-jar.xml file and update again.**

**Cause:** There was a concrete instance variable variableName already defined on the class ClassName.

**Action:** Either remove this instance variable from the class, refresh in the TopLink Workbench, and update from the ejb-jar.xml file again, or remove the field from the ejb-jar.xml file and update again.

**Level:** 1

---

**Type:** ERROR

**Impact:** Deployment

**TOP-72003: A mapping for the field named "{0}" could not be created on the descriptor "{1}". Check to see that there are abstract getters and setters accessible for this field.**

**Cause:** A mapping for a field fieldName could not be created on the descriptor DescriptorName.

**Action:** Check to ensure that there are abstract get and set methods accessible for this field.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**TOP-72004: Neither local home nor remote home interface for the class "{0}" was found on the classpath. The finders for this class were not updated.**

**Cause:** Neither local home nor remote home interface for the class ClassName was found on the classpath. The finders for this class were not updated.

**Action:** Update the finders for this class; ensure that either local home or remote home interface for the class is on the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**TOP-72005: The finder method named "{0}" was not defined on a home interface for the entity "{1}". The finder was not updated.**

**Cause:** The finder method methodName was not defined on a home interface for the entity EntityName. The finder was not updated

**Action:** Define the finder method.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**TOP-72006: TopLink Mapping Workbench could not determine a project persistence type from the xml file.**

**Cause:** TopLink Workbench could not determine a project persistence type from the XML file.

**Action:** Specify the persistence type for your TopLink project.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**TOP-72007: Could not find a corresponding ejbSelect method in the bean class: "{0}". No information was updated for this query.**

**Cause:** Failure to find a corresponding ejbSelect method in the bean class ClassName. No information was updated for this query.

**Action:** Define ejbSelect method in your bean class.

---

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**TOP-72008: The EJB descriptor, "{0}", must have an EJB name specified.**

**Cause:** The EJB descriptor DescriptorName does not have an EJB name specified.

**Action:** In your EJB descriptor, specify an EJB name.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**TOP-72009: The EJB descriptor, "{0}", must have a primary key class specified.**

**Cause:** The EJB descriptor DescriptorName does not have a primary key class specified.

**Action:** In your EJB descriptor, specify a primary key class.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**TOP-72010: The EJB name, "{0}", was used by more than one descriptor. EJB names must be unique.**

**Cause:** The EJB name EJBName was used by more than one descriptor. EJB names must be unique.

**Action:** Ensure that the EJB name is specified in one and only one descriptor.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**TOP-72011: The element "{1}" cannot have an empty text attribute "{0}"**

**Cause:** An element elementName has an empty text attribute attributeName.

**Action:** Use a non-empty text attribute for the subelement.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**TOP-72012: There were multiple entities with the ejb-name "{0}" in the xml file.**

**Cause:** There are multiple entities with the same EJB bean name BeanName in the XML file.

**Action:** Use a unique EJB bean name for each entity.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**TOP-72013: The entity "{0}" did not have a valid cmp-version. The version must be "1.x" or "2.x".**

---

**Cause:** The entity EntityName does not have a valid cmp-version definition. The cmp-version must be 1.x or 2.x.

**Action:** Use a cmp-version value of 1.x or 2.x only.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**TOP-72014: The ejb-name "{0}" in the ejb-relationship-role "{1}" is not found in any entity of the xml file**

**Cause:** The EJB bean name BeanName in the ejb-relationship-role element is not found in the XML file.

**Action:** Use the EJB bean name of an existing entity for the ejb-relationship-role.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**TOP-72015: There was an invalid multiplicity in a relationship involving the mapping "{0}" in the descriptor "{1}". The multiplicity must be "One" or "Many".**

**Cause:** There was an invalid multiplicity value defined for a relationship involving the mapping Mapping Name in a descriptor DescriptorName. The multiplicity must be either One or Many.

**Action:** Use a multiplicity value of One or Many only.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**TOP-72016: The entity "{0}" did not have a valid persistence-type. The type must be "Bean" or "Container".**

**Cause:** The entity EntityName does not have a valid persistence type. The type must be either Bean or Container.

**Action:** Use a persistence-type value of Bean or Container only.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**TOP-72017: The query method-name "{0}" does not start with "find" or "ejbSelect". No information was updated for this query.**

**Cause:** The query method methodName does not start with find or ejbSelect. No information was updated for this query.

**Action:** Verify that the query method name starts with either find or ejbSelect.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**TOP-72018: TopLink Mapping Workbench requires that all entities in the xml file for this project have the same persistence-type and/or cmp-version. The project**

---

**will be set according to the persistence-type and/or cmp-version of the first entity in the file.**

**Cause:** Attempt to use a nonuniform persistence type for the TopLink Workbench project: TopLink Workbench requires that all entities in the XML file for this project have the same persistence-type and/or cmp-version. The project will be set according to the persistence-type and/or cmp-version of the first entity in the file.

**Action:** Provide all entities in the XML file for this project with the same persistence-type and/or cmp-version.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**TOP-72019: The project, "{0}", must have at least one EJB descriptor.**

**Cause:** The project ProjectName does not have an EJB descriptor: it must have at least one EJB descriptor.

**Action:** Provide an EJB descriptor for the project.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**TOP-72021: The class "{0}" could not be found on the classpath. A descriptor could not be created for it.**

**Cause:** The class ClassName could not be found on the classpath. A descriptor could not be created for it.

**Action:** Ensure that the class ClassName is on the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**TOP-72022: There is an element, "{1}", that does not have a required attribute, "{0}".**

**Cause:** There is an element that does not have a required attribute.

**Action:** Add the subelement to the parent element.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment

**TOP-72023: EntityBean {1} has an ABSTRACT setter with an EntityBean attribute type for attribute {0} but no corresponding CMR field.**

**Cause:** Entity bean BeanName has an abstract setter method with an EntityBean attribute type for attribute attributeName, but does not have a corresponding CMR field.

**Action:** Verify that all CMP entities have the same cmp-version value.

**Level:** 1

**Type:** ERROR

**Impact:** Deployment





---

## TPC-00001 to TPC-90022

**TPC-00001: The document root cannot be deleted.**

**Cause:** The user tried to delete the document root.

**Action:** Do not try to delete the document root.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00002: Failed to create folder "{0}".**

**Cause:** The user does not have permission to create a folder.

**Action:** Check user permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00003: Failed to create local directory "{0}".**

**Cause:** The user does not have permission to create the local directory.

**Action:** Check user permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00004: Failed to create team document directory item.**

**Cause:** The user does not have permission to create documents.

**Action:** Check user permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00005: Failed to delete team document.**

**Cause:** The document has already been deleted or the user does not have permission.

**Action:** Verify document existence and check user permissions.

**Level:** 1

---

**Type:** ERROR

**Impact:** Logging

**TPC-00006: Failed to download document "{0}".**

**Cause:** The download failed because of connection failures or the user does not have permission.

**Action:** Verify connectivity and check user permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00007: Failed to get document connector.**

**Cause:** Failed to get an instance of the document connector.

**Action:** Verify connector installation and check user permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00008: Failed to rename document item to "{0}".**

**Cause:** The user does not have permission to rename documents.

**Action:** Check user permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00009: Failed to show team document content.**

**Cause:** The user does not have permissions to view the document.

**Action:** Check user permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00010: Failed to upload team document.**

**Cause:** The user does not have permissions to upload team documents.

**Action:** Check user permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00011: Connector for "{0}" may not be properly installed. Use Check for Update to install or fix the problem.**

**Cause:** The connector is not properly installed or the user does not have permission.

**Action:** Verify the connector installation and the user permissions.

**Level:** 1

---

**Type:** ERROR

**Impact:** Logging

**TPC-00012: Work Item Connector Login Error.**

**Cause:** The user could not log in to the connector.

**Action:** Ensure the user credentials are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00013: Creating User Repository Error.**

**Cause:** The user does not have permission to create a repository.

**Action:** Check user permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00014: Failed to construct the connector.**

**Cause:** The connector parameters are incorrect.

**Action:** Verify the connector parameters in the administration screen.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00015: Failed to log in to "{0}" repository.**

**Cause:** Failed to access repository.

**Action:** Check connection and access permission.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00016: Missing the required user repository.**

**Cause:** Miss the required user repository.

**Action:** Add needed user repository.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00017: No item has been found with the specified ID. Enter a valid ID value.**

**Cause:** No item with the specified ID exists.

**Action:** Enter a valid ID value.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

---

**TPC-00018: Specify your username.**

**Cause:** The username cannot be empty.

**Action:** Provide data for the username.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00019: Specify your password.**

**Cause:** The password cannot be empty.

**Action:** Provide data for the password.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00020: Cannot save your account information to server. Contact your administrator.**

**Cause:** There is an issue with server connectivity or user credentials.

**Action:** Contact your administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00021: Update failed. Check field values and try again.**

**Cause:** Invalid values for some fields.

**Action:** Verify field values and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00022: Cannot delete a repository that is being used by any team(s). Make sure that no team is using the current repository.**

**Cause:** The repository is being used by one or more teams.

**Action:** Remove the repository from all teams.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00023: Cannot save the new repository "{0}". Make sure its name is unique.**

**Cause:** The repository name is not unique.

**Action:** Specify a unique repository name.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

---

**TPC-00024: Cannot update repository "{0}". Check your log file for details.**

**Cause:** TPC server has encountered problem during updating the repository. Check the server's log to find out what has caused the problem.

**Action:** Check your log file for details.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00025: Create new repository error.**

**Cause:** The repository parameters are incorrect.

**Action:** Verify the repository parameters.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00026: Delete repository error.**

**Cause:** The user does not have permission to delete the repository.

**Action:** Check user permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00027: Repository Access Error.**

**Cause:** The user credentials may not be correct or there may be connectivity issues.

**Action:** Verify the user credentials and the connectivity of the repository.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00028: Repository field cannot be empty.**

**Cause:** The repository name cannot be empty.

**Action:** Provide a name for the repository.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00029: Test failed.**

**Cause:** The username and password are not correct.

**Action:** Provide a valid username and password.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

---

**TPC-00030: Update User Repository Account Failure.**

**Cause:** Failed to update user repository account.

**Action:** Check account parameters.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00031: Repository field cannot be empty.**

**Cause:** The repository field cannot be empty.

**Action:** Provide repository name.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00032: Update repository error.**

**Cause:** The repository data is invalid.

**Action:** Verify the repository data.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00033: Repository server name cannot be changed once it is committed.**

**Cause:** The repository server name cannot be changed once it is created.

**Action:** Do not change repository server name.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00034: Create repository server error.**

**Cause:** The repository server parameter values are incorrect.

**Action:** Verify the parameter values.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00035: Rename repository server error**

**Cause:** The repository server name is invalid.

**Action:** Verify the repository server name.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00036: Repository server "{0}" is already used. Choose a different name.**

**Cause:** The specified repository server name is already in use.

---

**Action:** Choose a different name.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00037: Create new role error.**

**Cause:** The role name is invalid.

**Action:** Verify that the name of the role is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00038: Name field cannot be empty.**

**Cause:** The name field cannot be empty.

**Action:** Enter data in name field.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00039: Failed to delete role.**

**Cause:** The user does not have permission to delete the role.

**Action:** Check user permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00040: Failed to delete role "{0}". Make sure no team member uses this role.**

**Cause:** The role is already associated to some users.

**Action:** Remove the role from all users.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00041: You can only delete a team that does not have any member. Make sure there is no user associated with this team.**

**Cause:** The team has members associated with it.

**Action:** Remove all members from the team in order to delete it.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00042: You can only delete a team that does not have any subteam. Make sure there is no team under this team.**

**Cause:** The team has teams beneath it in the hierarchy.

---

**Action:** Remove all teams below the specified team.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00043: Cannot save the new team "{0}". Make sure its name is unique.**

**Cause:** The team name is not unique.

**Action:** Enter a unique name for the team.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00044: Failed to Create Team.**

**Cause:** Some data fields are invalid.

**Action:** Verify the team fields.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00045: Failed to Delete Team.**

**Cause:** The user may not have permission to delete teams.

**Action:** Check user permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00046: Team name cannot be empty.**

**Cause:** The team name is empty.

**Action:** Provide a value for the team name.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00047: Create new team error.**

**Cause:** Some data fields are invalid.

**Action:** Verify the team fields.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00048: Update team error.**

**Cause:** Some data fields are invalid.

**Action:** Verify the team fields.



---

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00049: Create new user error.**

**Cause:** Some data fields are invalid.

**Action:** Verify the user fields.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00050: You can only delete a user that does not belong to any team. Make sure the current user is not associated with any team.**

**Cause:** The specified user was associated with a team, so deletion was not allowed.

**Action:** Remove the user from all teams.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00051: Failed to Delete User.**

**Cause:** The user did not have the permissions required to delete other users.

**Action:** Check user permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00052: Username, password and email field cannot be empty.**

**Cause:** Empty username, password or email field.

**Action:** Enter data for all fields.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00053: Login exists. Use different login.**

**Cause:** The login ID already exists.

**Action:** Provide a unique login ID.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00054: Failed to open file "{0}".**

**Cause:** The connection failed or the user does not have permission.

**Action:** Verify connectivity and check user permissions.

---

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00055: Failed to change Team Server password.**

**Cause:** Server connectivity issue.

**Action:** Verify server connectivity or contact your administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00056: The new password does not match the retyped password.**

**Cause:** The new password does not match the retyped password.

**Action:** Verify the passwords entered.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00057: The old password entered is incorrect.**

**Cause:** The old password entered is incorrect.

**Action:** Provide the correct password.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00058: Failed to create buddy "{0}".**

**Cause:** Server connectivity issue.

**Action:** Verify server connectivity or contact your administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00059: Buddy "{0}" already exists.**

**Cause:** The specified buddy already exists.

**Action:** Refresh your buddy list.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00060: Fail to create group "{0}" on the server.**

**Cause:** Server connectivity issue or the group name is invalid.

**Action:** Verify server connectivity and verify that the group name is valid.

**Level:** 1

**Type:** ERROR

---

**Impact:** Logging

**TPC-00061: Make sure you enter a valid account name before clicking the Add button.**

**Cause:** The account name is invalid.

**Action:** Verify the account name.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00062: Failed to connect to chat server "{0}".**

**Cause:** The connection information is incorrect.

**Action:** Verify the connection information.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00063: Failed to log in to chat server "{0}".**

**Cause:** The login credentials are incorrect.

**Action:** Verify the login credentials and connection information.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00064: Failed to save the work item.**

**Cause:** Some of the workitem field values are invalid.

**Action:** Verify the input data.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00065: Failed to update password.**

**Cause:** The password is invalid.

**Action:** Ensure the password is 12 characters or less.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**TPC-00066: Failed to log in to team server.**

**Cause:** The login credentials are incorrect.

**Action:** Verify the login credentials.

**Level:** 1

**Type:** ERROR

**Impact:** Session

---

**TPC-00067: Invalid username and/or password.**

**Cause:** Invalid username and/or password.

**Action:** Verify the login name and password.

**Level:** 1

**Type:** ERROR

**Impact:** Session

**TPC-00068: Invalid server name and/or server port.**

**Cause:** Invalid server name and/or server port.

**Action:** Verify the server name and/or server port.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00069: Failed to update query "{0}".**

**Cause:** The query specification is incorrect.

**Action:** Verify the query fields are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00070: Failed to create new query "{0}".**

**Cause:** The query specification is incorrect.

**Action:** Verify the query fields are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00071: Cannot save the query. Make sure the query is valid.**

**Cause:** The query specification is incorrect.

**Action:** Verify the query fields are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00072: Query "{0}" already exists. Provide another name.**

**Cause:** The specified query already exists.

**Action:** Provide a unique name for the query.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00073: Duplicate Tag Name Error.**

**Cause:** The tag name already exists.

---

**Action:** Provide a unique name for the tag.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00074: Failed to add tag to the current work item.**

**Cause:** Connectivity issue.

**Action:** Verify connectivity or contact your administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00075: Failed to create new tag.**

**Cause:** The user does not have permission to create new tags.

**Action:** Check user permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00076: Missing Required Information.**

**Cause:** Missing Required Information.

**Action:** Provide tag name and description.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00077: Tag "{0}" already exists.**

**Cause:** The tag name already exists.

**Action:** Provide a unique tag name.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00078: No result found. Either the tag used has been changed or there is no item associated with the tag. Close this window and try again.**

**Cause:** The tag used has been changed or there is no item associated with the tag.

**Action:** Select a different tag.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00079: Failed to delete the context.**

**Cause:** Connectivity issue.

**Action:** Verify server connectivity or contact your administrator.

---

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00080: There is no context being saved.**

**Cause:** There are no open files to be saved to the context.

**Action:** Open files in the editor and then save the context.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00081: Failed to update the context.**

**Cause:** The context files may not be present in the local file system.

**Action:** Restore the file system or delete the context.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00082: Restore context exception: "{0}".**

**Cause:** An error was encountered during restoring the context. Detailed exception should have been provided in the message dialog.

**Action:** Check the log files.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00083: Cannot retrieve context.**

**Cause:** The context was not properly stored.

**Action:** Delete the context and reopen the files manually.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00084: Save context exception: "{0}".**

**Cause:** An error was encountered during saving the context. Detailed exception should have been provided in the message dialog.

**Action:** Check the log files.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00085: Cannot find document "{0}" to add.**

**Cause:** The document may have been removed from the content store.

**Action:** Verify the document exists in the content store and contact your administrator.

---

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00086: Failed to download attachment "{0}".**

**Cause:** Connectivity issue.

**Action:** Verify the connectivity and retry or contact your administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00087: Failed to update attachment "{0}".**

**Cause:** Connectivity issue.

**Action:** Verify the connectivity and retry or contact your administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00088: Failed to update attributes on attachment "{0}". Error: {1}.**

**Cause:** Connectivity issue.

**Action:** Verify the connectivity and retry or contact your administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00089: Failed to upload attachment "{0}". Error: {1}.**

**Cause:** Connectivity issues or the upload directory is not properly set.

**Action:** Verify the connectivity and the upload directory.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00090: Cannot create the work item relationship.**

**Cause:** Connectivity issues or the specified work item does not exist.

**Action:** Verify the connectivity and ensure the work item specified was not deleted.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00091: Connector "{0}" is installed but its version "{1}" is not supported.**

**Supported version is "{2}". Use Check for Update to upgrade.**

**Cause:** Connector version mismatched.

**Action:** Use Check for Update to upgrade.

---

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00092: Cannot update team query "{0}".**

**Cause:** User may not have permission to update team query.

**Action:** Check permission to update team query.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00093: You can only delete a team that does not have any repository. Make sure there is no repository associated with this team.**

**Cause:** The team has repositories associated with it.

**Action:** Remove all repositories from the team in order to delete it.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00094: Failed to Update User.**

**Cause:** The user does not have permissions to update this user.

**Action:** Check user permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00095: Failed to delete team member "{0}".**

**Cause:** The team member may be in use.

**Action:** Remove all associations to the team member.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00096: Failed to delete team repository for team "{0}" using repository "{1}".**

**Cause:** The user does not have permissions to update the team repository.

**Action:** Check user permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00097: Failed to create team repository for team "{0}" using repository "{1}".**

**Cause:** The user does not have permissions to create the team repository.

**Action:** Check user permissions.

**Level:** 1



---

**Type:** ERROR

**Impact:** Logging

**TPC-00098: Failed to delete team parameter for team "{0}" using repository "{1}".**

**Cause:** The user does not have permissions to delete the parameter.

**Action:** Check user permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00099: Failed to update team parameter for team "{0}" using repository "{1}".**

**Cause:** The user does not have permissions to update the parameter.

**Action:** Check user permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00100: Failed to create team member "{0}".**

**Cause:** Some required property of the team member may be missing.

**Action:** Make sure the user associated with the team member is specified correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00101: Cannot grant privilege "{0}" to role "{1}". Make sure it does not exist.**

**Cause:** The association is not unique.

**Action:** Specify a unique association for the role.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00102: Cannot revoke privilege "{0}" from role "{1}". Make sure it exists.**

**Cause:** The association may not exist.

**Action:** Specify correct association to delete. This may be an error in the application.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00103: Cannot update privilege "{0}" for role "{1}".**

**Cause:** The association may not exist.

**Action:** Specify correct association to update. This may be an error in the application.

**Level:** 1

---

**Type:** ERROR  
**Impact:** Logging  
**TPC-00104: Cannot create role "{0}".**  
**Cause:** The role may exist.  
**Action:** Specify unique role to create.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Logging  
**TPC-00105: Cannot update role "{0}".**  
**Cause:** The role may not exist.  
**Action:** Specify correct role to update. This may be an error in the application.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Logging  
**TPC-00106: Cannot grant privilege "{0}" for login "{1}".**  
**Cause:** The association is not unique.  
**Action:** Specify a unique association for the login.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Logging  
**TPC-00107: Cannot revoke privilege "{0}" from login "{1}".**  
**Cause:** The association may not exist or the login may not exist.  
**Action:** Specify correct login.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Logging  
**TPC-00108: Cannot update team "{0}".**  
**Cause:** The team information may not be specified properly.  
**Action:** Specify correct team information.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Logging  
**TPC-00109: Cannot delete team "{0}".**  
**Cause:** The team may not exist.  
**Action:** Specify correct team.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Logging

---

**TPC-00110: Invalid email address. Specify valid email address.**

**Cause:** Email address specified is invalid.

**Action:** Specify valid email address.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00111: You have lost connection to TPC server. "{0}" Fix the problem and retry.**

**Cause:** You have lost connection to the server for the reason mentioned.

**Action:** Log in to TPC server.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00112: Server did not send valid certificate.**

**Cause:** Invalid certificate from server caused by the specified reason.

**Action:** Verify that you have specified correct server name and/or server port.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00113: You need a valid certificate to log in.**

**Cause:** User rejected a certificate sent by TPC server. The certificate is needed in SSL connection mode.

**Action:** Verify and accept the certificate before you connect.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00114: Unexpected problem during accepting the certificate. Try again.**

**Cause:** The certificate is either empty or there was a problem in accepting the certificate.

**Action:** Verify and accept the certificate again.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00115: Failed to delete attachment "{0}". Error: {1}.**

**Cause:** The specified attachment cannot be found in the content store.

**Action:** Verify the document exists in the content store and contact your administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

---

**TPC-00116: Password cannot be reused.**

**Cause:** The old password cannot be reused.

**Action:** Specify password different than the old one.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00117: You must specify a new password to commit. Click Cancel otherwise.**

**Cause:** You either did not type in a new password or specify a blank new password.

**Action:** Specify a new password to commit and it cannot be blank. Hit Cancel otherwise.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00118: User canceled.**

**Cause:** User has canceled login.

**Action:** None.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-00119: Unable to establish connection with server using this url: {0}.**

**Cause:** Failed to log in to specified server URL.

**Action:** Specify correct server URL.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-60000: Team Productivity Center services initialized.**

**Cause:** Service started normally.

**Action:** No action needed.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Threads

**TPC-60001: Cannot insert record with blank ID.**

**Cause:** The record has a blank ID.

**Action:** Enter a value for the ID.

**Level:** 1

**Type:** WARNING

**Impact:** Threads

---

**TPC-60002: The record you want to update does not exist.**

**Cause:** The record does not exist.

**Action:** Refresh your data.

**Level:** 1

**Type:** WARNING

**Impact:** Threads

**TPC-60003: Cannot retrieve a record with a null ID.**

**Cause:** The ID is null.

**Action:** Make sure the record has a valid ID.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**TPC-60004: Cannot retrieve a record with a null name.**

**Cause:** The Item name is null.

**Action:** Make sure the record has a valid name.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**TPC-60005: Cannot create a record with a null or empty password.**

**Cause:** Password for this record is either null or empty.

**Action:** Make sure the record has a valid password.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**TPC-60006: Username or password is invalid.**

**Cause:** Invalid username and/or password.

**Action:** Verify the login name and password.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**TPC-60007: Team Productivity Center services failed to start.**

**Cause:** Cannot find required startup credentials.

**Action:** Verify the server was installed correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**TPC-60008: Cannot delete record.**

**Cause:** The server received an error during deletion of the record.

---

**Action:** Verify the record is not being used by others.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**TPC-60009: Cannot connect to an inactive account.**

**Cause:** You are trying to connect using account that has been deactivated.

**Action:** Contact TPC Administrator to activate it.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**TPC-60010: TPC Server requires authentication for this request. Authenticate with the server, or upgrade your client to fix the problem.**

**Cause:** You either did not authenticate with the server, or your client version is no longer supported by the server.

**Action:** Authenticate with the server, or upgrade your client to correct the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**TPC-60011: Cannot initialize session in the webservice context.**

**Cause:** Internal error on the server.

**Action:** Contact OTPC Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**TPC-60012: This request is not supported by the server.**

**Cause:** You have requested a service that is not supported by the server.

**Action:** Contact TPC Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**TPC-60013: TPC client version "{0}" is not supported. Supported version is "{1}" or higher. Use Check for Update to upgrade your client.**

**Cause:** Client and Server versions mismatched.

**Action:** Use Check for Update to upgrade the client.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

---

**TPC-60014: This client is no longer supported. Use Check for Update to install or upgrade TPC client to "{0}" or higher to fix the problem.**

**Cause:** Your client is not recognized by the server either because it is invalid or no longer supported.

**Action:** Use Check for Update to install or upgrade the TPC client.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-60015: Server version does not exist.**

**Cause:** This is an internal error caused by missing a server version from the database.

**Action:** Contact TPC Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-60016: TPC Server has terminated your session. Rlogin to fix the problem.**

**Cause:** TPC server has terminated client session either unexpectedly or for scheduled maintenance.

**Action:** Rlogin to the server once it becomes available again. Contact TPC Administrator for the availability of the server.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**TPC-60017: Service is about to shut down...**

**Cause:** One of the TPC service is about to shut down.

**Action:** Save all works and log off.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**TPC-90001: Test failed. Make sure your username and password are correct.**

**Cause:** Test failed.

**Action:** Make sure your username and password are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-90002: Cannot create connector record in the target database. Make sure the specified connector jar or bundle file is correct.**

**Cause:** Cannot create connector record in the target database.

**Action:** Make sure the specified connector jar or bundle file is correct.

**Level:** 1

---

Type: ERROR

Impact: Logging

**TPC-90003: Incorrect connector definition. Check the connector.xml file and make sure all required parameters are defined correctly.**

**Cause:** Incorrect connector definition.

**Action:** Check the connector.xml file and make sure all required parameters are defined correctly.

Level: 1

Type: ERROR

Impact: Logging

**TPC-90004: The local file name specified is not a jar or zip file. Select the correct file.**

**Cause:** The local file name specified is not a jar or zip file.

**Action:** Select the correct file.

Level: 1

Type: ERROR

Impact: Logging

**TPC-90005: Cannot find the file to install the selected connector.**

**Cause:** Cannot find the file to install the selected connector.

**Action:** Make sure connector jar files are properly located.

Level: 1

Type: ERROR

Impact: Logging

**TPC-90006: Cannot copy otpc.war file. Make sure the destination folder is not read only.**

**Cause:** Cannot copy otpc.war file.

**Action:** Make sure the destination folder is not read only.

Level: 1

Type: ERROR

Impact: Logging

**TPC-90007: Failed to create temporary directory.**

**Cause:** Failed to create temporary directory.

**Action:** Check permission and space to create installation directory.

Level: 1

Type: ERROR

Impact: Logging

**TPC-90008: Failed to deploy Team Productivity Center server.**

**Cause:** Failed to deploy Team Productivity Center server.

**Action:** Check permission and space for deployment directory.



---

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-90009: Failed to install the selected connector.**

**Cause:** Failed to install the selected connector.

**Action:** Check permission and space for installation directory and file.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-90010: Installation failed. Review the system log.**

**Cause:** Installation failed.

**Action:** Review the system log.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-90011: The specified application server directory is not valid. Make sure the folder exists and is writable.**

**Cause:** The specified Application Server directory is not valid.

**Action:** Make sure the folder exists and is writable.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-90012: The otpc.war file specified does not function properly. The install image may be corrupted. Download a working copy of the installer.**

**Cause:** The otpc.war file specified does not function properly.

**Action:** The install image may be corrupted. Download a working copy of the installer.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-90013: JDBC Driver library path is not correct.**

**Cause:** JDBC Driver library path is not correct.

**Action:** Correct JDBC Driver library path.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-90014: Failed to add JDBC driver library to system class path.**

**Cause:** Failed to add JDBC driver library to system class path.

**Action:** Review system log.

---

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-90015: JDBC driver class cannot be found.**

**Cause:** JDBC driver class cannot be found.

**Action:** Make sure jdbc driver class is in appropriate jar file.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-90016: No component has been selected. Select the components to install.**

**Cause:** No component has been selected.

**Action:** Select the components to install.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-90017: SQL Exception.**

**Cause:** SQL Exception.

**Action:** Check system log.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-90018: Cannot create database tables or populate seed data. Review the system log.**

**Cause:** Cannot create database tables or populate seed data.

**Action:** Review the system log.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-90019: Cannot connect to the specified database. Make sure all parameters are set correctly.**

**Cause:** Cannot connect to the specified database.

**Action:** Make sure all parameters are set correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-90020: The file otpc.war already exists and cannot be overwritten. Make sure it is overwritable.**

**Cause:** The file otpc.war already exists and cannot be overwritten.

**Action:** Make sure otpc.war is overwritable.

---

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-90021: Update failed. Check field values and try again.**

**Cause:** Update failed.

**Action:** Check field values and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**TPC-90022: The version to be installed "{0}" is not newer than the current version "{0}".**

**Cause:** The version for installation or upgrade is the same or lower than the current installation.

**Action:** Check for new version.

**Level:** 1

**Type:** ERROR

**Impact:** Logging



---

---

## TRS-10000 to TRS-20017

**TRS-10000: TRSConnectionMgr: DataSource is null.**

**Cause:** DataSource is not set.

**Action:** Set DataSource first using MBeans.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TRS-10001: Dispatcher failed to get jobs. {0}**

**Cause:** SQLException

**Action:** Check database.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10002: {0} failed to check job status. {1}**

**Cause:** SQLException

**Action:** Check database

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10003: TxnReplayer URL:{0} is malformed. Replay item cannot be processed. {1}**

**Cause:** Malformed TxnReplayer URL

**Action:** Change TxnReplayer URL specified in MBean or web.xml

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TRS-10004: Cannot open TxnReplayer URL:{0}. Replay item cannot be processed. {1}**

**Cause:** TxnReplayer might not be running

**Action:** Check network. Make sure TxnReplayer is running

**Level:** 1

---

Type: ERROR

Impact: Network

**TRS-10005: Dispatcher encountered an error during update of the REPLAY\_USERS table. {0}**

Cause: SQLException

Action: Check database

Level: 1

Type: ERROR

Impact: Data

**TRS-10006: JOB FAILED: clientId = {0}, JobId ={1}.**

Cause: Job might be hanging or crashed.

Action: Consult administrator.

Level: 1

Type: ERROR

Impact: Data

**TRS-10007: {0} failed to get database connection.**

Cause: Database related

Action: Check database, or check DataSource.

Level: 1

Type: ERROR

Impact: Data

**TRS-10008: Dispatcher failed to prepare SQL Statement. {0}**

Cause: SQLException

Action: Check database

Level: 1

Type: ERROR

Impact: Data

**TRS-10009: Error creating DispatcherRuntimeInfo MBean. {0}**

Cause: Open MBean metadata information cannot be constructed.

Action: Check MBean validity constraints.

Level: 1

Type: ERROR

Impact: Data

**TRS-10010: Data source name: {0} cannot be resolved. Dispatcher thread will not start**

Cause: Cannot resolve DataSource name

Action: Check DataSource name

Level: 1

---

**Type:** ERROR  
**Impact:** Configuration

**TRS-10011: {0} - error registering. {1}**  
**Cause:** MBean might already exist, or other reasons  
**Action:** Ignore if MBean already exists. Otherwise consult administrator.

**Level:** 1  
**Type:** ERROR  
**Impact:** Data

**TRS-10012: {0} - error querying number of jobs. {1}**  
**Cause:** SQLException  
**Action:** Check database

**Level:** 1  
**Type:** ERROR  
**Impact:** Data

**TRS-10013: {0} - error closing resultset. {1}**  
**Cause:** SQLException  
**Action:** Check database

**Level:** 1  
**Type:** ERROR  
**Impact:** Data

**TRS-10014: {0} - error closing statement. {1}**  
**Cause:** SQLException  
**Action:** Check database

**Level:** 1  
**Type:** ERROR  
**Impact:** Data

**TRS-10015: {0} - error querying replay items. {1}**  
**Cause:** SQLException  
**Action:** Check database

**Level:** 1  
**Type:** ERROR  
**Impact:** Data

**TRS-10016: {0} - error querying replay users. {1}**  
**Cause:** SQLException  
**Action:** Check database

**Level:** 1  
**Type:** ERROR  
**Impact:** Data

---

**TRS-10017: {0} - error querying replay types. {1}**

**Cause:** SQLException

**Action:** Check database

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10018: DispatcherRuntimeInfo - error creating composite item. {0}**

**Cause:** Open MBean related OpenDataException

**Action:** Consult administrator

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10019: DispatcherRuntimeInfo - error creating composite job. {0}**

**Cause:** Open MBean related OpenDataException

**Action:** Consult administrator

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10020: {0} - error inserting replay type. {1}**

**Cause:** SQLException

**Action:** Check database

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10021: {0} - error updating replay type. {1}**

**Cause:** SQLException

**Action:** Check database

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10022: {0} - error removing replay items. {1}**

**Cause:** SQLException

**Action:** Check database

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10023: {0} - error removing replay jobs. {1}**

**Cause:** SQLException



---

**Action:** Check database

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10024: {0} - error removing replay users. {1}**

**Cause:** SQLException

**Action:** Check database

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10025: {0} - error in database connection operations: commit, rollback or setAutoCommit. {1}**

**Cause:** SQLException

**Action:** Check database

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10026: {0} - error loading settings. {1}**

**Cause:** Error related to preference node

**Action:** Consult administrator

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10027: {0} - Cannot resolve DataSource Name {1}.**

**Cause:** Cannot resolve DataSource

**Action:** Check DataSource name

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TRS-10028: {0} - DataSource name is null**

**Cause:** DataSource name is null

**Action:** Check DataSource name in MBean or web.xml

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**TRS-10029: {0} - error inserting replay items. {1}**

**Cause:** SQLException

**Action:** Check database

---

**Level:** 1  
**Type:** ERROR  
**Impact:** Data  
**TRS-10030: {0} - Cannot find keystore password from Credential Store.**  
**Cause:** Cannot find keystore password  
**Action:** Consult administrator

**Level:** 1  
**Type:** ERROR  
**Impact:** Security  
**TRS-10031: TRSConnectionMgr: fail to get database connection. {0}**  
**Cause:** SQLException  
**Action:** Check database

**Level:** 1  
**Type:** ERROR  
**Impact:** Data  
**TRS-10032: Cannot access Credential Store.**  
**Cause:** Credential store is not existing  
**Action:** Consult administrator

**Level:** 1  
**Type:** ERROR  
**Impact:** Security  
**TRS-10033: Fail to get private key.**  
**Cause:** cannot get private key  
**Action:** Check keystore, keystore password, certificate alias.

**Level:** 1  
**Type:** ERROR  
**Impact:** Security  
**TRS-10034: Client {0}, Replay item #{1}: Cannot update item status to {2}. {3}**  
**Cause:** SQLException  
**Action:** Check database

**Level:** 1  
**Type:** ERROR  
**Impact:** Data  
**TRS-10035: Client {0}, Replay item #{1}: Dependency not met. Parent item #{2} status is {3}.**  
**Cause:** Parent item status is not DONE  
**Action:** Check parent item status

**Level:** 1

---

**Type:** ERROR  
**Impact:** Data  
**TRS-10036: Client {0}, Replay item #{1}: Invalid Dependency #{2}.**  
**Cause:** DEPENDENCY value is not valid  
**Action:** Check DEPENDENCY column for this item in table  
**Level:** 1  
**Type:** ERROR  
**Impact:** Data  
**TRS-10037: Client {0}, Replay item #{1}: Fail to parse parameter. {2}**  
**Cause:** Cannot parse xml parameter  
**Action:** Check PARAMS column for this item in table  
**Level:** 1  
**Type:** ERROR  
**Impact:** Data  
**TRS-10038: Client {0}, Replay item #{1}: Error in retrieving password. {2}**  
**Cause:** Cannot get user's password  
**Action:** Check security configuration  
**Level:** 1  
**Type:** ERROR  
**Impact:** Security  
**TRS-10039: Client {0}, Replay item #{1}: Cannot find replay type class. {2}**  
**Cause:** Replay type class is missing  
**Action:** Check to make sure the class library is available  
**Level:** 1  
**Type:** ERROR  
**Impact:** Data  
**TRS-10040: Client {0}, Replay item #{1}: Cannot instantiate replay type class. {2}**  
**Cause:** Replay type class cannot be instantiated  
**Action:** Class might be an interface or abstract  
**Level:** 1  
**Type:** ERROR  
**Impact:** Data  
**TRS-10041: Client {0}, Replay item #{1}: Cannot find method with the right signature. {2}**  
**Cause:** No method available with the specified signature  
**Action:** Check parameter provided in REPLAY\_ITEM table  
**Level:** 1  
**Type:** ERROR

---

**Impact:** Data

**TRS-10042: Client {0}, Replay item #{1}: Invocation access failure. {2}**

**Cause:** Replay type method cannot be invoked

**Action:** The method does not have access to the definition of the specified class, field, method or constructor

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10043: Client {0}, Replay item #{1}, Calling Method = {2}, Class = {3}, Parameters = {4}: Invocation target failure. {5}**

**Cause:** Replay type class cannot be invoked

**Action:** The invoked method throws an exception

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10044: Client {0}, Replay item #{1}: Unexpected exception. {2}**

**Cause:** not known

**Action:** Check the error stack

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10045: Client {0}, Replay item #{1}: Unexpected error. {2}**

**Cause:** not known

**Action:** Check the error stack

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10046: Query pending replay items for client {0} failed. {1}**

**Cause:** SQLException

**Action:** Check database

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10047: Job #{0} for client {1} caught unexpected exception - {2}**

**Cause:** The job is possibly determined dead by dispatcher or it has encountered other errors.

**Action:** Check the error stack

**Level:** 1

**Type:** ERROR

---

**Impact:** Data

**TRS-10048: Cannot update job status to {0} for job id {1}.**  
**Cause:** SQLException  
**Action:** Check database

**Level:** 1  
**Type:** ERROR  
**Impact:** Data

**TRS-10049: Public key encryption is not set up properly. The feature is disabled.**  
**Cause:** Encryption configuration is not set up properly.  
**Action:** Check public key encryption setup.

**Level:** 1  
**Type:** ERROR  
**Impact:** Security

**TRS-10050: Default schema has not been set for user {0}, job {1}.**  
**Cause:** no default schema  
**Action:** Set default schema in MBean

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**TRS-10051: Caught RejectedExecutionException for user {0}, job {1}.**  
**Cause:** The job cannot be accepted for execution.  
**Action:** Check thread pool

**Level:** 1  
**Type:** ERROR  
**Impact:** Configuration

**TRS-10052: Thread pool is shut down for user {0}, job {1}.**  
**Cause:** Thread pool is shut down.  
**Action:** Restart application.

**Level:** 1  
**Type:** ERROR  
**Impact:** Threads

**TRS-10053: Missing ResourceBundle: {0}.**  
**Cause:** ResourceBundle is missing  
**Action:** Check if resourcebundle is available

**Level:** 1  
**Type:** ERROR  
**Impact:** Data

**TRS-10054: Client {0}, Replay item #{1}: Error processing the item.**

---

**Cause:** Exception happened during processing this item  
**Action:** Check log for errors logged before  
**Level:** 1  
**Type:** ERROR  
**Impact:** Data

**TRS-10055: Query outstanding replay items for client {0} failed. {1}**  
**Cause:** SQLException  
**Action:** Check database  
**Level:** 1  
**Type:** ERROR  
**Impact:** Data

**TRS-10056: Worker servlet detects job {0} for client {1} has unexpected status. The job is not executed.**  
**Cause:** The job is determined dead by dispatcher, so it is not executed.  
**Action:** Adjust failure recovery timeout if this error happens very frequently.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Data

**TRS-10057: {0}: Failed to enable auto archive of replay jobs and replay items. {1}**  
**Cause:** IllegalArgumentException  
**Action:** Check auto archive attributes  
**Level:** 1  
**Type:** ERROR  
**Impact:** Data

**TRS-10058: {0}: Failed to disable auto archive of replay jobs and replay items. {1}**  
**Cause:** IllegalArgumentException  
**Action:** Make sure auto archive was previously enabled  
**Level:** 1  
**Type:** ERROR  
**Impact:** Data

**TRS-10059: Failed to create archive file {0}. {1}**  
**Cause:** Exception happened during creation of archive file  
**Action:** Check database and make sure disk is not full  
**Level:** 1  
**Type:** ERROR  
**Impact:** Data

**TRS-10060: Failed to get value of attribute {0}.**  
**Cause:** Failed to get MBean attribute value

---

**Action:** Make sure attribute name is correct

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10061: Failed to set attribute {0} to {1}.**

**Cause:** Failed to set MBean attribute value

**Action:** Make sure attribute name and value are correct

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10062: Database operation failed after retrying. Number of retries is {0}.**

**Cause:** Database failure

**Action:** Check database.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10063: Exception caught. Exiting Dispatcher thread.**

**Cause:** Application is stopped or database failure.

**Action:** If it is database failure, check database.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**TRS-10064: Job Timeout triggered for client {0} for job {1} with status {2}. Updated time {3}, Timeout Value {4}**

**Cause:** The job has been in the present state for more than the timeout value.

**Action:** Adjust failure recovery timeout if this error happens very frequently.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10065: Failed to recover job {0} for client {1}**

**Cause:** Database error may have occurred while updating job status to error.

**Action:** Check database connections.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10066: Failed to query for the last processed item for client {0} and job {1}**

**Cause:** Database error may have occurred while querying for replay items.

**Action:** Check database connections.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10067: No items have been updated for client {0}**

**Cause:** The item has been in the present state for more than the timeout value.

**Action:** Adjust item processing timeout if this error happens very frequently.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10068: Failed to recover replay item for client {0} job {1}**

**Cause:** Database error may have occurred while updating replay item status.

**Action:** Check database connections.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10069: Received HTTP error code {0} for request {1}**

**Cause:** Some error has occurred in the TxnReplayer component.

**Action:** Check log for errors logged before.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10070: Cannot persist settings change for key: {0}, value: {1}**

**Cause:** Some error has occurred in Java preference node persistent storage.

**Action:** Check default Java preference node storage location for your system.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10071: Client {0}, Replay item #{1}: Custom Java class {2} cannot be found**

**Cause:** Custom Java class is missing

**Action:** Check to make sure the custom Java class library is available

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10072: Client {0}, Replay item #{1}: Invalid parameter value {2} for the {3} of type {4} has been detected**

**Cause:** Parameter value is not valid

**Action:** Check PARAMS column for this item in table

**Level:** 1



---

**Type:** ERROR

**Impact:** Data

**TRS-10073: Client {0}, Replay item #{1}: Invalid parameter value for the {2} of type {3} has been detected. {4}**

**Cause:** Parameter value is not valid

**Action:** Check PARAMS column for this item in table

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10074: Client {0}, Replay item #{1}: The value {2} of type char is empty**

**Cause:** Parameter value is not valid

**Action:** Check PARAMS column for this item in table

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10075: Client {0}, Replay item #{1}: Invalid parameter value {2} {3} of type boolean has been detected**

**Cause:** Parameter value is not valid

**Action:** Check PARAMS column for this item in table

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10076: Client {0}, Replay item #{1}: NULL is not a valid parameter value for the {2} of type {3}**

**Cause:** Parameter value is not valid

**Action:** Check PARAMS column for this item in table

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10077: Cannot get Response from {0}. Replay item cannot be processed. {1}**

**Cause:** TxnReplayer might not be running

**Action:** Check network. Make sure TxnReplayer is running

**Level:** 1

**Type:** ERROR

**Impact:** Network

**TRS-10078: Client {0}, Replay item #{1}: the replay type has an invalid PASSWORD\_TYPE value {2}.**

**Cause:** Invalid PASSWORD\_TYPE in REPLAY\_TYPE table

**Action:** Provide valid value for the PASSWORD\_TYPE column of the corresponding replay type in the REPLAY\_TYPE table

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10079: Client {0}, Replay Item {1}: PARAMS column in REPLAY\_ITEM table cannot be null or empty.**

**Cause:** The PARAMS column in REPLAY\_ITEM table is null or empty

**Action:** The PARAMS should have a value

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10080: TRS cannot publish the business event.**

**Cause:** Client {0}, Item {1}: The event publication failed

**Action:** Check the following: (1) the configuration (for example datasource) for event publication; (2)check the event payload; (3)check the DOM parser specified

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-10081: Cannot parse property {0} for Replay type {1}. The property will be ignored.**

**Cause:** The TYPE\_PROPERTIES value for the replay type is in wrong format.

**Action:** Verify the value is a single string with a sequence of name value pairs, for example, "name1=value1;name2=value2;name3=value3;..."

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-19000: Entity Object {0} with key {1} not found.**

**Cause:** The entity object row is not found in the database.

**Action:** Please check if the transaction needs to be changed and resubmitted.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-19001: Cannot find attribute {0} in Entity Object {1}.**

**Cause:** The definition of attribute is not found in the entity object.

**Action:** Please make sure that the mobile entity object and server entity object have consistent attribute definitions.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**TRS-19002: Entity Object {0} with key {1} has an update conflict on attribute {2}. Current server-side value is ({3}), client-side old value is ({4}) and new value is ({5}).**

**Cause:** The server value is different from the client's old value. Some other transaction(s) might have updated the server value since client's last synchronization.

**Action:** Please check if the transaction needs to be changed and resubmitted.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**TRS-20008: The system property {0} has value ({1}), which is different from the expected value ({2}).**

**Cause:** The Java VM does not have the system property needed to support full features of TRS.

**Action:** Set the property or check documentation on its impact.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**TRS-20011: TRSConnectionMgr is retrying to get connection. Number of times that TRSConnectionMgr retried:{0}**

**Cause:** Database failure.

**Action:** Check database.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**TRS-20012: TRSDBExecutor is retrying the database operation. Number of times that TRSDBExecutor retried:{0}**

**Cause:** Database failure.

**Action:** Check database.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**TRS-20013: A Replay Item for client {0} has been updated to status "ADMIN\_REVIEW".**

**Cause:** TxnReplayer failed while processing replay items.

**Action:** Adjust failure recovery timeout if this error happens very frequently.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**TRS-20014: {0} jobs to be submitted, but the expected number is {1} jobs.**

**Cause:** Job query failed to pick up all new jobs.

---

**Action:** Increase dispatcher cycle time if this warning happens very frequently.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**TRS-20015: Client {0}, Replay item #{1}: USER\_PASSWORD column is ignored for "CSF" password type.**

**Cause:** User password is retrieved from credential store for replay types with "CSF" password type.

**Action:** Remove the value in USER\_PASSWORD column in REPLAY\_ITEM table for replay items with "CSF" password type.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**TRS-20017: Test certificate is used for public key encryption.**

**Cause:** Test certificate was configured as the default certificate for development purpose only.

**Action:** Use a secure certificate in a production environment.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

---

## UCM-CS-000001 to UCM-CS-050023

### UCM-CS-000001: general exception

**Cause:** An exception occurred in the content server.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

### UCM-CS-000002: Error:

**Cause:** An error occurred in the content server.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

### UCM-CS-000003: Unknown system error encountered.

**Cause:** An error occurred in the content server.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

### UCM-CS-000004: Unknown error encountered.

**Cause:** The system encountered an unknown error.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

---

**Impact:** Logging

**UCM-CS-000005: Null pointer is dereferenced.**

**Cause:** A null pointer exception occurred in the content server.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**UCM-CS-001001: The NativeOsUtils class is not loaded.**

**Cause:** The required library 'NativeOsUtils' was not successfully loaded.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**UCM-CS-001002: Native file operations are disabled.**

**Cause:** The system's ability to do native file operations has been disabled.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**UCM-CS-001003: The platform {0} is not supported.**

**Cause:** The specified operating system does not support.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**UCM-CS-001004: The platform {0} is not supported for this operation.**

**Cause:** The specified operating system did not support the specified operation.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**UCM-CS-001005: The argument {0} is missing.**

**Cause:** The method or service was missing the required argument.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**UCM-CS-001006: {0} is missing from {1}.**

**Cause:** The method or service was missing the required argument.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**UCM-CS-001007: Unable to load database queries in table {0} for component {1}. The table does not exist.**

**Cause:** An error was encountered while loading the queries for the named component.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**UCM-CS-001008: The feature {0} is not installed.**

**Cause:** The required feature has not been installed.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**UCM-CS-001009: The feature {0} is at level {1}, but level {2} is required.**

**Cause:** An error was encountered while validating features. The requested feature is not supported.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

---

**Impact:** Configuration

**UCM-CS-001010: Incompatibility with feature {0} at level {1} has been detected.**

**Cause:** The specified feature was incompatible with a feature provided either by the system or another component.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**UCM-CS-001011: The feature {0} does not match feature {1}.**

**Cause:** The feature did not match an already installed feature.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**UCM-CS-001012: The feature {0} is installed at level {1}, but is also provided at level {2}.**

**Cause:** The feature already existed at a later version.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**UCM-CS-005001: Unable to copy the file {0} to {1}.**

**Cause:** An error occurred while copying files.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005002: Unable to rename the file {0} to {1}.**

**Cause:** An error occurred while renaming files.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR



---

**Impact:** Files

**UCM-CS-005003: Unable to open {0}.**

**Cause:** An error occurred while opening the named file.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005004: Unable to read {0}.**

**Cause:** An error occurred while accessing a file.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005005: Unable to write {0}.**

**Cause:** An error occurred while writing a file.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005006: The file is missing.**

**Cause:** The specified file was missing.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005007: The file {0} does not exist.**

**Cause:** The specified file did not exist.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

---

**UCM-CS-005008: The file {0} already exists.**

**Cause:** The file already existed in the system.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005009: The file {0} already exists in {1} directory.**

**Cause:** The file already existed in the named directory.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005010: File I/O error encountered while reading from file.**

**Cause:** An error occurred while reading the file.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005011: File I/O error encountered while writing to file.**

**Cause:** An error occurred while writing the specified file.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005012: Unable to delete {0}.**

**Cause:** An error occurred while deleting the specified file.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005013: Could not create the file {0}.**

---

**Cause:** An error occurred while creating the specified file.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005014: File I/O error encountered while saving to file {0}.**

**Cause:** An error occurred while saving the specified file.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005015: The file path {0} is invalid.**

**Cause:** The specified file path was invalid.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005016: Unable to find the file {0}. This may be a problem with the virtual machine.**

**Cause:** The system expected a file at the specified location, but it was missing.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005017: Unable to find the file {0}.**

**Cause:** The system was unable to locate the file at the specified location.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

---

**UCM-CS-005018: Error encountered while creating long-term lock {1} on directory {0}.**

**Cause:** An error occurred while creating the long term lock.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005019: Unable to create the directory.**

**Cause:** An error occurred while creating the directory.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005020: Unable to create directory {0}.**

**Cause:** An error occurred while creating the specified directory.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005021: Directory {0} does not exist.**

**Cause:** The system was unable to locate a directory at the specified location.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005022: File {0} does not exist.**

**Cause:** The system was unable to locate a file at the specified location.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

---

**UCM-CS-005023: Directory {0} cannot be accessed.**

**Cause:** An error occurred while accessing the directory.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005024: File {0} cannot be accessed.**

**Cause:** An error occurred while accessing the specified file.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005025: Directory {0} is read-only.**

**Cause:** A read-only directory was specified.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005026: File {0} is read-only.**

**Cause:** A read-only file was specified.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005027: Directory {0} has an invalid path.**

**Cause:** The system tried to access an invalid directory path.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005028: File {0} has an invalid path.**

---

**Cause:** The system tried access an invalid file path.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005029: Accessing the directory {0} caused a system error.**

**Cause:** An error was encountered while accessing the directory.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005030: File {0} caused a system error when accessed.**

**Cause:** An error was encountered while accessing the file.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005031: Unable to rename the file {0} to {1}.**

**Cause:** An error was encountered when trying to rename the specified file.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005032: The source file does not exist.**

**Cause:** The specified file did not exist.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005033: The target file cannot be accessed.**

**Cause:** The system was unable to access the specified file path.

---

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005034: Unable to copy the file {0} to {1}. The source file does not exist.**

**Cause:** An error was encountered while copying the file. The source file did not exist.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005035: Unable to copy the file {0} to {1}.**

**Cause:** An error was encountered while copying the file.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005037: File is locked by another process.**

**Cause:** The file was locked by another process.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005038: File {0} cannot be deleted. It may be locked by another process.**

**Cause:** An error was encountered while deleting the file.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-005039: Long-term lock {0} cannot be created for agent {1}.**

**Cause:** An error was encountered while attempting to create a long-term lock.

---

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**UCM-CS-010001: Cannot end string with {0}.**

**Cause:** During the parsing of a string, an illegal end character was encountered.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**UCM-CS-010002: Encountered an unterminated quote ({0}) at {1} in {2}.**

**Cause:** During the parsing of a string, the parser found an unclosed quoted string.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**UCM-CS-010003: Error encountered converting data with {0} character encoding.**

**Cause:** An encoding error was encountered while converting the data.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**UCM-CS-010004: Error encountered converting data with the default character encoding.**

**Cause:** The system encountered an error while converting data with the default character encoding.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**UCM-CS-010005: An error occurred decoding the stream.**



---

**Cause:** An error was encountered while decoding the data.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**UCM-CS-010006: Cannot find the parameter {0}.**

**Cause:** The system could not find the named parameter.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**UCM-CS-010007: The table does not exist.**

**Cause:** The named table did not exist or was not loaded into the resource container.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**UCM-CS-010008: The column {0} does not exist in this table.**

**Cause:** The specified column did not exist in the table.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**UCM-CS-010009: Parameter {0} is not present.**

**Cause:** The parameter was not defined in the current data set.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**UCM-CS-010010: Unable to parse result set {0}.**

---

**Cause:** An error was encountered while parsing the result set.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**UCM-CS-010011: Unable to parse properties. Name-value pair {0} is missing an equal sign (=).**

**Cause:** An error was encountered while parsing a property name-value pair.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**UCM-CS-010012: Error decoding the string. The string is badly formatted: {0}**

**Cause:** An error was encountered while decoding the badly formatted string.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**UCM-CS-010013: A name-value pair is missing the name in GET or POST syntax.**

**Cause:** An error was encountered while parsing the request.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**UCM-CS-010014: The input terminated before being able to read the line.**

**Cause:** An error was encountered while reading the input stream.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**UCM-CS-010015: The stream terminated before being able to read HTTP protocol line.**

**Cause:** An error was encountered while reading the input stream.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**UCM-CS-010016: Unable to parse data; the request method was not specified.**

**Cause:** An error was encountered while parsing the input stream. The request method has not been specified.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**UCM-CS-010017: The POST request did not send sufficient data.**

**Cause:** An error was encountered while parsing the request.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**UCM-CS-010018: Unable to read the stream to determine the format.**

**Cause:** An error was encountered while processing the server request.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**UCM-CS-010019: Unable to read additional bytes.**

**Cause:** An error was encountered while processing the server file request.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**UCM-CS-010020: Client terminated the upload of file {0}.**

**Cause:** The client terminated the upload of the file.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**UCM-CS-050001: illegal state**

**Cause:** Something put the system into an unexpected error; this is a generic error.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**UCM-CS-050002: The transaction listener {0} failed to close.**

**Cause:** The transaction failed to close when performing the service request.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**UCM-CS-050003: Database table does not exist.**

**Cause:** An error was encountered while performing a database activity.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**UCM-CS-050004: Cannot bind all parameters in query {0}.**

**Cause:** An error was encountered while creating the SQL query. The number of parameters required was inconsistent with the number of parameters provided.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**UCM-CS-050005: Unable to initialize the database {0}.**

**Cause:** An error was encountered while the system was initializing the database connections.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**UCM-CS-050006: Unable to create database connection for {0}.**

**Cause:** An error was encountered while trying to create a database connection for the named server instance.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**UCM-CS-050007: Server busy. Unable to obtain a connection to the database.**

**Cause:** The server was unable to establish a connection to the database.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**UCM-CS-050008: Unable to execute query {0}.**

**Cause:** An error was encountered while executing the specified query.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**UCM-CS-050009: Unable to execute callable query {0}.**

**Cause:** An error was encountered while executing the named callable query.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**UCM-CS-050010: Unable to create the result set for query {0}.**

**Cause:** An error was encountered while creating the results for the specified query.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**UCM-CS-050011: Unable to execute SQL statement {0}.**

**Cause:** An error was encountered while executing the given SQL statement.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**UCM-CS-050012: Unable to determine the database type.**

**Cause:** An error was encountered while determining the database type.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**UCM-CS-050013: Error occurred while closing connection: ({0}).**

**Cause:** An error was encountered while closing the database connection.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**UCM-CS-050014: Cannot begin the transaction. JDBC Error:**

**Cause:** An error was encountered while beginning a database transaction.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**UCM-CS-050015: Cannot commit the transaction. JDBC Error:**

**Cause:** An error was encountered while committing a database transaction.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**UCM-CS-050016: Failed to find indexable webviewable for content item {0} with revlabel {1} and dID {2}.**

**Cause:** An error was encountered while indexing the specified content item.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**UCM-CS-050017: Text conversion of the file {0} failed.**

**Cause:** An error was encountered while indexing the specified content item.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**UCM-CS-050018: Indexing failed.**

**Cause:** An error was encountered while indexing the specified content item.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**UCM-CS-050019: The creation date ({0}) of the new revision is not later than the creation date ({1}) of the latest revision in the system.**

**Cause:** An error was encountered while importing the content item. The create date for the new revision must be later than the older revision.

**Action:** The Archiver uses dates to validate the correct order of revisions. By default, it uses the dCreateDate, but this can be configured to use the dInDate by setting the configuration parameter UseRevisionCreateDate to true.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**UCM-CS-050020: The release date ({0}) of the new revision is not later than the release date ({1}) of the latest revision in the system.**

**Cause:** An error was encountered while importing the content item. The in date for the new revision must be later than the older revision.

**Action:** The Archiver uses dates to validate the correct order of revisions. By default, it uses the dCreateDate, but this can be configured to use the dInDate by setting the configuration parameter UseRevisionCreateDate to true.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**UCM-CS-050021: UCM Server failed to initialize inside its servlet environment.**

**Cause:** An error was encountered during initialization of the servlet environment./td>

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**UCM-CS-050022: Active index ({0}) is not valid for the indexer engine ({1}).**

**Cause:** The currently active search index was invalid for the configured indexer engine.

**Action:** A rebuild of the search collection is required.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**UCM-CS-050023: An error occurred during indexing.**

**Cause:** The system encountered an error while indexing a document.

**Action:** Details are usually given in the cause exception. Look for messages describing the cause exception and take the appropriate action. Also, examine the preceding or following log entries that are part of this message stack.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic



---

## UIX-00001 to UIX-00025

**UIX-00001: The servlet is not getting initialized.**

**Cause:** Servlet did not get initialized due to runtime errors

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:**

**UIX-00002: names contain '\$'**

**Cause:** Tried to create a oracle.cabo.servlet.Page Object with its name containing a '\$' character

**Action:** Remove the '\$' character.

**Level:** 1

**Type:** ERROR

**Impact:**

**UIX-00003: PageBroker entry is not present in the web.xml file.**

**Cause:** The parameter (param-name=oracle.cabo.servlet.pageBroker) was missing in the web.xml file.

**Action:** Contact Oracle Support Services

**Level:** 16

**Type:** INCIDENT\_ERROR

**Impact:**

**UIX-00004: Headers:**

**Cause:** The application was running in debug mode. Logs all HTTP request headers.

**Action:** Turn off the debug mode.

**Level:** 32

**Type:** NOTIFICATION

**Impact:**

**UIX-00005: Header {0} = {1}**

**Cause:** The application was running in debug mode. Logs all the HTTP request header names and their values in debug mode.

---

**Action:** Turn off the debug mode.

**Level:** 32

**Type:** NOTIFICATION

**Impact:**

**UIX-00005: Header {0} = {1}**

**Cause:** The application was running in the debug mode. Logs all the HTTP request header names and their values in debug mode.

**Action:** Turn off the debug mode.

**Level:** 32

**Type:** NOTIFICATION

**Impact:**

**UIX-00006: Requested page = {0}**

**Cause:** The application was running in the debug mode.

**Action:** Turn off debug mode.

**Level:** 32

**Type:** NOTIFICATION

**Impact:**

**UIX-00007: Page state: {0}**

**Cause:** The application was running in the debug mode.

**Action:** Turn off debug mode.

**Level:** 32

**Type:** NOTIFICATION

**Impact:**

**UIX-00008: Event = {0}**

**Cause:** The application was running in debug mode.

**Action:** Turn the debug mode off.

**Level:** 32

**Type:** NOTIFICATION

**Impact:**

**UIX-00009: Parameter {0} = {1}**

**Cause:** The application was running in debug mode.

**Action:** Turn the debug mode off.

**Level:** 32

**Type:** NOTIFICATION

**Impact:**

**UIX-00010: Rendering page = {0}**

**Cause:** The application was running in debug mode.

**Action:** Turn off the debug mode.

---

**Level:** 32

**Type:** NOTIFICATION

**Impact:**

**UIX-00011: finished doGet**

**Cause:** The application was running in debug mode.

**Action:** Turn off the debug mode.

**Level:** 32

**Type:** NOTIFICATION

**Impact:**

**UIX-00012: Time (s): {0}**

**Cause:** The application was running in debug mode.

**Action:** Turn off the debug mode.

**Level:** 32

**Type:** NOTIFICATION

**Impact:**

**UIX-00013: could not find renderer for {0}**

**Cause:** A custom renderer Java class was not found.

**Action:** Check for ClassNotFoundException and other errors.

**Level:** 3

**Type:** ERROR

**Impact:**

**UIX-00014: PageBroker was already initialized**

**Cause:** Double initialization of the page broker or the UIX servlet.

**Action:** Check the code for the second initialization.

**Level:** 2

**Type:** ERROR

**Impact:**

**UIX-00015: Could not create page flow engine: {0}**

**Cause:** The following pageflow engine class could not be loaded:  
oracle.cabo.servlet.event.TrivialPageFlowEngine

**Action:** Contact Oracle Support Services

**Level:** 2

**Type:** INCIDENT\_ERROR

**Impact:**

**UIX-00016: File upload manager was not created: {0}**

**Cause:** Could not load the custom FileUploadManager class or the default one given below. oracle.cabo.servlet.io.FileUploadManager

**Action:** Make sure the custom FileUploadManager is in classpath or the default one is as given below oracle.cabo.servlet.io.FileUploadManager

---

**Level:** 4

**Type:** ERROR

**Impact:**

**UIX-00017: Listener was not created: {0}**

**Cause:** Could not load one of the UIX listener classes or the default one given below. oracle.cabo.servlet.UIXRequestListeners

**Action:** Ensure all the custom listener classees are in classpath or the default one is as given below oracle.cabo.servlet.UIXRequestListeners

**Level:** 4

**Type:** ERROR

**Impact:**

**UIX-00018: The return type was invalid**

**Cause:** The event handler method that was bound to an event in the UIX page had the incorrect return type.

**Action:** The return type of a event handler method is oracle.cabo.servlet.event.EventResult.

**Level:** 10

**Type:** ERROR

**Impact:**

**UIX-00019: Method {0} was not static.**

**Cause:** The event handler method that was bound to an event was not static.

**Action:** Ensure that the event handler method bound to an event is static.

**Level:** 10

**Type:** ERROR

**Impact:**

**UIX-00020: The file was too large. The maximum file Size is: {0}**

**Cause:** The multiple-part file is too large.

**Action:** Upload a smaller file.

**Level:** 28

**Type:** ERROR

**Impact:**

**UIX-00021: Wildcarded events with explicit sources not supported for {0}**

**Cause:** Event registration is not specific.

**Action:** Register a specific event.

**Level:** 10

**Type:** ERROR

**Impact:**

**UIX-00022: The target was not a MutableDataObject {0}.**

---

**Cause:** The class name provided was not a subclass of  
oracle.cabo.ui.data.MutableDataObject

**Action:** Programmatic error correction needed.

**Level:** 10

**Type:** ERROR

**Impact:**

**UIX-00023: Target is not a MutableDataObject: {0}**

**Cause:** One of the following servlet init parameter is not a number.  
oracle.cabo.servlet.io.MaxMemory oracle.cabo.servlet.io.MaxDiskSpace

**Action:** The following servlet init parameters should be numbers  
oracle.cabo.servlet.io.MaxMemory oracle.cabo.servlet.io.MaxDiskSpace

**Level:** 10

**Type:** ERROR

**Impact:**

**UIX-00024: ActionEventHandler: cannot forward**

**Cause:** The value obtained is not a valid server resource.

**Action:** Make sure that the forward value is a valid server resource.

**Level:** 28

**Type:** ERROR

**Impact:**

**UIX-00025: QueueStateManager is expired**

**Cause:**

**Action:** Contact Oracle Support Services

**Level:** 10

**Type:** INCIDENT\_ERROR

**Impact:**



---

## UPGAST-00001 to UPGAST-02007

**UPGAST-00001: unable to continue due to an unexpected error**

**Cause:** An unexpected error occurred during the upgrade or verification.

**Action:** See the secondary error message for additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00002: Invalid argument {0}; an argument must begin with a hyphen.**

**Cause:** A command-line argument did not start with a hyphen.

**Action:** Run the command again, using a hyphen to identify any arguments. Enter the command `ua -help` for details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00003: invalid argument {0}**

**Cause:** The specified argument was not recognized.

**Action:** Run the command again, specifying a valid argument. Enter the command `ua -help` for details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00004: Value for argument {0} not supplied.**

**Cause:** The value for a command-line argument was not specified.

**Action:** Run the command again, specifying the required value for the command-line argument. Enter the command `ua -help` for details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00005: Mandatory argument {0} not supplied.**

**Cause:** A mandatory command-line argument was not supplied.

---

**Action:** Run the command again, specifying the mandatory command-line argument. Enter the command `ua -help` for details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00006: Mandatory arguments {0} not supplied.**

**Cause:** The listed mandatory command-line arguments were not supplied.

**Action:** Run the command again, specifying each mandatory command-line argument. Enter the command `ua -help` for details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00007: Invalid source Oracle home directory: {0}.**

**Cause:** The source Oracle home directory did not exist or cannot be accessed.

**Action:** Run the command again, specifying a valid source Oracle home directory.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00008: Invalid Oracle Universal Installer inventory location file: {0}.**

**Cause:** The Oracle Universal Installer inventory location file was not found.

**Action:** Run the command again, specifying a valid Oracle Universal Installer inventory location file.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00009: Invalid log level: {0}.**

**Cause:** The log level specified was not recognized.

**Action:** Run the command again, specifying a valid log level. See the command line help for details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00010: Port number {0} is not valid.**

**Cause:** The port number specified was not a positive numeric value or was out of range.

**Action:** Run the command again, specifying a valid port number.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade



---

**UPGAST-00011: Host name {0} is not valid or unknown.**

**Cause:** Lookup of the specified host name failed.

**Action:** Run the command again, specifying a valid host name.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00012: Required port is missing.**

**Cause:** A required port was not entered.

**Action:** Enter the required port.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00013: Invalid source Oracle home. The source Oracle home must be an Oracle home found in the Oracle Universal Installer inventory.**

**Cause:** The specified source Oracle home directory did not exist in the Oracle Universal Installer inventory.

**Action:** Run the command again, specifying a valid source Oracle home directory.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00014: unable to connect to WebLogic Server at {0}:{1}**

**Cause:** Failed connecting to the WebLogic Server at the specified host and port.

**Action:** See the secondary error message for additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00015: Invalid Oracle instance home directory: {0}.**

**Cause:** The Oracle instance home directory did not exist or cannot be accessed.

**Action:** Run the command again, specifying a valid Oracle instance home directory.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00016: Required password is missing.**

**Cause:** A required password was not entered.

**Action:** Enter the required password.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

---

**UPGAST-00019: Unable to connect to database. Reason: {0}.**

**Cause:** The database connection failed for the specified reason.

**Action:** Correct the problem using information provided in the log file; then retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00020: Required connect string is missing.**

**Cause:** A required connect string was not entered.

**Action:** Enter the required connect string.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00021: Required user name is missing.**

**Cause:** A required user name was not entered.

**Action:** Enter the required user name.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00022: The source file {0} does not exist.**

**Cause:** The source file for a file copy operation did not exist.

**Action:** Check the location of the specified file. This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-00023: cannot read file {0}**

**Cause:** The specified file could not be read.

**Action:** Check the permissions of the specified file and ensure that the file has read access.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00024: unable to expand wildcard file specification {0}**

**Cause:** The specified file specification could not be expanded.

**Action:** See log file for details. This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Upgrade

**UPGAST-00025: The directory {0} is not an Oracle instance home directory.**

**Cause:** The directory specified was not a valid Oracle instance home directory.

**Action:** Run the command again, specifying a valid destination Oracle instance home directory.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00026: The source Oracle home installation type must be an Identity Management installation type. {0} is not an Identity Management installation type.**

**Cause:** An incorrect source Oracle home was specified.

**Action:** Specify a source Oracle home that is an Identity Management installation type.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00027: The source Oracle home installation type must be a middle-tier installation type. {0} is not a middle-tier installation type.**

**Cause:** An incorrect source Oracle home was specified.

**Action:** Specify a source Oracle home that is a middle-tier installation type.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00028: Required service name is missing.**

**Cause:** A required service name was not entered.

**Action:** Enter the required service name. A service name typically includes the domain; for example, db1.example.com.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00030: Required Oracle instance home directory is missing.**

**Cause:** A required Oracle instance home directory was not entered.

**Action:** Enter the required Oracle instance home directory.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00031: unable to get the active DomainMBean for the WebLogic Server domain**

**Cause:** Failed getting the active DomainMBean for the WebLogic Server domain.

---

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-00032: unable to communicate with the WebLogic Server**

**Cause:** Communication with the WebLogic Administrative Server was either lost or never established.

**Action:** See the secondary error message for additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00033: unable to create a datasource definition named {0}**

**Cause:** The creation of a domain-level datasource in the WLS Administration Server failed.

**Action:** See the secondary error message for additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00034: unable to establish an EDIT connection**

**Cause:** The connection to the Edit service in the WLS Administration Server failed.

**Action:** See the secondary error message for additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00035: unable to save configuration changes**

**Cause:** Verification in the WLS Administration Server failed.

**Action:** See the secondary error message for additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00036: unable to start an edit operation**

**Cause:** The Edit service in the WLS Administration Server failed to start an edit operation.

**Action:** See the secondary error message for additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00037: unable to fetch or store attribute "{0}" in the WebLogic Server**

---

**Cause:** This is an internal logic error. The most common cause is an incorrect attribute name.

**Action:** See the secondary error message for additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00038: unable to locate an MBean named "{0}"**

**Cause:** One of the upgrade steps was looking for an MBean with this name. That is was not found might or might not be an error, depending on context.

**Action:** See the secondary error message for additional details.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**UPGAST-00039: Portal middle-tier upgrade does not allow the -noRetainPorts command-line argument.**

**Cause:** The -noRetainPorts command-line argument was specified during a Portal middle-tier upgrade.

**Action:** Rerun the upgrade specifying the -retainPorts command-line argument

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00040: unable to get the DomainRuntimeMBean for the WebLogic Server domain**

**Cause:** Failed getting the DomainRuntimeMBean for the current WebLogic Server domain.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-00041: unable to determine OID and RDBMS location**

**Cause:** Not all of the needed information was supplied on the command line.

**Action:** Specify -dbHost -dbPort -dbServiceName -oidHost and -oidSslPort options.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00042: unable to resolve OPMN MBean**

**Cause:** unable to find management information for the non-J2EE components

**Action:** Make sure that nonJ2EE components have been configured with the WLS Admin Server.

---

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00043: The -noStopComponents argument cannot be specified along with the retain ports option.**

**Cause:** The option to not stop source components was specified with the retain ports option.

**Action:** Run the command again, without specifying -noStopComponents.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00044: The source Oracle home does not contain any components which require an upgrade.**

**Cause:** The specified source Oracle home directory did not contain any components that would require an upgrade.

**Action:** Run the command again, specifying a valid source Oracle home directory.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00045: The version of the source Oracle home is not supported.**

**Cause:** The specified source Oracle home directory was not a supported version. For middle-tier upgrade, the source Oracle home version must be 10.1.2 or 10.1.3. For Identity Management upgrade, the source Oracle home version must be 10.1.2 or 10.1.4.

**Action:** Run the command again, specifying a valid source Oracle home directory.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00047: Upgrades of BAM schemas are not allowed from this type of Oracle home.**

**Cause:** The user has chosen to perform a BAM schema upgrade from an Oracle home that was not a SOA Oracle home.

**Action:** Perform the BAM schema upgrade from a SOA Oracle home.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00048: unable to open the log file**

**Cause:** failed to open the log file

**Action:** See the secondary error message for additional details.

**Level:** 1

**Type:** ERROR

---

**Impact:** Upgrade

**UPGAST-00049: unable to read the log file**

**Cause:** failed to read the log file

**Action:** See the secondary error message for additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00050: unable to create logging directory: {0}**

**Cause:** The directory for log files could not be created.

**Action:** See the secondary error message for additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00051: unable to create the log file**

**Cause:** failed to create the log file

**Action:** See the secondary error message for additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00052: unable to initialize logging**

**Cause:** Initialization of logging failed

**Action:** See the secondary error message for additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00053: No upgrade components were found in the config file {0}.**

**Cause:** No upgrade components in the specified configuration file.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-00054: error loading config file {0}**

**Cause:** failed to load the configuration file

**Action:** See the secondary error message for additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00055: error reading the Oracle Universal Installer inventory**

---

**Cause:** An error occurred while reading the Oracle Universal Installer inventory.

**Action:** See the secondary error message for additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00056: error initializing component {0}**

**Cause:** failed to initialize the specified components upgrade software

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-00057: Invalid source data home directory: {0}.**

**Cause:** The source data home directory did not exist or cannot be accessed.

**Action:** Run the command again, specifying a valid source data home directory.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00058: {0} file does not exist or cannot be accessed.**

**Cause:** The specified file did not exist or could not be accessed.

**Action:** Make sure the path to the file is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00059: Invalid database type: {0}.**

**Cause:** The database type specified was not recognized.

**Action:** Run the command again, specifying a valid database type. See the command line help for details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00060: An invalid installation type {0} has been found in properties file {1}.**

**Cause:** The installation type found in the source Oracle home was not supported.

**Action:** Specify a source Oracle home that has a supported installation type.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** Upgrade

**UPGAST-00061: installation type not found**

**Cause:** The installation type of the source Oracle home could not be determined.



---

**Action:** Ensure that the source Oracle home is a supported version and is working properly.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00062: An invalid installation type has been found in source Oracle home {0}.**

**Cause:** The installation type of the source Oracle home was not supported.

**Action:** Ensure that the source Oracle home is a supported version and is working properly.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00063: unable to load the properties file {0}**

**Cause:** An error was encountered reading or parsing the properties file of the source Oracle home. The information in the ias.properties file is used to determine the type of the source Oracle home.

**Action:** See the secondary message for additional details.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**UPGAST-00064: no components need to be upgraded**

**Cause:** No components were found in the source Oracle home that need upgrading. An upgrade will not be needed.

**Action:** No action needed.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Upgrade

**UPGAST-00065: Configuration parameter {0} not found in source Oracle home {1}.**

**Cause:** The information in the ias.properties file is used to determine the type and contents of the source Oracle home. In this case, a parameter in the properties file was missing and, as a result, the upgrade cannot proceed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-00066: Configuration parameter {0} has invalid value of {1} in source Oracle home {2}.**

**Cause:** The information in the ias.properties file is used to determine the type and contents of the source Oracle home. In this case, a parameter in the properties file was invalid and, as a result, the upgrade cannot proceed.

---

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-00067: One or more errors occurred while identifying components to be upgraded.**

**Cause:** Errors were encountered while analyzing the source Oracle home.

**Action:** See the log file for additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00068: One or more errors occurred while initializing components to be upgraded.**

**Cause:** Errors were encountered while setting up the components upgrade software.

**Action:** See the log file for additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00069: Examination found that no components need to be upgraded. No upgrade will be performed.**

**Cause:** No components were identified as needing upgrade during the examination phase. No upgrade will be performed.

**Action:** No action needed.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**UPGAST-00073: failed to set startup type to manual for Windows service {0}**

**Cause:** An error was encountered when changing the startup mode of a Windows service. At the end of the upgrade process, each Windows service associated with the 10g Oracle home is set to manual startup. Windows services in the source home must be set to manual startup to prevent resource conflicts with the 11g upgraded instance.

**Action:** Using the Windows Services utility, manually set the startup type for the specified Windows service.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**UPGAST-00074: spawned process timed out**

**Cause:** A spawned process stopped responding.

---

**Action:** Examine the log file to determine what actions were being performed when the error occurred.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00075: spawn process exception**

**Cause:** An error was encountered spawning a process.

**Action:** Examine the log file to determine what actions were being performed when the error occurred.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00076: spawned process exception**

**Cause:** An error was encountered in a spawned process.

**Action:** Examine the log file to determine what actions were being performed when the error occurred.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00077: The IP address of the source host {0} cannot be determined.**

**Cause:** The network address of a host could not be determined.

**Action:** Check the validity of the specified host.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00078: The IP address of the destination host {0} cannot be determined.**

**Cause:** The network address of a host could not be determined.

**Action:** Check the validity of the specified host.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00079: failed to create temporary directory: {0}**

**Cause:** An error was encountered creating a temporary directory.

**Action:** Ensure that the directory location exists and is not protected.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00080: failed to start WebLogic Server {0}**

**Cause:** An error was encountered starting a WebLogic Server.

---

**Action:** Examine the log file to determine the reason why the WebLogic server failed to start.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00081: failed to stop WebLogic Server {0}**

**Cause:** An error was encountered stopping a WebLogic Server.

**Action:** Examine the log file to determine the reason why the WebLogic server failed to stop.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00082: Required Oracle Single Sign-On policy.properties file is missing.**

**Cause:** The required Oracle Single Sign-On policy.properties file was not entered.

**Action:** Enter the required Oracle Single Sign-On policy.properties file.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00084: {0} file does not exist or cannot be accessed.**

**Cause:** The specified Oracle Single Sign-On policy.properties file did not exist or could not be accessed.

**Action:** Specify a valid Oracle Single Sign-On policy.properties file.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00085: unable to load the properties file {0}**

**Cause:** An error was encountered reading or parsing the Oracle Single Sign-On properties file.

**Action:** See the secondary message for additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00086: expected property "DefaultAuthLevel" not found in {0}**

**Cause:** The Oracle Single Sign-On properties file does not contain an expected property.

**Action:** Specify a valid Oracle Single Sign-On policy.properties file.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

---

**UPGAST-00087: Either the ASA install directory, the ARM install directory, or both install directories must be specified.**

**Cause:** A required ASA install directory or ARM install directory was not entered.

**Action:** Enter at least one of the install directories.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00088: Argument {0} is not valid for this upgrade operation.**

**Cause:** The specified argument could not be used with the type of upgrade attempted.

**Action:** Run the command again, without the invalid argument.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00089: Required schema name is missing.**

**Cause:** A required schema name was not entered.

**Action:** Enter the required schema name.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00090: failed to connect to Oracle Internet Directory**

**Cause:** unable to connect to the Oracle Internet Directory server

**Action:** See the secondary error message for additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00091: errors during the examine of components**

**Cause:** Errors were encountered while checking components' readiness for upgrade.

**Action:** See the log file for additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00092: errors during the upgrade of components**

**Cause:** Errors were encountered while upgrading one or more components.

**Action:** See the log file for additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

---

**UPGAST-00093: {0} directory does not exist or cannot be accessed.**

**Cause:** The specified directory did not exist or could not be accessed.

**Action:** Specify a valid directory.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00094: Either the -asaDir argument, -armDir argument, or both arguments must be specified.**

**Cause:** A required -asaDir argument or -armDir argument was not entered on the command-line.

**Action:** Enter at least one of the required arguments.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00095: error setting the Oracle look-and-feel for the graphical user interface**

**Cause:** An internal error occurred while setting the appearance for the graphical user interface.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-00096: error initializing the help system**

**Cause:** An internal error occurred while setting up the help system.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-00097: The IP address of the host {0} cannot be determined.**

**Cause:** The network address of the specified host could not be determined.

**Action:** Check the validity of the specified host.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00098: A running Oracle Internet Directory server cannot be located.**

**Cause:** No running Oracle Internet Directory server was detected in the 11g configuration. Upgrade needs this server.

**Action:** Ensure that at least one Oracle Internet Directory has been configured and is running.

**Level:** 1

---

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00099: End point named {0} cannot be found for {1}.**

**Cause:** The named end point could not be located for a component.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-00100: Required Oracle Universal Content Management directory is missing.**

**Cause:** The required Oracle Universal Content Management directory was not entered.

**Action:** Enter the required Oracle Universal Content Management directory.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00101: Unable to access the schema version registry. Reason: {0}.**

**Cause:** Access to schema version registry failed for the specified reason.

**Action:** See log file for details. Correct the problem causing the failure to connect to the schema version registry and then retry connecting.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00102: Required ODS schema password is missing.**

**Cause:** The required ODS schema password was not entered.

**Action:** Enter the required ODS schema password.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00103: failed to get Oracle Internet Directory host and port**

**Cause:** An error was encountered while trying to determine host and port information for an LDAP server.

**Action:** See log file for details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00104: Required Oracle Internet Directory password is missing.**

**Cause:** The required Oracle Internet Directory password was not entered.

**Action:** Enter the required Oracle Internet Directory password.

---

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00105: Required SYS password is missing.**

**Cause:** The required SYS password was not entered.

**Action:** Enter the required SYS password.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00106: Identity Management upgrade not allowed from this type of Oracle home.**

**Cause:** The user has chosen to perform an Identity Management upgrade from an Oracle home that does not allow this type of upgrade.

**Action:** Perform the upgrade from an Identity Management Oracle home.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00107: The DISPLAY environment variable is not set. The graphical user interface (GUI) requires that this environment variable be set on UNIX.**

**Cause:** The required DISPLAY environment variable was not defined.

**Action:** Set the required DISPLAY environment variable and then rerun the Assistant.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00108: Required Oracle Universal Content Management directory is missing.**

**Cause:** The required Oracle Universal Content Management directory was not entered.

**Action:** Enter the required Oracle Universal Content Management directory.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00109: The destination Oracle instance is not an Identity Management instance.**

**Cause:** An incorrect destination Oracle instance was specified.

**Action:** Specify a destination Oracle instance that is an Identity Management instance.

**Level:** 1

**Type:** ERROR



---

**Impact:** Upgrade

**UPGAST-00110: The destination Oracle instance is not a middle-tier instance.**

**Cause:** An incorrect destination Oracle instance was specified.

**Action:** Specify a destination Oracle instance that is a middle-tier instance.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00111: Verify instance option is not available for this type of Oracle home.**

**Cause:** The user has chosen to perform a verify instance from a Oracle home that does support verify.

**Action:** None.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00112: A middle-tier upgrade is not allowed from an Identity Management Oracle home.**

**Cause:** The user has chosen to perform a middle-tier upgrade from an Oracle home that does not allow this type of upgrade.

**Action:** Perform the upgrade from an Oracle home that allows middle-tier upgrade.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00113: Specify which schemas are to be upgraded using the {0} and {1} arguments.**

**Cause:** The user has chosen to perform a metadata repository upgrade without specifying which schemas to upgrade.

**Action:** Specify the schemas to be upgraded.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00114: Upgrades of Oracle Portal and Discoverer schemas are not allowed from this type of Oracle home.**

**Cause:** The user has chosen to perform an Oracle Portal or Discoverer schema upgrade from an Oracle home that does not allow this type of upgrade.

**Action:** Perform the upgrade from an Oracle home that allows Oracle Portal or Discoverer schema upgrades.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

---

**UPGAST-00115: Upgrades of B2B schemas are not allowed from this type of Oracle home.**

**Cause:** The user has chosen to perform a B2B schema upgrade from an Oracle home that is not a SOA Oracle home.

**Action:** Perform the B2B schema upgrade from a SOA Oracle home.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00116: Select which metadata repository schemas are to be upgraded.**

**Cause:** The user has chosen to upgrade metadata repository schemas but did not specify which schemas to upgrade.

**Action:** Specify the metadata repository schemas to be upgraded.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00117: Argument {0} is not valid with the graphical user interface.**

**Cause:** The specified argument cannot be used with the graphical user interface.

**Action:** Run the command again, without the invalid argument.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00118: End point named {0} not found while setting port values.**

**Cause:** An attempt was made to change a port number. A required ListeningEndpoint attribute was not found.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-00119: Port value {1} cannot be set for the end point named {0}.**

**Cause:** An error occurred while setting a new port value.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** SET\_AT\_RUNTIME

**Impact:** Upgrade

**UPGAST-00120: The password for schema {0} cannot be obtained from the credential storage facility (CSF).**

**Cause:** An error occurred while fetching a stored password.

**Action:** Contact Oracle Support Services.

**Level:** 1

---

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-00121: A middle-tier upgrade is not allowed from a SOA Oracle home.**

**Cause:** The user has chosen to perform a middle-tier upgrade from an Oracle home that does not allow this type of upgrade.

**Action:** Perform the upgrade from an Oracle home that allows middle-tier upgrade.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00122: Select a middle tier component to be upgraded.**

**Cause:** The user has chosen to upgrade middle tier components but did not specify which component to upgrade.

**Action:** Specify the middle tier component to be upgraded.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00123: The database cluster specification contains syntax errors.**

**Cause:** The cluster specification must be of the form "host:port:instance^...@service". See documentation for further details.

**Action:** Correct the errors.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00124: The root script file {0} cannot be written.**

**Cause:** A file I/O error has prevented the creation of a necessary root script file.

**Action:** Check that Oracle home directory protections allow the file to be created.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00125: The Oracle home that the Assistant is running from is not found in the Oracle Universal Installers inventory.**

**Cause:** The Assistant was not found in the Oracle Universal Installers inventory.

**Action:** Specify an inventory location pointer file on the command line or reinstall an Oracle home for the Assistant to run from.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00126: The Assistant is not supported in this Oracle home.**

---

**Cause:** The Assistant was not supported in this Oracle home and therefore could not be run from this Oracle home.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-00127: Oracle Internet Directory upgrade failed. The Assistant will not proceed.**

**Cause:** It is not possible to continue with the upgrade of the other components in the instance because they depend on the successful completion of Oracle Internet Directory upgrade.

**Action:** See log file for details. Correct the problem and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00128: Oracle Internet Directory examination failed. The Assistant will not proceed.**

**Cause:** It is not possible to continue with the examination of the other components in the instance because they depend on the successful completion of Oracle Internet Directory examination.

**Action:** See log file for details. Correct the problem and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00129: Registered database server not found for {0};{1} service {2}.**

**Cause:** A database server was not registered with the supplied connection information.

**Action:** Check that information entered is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00130: Registered schema named {0} not found.**

**Cause:** A schema was not registered under the supplied name.

**Action:** Check spelling of schema name.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00131: Required ASA install directory is missing.**

**Cause:** A required ASA install directory was not entered.

**Action:** Enter the required ASA install directory.

---

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00132: Required ARM install directory is missing.**

**Cause:** A required ARM install directory was not entered.

**Action:** Enter the required ARM install directory.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00133: unable to get host name or port for a database server object**

**Cause:** No value was obtained for the host name or port number.

**Action:** Check that the database server is properly registered at farm level and that host name and port values are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00134: Required dump file name is missing.**

**Cause:** A required dump file was not entered.

**Action:** Enter the required dump file name.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00135: Required password was not supplied**

**Cause:** No value was entered in response to a password prompt.

**Action:** Run the Assistant again and supply all required passwords.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00136: The source install directory is not an Oracle Identity Manager 9.1 installation.**

**Cause:** The source install directory specified did not include the mandatory files xlconfig.xml and XellerateFull.ear

**Action:** Specify a valid Oracle Identity Manager 9.1 source install directory.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00137: Required Oracle Universal Records Management directory is missing.**

---

**Cause:** The required Oracle Universal Records Management directory was not entered.

**Action:** Enter the required Oracle Universal Records Management directory.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00138: upgrade exception occurred**

**Cause:** An unexpected upgrade exception has occurred.

**Action:** See the secondary error message for additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00139: Upgrading the OWA packages to a new version as the database contains the older version. This process might take time.**

**Cause:** The OWA software package of Portal was detected, and its presence requires additional time for the upgrade to complete.

**Action:** No action needed.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Upgrade

**UPGAST-00140: Startup of {0} OPMN managed processes failed (Reason: {1}).**

**Cause:** The starting of OPMN or OPMN managed processes has failed.

**Action:** Check the log file for additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00141: startup of 11g OPMN managed processes failed**

**Cause:** The starting of OPMN or OPMN managed processes has failed.

**Action:** Check the log file for additional details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00142: User chose to cancel rather than upgrade OID without DIP.**

**Cause:** OID and DIP are both configured in the source Oracle Home, but only OID in the destination. User chose not to proceed.

**Action:** Configure DIP in the destination Instance and run the Assistant again.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

---

**UPGAST-00143: Although an Oracle Directory Integration Platform instance is configured within your source environment, one was not found within the destination environment. If you proceed with upgrade without configuring DIP in your destination environment, only OID will be upgraded. You will not be able to use the Assistant to upgrade DIP at a later time. Would you like to proceed with the upgrade?**

**Cause:** OID and DIP are both configured in the source Oracle home, but only OID in the destination.

**Action:** If you want to upgrade DIP, configure DIP in the destination Instance and run the Assistant again.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00144: Specify which component to be upgraded using either the {0}, {1}, or {2} argument.**

**Cause:** The user has chosen to perform a middle tier upgrade without specifying which component to be upgraded.

**Action:** Specify the component to be upgraded.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00145: Specify only one component to be upgraded using either the {0}, {1}, or {2} argument.**

**Cause:** The user has chosen to perform a middle tier upgrade and has specified more than one component to be upgraded.

**Action:** Specify only one component to be upgraded.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00146: PostgreSQL JDBC driver is missing or corrupted {0}.**

**Cause:** The user has chosen an upgrade with a PostgreSQL database but the JDBC driver that Oracle has certified for use is either missing or corrupt.

**Action:** Locate the precise version of the PostgreSQL JDBC driver jar file that Oracle has certified, and copy it into the ORACLE\_HOME/jlib directory. The name of the jar file must match the expected name, and the SHA1 signature of the file must match the expected value.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00147: Required Oracle Identity Manager namespace is missing.**

**Cause:** The required Oracle Identity Manager namespace was not entered.

**Action:** Enter the required Oracle Identity Manager namespace.

**Level:** 1

---

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00148: Required Oracle Universal Records Management directory is missing.**

**Cause:** The required Oracle Universal Records Management directory was not entered.

**Action:** Enter the required Oracle Universal Records Management directory.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00149: Required RPD file location is missing.**

**Cause:** A required RPD file location was not entered.

**Action:** Enter the required RPD file location.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00150: Required catalog directory is missing.**

**Cause:** A required catalog directory was not entered.

**Action:** Enter the required catalog directory.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00151: Upgrade repository or upgrade catalog must be selected.**

**Cause:** The upgrade repository checkbox or the upgrade catalog checkbox was not selected.

**Action:** Select the upgrade repository checkbox or the upgrade catalog checkbox, or both.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00152: Required confirm password is missing.**

**Cause:** A required confirm password was not entered.

**Action:** Enter the required confirm password.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00153: Password does not match the confirm password.**

**Cause:** The password and confirm password were not the same.

**Action:** Enter a matching password and confirm password.



---

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00154: Password must be at least 8 characters in length and contain a mix of letters and numbers.**

**Cause:** The password entered did not meet the password length requirements or contained characters that were not a mix of letters and numbers.

**Action:** Enter a password of at least 8 characters in length that contains a mix of letters and numbers.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00155: Unable to connect to ODI Supervisor account: {0}.**

**Cause:** The ODI supervisor user name or password were incorrect, or the ODI master repository name was incorrect, or an internal error occurred

**Action:** Correct the problem by entering the correct user name and password for both the ODI master repository and the ODI supervisor account; then, retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00156: The catalog directory is not a valid catalog directory.**

**Cause:** The catalog directory specified did not include the mandatory file root.atr.

**Action:** Specify a valid catalog directory.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00157: Both {0} and {1} must be specified or both {2} and {3} must be specified.**

**Cause:** A required RPD file and RPD administrator user name was not entered or a required catalog directory and catalog deliveries directory was not entered.

**Action:** Specify the RPD File and RPD administrator user name or the catalog directory and catalog deliveries directory, or all.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00158: Required BI Publisher repository directory is missing.**

**Cause:** A required BI Publisher repository directory was not entered.

**Action:** Enter the required BI Publisher repository directory.

**Level:** 1

**Type:** ERROR

---

**Impact:** Upgrade

**UPGAST-00159: Required 10g RPD administrator user name is missing.**

**Cause:** A required 10g RPD administrator user name was not entered.

**Action:** Enter the required 10g RPD administrator user name.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00160: unable to create directory: {0}**

**Cause:** The specified directory could not be created.

**Action:** Check the permissions for creating the specified directory.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00161: The ASA application directory is not a valid ASA application directory.**

**Cause:** The ASA application directory specified did not include the mandatory files `bharosauio.properties`, `bharosa_client.properties`, and `bharosa_common.properties`

**Action:** Specify a valid ASA application directory.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00162: The ARM application directory is not a valid ARM application directory.**

**Cause:** The ARM application directory specified did not include the mandatory files `bharosa_server.properties` and `bharosa_common.properties`

**Action:** Specify a valid ARM application directory.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00163: Specify which component to be upgraded using either the {0} or the {1} argument.**

**Cause:** The user has chosen to perform a middle tier upgrade without specifying which component to be upgraded.

**Action:** Specify the component to be upgraded.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00164: Specify only one component to be upgraded using either the {0} or the {1} argument.**

---

**Cause:** The user has chosen to perform a middle tier upgrade and has specified more than one component to be upgraded.

**Action:** Specify only one component to be upgraded.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00165: {0} is a directory instead of a RPD file.**

**Cause:** The RPD file specified was not a file.

**Action:** Specify a valid RPD file.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00166: Required E-Business Suite data template directory is missing.**

**Cause:** A required E-Business Suite data template directory was not entered.

**Action:** Enter the required E-Business Suite data template directory.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00167: Upgrade BI Publisher repository directory option or upgrade E-Business Suite data template directory option must be selected.**

**Cause:** The upgrade BI Publisher repository directory option or the upgrade E-Business Suite data template directory option was not selected.

**Action:** Choose either the upgrade BI Publisher repository directory option or the upgrade E-Business Suite data template directory option.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00168: {0} or {1} must be specified, but not both**

**Cause:** A required argument was not specified or you have specified both arguments.

**Action:** Specify only one of the required arguments.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00169: Required catalog deliveries directory is missing.**

**Cause:** A required catalog deliveries directory was not entered.

**Action:** Enter the required catalog deliveries directory.

**Level:** 1

**Type:** ERROR

---

**Impact:** Upgrade

**UPGAST-00170: unable to validate the 10g RPD administrator user name and password. Reason: {0}.**

**Cause:** The validation of the 10g RPD administrator user name and password failed for the specified reason.

**Action:** Correct the problem using information provided; then retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00171: A middle-tier upgrade is not allowed from a Web Center Oracle home.**

**Cause:** The user has chosen to perform a middle-tier upgrade from an Oracle home that does not allow this type of upgrade.

**Action:** Perform the upgrade from an Oracle home that allows middle-tier upgrade.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00172: The database credentials entered are not for a valid OAAM database.**

**Cause:** The user has entered incorrect OAAM database credentials.

**Action:** Enter valid OAAM database credentials. See the secondary error message.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00795: Verify instance option is not available from an Application Developer Oracle home.**

**Cause:** The user has chosen to perform a verify instance from an Application Developer Oracle home.

**Action:** None.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00796: A middle-tier upgrade is not allowed from an Application Developer Oracle home.**

**Cause:** The user has chosen to perform a middle-tier upgrade from an Oracle home that does not allow this type of upgrade.

**Action:** Perform the upgrade from an Oracle home that allows middle-tier upgrade.

**Level:** 1

**Type:** ERROR

---

**Impact:** Upgrade

**UPGAST-00797: Oracle Fusion Middleware Upgrade Assistant cannot be run from an Application Developer Oracle home.**

**Cause:** The user has chosen to perform a upgrade from an Oracle home that does not allow an upgrade.

**Action:** None.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00798: Oracle Fusion Middleware Upgrade Assistant cannot be run from a Web Center Oracle home.**

**Cause:** The user has chosen to perform a upgrade from an Oracle home that does not allow an upgrade.

**Action:** None.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00799: Verify instance option is not available from a Web Center Oracle home.**

**Cause:** The user has chosen to perform a verify instance from a Web Center Oracle home.

**Action:** None.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-00800: Oracle Fusion Middleware Patch Set Assistant cannot be run from a Web Tier Oracle home.**

**Cause:** The user has chosen to perform a patch set upgrade from an Oracle home that does not allow a patch set upgrade.

**Action:** Perform the patch set upgrade from an Oracle home that allows a patch set upgrade.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-01001: Upgrade is unable to connect to SSL port of OID.**

**Cause:** Repository upgrade framework was unable to connect to the OID server using the host name, SSL port number and password specified. The server might be down.

**Action:** Verify that the OID server is running. Verify that the host name, SSL port number, and cn=orcladmin password are correctly specified.

**Level:** 1

**Type:** ERROR

---

**Impact:** Upgrade

**UPGAST-01002: Upgrade is unable to connect to the metadata repository database.**

**Cause:** Repository upgrade framework was unable to connect to the metadata repository database. The database might be down, or the password might be incorrect.

**Action:** Verify that the Repository Database instance and listener have been started. Verify that the user name and password are correct. Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-01003: Upgrade is unable to open XML file: {0}.**

**Cause:** Repository upgrade framework was unable to open the xml file mrua.xml, or the file was corrupted.

**Action:** Verify that the file exists in the specified directory, and that the read permission on the file is set correctly. Examine the file to ensure that the contents are correct. Edit the file if needed to correct any errors.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-01004: Upgrade is unable to dynamically load component-specific software modules.**

**Cause:** Repository upgrade framework was unable to dynamically load the Java classes of its component-specific software modules. mrua.xml file might have been corrupted.

**Action:** This is an internal error. Verify that the Java classpath has been correctly set, the mrua.xml file is correct, and that the .jar files for all component-specific software modules are present in the jlib directory. Contact Oracle Support Services for assistance.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-01005: error initializing component-specific software module {0}**

**Cause:** Repository Upgrade was unable to initialize the named component-specific software module. This is an internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-01006: Schema upgrade failed for {0}.**

**Cause:** Repository Upgrade framework detected that schema upgrade of the component named in the error message failed.

**Action:** Examine the upgrade log files for additional error messages. It may be possible to correct the problem and retry the upgrade.

---

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-01007: Schema upgrade returned improper status.**

**Cause:** The Repository Upgrade component-specific software module for the named component returned an incorrect status to the upgrade framework. This is an internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-01008: Schema examination failed for {0}.**

**Cause:** Repository upgrade framework determined that the examination phase of upgrade failed for the named component. This is often due to a failed prerequisite check. No schemas changes have been made to the component that failed.

**Action:** Check the upgrade log files for the cause of the message. Correct the source of the problem if possible, and retry the examination. Do not go on to perform an actual upgrade in upgrade mode unless all components succeed during examination.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-01009: SQL script {0} does not exist.**

**Cause:** The repository upgrade component-specific software module named in the error message attempted to run a SQL script that could not be located. This is an internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-01011: Verify that database version {0} has been certified with Oracle Fusion Middleware.**

**Cause:** Repository upgrade framework determined that the database release number of the repository database is at a version that was not yet certified with Oracle Fusion Middleware repository upgrade at the time the product shipped. Upgrade will continue.

**Action:** Verify that this version of the database has been certified for use with Oracle Fusion Middleware repository upgrade. If upgrade is performed using an uncertified release of the database, errors may occur during or after the upgrade. Upgrade should not be performed using database releases that have not yet been certified for use with the current release of Oracle Fusion Middleware.

**Level:** 1

**Type:** ERROR

---

**Impact:** Upgrade

**UPGAST-01012: unable to load PL/SQL package DBMS\_IAS\_VERSION**

**Cause:** Repository upgrade framework was unable to load or validate the PL/SQL package DBMS\_IAS\_VERSION. This is an internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Upgrade

**UPGAST-01013: unable to load PL/SQL package DBMS\_IAS\_VERSION10G**

**Cause:** Repository upgrade framework was unable to load or validate the PL/SQL package DBMS\_IAS\_VERSION10G. This is an internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Upgrade

**UPGAST-01014: Component-specific software module raised an exception: {0}.**

**Cause:** During repository upgrade one of the component-specific software modules raised an uncaught exception to the upgrade framework. This is an internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-01015: Some repository upgrade component-specific software modules report failure.**

**Cause:** One or more component-specific software modules returned an error status during repository upgrade. Some other components might have upgraded successfully.

**Action:** Review the upgrade logs to determine which components have failed, and pinpoint the source of the errors for each component. Correct the conditions that caused the errors. It may be possible to rerun the upgrade.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-01016: Upgrade from OracleAS release {0} is not allowed.**

**Cause:** Repository upgrade framework detected that the metadata repository is from an OracleAS release that is no longer supported for upgrade to the current release.

**Action:** Start with an OracleAS release that is directly upgradable to the current release. It may be necessary to perform the upgrade as a two-step process. First upgrade the repository to a newer release that is supported by the current release of Oracle Fusion Middleware. Then repeat the upgrade process from that supported release to the current release of Oracle Fusion Middleware.



---

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-01017: Some Oracle Fusion Middleware components not set to VALID status in schema\_version\_registry. Check the log file.**

**Cause:** During repository upgrade one or more components did not record the necessary version and status information in SCHEMA\_VERSION\_REGISTRY. This is an internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-01018: {0} component version is: {1} {2} upgraded flag is: {3}.**

**Cause:** During repository upgrade one or more components reported a successful upgrade but the version and status information was not updated in SCHEMA\_VERSION\_REGISTRY. This is an internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-01019: {0} is not in schema\_version\_registry namespace {1}.**

**Cause:** Repository upgrade framework detected that the named component was missing a required entry in SCHEMA\_VERSION\_REGISTRY. This might be caused by an internal error or incorrect configuration before the upgrade was performed. The component might not be recorded in the repository database.

**Action:** Verify that the component already has been created in the repository database by Repository Creation Utility (RCU) under the same namespace being used for upgrade. Retry the upgrade. If RCU has created the component schemas and the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** INTERNAL\_ERROR

**Impact:** Upgrade

**UPGAST-01020: Oracle home {0} does not exist.**

**Cause:** Repository upgrade framework detected that the OracleHome input parameter refers to a nonexistent or inaccessible directory.

**Action:** Verify that the OracleHome parameter has been specified correctly and refers to an existing Oracle home directory. If the directory exists, verify that the file permissions on the directory permit access. Retry the upgrade operation.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-01021: Oracle home {0} does not contain the bin directory.**

---

**Cause:** Repository upgrade framework determined that the OracleHome input parameter refers to an existing directory; however, that directory lacked a bin subdirectory. The directory did not appear to be a valid Oracle home.

**Action:** Verify that the OracleHome parameter refers to an existing Oracle home directory, which must contain a bin subdirectory. Retry the upgrade.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-01022: Metadata repository is at MRC version: {0}.**

**Cause:** Repository upgrade detected that the metadata repository that was being upgraded is currently at the version listed in the message. This is an informational message.

**Action:** No action is needed.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Upgrade

**UPGAST-01023: Metadata repository database is at RDBMS version: {0}.**

**Cause:** Repository upgrade framework detected that the metadata repository database is at the version release number listed in the message. This is an informational message.

**Action:** No action is needed.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Upgrade

**UPGAST-01024: Oracle home {0} does not contain the rdbms directory.**

**Cause:** Repository upgrade framework determined that the OracleHome input parameter refers to an existing directory, however, that directory lacked the rdbms subdirectory. The directory did not appear to be a valid Oracle home.

**Action:** Verify that the OracleHome parameter points to an existing Oracle home directory that contains an rdbms subdirectory. Retry the upgrade.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-01025: Loaded PL/SQL package DBMS\_IAS\_VERSION.**

**Cause:** Repository upgrade framework successfully loaded and validated the PL/SQL package DBMS\_IAS\_VERSION. This is an informational message.

**Action:** No action is needed.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Upgrade

**UPGAST-01026: DBMS\_IAS\_VERSION package version is: {0}.**

---

**Cause:** Repository upgrade framework determined that the PL/SQL package DBMS\_IAS\_VERSION was at the software revision level specified in the message. This is an informational message.

**Action:** No action is needed.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Upgrade

**UPGAST-01027: not installed**

**Cause:** Repository upgrade framework detected that a necessary software component was not installed. This is an internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-01028: All repository upgrade component-specific software modules report success.**

**Cause:** Repository upgrade framework detected that all components reported success during the examination or upgrade phase of repository upgrade. All components returned either the upgrade successful or the already upgraded status. This message is displayed after repository upgrade has completed successfully. This is an informational message.

**Action:** No action is needed.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Upgrade

**UPGAST-01029: All Oracle Fusion Middleware components set to VALID status in schema\_version\_registry.**

**Cause:** Repository upgrade framework reports that all components were set to the VALID state in SCHEMA\_VERSION\_REGISTRY, and all component version numbers were correct. This is an informational message.

**Action:** No action is needed.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Upgrade

**UPGAST-01030: Component {0} has valid schema\_version\_registry settings after upgrade.**

**Cause:** The component named in the message had the correct and expected data in SCHEMA\_VERSION\_REGISTRY. This is an informational message.

**Action:** No action is needed.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Upgrade

---

**UPGAST-01031: {0} is not in schema\_version\_registry namespace {1}.**

**Cause:** The repository upgrade component-specific software module reported that an optional component was not found in SCHEMA\_VERSION\_REGISTRY. This is an informational message.

**Action:** No action is needed.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Upgrade

**UPGAST-01032: {0} app\_registry entry is: {1} {2}.**

**Cause:** Repository Upgrade component-specific software module reported that the named component has an entry in the 10g APP\_REGISTRY view. This is an informational message.

**Action:** No action is needed.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Upgrade

**UPGAST-01033: {0} schema\_registry entry is: {1} {2} namespace {3}.**

**Cause:** Repository upgrade component-specific software module reported that the named component has this version and status information recorded in SCHEMA\_VERSION\_REGISTRY under the specified namespace. This is an informational message.

**Action:** No action is needed.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Upgrade

**UPGAST-01034: Verify that connect string is correct and database listener process is started.**

**Cause:** Repository upgrade framework was unable to connect to the metadata repository database. This might be caused by an invalid database connection string, or because the database listener was down.

**Action:** Verify that connect string is correct and database listener process is started.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-01035: Verify that user name and password are correct.**

**Cause:** Repository upgrade framework was unable to connect to the metadata repository database. This might have been caused by an invalid user name or password. This is a warning message.

**Action:** Verify that user name and password are correct.

**Level:** 1

**Type:** ERROR

---

**Impact:** Upgrade

**UPGAST-01036: Connect as user 'SYS AS SYSDBA', not just 'SYS'.**

**Cause:** Repository upgrade framework was unable to connect to the metadata repository database. The possible cause is that the user name must be SYS AS SYSDBA, not SYS. This is a warning message.

**Action:** Connect as user 'SYS AS SYSDBA', not just 'SYS'.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-01037: Start the database.**

**Cause:** Repository upgrade framework was unable to connect to the metadata repository database. The possible cause is that the database instance is down and needs to be started. This is a warning message.

**Action:** Start the database.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-01038: Oracle Fusion Middleware Repository Upgrade Framework {0}**

**Cause:** Repository upgrade framework reported its software product version. This is an informational message.

**Action:** No action is needed.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Upgrade

**UPGAST-01039: error while reading from app\_registry**

**Cause:** The repository upgrade component-specific software module encountered an error while attempting to access the OracleAS 10g APP\_REGISTRY view. This is an internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-01040: {0} is not present in app\_registry.**

**Cause:** The repository upgrade component-specific software module detected that a component is missing an entry in the OracleAS 10g APP\_REGISTRY view. This error condition will cause the examination phase of upgrade to fail.

**Action:** Verify that the database being upgraded contains an OracleAS Metadata Repository. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

---

**UPGAST-01041: {0} is not present in app\_registry.**

**Cause:** Repository upgrade component-specific software module detected that an optional component is missing from the 10g APP\_REGISTRY view. This is an informational message.

**Action:** No action is needed.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Upgrade

**UPGAST-01042: SQL version and status query failed for component {0}.**

**Cause:** The repository upgrade component-specific software module encountered an error while trying to obtain version and status information for the component. This is an internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-01043: unable to connect to the source database**

**Cause:** Repository upgrade framework was unable to connect to the source database instance. The database might be down, or the password might be incorrect.

**Action:** Verify that the source connect string, user name, and password are correct. Verify that the database server and listener are running. Examine the log file for additional information.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-01044: unable to connect to the target database**

**Cause:** Repository upgrade framework was unable to connect to the target database instance. The database might be down, or the password might be incorrect.

**Action:** Verify that the target connect string, user name, and password are correct. Verify that the database server and listener are running. Examine the log file for additional information.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-01045: Database version {0} is not supported.**

**Cause:** A database connection could not be established because the database type identifier was not recognized as one of the known types that are supported by Repository Upgrade.

**Action:** Use only a supported database type either Oracle or Microsoft.

**Level:** 1

---

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-01047: Repository upgrade component-specific software module protocol error.**

**Cause:** During execution of a repository upgrade component-specific software module, the upgrade mode was neither examine nor upgrade.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-01048: Repository upgrade internal protocol error.**

**Cause:** During execution of schema upgrade an uncaught exception was raised during the examine or upgrade phases.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-01050: error loading config file {0}**

**Cause:** The Assistant failed to load its configuration file.

**Action:** See secondary message for details.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-01051: unable to connect to the Oracle B2B schema {0}**

**Cause:** Repository upgrade framework was unable to connect to the Oracle B2B schema. The database might be down, or the password might be incorrect.

**Action:** Verify that the host, port, service name, and password are correct. Verify that the database server and listener are running. Examine the log file for additional information.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-01052: unable to connect to the Oracle BAM schema {0}.**

**Cause:** Repository upgrade framework was unable to connect to the Oracle BAM database schema. The database might be down, or the password might be incorrect.

**Action:** Verify that the host, port, service name, and password are correct. Verify that the database server and listener are running. Examine the log file for additional information.

**Level:** 1

**Type:** ERROR

---

**Impact:** Upgrade

**UPGAST-01060: SCHEMA\_VERSION\_REGISTRY table CUSTOM1 or CUSTOM2 column is missing.**

**Cause:** Repository Upgrade framework detected that the SCHEMA\_VERSION\_REGISTRY database table is missing the CUSTOM1 or CUSTOM2 columns. This error message identifies an older preproduction version of schema version registry table that is no longer compatible with current software. The two custom columns need to be added to correct the problem. This is an interim error condition that can occur during product development cycle but will not occur in the production version of Oracle Fusion Middleware.

**Action:** The two missing columns CUSTOM1 and CUSTOM2 need be added to the schema version registry table. After the columns have been added this error will not appear again, and OFM Upgrade Assistant can be run again. To add the missing columns the user should connect to the database as SYS or SYSTEM user and then execute this SQL statement which will add the two missing columns to the table: ALTER TABLE SYSTEM.SCHEMA\_VERSION\_REGISTRY\$ ADD (custom1 NUMBER, custom2 VARCHAR2(30));

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-01061: Exception raised while repository upgrade was attempting to access MAS topology for BAM: {0}.**

**Cause:** Repository upgrade framework was unable to access the MAS topology for BAM. The error message displays the base exception that caused the failure. This error message indicates a severe error condition.

**Action:** Verify that BAM has been installed and configured for this instance. Verify that the MAS topology service is running. Examine the log file for additional information. Contact Oracle Support Services if BAM has been installed and configured yet this error persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-01062: Exception raised while repository upgrade was running an external command.**

**Cause:** An exception was raised while running an external command (such as sqlplus) in a subprocess. Check the stack trace for detailed information.

**Action:** Attempt to correct the environment problem if any, then retry the upgrade. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-01063: Exception raised while repository upgrade was performing SQL queries.**

**Cause:** An exception was raised while performing SQL operations to determine schema versions. Check the stack trace for detailed information.



---

**Action:** Attempt to correct the environment problem if any, then retry the upgrade. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-01064: The MAS topology for Business Intelligence may be corrupted. Unable to fetch node: {0} of {1}.**

**Cause:** Repository upgrade framework was unable to access the MAS topology for Business Intelligence. The error message indicates which topology node was missing. Either Business Intelligence is not configured for this instance, or the Business Intelligence topology is corrupt. This error message indicates a severe error condition.

**Action:** Verify that Business Intelligence has been installed and configured for this instance. Verify that the MAS topology service is running. Examine the log file for additional information. Contact Oracle Support Services if BI has been installed and configured yet this error persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-01065: LDAP DBCN entry is corrupted. Unable to fetch node: {0} of {1}.**

**Cause:** Repository upgrade framework was unable to access the LDAP directory to obtain a list of OracleAS 10g Metadata Repositories. The error message indicates which topology node was missing. This error message indicates a severe error condition.

**Action:** Delete the directory record that was identified as being corrupt. Examine the log file for additional information. After deleting the corrupt record, retry the repository upgrade that failed. Contact Oracle Support Services if this error persists.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-01066: unable to connect to the Oracle OIM schema {0}.**

**Cause:** Repository upgrade framework was unable to connect to the Oracle OIM database schema. The database might be down, or the password might be incorrect.

**Action:** Verify that the host, port, service name, and password are correct. Verify that the database server and listener are running. Examine the log file for additional information.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-01067: unable to connect to the Oracle ODI schema {0}.**

---

**Cause:** Repository upgrade framework was unable to connect to the Oracle ODI database schema. The database might be down, or the password might be incorrect.

**Action:** Verify that the host, port, service name, and password are correct. Verify that the database server and listener are running. Examine the log file for additional information.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-01068: unable to connect to the Oracle OAAM schema {0}.**

**Cause:** Repository upgrade framework was unable to connect to the Oracle OAAM database schema. The database might be down, or the password might be incorrect.

**Action:** Verify that the host, port, service name, and password are correct. Verify that the database server and listener are running. Examine the log file for additional information.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-01069: PostgreSQL JDBC driver SHA1 signature is invalid. Expected: {0} Computed: {1}.**

**Cause:** The user has chosen an upgrade with a PostgreSQL database but the JDBC driver that was found does not have the expected SHA1 signature.

**Action:** Locate the precise version of the PostgreSQL JDBC driver jar file that Oracle has certified, and copy it into the ORACLE\_HOME/jlib directory. The name of the jar file must match the expected name, and the SHA1 signature of the file must match the expected value.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-01070: Unable to process PostgreSQL JDBC driver jar file for SHA1.**

**Cause:** The user has chosen an upgrade with a PostgreSQL database but the JDBC driver that was found does not have the expected SHA1 signature.

**Action:** Locate the precise version of the PostgreSQL JDBC driver jar file that Oracle has certified, and copy it into the ORACLE\_HOME/jlib directory. The name of the jar file must match the expected name, and the SHA1 signature of the file must match the expected value.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-01071: Unable to close input stream for SHA1 calculation.**

**Cause:** The user has chosen an upgrade with a PostgreSQL database and while computing the SHA signature of the JDBC driver an internal error was detected while closing the input stream.

---

**Action:** This is an internal error. Locate the precise version of the PostgreSQL JDBC driver jar file that Oracle has certified, verify the file is not zero-length, and copy it into the ORACLE\_HOME/jlib directory. The name of the jar file must match the expected name, and the SHA1 signature of the file must match the expected value.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-01072: unable to connect to the Oracle BI schema {0}**

**Cause:** Repository upgrade framework was unable to connect to the Oracle BI schema. The database might be down, or the password might be incorrect.

**Action:** Verify that the host, port, service name, and password are correct. Verify that the database server and listener are running. Examine the log file for additional information.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-01073: unable to connect to the Oracle ECM schema {0}**

**Cause:** Repository upgrade framework was unable to connect to the Oracle ECM schema. The database might be down, or the password might be incorrect.

**Action:** Verify that the host, port, service name, and password are correct. Verify that the database server and listener are running. Examine the log file for additional information.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-01074: unable to connect to the database {0}**

**Cause:** Repository upgrade framework was unable to connect to the database instance. The database might be down, or the password might be incorrect.

**Action:** Verify that the host, port, service name, and password are correct. Verify that the database server and listener are running. Examine the log file for additional information.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-01075: An in-place upgrade will be performed on the original copy of database schemas**

**Cause:** While performing an ODI schema upgrade user has unchecked the option box labeled 'Check that Upgrade Occurs Only on Cloned Repositories'

**Action:** By unchecking this option box the user acknowledges that the ODI upgrade will modify the original copy of the ODI database schemas. Verify that a backup has been taken of the ODI schemas prior to upgrade when using this option.

---

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-02001: Unable to connect to {0} because {1}.**

**Cause:** The identified server could not be contacted.

**Action:** Review the log file for the server. Verify that the source of the URL is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-02002: Repository schema {0} wrong status {1} or version {2}.**

**Cause:** Something went wrong the last time the metadata repository was upgraded.

**Action:** Check the log from the repository upgrade.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-02003: unable to obtain port number.**

**Cause:** Component was not running or was misconfigured.

**Action:** Check that the component is running.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-02004: Error {1} while requesting {0}.**

**Cause:** The server was unavailable.

**Action:** Review the log file for the server. Verify that the source of the URL is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-02005: Verification has run into an unexpected error {1} on object {0}.**

**Cause:** An unexpected error occurred during verification.

**Action:** See the secondary message for additional details.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGAST-02006: Request to {0} URL {1} received error "{2}".**

**Cause:** The identified server did not respond as expected.

**Action:** Review the identified server's log to identify the problem.

---

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGAST-02007: Unable to find a schema with password to test on database {0}.**

**Cause:** To verify that the database is available, verification looks in the Credential Store for schema credentials. It was unable to locate a schema with credentials.

**Action:** None. The database cannot be tested.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade



---

## UPGCMP-00019 to UPGCMP-05203

**UPGCMP-00019: Component {0} is not in the SCHEMA\_VERSION\_REGISTRY for namespace {1}.**

**Cause:** Repository upgrade framework detected that the named component was missing a required entry in SCHEMA\_VERSION\_REGISTRY. This might be due to an internal error or incorrect configuration before the upgrade was performed. The component might be missing from the repository database.

**Action:** Verify that the component already has been created in the repository database by the Repository Creation Utility under the same namespace being used for upgrade. Retry the upgrade. If the Repository Creation Utility has created the component schemas and the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00037: Component {0} is not present in the SCHEMA\_VERSION\_REGISTRY for namespace {1}.**

**Cause:** The repository upgrade component-specific software module discovered that an optional component was not present in SCHEMA\_VERSION\_REGISTRY. This is an informational message.

**Action:** No action is needed.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Upgrade

**UPGCMP-00038: Component {0} app\_registry entry is: {1} {2}.**

**Cause:** Repository upgrade component-specific software module detected that the component had an entry in the 10g APP\_REGISTRY view. This is an informational message.

**Action:** No action is needed.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Upgrade

**UPGCMP-00039: Component {0} schema\_registry entry is: {1} {2} in the namespace {3}.**

---

**Cause:** Repository upgrade component-specific software module logged this data that was retrieved from SCHEMA\_VERSION\_REGISTRY. This is an informational message.

**Action:** No action is needed.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Upgrade

**UPGCMP-00045: failure reading from app\_registry**

**Cause:** Repository upgrade component-specific software module encountered an error while attempting to access the OracleAS 10g APP\_REGISTRY view. This is an internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00046: Component {0} is not present in app\_registry.**

**Cause:** Repository upgrade component-specific software module detected that a component was missing an entry in the OracleAS 10g APP\_REGISTRY view. This error condition will cause the examination phase of upgrade to fail.

**Action:** Verify that the database being upgraded contains an OracleAS metadata repository. If the problem persists notify Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00047: Component {0} is not present in app\_registry.**

**Cause:** Repository upgrade component-specific software module detected that an optional component was missing from the 10g APP\_REGISTRY view. This is an informational message.

**Action:** No action is needed.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Upgrade

**UPGCMP-00048: SQL version and status query failed for component {0}.**

**Cause:** The repository upgrade component-specific software module encountered an error while trying to obtain version and status information for the component. This is an internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00049: unable to connect to the source database**



---

**Cause:** Repository upgrade was unable to connect to the source database instance. The database might be down, or the password might be incorrect.

**Action:** Verify that the source connect string, user name, and password are correct. Verify that the database server and listener are running. Examine the log file for additional information.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00050: unable to connect to the target database**

**Cause:** Repository upgrade was unable to connect to the target database instance. The database might be down, or the password might be incorrect.

**Action:** Verify that the target connect string, user name, and password are correct. Verify that the database server and listener are running. Examine the log file for additional information.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00101: unable to retrieve password for {0} schema**

**Cause:** Oracle Portal repository upgrade component-specific software module encountered an error while fetching Oracle Portal password from Oracle Internet Directory.

**Action:** Verify that the Oracle Internet Directory associated with Oracle Portal is up and running and the Oracle Portal password within the Oracle Internet Directory is accessible. After making sure that Oracle Internet Directory is accessible, retry the upgrade.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00102: Oracle Portal {0} upgrade log files available in {1}.**

**Cause:** The location of Oracle Portal repository upgrade logs was generated by the Oracle Portal component-specific software module. This is an informational message.

**Action:** No action is needed.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Upgrade

**UPGCMP-00103: cannot find Perl in the Oracle home**

**Cause:** Perl was missing from the Oracle home.

**Action:** Verify that the Oracle home where you are running the Assistant contains the Perl executable.

**Level:** 1

**Type:** ERROR

---

**Impact:** Upgrade

**UPGCMP-00104: failure during the Oracle Portal {0} run**

**Cause:** An error occurred either during Oracle Portal precheck run or upgrade run.

**Action:** Contact Oracle Support Services with the log file details.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00105: failure with progress bar during the upgrade phase of Oracle Portal**

**Cause:** An unexpected error was encountered updating the progress bar.

**Action:** The Oracle Portal component upgrade was not impacted and the error can be ignored.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Upgrade

**UPGCMP-00201: missing 10g Entry in SCHEMA\_VERSION\_REGISTRY**

**Cause:** Oracle Internet Directory schema details were not found in the SCHEMA\_VERSION\_REGISTRY table.

**Action:** Refer to the Upgrade Guide for Oracle Identity Management for steps to perform the OID upgrade.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00202: The upgrade is not supported from a schema version of {0}.**

**Cause:** An unsupported base schema version was being upgraded.

**Action:** Refer to the Upgrade Guide for Oracle Identity Management for supported versions for upgrade.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00203: failure retrieving ODSSM schema password**

**Cause:** There is no LDAP attribute entry for the ODSSM schema password.

**Action:** Create 'orclPasswordAttribute' in the Oracle Internet Directory with ODSSM schema password under entry: 'cn=dsconfig,cn=configsets,cn=oracle internet directory' for upgrade to work.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00204: failure during upgrade precheck: {0}**

---

**Cause:** Error occurred during the Oracle Internet Directory upgrade precheck.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00205: The ODS schema upgrade is INVALID.**

**Cause:** Some of the packages in the Oracle Internet Directory schema were INVALID after upgrade.

**Action:** To see which objects are invalid, log in to the Database as user 'ODS' and execute 'select object\_name from user\_objects where status='INVALID' '. Restore the backed up database and correct the schema before running the Assistant again.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00206: error during Oracle Internet Directory upgrade: {0}**

**Cause:** An unexpected error occurred during Oracle Internet Directory Upgrade.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00207: Error getting OID Component name and ASInstance name**

**Cause:** Unable to get values from 11g opmn.xml

**Action:** 1. Check that 11g OPMN is running 2. Check that \$ORACLE\_INSTANCE/config/OPMN/opmn/opmn.xml exists 3. Contact Oracle Support Services if the above steps do not help you resolve the problem.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00208: Could not read details from OID subregistrysubentry**

**Cause:** An error occurred while reading entries from 10g OID

**Action:** 1. Make sure 10g OID is up and running 2. Contact Oracle Support Services if the above steps do not help you resolve the problem

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00209: error while contacting Oracle Internet Directory: {0}**

**Cause:** unable to connect to the Oracle Internet Directory server. See the exception details for exactly what happened.

**Action:** 1. Check that Oracle Internet Directory is running. 2. Check that the Oracle Internet Directory connection details are correct in preceding messages in this log.

---

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00210: exception during LDAP schema upgrade : {0}**

**Cause:** Check the preceding messages in this log for detailed cause.

**Action:** 1. Check the preceding messages in this log for the specific problem. 2. Ensure that the Oracle Internet Directory server is up. 3. Ensure that the Oracle Internet Directory connection credentials are correct. 4. Contact Oracle Support Services if the above steps do not resolve the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00211: error during Oracle Internet Directory schema upgrade: {0}**

**Cause:** An error in SQL processing was detected during Oracle Internet Directory schema upgrade.

**Action:** Check the SQL messages in \$ORACLE\_HOME/upgrade/logs/ua<timestamp>.out for the problem and correct the problem before running the Assistant again. Contact Oracle Support Services if you are unable to correct the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00212: error during Oracle Internet Directory schema validation: {0}**

**Cause:** An error occurred during validation of the ODS schema.

**Action:** 1. Check if Database is running. 2. Check the preceding messages in this log for any errors. Contact Oracle Support Services if you are unable to correct the problem.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00213: error starting Oracle Internet Directory server with retained ports**

**Cause:** An unexpected error occurred while setting Oracle Internet Directory ports to their 10g values.

**Action:** Check the preceding messages in this log for detailed cause.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00214: error trying to start the Oracle Internet Directory server: {0}**

**Cause:** An unexpected error occurred when trying to restart the Oracle Internet Directory server after the schema upgrade. See the detailed message at \$OI/diagnostics/logs/OID/<oid\_comp\_name>/oidmon\*.log

---

**Action:** 1. Check that OPMN is running. 2. Check whether Oracle Internet Directory was already running 3. Contact Oracle Support Services if the above steps do not help resolve the problem.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00215: Error connecting to database: {0}**

**Cause:** An error occurred when trying to contact/connect to Oracle Database

**Action:** 1. Check that Database is running. 2. Check the preceding messages in this log for any errors. 3. Contact Oracle Support Services if the above steps do not help resolve the problem.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00216: Error reading {0} value from {1} file**

**Cause:** An error occurred when trying to read a value from the specified file.

**Action:** 1. Check that the specified file exists and is readable. 2. Check the preceding messages in this log for any errors. 3. Contact Oracle Support Services if the above steps do not help resolve the problem.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00217: Error writing {0} value to {1} file**

**Cause:** An error occurred when trying to write a value to the specified file.

**Action:** 1. Check that the specified file exists and is write-enabled. 2. Check the preceding messages in this log for any errors. 3. Contact Oracle Support Services if the above steps do not help resolve the problem.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00218: Missing value for {0} in the {1} file**

**Cause:** An error occurred when trying to read a value from the specified file.

**Action:** 1. Add the missing value in the specified file and retry. 2. Check the preceding messages in this log for any errors. 3. Contact Oracle Support Services if the above steps do not help resolve the problem.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00219: Error deleting the {0} file**

**Cause:** An error occurred when trying to delete the specified file.

---

**Action:** 1. Manually delete the specified file and your upgrade is complete. 2. Check the preceding messages in this log for any errors. 3. Contact Oracle Support Services if the above steps do not help resolve the problem.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00220: Error updating registration details of OID in WLS: {0}**

**Cause:** An error occurred when trying to run 'opmnctl updatecomponentregistration' for OID.

**Action:** 1. Check the preceding messages in this log to see if the WLS server details are right. 2. Check if the WLS server is up and running. 3. Check the preceding messages in this log for any errors. 4. Manually run \$Oracle\_Instance/bin/opmnctl updatecomponentregistration for OID at the end of upgrade. 5. Contact Oracle Support Services if the above steps do not help resolve the problem.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00221: Error finding OID MBean in WLS: {0}**

**Cause:** An error occurred when trying to find OID Mbean 'oracle.as.management.mbeans.register:instance=<instName>,Location=AdminServer,name=<oidCompName>,type=component' in WLS.

**Action:** 1. Check the preceding messages in this log to see if the WLS server details are right. 2. Check if the WLS server is up and running. 3. Check the preceding messages in this log for any errors. 4. Manually register OID component in WLS after upgrade. Refer to the OPMN documentation for the same. 5. Contact Oracle Support Services if the above steps do not help resolve the problem.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00222: error trying to stop the Oracle Internet Directory server: {0}**

**Cause:** An unexpected error occurred when trying to stop the Oracle Internet Directory server after the schema upgrade. See the detailed message.

**Action:** 1. Check that OPMN is running. 2. Check whether Oracle Internet Directory was already stopped 3. Contact Oracle Support Services if the above steps do not help resolve the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00223: error trying to start the Oracle Process Manager(OPMN): {0}**

**Cause:** An unexpected error occurred when trying to start the Oracle Process Manager after the schema upgrade. See the detailed message at \$OI/diagnostics/logs/OPMN/opmn/opmn.log

---

**Action:** 1. Check that OPMN port is not occupied. 2. Check whether OPMN was already running 3. Contact Oracle Support Services if the above steps do not help resolve the problem.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00224: error trying to add configset entry to OID: {0}**

**Cause:** An unexpected error occurred when trying to add configset entry to OID using oidctl. See the detailed message at \$OI/diagnostics/logs/OID/<oid\_component\_name>/oidctl.log

**Action:** 1. Check that oidctl binary is present under \$OH/bin directory. 2. Verify that the connectstring used in oidctl syntax is the same as the one in \$OI/config/tnsnames.ora file. 3. Contact Oracle Support Services if the above steps do not help resolve the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00225: Error trying to set the SSL properties in the new 11g configset entry of OID: {0}**

**Cause:** An unexpected error occurred when trying to add ssl properties to OID.

**Action:** 1. Check that orclsslwalleturl attribute value is a valid path. 2. Contact Oracle Support Services if the above steps do not help resolve the problem.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00302: Target Master Repository is invalid.**

**Cause:** Target Master Repository wasn't found in the given schema.

**Action:** Define valid Target Master Repository credentials.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00303: Target Work Repository {0} is invalid.**

**Cause:** Target Work Repository wasn't found in the given schema.

**Action:** Define valid Target Work Repository credentials.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00304: Target Master Repository is not clone.**

**Cause:** Target and Source Master Repositories are the same.

**Action:** Make clone of Source Master Repository.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00305: Target Work Repository {0} is not clone.**

**Cause:** Target Work Repository and Source Master Repositories are the same.

**Action:** Enter correct credentials for Target Work Repository.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00306: Target Work Repository {0} is not clone.**

**Cause:** Target Work Repository has the same schema as Sourcer Work Repository.

**Action:** Enter correct credentials for Target Work Repository.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00307: More than one Target Work Repository has the same credentials as Target Master Repository.**

**Cause:** Only one Target Work Repository is allowed to have the same credentials as Target Master Repository.

**Action:** Enter correct credentials for Target Work Repositories.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00308: Target Work Repository {0} must have the same credentials as Target Master Repository.**

**Cause:** Wrong Target Work Repository has the same credentials as Target Master Repository.

**Action:** Enter correct credentials for Target Work Repository.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00309: Same Target Work Repositories credentials**

**Cause:** Two or more Target Work Repository have the same schema name.

**Action:** Enter correct credentials for Target Work Repositories.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00310: Target Work Repository {0} has the same credentials as Target Master Repository.**



---

**Cause:** Source Master Repository doesn't host Work Repository.

**Action:** Check credentials for Target Work Repository.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00311: Folder with 11g KM is not available**

**Cause:** Folder oracledi/xml-reference/ doesn't exist

**Action:** Check you ODI Home folder.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00327: Invalid credentials for ODI Supervisor.**

**Cause:** A wrong credentials were provided to upgrade Master and Work Repositories.

**Action:** Enter correct credentials for ODI Supervisor.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00328: Target Work Repository {0} is invalid.**

**Cause:** Target Work Repository doesn't belong to Master Repository.

**Action:** Define valid Target Work Repository credentials.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00401: The BIPublisher {0} run has an error. {1}.**

**Cause:** An error occurred either during BIPublisher precheck run or upgrade run.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00402: unable to get target schema prefix**

**Cause:** 11g schema prefix is not provided.

**Action:** Enter value for option '-schemaPrefix' while invoking the upgrade utility.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00403: 10g schema for BIPublisher does not have VALID status in SCHEMA\_VERSION\_REGISTRY**

---

**Cause:** The BIPublisher 10g schema version registry entry is invalid.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00404: 11g schema for BIPublisher does not have VALID status in SCHEMA\_VERSION\_REGISTRY.**

**Cause:** The BIPublisher 11g schema version registry entry is invalid.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00405: The table {0} doesn't exist.**

**Cause:** The upgrade assistant couldn't find the table.

**Action:** Check the upgrade assistant has access to the table.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00406: Error: A SQL error occurred during the migration.**

**Cause:** Perhaps the tablespace or log file is full.

**Action:** Notify your DBA. If unable to resolve, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00407: Error: Database connections for 10g and 11g are not the same type.**

**Cause:** The database types must be the same (i.e., migrating from DB2 to Oracle is disallowed).

**Action:** Ensure both database connections are of same type.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00408: Error: Table {0} does not exist in 10g instance.**

**Cause:** Perhaps the scheduler was not installed under this database account.

**Action:** Ensure that the appropriate database account is specified.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00409: Error: Table {0} does not exist in 11g instance.**

---

**Cause:** Perhaps the scheduler was not installed under this database account.

**Action:** Ensure that the appropriate database account is specified.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00410: Error: Failed to create connection for user {0} using connection string {1}.**

**Cause:** The username, password, or other connection information was incorrect.

**Action:** Provide the correct connection information.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00501: Directory {0} does not exist.**

**Cause:** The upgrade directory is required for the upgrade task to proceed.

**Action:** Create the directory shown in the error and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00502: No zip file is found for import in {0}.**

**Cause:** A required zip file was missing from the specified upgrade directory.

**Action:** Run the export utility on 10.1.2 and copy the zip file to the upgrade directory.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00503: error during the {0} phase of Oracle B2B upgrade**

**Cause:** An error occurred either during Oracle B2B precheck run or upgrade run.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00504: MDS configuration exception is detected during Oracle B2B upgrade: {0}.**

**Cause:** During the Oracle B2B schema upgrade an MDS configuration exception was detected. Refer to the secondary error message for details about the cause of the failure.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Upgrade

**UPGCMP-00505: MDS exception is detected during Oracle B2B upgrade: {0}.**

**Cause:** During the Oracle B2B schema upgrade an MDS exception was detected. Refer to the secondary error message for details about the cause of the failure.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00506: No files are found for import in {0}.**

**Cause:** A required .zip file was missing from the specified upgrade directory.

**Action:** Run the export utility on 10.1.2 and copy the zip file to the upgrade directory.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00507: MDS transfer fails due to secondary error {0}.**

**Cause:** An error occurred while transferring data from MDS. Refer to the secondary error message for details about the cause of the failure.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00701: The Discoverer {0} run has an error. {1}.**

**Cause:** An error occurred either during Discoverer precheck run or upgrade run.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00702: unable to get target schema prefix**

**Cause:** 11g schema prefix is not provided.

**Action:** Enter value for option '-schemaPrefix' while invoking the upgrade utility.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00703: 10g schema for Discoverer does not have VALID status in SCHEMA\_VERSION\_REGISTRY**

**Cause:** The Discoverer 10g schema version registry entry is invalid.

**Action:** Contact Oracle Support Services.

**Level:** 1

---

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00704: 11g schema for Discoverer does not have VALID status in SCHEMA\_VERSION\_REGISTRY.**

**Cause:** The Discoverer 11g schema version registry entry is invalid.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00705: Discoverer 10g database objects are not available or not in a valid state.**

**Cause:** Discoverer 10g database objects were not available or not in a valid state.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00706: Discoverer 11g database objects are not available or not in a valid state.**

**Cause:** Discoverer 11g database objects were not available or not in a valid state.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00707: Discoverer 10g metadata record with key {0} is corrupt. {1}.**

**Cause:** Specified Discoverer 10g metadata record is corrupt.

**Action:** Delete the corrupted record and rerun metadata repository upgrade.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00801: error during the Oracle BAM {0} run**

**Cause:** An error occurred either during Oracle BAM precheck run or upgrade run.

**Action:** Contact Oracle Support Services with the log file details.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00802: Oracle BAM precheck failure**

**Cause:** An error occurred during Oracle BAM precheck run.

**Action:** Contact Oracle Support Services with the log file details.

**Level:** 1

---

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00803: Oracle BAM upgrade failure**

**Cause:** An error occurred during Oracle BAM upgrade run.

**Action:** Contact Oracle Support Services with the log file details.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-00808: Oracle BAM OC4J is running. Stop the Oracle BAM OC4J application and retry the upgrade.**

**Cause:** Oracle BAM OC4J was running.

**Action:** Oracle BAM OC4J instance is running. Stop the Oracle BAM OC4J and retry the upgrade.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00809: The Oracle BAM schema is not a valid 10.1.3 schema.**

**Cause:** The Oracle BAM database schema was not a valid 10.1.3 schema.

**Action:** Ensure that the Oracle BAM schema is a version 10.1.3 schema.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-00901: Failed to update the rule Dictionary at {0}**

**Cause:** Error occurred while trying to update dictionary

**Action:** Moved the composite to Partially\_Upgraded\_Composites. Upgrade the composite manually.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**UPGCMP-00902: Invalid arguments are passed.**

**Cause:** Invalid arguments are passed

**Action:** Moved the composite to Partially\_Upgraded\_Composites. Upgrade the composite manually.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**UPGCMP-00903: Failed to create a template project at {0}**

**Cause:** Error occurred while creating the template BPEL composite

**Action:** Upgrade the Approval process manually.

---

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**UPGCMP-00904: Invalid target type {0} encountered.**

**Cause:** Invalid target type is encountered while generation of rules in BPEL composite.

**Action:** Moved the composite to Partially\_Upgraded\_Composites. Upgrade the composite manually.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**UPGCMP-00905: Rule with rule key {0} is not default rule.**

**Cause:** The Approval process contains only a single rule which is not default rule.

**Action:** Moved the composite to Partially\_Upgraded\_Composites. Upgrade the composite manually.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**UPGCMP-00906: Failed to retrieve user login for the user with key {0}**

**Cause:** Error in retrieving user details from the database.

**Action:** Moved the composite to Partially\_Upgraded\_Composites. Upgrade the composite manually.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**UPGCMP-00907: Failed to retrieve group name for the group with key {0}**

**Cause:** Error in retrieving group details from the database.

**Action:** Moved the composite to Partially\_Upgraded\_Composites. Upgrade the composite manually.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**UPGCMP-00908: Approval Task is associated with a custom adapter**

**Cause:** {0} is associated with a task assignment adapter

**Action:** {0} : Implement the task assignment logic in corresponding BPEL Composite.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**UPGCMP-00909: Callback URL cannot be set**

---

**Cause:** Cannot set the callback url in file {0}  
**Action:** Set the Callback URL manually in the file {0}

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**UPGCMP-00910: Cannot locate the project**

**Cause:** Cannot locate the project at {0}

**Action:** Check the project location and upgrade the process manually

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**UPGCMP-00911: Error in writing parsed XML Document to File**

**Cause:** Error in writing parsed XML Document to File : {0}. Cause : {1}

**Action:** Upgrade the process manually

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**UPGCMP-00912: Rule construction is based on Task information.**

**Cause:** Task Information unavailable for rule creation

**Action:** Update the payload with task information and upgrade the process manually.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**UPGCMP-01001: unexpected upgrade exception**

**Cause:** An unexpected error occurred while a component was being examined or upgraded.

**Action:** Check the log file for more details and contact Oracle Support Services, if needed.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-01101: exception while backing up file {0}**

**Cause:** Errors occurred backing up the specified configuration file during mod\_plsql upgrade.

**Action:** See the secondary error message for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade



---

**UPGCMP-01102: exception while upgrading mod\_plsql**

**Cause:** Errors occurred while upgrading one of the mod\_plsql configuration files.

**Action:** See the secondary error message for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01103: exception while replacing source Oracle home references in: {0}**

**Cause:** Errors occurred while replacing the Oracle home references in the specified configuration file.

**Action:** See the secondary error message for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01104: exception while copying file {0} to {1}**

**Cause:** Errors occurred copying the specified configuration file.

**Action:** See the secondary error message for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01105: File {0} does not exist in the target instance.**

**Cause:** The specified configuration file for the destination instance was not found.

**Action:** See the secondary error message for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01106: failure to remove obsolete configuration properties from {0}**

**Cause:** Errors occurred removing obsolete properties from the specified configuration file.

**Action:** See the secondary error message for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01201: exception during the upgrade of Oracle Portal**

**Cause:** Oracle Portal upgrade failed while upgrading one of the Oracle Portal configuration files.

**Action:** See the secondary error message for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

---

**UPGCMP-01202: File {0} does not exist in the destination Oracle instance.**

**Cause:** The specified Oracle Portal configuration file was not found in the destination Oracle instance.

**Action:** See the secondary error message in the OFM Upgrade Assistant log file for the cause of the failure. Ensure that the configuration file is present in the destination Oracle instance.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01203: Oracle Portal upgrade completed with errors.**

**Cause:** Errors were encountered during the Oracle Portal component upgrade.

**Action:** Check the OFM Upgrade Assistant log file for details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01204: The default location {0} of the log directory has changed in file {1} of the source Oracle home.**

**Cause:** The default location of log directory has changed in the given file in the source Oracle home.

**Action:** Check the value of log directory in the destination instance for the given file. Change it to point to the correct location if required.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**UPGCMP-01231: unable to copy file: {0}**

**Cause:** The Oracle JPDK upgrade failed to copy the specified configuration file.

**Action:** See the secondary error message in the OFM Upgrade Assistant log file for the cause of the failure.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01232: unable to create the directory: {0}**

**Cause:** The Oracle JPDK upgrade failed to create the specified directory.

**Action:** See the secondary error message in the OFM Upgrade Assistant log file for the cause of the failure.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01233: unable to upgrade the <preferenceStore> tag from providers.xml file: {0}**

---

**Cause:** The Oracle JPDK upgrade failed to migrate some of the provider configurations from the specified configuration file.

**Action:** See the secondary error message in the OFM Upgrade Assistant log file for the cause of the failure. Rerun the middle-tier upgrade after fixing the cause or migrate the configuration manually from the source Oracle home to the destination instance home.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01234: unable to upgrade Provider Group changes from source to destination iasProviders.xml file: {0}**

**Cause:** The Oracle JPDK upgrade failed to migrate the Provide Group changes from the specified configuration file.

**Action:** See the secondary error message in the OFM Upgrade Assistant log file for the cause of the failure. Rerun the middle-tier upgrade after fixing the cause or migrate the configuration manually from the source Oracle home to the destination instance home.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01235: unable to upgrade JNDI entries from source to destination orion-web.xml file: {0}**

**Cause:** The Oracle JPDK upgrade failed to migrate the JNDI entries from the specified configuration file.

**Action:** See the secondary error message in the OFM Upgrade Assistant log file for the cause of the failure. Rerun the middle-tier upgrade after fixing the cause or migrate the configuration manually from the source Oracle home to the destination instance home.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01236: unable to upgrade the Provider UI Security Settings Registry file: {0}**

**Cause:** The Oracle JPDK upgrade failed to migrate the specified Provider UI Security registry file.

**Action:** See the secondary error message in the OFM Upgrade Assistant log file for the cause of the failure. Rerun the middle-tier upgrade after fixing the cause or migrate the configuration manually from the source Oracle home to the destination instance home.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01237: Arguments passed for Oracle JPDK upgrade are illegal.**

**Cause:** The arguments passed to the Oracle JPDK upgrade were incorrect.

---

**Action:** See the secondary error message in the OFM Upgrade Assistant log file for the cause of the failure and rerun the middle-tier upgrade after fixing the cause of the error.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01238: No Namespace URI is present for the file {0}.**

**Cause:** The Namespace URI is missing in the specified configuration file.

**Action:** See the secondary error message in the OFM Upgrade Assistant log file for the cause of the failure and rerun the middle-tier upgrade after fixing the cause of the error.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01239: unable to create cache.xml at {0}**

**Cause:** The Oracle JPKD upgrade failed to create the cache.xml file at the specified location in the destination instance home.

**Action:** See the secondary error message in the OFM Upgrade Assistant log file for the cause of the failure and rerun the middle-tier upgrade after fixing the cause of the error.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01240: failure creating invalidation entries for cache.xml**

**Cause:** The Oracle JPKD upgrade failed to create the invalidation entries in the specified configuration file.

**Action:** See the secondary error message in the OFM Upgrade Assistant log file for the cause of the failure and rerun the middle-tier upgrade after fixing the cause of the error.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01241: failure while trying to obfuscate an authorization attribute in {0}**

**Cause:** The Oracle JPKD upgrade failed to obfuscate the authorization attributes in the specified configuration file.

**Action:** See the secondary error message in the OFM Upgrade Assistant log file for the cause of the failure and rerun the middle-tier upgrade after fixing the cause of the error.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01242: exception during Oracle JPKD upgrade**

---

**Cause:** The Oracle JSDK upgrade failed while upgrading one of the configuration files.

**Action:** See the secondary error message in the OFM Upgrade Assistant log file for the cause of the failure.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01271: OmniPortlet is unable to upgrade proxy settings.**

**Cause:** The OmniPortlet upgrade failed to upgrade proxy settings.

**Action:** Check the write permissions of provider.xml in the destination instance. Check the OFM Upgrade Assistant log file for other possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01272: OmniPortlet is unable to upgrade customizations.**

**Cause:** The OmniPortlet upgrade failed to copy the portlet customizations from the source Oracle home to the destination instance.

**Action:** Check the write permissions of the customization directory in the destination instance. Check the OFM Upgrade Assistant log file for other possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01273: OmniPortlet is unable to upgrade Locale Personalization Level.**

**Cause:** The OmniPortlet upgrade failed to copy the Locale Personalization Level from the source Oracle home to the destination instance.

**Action:** Check the write permissions of provider.xml in the destination instance. Check the OFM Upgrade Assistant log file for other possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01275: OmniPortlet is unable to upgrade the encodeHtmlField setting.**

**Cause:** The OmniPortlet upgrade failed to copy the encodeHtmlField setting from the source Oracle home to the destination instance.

**Action:** Check the write permissions of provider.xml in the destination instance. Check the OFM Upgrade Assistant log file for other possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01276: OmniPortlet is unable to upgrade the exportConnectionInfo setting.**

---

**Cause:** The OmniPortlet upgrade failed to copy the exportConnectionInfo setting from the source Oracle home to the destination instance.

**Action:** Check the write permissions of provider.xml in the destination instance. Check the OFM Upgrade Assistant log file for other possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01277: OmniPortlet is unable to upgrade Security Repository settings.**

**Cause:** The OmniPortlet upgrade failed to copy the Security Repository settings from the source Oracle home to the destination instance.

**Action:** Check the write permissions of provider.xml in the destination instance. Check the OFM Upgrade Assistant log file for other possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01278: OmniPortlet is unable to upgrade Preference Store settings.**

**Cause:** The OmniPortlet upgrade failed to copy the Preference Store settings from the source Oracle home to the destination instance.

**Action:** Check the write permissions of provider.xml in the destination instance. Check the OFM Upgrade Assistant log file for other possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01279: Web Clipping is unable to upgrade Trusted Certificate Location.**

**Cause:** The Web Clipping upgrade failed to copy the Trusted Certificate Location from the source Oracle home to the destination instance.

**Action:** Check the write permissions of provider.xml in the destination instance. Check the OFM Upgrade Assistant log file for other possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01280: Web Clipping is unable to upgrade Proxy settings.**

**Cause:** The Web Clipping upgrade failed to copy the Proxy settings from the source Oracle home to the destination instance.

**Action:** Check the write permissions of provider.xml in the destination instance. Check the OFM Upgrade Assistant log file for other possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01281: Web Clipping is unable to upgrade translated URL-service providers.**

---

**Cause:** The Web Clipping upgrade failed to copy the URL-service provider definition files from the source Oracle home to the destination instance.

**Action:** Check the OFM Upgrade Assistant log file for details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01282: Web Clipping is unable to upgrade Oracle Web Cache settings.**

**Cause:** The Web Clipping upgrade failed to copy the Oracle Web Cache settings from the source Oracle home to the destination instance.

**Action:** Check the write permissions of \$ORACLE\_HOME/portal/conf/cache.xml in the destination instance. Check the OFM Upgrade Assistant log file for other possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01284: Web Clipping is unable to upgrade Security Repository settings.**

**Cause:** The Web Clipping upgrade failed to copy the Security Repository settings from the source Oracle home to the destination instance.

**Action:** Check the write permissions of provider.xml in the destination instance. Check the OFM Upgrade Assistant log file for other possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01285: Web Clipping is unable to upgrade the database repository schema.**

**Cause:** The Web Clipping upgrade failed to upgrade the database repository schema to the new version.

**Action:** Ensure that the given database repository URL is correct. Check the OFM Upgrade Assistant log file for other possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01286: OmniPortlet is unable to upgrade the useThinGraph setting.**

**Cause:** The OmniPortlet upgrade failed to copy the useThinGraph setting from the source Oracle home to the destination instance.

**Action:** Check the write permissions of provider.xml in the destination instance. Check the OFM Upgrade Assistant log file for other possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01287: exception during Oracle Portal tools upgrade**

---

**Cause:** Errors were encountered while running the Oracle Portal tools upgrade.

**Action:** Check the OFM Upgrade Assistant log file for details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01288: failure to import init-param {0} from source {1}**

**Cause:** Errors occurred importing initialization parameters from the specified configuration file.

**Action:** See the secondary error message for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01301: error parsing file {0}**

**Cause:** An error occurred parsing the specified file.

**Action:** See the secondary error message for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01302: error updating file {0}**

**Cause:** An error occurred updating the specified file.

**Action:** See the secondary error message for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01501: invalid Oracle Internet Directory version for upgrade**

**Cause:** Oracle Internet Directory is not at version 11.1 or later.

**Action:** Upgrade Oracle Internet Directory before upgrading Oracle Directory Integration Platform.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01503: unable to connect to the Oracle Internet Directory server**

**Cause:** DIP upgrade needs to communicate with the Oracle Internet Directory server. See detailed preceding message in log for why that was not possible.

**Action:** Ensure that the Oracle Internet Directory server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade



---

**UPGCMP-01504: A Oracle Directory Integration Platform upgrade parameter is missing.**

**Cause:** A required parameter was not available for Oracle Directory Integration Platform upgrade. This is an internal failure of the OFM Upgrade Assistant.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-01505: Oracle Directory Integration Platform upgrade failed in the examine phase.**

**Cause:** The upgrade of Oracle Directory Integration Platform failed while checking for a valid starting configuration.

**Action:** See the secondary messages for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01506: unexpected error**

**Cause:** An unexpected error occurred while upgrading Oracle Directory Integration Platform.

**Action:** See the secondary messages for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01507: unexpected error**

**Cause:** An unexpected error occurred.

**Action:** See secondary message for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01508: error during Oracle Directory Integration Platform schema upgrade**

**Cause:** The schema files for the Oracle Directory Integration Platform component might be invalid or corrupt.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-01509: error during subscriber upgrade**

**Cause:** Upgrading subscriber schema with invalid file or invalid file content.

**Action:** The subscriber schema files are not valid. Contact Oracle Support Services.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-01510: error during LDAP operation**

**Cause:** An error occurred while performing an LDAP operation on the Oracle Internet Directory server. See secondary message for more details.

**Action:** Check that Oracle Internet Directory server is fully operational.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01511: error reading Oracle Directory Integration Platform profile information from file system**

**Cause:** A template profile could not be read from the OH/ldap/odi/conf directory.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-01512: error creating profile**

**Cause:** There was an unexpected error while creating an Oracle Directory Integration Platform profile.

**Action:** See secondary message for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01513: invalid parameter for profile creation**

**Cause:** An incorrect parameter was used for template profile creation.

**Action:** See secondary message for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01514: error connecting to database**

**Cause:** Oracle Directory Integration Platform upgrade was unable to connect to the database.

**Action:** Ensure that the database connect string, user name, and password are correct, and the database and listener are running.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

---

**UPGCMP-01515: error reading Oracle Directory Integration Platform configuration information from the database**

**Cause:** Incorrect SQL was detected while reading Oracle Directory Integration Platform information. This is a coding error within Upgrade.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-01516: error during rootcontext upgrade**

**Cause:** The Oracle Directory Integration Platform schema file had invalid file content.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-01517: error importing SSL wallet**

**Cause:** Oracle Directory Integration Platform upgrade was unable to import the SSL wallet from the source Oracle home to the Oracle Directory Integration Platform application node.

**Action:** See secondary message for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01518: failure to connect to the Oracle Internet Directory server**

**Cause:** The upgrade was unable to connect to an Oracle Internet Directory server, as required.

**Action:** Ensure that the Oracle Internet Directory server is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01519: error creating CSF key**

**Cause:** KEY creation for Oracle Directory Integration Platform encountered some error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-01520: error creating data source.**

**Cause:** Failure in data source creation for Oracle Directory Integration Platform.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-01702: Unexpected exception occurred during Oracle Web Cache upgrade.**

**Cause:** An unexpected exception occurred.

**Action:** Check the log file for the cause of this problem.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01703: The source Oracle Web Cache version {0} is not supported for upgrade.**

**Cause:** The source Oracle Web Cache version is not supported for upgrade.

**Action:** Upgrade the source Oracle Web Cache to a supported version first.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01704: Upgrade exception occurred during Oracle Web Cache upgrade on {0}.**

**Cause:** An exception occurred when upgrading Oracle Web Cache configuration files.

**Action:** Check the log file for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01706: The destination Oracle Web Cache version {0} is not supported by this Upgrade Assistant.**

**Cause:** The destination Oracle Web Cache version is not supported for upgrade.

**Action:** Run the Upgrade Assistant for the destination version.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01721: The local CACHE element cannot be found in the source configuration file.**

**Cause:** The configuration file of the source Oracle Web Cache does not contain the CACHE element for the source Web Cache component.

**Action:** Check the configuration file of the source Oracle Web Cache.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

---

**UPGCMP-01722: The local CACHE element cannot be found in the destination configuration file.**

**Cause:** The pre-upgrade configuration file of the destination Oracle Web Cache does not contain a valid CACHE element for the destination Oracle Web Cache.

**Action:** Check the destination Oracle Web Cache configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01723: Cannot create URL for {0}.**

**Cause:** Exception occurred when creating configuration file URL object. The file name string is malformed and cannot be parsed.

**Action:** Check configuration files, and contact Oracle Support Services if needed.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01724: The source configuration file webcache.xml does not exist or is invalid.**

**Cause:** The source configuration file webcache.xml does not exist or is invalid.

**Action:** Ensure that the source configuration file is valid and Oracle Web Cache 10g can start before running Upgrade Assistant.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01730: Backing up configuration file failed.**

**Cause:** Exception occurred when backing up destination configuration file.

**Action:** Check destination environment for the cause of this problem.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01731: Cannot read port properties from OPMN or OHS property file.**

**Cause:** The OPMN or OHS port properties file doesn't exist or is invalid.

**Action:** Check the log file for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01732: Cannot obtain a free port number for the listening port.**

**Cause:** Cannot obtain a free TCP port number for port number conversion.

**Action:** Manually modify the port number in Oracle WebCache configuration file after upgrade.

**Level:** 1

---

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01733: Testing TCP port {0} failed: {1}**

**Cause:** Exception occurred when testing the port number.

**Action:** Check the log file for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01735: The destination administration port number {0} conflicts with one source listening port. Importing destination administration port failed.**

**Cause:** The destination administration port number conflicts with one source non-admin listening port.

**Action:** Manually change the administration port number after upgrade.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01736: The specified CRL path is not a directory. Migrating CRL files in {0} stopped.**

**Cause:** The CRL path specified in CRLPATH is not a directory.

**Action:** Check the CRL configuration in source configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01801: Folder {0} doesn't exist.**

**Cause:** Standalone agent component is not installed

**Action:** Install standalone agent component.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-01901: failure creating Oracle Reports specific upgrade items**

**Cause:** The Oracle Reports upgrade failed to create Oracle Reports specific upgrade items.

**Action:** Check the log file for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01903: unable to create Oracle Reports server component {0}**

**Cause:** The creation of the specified Oracle Reports server component failed.

**Action:** Check the log file for more details.

---

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01904: unable to create Oracle Reports bridge component {0}**

**Cause:** The creation of the Oracle Reports bridge component failed.

**Action:** Check the log file for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01905: failure during upgrade of file {0}**

**Cause:** The Oracle Reports upgrade failed to upgrade the specified configuration file.

**Action:** Check the log file for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01906: unable to upgrade dependent components file {0}**

**Cause:** The Oracle Reports upgrade failed to upgrade a dependent component file.

**Action:** Check the log file for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01907: unable to upgrade Oracle Reports element**

**Cause:** The Oracle Reports upgrade failed to upgrade an Oracle Reports element.

**Action:** Check the log file for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01908: exception getting FRCOMMON node; FRCOMMON node managed files will not be upgraded**

**Cause:** An exception has occurred getting the FRCOMMON node.

**Action:** Check the log file for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01909: exception parsing file {0}**

**Cause:** An exception has occurred parsing a configuration file.

**Action:** Check the log file for more details.

---

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-01910: exception upgrading registry entries**

**Cause:** The Oracle Reports upgrade failed to upgrade registry entries.

**Action:** Check the log file for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02001: unable to complete examination phase for Oracle Single Sign-On midtier upgrade for the given source Oracle home**

**Cause:** The source Oracle home did not have a supported product version. Supported source product version numbers start with either 10.1.2 or 10.1.4

**Action:** Verify that the source Oracle home slated for upgrade has a supported version number.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02002: unable to complete the examination phase for Oracle Single Sign-On midtier upgrade to Oracle Access Manager for the given destination Oracle home**

**Cause:** The destination Oracle home was not at a supported version. Supported product version numbers start with 11.1.

**Action:** Select a destination Oracle home that is of a supported version for upgrade.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02003: The source Oracle home policy.properties configuration file does not exist.**

**Cause:** Either the source Oracle home is corrupted or a valid path was not provided.

**Action:** Restore a valid source Oracle home from backup or provide a valid path.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02004: The source Oracle home policy.properties configuration file is not readable.**

**Cause:** The source Oracle home is corrupted.

**Action:** Restore a valid source Oracle home from backup.

**Level:** 1



---

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02005: unable to get the Oracle Access Manager logger**

**Cause:** The Oracle Single Sign-On upgrade to Oracle Access Manager could not find an internal resource.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-02006: unable to complete Oracle Single Sign-On upgrade examination phase**

**Cause:** Received an unexpected error while attempting to access the policy.properties configuration file in the source Oracle home.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-02007: Could not connect to the Admin Domain MBean Server**

**Cause:** The connection settings are incorrect or Admin Server is down

**Action:** Ensure that the Admin Domain MBean server is up and that the connection information is correct

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02009: Source Oracle Single Sign-On Schema is Invalid**

**Cause:** The MBean look-up failed.

**Action:** Ensure that the Admin Domain MBean server is up and OAM Upgrade Mbean is registered.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02010: Error in osso.conf obfuscation**

**Cause:** osso.conf is not generated properly.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02101: source file {0} is not found**

**Cause:** The specified Discoverer configuration file was not found.

**Action:** Ensure that the source Oracle home is correctly configured.

---

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02102: destination file {0} is not found**

**Cause:** The specified Discoverer configuration file was not found.

**Action:** Ensure that the destination Oracle instance is correctly configured.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02103: Discoverer upgrade does not support upgrade from version {0}.**

**Cause:** Discoverer upgrade does not support upgrade from the specified version.

**Action:** Ensure that the version of the source Discoverer installation is certified to work with the OFM Upgrade Assistant.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02104: Discoverer upgrade does not support upgrade to version {0}.**

**Cause:** Discoverer upgrade does not support upgrade to the specified version.

**Action:** Ensure that the version of the destination Discoverer installation is certified to work with the OFM Upgrade Assistant.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02105: Discoverer configuration file {0} does not exist.**

**Cause:** The specified configuration file did not exist.

**Action:** Ensure that the destination Discoverer instance is correctly configured.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02107: Discoverer configuration file {0} appears to be corrupted.**

**Cause:** Specified configuration file was corrupted.

**Action:** Ensure that the destination Discoverer instance is correctly configured.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02108: Source Oracle home specified is invalid.**

**Cause:** Specified Oracle home was invalid.

**Action:** Ensure that the source Oracle home is specified correctly.

---

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02109: Destination Discoverer installation is remote.**

**Cause:** Specified destination Discoverer installation (Oracle home) was on a remote host.

**Action:** Ensure that both source and destination Discoverer installations are on the same host.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02201: Oracle Forms Services upgrade does not support upgrade from version {0}.**

**Cause:** Oracle Forms Services upgrade does not support upgrade from the specified version.

**Action:** Ensure that the version of the source Oracle Forms Services installation is certified to work with the OFM Upgrade Assistant.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02202: Oracle Forms Services upgrade does not support upgrade to version {0}.**

**Cause:** Oracle Forms Services upgrade does not support upgrade to the specified version.

**Action:** Ensure that the version of the destination Oracle Forms Services installation is certified to work with the OFM Upgrade Assistant.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02203: invalid section name in the configuration file {0}**

**Cause:** An invalid section name was found in the configuration file.

**Action:** Correct the application section syntax in the specified configuration file and run the upgrade again.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02205: invalid or missing Oracle Forms Services configuration file {0}**

**Cause:** The specified Oracle Forms Services configuration file was either invalid or missing.

**Action:** Fix the parent configuration file and run the upgrade again.

**Level:** 1

---

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02206: Oracle Forms Services is not configured in the source Oracle home {0}.**

**Cause:** Oracle Forms Services was not configured in the source Oracle home so no upgrade of Oracle Forms Services occurred.

**Action:** No upgrade required for the Oracle Forms Services component.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02208: The source File {0}, does not contain any additional user configuration, it will not be upgraded.**

**Cause:** The specified Oracle Forms Services source file did not contain any additional user configuration. No Oracle Forms Services upgrade is needed.

**Action:** No Action required.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02210: error reading file {0}**

**Cause:** The specified file is either missing or there was a permission error reading the file.

**Action:** Ensure that the file exists and the file permissions are correct. Run the upgrade again.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02211: error writing the User entries to file {0}**

**Cause:** An error occurred writing the User entries to the specified file.

**Action:** Rerun upgrade again.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02213: Configuration file error while parsing {0}.**

**Cause:** An error occurred while parsing the specified configuration file.

**Action:** Fix the syntax errors in the configuration file and run the upgrade again.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02214: Permissions problem writing the file, {0}.**

---

**Cause:** A permissions error occurred while writing the specified configuration file.

**Action:** Fix the file permissions and run the upgrade again.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02215: error reading the Oracle Forms Services configuration file {0} from the source Oracle home**

**Cause:** An unexpected error occurred while reading Oracle Forms Services configuration file {0} from the source Oracle home.

**Action:** See secondary message for details to resolve the error.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02218: failure to upgrade Oracle Forms Services configuration file {0}**

**Cause:** An unexpected error occurred during upgrade of the specified Oracle Forms Services configuration file.

**Action:** See secondary message for details to resolve the error.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02301: unable to parse httpd.conf**

**Cause:** A possible syntax error was encountered in the httpd.conf file.

**Action:** Inspect httpd.conf for possible syntax errors.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02310: unable to parse the default DMS configuration {0}**

**Cause:** A possible syntax error was encountered in the default DMS configuration file.

**Action:** Inspect the default DMS configuration file for possible syntax errors.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02351: OHS upgrade failure while upgrading {0}**

**Cause:** An unexpected exception occurred while upgrading the specified OHS configuration file.

**Action:** Check the OFM Upgrade Assistant log file for more details regarding the cause of this problem.

**Level:** 1

---

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02352: unable to parse {0}**

**Cause:** A possible syntax error was encountered in the specified configuration file.

**Action:** Inspect the specified configuration file for possible syntax errors.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02353: unable to retrieve the reference httpd.conf file from 11g instance.**

**Cause:** The download of the httpd.conf file from 11g instance failed.

**Action:** Ensure that httpd.conf exists in the 11g OHS instance.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02354: unable to upload the upgraded OHS configuration files to the destination 11g instance**

**Cause:** The upload of upgraded OHS configuration files to destination 11g instance failed.

**Action:** Make sure instance is in place.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02355: The wallet already exists; SSL wallet {0} is not imported.**

**Cause:** The SSL wallet already exists, most likely from a previous upgrade run.

**Action:** This is not an error. No action is required.

**Level:** 1

**Type:** WARNING

**Impact:** Upgrade

**UPGCMP-02356: unable to import the SSL wallet {0}**

**Cause:** An internal error has occurred.

**Action:** Import the SSL wallet manually after upgrade or contact Oracle Support Services for help.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-02357: unable to import the SSL wallet {0}**

**Cause:** An error occurred importing the specified SSL wallet.

**Action:** Ensure that the wallet is a valid 10g wallet, and run the upgrade again.

---

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02358: unable to configure the SSL end point for {0}**

**Cause:** An internal error has occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-02359: failure while upgrading an SSLWallet directive.**

**Cause:** An internal error has occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-02360: unable to write out the upgraded config file {0}.**

**Cause:** An error was encountered while attempting to write to a file.

**Action:** Ensure that the file exists and is writable.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02361: file I/O error while parsing {0}**

**Cause:** The file was either missing or not readable.

**Action:** Ensure that the file exists and is readable.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02401: Could not connect to the Admin Edit MBean Server**

**Cause:** The connection settings are incorrect or server is down

**Action:** Ensure that the Admin Edit MBean server is up and that the connection information is correct

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02402: Could not connect to the Admin Domain MBean Server**

**Cause:** The connection settings are incorrect or server is down

**Action:** Ensure that the Admin Domain MBean server is up and that the connection information is correct

---

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02403: The {0} parameter is missing**

**Cause:** A parameter required by the OIF Upgrade Plugin is missing

**Action:** Ensure that the required parameter is set

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02404: Some required parameters are missing**

**Cause:** One or several parameters required by the OIF Upgrade Plugin are missing

**Action:** Ensure that all the required parameters are set

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02405: Missing file or directory from OIF 10g install: {0}**

**Cause:** A directory or file from the OIF 10g deployment is missing or not readable

**Action:** Ensure that the directory or file exists and is readable

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02406: Missing file or directory from OIF 11g install: {0}**

**Cause:** A directory or file from the OIF 11g deployment is missing or not writable

**Action:** Ensure that the directory or file exists and is writable

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02407: An error occurred during the execution of the {0} OIF Upgrade Item**

**Cause:** An Upgrade Item from the OIF Upgrade plugin failed

**Action:** Check the logs and fix the error that caused the failure

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02408: Unexpected error occurred during the OIF Upgrade Plugin execution**

**Cause:** An error occurred during OIF Upgrade plugin execution

**Action:** Check the logs for more information



---

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02501: OVD upgrade failed.**

**Cause:** An error occurred during OVD Upgrade process.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02502: OVD Registration Error.**

**Cause:** An error occurred while registering OVD.

**Action:** Ensure that the Weblogic Server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02503: Error deleting the \$OI/OVD/tmp.dat file.**

**Cause:** Could not delete the \$OI/OVD/tmp.dat file

**Action:** Manually delete the \$OI/OVD/tmp.dat file.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02504: OVD MBean not found.**

**Cause:** Was not able to find the OVD Mbean.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02505: Error migrating 10g server.os\_xml to 11g.**

**Cause:** Unable to migrate server.os\_xml configuration file.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02506: Error migrating 10g listeners.os\_xml to 11g.**

**Cause:** Unable to migrate listeners.os\_xml configuration file.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Upgrade

**UPGCMP-02507: Error migrating 10g adapters.os\_xml to 11g.**

**Cause:** Unable to migrate adapters.os\_xml configuration file.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02508: OVD Upgrade Exception.**

**Cause:** An I/O error occurred while upgrading listeners.os\_xml.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02509: XML Configuration error**

**Cause:** An error occurred while upgrading configuration files.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02601: Unable to load OAAM property file {0} from the WebApp at {1}**

**Cause:** An error occurred while loading OAAM upgrade related properties.

**Action:** Check make sure 10G WebApp is valid and its path is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02602: Unable to get connection to OAAM database**

**Cause:** An error occurred while getting connection to OAAM database.

**Action:** Check the log file and then verify the database properties.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02604: Error occurred while generating sequence value**

**Cause:** An error occurred while generating sequence.

**Action:** Check the OAAM database and make sure all the sequences exist.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

---

**UPGCMP-02605: OAAM CSF Credential already exists for the mapName [{0}] and keyName [{1}]**

**Cause:** OAAM CSF Keys already exist. So not migrating the secret keys from 10G Keystore.

**Action:** Please delete the CSF Credential using Enterprise Manager and re-run the Middle Tier upgrade.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02606: Could not migrate secret key with alias [{0}] from keystore [{1}] to CSF**

**Cause:** An error occurred while trying to migrate secret key from keystore to CSF.

**Action:** Check the upgrade logs, fix the issue and re-run Middle Tier upgrade.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02607: Could not find the CSF MBean with the name [{0}]**

**Cause:** An error occurred while trying to lookup CSF MBean.

**Action:** Make sure OAAM domain is properly configured and CSF MBeans are properly deployed. Fix those issues and re-run Middle Tier upgrade.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02608: Could not open keystore [{0}]**

**Cause:** Could not open keystore.

**Action:** Make sure the keystore password is valid. Fix those issues and re-run Middle Tier upgrade.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02609: Could not find key alias [{0}] in keystore [{1}]**

**Cause:** Could not find key alias in keystore.

**Action:** Make sure OAAM 10G keystore is properly configured. Fix those issues and re-run Middle Tier upgrade.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02610: Could not find retrieve key with alias [{0}] from keystore [{1}]**

**Cause:** Could not retrieve key from keystore.

**Action:** Make sure the keyalias password is valid. Fix those issues and re-run Middle Tier upgrade.

---

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02611: OAAM table VCRYPT\_DB\_PATCHES does not exist for the specified OAAM schema user name.**

**Cause:** The OAAM table VCRYPT\_DB\_PATCHES could not be found using the entered credentials.

**Action:** Make sure you have entered credentials for a valid OAAM database.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02701: WLS/LDAP reports problems**

**Cause:** Error occurred while moving users and groups from the RPD to the identity store.

**Action:** Users and groups may not be migrated.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02703: Could not decrypt password for {0}**

**Cause:** Error occurred while decrypting a password.

**Action:** The password will not be upgraded and will need to be entered in EM.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02704: Application role {0} does not exist**

**Cause:** Error occurred while importing RPD groups.

**Action:** Enterprise group membership and application roles will need to be confirmed in EM.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02705: Repository file not found in : {0}**

**Cause:** Error occurred while copying RPD.

**Action:** The RPD file must be moved to the expected location.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02706: Unable to create the directory {0}**

**Cause:** Error occurred creating a directory.

---

**Action:** Investigate the permissions on the file system.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02707: Expected a single subdirectory under {0}**

**Cause:** Error occurred calculating a file path.

**Action:** Confirm a single instance is installed.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02708: Could not configure logging (Error creating {0})**

**Cause:** OBIPS could not be configured to log upgrade messages.

**Action:** The WLS configuration should be examined.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02709: Cannot upgrade an RPD which is in the TEMP directory ({0})**

**Cause:** The source RPD was in the temporary directory.

**Action:** Move the source RPD to another location.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02711: Error mapping application role {0} to enterprise group {1}**

**Cause:** Error occurred while importing RPD groups.

**Action:** The application role will have to be manually assigned to the enterprise group in EM.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02712: Expected {0} Oracle instance, found {1}**

**Cause:** Upgrade Assistant can only import to an 11g installation with a single Oracle instance.

**Action:** Check that a single instance is installed.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02713: Errors were reported during the catalog upgrade. Please refer to the log file for details.**

**Cause:** Error occurred upgrading the catalog.

---

**Action:** Please refer to the log file for details of the errors

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02714: Error creating the app role {0}**

**Cause:** See secondary error message for root cause.

**Action:** Check the permissions, or copy the item locally.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02716: Could not rename directory {0} to {1}**

**Cause:** Could not rename the directory.

**Action:** Check the file permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02717: Cannot copy {0} to a subdirectory of itself ({1})**

**Cause:** Cannot copy a directory to a subdirectory of itself.

**Action:** Select a source directory which is not in the 11g instance.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02718: The catalog upgrade did NOT complete successfully. Please refer to earlier in this upgrade log file or the OBIPS log files found under {0} for more information.**

**Cause:** OBIPS encountered a fatal error during upgrade of the catalog.

**Action:** Please refer to the upgrade log file and to OBIPS log files for details of the errors.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02719: Error granting {0} permission to app role {1}**

**Cause:** See secondary error message for root cause.

**Action:** The permission may need to be granted manually.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02720: RPD migration utility encountered the following fatal error: {0}**

**Cause:** RPD migration utility failed to complete successfully.

---

**Action:** Please review the above error messages and take appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02801: Directory {0} does not exist.**

**Cause:** Non existent directory mentioned.

**Action:** Please mention a location that is a existing directory.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02808: No valid report file found for upgrade in the source directory**

**Cause:** No valid report file found for upgrade

**Action:** Please make sure there are valid report files in the source directory.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-02901: unable to connect to the SOA server at {0}:{1}**

**Cause:** SOA Connection Details are not correct or the SOA server is down.

**Action:** Check the SOA connection details, start the SOA server if it is down.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-05001: The 10g table {0}.{1} doesn't use the default columns. It cannot be upgraded**

**Cause:** The 10g table metadata must not have been changed.

**Action:** Select a 10g table with the default columns for upgrade.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-05002: The schema {0} doesn't exist.**

**Cause:** The upgrade assistant couldn't find the schema.

**Action:** Select a table which contains the schema.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-05003: The table {0} doesn't exist.**

**Cause:** The upgrade assistant couldn't find the table.

**Action:** Check the upgrade assistant has access to the table.

---

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-05101: Audit Server database schema has already been updated.**

**Cause:** Specified Audit Server database schema has already been updated.

**Action:** No user action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Upgrade

**UPGCMP-05102: Audit Server database schema successfully updated.**

**Cause:** Specified Audit Server database schema was successfully updated.

**Action:** No user action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Upgrade

**UPGCMP-05103: The Audit schema updated is INVALID.**

**Cause:** Specified Audit Server database schema was updated but is invalid.

**Action:** Restore the Audit Server database from a backup and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-05105: Audit Server database schema update failed.**

**Cause:** Specified Audit Server database schema update failed.

**Action:** Check the log file and if necessary restore the database from backup.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-05106: Updating Audit Server database objects to PS2.**

**Cause:** The Audit Server database schema update script is now running.

**Action:** This is an informational message. No user action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Upgrade

**UPGCMP-05107: A SQL statement failed in Audit Server database schema update.**

**Cause:** A SQL error took place, likely because there are data in the OAAM table. Please note that although created in AS 11gR1 PS1 release, the OAAM table in audit schema is supposed to start being used since AS 11gR1 PS2 release. It is supposed to be empty now.



---

**Action:** Please move the existing data out of the OAAM table, for the schema to be upgraded. It is important to ensure that the table definition is consistent with the event definitions in component\_events.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Upgrade

**UPGCMP-05201: Seed data has already been loaded.**

**Cause:** Seed data for specified database schema has already been loaded.

**Action:** No user action is required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Upgrade

**UPGCMP-05202: Failure during the SDF run: {0}.**

**Cause:** An error occurred during seed data loading stage.

**Action:** Contact Oracle Support Services with the log file details.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade

**UPGCMP-05203: Error contacting database: {0}.**

**Cause:** An error occurred when trying to contact/connect to Oracle Database.

**Action:** 1. Check that Database is running. 2. Check the preceding messages in this log for any errors. 3. Contact Oracle Support Services if the above steps do not help resolve the problem.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Upgrade



---

## WCS-03051 to WCS-51006

**WCS-03051: No event is selected.**

**Cause:** There was invalid or missing information in the connection.xml or adf-config.xml file.

**Action:** Verify that the connections.xml and adf-config.xml file contains a valid entry with the correct connection information.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-03052: event date validation error**

**Cause:** An invalid date or time was selected for the event.

**Action:** Verify the date and time.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03053: No upcoming events were found.**

**Cause:** Either the connections.xml file did not contain a valid connection entry for the Group Space Events service, or the adapter was not defined.

**Action:** Verify that the connections.xml file contains a valid connection for the Group Space Events service, and the Group Space Events server is running

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-03101: The Events service is not able to acquire an adapter from the server.**

**Cause:** Either the connections.xml file did not contain a valid connection entry for the Personal Events service, or the adapter was not defined.

**Action:** Verify that the connections.xml file contains a valid connection entry for the Personal Events service, and the specified adapter is defined.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WCS-03102: The Events service is unavailable.**

**Cause:** The connections.xml file either did not contain a valid connection entry for the Personal Events service, or it was missing the entry for Personal Events with the state attribute set to default.

**Action:** Verify that the connections.xml file contains a valid connection entry for the Personal Events service, and the Personal Events server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03103: Data query in Personal Events service failed**

**Cause:** Either the connections.xml file did not contain a valid connection entry for the Personal Events service, or the Personal Events server was down.

**Action:** Verify that the connections.xml file contains a valid connection entry for the Personal Events service, and the Personal Events server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03104: Create event in Personal Events service failed**

**Cause:** Either the connections.xml file did not contain a valid connection entry for the Personal Events service, or the Personal Events server was down.

**Action:** Verify that the connections.xml file contains a valid connection entry for the Personal Events service, and the Personal Events server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03105: Update event in Personal Events service failed**

**Cause:** Either the connections.xml file did not contain a valid connection entry for the Personal Events service, or the Personal Events server was down.

**Action:** Verify that the connections.xml file contains a valid connection entry for the Personal Events service, and the Personal Events server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03106: Delete event in Personal Events service failed**

**Cause:** Either the connections.xml file did not contain a valid connection entry for the Personal Events service, or the Personal Events server was down.

**Action:** Verify that the connections.xml file contains a valid connection entry for the Personal Events service, and the Personal Events server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WCS-03107: failure to send event mail in Personal Events service**

**Cause:** Either the connections.xml file did not contain a valid connection for the Mail service, or the Mail server was down.

**Action:** Verify that the connections.xml file contains a valid connection for the Mail service, and that the Mail server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03108: failure to retrieve online meeting**

**Cause:** Either the connections.xml file did not contain a valid connection entry for the Conference service, or the Conference server was down.

**Action:** Verify that the connections.xml file contains a valid connection for the Conference service, and the Conference server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03109: failure to retrieve personal event list**

**Cause:** Either the connections.xml file did not contain a valid connection entry for the Personal Events service, or the Personal Events server was down.

**Action:** Verify that the connections.xml file contains a valid connection entry for the Personal Events service, and the Personal Events server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03110: failure to retrieve personal event detail**

**Cause:** Either the connections.xml file did not contain a valid connection entry for the Personal Events service, or the Personal Events server was down.

**Action:** Verify that the connections.xml file contains a valid connection entry for the Personal Events service, and the Personal Events server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03111: The Personal Events service credential is not configured properly.**

**Cause:** The Personal Events service credential was not configured properly.

**Action:** Verify that the Personal Events service credential is correct, and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03112: The Personal Events service is not properly configured.**

**Cause:** The Personal Events service was not properly configured in connections.xml.

---

**Action:** Verify that the connections.xml file contains a valid entry for the Personal Events service.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03113: The Personal Events server is not available.**

**Cause:** The Personal Events server was not available.

**Action:** Verify that the connections.xml file contains a valid entry for the Personal Events service, and the Personal Events server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03114: failure to send personal event**

**Cause:** Either the connections.xml file did not contain a valid connection for the Mail service, or the Mail server was down.

**Action:** Verify that the connections.xml file contains a valid connection for the Mail service, and the Mail server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03115: failure to log in to the Exchange server**

**Cause:** The credential for the Personal Events service was not configured properly or the Exchange server was not running.

**Action:** Verify that the credential for the Personal Events service is correct, and the Exchange server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03116: failure to log in to the Exchange server**

**Cause:** The credential for the Personal Events service credential was not configured properly.

**Action:** Verify that the credential for the Personal Events service is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03117: Failed to login to the exchange server.**

**Cause:** The credential for the Personal Events service is not configured properly or the exchange server is not running.

**Action:** Verify that the credential for the Personal Events service is correct, and the exchange server is running.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03118: Failed to login to the exchange server.**

**Cause:** The credential for the Personal Events service credential is not configured properly.

**Action:** Verify that the credential for the Personal Events service is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03201: The Events service is not able to acquire an adapter for an Events server.**

**Cause:** Either the connections.xml file did not contain a valid connection entry for the Group Space Events service.

**Action:** Verify that the connections.xml file contains a valid connection entry for the Group Space Events service.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03202: The Events service is unavailable.**

**Cause:** Either the connections.xml file did not contain a valid connection entry for the Group Space Events service, or the Group Space Events server was down.

**Action:** Verify that the connections.xml file contains a valid connection entry for the Group Space Events service, and the Group Space Events server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03203: Data query in Events service failed**

**Cause:** Either the connections.xml file did not contain a valid connection entry for the Group Space Events service, or the Group Space Events server was down.

**Action:** Verify that the connections.xml file contains a valid connection entry for the Group Space Events service, and the Group Space Events server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03204: Create event in Events service failed**

**Cause:** Either the connections.xml file did not contain a valid connection entry for the Group Space Events service, or the Group Space Events server was down.

**Action:** Verify that the connections.xml file contains a valid connection entry for the Group Space Events service, and the Group Space Events server is running.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WCS-03205: Update event in Events service failed**

**Cause:** Either the connections.xml file did not contain a valid connection entry for the Group Space Events service, or the Group Space Events server was down.

**Action:** Verify that the connections.xml file contains a valid connection entry for the Group Space Events service, and the Group Space Events server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03206: Delete event in Events service failed**

**Cause:** Either the connections.xml file did not contain a valid connection entry for the Group Space Events service, or the Group Space Events server was down.

**Action:** Verify that the connections.xml file contains a valid connection entry for the Group Space Events service, and the Group Space Events server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03207: Send event mail in Events service failed**

**Cause:** Either the connections.xml file did not contain a valid connection for the Mail service, or the Mail server was down.

**Action:** Verify that the connections.xml file contains a valid connection for the Mail service, and Mail server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03208: The changes to the event cannot be saved.**

**Cause:** The event was modified or deleted by another user after the event was retrieved.

**Action:** Refresh the Events task flow to view changes, and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03209: cannot create the category**

**Cause:** The category could not be created because a category of the same name already exists.

**Action:** Select the existing category.

**Level:** 1

**Type:** ERROR

**Impact:** Other



---

**WCS-03210: cannot add the group space event to the personal calendar**

**Cause:** Either the connections.xml file did not contain a valid connection entry for the Personal Events service, or the Personal Events server was down.

**Action:** Verify that the connections.xml file contains a valid connection entry for the Personal Events service, and the Personal Events server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03211: cannot add the group space event to the personal calendar**

**Cause:** The Personal Events service was not configured properly in connections.xml or the Personal Events service is down.

**Action:** Verify that the connections.xml file contains a valid connection entry for the Personal Events service, and the Personal Events server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03212: cannot add the group space event to the personal calendar**

**Cause:** The credential for the Personal Events service was not configured properly.

**Action:** Verify that the credential for the Personal Events service is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03213: failure to create category**

**Cause:** Either the connections.xml file did not contain a valid connection entry for the Group Space Events service, or the Group Space Events server was down.

**Action:** Verify that the connections.xml file contains a valid connection entry for the Group Space Events service, and the Group Space Events server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03214: failure to retrieve categories**

**Cause:** Either the connections.xml file did not contain a valid connection entry for the Group Space Events service, or the Group Space Events server was down.

**Action:** Verify that the connections.xml file contains a valid connection entry for the Group Space Events service, and the Group Space Events server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03215: failure to retrieve group space event list**

---

**Cause:** Either the connections.xml file did not contain a valid connection entry for the Group Space Events service, or the Group Space Events server was down.

**Action:** Verify that the connections.xml file contains a valid connection entry for the Group Space Events service, and the Group Space Events server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03216: failure to retrieve group space event detail**

**Cause:** Either the connections.xml file did not contain a valid connection entry for the Group Space Events service, or the Group Space Events server was down.

**Action:** Verify that the connections.xml file contains a valid connection entry for the Group Space Events service, and the Group Space Events server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03217: failure to check the relationship for the event**

**Cause:** Either the connections.xml file did not contain a valid connection entry for the Relationship service, or the Relationship service was down.

**Action:** Verify that the connections.xml file contains a valid entry for the Relationship service, the Relationship service is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03218: failure to save the display mode preference**

**Cause:** Either the connections.xml file did not contain a valid connection entry for the Preferences service, or the Preferences service was down.

**Action:** Verify that the connections.xml file contains a valid entry for the Preferences service, and the Preferences service is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03219: failure to change the repeat attributes**

**Cause:** Either the connections.xml file did not contain a valid connection entry for the Events service, or the Events service was down.

**Action:** Verify that the connections.xml file contains a valid entry for the Events service, and the Events service is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03220: The event was deleted by another user after you retrieved it. Refresh the Events task flow to see the changes if necessary.**

---

**Cause:** The event was deleted by another user after you retrieved it.

**Action:** Refresh the Events task flow to view changes, and try again.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-03221: The event was updated by another user after you retrieved it. Refresh the Events task flow to see the changes if necessary.**

**Cause:** The event was updated by another user after you retrieved it.

**Action:** Refresh the Events task flow to view changes, and try again.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-03222: You do not have permission to update this event or your permission to update this event is revoked. Refresh the Events task flow to see the changes if necessary.**

**Cause:** You do not have permission to update this event or your permission to update this event is revoked.

**Action:** Refresh the Events task flow to view changes, and try again.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-03223: You do not have permission to view this event or your permission to view this event is revoked. Refresh the Events task flow to see the changes if necessary.**

**Cause:** You do not have permission to view this event or your permission to view this event is revoked.

**Action:** Refresh the Events task flow to view changes, and try again.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-03224: You do not have permission to create the event or your permission to create the event is revoked. Refresh the Events task flow to see the changes if necessary.**

**Cause:** You do not have permission to create this event or your permission to create this event is revoked.

**Action:** Refresh the Events task flow to view changes, and try again.

**Level:** 1

**Type:** WARNING

**Impact:** Other

---

**WCS-03225: You do not have permission to delete the event or your permission to delete the event is revoked. Refresh the Events task flow to see the changes if necessary.**

**Cause:** You do not have permission to delete this event or your permission to delete this event is revoked.

**Action:** Refresh the Events task flow to view changes, and try again.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-03226: You do not have permission to manage the event or your permission to manage the event is revoked. Refresh the Events task flow to see the changes if necessary.**

**Cause:** You do not have permission to manage this event or your permission to manage this event is revoked.

**Action:** Refresh the Events task flow to view changes, and try again.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-03227: Event not found.**

**Cause:** The event doesn't exist or was deleted.

**Action:** Refresh the Events task flow to view changes, and try again.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-03228: The Events service is currently disabled, preventing you from performing this operation. Contact your administrator.**

**Cause:** The Events service is currently disabled.

**Action:** Contact your administrator. Enable the Events service.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-03301: The Web Conference service is unavailable.**

**Cause:** Either the connections.xml file did not contain a valid connection entry, or the adapter was not defined in the adf-config.xml file.

**Action:** Verify that the connections.xml file contains a valid connection entry, and the specified adapter is defined in the adf-config.xml file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03302: The Web Conference service is unavailable.**

---

**Cause:** The connections.xml file either did not contain a valid connection entry or the entry for conference service with the state attribute set to default was missing.

**Action:** Verify that the connections.xml file contains a valid connection entry and that the conference server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03303: failure to query data in WebCenter Conference service**

**Cause:** There was an issue with the connections.xml file, or the Conference server was down.

**Action:** Verify that the connections.xml file contains a valid connection entry and that the Conference server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03304: failure to create conference in WebCenter Conference service**

**Cause:** There was an issue with the connections.xml file, or the Conference server was down.

**Action:** Verify that the connections.xml file contains a valid connection entry and that the Conference server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03305: failure to update conference in WebCenter Conference service**

**Cause:** There was an issue with the connections.xml file, or the Conference server was down.

**Action:** Verify that the connections.xml file contains a valid connection entry and that the Conference server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03306: failure to delete conference in WebCenter Conference service**

**Cause:** There was an issue with the connections.xml file, or the Conference server was down.

**Action:** Verify that the connections.xml file contains a valid connection entry and that the Conference server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03307: failure to retrieve personal meetings**

---

**Cause:** There was an issue with the connections.xml file, or the Conference server was down.

**Action:** Verify that the connections.xml file contains a valid connection entry and that the Conference server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03308: The Conference service is not properly configured.**

**Cause:** The Conference service was not properly configured in connections.xml.

**Action:** Verify that the connections.xml file contains a valid entry for the Conference service.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03309: The Conference service is properly not configured.**

**Cause:** The Conference service was not configured in connections.xml.

**Action:** Verify that the connections.xml file contains a valid entry for the Conference service.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-03310: The Conference service is not properly configured.**

**Cause:** The ambiguous connections of Conference service were found in connections.xml.

**Action:** Verify that the connections.xml file contains a valid entry for the Conference service.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03701: WebCenter Tasks service unable to acquire a data connection.**

**Cause:** There was an issue with the connections.xml file, or the BPEL server was down.

**Action:** Verify that the connections.xml file contains a valid entry with the bpel.state set to default, and that the BPEL server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03702: Tasks query failed in WebCenter Task service.**

**Cause:** There was an issue with the connections.xml file, or the BPEL server was down.

---

**Action:** Verify that the connections.xml file contains a valid entry with the bpel.state set to default, and that the BPEL server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03703: Create task failed in WebCenter Task service.**

**Cause:** There was an issue with the connections.xml file, or the BPEL server was down.

**Action:** Verify that the connections.xml file contains a valid entry with the bpel.state set to default, and that the BPEL server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03704: Task update failed in WebCenter Tasks service.**

**Cause:** There was an issue with the connections.xml file, or the BPEL server was down.

**Action:** Verify that the connections.xml file contains a valid entry with the bpel.state set to default, and that the BPEL server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03705: Task purge failed in WebCenter Tasks service.**

**Cause:** There was an issue with the connections.xml file, or the BPEL server was down.

**Action:** Verify that the connections.xml file contains a valid entry with the bpel.state set to default, and that the BPEL server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03706: Task delete failed in WebCenter Tasks service.**

**Cause:** There was an issue with the connections.xml file, or the BPEL server was down.

**Action:** Verify that the connections.xml file contains a valid entry with the bpel.state set to default, and that the BPEL server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-03707: The adf-config.xml element associated with the BPEL connection to be used by the To-Dos and Group Tasks service was not present.**

**Cause:** "The application\'s adf-config.xml file was missing the adf-task-config element containing a BPELConnection name.

---

**Action:** Add the adf-config.xml entry associated with the To-Dos and Group Tasks service\'s BPEL connection using the appropriate configuration manipulation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04001: unable to resolve the name {0}**

**Cause:** The object with the given name could not be found.

**Action:** Check the JNDI configuration or the context passed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04002: ADFConfig does not contain adf-collaboration-config details with namespace: {0}.**

**Cause:** The collaboration configuration tag 'adf-collaboration-config' might have been missing in ADFConfig.

**Action:** Ensure that the adf-config.xml file contains the adf-collaboration-config tag.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04003: No adapter found for service {0}**

**Cause:** No adapter configuration found or the implementation class could not be loaded.

**Action:** Ensure adapter is configured properly or change the SessionFactory to override the default behavior.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04004: unable to load the class {0}**

**Cause:** The class named in the error message was not available in the class path.

**Action:** Check the class path and ensure this class is available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04005: unable to load the class {0}, due to: {1}**

**Cause:** Either the class named in the error message was not available in the class path or it could not be instantiated.

**Action:** Check the logs for more details. Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR



---

**Impact:** Other

**WCS-04006: ADFConfig {0} {1} does not contain the required attribute {1}.**

**Cause:** The required attribute was missing from the configuration.

**Action:** Ensure that the required attribute is added to the configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04007: The attachment size is too large to be consumed.**

**Cause:** The storage quota was exceeded.

**Action:** Select a different attachment with a smaller size.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04008: The attachment type is not supported.**

**Cause:** The attachment type was not supported.

**Action:** Try with a different MIME type.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04009: The attachment cannot be found.**

**Cause:** The attachment was not readable.

**Action:** Try a different attachment.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04010: failure to create, update, or fetch the service configuration file {0}, due to: {1}**

**Cause:** One of the following was the cause: There was a concurrent modification by another user; there was an MDS I/O exception; the metadata was not found; a validation error occurred; or the update was not supported.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04011: unable to find the service configuration file {0}, due to: {1}**

**Cause:** The service was not provisioned for this group space.

**Action:** Provision this service or contact the system administrator.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-04012: unable to find the credentials for user {0}**

**Cause:** The credentials were either not supplied, or were invalid.

**Action:** Supply credentials using the External Application configured for the service.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04013: failure to authenticate the user {0}, due to: {1}**

**Cause:** There was a failure while connecting to server, or the credentials were invalid.

**Action:** Ensure the credentials are supplied and are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04014: no connections available for: {0}**

**Cause:** There are no connections defined for this connection type.

**Action:** At least one connection must be defined for this connection type.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04015: There are multiple connections defined for the connection type {0}, but no default connection is specified.**

**Cause:** Multiple connections of this type were defined, but the default connection was not specified.

**Action:** Select the appropriate connection for this type and mark it as the default.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04016: unable to look up connection with name {0}**

**Cause:** Either the connection name was wrong or the connection was deleted.

**Action:** Verify the name of the connection supplied and also ensure that the connection with this name is available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04017: failure to create session instance for: {0}**

**Cause:** An instantiation exception occurred for the session class. Either this class was not a valid class or it could not be loaded from the class path.

---

**Action:** Verify that the session class supplied is a valid class, and that it is available in the class path.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04018: failure to create session for {0}, due to: {1}**

**Cause:** Either the required configuration was missing or class was not found.

**Action:** Verify that the session class supplied is a valid class, and that it is available in the class path.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04019: There are multiple adapters for the session {0}, but the default adapter is not specified.**

**Cause:** Multiple adapters were defined for this session type, but the default adapter was not specified in the connection.

**Action:** Update the connection and ensure that the adapter name is specified (ensure that the "adapter.name" property exists).

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04020: No adapter found with name {0}.**

**Cause:** Adapter not found with the given name.

**Action:** Ensure the adapter with this name configured in the adf-config.xml file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04021: Not an instance of {1} : {0}**

**Cause:** Supplied class is not an instance of SessionManager class.

**Action:** Check the service configuration property "session.manager.class".

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04022: The service is unavailable.**

**Cause:** Cannot establish connection to the server, either the server is down or the connect details are wrong.

**Action:** Contact system administrator.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-04023: Cache not available.**

**Cause:** Cache is not initialized.

**Action:** Contact system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04024: unable to find object {0} in the cache**

**Cause:** The object was either not cached or it had expired.

**Action:** Ensure that the object is cached.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04025: Session not initialized {0}.**

**Cause:** Either initialize method on the session is not invoked or initialization has failed.

**Action:** Check logs for more details or Contact system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04026: session instance acquired is null from SessionFactory: {0}**

**Cause:** SessionFactory returned null session instance. Wrong factory implementation.

**Action:** Check the SessionFactory implementation for more details or contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04027: Session Factory class not defined.**

**Cause:** Either the service-config for the session is missing or "session.factory.class" property is missing.

**Action:** Check the service-config.xml for the given session type exists and "session.factory.class" property is defined with a qualified class name that is available in the classpath. Contact system administrator for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04030: System user session is requested from session {0}, but administrator user name is not defined in the connection nor in adf-config.**

**Cause:** Missing "admin.user" property from connection and/or adf-config.xml.

---

**Action:** Ensure that either the connection or ADF service-config contains a property called "admin.user" with a valid administrator user.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04031: Unexpected error occurred, due to : {0}**

**Cause:** An unexpected server exception occurred.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04032: Could not get access to cache object.**

**Cause:** API should be invoked only for getting access to the root cache.

**Action:** Try using correct API.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04033: Invalid cache name: {0}.**

**Cause:** Cache name supplied is either empty or null.

**Action:** Supply valid name for the cache.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04034: Not able to fetch data due to {0}.**

**Cause:** Might be because the backend system is not reachable.

**Action:** Try after sometime.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04035: Session Type for Session instance {0} is null.**

**Cause:** Session Factory does not set the SessionType on the Session instance created.

**Action:** Check the session factory implementation.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04036: User not found: {0}.**

**Cause:** Unable to find the user with the supplied name in the user repository.

---

**Action:** Check user with the given identity exists in the user repository.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04037: Supplied class {0} is not an instance of {1}.**

**Cause:** Supplied class is not an instance of SessionFactory class.

**Action:** Check the adf-config.xml or service-config.xml configuration property "session.factory.class".

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04039: Session Manager instance creation failed for {0}**

**Cause:** Either the required configuration is missing or class is not found..

**Action:** Check the class supplied is a valid class and its available in the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04040: CacheFactory not specified.**

**Cause:** CacheFactory instance is not found.

**Action:** Set appropriate CacheFactory instance on the Cache class.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04041: No default or active connection available for: {0}**

**Cause:** There is no default or active connection defined for this connection type.

**Action:** At least one connection must be defined default or active for this connection type.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04042: Enterprise role not found: {0}.**

**Cause:** Unable to find the enterprise role with the supplied name in the backend server.

**Action:** Check group with the given identity exists in the backend server.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04201: Error loading relationship service implementation**

---

**Cause:** The relationship service encountered a problem while loading a relationship service implementation.

**Action:** Check the stack trace for more information

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04206: Error checking create permission**

**Cause:** There was an error loading the relationship security provider.

**Action:** Check to make sure that the relationship security provider is properly configured.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04207: Could not instantiate relationship repository**

**Cause:** The relationship service encountered a problem while instantiating the repository.

**Action:** Check the stack trace for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04208: jdbc/WebCenterDS data source not found: {0}**

**Cause:** The jdbc/WebCenterDS data source could not be found.

**Action:** Ensure that the jdbc/WebCenterDS data source is created.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04301: Relationship repository is not available.**

**Cause:** An error was encountered while checking if the relationship repository was available.

**Action:** Check the log for errors that may have caused this.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04401: Exception during event or action**

**Cause:** The relationship service encountered a problem while performing an event or action

**Action:** Check the application log for more information on the cause

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-04405: linksDetailedPanelWindow is null: cannot add partial target to RequestContext.**

**Cause:** The relationship popup task flow is not included in the page.

**Action:** Check to make sure the relationship popup task flow is included in the page.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04407: Exception while checking for existing links**

**Cause:** An error was encountered while checking for existing links.

**Action:** Check the application log for more information on the cause.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04408: Error instantiating RichLinksDetailButtonRow**

**Cause:** The relationship service encountered a problem while instantiating a custom component.

**Action:** Check the relationship links button component for valid attributes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04409: Error instantiating RichLinkDetailMenuItem**

**Cause:** The relationship service encountered a problem while instantiating a custom component.

**Action:** Check the relationship links menu component for valid attributes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04410: Could not find Links Detail Popup in the LinksDetailBean bean**

**Cause:** The relationship service encountered a problem while encoding the popup.

**Action:** Make sure the links popup task flow is included in the page.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04412: Attribute value is null for component: {0}**

**Cause:** A required attribute value is bound to a null value.

**Action:** Make sure the required attributes of this component are bound to non-null values.



---

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04413: An exception occurred while parsing parameter**

**Cause:** A number format exception was encountered while parsing a parameter.

**Action:** Make sure the window width/height parameters for launching relationship views are valid numbers.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04417: Could not find {0} parameter for the Links Detail taskflow.**

**Cause:** The parameter is required for processing links-detail task flow.

**Action:** Make sure the parameter is bound to a non-null value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04418: User principal is null.**

**Cause:** The user principal returned by the security context was null.

**Action:** Make sure security is properly configured for the application.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04419: Links components cannot render**

**Cause:** The links-detail-popup task flow panelWindow was not found.

**Action:** Make sure the view includes the links-detail-popup task flow.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04601: unexpected error**

**Cause:** An unexpected error occurred for the RTC service.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-04602: Unable to load RTC configuration**

**Cause:** Connections context could not be acquired.

**Action:** Ensure that the connections.xml file is available and valid.

**Level:** 1

---

**Type:** WARNING

**Impact:** Other

**WCS-04603: Unable to load RTC configuration**

**Cause:** No RTC (Real-Time Communication) connection was specified.

**Action:** Ensure that the property 'selected.connection' for the RTC service's 'service-config' element within the application's adf-config.xml file is available with a valid RTC connection name value.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04604: Unable to lookup RTC connection {0}**

**Cause:** The specified connection name either did not exist or did not resolve to a valid RTC connection.

**Action:** Ensure that the property 'selected.connection' for the RTC service's 'service-config' element within the application's adf-config.xml file contains a valid RTC connection name (as defined in the application's connections.xml file).

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04605: Unable to load RTC adapter {0}**

**Cause:** The specified RTC adapter name was invalid.

**Action:** Ensure that the property 'adapter.name' of the RTC connection is valid and the corresponding adapter definition is available within the RTC 'service-config' element in the application's adf-config.xml file.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04606: Unable to load RTC adapter {0}**

**Cause:** The specified RTC adapter class does not extend from IMPConnection class.

**Action:** Ensure that the RTC adapter class extends IMPConnection class and follows its contract.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04607: Unable to load RTC adapter {0}**

**Cause:** The specified RTC adapter class could not be instantiated.

**Action:** Ensure that the RTC adapter class extends IMPConnection class and follows its contract.

**Level:** 1

**Type:** WARNING

---

**Impact:** Other

**WCS-04608: Unable to load RTC adapter {0}**

**Cause:** The RTC configuration object was null or invalid.

**Action:** Ensure that the RTC configuration is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04610: Unable to create instance of the UserManager implementation class {0}.**

**Cause:** The specified user manager class could not be instantiated.

**Action:** Ensure that the class exists and can be instantiated with a default constructor.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04611: Unable to find a valid RTC connection.**

**Cause:** No RTC connections were found within the application's connections.xml file.

**Action:** Ensure that there is a valid RTC connection defined in the application's connections.xml file.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04612: Invalid RTC address resolver specified: {0}**

**Cause:** Specified address resolver was invalid.

**Action:** Ensure that the resolver type is one of DEFAULT, PROFILE\_ATTRIBUTE, or CUSTOM.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04614: Invalid attribute specified for PROFILE address resolver: {0}**

**Cause:** The specified profile attribute for the address resolver was invalid.

**Action:** Ensure that the 'rtc.address.resolver.mapping' attribute is not null and contains a valid profile attribute.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04615: Unable to load custom RTC address resolver: {0}**

**Cause:** The custom class could not be initialized.

**Action:** Ensure that the custom class extends RtcAddressResolver and follows the contract specified by it.

---

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04616: Unable to load custom RTC address resolver: {0}**

**Cause:** No custom class was specified for the CUSTOM type RTC address resolver.

**Action:** Ensure that the 'rtc.address.resolver.mapping' attribute is not null and contains a fully qualified and valid class name that extends from the RtcAddressResolver class.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04619: The RTC address resolver supplied is invalid or null.**

**Cause:** The RTC address resolver supplied was invalid or null.

**Action:** Ensure that 'rtc.address.resolver.mapping' attribute is not null.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04620: The domain supplied is invalid or null.**

**Cause:** The domain supplied was invalid or null.

**Action:** Ensure that the 'domain' attribute is not null or invalid.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04621: Invalid timeout value specified: {0} Defaulting to {1}**

**Cause:** The presence cache timeout value was either null or not a valid number.

**Action:** Ensure that the 'rtc.cache.time' attribute is not null and contains a valid number.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04625: Failed to instantiate IMPSession for the logged-in user.**

**Cause:** The adapter class could not be instantiated.

**Action:** Ensure that the property 'adapter-class' has been defined for the adapter in the adf-config.xml and is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04701: Unable to load LCS adapter: base connection URL is missing.**

---

**Cause:** The property 'base.connection.url' was missing.

**Action:** Ensure that the LCS connection entry contains the 'base.connection.url' property and points to a valid URL.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04702: Unable to load LCS adapter: LCS PoolName is missing.**

**Cause:** The property 'LCSPoolName' was missing.

**Action:** Ensure that the LCS connection entry in connections.xml contains the 'LCSPoolName' property and contains a valid LCS pool name.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04703: Unable to perform operation {0}**

**Cause:** Failed to perform the operation on remote Web service.

**Action:** Ensure that the RTC configuration is correct, the remote system is available, and the errors generated in the remote system's logs have been fixed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04704: Failed to log on user {0}.**

**Cause:** User login failed.

**Action:** Check user credentials and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04705: Exception caught while fetching buddy list for user {0}**

**Cause:** Failed to retrieve buddy list from the Remote Service.

**Action:** Ensure that valid LCS connection entries have been supplied and the server is up.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04706: Exception caught while fetching presence information using user account {0}**

**Cause:** Failed to fetch presence information from the remote service .

**Action:** Ensure that valid LCS connection entries have been supplied and the server is up.

**Level:** 1

---

**Type:** WARNING

**Impact:** Other

**WCS-04707: Failed to add user {0} to the logged in user's buddy list (logged in user:{1})**

**Cause:** Failed to update buddy list of the user.

**Action:** Ensure that the server is up and responding.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04708: Failed to remove user {0} from the logged in user's buddy list (logged in user:{1})**

**Cause:** Failed to update buddy list of the user.

**Action:** Ensure that the server is up and responding.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04751: Unable to load OCMS adapter**

**Cause:** Missing property 'base.connection.url'

**Action:** Ensure that the OCMS connection entry contains the 'base.connection.url' property and points to a valid URL. It should look like http://host:port. This is the machine where the OCMS server is installed.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04758: Exception caught while fetching buddy list for user {0}**

**Cause:** Exception caught while fetching buddy list.

**Action:** Ensure that valid OCMS connection entries have been supplied and the server is up.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04759: Failed to subscribe for presence for user {0}**

**Cause:** The OCMS Server threw back exception while subscribing for user's presence.

**Action:** Ensure that valid OCMS connection entries have been supplied

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04760: Failed to do bulk subscribe using user account {0}**

---

**Cause:** The OCMS Server threw back exception while subscribing for users' presence.

**Action:** Ensure that valid OCMS connection entries have been supplied

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04761: Failed to get bulk presence using user account {0}**

**Cause:** Failed to fetch presence information from the remote service .

**Action:** Ensure that valid OCMS connection entries have been supplied and resolve any exceptions thrown during subscription.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04762: Failed to get group space user's connection instance**

**Cause:** Failed to login using the group space credentials.

**Action:** Ensure that the server is up and responding.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04763: Exception caught while fetching presence information for user {0}**

**Cause:** Failed to fetch presence information from the remote service .

**Action:** Ensure that valid OCMS connection entries have been supplied and resolve any exceptions thrown during subscription.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04764: Failed to add user {0} to the group space user's buddy list (group space user:{1})**

**Cause:** Failed to update buddy list of the group space user.

**Action:** Ensure that the server is up and responding.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04765: Failed to remove user {0} from the group space user's buddy list (group space user:{1})**

**Cause:** Failed to update buddy list of the group space user.

**Action:** Ensure that the server is up and responding.

**Level:** 1

**Type:** WARNING

---

**Impact:** Other

**WCS-04768: Unable to read admin information for the OCMS Connection.**

**Cause:** Admin information not available to establish the connection.

**Action:** Provide admin username and password parameters for the connection.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04769: Unable to read buddy list information for group space user {0}.**

**Cause:** Buddy List information cannot be read for the Group Space.

**Action:** Make sure that the MDS database is accessible.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04771: Unable to read call information.**

**Cause:** Call information cannot be read for the current third party call.

**Action:** Make sure that the third party service is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04772: Failed to initialize call between {0} and {1}.**

**Cause:** Could not initialize the call using the OWLCS Third Party Call Service.

**Action:** Ensure the Third Party Call Service (WebService) is deployed and running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04801: Invalid timeout value specified: {0} Defaulting to {1}**

**Cause:** The presence cache timeout value was either null or not a valid number.

**Action:** Ensure that the 'rtc.cache.time' attribute is not null and contains a valid number.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04804: Unable to acquire RTC connection for user {0}. RTCService running in dummy mode.**

**Cause:** Exception caught while initializing IMPCConnection.

**Action:** Check the log file for more information.

**Level:** 1

**Type:** ERROR



---

**Impact:** Other

**WCS-04805: Unable to acquire associated external application details.**

**Cause:** The external application ID could not be loaded from the RTC connection configuration.

**Action:** Ensure that the 'ext.app.id' attribute is not null and refers to a valid external application ID.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04806: Unable to acquire associated external application details.**

**Cause:** The external application was not found for the external application ID.

**Action:** Ensure that external application ID refers to a valid external application.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04851: Failed to generate endpoint to talk to OCS WebService.**

**Cause:** The webservice is unreachable.

**Action:** Ensure that the OCS connection entry contains the 'base.connection.url' property and points to a valid URL.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04852: Unable to perform operation {0}**

**Cause:** Failed to perform the operation on remote Web service.

**Action:** Ensure that the RTC configuration is correct, the remote system is available, and the errors generated in the remote system's logs have been fixed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-04853: Exception caught while fetching buddy list for user {0}**

**Cause:** Failed to retrieve buddy list from the Remote Service.

**Action:** Ensure that valid OCS connection entries have been supplied and the server is up.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04854: Exception caught while fetching presence information using user account {0}**

**Cause:** Failed to fetch presence information from the remote service .

---

**Action:** Ensure that valid OCS connection entries have been supplied and the server is up.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04901: Not initializing RtcAction {0} as it does not extend from RtcAction**

**Cause:** Specified class does not extend from RtcAction.

**Action:** Ensure that the specified class is a proper subclass of RtcAction.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04902: Failed to initialize RtcAction {0}**

**Cause:** Unable to instantiate the supplied RtcAction subclass.

**Action:** Ensure that the specified class is a proper subclass of RtcAction, and provides a default constructor.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04903: ADFConfig does not contain rtc-config details with namespace : {0}.**

**Cause:** The RTC actions tag 'rtcC:actions' might be missing in ADFConfig.

**Action:** Ensure adf-config.xml file contains rtcC:actions tag.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04904: Cannot process call request : User Profile for user {0} not found**

**Cause:** User has selected PSTN call method but its profile cannot be found for the user to read the contact number.

**Action:** Ensure that the user profile exists in the system.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04905: Cannot process call request : Contact information for user {0} not found**

**Cause:** User has selected PSTN call method but has not supplied the correct ldap attribute to read the contact information.

**Action:** Ensure that correct ldap attribute has been supplied in connection/adf-config and its value has been set in the profile.

**Level:** 1

**Type:** WARNING

**Impact:** Other

---

**WCS-04906: Cannot process call request : Incorrect call method supplied**

**Cause:** User has supplied an incorrect call method.

**Action:** Ensure that correct call method is supplied. Refer to the documentation to find the supported call methods.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04907: Cannot process call request : Call domain not specified in connection.**

**Cause:** User has selected PSTN call method but has not supplied the call.domain property.

**Action:** Ensure that correct call.domain has been supplied in connection/adf-config.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-04908: Cannot process call request : User name is missing or not provided.**

**Cause:** User name is missing or it has not been provided.

**Action:** Ensure that correct user name is provided, contact administrator.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-05001: Cannot retrieve the metadata for a group space**

**Cause:** Unable to fetch the group space metadata due to an internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05002: An error occurred while trying to get the ScopeAPI implementation for the service {0}.**

**Cause:** Service {0} does not support provisioning.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05003: The service object passed to the wrapper is null.**

**Cause:** A null service object was retrieved from the service registry.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Other

**WCS-05004: A group space template named {0} already exists.**

**Cause:** Name specified for the group space template was not unique. A template with the same name already exists.

**Action:** Provide a unique name for the group space template.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05005: Cannot create group space template**

**Cause:** No name was provided for the group space template.

**Action:** Provide a unique name for the group space template.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05006: Unable to retrieve information about {0}.**

**Cause:** No group space template was found with the name specified.

**Action:** Provide the name of an existing group space template.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05007: The reference to the group space template metadata {0} is invalid.**

**Cause:** No group space template was found with the name specified.

**Action:** Provide the name of an existing group space template.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05008: Unable to get mutable metadata for the group space template {0}**

**Cause:** Some portion of the group space template metadata has already been modified.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05009: Metadata for the group space template {0} is invalid.**

**Cause:** MDS reported a metadata validation error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Other

**WCS-05010: An error occurred reading or writing metadata of group space template {0}.**

**Cause:** MDS reported an IO error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05011: The commit operation failed due to a concurrent metadata change for group space template {0}.**

**Cause:** MDS reported a concurrent metadata change error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05013: Unable to execute group space related operation on {0}**

**Cause:** Either the metadata did not exist, an invalid metadata reference was used or an attempt was made to get mutable metadata that has already been changed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05014: Unable to get metadata for group space {0}.**

**Cause:** Either the metadata did not exist, an invalid metadata reference was used or an attempt was made to get mutable metadata that has already been changed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05015: Cannot create metadata for group space {0}**

**Cause:** Metadata for the specified group space already exists.

**Action:** Provide a different name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05018: The reference to the metadata of group space {0} is invalid.**

**Cause:** The metadata reference was invalid.

**Action:** Contact Oracle Support Services.

**Level:** 1

---

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05019: Unable to get mutable metadata for the group space {0}**

**Cause:** Some portion of the group space metadata has already been modified.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05020: Metadata of group space {0} is invalid.**

**Cause:** MDS reported a metadata validation error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05021: An error occurred reading or writing metadata of group space {0}.**

**Cause:** MDS reported an IO error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05022: The commit operation failed due to a concurrent metadata change for group space {0}.**

**Cause:** MDS reported a concurrent metadata change error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05023: Cannot retrieve a list of members for the current group space.**

**Cause:** An error occurred trying to access the specified group space.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05025: Could not create group space {0} from group space template {1}.**

**Cause:** An internal error occurred.

**Action:** Contact Administrator.

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Other

**WCS-05026: Cannot save group space {0} as group space template {1}**

**Cause:** Either the specified group space template already exists or the name was invalid.

**Action:** Provide a valid,unique name for the group space template.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05027: Unable to get preference metadata for the group space {0}**

**Cause:** Either the metadata does not exist, an invalid metadata reference was used or an attempt was made to get mutable metadata that has changed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05035: Unexpected error in renaming group space from {0} to {1}. Contact administrator or try again after some time.**

**Cause:** An invalid character was found in the name.

**Action:** Remove the invalid character(s) from the name and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05036: A group space named {0} already exists.**

**Cause:** A group space with the specified name exists.

**Action:** Specify a unique name for the group space.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05037: The group space template name contains an invalid character {0}.**

**Cause:** An invalid character was found in the group space template name.

**Action:** Remove the invalid character(s) from the group space template name and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05038: A group space template named {0} already exists.**

**Cause:** A group space template with the specified name already exists.

**Action:** Specify a unique name for the group space template.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WCS-05039: An error occurred attempting to save this group space as a group space template.**

**Cause:** An internal error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05040: The group space name contains one or more blank space characters.**

**Cause:** A blank space was found in the group space name. Blank spaces are not allowed.

**Action:** Remove all blank spaces from the group space name and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05041: The group space template name contains one or more blank space characters.**

**Cause:** A blank space was found in the name of the group space template. Blank spaces are not allowed.

**Action:** Remove all blank spaces from the group space template name and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05042: Unable to get metadata {1} for group space {0}.**

**Cause:** Either the metadata did not exist, an invalid metadata reference was used or an attempt was made to get mutable metadata that has already been changed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05043: A group space with display name {0} already exists.**

**Cause:** A group space with the specified display-name exists.

**Action:** Specify a unique display-name for the group space.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05047: Sending invitation to user(s) failed. The reason is : {0}.**



---

**Cause:** Connection details for the BPEL Server providing group space invitation services were not available.

**Action:** Ask your WebCenter administrator to configure a connection to the BPEL Server providing group space invitation services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05048: Unexpected error occurred while trying to invite user(s) to group space {0}**

**Cause:** The BPEL server that provides the group space invitation service might have been down.

**Action:** Ask the WebCenter administrator to restart the BPEL Server, and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05058: Cannot create policy store metadata for group space {0}**

**Cause:** An internal error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05059: Cannot save the changes**

**Cause:** An internal error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05063: Cannot delete group space {0} due to unknown errors.**

**Cause:** An internal error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05065: Cannot not get the list of available services**

**Cause:** No services were available in the service registry.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Other

**WCS-05066: An error occurred while attempting to unsubscribe a user from group space {0}.**

**Cause:** The BPEL Server supporting group space unsubscription may be down

**Action:** Ask your WebCenter administrator to restart the BPEL Server and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05067: Unable to send unsubscription request to modertor(s). The reason is : {0}.**

**Cause:** Connection details for the BPEL Server providing group space unsubscription services were not available.

**Action:** Ask your WebCenter administrator to configure a connection to the BPEL Server providing group space unsubscription services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05068: An error occurred attempting to unsubscribe user from group space {0}: {1}.**

**Cause:** Connection details for the BPEL Server providing group space unsubscription services were not available.

**Action:** Ask your WebCenter administrator to configure a connection to the BPEL Server providing group space unsubscription services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05069: Unable to send subscription notification to moderator(s). The reason is : {0}.**

**Cause:** The BPEL URL has not been configured yet.

**Action:** Notify your WebCenter administrator that the BPEL service supporting group space subscription is not configured

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05070: An error occurred attempting to subscribe a user to the group space:{0}.**

**Cause:** The BPEL Server providing the group space subscription service may be down.

**Action:** Ask your WebCenter administrator to restart the BPEL Server, and try again.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-05071: An error occurred attempting to subscribe user to the group space {0}: {1}.**

**Cause:** The BPEL Server providing the group space subscription service may be down.

**Action:** Ask your WebCenter administrator to restart the BPEL Server, and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05072: Error occurred while navigating to the group space {0}.**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05073: Could not create group space with name {0}**

**Cause:** The scope name provided couldn't be created.

**Action:** Please contact Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05074: An error occurred attempting to access a page of the renamed group space.**

**Cause:** The group space rename operation was not successful.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05075: An error occurred attempting to rename a group space.**

**Cause:** An internal error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05077: Could not retrieve group space workflow configuration. Please contact administrator.**

**Cause:** An error occurred attempting to retrieve the BPEL Several URL configured in connections.xml

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05079: Cannot get the security handler for group space template {0}**

**Cause:** The policy store metadata was not available for group space template security initialization.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05080: Cannot create the group space template {0}**

**Cause:** The group space template was not created due to an error reported by the metadata store.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05081: Unable to retrieve metadata object for group space {0}**

**Cause:** An internal error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05083: An error occurred attempting to rename group space {0} to {1}.**

**Cause:** The group space rename operation was successful.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05084: An unexpected error occurred attempting to delete the group space {0}.**

**Cause:** The group space delete operation was unsuccessful.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05085: Group space name cannot be null**

**Cause:** Group space name was blank.

**Action:** Enter a valid alphanumeric name for the group space

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05086: Group space name is a reserved keyword.**

**Cause:** The group space name specified was a reserved keyword.

**Action:** Specify a valid alphanumeric name for the group space which excludes the following reserved keywords: webcenter, pages, page, spaces, space, group, groups, group space, group spaces, webcenter space, webcenter spaces, webcenter administration, my group spaces, admin, last.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05087: The group space name contains invalid characters. Only alphanumeric and space characters are allowed.**

**Cause:** Group space name contained non-alphanumeric/space characters.

**Action:** Specify a valid alphanumeric name for the group space that only contains a-z, A-Z, 0-9, \_, or a space character

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05088: cannot delete the seeded group space template {0}**

**Cause:** An attempt was made to delete a seeded group space template.

**Action:** Do not try to delete a seeded group space template.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05089: Connection details for the BPEL Server providing group space notification services are not available. Unable to send add or delete notifications to members of group space{0}**

**Cause:** Connection details for the BPEL Server providing group space invitation services were not available or configured incorrectly.

**Action:** Ask your WebCenter administrator to configure a connection to the BPEL Server providing group space notification services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05090: An error occurred attempting to send a notification to a member added to or deleted from group space {0}**

**Cause:** An error occurred attempting to send a group space notification.

**Action:** Contact Oracle Support.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WCS-05091: Connection details for the BPEL Server providing notification services in WebCenter Spaces not found.**

**Cause:** Connection details for the BPEL Server providing notification services in WebCenter Spaces were not available.

**Action:** Ask your WebCenter administrator to configure a connection to the BPEL Server providing notification services in Webcenter Spaces

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05092: One of the arguments passed to API call {0} is null**

**Cause:** A null argument was passed to an API call

**Action:** Invoke the API with non-null arguments

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05093: Group space template name cannot be null**

**Cause:** No name was specified for the group space template.

**Action:** Specify a valid alphanumeric name for group space template.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05094: Group space template name is a reserved keyword.**

**Cause:** The template name specified was a reserved keyword.

**Action:** Specify a valid alphanumeric name for the template which excludes the following reserved keywords: webcenter, pages, page, spaces, space, group, groups, group space, group spaces, webcenter space, webcenter spaces, webcenter administration, my group spaces, admin, last

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05095: Template name contains invalid characters. Only alphanumeric and space characters are allowed.**

**Cause:** Template name contains non-alphanumeric or space characters

**Action:** Specify a valid alphanumeric name for the template that only contains: a-z, A-Z, 0-9, \_, or a space character

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WCS-05096: A template with name {0} already exists.**

**Cause:** A template with the specified name exists.

**Action:** Specify a unique name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05097: Cannot upload group space icon**

**Cause:** An error occurred while attempting to upload the file to WebCenter

**Action:** Try again or contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05098: Cannot upload a group space logo**

**Cause:** An error occurred attempting to upload the file to WebCenter

**Action:** Try again or contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05099: Unable to set lock on group space {0}**

**Cause:** A lock could not be acquired for this group space.

**Action:** Wait and try after again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05100: Unable to execute operation on group space {0}**

**Cause:** Group space {0} was locked by some other operation.

**Action:** Wait for the first operation to complete and try again..

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05101: Unable to execute group space operation**

**Cause:** The group space was locked by some other operation.

**Action:** Wait for the first operation to complete and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05102: Error creating group space {0} from group space template {1}**

**Cause:** An internal error occurred.

---

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05103: Errors while renaming group space {0}**

**Cause:** An internal error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05104: unexpected error while trying to request change membership to group space {0}**

**Cause:** The BPEL server might have been down.

**Action:** Ensure BPEL server is up and retry. Contact the group space moderator for assistance.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05105: unexpected error while trying to send notification to user {0}**

**Cause:** The BPEL server might have been down.

**Action:** Ensure BPEL server is up and retry. Contact the group space moderator for assistance.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05106: unexpected error creating region in cache**

**Cause:** An attempt to create a region in the JOC (Java Object Cache) failed.

**Action:** Ensure that the JOC configuration is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05107: unexpected error getting object {0} from region {1} in cache**

**Cause:** An attempt to retrieve an object from the cache failed.

**Action:** Ensure that the JOC configuration is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05108: Search {0} for group space returned more than {2} results.**



---

**Cause:** Search matched {1} results for group space template. The maximum number of result records allowed for this report is {1}.

**Action:** Restrict your query further, or use a different query.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05109: Group space operation resulted in unexpected exception.**

**Cause:** An internal error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05111: Creating template resulted in unexpected exception.**

**Cause:** An internal error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05112: fetching group space member count resulted in unexpected exception.**

**Cause:** An internal error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05113: An error occurred while trying to provision the service "{0}". The service did not get provisioned.**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05114: An error occurred while trying to unprovision the service "{0}". The service did not get unprovisioned.**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WCS-05115: An error occurred while trying to determine the selected service.**

**Cause:** An unexpected error occurred.

**Action:** Reload the browser page, and if problem persists, contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05116: An error occurred while trying to process the service that was selected.**

**Cause:** An unexpected error occurred.

**Action:** Reload the browser page, and if problem persists, contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05117: An error occurred while trying to load the configuration screen for the selected service.**

**Cause:** An unexpected error occurred.

**Action:** Reload the browser page, and if problem persists, contact the administrator.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-05118: Failed to delete the group space {0} Security metadata**

**Cause:** Deletion of group space security metadata failed

**Action:** An unexpected error occurred while trying to deleting the scope {0}. Please contact administrator for assistance.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05119: An unexpected error occurred while trying to provision/unprovision services.**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05120: An unexpected error occurred while trying to save the configuration for the service "{0}".**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05121: An unexpected error occurred while trying to upload an image for group space {0}.**

**Cause:** An unexpected error occurred during image upload.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05122: There was an error while fetching the GUID for scope ID {0}.**

**Cause:** An unexpected error occurred while fetching the GUID for the space {0}.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05123: Metadata Not Found Exception occurred while fetching the service config metadata for a group space {0}.**

**Cause:** An unexpected error occurred while fetching the service config metadata for group space {0}

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05124: An exception occurred while fetching the Space Manager for the group space {0}.**

**Cause:** An unexpected error occurred while fetching the Space Manager for the group space {0}.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05125: An exception occurred while fetching the Space for the group space {0}.**

**Cause:** An unexpected error occurred while fetching the Space for the group space {0}.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05126: An exception occurred while fetching the GUID for the group space {0}.**

---

**Cause:** An unexpected error occurred while fetching the GUID the GUID for the group space {0}.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05127: An exception occurred while fetching the contacts list for group space {0}.**

**Cause:** An unexpected error occurred fetching the contacts list for group space {0}.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05128: An exception occurred while fetching the GUID for the group space {0}.**

**Cause:** An unexpected error occurred while fetching the GUID for the group space {0}.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05129: Error occurred while launching the delete role confirmation.**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05130: Error occurred while launching add/invite members table.**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05131: Error occurred while getting the message for inviting non-members.**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WCS-05132: Error occurred while performing operations on roles.**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05133: Error occurred while adding custom attributes name={0} and value={1}.**

**Cause:** An unexpected error occurred while adding the custom attributes.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05134: Error occurred while deleting the name={0} custom attribute**

**Cause:** An unexpected error occurred while deleting the custom attribute.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05135: Error occurred while editing the custom attribute name={0} and value={1}.**

**Cause:** An unexpected error occurred while editing the custom attribute.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05136: Error occurred while fetching the custom attributes for group space {0}**

**Cause:** An unexpected error occurred while fetching the custom attribute.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05137: No Such Attribute exists.**

**Cause:** Unable to find the custom attributes

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WCS-05138: Unexpected error in getting the list of group spaces. You can try again later or contact Administrator.**

**Cause:** Unexpected error in getting spaces.

**Action:** Please contact administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05139: Unexpected error in retrieving the group space {0}.**

**Cause:** Unexpected error in retrieving the group space.

**Action:** Contact Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05140: Unexpected error while rolling back the service {0}**

**Cause:** Error in rolling back the service.

**Action:** Contact Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05141: Unknown errors in Create Group Space. Please contact Administrator.**

**Cause:** Post creating the group space, there were errors.

**Action:** Contact administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05142: Group space was created successfully but refreshing the group space list failed. You may try to refresh the group space list manually.**

**Cause:** List refresh failed after creating group space.

**Action:** Manually refresh the group spaces list.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05143: Errors were encountered in creating group space. The main error is - {0}. You may want to delete the current group space if it is visible in your lists. Contact the administrator if the problem persists.**

**Cause:** Errors were seen in post-processing the create group space.

**Action:** Contact Administrator.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-05144:** Errors were encountered while creating the group space. The main error is - {0}. Rollback of the creation also failed. You may want to clean the current group space if it is visible in your lists. You may want to try to create the group space again later or contact the administrator.

**Cause:** Error in post-processing the group space.

**Action:** Contact administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05145:** Group space created with the following warning(s) : {0}

**Cause:** Group space was created with warnings.

**Action:** Contact Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05146:** Unexpected errors in deleting the group space. Contact Administrator.

**Cause:** Unexpected error in deleting the group space.

**Action:** Contact administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05147:** Deletion of the group space resulted in errors. The main error is - {0}.

You may want to try deleting the group space again later. If the error persists, contact the administrator.

**Cause:** Delete of the group spaces resulted in error.

**Action:** Contact Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05148:** Deletion of group space resulted in errors. The main error is - {0}.

Rollback of the deletion failed as well. You may want to try deleting the groups space again later. If the error persists, contact the administrator.

**Cause:** Delete of the group spaces resulted in error.

**Action:** Contact Administrator

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05149:** Group space was deleted successfully but refreshing the group space list failed. You may try to refresh the group space list manually.

---

**Cause:** List refresh failed after deleting group space.  
**Action:** You can refresh the group spaces list manually.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05150: Unexpected errors in renaming the group space. Contact Administrator.**

**Cause:** Unknown errors in renaming the group space.

**Action:** Contact Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05151: Rename of the group space resulted in errors. The main error is - {0}.**

**You may want to try to rename the group space again later. If the error persists, contact the administrator.**

**Cause:** Rename of the group space resulted in error.

**Action:** Contact Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05152: Rename of the group space resulted in errors. The main error is - {0}.**

**Rollback of renaming also failed. You may want to try to rename the group space again later or contact the administrator.**

**Cause:** Group space was renamed but there were errors in processing.

**Action:** Contact administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05153: Group space was renamed successfully but refreshing the group space list failed. You may try to refresh the group space list manually.**

**Cause:** Refreshing the list after renaming the group space failed.

**Action:** Manually refresh the list of group spaces.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05154: Group space was renamed with warnings. These are some of the warnings - {0}.**

**Cause:** Group space was renamed with warnings.

**Action:** Contact Administrator.

**Level:** 1



---

**Type:** ERROR

**Impact:** Other

**WCS-05155: Unexpected error in retrieving the group spaces list.**

**Cause:** Unexpected error in retrieving the group spaces list.

**Action:** Try again after some time. If problem persist, contact administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05156: Unexpected error while provisioning some optional services in the group space. You may want to provision them again by going to Group Space Administration.**

**Cause:** Unexpected error while provisioning some optional services in the group space.

**Action:** Contact Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05157: Provisioning some optional services {0} in the group space didn't go through successfully. You may want to provision them again by going to Group Space Administration.**

**Cause:** Provisioning some optional services in the group space didn't go through successfully.

**Action:** Contact Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05158: Unexpected error while unprovisioning the services.**

**Cause:** Unexpected error in unprovisioning the services.

**Action:** Contact administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05159: Group space was deleted with warnings. These are some of the warnings - {0}.**

**Cause:** Group space was renamed with warnings.

**Action:** Contact Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WCS-05160: Unexpected errors in while granting user access on new group space : {0}. Please contact Administrator.**

**Cause:** Unexpected errors in while granting access on new group space : {0}

**Action:** Contact Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05161: Unexpected errors in while removing access on new group space : {0}. Please contact Administrator.**

**Cause:** Unexpected errors in while removing access on new group space : {0}

**Action:** Contact Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05162: Unknown error in removing access for the group space : {0}**

**Cause:** Unexpected errors in while removing access on group Space : {0}

**Action:** Contact Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05163: Unknown error in mapping access for the new group space : {0}**

**Cause:** Unexpected errors in while mapping access on group Space : {0}

**Action:** Contact Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05164: Unexpected errors in provisioning services for new group Space : {0}**

**Cause:** Unexpected errors in provisioning services for new group Space : {0}

**Action:** Contact Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05165: Unknown error in re-provisioning services since delete failed for group space : {0}**

**Cause:** Unexpected errors in while re-provisioning services on group Space : {0}

**Action:** Contact Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WCS-05166: Unknown error while creating metadata for new template : {0}**

**Cause:** Unexpected errors in while copying metadata from space : {0} to template {1}

**Action:** Contact Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05167: Unknown error in creating metadata for the new group space : {0}**

**Cause:** Unexpected errors in while creating metadata for group Space : {0}

**Action:** Contact Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05168: Unknown error in renaming the group space.**

**Cause:** Unexpected errors in renaming the group space.

**Action:** Contact Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05169: Unknown error in renaming services from group space {0} to the group space {1}.**

**Cause:** Unexpected errors in renaming the services.

**Action:** Contact Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05170: Updates or deletes are being performed on group space {0} by another Moderator. Please try again after some time.**

**Cause:** Group space {0} is already being deleted.

**Action:** Contact Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05171: Error occurred while trying to determine if service {0} is provisioned in the current group space.**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-05172: The role {0} does not exist and hence could not be assigned to the user {1}.**

**Cause:** Role {0} may have already been deleted .

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05173: Error occurred while trying to modify the role for user {0}.**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05174: Error occurred while accessing footer information.**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05175: Group space {0} already exists.**

**Cause:** Name specified for the group space was not unique. A group space with the same name already exists.

**Action:** Provide a unique name for the group space.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05176: Group space name must contain at least one alphanumeric character**

**Cause:** Group space name did not contain any alphanumeric characters

**Action:** Provide at least one alphanumeric character for group space name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05177: Unable to perform the operation on the selected group space(s) due to unknown errors**

**Cause:** Selection of group space(s) failed

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-05178: Failed to refresh the group spaces list due to unknown errors**

**Cause:** Unknown error occurred while trying to refresh the group spaces list

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05179: Unable to perform the operation on the selected group space template(s) due to unavoidable errors**

**Cause:** Selection of group space template(s) failed

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05180: An error occurred while trying to delete the group space template(s).**

**Cause:** Selection of group space template(s) failed

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05181: Error in Create Group Space**

**Cause:** Error occurred during group space creation

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05182: Error in closing the Create GS pop-up**

**Cause:** Error occurred while closing the Group space Popup

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05183: Another user is modifying the settings. Please try after some time.**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WCS-05184: Unable to delete selected group space(s).**

**Cause:** Selection of group space(s) failed

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05185: Unable to export selected group space(s) due to unknown errors**

**Cause:** Selection of group space(s) failed

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05186: Error occurred while checking existing status of the group space {0}.**

**Cause:** An unexpected error occurred while checking existing status of the group space.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05187: Error occurred while retrieving the group space {0} creation date**

**Cause:** An unexpected error occurred while retrieving the group space creation date.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05188: Error occurred while retrieving the group space {0} status changed date.**

**Cause:** An unexpected error occurred while retrieving the group space status changed date.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05189: Failed to validate the name/display name**

**Cause:** Failed to validate the name/display name

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WCS-05190: An error occurred in post-processing the invite for {0} in group space {1}. Please contact Administrator.**

**Cause:** Unable to cleanup invited status metadata

**Action:** Please contact Administrator for assistance.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05191: Unexpected error occurred while saving the group space changes**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05192: Unexpected error occurred while making group space public.**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05193: Unexpected error retrieving data for the spaces switcher.**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05194: Group space template {0} based on group space {1} created successfully with the errors.**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05195: Group space template {0} deletion failed due to concurrent operation performed on the same resource by some other user.**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WCS-05197: Group space e-mail-id is not available because the mail service is not configured.**

**Cause:** Group space e-mail id is not available because the mail service is not configured.

**Action:** Contact the administrator to configure the mail service.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05198: Failed to initialize cache for group space template {0}.**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05199: Failed to publish/unpublish the selected group space template {0}.**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05200: Failed to update cache for group space template {0}.**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05201: Unknown error occurred while processing the templates.**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05202: User was added but could not be notified due to some errors.**

**Cause:** The BPEL server may be down.

**Action:** Ensure BPEL server is up and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Other



---

**WCS-05203: Template name must contain at least one alphanumeric character**

**Cause:** Template name did not contain any alphanumeric characters

**Action:** Provide at least one alphanumeric character for template name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05204: Group Space display name cannot be null**

**Cause:** Group space display name was blank.

**Action:** Enter a valid alphanumeric name for the group space display name

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05205: Group space display name is a reserved keyword. One of: webcenter, pages, page, spaces, space, group, groups, group space, group spaces, webcenter space, webcenter spaces, webcenter administration, my group spaces, admin, last**

**Cause:** The group space display name specified was a reserved keyword

**Action:** Specify a valid alphanumeric name for the group space display name which excludes the following reserved keywords: webcenter, pages, page, spaces, space, group, groups, group space, group spaces, webcenter space, webcenter spaces, webcenter administration, my group spaces, admin, last.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05206: The group space display name contains invalid characters. Only alphanumeric and space characters are allowed.**

**Cause:** Group space display name contained non-alphanumeric/space characters.

**Action:** Specify a valid alphanumeric name for the group space display name that only contains a-z, A-Z, 0-9, \_, or a space character

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05207: Group space display name must contain at least one alphanumeric character**

**Cause:** Group space display name did not contain any alphanumeric characters

**Action:** Provide at least one alphanumeric character for group space display name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05208: Select at least one Group Space to change state/status of Group Space.**

---

**Cause:** No Group Space has been selected or changing the state.

**Action:** Select at least one Group Space.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05209: There are no templates available for creating the Group Space(s). You should refresh the list of templates by going to "My group spaces -> templates" UI or create new templates or publish available templates if any to continue creating Group Space(s). If the problem persists contact system administrator**

**Cause:** No templates available for creating Group Space.

**Action:** Create new templates or publish existing templates if any.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05210: Unknown error occurred while initiating creation of a group space.**

**Cause:** Unable to launch the Create Group Space popup.

**Action:** Contact system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05211: Unknown error occurred while retrieving the list of templates.**

**Cause:** Unknown error occurred while retrieving the list of templates.

**Action:** Contact system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05212: User {0} not authorized to perform the operation {1}.**

**Cause:** User {0} not authorized to perform the operation {1}.

**Action:** User {0} not authorized to perform the operation {1}.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05213: Unexpected Error occurred while performing the method {0}. Contact system administrator.**

**Cause:** Unexpected Error occurred while performing the method {0}.

**Action:** Contact system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WCS-05214: Unable to retrieve information about {0} as another user is modifying the {0}. Please try again after some time.**

**Cause:** Cannot retrieve metadata for group space {0} as another user is modifying the settings. Please try after some time.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05215: User(s) added successfully, but sending notification to the user(s) failed**

**Cause:** The BPEL server may be down.

**Action:** Ensure BPEL server is up and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05216: User was removed successfully, but sending notification to the user failed**

**Cause:** The BPEL server may be down.

**Action:** Ensure BPEL server is up and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05217: User's role was modified successfully, but sending notification to the user failed**

**Cause:** The BPEL server may be down.

**Action:** Ensure BPEL server is up and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05218: Unknown error occurred while navigating to Group Space {0}.**

**Cause:** Unable to navigate to the Group Space.

**Action:** Contact system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05219: Try accessing the group space from the "Group Space menu" or "My Group Spaces". If the group space is not listed, refresh the list in "My Group Spaces". If the group space is still not visible, report the error to your administrator.**

**Cause:** You can try accessing the group space from the "group space drop-down" or "My Group Spaces". If the group space is not listed, try refreshing the listing in "My Group Spaces".

---

**Action:** Contact system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05220: Deletion or Rename is being performed on group space {0} by another Moderator. Refresh the list of Group Spaces and try again after some time.**

**Cause:** Group space {0} is already being deleted or renamed.

**Action:** Contact Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05221: An unexpected error occurred while trying to delete group space template. Try again after some time. If the problem persists, contact administrator.**

**Cause:** An unexpected error occurred while trying to delete group space template. Contact administrator.

**Action:** Contact system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05222: Some optional services in the group space could not be provisioned as they were disabled. You may want to provision them again by going to Group Space Administration.**

**Cause:** Unexpected error while provisioning some optional services in the group space.

**Action:** Contact Administrator and look in the logs for information about the specific service that has been disabled.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05223: Admin Role does not exist in the policy store for scope {0}, so creating it**

**Cause:** An internal error occurred

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05224: Unexpected error occurred while revoking group space public status.**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WCS-05228: Unable to send change membership notification. The reason is : {0}.**

**Cause:** The BPEL URL has not been configured yet.

**Action:** Notify your WebCenter administrator that the BPEL service supporting group space subscription is not configured

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05229: Can not retrieve group space workflow configuration. Please contact administrator.**

**Cause:** The BPEL URL has not been configured yet.

**Action:** Notify your WebCenter administrator that the BPEL service supporting group space subscription is not configured

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05230: An error occurred while searching invited user {0} in group space {1}. Please contact Administrator.**

**Cause:** Unable to search invited status metadata

**Action:** Please contact Administrator for assistance.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05231: Couldn't retrieve user {0} email id in scope {1} due to {2}**

**Cause:** Failed to retrieve email id due to {2}

**Action:** Please contact Administrator for assistance.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05232: Template publishing role does not exist in the policy store for scope {0}, so creating it**

**Cause:** Copy of the role failed, now trying to sanitize the scope security data

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05233: Sanitizing template {0} failed unable to copy the publish data**

**Cause:** An internal error occurred

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05234: WebCenter Spaces is not configured with SOA server information**

**Cause:** Soa server is not configured.

**Action:** Please contact Administrator for assistance.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05235: WebCenter Spaces is not properly configured with SOA server information**

**Cause:** Soa server information is not correct.

**Action:** Please contact Administrator for assistance.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05236: SOA server is either down or not properly configured**

**Cause:** Either SOA server may be down or spaces workflows not configured properly

**Action:** Please contact Administrator for assistance.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05237: Unexpected error occurred rebuilding the user spaces list**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05238: Unexpected error occurred rebuilding the public spaces list**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05239: Unable to retrieve group space tags.**

**Cause:** An error occurred while trying to retrieve the tags for group space.

**Action:** Please contact Administrator for assistance.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05240: Unable to create group space tags.**

**Cause:** An error occurred while trying to create the tags for group space.

**Action:** Please contact Administrator for assistance.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05241: Error occurred while getting group space activity streaming preferences**

**Cause:** An internal error occurred

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05242: Error occurred while fetching the Group Space Members Info.**

**Cause:** Error occurred while fetching the Group Space Members Info.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05243: Unexpected error deriving {0} list.**

**Cause:** An unexpected error occurred.

**Action:** Contact system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05244: The member's current role is selected. If you want to change this member's role, choose another role from the list.**

**Cause:** The new role is same as the old role.

**Action:** Select new role.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05246: Unexpected error persisting space information to tables**

**Cause:** Error saving space information to the database

**Action:** Contact Oracle Support Services.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WCS-05247: Unable to retrieve email-id for the group space.**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05248: Unable to find security policy store metadata while creating group space template {0}**

**Cause:** An error was detected in the application's configuration.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05249: Unexpected error occurred fetching ratings table from repository.**

**Cause:** An unexpected error occurred fetching the bulk ratings table from the repository.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05250: Unable to delete the group space {0} as either it is being exported or imported. Please refresh the list group spaces list and try again later.**

**Cause:** Attempt to delete group space {0} when the group space is being exported/imported.

**Action:** Try delete after sometime. Contact the administrator if the problem persist.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-05251: Unable to delete the group space template {0} as either it is being exported or imported. Please refresh the list group spaces template list and try again later.**

**Cause:** Attempt to delete group space template {0} when the group space is being exported/imported.

**Action:** Try delete after sometime. Contact the administrator if the problem persist.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other



---

**WCS-05252: Unexpected error in getting information from users table**

**Cause:** Error in getting information from the database

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05253: Role {1} of a user {0} is changed successfully to Role {2}, with failures in some of the services {3}**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05254: Unexpected error occurred while refreshing the group space cache**

**Cause:** Unexpected error occurred while refreshing the group space cache

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05255: Unexpected error occurred while cleaning up some of the permissions**

**Cause:** Failed to clean up the policies post scope creation due to unexpected error

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05256: Error while deleting role mapping metadata for group space {0}.**

**Cause:** An unexpected error occurred while deleting role mapping metadata for group space. Review the underlying exception in the logs to determine the exact cause.

**Action:** Take action based on the underlying exception details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05267: Error while deleting role mapping metadata for group space template {0}.**

**Cause:** An unexpected error occurred while deleting role mapping metadata for group space template. Review the underlying exception in the logs to determine the exact cause.

**Action:** Take action based on the underlying exception details.

**Level:** 1

---

Type: ERROR

Impact: Other

**WCS-05268: Error occurred while fetching the Group Space data.**

Cause: Error occurred while fetching the Group Space data.

Action: Contact Administrator.

Level: 1

Type: ERROR

Impact: Other

**WCS-05269: Error occurred while fetching the Group Space template data.**

Cause: Error occurred while fetching the Group Space template data.

Action: Contact Administrator.

Level: 1

Type: ERROR

Impact: Other

**WCS-05701: Deleting group space {0} failed**

Cause: WebService API failed to execute deleting web service call.

Action: Check the web service parameters, make sure the configuration is correct.

Level: 1

Type: ERROR

Impact: Other

**WCS-05702: Creating group space {0} failed**

Cause: WebService API failed to execute create web service call.

Action: Check the web service parameters, make sure the configuration is correct.

Level: 1

Type: ERROR

Impact: Other

**WCS-05703: An error occurred while revoking the roles {1} users in Group Space{0}**

Cause: WebService API failed to execute revoke role web service call.

Action: Check the web service parameters, make sure the configuration is correct.

Level: 1

Type: ERROR

Impact: Other

**WCS-05704: An error occurred while granting roles for {1} users in Group Space{0}**

Cause: WebService API failed to execute grant role web service call.

Action: Check the web service parameters, make sure the configuration is correct.

Level: 1

Type: ERROR

Impact: Other

---

**WCS-05705: Getting group space template {0} metadata failed**

**Cause:** WebService API failed to execute get space template metadata web service call.

**Action:** Check the web service parameters, make sure the configuration is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05706: Getting group space metadata {0} failed**

**Cause:** WebService API failed to execute get space metadata web service call.

**Action:** Check the web service parameters, make sure the configuration is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05707: Getting group spaces for search string {0} failed**

**Cause:** WebService API failed to execute get spaces web service call.

**Action:** Check the web service parameters, make sure the configuration is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05708: Getting group space templates for search string {0} failed**

**Cause:** WebService API failed to execute get template web service call.

**Action:** Check the web service parameters, make sure the configuration is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05709: Setting the Custom Attributes for scope {0} failed**

**Cause:** WebService API failed to execute Custom Attributes.

**Action:** Check the web service parameters, make sure the configuration is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05710: An error occurred while attempting to retrieve spaces web service endpoint configured in connections.xml of caller application**

**Cause:** Unable to retrieve spaces web service endpoint configured in caller applications connections.xml

**Action:** Please check spaces web service endpoint configured in connections.xml

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WCS-05711: One of the arguments passed to API call {0} is null**

**Cause:** A null argument was passed to an API call

**Action:** Ensure to invoke the API with non-null arguments

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05712: No group space name is provided**

**Cause:** Group space name is not provided

**Action:** Ensure to invoke the API with non-null arguments

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05713: No group space template name is provided**

**Cause:** Group space template name is not provided

**Action:** Ensure to invoke the API with non-null arguments

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05714: No group space user name is provided**

**Cause:** Group space user name is not provided

**Action:** Ensure to invoke the API with non-null arguments

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05715: No group space role name is provided**

**Cause:** Group space role name is not provided

**Action:** Ensure to invoke the API with non-null arguments

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05716: No group space custom attribute Name is provided**

**Cause:** Group space custom attribute name is not provided

**Action:** Ensure to invoke the API with non-null arguments

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05717: No group space custom attribute value is provided**

**Cause:** Group space custom attribute value is not provided

---

**Action:** Ensure to invoke the API with non-null arguments

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05718: Error while setting the new end point for the group space web services**

**Cause:** Group space web services client already has an endpoint {0}

**Action:** It cannot be overridden at the run-time. Try setting it in connections.xml and restarting the application

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05719: Spaces Web Service context is NULL**

**Cause:** Group space web service client is null

**Action:** You need to set the context for the client and then initialize it

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05720: An unexpected error occurred while instantiating group space web services client**

**Cause:** Unable to create an instance of GroupSpaceWSClient

**Action:** Please verify the context parameters or contact administrator

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05721: An error occurred when user {0} tried to accept invite for group space {2} with role {1}**

**Cause:** Failed to execute acceptance of group space invite

**Action:** Check the parameters being passed to the acceptInvite API or contact administrator

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05722: An error occurred when user {0} tried to reject the invite for group space {1}**

**Cause:** Failed to execute rejection of group space invite

**Action:** Check the parameters being passed to the rejectInvite API or contact administrator

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-05723: An error occurred while fetching the roles for Group Space {0}**

**Cause:** An error occurred while fetching the roles for Group Space{0}

**Action:** Contact administrator

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05724: An error occurred while inviting {0} members to Group Space {1}**

**Cause:** An error occurred while inviting the members to Group Space{1}

**Action:** Contact administrator

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05725: An error occurred while creating the Group Space Template{0} based on Group Space {1}**

**Cause:** An error occurred while creating the Group Space Template{0}

**Action:** Contact Administrator

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05726: An error occurred while fetching the roles for Group Space Template {0}**

**Cause:** An error occurred while fetching the roles for Group Space Template{0}

**Action:** Contact administrator

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05727: The Service ID {0}, is invalid.**

**Cause:** An error occurred while fetching the RSS Feed URL for the Service ID, {0}.

**Action:** Contact administrator

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05728: An error occurred while checking if a login user {0} is a member of Group Space {1}**

**Cause:** An error occurred while checking if a login user {1} is a member of Group Space {0}

**Action:** Contact administrator

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-05729: Deleting group space template {0} failed**

**Cause:** WebService API failed to execute deleting web service call.

**Action:** Check the web service parameters, make sure the configuration is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05730: Search on group spaces for search string {0} failed**

**Cause:** WebService API failed to execute search for group spaces.

**Action:** Check the web service parameters, make sure the configuration is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05731: Creation of role {0} failed in the group space {1}**

**Cause:** WebService API failed to execute create role for group spaces.

**Action:** Check the web service parameters, make sure the configuration is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05732: Dropping of role {0} failed in the group space {1}**

**Cause:** WebService API failed to execute drop role for group spaces.

**Action:** Check the web service parameters, make sure the configuration is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05733: Failed to get role information for identity {0} in group space {1}**

**Cause:** WebService API failed to get role information.

**Action:** Check the web service parameters, make sure the configuration is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05734: Failed to get member information for group space {0}**

**Cause:** WebService API failed to get member information.

**Action:** Check the web service parameters, make sure the configuration is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05735: Search on group space templates for search string {0} failed**

---

**Cause:** WebService API failed to execute search for group space template.  
**Action:** Check the web service parameters, make sure the configuration is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-05900: Unexpected error occurred while performing operation.**

**Cause:** Error occurred due to unknown cause

**Action:** Try the operation again or contact oracle support

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-06001: JCR session leak: leaked {0} sessions during {1} request to URI {2}.**

**Cause:** JCR sessions have not been returned to the pool after the request ended.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-06902: Incomplete repository connection, cannot login.**

**Cause:** The repository configuration details are not valid and a classpath issue prevented the loading of the underlying JCR repository.

**Action:** Verify that all the configuration parameters are correct and check the message from the underlying exception.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-06905: Credentials for connection {0} not found using External Application Identifier {1}.**

**Cause:** An attempt to fetch user credentials failed. User credentials may not have been provisioned or the external application configuration may be incorrect.

**Action:** Verify the external application configuration. If necessary, provision credentials for the user.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-06906: invalid credentials for connection {0} using External Application Identifier {1}**

**Cause:** An attempt to log in using the provisioned credentials failed. The user's credentials for this connection might have been changed or the external application configuration might have been incorrect.



---

**Action:** If the provisioned credentials for the given user are not valid, then those credentials must be provisioned again. It might also be necessary to verify the external application configuration.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-06908: JCR Repository creation failure.{0}**

**Cause:** A JCR repository instance could not be created from the parameters provided.

**Action:** Check the configuration parameters, and retry.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-06910: External Application Definition not found using External Application Identifier {0}**

**Cause:** An attempt to fetch user credentials failed. The External Application ID is incorrect.

**Action:** Verify that the External Application definition has been created for this connection.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-06911: There is no authenticated user and PUBLIC credentials are not supported for External Application ID {0}.**

**Cause:** An attempt to fetch credentials failed because there is not currently an authenticated user and the External Application ID does not support PUBLIC credentials.

**Action:** Use an External Application ID that supports PUBLIC credentials or authenticate so that no attempt to use PUBLIC credentials will occur.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-06912: There is no authenticated user and the PUBLIC credentials provisioned for External Application ID {0} are not valid.**

**Cause:** An attempt to login using PUBLIC credentials failed because the provisioned PUBLIC credentials are not valid.

**Action:** Contact your system administrator and inform them that the PUBLIC credentials need to be updated or authenticate so that no attempt to utilize the PUBLIC credentials will occur.

**Level:** 1

**Type:** WARNING

**Impact:** Other

---

**WCS-06913: The SHARED credentials provisioned for External Application ID {0} are not valid.**

**Cause:** An attempt to login using SHARED credentials failed because the provisioned SHARED credentials are not valid.

**Action:** Contact your system administrator and inform them that the SHARED credentials need to be updated.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-07001: severe internal error**

**Cause:** An irrecoverable internal error has occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-07002: error obtaining Documents service ADF configuration**

**Cause:** An error occurred while obtaining or interpreting the DocLib section of ADF configuration.

**Action:** Verify that the Documents service section of the ADF configuration is present, complete, and contains valid data.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-07003: error obtaining content repository connection**

**Cause:** A JNDI Naming Exception occurred while attempting to obtain the content repository connection.

**Action:** Verify that connections.xml contains a valid entry for the content repository connection.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-07004: content repository login failure**

**Cause:** The attempt to log on to the content repository failed.

**Action:** Make sure the credentials used are valid.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-07005: JCR error connecting to content repository**

**Cause:** A JCR repository exception (other than login) occurred.

**Action:** Use the associated JCR exception text to diagnose the problem.

---

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-07006: run-time error obtaining content repository**

**Cause:** An unexpected run-time exception occurred.

**Action:** Use the associated run-time exception text to diagnose the problem.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-07007: cannot list items in directory {0}**

**Cause:** An error occurred while trying to list the items in the specified folder.

**Action:** Make sure that the content repository connection is accessible and that the specified folder exists.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-07008: cannot get breadcrumbs for directory {0}**

**Cause:** An error occurred while trying to list the breadcrumbs items for the specified folder.

**Action:** Make sure that the content repository connection is accessible and that the specified folder exists.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-07013: No content repository connection with the name "{0}" can be found.**

**Cause:** A JNDI Name Not Found Exception occurred while attempting to obtain the content repository connection.

**Action:** Verify connections.xml contains an entry for the specified content repository connection name.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-07014: An attempt to log on to the content repository did not complete within the allotted time.**

**Cause:** The content repository may have been slowed by heavy loads or network congestion.

**Action:** Wait a while, and then retry. Optionally, ask the system administrator to allocate more resources for the content repository or to lengthen the timeout period.

**Level:** 1

**Type:** WARNING

---

**Impact:** Other

**WCS-07015: An attempt to log on to the content repository did not succeed because the Documents service is disabled.**

**Cause:** Login failed because the Documents service was disabled. Another login was still executing, exceeding its allotted timeout period.

**Action:** Wait a while, and then retry. Optionally, ask the system administrator to allocate more resources for the content repository or to lengthen the timeout period.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-07017: The target Content Server does not support the following query used to retrieve recent documents: {0}.**

**Cause:** Required components may not have been installed or properly configured.

**Action:** Check the Content Server installation guide for WebCenter for details on required components and their configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07078: The class method "{0}.{1}" cannot be called with a null or empty argument "{2}".**

**Cause:** The specified method call cannot be called with the specified argument with value of null.

**Action:** Ensure the specified argument has a non-null value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07079: Datasource type "{0}" was expected but found "{1}".**

**Cause:** The configured datasource type did not match the expected datasource type.

**Action:** Correct the presenter configuration to the expected datasource type.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07080: Error retrieving node(s).**

**Cause:** An error was encountered retrieving node(s).

**Action:** Please contact a system administrator for assistance.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07081: Error saving Content Presenter Configuration.**

---

**Cause:** An error was encountered saving the specified configuration document.

**Action:** Please contact a system administrator for assistance.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07082: Query expression must be a valid, non-empty expression.**

**Cause:** The specified query expression was invalid.

**Action:** Review the specified query expression and correct it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07083: The datasource type "{0}" requires "{1}" to be set.**

**Cause:** The specified datasource type is not consistent with the datasource state.

**Action:** Specific datasource types require different parameters to be set. Please resolve this situation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07084: Invalid datasource type "{0}". Valid datasource types:{1}.**

**Cause:** The specified datasource type was invalid.

**Action:** Correct the specified datasource type to one of the examples provided in the error message.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07085: The configuration {0} is required.**

**Cause:** You have not specified the mentioned configuration item.

**Action:** Make sure the mentioned configuration item is provided for this presenter instance.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07086: Both page size and maximum results are required and must be a positive integer (pageSize:{0}, maxResults:{1}).**

**Cause:** You have not specified the page size and maximum results.

**Action:** Correct the page size and maximum results.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WCS-07087: Error loading task-flow instance configuration**

**Cause:** An error occurred while loading the task-flow instance configuration.

**Action:** Check the base exception for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07088: Error saving task-flow instance configuration**

**Cause:** An error occurred while saving the task-flow instance configuration.

**Action:** Check the base exception for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07089: Unable to save presenter configuration data.**

**Cause:** An error occurred while saving the presenter configuration data.

**Action:** Check the base exception for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07090: Unable to retrieve presenter configuration data.**

**Cause:** An error occurred while retrieving the presenter configuration data.

**Action:** Check the base exception for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07091: Unable to retrieve presenter template data.**

**Cause:** An error occurred while retrieving the presenter template data.

**Action:** Check the base exception for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07092: An error occurred while running the query.**

**Cause:** An error occurred while previewing the query.

**Action:** Check the base exception for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07093: An error occurred while retrieving the node.**

**Cause:** An error occurred while retrieving the node.

---

**Action:** Check the base exception for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07094: Maximum results (current:{0}) must be an integer between {1} and {2}.**

**Cause:** The value you have specified for maximum results must inclusively be between the range specified.

**Action:** Correct the maximum results to be inclusively be between the specified range.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07095: An error occurred while running the query.**

**Cause:** A general repository exception has occurred.

**Action:** Check the base exception for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07101: Repository error: {0}**

**Cause:** An unexpected error occurred in the content repository.

**Action:** Check the base exception and repository's log for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-07102: Repository error**

**Cause:** An unexpected error occurred in the content repository.

**Action:** Check the base exception and repository's log for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-07103: Unsupported repository operation**

**Cause:** The Documents service tried to invoke an operation that is not supported by the underlying document repository.

**Action:** Avoid this operation with this repository.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-07201: Oracle Content Server error: {0}**

**Cause:** An unexpected error occurred in the Oracle Content Server.

---

**Action:** Check the Oracle Content Server logs for details on this exception.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-07301: Repository error: {0}**

**Cause:** An unexpected error occurred in the content repository.

**Action:** Check the base exception and repository's log for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-07302: Repository error**

**Cause:** An unexpected error occurred in the content repository.

**Action:** Check the base exception and repository's log for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-07303: Unsupported repository operation**

**Cause:** The Documents service tried to invoke an operation that is not supported by the underlying document repository.

**Action:** Avoid this operation with this repository.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-07401: Unexpected exception: {0}**

**Cause:** An unexpected exception occurred.

**Action:** Check the server logs for details on this exception.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-07402: Unexpected error**

**Cause:** An unexpected error occurred.

**Action:** Check the server logs for details on this error.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07403: Unsupported resource type**

**Cause:** The Documents service tried to perform an operation on a resource but failed to do so because the resource type was not recognized.



---

**Action:** Avoid this operation with this particular type of resource.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-07404: Renaming the root folder is not allowed.**

**Cause:** An attempt was made to rename the root folder.

**Action:** Avoid the rename operation with the root folder.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-07405: Error reading the document's content.**

**Cause:** The document's content could not be accessed.

**Action:** Verify that the document is available.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-07406: Error performing paste.**

**Cause:** An error prevented the items from being pasted at the destination folder.

**Action:** Verify that the destination folder still exists, is writable, and no items with the same names exist there.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07407: When searching between dates, if the dates are not specified in ascending order, the search may not return any results.**

**Cause:** The begin and end dates have been specified in the wrong order.

**Action:** Specify the dates in ascending order.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-07408: Operation not allowed on Public folders.**

**Cause:** An attempt has been made to perform an illegal operation on a Public folder.

**Action:** Do not select a Public folder when performing operations such as delete and rename. If performing a copy or move operation then select item(s) inside the Public folder, not the Public folder itself.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WCS-07501: There is no role matching the given ID: {0}.**

**Cause:** The application attempted to look up a service role with an invalid role ID.

**Action:** Ensure that your application uses a valid service role ID.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07502: Cannot grant role {0} for scope {1}.**

**Cause:** Could not grant the super administrator role to the scope. The super administrator role can only be granted to the default scope; other roles must be granted on a group space scope.

**Action:** Verify that the role mapping is correctly defined.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07503: Cannot log on to the content repository.**

**Cause:** The username and password used for the current login were not correct.

**Action:** Check the username and password.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-07601: Unable to read document metadata ("{0}", "{1}").**

**Cause:** Generally caused by a malformed xml document.

**Action:** Check the specified xml document for errors.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07602: Document metadata ("{0}", "{1}") is expected to be of type "{2}", but found "{3}".**

**Cause:** Generally caused by a malformed xml document with an incorrect namespace.

**Action:** Check the specified xml document and make sure the xmlns attribute is set to "http://xmlns.oracle.com/webcenter/content/templates/registry".

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07603: No content list template or content template found in registry("{0}", "{1}").**

**Cause:** Generally caused by an empty display template descriptor.

**Action:** Check the specified xml document and make sure that either content-templates or content-list-templates are defined.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07604: Default template view named "{0}" not found for content type "{1}".**

**Cause:** A content type has been configured in the template registry with a default template that has not been found.

**Action:** Check the specified xml document and make sure a template view exists with the id of the defaultView specified on the content type.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07605: There are duplicate template categories with id "{0}".**

**Cause:** There are duplicate template categories that are defined with the specified id.

**Action:** Check the template registry document and make sure and change the name of the specified template category.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07606: There are duplicate content types by name "{0}".**

**Cause:** There are duplicate content types that are defined with the specified name.

**Action:** Check the template registry document and make sure and change the name of the specified content type.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07607: There are duplicate content repositories by name "{0}" and type "{1}".**

**Cause:** There are duplicate content repositories that are defined with the specified name.

**Action:** Check the template registry document and make sure and change the name of the specified content repository.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07608: There are duplicate template views by id "{0}".**

**Cause:** There are duplicate template views that are defined with the specified id.

**Action:** Check the template registry document and make sure and change the id of the specified template view.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-07609: The class method "{0}.{1}" cannot be called with a null argument "{2}".**

**Cause:** The specified method call cannot be called with the specified argument with value of null.

**Action:** Ensure the specified argument has a non-null value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07610: Unable to locate resource key "{0}" in bundle "{1}".**

**Cause:** The display template registry is configured with a resource bundle and key that is unable to be found.

**Action:** Check the specified resource bundle and ensure that the specified key exists.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-07611: No template category defined by id "{0}".**

**Cause:** The display template registry does not contain a category configuration by the specified id.

**Action:** Add the specified category id to the template registry.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-07612: No template view defined by id "{0}".**

**Cause:** The display template registry does not contain a template configuration by the specified id.

**Action:** Add the specified template id to the template registry.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-07613: No template registry found in application.**

**Cause:** The display template registry does not exist or cannot be found.

**Action:** Check application configuration and ensure registry is properly configured.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-07614: Default template view named "{0}" not found in template category "{1}".**

**Cause:** A category has been configured in the template registry with a default template view that has not been found.

---

**Action:** Check the specified xml document and make sure a template view exists with the id of the defaultView specified on the category.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07615: Default category named "{0}" not found in the registry.**

**Cause:** A default category has been configured in the template registry that has not been found.

**Action:** Check the specified xml document and make sure a the default category has been defined.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07616: No template view defined by id "{0}" and category "{1}".**

**Cause:** The display template registry does not contain a template configuration by the specified category and view.

**Action:** Add the specified template id to the template registry.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-07617: A general display template error has occurred.**

**Cause:** An unexpected exception has occurred processing the display template registry.

**Action:** Review the original stacktrace cause for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07701: severe internal error while getting the template view ID**

**Cause:** An irrecoverable internal error has occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-07702: Error while getting the template view ID**

**Cause:** An error occurred while determining the template for a node.

**Action:** Check the underlying exception.

**Level:** 1

**Type:** WARNING

**Impact:** Other

---

**WCS-07703: No request dispatcher for template viewID {0} located at {1}**

**Cause:** An error occurred while trying to dispatch the request to the template. The target template may not exist.

**Action:** Check that the target template exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07704: Error processing the display template include for template viewID {0} located at {1}**

**Cause:** An error occurred while processing the template include. This may result from a syntax or logic error in the template code.

**Action:** Check the underlying exception for the details of the error.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07801: Cannot seed the WebCenter data into the content repository.**

**Cause:** An error occurred while seeding data for the Documents service in the content repository.

**Action:** Check the underlying exception and content repository log for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07802: Cannot find the adf-config.xml file.**

**Cause:** Could not find an adf-config.xml document in the classpath.

**Action:** To enable the Documents service in WebCenter, ensure adf-config.xml and connections.xml containing Documents service information are on the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07803: Cannot open a connection to the Oracle Content Server.**

**Cause:** The application failed to open a connection to the Oracle Content Server.

**Action:** Check that the Oracle Content Server connection is properly configured and that the server is available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07804: Cannot create the Security Group, {0}, in the Oracle Content Server.**

**Cause:** A Content Server error occurred while executing the operation.

**Action:** Check the underlying exception and Oracle Content Server log for more information.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07805: Cannot create the seeded role, {0}, in the Oracle Content Server.**

**Cause:** A Content Server error occurred while executing the operation.

**Action:** Check the underlying exception and Oracle Content Server log for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07806: Cannot create the folder, {0}, in the folder, {1}, in the Oracle Content Server.**

**Cause:** A Content Server error occurred while executing the operation.

**Action:** Check the underlying exception and Oracle Content Server log for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07807: Cannot rename the folder, {0}, to {1}, in the Oracle Content Server.**

**Cause:** A Content Server error occurred while executing the operation.

**Action:** Check the underlying exception and Oracle Content Server log for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07808: Cannot delete the folder, {0}, in the Oracle Content Server.**

**Cause:** A Content Server error occurred while executing the operation.

**Action:** Check the underlying exception and Oracle Content Server log for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07809: Cannot get folder with the path, {0}, from the Oracle Content Server.**

**Cause:** A Content Server error occurred while executing the operation.

**Action:** Check the underlying exception and Oracle Content Server log for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07810: Error obtaining the content repository connection "{0}".**

---

**Cause:** A JNDI Naming Exception occurred while attempting to obtain the content repository connection.

**Action:** Verify that connections.xml contains a valid content repository connection.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07811: Unsupported repository connection "{0}" for the Documents service.**

**Cause:** The specified content repository is not currently supported for Documents service WebCenter Spaces integration. The supported content repository types is Oracle Content Server.

**Action:** Verify that adf-config.xml and connections.xml contain a valid entry for the Documents service repository.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07812: Cannot remove permissions, {0}, for user/group, {1}, to the account for the folder, {2}.**

**Cause:** The application failed to remove permissions for the user/group on the folder.

**Action:** Check that the permissions and user/group are valid and that the folder exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07813: Cannot grant permissions, {0}, for user, {1}, to the account for the folder, {2}.**

**Cause:** The application failed to grant permissions for the user on the folder.

**Action:** Check that the permissions and user are valid and that the folder exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07814: Error while removing an account from all users credentials.**

**Cause:** A Content Server error occurred while executing the operation.

**Action:** Check the underlying exception and Oracle Content Server log for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07816: Unable to seed the WebCenter data in the Oracle Content Server repository.**



---

**Cause:** A Content Server error occurred while seeding the WebCenter data in the repository.

**Action:** Check the underlying exception and Oracle Content Server log for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07817: Unable to seed the Personal Folder data in the Oracle Content Server repository.**

**Cause:** A Content Server error occurred while seeding the Personal Folder data in the repository.

**Action:** Check the underlying exception and Oracle Content Server log for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07818: Cannot find the WebCenter administrators to seed in the Document Library repository.**

**Cause:** The application failed to determine the list of WebCenter administrators.

**Action:** Check the underlying exception for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07819: Cannot release the session pool.**

**Cause:** Failed to release the session pool for the content repository administrative connection.

**Action:** Check the underlying exception for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07821: Error while calling the EC\_SET\_PROPERTY service with dECPropType = {0}, dECPropKey = {1}, dECPropSubKey = {2}, dECPropValue = {3}.**

**Cause:** A call to the Oracle Content Server EC\_SET\_PROPERTY service during repository setup failed to complete.

**Action:** Check the underlying exception and Oracle Content Server log for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07823: Cannot grant the account, {0}, to all users.**

**Cause:** An error occurred while trying to grant the account to all users.

---

**Action:** Check the underlying exception and Oracle Content Server log for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07824: Unable to get the admin session to the Oracle Content Server repository.**

**Cause:** An error occurred while trying to obtain an admin session to the Oracle Content Server repository.

**Action:** Check the underlying exception and Oracle Content Server log for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07825: Cannot remove role, {0}, for user/group, {1}.**

**Cause:** The application failed to remove the specified role from the user/group.

**Action:** Check the role and user/group are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07826: Cannot remove role {0} and permissions, {1}, to the account for the folder, {2} for the user/group {3}.**

**Cause:** The application failed to remove the role and permissions on the folder for the user/group.

**Action:** Check that the permissions and user/group are valid and that the folder exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07827: Cannot add role, {0}, for user/group, {1}.**

**Cause:** The application failed to add the specified role to the user/group.

**Action:** Check the role and user/group are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07828: Cannot add role {0} and permissions, {1}, to the account for the folder, {2} for the user/group {3}.**

**Cause:** The application failed to add the role and permissions on the folder for the user/group.

**Action:** Check that the permissions and user/group are valid and that the folder exists.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07829: Cannot update the account for the group space {0}, with permission, {1}, for all users.**

**Cause:** An error occurred while trying to update the group space account for all users.

**Action:** Check the underlying exception and Oracle Content Server log for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07830: Cannot set default attributes, {0}, for the key, {1}**

**Cause:** An error occurred while trying to set default attributes for the specified key.

**Action:** Check the underlying exception and Oracle Content Server log for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07831: Cannot delete default attributes for the key, {0}.**

**Cause:** An error occurred while trying to delete default attributes for the specified key.

**Action:** Check the underlying exception and Oracle Content Server log for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07832: Cannot determine account and permission from the default attributes for the group space, {0}.**

**Cause:** An error occurred while trying to determine the account and permission from the default attributes for the group space. The default attributes are not in the correct format.

**Action:** Check the underlying exception and Oracle Content Server log for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07833: The Java Object Cache is not available.**

**Cause:** An error occurred while trying to retrieve the cache.

**Action:** Check the underlying exception for more information.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07834: A Java Object Cache operation timed out. Distributed caches may be inconsistent.**

**Cause:** A cache operation timed out.

**Action:** Check the underlying exception for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07835: Java Object Cache, Put operation failed.**

**Cause:** A cache put operation failed.

**Action:** Check the underlying exception for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07836: Java Object Cache, Destroy operation failed.**

**Cause:** A cache destroy operation failed.

**Action:** Check the underlying exception for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07837: Java Object Cache, Get operation failed.**

**Cause:** A cache get operation failed.

**Action:** Check the underlying exception for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07838: Java Object Cache, release ownership failed.**

**Cause:** A cache unlock operation on a cached object failed.

**Action:** Check the underlying exception for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07839: Invalid document service ADF configuration.**

**Cause:** The documents services configuration in adf-config.xml is invalid.

**Action:** Verify that the documents services configuration in adf-config.xml conforms to the documents service configuration data schema.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07840: Cannot get folder with the GUID, {0}, from the Oracle Content Server.**

**Cause:** A Content Server error occurred while executing the operation.

**Action:** Check the underlying exception and Oracle Content Server log for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07850: Failed to destroy Java Object Cache region, {0}.**

**Cause:** An error occurred while trying to destroy the Doclib Java Object Cache region.

**Action:** Check the underlying exception for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-07857: Cannot get the version for the {0} component from the Oracle Content Server.**

**Cause:** A Content Server error occurred while executing the operation.

**Action:** Check the underlying exception and Oracle Content Server log for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-08001: Supplied class {0} is not an instance of {1}.**

**Cause:** Forum service adapter details were not configured properly in the adf-config.xml file or the adapter implementation class was not correct.

**Action:** Check that the adapter class name in the adf-config file is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-08002: Not able to invoke constructor of class {0} through Constructor.newInstance() call.**

**Cause:** Application tried to instantiate a class through Constructor.newInstance().

**Action:** Check that the adapter class name in the adf-config file is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-08003: Not able to find the method "{0}" in the class "{1}".**

---

**Cause:** Matching constructor was not found in the adapter implementation class.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-08004: Not able to resolve the name {0}**

**Cause:** Not able to acquire Context to look up.

**Action:** Check for JNDI configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-08005: User "{0}" is not authorized.**

**Cause:** Contact your administrator for access to discussions forum.

**Action:** Provide valid user credentials, or check if user exists or has appropriate permissions.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-08006: User "{0}" not logged on.**

**Cause:** User might not have logged on to the system.

**Action:** Try logging on using correct user credentials.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-08007: User "{0}" not found**

**Cause:** User might not have been created, or user might have been deleted from the back-end application.

**Action:** Contact your administrator or try different user credentials.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-08008: Service "{0}" is not a valid service or it is not supported by the "{1}" adapter implementation.**

**Cause:** Adapter implementation does not recognize this service type.

**Action:** Read the documentation for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Other

---

**WCS-08009: Discussion forum Category with name "{0}" already exists.**

**Cause:** Category with the given name already exists.

**Action:** Try with a different category name.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-08010: Category not found.**

**Cause:** Category does not exists or user is not authorized to access it.

**Action:** Provide a valid category ID.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-08011: Discussion forum object Forum with name "{0}" already exists.**

**Cause:** Discussion forum object Forum with the given name already exists.

**Action:** Try with a different forum name.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-08012: No forums were found.**

**Cause:** Forum does not exists or user is not authorized to access it.

**Action:** Provide a valid forum ID.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-08013: Topic not found.**

**Cause:** Topic does not exists or user is not authorized to access it.

**Action:** Provide a valid topic ID.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-08014: Message not found.**

**Cause:** Message does not exists or user is not authorized to access it.

**Action:** Provide a valid message ID.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-08015: There is a problem with the supplied attachments.**

---

**Cause:** Possible causes: attachment was larger than expected, it was not readable or available, or it was not a supported mime type.

**Action:** Try with a different attachment or contact your system administrator.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-08016: Unable to look up the forum connection with name "{0}".**

**Cause:** Either the forum connection name is not valid or corresponding connection details are deleted from the connection store.

**Action:** Check the default connection name in adf-config and connection details in connection store for discussion forum service or contact your system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-08017: Ambiguous forum connection definitions found in the connection store.**

**Cause:** More than 1 connection type found for discussion forum service. Unable to decide which one to use.

**Action:** Configure the appropriate connection name as the default connection to use from the management console or contact your system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-08018: Discussion forum object Message with subject "{0}" is prevented from being posted.**

**Cause:** Discussion forum object Message is rejected because of any one of the following reasons: 1) blocking a set of users from posting, 2) preventing a user from posting more than once every X seconds, 3) rejecting any messages that contain profanity from the back-end application.

**Action:** If you are authorized to post messages and your text has valid language, then try again after some time.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-08019: Host address "{0}" configured in connection store is not correct.**

**Cause:** IP address of the host configured in connection store could not be determined.

**Action:** Configure the correct host name in connection store or contact your system administrator.

**Level:** 1

**Type:** ERROR



---

**Impact:** Other

**WCS-08020: Unable to connect to discussion server.**

**Cause:** Possible reasons: The IP address of the host configured in the connection store could not be determined, or the connection was refused by the host.

**Action:** Configure the correct host name in connection store or contact your system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-08021: Forum connection details are not available in the connection store.**

**Cause:** Forum connection details were not available in the connection store.

**Action:** Configure discussion forum service connection details in connection store or contact your system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-08022: Unable to create discussion forum object Forum with name "{0}".**

**Cause:** Unable to create discussion forum object Forum with the supplied name and description.

**Action:** Contact your administrator.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-08023: Not able to reach service endpoint port type due to {0}.**

**Cause:** Service end point is not reachable.

**Action:** Contact your administrator.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-08024: Input parameter value "{0}" supplied is invalid.**

**Cause:** Invalid input parameter value is supplied.

**Action:** Provide valid values for the input parameters.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-08025: You do not have permission to see forums for this group space.**

**Cause:** User is not authorized to access the forum.

**Action:** Contact your administrator.

**Level:** 1

---

Type: WARNING

Impact: Other

**WCS-08026: You do not have permission to see recent topics for this group space.**

**Cause:** User is not authorized to access the recent topics.

**Action:** Contact your administrator.

Level: 1

Type: WARNING

Impact: Other

**WCS-08027: You do not have permission to see popular topics for this group space.**

**Cause:** User is not authorized to access the popular topics.

**Action:** Contact your administrator.

Level: 1

Type: WARNING

Impact: Other

**WCS-08201: Not able to create forum configuration file for community "{0}" due to : {1}.**

**Cause:** Possible failure creating the category or forum, or an issue with the MDS write operation.

**Action:** Contact your system administrator or read the discussion forum service configuration documentation for more details.

Level: 1

Type: ERROR

Impact: Other

**WCS-08202: Failed to flush changes into preference store due to {0}.**

**Cause:** Possible failure in the backing store, or a failure to contact the backing store.

**Action:** Contact system administrator

Level: 1

Type: ERROR

Impact: Other

**WCS-09001: The IMAP host cannot be null or an empty string.**

**Cause:** The IMAP server host address was not specified.

**Action:** Configure Mail Service connection.

Level: 1

Type: ERROR

Impact: Other

**WCS-09002: The SMTP host cannot be null or an empty string.**

**Cause:** The SMTP server host address was not specified.

**Action:** Configure Mail Service connection.

---

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09003: Anonymous user access is not permitted on the mail service. Users must log on to the application.**

**Cause:** User was not logged on to the application. ADF security context was not set to authenticated user.

**Action:** Log on to the application using the ADF authentication mechanism.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09004: User credentials not found in the credential store for user "{0}" with external application ID: {1}.**

**Cause:** Mapped user credentials for the current logged on user were not found in the credential store.

**Action:** Supply valid credentials.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09005: Multiple connection definitions found for mail service.**

**Cause:** Multiple connection definitions were defined in the registry; could not identify the default connection to use.

**Action:** Specify the default connection to be used in adf-config.xml. For more details, refer to the Mail Service documentation for creating connections.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09006: Lookup for connection "{0}" failed.**

**Cause:** Failed to get the JNDI context, or the mail connection with the given name was not available.

**Action:** Supply proper connection name, and ensure that the entry exists in the connection repository.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-09007: ADF connections context could not be acquired. Failed to find mail connection.**

**Cause:** Failed to get the JNDI context for the connection repository.

**Action:** ADF connection context details were missing from the adf-config.xml file. For more information, refer to the ADF Developer's Guide.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WCS-09008: Failed to create mail session due to: {0}**

**Cause:** Unexpected failure: either the IMAP/SMTP server did not respond, it failed to understand the request, or it was not configured properly.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-09009: Failed to connect to the mail server. Connection timed out.**

**Cause:** Could not connect to the mail server in the given time.

**Action:** Confirm that the IMAP/SMTP servers are running or increase the timeout value.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09010: Failed to read messages from the folder "{0}". Further information: {1}**

**Cause:** Either the IMAP folder had issues or the search term was not supported by the server.

**Action:** Contact your system administrator to check the issues in the log file.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09011: Failed to get message with ID "{0}" from the folder "{1}". Further information: {2}.**

**Cause:** Either the IMAP folder had issues or the search term was not supported by the server.

**Action:** Contact your system administrator to check the issues in the log file.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09012: Failed to send the message with subject "{0}". Further information: {1}**

**Cause:** Either the SMTP server did not respond or the message was corrupted.

**Action:** Contact your system administrator to check the issues in the log file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-09013: Message with ID "{0}" has been permanently removed from the "{1}" folder.**

---

**Cause:** Either this message did not exist on the IMAP folder or it was been deleted via expunge on the folder.

**Action:** The IMAP folder has been expunged to permanently delete all messages. The message cannot be recovered.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09014: Unable to find the "{0}" folder.**

**Cause:** Either the folder with this name did not exist on the IMAP server or the mail server did not support folders.

**Action:** Ensure that the folder with the given name exists and that the IMAP server is properly configured.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09015: Failed to perform the {0} operation due to: {1}.**

**Cause:** Either the mail server was down or it did not support this operation.

**Action:** Ensure that the IMAP and SMTP servers are properly configured and available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-09016: Logon failed: unknown user name or incorrect password**

**Cause:** The user credentials acquired from the credential store were incorrect.

**Action:** Ensure that the user credentials supplied for logon are correct.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09017: Could not make an attachment: not a valid body part for creating an attachment.**

**Cause:** Either the body part was not recognized, it could not be attached to the message, or the body part could not be processed.

**Action:** Contact your system Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-09018: No recipients for the mail specified.**

**Cause:** No recipients for the mail specified.

**Action:** At least one recipient must be specified for the mail to be delivered.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WCS-09019: No mail connection found.**

**Cause:** No mail connection was specified.

**Action:** The mail connection is not available in the connection repository. Ensure that a connection to the mail server is defined.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-09020: Connection to the server failed.**

**Cause:** Connection to the server failed: either the host or port information was wrong or the server was down.

**Action:** Check the mail server connection details and ensure that the mail server is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-09021: User name to connect to the mail server for Email Gateway is not supplied.**

**Cause:** Connection to the server failed: mail user account was not complete.

**Action:** User account details are required to connect to the mail server.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-09022: User password to connect to the mail server for Email Gateway is not supplied.**

**Cause:** Connection to the server failed: mail user account is not complete.

**Action:** User account details are required to connect to the mail server.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-09023: Cannot attach file. Either the file exceeds the maximum allowed file size or it is empty(zero bytes). Attached files must be less than 2 MB.**

**Cause:** Either the attachment size is 0(zero) or greater than 2 MB.

**Action:** Attach a file within in the expected size limit.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WCS-09025: Message delivery failure: The message could not be sent because connecting to the SMTP mail server failed. The server may be unavailable. If the problem persists, report the error to your administrator.**

**Cause:** Connection to the server failed: either the host or port information was wrong or the server was down.

**Action:** Check the mail server connection details and ensure that the mail server is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-09026: Error processing the message.**

**Cause:** The message might have been sent with improper encoding.

**Action:** Contact system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-09201: Distribution list "{0}" already exists.**

**Cause:** A distribution list with the supplied name already exists.

**Action:** Create the distribution list with a different name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-09202: Distribution list "{0}" is not available.**

**Cause:** A distribution list with the supplied name does not exist.

**Action:** Verify the supplied name and ensure that the list exists on the mail server.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-09203: Mandatory connection property "{0}" missing from the directory connection.**

**Cause:** The mandatory connection property required to establish directory connection was not supplied.

**Action:** Verify the supplied directory connection details, and ensure that the required details are supplied.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-09204: Filter criteria not defined for the directory search: {0}.**

**Cause:** Filter criteria was not defined for the directory search.

**Action:** Search criteria should contain filter details.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-09205: Incorrect format for the schema attribute. Value retrieved is: {0}.**

**Cause:** The schema was not specified properly.

**Action:** Check the base DN for the schema details and supply the complete base DN.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-09214: Failed to acquire the initial directory context for name: {0}, due to : {1}**

**Cause:** Failed to acquire the connection either the connection details are wrong or server is not reachable.

**Action:** Ensure proper configuration is provided or Contact your administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-09215: Unable to create the distribution list: {0}, Mandatory attributes missing.**

**Further information:** {1}

**Cause:** Mandatory attributes to create a group are missing.

**Action:** Contact System Administrator

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-09216: Unexpected error occurred. Further info: {0}**

**Cause:** Unexpected error occurred contact system administrator.

**Action:** Contact Oracle Support

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-09217: Unable to lookup the context name: {0}, due to : {1}**

**Cause:** Unable to find the context.

**Action:** Contact System Administrator

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09218: Unable to destroy the context name: {0}, due to : {1}**

**Cause:** Either context does not exists or its not a proper context name.

**Action:** Contact System Administrator



---

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09219: Unable to modify attributes for the context name: {0}, due to : {1}**

**Cause:** Either context does not exists or its not a proper context name.

**Action:** Contact System Administrator

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09220: Unable to find the attribute: {0} under context {1}, due to {2}**

**Cause:** Required attribute not found in the context object.

**Action:** Ensure the required attribute is available in the context object.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09251: Failed to make attachment, due to: {0}.**

**Cause:** Either the file size was too large or the selected file was not readable. Check the server settings.

**Action:** Ensure that the file is available and readable. Also ensure that the file is not too large. If the problem persists, then contact your system administrator.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09252: Failed to remove attachment due to: {0}.**

**Cause:** Either this attachment did not exist or it failed to read the message. See the error log for more details.

**Action:** Contact your system administrator.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09253: Failed to send message, due to: {0}.**

**Cause:** Either the mail session was expired or the user was not logged in.

**Action:** Contact your system Administrator.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09254: Failed to read attachments, due to: {0}.**

**Cause:** Either the mail session is expired or the user is not logged-in.

**Action:** Contact your system Administrator.

---

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09255: External application ID not defined.**

**Cause:** The required configuration parameter External Application ID was not found.

**Action:** Contact your system Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-09256: This message has been deleted.**

**Cause:** This message had been deleted.

**Action:** Only non-deleted mails can be viewed.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09257: No compose message object found.**

**Cause:** User may not be in the compose mode or the state is lost.

**Action:** Ensure the user is in compose message view.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09258: Unable to find the attachment table component.**

**Cause:** Unable to find the table component in the current view.

**Action:** Ensure the table component id name is not changed.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09259: Unable to find the backing bean by name {0}.**

**Cause:** Either the backing bean is removed or the name is changed.

**Action:** Ensure the backing bean names are intact.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09501: An unexpected error occurred.**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

---

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-09502: Supplied class {0} is not an instance of {1}.**

**Cause:** Announcement service adapter details might not have been configured properly in the adf-config.xml file or adapter implementation class was not proper.

**Action:** Check that the adapter class name in the adf-config file is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-09503: Not able to invoke constructor of class {0} through Constructor.newInstance() call.**

**Cause:** Application is trying to instantiate a class through Constructor.newInstance().

**Action:** Check that the adapter class name in the adf-config file is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-09504: Not able to find the method "{0}" in the class "{1}".**

**Cause:** Matching constructor might not be found the adapter implementation class.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-09505: User "{0}" is not authorized.**

**Cause:** Contact your administrator for access to announcements.

**Action:** Provide valid user credentials, or check if user exists or has appropriate permissions.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09506: User "{0}" not logged on.**

**Cause:** User might not have logged on to the system.

**Action:** Try logging on using correct user credentials.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09507: User "{0}" is not found.**

**Cause:** User might not have been created, or user might have been deleted from the back-end application.

---

**Action:** Contact your administrator or try different user credentials.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09508: Announcement configuration file for community "{0}" not found or details such as category ID and announcement ID are not available.**

**Cause:** There was a failure in creating the announcement configuration or an issue with the MDS read or write operation.

**Action:** Contact your system administrator or read the announcement service configuration documentation for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09509: Announcement not found.**

**Cause:** Announcement object with the supplied announcement ID was not available or it was not accessible.

**Action:** Provide a valid announcement ID.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09510: Announcement parent not found.**

**Cause:** Announcement parent object with the supplied ID was not available or it was not accessible.

**Action:** Provide a valid accessible parent ID.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09511: Announcement parent not found.**

**Cause:** Announcement parent object is not accessible from discussion forum.

**Action:** Check if discussion service is configured properly.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09512: Unable to lookup the announcement connection with name "{0}".**

**Cause:** Either the announcement connection name is not valid or corresponding connection details are deleted from the connection store.

**Action:** Check the default connection name in adf-config for discussion announcement service or contact your system administrator.

**Level:** 1

**Type:** WARNING

---

**Impact:** Other

**WCS-09513: Ambiguous announcement connection definitions found in the connection store.**

**Cause:** More than 1 connection type found for discussion announcement service. Unable to decide which one to use.

**Action:** Configure the appropriate connection name as the default connection to use from the management console or contact your system administrator.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09516: Announcement service configuration not found**

**Cause:** service configuration details are missing

**Action:** Ensure service config details are either loadable from classpath or from adf-config.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09517: Announcement service configuration not correct.**

**Cause:** service configuration details are not provided as expected.

**Action:** Correct the service configuration details.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09518: Host address "{0}" configured in connection store is not correct.**

**Cause:** IP address of the host configured in connection store could not be determined.

**Action:** Configure the correct host name in connection store or contact your system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-09519: Not able to log on to the back-end system with host address "{0}".**

**Cause:** Possible reasons: The IP address of the host configured in the connection store could not be determined, or the connection was refused by the host.

**Action:** Configure the correct host name in connection store or contact your system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-09520: Expiry date cannot be earlier than start date.**

---

**Cause:** Expiry date is specified to be earlier than start date.

**Action:** Specify expiry date to be later than start date.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-09601: Not able to create announcement configuration file for community {0} due to : {1}.**

**Cause:** Possible failure creating category or announcement or an issue with the MDS write operation.

**Action:** Contact your system administrator or read the announcement service configuration documentation for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-09602: Failed to flush changes into preference store due to {0}.**

**Cause:** Possible failure in the backing store, or failure to contact the backing store.

**Action:** Contact system administrator

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-11001: Error on content write: {0}**

**Cause:** The content write operation failed for the given reason.

**Action:** Investigate the reason for the failure.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-11002: Internal server error: {0}**

**Cause:** An unexpected internal error has occurred.

**Action:** Contact your Oracle Support representative.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-11003: Invalid Request**

**Cause:** The client has submitted an invalid HTTP request.

**Action:** Re-send the corrected request.

**Level:** 1

**Type:** WARNING

**Impact:** Other

---

**WCS-11004: Path not found: {0}**

**Cause:** The requested path has not been found on the server.

**Action:** Correct the path on the client and re-send the request.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-11005: Not an ISO8601 date: {0}**

**Cause:** The client supplied a date which is not in ISO8601 format.

**Action:** Correct the date format on the client and re-send the request.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-11006: Not an HTTP date: {0}**

**Cause:** The client supplied a date which is not in HTTP date format.

**Action:** Correct the date format on the client and re-send the request.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-11007: Namespace not supported: {0}**

**Cause:** The repository does not support the given namespace.

**Action:** Specify a valid namespace.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-11008: Bad request**

**Cause:** The client submitted a request that could not be understood by the server.

**Action:** Correct the syntax and resubmit the request.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-11009: Not modified**

**Cause:** The client has performed a conditional GET request, access is allowed but the document has not changed.

**Action:** No action required as resource has not been modified and hence it is not returned.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WCS-11010: Not acceptable**

**Cause:** The requested resource could not generate an entity with an acceptable media-type for the client.

**Action:** If applicable, resubmit the request with a broader acceptance criteria.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-11011: Precondition failed**

**Cause:** A request precondition has failed.

**Action:** If applicable, resubmit the request with different preconditions.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-11012: The Java virtual machine does not support the UTF-8 character set.**

**Cause:** The UTF-8 character set is not supported by the Java virtual machine.

**Action:** Contact your Oracle Support Representative.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-11013: No DAV dead property name matches the JCR property name {0}.**

**Cause:** A unexpected JCR property name has been found that does not correspond to a DAV dead property name.

**Action:** Contact your Oracle Support Representative.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-11014: Cannot close the servlet output stream.**

**Cause:** There was an error closing the servlet output stream.

**Action:** Review the server logs for possible cause of failure.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-11015: Cannot close content input stream.**

**Cause:** There was an error closing the content input stream.

**Action:** Review the server logs for possible cause of failure.

**Level:** 1

**Type:** ERROR

**Impact:** Other



---

**WCS-11016: Invalid resource name: {0}**

**Cause:** The given name is not a valid resource name.

**Action:** The client should resubmit the request with a corrected URL.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-11017: Invalid resource name; illegal escape sequence in path: {0}**

**Cause:** The given name was not a valid resource name as it contains an illegal escape sequence.

**Action:** The client should resubmit the request with a corrected URL.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-11018: Forbidden request method: {0}**

**Cause:** The requested HTTP method was not completed as the server forbids the execution of this type of method.

**Action:** Compatible clients should not use the specified HTTP method.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-11019: Folder listing is disabled.**

**Cause:** Folder listing has been disabled.

**Action:** Folder listing must be explicitly enabled in the application's web.xml.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-12001: No handlers could be found for services with IDs: {0}.**

**Cause:** Handlers enable services to manage their data and metadata in the manner best suited to each service. Handlers that were recorded by the system during export were not available on import.

**Action:** Ensure that the specified services are included and configured in the application and restart the import process.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12002: The handler found in the classpath at run time cannot process the data or metadata of the archive: {0}.**

**Cause:** Handlers enable services to manage their data and metadata in the manner best suited to each service. The version of the handler used during import was not compatible with the version of the handler used while creating the data or metadata on export.

---

**Action:** Include compatible versions of handlers in the application and restart the import process.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12003: The required handlers are not found: {0}.**

**Cause:** Handlers enable services to manage their data and metadata in the manner best suited to each service. Not all handlers that were used while creating this archive could be found during the import.

**Action:** Ensure that the specified services are included and configured in the application and restart the import process.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12004: Unable to retrieve the JAXB bean for the export/import document in MDS.**

**Cause:** An error occurred in the MDS configuration of the application.

**Action:** Check the MDS configuration files of the application.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12006: The export archive does not contain any scope metadata.**

**Cause:** An error occurred during the export process, or the exported archive was damaged.

**Action:** Reattempt import with a different export file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12007: Scope with name {0} already exists in the import destination and it does not match with the scope being imported.**

**Cause:** A scope with the specified name already exists for the current application instance. This caused a conflict between the source and target instances.

**Action:** Delete the scope from the current application instance and reattempt the import.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12009: The Lifecycle Manager MBean cannot be deregistered.**

**Cause:** There are numerous possible reasons for this failure.

**Action:** For information, review other messages in the log file and the reported exception stacks.

---

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-12010: The Lifecycle Manager MBean cannot be created and registered. This problem will not prevent the application from running. However, the Lifecycle Manager will be unavailable.**

**Cause:** There are numerous possible reasons for this failure.

**Action:** For information, review other messages in the log file and the reported exception stacks.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-12012: Information related to run time MBeans cannot be saved in the ADFContext application scope.**

**Cause:** The system failed to store data in the ADFContext application scope. Lifecycle functions may not be available.

**Action:** Review the log files to see if there are any other problems which may have resulted in the ADFContext object becoming unusable.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-12013: An internal class cast error has occurred. Actual class: {0}, cast-to class: {1}.**

**Cause:** The possible errors could be in the code or application configuration.

**Action:** Resolve any application configuration errors. If the problem recurs on subsequent attempts, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-12017: The export/import listener {0} has thrown an exception, which is being ignored.**

**Cause:** A class listening to export/import progress events has thrown an exception.

**Action:** Retry the operation and review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-12038: IOException while creating stage directory for export**

**Cause:** The possible causes could be coding, hardware, or file system errors.

**Action:** Review the full exception stack for details of the exception.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12039: IOException while creating temporary directory to extract the import archive to**

**Cause:** The possible causes could be coding, hardware, or file system errors.

**Action:** Review the full exception stack for details of the exception.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12040: IOException extracting import archive**

**Cause:** The possible causes could be coding, hardware, or file system errors.

**Action:** Review the full exception stack for details of the exception.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12041: Input archive path not set on context.**

**Cause:** The possible errors could be in the code or application configuration.

**Action:** Resolve any application configuration errors. If the problem recurs on subsequent attempts, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-12042: Input archive does not exist.**

**Cause:** The possible errors could be in the code or application configuration.

**Action:** Resolve any application configuration errors. If the problem recurs on subsequent attempts, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-12043: MDSConfigurationException constructing source instance for MDS transfer.**

**Cause:** The possible errors could be in the code or application configuration.

**Action:** Resolve any application configuration errors. If the problem recurs on subsequent attempts, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-12044: An unanticipated exception {0} has occurred while generating the oracle-archive.xml deployment descriptor of the export archive.**

---

**Cause:** Cause is dependent upon the type and details of the exception being processed.

**Action:** Review the exception being processed for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12045: Operation aborted because of an exception thrown by subunit ({0})**

**Cause:** The cause of the exception that was thrown is dependent upon the type and details of the exception.

**Action:** Review the exception thrown for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12046: MDSException while creating lifecycle document in MDS transfer source**

**Cause:** The possible causes could be coding, application configuration, or hardware errors.

**Action:** Retry the operation and review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12047: The import archive file does not contain a metadata archive.**

**Cause:** The supplied file to import was not a valid export archive.

**Action:** Retry the import operation with a valid export archive.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12048: FileNotFoundException extracting metadata transport archive**

**Cause:** The possible causes could be coding, hardware, or file system errors.

**Action:** Resolve any hardware or file system errors. If the problem recurs on subsequent attempts, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-12049: IOException while extracting metadata transport archive**

**Cause:** The possible causes could be coding, hardware, or file system errors.

**Action:** Review the full exception stack for details of the exception.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WCS-12050: IOException while creating metadata transport archive**

**Cause:** The possible causes could be coding, hardware, or file system errors.

**Action:** Review the full exception stack for details of the exception.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12051: Output path has not been set on operation context.**

**Cause:** The possible errors could be in the code or application configuration.

**Action:** Resolve any application configuration errors. If the problem recurs on subsequent attempts, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-12052: MDSException constructing transfer list for MDS transfer.**

**Cause:** The possible causes could be coding, application configuration, or hardware errors.

**Action:** Retry the operation and review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12053: MDSException performing MDS transfer.**

**Cause:** The possible causes could be coding, application configuration, or hardware errors.

**Action:** Retry the operation and review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12054: MDSException deleting existing metadata.**

**Cause:** The possible causes could be coding, application configuration, or hardware errors.

**Action:** Retry the operation and review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WCS-12055: An exception has occurred while creating the transformer factory to write lifecycle information document.**

**Cause:** The possible causes could be coding, application configuration, or hardware errors.

**Action:** Retry the operation and review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12056: IOException occurred creating lifecycle information document**

**Cause:** An error occurred writing to the file system while creating the lifecycle information document. The possible causes could be application configuration, or hardware errors.

**Action:** Review the full exception stack for details of the exception.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12057: TransformerException while writing lifecycle information document**

**Cause:** The possible causes could be coding, application configuration, or hardware errors.

**Action:** Retry the operation and review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12058: Input path has not been set on operation context.**

**Cause:** The possible errors could be in the code or application configuration.

**Action:** Resolve any application configuration errors. If the problem recurs on subsequent attempts, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-12059: IOException while creating oracle-archive.xml**

**Cause:** An error occurred while writing the oracle-archive.xml file to the file system. The possible causes could be application configuration, or hardware errors.

**Action:** Review the full exception stack for details of the exception.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12060: IOException while creating transport archive**

---

**Cause:** The possible causes could be coding, hardware, or file system errors.

**Action:** Review the full exception stack for details of the exception.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12061: Output archive path has not been set on operation context.**

**Cause:** The possible errors could be in the code or application configuration.

**Action:** Resolve any application configuration errors. If the problem recurs on subsequent attempts, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-12062: An unexpected exception occurred while removing lock {0}:{1}**

**Cause:** The possible causes could be coding, application configuration, or hardware errors.

**Action:** Retry the operation and review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12063: MDSEException occurred while removing lock {0}:{1}**

**Cause:** The possible causes could be coding, application configuration, or hardware errors.

**Action:** Retry the operation and review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12064: Unable to proceed with application import as another lock is blocking the import.**

**Cause:** Another operation was being performed that prevented application import.

**Action:** Retry the import operation after the other operation is complete.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12065: A lock exists that prevents the application import.**

**Cause:** Another application import was being performed that prevented this import.

**Action:** Retry the import operation after the other operation is complete



---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12066: MDSEException while creating application import lock**

**Cause:** The possible causes could be coding, application configuration, or hardware errors.

**Action:** Retry the operation and review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12067: A lock is blocking the import of scope {0}.**

**Cause:** Another operation was being performed that prevented the import.

**Action:** Retry the import operation after the other operation is complete

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12068: A lock exists that prevents the import of scope {0}.**

**Cause:** An import of the specified scope was being performed that prevented this import.

**Action:** Retry the import operation after the other operation is complete

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12069: MDSEException while creating scope import lock**

**Cause:** The possible causes could be coding, application configuration, or hardware errors.

**Action:** Retry the operation and review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12070: A lock exists that blocks the export set import.**

**Cause:** Another operation was being performed that prevented the export set import.

**Action:** Retry the import operation after the other operation is complete

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12071: A lock exists that prevents the export set import.**

---

**Cause:** An export set import was already being performed preventing this import.

**Action:** Retry the import operation after the other operation is complete

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12072: MDSEException while creating an export set import lock**

**Cause:** The possible causes could be coding, application configuration, or hardware errors.

**Action:** Retry the operation and review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12073: MDSEException while obtaining the Lifecycle bean from the MDS session**

**Cause:** The possible causes could be coding, application configuration, or hardware errors.

**Action:** Retry the operation and review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12074: ID of export set in MDS does not match that of the application. MDS ID: {0}, Application ID: {1}.**

**Cause:** An export set was imported from an incompatible source and has been ignored.

**Action:** Import an export set from a compatible instance.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12076: NamingException while binding connection {0} to the export connections.xml**

**Cause:** The possible causes could be coding or application configuration errors.

**Action:** Retry the operation and review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12077: NamingException while getting environment for exporting the ADF credential store**

**Cause:** The possible causes could be coding or application configuration errors.

---

**Action:** Retry the operation and review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12078: IOException while exporting ADF credential store**

**Cause:** The possible causes could be coding, hardware, or file system errors.

**Action:** Review the full exception stack for details of the exception.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12079: JPSEException while exporting JPS credential store**

**Cause:** The possible causes could be coding, application configuration, or hardware errors.

**Action:** Retry the operation and review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12080: MDSEException while creating lifecycle information metadata in transport set**

**Cause:** An existing document with the same name as the lifecycle information document was found in the transport set being constructed.

**Action:** Retry the operation and review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12081: ReferenceException while creating lifecycle information metadata in transport set**

**Cause:** An unexpected exception occurred while creating the lifecycle document in transport set.

**Action:** Retry the operation and review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12082: UnsupportedUpdateException while creating lifecycle information metadata in transport set**

**Cause:** An unexpected exception occurred while creating the lifecycle document in the transport set.

---

**Action:** Retry the operation and review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12083: MDSEException while building transfer list for lifecycle metadata**

**Cause:** The possible causes could be coding, application configuration, or hardware errors.

**Action:** Retry the operation and review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12084: MDSEException while constructing metadata store for MDS transfer**

**Cause:** The possible causes could be coding, application configuration, or hardware errors.

**Action:** Retry the operation and review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12085: ParserConfigurationException while creating lifecycle information document**

**Cause:** An unexpected exception occurred while creating the lifecycle document in the transport set.

**Action:** Retry the operation and review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12086: SAXException while creating lifecycle information document**

**Cause:** An unexpected exception occurred while creating the lifecycle document in the transport set.

**Action:** Retry the operation and review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12087: ServiceException while getting registered services**

**Cause:** There was an error in the application's configuration.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-12088: Cannot find lifecycle service extension registry**

**Cause:** An error in the application's configuration.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-12089: Destination path specified to create the temporary directory is not a directory.**

**Cause:** The possible causes could be coding, application configuration, or hardware errors.

**Action:** Resolve any application configuration or hardware errors. If the problem recurs on subsequent attempts, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-12090: The source path specified to archive does not exist**

**Cause:** The possible causes could be coding, application configuration, or hardware errors.

**Action:** Resolve any application configuration or hardware errors. If the problem recurs on subsequent attempts, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-12091: The source path specified to archive is not a directory**

**Cause:** The possible causes could be coding, application configuration, or hardware errors.

**Action:** Resolve any application configuration or hardware errors. If the problem recurs on subsequent attempts, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-12092: A file already exists with the same name as the destination folder.**

**Cause:** A call was made to extract an archive to a destination directory with the same name as an existing file.

**Action:** Retry the operation that caused this error.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-12093: {0} is an invalid value for the maximum number of steps. The maximum number of steps must be a least 1.**

**Cause:** The probable cause is a coding error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-12094: MDSEException while constructing metadata store for MDS transfer**

**Cause:** The possible causes could be coding, application configuration, or hardware errors.

**Action:** Retry the operation and review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12095: Import archive file does not exist or could not be read.**

**Cause:** The specified file could not be found either because it does not exist or does not have the correct access permissions.

**Action:** Check that the path is correct, the file exists and has the appropriate access permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12096: Unable to proceed with application export as another lock is blocking the export.**

**Cause:** Another operation was being performed that prevented application export.

**Action:** Retry the export operation after the other operation is complete.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12097: A lock exists that prevents the application export.**

**Cause:** An import was being performed that prevented this export.

**Action:** Retry the export operation after the other operation is complete

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12098: MDSEException while creating application export lock**

---

**Cause:** The possible causes could be coding, application configuration, or hardware errors.

**Action:** Retry the operation and review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12099: An unexpected exception occurred while refreshing lock {0}:{1}**

**Cause:** The possible causes could be coding, application configuration, or hardware errors.

**Action:** Retry the operation and review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-12100: MDSException occurred while refreshing lock {0}:{1}**

**Cause:** The possible causes could be coding, application configuration, or hardware errors.

**Action:** Retry the operation and review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-12101: Unable to find data source**

**Cause:** The data source hasn't been configured

**Action:** Configure the data source

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12102: An exception occurred while refreshing lock {0}:{1}**

**Cause:** The possible causes could be coding, application configuration, or hardware errors.

**Action:** Retry the operation and review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12103: Unexpected RuntimeException performing MDS transfer.**

**Cause:** The possible causes could be coding, application configuration, or hardware errors.

---

**Action:** Retry the operation and review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12104: Unexpected exception occurred while exporting from a portlet producer.**

**Cause:** The possible causes could be the portlet producer is down or unavailable, errors from the portlet producer, or application configuration.

**Action:** Check that the portlet producers are available, and then retry the export. Review the full exception stack for details of the exception should it recur.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12106: Document {0} has been excluded from the export set.**

**Cause:** The path of the document exceeds file system constraints and therefore cannot be exported.

**Action:** None

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12920: A problem was encountered when invoking a method on a remote mBean ({0}) which has caused the local operation to fail.**

**Cause:** In order for the local operation to be performed a method on a remote mBean has to be invoked - there are numerous reasons why the remote method invocation could fail ranging from connection problems between servers to the remote object simply not existing

**Action:** Review the log files for a record of this error in order to ascertain the primary cause.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12950: The required customization class is not found: {0}**

**Cause:** To export the specified customization class, first an instance of the class must be created. An instance of this class could not be created because the class was not included in the classpath.

**Action:** Include the customization class in the classpath of the application and restart the application.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12951: The required customization class cannot be instantiated: {0}**



---

**Cause:** To export the specified customization class, first an instance of the class must be created. An instance of this class could not be created because it is an interface or abstract class.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-12952: The required customization class cannot be instantiated: {0}**

**Cause:** To export the specified customization class, first an instance of the class must be created. An instance of this class could not be created because the current method was unable to access it.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-12957: An exception occurred while importing data, no data has been imported.**

**Cause:** The possible causes could be hardware, or application configuration errors.

**Action:** For information, review other messages in the log file and the reported exception stacks. Resolve any application configuration or hardware errors.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-12958: Import has failed with errors.**

**Cause:** The possible causes could be hardware, or application configuration errors.

**Action:** For information, review other messages in the log file and the reported exception stacks. Resolve any application configuration or hardware errors.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12959: Export has failed with errors.**

**Cause:** The possible causes could be hardware, or application configuration errors.

**Action:** For information, review other messages in the log file and the reported exception stacks. Resolve any application configuration or hardware errors.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12980: Service {0} has not been provisioned for Scope {1}.**

---

**Cause:** The Service has not been provisioned for the specified Scope.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-12981: Service {0} has already been provisioned for Scope {1}.**

**Cause:** The Service has already been provisioned for the specified Scope.

**Action:** Do not provision the Service for a Scope it is already provisioned for or unprovision the Service first.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12982: Scope {0} is not known.**

**Cause:** A Scope with the specified name has not been created.

**Action:** Create a Scope with the specified name using the createScope method on the ServiceContext.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12983: Service {0} has not been configured for the application.**

**Cause:** The Service has not been configured for the application.

**Action:** Configure the Service and try the operation again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12984: An error occurred removing the security policies for service {0}.**

**Cause:** The possible causes could be coding, application configuration, or hardware errors.

**Action:** Review the full exception stack for details of the exception.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-12985: An error occurred invoking isProvisioned for service {0}.**

**Cause:** The possible causes could be coding, application configuration, or hardware errors.

**Action:** Review the full exception stack for details of the exception.

**Level:** 1

**Type:** WARNING

**Impact:** Other

---

**WCS-12990: Specified key does not match that of the lock with type "{0}" and name "{1}".**

**Cause:** The application attempted to manipulate a lock with an incorrect lock key.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-12991: Lock with type "{0}" and name "{1}" already exists.**

**Cause:** A lock with the specified type and name already exists.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-12992: Lock with type "{0}" and name "{1}" does not exist.**

**Cause:** The application attempted to manipulate a lock that no longer exists.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-12993: Lock with type "{0}" and name "{1}" could not be created as a lock with type "{2}" exists.**

**Cause:** A lock with a type that prevents locks with the specified type being created exists.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-14001: An unexpected error occurred.**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-14002: An object of type {0} with this id ({1}) already exists.**

**Cause:** An attempt was made to create an object with an id that is already in use.

**Action:** Specify a unique id.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WCS-14004: The name ({0}) is not valid.**

**Cause:** The specified name is not valid.

**Action:** Specify a valid name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-14005: The specified list type could not be found.**

**Cause:** The specified list type could not be found. This may be due to the list type being deleted by another user.

**Action:** Try reloading to see if the list has been deleted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-14006: Object has been changed by another user.**

**Cause:** The object has been changed by another user.

**Action:** Reload the object and try the operation again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-14007: An Object of type {0} with id={1} could not be found.**

**Cause:** The specified object could not be found. This may be due to the list being deleted by another user.

**Action:** Specify a valid id.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-14008: Object ({0}) is immutable.**

**Cause:** An attempt to change this object was made, but this object is currently immutable.

**Action:** Retrieve mutable object to make changes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-14010: {0} is not a valid reference name to MDS.**

**Cause:** The name is not a valid MDS reference name.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

---

**WCS-14011: The MDS session does not support updates.**

**Cause:** MDS was not configured correctly to support updates.

**Action:** Configure the MDS store to support updates.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-14012: An IO error occurred when accessing metadata.**

**Cause:** An IO error occurred in MDS.

**Action:** See the log for more details on the specific IO error to correct the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-14013: The object is not valid.**

**Cause:** The metadata for the object does not pass validation.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-14014: Failed to construct attribute set for list [{0}].**

**Cause:** Failed to construct attribute set for list.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-14015: Failed to add data flavor to ListTransferable. List=[{0}] DataFlavor=[{1}]**

**Cause:** Failed to add data flavor to ListTransferable.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-14017: An error occurred when deleting metadata.**

**Cause:** An error occurred in MDS while deleting metadata.

**Action:** See the log for more details on the specific error to correct the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-14018: A column with the name ({0}) already exists.**

---

**Cause:** A column was created or renamed with the name of an existing column in the list.

**Action:** Specify a unique column name within the list.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-14019: A list with the name ({0}) already exists.**

**Cause:** A list was created or renamed with the name of an existing list.

**Action:** Specify a unique list name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-14020: The maximum number of columns for this list has been exceeded.**

**Cause:** A list was created or modified with more than 30 columns.

**Action:** Do not add more than 30 columns to a list.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-14021: User does not have permission to perform {0} operation for {1}.**

**Cause:** User does not have permission to perform the specified operation.

**Action:** Grant the user permission to perform the specified operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-14022: The Lists service is not provisioned for scope {0}.**

**Cause:** The Lists service is not provisioned for the specified scope.

**Action:** Provision the Lists service for the specified scope.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-14023: The value is the wrong data type. The data type expected is {0}.**

**Cause:** The value is the wrong data type.

**Action:** Use the value with the correct data type.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-14024: The WebCenter repository is not available.**

**Cause:** An error occurred accessing the repository.

---

**Action:** Contact your system administrator. Check the log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-14025: An error occurred accessing the WebCenter metadata repository.**

**Cause:** An error occurred accessing the repository.

**Action:** Contact your system administrator. Check the log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-14501: The list was not found.**

**Cause:** The list could not be found.

**Action:** Remove the list view for the invalid list from the page.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-14502: Another user deleted the row while you modified it. Refresh the list and discard unsaved changes.**

**Cause:** Another user deleted the row while you modified it.

**Action:** Refresh the list and discard unsaved changes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-14503: Another user modified a row while you modified it. Refresh the list and discard unsaved changes.**

**Cause:** Another user modified a row while you modified it.

**Action:** Refresh the list and discard unsaved changes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-14504: Another user deleted the list after you displayed it. Refresh the list and discard unsaved changes.**

**Cause:** Another user deleted the list after you displayed it.

**Action:** Refresh the list and discard unsaved changes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-14505: Another user modified this list after you displayed it. Refresh the list and discard unsaved changes.**

---

**Cause:** Another user modified this list after you displayed it.

**Action:** Refresh the list and discard unsaved changes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-14506: Invalid minimum/maximum range**

**Cause:** Minimum value must be less than or equal to maximum value.

**Action:** Modify the minimum value or maximum value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-14507: Default value is out of range**

**Cause:** Default value must be between the minimum and maximum values.

**Action:** Modify the default value, minimum value, or maximum value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-14508: An error occurred accessing the WebCenter repository.**

**Cause:** An error occurred accessing the repository.

**Action:** Contact your system administrator. Check the log for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-14509: Your permission to perform this operation was revoked. Refresh the list and discard unsaved changes.**

**Cause:** Your permission to perform this operation was revoked.

**Action:** Request permission to perform this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-14510: The Lists service was disabled, preventing you from performing this operation. Refresh the list and discard unsaved changes.**

**Cause:** The Lists service was disabled, preventing you from performing this operation.

**Action:** Enable the Lists service.

**Level:** 1

**Type:** ERROR

**Impact:** Other



---

**WCS-14514: An unexpected error occurred. Please retry the operation.**

**Cause:** An unexpected error occurred.

**Action:** Retry the operation. If the problem persists, contact your administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-14515: Default value is too long**

**Cause:** Default value must not exceed the maximum length.

**Action:** Modify the default value or maximum length.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-14516: The WebCenter metadata repository was temporarily unavailable. Please retry the operation.**

**Cause:** The connection to the WebCenter metadata repository failed.

**Action:** Retry the operation. If the problem persists, contact your administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-16004: An unexpected error occurred**

**Cause:** Cannot find component with clientId - {0}

**Action:** Contact Oracle Support Services for assistance.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-16005: An unexpected error occurred**

**Cause:** ADFContext is null

**Action:** Contact Oracle Support Services for assistance.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-16006: An unexpected error occurred**

**Cause:** Cannot find the component with id {0}

**Action:** Contact Oracle Support Services for assistance.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-16007: An unexpected error occurred**

---

**Cause:** An error occurred while saving custom panel data

**Action:** Contact Oracle Support Services for assistance.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-16008: An unexpected error occurred**

**Cause:** An error occurred while saving event wiring data

**Action:** Contact Oracle Support Services for assistance.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-16009: An unexpected error occurred**

**Cause:** An error occurred while saving an EL

**Action:** Contact Oracle Support Services for assistance.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-16010: An unexpected error occurred**

**Cause:** Cannot find a persistence handler by name {0}

**Action:** Contact Oracle Support Services for assistance.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-16011: An unexpected error occurred**

**Cause:** Managed bean {0} does not implement {1}

**Action:** Correct the implementation of {0}

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-16012: An unexpected error occurred**

**Cause:** Circular reference detected for parameter {0}

**Action:** Correct the circular referencing of parameters and retry

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-16013: Parameter list is null**

**Cause:** Parameter list is null

**Action:** Contact Oracle Support Services for assistance.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-16014: Page Definition not found**

**Cause:** Page Definition not found

**Action:** Contact Oracle Support Services for assistance.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-16015: Could not get design time binding container**

**Cause:** Could not get design time binding container

**Action:** Contact Oracle Support Services for assistance.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-16026: error downloading file {0}**

**Cause:** An error occurred while downloading file {0}.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-16027: error downloading all customizations**

**Cause:** An error occurred while downloading all customizations.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-16028: error uploading file {0}**

**Cause:** An error occurred while uploading file {0}.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-16029: error uploading file {0}**

**Cause:** File {0} was not well formed. syntax error {1} occurred at line {2} column {3}

**Action:** Correct the XML syntax and upload the file again.

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Other

**WCS-16030: error deleting file {0}**

**Cause:** An error occurred while deleting file {0}.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-16031: error promoting file {0} from label {1}**

**Cause:** An error occurred while promoting file {0} from label {1}.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-16116: An unexpected error occurred. The structure navigator is not initialized**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services for assistance.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-16117: An error occurred executing phase listener - {0}**

**Cause:** An error occurred executing phase listener - {0}

**Action:** Contact Oracle Support Services for assistance.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-16118: An error occurred while deleting {0}**

**Cause:** An error occurred while persisting component deletion to datastore

**Action:** Contact Oracle Support Services for assistance.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-16130: Error occurred while re-ordering components.**

**Cause:** An error occurred while re-ordering components. Review the underlying exception in the logs to determine the exact cause.

**Action:** Take action based on the underlying exception details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WCS-16301: A facet named {0} declared by the toolbarLayout attribute was not found in page {1}.**

**Cause:** Failed to retrieve a facet definition corresponding to the declaration provided in the pageCustomizable's toolbarLayout attribute

**Action:** Verify all facets declared in toolbarLayout have a definition

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-16355: Could not find resource entry for {0}**

**Cause:** An error occurred while finding resource entry for {0}, The resource entry does not exist in the override bundle. It could also have been deleted.

**Action:** Ensure that the resource key entry is correctly spelt. Recreate the resource entry if it has been deleted.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-16407: An error occurred while destroying the sandbox**

**Cause:** An error occurred while destroying the sandbox - {0}

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-16408: Unable to create Application Session Options Factory {0}**

**Cause:** An error occurred while creating Application Session Options Factory {0}

**Action:** Verify configuration of Application Session Options Factory {0}

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-16409: Unable to create Sandbox {0} for Page {1}**

**Cause:** An error occurred while creating Sandbox {0} for Page {1}

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-16410: Error retrieving Metadata Object for page: {0}**

**Cause:** An error occurred while retrieving the Metadata Object

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Other

**WCS-16676: Not nested in ADF Faces tag: {0}**

**Cause:** The Behavior tag is not nested inside an ADF Faces tag.

**Action:** Enclose the Behavior tag inside an ADF Faces tag.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-16677: Parent UIComponent instance is null.**

**Cause:** Parent UIComponent is not created.

**Action:** Enclose the Behavior tag inside a UIComponent tag.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-16678: Component: {0} does not support client listeners.**

**Cause:** Parent component enclosing the Behavior tag does not support client listeners.

**Action:** Enclose the Behavior tag inside an ADF Faces tag that supports client listeners. Check if the Behavior tag is enclosed within a ADF command component.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-16679: Component: {0} does not support client attributes.**

**Cause:** Parent component enclosing the behavior tag does not support client attributes.

**Action:** Enclose the Behavior tag inside an ADF Faces tag that supports client attributes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-16728: Unable to parse markup: {0}**

**Cause:** An error occurred parsing the markup

**Action:** Please check if the markup is well formed

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-16729: I/O Exception occurred while parsing the markup: {0}**

**Cause:** An I/O error occurred parsing the markup

**Action:** Please take corrective action given by the exception stack trace.

---

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-16754: An error occurred while performing move action**

**Cause:** Error occurred while persisting the changes to datastore

**Action:** Check whether the persistence configuration is defined correctly and whether the document being customized specifies id's for all elements enclosed within pageCustomizable

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-16759: An error occurred while performing move action**

**Cause:** An error occurred while re-ordering components. Review the underlying exception in the logs to determine the exact cause.

**Action:** Take action based on the underlying exception details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-16912: The built-in extension file {0} is not found, or an error has occurred while reading the built-in extension file.**

**Cause:** Could not find the built-in extension file or error reading it.

**Action:** The Oracle Composer component may have been damaged or is inaccessible to the application. Ensure that the Oracle Composer JAR file is not damaged and is accessible to the application.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-16937: Error adding a custom property panel**

**Cause:** An error occurred adding a custom panel {0} for component of type {1}.

**Action:** Ensure that the expression {0} associated with "isRendered" attribute of the custom panel usage executes without errors.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-16951: An error has occurred while creating the security policy {0}.**

**Cause:** An error occurred while creating the security policy {0}.

**Action:** Ensure that the class {0} is in the classpath and has inherited the security policy specified by oracle.adf.view.page.editor.security.SecurityPolicy.

**Level:** 1

**Type:** WARNING

---

**Impact:** Other

**WCS-18001: An unexpected error occurred.**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-18002: Missing Configuration for List of Contacts. Could not locate the class {0}.**

**Cause:** An incorrect class name was provided.

**Action:** Please contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18003: Class {0} does not implement the interface {1}.**

**Cause:** The specified class had not implemented the required interface.

**Action:** Ensure that the class implements the required interface.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18004: Cannot instantiate class {0}.**

**Cause:** The specified class did not have a default constructor accessible to public.

**Action:** Ensure that the class has a default constructor and it is accessible to public.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18005: Cannot instantiate class {0}.**

**Cause:** Either the specified class was not a concrete implementation or it did not have a default constructor accessible to public.

**Action:** Ensure that the class is a concrete implementation and has a default constructor accessible to public.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18006: The implementation class {0} returned null.**

**Cause:** The implementation class returned a null object.

**Action:** Ensure that the implementation class returns a non-null list of contacts.

**Level:** 1



---

**Type:** WARNING

**Impact:** Other

**WCS-18007: An error occurred while trying to validate metadata.**

**Cause:** Invalid metadata has been introduced.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-18008: Unable to save the metadata in persistence store**

**Cause:** An error occurred while writing to persistence store or metadata was locked by another user.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-18009: Cannot apply the current metadata changes to a concurrently modified metadata.**

**Cause:** Recent changes in this session conflicts with changes made in the same session.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-18010: Cannot locate the requested metadata.**

**Cause:** The metadata was not found in the configured metadata stores or it had been deleted on this session.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-18011: Cannot obtain the metadata for write operations.**

**Cause:** The metadata store could be spanning multiple back-end stores or concurrent updates were attempted.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-18012: Metadata already exists in metadata store.**

**Cause:** An attempt was made to create a metadata document when it already exists.

---

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-18013: The reference to the specified metadata is invalid.**

**Cause:** The reference to the metadata was incorrect.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-18014: Could not be complete the sort operation.**

**Cause:** A null table component was returned.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-18015: Could not get contact details.**

**Cause:** The selected contact details were unavailable due to an internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-18016: Could not launch the dialog for view {0}.**

**Cause:** Profile page details are unavailable due to an internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-18017: Could not perform a people search.**

**Cause:** Instance of identity store is not available.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-18018: Could not get display name from user profile.**

**Cause:** User did not have the display name or user's profile was not accessible.

**Action:** Contact the administrator of directory services/webcenter.

---

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-18019: Could not get name from user profile.**

**Cause:** User does not have the name or user's profile is not accessible.

**Action:** Please contact the administrator of directory services/webcenter.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-18020: Could not save the search criterion.**

**Cause:** An internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-18021: Could not fetch the search criterion.**

**Cause:** An internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-18022: Could not fetch the sort criteria.**

**Cause:** An internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-18023: Could not save the sort criteria.**

**Cause:** An internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-18024: Cannot get an instance of the identity store**

**Cause:** There was either an improper configuration or an internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Other

**WCS-18025: Could not create the contacts list.**  
**Cause:** An internal error.  
**Action:** Contact Oracle Support Services.

**Level:** 1  
**Type:** INCIDENT\_ERROR  
**Impact:** Other

**WCS-18026: Could not perform a people search.**  
**Cause:** An internal error.  
**Action:** Contact Oracle Support Services.

**Level:** 1  
**Type:** INCIDENT\_ERROR  
**Impact:** Other

**WCS-18401: An unexpected error occurred in the Message Board sub-system.**  
**Cause:** An unexpected error occurred.  
**Action:** Contact Oracle Support Services.

**Level:** 1  
**Type:** INCIDENT\_ERROR  
**Impact:** Other

**WCS-18402: Failed to create an instance of Message Board**  
**Cause:** Message Board viewing user name not found  
**Action:** Make sure that the user is logged in

**Level:** 1  
**Type:** ERROR  
**Impact:** Other

**WCS-18403: Failed to create an instance of Message Board**  
**Cause:** Message Board owner user name not specified  
**Action:** Provide owner user name in the request for an instance of Message Board

**Level:** 1  
**Type:** ERROR  
**Impact:** Other

**WCS-18404: Failed to persist Message Board message**  
**Cause:** An unexpected error occurred  
**Action:** Contact Oracle Support Services

**Level:** 1  
**Type:** INCIDENT\_ERROR  
**Impact:** Other

**WCS-18405: Failed to publish Message Board activity**

---

**Cause:** Activity Stream service raised an exception

**Action:** Verify the reason for the failure in the Activity Stream sub-system

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18406: Message Board message cannot be deleted**

**Cause:** User is not authorized to delete this message

**Action:** Resubmit the request with correct parameters

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18407: Failed to delete Message Board message**

**Cause:** Message does not exist

**Action:** Resubmit the request with correct parameters

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18408: Message Board message cannot be updated**

**Cause:** User is not authorized to update this message

**Action:** Resubmit the request with correct parameters

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18409: Failed to update Message Board message**

**Cause:** Message does not exist

**Action:** Resubmit the request with correct parameters

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18410: Message Board message cannot be added**

**Cause:** Message content is empty

**Action:** Provide a non empty message board message text

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18411: Message Board message cannot be hidden**

**Cause:** User is not authorized to hide message

**Action:** Resubmit the request with correct parameters

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18412: Failed to hide Message Board message**

**Cause:** Message does not exist

**Action:** Resubmit the request with correct parameters

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18414: Failed to add message to Message Board.**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18415: Failed to hide or unhide message in Message Board.**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18416: Failed to delete message in Message Board.**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18417: Failed to query messages in Message Board.**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18418: Failed to update message in Message Board.**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-18419: Failed to create an instance of Message Board.**

**Cause:** Message Board preferences manager not specified

**Action:** Provide preferences manager in the request for Message Board

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18420: Failed to query preferences for Message Board.**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18421: Message cannot be added to Message Board.**

**Cause:** User is not authorized to add message

**Action:** Resubmit the request with correct parameters

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18422: Failed to retrieve Message Board message**

**Cause:** Message does not exist

**Action:** Resubmit the request with correct parameters

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18423: Failed to find the group space of the message board.**

**Cause:** The group space doesn't exist.

**Action:** Contact your administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18424: Failed to find the user of the message board.**

**Cause:** The user doesn't exist.

**Action:** Contact your administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18451: Unexpected error getting preference.**

---

**Cause:** An unexpected error occurred.  
**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18452: Unexpected error saving preference.**

**Cause:** An unexpected error occurred.  
**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18453: Encountered exception: {0}. For diagnosis, turn on the logging level to FINEST and retry the operation. Details about the current state: {1}.**

**Cause:** An unexpected error occurred.  
**Action:** To diagnose the error, turn on the logging level to FINEST and retry the operation.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-18501: Error retrieving the Profile**

**Cause:** An unexpected error occurred.  
**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-18502: User: {0} not found in identity store.**

**Cause:** An unexpected error occurred.  
**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-18503: Personal status note can be changed only for the current user**

**Cause:** attempt made by an user to update personal status of another user  
**Action:** login as the user whose status you want to change

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-18504: unexpected error operating on personal status note**



---

**Cause:** An unexpected error occurred.  
**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-18505: unexpected error saving profile**

**Cause:** An unexpected error occurred.  
**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-18506: Current user does not have view profile privilege.**

**Cause:** Insufficient privilege to view Profile.  
**Action:** Contact Webcenter Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18507: Insufficient Privilege.**

**Cause:** Cannot Edit Profile.  
**Action:** Contact Webcenter Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18508: Unexpected error retrieving user {0}'s photo**

**Cause:** An unexpected error occurred.  
**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18509: Unexpected error saving user {0}'s photo to the back-end. The photo may not have been saved. Please refresh to find out and then retry the operation.**

**Cause:** An unexpected error occurred.  
**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18510: Unexpected error invalidating user {0}'s photo cache**

---

**Cause:** An unexpected error occurred.  
**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18511: User not specified**

**Cause:** The supplied username was null or blank.

**Action:** Specify a valid username that is not null or blank.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18512: Unexpected error serving the requested photo {0}**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18514: Unexpected error saving the Profile Admin Settings**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18515: Unexpected error saving the Profile user preference**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18516: Unexpected error initializing the admin config bean**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18517: Unexpected error saving the profile**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

---

**Level: 1**

**Type: ERROR**

**Impact: Other**

**WCS-18518: Unexpected Error Initializing profile cache**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level: 1**

**Type: ERROR**

**Impact: Other**

**WCS-18519: Unexpected error doing cache operations on profile**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level: 1**

**Type: ERROR**

**Impact: Other**

**WCS-18520: Unexpected error retrieving unique identifier for user {0}'s photo**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level: 1**

**Type: ERROR**

**Impact: Other**

**WCS-18521: Unexpected error evaluating property "{0}" of base {1}**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level: 1**

**Type: ERROR**

**Impact: Other**

**WCS-18522: Modifying property "{0}" of base {1} not allowed**

**Cause:** The application does not allow modifying the value of the specified property of the specified base object.

**Action:** Ensure that property of the object being modified is not read-only.

**Level: 1**

**Type: ERROR**

**Impact: Other**

**WCS-18523: Error getting the instant message address for the person**

**Cause:** unexpected error getting the sip address

**Action:** contact the administrator

**Level: 1**

---

**Type:** ERROR

**Impact:** Other

**WCS-18524: Error getting tag data**

**Cause:** unexpected error getting tag data

**Action:** contact the administrator

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18525: Unexpected error saving attribute: {0}**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services with the error on the log.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18526: Current user does not have edit profile privilege.**

**Cause:** Insufficient privilege to edit Profile.

**Action:** Contact Webcenter Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18527: The image file {0} you tried to upload was invalid. Provide a valid image file.**

**Cause:** Unable to upload the image as the file is null or invalid.

**Action:** Upload a valid image file

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18528: Unexpected error instantiating object.**

**Cause:** Unexpected error instantiating object.

**Action:** contact the administrator

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18529: Error instantiating profile (user name: {0}, GUID: {1})**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-18701: An unexpected error occurred in the Feedback sub-system.**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-18702: Failed to create an instance of Feedback**

**Cause:** Feedback object's viewing user name not found

**Action:** Make sure that the user is logged in

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18703: Failed to create an instance of Feedback**

**Cause:** Feedback object's user name not specified

**Action:** Provide user name in the request for an instance of Feedback

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18704: Failed to persist Feedback message**

**Cause:** An unexpected error occurred

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-18705: Failed to publish Feedback activity**

**Cause:** Activity Stream service raised an exception

**Action:** Verify the reason for the failure in the Activity Stream sub-system

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18706: Feedback message cannot be deleted**

**Cause:** User is not authorized to delete this message

**Action:** Resubmit the request with correct parameters

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18707: Failed to delete Feedback message**

---

**Cause:** Message does not exist  
**Action:** Resubmit the request with correct parameters  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other

**WCS-18708: Feedback message cannot be updated**  
**Cause:** User is not authorized to update this message  
**Action:** Resubmit the request with correct parameters  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other

**WCS-18709: Failed to update Feedback message**  
**Cause:** Message does not exist  
**Action:** Resubmit the request with correct parameters  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other

**WCS-18710: Feedback message cannot be added**  
**Cause:** User is not authorized to add message  
**Action:** Resubmit the request with correct parameters  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other

**WCS-18711: Feedback message cannot be hidden**  
**Cause:** User is not authorized to hide message  
**Action:** Resubmit the request with correct parameters  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other

**WCS-18712: Failed to hide Feedback message**  
**Cause:** Message does not exist  
**Action:** Resubmit the request with correct parameters  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other

**WCS-18713: Feedback message cannot be added**  
**Cause:** Feedback message content is empty  
**Action:** Provide a non empty feedback message text

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18715: Failed to add feedback.**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18716: Failed to hide or unhide feedback.**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18717: Failed to delete feedback.**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18718: Failed to query feedback messages.**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18719: Failed to create an instance of Feedback**

**Cause:** Feedback object's preferences manager not specified

**Action:** Provide preferences manager in the request for an instance of Feedback

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-18720: Failed to query preferences for Feedback object.**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-19001: Unexpected error occurred**

**Cause:** An internal error occurred

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19002: Unable to execute WebCenter operation on {0}**

**Cause:** An internal error occurred

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19003: Metadata file {0} not found**

**Cause:** The expected metadata file was not found

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19004: Unexpected error occurred while creating page table**

**Cause:** An internal error occurred

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19005: Internal error while creating policy store metadata for WebCenter {0}**

**Cause:** Policy store for WebCenter not found

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19007: Unable to copy WebCenter or group space policies for {0}**

**Cause:** Exception occurred while copying WebCenter policies.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19008: No matching users were found with search string {0}**



---

**Cause:** No users matched the search string you entered: {0}

**Action:** Enter a new search term and try again

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19010: Couldn't retrieve metadata for role {0}**

**Cause:** No WebCenter roles matched the search string you entered: {0}

**Action:** Enter a new search term and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19013: User name can not be null**

**Cause:** A null or empty string was provided for the user name.

**Action:** Enter a valid user name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19014: Role name can not be null**

**Cause:** A null or empty string was provided for the role name.

**Action:** Enter a valid role name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19016: Unable to grant user {2} with role {1} in {0}**

**Cause:** An attempt to grant a user role failed. Either, role {1} does not exist, user {0} does not exist, or the user is already granted the role

**Action:** Determine the cause and, if necessary, try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19017: Unable to revoke role {1} from identity {0}**

**Cause:** An attempt to grant a identity role failed. Either, role {1} does not exist, identity {0} does not exist, or the identity does not have the specified role.

**Action:** Determine the cause and, if necessary, try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19018: Unable to add role {0} to the policy store**

---

**Cause:** An attempt to create a new role failed. Either the role already exists, or the policy store is currently unavailable

**Action:** Determine the cause and, if necessary, try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19019: An error occurred while trying to remove role{0} from the policy store**

**Cause:** An attempt to delete the specified role failed. Either the role does not exist, or the policy store is currently unavailable.

**Action:** Determine the cause and, if necessary, try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19020: Identity {0} has already been granted the role(s).**

**Cause:** User has been already granted the same role.

**Action:** Determine the cause and, if necessary, try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19022: Role {0} already exists in the policy store**

**Cause:** An attempt to create a new role failed because the policy store contains a role with the name specified.

**Action:** Enter a unique name for the role.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19025: Only authenticated users can perform the requested operation**

**Cause:** You do not have sufficient privileges to perform the requested operations.

**Action:** Ask your WebCenter administrator to grant you the appropriate privileges and then try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19026: Unable to revoke permission {0}**

**Cause:** The specified permission was not removed from the policy store. The permission may not exist

**Action:** Check whether the permission exists in the policy store

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-19027: Unable to grant permission {0}**

**Cause:** The user was not granted the specified permission. The user may already be assigned that permission.

**Action:** Check whether the user is assigned this permission.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19029: Application policy for WebCenter Spaces could not be found**

**Cause:** The application policy for WebCenter Spaces was missing from the policy store.

**Action:** Check the WebCenter Spaces policy store is configured correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19030: Page definition for page {0} not found**

**Cause:** Page definition for page {0} does not exist.

**Action:** Check whether the page definition for page {0} exists

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19031: Policy store instance cannot be null**

**Cause:** No policy store instance was found

**Action:** Verify and instantiate the policy store instance and try the operation again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19032: Security Manager already initialized**

**Cause:** An attempt was made to initialize the Security Manager but it was already initialized.

**Action:** Use the existing Security Manager.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19033: Security Manager is not initialized**

**Cause:** A security operation was attempted before the Security Manager was initialized.

**Action:** Initialize the Security Manager and try again

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19034: WebCenterSecurityManager class cannot be initialized directly**

**Cause:** An attempt was made to initialize the WebCenterSecurityManager class through a protected constructor.

**Action:** Initialize the WebCenterSecurityManager class with a default constructor.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19035: Security Manager is null**

**Cause:** Security Manager could not be initialized

**Action:** Use valid parameters and try again.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-19036: Scoped Security Manager is null for scope {0}**

**Cause:** Security manager can not be initialized

**Action:** Please try to initialize again with proper parameters

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-19037: Invalid context {1} for scope {0}**

**Cause:** Current scope did not match the cached scope

**Action:** Refresh your page again and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19038: An error occurred while importing security policies.**

**Cause:** Failed to create security policies (grants, roles and permissions) during import.

**Action:** Verify that the export archive is valid, otherwise check logs for error details and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19039: ADFContext is NULL, so returning NULL as username**

**Cause:** An internal error occurred while fetching the user name.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19040: SecurityContext is NULL, so returning NULL as username**

**Cause:** SecurityContext was not found for the current session

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19042: Unable to retrieve Personal Sidebar items**

**Cause:** An error locating for opening the JSPX document for the Personal Sidebar

**Action:** Ensure that the JSPX document pointing to the Personal Sidebar is available to the application

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19043: Unable to persist personalization for tag with webcenterId "{0}" in the Personal Sidebar**

**Cause:** An error saving the personalization document for the Personal Sidebar JSPX, or the tag with this webcenterId could not be located.

**Action:** Ensure that the personalization is enabled on the Personal Sidebar JSPX, and the tag has a unique webcenterId

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19044: Unable to retrieve item called {0} from the shell in the request {1}**

**Cause:** Either the item name is incorrect or the item is not available in the current shell context

**Action:** Verify that the item name is correct and that the shell context is setup properly for the current request.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-19045: Unable to register shell handler of type {0}**

**Cause:** Either the class name of the shell handler is incorrect or there was a problem while instantiating the shell handler

**Action:** Verify whether the shell handler type is correct or determine why the shell handler is not instantiating properly

**Level:** 1

**Type:** WARNING

---

**Impact:** Other

**WCS-19046: Unable to retrieve the visibility of shell panel {0}**

**Cause:** An error occurred trying to retrieve the visibility information from the shell handler of the current request.

**Action:** Defaulting visibility to 'true'

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-19048: Unable to retrieve panel metadata for panel properties (panel name: {0})**

**Cause:** The metadata for the panel in the shell metadata document may be corrupted or missing, or the name of the panel is incorrect.

**Action:** Verify whether the panel name is correct and whether the metadata for the panel is valid

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19049: An attempt to set change the skin was ignored**

**Cause:** An attempt was made to change the skin but this feature is not yet implemented.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-19051: An attempt was made to set the template and ignored**

**Cause:** This change would not take place as the feature is not implemented

**Action:** Please contact Oracle Support for more details

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-19054: Error retrieving a physical page view-id for the request {0} (context URL {1})**

**Cause:** The request URL could be invalid, or an unknown problem occurred fetching the metadata

**Action:** Verify the request URL and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19055: Unable to display a page for the requested URL {0}**

**Cause:** The request URL was invalid, either because there was no shell handler or the shell handler could not provide a physical page to forward to.

---

**Action:** Verify the request URL and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19058: Unable to retrieve scope IDs for the current user**

**Cause:** An internal error occurred while fetching the scope for the current user.

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19061: Unable to INSTANTIATE shell handler factory of type {0}**

**Cause:** Shell handler factory of type {0} was not in the classpath.

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19062: Unable to INITIALIZE the shell handler factory**

**Cause:** An internal error occurred while initializing the shell handler factory.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19066: Unable to set up the default shell handler factory.**

**Cause:** An internal error occurred while setting up the default shell handler factory.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19067: Unable to navigate to the page. Page creation might have failed or an error occurred while attempting to load the new page. Open your Manage Pages dialog box to see if the page exists. If the problem persists, contact your administrator.**

**Cause:** An error occurred trying to reference the newly created page (the page may not have been created properly).

**Action:** Try to selecting the new page from the pages dropdown list. If the page is not listed, try creating the page again

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-19068: Unable to create page in the current scope**

**Cause:** An unexpected error occurred while trying to create a page in a scope.

**Action:** Ask your WebCenter administrator to resolve the issue.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19070: Unable to delete page {0} ({1})**

**Cause:** An attempt to delete a page failed. Either the page and/or its associated files (for example, ADFm page definition) have been modified but not saved

**Action:** Verify that the page is not being modified and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19071: Page {0} ({1}) not deleted properly. Unable to remove associated metadata.**

**Cause:** An attempt was made to delete a page when metadata associated with the page was in use.

**Action:** Try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19072: Unable to retrieve the list of users**

**Cause:** An attempt to retrieve the user list failed. Either the Identity store was corrupt or is inaccessible.

**Action:** Verify that the identity store is valid and accessible, and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19073: Unable to register page {0} (of scope {1}) for navigation**

**Cause:** An error occurred while registering the page {0}.

**Action:** Try to register the page again and if unsuccessful contact Oracle Support.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-19075: No users available**

**Cause:** No users found in the WebCenter Spaces identity store.

**Action:** Contact Oracle Support Services.

**Level:** 1



---

**Type:** WARNING

**Impact:** Other

**WCS-19077: Permission class {0} does not have proper constructor method**

**Cause:** The specified class does not have the required constructor

**Action:** Provide the required constructor in the specified class

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19079: Unable to process the security extension metadata**

**Cause:** The argument is not an instance of ExtensionPermissionMetadata

**Action:** Provide an instance of ExtensionPermissionMetadata as the argument

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19080: Unable to access permission class {0} in your project libraries**

**Cause:** Either the specified permission class does not exist or it is not in the correct location.

**Action:** Ensure that the specified permission class is in the correct location.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19082: Unable to load up the {0} service.**

**Cause:** An internal error occurred and the {0} service failed to load.

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19083: Access to permission class {0} is not allowed**

**Cause:** An attempt was made to access the specified permission class. Permission class {0} is not accessible.

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19084: Permission class {0} can not be instantiated**

**Cause:** An internal error occurred

**Action:** Contact Oracle Support Services.

**Level:** 1

---

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19085: Unable to instantiate the policy store for WebCenter Spaces**

**Cause:** An error occurred while trying to access the WebCenter Spaces policy store.

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19088: Failed to register application management beans**

**Cause:** Application management beans(MBean) registration failed. Either there are issues with OC4J or the application was not packaged properly.

**Action:** Restart OC4J or examine OC4J log files for further details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19089: Failed to unregister application management beans**

**Cause:** Application management beans(MBean) unregistration failed. Either the Mbeans were not registered or the Mbeans were already unregistered.

**Action:** Examine the OC4J log files for further details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19090: An unexpected error has occurred, unable to complete the export process.**

**Cause:** The export process failed due to an internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19101: Unable to save the export archive on the local file system due to an unexpected error.**

**Cause:** Unexpected error occurred while saving the export archive on the local file system.

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19102: Unexpected error occurred while exporting the security policy. Unable to export the policy store.**

---

**Cause:** An unexpected error occurred while exporting policy store metadata to the local file system.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19104: Unable to export connection details for external application with ID {0}**

**Cause:** An internal error occurred. Unable to retrieve details for an external Application appearing in the Oracle WebCenter Spaces provides an open architecture to many different identity stores. Applications pane in the Sidebar

**Action:** Ask your WebCenter administrator to clean up external applications appearing in the Sidebar or reconfigure the external application connection using Enterprise Manager.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19105: Unable to find connection details for external application with ID {0}**

**Cause:** No connection details found for external application with the specified ID.

**Action:** Remove the external application link associated with the specified ID from the Applications pane in the Sidebar.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-19106: Unable to save preference settings**

**Cause:** An error occurred while attempting to save preferences settings to the metadata store.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19107: Invalid date format {0} retrieved from the preference store.**

**Cause:** An attempt was made to retrieve date information but the source date format was invalid.

**Action:** Verify whether the date format source returns the correct date format.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-19108: Invalid time format {0} retrieved from the preference store.**

**Cause:** An attempt was made to retrieve time information but the source time format was invalid.

**Action:** Verify whether the time format source returns the correct time format

---

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-19109: Unable to find service.**

**Cause:** Unable to find the service metadata in the Oracle WebCenter Framework

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19119: Unable to add the new link : {0}**

**Cause:** An attempt to add a new link {0} to the metadata store failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19120: Unable to add link as no proper handler found for the selected resource type**

**Cause:** An attempt to add a new link but the resource being added is neither a task flow or an external application.

**Action:** Only task flows or external application link can be included.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19121: Unable to retrieve the shell configuration metadata**

**Cause:** The metadata file is corrupt or missing.

**Action:** Ensure that the file exists and complies with the schema. Alternatively, contact your WebCenter administrator for assistance.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19122: Invalid shell panel name**

**Cause:** The shell panel name was probably NULL.

**Action:** Provide a valid shell panel name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19123: Unable to retrieve the shell handler for the current request {1}**

**Cause:** The shell handler was not set for the current request

---

**Action:** Verify the URL and that the WebCenter shell filter is configured to handle requests of this kind

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-19124: Unable to save changes to shell metadata**

**Cause:** An error occurred while saving the shell metadata document.

**Action:** Ensure that the shell metadata document is not corrupt and is writeable and personalizable.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19125: Account for user {0} is disabled**

**Cause:** The account for user {0} account is disabled.

**Action:** Ask the WebCenter administrator to activate the account.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19126: Account for user {0} is inactive**

**Cause:** The account for user {0} is disabled.

**Action:** Ask the WebCenter administrator to activate the account.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19127: The account for user {0} is locked**

**Cause:** The account is locked for user {0}

**Action:** Ask the WebCenter administrator to unlock the account.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19128: Password has expired for user account {0}**

**Cause:** Password for this user has expired

**Action:** Contact the WebCenter administrator for assistance.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19129: Incorrect Old Password for user account {0}**

**Cause:** The old password specified for this user is not correct.

---

**Action:** Enter the correct password

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19130: Password for user account {0} is null**

**Cause:** No password was specified.

**Action:** Enter a valid password.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19131: Error occurred granting permissions to user {0} for the newly created page {1}**

**Cause:** An unexpected error occurred while granting the user permission

**Action:** Contact the WebCenter administrator

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-19132: Unable to retrieve the permission target for page {0}**

**Cause:** An unexpected error occurred. The ADFm page definition of the page may be missing

**Action:** Ensure that the page definition exists and is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-19133: Unable to determine the tab in focus**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19134: Unable to hide a tab, locked by another user**

**Cause:** An attempt was made to hide a tab that is currently locked by another user.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19135: No tab selected for hiding**

**Cause:** Unable to determine which tab has focus.

---

**Action:** Select the tab you want to hide and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19136: Unable to hide the tab.**

**Cause:** An attempt was made to hide the last open tab.

**Action:** Open some other tab and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19137: Unable to determine the tab focus for hiding**

**Cause:** Unable to determine which tab has focus.

**Action:** Select the tab you want to hide and try again. Alternatively, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19138: Unable to encode the value {1} of parameter {0} using encoding format {2}**

**Cause:** The encoding format was unexpectedly invalid.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19139: Unable to decode the value {1} of parameter {0} using encoding format {2}**

**Cause:** The encoding format was unexpectedly invalid.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19140: Unable to update the page titled {0} ({1})**

**Cause:** An error occurred while saving the changes.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19141: Unable to save changes to the metadata store**

**Cause:** An error occurred while saving the changes.

---

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19142: Role mapping SPIs are throwing exception**

**Cause:** An internal occurred error while accessing role mapping SPIs.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19143: Unable to retrieve the catalog for adding applications**

**Cause:** An attempt to access the external application catalog failed. Either the external application catalog is not configured or configuration details are unavailable.

**Action:** Check whether the ext-app-catalog attribute is configured in webcenter-config.xml

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19144: Role name for user account is null or contains invalid characters**

**Cause:** Either the role name was left blank or the role name contained invalid characters.

**Action:** Enter a valid role name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19145: Operation succeeded with errors. The mapping of roles failed**

**Cause:** Changes in services failed due to the following errors

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19146: Grant role completed with errors The mapping of roles failed in scope {0}**

**Cause:** Changes in services failed due to the following errors

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other



---

**WCS-19147: Page path can not be null**

**Cause:** The specified page path is null or an empty string.

**Action:** Provide a valid string for the page path.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19148: Cannot get the service categories metadata from the application metadata**

**Cause:** Service category metadata has not been defined in the application metadata

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19149: Cannot get metadata for all services from the application metadata.**

**Cause:** All service metadata has not been defined in the application metadata.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19150: Cannot get metadata for configurable services from the application metadata**

**Cause:** Metadata for configurable services has not been defined in the application metadata.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19151: Cannot find a service with the ID {0}**

**Cause:** No definition exists for a service with the specified service identifier

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19154: This exception is due to one or more of the following exceptions -**

**Cause:** One or more services configurations have failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Other

**WCS-19157: Group space {0} may have been deleted or renamed**

**Cause:** An attempt was made to access a group space that has been deleted or renamed.

**Action:** Contact the group space moderator or try searching for the group spaces.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19158: Cannot personalize visibility of page {0} in group space {1}**

**Cause:** A personalization attempt failed. Either the backing store could not be accessed or some other personalization operation was performed simultaneously.

**Action:** Try the operation again. If the problem persists, contact your WebCenter administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19159: Unable to save page creation**

**Cause:** An attempt to save the new page failed. Either the back-end store could not be accessed or another page was created simultaneously.

**Action:** Try the operation again. If the problem persists, contact your WebCenter administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19160: Unable to save the personal sequence of pages in scope {0}**

**Cause:** An attempt to personalize the page sequence failed. Either the back-end store could not be accessed or some other personalization operation was performed simultaneously

**Action:** Try the operation again. If the problem persists, contact your WebCenter administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19161: Unable to save the change in sequence of pages in scope {0}**

**Cause:** An attempt to change page sequence failed. Either the back-end store could not be accessed or a similar operation was performed simultaneously.

**Action:** Try the operation again. If the problem persists, contact your WebCenter administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WCS-19162: Revoke role completed with errors The mapping of roles failed**

**Cause:** Changes in services failed due to the following errors

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19163: Scope is NULL for Security Manager**

**Cause:** Scope identifier passed to the security manager is NULL.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19164: The security policy in the archive file was found to be invalid.**

**Cause:** The imported security policy file was found to be invalid.

**Action:** Export the data again and try the import operation again.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-19165: The security policy in the archive file to be imported is invalid as it contains more than one jazn-policy node.**

**Cause:** The imported security policy file is invalid as it contains more than one jazn-policy node.

**Action:** Export the data again the import operation again.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-19166: The security policy in the archive file to be imported is located on a read-only file system and this means the data cannot be updated.**

**Cause:** The imported security policy file is located on a read-only file system and this means the data cannot be updated.

**Action:** Export the data again and try the import operation again.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-19167: Failed to import security configuration from the selected archive.**

**Cause:** An unexpected error occurred while updating the deployed application in the import source archive.

**Action:** Check the logs for details of the error. Alternatively, contact Oracle Support Services.

**Level:** 1

---

Type: WARNING

Impact: Other

**WCS-19168: Role {0} is created successfully but failed to copy the permissions from role {1}. The role {1} is not found.**

**Cause:** An attempt to create the role failed because the base role was not found.

**Action:** Check whether the base role is still available.

Level: 1

Type: ERROR

Impact: Other

**WCS-19169: An error occurred while trying to remove a role {0} from the policy store.**

**Cause:** The specified role does not exist in the policy store.

**Action:** Check the details of the error and try again.

Level: 1

Type: ERROR

Impact: Other

**WCS-19170: Application role {0} still used in the policy store**

**Cause:** The specified role is in use.

**Action:** Remove the usage of the role and try again.

Level: 1

Type: ERROR

Impact: Other

**WCS-19171: Application role {0} to be granted is not found**

**Cause:** Specified role was not found.

**Action:** Check the role name {0} and try again.

Level: 1

Type: ERROR

Impact: Other

**WCS-19172: Internal error while creating security manager for WebCenter Space {0}**

**Cause:** Unable to resolve the Scope GUID for Scope {0}

**Action:** Contact Oracle Support Services.

Level: 1

Type: INCIDENT\_ERROR

Impact: Other

**WCS-19173: New passwords for user account {0} do not match**

**Cause:** Passwords were entered incorrectly.

**Action:** Enter the correct passwords.

Level: 1

---

**Type:** ERROR

**Impact:** Other

**WCS-19174: Few of the mandatory resource(s) are in use. Please try again later.**

**Cause:** The lock, client is trying to release is already locked.

**Action:** Try after some time

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19175: Unable to release the lock on document {0}**

**Cause:** A call to release lock in the back-end has failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19176: Releasing the current lock on {0} failed**

**Cause:** The lock, client is trying to release is already released.

**Action:** Acquire the lock again to release.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19177: Name Cannot Be Null**

**Cause:** Name Cannot Be Null

**Action:** Enter a User or Group

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-19178: User Not Found**

**Cause:** User Not Found

**Action:** Enter a username

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-19179: Group not found or multiple groups with the same name exist.**

**Cause:** Group not found or multiple groups with the same name exist

**Action:** Enter a Group

**Level:** 1

**Type:** WARNING

**Impact:** Other

---

**WCS-19180: User with this name doesn't exist**

**Cause:** User with this name doesn't exist

**Action:** Enter a role which has users

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-19181: Unable to read the application configuration metadata**

**Cause:** The metadata file could have got corrupt or removed

**Action:** Please ensure that the file exists and complies with the schema, or contact the administrator for assistance

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19182: Unable to move link/folder**

**Cause:** The metadata file could have got corrupt or removed

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19183: Unable to create folder {0}**

**Cause:** The metadata file could have got corrupt or removed

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19184: Unable to delete link/folder {0}**

**Cause:** The metadata file could have got corrupt or removed

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19185: Role cannot be created because it contains special characters or whitespace**

**Cause:** Creation of Role {0} failed because it contains special characters or whitespace

**Action:** Remove special characters used in your role, also remove any whitespace and try again.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-19186: Role {0} cannot be created, as the role of same name exists in the policy store**

**Cause:** Creation of Role {0} failed because policy store already contains a role of same name

**Action:** Try changing role name

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19187: Granting of Role {0} partially succeeded for identity {1}. Granting permissions for {2} failed. You can take actions regarding these warnings in group space settings.**

**Cause:** Granting of Role for certain Services failed due to RoleMapping Exception

**Action:** Please check the log for actual error stack.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19188: Revoking of Role {0} partially succeeded for identity {1}. Revoking permissions for {2} failed. You can take actions regarding these warnings in group space settings.**

**Cause:** revoking of Role for certain Services failed due to RoleMapping Exception

**Action:** Please check the log for actual error stack.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19189: Mapping the permissions {0} failed. You may want to try the operation again after some time or can contact Administrator.**

**Cause:** Granting of Role for certain Services failed due to RoleMapping Exception

**Action:** Please check the log for actual error stack.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19190: Fatal Error while granting role for certain services.**

**Cause:** Granting of Role for certain Services failed due to RoleMapping Exception

**Action:** Please check the log for actual error stack.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19191: User(s) - {0} has already been granted the role {1}.**

**Cause:** Current User / Role {0} has been already granted the application role.

---

**Action:** Don't Provision this user since it is already provisioned.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19192: Role has been granted with errors. You might want to contact Administrator or Remove/Grant Role again.**

**Cause:** Role was granted with errors.

**Action:** Contact the Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19193: Fatal Error while granting the role.**

**Cause:** Fatal Error while granting the role.

**Action:** Contact Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19194: Invitations were sent out but persisting the invited users data resulted in fatal error.**

**Cause:** Members Fatal Error while granting the role.

**Action:** Contact Administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19195: Page {0} cannot be found in the system**

**Cause:** The page may have been deleted or the page path is incorrect

**Action:** Specify a correct path to an existing page

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19196: {0} : Irresolvable error(s) occurred. You may want to contact Administrator with the error reference.**

**Cause:** Fatal Error occurred.

**Action:** Contacts the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19197: {0} : Unexpected error(s) occurred. You may want to contact Administrator with the error reference.**



---

**Cause:** Fatal Error occurred.  
**Action:** Contacts the administrator.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other

**WCS-19198: {0} : Unknown error(s) occurred. You may want to contact Administrator with the error reference.**

**Cause:** Fatal Error occurred.  
**Action:** Contacts the administrator.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other

**WCS-19199: {0} : Multiple errors occurred - {1}**

**Cause:** Fatal Error occurred.  
**Action:** Contacts the administrator.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other

**WCS-19200: Fatal error while removing some grants. Please contact Administrator with error reference.**

**Cause:** Fatal Error occurred.  
**Action:** Contacts the administrator.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other

**WCS-19201: Fatal error while removing the role. Please contact Administrator with error reference.**

**Cause:** Fatal Error occurred.  
**Action:** Contacts the administrator.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other

**WCS-19202: Revoking role was partially successful. You can try this operation again after some time or contact Administrator.**

**Cause:** Fatal Error occurred.  
**Action:** Contacts the administrator.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other

---

**WCS-19203: Fatal error while creating the role. Please contact Administrator with error reference.**

**Cause:** Fatal Error occurred.

**Action:** Contacts the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19204: Unable to save Invite message for group space {0} due to unknown errors. Please try later or contact administrator**

**Cause:** Error occurred while obtaining the invite message

**Action:** Try later or contact administrator

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19205: Unable to save member changes for a group space{0} due to unknown errors. Please try later or contact administrator**

**Cause:** Error occurred while saving the member changes

**Action:** Try later or contact administrator

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19206: Could not find security policy in the archive file being imported.**

**Cause:** The security policy file was not found in import archive.

**Action:** Export the data again and try the import operation again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19207: One or more mandatory roles are not found in the copied instance for scope {0}. Role Name: {1}**

**Cause:** One or more mandatory roles are not found in the copied instance.

**Action:** Add the mandatory role {1} in the security metadata to get the webcenter functionality or contact administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19208: Deletion of security metadata failed for scope {0}**

**Cause:** Deletion of roles for the current scope {0} has failed.

**Action:** Try later or contact administrator.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WCS-19209: An unexpected error occurred while trying to upload WebCenter logo to path {0}**

**Cause:** MDS StreamedObject creation failed for WebCenter logo

**Action:** Contact administrator for further assistance.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19210: The image upload failed as the image file you tried to upload was invalid. Provide a valid image file.**

**Cause:** Unable to upload the WebCenter logo as the file is null or not available.

**Action:** Upload a valid image file

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19211: An error occurred while trying to retrieve the templates to be used for page creation. Please contact Administrator with error reference.**

**Cause:** An unexpected error occurred.

**Action:** Contacts the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19212: An error occurred while trying to determine the template selected for page creation. Please contact Administrator with error reference.**

**Cause:** An unexpected error occurred.

**Action:** Contacts the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19213: Unable to persist customization for tag with webcenterId "{0}" in the Personal Sidebar**

**Cause:** An error saving customizations on the Personal Sidebar JSPX, or the tag with this webcenterId could not be located.

**Action:** Ensure that the customization is enabled on the Personal Sidebar JSPX, and the tag has a unique webcenterId

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19214: Failed to get the custom page permission for pageDef {0} for action {1}**

- 
- Cause:** An unexpected error occurred.  
**Action:** Contact the administrator.
- Level:** 1  
**Type:** ERROR  
**Impact:** Other
- WCS-19215: Failed to get the roles having permission {0}**  
**Cause:** An unexpected error occurred.  
**Action:** Contact the administrator.
- Level:** 1  
**Type:** ERROR  
**Impact:** Other
- WCS-19216: Failed to get the users having permission {0}**  
**Cause:** An unexpected error occurred.  
**Action:** Contact the administrator.
- Level:** 1  
**Type:** ERROR  
**Impact:** Other
- WCS-19217: Unable to get list of links**  
**Cause:** An error occurred while getting the list.  
**Action:** Contact Oracle Support Services.
- Level:** 1  
**Type:** INCIDENT\_ERROR  
**Impact:** Other
- WCS-19218: An error occurred while saving the page default settings. The settings may not have been saved.**  
**Cause:** An unexpected error occurred.  
**Action:** Contact the administrator.
- Level:** 1  
**Type:** ERROR  
**Impact:** Other
- WCS-19219: Unexpected error occurred while deleting the page**  
**Cause:** An internal error occurred  
**Action:** Contact Oracle Support Services.
- Level:** 1  
**Type:** INCIDENT\_ERROR  
**Impact:** Other
- WCS-19220: Search for role {0} resulted in more than one result. Please contact Administrator to get it rectified**

---

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19221: While provisioning the services, errors were encountered for following services - {0}. Check if these services have been configured correctly.**

**Cause:** While copying the services, errors were encountered for certain services.

**Action:** Contact administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19222: Unknown error in adding link to the table**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19223: Unknown error in retrieving the link information**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19224: Unknown error in updating the link information**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19225: Unknown error in deleting the link**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19226: Unable to close connection**

**Cause:** An unexpected error occurred.

---

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19227: Unexpected error occurred while restoring the page**

**Cause:** An internal error occurred

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19228: Unexpected error occurred while creating list of tabs**

**Cause:** An internal error occurred

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19229: Error occurred in getting the complete list of pages you can access.**

**Please contact the administrator.**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19230: Invalid page name**

**Cause:** Invalid page name

**Action:** Please enter a valid page name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19231: Unexpected error occurred while creating the page**

**Cause:** An internal error occurred

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19232: While provisioning the services, errors were encountered for following services - {0}. Check if these services have been configured correctly.**

**Cause:** While provisioning the services, errors were encountered for certain services.

---

**Action:** Contact administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19233: While renaming all the provisioned services, errors were encountered for following services - {0}.**

**Cause:** While renaming the group space, errors were encountered for certain services.

**Action:** Contact administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19234: While unprovisioning the services, errors were encountered for following services - {0}.**

**Cause:** While unprovisioning the services, errors were encountered for certain services.

**Action:** Contact administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19235: Unknown error occurred. Please contact Administrator.**

**Cause:** Unknown error occurred.

**Action:** Contact administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19236: The following service(s) are currently unavailable: {0}. If the problem persists contact your WebCenter administrator.**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19237: Unable to export the group space {0} as either the group space does not exist or being exported/imported by another user. Refresh the group space list and try again.**

**Cause:** Unable to acquire a lock on the scope of group space.

**Action:** Refresh the group space list and try export again. If the problem persist contact the administrator.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WCS-19238: Unable to export the group space template {0} as either the group space template does not exist or being exported/imported by another user. Refresh the group space template list and try again.**

**Cause:** Unable to acquire a lock on the scope of group space template.

**Action:** Refresh the group space template list and try export again. If the problem persist contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19239: Unable to import as required resources are not available. Group space(s) being replaced on the target application either do not exist or are being exported/imported by another user. Refresh the group space list and try again.**

**Cause:** Unable to acquire a global lock of group space to avoid creation, delete, rename or import of group space(s).

**Action:** Wait for some time and try import again. If the problem persist contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19240: Unable to import as required resources are not available. Group space template(s) being replaced on the target application either do not exist or are being exported/imported by another user. Refresh the group space template list and try again.**

**Cause:** Unable to acquire a global lock of group space template to avoid creation, delete, rename or import of group space template(s).

**Action:** Wait for some time and try import again. If the problem persist contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19241: Errors occurred in the page.**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19242: Unexpected error occurred while accessing copyright message.**

**Cause:** An internal error occurred

**Action:** Contact Oracle Support Services.

**Level:** 1



---

Type: ERROR

Impact: Other

**WCS-19243: Unexpected error occurred while accessing privacy URL.**

Cause: An internal error occurred

Action: Contact Oracle Support Services.

Level: 1

Type: ERROR

Impact: Other

**WCS-19244: Unexpected error occurred while accessing footer information.**

Cause: An unexpected error occurred.

Action: Contact the administrator.

Level: 1

Type: ERROR

Impact: Other

**WCS-19245: An error occurred while saving the page security settings. The settings may not have been saved.**

Cause: An unexpected error occurred.

Action: Contact Oracle Support Services.

Level: 1

Type: ERROR

Impact: Other

**WCS-19246: Error occurred while refreshing the table of pages.**

Cause: An unexpected error occurred.

Action: Contact Oracle Support Services.

Level: 1

Type: INCIDENT\_ERROR

Impact: Other

**WCS-19247: Modification of role operation not supported for scope {0}**

Cause: Currently the modification of role not supported.

Action: Contact the administrator.

Level: 1

Type: ERROR

Impact: Other

**WCS-19248: Group space {0} being exported is either online or being exported/imported by another user. Try exporting after sometime.**

Cause: Group space is either online or blocked by another user/process.

Action: Refresh the group space list and try export again. If the problem persist contact the administrator.

Level: 1

---

**Type:** ERROR

**Impact:** Other

**WCS-19249: Group space template {0} being exported is either online or being exported/imported by another user. Try exporting after sometime.**

**Cause:** Group space template is either online or blocked by another user/process.

**Action:** Refresh the group space template list and try export again. If the problem persist contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19250: Group space template {0} on the target application is either online or being exported/imported by another user. Try importing after sometime.**

**Cause:** Group space template either online or blocked by another user/process.

**Action:** Wait for some time and try import again. If the problem persist contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19251: You are trying to import group space(s) with an archive file that contains group space template(s). Check the archive file and try again.**

**Cause:** The archive file contains template(s) but attempt is to import group space(s).

**Action:** Use an archive file that contains group space(s) exported. Contact oracle support service for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19252: You are trying to import group space template(s) with an archive file that contains group space(s). Check the archive file and try again.**

**Cause:** The archive file contains group space(s) but attempt was to import group space template(s).

**Action:** Use an archive file that contains group space template(s) exported. Contact oracle support service for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19253: Cannot locate the document "{0}".**

**Cause:** The path is incorrect or it is not available in the system.

**Action:** Verify whether the path is correct and is available in the system.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-19254: Error occurred while reading the WebCenter environment configuration file {0}.**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19255: Unexpected error occurred while navigating to Group Space Administration page.**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19256: Error occurred while saving the folder.**

**Cause:** An unexpected error occurred while saving the folder.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19257: Unexpected error occurred while acquiring the write lock on the document {0}.**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19258: Error occurred while clearing the Deleted/Renamed Group Space Tab.**

**Cause:** Error occurred while clearing the Deleted/Renamed Group Space Tab.

**Action:** Error occurred while clearing the Deleted/Renamed Group Space Tab.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19259: Group space {0} on the target application is either online or being exported/imported by another user. Try importing after sometime.**

**Cause:** Group space either online or blocked by another user/process.

**Action:** Wait for some time and try import again. If the problem persist contact the administrator.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19260: The current process could not be executed. Please try again after some time.**

**Cause:** An unexpected error occurred while saving the WebCenter admin changes.

**Action:** Contact system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19261: Error occurred while saving the WebCenter Admin changes.**

**Cause:** An unexpected error occurred while saving the WebCenterAdmin changes.

**Action:** Contact system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19262: The WebCenter admin settings is being modified by another administrator. Please try again after some time.**

**Cause:** An unexpected error occurred while saving the WebCenter admin changes.

**Action:** Contact system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19263: Fatal error occurred while getting the roles for current scope.**

**Cause:** An unexpected error occurred while getting the roles.

**Action:** Please contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19264: Fatal error occurred while inviting user {0} for role {1}**

**Cause:** An unexpected error occurred while getting the members.

**Action:** Please contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19265: Fatal error occurred while getting members.**

---

**Cause:** An unexpected error occurred while getting the members.

**Action:** Please contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19266: Fatal error occurred while getting invitation message from the repository.**

**Cause:** An unexpected error occurred while getting message.

**Action:** Please contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19267: Error occurred while reading the list of tabs from persistence store.**

**Cause:** An unexpected error occurred while reading the list of tabs.

**Action:** Contact system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19268: Following error occurred while storing the list of tabs to persistence store - {0}**

**Cause:** An unexpected error occurred while storing the list of tabs.

**Action:** Contact system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19269: Error in processing the pages.**

**Cause:** Unexpected error occurred while adding the tab.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19270: Error in processing the pages.**

**Cause:** Unexpected error occurred while removing the tab.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19271: Error in processing the pages.**

---

**Cause:** Unexpected error occurred while finding the tab.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19272: Error in processing the pages.**

**Cause:** Unexpected error occurred while creating the menu model.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19273: Error in navigation.**

**Cause:** Unexpected error occurred while navigating to secondary tab.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19274: Error in processing the pages.**

**Cause:** Unexpected error occurred while preparing the children.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19275: Error in processing the pages.**

**Cause:** Unexpected error occurred while preparing the tab for current request.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19276: Error in navigation.**

**Cause:** Unexpected error occurred while getting the navigable path to the tab.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19277: An error occurred while changing the page visibility. Refresh the page list and retry.**

**Cause:** Unexpected error occurred while changing the tab's visibility.

---

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19278: Error in renaming the page.**

**Cause:** Unexpected error occurred while changing the page name.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19279: Error in creating a copy of the page.**

**Cause:** Unexpected error occurred while coping the page.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19280: The role name {0} is reserved, please use some other name.**

**Cause:** Unexpected error occurred while creating the role name.

**Action:** Try creating a role with some other name.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19281: Unexpected error occurred while refreshing list of pages.**

**Cause:** Unexpected error occurred while refresh.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19282: Unable to save the BusinessRole sequence of pages.**

**Cause:** An attempt to customize the BR page sequence failed. Either the back-end store could not be accessed or some other customization operation was performed simultaneously

**Action:** Try the operation again. If the problem persists, contact your WebCenter administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19283: Error in reordering the pages.**

**Cause:** Unexpected error occurred while reordering the pages.

---

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19284: Error in reordering the business-role pages.**

**Cause:** Unexpected error occurred while reordering the business-role pages.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19285: Error in reordering the tabs.**

**Cause:** Unexpected error occurred while reordering the tabs.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19286: Error in moving the page up.**

**Cause:** Unexpected error occurred while moving the page up.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19287: Error in moving the page down.**

**Cause:** Unexpected error occurred while moving the page down.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19288: Error in processing the pages.**

**Cause:** Unexpected error occurred while closing the tab.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19289: Unexpected error in closing tab(s).**

**Cause:** Unexpected error occurred while closing the tabs.

**Action:** Contact Oracle Support Services.



---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19290: Unexpected error in getting list of moderators.**

**Cause:** Unexpected error occurred while getting the list of moderators.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19291: Unexpected error occurred in getting the page Uri for the favorites.**

**Cause:** Unexpected error occurred while getting the Uri for the favorites.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19292: Unexpected error occurred in creating the new folder.**

**Cause:** Unexpected error occurred while creating a new folder.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19293: Unexpected error occurred while getting the list of favorites.**

**Cause:** Unexpected error occurred while getting the list of favorites.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19294: Unexpected error occurred while trying to navigate to bookmark.**

**Cause:** Unexpected error occurred while trying to navigate to bookmark.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19295: Error occurred while reverting the WebCenter Admin changes.**

**Cause:** An unexpected error occurred while reverting the WebCenterAdmin changes.

**Action:** Contact system administrator.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WCS-19296: The application failed to access backend data store and cannot process requests**

**Cause:** Access to backend data store failed

**Action:** Ensure backend data store containing WebCenter schema and MDS schema is accessible.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19297: The URL typed by current user is not accessible, so redirecting to the unAuthorized page**

**Cause:** The current user does not have privileges to see the current URL

**Action:** Please contact system administrator

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19298: Unexpected error occurred, please retry the operation**

**Cause:** An internal error occurred

**Action:** Retry the operation. Contact Oracle Support Services if the issue persists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19299: Unexpected error occurred while preparing the administration tabs**

**Cause:** An internal error occurred

**Action:** Retry the operation. Contact Oracle Support Services if the issue persists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19300: Unexpected error trying to restore the Login page**

**Cause:** An internal error occurred

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19301: Unexpected error trying to navigate to the Login page**

**Cause:** An internal error occurred

**Action:** Contact Oracle Support Services.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WCS-19302: Unexpected error trying to open the Login page for edit**

**Cause:** An internal error occurred

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19303: Unexpected error occurred while moving a page to top of the pages list**

**Cause:** Unexpected error occurred while moving a page to top of the pages list

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19304: Unexpected error occurred while moving a page to bottom of the pages list**

**Cause:** Unexpected error occurred while moving a page to bottom of the pages list

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19305: Drag and drop is not allowed for ungrouped view**

**Cause:** Drag and drop was attempted in ungrouped view

**Action:** Drag and drop operation is not allowed for ungrouped view

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19306: Reorder of personal pages is not allowed here**

**Cause:** A personal page was selected as either the drag source or the drop target

**Action:** Exclude personal pages from drag and drop operations

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-19307: Unexpected error occurred while creating mandatory document.**

**Cause:** An internal error occurred

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-19308: Failed to grant a role {1} to identity {0} in scope {2}**

**Cause:** Failed to find identity {0} in Identity Store while Granting a role {1} in scope {2}

**Action:** Create a new Identity {0} in Identity Store and try again

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-19309: Unexpected error retrieving services for configuration**

**Cause:** An unexpected error occurred

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19310: Unexpected error occurred while trying to retrieve list of languages**

**Cause:** Unexpected error occurred while trying to retrieve list of languages

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19311: Error occurred granting role {0} in {1}. Refresh the members list to see which users were added successfully. Some errors are displayed below. Contact your administrator for a complete list of errors.**

**Cause:** An internal error occurred

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19312: Identities : {0}, failed with the errors {1}**

**Cause:** An internal error occurred

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19313: Setting {0} role for {1} failed. Please contact Administrator**

**Cause:** An internal error occurred

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-19314: Group space template {0} being exported is seeded. Exporting seeded template is not allowed.**

**Cause:** Group space template is seeded.

**Action:** Refer to export documentation or contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19315: One or more page(s) of group space {0} is being edited by user(s). Please try export later.**

**Cause:** One or more group space page is in edit mode. Cannot export when sandbox is created.

**Action:** Close all the pages from edit mode or contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19316: One or more page(s) of group space {0} is being edited by user(s). Please try import later.**

**Cause:** One or more group space page is in edit mode.

**Action:** Close all the pages from edit mode or contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19317: An unexpected error has occurred while sending notification to the administrator.**

**Cause:** An unexpected error occurred

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19318: Granting of Role {0} partially succeeded for identity {1}. Granting permissions for {2} failed.**

**Cause:** Granting of Role for certain Services failed due to RoleMapping Exception

**Action:** Please check the log for actual error stack.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19319: Revoking of Role {0} partially succeeded for identity {1}. Revoking permissions for {2} failed.**

**Cause:** revoking of Role for certain Services failed due to RoleMapping Exception

---

**Action:** Please check the log for actual error stack.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19320: File {0} in location {1} already exists. Do you want to overwrite it?**

**Cause:** File already exists in the location where the export archive is being saved.

**Action:** Enter a new location or overwrite the file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19321: Issues were faced while provisioning the service(s) - {0}. Check the group space services settings page if these services have been provisioned.**

**Cause:** While provisioning the services, errors were encountered for certain services.

**Action:** Contact administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19322: You do not have sufficient permission to edit the page.**

**Cause:** Your permission to edit the page might have been revoked.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19323: The image file {0} you tried to upload was invalid. Provide a valid image file.**

**Cause:** Unable to upload the image as the file is null or invalid.

**Action:** Upload a valid image file

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19324: An error occurred while cleaning the tabs from persistence store for current user.**

**Cause:** An unexpected error occurred while cleaning the list of tabs.

**Action:** Contact system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19325: One needs to login to access this url {0}**

---

**Cause:** Public Users don't have access to this url

**Action:** Please login first.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19332: Unexpected error occurred while processing roles in {0}**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19333: Unexpected error occurred while processing users in {0}**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19334: Unexpected error occurred while retrieving all users who have been assigned {0} in {1}**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19336: Unexpected error occurred while retrieving enterprise roles for user {0}**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19337: Unexpected error occurred while retrieving application role {0}**

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19342: Unexpected error occurred while retrieving users / groups who have been granted application role {0}**

---

**Cause:** An unexpected error occurred.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19343: Unable to send notification to administrator(s). The reason is : {0}.**

**Cause:** The BPEL server is not configured

**Action:** Configure workflows.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19344: User(s) - {0} has already been invited to Group Space.**

**Cause:** An unexpected error occurred while inviting users.

**Action:** Contact system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19345: Errors occurred in inviting user(s) to join the group space {1} as role {0}.**

Please refresh the members list below to see the latest status about the invited users. Some of the errors are displayed below( Please note that following list may not be listing all the errors. For the complete list of errors, please contact the administrator).

**Cause:** An unexpected error occurred while inviting users.

**Action:** Contact system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19346: User {0} not invited to Group Space {1}.**

**Cause:** User {0} not invited to Group Space {1}.

**Action:** Contact system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19347: The default shell-config document cannot be read for looking up application-specific URL parameters, due to {0}.**

**Cause:** The metadata repository might be down or the document may have got corrupted.

**Action:** Verify that the metadata repository is up and the document contents are valid.

**Level:** 1



---

Type: WARNING

Impact: Other

**WCS-19348: Error occurred during permissions related operations. Refresh the roles screen to see the updated information. Contact your administrator for the list of errors.**

**Cause:** An unexpected error occurred during permission related operations.

**Action:** Contact system administrator.

Level: 1

Type: ERROR

Impact: Other

**WCS-19351: Couldn't send notification to administrator as server may be down or spaces workflows are not accessible. Try again after some time.**

**Cause:** Failed to connect to SOA server.

**Action:** Check if the SOA server is up or if spaces workflows are deployed on SOA server.

Level: 1

Type: ERROR

Impact: Other

**WCS-19352: Unable to complete the export process as required resources are not available. Another export or import process might be in progress. Please try export again after sometime.**

**Cause:** Unable to get a lock on the global scope file. Another export process or group spaces operation might be in progress.

**Action:** Try after sometime. If the problem persists, contact system administrator.

Level: 1

Type: ERROR

Impact: Other

**WCS-19353: The import archive contains new group space(s) exported without security. Importing new group spaces without security is not allowed.**

**Cause:** Import archive contains new group space(s) exported without security. Importing new group spaces without security is not allowed.

**Action:** Export the new group space(s) with security and import again. If the problem persists, contact system administrator.

Level: 1

Type: ERROR

Impact: Other

**WCS-19354: The page {0} (in {1}) cannot be copied due to {2}.**

**Cause:** An error occurred while trying to copy the page.

**Action:** Refine the logging level, retry the operation, and check the logs for more information about the error, or contact Oracle Support Services.

Level: 1

---

**Type:** ERROR

**Impact:** Other

**WCS-19355: Unable to make updates to the attributes of the page {0} due to {1}.**

**Cause:** An error occurred while trying to make updates to the page attributes.

**Action:** Refine the logging level, retry the operation, and check the logs for more information about the error, or contact Oracle Support Services.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-19356: Unable to open the requested page.**

**Cause:** An unexpected error while opening the page or while creating a copy of it for editing.

**Action:** Contact the administrator.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-19358: Identity(s) - {0} has already been added to Group Space.**

**Cause:** An unexpected error occurred while adding users.

**Action:** Contact system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19359: You cannot invite yourself as a member.**

**Cause:** Operation not allowed.

**Action:** Contact system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19360: Couldn't retrieve the role {0}. Please contact administrator.**

**Cause:** An unexpected error occurred.

**Action:** Contact system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19362: You cannot add yourself as a member.**

**Cause:** Operation not allowed.

**Action:** Contact system administrator.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WCS-19365: Unable to change password. Contact administrator.**

**Cause:** An unexpected error occurred while setting the password.

**Action:** Contact system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19366: Export aborted. The export process took more time than allowed to complete. Please use WLST to perform this export.**

**Cause:** Thread timeout occurred. Either export set is too large or policy store info to be exported is large.

**Action:** Try reducing the count of group space in export set or use WLST command to perform the export.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19367: Import aborted. The import process took more time than allowed to complete. Please use WLST to perform this import.**

**Cause:** Thread timeout occurred. Either import set is too large or policy store info to be imported is large.

**Action:** Try reducing the count of group space in import set or use WLST command to perform the import.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19369: Get Member Info not supported for scope**

**Cause:** Currently get Member Info not supported.

**Action:** Contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19370: You can not invite a group for the group space subscription**

**Cause:** Inviting group is not supported

**Action:** Please contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19371: Failed to read the notification message from backend datastore**

**Cause:** Notification message is null, try setting it

---

**Action:** Please contact the administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19372: Group name is empty**

**Cause:** Given group name is empty

**Action:** Please pass the correct group name

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19373: Granting of Role {0} failed for identities {1}.**

**Cause:** Exception occurred while granting a role {0} to identities {1}

**Action:** Please check the log for actual error stack.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19374: Grant of role {1} to group {0} failed for following users : {2}. These users already have the particular role.**

**Cause:** An internal error occurred

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19375: Group {0} is not found in Identity store**

**Cause:** Given group name is not found

**Action:** Please pass the correct group name

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19376: User(s) - {0} has already been granted role(s).**

**Cause:** User(s) already granted roles.

**Action:** User(s) already granted roles.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19377: Group(s) - {0} has already been granted role(s).**

**Cause:** Group(s) already granted role(s)

**Action:** Group(s) already granted role(s)

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19378: Unable to grant role mapping permissions for role {0} in scope {1}**

**Cause:** The role was not granted role mapping permissions. Review the underlying exception in the logs to determine the exact cause.

**Action:** Take action based on the underlying exception details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19379: Unable to drop role mapping permissions for role {0} in scope {1}**

**Cause:** There was an error while dropping role mapping permissions for the role. Review the underlying exception in the logs to determine the exact cause.

**Action:** Take action based on the underlying exception details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-19380: Unexpected error while restoring the Default Profile Gallery Page.**

**Cause:** There was an error while removing the profile page customization. Review the underlying exception in the logs to determine the exact cause.

**Action:** Take action based on the underlying exception details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-23001: unexpected error has occurred**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26001: Search Configuration Error: {0}**

**Cause:** A configuration error has been encountered.

**Action:** Refer to the error details and the documentation for how to debug this.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26021: Invalid Query {0}.**

**Cause:** An invalid query was sent.

---

**Action:** Query validity is dependent on the service running it. Refer to the query in the log and the documentation for the service involved to debug this.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26022: Contradiction caused when clause "{0}" is added to "{1}"**

**Cause:** An unexpected programming error occurred. This is not something that can be fixed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26023: The addition of criteria to {0} existing date criterion is not supported**

**Cause:** An unexpected programming error occurred. This is not something that can be fixed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26041: General Search Execution Error**

**Cause:** A general execution error has been encountered.

**Action:** Query execution error is dependent on the service running it. Refer to the Query in the log and the documentation for the service involved to debug this.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26061: General Search Response Error**

**Cause:** A general response error has been encountered.

**Action:** Query execution response error is dependent on the service running it. Refer to the Query in the log and the documentation for the service involved to debug this.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26062: Query results are immutable; removing elements from it is unsupported.**

**Cause:** A caller tried to remove an element from the result set.

**Action:** Inform the caller that this is not a supported function.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-26063: SQL ResultSet consumption failed with the message "{0}".**

**Cause:** A SQL ResultSet cannot be consumed.

**Action:** Refer to the underlying exception to debug this.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26064: Cannot call "remove" method before calling "next" method.**

**Cause:** Caller tried to call "remove" method of QueryResult class before calling "next" method.

**Action:** Inform the caller that this is an illegal operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26065: Cannot convert "{0}" value to "{1}".**

**Cause:** The target object had no "valueOf" method to convert the source.

**Action:** No action is needed; appropriate contingencies have been applied.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26066: Parameter type {0} cannot be converted into a primitive type.**

**Cause:** The conversion failed because the bean property was not of primitive type.

**Action:** No action is needed; appropriate contingencies have been applied.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26081: General Search Authentication Error**

**Cause:** A general authentication error has been encountered.

**Action:** Query execution authentication error is dependent on the service running it. Refer to the Query in the log and the documentation for the service involved to debug this.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26091: Search API Implementation error in {0} class**

**Cause:** An implementation error has been encountered.

**Action:** Report to the provider of the Search API Implementation.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-26101: An error occurred while parsing an XML document at {0}.**

**Cause:** The XML document in question may not be well-formed or valid with respect to the referred XML schema.

**Action:** Examine the XML document again and check the XML schema to make sure there are not any mistakes or typos.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26102: An error occurred while parsing the search configuration in adf-config.xml at {0}.**

**Cause:** The XML fragment within adf-config.xml may not be well-formed or valid with respect to what is expected for search configuration.

**Action:** Examine the adf-config.xml document again and check the documented XML schema to make sure there are not any mistakes or typos.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26103: An unexpected XML error occurred.**

**Cause:** Something with the underlying XML system or implementation of JAXP failed unexpectedly.

**Action:** Check the nested exception for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26121: A general MDS error has occurred.**

**Cause:** An MDS-related error has occurred. Something with the MDS setup is misconfigured.

**Action:** Check the nested exception for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26122: An MDS error has occurred because a Metadata Object by the name of {0} cannot be found.**

**Cause:** An MDS Metadata Object was not found.

**Action:** Check the details of the Metadata Object and check the MDS repository to confirm that it is there.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26123: Encountered "{0}" with message "{1}" when committing MDS changes.**



---

**Cause:** Something within the current MDS Session cannot be committed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26124: Saved Search Deletion aborted because the Metadata Object (MO) Reference for ID "{0}" is not found.**

**Cause:** The system is in an inconsistent state allowing deletion of non-existent MDS documents

**Action:** There is nothing to be done about this. No deletion is performed.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26125: Encountered "{0}" with message "{1}" while formulating the final MDS Condition.**

**Cause:** Some MDS conditions that are being joined caused a failure to come up with the final condition.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26126: MDS query result is null**

**Cause:** MDS query result set is null. The MDS repository might be unavailable.

**Action:** Perform the operation again after MDS repository becomes available again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26141: A configuration error has occurred for the Search service model. The offending configuration is {0}.**

**Cause:** The Search service keeps its configuration in adf-config.xml, connections.xml, and MDS.

**Action:** Check in the appropriate configuration files to see if there are any obvious erroneous data.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26142: A security error has occurred for the Search service model. The offense is {0}.**

**Cause:** The Search service model security maintained by the service caused a failure.

---

**Action:** Check the security settings for each underlying service to identify any anomalies.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26143: Failed to commit changes to Search preferences, encountering {0}.**

**Cause:** Some underlying MDS issues with the Preferences implementation is causing the failure.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26144: An error occurred while parsing the default full crawl interval "{0}".**

**Cause:** An internal error occurred while trying to instantiate a DatatypeFactory for parsing Duration values.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26145: An invalid full crawl interval "{0}" was specified in adf-config.xml.**

**Cause:** The fullCrawlInterval attribute of the crawl-properties element in adf-config.xml may not be well-formed or valid.

**Action:** Make sure that the fullCrawlInterval attribute value is in the duration format as defined in the W3C XML Schema 1.0.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26146: An invalid full crawl interval "{0}" was specified for service {1}.**

**Cause:** The fullCrawlInterval attribute of a service-crawl-properties element in adf-config.xml may not be well-formed or valid.

**Action:** Make sure that the fullCrawlInterval attribute value is in the duration format as defined in the W3C XML Schema 1.0.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26147: An error occurred while parsing the crawl-properties element in adf-config.xml.**

**Cause:** An internal error occurred while trying to parse the crawl-properties element in adf-config.xml.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26161: Encountered a message from MDS indicating unsupported operation while deleting a Saved Search with ID "{0}", MO Reference name "{1}", and MO Absolute Name "{2}".**

**Cause:** The deletion of a Saved Search triggered some MDS operation that is not supported on said Saved Search document.

**Action:** Contact Oracle Support Services

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26162: A saved search with name "{0}" already exists, use a different name.**

**Cause:** The name you provided is used already.

**Action:** Use a different name when saving your searches.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26163: Duplicated identifier found while adding a saved search with a identifier "{0}" with Metadata Object name "{1}"; replacing with "{2}".**

**Cause:** The system is in an inconsistent state where an old ID is used on a new Saved Search.

**Action:** This is a cautionary message only. Appropriate actions will be taken to fix the uniqueness issue.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26164: Encountered an MDS exception "{1}" with message "{2}" while querying for saved searches with condition "{0}".**

**Cause:** An underlying MDS exception occurred during the query execution.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26165: Failed to retrieve a Saved Search in MDS with Metadata Object reference name "{0}", and absolute name "{1}".**

**Cause:** This can be due to an MDS misconfiguration issue.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Other

**WCS-26166: Failed to retrieve most recent Saved Searches in MDS with Metadata Object reference name "{0}", and absolute name "{1}".**

**Cause:** This can be due to an MDS misconfiguration issue.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26167: Encountered an MDS exception "{2}" with message "{3}" while saving a saved search with Metadata Object name "{0}", and absolute name "{1}".**

**Cause:** This can be due to an MDS misconfiguration issue.

**Action:** Refer to MDS documentation to resolve a lookup failure with the given details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26168: Encountered an MDS exception "{2}" with message "{3}" while deleting a saved search with Metadata Object name "{0}", and absolute name "{1}".**

**Cause:** An underlying MDS exception caused this.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26169: Encountered an MDS reference exception "{1}" with message "{2}" while retrieving Saved Search Metadata Object reference in MDS with Metadata Object absolute name "{0}".**

**Cause:** An underlying MDS exception caused this.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26170: Saved Search Update aborted because the Metadata Object (MO) Reference for ID "{0}" is not found.**

**Cause:** This can be due to an MDS misconfiguration issue.

**Action:** Refer to MDS documentation to resolve a lookup failure with the given details.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26171: Encountered an MDS exception "{1}" with message "{2}" while creating a document with Metadata Object absolute name "{0}".**

---

**Cause:** An underlying MDS exception caused this.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26181: Failed to retrieve UI Metadata in MDS with Metadata Object reference name "{0}", and absolute name "{1}".**

**Cause:** This can be due to an MDS misconfiguration issue.

**Action:** Refer to MDS documentation to resolve a lookup failure with the given details.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26182: Encountered an MDS exception "{2}" with message "{3}" while adding a UI Metadata with identifier "{0}" and Metadata Object name "{1}".**

**Cause:** An underlying MDS exception caused this.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26183: Encountered an MDS exception "{1}" with message "{2}" while querying for UI Metadata with condition "{0}".**

**Cause:** An underlying MDS exception caused this.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26184: Encountered an MDS reference exception "{1}" with message "{2}" while looking up UI Metadata Object reference in MDS with Metadata Object absolute name "{0}".**

**Cause:** An underlying MDS exception caused this.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26185: Encountered an MDS exception "{0}" with message "{1}" while creating default service list in MDS.**

**Cause:** An underlying MDS exception occurred during the creation of the service list in the Search UI Metadata.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26186: Encountered an MDS exception "{1}" with message "{2}" while updating UI Metadata Object in MDS with Metadata Object absolute name "{0}".**

**Cause:** An underlying MDS exception occurred during the update of the the Search UI Metadata.

**Action:** The update by this user will be lost. Refresh the page and continue.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26201: Encountered "{2}" with message "{3}" when loading QueryManager Class "{0}" for service "{1}" in Extension Handler.**

**Cause:** Any one of the possible exceptions resulting from loading a class using reflection occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26202: Search Extension Registry loading failed, encountering "{0}" with message "{1}".**

**Cause:** There may be misconfiguration in the adf-config.xml file.

**Action:** Check your adf-config.xml to see if the Search extension registry is declared. Make sure that the version numbers match those specified in the documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26203: Cannot access children, encountering "{0}" with message "{1}".**

**Cause:** Encountered a Search exception when trying to extract children executors from a Query Federator

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26204: Failed in creating a Row QueryHandler for "{0}", encountering "{1}" with message "{2}".**

**Cause:** A run time or Search exception was encountered. This can be due to the creation process timing out or any service-specific creation failure.

**Action:** Contact Oracle Support Services.

**Level:** 1

---

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26205: {0} occurred during the preparation of Query Handler with identifier "{1}".**

**Cause:** The Query Handlers are prepared in parallel; the preparation failed because of underlying concurrency mechanism.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26206: Creation of Row QueryHandler did not complete within the time limit for executor {0}.**

**Cause:** The time allowed to create a Row QueryHandler is not sufficient.

**Action:** If this problem is persistent, increase the value of prepareExecutionTimeoutMs parameter in adf-search-config section of adf-config.xml file.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26221: Search execution was interrupted because of "{0}" with message "{1}".**

**Cause:** The service search execution was interrupted because of a timeout of a failure.

**Action:** Examine the log to determine the root cause and take appropriate debugging steps.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26222: Search execution failure for service "{0}", encountering "{1}" with message "{2}".**

**Cause:** An exception occurred while executing search.

**Action:** Examine the log to determine the root cause and take appropriate debugging steps.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26223: Search executors not initialized due to null Query.**

**Cause:** Query is not set so no Query Executors have been initialized.

**Action:** No action is necessary; this is just a diagnostic message.

**Level:** 1

**Type:** WARNING

**Impact:** Other

---

**WCS-26224: Query Handler creation of {0} was interrupted.**

**Cause:** The Query Handler named took too long to be created and was timed out.

**Action:** Increase your prepareTimeoutMs value in the search-config section of the adf-config.xml file

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26321: {0} occurred during Search result transfer of service with identifier "{1}"**

**Cause:** An unexpected exception occurred when transferring search results after execution.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26322: Skipping consumption of a Date ComplexPredicate with 1 child because its type {0} is not AttributePredicate<Calendar> as expected.**

**Cause:** A Date ComplexPredicate was passed down from the query that contains the wrong type for its single child.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26323: Skipping consumption of a Date ComplexPredicate with 2 children because their types {0} and {1} are not AttributePredicate<Calendar> as expected.**

**Cause:** A Date ComplexPredicate was passed down from the query that contains the wrong type for both its children.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26324: Skipping consumption of a Date ComplexPredicate with {0} children because we only support at most two.**

**Cause:** Too many children are passed down the Date ComplexPredicate when we can only handle two.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26325: Execution of the search query to show all rows did not complete within the time limit for executor {0}.**



---

**Cause:** The time allowed to execute the search query to show all rows is not sufficient.

**Action:** Increase the value of showAllExecutionTimeoutMs parameter in adf-search-config section of adf-config.xml file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26326: Execution of the search query did not complete within the time limit for executor {0}.**

**Cause:** The time allowed to execute the search query is not sufficient.

**Action:** If this problem is persistent, increase the value of executionTimeoutMs parameter in adf-search-config section of adf-config.xml file.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26327: Query execution failed for {0}.**

**Cause:** Query execution failed.

**Action:** Examine the log files to extract the root cause to identify the proper debugging steps.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26341: Search UI Metadata Lookup Failed: {0}**

**Cause:** The UI Metadata document necessary for rendering Search views could not be found.

**Action:** Refer to the error messages presented in the dialog box and act accordingly.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26342: Search UI Metadata Update Failed: {0}**

**Cause:** The UI Metadata document necessary for rendering Search views could not be updated (customized).

**Action:** Refer to the error messages presented in the dialog box and act accordingly.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26343: Search Options Update Failed**

**Cause:** An MDS error caused the update of search options to fail.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26361: Failed to update the last used date / time of saved search with ID "{0}".**

**Cause:** An MDS error caused the update of the Saved Search document to fail when updating the last accessed date.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26362: Saved Search Update Failed**

**Cause:** An error occurred when trying to update a Saved Search.

**Action:** Refer to the error messages presented in the dialog box and act accordingly.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26363: Saved Search Creation Failed**

**Cause:** An error occurred when trying to create a Saved Search.

**Action:** Refer to the error messages presented in the dialog box and act accordingly.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26364: Saved Search Deletion Failed**

**Cause:** An error occurred when trying to delete a Saved Search.

**Action:** Refer to the error messages presented in the dialog box and act accordingly.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26365: Failed to delete saved search with ID "{0}".**

**Cause:** An MDS error caused the deletion of the Saved Search document to fail.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26366: Failed to update the sharing setting of saved search with ID "{0}".**

---

**Cause:** An MDS error caused the update of the Saved Search document to fail when updating the sharing setting.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26367: Saved search with ID "{0}" could not be found.**

**Cause:** Saved search was deleted by another user.

**Action:** Refresh page to get updated list of saved searches.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26381: Resource ID is not available to show the resource.**

**Cause:** A link to render a resource did not carry the unique identifier for that resource and therefore could not perform the rendering.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26391: Encountered an exception "{2}" with message "{3}" while populating Data Flavor "{0}" of "{1}" class.**

**Cause:** Failed to populate the given Data Flavor in the Resource Catalog Adapter.

**Action:** Examine the log for the root cause and take appropriate debugging steps.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26392: Failed to initialize Search service context DirContext Schema with message "{0}"**

**Cause:** A naming exception was encountered when binding attributes while initializing the Resource Catalog schema for the Search service.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-26393: Failed to get attributes of resource "{0}"**

**Cause:** Failed to get attributes of a given resource.

**Action:** Examine the log for the root cause and take appropriate debugging steps.

**Level:** 1

**Type:** WARNING

---

**Impact:** Other

**WCS-26401: Encountered "{0}" during proxy login with application entity "{1}" to Oracle SES at [{2}], as search user "{3}".**

**Cause:** The proxy login operation encountered error. Some underlying exception is causing the error.

**Action:** Refer to the root exception and identify the proper debugging steps.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26402: Received status "{0}" during proxy login with application entity "{1}" to Oracle SES at [{2}], as search user "{3}". Defaulting to public.**

**Cause:** The application entity may not have been provisioned in the identity management system used by SES, or its password may have been expired.

**Action:** Log on to the Oracle SES administration tool and make sure that the application entity has been provisioned. Then make sure that the account is enabled on the identity management system and has not expired.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26421: Failed to initialize data group ID from {0} in {1}, encountering {2}**

**Cause:** Either the group ID in question does not exist or SES is down.

**Action:** Make sure that SES is up and check the group IDs present on SES.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26422: Failed to discover attributes from {0} in {1}, encountering {2}**

**Cause:** Some underlying exception is causing the discovery of attributes from SES to fail.

**Action:** Refer to the root exception and identify the proper debugging steps.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26423: No attributes discovered from {0} in {1}**

**Cause:** The SES instance in question does not offer any attributes to query on.

**Action:** Confirm that Oracle SES is up.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26424: Failed to discover info source nodes from {0} in {1}, encountering {2}**

---

**Cause:** Some underlying exception is causing the discovery of info source nodes of SES to fail.

**Action:** Refer to the root exception and identify the proper debugging steps.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26441: Retrieving the SES Reference failed with Connection Architecture**

**Cause:** Something occurred when getReference of the SesReferenceable is called.

**Action:** Refer to the root exception and identify the proper debugging steps.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26442: Looking up the SES Connection failed with Connection Architecture**

**Cause:** Encountered a JCA ResourceException when calling getConnection on the connection factory for Searchlets.

**Action:** Refer to the root exception and identify the proper debugging steps.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26443: Connection entry "{0}" not found**

**Cause:** The specified connection entry is not in connections.xml

**Action:** Add the specified connection entry to connections.xml

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26444: Invalid value for addrType attribute in "{1}" entry. Expected value is "{0}"**

**Cause:** Incorrect value for addrType attribute found in connections.xml

**Action:** Update connections.xml with the correct value for addrType attribute

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26461: Failed to marshal SES Filter for Advanced Search due to JAXB issues - {0}**

**Cause:** A JAXB problem has caused the marshalling of an SES filter before sending it to SES for execution.

**Action:** Examine the log to look at the XML structure to verify validity.

**Level:** 1

**Type:** WARNING

---

**Impact:** Other

**WCS-26462: SES Search Execution failed, encountering "{0}" with message "{1}".**

**Cause:** The cause is embedded in the Exception and can be SES-specific.

**Action:** Examine the log files to extract the root cause to identify the proper debugging steps.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26463: Can not convert SES Result Element value from {0} to {1}**

**Cause:** Conversion from SES Result Element value failed.

**Action:** No action is needed. The conversion will default to using String

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26464: Cannot find attribute mapping for column {0}**

**Cause:** You have specified a column ID that cannot be found in the list of SES attributes.

**Action:** Examine your SES installation and make sure the attribute has a valid column ID.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26465: Failed to create JAXBContext using package {0}**

**Cause:** A JAXBContext instance could not be created for the SES cluster deserializer.

**Action:** Make sure that the required files can be found in the specified package and that the required classes can be loaded from the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26466: Failed to unmarshal byte stream into Cluster**

**Cause:** Unmarshalling failed because a JAXBContext instance could not be obtained.

**Action:** Make sure that the required files can be found in the specified package and that the required classes can be loaded from the classpath.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26501: Creation of the Tags service failed.**

---

**Cause:** The Tags service is loaded by reflection. Something may have happened to cause that to fail.

**Action:** Check whether the class name logged is accessible through the class path of the WebCenter Web application.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26502: Query Federator for the Tags service not created because a Tags Service cannot be created.**

**Cause:** The creation of the Tags service was unsuccessful causing the subsequent creation of a Row Query Federator for Tagging to fail.

**Action:** Check for /META-INF/tagging-class-config.properties and verify that a correct accessible class is specified.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26503: findSystemResources failed because of invalid arguments passed in to the method: keywords ({0}).**

**Cause:** One of the input arguments to findSystemResources was invalid.

**Action:** Make sure that arguments passed in to findSystemResources are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26504: findSystemTags failed because of invalid arguments passed in to the method: keywords ({0}).**

**Cause:** One of the input arguments to findSystemResources was invalid.

**Action:** Make sure that arguments passed in to findSystemTags are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26505: lookupTag failed because of invalid arguments passed in to the method: tagName ({0}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26506: findFilteredPersonalTags failed because of invalid arguments passed in to the method: userId ({0}), filter ({1}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26507: findTopFilteredSystemTags failed because of invalid arguments passed in to the method:userId({0}), filter ({1}), count({2}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26508: findTopFilteredPersonalTags failed because of invalid arguments passed in to the method: userId ({0}), filter ({1}), count({3}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26509: findAllTopFilteredSystemTags failed because of invalid arguments passed in to the method:userId({0}), filter({1}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26510: findAllTopFilteredPersonalTags failed because of invalid arguments passed in to the method: userId ({0}), filter ({1}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26511: findSystemTags failed because of invalid arguments passed in to the method: userId ({0}), filter ({1}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26512: findRelatedSystemTagsByTag failed because of invalid arguments passed in to the method: userId ({0}), tagWords ({1}).**



---

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26513: findRelatedSystemTags failed because of invalid arguments passed in to the method: serviceId ({0}), resourceId({1}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26514: findRecommendedTags failed because of invalid arguments passed in to the method: serviceId ({0}), resourceId ({1}), userId ({2}), count ({3}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26515: deleteTag failed because of invalid arguments passed in to the method: tag ({0}).**

**Cause:** One of the input arguments is invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26516: deletePersonalTags failed because of invalid arguments passed in to the method: userId ({0}), tagWord ({1}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26517: renamePersonalTags failed because of invalid arguments passed in to the method: userId ({0}), oldTagWord ({1}) newTagWord({2}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-26518: renamePersonalTags failed because of invalid arguments passed in to the method: userId ({0}), tagWord ({1}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26519: getTagsByName failed because of invalid arguments passed in to the method: userId ({0}), tagWord ({1}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26520: lookupResource failed because of invalid arguments passed in to the method: serviceId ({0}), resourceId ({1}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26521: createNewResource failed because of invalid arguments passed in to the method: serviceId ({0}), resourceId ({1}), resource name ({2}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26522: findFilteredPersonalResource failed because of invalid arguments passed in to the method: userId ({0}), filter ({1}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26523: findSystemResources failed because of invalid arguments passed in to the method: userId ({0}), userFilters ({1}), tagFilters ({2}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26524: findPersonalResources failed because of invalid arguments passed in to the method: userId ({0}), userFilters ({1}), tagFilters ({2}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26525: findRelatedSystemResources failed because of invalid arguments passed in to the method: serviceId ({0}), resourceId ({1}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26526: findRelatedUsers failed because of invalid arguments passed in to the method: serviceId ({0}), resourceId ({1}).**

**Cause:** One of the input arguments is invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26527: findRelatedUsersByTag failed because of invalid arguments passed in to the method: userId ({0}), tagWords ({1}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26528: createNewBookmark failed because of invalid arguments passed in to the method: userId ({0}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26529: lookupBookmark failed because of invalid arguments passed in to the method: serviceId ({0}), resourceId ({1}), userId ({2}).**

---

**Cause:** One of the input arguments was invalid.  
**Action:** Make sure that arguments passed in are all valid.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other

**WCS-26530: saveBookmark failed because of invalid arguments passed in to the method: bookmark ({0}).**

**Cause:** One of the input arguments was invalid.  
**Action:** Make sure that arguments passed in are all valid.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other

**WCS-26531: deleteBookmark failed because of invalid arguments passed in to the method: bookmark ({0}).**

**Cause:** One of the input arguments was invalid.  
**Action:** Make sure that arguments passed in are all valid.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other

**WCS-26532: A bookmark has been updated at the same time.**

**Cause:** There was a concurrent update on the bookmarks.  
**Action:** Ask user to retry the operation.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other

**WCS-26533: A database exception was thrown (for example., Unique Key constraint violation error).**

**Cause:** Tried to insert a duplicate object.  
**Action:** Retry the action.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other

**WCS-26534: Resource can not be displayed because the service with ID {0} is not found in the Service Registry.**

**Cause:** Service definition is not found in Service Registry.  
**Action:** Please register the service in Service Registry  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other

---

**WCS-26535: Tags service is not available due to {0}.**

**Cause:** Check the cause specified in the message.

**Action:** Act appropriately to reverse the cause.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26536: Resource can not be displayed because the authorizerClass {0} is not found.**

**Cause:** Class specified by authorizerClass is not found.

**Action:** Check the class path of the application to verify inclusion of the authorizerClass.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26537: findPopularTags failed because of invalid arguments passed in to the method: userId ({0}), order ({1}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26538: findPopularTags failed because of invalid arguments passed in to the method: userId ({0}), serviceId ({1}), resourceId ({2}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26539: findUpdatedResources failed because of invalid arguments passed in to the method: serviceId ({0}), date ({1}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26540: getTags failed because of invalid arguments passed in to the method: serviceId ({0}), resourceId ({1}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

---

Type: ERROR

Impact: Other

**WCS-26541: Error encountered while publishing to activity stream due to {0}.**

Cause: Error caused by Activity Stream

Action: Turn on the logging to finest to check the exception detail.

Level: 1

Type: ERROR

Impact: Other

**WCS-26542: Error encountered while retrieving user profile due to {0}.**

Cause: Error caused by Profile server

Action: Turn on the logging to finest to check the exception detail.

Level: 1

Type: ERROR

Impact: Other

**WCS-26543: Error encountered while renaming personal tags.**

Cause: The creation of the Tagging Service failed or input arguments were invalid

Action: Turn on the logging to finest to check the exception detail.

Level: 1

Type: ERROR

Impact: Other

**WCS-26544: Error encountered while deleting personal tags.**

Cause: The creation of the Tagging Service failed or input arguments were invalid

Action: Turn on the logging to finest to check the exception detail.

Level: 1

Type: ERROR

Impact: Other

**WCS-26545: Error encountered while finding personal tags.**

Cause: The creation of the Tagging Service failed or input arguments were invalid

Action: Turn on the logging to finest to check the exception detail.

Level: 1

Type: ERROR

Impact: Other

**WCS-26546: Error encountered while finding personal resources.**

Cause: The creation of the Tagging Service failed or input arguments were invalid

Action: Turn on the logging to finest to check the exception detail.

Level: 1

Type: ERROR

Impact: Other

---

**WCS-26601: No service ID or resource ID - cannot perform {0}.**

**Cause:** The consumption of the EditBookmarkBean from the view layer did not pass in the service or the resource IDs necessary.

**Action:** Check the view layer to make sure that the resourceId and the serviceId parameters are passed into the page flow scope.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26602: Cannot create a recommended list because the Tags service cannot be created.**

**Cause:** The creation of the Tags service was unsuccessful, so the recommended list could not be created.

**Action:** Check for /META-INF/tagging-class-config.properties and verify that a correct accessible class is specified.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26603: Bookmark cannot be loaded because Tags service cannot be created.**

**Cause:** The creation of the Tags service was unsuccessful, so the bookmark object could not be created.

**Action:** Check for /META-INF/tagging-class-config.properties and verify that a correct accessible class is specified.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26604: Bookmark saving failed because a Tags service cannot be created.**

**Cause:** The creation of the Tags service was unsuccessful, so the bookmark could not be saved.

**Action:** Check for /META-INF/tagging-class-config.properties and verify that a correct accessible class is specified.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26605: lookupBookmark failed because of invalid arguments passed in to the method: service ID ({0}), resource ID ({1}), and user ID ({2}).**

**Cause:** One of the input arguments to lookupBookmark was invalid.

**Action:** Make sure that arguments passed in to lookupBookmark are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WCS-26606: createBookmark failed because of invalid arguments passed in to the method: service ID ({0}), resource ID ({1}), resource name ({2}), and user ID ({3}).**

**Cause:** One of the input arguments to createBookmark was invalid.

**Action:** Make sure that arguments passed in to createBookmark are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26607: findRecommendedTags failed because of invalid arguments passed in to the method: service ID ({0}), resource ID ({1}), and user ID ({2}).**

**Cause:** One of the input arguments to findRecommendedTags was invalid.

**Action:** Make sure that arguments passed in to findRecommendedTags are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26608: This item has been tagged by the same user at the same time. Re-apply your changes.**

**Cause:** Concurrent update on the bookmarks.

**Action:** Retry the action.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26609: Some items whose tags are to be renamed have been updated at the same time. Re-apply your changes.**

**Cause:** Concurrent update on the bookmarks.

**Action:** Retry the action.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26610: Some items whose tags are to be deleted have been updated at the same time. Re-apply your changes.**

**Cause:** Concurrent update on the bookmarks.

**Action:** Retry the action

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26611: Tagging Button or Tagging Menu Item will not be rendered because the region "tagging-launch-dialog" is not included in the page.**

**Cause:** While building the page, the tagging button was added without adding a corresponding popup task flow.



---

**Action:** Check to make sure the "tagging-launch-dialog" region is indeed included in the page.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26612: The tagging component "{0}" was not rendered because the underlying Tags service was not available.**

**Cause:** The underlying Tags service was not available.

**Action:** Look for the errors causing the underlying Tags service to not be available and fix them.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26613: Error encountered while renaming personal tags.**

**Cause:** The creation of the Tagging Service failed or input arguments were invalid

**Action:** Turn on the logging to finest to check the exception detail.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26614: Error encountered while deleting personal tags.**

**Cause:** The creation of the Tagging Service failed or input arguments were invalid

**Action:** Turn on the logging to finest to check the exception detail.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26615: Error encountered while finding personal tags.**

**Cause:** The creation of the Tagging Service failed or input arguments were invalid

**Action:** Turn on the logging to finest to check the exception detail.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26616: Error encountered while finding personal resources.**

**Cause:** The creation of the Tagging Service failed or input arguments were invalid

**Action:** Turn on the logging to finest to check the exception detail.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26621: EncodeBegin error for TaggingPopup tag**

**Cause:** Catastrophic error

---

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26622: Error in Tagging Button tag usage - component {0} has attribute {1} whose value is {2}.**

**Cause:** The attribute mentioned in the error cannot be null, but no value was found for this attribute.

**Action:** Correct your tag usage.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26623: Component {0} does not support client listeners.**

**Cause:** Tried to add a client listener to a component that does not support client listeners.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26751: className property not found in: {0}**

**Cause:** The ResourceClassLoader could not find the class name in the properties file.

**Action:** Check the properties file to make sure the className is present.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26752: Encountered exception while attempting to instantiate concrete class for abstract class: {0}**

**Cause:** The ResourceClassLoader encountered an Exception

**Action:** Check log for more specific Exception information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-26753: CreateRating in Resource with ResourceID "{0}" failed because userRating "{2}" is outside maximum rating "{1}".**

**Cause:** The userRating argument to for this resource was invalid.

**Action:** Make sure that the userRating is less than the maximum rating for a resource.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-26754: GetRating with ResourceId {0}, ServiceId {1}, and UserId {2} failed because rating does not exist.**

**Cause:** This rating does not exist in the repository.

**Action:** Make sure rating exists before trying to get it.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26755: GetResource with ResourceId {0} and ServiceId {1} failed because resource does not exist.**

**Cause:** The Resource does not exist in the repository.

**Action:** Make sure Resource exists before trying to get it.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26756: jdbc/WebCenterDS data source not found: {0}**

**Cause:** The jdbc/WebCenterDS data source could not be found.

**Action:** Ensure that the jdbc/WebCenterDS data source is created.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-26757: Rating repository is not available.**

**Cause:** An error was encountered while checking if the rating repository was available.

**Action:** Check the log for errors that may have caused this.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-32003: Unable to load WebCenter Worklist configuration**

**Cause:** Connections context could not be acquired.

**Action:** Ensure that the connections.xml file is available and valid.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-32004: Worklist Connection "{0}" is an invalid WebCenter Worklist connection.**

**Cause:** The BPEL Worklist connection is invalid.

**Action:** Verify the specified Worklist connection is to a valid, accessible BPEL Workflow instance.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WCS-32005: The adf-config.xml element associated with the BPEL connection to be used by the To-Dos and Group Tasks service was not present.**

**Cause:** The application's adf-config.xml file was missing the adf-task-config element containing a BPELConnection name.

**Action:** Add the adf-config.xml entry associated with the To-Dos and Group Tasks service's BPEL connection using the appropriate configuration manipulation.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-32006: The adf-config.xml element associated with the BPEL connection to be used by the Worklist service was not present.**

**Cause:** The application's adf-config.xml file was missing the adf-worklist-config element containing one or more BPELConnection names.

**Action:** Add the adf-config.xml entry associated with the Worklist service BPEL connection using the appropriate configuration manipulation.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-32007: The BPEL Connection named "{0}" was not present in the connections.xml file. This will prevent the To-Dos and Group Tasks service from being able to function as a BPEL connection is required.**

**Cause:** The BPEL Connection matching the name specified in the adf-config.xml segment for the To-Dos and Group Tasks service requires adding to connections.xml.

**Action:** Add the BPEL Connection entry associated with the To-Dos and Group Tasks service adf-config.xml entry to connections.xml using the appropriate configuration manipulation.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-32008: The BPEL Connection named "{0}" was not present in the connections.xml file. This will prevent the Worklist service from being able to interact with the required this BPEL connection.**

**Cause:** The BPEL Connection matching the name specified in the adf-config.xml segment for the Worklist service requires adding to connections.xml.

**Action:** Add the BPEL Connection entry associated with the Worklist service adf-config.xml entry to connections.xml using the appropriate configuration manipulation.

**Level:** 1

**Type:** WARNING

**Impact:** Other

---

**WCS-32009: The Worklist service does not have a ConnectionName configuration entry in adf-config.xml that maps to a BPELConnection in connections.xml, therefore the Worklist service was not configured for this application.**

**Cause:** There was no Worklist service ConnectionName entry in adf-config.xml that maps to a corresponding BPELConnection name in connections.xml.

**Action:** Make sure there is a ConnectionName configuration entry in adf-config.xml in the adf-worklist-config element that maps to a BPELConnection entry in connections.xml using the appropriate configuration manipulation.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-32010: The To-Dos and Group Tasks service does not have an entry in adf-config.xml that maps to a BPELConnection in connections.xml, therefore the To-Dos and Group Tasks service was not configured for this application.**

**Cause:** There was no To-Dos and Group Tasks service ConnectionName entry in adf-config.xml that maps to a corresponding BPELConnection name in connections.xml.

**Action:** Make sure there is a ConnectionName configuration entry in adf-config.xml in the adf-task-config element that maps to a BPELConnection entry in connections.xml using the appropriate configuration manipulation.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-32011: The connection associated with connection name "{0}" was not of type BPELConnection. This will prevent the To-Dos and Group Tasks service from being able to use this connection.**

**Cause:** The To-Dos and Group Tasks service ConnectionName entry in adf-config.xml was not mapped to a corresponding BPELConnection name in connections.xml.

**Action:** Either recreate the connection to one of connection type BPELConnection in connections.xml, or update the To-Dos and Group Tasks service's adf-task-config adf-config.xml entry to refer to a BPELConnection.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-32012: The connection associated with connection name "{0}" was not of type BPELConnection. This will prevent the Worklist service from being able to use this connection.**

**Cause:** The Worklist service ConnectionName entry in adf-config.xml was not mapped to a corresponding BPELConnection name in connections.xml.

**Action:** Either recreate the connection to one of connection type BPELConnection in connections.xml, or update the Worklist service's adf-worklist-config adf-config.xml entry to refer to a BPELConnection.

**Level:** 1

**Type:** WARNING

---

**Impact:** Other

**WCS-32013: Unable to interact with the BPEL client APIs.**

**Cause:** The Worklist service was unable to interact with the BPEL client APIs.

**Action:** See the exception in the associated notification.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-32100: The WebCenter Worklist has queried the BPEL Worklist connection named "{0}", and encountered a WebCenter Executor error. Please see related exception for details. If the WebCenter Worklist is running in an Application Server, check to see if the wsm-pm application is up and running.**

**Cause:** Either, there is an issue with the BPEL Worklist instance being queried or, (if the WebCenter application is running in an Application Server) the wsm-pm application required by the Worklist is down.

**Action:** Validate the BPEL Worklist connection details in connections.xml, and check that the wsm-pm application process is up and running (if the WebCenter application is running in an Application Server).

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-32101: Cache not available.**

**Cause:** Cache is not initialized.

**Action:** Contact system administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-32102: Could not operate on cache object.**

**Cause:** Examine the associated Cache related exceptions that have been logged.

**Action:** Contact system administrator, if unable to resolve through examination of related logged Cache exception.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-32103: Unable to query BPEL repository.**

**Cause:** The Worklist service was unable to connect to the BPEL repository, as an exception occurred while querying the BPEL Client APIs.

**Action:** See the exception in the associated notification.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-33001: Exception while executing Query for Recent Activities "{0}" : "{1}".**

---

**Cause:** The execution of the search query for recent activities failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-33002: Unable to find any services to query.**

**Cause:** The Service Framework has not provided any services to query.

**Action:** Add services to application that can be searched for recent activity.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-33003: Exception while executing Search Query Thread for Recent Activities "{0}" : "{1}".**

**Cause:** The query of a specific service for recent activity has failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-33004: Unable to retrieve user preference "{0}".**

**Cause:** The user preferences could not be read.

**Action:** Check the WebCenter preference configuration and MDS settings.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-33005: Recency value of "{0} minutes" is too low (minimum value is 1 minute).**

**Cause:** The number of minutes considered to be recent is too low.

**Action:** Increase the recency value preference to greater than or equal to 1 minute.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WCS-33006: Search Execution API returned null.**

**Cause:** The search API used to query for recent activity returned a null object.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**WCS-33007: Service Extension for Recent Activities was not found.**

**Cause:** The WebCenter Service Extension for Recent Activities could not be found.

---

**Action:** Check the WebCenter configuration in adf-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-33008: View Layer API Exception: Exception {0}. Message: {1}.**

**Cause:** Unable to render the recent activity UI.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-33009: Exception reading from Recent Activity Cache: {0} : {1}.**

**Cause:** The data cache for recent activity for this user has failed.

**Action:** Clear the cache by clicking the Refresh button. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-33010: Invalid recent activity entry returned from service {0} with title "{1}".**

**Cause:** The service returning recent activity has responded with invalid data.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WCS-33011: Unhandled Error or Exception: {0} : {1}.**

**Cause:** The recent activity API has caught an unhandled Exception or Error, possibly thrown in an underlying service.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-33012: createExecutors timed out for all services or no services available.**

**Cause:** All searchable services have timed out or are not available.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-33013: Results found, but failed to be processed for service : {0}.**

**Cause:** Results from the given service are invalid and have been ignored.



---

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-33014: Search timed out or cancelled for {0}.**

**Cause:** The search for activity in the given service has taken too long to execute.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-33501: Unable to execute the search for recent activity. Search has not been provisioned.**

**Cause:** The WebCenter Recent Activity Service depends on the availability of the Search service to execute the search for recent activities, but the Search service has not been provisioned for the current scope.

**Action:** Provision the Search service for this scope.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-33502: The value given for the groupSpace parameter is not a valid group space scope.**

**Cause:** The task flow parameter groupSpace has been set to a scope that does not exist. If this application contains no groupSpace scopes, this parameter must be null.

**Action:** Edit the task flow parameter in the page definition to set the groupSpace parameter to a valid value (usually null).

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-33503: Unable to obtain recent activity data.**

**Cause:** The search may have timed out, failed, or been unable to find anything to search.

**Action:** Refresh the Recent Activity component using the refresh icon.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-33504: Recent Activity in the Personal Space requires a groupSpace taskflow parameter value to use for the search.**

**Cause:** Recent Activity cannot search the Personal Space.

**Action:** Edit the Recent Activities taskflow properties and specify a group space taskflow parameter.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34002: Item not found.**

**Cause:** Item did not exist in repository.

**Action:** Do not reference items that do not exist.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-34003: Item not found, ancestor depth is not valid.**

**Cause:** The depth of the ancestor was not valid.

**Action:** Check the depth of the node first.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-34004: This node is not in sync with the file system.**

**Cause:** The session contains stale file system information.

**Action:** Invoke refresh() or save() to synchronize the session with the file system.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-34005: This node does not have a primary item.**

**Cause:** Folders do not have primary items.

**Action:** Do not invoke getPrimaryItem() on a folder node.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-34007: Path not found: {0}.**

**Cause:** The method was invoked with an invalid path.

**Action:** Invoke the method with a valid path.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-34008: Unsupported repository operation.**

**Cause:** A method has been invoked that is not supported.

**Action:** Any code calling this method should be removed or skipped.

**Level:** 1

**Type:** WARNING

---

**Impact:** Other

**WCS-34013: Invalid file system adapter repository reference.**

**Cause:** The Reference provided to initialize the repository does not describe a file system connection or has incorrect parameters.

**Action:** Invoke the FSRepository constructor with a valid Reference constructed from FSRepository.getReference.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-34014: {0} is not a valid file system mount point.**

**Cause:** The mount point is not a valid file system directory.

**Action:** Invoke the repository constructor with a valid root directory.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-34015: {0} is not a known workspace in this repository**

**Cause:** Could not access the workspace, as the file system adapter does not support workspaces.

**Action:** Invoke login() with a null or empty workspace name.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-34016: The file system adapter does not accept login credentials**

**Cause:** Could not login as the file system adapter does not accept login credentials.

**Action:** Invoke login() with null credentials.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-34017: Impersonation is not allowed.**

**Cause:** Could not execute the impersonate method as the file system adapter does not support impersonation.

**Action:** Do not invoke the impersonate() method.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-34018: Cannot complete the delete operation.**

**Cause:** An unexpected file system error occurred during the delete operation.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-34019: Cannot complete the move operation.**

**Cause:** An unexpected file system error occurred during the move operation.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-34021: Cannot access the file system.**

**Cause:** There was an error reading a file.

**Action:** See the chained IOException for more details on this error.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34022: This property is not a REFERENCE.**

**Cause:** This property is not a REFERENCE.

**Action:** Do not invoke getNode() on this property.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-34023: Illegal single value access: property is multi valued.**

**Cause:** Accessed a single value property on a multi valued property.

**Action:** Do not access a single value property on a multi valued property.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-34024: Illegal multi value access: property is single valued.**

**Cause:** Accessed a multi value property on a single value property.

**Action:** Do not access a multi value property on a single value property.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-34025: XPath error**

**Cause:** Error occurred while processing XPath.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Other

**WCS-34026: Invalid XPath query**

**Cause:** The XPath query was invalid.

**Action:** Correct the XPath query.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-34035: An item with the same name already exists at the destination.**

**Cause:** An attempt was made to overwrite an existing item.

**Action:** Specify the overwrite option, or remove the item before attempting this operation.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-34036: Move prevented by constraint violation.**

**Cause:** Could not perform the requested move operation as it violates the constraints defined in the JCR specification.

**Action:** Verify that the target node is a valid parent and/or this node can be renamed.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-34037: Access denied**

**Cause:** Could not perform the specified action as it is not allowed on the path specified.

**Action:** Contact the system administrator.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-34038: The session has pending changes.**

**Cause:** The operation could not proceed as there are pending changes in the session.

**Action:** Invoke save() or refresh() before performing the operation.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-34047: Invalid parameter**

**Cause:** Could not parse a parameter to this call as it is invalid.

**Action:** Check and correct the parameters for this call.

---

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-34306: Error while executing a search.**

**Cause:** An unexpected error occurred while executing a search.

**Action:** Check the search criteria is valid and verify that the Portal instance is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34307: Invalid node type : {0}**

**Cause:** An invalid node type was specified for the search.

**Action:** Verify that the search query is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34308: Cannot determine the node type for the search.**

**Cause:** An unexpected error occurred while determining the node type for the search.

**Action:** Check the search query is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34310: Invalid search query.**

**Cause:** The XPath specified for the search was invalid.

**Action:** Ensure that the search query is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34311: An error occurred while building the search.**

**Cause:** An error occurred while building the search query.

**Action:** Ensure the search query is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34320: Property cannot be created for {0} as the data type, {1}, is invalid. Path: {2}; node ID: {3}; node site ID: {4}.**

**Cause:** The data type for the requested property was invalid.

**Action:** Specify a valid data type for the property, and retry.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34321: Primary item name for node type, {0}, cannot be returned. NodeTypeID: {1}; NodeTypeSiteID: {2}.**

**Cause:** The node type was invalid.

**Action:** Check if the requested node type exists in the repository.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34322: Property definitions of node type, {0}, cannot be determined.**

**Cause:** An error occurred while creating the property definitions.

**Action:** Check if the requested node type exists in the repository.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34323: Super types of node type, {0}, cannot be determined.**

**Cause:** An error occurred while creating the super types.

**Action:** Check the node type is valid and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34324: Primary item name for node type, {0}, cannot be determined.**

**Cause:** The node type was not found.

**Action:** Check the node type is valid and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34325: Node definitions for node type, {0}, cannot be determined.**

**Cause:** Node definition could not be created.

**Action:** Check the node type is valid and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34326: Super types of node type, {0}, cannot be determined. NodeTypeID: {1}; NodeTypeSiteID: {2}.**

**Cause:** The node type was not found.

**Action:** Verify that the requested node type exists in the repository.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34327: Invalid credentials.**

**Cause:** Session could not be created for the user.

**Action:** Verify that the credentials passed are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34328: Database connection could not be obtained.**

**Cause:** Could not access the database, which may be down.

**Action:** Verify that the Portal instance is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34329: Insufficient privileges to perform the operation.**

**Cause:** You did not have the sufficient privilege to perform this operation.

**Action:** Contact the Portal administrator to check your privileges.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-34330: The requested node type, {0}, does not exist.**

**Cause:** Could not locate the requested node type as it does not exist.

**Action:** Verify that the node type exists in the repository.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34331: Property definitions of node type, {0}, cannot be returned. NodeTypeID: {1}; NodeTypeSiteID: {2}.**

**Cause:** An error occurred while creating the property definitions.

**Action:** Check the node type is valid, verify that the Portal instance is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34332: Property, {0}, cannot be set for node type, {1}. NodeTypeID: {2}; NodeTypeSiteID: {3}.**

**Cause:** Property value was invalid.

**Action:** Provide a property value that is valid.



---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34333: Oracle data-source, {0}, cannot be looked up.**

**Cause:** The data-source was not available.

**Action:** Verify that the data-source is created correctly and is available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34335: The root nodes of the Portal repository cannot be obtained.**

**Cause:** An error occurred while listing the root nodes.

**Action:** Verify that the Portal instance is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34336: Statement/Connection objects cannot be closed.**

**Cause:** An error occurred while closing the statement or connection objects.

**Action:** Verify that the Portal instance is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34337: The child nodes of folder, {2}, cannot be obtained. Parent folder ID: {0}; folder site ID: {1}.**

**Cause:** A SQL exception occurred while trying to list the child nodes.

**Action:** Verify the folder ID, folder page group ID and path are valid, verify that the Portal instance is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34338: Property, {0}, is a single-valued property.**

**Cause:** The property was a single valued property.

**Action:** Verify the value for the property is a single value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34339: Unable to check if the session is live.**

**Cause:** An error occurred while checking whether the session is live.

**Action:** Verify that the Portal instance is up and running.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34340: The Portal session cannot be logged out.**

**Cause:** An error occurred while logging out of the Portal session; it is possible the Portal instance is no longer available.

**Action:** Verify that the Portal instance is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34341: Cannot determine UUID for node, {0}.**

**Cause:** An error occurred while determining the UUID of context node.

**Action:** Verify that the path is correct and that the node is referenceable.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34342: Cannot get the node, {0}.**

**Cause:** An error occurred while getting the requested node.

**Action:** Verify that the path is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34343: Cannot get the node for the given UUID, {0}.**

**Cause:** Error getting the requested node.

**Action:** Verify that the UUID is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34344: Cannot determine if item exists at given path, {0}.**

**Cause:** An error occurred while determining if the requested item exists.

**Action:** Verify that the path is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34346: Property definitions of node type cannot be determined. NodeTypeID: {0}; NodeTypeSiteID: {1}.**

**Cause:** An error occurred while creating the property definitions.

**Action:** Verify that the node type exists in the Portal repository.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34347: Property, {0}, cannot be set for node type. NodeTypeID: {1}; NodeTypeSiteID: {2}.**

**Cause:** Property value was invalid.

**Action:** Provide a property value that is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34348: Cannot retrieve all the node types from the Portal repository.**

**Cause:** An error occurred while retrieving the Portal node types.

**Action:** Verify that the Portal instance is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34349: Cannot get the properties for node with ID: {0}, site ID: {1}.**

**Cause:** An error occurred while obtaining the properties of the node from the repository.

**Action:** Verify that the node and node type are valid, and verify that the Portal instance is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34350: Cannot get the references for the requested node. Node ID: {0}; node site ID: {1}.**

**Cause:** An error occurred while obtaining the references for the requested node.

**Action:** Verify the node is valid, and verify that the Portal instance is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34351: Cannot get binary property value for property, {0}, that belongs to node, {1}.**

**Cause:** An error occurred while fetching the binary property of node.

**Action:** Verify that the path is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34352: Cannot get Portal property name for property ID: {0}.**

---

**Cause:** An error occurred while getting the Portal property name.

**Action:** Verify that the requested property is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34354: The Portal session could not be logged out.**

**Cause:** A SQL error occurred when attempting to log out.

**Action:** Verify that the Portal instance is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34355: Cannot determine the length of the given input stream.**

**Cause:** An error occurred while determining the length of the input stream.

**Action:** Verify that the input stream is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34356: Current operation is not supported for the single-valued property, {0}.**

**Cause:** The current operation could not be performed on a single property as single-valued properties are not supported by such an operation.

**Action:** This API cannot be invoked on a single-valued property.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34357: This node, {0}, cannot be referenced and hence, does not have a UUID property.**

**Cause:** The context node does not have a UUID property.

**Action:** Make this request on a referenceable node.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34358: Current operation is not supported for the multi-valued property, {0}.**

**Cause:** The current operation could not be performed on a multi-valued property as multi-valued properties are not supported by such an operation.

**Action:** This API cannot be invoked on a multi-valued property.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WCS-34359: This operation is not supported by the Portal repository.**

**Cause:** An error occurred while performing this action as the operation is not supported by the underlying Portal repository.

**Action:** Check the operation being attempted is a valid operation for the repository.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34360: The Portal repository has only 1 workspace, so this request is invalid.**

**Cause:** The underlying Portal repository has only one workspace.

**Action:** This is an invalid request since the repository is a single workspace repository. Retry with a valid request.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34361: Cannot convert length of property, {0}, to long.**

**Cause:** An error occurred while converting the length to the long data type.

**Action:** Verify the value of the property is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34362: Cannot parse the date value for property, {0}.**

**Cause:** An error occurred while parsing the date value.

**Action:** Verify the value of the property is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34363: The requested property cannot be found. Path of context node: {0}; Relative Path: {1}.**

**Cause:** The property was not found.

**Action:** Verify that the requested property is valid and that the path is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34364: The requested item, {0}, cannot found.**

**Cause:** An error occurred while getting the requested item.

**Action:** Verify that the item exists in the Portal repository.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-34365: The property, {0}, cannot be converted to a reference.**

**Cause:** The property could not be converted to a reference or was a multi-valued property.

**Action:** Verify that the property can be converted to a reference.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34366: {0} is a folder and hence, it does not have a primary item.**

**Cause:** The request could not be performed because folders cannot have primary items.

**Action:** This is an invalid request.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34367: The requested node was not found. Path of context node: {0}; Relative Path: {1}.**

**Cause:** The node was not found.

**Action:** Verify that the requested node is valid and that the path is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34368: The given path, {0}, is invalid.**

**Cause:** The specified path was invalid.

**Action:** Provide a valid path.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-34416: Error determining if child node, {0}, could be added.**

**Cause:** An error occurred while determining whether the child node could be added.

**Action:** Verify the node is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34417: Error determining if child node, {0}, based on type, {1}, could be added.**

**Cause:** An error occurred while determining whether a child node based on the given type could be added.

**Action:** Verify the node and type are valid.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34418: Error removing the child item, {0}, for node type, {1}.**

**Cause:** An error occurred while removing the child item.

**Action:** Verify item and node type are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34419: Error removing the property, {0}, for node type, {1}.**

**Cause:** An error occurred while removing the property.

**Action:** Verify the node type and property are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34421: The connection cannot be closed.**

**Cause:** The system encountered an unexpected error while trying to close a database connection.

**Action:** Verify that the Portal instance is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34422: The node types array object could not be stored in the cache.**

**Cause:** The system encountered an unexpected exception when trying to store the node types object in the cache.

**Action:** Contact the WebCenter administrator to check the status of the cache.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34423: The "all node types" node type iterator could not be stored in the cache.**

**Cause:** The system encountered an unexpected exception when trying to store the node type iterator in the cache.

**Action:** Contact the WebCenter administrator to check the status of the cache.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34424: The Portal node types linked list object could not be stored in the cache.**

---

**Cause:** The system encountered an unexpected exception when trying to store the Portal node types linked list object in the cache.

**Action:** Contact the WebCenter administrator to check the status of the cache.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34425: The cache region, {0}, has already been defined.**

**Cause:** The cache region has already been defined.

**Action:** No action is required as this is just indicating that the cache region has already been defined.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-34428: Generic cache exception when trying to retrieve object from cache.**

**Cause:** A cache exception occurred when trying to retrieve the object from the cache.

**Action:** Contact the WebCenter administrator to check the status of the Cache.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34429: Object cannot be stored in cache as the cache is full.**

**Cause:** The object could not be stored in cache because the cache was full.

**Action:** Contact the WebCenter administrator to check the status of the Cache.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34430: The root node does not have a parent node.**

**Cause:** The parent node was requested for a root node.

**Action:** Request the parent node of any node except the parent node.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34431: The node type iterator object cannot be removed from the cache.**

**Cause:** The node type iterator object could not be removed from the cache.

**Action:** Contact the WebCenter administrator to check the status of the cache.

**Level:** 1

**Type:** ERROR

**Impact:** Other



---

**WCS-34432: The node type name cannot be returned from the qualified name.**

**Cause:** The namespace could not be resolved.

**Action:** Verify the specified node type name is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34433: The property name cannot be returned from the qualified name.**

**Cause:** The namespace could not be resolved.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-34434: The property definition name cannot be returned from the qualified name.**

**Cause:** The namespace could not be resolved.

**Action:** Verify the property type is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34435: The item at the requested depth, {0}, cannot be found.**

**Cause:** An error occurred while getting the requested item.

**Action:** Verify that the depth is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34436: The root node does not have a parent.**

**Cause:** Could not request the parent node as root nodes do not have parent nodes.

**Action:** Verify that the context node is not the root node.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34437: The Portal session cannot be restored.**

**Cause:** A SQL error occurred when attempting to restore the session for the user.

**Action:** Verify that the user has been authenticated.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WCS-34438: The declared property definition array object cannot be stored in the cache.**

**Cause:** The system encountered an unexpected exception when trying to store the declared property definition array object in cache.

**Action:** Contact the WebCenter administrator to check the status of the cache.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34440: The property definition array object cannot be stored in the cache.**

**Cause:** The system encountered an unexpected exception when trying to store the property definition array object in the cache.

**Action:** Contact the WebCenter administrator to check the status of the cache.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34441: The property iterator object cannot be stored in the cache.**

**Cause:** The system encountered an unexpected exception when trying to store the property iterator object in the cache.

**Action:** Contact the WebCenter administrator to check the status of the Cache.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34442: The property object cannot be stored in the cache.**

**Cause:** The system encountered an unexpected exception when trying to store the property object in the cache.

**Action:** Contact the WebCenter administrator to check the status of the cache.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34443: The node iterator object cannot be stored in the cache.**

**Cause:** The system encountered an unexpected exception when trying to store the node iterator object in the cache.

**Action:** Contact the WebCenter administrator to check the status of the cache.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34444: The node object cannot be stored in the cache.**

**Cause:** The system encountered an unexpected exception when trying to store the node object in the cache.

**Action:** Contact the WebCenter administrator to check the status of the cache.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34446: The node type object cannot be stored in the cache.**

**Cause:** The system encountered an unexpected exception when trying to store the node type object in the cache.

**Action:** Contact the WebCenter administrator to check the status of the cache.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34447: The "primary node types" node type iterator cannot be stored in the cache.**

**Cause:** The system encountered an unexpected exception when trying to store the node type iterator in the cache.

**Action:** Contact the WebCenter administrator to check the status of the cache.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34448: The "mixin node types" node type iterator cannot be stored in the cache.**

**Cause:** The system encountered an unexpected exception when trying to store the node type iterator in the cache.

**Action:** Contact the WebCenter administrator to check the status of the cache.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34449: The "super types" node type array cannot be stored in cache.**

**Cause:** The system encountered an unexpected exception when trying to store the node type array in the cache.

**Action:** Contact the WebCenter administrator to check the status of the cache.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34450: The child node definitions of the node type cannot be stored in the cache.**

**Cause:** The system encountered an unexpected exception when trying to store the child node definitions of the node type in the cache.

**Action:** Contact the WebCenter administrator to check the status of the cache.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WCS-34451: The property definitions of the node type cannot be stored in the cache.**

**Cause:** The system encountered an unexpected exception when trying to store the property definitions of the node type in the cache.

**Action:** Contact the WebCenter administrator to check the status of the cache.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34452: The boolean object cannot be stored in the cache.**

**Cause:** The system encountered an unexpected exception when trying to store the boolean object in the cache.

**Action:** Contact the WebCenter administrator to check the status of the cache.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34453: The requested child node definition of the node type cannot be stored in the cache.**

**Cause:** The system encountered an unexpected exception when trying to store the child node definition of the node type in the cache.

**Action:** Contact the WebCenter administrator to check the status of the cache.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34454: The requested property definition of the node type cannot be stored in the cache.**

**Cause:** The system encountered an unexpected exception when trying to store the property definition of the node type in the cache.

**Action:** Contact the WebCenter administrator to check the status of the cache.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34456: The repository property objects cannot be stored in the cache.**

**Cause:** The system encountered an unexpected exception when trying to store the repository property objects in cache.

**Action:** Contact the WebCenter administrator to check the status of the cache.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34457: The repository property definition objects cannot be stored in the cache.**

**Cause:** The system encountered an unexpected exception when trying to store the repository property definition objects in the cache.

---

**Action:** Contact the WebCenter administrator to check the status of the cache.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34458: One of the cache regions could not be destroyed.**

**Cause:** The system encountered an unexpected exception when trying to destroy one of the cache regions.

**Action:** Contact the WebCenter administrator to check the status of the cache.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34459: The cache could not be initialized.**

**Cause:** The system encountered an unexpected exception when trying to initialize the cache.

**Action:** Contact the WebCenter administrator to check the status of the cache.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34460: The cache configuration file could not be read.**

**Cause:** The system encountered an IO exception when trying to read the cache configuration file.

**Action:** Verify that the configuration file exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34461: The repository node type objects could not be stored in cache.**

**Cause:** The system encountered an unexpected exception when trying to store the repository node type objects in cache.

**Action:** Contact the WebCenter administrator to check the status of the cache.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34462: Cannot get the super types for node type: {0}.**

**Cause:** An error occurred while fetching the super types of the given node type.

**Action:** Verify that the requested node type exists in the Portal repository and is a custom type.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WCS-34463: The cache region, {0}, cannot be found.**

**Cause:** Could not find the requested region, as it has not been defined in Java Object Cache (JOC).

**Action:** Verify that the region name is valid and is expected to exist in this hierarchy.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34464: Oracle Text search is unable to run.**

**Cause:** An error occurred with Oracle Text while running a search.

**Action:** Check with the Administrator of the Portal you are trying to search that Oracle Text is valid. Additional information as to the cause of the error may be in the portal diagnostics log.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34465: A root search can not be performed as the base languages of the page groups are different.**

**Cause:** The search could not be performed because the base language of the page groups to be searched are not the same.

**Action:** Only perform searches which search a single page group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-34466: Cannot look up the database connection with the name {0} from connections.xml.**

**Cause:** An error occurred while attempting to look up the database connection; the named database connection may not exist in connections.xml.

**Action:** Make sure the database connection is created in connections.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-35006: cannot load metadata from XML node**

**Cause:** The content of the data-control file (.dcx) might be invalid.

**Action:** Verify that the content in the data-control file (.dcx) is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-35008: Login failed.**

**Cause:** The specified user credentials were invalid.

**Action:** Provide valid user credentials.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-35013: missing method parameters**

**Cause:** The data-control operation was invoked without any parameters.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-35016: Retrieving data-control definition from run-time data-control object returned null.**

**Cause:** The ADF framework did not set the data-control definition within the run-time data control.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-35300: Parameters for the operation are missing.**

**Cause:** The ADF framework passed a null parameter map to the data-control operation.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-35301: The path parameter is not correct.**

**Cause:** The path string that was specified was not a valid JCR repository path.

**Action:** Verify that the specified path string is a valid path in the content repository, and that it starts with /.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-35302: The type parameter is not correct.**

**Cause:** The type string that was specified was not a valid node type in the JCR repository.

**Action:** Make sure the type specified is valid in the content repository on which the data control is based. Both the prefix and the local name should be valid. For example, nt:file and nt:folder are valid types.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WCS-35303: cannot generate XPath query**

**Cause:** The parameters that were given in the search operation could not be resolved into a valid XPath query string using the content repository session.

**Action:** Ensure the attribute names and prefixes used in the parameters are valid and registered in the JCR repository.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-35304: incorrect attribute {0} specified in the predicate**

**Cause:** The specified attribute was not found in the repository.

**Action:** Provide a valid attribute name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-35305: incorrect prefix for the attribute {0} in the predicate**

**Cause:** The namespace that was used in the attribute was not correct or not registered in the JCR repository.

**Action:** Provide a valid prefix, or report the problem to the provider of the JCR adapter used with the repository.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-35306: cannot resolve attribute {0} using the repository session**

**Cause:** An invalid attribute or an unregistered prefix was used in the JCR session.

**Action:** Provide a valid attribute name in the JCR repository session.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-35307: operator {0} not supported**

**Cause:** An invalid operator was specified.

**Action:** Specify a valid operator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-35309: The XPath query {0} is not supported by the JCR adapter.**

**Cause:** The JCR adapter might not have been compliant with the XPath support that is required to work with the Content Repository data control.

**Action:** Verify that the XPath query is supported by this JCR adapter.

**Level:** 1



---

**Type:** ERROR

**Impact:** Other

**WCS-35310: error in the JCR repository**

**Cause:** An error occurred in the JCR adapter.

**Action:** Check the exception's cause and JCR adapter's error log.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-35311: error getting the item's URL**

**Cause:** An error occurred while generating the URL for an item.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-35312: invalid return attribute name {0}**

**Cause:** An invalid Java name was entered. The name of a return attribute must be a valid Java name and must be different from "name", "URL", "path" and "primaryType".

**Action:** Verify that the attribute name is valid and is not "name", "URL", "path" and "primaryType".

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-35313: invalid return attribute type**

**Cause:** An invalid return attribute type was specified. Return attributes must be one of the following JCR types: Boolean, Integer, Double, String, or Date.

**Action:** Specify a valid return attribute type.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-35314: cannot get value for attribute {0}**

**Cause:** The value for the specified attribute could not be retrieved from the JCR node.

**Action:** Verify that the JCR path for the attribute is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-35501: No repository was set in the environment.**

**Cause:** No repository was specified for this resource.

**Action:** Specify a repository to use in creating the resource.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-35502: could not log on to the content repository**

**Cause:** There was a problem logging on to the content repository.

**Action:** Verify that the connection and credentials are defined correctly and that the repository is accessible.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-35503: An error occurred while accessing the content repository.**

**Cause:** There was a problem accessing the content repository.

**Action:** Verify that the content repository is accessible.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-35504: An error occurred while trying to close the connection.**

**Cause:** Could not close the content repository connection.

**Action:** Verify that the connection is still available, and try to close it again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-35505: Item {0} is not a file or folder.**

**Cause:** An item was specified that is not a file or folder.

**Action:** Specify an item that is either a file or a folder.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-35506: Item {0} does not exist.**

**Cause:** An item was specified that does not exist.

**Action:** Verify that the specified item exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-35507: unknown control type: {0}**

**Cause:** An unknown control type was specified.

**Action:** Specify a known control type.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WCS-35508: {0} does not name a ContentDirContext.**

**Cause:** An item was specified that is not a ContentDirContext.

**Action:** Verify that the item specified is a ContentDirContext.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-35509: invalid search operation: {0}**

**Cause:** An unrecognized search operation was specified.

**Action:** Use only recognized search operations.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-35510: unable to generate schema**

**Cause:** An error occurred while adding attributes to the schema.

**Action:** Make sure the schema attributes are defined properly and are not already bound.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-35511: unable to create DataFlavor**

**Cause:** An error occurred while trying to create a DataFlavor from the given MIME type.

**Action:** Make sure the MIME type is valid and non-null, and that any referenced classes can be loaded.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-35513: unable to create TaskFlowDescriptor**

**Cause:** An error occurred while trying to create a TaskFlowDescriptor object.

**Action:** Make sure the required classes are in the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-35514: This feature is only available in a design environment.**

**Cause:** A call to a design time only feature was made from run time.

**Action:** Do not call this method from run time code.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WCS-35900: Illegal value state, cannot read a value previously streamed.**

**Cause:** The application mixed calls to `getStream()` and other `get*` accessors on the same value object.

**Action:** Verify your application code.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-35901: Illegal value state, cannot stream a value previously read.**

**Cause:** The application mixed calls to `getStream()` and other `get*` accessors on the same value object.

**Action:** Verify your application code.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-35902: Error in value conversion (source type = {0}, target type = {1}).**

**Cause:** The JCR values could not be converted to the specified type; the source and target type may not be compatible.

**Action:** Verify the value conversion rules defined in the JCR specification.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-35903: Error in value conversion (invalid ISO8601 string).**

**Cause:** The specified string was not a valid ISO8601 string as specified by JCR and therefore could not be converted to a date.

**Action:** Verify the format of the date string.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-35904: Cannot create REFERENCE values.**

**Cause:** Values of type REFERENCE are not supported by this JCR repository.

**Action:** Avoid using properties of type REFERENCE in your application.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-35905: Input/Output error while reading the binary stream.**

**Cause:** The data for the binary property could not be accessed.

**Action:** Verify that the storage medium for the JCR repository is accessible.

---

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-35906: UTF8 encoding not supported on this JVM**

**Cause:** The JVM does not support UTF-8 encoding.

**Action:** Use a supported Java 5 compliant JVM.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-35907: This iterator does not contain any more elements.**

**Cause:** The iterator has exhausted all its elements.

**Action:** Check the usage of the RangeIterator by your application.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-35908: This iterator does not support the remove operation.**

**Cause:** The remove() operation is not supported on this iterator.

**Action:** Avoid making calls to RangeIterator#remove() in your application.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-35909: The item at path {0} is not a node.**

**Cause:** An item was found at the specified path but it was not a node.

**Action:** Check that your application is specifying the correct path.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-35910: "{0}" is not a known namespace prefix.**

**Cause:** The name or path contained a namespace prefix unknown to this repository.

**Action:** Check the namespace mappings in the current session.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-35911: "{0}" is not a known namespace URI.**

**Cause:** The repository did not recognize the specified namespace URI.

**Action:** Check the set of namespaces allowed by the current repository.

**Level:** 1

---

**Type:** WARNING

**Impact:** Other

**WCS-35912: The prefix "{0}" is already used.**

**Cause:** The specified prefix was already mapped to a namespace and could not be remapped.

**Action:** Change the prefix mapping for the URI associated with that prefix before mapping it to another URI.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-35913: {0} is a reserved namespace prefix and cannot be remapped**

**Cause:** The "xml" prefix could not be remapped as it is reserved by JCR.

**Action:** Check that your application is not trying to remap the "xml" prefix.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-35914: Namespace prefix remapping is not permitted**

**Cause:** Could not remap the namespace as the JCR repository does not permit persistent namespace remapping.

**Action:** Use the session for any namespace remapping requirements.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-35915: Invalid JCR name or path: {0}**

**Cause:** The name or path specified was not a valid JCR name or path.

**Action:** Check that the name or path uses valid namespace prefixes and satisfies the JCR grammar rules for names and paths.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-35916: Cannot append an absolute Path**

**Cause:** Could not append an absolute path to the existing path.

**Action:** Make sure that the appended path is always relative.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-35918: Unexpected error while accessing node type**

**Cause:** An unexpected error occurred while accessing a node type.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-35919: No such node type: {0}**

**Cause:** The node type specified was unknown to the JCR repository.

**Action:** Ensure that your are using correct node types for this repository.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-35920: Not a supported query language: {0}**

**Cause:** The query language specified was a not a supported query language; this repository only supports XPath.

**Action:** Make sure you use only XPath queries.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-35921: Saved queries are not supported.**

**Cause:** Could not save the query as this repository does not support saved queries.

**Action:** Ensure that your application does not call unsupported JCR functionality.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-35922: Incorrect XPath expression**

**Cause:** Could not recognize the XPath expression specified as it is not supported by this JCR repository.

**Action:** Check that your XPath query conforms to the JCR specification.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-35923: XPath expression error: invalid enumeration value.**

**Cause:** An internal data structure used an invalid value.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-35924: XPath expression error: invalid expression tree.**

**Cause:** The XPath expression specified was not recognized as it is not supported by this JCR repository.

---

**Action:** Check that your XPath query conforms to the JCR specification.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-35925: Error while generating XML representation of expression tree**

**Cause:** Could not create an XML representation of this expression tree.

**Action:** Check the exception stack trace for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-35926: Invalid xpath expression.**

**Cause:** The XPath expression specified was not recognized as it is not supported by this JCR repository.

**Action:** Check that your XPath query conforms to the JCR specification.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-35927: Invalid qualified name: {0}**

**Cause:** The specified XPath expression contained an invalid qualified name.

**Action:** Check that your XPath query conforms to the JCR specification.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-35928: Unexpected error during XML export.**

**Cause:** There was an XML processing error while performing an XML export operation.

**Action:** Check that you are using Oracle XML parser v2.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-35930: Index out of bound while accessing path**

**Cause:** The specified index for a path element was not valid.

**Action:** Check your use of the path object.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-35991: "{0}" is not a valid expression for use as a search string with jcr:contains().**



---

**Cause:** The specified full text search expression was not a valid argument for jcr:contains().

**Action:** Check the full text search expression syntax defined in the JCR specification.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-35992: "{0}" is not a valid expression for use as a search string with jcr:like().**

**Cause:** The specified regular expression was not a valid argument for jcr:like().

**Action:** Check the regular expression syntax defined in the JCR 1.0 specification.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-35993: This XPath expression contains constructs that are not supported by this query engine.**

**Cause:** Could not execute this XPath query as it contained constructs that were not supported by this repository.

**Action:** Check that your XPath query conforms to the JCR specification.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-36301: Unable to find page "{0}" in the Binding Context.**

**Cause:** Page objects do not exist in the Binding Context.

**Action:** Check if the page in the specified path exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-36302: Unable to create a document with name "{0}".**

**Cause:** Invalid MO name supplied for creation in MDS.

**Action:** Check the name provided for creation of the document and ensure that it is a valid MO name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-36303: Unable to create a document in path "{0}".**

**Cause:** MDS raised an MDS\_UNSUPPORTED\_UPDATE exception while creating document.

**Action:** Check the MDS config to ensure that the path is editable.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WCS-36304: Unable to create a pagedefs directory under the scope "{0}".**

**Cause:** MDS raised an exception while creating pagedefs folder.

**Action:** Check the MDS config to ensure that the path is editable.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-36305: Unable to delete page "{0}".**

**Cause:** MDS raised an exception while deleting the page.

**Action:** Check the MDS config to ensure that the path is editable.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-36306: Unable to create metadata for page "{0}".**

**Cause:** MDS raised an exception while creating metadata for page.

**Action:** The metadata for the page already exists under the scope.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-36307: Unable to copy page "{0}".**

**Cause:** MDS raised an exception while copying the page.

**Action:** Check the MDS config to ensure that the path is editable.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-36308: Unable to rename scope "{0}" to "{1}".**

**Cause:** MDS raised an exception while renaming the pages under the scope.

**Action:** Check the MDS config to ensure that the path is editable.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-36309: An unexpected error occurred.**

**Cause:** An unexpected error occurred.

**Action:** Contact your system administrator.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

---

**WCS-36310: Unable to create a page with the name "{0}".**

**Cause:** A page with the same name already exists.

**Action:** Change to use a different name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-36311: PageService object is not an instance of PageServiceImpl.**

**Cause:** PageService object is not an instance of PageServiceImpl.

**Action:** Create a Page service instance and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-36312: Could not flush changes to MDS. Adding view activity failed.**

**Cause:** Could not flush changes to MDS.

**Action:** Try to create a new page.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-36313: Unable to find page definition file for page "{0}".**

**Cause:** The page definition file does not exist or the page definition path is wrong in the Binding Context file.

**Action:** Check if the page definition file exists and make sure its path is correct in the Binding Context file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-36314: Unable to create a page for now because another page is being created.**

**Cause:** Another page is being created and all page metadata is locked.

**Action:** Try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-36801: Failed to change page permission to "{0}".**

**Cause:** An unexpected error occurred when changing page permission.

**Action:** Check error stack for details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WCS-36802: Failed to grant page permission "{0}" to user "{1}".**

**Cause:** An unexpected error occurred when granting page permission to a user.

**Action:** Check error stack for details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-36803: Failed to revoke page permission from user "{0}".**

**Cause:** An unexpected error occurred when granting page permission to a user.

**Action:** Check error stack for details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-36804: Failed to change page security to default mode.**

**Cause:** An unexpected error occurred when changing page security mode.

**Action:** Check error stack for details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-37001: An unexpected error occurred.**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-37002: An object of type {0} with this ID ({1}) already exists.**

**Cause:** An attempt was made to create an object with an existing ID.

**Action:** Use a unique ID to Create the object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-37003: Configuration invalid.**

**Cause:** Either the configuration does not exist or the MDS instance is not specified.

**Action:** Specify a valid configuration with a MDS instance.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-37004: The name ({0}) is invalid.**

---

**Cause:** The name specified was not valid.

**Action:** Specify a valid name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-37006: Object modified by another user.**

**Cause:** The object has been changed by another user.

**Action:** Refresh the object and try again.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-37007: Object of type {0} with ID={1} could not be found.**

**Cause:** The ID is invalid.

**Action:** Specify a valid object ID.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-37008: Object ({0}) is immutable.**

**Cause:** An attempt to change this object was made but this object is currently immutable.

**Action:** Either update object to allow changes or perform this operation on another object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-37009: Method: {1} in class: {0} is invalid.**

**Cause:** The specified class.method does not exist or is invalid.

**Action:** Check underlying method/property specification.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-37010: {0} is not a valid reference name to MDS.**

**Cause:** The name specified is not a valid MDS reference name.

**Action:** Correct the name to a valid reference.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-37500: The note no longer exists.**

---

**Cause:** Another user deleted the note.

**Action:** Refresh the links to see the latest changes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-37501: This note has been modified by another user.**

**Cause:** Another user modified the note. You can only modify the latest version.

**Action:** Refresh the page to see the latest changes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-38001: An unexpected error occurred.**

**Cause:** The cause of this error is unknown.

**Action:** Try repeating the action that caused this error.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-38002: Data source ({0}) does not exist.**

**Cause:** The specified data source is invalid.

**Action:** Specify a valid data source and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-38003: Invalid configuration.**

**Cause:** Either the configuration does not exist or MDSInstance is not specified.

**Action:** Specify a valid MDS configuration and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-38004: Object ({0}) is immutable.**

**Cause:** An attempt to change this object was made but this object is currently immutable.

**Action:** Either update the object to allow changes or perform this operation on another object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-38005: An object of type {0} with ID={1} could not be found.**

---

**Cause:** The object ID is invalid.  
**Action:** Specify a valid object ID.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-38006: Unable to perform transformation**

**Cause:** Transformation input sources were invalid.  
**Action:** Validate the input sources and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-38007: A search error occurred while searching for lists.**

**Cause:** The search parameters were invalid.  
**Action:** Validate the search parameters and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-38008: An error occurred while configuring the List API.**

**Cause:** An invalid List API configuration was specified.  
**Action:** Specify a valid List API configuration and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-38009: An error occurred while looking up list row data.**

**Cause:** The database connection not found.  
**Action:** Verify that a valid database connection exists and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-38010: A search error occurred while searching the discussion forums.**

**Cause:** A connection to the discussion forum service could not be established.  
**Action:** Validate the discussion forum connection details in connections.xml and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-38011: An error occurred while retrieving recent activity information.**

**Cause:** Invalid parameters were passed to the Recent Activity API.

---

**Action:** Validate the API usage and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-38012: A search error occurred while searching the service.**

**Cause:** Invalid parameters were passed to the Search API.

**Action:** Validate the API usage and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-38013: Unable to instantiate class**

**Cause:** An invalid class reference was detected.

**Action:** Validate the class usage and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-38014: Illegal access exception while accessing class**

**Cause:** An invalid class reference was detected.

**Action:** Validate the class usage and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-38015: Unable to find class**

**Cause:** An unknown class was referenced.

**Action:** Verify the class reference and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-38016: Unable to find 'getEnabledScopes' method in class**

**Cause:** Class is missing required method.

**Action:** Verify that the method exists and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-38017: Service exception while getting service registry.**

**Cause:** Invalid parameters were passed to the Service Registry API.

**Action:** Validate the API usage and try again.



---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-38022: The RSS XML does not have a root element**

**Cause:** Invalid XML content detected

**Action:** Ensure that the RSS feed URL returns XML conforming to the RSS format

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-38023: The root element name of the RSS XML is not rss**

**Cause:** The XML content is not RSS XML format compliant.

**Action:** Ensure that the XML returned by the feed URL is RSS XML format compliant.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-38024: The root element name of the RSS XML does not have any child elements**

**Cause:** The XML content returned by the feed URL is not valid

**Action:** Ensure that the XML returned by the feed URL is RSS XML format compliant.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-38025: The XML content returned by the feed URL does not have the channel element**

**Cause:** The XML content is not RSS XML format compliant

**Action:** Ensure that XML returned by the feed URL is RSS XML format compliant.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-38026: The channel element of the RSS XML does not have any child elements**

**Cause:** The XML content returned by the feed URL is invalid

**Action:** Ensure that the XML returned by the feed URL is RSS XML format compliant.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-39001: Unable to get portlet response (Internal Error) for portlet binding {0}.**

---

**Cause:** An internal error occurred in the portlet run-time code.

**Action:** Check the portlet client logs to locate the cause of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-39002: The binding context for this request is null.**

**Cause:** An internal error occurred in setting the context for the request.

**Action:** Check if the page definition exists for this page and the request is correctly passing through the `adfBinding` filter, where `bindingcontext` is created. You can see this error for log level `finer`, when the application does not have any Model objects.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-39003: Unable to get the binding container for page {0}.**

**Cause:** The application was unable to load the page definition for the requested page.

**Action:** Check whether the page definition for page {0} is properly defined.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-39101: Portlet component could not retrieve stored Faces View URL**

**Cause:** Information about the current Faces View should have been stored on the current request so that it can be passed to Oracle JPKD portlets but it was not found.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-39251: Unable to process portlet action for portlet binding {0}.**

**Cause:** An exception occurred during the processing of a portlet action in the portlet client.

**Action:** Check the portlet client logs for portlet binding {0}.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-39252: Unable to access the portlet container.**

**Cause:** A failure occurred trying to access the portlet container. It could be a configuration problem where the run time is not able to locate the registered producer metadata.

---

**Action:** Check the portlet run-time logs and confirm your configuration (MDS path location) in adf-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-39253: Unable to get the portlet with instance ID {0} from the container for portlet binding {1}.**

**Cause:** The portlet instance was stale or unavailable in the list of portlet instances from the registered producer.

**Action:** Confirm whether the portlet instance ID {0} is correct and has not been modified. Try removing the portlet and associated portlet bindings {1} from the page and page definition and add this portlet to the page again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-39254: Runnable portlet for portlet instance {0} for portlet binding {1} is null.**

**Cause:** This error occurred due to some internal errors in the portlet client.

**Action:** Check the portlet client logs for this error and take appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-39255: Unable to get portlet response for portlet instance ID {0} for portlet binding {1}.**

**Cause:** Errors have occurred in the Portlet runtime while getting the portlet response. The Stack trace for the actual error should be able to provide more information about the cause of error.

**Action:** Check the portlet client logs for the cause and action of this error.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-39256: Unable to find the public parameter {0} for portlet binding {1}.**

**Cause:** The public parameter {0} defined in the portlet binding {1} did not match the available portlet public parameters.

**Action:** Check the public parameter exposed by the portlet and make sure the public parameters used in the portlet bindings are the same as the one available in the portlet.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-39257: Unable to set portlet mode {0} for portlet binding {1}**

**Cause:** An exception occurred in the portlet run-time client.

---

**Action:** Check the portlet run-time client logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-39258: Unable to set the portlet window state {0} for the portlet view component {1}.**

**Cause:** An exception occurred in the portlet run-time client.

**Action:** Check the portlet run-time client logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-39259: Unable to process the portlet action for the portlet component {0} exception {1}.**

**Cause:** An exception occurred during the processing of a portlet action in the portlet client.

**Action:** Check the portlet client logs for the portlet component {0}.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-39260: Unable to get the portlet binding object for the portlet component {0}.**

**Cause:** Run time was not able to evaluate the value attribute of the portlet tag.

**Action:** Check the value attribute of the portlet tag and ensure it is defined properly in the associated page definition.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-39261: Portlet bindings object {0} is not properly defined for the portlet view component {1} (not of type portlet binding).**

**Cause:** The portlet binding (value) defined for portlet component {0} is of an illegal type.

**Action:** Check whether the portlet binding defined for the portlet component {0} is pointing to the PortletBinding element in the page definition.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-39262: Unable to get portlet binding object {0} from page {1}.**

**Cause:** The portlet servlet was not able to locate the portlet bindings from the supplied information.

**Action:** Check if the value attribute of the portlet tag is correctly defined and a PortletBinding of that object exists in the page defs. Also ensure that

---

ADDFPhaseListener (or its subclasses) are registered in the lifecycle phase listener in your application faces-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-39263: Unknown error for portlet instance Id {0} exception {1}.**

**Cause:** Errors have occurred in the Portlet runtime while getting the portlet response. The Stack trace for the actual error should be able to provide more information about the cause of error.

**Action:** Check portlet client logs for the cause and action of this error.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-39264: Portlet bindings are null for portlet component {0}.**

**Cause:** Run time was not able evaluate the value attribute of the portlet tag.

**Action:** Check the value attribute of the portlet tag and ensure it is defined properly in the associated page definition.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-39265: Unable to get portlet response (time-out) for portlet binding {0}.**

**Cause:** Timeout occurred while performing a task at the producer side. This can happen if some tasks at the producer are taking longer than the timeout specified for the registered producer.

**Action:** Edit the registration details for this producer and increase the timeout entry.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-39266: Unable to get portlet metadata naming policy.**

**Cause:** The portlet metadata naming policy class could not be initialized.

**Action:** The default naming policy will be used unless the resource META-INF/portlet/ADFPportletNamingPolicy is accessible and contains the name of a valid naming policy class.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-39267: Portlet binding was not refreshed.**

**Cause:** The portlet binding was not refreshed when it was accessed by the portlet view component to which it is bound.

**Action:** Check that the refresh option on the portlet binding is not set to Never.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-39268: Page variable {0} not defined in page definition {1}.**

**Cause:** The named page variable which is referenced by the parameter definition of a PortletBinding is not defined.

**Action:** Verify that the Portlet parameter page variable declarations in the page definition are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-39269: FullPageModeRequest object not found on Portlet UIComponent {0}**

**Cause:** The request object required to forward to Portlet full page modes is missing from the Portlet UIComponent.

**Action:** This is an internal error. The redirect to the full page mode will still occur but some information, such as stylesheet information may be missing when the full page mode is rendered.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-39270: Invalid request made to the portlet servlet.**

**Cause:** A request was made to the portlet servlet for a full page mode rendition or for portlet iframe content but the request parameters and / or information stored in the session were incomplete or incorrect.

**Action:** Portlet authors should ensure that all links or form action URLs back to the portlet are created using the appropriate portlet API.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-39271: Portlet with id {0} is not inside an appropriate JSF Form.**

**Cause:** This usually occurs because the portlet was not placed inside of a JSF Form.

**Action:** Ensure that the portlet is a descendent, direct or otherwise, of the page's JSF Form.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-39272: The metadata for portlet binding {0} was not found in MDS.**

**Cause:** This is often caused by a failed producer import or export.

**Action:** Check the server logs for producer import errors during application deployment. Also check for export errors when the application was packaged

---

prior to deployment. For example, if deployed from JDeveloper, check the deployment messages for errors.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-39501: Unable to create portlet parameter {0} with associated page variable {1} for portlet binding {2}.**

**Cause:** Portlet parameter name {0} or associated page variable {1} for portlet binding {2} was not defined or was null.

**Action:** Check the portlet parameter name {0} or associated page variable {1} in portlet binding {2}. If they are properly defined, they should use name and pageVariable with non-null string values.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-39502: Unable to find variable manager for page definition {0}.**

**Cause:** The variable manager was not defined in the page definition.

**Action:** Check the page definition {0} and ensure that page variables are being used and that the VariableIterator element is available inside executable binding section.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-39503: ADF lifeCycle does not execute properly for portlet bindings {0}.**

**Cause:** The ADF lifeCycle terminated abruptly.

**Action:** Check log files for any errors that occurred during the execution life cycle on other resources in the page definition.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-39504: Warning: Runnable portlet for portlet instance {0} for portlet binding {1} is null, trying to get again.**

**Cause:** This error was due to some internal errors from the portlet client.

**Action:** Check portlet client logs for this error and take the appropriate action.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-39505: Unable to create portlet event {0} with associated payload {1} for portlet binding {2}.**

**Cause:** Portlet parameter event {0} or associated payload {1} for portlet binding {2} was not defined or was null.

---

**Action:** Check the portlet event name {0} or associated payload {1} in portlet binding {2}. If they are properly defined, they should use name and payload with non-null string values.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-39507: Iframe content request checksum verification failed.**

**Cause:** The checksum verification of the parameters in the request for Portlet markup in the iframe has failed.

**Action:** This may indicate that a deliberately modified request for Portlet content has been made.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-39508: Portlet mode change unauthorized. Portlet {0} bound to PortletBinding {1}; Requested mode: {2}**

**Cause:** A portlet mode change was requested but the user does not have permission to access that mode.

**Action:** The mode change may have been via mode change links rendered by the Portlet.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40001: Configuration error: property "{0}".**

**Cause:** The named configuration property has a invalid value.

**Action:** Correct the value of the property.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40002: Configuration error: property "{0}" value "{1}" is not an integer.**

**Cause:** The named configuration property does not have an integer value.

**Action:** Specify an integer value for the named property.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40003: Configuration error: property "{0}" invalid value "{1}".**

**Cause:** The named configuration property has a invalid value.

**Action:** Correct the value of the property.

**Level:** 1

**Type:** ERROR



---

**Impact:** Configuration

**WCS-40004: Configuration error: property "{0}" value "{1}" is not a number.**

**Cause:** The named configuration property does not have a numeric value.

**Action:** Specify a numeric value for the named property.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40009: {0} element without a name or default='true'.**

**Cause:** User or subscriber cache partition settings are being defined for an unnamed entity.

**Action:** Specify a name or declare the element as defining default values.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40010: Parameter {0} specifies an unrecognized cache level: {1}.**

**Cause:** A cache configuration parameter uses an invalid cache level.

**Action:** Correct the parameter such that it uses a cache level of either 'system' or 'user'.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40011: Invalid cache configuration parameter: {0}.**

**Cause:** A configuration parameter starting with 'cache.' has an invalid name.

**Action:** Correct the parameter name.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40014: Unable to open Java Object Cache.**

**Cause:** Java Object Cache failed to open.

**Action:** Examine the Java Object Cache log file to determine the cause.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40015: Object {0} is too big to cache in region {1}.**

**Cause:** Portlet content cannot be cached because it is too large.

**Action:** Reconfigure the cache such that enough space is available for the content.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-40016: Unable to insert data into cache region {0} using key {1}.**

**Cause:** An error occurred while trying to cache portlet content.

**Action:** Examine the Java Object Cache log file to determine the cause.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40017: Unable to access cache to get entry for {0}.**

**Cause:** An error occurred while trying to retrieve content from the cache.

**Action:** Examine the Java Object Cache log file to determine the cause.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40018: Unable to access cache to remove entry for {0}.**

**Cause:** An error occurred while trying to remove content from the cache.

**Action:** Examine the Java Object Cache log file to determine the cause.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40021: Configuration error: property "{0}" cannot be greater than property "{1}".**

**Cause:** The named configuration properties have invalid values.

**Action:** Correct the values of the properties.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40022: Configuration error: property "{0}" cannot be less than property "{1}".**

**Cause:** The named configuration properties have invalid values.

**Action:** Correct the values of the properties.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40024: Timing out task: {0}.**

**Cause:** A task took too long to complete.

**Action:** If the problem persists, increase the timeout period for the task.

**Level:** 1

**Type:** WARNING

**Impact:** Threads

**WCS-40025: Muffling exception in method {0}, context = {1}.**

---

**Cause:** An error occurred but processing was allowed to continue.

**Action:** Use the context information to determine if remedial action is required.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40026: Invalid client id "{0}" for portlet resource request handle "{1}".**

**Cause:** A portlet resource request contained an invalid client id.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40027: Error proxying resource.**

**Cause:** An unexpected error occurred while proxying a request for a portlet resource.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40029: Error accessing ADF configuration.**

**Cause:** The portlet client was unable to access ADF configuration information.

**Action:** Examine the associated stack trace to resolve the issue.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**WCS-40030: Cannot export portlet {0} because it is a producer offered portlet.**

**Cause:** An attempt has been made to export a producer offered portlet.

**Action:** Remove the offered portlet from the export set.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40031: Unexpected portlet (handle = {0}) in group {1} for producer {2}.**

**Cause:** The producer returned a portlet in an export set that was not requested by the client.

**Action:** Check the producer's log file to determine that it is functioning correctly.

**Level:** 1

**Type:** WARNING

**Impact:** Other

---

**WCS-40032: Failed to export portlets with handles: {0}. Reason given by producer was: {1}.**

**Cause:** A producer was unable to export one or more portlets.

**Action:** Resolve the issue given by the producer as the reason for the failure and retry the export.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40033: Producer {0} does not support the WSRP ImportPortlets operation. Unable to proceed with import using API.**

**Cause:** An attempt was made to import data obtained using the WSRP ExportPortlets operation into a producer that does not support the ImportPortlets operation.

**Action:** The client will fall back to importing portlets by cloning. Enable ImportPortlets on the producer to import portlets using the API.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40034: Error calling producer to import portlets for export group {0}.**

**Cause:** The producer failed to import a group of portlets.

**Action:** Examine the associated exception and producer logs to resolve the issue.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40035: Unexpected portlet with ID {0} in ImportPortletResponse.**

**Cause:** The producer returned a portlet in an import response that was not requested by the client.

**Action:** Check the producer's log file to determine that it is functioning correctly.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40040: Error calling producer to delete portlet handle {0} overwritten during import.**

**Cause:** A call to the producer to delete a portlet failed.

**Action:** Delete the portlet manually if possible.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40041: Unable to import portlet with ID {0}.**

**Cause:** A portlet with the same ID already exists but is based on a different offered portlet.

---

**Action:** Remove the existing portlet and retry the import operation.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40042: Failed to import portlets with IDs: {0}. Reason given by producer was: {1}.**

**Cause:** A producer was unable to import one or more portlets.

**Action:** Resolve the issue given by the producer as the reason for the failure and retry the import.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40046: Filter unable to modify markup.**

**Cause:** An exception caused filtering of portlet markup to fail.

**Action:** Examine the associated exception to resolve the issue.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40047: Could not load markup filter {0}. Portlet markup cannot be filtered.**

**Cause:** An error prevented a portlet markup filter from being created.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40050: Unexpected content type "{0}" in {1} response.**

**Cause:** The producer responded with a content type the client was not expecting.

**Action:** Consult the producer's log file to determine why the incorrect content type was used.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40052: WSRP producer {0} supports the export feature but does not support export by value. Portlets will be exported by cloning.**

**Cause:** The producer supports the export feature but does not support export by value.

**Action:** If possible, enable the export by value feature on the producer.

**Level:** 1

**Type:** WARNING

**Impact:** Other

---

**WCS-40053: WSRP v2 style import failed for producer {0}. Will attempt import by cloning.**

**Cause:** An attempt to import portlets by calling the producer's ImportPortlets operation failed.

**Action:** Consult the client and producer logs to determine why the import failed.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40055: Error processing initSession for producer {0}.**

**Cause:** Invoking a WSRP producer's InitCookie operation failed.

**Action:** Consult the producer's log file to determine the cause of the failure.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40057: Ignoring remote producer requery handle: {0}.**

**Cause:** This feature is not implemented.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40058: ID {0} not found.**

**Cause:** An ID requested for export does not correspond to an object.

**Action:** Verify that the ID is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40059: ID {0} is not for a producer or portlet.**

**Cause:** An ID requested for export does not correspond to a producer or a portlet. Only producers and portlets can be exported.

**Action:** Correct the ID or remove it from the export request.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40060: Error during portlet export. Portlets will not be available in the target application. Context: input mds repository file path = {0}. output mds repository file path = {1}. input connections file path and name = {2}. export ID = {3}. producer/portlet IDs to export: {4}.**

**Cause:** An exception was thrown during a portlet export operation.

**Action:** Examine the exception and resolve the issue that caused the failure.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WCS-40061: Error during portlet import. Context: input mds repository file path = {0}. output mds repository file path = {1}. output connections file path and name = {2}. export ID = {3}.**

**Cause:** An exception was thrown during an import operation.

**Action:** Examine the exception and resolve the issue that caused the failure.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40062: No object with ID {0}.**

**Cause:** An ID does not correspond to an object.

**Action:** Verify that the ID is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40063: Object with ID {0} expected type {1} actual type {2}.**

**Cause:** An ID does not correspond to an object of the expected type.

**Action:** Verify that the ID and expected type are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40064: Parse error : unknown element "{0}".**

**Cause:** An internal error occurred.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40065: Parse error : unknown attribute "{0}".**

**Cause:** An internal error occurred.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40066: Source portlet ID = "{0}" not found when attempting to create copy name = "{1}" ID = "{2}".**

**Cause:** An ID does not correspond to an object.

**Action:** Verify that the ID is correct.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WCS-40067: Future.get() returned null [activity {0}].**

**Cause:** An internal error occurred.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40068: Future.get() returned type "{0}" expected "{1}".**

**Cause:** An internal error occurred.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40069: Could not import portlet with ID "{0}".**

**Cause:** A suitable offered portlet could not be found.

**Action:** Check that the producer that owns the imported portlet is properly registered.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40070: Portlet lists differ between locale {0} and {1}.**

**Cause:** The remote producer returned unexpected portlets for a particular locale.

**Action:** Check that the remote producer is functioning correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40071: Portlet {0} has no definition.**

**Cause:** An attempt was made to create a RunnablePortletBean based on a PortletBean without a definition.

**Action:** Associate a PortletDef with the PortletBean before creating a RunnablePortletBean.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40072: Mode {0} not allowed on producer offered portlets.**

**Cause:** An attempt was made to change to a invalid mode for a producer offered portlet.

**Action:** Only use this mode for non-offered portlets.



---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40073: Invalid portlet rendition generated.**

**Cause:** An internal error occurred.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40074: Could not import producer with ID "{0}" because that ID is already used by an object of a different type "{1}".**

**Cause:** The ID given for an imported producer is in use.

**Action:** If possible, use a different ID for the imported producer.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40075: Could not import portlet with ID "{0}" because that ID is already used by an object of a different type "{1}".**

**Cause:** The ID given for an imported portlet is in use by an object which is not a portlet.

**Action:** If possible, use a different ID for the imported portlet.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40076: Could not import portlet with ID "{0}" because that ID is already used by a portlet with a different producerPortletId. Importing producerPortletId = "{1}", existing producerPortletId = "{2}".**

**Cause:** The ID given for an imported portlet is in use by a portlet based on a different producer offered portlet.

**Action:** If possible, use a different ID for the imported portlet.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40077: Could not import portlet with ID "{0}" because that ID is already used by a portlet belonging to a different producer with ID "{1}".**

**Cause:** The ID given for an imported portlet is in use by a portlet belonging to a different producer.

**Action:** If possible, use a different ID for the imported portlet.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-40078: Errors during transport: {0}.**

**Cause:** The portlet producer reported errors during an export or import operation.

**Action:** Refer to the errors reported by the producer.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40079: SOAP Exception Fault Code = {0}**

**Cause:** The portlet producer raised a SOAP fault in response to a request.

**Action:** Refer to the error reported by the producer.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40080: Unexpected input of type {0} passed to the {1} pipe.**

**Cause:** An internal error occurred.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40081: Unexpected output of type {0} passed to the {1} pipe.**

**Cause:** An internal error occurred.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40082: Could not create a runnable for portlet {0}.**

**Cause:** An internal error occurred.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40083: Error copying portlet {0}.**

**Cause:** An internal error occurred.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

---

**WCS-40084: Error returned from prepareRendition(): {0}**

**Cause:** An error occurred while preparing portlet markup.

**Action:** Use the reported error message to resolve the issue.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40085: JNDI lookup failed for {0}.**

**Cause:** Looking up an object using the Java Naming and Directory Interface failed.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40086: Unable to obtain interaction for producer {0}.**

**Cause:** An internal error occurred.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40087: WSRP registration returned null producer.**

**Cause:** An internal error occurred.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40088: {0}Pipe caught exception: {1}: {2}**

**Cause:** An internal error occurred.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40089: WSRP producer returned markup but did not specify a MIME type.**

**Cause:** The producer behaved in an unexpected way.

**Action:** Contact the producer's administrator.

**Level:** 1

**Type:** WARNING

**Impact:** Compliance

**WCS-40090: WSRP producer returned both {0} and {1}. The {2} field will be ignored.**

---

**Cause:** The producer behaved in an unexpected way by returning values for mutually exclusive fields.

**Action:** Contact the producer's administrator.

**Level:** 1

**Type:** WARNING

**Impact:** Compliance

**WCS-40091: Parse error processing SOAP response: {0}**

**Cause:** The portlet client was unable to process a response it received from a producer.

**Action:** Check the producer URL and verify that the producer is running. Alternatively, contact the producer's administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WCS-40092: Web producer responded with an error: {0} (Fault code: {1})**

**Cause:** The portlet client received an error in response to a request to a producer.

**Action:** Check the producer URL and service ID. Alternatively, contact the producer's administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WCS-40093: An I/O error occurred while contacting a producer.**

**Cause:** The portlet client was unable to successfully communicate with the producer.

**Action:** Examine the stack trace associated with this message to determine the root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**WCS-40094: Portlet instance "{0}" already exists.**

**Cause:** An attempt was made to create a portlet with a name that is already in use.

**Action:** Retry the operation using a different name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40095: Unable to locate connection: {0}.**

**Cause:** A connection used for a producer cannot be found.

**Action:** Check that the connection exists.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WCS-40096: Unable to locate URL connection: {0}.**

**Cause:** A URL connection used by a producer connection cannot be found.

**Action:** Check that the URL connection exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40097: Error processing notification of {0} operation for object {1}.**

**Cause:** A portlet operation succeeded but notification of a listener failed.

**Action:** Examine the stack trace associated with this message to determine the root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40098: Unsupported WSRP service version: {0}.**

**Cause:** An attempt was made to use a WSRP service of an supported version.

**Action:** Use a version of the WSRP service that is supported or upgrade the portlet client.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**WCS-40099: No suitable WSRP ports found in WSDL at {0}.**

**Cause:** An attempt was made to use a WSDL document that does not define any WSRP ports that are compatible with this version of the portlet client.

**Action:** Verify that the URL for the WSRP WSDL document is correct and that the document is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**WCS-40100: WSRP producer responded with an error ({0}).**

**Cause:** The portlet client received an error in response to a request to a producer.

**Action:** Examine the stack trace associated with this message to determine the cause.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40101: Cannot open Web producer connection.**

**Cause:** An error occurred while opening a Web producer connection.

**Action:** Verify that the connection URL and any proxy server settings are correct.

---

**Level:** 1

**Type:** ERROR

**Impact:** Network

**WCS-40102: Error setting proxy server details ({0}) for connection {1}.**

**Cause:** There is a problem with the proxy server defined for a connection.

**Action:** Correct the proxy server details for the connection.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**WCS-40103: HTTP {0} request to URL {1} failed with status code {2} reason {3}. Check that the producer URL has been correctly specified, that the producer server machine and producer container are running, that the producer application is deployed correctly, and that the client can reach the server if behind a firewall.**

**Cause:** There was a problem communicating over HTTP to a remote producer.

**Action:** Check that the producer URL has been correctly specified, that the producer server machine and producer container are running, that the producer application is deployed correctly, and that the client can reach the server if behind a firewall. Also check that the producer server has no errors.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**WCS-40104: HTTP error**

**Cause:** There was a problem communicating over HTTP to a remote producer.

**Action:** Check that the producer URL has been correctly specified, that the producer server machine and producer container are running, that the producer application is deployed correctly, and that the client can reach the server if behind a firewall. Lastly check that the producer server has no errors.

**Level:** 1

**Type:** ERROR

**Impact:** Network

**WCS-40105: Remote error**

**Cause:** There was an error on the remote producer server.

**Action:** Check the remote producer server logs for further details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40106: Client queue full.**

**Cause:** This request was rejected because the client portlet request queue was full.

**Action:** Resubmit the request, or if this persists consider increasing the configured queue size.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WCS-40107: Client request time out.**

**Cause:** The client portlet request took too long to complete and so was timed out. This could have been because the client was too busy, the network was slow, or the remote producer server was too busy or in error.

**Action:** Resubmit the request, or if this persists consider increasing the configured timeout periods.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40108: Client producer connection not found.**

**Cause:** The client producer connection was not found in connections.xml.

**Action:** Create the producer connection.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40109: Client metadata error.**

**Cause:** An internal error occurred.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40110: Error**

**Cause:** An internal error occurred.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40111: Invalid Keystore Type ({0}).**

**Cause:** The valid keystore types are JKS and PKCS12.

**Action:** Correct the keystore type given for the connection.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40112: Content type error.**

**Cause:** The portlet response was of the wrong content type.

**Action:** This may indicate that the producer is returning an error, or that the URL registered is incorrect and not actually a producer URL, Check the registration and producer server logs.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40113: External Application : {0} does not exist.**

**Cause:** The external application does not exist.

**Action:** Verify that the external application specified in the registration wizard exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40114: Error determining disk cache status.**

**Cause:** An error occurred while requesting the status of the caching service's disk cache.

**Action:** Check the caching service's configuration and log file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40115: Error reading exception from byte array.**

**Cause:** An internal error occurred.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40116: Error writing exception to byte array.**

**Cause:** An internal error occurred.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40117: The portlet attempted to issue a redirect in response to a render request.**

**Redirect URL:** {0}.

**Cause:** The portlet attempted to redirect the browser window in response to a render request.

**Action:** This operation is not allowed in an Oracle WebCenter application. A portlet may only issue a redirect in response to a user interaction directly within the portlet. Contact the portlet developer.

**Level:** 1

**Type:** ERROR

**Impact:** Other



---

**WCS-40118: The parameter {0} may not be used in conjunction with wsrp-urlType {1}. The parameter will be ignored.**

**Cause:** The WSRP portlet markup contained an incorrectly formatted wsrp\_rewrite token.

**Action:** Contact the portlet developer.

**Level:** 1

**Type:** WARNING

**Impact:** Compliance

**WCS-40119: The WSRP service defined by {0} is not compatible with this version of the portlet client.**

**Cause:** The portlet client could not communicate with the remote producer using WSRP. This may be because the WSRP service implements a pre-release version of the WSRP 2.0 specification.

**Action:** If possible, update the WSRP container that is running the service.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**WCS-40120: External application not found.**

**Cause:** The portlet is configured on the client with an external application, however the application or user credential for it was not found.

**Action:** Correct the portlet configuration, external application configuration, or user.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40121: External application authentication failed.**

**Cause:** The portlet is associated with an external application, however the user credentials failed authentication.

**Action:** Correct the user credentials.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40122: ADF context get connections context failed.**

**Cause:** An unexpected error occurred.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40123: Portlet transfer not supported for transfer mode {0}.**

**Cause:** An MDS transfer was performed that included portlet metadata but is not supported by the portlet MDS transfer listener.

---

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40124: Queue Full** [cause={0} submittedTasks={1} queuedTasks={2} queueFreeSpace={3} completedTasks={4} activeThreads={5} corePoolSize={6} keepAliveTime={7} largestPoolSize={8} maxPoolSize={9} poolSize={10} isShutdown={11} isTerminated={12} isTerminating={13}]

**Cause:** A portlet request was submitted to be processed but the queue of portlet requests was already too large so it was rejected.

**Action:** If the server is under load then such warnings are fine, however if the system is not under load then the configuration settings such as thread pool size and queue size should be checked in relation to the server's hardware specification.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40125: Possible loss of portlet customizations for producer {0} : V2 export imported to V1.**

**Cause:** A WSRP V2 producer export may contain portlet customizations but is being imported to a V1 producer which cannot import them.

**Action:** Check that there are either no customizations to be imported, or that it is acceptable to not import them.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40126: This portlet must be rendered within an IFRAME.**

**Cause:** This portlet has declared that it must be rendered within an IFRAME. It cannot be rendered inline on an ADF page.

**Action:** Set the property renderPortletInIFrame on the portlet tag to "auto" or "true".

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40127: Null resource ID for portlet resource request handle "{0}"**

**Cause:** A portlet resource request contained a null resource ID.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40128: Unable to verify or sign resource URL.**

---

**Cause:** The supplied resource key is invalid.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40129: Unable to proxy request for resource with ID: "{0}" due to an incorrect checksum.**

**Cause:** A portlet resource request was received whose URL was not generated by the portlet client.

**Action:** Do not attempt to modify portlet resource URLs.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40130: Portlet {0} needs user property {1}.**

**Cause:** A user property that a portlet requires for complete functionality is not defined in the current context.

**Action:** Specify a value for the missing property.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40131: Error introspecting object of class {0}. Unable to set WSRP UserProfile data correctly.**

**Cause:** An unexpected error occurred.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40132: Unable to set field {0} to value {1} for UserProfile bean of class {2}.**

**Cause:** An exception was thrown while trying to set a UserProfile value.

**Action:** If possible, resolve the issue by setting the corresponding user property value correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40133: User attribute {0} cannot be retrieved from the identity store repository.**

**Cause:** The identity store repository cannot provide the required information.

**Action:** User profile information passed to producers may be incomplete.

**Level:** 1

**Type:** WARNING

---

**Impact:** Other

**WCS-40134: Unable to lookup value for user property {0}.**

**Cause:** User profile information is not available.

**Action:** Verify that the identity store repository is correctly configured.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40135: Security context is not available.**

**Cause:** The current ADFContext does not define a security context.

**Action:** Verify that the application's security settings are correct.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40136: User profile information is not available.**

**Cause:** The current Security Context does not define user profile information.

**Action:** Verify that the identity store repository is correctly configured.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40137: Unable to set field {0} to value {1} for UserProfile bean of class {2}.**

**Expected format:** {3}.

**Cause:** The format of data supplied for UserProfile data is incorrect.

**Action:** If possible, resolve the issue by setting the user property value correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40138: External Application Adapter not configured for portlets.**

**Cause:** A portlet uses an External Application, but an adapter is not configured.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40139: Web adapter using default private key.**

**Cause:** No private key was defined.

**Action:** Set the key to a random value using the 'private.key' Servlet context parameter.

**Level:** 1

**Type:** WARNING

---

**Impact:** Configuration

**WCS-40140: Private key is being padded using a default character sequence.**

**Cause:** The specified private key is too short.

**Action:** Make sure that the value of 'private.key' Servlet context parameter is at least 10 characters in length.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**WCS-40141: Resource URL checksums may not be correct across all nodes.**

**Cause:** Data cannot be written to MDS in order to coordinate private key generation.

**Action:** Make sure MDS is correctly configured and writable.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**WCS-40142: Error removing lock following private key generation.**

**Cause:** A exception was raised while releasing a lock.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40143: Using locally generated private key.**

**Cause:** It was not possible to co-ordinate distributed creation of a key.

**Action:** If possible, resolve the issue using information in this log.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40144: Import of producer {0} failed. The failure has been stored for possible retry.**

**Cause:** A producer import failed, however the operation was instructed to accept and store failures for later retry rather than to fail completely.

**Action:** The reason for failure must be investigated and corrected, then the import retried.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40146: Portlet session invalid.**

**Cause:** A producer response indicated that the session was invalid.

**Action:** Retry the request, but if the problem persists it may indicate a problem with the producer, and the producer status and logs should be checked.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-40147: Could not import portlet with ID "{0}" because the portlet does not exist on the remote producer.**

**Cause:** The producer being imported to is different from that exported from and does not include the specified portlet.

**Action:** Check if the producer being imported to is of the correct type.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40500: Unable to read portlet deployment descriptor from path "{0}".**

**Cause:** The path to the portlet deployment descriptor was wrong.

**Action:** Check that the portlet deployment descriptor exists and is readable at the given directory.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40501: Error processing deployment descriptor "{0}".**

**Cause:** There was a problem parsing the deployment descriptor.

**Action:** Check that the portlet deployment descriptor conforms to the appropriate schema.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40502: Null value passed to method {0}.**

**Cause:** A null value was passed to the specified method.

**Action:** Check that a non-null value is passed to the specified method.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WCS-40503: Unable to load resource bundle "{0}".**

**Cause:** The specified resource bundle could not be found.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40504: Parameter of invalid type passed to method {0}.**

---

**Cause:** One of the parameters passed to the specified method was of an incorrect type.

**Action:** Check that the correct set of parameter types are being passed to the specified method.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WCS-40505: Unable to create instance of class "{0}".**

**Cause:** Unable to create instance of the specified class.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40507: Unrecognized character encoding "{0}".**

**Cause:** The specified character was not recognized.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40508: Window state "{0}" is not allowed in current context.**

**Cause:** The specified window state is not allowed.

**Action:** Check that the use of the specified window state is allowed by the consumer.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WCS-40509: Portlet mode "{0}" is not allowed in current context.**

**Cause:** The specified portlet mode is not allowed.

**Action:** Check that the use of the portlet mode is allowed by the consumer.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WCS-40510: Illegal call to {0}: response is already committed.**

**Cause:** The response was already committed.

**Action:** Do not call the specified method on a committed response.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

---

**WCS-40511: Content type "{0}" is not allowed in current context.**

**Cause:** The response was trying to set a content type that is not allowed by the request.

**Action:** Correct the portlet code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WCS-40512: Value "{0}" not recognized as a session scope.**

**Cause:** The specified value is an invalid value for the session scope.

**Action:** Use one of the session scope values defined by the `javax.portlet.PortletSession` interface.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WCS-40515: Portlet mode "{0}" referenced by portlet "{1}" is not defined in the deployment descriptor.**

**Cause:** The specified portlet mode for the portlet was not defined in the portlet deployment descriptor.

**Action:** Check that the configuration allows for the specified mode.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40516: Error initializing Java Object Cache.**

**Cause:** Java Object Cache failed to start.

**Action:** Consult the Java Object Cache log file for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40517: Error loading preferences from path "{0}".**

**Cause:** Preference data could not be accessed properly.

**Action:** Check the persistence store is configured correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40518: Error saving preferences to path "{0}".**

**Cause:** Preference data could not be accessed properly.

**Action:** Check the persistence store is configured correctly.

**Level:** 1

**Type:** ERROR



---

**Impact:** Configuration

**WCS-40519: Error deleting preferences under path "{0}".**

**Cause:** Preference data could not be deleted.

**Action:** Check the persistence store is configured correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40520: Cannot find JNDI data source with specified name "{0}" or the Oracle Portal repository data source "{1}".**

**Cause:** The JNDI data source in the configuration could not be found at the specified location.

**Action:** Check the container configuration for the data source is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40521: Error getting connection from data source with JNDI path "{0}".**

**Cause:** There was an error getting the connection from the specified data source.

**Action:** Check that the data source referenced is available.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40522: Error getting connection from Oracle Portal repository with the name "{0}".**

**Cause:** There was an error connecting to the Oracle Portal repository.

**Action:** Check that the Oracle Portal repository is available.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40526: An internal error has occurred in method {0}.**

**Cause:** The specified method caused an internal error.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40530: Method {0} cannot be called after method {1}.**

**Cause:** The specified methods were not called in the correct order.

**Action:** Check that the specified methods are called in the correct order.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-40531: No such portlet "{0}".**

**Cause:** The specified portlet was not available.

**Action:** Check that the portlet is available.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40532: Invalid handle "{0}".**

**Cause:** Session, portlet, or registration handle specified was invalid.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40533: Illegal call to {0}: an output stream is already in use.**

**Cause:** The specified method cannot be called once the portlet has started writing binary data.

**Action:** Correct the portlet code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WCS-40534: Illegal call to {0}: a writer is already in use.**

**Cause:** The specified method cannot be called once the portlet has started writing character data.

**Action:** Correct the portlet code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WCS-40535: Illegal call to {0}: a content type has not been set.**

**Cause:** The setContentType() method was not called before the specified method.

**Action:** Correct the portlet code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WCS-40538: Error attempting to create handle "{0}".**

**Cause:** The specified handle could not be created.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

---

**Impact:** Other

**WCS-40539: Error checking for existence of handle "{0}".**

**Cause:** The specified handle could not be found.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40540: Error attempting to delete handle "{0}".**

**Cause:** The specified handle could not be deleted.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-40541: Portlet "{0}" is not modifiable in this context.**

**Cause:** The specified portlet is read only in this context.

**Action:** Check that the portlet is modifiable.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WCS-40542: Invalid URL "{0}".**

**Cause:** The specified URL is invalid.

**Action:** Correct the portlet code.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WCS-40543: Unable to read Web application deployment descriptor from path "{0}".**

**Cause:** The path to the Web application deployment descriptor was incorrect.

**Action:** Check that the Web application deployment descriptor exists and is readable at the given directory.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40544: Value "{1}" for JNDI environment entry "{0}" is not supported.  
Allowable values are "{2}".**

**Cause:** The JNDI environment entry was not one of the allowable values specified.

**Action:** Check the JNDI environment entry is one of the allowable values specified.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**WCS-40545: Location specified for persistent store "{0}" must be a directory.**

**Cause:** The location of the specified persistent store is not a directory.

**Action:** Check the specified persistent store is a directory and that there is not a file in existence at the given location.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40546: Unable to create persistent store root directory at "{0}".**

**Cause:** It was not possible to create the persistent store root directory at the specified location.

**Action:** Check that the parent directory is writable.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40547: Cannot resolve relative path ({0}) for persistent store, oracle.home system property is not set.**

**Cause:** The oracle.home was not set for the specified relative path.

**Action:** Set the oracle.home system property.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40548: Error connecting to database {0}/{1}@{2}.**

**Cause:** There is an error connecting to the specified database.

**Action:** Check that the specified database connection details are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40549: Error obtaining details of persisted objects.**

**Cause:** There was an error obtaining details of persisted objects.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WCS-40550: Unexpected database error.**

**Cause:** An unexpected database error occurred.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

---

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WCS-40551: Unable to create persistent store directory "{0}" for group "{1}".**

**Cause:** It was not possible to create the persistent store directory for the specified group.

**Action:** Check that the parent directory is writable.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40552: Unable to read mime mappings from path "{0}".**

**Cause:** The path to the mime mappings file was wrong.

**Action:** Check that the mime mappings file exists and is readable at the given directory.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40554: Portlet with handle "{0}" is hidden.**

**Cause:** The portlet entity was hidden and not currently available.

**Action:** Make sure the portlet is made available if that is the desired usage.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40555: Error processing file "{0}" at line {1} column {2}.**

**Cause:** An error occurred while processing the file at the specified line and column.

**Action:** Fix the error to the file based on the message specified.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40556: Object named "{0}" could not be found in the persistent store.**

**Cause:** Container object could not be found in the persistent store.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WCS-40561: Request timed out while shutting down portlet "{0}".**

**Cause:** A timeout occurred while waiting for a portlet to shutdown.

**Action:** No action required.

**Level:** 1

---

**Type:** WARNING

**Impact:** Other

**WCS-40562: Exception thrown while shutting down portlet "{0}".**

**Cause:** The specified portlet raised an exception while it was being shutdown.

**Action:** Resolve the issue if possible by looking at the exception raised.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40563: Exception thrown while deleting entity "{0}".**

**Cause:** The specified entity raised an exception while it was being deleted.

**Action:** Resolve the issue if possible by looking at the exception raised.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40564: Exception thrown while releasing session with handle "{0}".**

**Cause:** The specified session raised an exception while it was being released.

**Action:** Resolve the issue if possible by looking at the exception raised.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40565: Invalid security role reference: "{0}".**

**Cause:** The security role specified is invalid.

**Action:** Check and reconfigure the security roles set for the portlets.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**WCS-40566: Locale "{0}" can only be matched to "{1}" Resource Bundle.**

**Cause:** The locale requested by the client is not supported at the language level by the portlet. Fallback to English or Base bundle has occurred.

**Action:** The portlet must support the locale in the request.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**WCS-40570: The oracle.portlet.server.useStatelessProxying request attribute is being ignored when creating a resource URL.**

**Cause:** Stateless proxying is not possible for resources served using the ResourceServingPortlet.serveResource() method.

**Action:** Use the RenderResponse.encodeURL() method to create the resource URL.

---

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40571: The oracle.portlet.server.useStatelessProxying request attribute is being ignored when creating a resource URL.**

**Cause:** Stateless proxying is not possible for resources that require URL rewriting.

**Action:** If URL rewriting of the resource response is not required, set the oracle.portlet.server.resourceRequiresRewriting response attribute to false.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40572: Portlet with handle "{0}" cannot be accessed using WSRP version {1}, it requires at least WSRP version {2}.**

**Cause:** The portlet uses features that are not supported by the version of the WSRP protocol being used to access it.

**Action:** Check that the WSRP producer is accessed using the minimum protocol version (or higher).

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40573: Fast Connection Failover detected. Retrying operation once.**

**Cause:** The portlet container detected that the database used for personalization has performed Fast Connection Failover. The portlet container will retry the operation once.

**Action:** Contact the database administrator.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-40574: Java Object Cache support configured for this portlet application, but no display name specified in web.xml. Java Object Cache support will be disabled.**

**Cause:** Java Object Cache support has been configured to persist portlet registration and preference data, but no display name has been configured for the portlet application in web.xml. Java Object Cache support will be disabled for this portlet application.

**Action:** Specify a unique display-name for this portlet application in web.xml

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40575: PortletApplicationImpl.initHandler error processing config handler "{0}".**

**Cause:** Error processing the specified config handler.

---

**Action:** Check the JNDI environment entry mentioned.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40576: PortletApplicationImpl.initHandler error calling config handler setters "{0}" and "{1}".**

**Cause:** Error calling the specified config handler setters.

**Action:** Check the locations of these files.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40577: PortletApplicationImpl.loadMimeCsMappings() error closing input stream "{0}".**

**Cause:** The path to the mime mappings file was wrong.

**Action:** Check that the mime mappings file exists and is readable at the given directory.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-40578: PortletApplicationImpl.isConfigFileChanged error calling config handler has changed methods for "{0}" and "{1}".**

**Cause:** Error calling the specified config handler with change methods.

**Action:** Check the locations of these files.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-42301: The external application ID {0} found while rendering the credential provisioning page is invalid.**

**Cause:** The external application being referred was probably deleted.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**WCS-42302: No back URL exists in the process scope.**

**Cause:** The credential provisioning page could not establish the back URL because of the following possible reasons: 1) The page was run either in the standalone mode or as a dialog. 2) There was some unexpected error while setting the back URL in the process scope.

**Action:** Contact Oracle Support Services.

**Level:** 1



---

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**WCS-42303: cannot retrieve the back URL to redirect the credential provisioning page**

**Cause:** An I/O error occurred while trying to obtain the back URL to redirect the credential provisioning page.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**WCS-42304: The external application ID is found to be null while rendering the credential provisioning page.**

**Cause:** The credential provisioning page was probably run standalone, or it was invoked from a portlet added from a producer that was not associated with an external application.

**Action:** While running the credential provisioning page, ensure that: 1) It is not run in the standalone mode. 2) It is invoked from the link in portlets added from the producers associated with the external application.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-42305: The page is available only to authenticated users.**

**Cause:** You had not logged into the application before accessing the external application credential provisioning page.

**Action:** Ensure that you have logged in before accessing the external application credential provisioning page.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-42306: cannot initialize credential provisioning page**

**Cause:** An unexpected error occurred while trying to initialize the external application. Review the underlying exception in the logs for exact cause.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**WCS-42307: cannot store credentials of external application {0} for user {1}**

**Cause:** There was an unexpected error while trying to store external application credentials for the user. Review the underlying exception in the logs for exact cause.

---

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**WCS-42501: An unexpected error occurred.**

**Cause:** Review the root cause of the exception for more details.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**WCS-42502: A required parameter is missing. Parameter=[{0}]**

**Cause:** An attempt was made to invoke a method without passing all the required parameters.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**WCS-42503: call to API {0} not supported at design time**

**Cause:** This operation was not supported at design time.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

**WCS-42504: The external application context cannot be configured.**

**Cause:** An unexpected error occurred in initializing the external application manager while setting up the context. Review the underlying exception in the logs for the exact cause.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**WCS-42505: The page is available only to authenticated users.**

**Cause:** A null user subject was obtained while trying to automatically log in to the external application.

**Action:** Ensure that the user has logged into the application before accessing the automated login functionality.

**Level:** 1

---

**Type:** ERROR

**Impact:** Security

**WCS-42506: An unexpected error occurred while trying to automatically log in to the external application.**

**Cause:** An error occurred while trying to log in to the external application. Review the underlying exception in the logs for more details.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**WCS-42507: The external application that needs to be accessed cannot be found.**

**Cause:** The external application ID was not available in the servlet request.

**Action:** Ensure that the external application ID is passed in the form of the extappid parameter while invoking the automated login servlet.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-42508: cannot automatically log in to the external application**

**Cause:** The login URL was not specified for the external application being used for automated login.

**Action:** To use the automated login functionality for an external application, ensure that the login URL is specified.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-42509: A list of all external application connections cannot be obtained.**

**Cause:** An unexpected error occurred while trying to obtain the list of all external application connections. Review the underlying exception in the logs to determine the exact cause.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**WCS-42510: Connection for the external application {0} cannot be obtained.**

**Cause:** An unexpected error occurred while trying to obtain the connection for the external application. Review the underlying exception in the logs to determine the exact cause.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

---

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**WCS-42511: Cannot encode string {0} using encoding scheme {1}**

**Cause:** Encoding Scheme was not supported

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-42512: An error occurred after notifying service of change in the external application {0} credentials.**

**Cause:** An unexpected error occurred while the service was trying to process change in the external application credentials.

**Action:** Review the underlying exception in the logs. If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-42513: An unexpected condition occurred while trying to automatically log in to the external application {0} - {1}**

**Cause:** A unexpected condition while trying to log in to the external application. Review the underlying exception in the logs for more details.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-42601: The login URL {0} obtained for the external application {1} is invalid.**

**Cause:** The data in the external application definition was damaged.

**Action:** Check the underlying connection data and ensure that the URL for the specified external application is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-42602: The option for enabling automated login for the external application is not supported.**

**Cause:** The login URL for the external application was not specified.

**Action:** To enable automated login for the external application, set the login URL for the application.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**WCS-42603: cannot process authentication failure for external application {0}**

**Cause:** Public credentials were not enabled for this external application.

**Action:** To obtain external application credentials for a public user, configure the external application to specify public credentials.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-42604: Credentials cannot be stored or deleted.**

**Cause:** The external application identifier was not specified for the credential.

**Action:** Specify the external application identifier for the credential and then try to store or remove the credential.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WCS-42605: user {0} not authorized to access external application {1}**

**Cause:** The user did not have access to the external application.

**Action:** Contact your administrator for the necessary permission. If you are a public user, the administrator needs to allow public access to this external application by specifying public credentials.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-42606: The credentials specified by the user {0} for the external application {1} are invalid.**

**Cause:** Credentials for the external application have changed.

**Action:** Invoke the credential provisioning page to accept the latest set of credentials.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-42607: Shared access credentials for the external application {0} are invalid.**

**Cause:** Shared access credentials for the external application may have changed.

**Action:** Contact the administrator to update the shared access credentials.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-42608: Public access credentials for external application {0} are invalid.**

**Cause:** Public access credentials for the external application may have changed.

**Action:** Contact the administrator to update the public access credentials.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-42609: Credentials not found for the user {0} for the external application {1}.**

**Cause:** external application credentials were not provisioned for the user.

**Action:** Provide a link to the credential provisioning page so that the user can specify credentials.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-42610: Unable to obtain shared or public credentials for the external application {0}.**

**Cause:** The shared or public credentials might have been damaged.

**Action:** Contact the administrator to specify the credentials. If the error still persists, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**WCS-42613: Credentials cannot be deleted for the external application {0}.**

**Cause:** The credential store may not have been configured correctly.

**Action:** Ensure that the credential store is configured correctly.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-42614: Field {0} in external application {1} is invalid.**

**Cause:** The external application field used for the store or fetch credential operation does not exist.

**Action:** Check the field name used for the operation and ensure that it has been defined.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-42651: The listener {0} cannot be added to the external application.**

**Cause:** An unexpected error occurred while trying to register the listener. Review the underlying exception in the logs to determine the exact cause.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

---

**WCS-42652: The listener {0} cannot be deregistered.**

**Cause:** An unexpected error occurred while trying to deregister the listener. Review the underlying exception in the logs to determine the exact cause.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**WCS-42653: An external application with the name {0} already exists.**

**Cause:** The name specified for the external application was already used by another application.

**Action:** Specify a unique name for the external application.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-42654: URL {0} specified for external application {1} is invalid.**

**Cause:** The HTTP URL set for the external application was invalid.

**Action:** Specify a valid HTTP URL.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-42655: Property {0} specified for external application {1} is invalid.**

**Cause:** The property specified for the external application was either null or empty.

**Action:** Set a valid value for the specified property.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-42656: The authentication method {0} specified for the external application {1} is invalid.**

**Cause:** The authentication method set for the external application was not one of the following: GET, BASIC, or POST.

**Action:** Set the authentication method as GET, POST, or BASIC. The default authentication method is POST.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-42657: Field {0} already exists in external application {1}.**

**Cause:** A duplicate field was encountered in the additional fields definition.

**Action:** Ensure that the names of the additional fields defined for the external application are unique.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-42658: default value not specified for Field {0} in external application {1}**

**Cause:** The specified additional field of the external application was marked as hidden.

**Action:** Specify a default value for the additional field marked as hidden. If there is no default value, mark the field as to be displayed to users.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-42659: The {0} credential specified for external application {1} is invalid.**

**Cause:** Either the user name or password was not specified.

**Action:** Ensure that both the user name and password are specified for shared or public credentials in an external application.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-42660: external application {0} not found**

**Cause:** The name passed for retrieving the external application was invalid or the underlying external application was deleted.

**Action:** Pass a valid external application name for retrieving the application.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-42661: The ID of the external application cannot be set.**

**Cause:** The external application ID could not be set because the external application already had an ID set.

**Action:** The ID of an external application cannot be modified. To set a new ID, delete the external application and re-create the application with a new ID.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WCS-42662: The external application {0} cannot be created.**

**Cause:** An external application with the specified name already existed.

**Action:** Specify a unique name for your external application.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-42663: The external application {0} cannot be created.**



---

**Cause:** An unexpected error occurred while trying to create the external application. Review the underlying exception in the logs to determine the exact cause.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**WCS-42664: The external application {0} cannot be modified.**

**Cause:** An unexpected error occurred while trying to modify the external application. Review the underlying exception in the logs to determine the exact cause.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**WCS-42665: cannot delete external application {0}**

**Cause:** An unexpected error occurred while trying to delete the external application. Review the underlying exception in the logs to determine the exact cause.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**WCS-42666: An error has occurred while trying to retrieve the external application {0}.**

**Cause:** An unexpected error occurred while trying to obtain the given external application. Review the underlying exception in the logs to determine the exact cause.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**WCS-42667: An error has occurred while trying to retrieve all available external applications.**

**Cause:** An unexpected error occurred while trying to obtain all external applications. Review the underlying exception in the logs to determine the exact cause.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**WCS-42668: An error has occurred while trying to check if the specified external application name {0} is already used by another external application.**

**Cause:** An unexpected error occurred while trying to check if the external application name was already used. Review the underlying exception in the logs to determine the exact cause.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**WCS-42669: An error has occurred while trying to obtain a list of external application names.**

**Cause:** An unexpected error occurred while trying to obtain a list of external application names. Review the underlying exception in the logs to determine the exact cause.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**WCS-42670: An error has occurred while trying to obtain a map containing the ID-name pair of the external application.**

**Cause:** An unexpected error occurred while trying to obtain a map containing the ID-name pair of the external application. Review the underlying exception in the logs to determine the exact cause.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**WCS-42671: An external application with the display name {0} already exists.**

**Cause:** The display name specified for the external application was already used by another application.

**Action:** Specify a unique display name for the external application.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-42701: An unexpected naming exception has occurred while trying to create the external application connection {0}.**

---

**Cause:** An unexpected naming exception occurred while trying to create an external application connection. Review the underlying exception in the logs to determine the exact cause.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**WCS-42702: cannot update external application connection {0}**

**Cause:** An unexpected naming exception occurred while trying to update the external application connection. Review the underlying exception in the logs to determine the exact cause.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**WCS-42703: cannot delete external application connection {0}**

**Cause:** An unexpected naming exception occurred while trying to delete the external application connection. Review the underlying exception in the logs to determine the exact cause.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**WCS-42704: An unexpected naming exception has occurred while trying to look up the external application connection {0}.**

**Cause:** An unexpected naming exception occurred while trying to look up the external application connection. Review the underlying exception in the logs to determine the exact cause.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**WCS-42705: An unexpected naming exception has occurred while trying to list all available external application connections.**

**Cause:** An unexpected naming exception occurred while trying to list external application connections. Review the underlying exception in the logs to determine the exact cause.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**WCS-42706: Invalid fragment obtained while trying to build the external application connection from the reference {0}.**

**Cause:** Could not parse the required external application connection attributes from the reference because the entry in connections.xml may have been tampered with.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**WCS-42707: An unknown error occurred while trying to obtain connections context.**

**Cause:** An unknown exception occurred while trying to obtain connections context. Review the underlying exception in the logs to determine the exact cause.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**WCS-42708: A Connection Store cannot be configured for the external application {0}.**

**Cause:** An unexpected error occurred while trying to set up the connection store for the application. Review the underlying exception in the logs to determine the exact cause.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**WCS-42801: An error occurred while creating a transferable object for the external application connection {0}.**

**Cause:** An unexpected error occurred while creating a transferable object for an external application connection. Review the underlying exception in the logs to determine the exact cause.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

---

**WCS-42802: An error occurred while generating the transfer data for the external application connection {0}. DataFlavor={1}, TransferData={2}**

**Cause:** An unexpected error occurred while generating the transfer data for an external application connection. Review the underlying exception in the logs to determine the exact cause.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**WCS-42803: cannot initialize the Resource Catalog adapter.**

**Cause:** An unexpected error occurred while initializing the Resource Catalog adapter. Review the underlying exception in the logs to determine the exact cause.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**WCS-43001: Unable to find the service with ID "{0}" in the service registry.**

**Cause:** Either the service ID is wrong or the corresponding META-INF/service-definition.xml file is not available in the classpath.

**Action:** Ensure the service ID is correct and the corresponding META-INF/service-definition.xml file is available in the classpath. Note: service-definition.xml file is mostly available from service libraries (within .jar file) of each service, make sure the required service libraries are in the classpath.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43002: Cannot add service to the registry with the same ID. Service with ID "{0}" is already registered from source "{1}". Failed to add service read from source "{2}".**

**Cause:** Either the service-definition contains a service Id that conflicts with another service definition or the same service library (.jar containing the service-definition.xml) is available from multiple classpath locations.

**Action:** Ensure the service ID is correct in the corresponding META-INF/service-definition.xml file. Also ensure the same jar file is not available from multiple classpath locations.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43003: Failed to parse the service-definition.xml found at location "{0}". Due to : {1}**

**Cause:** Either the service-definition.xml does not conform to the schema or its not well-formed xml file or its not readable.

---

**Action:** Verify the corresponding service-definition.xml file conforms to the schema with well-formed xml and read access is set on it.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43004: ServiceContext resource configuration file "{0}" not found, cannot proceed.**

**Cause:** The main configuration file that defines the default implementation of ServiceContext class is missing.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-43005: ServiceContext resource configuration file "{0}" found, but the data is missing. Cannot proceed.**

**Cause:** The main configuration file that defines the default implementation of ServiceContext class is misconfigured, all the required data is not available in this file.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-43006: ServiceContext resource configuration file "{0}" found, but the class defined "{1}" is not an instance of oracle.webcenter.framework.service.ServiceContext.**

**Cause:** The main configuration file that defines the default implementation of ServiceContext class is misconfigured, the supplied class is not an instance oracle.webcenter.framework.service.ServiceContext.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-43007: service-definition being processed from source location "{0}" does not conform to the schema. Missing 'definitions' tag.**

**Cause:** This is caused due to wrong configuration of service-definition.xml file.

**Action:** Update the corresponding file and ensure it starts with 'definitions' tag with namespace as 'http://xmlns.oracle.com/webcenter/framework/service' (e.g.: <definitions xmlns="http://xmlns.oracle.com/webcenter/framework/service">).

**Level:** 1

**Type:** WARNING

**Impact:** Other

---

**WCS-43008: Required attribute "{0}" missing from tag "{1}".**

**Cause:** This is caused when the user is required to set the mandatory attribute for the given tag, but and its not set.

**Action:** Modify the appropriate configuration file to and supply the mandatory attribute with corresponding value.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43009: Attempt to invoke "{0}" method on class "{1}", when its locked.**

**Cause:** This class or method is locked and cannot be invoked in the current state.

**Action:** Do not invoke methods on this class in a state its not accessible, please check the class documentation for more help.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43010: Scope object cannot be null.**

**Cause:** This is caused when an attempt is made to set scope with null value.

**Action:** Supply a valid scope object, or create a scope from ServiceContext.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43011: Unable to find the "{0}" view definition from service: {1}.**

**Cause:** The required view definition is missing from the service-definition file.

**Action:** Check the appropriate service-definition.xml file to have an entry of the required view definition. Refer to service documentation for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43012: Error occurred processing the service-definition.xml file from source location "{0}". Due to: {1}.**

**Cause:** Either the service-definition is malformed or does not conform to the schema defined.

**Action:** Update the corresponding service-definition.xml with correct details.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43013: ExtensionRegistry instance found "{0}" for registry Id "{1}", is not an instance of {2} class.**

**Cause:** This is caused due to wrong configuration of adf-service-config tag in the adf-config.xml file.

---

**Action:** Check the adf-config.xml file for an entry of adf-service-config tag. Search for extension-registry tag here with ID "oracle.webcenter.framework.service.ServiceRegistry", this tag's registry-class attribute should point to a class that is extending from ServiceRegistry class.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43014: Either the supplied registry Class "{0}" for extension-registry ID "{1}", is not an instance of oracle.webcenter.framework.service.ExtensionRegistry or the class is not available in the classpath. Please check the adf-config.xml for corresponding configuration details.**

**Cause:** This is caused due to wrong configuration of extension-registry in the adf-config.xml file.

**Action:** Check the adf-config.xml file for an entry of adf-service-config tag. Search for extension-registry tag and ensure this tag's registry-class attribute point's to a class that is an instance of 'oracle.webcenter.framework.service.ExtensionRegistry' class. Also this class should be available in the classpath, otherwise it will fail to load.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43015: Unable to find the Extension Registry information in the adf-config for registry ID "{0}". Please check the adf-config.xml for corresponding configuration details.**

**Cause:** This is caused due to missing tension-registry in configuration in the adf-config.xml file.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-43016: Either the supplied handler Class "{0}" for extension-registry ID "{1}", is not an instance of oracle.webcenter.framework.service.ExtensionHandle or the class is not available in the classpath. Please check the adf-config.xml for corresponding configuration details.**

**Cause:** This is caused due to wrong configuration of extension-registry in the adf-config.xml.

**Action:** Check the adf-config.xml file for an entry of adf-service-config tag. Search for extension-registry tag and ensure this tag's handler-class attribute point's to a class that is an instance of 'oracle.webcenter.framework.service.ExtensionHandler' class. Also this class should be available in the classpath, otherwise it will fail to load.

**Level:** 1

**Type:** WARNING

**Impact:** Other



---

**WCS-43017: Extension tag name cannot be null or empty value.**

**Cause:** Wrong extension configuration, mandatory tag name cannot hold null or empty string.

**Action:** Refer to the service framework documentation for details on extension-registry configuration.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43018: No Extension Registry information available for element type "{0}", with the ServiceRegistry. Please check the adf-config.xml for extension registry configuration details.**

**Cause:** This is caused due to missing extension-registry configuration in the adf-config.xml for the specified registry Id.

**Action:** Check the adf-config.xml file for an entry of adf-service-config tag. Search for extension-registry tag for the appropriate registry Id that is missing and ensure all the registry details are provided.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43019: ADFConfig does not contain adf-service-config details. Ensure adf-config.xml file contains adf-service-config tag with namespace : {0}.**

**Cause:** This is caused due to missing adf-service-config tag from adf-config.xml file.

**Action:** Check the adf-config.xml file for an entry of adf-service-config tag.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43020: No ADF Config information.**

**Cause:** ADFConfig could not be acquired, either adf-config.xml file is missing or application is not configured properly.

**Action:** >Examine the adf-config.xml file and add or update the WebCenter section.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-43021: No Oracle WebCenter Framework information in adf-config file.**

**Cause:** The application adf-config.xml was found, but the Oracle WebCenter Framework section could not be read or is missing.

**Action:** Examine the adf-config.xml file and add or update the WebCenter section.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**WCS-43022: Unable to find ResourceUriListener class: {0}.**

**Cause:** Either the class name is wrongly configured or the class is not available in the classpath for this application to load.

**Action:** Examine the adf-config.xml file and add or update the WebCenter section specifying the resource Uri class.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-43023: Unable to instantiate ResourceUriListener class: {0}.**

**Cause:** Either the class does not have required constructor or it fails to initialize.

**Action:** Ensure the supplied ResourceUri Listener class implements the proper interface and has the required constructors.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WCS-43024: Unable to access ResourceUriListener class: {0}.**

**Cause:** This is caused when the application tries to reflectively create an instance, set or get field or invoke methods, but the currently executing method does not have access to the definition of the specified class, field, methods or constructor.

**Action:** Ensure that the ResourceUri Listener class implements the proper interface and all its required methods and constructors have public access.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WCS-43025: Failed to initialize specified ResourceUri Handler.**

**Cause:** A runtime problem occurred whilst initializing the Resource handler.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-43026: No resource ID found for resource group: {0}.**

**Cause:** This error occurs when the resource view does not define corresponding group ID.

**Action:** Supply valid resource group ID.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43027: Failed to generate an absolute URL to a resource view.**

**Cause:** A runtime problem occurred whilst generating the absolute URL to a resource view.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-43028: Scope with name "{0}" already exists.**

**Cause:** This error occurs when user tries to create a scope with a name that is already created. Duplicate scopes are not allowed.

**Action:** Chose a different name for the scope.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43029: Scope with name "{0}" does not exist.**

**Cause:** This error occurs when user tries to read a scope with a name that is not created earlier.

**Action:** Create the scope with the appropriate name and then access it.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43030: Could not handle complex element "{0}". Neither element has a class attribute nor any of the ElementTypeResolvers could handle it.**

**Cause:** This can occur due to missing extension-registry configuration in the adf-config.xml or there is no set/add method on the corresponding application bean to handle complex node.

**Action:** Have a proper extension handler registered for this complex node or have set/add method on the bean with the tag name.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43031: XML processing error: unable to create instance of the class: {0}. {1}**

**Cause:** This can occur due to missing extension-registry configuration in the adf-config.xml or there is no set/add method on the corresponding application bean to handle complex node.

**Action:** Have a proper extension handler registered for this complex node or have set/add method on the bean with the tag name.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43032: Class: {0} does not have set or add method for tag: {1}.**

**Cause:** This can occur due to missing extension-registry configuration in the adf-config.xml file or there is no set/add method on the corresponding application bean to handle complex node.

**Action:** Have a proper extension handler registered for this complex node or have set/add method on the bean with the tag name.

---

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43033: An error occurred processing the xml, due to: {0}.**

**Cause:** Runtime problem invoking the operation.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-43034: Unable to set or get an ADF Preference value.**

**Cause:** The ADF Preference service raised an exception whilst initializing, getting or setting a preference value.

**Action:** Check MDS classpath includes PreferenceNode.xsd.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43036: Cannot provide the resource link. No FacesContext and no webapp base URL set.**

**Cause:** Unable to build up a URL to WebCenter from outside of the web application.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-43038: Unable to find help for the current topic.**

**Cause:** Either the help system is not setup or it is not accessible.

**Action:** Examine the WebCenter Configuration for Help and make sure that Help System is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WCS-43039: Scope Provider resource configuration file "{0}" not found, cannot proceed.**

**Cause:** The main configuration file that defines the default implementation of ScopeMetadataProvider class is missing.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

---

**WCS-43040: Scope Provider resource configuration file "{0}" found, but the data is missing. Cannot proceed.**

**Cause:** The main configuration file that defines the default implementation of ScopeMetadataProvider class is misconfigured, all the required data is not available in this file.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-43041: ScopeMetadataProvider resource configuration file "{0}" found, but the class defined "{1}" is not an instance of oracle.webcenter.framework.service.ScopeMetadataProvider.**

**Cause:** The main configuration file that defines the default implementation of ScopeMetadataProvider class is misconfigured, the supplied class is not an instance oracle.webcenter.framework.service.ScopeMetadataProvider.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-43042: Resource Action not created due to missing attributes.**

**Cause:** The Group ID (Service ID) and the Resource ID are not present as f:attribute values in the consuming JSPX page.

**Action:** Check the JSPX page where this originated from and make sure you add the groupId and resourceId attributes and that they are not null.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43043: Failed to load resource action handler class "{0}"; using default.**

**Cause:** The resource action handler class specified failed to load.

**Action:** Check the classpath to inspect whether this class is available; then check accompanying exceptions in the log to further debug the cause.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43044: Failed to parse view renderer "{0}" as a valid TaskFlow ID; returning null.**

**Cause:** The specified task flow ID cannot be parsed properly.

**Action:** Check the value of the view renderer specified and investigate how you arrived at that value.

**Level:** 1

**Type:** WARNING

**Impact:** Other

---

**WCS-43045: Failed to parse view renderer "{0}" as a valid TaskFlow ID; treating it as a View ID instead.**

**Cause:** The specified task flow ID cannot be parsed properly.

**Action:** Check the META-INF/service-definition.xml of the service to verify whether it is a view ID or a TaskFlow ID by checking the documented syntax of both.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43046: Can not find TaskFlowId in pageFlowScope; returning null.**

**Cause:** The task flow ID sought in the pageFlowScope is not found.

**Action:** This is an internal warning and should not be acted on.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43047: The JPS Service Locator cannot be obtained.**

**Cause:** The error was caused while obtaining the JPS Service Locator. Review the underlying exception in the logs to determine the exact cause.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Security

**WCS-43048: User Principal could not be found for authenticated user.**

**Cause:** This indicates an error with the Identity Store, or Java Platform Security setup.

**Action:** This is an internal warning. The Administrator needs to verify the Identity Store setup.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43049: An error occurred reading the Connections Context.**

**Cause:** This indicates an error with reading the Connection Context.

**Action:** Refer to exception detail. If insufficient details to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43050: An error occurred reading a service's configuration.**

**Cause:** This indicates an error with reading a service's configuration.

---

**Action:** Refer to exception detail. If insufficient details to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43051: cannot access Java Object Cache**

**Cause:** An exception occurred while accessing Java object cache.

**Action:** Review the exception thrown for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43052: cannot create userprofile region in Java Object Cache**

**Cause:** An exception occurred while creating userprofile region in Java object cache.

**Action:** Review the exception thrown for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43053: cannot destroy userprofile region in Java Object Cache.**

**Cause:** An exception occurred while removing userprofile region from Java object cache.

**Action:** Review the exception thrown for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43054: An error occurred while trying to lookup connection {0}.**

**Cause:** The name may not have been pointing to a valid connection, or some other error occurred when trying to retrieve the connection object.

**Action:** Ensure that the connection defined in connections.xml is valid and that the necessary classes can be loaded.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43055: Resource can not be displayed because the authorizerClass {0} is not found.**

**Cause:** Class specified by authorizerClass is not found.

**Action:** Check the class path of the application to verify inclusion of the authorizerClass.

**Level:** 1

**Type:** WARNING

---

**Impact:** Other

**WCS-43056: Database type {0} is not recognised.**

**Cause:** WebCenter has been configured with a database platform that is not recognized.

**Action:** Ensure that the database platform type is set correctly.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43057: Error closing entity manager factory**

**Cause:** An unexpected exception occurred while closing the entity manager factory.

**Action:** Review the exception thrown for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-43058: Could not load LifecycleListener class for "{0}" from the service definition.**

**Cause:** An unexpected exception occurred while attempting to access the LifecycleListener.

**Action:** Review the exception thrown for more details.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-44001: cannot load role provider implementation for service ID: {0}**

**Cause:** The provider class configured in role-mapping-metadata tag of the specified service definition was not available to the classloader.

**Action:** Ensure that the provider class specified in the service-definition.xml file is available to the classloader.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WCS-44002: The Role Mapping provider encountered an exception while performing security role mapping for service {0}.**

**Cause:** This is caused by an error experienced by service-specific Role Mapping provider.

**Action:** Inspect the server logs and rectify the problem encountered by the service Role Mapping provider.

**Level:** 1

**Type:** ERROR

**Impact:** Security



---

**WCS-44003: The Role Mapping provider cannot find the service role: {0}. Exception from the provider: {1}.**

**Cause:** The Role Mapping provider cannot find the service role. Review the exception from the provider to determine the exact cause.

**Action:** Inspect the server logs and rectify the problem encountered by the service Role Mapping provider.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WCS-44004: An internal JPS error has occurred while retrieving information from the Application Policy Store.**

**Cause:** This may have been caused when retrieving information from the Application Policy Store.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Security

**WCS-44005: cannot find security extension in Service Registry for service ID: {0}**

**Cause:** No security extension was registered for the given service.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Security

**WCS-44006: There is no mapped service role for the WebCenter role {1} to which the user {0} is assigned.**

**Cause:** A user was assigned to a WebCenter role that was not yet mapped to any service role.

**Action:** Ensure that the WebCenter role is mapped to a service role.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WCS-44007: An internal JPS error has occurred while initializing the Application Policy Store.**

**Cause:** The Application Policy Store (jps-config.xml) was probably not configured correctly.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Security

---

**WCS-44009: Error obtaining JPS Service instance: {0}.**

**Cause:** The value returned for the JPS Service instance was null. This may be caused by configuration error in jps-config.xml.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Security

**WCS-44010: A JPS error is encountered while deleting users from the service ID/service role: {0} / {1}.**

**Cause:** The error was caused while accessing the application policy store for deleting users. Review the underlying exception in the logs to determine the exact cause.

**Action:** If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Security

**WCS-44101: Invalid PeoplePicker Scope {0} passed.**

**Cause:** The scope is not of the valid type. It can be GLOBAL or SUB\_SCOPED

**Action:** Pass a valid scope

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**WCS-44102: Invalid PeoplePicker Scope ID {0} passed.**

**Cause:** An invalid Scope ID has been passed.

**Action:** Ensure a valid scope/community ID is passed.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**WCS-44103: Unknown error encountered while selecting user(s) in people picker.**

**Cause:** Review the root cause of the exception for more details.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Security

**WCS-44104: Scope Id is a required parameter for scoped people search.**

**Cause:** Scope Id not provided.

**Action:** Provide Scope Id.

**Level:** 1

---

**Type:** WARNING

**Impact:** Security

**WCS-44105: And unknown error occurred while trying to validate if user {0} exists**

**Cause:** Review the root cause of the exception for more details.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Security

**WCS-44106: Unknown error encountered while selecting group(s) in group picker.**

**Cause:** Review the root cause of the exception for more details.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Security

**WCS-44107: And unknown error occurred while trying to validate if group {0} exists**

**Cause:** Review the root cause of the exception for more details.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Security

**WCS-44108: The search exceeded the time limit. Check the identity store connection details or refine your search criterion.**

**Cause:** The underlying identity store and policy store could be down.

**Action:** Check that underlying repositories are accessible. Check logs and contact Oracle Support

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WCS-44109: The search exceeded the size limit. Refine your search criterion.**

**Cause:** The search results in a large dataset that is not supported by the underlying identity store.

**Action:** Refine your search criterion to something more narrow.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WCS-44110: An unexpected error occurred while searching for users/roles. Check logs for further details.**

**Cause:** An unexpected error occurred while searching for identities. Consult the underlying cause.

---

**Action:** If the underlying cause does not provide any action, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WCS-44151: An error is encountered while retrieving the Identity Store.**

**Cause:** This is caused when the Identity Store configured in jps-config.xml is not accessible or is not running.

**Action:** Ensure that the Identity Store is configured correctly in jps-config.xml and is running.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WCS-44152: An error is encountered while sending an e-mail.**

**Cause:** The error occurred because the e-mail account or the e-mail service was not configured correctly or the e-mail server was not running.

**Action:** Ensure that your e-mail account and the e-mail service are configured properly and the e-mail server is running.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WCS-44153: An error is encountered while generating the HMAC token.**

**Cause:** The JVM did not support MessageDigest algorithms, such as MD5 or SHA, or the UTF8 encoding.

**Action:** Ensure the JVM supports UTF8 encoding and MD5/SHA message digest algorithms. If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WCS-44154: An error has occurred while getting the scope roles for scope ID {0}.**

**Cause:** Either the policy store was configured incorrectly or was inaccessible or the scope ID passed was invalid.

**Action:** Ensure that the policy store is configured correctly and is running. Also, ensure that the scope ID passed is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WCS-44155: The permission class is null for the service ID: {0}.**

**Cause:** The permission class was not defined in the service-definition.xml file.

---

**Action:** Ensure that the permission class is defined in the service-definition.xml file for the service.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WCS-44156: The value of resource bundle is null for the service ID: {0}.**

**Cause:** The resource bundle was not defined in the service-definition.xml file.

**Action:** Ensure that the resource bundle is defined in the service-definition.xml file.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WCS-44157: The value of permission target is null for the service ID: {0}.**

**Cause:** The permission target was not defined in the service-definition.xml file.

**Action:** Ensure that the permission target is defined in the service-definition.xml file.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WCS-44158: The value of permission action is not defined for the service ID: {0}.**

**Cause:** The permission action (permission-action-list tag) was not defined in the service-definition.xml file.

**Action:** Ensure that the permission actions are defined in the service-definition.xml file by using the permission-action-list tag.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WCS-44159: The value of permission admin action is not defined for the service ID: {0}.**

**Cause:** The permission admin action (permission-manage-action tag) was not defined in the service-definition.xml file.

**Action:** Ensure that the permission admin actions are defined in the service-definition.xml file by using the permission-manage-action tag.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WCS-44160: The role mapping class is not defined for the service ID: {0}.**

**Cause:** The role mapping class was not defined in the service-definition.xml file.

**Action:** Ensure that the role mapping class is defined in the service-definition.xml file.

---

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WCS-44161: The role mapping resource bundle is not defined for the service ID: {0}.**

**Cause:** The role mapping resource bundle was not defined in the service-definition.xml file.

**Action:** Ensure that the role mapping resource bundle is defined in the service-definition.xml file.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WCS-44162: Security Extension is not defined for the service ID: {0}.**

**Cause:** The Security Extension (security-definition node) was not defined in the service-definition.xml file of the service.

**Action:** Ensure that the Security Extension (security-definition node) is properly defined in the service-definition.xml file.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WCS-44163: An error has occurred while retrieving service extension definition(service-definition.xml).**

**Cause:** The service jars are not correctly packaged or the jars are corrupt.

**Action:** Ensure that webcenter framework shared library is correctly defined and the library jars are not corrupt.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WCS-44164: An error has occurred while retrieving the spi file .**

**Cause:** There are multiple spi files.

**Action:** Ensure that only spi file with the name oracle.webcenter.security.selfregistration.custom.SelfRegActionHandlerSpi.properties exists.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WCS-44165: The principal is not of type JpsRole**

**Cause:** The principal object passed to the api is not of type JpsRole.

**Action:** Ensure that the parameter passed to the api is of type JpsRole.

**Level:** 1

**Type:** WARNING

---

**Impact:** Security

**WCS-44166: Application Policy for {0} does not exist. Creating a new application policy.**

**Cause:** The application did not package any policies.

**Action:** None as a new policy has been created. However ensure that application did not indeed package any policies and this was not a case of policies not being migrated. Contact Oracle Support in that case.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WCS-44167: Public registration is not enabled for this site.**

**Cause:** The public registration option is not enabled.

**Action:** Ensure that public registration is enabled in the general tab of Webcenter administration.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WCS-44168: The principal argument is null**

**Cause:** The principal object passed to the api is null.

**Action:** Ensure that the parameter passed to the api is not null.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WCS-44169: Error while determining security attributes for user {0}**

**Cause:** The user {0} passed to determine security attributes does not exist in the underlying identity store.

**Action:** Ensure the user name is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WCS-44170: Error occurred while retrieving the security attributes of user {0}**

**Cause:** An error occurred while querying the identity store or the policy store to determine the user's security attributes. Review the underlying exception in the logs to determine the exact cause.

**Action:** Take action based on the underlying exception details.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WCS-44171: Error occurred while determining security attributes for service {0}**

---

**Cause:** An error occurred while querying the policy store to determine the principals that were granted view access for the given service. Review the underlying exception in the logs to determine the exact cause.

**Action:** Take action based on the underlying exception details.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WCS-44172: Error occurred while determining security attributes for service {0} in scope {1}**

**Cause:** An error occurred while querying the policy store to determine the principals that were granted view access for the given service and scope. Review the underlying exception in the logs to determine the exact cause.

**Action:** Take action based on the underlying exception details.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WCS-44173: Error occurred while determining security attributes for artifact {0} belonging to service {1}**

**Cause:** An error occurred while querying the policy store to determine the principals that were granted view access for the given service and artifact. Review the underlying exception in the logs to determine the exact cause.

**Action:** Take action based on the underlying exception details.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WCS-44174: Error encountered while getting the HMAC initial key from the credential store**

**Cause:** There is a problem while accessing the the credential store. Review the underlying exception in the logs to determine the exact cause.

**Action:** Ensure the credential store is setup properly. Take action based on the underlying exception details.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WCS-44175: Error occurred while obtaining mapped service {0} roles for WebCenter role {1}**

**Cause:** Review the underlying exception in the logs to determine the exact cause.

**Action:** Take action based on the underlying exception details. If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR



---

**Impact:** Security

**WCS-44176: Error occurred while obtaining mapped application roles for service {0} and service role with ID {1} in scope {2}**

**Cause:** Review the underlying exception in the logs to determine the exact cause.

**Action:** Take action based on the underlying exception details. If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Security

**WCS-44177: Error occurred while adding role mapping entry for service {0} and service role {1} to webcenter role {2}**

**Cause:** Review the underlying exception in the logs to determine the exact cause.

**Action:** Take action based on the underlying exception details. If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Security

**WCS-44178: Error occurred while removing role mapping entry for service {0} and service role {1} from WebCenter role {2}**

**Cause:** Review the underlying exception in the logs to determine the exact cause.

**Action:** Take action based on the underlying exception details. If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Security

**WCS-44179: Error occurred while removing role mapping entries for service {0} in scope {1}**

**Cause:** Review the underlying exception in the logs to determine the exact cause.

**Action:** Take action based on the underlying exception details. If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Security

**WCS-44180: Error occurred while removing role mapping entries for scope {0}**

**Cause:** Review the underlying exception in the logs to determine the exact cause.

**Action:** Take action based on the underlying exception details. If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Security

**WCS-44181: Error occurred while fetching role mapping metadata for scope {0}**

**Cause:** Review the underlying exception in the logs to determine the exact cause.

**Action:** Take action based on the underlying exception details. If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Security

**WCS-44182: Error occurred while adding role mapping metadata to scope {0}**

**Cause:** Review the underlying exception in the logs to determine the exact cause.

**Action:** Take action based on the underlying exception details. If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Security

**WCS-44183: Cannot copy role mapping metadata for scope {0}**

**Cause:** Role mapping metadata already existed for the given scope.

**Action:** Remove the role mapping metadata for the scope and then perform this operation again. Alternatively, you can pass a different scope for which the role mapping metadata does not already exist.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Security

**WCS-44184: Error occurred while fetching role mapping metadata for service {0} in scope {1}**

**Cause:** Review the underlying exception in the logs to determine the exact cause.

**Action:** Take action based on the underlying exception details. If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Security

**WCS-44185: Error occurred while adding role mapping metadata for service {0} in scope {1}**

**Cause:** Review the underlying exception in the logs to determine the exact cause.

**Action:** Take action based on the underlying exception details. If the exception details do not provide sufficient information to resolve the issue, then contact Oracle Support Services.

---

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Security

**WCS-44186: Unable to obtain service {0} role mapping metadata for scope {1}**

**Cause:** The query to obtain role mapping metadata for the scope returned a path for which the metadata did not exist.

**Action:** Ensure the service role mapping metadata exists for the scope.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WCS-44187: The role mapping metadata for service {0} in scope {1} is being modified by another user. Try the operation again after some time.**

**Cause:** Another user acquired the write lock on the service role mapping metadata.

**Action:** Try the operation after some time.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WCS-44188: Cannot copy the role mapping metadata for service {0} in scope {1}**

**Cause:** The service role mapping metadata for the scope already existed.

**Action:** Remove the service role mapping for the scope and then perform the operation again. Alternatively, you can pass a different service and scope for which the role mapping metadata does not already exist.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Security

**WCS-44189: Cannot find the WebCenter application role {0}**

**Cause:** The WebCenter application role passed to Role Manager did not exist.

**Action:** Ensure that a valid application role is passed to Role Manager.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WCS-44190: Error copying role mapping metadata from role {0} to role {1} in scope {2}**

**Cause:** Role mapping metadata could not be copied. Review the underlying exception in the logs to determine the exact cause.

**Action:** Take action based on the underlying exception details. To perform role mapping, use the Roles tab in the group space settings.

**Level:** 1

**Type:** ERROR

---

**Impact:** Security

**WCS-44191: Error deleting role mapping metadata from role {0} in scope {1}**

**Cause:** The role mapping metadata could not be deleted. Review the underlying exception in the logs to determine the exact cause.

**Action:** Take action based on the underlying exception details.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WCS-44192: Error occurred while determining enterprise role mapping support, assuming default behaviour, groups will not be shredded.**

**Cause:** Review the underlying exception in the logs to determine the exact cause.

**Action:** If a service configured does not support enterprise role mapping, then take action based on the underlying exception details.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WCS-46001: unexpected error has occurred**

**Cause:** Review the root cause of the exception for more details.

**Action:** If the root cause does not provide sufficient information to resolve the issue, contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**WCS-46002: cannot initialize the resource catalog**

**Cause:** There was an error initializing the catalog using the catalog specified in adf-config.xml or there was a problem with the underlying resource catalog service.

**Action:** Verify that the catalog name specified in adf-config.xml is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-46004: cannot create item for resource [{0}], path [{1}], catalog [{2}]**

**Cause:** There was an internal error when creating an item for the resource indicated above.

**Action:** Verify that the Resource Catalog and resource adapters are working correctly.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-46005: cannot create a Folder object for resource [{0}], catalog [{1}]**

---

**Cause:** There was an internal error when creating the folder object using the path specified.

**Action:** Verify that the Resource Catalog and resource adapters are working correctly.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-46006: cannot retrieve items in [{0}] from catalog [{1}]**

**Cause:** There was an error retrieving any resources from the catalog.

**Action:** Verify that the catalog is correctly configured in adf-config.xml.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-46007: Search predicate [{0}] is not valid for search path [{1}] in catalog [{2}].**

**Cause:** The search condition specified was invalid or incorrect.

**Action:** Correct the code that creates the search condition for the resource catalog viewer.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-46008: Specified folder [{0}], path [{1}] to search does not exist in catalog [{2}].**

**Cause:** The selected folder does not exist anymore.

**Action:** Perform the search by selecting a different folder.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-46009: cannot execute search for folder [{0}]**

**Cause:** An internal error occurred while executing the requested search.

**Action:** Verify that the Resource Catalog and resource adapters are working correctly.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-46010: cannot retrieve folder path for item [{0}]**

**Cause:** The folder path specified was not found.

**Action:** The folder path requested is either incorrect or does not exist anymore.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

---

**WCS-46011: cannot find Item [{0}] in catalog [{1}]**

**Cause:** The requested item could not be found.

**Action:** The item requested is either incorrect or does not exist anymore.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-46012: cannot find Folder [{0}] in catalog [{1}]**

**Cause:** The requested folder could not be found.

**Action:** The folder requested is either incorrect or does not exist anymore.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-46013: cannot retrieve icon**

**Cause:** Icon associated with the requested resource not found.

**Action:** Verify that the underlying resource provider adapter supports the iconURI attribute.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-46014: cannot retrieve attributes for item [{0}]**

**Cause:** Could not retrieve one or more attributes.

**Action:** Verify that the underlying resource provider supports the requested attributes.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-46015: cannot retrieve transferable for item [{0}]**

**Cause:** Could not retrieve transferable for resource.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

**WCS-46016: cannot retrieve repository reference for item [{0}]**

**Cause:** Could not retrieve a repository reference.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Logging

---

**WCS-46017: cannot retrieve schema attributes for folder [{0}]**

**Cause:** Error occurred while fetching information about the schema.

**Action:** Verify that the Resource Catalog and resource adapters are working correctly.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-46018: cannot retrieve any resources for folder [{0}]**

**Cause:** Error occurred while fetching resource catalog resources.

**Action:** Verify that the Resource Catalog and resource adapters are working correctly.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-46019: cannot retrieve any folders for folder [{0}]**

**Cause:** Error occurred while fetching resource catalog folders.

**Action:** Verify that the Resource Catalog and resource adapters are working correctly.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-46020: cannot retrieve any items for folder [{0}]**

**Cause:** Error occurred while fetching resource catalog items.

**Action:** Verify that the Resource Catalog and resource adapters are working correctly.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-46021: cannot retrieve any attributes for item [{0}]**

**Cause:** Error occurred while fetching resource catalog resource attributes.

**Action:** Verify that the Resource Catalog and resource adapters are working correctly.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-46022: cannot execute a search in folder [{0}], search criteria [{1}], include subfolders [{2}]**

**Cause:** Search could not be executed due to unknown reasons.

**Action:** Verify that the Resource Catalog and resource adapters are working correctly.

---

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-46023: cannot retrieve the complete path for folder [{0}]**

**Cause:** Error occurred while fetching the full path of the resource.

**Action:** The resource may not exist anymore. Refresh the viewer to get the latest content.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-46024: cannot retrieve the current folder**

**Cause:** There was an error while retrieving information about the current folder.

**Action:** The folder may not exist anymore. Refresh the viewer to get the latest content.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-46025: cannot initialize the catalog using the parameters specified in adf-config.xml**

**Cause:** The catalog name specified in adf-config.xml could not be used or there was an error retrieving the catalog name from the catalog selector class specified in adf-config.xml.

**Action:** Verify that the catalog name specified in adf-config.xml or the one returned by the catalog selector class exists.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-46027: cannot print attributes for item [{0}]**

**Cause:** Error printing information about the item attributes in the viewer.

**Action:** Check the error stack for more information.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-46028: cannot load ResourceCatalogConfig implementation using class [{0}]**

**Cause:** Resource catalog configuration implementation class defined in adf-config.xml is invalid.

**Action:** Check adf-config.xml to verify the implementation class is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Logging



---

**WCS-46029: cannot instantiate the catalog config class [{0}]**

**Cause:** An error occurred while instantiating a class defined in the <rcv-adf-config> section in adf-config.xml.

**Action:** Verify that the class name is correct and it implements the required interface

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-46030: cannot obtain the catalog name. ResourceCatalogSelector=[{0}]  
DefaultCatalog=[{1}].**

**Cause:** The resource catalog viewer was unable to determine the catalog to use for the current context and no default was specified.

**Action:** Verify the ResourceCatalogSelector implementation and specify a default catalog in adf-config.xml.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-46032: cannot retrieve item for item with ID [{0}]**

**Cause:** An error occurred while fetching the item using the item id.

**Action:** Review the resource catalog service logs for additional information.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-46033: cannot retrieve root folder**

**Cause:** An error occurred while fetching the root folder.

**Action:** Check the Resource Catalog logs for additional information.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-46035: cannot initialize the catalog context with catalog [{0}]**

**Cause:** The catalog name specified in adf-config.xml could not be used or there was an error retrieving the catalog name from the catalog selector class specified in adf-config.xml.

**Action:** Verify that the catalog name specified in adf-config.xml or the one returned by the catalog selector class exists.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-46037: cannot retrieve the catalog instance**

---

**Cause:** The catalog name specified in adf-config.xml could not be used or there was an error retrieving the catalog name from the catalog selector class specified in adf-config.xml.

**Action:** Verify that the catalog name specified in adf-config.xml or the one returned by the catalog selector class exists.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-46039: cannot parse the rcv config in adf-config.xml**

**Cause:** The rcv config xml element specified in adf-config.xml could not be parsed.

**Action:** Verify that the rcv config element specified in adf-config.xml exists and it is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WCS-47201: An unexpected error occurred in the activity stream sub-system.**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-47202: publish activity failed because of invalid arguments passed in to the method: activity ({0}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47203: retrieve activities failed because of invalid arguments passed in to the method: privateAndUpActorIds ({0}), sharedAndUpActorIds ({1}), publicActorIds ({2}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47205: Can not get connections. Connections Exception is thrown.**

**Cause:** Connections exception thrown.

**Action:** Check the exception's detail to see the reason why the exception is thrown.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47206: Service Framework Exception is thrown.**

**Cause:** Service Framework exception thrown.

**Action:** Check the exception's detail to see the reason why the exception is thrown.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47207: Settings Exception is thrown.**

**Cause:** Settings exception thrown.

**Action:** Check the exception's detail to see the reason why the exception is thrown.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47208: Retrieve activities failed because of invalid arguments passed in to the method: applicationId ({0}), servivceId ({1}), activityType ({2}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47209: Retrieve activities failed because of invalid arguments passed in to the method: applicationId ({0}), servivceId ({1}), activityType ({2}), sinceDate ({3}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47210: Database Exception occurred in Activity Stream Toplink module.**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47211: Query Exception occurred in Activity Stream Toplink module.**

**Cause:** An unexpected error occurred.

---

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47212: Create Actor failed because of invalid argument passed to the method: guid ({0}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47213: Create Object failed because of invalid argument passed to the method: guid ({0}), type ({1}), displayName ({2}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47214: Create Activity Element failed because of invalid argument passed to the method: applicationID ({0}), scope ({1}), serviceID ({2}), activityType ({3}), actors ({4}), permission ({5}), activityTime ({6}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47215: Create Activity Type failed because of invalid argument passed to the method: id ({0}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47216: Create Object Type failed because of invalid argument passed to the method: id ({0}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-47217: Create Activity element failed because of invalid argument passed to the method: applicationID ({0}), activityType ({1}), actors ({2}), permission ({3}), activityTime ({4}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47218: Publish activity {0} failed due to {1}.**

**Cause:** Unexpected error during publishing activity.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47219: Error occur in {0} due to {1}.**

**Cause:** Exception occurs.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47220: Unexpected error resolving property "{0}":"{1}" for analytics event of type {2}**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47221: Unable to publish analytics event (of type {0})**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47222: Operation is not supported.**

**Cause:** Operation not supported.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-47223: Unable to retrieve profile information for user {0}**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47225: Check for valid repository failed**

**Cause:** Either database is down or wc repository is not installed.

**Action:** Check the exception's detail to see the reason why the exception is thrown.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47229: Taskflow instance not specified**

**Cause:** The supplied taskflow instance ID was null or blank.

**Action:** Specify a valid taskflow instance ID that is not null or blank.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47230: Activity exception encountered during bulk publish.**

**Cause:** One or more activities to be published throws exception.

**Action:** Check the individual activity exception.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47231: Create Cust Attr failed because of invalid argument passed to the method: name ({0}), value ({1}), url ({2}).**

**Cause:** One of the input arguments was invalid.

**Action:** Make sure that arguments passed in are all valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47695: Unexpected error saving settings**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-47696: Fatal error initializing the settings management sub-system**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-47697: Unexpected error retrieving settings**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47698: Unable to locate the settings document**

**Cause:** Either the document path was incorrect or the document had got deleted.

**Action:** Ensure that the document path is correct and that the document exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47699: Unable to determine current user**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47700: An unexpected error occurred in the People Connections sub-system.**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-47801: An unexpected error occurred in the Connections sub-system.**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-47802: User not specified**

---

**Cause:** The supplied username was null or blank.

**Action:** Specify a valid username that is not null or blank.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47803: Unexpected error retrieving connections for user "{0}"**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47804: Unexpected error retrieving invitations for current user**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47805: User "{0}" not found**

**Cause:** The system could not find any user with the specified username.

**Action:** Specify a valid username.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47806: Unexpected error sending invitation to user "{0}"**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47807: No invitation found with ID "{0}"**

**Cause:** The system could not find any invitation with the specified ID.

**Action:** Ensure that the specified invitation ID is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47808: Invitation ID not specified**

**Cause:** The supplied invitation ID was null or blank.

**Action:** Specify a valid invitation ID that is not null or blank.



---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47809: Unexpected error accepting invitation with ID "{0}"**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47810: Unexpected error declining invitation with ID "{0}"**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47811: Unexpected error ignoring invitation with ID "{0}"**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47812: Unexpected error removing connection with user "{0}"**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47813: Unexpected error retrieving profile of user "{0}"**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47814: Unexpected error retrieving the connection lists owned by user "{0}"**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-47815: Connection list not specified**

**Cause:** The supplied connection list name was null or blank.

**Action:** Specify a valid connection list name that is not null or blank.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47816: Connection list named "{0}" not found for user "{1}"**

**Cause:** The system could not find any connection list with the specified name owned by the specified user.

**Action:** Ensure that the username is correct and that the connection list name refers to a connection list owned by that user.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47817: Unexpected error getting Connection list "{0}" for user "{1}"**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47818: User does not have the privilege required to perform specified operation**

**Cause:** Either the system policy or the target user's access control settings restrict the current user from performing this operation

**Action:** Contact the Administrator to grant the required permission, or contact the target user to allow access

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47819: Unexpected error creating a Connection list with name "{0}"**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47820: Unexpected error adding users to Connection list with name "{0}"**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47821: Unexpected error deleting Connection list with name "{0}"**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47822: Unexpected error retrieving members of Connection list with name "{0}"**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47823: Unexpected error retrieving invitations sent by current user**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47824: Unexpected error removing user "{0}" from one or more Connection lists**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47825: Unexpected error setting Connection list membership of user "{0}"**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47826: Unexpected error retrieving the Connection lists to which user "{0}" belongs**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47827: Unexpected error creating a connection between users "{0}" and "{1}"**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47828: Unexpected error preparing the user invitation screen**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47829: Cannot invite oneself as a connection**

**Cause:** You have specified yourself as the invitee.

**Action:** Specify a username other than that of yourself.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47830: Cannot invite a user who has been invited already ({0})**

**Cause:** The user you have specified has already been invited.

**Action:** Wait for the invited user to act on your invitation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47831: Cannot invite a user who has already invited you ({0})**

**Cause:** The user you have specified has already invited you.

**Action:** Accept the invitation you have received from the user.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47832: Cannot invite a user you are already connected with ({0})**

**Cause:** You have specified one of your existing connections as the invitee.

**Action:** Specify a username other than that of your existing connections.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-47833: Unexpected error searching for users**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47834: Cannot create a connection between users "{0}" and "{1}" who already connected**

**Cause:** The specified users are already connected with each other.

**Action:** Specify users who are not yet connected.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47835: Unexpected error reading configuration**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47836: Unexpected error getting connections with preferences (userGuid = {0}, applicationId = {1}, scope = {2}, serviceId = {3}, settingKey = {4}, configurableSettingKey = {5})**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47837: Unexpected error getting connections lists with preferences (listNames = {0}, userGuid = {1}, applicationId = {2}, scope = {3}, serviceId = {4}, settingKey = {5}, configurableSettingKey = {6})**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-47838: Cannot create a Connection list with the same name as existing one ({0})**

**Cause:** You already have a connection list with the specified name.

**Action:** Specify a name other than that of your existing connection lists.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49001: Injectable Service provider did not set list service**

**Cause:** Injectable Service provider could not find the list service.

**Action:** Make sure List Service injectable provider is available in webapp.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49002: List id is null**

**Cause:** List ID was not specified in request.

**Action:** Make sure List ID is specified in request.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49003: Column id is null**

**Cause:** Column ID was not specified in request.

**Action:** Make sure Column ID is specified in request.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49004: Row id is null**

**Cause:** Row ID was not specified in request.

**Action:** Make sure Row ID is specified in request.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49005: No "column" in the request body**

**Cause:** Column data was not found in the request body.

**Action:** Make sure Column data is specified in the request body.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49006: No "list" in the request body**

**Cause:** List data was not found in the request body.

**Action:** Make sure List data is specified in the request body.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-49007: No "row" in the request body**

**Cause:** Row data was not found in the request body.

**Action:** Make sure Row data is specified in the request body.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49008: List could not be found for list id [{0}]**

**Cause:** List ID was not found.

**Action:** Make sure List ID exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49009: Column could not be found for column id [{0}]**

**Cause:** Column ID was not found.

**Action:** Make sure Column ID exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49010: Row could not be found for row id [{0}]**

**Cause:** Row ID was not found.

**Action:** Make sure Row ID exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49011: Unable to create list**

**Cause:** List was not created.

**Action:** See logs for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49012: "id" should not be supplied with a POST -- use PUT if you want to update**

**Cause:** "id" should not be supplied with a POST.

**Action:** Use PUT if you want to update.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WCS-49013: Search parameter must follow**

**[column:[operator:]]value;[column:[operator:]value] syntax**

**Cause:** Search parameter syntax not understood.

**Action:** Syntax must follow: [column:[operator:]]value;[column:[operator:]value]

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49014: Comparator [{0}] is invalid**

**Cause:** Invalid search comparator.

**Action:** Use valid search comparator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49015: MetaColumn [{0}] is a required field, and cannot be set to null**

**Cause:** Missing required field.

**Action:** Make sure required field is present.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49016: Invalid "row" data in the request body [{0}]**

**Cause:** Invalid row data was found in the request body.

**Action:** Make sure valid row data is specified in the request body.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49017: Spacename not found [{0}]**

**Cause:** Spacename not found.

**Action:** Please specify a valid spacename.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49018: Spacename not found for GUID [{0}]**

**Cause:** Spacename GUID not found.

**Action:** Please specify a valid spacename GUID.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49101: Injectable Service provider did not set forum service**



---

**Cause:** Injectable Service provider could not find the forum service.  
**Action:** Make sure Forum Service injectable provider is available in webapp.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49102: Can't establish Forum Session**

**Cause:** Injectable Service provider could not establish a Forum Session.

**Action:** Make sure Jive Forum is configured and running and/or you have a valid user session established. Re-authenticating may help.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49103: Forum id not found [{0}]**

**Cause:** Forum not found.

**Action:** Please specify a valid forum.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49104: Spacename not found [{0}]**

**Cause:** Spacename not found.

**Action:** Please specify a valid spacename.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49105: All resources require a name.**

**Cause:** Resource name required.

**Action:** Please specify a resource name in the request body.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49106: Topic id not found [{0}]**

**Cause:** Topic not found.

**Action:** Please specify a valid topic.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49201: Injectable Service provider did not set Spaces service**

**Cause:** Injectable Service provider could not find Space the service.

---

**Action:** Make sure Space Service injectable provider is available in webapp.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49202: Space id is null**

**Cause:** Space ID was not specified in request.

**Action:** Make sure Space ID is specified in request.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49203: No "document" in the request body**

**Cause:** Space document data was not found in the request body.

**Action:** Make sure Space document is specified in the request body.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49204: Spacename not found [{0}]**

**Cause:** Spacename not found.

**Action:** Please specify a valid spacename.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49205: Members not found for groupSPACE [{0}]**

**Cause:** No Members found.

**Action:** Please specify a groupSPACE with members.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49206: Member [{0}] not found in groupSPACE [{1}]**

**Cause:** Member not found.

**Action:** Please specify a different member or groupSPACE name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49207: Attributes not found in groupSPACE [{0}]**

**Cause:** Attributes not found.

**Action:** Please specify a different groupSPACE name.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49208: Attribute name [{0}] not found in group space [{1}]**

**Cause:** Attribute name not found.

**Action:** Please specify a different Attribute name or group space name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49209: Space params [{0}] and [{1}] result in exception**

**Cause:** General exception.

**Action:** Please specify a different set of parameters.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49210: Retrieving Space resulted in security exception**

**Cause:** Insufficient authorization.

**Action:** Contact space administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49211: Retrieving Space failed due to service unavailability**

**Cause:** Service unaccessible.

**Action:** Contact space administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49212: Failed to retrieve document repository info for group space.**

**Cause:** Unknown document repository error.

**Action:** Contact space administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49251: REST API Injectable Service provider did not set message board service.**

**Cause:** REST API Injectable Service provider did not set message board service.

**Action:** Contact Oracle Support Services.

**Level:** 1

---

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-49252: No "message" in the request body**

**Cause:** Message data was not found in the request body.

**Action:** Make sure Message data is specified in the request body.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49253: Message body not specified**

**Cause:** No 'message' in the body when trying to create a new message.

**Action:** Specify a valid message body that is not null or blank.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49254: "id" should not be supplied with a POST -- use PUT if you want to update**

**Cause:** "id" should not be supplied with a POST.

**Action:** Use PUT if you want to update.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49255: Error accessing profile for user with GUID {0}. Ignoring.**

**Cause:** Error retrieving user profile.

**Action:** Verify that the user GUID is correct.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49259: Error retrieving messages {0} to {1} from user or group space message board {2}.**

**Cause:** Error retrieving message from user's message board.

**Action:** Check startIndex and itemsPerPage.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49262: Invalid message board type. Got '{0}', expected 'person' or 'space'.**

**Cause:** Invalid message board type in URI.

**Action:** Verify that the message board type is either 'person' or 'space'.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WCS-49301: REST API Injectable Service provider did not set profile service.**

**Cause:** REST API Injectable Service provider did not set profile service.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-49302: Cannot delete a member from a list that the current user does not own.**

**Cause:** Cannot delete a member from a list that the current user does not own.

**Action:** Make sure REST URL specifies the correct list and is accessing list for the current user.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49303: Retrieving list names is only supported for current user with @self id. Found GUID {0} and selector {1}.**

**Cause:** Retrieving list names is only supported for current user with @self id.

**Action:** Make sure REST URL specifies the current user GUID (or @me) and then the @self selector.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49304: Creating lists is only supported for the current user. Found GUID {0}.**

**Cause:** Creating lists is only supported for current user.

**Action:** Make sure REST URL specifies the current user GUID (or @me).

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49305: No "list" in the request body**

**Cause:** List data was not found in the request body.

**Action:** Make sure List data is specified in the request body.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49306: List name not specified**

**Cause:** No "name" in the body when trying to create a new list.

**Action:** Specify a valid list name that is not null or blank.

**Level:** 1

---

Type: WARNING

Impact: Other

**WCS-49307: Creating connections is only supported for the current user. Found GUID {0}.**

**Cause:** Creating connections is only supported for current user.

**Action:** Make sure REST URL specifies the current user GUID (or @me).

Level: 1

Type: WARNING

Impact: Other

**WCS-49308: No "member" in the request body**

**Cause:** Member data was not found in the request body.

**Action:** Make sure member data is specified in the request body.

Level: 1

Type: WARNING

Impact: Other

**WCS-49309: Connection GUID not specified**

**Cause:** No "guid" in the body when trying to create a new connection.

**Action:** Specify a valid user GUID that is not null or blank.

Level: 1

Type: WARNING

Impact: Other

**WCS-49310: Only connection lists can be deleted, and only by the current user. Found GUID {0} and list ID {1}.**

**Cause:** Only connection lists can be deleted, not the current user or the intrinsic connections list. They can only be deleted by the current user.

**Action:** Make sure REST URL specifies the connection list ID, not @self or @connections, and is accessing the current user.

Level: 1

Type: WARNING

Impact: Other

**WCS-49311: Accessing status is only supported for @self id. Found selector {0}.**

**Cause:** Accessing status is only supported for @self id.

**Action:** Make sure REST URL specifies the @self selector.

Level: 1

Type: WARNING

Impact: Other

**WCS-49312: Updating status is only supported for the current user. Found GUID {0}.**

**Cause:** Accessing status is only supported for the current user.

**Action:** Make sure REST URL is accessing the current user.

---

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49317: Error accessing connection list {0}.**

**Cause:** Error accessing connection list.

**Action:** Verify that the list ID is correct.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49319: Error adding/deleting user {0} for list {1} of current user.**

**Cause:** Error adding/deleting user in connection list of current user.

**Action:** Verify that the list ID is correct and is not @CONNECTIONS (use invitations instead) and the user GUID is correct, and that the user is not already a member of the list when adding user.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49321: Invalid user search query {0}. Unable to process search. Verify that the search query is of the form [loginid>equals:X] or [guid>equals:Y].**

**Cause:** Invalid search query was passed into People REST API.

**Action:** Verify that the search query is of the form [loginid>equals:X] or [guid>equals:Y].

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49322: Error accessing connection list {0} for user {1}.**

**Cause:** Error accessing connection list.

**Action:** Verify that the list ID and GUID are correct.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49323: Invalid invitation search query {0}. Unable to process search. Verify that the search query is either [invitor>equals:@me] or [invitee>equals:@me].**

**Cause:** Invalid search query was passed into People Invitations REST API.

**Action:** Verify that the search query is either [invitor>equals:@me] or [invitee>equals:@me].

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49324: No "invitation" in the request body**

---

**Cause:** Invitation data was not found in the request body when trying to create a new invitation.

**Action:** Make sure Invitation data is specified in the request body.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49325: Invitation invitee GUID not specified**

**Cause:** No "invitee" item or "guid" item in "invitee" in the body when trying to create a new invitation.

**Action:** Specify a valid invitee user GUID that is not null or blank.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49327: Error inviting user {0} to be a connection of the current user**

**Cause:** Error inviting user {0} to be a connection of the current user.

**Action:** Verify the invitee user GUID is correct and is not null or blank.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49328: The invitation ID in the request body ({0}) did not match the ID in the query string ({1})**

**Cause:** The invitation ID in the request body did not match the ID in the query string when trying to update invitation status.

**Action:** Make sure the invitation ID specified in the request body matches the invitation ID in the query string.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49329: Error deleting invitation {0}**

**Cause:** Error deleting invitation {0}.

**Action:** Verify the invitation ID is correct, and that the current user has permissions to delete the invitation (i.e. created or received it).

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49330: Unable to update invitation {0} with status {1}. Verify that the invitation id is valid, the current user has permission to update the invitation, and that the status is either "accepted" or "ignored".**

**Cause:** Unable to update invitation status.

**Action:** Verify that the invitation id is valid, the current user has permission to update the invitation, and that the status is either "accepted" or "ignored".



---

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49331: Error inviting user {0} to be a connection of current user.**

**Cause:** Error inviting user to be a connection of current user.

**Action:** Verify that the user GUID is correct, and that the user has not already been invited by the current user.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49351: REST API Injectable Service provider did not set activity service.**

**Cause:** REST API Injectable Service provider did not set activity service.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-49352: No "activity" in the request body**

**Cause:** Activity data was not found in the request body.

**Action:** Make sure Activity data is specified in the request body.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49353: "id" should not be supplied with a POST -- use PUT if you want to update**

**Cause:** "id" should not be supplied with a POST.

**Action:** Use PUT if you want to update.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49354: Creating activities is only supported for an individual user. Found list {0}.**

**Cause:** Creating activities is only supported for individual users.

**Action:** Make sure REST URL specifies @self for list ID.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49361: Unable to parse key {0} for activity parameter. Should be of form 'actor[n]}' or 'object[n]}.**

**Cause:** Unable to parse key for activity parameter.

---

**Action:** Make sure key starts with actor or object and the index is numeric.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49362: Unable to find Group Space scope for {0}.**

**Cause:** Unable to find Group Space scope from specified value.

**Action:** Make sure Group Space value is correct.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49401: REST API Injectable Service provider did not set feedback service.**

**Cause:** REST API Injectable Service provider did not set feedback service.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WCS-49402: No "message" in the request body**

**Cause:** Message data was not found in the request body.

**Action:** Make sure Message data is specified in the request body.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49403: Message body not specified**

**Cause:** No 'message' in the body when trying to create a new feedback item.

**Action:** Specify a valid message body that is not null or blank.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49404: "id" should not be supplied with a POST -- use PUT if you want to update**

**Cause:** "id" should not be supplied with a POST.

**Action:** Use PUT if you want to update.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49405: Error retrieving display name from profile for user with GUID {0}.**

**Ignoring.**

**Cause:** Error retrieving user profile.

---

**Action:** Verify that the user GUID is correct.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-49409: Error retrieving received feedback items from {0} to {1} for user {2}.**

**Cause:** Error retrieving received feedback for user.

**Action:** Check startIndex and itemsPerPage.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49410: Error retrieving given feedback items from user {0} for items {1} to {2}.**

**Cause:** Error retrieving feedback for user.

**Action:** Check startIndex and itemsPerPage.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-49414: Error trying to get feedback for user. Either unknown GUID {0} or unknown selector {1}.**

**Cause:** Either an unknown GUID was entered, expected @me or GUID or unknown selector was entered, expected @self, @all, or valid GUID. Selector can only be a valid GUID if the {guid} value entered is @me or the GUID of the current logged in user.

**Action:** Double check the GUID or selector entered is valid.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-50001: An unexpected error occurred in the notification sub-system.**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-50002: Error in Notification Button tag usage - component {0} has attribute {1} whose value is {2}.**

**Cause:** The attribute mentioned in the error cannot be null, but no value was found for this attribute.

**Action:** Correct your tag usage.

**Level:** 1

**Type:** WARNING

---

**Impact:** Other

**WCS-50003: Component {0} does not support client listeners.**

**Cause:** Tried to add a client listener to a component that does not support client listeners.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-50004: Mandatory parameter {0} not provided in parameters**

**Cause:** The caller did not provide the required parameter to generate notification

**Action:** Contact your system administrator

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-50005: Notification template {0} not found**

**Cause:** The service failed to read the notification template. The template is not available

**Action:** Contact your system administrator

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-50006: Could not create notification contents based on default template {0}**

**Cause:** The service failed to process the default notification template.

**Action:** Contact your system administrator

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-50007: Invalid child element {0} found for parent {1}**

**Cause:** The template contains invalid child elements.

**Action:** Contact your system administrator

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-50008: End tag {0} not found in CDATA section corresponding to the tag at index {2}**

**Cause:** The CDATA section of the template contains a notificaiton tag without corresponding end tag.

**Action:** Contact your system administrator

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WCS-50009: Value for the token {0} not found in parameters**

**Cause:** The value for the token is not provided in the list of parameter values

**Action:** Contact your system administrator

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-50010: Message key {0} not defined in resource bundle of service {1}**

**Cause:** The message key used in the template does not exist in the service resource bundle

**Action:** Contact your system administrator

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-50011: Error occurred in parsing message {0} in resource bundle of service {1}**

**Cause:** The message has invalid syntax

**Action:** Contact your system administrator

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WCS-50012: An unexpected error occurred in the notification sub-system.**

**Cause:** An unexpected error occurred.

**Action:** Contact your system administrator.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WCS-51001: Document {0} cannot be checked out as it is locked by user {1}.**

**Cause:** Another user has checked out the document.

**Action:** Contact the other user, or wait until they have checked in the document.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**WCS-51002: Unspecified Error**

**Cause:** See underlying error.final

**Action:** See underlying error

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WCS-51003: Document {0} does not exist.**

**Cause:** File may have been deleted, or the current user no longer has access to it.

**Action:** Check if file exists in the group space.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**WCS-51004: Document {0} cannot be checked in as it is not checked out.**

**Cause:** File is not checked out.

**Action:** Check out the file before attempting to check it in.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**WCS-51005: User {0} does not have the rights to access document {1}.**

**Cause:** User does not have rights to access documents.

**Action:** Check user rights to document.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**WCS-51006: Folder {0} already exists in this parent folder.**

**Cause:** Folder already exists.

**Action:** type the name of a folder that does not already exist.

**Level:** 1

**Type:** ERROR

**Impact:** Files

---

## WOR-70021 to WOR-70229

**WOR-70021: The specified Reports Server object was not found.**

**Cause:** The Reports Server that was specified is not registered with OracleAS Portal.

**Action:** Register the Reports Server, or specify the correct Reports Server name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WOR-70024: The specified Reports Calendar was not found**

**Cause:** The specified Reports Calendar does not exist or is not registered with OracleAS Portal.

**Action:** Register the Reports Calendar, or specify the correct Reports Calendar name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WOR-70071: cannot complete rwcalsum.show\_control**

**Cause:** There was an internal error while rendering the calendar.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WOR-70082: not a valid number**

**Cause:** A value was entered that contains non-numeric characters.

**Action:** Enter only numeric characters.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WOR-70135: failed to save parameters**

**Cause:** The operation to save parameters failed.

**Action:** This is an internal error. Contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WOR-70136: failed to initialize Builder attributes - %0**

**Cause:** Initialization of the specified Reports Builder attributes failed.

**Action:** Refer to the relevant Reports Builder error message, and take the appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WOR-70137: Failed to initialize servers - %0**

**Cause:** Initialization of the specified Reports Server failed.

**Action:** Check that the Reports Server is properly registered.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WOR-70166: Unable to delete object <B>%0 (version %1)</B> from Oracle Portal.**

**Cause:** The application was unable to delete the specified object.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WOR-70174: Invalid error ID:**

**Cause:** An invalid error ID was specified.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WOR-70175: Cannot access the server:**

**Cause:** The server is not accessible because the security check failed.

**Action:** Contact your portal administrator to get access to the server.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WOR-70176: Cannot access the printer:**

**Cause:** The printer is not accessible because the security check failed.

**Action:** Contact your portal administrator to get access to the printer.

**Level:** 1



---

**Type:** ERROR

**Impact:** Other

**WOR-70177: Cannot access the module.**

**Cause:** The module is not accessible because the security check failed.

**Action:** Contact your portal administrator to get access to the module.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WOR-70178: Cannot access the output type:**

**Cause:** The output type (destype) is not accessible because the security check failed.

**Action:** Contact your portal administrator to get access to the output type.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WOR-70179: Cannot access the output format:**

**Cause:** The output format (desformat) is not accessible because the security check failed.

**Action:** Contact the portal administrator to get access to the output format.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WOR-70180: Cannot run the report.**

**Cause:** The calendar check failed. The report cannot be run at this time.

**Action:** View the availability calendar to see when the report can be run.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WOR-70181: Cannot use the server at this moment.**

**Cause:** The calendar check failed. The report cannot be run on this server at this time.

**Action:** Check the availability calendar to see when the server can be used to run the report.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WOR-70182: Cannot use the printer at this moment.**

**Cause:** The calendar check failed. Printing on this printer is not possible at this time.

---

**Action:** Check the availability calendar to see when the report can be printed on this printer.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WOR-70183: Generic access check failed.**

**Cause:** The required privileges to perform this task were missing.

**Action:** Ask your portal administrator for the required privileges.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WOR-70184: LOV access check failed for parameter:**

**Cause:** The LOV access check failed. You currently do not have the privileges required to access this LOV.

**Action:** Ask your portal administrator for the required privileges.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WOR-70185: Low range access check failed for parameter:**

**Cause:** The value specified is less than the valid lower limit for this parameter.

**Action:** Specify a value within the valid range.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WOR-70186: High-range access check failed for parameter:**

**Cause:** The value specified is higher than the valid high limit for this parameter.

**Action:** Specify a value within the valid range.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WOR-70187: validation escape access check failed**

**Cause:** The validation trigger failed.

**Action:** Contact your portal administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WOR-70188: No report was specified.**

**Cause:** A report name was not specified.

---

**Action:** Specify a valid report name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WOR-70189: No server was specified.**

**Cause:** A server name was not specified.

**Action:** Specify a valid server name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WOR-70190: Conflicting module and report names are specified.**

**Cause:** The report name and the module name are conflicting.

**Action:** Ensure that the report name and the module name are the same.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WOR-70210: An exception occurred when sending a request to the Reports Server.**

**Cause:** An exception occurred when sending a request to the Reports Server. The report was not sent.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WOR-70212: The Oracle Reports Web gateway URL setting was not specified.  
Cannot run report.**

**Cause:** The Oracle Reports Web gateway URL was not specified.

**Action:** Edit the server component, and specify the Oracle Reports Web gateway.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WOR-70229: Your browser cannot display this Reports portlet.**

**Cause:** The browser version is not supported. The Reports portlet cannot be displayed in this version of the browser.

**Action:** Upgrade the browser version. Refer to the product documentation for supported browser versions.

**Level:** 1

**Type:** ERROR

**Impact:** Other



---

## WSM-00004 to WSM-09024

**WSM-00004: WS-Security Exception : {0}**

**Cause:** The system encountered a generic failure in security.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Security

**WSM-00005: Error in sending the request.**

**Cause:** Failure occurred while trying to send the request message, possibly due to a failure in security code.

**Action:** Retry the operation for a maximum of 3 times. If the problem persists, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Security

**WSM-00006: Error in receiving the request: {0}.**

**Cause:** Failure occurred while processing the request message, possibly due to a failure in security checks.

**Action:** Refer to the policy for the expected nature of the request message and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00007: JPS exception**

**Cause:** The error was most likely due to an invalid JPS configuration.

**Action:** Correct the JPS configuration and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00008: Web service authentication failed.**

**Cause:** Authentication failed at the server end.

---

**Action:** Resend valid credentials.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00009: The password policy does not match. Expected: {0}, Received:{1}.**

**Cause:** The expected and actual password types did not match.

**Action:** Refer to the policy to determine the allowed password type value.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00010: Message rejected as the nonce element in the WS-Security header is missing.**

**Cause:** Nonce was required according to policy requirements, but was not found.

**Action:** Resend the request with valid value of nonce.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00011: The wsu:Created element is required.**

**Cause:** The Created element was required, but was not found.

**Action:** Resend the request with valid value of the Created element with the UTC timestamp of the instance in which the request was created.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00012: The password is ignored, as it is not required by the policy.**

**Cause:** The password was sent in the <UsernameToken>, when it was not required.

**Action:** The password type prescribed by the policy is None, so password should not be sent.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WSM-00013: The nonce is ignored, as it is not required by the policy.**

**Cause:** The nonce was sent in the <UsernameToken>, when it was not required.

**Action:** Because the policy does not require the nonce, it should not be sent.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WSM-00014: The creation timestamp is ignored, as it is not required by the policy.**

---

**Cause:** The creation timestamp was sent in the <UsernameToken>, when it was not required.

**Action:** Because the policy does not require the creation timestamp inside <UsernameToken>, it should not be sent.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WSM-00015: The user name is missing.**

**Cause:** Username was expected but was not found.

**Action:** Either the username element or the username inside the username element is missing. Resend the request with a valid username.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00016: The username/password credentials or certificates {0} are missing.**

**Cause:** It is possible that username/password or certificate is missing.

**Action:** Resend valid credentials.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00017: The <bindings> element for {0}:{1} is missing.**

**Cause:** It is likely that the bindings element is missing inside policy.

**Action:** Re-create the policy with valid bindings.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00018: There is more than one security header with the same role {0}.**

**Cause:** More than one security header was found with the same role associated.

**Action:** Refer to the WS-Security 1.0 or 1.1 specifications. Do not send more than one security header having the same role.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00019: The version of SOAP used is not supported: {0}.**

**Cause:** An envelope was obtained that conforms to an unsupported version of SOAP.

**Action:** Use a supported version. SOAP 1.1 and 1.2 are supported.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**WSM-00020: Error sending the response.**

**Cause:** A failure occurred while building the response.

**Action:** Retry a maximum of three times. If the retry attempts fail, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WSM-00021: Error receiving the response.**

**Cause:** A failure occurred while processing the response, most likely due to a failure in the security check.

**Action:** Retry sending the response to the client.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00022: Error sending a fault.**

**Cause:** A failure occurred while sending the fault.

**Action:** Retry for a maximum of three times. If the retry attempts fail, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WSM-00023: Error receiving a fault.**

**Cause:** A failure occurred while processing the fault, most likely due to a failure in the security check.

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Security

**WSM-00024: The SAML token is missing from the security header.**

**Cause:** The SAML assertion that was expected inside the security header was not found.

**Action:** Insert valid SAML assertions and resend the request.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00025: SAML token verification failure.**

**Cause:** SAML token verification failed.



---

**Action:** Check the validity period of the SAML assertion using Conditions, or determine whether the assertion must be signed. Ensure that the SAML token conforms to the requirements of the SAML 1.0 specification.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00026: The SAML token cannot be added to the security header.**

**Cause:** A failure occurred while adding the SAML token to the security header.

**Action:** Check the log file for a possible cause.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WSM-00027: The configuration parameter {0} contains an invalid value [{1}].**

**Cause:** The configuration settings were invalid.

**Action:** Check the configuration and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00028: Failure in getting user credentials from client.**

**Cause:** Failure occurred while extracting user credentials from the client side.

**Action:** Check Keystore/Username and the Password/CSF configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00029: The algorithms used to encrypt the data do not match those specified in the policy. : Expected : {0}, Actual : {1}.**

**Cause:** The expected and actual data encryption algorithms did not match.

**Action:** Check the policy to determine the permitted values for the data encryption algorithm.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00030: The encryption method key wrap algorithms do not match : Expected : {0}, Actual : {1}.**

**Cause:** The expected and actual key wrap encryption algorithms did not match.

**Action:** Check the policy to determine the permitted values for the key wrap encryption algorithm. In addition, refer to WS-Security Policy 1.1 for a list of allowed values.

**Level:** 1

**Type:** ERROR

---

**Impact:** Security

**WSM-00031: The digest algorithms do not match.**

**Cause:** The actual digest algorithms for the signature did not match the expected algorithms.

**Action:** Check the policy to determine the permitted values for the signature digest algorithms.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00033: The encrypted message elements or parts do not comply with the policy. The following headers/elements (<name space: local name>) or attachments (<attachment ID: attachment type>) must be encrypted:- {0}**

**Cause:** Parts or elements to be encrypted according to policy were different from those in the SOAP message.

**Action:** Refer to the policy and WS-Security specifications to ensure that all encryption requirements mandated by the policy and the specifications are met.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00034: Error in Encryption reference mechanism compliance : Expected : {0} , Actual : {1}.**

**Cause:** The expected and actual encryption reference mechanisms did not match.

**Action:** Check the policy to determine the permitted values for the encryption reference mechanism.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00035: Error in Signature reference mechanism compliance : Expected : {0} , Actual : {1}.**

**Cause:** The expected and actual signature reference mechanisms did not match.

**Action:** Check the policy to determine the allowed value of the signature reference mechanism.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00036: The signed message elements or parts do not comply with the policy. The following headers/elements (<name space: local name>) or attachments (<attachment ID: attachment type>) must be signed:- {0}**

**Cause:** Parts or elements to be signed according to policy were different from those in the soap message.

**Action:** Refer to the policy and WS-Security specifications to make sure that all the signature requirements mandated by the policy and the specifications are met.

---

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00037: Error in signature confirmation compliance.**

**Cause:** The error could have occurred because the response signature confirmation element was not signed.

**Action:** Check that all the signature confirmations in the response are signed and referenced in the response signature.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00039: Timestamp element is not found in the message in accordance with policy.**

**Cause:** Timestamp policy compliance failed.

**Action:** Check the policy to find out whether a timestamp is required. If the policy indicates that the timestamp is not required, it should not be present; if timestamp is required, it should be present.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00042: The request must be made over SSL.**

**Cause:** The request was expected to be sent over SSL, but it was not.

**Action:** Check the SSL port and send the request over SSL.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WSM-00043: No peer certificates are present from the HTTP request.**

**Cause:** A certificate in the trust chain is missing.

**Action:** Ensure that the complete certificate chain is propagated in the request, if certificates signed by CA are used.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00044: The HTTP authorization header is missing.**

**Cause:** The authorization Header was not found.

**Action:** For basic over HTTP authentication, ensure that the request HTTP headers contain an authorization header.

**Level:** 1

**Type:** ERROR

**Impact:** Security

---

**WSM-00045: HTTP authentication/authorization failure.**

**Cause:** Failure occurred in basic authentication.

**Action:** Use the appropriate Base64 encoded combination of a valid username and password.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00046: Error in advertisement of WS-Policy.**

**Cause:** An error occurred while advertising ORAWSDL to WS-Policy.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WSM-00047: Invalid key referencing mechanism: {0}.**

**Cause:** The sign or encryption key reference mechanism used was invalid.

**Action:** Valid supported values are direct, issuerserial, SKI, or thumbprint.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00048: The signature confirmation value is invalid. Expected : {0}, Actual : {1}.**

**Cause:** Signature confirmation sent in the response was invalid.

**Action:** See the WS-Security 1.1 specification for the correct @Value of SignatureConfirmation.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00049: The expected {0} signature is missing in the request message.**

**Cause:** No signature (message, or endorsing) was found in the request to confirm.

**Action:** Resend the request with at least one <Signature>.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WSM-00050: Cannot obtain security token reference.**

**Cause:** The message was not signed or encrypted properly.

**Action:** Check the <ds:Reference> section of the message.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WSM-00051: The encrypted data or key cannot be obtained.**

**Cause:** The referenced encrypted object could not be found.

**Action:** Ensure that the reference points to valid <EncryptedKey> element.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WSM-00052: There is an invalid or nonexistent configuration for the Login Module class [{1}] in the Java Platform Security (JPS) context [{0}].**

**Cause:** An invalid or nonexistent configuration for Login Module could have been used.

**Action:** Change the configuration and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00053: The propagated subject is either null or empty.**

**Cause:** No Subject was found.

**Action:** Send a valid nonempty Subject.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00054: The password credentials cannot be obtained from the Credential Store Framework (CSF). Unable to retrieve the csfKey "{0}". The csf map "{1}" found in the credential store is being used and the following keys are found in this map <CsfKeyName: UserName>:- {2}**

**Cause:** Failure occurred while doing query for credentials from Credential Store Framework (CSF).

**Action:** Check CSF configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00055: The keystore located at {0} cannot be loaded due to {1}. Ensure that valid keystore type and password are configured.**

**Cause:** The following keystore-related configuration properties may not be valid:keystore.type, keystore.pass. Also, the keystore could be corrupt or could have been tampered with.

**Action:** Verify the configuration properties mentioned above and retry the operation. In a rare situation, replace or regenerate the keystore.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**WSM-00056: The key, {0}, is not retrieved. The location of the key store being used is "{1}" and its type is "{2}". The following aliases are found in the keystore:- {3}**

**Cause:** Error occurred while obtaining key from store.

**Action:** Make sure the key exists in the keystore. Check JPS configuration settings for correct key alias, key password and keystore password. Also, check the values of the key keystore-csf-key and its password in the oracle.wsm.security map, through EM or WLST. In a rare situation, this error can also happen if the actual keystore type is ORACLE\_WALLET and the keystore type specified in JPS configuration file is PKCS12.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00057: The certificate, {0}, is not retrieved. The location of the key store being used is "{1}" and its type is "{2}". The following aliases are found in the keystore:- {3}**

**Cause:** Failure occurred while retrieving certificate from store.

**Action:** Verify keystore location configuration property as well as make sure that the requested certificate is present.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00058: The key type {0} is not supported.**

**Cause:** The private key algorithm that was used is unsupported.

**Action:** Ensure that the private key follows the RSA algorithm.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00059: Signature method algorithms are mismatched. Expected : {0}, Actual : {1}.**

**Cause:** Expected and actual values of signature method algorithms did not match.

**Action:** Check the policy and WS-Security Policy 1.1 specification for valid values.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00060: Error validating timestamp.**

**Cause:** Timestamp is expired.

**Action:** Check the timestamp. Check the allowed clockskew and message expiration time.

**Level:** 1

**Type:** ERROR

**Impact:** Security

---

**WSM-00061: Signature digest verification failure.**

**Cause:** Digest verification failed possibly due to corrupted digest, or a message that was tampered with.

**Action:** Recompute the digest and send the message again.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00062: The path to the certificate used for the signature is invalid.**

**Cause:** The intermediate and root certificates of the signing certificate were not present in the keystore at the verifying end.

**Action:** Make sure that the entire certificate chain is available in the keystore for verification.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00063: The version of SAML is incorrect. Expected : {0}, Actual : {1}.**

**Cause:** SAML version in the SAML assertion did not match the expected version.

**Action:** Check to see that the major version and minor version of the assertion are according to policy.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00064: SAML subject confirmation mismatch. Expected : {0}, Actual : {1}.**

**Cause:** Subject confirmation method in SAML assertion did not match the policy requirements.

**Action:** Check to see that the confirmation method for all the SAML assertions is sender-vouches.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00065: Error sending request over SSL.**

**Cause:** Failure in creating SSL request possibly due to invalid configuration of Credential Store Framework (CSF).

**Action:** Check the JPS configuration for CSF.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WSM-00067: None SOAP message parts can be encrypted.**

**Cause:** The elements to be encrypted in the policy were selected to be either of soap Envelope/Body/Header.

---

**Action:** The core soap nodes cannot be encrypted according to WS-Security 1.0 specification.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00068: The security token is missing.**

**Cause:** Security token was expected but was not found.

**Action:** Security token is missing. Resend request with valid Security token.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00069: The security header is missing.**

**Cause:** Security header was expected but was not found.

**Action:** Security header is missing. It could be that client side policy has not been applied. Resend request with appropriate Security header.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00070: The nonce cannot be validated.**

**Cause:** Failure occurred while performing nonce Validation.

**Action:** This may be due to a repeated value of nonce. Resend the request with a valid nonce.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00071: Error validating the wsu:Created attribute.**

**Cause:** Failure occurred while doing Created(Timestamp) validation.

**Action:** Resend the request with a valid timestamp, and or within the expiration limits.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00072: An encryption algorithm suite policy compliance failure occurred.**

**Cause:** Failure occurred in encryption algorithms policy compliance check.

**Action:** Check the encryption algorithm requirements of the policy and resend the message with appropriate value of algorithm suite.

**Level:** 1

**Type:** ERROR

**Impact:** Security



---

**WSM-00073: The mechanism {0} used in the authentication header is not supported.**

**Cause:** The value of mechanism attribute used was not supported.

**Action:** Change the policy to point to valid value of mechanism(basic), and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00074: The authorization header {0} is not correctly encoded using the Base64 encoding.**

**Cause:** The authorization header was not encoded according to Base64 requirements.

**Action:** Encode the header with Base64(username:realm:password) format and resend the request.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00075: The realm property is not configured in the policy.**

**Cause:** The realm property was not configured in the policy.

**Action:** Configure appropriate value of realm inside the policy.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00076: The user name is missing from the encoded authorization header.**

**Cause:** The Authorization header did not contain a properly encoded username, or username was null.

**Action:** Encode the header with Base64(username:realm:password) format and resend the request.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

**WSM-00077: The password is missing from the encoded authorization header.**

**Cause:** The Authorization header did not contain password encoded properly, or password was null.

**Action:** Encode the header with Base64(username:realm:password) format and resend the request.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00078: The configuration of the credentials in the policy is incorrect.**

**Cause:** Credential configuration in the policy was incorrect.

---

**Action:** Configure policy with valid Credential Store Framework (CSF) key, or username/password properties.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00079: The <BinarySecurityToken> element is missing.**

**Cause:** <BinarySecurityToken> was not found.

**Action:** For reference mechanisms that are configured with value direct, send the certificate inside <BinarySecurityToken> element.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00080: STR Dereferencing Transform not found**

**Cause:** STR Dereferencing Transform was not found.

**Action:** For reference mechanisms that are configured with value SKI, the Transforms section should contain the STR Dereferencing Transform.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00081: The X.509 certificate is not signed.**

**Cause:** The X509 token used was not signed according to requirements of certificate authentication scenario.

**Action:** Sign the X509 token (depending upon the reference mechanism used) for certificate authentication.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00082: The roles and/or attributes of the user profile cannot be retrieved.**

**Cause:** No information could be obtained regarding the user roles or attributes.

**Action:** Try resending the request for another user.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00083: Error computing the digest for this reference.**

**Cause:** Digest computation for the <Reference> failed.

**Action:** Check log file for possible cause.

**Level:** 1

**Type:** ERROR

**Impact:** Security

---

**WSM-00084: Error computing <SignatureValue> for this signature block.**

**Cause:** Signature value computation for the signature block failed.

**Action:** Check log file for possible cause.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00085: The certificates cannot be retrieved from the keystore.**

**Cause:** Failure occurred while trying to retrieve certificate from keystore.

**Action:** Use a valid alias for the certificate and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00086: Error initializing nonce cache.**

**Cause:** Failure occurred while initializing iAS Cache.

**Action:** Check log file for possible cause.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00087: Either {0} property or the oracle.j2ee.home system property is not set.**

**Cause:** The cache configuration file for iAS cache was not found.

**Action:** Set the system property oracle.j2ee.home or javacache.config.home system property to the path of the configuration file javacache.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00088: The ObSSOCookie is missing.**

**Cause:** The OAM security token was not found.

**Action:** Resend the request by embedding the ObSSOCookie token inside a <BinarySecurityToken> element.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00089: The attachments security transform is incorrect. Expected : {0}, Actual : {1}.**

**Cause:** The attachment security transform used was incorrect.

**Action:** Refer to the recipient's policy for information about which SwA Security Transform is to be used.

**Level:** 1

**Type:** ERROR

---

**Impact:** Security

**WSM-00090: The signature for the attachment is non-compliant.**

**Cause:** The attachment signature was not compliant.

**Action:** Refer to the recipient's policy for information about which SwA Security Transform is to be used.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00091: The encryption of the attachment is non-compliant.**

**Cause:** The attachment encryption was not compliant.

**Action:** Refer to the recipient's policy for information about which SwA Security Transform is to be used.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00092: The <EncryptedKey> element is missing in the request.**

**Cause:** No <EncryptedKey> elements were found in the request.

**Action:** Refer to the WS-Security 1.0 and 1.0 specifications for the semantics.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00093: The <saml:Assertion> element is missing in the security header.**

**Cause:** No SAML assertions were found inside the security Header.

**Action:** Resend the message with at least one SAML assertion in the header.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00094: The negotiated cipher suite does not meet policy requirements.**

**Expected :** {0}, **Actual :** {1}.

**Cause:** The negotiated cipher suite did not meet policy requirements.

**Action:** Check the recipient's policy for the permitted values of the cipher suite.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00095: There is more than one assertion assigned to the same category {0} in the security policy.**

**Cause:** Two or more assertions assigned to the same category were used.

**Action:** Ensure that assertions inside a security policy belong to different categories.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00096: The order of the assertions is incorrect.**

**Cause:** Assertion order does not match the requirements of policy.

**Action:** Use the following order for client side policy : authentication -> msgprotection or authentication -> authorization and following for server side security policy msg-protection -> authentication or msg-protection -> authentication -> authorization.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00097: HTTP basic authentication header is missing.**

**Cause:** HTTP basic authentication header was missing.

**Action:** Client must provide the HTTP basic authentication header.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

**WSM-00098: User realm {0} is either null or is a mismatch with service realm {1}.**

**Cause:** User realm was either null or was a mismatch with service realm.

**Action:** Make sure user realm sent from client matches with the service realm.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Security

**WSM-00099: Username, password, or both are missing from the HTTP authentication header.**

**Cause:** Username, password, or both were missing from HTTP authentication header.

**Action:** Make sure the HTTP request header contains the username/password token.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00100: Found more than one keystore files {0} in application classpath. By default the first keystore is used. Make sure the desired keystore is being used by clearing others from the classpath.**

**Cause:** Found more than one keystore file in application classpath. By default, the first keystore is used.

**Action:** To ensure the desired keystore is being used, remove other keystores from the classpath, if possible.

**Level:** 1

---

Type: WARNING

Impact: Security

**WSM-00101: The specified keystore file {0} cannot be found; it either does not exist or its path is not included in the application classpath.**

**Cause:** Keystore file did not exist or its path was either incorrect or not included in the application classpath.

**Action:** Verify the keystore file does exist and its path is included in the application classpath.

Level: 1

Type: ERROR

Impact: Security

**WSM-00102: The specified user/subject does not belong to any role in system ID store.**

**Cause:** The subject/user did not belong to any defined role in system ID store.

**Action:** Verify and make sure that the specified user belongs to one or more roles.

Level: 1

Type: ERROR

Impact: Security

**WSM-00103: The policy is configured incorrectly without specifying roles, or denyAll or permitAll elements.**

**Cause:** The policy was incorrectly configured with no roles and no denyAll/permitAll elements.

**Action:** Correct the policy by configuring it with a denyAll element, a permitAll element, or at least one role.

Level: 1

Type: ERROR

Impact: Security

**WSM-00104: The specified JPS context {0} cannot be found in system-level JPS configuration file.**

**Cause:** The JPS context could not be found in system level JPS configuration.

**Action:** Verify system level JPS configuration file to ensure that it contains the context.

Level: 1

Type: ERROR

Impact: Security

**WSM-00105: Credential Store service instance is missing. Either the Oracle WSM JPS context being used for the keystore does not contain a reference to the Credential Store service instance, or the reference is not valid. The Credential Store service instance needs to be declared at the same level (system or application) as the keystore service instance. Therefore, if an application-level keystore is being used, a Credential Store Framework (CSF) store must also be declared at the application level.**

---

**Cause:** No Credential Store (CSF) was found at the level where keystore was used.

**Action:** Verify that the WSM JPS context is configured correctly. The error indicates that either the WSM JPS context which is being used for keystore does not contain reference to the Credential Store service instance, or the reference is not valid. The Credential Store service instance needs to be declared at the same level (system or application) as the keystore service instance. Therefore, if an application level keystore is being used, a CSF store must also be declared at the application level.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00106: Assertion assigned to a non-security category {0} cannot be added to policy assigned to a security category.**

**Cause:** Assertion belonging to non-security categories could not be added to policies belonging to security category.

**Action:** Ensure that assertions in security policy also belongs to security category.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00107: Assertion belonging to {0} category is not valid for generic policy. Only assertion of type security/logging can be added to a generic policy (policy applicable to clients and servers). Check the assertions added to the generic policy.**

**Cause:** Invalid assertions were found in generic policy.

**Action:** Only assertion of type security/logging can be added to a generic policy (policy applicable to clients and servers). Recheck the assertions added to the generic policy.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00108: If password type is set to digest, addNonce and addCreated should be true.**

**Cause:** UserNameToken Assertion had Passwordtype as digest but addNonce or addCreated was false.

**Action:** In case of passwordtype as digest, addNonce and addCreated both should be true. Recheck the assertion.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00109: Algorithm suite is not supported, only TripleDes is supported for Kerberos assertion.**

**Cause:** Kerberos Assertion had algorithm-suite other than TripleDES.

---

**Action:** Only TripleDES algorithm is supported in case of Kerberos, so set algorithm-suite as TripleDes.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00110: Basic192 and \*RSA15 algorithm-suites are not supported for SSL. Change the algorithm suite to one that is supported.**

**Cause:** Basic192 or RSA algorithm-suite was used for SSL.

**Action:** Use other supported Algorithm-suite for SSL except Basic192 and RSA algorithms.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00111: Keystore is not properly configured in JPS config.**

**Cause:** Keystore was not properly configured in JPS configuration or through config override properties.

**Action:** Check the keystore configuration, and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00112: Missing keystore service instance reference in Oracle WSM JPS context.**

**Cause:** Keystore Service instance reference was not found in WSM JPS context.

**Action:** Add the keystore service instance reference to WSM JPS context, and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00113: Unsupported configuration value for Client Credential Configuration location.**

**Cause:** An unsupported configuration value of Client Credential location configuration was provided.

**Action:** Refer to the documentation for valid values and add the proper configuration value for Client Credential Configuration Location, and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00114: No matching SSL cipher suite is found for algorithm suite value, specified in the Policy.**

**Cause:** No matching SSL cipher suite was found for algorithm suite value, specified in WS Policy.



---

**Action:** Set algorithm suite of Web Service policy to a value that has matching SSL cipher suite.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00115: JSSE System Property for SSL cipher suite is either not set or does not match algorithm suite value specified in WS Policy.**

**Cause:** JSSE System Property for SSL cipher suite was either not set or did not match algorithm suite value specified in WS Policy.

**Action:** Set JSSE System Property (https.cipherSuites) to a value that matches algorithm suite as specified in WS Policy.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00116: Error retrieving SOAP body from SOAP message.**

**Cause:** An error occurred while retrieving SOAPBody from SOAPMessage. Either the SOAPMessage was not proper or had been tampered with.

**Action:** Check whether the SOAPMessage is according to the Specifications and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00117: Error occurred while transforming the security header.**

**Cause:** TransformerException occurred while transforming the WssHeader to String. The SOAPMessage might not have been proper or it did not conform to the specifications.

**Action:** Check the SOAPMessage and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00118: OAM token can be inserted only on hosted clients where authenticated subject has been established.**

**Cause:** Insertion of an OAM token tried from a non-hosted client where Authenticated Subject is not established.

**Action:** Try to add OAM token from a hosted client as only the hosted clients can insert the OAM token extracting it from Authenticated Subject

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00119: Either authorization header or requireTLS must be present.**

---

**Cause:** The security policy attached did not have either auth Header or requireTLS set to true.

**Action:** Change the policy to have either auth Header or requireTLS to be true.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00120: Cannot compute endorsing signature as no message signature is present.**

**Cause:** The security policy did not sign anything from the message, so no signature was there. Endorsing Signature could not be computed as the signature which it was trying to endorse was not present.

**Action:** Change the policy to Sign at least something in the message.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00121: Only the attachments are to be signed/encrypted and they are not present.**

**Cause:** Only the attachments were to be signed/encrypted and they were not present.

**Action:** Retry after putting attachments in the SOAP Message.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00122: Valid timestamp is not present in the message.**

**Cause:** Timestamp was not present in the message or the timestamp present did not conform to specifications.

**Action:** Ensure the timestamp is present in the message.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00123: Timestamp of the message is in future.**

**Cause:** The message had Created timestamp of a time in future so it failed Future message validation.

**Action:** Ensure freshness of the message and check policy-accessor-config.xml for the configured values of agent.clock.skew.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00124: Timestamp of the message is in past.**

**Cause:** The message was older than the permissible time limit so it failed Past message validation.

---

**Action:** Ensure freshness of the Message and check the policy-accessor-config.xml for the configured values of agent.clock.skew and agent.expire.time.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00125: Password digest validation failed.**

**Cause:** The password digest in the message was not correct so it failed the digest validation.

**Action:** Retry after ensuring password digest is proper.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00126: Subject does not contain JPS user.**

**Cause:** The subject mentioned did not have the JPS User.

**Action:** Retry after ensuring JPS user in the subject.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00127: User not in identity store.**

**Cause:** The user mentioned was not present in the identity store.

**Action:** Retry after ensuring that user is present in the identity Store.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00128: Keystore instance is null.**

**Cause:** Could not obtain keystore instance. Either the keystore instance type was wrong or the keystore configuration was wrong.

**Action:** Check JPS configuration settings. Use correct keystore instance type.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00129: Unsupported SAML token provided : {0}.**

**Cause:** An unsupported SAML token confirmation method was provided.

**Action:** Provide a supported SAML token confirmation method and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00130: SAML assertion subject is missing.**

---

**Cause:** The SAML assertion subject name was not specified.

**Action:** Provide the SAML assertion subject and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00131: Unsupported data encryption algorithm: {0}.**

**Cause:** An unsupported data encryption algorithm was provided.

**Action:** Consult the documentation for the supported encryption algorithms and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00132: Invalid JPS configuration.**

**Cause:** An invalid JPS configuration was provided.

**Action:** Make sure that the JPS configuration is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00134: The signature key, {0}, is not retrieved due to exception {1}.**

**Cause:** Error occurred while obtaining the signature key from store.

**Action:** Check JPS configuration settings. Make sure that the key password , keystore password, and key alias are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00135: The encryption key, {0}, is not retrieved due to exception {1}.**

**Cause:** Error occurred while obtaining encryption key from store.

**Action:** Check JPS configuration settings. Use correct key password, keystore password, and key alias.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00136: The signature certificate, {0}, is not retrieved due to exception {1}.**

**Cause:** Failure occurred while retrieving the signature certificate from store.

**Action:** Check JPS configuration settings for keystore location and make sure that the requested certificate is present.

**Level:** 1

**Type:** ERROR

**Impact:** Security

---

**WSM-00137: The encryption certificate, {0}, is not retrieved due to exception {1}.**

**Cause:** Failure occurred while retrieving the encryption certificate from store.

**Action:** Check JPS configuration settings for keystore location and make sure that the requested certificate is present.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00138: The path to the certificate is invalid due to exception {0}.**

**Cause:** The intermediate and root certificates of the certificate were not present in the keystore during verification.

**Action:** Make sure that the entire certificate chain is available in the keystore for verification.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00139: The scenario category {0} is not supported.**

**Cause:** The scenario category is not supported.

**Action:** Consult the Oracle documentation for supported categories.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00140: Invalid execution stage {0} resulting in system internal error.**

**Cause:** System encountered an invalid execution stage.

**Action:** Retry the operation, If problem persists contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Security

**WSM-00141: Error retrieving SOAP header from SOAP message.**

**Cause:** An error occurred while retrieving the header from the SOAP Message. The SOAP message was invalid or was tampered with.

**Action:** Make sure that the SOAP message is valid according to the specifications and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00142: Assertion belonging to {0} category is not valid for Component policy**

**Cause:** Assertion belonging to authentication or message protection category was found in Component policy and it is invalid.

**Action:** Modify the policy to correct the problem and retry the operation.

**Level:** 1

---

**Type:** ERROR

**Impact:** Security

**WSM-00143: Failure creating Java Keystore instance for type {0}.**

**Cause:** Either the keystore type provided is not supported or there is no implementation provider for Java keystore.

**Action:** Consult the Oracle documentation for supported Keystore types and make sure the implementation provider for Java Keystore is available.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00144: Failure retrieving Keystore aliases.**

**Cause:** Keystore may have not been initialized.

**Action:** Check the log file for possible causes and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00149: SAML assertion is missing.**

**Cause:** Failed to locate SAML assertion with ID {0}.

**Action:** Make sure that a valid SAML assertion exists.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00150: Processed header list fetched from InterceptorContext is null, agentFunction:{0}, listType:{1}.**

**Cause:** Processed header list fetched from InterceptorContext is null.

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Security

**WSM-00153: Error retrieving Weblogic Server subject from JPS subject using SubjectSecurityUtil API**

**Cause:** A failure occurred while converting JPS subject to Weblogic Server subject.

**Action:** Check log file for possible cause.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00155: Error retrieving Oracle WSM security policies.**

**Cause:** A failure occurred while retrieving Oracle WSM security policies.

**Action:** Check log file for possible cause.

---

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00156: Invalid binary security token.**

**Cause:** Binary security token in the header and the certificate used for endorsing signature did not match.

**Action:** Make sure a valid binary security token is being passed.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00157: Recipient key alias not configured and signer certificate was not available because no part of the request was signed.**

**Cause:** Recipient key alias not configured and signer's certificate was not available because no part of request was signed.

**Action:** Set recipient key alias in service policy or sign part of the request.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00158: KerberosLoginModule class is not available in the classpath**

**Cause:** The class for the Kerberos login module was not available in the classpath.

**Action:** Make sure that the KerberosLoginModule class is included in the classpath, and configure the class name properly in policy-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00159: TextCallbackHandler class is not available in the classpath**

**Cause:** The class for the Text callback handler was not available in the classpath.

**Action:** Make sure that the TextCallbackHandler class is included in the classpath, and configure the class name properly in policy-config.xml.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00160: The SSL policy must contain a requireTLS element.**

**Cause:** The security policy attached did not have requireTLS set to true.

**Action:** Change the policy to have requireTLS as true.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00161: Client encryption public certificate is not configured for Async web service client**

---

**Cause:** Client encryption public certificate is not configured for async web service client with message protection.

**Action:** Make sure that client public certificate is configured in client keystore, or provided through client config override for Async web service client that uses message protection

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00162: Invalid recipient cert type: {0} may have been provided through override; It should be either a X509Certificate object or Base64 encoded value in String format.**

**Cause:** Invalid recipient cert type may have been provided through override; It should be either a X509Certificate object or Base64 encoded value in String format.

**Action:** Verify that only X509Certificate object, or Base64 encoded String value are provided in Policy, descriptor file or through program.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00163: Failure in getting recipient certificate using recipient key alias {0}**

**Cause:** The recipient key alias might not be valid

**Action:** Check to see if there is such certificate in keystore corresponding to the recipient key alias provided.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00164: Cannot obtain a valid recipient cert for client message sending**

**Cause:** Encountered error while obtaining recipient certificate for sending request.

**Action:** Must provide valid recipient certificate, or recipient alias for client to send request with message protection.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00165: Creating recipient certificate from base64 encoded string: {0} failed.**

**Cause:** Encountered error while creating recipient certificate from base64 encoded string.

**Action:** Must provide valid certificate in valid base64 encoded string.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00166: Extract certificate from saved ReplyTo header failed.**

**Cause:** X509Certificate within ReplyTo header element might be invalid.



---

**Action:** Ensure that cert. insertion, ReplyTo header serialization/deserialization to JMS queue are all working properly.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00167: Actual Hostname {0} and Hostname retrieved from Certificate {1} do not match**

**Cause:** HostName verification of certificate retrieved from WSDL failed

**Action:** Either ensure that the Subject Dn matches the Hostname of the Service or disable the HostName Verification check

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00168: Unable to extract X509Certificate from WSDL Definition Object as WSDL definition Object is unavailable**

**Cause:** WSDL definition required for extraction of X509Certificate not available

**Action:** Ensure that WSDL Definition Object is available from the MessageContext

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00169: Error decrypting the request message.**

**Cause:** The request message could not be decrypted using the key specified for decryption.

**Action:** Ensure that the key used for decryption is same as the one used for encryption.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00170: There are no assertions available under the ExactlyOne policy operator.**

**Cause:** There are no assertions under ExactlyOne policy operator.

**Action:** Ensure that one or more security assertions are kept under ExactlyOne policy operator.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00171: A client policy contains an ExactlyOne policy operator.**

**Cause:** A client policy contained an ExactlyOne policy operator.

**Action:** Remove the ExactlyOne policy operator or switch to a service binding.

**Level:** 1

**Type:** ERROR

---

**Impact:** Security

**WSM-00172: A generic policy contains an ExactlyOne policy operator.**

**Cause:** A generic policy contained an ExactlyOne policy operator.

**Action:** Remove the ExactlyOne policy operator or switch to a service binding.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00173: A policy contains more than one ExactlyOne policy operator.**

**Cause:** A policy contained more than one ExactlyOne policy operator.

**Action:** Remove the additional ExactlyOne policy operators.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00174: A policy contains a nested ExactlyOne policy operator.**

**Cause:** A policy contained a nested ExactlyOne policy operator.

**Action:** Remove the nested ExactlyOne policy operators.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00175: Recipient Certificate for async callback client is not found under the ReplyTo element in async callback client message context**

**Cause:** Recipient cert. for async callback client is not available from message context.

**Action:** Ensure that original async client has public encryption certificate configured and is inserted into the ReplyTo header or the original async request. Also ensure that the original ReplyTo header along with client encryption certification is preserved and restored to the callback client message context.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00176: The mapped long name(s) for property {0} is null, the property might not be available for client programmatic override. Make sure it is indeed the intension, otherwise, add a mapping to map ConfigOverrideMapping.**

**Cause:** The config override property does not have a corresponding long name mapping

**Action:** Make sure this is indeed intended, otherwise, add a mapping to the ConfigOverrideMapping.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

---

**WSM-00177: The CSF key provided by the user is not present in the credential store. So using the default key is being used.**

**Cause:** The CSF key provided by the user is not present in the credential store

**Action:** Provide a valid key. Till then the default key will be used.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WSM-00178: Public key not found for SAML signature verification.**

**Cause:** Public key not found for SAML signature verification

**Action:** Ensure that public key is present in Security header which is required For SAML signature verification

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**WSM-00179: SAML assertion issuer name is invalid.**

**Cause:** SAML assertion issuer name is invalid.

**Action:** Check to see that the overridden SAML trusted issuers has SAML assertion issuer name.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00180: The trust version {0} is not supported for policy advertisement, hence ignored. The default trust version {1} is advertised.**

**Cause:** The trust version specified in the policy is not supported.

**Action:** Modify the policy with a supported trust version.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**WSM-00181: A policy issued-token attributes require-internal-reference and require-external-reference both are false, one of them has to be true.**

**Cause:** A policy issued-token attribute require-internal-reference and require-external-reference can not both be false.

**Action:** At least one of the attribute require-internal-reference and require-external-reference must be set to true

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00182: A policy request-security-token-template element attribute token-type has an unsupported value: {0}**

**Cause:** A policy request-security-token-template element contains a token-type that is not supported.

---

**Action:** Check documentation for supported token-type

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00183: A policy request-security-token-template element attribute algorithm-suite has a value: {0} which does not match to that of msg-security: {1}, change it to match {1}.**

**Cause:** A policy request-security-token-template element contains an algorithm-suite value that does not match to that of msg-security.

**Action:** Change the algorithm-suite attribute value to match exactly the one in msg-security

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00184: An attribute trust-version has an unsupported version: {0}**

**Cause:** A policy contains an unsupported WS-TRUST version.

**Action:** Check documentation for supported WS-TRUST version

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00185: Attribute require-client-entropy and require-server-entropy can not both be set to false, at lease one of them must be set to true.**

**Cause:** A policy can not have both require-client-entropy and require-server-entropy attributes set to false.

**Action:** At lease set one of them to true

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00186: A policy request-security-token-template key-type attribute is expected to be: {0}, but got: {1}**

**Cause:** A policy request-security-token-template key-type attribute value is not set to the expected Bearer.

**Action:** Set the attribute value to the expected

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00187: A policy request-security-token-template key-type attribute is expected to be: {0}, but got: {1}**

**Cause:** A Bearer policy request-security-token-template key-type attribute value is not set to the expected Symmetric or Public.

**Action:** Set the attribute value to one of the expeted value Symmetric or Public

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00188: STS Trust Config policy attribute port-uri has invalid value "{0}", it must be not null, not empty and in the format of http(s)://host:port/sts-service**

**Cause:** STS trust config attribute port-uri is either null, empty or not in the format of "http(s)://host:port/sts-service-name".

**Action:** Provide valid attribute value which is in the format of "http(s)://host:port/sts-service"

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00189: STS Trust Config policy attribute port-endpoint has invalid value "{0}", it must be not empty and in the format of target-namespace#wsdl.endpoint(service-name/port-name)**

**Cause:** STS trust config attribute port-endpoint is either empty or not in the format of "target-namespace#wsdl.endpoint(service-name/port-name)".

**Action:** Provide valid attribute value which is in the format of "target-namespace#wsdl.endpoint(service-name/port-name)"

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00190: STS Trust Config policy attribute policy-reference-uri can not have empty value.**

**Cause:** The value of STS trust config attribute policy-reference-uri is empty or not in the URI format

**Action:** Specify value for attribute policy-reference-uri

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00191: STS Trust Config policy attribute sts-keystore-recipient-alias can not have null or empty value.**

**Cause:** The value of STS trust config attribute sts-keystore-recipient-alias is null or empty

**Action:** Specify a non null or empty value for attribute sts-keystore-recipient-alias

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00192: Kerberos name identifier format is not supported for SAML 1.1 token.**

**Cause:** Kerberos name identifier format is not supported for SAML 1.1 token.

**Action:** Kerberos name identifier format is only for SAML 2.0 token, use other name identifier formats.

---

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00193: Security policy contains NULL or empty value for signed-element local name or namespace.**

**Cause:** Security policy contains NULL or empty value for signed-element local name or namespace.

**Action:** Signed-element local name or namespace must not be null or empty.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00194: Security policy contains NULL or empty value for signed-part header namespace.**

**Cause:** Security policy contains NULL or empty value for signed-part header namespace.

**Action:** Signed-part header namespace must not be null or empty.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00195: Security context for derived key unknown (cannot determine the base symmetric key).**

**Cause:** Security context for derived key unknown (cannot determine the base symmetric key).

**Action:** DerivedKeyToken should include SecurityReferenceToken (can only be empty in responses where the message context includes the base key).

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00196: Unable to resolve base key referenced in DerivedKeyToken.**

**Cause:** Unable to resolve base key referenced in DerivedKeyToken.

**Action:** Ensure the SecurityTokenReference in the DerivedKeyToken specifies a valid base key within the security context.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00197: Unsupported SecurityTokenReference type for DerivedKeyToken.**

**Cause:** Unsupported SecurityTokenReference type for DerivedKeyToken.

**Action:** Ensure the SecurityTokenReference in the DerivedKeyToken is one of the supported types.

**Level:** 1

**Type:** ERROR

---

**Impact:** Security

**WSM-00198: Unable to resolve EncryptedKey that matches EncryptedKeySHA1 in KeyInfo.**

**Cause:** Unable to resolve EncryptedKey that matches EncryptedKeySHA1 in KeyInfo.

**Action:** The value of the EncryptedKeySHA1 should match an encrypted key in the security context.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00199: Unsupported key identifier type "{0}" in security token reference.**

**Cause:** Unsupported key identifier type in security token reference.

**Action:** Use only of the supported key identifier types in the security token.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00200: Exception encountered while checking compliance; returning false.**

**Cause:** Exception encountered while checking compliance; returning false.

**Action:** Check log for exception details.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00201: There are no <EncryptedKey> elements in the request.**

**Cause:** There are no <EncryptedKey> elements in the request.

**Action:** The request should have an <EncryptedKey> element.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00202: Proof key type is invalid, valid values are null, public, symmetric.**

**Cause:** The value of keytype is invalid for SAML Issued Token Policy, valid values are null (no proof key), public, symmetric

**Action:** Specify valid value for keytype based on the policy

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00203: Invalid OPSS Trust Service**

**Cause:** OPSS TrustService is empty or null

**Action:** Configure Trust Service in OPSS

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**WSM-00204: Invalid issued token from trust token exchange**

**Cause:** Issued token is null

**Action:** Check Logs and correct any errors during issuance

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WSM-00205: Proof key type is invalid, valid value is bearer**

**Cause:** The value of keytype is invalid for SAML Bearer Issued Token Policy , valid value is bearer

**Action:** Specify bearer as the key type for this policy

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00206: Requester credentials for authenticating to STS are invalid**

**Cause:** Requester Credentials required for authenticating to STS are missing

**Action:** Configure sts.auth.user.csf.key or sts.auth.x509.csf.key in issued token policy

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00207: Asymmetric proof key is invalid**

**Cause:** Asymmetric proof key is invalid

**Action:** Configure sts.auth.x509.csf.key in issued token policy

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00208: STS On behalf of user is invalid**

**Cause:** STS On behalf of user is invalid

**Action:** Configure sts.auth.on.behalf.of.csf.key in issued token policy

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00209: Permission{0} required to switch the identity not granted to the resource. {1}**

**Cause:** Permission required to switch the identity not granted

**Action:** Grant Permission for identity switching to the codesource.

**Level:** 1



---

**Type:** ERROR

**Impact:** Security

**WSM-00210: Client is unable to find actual webservice endpoint to set in appliesTo**

**Cause:** Client requires appliesTo and unable to find the actual webservice endpoint URL

**Action:** Check if agent binding ws port ID , service name and port name in log file

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00211: Trust token provider tried creating RequestSecurityToken message and it failed because algorithm use to generate asymmetric key pair was invalid**

**Cause:** Trust token provider tried creating RequestSecurityToken message and it failed because algorithm use to generate asymmetric key pair was invalid

**Action:** Check the asymmetric key algorithm

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WSM-00212: Trust token provider tried creating RequestSecurityToken message and it failed because asymmetric proof key was invalid**

**Cause:** Trust token provider tried creating RequestSecurityToken message and it failed because asymmetric proof key was invalid

**Action:** Check if sts.auth.x509.csf.key is configured correctly in issued token client policy

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WSM-00213: Unable to parse SOAP message sent by STS**

**Cause:** Unable to parse SOAP message sent by STS

**Action:** Check if message sent by STS is valid

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WSM-00214: Unable to parse RequestSecurityTokenResponseCollection**

**Cause:** Unable to parse RequestSecurityTokenResponseCollection

**Action:** Check if RequestSecurityTokenResponseCollection message sent by STS is valid

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**WSM-00215: Unable to parse STSTrustConfig**

**Cause:** Unable to parse STSTrustConfig

**Action:** Check if STSTrustConfig is valid

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WSM-00216: Unable to create SOAP RequestSecurityToken message**

**Cause:** Unable to create SOAP RequestSecurityToken message

**Action:** Failure in creating SOAP RequestSecurityToken message, check log files

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WSM-00217: STS endpoint URL or WSDL URL (if configured) is invalid**

**Cause:** STS endpoint URL or WSDL URL (if configured) is invalid

**Action:** Check if STS endpoint URL and WSDL URL (if configured) are valid

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WSM-00218: Security token returned by STS is null**

**Cause:** Security token returned by STS is null

**Action:** Check if RSTR message sent by STS is valid

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WSM-00219: Proof token returned by STS is null**

**Cause:** Proof token returned by STS is null

**Action:** Check if RSTR message sent by STS is valid

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WSM-00220: Invalid proof token type, valid values are computedKey and BinarySecret**

**Cause:** Invalid proof token type, valid values are computedKey and BinarySecret

**Action:** Check the proof token type, valid values are computedKey and BinarySecret

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**WSM-00221: Computed key in RSTR message sent by STS is invalid**

**Cause:** Computed key in RSTR message sent by STS is invalid

**Action:** Check the computed key in RSTR message sent by STS

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WSM-00222: Computed key algorithm in RSTR message sent by STS is invalid}**

**Cause:** Computed key algorithm in RSTR message sent by STS is invalid, valid value is <http://docs.oasis-open.org/ws-sx/ws-trust/200512/CK/PSHA1>

**Action:** Check the computed key in RSTR message sent by STS, valid value is <http://docs.oasis-open.org/ws-sx/ws-trust/200512/CK/PSHA1>

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WSM-00223: Request type is invalid, valid value is issue**

**Cause:** Request type invalid, valid value is issue

**Action:** Check request type in response sent by STS

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WSM-00224: User credentials of the user on behalf of whom the token is to be issued is missing**

**Cause:** User credentials of the user on behalf of whom the token is to be issued is missing

**Action:** Check on.benefit.of property in issued token policy. If its set to true then either subject or sts.auth.on.benefit.of.csf-key property needs to be present

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WSM-00225: STS On behalf of user password is invalid**

**Cause:** STS On behalf of user password is invalid

**Action:** Configure sts.auth.on.benefit.of.csf.key in issued token policy

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00226: Security policy contains NULL or empty value for encrypted-element local name or namespace.**

**Cause:** Security policy contains NULL or empty value for encrypted-element local name or namespace.

**Action:** Encrypted-element local name or namespace must not be null or empty.

---

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00227: Could not resolve key to use for decryption.**

**Cause:** Could not resolve key to use for decryption.

**Action:** Ensure request contains all the information necessary to successfully resolve decryption key.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00228: Oracle system user is missing in identity store**

**Cause:** Could not find oracle system user .

**Action:** Check if OracleSystemUser exists in identity store

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00229: jndi.lookup.csf.key missing in policy-accessor-config**

**Cause:** Could not find valid jndi.lookup.csf.key in policy-accessor-config.xml .

**Action:** Check jndi.lookup.csf.key is configured correctly in policy-accessor-config.xml

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00230: Cannot find service information from WSDL {0}**

**Cause:** Cannot find service information from WSDL

**Action:** Check the service information in the WSDL

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WSM-00231: Cannot find client compatible policy for STS {0}, port name {1}**

**Cause:** Cannot find compatible client policy for STS invocation

**Action:** Check if policy store has compatible client policy

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WSM-00232: Failed to create dynamic STS policy**

**Cause:** Failed to create dynamic STS policy

**Action:** Check exception stack trace for details

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WSM-00233: STS WSDL URI {0} is invalid**

**Cause:** STS trust config attribute wsdl-uri is not in the format of "http(s)://host:port/sts-service?wsdl".

**Action:** Provide valid attribute value which is in the format of "http(s)://host:port/sts-service?wsdl"

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00234: The <saml:Assertion> element of version {0} is missing in the security header.**

**Cause:** Saml assertion with specific version e.g. 1.1, or 2.0 etc. is missing. in the received message

**Action:** Check exception stack trace for details

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WSM-00235: Failed to initialize dispatcher**

**Cause:** Failed to initialize dispatcher for client to STS communication

**Action:** Check exception stack trace for details

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WSM-00237: FKS keystore with stripeName {0}, keystoreName {1} can not be loaded due to {2}.**

**Cause:** The following FKS keystore-related configuration properties may not be valid:keystore.type, keystore.pass, keystore.name. Also, check permissions on the keystore.

**Action:** Verify the configuration properties mentioned above and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00238: Unable to read FKS keystore. Grant necessary permission to read FKS keystore, stripe name {0} and keystore name {1}**

**Cause:** FKS keystore may have not been initialized or necessary permissions are not granted.

**Action:** Ensure that necessary permission to read FKS keystore is granted.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**WSM-00239: FKS trust store can not be loaded, ensure that necessary permissions are granted.**

**Cause:** FKS trust store can not be loaded, probably necessary permissions are not granted.

**Action:** Ensure that necessary permission to read FKS trust store is granted.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00240: FKS trust store is NULL, ensure that FKS system trust store exist.**

**Cause:** FKS trust store is NULL, may be it doesn't exist or probably necessary permissions are not granted.

**Action:** Ensure that FKS trust store exists in system stripe and permissions are granted.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00241: Failure retrieving FKS trust store aliases.**

**Cause:** FKS trust store may have not been initialized.

**Action:** Check the log file for possible causes and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00242: The certificates cannot be retrieved from the trust store.**

**Cause:** Failure occurred while trying to retrieve certificate from trust store.

**Action:** Use a valid alias for the certificate and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00243: Unable to read key from FKS keystore. Grant necessary permission to read alias {2} from FKS keystore, stripe name {0} and keystore name {1}**

**Cause:** Unable to read key from FKS keystore. FKS keystore may have not been initialized or necessary permissions are not granted.

**Action:** Ensure that alias exists in keystore and necessary permission to read key alias is granted.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**WSM-00244: Unable to read certificate from FKS keystore. Grant necessary permission to read certificate alias {2} from FKS keystore, stripe name {0} and keystore name {1}**

**Cause:** Unable to read certificate from FKS keystore. FKS keystore may have not been initialized or necessary permissions are not granted.

**Action:** Ensure that alias exists in keystore and necessary permission to read certificate alias is granted.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00245: Failure retrieving FKS key store aliases.**

**Cause:** Unable to list alias from FKS key store.

**Action:** Check the log file for possible causes and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-00246: Failure retrieving IssuedTokenAssertion from advertised policy.**

**Cause:** Possibilly there is a failure in parsing the advertised policy

**Action:** Check the log file for possible causes and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-00247: Failed to sign with RSA Key Pair**

**Cause:** Failed to sign with RSA Key Pair

**Action:** Check exception stack trace for details

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00248: Attesting entity attribute {0} is unsupported.**

**Cause:** Unsupported attesting entity attribute is used

**Action:** Attesting entity attribute must be DN.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00249: SAML token DN validation failed for SAML assertion signer DN {0}.**

**Cause:** SAML token DN list validation failed.

**Action:** Assertion signer DN is not present in trusted DN list, if DN is valid then add it to trusted DN's list.

**Level:** 1

---

**Type:** ERROR

**Impact:** Security

**WSM-00250: Unable to find an implementation class for {0}.**

**Cause:** Unable to find an implementation class for 'javax.el.ExpressionFactory'.

**Action:** Make sure that the implementation class for 'javax.el.ExpressionFactory' is available in the classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00251: Failed to create an instance of {0}.**

**Cause:** Failed to create an instance of the javax.el.ExpressionFactory implementation class.

**Action:** Make sure that the javax.el.ExpressionFactory implementation class can be instantiated.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00252: Failed to evaluate the constraint expression "{0}" due to the exception: {1}**

**Cause:** Failed to evaluate the constraint expression.

**Action:** Make sure that the constraint expression is valid. Check exception stack trace for details.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00253: The constraint expression "{0}" is not valid. The constraint expression should evaluate to the boolean values.**

**Cause:** The constraint expression is not valid.

**Action:** Make sure that the constraint expression evaluates to the boolean values.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00254: The current server time is "{0}", incoming message creation time is "{6}", configured agent expiry is {5} seconds, incoming message expiry is {7} seconds, effective message expiry (minimum of agent expiry and incoming message expiry) is {1} seconds, configured clock skew is {2} seconds. The acceptable time range is "{3}" to "{4}". The incoming message is before/after the acceptable time.**

**Cause:** The incoming message is outside the valid range as allowed by clock skew and expiry times.

**Action:** Adjust times on servers/clients. Check the allowed clockskew and message expiration time and configure them as required.

**Level:** 1



---

**Type:** ERROR

**Impact:** Security

**WSM-00257: Callback class name "{0}" set for SAML certificate validation not found**

**Cause:** Callback class set for SAML certificate validation not found.

**Action:** Make sure that callback class name is correct and added in classpath.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00258: Callback class name "{0}" set for SAML certificate validation is invalid.**

**Cause:** Callback class set for SAML certificate validation is not valid.

**Action:** Make sure that callback class correctly extends required class.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00259: SAML certificate validation callback failed. {0}.**

**Cause:** Callback class set for SAML certificate validation failed.

**Action:** Check the error message for details.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00260: SAML over SSL certificate validation failed because certificate returned from callback and actual certificate differ. Actual certificate DN={0} and callback cert DN={1}**

**Cause:** SAML over SSL certificate validation failed because certificate returned from callback and actual certificate differ.

**Action:** Make sure that client certificate sent over SSL and certificate returned from callback are same.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-00261: SAML certificate validation callback failed because certificate returned from callback is NULL.**

**Cause:** Callback class set for SAML certificate validation failed because certificate returned from callback is NULL.

**Action:** Check callback implementation class for the reason of null certificate.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-01501: failure in parsing the policy attachment**

---

**Cause:** The XML was not well formed, or the XML did not follow the policy attachment schema.

**Action:** Ensure that the XML is well formed, and the XML follows the policy attachment schema.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01502: failure in parsing the assertion template**

**Cause:** The XML was not well formed, or the XML did not follow the assertion template schema.

**Action:** Ensure that the XML is well formed, and the XML follows the assertion template schema.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01503: failure in parsing the assertion**

**Cause:** The XML was not well formed, or the XML did not follow the assertion schema.

**Action:** Ensure that the XML is well formed, and the XML follows the assertion schema.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01504: failure in parsing the property set configuration**

**Cause:** The XML was not well formed, or the XML did not follow the property set Config schema.

**Action:** Ensure that the XML is well formed, and the XML follows the property set Config schema.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01505: failure in creating a copy of the policy {0}**

**Cause:** Copying of the policy failed.

**Action:** Ensure that the policy to be copied is valid. If the problem persists, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-01506: failure in creating a copy of the assertion template {0}**

**Cause:** Copying of the assertion template failed.

---

**Action:** Ensure that the assertion template to be copied is valid. If the problem persists, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-01507: failure in creating a copy of the assertion {0}**

**Cause:** Copying of the assertion failed.

**Action:** Ensure that the assertion to be copied is valid. If the problem persists, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-01508: failure in transforming policy {0} to XML**

**Cause:** The policy could not be serialized to XML.

**Action:** Ensure that the policy Java object can be serialized to XML format.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01509: failure in transforming policy set {0} to XML**

**Cause:** The policy set could not be serialized to XML.

**Action:** Ensure that the policy set Java object can be serialized to XML format.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01510: failure in transforming policy attachment {0} to XML**

**Cause:** The policy attachment could not be serialized to XML.

**Action:** Ensure that the policy attachment Java object can be serialized to XML format.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01511: failure in transforming assertion template {0} to XML**

**Cause:** The assertion template could not be serialized to XML.

**Action:** Ensure that the assertion template Java object can be serialized to XML format.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01512: failure in transforming assertion {0} to XML**

---

**Cause:** The assertion could not be serialized to XML.

**Action:** Ensure that the assertion Java object can be serialized to XML format.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01513: failure in transforming configuration {0} to XML**

**Cause:** The configuration could not be serialized to XML.

**Action:** Ensure that the configuration Java object can be serialized to XML format.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01514: failure in transforming policy reference {0} to XML**

**Cause:** System could not serialize policy reference to XML.

**Action:** Ensure passed policy reference Java object doesn't have issues that causes the serialization to XML to fail.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01515: failure in transforming policy subject {0} to XML**

**Cause:** System could not serialize policy subject to XML.

**Action:** Ensure passed policy subject Java object doesn't have issues that cause the serialization to XML to fail.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01524: failure in serialization of WSDL**

**Cause:** WSDL Serialization failed.

**Action:** Ensure WSDL Extensions are available and configured. Consult diagnostic log for details or contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-01526: WSDL Definition object is null**

**Cause:** WSDL Definition Object is not available

**Action:** Ensure that a valid WSDL Definition object is sent to OWSM for advertisement of wsdl.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**WSM-01600: error in creating or initializing the assertion, key={0}, qname={1},  
wspqname={2}, constructorName={3}**

**Cause:** An assertion object could not be created.

**Action:** Verify that the assertion follows the interface requirements defined in the Oracle documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WSM-01601: failure in loading the resource**

**Cause:** The requested resource could not be loaded.

**Action:** Ensure that the requested resource is present in the class path.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-01602: error in loading class {0}**

**Cause:** The requested class could not be loaded.

**Action:** Ensure that the requested class is present in the class path.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WSM-01603: failure in parsing the policy**

**Cause:** Parsing of the policy failed.

**Action:** Ensure that the policy XML follows the policy schema, or a valid policy file exists.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01604: XML Parser Configuration error**

**Cause:** The XML Parser was not configured properly.

**Action:** Consult Oracle documentation or Java documentation on how to configure the XML Parser.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-01605: XML parser exception**

**Cause:** Parsing of the XML failed.

**Action:** Ensure that the XML is well formed.

**Level:** 1

**Type:** ERROR

---

**Impact:** Data

**WSM-01606: system I/O error**

**Cause:** The system could not open the Input/Output streams.

**Action:** Consult the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**WSM-01607: XPath expression evaluation error**

**Cause:** Evaluation of the XPATH expression failed.

**Action:** Ensure that the XPATH expression is valid, and the XML follows the schema.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01608: The class cannot be found.**

**Cause:** The requested class was not found in the class path.

**Action:** Ensure that the class name is correct in the configuration files and is in the class path.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-01610: cannot initialize standard serializers/deserializers**

**Cause:** The standard serializer and deserializer objects could not be loaded.

**Action:** Ensure that the product configuration is correct. If the problem persists, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**WSM-01611: The class cannot be loaded because of Java security restrictions.**

**Cause:** The requested classes could not be loaded due to class loading security restrictions.

**Action:** Contact the site administrator or consult the Java documentation to ensure that the classes have the necessary Java security permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-01612: An instance of the requested class cannot be created.**

**Cause:** The system could not create an instance of the requested class.

**Action:** Consult the Java documentation or contact Oracle Support Services.

---

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**WSM-01613: The XML parser cannot be configured.**

**Cause:** The XML parser could not be configured.

**Action:** Consult the Java documentation on how to configure the XML parser.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-01614: The assertion XML Java Document cannot be serialized to a String.**

**Cause:** The assertion XML Java Document could not be serialized to a String.

**Action:** Check the assertion for any errors and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01615: The assertion XML String cannot be converted to a Java object.**

**Cause:** The assertion XML String could not be converted to a Java Document.

**Action:** Ensure that the String being converted to XML is a well-formed XML.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01616: Policy {0} cannot be inserted into the WSDL.**

**Cause:** The WSDL extensions for the policy could not be found or were incorrectly configured.

**Action:** Ensure that the WSDL extensions for the policy being injected are available and configured. Consult Oracle documentation for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01617: error in parsing the policies embedded in the WSDL**

**Cause:** The WSDL extensions for the policy could not be found or were incorrectly configured.

**Action:** Ensure that the WSDL extensions for policy are available and configured. Consult Oracle documentation for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01618: error in parsing the policy references embedded in the WSDL**

**Cause:** The XML for the policy references in the WSDL could not be parsed.

---

**Action:** Ensure that the WSDL extensions for the policy reference are available and configured. Consult Oracle documentation for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01619: This assertion type is not recognized.**

**Cause:** The assertion type was not recognized.

**Action:** Consult Oracle documentation for the supported assertion types.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01620: cannot convert XML Java Document to String**

**Cause:** The XML Java Document being converted was not well formed.

**Action:** Ensure that the assertions can be serialized to a String.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01621: Policy intersection algorithm is not defined for assertion type :**

**Cause:** The policy intersection algorithm was not found for the assertion.

**Action:** Ensure that the intersection algorithm for the assertion used is configured.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01622: Policy merge algorithm is not defined for assertion type :**

**Cause:** The policy merge algorithm was not found for the assertion.

**Action:** Ensure that the merge algorithm for the assertion used is configured.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01623: Policy reference cannot be resolved :**

**Cause:** The policy reference was invalid.

**Action:** Ensure that the policy reference is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01624: The policy does not exist in the policy store :**

**Cause:** The policy reference was invalid, or the referenced policy could not be retrieved.



---

**Action:** Ensure that the policy reference is valid, and the policy exists in the policy store.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01625: The Name attribute of the property is missing.**

**Cause:** The Name attribute for a property was missing.

**Action:** Provide a value for the Name attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01626: The Type attribute of the property is missing.**

**Cause:** The Type attribute for a property was missing.

**Action:** Provide a value for the Type attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01627: The assertion contains too many bindings.**

**Cause:** The assertion contained more than one binding.

**Action:** Ensure that the assertion contains a single binding.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01628: The policy normalization algorithm is not defined for this assertion type**

**Cause:** The policy normalization algorithm was not found for the assertion.

**Action:** Ensure that the normalization algorithm for the assertion used is configured.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01629: The assertion template contains too many assertions.**

**Cause:** The assertion template contained more than one assertion.

**Action:** Ensure that assertion template contains only one assertion.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01630: Element {0} is not a known policy element.**

**Cause:** XML parsing failed; the system encountered unsupported XML elements.

---

**Action:** Ensure that the XML follows the schema, and the XML contains only those elements that are supported.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01631: The assertion {0} contains multiple bindings.**

**Cause:** The assertion contained more than one binding.

**Action:** Ensure that the assertion contains only one binding.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01632: The assertion {0} contains multiple policies as child elements.**

**Cause:** The assertion contained more than one policy child element.

**Action:** Ensure that the assertion contains only one policy child element.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01633: Assertion type {0} does not match the corresponding Java Object type created.**

**Cause:** The assertion type was incorrectly defined for the assertion.

**Action:** Ensure that the correct assertion type is set for the assertion.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**WSM-01635: Passed Java Object {0} does not extend the Assertion class**

**Cause:** The Assertion class did not extend the correct classes.

**Action:** Consult Oracle Documentation for creating assertion implementations.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-01636: The assertion type {0} is not supported.**

**Cause:** The assertion type does not match any of the predefined assertion types.

**Action:** Ensure that the assertion type is supported.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-01637: The policy attachment cannot be parsed.**

**Cause:** The policy attachment XML was invalid.

---

**Action:** Ensure that policy attachment XML follows the policy attachment XML schema.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01638: The policy attachment is not valid because the domain is not specified.**

**Cause:** The policy attachment did not contain domain expressions.

**Action:** Ensure that policy attachment XML follows the policy attachment XML schema.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01640: The policy reference {0} is not valid.**

**Cause:** The policy reference could not be resolved.

**Action:** Ensure that the referenced policy exists in the policy store.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01641: The policy advertisement level is not specified for the policy.**

**Cause:** The policy advertisement level was not specified.

**Action:** Ensure that a valid value is set for the policy advertisement level.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-01642: Policy advertisement is not supported for unsupported WSDL elements.**

**Cause:** Policy advertisement was not supported for the WSDL object.

**Action:** Consult Oracle documentation for supported WSDL objects.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01643: What the XML system expects is different from what is encountered.**

**Cause:** Usage of system was invalid or the feature was unsupported.

**Action:** Consult Documentation on usage and supported features.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01644: The WSDL object {0} is not supported.**

**Cause:** The WSDL object was not supported.

---

**Action:** Consult Oracle documentation for the supported WSDL objects.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01645: The resource pattern {0} does not match the corresponding WSDL object.**

**Cause:** WSDL Objects did not match.

**Action:** Ensure that the WSDL Objects match.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01646: The value for the attachTo attribute of the policy is not valid.**

**Cause:** The attachTo attribute of the policy did not match any of the predefined attachTo values.

**Action:** Consult Oracle documentation for the valid values for the attachTo attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01647: There are no policies that match the specified category {0} and resource pattern {1}.**

**Cause:** No policies matched the specified search criteria.

**Action:** Ensure that the policies that match the search categories exist in the policy store.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01650: cannot construct policy object**

**Cause:** Construction of the policy Java object failed.

**Action:** Consult the diagnostic log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WSM-01651: cannot advertise requested policies**

**Cause:** Advertisement of the policies failed.

**Action:** Consult the diagnostic log for details, or contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Programmatic

---

**WSM-01652: error in parsing the time stamp in the policy set document**

**Cause:** The Timestamp attribute in the XML representation of a policy set document is not a valid number.

**Action:** Correct or remove the invalid attribute value.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Data

**WSM-01653: The assertion contains more than one Guard element.**

**Cause:** The assertion contained more than one guard.

**Action:** Ensure that the assertion contains a single guard.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01654: failure in serialization of security scenario assertion**

**Cause:** The SecurityScenario in OraPolicy could not be serialized or was incorrectly configured.

**Action:** Ensure that the OraPolicy is correct. Consult Oracle documentation for more information.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01655: There are no policies that match the specified category {0}.**

**Cause:** No policies matched the specified category.

**Action:** Ensure that the policies that match the search category exist in the policy store.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01656: generic Oracle WSM Policy Manager error**

**Cause:** An internal error occurred during the Policy related operation.

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01657: Oracle WSM Advertisement Engine must be initialized with valid properties. Following properties [{0}] are either empty or null**

**Cause:** WSM Advertisement Engine initialized with invalid parameters.

**Action:** Ensure that valid parameters are set during WSM Advertisement Engine configuration

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-01658: X509 Certificate will not be advertised as {0} not found**

**Cause:** Implementation class for advertising X509 Certificate in WSDL is not available

**Action:** Ensure that implementation class required for advertising X509 Certificate in WSDL is not available. Consult diagnostic log for details or contact Oracle Support Services.

**Level:** 1

**Type:** WARNING

**Impact:** Other

**WSM-01659: A JAXBContext cannot be created due to underlying exception "{0}".**

**Cause:** One or more expected classes could not be located.

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01660: A JAXB unmarshaller cannot be created due to underlying exception "{0}".**

**Cause:** An error occurred while creating an unmarshaller.

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01661: A string cannot be unmarshalled into an object due to underlying exception "{0}".**

**Cause:** The string is not suitable for unmarshalling to the requested type.

**Action:** Provide a string that is suitable for unmarshalling to the requested type.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01662: The QName "{0}" does not match the expected QName "{1}" for the unmarshalled object.**

**Cause:** The string is not suitable for unmarshalling to the requested type.

**Action:** Provide a string that is suitable for unmarshalling to the requested type.

**Level:** 1

**Type:** ERROR

---

**Impact:** Data

**WSM-01663: A null or empty string cannot be unmarshalled into an Intent object.**

**Cause:** An attempt was made to unmarshall an Intent from a null or empty String.

**Action:** Provide a String that contains a marshalled Intent.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01664: A null or empty string cannot be unmarshalled into a PolicySet object.**

**Cause:** An attempt was made to unmarshall a PolicySet from a null or empty String.

**Action:** Provide a String that contains a marshalled PolicySet.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01665: A JAXB marshaller cannot be created due to underlying exception "{0}".**

**Cause:** An error occurred while creating a marshaller.

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01666: An object cannot be marshalled to a string due to underlying exception "{0}".**

**Cause:** Marshalling the supplied type of the object is not supported.

**Action:** Provide an object of a supported type.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01667: An object cannot be marshalled to a DOM object due to underlying exception "{0}".**

**Cause:** Marshalling the supplied type of the object is not supported.

**Action:** Provide an object of a supported type.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01668: A null Intent object cannot be marshalled.**

**Cause:** An attempt was made to marshall a null Intent object.

**Action:** Provide a non-null Intent object.

**Level:** 1

---

Type: ERROR

Impact: Data

**WSM-01669: A null PolicySet object cannot be marshalled.**

**Cause:** An attempt was made to marshall a null PolicySet object.

**Action:** Provide a non-null PolicySet object.

Level: 1

Type: ERROR

Impact: Data

**WSM-01670: An object cannot be marshalled into a null DOM object.**

**Cause:** An attempt was made to marshall an object into a null Document object.

**Action:** Provide a non-null Document object.

Level: 1

Type: ERROR

Impact: Data

**WSM-01671: The DOM element cannot be null for policy subject identified by the resource pattern: "{0}".**

**Cause:** The null DOM element was passed.

**Action:** Pass a valid non-null DOM element.

Level: 1

Type: ERROR

Impact: Compliance

**WSM-01672: The policy reference URI: "{1}" for policy subject identified by the resource pattern: "{0}" cannot be empty.**

**Cause:** Empty policy references were found in the DOM element node.

**Action:** Verify the DOM element node and make sure the policy references specify a valid value and the referenced policies exist in the repository.

Level: 1

Type: ERROR

Impact: Compliance

**WSM-01673: Duplicate policy references: "{1}" are found for policy subject identified by resource pattern "{0}".**

**Cause:** Duplicate policy references were found in the same DOM element node.

**Action:** Remove the duplicate policy references from the DOM element node.

Level: 1

Type: ERROR

Impact: Compliance

**WSM-01674: The DOM element: "{1}" for policy subject identified by resource pattern "{0}" is unsupported element.**

**Cause:** Policies cannot be retrieved for unsupported DOM element node.



---

**Action:** Verify that a supported DOM element node is provided for retrieving the policy.

**Level:** 1

**Type:** WARNING

**Impact:** Compliance

**WSM-01675: The policy references cannot be null.**

**Cause:** A null policy reference was passed.

**Action:** Pass the valid non-null policy reference object.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**WSM-01676: The resource pattern cannot be null.**

**Cause:** A null resource pattern was passed.

**Action:** Pass a valid non-null resource pattern.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**WSM-01677: The domain expression cannot be null.**

**Cause:** A null domain expression was passed.

**Action:** Pass a valid non-null domain expression.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**WSM-01678: Element {0} is not a valid child element for Policy object.**

**Cause:** Invalid child element found for Policy object.

**Action:** Check the policy string being parsed and make sure only valid child elements are present for the Policy.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01679: A DOM node cannot be unmarshalled into an object due to underlying exception "{0}".**

**Cause:** The string is not suitable for unmarshalling to the requested type.

**Action:** Provide a string that is suitable for unmarshalling to the requested type.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01680: A null node cannot be unmarshalled into a RepositoryInfo object.**

**Cause:** An attempt was made to unmarshall a RepositoryInfo from a null node.

---

**Action:** Provide a node that contains a marshalled RepositoryInfo.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01681: A null or empty string cannot be unmarshalled into a RepositoryInfo object.**

**Cause:** An attempt was made to unmarshall a RepositoryInfo from a null or empty String.

**Action:** Provide a String that contains a marshalled RepositoryInfo.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01682: A null RepositoryInfo object cannot be marshalled.**

**Cause:** An attempt was made to marshall a null RepositoryInfo object.

**Action:** Provide a non-null RepositoryInfo object.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01683: The passed String "{0}" could not be parsed using UTF encoding.**

**Cause:** Underlying JVM does not support UTF-8 encoding.

**Action:** Check the JVM configuration to make sure it supports UTF-8 encoding format.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01684: A null or empty string cannot be unmarshalled into a Policy object.**

**Cause:** An attempt was made to unmarshall a Policy from a null or empty String.

**Action:** Provide a String that contains a marshalled Policy.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01685: Issuer Uri is not available. Either sts\_trust\_config\_service\_policy is not attached to service or the Issuer Uri is missing from the policy. Ignore this warning if sts\_trust\_config\_client\_policy is attached to client.**

**Cause:** Issuer Uri is not available. Either sts\_trust\_config\_service\_policy is not attached to service or the Issuer Uri is missing from the policy. Ignore this warning if sts\_trust\_config\_client\_policy is attached to client.

**Action:** Attach sts\_trust\_config\_service\_policy if not attached yet, or specify issuer uri value in the policy if not specified. Ignore if using sts\_trust\_config\_client\_policy.

---

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**WSM-01686: Advertisement failed due to an unexpected assertion type: {0}.**

**Cause:** The assertion type is not recognized.

**Action:** Internal error. Provide

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-01687: The constant property "{0}" cannot be overridden.**

**Cause:** There is an attempt to override a property value which is defined as a constant in the policy.

**Action:** Ensure that there is no attempt to override a constant property.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**WSM-01688: X509 Certificate will not be advertised due to underlying exception "{0}".**

**Cause:** Either the keystore was not available or the keystore configuration was incorrect.

**Action:** Ensure the keystore exists and that the keystore password and aliases are correct.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**WSM-01689: Advertisement failed due to an incorrect ws-policy/ws-securitypolicy specification version {0}/{1}.**

**Cause:** Invalid ws-policy/ws-securitypolicy specification version used to advertise policy.

**Action:** Ensure the ws-policy/ws-securitypolicy specification versions are correct.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**WSM-01690: Assertion {0} located by QName {1} is not an instance of type {2}.**

**Cause:** An internal error, probably policy was not deserialized into the correct assertion instance.

**Action:** Consult diagnostic log for details or contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

---

**WSM-01691: Cannot construct policy object for policy "{0}" due to underlying exception "{1}".**

**Cause:** Construction of the policy Java object failed for the given policy name.

**Action:** Consult the diagnostic log for details.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WSM-01692: Advertisement failed due to multiple ws-policy specification version specified.**

**Cause:** Multiple ws-policy specification version used to advertise policy.

**Action:** Remove the duplicate ws-policy specification versions and try again.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**WSM-01693: Advertisement failed due to multiple wssecurity-policy specification version specified.**

**Cause:** Multiple ws-securitypolicy specification version used to advertise policy.

**Action:** Remove the duplicate ws-securitypolicy specification versions and try again.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**WSM-01751: The name of an assertion property is empty.**

**Cause:** The name of an assertion property was empty.

**Action:** Make sure that you specify a name for all assertion properties.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01752: The data type of the value does not match the data type of property {0}. The expected data type is String.**

**Cause:** The datatype of the property value entered was not of type String.

**Action:** Make sure that the data type for the property value is of type String.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01753: The data type of the value does not match the data type of property {0}. The expected data type is Boolean.**

**Cause:** The data type of the property value entered was not of type Boolean.

**Action:** Make sure that the data type for the property value is of type Boolean.

**Level:** 1

---

**Type:** ERROR

**Impact:** Data

**WSM-01754: The data type of the value does not match the data type of property {0}.  
The expected data type is Integer.**

**Cause:** The data type of the property value entered was not of type Integer.

**Action:** Make sure that the data type for the property value is of type Integer.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01755: An empty value is specified for property {0}.**

**Cause:** An empty value was specified for a property that has a data type of type Password.

**Action:** Specify a value for all properties that have a data type of type Password.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01756: The "Property Set Name" field is empty.**

**Cause:** The Property Set Name field in one of the assertions was empty.

**Action:** Make sure that you specify a name for all assertion property sets.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01757: The name attribute for the "Config" element is empty.**

**Cause:** The name for the Config element was empty.

**Action:** Make sure that a name is specified for the Config element.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01758: The assertion name is empty.**

**Cause:** The assertion name was empty.

**Action:** Make sure that the assertion name is specified.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01759: The policy ID is empty.**

**Cause:** The policy ID was empty.

**Action:** Make sure that the policy ID is specified.

**Level:** 1

---

**Type:** ERROR

**Impact:** Data

**WSM-01760: The policy name is empty.**

**Cause:** The policy name was empty.

**Action:** Make sure that the policy name is specified.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01761: Specifying a policy ID for a child policy is not permitted : {0}.**

**Cause:** Policy ID must not be specified for child policies.

**Action:** Remove the policy ID of the child policy.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Data

**WSM-01762: Specifying a policy name for a child policy is not permitted : {0}.**

**Cause:** Policy name must not be specified for child policies.

**Action:** Remove the policy name of the child policy.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Data

**WSM-01763: The value specified for the policy attachTo attribute {0}, does not match any of the supported values.**

**Cause:** The value specified for the policy attachTo attribute did not match any of the supported values.

**Action:** Specify a valid value for the attachTo attribute. Consult the Oracle documentation for the supported values.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01764: The value specified for the policy category {0} does not match any of the supported values.**

**Cause:** The value specified for policy category attribute did not match any of the supported values.

**Action:** Specify a valid value for the category attribute. Consult the Oracle documentation for the supported values.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01765: The data type of the value specified for property {0} is not supported.**

---

**Cause:** The data type specified for the property did not match any of the supported data types.

**Action:** Specify a valid data type for the property. Consult the Oracle documentation for the supported data types.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01766: The assertion template ID cannot be empty.**

**Cause:** The assertion template ID was empty.

**Action:** Specify a value for assertion template ID.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01767: The assertion template name cannot be empty.**

**Cause:** The assertion template name was empty.

**Action:** Specify a value for the assertion template name.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01768: The value specified for the assertion template attachTo attribute {0} does not match any of the supported values.**

**Cause:** The value specified for the assertion template attachTo attribute did not match any of the supported values.

**Action:** Specify a valid value for the attachTo attribute. Consult the Oracle documentation for the supported values.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01769: The value specified for the assertion template category {0} does not match any of the supported values.**

**Cause:** The value specified for the assertion template category attribute did not match any of the supported values.

**Action:** Specify a valid value for the category attribute. Consult the Oracle documentation for the supported values.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01770: A value or default value is not specified for property {0}.**

**Cause:** No value or default value was specified for the property.

**Action:** Specify a value or a default value for the property.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01771: Attaching multiple reliable messaging policies is not supported. Only one reliable messaging policy can be attached to a policy subject**

**Cause:** More than one reliable messaging policy was attached to a policy subject.

**Action:** Make sure that only one reliable messaging policy is attached to a policy subject.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01772: Attaching multiple Message Transmission Optimization Mechanism (MTOM) policies is not supported. Only one MTOM policy can be attached to a policy subject.**

**Cause:** More than one MTOM policy was attached to a policy subject.

**Action:** Make sure that only one reliable MTOM is attached to a policy subject.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01773: Attaching multiple WS-Addressing policies is not supported. Only one WS-Addressing policy can be attached to a policy subject.**

**Cause:** The user attached more than one WS-Addressing policy.

**Action:** Make sure that only one reliable WS-Addressing is attached to a policy subject.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01774: The policy "{0}" cannot be attached to policy subject "{1}" having unsupported subject type "{2}".**

**Cause:** A policy was attached to an unsupported policy subject.

**Action:** Make sure that the policy subject supports policy attachment. Consult the Oracle documentation for the supported values.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01775: The policy "{0}" cannot be attached to policy subject "{1}" having subject type "{2}" since it may only be used with "{3}".**

**Cause:** An incompatible policy was attached to the policy subject.

**Action:** Make sure that the attached policy is compatible with the policy subject.

**Level:** 1

**Type:** ERROR



---

**Impact:** Data

**WSM-01776: The policy reference "{0}" is invalid.**

**Cause:** The policy reference was invalid because the policy did not exist.

**Action:** Make sure that the referenced policy exists in the policy store.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01777: Attaching multiple authorization security policies is not supported.**

**Only one authorization security policy can be attached to a policy subject.**

**Cause:** More than one authorization security policy was attached to a policy subject.

**Action:** Make sure that only one authorization security policy is attached to a policy subject.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01778: Attaching multiple authentication security policies is not supported.**

**Only one authentication security policy can be attached to a policy subject.**

**Cause:** More than one authentication security policy was attached to a policy subject.

**Action:** Make sure that only one authentication security policy is attached to a policy subject.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01779: Attaching multiple message protection security policies is not supported. Only one message protection security policy can be attached to a policy subject.**

**Cause:** More than one message protection security policy was attached to a policy subject.

**Action:** Make sure that only one message protection security policy is attached to a policy subject.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01780: The policy reference category and the policy category do not match.**

**Cause:** There was a mismatch between the policy reference category and the policy category.

**Action:** Ensure that the policy reference category matches the policy category.

**Level:** 1

**Type:** ERROR

---

**Impact:** Data

**WSM-01781: Validation failure due to generic error.**

**Cause:** A generic internal error occurred.

**Action:** Consult the diagnostic logs for details.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01782: Policy contains no assertions. A policy must contain at least one assertion.**

**Cause:** The policy did not contain any assertions.

**Action:** Make sure that the policy contains at least one assertion.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01783: Guard does not contain any of the three elements of resource-match, action-match and constraint-match.**

**Cause:** Guard does not contain any of the three elements of resource-match, action-match and constraint-match.

**Action:** Make sure that at least one of three elements of resource-match, action-match and constraint-match is specified with its corresponding value in the Guard element.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01784: Validation not supported for Custom Documents. Only a Policy or PolicySet can be validated.**

**Cause:** Validation is not supported for Custom Documents.

**Action:** Ensure that the document is either a Policy or a PolicySet.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-01785: Signing or encryption of the soap fault is not supported.**

**Cause:** The soap fault is to be signed or encrypted.

**Action:** Make sure that the soap fault is not to be signed or encrypted.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01801: The type of resources expression is empty or missing.**

**Cause:** The value specified for the appliesTo attribute was empty.

**Action:** Specify a valid non-empty value for the appliesTo attribute.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01802: The type of resources expression "{0}" is not supported.**

**Cause:** The value specified for the appliesTo attribute was invalid.

**Action:** Specify a valid value for the appliesTo attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01811: The attachment expression is empty or missing. A non-empty expression with a function is expected.**

**Cause:** The value specified for the attachTo attribute was empty.

**Action:** Specify a valid, non-empty value for the attachTo attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01812: The function "{2}" at index {1} in attachment expression "{0}" is empty. A function requires a non-empty value.**

**Cause:** The argument for a function was missing or empty.

**Action:** Specify a valid, non-empty value for the function argument.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01813: The function "{2}" at index {1} in attachment expression "{0}" duplicates a previous function. A function may only appear once in an expression.**

**Cause:** A function appeared more than once in an attachment expression.

**Action:** Remove the duplicated function from the expression.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01814: The function "{2}" is not expected at index {1} in attachment expression "{0}". An operator is expected at this point.**

**Cause:** A function was found in an attachment expression where an operator was expected.

**Action:** Specify the "and" operator between each function.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01815: A function is expected at index {1} in attachment expression "{0}".**

---

**Cause:** The attachment expression ended with an operator.

**Action:** Remove the dangling operator or add the missing function.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01816: The operator "{2}" at index {1} in attachment expression "{0}" is not supported. "and" is the only supported operator.**

**Cause:** An unrecognized operator was found in an attachment expression.

**Action:** Specify the "and" operator between each function.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01817: The text "{2}" at index {1} in attachment expression "{0}" is not expected. A function is expected at this point.**

**Cause:** An unrecognized block of text was found in an attachment expression where a function was expected.

**Action:** Specify a valid function in the expression.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01818: The text "{2}" at index {1} in attachment expression "{0}" is unrecognized. The operator "and" is expected at this point.**

**Cause:** An unrecognized block of text was found in an attachment expression where an operator was expected.

**Action:** Specify the "and" operator between each function.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01821: The function "{0}" in attachment expression "{1}" is incompatible with "{2}" type of resources.**

**Cause:** A function was found in an attachment expression that is not usable with the type of resource.

**Action:** Specify a function that is compatible with the associated type of resource.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-01822: The function "{0}" in attachment expression "{1}" is not supported for attachment.**

**Cause:** A function was found in an attachment expression that is not usable for attachment.

**Action:** Specify a function that is compatible with the associated type of resource.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02000: Cannot retrieve assertion template {0}.**

**Cause:** A failure occurred while retrieving the assertion template from the data store.

**Action:** Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02001: Cannot serialize XML to policy attachment.**

**Cause:** The policy attachment XML was not well formed, or the XML did not follow the policy attachment schema.

**Action:** Ensure that the XML is well formed, and the XML follows the policy attachment schema.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02002: Cannot retrieve policies.**

**Cause:** A failure occurred while retrieving policies from the data store.

**Action:** Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02003: Cannot retrieve policy references for resource pattern {0}.**

**Cause:** A failure occurred while retrieving policy references from the data store.

**Action:** Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02004: Cannot search policies for condition {0}.**

**Cause:** A failure occurred while searching for policies in the data store.

**Action:** Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02005: Cannot perform policy compatibility check for policies {0}.**

**Cause:** An internal error was encountered while performing the policy compatibility check.

---

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02006: Cannot add policies {0} to data store.**

**Cause:** A failure occurred while adding policies to the data store.

**Action:** Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02007: Cannot delete assertion templates {0}.**

**Cause:** A failure occurred while deleting assertion templates from the data store.

**Action:** Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02008: Cannot delete policies {0}.**

**Cause:** A failure occurred while deleting policies from the data store.

**Action:** Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02009: Cannot delete all assertion templates from the data store.**

**Cause:** A failure occurred while deleting all assertion templates from the data store.

**Action:** Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02010: Unable to delete all policies from the data store.**

**Cause:** A failure occurred while deleting all policies from the data store.

**Action:** Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02011: Cannot delete assertion template {0}.**

**Cause:** A failure occurred while deleting the specified assertion template from the data store.

---

**Action:** Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02012: Cannot delete policy {0}.**

**Cause:** A failure occurred while deleting the specified policy from the data store.

**Action:** Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02013: Cannot retrieve policy configuration {0}.**

**Cause:** A failure occurred while retrieving the policy configuration.

**Action:** Check the policy configuration, and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02014: The value for the attachTo attribute {0} is not valid.**

**Cause:** The value for the attachTo attribute is not valid.

**Action:** Consult Oracle documentation for the valid values for the attachTo attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02015: Cannot retrieve object(s) due to Java RuntimeException.**

**Cause:** The unexpected RuntimeException was encountered while trying to access data store.

**Action:** Check the log file for possible causes, and retry the operation.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**WSM-02016: Cannot retrieve timestamp for the last data store update.**

**Cause:** A problem occurred while accessing the repository.

**Action:** Examine the logs for the cause of the failure.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**WSM-02044: Cannot save assertion template {0} to data store.**

**Cause:** Another process was trying to update the same assertion template.

---

**Action:** Ensure that no other process is trying to update the same assertion template object and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02045: Cannot delete policy version from data store.**

**Cause:** Failure occurred while deleting policy versions from the data store.

**Action:** Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-02046: Cannot delete assertion template versions from data store.**

**Cause:** Failure occurred while deleting assertion template versions from the data store.

**Action:** Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-02047: Unable to create multiple policies.**

**Cause:** Failure occurred while creating multiple policies

**Action:** Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-02048: Unable to update multiple policies.**

**Cause:** Failure occurred while updating multiple policies.

**Action:** Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-02049: Unable to update the assertion template.**

**Cause:** Failure occurred while updating an assertion template.

**Action:** Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-02050: Unable to set the older version of a policy as the latest version.**

**Cause:** Failure occurred while setting an older version of a policy as the latest version.



---

**Action:** Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-02051: Unable to add resources to policy attachment.**

**Cause:** Failure occurred while trying to add resources to a policy attachment.

**Action:** Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-02052: Unable to remove resources from policy attachment.**

**Cause:** Failure occurred while trying to remove resources from policy attachment.

**Action:** Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-02053: Unable to set the older version of a policy as the latest version.**

**Cause:** Failure occurred while setting an older version of a policy as the latest version.

**Action:** Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-02054: Failure in looking up EJB component {0}.**

**Cause:** Failure occurred in looking up requested component on the application server.

**Action:** Make sure that the right configuration is passed for the EJB lookup and retry the operation.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**WSM-02055: Failure calculating smart digest for policy {0}**

**Cause:** Failure occurred in calculating smart digest when updating or creating policy.

**Action:** You can ignore this message or you can retry the operation. Increase the log levels for more details as to the underlying cause for the smart digest calculation failure.

**Level:** 1

**Type:** WARNING

---

**Impact:** Data

**WSM-02056: Unable to locate the RMI port for communication**

**Cause:** Failure occurred when looking up RMI port for the application server.

**Action:** Confirm that the RMI port settings are correct in the application server configuration and retry the operation.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**WSM-02057: Mismatch in EJB lookup. Expected object type: {0}, Actual object type: {1}.**

**Cause:** Mismatch in expected EJB object type and actual object type.

**Action:** Confirm that the Policy Manager EJB is configured correctly, and its version is compatible with the client.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**WSM-02058: Failure occurred in Policy Manager while seeding policies in data store.**

**Cause:** Failure occurred in Policy Manager while seeding policies in data store.

**Action:** Make sure the correct configuration is passed to Policy Manager for seeding policies.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02059: Version-related operations are not supported for the configured datastore.**

**Cause:** Version-related operations are not supported for the configured datastore.

**Action:** Make sure the datastore used is a database and not file-system based.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02060: EJB lookup failed due to invalid lookup configuration**

**Cause:** Unable to perform EJB lookup.

**Action:** Make sure that valid JNDI name and JNDI properties are supplied for EJB lookups.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02061: Failed to close Initial Context created for EJB lookups**

**Cause:** Unable to close the Java Initial Context.

---

**Action:** Confirm that no other component is using the context and there are no memory leaks.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02062: Unable to retrieve credentials for the specified csf-key {0}**

**Cause:** Credential configuration in the policy accessor configuration file was incorrect.

**Action:** Configure policy with valid CSF key.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-02063: The password credentials cannot be obtained from the Credential Store.**

**Cause:** Failure occurred while querying for credentials from CSF.

**Action:** Check CSF configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-02064: The Java Object Name {0} being created is invalid.**

**Cause:** An error occurred while creating the specified JMX ObjectName.

**Action:** Check the MBean ObjectName being instantiated and retry the operation.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02065: The MBean being registered is not a JMX compliant MBean**

**Cause:** Failed to register MBean.

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02066: Failed to get server context**

**Cause:** Failed to get server initial context.

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

---

**WSM-02067: Cannot register MBean {0}, an MBean with same name already exists on the server**

**Cause:** The MBean being registered already exists on the server.

**Action:** Check the name of the MBean being registered and retry the operation.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02068: Failed to register MBean {0}**

**Cause:** Failed to register MBean.

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02069: Failed to deregister MBean {0}**

**Cause:** Failed to deregister MBean.

**Action:** No action needs to be taken at this time. However, if the server exhibits any erroneous behavior, try restarting the server.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02070: Failed to load updates.xml file**

**Cause:** Failed to load updates.xml file.

**Action:** Make sure that the wsm-seed-policies.jar exists and it corresponds to the latest version and retry the operation.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02071: No entries found in the wsm-seed-policies.jar file**

**Cause:** The wsm-seed-policies.jar file does not contain any entries.

**Action:** Make sure that the wsm-seed-policies.jar file is not corrupted and retry the operation.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02072: Failed to load wsm-seed-policies.jar file**

**Cause:** The wsm-seed-policies.jar file could not be loaded.

**Action:** Make sure that the wsm-seed-policies.jar file exists in the application classpath and retry the operation.

**Level:** 32

---

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02073: Unable to connect to the WSM datastore**

**Cause:** Unable to connect to the WSM datastore.

**Action:** Make sure the datastore settings are correctly set in the wsm-pm application and retry the operation.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02074: Invalid arguments passed to find the difference in shipped documents between versions**

**Cause:** The arguments supplied to find difference between repository versions are invalid.

**Action:** Make sure that the arguments passed comply with the Javadoc requirements and retry the operation.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02075: Cannot unregister MBean {0}. since it does not exist on the server**

**Cause:** The MBean being unregistered does not exists on the sever.

**Action:** Check the name of the MBean being unregistered and retry the operation.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02076: Unable to get an instance of PortableMBeanFactory.**

**Cause:** Could not obtain an instance of PortableMBeanFactory.

**Action:** Check the configuration and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-02077: Unable to get a handle to MBeanServer.**

**Cause:** Could not obtain an instance to MBeanServer

**Action:** Check the configuration and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-02078: Unable to construct MBean ObjectName due to null object name string.**

**Cause:** MBean object name is invalid.

**Action:** Make sure that the supplied object name is not null and retry the lookup.

---

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02079: Failed to connect to Policy Manager instance due to error "{0}".**

**Cause:** Connection to Policy Manager failed.

**Action:** Make sure that the WSM Policy Manager is up and running and retry the operation.

**Level:** 1

**Type:** TRACE

**Impact:** Data

**WSM-02080: Failure to get executor due to underlying error "{0}".**

**Cause:** Failed to get the correct executor to perform requested action.

**Action:** Check the system security configuration and retry the operation.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02081: Failed to login to perform requested action.**

**Cause:** Failed to login to perform requested action.

**Action:** Check the system security configuration and retry the operation.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**WSM-02082: Unsupported callback handler.**

**Cause:** Unsupported callback handler.

**Action:** Check the system security configuration and retry the operation.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**WSM-02083: Invalid security configuration entry name.**

**Cause:** Invalid security configuration entry name.

**Action:** Check the system security configuration and retry the operation.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**WSM-02100: Error parsing the resource from String {0}.**

**Cause:** An XML parsing failure occurred while creating the document from the passed String.

**Action:** Verify that the passed String is a well-formed XML and follows the XML schema for its object type.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02101: Generic Oracle WSM Policy Manager error.**

**Cause:** An internal error occurred during the Policy Manager operation.

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02102: The policy name is missing.**

**Cause:** The policy name was missing.

**Action:** Make sure that the supplied policy has a valid name, and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WSM-02103: The assertion template name is missing.**

**Cause:** The assertion template name was missing.

**Action:** Make sure that the supplied assertion template has a valid name, and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WSM-02104: The assertion template from file {0} cannot be parsed.**

**Cause:** A failure occurred while parsing the assertion template from the file.

**Action:** Check for any syntax errors in the file specified, and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02105: The policy search query is not valid.**

**Cause:** An invalid policy search condition was specified.

**Action:** Check the search query and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WSM-02106: Cannot retrieve policy {0}.**

**Cause:** A failure occurred while retrieving the policy.

**Action:** Retry the operation.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02107: Cannot update policy {0}.**

**Cause:** A failure occurred while updating the policy.

**Action:** Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02108: Cannot retrieve version {0} of policy {1}.**

**Cause:** A failure occurred while retrieving the requested version of the policy.

**Action:** Check the version and policy details and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02109: Cannot retrieve version {0} of assertion template {1}.**

**Cause:** A failure occurred while retrieving the requested version of the specified assertion template.

**Action:** Check the version and assertion template details, and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02111: The configuration name is missing.**

**Cause:** The policy configuration name was missing.

**Action:** Provide a valid name for the policy configuration, and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WSM-02112: The policy attachment name is missing.**

**Cause:** The policy attachment name was missing.

**Action:** Provide a valid policy attachment name, and retry the operation

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WSM-02113: Error in creating the policy attachment {0}.**

**Cause:** A failure occurred while creating the policy attachment.

**Action:** Check the specified values and retry the operation.

**Level:** 1



---

**Type:** ERROR

**Impact:** Data

**WSM-02114: Error in deleting the policy attachment {0}.**

**Cause:** A failure occurred while deleting the policy attachment.

**Action:** Check the specified values and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02115: Error in updating the policy attachment {0}.**

**Cause:** A failure occurred while updating the policy attachment.

**Action:** Check the specified values and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02116: The resource pattern used in the search is empty or contains wildcard characters like %.**

**Cause:** The resource pattern specified in the search was empty or contained wildcard characters such as %.

**Action:** Correct the search criteria and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02117: Cannot delete all policy attachments from the data store.**

**Cause:** A failure occurred when deleting multiple policy attachments from the data store.

**Action:** Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02118: The query service cannot be created.**

**Cause:** A failure occurred while creating the query service.

**Action:** Check the Policy Manager configuration and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-02119: The update service cannot be created.**

**Cause:** A failure occurred while creating the update service.

**Action:** Check the Policy Manager configuration and retry the operation.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**WSM-02120: Unable to connect to the policy access service.**

**Cause:** A connection to the policy access service could not be created.

**Action:** Check the Policy Manager configuration and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-02121: Internal system error, cannot look up credential.**

**Cause:** A failure occurred while looking up credentials due to an internal system configuration error.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**WSM-02122: The protocol is invalid.**

**Cause:** The protocol was invalid.

**Action:** Check Oracle documentation for the supported protocols.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-02123: Cannot access policy-accessor-config.xml file.**

**Cause:** A failure occurred while reading the policy-accessor-config.xml file.

**Action:** Ensure that the file exists.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-02124: Cannot create policy access service.**

**Cause:** The user connecting to the policy access service did not have sufficient privileges.

**Action:** Confirm that the user has rights to connect to the policy access service, and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-02125: Cannot perform policy compatibility check.**

**Cause:** A failure occurred while performing a policy compatibility check.

**Action:** Contact Oracle Support Services.

**Level:** 32

---

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**WSM-02126: Cannot add policy {0} to data store.**

**Cause:** A failure occurred while adding the policy to the data store.

**Action:** Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-02127: Cannot add assertion template {0} to data store.**

**Cause:** A failure occurred while adding the assertion template to the data store.

**Action:** Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-02128: Cannot read WSDL.**

**Cause:** A failure occurred while parsing the WSDL.

**Action:** Confirm that the supplied WSDL follows the WSDL XML schema.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**WSM-02129: Cannot create policy service.**

**Cause:** The user connecting to the policy service did not have sufficient privileges.

**Action:** Confirm that the user has privileges to connect to the policy service, and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-02130: Cannot retrieve policy attachment from data store.**

**Cause:** A failure occurred while retrieving the policy attachment from the data store.

**Action:** Retry the operation.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**WSM-02131: Standard WSDL is provided, but ORAWSDL is required.**

**Cause:** The WSDL did not have the expected Oracle extensions.

**Action:** Retry the operation with WSDL with Oracle Extensions.

**Level:** 1

---

**Type:** WARNING

**Impact:** Data

**WSM-02132: Cannot find service {0} in WSDL.**

**Cause:** The service was not found in the WSDL.

**Action:** Retry the operation with the correct parameters.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**WSM-02133: Cannot find policies in WSDL.**

**Cause:** No policies were found in the WSDL.

**Action:** Confirm that the supplied WSDL contains the correct policies.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**WSM-02134: Cannot access Policy Manager EJB.**

**Cause:** The user connecting to the Policy Manager EJB did not have sufficient privileges.

**Action:** Confirm that the user has privileges to connect to the Policy Manager EJB, and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02135: Insufficient privileges for accessing the Policy Manager interface.**

**Cause:** Caller's privileges for accessing the Policy Manager EJB were insufficient.

**Action:** Examine underlying errors for root cause.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02136: Bulk update operations are not supported for file-based data stores.**

**Cause:** The bulk update operation failed because the data store does not support transactions.

**Action:** Use a repository that supports transactions, for example, a database repository.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02138: Cannot save policy attachment {0} to data store.**

**Cause:** A concurrent update failure occurred while saving the policy attachment in the data store.

---

**Action:** Make sure no other process is trying to update the same policy attachment object and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02139: Cannot save policy {0} to data store.**

**Cause:** A concurrent update failure occurred while saving the policy in the data store.

**Action:** Make sure no other process is trying to update the same policy object and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02201: A comparator is required for a search criterion.**

**Cause:** A search comparator was not provided.

**Action:** Supply a comparator.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02202: The comparator "{0}" is not supported for a numeric attribute search criterion.**

**Cause:** The search comparator is not supported for numeric comparisons.

**Action:** Supply a comparator that supports numeric comparisons.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02203: The comparator "{0}" is not supported for a text attribute search criterion.**

**Cause:** The search comparator is not supported for numeric comparisons.

**Action:** Supply a comparator that supports numeric comparisons.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02204: The comparator "UNKNOWN" is not supported for an attribute search criterion.**

**Cause:** The search comparator UNKNOWN is not supported for attribute comparisons.

**Action:** Supply a comparator that supports attribute comparisons.

**Level:** 32

**Type:** INCIDENT\_ERROR

---

**Impact:** Data

**WSM-02205: The search criterion "{0}" cannot be parsed.**

**Cause:** The search criterion was corrupt or used an unrecognized schema.

**Action:** Supply a supported search criterion.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02206: The document name "{0}" is not valid for a search criterion.**

**Cause:** The document name contained illegal characters, such as a slash character.

**Action:** Supply a legal document name.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02207: A document type is required for a search criterion.**

**Cause:** The document type was null, whitespace, or empty.

**Action:** Supply a non-empty document type.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02208: A document URI ends with a path separator.**

**Cause:** The document URI ends with a path separator.

**Action:** Supply a document URI that does not appear to be a path.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02209: A document URI is required for a search criterion.**

**Cause:** The document URI was empty.

**Action:** Supply a non-empty document URI.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02210: An element search criterion cannot be created with the child search expression "{0}" because it contains a non-attribute criterion.**

**Cause:** The search expression contained one or more attribute criteria.

**Action:** Supply an expression containing only attribute criteria.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

---

**WSM-02211: A number is required for a search criterion.**

**Cause:** A number was not provided.

**Action:** Supply a valid number.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02212: The search expression "{0}" contains invalid operator "{1}".**

**Cause:** The search expression contained an invalid operator.

**Action:** Supply an expression with a valid operator.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02213: A search operator is required for a search expression.**

**Cause:** A search operator was not provided.

**Action:** Supply a valid operator.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02214: The operator "UNKNOWN" is not supported for a search expression.**

**Cause:** The search operator UNKNOWN is not supported for expressions.

**Action:** Supply a valid operator.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02215: A QName is required for a search criterion.**

**Cause:** A search QName was not provided.

**Action:** Supply a valid Name.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02216: The search expression "{0}" contains a close parenthesis at index {1} without a matching open parenthesis.**

**Cause:** The search expression contained an unbalanced parenthesis.

**Action:** Supply an expression with matching open and close parenthesis.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

---

**WSM-02217: The search expression "{0}" contains an open parenthesis without a matching close parenthesis.**

**Cause:** The search expression contained an unclosed parenthesis.

**Action:** Supply an expression with matching open and close parenthesis.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02218: The comparator "{0}" is not supported for text content search criterion.**

**Cause:** The search comparator is not supported for text comparisons.

**Action:** Supply a comparator that supports text comparisons.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02251: Subject metadata is required to build a PolicySet.**

**Cause:** Subject metadata was not provided for building a PolicySet.

**Action:** Supply valid subject metadata.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02252: A repository accessor is required to build a PolicySet.**

**Cause:** A repository accessor was not provided for building a PolicySet.

**Action:** Supply suitable repository accessor instance.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02253: The resource pattern for the subject "{0}" is invalid. External attachments and policy usage tracking is disabled.**

**Cause:** An invalid resource pattern was provided with the metadata for a policy subject.

**Action:** Contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02261: A map of terms is required when creating a ResourcePattern.**

**Cause:** A null map of terms was provided to the ResourcePattern constructor.

**Action:** Supply a valid map of terms when creating a resource pattern.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic



---

**WSM-02262: A "{0}" term is required when creating a ResourcePattern.**

**Cause:** The required term was not provided to the ResourcePattern constructor.

**Action:** Supply a valid map of terms when creating a resource pattern.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02263: A map of terms is required when creating a ResourcePattern.**

**Cause:** A null String was provided to the ResourcePattern constructor.

**Action:** Supply a valid resource pattern String.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WSM-02264: "{0}" is not a recognized resource pattern.**

**Cause:** The supplied String did not match one of the known resource pattern formats.

**Action:** Supply a valid resource pattern String.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02301: Failed to get document from URL "{0}" due to underlying error "{1}"**

**Cause:** URL resource was not loaded.

**Action:** Check that the passed URL is valid and retry the operation.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02302: Failed to access document repository due to underlying error "{0}"**

**Cause:** The Document Repository could not be accessed.

**Action:** Check the configuration for accessing Document Repository and retry the operation.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Requests/Responses

**WSM-02303: The passed search expression "{0}" could not be parsed due to underlying error "{1}"**

**Cause:** Failure in parsing the passed search expression.

**Action:** Check that the passed search expression is valid and retry the operation.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

---

**WSM-02304: The passed expressionMap "{0}" contains search expression which cannot be parsed due to underlying error "{1}".**

**Cause:** Failure in parsing the search expression contained in the passed expressionMap.

**Action:** Check that the passed expressionMap contains valid search expression and retry the operation.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02310: Failed to retrieve requested documents due to underlying error "{0}". The operation will be retried.**

**Cause:** Failure in retrieving the requested documents.

**Action:** No corrective action needed as this time, the operation will be retried.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02311: Failed to retrieve requested documents due to underlying error "{0}".**

**Cause:** Failure in retrieving the requested documents.

**Action:** Check that the document repository is reachable and is correctly configured.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02312: Failed to store resource usage information to underlying error "{0}". The operation will be retried.**

**Cause:** Failure in persisting usage information.

**Action:** No corrective action needed as this time, the operation will be retried..

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02313: Failed to store resource usage information to underlying error "{0}".**

**Cause:** Failure in persisting usage information.

**Action:** Check that the document repository is reachable and is correctly configured.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02351: A invalid bean class "{0}" is provided.**

**Cause:** A invalid bean class was provided to the bean factory to create a bean instance.

**Action:** Provide a valid bean class.

---

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02352: A invalid bean type "{0}" is provided.**

**Cause:** A invalid bean type was provided to the bean factory to create a bean instance.

**Action:** Provide a valid bean type.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02353: Unable to get the Action Executor.**

**Cause:** A failure occurred while getting Action Executor.

**Action:** Check that valid subject is passed to get the Action Executor

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-02354: Unexpected exception "{0}" caught when privileged method is called.**

**Cause:** Unexpected exception caught on calling a privileged code.

**Action:** Check the underlying signature of method called in privileged code

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-02355: A subject passed to BeanFactory is null.**

**Cause:** The subject passed to the bean factory is null.

**Action:** Ensure that the subject is not null.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**WSM-02356: Cannot cast to "{0}" object.**

**Cause:** Unable to cast the object. It may be using older implementation.

**Action:** Verify that the older implementation is not being used.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-02359: Lookup attempted for unsupported Server.**

**Cause:** A lookup is attempted for unsupported Server.

**Action:** Check the system configurations to ensure correct server is running.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**WSM-02360: The path to the jar file "{0}" is either invalid or the jar file is corrupt.**

**Cause:** The path provided to the jar file is either incorrect or the jar file is corrupt

**Action:** Provide the path to a valid jar file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-02401: Failed to store policy usage information to the repository because document criterion "{1}" is not a valid document name for the repository due to underlying error "{0}".**

**Cause:** The document criterion contains invalid document name for the repository.

**Action:** Choose a valid document name and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02402: Expression "{0}" does not identify specific documents.**

**Cause:** An invalid search expression was specified.

**Action:** Check the search expression and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02403: Failed to store policy usage information to the repository because the expressionMap "{0}" has document criterion with invalid document name for the repository resulting in underlying error "{1}".**

**Cause:** The search expression within the map has document criterion having invalid document name for the repository.

**Action:** Choose a valid document name and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02451: Document cannot be deleted from repository due to underlying error "{0}".**

**Cause:** Failure in deleting requested document.

**Action:** Check that the document exists in the repository

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

---

**WSM-02452: Document criterion "{0}" is invalid for the requested operation due to underlying error "{0}".**

**Cause:** Document criteria is invalid for the requested operation.

**Action:** Check that the document criterion is valid for the repository.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02453: Failed to delete the document with version "{1}" and criterion "{0}" due to underlying error "{2}".**

**Cause:** Failure in deleting the specified version of the document.

**Action:** Check that the document with the specified version exists in repository.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02454: The search expression "{0}" does not identify a unique document.**

**Cause:** The search expression do not identify unique document.

**Action:** Supply an expression which identifies unique document.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02455: Document version cannot be promoted to tip due to underlying error "{0}".**

**Cause:** Failure in promoting the requested document.

**Action:** Check that the document exists in the repository.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02456: A retrieval flag cannot be parsed into a number due to underlying error "{0}".**

**Cause:** Failure in parsing flags for document retrieval operation.

**Action:** Check that the value specified for the flags are valid.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02457: Document retrieval failed due to underlying error "{0}".**

**Cause:** Failure in retrieving documents due to invalid document criteria.

**Action:** Check that the value specified for the document criteria are valid.

**Level:** 32

**Type:** INCIDENT\_ERROR

---

**Impact:** Data

**WSM-02458: Document "{0}" cannot be overwritten as it does not exist in the repository.**

**Cause:** Failure in write operation using WRITE\_EXISTING mode since document do not exist in repository.

**Action:** Define a new search criterion.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02459: Document "{0}" cannot be created as already exists in the repository.**

**Cause:** Failure in write operation using WRITE\_NEW mode since document exists in repository.

**Action:** Define a new search criterion.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02460: Unable to write invalid document due to underlying error "{0}".**

**Cause:** URI for the document is invalid for the write operation.

**Action:** Check that the document URI is valid for the repository

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02461: A document without a naming attribute cannot be written.**

**Cause:** Document name is not specified at time of document creation.

**Action:** Please specify a valid document name for the document creation.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02462: The session state is invalid due to underlying error "{0}".**

**Cause:** Session state is invalid for the given operation.

**Action:** Retry the operation.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02463: A document transformer cannot be created due to underlying error "{0}".**

**Cause:** The DOM Parser was not configured properly.

**Action:** Consult Java documentation.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WSM-02464: A DOM document cannot be marshalled into XML due to underlying transformation error "{0}".**

**Cause:** Parsing of the document failed.

**Action:** Ensure that the document is in well-formed XML format.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WSM-02465: A DOM document builder cannot be created due to underlying error "{0}".**

**Cause:** The XML Parser was not configured properly.

**Action:** Consult Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-02466: An XML document cannot be unmarshalled into DOM due to underlying parsing error "{0}".**

**Cause:** Parsing of the XML failed.

**Action:** Ensure that the XML is well formed.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-02467: An XML document cannot be unmarshalled into DOM due to underlying I/O error "{0}".**

**Cause:** The system could not open the Input/Output streams.

**Action:** Consult the Java documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**WSM-02468: The document specified in search expression "{0}" resulted in underlying error "{1}".**

**Cause:** The document name specified for the repository is invalid.

**Action:** Please specify a valid document name.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**WSM-02469: Unable to retrieve document due to underlying error "{0}".**

**Cause:** URI for the document is invalid for the retrieve operation.

**Action:** Check that the document URI is valid for the repository

---

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02470: Unable to write document due to invalid Write Mode "{0}".**

**Cause:** Invalid Write Mode specified to write a document.

**Action:** Check that a valid Write Mode is specified to write a document.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02471: The exception "{0}" is caused because invalid document uri is being used.**

**Cause:** URI for any document is invalid.

**Action:** Check that all the document URI used are valid for the repository

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02551: Unable to retrieve document due to underlying error "{0}".**

**Cause:** URI for the jar is invalid for the retrieve operation.

**Action:** Check that the jar URI is valid.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02552: Unable to load seed policies jar file**

**Cause:** Inability to load seed policies jar either automatically or by a provided path

**Action:** Check that the path to the jar file is correct

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-02553: Unable to load updates.xml from the seed policy jar**

**Cause:** There is some problem while loading updates.xml from the seed policies jar

**Action:** Make sure a valid seed policies jar is provided containing a valid updates.xml file

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-03001: Oracle WSM Monitor internal error {0}**

**Cause:** An unexpected error occurred while monitoring Oracle WSM Agent.



---

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**WSM-03002: Failure initializing Oracle WSM Monitor, {0} is null.**

**Cause:** Creation of one or more DMS Event sensors failed while initializing Oracle WSM Monitor.

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-03003: The topology node value {0} is not valid.**

**Cause:** The topology node value passed from the security interceptor to Oracle WSM Agent was invalid.

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-03004: The parameter {0} is not valid.**

**Cause:** The parameter was either null or invalid.

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-04501: generic error in accessing the data store**

**Cause:** An internal error occurred while accessing the MDS data store.

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-04502: The name of the resource is empty.**

**Cause:** The name of the resource to be updated or retrieved was empty.

**Action:** Assign a name to the resource being processed.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**WSM-04503: resource {0} does not exist in the data store**

**Cause:** The requested resource was not found in the data store.

**Action:** Check the search criteria and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-04504: resource {0} cannot be updated**

**Cause:** The resource could not be updated.

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-04505: resource {0} cannot be created**

**Cause:** The specified name has already been assigned to another resource.

**Action:** Specify a unique name, and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-04506: cannot create resource {0}**

**Cause:** The resource could not be saved to the data store.

**Action:** Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-04507: cannot delete resource {0}**

**Cause:** The resource could not be deleted from the data store.

**Action:** Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-04508: cannot update resource {0}**

**Cause:** The resource could not be updated to the data store.

**Action:** Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

---

**WSM-04509: cannot initialize the connection to the data store**

**Cause:** Connecting to the data store failed.

**Action:** Check the data store credentials, and retry the operation. Ensure that WSM-PM is installed, deployed correctly and running at <http://<host:port>/wsm-pm/> and by clicking the Validator link. Also, ensure that the database to which WSM-PM connects is up and the mds-owsm data source is configured properly and targeted to the right server.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-04510: The version {0} for resource {1} cannot be found.**

**Cause:** The requested version for the specified resource was not found.

**Action:** Check the search criteria, and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-04511: cannot perform simultaneous deletes**

**Cause:** Deleting multiple resources simultaneously from the data store failed.

**Action:** Check supplied data, and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-04512: internal data store error**

**Cause:** A generic data store exception occurred.

**Action:** Check the data store credentials that were provided and retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-04513: cannot commit changes to the repository**

**Cause:** A failure occurred while finalizing changes to the data store.

**Action:** Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-04514: The version {0} for resource {1} cannot be deleted.**

**Cause:** Deleting the specified version(s) of the resource failed.

**Action:** Check the supplied values, and retry the operation.

**Level:** 1

---

**Type:** ERROR

**Impact:** Data

**WSM-04515: Auditing is disabled for MDS operations.**

**Cause:** An internal error occurred; failed to initialize the auditor.

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-04516: The version of the passed resource is invalid.**

**Cause:** The requested version of the resource was invalid.

**Action:** The version number must be a positive integer.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WSM-04517: cannot update resource {0}**

**Cause:** The resource to be updated was concurrently being updated by another process.

**Action:** Make sure no other process is attempting to change the resource being updated, and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WSM-04518: document name is invalid**

**Cause:** The document name was invalid.

**Action:** Specify a name for the document that follows the document naming conventions. Refer to Oracle documentation for the naming rules.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WSM-04519: Unable to create document.**

**Cause:** The repository permissions were read-only. Creation of a new document requires write permissions.

**Action:** Reconfigure the repository to have write permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WSM-04520: The repository timestamp is invalid.**

**Cause:** The repository timestamp was invalid or missing.

**Action:** Retry the operation. If the problem persists, consult the diagnostic logs.

---

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Programmatic

**WSM-04521: Resource to be deleted does not exist in datastore.**

**Cause:** The resource could not be deleted since it does not exist in the data store.

**Action:** You don't need to take any action, the resource is not present in the datastore.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-04601: A JDBC URL is required to connect to a database-based MDS repository.**

**Cause:** A null or empty JDBC URL was provided when attempting to create an MDS instance for a database-based repository.

**Action:** Provide a valid JDBC URL and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WSM-04602: A password is required to connect to a database-based MDS repository.**

**Cause:** A null or empty password was provided when attempting to create an MDS instance for a database-based repository.

**Action:** Provide a valid password and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WSM-04603: A username is required to connect to a database-based MDS repository.**

**Cause:** A null or empty username was provided when attempting to create an MDS instance for a database-based repository.

**Action:** Provide a valid username and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WSM-04606: One or more directories are required to connect to a file-based MDS repository.**

**Cause:** A path was not provided when attempting to create an MDS instance for a file-based repository.

**Action:** Provide a valid directory and try again.

**Level:** 1

**Type:** ERROR

---

**Impact:** Programmatic

**WSM-04611: An MDS session cannot be created due to underlying error "{0}".**

**Cause:** MDS encountered an unexpected condition.

**Action:** Follow the recommendations for the underlying exception.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-04641: The operation "{0}" for document "{1}" cannot be performed on a closed session.**

**Cause:** A operation was requested on a session that has already been closed.

**Action:** Create a new repository session and perform the operation again.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Programmatic

**WSM-04642: The operation "{0}" for document "{1}" cannot be performed on a read-only session.**

**Cause:** See error message.

**Action:** Create a new session on a writable repository and try again.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**WSM-04643: The operation "{0}" cannot be performed on virtual document "{1}".**

**Cause:** A write operation was requested on a virtual document.

**Action:** Choose a different document name and try again.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**WSM-04651: The search criterion "{0}" does not identify a specific document to be created.**

**Cause:** The supplied criterion does not have the correct type.

**Action:** Supply a NAME search criterion.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WSM-04652: The document "{0}" already exists in the repository.**

**Cause:** The document already exists in the repository.

**Action:** Choose a different name for the document to create or perform an update instead.

**Level:** 1

---

**Type:** ERROR

**Impact:** Data

**WSM-04653: The document "{0}" cannot be created in a read-only repository.**

**Cause:** The repository is read-only.

**Action:** Reconfigure the repository to support writes and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-04654: The name "{0}" is invalid for creating a document due to underlying reason "{2}".**

**Cause:** The document name is invalid for the repository.

**Action:** Choose a valid name and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-04655: Repository information cannot be marshalled due to underlying parser error "{2}"**

**Cause:** The system does not support the required DOM document builder configuration.

**Action:** Correct underlying error or contact Oracle Support Services for assistance.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Other

**WSM-04656: Repository information cannot be marshalled due to underlying marshalling error "{2}"**

**Cause:** The repository information object could not be marshalled into a DOM document.

**Action:** Correct underlying error or contact Oracle Support Services for assistance.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-04657: The document "{0}" cannot be created in a session spanning multiple stores due to underlying error "{2}".**

**Cause:** The document to be created belongs in a store that is different from other write operations in the session.

**Action:** Create the document in a different session.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-04661: The document "{0}" cannot be deleted in a read-only repository.**

---

**Cause:** The repository is read-only.

**Action:** Reconfigure the repository to support writes and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-04662: The name "{0}" is invalid for deleting a document due to underlying reason "{2}".**

**Cause:** The document name is invalid for the repository.

**Action:** Choose a valid name and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-04663: The document "{0}" cannot be deleted in a session spanning multiple stores due to underlying error "{2}".**

**Cause:** The document to be created belongs in a store that is different from other write operations in the session.

**Action:** Delete the document in a different session.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-04664: Version {1} to {3} of document "{0}" cannot be deleted.**

**Cause:** The repository does not support deletion of individual versions of a document.

**Action:** Ignore the document version or delete the entire document.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-04671: A concurrent write prevented the document "{0}" from being written due to underlying error "{2}".**

**Cause:** A document in this session was modified by another session.

**Action:** Retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-04672: The document "{0}" cannot be written to repository due to underlying error "{2}".**

**Cause:** An I/O error occurred while writing to repository.

**Action:** Correct the underlying problem and retry.

**Level:** 1



---

**Type:** ERROR

**Impact:** Data

**WSM-04673: The session cannot be committed due to underlying error "{2}".**

**Cause:** The resource could not be deleted since it does not exist in the data store.

**Action:** You don't need to take any action, the resource is not present in the datastore.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-04674: The document "{0}" cannot be validated due to underlying error "{2}".**

**Cause:** Validation failed for a metadata object written in the session.

**Action:** Correct the underlying problem and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-04681: The document "{0}" to be modified was not found in the repository due to underlying error "{2}".**

**Cause:** The document was not found in the repository.

**Action:** Create the document instead of modifying it.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-04682: The document "{0}" cannot be modified in a session spanning multiple stores due to underlying error "{2}".**

**Cause:** The document to be modified belongs in a store that is different from other write operations in the session.

**Action:** Modify the document in a different session.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-04691: The document "{0}" cannot be found in repository due to underlying error "{2}".**

**Cause:** The document was not found in the repository.

**Action:** Create the document and try again.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Data

**WSM-04692: The name "{0}" is invalid for retrieving a document due to the error "{2}".**

**Cause:** The document name is invalid for the repository.

---

**Action:** Choose a valid name and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-04693: Version information is not available for document "{0}".**

**Cause:** The repository does not support versioning.

**Action:** Configure the repository to support versioning.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-04694: An invalid directory was provided to connect to a file-base MDS repository.**

**Cause:** An invalid directory was provided when attempting to create an MDS instance for a file-based repository.

**Action:** Provide a valid directory and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WSM-04695: The retrieved version of document "{0}" is no longer available.**

**Cause:** A new version of the document was created after it was initially retrieved.

**Action:** Retry the operation to get the latest version of the document.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-04696: The operation "{0}" cannot be performed on a closed session.**

**Cause:** A operation was requested on a session that has already been closed.

**Action:** Create a new repository session and perform the operation again.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Programmatic

**WSM-04697: The operation "{0}" cannot be performed on a read-only session.**

**Cause:** See error message.

**Action:** Create a new session on a writable repository and try again.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**WSM-04698: Versions {1} to {3} of document "{0}" are not deletable due to underlying error "{2}".**

---

**Cause:** An I/O error occurred while trying to delete versions of a document from repository.

**Action:** Correct the underlying problem and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-04699: A write lock is not available to delete versions {1} to {3} of document "{0}" due to underlying error "{2}".**

**Cause:** A write lock could not be obtained to delete versions of a document.

**Action:** Retry the operation.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**WSM-06001: Error obtaining Policy Set.**

**Cause:** Failed to get PolicySet.

**Action:** Check log file for possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-06017: Error converting to the canonical path for the File Policy Resolver.**

**Cause:** An invalid canonical path was passed for the File Policy Resolver.

**Action:** Verify the canonical path passed for the File Policy Resolver and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**WSM-06036: The class cannot be instantiated.**

**Cause:** The system could not instantiate a class.

**Action:** Consult the Java documentation or Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**WSM-06101: The policy set cannot be created for null Service Component Architecture (SCA) node.**

**Cause:** The PolicySet could not be generated for the null Service Component Architecture (SCA) node.

**Action:** Pass a valid SCA node object.

**Level:** 1

**Type:** ERROR

---

**Impact:** Compliance

**WSM-06102: The policy referenced by URI "{0}" could not be retrieved.**

**Cause:** Cannot connect to the policy manager due to credential issue.

**Action:** Verify that credentials are correctly specified, if not using the default principal, and that the principal is authorized to access the policy manager application.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**WSM-06103: No configuration has been specified for the Policy Accessor.**

**Cause:** The Policy Accessor object could not be initialized because it is not correctly configured.

**Action:** Call the init method to initialize the Policy Accessor object before invoking this method.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-06104: The protocol specified for Policy Accessor is not supported.**

**Cause:** A policy access protocol was specified that was invalid for this environment.

**Action:** Change protocol to one that is supported by the environment. For J2EE environments, the supported protocols are "local" and "remote"; for J2SE environments, the supported protocols are "classpath", "local", and "remote".

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**WSM-06105: The duplicate policy references are found in the same Service Component Architecture (SCA) binding node.**

**Cause:** The same policy has been attached multiple times and so duplicate policy references were found in the same Service Component Architecture (SCA) binding node.

**Action:** Remove the duplicate policy references from the SCA binding node by attaching each policy only once.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**WSM-06106: The policy reference URI cannot be empty.**

**Cause:** Empty policy references were found in the Service Component Architecture (SCA) node.

**Action:** Verify the Service Component Architecture (SCA) node and make sure the policy references specify a valid value and the referenced policies exist in the repository.

---

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**WSM-06107: The node that is expected is <binding.ws> or <component>. The node {0} passed is not a supported node.**

**Cause:** An unsupported Service Component Architecture (SCA) node was found.

**Action:** Specify a supported SCA node. Consult Oracle documentation for further details

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**WSM-06108: Error initializing the Oracle WSM Policy Resolver because incorrect configuration is passed**

**Cause:** The Policy Resolver did not get created. This could be due to the wrong configuration being passed.

**Action:** Verify the configuration passed for creating the Policy Resolver. Verify that the correct Policy Accessor protocol is passed.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-06109: Cannot retrieve policies.**

**Cause:** The policies were not retrieved. This may be due to incorrect policy references in the Service Component Architecture (SCA) node.

**Action:** Verify that the policy references are referring to policies that exist in the repository. Also, ensure that the data store is seeded with policies.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-06110: The MetaData Store (MDS) home cannot be null.**

**Cause:** The Policy Repository was not valid because MDS Home is set to null.

**Action:** Check the mds.home.module property for the correct value for MDS Home.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-06111: The policy name cannot be null.**

**Cause:** The policy name passed was null or empty.

**Action:** Verify that the policy name is not an empty string, and verify that a null policy name is not being passed.

**Level:** 1

**Type:** ERROR

---

**Impact:** Compliance

**WSM-06112: Policies are not supported for a node of type:{0}.**

**Cause:** Policies cannot be retrieved for unsupported Service Component Architecture (SCA) nodes.

**Action:** Verify that a supported SCA node is provided for retrieving the policy.

**Level:** 1

**Type:** WARNING

**Impact:** Compliance

**WSM-06113: The configuration name cannot be null or empty.**

**Cause:** The configuration file was either empty or did not exist.

**Action:** Verify that the configuration file exists and contains policy references to retrieve policies from the Policy Repository.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-06114: The home directory for the File Policy Resolver cannot be null.**

**Cause:** The home directory for File Policy Resolver was null.

**Action:** Verify that a valid home directory is passed for the File Policy Resolver.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**WSM-06115: The path for the File Policy Resolver does not exist.**

**Cause:** The path for File Policy Resolver did not exist.

**Action:** Ensure that a valid path is passed for File Policy Resolver.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**WSM-06116: The path for the File Policy Resolver is not a directory.**

**Cause:** An invalid directory name was passed for the File Policy Resolver.

**Action:** Verify that a valid directory name is passed for the File Policy Resolver.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**WSM-06118: The resource name for the File Policy Resolver cannot be null.**

**Cause:** The resource name for the File Policy Resolver is null.

**Action:** Verify that a valid resource name is passed for the File Policy Resolver.

**Level:** 1

**Type:** ERROR

---

**Impact:** Files

**WSM-06119: The file {0} for the File Policy Resolver does not exist under {1}.**

**Cause:** The file did not exist.

**Action:** Verify that the file exists at the specified location.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**WSM-06120: The resource name for the File Policy Resolver cannot be null.**

**Cause:** The resource name for the File Policy Resolver was null.

**Action:** Ensure that a non-null resource name is passed for the File Policy Resolver.

**Level:** 1

**Type:** ERROR

**Impact:** Files

**WSM-06121: No policy is found for the policy reference: {0}.**

**Cause:** No policy was found for the specified policy reference.

**Action:** Verify that the policy exists in the repository for the given policy reference, and that the correct policy reference is passed.

**Level:** 1

**Type:** ERROR

**Impact:** Data

**WSM-06122: Error retrieving policies.**

**Cause:** An unexpected error occurred while retrieving the policies from the Policy Manager.

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Data

**WSM-06123: Error initializing internally the File Policy Resolver: {0} {1}**

**Cause:** An unexpected error occurred while initializing the File Policy Resolver.

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Security

**WSM-06124: Error initializing the Oracle WSM Policy Manager Policy Resolver : {0} {1}.**

---

**Cause:** An unexpected error occurred while initializing the Policy Manager Policy Resolver. The Policy Manager Policy Resolver was not able to find the property named mds.config

**Action:** Verify that the property mds.config exists and is referencing a valid property file.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**WSM-06125: Error in the XPath expression {0}.**

**Cause:** The XPath Expression for the policy reference for the given Service Component Architecture (SCA) node was invalid.

**Action:** Verify the XPath for the policy reference within the SCA node.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**WSM-06128: Error accessing the PolicySet : {0} : {1}.**

**Cause:** An unexpected error occurred while accessing the PolicySet.

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**WSM-06129: Error parsing the PolicySet : {0} : {1}.**

**Cause:** An unexpected error occurred while parsing the PolicySet.

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**WSM-06130: Error creating the policy parser.**

**Cause:** The Policy Parser did not get created.

**Action:** Check the configuration for the Policy Parser.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-06132: Error creating a connection to Oracle WSM Policy Manager.**

**Cause:** A failure occurred while connecting to the Policy Manager.

**Action:** Ensure that the Policy Manager is up and running. Ensure that WSM-PM is installed, deployed correctly and running at `http://<host:port>/wsm-pm/` and by clicking the Validator link. Also, ensure that the database to which WSM-PM



---

connects is up and the mds-owsm data source is configured properly and targeted to the right server.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-06133: Error connecting to Oracle WSM Policy Manager.**

**Cause:** A failure occurred while connecting to Policy Manager J2EE Application.

**Action:** Before connecting to a Policy Manager, ensure that the Policy Manager is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-06134: The class cannot be found.**

**Cause:** The class could not be found in the classpath.

**Action:** Verify that the class name is correct in the configuration files and ensure that the class is specified in the classpath variable.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-06135: The class cannot be loaded due to Java 2 security restrictions.**

**Cause:** Some classes were not loaded due to class loading security restrictions.

**Action:** Contact the site administrator or Java documentation to ensure that the classes have the necessary Java2 security permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-06137: The "mds" policy access protocol is deprecated - use "local" instead.**

**Cause:** A deprecated Policy Accessor Protocol was specified.

**Action:** Update the configuration to use the standard protocol name.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**WSM-06138: The "owsm" policy access protocol is deprecated - use "remote" instead.**

**Cause:** A deprecated Policy Accessor protocol was specified.

**Action:** Update the configuration to use the standard protocol name.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**WSM-06139: Error closing a stream**

---

**Cause:** Failure occurred in closing the stream while parsing the configuration file or the policy in the FILE protocol.

**Action:** Verify that the correct configuration file or policy name is provided.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**WSM-06140: Failure finding policy {0} in the classpath roots path {1}.**

**Cause:** The configured roots are invalid.

**Action:** Correct the classpath roots to point to the correct locations.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**WSM-06141: Error initializing Policy Resolver.**

**Cause:** The Policy Resolver was not initialized.

**Action:** Invoke the init method to initialize the Policy Resolver before executing this method.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-06142: Unable to retrieve policy store timestamp.**

**Cause:** The Policy Resolver could not connect to Policy Manager to retrieve the policy store timestamp.

**Action:** Check the MDS configuration file.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**WSM-06143: The validation check in the policy "{0}" failed.**

**Cause:** An error occurred while validating the policy.

**Action:** Ensure that the policy is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-06144: Null policy subject value is not allowed from JEE application.**

**Cause:** The null policy subject value was passed from JEE application.

**Action:** Ensure that a valid policy subject is passed from the JEE application.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

---

**WSM-06145: Internal system error, cannot look up credential**

**Cause:** Failure occurred while looking up credentials.

**Action:** Internal system configuration error. Contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**WSM-06146: Error deleting the attachment entries.**

**Cause:** Failure occurred while deleting the attachment entries.

**Action:** Ensure that a valid list of policy subjects for deactivated lifecycle type is passed

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**WSM-06147: There is mismatch in Policy reference category "{0}" and Policy category "{1}". Policy reference category should match with Policy category.**

**Cause:** Mismatch in expected policy category and fetched policy category.

**Action:** Confirm that the Policy Reference category is correct and that it matches the Policy category.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**WSM-06148: Unable to apply property overrides to Policy**

**Cause:** Unable to apply property overrides to Policy.

**Action:** Make sure the policy model conforms to the Oracle Web service policy model.

**Level:** 1

**Type:** WARNING

**Impact:** Data

**WSM-06149: The policy reference URI is not valid : {0}**

**Cause:** The Policy Reference URI provided was not valid.

**Action:** Verify that the Policy Reference URI is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**WSM-06150: Invalid category : {0} for policy : {1}. Only policies assigned to the security category are supported.**

**Cause:** The Policy category provided was not valid.

**Action:** Verify that the Policy category is correct.

**Level:** 1

---

**Type:** ERROR

**Impact:** Compliance

**WSM-06152: The Policy Cache is not available.**

**Cause:** The Policy Cache is not available.

**Action:** You may need to restart the server.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**WSM-06153: Could not access the Policy Cache.**

**Cause:** Cannot access the Policy Cache.

**Action:** You may need to restart the server.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**WSM-06154: Could not initialize Policy Java Object Cache.**

**Cause:** Cannot initialize the Policy Cache.

**Action:** You may need to restart the server.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**WSM-06155: Could not re-create Policy Java Object Cache.**

**Cause:** Could not re-create the Policy Cache.

**Action:** You may need to restart the server.

**Level:** 1

**Type:** ERROR

**Impact:** Compliance

**WSM-06201: The {0} repository accessor class cannot be accessed due to underlying error "{1}".**

**Cause:** The nullary constructor for the specified accessor is not accessible to the configuration framework.

**Action:** Specify a valid accessor.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-06202: The {0} repository accessor class cannot be initialized due to underlying error "{1}".**

**Cause:** A exception was encountered during evaluation of a static initializer for the specified accessor class.

**Action:** Specify a valid accessor.

---

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-06203: The {0} repository accessor class cannot be used as a repository accessor because it does not implement the {1} interface.**

**Cause:** The specified accessor does not implement the IRepositoryAccessor interface.

**Action:** Specify a valid accessor.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-06204: The {0} repository accessor class cannot be linked due to underlying error "{1}".**

**Cause:** The specified accessor depends on a class whose signature has changed since the accessor was compiled.

**Action:** Update the accessor class or revert to an older version of the dependent class.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-06205: The repository accessor "{0}" cannot be found due to underlying error "{1}".**

**Cause:** The specified accessor was not found.

**Action:** Specify a valid accessor.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-06206: The {0} repository accessor class cannot be instantiated due to underlying error "{1}".**

**Cause:** The specified accessor is an abstract class, an interface, an array class, a primitive type, or void, or the class does not have a nullary constructor.

**Action:** Specify a valid accessor.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-06207: A task scheduler was not available for configuring the {0} repository accessor for context "{1}".**

**Cause:** A task scheduler was not supplied to the configuration framework.

**Action:** Provide a task scheduler to the configuration framework.

**Level:** 1

**Type:** WARNING

---

**Impact:** Configuration

**WSM-06208: Access to the {0} repository accessor class is denied due to underlying error "{1}".**

**Cause:** The configuration framework does not have permission to instantiate the specified accessor.

**Action:** Ensure the necessary permissions are granted to the WSM code base.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-06209: An action executor cannot be created for user "{0}" due to underlying error "{1}".**

**Cause:** The configuration framework did not have permission to get an action executor.

**Action:** Ensure the necessary permissions are granted to the WSM code base.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-06210: An instance of the {2} bean for the local repository at path "{3}" was not available for configuring the {0} repository accessor for context "{1}".**

**Cause:** A bean instance could not be obtained by the configuration framework.

**Action:** Correct underlying problem and wait for configuration refresh.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**WSM-06211: An instance of the {2} bean for the local repository at path "{3}" was provided for configuring the {0} repository accessor for context "{1}".**

**Cause:** A bean instance was obtained by the configuration framework.

**Action:** None.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**WSM-06212: An instance of the {2} bean for a remote repository was not available for configuring the {0} repository accessor for context "{1}".**

**Cause:** A bean instance could not be obtained by the configuration framework.

**Action:** Correct underlying problem and wait for configuration refresh.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**WSM-06213: An instance of the {2} bean for a remote repository was provided for configuring the {0} repository accessor for context "{1}".**

---

**Cause:** A bean instance was obtained by the configuration framework.

**Action:** None.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**WSM-06214: A task scheduler was provided for configuring the {0} repository accessor for context "{1}".**

**Cause:** A task scheduler was supplied to the configuration framework.

**Action:** None.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**WSM-06215: An instance of the {1} bean for the local repository at path "{2}" was not available for configuring the {0} repository accessor for the default context.**

**Cause:** A bean instance could not be obtained by the configuration framework.

**Action:** Correct underlying problem and wait for configuration refresh.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**WSM-06216: An instance of the {1} bean for the local repository at path "{2}" was provided for configuring the {0} repository accessor for the default context.**

**Cause:** A bean instance was obtained by the configuration framework.

**Action:** None.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**WSM-06217: An instance of the {1} bean for a remote repository was not available for configuring the {0} repository accessor for the default context.**

**Cause:** A bean instance could not be obtained by the configuration framework.

**Action:** Correct underlying problem and wait for configuration refresh.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**WSM-06218: An instance of the {1} bean for a remote repository was provided for configuring the {0} repository accessor for the default context.**

**Cause:** A bean instance was obtained by the configuration framework.

**Action:** None.

**Level:** 1

**Type:** NOTIFICATION

---

**Impact:** Configuration

**WSM-06219: A task scheduler was not available for configuring the {0} repository accessor for the default context.**

**Cause:** A task scheduler was not supplied to the configuration framework.

**Action:** Provide a task scheduler to the configuration framework.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**WSM-06220: A task scheduler was provided for configuring the {0} repository accessor for the default context.**

**Cause:** A task scheduler was supplied to the configuration framework.

**Action:** None.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**WSM-06221: The password credentials cannot be obtained from the Credential Store.**

**Cause:** Failure occurred while querying for credentials from CSF.

**Action:** Check CSF configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-06222: The credentials passed to the credentials store are expired.**

**Cause:** The Credentials have expired.

**Action:** Ensure valid credentials are passed

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-06223: The access to the store or credentials is denied.**

**Cause:** The requested access Credentials or Store is denied.

**Action:** Ensure Store is properly initialized and valid credentials are passed

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-06224: Unexpected exception "{0}" caught when privileged method is called.**

**Cause:** Unexpected exception caught on calling a privileged code.

**Action:** Check the underlying signature of method called in privileged code

**Level:** 1

**Type:** ERROR



---

**Impact:** Configuration

**WSM-06225: Unable to retrieve credentials for the specified CSF key {0}.**

**Cause:** Credential configuration in the policy accessor configuration file was incorrect.

**Action:** Configure policy with valid CSF key.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-06301: Subject Metadata is required when registering a listener.**

**Cause:** A null value was provided for the subject metadata.

**Action:** Provide a valid metadata.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WSM-06302: A listener is required for asynchronous notification.**

**Cause:** A null value was provided for asynchronous listener registration.

**Action:** Provide a valid listener.

**Level:** 1

**Type:** ERROR

**Impact:** Programmatic

**WSM-06303: The method "{0}" was not called with required permission "{1}"**

**Cause:** The method was not called with required permission

**Action:** Ensure necessary permissions are granted to the caller before calling the required methods.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-07501: Failure in Oracle WSM Agent processRequest, category={0}, function={1}, application={2}, composite={3}, modelObj={4}, policy={5}, policyVersion={6}, assertionName={7}.**

**Cause:** Processing request failed in the security interceptor while enforcing policy.

**Action:** Check the log file for possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-07502: Failure in Oracle WSM Agent processResponse, category={0}, function={1}, application={2}, composite={3}, modelObj={4}, policy={5}, policyVersion={6}, assertionName={7}.**

**Cause:** Processing response failed in the security interceptor while enforcing policy.

---

**Action:** Check the log file for possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-07503: Failure in Oracle WSM Agent processFault, category= {0}, function={1}, application={2}, composite={3}, modelObj={4}, policy={5}, policyVersion={6}, assertionName={7}.**

**Cause:** Processing fault failed in the security interceptor while enforcing policy.

**Action:** Check the log file for possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-07504: Failure in Oracle WSM Agent processEvent, category= {0}, function={1}, application={2}, composite={3}, modelObj={4}.**

**Cause:** Processing Fabric Lifecycle event failed in security interceptor.

**Action:** Check the log file for possible causes

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-07505: Failure in Oracle WSM Agent initialization, category= {0}, function={1}.**

**Cause:** Agent initialization failed in the security interceptor.

**Action:** Check the log file for possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-07506: Failure in Oracle WSM Agent processFinish, category= {0}, function={1}, application={2}, composite={3}, modelObj={4}.**

**Cause:** Agent finish failed in the security interceptor.

**Action:** Check the log file for possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-07507: Failure in Oracle WSM Agent, category= {0}, function={1}, stage={2} due to RuntimeException.**

**Cause:** An unexpected RuntimeException was encountered while trying to access security interceptor.

**Action:** Check the log file for possible causes and retry the operation.

**Level:** 1

**Type:** WARNING

---

**Impact:** Data

**WSM-07508: Oracle WSM Agent must be initialized before policy enforcement**

**Cause:** Agent not initialized

**Action:** Initialize the Agent with required parameters

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-07509: Oracle WSM Agent must be initialized with valid properties.**

**Following parameters [{0}] are either Empty or null**

**Cause:** Agent not initialized with valid parameters.

**Action:** Initialize the Agent with required parameters

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-07600: Error while copying the message.**

**Cause:** An unexpected error occurred while cloning SOAP or normalized message context.

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Security

**WSM-07601: Failure initializing the WSPolicyExecutor class {0}.**

**Cause:** An unexpected error occurred while initializing the policy engine.

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**WSM-07602: Failure in WS-Policy Execution due to exception.**

**Cause:** Due to an unexpected error, policy execution failed at runtime.

**Action:** Check the log file for possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-07603: Failure in log assertion execution caused by exception.**

**Cause:** File I/O problem or SOAP message access problem occurred.

**Action:** Verify file access permission and the SOAP message.

**Level:** 1

---

**Type:** ERROR

**Impact:** Files

**WSM-07604: Internal error during policy enforcement.**

**Cause:** An unexpected error occurred while enforcing the policy.

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Security

**WSM-07605: The binding.ws port ID {0} is invalid.**

**Cause:** An unexpected error occurred in the Oracle WSM processEvent API.

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**WSM-07606: Policy {0} execution failure.**

**Cause:** Due to an unexpected error, policy execution failed at runtime.

**Action:** Check the log file for possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-07607: Failure in execution of assertion {0} executor class {1}.**

**Cause:** The policy engine failed to execute an assertion.

**Action:** Check the log file for possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-07608: The assertion type is not valid.**

**Cause:** Policy execution failed due to an invalid assertion.

**Action:** Check the assertion type.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-07609: Policy with attachto value of {0} cannot be applied to subject of type {1}.**

**Cause:** The attached policy was incompatible with the subject.

**Action:** Verify that the subject type and the policy's Attachto value are compatible.

**Level:** 1

---

**Type:** ERROR

**Impact:** Security

**WSM-07610: Internal error in policy status audit. One or more of the argument passed is null, result={0}, agentFunction={1}, policy={2}, msgCtx={3}**

**Cause:** An internal error occurred; the enforcement auditor encountered one or more null arguments.

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**WSM-07611: Failure initializing of enforcement auditor: category={0}, function= {1}, topologyNode={2}.**

**Cause:** An internal error occurred; the enforcement auditor initialization failed.

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**WSM-07612: Failure shutting down enforcement auditor.**

**Cause:** An internal error occurred; the enforcement auditor shutdown failed.

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**WSM-07613: Failure enforcing auditing policy.**

**Cause:** An internal error occurred while auditing security or management policy enforcement.

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**WSM-07614: Failure in Agent initialization due to invalid topology node path.**

**Topology node path cannot be null or empty for non-JSE client. category={0}, function={1}, topologyNode={2}, isRunningInJEE={3}**

**Cause:** Oracle WSM Agent initialization failed due to problem creating and initializing DMS instrumentation. An invalid, null, or empty topology node path was encountered for non-JSE client.

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

---

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Configuration

**WSM-07616: Resource name not retrievable from MessageContext. Guard evaluation requires resource name to be present in MessageContext**

**Cause:** Resource name not retrievable from MessageContext. Guard evaluation requires resource name to be present in MessageContext

**Action:** Retry the operation. If the problem persists, contact Oracle Support Services.

**Level:** 32

**Type:** INCIDENT\_ERROR

**Impact:** Security

**WSM-07617: Policy: {0} contains unsupported assertions.**

**Cause:** Policy contains unsupported assertions. Assertions of type http-security are not supported for WLS JAXWS web services.

**Action:** Check the assertion type.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-07618: Failed to execute the assertion "{0}" in the conditional policy. {1}**

**Cause:** Failed to execute the assertion

**Action:** Check exception stack trace for details

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WSM-09001: The audit event definitions cannot be found.**

**Cause:** Component audit event definitions were missing.

**Action:** Check the installation for any missing or corrupted JAR files.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-09002: The audit event definitions file cannot be opened.**

**Cause:** Component audit event definitions could not be opened.

**Action:** Check the installation for any corrupted JAR files, or free up system resources.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-09003: The audit event definitions file cannot be read.**

---

**Cause:** Component's audit event definitions were not readable.

**Action:** Check the installation for any corrupted JAR files.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-09004: Component auditing cannot be initialized.**

**Cause:** The audit framework encountered an error.

**Action:** Check the logs for the possible causes.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WSM-09005: It is not possible to verify that the event is enabled.**

**Cause:** The audit framework encountered an error.

**Action:** Check the logs for the possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**WSM-09007: The event cannot be audited.**

**Cause:** The audit framework encountered an error.

**Action:** Check the logs for the possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**WSM-09008: A URL cannot be created for {0}.**

**Cause:** XML utility encountered an error.

**Action:** Check the logs for the possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**WSM-09009: Failure parsing the XML file**

**Cause:** XML utility encountered an error.

**Action:** Check the logs for the possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**WSM-09010: Error opening and/or closing the stream**

**Cause:** XML utility encountered an error.

**Action:** Check the logs for the possible causes.

---

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**WSM-09011: Error writing the XML file**

**Cause:** XML utility encountered an error.

**Action:** Check the logs for the possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**WSM-09012: Key, {0}, is not found in the resource bundle {1}.**

**Cause:** No key was found in the provided resource bundle.

**Action:** Add the key to the resource bundle and retry the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WSM-09013: Failure shutting down auditing.**

**Cause:** An exception was caught when attempting to shut down the audit framework.

**Action:** Examine the stack trace for any underlying errors.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WSM-09014: Streaming SOAP message attachment is not being logged.**

**Cause:** SOAP message attachment was not logged because it was a streaming attachment.

**Action:** Check the logs for the possible causes.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WSM-09015: Interrupted while checking out object from pool.**

**Cause:** Received interrupt while checking out from pool.

**Action:** Check the logs for the possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WSM-09016: Failure creating transformer using factory {0}.**

**Cause:** Transformer factory failed to create new transformer instance.

**Action:** Check the logs for the possible causes.



---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WSM-09017: Failure checking out a transformer instance.**

**Cause:** Failure checking out a transformer instance.

**Action:** Check the logs for the possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WSM-09018: A ScheduledExecutorService is required when creating a scheduler wrapper.**

**Cause:** A ScheduledExecutorService was not provided when constructing a wrapper.

**Action:** Provide a valid ScheduledExecutorService instance.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WSM-09019: An executor requires a task for scheduling.**

**Cause:** A task was not provided when scheduling a task.

**Action:** Provide a valid task.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WSM-09020: An executor rejected a task due to error "{0}".**

**Cause:** The ScheduledExecutorService refused to schedule a task.

**Action:** Check the logs for the possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WSM-09021: A TimerManager is required when creating a scheduler wrapper.**

**Cause:** A TimerManager was not provided when constructing a wrapper.

**Action:** Provide a valid TimerManager instance.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WSM-09022: A timer cannot schedule a task due to illegal argument error "{0}".**

**Cause:** The scheduling parameters were negative.

**Action:** Provide non-negative values.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WSM-09023: A timer cannot schedule a task due to illegal state error "{0}".**

**Cause:** A task could not be scheduled because the underlying TimerManager was stopped.

**Action:** Schedule the task using a running TimerManager.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WSM-09024: Failure parsing the XML URL when: {0}, from: {1}**

**Cause:** XML utility parseXMLDocument from URL encountered an error.

**Action:** Check the logs for the possible causes.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

---

## WWC-00000 to WWC-59083

**WWC-00000: Normal**

**Cause:** The operation was successful if this message is displayed by itself. Unexpected errors may have occurred if other messages accompany this message.

**Action:** None, if this message is displayed by itself. If other messages accompany this message, review the information in those error messages and take corrective action.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-00001: Message not found: %0.%1**

**Cause:** The message identified by the stated type/name combination was not found in the system message table.

**Action:** This is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-00002: Message ID not found: %0**

**Cause:** The message identified by the given id was not found in the system message table.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-00006: Internal error**

**Cause:** A process encountered a low-level, unexpected condition. This is the generic internal error number for program exceptions.

**Action:** Report this error to Oracle Support Services. Include the error, the attempted operations that led to the error, any unusual circumstances that occurred before receiving this error message, and the complete stack trace produced by this error.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WWC-35002: An attempt was made to access the session context without a valid session.**

**Cause:** User sessions are cleaned up by a background job after a specified time interval. An attempt was made to access a session that did not exist.

**Action:** Close all browser instances to ensure that the session cookie is removed. Re-open the browser and login to the Single Sign-On Server again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-35006: Unable to obtain session information from the cookie.**

**Cause:** An error was encountered while decrypting the Oracle Portal session cookie.

**Action:** Close all browser instances to ensure that the session cookie is removed. Reopen the browser and log in to the Single Sign-On Server again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-35009: An unexpected error occurred**

**Cause:** An unexpected exception occurred. The error message may provide further details.

**Action:** Review the information in the error message and take appropriate corrective action.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-35026: The proxy was not found.**

**Cause:** The parameters specified to locate the proxy were not correct.

**Action:** Check the parameters and provide the correct value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-35038: A proxy with the specified name already exists.**

**Cause:** A proxy with the specified already exists.

**Action:** Either use the existing proxy or specify a different proxy name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWC-35039: The session context cannot be restored because the session is marked as inactive.**

**Cause:** The session cookie contained session reference marked as inactive.

**Action:** Close all browser instances to ensure that the session cookie is removed. Reopen the browser and log in to the Oracle Single Sign-On Server again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-35040: The session context cannot be restored because the cookie value does not match the value stored in the session repository.**

**Cause:** The session cookie was not consistent with the user session in the repository.

**Action:** Close all browser instances to ensure that the session cookie is removed. Re-open the browser and login to the Oracle Single Sign-On Server again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-35041: This API can only be used in non-Web sessions.**

**Cause:** An attempt was made to call an API from a browser session but the API is designated to be called from a SQL session.

**Action:** Check whether the API being called is meant for SQL sessions only. Do not call such APIs from a browser session.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-35042: The Globalization Support language code specified is not valid.**

**Cause:** The language abbreviation specified was invalid.

**Action:** Specify a correct language abbreviation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-35043: The value for the Globalization Support territory specified is not valid.**

**Cause:** The territory specified was invalid.

**Action:** Specify a correct territory.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-38164: An error occurred while displaying the Navigator.**

---

**Cause:** An internal error occurred while generating the list of objects to display in the Navigator. This may be because the requested object has been deleted, or some other internal error.

**Action:** Click the Navigator link at the top of the screen. If that does not solve the problem, restart your browser and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-40018: General invalidation message processing exception: %1**

**Cause:** One of the following occurred: <ol> <li>An error occurred when an invalidation message was sent. This can occur when Oracle Web Cache goes down, or is stopped while Oracle Portal writes an invalidation message to the Oracle Web Cache invalidation port. </li> <li>Some other unexpected exception occurred while processing an invalidation message.</li> </ol>

**Action:** Ensure that Oracle Web Cache is running and the invalidation port is accepting connections.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-40019: Cannot open Oracle Web Cache connection.**

**Cause:** Oracle Portal was not able to send the invalidation message to Oracle Web Cache. This can happen if one or more of the following occurred: <ol> <li>There is a problem in connecting to Oracle Web Cache from the host running the Portal database. An intermittent network issue could have caused this error. Or, the Oracle Web Cache host is not reachable. Verify that the Portal database host can consistently resolve and ping the Oracle Web Cache host. If a firewall exists between the two hosts, make sure that the firewall allows invalidation messages to pass through.</li> <li>Oracle Web Cache was not running. It might have been stopped, or restarted at the time when the invalidation messages were sent by Oracle Portal or providers. Or, Oracle Web Cache might have crashed.</li> <li>Oracle Web Cache invalidation port problems were encountered. This can happen if the Oracle Web Cache invalidation port value used by Oracle Portal is different from the actual Oracle Web Cache invalidation port. Try restarting the Oracle Portal OC4J instance to see if this helps.</li> <li>Another process used the Oracle Web Cache invalidation port before Oracle Web Cache started listening on it.</li> <li>Issues with the Oracle Web Cache invalidation password were encountered. Possibly, the Oracle Web Cache invalidator password value in Oracle Portal is different from the actual Oracle Web Cache invalidator password.</li> </ol>

**Action:** Verify the cause of this behavior and take the appropriate corrective action.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-40064: Error invalidating content: Invalid username/password passed to Oracle Web Cache**

---

**Cause:** The invalidation failed because an incorrect username and/or password was used whilst contacting Oracle Web Cache.

**Action:** Try restarting Oracle Portal's OC4J instance (oc4j\_portal) to see if it helps resolve the issue

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-40065: Error closing HTTP connection: Timeout occurred while communicating with Web Cache to send an invalidation**

**Cause:** The invalidation failed because of a timeout that occurred while Oracle Portal was attempting to read the response from Oracle Web Cache

**Action:** Make sure there is no network issue between Oracle Portal and Oracle Web Cache. Also, check whether the Oracle Web Cache process is not responding.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41031: Unable to connect to the LDAP server.**

**Cause:** The connection parameters required for connecting to the Oracle Internet Directory server were not available.

**Action:** Use the APIs "wwsec\_oid.get\_oid\_host" and "wwsec\_oid.get\_oid\_port" to verify that the preference store values for Oracle Internet Directory parameters exist and are valid. If necessary, run the command-line script ptlasst in MIDTIER mode to configure the Oracle Internet Directory connection parameters: ptlasst.csh -mode MIDTIER -type OID

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41078: The user you are trying to create already exists.**

**Cause:** The user name specified already exists in Oracle Internet Directory.

**Action:** Enter a different user name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41082: Email is a mandatory field. You must specify its value.**

**Cause:** The Email field was not populated.

**Action:** Enter an e-mail address for the user.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41083: The user lacks permission to perform this operation.**

---

**Cause:** An attempt was made to perform an action but the user did not have sufficient privileges.

**Action:** Contact the portal administrator and request that the necessary privileges be granted to perform this task.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41084: A user name is required to proceed to the next step.**

**Cause:** No user name was provided.

**Action:** Enter a valid user name in the Username field.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41094: Unable to save default group - %1**

**Cause:** An error occurred while setting the default group for a given user.

**Action:** Verify that the specified default group exists and the user has the necessary privileges to access this group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41223: Enter a group name**

**Cause:** The group name field was empty.

**Action:** Enter a group name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41227: Unauthorized to perform the operation**

**Cause:** An attempt was made to perform a task on a group, but the user did not have ownership, or the appropriate privileges to perform that task.

**Action:** Contact the portal administrator. Either request to be added to the group's OWNER list, or that the necessary privileges, be granted to perform the task.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41228: Group Not Found**

**Cause:** An attempt was made to access a group but the specified group was not found.

**Action:** Check the name of the group.

**Level:** 1



---

**Type:** ERROR

**Impact:** Other

**WWC-41229: The user did not have permission to perform this operation**

**Cause:** An attempt was made to perform a task, but the user had insufficient privileges to perform the action.

**Action:** Contact the portal administrator. Request the necessary privileges be granted to perform the task.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41239: You are not an owner of this group**

**Cause:** An attempt was made to perform a task on a group but the user did not have ownership, or the privilege to perform that task.

**Action:** Contact the portal administrator. Either request to be added to the group's OWNER list, or that the necessary privileges be granted to perform the task.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41358: This group is not deletable or there is no such group found.**

**Cause:** One of the following occurred: <ol> <li>An attempt was made to delete a special group, such as the DBA or PORTAL\_ADMIN group.</li> <li>The specified group profile does not exist in Oracle Internet Directory.</li> </ol>

**Action:** Check the details of the group to be deleted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41359: The schema owner is not deletable.**

**Cause:** An attempt was made to delete the schema owner but the schema owner may not be deleted.

**Action:** Check the details of the user to be deleted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41401: The group exists already**

**Cause:** An attempt was made to add a group, but a group with the specified name already exists.

**Action:** Either use the existing group, or specify a different group name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWC-41402: There is no such group found**

**Cause:** An attempt was made to access a group that does not exist.

**Action:** Check the name of the group required. If available, use the popup list to specify the group name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41404: The specified manager does not exist.**

**Cause:** The manager specified for a given user did not exist.

**Action:** Check that the manager specified for the given user is correct. If available, use the popup list to specify the manager's name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41405: Already a member of the group.**

**Cause:** An attempt was made to add a user (or group) to a given group but the specified user (or group) is already a member of that group.

**Action:** Check the name of the user (or group) being added.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41406: The specified user does not exist.**

**Cause:** An attempt was made to access a user that does not exist.

**Action:** Check the name of the specified user. If available, then select the user from the list.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41408: There are no accessible objects.**

**Cause:** There are no objects on which the specified privileges have been granted to given user.

**Action:** Verify that the criteria specified is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41409: Invalid value specified.**

**Cause:** An attempt was made to call the API with invalid parameter values.

**Action:** Check the values for the parameters.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WWC-41410: The specified site does not exist.**

**Cause:** An attempt was made to access a site but the specified site ID does not exist.

**Action:** Check the ID of the site specified.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41413: The user ID does not exist.**

**Cause:** An attempt was made to access a user but the specified user ID does not exist.

**Action:** Check the ID of the user specified.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41415: The user does not have permission to perform this operation.**

**Cause:** An attempt was made to perform an operation, but the user did not have sufficient privileges. This error message was displayed in Oracle Portal when viewing pages, or editing page layout or style.

**Action:** Log in to Oracle Portal as a user with permissions to perform the operation. Alternatively, contact the portal administrator to request that the necessary privileges be granted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41417: Unexpected error encountered in %0 (%1)**

**Cause:** An unexpected error was encountered.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41419: Authentication failed. Try again.**

**Cause:** An attempt was made to login with incorrect password or user name details.

**Action:** Login again using a valid user name and password combination. If your password is case-sensitive, enter the correct case for your password.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWC-41426: There is no such user or group found. Enter the name of a valid user or group and try again.**

**Cause:** While creating or editing a page, an invalid user or group name was specified when attempting to set access privileges for the page.

**Action:** Check that the name for the user or group is valid. If necessary, use the popup list to specify the user or group name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41428: Adding the group as a member would result in a circular reference.**

**Cause:** An attempt was made to add a group as a member to itself.

**Action:** Verify that the group being added as a member is different from the group to which it is being added.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41430: You have entered an invalid group name. Group names should not exceed 50 characters.**

**Cause:** An attempt was made to enter a group name but the specified name was invalid.

**Action:** Verify that the specified group name is less than 50 characters in length, or less than 255 bytes in length (for multibyte character set databases).

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41432: The description you have entered exceeds 500 characters. Group descriptions must be 500 characters or less.**

**Cause:** The group description specified was too long

**Action:** Enter a group description that is less than 500 characters in length.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41433: Specify an appropriate database user name. It should be an existing proxy client to %1. The proxy client must not be the Oracle Portal schema itself.**

**Cause:** When editing a user, an attempt was made to assign a database schema to the user's account but the specified database schema has not been granted connect privileges to the Portal schema.

**Action:** Use the Schema portlet to create a new schema that can be assigned to users. Select the "Use this Schema for Portal Users" check box. To edit an existing schema for this purpose, select Edit Schema in the Schema portlet.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWC-41438: Login is not possible because the login URL being retrieved for this application is not a fully qualified URL. Notify the portal administrator.**

**Cause:** Oracle Portal was unable to construct the URL required to redirect to the Oracle Single Sign-On Server. Partner application information may not be configured correctly.

**Action:** Contact the portal administrator and request that Oracle Portal is reregistered with the Oracle Single Sign-On Server.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41439: Login is not possible because there is either invalid or no configuration information stored in the enabler configuration table (WWSEC\_ENABLER\_CONFIG\_INFO\$).**

**Cause:** One of the following occurred: <ol> <li>An alias defined in the Apache configuration caused Apache to translate host.example.com to just host. If this is the case, the Login link will only shows host:port (dropping the domain)</li> <li>The default domain was not set in the Apache configuration. When this occurs, only the hostname is shown in the Login link and the domain is not included.</li> <li>Oracle Portal was configured with an incorrect host or port.</li> </ol>

**Action:** Do one of the following: <ol> <li>Remove all such aliases from your Apache configuration.</li> <li>Include the domain in the ServerName parameter.</li> <li>Fix the Host in the IASInstance element and ListenPort in the WebCacheComponent element in iasconfig.xml and run ptlconfig -dad portal -site. The ptlconfig script and the iasconfig.xml file are normally located in the directory portal/conf under the Oracle Portal and Oracle Wireless middle-tier home.</li> </ol> NOT USED

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41440: You cannot login because there was an error trying to parse the login URL for this application.**

**Cause:** A login request was made using a very long URL.

**Action:** Check the URL and reduce its length if it appears to be too long. There is no theoretical limit for the length of the URLs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41441: Unable to process the login request.**

**Cause:** The login URL was not constructed successfully. The reason is unknown. This problem could occur if Oracle Portal was unable to communicate with another component.

**Action:** Ensure that all components in the system are configured properly, are up and running, and are functioning correctly.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41443: %1**

**Cause:** The option 'Allow User to Log On' was not selected for this user. The user may login to Oracle Single Sign-On, but not Oracle Portal.

**Action:** Contact the portal administrator. Request that the 'Allow User to Log On' option is selected for this user.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41446: The system failed to initialize the necessary HTTP request to the Oracle Single Sign-On Server.**

**Cause:** The Oracle Single Sign-On Server was not running.

**Action:** Check whether the Oracle Single Sign-On Server is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41447: The system failed to retrieve the necessary HTTP request to the SSO Server.**

**Cause:** This error occurs in the following cases: <ol> <li>The Oracle Single Sign-On Server may not be operational. <li>There was an incorrect Querypath Url Prefix in the Oracle Single Sign-On Server settings.</li> </ol>

**Action:** Do one of the following: <ol> <li>Check whether the Oracle Single Sign-On Server is up and running. </li> <li>Verify the Querypath Url Prefix in the Oracle Single Sign-On Server settings.</li> </ol>

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41450: An invalid or null argument was passed into this routine.**

**Cause:** An invalid or null argument was passed into this routine.

**Action:** Check that valid parameter values are passed to this routine.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41451: There is no external application username mapping for the given user and the given application.**

**Cause:** There was no external application user name mapping for the given user and the given application.

**Action:** Log in to the external application and save the login credentials in the password store by selecting the 'Remember My Login Information' check box on the application login screen.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41452: The address from which this authentication request was made**

**Cause:** The system has IP address checking enabled and the IP address from the the client did not match the IP address associated with the original authentication. Using a proxy server can cause this problem.

**Action:** Disable IP address checking if a proxy server is being used.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41453: The cookie version specified in the authentication message is not supported by this configuration. Notify your administrator.**

**Cause:** The Oracle Single Sign-On Server does not support the version of the URLC token specified in the partner application configuration.

**Action:** Contact the portal administrator. Request that Oracle Portal be re-registered with the Oracle Single Sign-On Server.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41454: The decryption of the authentication information was unsuccessful. This may be caused by data inconsistency**

**Cause:** The URCL token received from the Oracle Single Sign-On Server was not decrypted.

**Action:** Contact the portal administrator to ensure that the Oracle Portal configuration is correct. Request that Oracle Portal be re-registered with the Oracle Single Sign-On Server if required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41470: Error while connecting to the Oracle Internet Directory.**

**Cause:** The Oracle Internet Directory Server may not have been operational.

**Action:** Contact the portal administrator to ensure that the Oracle Internet Directory Server is operational.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41471: Multiple groups with the given name were found in the directory. The group can't be resolved uniquely.**

**Cause:** Multiple groups with the given name were found in the directory.

**Action:** Use the popup list next to the name field to find the group name.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41472: An API used has been deprecated.**

**Cause:** An attempt was made to use a deprecated API.

**Action:** Check the latest API documentation for alternatives to this API.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41496: Unable to refresh the cache for OID Parameters.**

**Cause:** The Oracle Internet Directory Server may not have been operational.

**Action:** Check whether the Oracle Internet Directory port is operational and that the Oracle Portal configuration is referring to the correct host name and port. Use the command-line script 'ldapbind' to check if the LDAP port is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41610: The list of External Applications is too large.**

**Cause:** The list of External Applications returned from the Oracle Single Sign-On Server was too large.

**Action:** Try reducing the character length of External Application names by renaming them.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41611: The Enabler Configuration is missing.**

**Cause:** The Partner Application domain was not correctly set in the Oracle Single Sign-On Server configuration.

**Action:** Run the command line script ptlasst in MIDTIER mode to configure the Oracle Single Sign-On Server: ptlasst -mode MIDTIER -type SSO NOT USED

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41657: Your account is locked. Ask your administrator to reset the password.**

**Cause:** The number of attempts to login with an incorrect password exceeded the maximum number allowed.

**Action:** Contact your administrator to reset your password.

**Level:** 1

**Type:** ERROR

**Impact:** Other



---

**WWC-41742: There is a conflict with your assigned user name. There is a user entry with this name**

**Cause:** One or both of the following occurred: 

- Oracle Single Sign-On was using a stale user entry from its cache when transmitting user data to the Oracle Portal repository.
- The user profile for the specified user name already existed in the Oracle Portal schema, but it contains an incorrect Globally Unique Identifier.

**Action:** Contact the portal administrator to restart Oracle Single Sign-On after disabling its cache. If the problem persists then request the portal administrator to delete the existing local user profile using the `wwsec_api.delete_portal_user` API. Then login using that user's credentials.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41743: An exception was raised when accessing the Oracle Internet Directory: %1.**

**Cause:** An attempt was made to access the Oracle Internet Directory.

**Action:** Refer to the additional information (if any) displayed with this error message and take the appropriate action. Contact your portal administrator if additional information is not available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41744: You do not have permission to perform this operation in the Oracle Internet Directory (error status: %1).**

**Cause:** An attempt was made to perform an action in the Oracle Internet Directory without sufficient access privileges.

**Action:** Contact the portal administrator and request the necessary privileges be granted to perform this task.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41745: An entry was not found in the Oracle Internet Directory (error status: %1).**

**Cause:** An attempt was made to access an Oracle Internet Directory entry that does not exist.

**Action:** Check the value of the Oracle Internet Directory entry being accessed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41746: A value was not found in the Oracle Internet Directory (error status: %1).**

**Cause:** An attempt was made to search for an attribute value that does not exist in the specified directory entry.

---

**Action:** Check that the name of the attribute being searched is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41747: Multiple matches were found for the specified criteria in the Oracle Internet Directory (error status: %1).**

**Cause:** Multiple matches were found for the specified criteria in the Oracle Internet Directory.

**Action:** Verify that the specified search criteria is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41748: The specified entry or value already exists in the Oracle Internet Directory (error status: %1).**

**Cause:** An attempt was made to do one of the following: <ol> <li>Add a user or group entry in Oracle Internet Directory that already exists.</li> <li>Add an owner/member to a group that has already been added.</li> </ol>

**Action:** Check the name of the user or group that is being added. Check it either as an owner, or as a member of a group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41755: No portlet was specified.**

**Cause:** An attempt was made to call a portlet with an invalid reference.

**Action:** Remove the portlet and then add it again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41778: Delegated Administration Service (DAS) has not been configured properly. Contact the administrator.**

**Cause:** The DAS operation base URL was not specified in the Oracle Internet Directory.

**Action:** Specify the DAS operation base URL in the Oracle Internet Directory and refresh the Oracle Internet Directory cache in the repository.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41780: The system failed to process the HTTPS request to the SSO Server to retrieve the list of external applications.**

**Cause:** The wallet parameters were not available.

---

**Action:** Specify a valid wallet path and wallet password to access the external application information from the Oracle Single Sign-On Server using https.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41781: The system failed to process the HTTPS request to the SSO Server with specified wallet details.**

**Cause:** The Oracle Single Sign-On Server could not be reached using the given Query Path URL Prefix and the specified wallet parameters.

**Action:** Verify that the Query Path URL Prefix, wallet path, and wallet password are correct and that the Oracle Single Sign-On Server is up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41875: No external applications have been registered in the Oracle AS Single Sign-On Server.**

**Cause:** No external application existed.

**Action:** Add an external application. Portal administrators with single sign-on administrator privileges can add external applications.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41876: No external applications have been selected for display. To select applications to display**

**Cause:** One of the following occurred: <ol> <li>The portlet was customized to hide all external applications.</li> <li>No external applications existed.</li> </ol>

**Action:** Do one of the following: <ol> <li>Display one or more applications in the portlet.</li> <li>Add an external application. Portal administrators with single sign-on administrator privileges can add external applications.</li> </ol>

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41932: The specified user already exists. Specify a different user name.**

**Cause:** An attempt was made to create a user that already exists in Oracle Internet Directory.

**Action:** Specify a different user name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41934: An error occurred when attempting to set the default group.**

---

**Cause:** One of the following occurred: <ol> <li>An attempt was made to assign a group as the default group when the user was not a member of that group.</li> <li>The user did not have sufficient privileges to perform this task.</li> <li>An error occurred while accessing the Oracle Internet Directory.</li> </ol>

**Action:** Ensure that the user is already a member of the group when it is assigned as the default group. Report the error to your portal administrator and request that the appropriate privileges be granted if needed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41935: An error occurred when attempting to set the default page.**

**Cause:** An attempt was made to set the default page but the specified page does not exist.

**Action:** Specify a valid default page name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41937: Password is a mandatory field. You must specify its value.**

**Cause:** A password was not specified.

**Action:** Specify a password for the user.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41947: User Name is a mandatory field. You must specify its value.**

**Cause:** A user name was not specified.

**Action:** Specify a user name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41948: Confirm Password is a mandatory field. You must specify its value.**

**Cause:** The password was not confirmed.

**Action:** Re-enter the password to ensure that it was entered correctly.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41966: The preference store is missing the name of the schema required to perform this operation. Unable to continue.**

**Cause:** The name of the Oracle Single Sign-On schema is not available in the preference store.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-41974: You cannot access this screen because the enabler configuration is missing.**

**Cause:** An attempt was made to construct the URL required to access the Oracle Single Sign-On Server but the enabler configuration was not found. This can occur if the host and/or port information stored in the enabler configuration is removed after the user logged in.

**Action:** Contact the portal administrator. Request that Oracle Portal be re-registered with the Oracle Single Sign-On Server. NOT USED

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-42001: A null name was supplied. Supply a valid attribute name.**

**Cause:** A null value was provided for a required attribute.

**Action:** Specify an appropriate value for the attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43002: You do not have permission to perform this operation**

**Cause:** An attempt was made to perform an action but the user had insufficient privileges to perform the action.

**Action:** Contact the portal administrator and request the necessary privileges be granted to perform this task.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43007: There are no entities in cache to invalidate.**

**Cause:** A message was sent to Oracle Web Cache to invalidate an object, but the object was not found.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43100: A provider with this name has already been registered.**

**Cause:** An attempt was made to register a provider but the name specified has already been used.

**Action:** Specify a different provider name.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWC-43101: This provider was not found.**

**Cause:** A provider with the name specified could not be found.

**Action:** Make sure that you typed the name in correctly, or use the Navigator to find the provider you require.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43102: The name field is empty.**

**Cause:** A name for the provider was not specified.

**Action:** Specify a provider name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43103: The name field exceeds the maximum length.**

**Cause:** The provider name specified was too long.

**Action:** Enter a provider name that is less than 200 characters in length.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43105: The owning schema field is empty.**

**Cause:** An owning schema was not specified. This field is mandatory for database providers.

**Action:** Enter an owning schema.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43106: Schema %1 was not found.**

**Cause:** The schema entered was not found.

**Action:** Enter a valid schema name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43107: The package name field is empty.**

**Cause:** The package name was not specified. This field is mandatory for database providers.

**Action:** Enter a package name.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWC-43109: The package name exceeds the maximum length.**

**Cause:** The package name specified was too long.

**Action:** Enter a package name that is less than 2000 characters in length.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43112: The timeout must be left blank or be a positive value.**

**Cause:** The timeout value specified was a negative value.

**Action:** Either leave the timeout blank or enter a positive value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43113: The value for login frequency is not valid.**

**Cause:** An invalid value for the login frequency was specified.

**Action:** Set the login frequency to one of: Once, Always, Never or Public.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43116: The specified node was not found.**

**Cause:** It was not possible to find the local portal node record.

**Action:** Contact the portal administrator and report this error. This error indicates data inconsistencies in the portal instance.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43132: The implementation package is not in a valid state.**

**Cause:** A PL/SQL package implementing a provider was in an 'INVALID' state. For example, the PL/SQL package may contain a syntax error, or reference a missing or invalid object.

**Action:** Recompile the PL/SQL package. If the compilation fails, resolve the errors reported.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43133: The implementation package was not found.**

**Cause:** A PL/SQL package or package body implementing a provider was not found.

**Action:** Ensure the schema and package name specified for the provider is correct and that the PL/SQL package has been created in the specified schema.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43134: An error occurred when attempting to call the providers register function.**

**Cause:** An attempt was made to register a provider.

**Action:** Ensure that the provider is operational, and that the registration details are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43135: The Web URL for Web implementations is not valid.**

**Cause:** The URL specified for the Web provider was not valid, or was null.

**Action:** Specify the correct Web provider URL.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43137: An HTTP proxy was indicated but the proxy is invalid.**

**Cause:** It was specified that this provider required a proxy but the proxy definition provided was invalid.

**Action:** Verify the proxy settings in the Global Settings page.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43139: The Web application type is invalid.**

**Cause:** The Web provider had an invalid value for the HTTP application type.

**Action:** Ensure that the HTTP application type is one of `EXTERNAL_SECURED`, `PORTAL` or null. Constants are defined for these values in the `WWPRO_API_PROVIDER_REGISTRY` public API package.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43140: The Web external application id is invalid.**

**Cause:** The external application ID specified was not valid.

**Action:** Use the list of values provided to select a valid value, or leave this field blank.

**Level:** 1

**Type:** ERROR

**Impact:** Other



---

**WWC-43141: The following error occurred when converting \"%1\" into an integer: %2**

**Cause:** An attempt was made to convert a string into a number.

**Action:** Review the reported error and take the appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43144: The following error occurred when converting \"%1\" into a date: %2**

**Cause:** An attempt was made to convert a string into a date.

**Action:** Review the reported error and take the appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43145: The value \"%1\" is not a valid content type.**

**Cause:** The portlet content type specified was invalid.

**Action:** Ensure that the portlet's content type is one of text/html or text/xml.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43146: The specified shared key is not valid.**

**Cause:** The shared key specified was not valid.

**Action:** Enter a key that is between 10 and 30 characters in length.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43147: The following error occurred during the call to Web provider: %1**

**Cause:** A call to the Web provider failed with the specified error.

**Action:** Review the reported error and take the appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43167: The specified name is invalid. Names are alphanumeric and cannot contain spaces or special characters.**

**Cause:** An invalid name was specified.

**Action:** Enter a name that contains only letters, numbers, and underscores.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWC-43169: This provider is not deletable.**

**Cause:** An attempt was made to delete a provider that is offline or not deletable.

**Action:** If the provider is offline, make it online before attempting to delete it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43176: The provider URL specified may be wrong or the provider is not running.**

**Cause:** Oracle Portal could not contact the provider because the URL specified was either incorrect or the provider was not running.

**Action:** Verify that the URL specified during provider registration is correct and that the provider is up and running. One way to verify this for a Web provider is to enter the URL in browser. If the provider information is correct and the provider is up, the provider's test page is displayed. If the URL is correct and the provider is up, there may be a problem with the configuration of the portal repository. Contact the portal administrator to enable debug logging in the portal repository and view the log information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43183: The portlet ID and portlet name must be unique within a provider**

**Cause:** An attempt was made to register a provider that contains portlets and the portlet names or portlet IDs are not unique within that provider.

**Action:** Contact the developer responsible for the provider and request that this issue be resolved.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43184: Invalid portlet ID**

**Cause:** The portlet ID was invalid or null.

**Action:** Contact the developer responsible for the provider and request that this issue be resolved.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43185: The portlet ID value of %1 is invalid. The portlet ID must be in the range -2147483648 to 2147483648.**

**Cause:** A portlet ID was not in a valid range.

**Action:** Contact the developer responsible for the provider and request that this issue be resolved.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWC-43186: The portlet name for portlet with ID=%1 is null. The portlet name cannot be null.**

**Cause:** A portlet name was null.

**Action:** Contact the developer responsible for the provider and request that this issue be resolved.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43187: The portlet name '%1' contains space characters. The portlet name should not contain any space characters.**

**Cause:** A portlet name contained space characters.

**Action:** Contact the developer responsible for the provider and request that this issue be resolved.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43188: You have registered this web provider with the \"Same Cookie Domain\" check box checked.**

**Cause:** Cookies created by this provider are forwarded to the user's browser and managed by the browser instead of Oracle Portal. Once managed by the browser, the cookies are sent to any other Web server that: 

- Is accessed within the same browser session.
- Falls within the relaxed scope specified when the cookie was created.

**Action:** This can result in cookie collisions and errors/loss of sessions in unrelated Web applications. To minimize the possibility of cookie collisions, ensure that: 

- Any custom cookies created by the Web provider have names that are unique to that Web provider.
- All portal instances accessed using the Federated Portal Adapter are configured with different DAD names.
- PDK-Java release 1 (JServ) Web providers requiring this setting are installed in uniquely named JServ servlet zones.
- PDK-Java release 2 (OC4J) Web providers do not use this setting if they use servlet sessions. This is because the cookie used to identify the session is always called JSESSIONID. This name is specified in the Servlet 2.3 specification. Relaxing the scope of a JSESSIONID cookie will almost certainly cause session related problems to occur in other, unrelated, Web applications.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43190: An error occurred while trying to refresh the provider. The original registration could not be found.**

**Cause:** The provider URL used for the registration may not be a valid URL or is not be accessible.

**Action:** Make sure the the Provider URL is valid and properly accessible from portal.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43192: The provider package name %1 is reserved for internal use and cannot be used for registering a provider.**

**Cause:** The package name specified is reserved for internal use by Oracle Portal. Users cannot use it for registering providers.

**Action:** Specify a different package name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43220: The signature key password field is empty.**

**Cause:** The signature key password was not specified.

**Action:** Specify the signature key password.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43255: Registration handle cannot be null.**

**Cause:** The registration handle used to refer to the registration of the provider in all provider communications was not present.

**Action:** Check whether the provider has a registration port. If a registration port exists, contact the provider administrator and request that the provider supplies the necessary registration handle. If the provider expects an out-of-band registration handle, supply the value of the handle in the Connection tab.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43256: Registration handle length exceeds 255 characters.**

**Cause:** The length of the registration handle generated or supplied for this registration exceeded 255 characters.

**Action:** If you supplied the value for the registration handle as an out-of-band registration handle, provide a value that is less than 255 characters in length. If the registration handle is generated by the provider, contact the WSRP provider administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43257: Portlet handle cannot be null.**

**Cause:** The provider did not generate a handle for this portlet, or Oracle Portal failed to store the portlet handle returned by the provider.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43258: Portlet handle length exceeds 255 characters.**

**Cause:** The portlet handle returned by the WSRP Provider exceeded 255 characters.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43259: Translations for portlet multi-value attributes cannot be fetched.**

**Cause:** The provider did not return translations for the portlet attributes, or Oracle Portal failed to store them.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43273: An error occurred during the call to the WSRP Provider: %1.**

**Cause:** A problem occurred while getting the service description. This may be because the provider sent unsupported extensions.

**Action:** Try turning off extensions on the producer side or contact the WSRP provider administrator or portal administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43274: Markup types for the WSRP provider portlet \"%1\" [Provider id: %2] was not found in the Portlet Metadata Repository.**

**Cause:** If the WSRP provider's WSDL URL has changed, this may have caused existing portlets to be replaced with the portlets of the new provider. If the WSDL URL has not changed, there could be some data inconsistency.

**Action:** Check for changes in the WSRP provider's registration URL. If the URL has not changed, try re-registering the provider.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43275: The Web Service URL is either empty or not properly formed.**

**Cause:** The Web Service URL may be empty or it was not formed properly.

**Action:** Provide a correct URL or contact the WSRP provider administrator.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWC-43277: The producer URL specified may be wrong or the producer is not running.**

**Cause:** The URL specified was either incorrect or the producer was not running. This caused a problem when Oracle Portal tried to contact the producer using that URL.

**Action:** Verify that the URL specified for the producer registration is correct and that the producer is up and running. One way to verify this is to enter the registration URL in a browser. If the URL is correct and the producer is up and running, you will see the producer's WSDL document.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43295: The default user field is empty.**

**Cause:** A default user is not specified.

**Action:** Specify a default user.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43296: The issuer name field is empty.**

**Cause:** An issuer name was not specified.

**Action:** Specify an issuer name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43297: The store path field is empty.**

**Cause:** The store path was not specified.

**Action:** Specify the absolute location of the keystore on the server.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43298: The store password field is empty.**

**Cause:** The store password was not specified.

**Action:** Specify the store password.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43299: The signature key alias field is empty.**

**Cause:** The signature key alias is not specified.

**Action:** Specify the signature key alias.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43300: The mode parameter must be MODE\_SHOW**

**Cause:** A show request was made to a portlet with an invalid show mode.

**Action:** Ensure that the show mode for the request is one of: MODE\_SHOW, MODE\_SHOW\_ABOUT, MODE\_SHOW\_EDIT, MODE\_SHOW\_HELP, MODE\_SHOW\_EDIT\_DEFAULTS, MODE\_SHOW\_DETAILS, MODE\_PREVIEW, or MODE\_LINK. Note that these constants are defined in the WWPRO\_API\_PROVIDER public API.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43302: get\_portlet returned an implementation type other than Database or Web for Portlet %1.%2.**

**Cause:** The portlet returned an invalid implementation type.

**Action:** Ensure that the portlet implementation type is one of: PLSQL\_IMPL or HTTP\_IMPL. These constants are defined in the API WWPRO\_API\_PROVIDER\_REGISTRY public API.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43303: Web portlets can only be displayed in the parallel mode.**

**Cause:** A Web provider portlet was called by the PL/SQL API that was created to show PL/SQL portlets.

**Action:** Contact the portal administrator. This message indicates data inconsistency.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43307: The user did not have permission to update the portlets ACL.**

**Cause:** Either an attempt was made to update the portlet's access control list (ACL), or the portlet is offline.

**Action:** Contact the portal administrator. Request that the required privileges be granted, or ensure that the portlet is online.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43308: The specified portlet was not found in the Portlet Metadata Repository.**

**Cause:** The specified portlet was not found in the Portlet Metadata Repository. This error suggests data inconsistency.

---

**Action:** Refresh the provider that contains the portlet and attempt the operation again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43309: You do not have permission to access the portlet called \"%1\" (%2**

**Cause:** An attempt was made to access the portlet but the user had insufficient privileges.

**Action:** Contact the portal administrator. Request access to the portlet be granted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43310: The specified portlet's provider is offline.**

**Cause:** An attempt was made to access a portlet but its provider was offline.

**Action:** Ensure that the provider is online and attempt the operation again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43339: Analysis of the WSDL failed.**

**Cause:** Parsing of the WSDL provided failed. This could be due to an error entering the URI of the WSDL, or that the WSDL does not describe a valid WSRP service.

**Action:** Check the URI entered is correct, and check with the producer's administrator that the URI is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43343: Error: Could not get portlet markup. Try reloading the portlet or the page.**

**Cause:** A request for portlet markup failed.

**Action:** Try reloading the portlet or the page. Check that you still have permission to use the portlet and that the producer is running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43722: The Provider Group \"%1\" is not registered.**

**Cause:** The provider group specified was not found in the portal repository.

**Action:** Ensure that the name of the provider group requested is correct.

**Level:** 1

**Type:** ERROR



---

**Impact:** Other

**WWC-43725: The Provider Group \"%1\" is already registered with Oracle Portal.**

**Cause:** The provider group specified was already registered with Oracle Portal.

**Action:** This error suggests data inconsistency. Contact the portal administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43733: Error accessing remote provider group server: %1**

**Cause:** An error occurred while accessing the remote provider group server.

**Action:** Check the error text, and any subsequent error messages, for specific details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-43735: The Provider Group \"%2\" defined by the server at URL \"%1\" is already registered with Oracle Portal.**

**Cause:** An attempt was made to register a provider group but a provider group with the same details had already been registered with Oracle Portal.

**Action:** Use the provider group previously registered with these details.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44009: The Name you specified is already in use. Recommended Name:%1**

**Cause:** An attempt was made to specify a page/tab name that already exists.

**Action:** Specify a different name for the page/tab.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44081: Specify a display name for this style.**

**Cause:** A display name was not specified when creating or copying a style.

**Action:** Specify a display name for the style.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44085: This region was already split.**

**Cause:** An attempt was made to split a region that was already split.

**Action:** Specify a different region, that is, one which is not already split.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWC-44087: A region with this display name already exists.**

**Cause:** An attempt was made to create a region but a regions with the specified name already exists.

**Action:** Specify a unique name for the region.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44089: This region was not found.**

**Cause:** An attempt was made to delete, split, edit, or copy a region but the region could not be found.

**Action:** Specify a valid region.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44090: Cannot delete the main region.**

**Cause:** An attempt was made to delete the main region of the page but the main region cannot be deleted unless the page is deleted.

**Action:** Specify a different region for deletion.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44091: Specify a numeric value for the region width.**

**Cause:** An attempt was made to edit the width of a region but an non-numeric value was specified.

**Action:** Ensure that the width value is an integer value (preferably between 1 and 100). If the width is a relative width, specify the % symbol (for example, 65%). If the width is an absolute width, specify only the numeric value (for example, 35).

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44102: Specify a Display Name.**

**Cause:** Name and display name values were not provided for a page.

**Action:** Specify name and display name values for the page. These values may not be null.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44131: You do not have permission to perform this operation.**

---

**Cause:** An attempt was made to perform an operation but the user did not have sufficient privileges.

**Action:** Login to Oracle Portal as a user with permissions to perform the operation. Alternatively, contact the portal administrator to request that the necessary privileges be granted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44132: Error while setting the default page.**

**Cause:** An attempt was made to set the default page for a user or group but the operation failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44151: This style was not found.**

**Cause:** An attempt was made to access a style but the specified style name and page group ID do not exist.

**Action:** Provide a valid style name and page group ID.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44214: The URL specified is invalid.**

**Cause:** The value specified for a URL attribute did not begin with a valid protocol such as http://, https://, or ftp://.

**Action:** Correct the url, entering a valid protocol.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44233: The name that you entered is not valid. Valid names only contain alphabetic or numeric characters**

**Cause:** The name that was entered contained invalid characters.

**Action:** Specify a different name using only the characters A to Z, a to z, 0 to 9, and underscore (\_).

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44234: Page not found.**

**Cause:** An attempt was made to view or edit an Oracle Portal page but the specified page does not exist

**Action:** Check that the specified page name or page ID is correct.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44250: You do not have permission to move the selected portlets.**

**Cause:** An attempt was made to move one or more portlets, but the user did not have the appropriate privileges.

**Action:** Login as a user with Personalize (Full) privileges on the page containing the portlets. Alternatively, add the same portlet to the destination region and hide the portlet in the source region.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44251: You do not have permission to move the selected objects.**

**Cause:** An attempt was made to move one or more items or portlets, but the user did not have the appropriate privileges.

**Action:** Login as a user with either Manage Content privileges on the page containing the item or portlet, or Manage privileges on the item itself. Alternatively, add the same portlet to the destination region and hide the portlet in the source region.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44258: You do not have permission to move content into the selected region.**

**Cause:** An attempt was made to add content to a region, but the user did not have the appropriate privileges.

**Action:** Login as a user with the appropriate privileges to perform the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44279: The default page for the system cannot be deleted.**

**Cause:** An attempt was made to delete a system default page. Such pages cannot be deleted.

**Action:** Do not attempt to delete this page.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44284: Error while adding banner for the template.**

**Cause:** An attempt was made to set the default navigation page for a page group, but the specified navigation page does not exist.

**Action:** Select a different navigation page to be the default navigation page for the page group.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44334: Portlet Information could not be obtained.**

**Cause:** An attempt to access a portlet failed because the provider and/or portlet was not found.

**Action:** Make sure the provider is online, the portlet is available, and that the user has permission to access the provider/portlet.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44366: This page cannot be copied as a JSP**

**Cause:** An attempt was made to copy a page that is not a standard page as a JSP. Only standard pages can be copied as JSPs.

**Action:** Choose a standard page when copying as a JSP.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44552: Specify a numeric value for the space between portlets.**

**Cause:** When editing a region, a non-numeric value was specified for the "Space between Portlets" field.

**Action:** Specify an integer value (preferably between 1 and 100) for the "Space between Portlets" field. If no space is required between portlets, specify 0 or null.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44570: Specify a numeric value for the space around portlets.**

**Cause:** When editing a region, a non-numeric value was specified for the "Space around Portlets" field.

**Action:** Specify an integer value (preferably between 1 and 100) for the "Space around Portlets" field. If no space is required around portlets, specify 0 or null.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44582: Error while creating tab**

**Cause:** An attempt to add a tab failed. Either the specified tab name was invalid or the user does not have permission to add a tab.

**Action:** Specify a valid name for the tab, or make sure that the user has the appropriate privileges to add a tab.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWC-44583: Error while editing tab**

**Cause:** An attempt to edit a tab failed. Either the specified tab name was invalid or the user did not have permission to edit the tab.

**Action:** Specify a valid name for the tab, or make sure that the user has the appropriate privileges to edit the tab.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44650: Specify a numeric value for item icon height.**

**Cause:** An invalid value was specified for the Item Icon Height field.

**Action:** Specify a positive number for the height (in pixels) of item images.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44651: Specify a numeric value for item icon width.**

**Cause:** An invalid value was specified for the Item Icon Width field.

**Action:** Specify a positive number for the width (in pixels) of item images.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44652: Invalid number of columns. Value should be at least be 1.**

**Cause:** An invalid value was specified for the number of columns.

**Action:** Specify a positive number for the number of columns in the region.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44662: To perform this action**

**Cause:** An action button was clicked without first selecting any portlets, items, or tabs.

**Action:** Select one or more portlets, items, or tabs before clicking an action button.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44704: Error while creating the page parameter**

**Cause:** An attempt to create a page parameter failed.

**Action:** Refresh the screen and verify that the page is still available.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWC-44705: Error while reordering page parameter \"%1\"**

**Cause:** An attempt to reorder page parameters failed.

**Action:** Refresh the screen and verify that the page and page parameter are still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44706: Error while deleting page parameter \"%1\"**

**Cause:** An attempt to delete a page parameter failed.

**Action:** Refresh the screen and verify that the page and page parameter are still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44707: Error while editing page parameter \"%1\"**

**Cause:** An attempt to edit the value of a page parameter failed.

**Action:** Refresh the screen and verify that the page parameter is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44708: Invalid page parameter name \"%1\"**

**Cause:** The specified page parameter name was invalid.

**Action:** Enter a valid page parameter name. Refer to the Page Properties Parameter tab for a list of valid page parameter names.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44709: Error while editing value of portlet parameter \"%1\"**

**Cause:** An attempt to edit the value of a portlet parameter failed.

**Action:** Refresh the screen and verify that the portlet parameter is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44714: Error while personalizing page parameter \"%1\"**

**Cause:** An attempt to personalize a page parameter failed.

**Action:** Refresh the screen and verify that the page parameter is still available.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWC-44715: Error while resetting page parameters to default values.**

**Cause:** An attempt to reset page parameters to their default values failed.

**Action:** Refresh the screen and verify that the personalization screen is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44721: Error while fetching portlet parameters**

**Cause:** An attempt to fetch portlet parameters failed.

**Action:** Refresh the screen and verify that the portlet is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44751: Error while editing value of parameter \"%1\"**

**Cause:** An attempt to edit the value of an event parameter failed.

**Action:** Refresh the screen and verify that the event parameter is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44752: Error while linking event \"%1\" to page \"%2\"**

**Cause:** An attempt to link an event to a page failed.

**Action:** Refresh the screen and verify that the event and the page are still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44753: Error while removing link from event \"%1\"**

**Cause:** An attempt to remove a link from an event failed.

**Action:** Refresh the screen and verify that the event is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44754: Error while updating link between event \"%1\" and page \"%2\"**

**Cause:** An attempt to update the target page for an event failed.

**Action:** Refresh the screen and verify that the event and the page are still available.

**Level:** 1

**Type:** ERROR



---

**Impact:** Other

**WWC-44755: Invalid event output name \"%1\"**

**Cause:** The specified event output name was invalid.

**Action:** Specify a valid event output name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44756: The name that you entered has already been used. Pick a name that is unique.**

**Cause:** The specified name has already been used.

**Action:** Specify a different, unique name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44757: Error while creating the parameter: %1**

**Cause:** An attempt to create a parameter failed.

**Action:** Refresh the screen and verify that the parent object is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44758: Error while editing the parameter: %1**

**Cause:** An attempt to edit a parameter failed.

**Action:** Refresh the screen and verify that the parent object is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44759: Parameter cannot be personalized**

**Cause:** An attempt to personalize a parameter failed. The parameter cannot be personalized.

**Action:** Refresh the screen and verify whether or not the parameter is personalizable.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44761: Error while deleting parameter: %1**

**Cause:** An attempt to delete a parameter failed.

**Action:** Refresh the screen and verify that the parent object and the parameter are still available.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WWC-44762: Parameter \"%1\" not found**

**Cause:** The specified parameter was not found.

**Action:** Refresh the screen and verify that the parent object is still available and that the user has the appropriate access permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44765: Search for parameter \"%1\" caused an error: %2**

**Cause:** An attempt to search for a parameter failed.

**Action:** Refresh the screen and verify that the object is still available and that the user has the appropriate access permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44766: Error while creating the parameter mapping: %1**

**Cause:** An attempt to create a parameter map failed.

**Action:** Refresh the screen and verify that the parent object is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44767: Error while updating the parameter mapping: %1**

**Cause:** An attempt to edit a parameter map failed.

**Action:** Refresh the screen and verify that the parent object is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44768: Unsupported from type \"%1\"**

**Cause:** The source object type specified is not supported.

**Action:** Select a different source object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44769: Parameter \"%1\" already has the smallest display order and can't be moved up.**

**Cause:** An attempt was made to move the first parameter in the list to the top of the display order.

**Action:** Refresh the screen and verify that the parameter is already at the top of the display order.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44770: Moving parameter \"%1\" up in the display order failed: %2**

**Cause:** An attempt to move a parameter up in the display order failed.

**Action:** Refresh the screen and verify that the parameter is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44775: Flow element not found**

**Cause:** The specified flow element was not found.

**Action:** Refresh the screen and verify that the dependent object is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44779: Error while creating flow link \"%1\"**

**Cause:** An attempt to create a flow link failed.

**Action:** Refresh the screen and verify that the parent page is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44780: Error while deleting flow link \"%1\"**

**Cause:** An attempt to delete a flow link failed.

**Action:** Refresh the screen and verify that the parent page is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44781: Flow link not found**

**Cause:** The specified flow link was not found.

**Action:** Refresh the screen and verify that the parent page is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44783: Invalid parent type for event \"%1\"**

**Cause:** The specified parent object did not have a valid type.

**Action:** Refresh the screen and verify that the parent object is still available.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWC-44784: Parent of event \"%1\" is not a portlet**

**Cause:** The specified parent object was not a portlet.

**Action:** Specify a portlet.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44786: Event \"%1\" already exists**

**Cause:** The specified event name already exists.

**Action:** Specify a different, unique event name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44787: Error while creating event \"%1\": %2**

**Cause:** An attempt to create an event failed.

**Action:** Refresh the screen and verify that the parent object is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44788: Error while deleting event: %1**

**Cause:** An attempt to delete an event failed.

**Action:** Refresh the screen and verify that the event is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44789: Error while deleting events: %1**

**Cause:** An attempt to delete events failed.

**Action:** Refresh the screen and verify that the events are still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44790: Event not found**

**Cause:** The specified event was not found.

**Action:** Refresh the screen and verify that the parent object is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44791: Event \"%1\" not found**

---

**Cause:** The specified event was not found.

**Action:** Refresh the screen and verify that the parent object is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44792: Events not found**

**Cause:** The specified events were not found.

**Action:** Refresh the screen and verify that the parent objects are still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44793: Error while creating event map: %1**

**Cause:** An attempt to create an event map failed.

**Action:** Refresh the screen and verify that the event is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44794: Error while deleting event map: %1**

**Cause:** An attempt to delete an event map failed.

**Action:** Refresh the screen and verify that the event is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44795: Event map not found**

**Cause:** The specified event map was not found.

**Action:** Verify that the parent object is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44801: Error while searching for parameter mapping: %1**

**Cause:** The specified parameter map was not found.

**Action:** Refresh the screen, verify that the parent object is still available and that the user has the appropriate access permissions.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44803: Duplicate event maps not allowed**

**Cause:** An attempt was made to duplicate an event map.

---

**Action:** Edit or delete the existing event map, or create a new event map.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44812: Error while fetching portlet events**

**Cause:** An attempt to fetch portlet events failed.

**Action:** Refresh the screen and verify that the portlet is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44815: Error while retrieving link from event \"%1\"**

**Cause:** An attempt to retrieve the link from an event failed.

**Action:** Refresh the screen and verify that the event is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44816: Error while retrieving the target page for event \"%1\"**

**Cause:** An attempt to retrieve the target page for an event failed.

**Action:** Refresh the screen and verify that the event is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44829: Error while writing parameter map metadata: %1**

**Cause:** An attempt to write parameter map metadata failed.

**Action:** Refresh the screen and verify that the parameter map is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44833: Error while adding display name or description for event \"%1\"**

**Cause:** An attempt to add a display name or description for an event failed.

**Action:** Refresh the screen and verify that the event is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44834: Error while editing the event: %1**

**Cause:** An attempt to edit an event failed.

**Action:** Refresh the screen and verify that the event is still available.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44835: Error while creating page event from portlet event \"%1\": %2**

**Cause:** An attempt to create a page event from a portlet event failed.

**Action:** Refresh the screen and verify that the portlet event is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44836: Error while invalidating page cache after updating event: %1**

**Cause:** An attempt to invalidate the page cache after updating an event failed.

**Action:** Refresh the screen and verify that the event or dependent object is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44840: Invalid context for parameter \"%1\"**

**Cause:** The parent object (portlet, page, or event) for the parameter was not valid.

**Action:** Refresh the screen and verify that the parent object still exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44841: Error during a parameter change event: %1**

**Cause:** An attempt to update a parameter failed.

**Action:** Refresh the screen and verify that the parameter and/or dependent object are still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44843: Page not found: %1**

**Cause:** The specified page was not found.

**Action:** Verify that the page exists and that the details of the specified page are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44875: Portal Template not found**

**Cause:** An attempt was made to base a page on an invalid template.

**Action:** Specify a valid template.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44891: The system variable \"%1\" is not valid. Choose a different value.**

**Cause:** An invalid system variable was specified.

**Action:** Specify a valid system variable, one of USER\_NAME, USER\_ID, COMPANY\_NAME, SUBSCRIBER\_ID, NLS\_LANG, or NLS\_TERRITORY.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44899: Error during a parameter map change event: %1**

**Cause:** An attempt to update a parameter map failed.

**Action:** Refresh the screen and verify that the parameter map and/or the dependent objects are still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44901: Error while deleting flow link children: %1**

**Cause:** An attempt to delete the children of a flow link failed.

**Action:** Refresh the screen and verify that the dependent objects are still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44902: Error while deleting parameter maps: %1**

**Cause:** An attempt to delete parameter maps failed.

**Action:** Refresh the screen and verify that the dependent objects are still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44929: You can only download jsp file for a JSP page.**

**Cause:** An attempt was made to download a JSP file from a non-JSP type page.

**Action:** Specify a JSP page to download.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-44930: You do not have privileges to download the jsp file for this JSP page.**

**Cause:** An attempt was made to download the JSP file of a JSP page without the appropriate permissions.

**Action:** Login as a user with permissions to perform the operation.



---

**Level: 1**

**Type: ERROR**

**Impact: Other**

**WWC-44932: The page's template cannot be changed to \"%1\" because the page contains portlets or items and the selected template has no portlet regions or item regions.**

**Cause:** A template was selected without an item region or portlet region for the items or portlets on the page.

**Action:** Choose a different template. Make sure that the template contains the necessary region types.

**Level: 1**

**Type: ERROR**

**Impact: Other**

**WWC-44997: Error while refreshing the portlet repository.**

**Cause:** An attempt to refresh the portlet repository failed.

**Action:** The page is published as a portlet. Refresh the repository manually.

**Level: 1**

**Type: ERROR**

**Impact: Other**

**WWC-45026: Number of objects in each section must be a number greater than zero**

**Cause:** An invalid value was specified for the number of objects in each section.

**Action:** Specify a number greater than zero.

**Level: 1**

**Type: ERROR**

**Impact: Other**

**WWC-45235: Number entered for the limit must be a valid number greater than or equal to zero.**

**Cause:** An invalid number value was specified for the limit.

**Action:** Specify a valid number between 0 and 50.

**Level: 1**

**Type: ERROR**

**Impact: Other**

**WWC-45256: This page group does is not configured to allow JSP access.**

**Cause:** An attempt was made to copy a JSP to a page group that is not configured to allow JSP access.

**Action:** Edit the properties of the page group and, on the Configure tab, enable "JSP Access".

**Level: 1**

**Type: ERROR**

**Impact: Other**

---

**WWC-45290: The portlet was not found (%1**

**Cause:** An attempt was made to access a portlet with a given portlet ID and provider ID, using the API call `wwsbr_folder_portlet.describe_parameters`. The specified portlet was not found.

**Action:** Ensure that the specified provider ID and portlet ID are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-46800: Document not found.**

**Cause:** An attempt was made to access a document does not exist or that is no longer accessible.

**Action:** Verify that the specified URL is still valid, if applicable. Visit the parent page to check that the item still exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-46805: You do not have permission to perform this operation.**

**Cause:** An attempt was made to perform an action but the user does not have the appropriate permissions.

**Action:** Login as a user who has permission to perform the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-46811: Your file cannot be uploaded because it is larger than the maximum allowed file size.**

**Cause:** An attempt was made to upload a file that exceeds the maximum size allowed per file.

**Action:** Reduce the size of the file, or contact the portal administrator and request that the maximum permitted file size be increased.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-46813: Your file cannot be uploaded because doing so would exceed the total amount of space allocated for uploaded files.**

**Cause:** An attempt was made to upload a file that would result in the allocated space quota being exceeded.

**Action:** Create some free space by deleting other documents, or contact the portal administrator and request that the quota allocation be increased.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWC-47499: You do not have permission to access this screen.**

**Cause:** An attempt was made to access a screen but the user does not have sufficient privileges.

**Action:** Login as a user with at least the 'All Logs - Edit' privilege.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-49100: Unable to locate type %1.**

**Cause:** An attempt was made to load a non-existing dynamic type.

**Action:** Verify the name of the dynamic type.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-49101: Invalid conversion requested for type %1.**

**Cause:** A mismatch occurred between the dynamic type loaded and the requested conversion type. For example, the `type_to_number()` method was invoked after loading a date type.

**Action:** Ensure that the type loaded and the requested conversion type match. For example, if a number type is loaded a number, invoke the `type_to_number()` method for conversion.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-49102: No conversion performed for type %1**

**Cause:** The value provided could not be converted to the requested type using the available format masks. The format mask used may be invalid.

**Action:** Provide a valid format mask.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-50003: Object not found.**

**Cause:** The specified path to the given object did not exist.

**Action:** Check that the path is valid. Path names are case-sensitive.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-50015: You do not have permission to perform this operation.**

**Cause:** An attempt was made to perform an operation but the user does not have the appropriate permissions.

**Action:** Login as a user who has permission to perform the operation.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53100: General error**

**Cause:** An attempt to access the Oracle Internet Directory failed.

**Action:** Wait for a while and attempt the operation again. Contact the portal administrator if the problem persists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53101: Invalid input parameter**

**Cause:** Invalid values were specified for input parameters.

**Action:** Check the specified input parameter values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53102: The specified user is not a member of any group**

**Cause:** The specified user was not a member of any group.

**Action:** Check the specified user name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53103: The specified subscriber does not exist in the directory**

**Cause:** An attempt was made to access a subscriber that does not exist in the directory.

**Action:** Check the name of the subscriber required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53104: The specified user does not exist in the directory**

**Cause:** The specified user does not exist in the directory.

**Action:** Check the name of the specified user.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53105: The root oracle context doesn't exist in the directory**

**Cause:** The root Oracle Context was not found in the directory.

**Action:** Check the Oracle Internet Directory Server configuration and ensure the root Oracle Context information is loaded properly.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53106: Multiple subscriber entries were found for the specified subscriber nickname**

**Cause:** Multiple subscriber entries with the same subscriber nickname were found in the Oracle Internet Directory.

**Action:** Verify that the nickname attribute of subscribers in the Oracle Internet Directory are unique.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53107: Root oracle context doesn't contain all the required information**

**Cause:** The root Oracle Context level was not found.

**Action:** Check the Oracle Internet Directory Server configuration and ensure that the root Oracle Context information is loaded properly.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53108: Oracle context doesn't exist for the subscriber**

**Cause:** Oracle Context was not found for the subscriber.

**Action:** Check the Oracle Internet Directory Server configuration and ensure that the subscriber Oracle Context information is loaded properly.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53109: Oracle context for the subscriber is invalid**

**Cause:** Oracle Context for the subscriber was invalid.

**Action:** Check the Oracle Internet Directory Server configuration and ensure that the subscriber Oracle Context information is loaded properly.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53110: Multiple user entries exist for the specified user nickname**

**Cause:** Multiple users with the given name were found in the directory.

**Action:** Use the popup list next to the name field to specify the user name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53111: The specified group doesn't exist in the directory**

---

**Cause:** An attempt was made to access a group that does not exist in the directory.

**Action:** Check the name of the group required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53112: Multiple group entries exist for the specified group nickname in the directory**

**Cause:** Multiple groups with the given name were found in the directory.

**Action:** Check that the group name is valid. Use the popup list next to the name field to specify the group name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53113: Your account is locked. Have your administrator reset your password**

**Cause:** The user account was locked because the number of failed login attempts exceeded the maximum number allowed, as specified by the password policy.

**Action:** Contact the portal administrator and request that the password be reset. Alternatively, wait for the lockout period to expire.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53114: The password is about to expire and should be changed**

**Cause:** A password is about to expire.

**Action:** Change the password before it expires.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53115: Your username or password is incorrect**

**Cause:** An attempt was made to authenticate with incorrect login credentials.

**Action:** Specify the correct login credentials.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53116: Your password has expired**

**Cause:** A password has expired.

**Action:** Contact the portal administrator and request that the password be reset.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWC-53117: The entity handle properties are being reset by the caller**

**Cause:** An unexpected condition was encountered.

**Action:** Report this error to Oracle Support Services. Include the operations that led to the error, any unusual circumstances that occurred before receiving this error, and the complete stack trace produced by this error.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53118: Unable to locate the subscriber for the specified user**

**Cause:** An unexpected condition was encountered.

**Action:** Report this error to Oracle Support Services. Include the operations that led to the error, any unusual circumstances that occurred before receiving this error, and the complete stack trace produced by this error.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53119: The password is about to expire; change the password now.**

**Cause:** A password is about to expire.

**Action:** Change the password before it expires.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53120: Your password is smaller than the minimum required size of a password**

**Cause:** The password specified was less than the minimum required length required for passwords.

**Action:** Specify a password that is equal to, or greater than, the minimum required password length. If necessary, contact the portal administrator to confirm the minimum required length of passwords.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53121: Your password does not contain the minimum number of numeric characters required**

**Cause:** The password specified did not contain the minimum number of numeric characters required.

**Action:** Specify a password that contains at least the minimum number of numeric characters required. If necessary, contact the portal administrator to confirm the minimum number of numeric characters required for passwords.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWC-53122: Your password cannot be null**

**Cause:** A null value was specified for a password.

**Action:** Specify a valid password.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53123: Your new password cannot be the same as your old password**

**Cause:** While changing a password, the new password was the same as the previous password.

**Action:** Specify a new password that is different from the previous password.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53124: Your password contains an illegal value**

**Cause:** The password specified contained one or more illegal characters.

**Action:** Specify a password that does not contain any illegal characters.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53125: Your password has expired. You should change your password soon**

**Cause:** A password has expired but the user has been allowed to login and change the password.

**Action:** Change the password as soon as possible.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53126: Your password has expired. Contact your Administrator to change your password**

**Cause:** A password has expired.

**Action:** Contact the portal administrator to change the password.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53127: A user property was not found**

**Cause:** An attempt was made to search for a property that does not exist in the directory.

**Action:** Check the property name.

**Level:** 1

**Type:** ERROR



---

**Impact:** Other

**WWC-53128: Your account has been disabled**

**Cause:** An account has been disabled.

**Action:** Contact the portal administrator and request that the account be enabled.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53129: A property was not found while searching for the property in the directory**

**Cause:** An attempt was made to search for a property that does not exist in the directory.

**Action:** Check the property name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53149: The Portal was unable to establish contact with the Oracle Internet Directory because the following connection parameters are missing:%1**

**Cause:** The connection parameters specified were not available.

**Action:** Run the command line script ptlasst in MIDTIER mode to configure the Oracle Internet Directory connection parameters: ptlasst -mode MIDTIER -type OID

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53200: The specified grantee has already been granted %1 privilege. To change the privilege of this grantee**

**Cause:** An attempt was made to add a privilege for a grantee that has already been granted a different privilege. Only a single privilege can be granted on an object to any grantee.

**Action:** Change the privilege of this grantee by selecting the appropriate privilege from the down list shown against the name of the grantee.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53201: Value specified for the limit set for total space allocated must be a positive integer.**

**Cause:** The value specified for the total space allocated was invalid.

**Action:** Specify a positive integer for the total space allocated.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWC-53202: Value specified for the limit set for maximum file size must be a positive integer.**

**Cause:** The value specified for the maximum file size was invalid.

**Action:** Specify a positive integer for the maximum file size.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53203: Value specified for the SMTP port must be a positive integer.**

**Cause:** The value specified for the SMTP port is invalid.

**Action:** Specify a positive integer for the SMTP port.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53204: Value specified for the URL connection timeout interval must be a positive integer.**

**Cause:** The value specified for the URL connection timeout interval is invalid.

**Action:** Specify a positive integer for the URL connection timeout interval.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53205: Value specified for log switch interval must be a positive integer.**

**Cause:** The value specified for the log switch interval is invalid.

**Action:** Specify a positive integer for the log switch interval.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53206: Value specified for the directory synchronization interval must be a positive integer.**

**Cause:** The value specified for the interval between DIP notifications is invalid.

**Action:** Specify a positive integer for the interval between DIP notifications.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53207: Value specified for the web cache invalidation port must be a positive integer.**

**Cause:** The value specified for the invalidation port is invalid.

**Action:** Specify a positive integer for the invalidation port.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWC-53208: Value specified for the web cache administration port must be a positive integer.**

**Cause:** The value specified for the administration port is invalid.

**Action:** Specify a positive integer for the administration port.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53209: Value specified for the maximum web cache expiry time must be a positive integer.**

**Cause:** The value specified for the maximum expiry time is invalid.

**Action:** Specify a positive integer for the maximum expiry time.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53218: Cannot set the directory synchronization parameters as the provisioning profile does not exist.**

**Cause:** An attempt was made to set directory synchronization parameters when the provisioning profile does not exist.

**Action:** Create the provisioning profile by running ptlasst using -mode MIDTIER -type DIPREG and retry.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53220: An exception occurred while creating the user account in the Oracle Internet Directory. Verify that the specified password conforms to the password policy.**

**Cause:** The password specified violated the password policy or an attribute value was invalid.

**Action:** Specify a password that complies with the password policy and retry. Contact the portal administrator if the problem persists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53221: An exception occurred while creating the user account in the Oracle Internet Directory: %1**

**Cause:** The password specified violated the password policy or an attribute value was invalid. The error message provides specific information about the cause.

**Action:** Take appropriate action based on the error message. Contact the portal administrator if the problem persists.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWC-53222: The URL contains an invalid parameter value.**

**Cause:** The value specified for the parameter in the URL is invalid.

**Action:** Provide the correct value for the parameter and re-submit the request, or log in to the Oracle Single Sign-On Server again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53314: Number of users returned exceed the search return limit. Narrow the search criteria and try again.**

**Cause:** A large number of users matched the search criteria specified.

**Action:** Change the search criteria so that a smaller number of users is returned. Alternatively, contact the portal administrator and request that the LOV size limit be increased.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53366: Number of groups returned exceed the search return limit. Narrow the search criteria and try again.**

**Cause:** A large number of groups matched the search criteria specified.

**Action:** Change the search criteria so that a smaller number of groups is returned. Alternatively, contact the portal administrator and request that the LOV size limit be increased.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-53377: The external application does not exist and may have been deleted. Update your link. If using the External Applications portlet**

**Cause:** Some of the existing external application links are no longer valid.

**Action:** Refresh the portlet so that these obsolete links are removed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-57102: To perform this action**

**Cause:** An action button was clicked without first selecting any portlets or tabs.

**Action:** Select one or more portlets or tabs before clicking an action button.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-57103: No region selected. Select a region then click %1.**

---

**Cause:** An attempt was made to copy or move an item to a page that does not have an item region.

**Action:** Create an item region, and then copy or move the item.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-57106: To perform this action**

**Cause:** An action button was clicked without first selecting any portlets, items, or levels.

**Action:** Select one or more portlets, items, or levels before clicking an action button.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-57124: Moving tabs is not allowed. Only portlets can be moved using the Move button. To reorder tabs**

**Cause:** An attempt was made to move a tab. Tabs cannot be moved between regions.

**Action:** Although tabs cannot be moved between regions, you may reorder tabs within a single tab region. To reorder tabs, click the Arrange Tabs icon in the tab region.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-57186: Page %1 is a system level cache page; no personalization is allowed.**

**Cause:** An attempt was made to personalize a page that is cached at the system level. This is not permitted because all users see the same content on such pages. Only pages that are cached at the user level (or not cached at all) can be personalized.

**Action:** To modify this page, make changes affecting all users; this requires privileges to edit the page.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-57216: Invalid number of rows. Value should be at least be 1.**

**Cause:** The value specified for the number of rows was invalid.

**Action:** Specify a positive number for the number of rows in the region.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-57239: Choose a page for the template input parameter**

---

**Cause:** Page was specified as the value type for the template input, but a page was not selected.

**Action:** Click the Browse Pages icon and choose a page for the template input.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-57267: An error occurred while configuring the page group.**

**Cause:** An attempt to configure a page group failed.

**Action:** Refresh the screen and verify that the page group is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-57268: Error while writing parameter metadata: %1**

**Cause:** An attempt to write parameter metadata failed.

**Action:** Refresh the screen and verify that the parameter is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-57269: The parent object '%1' does not have a valid ID.**

**Cause:** The parent object ID was invalid.

**Action:** Refresh the screen and verify that the parent object is still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-57270: Error during a flow link change event: %1**

**Cause:** An attempt to update a flow link failed.

**Action:** Refresh the screen and verify that the dependent pages are still available.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-57272: The reference path %1 for the portlet instance %2 is not valid.**

**Cause:** The format of the reference path was incorrect. The correct format is <id>\_<portletname>\_<providerid>.

**Action:** Specify correct values and use the correct reference path format.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-57305: Tab pages cannot be edited directly**

---

**Cause:** An attempt was made to directly edit a tab.

**Action:** Edit the page that contains the tab.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-57306: This page cannot be edited in Layout Mode**

**Cause:** An attempt was made to edit a PL/SQL, JSP, or URL page in Layout Mode. Only standard pages can be edited in Layout Mode.

**Action:** Edit the page properties from the Navigator, or edit the page content using an editor appropriate for the page type.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-57307: Invalid expiry value. Value should be at least be 1 minute.**

**Cause:** The value specified for the cache expiration time was invalid.

**Action:** Specify a positive number for the cache expiration time.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-57323: The selected portal template was not found.**

**Cause:** The selected portal template could not be found. The page may have been deleted.

**Action:** Choose another portal template.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-57324: The selected page does not contain any item placeholders.**

**Cause:** The selected page does not contain any placeholder items, so it cannot be used as a portal template.

**Action:** Choose a page that contains placeholder items.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-57331: Specify a numeric value for height.**

**Cause:** The value specified for the region height was invalid.

**Action:** Specify a number (preferably between 1 and 100) for the region height. Note that leaving this field blank is the same as entering 1.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWC-57354: Invalid timeout value. Value should be number (zero or more).**

**Cause:** The value specified for the page timeout was invalid.

**Action:** Specify a positive number for the page timeout.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-57357: In order to choose another option**

**Cause:** An attempt was made to choose another template option without first detaching the current template.

**Action:** Click Detach from Template to remove the template from the page, then proceed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-57365: The given tabstring for the page is invalid.**

**Cause:** The tabstring specified for the page is invalid.

**Action:** Specify a valid tabstring for the page.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-57381: The language specified in the URL is invalid.**

**Cause:** The URL specified contained an invalid language element, for example, it may have been null.

**Action:** Specify a different language element, or remove it completely.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-57382: The version specified in the URL is invalid.**

**Cause:** The URL specified contained an invalid version element, for example, it may have been null.

**Action:** Specify a different version element, or remove it completely.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-57383: The language specified in the URL is not currently supported by this Portal.**

**Cause:** The URL specified contained a reference to a language that does not represent a legitimate language code, or is not currently available in this portal.

**Action:** Specify a different language element, or remove it completely.



---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-57384: The URL contains a reference to a version**

**Cause:** The URL specified requested a page and a version. Oracle Portal does not support versioning of pages and cannot resolve this URL.

**Action:** Remove the version element from the URL.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-57385: The template could not be detached from the page because you do not have privileges to access one or more portlets on the template.**

**Cause:** An attempt was made to detach a template from a page, but the user does not have the privileges to access every portlet on the template. These privileges are required as, when detaching a template, the portlets on the template are copied to the page.

**Action:** Contact the portal administrator and request that the appropriate privileges be granted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-57421: Specify a numeric value for the space between items.**

**Cause:** The value specified for the Space between Items field was invalid.

**Action:** Specify a number (preferably between 1 and 100) for the Space between Items field. If you do not want any space between items, specify 0 or null.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-57422: Specify a numeric value for the space around items.**

**Cause:** The value specified for the Space around Items field was invalid.

**Action:** Specify a number (preferably between 1 and 100) for the Space around Items field. If you do not want any space around items, specify 0 or null.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWC-57436: Invalid item attribute parameter name \"%1\"**

**Cause:** The specified item attribute parameter name was invalid.

**Action:** Specify a valid item attribute parameter name.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWC-59083: Unable to get SSO login configuration from mod\_osso**

**Cause:** The operation to retrieve the SSO login configuration from mod\_osso failed.

**Action:** Check that the Oracle AS Portal middle tier mod\_osso is properly registered with an Oracle SSO server.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

## WWS-18000 to WWS-33951

**WWS-18000: Document written successfully but the annotation failed.**

**Cause:** The write operation of the file completed, but the comments for it failed.

**Action:** Check the WebDAV error file in your Personal Page for possible reasons why this occurred.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18001: %1**

**Cause:** A re-direct required to get to the requested collection has failed.

**Action:** Check that the re-directed URL is valid and WebDAV is setup correctly for this portal.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18002: The document %1 cannot be located**

**Cause:** The requested document did not exist in the location specified.

**Action:** In Oracle Portal, check whether the document is accessible. If it is accessible, there is an internal error. Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18003: No such lock token %1 is associated with document ID %2**

**Cause:** No lock was associated with this resource.

**Action:** To create a lock, check it out using the lock command.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18004: User not authorized to perform the requested operation**

**Cause:** An attempt was made to perform an operation but the user does not have the necessary privileges to perform the task.

---

**Action:** If applicable, contact the portal administrator and request that privileges be granted to perform such operations.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18005: Driver versions do not match**

**Cause:** The version of the OraDAV module on the middle tier and its database counterpart do not match.

**Action:** Check your installation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18006: Unknown driver parameter: %1**

**Cause:** The version of the OraDAV module on the middle tier and its database counterpart do not match.

**Action:** Check your installation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18007: Invalid argument: %1**

**Cause:** The argument value specified is not valid.

**Action:** Check that the values supplied for all arguments are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18008: The requested operation is prohibited on the specified document.**

**Cause:** An attempt to perform an operation on a document failed.

**Action:** Check the permissions of the user, security on the document, and the status of the document.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18009: Supplied container version %1 does not match %2 for %3**

**Cause:** The version of the OraDAV module on the middle tier does not match the drivers in the database.

**Action:** Check the installation and ensure that all necessary patches have been applied.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWS-18010: Document %1 is locked.**

**Cause:** The document requested was checked out.

**Action:** Check in or undo the check out for the document to release the lock.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18011: The document exists but is not the expected type.**

**Cause:** The document found was a file when a directory was expected. Or, the document found was a directory when a file was expected.

**Action:** Check that the operation attempted is valid for this type of resource.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18012: ROWID %1 from %2 is already exposed.**

**Cause:** The document specified is already exposed to the client.

**Action:** No action is required, as the document is already exposed to the client.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18014: The collection %1 already contains non-external data.**

**Cause:** The directory specified exists and is not empty.

**Action:** Check the WebDAV error file in your Personal Page for possible reasons why this error occurred.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18017: A WebDAV table is corrupt.**

**Cause:** One of the internal WebDAV tables contains invalid data.

**Action:** Use the DAV Loader utility, `wwday_loader`, to repopulate the WebDAV tables with the latest data available from OracleAS Portal.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18018: The log file is already open.**

**Cause:** An attempt to open a log file failed as it was already open.

**Action:** If necessary, close the log file.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWS-18019: Some objects being dropped do not exist.**

**Cause:** An attempt was made to drop repository objects but some of the objects do not exist.

**Action:** Check your installation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18020: %1 already exists.**

**Cause:** The specified resource already exists.

**Action:** Check the WebDAV error file in your Personal Page for possible reasons why the error occurred.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18024: %1 does not exist.**

**Cause:** The specified resource was not found.

**Action:** Check the WebDAV error file in your Personal Page for possible reasons why this error occurred.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18025: %1 in storage area %2 is currently in use for storage and therefore cannot be deleted.**

**Cause:** An attempt to delete a resource failed because the requested resource was open and in use.

**Action:** Ensure that the resource is not in use before attempting to delete it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18026: %1**

**Cause:** An internal error has occurred.

**Action:** Check the WebDAV error file in user's Personal Page for possible reasons why this error occurred.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18027: Cannot return a multistatus response.**

**Cause:** An error occurred while trying to return a multistatus response for the requested operation.

---

**Action:** Check the WebDAV error file in the Personal Page and the Oracle HTTP Server error log file for possible reasons why this error occurred.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18028: Cannot upload document as quota was exceeded.**

**Cause:** An attempt to upload a document failed. The size quota permitted was exceeded.

**Action:** Check the page group quota and if necessary, free up some space.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18029: The requested operation is forbidden.**

**Cause:** An attempt to perform an operation failed.

**Action:** Check the permissions of the user and also whether this operation is permitted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18067: User %1 does not have a personal page in which the WebDAV error message log file can be created.**

**Cause:** No Personal Page was found for the logged in user.

**Action:** Create a Personal Page for this user, into which the WebDAV error log file can be placed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18068: The personal page for %1 does not include an item region in which the WebDAV error message log file can be created.**

**Cause:** No item region was available on the Personal Page for the logged in user.

**Action:** Create an item region on the Personal Page for this user, in which the WebDAV error log file can be placed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18070: There is no item in which to store error messages.**

**Cause:** A WebDAV error log file item does not exist.

**Action:** Create the WebDAV error log file item in the user's Personal Page.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWS-18072: An exception has occurred that was not anticipated: %1**

**Cause:** An internal error occurred.

**Action:** Check the WebDAV error log file in the user's Personal Page. for possible reasons why this error occurred. Also check the Apache error log file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18073: An exception occurred while creating or referencing the required preference.**

**Cause:** The preference required for the WebDAV error log file was not created.

**Action:** Check the Apache error log file for possible reasons why this error occurred.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18075: The default region of page %1 is incompatible with the object type being placed in it.**

**Cause:** The default region type did not allow file types to be placed in it.

**Action:** Check the value of the region type and ensure it allows file types to be uploaded.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18076: The error log item for user %1 cannot be used. It may not exist**

**Cause:** An attempt to write to the WebDAV error log file failed. Either the WebDAV error log file does not exist, cannot be found, or cannot be created.

**Action:** Check whether the WebDAV error log exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18077: No file-based item types are available. File upload via WebDAV is not available in this page group.**

**Cause:** No file-based or image based item types were specified for the page group.

**Action:** Select some allowable item types for the page group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18085: Expecting data to be returned from query using condition %1**



---

**Cause:** An internal error occurred.

**Action:** Check the WebDAV error file in the user's Personal Page for possible reasons why this error occurred.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18086: An internal module call has been made using an invalid or inconsistent set of parameters. module: %1**

**Cause:** It was not possible to create the WebDAV error log file as the user name was not supplied.

**Action:** Check the Apache error log file for possible reasons why this error occurred.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18087: An error occurred during the %1 for %2.**

**Cause:** The attempted operation failed to complete.

**Action:** Check the WebDAV error file in the user's Personal Page for possible reasons why this error occurred.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18088: An error occurred during the %1 from %2 to %3.**

**Cause:** The attempted operation failed to complete.

**Action:** Check the WebDAV error file in the user's Personal Page for possible reasons why this error occurred.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18089: An error occurred during the %1 operation.**

**Cause:** The attempted operation failed to complete.

**Action:** Check the WebDAV error file in the user's Personal Page for possible reasons why this error occurred.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18090: Cannot create a lock with scope %1 on the given resource of type %2. Shared or S locks are not permissible and collections or C cannot be locked.**

**Cause:** The attempted operation failed to complete.

**Action:** Check the WebDAV error file in the user's Personal Page for possible reasons why this error occurred.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18091: Updating the last-modified date for %1 failed**

**Cause:** It was not possible to update the last modified date as it is not a directory.

**Action:** Check the WebDAV error file in the user's Personal Page for possible reasons why this error occurred.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18092: Deleting the root path or top level directory is not allowed.**

**Cause:** The attempted operation is not permitted.

**Action:** The root path or top level directory cannot be deleted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18093: Writing to the root directory is not allowed.**

**Cause:** The attempted operation is not permitted.

**Action:** Writing to the root directory cannot be done.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18094: Moving %1 to %2 with destination name %3 fails. Moving resources across page groups is not allowed.**

**Cause:** An illegal operation was attempted.

**Action:** Resources cannot be moved across page groups.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18095: Copying %1 to %2 with destination name %3 failed. Copying resources across page groups is not allowed.**

**Cause:** The attempted operation is not permitted.

**Action:** Resources cannot be copied across page groups.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18096: The name %1 in path %2 contains slashes**

**Cause:** This name cannot contain slashes.

**Action:** Remove the slashes from the name.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18097: The creation of %1 failed**

**Cause:** The attempted operation failed to complete.

**Action:** Check the WebDAV error file in the user's Personal Page for possible reasons why this error occurred.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18098: The resource is already exclusively locked.**

**Cause:** The document specified is checked out.

**Action:** Check in or undo the check out for the document to release the lock.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18099: The resource cannot be locked because it is a collection. Collections cannot be checked out and locked.**

**Cause:** An attempt was made to check out a directory but this is not supported.

**Action:** Do not check out a directory, as it is not permitted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18100: Insufficient write permissions on the folder.**

**Cause:** An attempt was made to modify a directory but the user did not have sufficient privileges.

**Action:** If applicable, contact the portal administrator and request that privileges be granted to perform this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18101: WebDAV Path not found :**

**Cause:** The resource cannot be found in the underlying tables.

**Action:** Check the WebDAV error file in the user's Personal Page for possible reasons why this error occurred. Also check the Apache error log file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18102: Cannot validate at the given depth %1.**

---

**Cause:** It is not possible to check for locks at the given level in the directory hierarchy.

**Action:** Check the WebDAV error file in the user's Personal Page for possible reasons why this error occurred. Also check the Apache error log file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18103: It is not possible to perform the %1 operation on version zero of a document (dav-id = %2). This version is a placeholder for the first complete version of the document**

**Cause:** The attempted operation failed. It is not possible to perform any operations on this resource until it has been submitted to the approval system.

**Action:** To allow modifications, submit it to the approval system and approve it, if the user is not an approver or owner of the document.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18104: There is not yet a complete initial version of this document; it is still being edited or reviewed. It will become available for general use once it has been approval.**

**Cause:** The attempted operation failed. It is not possible to perform any operations on this resource until it has been submitted to the approval system.

**Action:** Wait until the document has been submitted to the approval system.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18105: OracleAS Portal has checked for the existence of WebDAV locks on the resource with dav-id = %1**

**Cause:** The attempted action required implicitly or explicitly that a WebDAV resource be moved or removed, for example, a file or image item. The operation failed because this resource was locked, either by a WebDAV client, or has been checked out. When a resource is locked, it indicates that someone is actively using the resource and therefore it is not appropriate to move or remove the resource.

**Action:** Determine why the item is locked or checked out and, if safe to do so, unlock or check in the item and attempt the operation again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18121: The requested menu action is invalid.**

**Cause:** A menu action specified in the request that is not supported by this portal.

**Action:** Ensure that the Portal WebDAV URL is pointing to the correct address.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WWS-18122: The access control list is not allowed for this document.**

**Cause:** Item Level Security is not enabled on this document.

**Action:** Contact your portal administrator. Request that Item Level Security is enabled on the document for which access control is required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18123: Unknown error occurred while processing the menu request.**

**Cause:** An internal error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18131: The operation %1 has been attempted on a resource**

**Cause:** An attempt was made to update a resource that is pending approval. The version in the approval process remains locked until it is either rejected or approved.

**Action:** Wait for the resource to be approved or rejected and attempt the operation again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18132: Locked: %1**

**Cause:** The given path is locked in WebDAV possibly because the resource is in use or pending approval.

**Action:** Attempt the operation again once all locks have been removed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18133: The itemtype used for uploading content from DAV has mandatory fields which cannot be set from WebDAV.**

**Cause:** The item type which has been chosen in the page properties for the type of file being uploaded has mandatory fields with no default values. It is not possible to upload items of this type from WebDAV as these fields cannot be set by the WebDAV Client.

**Action:** Either make these fields optional in the item type properties, specify a default value for these fields in the item type properties, or change the item type used for uploading files of this type in the page properties.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WWS-18136: The Approval/Rejection operation is not allowed for this document.**

**Cause:** The document is not pending approval.

**Action:** Check that Workflow is enabled and the document is submitted for Approval/Rejection.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18137: You do not have permission to Approve or Reject this document**

**Cause:** You are not an approver or owner of, nor do you have have manage content or administration privileges for this document.

**Action:** Make sure that you are logged on as a user who has permission to perform this operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18138: The page does not include an editable item region to upload the file.**

**Cause:** No editable item region was available on the page.

**Action:** Create an editable item region on the page or mark an existing one as editable.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18139: Sorry**

**Cause:** The document is not in draft status.

**Action:** Check that Workflow is enabled and the document is in draft status.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-18140: Syncing of the Item types for WebDAV Upload in the imported page has not been performed.**

**Cause:** The WebDAV item types selected for use in the imported page could not be updated to reflect the new settings in the portal.

**Action:** In the page properties of the imported page, set the WebDAV itemtype settings to the desired values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-19679: The item is already approved.**

---

**Cause:** The item cannot be approved or rejected because it has already been approved.

**Action:** Refresh your browser window to update your notifications. The item you were trying to approve or reject will no longer be listed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-19680: Item has been rejected!**

**Cause:** The item cannot be approved or rejected because it has already been rejected.

**Action:** Refresh your browser window to update your notifications. The item you were trying to approve or reject will no longer be listed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-19699: You do not have permission to view this item.**

**Cause:** Viewing the item required an appropriate privilege.

**Action:** Ask the page group administrator or page manager to grant you the appropriate privilege.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-19722: There are pending approvals in this routing process; the step cannot be moved.**

**Cause:** The change was rejected because the approval process definition had items pending approval.

**Action:** Wait until all the pending items are approved, then try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-19746: You have entered invalid values for the number of notification items**

**Cause:** A non-numeric value was entered.

**Action:** Enter a valid number value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-20331: You must first specify an HTML Content Layout.**

**Cause:** No valid HTML Content Layout was selected.

**Action:** Select an HTML Content Layout from the list or create one first if there is none available in the list.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-20369: Webcache could not access <a href=\"%1\">this URL</a>**

**Cause:** An exception was raised by the <esi:include> tag while fetching the contents of this item. Typically, this is because the item's URL is not accessible from the Web cache.

**Action:** Verify that the URL is valid and accessible from your browser. If the Web page displays properly, then verify the proxy settings in the Web cache. Note that URLs that require HTTP authentication headers are not supported.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22200: The value entered is invalid. Choose a valid value from the LOV.**

**Cause:** The value entered is not one of the values from the LOV.

**Action:** Enter a valid value from the LOV.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22201: You cannot copy the item because the category to which it belongs does not exist in the destination page group.**

**Cause:** The category that the item belongs to does not exist in the destination page group.

**Action:** Re-create the category in the destination page group or assign the item to a shared category.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22202: You cannot copy the item because one or more of the perspectives associated with it does not exist in the destination page group.**

**Cause:** The perspective attached to the item does not exist in the destination page group.

**Action:** Re-create the perspective in the destination page group, detach the perspective from the item, or attach a shared perspective to the item.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22203: You cannot move the item because the category to which it belongs does not exist in the destination page group.**

**Cause:** The category that the item belongs to does not exist in the destination page group.



---

**Action:** Re-create the category in the destination page group or assign the item to a shared category.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22204: You cannot move the item because one or more of the perspectives associated with it does not exist in the destination page group.**

**Cause:** The perspective attached to the item does not exist in the destination page group.

**Action:** Re-create the perspective in the destination page group, detach the perspective from the item, or attach a shared perspective to the item.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22208: The message cannot be added to the queue as the queue does not exist.**

**Cause:** The specified queue does not exist.

**Action:** Create the queue before attempting to add a message to the queue.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22209: The height value is invalid. Value should be at least 1 pixel.**

**Cause:** An invalid value was entered for the portlet height.

**Action:** Enter a positive number for the portlet height.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22210: Item is not checked out.**

**Cause:** The item types for WebDAV upload in the imported page are not synchronized

**Action:** Check out the item, make the necessary changes, then check it in.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22211: Item is not enabled for check-out.**

**Cause:** An attempt was made to check out an item that was not enabled for checkout.

**Action:** Enable the item for check-out, then check out the item.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWS-22212: The image that you are trying to reference does not exist.**

**Cause:** The image does not exist in the Oracle Application Server Metadata Repository.

**Action:** Supply an image that does exist.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22213: An invalid path was supplied to the Default Content attribute.**

**Cause:** The path supplied to the core attribute was invalid.

**Action:** Select a value from the LOV or supply a valid value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22214: An invalid path was supplied to the Item Link attribute.**

**Cause:** The path supplied to the core attribute was invalid.

**Action:** Select a value from the LOV or supply a valid value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22215: An invalid number was entered for the version number attribute.**

**Cause:** The number supplied to the version number attribute was either not greater than zero or is a value that has already been used up by an existing version.

**Action:** Supply a positive number that is unique across this item.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22216: Portal ESE Search : The portal event is acting on an object that cannot be found.**

**Cause:** The portal event handler is trying to find the object being processed, but it cannot be found.

**Action:** Check your configuration. If you cannot resolve this issue, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22217: Privileges cannot be assigned to the PUBLIC user.**

**Cause:** An attempt was made to assign an item level privilege to the PUBLIC user. This is not allowed.

---

**Action:** Assign the item level privilege to users and groups other than PUBLIC.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22218: Another user is drafting an update of this item. Wait to update until that draft is published or deleted.**

**Cause:** An attempt was made to update an item for which a draft version existed, although only one draft version of an item can exist.

**Action:** Wait until that draft is published or deleted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22219: An attempt was made to unzip an item that is pending approval or has a draft version. You must wait until the item is approved or rejected**

**Cause:** An attempt was made to unzip an item that is pending approval or is a draft item.

**Action:** If it is an item that is pending approval, unzip it after it is approved or rejected. If it is a draft item, unzip it after it is published or deleted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22220: Invalid portlet caching period. Value should be at least 1 minute.**

**Cause:** You entered an invalid value for the portlet caching period.

**Action:** Enter a portlet caching period of at least 1 minute.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22221: The delete or purge did not succeed. The item or one of its associated sub-items is checked out by another user.**

**Cause:** An item cannot be deleted or purged when the item or one of its associated sub-items is checked out by another user.

**Action:** Wait to perform the action until the other user checks in the item or its associated sub-item.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22222: You cannot modify the Access Settings of an item on a page that is cached at the system level.**

**Cause:** You attempted to modify the access settings of an item on a page cached at the system level, which affects all users. Item Level Security is disabled for pages cached at the system level.

---

**Action:** If you require Item Level Security on this item, then choose a different caching option for the page. Choose either user-level caching or no caching.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22223: This item does not have any translatable attribute and hence**

**Cause:** You attempted to edit an item that does not have any translatable attribute in the nondefault language.

**Action:** Edit the item in the default language of the page group and make the necessary changes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22224: An attempt was made to set an invalid publish date.**

**Cause:** The publish date for an item must be immediately or anytime greater than 2 minutes from immediately. For example, if the publish date is currently today at 12:00, and the publish date is set for today at 12:02, an exception is thrown and this error message is rendered.

**Action:** Reset the item's publish date to either immediately or more than 2 minutes from immediately.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22225: You cannot copy the page because the HTML template used by one of the regions of the page or its sub-pages is not from the Shared Objects page group.**

**Cause:** The HTML template used by a region on the page or its sub-pages is not from the Shared Objects page group.

**Action:** Move the HTML template to the Shared Objects page group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22226: Item type cannot be deleted because items are based on it.**

**Cause:** Deleting an item type also deletes all items that are based on the type. Though you may have permission to delete item types, you do not have permission to delete specific items.

**Action:** Verify that only non-essential content is based on the item type. Obtain the required privilege level to delete items. Then, try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22227: Page type cannot be deleted because pages are based on it.**

---

**Cause:** Deleting a page type also deletes all pages that are based on the type. Though you may have permission to delete page types, you may not have permission to delete specific pages.

**Action:** Verify that only non-essential pages are based on the page type. Obtain the required privilege level to delete pages. Then, try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22228: The action cannot be completed because a sub-item of the item has a status of Pending.**

**Cause:** The item you tried to modify has one or more sub-items pending approval. You cannot perform this action on items with sub-items that are pending approval.

**Action:** Complete the approval process on the sub-item and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22229: Copy cannot be completed because a sub-item of the item has a status of Pending.**

**Cause:** The item you tried to copy has one or more sub-items pending approval. You cannot copy items with sub-items that are pending approval.

**Action:** Complete the approval process on the sub-item and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22230: Move cannot be completed because a sub-item of the item has a status of Pending.**

**Cause:** The item you tried to move to another page has one or more sub-items pending approval. You cannot move items to another page when they have associated sub-items that are pending approval. However, you can move such items within the same page.

**Action:** Complete the approval process on the sub-item and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22231: Delete cannot be completed because a sub-item of the item has a status of Pending.**

**Cause:** The item you tried to delete has one or more sub-items pending approval. You cannot delete items with sub-items that are pending approval.

**Action:** Complete the approval process on the sub-item and try again.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWS-22232: The attribute display type cannot be changed from a multi-line to a single-line because items are based on the item type that uses this attribute.**

**Cause:** An attempt was made to switch an attribute from a multi-line to a single-line display type. This action was prevented because items exist that are based on the item types that use this attribute. This action can be completed successfully only after the attribute has been detached from the item types that use it.

**Action:** Detach the attribute from the item types that use it, and try again. Detaching an attribute from an item type means that all items based on the type lose the values that were entered for the attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22233: Copy cannot be completed because a sub-item of an item on the page has a status of Pending.**

**Cause:** An attempt was made to copy a page containing items with sub-items pending approval.

**Action:** Complete the approval process on the sub-items, and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22234: Deleted items cannot be unzipped. Undelete the item to unzip it.**

**Cause:** An attempt was made to unzip a deleted item.

**Action:** Unzip the item after it is undeleted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22235: %1 does not exist.**

**Cause:** The object cannot be found in the transport set.

**Action:** Export the transport set again, including this required object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22236: BPEL process name cannot be null.**

**Cause:** An attempt was made to create or edit a BPEL process without specifying a name.

**Action:** Enter a name for the BPEL process.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWS-22237: BPEL process deployment location cannot be null.**

**Cause:** An attempt was made to create or edit a BPEL process without specifying its process deployment location.

**Action:** Enter the deployment location for the BPEL process.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22238: BPEL process WSDL location cannot be null.**

**Cause:** An attempt was made to create or edit a BPEL process without specifying its WSDL location.

**Action:** Enter the WSDL location for the BPEL process.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22239: BPEL process operation cannot be null.**

**Cause:** An attempt was made to create or edit a BPEL process without specifying its operation.

**Action:** Enter the operation for the BPEL process.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22240: This BPEL process name is already used. Use another name.**

**Cause:** An attempt was made to create or edit a BPEL process with a name that is already being used for another BPEL process.

**Action:** Enter a different, unique name for BPEL process.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22241: The specified BPEL process is not available.**

**Cause:** A process was specified that did not exist.

**Action:** Specify a different process.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22242: Specify a name without spaces or special characters.**

**Cause:** The name entered contains invalid characters.

**Action:** Specify a valid name. Valid characters are [A-Z], [a-z], [0-9] and "\_".

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWS-22243: Specify a description that does not contain the following characters:** \ / : \* ? \" < > |

**Cause:** The description entered contains invalid characters.

**Action:** Specify a valid description. The description may not contain the following characters: \ / : \* ? \" < > | , & # %

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22244: Specify a valid deployment location.**

**Cause:** The deployment location entered is not a valid URL.

**Action:** Specify a valid URL for deployment location.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22245: Specify a valid process WSDL location.**

**Cause:** The process WSDL location entered is not a valid URL.

**Action:** Specify a valid URL for process WSDL location.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22246: Specify an operation without spaces or special characters.**

**Cause:** The operation entered contains invalid characters.

**Action:** Specify a valid operation. Valid characters are [A-Z], [a-z], [0-9] and "\_".

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22247: BPEL process that you are editing is not editable.**

**Cause:** The process specified is no longer editable. This process is being used by one or more pages or page groups.

**Action:** Remove its associations with pages and page groups and try again

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22248: BPEL process that you are removing is not removable.**

**Cause:** The process specified can not be removed. This process is being used by one or more pages or page groups.

**Action:** Remove its associations with pages and page group and then try again.

**Level:** 1



---

**Type:** ERROR

**Impact:** Other

**WWS-22249: Add Tab cannot be completed because the region contains an item that has a sub-item with status of Pending.**

**Cause:** An attempt was made to add a tab to a region where one or more items had sub-items pending approval.

**Action:** Complete the approval process on the sub-item and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22250: Process WSDL Location is not valid.**

**Cause:** The URL specified in the WSDL Location is not reachable.

**Action:** Check if the URL specified is reachable through the proxy configured in Portal Global Settings. If the URL is SSL enabled, then check for the valid certificates in the database wallet.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22251: Process Name not found in specified WSDL location.**

**Cause:** Process Name not found in specified WSDL location.

**Action:** Ensure that the process name given is associated with the WSDL.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22252: Process Deployment Location not found in specified WSDL location.**

**Cause:** Process Deployment Location not found in specified WSDL location.

**Action:** Ensure that the Process Deployment Location is associated with the WSDL.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22253: Process Operation not found in specified WSDL location.**

**Cause:** Process Operation not found in specified WSDL location.

**Action:** Ensure that the Operation Name is associated with the WSDL.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22254: Unexpected error in processing input parameters - %1.**

**Cause:** Unexpected error in processing input parameters.

---

**Action:** Refer database error messages guide for detailed information on the error.If the same error persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22255: BPEL is not configured for this instance. Check the Administrator's guide for steps to enable it.**

**Cause:** BPEL is not enabled for this portal instance.

**Action:** Refer Administrator's guide on how to enable BPEL.This is a post install step and needs to be performed manually.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22257: URL supplied not a callback URL.Portal Callback URL construct is like protocol://host:port/bpel/WSPortalApproval.**

**Cause:** URL supplied is not a callback URL.Enter proper Portal Callback URL and then register.

**Action:** Portal Callback URL construct is like protocol://host:port/bpel/WSPortalApproval.If callback webservice is not deployed yet check Administrator's guide for steps to deploy it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22258: Datasource connection maintained for the Callback Webservice is not pointing to %1\_APPROVAL schema.**

**Cause:** Datasource connection maintained for the Callback Webservice at the WLS is not pointing to proper APPROVAL schema.

**Action:** Check Administrator's guide for steps to maintain the connection.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22260: The value entered for the plsql code exceeds the 2000 characters limit. Please reduce it and try again.**

**Cause:** The size of the plsql content entered was exceeding 2000 characters.

**Action:** Reduce the content to be less than or equal to 2000 characters.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22507: Item does not exist.**

**Cause:** An action was attempted on an item that no longer exists.

**Action:** Refresh the page so that it displays the current content.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22517: An error has occurred while rendering the URL associated with the page. %1**

**Cause:** An error occurred while redirecting to the URL associated with the current page.

**Action:** Check the validity of the URL associated with the current page.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22518: An error has occurred while executing the PL/SQL associated with the page. %1**

**Cause:** The PL/SQL code associated with the current page executed with errors.

**Action:** Check the validity of the PL/SQL code that executes when the current page is viewed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-22519: The attribute does not exist.**

**Cause:** No value was found for the custom attribute associated with the current page.

**Action:** Edit the properties for the current page, and provide values for the custom attributes associated with it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-23017: Invalid search pattern specified**

**Cause:** A null value is specified for the search pattern.

**Action:** Specify a non-null value for the search pattern.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-25824: The specified name is already in use.**

**Cause:** The category/perspective name entered is not unique within this namespace.

**Action:** Enter a unique category/perspective name, one that is not used by another category, perspective, page or tab with the same parent.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWS-25827: This portlet cannot search any of the submitted page groups.**

**Cause:** A search submission portlet submitted a search to a search results portlet. The results portlet is customized to show results from a specific set of page groups and these do not include any of the page groups chosen in the submission portlet.

**Action:** Change the list of page groups chosen for the submission portlet or those chosen for the results portlet so that both portlets refer to a common set of page groups.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-25828: This portlet cannot search all the submitted page groups.**

**Cause:** A search submission portlet submitted a search to a search results portlet. The page groups selected for the results portlet were not all the same as those selected for the submission portlet. Only those page groups common to the submission portlet and the results portlet were searched.

**Action:** Change the list of page groups chosen for the submission portlet or those chosen for the results portlet so that both portlets refer to a common set of page groups.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-25829: This portlet cannot search any of the default page groups from the submitted portlet.**

**Cause:** A search submission portlet submitted a search to a search results portlet. The submission portlet searched a list of page groups that were chosen as the defaults for that portlet. The results portlet is customized to show results from a different set of page groups, none of which were common to the submission portlet.

**Action:** Change the default list of page groups for the submission portlet, or change the customizations in the Edit Defaults of the results portlet, so that both portlets refer to a common set of page groups.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-25830: This portlet cannot search all of the default page groups from the submitted portlet.**

**Cause:** A search submission portlet submitted a search to a search results portlet. The page groups identified for the submission portlet are different to those identified for the results portlet. Only the page groups common to the submission portlet's default page groups and the result portlet's customizations are searched.

**Action:** Change the default list of page groups for the submission portlet, or change the customizations in the Edit Defaults of the results portlet, so that both portlets refer to a common set of page groups.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WWS-25838: The expiry time must be an integer value between 1 and 1440 minutes.**

**Cause:** An expiry time was specified that is not an integer between 1 and 1440 minutes.

**Action:** Enter an expiry time that is an integer between 1 and 1440 minutes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-25845: The number of saved searches to display must be a number.**

**Cause:** The value for the number of saved searches to display was invalid, it must be a number.

**Action:** Specify the number of saved searches to display

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-25883: Some or all of the Oracle Text indexes are missing or invalid. Oracle Text searching is disabled.**

**Cause:** Oracle Text search capabilities could not be used because not all the Oracle Text indexes were present and valid.

**Action:** Ensure that the Oracle Text indexes are present and valid. If necessary, create or re-create these indexes. For more information, refer to the Oracle Portal Configuration Guide.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-25902: An error occurred while creating Oracle Text object %1.**

**Cause:** Oracle Text encountered an error while creating the preference or section group.

**Action:** Review the diagnostics logs for other messages. Correct these errors, then try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-25903: An error occurred while dropping Oracle Text object %1.**

**Cause:** Oracle Text encountered an error while removing the preference or section group.

**Action:** Review the diagnostics logs for other messages. Correct these errors, then try again.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWS-25907: %1 cannot be used in search criteria.**

**Cause:** The specified search attribute does not exist in the Oracle Text indexes.

**Action:** The Oracle Text indexes need to be updated to include the new attribute. Oracle Text indexes are updated automatically. Either wait until the indexes are updated, or use a different search attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-25934: The search query contained invalid query syntax: %1**

**Cause:** This usually occurs when a Query Language operator was used and the search expression contained invalid Oracle Text syntax.

**Action:** Correct the query language syntax.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-25976: The basic search results page is missing.**

**Cause:** The page selected to display results from Basic Search portlets and Basic Search Box items is missing.

**Action:** Specify a valid page for basic search results in the Search tab of the Global Settings screen.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-25977: The search results page is missing.**

**Cause:** The page selected to display results from Advanced, Custom and Saved Search portlets was missing.

**Action:** Specify a valid page in the Search tab of the Global Settings screen.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-25978: The destination page for Advanced Search links is missing.**

**Cause:** The destination page selected for Advanced Search links is missing. Links to advanced search pages cannot be displayed.

**Action:** Specify a valid page for Advanced Search links in the Search tab of the Global Settings screen.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-25979: Page selected to display search results is missing.**

---

**Cause:** The page selected to display results from this search portlet is missing.

**Action:** Edit the defaults of this portlet and specify a valid search results page in the Results Display tab.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-25980: Display name for the saved search is missing**

**Cause:** A display name for the saved search has not been provided.

**Action:** Enter a display name for the saved search.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-25981: You do not have permission to view this item.**

**Cause:** Viewing the item required an appropriate privilege.

**Action:** Ask the page group administrator or page manager to grant you the appropriate privilege.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-25982: A search parameter value is invalid.**

**Cause:** A value specified for a search parameter in the URL is incorrect.

**Action:** Specify a valid value for the search parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-25983: You do not have access to this page.**

**Cause:** You need to be logged in to access this page.

**Action:** Log in to Oracle Portal as a valid user.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-25984: No HTML content to display.**

**Cause:** The file was either empty or could not be displayed as HTML.

**Action:** Verify that the file item has a format that can be displayed as HTML.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-25985: No Themes to display.**

---

**Cause:** The file was either empty or Oracle Text could not extract themes from the content.

**Action:** Verify that the file item has a format that can be processed by Oracle Text.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-25986: No Gists to display.**

**Cause:** The file was either empty or Oracle Text could not extract gists from the content.

**Action:** Verify that the file item has a format that can be processed by Oracle Text.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-26000: Oracle Text Base URL cannot be null.**

**Cause:** No value is specified for the Oracle Text Base URL.

**Action:** Specify a value for the Oracle Text Base URL. Typically, this is the URL to the Portal instance, up to and including the Portal DAD. For example, `http://hostname.domain:port/pls/dad/`.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-26001: Link text for Internet Search Engine cannot be null if a URL is specified.**

**Cause:** A URL was specified for the Internet Search Engine, but link text was not specified.

**Action:** Specify link text for the Internet Search Engine.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-26119: Unable to render XML Schema Document.**

**Cause:** An internal error caused the generation of the requested XSD to fail.

**Action:** Check your configuration. If you cannot resolve the issue, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-26120: Resource Not Found**

**Cause:** Either 1. The Resource has been deleted or moved during the operation and so can no longer be found, or 2. The configuration of the Web server listener is not correct.



---

**Action:** This error is expected to occur infrequently if the Portal is being used to move or delete content while the Search Engine is indexing content. If this occurs frequently, check your configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-26121: Permission Denied**

**Cause:** You cannot perform this action because of one of the following reasons: 1. The Search Engine has not authenticated with Oracle Internet Directory and secure crawl is enabled, or 2. Secure crawling is disabled and the requested resource is not public, or 3. The configuration of the Web server listener is not correct

**Action:** Check the secure crawling configuration in the Global Settings and whether the Search Engine has authenticated with Oracle Internet Directory successfully, if applicable. If this is still not solved and the requested resource is accessible through the Portal UI to an unauthenticated user, check your configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-26122: Internal Exception in top level Crawler Procedure**

**Cause:** An internal error has caused the entry point to the XML generation to fail.

**Action:** Check your configuration. If you cannot resolve the issue, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-26123: Unexpected Exception while rendering XML**

**Cause:** An internal error has caused the code which outputs the XML to fail.

**Action:** If you cannot resolve the issue, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-28652: The bulk action cannot be performed on all the selected objects.**

**Cause:** One or more of the selected objects did not meet the required conditions for the action to be performed.

**Action:** Ensure that the objects are in the correct state, and have the correct permissions applied to them so that the required action can be performed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30071: Item %1 from page group %2 is not a valid image.**

---

**Cause:** The item specified is not a valid image.

**Action:** Choose a valid image.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30074: The value for results per page must be an integer greater than zero.**

**Cause:** A value specified for the results-per-page is not an integer greater than zero.

**Action:** Specify a value for the results-per-page that is an integer greater than zero.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30502: The page ID does not exist.**

**Cause:** The page that this item belongs to does not exist.

**Action:** Refresh the page, and try to edit the item again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30518: The item ID does not exist.**

**Cause:** This item does not exist.

**Action:** Refresh the page, and try to edit the item again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30529: You must specify a valid Style name.**

**Cause:** This error occurs when an internal API is called to retrieve a style setting value and the setting name or its type are not provided.

**Action:** Provide the setting name and type.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30534: You cannot move a page into itself.**

**Cause:** An attempt was made to make a page the sub-page of itself.

**Action:** Choose another page as the parent of the page.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWS-30535: You cannot move the root page of a page group.**

**Cause:** Moving the root page of a page group is not permitted.

**Action:** Consider moving each of the root page's sub-pages, or creating a new page group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30538: Another user has updated the value of this item.**

**Cause:** This error occurs when one user attempts to update page group properties at the same time as another user.

**Action:** Close the page group properties screen, then reload it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30541: Specify a name.**

**Cause:** A name was not provided.

**Action:** Make sure that the Name field is not left blank.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30542: Specify a display name.**

**Cause:** A display name was not provided.

**Action:** Make sure that the Display Name field is not left blank.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30558: An error occurred while executing the PL/SQL associated with the item. %1**

**Cause:** The PL/SQL code associated with the item executed with errors.

**Action:** Check the validity of the PL/SQL code that executes when the item is viewed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30563: You cannot copy the page because the category used by the page or its sub-pages is not from the Shared Objects page group.**

**Cause:** The category used by the page or its sub-pages is not from the Shared Objects page group.

**Action:** Move the category to the Shared Objects page group.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WWS-30573: You do not have permission to perform this operation.**

**Cause:** The user does not have permission to perform this operation.

**Action:** Make sure that you are logged on as the user who has permission to perform the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30582: You cannot copy the page because the style used by the page or its sub-pages is not from the Shared Objects page group.**

**Cause:** The style used by the page or its sub-pages is not from the Shared Objects page group.

**Action:** Move the style to the Shared Objects page group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30584: The action cannot be completed because the value entered for the TEXT attribute is too large.**

**Cause:** The value entered for the TEXT attribute exceeds 32 KB.

**Action:** Enter a text value that does not exceed 32 KB.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30586: The item name must be unique in this page.**

**Cause:** The name specified for the item is not unique.

**Action:** Specify a name that is unique across all the items on this page as well as all the tabs and sub-pages of this page.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30589: A category with the specified name already exists in this namespace.**

**Cause:** The category name entered is not unique within this namespace.

**Action:** Enter a unique category name that is not already used by another category with the same parent.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30590: A perspective with the specified name already exists in this namespace.**

---

**Cause:** The perspective name entered is not unique within this namespace.

**Action:** Enter a unique perspective name that is not already used by another perspective with the same parent.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30593: Invalid number format entered.**

**Cause:** An invalid value was entered for a number attribute. It is possible that the LOV associated with the attribute returns incorrect values.

**Action:** Request that the owner of the LOV change it to return the correct type of values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30595: A style with the specified name already exists**

**Cause:** The style name entered is not unique.

**Action:** Enter a unique style name that is not used in the current page group nor in the Shared Objects page group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30601: The date entered is invalid.**

**Cause:** An invalid date was entered.

**Action:** Enter a valid date.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30603: Invalid value entered for color.**

**Cause:** An invalid value was entered in the style's color field.

**Action:** Enter a valid color value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30617: At least one search term is required**

**Cause:** No search criteria was provided for the search.

**Action:** Enter some search criteria and submit the search.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWS-30626: You cannot copy the page because the Portal template which the page or its sub-pages are based on is not from the Shared Objects page group.**

**Cause:** The Portal template that the page and its sub-pages are based on is not from the Shared Objects page group.

**Action:** Copy the Portal template to the Shared Objects page group and change the page to be based on it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30627: No language specified for translation**

**Cause:** No language was specified in the internal API that creates translations for the page group. One way to avoid this is to create translations through the user interface.

**Action:** Specify a language for translation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30628: Specify a name that does not contain the following characters: \ / : \* ? \" < > |**

**Cause:** A name was entered that contained invalid characters.

**Action:** Specify a valid name. The name must not contain the following characters: \ / : \* ? \" < > | , & # %

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30629: Specify a name without spaces or special characters.**

**Cause:** The name entered contains invalid characters.

**Action:** Specify a valid name. Valid characters are [A-Z], [a-z], [0-9] and "\_".

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30630: An attribute with the specified name already exists.**

**Cause:** The attribute name entered is not unique.

**Action:** Enter a unique attribute name, one that is not used in the current page group nor in the Shared Objects page group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30632: You cannot copy the page because the type of the page or its sub-pages is not from the Shared Objects page group.**

---

**Cause:** The type of the page or its sub-pages is not from the Shared Objects page group.

**Action:** Move the page type to the Shared Objects page group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30640: The Page Group's default language cannot be deleted.**

**Cause:** An attempt was made to remove a page group's default language. This action is not permitted.

**Action:** Some translation languages can be removed. For a list of these, go to the Translations tab of page group properties.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30641: The Page Group ID does not exist.**

**Cause:** An invalid page group ID was entered.

**Action:** Enter a valid page group ID.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30644: A page group with the specified name already exists.**

**Cause:** The page group name entered is not unique.

**Action:** Enter a unique page group name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30660: Invalid date: %1**

**Cause:** An invalid date value was entered for the search attribute.

**Action:** Enter a valid date value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30661: Invalid number: %1**

**Cause:** An invalid number value was entered for the search attribute.

**Action:** Enter a valid number value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWS-30662: Procedure Call and Link Text cannot be null. Enter valid values for both these fields.**

**Cause:** A value was not entered for the Procedure Call or the Link Text.

**Action:** Enter values for both fields. If you do not want to add a procedure call to the page type, ensure that both fields are null.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30663: A URL is not specified for this page**

**Cause:** The URL for a URL page is not specified.

**Action:** Specify a URL for the URL page.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30664: Valid PL/SQL code is not specified for this page**

**Cause:** The PL/SQL code for a PL/SQL page is not specified.

**Action:** Specify PL/SQL code for the PL/SQL page.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30666: You cannot copy the page because the style used by one of the regions on the page or its sub-pages is not from the Shared Objects page group.**

**Cause:** The style used by a region on the page or its sub-pages is not from the Shared Objects page group.

**Action:** Move the style to the Shared Objects page group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30667: Saved search name already exists. Enter a new name.**

**Cause:** The name given for the saved search already exists.

**Action:** Specify a unique name for the saved search.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30670: You cannot copy the page because the item attribute parameter of the item template used by the page or its sub-pages is not from the Shared Objects page group.**

**Cause:** The item attribute parameter of the item template used by the page or its sub-pages is not from the Shared Objects page group.

**Action:** Copy the attribute to the Shared Objects page group.



---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30671: You cannot copy the page because an attribute associated with one of the regions on the page or its sub-pages is not from the Shared Objects page group.**

**Cause:** The attribute associated to a region on the page or its sub-pages is not from the Shared Objects page group.

**Action:** Move the attribute to the Shared Objects page group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30675: Display Name cannot be null.**

**Cause:** Nothing was entered in the Display Name field.

**Action:** Enter a valid Display Name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30676: You cannot copy the page because one or more of the perspectives associated with the page or its sub-pages are not from the Shared Objects page group.**

**Cause:** The perspective attached to the page or its sub-pages is not from the Shared Objects page group.

**Action:** Move the perspective to the Shared Objects page group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30677: You cannot copy the page because the HTML page skin used by the page or its sub-pages is not from the Shared Objects page group.**

**Cause:** The HTML page skin used by the page or its sub-pages is not from the Shared Objects page group.

**Action:** Move the HTML page skin to the Shared Objects page group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30680: Page Group not found**

**Cause:** An attempt was made to move an item to a nonexistent page group.

**Action:** Pass in a valid page group name to the move item API.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWS-30683: Enter a number greater than Zero**

**Cause:** One or more numeric values greater than zero were required but not entered in page group properties.

**Action:** Provide all the required number values.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30686: An item type with the specified name already exists.**

**Cause:** The item type name entered is not unique.

**Action:** Enter a unique item type name, one that is not used in the current page group nor in the Shared Objects page group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30687: A page type with the specified name already exists.**

**Cause:** The page type name entered is not unique.

**Action:** Enter a unique page type name, one that is not used in the current page group nor in the Shared Objects page group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30693: This user does not exist.**

**Cause:** An attempt was made to provide access to a user that does not exist.

**Action:** Provide a valid user name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30695: Page name contains spaces or special characters.**

**Cause:** The specified page name contained spaces or special characters.

**Action:** Remove the spaces and special characters from the page name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30698: The specified user name is invalid.**

**Cause:** An invalid user name or group name was entered.

**Action:** Enter a valid user name or group name. If you are not sure of the name, click the Browse Users or Browse Groups icon and select from the list provided.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WWS-30699: Path Alias Name is not defined for the Database Access Descriptor.**

**Cause:** The CGI environment variables were not initialized.

**Action:** Check the middle tier log files.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30701: You cannot copy the page because the item template used by the page or its sub-pages is not from the Shared Objects page group.**

**Cause:** The item template used by the page or its sub-pages is not from the Shared Objects page group.

**Action:** Copy the item template to the Shared Objects page group and change the page to use it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30706: You must specify a database schema.**

**Cause:** A schema name was not specified.

**Action:** Specify a valid schema name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30707: Invalid schema specified. Database schema does not exist.**

**Cause:** The database schema specified does not exist.

**Action:** Specify a valid database schema.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30710: You must specify an expiration date.**

**Cause:** The item is set to expire on a future date, but an expiration date was not specified.

**Action:** Specify the expiration date.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30711: You must specify the number of days for the expiration period.**

**Cause:** The item is set to expire in a certain number of days, but the number of days was not specified.

---

**Action:** Specify the number of days from the publish date when the item should expire.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30712: Publish Date must be in the proper date format. A 4-digit year must be indicated.**

**Cause:** The publish date was entered in an invalid format.

**Action:** Enter the publish date in the format specified. Ensure that the year is indicated in four digits.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30713: Publish Date cannot be earlier than current date**

**Cause:** An attempt was made to publish this item before the current date, or an attempt was made to create a sub-item with a publish date that precedes the publish date of the parent item.

**Action:** Change the publish date of the item to a future date, or set the publish date of the sub-item to the same or a later date than the publish date of the parent item.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30714: Expire Date must be in the proper date format. A 4-digit year must be indicated.**

**Cause:** The expiration date was entered in an invalid format.

**Action:** Enter the expiration date in the format specified. Ensure that the year is indicated in four digits.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30715: Expire Date must be later than current date.**

**Cause:** An expiration date was entered for the item that was not later than the current date.

**Action:** The item can be expired only in the future. Specify an expiration date that is later than the current date.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30716: An expire date that is the same as or earlier than the publish date signifies an Expired item**

---

**Cause:** The item has expired and cannot be edited.

**Action:** Un-expire the item, then try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30717: Number format specified for the expiration period is invalid.**

**Cause:** An invalid number was entered for the expiration period.

**Action:** Specify a valid number.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30718: This item is currently being unzipped. To unzip again**

**Cause:** The Unzip link was clicked while the file was in the process of being unzipped.

**Action:** To unzip the Zip file again, wait until the current unzip process is complete.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30719: Publish Date cannot be earlier than Create Date.**

**Cause:** An attempt was made to enter a publish date that precedes the item's creation date.

**Action:** Enter a publish date that is either the same or later than the current date.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30720: Unable to create items.**

**Cause:** Oracle Portal was unable to refresh a portlet provider or the Portlet Repository.

**Action:** Check the refresh log to determine the provider that throws error, then verify that the provider registration for that provider is correct. Ensure that the provider is up and running during refresh.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30721: You cannot copy the page because the default WebDAV item type of the page or its sub-pages is not from the Shared Objects page group.**

**Cause:** The default WebDAV item type of the page or its sub-pages is not from the Shared Objects page group.

**Action:** Copy the item type to the Shared Objects page group.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30722: The value entered for the page group quota is less than the page group's current usage.**

**Cause:** The new value for the page group quota was not greater than or equal to the number of megabytes already consumed by the contents of the page group.

**Action:** Enter a value greater than or equal to the current usage.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30723: The value entered for the page group quota is invalid.**

**Cause:** The value entered for the page group quota is invalid.

**Action:** Enter a valid value or select No Limit to impose no quota restriction on the page group's use of space. Valid values include any positive number, including fractional values, such as 50.5.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30724: Quota for this page group is exceeded.**

**Cause:** The document or image could not be uploaded because the page group quota has been exceeded.

**Action:** Contact the portal administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30725: Expire Date must be later than Publish Date.**

**Cause:** An attempt was made to enter an item expiration date that precedes the item publish date.

**Action:** Enter an expiration date that is later than the publish date.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30728: Invalid number format entered for number type attribute or invalid values specified for number type list of values.**

**Cause:** An invalid value or no value was specified for a number type attribute that is associated with this item type. The invalid value may be an invalid user-entered number or may be a selection from a list of values that contains invalid values.

**Action:** Edit the item type and provide valid values to all number type attributes. This may involve revising a list of values that is attached to a number type attribute.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30730: Unable to get the list of providers.**

**Cause:** The registration information for some provider was invalid, or an internal error occurred in the provider subsystem.

**Action:** Verify that registration information for all providers is valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30731: Invalid date format specified.**

**Cause:** An attempt was made to specify an invalid date format.

**Action:** Specify a valid date format.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30738: This e-mail address is invalid.**

**Cause:** An attempt was made to enter an e-mail address in an invalid format.

**Action:** Enter the e-mail address in a valid format, for example, name@oracle.com.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30741: This item has been checked out so you cannot edit it.**

**Cause:** Another user has checked the item out. The Edit icon was displayed because the page has not been refreshed since the other user checked the item out.

**Action:** Refresh the page to show the current status of its content. As soon as the other user checks the item in, you will be able to edit it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30742: Advanced Search link cannot be null.**

**Cause:** The choice to specify an Advanced Search Link was made, but the advanced search link value was not specified. The Advanced Search Link is specified either by selecting a page or specifying a URL.

**Action:** Specify an Advanced Search Link value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30743: Advanced Search page cannot be null.**

---

**Cause:** The choice was made to specify an Advanced Search Page, but the Advanced Search value was not specified. The Advanced Search Page is specified either by selecting a page or specifying a URL.

**Action:** Specify an Advanced Search Page value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30748: Pending items cannot be unzipped. The item must first be approved.**

**Cause:** An attempt was made to unzip an item that is pending approval. Items pending approval cannot be unzipped.

**Action:** Unzip after the item is approved.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-30749: Search Results Page Names cannot be null**

**Cause:** One or both search results pages were not specified.

**Action:** Choose search results pages for basic and advanced searches.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-31365: Valid date format: %1**

**Cause:** Dates were not entered in the correct format.

**Action:** Enter the date using the format specified.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-32018: The format of this URL has changed. Change the source of this URL to the New URL displayed below. The Old URL is not supported in future releases. If your browser does not automatically re-direct you in 30 seconds**

**Cause:** Portal URLs have changed, the old URL format is no longer valid.

**Action:** Wait to be redirected to the new URL, or click the link displayed.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-32021: An error was encountered while deleting the page group. The page group has been deleted but you should check the logs for more information.**

**Cause:** A page group that had some data inconsistency was deleted.

**Action:** No further action required. The page group has been deleted. You can look at the logs for additional details on the data inconsistency.

**Level:** 1



---

**Type:** ERROR

**Impact:** Other

**WWS-32022: The category has been created but it was not possible to place the search portlets on to the category page. The category page will not show the items or pages in the category.**

**Cause:** This is usually caused when the category page template has been modified and the region in which the portlets are to be placed has been removed.

**Action:** If the category template is deleted, it will be re-created with the correct regions the next time a category is created. However, existing categories will not be based on the new template. See the Oracle Portal Configuration Guide, for information on how to remove and re-create all of the category pages based on a re-created template.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-32023: The perspective has been created**

**Cause:** This is usually caused when the perspective page template has been modified and the region in which the portlets are to be placed has been removed.

**Action:** If the perspective template is deleted, it will be re-created with the correct regions the next time a perspective is created. However, existing perspectives will not be based on the new template. See the Oracle Portal Configuration Guide, for information on how to remove and re-create all of the perspective pages based on a re-created template.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-32024: The file could be not filtered.**

**Cause:** There may be a problem with an unsupported file format. To search file content and Themes and Gist, and view as HTML, the file must be filtered and converted to plain text. This is not always possible because some file formats are not supported. This error might also be caused by a problem with the set-up and configuration of Oracle Text.

**Action:** Ensure that the document is in a format supported by Oracle Text. See the Oracle Portal Configuration Guide, available on Portal Center, for information on how to work with Oracle Text.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-32025: The search criteria specified results in too many potential search terms.**

**Cause:** The combination of operator and search term were used to create a list of potential search terms that is too large. This can occur when using the "partially match (%term%)" operator with a non-specific search term.

**Action:** Enter a more specific search term or use a different operator.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WWS-32026: The Oracle Text Installation is not complete: Knowledge base file or files are missing.**

**Cause:** The Knowledge Base supplied with Oracle Text was not installed.

**Action:** Complete the installation of Oracle Text.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-32028: The Oracle Text search query is too complex to process.**

**Cause:** The Oracle Text search query provided is valid, but too complex for the installed version of Oracle Text to process.

**Action:** Simplify the search query expression and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-32029: Oracle Text error %1**

**Cause:** Oracle Text was unable to process the search query due to the specified error, starting with DRG-.

**Action:** For information on DRG- errors, refer to the Oracle Text documentation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-32101: No data found**

**Cause:** No data was found for the requested object.

**Action:** Try another request for a valid object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-32103: You do not have permission to perform this operation.**

**Cause:** The user does not have permission to perform this operation.

**Action:** Make sure that you are logged on as a user who has permission to perform the operation.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-32110: Page name is missing.**

**Cause:** A page name was required but not entered.

**Action:** Enter a valid page name.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-32111: Display name is missing.**

**Cause:** A display name was required but not entered.

**Action:** Enter a valid display name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-32118: Invalid REQUIRED value for an attribute**

**Cause:** One or more attributes required a value that was not provided.

**Action:** Provide values for all required attributes. Attributes that require a value are marked with an asterisk, \*.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-32139: The page group ID does not exist.**

**Cause:** An invalid page group ID was passed to a function getting the default language of a page group.

**Action:** Pass a valid page group ID.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-32141: The page does not exist.**

**Cause:** An invalid page was specified to be rendered in the page portlet.

**Action:** Pass a valid page by changing the parameter value passed to the page portlet.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-32143: Invalid display mode**

**Cause:** This portlet does not support the specified display mode.

**Action:** Choose either the Show or Edit display mode.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-32146: You cannot move the root page.**

**Cause:** Moving the root page of a page group is not permitted.

---

**Action:** Consider moving each of the root page's sub-pages or creating a new page group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-32147: You cannot move an object into itself.**

**Cause:** Moving a page into one of its own sub-pages is not permitted.

**Action:** Choose a different destination for the page.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-32150: The item name can contain an invalid character.**

**Cause:** A name containing one or more invalid characters was entered for the item.

**Action:** Enter a valid name for the item. Item names can contain the characters A to Z, a to z, 0 to 9, and \_. Item names cannot contain the characters \/:\*?"<>|,&#%.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-32153: PL/SQL code cannot exceed 2000 bytes**

**Cause:** Maximum length of PL/SQL code is 2000 bytes. The input length was longer than 2000 bytes

**Action:** Reduce the code within 2000 bytes

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-33668: You cannot copy the page because the item attribute parameter of the item template used by the page or its sub-pages is not from the Shared Objects page group.**

**Cause:** The item attribute parameter of the item template used by the page or its sub-pages is not from the Shared Objects page group.

**Action:** Copy the attribute to the Shared Objects page group.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWS-33797: You cannot move the item because the type of an item is not from the Shared Objects page group.**

**Cause:** The type of the item is not from the Shared Objects page group.

**Action:** Move the item type to the Shared Objects page group.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WWS-33951: You cannot copy the page because the type of an item on the page or its sub-pages is not from the Shared Objects page group.**

**Cause:** The type of an item on the page or its sub-pages is not from the Shared Objects page group.

**Action:** Move the item type to the Shared Objects page group.

**Level:** 1

**Type:** ERROR

**Impact:** Other



---

## WWU-52262 to WWU-83028

**WWU-52262: Exception in %1 : %2**

**Cause:** An unknown exception occurred during the export-import operation.

**Action:** Do nothing. The selected object will be exported. If the export fails, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52263: The object %1 was not added to the transport set because it already exists as (or is the child of) an explicit object.**

**Cause:** The object is already marked for export.

**Action:** Do nothing. The selected object will be exported.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52293: An unknown exception occurred while validating the system tables. Aborting the export.**

**Cause:** An abnormal exception occurred while performing the schema validation and cleanup.

**Action:** Check the schema-validation document, correct it, and export again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52294: An unknown exception occurred while validating the system tables. Exiting the validation process. All changes performed by the validation process will be reverted.**

**Cause:** An abnormal exception occurred while performing the schema validation and cleanup.

**Action:** Check the schema-validation document and correct it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWU-52295: An unknown exception occurred during the resolution of page group objects. The entire page group import is being rolled back.**

**Cause:** An unknown exception occurred during the resolution of page group objects.

**Action:** Follow these steps: <br /> 1. If the log displays the cause of the error, correct the error and run the importa again. <br /> 2. Run the schema-validation utility to correct the error and run the import again. <br /> 3. If you are still unable import successfully, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52298: The resource is held up by other process. Please try deleting after some time.**

**Cause:** The object trying to delete is in use by some other Portal session.

**Action:** Try deleting it after sometime.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52320: The source attribute %1 has been promoted to the Shared Objects page group. The same attribute on the target belongs to a local page group.**

**Cause:** The same attribute on the source and the target belongs to different page groups. The source attribute was promoted to the Shared Objects page group, while the target attribute belongs to a local page group.

**Action:** Promote the local attribute on the target to the Shared Objects page group, and re-import it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52321: The source attribute %1 belongs to a local page group. The same attribute on the target was promoted to the Shared Objects page group.**

**Cause:** The same attribute on the source and the target belongs to different page groups. The source attribute belongs to a local page group, while the target attribute has been promoted to the Shared Objects page group.

**Action:** Promote the local attribute on the source to the Shared Objects page group, and re-import it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52322: The Type or unique identifier of the source attribute %1 does not match the target attribute %1.**

**Cause:** A different attribute on the target uses the same name as the attribute on the source.

**Action:** Delete the attribute on the target, and re-import it.



---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52323: The source attribute %1 exists on the target under a different name. The target attribute cannot be reused.**

**Cause:** The attribute name has been changed on the source or the target.

**Action:** Import the attribute in overwrite mode, or make the names the same on both the source and the target.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52324: The length of the source attribute %1 is less than the same target attribute. Overwriting the target attribute can result in data inconsistency on the target.**

**Cause:** The length of a text attribute on the target is greater than the length of the same text attribute on the source.

**Action:** Modify the length of the text attribute on the source and re-import it, or import it in reuse mode.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52325: The length of the target attribute %1 is less than the same source attribute. Reuse of the target attribute can result in data inconsistency on the source.**

**Cause:** The length of a text attribute on the target is less than the length of the same text attribute on the source.

**Action:** Modify the length of the text attribute on the target and re-import it, or import it in overwrite mode.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52326: The source style %1 was promoted to the Shared Objects page group. The same style on the target belongs to a local page group.**

**Cause:** The same style on the source and the target belongs to different page groups. The source style was promoted to the Shared Objects page group, while the target style belongs to a local page group.

**Action:** Promote the local style on the target to the Shared Objects page group and re-import it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWU-52327: The source style %1 belongs to a local page group. The same style on the target was promoted to the Shared Objects page group.**

**Cause:** The source style belongs to a local page group, while the target style has been promoted to the Shared Objects page group.

**Action:** Promote the local style on the source to the Shared Objects page group and re-import it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52328: The unique identifier of the source style %1 does not match the target style %1.**

**Cause:** A different style on the target uses the same name as the source style.

**Action:** Delete the style on the target and re-import the source style.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52329: The source style %1 exists on the target with a different name. The target style cannot be reused.**

**Cause:** The style name has been changed on the source or on the target.

**Action:** Either import the style in overwrite mode, or make the names the same on the source and the target.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52330: The source item type %1 exists on the target with a different name. The target item type cannot be reused.**

**Cause:** The item type's name has been changed on the source or on the target.

**Action:** Either import the item type in overwrite mode, or make the names the same on the source and the target.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52331: The Type or unique identifier of the source item type %1 does not match the target item type %1.**

**Cause:** A different item type on the target uses the same name as the item type on the source.

**Action:** Delete the item type on the target and re-import it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWU-52332: The source item type %1 was promoted to the Shared Objects page group. The same item type on the target belongs to a local page group.**

**Cause:** The source item type has been promoted to the Shared Objects page group, while the target item type belongs to a local page group.

**Action:** Promote the local item type on the target to the Shared Objects page group and re-import it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52333: The source item type %1 belongs to a local page group. The same item type on the target has been promoted to the Shared Objects page group.**

**Cause:** The source item type belongs to a local page group, while the target item type has been promoted to the Shared Objects page group.

**Action:** Promote the local item type on the source to the Shared Objects page group and re-import it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52334: The source page type %1 exists on the target with a different name. The target page type cannot be reused.**

**Cause:** The page type's name has been changed on the source or on the target.

**Action:** Either import the page type in overwrite mode, or make the names the same on both the source and the target.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52335: The Type or unique identifier of the source page type %1 does not match the target page type %1.**

**Cause:** A different page type on the target uses the same name.

**Action:** Delete the page type on the target and re-import it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52336: The source page type %1 has been promoted to the Shared Objects page group. The same page type on the target belongs to a local page group.**

**Cause:** The source page type has been promoted to the Shared Objects page group, while the target page type belongs to a local page group.

**Action:** Promote the local page type on the target to the Shared Objects page group and re-import it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWU-52337: The source page type %1 belongs to a local page group. The same page type on the target has been promoted to the Shared Objects page group.**

**Cause:** The source page type belongs to a local page group, while the target page type has been promoted to the Shared Objects page group.

**Action:** Promote the local page type on the source to the Shared Objects page group and re-import it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52338: The portlet instance with unique identifier(portlet\_inst\_guid): %1 will be deleted from the page in the transport set because it has a dependency that does not exist on the target.**

**Cause:** The portlet's dependency, such as its page, Web Provider, Database Provider, or so on, does not exist on the target.

**Action:** Promote the portlet's dependency to the transport set in the source and re-import it. If the dependency is a Web Provider, register it on the target to make the portlet available in the Portlet Repository.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52339: An unexpected error occurred while extracting an HTML template's data into its corresponding transport tables.**

**Cause:** An unexpected error occurred while extracting metadata from an HTML template. Because metadata was not extracted, the import might result in errors.

**Action:** Contact Oracle Support Services and provide the logs obtained.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52340: An unexpected error occurred while importing the HTML template with the unique identifier %1**

**Cause:** An unexpected error occurred while importing an HTML template.

**Action:** Contact Oracle Support Services and provide the logs obtained.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52341: The source htmltemplate %1 was promoted to the Shared Objects page group. The same htmltemplate on the target belongs to a local page group.**

**Cause:** The same htmltemplate on the source and the target belongs to different page groups. The source htmltemplate was promoted to the Shared Objects page group, while the target htmltemplate belongs to a local page group.

**Action:** Promote the local htmltemplate on the target to the Shared Objects page group and re-import it.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WWU-52342: The source htmplate %1 belongs to a local page group. The same htmplate on the target was promoted to the Shared Objects page group.**

**Cause:** The source htmplate belongs to a local page group, while the target htmplate has been promoted to the Shared Objects page group.

**Action:** Promote the local htmplate on the source to the Shared Objects page group and re-import it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52343: The unique identifier of the source htmplate %1 does not match the target htmplate %1.**

**Cause:** A different htmplate on the target uses the same name as the source htmplate.

**Action:** Delete the htmplate on the target and re-import the source htmplate.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52454: An unexpected error has occurred. Verify the log in debug mode**

**Cause:** An unexpected error occurred while importing the access related information.

**Action:** Contact Oracle Support Services and provide the logs obtained.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52463: You do not have permission to %0 ACLs on %1.**

**Cause:** The user did not have sufficient privileges to manage the access control lists (ACLs) of the listed object.

**Action:** Ask the Oracle Portal administrator to grant the required privileges. Try the import operation again after the privileges have been granted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52464: Unable to resolve %0 external application on the target OracleAS Portal.**

**Cause:** Either the listed external application does not exist in the target OracleAS Single Sign-On, or there are multiple external applications with this name.

**Action:** Check the external application in the target OracleAS Single Sign-On. Create the application if it does not exist. Otherwise, check for external applications with duplicate names. Note that names of external applications are

---

case in-sensitive. Delete any redundant external applications. Re-import after taking one of these corrective actions.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52465: Name not updated for object type: %0**

**Cause:** The object list has not been updated with the mapping name while importing.

**Action:** Contact Oracle Support Services and provide the logs obtained.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52501: Initialization of component(ID : %1 Name : %2) failed.**

**Cause:** An unexpected error occurred while calculating the dependencies of the object.

**Action:** Retry the import. If the retry fails, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52566: Generation of Component %1**

**Cause:** The component generation has failed with compilation errors due to missing dependencies or privileges.

**Action:** Resolve the missing dependencies/privileges from a DB session and retry the import of the failed component.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52567: Import of %1 failed.**

**Cause:** The import failed for the object in the transport set.

**Action:** Retry the import. If the retry fails, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52571: Warning : Import of color %1 failed.**

**Cause:** An unexpected error occurred while creating the color on the target.

**Action:** Retry the import. If the retry fails, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWU-52572: Warning : Import of font %1 failed.**

**Cause:** An unexpected error occurred while creating the font on the target.

**Action:** Retry the import. If the retry fails, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52573: Warning : Import of image %1 failed.**

**Cause:** An unexpected error occurred while creating the image on the target.

**Action:** Retry the import. If the retry fails, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52574: Warning : Import of template %1 failed.**

**Cause:** An unexpected error occurred while creating the template on the target.

**Action:** Retry the import. If the retry fails, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52594: The DB Provider schema %1 does not have EXECUTE privileges on the OracleAS Portal packages used by the DB Provider portlets.**

**Cause:** The EXECUTE privilege on OracleAS Portal packages, used by the portlets, was not granted to the DB Provider schema.

**Action:** Grant the EXECUTE privilege on OracleAS Portal packages to the DB Provider schema using the script provsyns.sql.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52595: The schema %1 does not exist in this database instance.**

**Cause:** The schema, that a Portal DB Provider, being imported in the current import operation, uses, was not found in this database instance.

**Action:** Create the schema in this database instance and grant the CONNECT and RESOURCE roles to it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52596: The component %1 doesnot exist on target.**

**Cause:** This component was exported as an external object. Make sure that this component exists on target before import.

**Action:** Export this component seperately first or promote this component as explicit and repeat the export and import process.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52872: Mapping not found for Page ID %1 and Page Group ID %2 .**

**Cause:** There is a dependency on the specified page and page group, and neither exist on the target.

**Action:** Promote the specified page/page group to the transport set in the source, and re-import it. If the import still fails, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52883: Transport set name cannot be NULL.**

**Cause:** No name has been specified for the transport set.

**Action:** Specify a name for the transport set.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52884: Transport set %1 has already been exported and is now available for import.**

**Cause:** The transport set has already been exported.

**Action:** If the export was successful, the transport set can now be used for import.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52885: Transport set %1 has not yet been exported and is therefore unavailable for import.**

**Cause:** The transport set has not been exported.

**Action:** Export the transport set.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52886: Transport set %1 does not exist.**

**Cause:** The transport set was not found on the server.

**Action:** Verify that the transport set name was entered correctly. You may need to re-create the transport set.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52887: Transport set %1 is currently unavailable for either export or import. See the transport set for more details.**



---

**Cause:** The transport set status is neither EXTRACT\_COMPLETE nor AVAILABLE.

**Action:** Browse the list of transport sets to determine the status.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52888: Multiple matches found for transport set %1. Choose the one you want from the LOV.**

**Cause:** More than one transport set with the same name was found.

**Action:** Use the user/timestamp on the list of values to identify the transport set you want.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52889: Transport set %1 is not available for adding more objects.**

**Cause:** The transport set is not available because it has already been exported or imported.

**Action:** Browse the list of transport sets to determine the status.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52926: Transport set %1 does not contain any objects.**

**Cause:** The transport set is empty.

**Action:** To access the transport set, add at least one object to it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52927: Logged-in user %1 does not have MANAGE privilege on any transport set and therefore cannot perform this action.**

**Cause:** You do not appear to have MANAGE privilege on any transport sets.

**Action:** Ask your portal administrator to assign you this privilege.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52969: Transport set does not exist. Cannot pre-check search preferences.**

**Cause:** Search preferences cannot be pre-checked because the specified transport set does not exist.

**Action:** Verify the transport set name, or re-create the transport set.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WWU-52970: Could not obtain transport set information. Cannot pre-check search preferences.**

**Cause:** Search preferences cannot be pre-checked because information about the given transport set could not be obtained.

**Action:** Verify the transport set name, or re-create the transport set.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52971: Cannot obtain search preference with ID %1 from system table.**

**Cause:** The preference for a search portlet marked for export does not exist in the system tables.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52972: An error occurred when performing export pre-check of search portlet preferences.**

**Cause:** An unexpected error occurred while pre-checking search preferences prior to export.

**Action:** Check that the customizations for the search portlets you are exporting are valid.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52973: An error occurred when exporting system preferences for search portlets.**

**Cause:** The exporting of search preferences has failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52974: Transport set does not exist. Cannot export search preferences.**

**Cause:** The specified transport set does not exist. Exporting of search preferences cannot continue.

**Action:** Verify the transport set name, or re-create the transport set.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWU-52975: Could not obtain transport set information. Cannot export search preferences.**

**Cause:** Cannot export search preferences because could not obtain information about the given transport set.

**Action:** Verify the transport set name, or re-create the transport set.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52976: Exception occurred while exporting search portlet preferences.**

**Cause:** An unexpected error occurred while attempting to export search portlet preferences.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52977: Generating dependencies from search portlet preferences has failed. The transport set will not be valid for importing.**

**Cause:** The dependencies in the search portlet preferences to be exported could not be obtained.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52978: An error occurred while generating search portlet dependencies.**

**Cause:** The dependencies in the search portlet preferences to be exported could not be obtained.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52979: Exception occurred during search pre-check.**

**Cause:** An unexpected error occurred while pre-checking search preferences.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52980: An error occurred while marking an object in the transport set.**

**Cause:** An error occurred while marking a search portlet preference dependency included in the transport set.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52981: Exception occurred while setting the page as failed pre-check.**

**Cause:** An unexpected error occurred while attempting to mark a page as failed pre-check.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52982: There was an error in checking dependencies. Dependencies contained in search preferences did not exist in dependency table.**

**Cause:** Dependencies in the search preferences are not in the search dependency table.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52983: Error occurred checking for missing dependencies.**

**Cause:** An unexpected error occurred while checking if a search preference has missing dependencies.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52984: Cannot obtain new IDs from target tables. Cannot proceed with search pre-check.**

**Cause:** An error occurred while attempting to get the ID of an object in the target tables.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52985: Pre-check cannot continue because inconsistent data was found in dependency table and search transport table.**

**Cause:** The information in the search preferences does not match information in the search dependency table.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWU-52986: Exception occurred resolving search portlet preferences.**

**Cause:** An unexpected error occurred while attempting to resolve search preference information.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52987: Exception occurred resolving search portlet preference import actions.**

**Cause:** An unexpected error occurred while attempting to determine the import action of search portlet preferences.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52988: Exception occurred resolving search portlet preference reference paths.**

**Cause:** An unexpected error occurred while attempting to resolve a search portlet's reference path.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52989: An error occurred getting object information from the object path.**

**Object type does not exist.**

**Cause:** The object type of a search preference dependency is not valid.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52990: Exception occurred while updating dependency table with new IDs from the object path.**

**Cause:** An unexpected error occurred while attempting to update the dependency table with the new IDs.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52991: Exception occurred while determining IDs from the target tables.**

**Cause:** An unexpected error occurred when attempting to obtain the ID of a search preference dependency from the target tables.

---

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52992: Exception occurred while determining IDs from the transport tables.**

**Cause:** An unexpected error occurred when attempting to obtain the ID of a search preference dependency from the transport tables.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52993: Exception occurred while resolving dependency IDs.**

**Cause:** An unexpected error occurred while attempting to determine the new IDs of search preference dependencies.

**Action:** Contact Oracle Support Services. search import

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52994: Exception occurred while importing search portlet preferences.**

**Cause:** An unexpected error occurred when attempting to import search portlet preferences.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52995: Exception occurred while inserting new search portlet preferences.**

**Cause:** An unexpected error occurred when attempting to insert new search portlet preferences into the target tables.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52996: Error populating search dependency table with page group objects.**

**Cause:** An unexpected error occurred when obtaining the page group dependencies from the search portlets being exported.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWU-52997: An error occurred while populating search dependency table with image objects.**

**Cause:** An unexpected error occurred when obtaining the image dependencies from the search portlets being exported.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52998: An error occurred while populating search dependency table with style objects.**

**Cause:** An unexpected error occurred when obtaining the style dependencies from the search portlets being exported.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-52999: An error occurred while populating search dependency table with attribute objects.**

**Cause:** An unexpected error occurred when obtaining the attribute dependencies from the search portlets being exported.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74000: An error occurred while populating search dependency table with item type objects.**

**Cause:** An unexpected error occurred when obtaining the item type dependencies from the search portlets being exported.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74001: Efforts to determine the page path have failed. Object not found.**

**Cause:** An unexpected error occurred while obtaining the path of the page selected to display search results. The page cannot be found.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74002: Efforts to determine the page path have failed. Language not found.**

---

**Cause:** An unexpected error occurred while obtaining the path of the page selected to display search results. The language cannot be found.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74003: Efforts to determine the page path have failed due to invalid domain.**

**Cause:** An unexpected error occurred while obtaining the path of the page selected to display search results. The domain is invalid.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74004: Efforts to determine the page path have failed due to invalid object type.**

**Cause:** An unexpected error occurred while obtaining the path of the page selected to display search results. The object type is invalid.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74005: An error occurred while populating search dependency table with page objects.**

**Cause:** An unexpected error occurred while obtaining the page dependencies from the search portlets being exported.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74006: Efforts to determine the category path have failed because the category was not found.**

**Cause:** An unexpected error occurred while obtaining the path of the category selected as search criteria. The category cannot be found.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74007: Efforts to determine the category path have failed because the language was not found.**

**Cause:** An unexpected error occurred while obtaining the path of the category selected as search criteria. The language cannot be found.



---

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74008: Efforts to determine the category path have failed due to invalid domain.**

**Cause:** An unexpected error occurred while obtaining the path of the category selected as search criteria. The domain is invalid.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74009: Efforts to determine the category path have failed due to invalid object type.**

**Cause:** An unexpected error occurred while obtaining the path of the category selected as search criteria. The object type is invalid.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74010: An error occurred while populating the search dependency table with category objects.**

**Cause:** An unexpected error occurred while obtaining the category dependencies from the search portlets being exported.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74011: Efforts to determine the perspective path have failed because the object was not found.**

**Cause:** An unexpected error occurred while obtaining the path of the perspective selected as search criteria. The object cannot be found.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74012: Efforts to determine the perspective path have failed because the language was not found.**

**Cause:** An unexpected error occurred while obtaining the path of the perspective selected as search criteria. The language cannot be found.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74013: Efforts to determine the perspective path have failed due to invalid domain.**

**Cause:** An unexpected error occurred while obtaining the path of the perspective selected as search criteria. The domain is invalid.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74014: Efforts to determine the perspective path have failed due to invalid object type.**

**Cause:** An unexpected error occurred while obtaining the path of the perspective selected as search criteria. The object type is invalid.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74015: An error occurred while populating the search dependency table with perspective objects.**

**Cause:** An unexpected error occurred while obtaining the perspective dependencies from the search portlets being exported.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74017: An error occurred when attempting to clean up search preferences.**

**Cause:** An unexpected error occurred while removing dangling references from the preferences of the search portlets being exported.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74019: Copying data from source tables to transport tables failed.**

**Cause:** An unexpected error occurred while copying preferences of the search portlets being exported from the source table to the transport table.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWU-74021: The page on which portlet resides does not exist.**

**Cause:** Obtaining the page on which the search portlet resides failed because the page does not exist in the transport set.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74022: Too many pages were returned when attempting to determine the page on which the portlet resides.**

**Cause:** Obtaining the page on which the search portlet resides failed because too many pages were returned from the query.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74023: An error occurred getting the ID of the page object that contains the search portlet.**

**Cause:** An unexpected error occurred when attempting to get the object ID of the page on which the search portlet resides.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74024: Checking page group dependencies failed.**

**Cause:** An unexpected error occurred while checking if the page groups selected in search portlet customizations will exist in the target after import.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74025: Checking image dependencies failed.**

**Cause:** An unexpected error occurred while checking if the images selected in search portlet customizations will exist in the target after import.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74026: Checking style dependencies failed.**

---

**Cause:** An unexpected error occurred while checking if the styles selected in search portlet customizations will exist in the target after import.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74027: Checking page dependencies failed.**

**Cause:** An unexpected error occurred while checking if the pages selected in search portlet customizations will exist in the target after import.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74028: Checking submission attributes dependencies failed.**

**Cause:** An unexpected error occurred while checking if the submission attributes selected in search portlet customizations will exist in the target after import.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74029: Checking item type attribute default value failed.**

**Cause:** An unexpected error occurred while checking to see if the item types selected in the search portlet customizations will exist in the target after import.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74030: Checking category attribute default value failed.**

**Cause:** An unexpected error occurred while checking to see if the categories selected in the search portlet customizations will exist in the target after import.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74031: Checking perspective attribute default value failed.**

**Cause:** An unexpected error occurred while checking to see if the perspectives selected in the search portlet customizations will exist in the target after import.

**Action:** Contact Oracle Support Services.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WWU-74032: Checking results attributes dependencies failed.**

**Cause:** An unexpected error occurred while checking to see if the results attributes selected in the search portlet customizations will exist in the target after import.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74034: Resolving results page dependencies failed.**

**Cause:** An unexpected error occurred while replacing source IDs with target IDs for the results page option in the search portlet customizations.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74035: Resolving image dependencies failed.**

**Cause:** An unexpected error occurred while replacing source IDs with target IDs for the image option in the search portlet customizations.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74036: Resolving style dependencies failed.**

**Cause:** An unexpected error occurred while replacing source IDs with target IDs for the style option in the search portlet customizations.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74037: Resolving page groups dependencies failed.**

**Cause:** An unexpected error occurred while replacing source IDs with target IDs for the page group option in the search portlet customizations.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74038: Exception occurred while resolving default values identified by a pair of IDs.**

---

**Cause:** An unexpected error occurred while replacing source IDs with target IDs for attributes in the search portlet customizations, where the default values are objects in the portal.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74039: Exception occurred while resolving default values identified by a set of ID pairs.**

**Cause:** An unexpected error occurred while replacing source IDs with target IDs for attributes in the search portlet customizations, where the default values are objects in the portal.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74040: Resolving submission attributes dependencies failed.**

**Cause:** An unexpected error occurred while replacing source IDs with target IDs for the submission attributes option in the search portlet customizations.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74041: Resolving display attributes dependencies failed.**

**Cause:** An unexpected error occurred while replacing source IDs with target IDs for the display attributes option in the search portlet customizations.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74043: Cannot resolve search preferences because the transport set does not exist.**

**Cause:** The search preferences for the portlets being imported cannot be resolved because the transport set does not exist.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74044: Could not resolve search preferences because the transport set information could not be obtained.**

---

**Cause:** The search preferences for the portlets being imported cannot be resolved because the transport set information cannot be obtained.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74045: Exception occurred while updating existing search portlet preferences.**

**Cause:** An unexpected error occurred while the preferences for the search portlets being imported were being updated.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74047: Could not import search preferences because the transport set does not exist.**

**Cause:** The search preferences for the portlets being imported cannot be imported because the transport set does not exist.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74048: Could not import search preferences because transport set information could not be obtained.**

**Cause:** The search preferences for the portlets being imported cannot be imported because the transport set information cannot be obtained.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74062: Error resolving search portlet translations.**

**Cause:** An unexpected error occurred while resolving translations of search portlet preferences.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74063: Error resolving search portlet string preferences.**

**Cause:** An unexpected error occurred whilst the translations of search string preferences were being resolved, with the languages that exist in the target portal.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74066: Error populating the search mapping table with page group objects.**

**Cause:** An unexpected error occurred while attempting to obtain page group dependencies for the search items to be exported.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74071: Error resolving pages to be searched.**

**Cause:** An unexpected error occurred while replacing source IDs with target IDs for the pages that are defined within search portlet customizations; that is, pages defined using the 'Search-In' option.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74072: Check for missing pages failed.**

**Cause:** An unexpected error occurred while checking if the page groups selected in search item customizations will exist in the target after import.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74100: Page %1 of the page group with unique identifier %2 applies the user's default style. The default style of the user on the target will be used.**

**Cause:** The page group is using a user default style.

**Action:** The default style of the user on the target will be used. Or bring the source user's default style on the target and associate it with the user.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74101: Unable to find data for the attribute with unique identifier %1 and page group identifier %2. An attempt to import this transport set could result in errors.**

**Cause:** Data was not found for the specified attribute in the specified page group. The export proceeded without the attribute. An attempt to import the resulting transport set could result in errors. This is a data inconsistency issue in the base system, possibly in the itemtype or pagetype attribute association table.

**Action:** Contact Oracle Support Services, and provide the export logs.



---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74102: Multiple records were found while obtaining the metadata of the attribute with unique identifier %1 and page group identifier %2. An attempt to import this transport set could result in errors.**

**Cause:** An unexpected error occurred while obtaining attribute metadata. The export will proceed without the attribute. An attempt to import the resulting transport set could result in errors. This error may indicate a data inconsistency issue in the base system, possibly in the attribute metadata table.

**Action:** Contact Oracle Support Services and provide the export logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74103: Unable to add the attribute with unique identifier %1 and page group identifier %2. An attempt to import this transport set could result in errors.**

**Cause:** An unexpected error occurred while adding the specified attribute. The export proceeded without the attribute. An attempt to import the resulting transport set could result in errors.

**Action:** Contact Oracle Support Services, and provide the export logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74104: Multiple records were found while getting the page type of the page %1 in the page group with unique identifier %2. An attempt to import this transport set could result in errors.**

**Cause:** An unexpected error occurred while obtaining the page type. The export will proceed without the type. An attempt to import the resulting transport set could result in errors. This error may indicate a data inconsistency issue in the base system, possibly in the pagetype metadata table.

**Action:** Contact Oracle Support Services, and provide the export logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74105: No page type definition found for page %1 in the page group with unique identifier %2. An attempt to import this transport set could result in errors.**

**Cause:** An unexpected error occurred while obtaining the page type definition. The export proceeded without the page type definition. An attempt to import the resulting transport set could result in errors. This is a data inconsistency issue in the base system. The page table contains a inconsistent pagetype entry.

**Action:** Contact Oracle Support Services, and provide the resulting logs.

**Level:** 1

---

Type: ERROR

Impact: Other

**WWU-74106: Cannot add the page type of page %1 in the page group with unique identifier %2. An attempt to import this transport set could result in errors.**

**Cause:** An unexpected error occurred while adding the page type metadata. The export will proceed without the page type metadata. An attempt to import the resulting transport set could result in errors.

**Action:** Contact Oracle Support Services, and provide the export logs.

Level: 1

Type: ERROR

Impact: Other

**WWU-74107: No item type definition found for item %1 in page group with unique identifier %2. An attempt to import this transport set could result in errors.**

**Cause:** An unexpected error occurred while obtaining the item type definition. The export proceeded without the item type. An attempt to import the resulting transport set could result in errors. This is a data inconsistency issue in the base system. A inconsistent itemtype entry is present in the item table.

**Action:** Contact Oracle Support Services, and provide the export logs.

Level: 1

Type: ERROR

Impact: Other

**WWU-74108: Multiple records were found while obtaining the item type of item %1 in the page group with unique identifier %2. An attempt to import this transport set could result in errors.**

**Cause:** An unexpected error occurred while obtaining the specified item type. The export proceeded without the item type. An attempt to import the resulting transport set could result in errors. This may be a data inconsistency issue in the base system, possibly in the itemtype metadata table.

**Action:** Contact Oracle Support Services, and provide the export logs.

Level: 1

Type: ERROR

Impact: Other

**WWU-74109: Unable to add the item type of item %1 in the page group with unique identifier %2. An attempt to import this transport set could result in errors.**

**Cause:** An unexpected error occurred while adding the item type. The export will proceed without the item type metadata. An attempt to import the resulting transport set could result in errors.

**Action:** Contact Oracle Support Services, and provide the export logs.

Level: 1

Type: ERROR

Impact: Other

---

**WWU-74110: Multiple records were found while obtaining the category of page %1 in the page group with unique identifier %2. An attempt to import this transport set could result in errors.**

**Cause:** An unexpected error occurred while getting the specified category. The export proceeded without the category. An attempt to import the resulting transport set could result in errors. This error may indicate a data inconsistency issue in the base system, possibly in the category metadata table.

**Action:** Contact Oracle Support Services, and provide the export logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74111: Unable to add the category of page %1 in the page group with unique identifier %2. An attempt to import this transport set could result in errors.**

**Cause:** An unexpected error occurred while adding the category. The export will proceed without the category metadata. An attempt to import the resulting transport set could result in errors.

**Action:** Contact Oracle Support Services, and provide the export logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74112: Cannot find the perspective with the unique identifier %1 and page group identifier %2. An attempt to import this transport set could result in errors.**

**Cause:** An unexpected error occurred while getting the specified perspective. The export proceeded without the perspective. An attempt to import the resulting transport set could result in errors. This is a data inconsistency issue in the base system. An inconsistent perspective entry is present in the item or page perspective association tables.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74113: Multiple records were found while obtaining the perspective with the unique identifier %1 and page group identifier %2. An attempt to import this transport set could result in errors.**

**Cause:** An unexpected error occurred while obtaining the specified perspective. The export proceeded without the perspective. An attempt to use the resulting transport set could result in errors. This error may indicate a data inconsistency issue in the base system, possibly in the perspective metadata table.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWU-74114: Unable to add the perspective with the unique identifier %1 and page group identifier %2. An attempt to import this transport set could result in errors.**

**Cause:** An unexpected error occurred while adding the perspective. The export will proceed without the perspective. An attempt to import the resulting transport set could result in errors.

**Action:** Contact Oracle Support Services, and provide the export logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74115: Multiple records were found while obtaining the style of the page %1 with page group identifier %2. An attempt to import this transport set could result in errors.**

**Cause:** An unexpected error occurred while obtaining the style of the specified page. The export proceeded without the style. Import of the resulting transport set could result in errors. This error may indicate a data inconsistency issue in the base system, possibly in the style metadata table.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74116: Unable to add the style of the page %1 with page group identifier %2. An attempt to import this transport set could result in errors.**

**Cause:** An unexpected error occurred while adding the style. The export will proceed without the style. An attempt to import the resulting transport set could result in errors.

**Action:** Contact Oracle Support Services, and provide the export logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74117: Cannot find record for the external application with the unique identifier %1. Portlets based on this application will get lost on import.**

**Cause:** The specified external application was not found. The export will proceed without the dependencies. If the resulting transport set is imported, portlets that are dependent on this application will not be found. This error may indicate a data inconsistency issue in the base system. For example, there may be a inconsistent external application entry in the provider table.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74118: Multiple records were found while obtaining the details of external application with the unique identifier %1. Portlets based on this application will get lost during import.**

---

**Cause:** An unexpected error occurred while obtaining the details of the specified external application. The export proceeded without the dependencies. If the resulting transport set is imported, the portlets that are dependent on this application will not be found. This error may indicate a data inconsistency issue in the base system, possibly in the external application table.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74119: Unable to add the external application dependency with the unique identifier %1. Portlets based on this application will get lost on import.**

**Cause:** An unexpected error occurred while adding the external application dependency. The export proceeded without the dependency. If the resulting transport set is imported, portlets that are dependent on this application will not be found.

**Action:** Contact Oracle Support Services, and provide the export logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74120: Cannot find the page group with unique identifier %1**

**Cause:** The page group where the portlet is exposed as shared could not be found. The export proceeded without the page group. If the resulting transport set is imported, the portlet could be lost. This may be a data inconsistency issue in the base system, possibly in the portlet instance table. For example, the shared portlet instance entry may have a wrong pgrp identifier.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74121: Unable to add the dependencies of generic page portlet with the unique identifier %1 and page group identifier %2. An attempt to import this transport set could result in errors.**

**Cause:** An unexpected error occurred while adding the dependencies of the generic page portlet. The export proceeded without the dependencies. If the resulting transport set is imported, the generic page portlet could result in errors.

**Action:** Contact Oracle Support Services, and provide the export logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74122: Cannot find the definition of the DB Provider component that is exposed as the portlet with unique identifier %1. Portlets based on this component will get lost upon import.**

**Cause:** Could not find the definition of the specified DB Provider exposed as a portlet. The export proceeded without the portlet definition. If the resulting

---

transport set is imported, portlets based on this component will get lost upon import. This error may indicate a data inconsistency issue in the base system. For example, the wrong portlet ID information may be stored in the portlet instance table.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74123: Cannot find details for the provider with the unique identifier %1. An attempt to import this transport set could result in errors.**

**Cause:** No data was found while obtaining the provider definition. The export will proceed without it. An attempt to import the resulting transport set could result in errors, possibly the loss of the portlets owned by this provider. This error may indicate a data inconsistency issue in the base system. For example, a inconsistent provider entry may be stored in the portlet instance table.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74124: Multiple records were encountered while obtaining details for the provider with unique identifier %1. An attempt to import this transport set could result in errors.**

**Cause:** An unexpected error occurred while getting the provider definition. The export proceeded without it. An attempt to import the resulting transport set could result in errors, possibly the loss of this provider's portlets. This error may indicate a data inconsistency issue in the base system, possibly in the provider metadata table.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74125: No data was found while obtaining the provider associated with the page group with unique identifier %1. An attempt to import this transport set could result in errors.**

**Cause:** An unexpected error occurred while obtaining the specified provider. The export proceeded without the provider definition. An attempt to import the resulting transport set could result in errors. For example, the navigation page portlets dependent on this provider could be lost. This error may indicate a data inconsistency issue in the base system, possibly in the page group table or the provider metadata table.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWU-74126: No data was found while obtaining the page with unique identifier %1 and page group %2. This page is a page-link dependency of another page. The page link will get lost on import.**

**Cause:** An unexpected error occurred while obtaining the specified page. This page is a page-link dependency of another page. The export will proceed without the page link. An attempt to import the resulting transport set will result in errors, including the loss of the page link. This error may indicate a data inconsistency issue in the base system. For example, inconsistent page link entries may be present in the page table.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74127: Unable to get the page with unique identifier %1 and page group %2. This page is page-link dependency of another page. The page link will get lost on import.**

**Cause:** An unexpected error occurred while adding the page link dependency. The export proceeded without the page link dependency definition. An attempt to import the resulting transport set will result in errors, most likely because the page link will get lost.

**Action:** Contact Oracle Support Services, and provide the export logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74128: Cannot find the template metadata with unique identifier %1 and page group %2. Import of this transport set could result in errors for pages based on this template.**

**Cause:** An unexpected error occurred while obtaining the specified template metadata. The export proceeded without the template. Importing the resulting transport set could result in errors for any pages that are based on the specified template. This may a data inconsistency issue in the base system. For example, the page table may contain a inconsistent template entry.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74129: Multiple records were found while obtaining the template metadata with unique identifier %1 and page group %2. Importing this transport set could result in errors for pages based on this template.**

**Cause:** An unexpected error occurred while obtaining the specified template's metadata. The export proceeded without the template. Importing the resulting transport set could result in errors for pages based on this template. This error may indicate a data inconsistency issue in the base system, possibly in the template metadata table.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74132: Unable to get the UI template %1 of schema %2 associated with the given page.**

**Cause:** An unexpected error occurred while adding the specified UI template. The export proceeded without the template. Importing the resulting transport set could result in broken connections between pages and their related UI templates.

**Action:** Contact Oracle Support Services, and provide the export logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74133: Unable to get the dependencies associated with the page %1. Import this transport set could result in errors for this page.**

**Cause:** An unexpected error occurred while adding the dependencies associated with the page. The export proceeded without the page dependencies. Importing the resulting transport could result in errors for this page.

**Action:** Contact Oracle Support Services, and provide the export logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74134: Unable to get the default settings of the page group with unique identifier %1. Some of the default settings could be lost on import.**

**Cause:** An unexpected error occurred while adding the specified page group's default settings. The export proceeded without them. Importing the resulting transport set could result in loss of the page group's default settings.

**Action:** Contact Oracle Support Services, and provide the export logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74135: Unable to add the page group with unique identifier %1 as an external dependency. An attempt to import this transport set could result in errors.**

**Cause:** An unexpected error occurred while adding the page group as an external dependency. The export proceeded without it. Importing the resulting transport set could result in errors attributable to the omitted page group.

**Action:** Contact Oracle Support Services, and provide the export logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74136: Unable to add the category with unique identifier %1 of the page group %2 as an external dependency. Import of this transport set could result in errors.**



---

**Cause:** An unexpected error occurred while adding the category as an external dependency. The export proceeded without adding the category. Importing the resulting transport set could result in errors for any children of the omitted category.

**Action:** Contact Oracle Support Services, and provide the export logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74137: Unable to add the perspective with unique identifier %1 of the page group %2 as an external dependency. Import of this transport set could result in errors.**

**Cause:** An unexpected error occurred while adding the perspective as an external dependency. The export proceeded without the perspective. Importing the resulting transport set could result in errors for any children of the omitted perspective.

**Action:** Contact Oracle Support Services, and provide the export logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74138: Unable to add the page with unique identifier %1 of the page group %2 as an external dependency. Import of this transport set could result in errors.**

**Cause:** An unexpected error occurred while adding the page as an external dependency. The export proceeded without the page. Importing the resulting transport set could result in errors for any children of the omitted page.

**Action:** Contact Oracle Support Services, and provide the export logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74139: Unable to add the color %1. The components using this color that are imported from this transport set will use the default color that is specified for like components on the target.**

**Cause:** An unexpected error occurred while adding the specified color. The export proceeded without the color metadata. All the components in the resulting transport set that used this color will no longer have access to it. On the target, these components will use the default color that is specified for like components. This error may indicate a data inconsistency issue in the base system.

**Action:** As a workaround, after importing this transport set, bring in the associated color and re-associate it with the relevant components. Before proceeding with the import of this transport set, consult the Export/Import section of the Portal Configuration Guide for additional information on object behavior.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWU-74140: Unable to add the font %1. The components that use this font that are imported from this transport set will use the default font that is specified for like components on the target.**

**Cause:** An unexpected error occurred while adding font. The export proceeded without the font metadata. If the resulting transport set contains components that used this font, on import they will use the default font specified on the target. This error may indicate a data inconsistency issue in the base system.

**Action:** As a workaround, after importing this transport set, bring in the associated font and re-associate it with the relevant components. Before proceeding with the import of this transport set, consult the Export/Import section of the Portal Configuration Guide for additional information on object behavior.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74141: Unable to add the image %1. The components in this transport set that use this image will use the target's default image instead. The default image is often an X**

**Cause:** An unexpected error occurred while adding the specified image. The export proceeded without the image. Components that used this image that are imported from the resulting transport set will use the target's default image. This error may indicate a data inconsistency issue in the base system.

**Action:** As a workaround, after importing this transport set, bring in the associated image and re-associate it with the relevant components. Before proceeding with the import of this transport set, consult the Export/Import section of the Portal Configuration Guide for additional information on object behavior.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74142: Unable to add the JavaScript %1. The components in the transport set that use this script will use the default JavaScript.**

**Cause:** An unexpected error occurred while adding the JavaScript. The export proceeded without it. If the resulting transport set is imported, the components that used this script on the base will use the default JavaScript on the target. This error may indicate a data inconsistency issue in the base system.

**Action:** As a workaround, after importing this transport set, bring in the associated JavaScript and re-associate it with the relevant components. Before proceeding with the import of this transport set, consult the Export/Import section of the Portal Configuration Guide for additional information on object behavior.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74143: Unable to add the colors**

**Cause:** An unexpected error occurred while adding the colors, images, and fonts that are referenced by the template. The export proceeded without the referenced

---

objects. Importing the resulting transport set will result in the use of the target's default values for the referenced objects. This error may indicate a data inconsistency issue in the base system.

**Action:** As a workaround, after importing this transport set, bring in the associated objects and re-associate them with the template. Before importing this transport set, consult the Export/Import section of the Portal Configuration Guide for additional information on object behavior.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74144: Unable to add the template %1. This transport set will not contain this template.**

**Cause:** An unexpected error occurred while adding the specified template. The export proceeded without the template. Importing the resulting transport set could result in errors should any objects be dependent upon this template. This error may indicate a data inconsistency issue in the base system.

**Action:** As a workaround, after importing this transport set, bring in the associated template and re-associate it with the relevant objects. Before importing this transport set, consult the Export/Import section of the Portal Configuration Guide for additional information on object behavior.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74145: Unable to add the LOV %1. An attempt to import this transport set could result in errors.**

**Cause:** An unexpected error occurred while adding the specified LOV. The export proceeded without the LOV. This error may indicate a data inconsistency issue in the base system.

**Action:** As a workaround, after importing this transport set, bring in the associated LOV and re-associate it with the relevant objects. Before proceeding with the import of this transport set, consult the Export/Import section of the Portal Configuration Guide for additional information on object behavior.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74146: Unable to add the link %1. An attempt to import this transport set could result in errors.**

**Cause:** An unexpected error occurred while adding the specified link. The export proceeded without the link. Importing the resulting transport set could result in errors related to objects that use this link. This error may indicate a data inconsistency issue in the base system.

**Action:** As a workaround, after importing this transport set, bring in the associated link and re-associate it with the relevant objects. Before importing the transport set, consult the Export/Import section of the Portal Configuration Guide for additional information on object behavior.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WWU-74147: Unable to add all the colors. Importing this transport set could result in errors.**

**Cause:** An unexpected error occurred while adding all the colors. The export proceeded without the colors. Importing the resulting transport set could result in the application of undesirable colors to any affected objects. This error may indicate a data inconsistency issue in the base system.

**Action:** As a workaround, after importing this transport set, bring in the associated color and re-associate it with the relevant objects. Before importing this transport set, consult the Export/Import section of the Portal Configuration Guide for additional information on object behavior.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74148: Unable to add all the fonts. Importing this transport set could result in errors.**

**Cause:** An unexpected error occurred while adding all the fonts. The export proceeded without the fonts. Importing the resulting transport set could result in the application of undesirable fonts to affected objects. This error may indicate a data inconsistency issue in the base system.

**Action:** As a workaround, after importing this transport set, bring in the associated fonts and re-associate them with the relevant objects. Before importing this transport set, consult the Export/Import section of the Portal Configuration Guide for additional information on object behavior.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74150: Unable to add all the images. Import of this transport set could result in errors.**

**Cause:** An unexpected error occurred while adding all the images. The export proceeded without the images. Import of the resulting transport set could result in problems for the objects that use these images. This error may indicate a data inconsistency issue in the base system.

**Action:** As a workaround, after importing this transport set, bring in the associated images and re-associate them with the relevant objects. Before proceeding with the import of this transport set, consult the Export/Import section of the Portal Configuration Guide for additional information on object behavior.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74151: Unable to add all the JavaScripts. Import of this transport set could result in errors.**

**Cause:** An unexpected error occurred while adding all the JavaScripts. The export proceeded without these JavaScripts. Importing the resulting transport set could

---

result in problems for the objects that use these JavaScripts. This error may indicate a data inconsistency issue in the base system.

**Action:** As a workaround, after importing this transport set, bring in the associated JavaScripts and re-associate them with the relevant objects. Before proceeding with the import of this transport set, consult the Export/Import section of the Portal Configuration Guide for additional information on object behavior.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74152: Unable to add all the templates. An attempt to import this transport set could result in errors.**

**Cause:** An unexpected error occurred while adding all the templates. The export proceeded without these templates. This error may indicate a data inconsistency issue in the base system.

**Action:** As a workaround, after importing this transport set, bring in the associated templates and re-associate them with the relevant objects. Before proceeding with the import of this transport set, consult the Export/Import section of the Portal Configuration Guide for additional information on object behavior.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74153: Unable to add the objects referenced by the data component %1. Import of this transport set could result in errors.**

**Cause:** An unexpected error occurred while adding objects referenced by the specified data component. The export proceeded without the referenced objects. Import of the resulting transport set could result in errors. This error may indicate a data inconsistency issue in the base system.

**Action:** As a workaround, after importing this transport set, bring in the associated objects and re-associate them with the relevant data component. Before proceeding with the import of this transport set, consult the Export/Import section of the Portal Configuration Guide for additional information on object behavior.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74154: Unable to add the objects referenced by the report %1. Import of this transport set could result in errors.**

**Cause:** An unexpected error occurred while adding objects referenced by the specified report. The export proceeded without the referenced objects. Import of the resulting transport set could result in errors. This error may indicate a data inconsistency issue in the base system.

**Action:** As a workaround, after importing this transport set, bring in the associated objects and re-associate them with the specified report. Before proceeding with the import of this transport set, consult the Export/Import

---

section of the Portal Configuration Guide for additional information on object behavior.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74155: Unable to add the objects referenced by the menu link %1. Import of this transport set could result in errors.**

**Cause:** An unexpected error occurred while adding objects referenced by the specified menu link. The export proceeded without the referenced objects. Import of the resulting transport set could result in errors. This error may indicate a data inconsistency issue in the base system.

**Action:** As a workaround, after importing this transport set, bring in the associated objects and re-associate them with the specified menu link. Before proceeding with the import of this transport set, consult the Export/Import section of the Portal Configuration Guide for additional information on object behavior.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74156: Unable to add the objects referenced by the application %1.**

**Cause:** An unexpected error occurred while adding objects referenced by the application. The export proceeded without the referenced objects. Import of the resulting transport set could result in errors. This error may indicate a data inconsistency issue in the base system.

**Action:** As a workaround, after importing this transport set, bring in the associated objects and re-associate them with the specified application. Before proceeding with the import of this transport set, consult the Export/Import section of the Portal Configuration Guide for additional information on object behavior.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74157: Unable to add the application %1. Import of this transport set could result in errors.**

**Cause:** An unexpected error occurred while adding the specified application. The export proceeded without the application. Import of the resulting transport set could result in errors. This error may indicate a data inconsistency issue in the base system.

**Action:** As a workaround, after importing this transport set, bring in the associated objects and re-associate them with the specified application. Before proceeding with the import of this transport set, consult the Export/Import section of the Portal Configuration Guide for additional information on object behavior.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWU-74158: Unable to add the component %1 of type %2 of the application %3. Import this transport set could result in errors.**

**Cause:** An unexpected error occurred while adding the specified component. The export proceeded without the component. Import of the resulting transport set could result in errors. This error may indicate a data inconsistency issue in the base system.

**Action:** As a workaround, after importing this transport set, bring in the specified component. Before proceeding with the import of this transport set, consult the Export/Import section of the Portal Configuration Guide for additional information on object behavior.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74159: Unable to add item link dependency of item having unique identifier (id) %1 in pagegroup with identifier %2.**

**Cause:** An unexpected error occurred while extracting item link dependency.

**Action:** The export will proceed without the dependency. On import, the itemlink item will lose the association. Edit the item link and point to another item or bring the page containing the required item from the source for it to work. Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74160: Unable to add item template dependency having unique identifier %1 with pagegroup identifier %2. The export will proceed without the item template. On import**

**Cause:** An unexpected error occurred while adding item template dependency.

**Action:** The export will proceed without the item template dependency. Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74161: Unable to add HTML template dependencies of regions in page with unique identifier %1 in pagegroup with identifier %2. The export will proceed without HTML template dependencies. However the import could result in errors.**

**Cause:** An unexpected error occurred while adding HTML template of region. This could be due to a corrupted HTML template entry in region table.

**Action:** The export will proceed without HTML template dependencies. Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWU-74162: An unexpected error occurred while adding HTML template dependencies of pagegroup with identifier %1. The export will proceed without them. Import could result in errors for pages/regions using them.**

**Cause:** An unexpected error occurred while adding HTML template dependencies of given pagegroup.

**Action:** The export will proceed without HTML templates. Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74163: Unable to add item placeholder dependency of item. The configured item has unique identifier %1 in pagegroup with identifier %2.**

**Cause:** An unexpected error occurred while extracting item placeholder dependency.

**Action:** The export will proceed without the item placeholder dependency. On import, the item placeholder item will lose the association. You can edit the item and point it to another item or bring the page containing the required item from the source for it to work. Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74164: An unexpected error occurred while updating object details. %1**

**Cause:** An unexpected error occurred while updating object details.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74165: An unexpected error occurred while getting object Ids. %1**

**Cause:** An unexpected error occurred while getting object Ids.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74166: An unexpected error occurred while getting object list. %1**

**Cause:** An unexpected error occurred while getting object list.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74167: An unexpected error occurred while altering manifest data for duplicate entries in reference objects. %1**



---

**Cause:** An unexpected error occurred while altering manifest data.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74168: An unexpected error occurred while altering manifest data for duplicate entries in external objects. %1**

**Cause:** An unexpected error occurred while altering manifest data for external objects.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74169: An unexpected error occurred while altering manifest data for duplicate entries. %1**

**Cause:** An unexpected error occurred while altering manifest data.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74170: An unexpected error occurred while retrieving dependencies. %1**

**Cause:** An unexpected error occurred while retrieving dependencies.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74171: An unexpected error occurred while retrieving dependencies. %1**

**Cause:** An unexpected error occurred while retrieving dependencies.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74172: An unexpected error occurred while updating manifest data on to table. %1**

**Cause:** An unexpected error occurred while updating manifest data on to table.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

- 
- WWU-74173: An unexpected error occurred while updating manifest data for promoted objects on to table. %1**  
**Cause:** An unexpected error occurred while updating manifest data for promoted objects on to table.  
**Action:** Contact Oracle Support Services and provide the logs.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other
- WWU-74174: An invalid export id %1 is passed for dependency calculation.**  
**Cause:** An invalid export id is passed for dependency calculation  
**Action:** Make sure that a correct export id is passed. Contact Oracle Support Services and provide the logs.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other
- WWU-74175: An unexpected error occurred while calculating manifest for a transport set. %1**  
**Cause:** An unexpected error occurred while calculating manifest for a transport set.  
**Action:** Contact Oracle Support Services and provide the logs.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other
- WWU-74176: No objects were found in table for export id %1 while calculating manifest.**  
**Cause:** No objects were found in table while calculating manifest.  
**Action:** Contact Oracle Support Services and provide the logs.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other
- WWU-74180: An unexpected error occurred while altering the dependency list for each explicit object that was deleted. %1**  
**Cause:** An unexpected error occurred while altering the dependency list for each explicit object that was deleted.  
**Action:** Contact Oracle Support Services and provide the logs.  
**Level:** 1  
**Type:** ERROR  
**Impact:** Other
- WWU-74181: An unknown error while deleting object %2 from detail table for export id %1. %3.**  
**Cause:** An unexpected error occurred while deleting object from detail table.

---

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74182: An unknown error while deleting the given set of explicit objects. %1.**

**Cause:** An unexpected error occurred while deleting the given set of explicit objects.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74183: An unknown error while deleting the newly added objects and calculate manifest. %1.**

**Cause:** An unexpected error occurred while deleting the newly added objects and calculate manifest.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74184: An unknown error while getting all the explicit objects in the given transport set. %1.**

**Cause:** An unexpected error occurred while getting all the explicit objects in the given transport set.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74185: An unknown error while getting all the reference objects in the given transport set. %1.**

**Cause:** An unexpected error occurred while getting all the reference objects in the given transport set.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74186: An unknown error while getting all the external objects in the given transport set. %1.**

**Cause:** An unexpected error occurred while getting all the external objects in the given transport set.

**Action:** Contact Oracle Support Services and provide the logs.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74187: An invalid import mode %1 is passed for dependency calculation while updating the record.**

**Cause:** An invalid import mode is passed for dependency calculation.

**Action:** Make sure that a correct mode is passed. Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74188: An invalid import category %1 is passed for dependency calculation while updating the record.**

**Cause:** An invalid import category is passed for dependency calculation.

**Action:** Make sure that a correct category is passed. Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74189: An unknown error while updating the import modes of the objects passed. %1.**

**Cause:** An unexpected error occurred while updating the import modes of the objects passed.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74190: User Performing the operation does not have superadmin privilege to promote shared object.**

**Cause:** User Performing the operation does not have superadmin privilege to promote shared object.

**Action:** Ask portal administrator to assign the user superadmin privilege.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74191: An unknown error while promoting a given set of external objects. %1.**

**Cause:** An unexpected error occurred while promoting a given set of external objects.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWU-74201: The PL/SQL item with the unique identifier %1 will throw a runtime error because the schema %2 associated with it is not present on the target.**

**Cause:** The schema associated with the PL/SQL item does not exist on the target database.

**Action:** Migrate the schema using the database export/import utilities, and re-associate it with the PL/SQL item.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74202: The PL/SQL page %1 will throw a runtime error because the schema %2 associated with it is not present on the target. You can migrate the schema later on and re-associate it again.**

**Cause:** The schema does not exist on the target database.

**Action:** Migrate the schema using the database export/import utilities, and re-associate it with the PL/SQL page.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74203: The PL/SQL attribute %1 will throw a runtime error because the schema %2 associated with it is not present on the target.**

**Cause:** The schema associated with the PL/SQL attribute does not exist on the target database.

**Action:** Migrate the schema using the database export/import utilities, and re-associate it with the PL/SQL attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74204: The LOV %1 associated with %2 attribute does not exist. The LOV is being reset.**

**Cause:** The list of values does not exist on the target.

**Action:** Bring in the list of values separately, and re-associate or promote it to the transport set in the source. Then re-import it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74205: The contained object %1 will not be imported because the container object %2 is reused for the target.**

**Cause:** This can happen when the contained object is forcefully set to reuse mode because the container object was set to reuse mode.

**Action:** If you want the contained object to be merged to the target, bring in the container object in overwrite mode.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74206: Unable to import the page group %1. The internal identifier of the new page group already exists.**

**Cause:** The internal identifier of the page group being imported was already in use on the target.

**Action:** Try importing again. If the retry fails, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74207: Unable to update the properties of the page group %1 being imported.**

**Cause:** An unexpected error occurred while updating the page group properties.

**Action:** Try importing again. If the retry fails, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74208: Unable to propagate the new internal identifier of the page group being imported.**

**Cause:** The internal identifier of the page group was not updated to all of the page group objects.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74209: Unable to resolve the text attribute with internal identifier %1**

**Cause:** Resolution of the item with the text attribute failed.

**Action:** Try importing again. If the retry fails, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74210: Multiple records found pointing to the same text attribute with internal identifier %1**

**Cause:** More than one row was found for the text attribute of the custom item during resolution.

**Action:** Try importing again. If the retry fails, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74211: Unable to resolve the URL with internal identifier %1**

---

**Cause:** Resolution of the item with the URL attribute failed.

**Action:** Try importing again. If the retry fails, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74212: Multiple records found pointing to the same URL with internal identifier %1**

**Cause:** More than one row was found for the URL during resolution.

**Action:** Try importing again. If the retry fails, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74213: Unable to find the page type function with internal identifier %1 of the page group with internal identifier %2 .**

**Cause:** The attempt to find the page type function failed.

**Action:** Try importing again. If the retry fails, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74214: Unable to update the attribute %1.**

**Cause:** The attribute update failed.

**Action:** Try importing again. If the retry fails, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74215: Unable to update the style %1.**

**Cause:** The style update failed.

**Action:** Try importing again. If the retry fails, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74216: Unable to add translation for category %1 of the page group with internal identifier %2 .**

**Cause:** Failed to add translation for category.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWU-74217: Unable to add translation for perspective %1 of page group with internal identifier %2 .**

**Cause:** Failed to add translation for perspective.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74218: create\_item\_DAV\_err | Due to DAV error**

**Cause:** An unexpected DAV error occurred while creating the item on the target.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74219: Due to an unexpected error**

**Cause:** An unexpected error occurred while creating the item on the target.

**Action:** Try importing again. If the retry fails, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74220: Due to DAV error**

**Cause:** An unexpected DAV error occurred while updating the item on the target.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74221: Due to an unexpected error**

**Cause:** An unexpected error occurred while updating the item on the target.

**Action:** Try importing again. If the retry fails, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74222: Unable to create the region attributes for the region with unique identifier %1 .**

**Cause:** An unexpected error occurred while creating the region attributes.

**Action:** Try importing again. If the retry fails, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other



---

**WWU-74223: Unable to create region with unique identifier %1 for the page with internal identifier %2 because it already exists on the target system.**

**Cause:** Could not create region because it already exists on the target system.

**Action:** Try importing again. If the retry fails, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74224: Unable to create region with unique identifier %1 for the page with internal identifier %2**

**Cause:** An unexpected error occurred while creating the region on the target.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74225: Unable to update region with unique identifier %1 for the page with internal identifier %2**

**Cause:** An unexpected error occurred while updating the region on the target.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74226: Unable to update properties of the region with unique identifier %1 because it exists on another page.**

**Cause:** Region exists on another page.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74227: Unable to create Page**

**Cause:** An unexpected error occurred while creating the page on the target.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74228: Unable to update Page**

**Cause:** An unexpected error occurred while updating the page on the target.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWU-74229: Unable to share the portlet instance %1.**

**Cause:** Failed to share the portlet instance on the target.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74230: Unable to locate page group %1 on the target. Child objects of this page group will not be imported.**

**Cause:** The Child objects of this page group will not be imported because the page group does not exist on the target.

**Action:** In the source, promote the page group in your transport set, or export the page group explicitly, then import it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74231: The source default language %1 of the page group %2 is either not installed or not available on the target.**

**Cause:** The default language of the page group is either not installed or not available on the target.

**Action:** Install and make available the default language on the target and re-import.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74232: Default language %1 of the page group %2 is not installed on the target portal.**

**Cause:** The source page group's default language is not installed on the target portal.

**Action:** Install the language on the target, and re-import.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74233: An unexpected error occurred while deleting version %1 of item with unique identifier %2 .**

**Cause:** Deleting an item version has resulted in an unexpected error.

**Action:** Verify that the page with the item renders properly. If it doesn't, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWU-74234: Unable to merge approval related infrastructure due to an unexpected error.**

**Cause:** An unexpected error occurred while merging approval-related infrastructure on the target.

**Action:** Manually re-create the approval process on the target.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74235: Unable to sync style attributes due to an unexpected error.**

**Cause:** An unexpected error occurred while synchronizing style attributes on the target.

**Action:** Ensure that all the imported styles have correct settings for their attributes. If they don't, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74236: The template %1 cannot be reused because it has undergone significant changes since the last import.**

**Cause:** The template on the target has undergone significant changes since the last import. This will affect the import of pages that are dependent on the template. Consequently, the template cannot be reused.

**Action:** Set the import mode to overwrite. Save for later, and rerun precheck.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74237: The page %1 has failed precheck because its template %2 cannot be reused. Make %2 overwrite to proceed with import.**

**Cause:** The page's template on the target has undergone significant changes since the last import. Consequently, the template cannot be reused if the pages are to be overwritten.

**Action:** Set the import mode of the template to overwrite. Save for later, and rerun precheck.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74239: Portal Template %1 belonging to %2 page group is being imported in replace on import mode. Any changes done to the template objects (items**

**Cause:** Portal template replication deletes all template objects (items, portlets, etc) found in the pages using the template and re-creates them based on the template definition. This will remove any changes done at the page level for those template objects.

**Action:** If portal template needs to under-go constant updates do not make changes to the pages' template objects. If template objects changes need to be

---

preserved, bring the portal template in reuse mode (uncheck the Replace on Import checkbox in the manifest).

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74240: Portal Template %1 belonging to %2 pagegroup is being reused. If pages using the template accompany the template in the same transport set (and are imported in replace on import mode) they might have inconsistent behavior upon import.**

**Cause:** When importing the portal template in reuse mode (and there are significant changes between the source and the target template) and pages using the template are imported in replace on import mode, the pages will not be correctly synchronized with portal template on the target.

**Action:** Make sure the source and the target template are synchronized first by importing the portal template in overwrite mode. Once this synchronization is done, pages using the template can be imported in replace on import mode with the template set to reuse mode.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74241: The unique identifier of the source page/template/navigation page %1 of the page group %2 does not match the unique identifier of target page/template/navigation page %1. The page name you specified in source is already in use in target.**

**Cause:** A different page already exists on the target with the same name.

**Action:** Delete the page on the target and import again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74242: The unique identifier of the source category %1 of the page group %2 does not match the unique identifier of target category %1. The category name you specified on source is already in use on target.**

**Cause:** A different category already exists on the target with the same name.

**Action:** Delete the category on the target and import again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74243: The source category %1 has been promoted to shared objects but the same category %2 exists on the target in a local page group. The local category on the target cannot be overwritten or reused by the shared category on the source. Promote the local category on the target to shared objects and import the dump file again.**

**Cause:** The source category has been promoted but the same category exists on the target in a local page group.

---

**Action:** Promote the local category on the target and re-import.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74244:** The source category %1 belongs to a local page group. The same category %2 on the target has been promoted to shared objects. The shared category on the target cannot be overwritten or reused by the local category on the source.

**Cause:** The source category belongs to a local page group. The same category on the target has been promoted.

**Action:** Promote the local category on the source and re-import it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74245:** The unique identifier of the source perspective %1 of the page group %2 does not match the unique identifier of target perspective %1. The perspective name you specified on source is already in use on target.

**Cause:** A different perspective already exists on the target with the same name.

**Action:** Delete the perspective on the target and import again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74246:** The source perspective %1 has been promoted to shared objects but the same perspective %2 exists on the target in a local page group. The local perspective on the target cannot be overwritten or reused by the shared perspective on the source. Promote the local perspective on the target to shared objects and import the dump file again.

**Cause:** The source perspective has been promoted but the same perspective exists on the target in a local page group.

**Action:** Promote the local perspective on the target and re-import.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74247:** The source perspective %1 belongs to a local page group. The same perspective %2 on the target has been promoted to shared objects. The shared perspective on the target cannot be overwritten or reused by the local perspective on the source.

**Cause:** The source perspective belongs to a local page group. The same perspective on the target has been promoted.

**Action:** Promote the local perspective on the source and re-import it.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWU-74248: Precheck failed for %1 %2 of %3 pagegroup as %2 is being imported as an external object which does not exist on the target. An external object must exist on the target for it to be re-used.**

**Cause:** Object is being imported as an external object but it does not exist on the target.

**Action:** Promote the external object in the transport set and re-import.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74249: Unknown error occurred while resetting syspriv name for page with unique identifier %1. The syspriv name will not be reset for this page.**

**Cause:** An unexpected error occurred while resetting the syspriv name for that page.

**Action:** Check if all the pages imported appear normally with all the links in the navigator. Otherwise, contact Oracle Support Services with the necessary logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74250: The page configured for generic page portlet: %1 does not exist on target. Therefore resetting the values to default.**

**Cause:** The page configured for portlet was not found. The user might not have added the dependent page to the transport set. Normally you would see a warning status against the explicit object.

**Action:** Add the dependent page to the transport set and re-import. Or bring in the required page separately and reconfigure it manually.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74251: The unique identifier(GUID) of the source page group %1 does not match the unique identifier of target page group %1. The page group name you specified in source is already in use in target.**

**Cause:** A different page group already exists on the target with the same name.

**Action:** Delete the page group on the target and import again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74252: Page group %1 is not found in target or in the transport set**

**Cause:** The page group object listed under External Objects is not present on the target or in the transport set. The import cannot proceed for the explicitly selected object since its page group is not available on target.

**Action:** In source, promote the page group object from the external objects section and export/import the transport set again.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74253: You (%1) cannot create a shared object since you do not have ANYTRANSPORTSET\_MANAGE privilege.**

**Cause:** A shared object can be imported only by a user who has ANYTRANSPORTSET\_MANAGE privilege.

**Action:** Contact your administrator to obtain that privilege and then perform the import.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74254: HTML Template %1 belonging to %2 pagegroup does not exist on the target. All pages and regions using it will be reset.**

**Cause:** The HTML template does not exist on the target and therefore its association was reset.

**Action:** The user can migrate the HTML template individually and re-associate it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74255: Portal Template %1 belonging to %2 pagegroup does not exist on the target. All pages and items using it will be reset.**

**Cause:** The Portal template does not exist on the target and therefore its association was reset.

**Action:** The user can migrate the Portal template individually and re-associate it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74256: An unknown fatal error has occurred during the import of transport set. See the debug logs for details.**

**Cause:** An unknown fatal error has occurred during the import of transport set.

**Action:** See the debug log for details and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74257: The language %1 (%2) is not installed on target and hence all the language related data will be deleted.**

**Cause:** The specified language is not installed on target.

**Action:** Install the language and re-import.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWU-74263: Deleting the text entries from text/plsql items for the null text handler.**

**Cause:** Text ID is null for the item.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74264: Deleting the text entries from pagetype attributes for the null text handler.**

**Cause:** Text ID is null for pagetype attribute.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74265: Deleting the url entries from url-items for the null url handler.**

**Cause:** Url ID is null for the item.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74266: Deleting the url entries from pagetype attributes for the null url handler.**

**Cause:** Url ID is null for pagetype attribute.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74267: An unknown fatal error has occurred during the export of transport set. See the debug logs for details.**

**Cause:** An unknown fatal error has occurred during the export of transport set.

**Action:** See the debug log for details and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74268: The page configured for news announcement OIP portlet: %1 does not exist on target. Therefore resetting the values to null.**

**Cause:** The page configured for portlet was not found. It could have been deleted on the source.

**Action:** Edit the portlet and re-configure it to point to any valid page.



---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74269: The pagegroup configured for OIP summary portlet: %1 was not found on target. Therefore resetting the values to null.**

**Cause:** The pagegroup configured for portlet was not found. This could be due to a data inconsistency or an import error.

**Action:** Edit the portlet and re-configure it to point to a valid pagegroup.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74271: Mapping not found for Region Id: %1. Hence display all regions property is being set for this page portlet.**

**Cause:** Regions chosen for selective display customization for page portlets have issues during resolution.

**Action:** Instead of selective regions being displayed for the page portlet, all the regions will be displayed upon import.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74301: An error occurred while exporting registration properties.**

**Cause:** A problem may have occurred while inserting entries into the registration properties transport table.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74302: An error occurred while exporting user category maps.**

**Cause:** A problem may have occurred while inserting entries into the role maps transport table.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74303: An error occurred while exporting the ws-security information.**

**Cause:** A problem may have occurred while selecting and inserting the entries into the ws-security transport table.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWU-74304: The WSRP provider %1 is configured for ws-security. But**

**Cause:** The keystore and certificate information are not migrated.

**Action:** Edit the provider and furnish the keystore and certificate information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74305: An error occurred while importing ws-security information for the provider %1.**

**Cause:** A problem may have occurred while inserting entries into the ws-security table.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74402: There has been a metadata inconsistency.**

**Cause:** A metadata inconsistency resulted from the direct manipulation of system tables, such as WWAPP\_APPLICATION\$, WWAPP\_APPLICATION\_DETAIL\$, WWV\_MODULES\$, or WWV\_MODULE\_DETAILS\$, or from an incorrect component state during export.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74403: Metadata for %1 is not available in %2.**

**Cause:** Metadata is not available due to the direct manipulation of system tables, such as WWAPP\_APPLICATION\$, WWAPP\_APPLICATION\_DETAIL\$, WWV\_MODULES\$, or WWV\_MODULE\_DETAILS\$.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74404: %1 contains more than one row for %2.**

**Cause:** This error message can result from the direct manipulation of system tables, such as WWAPP\_APPLICATION\$, WWAPP\_APPLICATION\_DETAIL\$, WWV\_MODULES\$, or WWV\_MODULE\_DETAILS\$.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74405: %1 will not be considered for export.**

---

**Cause:** Export time pre-checks have failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74406: No versions for component %1 are available at the time of this export.**

**Cause:** No versions are available due to the direct manipulation of system tables, such as WWAPP\_APPLICATION\$, WWAPP\_APPLICATION\_DETAIL\$, WWV\_MODULES\$, or WWV\_MODULE\_DETAILS\$.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74407: Component %1 is in %2 state at the time of this export.**

**Cause:** At the time of export, a production version was unavailable. This situation can arise if a component has only one version and that version is being edited, or if all the versions of the component are archive versions.

**Action:** Complete or cancel the edit operation before exporting. Ensure that the component has a production version.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74408: Incorrect data detected for component %1 in table %2.**

**Cause:** Incorrect data due to the direct manipulation of system tables, such as WWAPP\_APPLICATION\$, WWAPP\_APPLICATION\_DETAIL\$, WWV\_MODULES\$, or WWV\_MODULE\_DETAILS\$ was detected.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74409: Metadata for LOV %1 is not available in %2.**

**Cause:** Metadata is not available due to the direct manipulation of metadata tables for lists of values.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74410: More than one row was detected for LOV %1 in %2.**

**Cause:** More than one row was detected for the list of values (LOVs) due to the direct manipulation of metadata tables for LOVs.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74411: Metadata for menu %1 is not available in %2.**

**Cause:** Menu metadata is not available due to the direct manipulation of metadata tables for menus.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74412: Metadata for data component %1 is not available in %2.**

**Cause:** Component metadata is not available due to the direct manipulation of metadata tables for data component.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74413: More than one row detected for data component %1 in %2.**

**Cause:** More than one row was detected for data component due to the direct manipulation of metadata tables for data component.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74414: At the time of this export**

**Cause:** Direct user intervention could have dropped the DB Provider schema.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74415: Metadata for owner of %1 is not available in %2.**

**Cause:** Owner metadata is not available due to the direct manipulation of system tables, such as WWAPP\_APPLICATION\$, WWAPP\_APPLICATION\_DETAIL\$, WWV\_MODULES\$, or WWV\_MODULE\_DETAILS\$.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74416: Provider ID is null**

---

**Cause:** The provider ID is null due to the direct manipulation of system tables, such as WWAPP\_APPLICATION\$, WWAPP\_APPLICATION\_DETAIL\$, WWV\_MODULES\$, or WWV\_MODULE\_DETAILS\$.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74417: The value %1 is invalid for flag %2 in table %3 .**

**Cause:** Value is invalid due to the direct manipulation of system tables, such as WWAPP\_APPLICATION\$, WWAPP\_APPLICATION\_DETAIL\$, WWV\_MODULES\$, or WWV\_MODULE\_DETAILS\$.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74418: The combination of values in columns EXPOSE\_AS\_PROVIDER and PROVIDER\_ID for component %1 is incorrect in table WWAPP\_APPLICATION\$.**

**Cause:** The combination of values is incorrect due to the direct manipulation of system tables, such as WWAPP\_APPLICATION\$, WWAPP\_APPLICATION\_DETAIL\$, WWV\_MODULES\$, or WWV\_MODULE\_DETAILS\$.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74419: Could not perform pre-check due to insufficient data.**

**Cause:** Direct manipulation of the system tables could have caused the unavailability of data.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74502: An error occurred while exporting data from web provider %1.**

**Cause:** Export of personalization data from the web provider, or one of its portlets, failed.

**Action:** Check the debug messages for possible reasons for this failure, for example: <br /> 1) Web provider's application server may be down or inaccessible<br /> 2) Underlying network error<br /> If you are unable to further diagnose the problem, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWU-74505: An error occurred while importing data to the web provider %1.**

**Cause:** Import of personalization data to the web provider, or one of its portlets, failed.

**Action:** Check the debug messages for possible reasons for this failure, for example: <br /> 1) Web provider's application server may be down or inaccessible<br /> 2) Underlying network error<br /> If you are unable to further diagnose the problem, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74511: The version of the web provider you are trying to export from is not supported. Export cannot proceed for web provider %1.**

**Cause:** The web provider is not version 10.1.2.0.0 or greater, or you are trying to export customizations from a Federated Portal Adapter provider.

**Action:** Contact the web provider's administrator to arrange for this web provider to be upgraded. Note that Federated Portal Adapter providers do not support export/import of customizations.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74512: The version of the web provider you are trying to import is not supported. Import cannot proceed for this web provider %1.**

**Cause:** The web provider is not version 10.1.2.0.0 or greater, or you are trying to import customizations from a Federated Portal Adapter provider.

**Action:** Contact the web provider's administrator to arrange for this web provider to be upgraded. Note that Federated Portal Adapter providers do not support export/import of customizations.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74513: The version of the web provider you are trying to export/import is not supported. Export/Import will not proceed for this web provider.**

**Cause:** Import of web provider or some of its portlets failed.

**Action:** It is possible that this version of the web provider is not supported by export and import. Refer to the documentation for supported versions. If you are still unable to export or import, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74514: Failed to write to transport set.**

**Cause:** An internal error occurred during the import/export operation.

**Action:** Examine other error messages for more information if available, or contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74515: An unexpected error occurred during import.**

**Cause:** An internal error occurred during the import operation.

**Action:** Examine other error messages for more information if available, or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74516: An unexpected error occurred during export.**

**Cause:** An internal error occurred during the export operation.

**Action:** Examine other error messages for more information if available, or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74517: Could not connect to web provider at %1.**

**Cause:** Could not connect to the web provider to import or export customizations.

**Action:** Make sure that the web provider is available and that there are no network issues.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74518: Timed out after %1ms waiting for response from web provider at %2.**

**Cause:** A timeout occurred during communication with the web provider to import or export customizations.

**Action:** Make sure that the web provider is available and that there are no network issues.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74519: Web provider does not implement data transport methods.**

**Cause:** The specified web provider does not support import/export of customization data.

**Action:** Contact the web provider's administrator to enable this feature, or upgrade the web provider.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWU-74520: HMAC authentication failed with provider %1 using shared key %2.**

**Cause:** An internal error occurred during the import/export operation.

**Action:** Examine other error messages for more information if available, or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74521: Web provider server error. Connection %1 unavailable**

**Cause:** An internal error occurred on the remote web provider during the import/export operation.

**Action:** Examine the error stack for more information, or contact the web provider's administrator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74522: Unable to create HMAC checksum for provider %1 using shared key %2.**

**Cause:** An internal error occurred during the import/export operation.

**Action:** Examine other error messages for more information if available, or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74523: An unexpected error occurred during the transport operation.**

**Cause:** An internal error occurred during the import/export operation.

**Action:** Examine other error messages for more information if available, or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74524: Unable to contact remote web provider: invalid URL %1.**

**Cause:** Could not connect to the web provider to import or export customizations due to an invalid provider URL.

**Action:** Correct the web provider URL.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74525: Unable to interact with the database.**

**Cause:** An internal error occurred during the import/export operation.

**Action:** Examine other error messages for more information if available, or contact Oracle Support Services.



---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74526: Failed to read from transport set for portlet instance %1**

**Cause:** An internal error occurred during the import/export operation.

**Action:** Examine other error messages for more information if available, or contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74550: An unexpected error occurred while exporting providers.**

**Cause:** An unexpected error occurred while exporting providers.

**Action:** Check the debug logs for further details. Contact Oracle Support Services before importing.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74551: An unexpected error occurred while exporting provider groups.**

**Cause:** An unexpected error occurred while exporting providers groups.

**Action:** Check the debug logs for further details. Contact Oracle Support Services before importing.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74552: An unexpected error occurred while exporting proxies.**

**Cause:** An unexpected error occurred while exporting proxies.

**Action:** Check the debug logs for further details. Contact Oracle Support Services before importing.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74553: Unexpected Error while exporting portlet preferences**

**Cause:** An unexpected error occurred while exporting portlet preferences.

**Action:** Check the debug logs for further details. Contact Oracle Support Services before importing.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74554: An unexpected error has occurred**

---

**Cause:** An unexpected error has caused the entire provider export to be rolled back.

**Action:** Check the debug logs for further details and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74555: An unexpected error occurred while importing proxies.**

**Cause:** An unexpected error occurred while importing proxies.

**Action:** Check the debug logs for further details and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74556: An unexpected error occurred while updating providers.**

**Cause:** An unexpected error occurred while updating provider information on the target.

**Action:** Check the debug logs for further details and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74557: Preference name %1 for the portlet with reference path %2 could not be created**

**Cause:** An unexpected error occurred while importing portlet preferences.

**Action:** Check the debug logs for further details and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74558: Unable to create the preference value for name %1 of the portlet with reference path %2**

**Cause:** An unexpected error occurred while importing the portlet's preferences.

**Action:** Check the debug logs for further details and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74559: An unexpected error occurred while setting edit defaults for the portlet with reference path %1.**

---

**Cause:** An unexpected error occurred while setting edit defaults for the imported portlets.

**Action:** Check the debug logs for further details and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74560: Unable to validate the portlet with reference path %1.**

**Cause:** An error occurred while validating the portlet.

**Action:** Check the debug logs for further details and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74561: An error occurred while executing the web provider with unique identifier %1 of the portlet with reference path %2.**

**Cause:** An unexpected error occurred during web provider execution.

**Action:** Check the debug logs for further details and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74562: An error was encountered while the portlet with reference path %1 was executing.**

**Cause:** An unexpected error occurred during portlet execution.

**Action:** Check the debug logs for further details and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74563: The portlet with reference path %1 could not be registered due to an unexpected error.**

**Cause:** An unexpected error occurred while registering the portlet.

**Action:** Check the debug logs for further details and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74564: The portlet with reference path %1 could not be de-registered due to an unexpected error**

**Cause:** An unexpected error occurred while de-registering the portlet.

---

**Action:** Check the debug logs for further details and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74565: An unexpected error occurred while importing portlet preferences.**

**Cause:** An unexpected error occurred while importing portlet preferences.

**Action:** Check the debug logs for further details and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74566: A failure occurred while adding the provider with unique identifier %1 to the repository.**

**Cause:** Provider refresh failed.

**Action:** Check the debug logs for further details and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74567: Post-import massaging of provider objects failed due to an unexpected error.**

**Cause:** An unexpected error occurred during post-import massage of providers.

**Action:** Check the debug logs for further details and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74568: You do not have permission to register provider %1. If you proceed with the import**

**Cause:** The user does not have sufficient privileges to register the provider.

**Action:** Ask the administrator to register the provider, or perform the import as a user who has privilege to register providers.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74569: Unable to validate information for provider %1. If you proceed with the import**

**Cause:** The registration API is unable to validate provider information.

**Action:** Try to register the provider manually. If that fails, check the debug logs for further details and contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74570: Call to register provider %1 failed. If you proceed with the import**

**Cause:** The call to register provider has failed.

**Action:** Try to register the provider manually. If that fails, check the debug logs for further details and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74571: An error occurred during provider %1 registration. If you proceed with the import**

**Cause:** Provider registration failed.

**Action:** Try to register the provider manually. If that fails, check the debug logs for further details and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74572: An unexpected error occurred during provider %1 registration. If you proceed with the import**

**Cause:** An unexpected error occurred while registering the provider.

**Action:** Try to register the provider manually. If that fails, check the debug logs for further details and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74573: Pre-check for database provider %1 failed**

**Cause:** The database provider cannot be registered because its schema does not exist on the target.

**Action:** Export/import the schema and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74574: Pre-check passed with a warning for database provider %1**

**Cause:** Schema registration details differ on the source and target.

**Action:** Ensure that the provider on the target is valid. If you want the same registration details on the target as on the source, de-register the provider on the target, migrate the necessary schema, and re-import.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWU-74575: The URL specified during web provider %1 registration is different on the source and target. Import will assume that the providers are the same.**

**Ensure that the provider has the same set of portlets on the source that it has on the target. Source URL: %2. Target URL: %3**

**Cause:** The provider may have been independently registered on the target, using the same name but a different URL.

**Action:** Ensure that the provider has the same set of portlets on the source as on the target.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74576: An unexpected error occurred during the provider pre-check. Pre-check has failed.**

**Cause:** An unexpected error occurred during the provider pre-check.

**Action:** Try to register the provider manually. If that fails, check the debug logs for further details and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74579: Invalid provider implementation - %2: %1. If you proceed with the import**

**Cause:** The status of the provider implementation in the database is invalid.

**Action:** Try to compile the component manually to find out why they cannot compile (for example missing tables, custom procedures and so on). Then fix the issues and repeat the export once the components are compiled.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74580: Missing provider implementation: %1. If you proceed with the import**

**Cause:** The provider implementation package is missing.

**Action:** Compile the provider package and make sure that the implementation package is in valid state in provider schema.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74581: Missing provider package implementation: %1. If you proceed with the import**

**Cause:** The provider implementation package is missing.

**Action:** Compile the provider package and make sure that the implementation package is in valid state in provider schema.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WWU-74582: Missing provider package body implementation: %1. If you proceed with the import**

**Cause:** The provider implementation package body is missing.

**Action:** Compile the provider package and make sure that the implementation package is in valid state in provider schema.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74583: An unexpected error occurred during provider implementation pre check of: %1. If you proceed with the import**

**Cause:** An unexpected error occurred during the provider implementation pre-check.

**Action:** If the Provider registration fails, Check the Provider implementation package. Then try to register the provider manually. If that fails, check the debug logs for further details and contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74584: Invalid component implementation - %2: %1. If you proceed with the import**

**Cause:** The status of the component implementation in the database is invalid.

**Action:** Please go to the Portal UI, edit the component, click Apply to create a valid package. Then repeat the export once all the components have a valid package.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74585: Missing component implementation: %1. If you proceed with the import**

**Cause:** The component implementation package is missing.

**Action:** Please go to the Portal UI, edit the component which doesnot have a package, click Apply to create a valid package. Then repeat the export once all the components have a valid package.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74586: Missing component package implementation: %1.If you proceed with the import**

**Cause:** The component implementation package is missing.

---

**Action:** Please go to the Portal UI, edit the component which doesnot have a package, click Apply to create a valid package. Then repeat the export once all the components have a valid package.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-74587: Missing component package body implementation: %1. If you proceed with the import**

**Cause:** The component implementation package body is missing.

**Action:** Please go to the Portal UI, edit the component which doesnot have a package, click Apply to create a valid package. Then repeat the export once all the components have a valid package.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-76778: There were some inconsistencies found and fixed. Check the debug log for further details.**

**Cause:** Some inconsistencies may have occurred as a result of the import.

**Action:** Check the debug logs for further details on what the inconsistencies were and how they were corrected. Contact Oracle Support if the imported objects caused errors.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80000: All the explicit objects in the transport set have failed pre-check. The import cannot proceed.**

**Cause:** All the explicitly selected objects have failed the pre-check, either due to missing dependent objects or missing shared references.

**Action:** Check the pre-check log to determine the cause of failure. After correcting the errors, try importing again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80001: Some of the explicit objects in the transport set have failed pre-check. Proceed with import?**

**Cause:** Some of the explicitly selected objects have failed pre-check, either due to missing dependent objects or missing shared references.

**Action:** Check the pre-check log to determine the cause of failure. After correcting the errors, try importing again.

**Level:** 1

**Type:** ERROR

**Impact:** Other



---

**WWU-80002: Some of the objects in the transport set have failed pre-check with warnings/errors. Proceed with import?**

**Cause:** Some of the objects have failed pre-check, either due to missing dependent objects or missing shared references.

**Action:** Review the pre-check log to determine the reason for the failure. After correcting the errors, try importing again, or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80024: Unexpected error occurred while acquiring the transport set - %1**

**Cause:** An unknown exception occurred while acquiring.

**Action:** Contact Oracle Support Services and provide the log information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80028: Source portal and transport set names cannot be NULL.**

**Cause:** Source portal and transport set values are NULL.

**Action:** Select a source portal and then select the corresponding transport set from the list.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80029: Transport set name cannot be NULL.**

**Cause:** Transport set name is null for the selected source portal.

**Action:** Select a transport set from the list.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80030: Source portal name cannot be NULL.**

**Cause:** Source portal was not selected from the list of available sources.

**Action:** Select a source portal and then select the corresponding transport set from the list.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80041: Transport set %1 does not exist on source portal %2 for acquiring source transport set.**

**Cause:** The transport set was not found on the on source portal.

**Action:** Verify that the transport set name was entered correctly for source. Vefify the source DB link. You may need to re-create the transport set.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80101: Web Provider: %1. Invalid url: %2 or the provider is not running. If you continue with import**

**Cause:** Web provider url is invalid.

**Action:** Check the url in a browser and make sure the url and proxy settings are correct before importing the provider.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80102: Unexpected error occurred while populating provider record. %1**

**Cause:** Unexpected error occurred while populating provider record.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80154: Web provider : %1. Provider may not be running or Invalid url: %2. If you continue with import**

**Cause:** The web provider url is invalid or provider may be down.

**Action:** Check the url in a browser and make sure the url and proxy setup is correct for the provider.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80157: An unexpected error occurred while checking free space. %1.**

**Cause:** An unexpected error occurred while checking free space.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80158: The data from the source portal couldn't be acquired. %1**

**Cause:** The transport set data could not be acquired from the selected source portal.

**Action:** Select the source portal and acquire the desired transport set again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80161: job\_queue\_processes value :%1 which should be greater than %2.**

---

**Cause:** The job queue processes value should be greater than %2 to allow the execution of background jobs.

**Action:** Please increase the job\_queue\_processes before starting any Export/Import operations.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80165: Unexpected error occurred while validating http url for provider %1. %2.**

**Cause:** An unexpected error occurred while validating http url.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80181: An unexpected error occurred while checking roles and privileges for user:%1.**

**Cause:** An unexpected error occurred while checking roles and privileges for user.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80182: An unexpected error occurred while checking privileges to perform import. %1.**

**Cause:** An unexpected error occurred while checking privileges to perform import.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80183: An unexpected error occurred while checking the sso schema dblink. %1.**

**Cause:** An unexpected error occurred while checking the sso schema dblink.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80184: An unexpected error occurred while checking languages. %1.**

**Cause:** An unexpected error occurred while checking languages.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WWU-80185: An unexpected error occurred while checking providers. %1.**

**Cause:** An unexpected error occurred while checking providers.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80186: An unexpected error occurred while checking provider DB schemas. %1.**

**Cause:** An unexpected error occurred while checking provider DB schema.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80187: An unexpected error occurred during Listing privileges and roles for Provider DB schema:%1. %2**

**Cause:** An unexpected error occurred during the provider DB schema privileges and roles check.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80188: An unexpected error occurred while checking the portal privileges granted for Provider schema:%1. %2**

**Cause:** An unexpected error occurred while checking the portal privileges granted for Provider schema.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80189: An unexpected error occurred during System precheck. Mode:%1. %2**

**Cause:** An unexpected error occurred during System precheck.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80192: Component %1 was not found. This component was exported as external object and expected to exist on target before import.**

---

**Cause:** This component was exported as external object and expected to exist on target before import.

**Action:** Make sure that this component exists with valid implementation before running import.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80193: DB Schema entry is missing for owner %1 for component %2. This component was exported as external object and expected to exist on target before import.**

**Cause:** This component was exported as external object and expected to exist on target before import.

**Action:** Make sure the component owner schema exists before running import.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80194: The transport set %1 already exists on target.**

**Cause:** The transport set you are trying to acquire already exists on target.

**Action:** Delete the transport set from browse transport set and try to acquire again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80202: An unexpected error occurred while checking components. %1.**

**Cause:** An unexpected error occurred while checking components.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80203: An unexpected error occurred while checking pagegroup. %1.**

**Cause:** An unexpected error occurred while checking pagegroups.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80211: | An unexpected error occurred while checking default languages for pagegroups. %1.**

**Cause:** An unexpected error occurred while checking pagegroups.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

---

Type: ERROR

Impact: Other

**WWU-80285: Source Portal %1(%2) couldn't be validated.The portal versions between source and target portals are different.**

**Cause:** The portal versions are not matching between source and target portals.

**Action:** Select a portal schema which has the same portal version as the target portal schema.

Level: 1

Type: ERROR

Impact: Other

**WWU-80286: Unexpected error occurred while validating source portal %1(%2) . %3.**

**Cause:** Unexpected error occurred while validation source portal.

**Action:** Contact Oracle support Services

Level: 1

Type: ERROR

Impact: Other

**WWU-80287: The souce portal %1(%2) can't be registered.The source portal selected to register is pointing to itself.**

**Cause:** The Database link selected to register as a source portal is pointing to the current schema.

**Action:** Select some other source portal.

Level: 1

Type: ERROR

Impact: Other

**WWU-80289: The schema %1 in DBlink %2 is not a portal schema.**

**Cause:** The DBLink is not pointing to valid 11g Portal Schema.

**Action:** Select a DBLink pointing to any valid 11g Portal Schema.

Level: 1

Type: ERROR

Impact: Other

**WWU-80309: Source portal with name %1 is already registered.Please enter another name.**

**Cause:** The source portal name you are trying to register already exists.

**Action:** Please enter another unique name

Level: 1

Type: ERROR

Impact: Other

**WWU-80317: An unexpected error occurred while checking external apps. %1.**

**Cause:** An unexpected error occurred while checking external apps.

**Action:** Contact Oracle Support Services and provide the logs.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80337: There were some inconsistencies found and hence export process is aborted. Check the debug log for further details. Fix those inconsistencies**

**Cause:** Portal has inconsistent data and hence the process aborted.

**Action:** Fix those inconsistencies by running the schema validation in cleanup mode.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80338: There were some inconsistencies found and hence import process is aborted. Check the debug log for further details. Fix those inconsistencies**

**Cause:** Portal has inconsistent data and hence the process aborted.

**Action:** Fix those inconsistencies by running the schema validation in cleanup mode.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80349: Invalid Pagination option**

**Cause:** No / Invalid value has been specified for the Paginate Objects per section.

**Action:** Specify a numeric value for the Paginate Objects per section.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80353: DBLink to SSO schema %1 is not reachable.**

**Cause:** DBLink used to retrieve the external application list from SSO schema is not accessible.

**Action:** Check the dblink.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80361: An unexpected error occurred while checking DBlinks for provider DB schema. %1.**

**Cause:** An unexpected error occurred while checking DBlinks for provider DB schema.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWU-80365: The transport set name %1 entered already exists**

**Cause:** A transport set with the same name already exists in the system.

**Action:** Give a different name to the transport set.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80367: WSRP Provider: %1. Invalid url: %2 or the provider is not running. If you continue with import**

**Cause:** WSRP provider url is invalid.

**Action:** Check the url in a browser and make sure the url and proxy settings are correct before importing the provider.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80375: Unexpected error occurred while copying the transport set -%1 to a new transport set - %2. %3**

**Cause:** An unknown exception occurred while copying.

**Action:** Contact Oracle Support Services and provide the log information.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80382: TNS entry error %1**

**Cause:** A connection to a database or other service was requested using a connect identifier and the connect identifier specified could not be resolved into a connect descriptor using one of the naming methods configured.

**Action:** Check the net service name used as the connect identifier in the database link.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-80421: Directory Object %1 does not exist. Create the directory object and try again. Otherwise configure a different directory object to be used for dump creation using the Global Settings page.**

**Cause:** The Directory object %1 does not exist.

**Action:** Configure the directory object to be used for dump creation using the Global Settings page .

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-83014: Unable to add the dependencies of generic page portlet for page group identifier %1. An attempt to import this transport set could result in errors.**



---

**Cause:** An unexpected error occurred while adding the dependencies of the generic page portlet. The export proceeded without the dependencies. If the resulting transport set is imported, the generic page portlet could result in errors.

**Action:** Contact Oracle Support Services and provide the export logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-83015: An unknown error while calculating manifest data.%1**

**Cause:** An unexpected error occurred while calculating Dependencies.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-83016: An unknown error in altering dependency list.%1**

**Cause:** An unexpected error occurred while calculating Dependencies.

**Action:** Contact Oracle Support Services and provide the logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-83017: There are no objects in the Transport set.**

**Cause:** There are no objects in the transport set.

**Action:** Add some objects to transport set and export again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-83021: Unexpected error while generating pagegroup dependencies for search portlet.**

**Cause:** An unexpected error occurred while calculating pagegroup dependencies for search portlet preferences.

**Action:** Contact Oracle Support Services and provide the dependency logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-83022: Unexpected error while generating image dependencies for search portlet.**

**Cause:** An unexpected error occurred while calculating image dependencies for search portlet preferences.

**Action:** Contact Oracle Support Services and provide the dependency logs.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WWU-83023: Unexpected error while generating style dependencies for search portlet.**

**Cause:** An unexpected error occurred while calculating style dependencies for search portlet preferences.

**Action:** Contact Oracle Support Services and provide the dependency logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-83024: Unexpected error while generating attribute dependencies for search portlet.**

**Cause:** An unexpected error occurred while calculating attribute dependencies for search portlet preferences.

**Action:** Contact Oracle Support Services and provide the dependency logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-83025: Unexpected error while calculating itemtype dependencies for search portlet.**

**Cause:** An unexpected error occurred while calculating itemtype dependencies for search portlet preferences.

**Action:** Contact Oracle Support Services and provide the dependency logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-83026: Unexpected error while calculating page dependencies for search portlet.**

**Cause:** An unexpected error occurred while calculating page dependencies for search portlet preferences.

**Action:** Contact Oracle Support Services and provide the dependency logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWU-83027: Unexpected error while calculating category dependencies for search portlet.**

**Cause:** An unexpected error occurred while calculating category dependencies for search portlet preferences.

**Action:** Contact Oracle Support Services and provide the dependency logs.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWU-83028: Unexpected error while calculating perspective dependencies for search portlet.**

**Cause:** An unexpected error occurred while calculating perspective dependencies for search portlet preferences.

**Action:** Contact Oracle Support Services and provide the dependency logs.

**Level:** 1

**Type:** ERROR

**Impact:** Other



---

## WWV-00100 to WWV-61294

**WWV-00100: Unexpected error encountered in %0 (%1)**

**Cause:** An unhandled exception was raised during this operation.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00201: Cannot initialize component ID: %1**

**Cause:** The attributes of the component wizard could not be initialized.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00202: Could not commit attributes.**

**Cause:** The attributes of the component wizard could not be saved. This could be caused by data inconsistency or an internal error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00203: Took exception**

**Cause:** The attributes of the component wizard could not be initialized or could not be saved.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00204: Save report columns attribute values failed**

**Cause:** Some attributes of the report were not saved, possibly because they were invalid.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00205: The set default columns failed.**

**Cause:** Some attributes were not saved, possibly because they were invalid.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00206: The selected tables or views contain column types that are not supported.**

**Cause:** Columns with unsupported types were selected for rendering.

**Action:** Change your query. If the problem persists, contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00207: The object(s) that you have selected contains columns that are either LOBs / object tables / user-defined type.**

**Cause:** The columns selected for rendering are of unsupported types.

**Action:** Change your query. If the problem persists, contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00208: You are trying to access an intermedia/LOB object over a remote database. This is not supported.**

**Cause:** An attempt was made to access an *inter*Media/LOB object over a remote database. This action is not supported.

**Action:** Change the query or column selection. If the problem persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00250: Could not save attribute name: %1.**

**Cause:** The attributes of the component could not be saved.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWV-00251: Could not initialize component ID: %1**

**Cause:** The attributes of the component could not be initialized.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00252: Could not commit attributes.**

**Cause:** The attributes of the component could not be saved.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00253: Took exception**

**Cause:** The attributes of the component wizard could not initialized or could not be saved.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00254: Save report columns attribute values failed.**

**Cause:** Some attributes of the report were not saved, possibly because they were invalid.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00255: Set default columns failed.**

**Cause:** Some attributes were not saved, possibly because they were invalid.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00256: The Table/View(s) that you have selected contains column types that are not supported.**

**Cause:** The columns selected for rendering are of unsupported types.

**Action:** Change your query. If the problem persists, contact Oracle Support Services

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWV-00402: An unexpected error occurred: %1**

**Cause:** An unhandled exception was raised during this operation.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00427: Failed to set component %1 as Portal DB Provider object: %2**

**Cause:** A component with the same ID already exists. The table WWAPP\_APPLICATION\_DETAIL\$ may have been directly manipulated.

**Action:** Use datafix scripts to help resolve this error. Contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00428: Failed to delete component %1 from Portal DB Provider: %2**

**Cause:** The component was not deleted from the Portal DB Provider.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00444: Portal DB Provider %1 does not exist.**

**Cause:** The Portal DB provider could not be found.

**Action:** Check that the provider exists. If it does not, create one.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00482: Unable to find Portal DB Provider for component %1**

**Cause:** The application on which the component was built could not be found, possibly because it was removed from the application metadata table.

**Action:** Check to see if the underlying application exists in the Navigator. If it does not, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00486: Unable to run component %1**

**Cause:** An attempt was made to run a package but the user does not have the appropriate privileges to run it or the package does not exist.

**Action:** Check the user's privilege level. If the user has the appropriate privileges, check that the package exists in the schema.



---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00495: Display Name is already used by another component in this Portal DB Provider %1. Specify another Display Name.**

**Cause:** The display name specified is already being used by another component.

**Action:** Specify a different, unique display name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00496: New Component Display Name is already used by another component in this Portal DB Provider %1. Specify another Display Name.**

**Cause:** The display name specified is already being used by another component.

**Action:** Specify a different, unique name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00547: The Portal DB Provider schema %1 does not exist or is not a valid schema.**

**Cause:** The schema specified could not be found.

**Action:** Check that the schema name is correct or create the schema.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00550: Unexpected error**

**Cause:** An unhandled exception was raised during the operation.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00551: Could not find columns for table %1**

**Cause:** The table selected does not have any columns of types supported by the component.

**Action:** Check the table for column types.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00552: Failed to parse query %1**

---

**Cause:** The SQL INSERT statement could not be parsed due to incorrect syntax or usage, or reference to inaccessible objects.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00553: Failed to fetch rows for query %1**

**Cause:** The SQL SELECT statement could not fetch any rows.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00600: Select query could not be created**

**Cause:** An unexpected error was encountered while generating the SELECT statement.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00601: Failed during code generation**

**Cause:** An unexpected error was encountered during code generation.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00602: Failed during code generation**

**Cause:** An unexpected error was encountered during code generation.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00605: Failed to initialize builder attributes**

**Cause:** Design time metadata for an image chart could not be fetched.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00651: Failed to fetch rows. Raised exception %1**

---

**Cause:** The rows could not be fetched.  
**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00652: Failed to define columns. Raised exception %1**

**Cause:** No columns were defined in the query.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00653: Failed to parse the query %1**

**Cause:** The query could not be parsed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00654: Null cursor for the query %1**

**Cause:** There was a error while parsing the query.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00700: Unable to find object %1**

**Cause:** The object could not be found or the user does not have sufficient privileges to retrieve it.

**Action:** Check to see if the object exists and, if it does, that the user has the appropriate privileges.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00704: Failed to get source for object %1: %2**

**Cause:** The source for the requested object could not be contacted.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00850: Error in create\_package**

---

**Cause:** The package for the component could not be created. This could be because a package with the same name already exists, there is a problem with the underlying schema, or the package specification does not exist.

**Action:** Check that the schema exists, a package with the same name exists, and the package specification exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00851: Error in create\_package\_body**

**Cause:** The package body for the component could not be created. This could be because a package body with the same name already exists, there is a problem with the underlying schema, or the package specification does not exist.

**Action:** Check that the schema exists, a package with the same name exists, and the package specification exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00852: Error in create\_show**

**Cause:** A problem was encountered while building the show procedure of the package.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00853: Error in create\_show\_params**

**Cause:** A problem was encountered while building the show\_params procedure of the package.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00854: Error in create\_help**

**Cause:** A problem was encountered while building the help procedure of the package.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00855: Error in create\_help\_params**

**Cause:** A problem was encountered while building the help\_params procedure of the package.

---

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00856: Error in create\_calendar\_call**

**Cause:** A problem was encountered while creating the calendar.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00866: Failed to initialize builder attributes.**

**Cause:** Design time metadata for this calendar component could not be fetched.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00900: Error in create\_package**

**Cause:** The package for the component could not be created. This could be because a package with the same name already exists, there is a problem with the underlying schema, or the package specification does not exist.

**Action:** Check that the schema exists, a package with the same name exists, and the package specification exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00901: Error in create\_package\_body**

**Cause:** The package body for the component could not be created. This could be because a package body with the same name already exists, there is a problem with the underlying schema, or the package specification does not exist.

**Action:** Check that the schema exists, a package with the same name exists, and the package specification exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00902: Error in create\_show**

**Cause:** A problem was encountered while building the show procedure of the package.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWV-00903: Error in create\_show\_parms**

**Cause:** A problem was encountered while building the show\_params procedure of the package.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00904: Error in create\_help**

**Cause:** A problem was encountered while building the help procedure of the package.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00905: Error in create\_help\_parms**

**Cause:** A problem was encountered while building the help\_params procedure of the package.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00906: Error in create\_chart\_call**

**Cause:** A problem was encountered while creating the chart call.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00907: Error in create\_about**

**Cause:** A problem was encountered while building the about procedure of the package.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-00908: Error in create\_about\_parms**

**Cause:** A problem was encountered while building the about\_params procedure of the package.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01000: Error in create\_package**

**Cause:** The package for the component could not be created. This could be because a package with the same name already exists, there is a problem with the underlying schema, or the package specification does not exist.

**Action:** Check that the schema exists, a package with the same name exists, and the package specification exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01001: Error in create\_package\_body**

**Cause:** The package body for the component could not be created. This could be because a package body with the same name already exists, there is a problem with the underlying schema, or the package specification does not exist.

**Action:** Check that the schema exists, a package with the same name exists, and the package specification exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01002: Error in create\_show**

**Cause:** A problem was encountered while building the show procedure of the package.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01003: Error in create\_show\_params**

**Cause:** A problem was encountered while building the show\_params procedure of the package.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01004: Error in create\_help**

**Cause:** A problem was encountered while building the help procedure of the package.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWV-01005: Error in create\_help\_parms**

**Cause:** A problem was encountered while building the help\_params procedure of the package.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01006: Error in create\_report\_call**

**Cause:** A problem was encountered while creating the report call.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01007: Error in create\_show\_body**

**Cause:** A problem was encountered while creating the show\_body call.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01008: Error in create\_show\_parm\_list**

**Cause:** A problem was encountered while creating the show\_parm\_list.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01243: The template name is blank.**

**Cause:** A name was not specified for the template.

**Action:** Specify a name for the template.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01244: The template name already exists.**

**Cause:** The template name specified already exists.

**Action:** Specify a different name for the template.

**Level:** 1

**Type:** ERROR

**Impact:** Other



---

**WWV-01265: Failed to save template. Obsolete banner tags are not allowed.**

**Cause:** The template could not be saved because an obsolete banner tag was used in the template.

**Action:** Remove the tag that is no longer supported. Refer to the Oracle Application Server Portal User's Guide for a list of supported tags.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01283: The following tags can be used in the HTML as substitution variables for information that is provided by pages.**

**Cause:** The template could not be created because an obsolete banner tag was used in the template.

**Action:** Remove the tag that is no longer supported. Refer to the Oracle Application Server Portal User's Guide for a list of supported tags.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01284: The template definition is blank.**

**Cause:** A template definition was not specified.

**Action:** Enter HTML for the template.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01450: Failed to submit DBMS job: %1. The HTTP cookie might be too long. Close all browser windows and try again.**

**Cause:** The job was not submitted. This could be because the HTTP cookie is too long.

**Action:** Close all browser windows and try again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01451: Error executing batch job %1: %2.**

**Cause:** The job failed to execute.

**Action:** Check that the job is submitted and running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01452: Error executing batch job %0**

**Cause:** The job failed to execute.

**Action:** Check that the job is submitted and running.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01500: Unable to expire old results.**

**Cause:** Results could not be deleted from the batch submissions table. This could be because the table does not exist or there is an underlying database problem.

**Action:** Ensure that your database is not experiencing a rollback segment problem, then contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01539: Insufficient privileges**

**Cause:** The user did not have sufficient privileges for the attempted operation.

**Action:** Log in as a user with the appropriate privileges. Alternatively, contact the portal administrator and request that the appropriate privileges be granted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01540: The job does not exist or the user does not have privilege to edit the job.**

**Cause:** The specified job could not be found or the user does not have sufficient privileges.

**Action:** Check that the job exists. If it exists, login as a user with the appropriate privileges or contact the portal administrator and request that the appropriate privileges be granted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01603: Failed to parse query.**

**Cause:** The SQL statement could not be parsed due to incorrect syntax or usage, or because it referred to inaccessible objects.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01801: Took exception**

**Cause:** An attempt was made to edit a dynamic page that contains more than 32 KB of HTML code.

**Action:** Avoid writing more than 32 KB of HTML code in a dynamic page.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWV-01805: Unable to save checkbox**

**Cause:** A limit was exceeded, such as using more than 15 check boxes in an HTML page.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01809: Unable to initialize component attributes (saved values)**

**Cause:** A limit was exceeded, such as using more than 15 check boxes in an HTML page.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01810: Unable to initialize component attributes (base version).**

**Cause:** The component attributes were not initialized because the component metadata could not be loaded.

**Action:** Contact Oracle Support Services to check that the component metadata is intact.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01814: Unable to clean up component ID: %1**

**Cause:** The component metadata could not be deleted, possibly because there are some dependencies that have not been eliminated.

**Action:** Contact Oracle Support Services to check that the component metadata is intact.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01817: Unable to obtain lock on component ID: %1**

**Cause:** This component was already locked by another user.

**Action:** Unlock the component before attempting to edit it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01820: Unable to initialize attribute for component ID %1**

**Cause:** The component was not initialized because the component metadata could not be loaded.

---

**Action:** Contact Oracle Support Services and ask them to see if the component metadata is intact.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01822: Unable to save hidden value for attribute ID: %1 for value: %2**

**Cause:** An attempt to save the component metadata failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01823: Unable to save value for attribute ID: %1 for value: %2**

**Cause:** An attempt to save the component metadata failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01824: Unable to save array value for attribute ID: %1 for value: %2**

**Cause:** An attempt to save the component metadata failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01825: Unable to save LONG value for attribute ID: %1**

**Cause:** An attempt to save the component metadata failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01830: Invalid component type: %1**

**Cause:** The component type could not be found, possibly because it was removed from the master table.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01831: Invalid component ID: %1 or version: %2**

**Cause:** The component ID or the module ID could not be found.

---

**Action:** Check to see if a component with this ID exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01832: Unable to clean up components table for component ID: %1 or version: %2**

**Cause:** The components table could not be cleaned up because there are dependencies that have not been cleaned up.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01833: Unable to create component for component type: %1**

**Cause:** The component could not be created, possibly because there was an error while inserting into the component metadata table.

**Action:** Check that this component already exists, or contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01834: Unable to execute function: %1**

**Cause:** An attempt to execute a function in the component builder failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01835: Unable to initialize module attributes.**

**Cause:** The module attributes were not initialized because the component metadata could not be loaded.

**Action:** Contact Oracle Support Services to check that the component metadata is intact.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01838: wwv\_utlattr.save\_attribute\_value failed.**

**Cause:** One or more component attributes could not be saved, possibly because the attributes were invalid.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWV-01839: wwv\_utlattr.commit\_attributes failed**

**Cause:** One or more component attributes could not be saved, possibly because the attributes were invalid.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01841: WWV\_BUILDER.GET\_LOV\_FIRST\_VALUE: fetch\_row failed.**

**Cause:** Metadata may be inconsistent.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-01849: Failed to initialize builder attributes**

**Cause:** Builder attributes could not be initialized because the design time metadata for the component could not be fetched.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-02124: Unable to render report**

**Cause:** The report cannot be rendered because the user does not have appropriate privileges to select from the wwlog\_activity\$ table, or because the table does not exist.

**Action:** Verify that the table exists and that the user has the appropriate privileges.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-02192: Unable to locate object**

**Cause:** The component could not be found in the component metadata.

**Action:** Check that the component appears in the Navigator.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-02200: Unable to delete object %0 (version %1). General error: %2.**

**Cause:** The component version could not be found in the component metadata.

**Action:** Ensure that the component version exists.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-02210: No version is selected**

**Cause:** An attempt was made to delete a component version, but no versions were selected.

**Action:** Select the versions to delete by clicking the appropriate check boxes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-02215: Unable to drop PACKAGE : %0**

**Cause:** The package could not be dropped because the user does not have the appropriate privileges or because the package does not exist.

**Action:** Make sure that the package exists in the schema and that the user has the appropriate privileges.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-02700: Unable to create Data Component %0. Data Component names must be unique. After creating a Data Component**

**Cause:** A data component with the specified name already exists.

**Action:** Specify a different name for the component.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-02751: Failed to save parameters**

**Cause:** An error occurred in the user preference storage subsystem.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-03008: Column %1 is of type %2**

**Cause:** A value was specified for the precision attribute but the column is of a data type that does not support the precision attribute.

**Action:** Do not specify a value for the precision attribute for columns of this data type.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-03009: Column %1 is of type %2**

---

**Cause:** A value was specified for the precision attribute but the column is of a data type that does not support the precision attribute.

**Action:** Do not specify a value for the precision attribute for columns of this data type.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-03010: The length attribute is mandatory for column %1 of type %2. Enter a valid number.**

**Cause:** The length attribute was not specified for the column.

**Action:** Specify a valid length for the column.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-03011: The length attribute for column %1 is not numeric. Enter a valid number.**

**Cause:** A non-numeric value was specified for the length attribute.

**Action:** Specify a valid number for the length attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-03702: Unable to find table: %0.%1**

**Cause:** The table could not be found or the user does not have the appropriate privileges.

**Action:** Make sure the table exists and that the user has appropriate privileges to access it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-04008: Failed to create help procedure - %1**

**Cause:** An unexpected error occurred while generating or compiling a frame driver component package body.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-04150: Failed to get attribute for %1**

**Cause:** An unexpected error occurred while fetching the value of the attribute. This could be as a result of inconsistent metadata.

**Action:** Contact Oracle Support Services.



---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-04151: Failed to create get cache for %1**

**Cause:** An unexpected error occurred while generating the PL/SQL code for portlet caching.

**Action:** Regenerate the component. If the error persists, contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-04152: Invalid value %1**

**Cause:** The value specified for the cache expiry period was incorrect.

**Action:** Provide an integer value for the cache expiry period.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-04154: Failed to invoke Oracle Reports generator**

**Cause:** An unexpected error occurred while trying to invoke the Oracle Reports generator.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-04300: Failed to execute - %1**

**Cause:** A SQL or PL/SQL statement could not be parsed due to incorrect syntax or usage, or because it referred to an inaccessible object.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-05516: Failed to unlock component: %1**

**Cause:** The component could not be unlocked.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06000: The font name you specified already exists. Enter a new name that is unique.**

---

**Cause:** A font with the specified name already exists.

**Action:** Specify a different name for the font.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06001: The font value is invalid.**

**Cause:** The value specified for the font was invalid.

**Action:** Specify a valid value for the font.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06002: You cannot leave the font name blank. Enter a name for the font.**

**Cause:** A name was not specified for the font.

**Action:** Specify a name for the font.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06013: The specified font name does not exist.**

**Cause:** This specified font could not be found.

**Action:** Check the name of the font and provide a valid name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06017: You cannot leave the font value blank. Enter a value for the font.**

**Cause:** A value was not specified for the font.

**Action:** Specify a value for the font.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06018: The font name can contain only alphanumeric characters and a set of special characters comprised of \_ \$ #**

**Cause:** The specified font name included invalid characters.

**Action:** Specify a name that contains only alphanumeric characters and the following special characters: \_ \$ # and space.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06029: Font Name already exists**

---

**Cause:** A font with the specified name already exists.

**Action:** Specify a different name for the font.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06100: Failed to add image**

**Cause:** An attempt to add an image failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06101: Unable to add image because the image name is null.**

**Cause:** A name was not specified for the image.

**Action:** Specify a name for the image.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06102: Failed to update image**

**Cause:** An attempt to update an image failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06103: Unable to update image because the image id is null.**

**Cause:** An attempt was made to update an image but the the image ID is null.

**Action:** Ensure that the image exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06117: The image specified does not exist**

**Cause:** The specified image could not be found.

**Action:** Specify the name of an image that does exist.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06118: You cannot leave the image filename blank. Enter a filename for the image.**

**Cause:** A file name was not specified for the image.

---

**Action:** Specify a valid file name for the image.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06123: The specified image does not exist**

**Cause:** The specified image could not be found.

**Action:** Specify a valid image name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06127: The image name can contain only alphanumeric characters or the special characters \_ \$ #**

**Cause:** The specified image name included invalid characters.

**Action:** Specify an image name that contains only alphanumeric characters and the following special characters: \_ \$ # and space.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06133: Image Name already exists**

**Cause:** An image with the specified name already exists.

**Action:** Specify a different name for the image.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06200: Failed to %1: %2**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06201: The Javascript Name can contain only alphanumeric characters and the special characters underscore**

**Cause:** The specified JavaScript name included invalid characters.

**Action:** Specify a JavaScript name that contains only alphanumeric characters and the following special characters: \_ \$ # and space.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06202: Javascript Name cannot be NULL**

---

**Cause:** A name was not specified for the JavaScript.

**Action:** Specify a name for the JavaScript.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06203: JavaScript name must not be longer than 30 characters: %1**

**Cause:** The name specified for the JavaScript was too long.

**Action:** Specify a name for the JavaScript that is no more than 30 characters in length.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06224: The javascript you have specified does not exist**

**Cause:** The specified JavaScript could not be found.

**Action:** Specify a valid JavaScript name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06241: Javascript Name already exists**

**Cause:** A JavaScript with the specified name already exists.

**Action:** Specify a different name for the JavaScript.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06406: No link is specified.**

**Cause:** An attempt was made to edit a link before a link was selected on the 'Column Formatting' tab.

**Action:** Select a link from the combo box on the 'Column Formatting' tab.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06409: Failed to save attribute %1: %2**

**Cause:** The attribute was not saved.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06450: Failed to initialize builder attributes: %1**

---

**Cause:** The design time metadata for this link component could not be fetched.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06500: Unable to create LOV %1. LOV names must be unique. After creating an LOV**

**Cause:** An LOV with the specified name already exists.

**Action:** Specify a different name for the LOV.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06502: Invalid LOV type. An LOV must be STATIC or DYNAMIC.**

**Cause:** The LOV type was invalid.

**Action:** Identify the LOV type as either STATIC or DYNAMIC.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06550: Failed to query LOV: %1**

**Cause:** An error occurred as identified in the accompanying Oracle error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06551: Failed to copy LOV: %1**

**Cause:** An error occurred as identified in the accompanying Oracle error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06552: Failed to update LOV: %1**

**Cause:** An error occurred as identified in the accompanying Oracle error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06553: Failed to delete LOV: %1**

**Cause:** An error occurred as identified in the accompanying Oracle error.

---

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-06554: Failed to create LOV: %1**

**Cause:** An error occurred as identified in the accompanying Oracle error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-07002: Failed to update menu**

**Cause:** An attempt to update the menu failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-07003: Failed to delete menu**

**Cause:** An attempt to delete the menu failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-07004: Failed to delete sub menus**

**Cause:** An attempt to delete the sub menu failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-07005: Failed to insert menu**

**Cause:** An attempt to insert the menu failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-07200: Failed to insert into table wwv\_menus for module %1**

**Cause:** An attempt to insert metadata for the menu failed.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-07201: Failed to update table wwv\_menus for module %1**

**Cause:** An attempt to update the metadata for the menu failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-07202: Failed to create package %1**

**Cause:** An attempt to compile the package for the menu failed.

**Action:** Regenerate the component. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-07203: Failed to create package body %1**

**Cause:** An attempt to compile the package body for the menu failed.

**Action:** Regenerate the component. If the error persists, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-07902: Sorry**

**Cause:** The content of the dynamic page could not be found.

**Action:** Edit the dynamic page to check the query. If the problem persists contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-08300: Failed to parse as %1 - %2**

**Cause:** The SQL statement could not be parsed due to incorrect syntax or usage, or because it referenced an inaccessible object.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-08301: Failed to parse(V7) as %1 - %2**



---

**Cause:** The SQL statement could not be parsed due to incorrect syntax or usage, or because it referenced an inaccessible object.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-08700: Set preference value failed: %1**

**Cause:** The preference path may be missing.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-08701: Get preference value failed**

**Cause:** The preference path may be missing.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-08800: Unable to view object: %1**

**Cause:** The database object type was invalid.

**Action:** Check that an object of this type exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-08801: Unable to show synonyms of remote objects: Table=%1 Owner=%2 DB\_link=%3**

**Cause:** An attempt was made to view a synonym on a remote table. This action is not supported.

**Action:** Do not attempt to view a synonym on a remote table.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-08900: Failed to initialize attributes**

**Cause:** The design time metadata for this QBE component could not be fetched.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWV-08901: Error in create\_package**

**Cause:** The package for the component could not be created. This could be because a package with the same name already exists or there is a problem with the underlying schema.

**Action:** Check that the schema exists and a package with the same name exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-08902: Error in create\_package\_body**

**Cause:** The package body for the component could not be created. This could be because a package body with the same name already exists, there is a problem with the underlying schema, or the package specification does not exist.

**Action:** Check that the schema exists, a package with the same name exists, and the package specification exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-08903: Error in create\_show**

**Cause:** A problem was encountered while building the show procedure of the package.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-08904: Error in create\_show\_params**

**Cause:** A problem was encountered while building the show\_params procedure of the package.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-08905: Error in create\_help**

**Cause:** A problem was encountered while building the help procedure of the package.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-08906: Error in create\_help\_params**

**Cause:** A problem was encountered while building the help\_params procedure of the package.

---

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-08907: Error in create\_show\_adt**

**Cause:** A problem was encountered while building the show\_adt procedure of the package.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-09000: Unable to describe object %1 of type %2**

**Cause:** The specified object does not exist or the user does not have sufficient permissions.

**Action:** Check to see if the object exists, and that the user has sufficient permissions on the object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-09002: Unknown type of request %1**

**Cause:** The type was not of Table, View, or Synonym.

**Action:** Check the type of the object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-09103: Unable to parse cursor and define columns**

**Cause:** The query was improperly written or the user does not have sufficient permissions on the query object.

**Action:** Check the syntax of the query and the user's permissions on the object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-09104: Unable to fetch row**

**Cause:** The query was improperly written or the user does not have sufficient permissions on the query object.

**Action:** Check the syntax of the query and the user's permissions on the object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWV-09105: Unable to locate the row indicated by the ID %1**

**Cause:** The query is improperly written or the user does not have sufficient permissions on the query object.

**Action:** Check the syntax of the query and the user's permissions on the object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-09106: Failed to insert**

**Cause:** The dynamic SQL statement could not be parsed due to incorrect syntax or usage, or because it referenced an inaccessible object.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-09500: Error in parse query %1**

**Cause:** There was an error while parsing the query.

**Action:** Check the syntax of the query.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-09501: Error in fetch column**

**Cause:** There was an error while fetching the column.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-09502: Invalid Cursor**

**Cause:** There was an error while parsing the query.

**Action:** Check the syntax, tables, and columns of the query.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-09600: Error in parse query %1**

**Cause:** There was an error while parsing the query.

**Action:** Check the syntax, tables, and columns of the query.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWV-09601: Invalid Cursor**

**Cause:** There was an error while parsing the query.

**Action:** Check the syntax, tables, and columns of the query.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-09700: Error occurred when binding query %1**

**Cause:** There was an error while binding the query.

**Action:** Check that the value of the column is of the expected type.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-09701: Error occurred when deleting saved parameters**

**Cause:** There was an error while deleting the parameters.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-10200: Unable to parse query**

**Cause:** The query is improperly written, or the user does not have sufficient permissions on the query object.

**Action:** Check the query and the user's permissions on the object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-10201: Unable to execute query**

**Cause:** The query is improperly written, or the user does not have sufficient permissions on the query object.

**Action:** Check the query and the user's permissions on the object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-10202: Unable to perform query**

**Cause:** The query is improperly written, or the user does not have sufficient permissions on the query object.

**Action:** Check the query and the user's permissions on the object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWV-10219: Unable to compute column sum for column %0**

**Cause:** An attempt to calculate the sum of a column failed.

**Action:** Make sure the column is numeric.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-10223: Unable to fetch column**

**Cause:** An attempt to fetch the column value failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-10250: The contents of this link cannot be rendered**

**Cause:** The specified component does not have mobile support.

**Action:** Do not add this component to a mobile page.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-10403: %1 Failed.**

**Cause:** An unexpected error occurred.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-10601: User %0 has insufficient privileges to grant privileges.**

**Cause:** An attempt was made to grant privileges but the user does not have the appropriate privileges to perform this task.

**Action:** Login as a user with privileges to perform this task. Alternatively, contact the portal administrator and request that the appropriate privileges be granted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-10602: User %0 has insufficient privileges to revoke privileges.**

**Cause:** An attempt was made to revoke privileges but the user does not have the appropriate privileges to perform this task.

**Action:** Login as a user with privileges to perform this task. Alternatively, contact the portal administrator and request that the appropriate privileges be granted.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWV-10603: Failed to grant privileges**

**Cause:** The user does not have permission to perform this action, or the grantee could not be found.

**Action:** Login as a user with privileges to perform this action or contact the portal administrator and request that the appropriate privileges be granted. If the user already has the appropriate privileges, check that the grantee exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-10604: Failed to revoke privileges**

**Cause:** The user does not have permission to perform this action, or the grantee could not be found.

**Action:** Login as a user with privileges to perform this action or contact the portal administrator and request that the appropriate privileges be granted. If the user already has the appropriate privileges, check that the grantee exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-10605: User %1 has insufficient privileges to build in Portal DB Provider**

**Cause:** The user does not have the appropriate privileges to build in the provider.

**Action:** Login as a user with sufficient privileges to perform this task. Alternatively, contact the portal administrator and request that the appropriate privileges be granted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-10606: User %1 has insufficient privileges to create Portal DB Provider**

**Cause:** The user does not have the appropriate privileges to create a database provider.

**Action:** Login as a user with sufficient privileges to perform this task. Alternatively, contact the portal administrator and request that the appropriate privileges be granted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-10607: User %1 has insufficient privileges to Manage Shared Components**

**Cause:** The user does not have the appropriate privileges to manage shared components.

**Action:** Login as a user with sufficient privileges to perform this task. Alternatively, contact the portal administrator and request that the appropriate privileges be granted.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-10608: User %1 has insufficient privileges to Create Shared Components**

**Cause:** The user does not have the appropriate privileges to create shared components.

**Action:** Login as a user with sufficient privileges to perform this task. Alternatively, contact the portal administrator and request that the appropriate privileges be granted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-10703: Insert label usage failed**

**Cause:** An inappropriate value was specified for a label usage ID.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-10704: Insert text block usage failed**

**Cause:** An inappropriate value was specified for a text block usage ID.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-10708: Insert label usage failed**

**Cause:** An inappropriate value was specified for a label usage ID.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-10709: Insert text block usage failed**

**Cause:** An inappropriate value was specified for a text block usage ID.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-11230: %1**

**Cause:** OracleAS Portal encountered the Oracle error identified in the error message.



---

**Action:** Refer to the Oracle Error Message Guide for a description of the Oracle error.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-12208: Unable to find LOV by NAME or by ID**

**Cause:** The LOV could not be found. The LOV may have been removed.

**Action:** Check that the LOV appears in the Navigator. If it does not, re-create it or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-12210: Unable to obtain LOV Query: \"'%0\"**

**Cause:** The LOV could not be found. The LOV may have been removed.

**Action:** Check that the LOV appears in the Navigator. If it does not, re-create it or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-12220: Query not found**

**Cause:** The LOV could not be found. The LOV may have been dropped or manually removed from the LOV tables.

**Action:** If this is a user defined LOV, check that it appears in the Navigator. If it is a system LOV, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-12227: You must supply an LOV query**

**Cause:** The LOV query, name, cursor, or static values were not specified.

**Action:** Specify a query or static values for the LOV.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-12700: Insufficient privileges.**

**Cause:** The user does not have sufficient privileges to perform this operation.

**Action:** Login as a user with privileges to perform this task. Alternatively, contact the portal administrator and request that the appropriate privileges be granted.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWV-12701: Failed to modify user %1**

**Cause:** The user settings could not be modified.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-12702: Failed to create user %1**

**Cause:** An attempt to create a user failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-12703: Drop user operation failed**

**Cause:** An attempt to drop a user failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-12704: Failed to drop user %1**

**Cause:** An attempt to drop a user failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-12950: Display Name must be entered**

**Cause:** A display name was not specified.

**Action:** Specify a valid display name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-12951: Display Name is too long: more than %1 bytes.**

**Cause:** The display name was too long.

**Action:** Specify a shorter display name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-12952: Component Display Name must be entered**

---

**Cause:** A display name was not specified.

**Action:** Specify a display name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-12953: Description must be entered**

**Cause:** A description was not specified.

**Action:** Specify a description.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-12954: Description length should not exceed 200 bytes**

**Cause:** The description was too long

**Action:** Specify a description that is no more than 200 bytes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-12955: Display length should not exceed 200 bytes**

**Cause:** The title was too long.

**Action:** Specify a title that is no more than 200 bytes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13000: Invalid component name: NULL - Name must be entered**

**Cause:** A name was not specified for the component.

**Action:** Specify a valid name for the component.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13001: Invalid component name: %1 - Spaces are not allowed. Choose another name.**

**Cause:** The component name contained spaces.

**Action:** Specify a name for the component that does not contain spaces.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13002: Invalid component name: %1 - is a reserved word. Choose another name.**

---

**Cause:** The component name included an Oracle reserved word.

**Action:** Specify a name for the component that does not include any Oracle reserved words.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13003: Invalid component name: %1 - Name already exists in the schema: %2. Choose another name.**

**Cause:** Another component in this database schema already exists with the same name as the one specified.

**Action:** Specify a different name for the component, or create it in a different schema.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13004: Invalid SQL statement: %1**

**Cause:** The SQL statement could not be parsed due to incorrect syntax or usage, or reference to inaccessible objects.

**Action:** Review the SQL statement and make the necessary changes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13005: Took exception**

**Cause:** An attempt to initialize the attributes of the component failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13006: Initialization failed for component ID: %1**

**Cause:** The design time metadata for this component could not be fetched.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13010: Unable to describe SQL statement. Please correct it**

**Cause:** The SQL statement could not be parsed due to incorrect syntax or usage, or reference to inaccessible objects.

**Action:** Review the SQL statement and make the necessary changes.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WWV-13017: Attribute save failed for: %1**

**Cause:** One or more attributes could not be saved, possibly because they are invalid.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13018: Commit failed**

**Cause:** The design time metadata could not be saved because there were one or more invalid attributes, or because the component was not in an appropriate state.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13020: This %1 does not exist or you do not have the required privileges**

**Cause:** The table, view, or synonym could not be found or the table owner did not grant the required privileges to the Portal DB Provider Schema.

**Action:** Confirm whether the table exists. If it does exist, contact the portal administrator and request that at least the SELECT privilege be granted to the Portal DB Schema on the table, view, or synonym.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13021: %1 name cannot be null**

**Cause:** A value was not specified for this field.

**Action:** Specify a value for this field.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13022: Duplicate columns not allowed : %1**

**Cause:** Duplicate columns were found in the query.

**Action:** Check for duplicate columns and remove them.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13023: Invalid columns : At least one column is required**

**Cause:** The columns names could not be found.

**Action:** Provide a valid list of columns.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13024: Invalid object name: %1 - The object you have selected is not available.**

**Choose the correct object from the LOV**

**Cause:** The columns names could not be found.

**Action:** Provide a valid list of columns.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13025: Invalid Object Name: %1 - The object you have selected is a synonym and its definition is not present in the DBE\_SYNONYMS system view**

**Cause:** The definition of the specified synonym is not present in the DBE\_SYNONYMS system view.

**Action:** Specify a valid synonym.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13026: Default Start with Value cannot be null. Enter a valid value depending on the Start with Column selected.**

**Cause:** The default start with value was null.

**Action:** Specify a valid start with value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13027: Display Column Expression cannot be null. Enter a column name or a column expression.**

**Cause:** The display value was null.

**Action:** Specify a valid display value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13028: Error in parsing SQL %1**

**Cause:** An attempt to parse the query failed.

**Action:** Specify a valid query.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13029: Error in parsing PL/SQL %1**

---

**Cause:** An attempt to parse the query failed.

**Action:** Specify a valid query.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13031: Incomplete formatting condition for column %1 : Enter a valid condition and select Row/Col to apply the format.**

**Cause:** The formatting condition specified for the column was incomplete.

**Action:** Specify a valid formatting condition.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13032: Incomplete Formatting Condition for Row/Col %1 : No Formatting condition specified.**

**Cause:** The formatting condition specified for the column was incomplete.

**Action:** Specify a valid formatting condition.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13033: Maximum Months Per Page must be an integer in the range 1 to 200**

**Cause:** The maximum months per page was not in the range of 1 to 200.

**Action:** Specify a valid value for months for each page.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13034: Start Month should be Less than or Equal to End Month.**

**Cause:** The start month was greater than the end month.

**Action:** Specify a valid start month.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13036: %1**

**Cause:** The date format was invalid.

**Action:** Specify a valid date format.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13037: Invalid join condition specified. Specify a join condition.**

---

**Cause:** The join condition was invalid.

**Action:** Specify a valid join condition.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13038: Incomplete Formatting Condition for Cell/Col %1 : No Formatting condition specified.**

**Cause:** The formatting condition was not specified.

**Action:** Specify a valid formatting condition.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13039: Incomplete formatting condition for column %1 : Enter a valid condition and select Cell/Col to apply the format.**

**Cause:** The formatting condition was not specified.

**Action:** Specify a valid formatting condition.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13040: Incomplete Formatting Condition for Bar/Col %1 : No Formatting condition specified.**

**Cause:** The formatting condition was not specified.

**Action:** Specify a valid formatting condition.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13041: Incomplete formatting condition for column %1 : Enter a valid condition and select Bar/Col to apply the format.**

**Cause:** The formatting condition was not specified.

**Action:** Specify a valid formatting condition.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13050: Failed to save attribute %1: %2**

**Cause:** One or more attributes could not be saved, possibly because they are invalid.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR



---

**Impact:** Other

**WWV-13051: Failed to commit: %1**

**Cause:** The design time metadata could not be saved because there were one or more invalid attributes, or because the component was not in an appropriate state.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13053: URL initiation failed**

**Cause:** The server could not be reached.

**Action:** Check that the URL is valid and ensure that the proxy settings are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13054: Either the URL is malformed or the target server could be down.**

**Cause:** The URL could not be reached.

**Action:** Check that the URL is valid and ensure that the proxy settings are correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13055: No content was retrieved from the URL OR you have not specified the URL itself**

**Cause:** The URL did not return any content or the URL was null.

**Action:** Specify a valid URL.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13056: Unknown exception : %1**

**Cause:** An unhandled exception occurred during this operation.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13057: HTTPS not supported by UTL\_HTTP**

**Cause:** The HTTPS protocol was not supported by this component.

**Action:** Specify a non HTTPS URL.

**Level:** 1

**Type:** ERROR

---

**Impact:** Other

**WWV-13058: Content and URL both cannot be null**

**Cause:** The URL and content are empty.

**Action:** Either the URL or the content must have a value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13059: Content and URL both cannot have values.Entry should be made in only one of them**

**Cause:** Both the URL and content have values.

**Action:** Specify a value for the URL or content, not both.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13065: The Portal DB Provider provider has been registered. However**

**Cause:** The package may have been locked by another session for a time sufficient to result into a timeout.

**Action:** Contact the portal administrator and request that EXECUTE privileges be granted on this package for the provider schema.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13150: Unable to execute function: %1**

**Cause:** An attempt to move from one section to another in a wizard failed. This may have happened while executing the section level pre and post functions.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13300: Invalid component ID: %1**

**Cause:** The component ID was invalid.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13301: Unable to retrieve values for component ID: %1**

**Cause:** An attempt to load the component metadata for editing failed. This could be because the metadata has been removed or an inconsistency exists.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13303: Unable to save values for component ID: %1**

**Cause:** An attempt to save the component metadata for editing failed. This could be because there is some inconsistency in the metadata or there is a problem in the underlying database.

**Action:** Examine the Oracle error. If you cannot resolve it, contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13304: Unable to save LONG value for component ID: %1**

**Cause:** An attempt to save the component metadata for editing failed. This could be because there is some inconsistency in the metadata or there is a problem in the underlying database.

**Action:** Examine the Oracle error. If you cannot resolve it, contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13305: Unable to create a new version of component ID: %1**

**Cause:** An attempt to create a new version of a component failed. This could be because there is already a version with this number, or because there is a problem writing to the database.

**Action:** Examine the Oracle error. If you cannot resolve it, contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13306: Unable to create a new copy of component ID: %1 as component ID: %2**

**Cause:** An attempt to create a copy of a component failed. This could be because there is some problem while writing to the database.

**Action:** Examine the Oracle error. If you cannot resolve it, contact Oracle Support Services

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13307: Attribute %1 not found in component %2**

**Cause:** The attribute for the component could not be found.

**Action:** Contact Oracle Support Services.

---

**Level:** 1  
**Type:** ERROR  
**Impact:** Other  
**WWV-13308: Attribute %1 not found in type %2**  
**Cause:** The attribute for the component could not be found.  
**Action:** Contact Oracle Support Services.

**Level:** 1  
**Type:** ERROR  
**Impact:** Other  
**WWV-13309: Attribute with ID %1 does not exist**  
**Cause:** The attribute for the component could not be found.  
**Action:** Contact Oracle Support Services.

**Level:** 1  
**Type:** ERROR  
**Impact:** Other  
**WWV-13400: Error creating new component version for component ID: %1**  
**Cause:** A new version for the component could not be created.  
**Action:** Check whether the component is locked or contact Oracle Support Services

**Level:** 1  
**Type:** ERROR  
**Impact:** Other  
**WWV-13401: Error creating new component version for component type: %1**  
**Cause:** A new version for the component could not be created.  
**Action:** Check whether the component is locked or contact Oracle Support Services

**Level:** 1  
**Type:** ERROR  
**Impact:** Other  
**WWV-13402: Unable to get schema for component ID: %1**  
**Cause:** The schema on which the application is built may have been removed.  
**Action:** Re-create the schema. If problem persists, contact Oracle Support Services

**Level:** 1  
**Type:** ERROR  
**Impact:** Other  
**WWV-13403: Unable to get name for component ID: %1**  
**Cause:** The component metadata may have been removed inconsistently.  
**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13404: Unable to get component ID for: %1**

**Cause:** The component metadata may have been removed inconsistently.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13405: Unable to get maximum version number for component ID: %1**

**Cause:** The component metadata may have been removed inconsistently.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13407: Unable to get component type for component ID: %1**

**Cause:** The component metadata may have been removed inconsistently.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13409: Unable to set component name to %1 for component ID: %2**

**Cause:** The component metadata may have been removed inconsistently, or there may be a problem writing to the database table.

**Action:** Check the Oracle error or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13410: Unable to set component schema to %1 for component ID: %2**

**Cause:** The component metadata may have been removed inconsistently, or there may be a problem writing to the database table.

**Action:** Check the Oracle error or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13411: Unable to get the maximum section number for component type: %1**

**Cause:** The component metadata may have been removed inconsistently.

**Action:** Contact Oracle Support Services.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13412: Failed to initialize attributes for component ID: %1**

**Cause:** The component metadata may have been removed inconsistently.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13413: Failed to save attribute %1**

**Cause:** The component metadata may have been removed inconsistently, or there may be a problem writing to the database table.

**Action:** Check the Oracle error or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13414: Failed to update component status for component ID: %1**

**Cause:** The component metadata may have been removed inconsistently, or there may be a problem writing to the database table.

**Action:** Check the Oracle error or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13415: Commit failed**

**Cause:** The component metadata may have been removed inconsistently, or there may be a problem writing to the database table.

**Action:** Check the Oracle error or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13418: Failed to insert component: %1**

**Cause:** The component metadata may have been removed inconsistently, or there may be a problem writing to the database table.

**Action:** Check the Oracle error or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13419: Failed to update component: %1**

---

**Cause:** The component metadata may have been removed inconsistently, or there may be a problem writing to the database table.

**Action:** Check the Oracle error or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13420: Failed to set Privilege from Portal DB Provider: %1**

**Cause:** An error occurred as identified in the accompanying Oracle error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13421: Failed to get module info: %1**

**Cause:** An error occurred as identified in the accompanying Oracle error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13422: Failed to query component: %1**

**Cause:** An error occurred as identified in the accompanying Oracle error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13423: Error while copying menu as : %1**

**Cause:** An attempt to copy the menu failed.

**Action:** Check that the source menu is valid or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13424: Component %1 not exist.**

**Cause:** The component could not be found.

**Action:** Check that the component exists or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13426: Failed to delete component: %1**

**Cause:** An error occurred as identified in the accompanying Oracle error.

---

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-13427: Unable to set component title to %1 for component ID: %2**

**Cause:** The component metadata may have been removed inconsistently, or there may be a problem writing to the database table.

**Action:** Check the Oracle error or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-14500: User \"%1\" does not exist.**

**Cause:** The user could not be found.

**Action:** Check that the user specified is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-14501: Unable to retrieve user ID for user \"%1\".**

**Cause:** A user ID for this user name could not be found, possibly because it was removed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-14502: Unable to execute SQL(%1).**

**Cause:** The user does not have permissions on the table specified in the query, or the table could not be found.

**Action:** Login as a user with the appropriate privileges on the table or contact the portal administrator and request that the appropriate privileges be granted. If the problem persists, check that the table exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-14503: Unable to execute SQL(%1) as user \"%2\".**

**Cause:** The user does not have permissions on the table specified in the query, or the table could not be found.

**Action:** Login as a user with the appropriate privileges on the table or contact the portal administrator and request that the appropriate privileges be granted. If the problem persists, check that the table exists.

**Level:** 1



---

**Type:** ERROR

**Impact:** Other

**WWV-14600: Unable to determine action**

**Cause:** The DML action was invalid.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-14601: Error while building insert statement**

**Cause:** An attempt to build the insert statement failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-14602: Unable to parse statement %1**

**Cause:** An attempt to parse the statement failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-14603: Unable to handle datatype**

**Cause:** One of the data types was not supported.

**Action:** Specify supported data types.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-14604: Error while binding**

**Cause:** An attempt to bind the statement failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-14605: Unable to insert row**

**Cause:** An attempt to bind the statement failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWV-14606: Error while executing insert**

**Cause:** An attempt to execute the insert statement failed.

**Action:** Check the SQL error or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-14607: Error while building delete statement**

**Cause:** An attempt to build the insert statement failed.

**Action:** Contact Oracle Support Services. No rows deleted

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-14609: Error while executing delete**

**Cause:** An attempt to execute delete failed.

**Action:** Check the SQL error or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-14610: Error while executing update**

**Cause:** An attempt to execute update failed.

**Action:** Check the SQL error or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-14612: This row was changed by somebody else.**

**Cause:** An attempt to update the row failed.

**Action:** Refresh the row before updating.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-14613: Error while executing select statement**

**Cause:** An attempt to execute the select statement failed.

**Action:** Check the error displayed or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-14614: Unknown error while executing select**

**Cause:** An attempt to execute the select statement failed.

---

**Action:** Check the error displayed or contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-14617: Unexpected error - %1**

**Cause:** An unhandled exception occurred during this operation.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-14618: Error while building %1 statement. Either no new values were entered or there were no updatable columns.**

**Cause:** An attempt to build the statement failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-14800: Failed to parse query %1**

**Cause:** The SQL statement in the error message could not be parsed due to incorrect syntax or usage, or because it referenced an inaccessible object.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-14801: Unable to define columns for query %1**

**Cause:** The user does not have permissions on the table specified in the query, or the table could not be found.

**Action:** Login as a user with the appropriate privileges on the table or contact the portal administrator and request that the appropriate privileges be granted. If the problem persists, check that the table exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-14802: Unable to execute cursor using query %1**

**Cause:** The user does not have permissions on the table specified in the query, or the table could not be found.

**Action:** Login as a user with the appropriate privileges on the table or contact the portal administrator and request that the appropriate privileges be granted. If the problem persists, check that the table exists.

**Level:** 1

---

**Type:** ERROR

**Impact:** Other

**WWV-14803: Unable to fetch rows using query %1**

**Cause:** The user does not have permissions on the table specified in the query, or the table could not be found.

**Action:** Login as a user with the appropriate privileges on the table or contact the portal administrator and request that the appropriate privileges be granted. If the problem persists, check that the table exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-14901: Failed to execute the PL/SQL code after successful submission of the form: %1**

**Cause:** An error occurred as identified in the accompanying Oracle error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-15000: Unable to execute function: %1**

**Cause:** An attempt to execute functions in the component builder failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-15100: Failed to insert menu %1**

**Cause:** An attempt to insert menu data failed.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-15106: Failed to initialize builder attributes**

**Cause:** Design time metadata for the menu component could not be fetched.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-15147: Cannot add a menu item with blank name**

**Cause:** A menu item name was not specified.

**Action:** Specify a valid item name.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-15151: Footer length cannot exceed 2000 characters**

**Cause:** The footer length was too long.

**Action:** Specify a footer that is less than 200 characters in length.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-15152: Name length cannot exceed 200 characters**

**Cause:** The menu item name was too long.

**Action:** Specify an item name that is less than 200 characters in length.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-15157: Could not change parent**

**Cause:** The specified node was the top-most node, therefore it does not have a parent.

**Action:** Specify a child node.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-15200: Unexpected error encountered: %1**

**Cause:** An unhandled exception occurred during this operation.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-15201: Duplicate attribute name: %1**

**Cause:** The attribute name specified already exists.

**Action:** Specify a different attribute name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-15202: User %1 does not have privileges to create a Portal DB Provider**

**Cause:** The user does not have sufficient privileges to perform this task.

**Action:** Login as a user with the appropriate privileges or contact the portal administrator and request that the appropriate privileges be granted.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-15238: Failed to set default attributes for component %1**

**Cause:** One or more attributes could not be saved, possibly because they are invalid.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-16062: Cannot link to the module: %1**

**Cause:** Target component is not present or is in INVALID state.

**Action:** Make sure that the target component is present and is VALID.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-16075: Failed to initialize builder attributes: %1**

**Cause:** Design time metadata for the image chart could not be fetched.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-16170: The session identifier specified is not valid for this Portal session.**

**Cause:** The form's session was dropped or the user's login session expired.

**Action:** If this form requires the user to login, ensure that the user's login session is active. Also, ensure that the form's session is not dropped by any action done on the form.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-16409: Unable to generate UI form: %1**

**Cause:** The form could not be generated. There may not be enough permissions on the tables used in the form.

**Action:** If tables are mentioned in the error, contact the portal administrator and request that the appropriate privileges be granted. Alternatively, contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-16729: The following object could not be exported:**

---

**Cause:** An attempt to export the listed components failed.

**Action:** Refer to the specific error message for each component.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-16752: The test did not succeed.**

**Cause:** The database object may be invalid.

**Action:** Check the status of the database object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-16753: Unable to connect to the remote database. There may be some error in the username**

**Cause:** The user name, password, or connect string used to create the database link may be incorrect, or the server may not be ready for a connection.

**Action:** Check that the database is up and verify that all connection information is correct.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-16865: The background job (id= %1) for revoking privileges on Portal packages from the database user %2 has failed. Thus**

**Cause:** A database issue could have caused the job to fail.

**Action:** Contact the database administrator to resolve the database issue that caused the job to fail and then try deleting the schema again.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-16866: The background job (id= %1) for revoking privileges on Portal packages from the database user %2 is still running. Deleting the schema %2 cannot be done unless the job is over.**

**Cause:** Background jobs may take a long time to complete if the database is overloaded.

**Action:** Check the Grant Access page of the schema to see the list of packages on which privileges should be revoked before the schema can be deleted. If, after a while, some packages still exist on which privileges have not been revoked, contact the database administrator and request that the background job be examined further.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWV-16871: Username cannot be null.**

**Cause:** A user name was not specified.

**Action:** Specify a valid user name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-16942: Choose another name for your script. The script %1 already exists.**

**Cause:** A script with this name already exists.

**Action:** Specify a different name for the script.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-16969: The script is empty**

**Cause:** Content was not specified for the script.

**Action:** Specify at least one valid SQL statement in the script.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17001: Argument name : %1 :: OUT and IN OUT Arguments cannot have default values**

**Cause:** Default values were provided for parameters of types OUT/IN OUT.

**Action:** Remove the default values for these parameters.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17002: Invalid argument : %1 cannot contain spaces**

**Cause:** The value specified contained a blank space. Blank spaces are not valid in this case.

**Action:** Specify a value that does not contain blank spaces.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17003: Invalid columns : At least one column required**

**Cause:** No columns were specified.

**Action:** Provide details for at least one column.

**Level:** 1

**Type:** ERROR

**Impact:** Other



---

**WWV-17005: Invalid column %1 : Mismatch between datatype and default value.**

**Cause:** The default value and the column are different data types.

**Action:** Make sure the data types match.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17007: Rename failed**

**Cause:** The database object may be invalid.

**Action:** Check the status of the database object.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17009: Duplicate columns not allowed : %1**

**Cause:** Multiple columns with the same name were found.

**Action:** Change the name of the columns so that each column has a distinct name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17021: Failed to grant the %1 privilege. To grant a privilege on a view**

**Cause:** The user may not have privileges for all the objects referenced in the view.

**Action:** Login as a user with the appropriate privileges or contact the portal administrator and request that the appropriate privileges be granted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17024: You have not selected any columns. Select at least one column**

**Cause:** No columns were selected for the component.

**Action:** Select at least one column.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17027: Duplicate constraints are not allowed : %1 is already used for specifying a constraint**

**Cause:** A constraint with the same name already exists.

**Action:** Specify a different name for the constraint.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWV-17043: Unable to disable trigger %1**

**Cause:** An attempt to disable a trigger failed. The user may not have the appropriate permissions, or the trigger may have been dropped during this operation.

**Action:** Login as a user with the appropriate privileges or contact the portal administrator and request that the appropriate privileges be granted. If the problem persists, check that the trigger exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17044: Unable to drop trigger %1**

**Cause:** An attempt to drop a trigger failed. The user may not have the appropriate permissions, or the trigger may have been dropped during this operation.

**Action:** Login as a user with the appropriate privileges or contact the portal administrator and request that the appropriate privileges be granted. If the problem persists, check that the trigger exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17046: Selected schema %1 does not exist or you do not have privilege to access it.**

**Cause:** An attempt to select a schema failed. The schema may not exist or the user may not have the appropriate privileges to access it.

**Action:** Login as a user with the appropriate privileges or contact the system administrator and request that the appropriate privileges be granted. If the problem persists, check that the schema exists.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17063: Select at least one table from the list of tables.**

**Cause:** A table was not specified.

**Action:** Select a table or specify a valid table name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17077: Precision value for a numeric column must be in the range of -84 and 127.**

**Cause:** The precision specified for the numeric column is invalid.

**Action:** Specify a valid precision for the numeric column.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWV-17078: A constraint name is required.**

**Cause:** A name was not specified for the constraint.

**Action:** Specify a name for the constraint.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17081: %1 length should not exceed %2 bytes.**

**Cause:** The value specified was too long.

**Action:** Specify a shorter value.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17082: %1 contains Invalid Characters. You cannot have the following characters in any name : `-=[];**

**Cause:** The specified name included invalid characters.

**Action:** Specify a name that does not contain the characters listed in the error message.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17083: Cannot edit index (%1) used for enforcement of unique/primary key. Change the integrity constraints instead of editing the index.**

**Cause:** An attempt was made to edit an index from a unique/primary key.

**Action:** Change the integrity constraints from the table instead of the unique/primary key.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17085: Either the object %1 does not exist**

**Cause:** The object does not exist, it is not a table or view, or the schema does not have the appropriate privileges on it.

**Action:** Ensure that the object is a table or view and that the schema has appropriate privileges on it.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17086: Column %1 is of type %2. Column of datatype CLOB**

**Cause:** The data type specified for the primary/unique/foreign key column is not appropriate.

**Action:** Refer to the SQL documentation for a list of data types that are not allowed to be part of a primary/unique/foreign key.

---

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17088: Column %1 is of datatype %2. Maximum length is %3 and minimum is %4.**

**Cause:** An invalid value was specified for the column length.

**Action:** Specify a value within the maximum and minimum values shown in the error message.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17090: Default value's length exceeds the column length for column %1.**

**Cause:** The value specified as the default column value is larger than the column can hold.

**Action:** Specify a value that fits in the column.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17091: Invalid Name : %1. A name cannot start with any of the following characters : `1234567890-=[]\;'**

**Cause:** The name specified starts with an invalid character.

**Action:** Specify a valid name and ensure that it does not start with any of the characters mentioned in the error message.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17104: Filename cannot be null.**

**Cause:** A file name was not specified.

**Action:** Specify a valid file name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17106: Invalid file extension. Permissible extensions are .java for Java Source**

**Cause:** The extension of the file specified is not appropriate.

**Action:** Specify a .java, .class, or .jar file.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17107: File does not exist or the file is empty.**

---

**Cause:** The file specified does not exist or is empty.

**Action:** Specify a valid file name.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17128: The constraint has not been added to the list. Click the Add-to-List button to do this.**

**Cause:** The constraint was not added to the table.

**Action:** Click the Add to List button to add the constraint to the table.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17129: Column %1 cannot be nullable since it is the primary key.**

**Cause:** A value was not specified for the primary key.

**Action:** Specify a value for the primary key.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17135: The database link was created successfully**

**Cause:** The remote database or listener could be down, or the connect information supplied may be incorrect.

**Action:** Verify the connect information. If the problem persists, make sure the remote database and listener are up and running.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17139: Either the column conditions are not specified properly or the specified where clause is invalid.**

**Cause:** An incorrect condition or an invalid clause were specified.

**Action:** Review the column condition/clause and make appropriate changes.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17141: Invalid Name: %1. Cannot use spaces in the name.**

**Cause:** The name specified contains a space.

**Action:** Specify a name that does not contain spaces.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWV-17245: Create schema failed**

**Cause:** A schema with the same name may already exist or the user may not have sufficient privileges to create a schema.

**Action:** Specify a different, unique name for the schema. If the problem persists, contact the portal administrator and request that the appropriate privileges be granted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17246: Update schema failed**

**Cause:** A schema with the same name may already exist or the user may not have sufficient privileges to create a schema.

**Action:** Specify a different, unique name for the schema. If the problem persists, contact the portal administrator and request that the appropriate privileges be granted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17293: GRANT ROLE action failed**

**Cause:** The user may not have sufficient privilege to perform the GRANT ROLE action.

**Action:** Login as a user with the appropriate privileges or contact the portal administrator and request that the appropriate privileges be granted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17294: REVOKE ROLE action failed**

**Cause:** The user may not have sufficient privilege to perform the REVOKE ROLE action.

**Action:** Login as a user with the appropriate privileges or contact the portal administrator and request that the appropriate privileges be granted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17298: Failed to grant role %1**

**Cause:** The user may not have sufficient privilege to perform the GRANT ROLE action.

**Action:** Login as a user with the appropriate privileges or contact the portal administrator and request that the appropriate privileges be granted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

---

**WWV-17299: Failed to revoke role %1**

**Cause:** The user may not have sufficient privilege to perform the REVOKE ROLE action.

**Action:** Login as a user with the appropriate privileges or contact the portal administrator and request that the appropriate privileges be granted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17300: Could not create role %1**

**Cause:** An attempt to create a role failed, possibly because the user does not have the appropriate privileges.

**Action:** Login as a user with the appropriate privileges or contact the portal administrator and request that the appropriate privileges be granted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17302: Schema or Password or Confirm Password does not follow Oracle Naming conventions or is a reserved word**

**Cause:** The values specified for the fields do not conform to the rules for naming schema objects.

**Action:** Specify correct values for these fields. Refer to the SQL for assistance.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17310: Password or Confirm Password is null**

**Cause:** A value was not specified for the Password field or Confirm Password field.

**Action:** Specify the same value for the Password and the Confirm Password fields.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17453: Unable to kill session**

**Cause:** The user may not have the appropriate permissions to kill the session, or the session may have been killed by another user.

**Action:** Check that the session still exists. If it does, contact the portal administrator and request that the appropriate privileges be granted.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17700: Failed to query data component: %1**

---

**Cause:** An error occurred as identified in the accompanying Oracle error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17701: Failed to copy data component: %1**

**Cause:** An error occurred as identified in the accompanying Oracle error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17702: Failed to update data component: %1**

**Cause:** An error occurred as identified in the accompanying Oracle error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17703: Failed to delete data component: %1**

**Cause:** An error occurred as identified in the accompanying Oracle error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17704: Failed to create data component: %1**

**Cause:** An error occurred as identified in the accompanying Oracle error.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17717: Set default columns failed**

**Cause:** One or more attributes were not saved, possibly because they were invalid.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-17719: Unable to save value for attribute ID: %1 for value: %2**

**Cause:** An attempt to save the component metadata failed.



---

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-61269: Failed to save parameters!**

**Cause:** An error occurred in the user preference storage subsystem.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other

**WWV-61294: Failed to initialize builder attributes**

**Cause:** Design time metadata could not be fetched.

**Action:** Contact Oracle Support Services.

**Level:** 1

**Type:** ERROR

**Impact:** Other



---

## WXE-00010 to WXE-21271

**WXE-00010: %s**

**Cause:** Internal error raised.

**Action:** No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-00800: Auto-Restart started successfully**

**Cause:** The Auto-Restart process has successfully completed its initialization.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-08000: Internal error. Auto-Restart process terminating.**

**Cause:** An internal error occurred in the Auto-Restart process.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. This error usually occurs as a result of insufficient system resources. If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**WXE-08001: Failed to start the cache server. Auto-Restart process terminating.**

**Cause:** Failed to start the Oracle Web Cache server.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. This error usually occurs as a result of insufficient system resources. If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Process

---

**WXE-08002: Failed to find an Oracle Web Cache listening port that does not require SSL client-side certificates. Auto-Restart pinging is disabled.**

**Cause:** Auto-Restart does not support the use of client-side certificates. If all Oracle Web Cache listening ports require client-side certificates, then pinging is disabled in the Auto-Restart mechanism.

**Action:** To enable pinging, add a listening port that does not require client-side certificates.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-08500: Cache server not responding on port %d.**

**Cause:** The cache server may not have been running. The Auto-Restart process will continue to try to reach the cache server on the specified port.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-08501: Timeout occurred communicating with the cache server.**

**Cause:** The cache server was either in an unstable state or slow responding to queries.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. From the Auto-Restart page of Oracle Enterprise Manager or Oracle Web Cache Manager, check the ping timeout interval and increase it if necessary.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-08502: Lost connection with the cache server.**

**Cause:** There were communication errors between the Auto-Restart process and the cache server. The Auto-Restart process will continue to try to reach the cache server.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-08503: Operating system level error in %s() (%d): %s.**

**Cause:** The specified system call returned the specified error.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 16

**Type:** ERROR

---

**Impact:** Operating System

**WXE-08504: %u consecutive errors ping the cache server.**

**Cause:** The Auto-Restart process received the specified number of failures when attempting to reach the cache server.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-08505: %u consecutive error(s) ping the cache server. %d error(s) required for restart.**

**Cause:** The Auto-Restart process received the specified number of failures when attempting to reach the cache server. The error message indicates the number of times the Auto-Restart process will attempt to reach the cache server.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-08506: Unable to retrieve the cache server process ID from %s. Stopping the Auto-Restart process.**

**Cause:** Unable to read the Oracle Web Cache server pid file. Most likely the file was deleted during a normal termination of the server. As a result, the Auto-Restart process was also shut down.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-08507: Cache server process not running.**

**Cause:** There was no process on the system matching the process ID listed in the Oracle Web Cache server pid file.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Process

**WXE-08508: Restarting the cache server.**

**Cause:** See accompanying error messages for more information.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

---

**Type:** ERROR

**Impact:** Process

**WXE-08509: Starting the cache server.**

**Cause:** See accompanying error messages for more information.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**WXE-08510: SSL set hardware acceleration failed. NZE-%d.**

**Cause:** The SSL library failed to initialize the hardware SSL acceleration. The specified error message provides more detail.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. See the "Network Security Messages (NZE)" chapter of the Oracle Database Error Messages for information about NZE errors.

**Level:** 16

**Type:** ERROR

**Impact:** Security

**WXE-08511: SSL Set Thread Usage Failed. NZE-%d.**

**Cause:** The SSL library failed to set the threading model. The specified error message provides more detail.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. See the "Network Security Messages (NZE)" chapter of the Oracle Database Error Messages for information about NZE errors.

**Level:** 16

**Type:** ERROR

**Impact:** Security

**WXE-08512: SSL Engine Failed to Initialize. NZE-%d.**

**Cause:** The SSL engine failed to initialize. The specified error message provides more detail.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. See the "Network Security Messages (NZE)" chapter of the Oracle Database Error Messages for information about NZE errors.

**Level:** 16

**Type:** ERROR

**Impact:** Security

**WXE-08513: Cache server process ID %u is starting up.**

**Cause:** The cache server is starting up.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

---

**Impact:** Process

**WXE-08514: Cache server process ID %u is shutting down.**

**Cause:** The cache server is shutting down.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Process

**WXE-08515: Event log message %d (%s) referenced %d time(s)**

**Cause:** Occurrence frequency of various event\_log message

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**WXE-08516: Event log index %d contains %d node(s)**

**Cause:** Occurrence frequency of various event\_log message

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**WXE-09000: Oracle Web Cache process of ID %d exits with code %d at line %d of file %s [label: %s]**

**Cause:** The Oracle Web Cache process shutdown.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**WXE-09001: An error occurred while disabling core file creation.**

**Cause:** Internal error. The system/library call to disable core file creation returned an error.

**Action:** If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WXE-09003: File %.\*s open failed; using %.\*s instead**

**Cause:** The attempt to open the specified file failed. Oracle Web Cache opened the new file instead.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

---

**Impact:** Logging

**WXE-09200: An error occurred while trying to create a background process.**

**Cause:** Could not open standard input while Oracle Web Cache is creating a process.

**Action:** Determine why Oracle Web Cache cannot read standard input or write to standard output for null device.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**WXE-09401: %s[%d].%s: %s**

**Cause:** Statistics information dumped to event log on server shutdown

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09402: %s[%d].%s: %ld**

**Cause:** Statistics information dumped to event log on server shutdown

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09403: Maximum number of file/socket descriptors set to %s.**

**Cause:** The specified number of file descriptors is set for use by Oracle Web Cache.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09404: DMS metadata load starting**

**Cause:** Loading DMS metadata information

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09405: DMS metadata load complete**

**Cause:** Loading DMS metadata information

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.



---

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09411: DMS shutdown starting**

**Cause:** Loading DMS metadata information

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09412: DMS shutdown complete**

**Cause:** Loading DMS metadata information

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09418: DMS disabled**

**Cause:** Loading DMS metadata information

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09420: Error accessing the Oracle Dynamic Monitoring Service library, %s: %s**

**Cause:** An error occurred when attempting to open or access functions in the Oracle Dynamic Monitoring Service (DMS) library. See the operating system level error message included in this message. The error message provides further details, such as "file not found" or function not available".

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09421: Unable to open the Oracle Dynamic Monitoring Service library, %s:%s. Searching the library path.**

**Cause:** An error occurred when attempting to open the Oracle Dynamic Monitoring Service (DMS) library. See the operating system level error message included in this message. The error message provides further details, such as "file not found". Oracle Web Cache will search the library path. If the library is still not / found, then Oracle Web Cache returns event message 09420. NOTE: DMS statistics collection has been disabled until the problem is resolved.

---

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-09422: Error accessing %s in the Oracle Dynamic Monitoring Service library, %s: %s**

**Cause:** An error occurred when attempting to open or access functions in the Oracle Dynamic Monitoring Service (DMS) library. See the operating system level error message included in this message. The error message provides further details, such as "file not found" or function not available".

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09424: The statistics persistent repository is disabled**

**Cause:** The statistics persistent repository has been disabled by the user in the webcache.xml configuration file.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09425: The %s file is no longer valid**

**Cause:** The wcstatsrepos.xml file has been modified since the cache was started. The contents and/or changes are ignored.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09426: The %s statistics persistent repository does not exist**

**Cause:** The wcstatsrepos.xml file statistics persistent repository does not exist; this may be the first time the repository has been accessed.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09427: Failure during file move of %s. Statistics persistent repository is abandoned**

**Cause:** File move or rename failed.

**Action:** No action required.

---

**Level: 1**

**Type: ERROR**

**Impact: Requests/Responses**

**WXE-09428: An error occurs during statistics repository download. The file %s has been corrupted or moved.**

**Cause:** The "wcstatsrepos.xml" file was corrupted or moved during the shutdown operation.

**Action:** Recover "wcstatsrepos.xml" by copying from "wcstatsrepos.bak".

**Level: 1**

**Type: ERROR**

**Impact: Requests/Responses**

**WXE-09429: Failed to open the %s file. Statistics persistent repository is abandoned**

**Cause:** Failed to open the "wcstatsrepos.tmp" temporary file.

**Action:** No action required.

**Level: 1**

**Type: ERROR**

**Impact: Requests/Responses**

**WXE-09430: Failure creating the %s file. Statistics persistent repository is abandoned**

**Cause:** Failed to write to or close the "wcstatsrepos.tmp" temporary file.

**Action:** No action required.

**Level: 1**

**Type: ERROR**

**Impact: Requests/Responses**

**WXE-09431: The statistics persistent repository is being reset by new version**

**Cause:** The statistics persistent repository has been invalidated by the installation of a new Oracle Web Cache software version

**Action:** No action required.

**Level: 1**

**Type: ERROR**

**Impact: Requests/Responses**

**WXE-09432: Starting statistics persistent repository checkpoint operation**

**Cause:** The statistics persistent repository is being checkpointed.

**Action:** No action required.

**Level: 1**

**Type: NOTIFICATION**

**Impact: Requests/Responses**

**WXE-09433: Completed statistics persistent repository checkpoint operation**

**Cause:** The statistics persistent repository is being checkpointed.

---

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09438: The statistics persistent repository is being reset by new configuration**

**Cause:** The statistics persistent repository has been invalidated by a change to the Oracle Web Cache configuration file (webcache.xml)

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09440: The statistics persistent repository is disabled by event**

**Cause:** The statistics persistent repository has been disabled because the "last" event is marked as "VALID=NO".

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09441: DMS enabled**

**Cause:** Loading DMS metadata information

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09442: Unable to resolve APIs in the Oracle Dynamic Monitoring Service library, %s:%s**

**Cause:** An error occurred when attempting to resolve public APIs in the Oracle Dynamic Monitoring Service (DMS) library.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09443: All APIs in the Oracle Dynamic Monitoring Service library have been resolved**

**Cause:** All external APIs have been identified and properly resolved.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** NOTIFICATION

---

**Impact:** Requests/Responses

**WXE-09444: The statistics persistent repository cannot be processed: %d**

**Cause:** The statistics persistent repository has been determined to not match the current statistics configuration.

**Action:** No action required. The statistics repository will be rebuilt automatically at the next specified checkpoint interval or when the webcache server shuts down.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09445: Dynamic Metric Services allocating excessive memory block:%d**

**Cause:** The Dynamic Metric Services (DMS) is allocating a memory buffer that is potentially too large.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-09446: Statistics initialization commencing.**

**Cause:** The statistics information initialization operation is beginning.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-09447: Statistics initialization complete.**

**Cause:** The statistics information initialization operation is complete.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-09521: Oracle Web Cache fails to find user ( %s ) in /etc/passwd.**

**Cause:** The specified user was not found in the password file.

**Action:** Add user to the password file.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09522: Oracle Web Cache fails to find group ( %s ) in /etc/group.**

**Cause:** The specified group was not found in the group file.

**Action:** Add the group to the group file or modify the group ID in the Security page of Fusion Middleware Control.

**Level:** 1

---

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09523: Invalid user ID ( %s ).**

**Cause:** The specified user ID was invalid.

**Action:** Correct the user ID in the Security page of Fusion Middleware Control.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09524: Invalid group ID ( %s )**

**Cause:** The specified group ID was invalid.

**Action:** Correct the group ID in the Security page of Fusion Middleware Control.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09525: Permission denied when setting user ID ( %s ).**

**Cause:** The specified user did not have the required permissions when setting the user ID.

**Action:** Grant the user required permissions or log in as a different user.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09526: Permission denied when setting group ID ( %s ).**

**Cause:** The user did not have the required permissions when setting group ID.

**Action:** Grant the user required permissions or log in as a different user.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09534: Unexpected File I/O Error ( %s ) when opening file %s.**

**Cause:** Could not open specified file.

**Action:** Review specified error to determine the problem on your system.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09570: Directory not found when unlinking file %s**

**Cause:** The directory was not found.

**Action:** Verify that Oracle Web Cache was installed properly. You may need to reinstall Oracle Web Cache.

**Level:** 1

---

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09571: Too many files open when unlinking file %s.**

**Cause:** Too many files were open for available system resources.

**Action:** Adjust system resources and restart Oracle Web Cache.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09572: No disk space available when unlinking file %s**

**Cause:** Insufficient disk space was available on the system.

**Action:** The system is running low on disk space. Free up disk space and restart Oracle Web Cache.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09573: Unexpected File I/O Error ( %s ) when unlinking file %s.**

**Cause:** There was an unexpected input/output file error.

**Action:** Review the specified error and correct the problem on the system.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09574: Permission denied when unlinking file %s.**

**Cause:** Permission denied on file.

**Action:** Set correct permission on the specified file.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09600: SIGTERM caught - program will shut down once all connections are complete.**

**Cause:** Normal notification behavior. Shutdown event written to the log file.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09601: SIGUSR1 caught - program will reread configuration files after all connections are complete.**

**Cause:** Normal notification behavior. Configuration file reread event written to the log file.

---

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09602: All configuration files have been reread.**

**Cause:** Normal notification behavior. All configuration files have been reread and this configuration reload event written to the log file.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**WXE-09603: There was an error rereading the configuration files. The program is exiting.**

**Cause:** Invalid Oracle Web Cache configuration files.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Correct the Oracle Web Cache configuration files and restart Oracle Web Cache.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WXE-09604: Could not increase the number of file/socket descriptors to %s.**

**Cause:** Ran out of file descriptors on the system.

**Action:** Decrease the Maximum Incoming Connections value in the Resource Limits of Fusion Middleware Control, or increase the system file descriptors. Run Oracle Web Cache as the root user.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09605: Cannot create OPMN shutdown thread. Continuing with startup.**

**Cause:** Oracle Web Cache could not create OPMN shutdown thread.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Use OPMN to abort the Oracle Web Cache process during Oracle Web Cache shutdown.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09606: Cannot create OPMN shutdown event. Continuing with startup.**

**Cause:** Oracle Web Cache could not create OPMN shutdown event.

**Action:** Use OPMN to abort the Oracle Web Cache process during Oracle Web Cache shutdown.



---

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09607: The admin server started successfully.**

**Cause:** The Oracle Web Cache admin server process started successfully.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Process

**WXE-09608: The cache server process started successfully.**

**Cause:** The Oracle Web Cache server process has started successfully.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Process

**WXE-09609: The server process could not initialize.**

**Cause:** The Oracle Web Cache configuration is invalid.

**Action:** Review the error log file or use the Event Viewer to help determine the cause of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**WXE-09610: The server is exiting.**

**Cause:** The cache server or admin server process is terminating.

**Action:** Review the error log file or use the Event Viewer to help determine the cause of the problem.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Process

**WXE-09611: The server could not start the service thread.**

**Cause:** The server process could not start the Service thread.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Determine why Oracle Web Cache cannot start a thread on your system.

**Level:** 1

**Type:** ERROR

**Impact:** Threads

**WXE-09612: Oracle Web Cache %s, %s**

---

**Cause:** Normal notification behavior. The Oracle Web Cache version number was written to the log file.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09614: The following Oracle Web Cache internal files are pre-populated to the cache: [[ %s ]]**

**Cause:** The specified Oracle Web Cache internal files are loaded into the cache.

**Action:** No required action.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09615: SMALLDOCBUFFERSIZE larger than DOCBUFFERSIZE. Setting SMALLDOCBUFFERSIZE=%s**

**Cause:** Invalid Oracle Web Cache configuration. The SMALLDOCBUFFERSIZE is larger than DOCBUFFERSIZE.

**Action:** Review your configuration. Oracle Web Cache will override your current configuration for SMALLDOCBUFFERSIZE.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-09616: The Oracle Web Cache is running in the routing only mode.**

**Cause:** The Oracle Web Cache is running in the routing only mode.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09700: Unable to initialize NLS. Error %d**

**Cause:** Internal error. A system/library call has unexpectedly failed.

**Action:** If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09701: Unable to initialize NLS global structure.**

**Cause:** Internal error. A system/library call has unexpectedly failed.

**Action:** If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**WXE-09702: NLS boot file not found or missing; using default.**

**Cause:** Internal error. A system/library call has unexpectedly failed.

**Action:** If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-09703: Stop Issued. The program will shut down after all accepted requests are served, or a timeout occurs.**

**Cause:** Stop was issued.

**Action:** Oracle Web Cache will be stopped.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09704: Abort Issued. The program will shut down immediately.**

**Cause:** Abort was issued.

**Action:** Oracle Web Cache will be stopped immediately.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09705: Error accessing the Oracle Notification Service library, %s: %s**

**Cause:** An error occurred when attempting to open or access functions in the Oracle Notification Service (ONS) library. See the operating system level error message included in this message. The error message provides further details, such as "file not found" or function not available".

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09706: Ignoring unrecognized option: %s**

**Cause:** An alert was logged.

**Action:** Refer to the logged alert details and take the appropriate action.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09707: Failed to start the server.**

**Cause:** Failed to start the Oracle Web Cache server. This error usually occurs as a result of insufficient system resources or invalid configuration.

**Action:** If the problem persists, contact Oracle Support.

---

**Level:** 1

**Type:** ERROR

**Impact:** Process

**WXE-09708: Failed to initialize DNS**

**Cause:** Failed to initialize DNS.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09709: Failed to initialize the HTTP component**

**Cause:** Failed to initialize HTTP.

**Action:** If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09710: Cache server failed to initialize.**

**Cause:** Insufficient system resources or invalid Oracle Web Cache configuration.

**Action:** Review the error log file or use the Event Viewer to help determine the cause of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Process

**WXE-09711: Problem loading message file for event log. Exiting.**

**Cause:** Message file for event log was not correctly loaded.

**Action:** Check the existence and permissions of the file wxeus.msb in \$ORACLE\_HOME/webcache/mesg/wxeus.msb on UNIX and ORACLE\_HOME\\webcache\\mesg on Windows.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09712: Unable to open the Oracle Notification Service library, %s:%s.  
Searching the library path.**

**Cause:** An error occurred when attempting to open the Oracle Notification Service (ONS) library. See the operating system level error message included in this message. The error message provides further details, such as "file not found". Oracle Web Cache will search the library path. If the library is still not / found, then Oracle Web Cache returns event message 09705.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. If the problem persists, contact Oracle Support.

**Level:** 1

---

**Type:** WARNING  
**Impact:** Requests/Responses  
**WXE-09716: LDMInit Error %d**  
**Cause:** LDM library cannot be initialized  
**Action:** Check the error number  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses  
**WXE-09717: LDMOpen Error %d**  
**Cause:** LDM repository cannot be opened  
**Action:** Check the error number  
**Level:** 1  
**Type:** ERROR  
**Impact:** Requests/Responses  
**WXE-09718: eOns component already initialized; continuing...**  
**Cause:** The eOns component could not be initialized directly by the Oracle Web Cache server because eOns has already been previously initialized. The Oracle Web Cache server will continue to startup.  
**Action:** No action required.  
**Level:** 1  
**Type:** WARNING  
**Impact:** Requests/Responses  
**WXE-09719: Initializing eOns component using port %s.**  
**Cause:** The eOns component is being initialized with the identified port number  
**Action:** No action required.  
**Level:** 1  
**Type:** NOTIFICATION  
**Impact:** Requests/Responses  
**WXE-09720: req-info**  
**Cause:** Logging request information to the event\_log.  
**Action:** No action required.  
**Level:** 1  
**Type:** NOTIFICATION  
**Impact:** Requests/Responses  
**WXE-09721: Cluster initialization failure.**  
**Cause:** Cluster initialization fails.  
**Action:** No action required.  
**Level:** 1

---

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09722: Could not create specified access\_log file.**

**Cause:** The access\_log was unable to be created.

**Action:** If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09723: Could not establish effective user identification.**

**Cause:** Could not establish the effective user identification. This may indicate an improper installation.

**Action:** If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-09732: Oracle Instance configuration directory is not available.**

**Cause:** One of the these environment variables, ORACLE\_INSTANCE, COMPONENT\_TYPE, or COMPONENT\_NAME, is not defined.

**Action:** If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WXE-09733: The configuration file webcache.xml cannot be found.**

**Cause:** The Oracle Web Cache instance may not be provisioned correctly or the file system is full.

**Action:** If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WXE-09807: Statistics query fatal error: %.\*s**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09811: Unknown value type:%d**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

---

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09812: Unknown instruction value type:%d**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09813: Bad operator in stack:%d**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09814: Unknown variable value type:%d**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09815: Unknown variable type:%d**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09816: Invalid register index**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09817: Invalid address value type**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

---

**WXE-09818: Incompatible operands**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09819: Unknown value type**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09820: Invalid addition operand type**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09821: Invalid subtraction operand type**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09822: Invalid less-than operand type**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09823: Invalid less-than-equal operand type**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09824: Invalid greater-than operand type**

**Cause:** The statistics query failed for the specified reason.



---

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09825: Invalid greater-than-equal operand type**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09826: Invalid multiply operand type**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09827: Invalid division operand type**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09828: Division by zero exception**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09829: Invalid modulo operand type**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09830: Invalid shift-left operand type**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09831: Invalid shift-right operand type**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09832: Invalid bitwise-AND operand type**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09833: Invalid exclusive-OR operand type**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09834: Invalid inclusive-OR operand type**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09835: Invalid function index type**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09836: Invalid instruction:%d**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**WXE-09837: Stack overflow**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09838: Bad expression**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09839: Assignment needs an lvalue**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09840: Missing an operand**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09841: Assignment needs an lvalue**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09842: Missing expression ')'**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09843: Missing function '('**

---

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09844: Missing function ')'**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09845: Unexpected character in input: '%c'**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09846: Too many variables**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09847: Unterminated string**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09848: Unterminated string**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09849: Unknown column number (only %d columns available)**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

---

**Level: 1**

**Type: ERROR**

**Impact: Requests/Responses**

**WXE-09850: Builtin function %s() argument type mismatch**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level: 1**

**Type: ERROR**

**Impact: Requests/Responses**

**WXE-09851: Invalid logical-OR operand type**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level: 1**

**Type: ERROR**

**Impact: Requests/Responses**

**WXE-09852: Expression already compiled**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level: 1**

**Type: ERROR**

**Impact: Requests/Responses**

**WXE-09853: Expression not yet compiled**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level: 1**

**Type: ERROR**

**Impact: Requests/Responses**

**WXE-09854: Invalid logical-AND operand type**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level: 1**

**Type: ERROR**

**Impact: Requests/Responses**

**WXE-09855: Unknown statistics group member %.\*s**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level: 1**

**Type: ERROR**

---

**Impact:** Requests/Responses

**WXE-09856: Invalid ones-complement operand type**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09857: Invalid negation operand type**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09858: Invalid regular expression: %.\*s**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09859: Expression context has not been initialized**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09860: Incorrect function argument separator usage**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09861: Invalid register name: '%c'**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09862: Expression too complex**

---

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09863: Invalid row %d specified when %d rows exist; no value obtained**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-09864: Query operation not yet implemented or supported: %s**

**Cause:** The statistics query failed for the specified reason.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-10054: Unable to resume service, UIPI return value is %s.**

**Cause:** Service could not be resumed.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Review the error to determine the problem on your system.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-10417: MIME Type Extension ( %s ) exceeds current size limit.**

**Cause:** Unexpected MIME type configured.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-10418: Encoding Extension ( %s ) exceeds current size limit.**

**Cause:** Unexpected encoding type configured.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

---

**WXE-10419: Language Extension ( %s ) exceeds current size limit.**

**Cause:** Unexpected language type configured.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-10536: You must specify a full path for %s. See %s %s.**

**Cause:** Failed to specify full path name.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Specify a full path name for the file.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-10555: Bad integer value ( %s ). See %s %s.**

**Cause:** Invalid drive letter.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-10599: Unexpected error**

**Cause:** Unexpected internal error.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11057: Dynamic origin server capacity is reduced to %d.**

**Cause:** Oracle Web Cache ran out of file descriptors on the computer.

**Action:** Increase the file descriptor limit. See the Oracle Fusion Middleware Secure Proxy Caching and Load Balancing Guide for Oracle Web Cache.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11058: Stale object updated for %.\*s%.\*s**

**Cause:** The complete response was successfully received and the cache entry is updated with the new response.

**Action:** No action required.

**Level:** 1



---

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11059: Garbage object updated for %.\*s%.\*s**

**Cause:** The complete response was successfully received and the cache entry is updated with the new response.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11060: Object update aborted.**

**Cause:** The response will not be used to update the stale or garbage object in the cache because it was determined that it is not cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11062: <!-- WEBCACHETAG--> and <!-- WEBCACHEEND--> tag parsing error**

**Cause:** The syntax for the <!-- WEBCACHETAG--> and <!-- WEBCACHEEND--> tags was incorrect.

**Action:** Correct the syntax of the <!-- WEBCACHETAG--> and <!-- WEBCACHEEND--> tags in the source.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11064: ESI object %.\*s%.\*s parsing error**

**Cause:** Object contained invalid ESI syntax.

**Action:** Correct the ESI syntax in the source.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11076: Cluster member %s - %s sent invalid configuration error**

**Cause:** The cache cluster member sent a response to Oracle Web Cache that indicates it has a configuration file different than the local configuration file for the cache cluster. A cluster runtime operates with the same webcache.xml configuration file for all members.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Compare the two configuration files, and then propagate the proper version to all cluster members.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

---

**WXE-11077: Cluster member sent invalid configuration error**

**Cause:** The cache cluster member sent a response to Oracle Web Cache that indicates it has a configuration file different than the local configuration file for the cache cluster. A cluster runtime operates with the same webcache.xml configuration file for all members.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Compare the two configuration files, and then propagate the proper version to all cluster members.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11078: Malformed environment object %.\*s%.\*s**

**Cause:** The syntax of the XML file specified by the ESI environment is incorrect.

**Action:** Check the XML object for possible syntax errors.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11081: error while setting up the URI for +wcdebug for peer**

**Cause:** Not applicable

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11082: error while constructing Inter-Cache Communication (ICC) header**

**Cause:** Not applicable

**Action:** No action required.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11083: Proxy server configuration error: %s**

**Cause:** The proxy server was not correctly configured.

**Action:** Check the proxy server configuration in the Origin Servers page of Fusion Middleware Control and the general configuration of the proxy server itself.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11085: Authentication for the remote or subscriber cache is being challenged by a central or provider cache. Retry.**

**Cause:** Access to the central or provider cache requires authorization.

**Action:** Try accessing the cache again.

---

**Level:** 1

**Type:** TRACE

**Impact:** Security

**WXE-11086: Retry-capable request removed from server %d**

**Cause:** The request was sent to an origin server that was unable to service the request due to the specified error code. Other servers exist that might be able to service this request, so the server is being marked as "serviced"

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11088: Following URL is now in cache:**

**Cause:** The complete response was successfully received and populated into the cache.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11089: Error while sending the entity body to the origin server**

**Cause:** Oracle Web Cache encountered a bad network connection or the origin server was down.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11091: Error while processing ESI for %.\*s%.\*s**

**Cause:** An error was encountered while ESI processing was done for the response. The page will not be cached.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11092: Object validated for %.\*s%.\*s**

**Cause:** The cached object was validated by the origin server and its expiration timestamps were updated accordingly.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

---

**WXE-11093: Content-Length value %d sent by origin server does not match number of bytes received, that is %d bytes for %.\*s%.\*s.**

**Cause:** This error can occur if the origin server sent an incorrect Content-Length value or if the connection was unexpectedly terminated.

**Action:** Check that the origin server is sending the correct Content-Length for the URL mentioned.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11095: Update fails because object is no longer cacheable.**

**Cause:** This request was no longer cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11096: Retry-capable request failed with error %s**

**Cause:** The request was sent to an origin server that was unable to service the request due to the specified error code. Other servers exist that might be able to service this request, so the request is being re-submitted to another server.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11097: Retry-capable request submitted to another server (%d of %d)**

**Cause:** The request was sent to an origin server that was unable to service the request due to the specified error code. Other servers exist that might be able to service this request, so the request is being re-submitted to another server.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11101: Unable to acquire write lock while inserting objects, cache insertion fails.**

**Cause:** Read/write lock acquire fails.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11104: Unknown state in voluntary garbage collection**

**Cause:** Unknown state in voluntary garbage collection.

---

**Action:** No action required.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11110: The maximum cache size is set too low. Oracle Web Cache failed to initialize.**

**Cause:** The maximum cache size is set too low. Some of the data structures could not be initialized because of insufficient memory. This error could also be caused by changes to the file internal.xml.

**Action:** Increase the maximum cache size. If this fails, revert to the original values in internal.xml. Contact Oracle Support for information about the internal.xml file.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11111: Based on maximum cache memory limit %s, a cache table is created.**

**Cause:** Normal trace behavior.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11118: Duplicate search key %.\*s found in Surrogate-Key response header is discarded.**

**Cause:** A duplicate search key was discovered in the Surrogate-Key response header.

**Action:** Remove the duplicate search key token from Surrogate-Key response header.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11119: The number of search keys changed.**

**Cause:** The number of search keys has changed for the same cached object.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11126: Unable to start voluntary garbage collection fiber.**

**Cause:** numHashBuckets\_x < MINIMUM\_CACHE\_HASHTABLE\_SIZE

**Action:** No action required.

**Level:** 8

**Type:** INTERNAL\_ERROR

---

**Impact:** Requests/Responses

**WXE-11128: A duplicate cache insertion is found. Cache insertion fails.**

**Cause:** Normal trace behavior.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11136: An error occurs during shutdown. The internal.xml file has been corrupted or moved.**

**Cause:** The internal.xml file was corrupted or moved during the shutdown operation.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Recover internal.xml by copying from internal.xml.bak.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11138: Maximum number of versions is reached.**

**Cause:** The number of versions in a cache entry has reached the maximum specified in the configuration.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11141: Traditional style basic key composed as %.\*s.**

**Cause:** Traditional style basic key composed.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11142: Traditional style cache key composed as %.\*s.**

**Cause:** Traditional style cache key composed.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11201: Oracle Web Cache is unable to resolve the IP address of %s. Check your DNS setup.**

**Cause:** Oracle Web Cache was unable to resolve the IP address of the origin server.

---

**Action:** Check whether the origin server is a valid host. You can alter origin server configuration in the Origin Servers page of Fusion Middleware Control.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11202: Origin server %s does not use IPv4.**

**Cause:** Oracle Web Cache only supports IP version 4. The IP address of the origin server could not be resolved because it used another version of IP.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Check that the origin server is a valid host and check the DNS setup. You can alter origin server configuration in the Origin Servers page of Fusion Middleware Control.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11203: Oracle Web Cache fails to connect to the origin server (id=%d).**

**Cause:** An origin server is not available.

**Action:** Check the status of the origin server and the network connection.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11205: Oracle Web Cache marks the origin server %s (id=%d) as down and removes all session information bound to it.**

**Cause:** The origin server was disabled or reached its failover threshold. Oracle Web Cache automatically distributes the request load over the remaining origin servers and polls the failed origin server for its current status.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11206: Oracle Web Cache is unable to start pingging the origin server. rc code=%d**

**Cause:** There was a potential memory allocation error.

**Action:** Check the configured memory usage in the Resource Limits page of Fusion Middleware Control. If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11207: Origin server %s (id=%d) is down; Oracle Web Cache starts polling for status.**

---

**Cause:** The origin server reached its failover threshold. Oracle Web Cache automatically distributes the request load over the remaining origin servers and polls the failed origin server for its current status.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11208: Cache cluster member %s (id=%d) is down; cache cluster members start polling for status. Ping threshold set at %d.**

**Cause:** The cache cluster member reached its failover threshold. Oracle Web Cache reassigns ownership of cache content, and polls the failed cache cluster member for its status.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11209: Origin server %s (id=%d) is back up; Oracle Web Cache stops polling and restores origin server.**

**Cause:** The ping URL to the origin server succeeded.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11210: Cache cluster member %s (id=%d) is up; cache cluster members stop polling and restore it.**

**Cause:** The ping URL to the cache cluster member succeeded.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11211: All origin servers for site %s are down. Last origin server was (id=%d).**

**Cause:** All origin servers configured for the site are down.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11212: Cache cluster member %s (id=%d) pinged successfully. %d successful pings so far.**

**Cause:** An origin server is not available.

**Action:** Check the status of the origin server and the network connection.



---

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11220: Session binding routing to origin server %s:%u (id=%d) for site %.\*s**

**Cause:** Normal trace behavior.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11221: The origin server request is queued for site %.\*s and site-to-server mapping %s.**

**Cause:** The origin server was busy.

**Action:** Increase the capacity of the origin servers used by the site-to-server mapping.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11222: The origin server request is dropped due to a full queue for site %.\*s and site-to-server mapping %s.**

**Cause:** The origin server request queue was full.

**Action:** Increase the capacity of the origin servers used by the site-to-server mapping.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11223: The origin server request is routed to peer cache cluster member %s (id=%d) for site %.\*s.**

**Cause:** The request did not support session binding, and the requested object was owned by the peer cache cluster member.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11224: Site %.\*s matches site-to-server mapping %s.**

**Cause:** Normal trace behavior.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

---

**WXE-11225: Oracle Web Cache cannot find any running origin servers to route the request for site %.\*s.**

**Cause:** All origin servers are down.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11226: The session binding request is to a busy origin server %s:%u (id=%d) for site %.\*s.**

**Cause:** The session binding request was to a server that was busy.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11227: Initial Request is routed to origin server %s using load balancing.**

**Cause:** Normal trace behavior.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11228: No defined origin server can serve this request for site %.\*s. The request is dropped.**

**Cause:** This request was for a non-ESI page or for an ESI template and no matching site-to-server mapping was found. Dynamic origin servers are not allowed for these requests.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11229: This ESI fragment request is forwarded to a dynamic origin server for ESI provider site %.\*s.**

**Cause:** The request was for an ESI fragment without a matching site-to-server mapping. If possible, the request is forwarded to a dynamic origin server.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11232: Session binding to origin server %s:%u (id=%d) for site %.\*s is given up because the origin server is down.**

**Cause:** Normal trace behavior.

---

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11233: Retry-capable request is routed to origin server %s using load balancing.**

**Cause:** Normal trace behavior.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11234: No defined origin server which does not exclude ESI fragments can serve this ESI fragment request for site %.\*s. The request is dropped.**

**Cause:** This request was for an ESI fragment and any site-to-server mapping which matched for host and URL excluded ESI fragments. Use of a dynamic origin server for this site could cause a loopback to this Oracle Web Cache. Therefore, a dynamic server will not be used for for this request.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11235: The request for site %.\*s is dropped because no origin server for site pattern %s is available.**

**Cause:** The origin server was not available.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11240: Origin server %s:%u (id=%d) has %d connections timed out or closed for other reasons.**

**Cause:** Normal trace behavior.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11250: ESI include fragment protocol does not match origin server protocol: Origin Server Protocol=%s URL=%s%.\*s%.\*s**

**Cause:** The protocol used in the src attribute does not match the protocol specified in the Sites page of Fusion Middleware Control. Oracle Web Cache used the protocol configured for the origin server in the Sites or Site-to-Server Mapping page.

---

**Action:** Correct the protocol in the template for the fragment.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11260: Session binding cookie name %.\*s with cookie value %.\*s exceeds limit %d.**

**Cause:** The cookie name and value exceeded the allowed length limit in Oracle Web Cache.

**Action:** Contact Oracle Support.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11261: Session binding query string parameter name %.\*s with value %.\*s exceeds limit %d.**

**Cause:** The query string parameter name and value exceeded the allowed length limit in Oracle Web Cache.

**Action:** Contact Oracle Support.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11265: Starting dynamic origin server lookup (dispatcher %d entry %d)**

**Cause:** Asynchronous dynamic origin server lookup started.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-11266: Completed dynamic origin server lookup (dispatcher %d entry %d)**

**Cause:** Asynchronous dynamic origin server lookup completed.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-11270: Cache cluster member %s (id=%d) sent a peer member a configuration error in the response.**

**Cause:** The response from a cache cluster member specified that its configuration did not match the configuration of a peer cache cluster member. This mismatch typically occurs because the configuration has not been propagated. You propagate configuration in the Cluster Operations page of Fusion Middleware Control.

**Action:** Contact Oracle Support.

---

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11272: A response error from a cache cluster member is not from a known peer cache cluster member.**

**Cause:** This error may be a logic error.

**Action:** Contact Oracle Support.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11290: DNS cache miss. Scheduling DNS task for host name %.\*s**

**Cause:** The entry for the host name was stale or missing in Oracle Web Cache's DNS cache. Oracle Web Cache scheduled a DNS task to get the host name.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11291: DNS lookup task scheduling fails for host %.\*s.**

**Cause:** Asynchronous task scheduling failed.

**Action:** Check the log of corresponding asynchronous task scheduling.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11292: DNS lookup succeeds for host %.\*s.**

**Cause:** The DNS cache miss and lookup succeeded.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11293: Oracle Web Cache fails to connect to dynamic origin server for ESI provider site and again performs a DNS lookup for host %.\*s.**

**Cause:** There was a possible stale DNS cache entry.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11294: Oracle Web Cache fails to connect to a dynamic origin server for ESI provider site with fresh DNS lookup result for host %.\*s.**

**Cause:** There was a potential system DNS error or invalid host.

---

**Action:** 1. Check whether the host is valid. 2. In a deployment environment, try to connect to this host and port. If the connection succeeds, then check the system/network DNS setup. 3. If problem persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11295: Oracle Web Cache failed in DNS lookup for host %.\*s.**

**Cause:** There was a potential system DNS error or invalid host.

**Action:** 1. Check whether the host is valid. 2. In a deployment environment, try to connect to this host and port. If the connection succeeds, then check the system/network DNS setup. 3. If problem persists, contact Oracle Support

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11296: Dynamic origin server name %.\*s is too long.**

**Cause:** Dynamic origin server name specified for an ESI fragment is longer than 255 characters.

**Action:** Check the host name that appears in src attribute of <esi:include> tag.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11297: Cached DNS look up result for host %.\*s is used.**

**Cause:** Cached DNS look up result was used to establish a connection to a dynamic origin server.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11298: The request is dropped because no routing relationship is configured for serving the content.**

**Cause:** No routing relationship is configured.

**Action:** Configure the routing relationships appropriately.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11299: The DMS ECID %.\*s detected in origin server response**

**Cause:** The ECID generated internally by Oracle Web Cache was identified as mapping to the DMS ECID discovered in the incoming X-Oracle-DMS-ECID" origin server response header.

**Action:** No action required.

---

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11300: The attempt to create an entry in the cache failed due to low memory.**

**Cause:** Memory low during insertion.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11301: Compose key failed for slave object in file %s line %s.**

**Cause:** Population\_ComposeKeyIfCacheable() return invalid values.

**Action:** No action required.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11302: No I/O vector is found at line %d file %s.**

**Cause:** tagInfo.nTotalNumberOfTags <= 0 && numDataBuffer > 0 for docBufList.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11303: Request method is not GET nor POST nor PUT; tunneling.**

**Cause:** The HTTP method in the request is not one of GET, POST or PUT. Oracle Web Cache will tunnel this request between the client and the origin server.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11304: Cache miss request.**

**Cause:** The cache did not have a object matching the request.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11306: Request is for a non-cacheable object, forwarding request to the backend.**

**Cause:** Normal trace behavior.

---

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11308: Request may not be cacheable according to caching rule.**

**Cause:** Normal trace behavior.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11311: Oracle Web Cache generates a HTTP 200 OK status code.**

**Cause:** The request completed successfully.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11312: invalid Oracle-ECID request header**

**Cause:** Oracle Web Cache was unable to parse the Oracle-ECID request header.

**Action:** Correct the syntax of the Oracle-ECID request header.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11313: The cache server reached the maximum number of allowed incoming connections. Listening is temporarily suspended on port %d.**

**Cause:** The cache server reached the maximum number of incoming connections specified in the Resource Limits page of Fusion Middleware Control.

**Action:** Try again later. If this message persists, increase the maximum incoming connections in the Resource Limits page of Fusion Middleware Control.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11314: Listening has resumed on port %d.**

**Cause:** The number of incoming connection count is under the threshold, enabling the cache server to accept new requests from browsers.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11315: Oracle Web Cache generates a HTTP 202 Accepted status code.**



---

**Cause:** The request was accepted.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11316: The request is for a End-User Performance Monitoring GIF file.**

**Cause:** Normal activity for End-User Performance Monitoring.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11317: Oracle Web Cache generates an HTTP 304 Not-Modified status code.**

**Cause:** Oracle Web Cache sent an HTTP 304 Not-Modified status code to the browser.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11321: Connection from browser cannot be established.**

**Cause:** The handshake with the browser failed.

**Action:** No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11322: Illegal value %d returned at frontend state machine.**

**Cause:** Invalid status for Serv\_HandleConn\_DoGetRequest.

**Action:** No action required.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11324: Function Serv\_HandleConn\_x is called with invalid state %d.**

**Cause:** Unknown state in Serv\_HandleConn\_x.

**Action:** No action required.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11325: Bad socket count**

**Cause:** The socket count was inconsistent.

---

**Action:** No action required.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11327: The request contains incorrect content.**

**Cause:** The object request could not be processed because the request contained incorrect or malformed information. Typical reasons are invalid, incomplete or malformed header information. This error can also occur when referencing ESI-only objects from non-ESI requests.

**Action:** Check the event log to determine which information is incorrect.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11328: Invalid socket**

**Cause:** Invalid socket was found.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11330: The request prefix %.\*s%.\*s matches an alias for configured site %.\*s.**

**Cause:** The alias for the site matched the Host request header.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11331: Request matches configured site:**

**Cause:** The Host request header matched the site name.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11332: Failed to rewrite URI from '%.\*s' to '%.\*s' according to rewrite rule '%.\*s'. The original URI will be used.**

**Cause:** URI rewrite failed. Oracle Web Cache will use the original URI in subsequent operations without rewriting.

**Action:** Modify URL rewrite rules.

**Level:** 1

**Type:** WARNING

---

**Impact:** Requests/Responses

**WXE-11333: URI is rewritten from %.\*s to %.\*s according to rewrite rule %.\*s.**

**Cause:** URI rewrite was successful.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11334: User-Agent request header %.\*s does not match any rule. Oracle Web Cache remapped User-Agent to the default value %.\*s.**

**Cause:** User-Agent request header did not match any rule.

**Action:** Manually modify user-agent rules in the webcache.xml file.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11335: User-Agent request header remapped from %.\*s to %.\*s according to mapping rule %s.**

**Cause:** User-Agent request header matched a rule.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11336: The request fails authorization check.**

**Cause:** The request was not processed due to insufficient privileges or authorization rejection.

**Action:** Make sure you are authorized to perform the administration, invalidation or monitoring operation.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11337: Administration service unavailable. Try again later.**

**Cause:** There were too many administration requests.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Ensure that only one user is the administrator user.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11338: URL is in the cache**

**Cause:** There was a matching entry in the cache for this request.

**Action:** No action required.

---

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11339: Oracle Web Cache determined the request might be cacheable based on existing cache policy.**

**Cause:** There was no matching cache entry for this request. However, based on existing cache policy, Oracle Web Cache determined that it is likely to be cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11340: A new entry in the cache is created.**

**Cause:** Oracle Web Cache created an entry in the cache for this request.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11342: Oracle Web Cache determined the request might not be cacheable based on existing cache policy.**

**Cause:** There was no matching cache entry for this request. However, based on existing cache policy, Oracle Web Cache determined that it is likely to be not cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11343: The requested site does not have a matching origin server mapping. A bad request error will be returned.**

**Cause:** There was no matching site-to-server mapping for this non-ESI-fragment request.

**Action:** No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11344: Returning a freshly cached object.**

**Cause:** The cached object will be returned because it is still fresh.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

---

**Impact:** Requests/Responses

**WXE-11345: The cached object is stale and this request will be served stale.**

**Cause:** The cached object is stale and Oracle Web Cache decided to serve the stale copy to the request.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11346: The cached object is stale and an origin server will be contacted for a fresh copy.**

**Cause:** Because the cached object is stale, Oracle Web Cache fetched a new version of the object to update the cache and satisfy this request with the new response.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11347: The cached object is garbage.**

**Cause:** The cached object is in garbage state, meaning that it could not be used to serve to the client.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11348: There is already another pending request for the same object being forwarded to the origin server for a fresh copy. This request will wait for the fresh copy.**

**Cause:** The cached object is in garbage state, and there is another request for the same object being forwarded to the origin server for a fresh copy to update the cache. Therefore, this request will wait until the fresh copy arrives.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11349: The request will be forwarded to the origin server to obtain a fresh copy of the object.**

**Cause:** The cached object was in garbage state, and there was no other request pending to update the cache. Oracle Web Cache will forward this request to the origin server for a fresh copy of the object to update the cache and satisfy this request with the new response.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

---

**Impact:** Requests/Responses

**WXE-11350: The request contains no site information in the URL or Host header. The configuration of the default site %s will be used.**

**Cause:** The request did not contain a Host header, nor did it have an absolute URL that contained a site name. Oracle Web Cache will use the default site in the configuration for this request.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11351: The complete site name is: %s**

**Cause:** The complete site name was resolved based on the configuration.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11352: There is no matching defined site or aliases in the configuration for this request.**

**Cause:** The configuration did not contain a matching site definition for the request. The site name will be taken from the request as is.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11354: Out of memory while processing the request. A service unavailable response is returned to the client. Client IP: %s**

**Cause:** Oracle Web Cache failed to obtain enough memory while processing the request.

**Action:** Adjust the maximum cache size in the Resource Limits page of Fusion Middleware Control. If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11355: Single request header length exceeds configured maximum. A forbidden error response is returned to the client. Client IP: %s**

**Cause:** One of the headers in the request exceeded the configured maximum.

**Action:** Adjust the maximum individual header size limit in the Security page of Fusion Middleware Control. If the problem persists, contact Oracle Support.

**Level:** 16

**Type:** ERROR

---

**Impact:** Requests/Responses

**WXE-11356: Total request header length exceeds configured maximum. A forbidden error response is returned to the client. Client IP: %s**

**Cause:** The total length of the headers in the request exceeded the configured maximum.

**Action:** Adjust the maximum combined header size limit in the Security page of Fusion Middleware Control. If the problem persists, contact Oracle Support.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11357: Failed to resolve the requested site name. A bad host error response is returned to the client.**

**Cause:** The request did not contain enough information about the site name.

**Action:** No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11358: Failed client certificate check. A forbidden error response is returned.**

**Cause:** The request was for a URL that requires a client certificate, and the certificate check failed for this request.

**Action:** No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11359: Host header missing in HTTP/1.1 request. A bad host error response is returned.**

**Cause:** The request was an HTTP/1.1 request, but is missing the required Host header.

**Action:** No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11360: Error processing the Transfer-Encoding header in the request. A bad request error response is returned.**

**Cause:** An error was encountered while processing the Transfer-Encoding header in the request.

**Action:** No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

---

**WXE-11361: Transfer-Encoding specified in the request is not supported. An HTTP not implemented error response is returned.**

**Cause:** Oracle Web Cache only supports chunked encoding. Other types transfer encoding are not supported.

**Action:** No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11362: Malformed request. A bad request error response is returned. Client IP: %s**

**Cause:** The request was malformed.

**Action:** No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11363: Out of memory while processing the request. The request is dropped.**

**Cause:** Oracle Web Cache failed to obtain enough memory while processing the request.

**Action:** Adjust the maximum cache size in the Resource Limits page of Fusion Middleware Control. If the problem persists, contact Oracle Support.

**Level:** 16

**Type:** ERROR

**Impact:** Memory

**WXE-11364: Network error response is returned.**

**Cause:** A network error was encountered while processing the request.

**Action:** Check other error messages related to this request.

**Level:** 16

**Type:** ERROR

**Impact:** Network

**WXE-11365: Server busy response is returned.**

**Cause:** The origin servers for the requested site were at full capacity, and the waiting queue was full.

**Action:** Increase the capacity of the origin servers.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11366: A client connection to listening port %d is dropped.**

**Cause:** A connection failure was encountered between Oracle Web Cache and the client, so the request could not be completed.

**Action:** No action required.



---

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11367: No matching origin server can be found for the requested site. A bad host error response is returned**

**Cause:** The requested site did not have any matching origin servers in the configuration.

**Action:** Modify the Sites page of Oracle Enterprise Manager or Site-to-Server Mapping page of Oracle Web Cache Manager.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11368: ESI exception error response is returned.**

**Cause:** An ESI exception was encountered while processing the request.

**Action:** Check other error messages related to this request.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11369: The request method is not supported. An HTTP not implemented error response is returned.**

**Cause:** The request specified an unsupported method.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11370: A chunk-encoded request entity body contains a chunk that exceeds %u bytes. A bad request error response is returned. Client IP: %s**

**Cause:** This chunk-encoded request contained a chunk that exceeded the DOCHEADERBUFFERSIZE setting in internal.xml

**Action:** Consider increasing DOCHEADERBUFFERSIZE.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11371: Malformed request. The chunk-encoded request entity body contains a line feed without a preceding carriage return. A bad request error response is returned. Client IP: %s**

**Cause:** The request is malformed.

**Action:** No action required.

**Level:** 16

**Type:** ERROR

---

**Impact:** Requests/Responses

**WXE-11372: Aborting origin server request**

**Cause:** A request sent to Oracle Web Cache was aborted. Because Oracle Web Cache was in the process of forwarding the request to an origin server, the request to the origin server was also aborted.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11373: This request %.\*s is not being enabled with End-User Performance Monitoring**

**Cause:** A single response from the origin server to Oracle Web Cache was not enabled for End-User Performance Monitoring because of a software limitation.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11376: The cached object is stale and this request will be served stale.**

**However origin server is already being contacted for the fresh copy by some other request**

**Cause:** The cached object is stale and Oracle Web Cache decided to serve the stale copy to the request. The origin server was already contacted for the fresh copy by some other request

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11377: Aborting receiving request entity body because origin server connection has been aborted**

**Cause:** An error occurred while sending the request entity body to an origin server. The origin server connection was aborted. Because of this, Oracle Web Cache is aborting the request received from the client.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11379: The request is using global site configuration.**

**Cause:** Oracle Web Cache used global site configuration for this request.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

---

**Impact:** Requests/Responses

**WXE-11381: A request is sent for a forbidden operation.**

**Cause:** The request was attempted to be performed on an IP address for which the operation is forbidden.

**Action:** Check the IP address to ensure the correct target platform was specified.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11382: The URL for the statistics monitoring request is not valid.**

**Cause:** The incorrect URL was used for the statistics monitoring request.

**Action:** Check the URL.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11383: The request has an internal error.**

**Cause:** The request was invalid.

**Action:** Contact Oracle Support.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11384: Changing incoming ECID from %.\*s to %.\*s**

**Cause:** The ECID discovered in the incoming Oracle-ECID request header has been changed to reflect the nested client request.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11385: The request fails because the service is unavailable.**

**Cause:** The request was not processed because the service at the specified IP address was not available.

**Action:** Make the sure service is available prior to initiating the invalidation request.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11386: The request fails because the portal service is unavailable.**

**Cause:** The request was not processed because the service at the specified IP address was not available.

**Action:** Make sure the service is available prior to initiating the invalidation request.

---

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11387: The request fails due to a gateway timeout.**

**Cause:** The request was not be processed due to a gateway timeout.

**Action:** Make sure the gateway is active and available for processing requests.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11388: The DMS ECID %.\*s overrides the legacy ECID %s.**

**Cause:** The ECID generated internally by Oracle Web Cache was identified as mapping to the DMS ECID discovered in the incoming ECID-Context" client request header.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11389: The request fails due to unsupported ESI operation.**

**Cause:** The request was not processed because no clients on the path of request can provide sufficient ESI processing capability.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Check the offending ESI tag for correctness or possible typographical errors.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11390: The ECID %.\*s overrides the temporary ECID %s.**

**Cause:** The ECID generated internally by Oracle Web Cache was overridden by the new ECID discovered in the incoming Oracle-ECID request header. From now on, events logged within the request/response context will be displayed with the new ECID instead of the temporary ECID.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11391: Detailed information about ECID %s is in the next line.**

**Cause:** Additional information about the request represented by the ECID was acquired and will be printed in the next line in the event log.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

---

**Impact:** Requests/Responses

**WXE-11392: The object is in the cache, but the inactivity timeout cookie must be updated.**

**Cause:** The cached object will be returned to the client, but the inactivity timeout cookie must first be updated.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11393: The central cache or provider cache has challenged the remote or subscriber cache for identity information.**

**Cause:** The central cache or provider cache requested content from its parent cache. Before receiving content, it must register itself as an Oracle Web Cache to establish a hierarchical relationship.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11394: The invalidation request is redundant.**

**Cause:** The invalidation request was not processed because the request was redundant with a previous requests. This error can occur in cache hierarchies.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11396: unknown internal error**

**Cause:** The error number was improperly set.

**Action:** Check which module is not setting the error number

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11397: request failed due to insufficient memory**

**Cause:** The object request failed due to insufficient memory necessary to process all of the objects.

**Action:** Increase the size of the pagefile.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11398: A client connection to listening port %d is dropped at the end of keep-alive session.**

---

**Cause:** A connection between Oracle Web Cache and the client was terminated, marking the end of the keep-alive session.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11399: The port number in the Host header %.\*s is replaced with the port number of the connection %.\*s.**

**Cause:** As a work around for an known Internet Explorer problem, the port number in the Host header was ignored and port number of the actual connection was used to determine the site instead.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11400: non-200 OK HTTP status code response code of %d**

**Cause:** The response received from the origin server contained a HTTP status code other than 200 OK.

**Action:** If this is not the intended response, then check the application code.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11403: begin cacheability decision for url:**

**Cause:** This marks the start of the cacheability decision for the specified URL. All messages logged between this message and the "final cacheability decision made" message are about the same request/response pair.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11404: Time %.\*s in the Last-Modified header is after the current time. The cache is using the current time instead.**

**Cause:** The Last-Modified response header received from the origin server contained a time that is in the future. The cache used the current time as the last-modified time instead.

**Action:** Check the application code that generates the Last-Modified response header, and make sure the machine where Oracle Web Cache is running has its clock in-sync with the clock of the application Web server.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

---

**WXE-11405: Request/Response matches no-cache rule with URL expression \"%s\".**

**Cause:** The request URL matched a non-cacheable caching rule.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11406: Request/Response matches no-cache rule with MIME type expression \"%s\".**

**Cause:** The request/response matched a non-cacheable caching rule.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11407: Request/Response matches no-cache rule with URL expression \"%s\" and MIME type expression \"%.\*s\".**

**Cause:** The request/response matched a non-cacheable caching rule.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11408: Request/Response matches no-cache catch-all rule.**

**Cause:** The request/response matched a non-cacheable caching rule.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11409: HTTP POST request body length %d exceeds maximum cacheable post body limit %d.**

**Cause:** The POST body length in the request exceeded the maximum cacheable limit for a POST body. Therefore, the corresponding response was not cached.

**Action:** If this response needs to be cached, contact Oracle Support.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11410: Response contains cookie \"%.\*s=.\*s\", which is not present in the request.**

**Cause:** The response received from the origin server contained a newly created cookie that was not present in the request. As a result, Oracle Web Cache considered the response to be non-cacheable.

**Action:** No action required.

---

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11411: Response contains cookie \"%.\*s=\"%.\*s\", which does not match the same cookie value \"%.\*s\" in the request.**

**Cause:** The response received from the origin server contained a new cookie that is different from the cookie value in the request. As a result, Oracle Web Cache considered the response to be non-cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11412: The Surrogate-Control header conflicts with an existing caching rule. Cached objects associated with the previous rule will be marked for removal from the cache.**

**Cause:** The Surrogate-Control header in the response contained control directives that were in conflict with an existing caching rule. This will cause Oracle Web Cache to mark all existing objects in the cache that were associated with the previous rule for removal.

**Action:** If this is not the intended behavior, then check the application logic, as well as the configured caching rule.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11413: The HTTP request method is not GET, or the URL contains query string parameters. The request is not cacheable.**

**Cause:** The request used an HTTP method that was neither GET nor POST. As a result, Oracle Web Cache considered it to be non-cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11414: Basic cache key is composed with sitename %.\*s, URI %.\*s, method %.\*s, post body %.\*s.**

**Cause:** The initial cache key was composed of the complete site name, the URL, the HTTP request method, and the POST body, if any.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11415: Final cache key is composed sitename %.\*s, URI %.\*s, method %.\*s, post body %.\*s, multiversion %.\*s, compressed %.\*s.**



---

**Cause:** The final cache key was composed of the initial cache key plus any cookies and headers as specified by caching rule.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11416: The response is considered not cacheable due to the lack of caching directives.**

**Cause:** The response did not contain any headers with caching directives and had no matching caching rule. As a result, Oracle Web Cache considered it to be non-cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11417: URL is not cacheable based on its HTTP headers.**

**Cause:** The response contained regular HTTP headers that indicated it was not cacheable. As a result, Oracle Web Cache considered it to be non-cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11418: The response contains a Surrogate-Control header with either a no-store control directive or a zero-value max-age control directive, indicating that the response is non-cacheable.**

**Cause:** The response contained a Surrogate-Control header with either a no-store control directive or a zero-value max-age control directive. As a result, Oracle Web Cache considered it to be non-cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11419: The Surrogate-Control header contains a nonzero max-age=%d+%d control directive, indicating that the response is cacheable.**

**Cause:** The response contained a Surrogate-Control header with a nonzero max-age directive. As a result, Oracle Web Cache considered it to be cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

---

**WXE-11420: The response contains Surrogate-Control header with a zero-value max-age control directive and ETag header, indicating that the response is cacheable with validation.**

**Cause:** The response contained Surrogate-Control header with a zero-value max-age control directive and ETag header. As a result, Oracle Web Cache considered it to be cacheable with validation.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11421: The response contains ETag and X-Oracle-Cache headers, indicating that the response is cacheable with validation.**

**Cause:** The response contained ETag and X-Oracle-Cache headers. As a result, Oracle Web Cache considered it to be cacheable with validation.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11422: The Surrogate-Control header contains the vary control directive, overriding configuration.**

**Cause:** The response Surrogate-Control header contained the vary control directive. It is used in place of the existing caching rule.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11423: Oracle Web Cache ran out of memory while creating caching rule according to the vary control directive of the Surrogate-Control header.**

**Cause:** There was not sufficient memory for Oracle Web Cache to process the vary control directive.

**Action:** Adjust the maximum cache size in the Resource Limits page of Fusion Middleware Control. If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11424: The request contains session %, which makes it non-cacheable based on the existing caching rule.**

**Cause:** The current caching rule for this URL specified that if a specific session exists in the request, then the request is treated as non-cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

---

**Impact:** Requests/Responses

**WXE-11425: The request does not contain session %s, which makes it non-cacheable based on the existing caching rule.**

**Cause:** The current caching rule for this URL specified that if a specific session did not exist in the request, the request is treated as non-cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11426: The request does not contain cookie %s, which makes it non-cacheable based on the existing caching rule.**

**Cause:** The current caching rule for this URL specified that if a specific cookie does not exist in the request, the request is treated as non-cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11427: The request does not contain HTTP request header %s, which makes it non-cacheable based on the existing caching rule.**

**Cause:** The current caching rule for this URL specified that if a specific header does not exist in the request, the request was treated as non-cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11428: The X-Oracle-Expires header contains TTL of %d seconds, indicating that the response is cacheable.**

**Cause:** The response contained an X-Oracle-Expires header with a nonzero TTL value. As a result, Oracle Web Cache considered it to be cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11429: The response contains ETag header and zero value TTL in X-Oracle-Expires header, indicating that the response is cacheable with validation.**

**Cause:** The response contained an X-Oracle-Expires header with a zero value TTL and an ETag header. As a result, Oracle Web Cache considered it to be cacheable with validation.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

---

**Impact:** Requests/Responses

**WXE-11430: The response contains zero value TTL in X-Oracle-Expires header with no ETag header, indicating that the response is non-cacheable.**

**Cause:** The response contained an X-Oracle-Expires header with a zero value TTL. As a result, Oracle Web Cache considered it to be not cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11431: In absence of any overriding headers in the response, the response is not cacheable based on the existing caching rule.**

**Cause:** The response was not cacheable because the matching caching rule indicates so, and there are no overriding response headers in the response to override the caching rule.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11432: The HTTP response headers indicate that the response is cacheable.**

**Cause:** The response contained the HTTP headers that indicate it is cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11433: An existing NCM entry states object is too large to be cacheable.**

**Cause:** The response body size was possibly greater than the maximum cacheable object size.

**Action:** If this is not the desired behavior, increase the maximum cached object size value in the Resource Limits page of Fusion Middleware Control.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11434: The ESI include or inline tag for this fragment contains reference TTL=%d+%d, making the fragment cacheable.**

**Cause:** The ESI include or inline tag for the fragment contained a nonzero reference TTL. As a result, Oracle Web Cache considered the fragment cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

---

**WXE-11442: Oracle Web Cache could not process the response for ESI because the Content-Type is not valid for ESI processing.**

**Cause:** The Surrogate-Control response header contained a content token with values indicating that ESI parsing should be done, but the Content-Type header value was not text or HTML.

**Action:** If the content needs to be processed for ESI, the application code must modify the Content-Type to be text or HTML.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11443: The request does not contain header %.\*s, which makes it non-cacheable based on the vary control directive in the Surrogate-Control response header.**

**Cause:** The request was missing a required header to be cacheable based on the vary control directive in the Surrogate-Control response header.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11444: The request does not contain cookie %.\*s, which makes it non-cacheable based on the vary control directive in the Surrogate-Control response header.**

**Cause:** The request was missing a required cookie to be cacheable based on the vary control directive in the Surrogate-Control response header.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11445: Following URL will not be cached:**

**Cause:** The final cacheability decision for this response is not cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11446: URL which will be cached is:**

**Cause:** The final cacheability decision for this response is cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11447: Request/Response matches a dynamic caching rule.**

---

**Cause:** The request/response matched a dynamic caching rule.

**Action:** No action required. caching rules.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11448: Request/Response does not match any caching rule.**

**Cause:** The request/response did not match any configured caching rule.

**Action:** If this is not the intended behavior, then check the configured caching rules.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11449: The response is too large to be cached.**

**Cause:** The response size is larger than the configured maximum size of a single cached object.

**Action:** Check the configured Maximum Size of Single Cached Object in the Resource Limits page of Fusion Middleware Control. If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11450: Object is cached because it does not exceed allowed size for an object.**

**Cause:** The object was cacheable because its response was within the configured maximum object size. Previously, the object was uncacheable because it exceeded the limit.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11451: Update fails because object is no longer cacheable.**

**Cause:** This request was no longer cacheable.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11452: Update fails; Oracle Web Cache fetches response as a cache miss.**

**Cause:** An update of the object failed. Oracle Web Cache processes the request as a cache miss.

**Action:** No action required.

---

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11453: A new cache policy is created based on the Surrogate-Control header.**

**Cause:** The caching properties specified in the Surrogate-Control header conflicts with the existing cache policy, therefore Oracle Web Cache created a new policy to be used for future requests.

**Action:** If this is not the intended behavior, then check the application logic, as well as the configured caching rule.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11454: Current compression is on, conflicting with the previous setting.**

**Cause:** The response contains a compression setting either explicitly through the Surrogate-Control header or implicitly through the absence of it that was in conflict with an existing compression setting. This will cause Oracle Web Cache to mark all existing objects in the cache that were associated with the previous setting for removal.

**Action:** If this is not the intended behavior, then check the application logic, as well as the configured caching rule.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11455: The response indicates security validation is required, conflicting with the previous setting.**

**Cause:** The response contains a security validation setting either explicitly through the Surrogate-Control: secure-view token or implicitly through the absence of it that was in conflict with an existing security validation setting. This will cause Oracle Web Cache to mark all existing objects in the cache that were associated with the previous setting for removal.

**Action:** If this is not the intended behavior, then check the application logic, as well as the configured caching rule.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11456: The response indicates version validation is required, conflicting with the previous setting.**

**Cause:** The response contains a version validation setting either explicitly through the Surrogate-Control: version token or implicitly through the absence of it that was in conflict with an existing security validation setting. This will cause Oracle Web Cache to mark all existing objects in the cache that were associated with the previous setting for removal.

**Action:** If this is not the intended behavior, then check the application logic, as well as the configured caching rule.

---

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11457: The response contains a Surrogate-Control: authentication token that is not supported by Oracle Web Cache.**

**Cause:** The Surrogate-Control: authentication token value of response header indicates an authentication mechanism that is not supported by Oracle Web Cache for caching such documents. The response will not be cached.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. If this is not the intended behavior, then check the application logic.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11458: Following URL that requires Oracle Single Sign-On authentication is being inserted in the cache:**

**Cause:** Caching is enabled for documents that require Oracle Single Sign-On authentication but have no other authorization requirement.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11459: URL is not cacheable because the request contains an Authorization header.**

**Cause:** The request contained a HTTP header that indicated the response would be non-cacheable. As a result, Oracle Web Cache considered it to be non-cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11460: URL is not cacheable because the request contains a Proxy-Authorization header.**

**Cause:** The request contained a HTTP header that indicated the response would be non-cacheable. As a result, Oracle Web Cache considered it to be non-cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11461: URL is not cacheable because the request contains a Cookie header.**

**Cause:** The request contained a HTTP header that indicated the response would be non-cacheable. As a result, Oracle Web Cache considered it to be non-cacheable.

**Action:** No action required.



---

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11462: URL is not cacheable because the response contains a Set-Cookie header.**

**Cause:** The response contained regular HTTP headers that indicated it was not cacheable. As a result, Oracle Web Cache considered it to be non-cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11463: URL is not cacheable because the response contains a Cache-Control: no-store header.**

**Cause:** The response contained regular HTTP headers that indicated it was not cacheable. As a result, Oracle Web Cache considered it to be non-cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11464: URL is not cacheable because the response contains a Cache-Control: no-cache header.**

**Cause:** The response contained regular HTTP headers that indicated it was not cacheable. As a result, Oracle Web Cache considered it to be non-cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11465: URL is not cacheable because the response contains a Pragma: no-cache header.**

**Cause:** The response contained regular HTTP headers that indicated it was not cacheable. As a result, Oracle Web Cache considered it to be non-cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11466: URL is not cacheable because the response contains a Warning header.**

**Cause:** The response contained regular HTTP headers that indicated it was not cacheable. As a result, Oracle Web Cache considered it to be non-cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

---

**Impact:** Requests/Responses

**WXE-11467: URL is not cacheable because the Expires header indicates that it has expired.**

**Cause:** The response contained regular HTTP headers that indicated it was not cacheable. As a result, Oracle Web Cache considered it to be non-cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11468: URL is not cacheable because the response contains no expiration information.**

**Cause:** The response contained no expiration headers. As a result, Oracle Web Cache considered it to be non-cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11469: URL is cacheable because the response contains an ETag header.**

**Cause:** The response contained HTTP headers that indicate it is cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11470: URL is cacheable because the response contains an Expires header, indicating it expires in the future.**

**Cause:** The response contained HTTP headers that indicate it is cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11471: URL is cacheable because the response contains a Cache-Control header with a positive max-age directive.**

**Cause:** The response contained HTTP headers that indicate it is cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11472: The response contains a Surrogate-Control header with a restore-POST directive, indicating that the response is not cacheable.**

---

**Cause:** The response contained instructions to cache the request POST data content. As a result, Oracle Web Cache considered the response to be non cacheable. If this is a 302 redirect to a POST response, Oracle Web Cache will save the the request POST content in the cache to be used upon a future restore POST request.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11473: Cache key output truncated due to excessive post body size**

**Cause:** The cache key message (11414, 11415) could not display the entire cache key because the post body message size exceeded the threshold specified in the configuration file.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11474: Current compression is off, conflicting with the previous setting.**

**Cause:** The response contains a compression setting either explicitly through the Surrogate-Control header or implicitly through the absence of it that was in conflict with an existing compression setting. This will cause Oracle Web Cache to mark all existing objects in the cache that were associated with the previous setting for removal.

**Action:** If this is not the intended behavior, then check the application logic, as well as the configured caching rule.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11475: Current SSO authentication is on, conflicting with the previous setting.**

**Cause:** The response contains an authentication setting either explicitly through the Surrogate-Control header or implicitly through the absence of it that was in conflict with an existing authentication setting. This will cause Oracle Web Cache to mark all existing objects in the cache that were associated with the previous setting for removal.

**Action:** If this is not the intended behavior, then check the application logic.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11476: Current SSO authentication is off, conflicting with the previous setting.**

**Cause:** The response contains an authentication setting either explicitly through the Surrogate-Control header or implicitly through the absence of it that was in conflict with an existing authentication setting. This will cause Oracle Web Cache to mark all existing objects in the cache that were associated with the previous setting for removal.

---

**Action:** If this is not the intended behavior, then check the application logic.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11477: The response contains a Surrogate-Control: authentication token but SSO authentication is not enabled.**

**Cause:** The Surrogate-Control: authentication token is present but SSO authentication is not enabled for caching. The response will not be cached.

**Action:** Turn on SSO authentication by editing webcache.xml: find the SECURITY element under the GENERAL element. Assign a positive value to the SSO\_COOKIE\_CACHE\_TIME attribute.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11478: The response indicates security validation is not required, conflicting with the previous setting.**

**Cause:** The response contains a security validation setting either explicitly through the Surrogate-Control: secure-view token or implicitly through the absence of it that was in conflict with an existing security validation setting. This will cause Oracle Web Cache to mark all existing objects in the cache that were associated with the previous setting for removal.

**Action:** If this is not the intended behavior, then check the application logic, as well as the configured caching rule.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11479: The response indicates version validation is not required, conflicting with the previous setting.**

**Cause:** The response contains a version validation setting either explicitly through the Surrogate-Control: version token or implicitly through the absence of it that was in conflict with an existing security validation setting. This will cause Oracle Web Cache to mark all existing objects in the cache that were associated with the previous setting for removal.

**Action:** If this is not the intended behavior, then check the application logic, as well as the configured caching rule.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11480: Post body masked due to security**

**Cause:** The cache key message (11414, 11415) will not display the entire cache key because the post body was masked.

**Action:** No action required.

**Level:** 1

---

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11481: Request/Response matches caching rule with URL expression \"%s\".**

**Cause:** The request/response matched a cacheable caching rule.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11482: Request/Response matches caching rule with MIME type expression \"%.\*s\".**

**Cause:** The request/response matched a cacheable caching rule.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11483: Request/Response matches caching rule with URL expression \"%s\" and MIME type expression \"%.\*s\".**

**Cause:** The request/response matched a cacheable caching rule.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11484: Request/Response matches catch-all caching rule.**

**Cause:** The request/response matched a cacheable caching rule.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11485: Request/Response matches disabled caching rule with URL expression \"%s\".**

**Cause:** The request/response matched a disabled caching rule; thus, the rule is ignored.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11486: Request/Response matches disabled caching rule with MIME type expression \"%.\*s\".**

**Cause:** The request/response matched a disabled caching rule; thus, the rule is ignored.

---

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11487: Request/Response matches disabled caching rule with URL expression \"%s\" and MIME type expression \"%.\*s\".**

**Cause:** The request/response matched a disabled caching rule; thus, the rule is ignored.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11488: Request/Response matches disabled catch-all caching rule.**

**Cause:** The request/response matched a disabled caching rule; thus, the rule is ignored.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11489: HTTP response-header parsing error on Surrogate-Control token: %.\*s. Full header line is: %.\*s.**

**Cause:** An HTTP Surrogate-Control response header from the origin server contained an individual header value that was malformed or unexpected. The Surrogate-Control tokens up to the malformed one were processed. The malformed token and any tokens which follow it were ignored.

**Action:** If the behavior is still as expected, no action is required. If the behavior is not as expected, check the application code that generates the Surrogate-Control header.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11500: StatisticsTimerInterval configuration parameter should be between 10,000 and 1,000,000 microseconds, and should be a factor of 1,000,000**

**Cause:** Illegal configuration parameter for statistics timer interval.

**Action:** This error usually occurs as a result of wrong configuration. Contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11501: While getting detailed memory statistics, pointer swapped while filling HTML**

---

**Cause:** While retrieving detailed memory statistics, the timer pointer swapped to a new index as it was filling the HTML template.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-11502: Unable to create or open file %s for write. Cache contents not written.**

**Cause:** The cache server was unable to open the file specified. Either the file already exists and the Oracle Web Cache user does not have write permission on the file or the Oracle Web Cache user does not have write permission to the directory.

**Action:** Check permissions on the file and the directory and correct them to allow Oracle Web Cache to create the file or write to it.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11503: Abnormal statistics value of %s was detected. Value 0 was recorded.**

**Cause:** Internal error. The statistics value that was returned was an abnormal (negative) value.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11504: Client IP checking for the statistics message fails. Access denied.**

**Cause:** Oracle Web Cache allows statistics requests to be sent from configured trusted hosts or trusted subnets. The current statistics request message was not sent from an IP address that belongs to a trusted host or subnet.

**Action:** Add the IP address for the computer as trusted host in the Security page of Fusion Middleware Control.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11505: The number of statistics monitoring requests exceeds queue limit.**

**Cause:** The number of statistics monitoring requests exceeded the request queue limit.

**Action:** Try the request at a later time.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11506: Invalid IP address in statistics request**

---

**Cause:** The request to the statistics port is from invalid IP address.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11600: Illegal value set for HeuristicsValidityFunc**

**Cause:** The heuristics validity function ID was corrupted. This error is the result of internal configuration errors.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. If the problem persists, contact Oracle Support.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11601: Illegal value set for HeuristicsPropensityFunc**

**Cause:** The heuristics propensity function ID was corrupted. This error is the result of internal configuration errors.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. If the problem persists, contact Oracle Support.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11602: Illegal value set for HeuristicsThresholdFunc**

**Cause:** The heuristics threshold function ID was corrupted.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. This error usually occurs as a result of internal configuration errors. If the problem persists, contact Oracle Support.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11604: Illegal value set for POPULARITYSCALE.**

**Cause:** The popularity heuristic parameter is not valid.

**Action:** Contact Oracle Support.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11605: Illegal value set for THRESHOLDSCALE.**

**Cause:** The threshold heuristic parameter is not valid.

**Action:** Contact Oracle Support.

**Level:** 8



---

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11606: Illegal value set for THRESHOLDBASE.**

**Cause:** The threshold base heuristic parameter is not valid.

**Action:** Contact Oracle Support.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11608: Illegal value set for ECATELMFACTOR.**

**Cause:** The Cate LMFactor heuristic parameter is not valid.

**Action:** Contact Oracle Support.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11610: Illegal value set for OWNERSHIPREFERENCE.**

**Cause:** The ownership preference heuristic parameter is not valid.

**Action:** Contact Oracle Support.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11700: Client IP checking for the invalidation message fails. Access denied.**

**Cause:** Oracle Web Cache allows invalidation to be sent from configured IP groups. The current invalidation message was not sent from an IP address that belongs to the configured groups.

**Action:** Configure trusted hosts in the Security page of Fusion Middleware Control.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11701: Authentication failed. Invalid username or password.**

**Cause:** The invalidation message contained an incorrect username or password.

**Action:** Resend the invalidation message with the correct invalidator user name and password. You can change the password in the Security page of Fusion Middleware Control.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11702: The invalidation request contains an empty request body.**

**Cause:** The invalidation request contained an empty request body.

---

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Resend the invalidation request with a request body.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11703: Invalidation request specifies a wrong URL.**

**Cause:** The invalidation message carried a wrong request URL.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11704: Invalidation message contains XML parsing errors.**

**Cause:** The invalidation message contained invalid XML.

**Action:** Correct the XML errors in the invalidation message.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11705: Invalid validity level '%s' is requested.**

**Cause:** The invalidation message specified an invalid validity level. The correct range of level is between 0 and 9.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Correct the message to use a validity level between 0 to 9.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11706: %d object(s) matching prefix '%s' are invalidated.**

**Cause:** Invalidation of objects was successful.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-11707: Object with URL '%s' is successfully invalidated.**

**Cause:** Invalidation was successful.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-11708: Object with URL '%s' is not cacheable. Invalidation is not done.**

---

**Cause:** The URL was not a cacheable object. Invalidation is not performed for non-cacheable objects.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-11710: Object with URL '%s' not in the cache. Invalidation is not performed.**

**Cause:** The object was not in the cache. Invalidation is not performed for non-cacheable objects.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-11711: Oracle Web Cache cannot compose key pattern for requested URL '%s'.**

**Cause:** Oracle Web Cache could not compose a key pattern for requested URL expression.

**Action:** Correct the URL expression in the invalidation message.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11712: Invalidation message contains unrecognized cookies.**

**Cause:** The invalidation message contained nonexistent cookies.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Correct the cookie name specified in the invalidation message.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11713: Invalid regular expression found in invalidation message. %s**

**Cause:** The invalidation message contained an invalid regular expression that could not be compiled.

**Action:** Correct the regular expression in the invalidation message.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11715: Regular expression matching error. Error number: %d**

**Cause:** The regular expression in the invalidation message was invalid. Oracle Web Cache could not perform regular expression matching successfully.

**Action:** Check regex man page with the error number for syntax error description.

**Level:** 16

---

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11716: Invalidation XML message cannot be parsed.**

**Cause:** Invalidation XML message could not be parsed.

**Action:** No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11717: Invalidation XML error found in invalidation message.**

**Cause:** Oracle Web Cache received an invalidation message in an old version. It is unable to obtain all information about the URL node.

**Action:** Correct the invalidation message or use an invalidation version of either "WCS-1.1" or "WCS-1.0".

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11718: Cannot allocate memory for KeyParam structure.**

**Cause:** Oracle Web Cache could not allocate memory for KeyParam structure.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Check memory configuration. Restart Oracle Web Cache if necessary.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11719: Cannot allocate memory for Invalidate\_AttributeT structure.**

**Cause:** Oracle Web Cache could not allocate memory for Invalidate\_AttributeT structure.

**Action:** Check memory configuration. Restart Oracle Web Cache if necessary.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11720: Cannot allocate memory for or sizeof '%s'.**

**Cause:** Oracle Web Cache could not allocate memory.

**Action:** Check memory configuration. Restart Oracle Web Cache if necessary.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11721: Cannot read value for XML element/attribute: '%s'.**

**Cause:** Oracle Web Cache was unable to obtain all information about the specified XML element or attribute.

**Action:** Correct the XML in the invalidation message.

---

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11722: Invalidation message specifies unknown version: '%s'.**

**Cause:** The invalidation message specified an unknown version.

**Action:** Correct the invalidation message to use version "WCS-1.1 or "WCS-1.0".

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11723: Value of XML string '%s' too long. Actual length: %d, max length allowed: %d.**

**Cause:** The XML string in the invalidation message exceeded the allowed length limit.

**Action:** Correct the XML in the invalidation message.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11724: URL path prefix does not end with '/': '%s'.**

**Cause:** The URL path prefix did not end with '/' in the invalidation message.

**Action:** Correct the syntax of the URL path prefix in the invalidation message.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11725: Cannot create XML element/attribute: '%s'.**

**Cause:** Oracle Web Cache could not create the XML element or attribute.

**Action:** Check the maximum cache size in the Resource Limits page of Fusion Middleware Control. Restart Oracle Web Cache if necessary.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11726: Cannot set XML attribute '%s' for element '%s'.**

**Cause:** Oracle Web Cache could not set the XML attribute value.

**Action:** Check the maximum cache size in the Resource Limits page of Fusion Middleware Control. Restart Oracle Web Cache if necessary.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11727: Unexpected/unsupported argument '%s' in function '%s'.**

---

**Cause:** The invalidation message specified an unsupported name and value pair for <SYSTEMINFO ... />

**Action:** See Chapter "Sending Invalidation Requests" in the Oracle Web Cache Administrator's Guide for the possible values allowed for <SYSTEMINFO ... />.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11728: Cluster error: Peer cache '%d' returns bad response.**

**Cause:** The invalidation response from a peer cache was not parsed.

**Action:** Check the network connection between current cache and its peer.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11729: Invalidation message contains conflicting HOST values: '%s' and '%s'.**

**Cause:** The invalidation message contained conflicting HOST values in the URIPREFIX and the HOST attributes.

**Action:** Correct the host information in the invalidation message.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11730: Invalidation message from provider cache with IP %s port %d is dropped.**

**Cause:** The invalidation message propagated from the specified provider cache is either outdated or invalid. Invalidation is discarded.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11731: Normal request is from an unknown Oracle Web Cache: IP %s port %s.**

**Cause:** The invalidation message was propagated from an unknown cache. Invalidation is discarded.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11732: Invalidation contains host name '%s' which does not match the IP '%s' from which invalidation comes.**

**Cause:** The invalidation message propagated from a cache provided no host name or the host name in the URIPREFIX or HOST attribute was not allowed for that cache. Invalidation is discarded.

---

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Correct the host information in the invalidation message.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11733: Invalidation object is ignored due to lack of host information.**

**Cause:** Invalidation propagated from a cache does not specify a host name in the URIPREFIX or HOST attribute of the message.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Correct the host information in the invalidation message.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-11734: Invalidation sent to subscriber cache with IP %s port %d has returned with response code: '%s'.**

**Cause:** The provider cache response was received.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-11735: Subscriber cache with IP %s port %d is removed due to an exceeded failure count. Total subscriber(s): %d.**

**Cause:** Subscriber cache was removed from the internal subscriber list because the invalidation propagated to it has failed too many times.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-11736: Failed to start fiber to send invalidation to subscriber cache with IP %s port %d.**

**Cause:** Oracle Web Cache failed to send invalidation. to subscriber cache.

**Action:** Check the configuration file. Restart Oracle Web Cache if necessary.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11737: Invalidation message may be lost from provider cache with IP %s port %d.**

**Cause:** The subscriber cache missed an invalidation message from the provider cache. All objects are invalidated.

**Action:** No action required.

---

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-11738: Provider cache fails in propagating invalidation message to subscriber cache.**

**Cause:** The provider cache failed in propagating the invalidation message to subscriber cache.

**Action:** Check the configuration file. Restart Oracle Web Cache if necessary.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11740: Invalidation message contains too many cookies, headers, or attributes. Maximum allowed is '%d'.**

**Cause:** Invalidation message contained too many cookies, headers, or attributes. Invalidation was not performed.

**Action:** Rephrase the invalidation message.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11748: Invalidation with INFO '%s' has returned with status '%s'; number of objects invalidated: '%d'.**

**Cause:** The result of the invalidation was successful. INFO is the comment specified in the INFO element of the invalidation request. The status can be SUCCESS for successful invalidations, URI NOT CACHEABLE for objects that are not cacheable, or URI NOT FOUND for objects not found in the cache.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-11750: Invalid syntax for the value of QUERYSTRING\_PARAMETER in invalidation message: '%s'.**

**Cause:** The invalidation message contained invalid syntax in the QUERYSTRING\_PARAMETER value.

**Action:** Correct the error in invalidation message.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11752: Cannot decode %s with value '%s', therefore decoding is not done.**

**Cause:** Cannot decode XML value specified. The original value is used.

**Action:** No action required.

**Level:** 1



---

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11754: Cannot allocate new XML context for invalidation.**

**Cause:** Oracle Web Cache could not create XML context for invalidation.

**Action:** Check memory resources on the machine. Reinstall Oracle Web Cache if necessary.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11755: Default URL size is too small for cache key.**

**Cause:** Default URL size was too small for cache key.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11757: Unsupported OTHER element specified in invalidation message:**

**name='%s', type='%s', value='%s'.**

**Cause:** Unsupported OTHER element was specified in the invalidation message.

**Action:** See Chapter "Sending Invalidation Requests" in the Oracle Web Cache Administrator's Guide for all supported OTHER elements.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11761: Site %.\*s has no matching site definition and thus cannot be verified.**

**Cause:** Response header invalidation failed because the site specified in the original request does not have a corresponding site definition with which to verify the invalidation response header.

**Action:** Create an appropriate site definition.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11762: Syntactically incorrect URI, '%.\*s', specified in invalidation response header.**

**Cause:** Response header invalidation failed because the URI in the invalidation response header was not syntactically valid.

**Action:** Change application to only append invalidation response headers with valid URIs.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

---

**WXE-11763: URI, '%.\*s', specified in invalidation response header does not match incoming request's site definition.**

**Cause:** Response header invalidation failed because the URI in the invalidation response header did not match the site specified in the original request.

**Action:** Change application to only append invalidation response headers whose site matches that of the incoming request.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11764: Unable to open connection to invalidation port of peer cache member \"%s\" because its state is not Ready.**

**Cause:** The invalidation port of the peer cache member is not ready to accept connections.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11800: CGI communication error.**

**Cause:** Network I/O error while communicating with CGI application.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11802: Cannot open Service Manager: %s**

**Cause:** The admin server was unable open the Windows Service Manager.

**Action:** If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11803: Cannot open Windows Service %s: %s**

**Cause:** The admin server was unable to open the specified service.

**Action:** If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11804: Cannot obtain the system status for Windows service %s: %s**

**Cause:** The admin server was unable to retrieve the status for the specified service.

**Action:** If the problem persists, contact Oracle Support.

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11805: Cannot control service %s: %s**

**Cause:** The admin server was unable to start or stop the specified Windows service.

**Action:** If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11806: Cannot stop service %s**

**Cause:** The admin server failed to stop the specified service.

**Action:** If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11807: Windows service, %s, stopped**

**Cause:** The admin server has successfully stopped the specified service.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-11809: The admin server could not start the cache server, running in admin-only mode: %s**

**Cause:** The admin server was unable to start the cache server.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Review the error log file or use the Event Viewer to help determine the cause of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11810: Cannot start Auto-Restart. %s does not exist**

**Cause:** Unable to find the specified Auto-Restart executable.

**Action:** Restore the Auto-Restart executable, webcachemon, to its proper location, which is the Oracle Web Cache bin directory.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11811: Unable to fork a new process for starting Auto-Restart.**

---

**Cause:** Oracle Web Cache was unable to fork a new process.

**Action:** This is probably a temporary system resource issue. If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11812: Auto-Restart did not start. An error code was returned.**

**Cause:** The Auto-Restart process failed to start.

**Action:** There may be associated error messages from the Auto-Restart process indicating why it was unable to start. If there are no other error messages, it may be a system resource problem. For example, the exec() call may have failed. If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11813: Cannot start service %s**

**Cause:** The admin server failed to start the specified service.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11814: Logging info: %s**

**Cause:** An error is logged.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Refer to the logged error details and take the appropriate action.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11815: The admin server process is unable to determine the OPMN auto-restart setting. Error reading or parsing %s**

**Cause:** An error occurred while the admin server process was attempting to obtain the restart setting for Oracle Web Cache in the OPMN XML configuration file, opmn.xml.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11816: Error while changing the OPMN auto-restart setting for Oracle Web Cache. Command: %s. Return code: %d. Command output: %s**

---

**Cause:** An error occurred while trying to execute the command specified. Oracle Web Cache uses this command to change the restart setting in the OPMN XML configuration file, opmn.xml.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Execute the command manually.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11817: Unable to allocate or access a shared memory segment of size %u bytes. %s(): %s**

**Cause:** The specified operating-system level function, which creates or accesses a shared memory segment of the size specified in the error message, has failed for the specified reason.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. This error usually occurs as a result of insufficient system resources. Refer to the included operating system level error message for further information.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11818: Login attempt fails to admin server process.**

**Cause:** An incorrect username or password was entered while attempting to access the admin server process. If this error occurs frequently, a malicious user might be attempting to crack the password

**Action:** Try the username and password again.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11819: Unable to open temporary file %s**

**Cause:** The admin server was unable to create a temporary file used during the processing of new configuration changes.

**Action:** No action required

**Level:** 1

**Type:** WARNING

**Impact:** Files

**WXE-11901: SSL context creation failed, NZE-%d**

**Cause:** SSL library failed to create a context.

**Action:** See the "Network Security Messages (NZE)" chapter of the Oracle Database Error Messages for information about NZE errors.

**Level:** 1

**Type:** ERROR

**Impact:** Security

---

**WXE-11902: SSL configuration fails, NZE-%d**

**Cause:** SSL library configuration failed.

**Action:** See the "Network Security Messages (NZE)" chapter of the Oracle Database Error Messages for information about NZE errors.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WXE-11903: SSL set credential fails, NZE-%d**

**Cause:** SSL library failed to set credentials.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. See the "Network Security Messages (NZE)" chapter of the Oracle Database Error Messages for information about NZE errors.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WXE-11904: SSL handshake fails NZE-%d**

**Cause:** SSL handshake error occurred.

**Action:** See the "Network Security Messages (NZE)" chapter of the Oracle Database Error Messages for information about NZE errors.

**Level:** 16

**Type:** ERROR

**Impact:** Security

**WXE-11905: SSL additional information: %.\*s**

**Cause:** This message provides additional diagnostic information about the preceding SSL error.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WXE-11907: The server cannot allocate memory while in %s.**

**Cause:** The system has run out of memory.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Restart the system and Oracle Web Cache.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11908: SSL set peerid fails, NZE-%d**

**Cause:** SSL library failed to create SSL Session

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. See the "Network Security Messages (NZE)" chapter of the Oracle Database Error Messages for information about NZE errors.

---

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WXE-11909: getpeername fails during SSL handshake, system error %d**

**Cause:** Could not determine peer IP Address.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g.  
Contact Oracle Support.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WXE-11910: failed to normalize Wallet Resource Locator (WRL) %s**

**Cause:** WRL could not be parsed.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g.  
Confirm that the WRL is in the correct format.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WXE-11912: unknown state in SSL session garbage collector**

**Cause:** There is an unknown code bug.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g.  
Contact Oracle Support.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Security

**WXE-11913: SSL set hardware acceleration fails, NZE-%d.**

**Cause:** The SSL library failed to initialize hardware SSL acceleration.

**Action:** See the "Network Security Messages (NZE)" chapter of the Oracle  
Database Error Messages for information about NZE errors.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WXE-11914: SSL set thread usage fails, NZE-%d.**

**Cause:** The SSL library failed to set threading model.

**Action:** See the "Network Security Messages (NZE)" chapter of the Oracle  
Database Error Messages for information about NZE errors.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WXE-11915: The SSL engine fails to initialize, NZE-%d.**

---

**Cause:** The SSL library engine failed to initialize.

**Action:** See the "Network Security Messages (NZE)" chapter of the Oracle Database Error Messages for information about NZE errors.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WXE-11916: Oracle cryptographic toolkit context initialization fails, NZE-%d.**

**Cause:** The SSL library toolkit context failed to initialize.

**Action:** See the "Network Security Messages (NZE)" chapter of the Oracle Database Error Messages for information about NZE errors.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WXE-11917: SSL wallet %s file %s does not exist.**

**Cause:** The wallet was not found in the wallet directory.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Check for wallet file ewallet.p12 or ewallet.der in the wallet directory.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WXE-11918: The SSL Wallet %s file %s is not readable.**

**Cause:** The wallet was not readable by Oracle Web Cache.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Check the file system permissions on this file.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WXE-11919: The SSL wallet auto-login file %s does not exist. Wallet does not appear to be auto-login wallet.**

**Cause:** The wallet auto-login file cwallet.sso was not found.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Check for wallet file cwallet.sso in wallet directory.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WXE-11920: The SSL wallet auto-login file %s is not readable. Wallet does not appear to be auto-login wallet.**

**Cause:** The wallet auto-login file cwallet.sso was not readable by Oracle Web Cache.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Check the file system permissions on this file.



---

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WXE-11921: The origin server wallet did not open. Operating without wallet for backend. Only Diffie-Hellman anonymous connections supported to origin servers.**

**Cause:** Origin server wallet did not open or was not specified.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Without an origin server wallet, only Diffie-Hellman SSL Connections can be made.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WXE-11922: %s wallet fails to open at location %s, NZE-%d, as user %s**

**Cause:** The wallet could not be opened as the user specified.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Check for the existence of the wallet and make sure auto-login was enabled as the user specified.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WXE-11923: %s wallet fails to open at location %s, NZE-%d.**

**Cause:** The wallet could not be opened

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Check for the existence of the wallet.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WXE-11924: Oracle wallet fails to open persona, NZE-%d.**

**Cause:** The SSL library failed to retrieve certificate from wallet.

**Action:** See the "Network Security Messages (NZE)" chapter of the Oracle Database Error Messages for information about NZE errors.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WXE-11925: No wallet configured with SSL; server initialization fails.**

**Cause:** SSL was configured without specifying a wallet.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Correct the configuration file.

**Level:** 1

**Type:** ERROR

---

**Impact:** Security

**WXE-11926: Oracle Web Cache fails to set cipher suite in SSL handshake, NZE-%d.**

**Cause:** The SSL library failed to set the cipher suite.

**Action:** See the "Network Security Messages (NZE)" chapter of the Oracle Database Error Messages for information about NZE errors.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WXE-11927: Oracle Web Cache fails to get supported cipher suites, NZE-%d.**

**Cause:** The SSL library failed to get the supported cipher suites.

**Action:** See the "Network Security Messages (NZE)" chapter of the Oracle Database Error Messages for information about NZE errors.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WXE-11928: Oracle Web Cache fails to set session reference, NZE-%d.**

**Cause:** The SSL library failed to get the supported cipher suites.

**Action:** See the "Network Security Messages (NZE)" chapter of the Oracle Database Error Messages for information about NZE errors.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WXE-11929: SSL handshake fails NZE-%s.**

**Cause:** SSL handshake error occurred.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. See the "Network Security Messages (NZE)" chapter of the Oracle Database Error Messages for information about NZE errors.

**Level:** 1

**Type:** WARNING

**Impact:** Security

**WXE-11930: The object is in the cache, but Single Sign-On authentication is required.**

**Cause:** The cached object will be served to the client, but Single Sign-On authentication must be done before the document is served.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Security

**WXE-11931: The object is in the cache, but the inactivity timeout cookie must be updated.**

---

**Cause:** The cached object will be served to the client, but the global inactivity timeout cookie must first be updated.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Security

**WXE-11932: The request has a Single Sign-On authentication cookie validated by Oracle Web Cache.**

**Cause:** The Single Sign-On authentication cookie associated with the request has been validated by Oracle Web Cache.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Security

**WXE-11933: The request has a Single Sign-On authentication cookie that needs to be validated by origin server.**

**Cause:** The Single Sign-On authentication cookie associated with the request needs to be validated by the origin server.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Security

**WXE-11934: The request has a global inactivity timeout cookie validated by Oracle Web Cache.**

**Cause:** The global inactivity timeout cookie associated with the request has been validated by Oracle Web Cache.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Security

**WXE-11935: The request has a global inactivity timeout cookie that needs to be validated by origin server.**

**Cause:** The global inactivity timeout cookie associated with the request needs to be updated by the origin server.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Security

**WXE-11936: Oracle Web Cache has started watching for %.\*s Single Sign-On authentication cookie.**

---

**Cause:** Oracle Web Cache has received new Single Sign-On authentication cookie name settings from origin server.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Security

**WXE-11937: Oracle Web Cache has started watching for %.\*s global inactivity timeout cookie.**

**Cause:** Oracle Web Cache has received new global inactivity timeout cookie name settings from an origin server.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Security

**WXE-11938: A new %s cookie with key %llx:%llx stored in memory for %d seconds.**

**Cause:** Oracle Web Cache has temporarily stored the cookie in memory.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11939: The %s cookie with key %llx:%llx and reference count %d in memory has been marked stale.**

**Cause:** The cookie stored in memory has been marked stale for garbage collection.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11940: The %s cookie with key %llx:%llx is being removed from memory.**

**Cause:** The stale cookie stored in memory is being garbage collected.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11941: Oracle-WebCache-OSSO response header contains token \"%.\*s\" with unexpected value \"%.\*s\".**

**Cause:** Oracle Web Cache has received a response that contains a malformed Oracle-WebCache-OSSO response header. It is possible that this Oracle Web Cache release is incompatible with the origin server.

**Action:** Ensure that the Oracle Web Cache version is compatible with that of the origin server

---

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11942: CRL is enabled without enabling client side certificate.**

**Cause:** CRL is enabled on one of the listening endpoints, without requiring client side certificate.

**Action:** Ensure that client side certificate is required on the endpoint.

**Level:** 1

**Type:** ERROR

**Impact:** Security

**WXE-11950: Internal XML parser error. Error code: %d. Error Message: %s**

**Cause:** An internal error occurred while inside the XML parser. Oracle Web Cache will attempt to log that internal error.

**Action:** This error usually occurs due to malformed XML. Look up the associated error code in the Oracle XDK documentation.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11951: invalid value for ESI redirect attribute**

**Cause:** The value specified for the redirect attribute by the <esi:include> tag was invalid.

**Action:** Set the value of the redirect attribute value to either "yes" or "no" in the ESI template.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11952: Start processing ESI document %.\*s%.\*s, nesting level %d**

**Cause:** Start processing of an ESI document (template or fragment).

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11953: In ESI template %.\*s%.\*s, the fragment's site name and URL has been discovered as %.\*s and %.\*s**

**Cause:** Start processing of an ESI fragment.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11960: Oracle Web Cache is unable to decode the URI passed in: %s**

---

**Cause:** URI decoding was unsuccessful, and it will be used as it is.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11962: Oracle Web Cache is unable to allocate enough memory to parse ESI vars tag string**

**Cause:** There was not sufficient memory for Oracle Web Cache to parse the string in the ESI vars tag.

**Action:** Adjust the maximum cache size in the Resource Limits page of Fusion Middleware Control. If the problem persists, contact Oracle Support.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11963: Oracle Web Cache failed to create new ESI fragment request. Template uri: %.\*s**

**Cause:** ESI fragment request could not be generated. This error is generally a result of insufficient memory.

**Action:** Adjust the maximum cache size in the Resource Limits page of Fusion Middleware Control. If the problem persists, contact Oracle Support.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11964: empty variable key in ESI vars tag**

**Cause:** The variable key specified in the ESI template by the ESI vars tag was empty."key" was missing from \${VARIABLE\_NAME{key="value"}}).

**Action:** Correct the format of the ESI vars tag.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11965: invalid variable name in ESI vars tag**

**Cause:** The variable name specified in the ESI template by the ESI vars tag is not defined.

**Action:** See the Oracle Web Cache Administrator's Guide for valid ESI variable names.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11966: In %.\*s%.\*s, request header failed to be added to the include request.**

**Cause:** There was not sufficient memory for Oracle Web Cache to include the request, or there was a request header parsing error.

---

**Action:** Adjust the maximum cache size in the Resource Limits page of Fusion Middleware Control. If the problem persists, contact Oracle Support.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11967: malformed request header when fetching %.\*s%.\*s.**

**Cause:** This request header did not have a colon (:) and was malformed.

**Action:** If the problem persists, contact Oracle Support.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11968: ESI fragment request URI parsing error**

**Cause:** There was an unexpected condition in parsing the URI in an ESI fragment.

**Action:** If the problem persists, contact Oracle Support.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11969: invalid ESI variable string type**

**Cause:** Oracle Web Cache reached some invalid vars string type other than TEXT, VARIABLE, and CRLF.

**Action:** If the problem persists, contact Oracle Support.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11970: Cache key composition failed**

**Cause:** Oracle Web Cache could not generate a cache key for an ESI fragment

**Action:** If the problem persists, contact Oracle Support.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11971: Oracle Web Cache attempted to return the \$(QUERY\_STRING) decoded**

**Cause:** A \$(QUERY\_STRING) was requested to be returned in decoded format. \$(QUERY\_STRING) must be returned in encoded format.

**Action:** Contact Oracle Support.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-11972: Template host header does not match UMD host header for Portal UMD request. template header: %.\*s UMD header: %.\*s**

---

**Cause:** In an Oracle Portal environment, a UMD specification is most likely using an incorrect URL specification. This could cause errors to be reported in the browser.

**Action:** Contact Oracle Support.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-11973: Site name cannot be resolved.**

**Cause:** Requested site in ESI fragment request could not be resolved.

**Action:** Make sure that site name in the ESI request is correct.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11974: Incomplete URI for ESI fragment.**

**Cause:** URI for ESI fragment only had "http:/" and was considered incomplete.

**Action:** Make sure that the URL in the ESI request is complete.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11975: Corrupted login data in ESI environment metadata block.**

**Cause:** The application delivered data that could not be parsed to Oracle Web Cache.

**Action:** Fix the application.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11976: Duplicate name %s in ESI environment metadata block.**

**Cause:** The environment block contained multiple name entries.

**Action:** Remove the duplicate entries. Only the first entry is used.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-11977: Memory allocation failure while initializing login metadata hash table.**

**Cause:** The Oracle Web Cache memory manager could not allocate any more memory.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Adjust the maximum cache size in the Resource Limits page of Fusion Middleware Control.

**Level:** 1



---

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11978: In ESI template %s%s, failed to add request header value.**

**Cause:** Wrong request-header was specified.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g.  
Check the ESI template file and correct the error in request\_header attribute.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11979: In ESI template %s%s, failed to add the request header because value is missing**

**Cause:** Value field in the request-header was missing.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g.  
Check the ESI template file and correct the error in the request\_header attribute

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11985: Oracle Web Cache is unable to obtain the size of the default ESI fragment page %s.**

**Cause:** The default ESI fragment was not readable or did not exist in the \$ORACLE\_HOME/webcache/files on UNIX or ORACLE\_HOME\\webcache\\files directory on Windows.

**Action:** Create a readable default ESI fragment in the \$ORACLE\_HOME/webcache/files on UNIX or ORACLE\_HOME\\webcache\\files directory on Windows, and then configure it in the Error Page of Fusion Middleware Control.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11986: The default ESI fragment page %s is too large.**

**Cause:** The default ESI fragment was too large.

**Action:** Alter the size of the default ESI fragment to less than 32 KB.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11987: Oracle Web Cache fails to open the default ESI fragment page %s.**

**Cause:** The default ESI fragment was not readable or did not exist in the \$ORACLE\_HOME/webcache/files on UNIX or ORACLE\_HOME\\webcache\\files directory on Windows.

**Action:** Create a readable default ESI fragment in the \$ORACLE\_HOME/webcache/files on UNIX or ORACLE\_HOME\\webcache\\files

---

directory on Windows, and then configure it in the Error Page of Fusion Middleware Control.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11989: read error while loading default ESI fragment page %s**

**Cause:** The default ESI fragment was not readable or did not exist in the \$ORACLE\_HOME/webcache/files on UNIX or ORACLE\_HOME\webcache\files directory on Windows.

**Action:** Create a readable default ESI fragment in the \$ORACLE\_HOME/webcache/files on UNIX or ORACLE\_HOME\webcache\files directory on Windows, and then configure it in the Error Page of Fusion Middleware Control.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-11997: ESI stack overflow**

**Cause:** Current stack maximum depth was set too low.

**Action:** Contact Oracle Support about how to increase the maximum stack depth.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12001: ESI <esi:include> tag nesting in template %.\*s%.\*s is too deep.**

**Cause:** The fragment <esi:include> depth exceeded the maximum include depth of three levels.

**Action:** Decrease the depth number in the ESI template, or contact Oracle Support to change the maximum <esi:include> depth.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-12002: Origin server busy exception in ESI template %.\*s%.\*s, fragment %.\*s%.\*s**

**Cause:** The origin server was busy and could not accept the new request.

**Action:** Check the health status of the origin server. If needed, increase the origin server capacity in the Origin Servers page of Fusion Middleware Control.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-12003: No connection exception in ESI template %.\*s%.\*s, fragment %.\*s%.\*s**

**Cause:** The cache was unable to connect to the origin server.

---

**Action:** Check the health status of the origin server. If needed, increase the origin server capacity in the Origin Servers page of Fusion Middleware Control.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-12004: Network timeout exception in ESI template %.\*s%.\*s, fragment %.\*s%.\*s**

**Cause:** The request to origin server timed out during a network connection.

**Action:** Check the health status of the origin server. If needed, increase the origin server capacity in the Origin Servers page of Fusion Middleware Control.

**Level:** 1

**Type:** WARNING

**Impact:** Network

**WXE-12005: HTTP Client Error 4xx exception in ESI template %.\*s%.\*s, fragment %.\*s%.\*s**

**Cause:** The origin server returned an HTTP 4xx status code.

**Action:** Check for errors in the ESI template and fragment files.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-12006: HTTP Server Error 5xx exception in ESI template %.\*s%.\*s, fragment %.\*s%.\*s**

**Cause:** The origin server returned an HTTP 5xx status code.

**Action:** Check for errors in the ESI template and fragment files. Additionally, check the health status of the origin server.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-12007: Incompatible fragment version exception in ESI template %.\*s%.\*s, fragment %.\*s%.\*s**

**Cause:** The value for the content control directive in the Surrogate-Control response-header was not compatible between the ESI fragment and template.

**Action:** Correct the error in either the ESI template or fragment file.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-12008: Incorrect response header exception in ESI template %.\*s%.\*s, fragment %.\*s%.\*s**

**Cause:** The response header of the ESI fragment caused an error.

**Action:** Correct the error in the ESI fragment.

---

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-12009: Incorrect ESI fragment exception in ESI template %.\*s%.\*s, fragment %.\*s%.\*s**

**Cause:** Oracle Web Cache was unable to parse the ESI fragment.

**Action:** Correct the error in the ESI fragment.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-12010: Incorrect XML Fragment exception in ESI template %.\*s%.\*s, fragment %.\*s%.\*s**

**Cause:** Oracle Web Cache was unable to parse the XML fragment.

**Action:** Correct the error in the XML fragment.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-12011: Generic exception in ESI template %.\*s%.\*s, fragment %.\*s%.\*s**

**Cause:** A generic ESI exception occurred.

**Action:** Check the template and fragment, and then correct the error.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-12012: No exception handler is defined in template %.\*s%.\*s:**

**Cause:** An uncaught ESI exception was detected. An error page is returned.

**Action:** Correct the syntax error in the ESI template.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12013: No resolved virtual host mapping was found for template.**

**Cause:** A ESI template contained an unresolved virtual host mapping.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-12014: The cached ESI inline fragment is stale because the origin server was contacted for a fresh copy of the parent page which contains this ESI inline fragment.**

---

**Cause:** Because the cached object is stale, Oracle Web Cache will use the new fresh copy of the inline fragment.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-12015: Non-fetchable inline fragment %.\*s%.\*s not found in cache or already expired, fetching template %.\*s%.\*s from origin server again.**

**Cause:** Normal trace behavior.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-12081: ESI parsing error. Dumping ESI content:**

**Cause:** ESI parsing error.

**Action:** For any syntax errors, correct the ESI syntax. For any non-syntax related error, contact Oracle Support Services.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12082: Oracle Web Cache cannot parse ESI due to insufficient memory**

**Cause:** Oracle Web Cache ran out of memory while parsing ESI.

**Action:** Adjust the maximum cache size in the Resource Limits page of Fusion Middleware Control. If the problem persists, contact Oracle Support.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12083: ESI parser internal error at line %d: %s**

**Cause:** An ESI tag closed too early or there was an internal error of the ESI parser.

**Action:** For any syntax errors, correct the ESI syntax. For any non-syntax related error, contact Oracle Support.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12084: JESI fragment preprocessing error**

**Cause:** Preprocessing of JESI fragment failed.

**Action:** Contact Oracle Support.

**Level:** 8

**Type:** INTERNAL\_ERROR

---

**Impact:** Requests/Responses

**WXE-12085: ESI syntax error. Bad exception type at line %d.**

**Cause:** An invalid token was encountered.

**Action:** Correct the error at the specified location in the ESI template.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12086: ESI syntax error. Unrecognized keyword %s is at line %d.**

**Cause:** An invalid token was encountered.

**Action:** Correct the error at the specified location in the ESI template.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12087: Bad Location response header in ESI fragment response**

**Cause:** A redirection response contained an invalid Location header.

**Action:** Make sure that the application Web server sends a valid Location header.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12088: ESI syntax error. The src attribute is missing at line %d.**

**Cause:** The src attribute is required for the <esi:include> and <esi:environment> tags.

**Action:** Correct the error at the specified location in the ESI template.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12089: Syntax error. The name attribute is missing at line %d.**

**Cause:** The name attribute is required for the <esi:inline> tag, <esi:environment> tag, and the request\_header element.

**Action:** Include the name attribute at the specified location in the ESI template.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12090: ESI syntax error. Bad attribute value appears at line %d.**

**Cause:** An invalid or empty value string was found.

**Action:** Correct the error at the specified location in the ESI template.

**Level:** 16

**Type:** ERROR

---

**Impact:** Requests/Responses

**WXE-12091: ESI syntax error. Multiple ESI <esi:environment> tags appear in a single template at line %d**

**Cause:** Multiple <esi:environment> tags in a single ESI template are not allowed.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Configure the ESI template with one <esi:environment> tag.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12092: ESI Syntax error. Multiple request\_body elements appear at line %d.**

**Cause:** Multiple request\_body elements are not allowed in <esi:include> and <esi:environment> tags.

**Action:** Correct the error at the specified location in the ESI template.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12093: ESI syntax error. The max-age attribute is incorrectly formatted at line %d.**

**Cause:** The max-age attribute is not in the format of: max-age="expiration\_time[+removal\_time]

**Action:** Correct the error at the specified location in the ESI template.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12094: ESI syntax error. String length exceeds maximum at line %d.**

**Cause:** The string length exceeded the maximum limit.

**Action:** Contact Oracle Support to change the string length limit.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12095: ESI syntax error. A variable requires a key at line %d.**

**Cause:** The specified variable requires a format of \$(VARIABLE\_NAME{key}).

**Action:** Include a key in the variable at the specified location in the ESI template.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12096: ESI syntax error. The POST request method requires an request\_body at line %d.**

**Cause:** The specified POST fragment did not have a request\_body element.

---

**Action:** Include the request\_body element at the specified location in the ESI template.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12097: ESI syntax error. The position of the <esi:environment> tag at line %d is invalid.**

**Cause:** The <esi:environment> did not appear before any <esi:include> tags in the syntax. To use the custom variables specified by the <esi:environment> tag with other ESI tags, the <esi:environment> must be included before other <esi:include> tags.

**Action:** Correct the error at the specified location in the ESI template.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12098: ESI syntax error. The value of the fetchable attribute at line %d is invalid.**

**Cause:** A value of yes or no are the only possible values for the fetchable attribute.

**Action:** Change the value to either yes or no at the specified location in the ESI template.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12099: ESI syntax error. The same attribute appears multiple times in an ESI element at line %d.**

**Cause:** An attribute can appear only once within an ESI element.

**Action:** Correct the error at the specified location in ESI object.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12100: Exhausted process memory. Exiting process.**

**Cause:** Memory usage is greater than the process' system memory allocation.

**Action:** Reduce the maximum cache size limit or increase the operating system's memory limit for the Oracle Web Cache process, if possible.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12101: Maximum receive buffer size 2 MB reached.**

**Cause:** Receive buffer size is bigger than 2 MB on Windows platforms.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Reduce receive buffer size to below 2 MB.



---

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12102: Unable to locate memory block (%db). Oracle Web Cache extends cache size over maximum limit to %dMB.**

**Cause:** Memory request was not fulfilled with existing process memory, even after forced garbage collection.

**Action:** 1. From `http://web_cache_hostname:web_cache_stats_port`, select review the Detailed Memory Statistics. If requesting block size for garbage collection is larger than object buffer size, then consider: a. Increase the object buffer size. Contact Oracle Support for further information. b. Increase the maximum cache size in the Resource page of Fusion Middleware Control. 2. If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12103: Unable to locate large memory block (%db). Oracle Web Cache extends cache size over maximum limit to %dMB.**

**Cause:** Large block memory request was not satisfied with existing process memory, even after forced garbage collection.

**Action:** 1. From `http://web_cache_hostname:web_cache_stats_port`, select review the Detailed Memory Statistics. If requesting block size for garbage collection is larger than object buffer size, then consider: a. Increase the object buffer size. Contact Oracle Support for further information. b. Increase the maximum cache size in the Resource Limits page of Fusion Middleware Control.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12104: Oracle Web Cache process has page faulted**

**Cause:** The Oracle Web Cache process has caused a hard operating system memory page fault to occur. This may indicate the physical system is overloaded or there is insufficient physical memory for the specified cache size.

**Action:** Try decreasing the maximum cache size.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-12200: Cache memory allocation for the cluster configuration block failed.**

**Cause:** Memory allocation failed.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

---

**WXE-12201: Cache memory allocation for the cluster member table failed.**

**Cause:** Memory allocation failed.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12202: Cluster member DNS lookup problem**

**Cause:** Could not resolve the IP address from the cluster member's host name.

**Action:** Check the Cluster Members and Properties page of Fusion Middleware Control to see if the host name is correctly listed.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-12203: Cluster member number %s owner slot allocation %s:%s**

**Cause:** Normal trace behavior.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-12204: Add cluster member number %s**

**Cause:** Normal notification behavior.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-12205: Remove cluster member number %s**

**Cause:** Normal notification behavior.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-12206: Cluster member number %s already marked alive**

**Cause:** The local cache tried to add the specified cluster member, but it was already marked as alive.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

---

**WXE-12207: Cluster member number %s already marked dead**

**Cause:** The local cache tried to remove the specified cluster member, but it was already marked as dead.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-12209: A %s node cluster successfully initialized**

**Cause:** Normal notification behavior.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-12212: Cluster member %s - %s configuration is invalid.**

**Cause:** The configuration file of the specified cluster member does not match the configuration of the local cache.

**Action:** Check that all cluster members have the same configuration file.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-12213: Cluster member %s - %s configuration is valid.**

**Cause:** Normal notification behavior.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-12217: Cluster member count %s is larger than maximum allowed %s**

**Cause:** There are more than the maximum number of cluster members. There cannot be more than 99 cluster members.

**Action:** Reduce the number of cluster members by removing some members in the Cluster Members and Properties page of Fusion Middleware Control.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12400: HTTP request-header exceeds configured maximum individual header size ( %s ). Client IP: %s**

**Cause:** Oracle Web Cache received an HTTP request with an abnormally large header, indicating a possible denial-of-service attack.

**Action:** If the problem persists, you may need to increase the maximum individual header size in the Security page of Fusion Middleware Control.

---

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12401: HTTP request-header exceeds configured maximum combined header size. Client IP: %s**

**Cause:** Oracle Web Cache received an HTTP request with an abnormally large header, indicating a possible denial-of-service attack.

**Action:** If the problem persists, you may need to increase the maximum combined header size in the Security page of Fusion Middleware Control.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12402: HTTP response-header parsing error: %.\*s.**

**Cause:** An HTTP response from the origin server contained a header or an individual header value that was malformed or unexpected.

**Action:** If the behavior is still as expected, no action is required. If the behavior is not as expected, check the application code which generates the specified header.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12403: HTTP response-header parsing error: %s ( %s ).**

**Cause:** An HTTP response from the origin server contained a malformed header or an individual header value that was malformed or unexpected.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12404: The number of search keys exceeds the maximum limit of search keys in the Surrogate-Key response-header.**

**Cause:** The number of search keys in the Surrogate-Key response-header exceeded the allowed configurable maximum defined in configuration file.

**Action:** Revise the Surrogate-Key response-header with configured maximum or fewer search keys.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-12405: Illegal time format in HTTP response-header.**

**Cause:** HTTP response-header contains an illegal time format.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

---

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-12408: Unexpectedly large HTTP response-header.**

**Cause:** An unexpectedly large response-header was received from the origin server, indicating a possible performance problem.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Contact Oracle Support.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-12409: Timeout while reading HTTP response.**

**Cause:** No timely response received from the origin server, indicating that the origin server is down.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Start origin server, if it is not running.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12410: Error while reading HTTP response ( SSL error %d ).**

**Cause:** Oracle Web Cache encountered an SSL read error.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. If the problem persists, contact Oracle Support.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12411: Non-parseable HTTP request-header line - questionable token syntax.**

**Client IP:** %s

**Cause:** An HTTP request from a browser contained a line with a token value containing either an unpaired parenthesis ( ( or ) ) or an unpaired double-quote ("). For example: Cookie: name="John Hancock

**Action:** No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12412: HTTP request-header parsing error - malformed request line. Client IP: %s**

**Cause:** An HTTP request from a browser contained a malformed request line; it contained either an unknown method name or an illegal version string.

**Action:** No action required.

**Level:** 16

---

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12413: Unable to get Oracle name of ESI template character set ( %. \*s ).**

**Cause:** A recoverable internal error occurred while doing character set conversion.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-12414: Unable to get Oracle name of ESI fragment character set ( %. \*s ).**

**Cause:** A recoverable internal error occurred while doing character set conversion.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-12415: Unable to do character set conversion.**

**Cause:** Internal error. A system/library call has unexpectedly failed.

**Action:** If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-12416: NLS library failure while doing character set conversion.**

**Cause:** Internal error. A system/library call has unexpectedly failed.

**Action:** If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-12417: HTTP request-header parsing error - no header name. Client IP: %s**

**Cause:** An HTTP request from a browser contained a malformed header line; the header name delimiting colon (':') was not present.

**Action:** No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12419: Dump of offending HTTP request-header line:**

**Cause:** Any of the causes associated with errors 12411, 12412 and 12417.

**Action:** No action required.

**Level:** 16

---

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12420: The number of search keys exceeds the maximum hard limit of search keys in the Surrogate-Key response-header thus excessive search keys are discarded.**

**Cause:** The number of search keys in the Surrogate-Key response-header exceeded the allowed hard maximum of 200.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Revise the Surrogate-Key response-header with 200 or fewer search keys.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12421: HTTP request is invalid due to a duplicate header occurrence: \"%.\*s\".**

**Client IP:** %s

**Cause:** An HTTP request from a browser contained multiple occurrences of the same header type.

**Action:** No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12422: Duplicate header occurrence(\"%.\*s\") is in HTTP request.**

**Cause:** An HTTP request from a browser contained multiple occurrences of the same header type.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-12423: Response ETag header has no value possibly indicating an application server problem. This message is only printed once per cache process.**

**Cause:** The response contains a NULL or empty string ETag header. This could be a problem with the application server

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-12424: Ignoring unrecognized token \"%.\*s\" in Oracle-WebCache-OSSO response header.**

**Cause:** Oracle Web Cache has received a response from origin server that contains a token in Oracle-WebCache-OSSO header that is not recognized by Oracle Web Cache.

---

**Action:** Ensure that the Oracle Web Cache version is compatible with that of the origin server

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-12425: Malformed invalidation capability request header (\ "%.\*s\ ") in HTTP request.**

**Cause:** An HTTP request from a browser contained a malformed invalidation capability request header.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-12700: Site %.\*s did not match any defined sites, resulting in no End User Performance Monitoring for URI**

**Cause:** Normal trace behavior.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-12701: Site %.\*s matched one of the defined sites for which End User Performance Monitoring is ON.**

**Cause:** Normal trace behavior.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-12702: Site %.\*s matched a defined site with End User Performance Monitoring OFF, resulting in no End User Performance Monitoring for URI**

**Cause:** Normal trace behavior.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-12703: No matching End User Performance Monitoring rule found for site %.\*s, resulting in End User Performance Monitoring for URI.**

**Cause:** Normal trace behavior.

**Action:** No action required.

**Level:** 1

**Type:** TRACE



---

**Impact:** Requests/Responses

**WXE-12704: There are no End User Performance Monitoring rules defined for site %.\*s, resulting in End User Performance Monitoring for URI.**

**Cause:** Normal trace behavior.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-12705: Matching End User Performance Monitoring REGEXP rule found regexp:%s and the rule is %s**

**Cause:** Normal trace behavior. Matching End User Performance Monitoring rule found. The rule determines whether or not to monitor End User Performance for the URI.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-12706: Matching End User Performance Monitoring SUBSTRING rule found. substring:%s and the rule is %s**

**Cause:** Normal trace behavior. Matching End User Performance Monitoring rule found. The rule determines whether or not to monitor End User Performance for the URI.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-12712: OEMPERFFILE can only be set to an .html file.**

**Cause:** The file specified by OEMPERFFILE must be an .html file, but it was not.

**Action:** Contact Oracle Support for help in specifying the correct OEMPERFFILE.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12713: OEMPERFFILE cannot be parsed. Use the following format: <SCRIPT SRC=\"%schronos\_JavaScript\_filename\"></SCRIPT> and restart Oracle Web Cache.**

**Cause:** OEMPERFFILE could not be parsed.

**Action:** Use the following format for the value of OEMPERFFILE: <SCRIPT SRC=\"%schronos\_JavaScript\_filename\"></SCRIPT>. Then, restart Oracle Web Cache.

**Level:** 16

**Type:** ERROR

---

**Impact:** Requests/Responses

**WXE-12714: Invalid string specified for OEMPERFFILE.**

**Cause:** The file name specified by OEMPERFFILE is an invalid string.

**Action:** Contact Oracle Support for help in specifying the correct OEMPERFFILE.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12715: OEMPERFFILE contains an invalid path separator.**

**Cause:** The file name specified for OEMPERFFILE contains an invalid path separator.

**Action:** Correct the file name specified for OEMPERFFILE.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12716: End-User Performance Monitoring is enabled.**

**Cause:** Normal notification behavior. End-User Performance Monitoring is enabled. The event is written to the log file.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-12800: Oracle Web Cache fails to read the configuration file. Dynamic changes have not been applied.**

**Cause:** Normal trace behavior.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Configuration

**WXE-12801: Dynamic Changes Applied Successfully**

**Cause:** Normal trace behavior.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Configuration

**WXE-12802: The cache server cannot dynamically mark the origin servers as running because they are not responding. Other selected dynamic changes are applied.**

**Cause:** The origin servers were not responding. The cache server disregarded this dynamic change, but applied other dynamic changes.

**Action:** No action required.

---

**Level:** 1

**Type:** TRACE

**Impact:** Configuration

**WXE-12803: Dynamic Changes Not Applied**

**Cause:** Normal trace behavior.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Configuration

**WXE-12804: Event Log rolled over.**

**Cause:** Normal trace behavior.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Logging

**WXE-12805: Access log %s rolls over.**

**Cause:** Access log rolled over as a result of an on-demand rollover request.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**WXE-12806: Non-existent access log %s specified in rollover request.**

**Cause:** On-demand rollover request was submitted with an invalid access log name.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**WXE-12807: Event log not rolled over because the rollover file already exists.**

**Cause:** Normal trace behavior.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Logging

**WXE-12808: Access Log %s not rolled over because the rollover file already exists.**

**Cause:** Access Log is rolled over as a result of on-demand rollover request.

**Action:** Submit another rollover request after more than one minute.

**Level:** 1

---

**Type:** NOTIFICATION

**Impact:** Logging

**WXE-12809: Could not find the matching Origin Server entry in original configuration which the cache server is running with.**

**Cause:** Normal trace behavior.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-12810: ESI fragment log for access log %s is not rolled over.**

**Cause:** Regular access log was rolled over due to an on-demand rollover request, but accompanying ESI fragment log was not rolled over for some reason.

**Action:** Submit another rollover request after one minute.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**WXE-12811: Dynamic event log rollover fails because the event log file does not exist.**

**Cause:** Dynamic event log rollover failed because Oracle Web Cache failed to create the event log file at startup time.

**Action:** Review the event log file name specified in configuration.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**WXE-12812: Dynamic event log rollover fails because the event log file could not be renamed.**

**Cause:** Dynamic event log rollover failed because Oracle Web Cache could not rename the file.

**Action:** Check the permissions of the event log file or if any other application is using the event log file.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**WXE-12813: Access log name is not specified in rollover request.**

**Cause:** On-demand access log rollover request did not contain the access log name.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

---

**WXE-12814: \*\*\*\*\* Request message notification begin \*\*\*\*\***

**Cause:** Request-specific event\_log messages.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**WXE-12815: \*\*\*\*\* Request message notification complete \*\*\*\*\***

**Cause:** Request-specific event\_log messages.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**WXE-12817: Directory %s size reduced from %dMB to rollover criteria %dMB**

**Cause:** The specified logfile was automatically purged because the directory exceeded the maximum size threshold designated in the configuration.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**WXE-12818: Logfile %s (size %dMB) deleted due to rollover criteria (%dMB)**

**Cause:** The specified logfile was automatically purged because the directory exceeded the maximum size threshold designated in the configuration.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**WXE-12819: event\_log reverted to old-style logging with WCDEBUG enabled**

**Cause:** When the event\_log is configured using the MODE="NEW" attribute (the default configuration), but the WCDEBUG feature is enabled, the logging sub-system must revert to the MODE="OLD" configuration.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Logging

**WXE-12820: Logfile %s (size %dMB) deleted due to time-based retention criteria**

**Cause:** The specified logfile was automatically purged because the directory exceeded the maximum retention period designated in the configuration.

**Action:** No action required.

**Level:** 1

---

**Type:** NOTIFICATION

**Impact:** Logging

**WXE-12822: Oracle Web Cache fails to rename file from %.\*s to %.\*s (%s)**

**Cause:** Dynamic event log rollover failed because Oracle Web Cache could not rename the file.

**Action:** Check the permissions of the event log file and if another application is using the event log file.

**Level:** 1

**Type:** TRACE

**Impact:** Logging

**WXE-12900: Oracle Web Cache fails to read the final byte ('X') from Oracle Web Conferencing client; redirect fails.**

**Cause:** Oracle Web Conferencing client did not send the character X to mark request end

**Action:** No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12901: Oracle Web Cache fails to send the message to the Oracle Web Conferencing client; redirect fails.**

**Cause:** Oracle Web Cache could not send Oracle Web Conferencing protocol message to client.

**Action:** No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12902: The mx list is empty in the Oracle Web Conferencing path %s.**

**Cause:** The configured mx path set was incorrect.

**Action:** Configure the correct mx path.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12903: The Oracle Web Conferencing pass descriptor fails; Error: %s.**

**Cause:** Oracle Web Cache was unable to pass descriptor to the mx server.

**Action:** Check the mx server configuration and log files.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12904: Oracle Web Conferencing redirect did not occur for mx path = %s.**

---

**Cause:** Oracle Web Cache was not able to pass descriptor to the mx server on any of the mx server ports.

**Action:** Check the mx server configuration and log files.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12905: Oracle Web Conferencing redirect is successful.**

**Cause:** Normal trace behavior.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-12906: The Windows socket could not be set to blocking; Error: %s.**

**Cause:** The error was caused the by the error printed in the message.

**Action:** Debug from the error printed in the message.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12907: The Oracle Web Conferencing URL is not valid.**

**Cause:** The URL received by webcache is invalid.

**Action:** Check the Oracle Web Conferencing configuration.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-12908: The Oracle Web Conferencing pass descriptor is successful.**

**Cause:** Normal trace behavior.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-13001: Virtual Host Map %s has a mixture of HTTP and HTTPS Protocol origin servers. All origin servers for a virtual host map must use the same protocol.**

**Cause:** The specified virtual host map consists of origin servers with HTTP and HTTPS protocols. A virtual host mapping must consist of origin servers that use either the HTTP protocol exclusively or the HTTPS protocol exclusively.

**Action:** From the Sites page of Fusion Middleware Control, correct the mapping. Then, restart Oracle Web Cache.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**WXE-13002: Maximum allowed incoming connections are %u**

**Cause:** Normal notification behavior indicating the maximum number of concurrent connections which will be accepted.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**WXE-13003: Configuration error. Stopping admin or cache server.**

**Cause:** The admin or cache server was unable to parse or read its configuration information.

**Action:** Review any other error messages to determine the cause of the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WXE-13005: The session definition for the session \"%s\" is missing but used in the WTI session key configuration for server \"%s\".**

**Cause:** A non-existent session definition is referenced by its name in WTI session key configuration in the configuration file.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Modify the configuration to either add the session definition or used another existing definition.

**Level:** 16

**Type:** ERROR

**Impact:** Configuration

**WXE-13006: The session inactivity timeout for the session \"%s\" is missing but required in the WTI session key configuration for server \"%s\".**

**Cause:** The session used for WTI session key does not have an inactivity timeout defined.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. A WTI session key is used for security purposes. It is based on a user session which should have an inactivity timeout. Please add the inactivity timeout to the session definition for this session.

**Level:** 16

**Type:** ERROR

**Impact:** Configuration

**WXE-13007: The specified listening IP address \"%s\" is not valid.**

**Cause:** The specified listening IP address was not valid 32-bit dotted decimal notation, resolvable host name, ANY, or asterisk (\*).

**Action:** 1. Check if the specified listening address is configured as a valid 32-bit numeric address written as four numbers separated by dots. Oracle Enterprise



---

Manager permits \* permits ANY to support all IP addresses. 2. If you need to specify host name instead of an IP address, check if the host name can be resolved to an IP address on your system. 3. If you need to rely on DNS to resolve the host name, check if DNS is correctly working.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WXE-13008: CRL is enabled for listen port %s but no CRL file or path is specified.**

**Cause:** Both port specific and global settings of SSLCRLPATH and SSLCRLFILE are NIL but SSLCRLENABLE is set to "YES"

**Action:** Modify the configuration to either specify a valid SSLCRLPATH and SSLCRLFILE or disable CRL checking.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WXE-13009: CRL is enabled for listen port %s without enabling client side certificate.**

**Cause:** CLIENT\_CERT must be set to "YES" or "OPTIONAL" when SSLCRLENABLE is set to "YES".

**Action:** Modify the configuration and correct CLIENT\_CERT setting or disable CRL checking.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WXE-13010: MAXLOGSIZE (%d) cannot be larger than MAXREPSIZE (%d)**

**Cause:** The maximum logfile rollover size specified by the MAXLOGSIZE parameter is larger than the repository rollover size specified by the MAXREPSIZE configuration parameter.

**Action:** Reduce the size specified by the MAXLOGSIZE configuration parameter, or increase the size specified by the MAXREPSIZE parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WXE-13011: Invalid tweak parameter \"%s\" value \"%s\"**

**Cause:** The specified tweak parameter contains an unknown or invalid value.

**Action:** Check the documentation for the set of valid values for the specified tweak parameter.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WXE-13050: Multiple access logs use the same file name: %s**

---

**Cause:** Multiple access logs were configured to use the same output file name. The output file name cannot be shared by multiple access logs.

**Action:** Ensure that the ACCESSLOG element in the webcache.xml file has a unique FILENAME attribute.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WXE-13051: List of IP addresses only valid for ALLOW=\"LIST\_OF\_IPS\" option**

**Cause:** The specified secure subnet IP address(es) can only be supplied when the ALLOW="LIST\_OF\_IPS" attribute is specified for the SECURESUBNET element.

**Action:** Remove the list of IP addresses, or change the ALLOW attribute to the value "LIST\_OF\_IPS".

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-13052: Cache attribute INSTANCENAME %s does not match environment variable INSTANCE\_NAME %s.**

**Cause:** The instance name specified in configuration file is wrong.

**Action:** This does not affect Web Cache from starting up since runtime Web Cache do not make use of this attribute. This attribute is used by the Enterprise Manager to find the correct CACHE element.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-13074: A session caching rule refers to an invalid session name: %s**

**Cause:** The session caching rule specifies a session ID which is not defined. This error usually occurs if webcache.xml has been edited manually instead of by using Fusion Middleware Control.

**Action:** Edit webcache.xml and set the session ID to a valid session definition.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WXE-13075: A session binding rule refers to an invalid session name: %s**

**Cause:** A session binding rule specified a session ID which was not defined. This error usually occurs if webcache.xml has been edited manually instead of by using Fusion Middleware Control.

**Action:** Edit webcache.xml and correct the session definition for the specified session ID.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

---

**WXE-13076: A caching rule refers to an invalid expiration rule: %s**

**Cause:** One of the caching rules contained the specified expiration rule. That expiration rule was invalid. This error usually occurs if webcache.xml has been edited manually instead of by using Fusion Middleware Control.

**Action:** Edit webcache.xml and find the specified expiration rule and replace it with a valid expiration rule.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WXE-13077: A caching rule refers to an invalid multi-version cookie rule: %s**

**Cause:** One of the caching rules contained the specified invalid multi-version cookie rule. This error usually occurs if webcache.xml has been edited manually instead of by using Fusion Middleware Control.

**Action:** Edit webcache.xml and find the multi-version cookie rule listed in the error message. Replace the rule with a valid one.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WXE-13078: A caching rule refers to an invalid session rule: %s**

**Cause:** One of the caching rules contained the specified invalid session rule. This error usually occurs if webcache.xml has been edited manually instead of by using Fusion Middleware Control.

**Action:** Edit webcache.xml and find the specified session rule. Replace the rule with a valid one.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WXE-13079: Oracle Web Cache did not find a matching CACHE element in webcache.xml for the current host name (%s) and Oracle home (%s).**

**Cause:** Oracle Web Cache was unable to find a CACHE element for this cache. The configuration file may be in error.

**Action:** Contact Oracle Support to fix the configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WXE-13080: No NAME attribute is specified in ROLLOVER element under ACCESSLOGSTYLES**

**Cause:** Unable to find a NAME attribute in ROLLOVER element for access logs. The ROLLOVER element for access logs must have a NAME attribute.

**Action:** Edit webcache.xml and find the ROLLOVER element under ACCESSLOGSTYLES which does not have NAME attribute. Add the NAME attribute to the ROLLOVER element.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**WXE-13081: Any Set-Cookie is not configured with the a session binding mechanism other than Cookie-based.**

**Cause:** A session binding rule specifying a session of Any Set-Cookie was not configured with the Cookie-based session binding mechanism. Any Set-Cookie cannot use a mechanism of OC4J-based or Internal-Tracking.

**Action:** Change the session binding mechanism to Cookie-based.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WXE-13082: Duplicate CACHE element found in webcache.xml for current instance name (%s), component name (%s), hostname (%s) and ORACLE\_HOME (%s)**

**Cause:** Identified a duplicate CACHE element for this cache.

**Action:** Check that the hostname and ORACLE\_HOME printed in the error message match the expected values and check the CACHE elements in webcache.xml for one which is defined for these values.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WXE-13106: Log file rollover schedule refers to an invalid TIME value for the HOURLY frequency: %u**

**Cause:** Time value specified for the HOURLY frequency was invalid.

**Action:** TIME must be set to a nonzero positive integer value less than 60.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WXE-13107: Log file rollover schedule refers to an invalid TIME value for the DAILY frequency: %u**

**Cause:** Time value specified for the DAILY frequency was invalid.

**Action:** For DAILY rollover, the time format is "hhmm", where hh ranges from 0 to 23 and mm ranges from 0 to 59.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WXE-13108: Log file rollover schedule refers to an invalid TIME value for the WEEKLY frequency: %u**

**Cause:** Time value specified for the WEEKLY frequency was invalid.

**Action:** For WEEKLY rollover, the time format is "dhhmm", where "d" ranges from 0 to 6, "hh" ranges from 0 to 23 and mm ranges from 0 to 59.

**Level:** 1

---

**Type:** ERROR

**Impact:** Configuration

**WXE-13109: XML parsing error in %s. Error code %u: %s**

**Cause:** The specified XML file did not match the DTD for the file.

**Action:** See the related Oracle XML library error message for more details.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WXE-13110: XML parser initialization error. Error code: %u**

**Cause:** Unable to initialize the XML parser.

**Action:** If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WXE-13111: XML parsing failed for file: %s. Error Code: %u**

**Cause:** An XML parsing error occurred when parsing the specified file.

**Action:** Review associated error messages for more information about the problem.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WXE-13112: XML parsing failed. Error Code: %u**

**Cause:** Failed to parse an XML message.

**Action:** Review associated error messages for more information about the problem.

**Level:** 16

**Type:** ERROR

**Impact:** Configuration

**WXE-13113: Syntax error in %s. Exception: \"%s\" in attribute \"%s\" having value \"%s\" in element %s**

**Cause:** An exception occurred while parsing the specified file.

**Action:** Edit the specified file to make it a valid XML object.

**Level:** 16

**Type:** ERROR

**Impact:** Configuration

**WXE-13114: A root directory mapping must be specified before all other mappings**

**Cause:** This error may have occurred if the internal configuration has been changed.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Contact Oracle Support.

---

**Level:** 16

**Type:** ERROR

**Impact:** Configuration

**WXE-13115: Out of memory error while scanning object root**

**Cause:** The process ran out of memory while scanning for objects in the object root.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Memory

**WXE-13116: An error occurred scanning the directory %s**

**Cause:** Oracle Web Cache was unable to get the contents of the specified directory.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. If the problem persists, contact Oracle Support.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-13117: Failed to add MIME type extension to pool: %s**

**Cause:** An error occurred while processing the MIME type extensions settings.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. If the problem persists, contact Oracle Support.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-13118: Out of memory error while initializing MIME type information**

**Cause:** An error occurred while processing the MIME type extensions settings.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. If the problem persists, contact Oracle Support.

**Level:** 16

**Type:** ERROR

**Impact:** Memory

**WXE-13119: Duplicate origin server hosts specified for host %s port %s.**

**Cause:** There are duplicate entries in the HOST section of the webcache.xml file.

**Action:** Remove the duplicate entries from webcache.xml.

**Level:** 16

**Type:** ERROR

**Impact:** Configuration

**WXE-13120: CACHEWITH and CACHEWITHOUT cannot both have the value \"NO\" in a session caching policy for session %s.**

---

**Cause:** The session caching policy has a value of "NO" for both CACHEWITH and CACHEWITHOUT in webcache.xml.

**Action:** Set at least one of them to be "YES", or remove the policy.

**Level:** 16

**Type:** ERROR

**Impact:** Configuration

**WXE-13121: The caching rule for %s contains more than one multi-version cookie policy based on the same cookie: %s.**

**Cause:** More than one multi-version cookie policy is associated for the same cookie with one caching rule.

**Action:** Remove the extra policies from the caching rule.

**Level:** 16

**Type:** ERROR

**Impact:** Configuration

**WXE-13122: The caching rule for %s contains more than one session-caching policy based on the same session: %s.**

**Cause:** More than one session caching policy is associated for the same session with one caching rule.

**Action:** Remove extra policies from the caching rule.

**Level:** 16

**Type:** ERROR

**Impact:** Configuration

**WXE-13123: Site name %s:%s%s exceeds maximum individual header limit.**

**Cause:** The site name was set to more than the maximum single header limit as defined in the security section.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Increase the maximum individual header size limit in the Security page of Fusion Middleware Control, so that the site name and port number string together is less than the specified limit.

**Level:** 16

**Type:** ERROR

**Impact:** Configuration

**WXE-13124: Alias name %s:%s%s exceeds maximum individual header limit %d.**

**Cause:** The alias name was set to more than maximum individual header limit as defined in the security section.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Increase the maximum individual header size limit in the Security page of Fusion Middleware Control or change the alias name in the Sites page of Fusion Middleware Control, so that the alias name and port number string together is less than the specified limit.

**Level:** 16

**Type:** ERROR

---

**Impact:** Configuration

**WXE-13125: internal.xml does not have CALYPSOINTERNALPARAMS element.**

**Cause:** Unable to find CALYPSOINTERNALPARAMS element in internal.xml.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g.  
Check whether internal.xml conforms to internal.dtd.

**Level:** 16

**Type:** ERROR

**Impact:** Configuration

**WXE-13127: Oracle XML Schema processor failed to initialize%s.**

**Cause:** Oracle XML Schema Processor failed to initialize.

**Action:** If the problem persists, contact Oracle Support.

**Level:** 16

**Type:** ERROR

**Impact:** Configuration

**WXE-13128: XML file%s did not pass validation against schema checking%s.**

**Cause:** Error occurs in validating the XML file against its corresponding XML schema

**Action:** Fix the error accordingly in the XML file

**Level:** 16

**Type:** ERROR

**Impact:** Configuration

**WXE-13129: Setting internal tweak parameter '%s' value to '%s'.**

**Cause:** Tweak mechanism was used to change the specified internal tweak parameter to the stated new value. This occurs only at startup.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Configuration

**WXE-13130: Ignoring internal tweak parameter '%s'; value '%s' is illegal**

**Cause:** Tweak mechanism can be used to change the specified internal tweak parameter's value, but only if the value is legal for that parameter. This occurs only at startup.

**Action:** Specify a legal value (please contact Oracle Support) and try again.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**WXE-13131: Ignoring unknown internal tweak parameter '%s'.**

**Cause:** An attempt was made to use the tweak mechanism for an unknown internal tweak parameter. Because the parameter name was unknown, its value was ignored.



---

**Action:** Fix the name to be a legitimate internal tweak parameter (please contact Oracle Support) and try again.

**Level:** 1

**Type:** WARNING

**Impact:** Configuration

**WXE-13132: Invalid logfile retention specified: %d %s**

**Cause:** The specified logfile retention period is invalid. This problem can occur if the frequency definition is incorrectly spelled.

**Action:** Verify that the retention period count and frequency are correct.

**Level:** 16

**Type:** ERROR

**Impact:** Configuration

**WXE-13133: Host 'name' is required**

**Cause:** The 'name' attribute of the 'host' element was not specified, or was specified as an empty value.

**Action:** Specify a unique host name.

**Level:** 16

**Type:** ERROR

**Impact:** Configuration

**WXE-13134: Oracle Web Cache did not find a matching CACHE element in webcache.xml for the current host name (%s), Oracle instance (%s) and system component name (%s).**

**Cause:** Oracle Web Cache was unable to find a CACHE element for this cache. The configuration file may be in error.

**Action:** Contact Oracle Support to fix the configuration file.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WXE-13200: Access logging was skipped as the request had not been parsed properly.**

**Cause:** Due to an error in request parsing, access logging could not be completed.

**Action:** No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Configuration

**WXE-13212: Access log file %s could not be opened.**

**Cause:** Access log file could not be opened.

**Action:** Check the status of access log file. For example, check the permission of the file.

**Level:** 1

---

**Type:** ERROR

**Impact:** Logging

**WXE-13213: Invalid access log field name: %s**

**Cause:** An invalid access log field is specified in the configuration file webcache.xml.

**Action:** Set valid access log field name.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**WXE-13215: I/O Error when writing access Log buffer to file. error number: %d**

**Cause:** I/O error happened when Oracle Web Cache tried to write to the access log file.

**Action:** Check the status of access log file. For example, see if the disk is full.

**Level:** 1

**Type:** ERROR

**Impact:** Logging

**WXE-13250: Search key configuration error**

**Cause:** Invalid Oracle Web Cache configuration for search key.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WXE-13251: The HTML file for End-User Monitoring was not found**

**Cause:** End-User Monitoring configuration error.

**Action:** Disable End-User Monitoring or restore the HTML file that is missing. If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-13252: On Demand Log File Rollover for file %s was not successful. File %s could not be created.**

**Cause:** The rollover file could not be created.

**Action:** Check the file permissions.

**Level:** 1

**Type:** WARNING

**Impact:** Logging

**WXE-13301: A failure occurred with DNS lookups. No more DNS lookups will occur.**

**Cause:** The DNS server might be unavailable.

---

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Check the DNS configuration on the local machine.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-13302: Failed to open directory: %s**

**Cause:** Directory could not be opened because it does not exist or the access permissions are incorrect.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Check the configuration and the permissions for accessing the directory.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-13305: Failed to assign port %s: %s**

**Cause:** The selected port is being used by another application.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Change the port to an unused port.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-13306: Failed to configure resources for port %s: %s**

**Cause:** System listen function call failed.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Restart Oracle Web Cache. If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-13307: Failed to allocate resources for port %s: %s**

**Cause:** Socket creation failed.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. If the problem persists, Restart Oracle Web Cache and check open file descriptors.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-13308: Failed to listen on port %s: %s**

**Cause:** Generally occurs when the port is in use by another application.

**Action:** Change the port to an unused port. Restart Oracle Web Cache. If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** ERROR

---

**Impact:** Requests/Responses

**WXE-13309: Listening on port %s**

**Cause:** Generally occurs when the port is in use by another application.

**Action:** Change the port to an unused port. Restart Oracle Web Cache. If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-13310: Problem opening file %s (Access Denied).**

**Cause:** The file could not be opened because of an access problem.

**Action:** Fix the file permissions so that the user running webcached can access the file.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-13312: Problem creating file %s (File Already Exists).**

**Cause:** The file could not be created because it already exists.

**Action:** Choose a file name that does not exist.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-13313: Problem opening file %s (Invalid Drive).**

**Cause:** The file could not be opened because the drive name is invalid.

**Action:** Correct the file specification.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-13314: Problem opening file %s (Invalid Name).**

**Cause:** The file could not be opened because the file name is invalid.

**Action:** Correct the file specification.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-13315: Problem opening file %s (Too Many Open Files).**

**Cause:** The file could not be opened because there are too many open files in the system.

**Action:** Close other files or programs and restart Oracle Web Cache.

**Level:** 1

**Type:** WARNING

---

**Impact:** Requests/Responses

**WXE-13316: Problem opening file %s (File Not Found).**

**Cause:** The file could not be opened because the file could not be found.

**Action:** Correct the file specification.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-13317: Problem opening file %s (Sharing violation).**

**Cause:** The file could not be opened because there has been a sharing violation.

**Action:** Close the file through other applications that are accessing it.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-13318: Problem opening file %s (Is a directory).**

**Cause:** The file could not be opened because it is directory.

**Action:** Correct the file specification.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-13319: Problem opening file %s, system error %s (Internal error).**

**Cause:** There was been an unknown error opening the file.

**Action:** Contact Oracle Support.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-13350: Error during network receive, system error %s**

**Cause:** There was system error during the networking receive.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-13351: Timeout during network receive, socket number %s**

**Cause:** There was timeout during the networking receive.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 16

**Type:** ERROR

---

**Impact:** Requests/Responses

**WXE-13365: Error during network send, system error %s**

**Cause:** There was system error during the networking send.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-13366: Timeout during network send, socket number %s**

**Cause:** There was timeout during the networking send.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-13380: Error during SSL handshake, system error %s**

**Cause:** There was system error during the SSL handshake.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-13381: Timeout during SSL handshake, socket number %s**

**Cause:** There was timeout during the SSL handshake.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-13382: File %s cannot be opened.**

**Cause:** The specified file could not be opened.

**Action:** Evaluate why the specified file cannot be opened. The file may not be located in the correct directory or permissions on the file may be incorrect. Correct the problem.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-13383: Unable to initialize DNS lookups**

**Cause:** Cannot use DNS for TCP/IP host resolution.

---

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-13400: parsing error of <!-- WEBCACHETAG--> and <!-- WEBCACHEEND--> at offset %d**

**Cause:** An invalid token was encountered in the <!-- WEBCACHETAG--> and <!-- WEBCACHEEND--> tags.

**Action:** Correct the syntax of the <!-- WEBCACHETAG--> and <!-- WEBCACHEEND--> tags at the specified location in the object.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-13500: Login Information missing for WTI key server \"%s\"**

**Cause:** A key server with the given server name is defined but no login (username, password) information is provided.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Please reconfigure WTI key server section to add the login information for this key server or remove this key server.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-13502: WTI Processor HTML parsing failure.**

**Cause:** A failure is reported by the HTML parser.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Validate this HTML page's syntax.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-13503: WTI HTML parser context creation failure.**

**Cause:** The system may be running low in memory.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Please increase the system memory.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-13504: WTI form descriptor creation failure.**

**Cause:** The system may be running low in memory.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Please increase the system memory.

---

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-13505: WTI processor failed in memory allocation.**

**Cause:** The system may be running low in memory.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Please increase the system memory.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-13508: The WTI processor failed to generate a form descriptor.**

**Cause:** A form descriptor cannot be generated in WTI processor.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Please check other form description generation error messages for detail.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-13509: The WTI processor failed to get a WTI session key.**

**Cause:** A WTI session key cannot be retrieved by the WTI processor.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Please check other messages to find out the specific reason for key retrieval failure.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-13540: WTI processor found request invalid.Error Descriptor:%s**

**Cause:** The cause should be shown by other more detailed messages.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-13541: WTI processor: request MAC verification failed.**

**Cause:** The cause should be shown by other more detailed messages.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-13570: WTI processor found unexpected request parameter ordering.**



---

**Cause:** The cause should be shown by other more detailed messages.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-13600: Assertion failed.**

**Cause:** Assertion is failed. Diagnostic information is printed in trace dump file.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Contact Oracle Support.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-13601: Signal SIGSEGV caught**

**Cause:** Signal SIGSEGV is caught. Diagnostic information is printed in trace dump file.

**Action:** Contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-13602: Signal SIGBUS caught**

**Cause:** Signal SIGBUS is caught. Diagnostic information is printed in trace dump file.

**Action:** Contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-13603: Signal SIGFPE caught**

**Cause:** Signal SIGFPE is caught. Diagnostic information is printed in trace dump file.

**Action:** Contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-13604: Signal SIGSEGV caught**

**Cause:** Signal SIGSEGV is caught. Diagnostic information is printed in trace dump file.

**Action:** Contact Oracle Support.

**Level:** 1

---

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-13606: Signal SIGABRT caught**

**Cause:** Signal SIGABRT is caught. Diagnostic information is printed in trace dump file.

**Action:** Contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-13704: Compression error in: %s**

**Cause:** A gzip library call failed.

**Action:** If the problem persists, contact Oracle Support.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-13705: Oracle Web Cache compresses object. Original size: %d bytes;**

**Compressed size: %d bytes.**

**Cause:** Normal trace behavior.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-13708: Compression is not yielding any benefit.**

**Cause:** Compression was not able to reduce the size of the object.

**Action:** Disable compression for this object..

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-13709: Compression disabled for invalid MIME type '%.\*s'; non-ascii or non-printable**

**Cause:** An invalid MIME type was identified. The MIME type either contained non-ascii characters, or contained non-printable (undisplayable) characters. Compression is disabled for this MIME type.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-13710: Compression disabled for invalid MIME type '%.\*s'; too large**

---

**Cause:** An invalid MIME type was identified. The MIME type was too large to be stored in the MIME type compression table. Compression is disabled for this MIME type.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-13720: Oracle Web Cache disables compression for %s due to a low rate: %d%%.**

**Cause:** Objects with this MIME type, file extension, or both, were compressed three times.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-13722: Compression policy for %s has expired. Re-instrumenting.**

**Cause:** Six hours have passed since the compression setting for this MIME type and file extension were set. As a result, the compression setting was reset.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-13730: Object will be compressed.**

**Cause:** No headers or policies disabled compression, so Oracle Web Cache compressed the object.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-13731: Object is too small to warrant compression.**

**Cause:** The requested object was too small to compress.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-13732: Compression disabled for this object by a Surrogate-control header.**

**Cause:** The Surrogate-Control header indicated that compression should be disabled.

**Action:** No action required.

**Level:** 1

---

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-13733: Compression disabled for this Site.**

**Cause:** An application-specific caching specified that compression should be disabled.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-13734: Compression disabled for this object by caching rule.**

**Cause:** A caching rule specified that compression should be disabled.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-13735: Compression is disabled because the browser has known issues.**

**Cause:** The browser was either Netscape version 4 or less, or it was Internet Explorer version 5.5 or less. These browsers have known issues.

**Action:** Upgrade the browser.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-13736: Compression is disabled because the browser does not support compression.**

**Cause:** The user's browser does not support compression.

**Action:** Upgrade the browser.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-13737: Compression is internally disabled for: %s.**

**Cause:** Compression for this object's MIME type or file extension is internally disabled.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-13738: Compression disabled because %s has a low compression rate.**

**Cause:** The compression rate on this MIME type, file extension, or both, was poor. Therefore Oracle Web Cache is disabling compression for this type.

**Action:** No action required.

---

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-13817: I/O Logging enabled; using file %s**

**Cause:** As specified, I/O Logging has been enabled using the specified file.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-13818: I/O Logging disabled; file %s could not be accessed**

**Cause:** As specified, I/O Logging has been enabled using the specified file.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-13916: Optimizer failure on pattern '%.\*s' - trying original '%.\*s'**

**Cause:** The optimized regular expression failed to compile; an attempt was made to compile the original supplied (unoptimized) expression.

**Action:** No action required.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-14000: unknown internal error**

**Cause:** error number is properly set

**Action:** check which module is not setting the error number

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-14001: bad arguments**

**Cause:** bad request

**Action:** check the code which is sending wrong argument to the calling function

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-14002: Error while sending the request to origin server (id=%d) %s:%d**

**Cause:** The request to the origin server failed.

**Action:** Ensure that the origin server is running.

**Level:** 1

---

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14003: Error while receiving response from the origin server (id=%d) %s:%d**

**Cause:** Oracle Web Cache was unable to receive a response from the origin server.

**Action:** Ensure that the origin server is running.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14004: HTTP status code error**

**Cause:** The origin server returned a non-HTTP status code.

**Action:** Check the origin server to determine what application is sending the response.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14005: Content-Type buffer is too small**

**Cause:** The buffer pool memory was not sufficient.

**Action:** Adjust the maximum individual header size limit in the Security page of Fusion Middleware Control. If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14006: SSL handshake with origin server (id=%d) %s:%d fails.**

**Cause:** The SSL handshake between Oracle Web Cache and the origin server failed.

**Action:** Check certificate configuration on the origin server.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14007: Connect request terminates.**

**Cause:** The connection request to the origin server was terminated.

**Action:** If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14008: Create request fails.**

**Cause:** Oracle Web Cache failed to create a request to the origin server.

**Action:** If the problem persists, contact Oracle Support.

**Level:** 1

---

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14009: Header operation fails.**

**Cause:** Oracle Web Cache could not write to the HTTP response header from the origin server. This occurs if the Oracle Web Cache computer is experiencing a system memory problem.

**Action:** If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14010: Invalid authentication credentials for proxy server**

**Cause:** The user name and password for the proxy server failed.

**Action:** Correct the user name and password in the Origin Servers page of Fusion Middleware Control.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14011: Proxy tunnel authentication required**

**Cause:** The user name and password for the proxy server failed.

**Action:** Correct the user name and password in the Origin Servers page of Fusion Middleware Control.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14012: Bad response from proxy tunnel**

**Cause:** The proxy tunnel response was incorrect.

**Action:** Check the proxy server configuration and setup.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14013: Send request to origin server (id=%d) %s:%d times out.**

**Cause:** The request to the origin server exceeded the network timeout limit.

**Action:** If the problem persists, adjust the network timeout between Oracle Web Cache and the origin server in the Resource Limits page of Fusion Middleware Control.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14014: Receive request from origin server (id=%d) %s:%d timed out.**

**Cause:** The response from the origin server exceeded the network timeout limit.

---

**Action:** If the problem persists, adjust the network timeout between Oracle Web Cache and the origin server in the Resource Limits page of Fusion Middleware Control.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14015: Browser terminates connection; the request to the origin server is terminated.**

**Cause:** The browser terminated its connection. As a result, Oracle Web Cache terminated its connection to the origin server.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14016: Connection to origin server (id=%d) %s:%d fails.**

**Cause:** The origin server is down.

**Action:** Check the origin server.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14017: Connection to origin server times out.**

**Cause:** The connection to the origin server exceeded the network timeout limit.

**Action:** If the problem persists, adjust the network timeout between Oracle Web Cache and the origin server in the Resource Limits page of Fusion Middleware Control.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14018: Socket creation fails for origin server.**

**Cause:** The Oracle Web Cache computer has run short of system resources.

**Action:** If the problem persists, increase the Maximum Incoming Connections setting in the Resource Limits page Fusion Middleware Control.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14019: Dynamic origin server DNS failure**

**Cause:** The DNS lookup for the ESI provider site failed, because either the site was down or does not exist.

**Action:** Ensure that the ESI provider site is operational. If it is, check the site configuration in the Sites page of Fusion Middleware Control.



---

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14020: Origin server rejects queue entry.**

**Cause:** The queue to the origin server was full, resulting in the new request not being accepted.

**Action:** If the problem persists, increase the capacity for the origin server in the Origin Servers page of Fusion Middleware Control.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14021: Capacity, as set by Web Cache, is exceeded for all origin servers that are available for processing this request.**

**Cause:** Oracle Web Cache was unable to forward the request to the origin server, because the origin server reached its capacity and queue limit.

**Action:** If the problem persists, increase the capacity for the origin server in the Origin Servers page of Fusion Middleware Control.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14022: Load balancing and failover functionality fails.**

**Cause:** All of the origin servers were down. Oracle Web Cache will continue to poll the origin server until they are back online.

**Action:** Check the state of the origin servers.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14023: No origin server is running.**

**Cause:** All communication to the origin servers has failed. Oracle Web Cache will continue to poll the origin server until they are back online.

**Action:** Check the state of the origin servers.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14024: Dynamic origin server is not allowed for request.**

**Cause:** The request was for a virtual host site. DNS discovery of origin servers is only permitted for ESI provider sites.

**Action:** Check the site configuration in the Sites page of Oracle Enterprise Manager or Site Definitions and Site-to-Server Mapping page of Fusion Middleware Control.

**Level:** 1

---

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14025: Dynamic connection to origin server (id=%d) %s:%d fails.**

**Cause:** Oracle Web Cache received the DNS lookup result for the ESI provider site, but was unable to connect to the site.

**Action:** Check that the ESI provider site is operational.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14026: Out of memory**

**Cause:** Oracle Web Cache is running out of memory.

**Action:** No action required.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-14027: Connection request to origin server (id=%d) %s:%d times out.**

**Cause:** The connection between Oracle Web Cache and the origin server timed out.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14028: incomplete header**

**Cause:** The HTTP response from the origin server did not contain a properly formatted HTTP header.

**Action:** Check the application sending the response.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14029: invalid header**

**Cause:** The HTTP header response from the origin server contained an invalid field.

**Action:** Check the application sending the response.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14030: Single response header is too long.**

**Cause:** Origin Server is sending longer header than Oracle Web Cache is expecting.

**Action:** No Action required

---

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-14031: Total header length is too long**

**Cause:** Origin Server is sending longer headers than Oracle Web Cache is expecting.

**Action:** Check the Origin Server setting.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-14032: Buffer finished before \ is found.**

**Cause:** The response from the origin server was not properly formatted.

**Action:** If the problem persists, check the application sending the response.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14033: Chunk length exceeded more 256 digits.**

**Cause:** Origin Server is sending wrong chunking length header than specified in HTTP specification.

**Action:** Check the Origin Server setting.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-14034: Network %.\*s during origin server %.\*s (details: internal=%.\*s system=%.\*s)**

**Cause:** A network operation failure was encountered between the origin server and Oracle Web Cache, so the request could not be completed.

**Action:** Check network status on the Oracle Web Cache host machine.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14035: strtol utility returned an error.**

**Cause:** Internal string function failed.

**Action:** No action required.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-14036: time overflow**

**Cause:** Invalid time string from Origin Server

---

**Action:** Check the Origin Server configuration setting

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14037: illegal time format**

**Cause:** The creation time received from the origin server was for a time in the future.

**Action:** Check the application sending the response.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14038: invalidation operation**

**Cause:** Internal error

**Action:** no action required

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-14039: HTTP response not found**

**Cause:** An HTTP response from the origin server was not found.

**Action:** Check the application sending the response.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14040: overflow**

**Cause:** Could be wrong time format

**Action:** no action required

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses

**WXE-14041: invalid format**

**Cause:** The response contained an invalid time format or inversion of an integer.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14044: Unexpected EOF while reading HTTP response-header.**

**Cause:** Connection prematurely closed by origin server.

**Action:** No action required.

---

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-14045: Error Parsing Chunk Length for %.\*s%.\*s.**

**Cause:** Incorrect chunk length

**Action:** No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-14047: Oracle Web Cache encounters an invalid HTTP response.**

**Cause:** An HTTP response from the origin server contained invalid contents. For example, the response indicated chunked contents but the response contained no chunks.

**Action:** Check the application sending the response.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-14050: The request is granted with view permission for the cached object.**

**Cause:** In response to a security validation request from WebCache on behalf of the request, the origin server responded with "304 Not Modified", with the Surrogate-Control: view-granted token. The cached object will be used to serve the request.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-14051: The request is validated with cached version %.\*s**

**Cause:** In response to a version validation request from Oracle Web Cache on behalf of the request, the origin server responded with "304 Not Modified", specifying the cached version in the Surrogate-Control: version token to be served to the client.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-14052: New content is received from the origin server in response to a validation request from WebCache.**

**Cause:** In response to a security or version validation request from Oracle Web Cache on behalf of the request, the origin server responded with new content. The cached objects will be updated accordingly.

**Action:** No action required.

---

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-14056: Origin server error: empty version string in Surrogate-Control in the response.**

**Cause:** The response contains an empty Surrogate-Control: version string. This will be treated as an invalid response, and an error will be sent to the client.

**Action:** Check that the origin server has proper support for version validation based caching.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14059: Object validation aborted.**

**Cause:** The response will not be used to update the validation-required entry in the cache because it was determined that it is not cacheable.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-14060: The response contains Surrogate-Control: secure-view, indicating the object requires security validation for all cache hits.**

**Cause:** The Surrogate-Control header contains a secure-view token indicating that the cached entry requires security validation for all hits.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-14061: The response contains the Surrogate-Control: version token with value %.\*s, indicating the object requires version validation for all cache hits.**

**Cause:** The Surrogate-Control header contains a Surrogate-Control: version token indicating that the cached entry requires version validation for all hits.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-14062: The validation-required cache entry is updated with new content for an existing version %.\*s**

**Cause:** The complete response for an existing version of the validation-required cache entry was successfully received and the version in the entry is updated with the new response.

**Action:** No action required.

---

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-14063: The validation-required cache entry is updated with content for a new version %.\*s**

**Cause:** The complete response for a new version of the validation-required object was successfully received and the cache entry is updated with the new response.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-14064: Failed to insert the new version %.\*s to the validation-required cache entry as the maximum allowed versions is reached for the entry, and none of the existing versions can be removed.**

**Cause:** The cache entry already contains the maximum allowed number of version objects, and all of them are currently being updated, so the new version received can not be added to the entry.

**Action:** Adjust the maximum allowed version objects per cache entry if you prefer to have all versions cached.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14066: Origin server denied view permission for the request.**

**Cause:** In response to a security validation request, or Oracle Single Sign-On authentication request from Oracle Web Cache on behalf of the request, the origin server responded with "401 Unauthorized", meaning the user does not have view permission for the requested object in cache.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-14067: Origin server error: missing Surrogate-Control: view-granted token in the response for a security validation request from WebCache.**

**Cause:** In response to a security validation request from Oracle Web Cache on behalf of the request, the origin server responded with "304 Not Modified", but without the Surrogate-Control: view-granted token required to indicate that an authorization check has been performed. This will be treated as an invalid response, and an error will be sent to the client.

**Action:** Check that the origin server has proper support for security validation based caching.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

---

**WXE-14068: Origin server error: incorrect Surrogate-Control: version string in the response for a version validation request from WebCache.**

**Cause:** In response to a version validation request from Oracle Web Cache on behalf of the request, the origin server responded with "304 Not Modified", but without the Surrogate-Control: version token required to indicate that version check has been performed, or with an incorrect version token that does not match any versions specified in the request. This will be treated as an invalid response, and an error will be sent to the client.

**Action:** Check that the origin server has proper support for version validation based caching.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14070: Origin server error: unexpected 304 response.**

**Cause:** In response to regular request from Oracle Web Cache with no validation clause, the origin server returned "304 Not Modified". This will be treated as an invalid response, and an error will be sent to the client.

**Action:** Check that the origin server has proper support for validation based caching.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14071: Unexpected EOF while reading HTTP response-body.**

**Cause:** Connection prematurely closed by origin server.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14072: The Location header of the 302 response is not found or is empty.**

**Cause:** The origin server response was a 302 redirect response, but the required Location header was not found or was empty.

**Action:** Check the application sending the response.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14130: [site #%.\*s - %s][filter type: %s][rule #%.\*s%s]%.\*s[action: allow]**

**Cause:** The request matched a request-filtering rule for a filter type and the action specified for a rule match was allow. Request was allowed for this filter type. The other filter types, if any, were checked.

**Action:** No action required, unless this action is not the desired behavior.

**Level:** 1

**Type:** TRACE



---

**Impact:** Requests/Responses

**WXE-14131: [site #%. \*s - %s][filter type: %s][rule #%. \*s%s]%. \*s[action: allow - MONITOR ONLY]**

**Cause:** The request matched a request-filtering rule for a filter type and the action specified for a rule match was allow. However, the rule was set to be in monitor-only mode, so the statistics for the rule were updated, but otherwise the rule was treated as disabled. The other rules, if any, for this filter type were checked.

**Action:** No action required, unless this action is not the desired behavior. This message is for informational purposes.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-14132: [site #%. \*s - %s][filter type: %s][rule #%. \*s%s]%. \*s[action: deny - %s]**

**Cause:** The request matched a request-filtering rule for a filter type and the action specified for a rule match was deny. The request was denied.

**Action:** No action required, unless this action is not the desired behavior.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14133: [site #%. \*s - %s][filter type: %s][rule #%. \*s%s]%. \*s[action: deny - %s - MONITOR ONLY]**

**Cause:** The request matched a request-filtering rule for a filter type and the action specified for a rule match was deny. But the rule is in monitor-only mode, so the statistics for the rule were updated, but otherwise the rule was treated as disabled. The other rules, if any, for this filter type were checked.

**Action:** No action required, unless this action is not the desired behavior. This message is for informational purposes.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-14143: Request filtering needs to check the POST body, but the POST body size exceeds the configured maximum. Oracle Web Cache returns a bad request error response.**

**Cause:** Oracle Web Cache received an HTTP request with a POST body which request filtering must check, but the POST body size exceeds the maximum configured POST body size. Oracle Web Cache returns a bad request error response.

**Action:** If the problem persists and rejecting the request is not acceptable, increase the configuration setting for the maximum POST body size if request filtering is needed in the Oracle Web Cache configuration. You configure this setting in the Security page (Properties > Security) of Oracle Web Cache Manager.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

---

**WXE-14147: [site #%. \*s - %s][filter type: %s][action: no match on any non-MONITOR-ONLY rule, so check other filters]**

**Cause:** The request did not match any request-filtering rule for the Privileged IP filter type which is not a monitor-only rule. Therefore, check the other request filters for this request.

**Action:** No action required, unless this action is not the desired behavior. This message is for informational purposes.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-14153: The request is from a Privileged IP address, so other request filter checks are bypassed.**

**Cause:** The normal request filtering checks were bypassed for this request, because the request is coming from a privileged IP.

**Action:** No action required, unless this action is not the desired behavior.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-14200: One or more sites are ACL-protected. Initializing secure caching tables.**

**Cause:** Normal notification. At least one site was configured as ACL-protected site. Oracle Web Cache will enable secure caching for those sites.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-14201: XML parser for WebDAV ACL initializes successfully.**

**Cause:** Normal notification. XML parser for WebDAV ACL was initialized successfully.

**Action:** No action required.

**Level:** 1

**Type:** NOTIFICATION

**Impact:** Requests/Responses

**WXE-14210: Invalid authorization header (%s)**

**Cause:** The authorization header in the request lacked the necessary items or was invalid.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14213: The requested object is ACL-protected. Starting ACL evaluation.**

---

**Cause:** The client requested an object from an ACL-protected site. Therefore, an ACL evaluation was started.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-14214: Oracle Web Cache does not have fresh copies of all ACLs. ACL evaluation terminates.**

**Cause:** Required ACL object was missing, stale or in update status. Therefore, ACL evaluation was terminated.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-14215: Oracle Web Cache does not have all the necessary information for the requesting user (%s). ACL evaluation terminates.**

**Cause:** The user/group table did not contain an entry of the user or the user's group membership was not updated yet. Therefore, ACL evaluation was terminated.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-14216: ACL evaluation completes. Access granted to the user (%s).**

**Cause:** The user has read privilege for the requested URL.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-14217: ACL evaluation completes. Access denied for the user (%s).**

**Cause:** The user does not have read privilege for the requested URL.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-14221: The response does not contain a valid X-Oracle-Current-User header.**

**Cause:** The response does not contain the X-Oracle-Current-User header or the header is invalid.

**Action:** No action required.

**Level:** 1

---

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14225: The insertion of user (%s) to the user/group table fails.**

**Cause:** Oracle Web Cache tried to insert a user entry for the user but failed.

**Action:** No action required.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-14229: A user and a group have the same principal URL (%s).**

**Cause:** A group had the same principal URL as a user.

**Action:** Check the origin server's user and group settings.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14233: Propfind request for fetching the password verifier of user (%s) is composed.**

**Cause:** Propfind request for the password verifier of the requesting user was composed.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-14234: Propfind request for fetching the group-membership of user (%s) is composed.**

**Cause:** Propfind request for the group membership of the requesting user was composed.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-14235: Propfind request for ACL HREF or ancestor ACL HREFs of the resource (%s) is composed.**

**Cause:** Propfind request for ACL HREF, ancestor ACL HREFs, or both ACL HREF and ancestor HREFs was composed.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-14236: Request for fetching ACL (%s) is composed.**

**Cause:** Propfind request for fetching ACL object was composed.

---

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-14240: Starting post-processing of user password verifier.**

**Cause:** Starting post-processing of password verifier.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-14241: Starting post-processing of user groupmembership.**

**Cause:** Starting post-processing of user groupmembership.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-14242: Starting post-processing of resource ACL HREF.**

**Cause:** Starting post-processing of resource ACL HREF.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-14243: Starting post-processing of ancestor ACL HREFs.**

**Cause:** Starting post-processing of ancestor ACL HREFs.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-14244: Starting post-processing of both resource and ancestor ACL HREFs.**

**Cause:** Starting post-processing of both resource and ancestor ACL HREFs.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-14245: Starting post-processing of ACL object.**

**Cause:** Starting post-processing of ACL object.

**Action:** No action required.

---

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-14246: Post processing successfully completes.**

**Cause:** Post processing of fetcher response was completed successfully.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-14250: Lexical analysis of XML response fails.**

**Cause:** Transitioned to ERROR state in the lexical transition matrix. This condition might be caused by incorrect definitions of state variables or incorrect transition matrix.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14251: The syntax of the XML response is incorrect. Syntax analysis fails (error no: %d).**

**Cause:** The syntax of XML response is wrong and building a syntax tree failed.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14252: The XML response has semantic error or the table/cache update fails.**

**Cause:** There might be two possible reasons: (1) The XML response has semantic errors, so the post-processing function could not understand the response and extract necessary authentication data or ACL data from the response. (2) The post-processing function received all the data from the response, but failed upon updating password verifier, user groupmembership, ACL HREFs, or ACL object.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14260: No user groupmembership inserted. Data validation fails.**

**Cause:** Oracle Web Cache failed in post-processing and insertion of user group membership. Possible reasons include but may not be limited to: 1) Server did not send a valid response. 2) There is syntax or semantic error in the response. 3) The special Oracle Web Cache user was not configured to have sufficient privileges.

**Action:** Check related server configuration and resources.

**Level:** 1

---

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14261: The HREF list is incomplete. Data validation fails.**

**Cause:** Oracle Web Cache could not insert all resource ACL HREF and ancestor ACL HREFs to the HREF list. Possible reasons include but may not be limited to: 1) Server did not send complete HREF list. 2) There is syntax or semantic error in the response. 3) The special Oracle Web Cache user was not configured to have sufficient privileges.

**Action:** Check related server configuration and resources.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14262: The HREF list is empty. Data validation fails.**

**Cause:** Oracle Web Cache could not get the HREFs from the server or the response has syntax/semantic error. Possible reasons include but may not be limited to: 1) Server did not send valid response. 2) There is syntax or semantic error in the response. 3) The special Oracle Web Cache user was not configured to have sufficient privileges.

**Action:** Check related server configuration and resources.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14263: Some ACL objects have not been parsed. Data validation fails.**

**Cause:** There is a syntax or semantic error in the ACL object. Oracle Web Cache could not parse it.

**Action:** Check server ACL objects.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14300: Empty resource HREF header or bad HREF format (%s).**

**Cause:** The server sent an empty X-Oracle-Resource-Acl-Href header or the format of the HREF string is invalid.

**Action:** Check the X-Oracle-Resource-Acl-Href header in the origin server's response.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-14301: Empty resource ancestor HREF header or bad ancestor href format (%s).**

**Cause:** The server sent an empty X-Oracle-Ancestor-Acl-Hrefs header or the format of the ancestor HREF string is invalid.

**Action:** Check the X-Oracle-Ancestor-Acl-Href header in the origin server's response.

---

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-15000: Requested resource has been moved permanently.**

**Cause:** The requested resource was assigned a new permanent URI. Any future references to this resource should use the returned URI.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-15001: Requested resource has been moved temporarily.**

**Cause:** The requested resource temporarily resided under a different URI.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-15002: Oracle Web Cache generates an HTTP 200 OK status code for a request with an Oracle-Web-Cache-Ping header.**

**Cause:** The request completed successfully.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-15003: Cache entry requires validation. The request will be forwarded to the origin server with a validation clause added.**

**Cause:** Cache entry is marked to require validation. Oracle Web Cache will add a conditional validation header "Oracle-Oracle Web Cache-Validate" to the request, listing the content information it has in the cache, and forward the modified request to the origin server. The origin server can respond with a full response, or a 304 Not Modified response to indicate to Oracle Web Cache that certain cached content can be used to service the request.

**Action:** No action required

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-15004: Invalid regular expression found in User-Agent remap rule. %s**

**Cause:** The remap rule contained an invalid regular expression that could not be compiled.

**Action:** Correct the regular expression in the remap rule.

**Level:** 1

**Type:** ERROR



---

**Impact:** Requests/Responses

**WXE-15005: Parse error on URL: %.\*s - invalid URL but continuing with processing**

**Cause:** The input URL was invalid. Oracle Web Cache continued processing, but the origin server probably returned a bad request (400) response.

**Action:** Ensure that the URL uses valid HTTP syntax.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-15006: Problem normalizing '%.\*s'; continuing with original value**

**Cause:** Attempt to normalize the input string failed.

**Action:** Ensure user supplied URI or host name is properly HTTP encoded.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-15101: Address resolution of Oracle Web Cache's listening endpoint \"%s\" fails.**

**Cause:** There was a problem in DNS.

**Action:** Check DNS configuration on the local machine.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-15102: CRL directory does not exist.**

**Cause:** CRL is enabled for one of the listening endpoints, but the CRL directory does not exist.

**Action:** Contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Configuration

**WXE-15300: Request for cached document is denied**

**Cause:** The request sender was not authorized to access the object.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-15400: An orcl\_wx\_repost parameter is found with a non-GET request.**

**Cause:** The request URL contained the special orcl\_wx\_repost parameter, but the request method was not a GET. The parameter will be stripped and the request processed as a regular request.

**Action:** No action required.

---

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-15402: The orcl\_wx\_repost parameter is invalid.**

**Cause:** The request URL contained the special orcl\_wx\_repost parameter, but its value was empty or invalid. It will be stripped from the URL, the request will be converted to a POST request with an empty body, and an additional request header Oracle-Oracle Web Cache-RePOST with the special value of UID=failed-restore will be sent to the origin server.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-15403: Forwarding the restore POST request to the owner cache of the POST data**

**Cause:** This cache was not the owner of the POST data specified by the request. The request will be forwarded as is to the owner cache.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-15404: Failed to find POST data with key %.\*s.**

**Cause:** The POST data entry specified by the request was not found in the cache. It is either expired or the cache key was invalid. The orcl\_wx\_repost parameter will be stripped from the URL, the request will be converted to a POST request with an empty body, and an additional request header Oracle-Oracle Web Cache-RePOST with the special value of UID=failed-restore will be sent to the origin server.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-15405: POST data successfully restored.**

**Cause:** Cache lookup of the POST data entry specified by the request was successful. The request has been converted to POST with the looked up POST content. The URL parameter orcl\_wx\_repost will be stripped and the restored request will be forwarded to the origin server.

**Action:** No action required.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-15406: The orcl\_wx\_sid parameter is invalid.**

---

**Cause:** The request URL contained the special orcl\_wx\_sid parameter, but its value was empty or invalid. It will be stripped from the URL, and the request will be treated as it would be without the parameter.

**Action:** No action required.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-17001: A duplicate POST data cache insertion is found with key %.\*s. POST data cache insertion fails.**

**Cause:** An existing POST data cache entry existed with the same key as the current one.

**Action:** Check the origin server to ensure no duplicate keys are sent for POST data records.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-17005: POST data cache insertion failed with key %.\*s because the POST data is too large.**

**Cause:** POST data was too large.

**Action:** Edit webcache.xml and find the POSTBODYCACHE element under the GENERAL element. Increase the MAXCACHEABLESIZE attribute to the desired value.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-17101: No matching cookies are found for cookie caching.**

**Cause:** No cacheable cookies were found in the response.

**Action:** See the Oracle Access Manager Integration Guide.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-17102: A duplicate cookie cache insertion is found with key %.\*s. Cookie cache insertion fails.**

**Cause:** An existing cookie cache entry existed with the same key as the current one. This could be caused by concurrent requests from the same browser.

**Action:** See the Oracle Access Manager Integration Guide.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-17110: Previously saved cookies are added to the request.**

---

**Cause:** A cookie record associated with the user was found and the cookies saved in the record were added to the request.

**Action:** See the Oracle Access Manager Integration Guide.

**Level:** 1

**Type:** TRACE

**Impact:** Requests/Responses

**WXE-17112: Cookie cache is enabled with no SSL enabled listen ports for browser requests.**

**Cause:** The cookie cache feature only works for requests made over SSL connections. The configuration contained the switch that enables cookie caching but no listen ports for browser requests are SSL enabled.

**Action:** See the Oracle Access Manager Integration Guide.

**Level:** 16

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-17113: Oracle Web Cache encountered an error while obtaining SSL session ID for cookie cache operations. NZE-%d**

**Cause:** While trying to retrieve the SSL session ID needed by the cookie cache, an error occurred. Cookie cache operations for this request will not succeed.

**Action:** See the Oracle Access Manager Integration Guide.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-19000: Audit initialization failed. Oracle Web Cache starts with audit logging disabled.**

**Cause:** The audit library failed to initialize.

**Action:** If the problem persists, contact Oracle Support.

**Level:** 1

**Type:** WARNING

**Impact:** Requests/Responses

**WXE-20101: Open socket fd=%d exceeded FDArr\_Size %d.**

**Cause:** Potential file descriptor leakage.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Contact Oracle Support.

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-20150: Failure in scheduling asynchronous task: %s.**

**Cause:** Potential memory shortage. Note: This is for all asynchronous functions.

**Action:** This message is no longer used as of Oracle Fusion Middleware 11g. Contact Oracle Support.

---

**Level:** 1

**Type:** ERROR

**Impact:** Requests/Responses

**WXE-21271: Member cache ID is invalid (id=%d), %s.**

**Cause:** This is a potential logic error. Param %s Desiree where the error happens

**Action:** Contact Oracle Support.

**Level:** 8

**Type:** INTERNAL\_ERROR

**Impact:** Requests/Responses



---

## XDF-10001 to XDF-10564

**XDF-10001: BstrapObject::readInputSXML(): Issue with bootstrap config file.**

**Cause:** Incorrect Bootstrap config file

**Action:** Provide a correct Bootstrap config file

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10002: BstrapObject::readFileToGetCommand(...): File {0} not found in the jar.**

**Cause:** Missing a file in the applxdf.jar

**Action:** Check if the applxdf.jar is an valid jar

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10003: There was an error during XDF deployment(standalone=Y),check the log for detail**

**Cause:** An error in XDF deployment

**Action:** Check the log for detail, fix the issue

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10004: There was an error running the SQL/PLSQL scripts, check the log for detail**

**Cause:** An error running the SQL/PLSQL scripts

**Action:** Check the log for detail, fix the issue

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10005: There was an error during XDF deployment(standalone=N),check the log for detail**

**Cause:** An error in XDF deployment

**Action:** Check the log for detail, fix the issue

---

**Level: 1**  
**Type: ERROR**  
**Impact: Application Diagnostics**  
**XDF-10006: BstrapObject::getConnection(): Could Not Get DB Connection**  
**Cause:** An error in database connection  
**Action:** Fix database connection errors

**Level: 1**  
**Type: ERROR**  
**Impact: Application Diagnostics**  
**XDF-10007: DataCollect::getMVLogTableSpace(...): Table space is null.**  
**Cause:** Table space is null  
**Action:** Fix Table space error

**Level: 1**  
**Type: ERROR**  
**Impact: Application Diagnostics**  
**XDF-10008: DBObjct::readInputSXML: Null or Empty XML Document.**  
**Cause:** Invalid SXML file  
**Action:** Use an valid SXML object file.

**Level: 1**  
**Type: ERROR**  
**Impact: Application Diagnostics**  
**XDF-10010: DBObjct::stripRowTag(...): SXML Object File is null!**  
**Cause:** Invalid SXML file  
**Action:** Use an valid SXML Object file

**Level: 1**  
**Type: ERROR**  
**Impact: Application Diagnostics**  
**XDF-10011: DBObjct::stripRowTag(...): Could not get Object File Document Root!**  
**Cause:** Incorrect SXML file format  
**Action:** Fix SXML file errors or select a correct SXML file

**Level: 1**  
**Type: ERROR**  
**Impact: Application Diagnostics**  
**XDF-10012: DBObjct::stripRowTag(...): Invalid DB Object File Format!**  
**Cause:** Incorrect SXML file format  
**Action:** Fix SXML file errors or select a correct SXML file

**Level: 1**  
**Type: ERROR**



---

**Impact:** Application Diagnostics

**XDF-10013: DBObject::executeDDLStmt: The statement is invalid and could not be executed!**

**Cause:** An invalid DDL statement

**Action:** Check and fix Object file

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10014: DBObjectComparision::doCompare(): The object type {0} is not recognized.**

**Cause:** Incorrect object type

**Action:** Fix object type in the SXML file

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10015: DBUtil::executeConsDDLSt: No connection available!**

**Cause:** NO database connection

**Action:** Fix database connection errors

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10016: DBUtil::executeConsDDLSt: The statement is invalid and could not be executed!**

**Cause:** An invalid ConsDDL statement

**Action:** Fix the SXML file

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10017: The statement is invalid and could not be executed!**

**Cause:** An invalid DDL statement

**Action:** Fix the SXML file

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10019: MViewObject::getRemapParameters(): Could not retrieve tablespace information for object {0}.**

**Cause:** May be caused by an invalid tspaceconfig file

**Action:** Check if a valid tspaceconfig file in the applxdf.jar

**Level:** 1

---

**Type:** ERROR  
**Impact:** Application Diagnostics  
**XDF-10020: MVLogObject::getRemapParameters(): Could not retrieve tablespace information for object {0}.**  
**Cause:** Error in getting tablespace from target database  
**Action:** XDF team debugs  
**Level:** 1  
**Type:** ERROR  
**Impact:** Application Diagnostics  
**XDF-10021: BstrapObject::executeDDLSt: No connection available!**  
**Cause:** NO database connection  
**Action:** Fix database connection errors  
**Level:** 1  
**Type:** ERROR  
**Impact:** Application Diagnostics  
**XDF-10022: DBUtil::returnsRecord(...): No connection available!**  
**Cause:** NO database connection  
**Action:** Fix database connection errors  
**Level:** 1  
**Type:** ERROR  
**Impact:** Application Diagnostics  
**XDF-10023: DBUtil::getConsFromDB(...): No connection available!**  
**Cause:** NO database connection  
**Action:** Fix database connection errors  
**Level:** 1  
**Type:** ERROR  
**Impact:** Application Diagnostics  
**XDF-10024: DBUtil::dropConst(...): No connection available!**  
**Cause:** NO database connection  
**Action:** Fix database connection errors  
**Level:** 1  
**Type:** ERROR  
**Impact:** Application Diagnostics  
**XDF-10025: DBUtil::getConsColsFromDB: No connection available!**  
**Cause:** NO database connection  
**Action:** Fix database connection errors  
**Level:** 1  
**Type:** ERROR

---

**Impact:** Application Diagnostics

**XDF-10026: DBUtil::isConsNameInDB: No connection available!**

**Cause:** NO database connection

**Action:** Fix database connection errors

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10027: IndexObject::renameIndex(...):No DB connection available.**

**Cause:** NO database connection

**Action:** Fix database connection errors

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10028: IndexObject::isIntable(): No DB connection available.**

**Cause:** NO database connection

**Action:** Fix database connection errors

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10029: IndexObject::isUniqueMatch:No DB connection available.**

**Cause:** NO database connection

**Action:** Fix database connection errors

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10031: Value exceed {0} characters.**

**Cause:** Too many characters or value to large

**Action:** Change value within the boundary

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10032: {0}={1}**

**Cause:** Too many characters or value too large

**Action:** Change value within the boundary

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10033: The format for "{}" pair is incorrect. Please check.**

---

**Cause:** Parameters incorrect errors

**Action:** Fix incorrect parameters

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10034: Argument {0} is not recognized**

**Cause:** Incorrect parameters in XdfSchemaDeploy

**Action:** Remove an incorrect parameters from command line

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10036: No Object Mode be provided!**

**Cause:** No Object Mode be provided

**Action:** Provide Object Mode in the command line

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10037: Invalid Object Mode!**

**Cause:** Invalid Object Mode

**Action:** Provide the correct Object Mode

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10038: No JDBC DB Address be provided!**

**Cause:** No JDBC Address is provided

**Action:** Provide JDBC address

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10039: No JDBC Protocol be provided!**

**Cause:** No JDBC Protocol is provided

**Action:** Provide JDBC Protocol

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10040: No Apps User Name be provided!**

**Cause:** No Apps User Name is provided

**Action:** Provide Apps User Name

---

**Level: 1**

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10041: No Owner User Name be provided!**

**Cause:** No Owner User Name is provided

**Action:** Provide Owner User Name

**Level: 1**

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10042: Object File Name is blank.**

**Cause:** Object File Name is blank

**Action:** Provide the Object File Name.

**Level: 1**

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10043: Editioning View option contradicts with stand alone option!**

**Cause:** Editioning View option can only be with standalone=n.

**Action:** Re-enter the options.

**Level: 1**

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10046: IO Exception when getting password.**

**Cause:** IO Exception when getting password.

**Action:** Try again

**Level: 1**

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10501: Error on getting the revoke Grants statement: {0}**

**Cause:** UNKNOWN

**Action:** Follow the error message detail to debug

**Level: 1**

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10502: Error on giving grant to the role: {0}**

**Cause:** UNKNOWN

**Action:** Follow the error message detail to debug

**Level: 1**

**Type:** ERROR

---

**Impact:** Application Diagnostics

**XDF-10504: Error on revoking Grants: {0}**

**Cause:** UNKNOWN

**Action:** XDF team debugs

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10519: XDFLogger::log: Date format error.**

**Cause:** Date format error

**Action:** XDF team debugs

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10520: XDFLogger::levelMap: Level number format error.**

**Cause:** Incorrect level number

**Action:** XDF team debugs

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10521: ViewObject::dropView: Error while dropping view {0}.{1}**

**Cause:** Cannot drop a view

**Action:** Check drop a view permission

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10525: XdfSchemaDeploy::applyXDF: The Role deployment NOT in a valid context.**

**Cause:** Role deployment not in schema separation context

**Action:** Make sure the deployment run in schema separation option

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10526: XdfSchemaDeploy::applyXDF: The object type {0} is not recognized.**

**Cause:** Incorrect object type

**Action:** FIX object type and re-run

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

---

**XDF-10531: XMLUtil::processorSetParam: Invalid value type in the hash table.**

**Cause:** XMLUtil::processorSetParam: Invalid value type

**Action:** XDF team debugs

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10535: Tablespace config file is null/empty. Exit the program ...**

**Cause:** Tablespace config file is null/empty

**Action:** Check and use an valid applxdf.jar

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10536: Invalid Tablespace Config File Format!**

**Cause:** Invalid Tablespace Config File Format

**Action:** Fix Tablespace config file and re-run

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10537: TspaceConfig::loadTspaceConfig(): Implicit classification not in correct format.**

**Cause:** TspaceConfig: Implicit classification not in correct format

**Action:** Fix Tablespace config file and re-run

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10538: TspaceConfig::loadTspaceConfig(): Type-Value classification not in correct format.**

**Cause:** TspaceConfig:Type-Value classification incorrect

**Action:** Fix Tablespace Type-Value classification and re-run

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10539: SQL Error: Missing FND\_CLEANUP\_PKG package in the target database.**

**Cause:** Missing FND\_CLEANUP\_PKG package in the target database

**Action:** Re-run bootstrap mode to install FND\_CLEANUP\_PKG package

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

---

**XDF-10546: Unable to find Application Short Name.**

**Cause:** No Application Short Name defined in the Object file

**Action:** Add Application Short Name

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10548: TableObject::getRemapParameters: Could not retrieve tablespace information for table {0}**

**Cause:** Error in the process of getting tablespace information from config file

**Action:** XDF team debugs

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10549: Tablespace type from DB is null.**

**Cause:** Incorrect Tablespace type

**Action:** Check if the tablespace exist in target DB.

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10561: TableComparison::doObjectCmp:Executing comment statement: {0}**

**Cause:** Failed executing comment statement

**Action:** Fix SXML file

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10562: Table SXML clob to xml doc processing error: {0}**

**Cause:** UNKNOWN

**Action:** Follow the error message detail to debug

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10563: Alter Table Exception: {0}**

**Cause:** Error in the alter table process, reason unknown

**Action:** XDF team debugs

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

**XDF-10564: DBUtil::isConsNameInDB: No connection available!**



---

**Cause:** No database connection

**Action:** Fix database connection

**Level:** 1

**Type:** ERROR

**Impact:** Application Diagnostics

