


Anchors	
^	Start of line
\$	End of line

Character Classes	
\s	White space character
\S	Non-white space character
\d	Digit character
\D	Non-digit character
\w	Word
\W	Non-word (e.g. punctuation, spaces)

Metacharacters (must be escaped)	
^	[ ]
\$	( )
.	{ }
*	+ ?
\	-

GA Filter group accessors	
\$Ax	Access group x in field A (e.g. \$A1)
\$Bx	Access group x in field B (e.g. \$B1)

**Cheatographer**



**Jay Taylor** (Jay Taylor)  
[cheatography.com/jay-taylor/](http://cheatography.com/jay-taylor/)  
[www.freshegg.com](http://www.freshegg.com)

Quantifiers	
*	Zero or more (greedy)
*?	Zero or more (lazy)
+	One or more (greedy)
+	One or more (lazy)
?	Zero or one (greedy)
??	Zero or one (lazy)
{X}	Exactly X (e.g. 3)
{X,}	X or more, (e.g. 3)
{X, Y}	Between X and Y (e.g. 3 and 5) (lazy)

Ranges and Groups	
.	Any character
(a b)	a or b (case sensitive)
(...)	Group, e.g. (keyword)
(?...)	Passive group, e.g. (?:keyword)
[abc]	Range (a or b or c)
[^abc]	Negative range (not a or b or c)
[A-Z]	Uppercase letter between A and Z
[a-z]	Lowercase letter between a and z
[0-7]	Digit between 0 and 7

**Cheat Sheet**

This cheat sheet was published on 10th February, 2012 and was last updated on 13th February, 2012.

Sample Patterns	
<code>^/directory/(.*)</code>	Any page URLs starting with /directory/
<code>(brand\s*?term)</code>	Brand term with or without whitespace between words
<code>^brands+[^cf]</code>	Key phrases beginning with 'brand' and the second word not starting with c or f
<code>\.aspx\$</code>	URLs ending in '.aspx'
<code>ORDER\d{6}</code>	"ORDER-" followed by a six digit ID
<code>(?:\? &amp;)utm=([^\&amp;\$]+)</code>	Value of 'utm' querystring parameter

**Sponsor**

**FeedbackFair**, increase your conversion rate today!  
 Try it free!  
<http://www.FeedbackFair.com>