

MODx Evo Doc. Vars

id / parent

pagetitle / menutitle / content

longtitle / alias / introtext / description

pub_date / unpub_date / createdon / editedon / deletedon

published / searchable / cacheable / richtext / dont hit / haskeywords / hasmetatags / privatweb / privatemgr / hidemenu / content_dispo

createdby / editedby / deletedby

menuindex

template

contentType

MODx Evo PHx

date=`dateformat`
| example: [+createdon:date=%d.%m.%Y +]

md5
| returns md5-hash

limit=`length`
| `substr($str,$length)`, default:100

reverse
| reversing letters

wordwrap=`length`

lcase
| example: [+string:lcase+]

ucase
| example: [+string:ucase+]

ucfirst
| example: [+string:ucfirst+]

length | len
| example: [+string:len+]

notags
| example: [+string:notags+]

userinfo=`field`

MODx Evo Wayfinder non-tpl Params

startId
| def. *current doc*

level
| def. 0

limit
| def. 0

sortOrder
| def. ASC, opt: ASC || DESC

sortBy
| def. menuindex

excludeDocs

includeDocs

debug
| def. false

hideSubMenus
| def. false, hides submenus, and shows for cur. item

removeNewLines
| def. false, deletes new line symbol from result

textOfLinks
| def. menutitle, parameter for text of link

titleOfLinks
| def. pagetitle, parameter for title of link

rowIdPrefix
| def. false, inserts prefix for id of each link

useWebLinkUrl
| def. false, outputs full link into [+wf.link+]

showSubDocCount
| def. false, output count of child docs into [+wf.subitemcount+]

ignoreHidden
| def. false

ph
| name of placeholder, which will insert results

MODx Evo Wayfinder tpl Params

outerTpl
| def. [+wf.wrapper+], menu container chunk

rowTpl
| def. [+wf.linktext+][+wf.wrapper+], menu item chunk

parentRowHereTpl
| def. false, active container-document chunk

parentRowTpl
| def. false, container-document *ITEM* chunk

hereTpl
| def. false, current menu chunk

innerTpl
| def. false, all container-documents *CONTAINER* chunk

innerRowTpl
| def. false, submenu item chunk

innerHereTpl
| def. false, current container-document *CONTAINER* chunk

activeParentRowTpl
| def. false, current item parents chunk

categoryFoldersTpl
| def. false, category chunk

firstClass
| def. none, first menu item class

hereClass
| here, current item-chain class

selfClass
| none, current item class

parentClass
| parent, container-documents class

rowClass
| none, all menu-items class

levelClass
| none, each level class

outerClass
| none, container class


innerClass
| none, submenu items class

webLinkClass
| none, links class

cssTpl
| insert css chunk

jsTpl
| insert javascript chunk

Cheatographer



media_slave
cheatography.com/media-slave/

Cheat Sheet

This cheat sheet was published on 28th September, 2012 and was last updated on 29th September, 2012.

Sponsor

FeedbackFair, increase your conversion rate today!
Try it free!
<http://www.FeedbackFair.com>