

Qlikview v10 file handling	
New document	<i>Ctrl+N</i>
Open Document	<i>Ctrl+O</i>
Open Document on server	<i>Ctrl+Shift+N</i>
Save Document	<i>Ctrl+S</i>
Save Document as	<i>F12</i>

Qlikview v10 actions keys	
Print document	<i>ctrl + P</i>
Print as PDF	<i>ctrl + shift + P</i>
Edit script	<i>ctrl + E</i>
Reload data	<i>ctrl + R</i>
Partial reload data	<i>ctrl + shift + R</i>
Table viewer	<i>ctrl + T</i>
Show/Hide grid	<i>ctrl + G</i>
Open User Preferences	<i>ctrl + alt + U</i>
Open Document Properties	<i>ctrl + alt + D</i>
Open Sheet Properties	<i>ctrl + alt + S</i>
Open Variable Overview	<i>ctrl + alt + V</i>
Open Expression Overview	<i>ctrl + alt + E</i>
Properties of the selected object(s)	<i>alt + enter</i>
Edit Module	<i>ctrl + M</i>
Alerts	<i>ctrl + alt + A</i>
Add Bookmark	<i>ctrl + B</i>
More Bookmark	<i>ctrl + shift + B</i>

Qlikview v10 script edition keys	
Go to line number in the script	<i>ctrl + G</i>
List of keyboard shortcuts	<i>ctrl + Q,S,C</i>
Comment lines in script	<i>ctrl + K,C</i>
Uncomment lines in script	<i>ctrl + K,U</i>
Add tab in script	<i>ctrl + Q,T,A</i>
Promote active tab	<i>ctrl + Q,T,P</i>
Demote active tab	<i>ctrl + Q,T,D</i>
Rename active tab	<i>ctrl + Q,T,N</i>
Remove active tab	<i>ctrl + Q,T,R</i>
Creates an autogenerated script	<i>ctrl + Q,Q</i>
Opens Unicode input utility	<i>ctrl + Q,U,I</i>
Creates a script for reading jpg attributes	<i>ctrl + Q,J,P,G</i>
Creates a script for reading mp3 attributes	<i>ctrl + Q,M,P,3</i>
Creates a script for reading wma attributes	<i>ctrl + Q,W,M,A</i>

ctrl + K,C means ctrl + K then ctrl + C

Qlikview v10 edit shortcut keys	
Undo layout change	<i>Ctrl + Z</i>
Redo layout change	<i>Ctrl + Y</i>
Cut	<i>Ctrl + X</i>
Copy	<i>Ctrl + C</i>
Paste	<i>Ctrl + V</i>
Remove	<i>Del</i>
Activate All	<i>Ctrl + A</i>
Find	<i>Ctrl + F</i>
Advanced Find	<i>Shift + Ctrl + F</i>

Qlikview v10 set analysis identifiers	
0	Empty set
1	Full set of all the records
\$	Current selection
\$1	Previous selection
\$_1	Forward selection
Bookmark01	Bookmark ID or name

Qlikview v10 set analysis examples	
<code>sum(sales) or sum({\$} sales)</code>	sales in current selection
<code>sum({1} sales) or sum({1} Total sales)</code>	sales disregarding the selection or disregarding selection and dimension
<code>sum({<OrderDate = DeliveryDate>} sales)</code>	sales in current selection for a specific date
<code>sum({1<Region = {US}>} sales)</code>	total sales for region=US
<code>sum({<Region =>} sales)</code>	sales in selection with region removed (idem \$)
<code>sum({\$<Year={2000}, Region = {"U*"}>} sales)</code>	current selection but year forced to 2000 and region like U*
<code>sum({\$<Year = \${vLastYear}>} sales)</code>	sales related to a variable
<code>p({<Year={\$=max(x(Year)-1)}>} customer)</code>	returns customers who are possible for last year
<code>e({<Year={\$=max(x(Year)-1)}>} customer)</code>	returns customers who are excluded for last year

Qlikview v10 F Keys	
Activates context sensitive help	<i>F1</i>
Enters search mode	<i>F3</i>
Activates the sheet tab to the left of the active one	<i>F6</i>
Activates the leftmost tab	<i>ctrl + F6</i>
Activates the sheet tab to the right of the active one	<i>F7</i>
Activates the rightmost tab	<i>ctrl + F7</i>
Save as	<i>F12</i>

Qlikview v10 set analysis operators	
+	Union
-	Exclusion (first but not the other)
*	Intersection (both)
/	Symmetric difference (either but not both)

Qlikview v10 set analysis modifiers	
<OrderDate = DeliverDate>	Select only data where field1 = field2
<Field = {value}>	Select specific value
<Region = >	Ignore the specific field
<Year={2000}, Region = {"U*"}>	Two fields can be filtered, with wildcards

Cheatographer	
	Frederic Villemin (fredv) cheatography.com/fredv/ www.tasteofindie.com

Cheat Sheet	
This cheat sheet was published on 6th November, 2011 and was last updated on 11th January, 2013.	

Sponsor	
FeedbackFair , increase your conversion rate today! Try it free! http://www.FeedbackFair.com	