

### Constants: Basic Constants

domain	To globally change your domain (to go live for example)
protocol	Globally change your protocol. e.g. from http:// to https://
fileadmin	change the basic path to your fileadmin directory ( <i>fileadmin/old_files</i> to <i>fileadmin/new_files</i> )

### TypoScript: Basic Configuration

```
config {

doctype = html5
xmlprologue = none

baseURL = {$protocol}://{domain}

language = de
locale_all = german
htmlTag_langKey = de
sys_language_uid = 0

# Add L Parameter to links
linkVars := addToList(L)
uniqueLinkVars = 1

# Enable ReaURL
tx_realurl_enable = 1

# Decide for yourself
moveJsFromHeaderToFooter = 0

# AdminPanel on
admPanel = 1

# Pagetitle off
noPageTitle = 2

# Spam-Protection - choose your favorite method
spamProtectEmailAddresses = ascii
}
```

### TypoScript: Change Website Title

```
page.headerData {
10 = TEXT
10 {
field = title
noTrimWrap = |<title>| - Website</title>|
}
}

config.noPageTitle = 2
is mandatory
```

### TypoScript: Fav Icon

```
page.shortcutIcon = {$fileadmin}/favicon.ico
```

### TypoScript: Language Condition

```
[globalVar = GP:L = 1]
config.sys_language_uid = 1
config.language = en
config.locale_all = english
config.htmlTag_langKey = en
[global]
```

### TypoScript: Add Meta-Tag "viewport"

```
page.meta.viewport = width=device-width, initial-scale=1, maximum-scale=1, user-scalable=no
```

### TypoScript: Canonical-Tag

```
page.headerData.930 = TEXT
page.headerData.930 {
typolink {
parameter = {page:uid}
parameter.insertData = 1
useCacheHash = 1
addQueryString = 1
addQueryString.method = GET
addQueryString.exclude = id,no_cache,tt_news[backPid]
returnLast = url
}
wrap = <link rel="canonical" href="{protocol}://{domain}" />
}
```

### TypoScript: Backend Layout

```
page.10 = FLUIDTEMPLATE
page.10 {

# Use the constants in your tpls
variables {
domain = TEXT
domain.value = {$domain}
protocol = TEXT
protocol.value = {$protocol}
fileadmin = TEXT
fileadmin.value = {$fileadmin}
# e.g. for anchor urls
typo3_request_url = TEXT
typo3_request_url.data = getIndpEnv: TYPO3_REQUEST_URL
}

file.stdWrap.cObject = CASE
file.stdWrap.cObject {

key.data = levelfield:-1, backend_layout_next_level, slide
key.override.field = backend_layout

# default template file
default = TEXT
default.value = {$fileadmin}/tpl/default.html
2 = TEXT
2.value = {$fileadmin}/tpl/alt_one.html
3 = TEXT
3.value = {$fileadmin}/tpl/alt_two.html
}
}
```

### Cheatographer



**achjaderleon**  
cheatography.com/achjaderleon/

### Cheat Sheet

This cheat sheet was published on 13th November, 2012 and was last updated on 22nd November, 2012.

### Sponsor

**FeedbackFair**, increase your conversion rate today!  
Try it free!  
<http://www.FeedbackFair.com>